

CASA Service Installation Manual
Oracle FLEXCUBE Universal Banking
Release 14.7.5.0.0
Part No. G14514-01
[September] [2024]



Table of Contents

- 1. **CASA Service Installation Manual**1
 - 1.1 Introduction**1
 - 1.2 Prerequisites**1
 - 1.3 CASA Service**1
 - 1.3.1 Server Setup**2
 - 1.3.2 CASA Service Maintenance**.....4
 - 1.3.3 WAR Deployment**5
 - 1.3.4 Server Restart**5

1. CASA Service Installation Manual

1.1 Introduction

This document provides step-by-step instructions to install CASA services in the Oracle FLEXCUBE server.

1.2 Prerequisites

- Weblogic Domain

1.3 CASA Service

The CASA Services Setup has the following set of services:

- **INFRA Services**
 - **Discovery Service**
 - **Config Service**
- **fcubs-customer-acc-service**
- **fcubs-audit-service**
- **fcubs-smsvalidation-service**
- **fcubs-signature-service**
- **obbrn-casacustomeraccount-services**

The following table describes the services available in the CASA services setup:

Table 1: CASA Service Details

Service		Service Name	Usage
INFRA Services	Discovery	plato-discovery-service	This service is required for registering all the CASA services during start-up. The registered services use the Discovery Service to make inter-service calls.
	Config Service	plato-config-service	This service provides required configuration details for the corresponding CASA services during service start-up, by referring to the database table (Table name: PROPERTIES). The mentioned database table stores all the configuration-related details.

CASA Service	fcubs-customer-account-service	This service fetches and updates details to and from the FLEXCUBE database.
SMS Validation Service	fcubs-smsvalidation-service	The Security Management Service validates the users.
Audit Service	fcubs-audit-service	This service updates audit logs in FLEXCUBE.
Signature Service	fcubs-signature-service	This service fetches and updates details to and from the FLEXCUBE database.
Casacustomeraccount Service	obbrn-casacustomeraccount-services	This service fetches and updates details to and from the FLEXCUBE database for CASA360 screen.

1.3.1 **Server Setup**

Before deploying the CASA services WAR files, the user must set up managed servers for the services.

1. In the Application Server, set up two Managed Servers for **INFRA Service** and **CASA Service**, respectively.
2. Name the Managed Servers as **ConfigServer** and **CasaServer**, respectively.

NOTE: Any name can be provided to the Managed Servers, and the **INFRA Service** and **CASA Service** can be deployed in any corresponding server created for that service.

3. Create the following Data Sources for **INFRA and CASA Services**:

Data Source JNDI Name	Type	Target
jdbc/CSRCASA	Non-XA Datasource	CasaServer
jdbc/PLATO	Non-XA Datasource	ConfigServer

4. Include the following line in **setDomainEnv.cmd** or **setDomainEnv.sh** of the Weblogic domain:

For Linux Server:

Syntax

```
JAVA_OPTIONS="${JAVA_OPTIONS} ${JAVA_PROPERTIES} -Dflyway.enabled=false -Dspring.flyway.enabled=false -Dplato.services.config.uri=http://<config-server-ip>:<config-server-port> -Dplato.service.logging.path=<Debug Path where Logs are to be written>"
```

```
export JAVA_OPTIONS
```

Sample

```
JAVA_OPTIONS="${JAVA_OPTIONS} ${JAVA_PROPERTIES} -Dflyway.enabled=false -  
Dspring.flyway.enabled=false -Dplato.services.config.uri=http://10.10.10.10:1010 -  
Dplato.service.logging.path=/mnt/FC144/CasaLogs"
```

```
export JAVA_OPTIONS
```

For Windows Server:

Syntax

```
set JAVA_OPTIONS=%JAVA_OPTIONS% %JAVA_PROPERTIES% -  
Dplato.services.config.uri=http://<config-server-ip>:<config-server-port> -Dflyway.enabled=false -  
Dspring.flyway.enabled=false -Dplato.service.logging.path=<Debug Path where Logs are to be  
written>
```

Sample

```
set JAVA_OPTIONS=%JAVA_OPTIONS% %JAVA_PROPERTIES% -Dflyway.enabled=false -  
Dspring.flyway.enabled=false -Dplato.services.config.uri=http://whf00bir:9005 -  
Dplato.service.logging.path=D:/CasaLogs
```

NOTE: If the Node-Manager is used to start the Managed Servers, the user can navigate to Servers > Managed Server > Server Start and set parameters specific to the Managed Server in the argument section.

1.3.2 **CASA Service Maintenance**

After setting up the Managed Servers for the **CASA Services**, the services must be enabled in the **FCUBS Maintenance** page.

Specify **User ID** and **Password** and login to **Homescreen**.

1. On **Homescreen**, specify **CSDPROPM** in the text box, and click **Next**.

Amend Service Properties screen displays.

Figure 1: Amend Service Properties

Amend Service Properties

Enter Query

Reference Number

Service URL

Service Port

Level ☐ Service ☐ All

Service Name

Service Details

No data to display.

Page 1 (0 of 0 items) |< < 1 > >|

Audit Exit

2. On **Amend Service Properties** screen, click **Unlock** at the top left corner.
3. Specify the **Reference Number** from the list of values.
4. Specify the **Service URL**.

Service URL Syntax:

`http://<config-server-ip>:<config-server-port>/plato-discovery-service/eureka`

Service URL Sample:

`http://10.10.10.10:1010/plato-discovery-service/eureka`

5. Specify the port of Managed Server (**CasaServer**) in the **Service Port** field.
6. Click **Save**.

1.3.3 WAR Deployment

While creating an FCUBS EAR build, CASA and INFRA war files are automatically copied into the destination location through the installer along with FCUBS EAR. After completing the build creation, the following files will be available in the destination folder:

- **FCUBS Application EAR and All Adapter EAR**
- **INFRA Service WAR**
- **CASA Service WAR**

1. Navigate to INFRA in the destination folder and copy the following **INFRA Service WAR** files:
 - **plato-discovery-services-7.2.0.war**
 - **plato-config-services-7.2.0.war**
2. Deploy the copied **INFRA Service WAR** files in the **ConfigServer**.
3. Navigate to the **OBBRN > CASA** in the destination folder and copy the **CASA Service WAR** files.
4. Deploy the copied **CASA Service WAR** files in the **CasaServer**.

1.3.4 Server Restart

After deploying the CASA Services or restarting the Application server, start the services in the following sequence:

- **plato-config-service**
- **plato-discovery-service**
- **fcubs-customer-acc-service**
- **fcubs-audit-service**
- **fcubs-smsvalidation-service**
- **fcubs-signature-service**
- **obbrn-casacustomeraccount-services**

NOTE:

- After restarting the Application server, start the **ConfigServer** first and then start the **CasaServer**.
- To enable the **Discovery Service** to fetch properties entries for self-registration from **plato-config- service**, **plato-discovery-service** must be stopped and started whenever the **ConfigServer** is restarted.

The deployed CASA services are listed in the service discovery URL. To confirm the running status of all the services, check the service discovery URL.

Service Discovery URL Syntax:

http://<config-server-ip>:<config-server-port>/plato-discovery-service

Service Discovery URL Sample

`http://10.10.10.10:1010/plato-discovery-service`



CASA Service Installation Guide

[September] [2024]
Version 14.7.5.0.0

Oracle Financial Services Software Limited
Oracle Park
Off Western Express Highway
Goregaon (East)
Mumbai, Maharashtra 400063
India

Worldwide Inquiries:
Phone: +91 22 6718 3000
Fax: +91 22 6718 3001
<https://www.oracle.com/industries/financial-services/index.html>

Copyright © [2007], [2024], Oracle and/or its affiliates. All rights reserved.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

U.S. GOVERNMENT END USERS: Oracle programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, delivered to U.S. Government end users are "commercial computer software" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, shall be subject to license terms and license restrictions applicable to the programs. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate failsafe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

This software or hardware and documentation may provide access to or information on content, products and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services.