

# **Oracle® Communications Network Charging and Control**

Upgrade Operations Guide

Release 6.0.1

April 2017

# Copyright

Copyright © 2017, Oracle and/or its affiliates. All rights reserved.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this is software or related documentation that is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, then the following notice is applicable:

U.S. GOVERNMENT END USERS: Oracle programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, delivered to U.S. Government end users are "commercial computer software" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, shall be subject to license terms and license restrictions applicable to the programs. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Xeon are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. AMD, Opteron, the AMD logo, and the AMD Opteron logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark of The Open Group.

This software or hardware and documentation may provide access to or information about content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services unless otherwise set forth in an applicable agreement between you and Oracle. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services, except as set forth in an applicable agreement between you and Oracle.

# Contents

About This Document .....	v
Document Conventions .....	vii
<b>Chapter 1</b>	
<b>Introduction to Upgrading .....</b>	<b>1</b>
Overview .....	1
About the Upgrade .....	1
<b>Chapter 2</b>	
<b>About the Upgrade Process .....</b>	<b>5</b>
Overview .....	5
Upgrade Process Overview .....	5
About Configuring Replication .....	6
About Service Interruption .....	6
<b>Chapter 3</b>	
<b>Preparing for the Upgrade .....</b>	<b>9</b>
Overview .....	9
Backing Up Database Tables and Ensuring Their Integrity .....	9
Preparing Upgrade Configuration Files .....	10
Unpacking the Patches .....	11
<b>Chapter 4</b>	
<b>Upgrading Oracle Communications Network Charging and Control</b>	<b>15</b>
Overview .....	15
About Upgrading .....	15
Using GNU Screen .....	17
Manually Configuring Replication .....	17
Upgrading the VWS .....	22
Upgrading the SLC .....	28
Upgrading the SMS .....	33
Migrating balance-related AVP Mappings .....	38
<b>Chapter 5</b>	
<b>Rolling Back the Upgrade .....</b>	<b>41</b>
Overview .....	41
About Rolling Back the Upgrade .....	41
Rolling Back the SMS Upgrade .....	42
Rolling Back the SLC Upgrade .....	46
Rolling Back the VWS Upgrade .....	48

## Appendix A

<b>Example of sms.jnlp file .....</b>	<b>55</b>
<b>Glossary of Terms .....</b>	<b>57</b>
<b>Index .....</b>	<b>65</b>

# About This Document

## Audience

This guide is for system administrators who upgrade the NCC platform.

## Scope

This document includes all the information required to upgrade the Oracle Communications Network Charging and Control (NCC) platform.

## Prerequisites

Before upgrading NCC, you should have a solid understanding of UNIX, Oracle Solaris, and Oracle Solaris Cluster, and a familiarity with IN concepts as well as an understanding of Oracle databases, Oracle Real Application Clusters (Oracle RAC), SQL, and PL/SQL. Attempting to upgrade the NCC system without the appropriate background skills could damage the system; including causing temporary or permanent incorrect operation, loss of service, or rendering your system beyond recovery.

This guide describes system tasks that should be carried out only by suitably trained operators.

## Ways to configure replication

You configure replication when you upgrade the SMS nodes. You can configure replication in two ways:

- By using the SMS UI. This results in all replication processes (`updateLoader`, `smsStatsDaemon`, `smsAlarmDaemon`, `replicationIF`) reconnecting at the same time, and therefore can be difficult to monitor.
- By using a command line interface to manually create a new **replication.config** file and then manually stopping and restarting the processes one by one. This provides more control and easier monitoring, and no SMS UI access is required.

Instructions on how to configure replication by using the SMS UI are provided in *Upgrading the SMS* (on page 33). For more detailed information about configuring replication by using the SMS UI, see *NCC Service Management System User's Guide*. For instructions on manually configuring replication from a command line, see *Manually Configuring Replication* (on page 17).

## Patch contents

When you unpack a patch **.zip** file, a directory is created for each component. Under that directory, a subdirectory is created for the patch; for example, the following directory is created for the SMS:

### SMS/PATCH23253932

Each subdirectory contains the patches for that component that you install when you upgrade the nodes. See *Where to install patches* (on page 12) for details of where each component patch should be installed. Additional information about the release is included in the readme text file for the SMS patch.

## Example

This example shows the patches and readme text file for the SMS component from the unpacked **NCC\_6\_0\_1\_0\_0-PATCH23253932\_svr4\_vX\_Y.zip** file:

```
# ls -l PATCH23253932
P23253932EXT
P23253932SCP
P23253932SMS
Patch23253932_v1_0_README.txt
```

**Notes:**

- Always carefully study the readme text file for the SMS patch prior to proceeding with the upgrade. This file contains additional information about the release.
- For information on how to unpack the patch .zip file, see *Unpacking the patch file* (on page 12).

**Related Documents**

See the following documents for information about installing and managing NCC:

- *Installation Guide*
- *System Administrator's Guide*
- *Configuration User's Guide*
- *Service Management System User's Guide*

# Document Conventions

## Typographical Conventions

The following terms and typographical conventions are used in the Oracle Communications Network Charging and Control (NCC) documentation.

Formatting Convention	Type of Information
<b>Special Bold</b>	Items you must select, such as names of tabs. Names of database tables and fields.
<i>Italics</i>	Name of a document, chapter, topic or other publication. Emphasis within text.
<b>Button</b>	The name of a button to click or a key to press. <b>Example:</b> To close the window, either click <b>Close</b> , or press <b>Esc</b> .
<b>Key+Key</b>	Key combinations for which the user must press and hold down one key and then press another. <b>Example:</b> <b>Ctrl+P</b> or <b>Alt+F4</b> .
Monospace	Examples of code or standard output.
<b>Monospace Bold</b>	Text that you must enter.
<i>variable</i>	Used to indicate variables or text that should be replaced with an actual value.
menu option > menu option >	Used to indicate the cascading menu option to be selected. <b>Example:</b> <b>Operator Functions &gt; Report Functions</b>
<a href="#">hypertext link</a>	Used to indicate a hypertext link.

Specialized terms and acronyms are defined in the glossary at the end of this guide.





# Introduction to Upgrading

## Overview

### Introduction

This chapter describes the Oracle Communications Network Charging and Control (NCC) components that are upgraded and makes general recommendations.

### In this chapter

---

This chapter contains the following topics.

About the Upgrade ..... 1

## About the Upgrade

### Releases upgraded

Upgrading to NCC release 6.0.1 upgrades the NCC platform from NCC 6.0.0.

### NCC node upgrade order

You upgrade each node on the NCC platform independently and sequentially in three phases:

- 1 Upgrade each Voucher and Wallet Server (VWS) pair in this order: secondary node, then primary node.
- 2 Upgrade all Service Logic Controller (SLC) nodes, one by one.
- 3 Upgrade the Service Management System (SMS).

**Note:** Service-critical functions remain available through redundant peer nodes during the upgrade process.

### NCC components upgrade table

The NCC upgrade to release 6.0.1 is composed of a number of NCC component patches.

**Warning:** If a particular component is not installed on your system, omit the patch for that component from the upgrade.

The following table lists the NCC components patched with this upgrade, the upgrade patch numbers, the name of the base packages for the nodes on which you install each component patch, and the prerequisite patch numbers.

When you upgrade a node, install each component patch or package on the node in the order listed in the column for the node's base packages. Before you install a component patch on a node, check that the prerequisite patch is already installed. For example, the P21489970SMS patch is the prerequisite for the P23253932SMS patch on the SMS node. A corresponding prerequisite patch must exist for each component patch.

For more information about the contents of the patch, see *Patch contents* (on page v). For information about where to install component patches, see *Where to install patches* (on page 12).

**Note:**

- The prerequisite patch numbers are not applicable if the previous release was a fresh install using the Oracle Universal Installer (the installer).
- NA in the column for the node means that this component should not be installed on this node.

Component	Upgrade Patch Number or Package	SMS Base Package	VWS Base Package	SLC Base Package	Prerequisite 6.0.0 Patch Number
SMS	23253932	smsSms efmSms	smsExtras	smsScp	21489970
SLEE	23253922	NA	SLEE	SLEE	21489966
BE	23248169	beSms	beBe	beScp	21489680
ACS	23248130	acsSms	acsBe	acsScp	21489661
OSD	23253855	osdSms	NA	osdScp	21489931
PI	23253869	piSms	NA	NA	21489935
DAP (SMS and SLC only)	23248281	dapSms	NA	dapScp	21489726
CCS	23248224	ccsSms ccsDapSms	ccsBe	ccsScp	21489701
DAP (VWS only)	23248281	NA	dapExtras	NA	21489726
CCSCDRPART	23248229	ccsCdrPart	NA	NA	21489706
CCSVCHRPART	23248236	ccsVchrPart	NA	NA	21489713
DCD	23248287	dcdSms	NA	dcdScp	21489741
DCA	23248284	dcaSms	NA	dcaScp	21489734
ECA	23248292	ecaSms	NA	ecaScp	214897644
LCP	23248304	lcpSms	NA	lcpScp	21489757
RCA	23253878	rcaSms	NA	rcaScp	21489938
MOB_ROAM	23248305	roamingSms	NA	roamingScp	21489823
RIMS	23253884	rimsSms	NA	rimsScp	21489939
XMS	23254038	xmsSms	NA	xmsScp	21490008
CCS_SMCB	23248219	smcbSms	NA	smcbScp	21489700
SEI	23253889	NA	NA	seiScp	21489942
SES	23253899	sesSms	NA	sesScp	21489953
SIGTRAN	23253905	sigtranSms	NA	sigtranScp	21489955
IS41 (CDMA_GW)	23248300	cdmaSms	NA	cdmagw	21489753
TFR	23254001	NA	NA	tfr	21489988
SCA (SIP)	23253912	scaSms	NA	scaScp	21489958
UIS (USSD_GW)	23254007	uisSms	NA	uisScp	21489993

Component	Upgrade Patch Number or Package	SMS Base Package	VWS Base Package	SLC Base Package	Prerequisite 6.0.0 Patch Number
UPC (USSD_GW)	23254016	upcSms	NA	upcScp	21490000
VPN	23254022	vpnSms	NA	vpnScp	21490002
XMLTCIF (SLEE_TC)	23253916	NA	NA	xmlTclf	21489961
CAP3_GW	23248194	capgwSms	NA	capgwScp	21489691
SMSC	23253944	NA	NA	SMSC	21489972
NP (NP_SERVICE_PACK)	23253848	npSms npPISms	NA	npScp	21489930
ENUM	23248294	enumSms enumPISms	NA	enumScp	21489751
CCSPI	23248245	piCcsSms piSubscriberSms piWalletSms piVouchersms piSrmSms	NA	NA	21489720
ACSPI	23248147	piAcsSms	NA	NA	21489672
VPNPI	23254030	piVpnSms	NA	NA	21490004
XMSPI	23254043	piXmsSms	NA	NA	21490013
VSSP	23254035	vsspSms	NA	VSSP	21490005
BCD	23248156	bcdSms	NA	bcdScp	21489676
CAP3GPRS (CAP3GPRS Control Agent)	23248182	cap3gprsSms	NA	cap3gprsScp	21489683
NGW (Notifications Gateway)	23253837	NA	NA	ngwScp	21489827
MFWD	24761834	NA	NA	NA	NA
SUPPORT	23253951	supportSms	SupportBe slee-ctrl	supportScp slee-ctrl	21489974

## About backward compatibility

The NCC application and upgrade patches are backward compatible. For example, backwards compatibility is maintained between:

- SLC and VWS nodes
- Primary and secondary VWS nodes

## General recommendations

Upgrading an environment of NCC is a complex process.

You should:

- Carefully study this upgrade guide, the updated NCC 6.0.1 user documentation, and the patch readme text file. See *NCC Release Notes* for a list of the updated documentation.
- Prepare a detailed step-by-step upgrade plan specific to the target environment being upgraded.
- Validate and rehearse the upgrade on a test environment that replicates your production system.
- Ensure a validated backup and restore process is in place for the production environment prior to proceeding with the upgrade.

# About the Upgrade Process

## Overview

### Introduction

This chapter describes the stages of a complete Oracle Communications Network Charging and Control (NCC) end-to-end upgrade process and the general tasks you perform at each stage.

### In this chapter

---

This chapter contains the following topics.

Upgrade Process Overview .....	5
About Configuring Replication .....	6
About Service Interruption .....	6

## Upgrade Process Overview

### About upgrade stages

There are two main stages to upgrading NCC: preparation and upgrade. Each stage includes a series of tasks you perform.

### Preparation stage

You perform the following tasks to prepare the system for upgrade:

- Back up the NCC databases and ensure database integrity.  
You can use the backup files to roll back the upgrade if necessary. You ensure database integrity by making sure triggers and constraints are enabled. This ensures that any operations that could corrupt the database are aborted.
- Back up configuration files and create new configuration files for the upgrade.
- Download and unpack the upgrade patch files on the target system.
- Update the replication configuration for changes to the tables replicated.

For instruction on the preparation tasks, see *Preparing for the Upgrade* (on page 9).

### Upgrade stage

When you upgrade NCC, you upgrade the Service Management System (SMS), Voucher and Wallet Server (VWS), and Service Logic Controller (SLC) nodes independently. The overall steps to upgrading a node include stopping processes on the node, installing upgrade patches, adding upgrade configuration files, and restarting processes on the node. Upgrading VWS and SLC nodes include additional steps specific to those types of nodes. The upgrade patches update the database schema and data and the NCC software.

**Note:** Service-critical functions remain available through redundant peer nodes during the upgrade process.

You upgrade the nodes on the NCC platform in three phases:

- 1 Upgrade each VWS node pair.  
Sequentially upgrade each VWS pair. Upgrade one VWS pair at a time. Within a VWS pair, upgrade the secondary and then the primary VWS separately. This allows for continuous service with minimal interruption because at least one VWS is always available.
- 2 Upgrade SLC nodes.  
Upgrading SLC nodes is very similar to upgrading VWS nodes: while the peer SLC nodes are handling all production traffic, you can upgrade another SLC.
- 3 Upgrade the SMS.

For instructions on upgrading the NCC nodes, see *Upgrading Oracle Communications Network Charging and Control* (on page 15).

### Making sure VWS and SLC nodes are stable during the upgrade

You can minimize interruptions to service by ensuring that each node is stable before upgrading the next node. For example, when upgrading a VWS pair, you can follow this process:

- Upgrade the secondary VWS node.
- Wait while traffic is moved to the secondary VWS node.
- Monitor the secondary VWS node to make sure it is working correctly.
- Upgrade the primary VWS node and repeat the process.

You follow a similar process when upgrading SLC nodes.

If you have more than one pair of VWS nodes, you can upgrade a VWS pair and then wait for a period of time, such as one or two days, before upgrading the next pair. This can help you to manage interruptions to services; for example, when different VWS node pairs provide different services.

## About Configuring Replication

### Ways to configure replication

You configure replication when you upgrade the SMS nodes. You can configure replication in two ways:

- By using the SMS UI. This results in all replication processes (`updateLoader`, `smsStatsDaemon`, `smsAlarmDaemon`, `replicationIF`) reconnecting at the same time, and therefore can be difficult to monitor.
- By using a command line interface to manually create a new `replication.config` file and then manually stopping and restarting the processes one by one. This provides more control and easier monitoring, and no SMS UI access is required.

Instructions on how to configure replication by using the SMS UI are provided in *Upgrading the SMS* (on page 33). For more detailed information about configuring replication by using the SMS UI, see *NCC Service Management System User's Guide*. For instructions on manually configuring replication from a command line, see *Manually Configuring Replication* (on page 17).

## About Service Interruption

### About minimizing the impact of service interruption

During the upgrade, system availability will be impacted. The upgrade process is designed to retain end user service to a maximum degree during the upgrade. This is particularly important when upgrading the VWS and SLC nodes because these are the key elements providing end user service.

**Note:** At various times when individual nodes are being upgraded, capacity is reduced. Depending on how redundancy has been configured, the failover for SLC nodes is reduced or does not exist.

## Service interruption on SMS

During the upgrade, you stop the NCC application processes. This means that all services and functions running from the SMS node will be interrupted until the processes are restarted.

Services interruption on the SMS occurs only while you upgrade the SMS node. The services and functions interrupted depend on the environment specific configuration. This list gives typical services and functions that will be interrupted:

- SMS UI access
- Provisioning Interface (PI) access
- Downstream replication to VWS and SLC nodes
- VWS call detail record (CDR) processing
- Update requests from VWS and SLC nodes: this includes Subscriber Self Management, which is executed from SLC control plans.

**Note:** Update requests will be queued during the upgrade and processed after the interruption.

## Minimizing service interruption on VWS

During the upgrade, service interruption on the VWS is minimized by the following two features:

- Backward compatibility between NCC 6.0.1 VWS nodes and NCC 6.0 SLC nodes for the releases upgraded. See *Releases upgraded* (on page 1). This means you can upgrade all VWS nodes while the SLC nodes remain operational.
- Backward compatibility between the NCC 6.0.1 and NCC 6.0 VWS synchronization processes. This means you can upgrade one node of a VWS pair while the other node continues to process traffic. When the first node is upgraded, the VWS node pair resynchronizes. You can then upgrade the second node while the first node processes traffic.

## Minimizing service interruption on SLC

The following attributes of the SLC allow you to perform a phased upgrade of all SLC nodes with no or minimal service interruption:

- Independence: SLC nodes do not interact with each other.
- Redundancy: where each network function is supported on multiple redundant SLC nodes in an N+1 or better configuration.

**Note:** The specific redundancy configuration deployed will determine the number of SLC nodes that can be taken out of service and upgraded simultaneously.





# Preparing for the Upgrade

## Overview

### Introduction

This chapter explains the tasks that you must perform before upgrading Oracle Communications Network Charging and Control (NCC).

### In this chapter

---

This chapter contains the following topics.

Backing Up Database Tables and Ensuring Their Integrity .....	9
Preparing Upgrade Configuration Files .....	10
Unpacking the Patches.....	11

## Backing Up Database Tables and Ensuring Their Integrity

### Introduction

Before you upgrade, you must ensure that data is backed up by performing a full database backup. You should use the mechanism normally used when performing system maintenance to back up the NCC database. The backup should be scheduled to run immediately before commencing this patch upgrade.

You should also ensure that the integrity of the database is maintained during the upgrade.

### Ensuring database integrity

You must verify that application triggers and constraints are enabled on all Service Management System (SMS), Voucher and Wallet Server (VWS) and Service Logic Controller (SLC) nodes to ensure:

- The integrity of the database is maintained during the upgrade
- No problems occur during the upgrade due to triggers and constraints having become accidentally disabled

Repeat these steps on each node to verify that application triggers and constraints are enabled.

Step	Action
1	Log in to the node as the oracle user.
2	<p>Enter the following commands to verify that triggers and constraints are enabled:</p> <pre>sqlplus '/ as sysdba' select table_name, constraint_name,status from dba_constraints where status != 'ENABLED' and owner != 'SYSTEM' and owner != 'SYS'; select table_name, trigger_name,status from dba_triggers where status != 'ENABLED' and owner != 'SYSTEM' and owner != 'SYS';</pre> <p><b>Result:</b> If no rows are returned, all triggers and constraints are enabled. If any triggers or constraints are returned, contact your database administrator for assistance.</p>

# Preparing Upgrade Configuration Files

## Introduction

The NCC 6.0.1 release notes include information about new and updated configuration. Review the release notes for any configuration file changes or additions. You will prepare updated configuration files that include all the configuration changes relevant to you, and you will copy these files into place during the upgrade.

To prepare updated configuration files, perform the following tasks:

- 1 Back up the existing configuration files on all nodes. See *Backing up configuration files* (on page 10).
- 2 Copy the existing configuration files to a new location and update the configuration files in the new location with the configuration changes. See *Preparing new configuration files* (on page 11).

**Note:** Some patches automatically update the configuration files with configuration changes. After installing the upgrade patches on a node, you must review the existing configuration files for additional configuration updates and apply these updates to the configuration files in the new location.

## Backing up configuration files

Follow these steps on all SMS, VWS, and SLC nodes in turn to back up the old configuration files.

Step	Action
1	Create a backup directory on the node: <code>mkdir -p /IN/service_packages/NCC601UP/config/old/</code>
2	Copy the existing configuration files to the backup directory by entering the following command for each file: <code>cp /IN/service_packages/<i>config_file_name</i> /IN/service_packages/NCC601UP/config/old/<i>backup_config_file_name</i></code> where: <ul style="list-style-type: none"> <li>• <i>config_file_name</i> is the name of the configuration file</li> <li>• <i>backup_config_file_name</i> is the name you give the configuration file</li> </ul> Back up the following configuration files on the specified nodes: <ul style="list-style-type: none"> <li>• <b>eserv.config</b> on all nodes</li> <li>• <b>SLEE.cfg</b> on VWS and SLC nodes</li> <li>• <b>acs.conf</b> on SLC nodes</li> </ul> Give the backup files meaningful names. For example, <b>eserv.config_pre_NCC601</b> .
3	Copy the existing .html and .jnlp files to the backup directory on the SMS node by entering the following command: <code>cp /IN/html/<i>file_name</i> /IN/service_packages/NCC601UP/config/old/<i>backup_file_name</i></code> where: <ul style="list-style-type: none"> <li>• <i>file_name</i> is the name of the .html or .jnlp file</li> <li>• <i>backup_file_name</i> is the name you give the .html or .jnlp file</li> </ul> Back up the following files on the SMS node: <ul style="list-style-type: none"> <li>• <b>acs.jnlp</b>, <b>ccp.jnlp</b>, <b>sms.jnlp</b>, and <b>vpn.jnlp</b></li> <li>• <b>acs.html</b>, <b>sms.html</b>, and <b>vpn.html</b></li> </ul>

## Preparing new configuration files

Follow these steps on all nodes to create new versions of the configuration files that have changes or additions.

Step	Action
1	Make a new directory for the configuration files that you will be updating: <code>mkdir -p /IN/service_packages/NCC601UP/config/new/</code>
2	Go to the new directory.
3	Copy the existing configuration files to the new directory by entering the following command for each file: <code>cp /IN/service_packages/config_file_name .</code> where <i>config_file_name</i> is the configuration file name.
4	Use a text editor such as vi to update the configuration files in the new directory.
5	Edit existing <b>sms.jnlp</b> and <b>sms.html</b> files, and do the following: <ul style="list-style-type: none"> <li>Remove <code>&lt;jar href="xmlpublic.sig.jar"/&gt;</code></li> <li>Remove <code>&lt;jar href="xbean.sig.jar"/&gt;</code></li> <li>Remove <i>applet-desc</i> info and add the following: <code>&lt;application-desc main-class="UserScreens.Application" /&gt;</code> For guidance on where to add this command, see <i>Example of sms.jnlp file</i> (on page 55).</li> <li>Do one of the following:               <ol style="list-style-type: none"> <li>If the <i>param name</i> contains ORB_HOST, replace <code>&lt;param name="xxxx"yyyy&gt;</code> with <code>&lt;property name="jnlp.xxxx" yyyy&gt;</code></li> <li>If the <i>param name</i> does not contain ORB_HOST, replace <code>&lt;param name="xxxx"yyyy&gt;</code> with <code>&lt;property name="jnlp.aaa.xxxx" yyyy&gt;</code> where <i>aaa</i> is the application (sms, acs, ccs, vpn, or osd).</li> </ol> </li> </ul> For the guidance on the application to use, see <i>Example of sms.jnlp file</i> (on page 55).

## Unpacking the Patches

### Patch contents

When you unpack a patch .zip file, a directory is created for each component. Under that directory, a subdirectory is created for the patch; for example, the following directory is created for the SMS:

**SMS/PATCH23253932**

Each subdirectory contains the patches for that component that you install when you upgrade the nodes. See *Where to install patches* (on page 12) for details of where each component patch should be installed. Additional information about the release is included in the readme text file for the SMS patch.

### Example

This example shows the patches and readme text file for the SMS component from the unpacked **NCC\_6\_0\_1\_0\_0-PATCH23253932\_svr4\_vX\_Y.zip** file:

```
# ls -l PATCH23253932
P23253932EXT
P23253932SCP
P23253932SMS
Patch23253932_v1_0_README.txt
```

**Notes:**

- Always carefully study the readme text file for the SMS patch prior to proceeding with the upgrade. This file contains additional information about the release.
- For information on how to unpack the patch .zip file, see *Unpacking the patch file* (on page 12).

**Where to install patches**

The following table lists the type of node on which to install the different patches for each component. The type of node is indicated by the letters at the end of the patch filename.

**Example**

**P23253932SMS** should be installed on the SMS node.

If the Patch Filename Ends In	Install on This Type of Node
SMS	SMS. If the SMS is a cluster, install on both cluster nodes.
EFM	SMS. If the SMS is a cluster, install on both cluster nodes.
SCP	SLC
SCS	SLC
EXT	VWS
BE	VWS
SLEE	SLC and VWS

**Unpacking the patch file**

You unpack the patches for NCC release 6.0.1 on all SMS, VWS, and SLC nodes. Before unpacking the patch files, ensure you have the following disk space available on each node:

- 3 GB of disk space for unpacking the patches. You can unpack the patches in any location. However, this document assumes the patches will be unpacked in the `/var/spool/pkg/NCC601` directory:
- 2 GB of disk space to install the patches on each node in the `/IN` directory.

Follow these steps to unpack the patches.

Step	Action
1	<p>Download the NCC 6.0.1 patches contained within the patch .zip file to the <code>/var/spool/pkg/NCC601</code> directory. The patch files are available from the Oracle Support website, located at <a href="https://support.oracle.com">https://support.oracle.com</a>.</p> <p><b>Note:</b> The patch number for NCC 6.0.1 is 23248120.</p>
2	<p>Go to the patch directory and as the root user, enter the following command to unzip all patches:</p> <pre>unzip filename.zip</pre> <p>where <i>filename</i> is the name of the patch .zip file.</p> <p><b>Result:</b> Creates a component directory for each patch, containing the component ZIP file.</p> <p><b>Example:</b></p> <pre>SMS/NCC_6_0_1_0_0-23253932_svr4_v1_0.zip SLEE/NCC_6_0_1_0_0-PATCH23253922_svr4_v1_0.zip ...</pre>

Step	Action
3	<p>Extract the patches from the <b>.zip</b> file: <code>./extract_patches.sh</code></p> <p><b>Result:</b> All the patches are extracted to their component directory.</p> <p><b>Example:</b></p> <p><b>SMS/PATCH23253932</b> <b>SLEE/PATCH23253922</b> ...</p>
4	<p>For each component being patched, ensure that the prerequisites are satisfied. For information about the prerequisite packages and prerequisite patch numbers, see <i>NCC components upgrade table</i> (on page 1).</p>



# Upgrading Oracle Communications Network Charging and Control

## Overview

### Introduction

This chapter explains how to install the Oracle Communications Network Charging and Control (NCC) upgrade patches and then upgrade the Service Management System (SMS), Service Logic Controller (SLC), and Voucher and Wallet Server (VWS).

### In this chapter

---

This chapter contains the following topics.

About Upgrading.....	15
Using GNU Screen .....	17
Manually Configuring Replication .....	17
Upgrading the VWS .....	22
Upgrading the SLC .....	28
Upgrading the SMS .....	33
Migrating balance-related AVP Mappings .....	38

## About Upgrading

### Upgrade order

Installing the upgrade requires each node of the NCC platform to be upgraded independently and sequentially in the following order:

- 1 Upgrade each VWS pair in this order: secondary node, then primary node.
- 2 Upgrade all SLC nodes, one by one.
- 3 Upgrade the SMS nodes.

### Upgrading an individual node

Upgrading an individual node typically consists of the following high level steps:

- 1 Shut down the NCC application processes.
- 2 Install the NCC upgrade patches on the node, one by one, in the order listed in the *NCC components upgrade table* (on page 1).  
Component patches that come later in the installation order require the preceding patches to be installed first. For example, the BE patch must be installed after the SMS and SLEE patches have been installed.
- 3 Restart the NCC application processes on the node.

**Note:** Service-critical functions remain available through redundant peer nodes during the upgrade process.

## About upgrading the NCC remote database

If you are using a remote database for NCC, you can perform the upgrade only if the Oracle sys user is able to log in to the database on the remote machine as sysdba.

Before you upgrade to NCC release 6.0.1, check whether the Oracle sys user can log in to the database as sysdba on the remote machine. Set up the TWO\_TASK environment variable to point to the remote database machine, and then enter the following command as the smf\_oper user:

```
sqlplus "sys/password as sysdba"
```

where *password* is the password for the sys user. If the SQL prompt appears, the sys user can log in as sysdba and no configuration is necessary.

If the SQL prompt does not appear, perform the following steps on the remote database machine where the database is installed:

Step	Action
1	<p>As the oracle user, create a password file by entering the following command:</p> <pre>orapwd file= \$ORACLE_HOME/dbs/orapwSID entries=10 force=n ignorecase=y nosysdba=n</pre> <p>where <i>SID</i> is the SID for the SMF database. The prompt for the sys user password appears.</p>
2	<p>As the oracle user, enter the following SQL query to determine whether the Oracle database instance is started using spfile:</p> <pre>show parameter spfile;</pre> <p>The Oracle database instance is started by spfile if the query returns no values.</p>
3	<p>Set the <code>remote_login_passwordfile</code> parameter to EXCLUSIVE by doing one of the following:</p> <ul style="list-style-type: none"> <li> <p>If the Oracle database instance is not started by spfile, update the <code>\$ORACLE_HOME/dbs/initSID.ora</code> file to include the following line:</p> <pre>remote_login_passwordfile = EXCLUSIVE</pre> <p>where <i>SID</i> is the SID for the SMF database.</p> </li> <li> <p>If the Oracle database instance is started by using spfile, enter the following commands:</p> <pre>sqlplus "/ as sysdba" alter system set remote_login_passwordfile=exclusive scope=spfile;</pre> </li> </ul>
4	Restart the database by using the dbshut and dbstart commands.
5	<p>As the oracle user, grant sysdba to the sys user by entering the following commands:</p> <pre>\$ sqlplus "/ as sysdba"; grant sysdba to sys;</pre>
6	<p>Recheck that the Oracle sys user can log in to the database as sysdba on the remote machine by entering the following command as the smf_oper user:</p> <pre>sqlplus "sys/password as sysdba"</pre> <p>where <i>password</i> is the password for the Oracle sys user. The SQL prompt appears.</p>



## Using GNU Screen

### About using GNU Screen

Use GNU Screen or a similar tool to perform every upgrade-related action on any NCC node. After installing GNU Screen, start a new screen session each time you perform an upgrade action. For example, start a screen session before installing a package on a node and running its configuration script.

Using GNU Screen ensures that shell sessions do not hang if there are any network connection issues between the session client and the telnet or ssh server on the node being upgraded. Using GNU Screen ensures that you can recover the shell session if the network connection is lost, and that any processes you were running in that shell session will not be stopped or left hanging.

### Using GNU Screen for a shell session

Follow these steps to start a GNU Screen session to perform upgrade-related actions on a node of NCC.

**Note:** You must have already installed GNU Screen on the system.

Step	Action
1	Log in as the root user.
2	Enter <b>screen</b> at the command line.
	<p><b>Tips:</b></p> <ul style="list-style-type: none"> <li>To see all screen sessions, enter: <b>screen -ls</b></li> <li>If the connection is lost, re-attach to the screen session by entering: <b>screen -DR id</b></li> </ul> <p>where <i>id</i> is the session ID.</p>
3	When the upgrade action completes, exit the screen session by using the standard exit command.
	<b>Note:</b> For more information about GNU Screen, see the GNU Screen user documentation.

## Manually Configuring Replication

### About replication configuration

You configure replication at specific points during the upgrade process.

You can configure replication automatically by using the SMS UI or manually configure replication from a command line. This section describes how to configure replication from a command line.

For more information, see *About Configuring Replication* (on page 6).

Instructions on how to configure replication by using the SMS UI are included in *Upgrading the SMS* (on page 33). If you choose to configure replication manually, perform the following tasks instead of using the SMS UI when you upgrade the SMS nodes.

To manually configure replication and stop and restart the replication process, you perform the following tasks.

Step	Action
1	Verify that the replication processes are running. See <i>Verifying that replication is running</i> (on page 18).
2	Configure replication. See <i>Configuring replication from the command line</i> (on page 18).
3	Stop and restart the replication processes. See <i>Stopping and starting replication processes</i> (on page 19).
4	Verify that the replication processes are running.

## Verifying that replication is running

You verify replication is running to ensure it is working before you modify the replication configuration. Then, if any problems occur when you restart replication, you will know that the problems have been caused by the modifications, and not as a result of a pre-existing problem.

Follow these steps on all SMS nodes to verify replication is running.

Step	Action
1	<p>From the command line on the SMS node, enter the following commands to verify that there are no synchronization processes running:</p> <pre>tail -f /IN/service_packages/SMS/tmp/smsMaster.log tail -f /IN/service_packages/SMS/tmp/resyncServer.log ps -ef   grep -i sync</pre> <p><b>Result:</b> No resyncs should be ongoing.</p>
2	<p>Log in to the SMS node as the smf_oper user and enter:</p> <pre>sqlplus / select * from rep_pending_queue; select count(*) from rep_ora_renumbered; select unique table_name from rep_ora_renumbered;</pre> <p><b>Result:</b> The ROE_EVENTID value for all replication nodes in the REP_PENDING_QUEUE table should be approximately the same, and should gradually but slowly increase. This means that updates are being replicated to the nodes.</p> <p>If replication is not running, you should determine the reason and resolve any problems. See <i>NCC Service Management System User's Guide</i> for more information.</p>

## Configuring replication from the command line

When configuring replication from the command line, you use the following two NCC utilities:

- `repConfigWrite` to manually create the **replication.config** file. `repConfigWrite` obtains the replication configuration from the database and writes it to the **replication.config** file in the location specified by the `output` parameter.
- `copyCnf` to copy the new **replication.config** file to the VWS and SLC nodes.

Follow these steps to configure replication from the command line.

Step	Action
1	Log in to the SMS as the smf_oper user.
2	<p>Back up the <b>replication.config</b> file on the SMS node by entering the following commands:</p> <pre>cd /IN/service_packages/SMS/bin cp ../etc/replication.config ../etc/replication.bak</pre>

Step	Action
3	<p>As the <code>smf_oper</code> user, make a backup of the <code>replication.config</code> file on each VWS or SLC node by entering the following commands:</p> <pre>bash cd /IN/service_packages/SMS/bin for NODE in hostname_list do     ssh \$NODE cp /IN/service_packages/SMS/etc/replication.config \     /IN/service_packages/SMS/etc/replication.bak done</pre> <p>where <code>hostname_list</code> is a space-separated list of host names for the VWS or SLC nodes, reachable from the SMS.</p>
4	<p>Create a new <code>replication.config</code> file by entering the following commands:</p> <pre>repConfigWrite -user smf_user/smf_password -output ../etc/replication.config ls -lart ../etc</pre> <p>where:</p> <ul style="list-style-type: none"> <li>• <code>smf_user</code> is the <code>smf</code> user on the local database</li> <li>• <code>smf_password</code> is the password for the <code>smf</code> user</li> </ul> <p><b>Note:</b> The new <code>replication.config</code> file replaces the existing <code>replication.config</code> file in the <code>/IN/service_packages/SMS/etc</code> directory.</p>
5	<p>Copy the new <code>replication.config</code> file created in step 4 to each VWS or SLC node by entering the following commands:</p> <pre>for NODE in hostname_list do     copyCnf /IN/service_packages/SMS/etc/replication.config \$NODE done</pre> <p>where <code>hostname_list</code> is a space-separated list of host names for the VWS or SLC nodes, reachable from the SMS.</p> <p><b>Note:</b> If you are running the NCC applications in a clustered environment, you must also copy the new <code>replication.config</code> file to the other SMS nodes in the cluster.</p>

## Stopping and starting replication processes

After configuring replication, you stop and restart the replication processes.

Follow these steps to stop and restart replication processes from the command line.

Step	Action
1	<p>Open terminal sessions to all nodes.</p> <p><b>Warning:</b> The next step will interrupt the replication subsystem. You should go through this procedure as quickly as possible to minimize the length of the interruption. Replication updates are normally queued and therefore will be processed when the replication subsystem is brought back up again.</p>

Step	Action
2	<p>Do the following to stop all <code>updateLoader</code> processes on the VWS and SLC nodes:</p> <ul style="list-style-type: none"> <li>On Solaris: <ul style="list-style-type: none"> <li>a) On each VWS or SLC node, log in as the root user and use a text editor such as <code>vi</code> to open the <code>inittab</code> file. For example:  <code>vi /etc/inittab</code></li> <li>b) In the <code>inittab</code> file, search for and comment out (prefix with <code>#</code>) the <code>updateLoader</code> lines prefixed with <code>scp5</code> or <code>ccs8</code>.</li> <li>c) Save the <code>inittab</code> file.</li> <li>d) Stop the <code>updateLoader</code> <code>inittab</code> processes by entering the command:  <code>init q</code></li> </ul> </li> </ul> <p><b>Result:</b> Replication is interrupted and all <code>updateLoader</code> processes are stopped.</p> <ul style="list-style-type: none"> <li>On Linux: <ul style="list-style-type: none"> <li>For VWS:  <code>systemctl stop updateLoaderWrapper.service</code></li> <li>For SLC:  <code>systemctl stop updateLoader.service</code></li> </ul> </li> </ul>
3	<p>Verify that the <code>updateLoader</code> processes have stopped by checking for connection errors in the <code>smsMaster.log</code> file in <code>/IN/service_packages/SMS/tmp</code> on the SMS nodes.</p> <p><b>Result:</b> You should see TCP connection errors which indicate that the <code>updateLoader</code> processes have disconnected.</p> <p><b>smsMaster.log example</b></p> <pre>Feb 6 10:28:34 smsMaster(4919) ERROR: TCP connection to 192.168.45.38.33007 was lost</pre>
4	<p>When all <code>updateLoader</code> processes have been stopped, restart the <code>smsMaster</code> processes on the SMS. If you are running the NCC applications in a clustered environment, you will need to do this at the same time for all cluster nodes running <code>smsMaster</code>.</p> <p>Log in to the SMS as the <code>smf_oper</code> user and enter the following commands:</p> <pre>ps -ef   grep smsMaster kill PID1 PID2</pre> <p>where:</p> <p><code>PID1</code> and <code>PID2</code> are the PIDs for the two <code>smsMaster</code> processes.</p> <p><b>Note:</b> Update requesters (<code>replicationIf</code>, <code>StatsDaemons</code>, and so on) are not stopped and should reconnect immediately.</p>

Step	Action
5	<p>Do one of the following to restart the <code>updateLoader</code> processes on the VWS and SLC nodes:</p> <ul style="list-style-type: none"> <li>On Solaris:           <ol style="list-style-type: none"> <li>On each VWS or SLC node, log in as the root user and use a text editor such as <code>vi</code> to open the <code>inittab</code> file. For example:  <code>vi /etc/inittab</code></li> <li>In the <code>inittab</code> file, search for and comment out (prefix with <code>#</code>) the <code>updateLoader</code> lines prefixed with <code>scp5</code> or <code>ccs8</code>.</li> <li>Save the <code>inittab</code> file.</li> <li>Stop the <code>updateLoader</code> <code>inittab</code> processes by entering the command:  <code>init q</code></li> </ol> </li> </ul> <p><b>Result:</b> In <code>smsMaster.log</code> you should see the <code>updateLoader</code> connecting to the <code>smsMaster</code> process. In <code>resyncServer.log</code> you should see an ENHANCED <code>resync</code> starting for the node.</p> <ul style="list-style-type: none"> <li>On Linux:           <p>For VWS:  <code>systemctl restart updateLoaderWrapper.service</code></p> <p>For SLC:  <code>systemctl restart updateLoader.service</code></p> </li> </ul>
6	<p>Enter the following command to check for FULL resyncs on the SMS node:  <code>tail -f /IN/service_packages/SMS/tmp/smsMaster.log</code></p> <p>When a FULL resync has started, then:</p> <ol style="list-style-type: none"> <li>Log in as the <code>smf_oper</code> user on the SMS node.</li> <li>Enter these commands:  <code>ps -ef   grep [Rr]esyncServer</code>  <code>kill -9 PID1 PID2</code>            where <code>PID1</code> and <code>PID2</code> are the PIDs of the <code>resyncServer</code> and <code>smsCompareResyncServer</code> processes on the node that is doing a full resync</li> <li>As the root user on the SLC or VWS replication node where the full <code>resync</code> is ongoing, enter:  <code>pkill -USR2 updateLoader</code>  <b>Result:</b> This causes the <code>updateLoader</code> process to read its queued orders file. It should report:  <code>"Node back in sync"</code>  <b>Note:</b> At this point, the interruption to the replication subsystem has ended.</li> <li>You can double check for hanging resynchronization processes by entering the following commands as the root user:  <code>for NODE in hostname_list</code>  <code>do</code>  <code>ssh \$NODE ls /IN/service_packages/SMS/tmp/???-queuedOrders.dat</code>  <code>done</code>            where <code>hostname_list</code> is a space-separated list of hostnames for VWS or SLC nodes, reachable from the SMS  <b>Result:</b> No <code>queuedOrders</code> files should exist.</li> </ol>
7	<p>On the SMS, verify that replication is running. For details, see <i>Verifying that replication is running</i> (on page 18).</p>

## Upgrading the VWS

### About upgrading the VWS

To upgrade VWS nodes to NCC release 6.0.1, complete these procedures in the order listed, on each primary and secondary VWS pair. For each pair of nodes, upgrade the secondary VWS node first, and then the primary VWS node.

Step	Action
1	Update the timeout configuration for the <code>beCDRMover</code> . See <i>Updating beCDRMover timeout configuration</i> (on page 22).
2	Disable the <code>beGroveler</code> process on the VWS. See <i>Disabling grovelling on the VWS</i> (on page 23).
	<b>Note:</b> You should disable the <code>beGroveler</code> for the period required to upgrade both the primary and the secondary VWS.
3	Stop the SLEE on the VWS. See <i>Stopping the SLEE</i> (on page 23).
4	Verify that the system is running. See <i>Verifying the system is running</i> (on page 24).
5	Stop the NCC processes and cronjobs on the VWS. See <i>Stopping NCC processes and cronjobs</i> (on page 24).
6	Update <code>.profile</code> file. See <i>Update .profile file</i> (on page 24).
7	Install the upgrade patches on the VWS. See <i>Installing patches on the VWS</i> (on page 25).
8	Install the updated configuration files on the VWS. See <i>Installing the updated configuration files</i> (on page 25).
9	Restart the NCC processes and cronjobs on the VWS. See <i>Restarting NCC processes and cronjobs</i> (on page 26).
10	Restart the SLEE on the VWS. See <i>Restarting the SLEE</i> (on page 27).
11	Re-enable the <code>beGroveler</code> process on the VWS only after you have upgraded both the primary and the secondary VWS nodes. See <i>Re-enabling grovelling on the VWS</i> (on page 27).
12	Verify that <code>BeClient</code> processes are running correctly on the VWS. See <i>Verifying BeClient processes on the VWS</i> (on page 27).

### Updating beCDRMover timeout configuration

Before you upgrade the VWS nodes, update the configuration for the `beCDRMover` process to set the `timeout` parameter to a low value, such as 4 seconds. By setting a low `timeout` value, you ensure that the upgrade process is not slowed down by the `beCDRMover` process.

**Note:** When the `timeout` parameter is set to a high value, the upgrade process will take longer. For example, if the `timeout` parameter is set to 600 seconds, the `beCDRMover` can take up to 10 minutes to respond to a SIGTERM, which in turn will make the patch upgrade process very slow.

Follow these steps to set the `beCDRMover` `timeout` parameter.

Step	Action
1	<p>Set the <code>timeout</code> parameter in the <code>beCDRMover</code> section of the <code>eserv.config</code> file on the VWS to a low value, by using the following syntax:</p> <pre>beCDRMover = {     timeout = int }</pre> <p>where <code>int</code> is the number of seconds before <code>beCDRMover</code> times out. You should set the <code>timeout</code> parameter to the recommended value of 4 or less.</p>
2	<p>Reload the configuration by sending a <code>SIGHUP</code> to <code>beCDRMover</code>.</p> <p>For more information about the <code>beCDRMover</code> process and <code>beCDRMover</code> configuration, see <i>NCC Voucher and Wallet Server Technical Guide</i>.</p>

## Disabling grovelling on the VWS

Disable grovelling while you upgrade the primary and secondary VWS nodes to ensure that wallet transactions are not duplicated by the `beGrovellor` process during the upgrade.

You disable `beGrovellor` by setting the `noProcessingTimes` parameter in the `beGrovellor` section of the `eserv.config` file on the VWS. For example, the following configuration disables the `beGrovellor` process for six hours starting at 06:00 AM.

```
beGrovellor = {
    noProcessingTimes = [
        { startsAt = "06:00", endsAt = "12:00" }
    ]
}
```

Follow these steps to disable grovelling for a specified period.

Step	Action
1	Make a note of the current configuration for the <code>noProcessingTimes</code> parameter. After completing the upgrade on the VWS node, you must reset the configuration for the <code>noProcessingTimes</code> parameter to its original value.
2	Set the <code>noProcessingTimes</code> parameter for the period of time required to upgrade the primary and secondary VWS nodes.
3	Reload the configuration by sending a <code>SIGHUP</code> to <code>beGrovellor</code> .

## Stopping the SLEE

To stop the SLEE on the VWS, as the `ebe_oper` user, enter the following command:

```
slee-ctrl stop
```

**Note:** While the SLEE is stopped, all traffic should fail over to the peer VWS.

## Verifying the system is running

Follow these steps to verify that the system is running correctly before proceeding with the upgrade.

Step	Action
1	<p>On the SMS, verify that CCS CDRs are being received from the peer VWS by entering the following commands:</p> <pre>cd /global/CDR/cdr_directory ls -l   grep VWS_peer</pre> <p>where:</p> <ul style="list-style-type: none"> <li><code>cdr_directory</code> is the directory used to store CDRs</li> <li><code>VWS_peer</code> is the name of the peer VWS node</li> </ul> <p><b>Note:</b> The folder used for storing CDRs will depend on the <code>ccsCDRLoader</code> configuration and the custom CDR archiving scripts.</p>
2	<p>On the SLC, verify that <code>BeClient</code> can still connect to the BE pair by checking the <code>syslog</code> for messages such as:</p> <pre>"Cannot contact either BE from BE Pair..."</pre>
3	<p>Go to the <code>/IN/service_packages/E2BE/sync/</code> directory on the peer VWS, and verify that the sync files are being queued in this directory by entering the command:</p> <pre>while true; do du -h; sleep 10; done.</pre>

## Stopping NCC processes and cronjobs

Follow these steps to stop NCC processes and cronjobs on the VWS node.

Step	Action
1	Log in to the VWS node you are upgrading as the <code>ccs_oper</code> user.
2	Stop all cronjobs that use NCC application binaries or scripts or that lock NCC database tables, or both, by commenting out all the jobs in <code>ccs_oper</code> crontab.
3	<p>As the root user, stop the NCC applications that are not started from the SLEE.</p> <p>Do one of the following to stop the <code>inittab</code> processes:</p> <ul style="list-style-type: none"> <li>On Solaris:           <ol style="list-style-type: none"> <li>Edit the <code>/etc/inittab</code> file to comment out the NCC application processes. <b>Note:</b> The NCC application process lines are lines which include the text, <code>"respawn:/IN/service_packages"</code>.</li> <li>Enter the following command: <pre>init q</pre> <b>Result:</b> The commented out <code>inittab</code> processes will stop.</li> </ol> </li> <li>On Linux:           <ol style="list-style-type: none"> <li>Create a copy of <code>/IN/bin/OUI_systemctl.sh</code> and name it as <code>OUI_systemctl_stop.sh</code>.</li> <li>Edit <code>/IN/bin/OUI_systemctl_stop.sh</code> and replace <code>"systemctl restart"</code> with <code>"systemctl stop"</code>.</li> <li>Run <code>/IN/bin/OUI_systemctl_stop.sh</code></li> </ol> </li> </ul>

## Update .profile file

Before you install the patches on the VWS, edit the `/IN/service_packages/SMS/.profile` file on VWS, and replace the following:



```

tty > /dev/null
if [ $? -eq 0 ]; then
with
if [ -t 0 ]; then

```

## Installing patches on the VWS

Install all patches that have a component for the VWS node on the VWS node you are upgrading. Component patches should be installed in the order listed in the *NCC components upgrade table* (on page 1).

Follow these steps to install a patch.

Step	Action
1	As the root user, log in to the VWS node on which you want to install the patch and go to the patch directory.
2	<p>Do one of the following to install the patch:</p> <ul style="list-style-type: none"> <li>On Solaris: <code>pkgadd -d . PPatch_numberSuffix</code></li> <li>On Linux: <code>rpm -i --nodeps PPatch_numberSuffix</code></li> </ul> <p>where:</p> <ul style="list-style-type: none"> <li><i>Patch_number</i> is the number of the patch you are adding</li> <li><i>Suffix</i> is one of BE, EXT, SLEE</li> </ul> <p><b>Warning:</b> If a particular component is not installed on your system, omit the patch for that component from the upgrade.</p>
3	<p>Enter the following command to run the patch package configuration script:</p> <pre>/IN/service_packages/PATCH/PatchPatch_numberSuffix/bin/configure.sh</pre> <p>where:</p> <ul style="list-style-type: none"> <li><i>Patch_number</i> is the number of the patch you are adding</li> <li><i>Suffix</i> is one of BE, EXT, SLEE</li> </ul>

## Installing the updated configuration files

Follow these steps to install updated configuration files required on the VWS node you are upgrading.

**Note:** These are the configuration files that you prepared earlier in the upgrade process. See *Preparing Upgrade Configuration Files* (on page 10) for details.

Step	Action
1	<p>Compare the current configuration files with the old configuration files to check for any automatic updates applied during patch installation by entering the following command for each configuration file on the VWS:</p> <pre>diff backup_config_file current_config_file</pre> <p>where:</p> <ul style="list-style-type: none"> <li><i>backup_config_file</i> is the backed up copy of the configuration file. See <i>Backing up configuration files</i> (on page 10)</li> <li><i>current_config_file</i> is the current configuration file after the upgrade patches have been installed</li> </ul>
2	Note any reported differences.

Step	Action
3	Go to the directory where you created the updated configuration files for the VWS node you are currently upgrading, for example <code>/IN/service_packages/NCC601UP/config/new</code> .
4	If any differences were reported in step 1, edit <i>current_config_file</i> to include these changes.
5	Copy <i>current_config_file</i> to the directory where they will be used. See <i>New configuration files</i> (on page 26) for a list of the directories in which to install the updated configuration files.
<b>Example</b> <pre>cd /IN/service_packages/NCC601UP/config/new cp eserv.config /IN/service_packages cp SLEE.cfg /IN/service_packages/SLEE/etc</pre>	

### New configuration files

The following table lists the location for new configuration files on the VWS node.

Configuration File	Location
<b>eserv.config</b>	<b>/IN/service_packages</b>
<b>SLEE.cfg</b>	<b>/IN/service_packages/SLEE/etc</b>

Open the **eserv.config** file and check for the database connection strings. If not already available, add or update the following database connections strings:

```
CCS = {
  oracleUserAndPassword = "/@E2BE"
  ..
}

BE = {
  oracleUserAndPassword = "/@E2BE"
  ..
  eventStorage = {
    oracleUserAndPassword = "/@E2BE"
    ..
  }
  ..
}
```

### Restarting NCC processes and cronjobs

Do one of the following to restart the NCC processes and cronjobs on the VWS node.

- On Solaris:

Step	Action
1	As the root user on the VWS node, edit the <code>/etc/inittab</code> file to uncomment (remove the # prefix) the NCC application processes previously commented out.
2	Restart the <b>inittab</b> processes by entering: <code>init q</code>
3	Restart the cronjobs previously commented out.

- On Linux:

Step	Action
1	Enter the following command to restart all services: <code>/IN/bin/OUI_systemctl.sh</code>

## Restarting the SLEE

To restart the SLEE on the VWS, as the `ebe_oper` user, enter the command:

```
slee-ctrl start
```

Log off the session where the upgrade was performed and create a new login session. This new session is required so that environment changes made by the patch upgrade on the VWS are reflected in the `ebe_oper` session that restarts the SLEE.

## Re-enabling grovelling on the VWS

Re-enable the `beGroveller` process on the VWS node only after you have upgraded both the primary and the secondary VWS nodes.

To re-enable the `beGroveller` process, restore the configuration that was specified for the `noProcessingTimes` parameter before you disabled the `beGroveller` process. Then reload the configuration by sending a `SIGHUP` to `beGroveller`.

You configure the `noProcessingTimes` parameter in the `beGroveller` section of the `eserv.config` file on the VWS.

## Verifying BeClient processes on the VWS

Follow these steps to verify `BeClient` processes are running on the VWS node.

Step	Action
1	<p>Enter one of the following commands to verify the VWS is starting up correctly and synchronizing with the peer VWS:</p> <ul style="list-style-type: none"> <li>• On Solaris: <code>tail -f /var/adm/messages</code></li> <li>• On Linux: <code>tail -f /var/log/messages</code></li> </ul> <p><b>Result:</b> Successful startup messages are logged for the VWS processes (<code>beServer</code>, <code>beVWARS</code>, and so on).</p>

Step	Action
	<p><b>Result:</b> After a couple of minutes, <code>sync</code> starts and the following messages are logged:</p> <pre>beSync(18712) NOTICE: BE Synchronisation process is running 28035 seconds behind target (28040s total delay)</pre> <p>You may see multiple occurrences of <code>beWriter</code> messages. You can ignore these messages. For example:</p> <pre>Apr 26 23:26:31 beid beWriter: [ID 953149 user.warning] beWriter(29194) WARNING: remote syncBuffer [seqNo 8316183..8316184] 1 items in (4294 .. 4295): output timed out message 8316184 Apr 26 23:26:31 beid beWriter: [ID 848595 user.crit] beWriter(29194) CRITICAL: syncBuffer remote: Incoming message has seqNo 8316107, before last sent seqNo 8316185, either a subsequent message timed out of this is a duplicate.</pre>
2	<p>Skip this step if you are upgrading the secondary VWS node.</p> <p>If you are upgrading the primary VWS node, after <code>sync</code> has completed, enter the following commands to verify that CDRs are being generated on the SMS:</p> <pre>cd /global/CDR/cdr_directory ls -l   grep VWS_name</pre> <p>where:</p> <ul style="list-style-type: none"> <li><code>cdr_directory</code> is the directory used to store CDRs</li> <li><code>VWS_name</code> is the name of the VWS you are upgrading.</li> </ul> <p><b>Result:</b> You should see newly generated CDRs coming from the primary VWS node.</p> <p><b>Note:</b> The directory used for storing CDRs is dependent on the <code>ccsCDRLoader</code> configuration and the custom CDR archiving scripts.</p>
3	<p>Verify <code>BeClient</code> processes on the SLC nodes:</p> <pre>tail -f /IN/service_packages/E2BE/tmp/BeClient.log</pre> <p><b>Result:</b> All <code>BeClient</code> processes should have reconnected to the primary VWS node which should have taken over traffic again.</p>

## Upgrading the SLC

### About upgrading the SLC

To upgrade SLC nodes to NCC release 6.0.1, complete these procedures in the order listed on each SLC.

Step	Action
1	Monitor calls and redirect traffic to the peer SLC. See <i>Monitoring calls and redirecting traffic</i> (on page 29).
2	Stop the SLEE on the SLC. See <i>Stopping the SLEE</i> (on page 29).
3	Stop the NCC applications on the SLC. See <i>Stopping the NCC cronjobs and applications</i> (on page 29).
4	Install the upgrade patches on the SLC. See <i>Installing patches on the SLC</i> (on page 30).
5	Install the updated configuration files on the SLC. See <i>Installing the updated configuration files</i> (on page 31).

Step	Action
6	Restart the NCC application processes on the SLC. See <i>Restarting processes and cronjobs on the SLC</i> (on page 33).
7	Restart the SLEE on the SLC. See <i>Restarting the SLEE</i> (on page 33).
8	Verify the system startup. See <i>Verifying the SLC startup</i> (on page 33).

## Monitoring calls and redirecting traffic

Follow these steps to monitor for outstanding calls and to direct traffic away from this SLC.

Step	Action
1	Log in as the <code>acs_oper</code> user.
2	Go to the <code>/IN/service_packages/SLEE/bin/</code> directory.
3	Redirect traffic away from this SLC, using the <code>check</code> command to monitor for any outstanding calls: <code>./check -b 10</code>

## Stopping the SLEE

To stop the SLEE, log in to the SLC as the `acs_oper` user and enter the command:

```
slee-ctrl stop
```

**Note:** While the SLEE is stopped, all traffic should fail over to the peer nodes.

## Where to install patches

The following table lists the type of node on which to install the different patches for each component. The type of node is indicated by the letters at the end of the patch filename.

### Example

**P23253932SMS** should be installed on the SMS node.

If the Patch Filename Ends In	Install on This Type of Node
SMS	SMS. If the SMS is a cluster, install on both cluster nodes.
EFM	SMS. If the SMS is a cluster, install on both cluster nodes.
SCP	SLC
SCS	SLC
EXT	VWS
BE	VWS
SLEE	SLC and VWS

## Stopping the NCC cronjobs and applications

Follow these steps to stop NCC cronjobs on the SLC node, and all NCC applications that are not started from the SLEE.

Step	Action
1	Log in to the SLC as the <code>acs_oper</code> user.

Step	Action
2	<p>Edit the crontab by entering the following command:</p> <pre>crontab -e</pre> <p><b>Note:</b> The crontab for the <code>acs_oper</code> user is located in the following directory by default: <code>/var/spool/cron/crontabs/acs_oper</code>.</p>
3	Stop the <code>rca_get_read_count</code> cronjob by commenting out the line in the crontab that runs <code>rca_get_read_count.sh</code> .
4	<p>As the root user, stop the NCC applications that are not started from the SLEE.</p> <p>Do one of the following to stop NCC processes:</p> <ul style="list-style-type: none"> <li>On Solaris:           <ol style="list-style-type: none"> <li>Edit the <code>/etc/inittab</code> file to comment out the NCC application processes. <b>Note:</b> The NCC application process lines are lines which include the text, <code>"respawn:/IN/service_packages"</code>.</li> <li>Enter the following command: <pre>init q</pre> <b>Result:</b> The commented out inittab processes will stop.</li> </ol> </li> <li>On Linux:           <ol style="list-style-type: none"> <li>Create a copy of <code>/IN/bin/OUI_systemctl.sh</code> and name it as <code>OUI_systemctl_stop.sh</code>.</li> <li>Edit <code>/IN/bin/OUI_systemctl_stop.sh</code> and replace <code>"systemctl restart"</code> with <code>"systemctl stop"</code>.</li> <li>Run <code>/IN/bin/OUI_systemctl_stop.sh</code></li> </ol> </li> </ul>

## Installing patches on the SLC

Install all patches that have a component for the SLC node on the SLC node you are upgrading. Component patches should be installed in the order listed in the *NCC components upgrade table* (on page 1).

Follow these steps to install a patch.

Step	Action
1	As the root user, log in to the SLC node on which you want to install the patch and go to the patch directory.
2	<p>Do one of the following to install the patch:</p> <ul style="list-style-type: none"> <li>On Solaris: <pre>pkgadd -d . PPatch_numberSuffix</pre></li> <li>On Linux: <pre>rpm -i --nodeps PPatch_numberSuffix</pre></li> </ul> <p>where:</p> <ul style="list-style-type: none"> <li><code>Patch_number</code> is the number of the patch you are adding</li> <li><code>Suffix</code> is SCP or SLEE</li> </ul> <p><b>Warning:</b> If a particular component is not installed on your system, omit the patch for that component from the upgrade</p>

Step	Action
3	<p>Enter the following command to run the patch package configuration script:</p> <pre>/IN/service_packages/PATCH/PatchPatch_numberSuffix/bin/configure.sh</pre> <p>where:</p> <ul style="list-style-type: none"> <li>• <i>Patch_number</i> is the number of the patch you are adding</li> <li>• <i>Suffix</i> is SCP or SLEE</li> </ul>

## Installing the updated configuration files

Follow these steps to add new configuration files on the SLC node you are upgrading.

**Note:** These are the configuration files that you prepared earlier on in the upgrade process. See *Preparing Upgrade Configuration Files* (on page 10) for details.

Step	Action
1	<p>Compare the current configuration files with the old configuration files to check for any automatic updates applied during patch installation by entering this command for each configuration file on the SLC:</p> <pre>diff backup_config_file current_config_file</pre> <p>where:</p> <ul style="list-style-type: none"> <li>• <i>backup_config_file</i> is the backup copy of the configuration file. See <i>Backing up configuration files</i> (on page 10)</li> <li>• <i>current_config_file</i> is the current configuration file after the upgrade patches have been installed</li> </ul>
2	Note any reported differences.
3	Go to the directory where you created the updated configuration files for the SLC node you are currently upgrading, for example <code>/IN/service_packages/NCC601UP/config/new</code> .
4	If any differences were reported in step 1, edit the updated configuration files to include these changes.
5	<p>Copy the updated configuration files to the directory where they will be used.</p> <p>See <i>New configuration files on the SLC</i> (on page 31) for a list of the directories in which to install the updated configuration files.</p> <p><b>Example</b></p> <pre>cd /IN/service_packages/NCC601UP/config/new cp eserv.config /IN/service_packages cp SLEE.cfg /IN/service_packages/SLEE/etc cp acs.conf /IN/service_packages/ACS/etc</pre>

## New configuration files on the SLC

The following table lists the location for new configuration files on the SLC node.

Configuration File	Location
<code>eserv.config</code>	<code>/IN/service_packages</code>
<code>SLEE.cfg</code>	<code>/IN/service_packages/SLEE/etc</code>
<code>acs.conf</code>	<code>/IN/service_packages/ACS/etc</code>

Open the `eserv.config` file and check for the database connection strings. Add or update the following database connections strings, if not already available:

## Chapter 4

```
CCS = {
    oracleUserAndPassword = "/@SCP"
    ..
}

OSD = {
    osdInterface = {
        oracleDatabase = "/@SCP"
        ..
    }
    ..
}

LCP = {
    oracleUserAndPassword = "/@SCP"
    ..
}

SES = {
    sesTrigger = {
    ..
        databaseLogin = "/@SCP"
    ..
    }
    ..
}

RADIUSControlAgent = {
    ..
    OracleUserAndPassword = "/@SCP"
    ..
}

XMS = {
    ..
    xmsTrigger = {
        oracleDatabase = "/@SCP"
        ..
    }
    ..
}

BCD = {
    ..
    bcdBillingClient = {
    ..
        oracleUserAndPassword = "/@SCP"
    ..
    }
    ..
}
```

The `brmBeClient` is configured by default for TLS connections to BRM. To use TLS connections, configuration of Oracle wallet is required. The default wallet directory path used is `/IN/service_packages/BCD/wallet`. Create the wallet directory and contents to make use of TLS connections to BRM. For more information on configuring a wallet for BRM, see the *BRM Charging Driver Technical Guide*. If TLS connections to BRM are not required, add the following settings to the `eserv.config` file on SLC:

```
BCD = {
    ...
    bcdBillingClient = {
    ...
```



```

        ConnectionManager = {
            enableTLS = 0
        }
    }
}

```

## Restarting processes and cronjobs on the SLC

Follow these steps to restart the NCC processes and cronjobs on the SLC.

Step	Action
1	As the root user, edit <code>/etc/inittab</code> on the SLC and uncomment the NCC process lines. The NCC process lines contain this text: <code>"service_packages"</code> .
2	Restart the NCC processes by entering one of the following commands: <ul style="list-style-type: none"> <li>On Solaris: <pre>init q</pre> </li> <li>On Linux: <pre>/IN/bin/OUI_systemctl.sh</pre> </li> </ul>
3	As the <code>acs_oper</code> user, restart the <code>rca_get_read_count</code> cronjob by editing the crontab.
4	Uncomment the line in the crontab that runs <code>rca_get_read_count.sh</code> by removing the <code>"#"</code> from the beginning of the line.

## Restarting the SLEE

To restart the SLEE on the SLC, as the `acs_oper` user, enter the command:

```
slee-ctrl start
```

## Verifying the SLC startup

Enter one of the following commands to verify that the SLC starts up correctly and that traffic is being processed:

- On Solaris:

```
tail -f /var/adm/messages
```
- On Linux:

```
tail -f /var/log/messages
```

## Upgrading the SMS

### About upgrading the SMS

To upgrade the SMS nodes to NCC release 6.0.1, complete these procedures in the order listed on each SMS.

Step	Action
1	Stop the NCC cronjobs on the SMS. See <i>Stopping NCC cronjobs</i> (on page 34).
2	Stop the NCC applications on the SMS. See <i>Stopping NCC applications</i> (on page 34).
3	Install the upgrade patches on the SMS. See <i>Installing patches on the SMS</i> (on page 35).
4	Install the updated configuration files on the SMS. See <i>Installing the updated configuration files</i> (on page 35).
5	Restart the NCC services on the SMS. See <i>Restarting the SMS</i> (on page 37).

## Stopping NCC cronjobs

Follow these steps to stop NCC cronjobs on the SMS.

### Important:

- This will stop all cronjobs that use NCC application binaries or scripts, or that lock NCC database tables, or both.
- SMS services will be interrupted following this procedure.

Step	Action
1	Log in to the SMS.
2	Comment out the following jobs in the <code>acs_oper</code> crontab: <ul style="list-style-type: none"> <li>• <code>acsDbCleanup</code></li> </ul>
3	Comment out the following jobs in the <code>ccs_oper</code> crontab: <ul style="list-style-type: none"> <li>• <code>ccsWalletExpiry</code></li> <li>• <code>ccsPeriodicCCRecharge</code></li> <li>• <code>ccsCDRTrimFiles</code></li> <li>• <code>ccsExpiryMessageLoader</code></li> <li>• <code>ccsPeriodicCharge</code></li> <li>• <code>ccsbt_deactivate_cleanup</code></li> <li>• <code>ccsbt_execute</code> (there can be more than one)</li> <li>• <code>cdrDeletion</code></li> </ul>
4	Comment out the following jobs in the <code>smf_oper</code> crontab: <ul style="list-style-type: none"> <li>• <code>smsDbCleanup</code></li> <li>• <code>smsCdrProcess</code></li> <li>• <code>smsReportsCleaner</code></li> </ul>
5	Comment out the following jobs in the <code>uis_oper</code> crontab: <ul style="list-style-type: none"> <li>• <code>cdrLoaderCron</code></li> </ul>

## Stopping NCC applications

To stop the application processes on a single non-clustered SMS node:

Step	Action
On Solaris:	
1	Write down the current system run-level, and then take the system to run-level 2 by entering the following command: <code>init 2</code>
2	Ensure that the Oracle database and <code>sshd</code> are running.
On Linux:	
1	Create a copy of <code>/IN/bin/OUI_systemctl.sh</code> and rename it as <code>OUI_systemctl_stop.sh</code> .
2	Edit <code>/IN/bin/OUI_systemctl_stop.sh</code> and replace <code>systemctl restart</code> with <code>systemctl stop</code> .
3	Run <code>/IN/bin/OUI_systemctl_stop.sh</code> .

To stop the application processes on a clustered SMS, shut down each resource group on the SMS node that you are upgrading by performing the following steps:

Step	Action
1	Determine the resource groups for all running processes by using the <code>scstat</code> command; for example: <pre>scstat -g   egrep -i 'group: sms group: acs group: ccs group: mmx group: rims'   grep -i Online   awk '{print \$2}'   sort -u</pre>
2	Shut down each resource group with the <code>scswitch</code> command; for example: <pre>scswitch -F -g resource-1, resource-2, resource-3</pre>

## Installing patches on the SMS

Install all patches that have a component for the SMS node on the SMS node. Component patches should be installed in the order listed in the *NCC components upgrade table* (on page 1).

Follow these steps to install a patch.

Step	Action
1	Log in to the SMS node on which you want to install the patch as the root user and go to the patch directory.
2	Do one of the following to install the patch: <ul style="list-style-type: none"> <li>On Solaris:  <pre>pkgadd -d . PPatch_numberSuffix</pre></li> <li>On Linux:  <pre>rpm -i --nodeps PPatch_numberSuffix</pre></li> </ul> where: <ul style="list-style-type: none"> <li><i>Patch_number</i> is the number of the patch you are adding</li> <li><i>Suffix</i> is SMS, EFM, or CLUSTER</li> </ul> <p><b>Warning:</b> If a particular component is not installed on your system, omit the patch for that component from the upgrade.</p>
3	Enter the following command to run the patch component configuration script: <pre>/IN/service_packages/PATCH/PatchPatch_numberSuffix/bin/configure.sh</pre> where <ul style="list-style-type: none"> <li><i>Patch_number</i> is the number of the patch you are adding</li> <li><i>Suffix</i> is one of SMS, EFM, or CLUSTER</li> </ul> <p><b>Note:</b> On a cluster model, install the patch on both primary and secondary SMS nodes, but run the database configuration on the primary node only.</p>

## Installing the updated configuration files

Follow these steps to install the updated configuration files required on the SMS node you are upgrading.

**Note:** These are the configuration files that you prepared earlier on in the upgrade process. See *Preparing Upgrade Configuration Files* (on page 10) for details.

Step	Action
1	<p>Compare the current configuration files with the old configuration files to check for any automatic updates applied during patch installation by entering this command for each configuration file on the SMS:</p> <pre>diff backup_config_file current_config_file</pre> <p>where:</p> <ul style="list-style-type: none"> <li><i>backup_config_file</i> is the backup copy of the configuration file. See <i>Backing up configuration files</i> (on page 10)</li> <li><i>current_config_file</i> is the current configuration file after the upgrade patches have been installed</li> </ul>
2	Note any reported differences.
3	<p>Go to the directory where you created the updated configuration files for the SMS node you are currently upgrading; for example:</p> <p><b>IN/service_packages/NCC601UP/config/new.</b></p>
4	If any differences were reported in step 1, edit the updated configuration files to include these changes.
5	<p>Copy the updated configuration files to the directory where they will be used.</p> <p>See <i>New configuration files on the SMS</i> (on page 36) for a list of the directories in which to install the updated configuration files.</p> <p><b>Example</b></p> <pre>cd /IN/service_packages/NCC601UP/config/new cp eserv.config /IN/service_packages</pre>

### New configuration files on the SMS

The following table lists the location for new configuration files on SMS nodes.

Configuration File	Location
<b>eserv.config</b>	<b>/IN/service_packages</b>

Open the **eserv.config** file and check for the database connection strings. If not already available, add or update the following database connections strings:

```
CCS = {
  oracleUserAndPassword = "/@SMF"
  ..
  ccsBeOrb = {
    ..
    mergeWalletsOptions = {
      oracleLogin = "/@SMF"
    }
    ..
  }
  ..
  ccsCDRLoader = {
    ..
    dbUserPass = "/@SMF"
    ..
  }
  ..
  ccsCDRFileGenerator = {
    ..
    OracleUsernamePassword = "/@SMF"
```

```

    ..
}
..
}

notificationIF = {
    oracleLogin = "/@SMF"
    ..
}

triggering = {
    ..
    oracleLogin = "/@SMF"
    ..
}

pi = {
    ..
    general =
        ..
        oraUser = "/@SMF"
        ..
    }

    PIbeClient = {
        ..
        oracleLogin = "/@SMF"
        ..
    }
    ..
}

```

## Restarting the SMS

Follow these steps to restart services on the SMS.

Step	Action
1	<p>Restart the previously stopped services. Do one of the following:</p> <ul style="list-style-type: none"> <li>• If NCC is installed on a single non-clustered SMS:           <p>On Solaris:</p> <ol style="list-style-type: none"> <li>a) Return the system to the previous run-level, which you wrote down before stopping the NCC applications.</li> </ol> <p>On Linux:</p> <ol style="list-style-type: none"> <li>a) Run the following command:  <code>/IN/bin/OUI_systemctl.sh</code> </li> </ol> </li> <li>• If NCC is installed on a clustered SMS, use the <b>scswitch</b> command on the upgraded SMS cluster node to restart each resource group that you shut down previously; for example:  <code>scswitch -Z -g resource-1, resource-2, resource-3</code> </li> </ul>

Step	Action
2	<p>Check that the SMS processes are running by entering the following commands:</p> <pre>tail -f /IN/service_packages/SMS/tmp/smsNamingServer.log tail -f /IN/service_packages/SMS/tmp/smsTaskAgent.log tail -f /IN/service_packages/SMS/tmp/smsMaster.log tail -f /IN/service_packages/CCS/tmp/ccsBeOrb.log</pre> <p>Restart any processes that are not running.</p>
3	<p>Continuously monitor the <b>syslog</b> file using one of the following commands:</p> <ul style="list-style-type: none"> <li>On Solaris: <pre>tail -f /var/adm/messages</pre> </li> <li>On Linux: <pre>tail -f /var/log/messages</pre> </li> </ul>
4	Restart the cronjobs you previously commented out.
5	Clear the temporary Internet files from the Java cache.
6	Restart the SMS UI.

## Migrating balance-related AVP Mappings

If you are upgrading from a previous release of NCC, perform the following to migrate your balance-related AVP mappings to the NCC 6.0.1 release:

Step	Action
1	Make a backup copy of the <b>eserv.config</b> file (for example, create a file named <b>eserv.config.backup</b> ).
2	Open your <b>eserv.config</b> file in a text editor.
3	Remove all instances of the <code>ccsBalanceScale</code> parameter from the file.
4	<p>Set the <code>conversionScale</code> parameter to 0 for appropriate balance-type AVPs:</p> <pre>DIAMETER = {   DomainTypes = [     AVPs = [       {         conversionScale = 0       }     ]   ] }</pre>

This configures DCD to use the scale factors specified in the **Balance Type Mapping** tab.

- | Step | Action                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
|------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 5    | <p>For balance-type AVPs, the <code>conversion</code> array must not include balance types that are defined in the <b>Balance Type Mapping</b> tab.</p> <p>For example, if you will define the scale factor for NCC General Cash balance types in the <b>Balance Type Mapping</b> tab, delete the following <code>conversion</code> array from your <code>eserv.config</code> file:</p> <pre> {   avpCode = 233   name = "ORA-Balance-Element-Id"   vendorId = 3512   ccsConcept = "walletInfoBalanceType"   type = "Unsigned32"   conversion = [     esg = 110          # NCC Balance Type Id (General Cash)     vendor = 1000091   # ECE Balance Type Id   ] }</pre>                                                                       |
| 6    | Save and close the file.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| 7    | Log in to the SMS UI.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| 8    | <p>From the <b>Services</b> menu, select <b>Prepaid Charging &gt; Service Management</b>.</p> <p>The Service Management screen is displayed.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| 9    | From the <b>Service Provider</b> list, select the service provider.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| 10   | Click the <b>Balance Type Mapping</b> tab.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| 11   | <p>Click the <b>New</b> button.</p> <p>The New Balance Type Mapping dialog box is displayed.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| 12   | <p>For each <code>ccsBalanceScale</code> entry in the <code>eserv.config.backup</code> file, create an equivalent mapping in the <b>New Balance Type Mapping</b> dialog box:</p> <ul style="list-style-type: none"> <li>From the <b>Balance Type</b> list, select the name of the NCC balance type.</li> <li>In the <b>Third-Party Resource</b> field, enter the equivalent balance type ID from the third-party application, such as BRM or ECE. The third-party balance type you enter is mapped to the NCC balance type.</li> <li>In the <b>Third-Party Resource Scale</b> field, enter the value from the <code>conversionScale</code> parameter.</li> <li>From the <b>Domain Type</b> list, select <b>DIAMETER_Diameter</b>.</li> </ul> |

The following table shows an example of how to migrate balance type mappings from the `ccsBalanceScale` parameter in an `eserv.config` file to the **New Balance Type Mapping** dialog box.

eserv.config File Entry	Balance Type Field	Third-Party Resource Field	Third-Party Resource Scale Field	Domain Type Field
<pre> ccsBalanceScale = [   {     # scale for General Cash     conversionScale = -100     balance_type_id = 110   } ]</pre>	General Cash	110	100	DIAMETER_Diameter

<pre>ccsBalanceScale = [ { # scale for SMS conversionScale = 1 balance_type_id = 111 } ]</pre>	SMS	111	1	DIAMETER_Diameter
<pre>ccsBalanceScale = [ { # scale for General Time conversionScale = -6000 balance_type_id = 113 } ]</pre>	General Time	113	6000	DIAMETER_Diameter
<pre>ccsBalanceScale = [ { # scale for ECE Currency conversionScale = 100 balance_type_id = 114 } ]</pre>	ECE Currency	114	0.01	DIAMETER_Diameter

**Note:** If a balance requires sign inversion between NCC and ECE, enter a negative number in the **Third-Party Resource Scale** field of the **Balance Type Mapping** dialog box. For example, to switch between negative ECE values and positive NCC values for General Cash balance types (shown in the table above), enter -100 in the **Third-Party Resource Scale** field. Do not use the `signInversion` parameter to apply sign inversion to balance-type AVPs, because NCC would apply sign inversion to all balances, regardless of balance type.



# Rolling Back the Upgrade

## Overview

### Introduction

This chapter explains how to roll back the Oracle Communications Network Charging and Control (NCC) upgrade on the Service Management System (SMS), Service Logic Controller (SLC), and Voucher and Wallet Server (VWS).

### In this chapter

---

This chapter contains the following topics.

About Rolling Back the Upgrade .....	41
Rolling Back the SMS Upgrade .....	42
Rolling Back the SLC Upgrade.....	46
Rolling Back the VWS Upgrade .....	48

## About Rolling Back the Upgrade

### Introduction to rolling back the upgrade

You may need to roll back the NCC release 6.0.1 upgrade, for example, if the upgrade is unsuccessful and the post-upgraded software is not functioning as expected.

### Rollback order

Rolling back the upgrade requires each node on the NCC platform to be rolled back independently and sequentially in the following order:

- 1 Roll back the SMS nodes.
- 2 Roll back all SLC nodes, one by one.
- 3 Roll back each VWS pair in reverse order: primary node, then secondary node.

### Rolling back an individual node

Rolling back an individual node consists of the following high-level steps:

- 1 Shut down the NCC application processes.
- 2 Remove the NCC upgrade patches on the node, one by one.
- 3 Restart the NCC application processes on the node.

## Rolling Back the SMS Upgrade

### About rolling back the SMS upgrade

To roll back the upgrade on the SMS, complete these procedures, in the order listed, on all the SMS nodes that have been upgraded to NCC release 6.0.1.

Step	Action
1	Stop the NCC cronjobs on the SMS. See <i>Stopping NCC cronjobs</i> (on page 42).
2	Stop the NCC applications on the SMS. See <i>Stopping NCC applications during rollback</i> (on page 43).
3	Remove NCC release 6.0.1 patches from the SMS. See <i>Removing patches on the SMS</i> (on page 43).
4	Configure the replication.config file. See <i>Configuring replication file</i> (on page 44).
5	Restore backed up configuration files. See <i>Restoring backed up configuration files</i> (on page 44).
6	Restart the SMS. See <i>Restarting the SMS</i> (on page 45).

### Stopping NCC cronjobs

Follow these steps to stop NCC cronjobs on the SMS.

#### Important:

- This will stop all cronjobs that use NCC application binaries or scripts or that lock NCC database tables, or both.
- SMS services will be interrupted following this procedure.

Step	Action
1	Log in to the SMS.
2	Comment out the following jobs in the <code>acs_oper</code> crontab: <ul style="list-style-type: none"> <li>• <code>acsDbCleanup</code></li> </ul>
3	Comment out the following jobs in the <code>ccs_oper</code> crontab: <ul style="list-style-type: none"> <li>• <code>ccsWalletExpiry</code></li> <li>• <code>ccsPeriodicCCRecharge</code></li> <li>• <code>ccsCDRTrimFiles</code></li> <li>• <code>ccsExpiryMessageLoader</code></li> <li>• <code>ccsPeriodicCharge</code></li> <li>• <code>ccsbt_deactivate_cleanup</code></li> <li>• <code>ccsbt_execute</code> (there can be more than one)</li> <li>• <code>cdrDeletion</code></li> </ul>
4	Comment out the following jobs in the <code>smf_oper</code> crontab: <ul style="list-style-type: none"> <li>• <code>smsDbCleanup</code></li> <li>• <code>smsCdrProcess</code></li> <li>• <code>smsReportsCleaner</code></li> </ul>
5	Comment out the following jobs in the <code>uis_oper</code> crontab: <ul style="list-style-type: none"> <li>• <code>cdrLoaderCron</code></li> </ul>

## Stopping NCC applications during rollback

To stop the application processes on a single non-clustered SMS node:

Step	Action
On Solaris:	
1	Write down the current system run-level, and then take the system to run-level 2 by entering the following command: <code>init 2</code>
2	Ensure that the Oracle database and <code>sshd</code> are running.
On Linux:	
1	Create a copy of <code>/IN/bin/OUI_systemctl.sh</code> and rename it as <code>OUI_systemctl_stop.sh</code> .
2	Edit <code>/IN/bin/OUI_systemctl_stop.sh</code> and replace <code>systemctl restart</code> with <code>systemctl stop</code> .
3	Run <code>/IN/bin/OUI_systemctl_stop.sh</code> .

To stop the application processes on a clustered SMS, shut down each resource group on the SMS node that you are rolling back by performing the following steps:

Step	Action
1	Determine the resource groups for all running processes by using the <code>scstat</code> command; for example:  <code>scstat -g   egrep -i 'group: sms group: acs group: ccs group: mmx group: rims'   grep -i Online   awk '{print \$2}'   sort -u</code>
2	Shut down each resource group with the <code>scswitch</code> command; for example:  <code>scswitch -F -g resource-1, resource-2, resource-3</code>

## Removing patches on the SMS

Remove all patches that have a component for the SMS node from the upgraded SMS nodes. You must remove component patches in the reverse order to the order used for installation, listed in the *NCC components upgrade table* (on page 1).

Follow these steps to remove a patch.

Step	Action
1	As the root user, log in to the SMS node on which you want to remove a patch.
2	Run the patch unconfiguration script by entering the following command:  <b>Note:</b> On a cluster model, run the patch unconfiguration script only on the primary node.  <code>/IN/service_packages/PATCH/PATCHPatch_numberSuffix/bin/unconfigure.sh</code> where: <ul style="list-style-type: none"> <li><code>Patch_number</code> is the number of the patch you are removing</li> <li><code>Suffix</code> is one of SMS, EFM, CLUSTER</li> </ul>

Step	Action
3	<p>Do one of the following to remove the patch:</p> <ul style="list-style-type: none"> <li>On Solaris: <pre>pkgrm PPatch_numberSuffix</pre> </li> <li>On Linux: <pre>rpm -e PPatch_numberSuffix</pre> </li> </ul> <p>where:</p> <ul style="list-style-type: none"> <li><i>Patch_number</i> is the number of the patch you are removing</li> <li><i>Suffix</i> is one of SMS, EFM, CLUSTER</li> </ul>

## Configuring replication file

After you remove the patches, create the replication config file and copy it to all nodes.

When configuring replication from the command line, you use the following two NCC utilities:

- `repConfigWrite` to manually create the **replication.config** file. `repConfigWrite` obtains the replication configuration from the database and writes it to the **replication.config** file in the location specified by the `output` parameter.
- `copyCnf` to copy the new **replication.config** file to the VWS and SLC nodes.

Follow these steps to configure replication from the command line.

Step	Action
1	Log in to the SMS as the <code>smf_oper</code> user.
2	<p>Create a new <b>replication.config</b> file by entering the following commands:</p> <pre>cd /IN/service_packages/SMS/bin repConfigWrite -user smf_user/smf_password -output ../etc/replication.config ls -lart ../etc</pre> <p>where:</p> <ul style="list-style-type: none"> <li><code>smf_user</code> is the smf user on the local database</li> <li><code>smf_password</code> is the password for the smf user</li> </ul> <p><b>Note:</b> The new <b>replication.config</b> file replaces the existing <b>replication.config</b> file in the <code>/IN/service_packages/SMS/etc</code> directory.</p>
3	<p>Copy the new <b>replication.config</b> file created in step 2 to each VWS or SLC node by entering the following commands:</p> <pre>for NODE in hostname_list do     copyCnf /IN/service_packages/SMS/etc/replication.config \$NODE done</pre> <p>where <code>hostname_list</code> is a space-separated list of host names for the VWS or SLC nodes, reachable from the SMS.</p> <p><b>Note:</b> If you are running the NCC applications in a clustered environment, you must also copy the new <b>replication.config</b> file to the other SMS nodes in the cluster.</p>

## Restoring backed up configuration files

Follow these steps to restore the old configuration files on the SMS node on which you are rolling back the upgrade.

**Note:** These are the configuration files that you backed up earlier in the upgrade process. See *Preparing Upgrade Configuration Files* (on page 10).

Step	Action
1	Go to the configuration files backup directory for the SMS node you are rolling back: <code>cd /IN/service_packages/NCC601UP/config/old</code>
2	Copy the backed up configuration files to their original directories. See <i>Restored configuration files on the SMS</i> (on page 45) for a list of the directories in which to restore configuration files on the SMS node. <b>Example</b> <code>cd /IN/service_packages/NCC601UP/config/old</code> <code>cp eserv.config_pre_NCC601 /IN/service_packages/eserv.config</code>

### Restored configuration files on the SMS

The following table lists the backup configuration files and the location in which to restore them on the SMS node.

Backup Configuration File	Restore to
<code>eserv.config_pre_NCC601</code>	<code>/IN/service_packages/eserv.config</code>

### Restarting the SMS

Follow these steps to restart services on the SMS.

Step	Action
1	Restart the previously stopped services. Do one of the following: <ul style="list-style-type: none"> <li>If NCC is installed on a single non-clustered SMS: <p>On Solaris:</p> <p>a) Return the system to the previous run-level, which you wrote down before stopping the NCC applications.</p> <p>On Linux:</p> <p>a) Run the following command: <code>/IN/bin/OUI_systemctl.sh</code></p> </li> <li>If NCC is installed on a clustered SMS, use the <code>scswitch</code> command to restart each resource group that you shut down previously; for example: <code>scswitch -Z -g resource-1, resource-2, resource-3</code></li> </ul>
2	Restart the cronjobs previously commented out.
3	Clear the temporary internet files in the Java cache.
4	Restart the SMS UI.

## Rolling Back the SLC Upgrade

### About rolling back the SLC upgrade

To roll back the upgrade on SLC nodes, complete these procedures in the order listed, on all the SLC nodes that have been upgraded to NCC release 6.0.1.

Step	Action
1	Stop the NCC applications on the SLC. See <i>Stopping the NCC cronjobs and applications</i> (on page 46).
2	Stop the SLEE on the SLC. See <i>Stopping the SLEE</i> (on page 46).
3	Remove the upgrade patches from the SLC. See <i>Removing patches from the SLC</i> (on page 47).
4	Restore the backed up configuration files on the SLC. See <i>Restoring backed up configuration files</i> (on page 47).
5	Restart the NCC application processes on the SLC. See <i>Restarting processes and cronjobs on the SLC</i> (on page 48).
6	Restart the SLEE on the SLC. See <i>Restarting the SLEE</i> (on page 48).
7	Verify the system startup. See <i>Verifying the SLC startup</i> (on page 48).

### Stopping the NCC cronjobs and applications

Follow these steps to stop NCC cronjobs on the SLC node, and all NCC applications that are not started from the SLEE.

Step	Action
1	Log in to the SLC as the <code>acs_oper</code> user.
2	Edit the crontab by entering the following command: <code>crontab -e</code>
	<b>Note:</b> The crontab for the <code>acs_oper</code> user is located in the following directory by default: <code>/var/spool/cron/crontabs/acs_oper</code> .
3	Stop the <code>rca_get_read_count</code> cronjob by commenting out the line in the crontab that runs <code>rca_get_read_count.sh</code> .
4	As the root user, do one of the following to stop NCC applications that are not started from the SLEE: <ul style="list-style-type: none"> <li>On Solaris:               <ol style="list-style-type: none"> <li>Edit the <code>/etc/inittab</code> file to comment out the NCC application processes. <b>Note:</b> The NCC application process lines are lines which include the text, <code>"respawn:/IN/service_packages"</code>.</li> <li>Enter the following command: <code>init q</code> <b>Result:</b> The commented out <code>inittab</code> processes will stop.</li> </ol> </li> <li>On Linux, run the following script that was created during upgrade: <code>/IN/bin/OUI_systemctl_stop.sh</code></li> </ul>

### Stopping the SLEE

To stop the SLEE, log in to the SLC as the `acs_oper` user and enter the command:

```
slee-ctrl stop
```

**Note:** While the SLEE is stopped, all traffic should fail over to the peer nodes.

## Removing patches from the SLC

Remove all patches that have a component for the SLC node from the upgraded SLC node. You must remove component patches in the reverse order to the order used for installation, listed in the *NCC components upgrade table* (on page 1).

Follow these steps to remove a patch.

Step	Action
1	As the root user, log in to the SLC node on which you want to remove a patch.
2	Enter the following command to run the patch unconfiguration script: <code>/IN/service_packages/PATCH/PATCHPatch_numberSuffix/bin/unconfigure.sh</code> where: <ul style="list-style-type: none"> <li>• <i>Patch_number</i> is the number of the patch you are removing</li> <li>• <i>Suffix</i> is one of SCP or SLEE</li> </ul>
3	Do one of the following to remove the patch: <ul style="list-style-type: none"> <li>• On Solaris:  <code>pkgrm PPatch_numberSuffix</code></li> <li>• On Linux:  <code>rpm -e PPatch_numberSuffix</code></li> </ul> where: <ul style="list-style-type: none"> <li>• <i>Patch_number</i> is the number of the patch you are removing</li> <li>• <i>Suffix</i> is one of SCP or SLEE</li> </ul>

## Restoring backed up configuration files

Follow these steps to restore the old configuration files on the SLC node on which you are rolling back the upgrade.

**Note:** These are the configuration files that you backed up earlier in the upgrade process. See *Preparing Upgrade Configuration Files* (on page 10).

Step	Action
1	Go to the configuration files backup directory for the SLC node you are rolling back; for example, <code>/IN/service_packages/NCC601UP/config/old</code> .
2	Copy the backed up configuration files to their original directories. See <i>Restored configuration files</i> (on page 48) for a list of the directories in which to restore configuration files on SLC nodes. <b>Example:</b> <pre>cd /IN/service_packages/NCC601UP/config/old cp eserv.config_pre_NCC601 /IN/service_packages/eserv.config cp SLEE.cfg_pre_NCC601 /IN/service_packages/SLEE/etc/SLEE.cfg cp acs.conf_pre_NCC601 /IN/service_packages/ACS/etc/acs.conf</pre>

## Restored configuration files

The following table lists the backup configuration files and the location in which to restore them on the SLC node.

Backup Configuration File	Restore to
<code>eserv.config_pre_NCC601</code>	<code>/IN/service_packages/eserv.config</code>
<code>SLEE.cfg_pre_NCC601</code>	<code>/IN/service_packages/SLEE/etc/SLEE.cfg</code>
<code>acs.conf_pre_NCC601</code>	<code>/IN/service_packages/ACS/etc/acs.conf</code>

## Restarting processes and cronjobs on the SLC

Follow these steps to restart the NCC processes and cronjobs on the SLC.

Step	Action
1	As the root user, edit the <code>/etc/inittab</code> file on the SLC and uncomment the NCC process lines. The NCC process lines contain this text: <code>"service_packages"</code> .
2	Restart the NCC processes by entering the following command: <ul style="list-style-type: none"> <li>On Solaris: <pre>init q</pre> </li> <li>On Linux: <pre>/IN/bin/OUI_systemctl.sh</pre> </li> </ul>
3	As the <code>acs_oper</code> user, restart the <code>rca_get_read_count</code> cronjob by editing the crontab.
4	Uncomment the line in the crontab that runs <code>rca_get_read_count.sh</code> by removing the <code>"#"</code> from the beginning of the line.

## Restarting the SLEE

To restart the SLEE on the SLC as the `acs_oper` user, enter the command:

```
slee-ctrl start
```

## Verifying the SLC startup

Enter one of the following commands to verify that the SLC starts up correctly and that traffic is being processed:

- On Solaris:

```
tail -f /var/adm/messages
```
- On Linux:

```
tail -f /var/log/messages
```

## Rolling Back the VWS Upgrade

### About rolling back the VWS upgrade

To roll back the upgrade on the VWS, complete these procedures, in the order listed, on all the VWS nodes that have been upgraded to NCC release 6.0.1. Roll back VWS pairs in reverse order of installation.

Step	Action
1	Disable <code>beGroveler</code> on the VWS. See <i>Disabling grovelling during the rollback</i> (on page 49).



Step	Action
2	Stop the SLEE on the VWS. See <i>Stopping the SLEE</i> (on page 49).
3	Set up system monitoring. See <i>Setting up system monitoring</i> (on page 50).
4	Stop the NCC processes and cronjobs on the VWS. See <i>Stopping NCC processes and cronjobs</i> (on page 50).
5	Remove the upgrade patches from the VWS. See <i>Removing patches on the VWS</i> (on page 51).
6	Restore the backed up configuration files on the VWS. See <i>Restoring backed up configuration files</i> (on page 51).
7	Restart the NCC processes and cronjobs on the VWS. See <i>Restarting NCC processes and cronjobs</i> (on page 52).
8	Restart the SLEE on the VWS. See <i>Restarting the SLEE</i> (on page 52).
9	Re-enable <code>beGrovellder</code> process on the VWS. See <i>Re-enabling grovelling on the VWS</i> (on page 52).
10	Verify <code>BeClient</code> processes on the VWS are working. See <i>Verifying BeClient processes on the VWS</i> (on page 52).

## Disabling grovelling during the rollback

Disable grovelling while you roll back the upgrade to the primary and secondary VWS nodes to ensure that wallet transactions are not duplicated by the `beGrovellder` process during the roll back process.

To disable grovelling for a specified period, set the `noProcessingTimes` parameter in the `beGrovellder` section of the `eserv.config` file on the VWS, and then reload the configuration by sending a SIGHUP to `beGrovellder`.

For example, the following configuration disables the `beGrovellder` process for six hours starting at 06:00 AM.

```
beGrovellder = {
  noProcessingTimes = [
    { startsAt = "06:00", endsAt = "12:00" }
  ]
}
```

**Note:** Before you update the `eserv.config` configuration file, make a note of the current configuration for the `noProcessingTimes` parameter. After you complete rolling back the upgrade on the VWS node, you must reset the configuration for the `noProcessingTimes` parameter to its original value.

## Stopping the SLEE

To stop the SLEE on the VWS, as the `ebe_oper` user, enter the following command:

```
slee-ctrl stop
```

**Note:** While the SLEE is stopped, all traffic should fail over to the peer VWS.

## Setting up system monitoring

Follow these steps to monitor the system prior to rolling back the upgrade on the VWS node.

Step	Action
1	<p>Enter one of the following commands to monitor the <code>syslog</code> on the peer VWS node:</p> <ul style="list-style-type: none"> <li>On Solaris:           <pre>tail -f /var/adm/messages</pre> </li> <li>On Linux:           <pre>tail -f /var/log/messages</pre> </li> </ul>
2	<p>Enter one of the following commands to monitor the <code>syslog</code> on the SMS and SLC nodes for billing errors:</p> <ul style="list-style-type: none"> <li>On Solaris:           <pre>tail -f /var/adm/messages</pre> </li> <li>On Linux:           <pre>tail -f /var/log/messages</pre> </li> </ul> <p><b>Result:</b> Only the connection loss to the upgraded VWS node is reported. Billing will continue using the peer VWS node.</p>
3	<p>On the SMS, verify that Charging Control Services (CCS) CDRs are being received from the peer VWS node by entering these commands:</p> <pre>cd /global/CDR/cdr_directory ls -l   grep VWS_peer</pre> <p>where:</p> <ul style="list-style-type: none"> <li><code>cdr_directory</code> is the directory used to store CDRs</li> <li><code>VWS_peer</code> is the name of the peer VWS node</li> </ul> <p><b>Note:</b> The folder used for storing CDRs will depend on the <code>ccsCDRLoader</code> configuration and the custom CDR archiving scripts.</p>

## Stopping NCC processes and cronjobs

Follow these steps to stop NCC processes and cronjobs on the VWS node.

Step	Action
1	Log in to the VWS node you are upgrading as the <code>ccs_oper</code> user.
2	Stop all cronjobs that use NCC application binaries or scripts or that lock NCC database tables, or both, by commenting out all the jobs in <code>ccs_oper</code> crontab.
3	<p>As the root user, do one of the following to stop NCC applications that are not started from the SLEE:</p> <ul style="list-style-type: none"> <li>On Solaris:           <ol style="list-style-type: none"> <li>Edit the <code>/etc/inittab</code> file to comment out the NCC application processes.               <p><b>Note:</b> The NCC application process lines are lines which include the text, <code>"respawn:/IN/service_packages"</code>.</p> </li> <li>Enter the following command:                   <pre>init q</pre> <p><b>Result:</b> The commented out inittab processes will stop.</p> </li> </ol> </li> <li>On Linux, run the following script that was created during upgrade:               <pre>/IN/bin/OUI_systemctl_stop.sh</pre> </li> </ul>

## Removing patches on the VWS

Remove all patches that have a component for the VWS node from the upgraded VWS node. You must remove component patches in the reverse order to the order used for installation, listed in the *NCC components upgrade table* (on page 1).

Follow these steps to remove a patch.

Step	Action
1	As the root user, log in to the VWS node on which you want to remove a patch.
2	Enter the following command to run the patch unconfiguration script: <code>/IN/service_packages/PATCH/PATCHPatch_numberSuffix/bin/unconfigure.sh</code> where: <ul style="list-style-type: none"> <li>• <i>Patch_number</i> is the number of the patch you are removing</li> <li>• <i>Suffix</i> is one of BE, EXT, SLEE</li> </ul>
3	Do one of the following to remove the patch: <ul style="list-style-type: none"> <li>• On Solaris:  <code>pkgrm PPatch_numberSuffix</code></li> <li>• On Linux:  <code>rpm -e PPatch_numberSuffix</code></li> </ul> where: <ul style="list-style-type: none"> <li>• <i>Patch_number</i> is the number of the patch you are removing</li> <li>• <i>Suffix</i> is one of BE, EXT, SLEE</li> </ul>

## Restoring backed up configuration files

Follow these steps to restore the old configuration files on the VWS node on which you are rolling back the upgrade.

**Note:** These are the configuration files that you backed up earlier in the upgrade process. See *Preparing Upgrade Configuration Files* (on page 10).

Step	Action
1	Go to the configuration files backup directory for the VWS node you are rolling back; for example, <code>/IN/service_packages/NCC601UP/config/old</code> .
2	Copy the backed up configuration files to their original directories. See <i>Restored configuration files</i> (on page 52) for a list of the directories in which to restore configuration files on the VWS node. <b>Example</b> <code>cd /IN/service_packages/NCC601UP/config/old</code> <code>cp eserv.config_pre_NCC601 /IN/service_packages/eserv.config</code> <code>cp SLEE.cfg_pre_NCC601 /IN/service_packages/SLEE/etc/SLEE.cfg</code>

## Restored configuration files

The following table lists the backup configuration files and the location in which to restore them on the VWS node.

Backup Configuration File	Restore to
<code>eserv.config_pre_NCC601</code>	<code>/IN/service_packages/eserv.config</code>
<code>SLEE.cfg_pre_NCC601</code>	<code>/IN/service_packages/SLEE/etc/SLEE.cfg</code>

## Restarting NCC processes and cronjobs

Follow these steps to restart the NCC processes and cronjobs on the VWS node.

- On Solaris:

Step	Action
1	As the root user on the VWS node, edit the <code>/etc/inittab</code> file to uncomment (remove the # prefix) the NCC application processes previously commented out.
2	Restart the <code>inittab</code> processes by entering: <code>init q</code> Restart the NCC processes by entering the following command:
3	Restart cronjobs previously commented out.

- On Linux:

:Step	Action
1	Enter the following command to restart all services: <code>/IN/bin/OUI_systemctl.sh</code>

## Restarting the SLEE

To restart the SLEE on the VWS, as the `ebe_oper` user, enter the command:

```
slee-ctrl start
```

## Re-enabling grovelling on the VWS

Re-enable the `beGroveler` process on the VWS node only after you have rolled back both the primary and the secondary VWS nodes.

To re-enable the `beGroveler` process, restore the configuration that was specified for the `noProcessingTimes` parameter before you disabled the `beGroveler` process. Then reload the configuration by sending a `SIGHUP` to `beGroveler`.

You configure the `noProcessingTimes` parameter in the `beGroveler` section of the `eserv.config` file on the VWS.

## Verifying BeClient processes on the VWS

Follow these steps to verify `BeClient` processes are running on the VWS node.

Step	Action
1	<p>Enter one of the following commands to verify the VWS is starting up correctly and synchronizing with the peer VWS:</p> <ul style="list-style-type: none"> <li>On Solaris: <pre>tail -f /var/adm/messages</pre> </li> <li>On Linux: <pre>tail -f /var/log/messages</pre> </li> </ul> <p><b>Result:</b> Successful startup messages are logged for the VWS processes (<code>beServer</code>, <code>beVWARS</code>, and so on).</p>
2	<p>After the startup completes, monitor the progress of <code>sync</code> by keeping the tail open and by entering these commands on the peer VWS:</p> <pre>cd /IN/service_packages/E2BE/sync while true do <b>find . -type f   wc -l</b> sleep 10 done</pre> <p><b>Result:</b> After a couple of minutes, <code>sync</code> starts and the following messages are logged:</p> <pre>beSync(18712) NOTICE: BE Synchronisation process is running 28035 seconds behind target (28040s total delay)</pre> <p>You may see multiple occurrences of <code>beWriter</code> messages. You can ignore these messages. For example:</p> <pre>Apr 26 23:26:31 beid beWriter: [ID 953149 user.warning] beWriter(29194) WARNING: remote syncBuffer [seqNo 8316183..8316184] 1 items in (4294 .. 4295): output timed out message 8316184 Apr 26 23:26:31 beid beWriter: [ID 848595 user.crit] beWriter(29194) CRITICAL: syncBuffer remote: Incoming message has seqNo 8316107, before last sent seqNo 8316185, either a subsequent message timed out of this is a duplicate.</pre>
3	<p>Skip this step if you are rolling back the secondary VWS node.</p> <p>If you are rolling back the primary VWS node, after <code>sync</code> has completed, enter the following commands to verify that CDRs are being generated on the SMS:</p> <pre>cd /global/CDR/cdr_directory ls -l   <b>grep</b> VWS_name</pre> <p>where:</p> <ul style="list-style-type: none"> <li><code>cdr_directory</code> is the directory used to store CDRs</li> <li><code>VWS_name</code> is the name of the VWS you are upgrading.</li> </ul> <p><b>Result:</b> You should see newly generated CDRs coming from the primary VWS node.</p> <p><b>Note:</b> The directory used for storing CDRs will depend on the <code>ccsCDRLoader</code> configuration and the custom CDR archiving scripts.</p>
4	<p>Verify <code>BeClient</code> processes on the SLC nodes:</p> <pre>tail -f /IN/service_packages/E2BE/tmp/BeClient.log</pre> <p><b>Result:</b> All <code>BeClient</code> processes should have reconnected to the primary VWS node which should have taken over traffic again.</p>



# Example of sms.jnlp file

Following is an example of sms.jnlp file:

```
<jnlp spec="1.0+"
  codebase="http://sms_ip_addr/"
  href="sms.jnlp" >

  <information>
    <title> SMS - name </title>
    <vendor> Oracle </vendor>
    <homepage href="SMS/install/index.html" />

    <description kind="short"> Starts the SMS Java Application Screens connecting
to host server: sms_ip_addr. </description>
    <description kind="tooltip"> Service Management System </description>

    <!-- gif or jpg only. Transparency does not work. Rectangular icons will be
badly stretched. -->
    <icon href="SMS/images/favicon.ico" width="64" height="64" kind="default" />
    <icon href="SMS/images/oracle.gif" kind="splash" />

    <!-- installs on Desktop and in Start->Programs->Oracle -->
    <shortcut online="true" >
      <desktop />
      <menu submenu="Oracle" />
    </shortcut>
  </information>

  <security>
    <all-permissions />
  </security>

  <resources>
    <j2se version="1.8.0+" href="http://java.sun.com/products/autodl/j2se" java-
vm-args="--add-modules=java.corba,java.xml.ws" />
    <property name="jnlp.packEnabled" value="true" />
    <jar href="sms.sig.jar" main="true" />
    <jar href="common.sig.jar" />
    <jar href="ojdbc7.sig.jar" />
    <jar href="oraclepki.sig.jar" />
    <extension name="Oracle Help for Java" href="ohj.jnlp" />
    <property name="java.util.Arrays.useLegacyMergeSort" value="true" />
    <jar href="acs.sig.jar" />
    <jar href="osd.sig.jar" />
    <jar href="PIsecurity.sig.jar" />
    <jar href="pi.sig.jar" />
    <jar href="dap.sig.jar" />
    <jar href="http_client.sig.jar" />
    <jar href="orawSDL.sig.jar" />
    <jar href="oc3c.sig.jar" />
    <jar href="UIS_GW.sig.jar" />
    <jar href="UPC.sig.jar" />
    <jar href="upcMacros.sig.jar" />
    <jar href="rims.sig.jar" />
    <jar href="xms.sig.jar" />
    <jar href="smcb.sig.jar" />
    <jar href="np.sig.jar" />
    <jar href="lcp.sig.jar" />
```

```

<jar href="enum.sig.jar" />
<jar href="ses.sig.jar" />
<jar href="vpn.sig.jar" />
<jar href="rca.sig.jar" />

<property name="jnlp.sms.TZ" value="GMT" />
<property name="jnlp.sms.host" value="sms_ip_addr" />
<property name="jnlp.sms.logo" value="SMS/images/oracle.gif" />
<property name="jnlp.sms.databaseID" value="1521:SMF" />
<property name="jnlp.sms.databaseHost" value="sms_ip_addr:1521:SMF" />
<property name="jnlp.sms.EncryptedSSLConnection" value="true" />
<property name="jnlp.sms.sslCipherSuites"
value="(TLS_RSA_WITH_AES_128_CBC_SHA)" />
<property name="jnlp.sms.secureConnectionDatabaseHost"
value="(DESCRIPTION= (ADDRESS_LIST=
(ADDRESS=(PROTOCOL=TCPS) (HOST=sms_ip_addr) (PORT=2484))) (CONNECT_DATA=
(SERVICE_NAME=SMF)))" />
<property name="jnlp.sms.showEFM" value="1" />

<property name="jnlp.acs.SuppressTagID" value="TRUE" />
<property name="jnlp.acs.maximiseAcscScreens" value="false" />
<property name="jnlp.acs.Profile8" value="Account Reference Profile" />
<property name="jnlp.acs.Profile9" value="Product Type Profile" />
<property name="jnlp.acs.Profile10" value="Control Plan Profile (App 3)" />
<property name="jnlp.acs.Profile12" value="CCS Global Profile" />
<property name="jnlp.acs.Profile13" value="CCS Temporary Profile (App 6)" />
<property name="jnlp.acs.Profile14" value="CCS Temporary Profile (App 7)" />
<property name="jnlp.acs.Profile15" value="CCS Temporary Profile (App 8)" />
<property name="jnlp.acs.ssfs" value="vssp,sca" />
<property name="jnlp.acs.scfs" value="scf" />

<property name="jnlp.vpn.INProtocol" value="IN_PROTOCOL" />

<property name="jnlp.osd.WSDLDirectory" value="/IN/html/wsdls" />
<property name="jnlp.osd.WSDLURL" value="http://wsdlmch/wsdls" />

<property name="jnlp.ccs.UseAnnouncements" value="YES" />
<property name="jnlp.ccs.BeORTimeoutms" value="5000" />
<property name="jnlp.ccs.VRRedeemMinVoucherLength" value="9" />
<property name="jnlp.ccs.VRRedeemMaxVoucherLength" value="15" />
<property name="jnlp.ccs.defaultEDRSearchAge" value="2" />

<property name="jnlp.ECEExtensions" value="true" />
<property name="jnlp.ORB_HOST" value="sms_ip_addr" />
</resources>

<application-desc main-class="UserScreens.Application" />

</jnlp>

```



# Glossary of Terms

## AAA

Authentication, Authorization, and Accounting. Specified in Diameter RFC 3588.

## ACS

Advanced Control Services configuration platform.

## API

Application Programming Interface

## AVP

Attribute Value Pair, used in Diameter to represent properties of a particular request or answer.

## CCS

- 1) Charging Control Services component.
- 2) Common Channel Signalling. A signalling system used in telephone networks that separates signalling information from user data.

## CDMA

Code Division Multiple Access is a method for describing physical radio channels. Data intended for a specific channel is modulated with that channel's code. These are typically pseudo-random in nature, and possess favourable correlation properties to ensure physical channels are not confused with one another.

## CDR

Call Data Record

**Note:** The industry standard for CDR is EDR (Event Detail Record).

## CORBA

Common Object Request Broker Architecture. It is a framework that provides interoperability between objects built in different programming languages, running on different physical machines perhaps on different networks. It specifies an Interface Definition Language, and API that allows client / server interaction with the ORB.

## cron

Unix utility for scheduling tasks.

## crontab

File used by cron.

## **DAP**

Data Access Pack. An extension module for ACS which allows control plans to make asynchronous requests to external systems over various protocols including XML and LDAP.

## **Diameter**

A feature rich AAA protocol. Utilises SCTP and TCP transports.

## **DP**

Detection Point

## **ENUM**

E.164 Number Mapping.

## **GPRS**

General Packet Radio Service - employed to connect mobile cellular users to PDN (Public Data Network- for example the Internet).

## **GSM**

Global System for Mobile communication.

It is a second generation cellular telecommunication system. Unlike first generation systems, GSM is digital and thus introduced greater enhancements such as security, capacity, quality and the ability to support integrated services.

## **GUI**

Graphical User Interface

## **HLR**

The Home Location Register is a database within the HPLMN (Home Public Land Mobile Network). It provides routing information for MT calls and SMS. It is also responsible for the maintenance of user subscription information. This is distributed to the relevant VLR, or SGSN (Serving GPRS Support Node) through the attach process and mobility management procedures such as Location Area and Routing Area updates.

## **HPLMN**

Home PLMN

## **HTML**

HyperText Markup Language, a small application of SGML used on the World Wide Web.

It defines a very simple class of report-style documents, with section headings, paragraphs, lists, tables, and illustrations, with a few informational and presentational items, and some hypertext and multimedia.

## **IN**

Intelligent Network

## **LCP**

Location Capabilities Pack - set of software components used by other applications to look up the location of mobile devices.

## **MAP**

Mobile Application Part - a protocol which enables real time communication between nodes in a mobile cellular network. A typical usage of the protocol would be for the transfer of location information from the VLR to the HLR.

## **Messaging Manager**

The Messaging Manager service and the Short Message Service components of Oracle Communications Network Charging and Control product. Component acronym is MM (formerly MMX).

## **MM**

Messaging Manager. Formerly MMX, see also *XMS* (on page 62) and *Messaging Manager* (on page 59).

## **MS**

Mobile Station

## **MT**

Mobile Terminated

## **NP**

Number Portability

## **ORB**

Object Request Broker. Within an Object based communication system, an ORB keeps track of the actual addresses of all defined objects and thus is used to route traffic to the correct destination. The CORBA defines the ORB in a series of standards enabling different platforms to share common information.

## **OSA**

Open Service Access provides a standard interface through which developers can design services that may interact with functions within the network.

## **PI**

Provisioning Interface - used for bulk database updates/configuration instead of GUI based configuration.

## **PL/SQL**

Oracle's Procedural Language for stored procedures and packages.

## **PLMN**

Public Land Mobile Network

## **RIMS**

Routing Information for Mobile Services. Used to cache HLR lookup information.

**Note:** Now known as "Messaging Manager Navigator".

## **SCA**

- 1) Service Centre Address
- 2) Session Control Agent for Session Initiation Protocol (SIP)

## **SCP**

Service Control Point. Also known as SLC.

## **SCS**

Service Capability Server (OSA)

## **SCTP**

Stream Control Transmission Protocol. A transport-layer protocol analogous to the TCP or User Datagram Protocol (UDP). SCTP provides some similar services as TCP (reliable, in-sequence transport of messages with congestion control) but adds high availability.

## **Service Provider**

See Telco.

## **SES**

Subscriber Event Service is an application that enables a service provider to send text messages to roaming subscribers (both their own and foreign subscribers) when they roam in and out of their network.

## **Session**

Diameter exchange relating to a particular user or subscriber access to a provided service (for example, a telephone call).

## **SGML**

Standard Generalized Markup Language. The international standard for defining descriptions of the structure of different types of electronic document.

## **SGSN**

Serving GPRS Support Node

## **SIP**

Session Initiation Protocol - a signaling protocol for Internet conferencing, telephony, event notification and instant messaging. (IETF)

## **SLC**

Service Logic Controller (formerly UAS).

## **SLEE**

Service Logic Execution Environment

## **SMS**

Depending on context, can be:

- Service Management System hardware platform
- Short Message Service
- Service Management System platform
- NCC Service Management System application

## **SMSC**

Short Message Service Centre stores and forwards a short message to the indicated destination subscriber number.

## **SN**

Service Number

## **SQL**

Structured Query Language is a database query language.

## **SSL**

Secure Sockets Layer protocol

## **SSP**

Service Switching Point

## **Switching Point**

Anything that can send and receive C7 messages.

## **System Administrator**

The person(s) responsible for the overall set-up and maintenance of the IN.

## **TCAP**

Transaction Capabilities Application Part – layer in protocol stack, message protocol.

## **TCP**

Transmission Control Protocol. This is a reliable octet streaming protocol used by the majority of applications on the Internet. It provides a connection-oriented, full-duplex, point to point service between hosts.

## **Telco**

Telecommunications Provider. This is the company that provides the telephone service to customers.

## **Telecommunications Provider**

See Telco.

## **TFR**

TCAP Filter Relay

## **TLS**

Transport Layer Security. Cryptographic protocol used to provide secure communications. Evolved from SSL.

## **UIS**

USSD Interactive Services

## **UPC**

USSD Portal Components

## **USSD**

Unstructured Supplementary Service Data - a feature in the GSM MAP protocol that can be used to provide subscriber functions such as Balance Query.

## **VLR**

Visitor Location Register - contains all subscriber data required for call handling and mobility management for mobile subscribers currently located in the area controlled by the VLR.

## **VPN**

The Virtual Private Network product is an enhanced services capability enabling private network facilities across a public telephony network.

## **VSSP**

Virtual SSP

## **VWS**

Oracle Voucher and Wallet Server (formerly UBE).

## **XML**

eXtensible Markup Language. It is designed to improve the functionality of the Web by providing more flexible and adaptable information identification.

It is called extensible because it is not a fixed format like HTML. XML is a 'metalanguage' — a language for describing other languages—which lets you design your own customized markup languages for limitless different types of documents. XML can do this because it's written in SGML.

## **XMS**

Three letter code used to designate some components and path locations used by the Oracle Communications Network Charging and Control *Messaging Manager* (on page 59) service and the Short Message Service. The published code is *MM* (on page 59) (formerly *MMX*).







# Index

## A

- AAA • 57
- About backward compatibility • 3
- About Configuring Replication • 6, 17
- About minimizing the impact of service interruption • 6
- About replication configuration • 17
- About rolling back the SLC upgrade • 46
- About rolling back the SMS upgrade • 42
- About Rolling Back the Upgrade • 41
- About rolling back the VWS upgrade • 48
- About Service Interruption • 6
- About the Upgrade • 1
- About the Upgrade Process • 5
- About This Document • v
- About upgrade stages • 5
- About Upgrading • 15
- About upgrading the NCC remote database • 16
- About upgrading the SLC • 28
- About upgrading the SMS • 33
- About upgrading the VWS • 22
- About using GNU Screen • 17
- ACS • 57
- API • 57
- Audience • v
- AVP • 57

## B

- Backing up configuration files • 10, 25, 31, 36
- Backing Up Database Tables and Ensuring Their Integrity • 9

## C

- CCS • 57
- CDMA • 57
- CDR • 57
- Configuring replication file • 42, 44
- Configuring replication from the command line • 18
- Copyright • ii
- CORBA • 57
- cron • 57
- crontab • 57

## D

- DAP • 58
- Diameter • 58
- Disabling grovelling during the rollback • 48, 49
- Disabling grovelling on the VWS • 22, 23
- Document Conventions • vii
- DP • 58

## E

- Ensuring database integrity • 9
- ENUM • 58
- Example of sms.jnlp file • 11, 55

## G

- General recommendations • 3
- GPRS • 58
- GSM • 58
- GUI • 58

## H

- HLR • 58
- HPLMN • 58
- HTML • 58

## I

- IN • 58
- Installing patches on the SLC • 28, 30
- Installing patches on the SMS • 33, 35
- Installing patches on the VWS • 22, 25
- Installing the updated configuration files • 22, 25, 28, 31, 33, 35
- Introduction • 9, 10
- Introduction to rolling back the upgrade • 41
- Introduction to Upgrading • 1

## L

- LCP • 59

## M

- Making sure VWS and SLC nodes are stable during the upgrade • 6
- Manually Configuring Replication • v, 6, 17
- MAP • 59
- Messaging Manager • 59, 62
- Migrating balance-related AVP Mappings • 38
- Minimizing service interruption on SLC • 7
- Minimizing service interruption on VWS • 7
- MM • 59, 62
- Monitoring calls and redirecting traffic • 28, 29
- MS • 59
- MT • 59

## N

- NCC components upgrade table • 1, 13, 15, 25, 30, 35, 43, 47, 51
- NCC node upgrade order • 1
- New configuration files • 26
- New configuration files on the SLC • 31
- New configuration files on the SMS • 36
- NP • 59

## O

- ORB • 59

OSA • 59  
Overview • 1, 5, 9, 15, 41

## P

Patch contents • v, 1, 11  
PI • 59  
PL/SQL • 59  
PLMN • 59  
Preparation stage • 5  
Preparing for the Upgrade • 5, 9  
Preparing new configuration files • 10, 11  
Preparing Upgrade Configuration Files • 10, 25, 31, 36, 45, 47, 51  
Prerequisites • v

## R

Re-enabling grovelling on the VWS • 22, 27, 49, 52  
Related Documents • vi  
Releases upgraded • 1, 7  
Removing patches from the SLC • 46, 47  
Removing patches on the SMS • 42, 43  
Removing patches on the VWS • 49, 51  
Restarting processes and cronjobs on the SLC • 29, 33  
Restarting NCC processes and cronjobs • 22, 26, 49, 52  
Restarting processes and cronjobs on the SLC • 46, 48  
Restarting the SLEE • 22, 27, 29, 33, 46, 48, 49, 52  
Restarting the SMS • 33, 37, 42, 45  
Restored configuration files • 47, 48, 51, 52  
Restored configuration files on the SMS • 45  
Restoring backed up configuration files • 42, 44, 46, 47, 49, 51  
RIMS • 60  
Rollback order • 41  
Rolling back an individual node • 41  
Rolling Back the SLC Upgrade • 46  
Rolling Back the SMS Upgrade • 42  
Rolling Back the Upgrade • 41  
Rolling Back the VWS Upgrade • 48

## S

SCA • 60  
Scope • v  
SCP • 60  
SCS • 60  
SCTP • 60  
Service interruption on SMS • 7  
Service Provider • 60  
SES • 60  
Session • 60  
Setting up system monitoring • 49, 50  
SGML • 60  
SGSN • 60

SIP • 60  
SLC • 60  
SLEE • 61  
SMS • 61  
SMSC • 61  
SN • 61  
SQL • 61  
SSL • 61  
SSP • 61  
Stopping and starting replication processes • 18, 19  
Stopping NCC applications • 33, 34  
Stopping NCC applications during rollback • 42, 43  
Stopping NCC cronjobs • 33, 34, 42  
Stopping NCC processes and cronjobs • 22, 24, 49, 50  
Stopping the NCC cronjobs and applications • 28, 29, 46  
Stopping the SLEE • 22, 23, 28, 29, 46, 49  
Switching Point • 61  
System Administrator • 61

## T

TCAP • 61  
TCP • 61  
Telco • 61  
Telecommunications Provider • 62  
TFR • 62  
TLS • 62  
Typographical Conventions • vii

## U

UIS • 62  
Unpacking the patch file • vi, 12  
Unpacking the Patches • 11  
UPC • 62  
Update .profile file • 22, 24  
Updating beCDRMover timeout configuration • 22  
Upgrade order • 15  
Upgrade Process Overview • 5  
Upgrade stage • 5  
Upgrading an individual node • 15  
Upgrading Oracle Communications Network Charging and Control • 6, 15  
Upgrading the SLC • 28  
Upgrading the SMS • v, 6, 17, 33  
Upgrading the VWS • 22  
Using GNU Screen • 17  
Using GNU Screen for a shell session • 17  
USSD • 62

## V

Verifying BeClient processes on the VWS • 22, 27, 49, 52  
Verifying that replication is running • 18, 21

Verifying the SLC startup • 29, 33, 46, 48  
Verifying the system is running • 22, 24  
VLR • 62  
VPN • 62  
VSSP • 62  
VWS • 62

## **W**

Ways to configure replication • v, 6  
Where to install patches • v, 1, 11, 12, 29

## **X**

XML • 62  
XMS • 59, 62