

**Oracle® Communications  
Convergent Charging Controller**

Provisioning Interface Alarms Guide

Release 6.0.1

April 2017

# Copyright

Copyright © 2017, Oracle and/or its affiliates. All rights reserved.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this is software or related documentation that is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, then the following notice is applicable:

U.S. GOVERNMENT END USERS: Oracle programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, delivered to U.S. Government end users are "commercial computer software" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, shall be subject to license terms and license restrictions applicable to the programs. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Xeon are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. AMD, Opteron, the AMD logo, and the AMD Opteron logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark of The Open Group.

This software or hardware and documentation may provide access to or information about content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services unless otherwise set forth in an applicable agreement between you and Oracle. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services, except as set forth in an applicable agreement between you and Oracle.

# Contents

Alarm Topic Description .....	1
PImanager .....	3
PIprocess.....	6
PIbatch .....	16
PIbatch XML .....	17



# Alarm Topic Description

## Alarm generation

Alarms on each configured node are written to the syslog and are then captured by the smsAlarmDaemon for entry in the SMF database.

For management of these alarms, refer to *SMS Technical Guide*.

## Severity levels

This table describes the alarms severity levels.

Level	Abbr	Description
Critical	C	These alarms are raised when the application has encountered an error which indicates that the system is unable to function.
Error	E	These alarms indicate the application has encountered a serious problem completing a necessary task and could not complete the task.
Warning	W	Warnings are raised to indicate the application encountered a problem completing a non-mission critical task.
Notice	N	Notices are raised to indicate that the application has completed a task successfully.

## Alarm format

Alarms usually follow this format:

```
Mon DD 24:MM:SS hostname process name: [ID alarmID user.severity] process(PID)  
SEVERITY: Alarm text with possible variables
```

Where:

Variable	Description
Mon DD	Month and date the alarm was logged.
24:MM:SS	Time the alarm was logged in 24 hour format.
hostname	Name of the machine on which the alarm was generated.
process name	Name of the process which logged the alarm.
alarmID	ID number of the alarm.
severity	Alarm severity.
process	Name of the process which logged the alarm.
PID	Process ID of the process which logged the alarm.
SEVERITY	Alarm severity.
Alarm text	Alarm text. This may include variables such as node number. <b>Note:</b> In some cases the entire alarm text is generated from variables.

**Note:** Some alarms from some subsystems may have a different format.

Example: This text shows an smsMaster alarm about pending update queues.

```
Mar 30 13:34:54 prodsmpl smsMaster: [ID 953149 user.warning] smsMaster(17833)  
WARNING: Pending queue now above 15 (Worst Node 317)
```

## Alarm text and variables

The %d and %s symbols represent variables within the alarm text. These values are generated by the subsystem and added to the message when the alarm is raised.

Usually the %d is a number and the %s is text in the context of the message to complete the alarm message. Occasionally other % symbols are also used (for example, %u) for different variables.

## Further information

For more information about:

- The SMS Alarms subsystem, see *SMS Technical Guide*
- Creating and maintaining the SMS Alarm Relay rule set, see *SMS User's Guide*

# PImanager

## Errors

This table defines the error messages for PImanager.

Alarm	Text	Cause	Resolution
210220	Cannot connect to Oracle - exiting	Oracle is not running.	Start Oracle.
210221	Could not make fifo <f> - exiting	The file <f> could not be created.	Check that the "smf_oper" user has sufficient permission to create the file. Check that the disk is not full.
210222	Could not make fifo directory <d> - exiting	The directory <d> could not be created.	Check that the "smf_oper" user has sufficient permission to create the directory. Check that the disk is not full.
201223	Error starting PIbeClient	PIbeClient could not be started.	If PIbeClient should be being started, check PIbeClient exists and is executable. If PIbeClient should not be being started, ensure there is no pi.PIbeClient section in <b>eserv.config</b> .
210225	Error starting PIprocess	PIprocess could not be started.	Check PIprocess exists and is executable.
210226	Exception reading configuration pi.general.oraUser: check format e.g. "oraUser = "/" - cannot continue	The configuration file entry for pi.general.oraUser has syntax errors.	Check the format of <b>eserv.config</b> .

Alarm	Text	Cause	Resolution
-	Exception reading configuration pi.general.synstamp: check format e.g. "synstamp = 'N'" - cannot continue	The configuration file entry for pi.general.synstamp has syntax errors.	Check the format of <b>eserv.config</b> .
-	Exception reading configuration pi.general.timeout: check format e.g. "timeout = 30" - cannot continue	The configuration file entry for pi.general.timeout has syntax errors.	Check the format of <b>eserv.config</b> .
-	Exception reading configuration pi.general.mode: check format e.g. "mode = 0" - cannot continue	The configuration file entry for pi.general.mode has syntax errors.	Check the format of <b>eserv.config</b> .
-	no PProcesses left	All PProcesses have stopped so the PManager has stopped.	Restart the PManager.
210211 210214	PIbeClient is dead	PIbeClient has stopped. See the PIbeClient output for more details.	PManager will attempt to restart the PIbeClient. If this persists, check for additional PIbeClient error messages.
210212	PProcess for port n is dead	A PProcess has stopped. See the PProcess output for more details.	Restart the PManager.
210213	PProcess pid <p> on port <n> timed out. Sending friendly timeout signal	A PProcess has timed out.	A timeout may indicate some problem with the database. Check the database is running correctly.
210358	PProcess pid <p> on port <n> timed out and not responding. Killing it now.	A PProcess has timed out and not responded to the time out signal.	A timeout may indicate some problem with the database. Check the database is running correctly.



Alarm	Text	Cause	Resolution
-	SQL Error: <message>	An Oracle error occurred.	Consult Oracle documentation for the error code.
-	SQL error <n> reading PI_PORTS - exiting	An oracle error occurred reading the PI_PORTS table.	Consult Oracle documentation for the error code.
-	Unknown message type n from PI <p>.	The PProcess on port <p> has sent an unknown message type to the PManager.	Check that the PProcess on port <p> is functioning correctly.

## Warnings

This table defines the warning messages for PManager.

Alarm	Text	Cause	Resolution
-	SQL Warning: <message>	An oracle warning occurred.	Consult oracle documentation for the error code.

## Notifications

This table defines the notification messages for PManager.

Alarm	Text	Cause	Resolution
-	About to turn debug <on off> for PManager	Debug has been turned on or off for the specified PManager.	Information only, no action required.
210229	PManager started	PManager has started.	Information only, no action required.
210230	Received SIGHUP - Sending SIGHUP to PProcesses	PManager has received a SIGHUP.	Information only, no action required.
-	Received SIGINT - Sending SIGINT to PProcesses and exiting	PManager has received a SIGINT.	Information only, no action required.
-	Received SIGQUIT - Sending SIGTERM to PProcesses and exiting	PManager has received a SIGQUIT.	Information only, no action required.

Alarm	Text	Cause	Resolution
210227	Received SIGTERM - Sending SIGTERM to PIprocesses and exiting	PImanager has received a SIGTERM.	Information only, no action required.

## PIprocess

### Error codes - general

This table defines the Error code messages for PI command responses.

Alarm	Text	Cause	Resolution
70	TOO MANY SESSIONS	The maximum allowed number of connections is already in use.	Check whether the number of active sessions is larger than the allowed sessions set in the PI Administration screen. If it is, either: <ul style="list-style-type: none"> <li>this message is information only and no action is required, or</li> <li>increase the number of maximum sessions to accommodate the load.</li> </ul> If it is lower than the specified maximum, contact support with details.
71	LOGON SYNTAX ERROR	Could not parse logon request. The login attempt had a syntax error.	Check that the login command is formatted correctly. Contact Oracle support with details.
72	INVALID LOGON - username, password	Username and/or password are not invalid.	If the username and password should not be recognised by the system, this message is information only, and no action is required. If the username and password should be recognised, either: <ul style="list-style-type: none"> <li>correct the details in the PI Administration screen, or</li> <li>contact support with details.</li> </ul>

Alarm	Text	Cause	Resolution
73	INVALID LOGON - user not allowed on this port	User cannot connect to a server running on the particular port used.	<p>If the port where the attempted logon occurred was not intended as a valid port, this message is information only, and no action is required.</p> <p>If the port should accept connections, either:</p> <ul style="list-style-type: none"> <li>• correct the port number in the PI Administration screen</li> <li>• check that the user is attempting to connect on the correct port, or</li> <li>• contact support with details.</li> </ul>
74	INVALID LOGON - host	Not allowed to connect from this host. The host ip address of the machine that is trying to connect to PI may not be defined in the SMF database.	<p>If the host where the attempted logon was from was not intended as a valid host, this message is information only, and no action is required.</p> <p>If the host should be allowed to make connections, either:</p> <ul style="list-style-type: none"> <li>• correct the host details in the PI Administration screen and restart the PImanager</li> <li>• check that the user is attempting to connect from the correct host, or</li> <li>• contact Oracle support with details.</li> </ul>
75	UNKNOWN COMMAND	The command is not recognised. The command is not defined in the PI_COMMANDS database.	<p>Check the defined commands using the PI Administration screen.</p> <p>Contact Oracle support with details.</p>

Alarm	Text	Cause	Resolution
76	USER DOES NOT HAVE SUFFICIENT SECURITY	The user does not have the privilege to run the requested command.	<p>If the user who attempted to run the command was not intended to be able to run it, this message is information only, and no action is required.</p> <p>If the user should be allowed to run this command, either:</p> <ul style="list-style-type: none"> <li>• correct the details in the PI Administration screen, or</li> <li>• contact support with details.</li> </ul>
77	SYNSTAMP NOT FOUND	The command did not have a synstamp when synstamps are required.	Make sure the command is appended with a synstamp.
78	SYNSTAMP NOT VALID	The synstamp appended to the command was not valid.	Check that the synstamp is larger than the last used synstamp.
79	INVALID OR MISSING MAC	The command was not appended by a security MAC when MACs are required.	Make sure the appended MAC is valid and that the correct MAC key is being used.
80	UNKNOWN PARAMETER FOR COMMAND	A parameter found in the command is recognised.	<p>Check that the command's parameters are as defined in the PI_COMMANDS table by using the PI Administration screen.</p> <p>Contact Oracle support with details.</p>
81	MISSING PARAMETERS FROM COMMAND	One or more required parameters are missing from the command.	<p>Check that the parameters were provided with the command.</p> <p>Check that the command's required parameters are as defined in the PI_COMMANDS table by using the PI Administration screen.</p> <p>Contact Oracle support with details.</p>
83	DUPLICATE PARAMETER	A parameter appeared twice in the command.	<p>Check whether only one parameter was supplied.</p> <p>Contact Oracle support with details.</p>

Alarm	Text	Cause	Resolution
84	ERROR RUNNING PROCEDURE	The message sent to the Provisioning Interface was valid, but a failure occurred when attempting to run the service.	Check syslog for errors. If the problem persists, contact Oracle support with details.
85	USER SESSION TERMINATED	The server has shut down the session. The user's session has been terminated by an administrator issuing the kill management command.	If the session was not intended to be shut down, and the problem persists, contact Oracle support with details.
86	COMMAND TOO BIG	The supplied command was too big.	Check the syntax of the command.
87	COMMAND SYNTAX ERROR	There is a syntax error in the command.	Check the syntax of the command. Contact Oracle support with details.
88	PARAMETER NAME TOO BIG	A parameter name is too big for the command syntax.	Check the parameter name. Contact Oracle support with details.
89	PARAMETER VALUE TOO BIG	A parameter value is too big for the command syntax.	Check the parameter value. Contact Oracle support with details.
90	SYNSTAMP OUT OF PLACE	The synstamp was in the wrong place in the command.	Check that the synstamp is in the correct place: <ul style="list-style-type: none"> <li>• When MAC security is ON, the synstamp should be between the last command parameter and the MAC.</li> <li>• When MAC security is OFF, the synstamp should be at the end of the command, after the last command parameter.</li> </ul> Contact Oracle support with details.
91	TIMEOUT	A timeout has occurred.	A timeout can indicate problems in the database. If the problem persists and there appears to be no other problems the timeout value can be increased.

Alarm	Text	Cause	Resolution
92	INTERNAL ERROR SEE SYSLOG	An internal error has occurred. More information is available from the system log.	If the problem persists, contact Oracle support with details.
93	ERROR READING REPLY FROM FILE	The PI could not read the results from a DB query that were saved to a temporary file.	Contact Oracle support with details.
94	INVALID AUTHENTICATION TOKEN	The authentication token passed has expired or no authentication token was supplied.	The session should be re-started.

## Errors

This table defines the error messages for PProcess.

Alarm	Text	Cause	Resolution
210234	Cannot connect to internal DB - cannot continue	The PProcess could not connect to oracle.	Start Oracle. Check that the oracle environment for the smf_oper UNIX user is correct.
210235 210236	Cannot read from internal DB - cannot continue	The PProcess could not read from the internal DB.	Check that the PI tables are installed correctly on the SMF machine and have at least one port configured.
-	Could not create SQL trace file <filename>. All sql tracing will go to PManager.log. perror for this follows	Could not create a new file.	Check the next reported error which will describe the file error in detail.
210233	Could not make fifo <f>	The fifo file <f> could not be created.	Check that the directory that the file <f> is to be made in is writable by the smf_oper user. Check that the disk is not full.

Alarm	Text	Cause	Resolution
210286	Could not open fifo <f>	The fifo file <f> could not be opened.	Check that the directory that the file <f> is to be made in is writable by the smf_oper user.
-	Could not rename SQL trace file <filename a> to <filename b>. SQL tracing will continue to <filename a>. perror for this follows	Could not create a new file.	Check the next reported error which will describe the file error in detail.
-	Currently got n connections so deferring database re-read until all connections closed	The PIprocess has received an instruction to re-read the internal database. This cannot be done safely with active connections, so will be delayed until all connections are closed	Close all connections to the PI to re-read the database.
210305	Error occurred running C function <f> in shared library <l>. Output is ...	An error occurred while running the command. Check for other errors preceding this error.	Check preceding errors in the PI commands library errors section below.
210306	Error reading request for user <x> on host <h> - logged off	An error occurred reading a command from a remote user. Usually occurs if the user disconnects in the middle of a command. The user is logged off.	The user should re-login.
-	Exception reading configuration pi.authentication.timeout : check format e.g. "timeout = 0" - cannot continue	The configuration file entry for pi.authentication.timeout has syntax errors.	Check the format of <b>eserv.config</b> .

Alarm	Text	Cause	Resolution
-	Exception reading configuration pi.general.logLevel: check format e.g. "loglevel = 0" - cannot continue	The configuration file entry for pi.general.logLevel has syntax errors.	Check the format of <b>eserv.config</b> .
-	Exception reading configuration pi.general.sqlTraceDirectory: check format e.g. "sqlTraceDirectory = "/IN/service_packages/PI/ tmp/trace/" - cannot continue	The configuration file entry for pi.general.sqlTraceDirectory has syntax errors.	Check the format of <b>eserv.config</b> .
-	Exception reading configuration pi.localTZ: check the format - cannot continue	The configuration file entry for pi.localTZ has syntax errors.	Check the format of <b>eserv.config</b> .
-	Exception reading configuration pi.throttling.sendRate: check the format e.g. "sendRate = 0" - cannot continue	The configuration file entry for pi.throttling.sendRate has syntax errors.	Check the format of <b>eserv.config</b> .
-	Exit due to exception: <message>	An internal error has occurred.	Restart the PI. Consult support if persistent.
210260 210371	Oracle connection lost - exiting	The PProcess connection to the database has been lost. The PProcess will restart to reconnect to the database cleanly.	Check the logs for related errors. If this occurs persistently, or the PProcess cannot reconnect, check the oracle database or contact support.
210261	PPID is 1 - PManager has died and not killed me - exiting	The controlling PManager has stopped or been stopped without firstly stopping the PProcesses.	Restart the PManager.



Alarm	Text	Cause	Resolution
210262	Problems setting up socket - cannot continue	The PIprocess could not bind to the port specified in the database, probably due to another process using the port.	Check that the port is not used by another process. Change the port number using the PI Administration screen.
210318	Security warning. Bad MAC in message from user <x>	A user has an incorrect mac on a command.	Check the user and system MAC keys are the same.
210319	Security warning. Bad synstamp in message from user <x>	A user has used an incorrect synstamp.	The next synstamp must be a number larger than the last synstamp returned from the PIprocess or used by the user.
210320	Security warning. Connection from unknown host <h>	A connection has been attempted from a host not listed in the hosts database.	If the host is valid it should be entered into the hosts database using the PI administration screens. Then the PImanager should be sent a SIGHUP signal using the PIreread script to force a database re-read.
210321	Security warning. Invalid login attempt (garbage read) from host <h>	The username/password were not separated by a comma.	Check that the correct format (username,password;) is being used for the login attempt.
210322	Security warning. Invalid login attempt (user on wrong port) from host <h>	A user has tried to connect to a port he is not allowed to connect to.	If the user should be allowed to connect to this port, add the port using the PI administration screens, and then send the PImanager a SIGHUP signal using PIreread.sh to force a database reread.
210323	Security warning. Invalid login attempt (username or password too long) from host <h>	The username/password combination was too long.	Check that the correct username and password combination is being used.

Alarm	Text	Cause	Resolution
210324	Security warning. Invalid login attempt (username, password) from host <h>	Either the username or the password is not correct.	Check that the correct username and password combination are being used.
210325	Security warning. User <x> level <n> requested command level <m>.	A user tried to use a command which has a higher security level than the user's security level.	If the user should be able to use that command, raise the user's security level to at least that command's security level.
Note (1)	Shared Library <l> not loaded: <error message>.	The shared library could not be loaded. The error message will give more detailed information.	Reinstall the package or patch. Contact Oracle support with details.
-	SQL Error: <message>	An oracle error occurred.	Consult oracle documentation for the error code.
210294	Symbol <s> not found is shared library <l>	The code for the specified command is not in the shared library.	Check that the database entry for the command in PI_COMMANDS is correct.
-	Timeout occurred.	The processing of the command timed out.	A timeout can indicate problems with the database or billing engine client resulting in long query times.

**Note (1)** Alarm IDs that would match this message: 210263 – 210270, 210293, 210372, 210373, and 210383.

## Warnings

This table defines the warning messages for PImanager.

Alarm	Text	Cause	Resolution
-	Warning: fifos to PImanager not opened.	The communication files to PImanager were not found or could not be opened.	Check that the files (in /tmp/PIfifo) exist and are read and writable by the smf_oper user.

## Notifications

This table defines the notification messages for PProcess.

Alarm	Text	Cause	Resolution
210214	About to start PProcess	PImanager has attempted to start a PProcess.	Information only, no action required.
-	About to turn debug <on off> for <command>	Debug has been turned on or off for the specified PI command.	Information only, no action required.
-	About to turn debug <on off> for PIbeClient	Debug has been turned on or off for the specified PIbeClient.	Information only, no action required.
-	About to turn debug <on off> for PProcess port <p>	Debug has been turned on or off for the specified PProcess.	Information only, no action required.
-	Debug turned [on off] by PProcess <n>	PImanager debug has been toggled by a PProcess	Information only, no action required.
Note (1)	PProcess started	PProcess has started.	Information only, no action required.
-	Received SIGALRM from PImanager PID <p> UID <u>. Timing out.	PProcess receives a SIGALRM from PImanager and the time out process starts.	Information only, no action required.
-	Received SIGALRM from unknown process PID <p>, UID <u>. Not timing out	PProcess receives a SIGALRM from a process that is not PImanager. The sending process and user is stated.	Information only, no action required.
-	Received SIGHUP from PID <p>, UID <u>	PProcess has received a SIGHUP. The sending process and user is stated.	Information only, no action required.
-	Received SIGINT - Exiting	PProcess has received a SIGINT.	Information only, no action required.
Note (2)	Received SIGTERM - Exiting	PProcess has received a SIGTERM.	Information only, no action required.
-	Received SIGTERM from PID <p>, UID <u>	PProcess receives a SIGTERM. The sending process and user is stated.	Information only, no action required.
-	Received SIGUSR1 from PID <p>, UID <u>	PProcess receives a SIGUSR1. The sending process and user is	Information only, no action required.

Alarm	Text	Cause	Resolution
		stated.	
-	Re-reading internal provisioning database	PIprocess has received a SIGHUP and is re-reading the database.	Information only, no action required.
210307	Shared library <l> successfully loaded.	The shared library has been successfully loaded.	Information only, no action required.
-	Unloading shared library <l>	The database has been re-read after a SIGHUP.	Information only, no action required.
210308	User <x> logged off on host <h>	A user had disconnected.	Information only, no action required.
210309	User <x> logged on from host <h>	A user has successfully logged on.	Information only, no action required.

**Note (1)** Alarm IDs that would match this message: odd numbers from 210327 through 210357.

**Note (2)** Alarm IDs that would match this message: even numbers from 210326 through 210356.

## PIbatch

### Errors

This table defines the error messages for PIbatch.

Alarm	Text	Cause	Resolution
-	Cannot open result file <file> - exiting	The PIbatch could not open the results file for writing.	Check file permissions for the user running the PIbatch.
-	Cannot open script file <file> - exiting	The PIbatch could not open the input script file for reading.	Check file permissions for the user running the PIbatch, and that the file exists.
-	Error reading script file <file> - exiting	The PIbatch could not read the input script file.	Check file permissions for the user running the PIbatch, and that the file exists.
-	Line <n>: Connect line found	Syntax error in the input file.	Correct the input file.

Alarm	Text	Cause	Resolution
	when already connected, disconnecting and will reconnect		
-	Line <n>: Disconnect line when not connected, skipping	Syntax error in the input file.	Correct the input file.
-	Line <n>: Not connected, not sending command	PI command in input file before the connection line.	Correct the input file.
-	Usage: Pibatch <script> <server>	Wrong number of command line arguments.	Usage is "Pibatch <script> <server>"

## Pibatch XML

### Errors

This table defines the error messages for Pibatch XML.

Alarm	Text	Cause	Resolution
-	unable to connect to PI: <message>	Could not connect to PIprocess.	Check the PIprocess is running. Check the hostname is correct. Check the port number is correct.
-	unable to read <filename>: open() failed with <message>	Unable to read the input file.	Check file permissions for the user running the Pibatch, and that the file exists.
-	-l not available when reading from stdin	Looping was requested with no input file	Do not specify looping when the input is standard input.

## Notifications

This table defines the notification messages for PIbatch XML.

Alarm	Text	Cause	Resolution
-	multiple IP addresses for host <h>, using <address>	The PI server has more than one address. The one to be used is stated.	Information only, no action required.