Oracle® Communications Convergent Charging Controller Service Management System Technical Guide



ORACLE

July 2021

Copyright

Copyright © 2021, Oracle and/or its affiliates.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be errorfree. If you find any errors, please report them to us in writing.

If this is software or related documentation that is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, then the following notice is applicable:

U.S. GOVERNMENT END USERS: Oracle programs (including any operating system, integrated software, any programs embedded, installed or activated on delivered hardware, and modifications of such programs) and Oracle computer documentation or other Oracle data delivered to or accessed by U.S. Government end users are "commercial computer software" or "commercial computer software documentation" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, reproduction, duplication, release, display, disclosure, modification, preparation of derivative works, and/or adaptation of i) Oracle programs (including any operating system, integrated software, any programs embedded, installed or activated on delivered hardware, and modifications of such programs), ii) Oracle computer documentation and/or iii) other Oracle data, is subject to the rights and limitations specified in the license contained in the applicable contract. The terms governing the U.S. Government's use of Oracle cloud services are defined by the applicable contract for such services. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Inside are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. AMD, Epyc, and the AMD logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark of The Open Group.

This software or hardware and documentation may provide access to or information about content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services unless otherwise set forth in an applicable agreement between you and Oracle. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services, except as set forth in an applicable agreement between you and Oracle.

Contents

About This Document	vi
Document Conventions	vii

Chapter 1

System Overview	1
Overview	1
What is the Service Management System?	1
Platform Configuration	4
Maintaining Network Connections	6
smsTrigDaemon	7
Alarms	9
Statistics	12
EDRs	15

Chapter 2

Replication Overview	19
Overview	
What is Replication?	
Failover and Error Recovery	
Replication in an Unclustered Installation	23
replication.def File	
replication.config File	

Chapter 3

Replication Check	41
Overview	41
Replication Checks	41
Database Comparisons	
Database Resynchronizations	
Auditing	47

Chapter 4

Overview	49
Configuration Overview	
Configuring the Resource Group in the Clustered Environment	51
Configuring Replication Files	55
Configuring the Oracle Wallet	56
Creating the Oracle Wallet Automatically by Using setupOracleWallet.sh	62
Configuring the Oracle Listener	65
Configuring the SNMP Agent	70
Configuring Connections for CORBA Services	76
SMF AlarmMessage Format	79
Defining the Screen Language	81
Defining the Help Screen Language	83
Setting up the Screens	84
Configuring Nodes	115
Installing Additional Applications	115

Configuring LDAP based SMS Login	115
Chapter 5	
Background Processes on the SMS	
Overview	
cmnConfigRead	
cmnReceiveFiles	
smsAlarmDaemon	
smsAlarmManager	
smsAlarmRelay	
smsConfigDaemon	
smsConfigDaemonScript	
smsCdrArchiver	131
smsCdrProcess.sh	140
smsDbCleanup.sh	140
smsLogCleaner	141
smsMergeDaemon	143
smsMaster	144
smsNamingServer	145
smsReportsDaemon	146
smsReportScheduler	148
smsReportCleanupStartup.sh	150
smsStatsDaemon	151
smsStatisticsWriter	151
smsStatsThreshold	162
smsSendConfig.sh	163
smsTaskAgent	164
smsTrigDaemon	

Chapter 6

Background Processes on the SLC	173
Overview	
smsApplyConfig.sh	
cmnPushFiles	
infMaster	
smsAlarmDaemon	
smsLogCleaner	
smsStatsDaemon	
updateLoader	

Chapter 7

Tools and Utilities	
Overview	
cmnConfigSyntaxCheck	
cmnSU	
compareNode	
comparisonServer	
inetCompareServer	
infoDisplayer	
inputBootstrap	
repConfigWrite	
resyncServer	

setupOracleWallet.sh	
smsCompareResvncClient	
smsCompareResvncServer	
smsDumpRepConfia	
smslorDump	
smsLogTest	
smsManualRequester	
smsProcessCdr	
smsRecordStatistic	
smsStatsQuerv	
startMerge	

Chapter 8

Reports	
Overview	
Reports Database Tables	
Installing a Report Script	
Report Script Worked Example	
Database Auditing	

Chapter 9

Troubleshooting	243
Overview	
Common Troubleshooting Procedures	
Possible Problems	
Index Defragmentation	246

Chapter 10

Pre-installation	
Overview	
SMS Client Specifications	
Preparing the System	
Database Timezone and Backups	
Starting Oracle Automatically on Reboot	

Chapter 11

About Installation and Removal	
Overview	
Installation and Removal Overview	
Raw Devices on Clustered SMS	
Setting up ssh keys	
Checking the Installation	

About This Document

Scope

The scope of this document includes all the information required to install, configure, and administer the Service Management System application.

Audience

This guide was written primarily for system administrators and persons installing, configuring, implementing and administering the USMS application. The documentation assumes that the person using this guide has a good technical knowledge of the system.

Prerequisites

Although there are no prerequisites for using this guide, familiarity with the target platform would be an advantage.

A solid understanding of Unix and a familiarity with IN concepts are an essential prerequisite for safely using the information contained in this technical guide. Attempting to install, remove, configure or otherwise alter the described system without the appropriate background skills, could cause damage to the system; including temporary or permanent incorrect operation, loss of service, and may render your system beyond recovery.

This manual describes system tasks that should only be carried out by suitably trained operators.

Related Documents

The following documents are related to this document:

- Service Management System User's Guide
- SC3.1 Data Service for OPS/RAC <u>https://support.oracle.com/CSP/main/article?type=NOT&id=1000611.1</u>

Document Conventions

Typographical Conventions

The following terms and typographical conventions are used in the Oracle Communications Convergent Charging Controller documentation.

Formatting Convention	Type of Information	
Special Bold	Items you must select, such as names of tabs.	
	Names of database tables and fields.	
Italics	Name of a document, chapter, topic or other publication.	
	Emphasis within text.	
Button	The name of a button to click or a key to press.	
	Example: To close the window, either click Close, or press Esc.	
Key+Key	Key combinations for which the user must press and hold down one key and then press another.	
	Example: Ctrl+P or Alt+F4.	
Monospace	Examples of code or standard output.	
Monospace Bold	Text that you must enter.	
variable	Used to indicate variables or text that should be replaced with an actual value.	
menu option > menu option >	Used to indicate the cascading menu option to be selected.	
	Example: Operator Functions > Report Functions	
hypertext link	Used to indicate a hypertext link.	

Chapter 1 System Overview

Overview

Introduction

This chapter provides a high-level overview of the application. It explains the basic functionality of the system and lists the main components.

It is not intended to advise on any specific Oracle Communications Convergent Charging Controller network or service implications of the product.

In this Chapter

This chapter contains the following topics.

Vhat is the Service Management System?	1
Platform Configuration	4
Maintaining Network Connections	6
smsTrigDaemon	7
Alarms	9
Statistics1	2
EDRs	5

What is the Service Management System?

Description

The Service Management System (SMS) product provides service management support for existing Oracle Communications Convergent Charging Controller Intelligent Network (IN) products.

The primary function of SMS is to provide operators with access to data used by service logic applications.

SMS provides the following:

- A central repository for other IN services, such as ACS and CCS
- Generic functions

The SMS main menu provides access to all installed services. To access any service, select the item from this menu.

Functions

The generic functions of SMS include:

- Security
- Replication
- Statistics gathering
- Alarm Management
- Report generation

• Auditing of Database Changes

SMS component diagram

Here is an example of the main components of the SMS system.



SMS subsystems

There are four main subsystems within SMS:

- Replication
- configuration management
- Reporting functions
- File transfer

Replication

Replication provides the main method of transferring data around the Service Management System. It provides:

- A reliable and fault tolerant delivery of data:
 - From administrators and SLCs into the SMF
 - Changes to persistent data held in the SMF to all relevant SLCs (so all parts of the system have consistent data)
- Alternative network routing between the SLC and SMS under network failure, or buffered updates under complete network failure or SMS downtime
- Disaster recovery in the event of a network failure

Replication moves the following data:

- Configuration data for the smsStatsDaemon
- Configuration data for other installed IN software (such as ACS, CCS and VWS)
- Any update of application data due to the actions of the service running on the SLCs (including client account and call routing data)
- System, application and interface statistics
- Alarms

For more information about replication, see Replication Overview (on page 19).

Reporting Functions

The reporting functions enable the administrator to run reports against the data collected in the SMF.

The reports are configured in the SMS Java administration screens.

Data flow

There are two main methods of data transfer:

- Replication
- File transfer (using ftp)

Process Descriptions

This table describes the main components in SMS.

Process	Role	Further information
smsMaster	Receives update requests and forwards them to the SMF.	s <i>msMaster</i> (on page 144)
SMF	The main SMF on the SMS.	
SCP	The databases on the SLCs. They hold a subset of the data on the SMF.	
updateLoaders	Receives update orders from the smsMaster and inserts them into the SCPs.	<i>updateLoader</i> (on page 192)

Process	Role	Further information
Update Requesters	Update requesters run on SMSs and SLCs and may run on other IPs as well . They send update requests to the smsMaster. They include the smsAlarmDaemon and the smsStatsDaemon.	
smsTaskAgent	Forwards administrator's instructions to the smsMaster.	s <i>msTaskAgent</i> (on page 164)
smsAlarmDaemon	Collects alarms from local sources and forwards them to the smsMaster.	<i>Alarm</i> s (on page 9)
smsAlarmRelay	Monitors the alarms in the SMF and forwards alarms to administrators.	<i>Alarm</i> s (on page 9)
smsReportsDaemon	Enables the user to run reports against the data held in the SMF.	smsReportsDaemon (on page 146)
smsStatsDaemon	Collects statistics and forwards them to the smsMaster.	Statistics (on page 12)

Platform Configuration

Overview

There are three configurations that SMS can be installed on. They are:

- On a single platform
- With one SMS on one platform and one or more SLCs on separate platforms
- With multiple SMSs connected to a RAID array and one or more SLCs on separate platforms

Unclustered platform configuration

Using the unclustered platform configuration, the smsSms package is installed on the SMS. The smsScp package is installed on one or more SLCs.

This configuration provides resilience by using a failover system from the SMS to the SLCs. However, while the SMS is unavailable, no configuration updates can be forwarded to the SLCs.

Unclustered platform configuration diagram

Here is an example of replication in an unclustered installation.



Single platform configuration

Using the single platform configuration, all required SMS functionality is installed on a single platform. Because all SMS functionality is on a single computer the parts of SMS which are involved in connecting the different components are removed.

This results in a simple, easy to administer system. However, because the system runs on one machine, resilience is reduced.

Single platform component diagram

Here is an example of the components in SMS installed on a single platform.



Maintaining Network Connections

Introduction

All replication elements (nodes) establish TCP connections with a master replicator by implicitly connecting to one.

To maintain reliable connection between nodes of the replication system two methods are employed to strengthen the underlying TCP protocol to be used:

- Heartbeating
- Dual network connection

Heartbeating

A simple heartbeating mechanism is used to overcome TCP's failure to detect connection severance (for example, cable failure).

Every node connected to a superior master node sends a periodic heartbeat message to which the master responds with an acknowledgment. This ensures both ends of the connection can detect failure within one heartbeat period.

When a connection fails, the **connecting** element should attempt to reconnect to a superior master. If the superior master is part of a cluster, the connecting element attempts to connect to the next master in the cluster.

Dual Network Connection

The replication system supports dual network connection to overcome a potential single point of failure (that of the underlying transport medium).

Each node can have two addresses by which it can be reached: a primary and a secondary address. These addresses can (and should) be on separate networks.

When a connection to a superior master is required by an element, two connection attempts are made:

- 1 Primary address (over the primary network)
- 2 Secondary address (over a secondary network)

The replication element uses the first connection to succeed, closing the other connection first.

If required, a configurable delay (of up to one second) occurs between the connection attempt to the primary address and the secondary one.

This provides the ability to favor the primary network over the secondary (for example, if one network has a better known latency).

If no delay is configured, the connection attempts occur simultaneously. If both networks have similar latency, the one that ultimately gets used is unpredictable.

smsTrigDaemon

Purpose

smsTrigDaemon manages control plan execution requests. It runs on the SMS platform.

smsTrigDaemon accepts control plan execution requests from either a remote PI client or the Java management screens. It forwards requests to ACS through the xmlTcapInterface on the SLC platform. An indication of whether or not the requests were successful passes back from the ACS to the initiating client.

Architectural overview



This diagram shows smsTrigDaemon and components that surround it.

Message flows

This table describes message the message flows that smsTrigDaemon uses.

Stage	Description
1	The Java management screens send control plan execution requests to smsTrigDaemon over a CORBA transport layer. Each request contains the name of the control plan to be executed, the SLC service handle, the CLI of the subscriber against which the control plan should be executed, an optional called party number and extensions.
2	A remote PI client sends control plan execution to requests to the provisioning interface. As with stage 1, each request contains the name of the control plan to be executed, the SLC service handle, the CLI of the subscriber against which the control plan should be executed, an optional called party number and extensions.
3	The provisioning interface forwards requests to smsTrigDaemon over the FIFO layer transport layer.
4	Using an XML request, smsTrigDaemon forwards the control plan execution request to the xmlTcapInterface on the SLC platform.

Stage	Description
5	The xmlTcapInterface constructs an InitialDP and sends it to ACS through the SLEE.
	For more information about the SLEE, see Service Logic Execution Environment Technical Guide.
6	An indication of success or failure is returned to the xmlTcapInterface using a Connect, Continue or ReleaseCall component.
7	The indication of success or failure is sent to smsTrigDaemon using an HTTP response. smsTrigDaemon then sends the indication back to the client.

Note: Third parties can also send XML requests directly to the xmlTcapInterface.

Components

The smsTrigDaemon interacts with three subsystems:

- Provisioning Interface
- xmlTcapInterface
- SLEE

ΡΙ

The Provisioning Interface (PI) provides a mechanism for manipulating data in the SMF. It enables bulk or scripted operations on SMF data where manual input using the Java management screens would be inefficient.

For more information, see PI User's and Technical Guide.

xmlTcapInterface

The xmlTcapInterface enables the SLEE to inter-work with a TCAP protocol. The interface converts XML messages arriving from smsTrigDaemon into SLEE events. Similarly, the interface converts events arriving from the SLEE into XML messages that smsTrigDaemon understands.

For more information, see XML TCAP Interface Technical Guide.

Alarms

Introduction

Alarms from the SMS and SLCs are collected in the SMF using replication. A set of tools enable management of the alarms in the SMF. Functions include:

- Filtering alarms
- Setting notification destinations
- Monitoring

This functionality is configured using the alarms screens in SMS. For more information about configuring alarms, see *Service Management System User's Guide*.

Alarms can be generated from monitoring statistics.

Alarms diagram



Here is an example of the alarms transfer process.

Alarms replication process

This table describes the stages involved in collecting and reporting about alarms within the SMS system using replication.

Stage	Description
1	 Alarms are collected by the smsAlarmDaemon on the SMS and SLCs. Sources include: The syslog file
	Oracle logs

Stage	Description	
2	The smsAlarmDaemon sends an update request to the superior master (usually the smsMaster).	
	Exception: The smsAlarmDaemon on the SMS makes its updates directly to the SMF, without sending anything to the smsMaster.	
3	When the superior master receives an update request, it inserts the updated data into the SMF_ALARMS_MESSAGE table of the SMF.	
4	The smsAlarmManager matches each alarm instance in the SMF_ALARMS_MESSAGE table with the correct alarm type from the SMF_ALARM_DEFN table, and additional information about the alarm type is saved with the alarm instance.	
5	The smsAlarmRelay process monitors the SMF_ALARMS_MESSAGE table and forwards alarms to the specified external resource.	
	Note: The administrator can run reports on the collected alarms using the reports screens in SMS (which are executed by the smsReportsDaemon).	

Statistics thresholds

Alarms can be generated from specific statistical measures.

The smsStatsThreshold process monitors the SMF_STATISTICS table in the SMF database. When a statistic or statistics match a rule specified in the SMF_STATISTICS_RULE table, the smsStatsThreshold process inserts an alarm record into the SMF_ALARM_MESSAGE table in the SMF database.

For more information about configuring statistics thresholds, see *Service Management System User's Guide*.

Enhanced Fault Management

Enhanced Fault Management (EFM) takes the alarms that are produced by the system and matches alarm instances to information that is held in the database for each alarm type. The alarm instances, including the additional information can then be relayed to an external resource for further processing.

Description of processes and executables

Process	Role	Further information
smsAlarmDaemon	Collects alarms from local sources and forwards them to the smsMaster.	s <i>msAlarmDaemon</i> (on page 121)
smsMaster	Receives alarms from smsAlarmDaemons and forwards them to the SMF.	<i>smsMaster</i> (on page 144)
smsAlarmRelay	Monitors the SMF_ALARM_MESSAGE table in the SMF and forwards alarms to relevant notification points (including SNMP).	<i>smsAlarmRelay</i> (on page 144)
smsReportsDaemon	Enables the user to run reports against the alarms held in the SMF.	smsReportsDaemon (on page 146)
smsStatsThreshold	Monitors the SMF_STATISTICS table in the SMF. If the statistics meet certain rules, the this process creates an alarm and inserts it into the SMF_ALARM_MESSAGE table in the SMF.	<i>smsStatsThreshold</i> (on page 162)

This table describes the roles of the components involved in the alarms process.

Process	Role	Further information
smsAlarmManager	The smsAlarmManager matches alarm instances with the alarm definitions stored in the SMF_ALARM_DEFN table on the SMF, and adds the extra information stored in the definition to each instance of that alarm as it occurs.	<i>smsAlarmManager</i> (on page 123)

Alarm replication and buffering

The smsAlarmDaemon filters alarms before they are sent. This enables:

- Protection against the SMS being flooded with alarms
- Filtering of repeating alarms

For more information about buffering alarms, see smsAlarmDaemon (on page 121).

Statistics

Introduction

Statistics generated by the SMS and SLCs are collected in the SMF_STATISTICS table of the SMF database. A set of tools provides management functions. Functions include:

- Filtering statistics
- Setting rules for statistics thresholds which raise alarms
- Running reports against the statistics held in SMF_STATISTICS

For more information about using these functions, see Service Management System User's Guide.

Statistics collection diagram

Here is an example of the statistics collection process.



Description of processes and executables

This table describes the roles of the components involved in the statistics process.

Process	Role	Further information
smsStatsDaemon	Collects statistics from SLCs and forwards them to smsMaster.	<i>smsStatsDaemon</i> (on page 184).
smsMaster	Receives statistics from the smsStatsDaemons and forwards them to the smsMaster for insertion into the SMF.	<i>smsMaster</i> (on page 144).

Process	Role	Further information
smsReportsDaemon	Enables the user to run reports against the statistics held in the SMF.	smsReportsDaemon (on page 146).
smsStatsThreshold	Monitors the SMF_STATISTICS table in the SMF. If the statistics meet certain rules, the smsStatsThreshold process creates an alarm and forwards it to the smsAlarmDaemon on the SMS.	<i>smsStatsThreshold</i> (on page 162).

Statistics collection process

This table describes the stages involved in collecting statistics within the SMS system using replication.

Stage	Description
1	 Statistics are gathered by the statistics daemon process (smsStatsDaemon) which runs on each SLC platform. Statistics which are collected include: Statistics from the shared memory which are generated by the slee_acs TCAP statistics from files saved by the TCAP interface System statistics from the kernel
2	At regular intervals, the smsStatsDaemon sends the values to the smsMaster process on the SMS platform as an update request.
3	The smsMaster adds the new statistics to the SMF_STATISTICS table in the SMF.

4 The administrator can run reports on the collected statistics using the statistics screens in SMS (which are executed by the smsReportsDaemon).

Statistics thresholds

Alarms can be generated from specific statistical measures.

The smsStatsThreshold process monitors the SMF_STATISTICS table in the SMF database. When a statistic or statistics match a rule specified in the SMF_STATISTICS_RULE table, the smsStatsThreshold process inserts an alarm record into the SMF_ALARM_MESSAGE table in the SMF database.

For more information about configuring statistics thresholds, see *Service Management System User's Guide*.

Statistics collected

The statistics system can collect any SMS-compatible IN application statistics. These are typically coarse values related to the general performance and behavior of the application. Typical statistics values include:

- Total number of requests from SSF
- Number of call instances resulting in error treatment
- Number of calls from invalid geographical locations
- Number of calls reaching successful call completion to international locations
- Number of calls reaching successful call completion to international category one partners Statistics sources may include:
- System statistics from the syslog
- System statistics from the operating system
- Statistics from the Sigtran stack
- Statistics from shared memory

Note: For statistics about call processing, see also Advanced Control Services Technical Guide.

EDRs

Introduction

The SMS software provides a complete, integrated reporting mechanism for Event Detail Records (EDR). It allows the developers of SMS-compatible IN applications to add report functions to their product, through the SMS reports interface.

EDR file transfer diagram

SMS SMS read read smsProcess Export. CDR writefmt SMS Java **EDRs** \$creens querysmsReports EDR Daemon write Reports cmnReceive Files FTP SLC Service SMS Applications cmnPush **EDRs** read Files SLEE Network IF Network

Here is an example of the transfer of files between SLCs and the SMS.

EDR file transfer process

This table describes the stages involved in transferring files around the system using the Common File Transfer process. The files usually transferred are EDRs.

Stage	Description
1	On the SLCs, cmnPushFiles collects files from the configured input directory and transfers them to the configured output directory on the SMS through an stdout. It adds the destination directory to the file.
2	If the transfer fails, cmnPushFiles copies the files to the configured retry directory to attempt the transfer again later.
3	When the files are successfully transferred to the SMS, cmnPushFiles moves the files to the configured completed directory.
4	On the SMS, cmnReceiveFiles scans the configured input directory and moves any files to the directory specified in the file.
5	smsCdrProcess.sh scans its input directory for *.cdr files and moves them to its processed directory.

Description of processes and executables

Process	Role	Further information
cmnPushFiles	Reads files from a specified directory and transfers them to the SMS using stdout. Depending on the success of the transfer, the file is also moved to another directory on the origination SLC.	<i>cmnPushFiles</i> (on page 174)
cmnReceiveFiles	Collects files from the input directory on the SMS and writes them to the specified output directory on the SMS.	<i>cmnReceiveFiles</i> (on page 120)
smsCdrProcess.sh	Provides a set of EDR processing and archiving functions.	s <i>msCdrProcess.sh</i> (on page 140)
smsReportDaemon	Enables the user to run reports against the statistics held in the SMF.	smsReportsDaemon (on page 146)

This table describes the roles of the components involved in the alarms process.

Directory structure and filenames

So that the Unix transfer scripts can locate the output EDR file, the file should be named according to the naming convention. This is usually done by the processes which create the files.

The directory structure which holds the files is in /IN/service_packages/SMS/cdr/.

For more information about the directory structure, see Advanced Control Services Technical Guide.

The file name is *ApplicationID.*cdr. In this case, the complete specification of the currently active EDR filename for the ACS application is *APP_yyyymmddhhmmss.*txt.

Where:

- *APP* is the three letter acronym for the originating process
- *yyyymmddhhmmss* is the date and time the file started to be written to

There is no need for the application to provide any further detail in the file name, as the subsequent processing of the EDR files can perform this. The file names for archived files on the SLC and SMS are detailed in the section that deals with the subsequent processing of these files.

EDR intermediate file format

The intermediate EDR, as output from the SMS EDR API is written to the /IN/service_packages/SMS/cdr/current/ directory.

The format of the file is a | separated list of TAG=VALUE pairs, except for the first entry which is the service name followed by a |. Each record is new line separated.

Example:

```
# File created at 1999060312449
Acs_Service|SN=1800906420|TN=4770360|CGN=9380360|TCS=1999060312449
Acs_Service|SN=1800906421|TN=4770361|CGN=9380361|TCS=1999060312450
Acs_Service|SN=1800906422|TN=4770362|CGN=9380362|TCS=1999060312457
Acs_Service|SN=1800906423|TN=4770363|CGN=9380363|TCS=1999060312521
Acs_Service|SN=1800906424|TN=4770364|CGN=9380364|TCS=1999060312590
Acs_Service|SN=1800906425|CGN=9380365|TCS=1999060312449
Acs_Service|SN=1800906426|CGN=9380366|TCS=1999060312449
Acs_Service|SN=1800906427|TN=4770367|CGN=9380367|TCS=1999060313036
Acs_Service|SN=1800906428|TN=4770368|CGN=9380368|TCS=1999060312036
```

Chapter 2

Replication Overview

Overview

Introduction

This chapter explains the replication system used in SMS.

In this chapter

This chapter contains the following topics.

What is Replication?	19
Failover and Error Recovery	22
Replication in an Unclustered Installation	23
replication.def File	31
replication.config File	38

What is Replication?

Introduction

Replication is the system which transfers data between nodes in the IN installation.

Data flow

The SMF database on the SMS holds the full set of authoritative data within the system. Data required for call processing and resilience is forwarded to the SCP database on the SLCs using SMS replication. Updates are received from processes on the SMSs and the SLCs and from the Service Management System administration screens.



Replication process

This table describes the stages involved in replicating data around the system.

Stage	Description
1	 Update Requests come from one of the following: The administration screens An event on the SMS or SLCs
2	 If the update comes from the administration screens, one of the following occurs: Forwarded to the smsTaskAgent, and then through to an smsMaster Inserted directly into the SMF database If the update request comes from the SMS or SLCs, the relevant update requester sends an update request to an smsMaster (parent).
3	 When an smsMaster (parent) receives an update request, it: a. Sends an update order to all configured destination replication groups (there may be no relevant groups, in which case no order is sent) b. Spawns a local smsMaster (child) process to insert the updated data into the SMF database.
4	updateLoader on the relevant SLCs reads the update order from the socket and inserts the data into the SCP database.

5 If requested to do so, updateLoader sends a confirmation to smsMaster that the update completed successfully.

Nodes

Replication occurs between nodes in the system. Nodes allow specific processes on machines to be replicated to and from, and for more than one node to exist on a single machine. Each node has a node number which identifies the node.

For more information about configuring nodes, see Service Management System User's Guide.

Superior Master Nodes

Superior master nodes are forwarded all data update requests within SMS, and distribute update orders to all SLCs that require the replication data through the updateLoaders.

In a clustered installation, the superior master role is shared between the available smsMaster nodes on the SMSs.

In an unclustered installation, the superior master node is the node with the lowest node number in the system. This is usually the smsMaster on the SMS, but at times may be an infMaster on an SLC.

Update Loader nodes

Update loader nodes run on any SLC that requires database updates. They are the updateLoader processes running on the SLCs. They accept update orders from superior master nodes and insert the data into the local SCP database.

The update loaders on a single SLC platform are independent of each other and are treated as separate replication nodes to the replication system. Hence there can be more than one per machine, although in practice there is normally just one.

An update loader must always be connected to a master. Even if it is not receiving any information from the master, it will have a connection.

Update Requester nodes

Update requesters create update requests in response to specific events on the SLCs and send them to the superior master to update the centralized data (and from there it is replicated to the relevant SLCs). Update requesters include:

- replicationIF
- smsAlarmsDaemons
- smsStatsDaemons

Update requesters do not need to be configured in the database.

Replication groups

A replication table has one or more replication groups. A replication group can be assigned to one or more replication nodes.

Example:

- Replication Group A resides on Node 1, Node 2 and Node 3
- Replication Group B resides on Node 1 and Node 3

Primary replication nodes

Primary nodes can be defined for a specific replication group. The primary is the highest priority destination node for the data defined in the replication group. This enables the IN to assign particular services to specific nodes, but still provide a failover to other nodes as required.

This only sets the node as the primary for the specific group involved and is independent of other groups. A node may be defined as a primary for one group without being a primary for another group.

Example:

- Replication Group A resides on Node 1, Node 2 and Node 3, where Node 3 is the primary for group A.
- Replication Group B resides on Node 1 and Node 3, where Node 1 is the primary for group B.

Primary nodes are not required unless a service is running with different priority on different nodes.

Update requests to primary nodes

Primary node status is relevant for processes which are requesting an smsMaster to update the SMF.

The update processes have three types of Update Requests:

- 1 Make the change and do not confirm that it has been made.
- 2 Send a notification when the change has been made to the SMF.
- **3** Send a notification when the change has been made to the primary replication node for this replication group.

The primary node status is used when the third type of update request is used. While the update may be successful without the primary node being configured, the requesting process may register errors if the notification of the update is not received.

For more information about setting primary and secondary status within a replication group, see *Service Management System User's Guide*.

Master Controllers

A master controller is any process which provides instructions to a superior master node. Possible instructions include:

- Update configuration
- Merge databases
- Resync databases

Master controllers include executables started from the command line and functions embedded in other processes. They include:

- smsTaskAgent
- resyncServer
- smsCompareResyncServer

Failover and Error Recovery

Introduction

If a node becomes unavailable for any reason, the system attempts to continue functioning. The nodes that remain available continue to operate normally. Updates for the node that is unavailable are queued for as long as the queue space lasts.

When the node becomes available again, the queued updates are resent.

If nodes become out of sync to the point where they cannot automatically recover, a manual resync can be run.

updateLoader failure

If the update loader fails, then the updates are queued until it is back on-line. If the Update Loader is still down after a period of time and a smsMaster's pending queue reaches its configured maximum size, then the update loader is marked as "Out Of History" by that smsMaster and its updates are removed. If this happens, after the Update Loader is back on-line, a total database re-synchronization is performed with the smsMaster.

Update queuing

If the nodes become disconnected, a number of processes queue updates until the connection is restored. After the connection is restored, the queued updates execute normally.

smsMaster queues all updates it sends out until an acknowledgment is sent out by the receiving updateLoader. The number of updates that are queued is set in the smsMaster configuration.

updateLoader queues all uncompleted updates in a file named using the following format:

updateLoaderNodeNumber-queuedOrders.dat

Further information

For more information on failover and error recovery processes, see Replication Check (on page 41).

Replication in an Unclustered Installation

Replication component diagram

Here is an example of replication in an unclustered installation.



Replication components

Process	Role	Further information
smsMaster	Runs on the SMS handling updates throughout SMS. This is the superior master for all connected nodes.	<i>smsMaster</i> (on page 144)
infMaster	An infMaster runs on each SLC. If it becomes the node with the highest number of all connected nodes, it stands in as the superior master until a higher node number becomes available again.	<i>infMaster</i> (on page 179)
updateLoaders	An updateLoader runs on each SLC. It manages all incoming update orders and inserts updated data into the SCP.	<i>updateLoader</i> (on page 192)
	At any point in time, an updateLoader is connected to a specific superior master.	
update requesters	update requesters may run on any machine. They send update requests to the Superior Master.	<i>Update Requester nodes</i> (on page 21)
smsMergeDaemon	The smsMergeDaemon runs on the SMS and monitors the connections between the SMS and the SLCs. If it notices a break in the connection, it may start a merge to update the disconnected nodes.	<i>smsMergeDaemon</i> (on page 143)
smsTaskAgent	The smsTaskAgent accepts instructions from the SMS Administration screens and produces instructions for the smsMaster. It generates the replication config file and copies it to the SLC nodes.	<i>smsTaskAgent</i> (on page 164)
smsNamingServer	The smsNamingServer enables non-SMS components to connect to elements within the SMS.	<i>smsNamingServer</i> (on page 145)
SMF	This Oracle database holds authoritative data for all SLCs.	
SCPs	These Oracle databases hold the subset of SMF data required to route calls.	

This table describes the components of replication in an unclustered installation.

Updates

The replication system performs 'row' level updates and buffers updates to reduce processing load on the real-time system elements. This is achieved by holding the update requests in a memory resident queue (called the Pending Updates Queue) until replication has been successfully completed.

Update requests are performed in the order they arrive at the superior master.

Inferior Master Nodes

An inferior master node is a master node with a higher node number than that of the current superior master. It does not perform any function unless it becomes the available master node with the highest node number (in which case it becomes the superior master).

Node numbers

Node Numbers	Description
1	This node number must assigned to the smsMaster process on the SMS.
17-255	These node numbers are available to infMaster processes on the SLCs.
256-511	These node numbers are available to updateLoaders on the SLCs.
512-999	These node numbers are available to updateRequesters. They are usually configured in the following pattern:• 601-699Replication IF nodes• 701-799smsStatsDaemon nodes• 801-899smsAlarmDaemon nodes
1000	In an unclustered installation, this node number is used for the smsMergeDaemon.

This table lists the node number ranges and their details for an unclustered installation.

Note: Node numbers are unique.

Failover

If a node becomes disconnected from the smsMaster node (due to network failure or a problem with the SMS), it attempts to contact the other nodes in descending node number order until it locates a node it can connect to.

An infMaster on one of the SLCs becomes the acting superior master until the failure is resolved. After the smsMaster becomes available again, smsMergeDaemon instructs the infMaster to merge its updates with the smsMaster.

If the infMaster that is the acting superior master becomes unavailable before the smsMaster is available again, the infMaster with the next node number is used instead.

All nodes connected

Here is an example showing all nodes in an unclustered configuration connected to the smsMergeDaemon.



Isolated SLC



This diagram depicts an isolated SLC in an unclustered environment.

Where an SLC has been isolated from the master it looks for and connects to the master in the network, which has the next lowest node number. In the diagram above, SLC1 has been isolated from the network and the update loader cannot find Master 1, so it looks for the master with the lowest node number it can see (in this case it is Inferior Master 2 on SLC1) and connects to that.

The Master 1 queues all updates for SLC1 until such time as it comes back on line. When SLC1 comes back on line, the smsMergeDaemon queries the infMaster process to see if there are any connections to it. If there are any processes connected to the infMaster, the smsMergeDaemon sends a start merge message to the smsMaster. The smsMaster then updates the rest of the network with the information received from SLC1.

If the smsMergeDaemon is not running, the startMerge process may be used instead. startMerge copies the data from SLC1 to the smsMaster. The smsMaster then updates the rest of the network with the information received from SLC1.

Isolated SMS

This diagram depicts an isolated SMS.



Where the master is isolated from the network, each update loader looks for the inferior master with the lowest node number and connects to that.
In the above case the Master 1 on the SMS has been isolated. The update loader on each node looks for the inferior master with the lowest node number it can find, in this case the update loaders on both SLC1 and SLC2 finds and connecst to inferior master 2 on SLC1. When the SMS comes back into the network, the smsMergeDaemon checks each SLC infMaster process to see if there are any connections to them. In this case, there are connections to the SLC1 infMaster process (node 2) from the SLC2 (node 3). The smsMergeDaemon runs startMerge against SLC1. startMerge copies SLC1's data across to the SMS. The smsMaster then attempts to update both SLCs with the new data from SLC1.

All nodes isolated

This diagram depicts all nodes isolated.





Where all nodes in the network are isolated, they each connect to the inferior master with the lowest node number that they can see. In the above example, this results in the update loader on SLC1 connecting to inferior master 2 on SLC1 (node 2), and the update loader on SLC2 connecting to the inferior master 3 (node 3).

As the SLCs reconnect to the SMS and reestablish a reliable heartbeat, the smsMergeDaemons run startMerge against each SLC to copy the data across to the SMS. Then the SMS replicates the data to the available SLCs.

Merging nodes

If a infMaster is acting as a superior master, it collects update requests in a table on the local SCP. When the smsMaster (or another infMaster with a higher node number) reconnects, all local update requests must be forwarded to the new superior master node and replicated.

The process for completing this task is known as a merge. Usually, the smsMergeDaemon initiates a merge automatically when the connection has stabilized. However, it is also possible to start a merge by hand by invoking the startMerge process from the command line.

For more information about using startMerge, see *startMerge* (on page 231).

Description of resync processes and executables

Process	Role	Further information
smsMaster	The smsMaster collects update requests in the pending update queue until the destination updateLoader acknowledges a successful update.	<i>smsMaster</i> (on page 144)
	If the smsMaster cannot connect to a updateLoader, it collects pending updates until a new connection to the updateLoader is made.	
resyncServer	Takes a snapshot of the SMF and sends it to the compareResyncReceive process on the SLC. One resyncServer is started for each resync commenced.	resyncServer
smsCompareResyncServe r	Reads configuration information from the configuration file created by resyncServer and starts a resync.	smsCompareResync Server (on page 208)
compareResyncReceiver	Updates the SCP with the data from the SMF (sent by resyncServer on the SMS).	
smsCompareResyncClient	Receives information from smsCompareResyncServer and updates the SCP.	smsCompareResync Client (on page 205)
updateLoader	When a resync is started, the updateLoader stops making updates to the SCP. Instead it writes the updates to a file named in the following file:	<i>updateLoader</i> (on page 192)
	nodenum-queuedOrders.dat	
	When the resync is completed, the queued update orders are processed as normal.	

This table describes the roles of the components involved in the resync process.

replication.def File

Introduction

The **replication.def** file defines default values for all the replication executables on the node it is on. Any of the defaults may be overridden on the command line when the executable is started.

Example: MAX PENDING=200 can be overridden when starting an smsMaster by adding the command line parameters -maxpending 400 (no spaces in the parameter and all lower case).

Note: Ensure that the heartbeat settings for both ends of a heartbeat are set to the same value. Otherwise, the connection is repeatedly dropped.

This file is located in the /IN/service_packages/SMS/etc/ directory.

Parameters

The replication.def accepts the following configurable parameters.

COMMIT IDLE TIME

Syntax:	COMMIT IDLE TIME=mseconds
Description:	Timeout period (in milliseconds) for the Update Receiver (Update Loader) to become idle after an Update Request (Update Order) and commit.
Туре:	Integer
Optionality:	Optional (default used if not set)
Allowed:	
Default:	100
Notes:	
Example:	COMMIT IDLE TIME=100

COMMIT BUSY TIME

Syntax:	COMMIT BUSY TIME=mseconds
Description:	Timeout period (in milliseconds) for the Update Receiver or updateLoader to commit a change even if it remains continuously busy.
Туре:	Integer
Optionality:	Optional (default used if not set)
Allowed:	
Default:	10000
Notes:	
Example:	COMMIT BUSY TIME=10000
CONFIG DIR	
Syntax:	CONFIG DIR=dir
Description:	The directory where the replication config file is stored. This parameter has been included for future development, it is recommended that the default is always used.
Туре:	String
Optionality:	Optional (default used if not set)
Allowed:	
Default:	/IN/service_packages/SMS/etc

Notes:			
Example:	CONFIG	DIR=/IN/service_	_packages/SMS/etc

CONN RETRY TIME

Syntax:	CONN RETRY TIME=seconds
Description:	Time (in seconds) before an updateLoader tries to reconnect to a master replicator if none is available.
Туре:	Integer
Optionality:	Optional (default used if not set)
Allowed:	
Default:	0
Notes:	If set to 0, no re-attempt is made.
Example:	CONN RETRY TIME=0

CONNECTION TIMEOUT

Syntax:	CONNECTION TIMEOUT=seconds
Description:	Timeout (in seconds) before an attempted connection to a master is terminated and alternative is tried.
Туре:	Integer
Optionality:	Optional (default used if not set)
Allowed:	
Default:	1
Notes:	
Example:	CONNECTION TIMEOUT=1

HB PERIOD

Syntax:	HB PERIOD=seconds
Description:	Heartbeat period (in seconds)
Туре:	Integer
Optionality:	Optional (default used if not set)
Allowed:	
Default:	10
Notes:	The period should be consistent across all platforms. Not advisable to take below 3 seconds.
Example:	HB PERIOD=10

HB TIMEOUT

Syntax:	HB TIMEOUT=seconds
Description:	Heartbeat timeout period (in seconds) used by smsMergeDaemon, before a heartbeat is considered late.
Туре:	Integer
Optionality:	Optional (default used if not set)
Allowed:	
Default:	10
Notes:	Generally set to the same as HB PERIOD.
Example:	HB TIMEOUT=10

HB TOLERANCE

Syntax:	HB TOLERANCE=mseconds
Description:	Heartbeat tolerance time (in millisecs).
Туре:	Integer
Optionality:	Optional (default used if not set)
Allowed:	
Default:	250
Notes:	Default is generally used
Example:	HB TOLERANCE=250
HTML DIR	
Syntax:	HTML DIR=dir
Description:	The directory where html files are written.
Туре:	String
Optionality:	Optional (default used if not set)
Allowed:	
Default:	/IN/html
Notes:	
Example:	HTML DIR=/IN/html
LONG TIMEOUT	
Syntax:	LONG TIMEOUT=seconds
Description:	Heartbeat timeout period (in seconds) used by smsMergeDaemon to check if the connections to smsMaster and the node to be merged are stable.
	If they have both been responding to heartbeats within the time specified in LONG TIMEOUT, the merge takes place.
Туре:	Integer
Optionality:	Optional (default used if not set)
Allowed:	
Default:	60
Notes:	
Example:	LONG TIMEOUT=60
MASTER PORT	
Syntax:	MASTER PORT=port
Description:	The TCP port that master replicators listen for connections on.
Туре:	Integer
Optionality: Allowed:	Optional (default used if not set)
Default:	12343
Notes:	Generally the default is used
Example:	MASTER PORT=12343

Chapter 2

MAXMASTERSNODES

	-
Syntax:	MAXMASTERSNODES=num
Description:	The number of master nodes used.
Туре:	Integer
Optionality:	Optional (default used if not set)
Allowed:	
Default:	8
Notes:	
Example:	MAXMASTERSNODES=8
MAX PENDING	
Syntax:	MAX PENDING=num
Description:	Used by master replicators to determine maximum size of their pending updates queue (the maximum number of outstanding updates that are stored before an unconnected updateLoader is considered "Out Of History").
Туре:	Integer
Optionality:	Optional (default used if not set)
Allowed:	
Default:	10000
Notes:	
Example:	MAX PENDING=10000
NODE ID	
Syntax:	NODE ID=ID
Description:	Used by an updateLoader to define its replication node number. This value must be unique, and is set to the default value at installation. If more than one updateLoader is running on the same SLC machine, you must override this value with a unique number, for example, by setting the nodeid command line parameter.
Туре:	Integer
Optionality:	Required
Default:	274
Example:	NODE ID=274
ORACLE USER	
Syntax:	ORACLE USER=user/pwd
Description:	Oracle username and associated password normally of the form user/password. Operator accounts are used to maintain security.
Туре:	String

 Optionality:
 Optional (default used if not set)

 Allowed:
 /

 Default:
 /

 Notes:
 It is recommended that this is left as the default.

 Example:
 ORACLE USER=/

POLLING INTERVAL

Syntax:	POLLING INTERVAL=useconds
Description:	Used to specify the polling interval (in microseconds) when the smsMaster is not receiving replication updates.
Туре:	Integer
Optionality:	Optional (default used if not set)
Allowed:	
Default:	50000
Notes:	
Example:	POLLING INTERVAL=50000

QUEUE WARN THRESH

Syntax:	QUEUE WARN THRESH=int
Description:	The threshold intervals at which warnings are sent to the error log to indicate an increasing or decreasing pending updates queue.
Туре:	Integer
Optionality:	Optional (default used if not set)
Allowed:	
Default:	50
Notes:	
Example:	QUEUE WARN THRESH=50

QUEUE ERR THRESH

Syntax:	QUEUE ERR THRESH=int	
Description:	The threshold intervals at which a warning is turned into an error and sent to the error log to indicate an increasing/decreasing pending updates queue.	
Туре:	Integer	
Optionality:	Optional (default used if not set)	
Allowed:		
Default:	200	
Notes:	To work correctly, this must be greater than the QUEUE WARN THRESH value.	
Example:	QUEUE ERR THRESH=200	

QUEUE CRIT THRESH

Syntax:	QUEUE CRIT THRESH=int	
Description:	The threshold intervals at which a warning or error is turned into a critical error and sent to the error log to indicate an increasing/decreasing pending updates queue.	
Туре:	Integer	
Optionality:	Optional (default used if not set)	
Allowed:		
Default:		
Notes:	To work correctly, this must be greater than the QUEUE ERR THRESH value.	
Example:	QUEUE CRIT THRESH=400	

Chapter 2

REP PATH

Syntax:	REP_PATH=path
Description:	The directory path of the replication.config file.
Туре:	String
Optionality:	Optional (default used if not set)
Allowed:	
Default:	/IN/service_packages/SMS/etc/replication.config
Notes:	Used by smsMergeDaemon.
Example:	REP_PATH=/IN/service_packages/SMS/etc/replication.config

REPORT DIR

Syntax:	REPORT DIR=dir	
Description:	The directory where replication reports (for example, merge reports and databas comparison reports) are stored.	
Туре:	String	
Optionality:	Optional (default used if not set)	
Allowed:		
Default:	/IN/service_packages/SMS/output/Replication	
Notes:		
Example:	REPORT DIR=/IN/service_packages/SMS/output/Replication	

RESYNC DIR

Syntax:	RESYNC DIR=dir
Description:	The directory where an updateLoader's pendingUpdates.dat file is stored during a resync.
Туре:	String
Optionality:	Optional (default used if not set)
Allowed:	
Default:	IN/service_packages/SMS/tmp
Notes:	
Example:	RESYNC DIR=IN/service_packages/SMS/tmp

SECONDARY DELAY

Syntax:	SECONDARY DELAY=useconds	
Description:	Initial time (in microseconds) that the primary network has to establish a connection before attempting to connect over the secondary network as well.	
Туре:	Integer	
Optionality:	Optional (default used if not set)	
Allowed:		
Default:	100000	
Notes:	A value of 0 means both networks are attempted immediately.	
Example:	SECONDARY DELAY=100000	
SMS_PORT		
Syntax:	SMS_PORT=port	
Description:	The SMS port used by the smsMergeDaemon process.	

36 Service Management System Technical Guide

Туре:	Integer	
Optionality:	Optional (default used if not set)	
Allowed: Default:	7	
Notes:	'	
Example:	SMS_PORT=7	
STATSKEY		
Syntax:	STATSKEY=key	
Description:	Shared memory key for updateLoader replication statistics.	
Туре:	Integer	
Optionality:	Optional (default used if not set).	
Allowed:		
Default:	270198	
Notes:	The default value is recommended. If the default is not used, part of the statistics gathering system (dm_sys) can no longer find the statistics.	
Example:	STATSKEY=270198	
tcpRxMaxBu	ıf	
Syntax:	tcpRxMaxBuf = <i>bytes</i>	
Description:	Sets the receive window size in bytes. This is equivalent to the TCP/IP Tunable Parameter tcp_recv_hiwat and is set via calls to setsockopt(). This will be limited by	
Type:	Integer	
Optionality:	Optional (default used if not set)	

optionality.		
Allowed:	Integer range from 2,048 to 1,073,741,824	
Default:	1,048,576	
Notes:	The parameter default is different than the system default of 24,576.	
Example:	tcpRxMaxBuf = 2048	

tcpTxMaxBuf

Syntax:	tcpTxMaxBuf = <i>bytes</i>
Description:	Sets the transmit window size in bytes. This is equivalent to the TCP/IP Tunable Parameter tcp_xmit_hiwat and is set via calls to setsockopt(). This will be limited by tcp_max_buf, which is the maximum transmit/receive buffer size in bytes.
Туре:	Integer
Optionality:	Optional (default used if not set)
Allowed:	Ranges from 4,096 to 1,073,741,824
Default:	1,048,576
Notes:	The parameter default is different than the system default of 16,384.
Example:	tcpTxBuf = 4096

Example replication.def file

Here is an example $\ensuremath{\textbf{replication.def}}$ file for an SMS platform:

MAX PENDING=10000 ORACLE USER=/ HB PERIOD=20 HB TIMEOUT=20 LONG TIMEOUT=60 HB TOLERANCE=10000 CONNECTION TIMEOUT=2 SECONDARY DELAY=100000 CONN RETRY=1 QUEUE WARN THRESH=5 POLLING INTERVAL=50000

CONN RETRY TIME=10

```
tcpRxMaxBuf=2048
tcpTxMaxBuf=4096
```

replication.config File

Introduction

The **replication.config** file is a binary configuration file that defines the current specific replication setup. It is a binary representation of the replication setup within the SMF created by the repConfigWrite process.

This file is used by all replication nodes on a machine, and must be:

- The same on each machine
- Accessible by each node

The file is written to the directory specified by the output parameter.

Generating replication.config

This file is usually created by clicking **Create Config File** on the **Table Replication** tab of the Node Management window.

Example replication.config

This text shows an example of a **replication.config** file which has been converted using smsDumpRepConfig.

```
smsDumpRepConfig: File /IN/service packages/SMS/etc/replication.config
smsDumpRepConfig: (PAD = 0)
smsDumpRepConfig: Short listing. Use -v (verbose) for full listing
_____
smsDumpRepConfig: Table, Column, Group definitions...
_____
                                            -------
TABLE [ACS CALL PLAN]
TABLE [ACS CALL PLAN PROFILE]
TABLE [ACS CALL PLAN STRUCTURE]
TABLE [ACS CLI CALL PLAN ACTIVATION]
TABLE [ACS CUSTOMER]
TABLE [ACS_CUSTOMER_CLI]
TABLE [ACS_CUSTOMER_SN]
TABLE [ACS_FN_TYPE]
TABLE [ACS GLOBAL PROFILE]
TABLE [ACS LANGUAGE]
TABLE [ACS NETWORK KEY]
TABLE [ACS SN CALL PLAN ACTIVATION]
TABLE [SMF_ALARM_MESSAGE]
TABLE [SMF STATISTICS]
TABLE [SMF STATISTICS DEFN]
```

```
_____
smsDumpRepConfig: Replication Groups configured for each node...
                                                 _____
_____
NODE NUMBER [1] Prim (192.168.0.173) Sec (0.0.0.0)
NODE NUMBER [301] Prim (192.168.0.163) Sec (0.0.0.0)
   GROUP [ACS CUSTOMER] [Prim=-1] Min=('+0','',') Max=('+9','','')
   GROUP [ACS FN TYPE] [Prim=-1] Min=('+0','',') Max=('+9','','')
   GROUP [ACS CALL PLAN PROFILE] [Prim=-1] Min=('+0','',') Max=('+9','','')
   GROUP [ACS_CALL_PLAN_STRUCTURE] [Prim=-1] Min=('+0','',') Max=('+9','','')
   GROUP [ACS CALL PLAN] [Prim=-1] Min=('+0','',') Max=('+9','','')
   GROUP [ACS CUSTOMER CLI] [Prim=-1] Min=('+0','',') Max=('+9','','')
   GROUP [ACS CUSTOMER SN] [Prim=-1] Min=('+0','',') Max=('+9','','')
   GROUP [ACS_LANGUAGE] [Prim=-1] Min=('+0','',') Max=('+9','','')
   GROUP [SMF_STATISTICS_DEFN] [Prim=-1] Min=('!','!',') Max=('~','~','')
   GROUP [ACS CLI CALL PLAN ACTIVATION] [Prim=-1] Min=('+0','',') Max=('+9','','')
   GROUP [ACS GLOBAL PROFILE] [Prim=-1] Min=('+0','',') Max=('+9','','')
   GROUP [ACS NETWORK KEY] [Prim=-1] Min=('+0','',') Max=('+9','','')
   GROUP [ACS SN CALL PLAN ACTIVATION] [Prim=-1] Min=('+0','',') Max=('+9','','')
NODE NUMBER [302] Prim (192.168.0.178) Sec (0.0.0.0)
   GROUP [ACS CUSTOMER] [Prim=-1] Min=('+0','',') Max=('+9','','')
   GROUP [ACS FN TYPE] [Prim=-1] Min=('+0','',') Max=('+9','','')
   GROUP [ACS CALL PLAN PROFILE] [Prim=-1] Min=('+0','',') Max=('+9','','')
   GROUP [ACS_CALL_PLAN_STRUCTURE] [Prim=-1] Min=('+0','',') Max=('+9','','')
   GROUP [ACS CALL PLAN] [Prim=-1] Min=('+0','',') Max=('+9','','')
   GROUP [ACS CUSTOMER CLI] [Prim=-1] Min=('+0','',') Max=('+9','','')
   GROUP [ACS LANGUAGE] [Prim=-1] Min=('+0','',') Max=('+9','','')
   GROUP [SMF_STATISTICS_DEFN] [Prim=-1] Min=('!','!',') Max=('~','~','')
   GROUP [ACS_CLI_CALL_PLAN_ACTIVATION] [Prim=-1] Min=('+0','',') Max=('+9','','')
   GROUP [ACS GLOBAL PROFILE] [Prim=-1] Min=('+0','',') Max=('+9','','')
   GROUP [ACS NETWORK KEY] [Prim=-1] Min=('+0','',') Max=('+9','','')
   GROUP [ACS CUSTOMER SN] [Prim=-1] Min=('+0','',') Max=('+9','','')
```

Further information

For more information, see:

- replication.config File (on page 38)
- smsDumpRepConfig (on page 218)
- Service Management System User's Guide

Chapter 3 Replication Check

Overview

Introduction

This chapter explains replication check and data resychronization processes used in SMS.

In this chapter

This chapter contains the following topics.

Replication Checks	. 41
Database Comparisons	. 43
Database Resynchronizations	. 45
Auditing	. 47

Replication Checks

Description

SMS provides a replication check mechanism to enable operators to check the replication of data across their services network.

A replication check will perform a comparison of the SMF data on each replication node. Once the comparison is complete a report will be generated detailing any discrepancies. No data is changed.

Depending on the size of the data set there may be sizable performance impact on the client node and care should be taken to perform such a check outside of peak times.

Replication check diagram



Here is a diagram that shows the elements involved in replication checks.

Replication check components

This table describes the components involved in replication check process.

Process	Role	Further information
SMF	The main database on the SMS.	
SCP	The databases on the SLCs. They hold a subset of the data on the SMF.	
writeHTMLDirFile	Updates index.html to include new replication, comparison and resynchronization reports.	
smsCompareResyncSe rver	Performs database resynchronizations and comparisons on the superior node.	smsCompareResyncSe rver (on page 208)
smsCompareResyncCli ent	Performs database resynchronizations and comparisons on the inferior node.	smsCompareResyncCli ent (on page 205)
inetCompareServer	Accepts Replication Check requests from the Replication Check screen.	<i>inetCompareServer</i> (on page 198)

Replication check process

The replication check process follows these stages.

Stage	Description
1	The run all command starts inetCompareServer as configured in the replication check report.
2	inetCompareServer configures and starts <i>smsCompareResyncServer</i> (on page 208) and writeHTMLDirFile.
3	smsCompareResyncClient (on page 205) handles the other end of the replication check.
4	writeHTMLDirFile updates index.html to include the new report for display in the screens.

Database Comparisons

Description

compareNode is used to initiate a full database comparison of an SCP database with the definitive copy in SMF db. This ensures that an SCP's data is consistent with the SMF database. Under normal conditions, this should always be the case, but there may be a time (for example, after multiple failures) where the system administrator wants to check an SLC is consistent.

compareNode tool requests a comparison between the contents of SMF and one other node, by invoking comparisonServer. Comparisons are a more time-efficient method than resyncs. compareServer compares all the entries of all tables which are defined to be replicated to specified updateLoader node.

Database comparison diagram

Here is a diagram that shows the elements involved in a database comparison process.



Database comparison components

This table describes the components involved in database comparison process.

Process	Role	Further information
compareNode	Initiates a full database comparison of an SCP with the definitive copy in SMF. Starts comparisonServer.	<i>compareNode</i> (on page 196)
inputBootstrap	Creates configuration files for smsCompareResyncServer from replication.config.	<i>inputBootstrap</i> (on page 200)
smsMaster	Receives update requests and forwards them to the SMF.	s <i>msMaster</i> (on page 144)

Process	Role	Further information
comparisonServer	Creates configuration files for smsCompareResyncServer from replication.config.	
smsCompareResync Client	Performs database resynchronizations and comparisons on the inferior node.	smsCompareResyncCli ent (on page 205)
writeHTMLDirFile	Updates index.html to include new replication, comparison and resynchronization reports.	

Database comparison process

The database comparison process follows these stages.

Step	Action
1	compareNode sends a comparison request to smsMaster.
2	smsMaster configures and starts comparisonServer.
3	inputBootstrap provides configuration for comparisonServer from replication.config.
4	comparisonServer configures and starts smsCompareResyncServer and writeHTMLDirFile.
5	smsCompareResyncClient handles the other end of the comparison.
6	writeHTMLDirFile updates index.html to include the new report for display in the screens.

Database Resynchronizations

Description

Nodes can become out of sync to the point where normal recovery processes cannot rectify the problem. This can happen if there is a network failure for a long period of time, or if there is a fault in the replication process.

If the databases are out of sync, a resynchronization must be run. Resyncs compare the data in two specified nodes and update the inferior database with the different information in the superior database.

Resyncs run automatically if:

- The updateLoader is started with the -resync flag, and there is a queuedOrders.dat file
- The smsMaster has marked that updateLoader node as out of history
- The smsMaster is connected to by an updateLoader which is not in its pending updates queue
- A resync instruction is included in a smsTaskAgent file

Resyncs can also be run from the command line. For more information about running resynchronizations, see *resyncServer* (on page 203).

Database resynchronization diagram

Here is a diagram that shows the elements involved in a database resynchronization process.



Database resynchronization components

This table describes the components involved in database resynchronization process.

Process	Role	Further information
inputBootstrap	Creates configuration files for smsCompareResyncServer from replication.config.	<i>inputBootstrap</i> (on page 200)
resyncServer	Starts smsCompareResyncServer and inputBootstrap for resyncs.	<i>resyncServer</i> (on page 203)
smsCompareResync Client	Performs database resynchronizations and comparisons on the inferior node.	smsCompareResyncCli ent (on page 205)
writeHTMLDirFile	Updates index.html to include new replication, comparison and resynchronization reports.	

Database resynchronization process

The resynchronization process follows these stages.

Stage	Description
1	If the resync has been started from the command line using resync, resync sends a resynchronization request to smsMaster.
2	smsMaster sends a resynchronization request to resyncServer.
3	resyncServer sends a request to inputBootstrap.
4	inputBootstrap reads data from replication.config and creates a configuration file for smsCompareResyncServer.
5	resyncServer starts smsCompareResyncServer in resync mode.
6	smsCompareResyncServer connects to the SMF and smsCompareResyncClient on the inferior node.
7	smsCompareResyncClient accepts the connection and connects to the SCP.
8	smsCompareResyncServer and smsCompareResyncClient resync the databases.
9	smsCompareResyncServer writes a resynchronization report to /IN/html/output/SMS/resyncl <i>inferior_node_numberl</i> yyyymmddhhmmss.report.
10	writeHTMLDirFile updates /IN/html/output/SMS/resync/inferior_node_number/index.html to include the new report.

Auditing

Description

SMS provides an auditing function for all services implemented through it. It tracks all changes made to the SMF database and stores them in the SMF_AUDIT table. It records:

- User's user ID
- IP address of terminal from which the change was made
- Timestamp of the change
- Table changed
- Copy of the record before the change and a copy of the record after the change

Most database tables also have Change User and Change Date columns which record:

- User name of the user that last changed the contents of a table
- Date at which this change was made

User actions that are logged include:

- Changing a user's password
- Performing a search from the Subscriber tab in the Subscriber Management screen, if only one record is found
- Opening a subscriber record in the Edit Subscriber screen
- Viewing an EDR in the EDR viewer
- Logging in and out of the Customer Care Portal (CCP)
- Locking and unlocking the CCP
- Performing a search in the CCP dashboard

• Viewing a subscriber record through the CCP Quick View

Auditing - listAudit.sh

Audit information is produced as a report by running **listAudit.sh**. Run either as a cron job or from command line using this command:

listAudit.sh usr/pwd [start_date] [end_date] [db_user] [table]

Configuring the Environment

Overview

Introduction

This chapter explains the steps required to configure Oracle Communications Convergent Charging Controller Service Management System (SMS).

In this chapter

This chapter contains the following topics.

Configuration Overview	49
Configuring the Resource Group in the Clustered Environment	51
Configuring Replication Files	55
Configuring the Oracle Wallet	56
Creating the Oracle Wallet Automatically by Using setupOracleWallet.sh	62
Configuring the Oracle Listener	65
Configuring the SNMP Agent	70
Configuring Connections for CORBA Services	76
SMF AlarmMessage Format	79
Defining the Screen Language	81
Defining the Help Screen Language	83
Assigning the Oracle Profile to New Users	84
Setting up the Screens	84
Configuring Nodes	. 115
Installing Additional Applications	. 115
Configuring LDAP based SMS Login	. 115

Configuration Overview

Introduction

This topic provides a high level overview of how the SMS application is configured. Configuration details for individual processes are located with the documentation for that process.

Configuration process overview

This table describes the steps involved in configuring SMS for the first time.

Stage	Description
1	 The environment SMS runs in must be configured correctly. This includes: If the directory SMS was installed into was not the recommended directory, setting the root directory
	 If this was a clustered installation, configuring the resource groups Configuring the Oracle wallet Configuring the Oracle listener

Chapter 4, Configuring the Environment 49

Stage	Description
	Configuring the SNMP agent
	 Configuring connections for CORBA services
	Configuring the location of the EDR directories
	Configuring the smf_oper profile
	Configuring the webserver
2	The replication groups must be configured.
3	If the default language for the SMS Java administration screens need changing, the new default language must be configured.

- 4 If the default language for the help system for the SMS Java administration screens needs changing, the new default language must be configured.
- 5 The SMS screen-based configuration must be completed. This includes checking node configuration and statistics configuration.

Configuration components

SMS is configured by the following components:

Component	Locations	Description	Further Information
SMS Java Administration screens	SMS	 The SMS screens provide a graphical interface for configuring many parts of SMS including: Replication Statistics Alarm filtering Reports 	Service Management System User's Guide
replication.def	All machines with running replication agents	This file specifies the configuration parameters for replication. These parameters may also be specified on the command-line for each application.	<i>replication.def File</i> (on page 31)
replication.config	All machines with running replication agents	This file holds a binary version of the configuration held in the SMF. It is copied out to all machines and is required by all replication agent.	<i>replication.config File</i> (on page 38)
logjob.conf	All SMSs	This file is automatically generated when the smsSms package is installed.	<i>logjob.conf</i> (on page 183)
snmp.cfg	All SMSs	This file configures the SNMP agent's details.	<i>Configuring the SNMP Agent</i> (on page 70)
repsib.cfg	All SLCs	This is the template file for the updateRequester program. Other applications typically append template definitions to this file when they are installed, and remove them when they are uninstalled.	

About Configuration for Secure SSL Connection to the Database

Convergent Charging Controller supports secure network logins through Secure Socket Layer (SSL) connections from the Convergent Charging Controller UI to the database. SSL is the default method for connecting to the database when you install Convergent Charging Controller.

To enable SSL connections to the database, the following additional configuration must be set in the **sms.jnlp** file:

- The jnlp.sms.secureConnectionDatabaseHost Java application property (on non-clustered systems) or the jnlp.sms.secureConnectionClusterDatabaseHost Java application property (on clustered systems) must specify the database connection in the CONNECT_DATA part. In addition the PROTOCOL part must be set to TCPS and the PORT part must be set to 2484.
- If present, the jnlp.sms.EncryptedSSLConnection Java application property should be set to true. The Convergent Charging Controller UI connects to the database by using encrypted SSL connections by default.

Note: If you are using non-SSL connections to the database then you must set EncryptedSSLConnection to false. When EncryptedSSLConnection is set to false, the secureConnectionDatabaseHost and the secureConnectionClusterDatabaseHost parameters are ignored.

See Java Application Properties (on page 85) for more information.

In addition, to enable SSL connections to the database:

- The Oracle wallet that identifies the database server must be created on the SMS node, and its location must be specified in the **listener.ora** and **sqlnet.ora** files. See *Configuring the Oracle Wallet* (on page 56) for more information.
- The listener.ora file must be changed to additionally listen on port 2484 by using the TCPS protocol for secure SSL connections to the database. See *Configuring the Oracle Listener* (on page 65) for more information.

Note: The standard Oracle listener TCP port is 1521. However, SSL connections use the standard port for the TCPS protocol, port 2484 instead. If there is a firewall between screen clients and the SMS then you will need to open port 2484 in the firewall.

Configuring the Resource Group in the Clustered Environment

Overview

Certain tasks performed by the cluster require only one instance running across all cluster nodes. For example, an application which modifies a shared data source. There must be a mechanism in place to monitor the running processes and make sure they are restarted when problems arise. This is similar to normal UNIX inittab functionality with the caveat that a process can be restarted on any of the cluster nodes (failover).

Configuration of resource groups must be completed on each node in the cluster.

Starting the webserver failover

Follow these steps to start the httpd failover.

Step	Action
1	Change to the ESERVHttpd directory.
	Example command: cd /opt/ESERVHttpd
2	Read the readme file.
3	Stop apache.
	Example command: /usr/apache/bin/apachectl stop
4	Change to the util directory within the httpd directory.
	Example command: cd util/
5	Start httpd failover using the following command. startHttpd -h <i>hostname</i> -p " <i>port</i> /tcp"
	Where:
	 hostname is the shared hostname for the SMS cluster
	 port is the port number the webserver accepts httpd requests on
	Example command: startHttpd -h smpVirtualCluster -p "80/tcp"
	For more information about shared hostnames for clustered machines, see the Oracle documentation.

Starting the sshd failover

Follow these steps to start the sshd failover.

Step	Action
1	Change to the ESERVSshd directory.
	Example command: cd /opt/ESERVSshd
2	Read the readme file.
3	Stop the sshd.
	Example command: /etc/init.d/sshd stop
4	Change to the util directory in ESERVSshd.
	Example command: cd util
5	Start the sshd failover with the following command: startSshd -h hostname -p "port/tcp"
	Where:
	 hostname is the shared hostname of the SMS cluster
	 port is the port number the sshd should be running on
	Example command: startSshd -h smpVirtualCluster -p "22/tcp"
	For more information about shared hostnames for clustered machines, see the Oracle documentation.

Starting the smsAlarmDaemon failover

Follow these steps to start the smsAlarmDaemon (on page 121) failover.

Step	Action
1	Unset the \$HOSTNAME environmental variable.
	Example commands: echo \$HOSTNAME unset HOSTNAME echo \$HOSTNAME
2	Change to the OracleSmsAlarmDaemon/util directory.
	Example command: cd /opt/OracleSmsAlarmDaemon/util
3	Start the smsAlarmDaemon.
	Example command: ./startSmsAlarmDaemon
	Result: The following information is sent to stdout: Creating a scalable instance Registering resource type <oracle.smsalarmdaemon>done. Creating scalable resource group <smsalarmdaemon-sarg>done. Creating resource <smsalarmdaemon-sars> for the resource type <oracle.smsalarmdaemon>done. Bringing resource group <smsalarmdaemon-sarg> onlinedone.</smsalarmdaemon-sarg></oracle.smsalarmdaemon></smsalarmdaemon-sars></smsalarmdaemon-sarg></oracle.smsalarmdaemon>

Starting the smsAlarmRelay failover

Follow these steps to start the *smsAlarmRelay* (on page 125) failover.

Step	Action
1	Change to the OracleSmsAlarmRelay directory.
	Example command: cd /opt/OracleSmsAlarmRelay
2	Read the readme file.
3	Change to the util directory in the OracleSmsAlarmRelay.
	Example command: cd util
4	Start the smsAlarmRelay.
	Example command: ./startSmsAlarmRelay
	Result: The following information is sent to stdout:
	Creating a failover instance
	Registering resource type <oracle.smsalarmrelay>done.</oracle.smsalarmrelay>
	Creating failover resource group <smsalarmrelay-harg>done.</smsalarmrelay-harg>
	Creating resource <smsalarmrelay-hars> for the resource type</smsalarmrelay-hars>
	<pre><oracle.smsalarmrelay>done.</oracle.smsalarmrelay></pre>
	Bringing resource group <smsalarmrelay-harg> onlinedone.</smsalarmrelay-harg>

Starting the smsNamingServer failover

Follow these steps to start the *smsNamingServer* (on page 145) failover.

Step	Action	
1	Change to the Orac	cleSmsNamingServer/util directory.
	Example command:	cd /opt/OracleSmsNamingServer/util

Step	Action
2	Start the smsNamingServer failover.
	Example command: ./startSmsNamingServer
	Result: The following information is sent to stdout: Creating a scalable instance Registering resource type <oracle.smsnamingserver>done. Creating scalable resource group <smsnamingserver-sarg>done. Creating resource <smsnamingserver-sars> for the resource type <oracle.smsnamingserver>done.</oracle.smsnamingserver></smsnamingserver-sars></smsnamingserver-sarg></oracle.smsnamingserver>
	Bringing resource group <smsnamingserver-sarg> onlinedone.</smsnamingserver-sarg>

Starting the smsReportScheduler failover

Follow these steps to start the *smsReportScheduler* (on page 148) failover.

Action
Change to the OracleSmsReportScheduler/util directory.
Example command: cd /opt/OracleSmsReportScheduler/util
Start the smsReportScheduler failover.
Example command: ./startSmsReportScheduler
Result: The following information is sent to stdout: Creating a failover instance Registering resource type <oracle.smsreportscheduler>done.</oracle.smsreportscheduler>
Creating failover resource group <smsreportscheduler-harg>done. Creating resource <smsreportscheduler-hars> for the resource type <oracle.smsreportscheduler>done. Bringing resource group <smsreportscheduler-harg> onlinedone.</smsreportscheduler-harg></oracle.smsreportscheduler></smsreportscheduler-hars></smsreportscheduler-harg>

Starting the smsReportsDaemon failover

Follow these steps to start the *smsReportsDaemon* (on page 146) failover.

Step	Action
1	Change to the OracleSmsReportsDaemon/util directory.
	Example command: cd /opt/OracleSmsReportsDaemon/util
2	Start the smsReportsDaemon failover.
	Example command: ./startSmsReportsDaemon
	Result: The following information is sent to stdout:
	Creating a scalable instance
	Registering resource type <oracle.smsreportsdaemon>done.</oracle.smsreportsdaemon>
	Creating scalable resource group <smsreportsdaemon-sarg>done.</smsreportsdaemon-sarg>
	Creating resource <smsreportsdaemon-sars> for the resource type</smsreportsdaemon-sars>
	<oracle.smsreportsdaemon>done.</oracle.smsreportsdaemon>
	Bringing resource group <smsreportsdaemon-sarg> onlinedone.</smsreportsdaemon-sarg>

Starting the smsStatsThreshold failover

Follow these steps to start the *smsStatsThreshold* (on page 162) failover.

Step	Action
1	Change to the OracleSmsStatsThreshold/util directory.
	Example command: cd /opt/OracleSmsStatsThreshold/util

Step	Action
2	Start the smsStatsThreshold failover.
	Example command: ./startSmsStatsThreshold
	Result: The following information is sent to stdout: Creating a failover instance Registering resource type <oracle.smsstatsthreshold>done.</oracle.smsstatsthreshold>
	Creating resource <smsstatsthreshold-hars> for the resource type <oracle.smsstatsthreshold>done. Bringing resource group <smsstatsthreshold-harg> onlinedone.</smsstatsthreshold-harg></oracle.smsstatsthreshold></smsstatsthreshold-hars>

Starting the smsTaskAgent failover

Follow these steps to start the *smsTaskAgent* (on page 164) failover.

Step	Action
1	Change to the OracleSmsTaskAgent/util directory.
	Example command: cd /opt/OracleSmsTaskAgent/util
2	Start the smsTaskAgent.
	Example command: ./startSmsTaskAgent
	Result: The following information is sent to stdout: Creating a scalable instance Registering resource type <oracle.smstaskagent>done. Creating scalable resource group <smstaskagent-sarg>done. Creating resource <smstaskagent-sars> for the resource type <oracle.smstaskagent>done. Bringing resource group <smstaskagent-sarg> onlinedone.</smstaskagent-sarg></oracle.smstaskagent></smstaskagent-sars></smstaskagent-sarg></oracle.smstaskagent>

Configuring Replication Files

Introduction

There are two configuration files for replication that may be changed by the administrator.

- replication.def
- replication.config

The replication.config file

The **replication.config** file is created and changed through the Node Management screens in the SMS screens. The user must move tables on the screen from the Available Replication Groups list to the node they are to be replicated to in the Allocated Replication Groups list. Clicking **Create Config File** produces a new **replication.config** file.

The previous configuration is deleted prior to the new configuration being loaded. This does not necessitate the application being restarted, but it causes disruption to service on any of the SLCs.

The **replication.config** file contains the configuration for the whole network. This includes all configuration details needed for smsMasters and infMasters (if necessary).

Implementing changes to the replication.config file

The new replication.config file takes effect after the program called changeConfig is run.

If you make the new configuration from the screens, this will be immediately. If you make the config from the command line, the change can be scheduled.

The replication.def file

The **replication.def** file is configured when the application is installed and should not need to be updated. It contains parameters that may be changed by the operator on start-up.

Implementing change to replication.def

Since **replication.def** is read only when the application starts up, if it does need to be updated and changes are made, the application (updateLoader, infMaster or smsMaster) must be restarted for these changes to take effect. After restart, these changes take effect immediately.

The **Replication.def** file is held on each node in the same directory as the application (updateLoader, infMaster or smsMaster). If changes are made to the SLC configuration, infMaster and updateLoader must be restarted.

Where changes are to be made to the SMS configuration, the smsMasters must be restarted. In an unclustered installation, smsMaster must be shut down by merging it with an infMaster to avoid loss of data and update information.

Example replication.def file

Here is an example of the default **replication.def** file that is installed when you install Convergent Charging Controller:

```
# @(#)replication.def
                        1 2
MAX PENDING=10000
ORACLE USER=/
HB PERIOD=10
HB TIMEOUT=10
HB TOLERENCE=250
CONNECTION TIMEOUT=2
SECONDARY DELAY=100000
CONN RETRY=1
OUEUE WARN THRESH=5
#Some Update Loader values
CONN RETRY TIME=0
RESYNC DIR=/IN/service packages/SMS/tmp
CONFIG DIR=/IN/service packages/SMS/etc
HTML DIR=/IN/html
REPORT DIR=/IN/service packages/SMS/output/Replication
```

Configuring the Oracle Wallet

About the Oracle Wallet

The Oracle wallet is the single-sign-on wallet that is used when connecting securely to the database and that contains certificate information for identifying the Oracle server. You must create the Oracle wallet if you are using secure SSL connections to the database.

The certificate identifying the server must be signed by a certificate authority (CA) either by creating a root CA and self-signing, or by sending a certificate signing request to a commercial CA.

You can create the Oracle wallet and server certificate in the following ways:

• Manually by using the Oracle PKI tool, orapki. The orapki tool provides a uniform interface for manipulating Oracle wallets and certificates. See *Manually Creating the Oracle Wallet* (on page 57) for more information.

• Automatically by using the **setupOracleWallet.sh** script. This script automatically issues the orapki commands and prompts you for the required information. See *Creating the Oracle Wallet Automatically by Using setupOracleWallet.sh* (on page 62) for more information.

On a clustered SMS you should create the Oracle wallet in a file system that is cluster-wide to allow all instances to access the same wallet information in a single location; for example, on a non-clustered SMS node the Oracle wallet is located in the following directory by default:

/u01/app/wallets/oracle/server

However, if **/global** is a shared volume on a cluster then you should use the following directory for the Oracle wallet:

/global/oracle/app/wallets/oracle/server

About Configuring the Location of the Oracle Wallet

The Oracle wallet is used for single sign on to the Oracle server. If you are using secure SSL connections to the database then you must configure the location of the Oracle wallet in the WALLET_LOCATION entry in the **listener.ora** and **sqlnet.ora** files by using the following syntax:

```
WALLET_LOCATION =
   (SOURCE =
        (METHOD = FILE)
        (METHOD_DATA =
        (DIRECTORY = directory))
)
```

Where *directory* is the directory where the Oracle auto-login wallet is located; for example, on a nonclustered system the Oracle wallet default location is:

/u01/app/wallets/oracle/server

On a clustered system, the Oracle wallet default location is:

/global/oracle/app/wallets/oracle/server

Note: On a clustered system you should specify a cluster-wide shared location so that a single Oracle wallet definition can be accessed from all cluster nodes.

In addition you must configure the following entries in the listener.ora and the sqlnet.ora files:

```
SSL_CLIENT_AUTHENTICATION=FALSE
SSL_CIPHER_SUITES = (TLS_RSA_WITH_AES_128_CBC_SHA)
```

You must also set the jnlp.sms.sslCipherSuites Java application property in the sms.jnlp file to the same value as the SSL_CIPHER_SUITES entry.

Manually Creating the Oracle Wallet

The following high-level procedure explains how to create the Oracle wallet by using the Oracle orapki tool, and how to add a trusted or a self-signed certificate to the server wallet.

Follow these steps to create the Oracle wallet and add a trusted or a self-signed certificate to the server wallet.

Step	Action
1	(Optional) Skip this step if you are using a commercial CA to sign the server certificate. If you want to use self-signed certificates, then you must create the wallet container for the root CA. See <i>Creating the Wallet Container for the Root CA</i> (on page 58) for more information.
2	(Optional) Skip this step if you are using a commercial CA to sign the server certificate. If you want to use self-signed certificates, then you must create a self-signed certificate. See <i>Creating a Self-Signed Certificate</i> (on page 59) for more information.
3	Create an Oracle wallet to store the Oracle server certificate. See <i>Creating an Oracle Wallet to Store the Oracle Server Certificate</i> (on page 59) for more information.
4	Add a user certificate to the server wallet. See <i>Adding a User Certificate to the Server Wallet</i> (on page 60) for more information.
5	Export a certificate-signing request from the server wallet. See <i>Exporting the Server Certificate Request</i> (on page 60) for more information.
6	Sign the server certificate request. If you are using:
	 Self-signed certificates, see Signing the Server Certificate Request by Using the Self-Signed Certificate from the Root CA (on page 61) for more information. A commercial CA, see Signing the Server Certificate Request by Using a Commercial CA (see Signing the Server Certificate Request by Using a Commercial CA (see Signing the Server Certificate Request by Using a Commercial CA (see Signing the Server Certificate Request by Using a Commercial CA (see Signing the Server Certificate Request by Using a Commercial CA (see Signing the Server Certificate Request by Using a Commercial CA (see Signing the Server Certificate Request by Using a Commercial CA (see Signing the Server Certificate Request by Using a Commercial CA (see Signing the Server Certificate Request by Using a Commercial CA (see Signing the Server Certificate Request by Using a Commercial CA (see Signing the Server Certificate Request by Using a Commercial CA (see Signing the Server Certificate Request by Using a Commercial CA (see Signing the Server Certificate Request by Using a Commercial CA (see Signing the Server Certificate Request by Using a Commercial CA (see Signing the Server Certificate Request by Using a Commercial CA (see Signing the Server Certificate Request by Using a Commercial CA (see Signing the Server Certificate Request by Using a Commercial CA (see Signing the Server Certificate Request by Using a Commercial CA (see Signing the Server Certificate Request by Using a Commercial CA (see Signing the Server Certificate Request by Using a Commercial CA (see Signing the Server Certificate Request by Using a Commercial CA (see Signing the Server Certificate Request by Using the Server Certificate Request by Using a Commercial CA (see Signing the Server Certificate Request by Using the
	Commercial CA (on page 61) for more information.
7	Configure the pathname to the server wallet in the WALLET_LOCATION entry in the listener.ora and sqlnet.ora files. See <i>About Configuring the Location of the Oracle Wallet</i> (on page 57) for more information.
8	(Optional) Skip this step if you are using a commercial CA. Add the trusted certificates to the keystore on client PCs. See <i>Adding Trusted Certificates to the Keystore on Client PCs</i> (on page 62) for more information.

Creating the Wallet Container for the Root CA

This procedure assumes that Convergent Charging Controller is installed on a non-clustered SMS node and that the following directory has been created for the Oracle wallet:

/u01/app/wallets/oracle

On a clustered SMS the Oracle wallet is located in a file system that is cluster-wide to allow all instances to access the same wallet information in a single location; for example, /global/oracle/app/wallets/oracle.

Follow these steps to create the wallet container for the root CA.

Step	Action
1	Log in to the SMS as user oracle.
2	Go to the directory created for the Oracle wallet, for example:
	cd /u01/app/wallets/oracle
3	Create the wallet container by entering the following command:
	orapki wallet create -wallet ./root

Step	Action
4	When prompted, specify a new password for the root wallet.
	Note: Wallet passwords have length and content validity checks applied to them. Generally passwords should have a minimum length of eight characters and contain alphabetic characters combined with numbers and special characters.
5	Confirm the password. orapki creates the following directory for the root wallet and adds the ewallet.p12 file in root directory: /u01/app/wallets/oracle/root

Creating a Self-Signed Certificate

Follow these steps to create a self-signed certificate in the root wallet and export it to a file named b64certificate.txt.

Step	Action
1	Create a self-signed certificate that is added to the root wallet by entering the following command:
	orapki wallet add -wallet ./root -dn CN=root_CA,C= <i>CC</i> -keysize 2048 - self_signed -validity 3650
	Where root_CA is the self-signed certificate name and CC is the local international country code.
2	When prompted, enter the password for the root wallet.
3	Export the self-signed certificate from the root wallet by entering the following command:
	orapki wallet export -wallet ./root -dn CN=root_CA,C= <i>CC</i> -cert ./root/b64certificate.txt
	Where CC is the local international country code, and the $-cert$ command line option specifies the location of the export certificate.
4	When prompted, enter the password for the root wallet.
	The self-signed certificate is exported to the file b64certificate.txt.

Creating an Oracle Wallet to Store the Oracle Server Certificate

You create an Oracle wallet in the server sub-directory of the wallet directory to store the Oracle server certificate. The server sub-directory is in addition to the root sub-directory that you optionally created for the root CA.

The server wallet is used to authenticate the Oracle server. The location of the Oracle server wallet must be specified in the following WALLET_LOCATION configuration in **listener.ora** and **sqlnet.ora** files:

```
WALLET_LOCATION =
   (SOURCE =
   (METHOD = FILE)
   (METHOD_DATA = (DIRECTORY = server_directory)
   )
```

Where server_directory is the directory you create for the Oracle server certificate; for example:

/u01/app/wallets/oracle/server

See About Configuring the Location of the Oracle Wallet (on page 57) for more information.

Follow these steps to create an Oracle wallet for the server certificate.

Step	Action
1	As user oracle on the SMS node, go to the Oracle wallet directory; for example:
	cd /u01/app/wallets/oracle
2	Create the server wallet by entering the following command:
	orapki wallet create -wallet ./server -auto_login
3	When prompted specify a new password for the server wallet.
	Note: Wallet passwords have length and content validity checks applied to them. Generally passwords should have a minimum length of eight characters and contain alphabetic characters combined with numbers and special characters.
4	Confirm the password.
	orapki creates the /u01/app/wallets/oracle/server directory for the server wallet and adds the following files in the directory:
	cwallet.sso
	ewallet.p12
5	To check that the files have been created, enter the following command:
	ls server

Adding a User Certificate to the Server Wallet

Follow these steps to add a user certificate for the SMS to the server wallet.

Step	Action
1	As user oracle on the SMS, enter the following command to add a user certificate for the SMS to the server wallet:
	orapki wallet add -wallet ./server/ewallet.p12 -dn 'CN=SMS,C=CC' -keysize 2048
0	Where ewallet.p12 is the name of the server wallet and <i>CC</i> is the local international country code.

2 When prompted, enter the password for the server wallet.

Exporting the Server Certificate Request

You export a certificate request from the server wallet so that the request can be signed by a CA.

To export the server certificate request enter the following command as user oracle:

orapki wallet export -wallet ./server -dn 'CN=SMS,C=CC' -request ./server/creq.txt

Where *CC* is the local international country code and **creq.txt** is the name of the server certificate request file.

The server request is exported to the following file in the server directory:

/u01/app/wallets/oracle/server/creq.txt

Signing the Server Certificate Request by Using the Self-Signed Certificate from the Root CA

The following procedure uses the root CA you initially created to sign the certificate request. Alternatively you can send the request to a commercial CA for signing.

Follow these steps to sign the server certificate request.

Step	Action
1	Create the server certificate in the file named cert.txt using the certificate request in the file named creq.txt. As user oracle on the SMS, enter the following command:
	orapki cert create -wallet ./root -request ./server/creq.txt -cert ./server/cert.txt -validity 3650
	Where the command line option:
	 -wallet specifies to use the self-signed certificate in the root CA to sign the server request
	• -cert specifies to create the signed certificate named cert.txt
2	When prompted, enter the password for the root wallet.
3	Add the trusted certificate of the root CA, ./root/b64certificate.txt, and the user certificate signed by the root CA, ./server/cert.txt, into the server wallet by entering the following commands:
	 orapki wallet add -wallet ./server/ewallet.p12 -trusted_cert -cert ./root/b64certificate.txt
	 orapki wallet add -wallet ./server/ewallet.p12 -user_cert - cert ./server/cert.txt
	When prompted, enter the password for the server wallet.

Signing the Server Certificate Request by Using a Commercial CA

Follow these steps to use a commercial CA to sign the server certificate request.

Step	Action
1	Send the certificate request in the file named creq.txt to the commercial CA for signing.
2	When you receive the signed certificate back from the commercial CA, add the commercial CA's trusted public certificate to the server wallet container.
	<pre>orapki wallet add -wallet ./server/ewallet.p12 -trusted_cert -cert trusted_CA_certificate</pre>
	Where trusted_CA_certificate is the file containing the CA's trusted public certificate.
3	When prompted for a password, enter the password for the server wallet.

Step	Action
4	Add the CA-signed server certificate to the server wallet container.
	orapki wallet add -wallet ./server/ewallet.p12 -user_cert -cert CA_signed_certificate
	Where CA_signed_certificate is the signed server certificate from the CA.
5	When prompted, enter the password for the server wallet.

Adding Trusted Certificates to the Keystore on Client PCs

If you are using self-signed certificates then you must update the keystore on client PCs to trust certificates from the SMS server that have been signed by the root CA.

Note: Certificates signed by a commercial CA are already trusted by definition, therefore update the keystore on client PCs only if you are using self-signed certificates.

Follow these steps to add a trusted certificate for the SMS server to the Java keystore on a client PC.

Step	Action
1	Copy the root CA certificate ./root/b64certificate.txt to the client PC.
2	As the Administrator user on the client PC, open the command tool window and enter the following command:
	<pre>keytool -importcert -keystore "path_to_java_lib_security_cacerts" -alias SMS -file "path_to_b64certificate_txt"</pre>
	where:
	 path_to_java_lib_security_cacerts is the path for the cacerts file
	 path_to_b64certificate_txt is the path for the b64certificate.txt file
3	When prompted, enter the password for the keystore.
	Note: The Java installation sets the keystore password to changeit by default.
4	Answer yes to the following prompt:
	Trust this certificate? [no]:
	Oracle keytool updates the keystore on the client PC to trust certificates from the SMS server that have been signed with the root CA.

Creating the Oracle Wallet Automatically by Using setupOracleWallet.sh

About Creating the Oracle Wallet by Using setupOracleWallet.sh

The Oracle wallet is the single-sign-on wallet that is used when connecting securely to the database and that contains certificate information for identifying the Oracle server. You must create the Oracle wallet if you are using secure SSL connections to the database. See *About the Oracle Wallet* (on page 56) for more information.

The **setupOracleWallet.sh** script enables you to automatically run the orapki commands for creating the Oracle wallet. The script prompts you to enter all the information it requires to create the Oracle wallet. See *setupOracleWallet.sh* (on page 203) for more information about **setupOracleWallet.sh**.

When you run **setupOracleWallet.sh**, you specify whether or not you want to use self-signed certificates. If you are using:

- Self-signed certificates, the script completes after creating the Oracle wallet and self-signed certificate. You must then update the Java keystore on client PCs with the trusted certificates. See Adding Trusted Certificates to the Keystore on Client PCs (on page 62) for more information.
- Certificates signed by a commercial CA, the script initially completes after creating the certificate signing request. You must send the certificate signing request to the commercial CA for signing. When the commercial CA returns the signed certificate, you re-run **setupOracleWallet.sh** to add the trusted CA certificate and the signed CA certificate to the Oracle server wallet.

After creating the Oracle wallet, the script prints details of the additional configuration that must be set in the Oracle **listener.ora** and **sqlnet.ora** files. See the discussion on *Configuring the Oracle Listener* (on page 65) for more information.

Information Required by setupOracleWallet.sh

Required Item	Description
Oracle wallet base directory	The base directory for the Oracle wallet. Specify the base directory to use for the Oracle root and Oracle server wallets. On a clustered SMS specify a file system that is cluster-wide to allow all instances to access the same wallet information in a single location. On a non-clustered system the default location for the Oracle wallet base directory is: /u01/app/wallets/oracle/
	On a clustered system the default location for the Oracle wallet base directory is: /global/oracle/app/wallets/oracle/
ISO country code	The local international country (ISO) code for your country. Specify the two-letter code.
Wallet passwords	The password to use for the root CA wallet and the password to use for the server wallet. You will be prompted for the password each time the wallet is accessed.
	Note: Wallet passwords have length and content validity checks applied to them. Generally passwords should have a minimum length of eight characters and contain alphabetic characters combined with numbers and special characters.

The following table lists the information that is required by the **setupOracleWallet.sh** script.

Setting Up the Oracle Wallet to Use Self-Signed Certificates by Using setupOracleWallet.sh

Follow these steps to set up the Oracle server wallet to use self-signed certificates by using **setupOracleWallet.sh**.

Step	Action
1	Log in to the SMS as user oracle.
2	Enter the following command: /IN/service_packages/SMS/bin/setupOracleWallet.sh
3	Answer y to the following prompt:
	Do you wish to proceed with the configuration (y/n) :

Step	Action				
4	Enter the following information as required:				
	 The base directory for the Oracle wallet. Specify the base directory to use for the Oracle root and Oracle server wallets. On a clustered SMS specify a file system that is cluster-wide to allow all instances to access the same wallet information in a single location. The local international country (ISO) code for your country. Specify the two-letter code. The password to use for the root CA wallet and the password to use for the server wallet. You will be prompted for the password each time the wallet is accessed. Note: Wallet passwords have length and content validity checks applied to them. Generally passwords should have a minimum length of eight characters and contain alphabetic 				
	characters combined with numbers and special characters.				
5	Answer y to the following prompt:				
	Would you like to use a self-signed root certificate to sign the SMS server certificate?				
	When processing completes, the self-signed root certificate is exported to the following file:				
	./root/b64certificate.txt				
	Where ./root is a sub-directory of the base directory for the Oracle wallet. You must import this certificate into the Java lib/security/cacerts file on each client PC by using the Java keytool utility. See Adding Trusted Certificates to the Keystore on Client PCs (on page 62) for more information.				
Setting L setupOra	Jp the Oracle Wallet to Use CA-Signed Certificates by Using acleWallet.sh				
Note: This p file:	procedure assumes that the commercial CA's own root certificate is available in the following				
./root/b64cer	tificate.txt				
Where ./roc	t is a sub-directory of the base directory for the Oracle wallet.				
Follow thes using setup	se steps to set up the Oracle server wallet to use certificates signed by a commercial CA by OracleWallet.sh .				
Step	Action				
1	Log in to the SMS as user <i>oracle</i> .				
2	Enter the following command: /IN/service_packages/SMS/bin/setupOracleWallet.sh				
3	Answer y to the following prompt: Do you wish to proceed with the configuration (y/n) :				
Step	Action				
------	---	--	--	--	--
4	Enter the following information as required:				
	• The base directory for the Oracle wallet. Specify the base directory to use for the Oracle root and Oracle server wallets. On a clustered SMS specify a file system that is cluster-wide to allow all instances to access the same wallet information in a single location.				
	 The local international country (ISO) code for your country. Specify the two-letter code. 				
	• The password the password to use for the server wallet. You will be prompted for the password each time the wallet is accessed.				
	Note: Wallet passwords have length and content validity checks applied to them. Generally passwords should have a minimum length of eight characters and contain alphabetic characters combined with numbers and special characters.				
5	Answer n to the following prompt:				
	Would you like to use a self-signed root certificate to sign the SMS server certificate?				
	The script creates the server auto-login wallet and exports the certificate signing request to the following file:				
	./server/creq.txt				
	Where ./server is a sub-directory of the base directory for the Oracle wallet.				
6	Send the certificate signing request to the commercial CA for signing. The commercial CA returns the signed certificate.				
7	Place the signed certificate in the following file: ./server/cert.txt				
8	Place the root certificate from the commercial CA in the following file: ./root/b64certificate.txt				
9	Log in as user oracle on the SMS and enter the following command:				
	<pre>/IN/service_packages/SMS/bin/setupOracleWallet.sh -s ./server/cert.txt -t ./root/b64certificate.txt -w wallet_base_directory</pre>				
	Where:				
	• -s ./server/cert.txt specifies the location of the signed server certificate				
	• -t ./root/b64certificate.txt specifies the location of the root certificate from the commercial CA				
	 -w wallet_base_directory specifies the Oracle wallet base directory 				
	The setupOracleWallet.sh script completes by adding the trusted CA certificate and the CA- signed certificate to the server wallet.				

Configuring the Oracle Listener

Introduction

In order for the database on the SMS node to operate correctly it requires an Oracle listener. The Oracle listener listens for external requests to connect to a database on the SMS node.

The Oracle listener configuration in this section is defined in the **listener.ora** file on the SMS platform only; specific additional configuration is not required on any of the SLC nodes. This is because the **listener.ora** file on the SLC nodes is part of the standard Oracle installation and should not be changed.

The following high-level procedure explains how to add support to the **listener.ora** file to enable access to Oracle database instances by using the TCPS network protocol for secure SSL connections, or by using the TCP network protocol for non-SSL connections. It does not explain how to create a **listener.ora** file. The process of adding support for TCPS or TCP is also described in the Oracle documentation, however it is outlined here for quick reference.

The task of creating or updating the Oracle listener should be performed by your database administrator. See Chapter 5 (Using Sql*Net) in *Understanding Sql*Net*, which is shipped with Oracle 7 for more information about creating an Oracle listener file.

Note: This is not a comprehensive guide to configuring Oracle Database. Configuring and maintaining a database is a non-trivial task, and if you are unsure how to proceed please consult your database administrator.

Procedure

Follow these steps to configure the Oracle listener.

Step	Action
1	Log in to the SMS as user <i>oracle</i> , or enter the following command from a root login to become the user <i>oracle</i> :
	su - oracle
	Note: Logging in as the user <i>oracle</i> ensures that the path to all the Oracle binaries is correct and that file ownership for Oracle files is preserved.
2	Go to the directory containing the listener.ora file. The location of the listener.ora file depends on the version of Oracle Database installed and the options selected at installation. It is located in one of the following directories by default:
	\$ORACLE_HOME/network/admin
3	Edit the listener.ora file by using a text editor such as vi; for example: vi listener.ora

Step Action

```
4
```

Add ADDRESS entries to ADDRESS_LIST to define the SMS hostname, protocols, and ports to use for connecting to the database. Use the following syntax:

```
LISTENER=
(DESCRIPTION_LIST =
(DESCRIPTION=(ADDRESS_LIST=
   (ADDRESS=
    (PROTOCOL=protocol)
    (HOST=hostname)
    (PORT=port_number)
   )))
```

where:

)

- protocol is the protocol to use for connecting to the SMF database. You must specify TCPS for secure SSL connections, or TCP for non-SSL connections
- hostname is the hostname of the SMS node
- port_number is the number of the port on which the listener listens for requests. You must specify 2484 for secure SSL connections, or 1521 for non-SSL connections

Note: The TCPS protocol entry in the listener.ora file must appear after the TCP protocol entry.

Example:

The following example shows ADDRESS_LIST configuration for an SMS node called "hostSMP":

```
LISTENER=
 (DESCRIPTION LIST =
 (DESCRIPTION=(ADDRESS LIST=
    (ADDRESS=
        (PROTOCOL=IPC)
        (KEY=SMF)
        )))
 (DESCRIPTION= (ADDRESS LIST=
    (ADDRESS=
        (PROTOCOL=TCP)
        (HOST=hostSMP)
        (PORT=1521)
        )))
 (DESCRIPTION=(ADDRESS LIST=
    (ADDRESS=
        (PROTOCOL=TCPS)
        (HOST=hostSMP)
        (PORT=2484)
        )))
    )
)
```

Note: The ORACLE_SID for the SMF database is SMF. The listener can be made aware of this by adding an ADDRESS entry to the ADDRESS_LIST.

5

Step Action

The listener also needs to know where it can find the information for any particular ORACLE_SID. This is accomplished through SID_LIST. The listener needs to know the name of the SID, the Oracle home directory and the global database name.

Add an entry to SID_LIST by using the following syntax:

```
SID_LIST_LISTENER=(SID_LIST=
   (SID_DESC=
        (SID_NAME=SMF)
        (ORACLE_HOME=oracle_home_directory)
        (GLOBAL_DBNAME=SMF.Hostname)
   )
)
```

Where:

- oracle_home_directory is the directory in which Oracle Database is installed
- SMF. Hostname is the global database name. Hostname is the hostname of the SMS node

Example

The following example shows SID_LIST configuration for an SMS node called "hostSMP":

```
SID_LIST_LISTENER=(SID_LIST=
    (SID_DESC=
        (SID_NAME=SMF)
        (ORACLE_HOME=/u01/app/oracle/product/12.1.0)
        (GLOBAL_DBNAME=SMF.hostSMP)
    )
)
```

6 Comment out the following entries:

USE_PLUG_AND_PLAY_LISTENER = TRUE USE_CKPFILE_LISTENER = TRUE

Important: Do not change the following settings:

- STARTUP WAIT TIME LISTENER = 0
- CONNECT TIMEOUT LISTENER = 10

7 If you are using SSL connections to the database, set the following lines to these values:

```
SSL_CLIENT_AUTHENTICATION=FALSE
SSL_CIPHER_SUITES=(TLS_RSA_WITH_AES_128_CBC_SHA)
```

Notes: You must also:

- Configure the same entries for SSL_CLIENT_AUTHENTICATION and SSL_CIPHER_SUITES in the sqlnet.ora file.
- Set the jnlp.sms.sslCipherSuites Java application property in sms.jnlp and the SSL_CIPHER_SUITES entry to the same value.
- 8 Save and close the file.

```
9 Stop the listener and then restart the listener using the updated configuration by entering the following commands:
```

```
lsnrctl stop
lsnrctl start
```

Configuring Oracle Listener Java Application properties

You configure the Java application properties for the Oracle listener in the **sms.jnlp** file. The installation process attempts to automatically configure this file for you, but you must check the data in the **sms.jnlp** file to ensure it is completely accurate.

Follow these steps to configure the Java application properties for the Oracle listener.

Step	Action
1	Log on as user <i>root</i> .
2	Edit the /IN/html/sms.jnlp file by using a text editor such as vi; for example: vi /IN/html/sms.jnlp
3	If you are using secure SSL connections to the database on a non-clustered system.

If you are using secure SSL connections to the database on a non-clustered system, configure the jnlp.sms.secureConnectionDatabaseHost application property entry. The parameter value must be all on one line in the JNLP file:

```
<property name="secureConnectionDatabaseHost" value="(DESCRIPTION=
(ADDRESS_LIST= (ADDRESS=(PROTOCOL=TCPS) (HOST=host_ip_addr)(PORT=lport)))
(CONNECT DATA= (SERVICE NAME=db sid )))" />
```

If you are using secure SSL connections to the database on a clustered system, configure the jnlp.sms.secureConnectionClusterDatabaseHost application property entry. The parameter value must be all on one line in the JNLP file:

```
<property name="secureConnectionClusterDatabaseHost" value="(DESCRIPTION=
(ADDRESS_LIST= (ADDRESS=(PROTOCOL=TCPS) (HOST=host_ip_addr)(PORT=lport)))
(CONNECT_DATA= (SERVICE_NAME=db_sid )))" />
```

Where:

- host_ip_addr is the host name or IP address of the SMS node
- *lport* is the listener port for SSL connections using the TCPS protocol. Set LPORT to 2484 for SSL connections.
- *db* sid is the database SID

In addition, for SSL connections the jnlp.sms.EncryptedSSLConnection Java application property must be left undefined or set to true.

```
Example Java application property configuration for SSL connections to the database (non-clustered)
>property name="secureConnectionDatabaseHost" value="(DESCRIPTION=
(ADDRESS_LIST= (ADDRESS=(PROTOCOL=TCPS) (HOST=hostSMP)(PORT=2484)))
(CONNECT_DATA= (SERVICE_NAME=SMF)))" />
> > > > >
```

4 If you are using SSL connections to the database you must set the jnlp.sms.sslCipherSuites Java application property to TLS_RSA_WITH_AES_128_CBC_SHA:

```
cproperty name = "sslCipherSuites" value="(TLS_RSA_WITH_AES_128_CBC_SHA)"
/>
```

Step	Action				
5	If you are using non-SSL connections to the database you must set the jnlp.sms.EncryptedSSLConnection parameter to false, and edit the following application property entries:				
	<property name="host" value="host_ip_addr"></property> <property host"="" name="databaseID" value="hostSMP"></property> <property name="DATABASEID" value="1521:SMF"></property> <property name="EncryptedSSLConnection" value="false"></property>				

6 Save and close the file.

The parameters in the **sms.jnlp** file are updated to reflect those of the Oracle listener.

Note: The **sms.html** file has been deprecated. However, if you upgraded from an earlier version of Convergent Charging Controller, you may continue to use the **sms.html** file. You must ensure that you set parameters to the same value in both the **sms.html** file, and the **sms.jnlp** file.

Configuring the SNMP Agent

Introduction

SNMP trap relaying is not automatically enabled. If you require SNMP trap relaying then you must perform the steps described in this topic.

The SNMP agent supports the following functionality:

- Forwarding of alarms as SNMP traps, using the Alarm Relay mechanism (see Service Management System User's Guide)
- Resynchronization of traps, enabling an SNMP manager to request resend of traps

Traps may be forwarded to multiple SNMP managers.

Note: This is subject to the following restrictions:

- All managers must use the same port to receive SNMP traps;
- All managers must be configured to use the same Community string
- Any triggering of the resynchronization mechanism results in duplicate traps being forwarded to all managers.

Configuring the snmp.cfg file

The SNMP agent is configured via the Alarm Notification screen and the snmp configuration file as described in this section. The configuration file is /IN/service_packages/SMS/etc/snmp.cfg.

The name of the network management station is defined by the destination field in the rule, used to match alarms. This allows alarms to be sent to multiple machines and also to determine which alarms should be sent to which machines. The SNMP-specific parameters are:

```
• TARGET = "SNMP"
```

• DESTINATION = manager_hostname

The other parameters are the same for all destinations and are determined from this configuration file, read at the start up of the smsAlarmRelay program.

In understanding these parameters, you must be familiar with the Simple Network Management Protocol (SNMP).

We currently support SNMP v3 (IETF STD0062). SNMP v1 (IETF RFC1157) traps are supported for backward compatibility purposes only.

To support integration with as broad a range of SNMP managers as possible, two forms of SNMP trap are supported:

- Opaque traps include all of the fault data in a single structured data type
- Multiple variable traps, wherein each fault datum is represented by a distinct trap variable

A single trap type must be chosen for each installation. See the "opaque" and "specific" configuration parameter descriptions below for details.

SNMP relaying - switching on

Follow these steps to turn on SNMP relaying of alarms.

Note: Like any command line switches, the -p can appear at any point in the command line. -p is a parameter without any options, and is used to enable SNMP relaying of alarms. SNMP relaying of alarms is off by default.

Step	Action
1	Open the snmp.cfg script with a text editor such as vi. The snmp.cfg file is located here by default:
	/IN/service_packages/SMS/etc/snmp.cfg
2	Add -p to the command line.
-	

3 Save and close the file.

snmp.cfg example

This text shows the content of an example snmp.cfg file.

```
use-SNMPv3: 1
listenPort: 1161
userName: smf_oper
community: public
my-addr: addr
trap: 6
specific: 1
opaque: 1
port: 162
```

snmp.cfg file parameters

The parameters available in this file are described below. The only parameter that you are required to modify is "my-addr"; the rest are given for reference only.

Note: Separate the parameter from the value using the colon ':'.

community

Syntax:	community: type
Description:	The community to which smsAlarmRelay belongs.

Туре:	String
Optionality:	Required
Allowed:	
Default:	public
Notes:	
Example:	community: public
listenPort	
Syntax:	listenPort: port
Description:	The UDP port number from which smsAlarmRelay listens for ${\tt get-}$ and ${\tt set-}$ variable requests.
Туре:	Integer
Optionality:	Required
Allowed:	1 - 65535
Default:	
Notes:	If the use-SNMPv3 parameter is set to 0, the listenPort parameter has no effect.
Example:	listenPort: 1161
my-addr	
Syntax:	my-addr: addr
Description:	The Internet Protocol (IP) address of the computer on which smsAlarmRelay is installed.
Туре:	String
Optionality:	Required
Allowed:	May be either a symbolic host name or an Internet protocol number expressed in dotted-decimal format.
Default:	
Notes:	In SNMP terminology, addr is called agent-addr.
	Most hosts have at least two addresses, the second one being the loop-back address: 127.0.0.1.
Example:	A symbolic host name might be SMS_main_1.
	my-addr: SMS_main_1
	An Internet protocol number could be 192.0.2.0.
	my-addr: 192.0.2.0
my-oid	
Syntax:	my-oid: <i>id</i>
Description:	The alarm parameter argument assigned to Oracle.
Туре:	String
Optionality:	Optional (deprecated)
Allowed:	1.2.36.52947743
Default:	1.2.36.52947743
Notes:	
Example:	

notification-oid

Syntax:	notification-oid: <i>str</i>					
Description:	A variable that can be queried or changed remotely.					
Туре:	String					
Optionality:	Optional (deprecated)					
Allowed:	Constructed from the value of the param-oid parameter to which is appended two additional digits. The value of each digit is determined by the format of alarms.					
	1.2.30	6.52947743	3.1.1 Opa	aque encodin	ng of Oracle fields.	
	1.2.36	6.52947743	3.1.2 id, . cpu	3 = machine , etc.	, .4 = time, .5 =	
	1.2.36	6.52947743	3.2.1 Opa	aque encodin	ng of X.733 fields.	
	1.2.30	6.52947743	3.2.2 Mai type	naged object e, etc.	instance, .3 event	
Default:	1.2.36	.52947743	.2.1			
Notes:	 The notification-oid parameter requires that: The use-SNMPv3 parameter is set for SNMP version 3. 					
	•	The list	tenPort p a	arameter is c	onfigured.	
Example:						
opaque						
Syntax:	opaqı	ue: 0 1				
Description:	Defines encoding for SNMP specific traps.					
Туре:	Boolean					
Optionality:	Requi	red if the sp	pecific (c	n page 74) p	arameter is used.	
Allowed:	0 Use if specific is set to 2 or 4.					
	1	Use if	specific	is set to 1 or	3.	
Default:						
Notes:	The va	alue depen	ds on the va	alue assigned	to the specific parameter.	
Example:	opaqı	1e: 1				
param-oid						
Syntax:	paran	n-oid: <i>ic</i>	d			
Description:	The alarm parameter argument assigned to Oracle.					
Туре:	String					
Optionality:	Optional (deprecated)					
Allowed:	1.2.36	.52947743				
Default:	1.2.36	.52947743				
Notes:	The <i>ia</i>	is construc	cted from th	e values of th	ne sub-parameters listed below.	
	iso	country	australia	Oracle		
	1	2	36	52947743		
Example:						

Chapter 4

port

-						
Syntax:	port: port					
Description:	The Internet Protocol (IP) port number of the remote SNMP manager computer.					
Туре:	Integer					
Optionality:	Required					
Allowed:	1 - 65535					
Default:	162					
Notes:	162 is the SNMP trap port.					
Example:	port: 162					
specific						
Syntax:	specific: int					
Description:	An SNMP-specific trap parameter.					
Type:	Integer					
Optionality:	Required if you set the opague parameter					
Allowed:	1 A single opaque binding.					
	2 Multiple variable bindings per trap. for each					
	parameter.					
	3 A single opaque binding in x733 format.					
	4 Multiple x733 variable bindings per trap.					
Default:						
Notes:	If you use the specific parameter, you must also set the opaque parameter.					
Example:	specific: 1					
trap						
Syntax:	trap: int					
Description:	The value of the generic trap.					
Туре:	Integer					
Optionality:	Required					
Allowed:	6					
Default:	6					
Notes:						
Example:	trap: 6					
use-SNMPv3						
Syntax:	use-SNMPv3: 0 1					
Description:	The version of the SNMP implementation.					
Туре:	Integer					
Optionality:	Required					
Allowed:	0 SNMPv1 is enabled					
	1 SNMPv3 is enabled					
Default:	1					
Notes:						

use-SNMPv3: 1

Example:

userName	
Syntax:	userName: name
Description:	Used by smsAlarmRelay when it listens on a standard SNMP port that has already been opened.
Туре:	String
Optionality:	Required
Allowed:	
Default:	smf_oper
Notes:	In order to open the standard SNMP port, smsAlarmRelay needs root privileges Once the port is open, smsAlarmRelay's privileges are restricted to those assigned to <i>name</i> .
Example:	userName: smf_oper

Formatting an SNMP trap message

The format of SNMP messages is defined in IETF STD0062.

At the top level the "Message" element has the "version" field set in accordance with the SNMP version set by the "use-SNMPv3" configuration parameter. The rest of the formatting differs according to the SNMP version that is being used.

SNMP v1

The SNMP v1 message is built up from each line of this table.

Part	Set from
version	Set by the use-SNMPv3 configuration parameter.
community	Set via the community configuration parameter.
enterprise	Set using the my-oid configuration parameter.
agent-addr	The IP address of the SMS set using my-addr parameter.
generic-trap	Set using the trap configuration parameter.
specific-trap	Set using the the specific parameter.

SNMP v3

The SNMP v3 message is built up as follows.

- version set by the use-SNMPv3 configuration parameter
- Global Header including a usm security model
- security parameters
 - authoritative Engine ID security ID
 - engine boots record of the number of boots of the alarmRelay
 - engine time record of the up of the alarmRelay
- context engine ID PID of smsAlarmRelay
- context name "smsAlarmRelay"
- v2 trap PDU
 - error status
 - error index

variable bindings

The variable-bindings take one of two forms, in accordance with the settings of the opaque (on page 73) and specific (on page 74) configuration parameters.

The opaque form is composed of a sequence containing a single item. That single item is itself a sequence comprising of a pair. The pair is the object ID of the alarm (obtained from the configuration file) and the alarm data itself encased as an "Opaque" data item.

The multiple variable form is composed of a sequence of pairs, each pair being an object ID identifying the variable and the variable values. The object IDs and variable datatypes are specified in the MIB.

See *SMF AlarmMessage Format* (see "*Configuring the SNMP Agent*" on page 70, on page 79) for the ASN.1 format of the alarm data.

Transmission of the SNMP trap message

Given the trap message that has been previously formatted we can now send it to the network management station. As defined in RFC 1157, the message is sent over the User Datagram Protocol (UDP). The destination IP address and the port are specified in the configuration file.

Failure to send the trap does not raise an alarm as this would lead to an infinite loop of alarm messages.

Starting and stopping

The SNMP additions to the smsAlarmRelay send a "start" trap to all configured destinations when it starts up. Similarly, it sends a "stopped" trap and process shutdown.

Restarting the smsAlarmRelay

By default, SNMP trap relaying is not performed. Therefore the smsAlarmRelayStartup.sh script must be edited and the smsAlarmRelay (on page 125) process restarted using the steps below.

Follow these steps to restart the smsAlarmRelay daemon.

Step	Action
1	Type following command to find the process ID: ps -ef grep smsAlarmRelay
	Note: The second column of the results returned is the process ID and the third column gives the parent process ID.
	Kill the process ID from the second column.
2	Type kill -TERM pid
	Result: The process is terminated and is restarted by the inittab process.

Configuring Connections for CORBA Services

About CORBA Services Configuration

The CorbaServices section in the **eserv.config** configuration file defines common connection parameters for CORBA services on SMS nodes. The CorbaServices configuration overrides the default and command-line values specified for CORBA listen ports and addresses.

If you are using IP version 6 addresses, then you must include the CorbaServices section in the **eserv.config** file on SMS nodes. This section is optional if you are using only IP version 4 addresses.

The CorbaServices section includes the following required parameters:

- AddressInIOR
- smsTaskAgentOrbListenPort
- smsReportDaemonOrbListenPort
- smsTrigDaemonOrbListenPort
- ccsBeOrbListenPort

Example CORBA Services Configuration on the SMS

The following example shows the CorbaServices configuration section in the **eserv.config** file for CORBA services on the SMS node.

```
CorbaServices = {
   AddressInIOR = "sms_machine.oracle.com"
   OrbListenAddresses = [
        "2001:db8:0:1050:0005:ffff:ffff:326b"
        "192.0.2.0"
   smsTaskAgentOrbListenPort = 6332
   smsReportDaemonListenPort = 6333
   smsTrigDaemonOrbListenPort = 6334
   ccsBeOrbListenPort = 6335
}
```

CorbaServices Parameters

You specify CORBA services configuration in the CorbaServices section of the **eserv.config** file on SMS and SLC nodes. The CorbaServices configuration supports the following parameters:

AddressInIOR

Syntax:	AddressInIOR = "str"	
Description:	The hostname or IP address to place in the IOR (Interoperable Object Reference) for the CORBA service.	
Туре:	String	
Optionality:	Required (on SMS nodes only)	
Allowed:	Hostname, IP version 6 address, or IP version 4 address	
Default:		
Notes:		
Examples:	AddressInIOR = "2001:db8:0:1050:0005:ffff:ffff:326b"	
	AddressInIOR = "192.0.2.0"	
	AddressInIOR = "sms03xxx.us.oracle.com"	
OrbListenA	Addresses	
Syntax:	OrbListenAddresses = [
-	"str"	

	["str"]
]
Description:	List of IP addresses on which the CORBA service listens for incoming requests.
Туре:	Array
Optionality:	Optional (on SMS nodes only)
Allowed:	IP version 6 addresses, and IP version 4 addresses

Default:

Notes:	If the OrbListAddresses parameter is not set, or you do not specify any IP addresses, then the CORBA service listens on all the IP addresses available on the host. Loopback IP addresses and special IP addresses, as defined in RFC 5156, are excluded.
Example:	<pre>OrbListenAddresses = ["2001:db8:0:1050:0005:ffff:ffff:326b" "192.0.2.0"]</pre>

smsTaskAgentOrbListenPort

Syntax:	<pre>smsTaskAgentOrbListenPort = int</pre>	
Description:	The number of the port on which smsTaskAgentOrb listens.	
Туре:	Integer	
Optionality:	Required (on SMS nodes only)	
Allowed:		
Default:		
Notes:	Overrides the CORBA service port specified for the smsTaskAgent process in the -s command-line parameter. For more information, see <i>smsTaskAgent</i> (on page 164).	
Example:	smsTaskAgentOrbListenPort = 6332	

smsReportDaemonOrbListenPort

Syntax:	<pre>smsReportDaemonOrbListenPort = int</pre>	
Description:	The number of the port on which smsReportDaemonOrb listens.	
Туре:	Integer	
Optionality:	Required (on SMS nodes only)	
Allowed:		
Default:		
Notes:	Overrides the CORBA listen port specified for the smsReportDaemon process in the -s command-line parameter. For more information about smsReportDaemon, see <i>smsReportsDaemon</i> (on page 146).	
Example:	<pre>smsReportDaemonOrbListenPort = 6333</pre>	

smsTrigDaemonOrbListenPort

Syntax:	<pre>smsTrigDaemonOrbListenPort = int</pre>		
Description:	The number of the port on which smsTrigDaemonOrb listens.		
Туре:	Integer		
Optionality:	Required (on SMS nodes only)		
Allowed:			
Default:			
Notes:	Overrides the smsTrigDaemon CORBA listen port set in the listenPort parameter in the triggering section of the eserv.config file. For more information about smsTrigDaemon, see <i>smsTrigDaemon</i> (on page 167).		
Example:	<pre>smsTrigDaemonOrbListenPort = 6334</pre>		

ccsBeOrbListenPort

Syntax:	ccsBeOrbListenPort = int
Description:	The number of the port on which ccsBeOrb listens.

Type: Optionality: Allowed: Default:	Integer Required (on SMS nodes only)
Notes:	Overrides the CORBA listen port specified for the ccsBeOrb process in the <code>listenPort</code> parameter. For more information, see <i>Charging Control Services Technical Guide</i> .
Example:	ccsBeOrbListenPort = 6335

SMF AlarmMessage Format

Introduction

This topic provides the format of the SMFalarmMessage including the MIB definitions.

Alarm Table fields

This table defines the layout of the SMF_ALARM_MESSAGE and SMF_ALARM_DEFN tables in the SMF from which the alarms are derived.

Name	Field size	Field type	Null value
id	38	NUMBER	not null
machine	16 (15 characters for hostname; 1 terminating charater)	VARCHAR2	not null
time		DATE	not null
сри	3	NUMBER	not null
name	6	NUMBER	not null
subsystem	24	VARCHAR2	not null
severity	1	NUMBER	not null
description	256	VARCHAR2	
opcomment	256	VARCHAR2	
count	4	NUMBER	not null
close_time		DATE	
status	7	VARCHAR2	
change_sequence	38	NUMBER	
managed_object_instan ce	2000	VARCHAR2	
event_type	2	NUMBER	
probable_cause	4	NUMBER	
specific_problem	256	VARCHAR2	
perceived_severity	1	NUMBER	
additional_text	1000	VARCHAR2	

MIB field mappings - SMF_ALARM_MESSAGE

This table provides the SMF_ALARM_MESSAGE to MIB field mappings.

DB Alarm		МІВ
0	id	Mapped directly (unique ID)
1	machine	Mapped directly (hostname)
2	time	Mapped directly ("YYYYMMDDHHMMSS"
3	сри	Mapped directly (CPU number)
4	name	= 0 for Solaris & HPUX
6	subsystem	Mapped directly (process identifier)
7	severity	Mapped directly (0=NOTICE, 2=WARNING, 4=ERROR, 6=CRITICAL, 8=CLEARANCE)
8	description	Mapped directly (free text)
9	opcomment	Mapped directly (free text)
10	count	Mapped directly (number of duplicates)
	close_time	Not sent
5	status	Mapped directly ("OPEN", "PENDING", "CLOSED")
	change_sequence	Not sent

MIB field mappings - SMF_ALARM_MESSAGE

This table provides the SMF_ALARM_MESSAGE to MIB field mappings.

DB Alarm		МІВ
0	id	Mapped directly (unique ID)
1	machine	Mapped directly (hostname)
2	time	Mapped directly ("YYYYMMDDHHMMSS"
3	сри	Mapped directly (CPU number)
4	name	= 0 for Solaris
6	subsystem	Mapped directly (process identifier)
7	severity	Mapped directly (0=NOTICE, 2=WARNING, 4=ERROR, 6=CRITICAL, 8=CLEARANCE)
8	description	Mapped directly (free text)
9	opcomment	Mapped directly (free text)
10	count	Mapped directly (number of duplicates)
	close_time	Not sent
5	status	Mapped directly ("OPEN", "PENDING", "CLOSED")
	change_sequence	Not sent

MIB field mappings - SMF_ALARM_DEFN

This table provides the SMF_ALARM_DEFN to MIB field mappings.

DB Alarm	МІВ
Alarm_type_id	not sent

80 Service Management System Technical Guide

DB Alarm	MIB
event_type	Mapped directly (event_type)
probable_cause	Mapped directly (probable_cause)
severity	Mapped directly (severity)
specific_problem	Mapped directly (specific_problem)
recommended_action	not sent
additional_text	Prefixed with description and mapped to additional_text
present_to_am	not sent
present_to_ar	not sent
autoclear period	not sent
regular_expression	not sent
notes	not sent

SMF Listen Messages

An SNMP manager may trigger the resend of traps by setting eServDataLastChgSeq to the value of the identifier (id or eServId) of the last successfully received trap.

Note: Use of this mechanism will cause traps to be sent to all active SNMP managers.

Defining the Screen Language

Introduction

The default language file sets the language that the Java administration screens start in. The user can change to another language after logging in.

The default language can be changed by the system administrator.

By default, the language is set to English. If English is your preferred language, you can skip this step and proceed to the next configuration task, *Defining the Help Screen Language* (on page 83).

Default.lang

When SMS is installed, a file called **Default.lang** is created in the application's language directory in the screens module. This contains a soft-link to the language file that defines the language used by the screens.

If a **Default.lang** file is not present, the **English.lang** file is used.

The SMS Default.lang file is:

/IN/html/SMS/language/Default.lang

Example Screen Language

If Dutch is the language you want to set as the default, create a soft-link from the **Default.lang** file to the **Dutch.lang** file.

Language files for multi-byte character sets

To create and use a language file for a language that requires a multi-byte character set, as simplified or traditional Chinese does, as well as others, you should create the file in the UTF-8 (Unicode Transformation Format-8) format.

Note: To support reading and writing of UTF-8 characters, you must ensure that the database character set is UTF-8. You can use the following query to determine what the database character set is:

select value from nls database parameters where parameter =
'NLS CHARACTERSET';

User-specific language settings

All screens in the SMS are able to support selected languages. On login, the screens are displayed in the default language. You can subsequently specify a language for a specific user in the **Configuration** field of the **User Management** screen by specifying LANGUAGE=*ABC* where *ABC* must match the language file name, is case-sensitive, and does not include the file name extension. After a language is selected for a user, it is stored in their profile.

If a character set other than UTF-8 is used to create the language file, you must specify the character set for a user using CHARSET=*XYZ* in the Configuration field on the **User** tab of the **User Management** screen, where *XYZ* specifies one of the following character sets: US-ASCII, ISO-8859-1, UTF-16BE, UTF-16LE, or UTF-16.

For more information about setting the Configuration field, see *Service Management System User's Guide*.

Procedure

Follow these steps to set the default language for your SMS Java Administration screens.

Step	Action
1	Change to the following directory: /IN/html/SMS/language
	Example command: cd /IN/html/SMS/language/
2	Ensure the Default.lang file exists in this directory.
3	If the required file does not exist, create an empty file called Default.lang.
4	Ensure that the language file for your language exists in this directory. The file should be in the format: <i>language.lang</i>
	Where:
	<i>language</i> = your language.
	Example: Spanish.lang
5	If the required language file does not exist, either:create a new one with your language preferences, or
	contact Oracle support.
	To create a language file, you need a list of the phrases and words used in the screens. These should appear in a list with the translated phrase in the following format: original phrase=translated phrase
	Any existing language file should have the full set of phrases. If you do not have an existing file to work from, contact Oracle support with details.
6	Create a soft-link between the Default.lang file, and the language file you want to use as the default language for the SMS Java Administration screens.

Step Action

```
Example command: ln -s Dutch.lang Default.lang
```

Defining the Help Screen Language

Introduction

The default Helpset file sets the language that the help system for the Java Administration screens start in. The user can change to another language after logging in.

The default language can be changed by the system administrator. By default, the language is set to English.

Default.SMS.hs

When SMS is installed, a file called **Default.SMS.hs** is created in the application's language directory in the screens module. This contains a soft-link to the language file which defines the language which will be used by the screens.

If a Default.SMS.hs file is not present, the English.SMS.hs file will be used.

If a **Default.SMS.hs** file is present, a user must explicitly set their language to their required language in the Tools screen or the default language will be used.

The Default.SMS.hs file is:

/IN/html/SMS/helptext/Default.SMS.hs

Example helpset language

If Dutch is the language you want to set as the default, create a soft-link from the **Default.SMS.hs** file to the **Dutch.SMS.hs** file.

Procedure

Follow these steps to set the default language for your SMS Java Administration screens.

Step	Action
1	Change to the following directory: /IN/html/SMS/helptext
	Example command: cd /IN/html/SMS/helptext
2	Ensure the Default.SMS.hs file exists in this directory.
3	If the required file does not exist, create an empty file called Default.SMS.hs.
4	Ensure that the language file for your language exists in this directory. The file should be in the format: language.SMS.hs
	Where:
	<i>language</i> is your language
	Example:
	Dutch.SMS.hs
5	If the required language file does not exist, either: create a new one with your language preferences, or

• contact Oracle support.

To create a language file, you need a list of the phrases and words used in the screens. These should appear in a list with the translated phrase in the following format: original phrase=translated phrase

Any existing language file should have the full set of phrases. If you do not have an existing file to work from, contact Oracle support with details.

6

Create a soft-link between the **Default.SMS.hs** file, and the language file you want to use as the default language for the SMS Java Administration screens.

Example command: In -s Dutch.Acs Service.hs Default.Acs Service.hs

Assigning the Oracle Profile to New Users

You create users that can access the SMS UI by using the Service Management System System, User Management screen. By default, when you add a new SMS user, the new user is assigned the standard Oracle profile, named DEFAULT. This profile includes a password verification function that checks things such as the minimum length, number of digits, and so on.

You can create a non-standard Oracle profile to assign to new users by using the CREATE PROFILE command. When you create the Oracle profile, you specify the password verification function that will be applied to user passwords. You can use this feature, for example, to specify an Oracle profile that uses a password verification function that has stricter password verification conditions.

For information about creating Oracle profiles by using the CREATE PROFILE command, see the Oracle Database documentation.

When you create or edit a user's password, smsTaskAgent verifies that you have entered an acceptable password by applying the password verification function that is specified in the Oracle profile assigned to the user.

You configure smsTaskAgent to assign a non-standard Oracle profile to new users instead of the default Oracle profile as follows:

```
smsTaskAgent = {
    defaultOracleProfile = "password_profile"
}
```

where *password_profile* is the name of the Oracle profile you want to use. You must specify the name of an existing Oracle profile. See *smsTaskAgent* (on page 164) for more information.

You specify the message that displays for failed attempts to create or change a user's password in the jnlp.sms.passwordPolicyMessage Java application property. See jnlp.sms.passwordPolicyMessage (on page 100) for more information.

Setting up the Screens

Accessing SMS

There are several ways to access the SMS user interface (UI). For example:

- Use Java WebStart by entering the following URL in a Web browser: http://SMS hostname/sms.jnlp
- Enter the following at the Windows command line:
 c:\> javaws http://SMS hostname/sms.jnlp

Where SMS_hostname is the hostname of an SMS in the IN.

For more information about the SMS UI, see SMS User's Guide.

About Customizing the SMS UI

You can customize the SMS UI by setting application properties in the **sms.jnlp** file, which is located in the **/IN/html**/ directory. You set JNLP application properties by using the following syntax:

```
<property name="property" value="value" /> Where:
```

- property is the name of the application property
- value is the value of the specified property

Resource properties

The following properties in the resources section of the **sms.jnlp** file define the Java 2 SE runtime environment:

jnlp.packEnabled

Syntax:	<property name="jnlp.packEnabled" value="value"></property>
Description:	Specifies whether to download the compressed or uncompressed signed JAR file.
Туре:	Boolean
Optionality:	Required
Allowed:	 True – The Java plug-in automatically downloads and uses the compressed JAR file (sms.sig.jar.pack.gz). If the Web browser is unable to use the compressed JAR file, it downloads the uncompressed JAR file (sms.jar.sig).
	 False – Downloads and uses the sms.jar.sig file.
Default:	True
Notes:	Using the compressed file improves the launching speed of the application. For more information, see the Oracle Java SE documentation.
Example:	<property name="jnlp.packEnabled" value="true"></property>
j2se version	
Syntax:	<j2se href="J2_url" version="version"></j2se>
Description:	Specifies the minimum Java 2 SE Runtime Environment (JRE) version that the application is supported on, and the URL for Java 2 SE.
Туре:	String
Optionality:	Required
Allowed:	
Default:	
Notes:	For more information, see the Oracle Java SE documentation.
Example:	<j2se <br="" version="1.8.0+">href="http://java.sun.com/products/autodl/j2se" /></j2se>

Java Application Properties

The following application properties are available to customize the UI:

jnlp.acs.ACSDefaultCustomerIsPrepaid

Syntax:	<property <br="" name="jnlp.acs.ACSDefaultCustomerIsPrepaid">value="value" /></property>
Description:	Specifies whether the ACS New Customer screen has the Prepaid Charging Customer check box selected by default.
Туре:	String
Optionality:	Optional
Allowed:	• True
	• t(rue)
	• Yes
	• y(es)
	• 1
	All other values are considered to be false.
Default:	True
Notes:	If set to:
	I rue – The Prepaid Charging Customer check box is selected by default.
	• Faise – The Prepaid Charging Customer check box is cleared by default.
Example:	<property <br="" name="jnlp.acs.ACSDefaultCustomerIsPrepaid">value="True" /></property>
jnlp.acs.	ACSStartScreenVersion
Syntax:	<property name="jnlp.acs.ACSStartScreenVersion" value="num"></property>
Description:	This property is provided for backwards compatibility only. It allows you to display the version of the ACS main screen for releases prior to NCC release 5.0.3. The current version of the ACS main screen is displayed by default.
Туре:	String
Optionality:	Optional
Allowed:	 1 – The version of the ACS main screen for releases prior to NCC release 5.0.3 is displayed that includes the Events button. The ACS events feature is now deprecated. Use this setting only if you want to access existing events configuration in ACS.
	 Not set – The current version of the ACS main screen is displayed.
Default:	Not set
Notes:	This property is provided for backwards compatibility.
Example:	<property name="jnlp.acs.ACSStartScreenVersion" value="1"></property>
jnlp.acs.	allowCallPlanSchedulingInPast
Syntax:	<property <br="" name="jnlp.acs.allowCallPlanSchedulingInPast">value="value" /></property>
Description:	Specifies whether control plans can be scheduled to start in the past.
Туре:	String
Optionality:	Optional
Allowed:	• True
	• t(rue)
	• Yes
	• y(es)
	• 1

All other values are considered to be false.

Default:	False
Notes:	If set to:
	 True – Control plans can be scheduled to start in the past.
	 False – Control plans cannot be scheduled to start in the past.
Example:	<property <br="" name="jnlp.acs.allowCallPlanSchedulingInPast">value="t" /></property>

jnlp.ccs.AllowDeletedVouchers

J 1	
Syntax: Description:	<property name="jnlp.ccs.allowDeletedVouchers" value="value"></property> Specifies whether you can set a voucher status or a voucher range state to Deleted. This parameter is used by the following in the Voucher Manager screens: The Vouchers tab The Voucher Ranges tab
Туре:	Boolean
Optionality:	Optional (default used if not set)
Allowed:	• True
	• t(rue)
	• Yes
	• y(es)
	• 1
	All other values are considered to be false.
Default:	True
Notes:	If set to:
	Frue – You can set a voucher range state or a voucher status to Deleted.
	• Faise – You cannot set a voucher range state or a voucher status to Deleted.
Example:	<property name="jnlp.ccs.allowDeletedVouchers" value="true"></property>
jnlp.acs.	allowRefInCustCombo
Syntax:	<property name="jnlp.acs.allowRefInCustCombo" value="value"></property>
Description:	Specifies whether users can perform searches in the ACS UI by using the customer reference number rather than the customer name.
Туре:	String
Optionality:	Optional
Allowed:	True
	• t(rue)
	• Yes
	• y(es)
	• 1
	All other values are considered to be false.
Default:	False
Notes:	If set to:
	 I rue – Allows searches using the customer reference number only. False – Deriving accepted to include a sustainable of the second second
	 Faise – Requires searches to include a customer name along with a customer reference number.

Example:	<property name="jnlp.acs.allowRefInCustCombo" value="t"></property>
jnlp.acs.auto	CloseCompileDialog
Syntax:	<property <br="" name="jnlp.acs.autoCloseCompileDialog">value="value" /></property>
Description:	Specifies whether the CPE compiler report closes automatically after a control plan compiles successfully.
Туре:	String
Optionality:	Optional
Allowed:	• True
	• t(rue)
	• Yes
	• y(es)
	• 1
	All other values are considered to be false.
Default:	False
Notes:	If set to:
	• True – The CPE compiler report closes automatically after a control plan compiles successfully.
	 False – The CPE compiler report remains open after a control plan compiles successfully.
Example:	<property name="jnlp.acs.autoCloseCompileDialog" value="t"></property>

jnlp.acs.autoCloseCPE

Syntax:	<property name="jnlp.acs.autoCloseCPE" value="value"></property>
Description:	Specifies whether the Control Plan Editor closes automatically after a control plan compiles successfully.
Туре:	String
Optionality:	Optional
Allowed:	• True
	• t(rue)
	• Yes
	• y(es)
	• 1
	All other values are considered to be false.
Default:	False
Notes:	If set to:
	 True – The CPE closes automatically after a control plan compiles successfully.
	 False – The CPE remains open after a control plan compiles successfully.
Example:	<property name="jnlp.acs.autoCloseCPE" value="t"></property>
jnlp.ccs.BeOR	BTimeoutms

Syntax:<property name=jnlp.ccs.BeORBTimeoutms value="num" />Description:Specifies the length of time, in milliseconds, after which an ORB request from the
screen operator's terminal to the Convergent Charging Controller server times out.

Туре:	Integer
Optionality:	Optional (default used if not set)
Allowed:	Any positive integer
Default:	20000 (that is, 20 seconds)
Notes:	
Example:	<property name="jnlp.ccs.BeORBTimeoutms" value="5000"></property>
jnlp.ccs.c	ccs_oper_cmnReceiveFiles_port
Syntax:	<property name="jnlp.ccs.ccs_oper_cmnReceiveFiles_port<br">value="port" /></property>
Description:	Specifies the port number on which the cmnReceiveFiles background process listens on the SMS machine when running as the ccs_oper user.
	 This property is used by the following: The Voucher Management GPG Public Keys tab to import public keys
	The Subscriber Management Subscriber Batch tab to upload batch files
Туре:	Integer
Optionality:	Optional (default used if not set)
Allowed:	Any positive integer
Default:	2027
Notes:	
Example:	<property name="jnlp.ccs.ccs_oper_cmnReceiveFiles_port<br">value="2027" /></property>
jnlp.ccs.(CCSAccountNumLength

Syntax:	<property name="jnlp.ccs.CCSAccountNumLength" value="num"></property>
Description:	Specifies the required length of credit card numbers entered in the Card Number field of the CCS New Subscriber screen.
Туре:	Integer
Optionality:	Optional (default used if not set)
Allowed:	Any positive integer
Default:	Not set
Notes:	If this property is not set, the number in the Card Number field must have more than 0 digits.
Example:	<property name="jnlp.ccs.CCSAccountNumLength" value="9"></property>

jnlp.sms.clusterDatabaseHost

Syntax:	<property name="jnlp.sms.clusterDatabaseHost" value="(DESCRIPTION= (LOAD_BALANCE=YES)(FAILOVER=ON)(ENABLE=BROKEN)</pre></th></tr><tr><td></td><td><pre>(ADDRESS_LIST=(ADDRESS=(PROTOCOL=type)(HOST=name)(PORT=port))
(ADDRESS=(PROTOCOL=type)(HOST=name)(PORT=port)))
(CONNECT_DATA=(SERVICE_NAME=SMF)(FAILOVER_MODE=(TYPE=SESSION)
(METHOD=BASIC)(RETRIES=5)(DELAY=3))))"></property>
Description:	Specifies the connection string (including a host and an alternative host address, in case the first IP address is unavailable) for non-SSL cluster-aware connection to the database.
	To use non-SSL connections to the database, set the <pre>jnlp.sms.EncryptedSSLConnection property to false.</pre>
Туре:	String
Optionality:	Optional
Allowed:	
Default:	By default, <i>port</i> is set to 1521.
Notes:	If present, this property is used instead of the jnlp.sms.databaseID property.
Example:	<property name="jnlp.sms.clusterDatabaseHost" value="(DESCRIPTION=</td></tr><tr><td></td><td>(LOAD BALANCE=YES) (FAILOVER=ON) (ENABLE=BROKEN)</td></tr><tr><td></td><td>(ADDRESS_LIST=(ADDRESS=(PROTOCOL=TCP)(HOST=smsphysnode1)</td></tr><tr><td></td><td>(PORT=1521))
(ADDRESS=(PROTOCOL=TCP)(HOST=smsphysnode2)(PORT=1521)))
(CONNECT_DATA=(SERVICE_NAME=SMF)(FAILOVER_MODE=(TYPE=SESSION)
(METHOD=BASIC)(RETRIES=5)(DELAY=3))))"></property>
jnlp.acs.	connectionsDialog
Syntax:	<property name="jnlp.acs.connectionsDialog" value="value"></property>
Description:	Specifies whether the Control Plan Editor displays the Manage Node Exits dialog box when you hold down the Shift key while dragging the mouse to connect a feature node exit to a feature node entry.

	over to a roader of house offer y.
Туре:	String
Optionality: Allowed:	 Optional (default used if not set) shown – CPE displays the Manage Node Exits dialog box. hidden – CPE does not display the Manage Node Exits dialog box.
Default: Notes:	shown
Example:	<property name="jnlp.acs.connectionsDialog" value="hidden"></property>
jnlp.acs	.cpeLineDrawingMechanism

Syntax:	<property <br="" name="jnlp.acs.cpeLineDrawingMechanism">value="<i>connection_type</i>" /></property>
Description:	Specifies the type of connector lines that the Control Plan Editor displays. You use connector lines to connect feature nodes in control plans.
	 Connector lines can be angled or straight lines: Angled connector lines bend around feature nodes where possible instead of crossing over them. Angled connector lines are colored when highlighted.

	 HV connector lines use a combination of horizontal and vertical lines to connect feature nodes and may cross over other feature nodes. HV connector lines can be black or colored when highlighted.
Туре:	String
Optionality:	Optional
Allowed:	 ColouredNodeConnectionDrawer – The CPE displays connectors as angled lines that are colored when highlighted.
	 HVNodeConnectionDrawer – The CPE displays connectors as horizontal and vertical lines that are black.
	 ColouredHVNodeConnectionDrawer – The CPE displays horizontal and vertical lines that are colored when highlighted.
Default:	ColouredNodeConnectionDrawer
Notes:	
Example:	<property name="jnlp.acs.cpeLineDrawingMechanism" value="HVNodeConnectionDrawer"></property>

jnlp.ccs.CreditTransferCP

Syntax:	<property name="jnlp.ccs.CreditTransferCP" value="name"></property>
Description:	Specifies the name of the control plan to run when a credit transfer is performed.
Туре:	String
Optionality:	Optional (default used if not set)
Allowed:	
Default:	CREDIT_TRANSFER
Notes:	
Example:	<property name="jnlp.ccs.CreditTransferCP" value="CREDIT_CP"></property>

jnlp.sms.database

Syntax:	<property name="jnlp.sms.database" value="SMF"></property>
Description:	Specifies the Oracle SID for the SMF database.
Туре:	String
Optionality:	Optional (default used if not set)
Allowed:	
Default:	SMF
Notes:	Set at installation.
Example:	<property name="jnlp.sms.database" value="SMF"></property>

jnlp.sms.databaseHost

Syntax:	<property name="jnlp.sms.databaseHost" value="ip:port:sid"></property>
Description:	 Sets the IP address and port to use for non-SSL connections to the SMF database, and the database SID. To use non-SSL connections to the database, set <i>port</i> to 1524 and the jnlp.sms.EncryptedSSLConnection property to false. To use SSL connections to the database, set the jnlp.sms.EncryptedSSLConnection property to true and set either the jnlp.sms.secureConnectionDatabaseHost property or the jnlp.sms.secureConnectionClusterDatatbaseHost property appropriately. When the jnlp.sms.EncryptedSSLConnection property is set to true or is undefined, jnlp.sms.databaseHost is ignored.
Туре:	String
Optionality: Allowed:	Optional
Default:	Not set. Secure SSL connection is enabled at installation by default.
Notes:	Internet Protocol version 6 (IPv6) addresses must be enclosed in square brackets []; for example: [2001:db8:n:n:n:n:n] where n is a group of 4 hexadecimal digits. The industry standard for omitting zeros is also allowed when specifying IP addresses.
Examples:	<pre><pre>cproperty name="jnlp.sms.databaseHost" value = "192.0.2.1:2484:SMF" /></pre></pre>
	<pre><property name="jnlp.sms.databaseHost" value="[2001:db8:0000:1050:0005:0600:300c:326b]:2484:SMF"></property></pre>
	<pre><pre>cproperty name="jnlp.sms.databaseHost" value = "[2001:db8:0:0:0:500:300a:326f]:2484:SMF" /></pre></pre>
	<property name="jnlp.sms.databaseHost" value="[2001:db8::c3]:2484:SMF"></property>

jnlp.sms.databaseID

Syntax: Description: Type: Optionality: Allowed:	<property name="jnlp.sms.databaseID" value="port:sid"></property> Specifies the SQL*Net port for connecting to the database, and the database SID. String Required
Default: Notes:	 1521:SMF To use non-SSL connections to the database, set <i>port</i> to 1521 and the inlp.sms.EncryptedSSLConnection property to false.
	• To use SSL connections to the database, set the jnlp.sms.EncryptedSSLConnection property to true and set either the jnlp.sms.secureConnectionDatabaseHost property or the jnlp.sms.secureConnectionClusterDatatbaseHost property appropriately. When the jnlp.sms.EncryptedSSLConnection property is set to true or is undefined, jnlp.sms.databaseID is ignored.
Example:	<property name="jnlp.sms.databaseID" value="1521:SMF"></property>

jnlp.sms.dbPassword

Syntax:	<property name="jnlp.sms.dbPassword" value="password"></property>
Description:	Specifies the database password. This password is for a special database user that the ACS Logon screen uses before the user logs in. This property is set during installation and is then not changed.
Туре:	String
Optionality:	Optional (default used if not set)
Allowed:	
Default:	acs_public
Notes:	Do not change this value.
Example:	<property name="jnlp.sms.dbPassword" value="acs_public"></property>

jnlp.sms.dBUser

Syntax:	<property name="jnlp.sms.dBUser" value="<i>user</i>"></property>
Description:	Specifies the database user name. This is a special database user that the ACS Logon screen uses before the user logs in. This property is set during installation and is then not changed.
Туре:	String
Optionality:	Optional (default used if not set)
Allowed:	
Default:	acs_public
Notes:	Do not change this value.
Example:	<property name="jnlp.sms.dBUser" value="acs public"></property>

jnlp.ccs.defaultEDRSearchAge

Syntax:	<property name="jnlp.ccs.defaultEDRSearchAge" value="num"></property>
Description:	Used to calculate the default start date that is shown in the EDR Viewer. The default start date is equal to the current date and time minus jnlp.ccs.defaultEDRSearchAge.
	The default end date is the current date and time.
Туре:	String
Optionality:	Optional (default used if not set)
Allowed:	Any positive integer
Default:	2
Notes:	
Example:	<property name="jnlp.ccs.defaultEDRSearchAge" value="5"></property>
jnlp.ccs.defa	ultEDRSearchCategories
Syntax:	<property <br="" name="jnlp.ccs.defaultEDRSearchCategories">value="list_of_categories" /></property>
Description:	Specifies the default EDR categories to search for when viewing EDRs in the CCS View EDRs for Subscriber screen.
	Use a comma-separated string of EDR sub-types.
Туре:	String
Optionality:	Optional (default used if not set)

Allowed:	
Default:	All
Notes:	The list of categories must be comma-separated and enclosed in single quotes.
Example:	<property <br="" name="jnlp.ccs.defaultEDRSearchCategories">value="'Amount Charge','Bad Pin'" /></property>
jnlp.ccs.	defaultSubscriberSearchType
Syntax:	<property <br="" name="jnlp.ccs.defaultSubscriberSearchType">value="exact prefix" /></property>
Description:	 Sets the default search type for subscribers in the following locations in the CCS UI: The Subscriber tab The Register Subscriber to Credit Card dialog box
Туре:	String
Optionality: Allowed:	 Optional (default used if not set) exact – Searches for the matching subscriber. prefix – Searches for all subscribers with IDs that match the entered prefix.
Default: Notes:	prefix
Example:	<property <br="" name="jnlp.ccs.defaultSubscriberSearchType">value="exact" /></property>
jnlp.acs.	defaultTelcoManaged
Syntax:	<property name="jnlp.acs.defaultTelcoManaged" value="value"></property>
Description:	Specifies whether new ACS customer accounts are marked as being managed by a Telecommunications Operator (telco) by default. Telco-managed customers are customers that never log into ACS but are managed explicitly (and without resource limits) by the telco.
	This property controls whether the Managed Customer check box is selected in the ACS New Customer Details dialog box by default.
Туре:	String
Optionality:	Optional
Allowed:	• True
	• t(rue)
	• (es)
	• 1
	All other values are considered to be false.
Default:	True
Notes:	If set to:
	• True – The Managed Customer check box is selected by default.
	• False – The Managed Customer check box is clear by default.
Example:	<property name="jnlp.acs.defaultTelcoManaged" value="f"></property>

jnlp.sms.DUAL_STATS_NODE

Syntax:	<property name="jnlp.sms.DUAL_STATS_NODE" value="value"></property>
Description:	Specifies whether the View Statistics tab of the Statistics Viewer screen displays information about the SMS node.
Туре:	String
Optionality:	Optional
Allowed:	• true – The View Statistics tab of the Statistics Viewer screen displays information about the SMS node.
	 false – The View Statistics tab of the Statistics Viewer screen does not display information about the SMS node.
Default:	false
Notes:	For more information, see Viewing Statistics in SMS User's Guide.
Example:	<property name="jnlp.sms.DUAL_STATS_NODE" value="true"></property>

jnlp.ECEExtensions

Syntax: Description: Type:	<property name="jnlp.ECEExtensions" value="value"></property> Specifies whether to enable the Notification Gateway tab in the OSD UI. Boolean
Optionality: Allowed:	Optional (default used if not set) true – Enables the Notification Gateway tab in the OSD UI. false or not set – Disables the Notification Gateway tab in the OSD UI.
Default: Notes:	Not set (disabled)
Example:	<property name="jnlp.ECEExtensions" value="true"></property>

jnlp.sms.EncryptedSSLConnection

Syntax:	<property <br="" name="jnlp.sms.EncryptedSSLConnection" value="value">/></property>
Description:	Specifies whether connections to the client UI use encrypted SSL.
Туре:	Boolean
Optionality:	Optional (default used if not set)
Allowed:	true – Use encrypted SSL connections to access the client UI.
	false – Use non-SSL connections to access the client UI.
Default:	true
Notes:	 To use SSL connections to the database, set the jnlp.sms.EncryptedSSLConnection property to true and set either the jnlp.sms.secureConnectionDatabaseHost property or the jnlp.sms.secureConnectionClusterDatatbaseHost property appropriately. To use non-SSL connections to the database, set the jnlp.sms.EncryptedSSLConnection property to false.
Example:	<property <br="" name="jnlp.sms.EncryptedSSLConnection" value="true">/></property>

	-					
-	nIn		ama	ho	C	+
- 1	$\Pi \perp D$		SIIIS	110	5	۰.
_	T-	-			-	_

Syntax:	<property name="jnlp.sms.host" value="IPaddress"></property>
Description:	Specifies the Internet Protocol (IP) address for the SMS host machine that is set at installation.
Туре:	String
Optionality:	Required
Allowed:	IP version 4 (IPv4) addresses
	IP version 6 (IPv6) addresses
Default:	No default
Notes:	You can use the industry standard for omitting zeros when specifying IP addresses.
Examples:	<property name="jnlp.sms.host" value="192.0.2.0"></property>
	<property <br="" name="jnlp.sms.host">value="2001:db8:0000:1050:0005:0600:300c:326b" /></property>
	<property <br="" name="jnlp.sms.host">value="2001:db8:0:0:0:500:300a:326f" /></property>
	<property name="jnlp.sms.host" value="2001:db8::c3"></property>

jnlp.vpn.INProtocol

Syntax:	<property name="jnlp.vpn.INProtocol" value="name"></property>		
Description:	Specifies the IN protocol for VPN screens.		
Туре:	String		
Optionality:	Required		
Allowed:	 AIN – Hides settings not relevant to AIN. Only customers using Advanced Intelligent Network (AIN) should set the property to AIN. Not set – All settings are shown. 		
Default:	Not set		
Notes:	Set at installation.		
Example:	<property name="jnlp.vpn.INProtocol" value="AIN"></property>		

jnlp.acs.issuePCClockWarning

Syntax:	<property <br="" name="jnlp.acs.issuePCClockWarning" value="value">/></property>
Description:	Specifies whether a warning is raised when the user's PC clock time is more than two minutes faster or slower than the SMS platform's clock time.
Туре:	String
Optionality:	Optional
Allowed:	True
	• t(rue)
	• Yes
	• y(es)
	• 1
	All other values are considered to be false.
Default:	True
Notes:	If set to:
	 True – A warning is raised.
	 False – A warning is not raised.

Example: <property name="jnlp</th><th>.acs.issuePCClockWarning" value="t"></property>

jnlp.sms.logo

Syntax:	<property name="jnlp.sms.logo" value="file"></property>			
Description:	Specifies the logo displayed on the splash screen immediately before the ACS Logon screen appears.			
	At installation, the property is set to an Oracle logo GIF file.			
Туре:	String			
Optionality:	Optional			
Allowed:	A valid network path and filename.			
Default:	None			
Notes:				
Example:	<property <br="" name="jnlp.sms.logo" value="SMS/images/oracle.gif">/></property>			

jnlp.acs.MAX_CONTROL_PLANS_DISPLAYED

Syntax:	<property <br="" name="jnlp.acs.MAX_CONTROL_PLANS_DISPLAYED">value="<i>num</i>" /></property>
Description:	Specifies the maximum number of control plans that can be displayed in the search results section of an ACS UI dialog box.
Туре:	String
Optionality:	Optional
Allowed:	1 through 999
Default:	200
Notes:	
Example:	<property <br="" name="jnlp.acs.MAX_CONTROL_PLANS_DISPLAYED">value="200" /></property>

jnlp.ccs.MaxGlobalLimitedLiabilityPromotions

•	
Syntax:	<property <br="" name="jnlp.ccs.MaxGlobalLimitedLiabilityPromotions">value="num" /></property>
Description:	Specifies the maximum number of promotions that can have global limited liability. This property is used by the Details tab of the Promotion Manager screen. After the maximum number is reached, the global limited liability fields are disabled on the Details tab.
Туре:	String
Optionality:	Optional (default used if not set)
Allowed:	Any integer greater than or equal to 0
Default:	20
Notes:	
Example:	<property <br="" name="jnlp.ccs.MaxGlobalLimitedLiabilityPromotions">value="25" /></property>

jnlp.acs.	maximiseAcsScreens		
Syntax:	<property name="jnlp.acs.maximiseAcsScreens" value="value"></property>		
Description:	Specifies whether the windows in the ACS UI are opened at maximum size or optimum size.		
Туре:	String		
Optionality:	Optional		
Allowed:	• True		
	• t(rue)		
	Yes		
	• y(es)		
	• 1		
	All other values are considered to be false.		
Default:	False		
Notes:	If set to:		
	 True – The windows in the ACS UI are opened at maximum size. 		
	 False – The windows in the ACS UI are opened at optimum size. 		
Example:	<property name="jnlp.acs.maximiseAcsScreens" value="t"></property>		
jnlp.ccs.	MaxPDSMSThresholdEntries		
Syntax:	<property name="jnlp.ccs.MaxPDSMSThresholdEntries" value="num"></property>		
Description:	Specifies the maximum number of promotional destination discount thresholds that you can define. That is, the number of non-discounted short messages that must be sent before the discount is applied.		
	This property is used by the Promotional Destination Rates option of the New Product Type screen.		
Туре:	Integer		
Optionality:	Optional (default used if not set)		
Allowed:	Any number greater than or equal to zero		
Default:	5		
Notes:			
Example:	<property name="jnlp.ccs.MaxPDSMSThresholdEntries" value="10"></property>		

jnlp.ccs.MaxRowsRTWN

Syntax:	<property name="jnlp.ccs.MaxRowsRTWN" value="num"></property>
Description:	Specifies the maximum number of rows to display in the Real Time Wallet Notifications option of the CCS New Product Type screen.
Туре:	Integer
Optionality:	Optional (default used if not set)
Allowed:	Any positive integer
Default:	100
Notes:	
Example:	<property name="jnlp.ccs.MaxRowsRTWN" value="50"></property>

jnlp.sms.namingServerPort

Syntax:	<property <br="" name="jnlp.sms.namingServerPort">value="port" /></property>
Description:	Tells the CCP Dashboard screens how to contact the naming server.
Туре:	Integer
Optionality:	Optional
Allowed:	
Default:	5556
Notes:	The value in this field should be the same as the value you set in the -p parameter of smsNamingServerStartup .
Example:	<property <br="" name="jnlp.sms.namingServerPort">value="5556" /></property>

jnlp.ORB_HOST

Syntax:	<property name="jnlp.ORB_HOST" value="hostsms"></property>
Description:	Specifies the host name of the machine running the ccsBeOrb background process.
Туре:	String
Optionality:	Optional (default used if not set)
Allowed:	
Default:	The SMS machine host name.
Notes:	
Example:	<property name="jnlp.ORB_HOST" value="hostname"></property>

jnlp.acs.paletteStyle

Syntax:	<property name="jnlp.acs.paletteStyle" value="value"></property>
Description:	 Specifies the style used to display the feature palette in the Control Plan Editor window. There are two possible feature palette styles: The floating panel style feature palette displays feature group names in a list, and the feature nodes within a selected group in a floating panel. The floating panel style enables you to quickly locate a feature node in the palette by using the Search Palette feature to filter the available feature nodes.
	• The static panel style feature palette displays an expandable list of feature node groups from which you select individual feature nodes in a static panel. The Search Palette feature is not available with this style.
Туре:	String
Optionality:	Optional
Allowed:	 old – Sets the feature palette to the static panel style.
	 Not set – Sets the feature palette to the floating panel style.
Default:	Floating panel style
Notes:	To enable the jnlp.acs.paletteStyle property, clear the Java cache and the client browser cache before restarting the Control Plan Editor.
Example:	<property name="jnlp.acs.paletteStyle" value="old"></property>

jnlp.sms.passwordPolicyMessage

Syntax:	<property <br="" name="jnlp.sms.passwordPolicyMessage">value="message_text" /></property>
Description:	Specifies the message text that is displayed for failed attempts to change a user's password through the User Management screen in the SMS UI.
Туре:	String
Optionality:	Optional (default used if not set)
Allowed:	Any text. The text should be relevant to the password restrictions imposed by the password verification function defined in the user's (Oracle) profile.
Default:	The new password is not compliant with the password policy.
Notes:	The definition must be specified on one line. Do not include new lines in the message text. If the message is longer than 80 characters, the displayed message is broken up into multiple lines automatically.
Example:	<property name="jnlp.sms.passwordPolicyMessage" value="The new password must contain at least 9 characters and must contain at least 2 digits"></property>

jnlp.sms.port

Syntax:	<property name="jnlp.sms.port" value="num"></property>
Description:	Specifies the SQL*Net port for connecting to the SMS host machine.
Туре:	Integer
Optionality:	Optional (default used if not set)
Allowed:	
Default:	1521
Notes:	Set at installation
Example:	<property name="jnlp.sms.port" value="1521"></property>

jnlp.sms.printingFontSize

Syntax:	<property name="jnlp.sms.printingFontSize" value="num"></property>
Description:	Specifies the point size of text that can be printed from screens that support printing.
Туре:	Integer
Optionality:	Optional (default used if not set)
Allowed:	6 through 12 (inclusive)
Default:	8
Notes:	
Example:	<property name="jnlp.sms.printingFontSize" value="10"></property>

jnlp.acs.ProfileN

Syntax:	<property name="jnlp.acs.Profile<i>number</i>" value="new_name"></property>
Description:	Specifies to suppress or change the name of any of the 20 profile blocks.
Туре:	String
Optionality:	Optional
Allowed:	1 ≤ number ≤ 20
	 new_name is one of the following: – (dash): The profile block is not displayed in screens.

• String comprising any printable characters.
Default:	The following table lists default profile block names in the order in which they
	appear in feature node drop-down lists.

Profile1	VPN Network Profile
Profile2	VPN Station Profile
Profile3	Customer Profile
Profile4	Control Plan Profile
Profile5	Global Profile
Profile6	CLI Subscriber Profile
Profile7	Service Number Profile
Profile8	App Specific 1
Profile9	App Specific 2
Profile10	App Specific 3
Profile11	App Specific 4
Profile12	App Specific 5
Profile13	App Specific 6
Profile14	App Specific 7
Profile15	App Specific 8
Profile16	Any Valid Profile
Profile17	Temporary Storage
Profile18	Call Context
Profile19	Outgoing Extensions
Profile20	Incoming Extensions

Notes:	 If VPN is not installed, Profile1 and Profile2 are suppressed by default. If Charging Control Services is installed, profile block names associated with Profile8 through Profile15 are changed automatically. For more information, see CCS Technical Guide.
	 If RCA is not installed, Profile19 and Profile20 are suppressed by default. You can make them available by installing RCA or by appending them to the sms.jnlp file.
	 Feature nodes with writable fields cannot write into Profile16.
Examples:	<property name="Profile1" value="-"></property>
	<property name="Profile6" value="Originating CLI"></property>
jnlp.acs.re	equireCustomerReference
Syntax:	<property <="" name="jnlp.acs.requireCustomerReference" th=""></property>

	value="value" />
Description:	Specifies whether a customer reference number is mandatory for each ACS customer that is created.
Туре:	String
Optionality:	Optional

Allowed:	 True t(rue) Yes y(es) 1
	All other values are considered to be false.
Default:	True
Notes:	If set to: • True – Customer reference numbers are mandatory for newly created ACS customers.
	False – Customer reference numbers are optional for newly created ACS customers.
Example:	<property name="jnlp.acs.requireCustomerReference" value="f"></property>

jnlp.sms.ResyncServerPort

Syntax:	<property name="jnlp.sms.ResyncServerPort" value="port"></property>
Description:	Specifies the port number on which the SMS resyncServer process listens for connections.
	This property is used by the SMS Replication Check screen.
Туре:	Integer
Optionality:	Optional (default used if not set)
Allowed:	Any positive integer
Default:	7669
Notes:	
Example:	<property name="jnlp.sms.ResyncServerPort" value="7669"></property>

jnlp.sms.reports_location

Syntax:	<property name="jnlp.sms.reports_location" value="hostname"></property>
Description:	Specifies the machine name of the HTML server on which generated reports are available in the <i>loutput</i> directory.
	This property is used by the SMS Report Functions screen.
Туре:	String
Optionality: Allowed:	Optional (default used if not set)
Default: Notes:	Not set, which means that reports are generated on the SMS machine.
Example:	<property name="jnlp.sms.reports_location" value="SMSmachine"></property>

jnlp.acs.scfs

Syntax:	<property name="jnlp.acs.scfs" value="scfn"></property>
Description:	Lists the network entities that are available for handover.
	 The names listed in this section are used by the following feature nodes: TCAP Handover (as the SCP Name list)
	 RIMS MAP Query and IS41 Query (as the Return Address for mapping the SCCP Calling Party Address)

Туре:	String
Optionality:	Optional. However, the TCAP Handover feature node must have at least one scf to work.
Allowed:	Any scf name configured in the acs.conf file. See acsChassis SSF Configuration (SLC).
Default:	None
Notes:	For every jnlp.acs.scfs property in the JNLP file, you must create a matching scf entry in the acs.conf file on each SLC defining the address associated with this entry.
Example:	<property name="jnlp.acs.scfs" value="SCF_Name1,SCF_Name2"></property>

jnlp.acs.SDRfastTimeoutDefault

Syntax:	<property name="jnlp.acs.SDRfastTimeoutDefault" value="secs"></property>
Description:	Specifies the default fast timeout period, in seconds, for the Selection Dependent Routing feature node. If the specified timeout period expires before a customer enters a digit on their telephone keypad, the feature node exits. You can use this feature, for example, to connect calls directly to the operator after timing out.
Туре:	Integer
Optionality:	Optional (default used if not set)
Allowed:	Any positive integer
Default:	10
Notes:	
Example:	<property name="jnlp.acs.SDRfastTimeoutDefault" value="5"></property>

jnlp.sms.secureConnectionClusterDatabaseHost

Syntax:	<property <br="" name="jnlp.sms.secureConnectionClusterDatabaseHost">value = "(DESCRIPTION= (ADDRESS_LIST=(ADDRESS=(PROTOCOL=type)(HOST=IPaddress) (PORT=port)) (ADDRESS=(PROTOCOL=type)(HOST=IPaddress)(PORT=port))) (CONNECT_DATA=(SERVICE_NAME=servicename)))" /></property>
Description:	Specifies the connection string (including host address and port) for encrypted SSL connections to the SMF database on a clustered system.
	To enable secure SSL connections to the database, set <i>port</i> to 2484 and set the jnlp.sms.EncryptedSSLConnection property to true.
Туре:	String
Optionality:	Optional (default used if not set)
Allowed:	
Default:	
Notes:	If present, this property is used instead of the jnlp.sms.secureConnectionDatabaseHost property.
Example:	<pre><pre>cproperty name="jnlp.sms.secureConnectionClusterDatabaseHost" value = "(DESCRIPTION= (ADDRESS_LIST=(ADDRESS=(PROTOCOL=TCPS)(HOST=192.0.1.1))</pre></pre>
	(PORT=2484)) (ADDRESS=(PROTOCOL=TCP)(HOST=192.0.2.1)(PORT=2484))) (CONNECT_DATA=(SERVICE_NAME=SMF)))" />

jnlp.sms.secureConnectionDatabaseHost

Syntax:	<property name="jnlp.sms.secureConnectionDatabaseHost" value="<br">"(DESCRIPTION= (ADDRESS_LIST=(ADDRESS=(PROTOCOL=type)(HOST=IPaddress) (PORT=port))))(CONNECT_DATA=(SERVICE_NAME=servicename)))" /></property>
Description:	Specifies the connection string (including host address and port) for encrypted SSL connections to the SMF database on a non-clustered system.
	To use SSL connections to the database, set <i>port</i> to 2484 and set the
Type:	String
Optionality:	Optional (default used if not set)
Allowed: Default:	
Notes:	If present, this property is used instead of the jnlp.sms.databaseID property.
Example:	<property name="jnlp.sms.secureConnectionDatabaseHost" value="<br">"(DESCRIPTION= (ADDRESS_LIST=(ADDRESS=(PROTOCOL=TCPS)(HOST=192.0.1.1))</property>
	(PORT=2484))))(CONNECT_DATA=(SERVICE_NAME=SMF)))" />

jnlp.ses.SES_DATE_FORMAT

Syntax:	<property name="jnlp.ses.SES_DATE_FORMAT" value="format"></property>
Description:	Specifies the date format used by the SES Configuration screens.
Туре:	String
Optionality:	Optional (default used if not set)
Allowed:	Any format supported by Java SimpleDateFormat (see https://docs.oracle.com/javase/8/docs/api/java/text/SimpleDateFormat.html)
Default:	dd/MM/yyyy HH:mm:ss
Notes:	
Example:	<property name="jnlp.ses.SES_DATE_FORMAT" value="yyMMddHHmmssZ"></property>

jnlp.acs.showAnnouncementSource

Syntax:	<property name="jnlp.acs.showAnnouncementSource" value="value"></property> />
Description:	Specifies whether announcement sources (i.e., the resource name and resource ID) are displayed next to announcement names in ACS UI windows.
Туре:	String
Optionality:	Optional
Allowed:	• TRUE
	• true
	• YES
	• yes
	• Y
	• y
	All other values are considered to be false.
Default:	True

Notes:	 If set to: True – Announcement sources are displayed. False – Announcement sources are not displayed.
Example:	<property name="jnlp.acs.showAnnouncementSource" value="f"></property>
jnlp.sms.	showEFM
Syntax:	<property name="jnlp.sms.showEFM" value="value"></property>
Description:	Specifies whether the Alarm Definition tab is available on the Alarm Management screen.
Туре:	Boolean
Optionality:	Optional (default used if not set)
Allowed:	• True
	• t(rue)
	• Yes
	• y(es)
	• 1
	All other values are considered to be false.
Default:	False
Notes:	If set to:
	• True – The Alarm Definition tab is available.
	 False – The Alarm Definition tab is not available.
Example:	<property name="jnlp.sms.showEFM" value="True"></property>
jnlp.ccs.	ShowEmptyEDRTags
Syntax:	<property <="" name="jnlp.ccs.ShowEmptyEDRTags" pre="" value="taglist"></property>

Syntax:	<property name="jnlp.ccs.ShowEmptyEDRTags" value="taglist"></property>
Description:	Lists the CCS EDR tags that must be displayed in EDR Viewer or CCP Dashboard when they are empty.
Туре:	String
Optionality:	Optional (default used if not set)
Allowed:	Comma separated list of the tags to include.
Default:	Empty tags are not displayed in EDR Viewer.
Notes:	Do not insert spaces in the list of tags.
Example:	<property <br="" name="jnlp.ccs.ShowEmptyEDRTags">value="ACS_CUST_ID,PI,WALLET_TYPE" /></property>

jnlp.acs.showNetwork

Syntax:	<property name="jnlp.acs.showNetwork" value="value"></property>
Description:	Specifies whether the Network field is displayed in the ACS New Customer dialog box.
Туре:	String
Optionality:	Optional
Allowed:	True
	• t(rue)
	• Yes
	• y(es)

	• 1
	All other values are considered to be false.
Default:	True
Notes:	If set to:
	 True – The Network field is displayed.
	 False – The Network field is not displayed.
Example:	<property name="jnlp.acs.showNetwork" value="f"></property>

jnlp.acs.showCallPlanCopy

Syntax:	<property name="jnlp.acs.showCallPlanCopy" value="value"></property>
Description:	Specifies whether the Copy button is enabled on the ACS Numbers screen.
Туре:	String
Optionality: Allowed:	Optional • True • t(rue) • Yes • y(es) • 1 All other values are considered to be false.
Default:	True
Notes:	 If set to: True – The Copy button is enabled. False – The Copy button is disabled.
Example:	<property name="jnlp.acs.showCallPlanCopy" value="f"></property>
jnlp.sms.	.smf_oper_cmnReceiveFiles_port
Syntax:	<property <br="" name="jnlp.sms.smf_oper_cmnReceiveFiles_port">value="<i>port</i>" /></property>
Description:	 Specifies the port number on which the cmnReceiveFiles background process listens on the SMS machine when running as the smf_oper user. This property is used by the following: The Location Capabilities Pack Import screen when importing LCP cell or area data The Voucher Management GPG Public Keys tab to import public keys The Subscriber Management Subscriber Batch tab to upload batch files
Type:	Integer
Optionality: Allowed:	Optional (default used if not set)
Default: Notes:	2028
Example:	<property <br="" name="jnlp.sms.smf_oper_cmnReceiveFiles_port">value="2028" /></property>
jnlp.sms.	smsProductInfo
Syntax:	<property name="jnlp.sms.smsProductInfo" value="<i>product</i>"></property>

Description: Specifies the product name displayed in the About Oracle Communications Convergent Charging Controller help screen.

Туре:	String
Optionality:	Optional (default used if not set)
Allowed:	
Default:	SMS – Service Management System
Notes:	
Example:	<property name="jnlp.sms.smsProductInfo" value="SMS - Service
Management System"></property>

jnlp.sms.smsVersionInfo

Syntax:	<property name="jnlp.sms.smsVersionInfo" value="version"></property>
Description:	Specifies the product version number displayed in the About Oracle Communications Convergent Charging Controller help screen.
Туре:	String
Optionality:	Optional (default used if not set)
Allowed:	
Default:	Version 6.0.1
Notes:	
Example:	<property name="jnlp.sms.smsVersionInfo" value="Version 6.0.1"></property>

jnlp.acs.ssfs

Syntax:	<property name="jnlp.acs.ssfs" value="ssf1,ssf2,,ssfn"></property>
Description:	Lists the switches that are available in the IN network.
	The switches listed in this section are used by the Call Initiation feature node (as the switch name list).
Туре:	String
Optionality:	Optional. However, the Call Initiation feature node must have at least one scf to work.
Allowed:	Any ssf name configured in the acs.conf file. See acsChassis SSF Configuration (SLC).
Default:	None
Notes:	
Example:	<property name="jnlp.acs.ssfs" value="SSF_Name1,SSF_Name2"></property>

jnlp.sms.sslCipherSuites

Syntax:	<property <br="" name="jnlp.sms.sslCipherSuites">value="(TLS_RSA_WITH_AES_128_CBC_SHA)" /></property>
Description:	Specifies the cipher suites to use for SSL encryption. You must set this property if you are using encrypted SSL for connecting to the SMS database.
Туре:	String
Optionality:	Optional (default used if not set)
Allowed:	(TLS_RSA_WITH_AES_128_CBC_SHA)
Default:	(TLS_RSA_WITH_AES_128_CBC_SHA)
Notes:	You must also set the SSL_CIPHER_SUITES property to (TLS_RSA_WITH_AES_128_CBC_SHA) in the listener.ora and sqlnet.ora files.

Example:	<property <br="" name="jnlp.sms.sslCipherSuites">value="(TLS_RSA_WITH_AES_128_CBC_SHA)" /></property>
jnlp.acs.	suppressedSDRDigits
Syntax: Description:	<property name="jnlp.acs.suppressedSDRDigits" value="digits"></property> The Selection Dependent Routing feature node allows you to route calls based on the number, letter, or special character entered on the caller's telephone keypad. You use the jnlp.acs.suppressedSDRDigits property to prevent users from assigning specified digits to a calling route and to exclude those digits from the Configure Selection Dependent Routing dialog box of the ACS Control Plan Editor.
Туре:	String
Optionality:	Optional
Allowed:	Numbers ranging from 0 (zero) through 9
	Letters ranging from A through F
	Special characters * and #
Default:	None
Notes:	
Example:	<property name="inlp.acs.suppressedSDRDigits" value="12ab"></property>
Example:	
jnlp.acs.S	SuppressTagID
Syntax:	<property name="jnlp.acs.SuppressTagID" value="value"></property>
Description:	Specifies to not include the profile tag value when displaying a profile field name
	in the ACS Control Plan Editor.
	For example, when jnlp.acs.SuppressTagID is set to:
	 true – The profile tag 196613 displays the name "PIN Prefix"
	 false – The profile tag 196613 displays the name "PIN Prefix (196613)"
Type:	Boolean
Optionality:	Optional
Allowed:	• True
	• t(rue)
	• Yes
	• v(es)
	• 1
	All other values are considered to be false
Default:	True
Notes:	If set to:
	 True – Only the profile field name is displayed.
	• False – Both the profile field name and the profile field value is displayed.
Example:	<property name="jnlp.acs.SuppressTagID" value="True"></property>
jnlp.trace	2
Syntax:	<pre><pre>cproperty name="jnlp.trace" value="value" /></pre></pre>
Description:	Specifies whether to enable tracing for the Control Plan Editor. The output is displayed in the Java Console.
Type:	Boolean
Optionality:	Optional (default used if not set)
Allowed:	on off, true false, yes no, 1 0, enabled disabled

Default:	Off
Notes:	
Example:	<property name="jnlp.trace" value="on"></property>

jnlp.sms.TZ

Syntax:	<property name="jnlp.sms.TZ" value="<i>timezone</i>"></property>
Description:	Specifies the time zone used for all time and date values displayed in Convergent Charging Controller UI windows.
Туре:	String
Optionality:	Optional (default used if not set)
Allowed:	Any Java supported time zone.
Default:	GMT
Notes:	For a full list of Java supported time zones, see Time Zones.
Example:	<property name="jnlp.sms.TZ" value="GMT"></property>

jnlp.acs.updateCPReferences

<property <="" name="jnlp.acs.updateC
/></pre></th><th>PReferences" th="" value="value"></property>	
Description: When you update a control plan, the Control the control plan. If any customers are sched control plan, the customers' service number version by default. This property specifies w service numbers or CLIs to the new control	ol Plan Editor creates a new version of duled to use the older version of the rs or CLIs remain attached to the older whether you can attach customers' plan version.
Type: String	
Optionality: Optional	
Allowed: • True	
• t(rue)	
• Yes	
• y(es)	
• 1	
All other values are considered to be false.	
Default: None	
Notes: If set to:	
 True – After an updated control plan Plan Editor prompts you to select the the new control plan version. 	n compiles successfully, the Control ne service numbers or CLIs to attach to
 False – The existing service number older version of the content plan. 	ers or CLIs remain attached to the
Example: <property name="jnlp.acs.updateC</th><th>PReferences" value="t"></property>	
jnlp.ccs.UseAnnouncements	
<pre>Syntax: <property name="jnlp.ccs.UseAnnounce" value="value"></property></pre>	ements"
Description: Specifies whether to play announcements.	
Type: String	
Optionality: Optional	

 t(rue) Yes Y(es)	Allowed:	• True
 Yes y(es) All other values are considered to be false. Default: False Notes:		• t(rue)
 y(es) 1 All other values are considered to be false. Default: False Notes: Example: <pre> <pre></pre></pre>		• Yes
• 1 All other values are considered to be false. Default: False Notes: Example: <property <br="" name="jnlp.ccs.UseAnnouncements">value="res" /> jnlp.acs.useTNForNodeName Synta: <property name="jnlp.acs.useTNForNodeName" value="value"></property> Description: Specifies whether the feature node name displayed in the Control Plan Editor window is the Termination Number (TN). This applies to the following feature nodes only: • Attempt Termination (UT) The TN is displayed for any UT or AT feature node in the CPE window, without requiring you to save each feature node to update the stored control plan data. Type: Boolean Optionality: Optional (default used if not set) Allowed: • True • true • true • true • true • true • true Notes: If set to: • True – The feature node name is displayed as the TN in the CPE window. • False – The feature node name is displayed as the stored feature node name in the CPE window. • False – The feature node name is displayed as the stored feature node name in the CPE window. • False – The feature node name is displayed as the stored feature node name in the CPE window. Vou can update the TN for these feature nodes in a control plan by using the ACS Numbers screen. See the discussion about Editing Termination Numbers in ACS User's Guide for more information. type: ypoperty name="jnlp.acs.useTNForNodeName" value="true" /> jnlp.vpn.vpnMaxNumOfHL Specifies the maximum number of hunting lists per station. Type:<</property>		• y(es)
All other values are considered to be false. Default: False Notes: Example: Example: <property name="jnlp.ccs.UseAnnouncements" value="value"></property> value="Yes" /> jnlp.acs.useTNForNodeName Syntax: Syntax: <property name="jnlp.acs.useTNForNodeName" value="value"></property> Description: Specifies whether the feature node name displayed in the Control Plan Editor window is the Termination Number (TN). This applies to the following feature nodes only: Attempt Termination (AT) Unconditional Termination (UT) The TN is displayed for any UT or AT feature node in the CPE window, without requiring you to save each feature node to update the stored control plan data. Type: Boolean Optional (default used if not set) Allowed: If set to: True If set to: If set to: If set to: True – The feature node name is displayed as the Stored feature node name in the CPE window. Vou can update the TN for these feature nodes in a control plan by using the ACS Numbers screen. See the discussion about Editing Termination Numbers in ACS User's Guide for more information. Example: <property name="jnlp.cyn.vpnMaxNumOfHL" value="num"></property> Syntax: <property name="jnlp.vpn.vpnMaxNumOfHL" value="num"></property> Syntax: <property jnlp.ccs.useannouncements"<br="" name="</th><th></th><th>• 1</th></tr><tr><th>Default: False Notes: Example: <property_name=">value="Yes" /> jnlp.acs.useTNForNodeName Synta: <property_name="jnlp.acs.usetnfornodename" value="value"></property_name="jnlp.acs.usetnfornodename"> Description: Specifies whether the feature node name displayed in the Control Plan Editor window is the Termination Number (TN). This applies to the following feature nodes only: • Attempt Termination (UT) • Unconditional Termination (UT) • True • Unconditional Termination (UT) • True • Unconditional Termination (UT) • True • True • True • True • True • True – The feature node name is displayed as the TN in the CPE window. • False – The feature node name is displayed as the stored feature node name in the CPE window. • Fal</property>		All other values are considered to be false.
Notes: Cproperty name="jnlp.ccs.UseAnnouncements" value="value" /> value="res" /> Synta: <property name="jnlp.acs.useTNForNodeName" value="value"></property> Synta: <property name="jnlp.acs.useTNForNodeName" value="value"></property> Specifies: Specifies whether the feature node name displayed in the Control Plan Editor window is the Termination Number (TN). This applies to the following feature nodes only: Attempt Termination (AT) Unconditional Termination (UT) The TN is displayed for any UT or AT feature node in the CPE window, without requiring you to save each feature node to update the stored control plan data. Type: Boolean Optionally: Optional (default used if not set) Allowed: True If set to: True - The feature node name is displayed as the TN in the CPE window. False - The feature node name is displayed as the stored feature node name in the CPE window. False - The feature node name is displayed as the stored feature node name in the CPE window. Vou can update the TN for these feature nodes in a control plan by using the ACS Numbers creen. See the discussion about Editing Termination Numbers in ACS User's Guide for more information. Example: <property <="" name="jnlp.vpn.vpnMaxNumOfHL" td=""> Synta: <property name="jnlp.vpn.vpnMaxNumOfHL" value="num"></property> Sp</property>	Default:	False
<pre>Example: <pre> <pre< th=""><th>Notes:</th><th></th></pre<></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre>	Notes:	
<pre>jnlp.acs.useTNForNodeName Synta: <pre><pre><pre><pre>Synta: <pre><pre><pre><pre>Specifies whether the feature node name displayed in the Control Plan Editor window is the Termination Number (TN). This applies to the following feature nodes only:</pre></pre></pre></pre></pre></pre></pre></pre></pre>	Example:	<property <br="" name="jnlp.ccs.UseAnnouncements">value="Yes" /></property>
Syntax: <property name="jnlp.acs.useTNForNodeName" value="value"></property> Description: Specifies whether the feature node name displayed in the Control Plan Editor window is the Termination Number (TN). This applies to the following feature nodes only: Attempt Termination (AT) Unconditional Termination (UT) The TN is displayed for any UT or AT feature node in the CPE window, without requiring you to save each feature node to update the stored control plan data. Type: Boolean Optionality: Optional (default used if not set) Allowed: • True • t(rue) • Yes • y(es) • 1 All other values are considered to be false. Default: False Notes: If set to: • True - The feature node name is displayed as the stored feature node name in the CPE window. • False - The feature node name is displayed as the stored feature node name in the CPE window. • False - The feature node name is displayed as the stored feature node name in the CPE window. • False - The feature node name is displayed as the stored feature node name in the CPE window. • False - The feature node name is displayed as the stored feature node name in the CPE window. • False - The feature node name is displayed as the stored feature node name in the CPE window.	jnlp.acs.	useTNForNodeName
Description: Specifies whether the feature node name displayed in the Control Plan Editor window is the Termination Number (TN). This applies to the following feature nodes only: Attempt Termination (AT) Unconditional Termination (UT) The TN is displayed for any UT or AT feature node in the CPE window, without requiring you to save each feature node to update the stored control plan data. Optionality: Optional (default used if not set) Allowed: True t(rue) Yes y(es) 1 All other values are considered to be false. Default: False True – The feature node name is displayed as the TN in the CPE window. False – The feature node name is displayed as the stored feature node name in the CPE window. False – The feature node name is displayed as the stored feature node name in the CPE window. False – The feature node name is displayed as the stored feature node name in the CPE window. False – The feature node name is displayed as the stored feature node name in the CPE window. False – The feature node name is displayed as the stored feature node name in the CPE window. False – The feature node name is displayed as the Stored feature node name in the CPE window. False – The feature node name is displayed as the stored feature node name in the CPE window. False – The feature node name is displayed as the stored feature node name in the CPE window. False – The feature node name is displayed a	Syntax:	<property name="jnlp.acs.useTNForNodeName" value="value"></property>
 Unconditional Termination (UT) The TN is displayed for any UT or AT feature node in the CPE window, without requiring you to save each feature node to update the stored control plan data. Type: Boolean Optionality: Optional (default used if not set) Allowed: True t(rue) Yes y(es) 1 All other values are considered to be false. Default: False Notes: True - The feature node name is displayed as the TN in the CPE window. False - The feature node name is displayed as the stored feature node name in the CPE window. False - The feature node name is displayed as the stored feature node name in the CPE window. False - The feature node name is displayed as the stored feature node name in the CPE window. False - The feature node name is displayed as the stored feature node name in the CPE window. You can update the TN for these feature nodes in a control plan by using the ACS Numbers screen. See the discussion about Editing Termination Numbers in ACS User's Guide for more information. Example: <pre> <pre></pre></pre>	Description:	 Specifies whether the feature node name displayed in the Control Plan Editor window is the Termination Number (TN). This applies to the following feature nodes only: Attempt Termination (AT)
The TN is displayed for any UT or AT feature node in the CPE window, without requiring you to save each feature node to update the stored control plan data. Type: Boolean Optionality: Optional (default used if not set) Allowed:		Unconditional Termination (UT)
Type: Boolean Optionality: Optional (default used if not set) Allowed: • True • It(rue) • Yes • y(es) • 1 All other values are considered to be false. Default: Palse Notes: If set to: • True – The feature node name is displayed as the TN in the CPE window. • False – The feature node name is displayed as the stored feature node name in the CPE window. • False – The feature node name is displayed as the stored feature node name in the CPE window. You can update the TN for these feature nodes in a control plan by using the ACS Numbers screen. See the discussion about Editing Termination Numbers in ACS User's Guide for more information. Example: <property name="jnlp.vpn.vpnMaxNumOfHL" value="rum"></property> Syntax: <property name="jnlp.vpn.vpnMaxNumOfHL" value="num"></property> Description: Specifies the maximum number of hunting lists per station. Type: Integer Optionality: Optional (default used if not set) Allowed: Default: Default: 10 Notes: A hunting list is a terminating call feature where a subscriber may request a list of alternate destination addresses. If their mobile station is not attached, or does not answer a call, the service logic attempts to reach the supplied altern		The TN is displayed for any UT or AT feature node in the CPE window, without requiring you to save each feature node to update the stored control plan data.
Optionality: Optional (default used if not set) Allowed: True t(rue) Yes y(es) 1 All other values are considered to be false. Default: False Notes: If set to: • True – The feature node name is displayed as the TN in the CPE window. • False – The feature node name is displayed as the stored feature node name in the CPE window. • False – The feature node name is displayed as the stored feature node name in the CPE window. • False – The feature node name is displayed as the stored feature node name in the CPE window. • False – The feature nodes in a control plan by using the ACS Numbers screen. See the discussion about Editing Termination Numbers in ACS User's Guide for more information. Example: <property name="jnlp.acs.useTNForNodeName" value="true"></property> jnlp.vpn.vpnMaxNumOfHL Syntax: Specifies the maximum number of hunting lists per station. Type: Integer Optional (default used if not set) Allowed: Default: 10 Notes: A hunting list is a terminating call feature where a subscriber may request a list of atternate destination addresses. If their mobile station is not attached, or does not answer a call, the service logic attempts to reach the supplied alternate destinations	Туре:	Boolean
Allowed: • True • t(rue) • Yes • y(es) • 1 All other values are considered to be false. Default: False Notes: If set to: • True – The feature node name is displayed as the TN in the CPE window. • False – The feature node name is displayed as the stored feature node name in the CPE window. • False – The feature node name is displayed as the stored feature node name in the CPE window. • Vou can update the TN for these feature nodes in a control plan by using the ACS Numbers screen. See the discussion about Editing Termination Numbers in ACS User's Guide for more information. Example: <property name="jnlp.acs.useTNForNodeName" value="true"></property> jnlp.vpn.vpnMaxNumOfHL Syntax: Syntax: <property name="jnlp.vpn.vpnMaxNumOfHL" value="num"></property> Description: Specifies the maximum number of hunting lists per station. Type: Integer Optionality: Optional (default used if not set) Allowed: Default: Default: 10 Notes: A hunting list is a terminating call feature where a subscriber may request a list of alternate destination addresses. If their mobile station is not attached, or does not answer a call, the service logic attempts to reach the supplied alternate destinations in <	Optionality:	Optional (default used if not set)
 t(rue) Yes y(es) 1 All other values are considered to be false. Default: False Notes: If set to: True – The feature node name is displayed as the TN in the CPE window. False – The feature node name is displayed as the stored feature node name in the CPE window. You can update the TN for these feature nodes in a control plan by using the ACS Numbers screen. See the discussion about Editing Termination Numbers in ACS User's Guide for more information. Example: <pre><pre><pre>cproperty name="jnlp.acs.useTNForNodeName" value="true" /></pre></pre></pre>	Allowed:	• True
 Yes y(es) 		• t(rue)
 y(es) 1 All other values are considered to be false. Default: False Notes: If set to: True – The feature node name is displayed as the TN in the CPE window. False – The feature node name is displayed as the stored feature node name in the CPE window. You can update the TN for these feature nodes in a control plan by using the ACS Numbers screen. See the discussion about Editing Termination Numbers in ACS User's Guide for more information. Example: <pre><pre><pre><pre>property name="jnlp.acs.useTNForNodeName" value="true" /></pre></pre></pre></pre>		• Yes
 1 All other values are considered to be false. Default: False Notes: If set to: True – The feature node name is displayed as the TN in the CPE window. False – The feature node name is displayed as the stored feature node name in the CPE window. You can update the TN for these feature nodes in a control plan by using the ACS Numbers screen. See the discussion about Editing Termination Numbers in ACS User's Guide for more information. Example: <pre><pre>property name="jnlp.acs.useTNForNodeName" value="true" /></pre> </pre> jnlp.vpn.vpnMaxNumOfHL Syntax: <pre><pre>property name="jnlp.vpn.vpnMaxNumOfHL" value="num" /></pre> </pre> Description: Specifies the maximum number of hunting lists per station. <pre>Type: Integer Optionality: Optional (default used if not set) Allowed: Default: 10 Notes: A hunting list is a terminating call feature where a subscriber may request a list of alternate destination addresses. If their mobile station is not attached, or does not answer a call, the service logic attempts to reach the supplied alternate destinations in</pre>		• y(es)
All other values are considered to be false. Default: False Notes: If set to: True – The feature node name is displayed as the TN in the CPE window. False – The feature node name is displayed as the stored feature node name in the CPE window. You can update the TN for these feature nodes in a control plan by using the ACS Numbers screen. See the discussion about Editing Termination Numbers in ACS User's Guide for more information. Example: <pre><pre><pre>>property name="jnlp.acs.useTNForNodeName" value="true" /></pre> </pre></pre> jnlp.vpn.vpnMaxNumOfHL Syntax: <pre>>property name="jnlp.vpn.vpnMaxNumOfHL" value="num" /></pre> Description: Specifies the maximum number of hunting lists per station. Type: Integer Optionality: Optional (default used if not set) Allowed: Default: 10 Notes: A hunting list is a terminating call feature where a subscriber may request a list of alternate destination addresses. If their mobile station is not attached, or does not answer a call, the service logic attempts to reach the supplied alternate destinations in		• 1
Default: False Notes: If set to: • True – The feature node name is displayed as the TN in the CPE window. • False – The feature node name is displayed as the stored feature node name in the CPE window. • False – The feature node name is displayed as the stored feature node name in the CPE window. • False – The feature node name is displayed as the stored feature node name in the CPE window. • False – The feature node name is displayed as the stored feature node name in the CPE window. • False – The feature node name is displayed as the stored feature node name in the CPE window. • False – The feature node name is displayed as the stored feature node name in the CPE window. • False – The feature node name is displayed as the stored feature node name in the CPE window. • You can update the TN for these feature nodes in a control plan by using the ACS Numbers screen. See the discussion about Editing Termination Numbers in ACS User's Guide for more information. • Property name="jnlp.acs.useTNForNodeName" value="true" /> jnlp.vpn.vpnMaxNumOfHL Syntax: <property name="jnlp.vpn.vpnMaxNumOfHL" value="num"></property> Specifies the maximum number of hunting lists per station. Type: Integer Optionality: Optional (default used if not set) Allowed: <t< th=""><th></th><th>All other values are considered to be false.</th></t<>		All other values are considered to be false.
Notes: If set to: • True – The feature node name is displayed as the TN in the CPE window. • False – The feature node name is displayed as the stored feature node name in the CPE window. • False – The feature node name is displayed as the stored feature node name in the CPE window. • False – The feature node name is displayed as the stored feature node name in the CPE window. • False – The feature node name is displayed as the stored feature node name in the CPE window. • False – The feature node name is displayed as the stored feature node name in the CPE window. • False – The feature node name is displayed as the stored feature node name in the CPE window. You can update the TN for these feature nodes in a control plan by using the ACS Numbers screen. See the discussion about Editing Termination Numbers in ACS User's Guide for more information. Example: <property name="jnlp.acs.useTNForNodeName" value="true"></property> jnlp.vpn.vpnMaxNumOfHL Syntax: <property name="jnlp.vpn.vpnMaxNumOfHL" value="num"></property> Description: Specifies the maximum number of hunting lists per station. Type: Integer Optional (default used if not set) Allowed: Default: 10 Notes: A hunting list is a terminating call feature where a subscriber may	Default:	False
 False – The feature node name is displayed as the TN in the CPE window. False – The feature node name is displayed as the stored feature node name in the CPE window. You can update the TN for these feature nodes in a control plan by using the ACS Numbers screen. See the discussion about Editing Termination Numbers in ACS User's Guide for more information. Example: <pre><pre>cyproperty name="jnlp.acs.useTNForNodeName" value="true" /></pre></pre> jnlp.vpn.vpnMaxNumOfHL Syntax: <pre>cyproperty name="jnlp.vpn.vpnMaxNumOfHL" value="num" /></pre> Description: Specifies the maximum number of hunting lists per station. Type: Integer Optional (default used if not set) Allowed: Default: 10 Notes: A hunting list is a terminating call feature where a subscriber may request a list of alternate destination addresses. If their mobile station is not attached, or does not answer a call, the service logic attempts to reach the supplied alternate destinations in 	Notes:	If set to:
 Faise - The leature node name is displayed as the stored feature node name in the CPE window. You can update the TN for these feature nodes in a control plan by using the ACS Numbers screen. See the discussion about Editing Termination Numbers in ACS User's Guide for more information. Example: <property name="jnlp.acs.useTNForNodeName" value="true"></property> jnlp.vpn.vpnMaxNumOfHL Syntax: <property name="jnlp.vpn.vpnMaxNumOfHL" value="num"></property> Description: Specifies the maximum number of hunting lists per station. Type: Integer Optional (default used if not set) Allowed: Default: 10 Notes: A hunting list is a terminating call feature where a subscriber may request a list of alternate destination addresses. If their mobile station is not attached, or does not answer a call, the service logic attempts to reach the supplied alternate destinations in 		 I rue – I ne reature node name is displayed as the I N in the CPE window. Folse The feature node name is displayed as the start of feature will be started for the started feature will be started feature will be started feature will be started for the started feature will be started fe
You can update the TN for these feature nodes in a control plan by using the ACS Numbers screen. See the discussion about Editing Termination Numbers in ACS User's Guide for more information. Example: <property name="jnlp.acs.useTNForNodeName" value="true"></property> jnlp.vpn.vpnMaxNumOfHL Syntax: <property name="jnlp.vpn.vpnMaxNumOfHL" value="num"></property> Description: Specifies the maximum number of hunting lists per station. Type: Integer Optionality: Optional (default used if not set) Allowed: Default: Default: 10 Notes: A hunting list is a terminating call feature where a subscriber may request a list of alternate destination addresses. If their mobile station is not attached, or does not answer a call, the service logic attempts to reach the supplied alternate destinations in		 Faise – The feature node name is displayed as the stored feature node name in the CPE window.
Example: <property name="jnlp.acs.useTNForNodeName" value="true"></property> jnlp.vpn.vpnMaxNumOfHL Syntax: <property name="jnlp.vpn.vpnMaxNumOfHL" value="num"></property> Description: Specifies the maximum number of hunting lists per station. Type: Integer Optionality: Optional (default used if not set) Allowed: Default: Default: 10 Notes: A hunting list is a terminating call feature where a subscriber may request a list of alternate destination addresses. If their mobile station is not attached, or does not answer a call, the service logic attempts to reach the supplied alternate destinations in		You can update the TN for these feature nodes in a control plan by using the ACS Numbers screen. See the discussion about Editing Termination Numbers in ACS User's Guide for more information.
<pre>jnlp.vpn.vpnMaxNumOfHL Syntax: <property name="jnlp.vpn.vpnMaxNumOfHL" value="num"></property> Description: Specifies the maximum number of hunting lists per station. Type: Integer Optionality: Optional (default used if not set) Allowed: Default: 10 Notes: A hunting list is a terminating call feature where a subscriber may request a list of alternate destination addresses. If their mobile station is not attached, or does not answer a call, the service logic attempts to reach the supplied alternate destinations in</pre>	Example:	<property name="jnlp.acs.useTNForNodeName" value="true"></property>
Syntax: <property name="jnlp.vpn.vpnMaxNumOfHL" value="num"></property> Description:Specifies the maximum number of hunting lists per station.Type:IntegerOptionality:Optional (default used if not set)Allowed:IntegerDefault:10Notes:A hunting list is a terminating call feature where a subscriber may request a list of alternate destination addresses. If their mobile station is not attached, or does not answer a call, the service logic attempts to reach the supplied alternate destinations in	jnlp.vpn.	vpnMaxNumOfHL
Description:Specifies the maximum number of hunting lists per station.Type:IntegerOptionality:Optional (default used if not set)Allowed:Default:Default:10Notes:A hunting list is a terminating call feature where a subscriber may request a list of alternate destination addresses. If their mobile station is not attached, or does not answer a call, the service logic attempts to reach the supplied alternate destinations in	Syntax:	<property name="jnlp.vpn.vpnMaxNumOfHL" value="num"></property>
Type:IntegerOptionality:Optional (default used if not set)Allowed:IntegerDefault:10Notes:A hunting list is a terminating call feature where a subscriber may request a list of alternate destination addresses. If their mobile station is not attached, or does not answer a call, the service logic attempts to reach the supplied alternate destinations in	Description:	Specifies the maximum number of hunting lists per station.
Optionality: Optional (default used if not set) Allowed: Default: Default: 10 Notes: A hunting list is a terminating call feature where a subscriber may request a list of alternate destination addresses. If their mobile station is not attached, or does not answer a call, the service logic attempts to reach the supplied alternate destinations in	Туре:	Integer
Allowed:Default:10Notes:A hunting list is a terminating call feature where a subscriber may request a list of alternate destination addresses. If their mobile station is not attached, or does not answer a call, the service logic attempts to reach the supplied alternate destinations in	Optionality:	Optional (default used if not set)
Default:10Notes:A hunting list is a terminating call feature where a subscriber may request a list of alternate destination addresses. If their mobile station is not attached, or does not answer a call, the service logic attempts to reach the supplied alternate destinations in	Allowed:	
Notes: A hunting list is a terminating call feature where a subscriber may request a list of alternate destination addresses. If their mobile station is not attached, or does not answer a call, the service logic attempts to reach the supplied alternate destinations in	Default:	10
sequence.	Notes:	A hunting list is a terminating call feature where a subscriber may request a list of alternate destination addresses. If their mobile station is not attached, or does not answer a call, the service logic attempts to reach the supplied alternate destinations in sequence.

Example: <property name="jnlp.vpn.vpnMaxNumOfHL" value="15" />

jnlp.vpn.vpnMaxNumOfHLEntries

Syntax:	<property name="jnlp.vpn.vpnMaxNumOfHLEntries" value="num"></property>
Description:	Specifies the maximum number of entries in a hunting list.
Туре:	Integer
Optionality:	Optional (default used if not set)
Allowed:	
Default:	20
Notes:	
Example:	<property name="jnlp.vpn.vpnMaxNumOfHLEntries" value="25"></property>

jnlp.ccs.VRRedeemMaxVoucherLength

Syntax:	<property name="jnlp.ccs.VRRedeemMaxVoucherLength" value="int"></property>
Description:	Specifies the maximum number of digits in a voucher number.
Туре:	Integer
Optionality:	Optional (default used if not set)
Allowed:	Must be equal to or larger than VRRedeemMinVoucherLength.
Default:	18
Example:	<property name="jnlp.ccs.VRRedeemMaxVoucherLength" value="18"></property>

jnlp.ccs.VRRedeemMinVoucherLength

Syntax:	<property name="jnlp.ccs.VRRedeemMinVoucherlength" value="int"></property>
Description:	Specifies the minimum number of digits in a voucher number.
Туре:	Integer
Optionality:	Optional (default used if not set)
Allowed:	Must be equal to or smaller than VRRedeemMaxVoucherLength.
Default:	10
Example:	<property name="jnlp.ccs.VRRedeemMinVoucherlength" value="10"></property>

jnlp.acs.warnAboutUnfilledExits

Syntax:	<property name="jnlp.acs.warnAboutUnfilledExits" value="True"></property>
Description:	Specifies whether a control plan passes validation if any of its feature nodes are missing exits.
	This property has a dependency on the endUnlinkedExits parameter. For more information, see endUnlinkedExits.
Туре:	String
Optionality:	Optional

Allowed:	 True t(rue) Xos
	 y(es) 1
	All other values are considered to be false.
Default:	False
Notes:	 If set to: True – Control plans that are missing feature node exits will pass validation. To work, you must also set the endUnlinkedExits parameter to 1.
Example	• Faise - Control plans that are missing node exits will fail during valuation.
Example.	<pre><pre>>property name= jnip.acs.warnAboutonititedExits value= file //</pre></pre>
jnlp.osd.V	NSDLDirectory
Syntax: Description:	<property name="jnlp.osd.WSDLDirectory" value="file"></property> Specifies the path to the Operation Sets WSDL file.
Type:	String
Optionality: Allowed:	Optional (default used if not set)
Default:	/IN/html/wsdls
Notes:	Part of OSD.
	If you change this property's value, you must also change the wsdlUriBaseName parameter in the eserv.config file.
Example:	<property <br="" name="jnlp.osd.WSDLDirectory">value="/IN/html/wsdls" /></property>
jnlp.osd.V	ISDLURL
Syntax:	<property name="jnlp.osd.WSDLURL" value="<i>url</i>"></property>
Description:	Specifies the WSDL URL field value (same as wsdlUriBaseName parameter), and has the form of:
Turner	<pre>http://nost_name/wsdls Ctring</pre>
Type: Ontionality	String Optional (default used if not act)
Allowed	Optional (default used if not set).
Default:	http:// <unset></unset>
Notes:	Part of OSD.
	If you change this property's value, you must also change the wsdlUriBaseName parameter in the eserv.config file.
Example:	<property name="jnlp.osd.WSDLURL" value="http://nzwn-
test08.uk.oracle.com/wsdls"></property>

jnlp.sms.OverWriteSwingFont

Syntax:	<property name="jnlp.sms.OverWriteSwingFont" value="value"></property>
Description:	Specifies whether to overwrite the default font of Swing components like JTextArea, JTextPane, JOptionPane, and JTable to support some special languages (for example: Dhivehi for Maldives).
Туре:	Boolean

Optionality: Allowed:	Optional (default used if not set) True t(rue) Yes y(es) 1 All other values are considered to be false.
Default:	False
Notes:	If set to:
	 True: Certain swing component default value is overwritten with value configured for jnlp.sms.OverWriteSwingFontValue. False: Default swing component font is used
Evennley	(property percential and OverWrite GuingEent" velue="""
Example:	<pre><pre>>property name=</pre></pre>
jnlp.sms.	OverWriteSwingFontValue
Syntax:	<property name="jnlp.sms.OverWriteSwingFontValue" value="value"></property>
Description:	Specifies the font to be used for certain Swing components like JTextArea, JTextPane, JOptionPane, and JTable in order to support some special languages.
Туре:	String
Optionality:	Optional (default used if not set)
Allowed:	Any valid font available in the system.
Default:	None
M. C.	

```
Notes: This field is used if jnlp.sms.OverWriteSwingFont is set to True.
Example: Set to True
```

Java WebStart

To launch GUI applications using Java WebStart, ensure that your Web server supports the JNLP file type.

For example, to configure an Apache Web server to support JNLP files:

Step	Action
1	Open the /etc/apache/mime.types file in a text editor such as vi.
2	Add the following line to the file:
	application/x-java-jnlp-file jnlp
3	Save and close the file.
4	Restart the Apache Web server.

Example JNLP Resources and Application Properties

Here is an example of the application properties for resources in the **sms.jnlp** file. Note that other applications, such as ACS and CCS, may add properties to this file.

```
<jnlp spec="1.0+"
    codebase="http://URL_IP_ADDR/"
    href="sms.jnlp" >
```

```
<resources>
   <j2se version="1.8.0+" href="http://java.sun.com/products/autodl/j2se" />
   <property name="jnlp.packEnabled" value="true" />
   <jar href="sms.sig.jar" main="true" />
   <jar href="common.sig.jar" />
   <jar href="ojdbc7.sig.jar" />
   <jar href="oraclepki.sig.jar" />
   <extension name="Oracle Help for Java" href="ohj.jnlp" />
   <property name="java.util.Arrays.useLegacyMergeSort" value="true" />
   <jar href="acs.sig.jar" />
   <jar href="osd.sig.jar" />
   <jar href="PIsecurity.sig.jar" />
   <jar href="pi.sig.jar" />
   <jar href="dap.sig.jar" />
   <jar href="http client.sig.jar" />
   <jar href="orawsdl.sig.jar" />
   <jar href="ccs.sig.jar" />
   <jar href="UIS_GW.sig.jar" />
   <jar href="UPC.sig.jar" />
   <jar href="upcMacros.sig.jar" />
   <jar href="rims.sig.jar" />
   <jar href="xms.sig.jar" />
   <jar href="smcb.sig.jar" />
   <jar href="np.sig.jar" />
   <jar href="lcp.sig.jar" />
   <jar href="enum.sig.jar" />
   <jar href="ses.sig.jar" />
   <jar href="vpn.sig.jar" />
   <jar href="rca.sig.jar" />
   <property name="jnlp.sms.TZ" value="GMT" />
   <property name="jnlp.sms.host" value="SMS_HOST_IP_ADDR" />
<property name="jnlp.sms.logo" value="SMS/images/oracle.gif" />
   <property name="jnlp.sms.databaseID" value="1521:SMF" />
   <property name="jnlp.sms.EncryptedSSLConnection" value="true" />
   <property name="jnlp.sms.sslCipherSuites" value="(TLS_RSA_WITH_AES_128_CBC_SHA)" /> <property name="jnlp.sms.secureConnectionDatabaseHost" value="(DESCRIPTION=")")
   (ADDRESS LIST= (ADDRESS=(PROTOCOL=TCPS) (HOST=SMS HOST IP ADDR) (PORT=2484)))
   (CONNECT DATA= (SERVICE NAME=SMF)))" />
   <property name="jnlp.sms.showEFM" value="1" />
   <property name="jnlp.sms.OverWriteSwingFont" value="True" />
   <property name="jnlp.sms.OverWriteSwingFontValue" value="MV Boli" />
   <property name="jnlp.acs.SuppressTagID" value="TRUE" />
   <property name="jnlp.acs.maximiseAcsScreens" value="false" />
   <property name="jnlp.acs.Profile8" value="Account Reference Profile" />
   <property name="jnlp.acs.Profile9" value="Product Type Profile" />
   <property name="jnlp.acs.Profile10" value="Control Plan Profile (App 3)" />
   <property name="jnlp.acs.Profile12" value="CCS Global Profile" />
   <property name="jnlp.acs.Profile13" value="CCS Temporary Profile (App 6)" />
   <property name="jnlp.acs.Profile14" value="CCS Temporary Profile (App 7)" />
   <property name="jnlp.acs.Profile15" value="CCS Temporary Profile (App 8)" />
   <property name="jnlp.acs.ssfs" value="vssp,sca" />
   <property name="jnlp.acs.scfs" value="scf" />
   <property name="jnlp.vpn.INProtocol" value="IN PROTOCOL" />
   <property name="jnlp.osd.WSDLDirectory" value="/IN/html/wsdls" />
   <property name="jnlp.osd.WSDLURL" value="http://SMS HOST NAME/wsdls" />
   <property name="jnlp.ccs.UseAnnouncements" value="YES" />
   <property name="jnlp.ccs.BeORBTimeoutms" value="5000" />
   <property name="jnlp.ccs.VRRedeemMinVoucherLength" value="9" />
   <property name="jnlp.ccs.VRRedeemMaxVoucherLength" value="15" />
   <property name="jnlp.ccs.defaultEDRSearchAge" value="2" />
   <property name="jnlp.ORB_HOST" value="SMS_HOST_NAME" />
</resources>
```

<application-desc main-class="UserScreens.Application" />

</jnlp>

Configuring Nodes

SMS Nodes

During installation of the SMS software, each SMS is set up so that it is a valid replication node. Check that each node has at least the following configuration details:

- Valid primary address (or hostname)
- Node number of 1-16 (starting at 1), and
- Validator check box checked.

You can check the setup via the Node Management screen in the SMS Administration screens. For more information on node configuration and setup, see *Service Management System User's Guide*.

SLC Nodes

In a clustered installation, each SLC has one node number associated with it:

• One in the range 256 to 511 for the Update Loader

These node numbers can be assigned using the Node Management screen in the SMS Java screens.

Each Update Loader should at least have:

- Valid primary address (or hostname)
- Node number in the range 256 to 511 (the Node Numbers of the Update Loader should start at 301).
- Empty validator check box.

For more information on node configuration and setup, see the SMS User's Guide.

Statistics nodes

You must complete the process by configuring Statistics within the SMS, see SMS User's Guide.

Installing Additional Applications

Installing the applications

Follow these steps to install the applications.

Step	Action
1	Install each application to create a set of replication groups.
2	Decide which SLCs will run this application.
3	Target all of the new groups (or such different set as is advised in the instructions for the application) onto each of these SLCs (the i+256 node).

Order of replication

Please note that the order in which replication tables are added is important.

Configuring LDAP based SMS Login

This topic provides details of configurations for setting up LDAP based authentication for SMS GUI login.

Prerequisites

Before setting up LDAP authentication, ensure you have the following configured:

- LDAP Server: This is the server which will perform the user authentications. It should have proper connectivity with the client system performing the SMS GUI login.
- LDAP Template Attribute: One of the user attributes has to be identified as the attribute having the list of NCC templates that the user is assigned to. The template names can be assigned to the attribute either one to one (attribute value pair), or one to many, in a comma separated pattern. For example, if **groups** is the attribute identified to be containing the template names, and you want to assign four templates (ACS_BOSS, OSD Superuser, DAP AspEdit Full, and CCSBPL) to the user, you can use the following methods for the template entries:

Method 1: Attribute Value Pairs - one to one

groups: ACS_BOSS
groups: OSD Superuser
groups: DAP AspEdit Full
groups: CCSBPL
Method 2: Attribute Value Pairs - one to many - comma separated
groups: ACS_BOSS,OSD Superuser,DAP AspEdit Full,CCSBPL
Method 3: (Mixed)
groups: ACS_BOSS
groups: OSD Superuser,DAP AspEdit Full
groups: CCSBPL

• LDAP NCC Database User: For LDAP authentication, you need to have a user which can connect to SMF database and fetch the required screen details. As a one-time activity, a screen user (LDAP_DB_USER) should be created from the NCC user management screen, and a password should be set for that user. You need not assign any template to this newly created user. For more information about creating a screen user, see *Service Management System User's Guide*.

Configurations

All the LDAP configurations are set as properties in **sms.jnlp** file which is located in the /IN/html directory.

Property	Description
sms.ldapDbUser	This is the LDAP_DB_USER created as part of prerequisite.
	This is used to connect to SMF database when any LDAP user logs in.
	Same LDAP_DB_USER is used for all LDAP logins.
	Example:
	<property <br="" name="jnlp.sms.ldapDbUser">value="ldapDbUser" /></property>
sms.ldapProviderURL	LDAP server host connection URL. This URL is used by the GUI to connect to LDAP server in order to authenticate the user and fetch the LDAP NCC templates.
	Example:
	<property <br="" name="jnlp.sms.ldapProviderURL">value="ldap://abc.def.com:389" /></property>

This table describes the properties that needs to be configured in the resources section of the **sms.jnlp** file.

Property	Description
sms.ldapAuthType	LDAP authentication type. Following authentication types are supported:
	a. none
	b. simple
	Example:
	<property <br="" name="jnlp.sms.ldapAuthType" value="simple">/></property>
sms.ldapSecurityPrincipal	Specifies the name of the user/program performing the authentication. This depends on the value of the sms.ldapAuthType property.
	It should be set to the fully qualified domain name of the client to authenticate, as per the LDAP user's domain hierarchy in the LDAP server.
	Example:
	<property <="" name="jnlp.sms.ldapSecurityPrincipal" td=""></property>
	<pre>value="uid=#username#,ou=people,dc=my-domain,dc=com" /></pre>
	Note : The <i>#username#</i> is a place holder for the LDAP username. Wherever you need to enter the LDAP username, enter <i>#username#</i> . This is replaced with actual LDAP username (as supplied by logging-in user) during the authentication process.
sms.ldapSecurityProtocol	Specifies the name of the security protocol to be used for communicating with LDAP server. It supports ssl with TLS 1.2. If this value is left blank or unspecified, SSL will not be used for communication.
	Example:
	<property <br="" name="jnlp.sms.ldapSecurityProtocol">value="ssl" /></property>
	Note : If ssl is specified here, then update sms.ldapProviderURL to use the 'ldaps' link, instead of the usual 'ldap' link.
sms.ldapTemplateAttribute	The attribute name which has the list of templates for the LDAP users.
	Example:
	<property <br="" name="jnlp.sms.ldapTemplateAttribute">value="groups" /></property>

Background Processes on the SMS

Overview

Introduction

This chapter provides a description of the programs or executables used by the System as background processes on an SMS.

Executables are located in the /IN/service packages/SMS/bin directory.

Some executables have accompanying scripts that run the executables after performing certain cleanup functions. All scripts should be located in the same directory as the executable.

For more information about the processes and systems that use these programs and executables, see *System Overview* (on page 1).

Important: It is a pre-requisite for managing these core service functions that the operator is familiar with the basics of Unix process scheduling and management. Specifically, the following Unix commands:

- init (and inittab)
- cron (and crontab)
- ps
- kill

In this chapter

This chapter contains the following topics.

0
0
1
3
5
8
9
51
0
0
1
.3
4
5
6
8
0
1
1
2
3
4
7

cmnConfigRead

Purpose

cmnConfigRead is used by the installation process to read the configuration files.

cmnConfigRead reads the Convergent Charging Controller configuration file (eserv.config), specified by the Oracle_CONFIG_FILE environment variable and returns the value of path.

This can be used in commands to return the eserv.config specified path value.

Example:

FILENAME=`cmnConfigRead CCS.MyReport.filename
/IN/service packages/CCS/tmp/MyReport.log`

This sets \$FILENAME to the value of CCS.MyReport.filename. If CCS.MyReport.filename is not present or there is an error, \$FILENAME defaults to /IN/service_packages/CCS/tmp/MyReport.log.

Startup

cmnConfigRead is started by the system and is not intended to be changed by the user.

cmnReceiveFiles

Purpose

cmnReceiveFiles collects EDRs from cmnPushFiles and writes them to the specified directory on the SMS.

Warning: You must install the xinetd daemon as a prerequisite to running cmnReceiveFiles. You install this daemon by entering the following command:

yum install xinetd

Startup

cmnReceiveFiles is started by the following entry in /etc/inetd.conf:

smsoperFile stream tcp nowait smf_oper /IN/service_packages/SMS/bin/
cmnReceiveFilesStartup.sh

Parameters

cmnReceiveFiles does not have any direct parameters or configuration. Most details are provided by cmnPushFiles with the EDR.

The port cmnReceiveFiles listens on is set in /etc/services in the following line:

smsoperFile 2028/tcp # cmnAddInetServicesEntry

Important: The port number must match the port specified by cmnPushFiles.

Failure

If cmnReceiveFiles fails, the EDRs stay on the SLC and are moved to the retry directory. For more information about this process, see *cmnPushFiles* (on page 174).

Output

cmnReceiveFiles writes the EDRs to the directory specified by cmnPushFiles.

smsAlarmDaemon

Purpose

The smsAlarmDaemon executable runs on all alarm-managed nodes in the SMS system, including the SMS node itself. The role of smsAlarmDaemon is to gather alarms from the following sources:

- Error messages log (/var/adm/messages)
- Oracle error log (\$ORACLE_BASE/admin/S/D/bdump/alert_S/D.log)
- Sigtran stack logs (/IN/service_packages/SLEE/stats) [If installed]

On the SMS machine itself, the error messages are written directly into the SMF_ALARM_MESSAGE database table. When run on other nodes, replication is used to update the SMF_ALARM_MESSAGE table.

Alarm replication and buffering

smsAlarmDaemon allows only a limited number of alarms to be sent within a configured time period. Both the number of messages that can be sent within a time period and the length of each period can be configured from the command line.

If more messages arrive than are allowed through the filter, the remaining messages are buffered and sent later. The buffer size is limited but can hold a large number of messages. If it needs to make more space, it discards messages of the lowest severity (informational). The buffer also has an upper limit, ensuring that the daemons do not grow unchecked. This upper limit defaults to a maximum of 1000 messages and can be configured.

If more than one of the same alarm appears within the configured time, only one update request is sent.

Startup

In an unclustered install, this task is started by entry sms5 in the inittab, through the /IN/service_packages/SMS/bin/smsAlarmDaemonSmsStartup.sh shell script.

In a clustered install, this task is started by the clustering software, through the /IN/service_packages/SMS/bin/smsAlarmDaemonCluster.sh shell script.

Configuration

smsAlarmDaemon accepts the following command-line arguments.

Usage:

```
smsAlarmDaemon [-1 seconds] [-h seconds] [-n number] [-m number] [-p] [-d] [-a path]
[-r node] [-u user/pass] [-f] [-i] [-g] [-c number] [-t seconds]
```

The available parameters are:

Parameter	Default	Description
-a path	Null	Propagate alarms from the specified Oracle alert log to the database.
		By default, smsAlarmDaemon does not propagate alarms from the Oracle alert log.
-c number	1	Commit Rate. The number of inserts before committing to the database.
-d	Sort messages	Disable sorting of messages in the buffer by severity. Specifically, messages are kept in the buffer and subsequently written into the SMF database, in the same sequence in which they are received.
-f	No filtering	Filtering. Delete duplicate alarms and increase the alarm count.
-g	Uses local time	GMT timezone. Use GMT instead of local time.
-h seconds	60	Heartbeat message. Will be forced to be greater or equal to time period (seconds).
-i	Use fuzzy matching	Filtering type. Use exact matching (rather than fuzzy matching). Indicates that duplicate matches should be performed on text only (that is, excluding digits).
		Note: Only valid when used in conjunction with -f.
-l seconds	2	Filter Period. Duration between linked-list checks (in seconds).
-n <i>number</i>	5	Filter Number. The number of alarm messages allowed within the time period.
_m_number	1000	Anowed values. Integers
-m number	1000	Allowed values: Integers 1-1000000
-p	Do not drop messages	Drop low-priority messages when the buffer is full. Specifically, when -m <i>number</i> messages have been received but it is not yet time to write the buffer contents to the SMS database, low priority messages in the buffer are dropped in favor of higher-priority messages that may be received on its input stream.

Parameter	Default	Description
-r node	Direct to the Oracle DB	Replication node. Specify the replication requester node.
-t seconds	1	Commit interval. The maximum interval between database commits (in seconds).
-u user/pass	/	Use the supplied Oracle user/password pair.

Usage example

Here is an example of using smsAlarmDaemon:

smsAlarmDaemon -l 5 -h 30 -n 10 -m 2000 -p -d -a /volB/home/saich -r 750 -u smf/smf -f -i -g -c 2 -t 2

- Filter Period (-I) = 5 seconds
- Heart beat (-h) = Yes every 30 seconds
- Filter Number (-n) = 10 each period
- Max number(-m) = 2000 records
- Drop low priority messages (-p) = true
- Sort messages by severity (-d) = false
- Oracle Alert Log location (-a) = /volB/home/saich
- Rep node (-r) = 750
- Oracle User (-u) = smf/smf
- Filtering (-f) = Multiple alarms combined
- Filtering type (-i) = Exact match
- GMT timezone (-g) = Yes
- Commit Rate (-c) = every 2 number of inserts
- Commit Interval (-t) = every 2 seconds if 2 records not reached

Failure

The smsAlarmDaemon on each alarm-managed node in the installation will by default generate a health-check alarm once per minute. These health check alarms will be relayed in the same fashion as all other alarms.

If these health check alarms are not received at the target destination, then the smsAlarmDaemon may have failed, and should be investigated.

Output

The smsAlarmDaemon writes error messages to the system messages file, and also writes additional output to /IN/service_packages/SMS/tmp/smsAlarmDaemonSms.log.

smsAlarmManager

Purpose

The smsAlarmManager runs on the SMS. The role of the smsAlarmManager is to:

• Match alarm instances to the correct alarm types

- Automatically time out alarms that have not been cleared
- record alarm instances that have no alarm type match

Startup

This task is started by entry efm1 in the inittab, through the /IN/service_packages/EFM/bin/smsAlarmManagerStartup.sh shell script.

The inittab entry will be similar to that shown below:

```
efm1:34:respawn:su - smf_oper -c "exec
/IN/service_packages/EFM/bin/smsAlarmManagerStartup.sh >> /IN
/service_packages/EFM/tmp/smsAlarmManager.log 2>&1" > /dev/null 2>&1 0<&1</pre>
```

Configuration

The smsAlarmManager accepts the following command line arguments.

Usage:

```
smsAlarmManager -a alarm_batch_size -c correlate_batch_size -o timeout_commit_rate -
p pending_timeout_length -r reload_defn_interval -s number -t timeout_check_interval
-u user/password
```

The available parameters are:

Parameter	Default	Description
-a alarm_batch_size	20	The number of alarms to attempt to find an ID for before carrying on to other tasks.
-c correlate_batch_s ize	20	The number of non-correlated CLEAR alarms to attempt to correlate against open alarms before carrying on to other tasks.
-o timeout_commit_ra te	1000	The number of rows to update with automatic timeout before committing.
-p pending_timeout_l ength	280	The amount of time given to another node in the cluster before assuming that it has failed to generate an ALARM_TYPE_ID
-r	86400	interval (s) for reloading the alarm definitions for the DB.
reload_defn_inter val		Interval between reloading the regular expressions from SMF_ALARM_DEFN and SMF_ALARM_IGNORE. This should only be needed after an install of new packages/patches, and also acts to keep the preferred cache current
-s	50000	interval (microseconds) to sleep for when no work to do
-t timeout_check_int erval	300	Interval between checks for alarms that need to be closed with a timeout.
-u "user/password"	/	u "/" The username/password combination used to log into the database. The default value is sufficient if smsAlarmManager is executed from the smf_oper user account.

smsAlarmManager will respond to SIGHUP, to reread the regular expressions from the database.

Failure

The smsAlarmManager matches alarm instances with alarm types and updates the alarm instances with the extra information. Should any of the following occur the smsAlarmManager may have failed, and should be investigated.

- Alarms missing expected information
- · Alarm clearances are not not being matched with the corresponding alarms
- Alarms not being automatically timed out

If the smsAlarmManager cannot match an alarm instance with an alarm type, it will save the alarm text into the SMF_ALARM_UNKNOWN database table.

Output

On startup the smsAlarmManager logs the following information:

```
smsAlarmManager startup.
Alarm Batch Size = 20
Correlate Batch Size = 20
Pending Timeout Length = 280
Timeout Check Interval = 300
Reload Defn Interval = 86400
Timeout Commit Rate = 1000
Sleep Time (microseconds) for no Work = 50000
Username/Password = /
Aug 30 15:31:07 smsAlarmManager(18347) NOTICE: smsAlarmManager started.
Cache successfully reloaded
```

smsAlarmRelay

Purpose

The smsAlarmRelay is responsible for implementing the *SNMP Agent* (on page 70). It runs continuously, polling the database to check for new entries written into the SMF_ALARM_MESSAGE table by the smsAlarmDaemon processes running on the various managed nodes which form the SMS-managed installation.

The information in the SMF_ALARM_MESSAGE is relayed to the destinations, as configured in the SMF_ALARM_HANDLER table using the Alarm Notification screens. For more information about how to configure alarm relay destinations, see the *Service Management System User's Guide*.

You can configure smsAlarmRelay to do the following:

- Send X.733 information with all forwarded alarms
- Check for SNMP requests (to resend alarms)
- Send version 3 (instead of version 1) SNMP traps

Startup

In an unclustered installation, this task is started by entry sms1 in the inittab, through the /IN/service_packages/SMS/bin/smsAlarmRelayStartup.sh shell script.

In a clustered installation, this task is started by the cluster software, through the /IN/service_packages/SMS/bin/smsAlarmRelayCluster.sh shell script.

Parameters

The smsAlarmRelay accepts the following command line arguments.

Usage:

smsAlarmRelay [-u <usr/pwd>] [-s <secs>] [-p] [-x] [-t] [-e]

Note: SNMP processing is not currently enabled by default.

The available parameters are:

-u

-u				
Syntax:	-u user/pwd			
Description:	The Oracle user and password pair.			
Туре:	String			
Optionality:	Optional (default used if not set).			
Allowed:				
Default:	/			
Notes:				
Example:				
-s				
Syntax:	-s seconds			
Description:	The number of seconds to sleep between database checks.			
Туре:	Integer			
Optionality:	Optional (default used if not set).			
Allowed:				
Default:	1			
Notes:				
Example:				
-р				
Syntax:	-p			
Description:	Whether to do SNMP processing or not.			
Туре:	Boolean			
Optionality:	Optional (default used if not set).			
Allowed:	set Use SNMP			
	not set Do not use SNMP			
Default:	not set			
Notes:				
Example:				
-x				
Syntax:	-x			
Description:	Whether to send SNMP traps in X.733 format or not.			
Туре:	Boolean			
Optionality:	Optional (default used if not set).			

Allowed:	set	Send in X.733 format.	
Default: Notes: Example:	not set	Do not send in X.733 format.	
-t			
Syntax: Description:	-t Whether t	o format the enterprise id with the severity	
Type:	Boolean		
Optionality:	Optional (default used if not set).		
Allowed:	set	Insert severity into penultimate object of the extended enterprise id.	
	not set	Do not format enterprise id with severity.	
Default:	not set		
Notes:			
Example:			
-е			
Syntax:	-e		
Description:	Loads the EFM rules from the smf_alarm_relay_filter database table to provide alarm filtering.		
Туре:	Boolean		
Optionality:	Optional.		
Allowed:	Set or not	set.	
Default:	Not set		

Resend Alarms

The smsAlarmRelay can be configured to listen for a request to resent all alarms above a certain alarm number. This is designed for use by an SNMP Manager that has been off line for a while and may have missed some alarm notifications.

To request a resend of alarms the relay application needs send an SNMP set-request using the format described in the **variables.mib** file.

The smsAlarmRelay will listen using the port number specified as the listenPort parameter in **snmp.cfg**. The alarmRelay keeps an internal count of the highest alarm number sent. When a valid SNMP setrequest is received, the alarmRelay will take note of the number in the message and send all alarms with an alarm ID greater than this number.

Failure

The smsAlarmDaemon on each alarm-managed node in the installation will by default generate a health-check alarm once per minute. These health check alarms will be relayed in the same fashion as all other alarms.

If these health check alarms are not received at the target destination, then the smsAlarmRelay may have failed, and should be investigated.

Output

The smsAlarmRelay.sh writes error messages to the system messages file, and also writes additional output to /IN/service_packages/SMS/tmp/smsAlarmRelay.log.

The following table summarizes the information in the Service Management System User's Guide.

Destination	Field Content		
SNMP	Host name of the target SNMP TRAPS recipient		
FILE	Name of a file to which the daemon has write access		
NFM	Host name of the NFM target.		
Q3	Host name of the Q3 target.		
SNMP	Host name of the SNMP target.		
NORELAY	The field is empty, as the alarm is not forwarded to a target		

Note: Setting the target to NORELAY will stop any other notification rules being actioned. Consequently, the NORELAY rules must be very specific. Otherwise an important alarm may accidentally be missed.

smsConfigDaemon

Purpose

smsConfigDaemon exists on both the source node (example, SMS) as well as the target node (example, SLC). It takes an optional parameter (-m) which decides its action.

When run with the -m, it monitors for changes to the master XML file (example, esgConfigMaster.xml). If it finds changes made to the master config file, smsConfigDaemon will call smsSendConfig.sh.

If the the -m parameter is missing, smsConfigDaemon monitors for changes to the derived **eserv.config** file (example, **eserv.config.derived**) on the target node, and calls **smsApplyConfig.sh** if it finds changes to the file.

About database connections

smsConfigDaemon connects to the database on a local or a remote SMS node by using the user credentials set in the following environment variables in smsConfigVariables.sh:

- SMP_DB_USER_NAME
- SMP_DB_PASSWORD
- SMP_DB_CONNECT_STRING

For connections to a:

- Local database, specify the username and password by setting the SMP_DB_USER_NAME and SMP_DB_PASSWORD variables. You can set only the user name in the SMP_DB_USER_NAME variable, if required.
- Remote database, specify the username and password by setting the SMP_DB_USER_NAME and SMP_DB_PASSWORD variables, and specify the SID of the remote database in the SMP_DB_CONNECT_STRING variable. You can set the SMP_DB_USER_NAME and the SMP_DB_CONNECT_STRING variables only, if required.
- Local or a remote database by using the Oracle wallet secure external password store, specify only the TNS connection string in the SMP_DB_CONNECT_STRING variable, where the connection string is the alias defined for the username and password credentials in the external password store. This alias can be either a TNS name or a service name from tnsnames.ora. The SMP_DB_CONNECT_STRING variable has the following format: "\@connect_string".

Note: If you set none of these variables, smsConfigDaemon connects to the database by using the default value of "/".

Startup

smsConfigDaemon is started by the script smsConfigDaemonScript. This process is driven by the system and is not intended to be changed by the user.

Configuration

For more information on the parameters used by smsConfigDaemon, see *smsConfigDaemonScript Configuration* (on page 130).

Failure

If the smsConfigDaemon fails, the secondary scripts, **smsSendConfig.sh** and **smsApplyConfig.sh** will fail to start and distribution of the updated configuration files is affected. Appropriate alarm messages are generated.

Output

The smsConfigDaemon and its sub-scripts write error messages to the system messages file, and also write additional output to /IN/service_packages/SMS/tmp/smsConfigDaemonMaster.log if they reside on the target node to /IN/service_packages/SMS/tmp/smsConfigDaemonClient.log.

smsConfigDaemonScript

Purpose

smsConfigDaemonScript is responsible for starting the smsConfigDaemon process. It also runs the **smsConfigVariables.sh** script which includes a set of configurable environment variables that are used by smsConfigDaemon and its helper scripts; for example, to set the username and password credentials for connecting to the Oracle database.

For more information about smsConfigDaemon, see smsConfigDaemon (on page 128).

Environment variables set in smsConfigVariables.sh

The smsConfigVariables.sh file is located in the following directory:

/IN/service_packages/SMS/bin

The following tables lists descriptions for the environment variables that you can configure in the smsConfigVariables.sh file and provides their default values.

Variable	Default Value	Description
SMP_DB_USER_NAM E	None	The Oracle user that smsConfigDaemon uses to log in to the Oracle database.
SMP_DB_PASSWORD	None	The password for the Oracle user that smsConfigDaemon uses to log in to the Oracle database.
SCP_DB_USER_NAME	None	The Oracle user that the smsSignalConfigChange script uses to access sqlplus.

Variable	Default Value	Description
SCP_DB_PASSWORD	None	The password for the Oracle user that the smsSignalConfigChange script uses to access sqlplus.
SMP_DB_CONNECT_S TRING	None	Any extra connect parameters that smsConfigDaemon requires to log in to the Oracle database.
DETECTION_PERIOD	10	The number of seconds between smsConfigDaemon change detection attempts.
RETRY_PERIOD	60	The number of seconds between smsConfigDaemon sendConfig retry attempts.
SLEEP_TIME	100	The number of milliseconds to sleep inside the smsConfigDaemon main loop.

Configuration

smsConfigDaemonScript sets the configurable parameters for smsConfigDaemon and its helper scripts.

The available parameters are:

Parameter	Default	Description
smp_db_user user/password		Oracle user/password for the SMF. Example: smf/smf
scp_db_user user/password		Oracle user/password for the smsSignalConfigChange script should use for sqlplus. Example: scp/scp
connect_strin g		Any extra connect parameters to be used by smsConfigDaemon
detection_per iod	10	Period (in seconds) after which smsConfigDaemon attempts to detect changes.
retry_period	60	Period (in seconds) after which smsConfigDaemon attempts to retry initiating sendConfig.
sleep_time	100	Period (in milliseconds) to wait inside smsConfigDaemon's main loop.
source_root	/IN/html/Configur ation	Location where all the XML-driven config files and directories are stored.
		Not to be changed by the user.
<pre>master_xml_di</pre>		Location of the master config.xml file.
r		Not to be changed by the user.
<pre>master_config _file</pre>	esgConfigMaster	Name of the master configuration xml file.
<pre>master_config _file_full_pa th</pre>		Full path of the master configuration file monitored by the SMP config daemon (derived from the master config xml file).
archive_xml_d ir		Location where the master config.xml files are archived to prior to modification.
derived_eserv _dir		Location of the derived eserv file.
pending_dir		Location where the config files from failed updates are held, pending a retry.

Parameter	Default	Description
<pre>xml_convert_s cript</pre>		Location of the XML to eserv.config converter script.
target_root	/IN/service_pack ages/Configuratio n	Location of the USP nodes where the eserv.config file is sent.
target_eserv_ config_dir		Location on the USP nodes where the eserv.config file is pushed out to.
derived_eserv	eserv.config .derive d	Name of the eserv.config file sent to the target nodes.
derived_confi g_file_full_p ath		Full path of the derived config file monitored by the SCP config daemon (derived from the eserv.config file sent to the target nodes)
<pre>management_in terface_host</pre>	localhost	Location of the management interface.
<pre>management_in terface_port</pre>		Port is the management interface listening on.

Note: It is not recommended to change the values of these parameters. All necessary configuration is done at installation time by the configuration script; this section exists for information only. Please contact Oracle support prior to attempting any modification to configuration data.

Startup

smsConfigDaemonScript is started by the system and is not intended to be changed by the user.

Failure

If smsConfigDaemonScript encounters problems, the smsConfigDaemon will fail to start and the updated **eserv.config** data will not be copied to the relevant platforms. Appropriate alarm messages are generated.

Output

The smsConfigDaemonScript writes error messages to the system messages file, and also writes additional output, when smsConfigDaemon has been started using the -m option, to the /IN/service_packages/SMS/tmp/smsConfigDaemonMaster.log.

If the -m option is not used, output will be written to /IN/service_packages/SMS/tmp/smsConfigDaemonClient.log.

smsCdrArchiver

Purpose

smsCdrArchiver performs a daily search of a specified input directory for CDR or EDR files to archive, and archives them to a file in a specified output directory. It also compresses and deletes old archive files according to the rules specified in the smsCdrArchiver configuration.

About archive file names

The name of the archive file output daily by smsCdrArchiver has the following format:

[machineName]+[outputFileTag]+[_serviceType]+_Date[-HH]+[outputFileSuffix]

Where

- *machineName* is the name of the machine that generated the data record. smsCdrArchiver prefixes the output file name with the machine name when you set the useMachineName parameter to true.
- *outputFileTag* is an identifying tag for the output file that you specify in the optional outputFileTag parameter.
- *serviceType* is the service type that generated the data record. smsCdrArchiver includes the service type in the output file name when you set the useServiceType parameter to true.
- Date is the date timestamp for the data record formatted as: YYYYMMDD.
- *HH* is the record hour that is appended to the *Date* value by using the following format: YYYYMMDD-HH, when you set the <code>UseRecordHour</code> parameter to true.
- outputFileSuffix is the suffix specified in the optional outputFileSuffix parameter that is appended to the output file name.

File name example

smsCdrArchiver has the following output file parameters configured in the eserv.config file:

```
smsCdrArchiver = {
    ...
    outputFileTag = "ACS"
    outputFileSuffix = ".cdr"
    useRecordHour = true
    useMachineName = true
    useServiceType = true
    ...
}
```

For machine name "telco-p-uas", service type "ACS", and timestamp "2014061512", the following output file would be created:

telco-p-uasACS_ACS_20140615-12.cdr

Startup

 $SMS = \{$

The smsCdrArchiver process is started by the smsCdrArchiver.sh script, that is located in the /IN/service_packages/SMS/bin/ directory. The smsCdrArchiver.sh script runs in the crontab for the smf_oper user.

Configuration

You configure smsCdrArchiver in the SMS, smsCdrArchiver section of the eserv.config configuration file:

```
smsCdrArchiver = {
   recordType = "CDR"
   inDir = "/cdr/processed"
   outDir = "/cdr/CDR-archive"
   outputFileSuffix = ".cdr"
   useRecordHour = true
   useMachineName = true
   useServiceType = true
   writeIndexFile = false
   useDateOutDirs = true
   prefixFileName2Data = false
   fileMatch = "telco-p-uas\*_ACS_"
   fileOwner = "smf_oper"
```

```
compressionCommand = "GZIP"
       compressModTime = 2
       compressImmediately = false
       compressMinRunTime = 0
       deleteModTime = 31
       runCleanupHour = 03
       BFT = \{
           exportBFTDataRecords = true
           exportBFTOutDir = "/cdr/export/BFT"
           exportBFTOutputFileSuffix = ""
           changeBFTOutputFileGroup = ""
           compressBFTDataRecords = true
           exportBFTKeepDays = 4
           ext5BFTHex2Dec = false
           zeroPadExt5Hex2Dec = 0
       }
   }
}
```

smsCdrArchiver parameters

The smsCdrArchiver section accepts the following parameters.

recordType

Syntax:	<pre>recordType = "str"</pre>
Description:	 Defines the type of data records to archive. When recordType is set to: CDR (for ACS Call Data Records), the ACS TCS (Time Call Start) tag is used to find the timestamp EDR (for VWS Event Data Records), the VWS RECORD_DATE tag is used to find the date timestamp
Туре:	String
Optionality:	Required
Allowed:	CDR, EDR
Default:	
Notes:	
Example:	recordType = "CDR"
inDir	
Syntax:	inDir = "dir"
Description:	The directory that contains CDR or EDR input files.
Туре:	String
Optionality:	Required
Allowed:	A vaild directory path and name.
Default:	
Notes:	ccsCdrArchiver will not search sub-directories of the specified directory for input files.
Example:	inDir = "/cdr/processed"

Chapter 5

outDir

outDir = value
The output directory for the archived CDR or EDR file.
String
Required
A valid directory path and name
<pre>outDir = "/cdr/CDR-archive"</pre>

outputFileTag

Syntax:	outputFileTag = "str"
Description:	An identifying tag for the output file, such as the name of the application that generated the data records. For example, for ACS CDRs set <code>outputFileTag</code> to "ACS".
Туре:	String
Optionality:	Optional
Allowed:	
Default:	Not used
Notes:	
Example:	<pre>outputFileTag = "ACS"</pre>

outputFileSuffix

Syntax:	<pre>outputFileSuffix = "suffix"</pre>
Description:	The suffix to append to the name of the output file; for example, ".cdr" or ."edr"
Туре:	String
Optionality:	Optional
Allowed:	
Default:	Not used
Notes:	
Example:	<pre>outputFileSuffix = ".cdr"</pre>

useRecordHour

Syntax:	useRecordHour = true false
Description:	When set to true, the record hour is appended to the record date in the archive output file name by using the following format: YYYYMMDD-HH
	Where YYYYMMDD is the record date, and HH is the record hour.
Туре:	Boolean
Optionality:	Optional
Allowed:	true, false
Default:	Not used
Notes:	
Example:	useRecordHour = true

useMachineName

Syntax:	useMachineName = true false
Description:	When set to true, prefix the archive output file name with the name of the machine that generated the data record.
Туре:	Boolean
Optionality:	Optional (default used if not set)
Allowed:	true, false
Default:	false
Notes:	The machine name can only be used in the output file name if the input file name has been prefixed with the machine name. This is the standard used by the cmnPushFiles process.
Example:	useMachineName = true

useServiceType

Syntax:	useServiceType = true false
Description:	 Include the data record service type tag in the output file name. The service type: For CDR records is specified in field 1 For EDR records is specified in the CDR TYPE field
Туре:	Boolean
Optionality:	Optional (default used if not set)
Allowed:	true, false
Default:	false
Notes:	
Example:	useServicetype = true
writeInde	exFile

Syntax:	<pre>writeIndexFile = true false</pre>
Description:	When set, smsCdrArchciver writes an index file that links data record entries to the output file name. The name of the index file is <i>outputFilename</i> .idx, where <i>outputFilename</i> is the archive output file name.
	Index file entries have the following formats:
	 CDR index file format: Date Time CID CLI ServiceType(field 1) [Data_SessionID]
	 EDR index file format: Date Time SEQUENCE_NUMBER CLI CDR_TYPE [Data_SessionID]
	Where:
	• Data_SessionID is the ID for the data session
	 CID in the CDR index file correlates to the VWS EDR SEQUENCE_NUMBER value (where applicable)
	You use the index file to search, based on the fields listed above, for the identity of the archived output file containing the complete record.
Туре:	Boolean
Optionality:	Optional (default used if not set)
Allowed:	true, false
Default:	false

Notes:	Using this option requires extra processing that can cause the smsCdrArchiver to run
	more slowly.

Example: writeIndexFile = true

useDateOutDirs

useDateOutDirs = true false		
When set to true, smsCdrArchiver separates output files into date (YYYYMMDD) directories based on the TCS or RECORD_DATE values. The output files are written to the following location: <pre>outDir/YYYYMMDD/outFile</pre>		
Boolean		
Optional (default used if not set)		
true, false		
false		
Using this option requires extra processing that can cause the smsCdrArchiver to run more slowly.		
useDateOutDirs = true		

prefixFileName2Data

Syntax:	prefixFileName2Data = true false		
Description:	When set to true, smsCdrlArchiver prefixes the archived data record with the filename of the CDR or EDR record, by using the following format:		
	original_filename:data_record_entry.		
	Where:		
	 original_filename is the name of the original file that contains the CDR or EDR record 		
	 data_record_entry is the archived data record 		
	You can use this option to identify the original filename in case of loading errors; for example, for CCS EDRs that are post-processed by the ccsCdrLoader.		
Туре:	Boolean		
Optionality:	Optional (default used if not set)		
Allowed:	true, false		
Default:	false		
Notes:	You should use this option for EDRs only.		
Example:	prefixFileName2Data = true		
fileMatch			
Syntax:	fileMatch = "str"		
Description:	Use to search for file names that match the prefix defined by the specified regular		

escription:	Use to search for file names that match the prefix defined by the specified regular expression. You can define more than one prefix to match. The prefixes should be enclosed in double quotes "", and separated by white space.
	 You can include the following wild cards in prefix strings: * wild card at the end of each prefix string
	\wild card to prevent shell expansion and unexpected results

Туре:	String
Optionality:	Optional
Allowed:	
Default:	Not set
```
Notes:
```

Example: filematch = "telco-p-uas* ACS "

fileOwner

Syntax:	fileOwner = "str"	
Description:	When set, smsCdrArchiver locates only those files that are owned by the specified user.	
Туре:	String	
Optionality:	Optional	
Allowed:		
Default:	Not set	
Notes:		
Example:	fileOwner = "smf_oper"	

compressionCommand

Syntax:	compressionCommand = "str"	
Description:	Specifies the compression utility to use for compressing old archive files.	
Туре:	String	
Optionality:	Optional (default used if not set)	
Allowed:	GZIP, BZIP2, PBZIP2	
Default:	GZIP	
Notes:		
Example:	compressionCommand = GZIP	

Billing Failure Treatment CDR parameters

The Billing Failure Treatment (BFT) parameters define rules for exporting BFT data records to a special directory for BFT post processing by the billing server.

Note: The BFT parameters apply only to ACS CDRs, where the recordType field is set to "CDR".

You configure BFT parameters in the smsCdrArchiver, BFT section of the **eserv.config** file by using the following syntax:

```
smsCdrArchiver = {
    BFT = {
        exportBFTDataRecords = true
        exportBFTOutDir = "/cdr/export/BFT"
        exportBFTOutputFileSuffix = ""
        changeBFTOutputFileGroup = ""
        compressBFTDataRecords = true
        exportBFTKeepDays = 4
        ext5BFTHex2Dec = false
        zeroPadExt5Hex2Dec = 0
    }
}
```

exportBFTDataRecords

Syntax: exportBFTDataRecords = true|false

Description: Enables BFT CDRs to be exported to the directory specified by the exportBFTOutDir parameter.

Chapter 5

Туре:	Boolean
Optionality:	Optional (default used if not set)
Allowed:	true, false
Default:	false
Notes:	
Example:	<pre>exportBFTDataRecords = true</pre>

exportBFTOutDir

Syntax:	exportBFTOutDir = "str"	
Description:	The directory path for the directory to which to export BFT CDRs.	
Туре:	String	
Optionality:	Optional	
Allowed:		
Default:		
Notes:		
Example:	exportBFTOutDir = "/cdr/export/BFT"	

exportBFTOutputFileSuffix

Syntax:	exportBFTOutputFileSuffix = "str"	
Description:	Specifies the suffix for the BFT output file. If this is unset, then the original input file name is used.	
Туре:	String	
Optionality:	Optional	
Allowed:		
Default:		
Notes:	White spaces are replaced by the _ (underscore) character.	
Example:	exportBFTOutputFileSuffix = ""	

changeBFTOutputFileGroup

<pre>changeBFTOutputFileGroup = "str"</pre>	
Sets the group file permissions for the output file; for example, to change group read/write access to allow third parties to collect BFT CDRs for post processing.	
String	
Optional (default used if not set)	
The group file permissions must be valid for the user running the smsCdrArchiver script.	
If the group is invalid, or left undefined, then the group file permissions are not changed.	
changeBFTOutputFileGroup = ""	

compressBFTDataRecords

Syntax:	compressBFTDataRecords = true false
Description:	Set to true to compress the BFT oputput files as they are written. If set to false, then the compressModTime parameter does not take the BFT CDR files into account and no further compression will be done.
Туре:	Boolean
Optionality:	Optional (default used if not set)

Allowed:	true, false	
Default:	true	
Notes:	The compression utility used is defined by the compressionCommand parameter.	
Example:	compressBFTDataRecords = true	

exportBFTKeepDays

Syntax:	exportBFTKeepDays = int
Description:	The number of days to keep the exported BFT CDRs before they are deleted.
Туре:	Integer
Optionality:	Optional (default used if not set)
Allowed:	
Default:	1 - The default value of one will be used if you specify a value that is less than one.
Notes:	
Example:	exportBFTKeepDays = 4

ext5BFTHex2Dec

Syntax:	ext5BFTHex2Dec = true false	
Description:	Whether the ACS CDR EXT5 field is written as a hexidecimal value, such as EXT5=0000000A , or whether it is converted to a decimal value, such as EXT5=10 , for the BFT post-processing tools.	
Туре:	Boolean	
Optionality: Allowed:	Optional (default used if not set) true (use decimal values) false (use hex values) 	
Default: Notes:	false	
Example:	<pre>ext5BFTHex2Dec = false</pre>	

zeroPadExt5Hext2Dec

Syntax:	<pre>zeroPadExt5Hext2Dec = int</pre>	
Description:	The number of leading zeros to use when padding the converted EXT5 decimal number (if <code>ext5BFTHex2Dec</code> is set to true). Set to 0 (zero) or 1 (one) for no leading zero padding.	
Туре:	Integer	
Optionality:	Optional (default used if not set)	
Allowed:		
Default:	0	
Notes:	If $zeroPadExt5Hext2Dec$ is set to a negative number then the decimal number will be padded so that it is the same length as the original hex number. For example, the hex number: 0000000A is converted to the decimal number: 00000010.	
Example:	zeroPadExt5Hext2Dec = 0	

smsCdrProcess.sh

Purpose

smsCdrProcess.sh performs basic EDR processing and archiving. **smsCdrProcess.sh** runs the smsProcessCdr binary with specified command line parameters. One output EDR file is created for each input EDR file.

smsCdrProcess.sh can also be configured to prevent processing the EDR.

For more information about how smsProcessCdr processes EDRs, see smsProcessCdr (on page 222).

EDR format

The format of the records in the EDR file are specific to the application which generates them. The most commonly used EDR format processed by this mechanism is the ACS "Pipe Tag LF" format, which uses TAG=VALUE pairs separated by the "|" character. Records are line field delimited.

For more information about this format, see the ACS Technical Guide.

Startup

This task is run in the crontab for smf_oper, by default at 1:00 am system clock time. It is scheduled as the /IN/service_packages/SMS/bin/smsCdrProcess.sh script.

The script runs the smsProcessCdr process with set parameters.

Configuration

The following command in the **smsProcessCdr.sh** prevents the EDR from being processed and copies it directly to the output directory.

Example Command: \$BINDIR/smsProcessCdr -d \$CDRDIR -D \$OUTDIR -s \$INSFX -S \$OUTSFX To process EDRs, use the following command instead:

```
Example Command: $BINDIR/smsProcessCdr -t $OUTFMT -d $CDRDIR -D $OUTDIR -s $INSFX -S $OUTSFX
```

Failure

If the process is not running, EDR files will build up in the /IN/service_packages/SMS/cdr/received directory.

The filesystem usage will rise above standard operational levels.

Output

The smsCdrProcess.sh writes error messages to the system messages file, and also writes additional output to /IN/service_packages/SMS/tmp/smsCdrProcess.sh.log.

smsDbCleanup.sh

Purpose

This task executes SQL statements to delete old data from the following tables.

SQL Statement	Data deleted
SMF_AUDIT	Audit trail of database changes.
SMF_STATISTICS	Application bulk usage counters.

140 Service Management System Technical Guide

SQL Statement	Data deleted
SMF_ALARM_MESSAGE	System messages.
SMF_ALARM_UNKNOWN	System messages which do not match any known alarm definitions.

Startup

This task is run in the crontab for smf_oper, by default at 1:00 am system clock time. It is a shell script, specifically /IN/service_packages/SMS/bin/smsDbCleanup.sh.

Parameters

The decision on when to delete data is determined according to various parameters configured in **eserv.config**. These values can be changed by the usual **eserv.config** editing method, subject to database sizing limitations and availability of space for additional historical data.

The default parameters are:

Parameter	Default	Description	
alarmAge	7	Delete records older than this number of days. Refers to the actual age of the alarm, and controls the deletion of all alarms of a certain age, regardless of whether they are noted (closed).	
alarmMax	100000	Maximum number of records to keep. After this value is reached, smsDbCleanup.sh delete records.	
alarmNotedAge	3	Controls the deletion of noted (closed) alarms.	
auditAge	7	Delete records older than this number of days.	
commit	100	Number of statistic records to delete before committing the deletions.	
statsAge	30	Delete records older than this number of days.	
unknownMax	5000	Maximum number of alarms to keep in table smf_alarm_unknown. After this value is reached, new additions cause oldest to be deleted from the table.	

Failure

If the process is not running, old data will not be purged from the database. The database may reach maximum size, and inserts may fail.

Output

The **smsDbCleanup.sh** writes error messages to the system messages file, and also writes additional output to /IN/service_packages/SMS/tmp/smsDbCleanup.sh.log.

smsLogCleaner

Purpose

smsLogCleaner archives the following types of log files:

- Convergent Charging Controller process log files (/IN/service_packages/Product/tmp/Process.log)
- System log files (syslog)

For more information, see System Administrator's Guide.

Startup

This task is run in the crontab for smf_oper. By default, it runs at 30 minutes past each hour. It is run via the shell script:

/IN/service_packages/SMS/bin/smsLogCleanerStartup.sh

Parameters

smsLogCleaner supports the following command-line options:

Usage:

```
smsLogCleaner -c configuration_file -d days -s storage_file [-h]
The available parameters are:
```

Parameter	Default	Description
-c configuration_file	logjob.conf	The name of the configuration file.
-d days	7	How often to clean the archive, in days.
-s storage_file	storage.txt	The name of the storage file.
-h		Provides help information.

At installation time, the cronjob is configured to execute by default with the following command-line parameters:

-c /IN/service_packages/SMS/etc/logjob.conf

```
-s /IN/service_packages/SMS/tmp/sms_storage.txt
```

-d 7

An operator may change these values, subject to disk storage availability and site-specific archiving policies.

Failure

If the process is not running, log files in the following directory will accumulate in size and age beyond the expected values.

/IN/service_packages/SMS/tmp

Output

The smsLogCleaner run by smf_oper writes error messages to the system messages file, and also writes additional output to /IN/service_packages/SMS/tmp/smsLogCleaner.log.

logjob.conf

The logjob.conf configuration file has the following format:

log file age hrs size size arcdir dir logonce zip size

The available parameters are:

Parameter	Description
log <i>file</i>	The full directory path and name of the file to be cleaned. You can include the '*' wildcard in the file name if required.
	<pre>Example: log /IN/service_packages/SMS/tmp/smsNamingServer.log</pre>
	Tip: Most processes and tools document where their output is written to in their Output topic.
age hrs	Sets the minimum age, in hours, for the log file before it is cleaned. You must set either this parameter or the size parameter. If both parameters are set, the log file is cleaned when either condition is met.
	Example: age 100
size <i>size</i>	Sets the minimum size for the log file before it is cleaned. You must set either this parameter or the age parameter. If both parameters are set, the log file is cleaned when either condition is met.
	Examples: size 60K, or size 60M
arcdir <i>dir</i>	The directory for storing the old log file. If this parameter is not specified, the log file is deleted.
	<pre>Example: arcdir /IN/service_packages/SMS/tmp/archive</pre>
logonce	Include this parameter if you want to keep only one archived version of the log file.
zip size	Automatically compress log files that exceed the specified size.
	Example: zip 100M

smsMergeDaemon

Purpose

The smsMergeDaemon monitors the connections between the SMS and SLCs via a heartbeat. The smsMergeDaemon will initiate a startMerge to resyncronise the SMS and SLCs where:

- the infMaster on the disconnected SLC reports that it has received updates that would have normally gone to the SMS or it has an updateLoader or updateRequester pointing to it, and
- the heartbeat to the SMS and SLC have been stable for a period.

For more information about the startMerge process, see *startMerge* (on page 231).

Startup

This task is started by entry sms9 in the inittab, via the shell script:

/IN/service_packages/SMS/bin/smsMergeDaemonStartup.sh

Note: smsMergeDaemon is not used in a clustered install.

Parameters

The smsMergeDaemon accepts the following command line arguments.

Usage:

smsMergeDaemon -nodeid The available parameters are:

Parameter	Default	Description
-nodeid	1000	The node number of the smsMergeDaemon.

The rest of the configuration details are taken from *replication.def* (on page 31). Relevant parameters include:

- HB PERIOD
- LONG TIMEOUT
- MAX_ROUNDTRIP 3
- MAX_CONNECTION_TIME 10000000
- MERGE_INTERVAL 600
- REP_PATH "/IN/service_packages/SMS/etc/replication.config"
- SMS_PORT 7
- TICK_TIME 1000

Failure

If the smsMergeDaemon's connection to the smsMaster is lost, it will exit.

Output

The smsMergeDaemon.sh writes error messages to the system messages file, and also writes additional output to /IN/service_packages/SMS/tmp/smsMergeDaemon.log.

smsMaster

Purpose

The smsMaster is the central correlation point for the replication system.

smsMaster:

- Sends notifications of updates to remote updateLoaders to be loaded into secondary databases.
- Accepts update requests from remote systems that wish to change the master database (including the smsStatsDaemon, RequesterIF and smsAlarmDaemon).
- Correlates full resynchronization with remote databases, and communicates with inferior masters which can assume some smsMaster functions in the case of a platform or network failure.

Startup

This task is started by entry sms7 in the inittab, through the shell script:

/IN/service_packages/SMS/bin/smsMasterStartup.sh

Configuration

The smsMaster supports the following command-line options:

Usage:

```
smsMaster -maxpending int
The available parameters are:
```

-maxpending	
Syntax:	-maxpending int
Description:	The size of pending request queue.
Туре:	Integer
Optionality:	Optional (default used if not set).
Allowed:	
Default:	10000
Notes:	
Example:	

Failure

. .

Remote replication nodes such as update loaders, updated requesters, inferior masters will generate alarms indicating connection failure to the smsMaster.

Output

The smsMaster writes error messages to the system messages file, and also writes additional output to /IN/service_packages/SMS/tmp/smsMaster.log.

smsNamingServer

Introduction

The smsNamingServer listens for IORs being exported from CORBA processes, and stores them in the database in the IORS table owned by Oracle user SMF. It also serves requests to read IOR strings from the database.

This functionality is required to support processes that wish to store/retrieve IOR strings, but which do not have Oracle access to the SMF database instance, for security or licensing reasons.

Startup

In an unclustered installation, this task is started by entry sms2 in the inittab, through the shell script:

/IN/service_packages/SMS/bin/smsNamingServerStartup.sh In a clustered installation this task is started by the cluster software, through the shell script:

/IN/service packages/SMS/bin/smsNamingServerCluster.sh

Parameters

The smsNamingServer supports the following command-line options:

Usage:

smsNamingServer [-u usr/pwd] [-p port]
The available parameters are:

-u

Syntax:	-u <i>usr/pwd</i>
Description:	The Oracle user and password pair.
Туре:	String

Chapter 5

Optionality: Allowed:	Optional (default used if not set)
Default:	1
Notes:	
Example:	-u /
-р	
Syntax:	-p port
Description:	The port number on which to listen for requests
Туре:	Integer
Optionality:	Optional (default used if not set)
Allowed:	
Default:	7362
Notes:	
Example:	-p 7362

Failure

If the smsNamingServer fails, then processes attempting to access the specified port will not be able to access the service, and should report an error indicating this.

Output

The smsNamingServer writes error messages to the system messages file, and also writes additional output to /IN/service_packages/SMS/tmp/smsNamingServer.log.

smsReportsDaemon

Purpose

smsReportsDaemon is a CORBA server process that generates reports on demand.

When the SMS user interface (UI) Reports function requests a report, smsReportsDaemon:

- Returns the report output filename
- Writes the report output to a specified directory on the SMS

The SMS UI Reports function then displays the report. For more information about the SMS Reports function, see *Service Management System User's Guide*.

Startup

In an unclustered installation, smsReportsDaemon is started by entry sms3 in the inittab, via the shell script:

/IN/service_packages/SMS/bin/smsReportsDaemonStartup.sh

In a clustered installation, smsReportsDaemon is started by the cluster software, via the shell script:

/IN/service_packages/SMS/bin/smsReportsDaemonCluster.sh

Parameters

smsReportsDaemon supports the following command-line options.

Usage:

```
smsReportsDaemon [-h host] [-p port] [-i dir] [-o dir] [-f dir] [-u user/password]
[-t host] [-s port] [-z timezone] [-m num]
```

The available parameters are:

Parameter	Default	Description
-h <i>host</i>	Value returned by gethostname	smsNamingServer hostname.
		Allowed value type: ASCII String
-p <i>port</i>	7362	smsNamingServer port number.
		Allowed value type: Number
-i <i>dir</i>	/IN/service_package	Report scripts/binaries input directory.
	s/SMS/input	Allowed value type: ASCII String
-o dir	/IN/service_package	Generated report output directory.
	s/SMS/output	Allowed value type: ASCII String
-f dir	/IN/service_package s/SMS/input	The setTZ.sql file directory. By default, the file is located in /IN/service packages/SMS/input.
-u user/password	•	Oracle SMF database username and password.
		Allowed value type: ASCII String
-t host	Default determined by CORBA	CORBA transport layer hostname.
-s port	Default determined by CORBA	CORBA transport layer port number. This parameter is ignored if the CorbaServices section is present in the eserv.config configuration file. For more information, see <i>Configuring Connections for CORBA Services</i> (on page 76).
-z timezone		Timezone in which the smsReportsDaemon SQL queries are run generating the report output.
-m <i>num</i>	2	Maximum number of concurrent reports per node.

Failure

If smsReportsDaemon fails, you will not be able to generate reports.

Output

smsReportsDaemon writes error messages to the system messages file, and writes additional output to /IN/service_packages/SMS/tmp/smsReportsDaemon.log.

smsReportsDaemon writes report output to subdirectories of the specified output directory (by default, /IN/service_packages/SMS/output). The subdirectory depends on the application and category defined for the report:

/IN/service_packages/SMS/output/Application/Category

The report output filename is in the format:

 $\verb"YYMMDDHHmmss.9" random characters.txt"$

Interactive reports

smsReportsDaemon generates on-demand reports.

Reports are defined through SQL commands, shell scripts, or compiled executable programs. Additional reports can be created and made available for on-demand and scheduled generation as a post-installation manual function. For more information, see *Reports* (on page 233).

At startup, smsReportsDaemon publishes its IOR string via the smsNamingServer. If not specified, the IP port number on which the CORBA service is provided will be determined by the CORBA framework. In most installations, a firewall is used to protect the SMS host, and hence the CORBA service port must be fixed. Use the -s parameter for this purpose.

smsReportScheduler

Purpose

The smsReportScheduler monitors the database table SMF_REPORT_SCHEDULE for entries inserted via the SMS Java screens.

smsReportScheduler sleeps until the next report is due to be executed. The output of the report is optionally copied to a specified directory, spooled to a specified printer, or sent to a specified email address. For more information about how to schedule reports which will be performed periodically and how to configure the report destination, see the *Service Management System User's Guide*.

Startup

In an unclustered installation, this task is started by entry sms4 in the inittab, via the shell script:

```
/IN/service_packages/SMS/bin/smsReportSchedulerStartup.sh
In a clustered installation this task is started by the cluster software, via the shell script:
```

/IN/service_packages/SMS/bin/smsReportSchedulerCluster.sh

Parameters

The smsReportScheduler supports the following command-line options:

Usage:

```
smsReportScheduler [-i dir] [-o dir] [-u usr/pwd] [-v] [-z timezone]
The available parameters are:
```

-i dir

Optionality:

Allowed:

Syntax:	-i dir
Description:	The input directory for report generation scripts/binaries dir.
Туре:	String
Optionality:	Optional (default used if not set)
Allowed:	
Default:	/IN/service_packages/SMS/input
Notes:	
Example:	
-o dir	
Syntax:	-o dir
Description:	The output directory for report generation.
Type:	String

Optional (default used if not set)

Default:	/IN/service_packages/SMS/output
Notes:	Report may provide a default output directory which overrides smsReportDaemon's default.

Example:

-u usr/pwd

Syntax:	-u usr/pwd
Description:	The userid and password for oracle login string.
Туре:	String
Optionality:	Optional (default used if not set)
Allowed:	
Default:	/
Notes:	
Example:	

-v

Syntax:	-v	
Description:	What lev	el of information to output.
Туре:	Boolean	
Optionality:	Optional	(default used if not set)
Allowed:	set	Print additional information.
	not set	Only print the standard level of information.
Default:	not set	
Notes:		

Example:

-z timezone

Syntax:	-z timezone
Description:	The timezone in which to schedule the report.
Туре:	String
Optionality:	Optional (default used if not set)
Allowed:	Java supported timezone
Default:	GMT
Notes:	For a full list of Java supported timezones see ACS Technical
	Guide - Appendix TimeZones.
Example:	-z "EST"

Failure

In the case of failure, the scheduled report will not appear at the specified destination, or may contain incorrect or missing output.

Output

The smsReportScheduler writes error messages to the system messages file, and also writes additional output to /IN/service_packages/SMS/tmp/smsReportScheduler.log.

Unix utilities

Unix Binary Required	Description	Location Expected
mailto	E-mail agent used by report generation component to send emails.	/usr/bin/mailto
sendmail (or equivalent delivery agent)	E-mail delivery agent.	daemon started at boot time.
lpr	Printing utility.	/usr/ucb/lpr

The table below lists the Unix utilities required for scheduling.

Note: E-mail sending/receiving/delivery agent requires all local e-mail user names to be under 13 characters. For local e-mail user names longer than 13 characters, mailto and sendmail will not function properly.

smsReportCleanupStartup.sh

Purpose

The Reports cleaner looks for output from ad-hoc and scheduled reports generated by the smsReportsDaemon and the smsReportScheduler.

It deletes files that are older than a specified age.

Startup

This task is run in the crontab for smf_oper. By default it runs at 2:00 am system time. It is scheduled as the following script:

/IN/service packages/SMS/bin/smsReportsCleanerStartup.sh

Parameters

The command inside the script contains a command line parameter specifying the cleanup age of report output files. By default this is seven days. Report output files older than this age are deleted.

An operator may change this value, subject to disk storage availability and site-specific archiving policies.

Failure

If the process is not running, reports files in the following directory will accumulate in size and age beyond the expected values.

/IN/service_packages/SMS/output

Output

The smsReportsCleaner run by smf_oper writes error messages to the system messages file, and also writes additional output to:

/IN/service_packages/SMS/tmp/smsReportsCleanerStartup.sh.log

smsStatsDaemon

Description

smsStatsDaemon can be run as a background process on an SMS, SLC, and also on other IPs such as Voucher and Wallet Servers.

For more information about smsStatsDaemon, see the discussion about the *smsStatsDaemon* (on page 184) background process on the SLC node.

smsStatisticsWriter

Purpose

The smsStatisticsWriter is responsible for collecting statistical data provided by the smsStatDaemons and writing it to files, either for standalone statistics, or for groups of statistics associated with an event.

smsStatisticsWriter structure

Here is an example structure of the smsStatisticsWriter.config file.

```
smsStatisticsWriter = {
   tempDir = "/IN/service packages/SMS/tmp/smsStatisticsWriter"
   outDir = "/IN/service packages/SMS/logs/smsStatisticsWriter"
   outDirType = 'FLAT'
   outDirExpectedFiles = 65536
   outDirBucketSize = 10
   outFileName = "smsStatisticsWriter"
   maxFileSize = 100
   maxFileOpenTime = 3600
   statsDaemonRestartDelay = 10
   statsDaemonStartupTime = 5
   scanInterval = 100000
   replicationAllowance = 60
   endOfEventTolerance = 5
   resetInterval = {
       days = 1
       hours = 0
       minutes = 0
       seconds = 0
    }
   Events = [
        {
            eventName = "EventGood"
            resetAllEventStatisticsOnStartup = true
            eventResetBaseTime = "20110511130000"
            resetInterval = {
               days = 0
               hours = 0
               minutes = 4
               seconds = 0
        }
       eventStartDateTime = "20100728000000"
       eventEndDateTime = "20101231000000"
       eventWritePeriod = 30
       Statistics = [
            {
                applicationName = "TELEVOTING"
```

```
statisticName = "Stat1"
        }
        {
            applicationName ="TELEVOTING"
            statisticName = Statn
        }
        etc
    ]
    {
        eventName = "Event2"
        parameters for event...
    }
    {
        eventName = "Eventn"
        parameters for event...
    }
]
Statistics = [
    {
        StatisticName = "Stat2"
       resetStatisticOnStartup = false
        statWritePeriod = 0
        statResetBaseTime = "20110511130000"
        resetInterval = {
           days = 0
           hours = 0
           minutes = 5
           seconds = 0
        }
    }
    {
        statisticName = "StatN"
        parameter for statistic...
    }
    Etc
1
```

smsStatisticsWriter parameters

The smsStatisticsWriter section accepts the following parameters.

tempDir

Description:

Syntax:	tempDir = "dir"
Description:	The temporary directory for writing intermediate statistics files to.
Туре:	String
Optionality:	Optional (default used if not set).
Allowed:	
Default:	"/IN/service_packages/SMS/tmp/smsStatisticsWriter"
Notes:	
Example:	<pre>tempDir = "/IN/service_packages/SMS/tmp/smsStatisticsWriter"</pre>
outDir	
Syntax:	outDir = "dir"

The base directory for storing completed statistics files.

Туре:	String
Optionality:	Optional (default used if not set).
Allowed:	
Default:	"/IN/service_packages/SMS/logs/smsStatisticsWriter"
Notes:	
Example:	<pre>outDir = "/IN/service_packages/SMS/logs/smsStatisticsWriter"</pre>

outDirType

Syntax:	outDirType: = " <i>type"</i>
Description:	File store type.
Туре:	String
Optionality:	Optional (default used if not set).
Allowed:	HASH or FLAT
Default:	"FLAT"
Notes:	
Example:	outDirType: = "FLAT"

outDirExpectedFiles

Syntax:	<pre>outDirExpectedFiles = num</pre>
Description:	The maximum number of files in outDir when outDirType is HASH.
Туре:	Integer
Optionality:	Optional (default used if not set).
Allowed:	
Default:	65536
Notes:	
Example:	outDirExpectedFiles = 65536

outDirBucketSize

Syntax:	outDirBucketSize = <i>size</i>
Description:	The maximun number of files in any leaf directory when outDirType is HASH.
Туре:	Integer
Optionality:	Optional (default used if not set).
Allowed:	
Default:	10
Notes:	
Example:	outDirBucketSize = 10

outFileName

Syntax:	<pre>outFileName = "name"</pre>
Description:	The base of the statistics file name.
Туре:	String
Optionality:	Optional (default used if not set).
Allowed:	

Default:	"smsStatisticsWriter"
Notes:	
Example:	<pre>outFileName = "smsStatisticsWriter"</pre>

maxFileSize

maxFileSize = <i>size</i>
The maximum size of a statistics file (kilobytes).
Integer
Optional (default used if not set).
100
maxFileSize = 100

maxFileOpenTime

Syntax:	maxFileOpenTime = <i>sec</i>
Description:	The maximum time a statistics file can be kept open (seconds).
Туре:	Integer
Optionality:	Optional (default used if not set).
Allowed:	
Default:	3600
Notes:	
Example:	<pre>maxFileOpenTime = 3600</pre>

statsDaemonRestartDelay

Syntax:	<pre>statsDaemonRestartDelay = sec</pre>
Description:	The length of time to allow updated statistics to be replicated to the SLC nodes before restarting the smsStatsDaemon processes on those nodes. (seconds).
Туре:	Integer
Optionality:	Optional (default used if not set).
Allowed:	
Default:	10
Notes:	
Example:	<pre>statsDaemonRestartDelay = 10</pre>

statsDaemonStartupTime

Syntax:	<pre>statsDaemonStartupTime = <seconds></seconds></pre>
Description:	The length of time (in seconds) to allow for smsStatsDaemon to restart and initialize after startUp request issued.
Туре:	Integer
Optionality:	Optional (default used if not set).
Allowed:	
Default:	5
Notes:	
Example:	statsDaemonStartupTime = 8

scanInterval

Syntax:	scanInterval = <i>msec</i>
Description:	Length of time between scans of the statistics (microseconds).
Туре:	Integer
Optionality:	Optional (default used if not set).
Allowed:	
Default:	100000
Notes:	
Example:	scanInterval = 100000

replicationAllowance

Syntax:	replicationAllowance = <seconds></seconds>
Description:	The time (in seconds) to allow for stats to be replicated to SMS from SLC.
Туре:	Integer
Optionality:	Optional (default used if not set).
Allowed:	
Default:	60
Notes:	For best results this value should be less than any of the reporting periods of statistics included in event configuration.
Example:	replicationAllowance = 40

Events

Event configuration parameters may or may not have default values, where defaults are defined that parameter may be omitted, for all others the parameter is required. There may be multiple events configured.

Each event accepts the following parameters.

```
Events = [
            {
                eventName = "EventGood"
                resetAllEventStatisticsOnStartup = true
                eventResetBaseTime = "20110511130000"
                resetInterval = {
                    days = 0
                    hours = 0
                    minutes = 4
                    seconds = 0
            }
            eventStartDateTime = "20100728000000"
            eventEndDateTime = "20101231000000"
            eventWritePeriod = 30
            Statistics = [
                {
                    applicationName = "TELEVOTING"
                    statisticName = "Stat1"
        }
eventName
                eventName = "name"
Syntax:
Description:
                The name of the event.
```

Туре:	String
Optionality:	Required
Allowed:	
Default:	no default
Notes:	
Example:	<pre>eventName = "eventGood"</pre>

resetAllEventStatisticsOnStartup

Syntax:	<pre>resetAllEventStatisticsOnStartup = true false</pre>
Description:	Reset all statistics defined for the event on start up.
Туре:	Boolean
Optionality:	Optional (default used when omitted)
Allowed:	• true, or
	• false
Default:	true
Notes:	If true, individual statistic resetStatisticOnStatup config is overidden.
Example:	resetAllEventStatisticsOnStartup = false

eventResetBaseTime

Syntax:	eventResetBaseTime = " <date and="" time="">"</date>
Description:	Sets a specific date and time base to calculate resets for the statistics configured for this event.
Туре:	String
Optionality:	Optional (default used if not set).
Allowed:	
Default:	"20100101000000" - (00:00:00 on Jan 1 2010)
Notes:	Date and time format is yyyymmddHHMMSS
	The event resetInterval parameter timing starts from this parameter's date and time.
Example:	<pre>eventResetBaseTime = "20110511130000"</pre>

resetInterval

Syntax: Description: Type: Optionality: Allowed:	<pre>resetInterval = {<days>, <hours>, <minutes>, <seconds>} The interval between periodic resets of all statistics configured for the event. Parameter list Optional (default used if missing)</seconds></minutes></hours></days></pre>
Default: Notes:	Global resetInterval values are used. If non zero, the reset period configured for individual statistics will be overridden.
Example:	<pre>resetInterval = { days = 0 hours = 0 minutes = 4 seconds = 0 }</pre>

eventStartDateTime

Syntax: Description:	<pre>eventStartDateTime = "dateandtime" The event start time.</pre>
Туре:	String
Optionality:	Required
Allowed:	Expected format yyyymmddHHMMSS
Default:	no default
Notes:	Statistics will only be collected for the event between the start and end times.
Example:	eventStartDateTime = "20100728000000"

eventEndDateTime

Syntax: Description:	<pre>eventEndDateTime = "dateandtime" The event end time.</pre>
Туре:	String
Optionality:	Required
Allowed:	Expected format yyyymmddHHMMSS
Default:	no default
Notes:	Statistics will only be collected for the event between the start and end times.
Example:	eventEndDateTime = "20101231000000"

eventWritePeriod

Syntax:	eventWritePeriod = <seconds></seconds>	
Description:	The period (in seconds) between successive writes of statistics data to the report	
Description.	file.	
Туре:	Integer	
Optionality:	Optional (default used if not set).	
Allowed:		
Default:	0	
Notes:	When set to 0 the write period is synchronized to the shortest sample period defined for the statistics included in the event.	
Example:	<pre>eventWritePeriod = 30</pre>	

Event statistics

Each event can collect more than one statistic.

For example the event "EventGood" is a contest where you can vote for three contestants. The statistic for each contestant is collected separately to determine the winner.

Each event statistic accepts the following parameters:

applicationName

Syntax:	applicationName = " <i>name</i> "
Description:	The name of application to which the statistic belongs.
Туре:	String
Optionality:	Required

Allowed:			
Default:	no default		
Notes:			
Example:	applicationName	=	"TELEVOTING"

statisticName

Syntax:	statisticName = "name"
Description:	The name of the statistic.
Туре:	String
Optionality:	Required
Allowed:	
Default:	no default
Notes:	
Example:	<pre>statisticName = "Stat1"</pre>

Statistics

As well as event statistics, smsStatisticsWriter statistics as a whole are collected, irrespective of events.

Each statistic accepts the following parameters:

applicationName

applicationName = "name"
The name of application to which the statistic belongs.
String
Required
no default
applicationName = "TELEVOTING"

statisticName

Syntax:	statisticName = "name"
Description:	The name of the statistic.
Туре:	String
Optionality:	Required
Allowed:	
Default:	no default
Notes:	
Example:	<pre>statisticName = "Stat1"</pre>

resetStatisticOnStartup

Syntax:	<pre>resetStatisticOnStartup = true false</pre>
Description:	Reset statistic on start up.
Туре:	Boolean
Optionality:	Optional (default used if omitted)

Allowed:	• true, or
	• false
Default:	true
Notes:	
Example:	<pre>resetStatisticOnStartup = false</pre>

statWritePeriod

Syntax:	<pre>statWritePeriod = <seconds></seconds></pre>
Description:	The period (seconds) between successive writes of statistics data to the report file.
Туре:	Integer
Optionality:	Optional (default used if not set).
Allowed:	
Default:	0
Notes:	When set to 0 the write period is synchronized to the sample period defined for the statistic.
Example:	<pre>statWritePeriod = 0</pre>

statResetBaseTime

Syntax:	<pre>statResetBaseTime = "<date and="" time="">"</date></pre>
Description:	Sets a specific date and time for setting the statistic to zero.
Туре:	String
Optionality:	Required
Allowed:	
Default:	None
Notes:	Date and time format is yyyymmddHHMMSS
	The statistic resetInterval parameter timing starts from this parameter's date and time.
Example:	statResetBaseTime = "20110511130000"

resetInterval

Syntax:	resetInterval = { <days>,<hours>,<minutes>,<seconds>}</seconds></minutes></hours></days>
Description:	The interval between periodic resets of the statistic.
Туре:	Array of parameters
Optionality:	optional (default used if not set).
Allowed:	
Default:	Global resetInterval values are used.
Notes:	This interval is started from the date and time statResetBaseTime if it is present.
Example:	<pre>resetInterval = { days = 0 hours = 0 minutes = 4 seconds = 0</pre>
	}

Event name file format

The smsStatisticsWriter process creates a file format as detailed below for an event configured in SMS.smsStatisticsWriter.Events.eventName:

_____ _____ "Event Name" "Start Time" "Stop Time" _____ [Automatic statistic reset Time Stamp] Timestamp [Automatic statistic reset Time Stamp] "Statistic ID" Statistics Count [Automatic statistic reset Time Stamp] "Statistic ID" Statistics Count Timestamp [Automatic statistic reset Time Stamp] "Statistic ID" Statistics Count [Automatic statistic reset Time Stamp] "Statistic ID" Statistics Count For example: _____ "Strictly Come Dancing" "20:00:00" "20:30:00" _____ Automatic statistic reset 21-04-2010 20:00:00 21-04-2010 20:00:00 "Contestant A" 0 "Contestant B" 0 "Contestant C" 0 21-04-2010 20:01:00 "Contestant A" 300 "Contestant B" 20 "Contestant C" 50 ... 21-04-2010 20:20:00 "Contestant A" 1200 Automatic statistic reset 21-04-2010 20:20:00 "Contestant B" 0 "Contestant C" 95 ... 21-04-2010 20:30:00 "Contestant A" 15345

"Contestant B" 12789 "Contestant C" 120

Statistics file format

The smsStatisticsWriter process creates a file format as detailed below for a statistic configured in SMS.smsStatisticsWriter.Statistics:

_____ "Application ID" "Statistic ID" _____ [Automatic statistic reset Timestamp] Statistics Count Timestamp [Automatic statistic reset Timestamp] Timestamp Statistics Count [Automatic statistic reset *Timestamp*] Timestamp Statistics Count For example: _____ "TPSA" "Service A" _____ 01-01-2010 00:00:00 0 01-01-2010 00:00:30 2 . . . Automatic statistic reset 31-01-2010 12:00:00 31-01-2010 12:00:00 0 31-01-2010 12:00:30 3 . . .

31-01-2010 23:00:00 4000

smsStatsThreshold

Purpose

The smsStatsThreshold polls the database for updates to the SMF_STATISTICS table. It compares the values against threshold rules defined in the SMF_STATISTICS_RULE table, and raises an alarm if the threshold is exceeded. It inserts the alarm into the SMF_ALARM_MESSAGE table in the SMF database.

For more information about how to define new statistics threshold rules, see the *Service Management System User's Guide*. New threshold rules are automatically recognised by the program.

Startup

In an unclustered installation, this task is started by entry sms6 in the inittab, via the shell script:

/IN/service_packages/SMS/bin/smsStatsThresholdStartup.sh
In a clustered installation, this task is started by the cluster software, via the shell script:

/IN/service_packages/SMS/bin/smsStatsThresholdCluster.sh

Parameters

The smsStatsThreshold supports the following command-line options:

Usage:

```
smsStatsThreshold -u <usr/pwd> -s <secs>
The available parameters are:
```

-u <usr/pwd>

Syntax:	-u <usr pwd=""></usr>
Description:	The Oracle user and password pair.
Туре:	String
Optionality:	Optional (default used if not set).
Allowed:	
Default:	/
Notes:	
Example:	

-s <secs>

Syntax:	-s <secs></secs>
Description:	The number of seconds to sleep between database checks.
Туре:	Integer
Optionality:	Optional (default used if not set).
Allowed:	
Default:	60
Notes:	
Example:	

Failure

Alarm messages derived from statistics values will not appear in the alarm system.

Output

The smsStatsThreshold writes error messages to the system messages file, and also writes additional output to /IN/service_packages/SMS/tmp/smsStatsThreshold.log.

smsSendConfig.sh

Purpose

smsSendConfig.sh resides on the source node (for example, an SMS) and performs the following functions:

- Archives current master XML file
- Stores audit information
- Sets link to current archived file
- Converts XML format to derived eserv.config using the script cmnConfigXmlConvert.sh
- Sends derived eserv.config file to target node using scp.

About database connections

smsSendConfig.sh connects to the database on a local or a remote SMS node by using the user credentials set in the following environment variables in **smsConfigVariables.sh**:

- SMP_DB_USER_NAME
- SMP_DB_PASSWORD
- SMP_DB_CONNECT_STRING

For connections to a:

- Local database, specify the username and password by setting the SMP_DB_USER_NAME and SMP_DB_PASSWORD variables. You can set only the user name in the SMP_DB_USER_NAME variable, if required.
- Remote database, specify the username and password by setting the SMP_DB_USER_NAME and SMP_DB_PASSWORD variables, and specify the SID of the remote database in the SMP_DB_CONNECT_STRING variable. You can set the SMP_DB_USER_NAME and the SMP_DB_CONNECT_STRING variables only, if required.
- Local or a remote database by using the Oracle wallet secure external password store, specify only the TNS connection string in the SMP_DB_CONNECT_STRING variable, where the connection string is the alias defined for the username and password credentials in the external password store. This alias can be either a TNS name or a service name from tnsnames.ora. The SMP_DB_CONNECT_STRING variable has the following format: "\@connect_string".

Note: If you do not set any of these variables, **smsSendConfig.sh** connects to the database by using the default value of "/".

Startup

smsSendConfig.sh is started by smsConfigDaemon (using the -m parameter). It is driven by the system and is not intended to be changed by the user.

Configuration

For more information on the parameters used by smsSendConfig.sh, see *smsConfigDaemonScript Configuration* (on page 130).

Failure

If smsSendConfig.sh fails, deployment process for the eserv.config on the source node will fail. Consequently, no updates will be sent to the target node. Appropriate alarm messages are generated.

Output

The smsSendConfig.sh and its sub-scripts write error messages to the system messages file, and also write additional output to /IN/service_packages/SMS/tmp/smsConfigDaemonMaster.log.

smsTaskAgent

Purpose

smsTaskAgent is a CORBA server that performs various utility functions as requested by the SMS Java screens, including:

- Create replication.config file
- Change Oracle password for Convergent Charging Controller screens user
- Perform data consistency checks with remote nodes
- Change the customer care PIN for a subscriber

CORBA service port

At startup, smsTaskAgent publishes its IOR string via the smsNamingServer. If the IP port number is not specified, the port number on which the CORBA service is provided will be determined by the CORBA framework. The CORBA service port must be fixed because a firewall is used to protect the SMS host. Use the -s parameter to provide the port number on the CORBA transport.

Startup

In an unclustered installation, this task is started by entry sms8 in the inittab, via the shell script:

```
/IN/service_packages/SMS/bin/smsTaskAgentStartup.sh
```

In a clustered installation, this task is started by the cluster software, via the shell script:

```
/IN/service_packages/SMS/bin/smsTaskAgentCluster.sh
```

If there is no local SMF database and smsTaskAgent connects to the Oracle database only on a remote SMS, remove or comment out the following lines and all the lines in between:

```
"echo "`date` - Waiting for DB SMF""
```

```
"echo "`date` - DB SMF is ready""
```

smsTaskAgent configuration in eserv.config

You configure smsTaskAgent in the SMS, smsTaskAgent section of the eserv.config configuration file:

```
SMS = {
    smsTaskAgent = {
        defaultOracleProfile = "password_profile"
    }
}
```

defaultOracleProfile

Syntax:	<pre>defaultOracleProfile = "password_profile"</pre>
Description:	The name of the Oracle profile to allocate to new users created through the User Management screen in the SMS UI. The SMS uses the verification function for the allocated Oracle profile to check that the entered password is acceptable. The SMS also applies the verification function whenever the system administrator attempts to change a user's password through the SMS UI.
	If the entered password is rejected, the SMS displays an error message. You specify the error message text in the passwordPolicyMessage Java application property. See <i>jnlp.sms.passwordPolicyMessage</i> (on page 100) for more information.
Туре:	String
Optionality:	Optional (default used if not set)
Allowed:	The name of an existing Oracle profile (created by using the CREATE PROFILE command).
Default:	Use the standard Oracle profile called DEFAULT.
Notes:	For information about creating Oracle profiles and using the CREATE PROFILE command, see the Oracle Database online documentation.
Example:	defaultOracleProfile = "password profile"

Command line parameters

smsTaskAgent supports the following command line options:

Usage:

```
smsTaskAgent [-c] [-i ior_host] [-p ior_port] [-u usr/pwd] [-t trans_host] [-s
trans_port] [-w secs]
```

The available parameters are:

_	\sim
	\sim

Syntax:	-c
Description:	Use secure shell and secure copy (ssh and scp).
Туре:	Boolean
Optionality:	Optional (default used if not set)
Allowed:	
Default:	Use standard connection and copy
Notes:	
Example:	

-i ior host

Syntax:	-i ior_host		
Description:	The IOR listener host to connection to		
Туре:	String		
Optionality:	Optional (default used if not set)		
Allowed:			
Default:	localhost		
Notes:			
Example:	-i produsms		

-p port			
Syntax:	-p port		
Description:	The port on the IOR listener host to connect to.		
Туре:	Integer		
Optionality:	Optional (default used if not set)		
Allowed:			
Default:	5556		
Notes:			
Example:	-p 13579		
-u usr/pwd			
Syntax:	-u usr/pwdl/@connect_string		
Description:	The username and password, or the connection string, to use for connections to the Oracle database on a local or a remote SMS node.		
Туре:	String		
Optionality:	Optional (default used if not set)		
Allowed:	For connections to a:		
	 Local or remote database by using user credentials, specify the user and password, or specify '/' for passwordless connections 		
	 Local or a remote database by using the Oracle wallet secure external password store, specify only the TNS connection string where the TNS connection string is the alias defined for the username and password credentials in the external password store. This alias can be either a TNS name or a service name from tnsnames.ora. 		
Default:	/		
Notes:	When smsTaskAgent invokes repConfigWrite in order to create the replication.config file, the specified user credentials are passed down to reConfigWrite as the -user argument.		
Example:	-u SMF/SMF		

-t trans_host

Syntax:	-t trans_host
Description:	The CORBA transport host to connect to.
Туре:	String
Optionality:	Optional (default used if not set)
Allowed:	
Default:	NULL
Notes:	
Example:	

-s trans_port

Syntax:	-s <i>trans_port</i>
Description:	The port on the CORBA transport host to connect to.
Туре:	Integer
Optionality:	Optional (default used if not set)
Allowed:	

166 Service Management System Technical Guide

Default: Notes: Example:	0
-w secs	
Syntax:	-w secs
Description:	The number of seconds smsTaskAgent waits for a consistency check update before timing out and abandoning a consistency check.
Туре:	Integer
Optionality:	Optional (default used if not set)
Allowed:	
Default:	20
Notes:	
Example:	-w 120

Failure - smsTaskAgent

If smsTaskAgent fails, any further smsTaskAgent based tasks that you perform are not processed and an error message is displayed. Oracle recommends that you call Oracle support when you see the following error messages:

Error Message	Description
Failed to hash subscriber PIN in subscribers CORBA interface.	The encryption call used by smsTaskAgent failed.
Cannot retrieve IOR for the subscribers service from the IORS database table.	smsTaskAgent did not add an entry to the IORS table because the subscriber's service is not registered.

Output

smsTaskAgent writes error messages to the system messages file, and also writes additional output to /IN/service_packages/SMS/tmp/smsTaskAgent.log.

smsTrigDaemon

Purpose

smsTrigDaemon manages control plan execution requests. It runs on the SMS platform.

smsTrigDaemon accepts control plan execution requests from either a remote PI client or the Java management screens. It forwards requests to ACS through the xmlTcapInterface on the SLC platform. An indication of whether or not the requests were successful passes back from the ACS to the initiating client.

Startup

In an unclustered installation, this task is started by entry sm11 in the inittab, via the shell script:

/IN/service_packages/SMS/bin/smsTrigDaemonStartup.sh

In a clustered environment this task is started by the binary startSmsTrigDaemon which is located in:

```
/opt/ESERVSmsTrigDaemon/util/startSmsTrigDaemon
```

Note: startSmsTrigDaemon must be manually run as root in a clustered environment. smsTrigDaemon is then added as a cluster resource.

Location

This binary is located on the SMS node.

Parameters

smsTrigDaemon is configured by the following parameters from the triggering section of eserv.config:

Usage:

```
triggering = {
   oracleLogin = "userName/password"
   useORB = true|false
   listenPort = portNumber
   slcBusyTimeout = seconds
   useFIFO = true|false
    extraFIFO = [
        "1stPath"
        "2ndPath"
            ...
            ...
            ...
        "nthPath"
    1
    scps = [
        "1stHostAddress:1stPortNumber"
        "2ndHostAddress:2ndPortNumber"
                ...
                ...
                ...
        "nthHostAddress:nthPortNumber"
    ]
}
```

Available parameters are:

oracleLogin

Syntax:	oracleLogin = " <i>usr/pwd</i> "
Description:	The Oracle user name and password that smsTrigDaemon uses when connecting to the database.
Туре:	String
Optionality:	Required
Allowed:	
Default:	/
Notes:	
Example:	
useORB	
Syntax:	useORB = <true false></true false>
Description:	Whether smsTrigDaemon accepts incoming CORBA requests.
Туре:	Boolean
Optionality:	Required

Allowed:	true	smsTrigDaemon accepts incoming CORBA requests.
	false	smsTrigDaemon refuses incoming CORBA requests.
Default: Notes:	false	

Example:

listenPort

Syntax:	listenPort = portNumber
Description:	The IP port on which smsTrigDaemon listens for CORBA requests.
Туре:	Integer
Optionality:	Required
Allowed:	0 - 65535
Default:	0
Notes:	If set to 0, any available port is used.
Example:	

slcBusyTimeout

Syntax:	<pre>slcBusyTimeout = seconds</pre>		
Description:	The numb out.	er of seconds before connections to the SLC or VWS nodes will time	
Туре:	Integer		
Optionality: Allowed:	Optional (default used if not set)		
Default:	10		
Notes:			
Example:	slcBusyTimeout = 15		
useFIFO			
Syntax:	useFIFO = true false		
Description:	Whether smsTrigDaemon accepts FIFO transport layer incoming requests.		
Туре:	Boolean		
Optionality:	Required		
Allowed:	true	smsTrigDaemon accepts FIFO transport layer incoming requests	
	false	smsTrigDaemon refuses FIFO transport layer incoming requests	
Default:	false		
Notes:	If set to false, the extraFIFO (on page 170) parameter array is ignored.		
	If set to false and <i>useORB</i> (on page 168) is also set to false, smsTrigDaemon will do nothing.		
Example:			

Chapter 5

extraFIFO				
Syntax:	extraFIFO = ["dir"			
	···· 1			
Description:	The paths that smsTrigDaemon should create for extra FIFOs.			
Туре:	Parameter array			
Optionality:	Optional			
Allowed:				
Default:	Empty set			
Notes:	If useFIFO (on page 169) is set to false, this parameter array is ignored.			
Example:	<pre>extraFIFO = ["/IN/service_packages/SMS/tmp/trg-req-3005" "/IN/service_packages/SMS/tmp/trg-req-3006"]</pre>			
scps				
Syntax:	<pre>scps = ["ip:port"</pre>			
]			
Description:	The Internet Protocol (IP) address and port number for each SLC to which the smsTrigDaemon connects. If you specify an IP version 6 (IPv6) address and port combination, then you must enclose the IPv6 address in square brackets [], see example for details.			
Туре:	Array			
Optionality:	The scps parameter array is optional.			
	In any row of the array, the : port part is optional.			
Allowed:	<i>ip</i> Any IP address or symbolic host name. <i>port</i> 0 - 65535			
Default:	Empty set			
Notes:	An example of an Internet protocol address is 192.0.2.1.			
	An example of an IPv6 address is $2001:db8:n:n:n:n:n:n$ where <i>n</i> is a group of 4 hexadecimal digits. The industry standard for omitting zeros is also allowed.			
	An example of an address in symbolic name format is primary_smc .			
Example:	<pre>scps = ["198.51.100.1" "192.0.2.1:4000" "[2001:db8:0000:1050:0005:0600:300c:326b]:3004" "[2001:db8:0:0:0:500:300a:326f]:1234:SMF" "[2001:db8:1c3]:1234:SMF" "2001:db8:1050:0:0:300a:0300:126c" "primary_smc" "secondary_smc:3006"]</pre>			

Failure

If smsTrigDaemon fails, then interaction with the BPL requests from the Java screens and the PI will fail.

Output

smsTrigDaemon writes error messages to the system messages file, and also writes additional output to /IN/service_packages/SMS/tmp/smsTrigDaemon.log.

Control plan execution requests

After receiving a control plan execution request the smsTrigDaemon follows a three-stage process:

Stage	Description	
1	 smsTrigDaemon attempts to connect to one of the SLCs in the following way. If a connection to a SLC is established and not in use, that connection is used. smsTrigDaemon maintains a list of currently-open connections. If a connection to a SLC is not established, smsTrigDaemon attempts to open one. SLCs are identified by the scps configuration parameter. smsTrigDaemon polls this list until it finds an available connection. If the connection fails, the next SLC in the list is tried. 	
2	 smsTrigDaemon connects to the SLC using either port 3072 or another port specified by the scps parameter. If a connection to a SLC is established and not in use, that connection is used. smsTrigDaemon maintains a list of currently-open connections. If a connection to an SLC is not established, smsTrigDaemon attempts to open one. SLCs are identified by the scps configuration parameter. smsTrigDaemon polls this list until it finds an available connection. If the connection fails, the next SLC in the list is tried. 	
3	<pre>smsTrigDaemon sends an XML message via an HTTP "POST / HTTP/1.1" request. The syntax of the message is: <control-plan-exec> <control-plan-exec> <control-plan><name control="" of="" plan=""></name></control-plan> <service-handle><service handle=""></service></service-handle> <cgpn><calling party=""></calling></cgpn> <cdpn><called party=""></called></cdpn> <ext id="400"><host></host></ext> <ext id="400"><host></host></ext> <ext id="401"><user></user> </ext></control-plan-exec></control-plan-exec></pre>	
Data consistency check		

A race condition can occur after the **Save & Execute** button has been pressed in a Java management screen. The race condition exists between the SMS's replication system and execution on the SLCs of

an smsTrigDaemon request. To avoid this possibility, a data consistency check is carried out on the current subscriber before proceeding with the request.

Because it is not possible to know in advance which SLC will be selected by smsTrigDaemon, a data consistency check is performed on all replicated SLCs. A decision to carry on with the request is only made after the check has been completed.

The following steps describe the consistency check process and the criteria used to determine whether the execution will be allowed.

Stage	Description			
1	The Java management screen sends to smsTaskAgent a request for a consistency check on the current subscriber.			
2	The Java management screen waits until a check report is received from smsTaskAgent. The report is in the form of an HTML file.			
3	 The Java management screen extracts relevant information from the report, including: The number of nodes checked. 			
	 The number of nodes that replied to the check request. The number of nodes that reported inconsistent data. 			
4	 The consistency check: succeeds, if: at least one node replied without error, and no node reported inconsistent data. fails, if: no nodes replied without error, or one or more nodes reported inconsistent data. 			

- 5 If the check succeeds, the request proceeds.
- 6 If the request fails, steps 1 through 4 are repeated. After three fails, the request is cancelled and the user informed in an SMS message dialogue box.
Background Processes on the SLC

Overview

Introduction

This chapter provides a description of the programs or executables used by the System as background processes on an SLC.

Executables are located in the /IN/service packages/SMS/bin directory.

Some executables have accompanying scripts that run the executables after performing certain cleanup functions. All scripts should be located in the same directory as the executable.

Important: It is a prerequisite for managing these core service functions that the operator is familiar with the basics of Unix process scheduling and management. Specifically, the following Unix commands:

- init (and inittab)
- cron (and crontab)
- ps
- kill

In this chapter

This chapter contains the following topics.

smsApplyConfig.sh	173
cmnPushFiles	174
infMaster	179
smsAlarmDaemon	
smsLogCleaner	
smsStatsDaemon	
updateLoader	

smsApplyConfig.sh

Purpose

smsApplyConfig.sh resides on the target node, example SLC.

It performs the following functions:

- Backup of the live eserv.config currently used in production,
- Merges changes from derived file into live eserv.config using smsConfigSurgeon.
- Signals changes using smsSignalConfigChanges.sh.

If a SIGHUP is required, smsSignalConfigChanges.sh will in turn call smsSendSighup.sh (which will run with root permissions).

Startup

smsApplyConfig.sh is started by smsConfigDaemon (without the -m parameter). It is driven by the system and is not intended to be changed by the user.

Configuration

For more information on the parameters used by smsApplyConfig.sh, see *smsConfigDaemonScript Configuration* (on page 130).

Failure

If smsApplyConfig.sh fails, the deployment process for eserv.config on the target node will fail. Appropriate alarm messages will be generated.

Output

The smsApplyConfig.sh and its sub-scripts write error messages to the system messages file, and also write additional output to /IN/service_packages/SMS/tmp/smsConfigDaemonClient.log.

cmnPushFiles

Purpose

cmnPushFiles transfers files to specific directories on the SMS from SLCs and VWSs. The files transferred include:

- EDRs
- PIN logs

Note: Other Oracle applications also use their own instances of this process.

Startup

This task is started by entry scp1 in the inittab, using the shell script:

```
/IN/service_packages/SMS/bin/cmnPushFilesStartup.sh
```

Configuration

cmnPushFiles accepts the following command-line options:

Usage:

```
cmnPushFiles -d <dir> [-o <dir> [-a <days>]] [-f <dir>] [-F] [-P <pref>] [-S <sufx>]
-h <host> [-r <pref>] [-p <port>] [-s <secs>] [-R <secs>] [-M <secs>] [-C <secs>] [-
t <bits>] [-T] [-x] [-e] [-w <secs>]
```

-d <dir>

Syntax:	-d <dir></dir>
Description:	The destination directory for files on remote machine.
Туре:	String
Optionality:	Optional (default used if not set).
Allowed:	Path must start with '/' or the -r option must also be used.
	Cannot be the same as <i>-f <dir></dir></i> (on page 177).
Default:	

Notes:	An example of a destination directory is the directory on a SLC where
	cmnPushFiles looks for the files to be sent to the SMS.

Example:

-P <dir>

Syntax:	-P <dir></dir>
Description:	The file prefix to match on.
Туре:	String
Optionality:	
Allowed:	
Default:	
Notes:	
Example:	

-S <sufx>

-S <sufx></sufx>
The file suffix.
String

-r <pref>

Syntax:	-r <pref></pref>
Description:	The remote directory prefix.
Туре:	String
Optionality:	Optional (default used if not set).
Allowed:	
Default:	null
Notes:	Required if -d <dir> (on page 174) is a relative directory.</dir>
Example:	

-h <host>

Syntax:	-h <host></host>
Description:	The hostname of the remote machine.
Туре:	String
Optionality:	Required
Allowed:	
Default:	null
Notes:	If set, a hostname must be specified.
Example:	

Chapter 6

-p <port>

-p <port></port>
The port number on the remote machine on which cmnReceiveFiles will listen for receiving files.
Integer
Optional (default used if not set).
port Port to connect to.
-1 Use stdin and stdout.
2027

-s <secs>

Syntax:	-s <secs></secs>
Description:	The number of seconds for the sleep period.
Туре:	Integer
Optionality:	Optional (default used if not set).
Allowed:	
Default:	15
Notes:	
Example:	

-t <bits>

Syntax:	-t <bits></bits>
Description:	The number of bits per second to start throttling at.
Туре:	Integer
Optionality:	Optional (default used if not set).
Allowed:	
Default:	0 (no throttling)
Notes:	
Example:	

-w <secs>

Syntax:	-w <secs></secs>
Description:	The number of seconds to wait for success.
Туре:	Integer
Optionality:	Optional (default used if not set).
Allowed:	
Default:	30
Notes:	
Example:	
-x	
Syntax:	-x
Description:	Whether to use hostname-prefixing on remote filenames.

Туре:	Boolean
Optionality:	Optional (default used if not set).
Allowed:	set Don't use prefixing.
	(false)
	not set Use prefixing.
Default:	true
Notes:	
Example:	
-o <dir></dir>	
Syntax:	-o <dir></dir>
Description:	The directory to transfer sent files to.
Туре:	String
Optionality:	Optional (default used if not set).
Allowed:	directory The directory to store transferred files in.
	null Delete the transferred files, do not store them.
Default:	null (file deleted)
Notes:	
Example:	
-f <dir></dir>	
Syntax:	-f <dir></dir>
Description:	The retry directory.
Type:	String
Optionality:	Optional (default used if not set).
Allowed:	Cannot be the same as $-d < dir > (on page 174).$
Default:	null (no retry directory)
Notes:	
Example:	
-F	
- Suntax:	$naraMater = \langle \rangle$
Description:	Use fuser to not move files in use
Type:	Boolean
Optionality:	Optional (default used if not set)
Allowed:	set (true) Use fuser.
	not set (false) Don't use fuser.
Default:	false
Notes:	
Example:	
-a <davs></davs>	
Syntax:	-a <days></days>
Description:	The number of days old a transferred file can be before it is deleted.

Chapter 6

Туре:	Integer	
Optionality:	Optional (default used if not set).	
Allowed:	positive integer	
	-1 never delete files.	
Default:	-1	
Notes:	This parameter only relevant when -o <dir> (on page 177) option is specified.</dir>	
Example:		

-e

Syntax:	-e	
Description:	Which mo	de to run in.
Туре:	Boolean	
Optionality:	Optional (default used if not set).
Allowed:	set (false)	Run in non-daemon mode. Execute file transfer only once, then exit.
	not set (true)	Run in daemon mode.
Default:	not set	
Notes:		
Example:		

-R <secs>

Syntax:	-R <secs></secs>
Description:	The number of seconds before Initial retry period starts.
Туре:	Integer
Optionality:	Optional (default used if not set).
Allowed:	
Default:	15
Notes:	
Example:	

-M <secs>

Syntax:	-M <secs></secs>
Description:	The maximum number of seconds for the retry period to continue.
Туре:	Integer
Optionality:	Optional (default used if not set).
Allowed:	
Default:	900
Notes:	
Example:	
-C <secs></secs>	

Syntax:	-C <secs></secs>
Description:	The number of seconds for the cleanup period.
Туре:	Integer

Optionality:	Optional (default used if not set).
Allowed: Default: Notes: Example:	1800
-т	
Syntax:	-T
Description:	Whether or not to move recursively.
Туре:	Boolean
Optionality:	Optional (default used if not set).
Allowed:	set Tree move: recursive into subdirectories not set
Default:	true
Notes:	
Example:	

Example

This text shows an example of the command line options for cmnPushFiles.

```
cmnPushFiles -d /IN/service_packages/SMS/cdr/closed -f
/IN/service_packages/SMS/cdr/retry -r /IN/service_packages/SMS/cdr/received -h
prodsmp1.telcoexample.com -s 10 -p 2028 -S cdr -w 20
```

Failure

If cmnPushFiles fails, EDRs will accumulate in:

/IN/service_packages/SMS/cdr/current/

cmnPushFiles will send error messages to the syslog and the cmnPushFiles log.

Output

The cmnPushFiles writes error messages to the system messages file, and also writes additional output to this default location:

/IN/service_packages/SMS/tmp/cmnPushFiles.log

infMaster

Purpose

The infMaster provides resilience for replication in case the smsMaster fails. For more information, see Inferior Master.

The infMaster is only used in the unclustered configuration.

Note: The infMaster does not replicate Alarms or Statistics.

Startup

This task is started by entry scp2 in the inittab, via the shell script:

```
/IN/service_packages/SMS/bin/infMasterStartup.sh
```

Parameters

The infMaster supports the following command-line options:

Usage:

infMaster [-maxpending <number>]
The available parameters are:

Parameter	Default	Description
-maxpending <number></number>	10000	This sets the maximum number of pending updates which will be queued in the infMaster's memory.

Failure

If the infMaster fails, no functionality will be affected unless the infMaster would normally be required to operate as the Superior Master (that is, the smsMaster and all other infMasters with higher node numbers were unavailable). In this case, replication will not work.

The infMaster will send error messages to syslog and infMaster.log.

Output

The infMaster writes error messages to the system messages file, and also writes additional output to /IN/service_packages/SMS/tmp/infMaster.log.

smsAlarmDaemon

Purpose

The smsAlarmDaemon runs on all alarm-managed nodes in the SMS system, including the SMS nodes. The role of the smsAlarmDaemon is to gather alarms from the following sources:

- System error log (/var/adm/syslog.log or /var/log/syslog)
- Oracle Standard DB error log
- Sigtran SUA logs (/IN/service_packages/SLEE/stats) [If installed]

On the SMSs, the resultant error messages are written directly into the SMF_ALARM_MESSAGE table in the SMF. When run on other nodes, replication is used to update the SMF_ALARM_MESSAGE table.

Startup

This task is started by entry scp4 in the inittab, via the shell script:

/IN/service_packages/SMS/bin/smsAlarmDaemonScpStartup.sh

Configuration

smsAlarmDaemon accepts the following command-line arguments.

Usage:

```
smsAlarmDaemon [-1 seconds] [-h seconds] [-n number] [-m number] [-p] [-d] [-a path]
[-r node] [-u user/pass] [-f] [-i] [-g] [-c number] [-t seconds]
```

Parameter	Default	Description
-a path	Null	Propagate alarms from the specified Oracle alert log to the database.
		By default, smsAlarmDaemon does not propagate alarms from the Oracle alert log.
-c number	1	Commit Rate. The number of inserts before committing to the database.
-d	Sort messages	Disable sorting of messages in the buffer by severity.
		Specifically, messages are kept in the buffer and subsequently written into the SMF database, in the same sequence in which they are received.
-f	No filtering	Filtering. Delete duplicate alarms and increase the alarm count.
-g	Uses local time	GMT timezone. Use GMT instead of local time.
-h seconds	60	Heartbeat message. Will be forced to be greater or equal to time period (seconds).
-i	Use fuzzy matching	Filtering type. Use exact matching (rather than fuzzy matching). Indicates that duplicate matches should be performed on text only (that is, excluding digits).
		Note: Only valid when used in conjunction with -f.
-l seconds	2	Filter Period. Duration between linked-list checks (in seconds).
-n <i>number</i>	5	Filter Number. The number of alarm messages allowed within the time period.
		Allowed values: Integers
-m number	1000	Maximum number of alarm messages to buffer.
		Allowed values: Integers 1-1000000
-p	Do not drop messages	Drop low-priority messages when the buffer is full. Specifically, when -m number messages have been received but it is not yet time to write the buffer contents to the SMS database, low priority messages in the buffer are dropped in favor of higher-priority messages that may be received on its input stream.
-r node	Direct to the Oracle DB	Replication node. Specify the replication requester node.
-t seconds	1	Commit interval. The maximum interval between database commits (in seconds).
-u user/pass	/	Use the supplied Oracle user/password pair.

The available parameters are:

Usage example

Here is an example of using smsAlarmDaemon:

sms Alarm
Daemon -l 5 -h 30 -n 10 -m 2000 -p -d -a /volB/home/saich -r 750 -
u smf/smf -f -i -g -c 2 -t 2

- Filter Period (-I) = 5 seconds
- Heart beat (-h) = Yes every 30 seconds
- Filter Number (-n) = 10 each period
- Max number(-m) = 2000 records
- Drop low priority messages (-p) = true
- Sort messages by severity (-d) = false
- Oracle Alert Log location (-a) = /volB/home/saich
- Rep node (-r) = 750
- Oracle User (-u) = smf/smf
- Filtering (-f) = Multiple alarms combined
- Filtering type (-i) = Exact match
- GMT timezone (-g) = Yes
- Commit Rate (-c) = every 2 number of inserts
- Commit Interval (-t) = every 2 seconds if 2 records not reached

Failure

The smsAlarmDaemon on each alarm-managed node in the installation will by default generate a health-check alarm once per minute. These health check alarms will be relayed in the same fashion as all other alarms.

If these health check alarms are not received at the target destination, then the smsAlarmDaemon may have failed, and should be investigated.

Output

The smsAlarmDaemon writes error messages to the system messages file, and also writes additional output to /IN/service_packages/SMS/tmp/smsAlarmDaemonScp.log.

smsLogCleaner

Purpose

smsLogCleaner archives the following types of log files:

- Convergent Charging Controller process log files (/IN/service_packages/Product/tmp/Process.log)
- System log files (syslog)

For more information, see System Administrator's Guide.

Startup

This task is run in the crontab for smf_oper. By default, it runs at 30 minutes past each hour. It is run via the shell script:

/IN/service_packages/SMS/bin/smsLogCleanerStartup.sh

Parameters

smsLogCleaner supports the following command-line options:

Usage:

```
smsLogCleaner -c configuration_file -d days -s storage_file [-h]
```

The available parameters are:

Parameter	Default	Description
-c configuration_file	logjob.conf	The name of the configuration file.
-d days	7	How often to clean the archive (in days).
-s storage_file	storage.txt	The name of the storage file.
-h		Provides help information.

At installation, the cronjob is configured to execute by default with the following command-line parameters:

-c /IN/service_packages/SMS/etc/logjob.conf

```
-s /IN/service_packages/SMS/tmp/sms_storage.txt
```

-d 7

An operator can change these values, subject to disk storage availability and site-specific archiving policies.

Failure

If the process is not running, log files in the following directory will accumulate in size and age beyond the expected values.

/IN/service_packages/SMS/tmp

Output

The smsLogCleaner run by smf_oper writes error messages to the system messages file, and also writes additional output to /IN/service_packages/SMS/tmp/smsLogCleaner.log.

logjob.conf

The logjob.conf configuration file has the following format:

```
log <file> age <hrs> size <size> arcdir <dir> logonce
The available parameters are:
```

Parameter	Description		
log <file></file>	The full directory path and name of the file to be cleaned. You can include the '*' wildcard in the file name if required.		
	Example: log /IN/service_packages/SMS/tmp/smsNamingServer.log		
	Tip: Most processes and tools document where their output is written to in their Output topic.		
age <hrs></hrs>	Sets the minimum age in hours for the log file before it will be cleaned. You must set either this parameter or the size parameter. If both parameters are set, then the log file is cleaned if either condition is met.		
	Example: age 100		
size <size></size>	Sets the minimum size for the logfile before it will be cleaned. You must set either this parameter or the age parameter. If both parameters are set, then the log file is cleaned if either condition is met.		
	Examples: size 60K, or size 60M		

Parameter	Description	
arcdir <dir></dir>	The directory to use to store the old log file. If this parameter is not specified, then the log file is deleted.	
	Example: arcdir /IN/service_packages/SMS/tmp/archive	
logonce	Only specify this parameter if you just want to keep one archived version of the log file.	

smsStatsDaemon

Purpose

The smsStatsDaemon program is the key component in the statistics process. The statistics process gathers and updates all statistics values through a single consistent mechanism over the network.

The smsStatsDaemon can optionally dynamically load extension libraries at runtime to provide extra functionality. This functionality includes node uptime, process uptime, and database row counts.

Startup

This task is started by entry scp3 in the inittab, via the shell script:

/IN/service_packages/SMS/bin/smsStatsDaemonStartup.sh

smsStatsDaemon configuration

The stats daemon can run in one of two modes:

- standard mode or
- legacy mode.

The standard mode uses command line options to configure the smsStatsDaemon, and uses the SMF_STATISTICS_DEFN table in the SMF database to define the statistics which should be collected.

The legacy mode is configured using a combination of command line parameters and a configuration file. The configuration file defines the statistics which should be collected.

Depending on which mode the smsStatsDaemon is running in, a different set of parameters will be used.

Parameters

The command line parameters for the smsStatsDaemon are:

Usage:

```
smsStatsDaemon [-e <secs>] [-u <usr/pwd>] [-f <dir/file>] [-v] [-r <node>] [-d
<size>] [-h <ratio>] [-w] [-F] [-m <size>] [-i] [-S] [-T] [-C <n>]
Or for largery form:
```

```
Or for legacy form:
```

```
smsStatsDaemon [-c <dir>] [-a <dir>] [-t <secs>] [-s <Kb>] [-e <secs>] [-f
<dir/file>] [-v] [-d <size>] [-h <ratio>] [-w] [-F] [-m <size>] [-i] [-S] [-T] [-C
<n>]
```

The available parameters are:

-e secs

Syntax: -e secs

Description: The minimum number of seconds between logging statistic counts of zero.

Туре:	Integer
Optionality:	Optional (default used if not set).
Allowed:	
Default:	0
Notes:	This only applies to collection mode 1 (always report).
Example:	

-f dir/file

Allowed:

Syntax:	-f dir/file		
Description:	The stats configuration file (full path, includes file name).		
Туре:	String		
Optionality:	Optional (stats file not used if not set).		
Allowed:			
Default:	null		
Notes:			
Example:			
-v			
Syntax:	-v		
Description:	Use verbose mode (provide more information while processing).		
Туре:	Boolean		
Optionality:	Optional (default used if not set).		
Allowed:			
Default:	Do not use verbose mode.		
Notes:	Usually used for debuggin set-up problems.		
Example:			
-d rows			
Syntax:	-d rows		
Description:	The number of rows for dynamic stats table.		
Туре:	Integer		
Optionality:	Optional (default used if not set).		
Allowed:	>1		
Default:	500		
Notes:	The dynamic stats table is the shared memory hash table used to contain the statistics information. The size of this table varies with the number of statistic being collected.		
Example:			
-h ratio			
Syntax:	-h ratio		
Description:	The ratio of the size of the hash index to the dynamic stats table.		
Туре:	Integer		
Optionality:	Optional (default used if not set).		

Default:	2		
Notes:	The dynamic stats table is the shared memory hash table used to contain the statistics information. The size of this table varies with the number of statistics being collected.		
Example:			
-F			
Syntax:	– F		
Description:	Only do SMS-specific statistic collection.		
Туре:	Boolean		
Optionality:	Optional (default used if not set).		
Allowed:			
Default:	Collect all statistics.		
Notes:	Only set when smsStatsDaemon is running on an SMS.		
	The SMF_STATISTICS_EXTN table specifies for each extension statistic whether it is an SMS stat or not. Also the shared memory hash table specifies whether each statistic is an SMS stat. Hence the -F option can do only SMS stats or all stats.		
	Examples: Uptime of <i>smsMaster</i> (on page 144) is an SMS stat, uptime of <i>updateLoader</i> (on page 192) is not an SMS stat.		
Example:			
-m size			
Syntax:	-m size		
Description:	The size of the details column in the dynamic stats table.		
Туре:	Integer		
Optionality:	Optional (default used if not set).		
Allowed:			
Default:	80		
Notes:	The dynamic stats table is the shared memory hash table used to contain the statistics information.		
Example:			
-i			
Syntax:	-i		
Description:	Silently ignore mount points that are longer than the <i>-m size</i> (on page 186) limit.		
Туре:	Boolean		
Optionality:	Optional (not used if not set).		
Allowed:			
Default:			
Notes:			
Example:			
-S			
Syntax:	-S		
Description:	Silently drop statistics where the details field is longer than -m size (on page 186).		
Туре:	Boolean		

Optionality: Allowed: Default: Notes: Example:	Optional (not used if not set).		
-т			
Syntax:	-т		
Description: Type:	Truncate the detail field for statistics that exceed <i>-m size</i> (on page 186). Boolean		
Optionality: Allowed: Default: Notes:	Optional (not used if not set).		
Example:			
-C n			
MERSyntax:	-C n		
Description:	Sets the global configuration variable mergeCpuStats to the value of "n". This defines whether individual CPU statistics will be output or whether CPU statistics will be summed. For summed statistics, the number of CPUs is also output.		
Туре:	Integer		
Optionality:	Optional (default used if not set).		
Allowed:	n = 0 output individual CPU statistics		
	n = 1 sum CPU statistics		
	Any other value of n will be ignored, and default behavior will be used		
Default:	0 - output individual CPU statistics		
Notes:	If MERGECPUSTATS config file entry is set, it overrides the default behaviour. If the command line switch (-C) is set, then it will override the MERGECPUSTATS config file entry.		
Example:	-C 1		

Parameters for standard mode

This parameters are used with the general parameters when smsStatsDaemon is running in standard mode.

Note: These parameters cannot be used with the Parameters for legacy mode (on page 188).

-u usr/pwd

Syntax:	-u usr/pwd
Description:	The userid and password to use to log into the SMF database.
Туре:	String
Optionality:	Optional (default used if not set).
Allowed:	
Default:	/
Notes:	

Chapter 6

Example:

-r node

Syntax:	-r node		
Description:	The replication node number smsStatsDaemon should use.		
Туре:	Integer		
Optionality:	Optional (default used if not set).		
Allowed:			
Default:	-1		
Notes:			
Example:			
-w			
Syntax:	-w		
Description:	Do Row Count statistic collection.		
Туре:	Boolean		
Optionality:	Optional (not used if not set).		
Allowed:			
Default:			
Notes:	Provides statistics of the number of rows in selected database tables as defined in the SMF_STATISTICS_EXTN table.		
	This type of statistic should only be collected on the primary SMS node.		
Evampla			

Example:

Parameters for legacy mode

These parameters can be used if smsStatsDaemon is being used in legacy mode.

Note: These parameters cannot be used with the Parameters for standard mode (on page 187).

-c dir	
Syntax:	-c dir
Description:	Current statistics file directory.
Туре:	String
Optionality:	Optional (default used if not set).
Allowed:	
Default:	/tmp
Notes:	
Example:	
-a dir	
Syntax:	-d dir
Description:	Archived statistics file directory.
Туре:	String
Optionality:	Optional (default used if not set).
Allowed:	
Default:	/tmp

188 Service Management System Technical Guide

Notes:

Example:

Syntax:	-t secs		
Description:	The maximum number of seconds a statistics file can be oper		
Туре:	Integer		
Optionality:	Optional (default used if not set).		
Allowed:			
Default:	1800		
Notes:			
Example:			
-s Kb			
Syntax:	-s Kb		
Description:	The maximum number of Kb a stats file can reach.		
Туре:	Integer		
Optionality:	Optional (default used if not set).		
Allowed:			
Default:	10		
Notes:			
Example:			

Failure

If the smsStatsDaemon fails, statistics on that SLC will not be processed. When the smsStatsDaemon is restarted the statistics will be processed.

Output

The smsStatsDaemon writes error messages to the system messages file, and also writes additional output to /IN/service_packages/SMS/tmp/smsStatsDaemon.log.

Measurement IDs - standard mode

Measurement IDs for the statistics which should be collected are loaded from the SMF_STATISTICS_DEFN and SMF_STATISTICS_EXTN tables in the Oracle Standard DB instance given by ORACLE_SID. Setting the TWO_TASK variable allows a machine without a database instance running access a database on a remote machine. One application of this may be to allow monitoring of a remote disaster recovery machine.

Statistics shared memory

The shared memory area contains an index to the statistics measurements it contains. Each measurement has an accumulator for up to 16 SLPI instances. The single SLPI process is the only process to write to that buffer. The per-SLPI statistics counters are never reset, the smsStatsDaemon treats them as read-only.

smsStatsDaemon parameters

Name	Туре	Description
CURRENTDIR	256 characters	Where active statistics files are stored.
ARCHIVEDIR	256 characters	Where archived statistics files are stored.
OPENTIME	unsigned long	The maximum length of time a statistics file should remain open. The range of values is 1-1440 minutes.
MAXSIZE	unsigned long	The maximum size (in Kbytes) a statistics file is allowed to reach.
		Note: This is only checked after a recording period, so a file may be larger than this size.
NOTIFY	256 characters	Space separated e-mail accounts to notify when the statistics file is rotated. This value is optional. If it does not exist, no e-mail is sent.
MID	Measurement description record	Specifies a measurement to be made available.
MERGECPUSTATS	1 character	If this config file entry is set, it overrides the default behaviour.
		config file entry and the default entry.

This table gives the type and valid values of the parameters.

Legacy mode configuration - config file

To provide full backwards support for sites using the SMS version 1 style configuration, the use of a configuration file is optional. A configuration file will be searched for according to the following rules:

- If the -f <*config_file_loc*> parameter is specified, the config file is used. An error occurs if the specified file does not exist.
- If the -f parameter is omitted, then a search is made for a file "etc/smsStatsDaemon.cfg" or "../etc/smsStatsDaemon.cfg". If one of these files exists, then the file is used. Otherwise the smsStatsDaemon will start with the default configuration as described above.

The configuration file provides:

- Parameters (for example, max open file size, archive file directory), and
- Measurement IDs (specified using "MID=..." entries).

Note: Any configuration specified in the command line will override the details in the configuration file. The database configuration is NOT used.

Syntax for the stats_config file

For legacy sites, the syntax of the stats_config file is given.

This is an example of a stats_config file:

```
# Log file locations (trailing / is optional)
CURRENTDIR=/IN/service_packages/SMS/statistics/current
ARCHIVEDIR=/IN/service_packages/SMS/statistics/archive
# Max open time is 10 min (1-1440)
OPENTIME=10
# Max file size is 128 kb (unlimited)
```

MAXSIZE=128 MID=npNotFound,NP,Portability request with no target,3600,Category NF MID=npTimeOut,NP,Exceeded regulated time-out on connect,300,No comment MID=vpnManagement,VPN,Calls to management hotline,3600,Non-charged MID=vpnSchedule,VPN,Calls activating scheduled routing,3600,No comment

Where:

#	indicates a comment. The comment character needs to start at the beginning of a line. The entire line is then ignored (up to 255 characters).		
CURRENTDIR	indicates the working directory of the daemon. This is where a temporary statistics file is stored until the file size of open time exceeds the configured value.		
ARCHIVEDIR	the location a closed statistics file is moved to.		
OPENTIME	indicates how long a statistics file can stay active (that is, how long can the daemon keep on writing statistics into a file) in minutes.		
MAXSIZE	The maximum allowable size of a statistics file in Kilobytes.		
	Note: If a statistics file becomes overloaded half way through a dump, the entire record will still be written.		
MID	The measurements to retrieve. Refer to the subsection on Measurements		

Measurements

Measurements are specified in the configuration file using one MID command for each measurement to be defined.

MID commands are comma separated value names, that must be in the order below:

- ID
- APPLICATION
- DESCRIPTION
- PERIOD
- COMMENT
- EXTN
- KEYWORD
- DETAIL
- LIB_NAME
- FUNCTION_NAME

Examples:

An example MID line without the extension fields might be:

MID=vpnManagement,VPN,Calls to management hotline,3600,Non-charged An example MID line with the extension fields would be:

 $\texttt{MID}=\texttt{STATSDAEMON}, \texttt{SCP}_\texttt{SYSTEM}, \texttt{Uptime}$ for <code>smsStatsDaemon</code> process, 60, <code>smsStatsDaemon</code> process uptime in

minutes, EXTN, PROCESS_UPTIME, smsStatsDaemon, libsmsextrastats.so, getProcessUptime

This table describes the measurement parameters.

Name	Туре	Description
APPLICATION	20 characters	The application ID. This may be up to 20 characters for clarity, however the first three characters must be unique.

Name	Туре	Description
COMMENT	256 characters	Textual comment relating to the statistic.
DESCRIPTION	256 characters	The textual description of the measurement.
DETAIL	80 characters	Extra data required to measure stat, i.e. process name for process uptime stats. Can be NULL (empty string).
EXTN	5 characters	The keyword 'EXTN' indicating that this mid line has the extra fields.
FUNCTION_NA ME	50 characters	Function within the library (specified at LIB_NAME) to call in order to measure stat.e.g. getNodeUptime.
ID	20 characters	The measurement ID.
KEYWORD	20 characters	May be required by measurement function. e.g. UPTIME_NODE.
LIB_NAME	30 characters	Dynamic library to load to get stat measurement function. e.g. libsmsextrastats.so.
PERIOD	unsigned long	The time in seconds between each recording in the output file of this statistic. Value range is 10-31536000 (1yr).

After a change is made to the Measurement IDs, the smsStatsDaemonRep process needs to be notified via a SIGHUP. This can be performed manually, or via the smsStatsDaemonRepReload.sh script provided as part of the installation.

Updating smsStatsDaemon measurements

After a change is made to the Measurement IDs, either via the database, or via modifying "MID=..." entries in the stats_config file, the smsStatsDaemon process needs to be notified via a SIGHUP. This can be performed manually, or via the smsStatsDaemonReload.sh script provided as part of the installation.

updateLoader

Purpose

The updateLoader accepts updates from the smsMaster and makes the requested changes to the database it is configured to update. More than one updateLoader may run on each SLC. For more information about updateLoaders and replication, see *What is Replication?* (on page 19)

If the SCP data becomes out of sync with the data in the SMF, a resync can be done to ensure the SCP has the correct information. It should not be necessary to do a manual resync. The system does automatic resyncs as necessary.

There are three cases where the system will resync:

Case	Description
A Node is Out of History	Where a node is isolated SMS will hold a queue of updates for the node. In the replication.def file there is a max pending variable that gives the maximum number of updates that will be held in this queue for each SLC. If this limit is exceeded (the node is out of history) SMS will drop all the entries and force a resync of the node when it comes back on line.
New Node Added	When a new node is added to the system a replication config file will be sent to the node. This forces a resync.
Replication Changed	If the replication config file for a node is changed then a resync will be forced.

Startup

This task is started by entry scp5 in the inittab, via the shell script:

/IN/service_packages/SMS/bin/updateLoaderStartup.sh

Parameters

The updateLoader supports the following command-line options:

Usage:

updateLoader [-nodeid node_number] [-resync]
The available parameters are:

Parameter	Default	Description
-nodeid node_number	274	The node number of the updateLoader requesting the resync.
-resync		Causes the updateLoader to re-synchronise with the smsMaster.

Failure

If the updateLoader is not working, updates from the SMS to the SCP database will be unsuccessful. The SLC will continue to run on the last configuration successfully loaded from the SMS.

An error message will be logged to the syslog and the updateLoader log, and may be logged to the smsMaster log.

Output

The updateLoader writes error messages to the system messages file.

Chapter 7 Tools and Utilities

Overview

Introduction

This chapter provides a description of the operational programs or executables used by the system.

Executables are located in the /IN/service packages/SMS/bin directory.

Some executables have accompanying scripts that run the executables after performing certain cleanup functions. All scripts should be located in the same directory as the executable.

In this chapter

This chapter contains the following topics.

cmnConfigSyntaxCheck	
cmnSU	
compareNode	
comparisonServer	
inetCompareServer	
infoDisplayer	
inputBootstrap	
repConfigWrite	
resyncServer	
setupOracleWallet.sh	
smsCompareResyncClient	
smsCompareResyncServer	
smsDumpRepConfig	
smslorDump	219
smsLogTest	
smsManualRequester	
smsProcessCdr	
smsRecordStatistic	
smsStatsQuery	
startMerge	231

cmnConfigSyntaxCheck

Purpose

cmnConfigSyntaxCheck is used to check that the syntax of the eserv.config file is correct.

Configuration

cmnConfigSyntaxCheck accepts the following command line options.

Usage:

cmnConfigSyntaxCheck [-v -d] filename [filename [...]]

The available parameters are:

Parameter	Default	Description
-V	-	Verbose mode. Displays in detail all information that is available.
-d	-	Reads and dumps the named files

Output

cmnConfigSyntaxCheck displays the results of the syntax check on the terminal.

Example: This text shows an example of a report from the cmnConfigSyntaxCheck.

```
$ cmnConfigSyntaxCheck -v filename /ACS/etc/acs.conf
cmn::FileNotFoundException: Opening config file filename
Config file syntax error: ACS/etc/acs.conf:30: Syntax Error
```

cmnSU

Purpose

cmnSU replaces the built in Solaris 11 "su" command for Convergent Charging Controller processes run from initab on Solaris 11 environments only. Run as root, it will provide a login shell to the specified user.

Configuration

cmnSU accepts the following command line options.

Usage:

```
/cmnSU - username [arg...]
The available parameters are:
```

Parameter	Default	Description
-		Provide a login shell. Required.
username		The user to become. Required.
[arg]:		The rest of the arguments to the shell

compareNode

Purpose

This command can be used to initiate a full database comparison of an SCP database with the definitive copy in the SMF database.

This is used to ensure that an SCP database has all its data consistent with the SMF database. Under normal conditions, this should always be the case, but there may be a time (for example, after multiple failures) where the System Administrator wants to check that an SLC database is consistent.

The compareNode tool requests a comparison between the contents of the SMF database and one other node, by invoking comparisonServer. This is a more time-efficient method than a resync. All the entries of all the tables that are defined to be replicated to the specified updateLoader will be compared.

A full report of the comparison is written in the report directory (REPORT DIR) on the SLC machine.

Configuration

compareNode accepts the following command line options.

Usage:

compareNode [-hostname hostname|-master node_num] [-with node_num] [-timeout
seconds]

The available parameters are:

Parameter	Default	Description
-hostname		Sets the hostname of the superior node in the comparison. (Optional. If used, -master must = 0, that is, if -master must be set to off.)
-master	1	Node number of the superior node in the comparison. (Optional, as the default will be used if it is not set. Or it can be turned off by setting to 0, and a hostname specified instead.)
		Note. This can be an initiality.
-with	256	Node number of the updateLoader in the comparison. (Optional, as the default will be used if it is not set.)
-timeout	10	Number of seconds before the connection between the nodes in the comparison is timed out. (Optional, as the default will be used if it is not set.)

Example: This text shows the common usage of compareNode being run on the superior master in a node comparison.

compareNode -with 301

Failure

If compareNode fails, it will send error messages to stdout and syslog.

Output

The compareNode writes error messages to the system messages file, and also writes additional output to /IN/html/SMS/output/node_number/timestamp.html.

comparisonServer

Purpose

comparisonServer is a shell script which starts node comparisons between data in two different nodes. It is started by an SMS in response to a database comparison request.

Configuration

comparisonServer accepts the following command line options.

Usage:

```
comparisonServer node_to_compare address port
```

The available parameters are:

Parameter	Default	Description
node_to_co mpare		
address		
port		

Output

comparisonServer writes error messages to the system messages file, and also writes additional output to IN/service_packages/SMS/tmp/comparisonServer.log.

inetCompareServer

Purpose

inetCompareServer is a shell script which is run by the Replication Check screens. It uses the report configuration information from the Replication Check screen to start a node comparison (which is performed by smsCompareResyncServer). It should not be necessary to run this script by hand.

Output

inetCompareServer writes to syslog and also logs additional information (including raw Replication Check report data) to /IN/service_packages/SMS/tmp/inetCompareServer.log.

Example: This text shows an example of a report from the inetCompareServer.

Copyright (c) 2002, Oracle. Contact Oracle at support@oracle.co.nz

```
Input delivered through standard input. Please consult the SMS administration guide for more information on this software. For command line options, pass '-h' as the only option to this program.
```

Awaiting server control information...

```
Input accepted. Now running server.
Mar 4 05:01:49 smsCompareResyncServer(28781) NOTICE: Beginning comparison for node
301.
COM: Fri Mar 4 05:01:50 2005: Node 301, started processing 186 SMS and 186 SCP
records.
COM: Fri Mar 4 05:01:50 2005: Node 301, table ACS CALL PLAN, started processing 186
SMS and 186 SCP records.
COM: Fri Mar 4 05:01:51 2005: Node 301, table ACS CALL PLAN, group ACS CALL PLAN,
started processing 186 SMS and 186 SCP records.
COM: Fri Mar 4 05:01:52 2005: Node 301, table ACS_CALL PLAN, group ACS CALL PLAN,
finished processing 186 of 186 SMS and 186 of 186 SCP records, 0 discrepancy found
in group.
COM: Fri Mar 4 05:01:52 2005: Node 301, table ACS CALL PLAN, finished processing
186 of 186 SMS and 186 of 186 SCP records, 0 discrepancy found in table.
COM: Fri Mar 4 05:01:52 2005: Node 301, finished processing 186 of 186 SMS and 186
SCP of 186 records, 0 discrepancy found in node.
Mar 4 05:01:54 smsCompareResyncServer(28781) NOTICE: Ending comparison for node
301.
Mar 4 05:01:54 smsCompareResyncServer(28781) NOTICE: Comparison was successful for
node 301.
Started writing index HTML file for reports.
```

Finished writing index HTML file for reports.

infoDisplayer

Purpose

infoDisplayer is an executable which can be used to display update request information results.

Configuration

infoDisplayer supports the following command-line options:

Usage:

```
infoDisplayer [-host value] [-master value] [-nodeid value] [-timeout value]
The available parameters are:
```

Parameter	Default	Description
host	localhost	The local host name
master	0	The node number of the smsMaster
nodeID	1	The ID of the node for which the information is to be displayed.
timeout	10	Period after which infoDisplayer will timeout

Output

Examples:

```
bash-2.05$ ./infoDisplayer -nodeid 999 -master 1
initialiseNode: Reading '/IN/service packages/SMS/etc/replication.def'
initialiseNode: heartbeatPeriod 20
initialiseNode: heartbeatTimeout 20
initialiseNode: connectionTimeout 2
initialiseNode: masterPortNum 12343
initialiseNode: queueWarnThresh 5
initialiseNode: queueErrThresh 100000
initialiseNode: queueCritThresh 1000000
initialiseNode: hBTolerance 10.0
initialiseNode: commitIdleTime 0.100000
initialiseNode: commitBusyTime 10.0
initialiseNode: tcpAbortSecs 20
initialiseNode: oracleUserPass '/'
initialiseNode: reportDir '/IN/service packages/SMS/tmp/'
initialiseNode: statusFile '/IN/html/status.html'
initialiseNode: configFilePath '/IN/service packages/SMS/etc/replication.config'
initialiseNode: configFileName 'replication.config'
initialiseNode: node number 999
initialiseNode: node type 5
initialiseNode: s side updates 1
Nov 22 22:05:17 infoDisplayer(6589) NOTICE: Master Controller `./infoDisplayer'
process started (node 999)
```

inputBootstrap

Purpose

The purpose of the inputbootstrap binary is to produce a configuration file to be passed to the smsCompareResyncServer from replication.config. It is started by the comparisonServer or the resyncServer which initiates requests. It can also be executed manually from the command line.

It must be noted that this binary cannot be run with DEBUG when used with the comparisonServer. (Applicable to production environment).

Note: This binary is not intended to be run by the user. Please contact your Oracle support before attempting to do so.

Configuration

inputBootstrap accepts the following command line options.

Usage:

```
inputBootstrap -n node id [-c config filename] [-a ip address] [--hex-address
ip address] [-p port] [-r] [-u usr/pwd] [-e] [-i interval] [-h] [-b]
```

Or long form:

```
inputBootstrap --node-id=node id [--config-file=config filename] [--
address=ip address] [--hex-address ip address] [--port=port] [--preserve-ranges] [--
oracle-user=usr/pwd] [--enhanced-recovery] [--sync-marker-retry-interval=interval [-
-help] [--build-info]
```

The available parameters are:

Parameter	Default	Description
-n node-id	none	The replication node ID for which the configuration file is produced. (Required.) Allowed values: integers, (any signed number of reasonable value, usually in decimal/octal/hex).
-c config- file	/IN/service_packages/ SMS/etc/ replication.config	Name of the replication configuration file to use. (Optional.) Allowed values: string
-a address	from file specified in config-file	The IP address of the node. This cannot be specified if the 'hex-address' option is specified. (Optional.) If specified, this will override all addresses specified in the configuration file. Allowed values: string
hex- address	from file specified in config-file	The IP address of the node as a hex string. This cannot be specified if the '-a' ('address') option is specified. (Optional.) If specified, this will override all addresses specified in the configuration file. Allowed values: string
-p port	none	The port number to connect to at the given node. (Optional.)
		Note: This can only be used when the address is also specified.
		Allowed values: integers, (any signed number of reasonable value, usually in decimal/octal/hex).

Parameter	Default	Description
-r preserve- ranges	false when missing	Leave the data from the configuration file as it is and do not correct the group ranges. This option is implied by the -e option. Allowed values: • 1, on, yes, true • 0, off, no, false
-u oracle- user	smf/smf	The Oracle database connection string (userid/password). (Optional.) Allowed values: string
-e enhanced- recovery	false when missing	Restrict range of rows to resync. If enhanced recovery mode is possible, the smsMaster process sets this option. Allowed values: • 1, on, yes, true • 0, off, no, false
-i sync- marker- retry- interval	30 seconds	The number of seconds between attempts to insert the replication synchronization marker into the database. The marker indicates when a total database re-synchronization has been performed with the smsMaster database. Inserting marker requires inputBootstrap to acquire a lock; failure to acquire the lock could result in updateLoader timing out. (Optional.) Allowed values: integers, (any signed number of reasonable value, usually in decimal/octal/hex).
-h help	false when missing	Shows the help for this binary. Allowed values: • 1, on, yes, true • 0, off, no, false
-b build- info	false when missing	 Prints out program build information of the binary. Allowed values: 1, on, yes, true 0, off, no, false

Note: Long options can be separated from their values by an equal sign ('='), or you can pass the value as the following argument on the command line (for example, '--port 4000' or '--port=4000'). Short options must have their values passed after them on the command line, and in the case of boolean short options, cannot have values (they default to true) (e.g., '-p 4000' or '-f').

Failure

If inputBootstrap fails, it will send error messages to stdout and syslog.

repConfigWrite

Purpose

This command can be used to create a replication.config file. It reads the local database to obtain the replication set-up and writes the file to the directory specified by the output parameter.

Generally this function is performed using the SMS Java screens.

For more information, see:

- replication.config File (on page 38)
- smsDumpRepConfig (on page 218)
- Service Management System User's Guide

Startup

This task is started by clicking **Create Config File** on the **Table Replication** tab of the Node Management screen.

It can also be started on the SMS from the command line.

For more information about the Node Management screen, see SMS User's Guide.

Configuration

repConfigWrite accepts the following command-line options:

Usage:

```
repConfigWrite [-user user/password] [-output file]
The available parameters are:
```

Parameter	Default	Description
-user		Oracle user/password for the SMF.
		Example: smf/smf
-output	./repCofigNNNN N	The output path and filename for the replication.config file. (Optional.)
	(Where NNNNN is a version number that counts for the number of times the file has generated OK.)	Example: /IN/service_packages/SMS/etc/replication.config

Failure

If repConfigWrite fails, replication.config may not have been written correctly. You can check the content of replication.config with smsDumpRepConfig. If there is a problem with replication.config, replication will not work.

Output

The repConfigWrite writes error messages to the system messages file, and also writes additional output to the specified directory and file.

resyncServer

Purpose

resyncServer initiates resyncs between databases by sending a resync request to a node Master process. This overwrites data in an SCP with data from the SMF. The node Master process is usually smsMaster.

This process is started by the smsMaster when a database resync is required and runs only for the duration of the resync. It should not be run manually.

Configuration

resyncServer accepts the following command line options.

Usage:

```
resyncServer inf_node address port enhanced_recovery
The available parameters are:
```

Parameter	Default	Description
inf_node		The node with the database which will be updated.
address		The ip address or hostname of the node which will be updated.
port		The port number on the node which will be updated.
enhanced_r ecovery	off	If set to on, the number of rows in the inferior database will not be counted during the resync. Allowed values:
		on, off.

Output

resyncServer writes error messages to the system messages file, and also writes additional output to /IN/service_packages/SMS/tmp/resyncServer.log.

setupOracleWallet.sh

Purpose

The **setupOracleWallet.sh** script automatically creates the Oracle server wallet on the SMS by performing a sequence of orapki commands. The Oracle server wallet is the single-sign-on wallet that is used when connecting securely to the database and that contains certificate information for identifying the Oracle server. Use this script only if you are using SSL connections to the database.

For information about creating the Oracle wallet automatically by using **setupOracleWallet.sh**, see *Creating the Oracle Wallet Automatically by Using setupOracleWallet.sh* (on page 62).

Important: You will not need to re-run this script after you complete the Oracle server wallet setup.

Information Required by setupOracleWallet.sh

Required Item	Description
Oracle wallet base directory	The base directory for the Oracle wallet. Specify the base directory to use for the Oracle root and Oracle server wallets. On a clustered SMS specify a file system that is cluster-wide to allow all instances to access the same wallet information in a single location. On a non-clustered system the default location for the Oracle wallet base directory is: /u01/app/wallets/oracle/
	On a clustered system the default location for the Oracle wallet base directory is: /global/oracle/app/wallets/oracle/
ISO country code	The local international country (ISO) code for your country. Specify the two-letter code.
Wallet passwords	The password to use for the root CA wallet and the password to use for the server wallet. You will be prompted for the password each time the wallet is accessed.
	Note: Wallet passwords have length and content validity checks applied to them. Generally passwords should have a minimum length of eight characters and contain alphabetic characters combined with numbers and special characters.

The following table lists the information that is required by the **setupOracleWallet.sh** script.

Startup

You run **setupOracleWallet.sh** on the SMS node from the command line. You must be logged in as user *oracle*. If Convergent Charging Controller is installed on a clustered system then you should run **setupOracleWallet.sh** only on the primary SMS node.

Configuration

The setupOracleWallet.sh script is configured by the following command-line parameters.

Usage:

```
setupOracleWallet.sh [-k keysize] [-v validdays] [-s server_certificate] [-t
root_certificate] [-w wallet_base]
```

Parameter	Default	Description
-k keysize	2048	The keysize for certificate keys.
-V validdays	3650	The validity period for certificates in days.
-S server_certif icate	NA	The signed certificate file for the server wallet; for example, ./server/cert.txt.
-t root_certific ate	NA	The root certificate file of the certificate authority (CA); for example, ./root/b64certificate.txt.

Parameter	Default	Description
-w wallet_base	NA	The base directory for the Oracle wallet. If not specified, the script prompts you to enter the location of the Oracle wallet base directory. Choose a directory accessible by user <i>oracle</i> ; for example, on a non-clustered SMS choose:
		/u01/app/wallets/oracle
		On a clustered system choose a directory located in a cluster global file system; for example:
		/global/oracle/app/wallets/oracle
		The script creates the following subdirectories for the root and server wallets under the wallet base location: ./ root and ./ server .

Ways to run setupOracleWallet.sh

When you initially run **setupOracleWallet.sh** you specify whether to use self-signed certificates or certificates signed by a commercial CA. You can optionally specify the -k, -v, and -w command-line parameters; for example:

setupOracleWallet.sh -k keysize -v validdays -w wallet base

If you specify to use self-signed certificates then **setupOracleWallet.sh** creates the self-signed root certificate and exports it to the following file:

./root/b64certificate.txt

Where ./root is a sub-directory of the base directory for the Oracle wallet. You must import this certificate into the Java lib/security/cacerts file on each client PC by using the Java keytool utility. See Adding Trusted Certificates to the Keystore on Client PCs (on page 62) for more information.

If you specify to use a commercial CA to sign your certificates then **setupOracleWallet.sh** creates the certificate request file that you must send to the commercial CA for signing. When the commercial CA returns the signed certificate, you must rerun **setupOracleWallet.sh** to add the trusted CA certificate and the CA-signed certificate to the server wallet. You can optionally specify the -s and -t command-line parameters; for example:

setupOracleWallet.sh -s server_certificate -t root_certificate

smsCompareResyncClient

Purpose

This is a child process of updateLoader. It is called by smsCompareResyncServer and updates the SCP during replication on a clustered install. It also performs database resynchronizations and comparisons on the inferior node during replication checks.

This process is not intended to be be started manually. It is installed on the SLC.

Configuration

smsCompareResyncClient accepts the following command line options.

Usage:

smsCompareResyncClient -n int [-u usr/pwd] [-h] [-b] [-i int] [-p port] [-o seconds]
[-t] [--outside-throttle-sample-rate int] [--inside-throttle-sample-rate int] [-start-threshold int] [--stop-threshold int] [-s dir] [--database-write-buffer-size
int] [--database-read-buffer-size int] [--database-commit-period int] [--max-buffersize int] [--dump-core-instead-of-exception] [--long-raw-size=max_size]
The available parameters are:

The available parameters are:

Parameter	Default	Description	
-n		The node number of the client. (Required.)	
node-id		Allowed values: integer (any signed number of reasonable	
		value, usually in decimal/octal/hex)	
-u	smf/smf	The Oracle database connection string. (Optional.)	
oracle-user		Allowed values: string	
-h	false	Prints this help screen. (Optional.)	
help		Allowed values:	
		 1, on, yes, true 	
		0, off, no, false	
-b	false	Prints out program build information then exits. (Optional.)	
build-info		Allowed values:	
		 1, on, yes, true 	
		• 0, off, no, false	
-i	no process is	Process to inform when the process is in a position to	
inform-parent	informed	resync/compare. For use only when used from the	
		updateLoader process. (Optional.)	
		Allowed values: integers (any signed number of reasonable value, usually in decimal/octal/hex)	
-р		The port to listen on for connections from the server.	
port		(Optional.)	
		Allowed values: integers (any signed number of reasonable value, usually in decimal/octal/hex)	
-0	-1	Timeout (in seconds) on TCP connection. (Optional.)	
tcp-timeout		Allowed values:	
		positive integers	
		• -1 = no timeout	
-t	false	To throttle the client. (Optional.)	
throttle-cpu		Allowed values:	
		 1, on, yes, true 	
		0, off, no, false	
outside-		Sample rate in seconds for throttling while not throttling.	
throttle-		(Required if -t given.)	
samp⊥e-rate		Allowed values: integers (any signed number of reasonable value, usually in decimal/octal/hex)	
inside-		Sample rate in seconds for throttling while throttling. (Required	
throttle-		if -t given.)	
sample-rate		Allowed values: integers (any signed number of reasonable value, usually in decimal/octal/hex)	

Parameter	Default	Description
start- threshold		CPU usage percentage to start throttling at. (Required if -t given.)
		Allowed values: integers (any signed number of reasonable value, usually in decimal/octal/hex)
stop- threshold		CPU usage percentage to end throttling at. (Required if -t given.)
		Allowed values: integers (any signed number of reasonable value, usually in decimal/octal/hex)
-s storage-dir	/tmp	Directory to store required database changes in during a resync. (Optional.)
boolage all		Allowed values: string
database- write-buffer-	10	The size in terms of records of the buffer size for writing to the database. (Optional.)
size		Allowed values: integers (any signed number of reasonable value, usually in decimal/octal/hex)
database- read-buffer-	100	The size in terms of records of the buffer size for reading to the database. (Optional.)
size		Allowed values: integers (any signed number of reasonable value, usually in decimal/octal/hex)
database- commit-period	1000	The number of changes to make to the database before committing them to the database. (Optional.)
		Allowed values: integers (any signed number of reasonable value, usually in decimal/octal/hex)
max-buffer- size	approximately 50Mb	The maximum size (in bytes) to allow messages received from the server to be. This size is reflected in the maximum size of bytes to allocate in memory for such messages. (Optional.)
		Allowed values: integers (any signed number of reasonable value, usually in decimal/octal/hex)
dump-core- instead-of-	false	If set, will force the process to dump a core file (and exit) if any network messages are received bigger than max-buffer-size.
exception		Allowed values:
		• 1, on, yes, true
		• 0, off, no, false
long-raw-size	512K	The maximum size (in bytes) to allocate for a long raw field used in a resync.
		Allowed values: • 512K.

Note: Long options can be separated from their values by an equal sign ('='), or you can pass the value as the following argument on the command line (for example, '--node-id 257' or '--node-id=257'). Short options must have their values passed after them on the command line, and in the case of boolean short options, cannot have values (they default to true) (for example, '-p 4000' or '-t').

smsCompareResyncServer

Purpose

smsCompareResyncServer performs comparisons and resyncs of data in specified tables and replication groups. This enables you to:

- Check that replication is working correctly
- Force updates of data between nodes

Note: This process is usually started by resyncServer.

smsCompareResyncServer is installed on the SMS.

Configuration

smsCompareResyncServer accepts the following command line options.

Usage:

```
smsCompareResyncServer [--dump-core-instead-of-exception] --max-buffer-size=size [--
dont-count-rows] [--inform-master] [--database-read-buffer-size=size] [--cancel-on-
eof] [--use-ip=int] [--report-directory=base_dir] [--tcp-timeout] [--input-
file=config_file_name] [--oracle-user=user] [--build-info] [--help] [--long-raw-
size=max_size]
```

The available parameters are:

Default	Description	
false when missing	If set, will force the process to dump a core file (and exit) if any network messages are received bigger than max-buffer-size. Allowed values:	
	1, on, yes, true0, off, no, false	
approximately 50Mb	The maximum size (in bytes) to allow messages sent to the client to be. This size is reflected in the maximum size of bytes to allocate in memory for such messages.	
	Allowed values: integers (any signed number of reasonable value, usually in decimal/octal/hex).	
false when missing	Do not make a count of the rows in the database. For very large comparisons/resyncs this may give a speed improvement.	
	 Allowed values: 1, on, yes, true 0, off, no, false 	
false when missing	If performing a resync, inform the smsMaster.	
	 Allowed values: 1, on, yes, true 0, off, no, false 	
	Default false when missing approximately 50Mb false when missing false when missing	
Parameter	Default	Description
-------------------------------	---	---
database-read- buffer-size	100	The size (in records) of the buffer size for reading from the database. Must match thedatabase-write- buffer-size specified for the smsCompResyncClient. (Optional.) Allowed values: integers (any signed number of reasonable value, usually in decimal/octal/hex).
		Note: Performance of the compare/resync can be seriously impacted if the number specified is too low, a recommended value for this parameter is 1000+.
cancel-on-eof	false when missing	Tells the server to cancel the resync/compare when EOF on standard input is reached.
		Note: This option is specifically for the inetCompareServer setup.
		Allowed values: • 1, on, ves, true
		• 0, off, no, false
use-ip	none	Forces the server to use the IP address ranked as per the mentioned integer for each client. If there are not enough IP addresses listed, or this option is not specified, it will start from the first IP address, attempting each in turn until connected.
		Allowed values: integers (any signed number of reasonable value, usually in decimal/octal/hex).
		Examples: Ifuse-ip = 2, the server will use the second IP address listed.
-r report-	/IN/html/output/ SMS/	The base directory to create and store final reports in. (Optional.)
directory		Allowed values: string.
-o tcp-timeout	0	Timeout (in seconds) on TCP connection. (Optional.) Zero = no timeout.
		Allowed values: integers (any signed number of reasonable value, usually in decimal/octal/hex).
-i input-file	Input is expected on the standard input stream.	Contains the name of a configuration file as input information for performing a resync/compare. (Optional.) See Input file for details. Allowed values: string
-u	smf/smf	The Oracle database connection string. (Optional.)
oracle-user		Allowed values: string
-b	false when missing	Prints out program build information then exits.
build-info		Allowed values:
		• 1, on, yes, true
		0, off, no, false

Parameter	Default	Description
-h	false when missing	Prints this help screen.
help		Allowed values:
		 1, on, yes, true
		• 0, off, no, false
long-raw-size	512K	The maximum size (in bytes) to allocate for a long raw field used in a resync.
		Allowed values: • 512K.

Notes:

- All options apart from '-h', '-b' and '-i' can be specified in the input configuration. .
- Long options can be separated from their values by an equal sign ('='), or you can pass the value as the following argument on the command line (for example, '--tcp-timeout 100' or '--tcp-timeout=100'). Short options must have their values passed after them on the command line, and in the case of boolean short options, cannot have values (they default to true) (for example, '-o 100' or '-h').

Input file

These are the configuration parameters contained within the input file optionally used by smsCompareResyncServer.

Replication

Syntax:	<pre>Replication = {list_of_replication_parameters}</pre>
Description:	The Replication section lists the required replication parameters.
Туре:	List
Optionality:	Required
Allowed:	
Default:	none
Notes:	
Example:	
perform	
Syntax:	perform = "action"
Description:	The action to be taken by smsCompareResyncServer.
Туре:	Boolean
Optionality:	Required
Allowed:	• resync
	compare
Default:	none

Notes: Example:

perform = "resync"

report-row-number-limit

Syntax: Description:	report-row-number-limit = max_value For a comparison, the maximum number of differences in a group that will be reported.
	For a resync, the maximum number of errors to report of each group synchronized.
Туре:	Integer
Optionality:	Optional (default used if not set).
Allowed:	
Default:	-1
Notes:	Specifying -1 indicates no limit will be imposed.
Example:	report-row-number-limit = 100

produce-final-reports

Syntax:	<pre>produce-final-reports = true false</pre>
Description:	Whether or not to produce final reports.
Туре:	Boolean
Optionality:	Optional (default used if not set).
Allowed:	true, false
Default:	true (reports produced)
Notes:	
Example:	<pre>produce-final-reports = false</pre>

report-directory

Syntax:	report-directory = "dir"
Description:	Specify which directory reports are to be written to.
Tuno	String

Type:	String
Optionality:	Optional (default used if not set)
Allowed:	Any valid directory
Default:	/IN/html/output/SMS
Notes:	
Example:	report-directory = "."

report-after

Syntax:	<pre>report-after = { type = "[comparisons seconds]" count = number }</pre>
Description:	Depending on the type option: Specify how many comparisons the client should process before sending progress report to the server.
	Specify how many seconds the client should allow to elapse before sending a progress report to the server.
Туре:	List

Optionality:	Optional (default used if not set)
Allowed:	
Default:	No progress reports are provided.
Notes:	type and count are both mandatory when report-after is specified.
Example:	<pre>report-after = { count = 10 type = "seconds" }</pre>

stop-on-limit

Syntax:	<pre>stop-on-limit = true false</pre>
Description:	A flag to tell the server to stop a resync or comparison for a replication group after the <i>report-row-number-limit</i> (on page 211) is reached.
Туре:	Boolean
Optionality:	Optional (default used if not set).
Allowed:	true, false
Default:	false (do not stop)
Notes:	
Example:	<pre>stop-on-limit = false</pre>
view	
Syntax:	view = {}
Description:	Describes the nodes, tables and groups for the replication action.
Туре:	List
Optionality:	Required
Allowed:	
Default:	none
Notes:	
Example:	
Node	
Syntax:	Node { id = number
	address = [
	"string", "string",
	}
Description:	A list of nodes for the replication action to work on.
Туре:	Array
Optionality: Allowed:	Required
Default:	none
Notes	
Fyamnle:	

	0
_	u

Syntax:	id = <i>id</i>
Description:	The ID of the node to be used.
Type: Ontionality	Integer
Optionality:	Optional (default used if not set)
Default:	Values from replication node configuration
Notes:	For normal replication resyncronization, these are calculated using the replication node configuration.
	When running from the command line this must match thenode-id of a smsCompareResyncClient.
Example:	id = 301
address	
Syntax:	<pre>address = ["string", "string",]</pre>
Description:	An array of IP addresses and port numbers for this node ID.
Туре:	Array
Optionality:	Required
Allowed:	
Default:	None
Notes:	Internet Protocol version 6 (IPv6) addresses must be enclosed in square brackets []; for example: [2001:db8:n:n:n:n:n] where n is a group of 4 hexadecimal digits. The industry standard for omitting zeros is also allowed when specifying IP addresses.
	Use a comma to separate address entries or specify each entry on a separate line.
Example:	address = [
·	"192.0.2.1:4000" "[2001:db8:0000:1050:0005:0600:300c:326b]:3004" "[2001:db8:0:0:0:500:300a:326f]:1234:SMF"
	[2001:ab8::C3]:1234:SMF"]
tables	
Syntax:	tables = [
	table = " <i>string</i> " [
	groups-cover-table-on-scp = bool
] key-columns = [
	"str", "str",
) other-columns = [
	"str", "str",
	L {
	1
Description:	An array of tables to action for this node ID.
Туре:	Array

Optionality: Allowed:	Required	
Default:	none	
Notes:		
Example:		
table		
Syntax:	table = "str"	
Description:	The name of the table to be used in this operation.	
Туре:	String	
Optionality:	Required	
Allowed:		
Default:	none	
Notes:		
Example:	table = "TEST_REP"	
groups-cover-table-on-scp		
Syntax:	groups-cover-table-on-scp = true false	
Description:		
Туре:	Boolean	
Optionality:	Optional (default used if not set)	
-		

Allowed:	true, false
Default:	false
Notes:	
Example:	groups-cover-table-on-scp = true

key-columns

<pre>key-columns = ["str", "str",]</pre>		
An array of the table column keys which are to be used for this table and this operation.		
Array		
Optional (default used if not set).		
Any valid key column name for this table.		
Pre-configured values.		
Normal replication resyncs are pre-configured and restricted to a maximum of 3 keys. When running from the command line this restriction is lifted.		
These columns must exist on the remote platform.		
<pre>key-columns = ["NUMBER_3"]</pre>		

other-column	S		
Syntax:	other-columns = [
	"str", "str",		
Description:	An array of the non keyed columns which are to be used for this table and this		
Becomption	operation.		
Туре:	Array		
Optionality:	Optional (default used if not set).		
Allowed:	Any valid non keyed column name for this table.		
Default:	Pre-configured values.		
Notes:	For normally replication resyncs these are pre-configured.		
	These columns must exist on the remote platform.		
Example:	other-columns = ["VARCHAR_1","LONG_RAW_2","CHAR_4", "DATE_5"		
]		
Groups			
Svntax:	groups = [
• • • • • • • • • • • • • • • • • • • •	{		
	group = <str> table = <str></str></str>		
	ranges = [
	<rangedata>, <rangedata>,</rangedata></rangedata>		
	nodes = [
	<int>, <int>,</int></int>		
	}		
]		
Description: –	An array of groups associated with this operation.		
Туре:	Array		
Optionality:	Required		
Allowed:			
Default:	none		
Notes:			
Example.			
group			
Syntax:	group = "str"		
Description:	The name associated with a node.		
Туре:	String		
Optionality:	Required		
Allowed:	Any character		
Default:	none		
Notes:			
Example:	group = "TEST_REP_0"		

table

Syntax:	table = " <i>str</i> "		
Description:	The name of the table associated with this group.		
Туре:	String		
Optionality:	Required		
Allowed:	Any characters		
Default:	none		
Notes:			
Example:	table = "TEST_REP"		
ranges			
Syntax:	ranges = [
	{ from - [<from data]<="" th=""></from>		
	to = $[\langle to data \rangle]$		
	}		
Description:	An array specifying the ranges to be associated with this group, table, and for this		
Description.	node.		
Туре:	Array		
Optionality:	Required		
Allowed:			
Default:	none		
Notes:	Although an index to support the ranges specified is not required, it is		
	recommended an index is used for performance reasons.		
	The number of elements in the from and to conditions must be the same and must match tables, key columns entry for the table specified.		
Example:	ranges = [
Examplei	{		
	from = [
]		
	to = ["2"		
]		
	}		
	1		
nodes			
Syntax:	nodes = [int, int, []]		
Description:	The list of nodes to be associated with this group.		
Туре:	Array		
Optionality:	Required		
Allowed:	Any nodes defined in Node section.		
Default:	none		
Notes:	These nodes must have been defined already in the Node section.		
Example:	nodes = [
]		

Input file example

This is an example of what the input configuration will look like, the indentation format is for readability.

```
replication = {
    perform = "resync"
    report-row-number-limit = 100
    produce-final-reports = true
    report-directory = "."
    report-after = {
       count = 10
       type = "seconds"
    }
    stop-on-limit = false
}
view = {
   nodes = [
    {
        id = 400
        address = [
            "127.0.0.1"
        ]
    }
    ]
    tables = [
    {
        table = "TEST REP"
        groups-cover-table-on-scp = true
        key-columns = [
            "NUMBER 3"
        ]
        other-columns = [
            "VARCHAR 1",
            "LONG RAW 2",
            "CHAR 4",
            "DATE 5"
        ]
    }
    ]
    groups = [
    {
        group = "TEST REP 0"
        table = "TEST REP"
        ranges = [
            {
                from = [
                    "1"
                ]
                to = [
                    "2"
                ]
            }
        ]
        nodes = [
            400
        ]
    }
    ]
}
```

Output

smsCompareResyncServer writes error messages to the system messages file.

smsCompareResyncServer writes replication checks and database comparisons to the /IN/html/output/SMS/compare/inferior_ node_number/ directory.

smsDumpRepConfig

Purpose

smsDumpRepConfig parses and displays the contents of **replication.config**. This provides access to the contents of the binary file where the replication configuration data is held.

For more information, see replication.config File (on page 38).

Configuration

The smsDumpRepConfig supports the following command-line options:

Usage:

```
smsDumpRepConfig -f filename [-v]
The available parameters are:
```

Parameter	Default	Description
-f	/IN/service_packages/SMS/et c/replication.config	Location of the configuration file to be displayed.
-v		Verbose, displays extra information, including column and field names.

Failure

If smsDumpRepConfig fails, it will send error messages to stdout and syslog. If an error is displayed while parsing a **replication.config** file, the file may be corrupted.

Output

smsDumpRepConfig displays output to stdout.

Example:

This text is an example of the output from a simple replication.config file which includes SMS and ACS replication groups between nodes 1 and 301.

TABLE [ACS FN TYPE]

```
TABLE [ACS GLOBAL PROFILE]
TABLE [ACS LANGUAGE]
TABLE [ACS NETWORK KEY]
TABLE [ACS SN CALL PLAN ACTIVATION]
TABLE [SMF ALARM MESSAGE]
TABLE [SMF STATISTICS]
TABLE [SMF STATISTICS DEFN]
smsDumpRepConfig: Replication Groups configured for each node...
        _____
NODE NUMBER [1] Prim (192.168.0.144) Sec (0.0.0.0)
NODE NUMBER [301] Prim (192.168.0.142) Sec (0.0.0.0)
    GROUP [ACS CUSTOMER] [Prim=-1] Min=('+0','',') Max=('+9','','')
    GROUP [ACS_FN_TYPE] [Prim=-1] Min=('+0','',') Max=('+9','','')
    GROUP [ACS CALL PLAN PROFILE] [Prim=-1] Min=('+0','',') Max=('+9','','')
    GROUP [ACS_CALL_PLAN_STRUCTURE] [Prim=-1] Min=('+0','',') Max=('+9','','')
    GROUP [ACS CALL PLAN] [Prim=-1] Min=('+0','',') Max=('+9','','')
    GROUP [ACS CUSTOMER CLI] [Prim=-1] Min=('+0','',') Max=('+9','','')
    GROUP [ACS_CUSTOMER_SN] [Prim=-1] Min=('+0','',') Max=('+9','','')
    GROUP [SMF STATISTICS DEFN] [Prim=-1] Min=('!','!',') Max=('~','~','')
    GROUP [ACS CLI CALL PLAN ACTIVATION] [Prim=-1] Min=('+0','',') Max=('+9','','')
    GROUP [ACS GLOBAL PROFILE] [Prim=-1] Min=('+0','',') Max=('+9','','')
    GROUP [ACS LANGUAGE] [Prim=-1] Min=('+0','',') Max=('+9','','')
    GROUP [ACS NETWORK KEY] [Prim=-1] Min=('+0','',') Max=('+9','','')
    GROUP [ACS SN CALL PLAN ACTIVATION] [Prim=-1] Min=('+0','',') Max=('+9','','')
```

Note: Both nodes are primaries for their groups and have no secondary network address configured.

smslorDump

Purpose

The smslorDump utility enables you to display details about the IORs (Interoperable Object References) available to CORBA services. You use smslorDump to investigate java exceptions related to CORBA.

The smslorDump utility is located in the following directory:

/IN/service_packages/SMS/bin/

Configuration

The smslorDump utility supports the following command-line options:

Usage:

```
smsIorDump [-u user/pw] -i IOR_str
```

Where:

- user/pw is the user and password for the database on the SMS
- IOR_str is the IOR whose details you want to display

Fields Displayed by smslorDump

This table describes the fields that display when you run the smslorDump utility.

Field	Description	
NAME	(Always display) The unique CORBA server label agreed between the server and the client.	

Field	Description
CLASS	(Display if available) Provides version information.
IP	(Display if available) The IP address that provides a key for distinguishing between multiple servers of the same type. Note that this IP address is not used to locate the server.
IOR	(Always display) The CORBA Interoperable Object Reference (IOR) that specifies the class of object actually served, and the host and port number of the server. The host and port number define the address that will be used to locate the server at run-time.

smsLogTest

Purpose

smsLogTest generates an alarm and writes it to the syslog on the local machine. You can configure the alarm details.

Configuration

smsLogTest supports the following command-line options:

Usage:

```
./smsLogTest name severity message [copies] [alarm_type_id]
The available parameters are:
```

Parameter	Default	Description
name	none	The subsystem name/identifier. (Required.)
severity	none	The severity value. (Required.)
		Allowed values:
		N or 0 [Notice]
		W or 1 [Warning]
		E or 2 [Error]
		C or 3 [Critical]
		- or 4 [clear]
message	none	The message to log. (Required.)
[copies]	1	Number of times to generate the alarm. (Optional.)
		Allowed values: integer
[{alarm_ty pe_id}]	none	Optional Alarm Type ID associated with the message. This must be up to a 9-digit number between braces (for example, {123456789}

Examples:

```
./smsLogTest smsAlarmRelay %d \"Failed to connect to Oracle\" 4\n {123456789}
./smsLogTest smsMaster %d \"Startup Successful\"
```

Failure

If smsLogTest fails, no alarm will be generated.

Output

smsLogTest displays progress and errors to stdout. It writes the alarm output to the local syslog.

smsManualRequester

Purpose

smsManualRequester sends update requests to the smsMaster.

Configuration

smsManualRequester supports the following command-line options:

Usage:

```
smsManualRequester [-nodeid value]
The available parameters are:
```

Parameter	Default	Description
value		the ID of the node (Optional)

Output

smsManualRequester displays the output to local terminal.

Examples:

```
./smsManualRequester -nodeid 999
Nov 22 22:01:48 smsManualRequester(6578) NOTICE: Update Requester
`./smsManualRequester' process registered (node 999)
Enter table name (start with `-' to indicate delete)
?-to set info return:-ACS CUSTOMER
Enter key names (key1, key2...):id
Enter values for keys & columns(terminate with ##):29
Enter values for keys & columns(terminate with ##):##
initialiseNode: Reading '/IN/service packages/SMS/etc/replication.def'
initialiseNode: heartbeatPeriod 20
initialiseNode: heartbeatTimeout 20
initialiseNode: connectionTimeout 2
initialiseNode: masterPortNum 12343
initialiseNode: queueWarnThresh 5
initialiseNode: queueErrThresh 100000
initialiseNode: queueCritThresh 1000000
initialiseNode: hBTolerance 10.0
initialiseNode: commitIdleTime 0.100000
initialiseNode: commitBusyTime 10.0
initialiseNode: tcpAbortSecs 20
initialiseNode: oracleUserPass '/'
initialiseNode: reportDir '/IN/service_packages/SMS/tmp/'
initialiseNode: statusFile '/IN/html/status.html'
initialiseNode: configFilePath '/IN/service packages/SMS/etc/replication.config'
initialiseNode: configFileName 'replication.config'
initialiseNode: node number 999
initialiseNode: node type 3
initialiseNode: s side updates 1
Nov 22 22:02:17 smsManualRequester(6578) NOTICE: Reached master node 1 at
`192.168.0.198'
Enter table name (start with `-' to indicate delete)
```

```
?-to set info return: .....
```

smsProcessCdr

Purpose

smsProcessCdr processes EDRs based on the rules set in a format file. The format file describes the fields, literal strings and functions to apply to the input data in order to produce the desired output EDR.

Functions include:

- Field selection
- Reordering
- Delimiter specification
- String concatenation with static strings and field values (such as would be required for field #13 in the EDR SRS)
- Multi-level pattern matching (as would be required for field #1) conditional field selection (as would be required for field #11)

This process is typically used to perform the following tasks for EDR files and ACS PIN log files:

- **1** (Optional) format conversion on files.
- 2 Move of files to a medium-term archive area.
- 3 (Optional) copy of files to directory for external retrieval.
- 4 Cleanup of expired files from the archive area.

Specification and implementation of EDR processing requirements is typically a system integration task which is performed prior to final system acceptance. This is usually implemented by the shell script smsCdrProcess.sh.

To prevent the EDR from being processed, see Configuring smsCdrProcess.sh (on page 140).

Configuration

smsProcessCdr accepts the following command line parameters.

Usage:

```
smsProcessCdr [-t edr_format] -d in_dir -D out_dir [-s in_suffix] [-p in_prefix] [-S
out_suffix] [-P out_prefix] [-u usr/pwd] [-1 tz] [-h] -b
The available parameters are:
```

Parameter	Default	Description
-t edr_format	none	The filename of the EDR format file.
		Note: No format conversion is performed by default. The formatting file supports the following:
		• Fields
		Literal strings
		Functions
-d in_dir	none	The directory to read EDRs from.
-D out_dir	none	The directory to write processed EDRs to.
-s in_suffix	none	The suffix that input EDR files must match (these are stripped from the output file name).

Parameter	Default	Description
-p in_prefix	none	The prefix that input EDR files must match (these are stripped from the output file name).
-S out_suffix	none	The suffix to add to output EDR files.
-P out_prefix	none	The prefix to add to output EDR files.
-u usr/pwd	/	The Oracle user and password to use.
		Note: smsProcessCdr will only attempt to connect to the database if the EDR format file contains functions that require it.
-1 <i>tz</i>	none	Alternate timezone TCS and TCE EDR fields are converted to.
-h	none	Displays a help page.
-b	none	Allows blank header tag values. Treats non-existent header tags as blank value.

Example 1

The following command would:

- Use /IN/service_packages/SMS/bin/cdrFormat.fmt as theEDR format file
- Process every file matching the pattern /IN/service_packages/SMS/cdr/received/scp2_acs*.cdr smsProcessCdr -t /IN/service packages/SMS/bin/cdrFormat.fmt -d

/IN/service_packages/SMS/cdr/received -D /tmp/processedCdrs -p scp2_acs -s .cdr -P ACS_ -S .out -u smf/smf

The output file name is a transformation of the input file name. For example, with the parameters supplied above, an input file /IN/service_packages/SMS/cdr/received/scp2_acs20010831120012.cdr would have output file named /tmp/processedCdrs/ACS_20010831120012.out.

Example 2

The following command:

```
smsProcessCdr -t /IN/service_packages/SMS/bin/mobifone.fmt -d
/IN/service_packages/SMS/cdr/received -D /tmp/processedCdrs -p scp2_acs -s .cdr -P
ACS_ -S .out -u smf/smf
Would cause the following file to be parsed as the EDR format file
/IN/service packages/SMS/bin/mobifone.fmt.
```

After parsing is complete, the binary will process its input files. With the parameters supplied above, this would be every file matching the pattern:

/IN/service_packages/SMS/cdr/received/scp2_acs*.cdr

When an input EDR is successfully processed, it is written out to an output EDR file. One output EDR file is created for each input EDR file. The output file name is a transformation of the input file name.

The input file /IN/service_packages/SMS/cdr/received/scp2_acs20010831120012.cdr would produce the following output file /tmp/processedCdrs/ACS_20010831120012.out.

Format File configuration

A EDR format file consists of field specifiers which translate input data to an output format.

The valid field specifiers are:

- Header tags
- Standard fields
- Special fields
- Strings
- Functions
- Format characters

Header tags

A HEADER tag may be specified in the format file passed in providing a single header line at the top of processed output files.

The header appears once and contains all HEADER tag values concatenated and space separated.

Through the use of a -b option passed in to smsProcessCdr at runtime blank values are allowed. When any tags are missing their respective value will be set blank rather than exiting on error. Underscores are allowed by default with no extra settings.

Standard fields

Standard fields are fields which relate to tags in the input EDR.

ACS EDRs have the following format:

```
APPLICATION| tag1=value1| tag2=value2| . . . | tagn=valuen A standard field is any one of the tag values.
```

If a EDR File format contains a field tag, then the corresponding value from the input EDR, value, will be written to the output EDR. Standard tags are written into the EDR format file using the same text which is used to specify them in the input EDR.

Special fields

Special fields are for data extracted from a EDR which does not occur in the input as a *tag=value* pair.

The only example of this is the EDR application name field, which always occurs as the first element in a EDR.

Placing the field <application> in the EDR format file will cause the application name from the input EDR to be written to the output EDR.

Strings

Strings are used to write literal text to the output EDR.

Strings appear in the EDR format file as double quoted strings "data".

Any characters occurring in *data* are written, verbatim, to the output EDR file. This can be used to supply field delimiters (for example: ",") or to hard code output values (for example: "0,2,-1,").

Functions

Functions are programmatic transformations that can be applied to values.

Functions occur in the DR format file with the form:

function_name (function_parameters)
Functions always produce a textual output.

The format of the functions used in smsProcessCdr are the same or similar to those used in the LISP programming language.

Most functions will support expressions as parameters so long as they produce textual output. The following types are included:

- Standard fields
- Special fields
- Strings
- Functions

Boolean expressions

Boolean expressions are used as parameters to COND functions (and could be used as parameters to other functions at a later date).

Boolean functions are functions which evaluate to either TRUE or FALSE. The compiler will not allow Boolean functions to be used as 'top level' functions, but they may be nested in other functions to provide the ability to test conditions.

EQUALS function

The EQUALS function compares two expressions for equality. EQUALS evaluates to TRUE if the expressions are equivalent. Otherwise it evaluates to FALSE. The equality test is a case-sensitive string comparison.

EQUALS (expr1 , expr2)

Example: This example shows the EQUALS function being used as part of a COND function. EQUALS is used to check whether the application name is "ACS".

```
COND ( ( EQUALS ( APPLICATION , "ACS" ) , "ACS Service" ) , ( TRUE , "Unknown Service" ) )
```

PREFIX function

The PREFIX function evaluates to TRUE if expr2 is a prefix of expr1. Otherwise it evaluates to FALSE.

PREFIX (expr1 , expr2)

Example: This example shows the PREFIX function being used as part of a COND function. PREFIX is used to check whether the service number (SN) in the input EDR starts with either the digits 0800 or 0900.

```
COND ( ( PREFIX ( SN , "0800" ) , "Freephone" ) , ( PREFIX ( SN , "0900" ) , "Pay Service" ) , ( TRUE , "Unknown Service" ) )
```

CONCAT function

The CONCAT function concatenates one or more expressions.

CONCAT (*expr1* [, *expr2* , *expr3* . . . *exprn*]) **Example:** This example concatenates the literal string T0 onto the value of the special field, *APPLICATION*. Therefore, if *APPLICATION* evaluates to CCS then the example would produce the output: T0CCS.

CONCAT ("TO" , APPLICATION)

Example: This example shows literal strings being concatenated to a field value and the result of another expression. If the value of the field XYZ is 21 and CCET is 12.32 then the result of the example would be: ABC2112.

CONCAT ("ABC" , XYZ , ROUND (CCET))

COND function

The COND function evaluates to an expression on the basis of a series of one or more test Boolean expressions.

The first Boolean expression which evaluates to TRUE causes its associated result expression to be evaluated as the result of the COND function. If none of the Boolean expressions evaluates to TRUE then the result of the COND function is an empty string.

COND ((bexpr1 , expr1) [, (bexpr2 , expr2) . . . , (bexprn , exprn)]) Examples:

In either of these two examples, the function evaluates to:

- Pizza Shed if the service number is 0800101101
- Pay Service if the service number starts with 0900
- Unknown in all other cases

```
COND ( ( EQUALS ( SN , "0800101101" ) , "Pizza Shed" ) , ( TRUE , ( COND ( ( PREFIX
  ( SN , "0900" ) , "Pay Service" ) , ( TRUE , "Unknown" )
COND ( ( EQUALS ( SN , "0800101101" ) , "Pizza Shed" ) , ( PREFIX ( SN , "0900" ) ,
"Pay Service" ) , ( TRUE , "Unknown" ))
```

For more examples, see the examples for PREFIX and EQUALS.

LANGUAGEID function

The LANGUAGEID function evaluates to the ID of a named language (from the ACS_SE_LANGUAGE table). The language name check is case insensitive.

If the named language can not be found, LANGUAGEID evaluates to -1.

LANGUAGEID ("string")

Note: Using the LANGUAGEID function requires a connection to the database, which requires setting the oracle user / password option when invoking smsProcessCdr (unless the default "/" will suffice).

Example: This example checks the language ID from the input EDR (the LGID field). If the LGID is the same as the ID for the language English, then the expression evaluates to 1. If it is French, it evaluates to 2, if it is German, it evaluates to 3.

```
COND ( ( EQUALS ( LANGUAGEID ( "English", LGID ) ) , "1" ) , ( EQUALS ( LANGUAGEID
( "French" , LGID ) ) , "2" ) , ( EQUALS ( LANGUAGEID ( "German" , LGID ) ) , "3"
) )
```

ROUND function

The ROUND function interprets the supplied expression as a floating point number and replaces it with the same value rounded to the nearest integer. ROUND also works for negative numbers (using the minus symbol). If the supplied expression cannot be interpreted as a floating point number, then ROUND will evaluate to 0.

```
ROUND ( expr ) Examples:
```

This example evaluates to 2.

```
ROUND ( "2.1" )
This example evaluates to 3.
```

ROUND (``2.6") If CCET evaluates to 12.3, this example evaluates to 12.

ROUND (CCET)

SUBSTR function

The SUBSTR function extracts a substring from a given expression. The parameters:

- expr is the source expression
- start is an integer indicating where the substring should start (counting starts at zero)
- *length* is an integer indicating how many characters should be read.

If *start* is greater than the length of *expr*, then SUBSTR returns an empty string. If the specified *start* and *length* would cause SUBSTR to read off the end of the input expression, then SUBSTR returns the maximum number of characters it could read.

SUBSTR (expr , start , length)
Examples:

This example evaluates to "the".

SUBSTR ("the happy elephant" , 0, 3) This example evaluates to "e ha".

SUBSTR ("the happy elephant" , 2, 4) This example evaluates to an empty string.

SUBSTR ("the happy elephant" , 50, 4)
This example evaluates to "appy elephant".
SUBSTR ("the happy elephant" , 5, 40)

Format characters

The format characters are a subset of the ASCII escape characters which allow special characters to be inserted into the output file. This table describes the supported format characters.

Format character	Definition
\n	New line
\r	Carriage return
\t	Tab
\0	Null

File Format example 1

A simple example which just picks up the application name, service number, CLI.

Fields are comma delimited, records are terminated with a newline character (\n).

Format File:

```
<application> "," sn "," cli n Input CDR file contents:
```

ACS | SN=0800101101 | CLI=044784333 | XYZ=123 ACS | SN=0900222333 | CLI=044784333 | XYZ=123 ACS | SN= | CLI=044784333 | XYZ=123

Output file contents:

```
ACS,0800101101,044784333
ACS,0900222333,044784333
ACS,,044784333
```

File Format example 2

A more complicated example using comments, special fields, and a function.

Fields are space delimited, records are terminated with a newline and a carriage return character.

Format File:

```
// our CDR format file
APPLICATION " "
// fields 2 and 3 are hard coded to be zero
```

```
"0 0 "
ROUND ( CCET ) " "
COND ( (EQUALS (APPLICATION, "CCS"), CONCAT("00", CA)), (TRUE, CONCAT("00", TN)) )
// end of line indicator:
\n \r
Input CDR file contents:
```

CCS | XYZ=123 | CCET=0.2 | TN=123123 | CA=321321 | ABC=333 ACS | XYZ=123 | CCET=8.8 | TN=123123 | CA=321321 | ABC=333 VPN | XYZ=123 | CCET=-1.6 | TN=123123 | CA=321321 | ABC=333 CCS | XYZ=123 | CCET=BOB | TN=123123 | CA=321321 | ABC=333

Output file contents:

CCS 0 0 0 00321321 ACS 0 0 9 00123123 VPN 0 0 -2 00123123 CCS 0 0 0 00321321

File Format example 3

Another complicated example using a header, comments, special fields, and a function.

Fields are space delimited, records are terminated with a newline and a carriage return character.

Format file:

```
HEADER ( "ONE TWO" )
//ROUND ( "6.1" )
<APPLICATION> " "
ROUND ( CCET ) " "
HEADER ( "THREE" )
COND ( (EQUALS(<APPLICATION>, "CCS"), CONCAT("00", CA)),
(TRUE,CONCAT("00", TN)) )
// end of line indicator:
\n \r
Input CDR file contents:
```

CCS | XYZ=123 | CCET=0.2 | TN=123123 | CA=321321 | ABC=333 ACS | XYZ=123 | CCET=8.8 | TN=123123 | CA=321321 | ABC=333 VPN | XYZ=123 | CCET=-1.6 | TN=123123 | CA=321321 | ABC=333

CCS | XYZ=123 | CCET=BOB | TN=123123 | CA=321321 | ABC=333 Output file:

 ONE
 TWO
 THREE

 CCS
 0
 00321321

 ACS
 9
 00123123

 VPN
 -2
 00123123

 CCS
 0
 00321321

Further information

Because of the wide range of external EDR processing systems and site-specific requirements, it is not feasible in this document to describe all of the tasks which may be required to complete EDR integration.

For more information about this process, contact Level 1 support with details.

smsRecordStatistic

Purpose

This tool makes use of the SMS statistics subsystem, which in turn makes use of shared memory for communicating with the smsStatsDaemon. The smsStatsDaemon must be installed and running.

Location

The smsRecordStatistic process is located on the SLC in the ./IN/service_packages/SMS/bin directory.

Configuration

smsRecordStatistic supports the following command-line options:

Usage:

```
smsRecordStatistic [application] [statistic] [value]
The available parameters are:
```

Parameter	Description
application	The name of the application for the statistic. (Optional)
statistic	The name of the statistic to record. (Optional)
value	Adds the given delta value to the statistic. (Optional.)

Output

The statistic named when running the script will be updated in the database.

smsStatsQuery

About smsStatsQuery

The smsStatsQuery utility enables you to directly query statistics generated on the Voucher and Wallet Server (VWS) and Service Logic Controller (SLC) before the statistics are replicated to the Service Management System (SMS). You use this utility for system monitoring.

Tip: You can view statistics that have been replicated to the SMS node by using the statistical viewing feature in the SMS user interface (UI). For more information, see *Service Management System User's Guide*.

The smsStatsQuery utility is located in the following directories:

- /IN/service_packages/BE/bin on the VWS nodes.
- /IN/service_packages/SMS/bin on the SLC nodes.

You can either supply a single query string as input to smsStatsQuery, or you can supply a text file containing a list of query strings as input.

Usage:

```
smsStatsQuery [options] "stats_query"
smsStatsQuery [options] -f "queryfile"
Where:
```

• options is a space-separated list of optional parameters. The available options include options for the standard bc (binary calculator) Solaris utility, that is accessed by smsStatsQuery to apply calculations to the statistics results.

The optional parameters and some typical bc options that you might want to set are listed in the *Optional Parameters Table* (on page 231) below.

Note: You can display a full list of bc options by entering man bc at the UNIX prompt.

• *stats_query* is a string that identifies the statistics to query. To retrieve multiple statistics, specify a space-separated list of the statistics you want in the query string. You can also include a mathematical formula in the query to perform calculations on the retrieved statistics and return a single value.

See Specifying the Statistics to Query (on page 230) for information about specifying the *stats_query* string.

• *queryfile* is the name of a text file that contains a list of *stats query* strings.

Note: Specify either stats query or queryfile, but not both.

Examples

In the following examples, the statistics to query are specified in a query string:

```
./smsStatsQuery "Acs_Service.elapsedTime"
./smsStatsQuery "Acs_Service.CALLS_INITIATED Acs_Service.ANNOUNCEMENTS_PLAYED"
```

In the following example, the statistics to query are specified in a text file:

./smsStatsQuery -f "queryFile.txt"

Note: The statistics on the VWS and SLC nodes are collected by smsStatsDaemon for replication to the SMS node. If you enter a query for a statistic that is not currently held by smsStatsDaemon then the smsStatsQuery utility returns an error. You can check which statistics are currently held by smsStatsDaemon by entering the following command:

./smsStatsQuery -1

For more information about smsStatsDaemon, see smsStatsDaemon (on page 184).

Specifying the Statistics to Query

To specify one or more statistics in the *stats* query string, use the following syntax:

```
application.statistic[.detail] [application.statistic[.detail]]
Where:
```

- *application* is the name of the application or service that generated the statistic, such as Acs_Service.
- *statistic* is the name of the statistic to query, such as *elapsedTime*.
- *detail* (optional field) is the name of a detail field associated with the specified statistic. Note: Not all statistics have detail fields.

For example, the following queries retrieve statistics for the ACS service:

```
./smsStatsQuery "Acs_Service.elapsedTime"
./smsStatsQuery "Acs_Service.CALLS_INITIATED Acs_Service.ANNOUNCEMENTS_PLAYED"
```

To query a statistic that contains a space in any of its attribute names, you must use double square brackets, "[[" and "]]", to enclose the statistic specification in the *stats* query string.

For example, the following queries include the "PrePaid Success" statistic in the stats query string:

```
./smsStatsQuery "[[Ccs_Service.PrePaid Success]]"
./smsStatsQuery "Acs_Service.CALLS_INITIATED [[Ccs_Service.PrePaid Success]]
Acs_Service.ANNOUNCEMENTS_PLAYED"
```

To specify a formula in the *stats* query string, use the following syntax:

```
[factor]statistic[[factor][statistic]]
Where:
```

- *factor* is a combination of a constant and an operator, or just an operator, that is applied to the statistic.
- *statistic* is a statistic specified as: *application.statistic.detail*.

For example:

./smsStatsQuery "10*Acs_Service.ANNOUNCEMENTS_PLAYED/Acs_Service.CALLS_INITIATED"

Note: You may not retrieve a list of statistics if you include a formula in the stats_query string.

Optional Parameters Table

This table describes the optional parameters for smsStatsQuery.

Parameter	Description		
-h	Lists usage information for the smsStatsQuery utility.		
-1	Lists the contents of statistics currently held by smsStatsDaemon.		
-t secs	(bc option) Calculates the average rate a statistic is used based on two readings of the statistic, where the second reading is taken $secs$ seconds after the first reading. The formula used to calculate the average rate a statistic is used is: (value of reading 2 - value of reading 1)/ $secs$.		
-p precision	(bc option) Specifies the number of decimal places to display for the statistics value output.		

startMerge

Purpose

This command initiates a master merge of an inferior master to a superior one. It can also be used to safely shut down an superior master by merging it with an inferior master.

Configuration

The startMerge supports the following command-line options:

Usage:

```
startMerge [-from nodenum] [-to nodenum]
The available parameters are:
```

Parameter	Default	Description
-from nodenum	none	Node number of the inferior master to merge from.
-to nodenum	none	Node number of the inferior master to merge to.

Failure

If startMerge fails, it will write an error to the syslog and exit.

Output

The startMerge writes error messages to the system messages file, and also writes additional output to /IN/service_packages/SMS/tmp/merge.rep.

Chapter 8 Reports

Overview

Introduction

This chapter explains SMS reporting functionality.

In this chapter

This chapter contains the following topics.

Reports Database Tables	
Installing a Report Script	
Report Script Worked Example	
Database Auditing	

Reports Database Tables

Introduction

Report-generating functionality is available via the SMS Java screens, to provide for service management reports of data.

This topic describes how to create reports:

- Service reports, to be installed at the time of service installation
- General reports, installed subsequently

Database tables

There are three database tables which are specific to report generation:

- SMF_REPORT_SCRIPT contains one entry for each report script
- SMF_REPORT_PARAMETER contains one entry for each report parameter (may be none)
- SMF_REPORT_SCHEDULE contains one entry for each scheduled report instance. This table is not used for report installation, and is not covered in this document.

In addition, the following tables are used for controlling who has access to a report:

- SMF_APPLICATION
- SMF_APPLICATION_PART
- SMF_APPLICATION_ACCESS

These tables are reviewed here in regards to their role in report security. Security is handled by the standard SMS application part mechanism (see, example 3). Auditing is provided by the standard SMS audit mechanism, and should not need changing. The last change fields are the standard SMS last change fields, and are not listed in this table.

Report Scripts table

The report database table is called SMF_REPORT_SCRIPT. It contains the details of reports as shown below.

Field	Description	
REPORT_ID	Unique identifier, primary key, generated by a counter.	
APP_ID	Application ID, foreign key to SMF_APPLICATION(app_id)	
PART_ID	Part ID for security, foreign key to SMF_APPLICATION_PART (part_id)	
CATEGORY	Script category, identifies the subdirectory.	
SCRIPT	Script name, identifies the . sql file or shell script to execute.	
NAME	Name to list in the report directory.	
DESCRIPTION	Help text.	

Report parameter table

The parameter table is called SMF_REPORT_PARAMETER. It contains the details of report parameters as shown below.

Field	Description
REPORT_ID	The ID of the report this parameter belongs to.
PARAM_NUMBER	The position of the parameter in the list, for example 1st, 2nd.
NAME	The parameter name.
DESCRIPTION	Help text.
TYPE	The type – INT, STRING, DATE, and so on. (See table following for details)
DEFAULT_VALUE	Default value, optional.
VALID_VALUES	Valid comma separated values.
CONSTRAINT1	A constraint on the parameter (interpretation depends on TYPE).
CONSTRAINT2	A constraint on the parameter (interpretation depends on TYPE).

Installing a Report Script

Introduction

A script must be installed before it can be made available to the system. This process is described here, along with examples.

The main steps in the procedure detailed below are:

- 1 Choose an application ID, a category, and a report name.
- 2 Determine the parameters (if any) required by your script, and write the script.
- 3 Decide which application part your report will belong to.
- 4 Install the actual script on the SMS in the correct location.
- 5 Insert entries into the REPORT tables in the SMS database.

Procedure

3

4

Follow these steps to install a report script.

Step	Action
1	The Application ID must be an existing entry from SMF_APPLICATION. Common values are shown below. If you have additional services installed, additional choices may be available. SQL> select app_id, application from smf_application; APP ID APPLICATION

----- 1 SMS

4 SYSTEM

2 Acs_Service

The Category is an arbitrary name for a group of reports within one application. For example: "Customer", "Management", "Resource Usage".

The Name is a name for your report. Typically, this will be similar to the script name. For example, if your script is **monthly_usage.sql**, your report name could be "Monthly Usage".

- 2 Your script may take user parameters. The SMS report functions allow you to determine whether these are string, numeric, or values from a constrained list of parameters. Refer to the description of the SMF_REPORT_PARAMETER table to see the parameter types supported.
 - A report must one of the following:
 - Have a .sql extension. In this case, it will be executed using sqlplus.
 - Be executable by the smf_oper user.

In either case, the script will be passed (n + 1) command line parameters, where n is the number of user parameters defined in SMF_REPORT_PARAMETER. Command line parameter one will always be the absolute output file name allocated to this report.

Examples:

for a .sql file:

sqlplus script-name output-file [user-parameters]

for an executable file without a .sql extension
 script-name output-file [user-parameters]

Exit status of report scripts are defined by the following:

- 0 = okay
- > = not okay. (Unix style)
- <0 = undefined

Neither the smsReportsDaemon nor the smsReportScheduler is responsible for the clean up or reclaim of resources used by reports. This must be done explicitly by the application programmer.

The user may request cancelation of a script, in which case it will be sent a SIGTERM. Scripts should not ignore SIGTERM.

If the report spawns children, it should implement a SIGTERM handler to dispose the children, in case the user cancels a report.

For simplicity, an application part may be reused. Access to multiple reports may be controlled by one application part. You can even re-use access parts controlling existing installed screens.

You can list all existing defined application parts with the SQL command: SQL> select app_id, part_id, part from smf_application_part;

If you choose to re-use application part 1030 (SMSReportScreens), all users who can access report screens will be able to run this report.

Step	Action
5	The script itself must be placed into /IN/service_packages/SMS/input/application- namelcategorylscript-file.
6	The script must now be made known to the SMS screens, and available for use to any SMS user who has access to the part ID, which owns your report script. This means:

- Inserting an entry into SMF_REPORT_SCRIPT for your script, indicating the category and script filename.
- Inserting one entry into SMF_REPORT_PARAMETER for each parameter in your report (if any). This indicates any constraints you wish enforced (for example, min/max values).

Report Script Worked Example

Introduction

A script must be installed before it can be made available to the system. This process is described here, along with examples.

The main steps are:

- 1 Choose a category and a name for your script.
- 2 Determine the parameters (if any) required by your script, and write the script.
- 3 Decide which application part your report will belong to.
- 4 Install the actual script on the SMS in the correct location.
- 5 Insert entries into the REPORT tables in the SMF database.

Example report script

Follow these steps to work through the example report script. The example script appears below description of each action in the procedure.

Step	Action		
1	The details for this example are:		
	Application: SMS (ID is 1)		
	Category: "Errors"		
	Name: "Program Errors"		
Script File: program_errors.sql			
	Application Part: 1805 (new part)		
	In this example, we are installing into the application SMS, which has the unique application ID of 1. Typically, you will install a service-specific report under the unique application ID that has been allocated to your service.		
	We are free to choose the category; we have chosen the "Errors" category.		
	We are free to choose a unique script name within this application and category; we have		

We are free to choose a unique script name within this application and category; we have chosen **program_errors.sql**. We have chosen to create a new application part (1805) to control access to this report. An existing part may be used, for example: 1030.

Step	Action		
2	The report takes three user parameters:Num Hours:Integer in range 1999, default is 24Program Prefix:String length 020 charactersCategory:One of FATAL, SERIOUS, WARNING, INFORMATIONAL		
	Note: The script itself will take four parameters. The first parameter is the output file name, which is determined by the reports daemon and is handed to us. You <i>must</i> generate your output to that file, if you wish it to be seen by the user.		
	The script below accepts three arguments, and shows the essential basic techniques of accepting input parameters, and spooling to the correct output file.		
/*			
* File:	program_errors.sq1		
* Updat *	ces:		
* Paran *	<pre>neters: &1 Output file, determined by reports daemon &2 Hours back</pre>		
*	&3 Program prefix		
*	(FATAL, SERIOUS, WARNING, INFORMATIONAL)		
* Copyi * (c)19	right Notice: 998 This source code is owned and copyrighted by Oracle		
* #ider Exp \$"	nt "@(#)\$Id: telephony_errors.sql,v 1.4 1999/02/25 22:10:29 rhwang		
so we set terr set veri	e won't print to stdout. nout off lfy off		
we are going to access the sms_program_errors table. set the column titles. column program 'Program' format a20 column error_code 'Error Code' format a16 column node_name 'Node Name' format a20 column severity 'Error Severity'			
set line set page	esize 80 esize 2100		
spool &1 now s ttitle c skip 1 - center	set the title at the top of the page. center 'Recent Telephony Errors for Application &3 Severity &4' - 'PROGRAM TELEPHONY ERRORS' -		
center = RIGHT 'H	center ====================================		

3

Step Action

```
break on program skip 1;
break on severity skip 1;
select program, severity, error_code, node_name, timestamp
from smf_program_errors
where (program like '%&3') and
        (severity like '%&4') and
        (timestamp < sysdate - &2/24)
order by program, severity;
spool off
quit
```

- The user must now specify an application part for security purposes. If you have decided to re-use an existing part_id (for example: 1030), proceed to Example part 4.
 - a. The Application ID for this example is 1. This is the unique ID for SMS.
 - b. Application Part IDs must be in the range App-ID * 1000 + (0 ... 999) so for SMS, this means 1000 .. 1999. In this example, it has been determined that the ID 1805 is available for use. This is a new ID, which will control access to this report (and possibly others placed in the same security domain).
 - c. Application Access IDs must be in the range <Part-ID> * 100 + (0..99). This is the part ID, so any Access ID within this range may be chosen. In the example, 180500 has been chosen.

As part of the installation for this script, run SQL to create this new Part ID.

Note: It is not necessary to create the SMF_APPLICATION for the SMS, since this is already created as part of the smsSms installation.

```
/*
 * Create our application part. We can re-use this if we
 *
   have multiple reports that we want to have all controlled
 * by a single security identifier
 */
insert into smf_application_part (part_id, app_id, part, description)
 values (1805, 1, 'SMSErrorReports', 'Access SMS error reports
category');
insert into smf application access (access id, part id, rights name,
description)
  values (180500, 1805, 'Access', 'Run reports');
/*
 * We also add this to the 'SMS CreateDelete' user template,
 ^{\star} so that any user who is granted this template will get
 ^{\star}\, access to this report. We could add this to other
 *
   templates too...
 */
var temp id number;
EXEC select template id into :temp id from smf template where
template='SMS CreateDelete';
insert into smf_template_access (template_id, access_id)
 values (:temp_id, 180500);
commit;
```

```
Action
Step
4
          As part of the installation package, ensure that the file, program errors.sql is installed into
          the correct destination location, for example,
          /IN/service packages/SMS/input/SMS/Errors/program errors.sgl.
          The smf oper user must have read access to this file. If this was a shell script or a binary
          program, it is necessary to ensure that the smf oper also has execute access to this file.
5
          The final task is to notify the SMS about the script, to make it visible.
          In this example, the report and the three user parameters to be collected are defined.
          Note: The screens constrain the content of the parameters to be passed to the script, but
          the interpretation of the parameters is of course up to the script itself.
/*
  * Add our script to the list of scripts.
  */
var report ref number;
insert into smf report script
   (app id, part id, category, script, name, description)
values
   (1, 1805, 'Errors', 'program errors.sql', 'Program Errors',
    'Dumps all the program errors for the specified program(s)');
exec select report id into :report ref -
from smf report script -
  where (app id=1) -
  and (category = 'Errors') -
  and (name = 'Program Errors');
insert into smf report parameter (
  report id, param number, name, description, type,
  default value, valid values, constraint1, constraint2)
values
   (:report ref, 1, 'Num Days', 'Number of hours to go back',
    'INT', <sup>'</sup>24', '', '1', '999');
insert into smf report parameter (
   report id, param number, name, description, type,
  default value, valid values, constraint1, constraint2)
values
   (:report ref, 2, 'User',
    'Leading string of program (0-20 characters)',
    'STRING', '', '', '0', '20');
insert into smf report parameter (
   report id, param number, name, description, type,
  default value, valid values, constraint1, constraint2)
values
   (:report ref, 3, 'Category', 'Error Category (pulldown menu)',
    'STRING, 'FATAL', 'FATAL, SERIOUS, WARNING, INFORMATIONAL', '', '');
commit;
```

Database Auditing

Introduction

Changes to the data held in the SMF are tracked in the SMF_AUDIT table.

The listAudit.sh tool enables reports to be run on the changes tracked in SMF_AUDIT.

Purpose

listAudit.sh enables you to run queries against the audit data held in the SMF_AUDIT table. The results are processes in to a comma separated report.

Configuration

listAudit.sh accepts the following command line options.

Usage:

```
listAudit.sh usr/pwd [start_date] [end_date] [db_user] [table]
The available parameters are:
```

Parameter	Default	Description
usr/pwd		The user and password combination to be used to log into the SMF. (Required.)
start_date		The time and date the query will start reporting on. The format is yyyymmddhh24mmss. (Optional.)
end_date		The time and date the query will stop reporting on. The format is yyyymmddhh24mmss. (Optional.)
db_user		The userid for the database user which made the changes to the database. (Optional.)
table		The database table which was changed. (Optional.)

The square brackets indicate optional parameters, but if a parameter is missed out and a later one used the missed out parameters should be indicated by using "".

Failure

If listAudit.sh fails, the report will not be completed. Errors will be sent to stdout.

Output

listAudit.sh writes error messages to the system messages file, and produces reports to stdout.

Example: This text shows an audit report for changes to the SMF_USER table by the SU user on the 08 Mar 2005.

```
$ listAudit.sh smf/smf 20050308000000 20050308235959 SU SMF_USER
Connected.
SU,20050308225724,192168007165,SMF_USER,ADMIN_TRAINING1_EX2,Student Training,Student
1,0,,31,20050321010942,LANGUAGE=ENGLISH
,,,ADMIN_TRAINING1_EX2,Student Training,Student 1,0,Locked for
testing,31,20050408000000,LANGUAGE=ENGLISH
SU,20050308225808,192168007165,SMF_USER,ADMIN_TRAINING1_EX1,Student Account,Student
1,0,,31,20050320205427,LANGUAGE=ENGLISH
,,,ADMIN_TRAINING1_EX1,Student Account,Student 1,0,Locked for
training,31,20050408000000,LANGUAGE=ENGLISH
```

SU,20050308225828,192168007165,SMF_USER,ADMIN_TRAINING1_EX1,Student Account,Student
1,0,Locked for training,31,20050408000000,LANGUAGE=ENGLISH
,,,,ADMIN_TRAINING1_EX1,Student Account,Student
1,0,,31,20050408000000,LANGUAGE=ENGLISH

SU,20050308225838,192168007165,SMF_USER,ADMIN_TRAINING1_EX2,Student Training,Student
1,0,Locked for testing,31,20050408000000,LANGUAGE=ENGLISH
,,,,ADMIN_TRAINING1_EX2,Student Training,Student
1,0,,31,20050408000000,LANGUAGE=ENGLISH

Chapter 9 Troubleshooting

Overview

Introduction

This chapter explains the important processes on each of the server components in Convergent Charging Controller, and describes a number of example troubleshooting methods that can help aid the troubleshooting process before you raise a support ticket.

In this chapter

This chapter contains the following topics.

Common Troubleshooting Procedures	
Possible Problems	
Index Defragmentation	

Common Troubleshooting Procedures

Introduction

Refer to System Administrator's Guide for troubleshooting procedures common to all Convergent Charging Controller components.

Checking current processes

You can check which processes are running using the standard UNIX command: ps. To find processes being run by Oracle software, you can grep for the string 'oper', which will display all processes being run by the application operator accounts (for example, acs_oper, ccs_oper and smf_oper).

Note: Some processes which are required for proper functioning may be run by other users, including root or the user which runs the webserver.

Example command: ps -ef | grep oper

For more information about the ps command, see the system documentation for the ps command.

You can also check how much of the processor a process is using by running the standard UNIX tool: top. If you have some baseline measurements, you will be able to compare it with the current load.

Example command: top

Tip: Some processes should only have one instance. If there are two or more instances, this may indicate a problem. For example, there will usually only be one timerIF running on each SLC.

For more information about which processes should be running on each node, check the Process List for each node in *Installation Guide*.

Restarting running processes using kill

Follow these steps to restart a running process.

Important: Restarting some processes can cause system instability or data loss. Some processes must be restarted using specific tools. Check the documentation for the process before restarting.

Step	Action
1	Find the Process ID for the process you want to restart.
	Example command: ps -ef grep smsAlarmRelay
	Note: The second column of the results returned is the Process ID and the third column gives the Parent Process ID.
2	Kill the process using the kill command. Example command: kill -TERM 123

Result: The process is terminated and will be restarted by the inittab process.

Checking configuration files

One of the significant areas where faults can occur and be remedied is in the configuration of processes. Configuration files can be edited by any standard text editor. A backup of the existing configuration file should always be taken before editing a configuration file.

For more information about the configuration files used in this application, see *Configuration User's Guide*.

For more information about the configuration file for a specific program or tool, see the section named after the binary in question.

Possible Problems

Introduction

This topic lists common problems and actions you can take to investigate or solve them. This list enables you to check for alarms based on the overall behavior you are experiencing.

SMS Java screens will not start

Follow these steps to resolve JavaClient problems.

Step	Action
1	Ensure that the HTTPD daemon (on the SMS) is running and that it is correctly configured.
2	 If you are able to start the SMS screens, but unable to login: Ensure that the sms.jnlp file is correctly configured.
	 Ensure that the SMS console is able to resolve host names into IP addresses.

Java help screen grayed out

This is caused by Java Runtime Environment (jre) running out of memory for the run time heap cache.

Under the default Java settings this may happen after 10 to 15 help screen accesses.

Follow these steps to extend the number of Help accesses.

Step	Action		
1	Close the SMS screens.		
Step	Action		
-------	---	--	--
2	From the Windows system, open the Control Panel.		
3	Switch to Classic View to see the complete list of installed applications.		
4	Double click Java icon to open java Control Panel.		
5	Select the Java tab.		
6	Click View in the Java Applet Runtime Settings panel.		
7	Click the Java Runtime Parameter field.		
	Note: This is the fourth field along, pop-up may require expanding to see this field.		
8	Type -Xms10M -Xmx512M in the Java Runtime Parameter field.		
	Note: If other parameters are there, add these to the end.		
9	Click OK .		
10	Click Apply .		
11	Click OK .		
12	Close the Control Panel.		
13	Restart the browser and start the SMS screen.		
Note:	Using Xmx512M may cause issues with starting jre. If the browser jre cannot start up, try -		

Replication is failing

Xmx180M.

This table describes possible problems with replication.

Alarm	Reason	Remedy
Cannot connect to Oracle - exiting	There is a problem with the replication.config files in the system.	Use smsDumpRepConfig to check that the content of replication.config is correct.
		Generate a new replication.config file and check is it correctly copied to each machine.
		For more information, see <i>replication.config File</i> (on page 38).
Could not make fifo f - exiting	A connection is being dropped because the heartbeat settings on each end of a connection are different.	Check that the heartbeat settings for both ends of the connection are the same. The heartbeat settings are in replication.def , though they can be overridden at the command line for any process.

comparisonServer is failing

Alarm	Reason	Remedy
	The replication.config file is not available to inetBootstrap, so smsCompareResync is not starting up.	Check that replication.config is in the correct directory and is readable by smf_oper.

This table describes possible problems with comparisonServer.

Index Defragmentation

Description

The automatic defragmentation facility provided by SMS is intended to prevent fragmentation of the replication tables which frequently use insert, delete and update functions.

In order to enable this defragmentation facility, the script fragmentation_install.sh must first be installed. This will install the stored procedure sms_defrag_rep_iot, and schedule a job to run it every 10 minutes.

The following tables are affected:

- REP_ORA_EVENT
- REP_ORA_RENUMBERED

Before you begin

The process for installing the defragmentation script varies depending on the Oracle configuration available on the SMS. For most clustered environments, Oracle configuration is stored in the service parameter file (SPFILE), which permits configuration parameters to be modified at runtime. If this is the case, then the there is no need to manually alter the Oracle configuration.

However, if SPFILEs are not in use (that is the traditional PFILEs are used to manage Oracle configuration), then it is important to first modify the cache and block sizings in the **initSMF.ora** file. The cache size for the 32 KB block size should be set to 32 MB or another suitably large value.

Note: It is recommended that this activity is performed by an experienced DBA.

Enabling defragmentation

To enable the defragmentation facility, run the following script:

```
fragmentation_install.sh
This script is located in:
```

/IN/service_packages/SMS/db/defragmentation

Disabling defragmentation

To disable the defragmentation facility, run the uninstallation script as the oracle SMF user:

fragmentation_uninstall.sh
This script is located in:

/IN/service_packages/SMS/db/defragmentation

Oracle configuration restriction

While editing the parameter files, it must be noted that the following sets of parameters are mutually exclusive and cannot be used in combination with each other.

Example: You cannot use one or more of:

```
{db_cache_size,
db_recycle_cache_size,
db_keep_cache_size,
db_nk_cache_size (where n is one of 2,4,8,16,32),
db_cache_advice }
```

AND one or more of the following in your configuration:

{db_block_buffers buffer_pool_keep buffer_pool_recycle}

Chapter 10 Pre-installation

Overview

Introduction

This chapter explains the pre-installation configuration requirements of the application.

In this chapter

This chapter contains the following topics.

SMS Client Specifications	
Preparing the System	
Database Timezone and Backups	
Starting Oracle Automatically on Reboot	

SMS Client Specifications

Specifications

This topic provides the specifications of SMS.

Network

The minimum requirements of network bandwidth for acceptable normal response times are as follows:

Number of Users	Minimum Requirements
1-5	512 KB
6-15	1 MB
16 +	LAN connection (at least 25% available resource of 10 MB)

Memory

The Convergent Charging Controller screens are written to optimize data interaction. As a result, it is necessary to cache data in such a way as to reduce redundant data retrieval. This means that heavy usage can lead to the requirement for a large amount of memory to be available on the client machine running the screens. The recommended memory installed on the client machine is 256MB minimum with 512 MB preferred, especially with machine running Windows XP.

This table shows the minimum client resources required.

RAM	СРИ
256 MB	800 MHz

This table shows the recommended client resources required.

RAM	СРИ
512 MB	1.2 GHz

Response Times

This table shows typical response time.

GUI Action	Response Time
Startup to Login dialog	30 seconds maximum
Login to SMS main screen	20 seconds maximum
SMS main screen to ACS	5 seconds maximum
ACS main screen to CPE	15 seconds maximum

Screen

Here is the required screen specification.

Pixel	
800 x 600 pixel resolution	

Preparing the System

Introduction

It is recommended that you check the kernel parameters on the system to ensure the system is optimally configured.

The following parameters are described in their respective technical guides. However, they are collated here for reference.

Note: Actual kernel parameters may be greater than those listed here.

Checking Kernel Parameters

Follow these steps to check the Kernel parameters for Solaris.

Step	Action
1	Log in as root.
2	Enter cat /etc/system
3	Check the parameters are set to at least the minimum values.
4	Change the parameters as required using the following command from /etc/system.

Parameters

This table shows all kernel parameters:

Parameter	Min Value	Hex Value	Description
semmni	1024		Number of semaphore identifiers.

Parameter	Min Value	Hex Value	Description
semmsl	1024		Maximum number of semaphores per unique ID.
semmns	14000		Maximum number of semaphores.
shmmax	429496729 5	4000000	Maximum shared memory segment (bytes).
shmmin	1		Minimum shared memory segment (bytes).
shmmni	400		Number of shared memory identifiers.
shmseg	50		Number of shared memory segments allowed per process.
semopm	100		Maximum number of semaphore operations that can be executed per semop system call.
semvmx	65535		Maximum semaphore value.

Database Timezone and Backups

Setting Oracle timezone

To operate correctly, Oracle must be running on Greenwich mean time (GMT).

To ensure that Oracle is running on GMT, check that the following line is in the Oracle user's .profile:

```
TZ=GMT
export TZ
```

Oracle database domain

Check that the sqlnet.ora file does not override the oracle database domain specified in the initSMF*.ora file. Overriding will cause database creation failure with an inability to resolve the required database name in the the term of term of

The initSMF*.ora files are located in the /IN/service_packages/SMS/db/install/create/SMP/machine-profile directory.

Each file should contain the following line:

```
db_domain=basms1p.SMF
The sqlnet.ora file should contain the following line:
```

```
NAMES.DEFAULT_DOMAIN = Oracle
The sqlnet.ora file will be in the $ORACLE_HOME/network/admin/ directory.
```

Note: The specific **initSMF*.ora** file used in the installation is specific during the execution of the smsSms installation script.

SMF backups

The SMF can be backed up in two ways.

- Shut down the database periodically and backup all the database data files. This is simple but will disable provisioning and service side updates for the duration of the backup.
- Hot Backups:

Archive logging should be enabled

Archive logs and table spaces must be backed up and archive logs removed periodically. This procedure must be implemented by an individual with good knowledge of Oracle databases.

Archive logging

It is important to remember that if archive logging is enabled and the archive logs are not removed periodically then the disk will eventually fill up and the database will cease to function.

Starting Oracle Automatically on Reboot

Setting the initialization

In an operational environment, it is desirable that Oracle automatically start on reboot. This requires the creation of various scripts in the Unix initialization directories. A script is provided to simplify this task.

Before you begin

These tasks require that the "dbstart" script is in the default PATH for the "Oracle" user.

Procedure

Follow these steps to configure Oracle on Solaris.

Step	Action
1	Log on as root.
2	Enter cd /IN/service_packages/SMS/install/init-sun
3	Enter sh ./oracle.sh
	Result: The script will start.
	The output below shows the steps that are performed to configure automatic starting of Oracle on reboot. Action: Configure Startup/Shutdown Removing /etc/init.d/oracle Removing /etc/rc.config.d/oracle
	Removing /etc/rc2.d/S901oracle Removing /etc/rc0.d/K011oracle Copying oracle to /etc/init.d/oracle /etc/rc.config.d exists Creating /etc/rc.config.d/oracle Creating link to /etc/rc2.d/S901oracle Creating link to /etc/rc0.d/K011oracle
For Linux, Administra	see the discussion about automating shutdown and startup in Oracle Database tor's Reference for Linux and UNIX-Based Operating Systems Guide.

About Installation and Removal

Overview

Introduction

This chapter provides information about the installed components for the Oracle Communications Convergent Charging Controller application described in this guide. It also lists the files installed by the application that you can check for, to ensure that the application installed successfully.

In this Chapter

This chapter contains the following topics.

Installation and Removal Overview	
Raw Devices on Clustered SMS	
Setting up ssh keys	
Checking the Installation	

Installation and Removal Overview

Introduction

For information about the following requirements and tasks, see Installation Guide:

- Convergent Charging Controller system requirements
- Pre-installation tasks
- Installing and removing Convergent Charging Controller packages

SMS packages

An installation of Service Management System includes the following packages, on the:

- SMS:
 - smsSms
 - smsCluster (clustered)
 - efmSms
 - efmCluster (clustered)
- SLC:
 - smsScp
- VWS:
 - smsExtras

Raw Devices on Clustered SMS

Raw devices

SMS can allocate tablespace storage based on raw (without a file system) partitions. This enhances the performance of SMS on the SMS.

If you are using the raw devices option, you must create the raw partitions before installing the database using tools such as the system's format command.

The raw devices file (which you will be prompted to complete during the installation) must contain the full paths of the device files for the appropriate partitions.

The partitions must be at least as big as the required datafile sizings listed in the sizing file which will be used by the installation.

Example smf_devices.sh file

This is an example smf_devices.sh file.

```
#!/bin/sh
# The following file is the structure required for knowledge of
# raw device utilization and a few details pertaining to cluster
# creation. If clusters are not used then retaining the default
# values will be sufficient and not impact installation for raw
# device only.
# Details about the cluster
# How many instances in the cluster?
CLUSTER INSTANCES=2
export CLUSTER INSTANCES
# For each instance in the cluster we need to know the node name
# to install into the service configuration
NODE_1=smp1
NODE_2=smp2
export NODE 1 NODE 2
# These are the generic RAW DEVICE requirements for the cluster
# NOTE:// ENSURE ALL THESE DEVICES ARE READ WRITEABLE BY THE
# ORACLE USER OTHERWISE INSTALLATION WILL FAIL
# System tablespace
SYSTEM TABLESPACE=/dev/did/rdsk/d10s5
export SYSTEM TABLESPACE
# USERS tablespace
USERS TABLESPACE=/dev/did/rdsk/d10s6
export USERS TABLESPACE
# Temporary tablespace
TEMP DATAFILE 1=/dev/did/rdsk/d10s2
TEMP DATAFILE 2=/dev/did/rdsk/d10s3
TEMP DATAFILE 3=/dev/did/rdsk/d10s4
TEMP DATAFILE 4=/dev/did/rdsk/d11s0
TEMP DATAFILE 5=/dev/did/rdsk/dl1s1
TEMP DATAFILE 6=/dev/did/rdsk/d11s2
TEMP DATAFILE 7=/dev/did/rdsk/d11s3
TEMP DATAFILE 8=/dev/did/rdsk/d11s4
export TEMP DATAFILE 1 TEMP DATAFILE 2 TEMP DATAFILE 3
export TEMP DATAFILE 4 TEMP DATAFILE 5 TEMP DATAFILE 6
export TEMP_DATAFILE_7 TEMP_DATAFILE_8
```

Tools tablespace TOOLS TABLESPACE=/dev/did/rdsk/d10s7 export TOOLS TABLESPACE # 3 control file devices CONTROL FILE 1=/dev/did/rdsk/d12s3 CONTROL FILE 2=/dev/did/rdsk/d12s4 CONTROL FILE 3=/dev/did/rdsk/d12s5 export CONTROL FILE 1 CONTROL FILE 2 CONTROL FILE 3 # Service Configuration Device SRVM=/dev/did/rdsk/d11s5 export SRVM # Now the UNDO tables. There will be 1 UNDO tablespace per instance in the # cluster, having 5 datafiles per tablespace # Standard to use here is UNDOTBS\${NODEID} DATAFILE X, so UNDOTBS1 # is the UNDO space for NODE 1 # If clusters are not in use and this is raw device then UNDOTBS1 # only needs populating. UNDOTBS1 DATAFILE 1=/dev/did/rdsk/d9s0 UNDOTBS1 DATAFILE 2=/dev/did/rdsk/d9s1 UNDOTBS1 DATAFILE 3=/dev/did/rdsk/d9s2 UNDOTBS1 DATAFILE 4=/dev/did/rdsk/d9s3 UNDOTBS1 DATAFILE 5=/dev/did/rdsk/d9s4 export UNDOTBS1_DATAFILE_1 UNDOTBS1_DATAFILE_2 UNDOTBS1_DATAFILE_3 export UNDOTBS1 DATAFILE 4 UNDOTBS1 DATAFILE 5 # We require one of the following UNDOTBS sections PER cluster instance # The ** REQUIRED ** format is UNDOTBSX DATAFILE Y= where X is the instance # ID of the node defined in NODE X and \overline{Y} is the log file number UNDOTBS2 DATAFILE 1=/dev/did/rdsk/d9s5 UNDOTBS2 DATAFILE 2=/dev/did/rdsk/d9s6 UNDOTBS2 DATAFILE 3=/dev/did/rdsk/d9s7 UNDOTBS2 DATAFILE 4=/dev/did/rdsk/d10s0 UNDOTBS2 DATAFILE 5=/dev/did/rdsk/d10s1 export UNDOTBS2 DATAFILE 1 UNDOTBS2 DATAFILE 2 UNDOTBS2 DATAFILE 3 export UNDOTBS2 DATAFILE 4 UNDOTBS2 DATAFILE 5 # And the redo logs. The sizing is for \$REDO LOGS PER NODE redo logs per # node in the cluster, so this section requires \$CLUSTER INSTANCES * # \$REDO LOGS PER NODE to be complete. Naming standard is # redo\$NODEID X, for example RED01 1, RED01 2 ... REDO LOGS PER NODE=16 export REDO LOGS PER NODE REDO1 1=/dev/did/rdsk/d5s0 REDO1 2=/dev/did/rdsk/d5s1 REDO1 3=/dev/did/rdsk/d5s2 REDO1 4=/dev/did/rdsk/d5s3 REDO1 5=/dev/did/rdsk/d5s4 REDO1 6=/dev/did/rdsk/d5s5 REDO1 7=/dev/did/rdsk/d5s6 REDO1 8=/dev/did/rdsk/d5s7 REDO1_9=/dev/did/rdsk/d6s0 REDO1_10=/dev/did/rdsk/d6s1 REDO1_11=/dev/did/rdsk/d6s2 REDO1_12=/dev/did/rdsk/d6s3 REDO1 13=/dev/did/rdsk/d6s4 REDO1 14=/dev/did/rdsk/d6s5 REDO1 15=/dev/did/rdsk/d6s6 REDO1 16=/dev/did/rdsk/d6s7 export REDO1 1 REDO1 2 REDO1 3 REDO1 4

```
export REDO1_5 REDO1_6 REDO1_7 REDO1_8
export REDO1 9 REDO1 10 REDO1 11 REDO1 12
export REDO1 13 REDO1 14 REDO1 15 REDO1 16
# As with the UNDOTBS we require a set of redo logs per nodal instance in
# the cluster. The format ** REQUIRED ** is REDOX Y= where X is the instance
# ID of the node defined in NODE X and Y is the log file number
REDO2 1=/dev/did/rdsk/d7s0
RED02 2=/dev/did/rdsk/d7s1
RED02 3=/dev/did/rdsk/d7s2
REDO2 4=/dev/did/rdsk/d7s3
REDO2 5=/dev/did/rdsk/d7s4
REDO2 6=/dev/did/rdsk/d7s5
REDO2 7=/dev/did/rdsk/d7s6
REDO2_8=/dev/did/rdsk/d7s7
REDO2_9=/dev/did/rdsk/d8s0
REDO2_10=/dev/did/rdsk/d8s1
RED02_11=/dev/did/rdsk/d8s2
REDO2_12=/dev/did/rdsk/d8s3
REDO2_13=/dev/did/rdsk/d8s4
REDO2<sup>14=/dev/did/rdsk/d8s5</sup>
REDO2 15=/dev/did/rdsk/d8s6
RED02 16=/dev/did/rdsk/d8s7
export REDO2 1 REDO2 2 REDO2 3 REDO2 4
export REDO2 5 REDO2 6 REDO2 7 REDO2 8
export REDO2 9 REDO2 10 REDO2 11 REDO2 12
export REDO2 13 REDO2 14 REDO2 15 REDO2 16
# SMS Specific
SMF DATA DATAFILE=/dev/did/rdsk/d11s6
SMF_INDEX_DATAFILE=/dev/did/rdsk/d11s7
SMF_LOGS_DATAFILE_1=/dev/did/rdsk/d12s0
SMF_LOGS_DATAFILE_2=/dev/did/rdsk/d12s1
SMF LOGS INDEX DATAFILE=/dev/did/rdsk/d12s2
export SMF DATA DATAFILE SMF INDEX DATAFILE
export SMF LOGS DATAFILE_1 SMF_LOGS_DATAFILE_2
export SMF LOGS INDEX DATAFILE
```

Setting up ssh keys

Introduction

Some of the processes in SMS use ssh and scp to transfer data around the network. Consequently, ssh keys and permissions need to be set up on the relevant machines.

Procedure

Follow these steps to generate an automatic ssh access to a replication node.

Step	Action
1	Log into the SMS host as smf_oper.
2	Enter ssh smf@host
	where $host$ stands for the replicated node host, for example, XXSCP1

Step	Action
3	Run the ssh-keygen package.
	Example command: ssh-keygen
	Result: The script will display the following prompts one at a time:
	Enter file in which to save the
	<pre>key(/IN/service_packages/SMS/.ssh/id_rsa):</pre>
	Generating public/private rsa key pair.
	Enter passphrase(empty for no passphrase):
	Enter same passphrase again:
4	Press Enter to continue.
	Result: The ssh public key will be generated and saved in .ssh/id_rsa.pub.
5	Log into the replicated node host, for example, XXSCP1, as smf oper.
6	Append the content of the public key to authorized keys.
	Example command: cat .ssh/id rsa.pub >> .ssh/authorized keys
7	Test the ssh access on the replicated node.
	Example command: ssh smf_oper@ <i>host</i>

Checking the Installation

Introduction

Refer to these checking procedures to ensure that SMS has installed correctly.

The end of the smsSms installation process (both unclustered and clustered) specifies a script designed to check the installation just performed. They must be run from the command line.

Check unclustered SMS procedure

Follow these steps to ensure SMS has been installed on an unclustered SMS machine correctly.

Step	Action
1	Log in to SMS machine as root.
2	Check the following directory structure exists with subdirectories: /IN/service_packages/SMS /IN/html
3	Check both directories contain subdirectories and that all are owned by: smf_oper user (group oracle)
4	Log into the system as smf_oper.
	Note: This step is to check that the smf_oper user is valid.
5	Check that the permissions for smf_oper's .ssh directory are:
	Note: These permissions are required for the ssh keys to work correctly.

Step	Action	
6	Type s	sqlplus /
	No pass	sword is required.
	Note: T	his step is to check that the smf_oper user has valid access to the database.
7	Check t	he entries of the /etc/inittab file
	Inittah e	Intries reserved for SMS on SMS.
	a.	sms7 /IN/service packages/SMS/bin/smsMasterStartup.sh
	b.	(runs smsMaster)
	C.	sms9 /IN/service packages/SMS/bin/smsMergeDaemonStartup.sh
	d.	(runs smsMergeDaemon)
	e.	sms5
		/IN/service_packages/SMS/bin/smsAlarmDaemonSmsStartup.sh
	f.	(runs smsAlarmDaemon)
	g.	<pre>sms1 /IN/service_packages/SMS/bin/smsAlarmRelayStartup.sh</pre>
	h.	(runs smsAlarmRelay)
	i	sms6
		/IN/service_packages/SMS/bin/smsStatsThresholdStartup.sh
	j. ((runs smsStatsThreshold)
	k.	sms4
		/IN/service_packages/SMS/bin/smsReportSchedulerStartup.sh
	I.	
	m.	sms3 /IN/service packages/SMS/bin/smsReportsDaemonStartup.sh
	n.	(runs smsReportsDaemon)
	0.	sms2
		/IN/service_packages/SMS/bin/smsNamingServerStartup.sh
	р.	(runs smsNamingServer)
	q.	<pre>sms8 /IN/service_packages/SMS/bin/smsTaskAgentStartup.sh</pre>
	r.	(runs smsTaskAgent)
•		

8 Check that the processes listed in the process lists are running on the relevant machine. For a list of the processes which should be running, see Process list - unclustered SMP.

Check clustered SMS procedure

Follow these steps to ensure SMS has been installed on a clustered SMS machine correctly.

Step	Action
1	Log in to SMS machine as root.
2	Check the following directory structure exists with subdirectories:
3	Check both directories contain subdirectories and that all are owned by: smf_oper user (group oracle)
4	Log into the system as smf_oper.
	Note: This step is to check that the smf_oper user is valid.
5	Check that the permissions for smf_oper's .ssh directory are:

Step	Action
	dwrx
	Note: These permissions are required for the ssh keys to work correctly.
6	Type sqlplus / No password is required.
	Note: This step is to check that the smf_oper user has valid access to the database.
7	Check the entries of the /etc/inittab file. Inittab entries reserved for SMS on SMS:
	sms// / / / / / / / / / / / / / / / / /
8	Ensure the following shell scripts are configured to be run by the clustering software:
	 /IN/service_packages/SMS/bin/smsAlarmDaemonSmsCluster.sh (runs smsAlarmDaemon)
	 /IN/service_packages/SMS/bin/smsAlarmRelayCluster.sh (runs smsAlarmRelay)
	 /IN/service_packages/SMS/bin/smsStatsThresholdCluster.sh (runs smsStatsThreshold)
	 /IN/service_packages/SMS/bin/smsReportSchedulerCluster.sh (runs smsReportScheduler)
	 /IN/service_packages/SMS/bin/smsReportsDaemonCluster.sh (runs smsReportsDaemon)
	 /IN/service_packages/SMS/bin/smsNamingServerCluster.sh (runs smsNamingServer)
	 /IN/service_packages/SMS/bin/smsTaskAgentCluster.sh (runs smsTaskAgent)

9 Check that the processes listed in the process lists are running on the relevant machine.

Check SLC procedure

Follow these steps to ensure SMS has been installed on the SLC machine correctly.

Step	Action
1	Log in to SLC machine as root.
2	Check the following directory structure exists with subdirectories: /IN/service_packages/SLEE.
3	Check both directories contain subdirectories and that all are owned by: smf_oper user (group oracle)
4	Log into the system as smf_oper.
	Note: This step is to check that the smf_oper user is valid.

Step	Action
5	Check that the permissions for smf_oper's .ssh directory are:
	Note: These permissions are required for the ssh keys to work correctly.
6	Type sqlplus / No password is required. Note: This step is to check that the smf_oper user has valid access to the database.
7	Ensure that the required ACS triggers have been added to the database for the ACS_ADMIN oracle user.
8	Check the entries of the /etc/inittab file. Inittab entries reserved for SMS on SLC:
	 scp1 /IN/service_packages/SMS/bin/cmnPushFilesStartup.sh (runs cmnPushFiles) scp2 /IN/service_packages/SMS/bin/infMasterStartup.sh (runs infMaster) scp3 /IN/service_packages/SMS/bin/smsStatsDaemonStartup.sh (runs smsStatsDaemon) scp4 /IN/service_packages/SMS/bin/smsAlarmDaemonScpStartup.sh (runs smsAlarmDaemon) scp5 /IN/service_packages/SMS/bin/updateLoaderStartup.sh
	(IUIIS UPUALELUAUEI)

9 Check that the processes listed in the process lists are running on the relevant machine

Check other machines procedure

Follow these steps to ensure SMS has been installed correctly on machines other than SMSs or SLCs.

Step	Action
1	Log in to the machine as root.
2	Check the following directory structure exists with subdirectories: /IN/service_packages/SMS
3	Check both directories contain subdirectories and that all are owned by: smf_oper user (group oracle)
4	Log into the system as smf_oper.
	Note: This step is to check that the smf_oper user is valid.
5	Check that the permissions for smf_oper's .ssh directory are:
	Note: These permissions are required for the ssh keys to work correctly.
6	If a database has been installed on the machine, and SMS statistics has been configured to use the database, type $~\sqlplus$ /
	No password is required.

Step	Action
	Note: This step is to check that the smf_oper user has valid access to the database.
7	Ensure that the required SMS tables have been added to the database for the SMF oracle user.
8	Check the entries of the /etc/inittab file:
	Inittab entries reserved for SMS on SLC:
	1 ext8 /IN/service_packages/SMS/bin/smsStatsDaemonStartup.sh
	(runs smsStatsDaemon)
	2 ext9 /IN/service_packages/SMS/bin/smsAlarmDaemonStartup.sh
	(runs smsAlarmDaemon)
9	Check that the processes listed in the process lists are running on the relevant machine.

For a list of the processes which should be running, see *Process list - other machines* (on page 262).

Process list

If the application is running correctly, the following processes should be running on each SMS, started from the inittab:

- smsMaster
- smsMergeDaemon
- smsAlarmDaemon
- smsAlarmManager
- smsAlarmRelay
- smsStatsThreshold
- smsReportScheduler
- smsReportsDaemon
- smsNamingServer
- smsTaskAgent
- smsTrifDaemon

Process list - clustered SMS

If the application is running correctly, the following processes should be running on each SMS.

- smsMaster, started from the inittab.
- The following are started by the clustering software.
 - smsAlarmDaemon
 - smsAlarmManager
 - smsAlarmRelay
 - smsStatsThreshold
 - smsReportScheduler
 - smsReportsDaemon
 - smsNamingServer
 - smsTaskAgent
 - smsTrigDaemon

Process list - SLC

If the application is running correctly, the following processes should be running on each SLC, started from the inittab:

- infMaster
- updateLoader
- smsAlarmDaemon
- smsStatsDaemon
- cmnPushFiles

Process list - other machines

If the application is running correctly, the following processes should be running on each platform, started from the inittab:

- If alarms use replication, smsAlarmDaemon
- If statistics use replication, smsStatsDaemon

Check the SMS Administration Screens

Check that the SMS administration screens are working correctly. Use an internet browser to open the following web page:

http://smshostname
Where:

smshostname is the hostname of an SMS in the IN.

Launch the application using the WebStart link. For more information about using the SMS Java administration screens, see *Service Management System User's Guide*.

Check alarm replication

Follow these steps to check that alarm replication is functioning correctly.

Step	Action
1	Open the SMS Java administration screen.
2	Open the Operator Functions > Node Management screen.
3	Click Create.
	Result: This will create a replication.config file and distribute a copy to all the machines in the IN.
4	Check that the file exists on all the machines in the IN.
5	On each node in the IN, use smsLogTest to generate an error. For more information about smsLogTest, see <i>smsLogTest</i> (on page 220).
6	Open the Operator Functions > Alarm Management screen.
7	Check that the alarm has replicated from each node into the SMF_ALARM_MESSAGE table in the SMF.

Enabling index defragmentation

Once the installation process is completed, it is advisable to enable the index defragmentation facility, although it is not strictly necessary.

Note: This facility has a dependency on specific Oracle configuration settings which relate to the nature of deployment. For more information how to install the defragmentation script, see *Index defragmentation*.