

Oracle® Communications Network Charging and Control

Session Initiation Protocol (SIP) Protocol Implementation Conformance Statement



Release 15.0.0

October 2023

The Oracle logo, consisting of the word "ORACLE" in white, uppercase, sans-serif font, positioned on a solid red rectangular background.

ORACLE®

Copyright

Copyright © 2023, Oracle and/or its affiliates.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this is software or related documentation that is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, then the following notice is applicable:

U.S. GOVERNMENT END USERS: Oracle programs (including any operating system, integrated software, any programs embedded, installed or activated on delivered hardware, and modifications of such programs) and Oracle computer documentation or other Oracle data delivered to or accessed by U.S. Government end users are "commercial computer software" or "commercial computer software documentation" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, reproduction, duplication, release, display, disclosure, modification, preparation of derivative works, and/or adaptation of i) Oracle programs (including any operating system, integrated software, any programs embedded, installed or activated on delivered hardware, and modifications of such programs), ii) Oracle computer documentation and/or iii) other Oracle data, is subject to the rights and limitations specified in the license contained in the applicable contract. The terms governing the U.S. Government's use of Oracle cloud services are defined by the applicable contract for such services. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Inside are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. AMD, Epyc, and the AMD logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark of The Open Group.

This software or hardware and documentation may provide access to or information about content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services unless otherwise set forth in an applicable agreement between you and Oracle. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services, except as set forth in an applicable agreement between you and Oracle.

Contents

About This Documentv

Document Conventionsvi

Chapter 1

Compliance Statement.....1

Overview1

Messaging Manager - RFC 3428 Introduction1

Specification Sections 1 to 111

About This Document

Scope

This statement of compliance refers to the Internet Engineering Task Force (IETF) document:

- RFC 3428 Session Initiation Protocol (SIP) Extension for Instant Messaging.

Audience

This document is intended to be read by NCC staff. It has been prepared on the assumption that the reader is familiar with Messaging Manager as well as the IETF - SIP instant messaging capabilities.

Document Conventions

Typographical Conventions

The following terms and typographical conventions are used in the Oracle Communications Network Charging and Control (NCC) documentation.

Formatting Convention	Type of Information
Special Bold	Items you must select, such as names of tabs. Names of database tables and fields.
<i>Italics</i>	Name of a document, chapter, topic or other publication. Emphasis within text.
Button	The name of a button to click or a key to press. Example: To close the window, either click Close , or press Esc .
Key+Key	Key combinations for which the user must press and hold down one key and then press another. Example: Ctrl+P or Alt+F4 .
Monospace	Examples of code or standard output.
Monospace Bold	Text that you must enter.
<i>variable</i>	Used to indicate variables or text that should be replaced with an actual value.
menu option > menu option >	Used to indicate the cascading menu option to be selected. Example: Operator Functions > Report Functions
hypertext link	Used to indicate a hypertext link.

Specialized terms and acronyms are defined in the glossary at the end of this guide.

Compliance Statement

Overview

Introduction

This chapter explains the compliance of Messaging Manager with RFC 3428.

In this chapter

This chapter contains the following topics.

Messaging Manager - RFC 3428 Introduction	1
Introduction	1
Specification Sections 1 to 11	1

Messaging Manager - RFC 3428 Introduction

Overview

The Messaging Manager product itself does not support SIP. SIP support is provided by the SIP Call Agent (SCA) product.

Messaging Manager can support the SIP Extension for Instant Messaging when used in conjunction with the SCA product.

Where this document states **Provided by the SCA** it means that the feature is provided by the SCA product and that the SCA compliance document should be referenced. See *SCA SIP Compliancev01.00* document.

This document states the compliance of Messaging Manager with RFC 3428. In many cases RFC 3428 refers to sections in the following IETF documents:

- RFC 3261 SIP: Session Initiation Protocol
- RFC 2779 Instant Messaging / Presence Protocol Requirements

Where relevant these documents will be referenced.

Introduction

Statements of compliance with Section 1 through 11 of RFC 3428 follow.

Specification Sections 1 to 11

Introduction (1)

This section requires that the protocol (RFC 3428) be compliant with all the instant message requirements in RFC 2779 relevant to its scope of applicability.

Scope of Applicability (2)

Messaging Manager complies.

Messaging Manager supports the pager model only.

Overview of Operation (3)

Messaging Manager complies.

Next hop processing provided by the SCA.

UAC Processing (4)

Messaging Manager complies.

Messaging Manager sends MESSAGE requests with a body of type text/plain.

Messaging Manager does NOT send bodies of type message/cpim.

Messaging Manager does NOT initiate dialogs.

Messaging Manager does NOT insert Contact header fields into MESSAGE requests.

Messaging Manager sends a 202 Accepted response to indicate that a request has been successfully received and forwarded to the destination.

This section also requires compliance with Section 8.1 of RFC 3261.

RFC 3261 Section 8.1

Compliance with RFC 3261 Section 8.1 is stated below:

8.1.1 Generating the Request

Messaging Manager complies.

8.1.1.1 Request-URI

Messaging Manager complies.

8.1.1.2 To

Messaging Manager complies.

8.1.1.3 From

Messaging Manager complies.

8.1.1.4 Call-ID

Messaging Manager complies.

8.1.1.5 CSeq

Messaging Manager complies.

8.1.1.6 Max-Forwards

Messaging Manager complies.

8.1.1.7 Via

Messaging Manager complies.

Messaging Manager uses the UDP transport for SIP requests.

Via processing is provided by the SCA.

8.1.1.8 Contact

Messaging Manager complies.

8.1.1.9 Supported and Require

Messaging Manager complies.

8.1.1.10 Additional Message Components

Messaging Manager complies.

8.1.2 Sending the Request

Provided by the SCA.

8.1.3.1 Transaction Layer Errors

Provided by the SCA.

8.1.3.2 Unrecognized Responses

Messaging Manager does not comply.

Messaging Manager does NOT handle 1xx responses.

8.1.3.3 Vias

Messaging Manager does not comply.

Messaging Manager does NOT discard messages with more than one Via header.

8.1.3.4 Processing 3xx Responses

Messaging Manager does not comply.

Messaging Manager does NOT handle 3xx redirection responses.

8.1.3.5 Processing 4xx Responses

Messaging Manager does not comply.

Messaging Manager does NOT support the following 4xx responses that require a retry using a new request:

- 401 (Unauthorized)
- 407 (Proxy Authentication Required)
- 413 (Request Entity Too Large)
- 415 (Unsupported Media Type)
- 416 (Unsupported URI Scheme)
- 420 (Bad Extension)

Use of Instant Message URIs (5)

Messaging Manager complies.

Messaging Manager does NOT use the abstract Instant Message URI.

Proxy Processing (6)

Provided by the SCA.

UAS Processing (7)

Messaging Manager complies.

Messaging Manager does NOT respond with a final response immediately.

Messaging Manager does NOT insert a Contact header field into a 2xx response.

Messaging Manager returns a 202 (Accepted) response indicating that the message was accepted, but end to end delivery has not been guaranteed.

Messaging Manager sends MESSAGE requests with a body of type text/plain.

Messaging Manager does NOT send bodies of type message/cpim.

Messaging Manager does NOT indicate to the user that the message has expired.

Congestion Control (8)

Messaging Manager does not comply.

Method Definition (9)

Messaging Manager complies.

Messaging Manager complies with and uses the following header fields from Table 1 and 2 in RFC 3428:

Call-ID

Messaging Manager uses the following format when sending SIP requests:

- 'delivery receipt id@hostname'
where the delivery receipt id is provided by the incoming transaction, or
- 'timestamp-random number@hostname'
where timestamp and random number are 32-bit numbers in hexadecimal format.

Messaging Manager copies this value from the originating SIP request when sending SIP responses.

Content-Length

Messaging Manager sets this value to the size of the message body.

Content-Type

Messaging Manager sends SIP requests using the 'text/plain' media-type.

Messaging Manager supports the following charsets:

- ISO-8859-1 to ISO-8859-16
- US-ASCII, and
- UTF-8.

Messaging Manager will use one of the charsets above or will attempt to convert the content to UTF-8.

CSeq

Messaging Manager uses the value '1 MESSAGE' when sending SIP requests.

Messaging Manager copies this value from the originating SIP request when sending SIP responses.

Date

Messaging Manager uses the service center timestamp if provided by the originating transaction when sending SIP requests.

Messaging Manager does NOT use this header when sending SIP responses.

Expires

Messaging Manager uses the validity date if provided by the originating transaction when sending SIP requests.

Messaging Manager does NOT use this header when sending SIP responses.

From

Messaging Manager uses the originating address when sending requests.

Messaging Manager copies this value from the originating SIP request when sending responses.

Max-Forwards

Messaging Manager sets this value to 70 when sending requests.

Note: This value will be decreased by the SCA when the request is proxied through the SCA.

Messaging Manager copies this value from the originating SIP request when sending SIP responses.

Priority

Messaging Manager uses the priority indicator if provided by the originating transaction.

Messaging Manager does NOT use this header when sending SIP responses.

To

Messaging Manager uses the terminating address when sending requests.

Messaging Manager copies this value from the originating SIP request when sending SIP responses.

Via

Messaging Manager uses the destination address domain when sending requests.

Messaging Manager copies this value from the originating SIP request when sending SIP responses.

Example Messages (10)

Not relevant.

Security Considerations (11)

The following security considerations are noted:

11.1 Outbound Authentication

Messaging Manager does not comply.

11.2 SIPS URIs

Messaging Manager does not comply.

11.3 End-to-End Protection

Messaging Manager does not comply.

11.4 Replay Prevention

Messaging Manager does not comply.

11.5 Using message/cpim Bodies

Messaging Manager does not comply.