

# Oracle® Communications Convergent Charging Controller Messaging Manager Navigator Technical Guide



Release 15.0.0

October 2023

The Oracle logo, consisting of the word "ORACLE" in white, uppercase, sans-serif font, centered within a solid red square.

# Copyright

Copyright © 2023, Oracle and/or its affiliates.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this is software or related documentation that is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, then the following notice is applicable:

U.S. GOVERNMENT END USERS: Oracle programs (including any operating system, integrated software, any programs embedded, installed or activated on delivered hardware, and modifications of such programs) and Oracle computer documentation or other Oracle data delivered to or accessed by U.S. Government end users are "commercial computer software" or "commercial computer software documentation" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, reproduction, duplication, release, display, disclosure, modification, preparation of derivative works, and/or adaptation of i) Oracle programs (including any operating system, integrated software, any programs embedded, installed or activated on delivered hardware, and modifications of such programs), ii) Oracle computer documentation and/or iii) other Oracle data, is subject to the rights and limitations specified in the license contained in the applicable contract. The terms governing the U.S. Government's use of Oracle cloud services are defined by the applicable contract for such services. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Inside are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. AMD, Epyc, and the AMD logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark of The Open Group.

This software or hardware and documentation may provide access to or information about content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services unless otherwise set forth in an applicable agreement between you and Oracle. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services, except as set forth in an applicable agreement between you and Oracle.

# Contents

About This Document .....	v
Document Conventions .....	vi
<b>Chapter 1</b>	
<b>System Overview .....</b>	<b>1</b>
Overview .....	1
What is Messaging Manager Navigator? .....	1
<b>Chapter 2</b>	
<b>Configuration.....</b>	<b>3</b>
Overview .....	3
RIMS Configuration File .....	3
MAP .....	5
IS41 .....	8
Caching .....	11
Chassis Actions .....	13
<b>Chapter 3</b>	
<b>Background Processes .....</b>	<b>17</b>
Overview .....	17
Statistics .....	17
<b>Chapter 4</b>	
<b>About Installation and Removal .....</b>	<b>19</b>
Overview .....	19
Installation and Removal Overview .....	19
Checking the Installation .....	19



# About This Document

## Scope

The scope of this document includes all the information required to install, configure and administer the Messaging Manager Navigator application.

## Audience

This guide was written primarily for system administrators and persons installing, configuring and administering the Messaging Manager Navigator application. However, sections of the document may be useful to anyone requiring an introduction to the application.

## Prerequisites

A solid understanding of Unix and a familiarity with IN concepts are an essential prerequisite for safely using the information contained in this technical guide. Attempting to install, remove, configure or otherwise alter the described system without the appropriate background skills, could cause damage to the system; including temporary or permanent incorrect operation, loss of service, and may render your system beyond recovery.

Although it is not a prerequisite to using this guide, familiarity with the target platform would be an advantage.

This manual describes system tasks that should only be carried out by suitably trained operators.

## Related Documents

The following documents are related to this document:

- *MM Technical Guide*
- *MM User's Guide*

# Document Conventions

## Typographical Conventions

The following terms and typographical conventions are used in the Oracle Communications Convergent Charging Controller documentation.

Formatting Convention	Type of Information
<b>Special Bold</b>	Items you must select, such as names of tabs. Names of database tables and fields.
<i>Italics</i>	Name of a document, chapter, topic or other publication. Emphasis within text.
<b>Button</b>	The name of a button to click or a key to press. <b>Example:</b> To close the window, either click <b>Close</b> , or press <b>Esc</b> .
<b>Key+Key</b>	Key combinations for which the user must press and hold down one key and then press another. Example: <b>Ctrl+P</b> or <b>Alt+F4</b> .
Monospace	Examples of code or standard output.
<b>Monospace Bold</b>	Text that you must enter.
<i>variable</i>	Used to indicate variables or text that should be replaced with an actual value.
menu option > menu option >	Used to indicate the cascading menu option to be selected. Example: <b>Operator Functions &gt; Report Functions</b>
<a href="#">hypertext link</a>	Used to indicate a hypertext link.

Specialized terms and acronyms are defined in the glossary at the end of this guide.

# System Overview

## Overview

### Introduction

This chapter provides a high-level overview of the application. It explains the basic functionality of the system and lists the main components.

It is not intended to advise on any specific Oracle Communications Convergent Charging Controller network or service implications of the product.

### In this Chapter

---

This chapter contains the following topics.

What is Messaging Manager Navigator? ..... 1

## What is Messaging Manager Navigator?

### Introduction


Messaging Manager Navigator is a SLEE interface which caches as much of the HLR lookup information as possible. This reduces the amount of network traffic, and makes the HLR information available to other applications.

Messaging Manager Navigator performs a protocol specific HLR dip. It supports both IS-41 CDMA and MAP (1,2,3) messages. It supports cache maintenance commands from other processes for functions such as clearing/invalidating cache entries and updating cache entries. The cached HLR information is required by Messaging Manager to perform FDA.

**Note:** Throughout this manual there are references to RIMS. This is the name of the Messaging Manager Navigator program.

## SLC processes

Here is a diagram showing the Messaging Manager Navigator and HLR lookup processes on the SLC.





# Configuration

## Overview

### Introduction

This chapter explains the configuration of the RIMS section of the **eserv.config** file.

### In this chapter

---

This chapter contains the following topics.

RIMS Configuration File .....	3
MAP .....	5
IS41 .....	8
Caching .....	11
Chassis Actions .....	13

## RIMS Configuration File

### Example config file

Here is an example of the Messaging Manager Navigator config section (known as RIMS) of the **eserv.config**.

```
RIMS = {

    tcapInterfaceServiceKey = 42

    sleepTime = 100000

    hlrTimeout = 3

    hlrErrorMap = [
        { error = 1, permanent = true }
        { error = 32, permanent = false }
    ]

    MAP = {
        defaultMapVersionHlr = 3
        hlrErrorMap = [
            { error = 1, permanent = true }
            { error = 32, permanent = false }
            { error = 73, permanent = true }
        ]

        GT = ""
        PC = 17
        SSN = 9

        checkCacheForTcap = false

        ignoreMwStatusMCEF = true
    }
}
```

```

        forwardInformSC = false
    }

    IS41 = {
        MdnMinTranslation = [
            { fromNoa=306, prefix="3", min=4, max=32, remove=2, prepend="1111" }
            { fromNoa=0, prefix="00", min=4, max=32, remove=0, prepend="" }
            { fromNoa=0, prefix="0", min=1, max=32, remove=1, prepend="0032" }
            { fromNoa=0, prefix="", min=1, max=6, remove=0, prepend="" }
            { fromNoa=0, prefix="", min=1, max=32, remove=0, prepend="0032" }
            { fromNoa=1, prefix="", min=1, max=32, remove=0, prepend="00" }
            { fromNoa=2, prefix="", min=1, max=32, remove=0, prepend="0032" }
        ]

        GT = ""
        PC = 17
        SSN = 8

        checkCacheForTcap = false

        supportIS841 = false

        minHLRTransType = 3
        mdnHLRTransType = 14
    }

    # Cache tuning options
    cache = {
        size = 5000000

        defaultSuccessValidityPeriod = "01:00:00"
        defaultTransientFailureValidityPeriod = "00:30:00"
        defaultPermanentFailureValidityPeriod = "04:00:00"

        successValidityPeriods = {
            { prefix = "027", period = "01:30:00" }
            { prefix = "021", period = "00:45:00" }
        }
        transientFailureValidityPeriods = {
            { prefix = "027", period = "00:15:00" }
        }
        permanentFailureValidityPeriods = {
            { prefix = "027", period = "03:00:00" }
        }
    }

    ChassisActions = {
        RimsChassisAction = {
            rimsInterfaceName = "rimsIf"
            TON = "001"
            NPI = "001"
            allowGPRS = true
            timeout = 3
            timeoutTick = 3
            scaUseRedirect = false
        }
    }
}

```

## RIMS parameters

Here are the parameters for the main section of the RIMS config.

### hlrTimeout

**Syntax:** `hlrTimeout = secs`  
**Description:** Timeout period for queries to the HLR.  
**Allowed:** seconds  
**Default:**  
**Notes:**  
**Example:** `hlrTimeout = 3`

### sleepTime

**Syntax:** `sleepTime = microseconds`  
**Description:** Sleep time when there is no work to do.  
**Allowed:** microseconds  
**Default:**  
**Notes:**  
**Example:** `sleepTime = 10000`

### tcapInterfaceServiceKey

**Syntax:** `tcapInterfaceServiceKey = num`  
**Description:** SLEE service key of Hughes stack.  
**Allowed:**  
**Default:**  
**Notes:**  
**Example:** `tcapInterfaceServiceKey = 42`

## MAP

### Introduction

The RIMS config includes a sub-section for interacting with the MAP plug-in.

### IMSI store location

Destination fields for data from RIMS for IMSI are in the `callingImsi` or `calledImsi`.

### VMSC store location

Destination fields for data from RIMS for VMSC are in the `locationNum` or the `calledLocationNum`.

### SGSN store location

Destination fields for data from RIMS for SGSN is in the `callingSgsn` or the `calledSgsn`.

### Example MAP config

Here is an example configuration of the `MAP` subsection of the `RIMS` section.

```
MAP = {
    defaultMapVersionHlr = 3
```

```
hlrErrorMap = [
    { error = 1, permanent = true }
    { error = 32, permanent = false }
    { error = 73, permanent = true }
]

GT = ""
PC = 17
SSN = 9

checkCacheForTcap = false

ignoreMwStatusMCEF = true

forwardInformSC = false
}
```

### MAP parameters

Here are the MAP configuration parameters.

**Note:** GT, PC and SSN form the source address used by Messaging Manager Navigator when consulting a MAP HLR.

#### checkCacheForTcap

**Syntax:** `checkCacheForTcap = true|false`  
**Description:** Determines whether the RIMS cache will be checked for MAP SRISM messages.  
**Type:** Boolean  
**Allowed:** true, false  
**Default:** false  
**Notes:**  
**Example:** `checkCacheForTcap = false`

#### defaultMapVersionHlr

**Syntax:** `defaultMapVersionHlr = num`  
**Description:** MAP version used to query the HLR.  
**Allowed:**  
**Default:**  
**Notes:**  
**Example:** `defaultMapVersionHlr = 3`

#### forwardInformSC

**Syntax:** `forwardInformSC = true|false`  
**Description:** Prevent RIMS sending InformServiceCentre message to XMS  
**Type:** Boolean  
**Optionality:** Optional (default used if not set).  
**Allowed:**  
**Default:** false  
**Notes:**  
**Example:** `forwardInformSC = false`

## GT

<b>Syntax:</b>	<code>GT = "num"</code>
<b>Description:</b>	Originating Global Title used by the HLR to communicate back to Messaging Manager or Messaging Manager Navigator (RIMS).
<b>Allowed</b>	Valid global title number
<b>Default:</b>	
<b>Note:</b>	This parameter takes priority over PC or SSN match.
<b>Example:</b>	<code>GT = "62912425346"</code>

## hlrErrorMap

<b>Syntax:</b>	<pre> hlrErrorMap = [   {     error = int, permanent = true false   }   ... ]</pre>
<b>Description:</b>	Mapping of HLR responses to severity.
<b>Type:</b>	Array
<b>Allowed:</b>	
<b>Default:</b>	
<b>Notes:</b>	
<b>Example:</b>	<pre> hlrErrorMap = [   { error = 1, permanent = true }   ... ]</pre>

## ignoreMwStatusMCEF

<b>Syntax:</b>	<code>ignoreMwStatusMCEF= true false</code>
<b>Description:</b>	If true, SMSC will deliver the SMS even with MCEF flag set.
<b>Type:</b>	Boolean
<b>Optionality:</b>	Optional (default used if not set).
<b>Allowed:</b>	true, false
<b>Default:</b>	true
<b>Notes:</b>	
<b>Example:</b>	<code>ignoreMwStatusMCEF= true</code>

## PC

<b>Syntax:</b>	<code>PC = num</code>
<b>Description:</b>	Originating Point Code array of messages used by the HLR to communicate back to Messaging Manager or Messaging Manager Navigator (RIMS).
<b>Allowed</b>	Defined by Network Administrator
<b>Default:</b>	0
<b>Note:</b>	<ul style="list-style-type: none"> <li>• This parameter takes priority over SSN match.</li> <li>• To remove the point code from outgoing requests, set the PC value to 65535.</li> </ul>
<b>Example:</b>	<code>PC = 17</code>

SSN

<b>Syntax:</b>	<code>SSN = num</code>
<b>Description:</b>	Originating Subsystem Number of the messages used by HLR to communicate back to Messaging Manager or Messaging Manager Navigator (RIMS).
<b>Allowed</b>	Valid sub system number.
<b>Default:</b>	
<b>Note:</b>	
<b>Example:</b>	<code>SSN = 9</code>

## IS41

### Introduction

When Messaging Manager performs a RIMS query using the IS41 Protocol, RIMS uses a set of number rules to normalise the MDN to a MIN. The MIN is then sent to the HLR and used to locate the VMSC.

**Note:** This is the default action; however you can turn this off and allow RIMS to send the MDN to the HLR, rather than perform the conversion.

The RIMS config includes a sub-section for interacting with the IS-41 plug-in.

### MIN store location

Destination fields for data from RIMS for MIN are in the callingImsi or calledImsi.

### VMSC store location

Destination fields for data from RIMS for VMSC are in the locationNum or the calledLocationNum.

### IS41 Errors

ACCESS\_DENIED\_REASON\_Denied and ACCESS\_DENIED\_REASON\_Invalid will generate permanent failures.

The presence of any other value in the SMS Access Denied field will generate a transient failure.

### Example IS41 config

Here is an example configuration of the IS41 subsection of the RIMS section.

```
IS41 = {
  MdnMinTranslation = [
    { fromNoa=306, prefix="3", min=4, max=32, remove=2, prepend="1111" }
    { fromNoa=0, prefix="00", min=4, max=32, remove=0, prepend="" }
    { fromNoa=0, prefix="0", min=1, max=32, remove=1, prepend="0032" }
    { fromNoa=0, prefix="", min=1, max=6, remove=0, prepend="" }
    { fromNoa=0, prefix="", min=1, max=32, remove=0, prepend="0032" }
    { fromNoa=1, prefix="", min=1, max=32, remove=0, prepend="00" }
    { fromNoa=2, prefix="", min=1, max=32, remove=0, prepend="0032" }
  ]

  GT = ""
  PC = 17
  SSN = 8

  checkCacheForTcap = false
}
```

```

        supportIS841 = false

        minHLRTransType = 3
        mdnHLRTransType = 14
    }

```

## IS41 parameters

Here are the IS41 configuration parameters.

**Note:** GT, PC and SSN form the address used by Messaging Manager Navigator when consulting IS41 HLR.

### checkCacheForTcap

**Syntax:** `checkCacheForTcap = true|false`  
**Description:** Determines whether the RIMS cache will be checked for IS41 SMSReq messages.  
**Type:** Boolean  
**Allowed:** true, false  
**Default:** false  
**Notes:**  
**Example:** `checkCacheForTcap = false`

### GT

**Syntax:** `GT = "num"`  
**Description:** Originating Global Title used by the HLR to communicate back to Messaging Manager or Messaging Manager Navigator (RIMS).  
**Allowed:** Valid global title number  
**Default:**  
**Note:** This parameter takes priority over PC or SSN match.  
**Example:** `GT = "62912425346"`

### mdnHLRTransType

**Syntax:** `mdnHLRTransType = num`  
**Description:** The Global Title translation type to be used for lookups to the HLR when using an MDN.  
**Allowed:**  
**Default:** 14  
**Note:**  
**Example:** `mdnHLRTransType = 14`

### MdnMinTranslation

**Syntax:**

```

MdnMinTranslation = [
    {
        Number_Normalization_Rules_Parameters
    }
    ...
]

```

**Description:** Translates an MDN to MIN.  
**Type:** Array

**Allowed:**

**Default:**

**Notes:** This parameter uses Number Normalization rules to perform the translation. For information about the Number Normalization parameters shown in the example below, see *MM Technical Guide*.

**Example:**

```
MdnMinTranslation = [
    {
        fromNoa = 0,
        prefix = "3">,
        min = 4,
        max = 32,
        remove = 2,
        prepend = "0035"
    }
    ...
]
```

### minHLRTransType

**Syntax:** minHLRTransType = num

**Description:** The Global Title translation type to be used for lookups to the HLR when using an MIN.

**Allowed**

**Default:** 3

**Note:**

**Example:** minHLRTransType = 3

### PC

**Syntax:** PC = num

**Description:** Originating Point Code array of messages used by the HLR to communicate back to Messaging Manager or Messaging Manager Navigator (RIMS).

**Allowed** Defined by Network Administrator

**Default:** 0

**Note:**

- This parameter takes priority over SSN match.
- To remove the point code from outgoing requests, set the PC value to 65535.

**Example:** PC = 17

### SSN

**Syntax:** SSN = num

**Description:** Originating Subsystem Number of the messages used by HLR to communicate back to Messaging Manager or Messaging Manager Navigator (RIMS).

**Allowed** Valid sub system number.

**Default:**

**Note:**

**Example:** SSN = 9

### supportIS841

**Syntax:** supportIS841 = true|false

**Description:** Determines whether to send the MDN to the HLR, if there is an MDN available, rather than perform the conversion.



<b>Type:</b>	Boolean
<b>Allowed:</b>	true, false
<b>Default:</b>	false
<b>Notes:</b>	If set to true, HLR lookups will be used in preference to <code>MdnMinTranslation</code> .
<b>Example:</b>	<code>supportIS841 = false</code>

## Caching

### Introduction

Messaging Manager Navigator is a SLEE component which provides HLR lookup and caching. This component communicates with other SLEE components using the predefined RIMS protocol or MAP/IS-41 HLR lookups over TCAP.

Messaging Manager Navigator caches the results of the HLR queries. This information should be retained for different periods of time depending on its type (a real result, or a failure of some kind) and which network it belongs to.

The primary input of information to the RIMS cache is from the Messaging Manager Navigator HLR query responses, however it is possible to update the RIMS cache from other processes. This is useful for such things as invalidating any cached entry when a MAP-ALERT-SERVICECENTRE message is received, reinvigorating the cached entry when a delivery using that information works, or updating the VMSC based on incoming calls.

The RIMS cache has indexes over the MSISDN/MDN and IMSI/MIN for the same data, although both point to the same information.

### Cache operations

There are a number of things that is done to the cache data.

- Look up existing entries
- Add new entries
- If the cache is full, expire the oldest entries
- Update existing entries

**Note:** When a new element is added to the cache, its validity period is set from the configuration. The configuration is only consulted when an item is added, not every time it is updated.

A validity period of 00:00:00 means that an entry should not be added to the cache. If an element is not added to the cache for this reason, the update function (used for both additions and updates) will return false as though it already contained more relevant data for that key.

### Example caching config

Here is an example configuration of the `cache` section of RIMS.

```
RIMS = {
  cache = {
    size = 5000000

    defaultSuccessValidityPeriod = "01:00:00"
    defaultTransientFailureValidityPeriod = "00:30:00"
    defaultPermanentFailureValidityPeriod = "04:00:00"

    successValidityPeriods = {
```

```

        { prefix = "027", period = "01:30:00" }
        { prefix = "021", period = "00:45:00" }
    }
    transientFailureValidityPeriods = {
        { prefix = "027", period = "00:15:00" }
    }
    permanentFailureValidityPeriods = {
        { prefix = "027", period = "03:00:00" }
    }
}

```

### Cache parameters

Here are the Cache configuration parameters

defaultPermanentFailureValidityPeriod

**Syntax:** defaultPermanentFailureValidityPeriod = "*time*"

**Description:** Lifetime of permanent failure results not covered by a specific IMSI/MIN prefix.

**Allowed** HH:MM:SS

**Default:**

**Note:**

**Example:** defaultPermanentFailureValidityPeriod = "00:00:30"

defaultSuccessValidityPeriod

**Syntax:** defaultSuccessValidityPeriod = "*time*"

**Description:** Lifetime of successful results not covered by a specific IMSI/MIN prefix.

**Allowed** HH:MM:SS

**Default:**

**Note:**

**Example:** defaultSuccessValidityPeriod = "00:01:00"

defaultTransientFailureValidityPeriod

**Syntax:** defaultTransientFailureValidityPeriod = "*time*"

**Description:** Lifetime of transient failure results not covered by a specific IMSI/MIN prefix.

**Allowed** HH:MM:SS

**Default:**

**Note:**

**Example:** defaultTransientFailureValidityPeriod = "00:00:10"

permanentFailureValidityPeriods

**Syntax:** permanentFailureValidityPeriods = "*time*"

**Description:** Permanent failure validity period set per IMSI/MIN prefix.

**Allowed** HH:MM:SS

**Default:**

**Note:**

**Example:** permanentFailureValidityPeriods = "00:00:30"

`size`

**Syntax:** `size = int`  
**Description:** Maximum number of HLR responses to cache at any one time  
**Allowed**  
**Default:**  
**Note:** Value specified in bytes  
**Example:** `size = 100`

`successValidityPeriods`

**Syntax:** `successValidityPeriods = "time"`  
**Description:** Success validity period set per IMSI/MIN prefix.  
**Allowed** HH:MM:SS  
**Default:**  
**Note:**  
**Example:** `successValidityPeriods = "00:00:30"`

`transientFailureValidityPeriods`

**Syntax:** `transientFailureValidityPeriods = "time"`  
**Description:** Transient failure validity period set per IMSI/MIN prefix.  
**Allowed** HH:MM:SS  
**Default:**  
**Note:**  
**Example:** `transientFailureValidityPeriods = "00:00:30"`

## Chassis Actions

### Introduction

The RIMS config includes a `ChassisActions` sub-section.

### Example ChassisActions config

Here is an example configuration of the `ChassisActions` sub-section of the RIMS section.

```
ChassisActions = {
  RimsChassisAction = {
    rimsInterfaceName = "rimsIf"
    TON = "001"
    NPI = "001"
    allowGPRS = true
    timeout = 3
    timeoutTick = 3
    scaUseRedirect = false
  }
}
```

## RimsChassisAction parameters

Here are the parameters in the `RimsChassisAction` array of the `ChassisActions` section of the `eserv.config`.

### `allowGPRS`

<b>Syntax:</b>	<code>allowGPRS = true false</code>
<b>Description:</b>	Determines whether the network supports GPRS.
<b>Type:</b>	Boolean
<b>Allowed:</b>	true, false
<b>Default:</b>	true
<b>Notes:</b>	MAP node specific parameter
<b>Example:</b>	<code>allowGPRS = true</code>

### `NPI`

<b>Syntax:</b>	<code>NPI = "value"</code>
<b>Description:</b>	Specifies the Number Plan Indicator value that will be filled into the query key value, in the case that the query key to be used in one of the extension digits fields.
<b>Allowed</b>	Values: <ul style="list-style-type: none"> <li>• 000 = unknown</li> <li>• 001 = ISDN (E.163/E.164)</li> <li>• 003 = Data (X.121)</li> <li>• 004 = Telex (F.69)</li> <li>• 006 = Land mobile (E.212)</li> <li>• 008 = National</li> <li>• 009 = Private</li> <li>• 010 = ERMES</li> <li>• 013 = Point Code &amp; subscriber number</li> <li>• 014 = Internet (IP)</li> <li>• 018 = WAP</li> </ul>
<b>Default:</b>	"001"
<b>Note:</b>	The <code>NPI</code> should be set to the most likely <code>NPI</code> for an MSISDN or MDN, as it will be used as part of the query to Messaging Manager Navigator and the HLR.
<b>Example:</b>	<code>NPI = "001"</code>

### `rimInterfaceName`

<b>Syntax:</b>	<code>rimInterfaceName = "name"</code>
<b>Description:</b>	Controls the interface that the chassis action creates a SLEE dialog to.
<b>Allowed</b>	string - valid name of interface
<b>Default:</b>	"rimIf"
<b>Note:</b>	
<b>Example:</b>	<code>rimInterfaceName = "rimIf"</code>

### `scaUseRedirect`

<b>Syntax:</b>	<code>scaUseRedirect = true false</code>
<b>Description:</b>	Populate the SCA Address from the IDP Redirecting Party

**Type:** Boolean  
**Optionality:** Optional (default used if not set).  
**Allowed:** true, false  
**Default:** false  
**Notes:**  
**Example:** `scaUseRedirect = false`

#### timeout

**Syntax:** `timeout = secs`  
**Description:** Timeout if Messaging Manager Navigator does not reply.  
**Allowed:** seconds  
**Default:**  
**Notes:**  
**Example:** `timeout = 3`

#### timeoutTick

**Syntax:** `timeout = secs`  
**Description:** The length of a timeout monitoring period.  
**Allowed:** seconds. Minimum value is 1.  
**Default:**  
**Notes:** Changing this value will change the timeout for all SLEE based applications running on the same SLEE as Messaging Manager Navigator.  
**Example:** `timeout = 3`

#### TON

**Syntax:** `TON = "value"`  
**Description:** Specifies the Type of Number value that will be filled into the query key value, in the case that the query key to be used in one of the extension digits fields.  
**Allowed** Values:
 

- 000 = unknown
- 001 = international
- 002 = national
- 003 = network\_specific
- 004 = subscriber\_number
- 005 = alphanumeric
- 006 = abbreviated

**Default:** "001"  
**Note:** The TON should be set to the most likely TON for an MSISDN or MDN, as it will be used as part of the query to Messaging Manager Navigator and the HLR.  
**Example:** `TON = "001"`



# Background Processes

## Overview

### Introduction

This chapter explains the background processes that run for Messaging Manager Navigator.

### In this chapter

---

This chapter contains the following topics.

Statistics ..... 17

## Statistics

### Introduction

Messaging Manager Navigator gathers statistics when it receives queries, for example from MMX, and when it sends requests to the HLR.

When Messaging Manager Navigator can't respond to a query from its internal cache, it will ask the HLR for information using:

- in the case of GSM MAP, a SendRoutingInfoForSM request; or
- in the case of IS-41 and IS841, an SMSequest.

Messaging Manager Navigator statistics are generated by each SCP, and then transferred at periodic intervals to the Service Management Platform (SMP) for permanent storage and analysis.

An existing statistics system (smsStats) provides functions for the collection of basic statistical events. This is provided in the Oracle SMS application. Refer to the *SMS Technical Guide* for details.

### Statistics gathered

The incidence of 12 separate events is counted, classified under the following names.

`SMS_SET_ROUTING_INFO`

Incremented when Messaging Manager Navigator receives a RIMS update request.

`SMS_GET_ROUTING_INFO`

Incremented when Messaging Manager Navigator receives a RIMS query request.

`SMS_GET_ROUTING_INFO_SUCCESS`

Incremented when Messaging Manager Navigator returns a RIMS response with the status of 'successful'.

`SMS_GET_ROUTING_INFO_FAIL`

Incremented when Messaging Manager Navigator returns a RIMS response with a status other than 'successful'.

SMS\_MAP\_SRI\_SM\_ATTEMPT

Incremented whenever Messaging Manager Navigator attempts to send a MAP SendRoutingInfoForSM message to the HLR.

SMS\_MAP\_SRI\_SM\_TEMP\_ERR

Incremented when Messaging Manager Navigator receives a transient error response to a MAP SendRoutingInfoForSM message.

SMS\_MAP\_SRI\_SM\_PERM\_ERR

Incremented when Messaging Manager Navigator receives a permanent error response to a MAP SendRoutingInfoForSM message.

SMS\_MAP\_SRI\_SM\_TIMEOUT

Incremented whenever Messaging Manager Navigator waits too long for a response to a MAP SendRoutingInfoForSM message.

SMS\_IS41\_SMSREQ\_ATTEMPT

Incremented whenever Messaging Manager Navigator attempts to send an IS-(8)41 SMSRequest message to the HLR.

SMS\_IS41\_SMSREQ\_TEMP\_ERR

Incremented whenever Messaging Manager Navigator receives a transient error response to an IS-(8)41 SMSRequest message.

SMS\_IS41\_SMSREQ\_PERM\_ERR

Incremented whenever Messaging Manager Navigator receives a permanent error response to an IS-(8)41 SMSRequest message.

SMS\_IS41\_SMSREQ\_TIMEOUT

Incremented whenever Messaging Manager Navigator has to wait too long for a response to an IS-(8)41 SMSRequest message.



# About Installation and Removal

## Overview

### Introduction

This chapter provides information about the installed components for the Oracle Communications Convergent Charging Controller application described in this guide. It also lists the files installed by the application that you can check for, to ensure that the application installed successfully.

### In this Chapter

---

This chapter contains the following topics.

Installation and Removal Overview .....	19
Checking the Installation .....	19

## Installation and Removal Overview

### Introduction

For information about the following requirements and tasks, see *Installation Guide*:

- Convergent Charging Controller system requirements
- Pre-installation tasks
- Installing and removing Convergent Charging Controller packages

### RIMS packages

An installation of Messaging Manager Navigator includes the following packages, on the:

- SMS:
  - rimsSms
- SLC:
  - rimsScp

## Checking the Installation

### rimsScp installation check

On successful installation the rimsScp package will have installed the following binaries:

`IN/service_packages/RIMS/bin/RIMS`

The following shared libraries will have been installed:

`/IN/service_packages/RIMS/lib/librimsChassisActions.so`  
`/IN/service_packages/RIMS/lib/librimsMacroNodes.so`

### Unclustered rimsSms installation check

On successful installation the rimsSms package on an unclustered SMS will have created the following directories:

```
/IN/service_packages/RIMS  
/IN/service_packages/RIMS/lib  
/IN/service_packages/RIMS/tmp  
/IN/service_packages/RIMS/db
```

### Clustered rimsSms installation check

On successful installation the rimsSms package on a clustered SMS will have created the following directories:

```
/IN/service_packages/RIMS  
/IN/service_packages/RIMS/lib  
/IN/service_packages/RIMS/tmp
```