

Oracle Service Cloud

Cobrowse API Reference for Oracle Service Cloud

19A

19A

Part Number: F13359-01

Copyright © 2019, Oracle and/or its affiliates. All rights reserved

Authors: The Service Cloud Information Development Team

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display in any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this is software or related documentation that is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, the following notice is applicable:

U.S. GOVERNMENT END USERS: Oracle programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, delivered to U.S. Government end users are "commercial computer software" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, shall be subject to license terms and license restrictions applicable to the programs. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Xeon are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. AMD, Opteron, the AMD logo, and the AMD Opteron logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark of The Open Group.

This software or hardware and documentation may provide access to or information about content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services unless otherwise set forth in an applicable agreement between you and Oracle. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services, except as set forth in an applicable agreement between you and Oracle.

The business names used in this documentation are fictitious, and are not intended to identify any real companies currently or previously in existence.

Oracle customers that have purchased support have access to electronic support through My Oracle Support. For information, visit <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=info> or visit <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=trs> if you are hearing impaired.

Contents

Preface	i
<hr/>	
1 Introduction	1
Document Purpose	1
2 Cobrowse Application States	3
Application States	3
3 Cobrowse Methods and Properties	5
Methods and Properties	5
Default UI API	7
4 Cobrowse Events	9
Cobrowse.Events Methods	9

Preface

This preface introduces information sources that can help you use the application and this guide.

Using Oracle Applications

To find guides for Oracle Applications, go to the [Oracle Help Center](#).

Documentation Accessibility

For information about Oracle's commitment to accessibility, visit the [Oracle Accessibility Program website](#).

Videos included in this guide are provided as a media alternative for text-based topics also available in this guide.

Contacting Oracle

Access to Oracle Support

Customers can access electronic support through Oracle Support. For information, visit [Oracle Service Cloud Support](#) or visit [Accessible Oracle Support](#) if you are hearing impaired.

Comments and Suggestions

Please give us feedback about Oracle Applications Help and guides. You can complete one of the following surveys:

- For guides: [Oracle Service Cloud Documentation Feedback](#).
- For tutorials: [Oracle Service Cloud Tutorial Feedback](#).

1 Introduction

Document Purpose

To provide basic understanding of the Cobrowse API.

The document also provides information about the set of methods, options, and event types involved in establishing and maintaining a Cobrowse session.

2 Cobrowse Application States

Application States

The Cobrowse application states help you to understand the current state of the application.

N	Application State	Description	Available Functionality
1	INIT	Application is initializing (for example, after a page loads). At this point, it is not clear if there is another active Cobrowse session.	Checking application state (Cobrowse.API.Session.getState), subscribing to application events.
2	READY	Application finished initializing, no active Cobrowse session detected.	Checking application state (Cobrowse.API.Session.getState), subscribing to application events, starting Cobrowse session.
3	STARTING	Application is in the process of starting a Cobrowse session. No access code received yet.	Checking application state, subscribing to application events.
4	ACTIVE (all sub-states)	Cobrowse session in progress	Checking application state (Cobrowse.API.Session.getState), subscribing to application events, disconnecting the Cobrowse session.
	ACTIVE:WAIT	Cobrowse session ID generated - but no agent is connected to the session yet	
	ACTIVE:ACTIVE	ICB session is in progress, at least one agent is connected	
	ACTIVE:ESCALATING	Escalation to advanced mode is in progress	
	ACTIVE:ESCALATED	ACB session is in progress, at least one agent is connected	
5	DISCONNECTING	Application is in the process of terminating a Cobrowse session	Checking application state (Cobrowse.API.Session.getState), subscribing to application events.
6	ERROR	Fatal application or environment error encountered	Checking application state (Cobrowse.API.Session.getState)

3 Cobrowse Methods and Properties

Methods and Properties

The methods and properties listed below can be accessed using the Cobrowse object:


N	Method	Required Application States	Description
1	Cobrowse.ready([callback])	Any state	This asynchronous function signals to the caller when Cobrowse API is fully loaded and ready to use. If callback function is provided, it is called when the API is ready. Otherwise, this method returns a Promise which is resolved when the API is ready.
2	Cobrowse.API.checkEnvironment()	INIT, READY	<p>Performs an environment check and returns a JSON object identifying whether the environment supports Cobrowse.</p> <p>The following are the properties of the returned object:</p> <p>ICB(boolean)Indicates whether the environment supports HTML-based Cobrowse (instant mode)</p> <p>ACB(boolean) Indicates whether the environment supports advanced Cobrowse</p> <p>If both properties have the value as false, the environment will not support Cobrowse, and an attempt to start a Cobrowse session will not succeed.</p>
3	Cobrowse.API.setReportingId(params)	INIT, READY	<p>Identifies non-mandatory parameters for Cobrowse reporting.</p> <p>params is a JSON object. Supported properties:</p> <p>extKey (unique alphanumeric value which will be associated with the Cobrowse session and propagated to Cobrowse reporting).</p> <p>This function must be called before starting the Cobrowsing session.</p> <p>Example:</p> <pre>Cobrowse.API.setReportingId ({ "extKey": "xZ097Ab" });</pre>
4	Cobrowse.API.Session.start([params])	READY	<p>Sends a request to the Oracle servers to start a Cobrowse session. Success or failure of the request can be further tracked via the events mechanism.</p> <p>params is an optional parameter containing a JSON object.</p>

N	Method	Required Application States	Description
			<p>Supported properties:</p> <p>SID(alphanumeric value which will be used as a Cobrowse session identifier)</p> <p>return value: JSON object with two properties:</p> <p>result(Boolean type) indicates whether the session start was successfully initiated</p> <p>description contains error description (if any) which occurred when session was attempted to start</p> <p>Example:<code>Cobrowse.Session.start({"SID": "107343:ABC9877"});</code></p>
5	<code>Cobrowse.API.Session.stop([params])</code>	STARTING, ACTIVE	<p>Initiates a request to stop the Cobrowse session.</p> <p>params is an optional parameter containing a JSON object. Supported properties: reason (string value describing a disconnect reason).</p> <p>return value: JSON object with two properties.</p> <p>result (Boolean type) indicates whether the termination of the active session was successfully initiated</p> <p>description contains error description (if any) which occurred when session was attempted to stop</p>
6	<code>Cobrowse.API.Session.getState()</code>	INIT, READY, STARTING, ACTIVE, DISCONNECTING	<p>Returns string describing current state of the Cobrowse application. Please refer to Application States section for the description of possible return values.</p>
7	<code>Cobrowse.API.Session.accessCode</code>	ACTIVE	<p>A read-only property which returns Cobrowse access code as a string value when the Cobrowse session is in progress, or undefined if there is no active session</p>
8	<code>Cobrowse.API.Session.mode</code>	ACTIVE	<p>A read-only property which returns a string with the mode for the active Cobrowse session, or undefined if there is no session in progress. "ICB": HTML-based Cobrowse (instant mode);"ACB": advanced screen-sharing mode</p>
9	<code>Cobrowse.API.Session.startAdvancedMode()</code>	ACTIVE	<p>Switches ongoing session to the advanced mode. This function call may require opening a new browser window or downloading an application file. Unless it is triggered from a user-initiated event handler (like onclick or onkeydown), the new window (and thus the advanced mode) may be blocked by the browser.</p> <p>return value: JSON object with two properties.</p> <p>result (Boolean type) indicates whether the switch to advanced mode was successfully initiated</p>

N	Method	Required Application States	Description
			description contains error description (if any) which occurred during this attempt.
10	<code>Cobrowse.API.Session.SID</code>	ACTIVE	A read-only property which returns a session identifier. If SID value is specified at session start, it has to be an alphanumeric value and upto 200 characters long; if the SID value is not specified, it will be undefined.

Default UI API

The methods and properties related to UI management can be accessed using the `Cobrowse.API.DefaultUI`.

N	Method Name	Parameters	Description
1	<code>Cobrowse.API.DefaultUI.setLanguage(lang)</code>	<p>lang: string with a language tag</p> <p>The API supports two-letter language tags as defined in ISO 639-1, three-letter language tags as described in ISO 639-2, culture names composed from language and region identifiers as described in Microsoft API (https://www.microsoft.com/resources/msdn/goglobal/default.mspx) or its decimal LCID equivalents. If the API is given a language tag which doesn't match any supported standard, the API will attempt to parse it according to the RFC 4647, section 3.4 (https://tools.ietf.org/html/rfc4647#section-3.4) until it matches any of the known standards. If no match is obtained, the API will fallback to use the default language for the current deployment.</p>	<p>Causes default UI to reload in the specified language (from the list of supported languages).</p> <p>return value: true if lang is found in the list of supported languages or false otherwise.</p> <p> Note: Result true does not guarantee UI is actually loaded in the specified language. Loading is a separate asynchronous process.</p>
2	<code>Cobrowse.API.DefaultUI.getLanguage</code>		Returns string with LCID corresponding to the currently selected UI language
3	<code>Cobrowse.API.DefaultUI.expand()</code>		Causes launch pad to expand to imitate click on launch panel
4	<code>Cobrowse.API.DefaultUI.collapse()</code>		Causes launch panel to minimize back to a button

4 Cobrowse Events

Cobrowse.Events Methods

The events that can be accessed via Cobrowse.Events object supports some methods.

N	Method Name	Parameters	Description
1	listen(callback)	callback: pointer to a function which will be called when the event is dispatched	Adds a listener to the list of subscribers to the event. Example: Cobrowse.Events.SessionStarted.listen(function (evt) {console.log("The session started event fired, the 6-digit code is: " + evt.accessCode);});
2	removeListener(callback)	callback: pointer to a function which should be removed from the subscribers list	Removes a subscriber from the list of event listeners

Supported Events

The supported events can be accessed using the Cobrowse.Events object.

N	Event Name	Properties	Description
1	SessionStarting		This event is triggered before session start request is sent to Oracle servers. Listeners to this event, when triggered, will receive a JSON object with the following properties:
		event.SID	SID: If session was initiated by Chat or other external application, event.SID property will contain external alphanumeric session identifier. If the session was started by the end user, this value will be undefined.
		event.siteCode	siteCode: string with client Site ID
2	SessionStarted		This event is triggered when a Cobrowse session successfully starts. Listeners to this event, when triggered, will receive a JSON object with the following properties:
		event.accessCode	accessCode: string with the 6 digit access code for standalone Cobrowse
		event.SID	SID: string with an external alphanumeric session identifier for integrated Cobrowse

N	Event Name	Properties	Description
		event.mode	mode: string with one of two pre-defined values: "ICB" for HTML-based Cobrowse mode, or "ACB" for advanced Cobrowse mode
		event.siteCode	siteCode: string with client Site ID
3	SessionEnded		This event is triggered when a co-browsing session is ended. Listeners to this event, when triggered, will receive a JSON object with the following properties:
		event.reason	reason: will contain a string indicating why the session was ended. It can contain one of the pre-defined values: "USER_INITIATED": requested by the end user "USER_TIMEOUT": no agent connected within a reasonable time "NETWORK_TIMEOUT": connection was lost and could not be recovered within a reasonable time It can also contain an arbitrary disconnect reason value if the session was stopped via the API method Cobrowse.API.Session.stop , and the reason value was specified in the parameter to that method.
		event.accessCode	accessCode: string with the 6-digit access code for standalone Cobrowse,
		event.SID	SID: string with an external alphanumeric session identifier for integrated Cobrowse
		event.siteCode	siteCode: string with client Site ID
		event.agentCount	agentCount: number of currently connected agents
4	AgentConnected		The event is fired when a new agent connects to an ongoing session. Listeners to this event, when triggered, will receive a JSON object with the following properties:
		event.name	name: agent's display name
		event.id	id: unique agent ID
		event.accessCode	accessCode: string with the 6-digit access code for standalone Cobrowse
		event.SID	SID: string with an external alphanumeric session identifier for integrated Cobrowse
		event.siteCode	siteCode: string with client Site ID
5	AgentDisconnected		The event is fired when agent disconnects from the ongoing session. Listeners to this event, when triggered, will receive a JSON object with the following properties:
		event.name	name: agent's display name
		event.id	id: unique agent ID

N	Event Name	Properties	Description
		event.accessCode	accessCode: string with the 6-digit access code for standalone Cobrowse
		event.SID	SID: string with an external alphanumeric session identifier for integrated Cobrowse
		event.siteCode	siteCode: string with client Site ID
6	StateChanged		This event is fired on each change of the co-browsing application state which is described in Cobrowse.API.Session.getState(). This event may be used to monitor Cobrowse application state and session activity. Listeners to this event, when triggered, will receive a JSON object with the following properties:
		event.state	state: strings with new value of the co-browsing application state
		event.previousState	previousState: strings with previous value of the co-browsing application state
		event.accessCode	accessCode: string with the 6-digit access code for standalone Cobrowse
		event.SID	SID: string with an external alphanumeric session identifier for integrated Cobrowse
		event.siteCode	siteCode: string with client Site ID
7	NavigatingAway		Indicates that the client has clicked on a link which will navigate to a third-party website, and which will terminate the Cobrowse session. Listeners to this event, when triggered, will receive a JSON object with the following properties:
		event.url	url: URL of the page to which the user will be taken if clicked on that URL
		event.accessCode	accessCode: string with the 6-digit access code for standalone Cobrowse
		event.SID	SID: string with an external alphanumeric session identifier for integrated Cobrowse
		event.siteCode	siteCode: string with client Site ID

