

Oracle Warehouse Management Cloud

Schedule Job Setup

Release 21C



This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this is software or related documentation that is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, then the following notice is applicable:

U.S. GOVERNMENT END USERS: Oracle programs (including any operating system, integrated software, any programs embedded, installed or activated on delivered hardware, and modifications of such programs) and Oracle computer documentation or other Oracle data delivered to or accessed by U.S. Government end users are "commercial computer software" or commercial computer software documentation pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, reproduction, duplication, release, display, disclosure, modification, preparation of derivative works, and/or adaptation of i) Oracle programs (including any operating system, integrated software, any programs embedded, installed or activated on delivered hardware, and modifications of such programs), ii) Oracle computer documentation and/or iii) other Oracle data, is subject to the rights and limitations specified in the license contained in the applicable contract. The terms governing the U.S. Governments use of Oracle cloud services are defined by the applicable contract for such services. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Inside are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. AMD, Epyc, and the AMD logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark of The Open Group.

This software or hardware and documentation may provide access to or information about content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services unless otherwise set forth in an applicable agreement between you and Oracle. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services, except as set forth in an applicable agreement between you and Oracle.

Documentation Accessibility

For information about Oracle's commitment to accessibility, visit the Oracle Accessibility Program website.

Access to Oracle Support

Oracle customers that have purchased support have access to electronic support through My Oracle Support. For information, visit My Oracle Support or visit Accessible Oracle Support if you are hearing impaired.

Contents

Preface

1	How to Set Up Scheduled Jobs with Job Type	1
	Extract Job Types	1
	Extract All Job Type	5
	Generating Job Type	7
	Run Job Type	8
	SFTP GET and PUT	9
	Process Input Files	18
	Calculating Storage Billing by Cube for Locations	22
	Purge Job Type	23
	Auto-Verify IB Shipment	25

1 How to Set Up Scheduled Jobs with Job Type

This document provides details of setting up a Scheduled Job with different Job Type for Oracle Warehouse Management Cloud.

The Schedule Job consist different types of Job Type:

Extract Job Types

Extract All Job Type

Generating Job Type

Run Job Type

SFTP GET and PUT

Process Input Files

Calculating Storage Billing by Cube for Locations

Purge Job Type

Extract Job Types

This schedule job types extracts data from the source system and process to generate the record in required format.

The following table list different Extract Job Types and their job parameters to be set:

Job Type	Description
Extract Order	Extracts information pertaining to the order from the source database such as Order number, status, destination information and shipment details.
Extract IBLPN	Extracts information of the inventory received in the warehouse.
Extract IB Shipment	Extracts information about the inventory shipment received in the warehouse.
Extract Vendor	Extracts vendors details such as name, address, phone number and so on.
Extract PO	Extracts information about the purchase order and relevant details such as vendor and customer information, shipment details, and order quantity.
Extract OBLPNS	Extract information of the inventories that are shipped from the warehouse from source system.
Extract IB LPNS LOCK	Extracts information of the inbound LPNs that has locks applied on them.
Extract Inventory History	Extracts inventory history records for the orders.

Job Type	Description
Extract Active Inventory	Extracts information about every active inventory or items in the warehouse.
Extract Parcel Manifest	Extracts manifest information such as carrier, trailer number, schedule departure and delivery information.
Extract OB LOAD	Extracts information of an outbound load and also captures information such as externally planned load number, order number, route number and destination company.
Extract Item	Extracts header information about item(s) from the source system.

To setup the job type, do the following:

1. From the Scheduled Jobs screen, click **Create (+)**.
2. Enter the mandatory field. Refer to mandatory section for field description.
3. Select the specific Extract Job Type from the Job Type drop-down.

Job Number *

Job Type * ext

Schedule Name * Extract Active Inventory

Enabled Extract All

Schedule Type * Extract IB LPN

Every * Extract IB LPN Lock

Period * Extract IBShipment

Minute * Extract ITEM

Hour * Extract Inventory History

Day Of Week * Extract OB LOAD

Day Of Month * Extract OB LPNS

Month Of Year * Extract Order

Job Parameters Extract PO

Extract Parcel Manifest

Extract Vendor

Generate Inventory History Extract

4. Enter the Job Parameters. Refer to job parameter section for field description.
5. Click **Save** or **Save/New**.

For more information, please refer to OWM-ScheduleJob-v1-R21B.xlsx file.

Mandatory Field

This table lists the Mandatory field required to run the schedule job:

Mandatory Fields	Required Action from the User
Job Number	Enter a name for the schedule job your creating.
Job Type	Select the job type.

Mandatory Fields	Required Action from the User
Schedule Name	Name can be up to the customer
Enable	Must be check in order to run
Schedule Type	Can be set up to be Interval or Crontab
If set up as Interval	Your required to enter Every and Period field.
If set up as Crontab	Your required to enter Minute, Hour, Day of the week, Day of the Month, Month of the year, where: - Minute – 1 to 60 seconds - Hour - 0-24 hours - Day of the week - 0 to 6 (Sunday=0) - Day of the month - 1 to 31 - Month of year - 1 to 12

Job Parameter

This table lists the Job Parameter field required to run the Schedule job:

Job Parameter	Required Action from the User
Username	Name of the user responsible to run to schedule job within the facility/company.
Start hours back	Enter the start hour period you want the data to be extracted. For example, Let's say system clock is 02:00 AM of 05 of July, 2009, you set the interval for Every =1, Period = Hour and Start Hours back = 3, then the schedule job is run every 1 hour and the system starts extracting all the modified data from the start hour period (3 hours behind from the system's clock, i.e., 23:00 PM of 04 of July, 2009) till the stop hour period set in the job parameter. Note: The recommended clock is set to 24 hours format.
Stop hours back	Enter the stop hour period until when you want the data to be extracted. For example, Let's say system clock is 02:00 AM of 05 of July, 2009, you set your interval Every =1, Period = Hour and Stop hour back =1, then the schedule job is run every 1 hour and the system stops extracting all the modified data till the stop hour period (1 hour from the system's clock, i.e., 01:00 AM of 04 of July, 2009).

Job Parameter	Required Action from the User
	Note: Stop hours must not be greater than Start hours. An error is thrown "Stop time cannot be before start time", and the data will not be generated.
Delimiter	Users can use this delimiter to separate the data fields. By default, " " is set as delimiter. User's can define their own delimited for example, *.
Header Required	Whether we populate a header row at the beginning of the file. Valid value ("y" or "n").
Header Prefix	Enter the prefix of your choice. For example, Header prefix = ABC. Then the output generated will have [ABC][Comp][FAC][ORD] Note: The system has default prefix defined. If the header prefix is left blank, system uses the default prefix to generate the file in the following format: {Hdrprefix}{comp}{fac}_{user}_{from_time}_{to_time} For information on the default prefix, refer Default Prefix .
Detail Prefix	Enter prefix of your choice. The file format is as follows: {dtlprefix}{comp}{fac}_{user}_{from_time}_{to_time}
Now	This is for internal use only.
Debug	This is for internal use only.

Default Prefix

These are system coded prefix that are used by default while generating output file.

Note: User can define their own prefix by defining in the parameter fields. If no value is entered in the header/detail prefix field, system automatically uses the following default values.

Job Type	Header	Detail
Extract Order	ORH	ORD
Extract IBLPN	IBH (iblpn header)	IBD (iblpn detail)

Job Type	Header	Detail
Extract IB Shipment	ISH (Ib shipment header)	ISD (ib shipment detail)
Extract Vendor	VEN	
Extract PO	POH (for PO header)	POD (for PO detail)
Extract OBLPNS	LPH (oblpn header)	LPD (oblpn detail)
Extract IB LPNS LOCK	IBLPN_LOCK	
Extract Inventory History	XIHT	
Extract Active Inventory	ACT	
Extract Parcel Manifest	OPS (header)	OPL (detail)
Extract OB LOAD	OBS (header)	OBL (detail)
Extract Item	ITM	

Extract All Job Type

On selecting **Extra All** job, you need to specifically enter the following job parameters:

- Facility Code : Facility code id
- Company Code: Company code id
- Start day: example 1 for yesterday, 7 for seven days ago
- Stop day: example 1 for yesterday, 7 for seven days ago

Note: If you want to get all Extract data, you must set up a **Copy Files** Job Type. Refer to *Copy Files Job Type* for more information

Copy Files Job Type

The Oracle WMS Cloud allows you to copies all the fiels from the source folder path to the destination path folder provided in the job parameter.

To set up the schedule job type, do the following:

1. From the Scheduled Jobs screen, click Create (+).
2. Select Copy Files from the Job Type drop-down.

Job Parameters

Username

Source Folder Path

Destination folder path

File Pattern

Include Sub Folder Level 1

Encrypt

Encrypt Recipient

Decrypt

Send Acknowledgement File

3. Populate the rest of the required fields.
4. Click **Save**.

Job Parameter	Required Action from the User
Username	Valid user name for the facility.
Source Folder Path	\$LGF_FILES_HOME/interfaces/<company_code>/<fac_code>/output/ETL Replacing <company_code> with the actual company code and the <fac_code> with the actual facility code.
Destination Folder Path	Set up by client.
File Pattern	If you have only set up one of the extract and will like to copy this info, then the value should be: ○ Order > ORH (for order header) ORD (for order dtl) OR* (for both) ○ IBLPN > IBH (iblpn header) IBD (iblpn detail) IB* (for both) ○ IB Shipment > ISH (lb shipment header) ISL (ib shipment detail) IS* (for both) ○ Vendor > VEN (no detail) ○ PO > POH (for PO header) POD (for PO detail) PO* (for both)

Job Parameter	Required Action from the User
	○ OBLPNS > LPH (oblpn header) LPD (oblpn detail) LP* (for both) ○ IB LPNS LOCK > IBLPN_LOCK (no detail) ○ Inventory History > XIHT ○ Active Inventory > ACT_INV ○ Parcel Manifest > OPS (header) OPL (detail) OP*(for both) ○ OB LOAD > OBS (header) OBL (detail) OB*(for both) ○ Item > ITM (no detail) Note: To set more than 1 copy file, you need to set up the value to *.
Include Sub Folder Level 1	Not supported. Do Not Use.
Encrypt	Not supported. Do Not Use.
Encrypt Recipient	Not supported. Do Not Use.
Decrypt	Not supported. Do Not Use.
Send Acknowledgement file	Not supported. Do Not Use.

Generating Job Type

The Oracle WMS Cloud provides an ability in the system to generate output reports for the following job type via Generate Schedule Job.

- Generate Inventory Summary
- Generate Order Files
- Generate LPN Modes
- Generate OB LPN Billing Report
- Generate Inventory History Extract
- Generate Verify Shipment Alert
- Generate Custom Inventory Summary
- Generate IB Shipment Files
- Generate OB Load Files
- Generate Parcel Manifest Files
- Generate IHT by billing location type

To set up the Generate job type, do the following:

1. From the Scheduled Jobs screen, click Create (+).
2. Select the specific Generate Job Type from the Job Type drop-down.

Job Number *	
Job Type *	Gene ▼
Schedule Name *	<u>Generate</u> Custom Inventory Summary
Enabled	<u>Generate</u> IB Shipment Files
Schedule Type *	<u>Generate</u> IHT by billing location type
Every *	<u>Generate</u> Inventory History Extract
Period *	<u>Generate</u> Inventory Summary
Minute *	<u>Generate</u> LPN Modes
Hour *	<u>Generate</u> OB LPN Billing Report
Day Of Week *	<u>Generate</u> OB Load Files
Day Of Month *	<u>Generate</u> Order Files
Month Of Year *	<u>Generate</u> Parcel Manifest Files
Job Parameters	<u>Generate</u> Verify Shipment Alert

3. Enter the mandator field for selected job type. Refer to the *Mandatory Field* section for field description.
4. Configure the respective parameter for the selected Job Parameter – Refer to OWM-ScheduleJob-v1-R21A.xlsx file

Run Job Type

The Oracle WMS Cloud provides you an ability to execute and run template based schedule job via Run Job Type:

- Run Stage Interface
- Run Wave Template
- Run Work Order Wave Template
- Run Replenishment Template
- Run Report
- Run CC Task Template
- Run Wave Group Template
- Run Web Report
- Run Iblpn Report
- Run WMS WFM Interface
- Run Web Report Gen2

To set up the Run job type, do the following

1. From the Scheduled Jobs screen, click Create (+).
2. Select the specific Run Job Type from the Job Type drop-down.

Job Number *	
Job Type *	run
Schedule Name *	Run CC Task Template
Enabled	Run Iblpn Report
Schedule Type *	Run Replenishment Template
Every *	Run Report
Period *	Run Stage Interface
Minute *	Run WMS WFM Interface
Hour *	Run Wave Group Template
Day Of Week *	Run Wave Template
Day Of Month *	Run Web Report
Month Of Year *	Run Web Report Gen2
	Run Work Order Wave Template
Job Parameters	

3. Enter the mandator field for selected job type. Refer to the [Mandatory Field](#) section for field description.
4. Configure the respective parameter for the selected Job Parameter – Refer to OWM-ScheduleJob-v1-R21A.xlsx file.

SFTP GET and PUT

Oracle Warehouse Management (WMS) Cloud is discontinuing the SFTP site hosted by Oracle WMS Cloud (LogFire). The date for this shutdown is May 31, 2019. This was originally announced to customers last year. This document details alternatives that are available.

Prior to this change, customers were able to directly connect to the Oracle WMS Cloud SFTP site using their own username and password, to transfer input files for loading into the WMS or extracting output files. If you currently do not use this feature, then you can ignore this notification as it does not impact you.

Oracle recommends REST WebServices as the path forward for integration. This provides a much more real time integration, eliminates unnecessary scheduled jobs, and simplifies configuration. All interfaces available earlier via SFTP are available via REST WebServices. Please review the [Integration API](#) document for details. You can contact support if you do not have this document.

Customers that are not able to immediately switch to web services, have the option to host their own SFTP server (either their own or a third party one they can purchase on their own), and to transfer files into WMS and from WMS into their site. New scheduled jobs for this purpose were made available as of patch bundle 4a for version 18C and 9.0.0.

This document provides examples to show customers what needs to be configured, so they can get files from their new remote SFTP or put files from Oracle WMS Cloud to their new remote SFTP. In order to accomplish this, the new scheduled jobs have been created to allow you to either pull or get files:

- SFTP GET Files
- SFTP PUT Files

- Multi Facility - SFTP Put Files

These jobs are designed to be configured in addition to your current input interface processing jobs and output interface configuration. No changes to your input interface processing job should be required normally. For output interfaces, there is a recommended change that will be useful to do since it will be more efficient and faster (see Recommended Change in *SFTP PUT Files*) for more details.

To set up the schedule job type, do the following:

1. From the Scheduled Jobs screen, click Create (+).
2. Populate all required fields and select the specific SFTP Job Type from the Job Type drop-down.

Scheduled Job Configuration

The following example explains the configuration needed to set up these two new jobs.

For the purpose of this example we will pretend we have the following information:

- Current Oracle WMS Cloud SFTP information is:
 - Host: `sftp://sftp.wms.ocs.oraclecloud.com`
 - Username: Customer1
 - Password: 123Password!
- New Remote customer provided SFTP information is:
 - Host: `sftp://clienthost.com`
 - Username: myremotesftp
 - Password: 567Password!

SFTP GET Files

The SFTP GET Files job was created, so customers have the ability to “drop” files to the Oracle WMS Cloud site. It can be used for Inbound Interfaces, including Purchase Orders, Advance Shipment Notices, Orders, etc.

Example:

Moving Advance Shipment Notice (ASN) from your remote SFTP into your local SFTP.

You will place your ASN file in your new remote SFTP folder that you have assigned for your ASNs.

/Data/Input/ASN

Local site:

Data/Input/ASN

ASN

Output

Desktop

Documents

Downloads

IntelGraphicsProfiles

Filename	Filesize	Filetype	Last modified
..			
ISS0001.psv	31,232	PSV File	5/1/2019 1...
ISS0002.psv	32,768	PSV File	4/2/2019 1...

Job Parameters

Hostname

sftp://clienthost.com

SFTP User

myremotesftp

Password

.....

port

22

Remote Directory

data/input/asn

Local Directory

\$LGF_FILES_HOME/interfaces/<CO

File Search Pattern

ISS*

Job Parameter	Required Action from the User
Hostname	sftp://clienthost.com

Job Parameter	Required Action from the User
SFTP User	Your remote SFTP user. In our example: myremotesftp
Password	Your remote SFTP password. In our example: 567Password!
Port	22
Remote Directory	Your remote directory where you want us to get the files from. Please note this is case sensitive, so the scheduled job may failed if written incorrectly or if the path does not exist. In our example the path is: data/input/asn
Local Directory	This is the local directory where you want to drop the files, so they could be picked up by Oracle WMS Cloud. It is important this is configured correctly as it is case sensitive. Please refer to the SFTP Troubleshooting section for more details. If you already have input interface jobs setup earlier to process these files, then this path can be copied from that scheduled job as is. See the SFTP Troubleshooting section for more details on which section needs to be copied here: <code>\$LGF_FILES_HOME/interfaces/<COMPANY_CODE>/<FACILITY_CODE>/input/</code>
File Search Pattern	This file search pattern selects the specific files to be pick up. It is a mandatory field. In our example: ISS* You could provide: Only one file patter, multiple file patterns separated by a comma, a list of file matching patterns such as *.png or *.jpg separated by a comma. If there is a Folders in the directory to be searched, it will not be transferred. Once files are picked up by this job, they will get deleted from the remote site. Customers are urged to keep a backup copy in a different path, prior to dropping the files into the remote site

The SFTP Get Files job will pick up the files that start with ISS from your new remote sftp, and it will drop them into Cloud WMS in an internal location, so that they can be picked up and processed as usual.

SFTP PUT Files

The SFTP Put Files job allows Oracle WMS Cloud to communicate with the new remote hosted SFTP services to transfer files such as Order confirmation, inventory history, etc.

RECOMMENDED CHANGE: As of 9.0.0, Output Interface Configuration allows these files to be sent directly to external SFTP sites (instead of the internal LogFire SFTP) and that is the recommended way over using “SFTP PUT files” as it will skip the internal file transfer step and improve the overall processing speed. For example, if you currently have output interface configuration setup with “Logfire internal sftp” or “Logfire internal file location” as the target, these files get created in that location which is accessible via your LogFire SFTP username and password. You have the option to leave it that way and use the SFTP PUT files job to transfer the file to your external site, but you can skip this step and instead configure the output interface to use “External SFTP” and directly send the file out.

If you use SFTP to extract Web reports, then you will need to use SFTP PUT files.

Job Parameters

<i>Hostname</i>
sftp://clienthost.com
<i>SFTP User</i>
myremotesftp
<i>Password</i>
.....
<i>port</i>
22
<i>Remote Directory</i>
data/input/asn
<i>Local Directory</i>
\$LGF_FILES_HOME/interfaces/<CO
<i>File Search Pattern</i>
*.csv

Interface Protocol *	External SFTP
URL	
FTP Host	sftp://clienthost.com
FTP Port	22
Target Directory	data/Output/InventoryHistory
Username	myremotesftp
Password	*****
Encrypt File	☐
Encrypt Recipient	
Send Acknowledgement Email	☐
Max Retries	0
Retry Delay (Seconds)	10
Send Failure Email	☐

If instead, you prefer to use the SFTP PUT files job, please see details below.

Example: You have configured your Inventory History file to be drop in a specific target directory using Output Interface Configuration.

As you will not be able to get direct access to the Local SFTP folder, you will have to configure this SFTP Get Schedule Job, so Oracle WMS Cloud can drop the file to your assigned folder.

Job Parameters

Hostname

sftp://clienthost.com

SFTP User

myremotesftp

Password

.....

port

22

Remote Directory

data/Output/InventoryHistory

Local Directory

_CODE>/<FACILITY_CODE>/output/

File Search Pattern

*csv

Job Parameter	Required Action from the User
Hostname	sftp://clienthost.com
SFTP User	your remote SFTP user. In our example: myremotesftp
Password	your remote SFTP password. In our example: 567Password!
Port	22
Remote Directory	your remote directory where you want us to get the files from. Please note this is case sensitive, so the schedule job may failed if written incorrectly or if the path does not exist. In our example, the path is: data/Output/InventoryHistory
Local Directory	This is the local directory where you want to pick the files from the Oracle WMS Cloud inorder to drop at the customer's SFTP folder. It is important this is configured correctly as it is case sensitive. Please refer to the <i>SFTP Troubleshooting</i> section for more details. \$LGF_FILES_HOME/interfaces/<COMPANY_CODE>/<FACILITY_CODE>/output/
File Search Pattern	This file search pattern selects the specific files to be pick up. It is a mandatory field. In our example:*.csv (if you want to narrow down the files picked up by this job) You could provide:

Job Parameter	Required Action from the User
	Only one file patter, multiple file patterns separated by a comma, a list of file matching patterns such as *.png or *.jpg separated by a comma. If there is a Folders in the directory to be searched, it will not be transferred. Once files are picked up by this job, they will get deleted from the remote site. Customers are urged to keep a backup copy in a different path, prior to dropping the files into the remote site.

This job will pick up the files generated in Oracle WMS Cloud, and it will drop them in the path configured in your remote SFTP. The files picked up will be moved to an internal success folder, customers will not have direct access to it. Customers are urged to make additional backups on their side if needed.

Multi-Facility - SFTP PUT Files

Previously, the SFTP PUT files scheduled job supported only one facility. Also, some extra steps like copy files were required if the job had to send multiple files across different interfaces. As a result, the user would need to configure and maintain a large number of scheduled jobs, which could also overload the system.

To enhance ease and use of SFTP PUT, a new type of SFTP PUT Job, "Multi Facility - SFTP Put Files" is now available.

The following screen shows Multi-Facility – SFTP Put Files parameters:

Job Parameter	Required Action from the User
Hostname	Your remote SFTP hostname. For example: sftp://clienthost.com
SFTP User	Your remote SFTP user. For example: myremotesftp
Password	Your remote SFTP password. For example: 567Password!
Port	SFTP Port server. The default port is 22.
Remote Directory (Required)	Root folder where the file will be transferred to. At least one folder with an absolute path (/data for e.g.) must be provided.
Remote Sub Directory (Optional)	Sub directory under the Remote Directory where the file(s) will be transferred. If left blank, this job will replicate the WMS folder structure on the remote system, starting with each facility. The following are examples: • Left blank - files will be under <remote_directory>/facility/output/<interface type> • Specific Path is provided, say folder1/folder2 - Files will be under <remote_directory>/folder1/folder2 • Specific Path with keyword {fac}, say {fac}/files - Files will be under <remote_directory>/facility1/files, <remote_directory>/facility2/files etc. "{fac}" is a keyword which allows the end user to still maintain a facility-based separation of files without recreating the complete folder structure

Job Parameter	Required Action from the User
Interface (Required)	Represents a valid output interface. Attempting to provide an un-supported interface will give a meaningful error with the supported interfaces. Currently, the supported interfaces are: Note: These are case-sensitive. • orderverification • iblpn_info • custinvsummary • lpn_inventory • shipping • invsummary • distribution_info • pallet_shipping_info • cntrshipping • wavepickinfo • oblpn_shipping_info • ibshipment • manifest • invhistory • iblpn_report • route_instruction
File Search Pattern (Required)	Pattern to pick up files from WMS. for example, CINS*.csv or CINS*. Note: "," comma is NOT supported here. "CINS,IHT*" will not work.
Max files to transfer (Optional)	For one execution of the job maximum number of files to transfer. Leave blank to transfer all files
WMS username	User eligible for the COMPANY under which all facilities will be considered for this job.

SFTP Troubleshooting

- It is important to have read and write permissions checked in your folders in SFTP. Otherwise, the system will not be able to get files or send files to your folder.
- Configuration of the Local Directory is important. This is case sensitive. Please note that if the folder doesn't exist currently, it will be created. Also, for get SFTP jobs, typically this path will be the same as your existing input interface processing jobs.

- Set up of Process Input Files: If you are using Local Oracle WMS Cloud SFTP, you currently have this scheduled job set up. If you are setting up the new SFTP GET scheduled job, then you can copy the input folder path (highlighted below) to the Local directory section in SFTP GET scheduled jobs.

Job Parameters

<i>Input folder path</i>	\$LGF_FILES_HOME/...../input/
<i>Output folder path</i>	\$LGF_FILES_HOME/...../output/
<i>Username</i>	lgf
<i>Generate OK files</i>	no
<i>Process error files</i>	no
<i>Archive</i>	yes
<i>Upload data</i>	yes
<i>File Pattern</i>	ISS*,IPP*,IST*,IXR*,IBR*,VEN*,STR*

- What is the goal of using SFTP Put files with a target as a LogFire system? Put is intended to transfer files to the client system because they will not have a way to download the file.
- After a file has been processed it will be returned with a .tmp extension.

Process Input Files

The Process Input Files Job Type allows you to process different input files based on different interface types. For example, if you process an ISS file pattern, this will allow you to process an Inbound Shipment.

This schedule job is processed in two steps:

1. You need to run the SFTP Get schedule job to fetch the required files from the clients SFTP folder. Refer *SFTP GET Files* section.
2. Place the acquired files in the internal lgf Home folder.
3. To run the Process Input File:
 - a. Go to the Scheduled Jobs screen, click Create (+).
 - b. Select **Process Input Files** from the Job Type drop-down and populate all remaining Mandatory fields. Refer to *Mandatory Field* section for description.
 - c. Configure the respective parameter for the selected Job Parameter – Refer to OWM-ScheduleJob-v1-R21A.xlsx file.

Note: This job does not support XML files. You need to use the API - **Init Stage** to process any XML files.

Job Number *

Job Type *

Schedule Name *

Enabled

Schedule Type *

Every *

inpl

Process **Input** Files

Process **Input** Files Multi Facility

Process Input File - Job Parameter

After you complete all of the required Scheduled Job fields, you need to complete the Job Parameters fields.

Job Parameters

Input folder path

\$LGF_FILES_HOME

Output folder path

Username

User1

Generate OK files

no

Process error files

no

Archive

yes

Upload data

yes

File Pattern

*ISS

The following are the job parameters for the **Process Input Files** Job Type:

Job Parameter	Required Action from Users
Input Folder path	\$LGF_FILES_HOME/interfaces/<company_code>/<fac_code>/input/ Replacing <company_code> with the actual company code and the <fac_code> with the actual facility code.

Job Parameter	Required Action from Users
Output Folder path	Not required
Username	Enter the username that has access to this facility / company
Generate .ok files	No
Process .error files	No
Archive files	Yes
Upload data	Yes
File Pattern	ISS*,ITM*,IPP*,IST*,IXR*,IBR*,VEN*,STR*,POS*,ORR*,PLI*,ISH* (these are prefixes for the different interfaces types such as POS = Purchase Orders)

Note: Please note that we only support the interface format in the Interface Specs document Interface Specification 21B.

Process Input File - Multi-Facility

In cases where you need to process input files for multiple facilities, you can process Input Files for Multi Facilities via the Scheduled Jobs screen.

This schedule job is useful when you have multiple physical facilities that use Oracle WMS Cloud and you want to avoid creating multiple jobs for each facility.

1. Go to the Scheduled Jobs screen, and click Create (+).
2. Select **Process Input Files Multi Facility** from the Job Type drop-down and populate all remaining required fields.

Note: This job does not support XML files. You need to use the API - **Init Stage** to process any XML files.



Job Number *	
Job Type *	Input
Schedule Name *	Process Input Files
Enabled	Process Input Files Multi Facility
Schedule Type *	
Every *	

After you complete all of the required Scheduled Job fields for your **Process Input Files Multi Facility** Job Type, complete the Job Parameters fields. The following are the job parameters for the **Process Input Files Multi Facility** Job Type:

Input Folder path	\$LGF_FILES_HOME/interfaces/<company_code>/<fac_code>/input/
	Replacing <company_code> with the actual company code and the <fac_code> with the actual facility code.
Output Folder path	Not required
Username	Enter the username that has access to this facility / company.
Generate .ok files	No
Process .error files	No
Archive files	Yes
Upload data	Yes
File Pattern	ISS*,ITM*,IPP*,IST*,IXR*,IBR*,VEN*,STR*,POS*,ORR*,PLI*, ISH* (these are prefixes for the different interfaces types such as POS = Purchase Orders)
Facility Group	This field is an optional parameter. If you do not provide a Facility Group, by default, this job uses a common internal folder to process all of the data. If you need to create more than one Process Input Files Multi Facility Job Type, you must provide a text value (with no special characters or spaces.) Ideally, you should add the same value as the path on the input directly.
Job Parameter	Required Action from the User

If you are specifying a Facility Group, the following are two examples of what your Input folder paths should look like:

Example path:

Input Folder path:

`$LGF_FILES_HOME/interfaces/<COMPANY_CODE>/<FACILITY_CODE>/input/store`

Example path:

Input Folder path:

`$LGF_FILES_HOME/interfaces/<COMPANY_CODE>/<FACILITY_CODE>/input/fc`

Job Parameters

Input folder path	\$LGF_FILES_HOME
Output folder path	
Username	User1
Generate OK files	no
Process error files	no
Archive	yes
Upload data	yes
File Pattern	store

Calculating Storage Billing by Cube for Locations

Typically, on running this schedule job, the system determines the storage volume for each item per location and the corresponding IHT records are written. During the execution, the SJ checks for the inventory to determine all the available location types. Now, in case of volume, the SJ checks for the dimensions for cases/packs first and then units.

Following explains the sequential flow:

- If std case qty is populated for an item, then std case LxWxH is used for computing the volume. The total inventory for the item times standard case LxWxH.
- If std case qty is not populated for an item or any of the item's std case LxWxH is not populated, then items' std pack and pack LxWxH will be used.
- If std pack qty for an item is not populated or any of the item's std pack LxWxH is not populated, then items' unit LxWxH will be used in computing the volume.
- IHT-79 will be written for each item/location combination irrespective of batch/attributes/expiry date. Orig_Qty on the IHT will contain the volume computed above.

Note: Currently, WMS does not have UOM associated for dimensions. The value entered is assumed to be in same dimensions, the system does not perform UOM conversions as part of this job.

To set up the schedule job type, do the following:

1. From the Scheduled Jobs screen, click Create (+).
2. Select Calculate storage billing by Cube for location from the Job Type drop-down.

Job Number *

Job Type * Calculate storage billing by Cube 1 ▼

Schedule Name *

Enabled ☐

Schedule Type * ▼

Every *

Period * ▼

Minute *

Hour *

Day Of Week *

Day Of Month *

Month Of Year *

Job Parameters Username


3. Populate the required fields and Click **Save**.

Purge Job Type

You can use this schedule job to delete older records from a selected period of time with status.

There are two types of Purge schedule Job:

- Purge Stage Track Record - Deletes records that are older than a period of time and with status FAILED, PROCESSED, IGNORED or CANCELLED.
- Purge WMS Stage Record - Deletes the records from the wms_activity_track table which are older than a certain period of time and have SUCCESS or ERROR as status.



Job Number *

Job Type * purge

Schedule Name * Purge Stage Track Record

Enabled Purge WMS Activity Track

Schedule Type *

Every *

Period *

Purge Stage Track Record

To set up the Purge Stage Track Record schedule job type, do the following:

1. From the Scheduled Jobs screen, click Create (+).
2. Select Purge Stage Track Record Type drop-down.
3. Enter the **number_of_days** job parameter. Click **Save**.

Based on the value you enter in the number of days field, the system determines from which date-time should the records be deleted. That is, the system calculates the date-time based on the following equation:

Calculated Date-Time = Current Date-Time – Number of days.

On completion of deletion, the system writes logs on the total number of records being deleted from stage_track_record table.

Note: Default value of nbr_of_days = 5

For example,

You're current date-time (facility time) = 20-01-2020 and the nbr_of_days =5 days.

The Calculated Date-Time = 15/02/2020 (20/01/2020 – 5 days).

Purge WMS Stage Record

This schedule job calculates the WMS activity track based on the following facility parameter:

1. PURGE_NUMBER_OF_DAYS (default value = 30days)
2. PURGE_UNKNOWN_SKU (default value =N)
3. PURGE_UNKNOWN_USER (default value =N)
4. PURGE_UNKNOWN_TRANSACTION (default value =N)

To set up the Purge WMS Stage Record schedule job type, do the following:

1. From the Scheduled Jobs screen, click Create (+).
2. Select Purge WMS Stage Record Type drop-down.
3. Enter the Username and the facility field and Click **Save**.

- a. If facility params are set to 'Y', then unknown sku transaction records will be deleted along with success records based on Nbr of days set.
- b. If facility params are set to 'N', then unknown sku transaction records will not be deleted only success records will be deleted based on Nbr of days set

Based on the PURGE_NUMBER_OF_DAYS determined, the system calculates the Purge_calculated_date from the current date on the following equation:

$$\text{Purge_calculated_date} = \text{Current Date} - \text{PURGE_NUMBER_OF_DAYS}$$

If the parameter are set to Y, then the system behaves as follows:

- a. If PURGE_UNKNOWN_SKU = 'Y', all the records with date in create_ts older than the calculated Purge_till_date and with status ERROR, then unknown_sku_line_name that is not NULL is selected and deleted. While deleting the records, its corresponding records in the tran_wms_activity_xref table are deleted.
- b. If PURGE_UNKNOWN_USER = 'Y', all the records with date in create_ts older than the calculated Purge_till_date and status ERROR, then unknown_wms_user is not NULL is selected and deleted. While deleting the records its corresponding records in the tran_wms_activity_xref table are deleted.
- c. If PURGE_UNKNOWN_TRANSACTION = 'Y', all the records with date in create_ts older than the calculated Purge_till_date and status ERROR, then unknown_sub_option_name is not NULL is selected and deleted. While deleting the records its corresponding records in the tran_wms_activity_xref table are deleted.

After completion of all the above deletion procedure, all the records with date in create_ts (column in wms_activity_track table) older than the calculated Purge_till_date and status SUCCESS (with stat_code = 11) are selected and deleted. While deleting the records its corresponding records in the tran_wms_activity_xref table are deleted.

After every deletion, the system writes logs on the total number of records being deleted from wms_activity_track table for each part.

Auto-Verify IB Shipment

Auto-Verify IB Shipment will mark shipments that are received and due for verification for a specified duration (or 72 hours from the last LPN received time) as verified depending on the configuration of the scheduled job. Auto-Verify IB Shipment will not only mark shipments as verified, it will also generate the shipment verification output file. This is beneficial because you don't have to verify the shipment you are not interested in tracking the shipment.

To set up the Auto-verify IB Shipemt schedule job type, do the following:

1. From the Scheduled Jobs screen, click Create.
2. Select Auto-Verify IB Shipemt Type drop-down and and populate all remaining required fields.

Job Parameters

Username

Shipment Type

Time since last receipt (hrs)

Save Cancel Save/New Reset

3. Enter the following fields:

- a. Username: Enter the valid username (Login) in WMS should be provided.
- b. Shipment Type: This is a mandatory field. When the job is run, all IB Shipments that have matching Shipment Type and fulfill other criteria for verification will be considered. You can provide one or more shipment types with comma(,) as the delimiter.

Note:

- If no values are entered and you attempt to save the job, the system errors out.
- Asterisk [*] is not an accepted value for 'Shipment Type' field on the job parameter. You will have to provide the shipment type values explicitly. On saving the schedule job with Asterisk [*] shipment type will display an error message.
- Shipments without a shipment type will not be considered by this schedule job.

- c. Time since last receipt (hrs): The field indicates the time elapsed since the last LPN was received for the IB Shipment. This field accepts decimal values. If no value is provided, the system will consider 72 hrs as default duration.

Note: When configuring lesser values, make sure to provide the right shipment type and time since last shipment, otherwise the system could update the status while receiving is still in process.

NOTE: Shipments with Receiving Started and Receiving Complete status are eligible for verification. Also, shipments will not be verified if they have QC pending LPNs even if the shipments match the job parameter criteria for auto-verify through the scheduler.

4. Click **Save**