

# Oracle Warehouse Management Cloud

---

## **WFM REST API Guide**

24B



Oracle Warehouse Management Cloud  
WFM REST API Guide

24B

F96918-01

Copyright © 2024, Oracle and/or its affiliates.

Author: Oracle WMS Cloud Product Team

# Contents

<b>Get Help</b>	<b>i</b>
<hr/>	
<b>2 Overview</b>	<b>3</b>
Overview	3
<b>3 WFM Entity Operations (POST)</b>	<b>5</b>
WFM Entity Operations (POST)	5
<b>4 WFM Entity Operations (GET)</b>	<b>19</b>
WFM Entity Operations (GET)	19



# Get Help

There are a number of ways to learn more about your product and interact with Oracle and other users.

## Get Help in the Applications

Use help icons  to access help in the application. If you don't see any help icons on your page, click your user image or name in the global header and select Show Help Icons.

## Get Support

You can get support at [My Oracle Support](#). For accessible support, visit [Oracle Accessibility Learning and Support](#).

## Get Training

Increase your knowledge of Oracle Cloud by taking courses at [Oracle University](#).

## Join Our Community

Use [Cloud Customer Connect](#) to get information from industry experts at Oracle and in the partner community. You can join forums to connect with other customers, post questions, suggest *ideas* for product enhancements, and watch events.

## Learn About Accessibility

For information about Oracle's commitment to accessibility, visit the [Oracle Accessibility Program](#). Videos included in this guide are provided as a media alternative for text-based topics also available in this guide.

## Share Your Feedback

We welcome your feedback about Oracle Applications user assistance. If you need clarification, find an error, or just want to tell us what you found helpful, we'd like to hear from you.

You can email your feedback to [oracle\\_fusion\\_applications\\_help\\_ww\\_grp@oracle.com](mailto:oracle_fusion_applications_help_ww_grp@oracle.com).

Thanks for helping us improve our user assistance!



# 2 Overview

## Overview

This document is dedicated to the REST APIs that are supported by Oracle Workforce Management (WFM) Cloud. For more information about Restful Web Services, data input methodology, HTTP response, entity module, creating a resource using POST and obtaining resource representations using GET, refer WMS REST API Guide (navigate to *Logistics Cloud Suite* > Oracle Warehouse Management > WMS REST API Guide).

## End User License Agreement

This guide contains REST APIs that are specific to Oracle Workforce Management (WFM) Cloud. These APIs should only be used by customers that have purchased WFM license.





# 3 WFM Entity Operations (POST)

## WFM Entity Operations (POST)

This section details the POST entity operations for WFM.

### SKU Lines

The **SKU Line** API allows you to create one or more SKU Lines in WFM.

#### URL

```
POST ..lqfapi/v10/entity/sku_line/
```

#### Fields

Name	Required	Type	Default	Description
name	X	String		SKU line name
description	X	String		SKU line description

#### Request Body Example (JSON)

##### Instance Create

```
{
  "fields": {
    {
      "name": "Skechers Shoes1234_23",
      "description": "Skechers Shoes for Women12345_23"
    }
  }
}
```

##### Bulk Create

```
{
  "options": {
    "commit_frequency": 2
  },
  "fields": [
    {
      "name": "SKU LINE PUMA",
      "description": "SKU PUMA T-SHIRT"
    },
    {
      "name": "SKU LINE PUMA10",
      "description": "SKU PUMA T-SHIRT10"
    }
  ]
}
```

```
}

```

## Request Body Example (XML)

### Instance Create

```
<request>
<fields>
<name>SKU PUMA SHOES</name>
<description>SKU PUMA SHOES FOR MEN</description>
</fields>
</request>
```

### Bulk Create

```
<request>
<fields>
<list-item>
<name>SKU LINE School Uniform</name>
<description>SKU School Uniform Set for Kindergarden</description>
</list-item>
<list-item>
<name>SKU LINE School Uniform</name>
<description>SKU School Uniform Sets for 1 to 5th</description>
</list-item>
</fields>
<options>
<commit_frequency>2</commit_frequency>
</options>
</request>
```

**Note:** If the options parameter "commit\_frequency" is not provided in the payload, the behavior defaults to same behavior as commit\_frequency = 0, which is a all or nothing functionality. In other words, either all records are processed (if successful) or none of the records are processed even if 1 record fails validations.

## Goals for System (WMS) Activities

The **Prod Goal Line Group** API allows you to create one or more goals for system activities in WFM.

### URL

```
POST ..lqfapi/v10/entity/prod_goal_line_group/
```

### Fields

Name	Required	Type	Description
facility_id	X	Integer	Facility ID
work_area_activity_id	X	Integer	WMS Internal ID of the Work Area Activity

sku_line_group_id	X	Integer	WMS Internal ID of the SKU Line Group
cal_month_id	X	Integer	Values 1 through 12. 1 for JAN, 2 for FEB..... 12 for DEC
cal_year	X	Integer	Four-digit year YYYY; Example 2023
uom_id	X	String	WMS Internal ID of the UOM
uom_per_hr	X	Integer	Qty expected to be handled in one hour (This is the goal)
is_pre_pack	X	Boolean	True or False; Indicates if the item represents a pre-pack

## Request Body Example (JSON)

### Instance Create

```
{
  "fields": {
    "facility_id": 648,
    "work_area_activity_id": 573,
    "sku_line_group_id": 22,
    "cal_month_id": 3,
    "cal_year": 2023,
    "uom_id": 2,
    "uom_per_hr": 200,
    "is_pre_pack": true
  }
}
```

### Bulk Create

```
{
  "options": {
    "commit_frequency": 2
  },
  "fields": [
    {
      "facility_id": 648,
      "work_area_activity_id": 573,
      "sku_line_group_id": 22,
      "cal_month_id": 1,
      "cal_year": 2022,
      "uom_id": 1,
      "uom_per_hr": 750,
      "is_pre_pack": "FALSE"
    },
    {
      "facility_id": 648,
      "work_area_activity_id": 573,
      "sku_line_group_id": 22,
      "cal_month_id": 11,
      "cal_year": 2023,
      "uom_id": 1,
      "uom_per_hr": 750,
      "is_pre_pack": false
    }
  ]
}
```

```
  },
  {
    "facility_id": 648,
    "work_area_activity_id": 573,
    "sku_line_group_id": 22,
    "cal_month_id": 12,
    "uom_id": 1,
    "uom_per_hr": 750,
    "is_pre_pack": false
  }
]
```

## Request Body Example (XML)

### Instance Create

```
<request>
  <fields>
    <facility_id>648</facility_id>
    <work_area_activity_id>553</work_area_activity_id>
    <sku_line_group_id>22</sku_line_group_id>
    <cal_month_id>1</cal_month_id>
    <cal_year>2027</cal_year>
    <uom_id>1</uom_id>
    <uom_per_hr>25</uom_per_hr>
    <is_pre_pack>FALSE</is_pre_pack>
  </fields>
</request>
```

### Bulk Create

```
<request>
  <fields>
    <list-item>
      <facility_id>648</facility_id>
      <work_area_activity_id>475</work_area_activity_id>
      <sku_line_group_id>22</sku_line_group_id>
      <cal_month_id>1</cal_month_id>
      <cal_year>2023</cal_year>
      <uom_id>1</uom_id>
      <uom_per_hr>20</uom_per_hr>
      <is_pre_pack>FALSE</is_pre_pack>
    </list-item>
    <list-item>
      <facility_id>648</facility_id>
      <work_area_activity_id>292</work_area_activity_id>
      <sku_line_group_id>42</sku_line_group_id>
      <cal_month_id>2</cal_month_id>
      <cal_year>2026</cal_year>
      <uom_id>2</uom_id>
      <uom_per_hr>200</uom_per_hr>
      <is_pre_pack>TRUE</is_pre_pack>
    </list-item>
  </list-item>
</fields>
</request>
```

**Note:** If the options parameter "commit\_frequency" is not provided in the payload, the behavior defaults to same behavior as commit\_frequency = 0, which is a all or nothing functionality. In other words, either all records are processed (if successful) or none of the records are processed even if 1 record fails validations.

## Goals for VAS Activities

The **Prod Goal VAS** API allows you to create one or more goals for VAS (non-WMS) productive activities in WFM.

### URL

```
POST ..lqfapi/v10/entity/prod_goal_vas/
```

### Fields

Name	Required	Type	Description
facility_id	X	Integer	Facility ID
work_area_activity_id	X	Integer	WMS Internal ID of the Work Area Activity
sku_line_group_id	X	Integer	WMS Internal ID of the SKU Line Group
cal_month_id	X	Integer	Values 1 through 12. 1 for JAN, 2 for FEB..... 12 for DEC
cal_year	X	Integer	Four-digit year YYYY; Example 2023
uom_id	X	String	WMS Internal ID of the UOM
uom_per_hr	X	Integer	Qty expected to be handled in one hour (This is the goal)

### Fields

Name	Required	Type	Description
facility_id	X	Integer	Facility ID
work_area_activity_id	X	Integer	WMS Internal ID of the Work Area Activity
sku_line_group_id	X	Integer	WMS Internal ID of the SKU Line Group
cal_month_id	X	Integer	Values 1 through 12. 1 for JAN, 2 for FEB..... 12 for DEC
cal_year	X	Integer	Four-digit year YYYY; Example 2023

uom_id	X	String	WMS Internal ID of the UOM
uom_per_hr	X	Integer	Qty expected to be handled in one hour (This is the goal)

## Request Body Example (JSON)

### Instance Create

```
"fields": {
  "facility_id": 648,
  "work_area_activity_id":494 ,
  "sku_line_group_id": 22,
  "cal_month_id": 6,
  "cal_year": 2023,
  "uom_id": 1,
  "uom_per_hr": 50
}
```

### Bulk Create

```
{
  "options": {
    "commit_frequency": 2
  },
  "fields": [
    {
      "facility_id": 648,
      "work_area_activity_id": 513,
      "sku_line_group_id": 22,
      "cal_month_id": 3,
      "cal_year": 2023,
      "uom_id": 1,
      "uom_per_hr": 50
    },
    {
      "facility_id": 648,
      "work_area_activity_id": 513,
      "sku_line_group_id": 22,
      "cal_month_id": 4,
      "cal_year": 2023,
      "uom_id": 1,
      "uom_per_hr": 50
    },
    {
      "facility_id": 648,
      "work_area_activity_id": 513,
      "sku_line_group_id": 22,
      "cal_month_id": 5,
      "cal_year": 2023,
      "uom_id": 1,
      "uom_per_hr": 50
    }
  ]
}
```

## Request Body Example (XML)

### Instance Create

```
<request>
<fields>
<facility_id>648</facility_id>
<work_area_activity_id>513</work_area_activity_id>
<sku_line_group_id>42</sku_line_group_id>
<cal_month_id>2</cal_month_id>
<cal_year>2023</cal_year>
<uom_id>1</uom_id>
<uom_per_hr>20</uom_per_hr>
</fields>
</request>
```

### Bulk Create

```
<request>
<fields>
<list-item>
<facility_id>648</facility_id>
<work_area_activity_id>553</work_area_activity_id>
<sku_line_group_id>42</sku_line_group_id>
<cal_month_id>1</cal_month_id>
<cal_year>2023</cal_year>
<uom_id>1</uom_id>
<uom_per_hr>20</uom_per_hr>
</list-item>
<list-item>
<facility_id>648</facility_id>
<work_area_activity_id>553</work_area_activity_id>
<sku_line_group_id>42</sku_line_group_id>
<cal_month_id>2</cal_month_id>
<cal_year>2023</cal_year>
<uom_id>1</uom_id>
<uom_per_hr>20</uom_per_hr>
</list-item>
<list-item>
<facility_id>648</facility_id>
<work_area_activity_id>553</work_area_activity_id>
<sku_line_group_id>42</sku_line_group_id>
<cal_month_id>1</cal_month_id>
<cal_year>2023</cal_year>
<uom_id>1</uom_id>
</list-item>
<list-item>
<facility_id>648</facility_id>
<work_area_activity_id>553</work_area_activity_id>
</list-item>
<list-item>
<facility_id>648</facility_id>
<work_area_activity_id>553</work_area_activity_id>
<sku_line_group_id>42</sku_line_group_id>
<cal_month_id>4</cal_month_id>
<cal_year>2023</cal_year>
<uom_id>1</uom_id>
<uom_per_hr>20</uom_per_hr>
</list-item>
</fields>
<options>
<commit_frequency>2</commit_frequency>
</options>
</request>
```

**Note:** If the options parameter "commit\_frequency" is not provided in the payload, the behavior defaults to same behavior as commit\_frequency = 0, which is a all or nothing functionality. In other words, either all records are processed (if successful) or none of the records are processed even if 1 record fails validations.

## VAS Activity Data

The **Daily VAS Track** API allows you to create one or more VAS activity data records in WFM.

### URL

```
POST ..lqfapi/v10/entity/daily_vas_track/
```

### Fields

Name	Required	Type	Description
facility_id	X	Integer	Facility ID
work_area_id	X	Integer	WFM Internal ID of the Work Area
work_area_activity_id	X	Integer	WFM Internal ID of the VAS Activity (Work Area Activity of Type 'VAS')
cal_date	X	date	Date in DDMMYYYY format
team_id	O	integer	WFM Internal ID of the team; If this is populated, cw_user_id should not be sent (**Refer Note below)
cw_user_id	O	integer	WFM Internal ID of the user; If this is populated, team_id should not be sent (**Refer Note below)
qty	X	integer	Qty of items handled
uom_id	X	integer	WFM Internal ID of the UOM
Sku_line_group_id	X	integer	WFM Internal ID of the SKU Line Group

**Note:** To indicate empty values for team\_id or cw\_user\_id, the following conventions should be used:

- In JSON, omit the tag completely or send a value of null.
- In XML, omit the tag completely or send empty tags.



## Request Body Example (JSON)

### Instance Create

```
{
  "fields": {
    "facility_id": 648,
    "work_area_id": 516,
    "work_area_activity_id": 476,
    "cal_date": "2024-02-15",
    "team_id": null,
    "cw_user_id": 10754,
    "qty": 150,
    "uom_id": 2,
    "sku_line_group_id": 42
  }
}
```

### Bulk Create

```
{
  "options": {
    "commit_frequency": 2
  },
  "fields": [
    {
      "facility_id": 648,
      "work_area_id": 516,
      "work_area_activity_id": 553,
      "cal_date": "2024-02-13",
      "team_id": "",
      "cw_user_id": "33423391",
      "qty": 120,
      "uom_id": 1,
      "sku_line_group_id": 162
    },
    {
      "facility_id": 648,
      "work_area_id": 516,
      "work_area_activity_id": 553,
      "cal_date": "2024-02-13",
      "team_id": 180,
      "cw_user_id": "",
      "qty": 100,
      "uom_id": 1,
      "sku_line_group_id": 162
    }
  ]
}
```

## Request Body Example (XML)

### Instance Create

```
<request>
  <fields>
    <facility_id>648</facility_id>
    <work_area_id>1056</work_area_id>
    <work_area_activity_id>893</work_area_activity_id>
    <cal_date>2024-03-08</cal_date>
    <team_id>181</team_id>
    <cw_user_id></cw_user_id>
    <qty>15</qty>
  </fields>
</request>
```

```
<uom_id>2</uom_id>
<sku_line_group_id>42</sku_line_group_id>
</fields>
```

### Bulk Create

```
<request>
  <fields>
    <list-item>
      <facility_id>648</facility_id>
      <work_area_id>1056</work_area_id>
      <work_area_activity_id>476</work_area_activity_id>
      <cal_date>2024-02-13</cal_date>
      <team_id>440</team_id>
      <cw_user_id></cw_user_id>
      <qty>35</qty>
      <uom_id>1</uom_id>
      <sku_line_group_id>2</sku_line_group_id>
    </list-item>
    <list-item>
      <facility_id>648</facility_id>
      <work_area_id>516</work_area_id>
      <work_area_activity_id>478</work_area_activity_id>
      <cal_date>2024-02-13</cal_date>
      <team_id></team_id>
      <cw_user_id>787</cw_user_id>
      <qty>350</qty>
      <uom_id>3</uom_id>
      <sku_line_group_id>249</sku_line_group_id>
    </list-item>
  </fields>
  <options>
    <commit_frequency>2</commit_frequency>
  </options>
</request>
```

**Note:** If the options parameter "commit\_frequency" is not provided in the payload, the behavior defaults to same behavior as commit\_frequency = 0, which is a all or nothing functionality. In other words, either all records are processed (if successful) or none of the records are processed even if 1 record fails validations.

## Clock In/Out

The **Clock** API allows you to create one or more clock records in WFM. Unlike other REST APIs, this API does not post information directly to the main view (Track Record) for clock data. Instead, records are posted to Stage Record tab of Clock in the Input Interfaces view. The scheduled job "Process Stage Track Record" validates and moves these records to Track Record at scheduled intervals. You can choose to trigger the scheduled job immediately as a part of the API request, using the `async_flg` parameter on the request.

### URL

```
POST ..lqfapi/v10/stage_track_record/clock_inout/
```

### Request Body

- **message\_id** - Mandatory field of string type that would uniquely identify a payload. Max length – 50

- **async\_flg** - true/false; default true
  - When false:
    - Posts data to Stage Record of Clock Input Interface and triggers "Process Stage Track Record" immediately after.
    - If all records are processed successfully, response 204 "No Content" is returned with no response body. All the records show up in Track Record view.
    - If one or more records fail validations, response 400 "Bad Request" is returned with the count of failed records in the response. Since clock records need to be sequential and are dependent on other clock records (such as facility clock-in before work area clock-in), no records will be processed after the first failure has been encountered.

**Note:** It is advisable not to use `async_flg = false` if you intend to post large volume of records since the calling system may have to wait for considerable time to receive a response from WFM.

- When true:
  - Posts data to Stage Record of Clock Input Interface
  - Returns response 202 - "Accepted" with no response body.
  - Posted records remain in Stage Record of Clock Input Interface for further processing.
- **cico\_data** - The table below describes the fields within this parameter:

Name	Required	Type	Description
facility_code	X	String	Facility code
univ_id_1	C	String	Employee ID of the user that needs to be clocked. Mandatory for all cico_types except F7 and F8. If F7 or F8, either univ_id_1 or team should be provided, not both.
cico_ts	X	DateTime	Clock in/out date time  Format: YYYYMMDDHHMMSS Example: 20190727052020
cico_type	X	String	Valid Values: F1, F2, F3, F4, F5, F6, F7, F8, F9, F10  F1 - Facility Clock In  F2 - Break Clock In  F3 - Break Clock Out  F4 - Facility Clock Out  F5 - Work Area Clock In  F6 - Work Area Clock Out

			<p>F7 - VAS Activity Clock In</p> <p>F8 - VAS Activity Clock Out</p> <p>F9 - Manual Activity Clock In</p> <p>F10 - Manual Activity Clock Out</p>
originating_system	X	String	<p>Valid Values: M and S</p> <p><b>M</b> - M is used to create new data. If M is sent for data that already exists, the record fails to be processed</p> <p><b>S</b> - S is used to update existing data. If S is sent for data that doesn't exist, the record is inserted as new data.</p> <p><b>Note:</b> This check is done by "Process Stage Track" process.</p>
work_area	C	String	<p>Work Area Code. Required when cico_type is F5, F6, F7, F8, F9, F10.</p> <p>If F7 or F8, the work area code should be associated to the VAS activity.</p> <p>If F9 or F10, the work area code should be associated to the manual activity.</p>
break	C	String	<p>Name of the break taken by employee. Required when cico_type is F2 or F3.</p>
activities	C	String	<p>Work Area Activity Code of the VAS or Manual activity. Required when cico_type is F7, F8, F9, F10.</p>
team	C		<p>Required only for F7 and F8, if univ_id_1 is not provided. If univ_id_1 is provided, this field should not be populated.</p>

## Request Body Example (JSON)

### Instance Create

```
{
  "message_id": 12345,
  "async_flg": false,
  "cico_data": [{
    "facility_id_code": "QATST01",
    "univ_id_1": "1115472",
    "cico_ts": "20230505063027",
    "cico_type": "F7",
    "originating_system": "M",
    "work_area": "VASWABN",
    "activities": "BNVASACT01",
    "team": ""
  }]
}
```

### Bulk Create

```
{
  "message_id": 12345,
  "async_flg": false,
  "cico_data": [
    {
      "facility_id_code": "QATST01",
      "univ_id_1": "",
      "cico_ts": "20230505063027",
      "cico_type": "F7",
      "originating_system": "M",
      "work_area": "VASWABN",
      "activities": "BNVASACT01",
      "team": "T345"
    },
    {
      "facility_id_code": "QATST01",
      "univ_id_1": "",
      "cico_ts": "20230505072014",
      "cico_type": "F8",
      "originating_system": "M",
      "work_area": "VASWABN",
      "activities": "BNVASACT01",
      "team": "T345"
    }
  ]
}
```

## Request Body Example (XML)

### Instance Create

```
<request>
  <message_id>12345</message_id>
  <async_flg>true</async_flg>
  <cico_data>
    <list-item>
      <facility_code>QA3PLEST</facility_code>
      <univ_id_1>12453</univ_id_1>
      <cico_ts>20230510092030</cico_ts>
      <cico_type>F9</cico_type>
      <originating_system>M</originating_system>
      <work_area>MISC</work_area>
    </list-item>
  </cico_data>
</request>
```

```
<break></break>
<activities>Maintenance</activities>
</list-item>
</cico_data>
</request>
```

### Bulk Create

```
<request>
  <message_id>12345</message_id>
  <async_flg>true</async_flg>
  <cico_data>
    <list-item>
      <facility_code>QA3PLEST</facility_code>
      <univ_id_1>23145</univ_id_1>
      <cico_ts>20230510092030</cico_ts>
      <cico_type>F9</cico_type>
      <originating_system>M</originating_system>
      <work_area>MISC</work_area>
      <break></break>
      <activities>Maintenance</activities>
    </list-item>
    <list-item>
      <facility_code>QA3PLEST</facility_code>
      <univ_id_1>23145</univ_id_1>
      <cico_ts>20230510104511</cico_ts>
      <cico_type>F10</cico_type>
      <originating_system>M</originating_system>
      <work_area>MISC</work_area>
      <break></break>
      <activities>Maintenance</activities>
    </list-item>
  </cico_data>
</request>
```

# 4 WFM Entity Operations (GET)

## WFM Entity Operations (GET)

This section overviews the GET Entity Operations for WFM.

### WMS Activity Entities

The **WMS Activity** view captures activities performed by users on the warehouse floor using Oracle Cloud Warehouse Management System (WMS). The following APIs can be used to get relevant **WMS Activity** data.

**Note:** As of release 24B, only operations performed using WMS RF Transactions are written to WMS Activity. In future releases, support will be extended to operations performed using WMS PWA App and WMS REST APIs.

#### WMS Activity URLs

Check for the existence of the resource:

```
HEAD .../lgfapi/v10/entity/wms_activity/{id}
```

Fetch paginated results:

```
GET .../lgfapi/v10/entity/wms_activity/
```

Fetch non-paginated result by specific 'ID':

```
GET .../lgfapi/v10/entity/wms_activity/{id}
```

#### WMS Activity Dtl URLs

Check for the existence of the resource:

```
HEAD .../lgfapi/v10/entity/wms_activity_dtl/{id}
```

Fetch paginated results when users use the following URL:

```
GET .../lgfapi/v10/entity/wms_activity_dtl/
```

Fetch non-paginated result by specific 'ID'

```
GET .../lgfapi/v10/entity/wms_activity_dtl/{id}
```

#### WMS Activity Code URLs

Check for the existence of the resource:

```
HEAD .../lgfapi/v10/entity/wms_activity_code/{id}
```

Fetch paginated results when users use the following URL:

```
GET .../lgfapi/v10/entity/wms_activity_code/
```

Fetch non-paginated result by specific 'ID'

```
GET .../lgfapi/v10/entity/wms_activity_code/{id}
```

## WMS Activity Status URLs

Check for the existence of the resource:

```
HEAD .../lgfapi/v10/entity/wms_activity_status/{id}
```

Fetch paginated results when users use the following URL:

```
GET .../lgfapi/v10/entity/wms_activity_status/
```

Fetch non-paginated result by specific 'ID'

```
GET .../lgfapi/v10/entity/wms_activity_status/{id}
```

## WMS Activity Track Entities

As a first step, the **WMS WFM Interface** scheduled job moves WMS data from **WMS Activity** to **WMS Activity Track** view. The following APIs can be used to get relevant **WMS Activity Track** data.

### WMS Activity Track URLs

Check for the existence of the resource:

```
HEAD .../lgfapi/v10/entity/wms_activity_track/{id}
```

Fetch paginated results:

```
GET .../lgfapi/v10/entity/wms_activity_track/
```

Fetch non-paginated result by specific 'ID':

```
GET .../lgfapi/v10/entity/wms_activity_track/{id}
```

### WMS Activity Track Dtl URLs

Check for the existence of the resource:

```
HEAD .../lgfapi/v10/entity/wms_activity_track_dtl/{id}
```

Fetch paginated results when users use the following URL:

```
GET .../lgfapi/v10/entity/wms_activity_track_dtl/
```

Fetch non-paginated result by specific 'ID'

```
GET .../lgfapi/v10/entity/wms_activity_track_dtl/{id}
```

### WMS Activity Track Status URLs

Check for the existence of the resource:

```
HEAD .../lgfapi/v10/entity/wms_activity_track_status/{id}
```



Fetch paginated results when users use the following URL:

```
GET .../lgfapi/v10/entity/wms_activity_track_status/
```

Fetch non-paginated result by specific 'ID'

```
GET .../lgfapi/v10/entity/wms_activity_track_status/{id}
```

## Daily Activity Track Entities

As a second step, the **WMS WFM Interface** scheduled job moves WMS data from **WMS Activity Track** to **Daily Activity Track** view. The following APIs can be used to get relevant **Daily Activity Track** data.

### Daily Activity Track URLs

Check for the existence of the resource:

```
HEAD .../lgfapi/v10/entity/daily_activity_track/{id}
```

Fetch paginated results:

```
GET .../lgfapi/v10/entity/daily_activity_track/
```

Fetch non-paginated result by specific 'ID':

```
GET .../lgfapi/v10/entity/daily_activity_track/{id}
```

### Daily Activity Track Dtl URLs

Check for the existence of the resource:

```
HEAD .../lgfapi/v10/entity/daily_activity_track_dtl/{id}
```

Fetch paginated results when users use the following URL:

```
GET .../lgfapi/v10/entity/daily_activity_track_dtl/
```

Fetch non-paginated result by specific 'ID'

```
GET .../lgfapi/v10/entity/daily_activity_track_dtl/{id}
```

## Daily VAS Track

The **Daily VAS Track** view captures VAS (non-WMS) productive activities performed by the users on the warehouse floor. The following APIs can be used to get relevant **Daily VAS Track** data.

### URLs

Check for the existence of the resource:

```
HEAD .../lgfapi/v10/entity/daily_vas_track/{id}
```

Fetch paginated results:

```
GET .../lgfapi/v10/entity/daily_vas_track/
```

Fetch non-paginated result by specific 'ID':

```
GET .../lgfapi/v10/entity/daily_vas_track/{id}
```

## Track Record

The **Track Record** view captures user clock data. The following APIs can be used to get relevant **Track Record** data.

### URLs

Check for the existence of the resource:

```
HEAD .../lgfapi/v10/entity/track_record/{id}
```

Fetch paginated results:

```
GET .../lgfapi/v10/entity/track_record/
```

Fetch non-paginated result by specific 'ID':

```
GET .../lgfapi/v10/entity/track_record/{id}
```

## Stage Track Record

User clock data that is interfaced from external systems using Clock input interface or Clock REST API is first written to **Stage Track Record** before validating and moving to **Track Record**. The following APIs can be used to get relevant **Stage Track Record** data.

### URLs

Check for the existence of the resource:

```
HEAD .../lgfapi/v10/entity/stage_track_record/{id}
```

Fetch paginated results:

```
GET .../lgfapi/v10/entity/stage_track_record/
```

Fetch non-paginated result by specific 'ID':

```
GET .../lgfapi/v10/entity/stage_track_record/{id}
```

## Team

A **Team** consists of groups of users performing a VAS activity collectively. The following APIs can be used to get relevant **Team** information from WFM.

## URLs

Check for the existence of the resource:

```
HEAD .../lgfapi/v10/entity/team/{id}
```

Fetch paginated results:

```
GET .../lgfapi/v10/entity/team/
```

Fetch non-paginated result by specific 'ID':

```
GET .../lgfapi/v10/entity/team/{id}
```

## Team User XREF

A **Team** consists of groups of users performing a VAS activity collectively. The following APIs can be used to get the association between **Users** and **Teams** in WFM.

### URLs

Check for the existence of the resource:

```
HEAD .../lgfapi/v10/entity/team_user_xref/{id}
```

Fetch paginated results:

```
GET .../lgfapi/v10/entity/team_user_xref/
```

Fetch non-paginated result by specific 'ID':

```
GET .../lgfapi/v10/entity/team_user_xref/{id}
```

## SKU Line

SKU Lines are assigned to items in WMS in the items view. The same SKU Lines are also defined in WFM that are captured in the **SKU Line** view. The following APIs can be used to get relevant **SKU Line** data from WFM.

### URLs

Check for the existence of the resource:

```
HEAD .../lgfapi/v10/entity/sku_line/{id}
```

Fetch paginated results:

```
GET .../lgfapi/v10/entity/sku_line/
```

Fetch non-paginated result by specific 'ID':

```
GET .../lgfapi/v10/entity/sku_line/{id}
```

## Stage SKU Line

SKU Line data that is interfaced from external systems using SKU Line input interface is first written to **Stage SKU Line** before validating and moving to **SKU Line**. The following APIs can be used to get relevant **Stage SKU Line** data.

### URLs

Check for the existence of the resource:

```
HEAD .../lgfapi/v10/entity/stage_sku_line/{id}
```

Fetch paginated results:

```
GET .../lgfapi/v10/entity/stage_sku_line/
```

Fetch non-paginated result by specific 'ID':

```
GET .../lgfapi/v10/entity/stage_sku_line/{id}
```

## SKU Line Group

SKU Lines Groups are item categories against which goals can be defined. The following APIs can be used to get relevant **SKU Line Group** from WFM.

### URLs

Check for the existence of the resource:

```
HEAD .../lgfapi/v10/entity/sku_line_group/{id}
```

Fetch paginated results:

```
GET .../lgfapi/v10/entity/sku_line_group/
```

Fetch non-paginated result by specific 'ID':

```
GET .../lgfapi/v10/entity/sku_line_group/{id}
```

## SKU Line Group XREF

Multiple SKU Lines are grouped into a single SKU Line Group. The following APIs can be used to get the association between **SKU lines** and **SKU Line Groups** in WFM.

### URLs

Check for the existence of the resource:

```
HEAD .../lgfapi/v10/entity/sku_line_group_xref/{id}
```

Fetch paginated results:

```
GET .../lgfapi/v10/entity/sku_line_group_xref/
```

Fetch non-paginated result by specific 'ID':

```
GET .../lgfapi/v10/entity/sku_line_group_xref/{id}
```

## Cost Center

There could be a single or multiple cost centers within a facility which is captured in the **Cost Center** view. The following APIs can be used to get relevant **Cost Center** data from WFM.

### URLs

Check for the existence of the resource:

```
HEAD .../lgfapi/v10/entity/cost_center/{id}
```

Fetch paginated results:

```
GET .../lgfapi/v10/entity/cost_center/
```

Fetch non-paginated result by specific 'ID':

```
GET .../lgfapi/v10/entity/cost_center/{id}
```

## Work Group

There could be a single or multiple work groups within each cost center which is captured in the **Work Group** view. The following APIs can be used to get relevant **Work Group** data from WFM.

### URLs

Check for the existence of the resource:

```
HEAD .../lgfapi/v10/entity/work_group/{id}
```

Fetch paginated results:

```
GET .../lgfapi/v10/entity/work_group/
```

Fetch non-paginated result by specific 'ID':

```
GET .../lgfapi/v10/entity/work_group/{id}
```

## Work Area

Users are assigned to different work areas which is captured in the **Work Area** view. The following APIs can be used to get relevant **Work Area** information from WFM.

## URLs

Check for the existence of the resource:

```
HEAD .../lgfapi/v10/entity/work_area/{id}
```

Fetch paginated results:

```
GET .../lgfapi/v10/entity/work_area/
```

Fetch non-paginated result by specific 'ID':

```
GET .../lgfapi/v10/entity/work_area/{id}
```

## Work Area Activity Entities

All activities that are expected to be performed by users on the warehouse floor is defined in the **Work Area Activity** view. The activities are categorized as System (WMS), VAS and Manual activities. The following APIs can be used to get relevant **Work Area Activity** information from WFM.

### Work Area Activity URLs

Check for the existence of the resource:

```
HEAD .../lgfapi/v10/entity/work_area_activity/{id}
```

Fetch paginated results:

```
GET .../lgfapi/v10/entity/work_area_activity/
```

Fetch non-paginated result by specific 'ID':

```
GET .../lgfapi/v10/entity/work_area_activity/{id}
```

### Work Area Activity Type URLs

Check for the existence of the resource:

```
HEAD .../lgfapi/v10/entity/work_area_activity_type/{id}
```

Fetch paginated results:

```
GET .../lgfapi/v10/entity/work_area_activity_type/
```

Fetch non-paginated result by specific 'ID':

```
GET .../lgfapi/v10/entity/work_area_activity_type/{id}
```

## WAA Screen XREF

Any activity performed using WMS RF screen is mapped to a system activity in WFM. The mapping between WMS RF screens and WFM system activities is captured in WAA Screen XREF. The following APIs can be used to get relevant **WAA Screen XREF** information from WFM.

## URLs

Check for the existence of the resource:

```
HEAD .../lgfapi/v10/entity/waa_screen_xref/{id}
```

Fetch paginated results:

```
GET .../lgfapi/v10/entity/ waa_screen_xref /
```

Fetch non-paginated result by specific 'ID':

```
GET .../lgfapi/v10/entity/ waa_screen_xref/{id}
```

## Prod Goal Line Group

Goals for System (WMS) Activities are captured in the **Prod Goal Line Group** view. The following APIs can be used to get relevant **Prod Goal Line Group** data from WFM.

### URLs

Check for the existence of the resource:

```
HEAD .../lgfapi/v10/entity/prod_goal_line_group/{id}
```

Fetch paginated results:

```
GET .../lgfapi/v10/entity/prod_goal_line_group/
```

Fetch non-paginated result by specific 'ID':

```
GET .../lgfapi/v10/entity/prod_goal_line_group/{id}
```

## Stage Prod Goal Line Group

Goals for system activities that are interfaced from external systems using **Line Group Goal** input interface is first written to **Stage Prod Goal Line Group** before validating and moving to **Prod Goal Line Group**. The following APIs can be used to get relevant **Stage Prod Goal Line Group** data.

### URLs

Check for the existence of the resource:

```
HEAD .../lgfapi/v10/entity/stage_prod_goal_line_group/{id}
```

Fetch paginated results:

```
GET .../lgfapi/v10/entity/stage_prod_goal_line_group/
```

Fetch non-paginated result by specific 'ID':

```
GET .../lgfapi/v10/entity/stage_prod_goal_line_group/{id}
```

## Prod Goal VAS

Goals for VAS (non-WMS) productive activities are captured in the **Prod Goal VAS** view. The following APIs can be used to get relevant **Prod Goal VAS** data from WFM.

### URLs

Check for the existence of the resource:

```
HEAD .../lgfapi/v10/entity/prod_goal_vas/{id}
```

Fetch paginated results:

```
GET .../lgfapi/v10/entity/prod_goal_vas/
```

Fetch non-paginated result by specific 'ID':

```
GET .../lgfapi/v10/entity/prod_goal_vas/{id}
```

## Stage Prod Goal VAS

Goals for VAS activities that is interfaced from external systems using **VAS Goal** input interface is first written to **Stage Prod Goal VAS** before validating and moving to **Prod Goal VAS**. The following APIs can be used to get relevant **Stage Prod Goal VAS** data.

### URLs

Check for the existence of the resource:

```
HEAD .../lgfapi/v10/entity/stage_prod_goal_vas/{id}
```

Fetch paginated results:

```
GET .../lgfapi/v10/entity/stage_prod_goal_vas/
```

Fetch non-paginated result by specific 'ID':

```
GET .../lgfapi/v10/entity/stage_prod_goal_vas/{id}
```

## Break

Breaks taken by users are defined in the **Break** view. The following APIs can be used to get relevant **Break** information from WFM.

### URLs

Check for the existence of the resource:

```
HEAD .../lgfapi/v10/entity/cw_break/{id}
```



Fetch paginated results:

```
GET .../lgfapi/v10/entity/cw_break/
```

Fetch non-paginated result by specific 'ID':

```
GET .../lgfapi/v10/entity/cw_break/{id}
```

## Shifts

A facility could be operating in multiple shifts which is defined in the **Shifts** view. The following APIs can be used to get relevant **Shift** information from WFM.

### URLs

Check for the existence of the resource:

```
HEAD .../lgfapi/v10/entity/shift/{id}
```

Fetch paginated results:

```
GET .../lgfapi/v10/entity/shift/
```

Fetch non-paginated result by specific 'ID':

```
GET .../lgfapi/v10/entity/shift/{id}
```

