# Oracle® APEX Installation Guide





Oracle APEX Installation Guide, Release 24.2

G12910-03

Copyright © 2003, 2025, Oracle and/or its affiliates.

Primary Author: John Godfrey

Contributors: Terri Jennings, David Bliss, Christina Cho, Hilary Farrell , Salim Hlayel, Christian Neumueller, Marc Sewtz, Jason Straub, Vlad Uvarov, Patrick Wolf

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this is software, software documentation, data (as defined in the Federal Acquisition Regulation), or related documentation that is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, then the following notice is applicable:

U.S. GOVERNMENT END USERS: Oracle programs (including any operating system, integrated software, any programs embedded, installed, or activated on delivered hardware, and modifications of such programs) and Oracle computer documentation or other Oracle data delivered to or accessed by U.S. Government end users are "commercial computer software," "commercial computer software documentation," or "limited rights data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, reproduction, duplication, release, display, disclosure, modification, preparation of derivative works, and/or adaptation of i) Oracle programs (including any operating system, integrated software, any programs embedded, installed, or activated on delivered hardware, and modifications of such programs), ii) Oracle computer documentation and/or iii) other Oracle data, is subject to the rights and limitations specified in the license contained in the applicable contract. The terms governing the U.S. Government's use of Oracle cloud services are defined by the applicable contract for such services. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

Oracle®, Java, MySQL, and NetSuite are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Inside are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. AMD, Epyc, and the AMD logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark of The Open Group.

This software or hardware and documentation may provide access to or information about content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services unless otherwise set forth in an applicable agreement between you and Oracle. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services, except as set forth in an applicable agreement between you and Oracle.

# Contents

Audience		
Related Do	ocuments	
Conventio		
Third-Party	/ License Information	
Change	es in Release 24.2 for Oracle APEX Installation Guide	
Oracle .	APEX Installation Requirements	
2.1 Orac	cle Database Requirements	:
2.1.1	Checking the Memory Settings of the Target Database	
2.1.2	Checking the WORKAREA_SIZE_POLICY of the Target Database	;
2.1.3	Installing APEX in Databases where Database Vault is Enabled	4
2.2 Brov	vser Requirements	4
	Server Requirements	4
	Space Requirement	Ĺ
2.5 Orac	cle XML DB Requirement	į
APEX I	nstallation Overview	
	ut APEX Architecture	-
	ut Accessing APEX in Oracle Cloud	4
	erstanding the Installation Process	3
3.3.1	About Planning Your Installation	(
3.3.2	About Patch Sets	2
3.3.3	About Associate AREX	
224	About Accessing APEX Requesting a Workspace from the Sign In Dialog	ļ
3.3.4	Requesting a workspace from the Sign in Dialog	(
3.3.5		-
	Resetting Your Password from the Sign In Page Recovering Your Workspace Name	- -

4 Upgrading from a Previous APEX Rele	lease
---------------------------------------	-------

4.1 Abo	ut Release Numbering Conventions	2
4.2 San	nple Upgrade Scenarios	2
4.3 View	ving the APEX Release Number	3
4.4 View	ving the Oracle REST Data Services Release Number	3
4.5 Abo	ut Installing an APEX Release Included with the Oracle Database	3
4.6 Abo	ut Upgrading Existing Applications	4
4.7 Abo	ut Testing Requirements	4
4.8 Abo	ut Cleaning Up Your Environment	4
4.9 Abo	ut Reverting to a Previous Release	5
Utilizin	g Multitenant Architecture	
5.1 Und	lerstanding the Installation Choices	1
5.2 Inst	alling APEX into an Application Container	2
5.2.1	About Application Containers	2
5.2.2	Creating an Application Container	2
5.2.3	Installing or Upgrading APEX in an Application Container	3
5.2.4	Verifying the Application Container Installation	3
5.2.5	Creating an Application Seed	4
5.2.6	Creating an Application PDB from the Application Root Seed	5
5.2.7	Configure HTTP Access to the Application PDB	6
5.3 Inst	alling APEX into Different PDBs	6
5.3.1	Uninstalling APEX from a CDB	6
5.3.2	Installing APEX Locally in a PDB	7
5.3.3	Installing APEX into a CDB	9
5.4 Pluç	gging in a PDB When APEX Is Installed in the Root Container	10
5.4.1	Scenario 1: Plug-in Non-CDB with APEX	11
5.4.2	Scenario 2: Plug-in PDB with a Common APEX from Another CDB	11
5.4.3	Scenario 3: Plug-in PDB with a Local APEX from Another CDB	12
5.4.4	Scenario 4: Plug-in Non-CDB or PDB with No APEX	12
5.4.5	Working with Incompatible APEX Versions	13
5.	4.5.1 Patching or Upgrading APEX in a CDB	13
5.	4.5.2 Patching or Upgrading APEX in a PDB	14
5.5 Pluç	gging in a PDB When APEX Is Not in the Root Container of the Target CDB	15
5.5.1	Scenario 1: Plug-in a Non-CDB or PDB with Locally Installed APEX	16
5.5.2	Scenario 2: Plug-in PDB with Common APEX from Another CDB	16
5.5.3	Scenario 3: Plug-in PDB with a Local APEX from Another CDB	17

## 6 Installing and Configuring APEX and Oracle REST Data Services

6.1	Perf	orming	Pre-installation Tasks for APEX	2
6.2	Abou	ıt SQL	cl Support	3
6.3	Dow	nloadir	ng and Installing APEX	3
	6.3.1	Insta	lling APEX	4
	6.3.2	Crea	ting or Updating Your Instance Administration Account	6
	6.3	3.2.1	What Is an Instance Administrator?	6
	6.3	3.2.2	About apxchpwd.sql	7
	6.3	3.2.3	Running apxchpwd.sql	7
	6.3.3	Resta	arting Processes	8
	6.3.4	Confi	guring the APEX_PUBLIC_USER Account	8
	6.3	3.4.1	About the APEX_PUBLIC_USER Account	8
	6.3	3.4.2	Unlocking the APEX_PUBLIC_USER Account	9
	6.3	3.4.3	Changing the Password for the APEX_PUBLIC_USER Account	9
	6.3	3.4.4	About Password Expiration in Oracle Database	10
	6.3.5	Confi	guring the APEX_PUBLIC_ROUTER Account	10
6.4	Dow	nloadir	ng and Installing Oracle REST Data Services (ORDS)	11
	6.4.1	Dowr	nloading Oracle REST Data Services	12
	6.4.2	Abou Balar	t Configuring Oracle REST Data Services Behind a Reverse Proxy or Load	12
	6.4.3	Web	Server HTTP POST Request Limits	13
6.5	Conf	iguring	Oracle REST Data Services	13
	6.5.1	Mana	aging Static Resources (Images)	13
	6.5	5.1.1	Copying the Images Directory	14
	6.5	5.1.2	Using a Static Resources CDN	14
	6.5.2	Valida	ating the Oracle REST Data Services Installation	15
	6.5.3	Confi	guring Static File Support	15
	6.5.4 Securing Oracle REST Data Service		15	
6.6	6.6 Enabling Network Services in Oracle Database			15
	6.6.1	Wher	n and Why Network Services Must be Enabled	16
	6.6.2	Gran	ting Connect Privileges	17
	6.6.3	Troub	pleshooting an Invalid ACL Error	18
6.7	Perfo	orming	Security Tasks	19
6.8	Cont	rolling	the Number of Concurrent Jobs	19
	6.8.1	Abou	t Managing the Number of Concurrent Jobs	19
	6.8.2	Viewi	ing the Number of JOB_QUEUE_PROCESSES	19
	6.8	3.2.1	Viewing JOB_QUEUE_PROCESSES in the Installation Log File	20
	6.8	3.2.2	Viewing JOB_QUEUE_PROCESSES in APEX	20
	6.8	3.2.3	Viewing JOB_QUEUE_PROCESSES from SQLcl	20

6.8.3	Changing the Number of JOB_QUEUE_PROCESSES	21			
6.9 About	Running APEX in Other Languages	21			
6.10 Insta	Illing Translated Versions of APEX	22			
6.10.1	About Installing Translated Versions of APEX	22			
6.10.2	Installing a Translated Version of APEX	23			
6.11 Crea					
6.11.1	About Workspaces and Users	25			
6.11.2	Signing In To Administration Services	25			
6.11.3	Creating a Workspace Manually	26			
6.11.4	Creating APEX Users	27			
6.11.5	Signing In to Your Workspace	29			
6.12 Perfo	orming Post Installation Tasks for Upgrade Installations	29			
6.12.1	About Removing Prior APEX Installations	30			
6.12.2	Verifying if a Prior Installation Exists	30			
6.12.3	Removing Schemas and SYS Objects from Prior Installations	31			
6.12.4	Removing Schemas from Prior Installations in a CDB	31			
6.12.5	Fixing Invalid ACL	31			
6.13 Abou	ut Performance Optimization Tasks	32			
6.14 Conv	verting Between Runtime and Full Development Environments	32			
6.14.1	About Runtime and Full Development Environments	33			
6.14.2	Converting a Runtime Environment to a Full Development Environment	33			
6.14.3	Converting a Full Development Environment to a Runtime Environment	34			
A.1 About	ing the APEX Installation Process  apxsilentins.sql	A-1			
A.2 Runni	ing apxsilentins.sql	A-1			
	ing Uptime During an APEX Upgrade stallation Troubleshooting				
C.1 Revie	ewing a Log of an Installation Session	C-1			
C.2 Verify	ing the Validity of an APEX Installation	C-1			
C.3 Clean	ning Up After a Failed Installation	C-2			
C.3.1	Reverting to a Previous Release After a Failed Upgrade Installation	C-2			
C.3.		C-2			
C.3.	, ,	C-3			
C.3.		C-3			
C.3.		C-52			
	Removing APEX from the Database	C-54			
	<del>-</del>				

C.4	About Images Displaying Incorrectly in APEX
C.5	About Page Protection Violation

C-55

C-55

## Index



## **Preface**

This guide explains how to install and configure Oracle APEX.

- Audience
- Related Documents
- Conventions
- Third-Party License Information

## **Audience**

Oracle APEX Installation Guide is intended for anyone responsible for installing Oracle APEX.

To use this manual, you must have administrative privileges on the computer where you installed your Oracle database and familiarity with object-relational database management concepts.

## **Related Documents**

For more information, see these Oracle resources:

- Oracle APEX Release Notes
- Oracle APEX App Builder User's Guide
- Oracle APEX End User's Guide
- Oracle APEX Administration Guide
- Oracle APEX SQL Workshop Guide
- Oracle APEX API Reference
- Oracle Database Concepts
- Oracle Database Administrator's Guide
- Oracle Database SQL Language Reference
- Oracle SQLcl User's Guide

## Conventions

The following text conventions are used in this document:

Convention	Meaning
boldface	Boldface type indicates graphical user interface elements associated with an action, or terms defined in text or the glossary.



Convention	Meaning
italic	Italic type indicates book titles, emphasis, or placeholder variables for which you supply particular values.
monospace	Monospace type indicates commands within a paragraph, URLs, code in examples, text that appears on the screen, or text that you enter.

# Third-Party License Information

Oracle APEX contains third-party code. Please see the *Oracle APEX Licensing Information User Manual* for notices Oracle is required to provide.

Note, however, that the Oracle program license that accompanied this product determines your right to use the Oracle program, including the third-party software, and the terms contained in the following notices do not change those rights.

# Changes in Release 24.2 for *Oracle APEX Installation Guide*

All content in *Oracle APEX Installation Guide* has been updated to reflect release 24.2 functionality.

## **Deprecated and Desupported Features**

See Deprecated Features and Desupported Features in *Oracle APEX Release Notes*.

# Oracle APEX Installation Requirements

Before installing Oracle APEX in a local self-managed installation you must verify your configuration meets the minimum installation requirements.

#### Oracle Database Requirements

Oracle APEX release 24.2 requires an Oracle Database release 19c or later. APEX runs on all database editions, including Enterprise Edition (EE), Standard Edition (SE), and Oracle Database Free. APEX can be installed in single-instance database and in Oracle Real Application Clusters (Oracle RAC) database.

#### Browser Requirements

Oracle APEX requires a JavaScript-enabled browser and supports the current and prior major release of Google Chrome, Mozilla Firefox, Apple Safari, and Microsoft Edge.

#### Web Server Requirements

Oracle APEX requires Oracle REST Data Services (ORDS) 23.3 or later.

#### Disk Space Requirement

Oracle APEX disk space requirements are described in this section.

#### Oracle XML DB Requirement

Oracle XML DB must be installed in the Oracle database that you want to use if you are installing a full development environment. If you are using a preconfigured database created either during an installation or by Database Configuration Assistant (DBCA), Oracle XML DB is already installed and configured.

## 2.1 Oracle Database Requirements

Oracle APEX release 24.2 requires an Oracle Database release 19c or later. APEX runs on all database editions, including Enterprise Edition (EE), Standard Edition (SE), and Oracle Database Free. APEX can be installed in single-instance database and in Oracle Real Application Clusters (Oracle RAC) database.

## Checking the Memory Settings of the Target Database

Oracle APEX requires the system global area (SGA) to be at least 1200 MB and program global area (PGA) to be at least 300 MB.

#### Checking the WORKAREA SIZE POLICY of the Target Database

For the Oracle APEX installation or upgrade process, the <code>WORKAREA\_SIZE\_POLICY</code> session parameter must be set to <code>AUTO</code>.

#### Installing APEX in Databases where Database Vault is Enabled

Complete additional configuration steps to install Oracle APEX in databases where Oracle Database Vault is enabled.



## 2.1.1 Checking the Memory Settings of the Target Database

Oracle APEX requires the system global area (SGA) to be at least 1200 MB and program global area (PGA) to be at least 300 MB.

Databases typically have two parameters to control the memory allocation: SGA\_TARGET and PGA\_AGGREGATE\_TARGET. For full details on Oracle Database memory configuration, consult the *Oracle Database Administrator's Guide* to find out how to configure manual memory parameters (for example, SGA\_TARGET, PGA\_AGGREGATE\_TARGET, SHARED\_POOL\_SIZE).

To check the memory parameters of the target database:

**1.** Start the database:

```
SOL> STARTUP
```

2. (Optional) Enter the following command to determine whether the system uses an initialization parameter file (initsid.ora) or a server parameter file (spfiledbname.ora):

```
SOL> SHOW PARAMETER PFILE;
```

This command displays the name and location of the server parameter file or the initialization parameter file.

3. Determine the current values of the memory parameters, then do one of the following:

```
SQL> SHOW PARAMETER SGA_TARGET
SQL> SHOW PARAMETER PGA AGGREGATE TARGET
```

- If the value of SGA\_TARGET is 0, your database is using automatic memory management. Consult Using Automatic Memory Management in *Oracle Database Administrator's Guide* to learn how to configure an equivalent memory size using the MEMORY\_TARGET parameter. Stop this procedure.
- If the values of SGA\_TARGET or PGA\_AGGREGATE\_TARGET are lower than the
  recommended sizes, then you must increase them depending on whether your
  database is using a server parameter file or the initialization parameter file. Proceed to
  the next step.
- 4. To determine whether your system uses a server parameter file or initialization parameter file:

```
SQL> SHOW PARAMETER PFILE;
```

• If the file begins with the prefix sp for **server parameter**, then issue:

```
SQL> ALTER SYSTEM SET SGA_TARGET='1200M' SCOPE=spfile;
SQL> ALTER SYSTEM SET PGA_AGGREGATE_TARGET='300M' SCOPE=spfile;
```

 Otherwise, the system is using an initialization parameter file. Change the value of the MEMORY\_TARGET parameter to at least 300 MB in the initialization parameter file (init<sid>.ora).



5. Shut down the database:

SQL> SHUTDOWN

6. Restart the database:

SQL> STARTUP

7. Confirm the new memory settings:

```
SQL> SHOW PARAMETER SGA_TARGET
SQL> SHOW PARAMETER PGA_AGGREGATE_TARGET
```

#### (i) See Also

Using Automatic Memory Management in Oracle Database Administrator's Guide

## 2.1.2 Checking the WORKAREA\_SIZE\_POLICY of the Target Database

For the Oracle APEX installation or upgrade process, the <code>WORKAREA\_SIZE\_POLICY</code> session parameter must be set to <code>AUTO</code>.

To check the WORKAREA\_SIZE\_POLICY of the target database:

- Start SQLcI and connect to the database as SYS specifying the SYSDBA role. For example:
  - On Windows:

```
SYSTEM_DRIVE:\ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS_password
```

On UNIX and Linux:

```
$ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS_password
```

2. Check the current value of the WORKAREA\_SIZE\_POLICY parameter:

```
SQL> SHOW PARAMETER WORKAREA_SIZE_POLICY
```

3. If the value of the parameter is MANUAL, change it to AUTO for the current database session. For example:

```
SQL> ALTER SESSION SET WORKAREA_SIZE_POLICY = AUTO;
```

4. Within the same database session, perform the installation or upgrade of Oracle APEX.



### (i) Note

If you are installing Oracle APEX in a CDB, WORKAREA\_SIZE\_POLICY must be set system-wide. For example:

SQL> ALTER SYSTEM SET WORKAREA\_SIZE\_POLICY=AUTO SCOPE=BOTH;

Then, if needed, change it back to MANUAL after Oracle APEX installation or upgrade.

#### (i) See Also

WORKAREA\_SIZE\_POLICY in Oracle Database Reference

## 2.1.3 Installing APEX in Databases where Database Vault is Enabled

Complete additional configuration steps to install Oracle APEX in databases where Oracle Database Vault is enabled.

To begin, see Integrating Oracle Database Vault with Oracle APEX in *Oracle Database Vault Administrator's Guide*.

You must also complete additional configuration steps for some APEX features, including workspace provisioning and SQL Workshop.

The Database Vault security controls protect application data from unauthorized access and help you to comply with privacy and regulatory requirements. Database Vault is a licensable option of Oracle Database Enterprise Edition. Its purpose is to mitigate the potential impact of privileged account abuse, misuse, insider and external threats, and human error on your sensitive data.

# 2.2 Browser Requirements

Oracle APEX requires a JavaScript-enabled browser and supports the current and prior major release of Google Chrome, Mozilla Firefox, Apple Safari, and Microsoft Edge.

# 2.3 Web Server Requirements

Oracle APEX requires Oracle REST Data Services (ORDS) 23.3 or later.

Oracle REST Data Services (ORDS) is Java-based web server. Oracle REST Data Services features the ability to emit RESTful web services, offers improved file upload capability, and is certified with Oracle WebLogic Server and Apache Tomcat.





APEX-based REST Services were desupported in release 22.1. Oracle REST Data Services (ORDS) release 21.4.2 and newer now ship with migration scripts that enable you to upgrade any remaining APEX-based REST Services to ORDS-based Services. To learn more, see Migration of Oracle APEX RESTful Service Modules in Oracle **REST Data Services Release Notes.** 

# 2.4 Disk Space Requirement

Oracle APEX disk space requirements are described in this section.

APEX disk space requirements are as follows:

- Free space for APEX software files on the file system: 670 MB if using English only download (apex\_24.2\_en.zip) and 1,178 MB if using full download (apex\_24.2.zip).
- Free space in APEX tablespace: 260 MB
- Free space in System tablespace: 128 MB
- Free space in APEX tablespace for each additional language (other than English) installed: 60 MB

# 2.5 Oracle XML DB Requirement

Oracle XML DB must be installed in the Oracle database that you want to use if you are installing a full development environment. If you are using a preconfigured database created either during an installation or by Database Configuration Assistant (DBCA), Oracle XML DB is already installed and configured.



#### 🕜 Tip

The installer does a prerequisite check for Oracle XML DB and will exit if it is not installed.



The installation of Oracle XML DB creates the user ANONYMOUS. In order for Oracle APEX workspace provisioning to work properly, the ANONYMOUS user must not be dropped from the database.



## Tip

For more information about manually adding Oracle XML DB to an existing database, see Administration of Oracle XML DB in Oracle XML DB Developer's Guide

## APEX Installation Overview

Oracle APEX Installation Guide describes how to install Oracle APEX in a self-managed (local) database.

How you sign in and access APEX depends upon your user role and where APEX resides. APEX may reside in a local self-managed Oracle or in an Oracle Cloud Service.

#### About APEX Architecture

Oracle APEX uses a simple architecture in which pages are dynamically generated using metadata stored within the Oracle database.

- About Accessing APEX in Oracle Cloud
   Learn about accessing Oracle APEX in Oracle Cloud.
- <u>Understanding the Installation Process</u>
   Installing Oracle APEX is a multiple step process. You follow the same instructions for new or upgrade installations.
- About the APEX Runtime Environment
   Learn about the Oracle APEX runtime environment.
- About APEX Database Accounts
   Oracle APEX creates the following database accounts at installation.

(i) See Also

Upgrading from a Previous APEX Release


## 3.1 About APEX Architecture

Oracle APEX uses a simple architecture in which pages are dynamically generated using metadata stored within the Oracle database.

#### **About the APEX Architecture**

The APEX architecture consists of a web browser, Oracle REST Data Services (the web server), and an Oracle database containing APEX. The major advantage of this architecture is the separation of the mid-tier and the database tier.





The web server, Oracle REST Data Services, functions as a communications broker between the web browser and the APEX objects in the Oracle database by mapping browser requests into database stored procedure calls.

Once fully installed, a Uniform Resource Locator (URL) is defined for both developers and end users to access APEX. Users require only a web browser and the required URL. No additional client software is required.

#### **About Oracle REST Data Services**

Oracle REST Data Services (ORDS) (formerly known as Oracle Application Express Listener) is a J2EE application which communicates with the Oracle database by mapping browser requests to the APEX engine database over a SQL\*Net connection.

Oracle REST Data Services is fully supported when deployed in a standalone mode as well as when deployed into Oracle WebLogic Server or Apache Tomcat application servers.

## ① Note

There are licensing costs associated with Oracle WebLogic Server.

## (i) See Also

- Web Server Requirements
- Installing and Configuring APEX and Oracle REST Data Services
- Introduction to Oracle REST Data Services in Oracle REST Data Services Developer's Guide
- Installing and Configuring Oracle REST Data Services in Oracle REST Data Services Installation and Configuration Guide

# 3.2 About Accessing APEX in Oracle Cloud

Learn about accessing Oracle APEX in Oracle Cloud.

APEX may reside in a local self-managed Oracle database or in a hosted environment (such as an Oracle Cloud service). The sign in process differs depending on where APEX resides.

In Oracle Cloud, APEX is installed, enabled, and ready to use in the following products:



- Oracle APEX Application Development (APEX Service)
- Oracle Autonomous Transaction Processing
- Oracle Autonomous Data Warehouse

APEX is available in Exadata Cloud Service and Database Cloud Service in Oracle Cloud Infrastructure. However, you need to manually customize your databases to install and enable APEX by following the self-managed database installation process or using cloud tooling such as Terraform.

## **Related Topics**

- Get an Environment
- Welcome to Oracle APEX Application Development Service in Getting Started with Oracle APEX Application Development
- Creating Applications with Oracle APEX on Autonomous Database in Using Oracle Autonomous Database Serverless

# 3.3 Understanding the Installation Process

Installing Oracle APEX is a multiple step process. You follow the same instructions for new or upgrade installations.

- About Planning Your Installation
   Learn about the steps needed to install Oracle APEX.
- About Patch Sets

Patch sets provide bug fixes only. Oracle may release one or several patch set bundles in between major product releases.

About the Installation Scripts

You can install Oracle APEX or update from previous release using the same installation procedure and the installation scripts.

- About Accessing APEX
  - You access the Oracle APEX development environment, by signing in to a shared work area called a workspace.
- Requesting a Workspace from the Sign In Dialog Request a workspace from the Sign In dialog.
- Resetting Your Password from the Sign In Page
   Reset your password by clicking a link on Oracle APEX Sign In page.
- Recovering Your Workspace Name
   Recover your workspace name from the Oracle APEX Sign In page.
  - (i) See Also

Upgrading from a Previous APEX Release

## 3.3.1 About Planning Your Installation

Learn about the steps needed to install Oracle APEX.

Oracle recommends you take the time to carefully plan your installation.



Installing Oracle APEX involves the following steps:

Decide on a Full or Runtime Environment - Determine whether to install a full
development environment or runtime environment. A full development environment
provides complete access to the App Builder development environment to develop
applications. A runtime environment is the appropriate choice for production
implementations in which you want to run applications that cannot be modified.

See About the APEX Runtime Environment.

2. **Verify installation requirements**- Before installing, verify your system meets the minimum requirements.

See Oracle APEX Installation Requirements.

3. Install the software - Install or upgrade Oracle APEX by downloading a ZIP file from the Oracle APEX download page and then downloading and installing Oracle REST Data Services (ORDS) as described in <a href="Installing and Configuring APEX">Installing and Configuring APEX</a> and Oracle REST Data Services.

(i) See Also

**Upgrading from a Previous APEX Release** 

## 3.3.2 About Patch Sets

Patch sets provide bug fixes only. Oracle may release one or several patch set bundles in between major product releases.

Patch sets are a mechanism for delivering fully tested and integrated product fixes. Patch sets provide bug fixes only. Patch sets typically do not include new functionality and they do not require certification on the target system. Patch sets include all of the libraries that have been rebuilt to implement the bug fixes in the set. All of the fixes in the patch set have been tested and are certified to work with each other.

In between major product releases, Oracle may release one or several patch set bundles. Visit Oracle APEX Downloads to learn about the contents of each patch set.

In fully managed Cloud databases, such as an Autonomous Database or Oracle APEX Application Development (APEX Service), Oracle automatically applies patch set bundles. For all other environments, customers can download patch set bundles from My Oracle Support.

To review the history of APEX patch sets installed in your database, query the APEX\_PATCHES dictionary view:

select patch\_number, patch\_version, installed\_on
 from APEX\_PATCHES
 order by installed\_on;



#### (i) See Also

- Upgrading from a Previous APEX Release
- Oracle APEX Downloads
- My Oracle Support

## 3.3.3 About the Installation Scripts

You can install Oracle APEX or update from previous release using the same installation procedure and the installation scripts.

The installation script checks for the latest existing Oracle APEX schema and automatically copies the instance metadata, workspaces, and applications from the previous schema into the current schema. The original schema associated with the previous release is left completely unaltered. Following best practices, Oracle recommends that you create new tablespaces for a new release of Oracle APEX and follow the appropriate installation instructions as outlined in this document.

## 3.3.4 About Accessing APEX

You access the Oracle APEX development environment, by signing in to a shared work area called a workspace.

How you sign in and access APEX depends upon your user role.

A workspace enables multiple users to work within the same APEX installation while keeping their objects, data, and applications private. Each workspace has a unique ID and name. An instance administrator can create a workspace manually within APEX Administration Services or have users submit requests. APEX Administration Services is a separate application for managing an entire APEX instance.

Users are divided into four primary roles:

- Instance administrators are superusers that manage an entire hosted instance using a separate application called APEX Administration Services. Instance administrators manage workspace provisioning, configure features and instance settings, and manage security.
- Workspace administrators can perform administrator tasks specific to a workspace such as configuring workspace preferences, managing user accounts, monitoring workspace activity, and viewing log files.
- Developers are users who sign in to a workspace and create and edit applications.
- End users can only run existing applications.

If you are a developer, an administrator must grant you access to shared work area called a workspace. If you are an Instance administrator, you must sign in to APEX Administration Services, determine whether to specify a provisioning mode, create a workspace, and then sign in to that workspace.

#### **About Specifying a Provisioning Mode**

The Instance administrator determines how the process of provisioning (or creating) a workspace works for a specific APEX instance. To determine how provisioning works, an Instance Administrator selects a Provisioning Methods on the Instance Settings page:



- Manual An Instance administrator creates new workspaces and notifies the Workspace administrator regarding the Sign In credentials.
- Request Users request a workspace. Once an administrator approves the request, the
  user receives an email containing an email verification link. After the user clicks the email
  verification link, the workspace is created.
- Automatic Works similar to Request except requests are automatically approved with no administrator review required

### (i) See Also

About Specifying How Workspaces Are Created and Selecting a Workspace Provisioning Mode in *Oracle APEX Administration Guide* 

### **About Creating Workspaces and Users**

Before you can develop or install applications, an administrator must create a workspace and add APEX users. To learn more contact your administrator, or see <a href="Creating a Workspace and Adding APEX Users">Creating a Workspace and Adding APEX Users</a>.

## See Also

- Creating Workspaces in Administration Services in Oracle APEX Administration Guide
- Making a Service Request in Oracle APEX Administration Guide
- Managing Requests in Oracle APEX Administration Guide

## 3.3.5 Requesting a Workspace from the Sign In Dialog

Request a workspace from the Sign In dialog.

Your administrator determines how you request a new workspace. If your administrator has set Provisioning Method to either **Request** or **Automatic** and has configured email, you can request a workspace on the Sign In dialog.

To request a workspace from the Sign In dialog:

- Navigate to the Oracle APEX Sign in dialog.
- Under Sign In, click Request a Workspace.

The Request a Workspace Wizard appears.

- 3. For Identification:
  - a. First Name Enter your first name.
  - Last Name Enter your last name.
  - c. Email Enter the email address. A link to activate your workspace will be sent to this email address.
  - Workspace Enter a workspace name that name uniquely identifies your development environment.



- e. Click Next.
- If defined, review and accept the service agreement and click **Next**.
- Verify your request and click **Submit Request**.

Once you complete the Identification form, the following events occur:

- You will receive an email containing a verification link.
- When you click the verification link, the workspace is created.
- You will receive another email containing Sign In credentials (that is, the workspace name, username, and password).

Once you complete the Identification form, the following events occur:

- You will receive an email containing a verification link.
- When you click the verification link, the workspace is created.
- You will then receive another email containing Sign In credentials (that is, the workspace name, username, and password).

## (i) See Also

About Specifying How Workspaces Are Created in Oracle APEX Administration Guide

## 3.3.6 Resetting Your Password from the Sign In Page

Reset your password by clicking a link on Oracle APEX Sign In page.



#### Tip

To reset your password from the Sign In page, you must provide your email address and the workspace name.

To reset your password from the Sign In Page:

- In a web browser, navigate to the Oracle APEX Sign In page.
  - The Sign In page appears.
- Under Sign In, click Reset Password.
- In the Reset Password form, enter your email address, workspace name, and click Reset Password.

You will receive an email confirming your workspace name and username and containing a Reset Password URL link.

- In the email, click the **Reset Password URL** link.
- In the Change Password form:
  - New Password Enter your new password.





Passwords are case sensitive.

- Confirm Password Enter your new password again.
- c. Click Apply Changes.



You can also reset your password within Oracle APEX. See Changing Your Profile or Password in *Oracle APEX App Builder User's Guide* 

## 3.3.7 Recovering Your Workspace Name

Recover your workspace name from the Oracle APEX Sign In page.

If you cannot remember your workspace name, you can request a list of all workspace names associated with your email address.

To find your workspace name:

- 1. In a web browser, navigate to the Oracle APEX Sign In page.
- 2. On the Sign In page, click Reset Password.
- 3. Click Find My Workspace.
- Enter your email address and click Find Workspace.

You will receive an email listing all workspaces associated with the email address you provided.

## 3.4 About the APEX Runtime Environment

Learn about the Oracle APEX runtime environment.

As with any software development life cycle, Oracle strongly recommends that you have different environments for development, testing/QA, and production. For testing and production instances, APEX supports the ability to install just a runtime version of APEX. This runtime environment minimizes the installed footprint and privileges and improves application security since in a runtime instance developers cannot inadvertently update a production application.

An APEX runtime environment enables you to run applications, but it does not provide a Web interface for administration. A runtime environment only includes the packages necessary to run your application, making it a more hardened environment. You administer the APEX runtime environment using the APEX\_INSTANCE\_ADMIN API and SQL Developer or SQLcl.

Scripts are provided to remove or add the developer interface from an existing instance.

To ensure the security and performance of your development environment, APEX runtime environment is not available in Oracle Autonomous Database. To harden your testing and production instances, you can use the RESTRICT\_DEV\_HEADER instance parameter, which disables access to APEX App Builder and APEX Administration Services.



#### **Related Topics**

- Converting Between Runtime and Full Development Environments
   Learn about converting between runtime and full development environments.
- About the Advantages of the Oracle APEX Runtime Environment in Oracle APEX App Builder User's Guide
- About the Advantages of the Oracle APEX Runtime Environment in Oracle APEX API Reference

## 3.5 About APEX Database Accounts

Oracle APEX creates the following database accounts at installation.

- APEX\_240200 This schema-only account owns the APEX platform schema and metadata.
   This account is always locked.
- FLOWS\_FILES This schema-only account owns the APEX-uploaded files that are not stored in workspace schemas. This account is always locked.
- APEX\_PUBLIC\_USER This minimally privileged account is used for APEX configuration with Oracle REST Data Services.
- APEX\_PUBLIC\_ROUTER This minimally privileged account is used for an ORDS REST module to resolve friendly URLs.

If you configured RESTful Web services, APEX also creates the following additional accounts:

- APEX\_REST\_PUBLIC\_USER This account is used when invoking RESTful Services definitions stored in APEX.
- APEX\_LISTENER This account is used to query RESTful Services definitions stored in APEX.

If you are upgrading from a previous release, all of the above accounts may already exist **except** APEX 240200.

# Upgrading from a Previous APEX Release

Upgrading Oracle APEX creates new database objects in a new schema and migrates the application metadata to the new release.

If you have APEX release 24.1 or earlier, following any of the installation scenarios in this guide upgrades your APEX instance to the current release, creates APEX 24.2 database objects in a new schema, and migrates the application metadata to the new release.

- About Release Numbering Conventions
- New releases of Oracle APEX correlate to the calendar year.
- Sample Upgrade Scenarios

  Review common upgrade scenarios including upgrading from a prior release and upgrading when an Oracle Database release includes Oracle APEX.
- Viewing the APEX Release Number
   View your Oracle APEX release number on the Workspace home page or on the About APEX page.
- Viewing the Oracle REST Data Services Release Number
   View the Oracle REST Data Services release number on the About Oracle APEX page.
- About Installing an APEX Release Included with the Oracle Database
   Learn about which Oracle Database releases include Oracle APEX and the importance of updating to the lastest APEX release.
- About Upgrading Existing Applications
   Installing a new release of Oracle APEX, updates existing applications to the latest release, but does not alter application user interface or application components.
- About Testing Requirements
   Determining the appropriate amount of regression testing when upgrading Oracle APEX depends upon the complexity, size, and number of applications you are upgrading.
- About Cleaning Up Your Environment
   Following the successful upgrade of all of the environments to the latest release of Oracle APEX, you should clean up the environments.
- About Reverting to a Previous Release
   You can revert to a previous release of Oracle APEX.
  - (i) See Also
    - Understanding the Installation Process
    - Maximizing Uptime During an APEX Upgrade



# 4.1 About Release Numbering Conventions

New releases of Oracle APEX correlate to the calendar year.

In 2018 and starting with release 18.1 and 18.2, APEX introduced correlating the release number to the calendar year.

In addition, APEX now only offers full releases and no longer provides patch set releases (such as 5.1.1). Eliminating patch set releases reduces downtime when updating existing installations. APEX architecture also enables developers to revert releases if necessary.

Patch set exceptions (PSEs) may still be delivered for major defects. To learn more about PSEs, visit the <u>Oracle APEX 24.2 Known Issues</u> page or the <u>Prior Release Archives</u> for earlier releases.

# 4.2 Sample Upgrade Scenarios

Review common upgrade scenarios including upgrading from a prior release and upgrading when an Oracle Database release includes Oracle APEX.

Table 4-1 lists common upgrade scenarios.

Table 4-1 Sample Upgrade Scenarios

Upgrade Scenarios	Action
Upgrade from a prior Oracle APEX release.	Download the most recent ZIP file from the Oracle APEX download page and run a script to upgrade to the latest release. For details, see Installing APEX.
You install an Oracle Database which includes Oracle APEX.	Download the most recent ZIP file from the Oracle APEX download page and run a script to upgrade to the latest release.  For details, see Installing APEX.



When upgrading from APEX 18.1 to APEX 24.2, upgrade to APEX 24.1 first, and then to APEX 24.2. For more information, review Oracle APEX 24.2 Known Issues.

#### **Related Topics**

- <u>Downloading and Installing APEX</u>
   Learn about downloading and installing Oracle APEX.
- Oracle APEX Release Notes



# 4.3 Viewing the APEX Release Number

View your Oracle APEX release number on the Workspace home page or on the About APEX page.

You can view the APEX release number on the Workspace home page or on the About APEX page:

- Workspace home page:
  - Sign in to APEX.

On the Workspace home page, the current release number displays in the bottom right corner.

- About APEX page:
  - Sign in to APEX.
  - Click the Help menu in the upper right and select About.
     On the About APEX page, the release number appears next to Product Build.

# 4.4 Viewing the Oracle REST Data Services Release Number

View the Oracle REST Data Services release number on the About Oracle APEX page.

Oracle APEX requires access to the web server, Oracle REST Data Services (ORDS) 23.3 or later.

To view the Oracle REST Data Services release number:

- Sign in to Oracle APEX.
- Click the Help menu in the upper right and select About.
- 3. Under the CGI Environment section, find APEX\_LISTENER\_VERSION.

# 4.5 About Installing an APEX Release Included with the Oracle Database

Learn about which Oracle Database releases include Oracle APEX and the importance of updating to the lastest APEX release.

APEX is included with the following Oracle Database releases:

- Oracle Database 19c Oracle Application Express release 18.1.
- Oracle Database 18c Oracle Application Express release 5.1.
- Oracle Database 12c Release 2 (12.2)- Oracle Application Express release 5.0.
- Oracle Database 12c Release 1 (12.1) Oracle Application Express release 4.2.
- Oracle Database 11g Release 2 (11.2) Oracle Application Express release 3.2.
- Oracle Database 11g Release 1 (11.1) Oracle Application Express release 3.0.

Since Oracle Database releases less frequently than APEX, Oracle recommends updating to the latest APEX release available. To learn more, see <u>Downloading and Installing APEX</u>.





If upgrading APEX from a release that ships with the database, do not alter any APEX files in the Oracle home directory (for example,  $/u01/app/oracle/product/18.0.0/dbhome_1/apex$ ).

# 4.6 About Upgrading Existing Applications

Installing a new release of Oracle APEX, updates existing applications to the latest release, but does not alter application user interface or application components.

Once you upgrade an Oracle APEX instance from a previous release, existing applications will work without modification. However, to keep applications maintainable, up-to-date, and to leverage new functionality, developers should perform the steps outlined in Upgrading APEX Applications in *Oracle APEX App Builder User's Guide*.

# 4.7 About Testing Requirements

Determining the appropriate amount of regression testing when upgrading Oracle APEX depends upon the complexity, size, and number of applications you are upgrading.

You should include the majority of complex pages, particularly those that incorporate significant JavaScript or extensive PL/SQL computations or processes. Developers should ensure pages which they manually update based on the Upgrade Application or Advisor are also included in regression tests. Not all remaining pages have to be included in regression testing. Oracle recommends you include a good representation of different page types includes reports, charts, and forms. An application should always be included in regression testing if its compatibility mode was modified post-upgrade.

While regression testing of upgraded applications is imperative to minimize risk of disrupting the end users, it is important that testing is not drawn out for an extended period. As a general rule:

- Step 1: Upgrade your development environment first. Allow developers to review the applications and make initial updates as needed.
- Step 2: Upgrade your QA/Test environment.
- Step 3: Upgrade applications from development are built into this environment.
- Step 4: Upgrade your production environment.
- Step 5: Build upgraded applications into this environment.

# 4.8 About Cleaning Up Your Environment

Following the successful upgrade of all of the environments to the latest release of Oracle APEX, you should clean up the environments.

Once you start developing with the newer release, the Oracle APEX schema associated with the prior release can be deleted. If you installed the prior release into a separate tablespace, you can simply drop the specific tablespace. Oracle recommends leaving the older Oracle APEX schema(s) for a few weeks and then remove them from the development, test, and production environments. This cleanup process releases disk space and ensures that no one accesses an outdated schema using tools such as SQL Developer or SQLcl.



# 4.9 About Reverting to a Previous Release

You can revert to a previous release of Oracle APEX.

Because Oracle APEX creates a new schema for each major release, reverting back to a prior release is a relatively simple process. If you revert to a prior release, any modifications made in the current Oracle APEX instance are lost. The main task is to switch the public synonyms and grants to point at the previous schema instead of the new schema.

See Also

Reverting to a Previous Release After a Failed Upgrade Installation

# **Utilizing Multitenant Architecture**

Learn about installation choices and different scenarios associated with copying and moving pluggable databases introduced by the multitenant architecture with respect to Oracle APEX.

- Understanding the Installation Choices Learn about the installation choices in Oracle APEX.
- Installing APEX into an Application Container Learn about the Application Container that stores data and metadata for Oracle APEX application back ends.
- **Installing APEX into Different PDBs** You can install different versions of Oracle APEX into different PDBs.
- Plugging in a PDB When APEX Is Installed in the Root Container Learn about scenarios in which the target database has Oracle APEX installed into the root container, CDB\$ROOT - the default installation option.
- Plugging in a PDB When APEX Is Not in the Root Container of the Target CDB The scenarios in this section describe when Oracle APEX is not installed in the root container, CDB\$ROOT, by explicitly removing it as described in "Uninstalling APEX from a CDB."

# 5.1 Understanding the Installation Choices

Learn about the installation choices in Oracle APEX.

The multitenant database architecture has a multitenant container database (CDB) that includes a root container, CDB\$ROOT, a seed database, PDB\$SEED, and multiple pluggable databases (PDBs). Each pluggable database is equivalent to a separate database instance in Oracle Database release 11g. The root container, CDB\$ROOT, holds common objects that are accessible to every PDB utilizing metadata links or object links. The seed database, PDB\$SEED, is used when creating a new PDB to seed the new database. The key benefit of the multitenant architecture is that the database resources, such as CPU and memory, can be shared across all of the PDBs. This architecture also enables many databases to be treated as one for tasks such as upgrades or patches, and backups.



#### Tip

Oracle recommends installing APEX in individual PDBs for the majority of use cases. except for hosting companies or installations where all PDBs utilize APEX and they all need to run the exact same release and patch set of APEX.

When APEX is installed in the CDB, you still install and run APEX applications from individual PDBs. Running APEX applications or accessing an APEX development environment in the CDB\$ROOT container is **not** supported.





Installing APEX into Different PDBs

# 5.2 Installing APEX into an Application Container

Learn about the Application Container that stores data and metadata for Oracle APEX application back ends.

#### About Application Containers

An application container is a CDB component that stores data and metadata for application backends.

## Creating an Application Container

To create a PDB within a CDB as an application container, you use the AS APPLICATION CONTAINER clause of the create PDB command.

- Installing or Upgrading APEX in an Application Container
- <u>Verifying the Application Container Installation</u>

Verify the application container by inpsecting the log file for ORA- or PLS- errors and compiling invalid objects.

### Creating an Application Seed

An application seed is used to provision application PDBs with the Oracle APEX application root's applications pre-installed.

## Creating an Application PDB from the Application Root Seed

An application PDB is created by issuing the CREATE PLUGGABLE DATABASE statement from the application root.

Configure HTTP Access to the Application PDB

Configure a new application PDB for HTTP access.

## 5.2.1 About Application Containers

An application container is a CDB component that stores data and metadata for application backends.

Oracle APEX can be installed into an application container using the <code>apxappcon.sql</code> script. An application container consists of an application root where the application is defined and one or more PDBs that share data and metadata about the application from the application root. You can have multiple application containers within a CDB and each container can have a different version of Oracle APEX.

Patching or upgrading Oracle APEX in an application container is simplified, because these actions are done against the application root. When an application PDB wishes to uptake the patch or upgraded version, it simply syncs with the application root. Oracle APEX continues to run in the application PDB at the existing version until the application PDB syncs with the application root.

## 5.2.2 Creating an Application Container

To create a PDB within a CDB as an application container, you use the AS APPLICATION CONTAINER clause of the create PDB command.

To create Application Container:



- 1. Use the AS APPLICATION CONTAINER clause of the CREATE PLUGGABLE DATABASE statement to create an application container.
- 2. Open the application container.

#### For Example:

```
CREATE PLUGGABLE DATABASE apex_approot1 AS APPLICATION CONTAINER admin user admin IDENTIFIED

BY <admin_password> FILE_NAME_CONVERT=('pdbseed','apex_approot1');
ALTER PLUGGABLE DATABASE apex_approot1 open;
```

## (i) Note

apex\_approot1 and the admin user in the previous example can be any valid ORACLE identifier.

## 5.2.3 Installing or Upgrading APEX in an Application Container

To install or upgrade Oracle APEX in an Application Container:

- Connect to Application Container.
- 2. Run apxappcon.sql.

apxappcon.sql installs APEX as an application named APEX into the application root.

The script takes the exact same first four arguments as the apexins.sql script, with the addition of a fifth parameter which is the password to use for the APEX\_PUBLIC\_USER password. In an upgrade installation, the fifth argument is ignored because the APEX\_PUBLIC\_USER database user will already exist.

#### For example:

```
ALTER SESSION SET CONTAINER = apex_approot1;
@apxappcon.sql SYSAUX SYSAUX TEMP /i/ P@ssw0rd!
```

## 5.2.4 Verifying the Application Container Installation

Verify the application container by inpsecting the log file for ORA- or PLS- errors and compiling invalid objects.

To verify the Application Container installation:

- Manually inspect the installation log file for ORA- or PLS- errors.
- Compile invalid objects by running the following command:

#### For example:

```
ALTER SESSION SET CONTAINER=apex_approot1;
begin
    sys.dbms_utility.compile_schema( 'APEX_240200', false );
    sys.dbms_utility.compile_schema( 'FLOWS_FILES', false );
```



```
end;
```

3. Query dba\_applications and dba\_app\_errors.

no rows selected

## 5.2.5 Creating an Application Seed

An application seed is used to provision application PDBs with the Oracle APEX application root's applications pre-installed.

To create an Application Seed:

- 1. Connect to CDB\$ROOT as sysdba.
- 2. Alter session and set container to the application root.
- 3. Use the AS SEED clause of the CREATE PLUGGABLE DATABASE statement to create an application seed.
- 4. Sync the APEX application with the application seed.
- Compile invalid objects.
- 6. Open the application seed in read only mode.

For example:

```
ALTER SESSION SET CONTAINER=apex_approot1;

CREATE PLUGGABLE DATABASE as seed admin user admin identified by 
<admin_password> file_name_convert=('pdbseed','apex_approot1_seed');

ALTER PLUGGABLE DATABASE apex_approot1$seed open;

ALTER SESSION SET CONTAINER=apex_approot1$seed;

ALTER PLUGGABLE DATABASE application APEX sync;

begin    sys.dbms_utility.compile_schema( 'APEX_240200', false );
    sys.dbms_utility.compile_schema( 'FLOWS_FILES', false );
end;
```



ALTER PLUGGABLE DATABASE close immediate; ALTER PLUGGABLE DATABASE open read only;



(i) Note

apex\_approot1 and the admin user in the previous example can be any valid ORACLE identifier.

## 5.2.6 Creating an Application PDB from the Application Root Seed

An application PDB is created by issuing the CREATE PLUGGABLE DATABASE statement from the application root.

The PLUGGABLE DATABASE is created from the application container seed so the APEX application is already installed and ready for configuration.

To create an Application PDB from the Application Root Seed:

- Connect to CDB\$ROOT as sysdba.
- Alter session and set container to the application root.
- Use the CREATE PLUGGABLE DATABASE command to create a PDB from the application seed.

#### For example:

```
ALTER SESSION SET CONTAINER=apex_approot1;
CREATE PLUGGABLE DATABASE apex_pdb1 admin user admin identified by <admin
password> file_name_convert=('apex_approot1_seed','apex_pdb1');
ALTER PLUGGABLE DATABASE apex pdb1 open;
ALTER SESSION SET CONTAINER=apex_pdb1;
SQL> select app_name, app_version, app_status from dba_applications where
app_name = 'APEX';
APP_NAME
                               APP_VERSION
                                                               APP_STATUS
APEX
                               24.2
                                                               NORMAL
```





#### (i) Note

apex\_approot1 and the admin user in the previous example can be any valid ORACLE identifier.

## 5.2.7 Configure HTTP Access to the Application PDB

Configure a new application PDB for HTTP access.

Configure the new application PDB for HTTP access by following the instructions starting with the section Downloading and Installing Oracle REST Data Services.



#### (i) See Also

Setting Up ORDS in an Application Container

# 5.3 Installing APEX into Different PDBs

You can install different versions of Oracle APEX into different PDBs.

If APEX is not installed in the container database, you can install a local APEX within each PDB as required. When APEX is installed locally there are no APEX metadata linked objects and all packages, views, and tables are created within the APEX 240200 schema, within each PDB where APEX is installed.

- Uninstalling APEX from a CDB Learn how to uninstall Oracle APEX from a CDB.
- Installing APEX Locally in a PDB Learn how to install Oracle APEX locally in a PDB.
- **Installing APEX into a CDB**

## 5.3.1 Uninstalling APEX from a CDB

Learn how to uninstall Oracle APEX from a CDB.

To uninstall APEX from a CDB:



#### (i) Note

Installing or removing APEX from a CDB requires a local connection to the database.

This section describes removing APEX from a CDB.

- Change to the apex directory in the location where you unzipped the distribution.
- Start SQLcl and connect to the database where APEX is installed as SYS specifying the SYSDBA role. For example:



On Windows:

SYSTEM\_DRIVE:\ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS\_password

On UNIX and Linux:

\$ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS\_password

3. Run apxremov.sql.

For example:

@apxremov.sql



If you run apexremov.sql after PDBs have been added to the CDB, then APEX uninstalls from all of the PDBs, as well as CDB\$ROOT and PDB\$SEED. Any applications defined in any of the PDBs will be removed.

## 5.3.2 Installing APEX Locally in a PDB

Learn how to install Oracle APEX locally in a PDB.

Once you have removed APEX from the container database by following the instructions in Uninstalling APEX from a CDB, you can install APEX locally in a PDB.

To install APEX locally in a PDB:

- Change the apex directory in the location where you unzipped the distribution.
- Start SQLcl and connect to the database where APEX is installed as SYS specifying the SYSDBA role. For example:
  - On Windows:

```
SYSTEM_DRIVE:\ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS password
```

On UNIX and Linux:

```
$ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS_password
```

Set the container to the PDB you want to install APEX locally:

```
ALTER SESSION SET CONTAINER = <PDB_name>;
```

Select the appropriate installation option.



**Full development environment** provides complete access to the App Builder environment to develop applications. A **Runtime environment** enables users to run applications that cannot be modified.

Available installation options include:

• Full development environment - Run apexins.sql passing the following four arguments in the order shown:

@apexins.sql tablespace\_apex tablespace\_files tablespace\_temp images

#### Where:

- tablespace\_apex is the name of the tablespace for the APEX platform schema.
- tablespace\_files is the name of the tablespace for the APEX files schema.
- tablespace\_temp is the name of the temporary tablespace or tablespace group.
- images is the virtual directory for APEX images. To support future APEX upgrades, define the virtual image directory as /i/.

#### For example:

```
@apexins.sql SYSAUX SYSAUX TEMP /i/
```

 Runtime environment - Run apxrtins.sql passing the following four arguments in the order shown:

@apxrtins.sql tablespace\_apex tablespace\_files tablespace\_temp images

### Where:

- tablespace apex is the name of the tablespace for the APEX platform schema.
- tablespace\_files is the name of the tablespace for the APEX files schema.
- tablespace\_temp is the name of the temporary tablespace or tablespace group.
- images is the virtual directory for APEX images. To support future APEX upgrades, define the virtual image directory as /i/.

### For example:

```
@apxrtins.sql SYSAUX SYSAUX TEMP /i/
```

**5.** Complete the appropriate steps in <u>Installing and Configuring APEX and Oracle REST Data</u> Services.

### See Also

- Installing and Configuring APEX and Oracle REST Data Services
- About APEX Database Accounts
- Working with SQLcl in Oracle SQLcl User's Guide for more information about SQLcl



### 5.3.3 Installing APEX into a CDB

To install Oracle APEX into a CDB:



Installing or removing APEX from a CDB requires a local connection to the database.

- Change your working directory to the apex directory in the location where you unzipped the distribution.
- 2. Start SQLcl and connect to CDB\$ROOT of the database where APEX is installed as SYS specifying the SYSDBA role. For example:
  - On Windows:

```
SYSTEM_DRIVE:\ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS_password
```

On UNIX and Linux:

```
$ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS_password
```

3. Select the appropriate installation option.

**Full development environment** provides complete access to the App Builder environment to develop applications. A **Runtime environment** enables users to run applications that cannot be modified.

Available installation options include:

• Full development environment. Run apexins.sql passing the following four arguments in the order shown:

```
@apexins.sql tablespace_apex tablespace_files tablespace_temp images
```

### Where:

- tablespace\_apex is the name of the tablespace for the APEX platform schema.
- tablespace\_files is the name of the tablespace for the APEX files schema.
- tablespace temp is the name of the temporary tablespace or tablespace group.
- images is the virtual directory for APEX images. To support future APEX upgrades, define the virtual image directory as /i/.

#### Example:

@apexins.sql SYSAUX SYSAUX TEMP /i/



 Runtime environment. Run apxrtins.sql passing the following arguments in the order shown:

@apxrtins.sql tablespace\_apex tablespace\_files tablespace\_temp images

#### Where:

- tablespace\_apex is the name of the tablespace for the APEX platform schema.
- tablespace\_files is the name of the tablespace for the APEX files schema.
- tablespace\_temp is the name of the temporary tablespace or tablespace group.
- images is the virtual directory for APEX images. To support future APEX upgrades, define the virtual image directory as /i/.

#### Example:

@apxrtins.sql SYSAUX SYSAUX TEMP /i/

4. Complete appropriate steps in <u>Installing and Configuring APEX and Oracle REST Data Services.</u>

### See Also

- Patching or Upgrading APEX in a CDB
- About the APEX Runtime Environment
- Installing and Configuring APEX and Oracle REST Data Services
- About APEX Database Accounts
- Working with SQLcl in Oracle SQLcl User's Guide

# 5.4 Plugging in a PDB When APEX Is Installed in the Root Container

Learn about scenarios in which the target database has Oracle APEX installed into the root container, CDB\$ROOT - the default installation option.

This section describes scenarios in which the target database has APEX installed into the root container, CDB\$ROOT - the default installation option. Note there are multiple scenarios related to where the database being plugged in originated from and how APEX was configured in the originating database.

- Scenario 1: Plug-in Non-CDB with APEX Plug-in Non-CDB with Oracle APEX.
- Scenario 2: Plug-in PDB with a Common APEX from Another CDB Plug-in a PDB with Oracle APEX from another CDB.
- Scenario 3: Plug-in PDB with a Local APEX from Another CDB Plug-in a PDB with a local Oracle APEX from another CDB.
- Scenario 4: Plug-in Non-CDB or PDB with No APEX
  Plug-in a Non-CDB or PDB if Oracle APEX is not installed.



Working with Incompatible APEX Versions
 Learn how to work with the incompatible versions of Oracle APEX.

## 5.4.1 Scenario 1: Plug-in Non-CDB with APEX

Plug-in Non-CDB with Oracle APEX.

If you are upgrading from a previous Oracle Database release, then you first need to upgrade to a Oracle Database 12c non-CDB (or PDB with locally installed APEX) or and then plug the database into your CDB. Alternatively, if you have configured a non-CDB Oracle Database 12c or later (or PDB with locally installed APEX), you may now want to plug this database into a CDB. In both cases, the originating database has APEX installed and was not formerly a PDB.

As described in the *Oracle Database Installation Guide* for your operating system, when plugging in a standalone database you need to run the <code>\$ORACLE\_HOME/rdbms/admin/noncdb\_to\_pdb.sql script</code>. This script creates the necessary metadata linked objects, instead of local objects and recompiles the database objects for all common database options, including APEX.

After installing APEX, you need to configure the web server for the PDB.

If the version of APEX installed in the originating database (which is now a PDB) is different from what is installed into the root container of the target, an error will be raised when trying to open the PDB.

### See Also

- Installing and Configuring APEX and Oracle REST Data Services
- Working with Incompatible APEX Versions

# 5.4.2 Scenario 2: Plug-in PDB with a Common APEX from Another CDB

Plug-in a PDB with Oracle APEX from another CDB.

If you are copying or moving a PDB from an existing Oracle Database 12c or later where the originating CDB had APEX installed in the root container, you will not need to perform any additional steps, other than configuring the web server for the PDB.

This scenario assumes APEX release 24.2 is installed and the APEX\_240200 schema within the PDB being plugged in already has the metadata linked objects defined and will compile without error against the metadata linked objects within the target CDB.

If the version of APEX installed in the originating database is different from what is installed in the root container of the target an error is raised when trying to open the PDB.

### See Also

- Installing and Configuring APEX and Oracle REST Data Services
- Working with Incompatible APEX Versions



## 5.4.3 Scenario 3: Plug-in PDB with a Local APEX from Another CDB

Plug-in a PDB with a local Oracle APEX from another CDB.

If you are copying or moving a PDB from an existing Oracle Database 12c or later where APEX was not installed in the root container but is installed locally, then you need to perform additional steps before the PDB can be opened without errors.

This scenario assumes APEX release 24.2 is installed and the APEX\_240200 schema within the PDB being plugged in contains all of the APEX database objects and has no metadata linked objects. Therefore, you need to run \$ORACLE\_HOME/rdbms/admin/apex\_to\_common.sql to remove the common objects and create the metadata links for the packages, views and so forth.

To replace local objects with metadata links in the PDB:

- 1. Change your working directory to \$ORACLE\_HOME/rdbms/admin.
- Start SQLcl and connect to the database where APEX is installed as SYS specifying the SYSDBA role. For example:
  - On Windows:

```
SYSTEM_DRIVE:\ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS_password
```

On UNIX and Linux:

```
$ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS password
```

**3.** Set the container to the PDB to be configured:

```
ALTER SESSION SET CONTAINER = <PDB_name>;
```

4. Run apex\_to\_common.sql. For example:

```
@apex_to_common.sql
```

If the version of APEX installed in the originating database is different from what is installed in the root container of the target an error is raised when trying to open the PDB.



Working with Incompatible APEX Versions

# 5.4.4 Scenario 4: Plug-in Non-CDB or PDB with No APEX

Plug-in a Non-CDB or PDB if Oracle APEX is not installed.

In this scenario, the APEX schema, such as APEX\_240200 for Oracle APEX release 24.2, will not be present in the originating database or the PDB being plugged in. In order to open the



PDB without issue and be able to run APEX within the new PDB, you must install APEX into the originating database or PDB before attempting to plug in to the target database. You should install the same version of APEX into the originating database or PDB as the version installed into the target database.

# 5.4.5 Working with Incompatible APEX Versions

Learn how to work with the incompatible versions of Oracle APEX.

If the version of APEX in the root container, CDB\$ROOT, is not the same as the APEX version in the PDB then an error is raised every time the PDB is opened preventing normal database operations within the PDB. The PDB can only be opened in restricted mode by users with RESTRICTED SESSION privilege, until the versions are compatible.

- Patching or Upgrading APEX in a CDB
   Learn how to patch or upgrade Oracle APEX in the root container.
- Patching or Upgrading APEX in a PDB
   Learn how to patch or upgrade Oracle APEX in a PDB.

### 5.4.5.1 Patching or Upgrading APEX in a CDB

Learn how to patch or upgrade Oracle APEX in the root container.

If the version of APEX in the PDB is a later minor release version than the version of APEX in the root container (for example, the PDB contains APEX release 5.1.4 and the CDB contains APEX release 5.1.3) then you must patch the version of APEX in the root container to be able to open the PDB without error. If the major version of APEX in the PDB is higher than the version in the CDB (for example the PDB has APEX release 19.2 and the CDB has APEX release 18.1) then you must upgrade the version of APEX in the CDB to be able to open the PDB without error.

To patch APEX in the root container:

- Download the appropriate patch from My Oracle Support.
- 2. Unzip and extract the installation files.
- 3. Change your working directory to where the installation files were extracted
- 4. Start SQLcl and connect to the database where APEX is installed as SYS specifying the SYSDBA role. For example:
  - On Windows:

```
SYSTEM_DRIVE:\ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS_password
```

On UNIX and Linux:

```
$ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS_password
```

5. Run apxpatch\_con.sql for example:

```
@apxpatch_con.sql
```



6. Follow the instructions outlined in the Patch Set Notes for updating the images directory.

(i) See Also

Installing APEX into a CDB

### 5.4.5.2 Patching or Upgrading APEX in a PDB

Learn how to patch or upgrade Oracle APEX in a PDB.

If the minor version of APEX in the PDB is lower than the version of APEX in the root container (for example the PDB has APEX release 4.2.0 and the CDB has APEX release 4.2.6) then it will be necessary to patch the version of APEX in the PDB. If the major version of APEX in the PDB is lower than the version in the root container (for example, the PDB has APEX release 4.2 and the CDB has APEX release 19.2) then the version of APEX in the PDB will need to be upgraded.

- Patching APEX in a PDB
   Learn how to patch Oracle APEX in a PDB.
- Upgrading APEX in a PDB
   Learn how to upgrade Oracle APEX in a PDB.

### 5.4.5.2.1 Patching APEX in a PDB

Learn how to patch Oracle APEX in a PDB.

To patch APEX in a PDB:

- Download the appropriate patch from My Oracle Support.
- Unzip and extract the installation files.
- Change your working directory to where the installation files were extracted.
- 4. Start SQLcl and connect to the database where APEX is installed as SYS specifying the SYSDBA role. For example:
  - On Windows:

```
SYSTEM_DRIVE:\ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS password
```

On UNIX and Linux:

```
$ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS_password
```

**5.** Run apxpatch.sql using catcon.pl like the following example:

```
host &OH_HOME/perl/bin/perl -I

&OH_HOME/rdbms/admin &OH_HOME/rdbms/admin/catcon.pl -b apxpatch -c
'<PDB_name>' apxpatch.sql
```



#### Where:

- &OH\_HOME represents the full path to the Oracle home
- <PDB\_name> is the name of the PDB you are patching
- 6. Follow the instructions outlined in the patch set notes for updating the images directory.

### 5.4.5.2.2 Upgrading APEX in a PDB

Learn how to upgrade Oracle APEX in a PDB.

To upgrade APEX in a PDB:

- Unzip and extract the installation files.
- 2. Change your working directory to where the installation files were extracted.
- 3. Start SQLcl and connect to the database where APEX is installed as SYS specifying the SYSDBA role. For example:
  - On Windows:

```
SYSTEM_DRIVE:\ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS password
```

On UNIX and Linux:

```
$ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS_password
```

4. Run apexins\_nocdb.sql or apxrtins\_nocdb.sql using catcon.pl like the following example:

```
host &OH_HOME/perl/bin/perl -I

&OH_HOME/rdbms/admin &OH_HOME/rdbms/admin/catcon.pl -b apexins -c
'<PDB_name>' apexins_nocdb.sql --pSYSAUX --pSYSAUX --pTEMP --p/i/ --p1,2,3
```

#### Where:

- &OH HOME represents the full path to the Oracle home
- <PDB\_name> is the name of the PDB you are patching
- 5. Follow the instructions outlined in the patch set notes for updating the images directory.

# 5.5 Plugging in a PDB When APEX Is Not in the Root Container of the Target CDB

The scenarios in this section describe when Oracle APEX is not installed in the root container, CDB\$ROOT, by explicitly removing it as described in "Uninstalling APEX from a CDB."

In such cases, you can optionally install a APEX into each PDB independently. If APEX is installed into a PDB it is considered to be installed locally and has no metadata linked objects.



There are multiple scenarios related to where the database being plugged in originated from and how APEX was configured in the originating database.

- Scenario 1: Plug-in a Non-CDB or PDB with Locally Installed APEX
  Plug-in a Non-CDB or PDB with locally installed Oracle APEX.
- Scenario 2: Plug-in PDB with Common APEX from Another CDB Plug-in a PDB with Oracle APEX from another CDB.
- Scenario 3: Plug-in PDB with a Local APEX from Another CDB Plug-in a PDB with local Oracle APEX from another CDB.
- Scenario 4: Plug-in a Non-CDB or PDB with No APEX
  Plug-in a Non-CDB or PDB if Oracle APEX is not installed.
  - (i) See Also

Uninstalling APEX from a CDB

# 5.5.1 Scenario 1: Plug-in a Non-CDB or PDB with Locally Installed APEX

Plug-in a Non-CDB or PDB with locally installed Oracle APEX.

As described in the *Oracle Database Installation Guide* for your operating system, when plugging in a standalone database you need to run the <code>\$ORACLE\_HOME/rdbms/admin/noncdb\_to\_pdb.sql</code> script. This script creates the necessary metadata linked objects (instead of local objects) and recompiles the database objects for all common database options. However, because APEX has been removed from the root container, the script will not create any metadata links for any of the APEX objects. The script does not change the APEX installation from the originating database and no additional steps are needed other than configuring the web server.

(i) See Also

Installing and Configuring APEX and Oracle REST Data Services

# 5.5.2 Scenario 2: Plug-in PDB with Common APEX from Another CDB

Plug-in a PDB with Oracle APEX from another CDB.

If you are copying or moving a PDB from an existing Oracle Database where the originating CDB had APEX installed in the root container, then an error is raised whenever you try to open the PDB. The error is due to the originating PDB included metadata links to objects in the originating root container which cannot be recompiled because the target root container does not include APEX. You will not be able to open the PDB unless you remove APEX from the PDB or if APEX is already installed in the target root container. Oracle does not support installing APEX in the root container if it contains PDBs with locally installed APEX.



### 5.5.3 Scenario 3: Plug-in PDB with a Local APEX from Another CDB

Plug-in a PDB with local Oracle APEX from another CDB.

If you are copying or moving a PDB from an existing Oracle Database where the originating PDB had a local APEX installed (not in the CDB) then you do not need to perform any additional steps, other than configuring the web server in the PDB.

This scenario assumes APEX release 24.2 is installed and the APEX 240200 schema within the PDB being plugged in, already has all of the APEX objects defined locally and no metadata links.



### (i) See Also

Installing and Configuring APEX and Oracle REST Data Services

## 5.5.4 Scenario 4: Plug-in a Non-CDB or PDB with No APEX

Plug-in a Non-CDB or PDB if Oracle APEX is not installed.

If you are plugging in a non-CDB, or copying or moving a PDB from another CDB, where APEX was not installed in the originating database or PDB then you do not need to perform any additional steps. There will be no APEX engine schema, such as APEX\_240200, within the PDB, and the PDB can be started without error.

# Installing and Configuring APEX and Oracle REST Data Services

Install or upgrade Oracle APEX by downloading a ZIP file from the APEX download page and then downloading and installing Oracle REST Data Services (ORDS). These instructions apply to both new and upgrade installations.

### Performing Pre-installation Tasks for APEX

Review and perform pre-installation tasks before installing Oracle APEX.

### About SQLcl Support

Oracle SQL Developer Command Line (SQLcI) is a Java-based command-line interface for Oracle Database.

### Downloading and Installing APEX

Learn about downloading and installing Oracle APEX.

### Downloading and Installing Oracle REST Data Services (ORDS)

Learn about downloading and installing Oracle REST Data Services (ORDS).

#### Configuring Oracle REST Data Services

Configuring Oracle REST Data Services requires that you copy the images directory, if you are using an older release validate the Oracle REST Data Services installation, configure static files support, and secure Oracle REST Data Services.

### Enabling Network Services in Oracle Database

Database administrators must enable network services in Oracle Database to send outbound mail, invoke web services, or use template-based PDF report printing with external print servers in Oracle APEX.

### Performing Security Tasks

Oracle recommends configuring and using Secure Sockets Layer (SSL) to ensure that passwords and other sensitive data are not transmitted in clear text in HTTP requests.

### Controlling the Number of Concurrent Jobs

Learn about specifying the number of concurrently running jobs.

#### About Running APEX in Other Languages

You can install a single instance of Oracle APEX with one or more translated versions.

### Installing Translated Versions of APEX

Learn about installing translated versions of Oracle APEX.

### Creating a Workspace and Adding APEX Users

Before you can develop or install applications, you must create a workspace, add Oracle APEX users, and sign in to your workspace.

### Performing Post Installation Tasks for Upgrade Installations

Once you have verified that your upgrade installation was successful and all upgraded applications function properly, you should remove schemas from prior Oracle APEX installations.

### About Performance Optimization Tasks

Learn about performance optimization.



Converting Between Runtime and Full Development Environments
 Learn about converting between runtime and full development environments.

(i) See Also

Web Server Requirements

# 6.1 Performing Pre-installation Tasks for APEX

Review and perform pre-installation tasks before installing Oracle APEX.

Before installing APEX, Oracle recommends that you complete the following steps:

- 1. Review and satisfy all APEX installation requirements.
- If you are actively using APEX and upgrading the current installation, then shut down with normal or immediate priority the Oracle Database instances where you plan to install APEX. On Oracle Real Application Clusters (Oracle RAC) systems, shut down all instances on each node.

An alternative to shutting down the database, you can prevent all users from accessing APEX when upgrading your installation from a previous release of APEX. Oracle only recommends this option in high availability production environments where planned outages are not available. For all other scenarios, the database should be shut down.

To disable access to APEX, shut down the appropriate application server where Oracle REST Data Services is deployed.

Once you have prevented access from APEX users, log in to SQLcl as SYS, connecting to the database where APEX is installed, and query V\$SESSION to ensure there are no long running sessions which would interfere with the upgrade process.

3. Back up the Oracle Database installation.

Oracle recommends that you create a backup of the current Oracle Database installation before you install APEX. You can use Oracle Database Recovery Manager, which is included in the Oracle Database installation, to perform the backup.

Start the Oracle Database instance that contains the target database.

After backing up the system, you must start the Oracle instance that contains the target Oracle Database.

- (i) See Also
  - Oracle APEX Installation Requirements
  - Oracle Database Backup and Recovery User's Guide



# 6.2 About SQLcl Support

Oracle SQL Developer Command Line (SQLcI) is a Java-based command-line interface for Oracle Database.

It should be used as the command line interface for running the SQL scripts mentioned in this book.



Working with SQLcl in Oracle SQLcl User's Guide

# 6.3 Downloading and Installing APEX

Learn about downloading and installing Oracle APEX.

How you install Oracle APEX depends upon by the type of database into which you are installing. This chapter describes how to download and install Oracle APEX in self-managed databases, such as your laptop or your data center, or co-managed Cloud databases such as Database Cloud Service (DBaaS) and Exadata Cloud Service.



In fully managed Cloud databases, such as an Autonomous Database or Oracle APEX Application Development (APEX Service), APEX is pre-installed and pre-configured, so you may skip the steps listed in this chapter. To learn more, refer to the documentation for your service.

- Installing APEX
  - Install Oracle APEX by downloading a ZIP file from the APEX download page.
- Creating or Updating Your Instance Administration Account
   Learn how to create or update Instance Administrator account.
- Restarting Processes
  - Restart the processes that you stopped before you began the installation.
- Configuring the APEX\_PUBLIC\_USER Account
   It is important to correctly configure the APEX\_PUBLIC\_USER account to enable proper operation of Oracle APEX.
- Configuring the APEX\_PUBLIC\_ROUTER Account
   The APEX\_PUBLIC\_ROUTER account is a minimally privileged account used for an ORDS REST module to resolve friendly URLs.

### **Related Topics**

- Utilizing Multitenant Architecture
  - Learn about installation choices and different scenarios associated with copying and moving pluggable databases introduced by the multitenant architecture with respect to Oracle APEX.
- Welcome to Oracle APEX Application Development Service in Getting Started with Oracle APEX Application Development



 Create Applications with Oracle APEX on Autonomous Database in Using Oracle Autonomous Database Serverless

## 6.3.1 Installing APEX

Install Oracle APEX by downloading a ZIP file from the APEX download page.



APEX must be installed from a writable directory on the file system. See <u>Reviewing a Log of an Installation Session</u>.

#### To install APEX:

1. For installations where the development will be in English only, download the file apex\_24.2\_en.zip from the APEX download page. If the development will include languages other than English, download apex\_24.2.zip from the APEX download page. See:

https://www.oracle.com/tools/downloads/apex-downloads.html

Note that the actual file name may differ if a more recent release has shipped since this document was published.

- 2. Unzip downloaded zip file:
  - If English only, unzip apex\_24.2\_en.zip as follows, preserving directory names:
    - UNIX and Linux: \$ unzip apex 24.2 en.zip
    - Windows: Double click the file apex\_24.2\_en.zip in Windows Explorer
  - If multiple languages, unzip apex\_24.2.zip as follows, preserving directory names:
    - UNIX and Linux: \$ unzip apex\_24.2.zip
    - Windows: Double click the file apex\_24.2.zip in Windows Explorer

### Note

You should keep the directory tree where you unzip the files short and not under directories that contain spaces. For example, within Windows unzip to  $C:\TEMP$ .

- 3. Change your working directory to apex.
- **4.** Start SQLcl and connect to the database where APEX is installed as SYS specifying the SYSDBA role. For example:
  - · On Windows:

SYSTEM\_DRIVE:\ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS\_password



On UNIX and Linux:

```
$ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS_password
```

- 5. Disable any existing password complexity rules for the default profile.
- 6. Select the appropriate installation option.

**Full development environment** provides complete access to the App Builder environment to develop applications. A **Runtime environment** enables users to run applications that cannot be modified.

Available installation options include:

• **Full development environment**. Run apexins.sql passing the following four arguments in the order shown:

```
@apexins.sql tablespace_apex tablespace_files tablespace_temp images
```

#### Where:

- tablespace\_apex is the name of the tablespace for the APEX application user.
- tablespace\_files is the name of the tablespace for the APEX files user.
- tablespace\_temp is the name of the temporary tablespace or tablespace group.
- images is the virtual directory for APEX images. To support future APEX upgrades, define the virtual image directory as /i/.

#### Example:

```
@apexins.sql SYSAUX SYSAUX TEMP /i/
```

### Note

If you receive the following error, exit SQLcl and change your working directory to where you unzipped the installation file, for example  $C:\TEMP$  in Windows, before starting SQLcl:

```
SP2-0310: unable to open file "apexins.sql"
```

• Runtime environment. Run apxrtins.sql passing the following arguments in the order shown:

```
@apxrtins.sql tablespace apex tablespace files tablespace temp images
```

### Where:

- tablespace\_apex is the name of the tablespace for the APEX application user.
- tablespace\_files is the name of the tablespace for the APEX files user.
- tablespace\_temp is the name of the temporary tablespace or tablespace group.
- images is the virtual directory for APEX images. To support future APEX upgrades, define the virtual image directory as /i/.



#### Example:

@apxrtins.sql SYSAUX SYSAUX TEMP /i/

### (i) See Also

- About the APEX Runtime Environment
- Configuring Password Protection in Oracle Database Security Guide
- Working with SQLcl in Oracle SQLcl User's Guide
- **About APEX Database Accounts**

### 6.3.2 Creating or Updating Your Instance Administration Account

Learn how to create or update Instance Administrator account.

This section describes how to create or update your Instance Administrator account.



### Tip

Skip this section if you are upgrading from a previous release of Oracle APEX. In an upgrade scenario, the Instance Administrator account and password is preserved and carried over from the prior release.

#### What Is an Instance Administrator?

Instance administrators are superusers that are responsible for managing an entire Oracle APEX instance, including managing workspace provisioning, configuring features and instance settings, and managing security.

About apxchpwd.sql

Running the apxchpwd.sql script enables you to create or update your Instance Administrator account.

Running apxchpwd.sql

Run the apxchpwd.sql script to create and update your Instance Administrator account.

### 6.3.2.1 What Is an Instance Administrator?

Instance administrators are superusers that are responsible for managing an entire Oracle APEX instance, including managing workspace provisioning, configuring features and instance settings, and managing security.

To perform these tasks, an Instance administrator signs in to the Oracle APEX Administration Services application.



### (i) See Also

Oracle APEX Administration Services in Oracle APEX Administration Guide



### 6.3.2.2 About apxchpwd.sql

Running the apxchpwd.sql script enables you to create or update your Instance Administrator account.



### (i) Note

The apxchpwd.sql script is not supported on Oracle Autonomous Database Serverless and Oracle APEX Application Development (APEX Service).

You must run the apxchpwd.sql script in the following scenarios:

- New Oracle APEX installations Run apxchpwd.sql to create an Instance Administrator account and password.
- Converting of a runtime environment to a development environment Run apxchpwd.sql to change the Instance Administrator account password.
- Changing Your Instance Administrator Password -Run apxchpwd.sql to change the password for an existing Instance Administrator account.
- Unlocking Your Instance Administrator Account Run apxchpwd.sql to unlock an existing Instance Administrator account.



### Tip

You do not need to run apxchpwd.sql when upgrading from a previous release of Oracle APEX. In an upgrade scenario, the Instance Administrator account password is preserved and carried over from the prior release.

### 6.3.2.3 Running apxchpwd.sql

Run the apxchpwd.sql script to create and update your Instance Administrator account.

To create or update your Instance Administrator account:

- Change your working directory to the apex directory where you unzipped the installation software.
- Start SQLcI and connect to the database where Oracle APEX is installed as SYS specifying the SYSDBA role. For example:
  - On Windows:

SYSTEM\_DRIVE: \ sql /nolog SQL> CONNECT SYS as SYSDBA Enter password: SYS\_password

On UNIX and Linux:

\$ sql /nolog SQL> CONNECT SYS as SYSDBA Enter password: SYS\_password



3. Run apxchpwd.sql. For example:

@apxchpwd.sql

Follow the on-screen instructions. You will be prompted provide a username, password, and email address. If the account username does not exist, it will be created for you.

### See Also

Working with SQLcl in Oracle SQLcl User's Guide

### 6.3.3 Restarting Processes

Restart the processes that you stopped before you began the installation.

After you install Oracle APEX, you must restart the processes that you stopped before you began the installation.

## 6.3.4 Configuring the APEX\_PUBLIC\_USER Account

It is important to correctly configure the APEX\_PUBLIC\_USER account to enable proper operation of Oracle APEX.

- About the APEX\_PUBLIC\_USER Account
  - The APEX\_PUBLIC\_USER account is created with a random password in a new installation of Oracle APEX.
- Unlocking the APEX\_PUBLIC\_USER Account
   Unlock the APEX\_PUBLIC\_USER account by running a SQL statement.
- Changing the Password for the APEX\_PUBLIC\_USER Account
   Change the password for the APEX\_PUBLIC\_USER account by running a SQL statement.
- About Password Expiration in Oracle Database

You can set PASSWORD\_LIFE\_TIME parameter to unlimited by altering APEX\_PUBLIC\_USER to prevent password expiration. To do this create another profile in which the PASSWORD\_LIFE\_TIME parameter is set to unlimited and alter the APEX\_PUBLIC\_USER account and assign it to the new profile.

### 6.3.4.1 About the APEX\_PUBLIC\_USER Account

The APEX\_PUBLIC\_USER account is created with a random password in a new installation of Oracle APEX.

You must change the password for this account before configuring the database access descriptor (DAD) in a new installation.



### 6.3.4.2 Unlocking the APEX PUBLIC USER Account

Unlock the APEX\_PUBLIC\_USER account by running a SQL statement.



If you are upgrading from a prior release of Oracle APEX, this step is unnecessary.

To unlock the APEX\_PUBLIC\_USER account:

- Start SQLcl and connect to the database where Oracle APEX is installed as SYS specifying the SYSDBA role. If Oracle APEX is installed in the CDB, ensure you connect to CDB\$ROOT. For example:
  - On Windows:

```
SYSTEM_DRIVE:\ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS password
```

On UNIX and Linux:

```
$ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS_password
```

2. Run the following statement:

ALTER USER APEX\_PUBLIC\_USER ACCOUNT UNLOCK

# 6.3.4.3 Changing the Password for the APEX\_PUBLIC\_USER Account

Change the password for the APEX\_PUBLIC\_USER account by running a SQL statement.



If you are upgrading from a prior release of Oracle APEX, this step is unnecessary.

To change the password for the APEX\_PUBLIC\_USER account:

- Start SQLcl and connect to the database where Oracle APEX is installed as SYS specifying the SYSDBA role. If Oracle APEX is installed in the CDB, ensure you connect to CDB\$ROOT. For example:
  - On Windows:

SYSTEM\_DRIVE:\ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS\_password



#### On UNIX and Linux:

\$ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS\_password

#### 2. Run the following statement:

ALTER USER APEX\_PUBLIC\_USER IDENTIFIED BY new\_password

Where new\_password is the new password you are setting for APEX\_PUBLIC\_USER. You will use this password when creating the DAD in the sections that follow.

### 6.3.4.4 About Password Expiration in Oracle Database

You can set PASSWORD\_LIFE\_TIME parameter to unlimited by altering APEX\_PUBLIC\_USER to prevent password expiration. To do this create another profile in which the PASSWORD\_LIFE\_TIME parameter is set to unlimited and alter the APEX\_PUBLIC\_USER account and assign it to the new profile.

In the default profile in Oracle Database, the parameter PASSWORD\_LIFE\_TIME is set to 180. If you are using Oracle Database with Oracle APEX, this causes the password for APEX\_PUBLIC\_USER to expire in 180 days. As a result, your APEX instance will become unusable until you change the password.

### See Also

Oracle Database Security Guide for information on creating profiles and assigning them to database users

### 6.3.5 Configuring the APEX PUBLIC ROUTER Account

The APEX\_PUBLIC\_ROUTER account is a minimally privileged account used for an ORDS REST module to resolve friendly URLs.

### **About Sessions Per User in Oracle Database**

On highly active systems, APEX\_PUBLIC\_ROUTER may reach the maximum number of sessions allowed in the database which results in a "Service Unavailable HTTP 503" error. You can set the SESSIONS\_PER\_USER parameter to "unlimited" by modifying APEX\_PUBLIC\_ROUTER to remove limit on the maximum number of sessions.

Create another profile in which the SESSIONS\_PER\_USER parameter is set to "unlimited" and modify the APEX\_PUBLIC\_ROUTER account and assign it to the new profile.

This behavior differs depending on your version of Oracle REST Data Services (ORDS). For ORDS 24.x and later, all GET requests that reference the /r/ path use an ORDS REST module.

If ORDS was updated after Oracle APEX, you must run sys.validate\_apex.



**After each ORDS upgrade** or if ORDS is installed **after** APEX is installed, you must run the following as sys:

```
-- Run as SYS
set serveroutput on
begin
    sys.validate_apex;
end;
/
```

### (i) See Also

DBA PROFILES in Oracle Database Reference

# 6.4 Downloading and Installing Oracle REST Data Services (ORDS)

Learn about downloading and installing Oracle REST Data Services (ORDS).

The Oracle APEX architecture requires a web server to proxy requests between a web browser and the APEX engine. Oracle REST Data Services meets the requirement but its use goes beyond that of APEX. Oracle REST Data Services simplifies the deployment process because there is no Oracle home required, as connectivity is provided using an embedded JDBC driver.

- <u>Downloading Oracle REST Data Services</u>
   Learn how to download Oracle REST Data Services.
- About Configuring Oracle REST Data Services Behind a Reverse Proxy or Load Balancer
  When Oracle APEX is running behind a reverse proxy or load balancer, it is important to
  communicate the original HTTP hostname and protocol as seen by the user's browser to
  the Oracle APEX engine.
- Web Server HTTP POST Request Limits
   Learn about Web Server HTTP POST request limits.

#### (i) See Also

- Introduction to Oracle REST Data Services in Oracle REST Data Services Developer's Guide
- Installing and Configuring Oracle REST Data Services in Oracle REST Data Services Installation and Configuration Guide



# 6.4.1 Downloading Oracle REST Data Services

Learn how to download Oracle REST Data Services.



### Tip

By default, the context root for accessing Oracle APEX through Oracle REST Data Services is /ords. If you wish to have a context root of /apex for accessing Oracle APEX, rename the ords.war file to apex.war before installing Oracle REST Data Services. See Deploying and Monitoring Oracle REST Data Services in Oracle REST Data Services Installation and Configuration Guide.

#### To download Oracle REST Data Services:

- Download the latest release of Oracle REST Data Services from the Oracle REST Data Services download page.
- Unzip the downloaded zip file into a directory (or folder) of your choice:
  - UNIX and Linux: unzip ords.version.number.zip
  - Windows: Double-click the file ords.version.number.zip in Windows Explorer
- Copy the images directory, apex/images, from the APEX software ZIP to a location on the file system where Oracle REST Data Services is installed.



### Note

This step is optional if you use the APEX static resource of the CDN. See Managing Static Resources (Images).

- Follow and complete all installation and configuration steps described in Installing and Configuring Oracle REST Data Services in Oracle REST Data Services Installation and Configuration Guide.
- 5. For Oracle Database multitenant architecture, ensure that you configure the connection using the service name of the specific pluggable database (PDB) you want to access. Do not use the service name of the CDB\$ROOT unless you are configuring Oracle REST Data Services to address PDBs through the URL. See Using the Multitenant Architecture with Oracle REST Data Services in Oracle REST Data Services Installation and Configuration Guide for more information.

# 6.4.2 About Configuring Oracle REST Data Services Behind a Reverse Proxy or Load Balancer

When Oracle APEX is running behind a reverse proxy or load balancer, it is important to communicate the original HTTP hostname and protocol as seen by the user's browser to the Oracle APEX engine.

The Oracle APEX engine uses this information to generate valid URLs in HTML responses and HTTP redirects that the user's browser can successfully follow. The exact configuration steps depend on your Java EE application server. For example, for Oracle WebLogic Server, this is



accomplished using Oracle WebLogic Server Proxy Plug-Ins. To learn more, see your Java EE application server documentation.

### 6.4.3 Web Server HTTP POST Request Limits

Learn about Web Server HTTP POST request limits.

When running Oracle REST Data Services (ORDS) in standalone mode or within a Tomcat Java Container, size limits are being imposed on POST requests which are not file uploads. Oracle APEX users will encounter these limits when uploading data in SQL Workshop using copy and paste or when using copy and paste while building an application from spreadsheet.

When running Oracle REST Data Services in Standalone Mode, the default limit is 200 KB for ORDS 19.4.6 and earlier. It is recommended to increase the limit as follows:

Set the Java System property org.eclipse.jetty.server.Request.maxFormContentSize to a higher value in bytes. You can set this property upon startup of Oracle REST Data Services. For example: java -

Dorg.eclipse.jetty.server.Request.maxFormContentSize=3000000 -jar ords.war

When running on Apache Tomcat, the default limit is 2 megabytes. Adjust Apache Tomcat's maxPostSize parameter to change that limit.



#### See Also

http://tomcat.apache.org/ for more information.

# 6.5 Configuring Oracle REST Data Services

Configuring Oracle REST Data Services requires that you copy the images directory, if you are using an older release validate the Oracle REST Data Services installation, configure static files support, and secure Oracle REST Data Services.

- Managing Static Resources (Images) Manage images and static resources used by an Oracle APEX installation.
- Validating the Oracle REST Data Services Installation In a new installation or upgrade of Oracle APEX and if you are using Oracle REST Data Services 21.2.1 or older, you must validate the Oracle REST Data Services installation.
- Configuring Static File Support For configuring static files, you must run apex\_rest\_config.sql after a new installation of Oracle APEX.
- Securing Oracle REST Data Service In a configuration for Oracle APEX, Oracle recommends setting the parameter security.requestValidationFunction to wwv flow epg include modules.authorize.

# 6.5.1 Managing Static Resources (Images)

Manage images and static resources used by an Oracle APEX installation.

The images and static resources used by an Oracle APEX installation can either be stored on the local file system accessible by Oracle REST Data Services, or referenced to the Oracle APEX static resources Content Delivery Network (CDN).



#### Copying the Images Directory

Store images and static resources used by an Oracle APEX installation on a local filesystem accessible by Oracle REST Data Services.

### Using a Static Resources CDN

Reference images and static resources used by an Oracle APEX instance by referencing a static resources Content Delivery Network (CDN).

### 6.5.1.1 Copying the Images Directory

Store images and static resources used by an Oracle APEX installation on a local filesystem accessible by Oracle REST Data Services.

### (i) Note

Skip this step if you choose to use the Oracle APEX static resources CDN as described in <u>Using a Static Resources CDN</u>.

Perform this task whether you are loading a new installation or upgrading from a previous version. To host the images and static resources on a local file system, you must copy the images directory from the top level of the apex\images directory, for example C:\TEMP, to the location used by your Oracle REST Data Services installation.

During an upgrade, you overwrite your existing images directory. Before you begin the upgrade, to ensure that you can revert to the previous version, Oracle recommends that you create a copy of your existing images directory for APEX, indicating the release number of the images (for example, images\_24\_1).

### 6.5.1.2 Using a Static Resources CDN

Reference images and static resources used by an Oracle APEX instance by referencing a static resources Content Delivery Network (CDN).

Using the CDN may improve performance of APEX and your applications by distributing the static resources from a server that is physically located near the end user. Enabling the CDN for your APEX instance is a one-time configuration step. The CDN reference is automatically updated during patches and upgrades to point to the appropriate CDN for that version.

To use the APEX static resources CDN, connect to the database as a user with the APEX\_ADMINISTRATOR\_ROLE role and run the following code:



### 6.5.2 Validating the Oracle REST Data Services Installation

In a new installation or upgrade of Oracle APEX and if you are using Oracle REST Data Services 21.2.1 or older, you must validate the Oracle REST Data Services installation.

For validating the Oracle REST Data Services installation in a new installation or upgrade of Oracle APEX, run the following command:

java -jar ords.war validate [--database <dbname>]



### See Also

Repairing the Oracle REST Data Services Installation in Oracle REST Data Services Installation and Configuration Guide

### 6.5.3 Configuring Static File Support

For configuring static files, you must run apex\_rest\_config.sql after a new installation of Oracle APEX.

Oracle APEX enables application developers to include static files with their applications. Static files can be associated with a workspace, an application, a plug-in, or an application theme. When using Oracle REST Data Services as your web server, static files are served using RESTful service module built into Oracle APEX. Therefore, you must run apex\_rest\_config.sql after a new installation of Oracle APEX.

# 6.5.4 Securing Oracle REST Data Service

In a configuration for Oracle APEX, Oracle recommends setting the parameter  ${\tt security.requestValidationFunction}\ to\ {\tt wwv\_flow\_epg\_include\_modules.authorize}.$ 

Set parameter security.requestValidationFunction to wwv flow epg include modules.authorize activates the allowed list of callable procedures which ships with Oracle APEX and prohibits calls to other procedures.



### (i) See Also

About Configuring Oracle REST Data Services with Oracle APEX in Oracle APEX App Builder User's Guide

# 6.6 Enabling Network Services in Oracle Database

Database administrators must enable network services in Oracle Database to send outbound mail, invoke web services, or use template-based PDF report printing with external print servers in Oracle APEX.

To learn more, see Enabling Network Services in Oracle Database in Oracle APEX Installation Guide.





Enabling network services does not apply to APEX instances running on Oracle Autonomous Database. APEX can communicate with external endpoints over the internet without additional configuration.

- When and Why Network Services Must be Enabled Enabling network services enables support for sending outbound mail in Oracle APEX, using REST Services, REST Enabled SQL, or other web services, and using a remote server for report printing.
- **Granting Connect Privileges**
- Troubleshooting an Invalid ACL Error Learn how to identify any invalid ACL error by running the query.

# 6.6.1 When and Why Network Services Must be Enabled

Enabling network services enables support for sending outbound mail in Oracle APEX, using REST Services, REST Enabled SQL, or other web services, and using a remote server for report printing.

By default, the ability to interact with network services is disabled in Oracle Database. Therefore, you must use the DBMS NETWORK ACL ADMIN package to grant network connect privileges to the database user that owns the APEX schema (APEX\_240200). Failing to grant these privileges results in issues with:

- Sending outbound mail in Oracle APEX.
  - Users can call methods from the APEX\_MAIL package, but issues arise when sending outbound email.
- Consuming REST services and other web services from APEX.
- Making outbound LDAP calls from APEX.
- Using a remote print server for report printing.

The granted network connect privileges apply to the entire APEX instance and enable all applications in all workspaces to perform outbound network calls. You do not need to grant network connect privileges to individual workspace schemas unless applications also use native database PL/SQL API such as UTL\_HTTP and UTL\_SMTP.



### (i) Note

When upgrading APEX, the upgrade automatically configures Network Services based on the configuration of the previous APEX version.





To run the examples described in this section, the compatible initialization parameter of the database must be set to at least 11.1.0.0.0. By default, the parameter is set properly, but a database upgraded from a version prior to 11g may require an update. For information about changing database initialization parameters, see Specifying the Database Compatibility Level in *Oracle Multitenant Administrator's Guide*.

### See Also

About Report Printing in Oracle APEX App Builder User's Guide.

# 6.6.2 Granting Connect Privileges

The following example demonstrates how to grant connect privileges to any host for the the database user that owns the APEX schema (APEX\_240200). This example assumes you connected to the database where Oracle APEX is installed as SYS specifying the SYSDBA role.

The following example demonstrates how to provide less privileged access to local network resources. This example enables access only to servers running on the same database host (localhost), such as email and report printing servers.



## 6.6.3 Troubleshooting an Invalid ACL Error

Learn how to identify any invalid ACL error by running the query.

If you receive an ORA-44416: Invalid ACL error after running the previous script, use the following query to identify the invalid ACL:

```
REM Show the dangling references to dropped users in the ACL that is assigned
REM to '*'.

SELECT ACL, PRINCIPAL

FROM DBA_NETWORK_ACLS NACL, XDS_ACE ACE

WHERE HOST = '*' AND LOWER_PORT IS NULL AND UPPER_PORT IS NULL AND

NACL.ACLID = ACE.ACLID AND

NOT EXISTS (SELECT NULL FROM ALL USERS WHERE USERNAME = PRINCIPAL);
```

Next, run the following code to fix the ACL:

```
DECLARE
  ACL_ID
         RAW(16);
  CNT
          NUMBER;
BEGIN
  -- Look for the object ID of the ACL currently assigned to '*'
  SELECT ACLID INTO ACL_ID FROM DBA_NETWORK_ACLS
  WHERE HOST = '*' AND LOWER_PORT IS NULL AND UPPER_PORT IS NULL;
  -- If just some users referenced in the ACL are invalid, remove just those
  -- users in the ACL. Otherwise, drop the ACL completely.
  SELECT COUNT(PRINCIPAL) INTO CNT FROM XDS_ACE
  WHERE ACLID = ACL_ID AND
         EXISTS (SELECT NULL FROM ALL_USERS WHERE USERNAME = PRINCIPAL);
  IF (CNT > 0) THEN
    FOR R IN (SELECT PRINCIPAL FROM XDS ACE
               WHERE ACLID = ACL_ID AND
                     NOT EXISTS (SELECT NULL FROM ALL_USERS
                                  WHERE USERNAME = PRINCIPAL)) LOOP
      UPDATE XDB.XDB$ACL
         SET OBJECT_VALUE =
               DELETEXML (OBJECT_VALUE,
                         '/ACL/ACE[PRINCIPAL="'||R.PRINCIPAL||'"]')
       WHERE OBJECT_ID = ACL_ID;
    END LOOP;
  ELSE
    DELETE FROM XDB.XDB$ACL WHERE OBJECT_ID = ACL_ID;
  END IF;
END;
REM commit the changes.
```



COMMIT;

Once the ACL has been fixed, you must run the first script in this section to apply the ACL to the APEX\_240200 user.

# 6.7 Performing Security Tasks

Oracle recommends configuring and using Secure Sockets Layer (SSL) to ensure that passwords and other sensitive data are not transmitted in clear text in HTTP requests.

Without the use of SSL, passwords could potentially be exposed, compromising security.

SSL is an industry standard protocol that uses RSA public key cryptography in conjunction with symmetric key cryptography to provide authentication, encryption, and data integrity.

See Also

Configuring HTTP Protocol Attributes in Oracle APEX Administration Guide

# 6.8 Controlling the Number of Concurrent Jobs

Learn about specifying the number of concurrently running jobs.

- About Managing the Number of Concurrent Jobs
   Learn about managing maximum number of concurrently running jobs.
- Viewing the Number of JOB\_QUEUE\_PROCESSES
  You can view number of JOB\_QUEUE\_PROCESSES in three ways.
- Changing the Number of JOB\_QUEUE\_PROCESSES
   You can change the number of JOB\_QUEUE\_PROCESSES by running a SQL statement in SQLcl.

# 6.8.1 About Managing the Number of Concurrent Jobs

Learn about managing maximum number of concurrently running jobs.

JOB\_QUEUE\_PROCESSES determine the maximum number of concurrently running jobs. In Oracle APEX transactional support and SQL scripts require jobs. If JOB\_QUEUE\_PROCESSES is not enabled and working properly, you cannot successfully execute a script.

## 6.8.2 Viewing the Number of JOB QUEUE PROCESSES

You can view number of JOB\_QUEUE\_PROCESSES in three ways.

- <u>Viewing JOB\_QUEUE\_PROCESSES in the Installation Log File</u> View JOB\_QUEUE\_PROCESSES in the installation log files.
- Viewing JOB\_QUEUE\_PROCESSES in APEX
   View the number of JOB\_QUEUE\_PROCESSES on the About Oracle APEX page.
- Viewing JOB\_QUEUE\_PROCESSES from SQLcl
   View the number of JOB\_QUEUE\_PROCESSES from SQLcl.



### 6.8.2.1 Viewing JOB QUEUE PROCESSES in the Installation Log File

View JOB\_QUEUE\_PROCESSES in the installation log files.

(i) See Also

Reviewing a Log of an Installation Session

### 6.8.2.2 Viewing JOB QUEUE PROCESSES in APEX

View the number of JOB\_QUEUE\_PROCESSES on the About Oracle APEX page.

To view the About Oracle APEX page:

- 1. Sign in to APEX.
- 2. Locate the Help menu at the top of the page.
- **3.** From the Help menu, select **About**.

The About APEX page appears.

4. Scroll down and find JOB\_QUEUE\_PROCESSES at the bottom of the page.

(i) See Also

Signing In to Your Workspace

# 6.8.2.3 Viewing JOB\_QUEUE\_PROCESSES from SQLcl

View the number of JOB\_QUEUE\_PROCESSES from SQLcl.

To view the number of <code>JOB\_QUEUE\_PROCESSES</code> from SQLcl:

- Start SQLcl and connect to the database where Oracle APEX is installed as SYS specifying the SYSDBA role:
  - On Windows:

SYSTEM\_DRIVE:\ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS\_password

On UNIX and Linux:

\$ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS\_password



2. Run the appropriate SQL statement. For example:

```
SELECT VALUE FROM v$parameter WHERE NAME = 'job_queue_processes'
```

## 6.8.3 Changing the Number of JOB\_QUEUE\_PROCESSES

You can change the number of JOB\_QUEUE\_PROCESSES by running a SQL statement in SQLcl.

To update the number of JOB\_QUEUE\_PROCESSES:

- Start SQLcl and connect to the database where Oracle APEX is installed as SYS specifying the SYSDBA role:
  - On Windows:

```
SYSTEM_DRIVE:\ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS password
```

On UNIX and Linux:

```
$ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS password
```

2. In SQLcl run the following SQL statement:

```
ALTER SYSTEM SET JOB_QUEUE_PROCESSES = <number>
```

For example, running the statement ALTER SYSTEM SET JOB\_QUEUE\_PROCESSES = 20 sets JOB\_QUEUE\_PROCESSES to 20.

# 6.9 About Running APEX in Other Languages

You can install a single instance of Oracle APEX with one or more translated versions.

The APEX developer and admin interface is translated into the 9 standard languages: French, German, Italian, Japanese, Korean, Portuguese (Brazil), Simplified Chinese, Spanish, and Traditional Chinese. Developers can choose to run the APEX development environment in any of the installed languages by simply selecting the language from the App Builder sign-in or home page.

The APEX runtime engine which is used by developers to create applications is available in the following additional languages: Arabic, Brazilian Portuguese, Croatian, Czech, Danish, Dutch, Finnish, French, French - Canada, German, Greek, Hebrew, Hungarian, Icelandic Italian, Japanese, Korean, Norwegian, Polish, Portuguese (Portugal) (pt), Romanian, Russian, Serbian - Cyrillic, Serbian - Latin, Simplified Chinese, Slovak, Slovenian, Spanish, Swedish, Thai, Traditional Chinese, Turkish, Ukrainian, and Vietnamese.

A single instance of APEX can be installed with one or more of these translated versions.

In order to install other languages you must use the <code>apex\_24.2.zip</code> file which contains the extra files as described in <a href="Installing Translated Versions of APEX">Installing Translated Versions of APEX</a>. If you previously downloaded <code>apex\_24.2\_en.zip</code>, then you do not need to re-install APEX. Simply download



apex\_24.2.zip and unzip the file into the same directory where you unzipped apex 24.2 en.zip.

The translated version of APEX should be loaded into a database that has a character set that supports the specific language. If you attempt to install a translated version of APEX into a database that does not support the character encoding of the language, the installation may fail or the translated APEX instance may appear corrupt when run. The database character set AL32UTF8 supports all the translated versions of APEX.

You can manually install translated versions of APEX using SQLcl. The installation files are encoded in AL32UTF8.



#### (i) Note

Regardless of the target database character set, to install a translated version of APEX, you must set the character set value of the NLS\_LANG environment variable to AL32UTF8 before starting SQLcl.

The following examples illustrate valid NLS LANG settings for loading APEX translations:

American America.AL32UTF8 Japanese\_Japan.AL32UTF8



#### (i) See Also

**Installing Translated Versions of APEX** 

# 6.10 Installing Translated Versions of APEX

Learn about installing translated versions of Oracle APEX.

- About Installing Translated Versions of APEX
  - Whether you are installing for the first time or upgrading from a previous release, you must run the load\_lang.sql script to run a translated version of Oracle APEX.
- Installing a Translated Version of APEX Learn how to run the appropriate language specific script to install a translated version of Oracle APEX.



#### (i) See Also

Managing Application Globalization in Oracle APEX App Builder User's Guide

# 6.10.1 About Installing Translated Versions of APEX

Whether you are installing for the first time or upgrading from a previous release, you must run the load lang.sgl script to run a translated version of Oracle APEX.



The APEX developer and admin interface is translated into the 9 standard languages: French. German, Italian, Japanese, Korean, Portuguese (Brazil), Simplified Chinese, Spanish, and Traditional Chinese. Developers can choose to run the APEX development environment in any of the installed languages by simply selecting the language from the Sign In page or home page.

The APEX runtime engine which is used by developers to create applications is available in the following languages: Arabic, Brazilian Portuguese, Croatian, Czech, Danish, Dutch, Finnish, French, French - Canada, German, Greek, Hebrew, Hungarian, Icelandic, Italian, Japanese, Korean, Norwegian, Polish, Portuguese (Portugal) (pt), Romanian, Russian, Serbian - Cyrillic, Serbian - Latin, Simplified Chinese, Slovak, Slovenian, Spanish, Swedish, Thai, Traditional Chinese, Turkish, Ukrainian, and Vietnamese.



### Tip

In fully managed Cloud databases such as Oracle Autonomous Database Serverless or Oracle APEX Application Development (APEX Service), APEX is pre-installed and pre-configured with all languages from the above list. Separate installation of the supported languages is unnecessary.

To support additional languages not covered in the above list, developers must provide their own translations. For example, if you develop a Bulgarian application and want to include report messages, such as pagination, in Bulgarian, you must translate the strings used in messages displayed in reports.



#### (i) See Also

Translating Messages Used Internally by APEX in Oracle APEX App Builder User's

# 6.10.2 Installing a Translated Version of APEX

Learn how to run the appropriate language specific script to install a translated version of Oracle APEX.

The installation scripts are located in subdirectories identified by a language code in the unzipped distribution apex/builder. For example, the German version is located in apex/ builder/de and the Japanese version is located in apex/builder/ja. Within each directory, there is a language loading script identified by the language code (for example, load\_de.sql or load ja.sql).



### (i) Note

If you have applied a Patch Set and then install translations, you must re-execute the Patch Set to apply all fixes to the translations.

To install a translated version of APEX:

Set the NLS\_LANG environment variable, making sure that the character set is AL32UTF8. For example:



Bourne or Korn shell:

```
NLS_LANG=American_America.AL32UTF8 export NLS_LANG
```

C shell:

```
setenv NLS LANG American America.AL32UTF8
```

For Windows based systems:

```
set NLS LANG=American America.AL32UTF8
```

- 2. Navigate to the directory under apex/builder based on the language you need to install. For example for German, navigate to apex/builder/de. Start SQLcl and connect to the database where APEX is installed as SYS specifying the SYSDBA role. For example:
  - On Windows:

```
SYSTEM_DRIVE:\ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS_password
```

On UNIX and Linux:

```
$ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS_password
```

3. Execute the appropriate language specific script. For example:

```
@load_lang.sql
```

Where lang is the specific language (for example, load\_de.sql for German or load\_ja.sql for Japanese).

# 6.11 Creating a Workspace and Adding APEX Users

Before you can develop or install applications, you must create a workspace, add Oracle APEX users, and sign in to your workspace.

About Workspaces and Users

A workspace enables multiple users to work within the same Oracle APEX installation while keeping their objects, data, and applications private.

Signing In To Administration Services

Sign in to Oracle APEX Administration Services using the Instance administrator account and password created or reset during the installation process.

Creating a Workspace Manually

Sign in to Oracle APEX Administration Services to create workspace manually.

Creating APEX Users

Create new users in Oracle APEX Administration Services.



Signing In to Your Workspace Sign in to a workspace by navigating to the Oracle APEX Sign In page.

## 6.11.1 About Workspaces and Users

A workspace enables multiple users to work within the same Oracle APEX installation while keeping their objects, data, and applications private.

You access the APEX home page by logging in to a workspace using a JavaScript enabled Web browser.

Each workspace has a unique ID and name. An instance administrator can create a workspace manually within APEX Administration Services or have users submit requests. APEX Administration Services is a separate application for managing an entire APEX instance.

# 6.11.2 Signing In To Administration Services

Sign in to Oracle APEX Administration Services using the Instance administrator account and password created or reset during the installation process.

To manually create a workspace and user accounts, you sign in to a separate application for managing an entire Oracle APEX instance called Oracle APEX Administration Services.

To sign in to Oracle APEX Administration Services:

In a Web browser, navigate to the Administration Services Sign In page:



By default, the context root for accessing Oracle APEX through Oracle REST Data Services is /ords. If you wish to have a context root of /apex for accessing Oracle APEX, rename the ords.war file to apex.war before installing Oracle REST Data Services. See Deploying and Monitoring Oracle REST Data Services in Oracle REST Data Services Installation and Configuration Guide.

By default, Administration Services installs to the following location:

http://hostname:port/ords/apex\_admin

#### Where:

- hostname is the name of the system where Oracle REST Data Services is installed.
- port is the port number assigned when configuring Oracle REST Data Services. In a default installation, this number is 8080. To learn more, see Installing and Configuring Oracle REST Data Services in Oracle REST Data Services Installation and Configuration Guide.
- ords is the service name defined when configuring Oracle REST Data Services.
- On the Sign In page:
  - Username Enter the Instance administrator account username specified in Creating or Updating Your Instance Administration Account.
  - Password Enter your Instance administrator account password.
  - Click Sign In to Administration.



Oracle APEX Administration Services appears.

Note that, depending on your setup, you might be required to change your password when you log in for the first time.

### See Also

Oracle APEX Administration Services in Oracle APEX Administration Guide

## 6.11.3 Creating a Workspace Manually

Sign in to Oracle APEX Administration Services to create workspace manually.

To manually create a workspace you sign in, sign in to APEX Administration Services using the ADMIN account and password created or reset during the installation process.

To create an APEX workspace manually:

1. Access APEX Administration Services.

Administration Services appears. Next, create a workspace.

- 2. Click Manage Workspaces.
- Under Workspace Actions, click Create Workspace.

The Create Workspace Wizard appears.

- 4. For Identify Workspace, enter the following:
  - a. Workspace Name Enter a unique workspace name.
  - b. Workspace ID Leave Workspace ID blank to have the new Workspace ID automatically generated. A Workspace ID must be a positive integer greater than 100000.
  - c. Workspace Description Enter a workspace description.
  - d. Click Next.
- For Identify Schema, specify whether you are re-using an existing schema or creating a new one.

If you are using an existing schema:

- a. For Re-use existing schema, select Yes.
- b. Select a schema from the list.
- c. Click Next.

If you are creating a new schema:

- a. For Re-use existing schema, select No.
- b. Enter a schema name and password.
- **c.** Specify a space quota.
- d. Click Next.
- For Identify Administrator, enter the Workspace administrator information and click Next.
- Confirm your selections and click Create Workspace.



### (i) See Also

- Creating Workspaces in Administration Services in Oracle APEX Administration Guide
- Managing Existing Workspaces in Oracle APEX Administration Guide

# 6.11.4 Creating APEX Users

Create new users in Oracle APEX Administration Services.

Create new users by signing into the APEX Administration Services application using your Instance administrator password.

To create an APEX user account:

- Sign in to APEX Administration Services.
- Click Manage Workspaces.
- Under Workspace Actions, click Manage Developers and Users.

The Manage Developers and Users page appears.

- Click Create User.
- Under User Attributes, enter the appropriate information. Fields marked with an asterisk are required.



Most attributes in APEX include field-level Help. Attributes with field-level Help. have light gray icon that resembles a question mark (?). To view field-level Help, click the Help icon.

- **Under Account Privileges:** 
  - Workspace Select a workspace from the list.
  - b. **Default Schema** Specify the default schema used for this user

When using workspaces that have more than one schema available, this schema is the default. This setting does not control security, only the user's preference.

User is an administrator - Specify if this user should have workspace administrator privileges.

Administrators are given access to all components. Additionally, they can manage user accounts, groups, and development services. Components may not be available if they are switched off by Instance Administrators.

d. User is a developer - Specify if this user should have developer privileges.

Developers must have access to either App Builder, SQL Workshop, or both. These components may not be available if they are switched off by the Instance Administrator.

App Builder Access - Determines whether a developer has access to the App Builder.



- f. SQL Workshop Access Determines whether a developer has access to the SQL Workshop.
- g. Team Development Access Determines whether a developer has access to the Team Development.
- h. Set Account Availability Select Locked to prevent the account from being used. Select Unlocked to allow the account to be used.

If the user has exceeded the maximum log in failures allowed, specified in Workspace Preferences, then their account will be locked automatically.

- a. Workspace Select a workspace in which to create the user.
- Default Schema Select the default schema for this user.
- c. Accessible Schemas (null for all) Enter a colon-delimited list of schemas for which this developer has permissions when using the SQL Workshop.

The list of schemas you enter here restricts the user to a subset of the full set of schemas provisioned for the workspace and determines what schema names the user sees in SQL Workshop.

d. User is an administrator - Select Yes or No to specify if this user should have workspace administrator privileges.

Administrators are given access to all components. Additionally, they can manage user accounts, groups, and development services. Components may not be available if they are switched off by an Instance Administrator.

 User is a developer - Select Yes or No to specify if this user should have developer privileges.

Developers must have access to either the App Builder, SQL Workshop, or both. Components may not be available if they are switched off by Instance Administrators.

- f. App Builder Access Determines whether a developer has access to App Builder
- SQL Workshop Access Determines whether a developer has access to the SQL Workshop.
- Team Development Access Determines whether a user has access to the Team Development.
- Account Availability Select Locked to prevent the account from being used. Select Unlocked to allow the account to be used.
- 7. Under Password:
  - Password Enter a case sensitive password.
  - Confirm Password Enter the password again.
  - Require Change of Password On First Use Select No to allow the user to use the same password until it expires. Select Yes to require the user to change the password immediately when logging in the first time.
- 8. Click Create User or Create and Create Another.

#### (i) See Also

Managing Users Across an Oracle APEX Instance in *Oracle APEX Administration Guide* 



# 6.11.5 Signing In to Your Workspace

Sign in to a workspace by navigating to the Oracle APEX Sign In page.

After you create a workspace and APEX users, you can sign in to your workspace using your credentials (that is, your workspace name, user name and password).

To sign in to a workspace:

In a Web browser, navigate to the APEX Sign In page:

http://hostname:port/apex/

#### Where:

- hostname is the name of the system where Oracle REST Data Services is installed.
- port is the port number assigned when configuring Oracle REST Data Services. In a
  default installation, this number is 8080. To learn more, see Installing and Configuring
  Oracle REST Data Services in Oracle REST Data Services Installation and
  Configuration Guide.
- apex is the service name defined when configuring Oracle REST Data Services.

The Sign In page appears.

- 2. On the Sign In page, enter:
  - Workspace Enter the name of your workspace.
  - Username Enter your user name.
  - Password Enter your case-sensitive password.
- Click Sign In.

Note that, depending on your setup, you might be required to change your password when you log in for the first time.

#### (i) See Also

- Creating Workspaces in Administration Services in Oracle APEX Administration Guide
- Managing Requests in Oracle APEX Administration Guide

# 6.12 Performing Post Installation Tasks for Upgrade Installations

Once you have verified that your upgrade installation was successful and all upgraded applications function properly, you should remove schemas from prior Oracle APEX installations.

About Removing Prior APEX Installations

Learn about removing schemas from a prior installation by verifying if a prior installation exists.



- Verifying if a Prior Installation Exists
  - Run the SQL query to verify if a prior Oracle APEX installation exists.
- Removing Schemas and SYS Objects from Prior Installations
   Start SQLcl and connect to database and execute a statement to remove schemas and SYS objects.
- Removing Schemas from Prior Installations in a CDB
   Use catcon.pl to remove schemas of prior installations in a CDB.
- <u>Fixing Invalid ACL</u>
   Learn how to fix an invalid ACL.

```
① See Also

Upgrading from a Previous APEX Release
```

# 6.12.1 About Removing Prior APEX Installations

Learn about removing schemas from a prior installation by verifying if a prior installation exists.

The database users associated with schemas from prior installations are privileged users and should be removed when they are no longer necessary. Removing schemas from a prior installation is a two step process. First you verify if a prior installation exists and then you remove the schemas.

# 6.12.2 Verifying if a Prior Installation Exists

Run the SQL query to verify if a prior Oracle APEX installation exists.

To verify if a prior installation exists:

- Start SQLcl and connect to the database where Oracle APEX is installed as SYS. For example:
  - On Windows:

```
SYSTEM_DRIVE:\ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS password
```

On UNIX and Linux:

```
$ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS_password
```

**2.** Run the following query:

```
SELECT username

FROM dba_users

WHERE ( username LIKE 'FLOWS\_____' ESCAPE '\'

OR username LIKE 'APEX\_____' ESCAPE '\')

AND username NOT IN ( SELECT schema
```



```
FROM dba_registry
WHERE comp id = 'APEX' );
```

If the results contain entries in the form <code>FLOWS\_XXXXXX</code> or <code>APEX\_XXXXXX</code> where <code>XXXXXX</code> represents six numbers, those entries are candidates for removal.

# 6.12.3 Removing Schemas and SYS Objects from Prior Installations

Start SQLcI and connect to database and execute a statement to remove schemas and SYS objects.

To remove schemas and SYS objects from prior installations:

- Start SQLcl and connect to the database where Oracle APEX is installed as SYS specifying the SYSDBA role. For example:
  - On Windows:

```
SYSTEM_DRIVE:\ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS_password
```

On UNIX and Linux:

```
$ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS_password
```

2. Execute statements similar to the following example:

```
DROP USER APEX_240100 CASCADE;
DROP PACKAGE SYS.WWV_DBMS_SQL_APEX_240100;
```

# 6.12.4 Removing Schemas from Prior Installations in a CDB

Use catcon.pl to remove schemas of prior installations in a CDB.

To remove schemas and SYS objects from prior installations, run commands using the following example:

```
$ORACLE_HOME/perl/bin/perl -I $ORACLE_HOME/rdbms/admin $ORACLE_HOME/rdbms/
admin/catcon.pl -b drop_apex240100 -- --x'drop user APEX_240100 cascade'
$ORACLE_HOME/perl/bin/perl -I $ORACLE_HOME/rdbms/admin $ORACLE_HOME/rdbms/
admin/catcon.pl -b drop_wwv_dbms_sql -- --x'drop package
SYS.WWV_DBMS_SQL_APEX_240100'
```

# 6.12.5 Fixing Invalid ACL

Learn how to fix an invalid ACL.

After following the instructions in <u>About Removing Prior APEX Installations</u>, you may need to fix an invalid ACL if you are running Oracle Database and you enabled network services for the prior Oracle APEX schema.

To fix an invalid ACL:



- Change your working directory to the apex directory where you unzipped the installation software.
- 2. Start SQLcl and connect to the database where APEX is installed as SYS specifying the SYSDBA role. For example:
  - On Windows:

```
SYSTEM_DRIVE:\ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS_password
```

```
$ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS_password
```

3. Execute a statement similar to the following:

```
EXEC DBMS_NETWORK_ACL_ADMIN.DELETE_PRIVILEGE('power_users.xml',
'APEX_240100');
```

# 6.13 About Performance Optimization Tasks

Learn about performance optimization.

Performance of web applications heavily depends on their size and how often a browser has to request static content like images, CSS, and JavaScript files. To improve performance, most web servers support on-the-fly HTTP response compression and provide settings that enable you to configure how long browsers can cache a file before requesting it again. The HTTP response compression is usually implemented using gzip encoding, while browser file caching is enabled by issuing Cache-Control HTTP response header.

Please see your web server documentation to learn how to enable response compression and browser file caching. For optimal performance of the Oracle APEX development environment and APEX applications, Oracle recommends enabling gzip compression of files in the virtual images directory (for example, /i/) and responses from the database access descriptor in addition to enabling browsers to cache files from the virtual images directory for at least 12 hours.

# 6.14 Converting Between Runtime and Full Development Environments

Learn about converting between runtime and full development environments.

This section describes how to convert between runtime and full development environments.

- About Runtime and Full Development Environments
   An Oracle APEX runtime environment enables users to run an application without supporting the ability to change or edit the application.
- Converting a Runtime Environment to a Full Development Environment
   Start SQLcl and connect to the database where Oracle APEX is installed as SYS specifying the SYSDBA role and run the apxdvins.sgl.



Converting a Full Development Environment to a Runtime Environment
 Start SQLcl and connect to the database where Oracle APEX is installed as SYS specifying the SYSDBA role and run the apxdevrm.sgl.

# 6.14.1 About Runtime and Full Development Environments

An Oracle APEX runtime environment enables users to run an application without supporting the ability to change or edit the application.

A runtime environment includes only the packages necessary to run your applications, making it a more hardened environment. It does not provide a web interface for administration.

You administer an APEX runtime environment using SQLcl or SQL Developer and the APEX INSTANCE ADMIN API.

### (i) See Also

- About the APEX Runtime Environment
- Installing Exported Applications into a Runtime Environment in Oracle APEX Administration Guide

# 6.14.2 Converting a Runtime Environment to a Full Development Environment

Start SQLcl and connect to the database where Oracle APEX is installed as SYS specifying the SYSDBA role and run the apxdvins.sql.

To convert an Oracle APEX runtime environment to a full development environment:

- Change your working directory to the apex directory where you unzipped the installation software.
- 2. Start SQLcl and connect to the database where Oracle APEX is installed as SYS specifying the SYSDBA role. For example:
  - On Windows:

```
SYSTEM_DRIVE:\ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS_password
```

· On UNIX and Linux:

```
$ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS_password
```

**3.** Run apxdvins.sql. For example:

```
@apxdvins.sql
```

4. Follow the instructions in Creating or Updating Your Instance Administration Account.



### (i) See Also

Working with SQLcl in Oracle SQLcl User's Guide

# 6.14.3 Converting a Full Development Environment to a Runtime Environment

Start SQLcl and connect to the database where Oracle APEX is installed as SYS specifying the SYSDBA role and run the apxdevrm.sql.

### Note

To ensure the security and performance of your development environment, this functionality is not available in APEX instances running in Oracle Cloud.

To convert an APEX full development environment to a runtime environment:

- Change your working directory to the apex directory where you unzipped the installation software.
- 2. Start SQLcl and connect to the database where APEX is installed as SYS specifying the SYSDBA role. For example:
  - On Windows:

```
SYSTEM_DRIVE:\ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS password
```

On UNIX and Linux:

```
$ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS_password
```

**3.** Run apxdevrm.sql. For example:

@apxdevrm.sql

### (i) See Also

Working with SQLcl in Oracle SQLcl User's Guide



# Automating the APEX Installation Process

Automate the process of installing and configuring an Oracle APEX instance.

- About apxsilentins.sql
   Run the apxsilentins.sql script to automate the installation and configuration of an Oracle APEX instance.
- Running apxsilentins.sql
   Run the apxsilentins.sql script.

# A.1 About apxsilentins.sql

Run the apxsilentins.sql script to automate the installation and configuration of an Oracle APEX instance.

Traditionally you run the run the apexins.sql script to install Oracle APEX and then perform a multiple other steps to configure the APEX\_PUBLIC\_USER account. The apxsilentins.sql script simplifies the installation and configuation process. apxsilentins.sql accepts additional parameters so that passwords can be passed for following database users associated with the Oracle APEX schema: APEX\_PUBLIC\_USER, APEX\_LISTENER, APEX\_REST\_PUBLIC\_USER and the Oracle APEX Instance Administration user, ADMIN. You can also use these passwords for the configuration of middle tiers and other processes. apxsilentins.sql also completes other installation steps such as creating and setting the password for the Instance Administration user, ADMIN, configuring a network ACL, and configuring Oracle REST Data Services.

Running the apxsilentins.sql script, removes the need for completing the following topics:

- Installing APEX
- Creating or Updating Your Instance Administration Account
- Configuring the APEX PUBLIC USER Account
- Enabling Network Services in Oracle Database
- Configuring Static File Support (apex\_rest\_config.sql)

# A.2 Running apxsilentins.sql

Run the apxsilentins.sql script.

To run apxsilentins.sql:

- Change your working directory to apex.
- 2. Start SQLcl and connect as user SYS to the database where Oracle APEX is installed. You will need to specify the SYSDBA role. For example:
  - On Windows:

SYSTEM\_DRIVE:\ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS\_password



```
$ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS_password
```

- 3. Disable any existing password complexity rules for the default profile.
- 4. Run apxsilentins.sql passing the following eight arguments in the order shown:

```
@apxsilentins.sql tablespace_apex tablespace_files tablespace_temp images
    password_apex_pub_user password_apex_listener
password_apex_rest_pub_user
    password internal admin
```

#### Where:

- tablespace\_apex is the name of the tablespace for the APEX platform schema.
- tablespace\_files is the name of the tablespace for the APEX files schema.
- tablespace\_temp is the name of the temporary tablespace or tablespace group.
- *images* is the virtual directory for APEX images. To support future APEX upgrades, define the virtual image directory as /i/.
- password\_apex\_pub\_user is the password for the APEX\_PUBLIC\_USER database account.
- password\_apex\_listener is the password for the APEX\_LISTENER database account.
- password\_apex\_rest\_pub\_user is the password for the APEX\_REST\_PUBLIC\_USER database account.
- password\_internal\_admin is the password for the Instance Administration ADMIN APEX account. This password must meet the following requirements:
  - Contain at least 6 characters.
  - Contain at least one numeric character (0123456789).
  - Contain at least one punctuation character (!"#\$%&()``\*+,-/:;? ).
  - Contain at least one uppercase alphabetic character.

#### For example:

@apxsilentins.sql SYSAUX SYSAUX TEMP /i/ Passw0rd!1 Passw0rd!2 Passw0rd!3 Passw0rd!4

Once apxsilentins.sql completes, you follow the steps in <u>Downloading and Installing Oracle REST Data Services (ORDS)</u> and <u>Configuring Oracle REST Data Services</u> (except for "Configuring Static File Support").

Use the passwords you supplied to apxsilentins.sql when completing these steps. Then, move on to Creating a Workspace and Adding APEX Users.

# Maximizing Uptime During an APEX Upgrade

Learn how to maximize uptime during an Oracle APEX upgrade.

Previously, APEX could only be upgraded by completely disabling application usage for an extended length of time. The following is an overview of the additional steps you can take to keep your applications usable for end users during most portions of an APEX upgrade.

This advanced procedure is an alternative to the following the topics in <u>Downloading and Installing APEX.</u>

To upgrade the instance, administrators typically run these phases in one step by executing one of the following:

• For full development environment:

```
@apexins.sql tablespace_apex tablespace_files tablespace_temp images
```

For runtime-only environment:

@apxrtins.sql tablespace\_apex tablespace\_files tablespace\_temp images

#### Where:

- tablespace\_apex is the name of the tablespace for the APEX platform schema.
- tablespace\_files is the name of the tablespace for the APEX files schema.
- tablespace\_temp is the name of the temporary tablespace or tablespace group.
- images is the virtual directory for APEX images.

The upgrade of an APEX instance runs in four phases:

- 1. Create database schemas and database objects (tables, packages).
- 2. Migrate application metadata.
- 3. Migrate data that runtime applications modify and switch to the new version.
- Migrate additional log and summary data.

Phases 1 and 4 do not disable end users using the instance. Phase 2 only affects developers who modify applications, and new background processes for Page Processes do not run. Phase 3 affects all access to APEX.

Oracle now also provides alternative upgrade scripts to run the phases independently. Administrators can use these scripts instead of apexins.sql and apxrtins.sql, to reduce the effective downtime of an APEX instance from potentially hours to just a few minutes (depending on hardware performance).



This feature is not supported when APEX is installed in CDB\$ROOT.



Administrators must sequentially execute the following scripts to start phases 1, 2 and 3, respectively. At the end of phase 3, a scheduler job automatically starts to execute phase 4.

To reduce downtime during an APEX upgrade:

- Execute phase 1 script: Development and runtime usage is not affected.
  - For full development environment:

```
@apexins1.sql tablespace apex tablespace files tablespace temp images
```

For runtime-only environment:

```
@apxrtins1.sql tablespace_apex tablespace_files tablespace_temp images
```

#### Example:

```
@apexinsl.sql sysaux sysaux temp /i/
```

- Execute phase 2 script: Development is disabled, but runtime usage is not affected.
  - For full development environment:

```
@apexins2.sql tablespace apex tablespace files tablespace temp images
```

For runtime-only environment:

```
@apxrtins2.sql tablespace apex tablespace files tablespace temp images
```

### Example:

```
@apexins2.sql sysaux sysaux temp /i/
```

- 3. Disable web access for the web server, Oracle REST Data Services.
- Execute phase 3 script: APEX can not be used.
  - For full development environment:

```
@apexins3.sql tablespace_apex tablespace_files tablespace_temp images
```

For runtime-only environment:

```
@apxrtins3.sql tablespace_apex tablespace_files tablespace_temp images
```

```
Example: @apexins3.sql sysaux sysaux temp /i/
```

5. Install images of the new APEX version in your web server. Administrators can do this while phase 3 is running or even earlier, if the new version's images directory is different to the previous APEX version's (for example: /i212/ for the new version vs. /i211/ for the old version).

For details refer to the installation instructions for Oracle REST Data Services.

6. Re-enable web access for the web server and restart Oracle REST Data Services.

After web access is restarted, developers and users can access the instance again, while phase 4 finishes in the background.



(i) See Also

Installing and Configuring APEX and Oracle REST Data Services

C

# **APEX Installation Troubleshooting**

Learn about troubleshooting Oracle APEX Installation.

This section contains information on troubleshooting.

### Reviewing a Log of an Installation Session

The apexins.sql script creates a log file in the apex directory using the naming convention installyyyy-MM-DD\_HH24-MI-SS.log.

Verifying the Validity of an APEX Installation

Verify the validity of an Oracle APEX installation by running a query.

Cleaning Up After a Failed Installation

Learn about best practices for troubleshooting and cleaning up after a failed installation.

About Images Displaying Incorrectly in APEX

Learn about troubleshooting if images in Oracle APEX do not display correctly.

About Page Protection Violation

A page protection violation may be caused by manual alteration of protected page items.

(i) See Also

Upgrading from a Previous APEX Release

# C.1 Reviewing a Log of an Installation Session

The apexins.sql script creates a log file in the apex directory using the naming convention  $installyyyy-MM-DD\_HH24-MI-SS.log$ .

In a successful installation, the log file contains the following text:

Thank you for installing Oracle APEX.

Oracle APEX is installed in the APEX\_240200 schema.

If the log file contains a few errors, it does not mean that your installation failed. Note that acceptable errors are noted as such in the log file.

# C.2 Verifying the Validity of an APEX Installation

Verify the validity of an Oracle APEX installation by running a query.

You can verify the validity of an APEX installation by running the following query:

SELECT STATUS FROM DBA\_REGISTRY WHERE COMP\_ID = 'APEX';

If the result is VALID, you can assume the installation was successful.



# C.3 Cleaning Up After a Failed Installation

Learn about best practices for troubleshooting and cleaning up after a failed installation.

In a successful installation the following banner displays near the end of the installation:

```
Thank you for installing Oracle APEX.

Oracle APEX is installed in the APEX_240200 schema.
```

To reinstall, you must either drop the APEX database schemas, or run a script to completely remove APEX from the database, depending upon the installation type.

- Reverting to a Previous Release After a Failed Upgrade Installation
   Learn about reverting to Oracle APEX to a previous release in the case of a failed upgrade installation.
- Removing APEX from the Database
   Start SQLcl and connect to the database where Oracle APEX is installed as SYS specifying the SYSDBA role and execute the SQL> @apxremov.sql command.

# C.3.1 Reverting to a Previous Release After a Failed Upgrade Installation

Learn about reverting to Oracle APEX to a previous release in the case of a failed upgrade installation.

In the case of a failed upgrade installation, you may want to revert Oracle APEX to a previous release and then remove the schemas associated with the current release.

- Verifying If You Have a Previous Release of APEX
   Run a query to verify if you have previous release of Oracle APEX.
- Reverting the Images Directory
   If you altered your images directory, revert it back to the release you want to revert to. You must point the text alias /i/ back to images directory for the release you want to revert to.
- Reverting to a Previous Release
   Learn how to revert to a previous release Oracle APEX.
- Removing the APEX Release Schema
   After you revert to the prior release, remove the Oracle APEX schema.

# C.3.1.1 Verifying If You Have a Previous Release of APEX

Run a query to verify if you have previous release of Oracle APEX.

To verify whether you have a previous release of APEX:

- 1. Start SQLcl and connect to the database where APEX is installed as SYS specifying the SYSDBA role. For example:
  - On Windows:

SYSTEM\_DRIVE:\ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS\_password



```
$ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS_password
```

2. Execute the following command in SQLcl:

```
select username from dba_users
where regexp_like(username,'(FLOWS|APEX)_\d{6}')
    and username <> (select table_owner from all_synonyms
    where synonym_name = 'WWV_FLOW'
    and owner = 'PUBLIC')
```

If the query above returns any rows, the database contains a previous release of APEX.

# C.3.1.2 Reverting the Images Directory

If you altered your images directory, revert it back to the release you want to revert to. You must point the text alias /i/ back to images directory for the release you want to revert to.

(i) See Also

Copying the Images Directory

# C.3.1.3 Reverting to a Previous Release

Learn how to revert to a previous release Oracle APEX.

- Reverting to Release 1.5
- Reverting to Release 1.6
- Reverting to Release 2.0
- Reverting to Release 2.2
- Reverting to Release 3.0
- Reverting to Release 3.1
- Reverting to Release 3.2
- Reverting to Release 4.0
- Reverting to Release 4.1
- Reverting to Release 4.2 in a non-CDB or PDB with Local APEX
- Reverting to Release 4.2 in a CDB
- Reverting to Release 5.0 in a non-CDB or PDB with Local APEX
- Reverting to Release 5.0 in a CDB
- Reverting to Release 5.1 in a non-CDB or PDB with Local APEX
- Reverting to Release 5.1 in a CDB
- Reverting to Release 18.1 in a non-CDB or PDB with Local APEX



- Reverting to Release 18.1 in a CDB
- Reverting to Release 18.2 in a non-CDB or PDB with Local APEX
- Reverting to Release 18.2 in a CDB
- Reverting to Release 19.1 in a non-CDB or PDB with Local APEX
- Reverting to Release 19.1 in a CDB
- Reverting to Release 19.2 in a non-CDB or PDB with Local APEX
- Reverting to Release 19.2 in a CDB
- Reverting to Release 20.1 in a non-CDB or PDB with Local APEX
- Reverting to Release 20.1 in a CDB
- Reverting to Release 20.2 in a non-CDB or PDB with Local APEX
- Reverting to Release 20.2 in a CDB
- Reverting to Release 21.1 in a non-CDB or PDB with Local APEX
- Reverting to Release 21.1 in a CDB
- Reverting to Release 21.2 in a non-CDB or PDB with Local APEX
- Reverting to Release 21.2 in a CDB
- Reverting to Release 22.1 in a non-CDB or PDB with Local APEX
- Reverting to Release 22.1 in a CDB
- Reverting to Release 22.2 in a non-CDB or PDB with Local APEX
- Reverting to Release 22.2 in a CDB
- Reverting to Release 23.1 in a non-CDB or PDB with Local APEX
- Reverting to Release 23.1 in a CDB
- Reverting to Release 23.2 in a non-CDB or PDB with Local APEX
- Reverting to Release 23.2 in a CDB
- Reverting to Release 24.1 in a non-CDB or PDB with Local APEX
- Reverting to Release 24.1 in a CDB
- Re-enabling the REST Administration Interface After Downgrading

### C.3.1.3.1 Reverting to Release 1.5

To revert to Oracle APEX release 1.5:

- If you altered your images directory, revert it back to the release you want to revert to.
- 2. Start SQLcl and connect to the database where APEX is installed as SYS specifying the SYSDBA role:
  - On Windows:

SYSTEM\_DRIVE:\ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS\_password



```
$ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS_password
```

Execute the following:

```
ALTER SESSION SET CURRENT_SCHEMA = FLOWS_010500;
exec
flows_010500.wwv_flow_upgrade.switch_schemas('APEX_240200','FLOWS_010500');
```

4. Remove the APEX release schema. See Removing the APEX Release Schema.

(i) See Also

**Reverting the Images Directory** 

### C.3.1.3.2 Reverting to Release 1.6

To revert to Oracle APEX release 1.6:

- 1. If you altered your images directory, revert it back to the release you want to revert to.
- 2. Start SQLcl and connect to the database where APEX is installed as SYS specifying the SYSDBA role:
  - On Windows:

```
SYSTEM_DRIVE:\ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS_password
```

On UNIX and Linux:

```
$ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS_password
```

3. Execute the following:

```
ALTER SESSION SET CURRENT_SCHEMA = FLOWS_010600;
exec
flows_010600.wwv_flow_upgrade.switch_schemas('APEX_240200','FLOWS_010600');
```

- **4.** Depending upon the release you are reverting to, execute the appropriate command in SQLcl.
- **5.** Remove the APEX release schema. See <u>Removing the APEX Release Schema</u>.
  - (i) See Also

Reverting the Images Directory



### C.3.1.3.3 Reverting to Release 2.0

To revert to Oracle APEX release 2.0:

- 1. If you altered your images directory, revert it back to the release you want to revert to.
- 2. Start SQLcl and connect to the database where APEX is installed as SYS specifying the SYSDBA role:
  - On Windows:

```
SYSTEM_DRIVE:\ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS_password
```

On UNIX and Linux:

```
$ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS_password
```

Execute the following:

```
ALTER SESSION SET CURRENT_SCHEMA = FLOWS_020000;
exec
flows_020000.wwv_flow_upgrade.switch_schemas('APEX_240200','FLOWS_020000');
```

4. Remove the APEX release schema. See Removing the APEX Release Schema.

(i) See Also

**Reverting the Images Directory** 

### C.3.1.3.4 Reverting to Release 2.2

To revert to Oracle APEX release 2.2:

- 1. If you altered your images directory, revert it back to the release you want to revert to.
- 2. Start SQLcl and connect to the database where APEX is installed as SYS specifying the SYSDBA role:
  - On Windows:

```
SYSTEM_DRIVE:\ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS_password
```

On UNIX and Linux:

```
$ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS_password
```



3. Execute the following:

```
ALTER SESSION SET CURRENT_SCHEMA = FLOWS_020200;
exec
flows_020200.wwv_flow_upgrade.switch_schemas('APEX_240200','FLOWS_020200');
```

4. Remove the APEX release schema. See Removing the APEX Release Schema.

(i) See Also

Removing the APEX Release Schema

### C.3.1.3.5 Reverting to Release 3.0

To revert to Oracle APEX release 3.0:

- 1. If you altered your images directory, revert it back to the release you want to revert to.
- 2. Change your working directory to apex in the 3.0 source.
- Start SQLcl and connect to the database where APEX is installed as SYS specifying the SYSDBA role:
  - On Windows:

```
SYSTEM_DRIVE:\ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS_password
```

On UNIX and Linux:

```
$ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS password
```

4. Execute the following:

```
get define '^'
@apexvalidate x x FLOWS_030000
ALTER SESSION SET CURRENT_SCHEMA = FLOWS_030000;
exec
flows_030000.wwv_flow_upgrade.switch_schemas('APEX_240200','FLOWS_030000');
ALTER SESSION SET CURRENT_SCHEMA = SYS;
declare
    l_apex_version varchar2(30);
begin
    sys.dbms_registry.set_session_namespace (namespace => 'DBTOOLS');
    l_apex_version := flows_030000.wwv_flows_release;
    dbms_registry.downgrading('APEX','Oracle Application
Express','validate_apex','FLOWS_030000');
    dbms_registry.downgraded('APEX',l_apex_version);
    validate apex;
```



```
end;
```

5. Remove the APEX release schema. See Removing the APEX Release Schema.

(i) See Also

**Reverting the Images Directory** 

### C.3.1.3.6 Reverting to Release 3.1

To revert to Oracle APEX release 3.1:

- 1. If you altered your images directory, revert it back to the release you want to revert to.
- 2. Change your working directory to apex/core in the 3.1 source.
- 3. Start SQLcl and connect to the database where APEX is installed as SYS specifying the SYSDBA role:
  - On Windows:

```
SYSTEM_DRIVE:\ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS_password
```

On UNIX and Linux:

```
$ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS_password
```

4. Execute the following commands:

```
@wwv_flow_val.plb
@wwv_dbms_sql.sql
@wwv_dbms_sql.plb
```

- Change your working directory to apex in the 3.1 source.
- **6.** Start SQLcl and connect to the database where APEX is installed as SYS specifying the SYSDBA role:
  - On Windows:

```
SYSTEM_DRIVE:\ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS_password
```

On UNIX and Linux:

```
$ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS_password
```



7. Execute the following:

```
set define '^'
@apexvalidate x x FLOWS_030100
ALTER SESSION SET CURRENT_SCHEMA = FLOWS_030100;
exec
flows_030100.wwv_flow_upgrade.switch_schemas('APEX_240200','FLOWS_030100');
ALTER SESSION SET CURRENT_SCHEMA = SYS;
declare
    l apex version varchar2(30);
begin
    sys.dbms_registry.set_session_namespace (namespace => 'DBTOOLS');
    l_apex_version := flows_030100.wwv_flows_release;
    dbms_registry.downgrading('APEX','Oracle Application
Express','validate_apex','FLOWS_030100');
    dbms_registry.downgraded('APEX',l_apex_version);
    validate_apex;
end;
```

8. Remove the APEX release schema. See Removing the APEX Release Schema.

### (i) See Also

**Reverting the Images Directory** 

## C.3.1.3.7 Reverting to Release 3.2

To revert to Oracle APEX release 3.2:

- 1. If you altered your images directory, revert it back to the release you want to revert to.
- Change your working directory to apex/core in the 3.2 source.
- 3. Start SQLcl and connect to the database where APEX is installed as SYS specifying the SYSDBA role:
  - On Windows:

```
SYSTEM_DRIVE:\ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS_password
```

On UNIX and Linux:

```
$ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS_password
```



4. Execute the following commands:

```
@wwv_flow_val.plb
@wwv_dbms_sql.sql
@wwv_dbms_sql.plb
```

- Start SQLcI and connect to the database where APEX is installed as SYS specifying the SYSDBA role:
  - On Windows:

```
SYSTEM_DRIVE:\ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS_password
```

On UNIX and Linux:

```
$ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS password
```

Execute the following:

```
get define '^'
@apexvalidate x x APEX_030200
ALTER SESSION SET CURRENT_SCHEMA = APEX_030200;
exec
apex_030200.wwv_flow_upgrade.switch_schemas('APEX_240200','APEX_030200');
ALTER SESSION SET CURRENT_SCHEMA = SYS;
declare
    l_apex_version varchar2(30);
begin
    sys.dbms_registry.set_session_namespace (namespace => 'DBTOOLS');
    l_apex_version := apex_030200.wwv_flows_release;
    dbms_registry.downgrading('APEX','Oracle Application
Express','validate_apex','APEX_030200')
    dbms_registry.downgraded('APEX',l_apex_version);
    validate_apex;
end;
//
```

7. Remove the APEX release schema. See Removing the APEX Release Schema.

### (i) See Also

Reverting the Images Directory

### C.3.1.3.8 Reverting to Release 4.0

To revert to Oracle APEX release 4.0:

1. If you altered your images directory, revert it back to the release you want to revert to.



- Start SQLcl and connect to the database where APEX is installed as SYS specifying the SYSDBA role:
  - On Windows:

```
SYSTEM_DRIVE:\ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS_password
```

```
$ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS_password
```

3. Execute the following commands:

```
@wwv_flow_val.sql
@wwv_flow_val.plb
@wwv_dbms_sql.sql
@wwv_dbms_sql.plb
```

- 4. Change your working directory to apex in the 4.0 source.
- 5. Start SQLcl and connect to the database where APEX is installed as SYS specifying the SYSDBA role:
  - On Windows:

```
SYSTEM_DRIVE:\ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS_password
```

On UNIX and Linux:

```
$ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS_password
```

Execute the following:

```
get define '^'
@apexvalidate x x APEX_040000
ALTER SESSION SET CURRENT_SCHEMA = APEX_040000;
exec
apex_040000.wwv_flow_upgrade.switch_schemas('APEX_240200','APEX_040000');
ALTER SESSION SET CURRENT_SCHEMA = SYS;
declare
    l_apex_version varchar2(30);
begin
    sys.dbms_registry.set_session_namespace (namespace => 'DBTOOLS');
    l_apex_version := apex_040000.wwv_flows_release;
    dbms_registry.downgrading('APEX','Oracle Application
Express','validate_apex','APEX_040000');
    dbms_registry.downgraded('APEX',l_apex_version);
```



```
validate_apex;
end;
/
```

7. Remove the APEX release schema. See Removing the APEX Release Schema.

(i) See Also

**Reverting the Images Directory** 

## C.3.1.3.9 Reverting to Release 4.1

To revert to Oracle APEX release 4.1:

- 1. If you altered your images directory, revert it back to the release you want to revert to.
- 2. Change your working directory to apex/core in the 4.1 source.
- 3. Start SQLcl and connect to the database where APEX is installed as SYS specifying the SYSDBA role:
  - On Windows:

```
SYSTEM_DRIVE:\ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS_password
```

On UNIX and Linux:

```
$ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS_password
```

4. Execute the following commands:

```
@wwv_flow_val.sql
@wwv_flow_val.plb
@wwv_dbms_sql.sql
@wwv_dbms_sql.plb
```

- 5. Change your working directory to apex in the 4.1 source.
- 6. Start SQLcl and connect to the database where APEX is installed as SYS specifying the SYSDBA role:
  - On Windows:

```
SYSTEM_DRIVE:\ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS_password
```



```
$ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS_password
```

7. Execute the following:

```
get define '^'
@apexvalidate x x APEX_040100
ALTER SESSION SET CURRENT_SCHEMA = APEX_040100;
exec
apex_040100.wwv_flow_upgrade.switch_schemas('APEX_240200','APEX_040100');
ALTER SESSION SET CURRENT_SCHEMA = SYS;
declare
    l_apex_version varchar2(30);
begin
    sys.dbms_registry.set_session_namespace (namespace => 'DBTOOLS');
    l_apex_version := apex_040100.wwv_flows_release;
    dbms_registry.downgrading('APEX','Oracle Application
Express','validate_apex','APEX_040100');
    dbms_registry.downgraded('APEX',l_apex_version);
    validate_apex;
end;
//
```

8. Remove the APEX release schema. See Removing the APEX Release Schema.

### (i) See Also

**Reverting the Images Directory** 

### C.3.1.3.10 Reverting to Release 4.2 in a non-CDB or PDB with Local APEX

To revert to Oracle APEX release 4.2 in a non-CDB or PDB with a locally installed APEX:

- 1. If you altered your images directory, revert it back to the release you want to revert to.
- 2. Change your working directory to apex/core in the 4.2 source.
- 3. Start SQLcl and connect to the database where APEX is installed as SYS specifying the SYSDBA role:
  - On Windows:

```
SYSTEM_DRIVE:\ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS password
```



```
$ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS_password
```

4. Execute the following commands:

```
alter session set current_schema = SYS;
@core_sys_views.sql
grant select on sys.wwv_flow_gv$session to APEX_040200;
@wwv_flow_val.sql
@wwv_flow_val.plb
@wwv_dbms_sql.sql
grant execute on wwv_dbms_sql to APEX_040200;
@wwv_dbms_sql.plb
begin
   dbms_utility.compile_schema('APEX_040200');
end;
//
```

- 5. Change your working directory to apex in the 4.2 source.
- 6. Start SQLcl and connect to the database where APEX is installed as SYS specifying the SYSDBA role:
  - On Windows:

```
SYSTEM_DRIVE:\ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS_password
```

On UNIX and Linux:

```
$ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS_password
```

7. Execute the following:

```
set define '^'
@apexvalidate x x APEX_040200
ALTER SESSION SET CURRENT_SCHEMA = APEX_040200;
exec
apex_040200.wwv_flow_upgrade.switch_schemas('APEX_240200','APEX_040200');
ALTER SESSION SET CURRENT_SCHEMA = SYS;
declare
    l_apex_version varchar2(30);
begin
    sys.dbms_registry.set_session_namespace (namespace => 'DBTOOLS');
    l apex version := apex 040200.wwv flows release;
```



```
dbms_registry.downgrading('APEX','Oracle Application
Express','validate_apex','APEX_040200');
   dbms_registry.downgraded('APEX',l_apex_version);
   validate_apex;
end;
/
```

8. Remove the APEX release schema. See Removing the APEX Release Schema.

(i) See Also

**Reverting the Images Directory** 

### C.3.1.3.11 Reverting to Release 4.2 in a CDB

To revert to Oracle APEX release 4.2 in a CDB:

- If you altered your images directory, revert it back to the release you want to revert to.
- 2. Change your working directory to apex/core in the 4.2 source.
- 3. Create a new text file in that directory named apx42dgrd1.sql consisting of the following:

```
alter session set current_schema = SYS;
@core_sys_views.sql
grant select on sys.wwv_flow_gv$session to APEX_040200;
@wwv_flow_val.sql
@wwv_flow_val.plb
@wwv_dbms_sql.sql
grant execute on wwv_dbms_sql to APEX_040200;
@wwv_dbms_sql.plb
begin
   dbms_utility.compile_schema('APEX_040200');
end;
//
```

4. Create a second new text file in that directory named apx42dgrd.sql consisting of the following:

```
set define '^'
whenever sqlerror exit

column :xe_home new_value OH_HOME NOPRINT
variable xe_home varchar2(255)

set serverout on
begin
-- get oracle_home
    sys.dbms_system.get_env('ORACLE_HOME',:xe_home);
    if length(:xe_home) = 0 then
```



- 5. Start SQLcl and connect to CDB\$ROOT of the database where APEX is installed as SYS specifying the SYSDBA role:
  - On Windows:

```
SYSTEM_DRIVE:\ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS_password
```

```
$ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS_password
```

**6.** Execute the following commands:

```
@apx42dgrd.sql
```

- 7. Change your working directory to apex in the 4.2 source.
- 8. Create a new text file in that directory name apx42dqrd1.sql with the following contents:

```
set define '^'

ALTER SESSION SET CURRENT_SCHEMA = SYS;

@apexvalidate x x APEX_040200

ALTER SESSION SET CURRENT_SCHEMA = APEX_040200;
exec
apex_040200.wwv_flow_upgrade.switch_schemas('APEX_240200','APEX_040200');
ALTER SESSION SET CURRENT_SCHEMA = SYS;
declare
    l_apex_version varchar2(30);
begin
    sys.dbms_registry.set_session_namespace (namespace => 'DBTOOLS');
    l_apex_version := apex_040200.wwv_flows_release;
    dbms_registry.downgrading('APEX','Oracle Application
Express','validate_apex','APEX_040200');
```



```
dbms_registry.downgraded('APEX',l_apex_version);
   validate_apex;
end;
/
```

Create a second new text file in that directory named apx42dgrd.sql consisting of the following:

```
set define '^'
whenever sqlerror exit
column :xe_home new_value OH_HOME NOPRINT
variable xe_home varchar2(255)
set serverout on
begin
-- get oracle_home
    sys.dbms_system.get_env('ORACLE_HOME',:xe_home);
    if length(:xe_home) = 0 then
        sys.dbms_output.put_line(lpad('-',80,'-'));
        raise_application_error (
            -20001,
            'Oracle Home environment variable not set' );
    end if;
end;
whenever sqlerror continue
set termout off
select :xe_home from sys.dual;
set termout on
host ^OH_HOME/perl/bin/perl -I ^OH_HOME/rdbms/admin ^OH_HOME/rdbms/admin/
catcon.pl -b apx42dgrd apx42dgrd1.sql
```

- 10. Start SQLcl and connect to CDB\$ROOT of the database where APEX is installed as SYS specifying the SYSDBA role:
  - On Windows:

```
SYSTEM_DRIVE:\ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS_password
```

On UNIX and Linux:

```
$ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS_password
```

11. Execute the following:

```
@apx42dgrd.sql
```

12. Remove the APEX release schema. See Removing the APEX Release Schema.



### (i) See Also

Reverting the Images Directory

### C.3.1.3.12 Reverting to Release 5.0 in a non-CDB or PDB with Local APEX

To revert to Oracle APEX release 5.0 in a non-CDB or PDB with a locally installed APEX:

- 1. If you altered your images directory, revert it back to the release you want to revert to.
- 2. Change your working directory to apex/core in the 5.0 source.
- Start SQLcI and connect to the database where APEX is installed as SYS specifying the SYSDBA role:
  - On Windows:

```
SYSTEM_DRIVE:\ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS_password
```

On UNIX and Linux:

```
$ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS_password
```

4. Execute the following commands:

```
alter session set current schema = SYS;
@wwv flow val.sql
@wwv_flow_val.plb
begin
     dbms_utility.compile_schema('APEX_050000');
end;
set define '^'
@validate_apex x x APEX_050000
  for i in ( select owner, trigger_name
               from sys.dba_triggers
              where owner
                                =
                                      'APEX 050000'
                and trigger_name like 'WWV_FLOW_UPGRADE_%'
              order by 1 )
  loop
    sys.dbms_output.put_line('Dropping trigger '||i.owner||'.'||
i.trigger_name);
    execute immediate 'drop trigger '||i.owner||'.'||i.trigger_name;
  end loop;
end;
```



```
ALTER SESSION SET CURRENT SCHEMA = APEX 050000;
apex_050000.wwv_flow_upgrade.switch_schemas('APEX_240200','APEX_050000');
ALTER SESSION SET CURRENT SCHEMA = SYS;
drop context APEX$SESSION;
create context APEX$SESSION using APEX 050000.WWV FLOW SESSION CONTEXT;
declare
     l apex version varchar2(30);
     l_schemas sys.dbms_registry.schema_list_t;
begin
     sys.dbms registry.set session namespace (namespace => 'DBTOOLS');
     l apex version := apex 050000.wwv flows release;
     dbms_registry.downgrading('APEX','Oracle Application
Express','validate_apex','APEX_050000');
     dbms_registry.downgraded('APEX',l_apex_version);
     select username
       bulk collect into 1 schemas
       from all_users
      where username in
('FLOWS_FILES', 'APEX_PUBLIC_USER', 'APEX_LISTENER', 'APEX_REST_PUBLIC_USER', '
APEX INSTANCE ADMIN USER')
      order by 1;
     sys.dbms registry.update schema list('APEX', l schemas);
     validate apex;
end;
```

5. Remove the APEX release schema. See Removing the APEX Release Schema.

### (i) See Also

**Reverting the Images Directory** 

## C.3.1.3.13 Reverting to Release 5.0 in a CDB

To revert to Oracle APEX release 5.0 in a CDB:

- 1. If you altered your images directory, revert it back to the release you want to revert to.
- 2. Change your working directory to apex/core in the 5.0 source.
- Create a new text file in that directory named apx50dgrd1.sql consisting of the following:

```
alter session set current_schema = SYS;
@wwv_flow_val.sql
@wwv_flow_val.plb
begin
        dbms_utility.compile_schema('APEX_050000');
end;
/
```



```
@validate apex x x APEX 050000
begin
  for i in ( select owner, trigger_name
               from sys.dba_triggers
                                       'APEX 050000'
              where owner
                and trigger name like 'WWV FLOW UPGRADE %'
              order by 1 )
  loop
    sys.dbms_output.put_line('Dropping trigger '||i.owner||'.'||
i.trigger name);
    execute immediate 'drop trigger '||i.owner||'.'||i.trigger name;
  end loop;
end;
ALTER SESSION SET CURRENT SCHEMA = APEX 050000;
apex_050000.wwv_flow_upgrade.switch_schemas('APEX_240200','APEX_050000');
ALTER SESSION SET CURRENT SCHEMA = SYS;
drop context APEX$SESSION;
create context APEX$SESSION using APEX_050000.WWV_FLOW_SESSION_CONTEXT;
declare
     l apex version varchar2(30);
     l_schemas sys.dbms_registry.schema_list_t;
begin
     sys.dbms_registry.set_session_namespace (namespace => 'DBTOOLS');
     l apex version := apex 050000.wwv flows release;
     dbms registry.downgrading('APEX','Oracle Application
Express','validate_apex','APEX_050000');
     dbms registry.downgraded('APEX',l apex version);
     select username
       bulk collect into 1 schemas
       from all users
      where username in
('FLOWS_FILES','APEX_PUBLIC_USER','APEX_LISTENER','APEX_REST_PUBLIC_USER','
APEX_INSTANCE_ADMIN_USER')
      order by 1;
     sys.dbms registry.update schema list('APEX', l schemas);
     validate apex;
end;
```

4. Create a second new text file in that directory named apx50dgrd.sql consisting of the following:

```
set define '^'
whenever sqlerror exit
column :xe_home new_value OH_HOME NOPRINT
variable xe_home varchar2(255)
set serverout on
begin
-- get oracle_home
sys.dbms_system.get_env('ORACLE_HOME',:xe_home);
if length(:xe_home) = 0 then
    sys.dbms_output.put_line(lpad('-',80,'-'));
```



```
raise_application_error (-20001,'Oracle Home environment variable not
set' );
end if;
end;
/
whenever sqlerror continue
set termout off
select :xe_home from sys.dual;
set termout on
host ^OH_HOME/perl/bin/perl -I ^OH_HOME/rdbms/admin ^OH_HOME/rdbms/admin/
catcon.pl -b apx50dgrd apx50dgrd1.sql
```

- 5. Start SQLcl and connect to CDB\$ROOT of the database where APEX is installed as SYS specifying the SYSDBA role:
  - On Windows:

```
SYSTEM_DRIVE:\ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS password
```

```
$ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS_password
```

**6.** Execute the following commands:

```
@apx50dgrd.sql
```

7. Remove the APEX release schema. See Removing the APEX Release Schema.

```
See Also
```

**Reverting the Images Directory** 

### C.3.1.3.14 Reverting to Release 5.1 in a non-CDB or PDB with Local APEX

To revert to Oracle APEX release 5.1 in a non-CDB or PDB with a locally installed APEX:

- 1. If you altered your images directory, revert it back to the release you want to revert to.
- 2. Change your working directory to apex/core in the 5.1 source.
- 3. Start SQLcl and connect to the database where APEX is installed as SYS specifying the SYSDBA role:
  - On Windows:

```
SYSTEM_DRIVE:\ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS_password
```



```
$ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS_password
```

#### 4. Execute the following commands:

```
alter session set current_schema = SYS;
@wwv_flow_val.sql
@wwv_flow_val.plb
begin
     dbms_utility.compile_schema('APEX_050100');
end;
set define '^'
@validate_apex x x APEX_050100
begin
  for i in ( select owner, trigger_name
               from sys.dba_triggers
                                       'APEX_050100'
              where owner
                and trigger_name like 'WWV_FLOW_UPGRADE_%'
              order by 1 )
  loop
    sys.dbms_output.put_line('Dropping trigger '||i.owner||'.'||
i.trigger_name);
    execute immediate 'drop trigger '||i.owner||'.'||i.trigger_name;
  end loop;
end;
ALTER SESSION SET CURRENT_SCHEMA = APEX_050100;
apex_050100.wwv_flow_upgrade.switch_schemas('APEX_240200','APEX_050100');
ALTER SESSION SET CURRENT_SCHEMA = SYS;
drop context APEX$SESSION;
create context APEX$SESSION using APEX_050100.WWV_FLOW_SESSION_CONTEXT;
declare
     l_apex_version varchar2(30);
     l_schemas sys.dbms_registry.schema_list_t;
begin
     sys.dbms_registry.set_session_namespace (namespace => 'DBTOOLS');
     l_apex_version := apex_050100.wwv_flows_release;
     dbms_registry.downgrading('APEX','Oracle Application
Express','validate_apex','APEX_050100');
     dbms_registry.downgraded('APEX',l_apex_version);
     select username
       bulk collect into 1 schemas
       from all_users
      where username in
('FLOWS_FILES','APEX_PUBLIC_USER','APEX_LISTENER','APEX_REST_PUBLIC_USER','
APEX_INSTANCE_ADMIN_USER')
```



```
order by 1;
sys.dbms_registry.update_schema_list('APEX', l_schemas);
validate_apex;
end;
/
```

Remove the APEX release schema. See Removing the APEX Release Schema.

(i) See Also

**Reverting the Images Directory** 

### C.3.1.3.15 Reverting to Release 5.1 in a CDB

To revert to Oracle APEX release 5.1 in a CDB:

- If you altered your images directory, revert it back to the release you want to revert to.
- 2. Change your working directory to apex/core in the 5.1 source.
- 3. Create a new text file in that directory named apx51dgrd1.sql consisting of the following:

```
alter session set current_schema = SYS;
@wwv flow val.sql
@wwv flow val.plb
begin
     dbms_utility.compile_schema('APEX_050100');
end;
set define '^'
@validate_apex x x APEX_050100
begin
  for i in ( select owner, trigger name
               from sys.dba_triggers
              where owner
                                       'APEX 050100'
                and trigger_name like 'WWV_FLOW_UPGRADE_%'
              order by 1 )
  loop
    sys.dbms_output.put_line('Dropping trigger '||i.owner||'.'||
i.trigger_name);
    execute immediate 'drop trigger '||i.owner||'.'||i.trigger_name;
  end loop;
end;
ALTER SESSION SET CURRENT SCHEMA = APEX 050100;
apex 050100.wwv flow upgrade.switch schemas('APEX 240200', 'APEX 050100');
ALTER SESSION SET CURRENT SCHEMA = SYS;
drop context APEX$SESSION;
```



```
create context APEX$SESSION using APEX 050100.WWV FLOW SESSION CONTEXT;
declare
     l_apex_version varchar2(30);
     l_schemas sys.dbms_registry.schema_list_t;
begin
     sys.dbms_registry.set_session_namespace (namespace => 'DBTOOLS');
     l apex version := apex 050100.wwv flows release;
     dbms registry.downgrading('APEX','Oracle Application
Express','validate apex','APEX 050100');
     dbms_registry.downgraded('APEX',l_apex_version);
     select username
       bulk collect into 1 schemas
       from all users
      where username in
('FLOWS_FILES','APEX_PUBLIC_USER','APEX_LISTENER','APEX_REST_PUBLIC_USER','
APEX_INSTANCE_ADMIN_USER')
      order by 1;
     sys.dbms registry.update schema list('APEX', l schemas);
     validate apex;
end;
```

4. Create a second new text file in that directory named apx51dgrd.sql consisting of the following:

```
set define '^'
whenever sqlerror exit
column :xe_home new_value OH_HOME NOPRINT
variable xe_home varchar2(255)
set serverout on
begin
-- get oracle_home
sys.dbms_system.get_env('ORACLE_HOME',:xe_home);
if length(:xe_home) = 0 then
    sys.dbms_output.put_line(lpad('-',80,'-'));
    raise_application_error (-20001, 'Oracle Home environment variable not
set');
end if;
end;
whenever sqlerror continue
set termout off
select :xe_home from sys.dual;
set termout on
host ^OH_HOME/perl/bin/perl -I ^OH_HOME/rdbms/admin ^OH_HOME/rdbms/admin/
catcon.pl -b apx51dgrd apx51dgrd1.sql
```

- 5. Start SQLcl and connect to CDB\$ROOT of the database where APEX is installed as SYS specifying the SYSDBA role:
  - On Windows:

```
SYSTEM_DRIVE:\ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS_password
```



```
$ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS_password
```

**6.** Execute the following commands:

```
@apx51dgrd.sql
```

7. Remove the APEX release schema. See Removing the APEX Release Schema.

#### (i) See Also

**Reverting the Images Directory** 

#### C.3.1.3.16 Reverting to Release 18.1 in a non-CDB or PDB with Local APEX

To revert to Oracle APEX release 18.1 in a non-CDB or PDB with a locally installed APEX:

- 1. If you altered your images directory, revert it back to the release you want to revert to.
- 2. Change your working directory to apex in the 18.1 source.
- 3. Create a new text file in that directory named apxdwngrd.sql consisting of the following:

```
set define '^'
set concat on
set concat .
set verify off
set termout off
column foo new_val LOG
select 'apxdwngrd_' ||to_char(sysdate, 'YYYY-MM-DD_HH24-MI-SS') || '.log'
as foo
  from sys.dual;
set termout on
spool ^LOG
@@core/scripts/set_appun.sql
whenever sqlerror exit
set serveroutput on size unlimited
declare
    l_cnt
          number := 0;
begin
    select count(*) into l_cnt from sys.dba_users where username =
'^APPUN';
    if l cnt = 0 then
        dbms_output.put_line('^APPUN not found in this database.');
        raise program_error;
    end if;
end;
```



whenever sqlerror continue prompt ... Create validate procedure in SYS schema and start registration @@core/validate\_apex.sql x x ^APPUN grant inherit any privileges to ^APPUN; prompt Installing SYS views @@core/sys\_core\_views.sql @@core/wwv\_flow\_val.sql grant execute on sys.wwv\_flow\_val to ^APPUN.; @@core/wwv\_flow\_val.plb ALTER SESSION SET CURRENT SCHEMA = ^APPUN; exec sys.dbms\_session.modify\_package\_state(sys.dbms\_session.reinitialize); begin ^APPUN..wwv\_flow\_upgrade.remove\_jobs(); ^APPUN..wwv flow upgrade.create jobs('^APPUN'); ^APPUN..wwv\_flow\_upgrade.create\_public\_synonyms('^APPUN'); ^APPUN..wwv\_flow\_upgrade.grant\_public\_synonyms('^APPUN'); ^APPUN..wwv\_flow\_upgrade.flows\_files\_objects\_remove('^APPUN'); ^APPUN..wwv flow upgrade.flows files objects create('^APPUN'); end; ALTER SESSION SET CURRENT\_SCHEMA = SYS; drop context APEX\$SESSION; create context APEX\$SESSION using ^APPUN..WWV FLOW SESSION CONTEXT; alter package sys.wwv\_dbms\_sql\_^APPUN. compile; alter package sys.wwv\_dbms\_sql\_^APPUN. compile body; exec sys.dbms session.modify package state(sys.dbms session.reinitialize); set serveroutput on size unlimited declare l apex version varchar2(30); l\_schemas sys.dbms\_registry.schema\_list\_t; begin sys.dbms\_registry.set\_session\_namespace (namespace => 'DBTOOLS'); execute immediate 'drop package ^APPUN..WWV\_FLOW\_DB\_VERSION'; l apex version := ^APPUN..wwv flows release; sys.dbms registry.loading('APEX','Oracle Application Express','validate\_apex', '^APPUN'); select username bulk collect into l\_schemas from sys.all users where username in



```
('FLOWS_FILES','APEX_PUBLIC_USER','APEX_LISTENER','APEX_REST_PUBLIC_USER','
APEX_INSTANCE_ADMIN_USER')
    order by 1;
    sys.dbms_registry.update_schema_list('APEX', l_schemas);
    sys.dbms_registry.loaded('APEX',l_apex_version);
    commit;
    sys.validate_apex;
end;
/
```

- 4. Start SQLcl and connect to the database where APEX is installed as SYS specifying the SYSDBA role:
  - On Windows:

```
SYSTEM_DRIVE:\ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS_password
```

```
$ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS_password
```

5. Run the apxdwngrd.sql script:

```
SQL> @apxdwngrd.sql
```

6. Remove the APEX release schema. See Removing the APEX Release Schema.

#### (i) See Also

**Reverting the Images Directory** 

## C.3.1.3.17 Reverting to Release 18.1 in a CDB

To revert to Oracle APEX release 18.1 in a CDB:

- 1. If you altered your images directory, revert it back to the release you want to revert to.
- 2. Change your working directory to apex in the 18.1 source.
- Create a new text file in that directory named apxdwngrd.sql consisting of the following:

```
set define '^'
set concat on
set concat .
set verify off

set termout off
column foo new_val LOG
select 'apxdwngrd_' ||to_char(sysdate, 'YYYY-MM-DD_HH24-MI-SS') || '.log'
as foo
    from sys.dual;
```



```
set termout on
spool ^LOG
@@core/scripts/set_appun.sql
whenever sqlerror exit
set serveroutput on size unlimited
declare
            number := 0;
    l_cnt
begin
    select count(*) into 1 cnt from sys.dba users where username =
'^APPUN';
    if l_cnt = 0 then
        dbms_output.put_line('^APPUN not found in this database.');
        raise program_error;
    end if;
end;
whenever sqlerror continue
prompt ... Create validate procedure in SYS schema and start registration
@@core/validate apex.sql x x ^APPUN
grant inherit any privileges to ^APPUN;
prompt Installing SYS views
@@core/sys_core_views.sql
@@core/wwv_flow_val.sql
grant execute on sys.wwv_flow_val to ^APPUN.;
@@core/wwv_flow_val.plb
ALTER SESSION SET CURRENT_SCHEMA = ^APPUN;
exec sys.dbms_session.modify_package_state(sys.dbms_session.reinitialize);
begin
    ^APPUN..wwv flow upgrade.remove jobs();
    ^APPUN..wwv_flow_upgrade.create_jobs('^APPUN');
    ^APPUN..wwv_flow_upgrade.create_public_synonyms('^APPUN');
    ^APPUN..wwv_flow_upgrade.grant_public_synonyms('^APPUN');
    ^APPUN..wwv_flow_upgrade.flows_files_objects_remove('^APPUN');
    ^APPUN..wwv_flow_upgrade.flows_files_objects_create('^APPUN');
end;
ALTER SESSION SET CURRENT SCHEMA = SYS;
drop context APEX$SESSION;
create context APEX$SESSION using ^APPUN..WWV_FLOW_SESSION_CONTEXT;
alter package sys.wwv_dbms_sql_^APPUN. compile;
```



```
alter package sys.wwv dbms sql ^APPUN. compile body;
exec sys.dbms_session.modify_package_state(sys.dbms_session.reinitialize);
set serveroutput on size unlimited
declare
     l apex version varchar2(30);
     l schemas sys.dbms registry.schema list t;
begin
    sys.dbms_registry.set_session_namespace (namespace => 'DBTOOLS');
    execute immediate 'drop package ^APPUN..WWV FLOW DB VERSION';
    l_apex_version := ^APPUN..wwv_flows_release;
    sys.dbms_registry.loading('APEX','Oracle Application
Express','validate_apex', '^APPUN');
    select username
     bulk collect into 1 schemas
     from sys.all users
     where username in
('FLOWS_FILES','APEX_PUBLIC_USER','APEX_LISTENER','APEX_REST_PUBLIC_USER','
APEX_INSTANCE_ADMIN_USER')
     order by 1;
     sys.dbms registry.update schema list('APEX', l schemas);
     sys.dbms registry.loaded('APEX',l apex version);
     commit;
    sys.validate_apex;
end;
/
```

4. Create a second new text file in that directory named apxdwngrd\_cdb.sql consisting of the following:

```
set define '^'
whenever sqlerror exit
column :xe_home new_value OH_HOME NOPRINT
variable xe_home varchar2(255)
set serverout on
begin
-- get oracle_home
sys.dbms_system.get_env('ORACLE_HOME',:xe_home);
if length(:xe_home) = 0 then
    sys.dbms_output.put_line(lpad('-',80,'-'));
    raise_application_error (-20001,'Oracle Home environment variable not
set');
end if;
end;
whenever sqlerror continue
set termout off
select :xe_home from sys.dual;
set termout on
host ^OH_HOME/perl/bin/perl -I ^OH_HOME/rdbms/admin ^OH_HOME/rdbms/admin/
catcon.pl -b apx181dgrd apxdwngrd.sql
```

5. Start SQLcl and connect to CDB\$ROOT of the database where APEX is installed as SYS specifying the SYSDBA role:



```
SYSTEM_DRIVE:\ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS_password
```

On UNIX and Linux:

```
$ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS_password
```

**6.** Run the apxdwngrd\_cdb.sql script:

```
SQL> @apxdwngrd_cdb.sql
```

7. Remove the APEX release schema. See Removing the APEX Release Schema.

#### (i) See Also

**Reverting the Images Directory** 

#### C.3.1.3.18 Reverting to Release 18.2 in a non-CDB or PDB with Local APEX

To revert to Oracle APEX release 18.2 in a non-CDB or PDB with a locally installed APEX:

- If you altered your images directory, revert it back to the release you want to revert to.
- 2. Change your working directory to apex in the 18.2 source.
- Create a new text file in that directory named apxdwngrd.sql consisting of the following:

```
set define '^'
set concat on
set concat .
set verify off
set termout off
column foo new_val LOG
select 'apxdwngrd_' ||to_char(sysdate, 'YYYY-MM-DD_HH24-MI-SS') || '.log'
  from sys.dual;
set termout on
spool ^LOG
@@core/scripts/set_appun.sql
whenever sqlerror exit
set serveroutput on size unlimited
declare
    l_cnt
             number := 0;
begin
    select count(*) into l_cnt from sys.dba_users where username =
```



```
'^APPUN';
    if l cnt = 0 then
        dbms output.put line('^APPUN not found in this database.');
        raise program_error;
    end if;
end;
whenever sqlerror continue
prompt ... Create validate procedure in SYS schema and start registration
@@core/validate apex.sql x x ^APPUN
grant inherit any privileges to ^APPUN;
prompt Installing SYS views
@@core/sys core views.sql
@@core/wwv flow val.sql
grant execute on sys.wwv_flow_val to ^APPUN.;
@@core/wwv_flow_val.plb
ALTER SESSION SET CURRENT_SCHEMA = ^APPUN;
exec sys.dbms_session.modify_package_state(sys.dbms_session.reinitialize);
begin
    ^APPUN..wwv_flow_upgrade.remove_jobs();
    ^APPUN..wwv_flow_upgrade.create_jobs('^APPUN');
    ^APPUN..wwv_flow_upgrade.create_public_synonyms('^APPUN');
    ^APPUN..wwv_flow_upgrade.grant_public_synonyms('^APPUN');
    ^APPUN..wwv flow upgrade.flows files objects remove('^APPUN');
    ^APPUN..wwv flow upgrade.flows files objects create('^APPUN');
end;
ALTER SESSION SET CURRENT SCHEMA = SYS;
drop context APEX$SESSION;
create context APEX$SESSION using ^APPUN..WWV FLOW SESSION CONTEXT;
alter package sys.wwv_dbms_sql_^APPUN. compile;
alter package sys.wwv_dbms_sql_^APPUN. compile body;
exec sys.dbms_session.modify_package_state(sys.dbms_session.reinitialize);
set serveroutput on size unlimited
declare
     l_apex_version varchar2(30);
     l_schemas sys.dbms_registry.schema_list_t;
begin
    sys.dbms_registry.set_session_namespace (namespace => 'DBTOOLS');
    execute immediate 'drop package ^APPUN..WWV_FLOW_DB_VERSION';
```



```
l_apex_version := ^APPUN..wwv_flows_release;
sys.dbms_registry.loading('APEX','Oracle Application

Express','validate_apex', '^APPUN');
select username
   bulk collect into l_schemas
   from sys.all_users
   where username in
('FLOWS_FILES','APEX_PUBLIC_USER','APEX_LISTENER','APEX_REST_PUBLIC_USER','
APEX_INSTANCE_ADMIN_USER')
   order by 1;
   sys.dbms_registry.update_schema_list('APEX', l_schemas);
   sys.dbms_registry.loaded('APEX', l_apex_version);
   commit;
   sys.validate_apex;
end;
//
```

- 4. Start SQLcl and connect to the database where APEX is installed as SYS specifying the SYSDBA role:
  - On Windows:

```
SYSTEM_DRIVE:\ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS_password
```

```
$ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS_password
```

5. Run the apxdwngrd.sql script:

```
SQL> @apxdwngrd.sql
```

6. Remove the APEX release schema. See Removing the APEX Release Schema.

(i) See Also

Reverting the Images Directory

## C.3.1.3.19 Reverting to Release 18.2 in a CDB

To revert to Oracle APEX release 18.2 in a CDB:

- If you altered your images directory, revert it back to the release you want to revert to.
- 2. Change your working directory to apex in the 18.2 source.
- Create a new text file in that directory named apxdwngrd.sql consisting of the following:

```
set define '^'
set concat on
set concat .
```



```
set verify off
set termout off
column foo new val LOG
select 'apxdwngrd_' ||to_char(sysdate, 'YYYY-MM-DD_HH24-MI-SS') || '.log'
as foo
  from sys.dual;
set termout on
spool ^LOG
@@core/scripts/set_appun.sql
whenever sqlerror exit
set serveroutput on size unlimited
declare
    1 cnt
            number := 0;
begin
    select count(*) into l_cnt from sys.dba_users where username =
'^APPUN';
    if l_cnt = 0 then
        dbms_output.put_line('^APPUN not found in this database.');
        raise program error;
    end if;
end;
whenever sqlerror continue
prompt ... Create validate procedure in SYS schema and start registration
@@core/validate apex.sql x x ^APPUN
grant inherit any privileges to ^APPUN;
prompt Installing SYS views
@@core/sys_core_views.sql
@@core/wwv_flow_val.sql
grant execute on sys.wwv flow val to ^APPUN.;
@@core/wwv_flow_val.plb
ALTER SESSION SET CURRENT SCHEMA = ^APPUN;
exec sys.dbms_session.modify_package_state(sys.dbms_session.reinitialize);
begin
    ^APPUN..wwv_flow_upgrade.remove_jobs();
    ^APPUN..wwv_flow_upgrade.create_jobs('^APPUN');
    ^APPUN..wwv flow upgrade.create public synonyms('^APPUN');
    ^APPUN..wwv_flow_upgrade.grant_public_synonyms('^APPUN');
    ^APPUN..wwv_flow_upgrade.flows_files_objects_remove('^APPUN');
    ^APPUN..wwv_flow_upgrade.flows_files_objects_create('^APPUN');
end;
```



```
ALTER SESSION SET CURRENT SCHEMA = SYS;
drop context APEX$SESSION;
create context APEX$SESSION using ^APPUN..WWV_FLOW_SESSION_CONTEXT;
alter package sys.wwv dbms sql ^APPUN. compile;
alter package sys.wwv_dbms_sql_^APPUN. compile body;
exec sys.dbms_session.modify_package_state(sys.dbms_session.reinitialize);
set serveroutput on size unlimited
declare
     l_apex_version varchar2(30);
     l_schemas sys.dbms_registry.schema_list_t;
begin
    sys.dbms registry.set session namespace (namespace => 'DBTOOLS');
    execute immediate 'drop package ^APPUN..WWV_FLOW_DB_VERSION';
    l apex version := ^APPUN..wwv flows release;
    sys.dbms_registry.loading('APEX','Oracle Application
    select username
      bulk collect into 1 schemas
      from sys.all users
     where username in
('FLOWS_FILES','APEX_PUBLIC_USER','APEX_LISTENER','APEX_REST_PUBLIC_USER','
APEX_INSTANCE_ADMIN_USER')
     order by 1;
     sys.dbms registry.update schema list('APEX', l schemas);
     sys.dbms_registry.loaded('APEX',l_apex_version);
     commit;
     sys.validate_apex;
end;
```

4. Create a second new text file in that directory named apxdwngrd\_cdb.sql consisting of the following:

```
set define '^'
whenever sqlerror exit
column :xe_home new_value OH_HOME NOPRINT
variable xe_home varchar2(255)
set serverout on
begin
-- get oracle_home
sys.dbms_system.get_env('ORACLE_HOME',:xe_home);
if length(:xe_home) = 0 then
    sys.dbms_output.put_line(lpad('-',80,'-'));
    raise_application_error (-20001,'Oracle Home environment variable not
set');
end if;
end;
whenever sqlerror continue
set termout off
select :xe_home from sys.dual;
```



set termout on
host ^OH\_HOME/perl/bin/perl -I ^OH\_HOME/rdbms/admin ^OH\_HOME/rdbms/admin/
catcon.pl -b apx182dgrd apxdwngrd.sql

- 5. Start SQLcl and connect to CDB\$ROOT of the database where APEX is installed as SYS specifying the SYSDBA role:
  - On Windows:

SYSTEM\_DRIVE:\ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS\_password

On UNIX and Linux:

\$ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS\_password

**6.** Run the apxdwngrd\_cdb.sql script:

SQL> @apxdwngrd\_cdb.sql

7. Remove the APEX release schema. See Removing the APEX Release Schema.

(i) See Also

**Reverting the Images Directory** 

## C.3.1.3.20 Reverting to Release 19.1 in a non-CDB or PDB with Local APEX

To revert to Oracle APEX release 19.1 in a non-CDB or PDB with a locally installed APEX:

- 1. If you altered your images directory, revert it back to the release you want to revert to.
- 2. Change your working directory to apex in the 19.1 source.
- 3. Start SQLcl and connect to the database where APEX is installed as SYS specifying the SYSDBA role:
  - On Windows:

SYSTEM\_DRIVE:\ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS password

On UNIX and Linux:

\$ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS password



4. Run the apxdwngrd.sql script:

```
SQL> @apxdwngrd.sql
```

Remove the APEX release schema. See <u>Removing the APEX Release Schema</u>.

#### C.3.1.3.21 Reverting to Release 19.1 in a CDB

To revert to Oracle APEX release 19.1 in a CDB:

- 1. If you altered your images directory, revert it back to the release you want to revert to.
- 2. Change your working directory to apex in the 19.1 source.
- 3. Create a script in the apex directory called apxdwngrd\_cdb.sql with the following contents:

```
set define '^'
whenever sqlerror exit
column :xe_home new_value OH_HOME NOPRINT
variable xe_home varchar2(255)
set serverout on
begin
-- get oracle_home
sys.dbms_system.get_env('ORACLE_HOME',:xe_home);
if length(:xe_home) = 0 then
    sys.dbms_output.put_line(lpad('-',80,'-'));
    raise_application_error (-20001, 'Oracle Home environment variable not
set');
end if;
end;
whenever sqlerror continue
set termout off
select :xe_home from sys.dual;
set termout on
host ^OH_HOME/perl/bin/perl -I ^OH_HOME/rdbms/admin ^OH_HOME/rdbms/admin/
catcon.pl -b apx191dgrd apxdwngrd.sql
```

- **4.** Start SQLcl and connect to the database where APEX is installed as SYS specifying the SYSDBA role:
  - On Windows:

```
SYSTEM_DRIVE:\ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS_password
```

On UNIX and Linux:

```
$ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS_password
```

5. Run the apxdwngrd\_cdb.sql script:

```
SQL> @apxdwngrd_cdb.sql
```



6. Remove the APEX release schema. See Removing the APEX Release Schema.

#### C.3.1.3.22 Reverting to Release 19.2 in a non-CDB or PDB with Local APEX

To revert to Oracle APEX release 19.2 in a non-CDB or PDB with a locally installed APEX:

- 1. If you altered your images directory, revert it back to the release you want to revert to.
- 2. Change your working directory to apex in the 19.2 source.
- Start SQLcl and connect to the database where APEX is installed as SYS specifying the SYSDBA role:
  - On Windows:

```
SYSTEM_DRIVE:\ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS_password
```

On UNIX and Linux:

```
$ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS_password
```

4. Run the apxdwngrd.sql script:

```
SQL> @apxdwngrd.sql
```

5. Remove the APEX release schema. See Removing the APEX Release Schema.

### C.3.1.3.23 Reverting to Release 19.2 in a CDB

To revert to Oracle APEX release 19.2 in a CDB:

- 1. If you altered your images directory, revert it back to the release you want to revert to.
- 2. Change your working directory to apex in the 19.2 source.
- Create a script in the apex directory called apxdwngrd\_cdb.sql with the following contents:

```
set define '^'
whenever sqlerror exit
column :xe home new value OH HOME NOPRINT
variable xe_home varchar2(255)
set serverout on
begin
-- get oracle_home
sys.dbms_system.get_env('ORACLE_HOME',:xe_home);
if length(:xe_home) = 0 then
    sys.dbms_output.put_line(lpad('-',80,'-'));
    raise_application_error (-20001,'Oracle Home environment variable not
set');
end if;
end;
whenever sqlerror continue
set termout off
```



```
select :xe_home from sys.dual;
set termout on
host ^OH_HOME/perl/bin/perl -I ^OH_HOME/rdbms/admin ^OH_HOME/rdbms/admin/
catcon.pl -b apx192dgrd apxdwngrd.sql
```

- **4.** Start SQLcl and connect to the database where APEX is installed as SYS specifying the SYSDBA role:
  - On Windows:

```
SYSTEM_DRIVE:\ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS password
```

```
$ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS_password
```

5. Run the apxdwngrd\_cdb.sql script:

```
SQL> @apxdwngrd_cdb.sql
```

6. Remove the APEX release schema. See Removing the APEX Release Schema.

#### C.3.1.3.24 Reverting to Release 20.1 in a non-CDB or PDB with Local APEX

To revert to Oracle APEX release 20.1 in a non-CDB or PDB with a locally installed APEX:

- 1. If you altered your images directory, revert it back to the release you want to revert to.
- 2. Change your working directory to apex in the 20.1 source.
- 3. Start SQLcl and connect to the database where APEX is installed as SYS specifying the SYSDBA role:
  - On Windows:

```
SYSTEM_DRIVE:\ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS_password
```

On UNIX and Linux:

```
$ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS_password
```

4. Run the apxdwngrd.sql script:

```
SQL> @apxdwngrd.sql
```

5. Remove the APEX release schema. See Removing the APEX Release Schema.



### C.3.1.3.25 Reverting to Release 20.1 in a CDB

To revert to Oracle APEX release 20.1 in a CDB:

- 1. If you altered your images directory, revert it back to the release you want to revert to.
- 2. Change your working directory to apex in the 20.1 source.
- 3. Create a script in the apex directory called apxdwngrd\_cdb.sql with the following contents:

```
set define '^'
whenever sqlerror exit
column :xe home new value OH HOME NOPRINT
variable xe home varchar2(255)
set serverout on
begin
-- get oracle_home
sys.dbms_system.get_env('ORACLE_HOME',:xe_home);
if length(:xe home) = 0 then
    sys.dbms_output.put_line(lpad('-',80,'-'));
    raise_application_error (-20001,'Oracle Home environment variable not
set');
end if;
end;
whenever sqlerror continue
set termout off
select :xe home from sys.dual;
set termout on
host ^OH HOME/perl/bin/perl -I ^OH HOME/rdbms/admin ^OH HOME/rdbms/admin/
catcon.pl -b apx201dgrd apxdwngrd.sql
```

- **4.** Start SQLcl and connect to the database where APEX is installed as SYS specifying the SYSDBA role:
  - On Windows:

```
SYSTEM_DRIVE:\ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS_password
```

On UNIX and Linux:

```
$ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS_password
```

5. Run the apxdwngrd\_cdb.sql script:

```
SQL> @apxdwngrd_cdb.sql
```

Remove the APEX release schema. See <u>Removing the APEX Release Schema</u>.

#### C.3.1.3.26 Reverting to Release 20.2 in a non-CDB or PDB with Local APEX

To revert to Oracle APEX release 20.2 in a non-CDB or PDB with a locally installed APEX:



- 1. If you altered your images directory, revert it back to the release you want to revert to.
- 2. Change your working directory to apex in the 20.2 source.
- 3. Start SQLcl and connect to the database where APEX is installed as SYS specifying the SYSDBA role:
  - On Windows:

```
SYSTEM_DRIVE:\ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS_password
```

```
$ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS_password
```

**4.** Run the apxdwngrd.sql script:

```
SQL> @apxdwngrd.sql
```

5. Remove the APEX release schema. See Removing the APEX Release Schema.

#### C.3.1.3.27 Reverting to Release 20.2 in a CDB

To revert to Oracle APEX release 20.2 in a CDB:

- 1. If you altered your images directory, revert it back to the release you want to revert to.
- Change your working directory to apex in the 20.2 source.
- 3. Create a script in the apex directory called apxdwngrd\_cdb.sql with the following contents:

```
set define '^'
whenever sqlerror exit
column :xe home new value OH HOME NOPRINT
variable xe_home varchar2(255)
set serverout on
begin
-- get oracle home
sys.dbms_system.get_env('ORACLE_HOME',:xe_home);
if length(:xe_home) = 0 then
    sys.dbms_output.put_line(lpad('-',80,'-'));
    raise application error (-20001, 'Oracle Home environment variable not
set');
end if;
end;
whenever sqlerror continue
set termout off
select :xe home from sys.dual;
set termout on
host ^OH_HOME/perl/bin/perl -I ^OH_HOME/rdbms/admin ^OH_HOME/rdbms/admin/
catcon.pl -b apx202dgrd apxdwngrd.sql
```



- 4. Start SQLcl and connect to the database where APEX is installed as SYS specifying the SYSDBA role:
  - On Windows:

```
SYSTEM_DRIVE:\ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS_password
```

```
$ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS_password
```

5. Run the apxdwngrd\_cdb.sql script:

```
SQL> @apxdwngrd_cdb.sql
```

6. Remove the APEX release schema. See Removing the APEX Release Schema.

#### C.3.1.3.28 Reverting to Release 21.1 in a non-CDB or PDB with Local APEX

To revert to Oracle APEX 21.1 in a non-CDB or PDB with a locally installed APEX:

- 1. If you altered your images directory, revert it back to the release you want to revert to.
- 2. Change your working directory to apex in the 21.1 source.
- 3. Start SQLcl and connect to the database where Oracle APEX is installed as SYS specifying the SYSDBA role:
  - On Windows:

```
SYSTEM_DRIVE:\ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS_password
```

On UNIX and Linux:

```
$ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS password
```

4. Run the apxdwngrd.sql script:

```
SQL> @apxdwngrd.sql
```

5. Remove the APEX release schema. See Removing the APEX Release Schema.

## C.3.1.3.29 Reverting to Release 21.1 in a CDB

To revert to Oracle APEX release 21.1 in a CDB:

- 1. If you altered your images directory, revert it back to the release you want to revert to.
- 2. Change your working directory to apex in the 21.1 source.



Create a script in the apex directory called apxdwngrd\_cdb.sql with the following contents:

```
set define '^'
whenever sqlerror exit
column :xe_home new_value OH_HOME NOPRINT
variable xe_home varchar2(255)
set serverout on
begin
-- get oracle_home
sys.dbms_system.get_env('ORACLE_HOME',:xe_home);
if length(:xe_home) = 0 then
    sys.dbms_output.put_line(lpad('-',80,'-'));
    raise_application_error (-20001,'Oracle Home environment variable not
set');
end if;
end;
whenever sqlerror continue
set termout off
select :xe_home from sys.dual;
set termout on
host ^OH_HOME/perl/bin/perl -I ^OH_HOME/rdbms/admin ^OH_HOME/rdbms/admin/
catcon.pl -b apx211dgrd apxdwngrd.sql
```

- **4.** Start SQLcl and connect to the database where APEX is installed as SYS specifying the SYSDBA role:
  - On Windows:

```
SYSTEM_DRIVE:\ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS_password
```

On UNIX and Linux:

```
$ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS_password
```

5. Run the apxdwngrd\_cdb.sql script:

```
SQL> @apxdwngrd_cdb.sql
```

6. Remove the APEX release schema. See Removing the APEX Release Schema.

#### C.3.1.3.30 Reverting to Release 21.2 in a non-CDB or PDB with Local APEX

To revert to Oracle APEX 21.2 in a non-CDB or PDB with a locally installed APEX:

- 1. If you altered your images directory, revert it back to the release you want to revert to.
- 2. Change your working directory to apex in the 21.2 source.
- 3. Start SQLcl and connect to the database where APEX is installed as SYS specifying the SYSDBA role:



```
SYSTEM_DRIVE:\ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS_password
```

On UNIX and Linux:

```
$ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS_password
```

**4.** Run the apxdwngrd.sql script:

```
SQL> @apxdwngrd.sql
```

5. Remove the APEX release schema. See Removing the APEX Release Schema.

#### C.3.1.3.31 Reverting to Release 21.2 in a CDB

To revert to Oracle APEX release 21.2 in a CDB:

- 1. If you altered your images directory, revert it back to the release you want to revert to.
- 2. Change your working directory to apex in the 21.2 source.
- 3. Create a script in the apex directory called apxdwngrd\_cdb.sql with the following contents:

```
set define '^'
whenever sqlerror exit
column :xe_home new_value OH_HOME NOPRINT
variable xe_home varchar2(255)
set serverout on
begin
-- get oracle_home
sys.dbms_system.get_env('ORACLE_HOME',:xe_home);
if length(:xe_home) = 0 then
    sys.dbms_output.put_line(lpad('-',80,'-'));
    raise_application_error (-20001,'Oracle Home environment variable not
set');
end if;
end;
whenever sqlerror continue
set termout off
select :xe_home from sys.dual;
set termout on
host ^OH_HOME/perl/bin/perl -I ^OH_HOME/rdbms/admin ^OH_HOME/rdbms/admin/
catcon.pl -b apx212dgrd apxdwngrd.sql
```

4. Start SQLcl and connect to the database where APEX is installed as SYS specifying the SYSDBA role:



SYSTEM\_DRIVE:\ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS\_password

On UNIX and Linux:

```
$ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS_password
```

**5.** Run the apxdwngrd\_cdb.sql script:

```
SQL> @apxdwngrd_cdb.sql
```

6. Remove the APEX release schema. See Removing the APEX Release Schema.

#### C.3.1.3.32 Reverting to Release 22.1 in a non-CDB or PDB with Local APEX

To revert to Oracle APEX 22.1 in a non-CDB or PDB with a locally installed APEX:

- 1. If you altered your images directory, revert it back to the release you want to revert to.
- 2. Change your working directory to apex in the 22.1 source.
- 3. Start SQLcl and connect to the database where APEX is installed as SYS specifying the SYSDBA role:
  - On Windows:

```
SYSTEM_DRIVE:\ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS_password
```

On UNIX and Linux:

```
$ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS password
```

4. Run the apxdwngrd.sql script:

```
SQL> @apxdwnqrd.sql
```

5. Remove the APEX release schema. See Removing the APEX Release Schema.

#### C.3.1.3.33 Reverting to Release 22.1 in a CDB

To revert to Oracle APEX release 22.1 in a CDB:

- 1. If you altered your images directory, revert it back to the release you want to revert to.
- 2. Change your working directory to apex in the 22.1 source.



Create a script in the apex directory called apxdwngrd\_cdb.sql with the following contents:

```
set define '^'
whenever sqlerror exit
column :xe_home new_value OH_HOME NOPRINT
variable xe_home varchar2(255)
set serverout on
begin
-- get oracle_home
sys.dbms_system.get_env('ORACLE_HOME',:xe_home);
if length(:xe_home) = 0 then
    sys.dbms_output.put_line(lpad('-',80,'-'));
    raise_application_error (-20001,'Oracle Home environment variable not
set');
end if;
end;
whenever sqlerror continue
set termout off
select :xe_home from sys.dual;
set termout on
host ^OH_HOME/perl/bin/perl -I ^OH_HOME/rdbms/admin ^OH_HOME/rdbms/admin/
catcon.pl -b apx212dgrd apxdwngrd.sql
```

- **4.** Start SQLcl and connect to the database where APEX is installed as SYS specifying the SYSDBA role:
  - On Windows:

```
SYSTEM_DRIVE:\ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS_password
```

On UNIX and Linux:

```
$ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS_password
```

5. Run the apxdwngrd\_cdb.sql script:

```
SQL> @apxdwngrd_cdb.sql
```

6. Remove the APEX release schema. See Removing the APEX Release Schema.

#### C.3.1.3.34 Reverting to Release 22.2 in a non-CDB or PDB with Local APEX

To revert to Oracle APEX 22.2 in a non-CDB or PDB with a locally installed APEX:

- 1. If you altered your images directory, revert it back to the release you want to revert to.
- 2. Change your working directory to apex in the 22.2 source.
- 3. Start SQLcl and connect to the database where APEX is installed as SYS specifying the SYSDBA role:



```
SYSTEM_DRIVE:\ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS_password
```

On UNIX and Linux:

```
$ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS_password
```

**4.** Run the apxdwngrd.sql script:

```
SQL> @apxdwngrd.sql
```

5. Remove the APEX release schema. See Removing the APEX Release Schema.

#### C.3.1.3.35 Reverting to Release 22.2 in a CDB

To revert to Oracle APEX release 22.2 in a CDB:

- 1. If you altered your images directory, revert it back to the release you want to revert to.
- 2. Change your working directory to apex in the 22.2 source.
- 3. Create a script in the apex directory called apxdwngrd\_cdb.sql with the following contents:

```
set define '^'
whenever sqlerror exit
column :xe_home new_value OH_HOME NOPRINT
variable xe_home varchar2(255)
set serverout on
begin
-- get oracle_home
sys.dbms_system.get_env('ORACLE_HOME',:xe_home);
if length(:xe_home) = 0 then
    sys.dbms_output.put_line(lpad('-',80,'-'));
    raise_application_error (-20001,'Oracle Home environment variable not
set');
end if;
end;
whenever sqlerror continue
set termout off
select :xe_home from sys.dual;
set termout on
host ^OH_HOME/perl/bin/perl -I ^OH_HOME/rdbms/admin ^OH_HOME/rdbms/admin/
catcon.pl -b apx222dgrd apxdwngrd.sql
```

4. Start SQLcl and connect to the database where APEX is installed as SYS specifying the SYSDBA role:



SYSTEM\_DRIVE:\ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS\_password

On UNIX and Linux:

\$ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS\_password

**5.** Run the apxdwngrd\_cdb.sql script:

```
SQL> @apxdwngrd_cdb.sql
```

6. Remove the APEX release schema. See Removing the APEX Release Schema.

#### C.3.1.3.36 Reverting to Release 23.1 in a non-CDB or PDB with Local APEX

To revert to Oracle APEX 23.1 in a non-CDB or PDB with a locally installed APEX:

- 1. If you altered your images directory, revert it back to the release you want to revert to.
- Change your working directory to apex in the 23.1 source.
- 3. Start SQLcl and connect to the database where APEX is installed as SYS specifying the SYSDBA role:
  - On Windows:

```
SYSTEM_DRIVE:\ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS_password
```

On UNIX and Linux:

```
$ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS password
```

4. Run the apxdwngrd.sql script:

```
SQL> @apxdwnqrd.sql
```

5. Remove the APEX release schema. See Removing the APEX Release Schema.

#### C.3.1.3.37 Reverting to Release 23.1 in a CDB

To revert to Oracle APEX release 23.1 in a CDB:

- 1. If you altered your images directory, revert it back to the release you want to revert to.
- 2. Change your working directory to apex in the 23.1 source.



3. Create a script in the apex directory called apxdwngrd\_cdb.sql with the following contents:

```
set define '^'
whenever sqlerror exit
column :xe_home new_value OH_HOME NOPRINT
variable xe_home varchar2(255)
set serverout on
begin
-- get oracle_home
sys.dbms_system.get_env('ORACLE_HOME',:xe_home);
if length(:xe_home) = 0 then
    sys.dbms_output.put_line(lpad('-',80,'-'));
    raise_application_error (-20001,'Oracle Home environment variable not
set');
end if;
end;
whenever sqlerror continue
set termout off
select :xe_home from sys.dual;
set termout on
host ^OH_HOME/perl/bin/perl -I ^OH_HOME/rdbms/admin ^OH_HOME/rdbms/admin/
catcon.pl -b apx231dgrd apxdwngrd.sql
```

- **4.** Start SQLcl and connect to the database where APEX is installed as SYS specifying the SYSDBA role:
  - On Windows:

```
SYSTEM_DRIVE:\ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS_password
```

On UNIX and Linux:

```
$ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS_password
```

5. Run the apxdwngrd\_cdb.sql script:

```
SQL> @apxdwngrd_cdb.sql
```

6. Remove the APEX release schema. See Removing the APEX Release Schema.

#### C.3.1.3.38 Reverting to Release 23.2 in a non-CDB or PDB with Local APEX

To revert to Oracle APEX 23.2 in a non-CDB or PDB with a locally installed APEX:

- 1. If you altered your images directory, revert it back to the release you want to revert to.
- 2. Change your working directory to apex in the 23.2 source.
- 3. Start SQLcl and connect to the database where APEX is installed as SYS specifying the SYSDBA role:



```
SYSTEM_DRIVE:\ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS_password
```

On UNIX and Linux:

```
$ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS_password
```

**4.** Run the apxdwngrd.sql script:

```
SQL> @apxdwngrd.sql
```

5. Remove the APEX release schema. See Removing the APEX Release Schema.

#### C.3.1.3.39 Reverting to Release 23.2 in a CDB

To revert to Oracle APEX release 23.2 in a CDB:

- 1. If you altered your images directory, revert it back to the release you want to revert to.
- 2. Change your working directory to apex in the 23.2 source.
- 3. Create a script in the apex directory called apxdwngrd\_cdb.sql with the following contents:

```
set define '^'
whenever sqlerror exit
column :xe_home new_value OH_HOME NOPRINT
variable xe_home varchar2(255)
set serverout on
begin
-- get oracle_home
sys.dbms_system.get_env('ORACLE_HOME',:xe_home);
if length(:xe_home) = 0 then
    sys.dbms_output.put_line(lpad('-',80,'-'));
    raise_application_error (-20001,'Oracle Home environment variable not
set');
end if;
end;
whenever sqlerror continue
set termout off
select :xe_home from sys.dual;
set termout on
host ^OH_HOME/perl/bin/perl -I ^OH_HOME/rdbms/admin ^OH_HOME/rdbms/admin/
catcon.pl -b apx232dgrd apxdwngrd.sql
```

4. Start SQLcl and connect to the database where APEX is installed as SYS specifying the SYSDBA role:



SYSTEM\_DRIVE:\ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS\_password

On UNIX and Linux:

```
$ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS_password
```

**5.** Run the apxdwngrd\_cdb.sql script:

```
SQL> @apxdwngrd_cdb.sql
```

6. Remove the APEX release schema. See Removing the APEX Release Schema.

#### C.3.1.3.40 Reverting to Release 24.1 in a non-CDB or PDB with Local APEX

To revert to Oracle APEX 24.1 in a non-CDB or PDB with a locally installed APEX:

- 1. If you altered your images directory, revert it back to the release you want to revert to.
- 2. Change your working directory to apex in the 24.1 source.
- 3. Start SQLcl and connect to the database where APEX is installed as SYS specifying the SYSDBA role:
  - On Windows:

```
SYSTEM_DRIVE:\ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS_password
```

On UNIX and Linux:

```
$ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS password
```

4. Run the apxdwngrd.sql script:

```
SQL> @apxdwngrd.sql
```

5. Remove the APEX release schema. See Removing the APEX Release Schema.

### C.3.1.3.41 Reverting to Release 24.1 in a CDB

To revert to Oracle APEX release 24.1 in a CDB:

- 1. If you altered your images directory, revert it back to the release you want to revert to.
- 2. Change your working directory to apex in the 24.1 source.



3. Create a script in the apex directory called apxdwngrd\_cdb.sql with the following contents:

```
set define '^'
whenever sqlerror exit
column :xe_home new_value OH_HOME NOPRINT
variable xe_home varchar2(255)
set serverout on
begin
-- get oracle_home
sys.dbms_system.get_env('ORACLE_HOME',:xe_home);
if length(:xe_home) = 0 then
    sys.dbms_output.put_line(lpad('-',80,'-'));
    raise_application_error (-20001,'Oracle Home environment variable not
set');
end if;
end;
whenever sqlerror continue
set termout off
select :xe_home from sys.dual;
set termout on
host ^OH_HOME/perl/bin/perl -I ^OH_HOME/rdbms/admin ^OH_HOME/rdbms/admin/
catcon.pl -b apx241dgrd apxdwngrd.sql
```

- **4.** Start SQLcl and connect to the database where APEX is installed as SYS specifying the SYSDBA role:
  - On Windows:

```
SYSTEM_DRIVE:\ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS_password
```

On UNIX and Linux:

```
$ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS_password
```

5. Run the apxdwngrd\_cdb.sql script:

```
SQL> @apxdwngrd_cdb.sql
```

6. Remove the APEX release schema. See Removing the APEX Release Schema.

### C.3.1.3.42 Re-enabling the REST Administration Interface After Downgrading

If the REST Administration Interface was used before the upgrade attempt, you must re-create the APEX\_INSTANCE\_ADMIN\_USER. If the REST Administration Interface was not used, skip this step.

To re-create the APEX\_INSTANCE\_ADMIN\_USER:

 Change your working directory to apex in the, XX.X release source (where XX.X is the release number you reverted to).



- Start SQLcl and connect to the database where Oracle APEX is installed as SYS specifying the SYSDBA role:
  - On Windows:

```
SYSTEM_DRIVE:\ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS_password
```

```
$ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS_password
```

3. If the no authentication was used, run the following:

```
create user apex_instance_admin_user no authentication
```

4. If the authentication was used, run the following:

```
create user apex_instance_admin_user identified by <random-password>
password expire
```

## C.3.1.4 Removing the APEX Release Schema

After you revert to the prior release, remove the Oracle APEX schema.

- Removing the APEX Release 24.2 Schema from a Non-CDB
   Start SQLcl and connect to the database and execute DROP USER APEX\_240200 CASCADE; command.
- Removing the APEX Release 24.2 Schema from a CDB
   Create text files, start SQLcl and connect to the database execute
   @remove\_apx242\_usr.sql.

## C.3.1.4.1 Removing the APEX Release 24.2 Schema from a Non-CDB

Start SQLcl and connect to the database and execute DROP USER APEX\_240200 CASCADE; command.

To remove the release 24.2 schema from a non-CDB:

- 1. Start SQLcl and connect to the database where APEX is installed as SYS specifying the SYSDBA role:
  - On Windows:

SYSTEM\_DRIVE:\ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS\_password



```
$ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS_password
```

2. Execute the following command:

```
DROP USER APEX_240200 CASCADE;
```

Once you have removed the APEX 24.2 schema, you can now attempt the upgrade again.

#### C.3.1.4.2 Removing the APEX Release 24.2 Schema from a CDB

Create text files, start SQLcI and connect to the database execute @remove\_apx242\_usr.sql.

To remove the release 24.2 schema from a CDB:

1. Create a new text file named remove\_apx242\_usr1.sql with the following contents:

```
alter session set current_schema = SYS;
drop user APEX_240200 cascade;
```

2. Create a second new text file named remove\_apx242\_usr.sql with the following contents:

```
set define '^'
whenever sqlerror exit
column :xe_home new_value OH_HOME NOPRINT
variable xe_home varchar2(255)
set serverout on
begin
-- get oracle_home
    sys.dbms_system.get_env('ORACLE_HOME',:xe_home);
    if length(:xe_home) = 0 then
        sys.dbms_output.put_line(lpad('-',80,'-'));
        raise_application_error (
            -20001,
            'Oracle Home environment variable not set' );
    end if;
end;
whenever sqlerror continue
set termout off
select :xe_home from sys.dual;
set termout on
host ^OH_HOME/perl/bin/perl -I ^OH_HOME/rdbms/admin ^OH_HOME/rdbms/admin/
      remove_apx242_usr remove_apx242_usr.sql
```

3. Start SQLcl and connect to the database where APEX is installed as SYS specifying the SYSDBA role:



SYSTEM\_DRIVE:\ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS password

On UNIX and Linux:

\$ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS\_password

**4.** Execute the following command:

```
@remove_apx242_usr.sql
```

Once you have removed the APEX 24.2 schema, you can now attempt the upgrade again.

## C.3.2 Removing APEX from the Database

Start SQLcl and connect to the database where Oracle APEX is installed as SYS specifying the SYSDBA role and execute the SQL> @apxremov.sql command.

This section describes how to remove the APEX schema, synonyms, and users from the database without deleting the database.

#### (i) Note

Do NOT follow these steps if you have upgraded your database from a prior release, and still want to use the prior release of APEX. For information about reverting to a prior release, see <u>Reverting to a Previous Release</u>. If you are not sure whether you have completed a new installation or an upgrade installation, review <u>Cleaning Up After a Failed Installation</u> to verify if a previous release of APEX exists in the database.

To remove APEX from the database:

- Change your working directory to the apex directory where you unzipped the APEX software.
- 2. Start SQLcl and connect to the database where APEX is installed as SYS specifying the SYSDBA role:
  - On Windows:

SYSTEM\_DRIVE:\ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS\_password

On UNIX and Linux:

\$ sql /nolog
SQL> CONNECT SYS as SYSDBA
Enter password: SYS\_password



3. Execute the following command:

SQL> @apxremov.sql

**4.** After successfully removing APEX using apxremov.sql, you must exit your current SQLcl session and reconnect before attempting another install using apexins.sql.

## C.4 About Images Displaying Incorrectly in APEX

Learn about troubleshooting if images in Oracle APEX do not display correctly.

If images in APEX do not display correctly, you may have more than one definition of the /i/ alias. To address this issue:

- If possible, rename the first instance of /i/ to a different alias name.
- Alternatively, copy the images from the directory where APEX was downloaded or the images copied for Oracle REST Data Services (ORDS) to the directory defined by the first /i/ alias.

## C.5 About Page Protection Violation

A page protection violation may be caused by manual alteration of protected page items.

If this error occurs after installation when trying to log into Oracle APEX, then stop and start Oracle REST Data Services. If you are unsure of what caused this error, contact the application administrator for assistance.

# Index

A	С
accounts, 9	CDB
ACL	application container, 2
fixing invalid, 31	CDBs
Administration Services	patching Oracle APEX, 13
signing in, 25	uninstalling, 6
APEX	CDBs reinstalling Oracle APEX, 9
accessing in Oracle Cloud, 2	CDN
architecture, 1	referencing images, 14
getting started, 24	referencing static resources, 14
XML DB requirement, 5	common APEX from another CDB, 16
APEX_PUBLIC_ROUTER, 10	configure
SESSIONS_PER_USER, 10	HTTP access, 6
APEX_PUBLIC_USER account	creating
about, 8	application PDB, application root seed, 5
changing password, 9	application seed, 4
configuring, 8	•
expiration in Oracle Database, 10	D
unlocking, 9	D
apexins.sql	database accounts, 9
running, 4	database requirement
application container	Oracle APEX, 1
about, 2	Database Vault, 4
applications	development environment
upgrading, 4	changing to runtime, 34
apxchpwd.sql, 8	disk space
changing Instance Administrator account	requirements, 5
password, 7	requirements, o
creating Instance Administrator account, 7	_
running, 7	E
unlockin Instance Administrator account, 7	anvironment configuring 5
updating Instance Administrator account, 7	environment, configuring, 5
apxdevrm.sql, 34	
apxdvins.sql, 33	F
apxrtins.sql	<del> </del>
running, 4	friendly URL, 10
- 31	full development environment
D	about, 33
В	converting to runtime, 34
browser	installing in, 4
requirement, 4	
requirement, -	G
	getting started
	APEX, 24

I	login credentials
images	recovering workspace name, 8
copying, 14	N.4
hosting on local file system, 14	M
referencing CDN, 14	MEMORY_TARGET
installation	checking, 2
downloading Oracle REST Data Services, 12	Multitenant Architecture, 1
enabling network services, 15	Walatorial Controllary 1
installing in other languages, 21	N I
managing JOB_QUEUE_PROCESSES, 19	N
Oracle APEX, 3	network services
Oracle REST Data Services, 11	enabling, 15
overview, 5	granting connect privileges, Oracle Database
patch sets, 4	12c, 17
performing security tasks, 19	invalid ACL error, 18
planning, 3	non-CDB
point releases, 4	installing in, 4
process, 5	scag,
requirements, 1, 3	0
restart processes, 8	0
signing in, 24	Oracle APEX
understanding, 3	about users, 25
verifying validity, <i>C-1</i>	about workspaces, 25
installation option	Administration Services, 25
full development environment, 5	browser requirement, 4
runtime environment, 5	configuring, 1
installing	configuring your environment, 5
failures, C-2	creating users, 27
in application container, 3	creating workspace manually, 26
Oracle APEX, 3	database requirement, 1
Oracle REST Data Services, 11, 12 other languages, 21	disk space requirements, 5
Instance administrator account	download and install in non-CDB, 4
about, 6	download and install locally, 4
creating, 6	downloading, 3
running apxchpwd.sql, 7	incompatible versions, 13
updating, 6	installing, 1, 3
Instance Administrator account	installing translated versions, 22
changing password, 7	patching in CDBs, 13
creating, 7	patching in PDBs, 14, 15
creating password, 7	pre-installation tasks, 2
unlocking, 7	reinstalling in CDBs, 9
•	release number, 3
J	releases included with Oracle Database, 3
	signing in to workspace, 29
JOB_QUEUE_PROCESSES, 19	uninstalling in CDBs, 6
changing number of, 21	Oracle APEX Application Services, 26
viewing from SQLcl, 20	Oracle APEX Application Development accessing APEX, 2
viewing in installation log, 20	Oracle APEX Clusters (Oracle RAC)
viewing number of, 19	shutting down instances, 2
viewing on About page, 20	Oracle Autonomous Database
	accessing Oracle APEX, 2
L	Oracle Cloud
	accessing APEX, 2
log file, C-1	

Oracle Database Oracle APEX included, 3 Oracle Database Vault, 4 Oracle REST Data Services configuring, 1, 13 configuring behind load balancer, 12 configuring behind reverse proxy, 12 copying the Images Directory, 14 Copying the Images Directory, 13 downloading, 11, 12 installing, 1, 11, 12 release number, 3 using static resources CDN, 14 Validating the Oracle REST Data Services Installation, 15 Web Server HTTP POST Request Limits, 13 Oracle SQL Developer Command Line support, 3 ORDS APEX_PUBLIC_ROUTER, 10 friendly URL, 10 ords.version.number.zip, 12	post-installation tasks installing other languages, 21 pre-installation tasks, 2 prior installations removing when upgrading, 30
	release number Oracle REST Data Services, 3 viewing, 3 release numbering convention, 2 removing schemas from prior installation, 31 requirements, 1 browser, 4 database, 1 disk space, 5 MEMORY_TARGET, 2 Oracle XML DB, 5 WORKAREA_SIZE_POLICY, 3 reverting to previous release, 5
overview, 5  P password	running apexins.sql, 4 apxchpwd.sql, 8 apxdevrm.sql, 34 apxdvins.sql, 33
resetting from Sign In page, 7 patch sets, 4 PDB application container, 2	runtime environment about, 8, 33 converting to development environment, 33 installing in, 4
PDBs patching APEX, 14 patching Oracle APEX, 14, 15	S
performance optimizing, 32 performance optimization about, 32 expired header attribute, 32 gzip compression, 32 Plug-in non-CDB, 12 Plug-in PDB, 12 plugging in non-CDB or PDB with locally installed APEX, 11, 16 plugging in PDBs APEX from another CDB, 11 APEX in root, 10 APEX not contained root, 16 APEX not in the root of CDB, 15 APEX root another CDB, 12 not in the root container of the target CDB non-CDB or PDB with no APEX, 17 when not contained in the root container local APEX from another CDB, 17	Secure Sockets Layer (SSL), 19 sessions per user, 10 SESSIONS_PER_USER, 10 Sign In dialog requesting a workspace, 6 SQLcl support, 3 SSL, 19 static resources copying, 14 hosting on local file system, 14 referencing CDN, 14  T  translated version installing, 21 translated versions about installing, 22 troubleshooting, C-1
point releases, 4	cleaning up after failed installation, <i>C-2</i> images, <i>C-55</i>

```
troubleshooting (continued)
    reviewing log file, C-1
U
upgrade post installation tasks, 29
    fixing invalid ACL, 31
    removing prior installation, 30
    removing schemas from prior installation, 31
    verifying prior installation, 30
upgrading
    about, 1
    environment clean-up, 4
    existing applications, 4
    in application container, 3
    reverting, 5
    sample scenarios, 2
    testing, 4
user accounts
    creating, 27
V
verifying
    application container installation, 3
```

#### W

```
Web browser
   requirements, 4
web server
   Oracle REST Data Services, 4, 1
   requirements, 4
WORKAREA_SIZE_POLICY
   checking, 3
workspace
   creating, 26
   recovering workspace name, 8
   requesting from Sign In dialog, 6
   signing in, 29
workspace name
   recovering, 8
X
XML DB
   requirement, 5
```