

Oracle® Communications Billing and Revenue Management

Cloud Native Performance Test Summary



Release 15.0
G30726-02
May 2025

ORACLE®

Copyright © 2025, Oracle and/or its affiliates.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this is software, software documentation, data (as defined in the Federal Acquisition Regulation), or related documentation that is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, then the following notice is applicable:

U.S. GOVERNMENT END USERS: Oracle programs (including any operating system, integrated software, any programs embedded, installed, or activated on delivered hardware, and modifications of such programs) and Oracle computer documentation or other Oracle data delivered to or accessed by U.S. Government end users are "commercial computer software," "commercial computer software documentation," or "limited rights data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, reproduction, duplication, release, display, disclosure, modification, preparation of derivative works, and/or adaptation of i) Oracle programs (including any operating system, integrated software, any programs embedded, installed, or activated on delivered hardware, and modifications of such programs), ii) Oracle computer documentation and/or iii) other Oracle data, is subject to the rights and limitations specified in the license contained in the applicable contract. The terms governing the U.S. Government's use of Oracle cloud services are defined by the applicable contract for such services. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

Oracle®, Java, MySQL, and NetSuite are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Inside are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. AMD, Epyc, and the AMD logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark of The Open Group.

This software or hardware and documentation may provide access to or information about content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services unless otherwise set forth in an applicable agreement between you and Oracle. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services, except as set forth in an applicable agreement between you and Oracle.

Contents

1	Introduction	
	About BRM and ECE	1-1
	Purpose and Scope	1-1
	References	1-2
2	Database and Hardware Configuration	
	About the Database and Hardware Configuration	2-1
3	System Performance Benchmarking Metrics	
	CPU Usage	3-1
	Throughput per Schema	3-1
	Throughput Efficiency Indexes	3-2
	IOPS Efficiency	3-2
	Latency 95th Percentile	3-2
	Memory Usage	3-2
	Billing Care REST API Performance Metrics	3-3
4	Billing and Invoicing Performance	
	Scenario 1: 14 Million Prepaid Accounts in 2 Schemas with Taxation Disabled	4-1
	Scenario 2: 5 Million Wholesale Accounts in 1 Schema with Taxation Disabled	4-1
	Scenario 3: 6 Million Postpaid Accounts in 2 Schemas with Taxation Enabled	4-2
	Performance Results	4-2
5	Charging Efficiency	
	Scenario: Voice/Data/SMS Charging Efficiency (19,700 Transactions)	5-1
	Charging Efficiency Results	5-1
6	Billing Care REST API Performance	
	Scenario 1: Create 100,000 Accounts Using 50 Threads in 2 Schemas	6-1

Scenario 2: Get 100,000 Accounts Using 50 Threads in 2 Schemas	6-2
Performance Results	6-2

7 Offline Mediation Controller Performance

Scenario: Collect, Enhance, and Distribute Node Chain Performance with 5 Million CDRs	7-1
Performance Results	7-1

Disclaimer

The following is intended to outline Oracle's general product direction. It is intended for information purposes only, and may not be incorporated into any contract. It is not a commitment to deliver any material, code, or functionality, and should not be relied upon in making purchasing decisions. The development, release, timing, and pricing of any features or functionality described for Oracle's products may change and remains at the sole discretion of Oracle Corporation.

This document is provided for information purposes and should not be relied upon in making a purchasing decision. The contents hereof are subject to change without notice. This document is not warranted to be errorfree, nor subject to any other warranties or conditions, whether expressed orally or implied in law, including implied warranties and conditions of merchantability or fitness for a particular purpose.

This document is not part of a license agreement nor can it be incorporated into any contractual agreement with Oracle Corporation or its subsidiaries or affiliates.

Failure to adhere to these benchmarks does not constitute a breach of Oracle's obligations. Oracle specifically disclaims any liability with respect to this document and no contractual obligations are formed either directly or indirectly by this document.

Preface

This guide provides guidelines for benchmarking your Oracle Communications Billing and Revenue Management (BRM) cloud native system. It serves as an initial reference to the benchmarking of a BRM cloud native system. The actual performance of the system can vary significantly based on the capacity and performance in the target infrastructure.

Audience

This guide is intended for operations personnel and system administrators.

Documentation Accessibility

For information about Oracle's commitment to accessibility, visit the Oracle Accessibility Program website at <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=docacc>.

Access to Oracle Support

Oracle customer access to and use of Oracle support services will be pursuant to the terms and conditions specified in their Oracle order for the applicable services.

Diversity and Inclusion

Oracle is fully committed to diversity and inclusion. Oracle respects and values having a diverse workforce that increases thought leadership and innovation. As part of our initiative to build a more inclusive culture that positively impacts our employees, customers, and partners, we are working to remove insensitive terms from our products and documentation. We are also mindful of the necessity to maintain compatibility with our customers' existing technologies and the need to ensure continuity of service as Oracle's offerings and industry standards evolve. Because of these technical constraints, our effort to remove insensitive terms is ongoing and will take time and external cooperation.

1

Introduction

Oracle Communications Billing and Revenue Management (BRM) and Elastic Charging Engine (ECE) are a proven, pre-integrated solution spanning mediation, 2G to 5G converged charging, billing, and end-to-end revenue management. The solution enables techco CSPs to monetize any network, service, experience, or business model, at any scale, using cloud infrastructure.

Topics in this document:

- [About BRM and ECE](#)
- [Purpose and Scope](#)
- [References](#)

About BRM and ECE

BRM provides industry proven, modern billing and revenue management for communications and digital businesses, offering:

- Flexible service, and industry business model support.
- Faster innovation: rapid launch of digital offers with design-time flexibility.
- IT agility: modern cloud native deployment model with low total cost of ownership, designed to be deployed in public and private cloud infrastructure.

Oracle's BRM has been designed to support the efficient scheduling and running of high performance billing and invoicing tasks, running on cloud native infrastructure. Billing and invoicing are multithreaded applications designed to optimally utilize the available compute resources to ensure large scale jobs are completed in the minimum time.

ECE, powered by industry leading in-memory grid technology, has been designed from the outset to support the technical and business monetization demands for hyperscale digital communications providers. It is a digital experience engine for the 5G era, providing 3GPP aligned real-time converged data and communications session charging and balance management, with native integration into Oracle's full suite of billing and revenue management capabilities designed in accordance with TM Forum principles.

ECE uses mesh-based in-memory technology to provide high performance, resilient and linearly scalable charging, with pre-integrations available to advanced revenue management capabilities. Built around network and IT industry standards, ECE uses an innovative high performance and coherent data management architecture to support near-linear scalability, low latency, and highly available geographically redundant deployments with transactional consistency.

Purpose and Scope

This document is designed to provide an insight to the measured performance and capacity of BRM, ECE, and Offline Mediation Controller deployed in a Cloud Native lab Environment (CNE) setup.

These are just references, since the actual performance of the system can vary significantly based on the details of the infrastructure. It is recommended that BRM, ECE, and Offline

Mediation Controller are run through a benchmark on the target cloud native infrastructure to determine the capacity and performance in the target infrastructure.

References

For more information, refer to the following books:

Oracle Communications Billing and Revenue Management Cloud Native Deployment Guide

Oracle Communications Billing and Revenue Management System Administrator's Guide

Oracle Communications Offline Mediation Controller Cloud Native Installation and Administration Guide

Oracle Communications Offline Mediation Controller System Administrator's Guide

2

Database and Hardware Configuration

This chapter provides details about the specific system configuration used as well as the various deployment components used for the benchmarking process for BRM and its components in this guide.

This information serves as a reference point for interpreting the results and understanding how your own configuration might influence the performance of your BRM and its components.

Topics in this document:

- [About the Database and Hardware Configuration](#)

About the Database and Hardware Configuration

[Table 2-1](#) contains details of the specific configuration of the Oracle Database platform supporting the BRM system.

Table 2-1 Oracle Database Configuration

Component	Details
Database	2-Node RAC
Oracle Database version	19.21
Shape	VM.Standard.E4.Flex
Cores per VM	24 cores
Memory per VM	384 GB
Database Storage	32 TB



Note:

The following hardware configuration applies only to BRM and ECE components. For Offline Mediation Controller cloud native hardware configuration, see [Table 7-1](#).

[Table 2-2](#) contains details of the key hardware components used for Invoicing and REST API Performance Testing.

Table 2-2 Hardware Configuration for E4-based OKE Nodes (BRM and ECE)

Component	Details
Shape	VM.Standard.E4.Flex
CPU	AMD EPYC 7J13 processor
Clock Speed	2.55 GHz
Memory per Node	256 GB
oCPU Per Node	10

Table 2-2 (Cont.) Hardware Configuration for E4-based OKE Nodes (BRM and ECE)

Component	Details
Number of Worker Nodes	12
Boot Volume Size	300 GB

[Table 2-3](#) contains details of the key hardware components used for Billing and Charging Performance Testing.

Table 2-3 Hardware Configuration for E5-based OKE Nodes (BRM and ECE)

Component	Details
Shape	VM.Standard.E5.Flex
CPU	AMD EPYC 9J14 processor
Clock Speed	2.60 GHz
Memory per Node	256 GB
oCPU Per Node	10
Number of Worker Nodes	12
Boot Volume Size	200 GB

3

System Performance Benchmarking Metrics

This chapter details the key metrics employed during the benchmarking process for Oracle Communications Billing and Revenue Management (BRM) Cloud Native Deployment.

Topics in this document:

- [CPU Usage](#)
- [Throughput per Schema](#)
- [Throughput Efficiency Indexes](#)
- [IOPS Efficiency](#)
- [Latency 95th Percentile](#)
- [Memory Usage](#)
- [Billing Care REST API Performance Metrics](#)

CPU Usage

The benchmarking process monitors two key CPU usage metrics: App CPU Usage and Database CPU Usage. These metrics represent the average percentage of CPU resources utilized by the application (App CPU Usage) and database server (Database CPU Usage) during peak hours.

They are calculated as follows:

- **App CPU Usage Percentage:** (Average number of used OCPUs across all OKE nodes during peak hours) / (Total number of OCPUs per node) x 100%
- **App CPU Usage (Cores Consumed):** (Application CPU Usage percentage) x (Total Number of Worker Nodes) x (Number of Cores)
- **Database CPU Usage Percentage:** (Average number of used CPU cores across both database nodes during peak hours) / (Total number of CPU cores per database instance) x 100%
- **Database CPU Usage (Cores Consumed):** (Database CPU Usage percentage) x (Total Number of RAC Nodes) x (Number of Cores per Node)

Throughput per Schema

Throughput (ops/sec) per Schema is a metric that reflects the transaction processing speed for each individual schema within the system. It essentially measures the number of transactions processed per second for a specific schema. It is calculated as follows:

Throughput (ops/sec) per Schema = (# of Accounts in a Schema) / (Processing Time per Account for that Schema)

Throughput Efficiency Indexes

The benchmarking process utilizes three Throughput Efficiency Indexes:

- Overall Throughput Efficiency Index
- Application Throughput Efficiency Index
- Database Throughput Efficiency Index

They are calculated as follows:

- **Overall Throughput Efficient Index:** This is calculated by dividing the Total Throughput (op/sec) by the sum of App oCPU consumed and DB oCPU consumed. This index provides an overall system efficiency rating, encompassing both application and database resource utilization.
- **App Throughput Efficient Index:** This metric focuses specifically on application efficiency. It's calculated by dividing the Total Throughput (ops/sec) by the App oCPU consumed alone. Analyzing this index helps identify how efficiently the application utilizes CPU resources for processing transactions.
- **Database Throughput Efficient Index:** Similar to the App Throughput Efficient Index, this metric focuses on database efficiency. It's calculated by dividing the Total Throughput (ops/sec) by the DB oCPU consumed to assess how effectively the database server utilizes its CPU resources for processing transactions.

IOPS Efficiency

The benchmarking process also evaluates input/output operations per second (IOPS) efficiency through three metrics: IOPS Overall Efficiency, IOPS Read Efficiency, and IOPS Write Efficiency.

They are calculated as follows:

- **IOPS Overall Efficiency:** This metric is calculated by dividing the Total Throughput (ops/sec) by the combined Read IOPS and Write IOPS. It provides an overall picture of IOPS efficiency for all system operations.
- **IOPS Read Efficiency:** This metric focuses on read operations specifically. It is calculated by dividing the Total Throughput (ops/sec) by the Read IOPS, offering insights into how efficiently the system processes read requests.
- **IOPS Write Efficiency:** Similar to IOPS Read Efficiency, this metric focuses on write operations. It's calculated by dividing the Total Throughput (ops/sec) by the Write IOPS, providing insights into how efficiently the system handles write requests.

Latency 95th Percentile

Latency refers to the time taken by the system to process a transaction. The 95th percentile latency is a metric that indicates the time taken to process 95% of transactions within the system.

Memory Usage

Memory usage is monitored for both the application (App Memory Usage) and the database server (DB Memory Usage) during peak hours.

They are calculated as follows:

- **App Memory Usage:** (Average used memory per OKE node during peak hours) x (Total number of OKE nodes)
- **Database Memory Usage:** (Average used memory per database instance during peak hours) x (Number of database instances)

Billing Care REST API Performance Metrics

Some common metrics captured during testing for the Billing Care REST API include:

- **Response Times:** Time taken by the API to respond to each request. Analyzed to identify potential bottlenecks.
- **Throughput (ops/sec):** Number of API requests processed per second. Provides an overall picture of processing speed under load.

4

Billing and Invoicing Performance

This chapter provides an analysis of the performance of an Oracle Communications Billing and Revenue Management (BRM) 15.0 cloud native system during billing and invoicing. The performance focuses on the system's resource utilization and transaction processing speed.

Topics in this document:

- [Scenario 1: 14 Million Prepaid Accounts in 2 Schemas with Taxation Disabled](#)
- [Scenario 2: 5 Million Wholesale Accounts in 1 Schema with Taxation Disabled](#)
- [Scenario 3: 6 Million Postpaid Accounts in 2 Schemas with Taxation Enabled](#)
- [Performance Results](#)

Scenario 1: 14 Million Prepaid Accounts in 2 Schemas with Taxation Disabled

This scenario evaluates the billing and invoicing performance of a BRM 15.0.1 cloud native system with 14 million prepaid accounts in 2 schemas and taxation disabled.

[Table 4-1](#) shows the various parameters used for the test.

Table 4-1 Scenario 1 Test Case and Setup Details

Parameter	Value
Account Volume	14,000,000
Subscribers per Schema	7,000,000
Schemas	2
ECE Synchronization	Enabled
Taxation	Disabled
Billing Threads	100
CM Replicas	10
Oracle DM Replicas	5
Oracle DM2 Replicas	5
OKE Nodes	12 (10 OCPUs each)
Shape	VM.Standard.E5.Flex

Scenario 2: 5 Million Wholesale Accounts in 1 Schema with Taxation Disabled

This scenario evaluates the billing and invoicing performance of a BRM 15.0.1 cloud native system with 5 million wholesale accounts in 1 schema and taxation disabled.

[Table 4-2](#) shows the various parameters used for the test.

Table 4-2 Scenario 2 Test Case and Setup Details

Parameter	Value
Account Volume	5,063,896
Schemas	1
ECE Synchronization	Disabled
Taxation	Disabled
Billing Threads	200
CM Replicas	10
Oracle DM Replicas	10
OKE Nodes	12 (10 OCPUs each)
Shape	VM.Standard.E4.Flex

Scenario 3: 6 Million Postpaid Accounts in 2 Schemas with Taxation Enabled

This scenario evaluates the invoicing performance of a BRM 15.0 cloud native system with 6 million accounts in 2 schemas and taxation enabled.

[Table 4-3](#) shows the various parameters used for the test.

Table 4-3 Scenario 3 Test Case and Setup Details

Parameter	Description
Account volume	6,000,000
Subscribers per Schema	3,000,000
Schemas	2
ECE Synchronization	Enabled
Taxation	Enabled
Billing Threads	100
CM Replicas	10
Oracle DM Replicas	5
Oracle DM2 Replicas	5
OKE Nodes	12 (10 OCPUs each)
Shape	VM.Standard.E4.Flex

Performance Results

[Table 4-4](#) provides observation data for the billing performance test.

Table 4-4 Results for Billing

Test	Number of Accounts	Throughput (bills/second)	App CPU Usage (Cores Consumed)	Database CPU Usage (Cores Consumed)	Billing Efficiency
Scenario 1	14,000,000	2190	38	22	36

Table 4-4 (Cont.) Results for Billing

Test	Number of Accounts	Throughput (bills/second)	App CPU Usage (Cores Consumed)	Database CPU Usage (Cores Consumed)	Billing Efficiency
Scenario 2	5,063,896	362	29	16	8

See "[System Performance Benchmarking Metrics](#)" for more information on how these metrics are calculated.

[Table 4-5](#) provides observation data for the invoicing performance test that you can use for benchmarking your system.

Table 4-5 Results for Invoicing

Test	Number of Accounts	Throughput (invoices/second)	App CPU Usage (Cores Consumed)	Database CPU Usage (Cores Consumed)
Scenario 3	6,000,000	683	42	8

See "[System Performance Benchmarking Metrics](#)" for more information on how these metrics are calculated.

5

Charging Efficiency

This chapter focuses on the charging efficiency of an Oracle Communications Billing and Revenue Management (BRM) 15.0.1 cloud native system, specifically its ability to handle transaction processing while maintaining optimal resource utilization.

Topics in this document:

- [Scenario: Voice/Data/SMS Charging Efficiency \(19,700 Transactions\)](#)
- [Charging Efficiency Results](#)

Scenario: Voice/Data/SMS Charging Efficiency (19,700 Transactions)

This scenario evaluates the charging efficiency of a BRM 15.0.1 cloud native system by simulating a high volume of transactions. The system's performance is analyzed using Throughput Efficiency Indexes, which consider the transaction processing speed and CPU usage.

[Table 5-1](#) shows the various parameters used for the test.

Table 5-1 Test Setup and Conditions

Parameter	Description
Account Volume	20,000,000 (all active)
Load Type	High volume
Schemas	2
Data Traffic per Diameter Gateway	15 GB
Database Optimization	Truncated partition for inserts
REM Logging Level	INFO
OKE Node Shape	VM.Standard.E5.Flex

Charging Efficiency Results

[Table 5-2](#) shows the resource utilization, CPU usage, and memory usage of a BRM 15.0.1 cloud native system.

Table 5-2 Resource Utilization

TPS	App CPU Usage (Cores Consumed)	Database CPU Usage (Cores Consumed)	App Memory Usage	Database Memory Usage
19,700	31	5	1715 GB	434 GB

[Table 5-3](#) shows the Throughput Efficiency Index while performing charging on a BRM 15.0.1 cloud native system.

Table 5-3 Throughput Efficiency Index

Overall	App	Database
1098	1281	7707

[Table 5-4](#) shows the input/output operations per second (IOPS) efficiency.

Table 5-4 IOPS Efficiency

Overall	Read	Write
3.83	5.46	12.87

[Table 5-5](#) provides latency results in milliseconds. Latency 95th percentile is taken from peak time of the process.

Table 5-5 Latency

Action	Latency (milliseconds)
Balance Query	1.57
Initiate	2.85
Terminate	3.52
Update	3.62

See "[System Performance Benchmarking Metrics](#)" for more information on how these metrics are calculated.

6

Billing Care REST API Performance

This chapter provides an analysis of the performance of Oracle Communications Billing Care REST API.

The test focuses on the API's ability to handle concurrent requests and its processing speed. Apache JMeter, a load testing tool, was used to generate and manage the API requests.

Topics in this document:

- [Scenario 1: Create 100,000 Accounts Using 50 Threads in 2 Schemas](#)
- [Scenario 2: Get 100,000 Accounts Using 50 Threads in 2 Schemas](#)
- [Performance Results](#)

Scenario 1: Create 100,000 Accounts Using 50 Threads in 2 Schemas

This scenario evaluates the Billing Care REST API's ability to create 100,000 accounts using 50 threads in 2 schemas.

[Table 6-1](#) shows the client configuration used for the test.

Table 6-1 Scenario 1 Test Client Configuration

Parameter	Description
CPU Cores	4 OCPU
Memory	64 GB
Network Bandwidth	8 Gbps

[Table 6-2](#) shows the various parameters used for the test.

Table 6-2 Scenario 1 Test Case and Setup Details

Parameter	Description
Account volume	20,000,000
Number of Accounts to Create	100,000
Schemas	2
Threads	50
CM Replicas	10
Oracle DM Replicas	5
Oracle DM2 Replicas	5
OKE Nodes	12 (10 OCPUs each)
Shape	VM.Standard.E4.Flex

Scenario 2: Get 100,000 Accounts Using 50 Threads in 2 Schemas

This scenario evaluates the Billing Care REST API's ability to retrieve 100,000 accounts using 50 threads in 2 schemas.

[Table 6-3](#) shows the client configuration used for the test.

Table 6-3 Scenario 2 Test Client Configuration

Parameter	Description
CPU Cores	4 OCPU
Memory	64 GB
Network Bandwidth	8 Gbps

[Table 6-4](#) shows the various parameters used for the test.

Table 6-4 Scenario 2 Test Case and Setup Details

Parameter	Description
Account volume	20,000,000
Number of Accounts to Retrieve	100,000
Schemas	2
Threads	50
CM Replicas	10
Oracle DM Replicas	5
Oracle DM2 Replicas	5
OKE Nodes	12 (10 OCPUs each)
Shape	VM.Standard.E4.Flex

Performance Results

[Table 6-5](#) shows the performance results for the Billing Care REST API.

Table 6-5 Performance Results

Test	Number of Accounts	Number of Threads	Number of Schemas	Throughput (transactions/second)	Latency 95th Percentile (ms)
Scenario 1	100,000	50	2	142	423
Scenario 2	100,000	50	2	112	772

See "[System Performance Benchmarking Metrics](#)" for more information on how these metrics are calculated.

Offline Mediation Controller Performance

This chapter provides an analysis of the performance of an Oracle Communications Offline Mediation Controller 15.0.1 cloud native system. The performance focuses on the system's node chain with all cartridges multithreaded.

Topics in this document:

- [Scenario: Collect, Enhance, and Distribute Node Chain Performance with 5 Million CDRs](#)
- [Performance Results](#)

Scenario: Collect, Enhance, and Distribute Node Chain Performance with 5 Million CDRs

This scenario evaluates 5 Million CDRs collected using 1 ASCII Collection Cartridge. This data is then enriched using 1 Enhancement Processor and distributed through 1 Distribution Cartridge.

[Table 7-1](#) shows the various parameters used for the test.

Table 7-1 Scenario Test Case and Setup Details: Offline Mediation Controller Cloud Native

Parameter	Value
Number of Call Detail Records (Input Records)	5,000,000 (100,000 distributed equally across 50 files)
Maximum Number of Records per File (Output Records)	10,000
Number of Threads	• Collection Cartridge Thread Count: 2 • Enhancement Processor Thread Count: 5 • Distribution Cartridge: 5
Bulk Read and Write	Enabled
File Parse Delay	10 Seconds
Idle Write Time	10 Seconds
Read Timer	10 Seconds
Output NARs Per File for Collection Cartridge and Enhancement Processor	10,000
OKE Node Shape	VM.Standard.E5.Flex
Memory Per OKE Node	128 GB
Number of Worker Nodes	4
oCPU Per OKE Node	12
Boot Volume Size per OKE Node	200 GB

Performance Results

[Table 7-2](#) provides observation data for the Offline Mediation Controller end-to-end performance test.

Table 7-2 Performance Results

Duration	Throughput (Number of CDRs Processed Per Second)	App CPU Usage (Cores Consumed)
40 Seconds	125,000	4