

Oracle® Communications

Cloud Native Core, Security Edge Protection Proxy Benchmarking Guide



Release 25.1.202
G38039-03
October 2025

ORACLE®

Copyright © 2025, Oracle and/or its affiliates.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this is software, software documentation, data (as defined in the Federal Acquisition Regulation), or related documentation that is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, then the following notice is applicable:

U.S. GOVERNMENT END USERS: Oracle programs (including any operating system, integrated software, any programs embedded, installed, or activated on delivered hardware, and modifications of such programs) and Oracle computer documentation or other Oracle data delivered to or accessed by U.S. Government end users are "commercial computer software," "commercial computer software documentation," or "limited rights data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, reproduction, duplication, release, display, disclosure, modification, preparation of derivative works, and/or adaptation of i) Oracle programs (including any operating system, integrated software, any programs embedded, installed, or activated on delivered hardware, and modifications of such programs), ii) Oracle computer documentation and/or iii) other Oracle data, is subject to the rights and limitations specified in the license contained in the applicable contract. The terms governing the U.S. Government's use of Oracle cloud services are defined by the applicable contract for such services. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

Oracle®, Java, MySQL, and NetSuite are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Inside are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. AMD, Epyc, and the AMD logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark of The Open Group.

This software or hardware and documentation may provide access to or information about content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services unless otherwise set forth in an applicable agreement between you and Oracle. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services, except as set forth in an applicable agreement between you and Oracle.

Contents

1	Overview	
1.1	Purpose and Scope	1
1.2	References	1
2	Deployment Environment	
2.1	Overall Summary of Benchmarking Configurations	1
3	SEPP Benchmark Testing	
3.1	Test Scenario 1: SEPP 40K MPS, 36 Hrs Run with Features Enabled with 50ms Delay at Server End	1
3.1.1	Testcase and Setup Details	1
3.1.2	Traffic and Latency	9
3.1.3	Results	9
3.2	Test Scenario 2: SEPP 40K MPS, 24 Hrs Run with ASM Enabled and without any Feature Enabled with 50ms Delay at Server End	10
3.2.1	Test Case and Setup Details	11
3.2.2	Traffic and Latency	14
3.2.3	Results	15

Preface

- [Documentation Accessibility](#)
- [Diversity and Inclusion](#)
- [Conventions](#)

Documentation Accessibility

For information about Oracle's commitment to accessibility, visit the Oracle Accessibility Program website at <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=docacc>.

Access to Oracle Support

Oracle customer access to and use of Oracle support services will be pursuant to the terms and conditions specified in their Oracle order for the applicable services.

Diversity and Inclusion

Oracle is fully committed to diversity and inclusion. Oracle respects and values having a diverse workforce that increases thought leadership and innovation. As part of our initiative to build a more inclusive culture that positively impacts our employees, customers, and partners, we are working to remove insensitive terms from our products and documentation. We are also mindful of the necessity to maintain compatibility with our customers' existing technologies and the need to ensure continuity of service as Oracle's offerings and industry standards evolve. Because of these technical constraints, our effort to remove insensitive terms is ongoing and will take time and external cooperation.

Conventions

The following text conventions are used in this document:

Convention	Meaning
boldface	Boldface type indicates graphical user interface elements associated with an action, or terms defined in text or the glossary.
<i>italic</i>	Italic type indicates book titles, emphasis, or placeholder variables for which you supply particular values.
monospace	Monospace type indicates commands within a paragraph, URLs, code in examples, text that appears on the screen, or text that you enter.

My Oracle Support

My Oracle Support (<https://support.oracle.com>) is your initial point of contact for all product support and training needs. A representative at Customer Access Support can assist you with My Oracle Support registration.

Call the Customer Access Support main number at 1-800-223-1711 (toll-free in the US), or call the Oracle Support hotline for your local country from the list at <http://www.oracle.com/us/support/contact/index.html>. When calling, make the selections in the sequence shown below on the Support telephone menu:

1. Select **2** for New Service Request.
2. Select **3** for Hardware, Networking and Solaris Operating System Support.
3. Select one of the following options:
 - For Technical issues such as creating a new Service Request (SR), select **1**.
 - For Non-technical issues such as registration or assistance with My Oracle Support, select **2**.

You are connected to a live agent who can assist you with My Oracle Support registration and opening a support ticket.

My Oracle Support is available 24 hours a day, 7 days a week, 365 days a year.

Acronyms

The following table lists the acronyms and the terminologies used in the document:

Table Acronyms and Terminologies

Acronym	Description
Cat-0	Category 0 SBI Message Schema Validation Feature
Cat-1	Category 1 Service API Validation Feature
Cat-2	Category 2 Network ID Validation Feature
Cat-3	Category 3 Previous Location Check/ Category 3 Time location check
CNC Console	Oracle Communications Cloud Native Configuration Console
CRD	Custom Resource Definition
CNE	Oracle Communications Cloud Native Environment
cSEPP/C-SEPP	Consumer Security Edge Protection Proxy
DB	Database
DNS	Domain Name System
DRL	Drools Rule Language
EGW	Egress Gateway
FQDN	Fully Qualified Domain Name
GSMA	Groupe Speciale Mobile Association (GSMA). Represents the interests of mobile operators and the broader mobile industry worldwide.
Hosted SEPP	Hosted SEPP functionality provides selective routing in Roaming Hub Mode
IGW	Ingress Gateway
IPX	Internetwork Packet Exchange
K8s	Kubernetes
Local PLMN	PLMN managed by Local SEPP
Local SEPP	SEPP in Local PLMN
MNO	Mobile Network Operator
NDB	Network Database
NF	Network Function
Network Function	A functional building block within a network infrastructure, which has well defined external interfaces and well defined functional behavior. In practical terms, a network function is often a network node or physical appliance.
NF Consumer	A generic way to refer to an NF which consumes services provided by another NF. Example: An AMF acts as a Consumer NF that consumes AMPolicy services provided by the PCF.
NF Instance	A specific instance of a network function type.
NF Producer or NF Provider	A generic way to refer to an NF which provides services that can be consumed by another NF. Example: A PCF acts as a Producer NF that provides AMPolicy Services to the AMF.
NRF	Oracle Communications Cloud Native Core, Network Repository Function
OHC	Oracle Help Center
OSDC	Oracle Software Delivery Cloud
PDB	PodDisruptionBudget

Table (Cont.) Acronyms and Terminologies

Acronym	Description
PLMN	Public Land Mobile Network
pSEPP/P-SEPP	Producer Security Edge Protection Proxy
Remote PLMN	PLMN managed by Remote SEPP
Remote SEPP	SEPP in Remote PLMN
Remote SEPP Set	Set of Remote SEPPs to allow alternate routing across Remote SEPPs
REST API	Representational State Transfer Application Programming Interface
Roaming Hub	Roaming Hub is the deployment mode of SEPP. Roaming Hub is used as an intermediate proxy. Each SEPP connects to the Roaming Hub which further connect to another SEPP. All the Remote SEPPs can communicate with each other through roaming hub.
Scaling	Ability to dynamically extend or reduce resources granted to the Virtual Network Function (VNF) as needed. This includes scaling out and in or scaling up and down.
SCM	Security Countermeasure
SEPP	Oracle Communications Cloud Native Core, Security Edge Protection Proxy
SUCI	Subscription Concealed Identifier
SUPI	Subscription Permanent Identifier
SVC	Service
TLS	Transport Layer Security
TH	Topology Hiding
TUH	Topology Unhiding
TPS	Transactions Per Second
UE	User Equipment
UDR	Oracle Communications Cloud Native Core, Unified Data Repository

What's New in This Guide

This section introduces the documentation updates for Release 25.1.2xx.

Release 25.1.202 - G38039-03, October 2025

There are no updates made to this document in this release.

Release 25.1.201 - G38039-02, August 2025

There are no updates made to this document in this release.

Release 25.1.200 - G38039-01, July 2025

Added the following test scenarios:

- [Test Scenario 1: SEPP 40K MPS, 36 Hrs Run with Features Enabled with 50ms Delay at Server End](#)
- [Test Scenario 2: SEPP 40K MPS, 24 Hrs Run without any Feature Enabled with 50ms Delay at Server End](#)

1

Overview

Security Edge Protection Proxy (SEPP) is a key component of the 5G Service Based Architecture. It is a proxy Network Function (NF) which is used for the secured communication for inter Public Land Mobile Network (PLMN) messages.

For more information about the SEPP architecture, see *Oracle Communications Cloud Native Core, Security Edge Protection Proxy User Guide*.

The user can install either SEPP or Roaming Hub/Hosted SEPP.

Note

The performance and capacity of the SEPP system may vary based on the call model, Feature/Interface configuration, and underlying CNE and hardware environment.

1.1 Purpose and Scope

This document is designed to help operators measure the capacity and performance of SEPP, SEPP microservices, and deployment environment setup software such as Cloud Native Environment (CNE) and cnDBTier.

This document provides SEPP performance and capacity data. It is recommended that SEPP is run through a benchmark on the target cloud native infrastructure to determine the capacity and performance in the target infrastructure. This information can be used to adjust the initial deployment resources and to help predict resource requirements when SEPP is scaled up.

1.2 References

For more information on Security Edge Protection Proxy (SEPP), refer to the following documents:

- *Oracle Communications Cloud Native Core, Security Edge Protection Proxy Installation, Upgrade, and Fault Recovery Guide*
- *Oracle Communications Cloud Native Core, Security Edge Protection Proxy User Guide*
- *Oracle Communications Cloud Native Core, Security Edge Protection Proxy REST Specification Guide*
- *Oracle Communications Cloud Native Core, Security Edge Protection Proxy Troubleshooting Guide*
- *Oracle Communications Cloud Native Core, cnDBTier Installation, Upgrade, and Fault Recovery Guide*
- *Oracle Communications Cloud Native Core, cnDBTier User Guide*


2

Deployment Environment

This section provides information about the cloud native infrastructure used for SEPP benchmarking.

The following diagram represents the deployment configurations of SEPP:

Figure 2-1 Deployment Diagram



The details about the deployment configurations are as follows:

- cnDBTier, cSEPP, pSEPP, perfgo-client, and perfgo-server are deployed in same cluster
- DNS server is running on a standalone VM in a different cluster
- cSEPP to pSEPP n32 TLS 1.3 connection is on External IP (metalLB)
- perfgo-client is sending traffic on SEPP external IP
- SEPP to perfgo-server connection is using External IP (metalLB)
- Both SEPP have 30 local PLMNs
- Network delay of 50 ms on server side

2.1 Overall Summary of Benchmarking Configurations

The following table lists the overall summary of benchmarking configurations.

Overall Summary

Table 2-1 Overall Summary

S. No.	Execution Time	SEP Release	CNC Release	cnDBTier Release	ASM Enabled/ Disabled	OS O(Y es/ No)	HA Proxy Installed	Cluster	Site -1 MP S	Site -2 MP S	Overall MP S	Network Delay on server side	Features Enabled
Run1	36 Hr	25.1.200	25.1.200	25.1.200	Enabled	Yes	NA	Hard head 1	20K	20K	40K	50ms	Topology Hiding, SCM (Cat-0, Cat-1,Cat-2, and Cat3), Overload,Mediation, SOR,and Rate Limiting (Only Global PLMN Ingress Rate Limiting) and DNS SRV
Run2	24 Hr	25.1.200	25.1.200	25.1.200	Enabled	Yes	NA	Hard head 1	20K	20K	40K	50ms	Vanilla Run

3

SEPP Benchmark Testing

This section provides information about the SEPP testcases run in different scenarios.

3.1 Test Scenario 1: SEPP 40K MPS, 36 Hrs Run with Features Enabled with 50ms Delay at Server End

This test scenario describes the performance and capacity of SEPP and provides the benchmarking results for 40K MPS, 36 hours run with the following SEPP features enabled with 50ms delay at the server end:

- Topology Hiding
- Security Counter Measure features:
 - Cat-0 SBI Message Schema Validation Feature
 - Cat-1 NRF Service API Query Parameters Validation
 - Cat-1 Service API Validation Feature
 - Cat -2 Network ID Validation Feature
 - Cat-3 Previous Location Check Feature
 - Cat-3 Time Check for Roaming Subscribers
- Overload Control
- 5G SBI Message Mediation Support
- Steering of Roaming (SOR) Feature
- Global Rate Limiting on Ingress Gateway of SEPP
- Alternate Routing and Load Sharing based on the DNS SRV Record for Home Network Functions

Note

ASM is enabled in this test case scenario.

3.1.1 Testcase and Setup Details

Following are the testcase and setup details:

Traffic Model Details

Table 3-1 Transactions Per Second (TPS)

Total TPS	Site 1	Site 2
40K MPS	20K MPS	20K MPS

Setup Details**Table 3-2 Setup Details**

Setup Details	Values
Active User	NA for SEPP
Execution Time	36 Hrs
Environment	vcNE
Cluster	Hardhead1
cnDBTier	25.1.200
cSEPP	25.1.200
pSEPP	25.1.200
CNC Console	25.1.200
Setup Configuration	- Both SEPPs are deployed on Model-B. - cnDBTier is deployed on both sites.
List of SEPP Features enabled	- Topology Hiding - Security Counter Measure features: - Cat-0 SBI Message Schema Validation Feature - Cat-1 NRF Service API Query Parameters Validation - Cat-1 Service API Validation Feature - Cat -2 Network ID Validation Feature - Cat-3 Previous Location Check Feature - Cat-3 Time Check for Roaming Subscribers - Overload Control 5G SBI Message Mediation Support - Steering of Roaming (SOR) Feature - Global Rate Limiting on Ingress Gateway of SEPP - Alternate Routing and Load Sharing based on the DNS SRV Record for Home Network Functions

Resource Footprint**Table 3-3 Resource Footprint**

Microservices / container	Container Count	CPU Resource per container (Limit)	CPU Resource per container (Request)	Memory Resource per container (Limit)	Memory Resource per container (Request)
Site1-ocsepp-alternate-route/ alternate-route	2	2	2	4Gi	4Gi

Table 3-3 (Cont.) Resource Footprint

Microservices / container	Container Count	CPU Resource per container (Limit)	CPU Resource per container (Request)	Memory Resource per container (Limit)	Memory Resource per container (Request)
Site1-ocsepp-appinfo/appinfo	2	1	1	2Gi	1Gi
Site1-ocsepp-cn32c-svc/cn32c-svc	2	2	2	2Gi	2Gi
Site1-ocsepp-cn32f-svc/cn32f-svc	7	5	5	8Gi	8Gi
Site1-ocsepp-coherence-svc/coherence-svc	1	1	1	2Gi	2Gi
Site1-ocsepp-config-mgr-svc/config-mgr-svc	1	2	2	2Gi	2Gi
Site1-ocsepp-n32-egress-gateway/n32-egress-gateway	7	5	5	5Gi	5Gi
Site1-ocsepp-n32-ingress-gateway/n32-ingress-gateway	7	6	6	5Gi	5Gi
ocsepp-nf-mediation/nf-mediation	2	8	8	8Gi	8Gi
Site1-ocsepp-ocpm-config/config-server	2	1	1	1Gi	1Gi
Site1-ocsepp-performance/perf-info	2	2	2	4Gi	200Mi
Site1-ocsepp-plmn-egress-gateway/plmn-egress-gateway	7	5	5	5Gi	5Gi
Site1-ocsepp-plmn-ingress-gateway/plmn-ingress-gateway	7	5	5	5Gi	5Gi
Site1-ocsepp-pn32c-svc/pn32c-svc	2	2	2	2Gi	2Gi
Site1-ocsepp-pn32f-svc/pn32f-svc	7	5	5	8Gi	8Gi

Table 3-3 (Cont.) Resource Footprint

Microservices / container	Container Count	CPU Resource per container (Limit)	CPU Resource per container (Request)	Memory Resource per container (Limit)	Memory Resource per container (Request)
Site1-ocsepp-sepp-nrf-client-nfdiscovery/nrf-client-nfdiscovery	2	1	1	2Gi	2Gi
Site1-ocsepp-sepp-nrf-client-nfmanagement/nrf-client-nfmanagement	1	1	1	1Gi	1Gi
Site2-ocsepp-alternate-route/alternate-route	1	2	2	4Gi	4Gi
Site2-ocsepp-appinfo/appinfo	2	1	1	2Gi	1Gi
Site2-ocsepp-cn32c-svc/cn32c-svc	2	2	2	2Gi	2Gi
Site2-ocsepp-cn32f-svc/cn32f-svc	7	5	5	8Gi	8Gi
Site2-ocsepp-coherence-svc/coherence-svc	1	1	1	2Gi	2Gi
Site2-ocsepp-config-mgr-svc/config-mgr-svc	1	2	2	2Gi	2Gi
Site2-ocsepp-n32-egress-gateway/n32-egress-gateway	7	5	5	5Gi	5Gi
Site2-ocsepp-n32-ingress-gateway/n32-ingress-gateway	7	6	6	5Gi	5Gi
Site2-ocsepp-ocpm-config/config-server	2	1	1	1Gi	1Gi
Site2-ocsepp-performance/perf-info	2	2	2	4Gi	200Mi
Site2-ocsepp-plmn-egress-gateway/plmn-egress-gateway	7	5	5	5Gi	5Gi

Table 3-3 (Cont.) Resource Footprint

Microservices / container	Container Count	CPU Resource per container (Limit)	CPU Resource per container (Request)	Memory Resource per container (Limit)	Memory Resource per container (Request)
Site2-ocsepp-plmn-ingress-gateway/plmn-ingress-gateway	7	5	5	5Gi	5Gi
Site2-ocsepp-pn32c-svc/pn32c-svc	2	2	2	2Gi	2Gi
Site2-ocsepp-pn32f-svc/pn32f-svc	7	5	5	8Gi	8Gi
Site2-ocsepp-sepp-nrf-client-nfdiscovery/nrf-client-nfdiscovery	2	1	1	2Gi	2Gi
Site2-ocsepp-sepp-nrf-client-nfmanagement/nrf-client-nfmanagement	1	1	1	1Gi	1Gi
Site2-mysql-cluster-db-backup-manager-svc/db-backup-manager-svc	1	100m	100m	128Mi	128Mi
Site2-mysql-cluster-db-monitor-svc/db-monitor-svc	1	4	4	4Gi	4Gi
Site2-ndbappmysqld/mysqlndbcluster	2	8	8	10Gi	10Gi
Site2-ndbappmysqld/init-sidecar	2	100m	100m	256Mi	256Mi
Site2-ndbmgmd/mysqlndbcluster	2	4	4	10Gi	8Gi
Site2-ndbmgmd/db-infra-monitor-svc	2	100m	100m	256Mi	256Mi
Site2-ndbmtl/mysqlndbcluster	4	10	10	18Gi	16Gi

Table 3-3 (Cont.) Resource Footprint

Microservices / container	Container Count	CPU Resource per container (Limit)	CPU Resource per container (Request)	Memory Resource per container (Limit)	Memory Resource per container (Request)
Site1-mysql-cluster-db-backup-manager-svc/db-backup-manager-svc	1	100m	100m	128Mi	128Mi
Site2-ndbmttd/db-backup-executor-svc	4	100m	100m	256Mi	256Mi
Site1-mysql-cluster-db-monitor-svc/db-monitor-svc	1	4	4	4Gi	4Gi
Site2-ndbmttd/db-infra-monitor-svc	4	100m	100m	256Mi	256Mi
Site1-ndbappmysqld/mysqlndbcluster	2	8	8	10Gi	10Gi
Site1-ndbappmysqld/init-sidecar	2	100m	100m	256Mi	256Mi
Site1-ndbmcmd/mysqlndbcluster	2	4	4	10Gi	8Gi
Site1-ndbmcmd/db-infra-monitor-svc	2	100m	100m	256Mi	256Mi
Site1-ndbmttd/mysqlndbcluster	4	10	10	18Gi	16Gi
Site1-ndbmttd/db-backup-executor-svc	4	100m	100m	256Mi	256Mi
Site1-ndbmttd/db-infra-monitor-svc	4	100m	100m	256Mi	256Mi
Site1-hello-world2/hello-world2	2	NA	NA	NA	NA

Table 3-3 (Cont.) Resource Footprint

Microservices / container	Container Count	CPU Resource per container (Limit)	CPU Resource per container (Request)	Memory Resource per container (Limit)	Memory Resource per container (Request)
Site1-occne-alertmanager-snmp-notifier/alertmanager-snmp-notifier	1	NA	NA	NA	NA
Site1-occne-bastion-controller/bastion-controller	1	200m	10m	256Mi	128Mi
Site1-occne-kube-prom-stack-grafana/grafana-sc-dashboard	1	NA	NA	NA	NA
Site1-occne-kube-prom-stack-grafana/grafana-sc-datasources	1	NA	NA	NA	NA
Site1-occne-kube-prom-stack-grafana/grafana	1	500m	500m	500Mi	500Mi
Site1-occne-kube-prom-stack-kube-operator/kube-prometheus-stack	1	200m	100m	200Mi	100Mi
Site1-occne-kube-prom-stack-kube-state-metrics/kube-state-metrics	1	20m	20m	500Mi	32Mi
Site1-occne-metrics-server/metrics-server	1	100m	100m	200Mi	200Mi
Site1-occne-promxy/promxy	1	100m	100m	512Mi	512Mi
Site1-occne-promxy-apigw-nginx/nginx	2	2	1	1536Mi	1Gi
Site1-occne-tracer-jaeger-collector/occne-tracer-jaeger-collector	1	1250m	500m	1Gi	512Mi

Table 3-3 (Cont.) Resource Footprint

Microservices / container	Container Count	CPU Resource per container (Limit)	CPU Resource per container (Request)	Memory Resource per container (Limit)	Memory Resource per container (Request)
Site1-occne-tracer-jaeger-query/occne-tracer-jaeger-query	1	500m	256m	512Mi	128Mi
Site1-occne-tracer-jaeger-query/occne-tracer-jaeger-agent-sidecar	1	NA	NA	NA	NA
Site1-alertmanager-occne-kube-prom-stack-kube-alertmanager/alertmanager	2	20m	20m	64Mi	64Mi
Site1-alertmanager-occne-kube-prom-stack-kube-alertmanager/config-reloader	2	200m	200m	50Mi	50Mi
Site1-occne-opensearch-cluster-client/opensearch	3	1	1	2Gi	2Gi
Site1-occne-opensearch-cluster-data/opensearch	5	2	1	32Gi	16Gi
Site1-occne-opensearch-cluster-master/opensearch	3	2	1	32Gi	16Gi
Site1-prometheus-occne-kube-prom-stack-kube-prometheus/prometheus	2	12	12	55Gi	55Gi
Site1-prometheus-occne-kube-prom-stack-kube-prometheus/config-reloader	2	200m	200m	50Mi	50Mi

Note

- Mi- Megabytes
- Gi- Gigabytes
- m- millicores
- CPU Resource per container without unit is represented in cores

3.1.2 Traffic and Latency

The following tables describe the traffic and latency details:

Traffic Details

Table 3-4 Traffic Details

TPS	Site-1	Site-2
PLMN-IGW-requests-rate	10290.83	10305.44
CN32F-requests-rate	10148.51	10237.15
N32-IGW-requests-rate	10237.13	10148.64
N32-EGW-requests-rate	10148.65	10237.16
PN32F-requests-rate	10236.35	10147.94
PLMN-EGW-requests-rate	10537.70	10445.02
Total TPS	10266.5	10253.5

Latency Details

Table 3-5 Latency Details

NF Service Latency(In MilliSecond)	Site-1	Site-2
IGW(s)	0.17	0.24
EGW(s)	0.25	0.18
cn32f(s)	0.13	0.10
pn32f(s)	0.03	0.03

3.1.3 Results

- csepp call success rate: 99.522%

Note

A 0.48% drop was intentionally introduced by enabling global rate limiting on the PLMN Ingress gateway. Actual success rate is 99.998%.

- psepp call success rate: 99.677%

Note

A 0.33% drop was intentionally introduced by enabling global rate limiting on the PLMN Ingress gateway. Actual success rate is 99.999%.

- csepp_Avg_Latency_rate: 107.03ms
- psepp_Avg_Latency_rate: 101.61ms
- No pod restarts are observed
- Perfgo deployed on hardhead 1 cluster with 15 server and 4 client each side
- Run with 50ms server delay
- Features enabled:
 - Topology Hiding
 - Security Counter Measure features:
 - * Cat-0 SBI Message Schema Validation Feature
 - * Cat-1 NRF Service API Query Parameters Validation
 - * Cat-1 Service API Validation Feature
 - * Cat -2 Network ID Validation Feature
 - * Cat-3 Previous Location Check Feature
 - * Cat-3 Time Check for Roaming Subscribers
 - Overload Control
 - 5G SBI Message Mediation Support
 - Steering of Roaming (SOR) Feature
 - Global Rate Limiting on Ingress Gateway of SEPP
 - Alternate Routing and Load Sharing based on the DNS SRV Record for Home Network Functions

3.2 Test Scenario 2: SEPP 40K MPS, 24 Hrs Run with ASM Enabled and without any Feature Enabled with 50ms Delay at Server End

This test scenario describes the performance and capacity of SEPP and provides the benchmarking results for 24 Hrs with ASM enabled and without any feature enabled with 50ms delay at the server end.

Note

ASM is enabled in this test case scenario.

3.2.1 Test Case and Setup Details

Following are the testcase and setup details:

Traffic Model Details

Table 3-6 Transactions Per Second (TPS)

Total TPS	Site 1	Site 2
40K MPS	20K MPS	20K MPS

Setup Details

Table 3-7 Setup Details

Setup Details	Values
Active User	NA for SEPP
Execution Time	24 Hrs
Environment	vCNE
Cluster	Hardhead1
cnDBTier	25.1.200
cSEPP	25.1.200
pSEPP	25.1.200
CNC Console	25.1.200
Setup Configuration	- Both SEPPs are deployed on hardhead1. - cnDBTier is deployed on both sites.
List of SEPP Features enabled	None. This test case is performed on a vanilla SEPP deployment.

Resource Footprint

Table 3-8 Resource Footprint

Micro services/ container	Replicas	CPU (Limit)	CPU (Request)	Memory (Limit)	Memory (Request)
Site2-ocsepp-alternate-route/ alternate-route	2	2	2	4Gi	4Gi
Site2-ocsepp-appinfo/appinfo	2	1	1	2Gi	1Gi
Site2-ocsepp-cn32c-svc/ cn32c-svc	2	2	2	2Gi	2Gi
Site2-ocsepp-cn32f-svc/ cn32f-svc	7	5	5	8Gi	8Gi
Site2-ocsepp-coherence-svc/ coherence-svc	1	1	1	2Gi	2Gi

Table 3-8 (Cont.) Resource Footprint

Micro services/ container	Replicas	CPU (Limit)	CPU (Request)	Memory (Limit)	Memory (Request)
Site2-ocsepp- config-mgr-svc/ config-mgr-svc	1	2	2	2Gi	2Gi
Site2-ocsepp- n32-egress- gateway/n32- egress-gateway	7	5	5	5Gi	5Gi
Site2-ocsepp- n32-ingress- gateway/n32- ingress- gateway	7	6	6	5Gi	5Gi
Site2-ocsepp- nf-mediation/nf- mediation	2	8	8	8Gi	8Gi
Site2-ocsepp- ocpm-config/ config-server	2	1	1	1Gi	1Gi
Site2-ocsepp- performance/ perf-info	2	2	2	4Gi	200Mi
Site2-ocsepp- plmn-egress- gateway/plmn- egress-gateway	7	5	5	5Gi	5Gi
Site2-ocsepp- plmn-ingress- gateway/plmn- ingress- gateway	7	5	5	5Gi	5Gi
Site2-ocsepp- pn32c-svc/ pn32c-svc	2	2	2	2Gi	2Gi
Site2-ocsepp- pn32f-svc/ pn32f-svc	7	5	5	8Gi	8Gi
Site2-ocsepp- sepp-nrf-client- nfdiscovery/nrf- client- nfdiscovery	2	1	1	2Gi	2Gi
Site2-ocsepp- sepp-nrf-client- nfmanagement/ nrf-client- nfmanagement	1	1	1	1Gi	1Gi
Site1-ocsepp- alternate-route/ alternate-route	2	2	2	4Gi	4Gi

Table 3-8 (Cont.) Resource Footprint

Micro services/ container	Replicas	CPU (Limit)	CPU (Request)	Memory (Limit)	Memory (Request)
Site1-ocsepp-appinfo/appinfo	2	1	1	2Gi	1Gi
Site1-ocsepp-cn32c-svc/ cn32c-svc	2	2	2	2Gi	2Gi
Site1-ocsepp-cn32f-svc/ cn32f-svc	7	5	5	8Gi	8Gi
Site1-ocsepp-coherence-svc/ coherence-svc	1	1	1	2Gi	2Gi
Site1-ocsepp-config-mgr-svc/ config-mgr-svc	1	2	2	2Gi	2Gi
Site1-ocsepp-n32-egress-gateway/ n32-egress-gateway	7	5	5	5Gi	5Gi
Site1-ocsepp-n32-ingress-gateway/ n32-ingress-gateway	7	6	6	5Gi	5Gi
Site1-ocsepp-nf-mediation/nf-mediation	2	8	8	8Gi	8Gi
Site1-ocsepp-ocpm-config/ config-server	2	1	1	1Gi	1Gi
Site1-ocsepp-performance/ perf-info	2	2	2	4Gi	200Mi
Site1-ocsepp-plmn-egress-gateway/ plmn-egress-gateway	7	5	5	5Gi	5Gi
Site1-ocsepp-plmn-ingress-gateway/ plmn-ingress-gateway	7	5	5	5Gi	5Gi
Site1-ocsepp-pn32c-svc/ pn32c-svc	2	2	2	2Gi	2Gi
Site1-ocsepp-pn32f-svc/ pn32f-svc	7	5	5	8Gi	8Gi

Table 3-8 (Cont.) Resource Footprint

Micro services/ container	Replicas	CPU (Limit)	CPU (Request)	Memory (Limit)	Memory (Request)
Site1-ocsepp-sepp-nrf-client-nfdiscovery/nrf-client-nfdiscovery	2	1	1	2Gi	2Gi
Site1-ocsepp-sepp-nrf-client-nfmanagement/nrf-client-nfmanagement	1	1	1	1Gi	1Gi

Note

- Mi- Megabytes
- Gi- Gigabytes
- m- millicore
- CPU Resource per container without unit is represented in cores

3.2.2 Traffic and Latency

The following tables describe the traffic and latency details:

Traffic Details

Table 3-9 Traffic Details

TPS	Site-1	Site-2
PLMN-IGW-requests-rate	10289.46	10289.58
CN32F-requests-rate	10289.45	10289.59
N32-IGW-requests-rate	10289.61	10289.47
N32-EGW-requests-rate	10289.45	10289.57
PN32F-requests-rate	10289.61	10289.42
PLMN-EGW-requests-rate	10289.60	10289.46
Total TPS	10289.5	10289.5

Latency Details

Table 3-10 Latency Details

NF Service Latency(In MilliSecond)	Site-1	Site-2
IGW(s)	0.06	0.06

Table 3-10 (Cont.) Latency Details

NF Service Latency(In MilliSecond)	Site-1	Site-2
EGW(s)	0.07	0.07
cn32f(s)	0.04	0.04
pn32f(s)	0.03	0.03

3.2.3 Results

- csepp call success rate: 100%
- psepp call success rate: 100%
- csepp_Avg_Latency_rate: 86.165 ms
- psepp_Avg_Latency_rate: 85.670 ms
- No pod restarts are observed.
- Perfgo deployed on hardhead 1 cluster with 7 server and 8 client each side.
- Run with 50ms server delay.
- Feature enabled: NA (Vanilla run)