

Oracle® Communications

Cloud Native Core, Converged Policy REST Specification Guide



Release 26.1.201
G55981-01
August 2026

ORACLE®

Copyright © 2019, 2026, Oracle and/or its affiliates.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this is software, software documentation, data (as defined in the Federal Acquisition Regulation), or related documentation that is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, then the following notice is applicable:

U.S. GOVERNMENT END USERS: Oracle programs (including any operating system, integrated software, any programs embedded, installed, or activated on delivered hardware, and modifications of such programs) and Oracle computer documentation or other Oracle data delivered to or accessed by U.S. Government end users are "commercial computer software," "commercial computer software documentation," or "limited rights data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, reproduction, duplication, release, display, disclosure, modification, preparation of derivative works, and/or adaptation of i) Oracle programs (including any operating system, integrated software, any programs embedded, installed, or activated on delivered hardware, and modifications of such programs), ii) Oracle computer documentation and/or iii) other Oracle data, is subject to the rights and limitations specified in the license contained in the applicable contract. The terms governing the U.S. Government's use of Oracle cloud services are defined by the applicable contract for such services. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

Oracle®, Java, MySQL, and NetSuite are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Inside are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. AMD, Epyc, and the AMD logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark of The Open Group.

This software or hardware and documentation may provide access to or information about content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services unless otherwise set forth in an applicable agreement between you and Oracle. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services, except as set forth in an applicable agreement between you and Oracle.

Contents

1 Introduction

1.1	Overview	1
1.2	References	2

2 Policy REST Specifications

2.1	PCF Traffic Profile ADC Rule	1
2.2	PCF Predefined ADC Rule	6
2.3	PCF Predefined ADC Rule Base	8
2.4	Mated Region	11
2.5	Site Fallback	13
2.6	Timer Service	15
2.7	Bulwark Congestion Migration	17
2.8	Diameter Gateway Congestion Migration	24
2.9	Congestion Control	29
2.10	Congestion Control Load Shedding Profiles	44
2.11	NRF Agent	59
2.12	Error Configurations	61
2.13	Diameter Error Codes	63
2.14	Session Viewer	66
2.15	Policy General Settings	69
2.16	Subscriber Logging	73
2.17	Recreate Attempts	75
2.18	Retry Profile	84
2.19	Timer Profile	100
2.20	Retry Profile for PCC	105
2.21	Retry Profile for ADC	109
2.22	Site Takeover	113
2.23	NF Profile	114
2.24	Session Management Service	123
2.25	Session Rule	151
2.26	Session Rule Profile	154
2.27	QoS Information	157
2.28	QoS Data	161

2.29	Traffic for PCC Rule	166
2.30	Traffic for PCC Profile	173
2.31	Traffic for Diameter QoS	179
2.32	Traffic for ADC Rule	183
2.33	Time Period	187
2.34	Predefined Pcc Rule Base	190
2.35	Predefined Pcc Rule	193
2.36	Predefined Adc Rule Base	196
2.37	Predefined Adc Rule	198
2.38	PCRF Presence Reporting Area	201
2.39	Media Profile	207
2.40	Match List	211
2.41	Dropdown Blocks	214
2.42	Custom Vendor	215
2.43	Custom Schema	218
2.44	Custom AVP	219
2.45	Charging Server	222
2.46	PCRF Public Log	225
2.47	User Service	226
2.48	Test Policy Projects	235
2.49	Data Model	237
2.50	Policy Projects	239
2.51	Policy Data	242
2.52	URSP	244
2.53	UPSI	248
2.54	Traffic Control Data	251
2.55	PCC Rule	257
2.56	PCC Rule Profile	265
2.57	Condition Data	273
2.58	Charging Data	276
2.59	Service Area Restriction	282
2.60	PCF Presence Reporting Area	286
2.61	Policy Table	295
2.62	Policy Counter Id	299
2.63	Diameter Settings	302
2.64	Diameter Repaving	308
2.65	Diameter Routing Table	312
2.66	Data Sources	315
2.67	Bulk Import Export Controller	321
2.68	Consistent Logging Level	323
2.69	Load Shedding Profile	325
2.70	Message Priority Profile	331

2.71	Congestion Threshold	338
2.72	Peer Node Sets	342
2.73	Peer Nodes	343
2.74	Access and Mobility Service	346
2.75	Policy Authorization Service	358
2.76	UE Policy	368
2.77	PCRF Core Service	385
2.78	Serving Gateway	393
2.79	Network for PGW	396
2.80	Network for GGSN	399
2.81	Audit Service	402
2.82	Binding Service	405
2.83	NF Communication Profiles	416
2.84	PDS Settings	427
2.85	PDS Workflow	435
2.86	Policy Engine	438
2.87	NWDAF Agent	439
2.88	Notifier Service	442
2.88.1	Notifier Configurations	442
2.88.2	SMS Gateway	444
2.88.3	SMSC HOST Info	447
2.89	Usage Monitoring	449
2.89.1	Usage Monitoring Service	450
2.89.2	Attribute Forwarding Profile	468
2.89.3	UM Data Limit Selection Profile	471
2.89.4	UM Data Limit Profile	476
2.89.5	Data Limit Sorting Profile	482
2.89.6	Data Rollover Profile	484
2.90	Rx Reauth Profiles	488
2.91	Diameter Connector	493
2.92	PDS UE ID Configuration Settings	496
2.93	Force Cleanup API	501
2.94	DNN	501
2.95	SNSSAI	502
2.96	Service URN	503
2.97	Message Profile	504
2.98	Service Profiles	515
2.99	Default Processing Profile	517
2.100	Overload Configurations	522
2.101	Yaml Schema API	526
2.102	HTTP Server API	538

3 Common Services REST Specifications

3.1	OAuth Validator REST API Configuration	1
3.2	CCA Header Validation	4
3.3	XFCC Header Validation	6
3.4	Egress Gateway for SCP Health	8
3.5	OC Policy Mapping	13
3.6	Error Code Profiles	14
3.7	OC Discard Policies	16
3.8	Overload Level Threshold	18
3.8.1	Overload Level Threshold Profiles	21
3.9	NF profile registration with NRF	29
3.10	Server Header at Ingress Gateway	31
3.11	Rate Limiting	35
3.11.1	Rate Limiting at Ingress Gateway	35
3.12	Failure Count at Ingress Gateway	38
3.13	Route Level Configuration	41
3.14	Controlled Shutdown at Ingress and Diameter Gateway	42
3.15	NF Scoring for a Site	49
3.16	Configuration for User-Agent Header Generation at Egress Gateway	53

A Result Codes

Preface

- [Documentation Accessibility](#)
- [Diversity and Inclusion](#)

Documentation Accessibility

For information about Oracle's commitment to accessibility, visit the Oracle Accessibility Program website at <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=docacc>.

Access to Oracle Support

Oracle customers that have purchased support have access to electronic support through My Oracle Support. For information, visit <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=info> or visit <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=trs> if you are hearing impaired.

Diversity and Inclusion

Oracle is fully committed to diversity and inclusion. Oracle respects and values having a diverse workforce that increases thought leadership and innovation. As part of our initiative to build a more inclusive culture that positively impacts our employees, customers, and partners, we are working to remove insensitive terms from our products and documentation. We are also mindful of the necessity to maintain compatibility with our customers' existing technologies and the need to ensure continuity of service as Oracle's offerings and industry standards evolve. Because of these technical constraints, our effort to remove insensitive terms is ongoing and will take time and external cooperation.

Conventions

The following text conventions are used in this document:

Convention	Meaning
boldface	Boldface type indicates graphical user interface elements associated with an action, or terms defined in text or the glossary.
<i>italic</i>	Italic type indicates book titles, emphasis, or placeholder variables for which user supply particular values.
monospace	Monospace type indicates commands within a paragraph, URLs, code in examples, text that appears on the screen, or text that user enter.

My Oracle Support

My Oracle Support (<https://support.oracle.com>) is your initial point of contact for all product support and training needs.

Use My Oracle Support to access support resources, create and manage Service Requests (SRs), and get assistance with product issues.

For help with My Oracle Support registration, Service Request creation, or other support access questions, use the available support options in My Oracle Support, including MOSFS and MOS Chat.

My Oracle Support is available 24 hours a day, 7 days a week, 365 days a year.

Acronyms

Below table provides information about the acronyms used in the document.

Table Acronyms

Acronym	Definition
AMF	Access and Mobility Management Function
BSF	Oracle Communications Cloud Native core Binding Support Function
CHF	Charging Function
CM	Configuration Management
CUSTOMER_REPO	Docker registry address including the port number, if the docker registry has an associated port.
IMAGE_TAG	Image tag from release tar file. You can use any tag number. However, make sure that you use that specific tag number while pushing docker image to the docker registry.
MCC	Mobile Country code
METALLB_ADDRESS_POOL	Address pool which configured on metallb to provide external IPs .
MNC	Mobile Network code
NRF	Network Repository Function
PCF	Policy Control Function
REST API	Representational State Transfer Application Program Interfaces (REST API)
CNPCRF	Cloud Native Policy and Charging Rules Function
SAN	Subject Alternate Name
SMF	Session Management Function
UDR	Unified Data Repository

What's New in This Guide

This section introduces the documentation updates for release 26.1.2xx.

Release 26.1.201 - G55981-01, August 2026

- Added the following APIs:
 - [Default Processing Profile](#) to describe creating and configuring Default Processing Profile.
- Added [Service Profiles](#) to describe creating and configuring Service Profiles.
- Updated [Session Management Service](#) with the following parameters for Overload configurations:
 - `serviceType`
 - `configureOverLoadRules.serviceProfile`
 - `configureOverLoadRules.apPercentage`
- Updated [Load Shedding Profile](#) to describe configuring additional load levels upto L10 for SM service and Diameter Connector service APIs.
- Updated [OC Discard Policies](#) to describe configuring additional load levels upto L10 for SM service and Diameter Connector service APIs.
- Added the following parameters to PCF Session Management section and also updated description of `overloadConfiguration.enhancedOverloadControlLevel` to describe configuring additional load levels upto L10 for SM service.
 - `defaultProcessing.smdpProfile` to configure default processing for SM service.
 - `qosMonitoring.notificationTarget` to configure notification target for QoS Monitoring.
 - `messagePriority.messagePriorityProfile` to configure message priority profile for SM service.
- Updated the following parameters in PCF Session Management section:
 - `overloadConfiguration.enhancedOverloadControlLevel` to describe configuring additional load levels upto L10 for SM service.
 - `system.overrideSupportedFeatures` to describe the support for QoS Monitoring.
- Updated the description for `remoteSSVRootPath.operatorSpecificData` field and updated the sample request body structure for PUT and PATCH operations in the [PDS Settings](#) section.
- Added `retryAfterSettings.enableRetryAfterIE` to configure RetryAfter settings to **Retry Profiles** section.
- Added the following fields in [Session Management Service](#) for enabling and configuring the Supports `pcfIpEndPoints` in PCF Binding BSF Registration feature:
 - `binding.fqdnIpEndpointsConfiguration`
 - `binding.fqdnIpEndpointsProfile`
- Added the following parameters in the [NF Communication Profiles](#) section to configure the interface-specific NF Peer Info settings:
 - `nfPeerInfoSettings.sendNfPeerInfo`

- `nfPeerInfoSettings.includeSrcServInst`
- Added the `messagePriority.messagePriorityProfile` parameter to Binding Service API.
- Added the `messagePriority.messagePriorityProfile` parameter under CHF and UDR sections in User Service API.
- Updated the following parameters in Message Profiles API:
 - `serviceType`
 - `messageProfileAttributes.messageType`
 - `messageProfileAttributes.messageProfileFilterConditions.attributeName`
- Added the following parameters to [Binding Service](#), which are used to configure query optimization on Binding service database:
 - `optimization.enableIndexMigration`
 - `optimization.enableQueryOptimization`
 - `optimization.preferredSubscriberId`
- Added [Diameter Repaving](#) to describe configuring Diameter Gateway Connection Repaving feature.
- Updated the sample request and response body structure for export operations in the [Policy Data](#) section.
- Removed the following APIs from [Time Period](#), [Media Profile](#), and [Custom Vendor](#) sections:
 - `{apiRoot}/ocpm/ pcrf/v1/configuration/ policy/timePeriod/ {timePeriodName}`
 - `{apiRoot}/ocpm/ pcrf/v1/configuration/ policy/timePeriod`
 - `{apiRoot}/ocpm/pcrf/v1/ configuration/policy/ timePeriod/import`
 - `{apiRoot}/ocpm/pcrf/v1/ configuration/policy/ timePeriod/export`
 - `/ocpm/pcrf/v1/configuration/policy/mediaProfile/{mediaProfileName}`
 - `{apiRoot}/ocpm/pcrf/v1/configuration/policy/mediaProfile`
 - `{apiRoot}/ocpm/pcrf/v1/configuration/policy/mediaProfile/import`
 - `{apiRoot}/ocpm/pcrf/v1/configuration/policy/mediaProfile/export`
 - `{apiRoot}/ocpm/pcrf/v1/configuration/policy/customVendor/ {customVendorName}`
 - `{apiRoot}/ocpm/pcrf/v1/configuration/policy/customVendor`
- Updated the descriptions for the following fields in the [Binding Service](#) section:
 - `enable`
 - `notificationRate`
 - `tTl`
 - `maxTtl`
 - `minAuditAttempts`
 - `frequency`
- Removed Policy Library REST API.

1

Introduction

This document provides information about how to configure the services and manageable objects in Oracle Communications Cloud Native Core Converged Policy using Representational State Transfer Application Program Interfaces (REST API).

1.1 Overview

The Policy solution provides a standard policy design experience and a consistent user experience. This solution supports both 4G and 5G networks. In addition, there is an overlap in PCF and PCRF functionalities, such as need for a policy engine, policy design, Rx, similarity between Sy and Nchf_Spending LimitControl, and so on. Policy utilizes this overlap to build microservices that can be used for providing PCRF and PCF functionalities. Although, it is a unified policy solution, you can deploy PCF and PCRF independently.

Policy is a functional element for policy control decision and flow based charging control functionality. It provides the following functions:

- Policy rules for application and service data flow detection, gating, QoS, and flow based charging to the Session Management Function (SMF)
- Access and Mobility Management related policies to the Access and Mobility Management Function (AMF)
- UE Route Selection Policies (URSP) rules to User Equipment (UE) through AMF
- Access to subscription information relevant for policy decisions in a Unified Data Repository (UDR)
- Network control for service data flow detection, gating, and Quality of Service (QoS)
- Flow based charging towards the Policy and Charging Enforcement Function (PCEF)
- Receiving session and media related information from Application Function (AF) and informing AF of traffic plane events
- Provision of PCC Rules to PCEF through the Gx reference point

The CNC Policy supports the above functions through the following services:

- Session Management Service
- Access and Mobility Service
- Policy Authorization Service
- User Equipment (UE) Policy Service
- PCRF Core Service
- Binding Service
- Policy Data Source Service
- Usage Monitoring Service
- Notifier Service
- NWDAF Agent

Note

The performance and capacity of the Policy system may vary based on the Call model, Feature/Interface configuration, underlying CNE and hardware environment, including but not limited to the complexity of deployed policies, policy table size , object expression and custom json usage in policy design.

For more information about the Policy supported services, see *Oracle Communications Cloud Native Core, Converged Policy User's Guide*.

1.2 References

Refer the following documents for more information about Policy:

- *Oracle Communications Cloud Native Core, Converged Policy User's Guide*
- *Oracle Communications Cloud Native Core, Converged Policy Installation, Upgrade and Fault Recovery Guide*

2

Policy REST Specifications

This chapter provides information about REST specifications used in Oracle Communications Cloud Native Core, Converged Policy (Policy).

Note

action is a query parameter that has been provided for each individual import api, which can either have **replace** or **ignore** value. If the **action** parameter is not provided, then the default value is **ignore**.

2.1 PCF Traffic Profile ADC Rule

Table 2-1 PCF traffic for adc rule APIs

Description	HTTP Method or Custom Operation	Resource URI	Possible Result Code
Get Traffic ADC Rule	GET	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcfsm/adctrfficrules/{trafficAdcRuleName}	See Table A-1
Update Traffic Adc Rule	PUT	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcfsm/adctrfficrules/{trafficAdcRuleName}	See Table A-2
Delete Traffic ADC Rule	DELETE	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcfsm/adctrfficrules/{trafficAdcRuleName}	See Table A-4
Create Traffic ADC Rule	POST	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcfsm/adctrfficrules	See Table A-3

Get and Update Operations

Table 2-2 TrafficAdcRule Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
name	string	M	Name of the Traffic Profile.

Table 2-2 (Cont.) TrafficAdcRule Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
description	string	O	Description of the profile.
param.diameter.adcRule.name	string	M	Uniquely identifies the ADC rule. Used to reference an ADC rule in communication between the CNC Policy and a PCEF within one IP-CAN session. Note: The name and the param.diameter.adcRule.name fields must have the different values. The API exports the correct data if param.diameter.adcRule.name is provided and not the name .
param.diameter.adcRule.maxAuthUL	string	O	Maximum authorized bandwidth in bits per second for uplinks (user equipment to network). Provide a valid numerical value.
param.diameter.adcRule.maxAuthDL	string	O	Maximum authorized bandwidth in bits per second for downlinks (network to user equipment). Provide a valid numerical value.
param.diameter.adcRule.MonitoringKey	string	O	Monitoring key that may apply to the ADC rule.
param.diameter.adcRule.FlowStatus	string: Enum	O	Indicates whether the application traffic is enabled or disabled in either the uplink or downlink direction. Allowed values: • 0: ENABLED_UPLINK • 1: ENABLED_DOWNLINK • 2: ENABLED • 3: DISABLED
param.diameter.adcRule.tdfApplicationIdentifier	string	O	Identifies the traffic that belongs to the application to which the rule applies.

Table 2-2 (Cont.) TrafficAdcRule Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
param.diameter.adcRule. .tdfRedirectSupport	string: Enum	O	Indicates whether the application traffic should be redirected to another controlled address. Allowed values: 0: REDIRECTION_DISABLED 1: REDIRECTION_ENABLED
param.diameter.adcRule. .tdfRedirectAddressType	string : Enum	O	Specifies the format for the redirect address. Allowed values: 0: IPv4 1: IPv6 2: URL 3: SIP_URI
param.diameter.adcRule. .tdfRedirectServerAddress	string	O	The address of the TDF redirect server in the specified address type.
param.diameter.adcRule. .tdfMuteNotification	string : Enum	O	Notification to disable application detection notifications from the TDF device. By default, mute remains disabled. 0: Mute is Disabled. 1: MUTE_REQUIRED
param.diameter.adcRule. .ServiceIdentifier	string : Enum	O	Credit-control service identifier associated with the traffic defined by this rule. Only applicable if online charging is enabled. Provide a valid numerical value.
param.diameter.adcRule. .RatingGroup	string : Enum	O	Credit-control rating group associated with the traffic defined by this profile. Only applicable if online charging is enabled. Provide a valid numerical value.
param.diameter.adcRule. .ReportingLevel	string : Enum	O	Allowed values: 0: SERVICE_IDENTIFIER_LEVEL 1: RATING_GROUP_LEVEL

Table 2-2 (Cont.) TrafficAdcRule Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
param.diameter.adcRule. .Online	string : Enum	O	Specifies whether or not online charging is enabled in this profile. Allowed values: 0: DISABLE_ONLINE 1: ENABLE_ONLINE
param.diameter.adcRule. .Offline	string : Enum	O	Specifies whether or not offline charging is enabled in this profile. Allowed values: 0: DISABLE_OFFLINE 1: ENABLE_OFFLINE
param.diameter.adcRule. .MeteringMethod	string : Enum	O	Defines how service data-flow traffic is metered for offline charging. Allowed values: 0: DURATION 1: VOLUME 2: DURATION_VOLUME 3: EVENT
param.diameter.adcRule. .Precedence	string	O	Precedence value of the profile. The lower the precedence, the higher the priority. Provide a valid numerical value.

A sample of the request or response body:

```
{
  "name": "string",
  "description": "string",
  "param.diameter.adcRule.name": "string",
  "param.diameter.adcRule.maxAuthUL": "4292566642",
  "param.diameter.adcRule.maxAuthDL": "4294206946",
  "param.diameter.adcRule.MonitoringKey": "string",
  "param.diameter.adcRule.FlowStatus": "0",
  "param.diameter.adcRule.tdfApplicationIdentifier": "string",
  "param.diameter.adcRule.tdfRedirectSupport": "0",
  "param.diameter.adcRule.tdfRedirectAddressType": "0",
  "param.diameter.adcRule.tdfRedirectServerAddress": "string",
  "param.diameter.adcRule.tdfMuteNotification": "0",
  "param.diameter.adcRule.ServiceIdentifier": "56562570273140140",
  "param.diameter.adcRule.RatingGroup":
```

```

"834230701429507004586357990032488266149954030625803028841937860169",
  "param.diameter.adcRule.ReportingLevel": "0",
  "param.diameter.adcRule.Online": "0",
  "param.diameter.adcRule.Offline": "0",
  "param.diameter.adcRule.MeteringMethod": "0",
  "param.diameter.adcRule.Precedence":
"982282151896732255224072394658191119482788772631487340307602311123858135"
}

```

Import or Export PCF traffic profile ADC rule APIs

Table 2-3 Import or Export PCF traffic profile ADC rule APIs

API Name	Request Type	Request Url	Possible Result Code
Import Traffic Adc Rule	POST	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcfsm/adcrules/import	See Table A-3
Export Traffic Adc Rule	GET	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcfsm/adcrules/export	See Table A-1

Table 2-4 Request/Response Body Parameters

Field Name	Data Type	Mandatory/Optional/Conditional	Description
topic	String	M	
sourceVersion	String	M	Build version
date	String	M	Date in pattern "yyyy-MM-dd'T'HH:mm:ss'Z'"
exportData		M	
errors			

A sample of the import or export request:

```

{
  "topic": "string",
  "sourceVersion": "string",
  "date": "string",
  "exportData": [
    {
      "name": "string",
      "description": "string",
      "param.diameter.adcRule.name": "string",
      "param.diameter.adcRule.maxAuthUL": "4264534498",
      "param.diameter.adcRule.maxAuthDL": "4293625992",
      "param.diameter.adcRule.MonitoringKey": "string",
      "param.diameter.adcRule.FlowStatus": "0",
      "param.diameter.adcRule.tdfApplicationIdentifier": "string",
      "param.diameter.adcRule.tdfRedirectSupport": "0",
      "param.diameter.adcRule.tdfRedirectAddressType": "0",

```

```

    "param.diameter.adcRule.tdfRedirectServerAddress": "string",
    "param.diameter.adcRule.tdfMuteNotification": "0",
    "param.diameter.adcRule.ServiceIdentifier": "27725208328769",
    "param.diameter.adcRule.RatingGroup": "50423799",
    "param.diameter.adcRule.ReportingLevel": "0",
    "param.diameter.adcRule.Online": "0",
    "param.diameter.adcRule.Offline": "0",
    "param.diameter.adcRule.MeteringMethod": "0",
    "param.diameter.adcRule.Precedence":
    "616801263210908668475153217630024988"
  }
],
"errors": [
  {
    "name": "string",
    "message": "string"
  }
]
}

```

2.2 PCF Predefined ADC Rule

Table 2-5 PCF Predefined ADC Rule APIs

Description	HTTP Method or Custom Operation	Resource URI	Possible Result Code
Get Predefined Adc Rule	GET	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcfsm/predefinedadcrules/{predefinedAdcRuleName}	See Table A-1
Update Predefined Adc Rule	PUT	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcfsm/predefinedadcrules/{predefinedAdcRuleName}	See Table A-2
Delete Predefined Adc Rule	DELETE	/oc-cnpolicy-configuration/v1/policydata/pcfsm/predefinedadcrules/{predefinedAdcRuleName}	See Table A-4
Create Predefined Adc Rule	POST	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcfsm/predefinedadcrules	See Table A-3

Get and Update Operations

Table 2-6 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
name	string	M	Name of the Predefined ADC Rule.
param.diameter.adcPredefRule.description	string	M	Uniquely identifies the Predefined ADC Rule. Used to reference an Predefined ADC Rule in communication between the CNC Policy and a PCEF within one IP-CAN session.
param.diameter.adcPredefRule.name	string	O	Description of the ADC Rule.

A sample of the request or response body:

```
{
  "name": "string",
  "param.diameter.adcPredefRule.description": "string",
  "param.diameter.adcPredefRule.name": "string"
}
```

Import or Export PCF predefined ADC rule APIs

Table 2-7 Import or Export PCF predefined ADC rule APIs

API Name	Request Type	Request Url	Possible Result Code
Import Predefined Adc Rule	POST	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcfsm/predefinedadcrules/import	See Table A-3
Export Predefined Adc Rule	GET	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcfsm/predefinedadcrules/export	See Table A-1

Table 2-8 Request/Response Body Parameters

Field Name	Data Type	Mandatory/Optional/ Conditional	Description
topic	String	M	
sourceVersion	String	M	Build version
date	String	M	Date in pattern "yyyy-MM-dd'T'HH:mm:ss'Z'"

Table 2-8 (Cont.) Request/Response Body Parameters

Field Name	Data Type	Mandatory/Optional/ Conditional	Description
exportData		M	
errors			

A sample of the import or export request:

```

"topic": "string",
"sourceVersion": "string",
"date": "string",
"exportData": [
  {
    "name": "string",
    "param.diameter.adcPredefRule.description": "string",
    "param.diameter.adcPredefRule.name": "string"
  }
],
"errors": [
  {
    "name": "string",
    "message": "string"
  }
]
}

```

2.3 PCF Predefined ADC Rule Base

Table 2-9 PCF predefined adc rule base APIs

Description	HTTP Method or Custom Operation	Resource URI	Possible Result Code
Get Predefined Adc Rule Base	GET	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcfsm/predefinedadcrulebases/{predefinedAdcRuleBaseName}	See Table A-1
Update Predefined Adc Rule Base	PUT	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcfsm/predefinedadcrulebases/{predefinedAdcRuleBaseName}	See Table A-2

Table 2-9 (Cont.) PCF predefined adc rule base APIs

Description	HTTP Method or Custom Operation	Resource URI	Possible Result Code
Delete Predefined Adc Rule Base	DELETE	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcfsm/predefinedadcrules/ s/ {predefinedAdcRuleBaseName}	See Table A-4
Create Predefined Adc Rule Base	POST	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcfsm/predefinedadcrules/ s	See Table A-3

Get and Update Operations**Table 2-10 Request/Response Body Parameters**

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
name	string	M	Name of the Predefined ADC Rule Base.
param.diameter.adcPredefBaseRule.description	string	M	Uniquely identifies the Predefined ADC Rule Base. Used to reference an Predefined ADC Rule Base in communication between the CNC Policy and a PCEF within one IP-CAN session.
param.diameter.adcPredefBaseRule.name	string	O	Description of the Predefined ADC Rule Base.

A sample of the request or response body:

```
{
  "name": "string",
  "param.diameter.adcPredefBaseRule.description": "string",
  "param.diameter.adcPredefBaseRule.name": "string"
}
```

Import or Export PCF predefined ADC rule APIs

Table 2-11 Import or Export PCF predefined ADC rule APIs

API Name	Request Type	Request Url	Possible Result Code
Import Predefined Adc Rule Base	POST	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcfsm/predefinedadcrulebases/import	See Table A-3
Export Predefined Adc Rule Base	GET	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcfsm/predefinedadcrulebases/export	See Table A-1

Table 2-12 Request/Response Body Parameters

Field Name	Data Type	Mandatory/Optional/Conditional	Description
topic	String	M	
sourceVersion	String	M	Build version
date	String	M	Date in pattern "yyyy-MM-dd'T'HH:mm:ss'Z"
exportData		M	
errors			

A sample of the import or export request:

```
{
  "topic": "string",
  "sourceVersion": "string",
  "date": "string",
  "exportData": [
    {
      "name": "string",
      "param.diameter.adcPredefBaseRule.description": "string",
      "param.diameter.adcPredefBaseRule.name": "string"
    }
  ],
  "errors": [
    {
      "name": "string",
      "message": "string"
    }
  ]
}
```

2.4 Mated Region

Table 2-13 Policy Mated Region APIs

API Name	HTTP Method or Custom Operation	Resource URI	Possible Result Code
Get Mated Region	GET	{apiRoot}/oc-cnpolicy-configuration/v1/general/matedRegion/{matedRegionName}	See Table A-1
Update Mated Region	PUT	{apiRoot}/oc-cnpolicy-configuration/v1/general/matedRegion/{matedRegionName}	See Table A-2
Delete Mated Region	DELETE	{apiRoot}/oc-cnpolicy-configuration/v1/general/matedRegion/{matedRegionName}	See Table A-4
Create Mated Region	POST	{apiRoot}/oc-cnpolicy-configuration/v1/general/matedRegion	See Table A-3

Get and Update Operations

Table 2-14 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/Optional(O)/Conditional(C)	Description
name	string	M	The unique name for the site. This name is used to refer to the site in Site Fallback configuration as explained in Site Fallback . The name can only contain the characters A–Z, a–z, 0–9, period (.), hyphen (-), and underline (_). The maximum length is 255 characters.
siteId	string	O	The UUID of the site.

A sample of the request or response body:

```
{
  "name": "string",
  "siteId": "string"
}
```


Import or Export Mated Region APIs

Table 2-15 Import or Export Mated Region APIs

API Name	Request Type	Request Url	Possible Result Code
Import Mated Region	POST	{apiRoot}/oc-cnpolicy-configuration/v1/general/matedRegion/import	See Table A-3
Export Mated Region	GET	{apiRoot}/oc-cnpolicy-configuration/v1/general/matedRegion/export	See Table A-1

Table 2-16 Request/Response Body Parameters

Field Name	Data Type	Mandatory/Optional/Conditional	Description
topic	String	M	
sourceVersion	String	M	Build version
date	String	M	Date in pattern "yyyy-MM-dd'T'HH:mm:ss'Z"
exportData		M	
errors			

A sample of the import or export request:

```
{
  "topic": "string",
  "sourceVersion": "string",
  "date": "string",
  "exportData": [
    {
      "name": "string",
      "siteId": "string"
    }
  ],
  "errors": [
    {
      "name": "string",
      "message": "string"
    }
  ]
}
```

2.5 Site Fallback

Table 2-17 Policy Site Fallback APIs

API Name	HTTP Method or Custom Operation	Resource URI	Possible Result Code
Get Site Fallback	GET	{apiRoot}/oc-cnpolicy-configuration/v1/general/siteFallback/{siteFallbackName}	See Table A-1
Update Site Fallback	PUT	{apiRoot}/oc-cnpolicy-configuration/v1/general/siteFallback/{siteFallbackName}	See Table A-2
Delete Site Fallback	DELETE	{apiRoot}/oc-cnpolicy-configuration/v1/general/siteFallback/{siteFallbackName}	See Table A-4
Create Site Fallback	POST	{apiRoot}/oc-cnpolicy-configuration/v1/general/siteFallback	See Table A-3

Get and Update Operations

Table 2-18 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/Optional(O)/Conditional(C)	Description
name	string	O	Name of the site for which the fallback sites must be configured. The fallback site can be selected from the drop-down list of sites that are created on Policy Mated Region page. The name can only contain the characters A–Z, a–z, 0–9, period (.), hyphen (-), and underline (_). The maximum length is 255 characters.
fallbackList	FallbackList	O	Click Add to configure Fallback List , this opens the Add Site Fallback List pop-up window. In the Add Site Fallback List window configure the following fields:

Table 2-19 FallbackList

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
fallbackSiteName	string	O	The drop down list of fallback site names. This list is populated from Policy Mated Region Configurations. Select the sites that must be considered for fallback. Timer adoption for Audit service is considered based on the configured fallback priority.
preferenceOrder	integer	O	The preference order of the selected sites. Site with highest priority is considered for timer adoption. If the site with higher priority is unavailable, site with next priority takes over the timer adoption.

A sample of the request or response body:

```
{
  "name": "string",
  "fallbackList": [
    {
      "fallbackSiteName": "string",
      "preferenceOrder": 0
    }
  ]
}
```

Import or Export Site Fallback APIs

Table 2-20 Import or Export Site Fallback APIs

API Name	Request Type	Request Url	Possible Result Code
Import Site Fallback	POST	{apiRoot}/oc-cnpolicy-configuration/v1/general/siteFallback/import	See Table A-3
Export Site Fallback	GET	{apiRoot}/oc-cnpolicy-configuration/v1/general/siteFallback/export	See Table A-1

Table 2-21 Request/Response Body Parameters

Field Name	Data Type	Mandatory/Optional/Conditional	Description
topic	String	M	
sourceVersion	String	M	Build version
date	String	M	Date in pattern "yyyy-MM-dd'T'HH:mm:ss'Z'"
exportData		M	
errors			

A sample of the import or export request:

```
{
  "topic": "string",
  "sourceVersion": "string",
  "date": "string",
  "exportData": [
    {
      "name": "string",
      "fallbackList": [
        {
          "fallbackSiteName": "string",
          "preferenceOrder": 0
        }
      ]
    }
  ],
  "errors": [
    {
      "name": "string",
      "message": "string"
    }
  ]
}
```

2.6 Timer Service

Table 2-22 Policy Timer Service APIs

API Name	HTTP Method or Custom Operation	Resource URI	Possible Result Code
Get Individual Timer Service Configuration	GET	{apiRoot}/oc-cnpolicy-configuration/v1/services/timerService	See Table A-1
Update Timer Service Configuration.	PUT	{apiRoot}/oc-cnpolicy-configuration/v1/services/timerService	See Table A-2

Get and Update Operations

Table 2-23 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
timerEnabled	boolean	O	Enable or Disable the timer service.
advancedSettings	AdvancedSettings	O	To add additional advanced settings keys to the settings.

Table 2-24 AdvancedSettings

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
key	string	O	Specifies the key name.
value	string	O	Specifies the value of the key.

Sample body request for Put operation for timer service:

```
{
  "timerEnabled": true,
  "advancedSettings": [
    {
      "key": "string",
      "value": "string"
    }
  ]
}
```

Table 2-25 Import/Export Timer Service

API Name	Request Type	Request Url	Possible Result Code
Export Timer Service Configuration	GET	{apiRoot}/oc-cnpolicy-configuration/v1/services/timerService/export	See Table A-1
Import Timer Service Configuration	POST	{apiRoot}/oc-cnpolicy-configuration/v1/services/timerService/import	See Table A-3

Table 2-26 Request/Response Body Parameters

Field Name	Data Type	Mandatory/Optional/Conditional	Description
topic	String	M	
sourceVersion	String	M	Build version
date	String	M	Date in pattern "yyyy-MM-dd'T'HH:mm:ss'Z"
exportData		M	

Sample Request Body structure for Import and Export operations:

```
{
  "topic": "string",
  "sourceVersion": "string",
  "date": "string",
  "exportData": {
    "timerEnabled": true,
    "advancedSettings": [
      {
        "key": "string",
        "value": "string"
      }
    ]
  }
}
```

2.7 Bulwark Congestion Migration

Bulwark Service Congestion Control Data Migration

Table 2-27 Bulwark Congestion Migration APIs

API Description	HTTP Method or Custom Operation	Resource URI	Description	Possible Result Code
Get Bulwark Congestion Migration Details	GET	{apiRoot}/oc-cnpolicy-configuration/v1/congestioncontrol/bulwark/migration	To get the status of data migration details when the systems is upgraded from the older version to current version.	See Table A-1

Table 2-27 (Cont.) Bulwark Congestion Migration APIs

API Description	HTTP Method or Custom Operation	Resource URI	Description	Possible Result Code
Migrate bulwark congestion control previous version configuration data to current version	POST	{apiRoot}/oc-cnpolicy-configuration/v1/congestioncontrol/bulwark/migration	Migrate congestion control previous version configuration data to current version by taking some required inputs from the user and this migration is the one-time activity after version upgrade from old version to current version.	See Table A-3

Table 2-28 Request/Response Congestion Migration Data

Field Name	Data Type	Mandatory(M)/Optional(O)/Conditional(C)	Description
enabled	boolean	M	This enables the congestion control feature after successful migration.
activeThresholdProfile	string	M	The name of the active threshold profile.
thresholdProfiles	CongestionThresholdsProfile	M	This new thresholds profile will be created with this profile data.
activeLoadSheddingProfile	string	M	The active load shedding rule.
loadSheddingRules	CongestionControlLoadShedding	M	This load shedding profile will configure as default profile for congestion load shedding rules.

Table 2-29 Request/Response CongestionThresholdsProfile

Field Name	Field Type	Mandatory(M)/Optional(O)/Conditional(C)	Description
name	string	M	A new thresholds profile will be created with this profile name to migrate the old version thresholds data.

Table 2-29 (Cont.) Request/Response CongestionThresholdsProfile

Field Name	Field Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
value	CongestionThresholdData	M	This queue data will be applied for different congestion states to migrate the old version threshold data.
isCustomProfile	boolean	M	This CPU data will be applied for congestion states to migrate the old version thresholds data.

Table 2-30 Request/Response CongestionControlLoadShedding

Field Name	Field Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
name	string	M	The provided load shedding profile will become the default profile for congestion load shedding rules. Value: Provide previous version profile name.
value	CongestionLoadSheddingState	M	This Respective Discard Priority data will be applied for congestion states to migrate the old version thresholds data.
isCustomProfile	boolean	M	Is this custom profile.

Table 2-31 Request/Response CongestionThresholdState

Field Name	Field Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
state	string	M	The congestion state: DANGER_OF_CONGESTION, CONGESTION_L1, CONGESTION_L2, CONGESTED.
resourceUsageLimit	CongestionResourceUsageLimit	M	The congestion state resource values.

Table 2-32 Request/Response CongestionResourceUsageLimit

Field Name	Field Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
cpu	integer	M	The congestion resource threshold limit for CPU. This value can be in the range of 1 - 100.
queue	integer	M	The congestion resource threshold limit for Queue. This value can be in the range of 1 - 40.

Table 2-33 Request/Response CongestionLoadSheddingState

Field Name	Field Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
state	string	M	
discardPriority	integer	M	
discardPriorityPercentage	DiscardPriorityPercentage	O	

Table 2-34 Request/Response DiscardPriorityPercentage

Field Name	Field Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
range	string	M	
percentage	integer	M	

Sample for GET Congestion migration details:

```
{
  "migrated": true,
  "attempts": 0,
  "cause": "string"
}
```

Sample for add (POST) migration details from previous version configuration data to current version:

```
{
  "enabled": true,
  "activeThresholdProfile": "string",
  "thresholdProfiles": [
    {
      "name": "profileName",
      "value": [
```

```

        {
          "state": "CONGESTED",
          "resourceUsageLimit": {
            "cpu": 45,
            "queue": 40
          }
        }
      ],
      "isCustomProfile": true
    }
  ],
  "activeLoadSheddingProfile": "string",
  "loadSheddingRules": [
    {
      "name": "ruleName",
      "value": [
        {
          "state": "CONGESTED",
          "discardPriority": 5,
          "discardPriorityPercentage": [
            {
              "range": "1 or 11-13",
              "percentage": 23
            }
          ]
        }
      ]
    }
  ],
  "isCustomProfile": true
}
]
}

```

Note

- When Policy is upgraded from previous versions to 25.1.200 and before Bulwark Congestion Migration, if user used the Congestion Active Threshold GET/PUT API's then the system will respond 404 with below API response as these API's are not supported before Bulwark Congestion Migration and once system completed the Bulwark Congestion Migration then these above said API are accessible

API:

```
{apiRoot}/oc-cnpolicy-configuration/v1/
congestionActiveThresholdProfile/{serviceName}
```

API Response:

PUT:

```
{
  "title": "UNABLE TO UPDATE CONGESTION ACTIVE THRESHOLD PROFILE",
  "status": 400,
  "detail": "Updating active threshold profile is not supported for
Bulwark using this API. Use congestion configurations API",
  "cause": "Updating active threshold profile is not supported for
Bulwark using this API. Use congestion configurations API"
}
```

GET:

```
{
  "title": "UNABLE TO GET CONGESTION ACTIVE THRESHOLD PROFILE",
  "status": 400,
  "detail": "Getting active threshold profile is not supported for
Bulwark using this API. Use congestion configurations API",
  "cause": "Getting active threshold profile is not supported for
Bulwark using this API. Use congestion configurations API"
}
```

- When Policy 25.1.200 or any of the later versions is fresh installed or when Policy is upgraded from any of the previous versions to Policy 25.1.200 or later versions and after the Bulwark congestion migration is completed, then the Update Congestion Control Configurations REST API does not accept the configuration of activeThresholdProfile parameter in the request body and if user uses this activeThresholdProfile parameter then system will respond 404 with below API response as this API is not supported the activeThresholdProfile parameter before Bulwark congestion migration

API:

```
{apiRoot}/oc-cnpolicy-configuration/v1/congestionConfigurations/
{serviceName}
```

API Response:

PUT:

```
{
  "title": "UNABLE TO UPDATE CONGESTION CONFIGURATIONS",
  "status": 400,
  "detail": "Use activeThresholdProfile API for setting active
threshold Profile for bulwark",
  "cause": "Use activeThresholdProfile API for setting active
threshold Profile for bulwark"
}
```

So, to update the activeThresholdProfile parameter, user needs to use the below Update Congestion Active Threshold API:

API:

```
{apiRoot}/oc-cnpolicy-configuration/v1/
congestionActiveThresholdProfile/{serviceName}/
{activeThresholdProfile}
```

- When Policy 25.1.200 or any of the later versions is fresh installed or when Policy is upgraded from any of the previous versions to Policy 25.1.200 or later versions, after the Bulwark congestion migration is completed, the updated Congestion Control REST API does not accept the configuration of activeThresholdProfile parameter in the request body. This is inline with all services congestion control behaviour.

Sample REST API:

```
Method: PUT
URL: ../oc-cnpolicy-configuration/v1/congestionConfigurations/
bulwark
Header:
  Content-Type: application/json
  Accept: application/json
Body:
{
  "enable": true,
  "stateChangeSampleCount": 5,
  "stateCalculationInterval": 5000
}
```

- When Policy is upgraded from any of the previous versions to 25.1.200 or later versions, before the Bulwark congestion migration completed, the updated Congestion Control REST API accepts the activeThresholdProfile parameter in the Request Body as this is old Bulwark congestion behaviour and is not inline with all services congestion control behaviour.

Sample REST API:

```
Method: PUT
URL: ../oc-cnpolicy-configuration/v1/congestionConfigurations/
bulwark
Header:
```

```

Content-Type: application/json
Accept: application/json
Body:
{
  "activeThresholdProfile":"DEFAULT",
  "enable":true,
  "stateChangeSampleCount":5,
  "stateCalculationInterval":5000
}

```

2.8 Diameter Gateway Congestion Migration

Table 2-35 Diameter Gateway Congestion Migration APIs

API Name	HTTP Method or Custom Operation	Resource URI	Description	Possible Result Code
Get Diameter-Gateway Congestion Migration Details	GET	{apiRoot}/oc-cnpolicy-configuration/v1/congestioncontrol/diameter-gateway/migration	To get the status of data migration details when the systems is upgraded from the older version to current version.	See Table A-1
Migrate congestion control previous version configuration data to current version	POST	{apiRoot}/oc-cnpolicy-configuration/v1/congestioncontrol/diameter-gateway/migration	Migrate congestion control previous version configuration data to current version by taking some required inputs from the user and this migration is the one-time activity after version upgrade from old version to current version.	See Table A-3

Table 2-36 Request/Response Congestion Migration Data

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
enable	boolean	M	This enables the congestion control feature after successful migration.
thresholdsProfileData	ThresholdsProfileData	M	This new thresholds profile will be created with this profile data.

Table 2-36 (Cont.) Request/Response Congestion Migration Data

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
loadSheddingProfileData	LoadSheddingProfileData	M	This load shedding profile will configure as default profile for congestion load shedding rules.
messagePriorityProfileData	MessagePriorityProfileData	M	This message priority profile will configure as default profile for message priority profile, and this will be the common profile for both overload and congestion control feature.

Table 2-37 Request/Response ThresholdsProfileData

Field Name	Field Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
profileName	string	M	A new thresholds profile will be created with this profile name to migrate the old version thresholds data.
queueData	CongestionStateData	M	This queue data will be applied for different congestion states to migrate the old version threshold data.
cpuData	CongestionStateData	M	This CPU data will be applied for congestion states to migrate the old version thresholds data.

Table 2-38 Request/Response LoadSheddingProfileData

Field Name	Field Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
profileName	string	M	The provided load shedding profile will become the default profile for congestion load shedding rules. Value: Provide previous version profile name.

Table 2-38 (Cont.) Request/Response LoadSheddingProfileData

Field Name	Field Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
ruleDiscardPriorityData	CongestionStateData	M	This Respective Discard Priority data will be applied for congestion states to migrate the old version thresholds data.
loadSheddingResponseCodeData	LoadSheddingResponseCodeData	M	This congestion response result code will configure as common response code for all congestion discards in advance settings configurations.
ruleDiscardPriorityPercentageData	CongestionStatePriorityPercentageData	M	This is to decide the result code is the general result code or experimental result code, so if this value is greater than then the congestionResponseResultCode is consider as experimental result code.

Table 2-39 Request/Response CongestionStateData

Field Name	Field Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
queueData.state	string	M	Specify different congestion states. The allowed values are: • DANGER_OF_CONGESTION • CONGESTION_L1 • CONGESTION_L1 • CONGESTED
queueData.value	integer	M	Provide a numerical value in the range of 1-2147483647.
cpuData.state	string	M	Specify different congestion states. The allowed values are: • CONGESTION_L1 • CONGESTION_L1
cpuData.value	integer	M	Provide a numerical value in the range of 1-100.

Table 2-39 (Cont.) Request/Response CongestionStateData

Field Name	Field Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
ruleDiscardPriorityData. state	string	M	Specify different congestion states. The allowed values are: • CONGESTION_L1 • CONGESTION_L1
ruleDiscardPriorityData. value	integer	M	Provide a numerical value in the range of 1-31.

Table 2-40 Request/Response CongestionStatePriorityPercentageData

Field Name	Field Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
state	string	M	
discardPriorityPercentageData	DiscardPriorityPercentage	M	

Table 2-41 Request/Response DiscardPriorityPercentage

Field Name	Field Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
range	string	M	
percentage	integer	M	

Table 2-42 Request/Response LoadSheddingResponseCodeData

Field Name	Field Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
congestionResponseResultCode	integer	M	Provide a numerical value in the range of 1001-5999.
congestionResponseVendorId	integer	O	Provide a numerical value in the range of 0-4294967295

Table 2-43 Request/Response MessagePriorityProfileData

Field Name	Field Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
profileName	string	M	This message priority profile will configure as default profile for message priority profile, and this will be the common profile for both overload and congestion control feature Value: Provide previous version profile name.

Sample for GET Congestion migration details:

```
{
  "migrated": true,
  "attempts": 0,
  "cause": "string"
}
```

Sample for add (POST) migration details from previous version configuration data to current version:

```
{
  "enable": true,
  "thresholdsProfileData": {
    "profileName": "string",
    "queueData": [
      {
        "state": "string",
        "value": 0
      }
    ],
    "cpuData": [
      {
        "state": "string",
        "value": 0
      }
    ]
  },
  "loadSheddingProfileData": {
    "profileName": "string",
    "ruleDiscardPriorityData": [
      {
        "state": "string",
        "value": 0
      }
    ]
  },
}
```

```
"ruleDiscardPriorityPercentageData": [
  {
    "state": "string",
    "discardPriorityPercentagesData": [
      {
        "range": "1 or 11-13",
        "percentage": 23
      }
    ]
  }
],
"loadSheddingResponseCodeData": {
  "congestionResponseResultCode": 0,
  "congestionResponseVendorId": 0
},
"messagePriorityProfileData": {
  "profileName": "string"
}
}
```

2.9 Congestion Control

Note

The default Congestion Control Threshold profile cannot be updated by the User.

The Pod Congestion Control PCF services, resource URI parameter {serviceName} values can be:

- bulwark
- binding
- usage-mon
- policy-ds
- pcf-sm
- pcrf-core
- pcf-ue
- oc-diam-gateway
- diam-connector
- udr-connector
- chf-connector
- pcf-am
- notifier

Table 2-44 Congestion Control Configurations

API Description	HTTP Method or Custom Operation	Resource URI	Description	Possible Result Code
Get congestion control configurations.	GET	{apiRoot}/oc-cnpolicy-configuration/v1/congestionConfigurations/{serviceName}	To get enable, stateChangeSampleCount and stateCalculationInterval	See Table A-1
Update congestion control configurations.	PUT	{apiRoot}/oc-cnpolicy-configuration/v1/congestionConfigurations/{serviceName}	To update enable, stateChangeSampleCount and stateCalculationInterval	See Table A-2

Get and Update Operations

Table 2-45 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/Optional(O)/Conditional(C)	Description
enable	boolean	M	Enable or Disable the Pod Congestion Control feature.
stateChangeSampleCount	integer	M	After how many continuous intervals, state can be changed. The count can range from 1 to 2147483647. Default value: 5
stateCalculationInterval	integer	M	Number of interval in milliseconds, after which the pod congestion state will be re-verified. Default value: 200ms
advancedSettings	AdvancedSettings	O	To add additional advanced settings keys to the settings.

Table 2-46 AdvancedSettings

Field Name	Data Type	Mandatory(M)/Optional(O)/Conditional(C)	Description
key	string	O	Specifies the key name.
value	string	O	Specifies the value of the key.

Sample body request for PUT operation for Congestion Control Settings:

```
{
  "stateChangeSampleCount": 5,
  "stateCalculationInterval": 200,
  "enable": true,
  "advancedSettings": [
    {
      "key": "string",
      "value": "string"
    }
  ]
}
```

Table 2-47 Congestion Control Threshold Profile

API Description	HTTP Method or Custom Operation	Resource URI	Description	Possible Result Code
Update congestion control active threshold profile	PUT	{apiRoot}/oc-cnpolicy-configuration/v1/congestionActiveThresholdProfile/{serviceName}/	To update the active threshold profile.	See Table A-2
Get congestion control active threshold profile	GET	{apiRoot}/oc-cnpolicy-configuration/v1/congestionActiveThresholdProfile/{serviceName}	To get the active threshold profile.	See Table A-1
Update congestion control threshold profile.	PUT	{apiRoot}/oc-cnpolicy-configuration/v1/congestionThresholdProfiles/{serviceName}/{profileName}	To update the CPU and Queue threshold of DANGER_OF_CONGESTION, CONGESTION_L1, CONGESTION_L2 and CONGESTED states of specific threshold profile.	See Table A-2
Get Congestion Control Threshold Profiles	GET	{apiRoot}/oc-cnpolicy-configuration/v1/congestionThresholdProfiles/{serviceName}	Get the configured threshold profile for the selected policy service.	See Table A-1
Add congestion control threshold profile.	POST	{apiRoot}/oc-cnpolicy-configuration/v1/congestionThresholdProfiles/{serviceName}/{profileName}	To add new congestion threshold profile with specified name	See Table A-3

Table 2-47 (Cont.) Congestion Control Threshold Profile

API Description	HTTP Method or Custom Operation	Resource URI	Description	Possible Result Code
Delete congestion control threshold profile.	DELETE	{apiRoot}/oc-cnpolicy-configuration/v1/congestionThresholdProfiles/{serviceName}/{profileName}	To delete new congestion threshold profile with specified name	See Table A-4

GET, PUT, and POST Operations

Table 2-48 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/Optional(O)/Conditional(C)	Description
name	String	M	This value should be same as the profileName in path variable.
value	CongestionThresholdState	M	Provide the congestion state.
isCustomProfile	Boolean	M	Denotes that this profile is custom created. Note: Currently user can create custom profiles only. Hence this value should be set to true.

Table 2-49 CongestionThresholdState

Field Name	Data Type	Mandatory(M)/Optional(O)/Conditional(C)	Description
state	String	M	The value can be following pod Congestion states: • DANGER_OF_CONGESTION • CONGESTION_L1 • CONGESTION_L2 • CONGESTED Bulwark service supports only two states DANGER_OF_CONGESTION and CONGESTED.
resourceUsageLimit	CongestionResourceUsageLimit	M	The Threshold profiles resource usage limits for CPU & Queue.

Table 2-50 CongestionResourceUsageLimit

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
cpu	integer	M	Specifies the Queue percentage for Bulwark and Queue (pending requests) for all other Policy services across all the congestion levels. For Bulwark the range is 1 to 100 and for other services the range is between 1 to 2147483647.
queue	integer	M	Specifies the CPU percentage across all the congestion levels. The number can be between 1 to 100.

Sample body request for PUT and POST operations for Bulwark Service:

```
{
  "name": "profileName",
  "isCustomProfile": true,
  "value": [
    {
      "state": "DANGER_OF_CONGESTION",
      "resourceUsageLimit": {
        "cpu": 80,
        "queue": 75
      }
    },
    {
      "state": "CONGESTED",
      "resourceUsageLimit": {
        "cpu": 90,
        "queue": 85
      }
    }
  ]
}
```

Sample body request for PUT and POST operations for Congestion Threshold Profiles:

```
{
  "name": "profileName",
  "isCustomProfile": true,
  "value": [
    {
      "state": "DANGER_OF_CONGESTION",
      "resourceUsageLimit": {
```

```

        "cpu": 70,
        "queue": 30
    },
    {
        "state": "CONGESTION_L1",
        "resourceUsageLimit": {
            "cpu": 75,
            "queue": 36
        }
    },
    {
        "state": "CONGESTION_L2",
        "resourceUsageLimit": {
            "cpu": 80,
            "queue": 42
        }
    },
    {
        "state": "CONGESTED",
        "resourceUsageLimit": {
            "cpu": 85,
            "queue": 48
        }
    }
  ]
}
```

Table 2-51 Import/Export Congestion Control Settings

API Name	Request Url	Request Type	Description
Export Congestion Control Settings	{apiRoot}/oc-cnpolicy-configuration/v1/congestionConfigurations/export	GET	To export congestion control settings
Import Congestion Control Settings	{apiRoot}/oc-cnpolicy-configuration/v1/congestionConfigurations/import?action={action}	POST	To import congestion control settings

Table 2-52 Request/Response Body Parameters

Field Name	Data Type	Mandatory/Optional/Conditional	Description
topic	String	M	It should be commonconfig.congestionControlSettings
sourceVersion	String	M	Build version
date	String	M	Date in pattern "yyyy-MM-dd'T'HH:mm:ss'Z"

Table 2-52 (Cont.) Request/Response Body Parameters

Field Name	Data Type	Mandatory/Optional/Conditional	Description
exportData	Congestion Control Settings Data	M	Array for Congestion Control Settings. This array contains JSON objects for each service that supports congestion control feature.

```
{
  "topic": "commonconfig.congestionControlSettings",
  "sourceVersion": "24.3.0-beta.5",
  "date": "2024-08-29T07:15:09Z",
  "exportData": [
    {
      "serviceName": "binding",
      "stateChangeSampleCount": 5,
      "stateCalculationInterval": 200,
      "enable": false
    },
    {
      "serviceName": "diameter-gateway",
      "stateChangeSampleCount": 10,
      "stateCalculationInterval": 1000,
      "enable": true
    },
    {
      "serviceName": "pcf-sm",
      "stateChangeSampleCount": 2,
      "stateCalculationInterval": 5000,
      "enable": false
    },
    {
      "serviceName": "usage-mon",
      "stateChangeSampleCount": 5,
      "stateCalculationInterval": 200,
      "enable": false
    },
    {
      "serviceName": "pcrf-core",
      "stateChangeSampleCount": 5,
      "stateCalculationInterval": 200,
      "enable": true
    },
    {
      "serviceName": "policy-ds",
      "stateChangeSampleCount": 5,
      "stateCalculationInterval": 200,
      "enable": false
    }
  ]
}
```



```

        "serviceName": "pcf-ue",
        "stateChangeSampleCount": 5,
        "stateCalculationInterval": 200,
        "enable": false
    },
    {
        "serviceName": "udr-connector",
        "stateChangeSampleCount": 2,
        "stateCalculationInterval": 5000,
        "enable": true
    },
    {
        "serviceName": "chf-connector",
        "stateChangeSampleCount": 2,
        "stateCalculationInterval": 5000,
        "enable": true
    },
    {
        "serviceName": "bulwark",
        "stateChangeSampleCount": 2,
        "stateCalculationInterval": 5000,
        "enable": true
    }
  ]
}

```

Table 2-53 Import/Export Congestion Control Threshold Profiles

API Name	Request Url	Request Type	Description
Export Congestion Control Threshold Profiles	{apiRoot}/oc-cnpolicy-configuration/v1/congestionThresholdProfiles/export	GET	To export congestion control threshold profiles
Import Congestion Control Threshold Profiles	{apiRoot}/oc-cnpolicy-configuration/v1/congestionThresholdProfiles/import?action={action}	POST	To import congestion control threshold profiles

Table 2-54 Request/Response Body Parameters

Field Name	Data Type	Mandatory/Optional/Conditional	Description
topic	String	M	It should be commonconfig.congestionThresholdProfiles
sourceVersion	String	M	Build version
date	String	M	Date in pattern "yyyy-MM-dd'T'HH:mm:ss'Z"

Table 2-54 (Cont.) Request/Response Body Parameters

Field Name	Data Type	Mandatory/Optional/Conditional	Description
exportData	Congestion Threshold Profiles Data	M	Array for Congestion Control Threshold Profiles. This array contains JSON objects of each service that supports congestion control feature.

```

{
  "topic": "commonconfig.congestionThresholdProfiles",
  "sourceVersion": "24.3.0-beta.5",
  "date": "2024-08-29T07:17:37Z",
  "exportData": [
    {
      "congestionThresholdProfiles": [
        {
          "name": "DEFAULT",
          "value": [
            {
              "state": "DANGER_OF_CONGESTION",
              "resourceUsageLimit": {
                "cpu": 70,
                "queue": 120
              }
            },
            {
              "state": "CONGESTION_L1",
              "resourceUsageLimit": {
                "cpu": 75,
                "queue": 150
              }
            },
            {
              "state": "CONGESTION_L2",
              "resourceUsageLimit": {
                "cpu": 80,
                "queue": 180
              }
            },
            {
              "state": "CONGESTED",
              "resourceUsageLimit": {
                "cpu": 85,
                "queue": 200
              }
            }
          ],
          "isCustomProfile": false
        }
      ]
    }
  ]
}

```

```

    ],
    "serviceName": "binding"
  },
  {
    "activeThresholdProfile": "DEFAULT",
    "congestionThresholdProfiles": [
      {
        "name": "DEFAULT",
        "value": [
          {
            "state": "DANGER_OF_CONGESTION",
            "resourceUsageLimit": {
              "cpu": 60,
              "queue": 20
            }
          },
          {
            "state": "CONGESTION_L1",
            "resourceUsageLimit": {
              "cpu": 70,
              "queue": 30
            }
          },
          {
            "state": "CONGESTION_L2",
            "resourceUsageLimit": {
              "cpu": 75,
              "queue": 40
            }
          },
          {
            "state": "CONGESTED",
            "resourceUsageLimit": {
              "cpu": 80,
              "queue": 50
            }
          }
        ]
      },
      {
        "isCustomProfile": false
      }
    ]
  },
  {
    "serviceName": "diameter-gateway"
  },
  {
    "congestionThresholdProfiles": [
      {
        "name": "DEFAULT",
        "value": [
          {
            "state": "DANGER_OF_CONGESTION",
            "resourceUsageLimit": {
              "cpu": 77,
              "queue": 140
            }
          }
        ]
      },
      {

```

```

        "state": "CONGESTION_L1",
        "resourceUsageLimit": {
            "cpu": 78,
            "queue": 160
        }
    },
    {
        "state": "CONGESTION_L2",
        "resourceUsageLimit": {
            "cpu": 79,
            "queue": 180
        }
    },
    {
        "state": "CONGESTED",
        "resourceUsageLimit": {
            "cpu": 80,
            "queue": 200
        }
    }
],
"isCustomProfile": false
}
],
"serviceName": "pcf-sm"
},
{
    "congestionThresholdProfiles": [
        {
            "name": "DEFAULT",
            "value": [
                {
                    "state": "DANGER_OF_CONGESTION",
                    "resourceUsageLimit": {
                        "cpu": 70,
                        "queue": 80
                    }
                },
                {
                    "state": "CONGESTION_L1",
                    "resourceUsageLimit": {
                        "cpu": 75,
                        "queue": 100
                    }
                },
                {
                    "state": "CONGESTION_L2",
                    "resourceUsageLimit": {
                        "cpu": 80,
                        "queue": 120
                    }
                },
                {
                    "state": "CONGESTED",
                    "resourceUsageLimit": {
                        "cpu": 85,

```

```

        "queue": 140
      }
    },
    "isCustomProfile": false
  },
  "serviceName": "usage-mon"
},
{
  "congestionThresholdProfiles": [
    {
      "name": "DEFAULT",
      "value": [
        {
          "state": "DANGER_OF_CONGESTION",
          "resourceUsageLimit": {
            "cpu": 60,
            "queue": 250
          }
        },
        {
          "state": "CONGESTION_L1",
          "resourceUsageLimit": {
            "cpu": 65,
            "queue": 300
          }
        },
        {
          "state": "CONGESTION_L2",
          "resourceUsageLimit": {
            "cpu": 75,
            "queue": 350
          }
        },
        {
          "state": "CONGESTED",
          "resourceUsageLimit": {
            "cpu": 85,
            "queue": 400
          }
        }
      ],
      "isCustomProfile": false
    },
    {
      "name": "p1",
      "value": [
        {
          "state": "DANGER_OF_CONGESTION",
          "resourceUsageLimit": {
            "cpu": 96,
            "queue": 50
          }
        }
      ],
      "isCustomProfile": false
    }
  ]
}

```

```

        "state": "CONGESTION_L1",
        "resourceUsageLimit": {
            "cpu": 97,
            "queue": 100
        }
    },
    {
        "state": "CONGESTION_L2",
        "resourceUsageLimit": {
            "cpu": 98,
            "queue": 150
        }
    },
    {
        "state": "CONGESTED",
        "resourceUsageLimit": {
            "cpu": 99,
            "queue": 200
        }
    }
],
"isCustomProfile": true
}
],
"serviceName": "pcrf-core"
},
{
    "congestionThresholdProfiles": [
        {
            "name": "DEFAULT",
            "value": [
                {
                    "state": "DANGER_OF_CONGESTION",
                    "resourceUsageLimit": {
                        "cpu": 65,
                        "queue": 50
                    }
                },
                {
                    "state": "CONGESTION_L1",
                    "resourceUsageLimit": {
                        "cpu": 70,
                        "queue": 100
                    }
                },
                {
                    "state": "CONGESTION_L2",
                    "resourceUsageLimit": {
                        "cpu": 75,
                        "queue": 150
                    }
                },
                {
                    "state": "CONGESTED",
                    "resourceUsageLimit": {
                        "cpu": 80,

```

```

        "queue": 200
      }
    },
    "isCustomProfile": false
  },
  "serviceName": "policy-ds"
},
{
  "congestionThresholdProfiles": [
    {
      "name": "DEFAULT",
      "value": [
        {
          "state": "DANGER_OF_CONGESTION",
          "resourceUsageLimit": {
            "cpu": 77,
            "queue": 140
          }
        },
        {
          "state": "CONGESTION_L1",
          "resourceUsageLimit": {
            "cpu": 78,
            "queue": 160
          }
        },
        {
          "state": "CONGESTION_L2",
          "resourceUsageLimit": {
            "cpu": 79,
            "queue": 180
          }
        },
        {
          "state": "CONGESTED",
          "resourceUsageLimit": {
            "cpu": 80,
            "queue": 200
          }
        }
      ]
    },
    "isCustomProfile": false
  },
  "serviceName": "pcf-ue"
},
{
  "congestionThresholdProfiles": [
    {
      "name": "DEFAULT",
      "value": [
        {
          "state": "DANGER_OF_CONGESTION",
          "resourceUsageLimit": {

```

```

        "cpu": 55,
        "queue": 60
    }
},
{
    "state": "CONGESTION_L1",
    "resourceUsageLimit": {
        "cpu": 65,
        "queue": 70
    }
},
{
    "state": "CONGESTION_L2",
    "resourceUsageLimit": {
        "cpu": 75,
        "queue": 80
    }
},
{
    "state": "CONGESTED",
    "resourceUsageLimit": {
        "cpu": 85,
        "queue": 90
    }
}
],
"isCustomProfile": false
},
],
"serviceName": "udr-connector"
},
{
    "congestionThresholdProfiles": [
        {
            "name": "DEFAULT",
            "value": [
                {
                    "state": "DANGER_OF_CONGESTION",
                    "resourceUsageLimit": {
                        "cpu": 55,
                        "queue": 60
                    }
                },
                {
                    "state": "CONGESTION_L1",
                    "resourceUsageLimit": {
                        "cpu": 65,
                        "queue": 70
                    }
                },
                {
                    "state": "CONGESTION_L2",
                    "resourceUsageLimit": {
                        "cpu": 75,
                        "queue": 80
                    }
                }
            ]
        }
    ]
}

```



```

        },
        {
            "state": "CONGESTED",
            "resourceUsageLimit": {
                "cpu": 85,
                "queue": 90
            }
        }
    ],
    "isCustomProfile": false
},
{
    "serviceName": "chf-connector"
},
{
    "congestionThresholdProfiles": [
        {
            "name": "DEFAULT",
            "value": [
                {
                    "state": "DANGER_OF_CONGESTION",
                    "resourceUsageLimit": {
                        "cpu": 80,
                        "queue": 75
                    }
                },
                {
                    "state": "CONGESTED",
                    "resourceUsageLimit": {
                        "cpu": 90,
                        "queue": 85
                    }
                }
            ],
            "isCustomProfile": false
        }
    ],
    "serviceName": "bulwark"
}
]
}

```

2.10 Congestion Control Load Shedding Profiles

Congestion Control Load Shedding Rules APIs

Note

The default Congestion Control Load Shedding Rule cannot be updated by the User.

The Pod Congestion Control PCF services, resource URI parameter {serviceName} values can be:

- bulwark
- binding
- usage-mon
- policy-ds
- pcf-sm
- pcrf-core
- pcf-ue
- oc-diam-gateway
- diam-connector
- udr-connector
- chf-connector
- pcf-am
- notifier

Table 2-55 Congestion Control Load Shedding Rules APIs

API Description	HTTP Method or Custom Operation	Resource URI	Description	Possible Result Code
Get Congestion Control Load Shedding Rules	GET	/oc-cnpolicy-configuration/v1/congestionLoadSheddingRule/{serviceName}	Gets the load shedding rules for bulwark, binding, usage-mon, policy-ds, pcf-sm, pcrf-core, pcf-ue, oc-diam-gateway, diam-connector, udr-connector, chf-connector, pcf-am, and notifier services.	See Table A-1
Update congestion control load shedding rule.	PUT	{apiRoot}/oc-cnpolicy-configuration/v1/congestionLoadSheddingRule/{serviceName}/{ruleName}	To update the discard priority of DANGER_OF_CONGESTION, CONGESTION_L1, CONGESTION_L2 and CONGESTED states of specific threshold rule.	See Table A-2
Add congestion control load shedding rule.	POST	{apiRoot}/oc-cnpolicy-configuration/v1/congestionLoadSheddingRule/{serviceName}/{ruleName}	To add new congestion load shedding rule with specified name	See Table A-3

Table 2-55 (Cont.) Congestion Control Load Shedding Rules APIs

API Description	HTTP Method or Custom Operation	Resource URI	Description	Possible Result Code
Delete congestion control load shedding rule.	DELETE	{apiRoot}/oc-cnpolicy-configuration/v1/congestionLoadSheddingRule/{serviceName}/{ruleName}	To delete congestion load shedding rule with specified name	See Table A-4

Table 2-56 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/Optional(O)/Conditional(C)	Description
name	String	M	This value should be same as the ruleName in path variable.
value	CongestionLoadSheddingState	M	This value should be different congestion states.
isCustomProfile	Boolean	M	Denotes that the rule is custom created by user. Note: Currently user can create custom rules only. Hence this value should be set to true.

Table 2-57 CongestionLoadSheddingState

Field Name	Data Type	Mandatory(M)/Optional(O)/Conditional(C)	Description
state	String	M	The value can be following pod Congestion states: • DANGER_OF_CONGESTION • CONGESTION_L1 • CONGESTION_L2 • CONGESTED Bulwark service supports only two states DANGER_OF_CONGESTION and CONGESTED.

Table 2-57 (Cont.) CongestionLoadSheddingState

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
discardPriority	integer	M	The discard priority value for the requests. The minimum value is 0 and maximum value is 31. Default Value: 5
discardPriorityPercentage	DiscardPriorityPercentage	O	The discard priority range or percentage for the requests. Note: This is applicable only to Diameter Gateway service.

Table 2-58 DiscardPriorityPercentage

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
range	string	M	The discard priority value or range for the requests. The values allowed is a number such as 1 or a pattern like 11-13. Note: This is applicable only to Diameter Gateway service.
percentage	integer	M	The percentage of requests that needs to be discarded. The minimum value is 1 and maximum value is 100. Example: 23 Note: This is applicable only to Diameter Gateway service.

Sample body request for Put and Post operations for Priority Based Load Shedding for Bulwark Service:

```
{
  "name": "ruleName",
  "value":
  [
    {
      "state": "CONGESTED",
      "discardPriority": 10
    }
  ]
}
```

```

    },
    {
      "state": "DANGER_OF_CONGESTION",
      "discardPriority": 20
    }
  ],
  "isCustomProfile": true
}

```

Sample body request for Put and Post operations for Priority Based Load Shedding for Other Policy Services :

```

{
  "name": "ruleName",
  "value": [
    {
      "state": "CONGESTED",
      "discardPriority": 20
    },
    {
      "state": "CONGESTION_L2",
      "discardPriority": 24
    },
    {
      "state": "CONGESTION_L1",
      "discardPriority": 27
    },
    {
      "state": "DANGER_OF_CONGESTION",
      "discardPriority": 30
    }
  ],
  "isCustomProfile": true
}

```

Sample body request for Put and Post operations for Priority and Percentage based Load Shedding for Diameter Gateway Services:

```

{
  "name": "ruleName",
  "value": [
    {
      "state": "CONGESTED",
      "discardPriorityPercentage": [
        {
          "range": 11
          "percentage": 20
        }
      ]
    },
    {
      "state": "CONGESTION_L2",

```

```
    "discardPriorityPercentage": [
      {
        "range": 1-3
        "percentage": 30
      },
      {
        "range": 5
        "percentage": 60
      }
    ]
  },
  {
    "state": "CONGESTION_L1",
    "discardPriorityPercentage": [
      {
        "range": 5-10
        "percentage": 60
      },
      {
        "range": 1-3
        "percentage": 30
      },
      {
        "range": 12
        "percentage": 70
      }
    ]
  },
  {
    "state": "DANGER_OF_CONGESTION",
    "discardPriorityPercentage": [
      {
        "range": 6
        "percentage": 70
      }
    ]
  }
],
"isCustomProfile": true
}
```

Congestion Control Load Shedding Profile APIs

Table 2-59 Congestion Control Load Shedding Profiles

API Description	HTTP Method or Custom Operation	Resource URI	Description	Possible Result Code
Get Congestion Control Load Shedding Profiles	GET	{apiRoot}/oc-cnpolicy-configuration/v1/congestionLoadSheddingProfile/{serviceName}	To get the name, type and active load shedding rule.	See Table A-1
Update Congestion Control Load Shedding Profile	PUT	{apiRoot}/oc-cnpolicy-configuration/v1/congestionLoadSheddingProfile/{serviceName}	To update name and loadSheddingRule Name	See Table A-2

Table 2-60 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/Optional(O)/Conditional(C)	Description
name	String	M	Name of the load shedding profile.
loadSheddingRuleName	String	M	Name of profile name which we want to activate.
type	String	M	This value will be congestion always.

Sample body request for Get operations for Load Shedding Profiles:

```
{
  "name": "loadSheddingProfile",
  "loadSheddingRuleName": "DEFAULT",
  "type": "congestion"
}
```

Sample body request for Put operations for Load Shedding Profiles:

```
{
  "name": "loadSheddingProfile",
  "loadSheddingRuleName": "loadSheddingRule",
  "type": "congestion"
}
```

Import or Export Congestion Control Load Shedding Rules

Table 2-61 Import/Export Congestion Control Load Shedding Rules

API Name	Request Url	Request Type	Description
Export Congestion Control Load Shedding Rules	{apiRoot}/oc-cnpolicy-configuration/v1/congestionLoadSheddingRule/export	GET	To export congestion control load shedding rules
Import Congestion Control Load Shedding rules	{apiRoot}/oc-cnpolicy-configuration/v1/congestionLoadSheddingRule/import?action={action}	POST	To import congestion control load shedding rules

Table 2-62 Request/Response Body Parameters

Field Name	Data Type	Mandatory/Optional/Conditional	Description
topic	String	M	commonconfig.congestionLoadSheddingRules
sourceVersion	String	M	Build version
date	String	M	Date in pattern "yyyy-MM-dd'T'HH:mm:ss'Z"
exportData	Congestion Load Shedding Data	M	Array for Congestion Control Settings. This array contains JSON objects for each service that supports congestion control feature.

```
{
  "topic": "commonconfig.congestionLoadSheddingRules",
  "sourceVersion": "25.1.100",
  "date": "2025-01-03T09:29:46Z",
  "exportData": [
    {
      "congestionLoadSheddingProfiles": [
        {
          "name": "loadSheddingProfile",
          "loadSheddingRuleName": "DEFAULT",
          "type": "congestion"
        }
      ],
      "congestionLoadSheddingRules": [
        {
          "name": "DEFAULT",
          "value": [
            {
              "state": "DANGER_OF_CONGESTION",
              "discardPriority": 27
            }
          ],
        }
      ]
    }
  ]
}
```



```

    {
      "state": "CONGESTION_L1",
      "discardPriority": 19
    },
    {
      "state": "CONGESTION_L2",
      "discardPriority": 17
    },
    {
      "state": "CONGESTED",
      "discardPriority": 15
    }
  ],
  "isCustomProfile": false
},
{
  "name": "DEFAULT_PRIORITY_AND_PERCENTAGE",
  "value": [
    {
      "state": "DANGER_OF_CONGESTION",
      "discardPriorityPercentage": [
        {
          "range": "27-31",
          "percentage": 50
        }
      ]
    },
    {
      "state": "CONGESTION_L1",
      "discardPriorityPercentage": [
        {
          "range": "19-26",
          "percentage": 50
        },
        {
          "range": "27-31",
          "percentage": 75
        }
      ]
    },
    {
      "state": "CONGESTION_L2",
      "discardPriorityPercentage": [
        {
          "range": "17-18",
          "percentage": 50
        },
        {
          "range": "19-26",
          "percentage": 75
        },
        {
          "range": "27-31",
          "percentage": 100
        }
      ]
    }
  ]
}

```

```

        },
        {
            "state": "CONGESTED",
            "discardPriorityPercentage": [
                {
                    "range": "15-31",
                    "percentage": 100
                }
            ]
        }
    ],
    "isCustomProfile": false
},
{
    "serviceName": "oc-diam-gateway"
},
{
    "congestionLoadSheddingProfiles": [
        {
            "name": "loadSheddingProfile",
            "loadSheddingRuleName": "DEFAULT",
            "type": "congestion"
        }
    ],
    "congestionLoadSheddingRules": [
        {
            "name": "DEFAULT",
            "value": [
                {
                    "state": "DANGER_OF_CONGESTION",
                    "discardPriority": 29
                },
                {
                    "state": "CONGESTION_L1",
                    "discardPriority": 23
                },
                {
                    "state": "CONGESTION_L2",
                    "discardPriority": 17
                },
                {
                    "state": "CONGESTED",
                    "discardPriority": 15
                }
            ]
        },
        {
            "isCustomProfile": false
        }
    ],
    "serviceName": "udr-connector"
},
{
    "congestionLoadSheddingProfiles": [
        {
            "name": "loadSheddingProfile",
            "loadSheddingRuleName": "DEFAULT",
            "type": "congestion"
        }
    ]
}

```

```

    }
  ],
  "congestionLoadSheddingRules": [
    {
      "name": "DEFAULT",
      "value": [
        {
          "state": "DANGER_OF_CONGESTION",
          "discardPriority": 28
        },
        {
          "state": "CONGESTION_L1",
          "discardPriority": 25
        },
        {
          "state": "CONGESTION_L2",
          "discardPriority": 20
        },
        {
          "state": "CONGESTED",
          "discardPriority": 17
        }
      ],
      "isCustomProfile": false
    }
  ],
  "serviceName": "diam-connector"
},
{
  "congestionLoadSheddingProfiles": [
    {
      "name": "loadSheddingProfile",
      "loadSheddingRuleName": "DEFAULT",
      "type": "congestion"
    }
  ],
  "congestionLoadSheddingRules": [
    {
      "name": "DEFAULT",
      "value": [
        {
          "state": "DANGER_OF_CONGESTION",
          "discardPriority": 30
        },
        {
          "state": "CONGESTION_L1",
          "discardPriority": 27
        },
        {
          "state": "CONGESTION_L2",
          "discardPriority": 24
        },
        {
          "state": "CONGESTED",
          "discardPriority": 20
        }
      ]
    }
  ]
}

```

```

    ],
    "isCustomProfile": false
  }
],
"serviceName": "binding"
},
{
  "congestionLoadSheddingProfiles": [
    {
      "name": "loadSheddingProfile",
      "loadSheddingRuleName": "DEFAULT",
      "type": "congestion"
    }
  ],
  "congestionLoadSheddingRules": [
    {
      "name": "DEFAULT",
      "value": [
        {
          "state": "DANGER_OF_CONGESTION",
          "discardPriority": 27
        },
        {
          "state": "CONGESTION_L1",
          "discardPriority": 19
        },
        {
          "state": "CONGESTION_L2",
          "discardPriority": 17
        },
        {
          "state": "CONGESTED",
          "discardPriority": 15
        }
      ],
      "isCustomProfile": false
    }
  ],
  "serviceName": "pcf-sm"
},
{
  "congestionLoadSheddingProfiles": [
    {
      "name": "loadSheddingProfile",
      "loadSheddingRuleName": "DEFAULT",
      "type": "congestion"
    }
  ],
  "congestionLoadSheddingRules": [
    {
      "name": "DEFAULT",
      "value": [
        {
          "state": "DANGER_OF_CONGESTION",
          "discardPriority": 30
        },

```

```

        {
          "state": "CONGESTION_L1",
          "discardPriority": 27
        },
        {
          "state": "CONGESTION_L2",
          "discardPriority": 24
        },
        {
          "state": "CONGESTED",
          "discardPriority": 20
        }
      ],
      "isCustomProfile": false
    }
  ],
  "serviceName": "usage-mon"
},
{
  "congestionLoadSheddingProfiles": [
    {
      "name": "loadSheddingProfile",
      "loadSheddingRuleName": "DEFAULT",
      "type": "congestion"
    }
  ],
  "congestionLoadSheddingRules": [
    {
      "name": "DEFAULT",
      "value": [
        {
          "state": "DANGER_OF_CONGESTION",
          "discardPriority": 29
        },
        {
          "state": "CONGESTION_L1",
          "discardPriority": 23
        },
        {
          "state": "CONGESTION_L2",
          "discardPriority": 17
        },
        {
          "state": "CONGESTED",
          "discardPriority": 15
        }
      ],
      "isCustomProfile": false
    }
  ],
  "serviceName": "pcrf-core"
},
{
  "congestionLoadSheddingProfiles": [
    {
      "name": "loadSheddingProfile",

```

```

        "loadSheddingRuleName": "DEFAULT",
        "type": "congestion"
    }
],
"congestionLoadSheddingRules": [
    {
        "name": "DEFAULT",
        "value": [
            {
                "state": "DANGER_OF_CONGESTION",
                "discardPriority": 28
            },
            {
                "state": "CONGESTION_L1",
                "discardPriority": 20
            },
            {
                "state": "CONGESTION_L2",
                "discardPriority": 17
            },
            {
                "state": "CONGESTED",
                "discardPriority": 15
            }
        ],
        "isCustomProfile": false
    }
],
"serviceName": "policy-ds"
},
{
    "congestionLoadSheddingProfiles": [
        {
            "name": "loadSheddingProfile",
            "loadSheddingRuleName": "DEFAULT",
            "type": "congestion"
        }
    ],
    "congestionLoadSheddingRules": [
        {
            "name": "DEFAULT",
            "value": [
                {
                    "state": "DANGER_OF_CONGESTION",
                    "discardPriority": 29
                },
                {
                    "state": "CONGESTION_L1",
                    "discardPriority": 23
                },
                {
                    "state": "CONGESTION_L2",
                    "discardPriority": 17
                },
                {
                    "state": "CONGESTED",

```

```

        "discardPriority": 15
      }
    ],
    "isCustomProfile": false
  }
},
"serviceName": "chf-connector"
},
{
  "congestionLoadSheddingProfiles": [
    {
      "name": "loadSheddingProfile",
      "loadSheddingRuleName": "DEFAULT",
      "type": "congestion"
    }
  ],
  "congestionLoadSheddingRules": [
    {
      "name": "DEFAULT",
      "value": [
        {
          "state": "DANGER_OF_CONGESTION",
          "discardPriority": 28
        },
        {
          "state": "CONGESTION_L1",
          "discardPriority": 25
        },
        {
          "state": "CONGESTION_L2",
          "discardPriority": 20
        },
        {
          "state": "CONGESTED",
          "discardPriority": 17
        }
      ],
      "isCustomProfile": false
    }
  ],
  "serviceName": "pcf-ue"
},
{
  "congestionLoadSheddingProfiles": [
    {
      "name": "loadSheddingProfile",
      "loadSheddingRuleName": "DEFAULT",
      "type": "congestion"
    }
  ],
  "congestionLoadSheddingRules": [
    {
      "name": "DEFAULT",
      "value": [
        {
          "state": "DANGER_OF_CONGESTION",

```

```

        "discardPriority": 20
      },
      {
        "state": "CONGESTED",
        "discardPriority": 10
      }
    ],
    "isCustomProfile": false
  }
],
"serviceName": "bulwark"
}
]
}

```

2.11 NRF Agent

Table 2-63 Policy General Settings APIs Schema updated for supporting Sbi-correlation:

Description	HTTP Method	Resource URI	Application Type	Response Status
Get NRF Agent Service	GET	{apiRoot}/oc-cnpolicy-configuration/v1/services/nrfAgent	application/json	See Table A-1
Update NRF Agent Service	PUT	{apiRoot}/oc-cnpolicy-configuration/v1/services/nrfAgent	application/json	See Table A-2
Import NRF agent service	POST	{apiRoot}/oc-cnpolicy-configuration/v1/services/nrfAgent/import	application/json	
Export NRF agent service	GET	{apiRoot}/oc-cnpolicy-configuration/v1/services/nrfAgent/export	application/json	

Table 2-64 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/Optional(O)/Conditional(C)	Description
nrfAgentNfCommProfile	String	O	NRF Agent Communication Profile
onDemandDiscoveryCaching.enableFeature	Boolean	O	Indicates NRF Client to cache the profile data and use it to process the future discovery on-demand requests. Default value: false

Table 2-64 (Cont.) Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
onDemandDiscoveryCaching.queryParameters	String	O	Accepts the list of parameters that NRF Client uses to fetch the profile data from cache. Note: The query parameters in the request from SM service, AM service, UE Policy service must match and must be in the same order as the data received from NRF. Otherwise, NRF Client can not process the request. Supported values: • target-nf-type • requester-nf-type • target-nf-set-id • service-names • amf-region-id • amf-set-id • GUAMI
onDemandDiscoveryCaching.refreshBeforeExpiryTime	String	O	Indicates the time in milliseconds before expiration when a rediscovery must be performed for the requested discovery parameters. Default value: 4500
onDemandDiscoveryCaching.limitCacheEntries	String	O	Parameter to set the upper bound of cache registries allowed to be retained. Default value: 2000
onDemandDiscoveryCaching.retentionPeriod	String	O	Indicates the time a record is allowed to stay in database after expiry and before any clean process is executed. Default value: 864000000 Note: Retention Period value is ignored when force discovery is enabled

Table 2-64 (Cont.) Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
onDemandDiscoveryCaching.auditorSchedulerInterval	String	O	Parameter to set time in milliseconds to activate the Discovery Cache auditor service to clean stale records. Default value: 1800000
onDemandDiscoveryCaching.auditorPurgePercentage	String	O	Parameter to set the percentage of the cached DiscoveryRequests that will be pruned once the threshold has been passed. Default value: 20

Sample Response/Request body structure for GET and PUT operations respectively:

```
{
  "nrfAgentNfCommProfile": "string"
  "onDemandDiscoveryCaching":
    {
      "enableFeature": false,
      "queryParameters": [],
      "refreshBeforeExpiryTime": 4500,
      "limitCacheEntries": 2000,
      "retentionPeriod": 864000000,
      "auditorSchedulerInterval": 1800000,
      "auditorPurgePercentage": 20
    }
}
```

2.12 Error Configurations

API support is available for EXPORT/IMPORT of error handler configurations.

Table 2-65 Supported REST APIs

Description	HTTP Method or Custom Operation	Resource URI	Media Type	Possible Result Code
Export Error Configuration	GET	{apiRoot}/oc-cnpolicy-configuration/v1/services/errorHandler/errorConfiguration/export	application/json	See Table A-1

Table 2-65 (Cont.) Supported REST APIs

Description	HTTP Method or Custom Operation	Resource URI	Media Type	Possible Result Code
Import Error Configuration	POST	{apiRoot}/oc-cnpolicy-configuration/v1/services/errorHandler/errorConfiguration/import?action=replace*	application/json	See Table A-3

Note

This API accepts a JSON that may contain both default and non-default error configurations. However, during the import operation, only the non-default error configurations are imported. Any modifications made to the default error configurations in the JSON, except for **priority**, are ignored and will not be applied. This behavior is consistent with the GUI, where the default error configurations cannot be modified. The only attribute of the default rules that can be updated through the API is their **priority**.

This section describes the body parameters for Error Import or Export Configurations.

Table 2-66 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
topic	string	M	Topic of each managed object
sourceVersion	string	O	System version of product from which data is exported
date	string	O	Current Timestamp
exportData	array	O	Exported list of error rules configurations

2.13 Diameter Error Codes

Table 2-67 Supported REST APIs - Diameter Error Codes

Description	HTTP Method or Custom Operation	Resource URI	Possible Result Code
Get Diameter Error Codes	GET	/oc-cnppolicy-configuration/v1/diameter/diameterErrorCodes/{appld}	200: OK 400: Bad request 404: Not Found 500: Internal Server Error 503: Service Unavailable
Update Diameter Error Codes	PUT	/oc-cnppolicy-configuration/v1/diameter/diameterErrorCodes/{appld}	200: OK 400: Bad request 404: Not Found 500: Internal Server Error 503: Service Unavailable
Export Diameter Error Codes	GET	/oc-cnppolicy-configuration/v1/diameter/diameterErrorCodes/export	200: OK 400: Bad request 404: Not Found 500: Internal Server Error 503: Service Unavailable
Import Diameter Error Codes	POST	/oc-cnppolicy-configuration/v1/diameter/diameterErrorCodes/import	200: OK 400: Bad request 404: Not Found 500: Internal Server Error 503: Service Unavailable

Get and Update Diameter Error Codes

Table 2-68 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/Optional(O)/Conditional(C)	Description
appld	string	Mandatory	Specifies the application ID.
errorCodes	array	Mandatory	Specifies the error parameters.
conditionName	string	Mandatory	Specifies the system defined name for a given condition.
useExperimentalResultCode	boolean	Optional	Indicates whether to use the Result Code AVP (268) or Experimental Result AVP (297) when an error result is generated by Policy.
errorMessage	string	Optional	Specifies the description for a defined condition. It is recommended to use descriptions that clearly explain the condition.

Table 2-68 (Cont.) Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
diameterResultCode	string	Conditional	Specifies the Diameter result code for a defined condition.
experimentalResultCode	string	Conditional	Specifies the custom Diameter result code for a defined condition.

Sample Request body for Diameter Error Codes PUT operation:

```
{
  "appId": "Rx",
  "errorCodes": [
    {
      "conditionName": "IP CAN session not established",
      "useExperimentalResultCode": false,
      "errorMessage": "Enforcement session not found for current request",
      "diameterResultCode": "3012"
    }
  ]
}
```

Sample Response body structure for Diameter Error Codes GET and PUT operation:

```
{
  "appId": "Rx",
  "errorCodes": [
    {
      "conditionName": "IP CAN session not established",
      "useExperimentalResultCode": false,
      "errorMessage": "Enforcement session not found for current request",
      "diameterResultCode": "3012"
    }
  ]
}
```

Import and Export Diameter Error Codes

Table 2-69 Request or Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
topic	string	Mandatory	Topic of each managed object
sourceVersion	string	Optional	System version of product from which data is exported
date	string	Optional	Current timestamp

Table 2-69 (Cont.) Request or Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
exportData	array	Mandatory	Exported list of Error Codes.
appId	string	Mandatory	Specifies the application ID.
errorCodes	string	Mandatory	Specifies the error parameters.
conditionName	string	Mandatory	Specifies the error condition name
useExperimentalResult Code	Boolean	Optional	Indicates whether to use the Result Code AVP (268) or Experimental Result AVP (297) when an error result is generated by BSF.
errors.message	string	Optional	Error message
diameterResultCode	string	Conditional	Specifies the custom Diameter result code for a defined condition.

Sample Request Body structure for Diameter Error Codes Import and Export operations:

```
{
  "topic": "diameter.errorcodes.test",
  "sourceVersion": "23.2.0-od-20230307",
  "date": "2023-03-10T17:44:08Z",
  "exportData": [
    {
      "appId": "Rx",
      "errorCodes": [
        {
          "conditionName": "IP CAN session not established",
          "useExperimentalResultCode": false,
          "errorMessage": "Enforcement session not found for current request",
          "diameterResultCode": "3012"
        }
      ]
    }
  ]
}
```

2.14 Session Viewer

Table 2-70 Policy Session Viewer APIs

Description	HTTP Method or Custom Operation	Resource URI	Possible Result Code
Get Session	GET	{apiRoot}/oc-cnpolicy-query/v1/sessions	See Table A-1
Delete Session	DELETE	{apiRoot}/oc-cnpolicy-query/v1/sessions	See Table A-4

Get and Delete Session

Table 2-71 Request Parameters

Field Name	Data Type	Mandatory(M)/Optional(O)/Conditional(C)	Description
sessionType	string	M	Allowed Values: 1. SM_Policy_Association 2. AM_Policy_Association 3. PA_Policy_Association 4. SM_TDF_Session 5. PCRF_Core_Session 6. Binding_Session 7. User_Data 8. UE_Policy_Association 9. Usage_Monitoring 10. All DELETE with "All" option is implemented to delete all subscriber/session for SM and PA session type only.

Table 2-71 (Cont.) Request Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
identifierType	string	M	Allowed Values: • SUPI • IMSI • MSISDN • POLICY_ASSOC_ID • DIAMETER_SESSION_ID • GPSI • PEI SM Service supports all the values from 1-6 UE Service supports SUPI, GPSI, PEI, and POLICY_ASSOC_ID AM Service supports SUPI, GPSI, and POLICY_ASSOC_ID PA service only supports POLICY_ASSOC_ID PCRF-CORE supports (IMSI , MSISDN ,IPV4, IPV6, DIAMETER_SESSION_ID) USER-DATA supports SUPI and GPSI UE Service supports (SUPI and POLICY_ASSOC_ID) Usage Monitoring supports SUPI and GPSI ALL supports SUPI and GPSI
identifierValue	string	M	Indicates the value of the selected identifier type.
sessionSubtype	string	O	Allowed Values: • ALL • GX • RX • SD
remote	boolean	O	Allowed Values: • true • false
getUserData	boolean	M	Allowed Values: • true • false

Sample Response body structure for GET operation:

"string"

cURL Commands

The following are sample cURL commands for some of the services:

For UE Service

- **GET**

```
curl -X GET "http://<localhost>/oc-cnpolicy-query/v1/sessions?
identifierType=POLICY_ASSOC_ID&identifierValue=5bc04e63-b2b8-4084-
b8d5-577c8d05a0b2&sessionType=UE_Policy_Association" -H "accept: application/
json"
```

- **DELETE**

```
curl -X DELETE "http://<localhost>/oc-cnpolicy-query/v1/sessions?
identifierType=SUPI&identifierValue=imsi-100000000002&sessionType=UE_Policy_Ass
ociation" -H "accept: application/json"
```

For PA Service

- **GET**

```
curl -X GET "http://<localhost>/oc-cnpolicy-query/v1/sessions?
identifierType=POLICY_ASSOC_ID&identifierValue=5bc04e63-b2b8-4084-
b8d5-577c8d05a0b2&sessionType=PA_Policy_Association" -H "accept: application/
json"
```

- **DELETE**

```
curl -X DELETE "http://<localhost>/oc-cnpolicy-query/v1/sessions?
identifierType=POLICY_ASSOC_ID&identifierValue=73c3a7cd-afdb-4ce6-828b-
a0fd2bd401ae&sessionType=PA_Policy_Association" -H "accept: application/json"
```

For AM Service

- **GET**

```
curl -X GET "http://<localhost>/oc-cnpolicy-query/v1/sessions?
identifierType=supi&identifierValue=imsi-450081000000001&sessionType=AM_Policy
_Association" -H "accept: application/json"
```

- **DELETE**

```
curl -X DELETE "http://<localhost>/oc-cnpolicy-query/v1/sessions?
identifierType=SUPI&identifierValue=imsi-450081000000001&sessionType=AM_Policy
_Association" -H "accept: application/json"
```

For PCRF Core Service

- **GET**

```
curl -X 'GET' \ 'https://<localhost>/oc-cnpolicy-query/v1/sessions?
getUserData=true&identifierType=MSISDN&identifierValue=01151601062&sessionType
=PCRF_Core_Session' \ -H 'accept: application/json'
```

- **DELETE**

```
curl -X 'DELETE' \ 'https://<localhost>/oc-cnpolicy-query/v1/sessions?
getUserData=true&identifierType=MSISDN&identifierValue=01151601062&sessionType
=PCRF_Core_Session' \ -H 'accept: application/json'
```

2.15 Policy General Settings

Table 2-72 Supported REST APIs

Description	HTTP Method or Custom Operation	Resource URI	Possible Result Code
Get Individual General Configuration	GET	{apiRoot}/oc-cnpolicy-configuration/v1/general	See Table A-1
Update General Configuration	PUT	{apiRoot}/oc-cnpolicy-configuration/v1/general	See Table A-2
Export Global Configurations	GET	{apiRoot}/oc-cnpolicy-configuration/v1/general/export	See Table A-1
Import Global Configurations	POST	{apiRoot}/oc-cnpolicy-configuration/v1/general/import	See Table A-3

Get and Update Operations

Table 2-73 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
apiGatewayHost	String	O	Name for the API gateway host
apiGatewayPort	Number	O	Port number of the API gateway
enableMetrics	boolean	O	This determines if system metrics is enabled. This will take priority on global metrics config Default Value: TRUE
enableTLS	boolean	O	This determines if TLS is enabled Default Value: TRUE
enableTracing	boolean	O	This determines if tracing is enabled Default Value: TRUE
enableSubscriberLog	boolean	O	This determines if subscriber logging is enabled for a subscriber Default Value: FALSE

Table 2-73 (Cont.) Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
perHost	string	O	Valid url of PER host to receive the PER record. The format of the url is: http://per-host:per-port, where per-host specifies the PER host and per-port specifies the PER port. For example, http://localhost:8101/v1/echo
enablePER	boolean	O	This determines whether to enable/disable Policy Event Record (PER) feature Default Value: false
enableSBICorrelation	boolean	O	This determines whether to enable/disable correlation-info header in PCF Default Value: false
enhancedLogging	Array	O	Used to configure the enhanced logging for Policy. For details on the parameters under in section, see Table 2-74 .
truncateStackTrace	Array	O	Used to configure the stack trace truncation feature. For details on the parameters under in section, see Table 2-75 .

Table 2-74 Request/Response Parameters for Enhanced Logging

Name	Data Type	Mandatory (M)/ Optional (O)	Description
enhancedLogging.enableEnhancedLogging	Boolean	O	Specifies whether to enable or disable enhanced logging for the Policy deployment. Default value: false
enhancedLogging.enableLogUEIdentifierInfo	Boolean	O	Specifies whether to enable or disable UE Identifier information for the Policy deployment. Default value: false

Table 2-75 Request/Response Parameters for TruncateStackTrace

Name	Data Type	Mandatory (M)/ Optional (O)	Description
truncateStackTrace.enableTruncateStackTrace	Boolean	O	Specifies whether to enable or disable the Stack Trace Truncation feature. When this field is enabled, the amount of lines configured on all stack traces are truncated. Default value: true
truncateStackTrace.stackTraceLines	Integer	O	This field is configured to limit the number of lines shown on the stack trace. Default value: 5 Range: 0 to 65535

Sample Request body structure for PUT operations:

```
{
  "enableTracing": true,
  "enableMetrics": true,
  "apiGatewayHost": "string",
  "apiGatewayPort": 80,
  "enableTls": true,
  "enableSubscriberLog": false,
  "enablePER": false,
  "perHost": "string",
  "enableSBICorrelation": false,
  "enhancedLogging": {
    "enableTruncateStackTrace": true,
    "stackTraceLines": 0,
    "enableEnhancedLogging": true,
    "stateSessionDeletionLogLevel": "string",
    "enableLogUEIdentifierInfo": true,
    "enableLogUeInfoInSessionDeletion": true
  },
  "truncateStackTrace": {
    "stackTraceLines": 0,
    "enableTruncateStackTrace": true
  }
}
```

Sample Response body structure for GET and PUT operations:

```
{
  "enableTracing": true,
  "enableMetrics": true,
  "apiGatewayHost": "string",
```

```

"apiGatewayPort": 80,
"enableTls": true,
"enableSubscriberLog": false,
"enablePER": false,
"perHost": "string",
"enableSBICorrelation": false,
"enhancedLogging": {
  "enableTruncateStackTrace": true,
  "stackTraceLines": 0,
  "enableEnhancedLogging": true,
  "staleSessionDeletionLogLevel": "string",
  "enableLogUEIdentifierInfo": true,
  "enableLogUeInfoInSessionDeletion": true
},
"truncateStackTrace": {
  "stackTraceLines": 0,
  "enableTruncateStackTrace": true
}
}

```

Export/Import Global Configurations

Table 2-76 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
date	string		Current timestamp
exportData	array		Exported list of diameter settings. For more information, see Get and Update Operations
sourceVersion	string		System version of product from which data is exported
topic	string		Topic of each managed object

Sample Request Body structure for Import/Export operations:

```

{
  "topic": "string",
  "sourceVersion": "string",
  "date": "string",
  "exportData": {
    "enableTracing": true,
    "enableMetrics": true,
    "apiGatewayHost": "string",
    "apiGatewayPort": 80,
    "enableTls": true,
    "enableSubscriberLog": false,
    "enablePER": false,
    "perHost": "string",
    "enableSBICorrelation": false,
    "enhancedLogging": {

```

```

    "enableTruncateStackTrace": true,
    "stackTraceLines": 0,
    "enableEnhancedLogging": true,
    "staleSessionDeletionLogLevel": "string",
    "enableLogUEIdentifierInfo": true,
    "enableLogUEInfoInSessionDeletion": true
  },
  "truncateStackTrace": {
    "stackTraceLines": 0,
    "enableTruncateStackTrace": true
  }
}
}

```

2.16 Subscriber Logging

Table 2-77 Supported REST APIs

Description	HTTP Method or Custom Operation	Resource URI	Possible Result Code
Create Subscriber Logging	POST	{apiRoot}/oc-cnpolicy-configuration/v1/subscriberActivityLogging	See Table A-3
Export Subscriber Logs	GET	{apiRoot}/oc-cnpolicy-configuration/v1/subscriberActivityLogging/export	See Table A-1
Import Subscriber Logs	POST	{apiRoot}/oc-cnpolicy-configuration/v1/subscriberActivityLogging/import	See Table A-3
Get Subscriber Logging	GET	{apiRoot}/oc-cnpolicy-configuration/v1/subscriberActivityLogging/{identifierValue}	See Table A-1
Update Subscriber Logging	PUT	{apiRoot}/oc-cnpolicy-configuration/v1/subscriberActivityLogging/{identifierValue}	See Table A-2
Delete Subscriber Logging	DELETE	{apiRoot}/oc-cnpolicy-configuration/v1/subscriberActivityLogging/{identifierValue}	See Table A-4

Get and Create Subscriber Logging

Table 2-78 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/Optional(O)/Conditional(C)	Description
enable	boolean	M	

Table 2-78 (Cont.) Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
type	string	M	
value	string	M	

Sample Request body structure for POST operation:

```
{
  "enable": true,
  "type": "gpsi",
  "value": "string"
}
```

Sample Response body structure for GET, POST, and PUT operations:

```
[
  {
    "date": "string",
    "errors": [
      {
        "message": "string",
        "name": "string"
      }
    ],
    "exportData": [
      {
        "enable": true,
        "type": "gpsi",
        "value": "string"
      }
    ],
    "sourceVersion": "string",
    "topic": "string"
  }
]
```

Delete Subscriber Logging**Table 2-79 Request/Response Body Parameters**

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
identifierValue	string	M	Subscriber Identifier

Export/Import Subscriber Logging

Table 2-80 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
date	string	O	Current timestamp
exportData	array	M	Exported list of subscriber logs. For more information, see Get and Create Subscriber Logging .
sourceVersion	string	O	System version of product from which data is exported
topic	string	M	Topic of each managed object

Sample Request Body structure for Import/Export operations:

```
{
  "date": "string",
  "errors": [
    {
      "message": "string",
      "name": "string"
    }
  ],
  "exportData": [
    {
      "enable": true,
      "type": "gpsi",
      "value": "string"
    }
  ],
  "sourceVersion": "string",
  "topic": "string"
}
```

2.17 Recreate Attempts

This section describes the service URIs available to create and configure reattempts profile for Policy.

Table 2-81 Policy Recreate Attempts Profile APIs

Description	HTTP Method or Custom Operation	Resource URI	Possible Result Code
Create Reattempt Profile	POST	{apiRoot}/oc-cnpolicy-configuration/v1/services/common/reattemptsProfile	See Table A-3
Get Reattempt Profile	GET	{apiRoot}/oc-cnpolicy-configuration/v1/services/common/reattemptsProfile/{attemptName}	See Table A-1
Update Reattempt Profile	PUT	{apiRoot}/oc-cnpolicy-configuration/v1/services/common/reattemptsProfile/{attemptName}	See Table A-2
Delete Reattempt Profile	DELETE	{apiRoot}/oc-cnpolicy-configuration/v1/services/common/reattemptsProfile/{attemptName}	See Table A-4

Request and Response Body Parameters

This section describes the request and response parameters used in reattempts profile APIs.

Table 2-82 Request and Response Body Parameters (for POST and PUT operations)

Field Name	Data Type	Mandatory(M)/Optional(O)/Conditional(C)	Description
name	String	M	The unique name for the reattempt profile. This name is used to refer to the reattempt profile in other service configuration screen, such as SM Service. The name can only contain the characters A–Z, a–z, 0–9, period (.), hyphen (-), and underline (_). The maximum length is 255 characters.
interface Type	String	O	The interface for which a reattempt profile is being created. The interface types are: • BSF • AMF • NRF

Table 2-82 (Cont.) Request and Response Body Parameters (for POST and PUT operations)

Field Name	Data Type	Mandatory(M)/Optional(O)/Conditional(C)	Description
reattemptSettings	BSFRecreateAttempt	O	Creates a number of reattempts that should be run for the chosen interface type.
reattemptErrorCodeSettings	ReattemptErrorCodeSettings	O	Provide Re-attempt Error Code settings details.
rateLimitSettings	RateLimitSettings	O	Provide Rate Limiting settings details.

Table 2-83 BSFRecreateAttempt

Field Name	Data Type	Mandatory(M)/Optional(O)/Conditional(C)	Description
numberOfAttempts	integer	M	To configure the maximum number of reattempts that are allowed for a service operation. On selecting BSF interface type, it is the number of reattempts that must be run when PCF Binding request fails. It takes a range between 0 - 50. On selecting NRF interface type, it is the number of reattempts that must be run when AMF discovery request fails. It takes a range between 0 - 100. On selecting AMF interface type, it is the number of reattempt that must be run when N1N2 Subscribe, N1N2 Transfer, N1N2 Failure Notification requests fails. It takes a range between 0 - 100.
backOffTimerConfig	Attempt	O	The amount of time that represents each back-off timer. Note: In case the number of configured attempts in the Back-off timer configurations table is less than the set value for Maximum Number of Attempts , the remaining attempts uses the back off timer and max random number of the last configured attempt. Note: Policy supports a maximum of 20 back-off timer configurations.

Table 2-83 (Cont.) BSFRecreateAttempt

Field Name	Data Type	Mandatory(M)/Optional(O) / Conditional(C)	Description
thresholdLimitLevel	integer	O	The threshold limit for the Pending Operations. Once this value is reached, no pending operations are added to the table. Range: 0 - 1000 for BSF interface type. Range: 0 - 360000 for NRF/AMF interface type.

Table 2-84 Attempt

Field Name	Data Type	Mandatory(M)/Optional(O) / Conditional(C)	Description
index	integer	O	Represents the number of back-off timer.
backOffTimer	integer	M	Configure back-off timer for every reattempt request in seconds.
maxRandomNumber	integer	O	Configure any random number in milliseconds that is added to the back-off timer. This can be in the range of 0-5000 milliseconds. If this is not configured then the back-off timer is considered without an random value.

Table 2-85 ReattemptErrorCodeSettings

Field Name	Data Type	Mandatory(M)/Optional(O)/Conditional(C)	Description
reattemptOnInternalFailure	boolean	O	To enable reattempt for internal failure, for example: request timed out at UE service. Default value: true
reattemptErrorCodes	ReattemptErrorCodes	O	Configure the list of combination of HTTP error code and cause for reattempt with back off. A maximum of 32 combinations of error code and cause can be provided.

Table 2-86 ReattemptErrorCodes

Field Name	Data Type	Mandatory(M)/Optional(O)/Conditional(C)	Description
errorCode	integer	M	Provide the HTTP error code for which the reattempt is applicable. It is a number and can range from 100-999.
errorCauses	[string]	O	Provide the cause for an error code so that reattempt is made only for the matching causes of the error code. Note: The Error Cause value should be in upper case. Use only underscore '_' between words, and do not use space.

Table 2-87 RateLimitSettings

Field Name	Data Type	Mandatory(M)/Optional(O)/Conditional(C)	Description
rateLimitPerSecond	integer	M	Configure the rate limit threshold per second for NF service operation(s). This value can be in the range between 0 - 700. Default value: 50

Sample Request body structure for POST and PUT operations:

```
{
  "name": "string",
  "interfaceType": "bsf",
  "retrySettings": {
    "numberOfAttempts": 0,
    "backOffTimerConfig": [
      {
        "index": 0,
        "backOffTimer": 0,
        "maxRandomNumber": 5000
      }
    ],
    "thresholdLimitLevel": 0
  },
  "retryErrorCodeSettings": {
    "retryOnInternalFailure": true,
    "retryErrorCodes": [
      {
        "errorCode": 999,
        "errorCauses": [
          "string"
        ]
      }
    ]
  },
  "rateLimitSettings": {
    "rateLimitPerSecond": 50
  }
}
```

```

    }
  }

  {
    "name": "string",
    "interfaceType": "bsf",
    "reattemptSettings": {
      "numberOfAttempts": 0,
      "backOffTimerConfig": [
        {
          "index": 0,
          "backOffTimer": 0,
          "maxRandomNumber": 5000
        }
      ],
      "thresholdLimitLevel": 0
    },
    "reattemptErrorCodeSettings": {
      "reattemptOnInternalFailure": true,
      "reattemptErrorCodes": [
        {
          "errorCode": 999,
          "errorCauses": [
            "string"
          ]
        }
      ]
    },
    "rateLimitSettings": {
      "rateLimitPerSecond": 50
    }
  }
}

```

cURL Command for GET

```
curl -X GET "http://<IP Address>/oc-cnpolicy-configuration/v1/services/common/reattemptProfile/<retryProfileName>" -H "accept: application/json"
```

cURL Command for POST

```
curl -X POST "http://<IP Address>/oc-cnpolicy-configuration/v1/services/common/reattemptProfile" -H "accept: application/json" -H "Content-Type: application/json" -d "{ \"alternateRoutingSettings\": { \"enableFallback\": true, \"errorCodesAlternateRoute\": [ { \"errorCauses\": [ \"string\" ], \"errorCode\": 0 } ], \"errorCodesReAttempt\": [ { \"errorCauses\": [ \"string\" ], \"errorCode\": 0 } ], \"localityPreference\": \"DIFFERENT\", \"maxNumOfAlternateRoutingAttempts\": 3, \"nfSetPreference\": \"DIFFERENT\", \"priorityPool\": false, \"reAttemptFailedNF\": true, \"reAttemptSameNF\": true, \"retryFallbackAfterInterval\": 900, \"useAlternateSCPforAlternateRouting\": true, \"useSbiBindingInformation\": true }, \"enableAlternateRouting\": true, \"enableRetry\": true, \"name\":
```

```
\\"string\\", \\"retrySettings\\": { \\"maximumNumberOfRetries\\": 3 },  
\\"serverHeaderSupport\\": \\"DISABLED\\"}"
```

Export or Import Recreate Attempts

Table 2-88 Response Body Parameters for Import Request

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
date	string	O	Specifies the current timestamp
errors:message	string	O	Specifies the error message.
errors:name	string	O	Specifies the name of the error.
exportData	array	M	Exported retry profile. For more information, see Table 2-92 .
key	string	O	Indicates the ID of Retry Profile
sourceVersion	string	O	System version of product from which data is exported
topic	string	M	Topic of each managed object

Table 2-89 Import/Export Recreate Attempts

API Name	Request Type	Request Url	Possible Result Code
Export Recreate Profile	GET	{apiRoot}/oc-cnpolicy-configuration/v1/services/common/re-attemptsProfile/export	See Table A-1
Import Recreate Profile	POST	{apiRoot}/oc-cnpolicy-configuration/v1/services/common/re-attemptsProfile/import	See Table A-3

Table 2-90 Request/Response Body Parameters

Field Name	Data Type	Mandatory/Optional/ Conditional	Description
topic	String	M	It should be commonconfig.congestionThresholdProfiles
sourceVersion	String	M	Build version
date	String	M	Date in pattern "yyyy-MM-dd'T'HH:mm:ss'Z'"

Table 2-90 (Cont.) Request/Response Body Parameters

Field Name	Data Type	Mandatory/Optional/Conditional	Description
exportData	Congestion Threshold Profiles Data	M	Array for Congestion Control Threshold Profiles. This array contains JSON objects of each service that supports congestion control feature.

Sample Request Body structure for Import and Export operations:

```
{
  "topic": "string",
  "sourceVersion": "string",
  "date": "string",
  "exportData": [
    {
      "name": "string",
      "interfaceType": "bsf",
      "reattemptSettings": {
        "numberOfAttempts": 0,
        "backOffTimerConfig": [
          {
            "index": 0,
            "backOffTimer": 0,
            "maxRandomNumber": 5000
          }
        ],
        "thresholdLimitLevel": 0
      },
      "reattemptErrorCodeSettings": {
        "reattemptOnInternalFailure": true,
        "reattemptErrorCodes": [
          {
            "errorCode": 999,
            "errorCauses": [
              "string"
            ]
          }
        ]
      }
    }
  ],
  "rateLimitSettings": {
    "rateLimitPerSecond": 50
  }
},
"errors": [
  {
    "name": "string",
    "message": "string"
  }
]
```



```
    ]
  }
```

2.18 Retry Profile

This section describes the service URIs available to create and configure retry profiles for Policy.

Table 2-91 Supported REST APIs for Retry Profile

Description	HTTP Method or Custom Operation	Resource URI	Possible Result Code
Create Retry Profile	POST	{apiRoot}/oc-cnpolicy-configuration/v1/services/common/retryprofiles	See Table A-3
Get Retry Profile	GET	{apiRoot}/oc-cnpolicy-configuration/v1/services/common/retryprofiles/{retryProfileName}	See Table A-1
Update Retry Profile	PUT	{apiRoot}/oc-cnpolicy-configuration/v1/services/common/retryprofiles/{retryProfileName}	See Table A-2
Export Retry Profiles	GET	{apiRoot}/oc-cnpolicy-configuration/v1/services/common/retryprofiles/export	See Table A-1
Import Retry Profiles	POST	{apiRoot}/oc-cnpolicy-configuration/v1/services/common/retryprofiles/import	See Table A-3
Delete Retry Profile	DELETE	{apiRoot}/oc-cnpolicy-configuration/v1/services/common/retryprofiles/{retryProfileName}	See Table A-4

Request and Response Body Parameters

This section describes the request and response parameters used in retry profile APIs.

Table 2-92 Request and Response Body Parameters (for POST and PUT operations)

Field Name	Data Type	Mandatory(M)/Optional(O)/Conditional(C)	Description
alternateRoutingSettings	AlternateRoutingSettings	Optional	Specifies the alternate routing settings for a retry profile.

Table 2-92 (Cont.) Request and Response Body Parameters (for POST and PUT operations)

Field Name	Data Type	Mandatory(M)/Optional(O)/Conditional(C)	Description
enableAlternateRouting	boolean	Optional	Specifies whether to enable or disable alternate routing. On enabling this switch, ensure that you configure the parameters under the Alternate Routing Settings group. When enabled, alternate routing is attempted when Policy messages are not delivered successfully to an external NF destination. It may happen because of an exception on the Egress Gateway, such as connection error, timeout, or a failure returned by the external NF or an intermediate router.
enableRetry	boolean	Optional	Specifies whether to enable or disable retry for failed messages between core microservices of Policy. On enabling this switch, ensure that you configure the parameters under Retry Settings group. However, if the switch is disabled, the configurations in the Retry Settings group are not taken into consideration. When enabled, retries are attempted when PCF encounters internal send failures for egress messages. A failure to send egress messages internally indicates an exception in the core service, such as SM service, UDR or CHF connector, and so on. The exception can occur while connecting to the next microservice or a failure on the microservice itself. For example, egress message did not reach the egress gateway. This also includes the connection errors and timeouts on the core microservice. Note: Since the failure is internal, the external NF and SCP (if applicable) remain the same during retry attempt.
name	string	Optional The name can only contain the characters A–Z, a–z, 0–9, period (.), hyphen (-), and underline (_). The maximum length is 255 characters.	Specifies the unique name for the retry profile.

Table 2-92 (Cont.) Request and Response Body Parameters (for POST and PUT operations)

Field Name	Data Type	Mandatory(M)/Optional(O)/Conditional(C)	Description
retrySettings	RetrySettings	Optional	Specifies the retry settings for a retry profile.
serverHeaderSupport	Enum The valid values for this parameter are as follow: - DISABLED - MULTI_INSTANCE - SINGLE_INSTANCE	Optional	Specifies whether to enable or disable server header. The value configured in this parameter is used when PCF acts as a consumer and receives server header in error response messages. - Disabled: Disable server header. On disabling server header, Policy as a consumer searches for alternate producer without considering the value of server header. - Single Instance: Accept only one value in the server header. When the value is configured as Single Instance and server header contains multiple values, Policy rejects the header. - Multi Instance: Accept only one value in the server header.
patternToIgnoreServerHeader	String	Optional	This field appears on selection of either "Single Instance" or "Multi Instance" value for the field Server Header Support . In this field you can specify the string pattern that can be ignored in the server header value. This is provided in the form of regular expression. The regular expression evaluates the server header content to ignore the strings that match the pattern specified the regular expression.

Table 2-93 AlternateRoutingSettings

Field Name	Data Type	Mandatory(M)/Optional(O)/Conditional(C)	Description
enableFallback	boolean	Optional	Specifies whether to enable or disable falling back to the higher priority destination that failed earlier (after the retry interval). Policy attempts fallback even if the current destination is available. When enabled, Policy attempts to fallback to a higher priority NF destination. The priority of NF destination is determined by Alternate Route service (either via DNS-SRV resolution or by static configuration). By default, it is disabled.
errorCodesAlternateRoute	AlternateRoutingErrorCodes	Optional	Specifies the HTTP error codes for which Policy retries alternate routing on receiving the error response from the destination network function or Egress Gateway.
errorCodesReAttempt	AlternateRoutingErrorCodes	Optional	Specifies the HTTP error codes for which Policy does not look for alternate producer and retries the request to the same producer NF or SCP that failed in the first attempt. Policy considers this parameter only when Re-attempt to same NF switch is enabled.

Table 2-93 (Cont.) AlternateRoutingSettings

Field Name	Data Type	Mandatory(M)/Optional(O)/Conditional(C)	Description
localityPreference	ENUM The valid values for this parameter are as follow: • DIFFERENT • NONE • SAME	Optional	Specifies the locality preference when choosing the alternate producer for a failed request. Policy excludes the producer (received in the failed request) and selects an alternate producer based on the value provided for this attribute. • Same: Chooses the next producer from the same locality as the previous request. • Different: Chooses the next producer from a different locality. • None (default): Locality filter does not apply.

Table 2-93 (Cont.) AlternateRoutingSettings

Field Name	Data Type	Mandatory(M)/Optional(O)/Conditional(C)	Description
maxNumOfAlternateRoutingAttempts	boolean	Optional	Specifies the number of retries that PCF attempts on receiving error response from Ingress Gateway. The number of retry attempts can be in the range of 1 to 10. Note: The value configured for this parameter does not include the initial attempt. For instance, if you set the value as 3, Policy performs the retry cycle three times after the initial attempt. If the retry attempts are exhausted, Policy fails the transaction with an exception. In certain cases, the number of retry attempts can be greater than the available alternate destinations to be tried. If such a situation arises, Policy fails the transaction when no alternate destination is available even if retry attempts are still available.

Table 2-93 (Cont.) AlternateRoutingSettings

Field Name	Data Type	Mandatory(M)/Optional(O)/Conditional(C)	Description
nfSetPreference	ENUM The valid values for this parameter are as follow: • DIFFERENT • NONE • SAME	Optional	Specifies the NF set preference when choosing the alternate producer for an initial request. Policy excludes the producer (received in the failed request) and selects an alternate producer based on the value provided for this attribute. • Same: Selects the next producer from the same NFSet as the previous request. • Different: Selects the next producer from a different NFSet. • None (default): NFSets filter does not apply. Note: This parameter applies only to initial requests. For subsequent requests, the default behavior is to choose the same NFSet irrespective of the value configured for this field.

Table 2-93 (Cont.) AlternateRoutingSettings

Field Name	Data Type	Mandatory(M)/Optional(O)/Conditional(C)	Description
reAttemptFailedNF	boolean	Optional	When you set the value for this parameter to true, Policy initiates the retry cycle and sends request to the selected NF when the following conditions are true: • Retry attempts made to all available NF instances • Maximum Number of Alternate Routing Attempt is not exhausted
reAttemptSameNf	boolean	Optional	Specifies whether Policy shall send the request to the same NF that failed in the first attempt. If you set the value to true, make sure to configure the value for <code>errorCodesReAttempt</code> attribute. By default, the value is false for this parameter.

Table 2-93 (Cont.) AlternateRoutingSettings

Field Name	Data Type	Mandatory(M)/Optional(O)/Conditional(C)	Description
retryFallbackAfterInterval	integer	Optional	Specifies the time in seconds after which Policy re-attempts a request to a higher priority destination. In case of fallback, when a route is being determined while the current destination has not failed, PCF attempts to fallback to a higher priority NF destination. Priority of NF destination is determined by Alternate Route service, either through DNS-SRV resolution or static configuration. You can set the value for retry after interval from 0 to 86,400 seconds. By default, the value is set to 0, which means that a high priority destination is blocklisted. Note: • This configuration applies to subsequent message routing only. • Blacklisting may still be done by Egress Gateway • An NF destination (FQDN) is not re-attempted within the context of a single operation, such as SM Modification request

Table 2-93 (Cont.) AlternateRoutingSettings

Field Name	Data Type	Mandatory(M)/Optional(O)/Conditional(C)	Description
useAlternateSCPforAlternateRouting	boolean	Optional	Specifies whether to enable or disable choosing alternate SCP to reach the alternate destination. If you set the value for this parameter as true, Egress Gateway uses an alternate SCP for routing to an alternate NF destination. If there are fewer SCPs than alternate NF destinations, Egress Gateway tries sending the request through one of the previously used SCPs. Note: Additional SCP configuration is required for Egress Gateway. For more information, see <i>Oracle Communications Cloud Native Core, Converged Policy Installation, Upgrade and Fault Recovery Guide</i>.

Table 2-93 (Cont.) AlternateRoutingSettings

Field Name	Data Type	Mandatory(M)/Optional(O)/Conditional(C)	Description
useSbiBindingInformation	boolean	Optional	Specifies whether to enable or disable use of information received in 3gpp-sbi-binding header. When Policy receives the unique NF Instance ID in the error response, it retrieves 3gpp-sbi-binding header for that particular NF instance, and then extracts the SetId to choose the alternate producer. This parameter is considered only for subsequent retry requests. By default, the value is false for this attribute. Note: When the value is set to false, the NFSet Preference parameter is not taken into consideration.

Table 2-94 AlternateRoutingErrorCodes

Field Name	Data Type	Mandatory(M)/Optional(O)/Conditional(C)	Description
errorCauses	string	Optional You can configure up to five error causes per error code.	Specifies the HTTP error code. For example, 504
errorCode	integer	Mandatory You can configure up to 10 error codes for a retry profile. Enter a range in [100-999] number	Specifies the error cause. For example, GATEWAY_TIMEOUT, NF_TIMEOUT.

Table 2-95 RetrySettings

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
maximumNumberOfRetries	integer	Optional The number of retry attempts can be in the range of 1 to 10. Note: It is mandatory to configure this parameter if Retry on Internal Send Failure parameter is set to true.	Specifies the number of retries that PCF attempts on encountering failure while sending egress messages between Policy core microservices. Note: The value configured for this parameter does not include the initial attempt. For instance, if you set the value as 3, Policy performs the retry cycle three times after the initial attempt.

Table 2-96 retryAfterSettings

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
retryAfterSettings.enableRetryAfterIE	Boolean	O	This parameter enables or disables deferring an N1N2Transfer message for the retryAfter IE value received from AMF. The supported retryAfter IE range is 1 to 600 seconds. Note: This parameter applies only to the retryAfter IE received from AMF over the N1N2 interface; it does not apply to the HTTP Retry-After header or other service interfaces.

Sample Request body structure for POST and PUT operations:

```
{
  "name": "string",
  "enableRetry": true,
  "enableAlternateRouting": true,
  "retrySettings": {
    "maximumNumberOfRetries": 3
  },
  "alternateRoutingSettings": {
    "maxNumOfAlternateRoutingAttempts": 3,
    "errorCodesAlternateRoute": [
      {
        "errorCode": 100,
        "errorCauses": [
          "string"
        ]
      }
    ]
  }
}
```

```

    ]
  }
],
"priorityPool": false,
"useAlternateSCPforAlternateRouting": true,
"useSbiBindingInformation": false,
"useBindingInformationFromNFProfile": true,
"enableDNSResolution": true,
"nfSetResolution": "CACHED_NF_PROFILES",
"nfSetPreference": "NONE",
"localityPreference": "NONE",
"reAttemptSameNf": false,
"errorCodesReAttempt": [
  {
    "errorCode": 100,
    "errorCauses": [
      "string"
    ]
  }
],
"enableFallback": false,
"retryFallbackAfterInterval": 900,
"reAttemptFailedNF": true,
"retryAfterSettings": {
  "enableRetryAfterIE": "true"
}
},
"serverHeaderSupport": "DISABLED",
"patternToIgnoreServerHeader": "string"
}

```

Sample Response body structure for GET, POST, and PUT operations:

```

[
  {
    "name": "string",
    "enableRetry": true,
    "enableAlternateRouting": true,
    "retrySettings": {
      "maximumNumberOfRetries": 3
    },
    "alternateRoutingSettings": {
      "maxNumOfAlternateRoutingAttempts": 3,
      "errorCodesAlternateRoute": [
        {
          "errorCode": 100,
          "errorCauses": [
            "string"
          ]
        }
      ]
    },
    "priorityPool": false,
    "useAlternateSCPforAlternateRouting": true,
    "useSbiBindingInformation": false,
    "useBindingInformationFromNFProfile": true,
  }
]

```

```

    "enableDNSResolution": true,
    "nfSetResolution": "CACHED_NF_PROFILES",
    "nfSetPreference": "NONE",
    "localityPreference": "NONE",
    "reAttemptSameNf": false,
    "errorCodesReAttempt": [
      {
        "errorCode": 100,
        "errorCauses": [
          "string"
        ]
      }
    ],
    "enableFallback": false,
    "retryFallbackAfterInterval": 900,
    "reAttemptFailedNF": true,
    "retryAfterSettings": {
      "enableRetryAfterIE": "true"
    }
  },
  "serverHeaderSupport": "DISABLED",
  "patternToIgnoreServerHeader": "string"
}
]

```

cURL Command for POST

```

curl -X 'POST' \
  'http://10.123.134.17:8000/oc-cnpolicy-configuration/v1/services/common/retryprofiles' \
  -H 'accept: application/json' \
  -H 'Content-Type: application/json' \
  -d '{
    "name": "string",
    "enableRetry": true,
    "enableAlternateRouting": true,
    "retrySettings": {
      "maximumNumberOfRetries": 3
    },
    "alternateRoutingSettings": {
      "maxNumOfAlternateRoutingAttempts": 3,
      "errorCodesAlternateRoute": [
        {
          "errorCode": 100,
          "errorCauses": [
            "string"
          ]
        }
      ]
    },
    "priorityPool": false,
    "useAlternateSCPforAlternateRouting": true,
    "useSbiBindingInformation": false,
    "useBindingInformationFromNFProfile": true,
    "enableDNSResolution": true,
    "nfSetResolution": "CACHED_NF_PROFILES",
  }'

```

```

    "nfSetPreference": "NONE",
    "localityPreference": "NONE",
    "reAttemptSameNf": false,
    "errorCodesReAttempt": [
      {
        "errorCode": 100,
        "errorCauses": [
          "string"
        ]
      }
    ],
    "enableFallback": false,
    "retryFallbackAfterInterval": 900,
    "reAttemptFailedNF": true,
    "retryAfterSettings": {
      "enableRetryAfterIE": "true"
    }
  },
  "serverHeaderSupport": "DISABLED",
  "patternToIgnoreServerHeader": "string"
}'

```

Export or Import Retry Profile

Table 2-97 Response Body Parameters for Import Request

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
date	string	O	Specifies the current timestamp
errors:message	string	O	Specifies the error message.
errors:name	string	O	Specifies the name of the error.
exportData	array	M	Exported retry profile. For more information, see Table 2-92 .
key	string	O	Indicates the ID of Retry Profile
sourceVersion	string	O	System version of product from which data is exported
topic	string	M	Topic of each managed object

Sample Request Body structure for Import and Export operations:

```

{
  "topic": "string",
  "sourceVersion": "string",
  "systemVersion": "string",
  "date": "string",
  "errors": [

```

```

    {
      "name": "string",
      "message": "string"
    }
  ],
  "exportData": [
    {
      "name": "string",
      "enableRetry": true,
      "enableAlternateRouting": true,
      "retrySettings": {
        "maximumNumberOfRetries": 3
      },
      "alternateRoutingSettings": {
        "maxNumOfAlternateRoutingAttempts": 3,
        "errorCodesAlternateRoute": [
          {
            "errorCode": 100,
            "errorCauses": [
              "string"
            ]
          }
        ]
      },
      "priorityPool": false,
      "useAlternateSCPforAlternateRouting": true,
      "useSbiBindingInformation": false,
      "useBindingInformationFromNFProfile": true,
      "enableDNSResolution": true,
      "nfSetResolution": "CACHED_NF_PROFILES",
      "nfSetPreference": "NONE",
      "localityPreference": "NONE",
      "reAttemptSameNf": false,
      "errorCodesReAttempt": [
        {
          "errorCode": 100,
          "errorCauses": [
            "string"
          ]
        }
      ],
      "enableFallback": false,
      "retryFallbackAfterInterval": 900,
      "reAttemptFailedNF": true,
      "retryAfterSettings": {
        "enableRetryAfterIE": "true"
      }
    },
    {
      "serverHeaderSupport": "DISABLED",
      "patternToIgnoreServerHeader": "string"
    }
  ]
}

```


2.19 Timer Profile

Table 2-98 Supported REST APIs

Description	HTTP Method or Custom Operation	Resource URI	Possible Result Code
Create Timer Profile	POST	{apiRoot}/oc-cnpolicy-configuration/v1/services/common/timerprofiles	See Table A-3
Get Timer Profile	GET	{apiRoot}/oc-cnpolicy-configuration/v1/services/common/timerprofiles/{serviceType}	See Table A-1
Update Timer Profile	PUT	{apiRoot}/oc-cnpolicy-configuration/v1/services/common/timerprofiles/{serviceType}	See Table A-2
Export Timer Profiles	GET	{apiRoot}/oc-cnpolicy-configuration/v1/services/common/timerprofiles/export	See Table A-1
Import Timer Profiles	POST	{apiRoot}/oc-cnpolicy-configuration/v1/services/common/timerprofiles/import	See Table A-3
Delete Timer Profile	DELETE	{apiRoot}/oc-cnpolicy-configuration/v1/services/common/timerprofiles/{serviceType}	See Table A-4

Get, Create, and Update Timer Profiles

Table 2-99 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
serviceType	string	M	Specifies the following supported service types: - PCF User Connector - PCF Session Management - PCF Access and Mobility - PCF UE Policy - PCF Binding Service
UDR.svcTimeoutMapping	SvcTimeoutMapping ForUDR	C	Details of UDR service time out.

Table 2-99 (Cont.) Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
CHF.svcTimeoutMapping	SvcTimeoutMapping ForCHF	C	Details of CHF service time out.
BSF.svcTimeoutMapping	SvcTimeoutMapping ForBSF	C	Details of BSF service time out.
SMF.svcTimeoutMapping	SvcTimeoutMapping ForSMF	C	Details of SMF service time out.
AF.svcTimeoutMapping	SvcTimeoutMapping ForAF	C	Details of AF service time out.
AMF.svcTimeoutMapping	SvcTimeoutMapping ForAMF	C	Details of AMF service time out.

Table 2-100 SvcTimeoutMappingForUDR Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
nudr-dr	integer	O	Timeout value specified in "3gpp-Sbi-Max-Rsp-Time" header for the nudr-dr service. Provide a number between 1 to 2147483647. For example: 3000.
QUERY	integer	O	Timeout value specified in "3gpp-max-response-time" header for the Query messages.
SUBSCRIBE	integer	O	Timeout value specified in "3gpp-max-response-time" header for the subscribe messages.
UNSUBSCRIBE	integer	O	Timeout value specified in "3gpp-max-response-time" header for the unsubscribe messages.
UPDATE	integer	O	Timeout value specified in "3gpp-max-response-time" header for the update messages.
SUBSCRIBE_WITH_IM MEDIATE_REPORTING	integer	O	Timeout when a POST (subscribe) request is sent from PCF to UDR having the attribute "immRep" set to true. Range: 0 - 15000 ms Default: 3000

Table 2-101 SvcTimeoutMappingForCHF Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
nchf-spendinglimitcontrol	integer	O	Timeout value specified in "3gpp-Sbi-Max-Rsp-Time" header for the nchfspendinglimitcontrol service. Provide a number between 1 to 2147483647. For example: 3000.

Table 2-102 SvcTimeoutMappingForBSF Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
nbsf-management	integer	O	Timeout value specified in "3gpp-Sbi-Max-Rsp-Time" header for the nbsfmanagement service. Provide a number between 1 to 2147483647. For example: 3000.

Table 2-103 SvcTimeoutMappingForSMF Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
notification	integer	O	Timeout value specified in "3gpp-Sbi-Max-Rsp-Time" header for the notification service. Provide a number between 1 to 2147483647. For example: 3000.

Table 2-104 SvcTimeoutMappingForAF Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
notification	integer	O	Timeout value specified in "3gpp-Sbi-Max-Rsp-Time" header for the notification service. Provide a number between 1 to 2147483647. For example: 3000.

Table 2-105 SvcTimeoutMappingForAMF Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
namf-comm	integer	O	Timeout value specified in "3gpp-Sbi-Max-Rsp-Time" header for the namf-comm service. Provide a number between 1 to 2147483647. For example: 3000.
notification	integer	O	Timeout value specified in "3gpp-max-response-time" header for the notification service.

Sample Request body structure for POST and PUT operations:

```
{
  "serviceType": "string",
  "UDR": {
    "svcTimeoutMapping": {
      "nudr-dr": 3000,
      "QUERY": 0,
      "SUBSCRIBE": 0,
      "UNSUBSCRIBE": 0,
      "UPDATE": 0,
      "SUBSCRIBE_WITH_IMMEDIATE_REPORTING": 0
    }
  },
  "CHF": {
    "svcTimeoutMapping": {
      "nchf-spendinglimitcontrol": 3000
    }
  },
  "BSF": {
    "svcTimeoutMapping": {
      "nbsf-management": 3000
    }
  }
}
```

```

    },
    "SMF": {
      "svcTimeoutMapping": {
        "notification": 3000
      }
    },
    "AF": {
      "svcTimeoutMapping": {
        "notification": 3000
      }
    },
    "AMF": {
      "svcTimeoutMapping": {
        "namf-comm": 3000,
        "notification": 3000
      }
    }
  }
}

```

Export/Import Timer Profiles

Table 2-106 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
systemVersion	string	O	The system version.
topic	string	M	Topic of each managed object
sourceVersion	string	O	System version of the product from which data is exported
date	string	O	Current timestamp
exportData	array	M	Date to be exported.
errors.message	string	O	The error message.
errors.name	string	O	The error name.

Sample Request Body structure for Import/Export operations:

```

{
  "topic": "string",
  "sourceVersion": "string",
  "date": "string",
  "exportData": [
    {
      "serviceType": "string",
      "UDR": {
        "svcTimeoutMapping": {
          "nudr-dr": 3000,
          "QUERY": 0,
          "SUBSCRIBE": 0,
          "UNSUBSCRIBE": 0,
          "UPDATE": 0,
          "SUBSCRIBE_WITH_IMMEDIATE_REPORTING": 0
        }
      }
    }
  ]
}

```

```

    }
  },
  "CHF": {
    "svcTimeoutMapping": {
      "nchf-spendinglimitcontrol": 3000
    }
  },
  "BSF": {
    "svcTimeoutMapping": {
      "nbsf-management": 3000
    }
  },
  "SMF": {
    "svcTimeoutMapping": {
      "notification": 3000
    }
  },
  "AF": {
    "svcTimeoutMapping": {
      "notification": 3000
    }
  },
  "AMF": {
    "svcTimeoutMapping": {
      "namf-comm": 3000,
      "notification": 3000
    }
  }
}
],
"errors": [
  {
    "name": "string",
    "message": "string"
  }
]
}

```

2.20 Retry Profile for PCC

Table 2-107 Supported REST APIs

Description	HTTP Method or Custom Operation	Resource URI	Possible Result Code
Create PCC Retry Profile	POST	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcrf/pccretryprofiles	See Table A-3
Export PCC Retry Profile	GET	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcrf/pccretryprofiles/export	See Table A-1

Table 2-107 (Cont.) Supported REST APIs

Description	HTTP Method or Custom Operation	Resource URI	Possible Result Code
Import PCC Retry Profile	POST	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcrf/pccretryprofiles/import	See Table A-3
Get PCC Retry Profile	GET	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcrf/pccretryprofiles/{pccRetryProfileName}	See Table A-1
Update PCC Retry Profile	PUT	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcrf/pccretryprofiles/{pccRetryProfileName}	See Table A-2
Delete PCC Retry Profile	DELETE	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcrf/pccretryprofiles/{pccRetryProfileName}	See Table A-4

Create, Get, and Update Retry Profile for PCC

Table 2-108 Data structures supported by the POST, GET, and PUT Response Body

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
backOffInterval	integer	M	Enter a value between 1 and 86400
description	string	O	
id	string	O	
initialRetryInterval	integer	M	Enter a value between 0 and 30
maxRetryAttempt	integer	M	Enter a value between 1 and 10
maxRetryCycles	integer	M	Enter a value between 1 and 4
maxRetryInterval	integer	M	Enter a value between 1 and 180
name	string	M	

Table 2-108 (Cont.) Data structures supported by the POST, GET, and PUT Response Body

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
ruleFailureCode	array		Contains items of type string. Supported values: - UNKNOWN_RULE_NAME - RATING_GROUP_ERROR - SERVICE_IDENTIFIER_ERROR - GW_PCEF_MALFUNCTION - RESOURCES_LIMITATION - MAX_NR_BEARERS_REACHED - UNKNOWN_BEARER_ID - MISSING_BEARER_ID - MISSING_FLOW_INFORMATION - RESOURCE_ALLOCATION_FAILURE - UNSUCCESSFUL_QOS_VALIDATION - INCORRECT_FLOW_INFORMATION - PS_TO_CS_HANDOVER - TDF_APPLICATION_IDENTIFIER_ERROR - NO_BEARER_BOUND - FILTER_RESTRICTIONS - AN_GW_FAILED - MISSING_REDIRECT_SERVER_ADDRESS - CM_END_USER_SERVICE_DENIED - CM_CREDIT_CONTROL_NOT_APPLICABLE - CM_AUTHORIZATION_REJECTED - CM_USER_UNKNOWN - CM_RATING_FAILED

Sample Request Body structure for POST and PUT operations:

```
{
  "backOffInterval": 0,
  "description": "string",
  "id": "string",
  "initialRetryInterval": 0,
  "maxRetryAttempt": 0,
  "maxRetryCycles": 0,
  "maxRetryInterval": 0,
  "name": "string",
  "ruleFailureCode": [
```



```

    "AN_GW_FAILED"
  ]
}

```

Sample Response Body structure for GET, POST and PUT operations:

```

{
  "backOffInterval": 0,
  "description": "string",
  "id": "string",
  "initialRetryInterval": 0,
  "maxRetryAttempt": 0,
  "maxRetryCycles": 0,
  "maxRetryInterval": 0,
  "name": "string",
  "ruleFailureCode": [
    "AN_GW_FAILED"
  ]
}

```

Export/Import Retry Profile for PCC

Table 2-109 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
date	string		Current timestamp
errors	array		
errors:message	string		
errors:name	string		
exportData	array	M	Exported list of PCC retry profile. For more information, see Table 2-108 .
key	string		Indicates the ID
sourceVersion	string		System version of the product from which data is exported
topic	string	M	Topic of each managed object

Sample Request Body structure for Import/Export operations:

```

{
  "date": "string",
  "errors": [
    {
      "message": "string",
      "name": "string"
    }
  ],
  "exportData": [

```

```

{
  "backOffInterval": 0,
  "description": "string",
  "id": "string",
  "initialRetryInterval": 0,
  "maxRetryAttempt": 0,
  "maxRetryCycles": 0,
  "maxRetryInterval": 0,
  "name": "string",
  "ruleFailureCode": [
    "AN_GW_FAILED"
  ]
}
],
"key": "string",
"sourceVersion": "string",
"topic": "string"
}

```

Delete Retry Profile for PCC

Table 2-110 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
pccRetryProfileName	string	M	PCC Retry Profile Name

2.21 Retry Profile for ADC

Table 2-111 Supported REST APIs

Description	HTTP Method or Custom Operation	Resource URI	Possible Result Code
Create ADC Retry Profile	POST	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcrf/adcretryprofiles	See Table A-3
Export ADC Retry Profile	GET	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcrf/adcretryprofiles/export	See Table A-1
Import ADC Retry Profile	POST	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcrf/adcretryprofiles/import	See Table A-3
Get ADC Retry Profile	GET	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcrf/adcretryprofiles/{adcRetryProfileName}	See Table A-1

Table 2-111 (Cont.) Supported REST APIs

Description	HTTP Method or Custom Operation	Resource URI	Possible Result Code
Update ADC Retry Profile	PUT	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcrf/adcretryprofiles/{adcRetryProfileName}	See Table A-2
Delete ADC Retry Profile	DELETE	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcrf/adcretryprofiles/{adcRetryProfileName}	See Table A-4

Create, Get, and Update Retry Profile for ADC**Table 2-112 Data structures supported by the POST, GET, and PUT Response Body**

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
backOffInterval	integer	M	Enter a value between 1 and 86400
description	string	O	
id	string	O	
initialRetryInterval	integer	M	Enter a value between 0 and 30
maxRetryAttempt	integer	M	Enter a value between 1 and 10
maxRetryCycles	integer	M	Enter a value between 1 and 4
maxRetryInterval	integer	M	Enter a value between 1 and 180
name	string	M	

Table 2-112 (Cont.) Data structures supported by the POST, GET, and PUT Response Body

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
ruleFailureCode	array		Contains items of type string. Supported values: - UNKNOWN_RULE_NAME - RATING_GROUP_ERROR - SERVICE_IDENTIFIER_ERROR - GW_PCEF_MALFUNCTION - RESOURCES_LIMITATION - MAX_NR_BEARERS_REACHED - UNKNOWN_BEARER_ID - MISSING_BEARER_ID - MISSING_FLOW_INFORMATION - RESOURCE_ALLOCATION_FAILURE - UNSUCCESSFUL_QOS_VALIDATION - INCORRECT_FLOW_INFORMATION - PS_TO_CS_HANDOVER - TDF_APPLICATION_IDENTIFIER_ERROR - NO_BEARER_BOUND - FILTER_RESTRICTIONS - AN_GW_FAILED - MISSING_REDIRECT_SERVER_ADDRESS - CM_END_USER_SERVICE_DENIED - CM_CREDIT_CONTROL_NOT_APPLICABLE - CM_AUTHORIZATION_REJECTED - CM_USER_UNKNOWN - CM_RATING_FAILED

Sample Request Body structure for POST and PUT operations:

```
{
  "backOffInterval": 0,
  "description": "string",
  "id": "string",
  "initialRetryInterval": 0,
  "maxRetryAttempt": 0,
  "maxRetryCycles": 0,
  "maxRetryInterval": 0,
  "name": "string",
  "ruleFailureCode": [
```

```

    "AN_GW_FAILED"
  ]
}

```

Sample Response Body structure for GET, POST and PUT operations:

```

{
  "backOffInterval": 0,
  "description": "string",
  "id": "string",
  "initialRetryInterval": 0,
  "maxRetryAttempt": 0,
  "maxRetryCycles": 0,
  "maxRetryInterval": 0,
  "name": "string",
  "ruleFailureCode": [
    "AN_GW_FAILED"
  ]
}

```

Export/Import Retry Profile for ADC

Table 2-113 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
date	string		Current timestamp
errors	array		
errors:message	string		
errors:name	string		
exportData	array	M	Exported list of ADC retry profile.
key	string		Indicates the ID
sourceVersion	string		System version of the product from which data is exported
topic	string	M	Topic of each managed object

Sample Request Body structure for Import/Export operations:

```

{
  "date": "string",
  "errors": [
    {
      "message": "string",
      "name": "string"
    }
  ],
  "exportData": [
    {
      "backOffInterval": 0,

```

```

        "description": "string",
        "id": "string",
        "initialRetryInterval": 0,
        "maxRetryAttempt": 0,
        "maxRetryCycles": 0,
        "maxRetryInterval": 0,
        "name": "string",
        "ruleFailureCode": [
            "AN_GW_FAILED"
        ]
    }
],
"key": "string",
"sourceVersion": "string",
"topic": "string"
}

```

Delete Retry Profile for ADC

Table 2-114 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
adcRetryProfileName	string	M	ADC Retry Profile Name

2.22 Site Takeover

This section describes the service URIs available to create and configure sites for takeover for Policy.

Table 2-115 Supported REST APIs for Site Takeover

Description	HTTP Method or Custom Operation	Resource URI	Possible Result Code
Export Site Takeovers	GET	{apiRoot}/oc-cnpolicy-configuration/v1/services/common/sitetakeover/export	See Table A-1
Import Site Takeovers	POST	{apiRoot}/oc-cnpolicy-configuration/v1/services/common/sitetakeover/import	See Table A-3

Export or Import Site Takeover

Table 2-116 Response Body Parameters for Import Request

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
date	string	O	Specifies the current timestamp
errors:message	string	O	Specifies the error message.
errors:name	string	O	Specifies the name of the error.
exportData	array	M	Exported Site Takeover. For more information, see Table 2-92 .
key	string	O	Indicates the ID of Site Takeover
sourceVersion	string	O	System version of product from which data is exported
topic	string	M	Topic of each managed object

Sample Request Body structure for Import and Export operations:

```
{
  "date": "string",
  "errors": [
    {
      "message": "string",
      "name": "string"
    }
  ],
  "exportData": [
    {
      "name": "site1",
      "targetSiteId": "siteid12345"
    }
  ]
}
```

2.23 NF Profile

Table 2-117 Supported REST APIs

Description	HTTP Method or Custom Operation	Resource URI	Possible Result Code
Create the NF Profile	POST	/oc-cnpolicy-configuration/v1/services/common/producer-nfprofile/{NFType}	See Table A-3

Table 2-117 (Cont.) Supported REST APIs

Description	HTTP Method or Custom Operation	Resource URI	Possible Result Code
Update the NF Profile	PUT	/oc-cnpolicy-configuration/v1/services/common/producer-nfprofile/{NFType}/{nfInstanceId}	See Table A-2
Delete the NF Profile	DELETE	/oc-cnpolicy-configuration/v1/services/common/producer-nfprofile/{NFType}/{nfInstanceId}	See Table A-4
Get All nfInstanceIds	GET	/oc-cnpolicy-configuration/v1/services/common/producer-nfinstanceids/{NFType}	See Table A-1
Get a NF Profile	GET	/oc-cnpolicy-configuration/v1/services/common/producer-nfprofile/{NFType}/{nfInstanceId}	See Table A-1

Table 2-118 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M) / Optional(O) Conditional(C)	Description
nfInstanceId	NfInstanceId	M	Unique identity of the NF Instance.
nfType	NFType	M	Type of Network Function
nfStatus	NFStatus	M	Status of the NF Instance
heartBeatTimer	Integer	C	Time in seconds expected between two consecutive heartbeat messages from an NF Instance to the NRF.
plmnList	array(PlmnId)	C	PLMN(s) of the Network Function
sNssais	array(Snssai)	O	S-NSSAIs of the Network Function.
perPlmnSnssaiList	array(PlmnSnssai)	O	List of S-NSSAIs supported by the Network Function for each PLMN.
nsiList	array(string)	O	NSI identities of the Network Function.
fqdn	Fqdn	C	FQDN of the Network Function
interPlmnFqdn	Fqdn	C	Specifies the FQDN that is used for inter-PLMN routing, if the NF needs to be discoverable by other NFs in a different PLMN.
ipv4Addresses	array(Ipv4Address)	C	IPv4 address(es) of the Network Function

Table 2-118 (Cont.) Request/Response Body Parameters

Field Name	Data Type	Mandatory(M) / Optional(O) Conditional(C)	Description
ipv6Addresses	rarray(Ipv6Addr)	C	IPv6 address(es) of the Network Function
allowedPlmns	array(PlmnId)	O	PLMNs allowed to access the NF instance.
allowedNfTypes	array(NFType)	O	Type of the NFs allowed to access the NF instance.
allowedNfDomains	array(string)	O	Pattern representing the NF domain names allowed to access the NF instance. If not provided, any NF domain is allowed to access the NF.
allowedNssais	array(Snssai)	O	S-NSSAI of the allowed slices to access the NF instance.
priority	integer	O	Priority (relative to other NFs of the same type) in the range of 0-65535, to be used for NF selection; lower values indicate a higher priority.
capacity	integer	O	Static capacity information in the range of 0-65535, expressed as a weight relative to other NF instances of the same type.
load	integer	O	Dynamic load information, ranged from 0 to 100, indicates the current load percentage of the NF.
locality	string	O	Operator defined information about the location of the NF instance (e.g. geographic location, data center)
udrInfo	UdrInfo	O	Specific data for the UDR (ranges of SUPI, group ID ...)
groupId	NfGroupId	O	Identity of the UDM group that is served by the UDM instance. If not provided, the UDM instance does not pertain to any UDM group.
supiRanges	array(SupiRange)	O	List of ranges of SUPIs whose profile data is available in the UDM instance.
gpsiRanges	array(IdentityRange)	O	List of ranges of GPSIs whose profile data is available in the UDM instance.
externalGroupIdentifiersRanges	array(IdentityRange)	O	List of ranges of external groups whose profile data is available in the UDM instance
supportedDataSets	array(DataSetId)	O	List of supported data sets in the UDR instance. If not provided, the UDR supports all data sets.
bsfInfo	BsfInfo	O	Specific data for the BSF
ipv4AddressRanges	array(Ipv4AddressRange)	O	List of ranges of IPv4 addresses handled by BSF. If not provided, the BSF can serve any IPv4 address.
dnnList	array(Dnn)	O	List of DNNs handled by the BSF. If not provided, the BSF can serve any DNN.
ipDomainList	array(string)	O	List of IPv4 address domains.
ipv6PrefixRanges	array(Ipv6PrefixRange)	O	List of ranges of IPv6 prefixes handled by the BSF. If not provided, the BSF can serve any IPv6 prefix.
chfInfo	ChfInfo	O	specific data for the CHF.
gpsiRangeList	array(IdentityRange)	O	List of ranges of GPSI that can be served by the CHF instance. If not provided, the CHF can serve any GPSI.

Table 2-118 (Cont.) Request/Response Body Parameters

Field Name	Data Type	Mandatory(M) / Optional(O) Conditional(C)	Description
customInfo	Object	O	Specific data for custom Network Functions
nfProfileChangesSupportInd	boolean	O	NF Profile Changes Support Indicator. This parameter indicates if the NF Service Consumer supports receiving NF Profile Changes in the response or not.
nfProfileChangesInd	boolean	O	NF Profile Changes Indicator. This parameter indicates if the NF Profile contains NF Profile changes or the complete NF Profile.

Sample request body:

```
{
  "nfInstanceId": "3fa85f64-5717-4562-b3fc-2c963f66afa",
  "nfType": "BSF",
  "nfStatus": "REGISTERED",
  "heartBeatTimer": 0,
  "plmnList": [
    {
      "mcc": "string",
      "mnc": "string"
    }
  ],
  "sNssais": [
    {
      "sst": 0,
      "sd": "string"
    }
  ],
  "perPlmnSnsaiList": [
    {
      "plmnId": {
        "mcc": "string",
        "mnc": "string"
      },
      "sNssaiList": [
        {
          "sst": 0,
          "sd": "string"
        }
      ]
    }
  ],
  "nsiList": [
    "string"
  ],
  "fqdn": "string",
  "interPlmnFqdn": "string",
}
```

```

"ipv4Addresses": [
  "string"
],
"ipv6Addresses": [
  "string"
],
"allowedPlmns": [
  {
    "mcc": "string",
    "mnc": "string"
  }
],
"allowedNfTypes": [
  "string"
],
"allowedNfDomains": [
  "string"
],
"allowedNssais": [
  {
    "sst": 0,
    "sd": "string"
  }
],
"priority": 0,
"capacity": 0,
"load": 0,
"locality": "string",
"udrInfo": {
  "groupId": "string",
  "supiRanges": [
    {
      "start": "string",
      "end": "string",
      "pattern": "string"
    }
  ],
  "gpsiRanges": [
    {
      "start": "string",
      "end": "string",
      "pattern": "string"
    }
  ],
  "externalGroupIdentifiersRanges": [
    {
      "start": "string",
      "end": "string",
      "pattern": "string"
    }
  ],
  "supportedDataSets": [
    "APPLICATION"
  ]
},
"bsfInfo": {

```

```

    "ipv4AddressRanges": [
      {
        "start": "string",
        "end": "string"
      }
    ],
    "dnnList": [
      "string"
    ],
    "ipDomainList": [
      "string"
    ],
    "ipv6PrefixRanges": [
      {
        "start": "string",
        "end": "string"
      }
    ]
  },
  "chfInfo": {
    "supiRangeList": [
      {
        "start": "string",
        "end": "string",
        "pattern": "string"
      }
    ],
    "gpsiRangeList": [
      {
        "start": "string",
        "end": "string",
        "pattern": "string"
      }
    ]
  },
  "customInfo": {},
  "recoveryTime": "string",
  "nfServicePersistence": true,
  "nfServices": [
    {
      "serviceInstanceId": "string",
      "serviceName": "string",
      "versions": [
        {
          "apiVersionInUri": "string",
          "apiFullVersion": "string",
          "expiry": "string"
        }
      ],
      "scheme": "http",
      "nfServiceStatus": "REGISTERED",
      "fqdn": "string",
      "ipEndpoints": [
        {
          "ipv4Address": "string",
          "ipv6Address": "string",

```

```

        "transport": "TCP",
        "port": 0
      }
    ],
    "apiPrefix": "string",
    "allowedNfTypes": [
      "string"
    ],
    "priority": 0,
    "capacity": 0,
    "load": 0
  }
],
"nfProfileChangesSupportInd": true,
"nfProfileChangesInd": true
}

```

Sample response body:

```

{
  "nfInstanceId": "3fa85f64-5717-4562-b3fc-2c963f66afa9",
  "nfType": "BSF",
  "nfStatus": "REGISTERED",
  "heartBeatTimer": 0,
  "plmnList": [
    {
      "mcc": "string",
      "mnc": "string"
    }
  ],
  "sNssais": [
    {
      "sst": 0,
      "sd": "string"
    }
  ],
  "perPlmnSnssaiList": [
    {
      "plmnId": {
        "mcc": "string",
        "mnc": "string"
      },
      "sNssaiList": [
        {
          "sst": 0,
          "sd": "string"
        }
      ]
    }
  ],
  "nsiList": [
    "string"
  ],
  "fqdn": "string",
  "interPlmnFqdn": "string",

```

```

"ipv4Addresses": [
  "string"
],
"ipv6Addresses": [
  "string"
],
"allowedPlmns": [
  {
    "mcc": "string",
    "mnc": "string"
  }
],
"allowedNfTypes": [
  "string"
],
"allowedNfDomains": [
  "string"
],
"allowedNssais": [
  {
    "sst": 0,
    "sd": "string"
  }
],
"priority": 0,
"capacity": 0,
"load": 0,
"locality": "string",
"udrInfo": {
  "groupId": "string",
  "supiRanges": [
    {
      "start": "string",
      "end": "string",
      "pattern": "string"
    }
  ],
  "gpsiRanges": [
    {
      "start": "string",
      "end": "string",
      "pattern": "string"
    }
  ],
  "externalGroupIdentifiersRanges": [
    {
      "start": "string",
      "end": "string",
      "pattern": "string"
    }
  ],
  "supportedDataSets": [
    "APPLICATION"
  ]
},
"bsfInfo": {

```

```

    "ipv4AddressRanges": [
      {
        "start": "string",
        "end": "string"
      }
    ],
    "dnnList": [
      "string"
    ],
    "ipDomainList": [
      "string"
    ],
    "ipv6PrefixRanges": [
      {
        "start": "string",
        "end": "string"
      }
    ]
  },
  "chfInfo": {
    "supiRangeList": [
      {
        "start": "string",
        "end": "string",
        "pattern": "string"
      }
    ],
    "gpsiRangeList": [
      {
        "start": "string",
        "end": "string",
        "pattern": "string"
      }
    ]
  },
  "customInfo": {},
  "recoveryTime": "string",
  "nfServicePersistence": true,
  "nfServices": [
    {
      "serviceInstanceId": "string",
      "serviceName": "string",
      "versions": [
        {
          "apiVersionInUri": "string",
          "apiFullVersion": "string",
          "expiry": "string"
        }
      ],
      "scheme": "http",
      "nfServiceStatus": "REGISTERED",
      "fqdn": "string",
      "ipEndpoints": [
        {
          "ipv4Address": "string",
          "ipv6Address": "string",

```

```

        "transport": "TCP",
        "port": 0
    },
    "apiPrefix": "string",
    "allowedNfTypes": [
        "string"
    ],
    "priority": 0,
    "capacity": 0,
    "load": 0
}
],
"nfProfileChangesSupportInd": true,
"nfProfileChangesInd": true
}

```

2.24 Session Management Service

Table 2-119 Supported REST APIs

Description	HTTP Method or Custom Operation	Resource URI	Possible Result Code
Get Session Management Service	GET	{apiRoot}/oc-cnpolicy-configuration/v1/services/pcfsm	See Table A-1
Update Session Management Service	PUT	{apiRoot}/oc-cnpolicy-configuration/v1/services/pcfsm	See Table A-2
Export Session Management Service	GET	{apiRoot}/oc-cnpolicy-configuration/v1/services/pcfsm/export	See Table A-1
Import Session Management Service	POST	{apiRoot}/oc-cnpolicy-configuration/v1/services/pcfsm/import	See Table A-3

Get and Update Session Management Service

Table 2-120 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/Optional(O)	Description
system	SystemConfiguration	O	
user	SmUserConfiguration	O	
policy	Policy	O	
policyControlRequestTrigger	PolicyControlRequestTrigger	O	
binding	SmBindingConfiguration	O	
qos	QOSConfiguration	O	

Table 2-120 (Cont.) Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)	Description
qosMonitoring	QoSMonitoring	O	Enables to configure QoS Monitoring feature
rule	RuleConfiguration		
charging	ChargingConfigurati on	O	
trafficControl	TrafficControlConfigu ration	O	
imsEmergencySession	IMSEmergencySessi onConfiguration	O	
audit	AuditConfiguration	O	
extendedAudit	AuditExtendedConfi guration	O	
pendingTransaction	PendingTransaction Configuration	O	
nwdaf	SmNwdafConfigurati on	O	
overloadConfiguration	Overload Configuration	O	
defaultProcessing	Default Processing configuration for SM service	O	Default Processing configuration for SM service
messagePriority	MessagePriority	O	To configure Message Priority for SM Call flows.
advancedSettings	AdvancedSettings	M	

Table 2-121 SystemConfiguration

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
componentTracing Enabled	Boolean	O	Determines if component tracing is enabled. Component tracing is used to evaluate system process latency in detail level. Default Value: false
pcf_fqdn	string	O	This is the PCF FQDN used by the PCF to register Binding data to BSF. AF may use this FQDN to communicate with PCF on N5 reference point. Default Value: pcf-smervice.pcf
pcf_diamrealm	string	O	This is the PCF diameter realm used by the PCF to register Binding data to BSF. Diameter based AF may use this diameter realm to communicate with PCF on Rx reference point. Default Value: pcf-smervice.svc

Table 2-121 (Cont.) SystemConfiguration

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
pcf_diamidentity	string	O	This is the PCF diameter identity used by the PCF to register Binding data to BSF. Diameter based AF may use this diameter identity to communicate with PCF on Rx reference point. Default Value: pcf-smsservice.svc
snssai	string	O	This is the PCF SNSSAI used by the PCF to register Binding data to BSF. AF/BSF may use this SNSSAI to discover proper PCF. Format: sst,sd. Default Value: 0-000000
metricsEnabled	Boolean	O	This determines if system metrics is enabled. This will take priority on global metrics config. Default Value: true
smfNotificationRetryProfile	string	O	Defines the retry profile configuration for session management.
overrideSupportedFeatures	string, array	O	Specifies the list of supported features that can be configured to override system embedded values. For example: • SessionRuleErrorHandling • NetLoc • PolicyDecisionErrorHandling • QoSMonitoring • ResShare • 3GPP-PS-Data_Off • ADC • UMC • RAN-NAS-Cause • ProvAFsignalFlow Note: If any supported feature is enabled in one site then the same needs to be enabled on all other sites at the same time.
enableCustomJson	Boolean	O	Specifies either to enable or disable customized JSON file reading.
nfCommProfile	string	O	Specifies the NF communication profile used by SMF.
dataCompressionScheme	string	O	Specifies the data compression scheme used by SM. Following are the allowed values for this field: • Disabled • MySQL_Compressed • Zlib_Compressed By default, this value remains disabled.

Table 2-121 (Cont.) SystemConfiguration

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
dbEncodingEnabled	Boolean	O	Specifies either to enable or disable database encoding. Default Value: false
rxReauthProfileForRxCreate	String	O	Specifies the selection of the Rx Reauth Profile for Update Notify Failures happens due to Rx Create Request. Allowed Value: String (Only one profile) Default Value: Empty
rxReauthProfileForRxUpdate	String	O	Specifies the selection of the Rx Reauth Profile for Update Notify Failure happens due to Rx Update Request. Allowed Value: String (Only one profile) Default Value: Empty

Table 2-122 SmUserConfiguration

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
validateUser	Boolean	O	Determines if user validate is enabled. HTTP 400 with cause USER_UNKNOWN returns, if this is enabled and user not found in UDR. Default Value: FALSE
queryUser	Boolean	O	Determines if user query from UDR is enabled. Default Value: TRUE
queryUserOnUpdate	Boolean	O	Determines if user query from UDR on update is enabled. Default Value: FALSE
queryUserOnDelete	Boolean	O	Determines if user query from UDR on delete is enabled. Default Value: FALSE
queryUserOnReauth	Boolean	O	Determines if user query from UDR on reauth is enabled. Default Value: FALSE
subsToNotifyEnabled	Boolean	O	Determines if subscribe to notify about subscriber data change is enabled. Default Value: true
ignoreSubsNotificationCheck	Boolean	O	Ignore subscriber's notification check. Default Value: false Note: Currently, this field is not used by the Policy application.
enableChfQueryAll	Boolean	O	Determines whether to enable on-demand retrieval of policy counters for a subscriber from OCS synchronously.
enableAsyncChfQuery	Boolean	O	Determines whether to enable on-demand retrieval of policy counters for a subscriber from OCS asynchronously.

Table 2-122 (Cont.) SmUserConfiguration

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
enableOcsQueryAll	Boolean	O	Determines whether to fetch policy counters for a subscriber from OCS.
forceLookupOcsDataOnSmUpdate	Boolean	O	Determines whether to perform force lookup for OCS Data. Default Value: false
enableSmDataQuery	Boolean	O	
enableOsdQuery	Boolean		Determines whether to perform on demand lookup for Policy Counters to be fetched from OCS. Default Value: false
includeSnssaiInUserQuery	Boolean	O	Determines if Snssai is included for SmPolicyData for PCF query and subscribe to UDR for Notification.
includeDnnInUserQuery	Boolean	O	Determines if Dnn is included for SmPolicyData for PCF query and subscribe to UDR for Notification.
disableSubscriberVariables	Boolean	O	Determines if subscriber variables are stored or not in the PCF database. Default Value: false
ldapData.enable	Boolean	O	PCF fetches user profile from LDAP through PDS. Default Value: false
operatorSpecificData.subscribeToNotify	Boolean	O	PCF fetches OperatorSpecificData (imported using Custom Schema) from UDR.

Table 2-123 Policy

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
evaluateEnabled	Boolean	O	This determines if policy evaluation is enabled or not. Default Value: TRUE

Table 2-124 PolicyControlRequestTrigger

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
defaultPolicyControlRequestTriggers	defaultPolicyControlRequestTriggers [string, ENUM]	O	Default Policy Control Request Trigger(s) to install on PDU session at SM Policy association establishment. This is a comma split string. Example: [PLMN_CH, RES_MO_RE, AC_TY_CH, UE_IP_CH, UE_MAC_CH, AN_CH_COR, US_RE, APP_STA, APP_STO, AN_INFO, CM_SES_FAIL, PS_DA_OFF, DEF_QOS_CH, SE_AMBR_CH, QOS_NOTIF, NO_CREDIT, PRA_CH, SAREA_CH, SCNN_CH, RE_TIMEOUT, RES_RELEASE, SUCC_RES_ALLO, RAT_TY_CH, REF_QOS_IND_CH, SCELL_CH]

Table 2-125 SmBindingConfiguration

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
bsfRetryProfileForInitMsgs	string	O	Retry Profile to be used when PCF fails to send a create message to a producer node.
bindingOperationEnabled	Boolean	O	This determines if binding operation (register and deregister) to the BSF is enabled. Default Value: TRUE
useLocalConfiguredBsfAlways	Boolean	O	Whether to use local configured BSF without Always discovering. Default Value: FALSE
useLocalConfiguredBsfWhenNotDiscovered	Boolean	O	Whether to use local configured (if having) BSF when not discovered or discover failed. Default Value: FALSE
useHttp2	Boolean	O	Determines if using http/2 to communicate with BSF. Otherwise use http/1.1. Default Value: TRUE
abortOnBindingError	Boolean	O	Determines if PCF (SM service) should abort terminate session when binding error is received.

Table 2-125 (Cont.) SmBindingConfiguration

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
bsfRetryProfileForSubsqMsgs	string	O	Retry Profile to be used when PCF fails to send an in-session message to a producer node. Note: • If both “Retry Profile for Initial Messages” and “Retry Profile for Subsequent Messages” are not configured (default case) no retry is attempted. • If both “Retry Profile for Initial Messages” and “Retry Profile for Subsequent Messages” are configured, retries is attempted accordingly. • If “Retry Profile for Initial Messages” is configured but “Retry Profile for Subsequent Messages” is not configured then the profile for initial messages is used for subsequent messages. (to be backward compatible with release 1.8.x) • If “Retry Profile for Initial Messages” is not configured but “Retry Profile for Subsequent Messages” is configured then retry is not attempted for initial messages but is attempted for subsequent messages.
bsfRecreateAttemptState	string	O	Specifies to either enable or disable the BSF recreate attempts functionality. The possible values: Enabled Disable Disable and Cleanup
bsfReattemptProfile	string	O	Specifies the reattempt profile to be used for binding recreate attempts.
bsfNfCommProfile	string	O	Specifies the NF communication profile used by BSF.

Table 2-125 (Cont.) SmBindingConfiguration

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
defaultBindingOperationMode	ENUM	O	Allows users to configure binding operation mode as synchronous or asynchronous. Note: The mode chosen during the CREATE request remains same during UPDATE and TERMINATE operations for the same SM session. The default binding operation mode is set to synchronous. Note: To ensure backward compatibility, if this attribute is not available in the database, the value is set to "Synchronous" After performing necessary configurations, user may use the policy action - Set Binding Registration Mode to update configurations for specific policies. For more information, see <i>Oracle Communications Cloud Native Core, Converged Policy Design Guide</i>.
fqdnIpEndpointsConfiguration	String	M	Determines if Service FQDN and IP Endpoints are sent to BSF in the PCF Binding registration request. Possible values: - SERVICE_FQDN - SERVICE_FQDN_AND_ENDPOINTS - SERVICE_ENDPOINTS Default: SERVICE_FQDN
fqdnIpEndpointsProfile	String	M	Determines from which NF Profile are the FQDN and IP Endpoints going to be taken from. Possible Values: - npcf-policyauthorization - npcf-smpolicycontrol Default: npcf-smpolicycontrol

Table 2-126 QOSConfiguration

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)ain ts	Description
defaultQos5qi	string	O	This is the 5Qi of default Qos which will be applied if no default Qos is requested by UE. Default Value: 9

Table 2-126 (Cont.) QOSConfiguration

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)ain ts	Description
defaultQosArpPreemptCap	ENUM	O	This is the ARP PreemptionCapability of default Qos which will be applied if no default Qos is requested by UE. Default Value: MAY_PREEMPT
defaultQosArpPreemptVuln	ENUM	O	This is the ARP PreemptionVulnerability of default Qos which will be applied if no default Qos is requested by UE. Default Value: NOT_PREEMPTABLE
defaultQosArpPriorityLevel	string	O	This is the ARP Priority Level of default Qos which will be applied if no default Qos is requested by UE. Default Value: 1
installDefQosIfNotRequested	Boolean	O	This determines whether to install default Qos to the PDU session if UE not requested Default Value: TRUE
qosDataIdPrefix	string	O	This is the prefix of qos data id used by PCF to generate qos data id. For example, prefix is "qosdata_", the generated qos data id is qosdata_0, chgdata_1, etc. Default Value: qosdata_
updateDefaultPcfRuleWithAuthDefQos	Boolean	O	This determines whether to update Qos of default PccRule with the authDefQos of session rule. Default Value: TRUE

Table 2-127 QoS Monitoring

Field Name	Data Type	Mandatory(M)/ Optional(O)	Description
qosMonitoring.notificationTarget	String	O	Specifies the target for notifications that SMF triggers when PCF subscribes to QoS Monitoring.

Table 2-128 RuleConfiguration

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)ain ts	Description
appRulePrecedenceMax	string	O	This value defines the maximum value for precedence of a PCC rule as authorized by the establishment of an application flow by the AF. If multiple rules are applied to the same packet flow or UE resource (that is., overlapping rules) a rule with lower precedence value takes the priority over a rule with higher precedence value. The value of -1 is used to not set the precedence of a rule (NOT RECOMMENDED). Default Value: 899
appRulePrecedenceMin	string	O	This value defines the minimum value for precedence of a PCC rule as authorized by the establishment of an application flow by the AF. If multiple rules are applied to the same packet flow or UE resource (that is., overlapping rules) a rule with lower precedence value takes the priority over a rule with higher precedence value. The value of -1 is used to not set the precedence of a rule (NOT RECOMMENDED). Default Value: 400
defaultPccRule5qi	string	O	This is the 5Qi of default pcc rule. Default Value: 9
defaultQosArpPriorityLevel	string	O	This is the ARP Priority Level of qos of default pcc rule The range is 1 to 15. Values are ordered in decreasing order of priority, for example, with 1 as the highest priority and 15 as the lowest priority. Default Value: 15
defaultPccRuleArpPreemptCap	ENUM	O	This is the ARP PreemptionCapability of qos of default PCC rule. - NOT_PREEMPT - MAY_PREEMPT Default Value: NOT_PREEMPT
defaultPccRuleArpPreemptVuln	ENUM	O	This is the ARP PreemptionVulnerability of qos of default pcc rule. - PREEMPTABLE - NOT_PREEMPTABLE Default Value: PREEMPTABLE
defaultPccRuleArpPriorityLevel	string example: 15	O	This is the ARP Priority Level of qos of default pcc rule The range is 1 to 15. Values are ordered in decreasing order of priority, for example, with 1 as the highest priority and 15 as the lowest priority. Default Value: 15
defaultPccRulePrecedence	string	O	This is the precedence of default pcc rule. Default Value: 3000

Table 2-128 (Cont.) RuleConfiguration

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)ain ts	Description
installDefaultPccRule	ENUM	O	This determine whether and how to install default pcc rule for a PDU session • ALWAYS • IF_NO_PROVISIONED_RULE: Only if no other provisioned rule is configured • IF_NO_RULE: Only if no other rule (predefined or provisioned) is configured/installed • NEVER Default Value: IF_NO_RULE
defaultPccRuleProfile	string	O	If a default PCC Rule Profile is configured by the user, it is applied to the chosen PCC Rule.
ruleIdPrefix	string	O	This is the prefix of rule id of the pcc rule or session rule auto generated by PCF. for example, prefix is "0_", the generated rule id is 0_0, 0_1, etc. Default Value: 0_
switchFlowInToOutEnabled	Boolean	O	This determines whether to switch "in" to "out" in flow description. The src and desc will be switched as well. For example, if enabled, "permit in ip from 2800:a00:cc01:c056:1c00:de10:c481:f193/128 to 2800:a00:800:7::1:3b/128 36004" will be changed to "permit out ip from 2800:a00:800:7::1:3b/128 36004 to 2800:a00:cc01:c056:1c00:de10:c481:f193/128" Default Value: FALSE
packetFilterUsageToTrueForPreliminaryServiceInfo	string	O	
ruleConflictsStrategy	string	O	
setPacketFilterUsageToTrueForPreliminaryServiceInfo	Boolean	O	
defaultPolicyControlRequestTriggers	string, ENUM	O	This is the default Policy Control Request Trigger(s) to install on PDU session at SM Policy association establishment. This is a comma split string.
defaultPccRuleRequestedRuleData	string, ENUM	O	

Table 2-129 ChargingConfiguration

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
chgDataIdPrefix	string	O	This is the prefix of chg data id used by PCF to generate chg data id. For example, prefix is "chgdata_", the generated chg data id is chgdata_0, chgdata_1, etc. Default Value: chgdata_
offline	Boolean	O	Indicates the offline charging is applicable to the PDU session.
online	Boolean	O	Indicates the online charging is applicable to the PDU session.
primaryChfAddress	string	O	Specifies the primary CHF address.
primaryChfInstanceld	string	O	Specifies the Instance ID of the primary CHF.
primaryChfSetId	string	O	Specifies the Set ID of the primary CHF.
secondaryChfAddress	string	O	Specifies the secondary CHF address.
secondaryChfInstanceld	string	O	Specifies the Instance ID of the secondary CHF.
secondaryChfSetId	string	O	Specifies the Set ID of the secondary CHF.
useSubscriberDefChgMethod	Boolean	O	Indicates whether to use the online value defined in the PDU session. Default Value: true

Table 2-130 TrafficControlConfiguration

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
tcDataIdPrefix	string	O	This is the prefix of traffic control data id used by PCF to generate tc data id. For example, prefix is "tcdata_", the generated tc data id is tcdata_0, tcdata_1, etc. Default Value: tcdata_

Table 2-131 IMSEmergencySessionConfiguration

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
arpPreemptCap	ENUM	M	Defines whether a service data flow may get resources that were already assigned to another service data flow with a lower priority level. Default Value: MAY_PREEMPT
arpPreemptVuln	Boolean	M	Defines whether a service data flow may lose the resources assigned to it in order to admit a service data flow with higher priority level. Default Value: NOT_PREEMPTABLE
arpPriorityLevel	integer (\$int32)	O	Defines the relative importance of a resource request. Default Value: 1
Any number of values are permitted for Emergency DNNs	string	O	DNN included in the request from SMF to PCF to establish an emergency session.

Table 2-132 AuditConfiguration

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
audit.enable	Boolean	O	Determines whether to send registration request to Audit service or not. Default Value: true
audit.frequency	integer	M	Defines the time when next audit for the SM service table begins after delta time if auditing this table has been finished before this specified time. Default Value: 330

Table 2-132 (Cont.) AuditConfiguration

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
audit.maxTtl	integer	M	Defines the maximum age of a SM policy association after which a record is purged from PCF SM database without sending further queries to SM. Default Value: 2880
audit.notificationRate	integer	M	Defines the number of stale records which Audit service will notify to Session Management (SM) service in one second. Default Value: 50 Note: To configure higher number than the recommended value, contact My Oracle Support (https://support.oracle.com).
audit.ttl	integer	M	Defines the age of a SM policy association after which a record is considered to be stale on PCF and the SMF is queried for presence of such associations. Default Value: 1440

Table 2-133 AuditExtendedConfiguration

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
pendingOperation	AuditPendingOperation	M	Pending Operation details.
smPolicyAssociation	AuditSmPolicyAssociation	M	SM Policy Association details.
tdfSession	AuditTdfSession	M	TDF Session details for Audit.

Table 2-134 AuditPendingOperation

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
notificationRate	integer	O	Defines the number of pending operation records which Audit service notifies to Session Management (SM) service in one second. Note: The notification rate for all the operations of Audit service remains the same. Policy does not allow to configure different values for different operations. Therefore, by default the notification rate configured for the SmPolicyAssociation section applies for Pending Operations . Default Value: 50
ttl	integer	O	Defines the age of a pending operation after which a record is considered to be stale. This is a non modifiable field. Default Value: 0
maxTtl	integer	O	Defines the maximum age of a pending operation after which a record is purged from PCF SM database without sending further queries to SM. Default Value: 2880
frequency	integer	O	Defines the frequency with which the Audit service performs audit of the pending operation table for the Retry Timestamps that have been reached. Default Value: 10
enableAlternateSite	Boolean	O	The site takeover profile.
alternateSiteId	string	O	Specifies if the site takeover must be enabled in case of failure.

Table 2-135 AuditSmPolicyAssociation

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
enable	Boolean	O	Determines whether to send registration request to Audit service or not. Default Value: True
notificationRate	integer	O	Defines the number of stale records which Audit service notifies to Session Management (SM) service in one second. Default and Recommended Value: 50 Note: To configure higher number than the recommended value, contact My Oracle Support (https://support.oracle.com)
ttl	integer	O	Defines the age of a SM policy association after which a record is considered to be stale on PCF and the SMF is queried for presence of such associations. Default Value: 1440
maxTtl	integer	O	Defines the maximum age of a SM policy association after which a record is purged from PCF SM database without sending further queries to SM. Default Value: 2880

Table 2-135 (Cont.) AuditSmPolicyAssociation

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
minAuditAttempts	integer	M	Specifies the minimum number of consecutive failed audit attempts until maxTTL / forceTTL is reached. If maxTTL is reached and audit_attempts + 1 >= Minimum Audit Attempts for maxTTL, Audit service sends notification to SM service with maxTTL flag set to <i>true</i>. SM Service sends DELETE request to PDS and Binding Service. Range: 0-99 Default Value: 0 Note: If maxTTL is not reached and if audit attempts are reached, the number of audit attempts are incremented until maxTTL is reached.
frequency	integer	O	Defines the time when next audit for the SM service table is done after delta time if auditing this table has been finished before this specified time. Default Value: 10

Table 2-136 AuditTdfSession

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
enable	Boolean	O	SM determines whether to send registration request to Audit service or not. Default Value: True

Table 2-136 (Cont.) AuditTdfSession

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
notificationRate	integer	O	Defines the number of TDF stale records which Audit service notifies to Session Management (SM) service in one second. Default Value: 50
ttl	integer	O	Defines the age of a TDF session after which a record is considered to be stale on PCF and the TDF is queried for presence of such associations. Default Value: 1440
maxTtl	integer	O	Defines the maximum age of a pending operation after which a record is purged from PCF SM database without sending further queries to SM. Default Value: 2880
minAuditAttempts	integer	M	Specifies the minimum number of consecutive failed audit attempts until maxTTL / forceTTL is reached. If maxTTL is reached and audit_attempts + 1 >= Minimum Audit Attempts for maxTTL, Audit service sends notification to SM service with maxTTL flag set to <i>true</i> . SM Service deletes stale TDF Session from TdfSession table. If maxTTL is not reached and if audit attempts are reached, the number of audit attempts are incremented until maxTTL is reached. Range: 0-99 Default Value: 0

Table 2-136 (Cont.) AuditTdfSession

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
frequency	integer	O	Defines the time frequency with which the Audit service performs audit for the stale sessions in TdfSession table. If the audit of TdfSession table is finished before this specified time, then next audit for this table happens after the delta time. Default Value: 10
queryTDF	Boolean	O	On true, SM sends a RAR request with Tdfsession toward TDF. On false, SM deletes the Tdfsession. Default Value: False

Table 2-137 PendingTransactionConfiguration

Field Name	Data Type	Mandatory(M)/ Optional(O)	Description
updateNotifyRetry Backoff	integer	M	Indicates the time between two consecutive retry UpdateNotify messages when UpdateNotify message is held back from being sent to SMF. The default value for this field is 1000.
updateNotifyRetry Count	integer	M	Indicates the count for UpdateNotify message to be retried when it is held back from sending to SMF. The default value for this field is 2.
errorUpdateNotifyH andlingApp	string	O	On Update Notify to SMF triggered by Rx, this configuration decides if it should RETRY (with UpdateNotifyRetryBackoff and UpdateNotifyRetryCount settings) or DISCARD when receiving 400 Pending Transaction response from SMF. The default value for this field is DISCARD. The allowed values are: - DISCARD (0) - RETRY (1)

Table 2-137 (Cont.) PendingTransactionConfiguration

Field Name	Data Type	Mandatory(M)/ Optional(O)	Description
updateNotifyHandling	string	O	On Update Notify to SMF triggered by Subscriber Notification, this configuration decides if it should RETRY (with UpdateNotifyRetryBackoff and UpdateNotifyRetryCount settings) or DISCARD when receiving 400 Pending Transaction response from SMF. The default value for this field is RETRY. The allowed values are: • DISCARD (0) • RETRY (1)

Table 2-138 SmNwdafConfiguration

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
enableNwdafData	Boolean	O	To enable or disable the Nwdaf data.

Table 2-139 overloadConfiguration

Field Name	Data Type	Mandatory(M)/ Optional(O)	Description
overloadConfiguration.enhancedOverloadControlLevel	Integer	O	Specifies the current status of the Enhanced Overload Control mechanism. It indicates whether advanced overload management features are active for this service. Possible Values: • -1 (DISABLED) • L1 • L2 • L3 • L4 • L5 • L6 • L7 • L8 • L9 • L10 Default Value: -1 DISABLED, L1, L2, L3 are the corresponding value of this parameter in UI. Note: Setting one of these different control level to either 1, 2, and 3 signifies that, if the configuration Control Level is set to 1, and the actual Load Level of SM service is either in L1 or above state (that is, L2 or L3), then only Enhanced Overload Actions will be applied. Similarly, if the Configuration control level is set to 2 and even if the service load Level of SM service is in L1 state, the Enhance Overload actions will not be applied. Once the system load level reaches L2, then the Overload actions will get applied. Similarly, if the configuration is in L3 state, then even if the SM service load level is in L1 or L2 state, enhance overload actions will not be performed.
overloadConfiguration.overloadConfigurationProfile	String	O	Specifies the name of the overload configuration profile assigned to this service. A profile includes specific rules for overload handling.

Table 2-140 defaultProcessing

Field Name	Data Type	Mandatory(M)/ Optional(O)	Description
defaultProcessing.smdpProfile	Integer	O	Select one of the default processing profiles created using Default Processing Profile API that must be applied for SM service.

Table 2-141 Message Priority Profile

Field Name	Data Type	Mandatory(M)/ Optional(O)	Description
messagePriority.messagePriorityProfile	String	O	Select one of the message priority profiles created on Message Profiles page that must be applied for SM Service. When a message profile is selected under Message Priority Profile section, support for 3GPP-SBI-Message-Priority header gets enabled for SM Service.

Table 2-142 AdvancedSettings

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
key	string	O	Specifies the key name.
value	string	O	Specifies the value of the key.

For more information on the Advanced Settings "Keys" and "Values", see "**Session Management Service**" section of "Configuring Policy Using CNC Console" in *Oracle Communications Cloud Native Core, Converged Policy User Guide*.

Sample Request body structure for POST operation:

```
{
  "system": {
    "componentTracingEnabled": false,
    "pcf_fqdn": "oc-diam-gateway",
    "pcf_diamrealm": "oracle.com",
    "pcf_diamidentity": "oc-diam-gateway",
    "metricsEnabled": true,
    "enableCustomJson": false,
    "dataCompressionScheme": "0",
    "dbEncodingEnabled": false
  },
  "user": {
    "validateUser": false,
    "queryUser": true,
    "queryUserOnUpdate": false,
  }
}
```

```

    "queryUserOnDelete": false,
    "queryUserOnReauth": false,
    "disableSubscriberVariables": false,
    "enableSmDataQuery": true,
    "subsToNotifyEnabled": false,
    "ignoreSubsNotificationCheck": false,
    "includeSnssaiInUserQuery": true,
    "includeDnnInUserQuery": true,
    "enableOsdQuery": false,
    "operatorSpecificData.subscribeToNotify": true,
    "ldapData.enable": false,
    "enableChfQueryAll": false,
    "enableAsyncChfQuery": false,
    "enableOcsQueryAll": false,
    "enableAsyncOcsQuery": false,
    "forceLookupOcsDataOnSmUpdate": false
  },
  "policy": {
    "evaluateEnabled": true
  },
  "policyControlRequestTrigger": {
    "defaultPolicyControlRequestTriggers": [
      "PLMN_CH",
      "UE_IP_CH",
      "DEF_QOS_CH",
      "AC_TY_CH"
    ]
  },
  "binding": {
    "bindingOperationEnabled": true,
    "useLocalConfiguredBsfAlways": false,
    "useLocalConfiguredBsfWhenNotDiscovered": true,
    "useHttp2": true,
    "abortOnBindingError": false,
    "defaultBindingOperationMode": "SYNCHRONOUS",
    "bsfRecreateAttemptState": "Disabled",
    "fqdnIpEndpointsConfiguration": "SERVICE_FQDN_AND_ENDPOINTS",
    "fqdnIpEndpointsProfile": "npcf-smpolicycontrol"
  },
  "qos": {
    "qosDataIdPrefix": "qosdata_",
    "updateDefaultPcfRuleWithAuthDefQos": true,
    "installDefQosIfNotRequested": true,
    "defaultQos5qi": "9",
    "defaultQosArpPreemptCap": "MAY_PREEMPT",
    "defaultQosArpPreemptVuln": "NOT_PREEMPTABLE",
    "defaultQosArpPriorityLevel": "1"
  },
  "qosMonitoring": {
    "notificationTarget": "AF/NEF"
  },
  "rule": {
    "installDefaultPccRule": "IF_NO_RULE",
    "ruleIdPrefix": "0_",
    "defaultPccRule5qi": "9",
    "defaultPccRulePrecedence": "3000",

```

```

"defaultPccRuleArpPreemptCap": "NOT_PREEMPT",
"defaultPccRuleArpPreemptVuln": "PREEMPTABLE",
"appRulePrecedenceMin": "400",
"appRulePrecedenceMax": "899",
"defaultPccRuleArpPriorityLevel": "15",
"switchFlowInToOutEnabled": false,
"setPacketFilterUsageToTrueForPreliminaryServiceInfo": false,
"ruleConflictsStrategy": ""
},
"charging": {
  "chgDataIdPrefix": "chgdata_",
  "useSubscriberDefChgMethod": true
},
"trafficControl": {
  "tcDataIdPrefix": "tcdata_"
},
"imsEmergencySession": {
  "arpPriorityLevel": 1,
  "arpPreemptCap": "MAY_PREEMPT",
  "arpPreemptVuln": "NOT_PREEMPTABLE"
},
"extendedAudit": {
  "smPolicyAssociation": {
    "enable": true,
    "notificationRate": 50,
    "ttl": 1440,
    "maxTtl": 2880,
    "minAuditAttempts": 0,
    "frequency": 10
  },
  "pendingOperation": {
    "notificationRate": 50,
    "ttl": 0,
    "maxTtl": 2880,
    "frequency": 10,
    "enableAlternateSite": false
  },
  "tdfSession": {
    "enable": true,
    "queryTDF": false,
    "notificationRate": 50,
    "ttl": 1440,
    "maxTtl": 2880,
    "minAuditAttempts": 0,
    "frequency": 10
  }
},
"pendingTransaction": {
  "updateNotifyRetryBackoff": 1000,
  "updateNotifyRetryCount": 2,
  "errorUpdateNotifyHandlingApp": "0",
  "updateNotifyHandling": "1"
},
"nwdaf": {
  "enableNwdafData": false
},

```

```

    "overloadConfiguration": {
      "enhancedOverloadControlLevel": -1
    },
    "messagePriority": {
      "messagePriorityProfile": "string"
    },
    "advancedSettings": []
  }

```

Export/Import Session Management Service

Table 2-143 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
date	string		Current timestamp
errors:message	string		
errors:name	string		
exportData	array		Exported list of session management service. For more information, see Get and Update Session Management Service .
sourceVersion	string		System version of product from which data is exported
topic	string		Topic of each managed object

Sample Request Body structure for Import/Export operations:

```

{
  "topic": "string",
  "sourceVersion": "string",
  "date": "string",
  "exportData": {
    "system": {
      "componentTracingEnabled": false,
      "": "This is the PCF diameter identity used by the PCF to register Binding data to BSF. Diameter based AF may use this diameter identity to communicate with PCF on Rx reference point",
      "snssai": "This is the PCF SNSSAI used by the PCF to register Binding data to BSF. AF/BSF may use this SNSSAI to discover proper PCF",
      "metricsEnabled": true,
      "overrideSupportedFeatures": [
        "Tsc"
      ],
      "enableCustomJson": true,
      "smfNotificationRetryProfile": "string",
      "nfCommProfile": "string",
      "dataCompressionScheme": "string",
      "dbEncodingEnabled": true,
      "rxReauthProfileForRxCreate": "string",

```



```

    "rxReauthProfileForRxUpdate": "string"
  },
  "user": {
    "validateUser": false,
    "queryUser": true,
    "queryUserOnUpdate": false,
    "queryUserOnDelete": false,
    "queryUserOnReauth": false,
    "subsToNotifyEnabled": false,
    "ignoreSubsNotificationCheck": false,
    "enableChfQueryAll": true,
    "enableOcsQueryAll": true,
    "enableAsyncChfQuery": true,
    "enableAsyncOcsQuery": true,
    "forceLookupOcsDataOnSmUpdate": false,
    "enableSmDataQuery": true,
    "enableOsdQuery": false,
    "includeSnssaiInUserQuery": true,
    "includeDnnInUserQuery": true,
    "disableSubscriberVariables": false,
    "ldapData.enable": false,
    "operatorSpecificData.subscribeToNotify": true
  },
  "policy": {
    "evaluateEnabled": true
  },
  "policyControlRequestTrigger": {
    "defaultPolicyControlRequestTriggers": [
      "PLMN_CH"
    ]
  },
  "binding": {
    "bindingOperationEnabled": true,
    "useLocalConfiguredBsfaAlways": true,
    "useLocalConfiguredBsfaWhenNotDiscovered": false,
    "useHttp2": true,
    "abortOnBindingError": true,
    "bsfRetryProfileForInitMsgs": "string",
    "bsfRetryProfileForSubsqtMsgs": "string",
    "defaultBindingOperationMode": "SYNCHRONOUS",
    "bsfNfCommProfile": "string",
    "bsfRecreateAttemptState": "string",
    "bsfReattemptProfile": "string",
    "fqdnIpEndpointsConfiguration": "SERVICE_FQDN",
    "fqdnIpEndpointsProfile": "npcf-smpolicycontrol"
  },
  "qos": {
    "qosDataIdPrefix": "qosdata_",
    "updateDefaultPcfRuleWithAuthDefQos": true,
    "installDefQosIfNotRequested": true,
    "defaultQos5qi": "9",
    "defaultQosArpPreemptCap": "MAY_PREEMPT",
    "defaultQosArpPreemptVuln": "NOT_PREEMPTABLE",
    "defaultQosArpPriorityLevel": "1"
  },
  "qosMonitoring": {

```

```

    "notificationTarget": "AF/NEF"
  },
  "rule": {
    "defaultPolicyControlRequestTriggers": [
      "SUCC_RES_ALLO"
    ],
    "installDefaultPccRule": " IF_NO_RULE",
    "defaultPccRuleProfile": "string",
    "ruleIdPrefix": "0_",
    "defaultPccRule5qi": "9",
    "defaultPccRulePrecedence": "3000",
    "defaultPccRuleArpPreemptCap": "NOT_PREEMPT",
    "defaultPccRuleArpPreemptVuln": "PREEMPTABLE",
    "": "INSTALL",
    "appRulePrecedenceMin": "400",
    "appRulePrecedenceMax": "899",
    "defaultPccRuleArpPriorityLevel": "15",
    "switchFlowInToOutEnabled": false,
    "packetFilterUsageToTrueForPreliminaryServiceInfo": true,
    "setPacketFilterUsageToTrueForPreliminaryServiceInfo": true
  },
  "charging": {
    "chgDataIdPrefix": "chgdata_",
    "primaryChfAddress": "string",
    "primaryChfInstanceId": "string",
    "primaryChfSetId": "string",
    "secondaryChfAddress": "string",
    "secondaryChfInstanceId": "string",
    "secondaryChfSetId": "string",
    "online": true,
    "offline": true,
    "useSubscriberDefChgMethod": true
  },
  "trafficControl": {
    "": "tcdata_"
  },
  "imsEmergencySession": {
    "emergencyDNNs": [
      "string"
    ],
    "arpPriorityLevel": 15,
    "arpPreemptCap": {},
    "arpPreemptVuln": {}
  },
  "audit": {
    "enable": false,
    "notificationRate": 50,
    "ttl": 1440,
    "maxTtl": 2880,
    "frequency": 330
  },
  "extendedAudit": {
    "tdfSession": {
      "enable": true,
      "notificationRate": 0,
      "ttl": 0,

```

```

        "maxTtl": 0,
        "frequency": 0,
        "queryTDF": true,
        "minAuditAttempts": 5
    },
    "pendingOperation": {
        "notificationRate": 0,
        "ttl": 0,
        "maxTtl": 0,
        "frequency": 0,
        "enableAlternateSite": true,
        "alternateSiteId": "string"
    },
    "smPolicyAssociation": {
        "enable": true,
        "notificationRate": 0,
        "ttl": 0,
        "maxTtl": 0,
        "frequency": 0,
        "minAuditAttempts": 5
    }
},
"pendingTransaction": {
    "updateNotifyRetryBackoff": 1000,
    "updateNotifyRetryCount": 2,
    "errorUpdateNotifyHandlingApp": "string",
    "updateNotifyHandling": "string"
},
"overloadConfiguration": {
    "enhancedOverloadControlLevel": -1,
    "overloadConfigurationProfile": "string"
},
"defaultProcessing": {
    "smdpProfile": "string"
},
"messagePriority": {
    "messagePriorityProfile": "string"
},
"advancedSettings": [
    {
        "key": "0",
        "value": "B"
    }
]
},
"errors": [
    {
        "name": "string",
        "message": "string"
    }
]
}

```

2.25 Session Rule

Table 2-144 Supported REST APIs

Description	HTTP Method or Custom Operation	Resource URI	Possible Result Code
Create Session Rule	POST	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcfsm/sessionrules	See Table A-3
Export Session Rules	GET	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcfsm/sessionrules/export	See Table A-1
Import Session Rule	POST	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcfsm/sessionrules/import	See Table A-3
Get Session Rule	GET	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcfsm/sessionrules/{sessionRuleName}	See Table A-1
Update Session Rule	PUT	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcfsm/sessionrules/{sessionRuleName}	See Table A-2
Delete Session Rule	DELETE	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcfsm/sessionrules/{sessionRuleName}	See Table A-4

Get, Create, and Update Session Rules

Table 2-145 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)aints	Description
authDefQosId	string	O	Authorized default QoS information
authSessAmbr	AuthSessAmbr	O	Authorized Session-AMBR
description	string	O	Specifies the description of the Session Rule
name	string	M	Specifies the name of the Session Rule
refCondData	string		specifies the reference to the condition data
sessRuleId	string	M	Specifies the Session Rule ID

Table 2-146 AuthSessAmbr

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
downlink	string Enter a value starting with number and ending bps or Kbps or Mbps or Gbps or Tbps	O	AMBR for downlink
uplink	string Enter a value starting with number and ending bps or Kbps or Mbps or Gbps or Tbps	O	AMBR for uplink

Sample Request body structure for POST and PUT operations:

```
{
  "authDefQosId": "string",
  "authSessAmbr": {
    "downlink": "string",
    "uplink": "string"
  },
  "description": "string",
  "name": "string",
  "refCondData": "string",
  "sessRuleId": "string"
}
```

Sample Response body structure for GET, POST, and PUT operations:

```
{
  "authDefQosId": "string",
  "authSessAmbr": {
    "downlink": "string",
    "uplink": "string"
  },
  "description": "string",
  "name": "string",
  "refCondData": "string",
  "sessRuleProfileId": "string"
}
```

Delete Session Rule**Table 2-147 Request/Response Body Parameters**

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
sessionRuleName	string	M	Session Rule Name

Export/Import Session Rule

Table 2-148 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
date	string		Current timestamp
errors:message	string		Error message
errors:name	string		Name of the error
exportData	array		Exported list of session rules. For more information, see Get, Create, and Update Session Rules
key	string		Indicates the ID of Session Rule
sourceVersion	string		System version of product from which data is exported
topic	string		Topic of each managed object

Sample Request Body structure for Import/Export operations:

```

{
  "date": "string",
  "errors": [
    {
      "message": "string",
      "name": "string"
    }
  ],
  "exportData": [
    {
      "authDefQosId": "string",
      "authSessAmbr": {
        "downlink": "string",
        "uplink": "string"
      },
      "description": "string",
      "name": "string",
      "refCondData": "string",
      "sessRuleId": "string"
    }
  ],
  "key": "string",
  "sourceVersion": "string",
  "topic": "string"
}

```

2.26 Session Rule Profile

Table 2-149 Supported REST APIs

Description	HTTP Method or Custom Operation	Resource URI	Possible Result Code
Create Session Rule Profile	POST	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcfsm/sessionruleprofiles	See Table A-3
Export Session Rule Profiles	GET	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcfsm/sessionruleprofiles/export	See Table A-1
Import Session Rule Profile	POST	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcfsm/sessionruleprofiles/import	See Table A-3
Get Session Rule Profile	GET	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcfsm/sessionruleprofiles/{sessionRuleProfileName}	See Table A-1
Update Session Rule Profile	PUT	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcfsm/sessionruleprofiles/{sessionRuleProfileName}	See Table A-2
Delete Session Rule Profile	DELETE	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcfsm/sessionruleprofiles/{sessionRuleProfileName}	See Table A-4

Get, Create, and Update Session Rule Profiles

Table 2-150 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)aints	Description
authDefQosId	string	O	Authorized default QoS information
authSessAmbr	AuthSessAmbr	O	Authorized Session-AMBR
description	string		Specifies the description of the Session Rule Profile
name	string	M	Specifies the name of the Session Rule Profile

Table 2-150 (Cont.) Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
refCondData	string		
sessRuleProfileId	string	M	Specifies the Session Rule Profile ID

Table 2-151 AuthSessAmbr

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
downlink	string	O	AMBR for downlink
uplink	string	O	AMBR for uplink

Sample Request body structure for POST and PUT operations:

```
{
  "authDefQosId": "string",
  "authSessAmbr": {
    "downlink": "string",
    "uplink": "string"
  },
  "description": "string",
  "name": "string",
  "refCondData": "string",
  "sessRuleProfileId": "string"
}
```

Sample Response body structure for GET, POST, and PUT operations:

```
{
  "authDefQosId": "string",
  "authSessAmbr": {
    "downlink": "string",
    "uplink": "string"
  },
  "description": "string",
  "name": "string",
  "refCondData": "string",
  "sessRuleProfileId": "string"
}
```


Delete Session Rule Profile**Table 2-152 Request/Response Body Parameters**

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
sessionRuleProfileName	string	M	Session Rule Profile Name

Export/Import Session Rule Profile**Table 2-153 Request/Response Body Parameters**

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
date	string		Current timestamp
errors:message	string		Error message
errors:name	string		Name of the error
exportData	array		Exported list of session rule profiles. For more information, see Get, Create, and Update Session Rule Profiles .
key	string		Indicates the ID of Session Rule Profile
sourceVersion	string		System version of product from which data is exported
topic	string		Topic of each managed object

Sample Request Body structure for Import/Export operations:

```
{
  "date": "string",
  "errors": [
    {
      "message": "string",
      "name": "string"
    }
  ],
  "exportData": [
    {
      "authDefQosId": "string",
      "authSessAmbr": {
        "downlink": "string",
        "uplink": "string"
      },
      "description": "string",
      "name": "string",
      "refCondData": "string",
      "sessRuleProfileId": "string"
    }
  ]
}
```

```

    }
  ],
  "key": "string",
  "sourceVersion": "string",
  "topic": "string"
}

```

2.27 QoS Information

Table 2-154 Supported REST APIs

Description	HTTP Method or Custom Operation	Resource URI	Possible Result Code
Create QoS Information	POST	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcfsm/qosinformation	See Table A-3
Export QoS Information	GET	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcfsm/qosinformation/export	See Table A-1
Import QoS Information	POST	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcfsm/qosinformation/import	See Table A-3
Get QoS Information	GET	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcfsm/qosinformation/{qosInformationName}	See Table A-1
Update QoS Information	PUT	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcfsm/qosinformation/{qosInformationName}	See Table A-2
Delete QoS Information	DELETE	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcfsm/qosinformation/{qosInformationName}	See Table A-4

Get, Create, and Update QoS Information

Table 2-155 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)aints	Description
5qi	string (\$int32) enter a range in [0-255] number	O	Identifier for the authorized QoS parameters for the service data flow. It shall be included when the QoS data decision is initially provisioned.

Table 2-155 (Cont.) Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
arp	Arp	O	Indicates the allocation and retention priority. It shall be included when the Authorized Default QoS is initially provisioned.
averWindow	integer	O	Represents the duration over which the guaranteed and maximum bitrate shall be calculated. The allowed integer value ranges from 1 to 4095. Default Value: 2000
description	string	O	The description of the Qos Information.
maxDataBurstVol	integer	O	Denotes the largest amount of data that is required to be transferred within a period of 5GAN PDB. The allowed integer value ranges from 1 to 4095. Default Value: 2000
name	string	M	The name of the Qos Information.
priorityLevel	integer (\$int32)	O	Unsigned integer indicating the 5QI Priority Level, within a range of 1 to 127.

Table 2-156 Arp

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
preemptCap	ENUM	M	Defines whether a service data flow may get resources that were already assigned to another service data flow with a lower priority level. Possible values are: • NOT_PREEMPT : Shall not trigger pre-emption. • MAY_PREEMPT : May trigger pre-emption.

Table 2-156 (Cont.) Arp

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
preemptVuln	ENUM	M	Defines whether a service data flow may lose the resources assigned to it in order to admit a service data flow with higher priority level. Possible values are: • NOT_PREEMPTABLE : Shall not be pre-empted. • PREEMPTABLE : May be pre-empted.
priorityLevel	integer (\$int32)	M	Unsigned integer indicating the ARP Priority Level, within the range 1 to 15.

Sample Request body structure for POST and PUT operations:

```
{
  "5qi": "string",
  "arp": {
    "preemptCap": "MAY_PREEMPT",
    "preemptVuln": "NOT_PREEMPTABLE",
    "priorityLevel": 0
  },
  "averWindow": 2000,
  "description": "string",
  "maxDataBurstVol": 2000,
  "name": "string",
  "priorityLevel": "string"
}
```

Sample Response body structure for GET, POST, and PUT operations:

```
{
  "5qi": "string",
  "arp": {
    "preemptCap": "MAY_PREEMPT",
    "preemptVuln": "NOT_PREEMPTABLE",
    "priorityLevel": 0
  },
  "averWindow": 2000,
  "description": "string",
  "maxDataBurstVol": 2000,
  "name": "string",
  "priorityLevel": "string"
}
```

Delete QoS Information**Table 2-157 Request/Response Body Parameters**

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
qosInformationName	string	M	Qos Information Name

Export/Import QoS Information**Table 2-158 Request/Response Body Parameters**

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
date	string	M	Current timestamp
exportData	array	M	Exported list of QoS information. For more information, see Get, Create, and Update QoS Information .
key	string	M	Indicates the ID of QoS Information
sourceVersion	string	M	System version of product from which data is exported
topic	string	M	Topic of each managed object

Sample Request Body structure for Import/Export operations:

```
{
  "date": "string",
  "errors": [
    {
      "message": "string",
      "name": "string"
    }
  ],
  "exportData": [
    {
      "5qi": "string",
      "arp": {
        "preemptCap": "MAY_PREEMPT",
        "preemptVuln": "NOT_PREEMPTABLE",
        "priorityLevel": 0
      },
      "averWindow": 2000,
      "description": "string",
      "maxDataBurstVol": 2000,
      "name": "string",
      "priorityLevel": "string"
    }
  ]
}
```

```

    }
  ],
  "key": "string",
  "sourceVersion": "string",
  "topic": "string"
}

```

2.28 QoS Data

Table 2-159 Supported REST APIs

Description	HTTP Method or Custom Operation	Resource URI	Possible Result Code
Create QoS Data	POST	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcfsm/qosdata	See Table A-3
Export QoS Data	GET	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcfsm/qosdata/export	See Table A-1
Import QoS Data	POST	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcfsm/qosdata/import	See Table A-3
Get QoS Data	GET	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcfsm/qosdata/{qosDataName}	See Table A-1
Update QoS Data	PUT	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcfsm/qosdata/{qosDataName}	See Table A-2
Delete QoS Data	DELETE	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcfsm/qosdata/{qosDataName}	See Table A-4

Get, Create, and Update QoS Data s

Table 2-160 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)aints	Description
5qi	string (\$int32) enter a range in [0-255] number	O	Identifier for the authorized QoS parameters for the service data flow. It shall be included when the QoS data decision.
arp	Arp	O	ARP information

Table 2-160 (Cont.) Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
averwindow	string	O	Averwindow details.
defQosFlowIndication	boolean	O	Indicates that the dynamic PCC rule shall always have its binding with the QoS Flow associated with the default QoS rule. Default value is "FALSE", if not present and has not been supplied previously.
description	string	O	The description of the Qos Data
gbrDL	string , Enter a value starting with number and ending bps or Kbps or Mbps or Gbps or Tbps	O	Indicates the guaranteed bandwidth in downlink.
gbrUL	string , Enter a value starting with number and ending bps or Kbps or Mbps or Gbps or Tbps	O	Indicates the guaranteed bandwidth in uplink.
maxDataBurstVol	integer (\$int32) Enter a value between 1 and 4095	O	Denotes the largest amount of data that is required to be transferred within a period of 5GAN PDB (NOTE).
maxPacketLossRateDL	integer (\$int32) Enter a value between 0 and 1000	O	Indicates the downlink maximum rate for lost packets that can be tolerated for the service data flow.
maxPacketLossRateUL	integer (\$int32) Enter a value between 0 and 1000	O	Indicates the uplink maximum rate for lost packets that can be tolerated for the service data flow.
maxbrDL	string , Enter a value starting with number and ending bps or Kbps or Mbps or Gbps or Tbps	O	Indicates the max bandwidth in downlink.
maxbrUL	string , Enter a value starting with number and ending bps or Kbps or Mbps or Gbps or Tbps	O	Indicates the max bandwidth in uplink.
name	string	M	The name of the Qos Data
priorityLevel	integer (\$int32) Enter a value between 1 and 127	O	Defines the relative importance of a resource request.

Table 2-160 (Cont.) Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
qnc	boolean	O	Indicates whether notifications are requested from 3GPP NG-RAN when the GFBF can no longer (or again) be guaranteed for a QoS flow during the lifetime of the QoS flow.
qosId	string	O	Specifies the QoS Id.
reflectiveQos	boolean	O	Indicates whether the QoS information is reflective for the corresponding service data flow. Default value is "FALSE", if not present and has not been supplied previously.
sharingKeyDI	string	O	Indicates, by containing the same value, what PCC rules may share resource in downlink direction.
sharingKeyUI	string	O	Indicates, by containing the same value, what PCC rules may share resource in uplink direction.

Table 2-161 Arp

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
preemptCap	ENUM	M	Defines whether a service data flow may get resources that were already assigned to another service data flow with a lower priority level.
preemptVuln	ENUM	M	Defines whether a service data flow may lose the resources assigned to it in order to admit a service data flow with higher priority level.
priorityLevel	integer (\$int32) enter a range in [1-15] number	M	Defines the relative importance of a resource request.

Sample Request body structure for POST and PUT operations:

```
{
  "5qi": 0,
  "arp": {
    "preemptCap": "MAY_PREEMPT",
    "preemptVuln": "NOT_PREEMPTABLE",
    "priorityLevel": 0
  },
  "averWindow": 2000,
  "defQosFlowIndication": true,
  "description": "string",
  "gbrDL": "string",
  "gbrUL": "string",
  "maxDataBurstVol": 0,
  "maxPacketLossRateDL": 0,
  "maxPacketLossRateUL": 0,
  "maxbrDL": "string",
  "maxbrUL": "string",
  "name": "string",
  "priorityLevel": 0,
  "qnc": true,
  "qosId": "string",
  "reflectiveQos": true,
  "sharingKeyDL": "string",
  "sharingKeyUL": "string"
}
```

Sample Response body structure for GET, POST, and PUT operations:

```
{
  "5qi": 0,
  "arp": {
    "preemptCap": "MAY_PREEMPT",
    "preemptVuln": "NOT_PREEMPTABLE",
    "priorityLevel": 0
  },
  "averWindow": 2000,
  "defQosFlowIndication": true,
  "description": "string",
  "gbrDL": "string",
  "gbrUL": "string",
  "maxDataBurstVol": 0,
  "maxPacketLossRateDL": 0,
  "maxPacketLossRateUL": 0,
  "maxbrDL": "string",
  "maxbrUL": "string",
  "name": "string",
  "priorityLevel": 0,
  "qnc": true,
  "qosId": "string",
  "reflectiveQos": true,
  "sharingKeyDL": "string",
  "sharingKeyUL": "string"
}
```

Delete QoS Data**Table 2-162 Request/Response Body Parameters**

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
qosDataName	string	M	Qos Data Name

Export/Import QoS Data s**Table 2-163 Request/Response Body Parameters**

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
date	string	M	Current timestamp
exportData	array	M	Exported list of QoS data. For more information, see Get, Create, and Update QoS Data s .
key	string	O	Indicates the ID of QoS Data
sourceVersion	string	O	System version of product from which data is exported
topic	string	O	Topic of each managed object

Sample Request Body structure for Import/Export operations:

```
{
  "date": "string",
  "errors": [
    {
      "message": "string",
      "name": "string"
    }
  ],
  "exportData": [
    {
      "5qi": 0,
      "arp": {
        "preemptCap": "MAY_PREEMPT",
        "preemptVuln": "NOT_PREEMPTABLE",
        "priorityLevel": 0
      },
      "averWindow": 2000,
      "defQosFlowIndication": true,
      "description": "string",
      "gbrDl": "string",
      "gbrUl": "string",

```

```

        "maxDataBurstVol": 0,
        "maxPacketLossRateDl": 0,
        "maxPacketLossRateUl": 0,
        "maxbrDl": "string",
        "maxbrUl": "string",
        "name": "string",
        "priorityLevel": 0,
        "qnc": true,
        "qosId": "string",
        "reflectiveQos": true,
        "sharingKeyDl": "string",
        "sharingKeyUl": "string"
    }
},
"key": "string",
"sourceVersion": "string",
"topic": "string"
}

```

2.29 Traffic for PCC Rule

Table 2-164 Supported REST APIs

Description	HTTP Method or Custom Operation	Resource URI	Possible Result Code
Create Traffic PCC Rule	POST	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcrf/pccrules	See Table A-3
Export Traffic PCC Rule	GET	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcrf/pccrules/export	See Table A-1
Import Traffic PCC Rule	POST	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcrf/pccrules/import	See Table A-3
Get Traffic PCC Rule	GET	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcrf/pccrules/{trafficPccRuleName}	See Table A-1
Update Traffic PCC Rule	PUT	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcrf/pccrules/{trafficPccRuleName}	See Table A-2
Delete Traffic PCC Rule	DELETE	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcrf/pccrules/{trafficPccRuleName}	See Table A-4

Create, Get, and Update Traffic for PCC Rule

Table 2-165 Data structures supported by the POST, GET, and PUT Response Body

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
description	string	O	
name	string	M	
param.diameter.pccRule.ARP.PreemptionCapability	string	O	Allowed values • 0 • 1
param.diameter.pccRule.ARP.PreemptionVulnerability	string	O	Allowed values • 0 • 1
param.diameter.pccRule.ARP.PriorityLevel	string	O	
param.diameter.pccRule.FlowDescriptions	string	O	
param.diameter.pccRule.FlowInformations	array	O	
param.diameter.pccRule.FlowStatus	string	O	Allowed values • 0 • 1 • 2 • 3
param.diameter.pccRule.bearerUsage	ENUM	O	
param.diameter.pccRule.MeteringMethod	string	O	Allowed values • 0 • 1 • 2 • 3
param.diameter.pccRule.MonitoringKey	string	O	
param.diameter.pccRule.Offline	string	O	Allowed values • 0 • 1
param.diameter.pccRule.Online	string	O	Allowed values • 0 • 1
param.diameter.pccRule.Precedence	string	O	
param.diameter.pccRule.RatingGroup	string	O	
param.diameter.pccRule.ReportingLevel	string	O	Allowed values • 0 • 1 • 2

Table 2-165 (Cont.) Data structures supported by the POST, GET, and PUT Response Body

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
param.diameter.pccRule.RequiredAccessInfo	string	O	Allowed values • 1 • 2 • 3
param.diameter.pccRule.ResourceAllocationNotification	string	O	Allowed values • 0
param.diameter.pccRule.ServiceIdentifier	string	O	
param.diameter.pccRule.applicationServiceProviderIdentity	string	O	
param.diameter.pccRule.maxAuthDL	string	O	
param.diameter.pccRule.maxAuthUL	string	O	
param.diameter.pccRule.minRateDL	string	O	
param.diameter.pccRule.minRateUL	string	O	
param.diameter.pccRule.qci	string	O	Allowed values: • 1 • 2 • 3 • 4 • 5 • 6 • 7 • 8 • 9 • 65 • 66 • 69 • 70
param.diameter.pccRule.sponsorIdentity	string	O	
param.diameter.pccRule.tdfApplicationIdentifier	string	O	
param.diameter.pccRule.tdfMuteNotification	string	O	Allowed values • 0

Table 2-165 (Cont.) Data structures supported by the POST, GET, and PUT Response Body

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
param.diameter.pccRule.tdfRedirectAddressType	string	O	Allowed values • 0 • 1 • 2 • 3
param.diameter.pccRule.tdfRedirectServerAddress	string	O	
param.diameter.pccRule.tdfRedirectSupport	string	O	Allowed values • 0 • 1

Table 2-166 param.diameter.pccRule.FlowInformations

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
flowDescription	string	O	
flowDirection	string	M	Allowed values: • -1 • 0 • 1 • 2 • 3
tos	string	O	
tosMask	string	O	

Sample Request Body structure for POST and PUT operations:

```
{
  "description": "string",
  "name": "string",
  "param.diameter.pccRule.ARP.PreemptionCapability": "0",
  "param.diameter.pccRule.ARP.PreemptionVulnerability": "0",
  "param.diameter.pccRule.ARP.PriorityLevel": "string",
  "param.diameter.pccRule.FlowDescriptions": "string",
  "param.diameter.pccRule.FlowInformations": [
    {
      "flowDescription": "string",
      "flowDirection": "-1",
      "tos": "string",
      "tosMask": "string"
    }
  ],
  "param.diameter.pccRule.FlowStatus": "0",
  "param.diameter.pccRule.MeteringMethod": "0",
}
```

```

"param.diameter.pccRule.MonitoringKey": "string",
"param.diameter.pccRule.Offline": "0",
"param.diameter.pccRule.Online": "0",
"param.diameter.pccRule.PStoCSSessionContinuity": "0",
"param.diameter.pccRule.Precedence": "string",
"param.diameter.pccRule.RatingGroup": "string",
"param.diameter.pccRule.ReportingLevel": "0",
"param.diameter.pccRule.RequiredAccessInfo": "1",
"param.diameter.pccRule.ResourceAllocationNotification": "0",
"param.diameter.pccRule.ServiceIdentifier": "string",
"param.diameter.pccRule.applicationServiceProviderIdentity": "string",
"param.diameter.pccRule.maxAuthDL": "string",
"param.diameter.pccRule.maxAuthUL": "string",
"param.diameter.pccRule.minRateDL": "string",
"param.diameter.pccRule.minRateUL": "string",
"param.diameter.pccRule.name": "string",
"param.diameter.pccRule.qci": "1",
"param.diameter.pccRule.sponsorIdentity": "string",
"param.diameter.pccRule.tdfApplicationIdentifier": "string",
"param.diameter.pccRule.tdfMuteNotification": "0",
"param.diameter.pccRule.tdfRedirectAddressType": "0",
"param.diameter.pccRule.tdfRedirectServerAddress": "string",
"param.diameter.pccRule.tdfRedirectSupport": "0"
}

```

Sample Response Body structure for GET, POST and PUT operations:

```

{
  "description": "string",
  "name": "string",
  "param.diameter.pccRule.ARP.PreemptionCapability": "0",
  "param.diameter.pccRule.ARP.PreemptionVulnerability": "0",
  "param.diameter.pccRule.ARP.PriorityLevel": "string",
  "param.diameter.pccRule.FlowDescriptions": "string",
  "param.diameter.pccRule.FlowInformations": [
    {
      "flowDescription": "string",
      "flowDirection": "-1",
      "tos": "string",
      "tosMask": "string"
    }
  ],
  "param.diameter.pccRule.FlowStatus": "0",
  "param.diameter.pccRule.MeteringMethod": "0",
  "param.diameter.pccRule.MonitoringKey": "string",
  "param.diameter.pccRule.Offline": "0",
  "param.diameter.pccRule.Online": "0",
  "param.diameter.pccRule.PStoCSSessionContinuity": "0",
  "param.diameter.pccRule.Precedence": "string",
  "param.diameter.pccRule.RatingGroup": "string",
  "param.diameter.pccRule.ReportingLevel": "0",
  "param.diameter.pccRule.RequiredAccessInfo": "1",
  "param.diameter.pccRule.ResourceAllocationNotification": "0",
  "param.diameter.pccRule.ServiceIdentifier": "string",
  "param.diameter.pccRule.applicationServiceProviderIdentity": "string",

```

```

"param.diameter.pccRule.maxAuthDL": "string",
"param.diameter.pccRule.maxAuthUL": "string",
"param.diameter.pccRule.minRateDL": "string",
"param.diameter.pccRule.minRateUL": "string",
"param.diameter.pccRule.name": "string",
"param.diameter.pccRule.qci": "1",
"param.diameter.pccRule.sponsorIdentity": "string",
"param.diameter.pccRule.tdfApplicationIdentifier": "string",
"param.diameter.pccRule.tdfMuteNotification": "0",
"param.diameter.pccRule.tdfRedirectAddressType": "0",
"param.diameter.pccRule.tdfRedirectServerAddress": "string",
"param.diameter.pccRule.tdfRedirectSupport": "0"
}

```

Export/Import Traffic for PCC Rule

Table 2-167 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
date	string		Current timestamp
errors	array		
errors:message	string		
errors:name	string		
exportData	array	M	Exported list of traffic PCC Rule. For more information, see Table 2-165 .
key	string		Indicates the ID
sourceVersion	string		System version of the product from which data is exported
topic	string	M	Topic of each managed object

Sample Request Body structure for Import/Export operations:

```

{
  "date": "string",
  "errors": [
    {
      "message": "string",
      "name": "string"
    }
  ],
  "exportData": [
    {
      "description": "string",
      "name": "string",
      "param.diameter.pccRule.ARP.PreemptionCapability": "0",
      "param.diameter.pccRule.ARP.PreemptionVulnerability": "0",
      "param.diameter.pccRule.ARP.PriorityLevel": "string",
      "param.diameter.pccRule.FlowDescriptions": "string",

```



```

"param.diameter.pccRule.FlowInformations": [
  {
    "flowDescription": "string",
    "flowDirection": "-1",
    "tos": "string",
    "tosMask": "string"
  }
],
"param.diameter.pccRule.FlowStatus": "0",
"param.diameter.pccRule.MeteringMethod": "0",
"param.diameter.pccRule.MonitoringKey": "string",
"param.diameter.pccRule.Offline": "0",
"param.diameter.pccRule.Online": "0",
"param.diameter.pccRule.PStoCSSessionContinuity": "0",
"param.diameter.pccRule.Precedence": "string",
"param.diameter.pccRule.RatingGroup": "string",
"param.diameter.pccRule.ReportingLevel": "0",
"param.diameter.pccRule.RequiredAccessInfo": "1",
"param.diameter.pccRule.ResourceAllocationNotification": "0",
"param.diameter.pccRule.ServiceIdentifier": "string",
"param.diameter.pccRule.applicationServiceProviderIdentity": "string",
"param.diameter.pccRule.maxAuthDL": "string",
"param.diameter.pccRule.maxAuthUL": "string",
"param.diameter.pccRule.minRateDL": "string",
"param.diameter.pccRule.minRateUL": "string",
"param.diameter.pccRule.name": "string",
"param.diameter.pccRule.qci": "1",
"param.diameter.pccRule.sponsorIdentity": "string",
"param.diameter.pccRule.tdfApplicationIdentifier": "string",
"param.diameter.pccRule.tdfMuteNotification": "0",
"param.diameter.pccRule.tdfRedirectAddressType": "0",
"param.diameter.pccRule.tdfRedirectServerAddress": "string",
"param.diameter.pccRule.tdfRedirectSupport": "0"
}
],
"key": "string",
"sourceVersion": "string",
"topic": "string"
}

```

Delete Traffic for PCC Rule

Table 2-168 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
trafficPccRuleName	string	M	Traffic PCC Rule Name

2.30 Traffic for PCC Profile

Table 2-169 Supported REST APIs

Description	HTTP Method or Custom Operation	Resource URI	Possible Result Code
Create Traffic PCC Profile	POST	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcrf/pccruleprofiles	See Table A-3
Export Traffic PCC Profile	GET	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcrf/pccruleprofiles/export	See Table A-1
Import Traffic PCC Profile	POST	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcrf/pccruleprofiles/import	See Table A-3
Get Traffic PCC Profile	GET	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcrf/pccruleprofiles/{trafficPccProfileName}	See Table A-1
Update Traffic PCC Profile	PUT	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcrf/pccruleprofiles/{trafficPccProfileName}	See Table A-2
Delete Traffic PCC Profile	DELETE	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcrf/pccruleprofiles/{trafficPccProfileName}	See Table A-4

Create, Get, and Update Traffic for PCC Profile

Table 2-170 Data structures supported by the POST, GET, and PUT Response Body

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
description	string	O	
name	string	M	
param.diameter.pcc Profile.ARP.PreemptionCapability	string	O	Allowed values 0 1
param.diameter.pcc Profile.ARP.PreemptionVulnerability	string	O	Allowed values 0 1
param.diameter.pcc Profile.ARP.Priority Level	string	O	

Table 2-170 (Cont.) Data structures supported by the POST, GET, and PUT Response Body

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
param.diameter.pcc Profile.FlowDescriptions	string	O	
param.diameter.pcc Profile.FlowInformations	array	O	
param.diameter.pcc Profile.FlowStatus	string	O	Allowed values • 0 • 1 • 2 • 3
param.diameter.pcc Profile.bearerUsage	ENUM	O	
param.diameter.pcc Profile.MeteringMethod	string	O	Allowed values • 0 • 1 • 2 • 3
param.diameter.pcc Profile.MonitoringKey	string	O	
param.diameter.pcc Profile.Offline	string	O	Allowed values • 0 • 1
param.diameter.pcc Profile.Online	string	O	Allowed values • 0 • 1
param.diameter.pcc Profile.Precedence	string	O	
param.diameter.pcc Profile.RatingGroup	string	O	
param.diameter.pcc Profile.ReportingLevel	string	O	Allowed values • 0 • 1 • 2
param.diameter.pcc Profile.RequiredAccessInfo	string	O	Allowed values • 1 • 2 • 3
param.diameter.pcc Profile.ResourceAllocationNotification	string	O	Allowed values • 0
param.diameter.pcc Profile.ServiceIdentifier	string	O	

Table 2-170 (Cont.) Data structures supported by the POST, GET, and PUT Response Body

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
param.diameter.pccProfile.applicationServiceProviderIdentity	string	O	
param.diameter.pccProfile.maxAuthDL	string	O	
param.diameter.pccProfile.maxAuthUL	string	O	
param.diameter.pccProfile.minRateDL	string	O	
param.diameter.pccProfile.minRateUL	string	O	
param.diameter.pccProfile.qci	string	O	Allowed values: • 1 • 2 • 3 • 4 • 5 • 6 • 7 • 8 • 9 • 65 • 66 • 69 • 70
param.diameter.pccProfile.sponsorIdentity	string	O	
param.diameter.pccProfile.tdfApplicationIdentifier	string	O	
param.diameter.pccProfile.tdfMuteNotification	string	O	Allowed values • 0
param.diameter.pccProfile.tdfRedirectAddressType	string	O	Allowed values • 0 • 1 • 2 • 3
param.diameter.pccProfile.tdfRedirectServerAddress	string	O	
param.diameter.pccProfile.tdfRedirectSupport	string	O	Allowed values • 0 • 1

Table 2-171 param.diameter.pccProfile.FlowInformations

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
flowDescription	string	O	
flowDirection	string	M	Allowed values: • -1 • 0 • 1 • 2 • 3
tos	string	O	
tosMask	string	O	

Sample Request Body structure for POST and PUT operations:

```
{
  "description": "string",
  "name": "string",
  "param.diameter.pccProfile.ARP.PreemptionCapability": "0",
  "param.diameter.pccProfile.ARP.PreemptionVulnerability": "0",
  "param.diameter.pccProfile.ARP.PriorityLevel": "string",
  "param.diameter.pccProfile.FlowDescriptions": "string",
  "param.diameter.pccProfile.FlowInformations": [
    {
      "flowDescription": "string",
      "flowDirection": "-1",
      "tos": "string",
      "tosMask": "string"
    }
  ],
  "param.diameter.pccProfile.FlowStatus": "0",
  "param.diameter.pccProfile.MeteringMethod": "0",
  "param.diameter.pccProfile.MonitoringKey": "string",
  "param.diameter.pccProfile.Offline": "0",
  "param.diameter.pccProfile.Online": "0",
  "param.diameter.pccProfile.Precedence": "string",
  "param.diameter.pccProfile.RatingGroup": "string",
  "param.diameter.pccProfile.ReportingLevel": "0",
  "param.diameter.pccProfile.RequiredAccessInfo": "1",
  "param.diameter.pccProfile.ResourceAllocationNotification": "0",
  "param.diameter.pccProfile.ServiceIdentifier": "string",
  "param.diameter.pccProfile.applicationServiceProviderIdentity": "string",
  "param.diameter.pccProfile.maxAuthDL": "string",
  "param.diameter.pccProfile.maxAuthUL": "string",
  "param.diameter.pccProfile.minRateDL": "string",
  "param.diameter.pccProfile.minRateUL": "string",
  "param.diameter.pccProfile.qci": "1",
  "param.diameter.pccProfile.sponsorIdentity": "string",
  "param.diameter.pccProfile.tdfApplicationIdentifier": "string",
  "param.diameter.pccProfile.tdfMuteNotification": "0",
  "param.diameter.pccProfile.tdfRedirectAddressType": "0",
  "param.diameter.pccProfile.tdfRedirectServerAddress": "string",
}
```

```
"param.diameter.pccProfile.tdfRedirectSupport": "0"
}
```

Sample Response Body structure for GET, POST and PUT operations:

```
{
  "description": "string",
  "name": "string",
  "param.diameter.pccProfile.ARP.PreemptionCapability": "0",
  "param.diameter.pccProfile.ARP.PreemptionVulnerability": "0",
  "param.diameter.pccProfile.ARP.PriorityLevel": "string",
  "param.diameter.pccProfile.FlowDescriptions": "string",
  "param.diameter.pccProfile.FlowInformations": [
    {
      "flowDescription": "string",
      "flowDirection": "-1",
      "tos": "string",
      "tosMask": "string"
    }
  ],
  "param.diameter.pccProfile.FlowStatus": "0",
  "param.diameter.pccProfile.MeteringMethod": "0",
  "param.diameter.pccProfile.MonitoringKey": "string",
  "param.diameter.pccProfile.Offline": "0",
  "param.diameter.pccProfile.Online": "0",
  "param.diameter.pccProfile.Precedence": "string",
  "param.diameter.pccProfile.RatingGroup": "string",
  "param.diameter.pccProfile.ReportingLevel": "0",
  "param.diameter.pccProfile.RequiredAccessInfo": "1",
  "param.diameter.pccProfile.ResourceAllocationNotification": "0",
  "param.diameter.pccProfile.ServiceIdentifier": "string",
  "param.diameter.pccProfile.applicationServiceProviderIdentity": "string",
  "param.diameter.pccProfile.maxAuthDL": "string",
  "param.diameter.pccProfile.maxAuthUL": "string",
  "param.diameter.pccProfile.minRateDL": "string",
  "param.diameter.pccProfile.minRateUL": "string",
  "param.diameter.pccProfile.qci": "1",
  "param.diameter.pccProfile.sponsorIdentity": "string",
  "param.diameter.pccProfile.tdfApplicationIdentifier": "string",
  "param.diameter.pccProfile.tdfMuteNotification": "0",
  "param.diameter.pccProfile.tdfRedirectAddressType": "0",
  "param.diameter.pccProfile.tdfRedirectServerAddress": "string",
  "param.diameter.pccProfile.tdfRedirectSupport": "0"
}
```

Export/Import Traffic for PCC Profile

Table 2-172 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
date	string		Current timestamp
errors	array		

Table 2-172 (Cont.) Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
errors:message	string		
errors:name	string		
exportData	array	M	Exported list of traffic Pcc Profile. For more information, see Table 2-170 .
key	string		Indicates the ID
sourceVersion	string		System version of the product from which data is exported
topic	string	M	Topic of each managed object

Sample Request Body structure for Import/Export operations:

```
{
  "date": "string",
  "errors": [
    {
      "message": "string",
      "name": "string"
    }
  ],
  "exportData": [
    {
      "description": "string",
      "name": "string",
      "param.diameter.pccProfile.ARP.PreemptionCapability": "0",
      "param.diameter.pccProfile.ARP.PreemptionVulnerability": "0",
      "param.diameter.pccProfile.ARP.PriorityLevel": "string",
      "param.diameter.pccProfile.FlowDescriptions": "string",
      "param.diameter.pccProfile.FlowInformations": [
        {
          "flowDescription": "string",
          "flowDirection": "-1",
          "tos": "string",
          "tosMask": "string"
        }
      ],
      "param.diameter.pccProfile.FlowStatus": "0",
      "param.diameter.pccProfile.MeteringMethod": "0",
      "param.diameter.pccProfile.MonitoringKey": "string",
      "param.diameter.pccProfile.Offline": "0",
      "param.diameter.pccProfile.Online": "0",
      "param.diameter.pccProfile.Precedence": "string",
      "param.diameter.pccProfile.RatingGroup": "string",
      "param.diameter.pccProfile.ReportingLevel": "0",
      "param.diameter.pccProfile.RequiredAccessInfo": "1",
      "param.diameter.pccProfile.ResourceAllocationNotification": "0",

```

```

        "param.diameter.pccProfile.ServiceIdentifier": "string",
        "param.diameter.pccProfile.applicationServiceProviderIdentity":
"string",
        "param.diameter.pccProfile.maxAuthDL": "string",
        "param.diameter.pccProfile.maxAuthUL": "string",
        "param.diameter.pccProfile.minRateDL": "string",
        "param.diameter.pccProfile.minRateUL": "string",
        "param.diameter.pccProfile.qci": "1",
        "param.diameter.pccProfile.sponsorIdentity": "string",
        "param.diameter.pccProfile.tdfApplicationIdentifier": "string",
        "param.diameter.pccProfile.tdfMuteNotification": "0",
        "param.diameter.pccProfile.tdfRedirectAddressType": "0",
        "param.diameter.pccProfile.tdfRedirectServerAddress": "string",
        "param.diameter.pccProfile.tdfRedirectSupport": "0"
    }
},
"key": "string",
"sourceVersion": "string",
"topic": "string"
}

```

Delete Traffic for PCC Profile

Table 2-173 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
trafficPccProfileName	string	M	Traffic PCC Profile Name

2.31 Traffic for Diameter QoS

Table 2-174 Supported REST APIs

Description	HTTP Method or Custom Operation	Resource URI	Possible Result Code
Create Traffic Diameter QoS	POST	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcrf/diameterqos	See Table A-3
Export Traffic Diameter QoS	GET	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcrf/diameterqos/export	See Table A-1
Import Traffic Diameter QoS	POST	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcrf/diameterqos/import	See Table A-3

Table 2-174 (Cont.) Supported REST APIs

Description	HTTP Method or Custom Operation	Resource URI	Possible Result Code
Get Traffic Diameter QoS	GET	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcrf/diameterqos/{trafficDiameterQoSName}	See Table A-1
Update Traffic Diameter QoS	PUT	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcrf/diameterqos/{trafficDiameterQoSName}	See Table A-2
Delete Traffic Diameter QoS	DELETE	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcrf/diameterqos/{trafficDiameterQoSName}	See Table A-4

Create, Get, and Update Traffic for Diameter QoS

Table 2-175 Data structures supported by the POST, GET, and PUT Response Body

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
description	string	O	
name	string	M	
param.diameter.qos Profile.ARP.PreemptionCapability	string	O	Allowed values: 0 1
param.diameter.qos Profile.ARP.PreemptionVulnerability	string	O	Allowed values: 0 1
param.diameter.qos Profile.ARP.Priority Level	string	O	
param.diameter.qos Profile.ResourceAllocationNotification	string	O	Allowed values: 0
param.diameter.qos Profile.maxAuthDL	string	O	
param.diameter.qos Profile.maxAuthUL	string	O	
param.diameter.qos Profile.minRateDL	string	O	
param.diameter.qos Profile.minRateUL	string	O	

Table 2-175 (Cont.) Data structures supported by the POST, GET, and PUT Response Body

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
param.diameter.qosProfile.qci	string	O	Allowed values: • 1 • 2 • 3 • 4 • 5 • 6 • 7 • 8 • 9 • 65 • 66 • 69 • 70

Sample Request Body structure for POST and PUT operations:

```
{
  "description": "string",
  "name": "string",
  "param.diameter.qosProfile.ARP.PreemptionCapability": "0",
  "param.diameter.qosProfile.ARP.PreemptionVulnerability": "0",
  "param.diameter.qosProfile.ARP.PriorityLevel": "string",
  "param.diameter.qosProfile.ResourceAllocationNotification": "0",
  "param.diameter.qosProfile.maxAuthDL": "string",
  "param.diameter.qosProfile.maxAuthUL": "string",
  "param.diameter.qosProfile.minRateDL": "string",
  "param.diameter.qosProfile.minRateUL": "string",
  "param.diameter.qosProfile.qci": "1"
}
```

Sample Response Body structure for GET, POST and PUT operations:

```
{
  "description": "string",
  "name": "string",
  "param.diameter.qosProfile.ARP.PreemptionCapability": "0",
  "param.diameter.qosProfile.ARP.PreemptionVulnerability": "0",
  "param.diameter.qosProfile.ARP.PriorityLevel": "string",
  "param.diameter.qosProfile.ResourceAllocationNotification": "0",
  "param.diameter.qosProfile.maxAuthDL": "string",
  "param.diameter.qosProfile.maxAuthUL": "string",
  "param.diameter.qosProfile.minRateDL": "string",
  "param.diameter.qosProfile.minRateUL": "string",
  "param.diameter.qosProfile.qci": "1"
}
```

Export/Import Traffic for Diameter QoS

Table 2-176 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
date	string		Current timestamp
errors	array		
errors:message	string		
errors:name	string		
exportData	array	M	Exported list of traffic diameter QoS. For more information, see Table 2-175 .
key	string		Indicates the ID
sourceVersion	string		System version of the product from which data is exported
topic	string	M	Topic of each managed object

Sample Request Body structure for Import/Export operations:

```
{
  "date": "string",
  "errors": [
    {
      "message": "string",
      "name": "string"
    }
  ],
  "exportData": [
    {
      "description": "string",
      "name": "string",
      "param.diameter.qosProfile.ARP.PreemptionCapability": "0",
      "param.diameter.qosProfile.ARP.PreemptionVulnerability": "0",
      "param.diameter.qosProfile.ARP.PriorityLevel": "string",
      "param.diameter.qosProfile.ResourceAllocationNotification": "0",
      "param.diameter.qosProfile.maxAuthDL": "string",
      "param.diameter.qosProfile.maxAuthUL": "string",
      "param.diameter.qosProfile.minRateDL": "string",
      "param.diameter.qosProfile.minRateUL": "string",
      "param.diameter.qosProfile.qci": "1"
    }
  ],
  "key": "string",
  "sourceVersion": "string",
  "topic": "string"
}
```

Delete Traffic for Diameter QoS

Table 2-177 Request/Response Body Parameters

Field Name	Data Type	Constraints	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
trafficDiameterQoS Name	string		M	Traffic Diameter QoS Name

2.32 Traffic for ADC Rule

Table 2-178 Supported REST APIs

Description	HTTP Method or Custom Operation	Resource URI	Possible Result Code
Create Traffic Adc Rule	POST	{apiRoot}/oc-cnpolicy- configuration/v1/ policydata/pcrf/ adcrules	See Table A-3
Export Traffic Adc Rule	GET	{apiRoot}/oc-cnpolicy- configuration/v1/ policydata/pcrf/ adcrules/export	See Table A-1
Import Traffic Adc Rule	POST	{apiRoot}/oc-cnpolicy- configuration/v1/ policydata/pcrf/ adcrules/import	See Table A-3
Get Traffic Adc Rule	GET	{apiRoot}/oc-cnpolicy- configuration/v1/ policydata/pcrf/ adcrules/ {trafficAdcRuleName}	See Table A-1
Update Traffic Adc Rule	PUT	{apiRoot}/oc-cnpolicy- configuration/v1/ policydata/pcrf/ adcrules/ {trafficAdcRuleName}	See Table A-2
Delete Traffic Adc Rule	DELETE	{apiRoot}/oc-cnpolicy- configuration/v1/ policydata/pcrf/ adcrules/ {trafficAdcRuleName}	See Table A-4

Create, Get, and Update Traffic for ADC Rule

Table 2-179 Data structures supported by the POST, GET, and PUT Response Body

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
description	string	O	

Table 2-179 (Cont.) Data structures supported by the POST, GET, and PUT Response Body

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
name	string	M	
param.diameter.adc Rule.FlowStatus	string	O	Allowed values: • 0 • 1 • 2 • 3
param.diameter.adc Rule.MeteringMethod	string	O	Allowed values: • 0 • 1 • 2 • 3
param.diameter.adc Rule.MonitoringKey	string	O	
param.diameter.adc Rule.Offline	string	O	Allowed values: • 0 • 1
param.diameter.adc Rule.Online	string	O	Allowed values: • 0 • 1
param.diameter.adc Rule.Precedence	string	O	
param.diameter.adc Rule.RatingGroup	string	O	
param.diameter.adc Rule.ReportingLevel	string	O	Allowed values: • 0 • 1
param.diameter.adc Rule.ServiceIdentifier	string	O	
param.diameter.adc Rule.maxAuthDL	string	O	
param.diameter.adc Rule.maxAuthUL	string	O	
param.diameter.adc Rule.name	string	M	
param.diameter.adc Rule.tdfApplicationIdentifier	string	O	
param.diameter.adc Rule.tdfMuteNotification	string	O	Allowed values: • 0
param.diameter.adc Rule.tdfRedirectAddressType	string	O	Allowed values: • 0 • 1 • 2 • 3

Table 2-179 (Cont.) Data structures supported by the POST, GET, and PUT Response Body

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
param.diameter.adcRule.tdfRedirectServerAddress	string	O	
param.diameter.adcRule.tdfRedirectSupport	string	O	Allowed values: • 0 • 1

Sample Request Body structure for POST and PUT operations:

```
{
  "description": "string",
  "name": "string",
  "param.diameter.adcRule.FlowStatus": "0",
  "param.diameter.adcRule.MeteringMethod": "0",
  "param.diameter.adcRule.MonitoringKey": "string",
  "param.diameter.adcRule.Offline": "0",
  "param.diameter.adcRule.Online": "0",
  "param.diameter.adcRule.Precedence": "string",
  "param.diameter.adcRule.RatingGroup": "string",
  "param.diameter.adcRule.ReportingLevel": "0",
  "param.diameter.adcRule.ServiceIdentifier": "string",
  "param.diameter.adcRule.maxAuthDL": "string",
  "param.diameter.adcRule.maxAuthUL": "string",
  "param.diameter.adcRule.name": "string",
  "param.diameter.adcRule.tdfApplicationIdentifier": "string",
  "param.diameter.adcRule.tdfMuteNotification": "0",
  "param.diameter.adcRule.tdfRedirectAddressType": "0",
  "param.diameter.adcRule.tdfRedirectServerAddress": "string",
  "param.diameter.adcRule.tdfRedirectSupport": "0"
}
```

Sample Response Body structure for GET, POST and PUT operations:

```
{
  "description": "string",
  "name": "string",
  "param.diameter.adcRule.FlowStatus": "0",
  "param.diameter.adcRule.MeteringMethod": "0",
  "param.diameter.adcRule.MonitoringKey": "string",
  "param.diameter.adcRule.Offline": "0",
  "param.diameter.adcRule.Online": "0",
  "param.diameter.adcRule.Precedence": "string",
  "param.diameter.adcRule.RatingGroup": "string",
  "param.diameter.adcRule.ReportingLevel": "0",
  "param.diameter.adcRule.ServiceIdentifier": "string",
  "param.diameter.adcRule.maxAuthDL": "string",
  "param.diameter.adcRule.maxAuthUL": "string",
}
```

```

"param.diameter.adcRule.name": "string",
"param.diameter.adcRule.tdfApplicationIdentifier": "string",
"param.diameter.adcRule.tdfMuteNotification": "0",
"param.diameter.adcRule.tdfRedirectAddressType": "0",
"param.diameter.adcRule.tdfRedirectServerAddress": "string",
"param.diameter.adcRule.tdfRedirectSupport": "0"
}

```

Export/Import Traffic for ADC Rule

Table 2-180 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
date	string		Current timestamp
errors	array		
errors:message	string		
errors:name	string		
exportData	array	M	Exported list of traffic Adc Rule. For more information, see Create, Get, and Update Traffic for ADC Rule
key	string		Indicates the ID
sourceVersion	string		System version of the product from which data is exported
topic	string	M	Topic of each managed object

Sample Request Body structure for Import/Export operations:

```

{
  "date": "string",
  "errors": [
    {
      "message": "string",
      "name": "string"
    }
  ],
  "exportData": [
    {
      "description": "string",
      "name": "string",
      "param.diameter.adcRule.FlowStatus": "0",
      "param.diameter.adcRule.MeteringMethod": "0",
      "param.diameter.adcRule.MonitoringKey": "string",
      "param.diameter.adcRule.Offline": "0",
      "param.diameter.adcRule.Online": "0",
      "param.diameter.adcRule.Precedence": "string",
      "param.diameter.adcRule.RatingGroup": "string",
      "param.diameter.adcRule.ReportingLevel": "0",
      "param.diameter.adcRule.ServiceIdentifier": "string",

```

```

        "param.diameter.adcRule.maxAuthDL": "string",
        "param.diameter.adcRule.maxAuthUL": "string",
        "param.diameter.adcRule.name": "string",
        "param.diameter.adcRule.tdfApplicationIdentifier": "string",
        "param.diameter.adcRule.tdfMuteNotification": "0",
        "param.diameter.adcRule.tdfRedirectAddressType": "0",
        "param.diameter.adcRule.tdfRedirectServerAddress": "string",
        "param.diameter.adcRule.tdfRedirectSupport": "0"
    }
},
"key": "string",
"sourceVersion": "string",
"topic": "string"
}

```

Delete Traffic for ADC Rule

Table 2-181 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
trafficAdcRuleName	string	M	Traffic ADC Rule Name

2.33 Time Period

Table 2-182 PCRF and PCF Time Period APIs

Description	HTTP Method or Custom Operation	Resource URI	Possible Result Code
Get Time Period	GET	{apiRoot}/oc-cnpolicy-configuration/v1/timePeriod/{timePeriodName}	See Table A-1
Update Time Period	PUT	{apiRoot}/oc-cnpolicy-configuration/v1/timePeriod/{timePeriodName}	See Table A-2
Delete Time Period	DELETE	{apiRoot}/oc-cnpolicy-configuration/v1/timePeriod/{timePeriodName}	See Table A-4
Create Time Period	POST	{apiRoot}/oc-cnpolicy-configuration/v1/timePeriod	See Table A-3

Table 2-183 PCF Time Period REST APIs

Description	HTTP Method or Custom Operation	Resource URI	Possible Result Code
Get Time Period	GET	{apiRoot}/oc-cnpolicy-configuration/v1/timePeriod/{timePeriodName}	See Table A-1
Update Time Period	PUT	{apiRoot}/oc-cnpolicy-configuration/v1/timePeriod/{timePeriodName}	See Table A-2
Delete Time Period	DELETE	{apiRoot}/oc-cnpolicy-configuration/v1/timePeriod/{timePeriodName}	See Table A-4
Create Time Period	POST	{apiRoot}/oc-cnpolicy-configuration/v1/timePeriod	See Table A-3

Create, Get, and Update Time Period**Table 2-184 Data structures supported by the POST, GET, and PUT Response Body**

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
description	string	O	Provide the description.
name	string	M	Provide the name.
precedence	string	O	Provide the precedence.
timeSlot	TimeSlot	O	

Table 2-185 TimeSlot

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
daysOfMonth	string	O	
daysOfWeek	string	O	
endTime	string	O	
monthsOfYear	string	O	
startTime	string	O	
years	string	O	

Sample Request Body structure for GET, POST, and PUT operations:

```
{
  "name": "string",
  "description": "string",
  "precedence": "string",
```

```

"timeSlot": [
  {
    "years": "string",
    "monthsOfYear": "string",
    "daysOfMonth": "string",
    "daysOfWeek": "string",
    "startTime": "string",
    "endTime": "string"
  }
]
}

```

Export/Import Time Period

Table 2-186 Export/Import Time Period APIs

Description	HTTP Method or Custom Operation	Resource URI	Possible Result Code
PCF Import Time Period	POST	{apiRoot}/oc-cnpolicy-configuration/v1/timePeriod/import	See Table A-3
PCF Export Time Period	GET	{apiRoot}/oc-cnpolicy-configuration/v1/timePeriod/export	See Table A-1

Table 2-187 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
date	string		Current timestamp
errors	array		
errors:message	string		
errors:name	string		
exportData	array	M	Exported list of time period.
key	string		Indicates the ID
sourceVersion	string		System version of the product from which data is exported
topic	string	M	Topic of each managed object

Sample Request Body structure for Import/Export operations:

```

{
  "topic": "string",
  "sourceVersion": "string",
  "date": "string",
  "exportData": [
    {
      "name": "string",

```

```

    "description": "string",
    "precedence": "string",
    "timeSlot": [
      {
        "years": "string",
        "monthsOfYear": "string",
        "daysOfMonth": "string",
        "daysOfWeek": "string",
        "startTime": "string",
        "endTime": "string"
      }
    ]
  },
  ],
  "errors": [
    {
      "name": "string",
      "message": "string"
    }
  ]
}

```

2.34 Predefined Pcc Rule Base

Table 2-188 Supported REST APIs

Description	HTTP Method or Custom Operation	Resource URI	Possible Result Code
Create Predefined Pcc Rule Base	POST	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcrf/predefinedpccrules	See Table A-3
Export Predefined Pcc Rule Base	GET	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcrf/predefinedpccrules/export	See Table A-1
Import Predefined Pcc Rule Base	POST	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcrf/predefinedpccrules/import	See Table A-3
Get Predefined Pcc Rule Base	GET	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcrf/predefinedpccrules/{predefinedPccRuleBaseName}	See Table A-1

Table 2-188 (Cont.) Supported REST APIs

Description	HTTP Method or Custom Operation	Resource URI	Possible Result Code
Update Predefined Pcc Rule Base	PUT	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcrf/predefinedpccrulebases/{predefinedPccRuleBaseName}	See Table A-2
Delete Predefined Pcc Rule Base	DELETE	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcrf/predefinedpccrulebases/{predefinedPccRuleBaseName}	See Table A-4

Create, Get, and Update Predefined Pcc Rule Base

Table 2-189 Data structures supported by the POST, GET, and PUT Response Body

Field Name	Data Type	Mandatory(M)/Optional(O)/Conditional(C)	Description
name	string	M	
param.diameter.pccPredefBaseRule.description	string	O	
param.diameter.pccPredefBaseRule.name	string	O	

Sample Request Body structure for POST and PUT operations:

```
{
  "name": "string",
  "param.diameter.pccPredefBaseRule.description": "string",
  "param.diameter.pccPredefBaseRule.name": "string"
}
```

Sample Response Body structure for GET, POST and PUT operations:

```
{
  "name": "string",
  "param.diameter.pccPredefBaseRule.description": "string",
  "param.diameter.pccPredefBaseRule.name": "string"
}
```

Export/Import Predefined Pcc Rule Base

Table 2-190 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
date	string		Current timestamp
errors	array		
errors:message	string		
errors:name	string		
exportData	array	M	Exported list of predefined Pcc Rule Base. For more information, see Table 2-189 .
key	string		Indicates the ID
sourceVersion	string		System version of the product from which data is exported
topic	string	M	Topic of each managed object

Sample Request Body structure for Import/Export operations:

```

{
  "date": "string",
  "errors": [
    {
      "message": "string",
      "name": "string"
    }
  ],
  "exportData": [
    {
      "name": "string",
      "param.diameter.pccPredefBaseRule.description": "string",
      "param.diameter.pccPredefBaseRule.name": "string"
    }
  ],
  "key": "string",
  "sourceVersion": "string",
  "topic": "string"
}

```

Delete Predefined Pcc Rule Base

Table 2-191 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
predefinedPccRuleBase Name	string	M	Predefined Pcc Rule Base Name

2.35 Predefined Pcc Rule

Table 2-192 Supported REST APIs

Description	HTTP Method or Custom Operation	Resource URI	Possible Result Code
Create Predefined Pcc Rule	POST	{apiRoot}/oc-cnpolicy- configuration/v1/ policydata/pcrf/ predefinedpccrules	See Table A-3
Export Predefined Pcc Rule	GET	{apiRoot}/oc-cnpolicy- configuration/v1/ policydata/pcrf/ predefinedpccrules/ export	See Table A-1
Import Predefined Pcc Rule	POST	{apiRoot}/oc-cnpolicy- configuration/v1/ policydata/pcrf/ predefinedpccrules/ import	See Table A-3
Get Predefined Pcc Rule	GET	{apiRoot}/oc-cnpolicy- configuration/v1/ policydata/pcrf/ predefinedpccrules/ {predefinedPccRuleNa me}	See Table A-1
Update Predefined Pcc Rule	PUT	{apiRoot}/oc-cnpolicy- configuration/v1/ policydata/pcrf/ predefinedpccrules/ {predefinedPccRuleNa me}	See Table A-2
Delete Predefined Pcc Rule	DELETE	{apiRoot}/oc-cnpolicy- configuration/v1/ policydata/pcrf/ predefinedpccrules/ {predefinedPccRuleNa me}	See Table A-4

Create, Get, and Update Predefined Pcc Rule**Table 2-193 Data structures supported by the POST, GET, and PUT Response Body**

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
name	string	M	
param.diameter.pccPredefRule.MonitoringKey	string	O	
param.diameter.pccPredefRule.description	string	O	
param.diameter.pccPredefRule.name	string	O	

Sample Request Body structure for POST and PUT operations:

```
{
  "name": "string",
  "param.diameter.pccPredefRule.MonitoringKey": "string",
  "param.diameter.pccPredefRule.description": "string",
  "param.diameter.pccPredefRule.name": "string"
}
```

Sample Response Body structure for GET, POST and PUT operations:

```
{
  "name": "string",
  "param.diameter.pccPredefRule.MonitoringKey": "string",
  "param.diameter.pccPredefRule.description": "string",
  "param.diameter.pccPredefRule.name": "string"
}
```

Export/Import Predefined Pcc Rule**Table 2-194 Request/Response Body Parameters**

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
date	string		Current timestamp
errors	array		
errors:message	string		
errors:name	string		
exportData	array	M	Exported list of predefined Pcc Rule.
key	string		Indicates the ID

Table 2-194 (Cont.) Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
sourceVersion	string		System version of the product from which data is exported
topic	string	M	Topic of each managed object

Sample Request Body structure for Import/Export operations:

```

{
  "date": "string",
  "errors": [
    {
      "message": "string",
      "name": "string"
    }
  ],
  "exportData": [
    {
      "name": "string",
      "param.diameter.pccPredefRule.MonitoringKey": "string",
      "param.diameter.pccPredefRule.description": "string",
      "param.diameter.pccPredefRule.name": "string"
    }
  ],
  "key": "string",
  "sourceVersion": "string",
  "topic": "string"
}

```

Delete Predefined Pcc Rule**Table 2-195 Request/Response Body Parameters**

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
predefinedPccRuleName	string	M	Predefined Pcc Rule Name

2.36 Predefined Adc Rule Base

Table 2-196 Supported REST APIs

Description	HTTP Method or Custom Operation	Resource URI	Possible Result Code
Create Predefined Adc Rule Base	POST	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcrf/predefinedadcrulebases	See Table A-3
Export Predefined Adc Rule Base	GET	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcrf/predefinedadcrulebases/export	See Table A-1
Import Predefined Adc Rule Base	POST	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcrf/predefinedadcrulebases/import	See Table A-3
Get Predefined Adc Rule Base	GET	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcrf/predefinedadcrulebases/{predefinedAdcRuleBaseName}	See Table A-1
Update Predefined Adc Rule Base	PUT	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcrf/predefinedadcrulebases/{predefinedAdcRuleBaseName}	See Table A-2
Delete Predefined Adc Rule Base	DELETE	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcrf/predefinedadcrulebases/{predefinedAdcRuleBaseName}	See Table A-4

Create, Get, and Update Predefined Adc Rule Base

Table 2-197 Data structures supported by the POST, GET, and PUT Response Body

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
name	string	M	
param.diameter.adcPredefBaseRule.description	string	O	

Table 2-197 (Cont.) Data structures supported by the POST, GET, and PUT Response Body

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
param.diameter.adcPredefBaseRule.name	string	O	

Sample Request Body structure for POST and PUT operations:

```
{
  "name": "string",
  "param.diameter.adcPredefBaseRule.description": "string",
  "param.diameter.adcPredefBaseRule.name": "string"
}
```

Sample Response Body structure for GET, POST and PUT operations:

```
{
  "name": "string",
  "param.diameter.adcPredefBaseRule.description": "string",
  "param.diameter.adcPredefBaseRule.name": "string"
}
```

Export/Import Predefined Adc Rule Base

Table 2-198 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
date	string		Current timestamp
errors	array		
errors:message	string		
errors:name	string		
exportData	array	M	Exported list of predefined Adc Base Rule.
key	string		Indicates the ID
sourceVersion	string		System version of the product from which data is exported
topic	string	M	Topic of each managed object

Sample Request Body structure for Import/Export operations:

```
{
  "date": "string",
```

```

"errors": [
  {
    "message": "string",
    "name": "string"
  }
],
"exportData": [
  {
    "name": "string",
    "param.diameter.adcPredefBaseRule.description": "string",
    "param.diameter.adcPredefBaseRule.name": "string"
  }
],
"key": "string",
"sourceVersion": "string",
"topic": "string"
}

```

Delete Predefined Adc Rule Base

Table 2-199 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
predefinedAdcRuleBase Name	string	M	Predefined Adc Rule Base Name

2.37 Predefined Adc Rule

Table 2-200 Supported REST APIs

Description	HTTP Method or Custom Operation	Resource URI	Possible Result Code
Create Predefined Adc Rule	POST	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcrf/predefinedadcrules	See Table A-3
Export Predefined Adc Rule	GET	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcrf/predefinedadcrules/export	See Table A-1
Import Predefined Adc Rule	POST	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcrf/predefinedadcrules/import	See Table A-3
Get Predefined Adc Rule	GET	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcrf/predefinedadcrules/{predefinedAdcRuleName}	See Table A-1

Table 2-200 (Cont.) Supported REST APIs

Description	HTTP Method or Custom Operation	Resource URI	Possible Result Code
Update Predefined Adc Rule	PUT	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcrf/predefinedadcrules/{predefinedAdcRuleName}	See Table A-2
Delete Predefined Adc Rule	DELETE	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcrf/predefinedadcrules/{predefinedAdcRuleName}	See Table A-4

Create, Get, and Update Predefined Adc Rule**Table 2-201 Data structures supported by the POST, GET, and PUT Response Body**

Field Name	Data Type	Mandatory(M)/Optional(O)/Conditional(C)	Description
name	string	M	
param.diameter.adcPredefRule.description	string	O	
param.diameter.adcPredefRule.name	string	O	

Sample Request Body structure for POST and PUT operations:

```
{
  "name": "string",
  "param.diameter.adcPredefRule.description": "string",
  "param.diameter.adcPredefRule.name": "string"
}
```

Sample Response Body structure for GET, POST and PUT operations:

```
{
  "name": "string",
  "param.diameter.adcPredefBaseRule.description": "string",
  "param.diameter.adcPredefBaseRule.name": "string"
}
```

Export/Import Predefined Adc Rule**Table 2-202 Request/Response Body Parameters**

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
date	string		Current timestamp
errors	array		
errors:message	string		
errors:name	string		
exportData	array	M	Exported list of predefined Adc Rule.
key	string		Indicates the ID
sourceVersion	string		System version of the product from which data is exported
topic	string	M	Topic of each managed object

Sample Request Body structure for Import/Export operations:

```
{
  "date": "string",
  "errors": [
    {
      "message": "string",
      "name": "string"
    }
  ],
  "exportData": [
    {
      "name": "string",
      "param.diameter.adcPredefBaseRule.description": "string",
      "param.diameter.adcPredefBaseRule.name": "string"
    }
  ],
  "key": "string",
  "sourceVersion": "string",
  "topic": "string"
}
```

Delete Predefined Adc Rule**Table 2-203 Request/Response Body Parameters**

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
predefinedAdcRuleName	string	M	Predefined Adc Rule Name

2.38 PCRF Presence Reporting Area

Table 2-204 Supported REST APIs

Description	HTTP Method or Custom Operation	Resource URI	Possible Result Code
Create PCRF Presence Reporting Area	POST	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcrf/pras	See Table A-3
Export PCRF Presence Reporting Area	GET	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcrf/pras/export	See Table A-1
Import PCRF Presence Reporting Area	POST	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcrf/pras/import	See Table A-3
Get PCRF Presence Reporting Area	GET	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcrf/pras/{praPcrfName}	See Table A-1
Update PCRF Presence Reporting Area	PUT	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcrf/pras/{praPcrfName}	See Table A-2
Delete PCRF Presence Reporting Area	DELETE	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcrf/pras/{praPcrfName}	See Table A-4

Create, Get, and Update Pra

Table 2-205 Data structures supported by the POST, GET, and PUT Response Body

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
description	string	O	
id	string	M	
name	string	M	
praltems	array	O	
type	string		Allowed value: Core Network pre-configured

Table 2-206 praltems

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
cgi	Cgi	O	

Table 2-206 (Cont.) praltems

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
ecgi	Ecgi	O	Allowed values: • -1 • 0 • 1 • 2 • 3
home_enodeb	HomeEnodeb	O	
macro_enodeb	MacroEnodeb	O	
rai	RAI		
sai	SAI		
tai	TAI		
type	string		Allowed values: • tai • rai • macro_enodeb • home_enodeb • ecgi • sai • cgi

Table 2-207 cgi

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
ci	string	O	
lac	string	O	
mcc	string	O	
mnc	string	O	

Table 2-208 ecgi

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
eci	string	O	
mcc	string	O	
mnc	string	O	

Table 2-209 home_enodeb

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
henb	string	O	
mcc	string	O	
menb	string	O	
mnc	string	O	

Table 2-210 macro_enodeb

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
mcc	string	O	
menb	string	O	
mnc	string	O	

Table 2-211 rai

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
lac	string	O	
mcc	string	O	
mnc	string	O	
rac	string	O	

Table 2-212 sai

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
lac	string	O	
mcc	string	O	
mnc	string	O	
sac	string	O	

Table 2-213 tai

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
mcc	string	O	
mnc	string	O	
tac	string	O	

Sample Request Body structure for POST and PUT operations:

```

{
  "description": "string",
  "id": "string",
  "name": "string",
  "praItems": [
    {
      "cgi": {
        "ci": "string",
        "lac": "string",
        "mcc": "string",
        "mnc": "string"
      },
      "ecgi": {
        "eci": "string",
        "mcc": "string",
        "mnc": "string"
      },
      "home_enodeb": {
        "henb": "string",
        "mcc": "string",
        "menb": "string",
        "mnc": "string"
      },
      "macro_enodeb": {
        "mcc": "string",
        "menb": "string",
        "mnc": "string"
      },
      "rai": {
        "lac": "string",
        "mcc": "string",
        "mnc": "string",
        "rac": "string"
      },
      "sai": {
        "lac": "string",
        "mcc": "string",
        "mnc": "string",
        "sac": "string"
      },
      "tai": {
        "mcc": "string",
        "mnc": "string",
        "tac": "string"
      },
      "type": "cgi"
    }
  ],
  "type": "Core Network pre-configured"
}

```

Sample Response Body structure for GET, POST and PUT operations:

```
{
  "description": "string",
  "id": "string",
  "name": "string",
  "praItems": [
    {
      "cgi": {
        "ci": "string",
        "lac": "string",
        "mcc": "string",
        "mnc": "string"
      },
      "ecgi": {
        "eci": "string",
        "mcc": "string",
        "mnc": "string"
      },
      "home_enodeb": {
        "henb": "string",
        "mcc": "string",
        "menb": "string",
        "mnc": "string"
      },
      "macro_enodeb": {
        "mcc": "string",
        "menb": "string",
        "mnc": "string"
      },
      "rai": {
        "lac": "string",
        "mcc": "string",
        "mnc": "string",
        "rac": "string"
      },
      "sai": {
        "lac": "string",
        "mcc": "string",
        "mnc": "string",
        "sac": "string"
      },
      "tai": {
        "mcc": "string",
        "mnc": "string",
        "tac": "string"
      },
      "type": "cgi"
    }
  ],
  "type": "Core Network pre-configured"
}
```

Export/Import Pra

Table 2-214 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
date	string		Current timestamp
errors	array		
errors:message	string		
errors:name	string		
exportData	array	M	Exported list of Pra.
key	string		Indicates the ID
sourceVersion	string		System version of the product from which data is exported
topic	string	M	Topic of each managed object

Sample Request Body structure for Import/Export operations:

```
{
  "date": "string",
  "errors": [
    {
      "message": "string",
      "name": "string"
    }
  ],
  "exportData": [
    {
      "description": "string",
      "id": "string",
      "name": "string",
      "praItems": [
        {
          "cgi": {
            "ci": "string",
            "lac": "string",
            "mcc": "string",
            "mnc": "string"
          },
          "ecgi": {
            "eci": "string",
            "mcc": "string",
            "mnc": "string"
          },
          "home_enodeb": {
            "henb": "string",
            "mcc": "string",
            "menb": "string",
            "mnc": "string"
          }
        }
      ]
    }
  ],
}
```

```

    "macro_enodeb": {
      "mcc": "string",
      "menb": "string",
      "mnc": "string"
    },
    "rai": {
      "lac": "string",
      "mcc": "string",
      "mnc": "string",
      "rac": "string"
    },
    "sai": {
      "lac": "string",
      "mcc": "string",
      "mnc": "string",
      "sac": "string"
    },
    "tai": {
      "mcc": "string",
      "mnc": "string",
      "tac": "string"
    },
    "type": "cgi"
  },
  "type": "Core Network pre-configured"
}
},
"key": "string",
"sourceVersion": "string",
"topic": "string"
}

```

Delete Pra

Table 2-215 Request/Response Body Parameters

Field Name	Data Type	Constraints	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
praPcrfName	string		M	Pra Pcrf Name

2.39 Media Profile

Table 2-216 PCRF and PCF Media Profile APIs

Description	HTTP Method or Custom Operation	Resource URI	Possible Result Code
Get Media Profile	GET	{apiRoot}/oc-cnpolicy- configuration/v1/ mediaProfile/ {mediaProfileName}	See Table A-1

Table 2-216 (Cont.) PCRF and PCF Media Profile APIs

Description	HTTP Method or Custom Operation	Resource URI	Possible Result Code
Update Media Profile	PUT	{apiRoot}/oc-cnpolicy-configuration/v1/mediaProfile/{mediaProfileName}	See Table A-2
Delete Media Profile	DELETE	{apiRoot}/oc-cnpolicy-configuration/v1/mediaProfile/{mediaProfileName}	See Table A-4
Create Media Profile	POST	{apiRoot}/oc-cnpolicy-configuration/v1/mediaProfile	See Table A-3

Table 2-217 PCF Media Profile APIs

Description	HTTP Method or Custom Operation	Resource URI	Possible Result Code
Get Media Profile	GET	{apiRoot}/oc-cnpolicy-configuration/v1/mediaProfile/{mediaProfileName}	See Table A-1
Update Media Profile	PUT	{apiRoot}/oc-cnpolicy-configuration/v1/mediaProfile/{mediaProfileName}	See Table A-2
Delete Media Profile	DELETE	{apiRoot}/oc-cnpolicy-configuration/v1/mediaProfile/{mediaProfileName}	See Table A-4
Create Media Profile	POST	{apiRoot}/oc-cnpolicy-configuration/v1/mediaProfile	See Table A-3

Create, Get, and Update Media Profile**Table 2-218 Data structures supported by the POST, GET, and PUT Response Body**

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
codecName	string	M	
description	string		Provide the description of the Media.
frameSizeInBytes	integer	M	enter a range in 0 to 65535
frameSizeInMS	number	M	
id	string	M	
mediaType	string	M	
name	string	M	
pTime	integer	M	enter a range in 0 to 65535

Table 2-218 (Cont.) Data structures supported by the POST, GET, and PUT Response Body

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
payLoad	integer	M	enter a range in 0 to 255
sampleRate	integer	M	enter a range in 0 to 65535
transportType	string ENUM	M	Possible values: RTP/AVP RTP/SAVP RTP/AVPF
useDefaultPTime	boolean	M	

Sample Request Body structure for GET, POST, and PUT operations:

```
{
  "id": "string",
  "name": "string",
  "description": "string",
  "codecName": "string",
  "transportType": "RTP/AVP",
  "mediaType": "string",
  "enter a range in 0 to 255": 255,
  "enter a range in 0 to 65535": 65535,
  "frameSizeInMS": 0,
  "useDefaultPTime": true
}
```

Export/Import Media Profile

Table 2-219 Export/Import Media Profile APIs

Description	HTTP Method or Custom Operation	Resource URI	Possible Result Code
PCF Import Media Profile	POST	{apiRoot}/oc-cnpolicy-configuration/v1/mediaProfile/import	See Table A-3
PCF Export Media Profile	GET	{apiRoot}/oc-cnpolicy-configuration/v1/mediaProfile/export	See Table A-1

Table 2-220 Export/Import Media Profile Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
date	string	M	Current timestamp
errors	array	M	
errors:message	string	M	

Table 2-220 (Cont.) Export/Import Media Profile Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
errors:name	string	M	
exportData	array	M	Exported list of media profile.
key	string	M	Indicates the ID
sourceVersion	string	O	System version of the product from which data is exported
topic	string	M	Topic of each managed object

Sample Request Body structure for Import/Export operations:

```
{
  "topic": "string",
  "sourceVersion": "string",
  "date": "string",
  "exportData": [
    {
      "id": "string",
      "name": "string",
      "description": "string",
      "codecName": "string",
      "transportType": "RTP/AVP",
      "mediaType": "string",
      "enter a range in 0 to 255": 255,
      "enter a range in 0 to 65535": 65535,
      "frameSizeInMS": 0,
      "useDefaultPTime": true
    }
  ],
  "errors": [
    {
      "name": "string",
      "message": "string"
    }
  ]
}
```

Delete Media Profile

Table 2-221 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
mediaProfileName	string	M	Media Profile Name

2.40 Match List

Table 2-222 Supported REST APIs

Description	HTTP Method or Custom Operation	Resource URI	Possible Result Code
Export Match List	GET	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/common/matchList/export	See Table A-1
Import Match List	POST	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/common/matchList/import	See Table A-3
Delete Match List	DELETE	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/common/matchList/{matchListName}	See Table A-4
Get Match List	GET	/oc-cnpolicy-configuration/v1/policydata/common/matchList/{matchListName}	See Table A-1
Update Match List	PUT	/oc-cnpolicy-configuration/v1/policydata/common/matchList/{matchListName}	See Table A-2
Create Match List	POST	/oc-cnpolicy-configuration/v1/policydata/common/matchList	See Table A-3

Export/Import Match List

Table 2-223 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
date	string	O	Current timestamp
exportData.description	string	O	Includes a brief description of the match list.
exportData.id	string	M	A unique identifier for the match list. This unique identifier cannot be changed once set.
exportData.options.label	string	O	Includes a label for the match list.

Table 2-223 (Cont.) Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
exportData.items	array	M	Includes a list or array of homogeneous items in the match list. The data type of the items in the list must be the same as the data type of exportData.type parameter.
exportData.name	string	M	Specifies the name of the match list.
exportData.type	string	M	Specifies the data type of the items in the match list. The allowed data types are: • string • wildcard • ipv4 • ipv6 • Regular expression
sourceVersion	string	O	System version of the product from which data is exported
topic	string	M	Topic of each managed object

Sample Request Body structure for Import/Export operations:

```

{
  "date": "string",
  "errors": [
    {
      "message": "string",
      "name": "string"
    }
  ],
  "exportData": [
    {
      "description": "string",
      "id": "string",
      "items": [
        "string"
      ],
      "name": "string",
      "type": "string"
    }
  ],
  "sourceVersion": "string",
  "topic": "string"
}

```

Sample cURL GET command

```
curl -X 'GET' \
  'http://10.75.206.134:8000/oc-cnpolicy-configuration/v1/policydata/common/
matchList/export' \
  -H 'accept: application/json'
```

Sample cURL POST command

```
curl -X 'POST' \
  'http://10.75.206.134:8000/oc-cnpolicy-configuration/v1/policydata/common/
matchList/import' \
  -H 'accept: application/json' \
  -H 'Content-Type: application/json' \
  -d '{
    "topic": "string",
    "sourceVersion": "string",
    "date": "string",
    "errors": [
      {
        "name": "string",
        "message": "string"
      }
    ],
    "exportData": [
      {
        "id": "string",
        "name": "string",
        "description": "string",
        "type": "STRING",
        "items": [
          "string"
        ]
      }
    ]
  }'
```

Sample cURL DELETE command

```
curl -X 'DELETE' 'http://localhost:8000/oc-cnpolicy-configuration/v1/
policydata/common/matchList/{matchListName}' -H 'accept: */*'
```

2.41 Dropdown Blocks

Table 2-224 Supported REST APIs

Description	HTTP Method or Custom Operation	Resource URI	Possible Result Code
Export dropdown blocks	GET	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/common/dropdownBlocks/export	See Table A-1
Import Dropdown Blocks	POST	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/common/dropdownBlocks/import	See Table A-3

Export/Import Dropdown Blocks

Table 2-225 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
date	string		Current timestamp
exportData.attrName	string		
exportData.description	string		
exportData.options.label	string		
exportData.options.value	string		
exportData.topic	string		
exportData.type	string		
sourceVersion	string		System version of the product from which data is exported
topic	string	M	Topic of each managed object

Sample Request Body structure for Import/Export operations:

```
{
  "date": "string",
  "errors": [
    {
      "message": "string",
      "name": "string"
    }
  ],
  "exportData": [
    {
      "attrName": "string",
      "description": "string",
```

```

    "options": [
      {
        "label": "string",
        "value": "string"
      }
    ],
    "topic": "string",
    "type": "DYNAMIC"
  }
],
"sourceVersion": "string",
"topic": "string"
}

```

2.42 Custom Vendor

Create, Get, and Update Custom Vendor

Table 2-226 PCRF and PCF Custom Vendor APIs

API Name	HTTP Method or Custom Operation	Resource URI	Description	Possible Result Code
Get Custom Vendor	GET	{apiRoot}/oc-cnpolicy-configuration/v1/customVendor/{customVendorName}	Fetch the provided Custom Vendor details.	See Table A-1
Create Custom Vendor	POST	{apiRoot}/oc-cnpolicy-configuration/v1/customVendor	Create a Custom Vendor	See Table A-3
Update Custom Vendor	PUT	{apiRoot}/oc-cnpolicy-configuration/v1/customVendor/{customVendorName}	Update the provided Custom Vendor information.	See Table A-2
Delete custom Vendor	DELETE	{apiRoot}/oc-cnpolicy-configuration/v1/customVendor/{customVendorName}	Delete the provided Custom vendor information.	See Table A-4

Table 2-227 PCF Custom Vendor APIs

API Name	HTTP Method or Custom Operation	Resource URI	Description	Possible Result Code
Get Custom Vendor	GET	{apiRoot}/oc-cnpolicy-configuration/v1/customVendor/{customVendorName}	Fetch the provided Custom Vendor details.	See Table A-1
Create Custom Vendor	POST	{apiRoot}/oc-cnpolicy-configuration/v1/customVendor	Create a Custom Vendor	See Table A-3
Update Custom Vendor	PUT	{apiRoot}/oc-cnpolicy-configuration/v1/customVendor/{customVendorName}	Update the provided Custom Vendor information.	See Table A-2
Delete custom Vendor	DELETE	{apiRoot}/oc-cnpolicy-configuration/v1/customVendor/{customVendorName}	Delete the provided Custom vendor information.	See Table A-4

Table 2-228 Data structures supported by the POST, GET, and PUT Response Body

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
description	string	O	Provide description about the Custom Vendor.
name	string	M	Provide a name to the Custom Vendor.
value	string	O	Provide a value to the Custom Vendor.

Sample Request Body structure for POST and PUT operations:

```
{
  "name": "string",
  "description": "string",
  "value": "string"
}
```

Export/Import Custom Vendor

Table 2-229 Export/Import Custom Vendor REST APIs

Description	HTTP Method or Custom Operation	Resource URI	Possible Result Code
Export Custom Vendor	GET	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/common/customattributes/customvendor/export	See Table A-1
Import Custom Vendor	POST	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/common/customattributes/customvendor/import	See Table A-3

Table 2-230 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
date	string		Current timestamp
errors	array		
errors:message	string		
errors:name	string		
exportData	array	M	Exported list of custom avp.
key	string		Indicates the ID
sourceVersion	string		System version of the product from which data is exported
topic	string	M	Topic of each managed object

Sample Request Body structure for Import/Export operations:

```
{
  "date": "string",
  "errors": [
    {
      "message": "string",
      "name": "string"
    }
  ],
  "exportData": [
    {
      "description": "string",
      "name": "string",
      "value": "string"
    }
  ],
  "key": "string",
```

```

    "sourceVersion": "string",
    "topic": "string"
  }

```

2.43 Custom Schema

Table 2-231 Supported REST APIs

Description	HTTP Method or Custom Operation	Resource URI	Possible Result Code
Export Custom Schema	GET	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/common/customattributes/customschema/export	See Table A-1
Import Custom Schema	POST	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/common/customattributes/customschema/import	See Table A-3

Export/Import Custom Schema

Table 2-232 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/Optional(O)/Conditional(C)	Description
date	string		Current timestamp
exportData.name	string		
exportData.type	string		
key			
sourceVersion	string		System version of the product from which data is exported
topic	string	M	Topic of each managed object

Sample Request Body structure for Import/Export operations:

```

{
  "date": "string",
  "errors": [
    {
      "message": "string",
      "name": "string"
    }
  ],
  "exportData": [
    {
      "name": "string",
      "tag": [

```

```

        "string"
      ]
    }
  ],
  "key": "string",
  "sourceVersion": "string",
  "topic": "string"
}

```

2.44 Custom AVP

Table 2-233 Supported REST APIs

Description	HTTP Method or Custom Operation	Resource URI	Possible Result Code
Create Custom AVP	POST	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/common/customattributes/avp	See Table A-3
Export Custom AVP	GET	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/common/customattributes/avp/export	See Table A-1
Import Custom AVP	POST	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/common/customattributes/avp/import	See Table A-3
Get Custom AVP	GET	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/common/customattributes/avp/{customAVPName}	See Table A-1
Update Custom AVP	PUT	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/common/customattributes/avp/{customAVPName}	See Table A-2
Delete Custom AVP	DELETE	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/common/customattributes/avp/{customAVPName}	See Table A-4

Create, Get, and Update Custom AVP Name

Table 2-234 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
vendorSpecificFlag	boolean		
avpCode	string		

Table 2-234 (Cont.) Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
avpType	string		- enumerated - float32 - float64 - grouped - id - int32 - int64 - ipFilterRule - octetString - time - uint32 - uint64 - uri - utf8String
description	string		
mandatoryFlag	boolean		
mayEncryptFlag	boolean		
name	string	M	
protectFlag	boolean		
rootAvp	string		
vendorId	string	M	10415 5535 21274 9 5263 3076 255 2636 4874
vendorSpecificFlag	boolean		

Sample Request body structure for POST and PUT operations:

```

{
  "VendorSpecificFlag": true,
  "avpCode": "string",
  "avpType": "address",
  "description": "string",
  "mandatoryFlag": true,
  "mayEncryptFlag": true,
  "name": "string",
  "protectFlag": true,
  "rootAvp": "ADC-Rule-Definition:10415",
  "vendorId": "10415",
  "vendorSpecificFlag": true
}

```

Sample Response body structure for GET, POST, and PUT operations:

```
{
  "VendorSpecificFlag": true,
  "avpCode": "string",
  "avpType": "address",
  "description": "string",
  "mandatoryFlag": true,
  "mayEncryptFlag": true,
  "name": "string",
  "protectFlag": true,
  "rootAvp": "ADC-Rule-Definition:10415",
  "vendorId": "10415",
  "vendorSpecificFlag": true
}
```

Delete Custom AVP**Table 2-235 Request/Response Body Parameters**

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
customAVPName	string	M	Custom AVP Name

Export/Import Custom AVP**Table 2-236 Request/Response Body Parameters**

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
date	string		Current timestamp
errors	array		
errors:message	string		
errors:name	string		
exportData	array	M	Exported list of custom avp.
key	string		Indicates the ID
sourceVersion	string		System version of the product from which data is exported
topic	string	M	Topic of each managed object

Sample Request Body structure for Import/Export operations:

```
{
  "date": "string",
  "errors": [
    {
      "message": "string",
      "name": "string"
    }
  ]
}
```

```

    }
  ],
  "exportData": [
    {
      "VendorSpecificFlag": true,
      "avpCode": "string",
      "avpType": "address",
      "description": "string",
      "mandatoryFlag": true,
      "mayEncryptFlag": true,
      "name": "string",
      "protectFlag": true,
      "rootAvp": "ADC-Rule-Definition:10415",
      "vendorId": "10415",
      "vendorSpecificFlag": true
    }
  ],
  "key": "string",
  "sourceVersion": "string",
  "topic": "string"
}

```

2.45 Charging Server

Table 2-237 Supported REST APIs

Description	HTTP Method or Custom Operation	Resource URI	Possible Result Code
Create Charging Server	POST	/oc-cnpolicy-configuration/v1/policy/chargingServer	See Table A-3
Export Charging Server	GET	/oc-cnpolicy-configuration/v1/policy/chargingServer/export	See Table A-1
Import Charging Server	POST	/oc-cnpolicy-configuration/v1/policy/chargingServer/import	See Table A-3
Get Charging Server	GET	/oc-cnpolicy-configuration/v1/policy/chargingServer/{chargingServerName}	See Table A-1
Update Charging Server	PUT	/oc-cnpolicy-configuration/v1/policy/chargingServer/{chargingServerName}	See Table A-2
Delete Charging Server	DELETE	/oc-cnpolicy-configuration/v1/policy/chargingServer/{chargingServerName}	See Table A-4

Get, Create, and Update Charging Server

Table 2-238 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
description	string		
hostName	string		
name	string	M	
port	string		
protocol	string	M	diameter radius tacacs+
security	boolean		
transport	string	M	tcp udp sctp

Sample Request body structure for POST and PUT operations:

```
{
  "description": "string",
  "hostName": "string",
  "name": "string",
  "port": "string",
  "protocol": "diameter",
  "security": true,
  "transport": "sctp"
}
```

Sample Response body structure for GET, POST, and PUT operations:

```
{
  "description": "string",
  "hostName": "string",
  "name": "string",
  "port": "string",
  "protocol": "diameter",
  "security": true,
  "transport": "sctp"
}
```

Delete Charging Server**Table 2-239 Request/Response Body Parameters**

Field Name	Data Type	Constraints	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
chargingServerName	string		M	Charging Server Name

Export/Import Charging Server**Table 2-240 Request/Response Body Parameters**

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
date	string		Current timestamp
errors	array		
errors:message	string		
errors:name	string		
exportData	array	M	Exported list of charging server. For more information, see Get, Create, and Update Charging Server .
key	string		Indicates the ID
sourceVersion	string		System version of the product from which data is exported
topic	string	M	Topic of each managed object

Sample Request Body structure for Import/Export operations:

```
{
  "date": "string",
  "errors": [
    {
      "message": "string",
      "name": "string"
    }
  ],
  "exportData": [
    {
      "description": "string",
      "hostName": "string",
      "name": "string",
      "port": "string",
      "protocol": "diameter",
      "security": true,
      "transport": "sctp"
    }
  ]
}
```

```

    ],
    "key": "string",
    "sourceVersion": "string",
    "topic": "string"
  }

```

2.46 PCRF Public Log

Table 2-241 Supported REST APIs

Description	HTTP Method or Custom Operation	Resource URI	Possible Result Code
Export Pcrf Log	GET	{apiRoot}/ocpm/pcrf/v1/configuration/diameter/logPcrf/export	See Table A-1
Import Pcrf Log	POST	{apiRoot}/ocpm/pcrf/v1/configuration/diameter/logPcrf/import	See Table A-3
Get Pcrf Log	GET	{apiRoot}/ocpm/pcrf/v1/configuration/service/logPcrf	See Table A-1
Update Pcrf Log	PUT	{apiRoot}/ocpm/pcrf/v1/configuration/service/logPcrf	See Table A-2

Get and Update PCRF Public Log

Table 2-242 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/Optional(O)/Conditional(C)	Description
packageLogLevel	Array	O	
rootLogLevel	string	M	Allowed values: • trace • debug • info • warn • error • fatal

Table 2-243 packageLogLevel

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
logLevelForPackage	string	O	Allowed values: • trace • debug • info • warn • error • fatal
packageName	string	M	

Export/Import PCRF Public Log

Table 2-244 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
date	string		Current timestamp
exportData	array		Exported list of Pcrf Log. For more information, see Get and Update PCRF Public Log .
sourceVersion	string		System version of the product from which data is exported
topic	string		Topic of each managed object

2.47 User Service

Table 2-245 Supported REST APIs

Description	HTTP Method or Custom Operation	Resource URI	Possible Result Code
Get User Service	GET	{apiRoot}/oc-cnpolicy-configuration/v1/services/pcfuser	See Table A-1
Update User Service	PUT	{apiRoot}/oc-cnpolicy-configuration/v1/services/pcfuser	See Table A-2
Export User Service	GET	{apiRoot}/oc-cnpolicy-configuration/v1/services/pcfuser/export	See Table A-1
Import User Service	POST	{apiRoot}/oc-cnpolicy-configuration/v1/services/pcfuser/import	See Table A-3

Get and Update User Service

Table 2-246 Request/Response Body Parameters

Field Name	Data Type	Constraints	Mandatory(M)/ Optional(O)/ Conditional(C)a ints	Description
chf	chf configuration		O	
common	CommonConfigu ration		O	
db	DBConfiguration		O	
system	UserSystemConf iguration		O	
udr	UDRConfiguratio n		O	

Table 2-247 chf Configuration

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
chf.retryProfileForInitMs gs	String	O	Specifies the retry or alternate routing options to communicate with CHF.
chf.retryProfileForSubsq tMsgs	String	O	Specifies the retry or alternate routing options to send subsequent messages to CHF.
chf.nfCommProfile	String	O	Indicates whether to assign a profile created on the NF Communication Profile page to CHF.

Table 2-247 (Cont.) chf Configuration

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
chf.pcfServiceName	String	O	Specifies the custom/ 3gpp defined PCF service name to be included in the Binding Header in the subscription request or notification responses sent towards CHF. Possible values: - Aggregate or custom service name that represents a group of PCF services with aggregated service level information. For example: npcfcustom-service - Any of the 3GPP defined PCF service names such as npcfsmpolicycontrol or npcfsmpolicy-control By default, the value of this parameter is empty.
messagePriority.messagePriorityProfile	String	O	Select one of the message priority profiles created on Message Profiles page that must be applied for CHF Connector. When a message profile is selected under Message Priority Profile section, support for 3GPP-SBI-Message-Priority header gets enabled for CHF Connector.

Table 2-248 CommonConfiguration

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
requestTimeout	string example: 1000	O	

Table 2-248 (Cont.) CommonConfiguration

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
resourceGetSub	boolean	O	

Table 2-249 DBConfiguration

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
indexing	Indexing	O	
keysPrecedence	ENUM	O	
userIndexKeys	ENUM	O	

Table 2-250 Indexing

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
indexByExtid	boolean	O	
indexByImsi	boolean	O	
indexByMsisdn	boolean	O	
indexByNai	boolean	O	

Table 2-251 UserSystemConfiguration

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
apiRoot	string	O	This is PCF User Service API Root URI. It is part of PCF user service. This value is auto injected at service deployment. User can also configure this manually. Default Value: N/A
logLevel	string, ENUM	O	Indicates the log level of PCF Session Management (SM) service. Default Value: WARN

Table 2-252 UDR Configuration

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
udr.retryProfileForInitMsgs	string	O	
udr.baseUri	string example: /nudr-dr/v1	O	
udr.supportedFeatures	string example: f	O	
udr.smDataVSANames	string	O	
udr.amDataUri	string example: /policy-data/ues/{ueId}/am-data	O	
udr.uePolicySetUri	string example: /policy-data/ues/{ueId}/ue-policy-set	O	
udr.smDataUri	string example: /policy-data/ues/{ueId}/sm-data	O	
udr.usageMonUri	string example: /policy-data/ues/{ueId}/sm-data/{usageMonId}	O	
udr.subsToNotifyUri	string example: /policy-data/subs-to-notify	O	
udr.subsToNotifySubsIdUri	string example: /policy-data/subs-to-notify/{subsId}	O	
udr.retryProfileForSubsqtmMsgs	string		
udr.smDataSubscriptionResource	integer		
smDataSubscriptionResource	string, ENUM		
udr.discoverUdrWithPolicyAsSupportedDataSet	boolean		udr
udr.requestTimeout	string example: 1000	O	
udr.explodeSnssai	boolean	O	
udr.enableDiscoveryOnDemand	boolean	O	
udr.retrySubscriptionAs	string	O	

Table 2-252 (Cont.) UDR Configuration

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
udr.nfCommProfile	String	O	Indicates whether to assign a profile created on the NF Communication Profile page to UDR.
udr.sendTargetAPIRouteInSubsToNotify	boolean	O	Specifies whether to send target API route header in subscribe to notify request towards UDR.
udr.sendInitDiscParamsInSubsToNotify	boolean	O	Specifies whether to send discovery parameters in subscribe to notify request towards UDR.
udr.sendProdIdInSubsToNotify	boolean	O	Specifies whether to send producer Id in Discovery header in subscribe to notify request towards UDR.
enableHttp11	boolean	O	
immRep	boolean	O	
enableImmRepGetFb	boolean	O	
messagePriority.messagePriorityProfile	String	O	Select one of the message priority profiles created on Message Profiles page that must be applied for UDR Connector. When a message profile is selected under Message Priority Profile section, support for 3GPP-SBI-Message-Priority header gets enabled for UDR Connector.

Sample Request body structure for PUT operations:

```
{
  "system": {
    "apiRoot": "string"
  },
  "common": {
    "requestTimeout": "1000"
  },
  "db": {
    "keysPrecedence": [
      "MSISDN"
    ]
  }
}
```

```

    ],
    "userIndexKeys": [
        "msisdn"
    ],
    "indexing": {
        "indexByMsisdn": true,
        "indexByExtid": true,
        "indexByImsi": true,
        "indexByNai": true
    }
},
"udr": {
    "retryProfileForInitMsgs": "string",
    "baseUri": "/nudr-dr/v1",
    "supportedFeatures": "f",
    "smDataVSANames": "string",
    "amDataUri": "/policy-data/ues/{ueId}/am-data",
    "uePolicySetUri": "/policy-data/ues/{ueId}/ue-policy-set",
    "smDataUri": "/policy-data/ues/{ueId}/sm-data",
    "usageMonUri": "/policy-data/ues/{ueId}/sm-data/{usageMonId}",
    "subsToNotifyUri": "/policy-data/subs-to-notify",
    "subsToNotifySubsIdUri": "/policy-data/subs-to-notify/{subsId}",
    "retryProfileForSubsqtMsgs": "string",
    "smDataSubscriptionResource": "1",
    "discoverUdrWithPolicyAsSupportedDataSet": true,
    "requestTimeout": "1000",
    "explodeSnssai": true,
    "enableDiscoveryOnDemand": true,
    "retrySubscriptionAs": "subsequent",
    "nfCommProfile": "string",
    "sendTargetAPIRouteInSubsToNotify": true,
    "sendInitDiscParamsInSubsToNotify": false,
    "sendProdIdInSubsToNotify": false "immRep": false,
    "enableImmRepGetFb": false
    "messagePriorityProfile": "string"
},
"chf": {
    "retryProfileForInitMsgs": "string",
    "retryProfileForSubsqtMsgs": "string",
    "nfCommProfile": "string"
    "pcfServiceName": "string"
    "messagePriorityProfile": "string"
},
"advancedSettings": [
    {
        "key": "string",
        "value": "string"
    }
]
}

```

Sample Response body structure for GET and PUT operations:

```

{
  "system": {
    "apiRoot": "string"
  },
  "common": {
    "requestTimeout": "1000"
  },
  "db": {
    "keysPrecedence": [
      "MSISDN"
    ],
    "userIndexKeys": [
      "msisdn"
    ],
    "indexing": {
      "indexByMsisdn": true,
      "indexByExtid": true,
      "indexByImsi": true,
      "indexByNai": true
    }
  },
  "udr": {
    "retryProfileForInitMsgs": "string",
    "baseUri": "/nudr-dr/v1",
    "supportedFeatures": "f",
    "smDataVSANames": "string",
    "amDataUri": "/policy-data/ues/{ueId}/am-data",
    "uePolicySetUri": "/policy-data/ues/{ueId}/ue-policy-set",
    "smDataUri": "/policy-data/ues/{ueId}/sm-data",
    "usageMonUri": "/policy-data/ues/{ueId}/sm-data/{usageMonId}",
    "subsToNotifyUri": "/policy-data/subs-to-notify",
    "subsToNotifySubsIdUri": "/policy-data/subs-to-notify/{subsId}",
    "retryProfileForSubsqtMsgs": "string",
    "smDataSubscriptionResource": "1",
    "discoverUdrWithPolicyAsSupportedDataSet": true,
    "requestTimeout": "1000",
    "explodeSnssai": true,
    "enableDiscoveryOnDemand": true,
    "retrySubscriptionAs": "subsequent",
    "nfCommProfile": "string",
    "sendTargetAPIRouteInSubsToNotify": true,
    "sendInitDiscParamsInSubsToNotify": false,
    "sendProdIdInSubsToNotify": false,
    "immRep": false,
    "enableImmRepGetFb": false
  },
  "chf": {
    "retryProfileForInitMsgs": "string",
    "retryProfileForSubsqtMsgs": "string",
    "nfCommProfile": "string"
  },
  "advancedSettings": [
    {
      "key": "string",

```

```

        "value": "string"
    }
  ]
}

```

Export/Import User Service

Table 2-253 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
date	string		Current timestamp
exportData	array		Exported list of user service. For more information, see Get and Update User Service .
sourceVersion	string		System version of product from which data is exported
topic	string		Topic of each managed object

Sample Request Body structure for Import/Export operations:

```

{
  "date": "string",
  "errors": [
    {
      "message": "string",
      "name": "string"
    }
  ],
  "exportData": {
    "chf": {
      "nfCommProfile": "string",
      "retryProfileForInitMsgs": "string",
      "retryProfileForSubsqMsgs": "string"
    },
    "common": {
      "requestTimeout": 1000,
      "resourceGetSub": true
    },
    "db": {
      "indexing": {
        "indexByExtid": true,
        "indexByImsi": true,
        "indexByMsisdn": true,
        "indexByNai": true
      },
      "keysPrecedence": [
        "EXTID"
      ],
      "userIndexKeys": [
        "extid"
      ]
    }
  }
}

```

```

    ]
  },
  "system": {
    "apiRoot": "string"
  },
  "udr": {
    "amDataUri": "/policy-data/ues/{ueId}/am-data",
    "baseUri": "/nudr-dr/v1",
    "discoverUdrWithPolicyAsSupportedDataSet": true,
    "enableDiscoveryOnDemand": true,
    "enableHttp11": true,
    "explodeSnssai": true,
    "nfCommProfile": "string",
    "requestTimeout": 1000,
    "retryProfileForInitMsgs": "string",
    "retryProfileForSubsqtMsgs": "string",
    "sendInitDiscParamsInSubsToNotify": false,
    "sendProdIdInSubsToNotify": false,
    "sendTargetAPIRouteInSubsToNotify": true,
    "smDataSubscriptionResource": "1",
    "smDataUri": "/policy-data/ues/{ueId}/sm-data",
    "subsToNotifySubsIdUri": "/policy-data/subs-to-notify/{subsId}",
    "subsToNotifyUri": "/policy-data/subs-to-notify",
    "supportedFeatures": "f",
    "uePolicySetUri": "/policy-data/ues/{ueId}/ue-policy-set",
    "usageMonUri": "/policy-data/ues/{ueId}/sm-data/{usageMonId}"
  }
},
"sourceVersion": "string",
"topic": "string"
}

```

2.48 Test Policy Projects

Table 2-254 Supported REST APIs

Description	HTTP Method or Custom Operation	Resource URI	Possible Result Code
Export test policy project	GET	{apiRoot}/oc-cnpolicy-configuration/v1/policymgmt/policytests/testpolicyproject/export	See Table A-1
Import test policy project	POST	{apiRoot}/oc-cnpolicy-configuration/v1/policymgmt/policytests/testpolicyproject/import	See Table A-3

Export/Import Test Policy Projects

Table 2-255 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
date	string		Current timestamp
exportData.script	string		
exportData.serviceType	string		
exportData.suiteName	string		
exportData.testcase.fieldVal.basicInfo.caseDesc	string		
exportData.testcase.fieldVal.basicInfo.caseName	string		
exportData.inputVal	string		
exportData.resVal	string		
exportData.name	string		
exportData.reqDataModel	string		
exportData.resDataModel	string		
exportData.suiteName	string		
exportData.testCaseScript	string		
key	string		
sourceVersion	string		System version of the product from which data is exported
topic	string	M	Topic of each managed object

Sample Request Body structure for Import/Export operations:

```

{
  "date": "string",
  "exportData": [
    {
      "script": "string",
      "serviceType": "string",
      "suiteName": "string",
      "testCase": [
        {
          "fieldVal": {
            "basicInfo": {
              "caseDesc": "string",
              "caseName": "string"
            },
            "inputVal": {},
            "resVal": {}
          },
          "name": "string",

```

```

        "reqDataModel": "string",
        "resDataModel": "string",
        "suiteName": "string",
        "testCaseScript": "string"
    }
  ]
}
],
"key": "string",
"sourceVersion": "string",
"topic": "string"
}

```

2.49 Data Model

Table 2-256 Supported REST APIs

Export data model	HTTP Method or Custom Operation	Resource URI	Possible Result Code
Import data model	GET	{apiRoot}/oc-cnpolicy-configuration/v1/policymgmt/polytests/datamodels/export	See Table A-1
Description	POST	{apiRoot}/oc-cnpolicy-configuration/v1/policymgmt/polytests/datamodels/import	See Table A-3

Export/Import Data Model s

Table 2-257 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/Optional(O)/Conditional(C)	Description
date	string		Current timestamp
exportData.description	string		
exportData.enumItems.name	string		
exportData.enumItems.value	string		
exportData.fields.description	string		
exportData.fields.itemType.objectType	string		
exportData.fields.itemType.primitiveType	string		
exportData.fields.itemType.type	string		
exportData.fields.labelName	string		
exportData.fields.name	string		

Table 2-257 (Cont.) Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
exportData.fields.object Type	string		
exportData.fields.primitive Type	string		
exportData.fields.type	string		
exportData.id	string		
exportData.labelName	string		
exportData.multiValue	string		
exportData.name	string		
exportData.type	string		
key	string		
sourceVersion	string		System version of the product from which data is exported
topic	string	M	Topic of each managed object

Sample Request Body structure for Import/Export operations:

```

{
  "date": "string",
  "exportData": [
    {
      "description": "string",
      "enumItems": [
        {
          "name": "string",
          "value": "string"
        }
      ],
      "fields": [
        {
          "description": "string",
          "itemType": {
            "objectType": "string",
            "primitiveType": "boolean",
            "type": "object"
          },
          "labelName": "string",
          "name": "string",
          "objectType": "string",
          "primitiveType": "string",
          "type": "array"
        }
      ],
      "id": "string",
      "labelName": "string",
      "multiValue": true,

```

```

        "name": "string",
        "type": "enum"
    }
],
"key": "string",
"sourceVersion": "string",
"topic": "string"
}

```

2.50 Policy Projects

Table 2-258 Supported REST APIs

Description	HTTP Method or Custom Operation	Resource URI	Possible Result Code
Import policy projects	POST	{apiRoot}/oc-cnpolicy-configuration/v1/policymgmt/policyprojects/import	See Table A-3
Export Policy Projects	GET	{apiRoot}/oc-cnpolicy-configuration/v1/policymgmt/policyprojects/export	See Table A-1
Get policy project	GET	{apiRoot}/oc-cnpolicy-configuration/v1/policymgmt/policyprojects?policyProjectName=projectName&serviceName=service where, serviceName is a mandatory query Parameter and policyProjectName is an optional parameter.	See Table A-1
Export Policy	GET	{apiRoot}/oc-cnpolicy-configuration/v1/policymgmt/policyprojects/policy/export/{serviceName}/{policyProjectName}/{policyName}	See Table A-1
Import Policy	POST	{apiRoot}/oc-cnpolicy-configuration/v1/policymgmt/policyprojects/policy/import	See Table A-3
Delete policy project	DELETE	{apiRoot}/oc-cnpolicy-configuration/v1/policymgmt/policyprojects/{serviceName}/{policyProjectName}	See Table A-4
Update Policy Project State	PUT	{apiRoot}/oc-cnpolicy-configuration/v1/policymgmt/policyprojects/{serviceName}/{policyProjectName}	See Table A-2

Get, Create, and Update Policy Projects

Table 2-259 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
description	string	O	Specifies the description of a policy project.
name	String	O	Specifies the name of a policy project.
policy	array	O	
serviceType	String	O	Specifies the following supported service types: • PCF Session Management • PCF Access and Mobility • PCRF Core • PCF UE Policy • PCF Data Source • Usage Monitoring

Sample Response body structure for GET, POST, and PUT operations:

```

{
  "date": "string",
  "errors": [
    {
      "message": "string",
      "name": "string"
    }
  ],
  "exportData": [
    {
      "description": "string",
      "entrance": true,
      "key": "string",
      "layout": "string",
      "name": "string",
      "outputModels": [
        "string"
      ],
      "policy": [
        {
          "entrance": true,
          "layout": "string",
          "name": "string",
          "outputModels": [
            "string"
          ],
          "script": "string"
        }
      ]
    }
  ],

```

```

        "projectId": "string",
        "script": "string",
        "serviceType": "string"
    }
],
"key": "string",
"sourceVersion": "string",
"topic": "string"
}

```

Delete Policy Projects

Table 2-260 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
policyProjectName	string	M	Policy Project Name

Export/Import Policy Projects

Sample Request Body structure for Import/Export operations:

```

{
  "date": "string",
  "errors": [
    {
      "message": "string",
      "name": "string"
    }
  ],
  "exportData": [
    {
      "description": "string",
      "entrance": true,
      "key": "string",
      "layout": "string",
      "name": "string",
      "outputModels": [
        "string"
      ],
      "policy": [
        {
          "entrance": true,
          "layout": "string",
          "name": "string",
          "outputModels": [
            "string"
          ],
          "script": "string"
        }
      ],
      "projectId": "string",
      "script": "string",
      "serviceType": "string"
    }
  ],
  "projectId": "string",
  "script": "string",
  "serviceType": "string"
}

```

```
    }  
  ],  
  "key": "string",  
  "sourceVersion": "string",  
  "topic": "string"  
}
```

2.51 Policy Data

Table 2-261 Supported REST APIs

API Name	HTTP Method or Custom Operation	Resource URI	Possible Result Code
Export Policy Data with or without Dependencies	POST	{apiRoot}/oc-cnpolicy-configuration/v1/policymgmt/policydata/export	See Table A-3

Note

The **Policy Data** export API returns a ResourceId in response to the POST request. The ResourceId is the background task id for the POST operation. This id can be used to track the policy data export requests, and download the export data. For example, the POST API for Policy Data export operation takes the project name, policy name, and service type as input. The response of this API contains the resource id of the file created for export. You can use this resource Id to download the export data at any point of time. For more information about the API to download the export data, see [Bulk Import Export Controller](#).

Export Policy Data

Table 2-262 Request Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
name	string	M	Name of the project.
policies	array	M	Name of the policies.
serviceType	string	M	Service type. Note: Only AM and SM service types are supported.

Table 2-262 (Cont.) Request Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
includeDependencies	boolean	O	This is a flag to decide, if dependencies must be included with export data. Provide any of the following values: true: Export all the dependent MOs of the policy names provided in the policies field false: Does not export all the dependent MOs of the policy names provided in the policies field

Sample Request Body structure for Export operations:

```
[
  {
    "serviceType": "string",
    "policyProjects": [
      {
        "name": "string",
        "policies": [
          "string"
        ]
      }
    ]
  }
]
```

Sample Response Body structure for Export operations:

```
{
  "resourceId": "8376a6d2-708d-49a8-980c-016fab027cc2"
}
```

Below are the status displayed by Policy Data export:

- **INIT**: The policies are being validated and export of MOs is not started.
- **IN_PROGRESS**: The export is running.
- **DONE**: The export is complete. Following are the possible status if the export is in DONE status:
 - **SUCCESS** : The export is successful
 - **FAILED** : When error exist in all the Policies exported.
 - **PARTIAL_SUCCESS** : The export is partially successful

2.52 URSP

Table 2-263 Supported REST APIs

Description	HTTP Method or Custom Operation	Resource URI	Possible Result Code
Create URSP	POST	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcfue/ursps	See Table A-3
Export URSP	GET	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcfue/ursps/export	See Table A-1
Import URSP	POST	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcfue/ursps/import	See Table A-3
Get URSP	GET	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcfue/ursps/{urspName}	See Table A-1
Update URSP	PUT	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcfue/ursps/{urspName}	See Table A-2
Delete URSP	DELETE	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcfue/ursps/{urspName}	See Table A-4

Get, Create, and Update URSPs

Table 2-264 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
name	string	M	Name of the URSP rule.
precedence	integer(\$int32) Enter a value between 0 and 255.	M	Precedence value of the URSP rule.
routeSelectionDescriptorList	UrsprouteSelectionDescriptorList	O	List of URSP routes.
trafficDescriptors	TrafficDescriptorIE	O	List of traffic descriptors.

Table 2-265 UrsprouteSelectionDescriptorList

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
routePrecedence	integer(\$int32)	M	

Table 2-265 (Cont.) UrspRouteSelectionDescriptorList

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
routeSelectionDescriptor Components	RouteSelectionDescript orComponentIE	M	

Table 2-266 UrspRouteSelectionDescriptorList

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
routePrecedence	integer(\$int32)	O	
routeSelectionDescriptor Components	RouteSelectionDescript orComponentIE	O	

Table 2-267 RouteSelectionDescriptorComponentIE

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
routeSelectionDescriptor Type	ENUM	O	
value	RouteSelectionDescript orComponent	O	

Table 2-268 TrafficDescriptorIE

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
trafficDescriptorType	ENUM	O	
value	RouteSelectionDescript orComponent	O	

Table 2-269 RouteSelectionDescriptorComponentIE

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
routeSelectionDescriptor Type	ENUM	O	
value	TrafficDescriptorCompon ent	O	

Sample Request body structure for POST and PUT operations:

```
{
  "name": "string",
```

```

    "precedence": 0,
    "routeSelectionDescriptorList": [
      {
        "routePrecedence": 0,
        "routeSelectionDescriptorComponents": [
          {
            "routeSelectionDescriptorType": "DNN",
            "value": {}
          }
        ]
      }
    ],
    "trafficDescriptors": [
      {
        "trafficDescriptorType": "CONNECTION_CAPABILITIES",
        "value": {}
      }
    ]
  }
}

```

Sample Response body structure for GET, POST, and PUT operations:

```

{
  "name": "string",
  "precedence": 0,
  "routeSelectionDescriptorList": [
    {
      "routePrecedence": 0,
      "routeSelectionDescriptorComponents": [
        {
          "routeSelectionDescriptorType": "DNN",
          "value": {}
        }
      ]
    }
  ],
  "trafficDescriptors": [
    {
      "trafficDescriptorType": "CONNECTION_CAPABILITIES",
      "value": {}
    }
  ]
}

```

Delete URSP

Table 2-270 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
urspName	string	M	URSP Name

Export/Import URSP

Table 2-271 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
date	string		Current timestamp
exportData	array		Exported list of URSPervice. For more information, see Get, Create, and Update URSPs .
key	string		Indicates the ID of URSP
sourceVersion	string		System version of product from which data is exported
topic	string		Topic of each managed object

Sample Request Body structure for Import/Export operations:

```
{
  "date": "string",
  "errors": [
    {
      "message": "string",
      "name": "string"
    }
  ],
  "exportData": [
    {
      "name": "string",
      "precedence": 0,
      "routeSelectionDescriptorList": [
        {
          "routePrecedence": 0,
          "routeSelectionDescriptorComponents": [
            {
              "routeSelectionDescriptorType": "DNN",
              "value": {}
            }
          ]
        }
      ]
    }
  ],
  "trafficDescriptors": [
    {
      "trafficDescriptorType": "CONNECTION_CAPABILITIES",
      "value": {}
    }
  ]
},
```

```

    "key": "string",
    "sourceVersion": "string",
    "topic": "string"
  }

```

2.53 UPSI

Table 2-272 Supported REST APIs

Description	HTTP Method or Custom Operation	Resource URI	Possible Result Code
Create UPSI	POST	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcfue/upsis	See Table A-3
Export UPSI	GET	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcfue/upsis/export	See Table A-1
Import UPSI	POST	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcfue/upsis/import	See Table A-3
Get UPSI	GET	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcfue/upsis/{upsiName}	See Table A-1
Update UPSI	PUT	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcfue/upsis/{upsiName}	See Table A-2
Delete UPSI	DELETE	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcfue/upsis/{upsiName}	See Table A-4

Get, Create, and Update UPSIs

Table 2-273 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
name	string	M	Name of the UPSI.
plmn	Plmn	M	PLMN Identity
upsc	integer(\$int32) Enter a value between 0 and 65535.	M	Defines UE Policy Section Code. Enter a number between 0 and 65,535.
urspRules	string	O	Defines URSP rules.

Table 2-274 Plmn

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
mcc	string Valid Range [0-999]	M	Specifies a Mobile Country Code. enter a 2 or 3 digit number.
mnc	string Valid Range [0-999]	M	Specifies a Mobile Network Code. enter a 2 or 3 digit number.

Sample Request body structure for POST and PUT operations:

```
{
  "name": "string",
  "plmn": {
    "mcc": "string",
    "mnc": "string"
  },
  "upsc": 0,
  "urspRules": [
    "string"
  ]
}
```

Sample Response body structure for GET, POST, and PUT operations:

```
{
  "name": "string",
  "plmn": {
    "mcc": "string",
    "mnc": "string"
  },
  "upsc": 0,
  "urspRules": [
    "string"
  ]
}
```

Delete UPSI

Table 2-275 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
upsiName	string	M	UPSI Name

Export/Import UPSI

Table 2-276 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
date	string		Current timestamp
errors:message	string		
errors:name	string		
exportData	array		Exported list of UPSI service. For more information, see Get, Create, and Update UPSIs .
sourceVersion	string		System version of product from which data is exported
topic	string		Topic of each managed object

Sample Request Body structure for Import/Export operations:

```
{
  "date": "string",
  "errors": [
    {
      "message": "string",
      "name": "string"
    }
  ],
  "exportData": [
    {
      "name": "string",
      "plmn": {
        "mcc": "string",
        "mnc": "string"
      },
      "upsc": 0,
      "urspRules": [
        "string"
      ]
    }
  ],
  "sourceVersion": "string",
  "topic": "string"
}
```

2.54 Traffic Control Data

Table 2-277 Supported REST APIs

Description	HTTP Method or Custom Operation	Resource URI	Possible Result Code
Create Traffic Control Data	POST	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcfsm/trafficcontroldata	See Table A-3
Export Traffic Control Data	GET	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcfsm/trafficcontroldata/export	See Table A-1
Import Traffic Control Data	POST	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcfsm/trafficcontroldata/import	See Table A-3
Get Traffic Control Data	GET	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcfsm/trafficcontroldata/{trafficControlDataName}	See Table A-1
Update Traffic Control Data	PUT	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcfsm/trafficcontroldata/{trafficControlDataName}	See Table A-2
Delete Traffic Control Data	DELETE	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcfsm/trafficcontroldata/{trafficControlDataName}	See Table A-4

Get, Create, and Update Traffic Control Data

Table 2-278 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
description	string	O	The description of the Traffic Control policy data.

Table 2-278 (Cont.) Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
flowStatus	ENUM	O	The following options are available: - ENABLED-UPLINK - ENABLED-DOWNLINK - ENABLED - DISABLED - REMOVED Enum determining what action to perform on traffic. Possible values are: [enable, disable, enable_uplink, enable_downlink] . The default value "ENABLED" shall apply, if the attribute is not present and has not been supplied previously.
muteNotif	boolean	O	Indicates whether application's start or stop notification is to be muted. The default value "FALSE" shall apply, if the attribute is not present and has not been supplied previously.
name	string	M	The name of the Traffic Control policy data.
redirectInfo	RedirectInfo	O	Redirect Information
routeToLocs	RouteToLocs	O	Route To Locs Information
tcId	string	O	Specifies the traffic control ID.
trafficSteeringPolIdDl	string	O	Reference to a pre-configured traffic steering policy for downlink traffic at the SMF.
trafficSteeringPolIdUl	string	O	Reference to a pre-configured traffic steering policy for uplink traffic at the SMF.
upPathChgEvent	UpPathChgEvent	O	Up Path Chg Event Information

Table 2-279 RedirectInfo

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
redirectAddressType	ENUM	O	This string provides forward-compatibility with future extensions to the enumeration but is not used to encode content defined in the present version of this API.
redirectEnabled	boolean	O	Indicates the redirect is enabled.

Table 2-279 (Cont.) RedirectInfo

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
redirectServerAddress	string	O	Indicates the address of the redirect server.

Table 2-280 RouteToLocs

Field Name	Data Type	Constraints	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
dnai	string		O	Identifies the location of the application.
routeInfo	RouteInfo		O	Includes the traffic routing information.
routeProfileId	string		O	Identifies the routing profile Id.

Table 2-281 RouteInfo

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
ipv4Addr	string	O	Ipv4 address of the tunnel end point in the data network.
ipv6Addr	string	O	Ipv6 address of the tunnel end point in the data network
portNumber	integer (\$int32) Enter a number greater than or equal to 0	O	UDP port number of the tunnel end point in the data network.

Table 2-282 UpPathChgEvent

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
dnaiChgType	ENUM	O	The following options are available: • EARLY • EARLY_LATE • LATE Possible values are - EARLY: Early notification of UP path reconfiguration. - EARLY_LATE: Early and late notification of UP path reconfiguration. This value shall only be present in the subscription to the DNAI change event. - LATE: Late notification of UP path reconfiguration. This string provides forwardcompatibility with future extensions to the enumeration but is not used to encode content defined in the present version of this API.
notifCorreId	string	O	It is used to set the value of Notification Correlation ID in the notification sent by the SMF.
notificationUri	string	O	

Sample Request body structure for POST and PUT operations:

```
{
  "description": "string",
  "flowStatus": "DISABLED",
  "muteNotif": true,
  "name": "string",
  "redirectInfo": {
    "redirectAddressType": "IPV4_ADDR",
    "redirectEnabled": true,
    "redirectServerAddress": "string"
  },
  "routeToLocs": [
    {
      "dnai": "string",
      "routeInfo": {
        "ipv4Addr": "string",
        "ipv6Addr": "string",
        "portNumber": 0
      }
    }
  ]
}
```

```

        },
        "routeProfId": "string"
    }
},
"tcId": "string",
"trafficSteeringPolIdDl": "string",
"trafficSteeringPolIdUl": "string",
"upPathChgEvent": {
    "dnaiChgType": "EARLY",
    "notifCorreId": "string",
    "notificationUri": "string"
}
}

```

Sample Response body structure for GET, POST, and PUT operations:

```

{
    "description": "string",
    "flowStatus": "DISABLED",
    "muteNotif": true,
    "name": "string",
    "redirectInfo": {
        "redirectAddressType": "IPV4_ADDR",
        "redirectEnabled": true,
        "redirectServerAddress": "string"
    },
    "routeToLocs": [
        {
            "dnai": "string",
            "routeInfo": {
                "ipv4Addr": "string",
                "ipv6Addr": "string",
                "portNumber": 0
            },
            "routeProfId": "string"
        }
    ],
    "tcId": "string",
    "trafficSteeringPolIdDl": "string",
    "trafficSteeringPolIdUl": "string",
    "upPathChgEvent": {
        "dnaiChgType": "EARLY",
        "notifCorreId": "string",
        "notificationUri": "string"
    }
}

```

Delete Traffic Control Data**Table 2-283 Request/Response Body Parameters**

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
trafficControlDataName	string	M	Traffic Control Data Name

Export/Import Traffic Control Data**Table 2-284 Request/Response Body Parameters**

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
date	string		Current timestamp
exportData	array		Exported list of traffic control data service. For more information, see Get, Create, and Update Traffic Control Data .
key	string		Indicates the ID of Traffic Control Data
sourceVersion	string		System version of product from which data is exported
topic	string		Topic of each managed object

Sample Request Body structure for Import/Export operations:

```
{
  "date": "string",
  "errors": [
    {
      "message": "string",
      "name": "string"
    }
  ],
  "exportData": [
    {
      "description": "string",
      "flowStatus": "DISABLED",
      "muteNotif": true,
      "name": "string",
      "redirectInfo": {
        "redirectAddressType": "IPV4_ADDR",
        "redirectEnabled": true,
        "redirectServerAddress": "string"
      },
      "routeToLocs": [
        {
```

```

        "dnai": "string",
        "routeInfo": {
            "ipv4Addr": "string",
            "ipv6Addr": "string",
            "portNumber": 0
        },
        "routeProfId": "string"
    }
},
"tcId": "string",
"trafficSteeringPolIdDl": "string",
"trafficSteeringPolIdUl": "string",
"upPathChgEvent": {
    "dnaiChgType": "EARLY",
    "notifCorreId": "string",
    "notificationUri": "string"
}
}
},
"key": "string",
"sourceVersion": "string",
"topic": "string"
}

```

2.55 PCC Rule

Table 2-285 Supported REST APIs

Description	HTTP Method or Custom Operation	Resource URI	Possible Result Code
Create PCC Rule	POST	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcfsm/pccrules	See Table A-3
Export PCC Rules	GET	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcfsm/pccrules/export	See Table A-1
Import PCC Rule	POST	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcfsm/pccrules/import	See Table A-3
Get PCC Rule	GET	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcfsm/pccrules/{pccRuleName}	See Table A-1
Update PCC Rule	PUT	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcfsm/pccrules/{pccRuleName}	See Table A-2

Table 2-285 (Cont.) Supported REST APIs

Description	HTTP Method or Custom Operation	Resource URI	Possible Result Code
Delete PCC Rule	DELETE	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcfsm/pccrules/{pccRuleName}	See Table A-4

Get, Create, and Update PCC Rules

Table 2-286 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/Optional(O)/Conditional(C)aints	Description
afSigProtocol	ENUM	O	Indicates the protocol used for signalling between the UE and the AF. The default value "NO_INFORMATION" shall apply, if the attribute is not present and has not been supplied previously.
qosFlowUsage	ENUM	O	Indicates the QoS flow usage. The default value is not applicable for this field. Users can select GENERAL or IMS_SIG from the drop down list as per the requirement.
appld	string	O	A reference to the application detection filter configured at the UPF.
appReloc	boolean	O	Indication of application relocation possibility. The default value "NO_INFORMATION" shall apply, if the attribute is not present and has not been supplied previously.
contVer	string	O	Indicates the content version of the PCC rule.
description	string	O	The description of the PCC rule
flowInfos	FlowInfos	O	An array of IP flow packet filter information.
name	string	M	The name of the PCC rule
pccRuleId	string	M	Univocally identifies the PCC rule within a PDU session.

Table 2-286 (Cont.) Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
precedence	string	O	Determines the order in which this PCC rule is applied relative to other PCC rules within the same PDU session. It shall be included if the "flowInfos" attribute is included or may be included if the "appld" attribute is included when the PCF initially provisions the PCC rule.
refChgData	string	O	A reference to the ChargingData policy decision type.
refCondData	string	O	A reference to the condition data.
refQosData	string	O	A reference to the QoSData policy type decision type.
refTcData	string	O	A reference to the TrafficControlData policy decision type.
refUmData	string	O	A reference to UsageMonitoringData policy decision type.
type	ENUM	O	

Table 2-287 FlowInfos

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
ethFlowDescription	ethFlowDescription	O	Ethernet Flow Description Information
flowDescription	string	O	Indicates the details about flow. Enter a description for the flow.
flowDirection	ENUM	O	Indicates the flow direction. Select from the following options: • DOWNLINK • UPLINK • BIDIRECTIONAL • UNSPECIFIED
flowLabel	string	O	The Ipv6 flow label header field.
name	string	M	Indicates the name for the flow
packFiltId	string	O	An identifier of packet filter

Table 2-287 (Cont.) FlowInfos

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
packetFilterUsage	boolean	O	The packet shall be sent to the UE. The default value "FALSE" shall apply, if the attribute is not present and has not been supplied previously
spi	string	O	The security parameter index of the IPSec packet.
tosTrafficClass	string	O	Contains the Ipv4 Type-of-Service and mask field or the Ipv6 Traffic-Class field and mask field.

Table 2-288 ethFlowDescription

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
destMacAddr	string enter a MAC address ,such as'3D-F2-C9-A6-B3-4F'.	O	A string indicating MAC address. Enter a valid MAC address. For example, 3D-F2-C9-A6-B3-4F
ethType	string	O	A two-octet string that represents the Ethertype, in hexadecimal representation. Each character in the string shall take a value of "0" to "9" or "A" to "F" and shall represent 4 bits. The most significant character representing the 4 most significant bits of the ethType shall appear first in the string, and the character representing the 4 least significant bits of the ethType shall appear last in the string.
fDesc	string	O	Contains the flow description for the Uplink or Downlink IP flow. It shall be present when the Ethertype is IP.

Table 2-288 (Cont.) ethFlowDescription

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
fDir	ENUM	O	Indicates the packet filter direction. Select from the following options: • DOWNLINK • UPLINK • BIDIRECTIONAL • UNSPECIFIED
sourceMacAddr	string enter a MAC address ,such as'3D-F2-C9-A6-B3-4F'	O	Enter a source MAC Address. For example, 3D-F2-C9- A6-B3-4F
vlanTags	string	O	Customer-VLAN and/or Service-VLAN tags containing the VID, PCP/DEI fields. Each field is encoded as a two-octet string in hexadecimal representation. Each character in the string shall take a value of "0" to "9" or "A" to "F" and shall represent 4 bits. The most significant character representing the 4 most significant bits of the VID or PCF/DEI field shall appear first in the string, and the character representing the 4 least significant bits of the VID or PCF/DEI field shall appear last in the string.

Sample Request body structure for POST and PUT operations:

```
{
  "afSigProtocol": "NO_INFORMATION",
  "appId": "string",
  "appReloc": true,
  "contVer": "string",
  "description": "string",
  "flowInfos": [
    {
      "ethFlowDescription": {
        "destMacAddr": "string",
        "ethType": "string",
        "fDesc": "string",
```

```

        "fDir": "BIDIRECTIONAL",
        "fDesc": "string",
        "fdir": "BIDIRECTIONAL",
        "sourceMacAddr": "string",
        "vlanTags": [
            "string"
        ]
    },
    "flowDescription": "string",
    "flowDirection": "BIDIRECTIONAL",
    "flowLabel": "string",
    "name": "string",
    "packFiltId": "string",
    "packetFilterUsage": true,
    "spi": "string",
    "tosTrafficClass": "string"
}
],
"name": "string",
"pccRuleId": "string",
"precedence": "string",
"refChgData": [
    "string"
],
"refCondData": "string",
"refQosData": [
    "string"
],
"refTcData": [
    "string"
],
"refUmData": [
    "string"
],
"type": "DYNAMIC"
}

```

Sample Response body structure for GET, POST, and PUT operations:

```

{
    "afSigProtocol": "NO_INFORMATION",
    "appId": "string",
    "appReloc": true,
    "contVer": "string",
    "description": "string",
    "flowInfos": [
        {
            "ethFlowDescription": {
                "destMacAddr": "string",
                "ethType": "string",
                "fDesc": "string",
                "fDir": "BIDIRECTIONAL",
                "fDesc": "string",
                "fdir": "BIDIRECTIONAL",
                "sourceMacAddr": "string",
            }
        }
    ]
}

```

```

        "vlanTags": [
            "string"
        ]
    },
    "flowDescription": "string",
    "flowDirection": "BIDIRECTIONAL",
    "flowLabel": "string",
    "name": "string",
    "packFiltId": "string",
    "packetFilterUsage": true,
    "spi": "string",
    "tosTrafficClass": "string"
}
],
"name": "string",
"pccRuleId": "string",
"precedence": "string",
"refChgData": [
    "string"
],
"refCondData": "string",
"refQosData": [
    "string"
],
"refTcData": [
    "string"
],
"refUmData": [
    "string"
],
"type": "DYNAMIC"
}

```

Delete PCC Rule

Table 2-289 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
PCCRuleName	string	M	PCC Rule Name

Export/Import PCC Rule s

Table 2-290 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
date	string		Current timestamp

Table 2-290 (Cont.) Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
exportData	array		Exported list of PCC Rule. For more information, see Get, Create, and Update PCC Rules .
key	string		Indicates the ID
sourceVersion	string		System version of product from which data is exported
topic	string		Topic of each managed object

Sample Request Body structure for Import/Export operations:

```
{
  "date": "string",
  "errors": [
    {
      "message": "string",
      "name": "string"
    }
  ],
  "exportData": [
    {
      "afSigProtocol": "NO_INFORMATION",
      "appId": "string",
      "appReloc": true,
      "contVer": "string",
      "description": "string",
      "flowInfos": [
        {
          "ethFlowDescription": {
            "destMacAddr": "string",
            "ethType": "string",
            "fDesc": "string",
            "fDir": "BIDIRECTIONAL",
            "fdesc": "string",
            "fdir": "BIDIRECTIONAL",
            "sourceMacAddr": "string",
            "vlanTags": [
              "string"
            ]
          },
          "flowDescription": "string",
          "flowDirection": "BIDIRECTIONAL",
          "flowLabel": "string",
          "name": "string",
          "packFiltId": "string",
          "packetFilterUsage": true,

```

```

        "spi": "string",
        "tosTrafficClass": "string"
    }
],
"name": "string",
"pccRuleId": "string",
"precedence": "string",
"refChgData": [
    "string"
],
"refCondData": "string",
"refQosData": [
    "string"
],
"refTcData": [
    "string"
],
"refUmData": [
    "string"
],
"type": "DYNAMIC"
}
],
"key": "string",
"sourceVersion": "string",
"topic": "string"
}

```

2.56 PCC Rule Profile

Table 2-291 Supported REST APIs

Description	HTTP Method or Custom Operation	Resource URI	Possible Result Code
Create PCC Rule Profile	POST	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcfsm/pccruleprofiles	See Table A-3
Export PCC Rule Profiles	GET	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcfsm/pccruleprofiles/export	See Table A-1
Import PCC Rule Profile	POST	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcfsm/pccruleprofiles/import	See Table A-3
Get PCC Rule Profile	GET	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcfsm/pccruleprofiles/{pccRuleProfileName}	See Table A-1

Table 2-291 (Cont.) Supported REST APIs

Description	HTTP Method or Custom Operation	Resource URI	Possible Result Code
Update PCC Rule Profile	PUT	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcfsm/pccruleprofiles/{pccRuleProfileName}	See Table A-2
Delete PCC Rule Profile	DELETE	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcfsm/pccruleprofiles/{pccRuleProfileName}	See Table A-4

Get, Create, and Update PCC Rule Profile**Table 2-292 Request/Response Body Parameters**

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)aints	Description
afSigProtocol	ENUM	O	Specifies the protocol used for signaling between the UE and the AF.
qosFlowUsage	ENUM	O	Indicates the QoS flow usage. The default value is not applicable for this field. Users can select GENERAL or IMS_SIG from the drop down list as per the requirement.
appld	string	O	A reference to the application detection filter configured at the UPF.
appReloc	boolean	O	Specifies application relocation possibility.
contVer	string	O	Specifies the content version of the PCC rule.
description	string	O	Description of PCC Rule Profile.
flowInfos	FlowInfos	O	An array of IP flow packet filter information.
id	string	M	Unique identifier of PCC Rule Profile
name	string	M	Specifies the name of PCC Rule Profile.

Table 2-292 (Cont.) Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
precedence	string		Determines the order in which this PCC rule is applied relative to other PCC rules within the same PDU session. It shall be included if the flowInfos attribute is included or may be included if the appld attribute is included when the PCF initially provisions the PCC rule.
refChgData	string		A reference to the ChargingData policy decision type.
refCondData	string		A reference to the condition data.
refQosData	string		A reference to the QoSData policy type decision type.
refTcData	string		A reference to the TrafficControlData policy decision type.
refUmData	string		A reference to UsageMonitoringData policy decision type.
type	ENUM		Possible values are: • DYNAMIC • PREDEFINED

Table 2-293 FlowInfos

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
ethFlowDescription	ethFlowDescription		Defines a packet filter for an Ethernet flow.
flowDescription	string		Specifies the packet filters of the IP flow(s).
flowDirection	ENUM		Indicates the direction/directions that a filter is applicable, downlink only, uplink only or both down- and uplink (bidirectional).
flowLabel	string		Ipv6 flow label header field.
name	string	M	
packFiltId	string		An identifier of packet filter.

Table 2-293 (Cont.) FlowInfos

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
packetFilterUsage	boolean		The packet shall be sent to the UE. The default value FALSE shall apply, if the attribute is not present and has not been supplied previously.
spi	string		Specifies the security parameter index of the IPSec packet.
tosTrafficClass	string		Specifies the Ipv4 Type-of-Service and mask field or the Ipv6 Traffic-Class field and mask field.

Table 2-294 ethFlowDescription

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
destMacAddr	string enter a MAC address ,such as'3D-F2-C9-A6-B3-4F'.		A string indicating MAC address. Enter a valid MAC address. For example, 3D-F2-C9-A6-B3-4F
ethType	string		A two-octet string that represents the Ethertype, in hexadecimal representation. Each character in the string shall take a value of "0" to "9" or "A" to "F" and shall represent 4 bits. The most significant character representing the 4 most significant bits of the ethType shall appear first in the string, and the character representing the 4 least significant bits of the ethType shall appear last in the string.
fDesc	string		Indicates the details about flow. Enter a description for the flow.

Table 2-294 (Cont.) ethFlowDescription

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
fDir	ENUM		Indicates the flow direction. Select from the following options: • DOWNLINK • UPLINK • BIDIRECTIONAL • UNSPECIFIED
sourceMacAddr	string enter a MAC address ,such as'3D-F2-C9-A6-B3-4F'		Enter a MAC Address. For example, 3D-F2-C9-A6-B3-4F
vlanTags	string		Customer-VLAN and/or Service-VLAN tags containing the VID, PCP/DEI fields. Each field is encoded as a two-octet string in hexadecimal representation. Each character in the string shall take a value of "0" to "9" or "A" to "F" and shall represent 4 bits. The most significant character representing the 4 most significant bits of the VID or PCF/DEI field shall appear first in the string, and the character representing the 4 least significant bits of the VID or PCF/DEI field shall appear last in the string.

Sample Request body structure for POST and PUT operations:

```
{
  "afSigProtocol": "NO_INFORMATION",
  "appId": "string",
  "appReloc": true,
  "contVer": "string",
  "description": "string",
  "flowInfos": [
    {
      "ethFlowDescription": {
        "destMacAddr": "string",
        "ethType": "string",
        "fDesc": "string",
        "fDir": "BIDIRECTIONAL",
```

```

        "fdesc": "string",
        "fdir": "BIDIRECTIONAL",
        "sourceMacAddr": "string",
        "vlanTags": [
            "string"
        ]
    },
    "flowDescription": "string",
    "flowDirection": "BIDIRECTIONAL",
    "flowLabel": "string",
    "name": "string",
    "packFiltId": "string",
    "packetFilterUsage": true,
    "spi": "string",
    "tosTrafficClass": "string"
}
],
"id": "string",
"name": "string",
"precedence": "string",
"refChgData": [
    "string"
],
"refCondData": "string",
"refQosData": [
    "string"
],
"refTcData": [
    "string"
],
"refUmData": [
    "string"
],
"type": "DYNAMIC"
}

```

Sample Response body structure for GET, POST, and PUT operations:

```

{
    "date": "string",
    "errors": [
        {
            "message": "string",
            "name": "string"
        }
    ],
    "exportData": [
        {
            "afSigProtocol": "NO_INFORMATION",
            "appId": "string",
            "appReloc": true,
            "contVer": "string",
            "description": "string",
            "flowInfos": [

```

```

        {
          "ethFlowDescription": {
            "destMacAddr": "string",
            "ethType": "string",
            "fDesc": "string",
            "fDir": "BIDIRECTIONAL",
            "fdesc": "string",
            "fdir": "BIDIRECTIONAL",
            "sourceMacAddr": "string",
            "vlanTags": [
              "string"
            ]
          },
          "flowDescription": "string",
          "flowDirection": "BIDIRECTIONAL",
          "flowLabel": "string",
          "name": "string",
          "packFiltId": "string",
          "packetFilterUsage": true,
          "spi": "string",
          "tosTrafficClass": "string"
        }
      ],
      "id": "string",
      "name": "string",
      "precedence": "string",
      "refChgData": [
        "string"
      ],
      "refCondData": "string",
      "refQosData": [
        "string"
      ],
      "refTcData": [
        "string"
      ],
      "refUmData": [
        "string"
      ],
      "type": "DYNAMIC"
    }
  ],
  "key": "string",
  "sourceVersion": "string",
  "topic": "string"
}

```

Delete PCC Rule Profile**Table 2-295 Request/Response Body Parameters**

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
PCCRuleProfileName	string	M	PCC Rule Profile Name

Export/Import PCC Rule Profile**Table 2-296 Request/Response Body Parameters**

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
date	string		Current timestamp
exportData	array		Exported list of PCC Rule Profile. For more information, see Get, Create, and Update PCC Rule Profile .
key	string		Indicates the ID
sourceVersion	string		System version of product from which data is exported
topic	string		Topic of each managed object

Sample Request Body structure for Import/Export operations:

```
{
  "date": "string",
  "errors": [
    {
      "message": "string",
      "name": "string"
    }
  ],
  "exportData": [
    {
      "afSigProtocol": "NO_INFORMATION",
      "appId": "string",
      "appReloc": true,
      "contVer": "string",
      "description": "string",
      "flowInfos": [
        {
          "ethFlowDescription": {
            "destMacAddr": "string",
            "ethType": "string",
            "fDesc": "string",

```

```

        "fDir": "BIDIRECTIONAL",
        "fdesc": "string",
        "fdir": "BIDIRECTIONAL",
        "sourceMacAddr": "string",
        "vlanTags": [
            "string"
        ]
    },
    "flowDescription": "string",
    "flowDirection": "BIDIRECTIONAL",
    "flowLabel": "string",
    "name": "string",
    "packFiltId": "string",
    "packetFilterUsage": true,
    "spi": "string",
    "tosTrafficClass": "string"
}
],
"id": "string",
"name": "string",
"precedence": "string",
"refChgData": [
    "string"
],
"refCondData": "string",
"refQosData": [
    "string"
],
"refTcData": [
    "string"
],
"refUmData": [
    "string"
],
"type": "DYNAMIC"
}
],
"key": "string",
"sourceVersion": "string",
"topic": "string"
}

```

2.57 Condition Data

Table 2-297 Supported REST APIs

Description	HTTP Method or Custom Operation	Resource URI	Possible Result Code
Create Condition Data	POST	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcfsm/conditiondata	See Table A-3

Table 2-297 (Cont.) Supported REST APIs

Description	HTTP Method or Custom Operation	Resource URI	Possible Result Code
Export Condition Data	GET	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcfsm/conditiondata/export	See Table A-1
Import Condition Data	POST	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcfsm/conditiondata/import	See Table A-3
Get Condition Data	GET	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcfsm/conditiondata/{conditionDataName}	See Table A-1
Update Condition Data	PUT	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcfsm/conditiondata/{conditionDataName}	See Table A-2
Delete Condition Data	DELETE	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcfsm/conditiondata/{conditionDataName}	See Table A-4

Get, Create, and Update Condition Data**Table 2-298 Request/Response Body Parameters**

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)aints	Description
activationTime	string, example : YYYY-MM-DDTHH:MM:SS	O	The time when the decision data shall be activated.
condId	string	O	Specifies the condition ID.
deactivationTime	string example : YYYY-MM-DDTHH:MM:SS	O	The time when the decision data shall be deactivated.
description	string	O	The description of the Condition Data policy data.
name	string	M	The name of the Condition Data policy data.

Sample Request body structure for POST and PUT operations:

```
{
  "activationTime": "YYYY-MM-DDTHH:MM:SS",
  "condId": "string",
  "deactivationTime": "YYYY-MM-DDTHH:MM:SS",
```

```

    "description": "string",
    "name": "string"
  }

```

Sample Response body structure for GET, POST, and PUT operations:

```

{
  "date": "string",
  "errors": [
    {
      "message": "string",
      "name": "string"
    }
  ],
  "exportData": [
    {
      "activationTime": "YYYY-MM-DDTHH:MM:SS",
      "condId": "string",
      "deactivationTime": "YYYY-MM-DDTHH:MM:SS",
      "description": "string",
      "name": "string"
    }
  ],
  "key": "string",
  "sourceVersion": "string",
  "topic": "string"
}

```

Delete Condition Data

Table 2-299 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
conditionDataName	string	M	The name of the Condition Data policy data.

Export/Import Condition Data

Table 2-300 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
date	string		Current timestamp
exportData	array		Exported list of condition data. For more information, see Get, Create, and Update Condition Data .
key	string		Indicates the ID

Table 2-300 (Cont.) Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
sourceVersion	string		System version of product from which data is exported
topic	string		Topic of each managed object

Sample Request Body structure for Import/Export operations:

```
{
  "date": "string",
  "errors": [
    {
      "message": "string",
      "name": "string"
    }
  ],
  "exportData": [
    {
      "activationTime": "YYYY-MM-DDTHH:MM:SS",
      "condId": "string",
      "deactivationTime": "YYYY-MM-DDTHH:MM:SS",
      "description": "string",
      "name": "string"
    }
  ],
  "key": "string",
  "sourceVersion": "string",
  "topic": "string"
}
```

2.58 Charging Data

Table 2-301 Supported REST APIs

Description	HTTP Method or Custom Operation	Resource URI	Possible Result Code
Create Charging Data	POST	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcfsm/chargingdata	See Table A-3
Export Charging Data	GET	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcfsm/chargingdata/export	See Table A-1

Table 2-301 (Cont.) Supported REST APIs

Description	HTTP Method or Custom Operation	Resource URI	Possible Result Code
Import Charging Data	POST	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcfsm/chargingdata/import	See Table A-3
Get Charging Data	GET	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcfsm/chargingdata/{chargingDataName}	See Table A-1
Update Condition Data	PUT	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcfsm/chargingdata/{chargingDataName}	See Table A-2
Delete Charging Data	DELETE	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcfsm/chargingdata/{chargingDataName}	See Table A-4

Get, Create, and Update Charging Data

Table 2-302 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)aints	Description
afChargingIdentifiercgiList	integer (\$int64), Enter a value between 0 and 4294967295	O	Univocally identifies the charging control policy data within a PDU session.
appSvcProvId	string	O	Indicates the application service provider identity.
chgId	string	M	Specifies the charging id.
description	string	O	The description of the Charging Data.

Table 2-302 (Cont.) Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)aints	Description
meteringMethod	ENUM	O	The following options are available • DURATION • VOLUME • DURATION_VOLUME • EVENT Defines what parameters shall be metered for offline charging. If the attribute is not present but it has been supplied previously, the previous information remains valid. If the attribute is not present and it has not been supplied previously or the attribute has been supplied previously but the attribute is set to NULL, the metering method pre-configured at the SMF is applicable as default metering method.
name	string	M	The name of the Charging Data.
offline	boolean	O	Indicates the offline charging is applicable to the PDU session or PCC rule. The default value "FALSE" shall apply, if the attribute is not present and has not been supplied previously. (NOTE)
online	boolean	O	Indicates the online charging is applicable to the PDU session or PCC rule. The default value "FALSE" shall apply, if the attribute is not present and has not been supplied previously. (NOTE)
ratingGroup	integer (\$int64), Enter a value between 0 and 4294967295	O	The charging key for the PCC rule used for rating purposes.

Table 2-302 (Cont.) Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
reportingLevel	ENUM	O	The following options are available: - SER_ID_LEVEL - RAT_GR_LEVEL - SPON_CON_LEVEL Defines on what level the SMF reports the usage for the related PCC rule. If the attribute is not present but it has been supplied previously, the previous information remains valid. If the attribute is not present and it has not been supplied previously or the attribute has been supplied previously but it is set to NULL, the reporting level pre-configured at the SMF is applicable as default reporting level.
sdfHandl	boolean		
serviceId	integer (\$int64), Enter a value between 0 and 4294967295	O	Indicates the identifier of the service or service component the service data flow in a PCC rule relates to.
sponsorId	string	O	Indicates the sponsor identity.

Sample Request body structure for POST and PUT operations:

```
{
  "afChargingIdentifier": 0,
  "appSvcProvId": "string",
  "chgId": "string",
  "description": "string",
  "meteringMethod": "DURATION",
  "name": "string",
  "offline": true,
  "online": true,
  "ratingGroup": 0,
  "reportingLevel": "RAT_GR_LEVEL",
  "sdfHandl": true,
  "serviceId": 0,
  "sponsorId": "string"
}
```

Sample Response body structure for GET, POST, and PUT operations:

```

{
  "date": "string",
  "errors": [
    {
      "message": "string",
      "name": "string"
    }
  ],
  "exportData": [
    {
      "afChargingIdentifier": 0,
      "appSvcProvId": "string",
      "chgId": "string",
      "description": "string",
      "meteringMethod": "DURATION",
      "name": "string",
      "offline": true,
      "online": true,
      "ratingGroup": 0,
      "reportingLevel": "RAT_GR_LEVEL",
      "sdfHandl": true,
      "serviceId": 0,
      "sponsorId": "string"
    }
  ],
  "key": "string",
  "sourceVersion": "string",
  "topic": "string"
}

```

Delete Charging Data**Table 2-303 Request/Response Body Parameters**

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
chargingDataName	string	M	Charging Data Name

Export/Import Charging Data**Table 2-304 Request/Response Body Parameters**

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
date	string		Current timestamp
exportData	array		Exported list of charging data. For more information, see Get, Create, and Update Charging Data .

Table 2-304 (Cont.) Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
key	string		Indicates the ID
sourceVersion	string		System version of product from which data is exported
topic	string		Topic of each managed object

Sample Request Body structure for Import/Export operations:

```

{
  "date": "string",
  "errors": [
    {
      "message": "string",
      "name": "string"
    }
  ],
  "exportData": [
    {
      "afChargingIdentifier": 0,
      "appSvcProvId": "string",
      "chgId": "string",
      "description": "string",
      "meteringMethod": "DURATION",
      "name": "string",
      "offline": true,
      "online": true,
      "ratingGroup": 0,
      "reportingLevel": "RAT_GR_LEVEL",
      "sdfHandl": true,
      "serviceId": 0,
      "sponsorId": "string"
    }
  ],
  "key": "string",
  "sourceVersion": "string",
  "topic": "string"
}

```

2.59 Service Area Restriction

Table 2-305 Supported REST APIs

Description	HTTP Method or Custom Operation	Resource URI	Possible Result Code
Create Service Area Restriction	POST	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcfam/servicearearestrictions	See Table A-3
Export All Service Area Restrictions	GET	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcfam/servicearearestrictions/export	See Table A-1
Import All Service Area Restrictions	POST	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcfam/servicearearestrictions/import	See Table A-3
Get Service Area Restriction	GET	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcfam/servicearearestrictions/{serviceAreaRestrictionName}	See Table A-1
Update Service Area Restriction	PUT	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcfam/servicearearestrictions/{serviceAreaRestrictionName}	See Table A-2
Delete Service Area Restriction	DELETE	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/pcfam/servicearearestrictions/{serviceAreaRestrictionName}	See Table A-4

Get, Create, and Update Service Area Restriction s

Table 2-306 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
areas	ServiceArea RestrictionAr eas	O	A list of Areas. These areas are: - allowed areas if RestrictionType is "ALLOWED_AREAS" - not allowed areas if RestrictionType is "NOT_ALLOWED_AREAS"
description	Number	O	Specifies description of the Service Area Restriction
maxNumOfTAs	boolean	O	Specifies maximum number of TAs
name	string	M	Specifies name of the Service Area Restriction
restrictionType	ENUM	O	Possible values are: - ALLOWED_AREAS - NOT_ALLOWED_AREAS

Table 2-307 ServiceAreaRestrictionAreas

Field Name	Data Type	Description
areaCodes	String	Specifies area codes.
tacs	String	List of Type Allocation Codes. A decimal number between 0 and 65535.

Sample Request body structure for POST/PUT operation:

```
{
  "areas": [
    {
      "areaCodes": "string",
      "tacs": [
        "string"
      ]
    }
  ],
  "description": "string",
  "maxNumOfTAs": 0,
  "name": "string",
  "restrictionType": "ALLOWED_AREAS"
}
```


Sample Response body structure for GET, POST, and PUT operations:

```
[
  {
    "date": "string",
    "errors": [
      {
        "message": "string",
        "name": "string"
      }
    ],
    "exportData": [
      {
        "areas": [
          {
            "areaCodes": "string",
            "tacs": [
              "string"
            ]
          }
        ],
        "description": "string",
        "maxNumOfTAs": 0,
        "name": "string",
        "restrictionType": "ALLOWED_AREAS"
      }
    ],
    "key": "string",
    "sourceVersion": "string",
    "topic": "string"
  }
]
```

Delete Service Area Restriction s**Table 2-308 Request/Response Body Parameters**

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
serviceAreaRestrictionName	string	M	Service Area Restriction Name

Export/Import Service Area Restrictions**Table 2-309 Request/Response Body Parameters**

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
date	string		Current timestamp

Table 2-309 (Cont.) Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
exportData	array		Exported list of service area restrictions. For more information, see Get, Create, and Update Service Area Restrictions
key	string		Indicates the ID
sourceVersion	string		System version of product from which data is exported
systemVersion			
topic	string		Topic of each managed object

Sample Request Body structure for Import/Export operations:

```
[
  {
    "date": "string",
    "errors": [
      {
        "message": "string",
        "name": "string"
      }
    ],
    "exportData": [
      {
        "areas": [
          {
            "areaCodes": "string",
            "tacs": [
              "string"
            ]
          }
        ],
        "description": "string",
        "maxNumOfTAs": 0,
        "name": "string",
        "restrictionType": "ALLOWED_AREAS"
      }
    ],
    "key": "string",
    "sourceVersion": "string",
    "topic": "string"
  }
]
```

2.60 PCF Presence Reporting Area

Table 2-310 Supported REST APIs

HTTP Method or Custom Operation	Description	Resource URI	Possible Result Code
POST	Create Presence Reporting Area	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/common/pras	See Table A-3
GET	Export Presence Reporting Area	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/common/pras/export	See Table A-1
POST	Import Presence Reporting Area	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/common/pras/import	See Table A-3
GET	Get Presence Reporting Area	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/common/pras/{presenceReportingAreaName}	See Table A-1
PUT	Update Presence Reporting Area	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/common/pras/{presenceReportingAreaName}	See Table A-2
DELETE	Delete Presence Reporting Area	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/common/pras/{presenceReportingAreaName}	See Table A-4

Get, Create, AND Update Presence Reporting Areas

Table 2-311 Request/Response Body Parameters GET, PUT, and POST operations

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)aints	Description
ecgiList	PresenceReportingAreaEcgiList	O	Represents the list of tracking areas that constitutes the area. This IE shall be present if the subscription or the event report is for tracking UE presence in the tracking areas. For non 3GPP access the TAI shall be the N3GPP TAI.

Table 2-311 (Cont.) Request/Response Body Parameters GET, PUT, and POST operations

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)aints	Description
globalRanNodeIdList	PresenceReportingAreaGlobalRanNodeIdList	O	Represents the list of NG RAN node identifiers that constitutes the area. This IE shall be present if the Area of Interest subscribed is a list of NG RAN node identifiers.
name	string	M	The unique name assigned to the PRA.
praid	String	M	The unique identifying number of the PRA list. The ID must be numeric value between 0 and 16777125.
ncgiList	PresenceReportingAreaNcgiList	O	Represents the list of NR cell Ids that constitutes the area. This IE shall be present if the Area of Interest subscribed is a list of NR cell Ids.
presenceState	ENUM	O	Indicates whether the UE is inside or outside of the area of interest (e.g presence reporting area or the LADN area), or if the presence reporting area is inactive in the serving node. Select any one of the following values: • IN_AREA : Indicates that the UE is inside or enters the presence reporting area. • OUT_OF_AREA : Indicates that the UE is outside or leaves the presence reporting area. • UNKNOWN : Indicates it is unknown whether the UE is in the presence reporting area or not. • INACTIVE : Indicates that the presence reporting area is inactive in the serving node.

Table 2-311 (Cont.) Request/Response Body Parameters GET, PUT, and POST operations

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
trackingAreaList	PresenceReportingAreaTrackingAreaList	O	Represents the list of tracking areas that constitutes the area. This IE shall be present if the subscription or the event report is for tracking UE presence in the tracking areas. For non 3GPP access the TAI shall be the N3GPP TAI.

Table 2-312 PresenceReportingAreaEcgiList

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
ecgiList. eutraCellId	String, enter a 7 digit hexadecimal value	M	28-bit string identifying an E-UTRA Cell Id as specified in hexadecimal representation. Each character in the string shall take a value of "0" to "9" or "A" to "F" and shall represent 4 bits. The most significant character representing the 4 most significant bits of the Cell Id shall appear first in the string, and the character representing the 4 least significant bit of the Cell Id shall appear last in the string. Pattern: '[A-Fa-f0-9]{7}\$' Example: An E-UTRA Cell Id 0x5BD6007 shall be encoded as "5BD6007".
ecgiList. plmnId	PlmnId	M	PLMN Identity

Table 2-313 PresenceReportingAreaGlobalRanNodeIdList

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
globalRanNodeIdList.gNbId	GNbId		This field is included if the RAN Node Id represents a gNB. When present, this field contains the identifier of the gNB.
globalRanNodeIdList.n3IwfId	string		This field is included if the RAN node belongs to non 3GPP access (i.e a N3IWF). If included, this field contains the FQDN of the N3IWF.
globalRanNodeIdList.ngenBId	string		This field is included if the RAN Node Id represents a NG-eNB. When present, this field contains the identifier of an NG-eNB.
globalRanNodeIdList.plmnId	PlmnId	M	Indicates the identity of the PLMN that the RAN node belongs to.

Table 2-314 PlmnId

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
PlmnId.mcc	String	M	Specifies a Mobile Country Code of the PLMN. enter a 2 or 3 digit number.
PlmnId.mnc	String	M	Specifies a Mobile Network Code of the PLMN. enter a 2 or 3 digit number.

Table 2-315 PresenceReportingAreaNcgiList

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
ncgiList.nrCellId	String, enter a 9 digit hexadecimal value	M	36-bit string identifying an NR Cell Id as specified in hexadecimal representation. Each character in the string shall take a value of "0" to "9" or "A" to "F" and shall represent 4 bits. The most significant character representing the 4 most significant bits of the Cell Id shall appear first in the string, and the character representing the 4 least significant bit of the Cell Id shall appear last in the string. Pattern: '[A-Fa-f0-9]{9}\$' Example: An NR Cell Id 0x225BD6007 shall be encoded as "225BD6007".
ncgiList.plmnlId	PlmnlId	M	PLMN Identity

Table 2-316 PresenceReportingAreaTrackingAreaList

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
trackingAreaList.plmnlId	PlmnlId		PLMN Identity

Table 2-316 (Cont.) PresenceReportingAreaTrackingAreaList

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
trackingAreaList.tac	string, enter a 4 or 6 digit hexadecimal value		28-bit string identifying an E-UTRA Cell Id as specified, in hexadecimal representation. Each character in the string shall take a value of "0" to "9" or "A" to "F" and shall represent 4 bits. The most significant character representing the 4 most significant bits of the Cell Id shall appear first in the string, and the character representing the 4 least significant bit of the Cell Id shall appear last in the string. Pattern: '^[A-Fa-f0-9] {7}\$' Example: An E-UTRA Cell Id 0x5BD6007 shall be encoded as "5BD6007".

Sample Request body structure for POST and PUT operations:

```
{
  "ecgiList": [
    {
      "eutraCellId": "string",
      "plmnId": {
        "mcc": "string",
        "mnc": "string"
      }
    }
  ],
  "globalRanNodeIdList": [
    {
      "gNbId": {
        "bitLength": 0,
        "gNbValue": "string"
      },
      "n3IwfId": "string",
      "ngeNbId": "string",
      "plmnId": {
        "mcc": "string",
        "mnc": "string"
      }
    }
  ]
}
```



```

    ],
    "name": "string",
    "ncgiList": [
      {
        "nrCellId": "string",
        "plmnId": {
          "mcc": "string",
          "mnc": "string"
        }
      }
    ],
    "praId": "string",
    "presenceState": "INACTIVE",
    "trackingAreaList": [
      {
        "plmnId": {
          "mcc": "string",
          "mnc": "string"
        },
        "tac": "string"
      }
    ]
  ]
}

```

Sample Response body structure for GET, POST, and PUT operations:

```

{
  "date": "string",
  "errors": [
    {
      "message": "string",
      "name": "string"
    }
  ],
  "exportData": [
    {
      "ecgiList": [
        {
          "eutraCellId": "string",
          "plmnId": {
            "mcc": "string",
            "mnc": "string"
          }
        }
      ],
      "globalRanNodeIdList": [
        {
          "gNbId": {
            "bitLength": 0,
            "gNbValue": "string"
          },
          "n3IwfId": "string",
          "ngeNbId": "string",
          "plmnId": {
            "mcc": "string",

```

```

        "mnc": "string"
      }
    },
    "name": "string",
    "ncgiList": [
      {
        "nrCellId": "string",
        "plmnId": {
          "mcc": "string",
          "mnc": "string"
        }
      }
    ],
    "praId": "string",
    "presenceState": "INACTIVE",
    "trackingAreaList": [
      {
        "plmnId": {
          "mcc": "string",
          "mnc": "string"
        },
        "tac": "string"
      }
    ]
  },
  "key": "string",
  "sourceVersion": "string",
  "topic": "string"
}

```

Delete Presence Reporting Areas

Table 2-317 Request/Response Body Parameters for DELETE operation

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
presenceReportingAreaName	string	M	Presence Reporting Area Name

Export/Import Presence Reporting Areas

Table 2-318 Request/Response Body Parameters for Export/Import operations

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
date	string		Current timestamp

Table 2-318 (Cont.) Request/Response Body Parameters for Export/Import operations

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
exportData	array		Exported list of presence reporting area. For more information, see Get, Create, AND Update Presence Reporting Areas .
key	string		Indicates the ID
sourceVersion	string		System version of product from which data is exported
topic	string		Topic of each managed object

Sample Request Body structure for Import/Export operations:

```
{
  "date": "string",
  "errors": [
    {
      "message": "string",
      "name": "string"
    }
  ],
  "exportData": [
    {
      "ecgiList": [
        {
          "eutraCellId": "string",
          "plmnId": {
            "mcc": "string",
            "mnc": "string"
          }
        }
      ],
      "globalRanNodeIdList": [
        {
          "gNbId": {
            "bitLength": 0,
            "gNbValue": "string"
          },
          "n3IwfId": "string",
          "ngeNbId": "string",
          "plmnId": {
            "mcc": "string",
            "mnc": "string"
          }
        }
      ],
      "name": "string",
```

```

    "ncgiList": [
      {
        "nrCellId": "string",
        "plmnId": {
          "mcc": "string",
          "mnc": "string"
        }
      }
    ],
    "praId": "string",
    "presenceState": "INACTIVE",
    "trackingAreaList": [
      {
        "plmnId": {
          "mcc": "string",
          "mnc": "string"
        },
        "tac": "string"
      }
    ]
  }
},
"key": "string",
"sourceVersion": "string",
"topic": "string"
}

```

2.61 Policy Table

Table 2-319 Supported REST APIs

Description	HTTP Method or Custom Operation	Resource URI	Possible Result Code
Get Policy Tables	GET	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/common/policytables	See Table A-1
Create Policy Tables	POST	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/common/policytables	See Table A-3
Export Policy Tables	GET	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/common/policytables/export	See Table A-1
Import Policy Tables	POST	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/common/policytables/import	See Table A-3

Table 2-319 (Cont.) Supported REST APIs

Description	HTTP Method or Custom Operation	Resource URI	Possible Result Code
Delete Policy Table	DELETE	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/common/policytables/{serviceName}/{policyTableName}	See Table A-4

Get and Create Policy Tables

Table 2-320 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
columns	array	O	Specifies the column of a policy table.
name	String	O	Specifies the name of a policy table.
description	name	O	Specifies the description of a policy table.
rows	array	O	Specifies the rows of a policy table.

Sample Request body structure for POST operation:

```
[
  {
    "columns": [
      {
        "dataType": "accessType",
        "isKey": true,
        "name": "string"
      }
    ],
    "description": "string",
    "name": "string",
    "rows": [
      {}
    ],
    "serviceName": "string",
    "serviceType": "string"
  }
]
```

Sample Response body structure for GET and POST operations:

```
{
  "date": "string",
  "errors": [
```

```

    {
      "message": "string",
      "name": "string"
    }
  ],
  "exportData": [
    {
      "columns": [
        {
          "dataType": "accessType",
          "isKey": true,
          "name": "string"
        }
      ],
      "description": "string",
      "name": "string",
      "rows": [
        {}
      ],
      "serviceName": "string"
    }
  ],
  "sourceVersion": "string",
  "topic": "string"
}

```

Delete Policy Tables

Table 2-321 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
policyTableName	string	M	Policy Table Name
serviceName	string	M	Service Name

Export and Import Policy Tables

The following table describes the request and response body parameters for Import and Export operations:

Table 2-322 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
date	string		Current timestamp
errors:message	string		Error message.
errors:name	string		Error name.
exportData	array		Exported list of policy tables. For more information, see Get and Create Policy Tables .

Table 2-322 (Cont.) Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
sourceVersion	string		System version of product from which data is exported
topic	string		Topic of each managed object

Supported Actions for Importing Policy Tables

The following table describes the actions supported by Policy when the user imports Policy Tables:

Table 2-323 Supported Actions for Importing Policy Tables

Action	Description
ignore	On selecting the <code>ignore</code> option, no changes are made to the existing Policy Table. The Policy Table in the imported file is ignored or skipped. No changes are made to the UUIDs and existing policies remain unaffected with this option.
retain	On selecting the <code>retain</code> option, no changes are made to the existing Policy Table. The Policy Table in the imported file is ignored or skipped. No changes are made to the UUIDs and existing policies remain unaffected with this option.
replace	On selecting the <code>replace</code> option, the existing Policy Table is completely replaced with the Policy table in the imported file. Since UUIDs are re-generated for rows and columns, the user needs to update the existing policies that use the Policy Table being replaced with the new one.
merge	On selecting the Merge option, rows of the existing Policy Table are merged with the rows of the Policy table in the imported file only if the schema for key and non-key columns is same for both the Policy Tables. All rows of the existing table with conflict are replaced with the new rows from the imported table. Note: Two rows are considered to be in conflict when they have same values for the Key columns. In case of a conflict, the rows of the existing Policy Table are replaced with the rows of the new Policy Table. In this case, the UUIDs remain unaffected and do not impact the existing policies.

Sample Request Body structure for Import/Export operations:

```
{
  "date": "string",
  "errors": [
    {
```

```

        "message": "string",
        "name": "string"
    }
  ],
  "exportData": [
    {
      "columns": [
        {
          "dataType": "accessType",
          "isKey": true,
          "name": "string"
        }
      ],
      "description": "string",
      "name": "string",
      "rows": [
        {}
      ],
      "serviceName": "string"
    }
  ],
  "sourceVersion": "string",
  "topic": "string"
}

```

2.62 Policy Counter Id

Table 2-324 Supported REST APIs

Description	HTTP Method or Custom Operation	Resource URI	Possible Result Code
Create Policy Control Id	POST	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/common/policycounterids	See Table A-3
Export Policy Control Id	GET	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/common/policycounterids/export	See Table A-1
Import Policy Control Id	POST	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/common/policycounterids/import	See Table A-3
Get Policy Control Id	GET	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/common/policycounterids/{policyCounterIdName}	See Table A-1
Update Policy Control Id	PUT	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/common/policycounterids/{policyCounterIdName}	See Table A-2

Table 2-324 (Cont.) Supported REST APIs

Description	HTTP Method or Custom Operation	Resource URI	Possible Result Code
Delete Policy Control Id	DELETE	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/common/policycounterids/{policyCounterIdName}	See Table A-4

Get, Create, and Update Policy Counter Id s**Table 2-325 Request/Response Body Parameters**

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)aints	Description
defaultStatus	string	O	Specifies the default status of Policy Counter Id.
desc	string	O	Specifies the description of Policy Counter Id.
id	string	O	Specifies the ID of Policy Counter Id.
name	string	M	Specifies the name of Policy Counter Id.

Sample Request body structure for POST and PUT operations:

```
[
  {
    "columns": [
      {
        "dataType": "accessType",
        "isKey": true,
        "name": "string"
      }
    ],
    "description": "string",
    "name": "string",
    "rows": [
      {}
    ],
    "serviceName": "string",
    "serviceType": "string"
  }
]
```

Sample Response body structure for GET, POST, and PUT operations:

```
{
  "date": "string",
  "errors": [
    {
```

```

        "message": "string",
        "name": "string"
    }
],
"exportData": [
    {
        "columns": [
            {
                "dataType": "accessType",
                "isKey": true,
                "name": "string"
            }
        ],
        "description": "string",
        "name": "string",
        "rows": [
            {}
        ],
        "serviceName": "string"
    }
],
"sourceVersion": "string",
"topic": "string"
}

```

Delete Policy Counter Id s

Table 2-326 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
policyControlIdName	string	M	Policy Counter Id's Name

Export/Import Policy Counter Id s

Table 2-327 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
date	string		Current timestamp
exportData	array		Exported list of policy control id. For more information, see Get, Create, and Update Policy Counter Id s .
key	string		Indicates the ID
sourceVersion	string		System version of product from which data is exported
topic	string		Topic of each managed object

Sample Request Body structure for Import/Export operations:

```

{
  "date": "string",
  "errors": [
    {
      "message": "string",
      "name": "string"
    }
  ],
  "exportData": [
    {
      "columns": [
        {
          "dataType": "accessType",
          "isKey": true,
          "name": "string"
        }
      ],
      "description": "string",
      "name": "string",
      "rows": [
        {}
      ],
      "serviceName": "string"
    }
  ],
  "sourceVersion": "string",
  "topic": "string"
}

```

2.63 Diameter Settings

This section describes the available service URIs to retrieve and update diameter settings.

Table 2-328 Supported REST APIs

Description	HTTP Method or Custom Operation	Resource URI	Possible Result Code
Get Diameter Settings	GET	{apiRoot}/oc-cnpolicy-configuration/v1/diameter/settings	See Table A-1
Update Diameter Settings	PUT	{apiRoot}/oc-cnpolicy-configuration/v1/diameter/settings	See Table A-2
Export Diameter Settings	GET	{apiRoot}/oc-cnpolicy-configuration/v1/diameter/settings/export	See Table A-1
Import Diameter Settings	POST	{apiRoot}/oc-cnpolicy-configuration/v1/diameter/settings/import	See Table A-3

Get and Update Operations

This section describes the body parameters for APIs for diameter settings.

Table 2-329 Request and Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
congestionControl	DiamSettingsCongestionControl	O	Specifies the congestion control configurations.
overloadControl	DiamSettingsOverloadControl	O	Specifies the overload control configurations.
timer	DiamSettingsTimer	O	Specifies the timer configurations for Diameter Gateway.
transport	DiamSettingsTransport	O	Specifies the transport protocol configurations for Diameter Gateway.
topologyhiding	DiamSettingTopologyhiding	O	Specifies the topology hiding configurations for Diameter Gateway.
messageTimers	DiamSettingsMessageTimers	O	Specifies the request timer configurations for Diameter applications.
messagePriority	DiameterSettingsMessagePriority	O	Specifies the message priority profile.
advancedSettings	DiamAdvancedSettings	O	Specifies the list of key/value pair.

Table 2-330 DiamSettingsCongestionControl

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
congestionLoadSheddingProfile	string	O	Specifies the load shedding profile name for congestion control.

Table 2-331 DiamSettingsOverloadControl

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
overloadLoadSheddingProfile	string	Optional	Specifies the load shedding profile name for overload control.

Table 2-332 messagePriority

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
messagePriorityProfile	string	Optional	Specifies the message priority profile name for overload control and congestion control.

Table 2-333 DiamSettingsTimer

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
connectionTimeout	Number	M	Defines the connection timeout interval in seconds. The default value is 3 seconds.
reconnectDelay	Number	M	Defines the time frame to delay before attempting to reconnect after a connection failure in seconds. The default value is 3 seconds.
responseTimeout	Number	M	Defines the response timeout interval in milliseconds. The default value is 5000 ms.
watchdogInterval	Number	M	Defines the watchdog interval in seconds. The default value is 6 seconds.

Table 2-334 DiamSettingsTransport

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
protocol	string, Enum: Array[]	O	Specifies the Diameter protocol. The values: [TCP, SCTP].

Table 2-335 DiamSettingsMessageTimers

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
applId	intger	O	Specifies the diameter application ID for which topology hiding feature is to be enabled. Example: 16777236
appResponseTimeoutValue	integer	O	Specifies the application response timeout value in milliseconds. Minimum: 3 Maximum: 2147483647 Example: 5000
cmdCodeResponseTimeoutValueMap	Map(String:String)	O	Specifies Command Code Response Timeout for AAR, STR, RAR and ASR.

Table 2-336 DiamAdvancedSettings

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
key	string	O	Specifies the key name.
value	string	O	Specifies the value of the key.

Sample Request body structure for GET and PUT operations:

```
{
  "timer": {
    "reconnectDelay": "3",
    "responseTimeout": "5000",
    "connectionTimeout": "3",
    "watchdogInterval": "6"
  },
  "transport": {
    "protocol": "TCP"
  },
  "congestionControl": {
    "congestionLoadSheddingProfile": "string",
  },
  "overloadControl": {
    "overloadLoadSheddingProfile": "string",
  },
  "messagePriority": {
    "messagePriorityProfile": "string"
  },
  "topologyhiding": {
    "EnableTopologyHiding": true,

```

```

    "AppsToHide": [
      "Gx"
    ]
  },
  "messageTimers": [
    {
      "appId": 16777236,
      "appResponseTimeoutValue": 5000,
      "cmdCodeResponseTimeoutValueMap": {
        "258": 5000,
        "265": 5000,
        "272": 5000,
        "274": 5000,
        "275": 5000,
        "8388635": 5000,
        "8388636": 5000,
        "8388637": 5000
      }
    }
  ],
  "advancedSettings": [
    {
      "key": "string",
      "value": "string"
    }
  ]
}

```

Export and Import Diameter Settings

The following table describes the request and response parameters for export and import operations:

Table 2-337 Request and Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
date	string	Optional	Specifies the current timestamp.
errors.message	string	Optional	The reason of the failure.
error.name	string	Optional	Name of the components that the user is unable to export or import successfully.
exportData	array	Mandatory	Exported list of diameter settings. For more information, see Get and Update Operations .
sourceVersion	string	Optional	System version of product from which data is exported.

Table 2-337 (Cont.) Request and Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
topic	string	Mandatory	Topic of each managed object.

Sample Request Body structure for Import/Export operations:

```

{
  "topic": "string",
  "sourceVersion": "string",
  "date": "string",
  "exportData": {
    "timer": {
      "reconnectDelay": "3",
      "responseTimeout": "5000",
      "connectionTimeout": "3",
      "watchdogInterval": "6"
    },
    "transport": {
      "protocol": "TCP"
    },
    "congestionControl": {
      "congestionLoadSheddingProfile": "string",
    },
    "overloadControl": {
      "overloadLoadSheddingProfile": "string",
    },
    "messagePriority": {
      "messagePriorityProfile": "string"
    },
    "topologyhiding": {
      "EnableTopologyHiding": true,
      "AppsToHide": [
        "Gx"
      ]
    },
    "messageTimers": [
      {
        "appId": 16777236,
        "appResponseTimeoutValue": 5000,
        "cmdCodeResponseTimeoutValueMap": {
          "258": 5000,
          "265": 5000,
          "272": 5000,
          "274": 5000,
          "275": 5000,
          "8388635": 5000,
          "8388636": 5000,
          "8388637": 5000
        }
      }
    ]
  }
}

```



```

    ],
    "advancedSettings": [
      {
        "key": "string",
        "value": "string"
      }
    ],
    "errors": [
      {
        "name": "string",
        "message": "string"
      }
    ]
  }
}

```

2.64 Diameter Repaving

This section describes the available service URIs to retrieve and update diameter settings.

Table 2-338 Supported REST APIs

Description	HTTP Method or Custom Operation	Resource URI	Possible Result Code
Get Current Diameter Repaving Configuration	GET	{apiRoot}/oc-cnpolicy-configuration/v1/diameterRepaving/config	200: Success 400: Bad request - Invalid JSON or missing required fields 500: Internal Server Error
Update Diameter Repaving Configuration	PUT	{apiRoot}/oc-cnpolicy-configuration/v1/diameterRepaving/config	200: Configuration updated successfully 400: Bad request - Invalid JSON or missing required fields 500: Internal Server Error
Export Diameter Repaving Configuration	GET	{apiRoot}/oc-cnpolicy-configuration/v1/diameterRepaving/export	200: Success 400: Bad request - Invalid JSON or missing required fields 404: Configuration not found
Import Diameter Repaving Configuration	POST	{apiRoot}/oc-cnpolicy-configuration/v1/diameterRepaving/import?action={action} Supported actions are: - ignore: to ignore the imported configuration - replace: to replace the existing configuration with the imported configuration	200: importDiameterRepaving Config 200 response 201: Imported successfully 400: Bad request

Table 2-338 (Cont.) Supported REST APIs

Description	HTTP Method or Custom Operation	Resource URI	Possible Result Code
Trigger Diameter Disconnection	POST	{apiRoot}/oc-cnpolicy-configuration/v1/diameterRepaving/triggerDisconnection	• 200: triggerDisconnection 200 response • 202: Disconnection triggered • 400: Bad request - Invalid JSON or missing required fields • 409: Conflict • 500: Internal Server Error
Get Diameter Trigger History	GET	{apiRoot}/oc-cnpolicy-configuration/v1/diameterRepaving/triggerHistory	• 200: Success • 400: Bad request - Invalid JSON or missing required fields • 500: Internal Server Error

Table 2-339 Request and Response Body Parameters for GET/PUT Diameter Repaving Configuration

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
enableRepaving	Boolean	Mandatory	Specifies whether to enable or disable the Diameter Gateway Repaving feature.

Sample Request Body structure for GET/PUT operations:

```
{
  "enableRepaving": true
}
```

Table 2-340 Request and Response Body Parameters for Import Diameter Repaving Configuration

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
sourceVersion	string	Optional	System version of product from which data is exported.

Table 2-340 (Cont.) Request and Response Body Parameters for Import Diameter Repaving Configuration

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
topic	string	Mandatory	Configuration topic name. Must match the Diameter Repaving config topic. Possible value: common.public.connectionrepaving.diameter-gateway.config
exportData	object	Mandatory	Exported list of Diameter repaving configuration.
exportData.enableRepaving	Boolean	Mandatory	Specifies whether the Diameter Gateway Repaving feature is enabled. Possible values: - true - false

Sample Request Body structure for Import operations:

```
{
  "topic": "common.public.connectionrepaving.diameter-gateway.config",
  "sourceVersion": "<system-version>",
  "exportData": {
    "enableRepaving": true
  }
}
```

Table 2-341 Request and Response Body Parameters for Export Diameter Repaving Configuration

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
sourceVersion	string	Optional	System version of product from which data is exported.
topic	string	Mandatory	Topic of each managed object.
exportData	object	Mandatory	Exported list of Diameter repaving configuration.
exportData.enableRepaving	Boolean	Mandatory	Specifies whether the Diameter Gateway Repaving feature is enabled.

Sample Request Body structure for Export operations:

```

{
  "topic": "common.public.connectionrepaving.diameter-gateway.config",
  "sourceVersion": "<system-version>",
  "exportData": {
    "enableRepaving": true
  }
}

```

Table 2-342 Request and Response Body Parameters for Trigger Disconnection

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
action	string	Mandatory	Indicates to trigger the Diameter Gateway repaving action and force disconnection in Diameter Gateway pods. Possible value: TRIGGER_REPAVING

Sample Response for Trigger Diameter Disconnection:

```

{
  "action": "TRIGGER_REPAVING"
}

```

Table 2-343 Request and Response Body Parameters for Get Diameter Trigger History

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
id	string	Mandatory	Unique identifier for the entry (String/UUID)
type	string	Mandatory	Stores the category of the historical data. For Diameter Gateway Repaving feature, the value is DIAMETER_REPAVING.
value	string	Mandatory	Records when the state change occurred (Timestamp).
timeStamp	string	Mandatory	Records when the state change occurred (Timestamp).
status	string	Mandatory	Indicates the trigger result. Supported values are SUCCESS and FAILURE.

Sample Response for Get Diameter Trigger History:

```
{
  "id": "string",
  "type": "string",
  "value": "string",
  "timeStamp": "2026-06-06T13:57:52.502Z",
  "status": "string"
}
```

2.65 Diameter Routing Table

Table 2-344 Supported REST APIs

Description	HTTP Method or Custom Operation	Resource URI	Possible Result Code
Export Diameter Routing Table	GET	{apiRoot}/oc-cnpolicy-configuration/v1/diameter/routingTable/export	See Table A-1
Import Diameter Routing Table	POST	{apiRoot}/oc-cnpolicy-configuration/v1/diameter/routingTable/import	See Table A-3
Get Diameter Routing Table	GET	{apiRoot}/oc-cnpolicy-configuration/v1/diameter/routingTable	See Table A-1
Update Diameter Routing Table	PUT	{apiRoot}/oc-cnpolicy-configuration/v1/diameter/routingTable	See Table A-2

Get and Update Operations**Table 2-345 Request/Response Body Parameters**

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
defaultRoute			
routeTable			

Table 2-346 defaultRoute

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
serverID	string	O	

Table 2-347 routeTable

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
appIDs			
hosts	string		
name	string	O	
priority	string	O	
realms	string		
type	Realm		

Sample Request body structure for PUT operations:

```

"defaultRoute": {
  "serverId": "string"
},
"routeTable": [
  {
    "appIds": [
      "All"
    ],
    "hosts": [
      "string"
    ],
    "name": "string",
    "priority": "string",
    "realms": [
      "string"
    ],
    "serverIds": [
      "string"
    ],
    "type": "Host"
  }
]

```

Sample Response body structure for GET and PUT operations:

```

{
  "defaultRoute": {
    "serverId": "string"
  },
  "routeTable": [
    {
      "appIds": [
        "All"
      ],
      "hosts": [
        "string"
      ],

```

```

    "name": "string",
    "priority": "string",
    "realms": [
      "string"
    ],
    "serverIds": [
      "string"
    ],
    "type": "Host"
  }
]
}

```

Export/Import Diameter Routing Table

Table 2-348 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
date	string		Current timestamp
exportData	array		Exported list of diameter routing table. For more information, see Get and Update Operations .
sourceVersion	string		System version of product from which data is exported
topic	string		Topic of each managed object

Sample Request Body structure for Import/Export operations:

```

{
  "date": "string",
  "exportData": {
    "defaultRoute": {
      "serverId": "string"
    },
    "routeTable": [
      {
        "appIds": [
          "All"
        ],
        "hosts": [
          "string"
        ],
        "name": "string",
        "priority": "string",
        "realms": [
          "string"
        ],
        "serverIds": [
          "string"
        ],
      },
    ],
  },
}

```

```

        "type": "Host"
      }
    ]
  },
  "sourceVersion": "string",
  "topic": "string"
}

```

2.66 Data Sources

Table 2-349 Supported REST APIs

Create Data Sources	HTTP Method or Custom Operation	Resource URI	Possible Result Code
Get Data Sources	GET	{apiRoot}/oc-cnpolicy-configuration/v1/datasources/{datasourceName}	See Table A-1
Update Data Sources	PUT	{apiRoot}/oc-cnpolicy-configuration/v1/datasources/{datasourceName}	See Table A-2
Delete Data Source	DELETE	{apiRoot}/oc-cnpolicy-configuration/v1/datasources/{datasourceName}	See Table A-4
Create Data Sources	POST	{apiRoot}/oc-cnpolicy-configuration/v1/datasources	See Table A-3
Import Data Sources	POST	{apiRoot}/oc-cnpolicy-configuration/v1/datasources/import	See Table A-3
Export Data Sources	GET	{apiRoot}/oc-cnpolicy-configuration/v1/datasources/export	See Table A-1

Get, Create, and Update Data Sources

Table 2-350 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/Optional(O)/Conditional(C)	Description
name	string	M	Data Source Name
description	string	O	Details about the data source.
type	string	O	Type of data source. Possible values are: Enum:[LDAP, Sy]
admin_state	boolean	O	when value is set to true, datasource (Sy) interaction takes place. Default Value: true

Table 2-350 (Cont.) Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
realm	string	O	Defines the realm of the primary and optional secondary servers to connect (required).
enable_subscription	boolean	O	Indicates whether MPE needs to subscribe to notifications from SH. Default Value: true
use_notif_eff	boolean	O	Specifies the User Data Request / Answer will allow multiple data references, Service Indications, and Identity Sets. The User Data Answer will be able to combine DataReference items resulting in the User Data Answer contents including a single XML document with the separate XML sections populated.
ocs_from_peer_nodes	boolean	O	Selecting diameter peer nodes as primary, secondary, tertiary, and quaternary servers for Sy data source type.
refPeerNodePrimary	string	O	Primary diameter peer node server.
refPeerNodeSecondary	string	O	Secondary diameter peer node server.
refPeerNodeTertiary	string	O	Tertiary diameter peer node server.
refPeerNodeQuaternary	string	O	Quaternary diameter peer node server.
timer_profile	string	-	-
read_connection	string	O	Number of read connections established with data source. Possible values are: Enum:[1, 2, 3, 4, 5, 6, 7, 8, 9, 10]
primary_server	PrimaryServer	M	Primary data source server. The LDAP connection will be established with primary data source.
secondary_server	CommonServer	O	Secondary data source server. If Primary server is not reachable, then LDAP connection will be established with secondary (if available).
tertiary_server	CommonServer	O	Tertiary data source server. If primary and secondary are not reachable, then LDAP connection will be established with tertiary (if available) .

Table 2-350 (Cont.) Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
quaternary_server	CommonServer	O	Quaternary data source server. If primary , secondary and tertiary are not reachable then LDAP connection will be established with tertiary (if available) .
search_criteria	SearchCriteria	O	The criteria on which the data source search will be performed.
search_filter	SearchFilter	O	The search filter during the data source search.
ldap_retry	LdapRetry	O	The retry configuration for LDAP requests.

Table 2-351 PrimaryServer

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
identity	string	M	Primary server identity.
addr	string	M	Load balancer IP of Diameter gateway.
port	string	M	Primary server Port. Possible values are: Enter a range in [0-65535] number.

Table 2-352 CommonServer

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
identity	string	O	Common server identity.
addr	string	O	Load balancer IP of Diameter gateway.
port	string	M	Common server Port. Possible values are: Enter a range in [0-65535] number.

Table 2-353 SearchCriteria

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
rootDN	string	O	-
baseDN	string	O	-

Table 2-353 (Cont.) SearchCriteria

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
type	string	O	Possible values are: Enum:[NAI, MSISDN, IMSI]

Table 2-354 SearchFilter

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
id_filters_type	string	O	Possible values are: Enum:[NAI, MSISDN, IMSI]

Table 2-355 LdapRetry

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
retry_enabled	Boolean	O	Possible values are: True, False.
max_retry_count	Integer	O	Possible values are: 1, 2.
retry_on_error_timeout	List of Integers	O	Possible values are: Positive Integers

Sample Request body structure for GET, POST, and PUT operations:

```
{
  "name": "string",
  "description": "string",
  "type": "LDAP",
  "admin_state": true,
  "realm": "string",
  "enable_subscription": true,
  "use_notif_eff": true,
  "ocs_from_peer_nodes": true,
  "refPeerNodePrimary": "string",
  "refPeerNodeSecondary": "string",
  "refPeerNodeTertiary": "string",
  "refPeerNodeQuaternary": "string",
  "sh_profile": "v1",
  "timer_profile": "string",
  "read_connection": "1",
  "primary_server": {
    "identity": "string",
    "addr": "string",
    "port": "string"
  }
}
```

```

    },
    "secondary_server": {
      "identity": "string",
      "addr": "string",
      "port": "string"
    },
    "tertiary_server": {
      "identity": "string",
      "addr": "string",
      "port": "string"
    },
    "quaternary_server": {
      "identity": "string",
      "addr": "string",
      "port": "string"
    },
    "search_criteria": {
      "rootDN": "string",
      "baseDN": "string",
      "type": "NAI"
    },
    "search_filter": {
      "id_filters_type": "NAI"
    }
  }
  "ldap_retry": {
    "retry_enabled": true,
    "max_retry_count": 0,
    "retry_on_error_timeout": [0]
  }
}

```

Delete Data Sources

Table 2-356 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
Data Source Name	string	M	Data Source Name

Export/Import Data Sources

Table 2-357 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
date	string	-	Current timestamp
exportData	array	-	Exported list of data sources. For more information, see Get, Create, and Update Data Sources .
key	string	-	Indicates the ID

Table 2-357 (Cont.) Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
sourceVersion	string	-	System version of the product from which data is exported
systemVersion	string	-	
topic	string	-	Topic of each managed object

Sample Request Body structure for Import/Export operations:

```

{
  "systemVersion": "string",
  "topic": "string",
  "sourceVersion": "string",
  "date": "string",
  "exportData": [
    {
      "name": "string",
      "description": "string",
      "type": "LDAP",
      "admin_state": true,
      "realm": "string",
      "enable_subscription": true,
      "use_notif_eff": true,
      "ocs_from_peer_nodes": true,
      "refPeerNodePrimary": "string",
      "refPeerNodeSecondary": "string",
      "refPeerNodeTertiary": "string",
      "refPeerNodeQuaternary": "string",
      "sh_profile": "v1",
      "timer_profile": "string",
      "read_connection": "1",
      "primary_server": {
        "identity": "string",
        "addr": "string",
        "port": "string"
      },
      "secondary_server": {
        "identity": "string",
        "addr": "string",
        "port": "string"
      },
      "tertiary_server": {
        "identity": "string",
        "addr": "string",
        "port": "string"
      },
      "quaternary_server": {
        "identity": "string",

```

```

        "addr": "string",
        "port": "string"
    },
    "search_criteria": {
        "rootDN": "string",
        "baseDN": "string",
        "type": "NAI"
    },
    "search_filter": {
        "id_filters_type": "NAI"
    }
}
],
"errors": [
    {
        "name": "string",
        "message": "string"
    }
]
}

```

2.67 Bulk Import Export Controller

Table 2-358 Supported REST APIs

Description	HTTP Method or Custom Operation	Resource URI	Possible Result Code
Bulk Import	POST	{apiRoot}/oc-cnpolicy-configuration/v1/administration/import	200: OK 201: Created 401: Unauthorized 403: Forbidden 404: Not Found
Import Status	GET	{apiRoot}/oc-cnpolicy-configuration/v1/administration/import/{importResourceId}/status	200: OK 401: Unauthorized 403: Forbidden 404: Not Found
Import Report	GET	{apiRoot}/oc-cnpolicy-configuration/v1/administration/import/{importResourceId}/report	200: OK 401: Unauthorized 403: Forbidden 404: Not Found
Import Resource Ids	GET	{apiRoot}/oc-cnpolicy-configuration/v1/administration/import	200: OK 401: Unauthorized 403: Forbidden 404: Not Found
Bulk Export	POST	{apiRoot}/oc-cnpolicy-configuration/v1/administration/export	200: OK 201: Created 401: Unauthorized 403: Forbidden 404: Not Found

Table 2-358 (Cont.) Supported REST APIs

Description	HTTP Method or Custom Operation	Resource URI	Possible Result Code
Export Status for Policy	GET	{apiRoot}/oc-cnpolicy-configuration/v1/administration/export/{exportResourceId}/status	200: OK 401: Unauthorized 403: Forbidden 404: Not Found
Export Report for Policy	GET	{apiRoot}/oc-cnpolicy-configuration/v1/administration/export/{exportResourceId}/report	200: OK 401: Unauthorized 403: Forbidden 404: Not Found
Download Exported File	GET	{apiRoot}/oc-cnpolicy-configuration/v1/administration/export/{exportResourceId}/download	200: OK 401: Unauthorized 403: Forbidden 404: Not Found
Export Resource Ids	GET	{apiRoot}/oc-cnpolicy-configuration/v1/administration/export	200: OK 401: Unauthorized 403: Forbidden 404: Not Found

Note

The **Bulk Import/Export** APIs return a ResourceId in response to the POST request. The ResourceId is the background task id for the POST operations. This id can be used to track the import or export requests, and download the export data. For example, the POST API for bulk export operation takes MO name as input. The response of this API contains the resource id of the file created for export. You can use this resource Id to download the export data at any point of time.

Below are the status displayed by Bulk import/export:

- **IN_PROGRESS**: The import/export is running.
- **DONE**: The import/export is finished. Following are the possible status if the import/export is in DONE status:
 - **SUCCESS** : The import/export is successful
 - **FAILED** : The import/export is failed
 - **PARTIAL_SUCCESS** : The import/export is partially successful

2.68 Consistent Logging Level

Table 2-359 Supported REST APIs - Consistent Logging Level

Description	HTTP Method or Custom Operation	Resource URI	Possible Result Code
Get All (Export) Consistent Logging Level	GET	/oc-cnpolicy-configuration/v1/conLoggingLevelConfig/export/{serviceType}	See Table A-1
Import Consistent Logging Level	POST	/oc-cnpolicy-configuration/v1/conLoggingLevelConfig/import/{serviceType}	See Table A-3
Get Consistent Logging Level	GET	/oc-cnpolicy-configuration/v1/conLoggingLevelConfig/{serviceType}	See Table A-1
Update Consistent Logging Level	PUT	/oc-cnpolicy-configuration/v1/conLoggingLevelConfig/{serviceType}	See Table A-2

Get and Update Consistent Logging Level

Table 2-360 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
appLogLevel	String	M	Defines the application's root log level.
packageLogLevel: logLevelForPackage	String	O	Defines the log level for the package.
packageLogLevel:package packageName	String	O	Defines the package name.
serviceType	String	M	Specifies the following supported service types: • PCRF Core • PCF Session Management • PCF Access and Mobility • PCF UE Policy • PCF User Connector • NRF Discovery Client • NRF Management Client • Policy DS

Sample Request body for Consistent Logging Level PUT operation:

```
{
  "appLogLevel": "DEBUG",
  "packageLogLevel": [
```



```

    {
      "logLevelForPackage": "DEBUG",
      "packageName": "string"
    }
  ]
}

```

Sample Response body structure for Consistent Logging Level GET and PUT operation:

```

{
  "appLogLevel": "DEBUG",
  "packageLogLevel": [
    {
      "logLevelForPackage": "DEBUG",
      "packageName": "string"
    }
  ]
}

```

Import and Export Consistent Logging Level

Table 2-361 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
date	string		Current timestamp
exportData	array		Exported list of Consistent Logging Level. For more information, see Get and Update Consistent Logging Level .
key	string		Indicates the ID
sourceVersion	string		System version of product from which data is exported
topic	string		Topic of each managed object

Sample Request Body structure for Consistent Logging Level Import and Export operations:

```

{
  "date": "string",
  "exportData": {
    "appLogLevel": "DEBUG",
    "packageLogLevel": [
      {
        "logLevelForPackage": "DEBUG",
        "packageName": "string"
      }
    ]
  },
}

```

```

    "key": "string",
    "sourceVersion": "string",
    "topic": "string"
  }

```

2.69 Load Shedding Profile

This section describes the available service URIs to create and configure load shedding profiles for CNC Policy.

Table 2-362 Supported REST APIs - Load Shedding Profile

Description	HTTP Method or Custom Operation	Resource URI	Possible Result Code
Create Load Shedding Profile	POST	{apiRoot}/oc-cnpolicy-configuration/v1/diameter/loadsheddingprofiles	See Table A-3
Get Load Shedding Profile	GET	{apiRoot}/oc-cnpolicy-configuration/v1/diameter/loadsheddingprofiles/{loadsheddingName}	See Table A-1
Update Load Shedding Profile	PUT	{apiRoot}/oc-cnpolicy-configuration/v1/diameter/loadsheddingprofiles/{loadsheddingName}	See Table A-2
Export Load Shedding Profiles	GET	{apiRoot}/oc-cnpolicy-configuration/v1/diameter/loadsheddingprofiles/export	See Table A-1
Import Load Shedding Profiles	POST	{apiRoot}/oc-cnpolicy-configuration/v1/diameter/loadsheddingprofiles/import	See Table A-3
Delete Load Shedding Profile	DELETE	{apiRoot}/oc-cnpolicy-configuration/v1/diameter/loadsheddingprofiles/{loadsheddingName}	See Table A-4

Get, Create, and Update Load Shedding Profile

The following table describes the request and response body parameters used in APIs for load shedding profiles.

Table 2-363 Request and Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
loadSheddingRules	CongestionLoadSheddingRules	Optional	Specifies the list of configured Congestion Load Shedding Rules.
name	string	Mandatory	Specifies the unique name of the load shedding profile.
overloadLoadSheddingRules	OverloadLoadSheddingRules	Optional	Specifies the list of configured Overload Load Shedding Rules.
type	Enum The supported values are: • L1 • L2 • L3 • L4 • L5 • L6 • L7 • L8 • L9 • L10 Note: Currently, Policy supports configuring load shedding profiles upto L10 only for PCF Session Management and Diameter call flows. For all other service call flows, load shedding profile can be configured only up to L3 level.	Optional	Specifies the type of load shedding profile. The load shedding profile can be one of the following types: • Congestion Control • Overload Control

Table 2-364 CongestionLoadSheddingRules

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
ansWithResultCode	Enum The supported values are: • DIAMETER_TO_O_BUSY • DIAMETER_UNABLE_TO_COMPLY • DIAMETER_UNABLE_TO_DELIVER • EXPERIMENTAL_RESULT_CODE	Optional	Specifies the result code, returned in the answer response, when request message is rejected as part of congestion control.
discardPriority	integer	Mandatory	Specifies the discard priority for the congestion load shedding rule. The discard priority value can be a number from 0 to 15. Any request message with equal or lower priority is rejected.
resultCode	integer	Conditional	Note: Specify a value for this parameter when you choose EXPERIMENTAL_RESULT_CODE value for the ansWithResultCode parameter. Specifies the custom result code, which is returned in the answer response when service request is rejected due to congestion control. .
state	Enum The supported values are: • CONGESTED • DANGER_OF_CONGESTION	Optional	Specifies the type of state for which you are defining the rule.
vendorId	integer	Conditional	Note: Specify a value for this parameter when you choose EXPERIMENTAL_RESULT_CODE value for the ansWithResultCode parameter. Specifies the vendor ID, which is returned in the answer response when service request is rejected due to congestion control. .

Table 2-365 OverloadLoadSheddingRules

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
ansWithResultCode	Enum The supported values are: • DIAMETER_TO_O_BUSY • DIAMETER_UNABLE_TO_COMPLY • DIAMETER_UNABLE_TO_DELIVER • EXPERIMENTAL_RESULT_CODE	Optional	Specifies the result code, returned in the answer response, when request message is rejected as part of overload control.
discardPriority	integer	Mandatory	Specifies the discard priority for the overload shedding rule. The discard priority value can be a number from 0 to 15. Any request message with equal or lower priority is rejected.
level	Enum The supported values are: • L1 • L2 • L3 • L4 • L5 • L6 • L7 • L8 • L9 • L10 Note: Currently, Policy supports configuring load shedding profiles upto L10 only for PCF Session Management and Diameter call flows. For all other service call flows, load shedding profile can be configured only up to L3 level.	Mandatory	Specifies the name of the level. The name specified in this parameter must match the level name in Ingress Gateway's ocdiscardpolicies.

Table 2-365 (Cont.) OverloadLoadSheddingRules

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
resultCode	integer	Conditional	Note: Specify a value for this parameter when you choose EXPERIMENTAL_RESULT_CODE value for the ansWithResultCode parameter. Specifies the custom result code, which is returned in the answer response when service request is rejected due to overload control.
vendorId	integer	Conditional	Note: Specify a value for this parameter when you choose EXPERIMENTAL_RESULT_CODE value for the ansWithResultCode parameter. Specifies the vendor ID, which is returned in the answer response when service request is rejected due to overload control.

Sample Request body for Load Shedding Profile (PUT and POST operations):

```
{
  "loadSheddingRules": [
    {
      "ansWithResultCode": "DIAMETER_TOO_BUSY",
      "discardPriority": 0,
      "resultCode": 0,
      "state": "CONGESTED",
      "vendorId": 0
    }
  ],
  "name": "string",
  "overloadLoadSheddingRules": [
    {
      "ansWithResultCode": "DIAMETER_TOO_BUSY",
      "discardPriority": 0,
      "level": "L1",
      "resultCode": 0,
      "vendorId": 0
    }
  ],
  "type": "DIAMETER_TOO_BUSY"
}
```

Sample Response body for Load Shedding Profile (PUT, GET, and POST operation):

```

{
  "loadSheddingRules": [
    {
      "ansWithResultCode": "DIAMETER_TOO_BUSY",
      "discardPriority": 0,
      "resultCode": 0,
      "state": "CONGESTED",
      "vendorId": 0
    }
  ],
  "name": "string",
  "overloadLoadSheddingRules": [
    {
      "ansWithResultCode": "DIAMETER_TOO_BUSY",
      "discardPriority": 0,
      "level": "L1",
      "resultCode": 0,
      "vendorId": 0
    }
  ],
  "type": "DIAMETER_TOO_BUSY"
}

```

Import and Export Load Shedding Profile**Table 2-366 Request and Response Body Parameters**

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
date	string	Optional	Specifies the current timestamp.
errors.message	string	Optional	The reason of the failure.
error.name	string	Optional	Name of the components that the user is unable to export or import successfully.
exportData	array	Mandatory	Exported list of Load Shedding Profiles. For more information, see Get, Create, and Update Load Shedding Profile .
key	string	Optional	Indicates the ID of the load shedding profile.
sourceVersion	string	Optional	System version of product from which data is exported.
topic	string	Mandatory	Topic of each managed object.

Sample Request Body structure for Load Shedding Profile Import and Export operations:

```

{
  "date": "string",
  "errors": [
    {
      "message": "string",
      "name": "string"
    }
  ],
  "exportData": [
    {
      "loadSheddingRules": [
        {
          "ansWithResultCode": "DIAMETER_T00_BUSY",
          "discardPriority": 0,
          "resultCode": 0,
          "state": "CONGESTED",
          "vendorId": 0
        }
      ],
      "name": "string",
      "overloadLoadSheddingRules": [
        {
          "ansWithResultCode": "DIAMETER_T00_BUSY",
          "discardPriority": 0,
          "level": "L1",
          "resultCode": 0,
          "vendorId": 0
        }
      ],
      "type": "DIAMETER_T00_BUSY"
    }
  ],
  "key": "string",
  "sourceVersion": "string",
  "topic": "string"
}

```

2.70 Message Priority Profile

Table 2-367 Supported REST APIs - Message Priority Profile

Description	HTTP Method or Custom Operation	Resource URI	Possible Result Code
Create Message Priority Profile	POST	{apiRoot}/oc-cnpolicy-configuration/v1/diameter/messagepriorityprofiles	See Table A-3

Table 2-367 (Cont.) Supported REST APIs - Message Priority Profile

Description	HTTP Method or Custom Operation	Resource URI	Possible Result Code
Get Message Priority Profile	GET	{apiRoot}/oc-cnpolicy-configuration/v1/diameter/messagepriorityprofiles / {messagepriorityName }	See Table A-1
Update Message Priority Profile	PUT	{apiRoot}/oc-cnpolicy-configuration/v1/diameter/messagepriorityprofiles / {messagepriorityName }	See Table A-2
Export Message Priority Profiles	GET	{apiRoot}/oc-cnpolicy-configuration/v1/diameter/messagepriorityprofiles /export	See Table A-1
Import Message Priority Profiles	POST	{apiRoot}/oc-cnpolicy-configuration/v1/diameter/messagepriorityprofiles /import	See Table A-3
Delete Message Priority Profile	DELETE	{apiRoot}/oc-cnpolicy-configuration/v1/diameter/messagepriorityprofiles / {messagepriorityName }	See Table A-4

Get, Create, and Update Message Priority Profile**Table 2-368 Request/Response Body Parameters**

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
name	string	Mandatory	Unique name of the message priority profile.
priorityRules []	array	Optional	Specifies configured message priority rules.
priorityRules [].conditions	conditions	Optional	Specifies the conditions for message priority rule.
priorityRules [].conditions.application	string	Mandatory	Specifies the type of application.
priorityRules [].conditions.message	string	Mandatory	Specifies the type of message for the selected application.

Table 2-368 (Cont.) Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
priorityRules [].conditions.preDefinedAVPConditions	array	Optional	Specifies the pre-defined AVP conditions.
enableDRMPPriority	boolean	Optional	When this switch is enabled, the priority for the message rule is assigned from DRMP AVP.
enableOCMessagePriority	boolean	Optional	When this switch is enabled, the priority for the message rule is assigned from OC-Message-Priority header attribute. Note: In case both Use DRMP Priority and Use OC-Message-Priority is enabled, then OC-Message-Priority value is considered. In case both are disabled then the default message priority is considered.
messagePriority	integer	Mandatory	Specifies the priority assigned to the message. It can be a number from 0 to 15.
ruleName	string	Mandatory	Specifies the unique name of the message priority rule.
rulePriority	integer	Mandatory	Specifies the priority assigned to the message priority rule.

Sample Request body for Message Priority Profile PUT operation:

```
{
  "name": "string",
  "priorityRules": [
    {
      "ruleName": "string",
      "messagePriority": 8,
      "rulePriority": 3,
      "enableDRMPPriority": true,
      "enableOCMessagePriority": true,
      "conditions": {
        "application": "Gx",
        "message": "CCR",
        "preDefinedAVPConditions": [
          {
            "conditionName": "Service-URN",
            "conditionServiceURNIDValue": [
              "SOS"
            ]
          },
          {
            "conditionName": "Called-Station-Id",
            "conditionCSIDValue": [
```

```

        "SOS1"
    ]
},
{
    "conditionName": "CC-Request-Type",
    "conditionCCRTValue": [
        "INITIAL_REQUEST"
    ]
},
{
    "conditionName": "Rx-Request-Type",
    "conditionRxRTValue": [
        "INITIAL_REQUEST"
    ]
},
{
    "conditionName": "MPS-Identifier",
    "conditionMPSIdValue": [
        "123"
    ]
},
{
    "conditionName": "MCPTT-Identifier",
    "conditionMCPTTIdValue": [
        "456"
    ]
},
{
    "conditionName": "MCVideo-Identifier",
    "conditionMCVideoIdValue": [
        "890"
    ]
},
{
    "conditionName": "Reservation-Priority",
    "conditionReservPriorityValue": [
        "1"
    ]
},
{
    "conditionName": "SN-Request-Type",
    "conditionSNRTTypeValue": [
        "ABORT_SESSION_REQUEST"
    ]
},
{
    "conditionName": "OC-Message-Priority",
    "conditionOperator": [
        "EQUALS"
    ],
    "conditionOcMsgPriorityValue": [
        "4"
    ]
}
]
}

```

```

    }
  ]
}

```

Sample Response body structure for Message Priority Profile GET operation:

```

{
  "name": "string",
  "priorityRules": [
    {
      "ruleName": "string",
      "messagePriority": 8,
      "rulePriority": 3,
      "enableDRMPPriority": true,
      "enableOCMessagePriority": true,
      "conditions": {
        "application": "Gx",
        "message": "CCR",
        "preDefinedAVPConditions": [
          {
            "conditionName": "CC-Request-Type",
            "conditionOperator": "EQUALS",
            "conditionCSIDValue": [
              "string"
            ],
            "conditionCCRTValue": "UPDATE_REQUEST",
            "conditionRxRTValue": [
              "INITIAL_REQUEST"
            ],
            "conditionServiceURNIDValue": [
              "string"
            ],
            "conditionMPSIdValue": [
              "string"
            ],
            "conditionMCPTTIdValue": [
              "string"
            ],
            "conditionMCVideoIdValue": [
              "string"
            ],
            "conditionReservPriorityValue": [
              "string"
            ],
            "conditionSNRTypeValue": [
              "ABORT_SESSION_REQUEST"
            ],
            "conditionDRMPValue": [
              "string"
            ],
            "conditionOCMsgPriorityValue": [
              "string"
            ]
          ]
        ]
      }
    ]
  ]
}

```

```

    }
  }
}

```

Import and Export Message Priority Profile

Table 2-369 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
date	string		Current timestamp
errors.message	string		The reason of the failure.
errors.name	string		Name of the components that failed to export or import.
exportData	array		Exported list of Message Priority Profile. For more information, see Get, Create, and Update Message Priority Profile .
key	string		Indicates the ID
sourceVersion	string		System version of product from which data is exported
topic	string		Topic of each managed object

Sample Request Body structure for Message Priority Profile Import and Export operations:

```

{
  "topic": "string",
  "sourceVersion": "string",
  "date": "string",
  "exportData": [
    {
      "name": "string",
      "priorityRules": [
        {
          "ruleName": "string",
          "messagePriority": 8,
          "rulePriority": 3,
          "enableDRMPPriority": true,
          "enableOCMessagePriority": true,
          "conditions": {
            "application": "Gx",
            "message": "CCR",
            "preDefinedAVPConditions": [
              {
                "conditionName": "CC-Request-Type",
                "conditionOperator": "EQUALS",
                "conditionCSIDValue": [

```

```

        "string"
      ],
      "conditionCCRTValue": "UPDATE_REQUEST",
      "conditionRxRTValue": [
        "INITIAL_REQUEST"
      ],
      "conditionServiceURNIDValue": [
        "string"
      ],
      "conditionMPSIdValue": [
        "string"
      ],
      "conditionMCPTTIdValue": [
        "string"
      ],
      "conditionMCVideoIdValue": [
        "string"
      ],
      "conditionReservPriorityValue": [
        "string"
      ],
      "conditionSNRTypeValue": [
        "ABORT_SESSION_REQUEST"
      ],
      "conditionDRMPValue": [
        "string"
      ],
      "conditionOcMsgPriorityValue": [
        "string"
      ]
    ]
  }
}
]
}
],
"errors": [
  {
    "name": "string",
    "message": "string"
  }
]
}

```

2.71 Congestion Threshold

Table 2-370 Supported REST APIs - Congestion Threshold

Description	HTTP Method or Custom Operation	Resource URI	Possible Result Code
Get Congestion Threshold	GET	{apiRoot}/oc-cnpolicy-configuration/v1/threshold/{serviceType} {serviceType} available value is "diam-gateway"	See Table A-1
Update Congestion Threshold	PUT	{apiRoot}/oc-cnpolicy-configuration/v1/threshold/{serviceType} {serviceType} available value: "diam-gateway"	See Table A-2
Export Congestion Thresholds	GET	{apiRoot}/oc-cnpolicy-configuration/v1/threshold/export/{serviceType} {serviceType} available value: "diam-gateway"	See Table A-1
Import Congestion Thresholds	POST	{apiRoot}/oc-cnpolicy-configuration/v1/threshold/import/{serviceType} {serviceType} available value: "diam-gateway"	See Table A-3

Note

/oc-cnpolicy-configuration/v1/threshold/diameter-gateway APIs will be deprecated and returns 400 for fresh installations starting with release 25.1.100. For releases prior to 25.1.100, these APIs will continue to work. If a deployment was originally installed on a release earlier than 25.1.100 and is later upgraded to 25.1.100 or a subsequent release, these APIs will continue to work until it is migrated. Once the migration is completed after the upgrade, these APIs will also be deprecated and return 400.

Get and Update Congestion Threshold

Table 2-371 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
stateCalculationInterval	integer	Mandatory	Specifies the interval at which congestion state is calculated.
stateChangeSampleCount	integer	Mandatory	Specifies the continuous sample counts for which calculated state remains the same.
thresholds	Threshold	Mandatory	An array to define threshold values for each resource for a given state,

Table 2-372 Request/Response Body Parameters for Thresholds

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
state	string	Optional	Specifies the congestion state. The state can be in either DANGER_OF_CONGESTION and CONGESTED.
resourceUsageLimit	ResourceUsageLimit	Mandatory	Specifies the resource usage limit for a defined state.

Table 2-373 Request/Response Body Parameters for ResourceUsageLimit

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
cpu	integer	Mandatory	Specifies the threshold value for CPU message. For DANGER_OF_CONGESTION (DOC) state, CPU default value: 60 For CONGESTED state, CPU default value: 80
memory	integer	Mandatory	Specifies the threshold value for memory message. Default Value: 60

Table 2-373 (Cont.) Request/Response Body Parameters for ResourceUsageLimit

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
queue	integer	Mandatory	Specifies the threshold value for number of messages in the queue. For DANGER_OF_CONGESTION (DOC) state, Queue count default value: 20 For CONGESTED state, Queue count default value: 50

Sample Request body for Congestion Threshold GET and PUT operation:

```
{
  "stateCalculationInterval": 100,
  "stateChangeSampleCount": 10,
  "thresholds": [
    {
      "state": "CONGESTED",
      "resourceUsageLimit": {
        "cpu": 80,
        "memory": 60,
        "queue": 50
      }
    },
    {
      "state": "DANGER_OF_CONGESTION",
      "resourceUsageLimit": {
        "cpu": 60,
        "memory": 60,
        "queue": 20
      }
    }
  ]
}
```

Import and Export Congestion Threshold

Table 2-374 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
date	string		Current timestamp
errors.message			The reason of the failure.

Table 2-374 (Cont.) Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
errors.name			Name of the components that failed to export or import.
exportData	array		Exported list of Congestion Threshold. For more information, see Get and Update Congestion Threshold .
key	string		Indicates the ID
sourceVersion	string		System version of product from which data is exported
topic	string		Topic of each managed object

Sample Request Body structure for Congestion Threshold Import and Export operations:

```
{
  "date": "string",
  "errors": [
    {
      "message": "string",
      "name": "string"
    }
  ],
  "exportData": {
    "stateCalculationInterval": 100,
    "stateChangeSampleCount": 10,
    "thresholds": [
      {
        "state": "CONGESTED",
        "resourceUsageLimit": {
          "cpu": 80,
          "memory": 80,
          "queue": 50
        }
      },
      {
        "state": "DANGER_OF_CONGESTION",
        "resourceUsageLimit": {
          "cpu": 60,
          "memory": 60,
          "queue": 30
        }
      }
    ]
  },
  "sourceVersion": "string",
```

```

    "topic": "string"
  }

```

2.72 Peer Node Sets

(Required) <Enter introductory text here, including the definition and purpose of the concept.>

Table 2-375 Supported REST APIs

Description	HTTP Method or Custom Operation	Resource URI	Possible Result Code
Create Peer Node Set	POST	{apiRoot}/oc-cnpolicy-configuration/v1/diameter/peernodesets	See Table A-3
Get Peer Node Set	GET	{apiRoot}/oc-cnpolicy-configuration/v1/diameter/peernodesets/{peerNodeSetName}	See Table A-1
Update Peer Node Set	PUT	{apiRoot}/oc-cnpolicy-configuration/v1/diameter/peernodesets/{peerNodeSetName}	See Table A-2
Delete Peer Node Set	DELETE	{apiRoot}/oc-cnpolicy-configuration/v1/diameter/peernodesets/{peerNodeSetName}	See Table A-4

Get, Create, and Update Peer Nodes

Table 2-376 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/Optional(O)/Conditional(C)	Description
description	String	O	Description of the Peer Node Set
name	String	O	Unique Name of the Peer Node Set.
realm	String	O	The realm name, that is, FQDNs to all of that computers that transact diameter traffic.
Primary Server	String	O	The primary server for a TDF client.
Secondary Server	String	O	The Secondary server for a TDF client.
Tertiary Server	String	O	The Tertiary server for a TDF client.
Quaternary Server	String	O	The Quaternary server for a TDF client.

Sample Request body structure for POST and PUT operations:

```

{
  "description": "string",

```

```

    "name": "string",
    "realm": "string",
    "refPeerNodePrimary": "string",
    "refPeerNodeQuaternary": "string",
    "refPeerNodeSecondary": "string",
    "refPeerNodeTertiary": "string",
    "type": "tdf"
  }

```

Sample Response body structure for GET, POST, and PUT operations:

```

{
  "description": "string",
  "name": "string",
  "realm": "string",
  "refPeerNodePrimary": "string",
  "refPeerNodeQuaternary": "string",
  "refPeerNodeSecondary": "string",
  "refPeerNodeTertiary": "string",
  "type": "tdf"
}

```

2.73 Peer Nodes

Table 2-377 Supported REST APIs

Description	HTTP Method or Custom Operation	Resource URI	Possible Result Code
Create Peer Node	POST	{apiRoot}/oc-cnpolicy-configuration/v1/diameter/peernodes	See Table A-3
Get All (Export) Peer Nodes	GET	{apiRoot}/oc-cnpolicy-configuration/v1/diameter/peernodes/export	See Table A-1
Import Peer Nodes	POST	{apiRoot}/oc-cnpolicy-configuration/v1/diameter/peernodes/import	See Table A-3
Get Peer Node	GET	{apiRoot}/oc-cnpolicy-configuration/v1/diameter/peernodes/{peernodeName}	See Table A-1
Update Peer Node	PUT	{apiRoot}/oc-cnpolicy-configuration/v1/diameter/peernodes/{peernodeName}	See Table A-2
Delete Peer Node	DELETE	{apiRoot}/oc-cnpolicy-configuration/v1/diameter/peernodes/{peernodeName}	See Table A-4

Get, Create, and Update Peer Nodes

Table 2-378 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/Optional(O)/Conditional(C)	Description
diamName	String	O	Unique Name of the Peer Node
dtype	String	O	Defines which type of Diameter Service it should take up. Possible values are: - af - tdf - dra - ocs
host	String	O	The host name. Enter a FQDN, ipv4 or ipv6 address available for establishing diameter transport connections to the peer node.
identity	String	O	An identity to define a node in a realm. Note: It is mandatory if Type is set to <i>TDF</i> .
initiateConnection	boolean	O	Set it to True to initiate a connection for this peer node. Default Value: FALSE
port	Number	O	The port number. Enter a number from 0 to 65535.
transport	String	O	Type of transport ways for configuring a peer. The values can be: - TCP - TLSv1.2 - TLSv1.3 - TLSv1.2_OR_TLSv1.3
realm	String	O	The realm name, that is, FQDNs to all of that computers that transact diameter traffic.
reconnectLimit	Number	O	The reconnect limit. This value must be configured as the Diameter peer configuration. Currently, all the Gateway pods reconnect for infinite time for the cloud native environment. Hence, this variable is of no use. This value can be kept as it is.

Sample Request body structure for POST and PUT operations:

```
{
  "diamName": "string",
  "dtype": "af",
  "host": "string",
  "identity": "string",
  "initiateConnection": true,
  "port": "3868",
  "realm": "string",
```

```
"reconnectLimit": "3"
}
```

Sample Response body structure for GET, POST, and PUT operations:

```
{
  "diamName": "string",
  "dtype": "af",
  "host": "string",
  "identity": "string",
  "initiateConnection": true,
  "port": "3868",
  "realm": "string",
  "reconnectLimit": "3"
}
```

Delete Peer Nodes

DELETE - delete peer node

Table 2-379 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
Peer Node Name	string	M	Peer Node Name

Export/Import Peer Nodes

Table 2-380 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
date	string		Current timestamp
exportData	array		Exported list of peer nodes. For more information, see Get, Create, and Update Peer Nodes .
key	string		Indicates the ID
sourceVersion	string		System version of product from which data is exported
topic	string		Topic of each managed object

Sample Request Body structure for Import/Export operations:

```
[
  {
    "date": "string",
    "errors": [
```

```

    {
      "message": "string",
      "name": "string"
    }
  ],
  "exportData": [
    {
      "diamName": "string",
      "dtype": "af",
      "host": "string",
      "identity": "string",
      "initiateConnection": true,
      "port": "3868",
      "realm": "string",
      "reconnectLimit": "3"
    }
  ],
  "key": "string",
  "sourceVersion": "string",
  "topic": "string"
}
]

```

2.74 Access and Mobility Service

Table 2-381 Supported REST APIs

Description	HTTP Method or Custom Operation	Resource URI	Possible Result Code
Get Access and Mobility Service	GET	{apiRoot}/oc-cnpolicy-configuration/v1/services/pcfam	See Table A-1
Update Access and Mobility Service	PUT	{apiRoot}/oc-cnpolicy-configuration/v1/services/pcfam	See Table A-2
Export Access and Mobility Management Service	GET	{apiRoot}/oc-cnpolicy-configuration/v1/services/pcfam/export	See Table A-1
Import Access and Mobility Service	POST	{apiRoot}/oc-cnpolicy-configuration/v1/services/pcfam/import	See Table A-3

Get and Update Access and Mobility Service

Table 2-382 Request/Response Body Parameters

Field Name	Data Type
System	SystemConfiguration
User	AmUserConfiguration
Policy	Policy
rules	RuleConfiguration
audit	AuditConfiguration

Table 2-382 (Cont.) Request/Response Body Parameters

Field Name	Data Type
pendingTransaction	PendingTransactionConfiguration
advancedSettings	AdvancedSettings

Table 2-383 System

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
amfNotificationRetryProfile	string	O	Specifies the retry profile configuration for Access and Mobility service.
amNfCommProfile	string	O	Specifies the NF communication profile used by AMF.
enableHttp2Client	boolean	O	Enables http2 client. Default Value: TRUE
isSubscribe	boolean	O	Indicates whether service is subscribed. Default Value: TRUE
isValidateUser	boolean	O	Determines if user validate is enabled. HTTP 400 with cause USER_UNKNOWN returns, if this is enabled and user not found in UDR. Default Value: FALSE
logList	AMServiceSystemConfigurationLogList	O	
rootLogLevel	string, ENUM	M	Indicates the log level of PCF Session Management (SM) service. Default Value: WARN
usePolicyService	boolean	O	If selected, uses the policy service. Component tracing is used to evaluate system process latency in detail level. Default Value: TRUE
useUserPolicy	boolean	O	If selected uses the user service. Default Value: TRUE
enableLimitingSessionByPerUser	boolean	O	Specifies whether to enable the Limiting the Number of Sessions functionality. Default value: false

Table 2-383 (Cont.) System

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
maxSessionLimitUser	integer	C	Enables to configure the maximum number of sessions to be limited by the user if Enable Max Session Limit flag is enabled. The value of this parameter ranges between 1 and 2. Default value: 1
overrideSupportedFeatures	string, Array	O	Indicates a list of supported features that can be configured to override system embedded values. For example: • PendingTransaction • DNNReplacementControl • SliceSupport
dataCompressionScheme	string, Array	O	Specifies the data compression scheme that can be used. The following values are supported: • Disabled • MySQL_Compressed • Application Compressed Default value: Disabled

Table 2-384 User Configuration

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
validateUser		O	Determines if user validate is enabled. HTTP 400 with cause USER_UNKNOWN returns, if this is enabled and user not found in UDR. Default Value: FALSE

Table 2-384 (Cont.) User Configuration

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
subscriberStateVariablesEnabled	Boolean	O	If this parameter is enabled, AM Service controls the querying and saving of local and remote subscriber state variables (SSV) on PDS. Default value: false.
amPolicyDataEnabled	Boolean	O	If this parameter is enabled, PCF fetches AMPolicyData from nUDR.
queryUserOnCreate	boolean	O	Determines if user query from UDR is enabled. When this option is enabled, PDS queries the UDR about the subscriber contained in the AM Association create request by sending a GET request for "am-policy-set" resource on the nudr-dr service. Default Value: true
subscribeToNotify	boolean	O	When Subscribe to Notify is enabled, Policy subscribes with the UDR to get notified on changes in subscriber profile. Default Value: false
queryUserOnUpdate	boolean	O	Determines if user query from UDR on update is enabled. When this option is enabled, PDS queries the UDR about the subscriber present in the AM Association update request by sending a GET request for "am-policy-set" resource on the nudr-dr service. Default Value: false

Table 2-384 (Cont.) User Configuration

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
queryUserOnTerminate	boolean	O	Determines if user query from UDR on delete is enabled. When this option is enabled, PCF queries the UDR about the subscriber present in the AM Association delete request by sending a GET request for "am-policy-set" resource on the nudr-dr service. Default Value: false
isChfQueryEnabled	Boolean	O	If this parameter is enabled, PCF fetches policy counters from CHF.
asyncChfQueryEnabled	Boolean	O	When this parameter is enabled, PCF interacts with CHF in Asynchronous mode.

Table 2-385 Policy

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
evaluate	Boolean	O	This parameter determines if policy evaluation is enabled on AM Policy Data. By default, this parameter is enabled.

Table 2-386 Rules

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
defaultRfsp	string	O	RFSP (Rat Frequency Selection Priority)
defaultServAreaResCfgl d	string	O	SAR (Service Area Restriction)

Table 2-386 (Cont.) Rules

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
defaultTriggers	ENUM	O	This parameter specifies the default triggers. The supported values are: • LOC_CH, that is, change in location • PRA_CH, that is, change of UE presence in PRA • ALLOWED_NSSAI_CH • SMF_SELECT_CH

Table 2-387 Audit Configuration

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
enable	Boolean	O	Determines whether to send registration request to Audit service or not. Default Value: True
queryAMF	Boolean		When this flag is set to true, audit service sends notification to AMF to check the presence of a stale session. If a stale session is present, AMF sends a 404 response to audit service. Then, audit service deletes the AM Policy association from the database. Default Value: False Note: When Minimum Audit Attempts is 1 and Query AMF is false, Audit service removes the AM session after the maxTTL expiry and the Minimum Audit Attempts remains 0 in Audit database.

Table 2-387 (Cont.) Audit Configuration

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
notificationRate	Integer		Defines the number of stale records which Audit service notifies to AM service in one second. Value of this parameter ranges between 20 and 700. Default and Recommended Value: 50 Note: To configure higher number than the recommended value, contact My Oracle Support (https://support.oracle.com)
ttl	Integer		Defines the age of an AM policy association after which a record is considered to be stale on PCF and the AMF is queried for presence of such associations. Value of this parameter ranges between 1 and 10080. Default Value: 1440
maxTtl	Integer		Defines the maximum age of an AM policy association after which a record is purged from PCF AMPolicyAssociation database. Value of this parameter ranges between 1 and 20160. Default Value: 2880

Table 2-387 (Cont.) Audit Configuration

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
minAuditAttempts	Integer		Specifies the minimum number of consecutive failed audit attempts until maxTTL / forceTTL is reached. If maxTTL is reached and audit_attempts >= Minimum Audit Attempts for maxTTL, Audit service sends notification to AM service with maxTTL flag set to true. AM Service sends DELETE request to PDS. Range: 0-255 Default Value: 0 Note: If maxTTL is not reached and if audit attempts are reached, the number of audit attempts are incremented until maxTTL is reached.
frequency	Integer		Defines the time when next audit for the AM service table begins after delta time if auditing this table has been finished before this specified time. Default Value: 330

Table 2-388 pendingTransaction

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
updateNotifyRetryBackoff			Defines the retry backoff for UpdateNotify in milliseconds. Default Value: 0 - 10000 milliseconds
updateNotifyRetryCount			Defines the total number of retries for UpdateNotify. Default Value: 0 - 5
errorUpdateNotifyHandlingApp			

Table 2-388 (Cont.) pendingTransaction

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
updateNotifyHandling			

Table 2-389 AdvancedSettings

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
Key	string	O	Specifies the key name.
Value	string	O	Specifies the value of the key.

For more information on the Advanced Settings Keys and Values, see *PCF Access and Mobility* section of *Configuring Policy Using CNC Console* chapter in *Oracle Communications Cloud Native Core, Converged Policy User Guide*.

Table 2-390 AMServiceSystemConfigurationLogList

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
level	ENUM	O	
name	string	M	

Sample Request body structure for POST and PUT operations:

```
{
  "system": {
    "amfNotificationRetryProfile": "string",
    "amNfCommProfile": "string",
    "enableLimitingSessionByPerUser": false,
    "maxSessionLimitUser": 1,
    "overrideSupportedFeatures": [
      "PendingTransaction"
    ],
    "dataCompressionScheme": "0"
  },
  "user": {
    "validateUser": true,
    "subscriberStateVariablesEnabled": true,
    "amPolicyDataEnabled": true,
    "queryUserOnCreate": true,
    "subscribeToNotify": true,
    "queryUserOnUpdate": true,
    "queryUserOnTerminate": true,
    "isChfQueryEnabled": true,
    "asyncChfQueryEnabled": true
  }
},
```

```

    "policy": {
      "evaluate": true
    },
    "rules": {
      "defaultServAreaResCfgId": "string",
      "defaultRfsp": 3,
      "defaultTriggers": [
        "LOC_CH"
      ]
    },
    "audit": {
      "enable": true,
      "queryAMF": true,
      "notificationRate": 50,
      "ttl": 1440,
      "maxTtl": 2880,
      "frequency": 330,
      "minAuditAttempts": 0
    },
    "pendingTransaction": {
      "updateNotifyRetryBackoff": 1000,
      "updateNotifyRetryCount": 2,
      "errorUpdateNotifyHandlingApp": "string",
      "updateNotifyHandling": "string"
    },
    "advancedSettings": [
      {
        "key": "z9juPMutruXy%t2#(q:zG^6iIky~u)~szTX& CMEok^uzF\\
{gTML..@V-:6&:w\"w5",
        "value": ""
      }
    ]
  }
}

```

Sample Response body structure for GET, POST, and PUT operations:

```

{
  "system": {
    "amfNotificationRetryProfile": "string",
    "amNfCommProfile": "string",
    "enableLimitingSessionByPerUser": false,
    "maxSessionLimitUser": 1,
    "overrideSupportedFeatures": [
      "PendingTransaction"
    ],
    "dataCompressionScheme": "2"
  },
  "user": {
    "validateUser": true,
    "subscriberStateVariablesEnabled": true,
    "amPolicyDataEnabled": true,
    "queryUserOnCreate": true,
    "subscribeToNotify": true,
    "queryUserOnUpdate": true,
    "queryUserOnTerminate": true,
  }
}

```



```

        "isChfQueryEnabled": true,
        "asyncChfQueryEnabled": true
    },
    "policy": {
        "evaluate": true
    },
    "rules": {
        "defaultServAreaResCfgId": "string",
        "defaultRfsp": 3,
        "defaultTriggers": [
            "LOC_CH"
        ]
    },
    "audit": {
        "enable": true,
        "queryAMF": true,
        "notificationRate": 50,
        "ttl": 1440,
        "maxTtl": 2880,
        "frequency": 330,
        "minAuditAttempts": 0
    },
    "pendingTransaction": {
        "updateNotifyRetryBackoff": 1000,
        "updateNotifyRetryCount": 2,
        "errorUpdateNotifyHandlingApp": "string",
        "updateNotifyHandling": "string"
    },
    "advancedSettings": [
        {
            "key": "T",
            "value": "M"
        }
    ]
}

```

Export/Import Access and Mobility Service

Table 2-391 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
date	string		Current timestamp
errors:message	string		
errors:name	string		
exportData	array		Exported list of access and mobility management service. For more information, see Get and Update Access and Mobility Service .

Table 2-391 (Cont.) Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
sourceVersion	string		System version of product from which data is exported
topic	string		Topic of each managed object

Sample Request Body structure for Import/Export operations:

```

{
  "topic": "string",
  "sourceVersion": "string",
  "date": "string",
  "exportData": {
    "system": {
      "amfNotificationRetryProfile": "string",
      "amNfCommProfile": "string",
      "enableLimitingSessionByPerUser": false,
      "maxSessionLimitUser": 1,
      "overrideSupportedFeatures": [
        "PendingTransaction"
      ],
      "dataCompressionScheme": "0"
    },
    "user": {
      "validateUser": true,
      "subscriberStateVariablesEnabled": true,
      "amPolicyDataEnabled": true,
      "queryUserOnCreate": true,
      "subscribeToNotify": true,
      "queryUserOnUpdate": true,
      "queryUserOnTerminate": true,
      "isChfQueryEnabled": true,
      "asyncChfQueryEnabled": true
    },
    "policy": {
      "evaluate": true
    },
    "rules": {
      "defaultServAreaResCfgId": "string",
      "defaultRfsp": 3,
      "defaultTriggers": [
        "LOC_CH"
      ]
    },
    "audit": {
      "enable": true,
      "queryAMF": true,
      "notificationRate": 50,
      "ttl": 1440,

```

```

        "maxTtl": 2880,
        "frequency": 330,
        "minAuditAttempts": 0
    },
    "pendingTransaction": {
        "updateNotifyRetryBackoff": 1000,
        "updateNotifyRetryCount": 2,
        "errorUpdateNotifyHandlingApp": "string",
        "updateNotifyHandling": "string"
    },
    "advancedSettings": [
        {
            "key": "|",
            "value": ">"
        }
    ]
},
"errors": [
    {
        "name": "string",
        "message": "string"
    }
]
}

```

2.75 Policy Authorization Service

Table 2-392 Supported REST APIs

Description	HTTP Method or Custom Operation	{apiRoot}/oc-cnpolicy-configuration/v1/services/pcfpa	Possible Result Code
Get Policy Authorization Service	GET	{apiRoot}/oc-cnpolicy-configuration/v1/services/pcfpa	See Table A-1
Update Policy Authorization Service	PUT	{apiRoot}/oc-cnpolicy-configuration/v1/services/pcfpa	See Table A-2
Export All Policy Authorization Service	GET	{apiRoot}/oc-cnpolicy-configuration/v1/services/pcfpa/export	See Table A-1
Import Policy Authorization Service	POST	{apiRoot}/oc-cnpolicy-configuration/v1/services/pcfpa/import	See Table A-3

Get and Update Policy Authorization Service

Table 2-393 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
imsEmergencySession	IMSEmergencySessionPAServiceConfiguration	O	
system	System Configuration	O	

Table 2-394 IMSEmergencySessionPAServiceConfiguration

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
emergencyServiceURNs	string Any number of values are permitted for Emergency Service URNs	O	Specifies the Uniform Resource Name (URN) values for emergency and other well-known services.
reservationPriorityTypes	ENUM	O	Specifies the IMS Signalling Priority.

Table 2-395 System Configuration

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
afDirectReply	Boolean	O	Specifies, if reply must be sent to AF before the PCF that sends the policy decision to SMF, after successful session binding.
afNotificationsRetryProfile	string		Specifies the retry profile configuration for Policy Authorization.
afSubsNotifySegment	string example: termination	O	Specifies AF subscription notify uri segment appended to AF subs notify uri. For example, {NotificationUri}/notify. "notify" is the subscription notify uri segment.

Table 2-395 (Cont.) System Configuration

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
afTerminateUriSegment	string example: termination	O	Specifies AF notify to terminate uri segment appended to AF notify uri. For example, {NotificationUri}/termination. "termination" is the terminate uri segment.
overrideSupportedFeatures	string	O	Defines the supported features that can be configured to override system embedded values. Represent a string separated by comma. For example, - InfluenceOnTrafficRouting - SponsoredConnectivity - QoSMonitoring - EnhancedSubscriptionToNotification The "" means an empty supported feature set.
paNfCommProfile	string	O	Specifies the NF communication profile used by AF.
dataCompressionScheme	string	O	Specifies the data compression scheme that can be used. The following values are supported: - Disabled - MySQL_Compressed - Application Compressed Default value: Disabled
authorizationLifetime	Long	O	If included implies authorization lifetime feature is to be negotiated, includes a value higher than 0 specifying Authorization Lifetime AVP. Default Value: null

Table 2-395 (Cont.) System Configuration

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
reportPartialFailedEvent	string	O	After PCF triggers a notification to Diameter Connector, the connector generates a RAR message. The partial failed specific action in the RAR message depends on the priority of the action subscribed in the AAR message. The priority of the actions is INDICATION_OF_FAILURE_RESOURCES_ALLOCATION > INDICATION_OF_RELEASE_OF_BEARER > INDICATION_OF_LOSS_OF_BEARER. If you want to assign the action not depend on the priority, you can assign the action in this field. The default configuration is empty, you can choose one action from the following options. Once the value is defined in this field, the connector uses the configured action not depend on the priority. The valid options are: • INDICATION_OF_FAILURE_RESOURCES_ALLOCATION • INDICATION_OF_RELEASE_OF_BEARER • INDICATION_OF_LOSS_OF_BEARER

Table 2-396 QoS Monitoring Configuration

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
acceptOnMissingQosAttributes	Boolean	O	Indicates whether to accept or reject any PA Create request with QOS_MONITORING event. Possible values: • false: Rejects any PA Create request with QOS_MONITORING event that misses any mandatory value required to subscribe to such event. • true: Accepts any request with QOS_MONITORING event, irrespective of whether all the mandatory values required to subscribe were provided or not. This allows to derive the missing values via Policy Evaluation. Default value: false

Table 2-396 (Cont.) QoS Monitoring Configuration

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
acceptOnQosMonNotSupported	string		Indicates whether to accept or reject any PA Create request with QOS_MONITORING event that is not supported or not negotiated. Possible values: • false: Rejects any PA Create request with QOS_MONITORING event, which did not negotiate QosMonitoring feature based on one of the following: – QosMonitoring feature is not negotiated by SMF during SM operations (not passed in suppFeat attribute or not present in Override supported features configuration for PCF Session Management service. – QosMonitoring feature is not added as supported in Override supported features configuration for PCF Policy Authorization service. • true: Accepts any PA Create request with QOS_MONITORING event but ignores the event and its related data if the feature was not negotiated based

Table 2-396 (Cont.) QoS Monitoring Configuration

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
			on the same conditions mentioned above. Default value: true

Sample Request body structure for PUT operations:

```
{
  "imsEmergencySession": {
    "emergencyServiceURNs": [
      "string"
    ],
    "reservationPriorityTypes": [
      "PRIO_1"
    ]
  },
  "system": {
    "afDirectReply": true,
    "overrideSupportedFeatures": "string",
    "afTerminateUriSegment": "terminate",
    "afSubsNotifySegment": "notify",
    "afNotificationsRetryProfile": "string",
    "paNfCommProfile": "string",
    "dataCompressionScheme": "string",
    "authLifetime": true,
    "reportPartialFailedEvent": "INDICATION_OF_LOSS_OF_BEARER"
  },
  "qosMonitoring": {
    "acceptOnMissingQosAttributes": false,
    "acceptOnQosMonNotSupported": true
  },
}
```

Sample Response body structure for GET, POST, and PUT operations:

```
{
  "imsEmergencySession": {
    "emergencyServiceURNs": [
      "string"
    ],
    "reservationPriorityTypes": [
      "PRIO_1"
    ]
  },
  "system": {
    "afDirectReply": true,
    "overrideSupportedFeatures": "string",
    "afTerminateUriSegment": "terminate",

```

```

    "afSubsNotifySegment": "notify",
    "afNotificationsRetryProfile": "string",
    "paNfCommProfile": "string",
    "dataCompressionScheme": "string",
    "authLifetime": true,
    "reportPartialFailedEvent": "INDICATION_OF_LOSS_OF_BEARER"
  },
  "qosMonitoring": {
    "acceptOnMissingQosAttributes": false,
    "acceptOnQosMonNotSupported": true
  },
}

```

Export/Import Policy Authorization Service

Table 2-397 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
date	string		Current timestamp
exportData	array		Exported list of policy authorization service. For more information, see Get and Update Policy Authorization Service .
sourceVersion	string		System version of product from which data is exported
topic	string		Topic of each managed object

Sample Request Body structure for Import/Export operations:

```

{
  "date": "string",
  "errors": [
    {
      "message": "string",
      "name": "string"
    }
  ],
  "exportData": {
    "imsEmergencySession": {
      "emergencyServiceURNs": [
        "string"
      ],
      "reservationPriorityTypes": [
        "PRIO_1"
      ]
    },
    "system": {
      "afDirectReply": true,
      "afNotificationsRetryProfile": "string",

```

```

    "afSubsNotifySegment": "notify",
    "afTerminateUriSegment": "terminate",
    "overrideSupportedFeatures": "string",
    "paNfCommProfile": "string",
    "reportPartialFailedEvent": "INDICATION_OF_FAILED_RESOURCES_ALLOCATION"
  }
},
"sourceVersion": "string",
"topic": "string"
}

```

Audit Authorization Service

Table 2-398 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
enable	Boolean	O	Specifies whether to enable or disable the stale Rx session audit and deletion. When this parameters is enabled, SM Service registers with Audit service for monitoring Rx sessions. Default Value: false
ttl	integer	O	Specifies the Time To Live (TTL) of Rx sessions. Range: 0-21600 Default Value: 1440
maxTtl	integer	O	Specifies the maximum Time To Live (TTL) of Rx sessions. Default Value: 4320 Range: 0-21600
notificationRate	integer	O	Maximum amount of app session cleanup requests per second. Default Value: 50
frequency	integer	O	Specifies how long the Audit Service waits for next audit cycle. Default Value: 10

Table 2-398 (Cont.) Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
nullAsStale	Boolean	O	If EXPIRY_TIMESTAMP or SITEID contains NULL value, (legacy stale records after upgrade) they will be considered in the next audit cycle as TTL expired. Default Value: false

Sample Request Body structure for GET/PUT operations:

```
{
  "system": {
    "afDirectReply": true,
    "overrideSupportedFeatures": "string",
    "afTerminateUriSegment": "terminate",
    "afSubsNotifySegment": "notify",
    "afNotificationsRetryProfile": "string",
    "paNfCommProfile": "string",
    "dataCompressionScheme": "string",
    "authLifetime": true,
    "reportPartialFailedEvent": "INDICATION_OF_LOSS_OF_BEARER"
  },
  "imsEmergencySession": {
    "Any number of values are permitted for Emergency Service URNs": [
      "string"
    ],
    "reservationPriorityTypes": [
      "PRIO_1"
    ]
  },
  "nwdaf": {
    "enableNwdafData": true
  },
  "audit": {
    "enable": true,
    "ttl": 1440,
    "maxTtl": 4320,
    "notificationRate": 50,
    "frequency": 10,
    "nullAsStale": true
  },
  "advancedSettings": [
    {
      "key": "string",
      "value": "string"
    }
  ]
}
```

```

}
}

```

2.76 UE Policy

Table 2-399 Supported REST APIs

Description	HTTP Method or Custom Operation	Resource URI	Possible Result Code
Get UE Policy Service	GET	{apiRoot}/oc-cnpolicy-configuration/v1/services/pcfue	See Table A-1
Update UE Policy Service	PUT	{apiRoot}/oc-cnpolicy-configuration/v1/services/pcfue	See Table A-2
Export All UE Policy Service	GET	{apiRoot}/oc-cnpolicy-configuration/v1/services/pcfue/export	See Table A-1
Import UE Policy Service	POST	{apiRoot}/oc-cnpolicy-configuration/v1/services/pcfue/import	See Table A-3

Get and Update UE Policy

Table 2-400 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)aints	Description
amf	AMFConfiguration	O	
system	UEPolicyServiceSystemConfiguration	O	
user	UserUEPolicyServiceConfiguration	O	
homePLMN	HomePLMNConfiguration	O	
rule	rule	O	
n1MsgTransferSettings	N1MessageTransferSettingsConfiguration	O	
timerSettings	TimerSettingsConfiguration	O	
n1MsgRetransmissionSettings	N1MessageRetransmissionSettingsConfiguration	O	
audit	AuditConfiguration	O	

Table 2-401 AMFConfiguration

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
enableHttp11Client	boolean	O	
naSMsgTransferMaxSize	integer (\$int32)	O	Enter a range in [0-65535] number
amf.ueAMFCommProfile	string	O	Specifies the NF communication profile used by AMF.
amf.ueNASCommProfile	string	O	Specifies the NF communication profile used by NAS.
amf.ueAMFRetryProfileNotification	string	O	
amf.ueNASRetryProfileInitial	string	O	
amf.ueNASRetryProfileSubs	string	O	
amf.ueAMFDiscoveryCriteria	string	O	
amf.sendSbiBhForN1N2TransferReq	String	O	Indicates when to send the SBI binding header for N1N2Transfer request. The options can be: • When binding information changes: Sends the binding header in the HTTP request only whenever there is a change in the binding information. • Always: Sends the binding header in all the N1N2Transfer requests. • Never: Never includes the binding header in any N1N2Transfer request. Default value: When binding information changes Note: This configuration will override the values being set towards NF Communication Profile under NAS (The NF Communication Profile for NAS is mandatory to be set in UE service configuration).

Table 2-401 (Cont.) AMFConfiguration

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
amf.sendRoutingBhForN1N2TransferReq	String	O	Indicates when to send the routing binding header for N1N2Transfer request. The options can be: • Always: Sends the routing binding header in all the N1N2Transfer requests. • Never: Never sends the routing binding header in any N1N2Transfer request. Default value: There is no default value configured for this field. Note: • This configuration will override the values being set towards NF Communication Profile under NAS (The NF Communication Profile for NAS is mandatory to be set in UE service configuration). • To rollback the value of the parameter from "ALWAYS"/"NEVER" to default value, click Please Select.

Table 2-401 (Cont.) AMFConfiguration

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
amf.sendDiscHeaderFor N1N2TransferReq	String	O	Indicates whether to send the discovery header for N1N2Transfer request when the routing binding information is not present. The options can be: - Always: Sends the discovery header in all the N1N2Transfer requests when the routing binding header is not included. - Never: Never sends the discovery header in any N1N2Transfer request. Default value: There is no default value configured for this field. Note: - This configuration will override the values being set towards NF Communication Profile under NAS (The NF Communication Profile for NAS is mandatory to be set in UE service configuration). - To rollback the value of the parameter from "ALWAYS"/"NEVER" to default value, click Please Select.
amf.enableConsolidation	Boolean	O	Specifies whether to enable consolidation of policy decisions for a UE. When enabled, multiple sequenced policy decisions are consolidated as part of the next UE Policy Management Procedure. Default value: False

Table 2-401 (Cont.) AMFConfiguration

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
amf.amfResubscriptionCondition	String	O	Possible values are: - DISABLED - AMF Set ID and AMF Region ID - AMF Set ID - GUAMI If the value of this field is configured to any of the below mentioned values other than DISABLED, when the set ID is different in the UE Update received from AMF, PCF sends unsubscribe to old AMF and subscribes to new AMF. Default value: DISABLED

Table 2-402 UEPolicyServiceSystemConfiguration

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
loglevel	String, ENUM	O	Indicates the log level of PCF Session Management (SM) service. Default Value: WARN
notifUriRoot	string	O	
enableLimitingSessionByPerUser	boolean	O	Specifies whether to enable the Limiting the Number of Sessions functionality. Default value: false
maxSessionLimitUser	integer	C	Enables to configure the maximum number of sessions to be limited by the user if Enable Max Session Limit flag is enabled. The value of this parameter ranges between 1 and 2. Default value: 1

Table 2-403 UserUEPolicyServiceConfiguration

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
asyncChfQueryEnabled	Boolean	O	When this button is enabled, PCF interacts with CHF in Asynchronous mode.
chfQueryEnabled	Boolean	O	If this switch is enabled, PCF fetches policy counters from CHF.
isChfQueryEnabled	Boolean	O	If this switch is enabled, PCF fetches policy counters from CHF.
queryUser	boolean	O	Determines if user query from UDR is enabled. Default Value: TRUE
validateUser	boolean	O	Determines if user validate is enabled. HTTP 400 with cause USER_UNKNOWN returns, if this is enabled and user not found in UDR. Default Value: FALSE
queryUserOnCreate	boolean	O	Determines if user query from UDR is enabled. When this option is enabled, PDS queries the UDR about the subscriber contained in the UE Association create request by sending a GET request for "ue-policy-set" resource on the nudr-dr service. Default Value: true
subscribeToNotify	boolean	O	When Subscribe to Notify is enabled, Policy subscribes with the UDR to get notified on changes in subscriber profile. Default Value: true

Table 2-403 (Cont.) UserUEPolicyServiceConfiguration

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
queryUserOnUpdate	boolean	O	Determines if user query from UDR on update is enabled. When this option is enabled, PDS queries the UDR about the subscriber present in the UE Association update request by sending a GET request for "ue-policy-set" resource on the nudr-dr service. Default Value: false
queryUserOnTerminate	boolean	O	Determines if user query from UDR on delete is enabled. When this option is enabled, PCF queries the UDR about the subscriber present in the UE Association delete request by sending a GET request for "ue-policy-set" resource on the nudr-dr service. Default Value: false
uePolicyDataEnabled	Boolean	O	If this switch is enabled, PCF fetches UEPolicyData from nUDR.

Table 2-404 HomePLMNConfiguration

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
mcc	Number	O	The Mobile Country Code and Mobile Network Code of the Home PLMN. Default Value: NA
mnc	Number	O	The Mobile Country Code and Mobile Network Code of the Home PLMN. Default Value: NA

Table 2-405 rule

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
conflictResolutionStrategy	String	O	A new functionality "Conflict Resolution Strategy" is added and the values are: • Install • Remove • Drop

Table 2-406 N1MessageTransferSettings

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
n1MsgMaxSize	Number	O	Maximum number of URSP Rules to be encoded in a single UE Policy Section (UPSI) container. Default Value: 2000
uePolicySectionMaxSize	Number	O	The maximum size in bytes of a "MANAGE UE POLICY COMMAND" after encoding to send out to AMF for delivery to UE. Default Value: 2000
maxNoOfURSPRules	Number	O	Maximum number of URSP Rules to be encoded in a single UE Policy Section (UPSI) container. Default Value: 4

Table 2-406 (Cont.) N1MessageTransferSettings

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
upscStart	Number	O	This fields indicate the range of UPSC allocation by PCF and can be used to maintain a dedicated range of UPSCs used by PCF generated UPSIs. Configuring these fields avoids the conflict of UPSCs between the UE built-in UPSC and the PCF delivered UPSC. Note: If the UPSI based policy action is also used for non-fragmented URSP delivery, then the range of UPSCs used by that method should be outside the range configured here. Default Value: Start: 0
upscEnd	Number	O	This fields indicate the range of UPSC allocation by PCF and can be used to maintain a dedicated range of UPSCs used by PCF generated UPSIs. Configuring these fields avoids the conflict of UPSCs between the UE built-in UPSC and the PCF delivered UPSC. Note: If the UPSI based policy action is also used for non-fragmented URSP delivery, then the range of UPSCs used by that method should be outside the range configured here. Default Value: End: 65535

Table 2-407 TimerSettings

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
T 3501 Timer Duration	Number	O	If it's value is zero, T 3501 Timer handling functionality will be disabled. If a non-zero value is configured, then the timer will be initiated after every N1 transfer received successfully from AMF from the N1 Notify. Default Value: 5000
backOffTimerDuration	Number	O	The action to be taken by PCF when the AMF notifies the PCF that it could not deliver the "MANAGE UE POLICY COMMAND" message to UE. Default Value: 15000

Table 2-408 N1MessageRetransmissionSettings

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
On T 3501 Timer Expiry	Enumeration	O	The action to be taken by PCF when N1 notification is not received within configured duration defined in T 3501 Timer Duration. Default Value: Abort N1 Delivery

Table 2-408 (Cont.) N1MessageRetransmissionSettings

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
onTransactionFailureNotification	Number	O	The action to be taken by PCF when the AMF notifies the PCF that it could not deliver the "MANAGE UE POLICY COMMAND" message to UE. Default Value: Abort The value for the Skip Fragment label must be "SKIP". The value for the Re-Transmit N1 Message label must be "RETRANSMIT". The value for the Abort N1 Delivery label must be "ABORT".
onUEPolicyCommandReject	Enumeration	O	The action to be taken by PCF when the UE notifies the PCF that it could not process the "MANAGE UE POLICY COMMAND" message. Default Value: Abort The value for the Skip Fragment label must be "SKIP". The value for the Re-Transmit N1 Message label must be "RETRANSMIT". The value for the Abort N1 Delivery label must be "ABORT".

Table 2-408 (Cont.) N1MessageRetransmissionSettings

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
maxNoOfRetransmissions	Enumeration	O	Maximum number of re-transmissions to be attempted (excluding the initial attempt) after which UE service shall not try further to re-send the same fragment to AMF Default Value: 2 The value of the drop down items are as follows: • Re-Transmit N1 Message-RETRANSMIT • Skip Fragment-SKIP • Abort N1 Delivery-ABORT
reTransmissionFailureBehavior	Enumeration	O	The behavior of PCF UE service if the N1 message is not delivered to the UE after a maximum number of re-transmissions have been tried. Default Value: Abort The value for the Skip Fragment label must be "SKIP". The value for the Abort N1 Delivery label must be "ABORT".
allowT3501RetransmissionConsolidation	Boolean	O	Specifies whether to enable consolidation of UE policy decisions for re-transmission on T3501 expiration. When disabled, no consolidation is performed and sequenced policy decisions are processed after the current UE policy management procedure or re-transmission completes. Default value: False

Table 2-409 AuditConfiguration

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
enable	boolean	O	If this flag is enabled, UE service registers with Audit service for auditing the records in UEPolicyAssociation table. Once the registration is successful, a record for UE service is created in the AuditRegistration table. Default Value: False
query AMF	boolean	O	If this flag is enabled, the UE service sends the stale session notification received from Audit service to AMF to check if the session is present in AMF. Default Value: False
notificationRate	integer	M	Defines the maximum number of stale records, which Audit Service notifies to UE service in one second. Value of this parameter ranges between 20 and 700. Default Value: 50
ttl	integer	M	Defines the age of the UE Policy Association, after which a record is considered to be stale on PCF and the AMF is queried (if query AMF is set to TRUE) for presence of such associations. Value of this parameter ranges between 1 and 10080. Default Value: 1440

Table 2-409 (Cont.) AuditConfiguration

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
maxTtl	integer	M	Defines the maximum age of a UE Policy Association, after which a record is considered as stale and is purged from PCF UE database without sending further queries to AMF. Value of this parameter ranges between 1 and 20160. Default Value: 2880
frequency	integer	M	Defines the time when next audit for the UE service table is done after delta time if auditing this table has been finished before this specified time. Value of this parameter ranges between 1 and 1440. Default Value: 10

Sample Request body structure for PUT operations:

```
{
  "amf": {
    "ueAMFCommProfile": "string",
    "ueAMFRetryProfileNotification": "string",
    "ueNASCommProfile": "string",
    "ueNASRetryProfileInitial": "string",
    "ueNASRetryProfileSubs": "string"
    "amfResubscriptionCondition": "amfSetIdAndRegionId"
  },
  "audit": {
    "enable": true,
    "frequency": 5,
    "maxTtl": 2880,
    "notificationRate": 50,
    "queryAMF": true,
    "ttl": 1440
  },
  "homePLMN": {
    "mcc": 0,
    "mnc": 0
  },
  "rule": "INSTALL, REMOVE OR DROP",
  "n1MsgRetransmissionSettings": {
    "maxNoOfRetransmissions": 2,

```

```

    "onT3501TimerExpiry": "ABORT",
    "onTransactionFailureNotification": "ABORT",
    "onUEPolicyCommandReject": "ABORT",
    "reTransmissionFailureBehavior": "ABORT"
  },
  "n1MsgTransferSettings": {
    "maxNoOfURSPRules": 4,
    "n1MsgMaxSize": 2000,
    "uePolicySectionMaxSize": 2000,
    "upscEnd": 65535,
    "upscStart": 0
  },
  "system": {
    "enableLimitingSessionByPerUser": true,
    "maxSessionLimitUser": 1,
    "notifUriRoot": "string"
  },
  "timerSettings": {
    "backOffTimerDuration": 15000,
    "t3501TimerDuration": 5000
  },
  "user": {
    "asyncChfQueryEnabled": true,
    "chfQueryEnabled": true,
    "isChfQueryEnabled": true,
    "queryUserOnCreate": true,
    "queryUserOnTerminate": true,
    "queryUserOnUpdate": true,
    "subscribeToNotify": true,
    "uePolicyDataEnabled": true,
    "validateUser": true
  }
}

```

Sample Response body structure for GET and PUT operations:

```

{
  "system": {
    "enableLimitingSessionByPerUser": true,
    "maxSessionLimitUser": 1
  },
  "user": {
    "validateUser": false,
    "queryUserOnCreate": false,
    "subscribeToNotify": false,
    "queryUserOnUpdate": false,
    "queryUserOnTerminate": false
  },
  "homePLMN": {
    "mcc": "0",
    "mnc": "0"
  },
  "rule": "INSTALL, REMOVE OR DROP",
  "n1MsgTransferSettings": {
    "n1MsgMaxSize": 2000,

```

```

        "uePolicySectionMaxSize": 2000,
        "maxNoOfURSPRules": 4,
        "upscStart": 0,
        "upscEnd": 65535
    },
    "timerSettings": {
        "backOffTimerDuration": 15000
        "t3501TimerDuration": 5000
    },
    "n1MsgRetransmissionSettings": {
        "onTransactionFailureNotification": "ABORT",
        "onT3501TimerExpiry": "ABORT",
        "onUEPolicyCommandReject": "ABORT",
        "maxNoOfRetransmissions": 2,
        "reTransmissionFailureBehavior": "ABORT"
    },
    "audit": {
        "enable": false,
        "queryAMF": false,
        "notificationRate": 50,
        "ttl": 1440,
        "maxTtl": 2880,
        "frequency": 10
    }
}

```

Export/Import UE Policy

Table 2-410 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
date	string		Current timestamp
exportData	array		Exported list of UE policy service. For more information, see Get and Update UE Policy
sourceVersion	string		System version of product from which data is exported
topic	string		Topic of each managed object

Sample Request Body structure for Import/Export operations:

```

{
  "amf": {
    "ueAMFCommProfile": "string",
    "ueAMFRetryProfileNotification": "string",
    "ueNASCommProfile": "string",
    "ueNASRetryProfileInitial": "string",
    "ueNASRetryProfileSubs": "string"
    "amfResubscriptionCondition": "string"
  }
}

```

```

    },
    "audit": {
      "enable": true,
      "frequency": 5,
      "maxTtl": 2880,
      "notificationRate": 50,
      "queryAMF": true,
      "ttl": 1440
    },
    "homePLMN": {
      "mcc": 0,
      "mnc": 0
    },
    "rule": "INSTALL, REMOVE OR DROP",
    "n1MsgRetransmissionSettings": {
      "maxNoOfRetransmissions": 2,
      "onT3501TimerExpiry": "ABORT",
      "onTransactionFailureNotification": "ABORT",
      "onUEPolicyCommandReject": "ABORT",
      "reTransmissionFailureBehavior": "ABORT"
    },
    "n1MsgTransferSettings": {
      "maxNoOfURSPRules": 4,
      "n1MsgMaxSize": 2000,
      "uePolicySectionMaxSize": 2000,
      "upscEnd": 65535,
      "upscStart": 0
    },
    "system": {
      "enableLimitingSessionByPerUser": true,
      "maxSessionLimitUser": 1,
      "notifUriRoot": "string"
    },
    "timerSettings": {
      "backOffTimerDuration": 15000,
      "t3501TimerDuration": 5000
    },
    "user": {
      "asyncChfQueryEnabled": true,
      "chfQueryEnabled": true,
      "isChfQueryEnabled": true,
      "queryUserOnCreate": true,
      "queryUserOnTerminate": true,
      "queryUserOnUpdate": true,
      "subscribeToNotify": true,
      "uePolicyDataEnabled": true,
      "validateUser": true
    }
  }
}

```

2.77 PCRF Core Service

Table 2-411 Supported REST APIs

Description	HTTP Method or Custom Operation	Resource URI	Possible Result Code
Get PCRF Core Service	GET	{apiRoot}/oc-cnpolicy-configuration/v1/services/pcrfcore/settings	See Table A-1
Update PCRF Core Service	PUT	{apiRoot}/oc-cnpolicy-configuration/v1/services/pcrfcore/settings	See Table A-2
Export PCRF Core Service	GET	{apiRoot}/oc-cnpolicy-configuration/v1/services/pcrfcore/settings/export	See Table A-1
Import PCRF Core Service	POST	{apiRoot}/oc-cnpolicy-configuration/v1/services/pcrfcore/settings/import	See Table A-3

Get and Update Core Service

Table 2-412 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
advancedSettings	AdvanceSettingsConfiguration	O	
user	UserConfiguration	O	
mcptt	MCPTTConfiguration	O	
audit	AuditConfiguration	O	
usageMonService	UsageMonServiceConfiguration	O	
pendingTransaction	pendingTransactionConfiguration	O	

Table 2-413 AdvancedSettings

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
key	string	O	
value	string	O	

For more information on the Advanced Settings "Keys" and "Values", see PCRF Core Service Configurations "**Settings**" section of "Configuring Policy Using CNC Console" in *Oracle Communications Cloud Native Core, Converged Policy User Guide*.

Table 2-414 UserConfiguration

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
enableSubscriberVariables	boolean	O	If this switch is enabled, PCRF Core controls the querying and saving of remote subscriber state variables (SSV) on PDS. When CCR message is received by PCRF Core, then it queries PDS to fetch SSV for the user, instead of retrieving it locally. By default, the switch remains disabled.
ldapData.enable	boolean	O	If this is true, PCRF-Core fetches user profile from LDAP through PDS.
ocsSpendingLimit.enable	boolean	O	If this is true, PCRF-Core fetches user profile from 4G OCS.
ocsSpendingLimit.asyncQuery	boolean	O	When this switch is enabled, PCRF Core performs on-demand lookup of Policy Counters for a subscriber.
ocsSpendingLimit.forceLookup	boolean	O	When this switch is enabled, PCRF Core forces OCS lookup for Policy counters for a subscriber.
smPolicyData.enable	boolean	O	If this value is true, PCRF-Core fetches SMPolicyData from nUDR.
smPolicyData.queryOnDelete	boolean	O	Determines if user query from UDR on delete is enabled. When this option is true, PCRF Core queries the UDR about the subscriber present in the SM Association delete request by sending a GET request for "SmPolicyData" resource on the nudr-dr service.
smPolicyData.queryOnReauth	boolean	O	Determines if user query from UDR on reauth is enabled. When this option is true, PCRF Core queries the UDR about the subscriber, when it receives a Reauthorization request, such as Rx or Policy Authorization request by sending a GET request for "SmPolicyData" resource on the nudr-dr service.

Table 2-414 (Cont.) UserConfiguration

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
smPolicyData.queryOnUpdate	boolean	O	Determines if user query from UDR on update is enabled. When this value is true, PCRF Core queries the UDR about the subscriber present in the SM Association update request by sending a GET request for “SmPolicyData” resource on the nudr-dr service. Note: The PDS caches the subscriber profile when the “Subscribe To Notify” option is enabled, in that case, the PCRF core may not always reach the UDR when the subscriber profile is found in the local cache.
smPolicyData.subscribeToNotify	boolean	O	When this value is true, the PCRF Core subscribes with UDR to get notified for any changes in subscriber profile.
validateUser	boolean	O	If the User profile, for any of the User Data types given under the User Data Types group, is fetched successfully, the user is considered to be a known user. However, if the user profile lookup has failed on all the configured data sources, the user profile is marked as Unknown. If this value is true and user is marked as Unknown, the session creation requests are rejected. If this value is false and user is marked as Unknown, the session creation requests are handled and sessions are created successfully.
smPolicyData.autoEnrollment	boolean	O	To specify whether to enable or disable the autoprovisioning of the subscriber profile at UDR when the subscriber profile is not available.
smPolicyData.default.snsai	string	O	To configure a default S-NSSAI, which will be used when a subscriber is auto-enrolled on the UDR. This parameter is applicable only when Auto-Enrollment on UDR is set to true. The value configured here must match the Default S-NSSAI configured on UDR.
operatorSpecificData.enable	boolean	O	If this switch is enabled, PCRF fetches OperatorSpecificData (imported using Custom Schema) from nUDR.
operatorSpecificData.subscribeToNotify	boolean	O	When this switch is enabled, PCRF Core subscribes to get notified of any changes in the profile. Default Value: true

Table 2-415 MCPTT

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
mcptt.defaultBearerARP			
mcptt.defaultBearerARP.arpPriorityLevel	integer	O	Indicates the priority level. It ranges between 1-15. Default Value: 1
mcptt.defaultBearerARP.arpPreemptCap	Array	O	Indicates if the preemption capability is enabled or disabled. It can take the following values: - PREEMPTION_CAPABILITY_ENABLED - PREEMPTION_CAPABILITY_DISABLED Default Value: PREEMPTION_CAPABILITY_ENABLED
mcptt.defaultBearerARP.arpPreemptVuln	Array	O	Indicates if the preemption vulnerability is enabled or disabled. It can take the following values: - PREEMPTION_VULNERABILITY_ENABLED - PREEMPTION_VULNERABILITY_DISABLED Default Value: PREEMPTION_VULNERABILITY_DISABLED
mcptt.defaultPreemptionControl			
mcptt.defaultPreemptionControl.defaultPreemptControlInfo	Array	O	Includes the Default Preemption Control information: - LEAST_RECENT_ADDED_FLOW - MOST_RECENT_ADDED_FLOW - HIGHEST_BANDWIDTH_FLOW Default Value: LEAST_RECENT_ADDED_FLOW

Table 2-416 AuditConfiguration

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
audit.enable	boolean	M	Determines whether to send registration request to Audit service or not. By default, this switch is enabled.
audit.frequency	integer		Defines the frequency by which Audit service notifies to PCRF Core service in one second.

Table 2-416 (Cont.) AuditConfiguration

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
audit.gxSessionMaxTtl	integer		Defines the maximum age of a Gx session after which a record is purged from PCRF Core database (Gx Session table) without sending further queries to PGW.
audit.gxSessionTtl	integer		Defines the age of a Gx session after which a record is considered to be stale on PCRF Core and the PGW is queried for presence of such associations.
audit.notificationRate	integer		Defines the number of stale records which Audit service notifies to PCRF Core service in one second. Default Value: 50
audit.rxSessionMaxTtl	integer		Defines the maximum age of an Rx session after which a record is purged from PCRF Core database (Rx Session table) without sending further queries to PGW.
rxSessionTtl	integer		Defines the age of an Rx session after which a record is considered to be stale on PCRF Core and the PGW is queried for presence of such associations.
sessionMaxTtl	integer		

Table 2-417 UsageMonServiceConfiguration

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
enable	boolean		Specifies whether to enable or disable Usage Monitoring service for PCRF. By default, this switch is disabled.
apnList	List [string]		Specifies the list of APNs for which usage monitoring is enabled. If you leave this field empty, Usage Monitoring is enabled for all APNs.
attributeForwarding			
interfaceType	string		Indicates the interface type for which the profile applies.
messageType	string		Indicates the message type for which the profile applies
forwardingProfile	string		Refers to the configured attribute forwarding Profile.

Table 2-418 pendingTransactionConfiguration

Field Name	Data Type	Mandatory(M)/Optional(O)/Conditional(C)	Description
enabled	boolean		Specifies whether to enable or disable pending transaction service for PCRF. By default, this switch is disabled.
rarRetryBackoff	Integer		Specifies the time gap between the consecutive retry RAR messages when PGW is sending error response with cause of DIAMETER_PENDING_TRANSACTION and RAR message is triggered by PDS/AF/PRE.
rarRetryCount	Integer		Specifies the count for RAR messages when P-GW is sending error response with cause of DIAMETER_PENDING_TRANSACTION and RAR message is triggered by Notification message from PDS/AF/PRE
userNotifyReauthErrorHandling	List [string]		Specifies if an RAR initiated by User Notification message need to be discarded or retried when it is responded by P-GW with an error of DIAMETER_PENDING_TRANSACTION.
afReauthErrorHandling	List [string]		Specifies if an RAR initiated by AF message should be discarded or retried when it is responded by P-GW with an error of DIAMETER_PENDING_TRANSACTION.
reauthErrorHandling	List [string]		Specifies if an RAR initiated by any message should be discarded or retried when it is responded by P-GW with an error of DIAMETER_PENDING_TRANSACTION.

Sample Request body structure for GET and PUT operations:

```
{
  "advancedSettings": [
    {
      "key": "!",
      "value": "H"
    }
  ],
  "user": {
    "validateUser": false,
    "enableSubscriberVariables": false,
    "smPolicyData.enable": false,
    "ldapData.enable": false,
    "ocsSpendingLimit.enable": false,
    "ocsSpendingLimit.forceLookupOnUpdate": false,
    "smPolicyData.subscribeToNotify": false,
    "smPolicyData.queryOnUpdate": false,
    "smPolicyData.queryOnDelete": false,
    "smPolicyData.queryOnReauth": false,
  }
}
```

```

    "smPolicyData.autoEnrollment": false,
    "smPolicyData.default.snssai": "string",
    "ocsSpendingLimit.asyncQuery": false,
    "operatorSpecificData.enable": false,
    "operatorSpecificData.subscribeToNotify": true
  },
  "mcptt": {
    "defaultBearerARP": {
      "arpPriorityLevel": 1,
      "arpPreemptCap": "PREEMPTION_CAPABILITY_ENABLED",
      "arpPreemptVuln": "PREEMPTION_VULNERABILITY_DISABLED"
    },
    "defaultPreemptionControl": {
      "defaultPreemptControlInfo": "LEAST_RECENT_ADDED_FLOW"
    }
  },
  "audit": {
    "enable": true,
    "notificationRate": 50,
    "gxSessionTtl": 1440,
    "sessionMaxTtl": 0,
    "gxMinAuditAttempts": 5,
    "rxSessionTtl": 1440,
    "rxSessionMaxTtl": 2880,
    "sdSessionTtl": 1440,
    "sdSessionMaxTtl": 2880,
    "sdMinAuditAttempts": 5,
    "frequency": 330
  },
  "usageMonService": {
    "enable": true,
    "disableMonitoringKeyAVP": true,
    "apnList": [
      "string"
    ],
    "attributeForwarding": [
      {
        "interfaceType": {},
        "messageType": {},
        "forwardingProfile": "string"
      }
    ]
  },
  "pendingTransaction": {
    "enabled": true,
    "skipPolicyOnReauthRetry": false,
    "rarRetryBackoff": 1000,
    "rarRetryCount": 2,
    "userNotifyReauthErrorHandling": "string",
    "reauthErrorHandling": "string",
    "afReauthErrorHandling": "string"
  }
}

```

Export/Import Core Service

Table 2-419 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
date	string		Current timestamp
exportData	array		Exported list of core service. For more information, see Get and Update UE Policy
sourceVersion	string		System version of product from which data is exported
topic	string		Topic of each managed object

Sample Request Body structure for Import/Export operations:

```
{
  "topic": "string",
  "sourceVersion": "string",
  "date": "string",
  "exportData": {
    "advancedSettings": [
      {
        "key": "5PWl4;b6_I|ny:2B$\"U13x5t2U2I>G$kfFbq!}}x=0>[o2Q/#Eea9l w/
E3UnIdCa0vB!yp]%s>Kbp0=| cI1U1`$99t7kBxgUXC}",
        "value": "/cBV7m^~PA6v\"I'Z:Kx\"JKEKP3rvBH)ZP?/"
      }
    ],
    "user": {
      "validateUser": false,
      "enableSubscriberVariables": false,
      "smPolicyData.enable": false,
      "ldapData.enable": false,
      "ocsSpendingLimit.enable": false,
      "ocsSpendingLimit.forceLookupOnUpdate": false,
      "smPolicyData.subscribeToNotify": false,
      "smPolicyData.queryOnUpdate": false,
      "smPolicyData.queryOnDelete": false,
      "smPolicyData.queryOnReauth": false,
      "smPolicyData.autoEnrollment": false,
      "smPolicyData.default.snssai": "string",
      "ocsSpendingLimit.asyncQuery": false,
      "operatorSpecificData.enable": false,
      "operatorSpecificData.subscribeToNotify": true
    },
    "mcptt": {
      "defaultBearerARP": {
        "arpPriorityLevel": 1,
        "arpPreemptCap": "PREEMPTION_CAPABILITY_ENABLED",
        "arpPreemptVuln": "PREEMPTION_VULNERABILITY_DISABLED"
      }
    }
  }
}
```

```

    },
    "defaultPreemptionControl": {
      "defaultPreemptControlInfo": "LEAST_RECENT_ADDED_FLOW"
    }
  },
  "audit": {
    "enable": true,
    "notificationRate": 50,
    "gxSessionTtl": 1440,
    "sessionMaxTtl": 0,
    "gxMinAuditAttempts": 5,
    "rxSessionTtl": 1440,
    "rxSessionMaxTtl": 2880,
    "sdSessionTtl": 1440,
    "sdSessionMaxTtl": 2880,
    "sdMinAuditAttempts": 5,
    "frequency": 330
  },
  "usageMonService": {
    "enable": true,
    "disableMonitoringKeyAVP": true,
    "apnList": [
      "string"
    ],
    "attributeForwarding": [
      {
        "interfaceType": {},
        "messageType": {},
        "forwardingProfile": "string"
      }
    ]
  },
  "pendingTransaction": {
    "enabled": true,
    "skipPolicyOnReauthRetry": false,
    "rarRetryBackoff": 1000,
    "rarRetryCount": 2,
    "userNotifyReauthErrorHandling": "string",
    "reauthErrorHandling": "string",
    "afReauthErrorHandling": "string"
  }
}
}
}

```

2.78 Serving Gateway

Table 2-420 Supported REST APIs

Description	HTTP Method or Custom Operation	Resource URI	Possible Result Code
Create Serving Gateway	POST	{apiRoot}/oc-cnpolicy-configuration/v1/services/pcrfcore/sgws	See Table A-3

Table 2-420 (Cont.) Supported REST APIs

Description	HTTP Method or Custom Operation	Resource URI	Possible Result Code
Export Serving Gateway	GET	{apiRoot}/oc-cnpolicy-configuration/v1/services/pcrfcore/sgws/export	See Table A-1
Import Serving Gateway	POST	{apiRoot}/oc-cnpolicy-configuration/v1/services/pcrfcore/sgws/import	See Table A-3
Get Serving Gateway	GET	{apiRoot}/oc-cnpolicy-configuration/v1/services/pcrfcore/sgws/{servingGatewayName}	See Table A-1
Update Serving Gateway	PUT	{apiRoot}/oc-cnpolicy-configuration/v1/services/pcrfcore/sgws/{servingGatewayName}	See Table A-2
Delete Serving Gateway	DELETE	{apiRoot}/oc-cnpolicy-configuration/v1/services/pcrfcore/sgws/{servingGatewayName}	See Table A-4

Create, Get, and Update Serving Gateway**Table 2-421 Data structures supported by the POST, GET, and PUT Response Body**

Field Name	Data Type	Mandatory(M)/Optional(O)/Conditional(C)	Description
description	string		
mccMnc	string		
name	string	M	
sgwIpAddress	array		

Sample Request Body structure for POST and PUT operations:

```
{
  "description": "string",
  "mccMnc": "string",
  "name": "string",
  "sgwIpAddress": [
    "string"
  ]
}
```

Sample Response Body structure for GET, POST and PUT operations:

```
{
  "description": "string",
  "mccMnc": "string",
  "name": "string",
  "sgwIpAddress": [
    "string"
  ]
}
```

Export/Import Serving Gateway**Table 2-422 Request/Response Body Parameters**

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
date	string		Current timestamp
errors	array		
errors:message	string		
errors:name	string		
exportData	array	M	Exported list of serving gateway. For more information, see Table 2-421 .
key	string		Indicates the ID
sourceVersion	string		System version of the product from which data is exported
topic	string	M	Topic of each managed object

Sample Request Body structure for Import/Export operations:

```
{
  "date": "string",
  "errors": [
    {
      "message": "string",
      "name": "string"
    }
  ],
  "exportData": [
    {
      "description": "string",
      "mccMnc": "string",
      "name": "string",
      "sgwIpAddress": [
        "string"
      ]
    }
  ],
  "key": "string",
```



```

    "sourceVersion": "string",
    "topic": "string"
  }

```

Delete Serving Gateway

Table 2-423 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
servingGatewayName	string	M	Serving Gateway Name

2.79 Network for PGW

Table 2-424 Supported REST APIs

Description	HTTP Method or Custom Operation	Resource URI	Possible Result Code
Create Network PGW	POST	{apiRoot}/oc-cnpolicy-configuration/v1/services/pcrfcore/network/pgws	See Table A-3
Export Network PGW	GET	{apiRoot}/oc-cnpolicy-configuration/v1/services/pcrfcore/network/pgws/export	See Table A-1
Import Network PGW	POST	{apiRoot}/oc-cnpolicy-configuration/v1/services/pcrfcore/network/pgws/import	See Table A-3
Get Network PGW	GET	{apiRoot}/oc-cnpolicy-configuration/v1/services/pcrfcore/network/pgws/{networkPGWName}	See Table A-1
Update Network PGW	PUT	{apiRoot}/oc-cnpolicy-configuration/v1/services/pcrfcore/network/pgws/{networkPGWName}	See Table A-2
Delete Network PGW	DELETE	{apiRoot}/oc-cnpolicy-configuration/v1/services/pcrfcore/network/pgws/{networkPGWName}	See Table A-4

Create, Get, and Update Network for PGW**Table 2-425 Data structures supported by the POST, GET, and PUT Response Body**

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
backupHostName		O	
capabilities	array	O	
capacity	string	O	
description	string	O	
diameterRealm	string	O	
fqdn	string	O	
hostName	string	O	
ipDomainId	string	O	
name	string	M	
neDiameterId	array	O	

Sample Request Body structure for POST and PUT operations:

```
{
  "backupHostName": "string",
  "capabilities": [
    "string"
  ],
  "capacity": "string",
  "description": "string",
  "diameterRealm": "string",
  "fqdn": "string",
  "hostName": "string",
  "ipDomainId": "string",
  "name": "string",
  "neDiameterId": [
    "string"
  ]
}
```

Sample Response Body structure for GET, POST and PUT operations:

```
{
  "backupHostName": "string",
  "capabilities": [
    "string"
  ],
  "capacity": "string",
  "description": "string",
  "diameterRealm": "string",
  "fqdn": "string",
  "hostName": "string",
  "ipDomainId": "string",
  "name": "string",
  "neDiameterId": [
```

```

    "string"
  ]
}

```

Export/Import Network for PGW

Table 2-426 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
date	string		Current timestamp
errors	array		
errors:message	string		
errors:name	string		
exportData	array	M	Exported list of network for PGW. For more information, see Table 2-425 .
key	string		Indicates the ID
sourceVersion	string		System version of the product from which data is exported
topic	string	M	Topic of each managed object

Sample Request Body structure for Import/Export operations:

```

{
  "date": "string",
  "errors": [
    {
      "message": "string",
      "name": "string"
    }
  ],
  "exportData": [
    {
      "backupHostName": "string",
      "capabilities": [
        "string"
      ],
      "capacity": "string",
      "description": "string",
      "diameterRealm": "string",
      "fqdn": "string",
      "hostname": "string",
      "ipDomainId": "string",
      "name": "string",
      "neDiameterId": [
        "string"
      ]
    }
  ]
},

```

```

    "key": "string",
    "sourceVersion": "string",
    "topic": "string"
  }

```

Delete Network for PGW

Table 2-427 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
networkPGWName	string	M	Network PGW Name

2.80 Network for GGSN

Table 2-428 Supported REST APIs

Description	HTTP Method or Custom Operation	Resource URI	Possible Result Code
Create Network GGSN	POST	{apiRoot}/oc-cnpolicy-configuration/v1/services/pcrfcore/network/ggsns	See Table A-3
Export Network GGSN	GET	{apiRoot}/oc-cnpolicy-configuration/v1/services/pcrfcore/network/ggsns/export	See Table A-1
Import Network GGSN	POST	{apiRoot}/oc-cnpolicy-configuration/v1/services/pcrfcore/network/ggsns/import	See Table A-3
Get Network GGSN	GET	{apiRoot}/oc-cnpolicy-configuration/v1/services/pcrfcore/network/ggsns/{networkGGSNName}	See Table A-1
Update Network GGSN	PUT	{apiRoot}/oc-cnpolicy-configuration/v1/services/pcrfcore/network/ggsns/{networkGGSNName}	See Table A-2
Delete Network GGSN	DELETE	{apiRoot}/oc-cnpolicy-configuration/v1/services/pcrfcore/network/ggsns/{networkGGSNName}	See Table A-4

Create, Get, and Update Network for GGSN

Table 2-429 Data structures supported by the POST, GET, and PUT Response Body

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
backupHostName		O	
capabilities	array	O	
capacity	string	O	
description	string	O	
diameterRealm	string	O	
hostName	string	O	
ipDomainId	string	O	
name	string	M	
neDiameterId	array	O	

Sample Request Body structure for POST and PUT operations:

```
{
  "backupHostName": "string",
  "capabilities": [
    "string"
  ],
  "capacity": "string",
  "description": "string",
  "diameterRealm": "string",
  "hostName": "string",
  "ipDomainId": "string",
  "name": "string",
  "neDiameterId": [
    "string"
  ]
}
```

Sample Response Body structure for GET, POST and PUT operations:

```
{
  "backupHostName": "string",
  "capabilities": [
    "string"
  ],
  "capacity": "string",
  "description": "string",
  "diameterRealm": "string",
  "hostName": "string",
  "ipDomainId": "string",
  "name": "string",
  "neDiameterId": [
    "string"
  ]
}
```

```

    ]
  }

```

Export/Import Network for GGSN

Table 2-430 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
date	string		Current timestamp
errors	array		
errors:message	string		
errors:name	string		
exportData	array	M	Exported list of network for GGSN. For more information, see Table 2-429 .
key	string		Indicates the ID
sourceVersion	string		System version of the product from which data is exported
topic	string	M	Topic of each managed object

Sample Request Body structure for Import/Export operations:

```

{
  "date": "string",
  "errors": [
    {
      "message": "string",
      "name": "string"
    }
  ],
  "exportData": [
    {
      "backupHostName": "string",
      "capabilities": [
        "string"
      ],
      "capacity": "string",
      "description": "string",
      "diameterRealm": "string",
      "hostname": "string",
      "ipDomainId": "string",
      "name": "string",
      "neDiameterId": [
        "string"
      ]
    }
  ],
  "key": "string",
  "sourceVersion": "string",

```

```
"topic": "string"
}
```

Delete Network for GGSN

Table 2-431 Request/Response Body Parameters

Field Name	Data Type	Constraints	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
networkGGSNName	string		M	Network GGSN Name

2.81 Audit Service

Table 2-432 Supported REST APIs

Description	HTTP Method or Custom Operation	Resource URI	Possible Result Code
Get Audit Service	GET	{apiRoot}/oc-cnpolicy-configuration/v1/services/audit	See Table A-1
Update Audit Service	PUT	{apiRoot}/oc-cnpolicy-configuration/v1/services/audit	See Table A-2
Export Audit Service Configuration	GET	{apiRoot}/oc-cnpolicy-configuration/v1/services/audit/export	See Table A-1
Import Audit Service Configuration	POST	{apiRoot}/oc-cnpolicy-configuration/v1/services/audit/import	See Table A-3

Get and Update Audit Services

Table 2-433 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
auditEnabled	boolean	O	Determines whether to send registration request to Audit service or not. Default Value: True
logLevel	String	O	Indicates the log level of PCF Session Management (SM) service.

Table 2-433 (Cont.) Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)aints	Description
forcedDeletion.minAttempts BeforeForceDelete	integer	O	Specifies the minimum number of consecutive failed audit attempts until maxTTL / forceTTL is reached. If maxTTL is reached and audit_attempts + 1 >= Minimum Audit Attempts for maxTTL, Audit service sends notification to SM service with maxTTL flag set to true. SM Service sends DELETE request to PDS and Binding Service. Range: 0-255 Default Value: 0 Note: If maxTTL is not reached and if audit attempts are reached, the number of audit attempts are incremented until maxTTL is reached.

Sample Request body structure for PUT operation:

```
{
  "auditEnabled": true,
  "forcedDeletion": {
    "minAttemptsBeforeForceDelete": 5
  }
}
```

Sample Response body structure for GET, POST, and PUT operations:

```
{
  "auditEnabled": true,
  "forcedDeletion": {
    "minAttemptsBeforeForceDelete": 5
  }
}
```


Export/Import Audit Services

Table 2-434 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
date	string		Current timestamp
exportData	array		Exported list of policy audit service. For more information, see Get and Update Audit Services .
sourceVersion	string		System version of the product from which data is exported
topic	string	M	Topic of each managed object

Sample Request Body structure for Import/Export operations:

```
{
  "topic": "common.audit-service.cfg",
  "sourceVersion": "24.3.0-rc.11",
  "date": "2024-10-28T06:05:29Z",
  "exportData": {
    "auditEnabled": true,
    "forcedDeletion": {
      "minAttemptsBeforeForceDelete": 35
    }
  }
}
```

Audits Scheduled REST API

Note

The "Audits Scheduled REST API" must be accessed through Audit port.

Table 2-435 Services Audits Scheduled API description:

Description	HTTP Method or Custom Operation	Resource URI	Possible Result Code
Audit Service Fetch	GET	{apiRoot}/audits/{serviceName}	See Table A-1
Get Audit Table Data for CM GUI	GET	{apiRoot}/audit?serviceName={serviceName}&tableName={tableName}	See Table A-1
Get Statistics for a table	GET	{apiRoot}/audits/stats/{serviceName}	See Table A-1

Table 2-435 (Cont.) Services Audits Scheduled API description:

Description	HTTP Method or Custom Operation	Resource URI	Possible Result Code
Operation Name for Audit	PUT	{apiRoot}/audit/{operationName}	See Table A-2
Audit Service Registration	PUT	{apiRoot}/audits/{serviceName}	See Table A-2
Audit Service Deregistration	DELETE	{apiRoot}/audits/{serviceName}	See Table A-4
GET Audit for all services	GET	{apiRoot}/audit	See Table A-1

Table 2-436 Request/Response Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
serviceName	string	M	Identifier of the requestor NF service, e.g. pcf-sm
operationName	string	M	Operation name for audit , e.g. NOW/ PAUSE/RESUME
tableName	string	M	Table name thats need to be audited.

2.82 Binding Service

Table 2-437 Supported REST APIs - Binding Service

Description	HTTP Method or Custom Operation	Resource URI	Possible Result Code
Get Binding Service	GET	{apiRoot}/oc-cnpolicy-configuration/v1/services/binding	See Table A-1
Update Binding Service	PUT	{apiRoot}/oc-cnpolicy-configuration/v1/services/binding	See Table A-2
Export Binding Services	GET	{apiRoot}/oc-cnpolicy-configuration/v1/services/binding/export	See Table A-1
Import Binding Services	POST	{apiRoot}/oc-cnpolicy-configuration/v1/services/binding/import	See Table A-3

Get and Update Binding Service

Table 2-438 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
abortOnBindingError	boolean	O	Determines if PCF (SM service) should abort terminate session when binding error is received.
bindingOperationEnabled	boolean	O	This determines if binding operation (register and deregister) to the BSF is enabled. Default Value: TRUE
bsfEnabled	boolean	O	Determines if BSF is enabled or disabled.
bsfNfCommProfile	String	O	Specifies the NF communication profile used by BSF.
bsfRetryProfileForInitMsgs	string	O	Retry Profile to be used when PCF fails to send a create message to a producer node .
bsfRetryProfileForSubsqMsgs	string	O	Retry Profile to be used when PCF fails to send an in-session message to a producer node.
defaultBindingOperationMode	Enum	O	Allows users to configure binding operation mode as synchronous or asynchronous.
enableApnFilterBySnssai	boolean	O	This parameter can be used to enable or disable limiting of number of bindings at DNN + SNSSAI + IP domain level at Binding service.
enableSessionLimitByUser	boolean	O	This parameter can be used to enable or disable user level limiting for bindings at Binding service.
maxSessionLimitByApn	integer	O	This parameter can be used to specify the maximum session limit for DNN + SNSSAI + IP domain level.
maxSessionLimitByUser	integer	O	This parameter can be used to specify the maximum session limit for a particular user.
useHttp2	boolean	O	Determines if using http/2 to communicate with BSF. Otherwise use http/1.1. Default Value: TRUE
useLocalConfiguredBsfAlways	boolean	O	Whether to use local configured BSF without Always discovering. Default Value: FALSE
useLocalConfiguredBsfWhenNotDiscovered	boolean	O	Whether to use local configured (if having) BSF when not discovered or discover failed. Default Value: FALSE

Table 2-438 (Cont.) Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
enableVSAInRegisterRequest	boolean	O	Determines if PCF sends Vendor-Specific-Attribute in the Binding Create or Register request. By default, the value is set to false.
vendorID	integer	O	Note: This field becomes active only when Enable Vendor Specific Attribute in Register Request switch is enabled. Specifies the Vendor ID that is mapped to the vendorId in the Vendor-Specific-Attribute.
dataCompressionScheme	String	O	Specifies the data compression scheme used by Binding Service. Default value is "0"; compression is disabled by default. Following are the allowed values for this field: 0- Disabled 2- Application Compressed
Optimization	Binding Query Optimization	O	This section is used to configure query optimization on Binding service database. For more details, see Table 2-439 .
audit	BindingAuditConfiguration	O	Provide Binding Audit Configuration details.
maxSessionCleanupMode	String Enum:[Local, Remote]	O	Binding service uses this flag to send request to SM service for either local or remote session clean up. The allowed values for this flag are: - Local - Remote On choosing the flag to Local, PCF deletes the session locally and does not send notify terminate request toward SMF. Default Value: Local
maxSessionForceDeleteOnExpiryOfWaitTimer	integer	O	On Max Session Cleanup Mode set to Remote this toggle flag appears. It makes forceDeleteOnExpiryOfWaitTimer flag to true or false which is used in SM service request for remote cleanup. Default Value: false

Table 2-438 (Cont.) Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
maxSessionForceDeleteOnError	boolean	O	On Max Session Cleanup Mode set to Remote this toggle flag appears. It makes forceDeleteOnError flag to true or false which is used in SM service request for remote cleanup. On SM service notify terminate request failure and based on forceDeleteOnError flag, the session with 4xx and 5xx response status codes are deleted except for the 404 status code. Default Value: false
messagePriority	Message Priority	O	To configure Message Priority Profile for Binding service.
advancedSettings	AdvanceSettings	O	-

Table 2-439 Configuring Optimization

Parameter	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
optimization.enableIndex Migration	Boolean	M	Indicates whether data must be migrated to the new format and populated into the index tables. Possible values: - true: contextBindingId is made equal to contextId and records are inserted in index-tables. - false: no change to existing call flows, and data migration or indexing is not performed. Default value: false

Table 2-439 (Cont.) Configuring Optimization

Parameter	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
optimization.enableQueryOptimization	Boolean	C	It indicates if the search needs to be optimized using new approaches: Possible values: • true: search contextBinding table using primary key column and also search index table using partition-key, for find context-owner and session limiting features. • false: existing index-key based queries are continued as is. Before enabling optimization.enableQueryOptimization parameter, verify on the Custom Query page that all records are indexed. NOTE: Before enabling the flag, please make sure that the software in all sites are upgraded and all the records are migrated properly to new format. Default value: false

Table 2-439 (Cont.) Configuring Optimization

Parameter	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
optimization.preferredSubscriberId	Enum	C	This field appears only when optimization.enableQueryOptimization parameter is enabled. Specifies if the preferred subscriber ID to be used to search binding while session limiting. Possible values: • SUPI • GPSI • SUPI_OR_GPSI Default value: SUPI_OR_GPSI Note: Session limiting may not work as expected if the configured subscriber ID preference does not match the identifiers present in incoming Binding registration requests.

Table 2-440 BindingAuditConfiguration

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
enable	boolean	O	Determines whether to send registration request to Audit service or not. Default Value: True
notificationRate	integer	M	Defines the number of stale records which Audit service notifies to Binding service in one second. The allowed value ranges 20 to 700 seconds. The CNC Console filed name is Notification Rate (per second). Default Value: 50

Table 2-440 (Cont.) BindingAuditConfiguration

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
maxTtl	integer	M	Defines the maximum binding age in minutes, after which the Binding session record becomes eligible for alternate site audit handling. The CNC Console filed name is Maximum Binding Age (in minutes). Default Value: 2940
minAuditAttempts	integer	M	Specifies the minimum number of failed audit attempts required before Audit service sends a maxTTL notification with maxTtlReached=true. When maxTTL is reached, Audit service compares the total attempts stored in auditAttempts with minAuditAttempts. If auditAttempts < minAuditAttempts, the notification is sent with maxTtlReached=false; if auditAttempts >= minAuditAttempts, the notification is sent with maxTtlReached=true. The CNC Console filed name is Minimum Audit Attempts. Range: 0-255 Default Value: 0 Note: If maxTTL is not reached and if audit attempts are reached, the number of audit attempts are incremented until maxTTL is reached.

Table 2-440 (Cont.) BindingAuditConfiguration

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
ttl	integer	-	Defines the binding age in minutes, after which the record is considered stale. Audit service notifies Binding service and Binding service validates the record with the owning core service, such as SM or PCRF Core. The CNC Console filed name is Binding Age (in minutes). Default Value: 1500
frequency	integer	O	Specifies the minimum interval in minutes between two consecutive audit passes for Binding audit tables. The CNC Console filed name is Minimum Audit Passes Interval (in minutes). Default Value: 15
revalidateEnable	boolean	O	Determines whether to revalidate the binding session details with BSF. When this field is enabled, Binding service sends a request for revalidating the binding session records for valid PDU sessions in BSF. Default value: False
bsfRetryProfRevalid	string	O	Specifies the retry profile for revalidating the session binding records with BSF.

Table 2-441 Message Priority Profile

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
messagePriority.messagePriorityProfile	String	O	Select one of the message priority profiles created on Message Profiles page that must be applied for Binding Service. When a message profile is selected under Message Priority Profile section, support for 3GPP-SBI-Message-Priority header gets enabled for Binding Service.

Table 2-442 AdvancedSettings

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
key	string	O	Specifies the key name.
value	string	O	Specifies the value of the key.

For more information on the Advanced Settings "Keys" and "Values", see "Binding Service" section of "Configuring Policy Using CNC Console" in *Oracle Communications Cloud Native Core, Converged Policy User Guide*.

Sample Response body structure for Binding Service GET and PUT operation:

```
{
  "useLocalConfiguredBsfAlways": true,
  "useLocalConfiguredBsfWhenNotDiscovered": true,
  "useHttp2": true,
  "abortOnBsfError": true,
  "bsfRetryProfileForInitMsgs": "string",
  "bsfRetryProfileForSubsqMsgs": "string",
  "maxSessionLimitByUser": 10,
  "maxSessionLimitByApn": 2,
  "enableSessionLimitByUser": true,
  "enableApnFilterBySnssai": true,
  "bindingServiceNfCommProfile": "string",
  "enableVSAInRegisterRequest": true,
  "vendorId": "000111",
  "dataCompressionScheme": "0",
  "optimization": {
    "enableIndexMigration": false,
    "enableQueryOptimization": false,
    "preferredSubscriberId": "SUPI_OR_GPSI"
  }
}
```

```

    },
    "audit": {
      "enable": true,
      "notificationRate": 50,
      "ttl": 1440,
      "maxTtl": 7200,
      "frequency": 330,
      "minAuditAttempts": 5,
      "revalidateEnable": false,
      "bsfRetryProfRevalid": "string"
    },
    "maxSessionCleanupMode": "Local",
    "maxSessionForceDeleteOnExpiryOfWaitTimer": false,
    "maxSessionForceDeleteOnError": false,
    "messagePriority": {
      "messagePriorityProfile": "string"
    },
    "advancedSettings": [
      {
        "key": "&",
        "value": "AE<"
      }
    ]
  }
}

```

Import and Export Binding Service

Table 2-443 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
date	string	-	Current timestamp
errors.message	-	-	The reason of the failure.
errors.name	-	-	Name of the components that failed to export or import.
exportData	array	-	Exported list of Binding Service. For more information, see Get and Update Binding Service .
key	string	-	Indicates the ID
sourceVersion	string	-	System version of product from which data is exported
topic	string	-	Topic of each managed object

Sample Request Body structure for Binding Service Import and Export operations:

```

{
  "topic": "string",
  "sourceVersion": "string",

```

```

"date": "string",
"exportData": {
  "useLocalConfiguredBsfAlways": true,
  "useLocalConfiguredBsfWhenNotDiscovered": true,
  "useHttp2": true,
  "abortOnBsfError": true,
  "bsfRetryProfileForInitMsgs": "string",
  "bsfRetryProfileForSubsqMsgs": "string",
  "maxSessionLimitByUser": 10,
  "maxSessionLimitByApn": 2,
  "enableSessionLimitByUser": true,
  "enableApnFilterBySnssai": true,
  "bindingServiceNfCommProfile": "string",
  "enableVSAInRegisterRequest": true,
  "vendorId": "000111",
  "dataCompressionScheme": "0",
  "optimization": {
    "enableIndexMigration": false,
    "enableQueryOptimization": false,
    "preferredSubscriberId": "SUPI_OR_GPSI"
  },
  "audit": {
    "enable": true,
    "notificationRate": 50,
    "ttl": 1440,
    "maxTtl": 7200,
    "frequency": 330,
    "minAuditAttempts": 5,
    "revalidateEnable": false,
    "bsfRetryProfRevalid": "string"
  },
  "maxSessionCleanupMode": "Local",
  "maxSessionForceDeleteOnExpiryOfWaitTimer": false,
  "maxSessionForceDeleteOnError": false,
  "messagePriority": {
    "messagePriorityProfile": "string"
  },
  "advancedSettings": [
    {
      "key": "?T~|",
      "value": "Z"
    }
  ]
},
"errors": [
  {
    "name": "string",
    "message": "string"
  }
]
}

```

2.83 NF Communication Profiles

This section describes the service URIs available to create and configure NF communication profiles for CNC Policy.

Table 2-444 Policy NF Communication Profiles APIs

Description	HTTP Method or Custom Operation	Resource URI	Possible Result Code
Create NF Communication Profile	POST	{apiRoot}/oc-cnpolicy-configuration/v1/services/common/nfcommprofiles	See Table A-3
Get NF Communication Profile	GET	{apiRoot}/oc-cnpolicy-configuration/v1/services/common/nfcommprofiles/{nfCommunicationProfileName}	See Table A-1
Update NF Communication Profile	PUT	{apiRoot}/oc-cnpolicy-configuration/v1/services/common/nfcommprofiles/{nfCommunicationProfileName}	See Table A-2
Export NF Communication Profiles	GET	{apiRoot}/oc-cnpolicy-configuration/v1/services/common/nfcommprofiles/export	See Table A-1
Import NF Communication Profiles	POST	{apiRoot}/oc-cnpolicy-configuration/v1/services/common/nfcommprofiles/import	See Table A-3
Delete NF Communication Profile	DELETE	{apiRoot}/oc-cnpolicy-configuration/v1/services/common/nfcommprofiles/{nfCommunicationProfileName}	See Table A-4

Get, Create, and Update NF Communication Profile

This section describes the request and response parameters used in NF communication profile APIs.

Table 2-445 Request and Response Body Parameters

Field Name	Data Type	Mandatory(M)/Optional(O)/Conditional(C)	Description
nfCommunicationProfileName	string	M	The unique name for the NF communication profile. This name is used to refer to the profile in other service configuration screen, such as SM Service, User Connector, and so on. The name can only contain the characters A–Z, a–z, 0–9, period (.), hyphen (-), and underline (_). The maximum length is 255 characters.
policyNfCommunicationModel	String	O	Indicates the communication model, in which the Policy NF is deployed. Provide any of the following values: - CUSTOM - Model_B - Model_C - Mode_D Default value: CUSTOM
nfDiscoverySettings.discoveryParameters	DiscoveryParam	M Note: This parameter is mandatory when either of the following attributes is set to true: - sendDiscoveryHeaderInItMsg - sendDiscoveryHeaderSubMsg	Indicates the discovery parameter to be used in the 3gpp-sbi-discovery-<discovery-parameter>. This parameter is ignored when the "policyNfCommunicationModel" is set to MODEL_B.

Table 2-445 (Cont.) Request and Response Body Parameters

Field Name	Data Type	Mandatory(M)/Optional(O)/Conditional(C)	Description
nfDiscoverySettings.sendDiscoveryHeaderInitMsg	boolean	O	This value indicates if PCF must include the following 3gpp-sbi-discovery-<discovery-parameter> parameters in SBI messages: - Parameters that create a subscription, such as POST messages - Parameters that do not belong to a subscription, such as GET or PATCH messages Default value: False, for Custom model. This attribute is ignored when "policyNfCommunicationModel" is set to any value other than CUSTOM.
nfDiscoverySettings.sendDiscoveryHeaderSubsMsg	boolean	O	This value indicates if PCF must include the following 3gpp-sbi-discovery-<discovery-parameter> parameters in SBI messages: - Parameters to update a subscription, such as PUT messages when unable to fill in a 3gpp-sbi-routing-binding header. - Parameters to delete a subscription, such as DELETE messages when unable to fill in a 3gpp-sbi-routing-binding header. Default value: False, for Custom model. This attribute is ignored when "policyNfCommunicationModel" is set to any value other than CUSTOM.
nfDiscoverySettings.sendTargetApiRootHeaderInitMsg	boolean	false	Indicates if PCF must include 3gpp-sbi-target-apiroot header in initial request messages. If the user selects Model D for Policy NF Communication Model, the value for this parameter must be set to false. For other Policy NF Communication Model values, the default value is true.

Table 2-445 (Cont.) Request and Response Body Parameters

Field Name	Data Type	Mandatory(M)/Optional(O)/Conditional(C)	Description
onDemandDiscoveryCaching.forceDiscovery	String	O	Indicates whether to cache the NF profiles in NRF client or to skip caching and receive the response directly from NRF. Value of this parameter can be 0 or 1. — When the value of OC-Force-Rediscovery parameter is set to 0, it enables the feature and caches the NF profiles details received from NRF in NRF Client. — When the value of OC-Force-Rediscovery parameter is set to 1, it disables the feature and retrieves the NF profiles directly from NRF while responding to the query from the backend services. Default value: 0
onDemandDiscoveryCaching.retentionPeriod	String	O	Indicates whether to cache the NF profiles in NRF client or to skip caching and receive the response directly from NRF. Value of this parameter can be 0 or 1. — When the value of OC-Force-Rediscovery parameter is set to 0, it enables the feature and caches the NF profiles details received from NRF in NRF Client. — When the value of OC-Force-Rediscovery parameter is set to 1, it disables the feature and retrieves the NF profiles directly from NRF while responding to the query from the backend services. Default value: 0
nfBindingSettings.bindingLevel	boolean	M Note: This parameter is mandatory when the sendBindingHeader parameter is set to true.	Indicates the binding level that must to be included in the 3gpp-sbi-binding header when PCF adds this header in a message to another NF. Provide any of the following values: • NF_SET • NF_INSTANCE

Table 2-445 (Cont.) Request and Response Body Parameters

Field Name	Data Type	Mandatory(M)/Optional(O)/Conditional(C)	Description
nfBindingSettings.sendBindingHeader	boolean	O	Indicates if PCF includes the 3gpp-sbi-binding header in SBI messages for the subscription creation, modification, or notification requests and responses, as applicable. Default value: False, for Custom model. This attribute is ignored when "policyNfCommunicationModel" is set to any value other than "Custom".
nfBindingSettings.sendServiceName	boolean	O	Indicates whether to enable or disable the support for sending service name in binding header. Possible values: - true: includes svcname in the Binding Header sent towards NFs such as UDR, AMF, or BSF (customized) except for CHF, which contains the 3GPP defined PCF service name. - false: does not include svcname in the Binding Header. Default value : false
nfBindingSettings.sendRoutingBindingHeader	boolean	O	Indicates if PCF includes the 3gpp-sbi-routing-binding header in SBI messages for the subscription creation, modification, or notification requests, as applicable. Default value: False
nfBindingSettings.sendCallbackHeader	boolean	O	Indicates if PCF includes the 3gpp-sbi-callback header in SBI messages for the subscription creation, modification, or notification requests, as applicable. Default value: False, for Custom model. This attribute is ignored when "policyNfCommunicationModel" is set to any value other than CUSTOM . For more information, see Table 2-448
nfServerSettings	NFServerSettings	O	Specifies the server header settings for the NF communication profile.
nfServerSettings.sendServerHeader	Boolean	O	Indicates if services Converged Policy microservices include server header while sending an error response.
nfServerSettings.serverHeaderErrorCodes	String	O	Specifies the error codes for which service header is generated. The error codes can be from 100 to 999. Note: If no error is specified, then Converged Policy sends server header for all error responses.

Table 2-445 (Cont.) Request and Response Body Parameters

Field Name	Data Type	Mandatory(M)/Optional(O)/Conditional(C)	Description
retryAndAlternateRoutingSettings.retryProfileInitMsg	string	O	Specifies the retry or alternate routing options when an SBI message is not delivered successfully in any of the following scenarios: - POST operation to create a subscription - GET or PATCH request not belonging to a subscription
retryAndAlternateRoutingSettings.retryProfileSubsMsg	string	O	Specifies the retry or alternate routing options when an SBI message that updates, deletes or notifies a subscription is not delivered successfully.
nfCorrelationSettings.sendCorrelationHeader	string	O	Indicates whether to carry subscriber identifier included in SBI messages and can be used for SBI message correlation. Default Value: false
nfCorrelationSettings.allowedCorrelationInfoType	string	O	Displays the types of values that can be included in Correlation-info Header. Currently only SUPI and GPSI are supported.
nfPeerInfoSettings.sendNfPeerInfo	Boolean	O	Enables PCF to send received or generated NF Peer Info headers to producer NFs. Default Value: false
nfPeerInfoSettings.includeSrcServInst	Boolean	O	Enables PCF to include the NF service instance ID when forwarding received or generated headers. Note: The Include NF Service Instance ID field depends on the Send NF-Peer-Info Header field. - If Send NF-Peer-Info Header is disabled, then Include NF Service Instance ID is hidden and cannot be enabled. - If Send NF-Peer-Info Header is enabled, then Include NF Service Instance ID is displayed and configurable. - The Include NF Service Instance ID option is automatically hidden if the user attempts to enable it before enabling the Send NF-Peer-Info Header flag. Default Value: false
reattemptSettings	ReattemptSettings	O	Provide Re-attempt Settings details.

Table 2-446 ReattemptSettings

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
enableNFServiceOperationReattempt	boolean	O	This is a global flag to enable re-attempt for NF service operations. Default Value: false
nfServiceOperationProfiles	NFServiceOperationProfiles	O	Configure the list of NF Service Operations along with Reattempts Profile.

Table 2-447 NFServiceOperationProfiles

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
nfServiceOperation	string Enum:[]	O	Configure the list of NF Service Operations. The possible values are: • AMFDiscovery • N1N2MessageSubscribe • N1N2MessageTransfer • N1N2TransferFailureNotification
reattemptProfile	NFServiceOperationProfiles	O	Provide the Reattempts Profiles for the selected service operation.

Default Header Values

The following table informs about the default values of Binding headers for each of the supported communication models:

Table 2-448 Default Header Values for Communication Model

Flags	Model B	Model C	Model D	Custom
Send Target Api Root Header in Initial Message	True	True	False	True
Send Discovery Header In Initial Messages	False	False	True	False
Send Discovery Header In Subsequent Messages	False	False	True	False
Send Binding Header	True	True	True	False

Table 2-448 (Cont.) Default Header Values for Communication Model

Flags	Model B	Model C	Model D	Custom
Send Routing Binding Header	False	True	True	False
Send Callback Header	False	True	True	False

Sample Request body for NF Communication Profile POST and PUT operations:

```

{
  "nfCommunicationProfileName": "String",
  "policyNfCommunicationModel": "CUSTOM",
  "onDemandDiscoveryCaching": {
    "forceDiscovery": 1,
    "ignoreCacheAndForceDiscovery": 0,
    "retentionPeriod": 10000
  },
  "nfDiscoverySettings": {
    "discoveryParameters": [
      {
        "paramName": "TARGET_NF_SET_ID",
        "paramValue": "string"
      }
    ],
    "sendDiscoveryHeaderInitMsg": false,
    "sendDiscoveryHeaderSubsMsg": false,
    "sendTargetApiRootHeaderInitMsg": true
  },
  "nfBindingSettings": {
    "bindingLevel": "NF_SET",
    "sendBindingHeader": false,
    "sendRoutingBindingHeader": false,
    "sendCallbackHeader": false,
    "sendServiceName": false
  },
  "nfServerSettings": {
    "serverHeaderErrorCodes": [
      0
    ],
    "sendServerHeader": true
  },
  "retryAndAlternateRoutingSettings": {
    "retryProfileInitMsg": "string",
    "retryProfileSubsMsg": "string"
  },
  "nfCorrelationSettings": {
    "sendCorrelationHeader": false,
    "allowedCorrelationInfoIdType": [
      "SUPI"
    ]
  },
  "nfPeerInfoSettings": {
    "sendNfPeerInfo": true,

```

```

    "includeSrcServInst": false
  },
  "reattemptSettings": {
    "enableNFServiceOperationReattempt": true,
    "nfServiceOperationProfiles": [
      {
        "nfServiceOperation": "AMFDiscovery",
        "reattemptProfile": "string"
      }
    ]
  }
}

```

Sample Response body structure for NF Communication Profile GET, POST, and PUT operation:

```

{
  "topic": "string",
  "sourceVersion": "string",
  "systemVersion": "string",
  "date": "string",
  "errors": [
    {
      "name": "string",
      "message": "string"
    }
  ],
  "exportData": [
    {
      "nfCommunicationProfileName": "String",
      "policyNfCommunicationModel": "CUSTOM",
      "onDemandDiscoveryCaching": {
        "forceDiscovery": 1,
        "ignoreCacheAndForceDiscovery": 0,
        "retentionPeriod": 10000
      },
      "nfDiscoverySettings": {
        "discoveryParameters": [
          {
            "paramName": "TARGET_NF_SET_ID",
            "paramValue": "string"
          }
        ]
      },
      "sendDiscoveryHeaderInitMsg": false,
      "sendDiscoveryHeaderSubsMsg": false,
      "sendTargetApiRootHeaderInitMsg": true
    },
    {
      "nfBindingSettings": {
        "bindingLevel": "NF_SET",
        "sendBindingHeader": false,
        "sendRoutingBindingHeader": false,
        "sendCallbackHeader": false,
        "sendServiceName": false
      },
      "nfServerSettings": {

```

```

        "serverHeaderErrorCodes": [
            0
        ],
        "sendServerHeader": true
    },
    "retryAndAlternateRoutingSettings": {
        "retryProfileInitMsg": "string",
        "retryProfileSubsMsg": "string"
    },
    "nfCorrelationSettings": {
        "sendCorrelationHeader": false,
        "allowedCorrelationInfoIdType": [
            "SUPI"
        ]
    },
    "nfPeerInfoSettings": {
        "sendNfPeerInfo": true,
        "includeSrcServInst": false
    },
    "reattemptSettings": {
        "enableNFServiceOperationReattempt": true,
        "nfServiceOperationProfiles": [
            {
                "nfServiceOperation": "AMFDiscovery",
                "reattemptProfile": "string"
            }
        ]
    }
}
]
}
}

```

Import and Export NF Communication Profile

Table 2-449 Import/Export NF Communication Profile

API Name	Request Type	Request Url	Possible Result Code
Export NF Communication Profiles	GET	{apiRoot}/oc-cnpolicy-configuration/v1/services/common/nfcommprofiles/export	Table A-1
Import NF Communication Profiles	POST	{apiRoot}/oc-cnpolicy-configuration/v1/services/common/nfcommprofiles/import	See Table A-3

Table 2-450 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/Optional(O)/Conditional(C)	Description
date	string	O	Current timestamp
error.message	string	O	The reason of the failure.

Table 2-450 (Cont.) Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
error.name	string	O	Name of the components that failed to export or import.
exportData	array	M	Exported list of NF Communication Profile. For more information, see Get, Create, and Update NF Communication Profile .
key	string	O	Indicates the ID of NF Communication Profile.
sourceVersion	string	O	System version of product from which data is exported
topic	string	M	Topic of each managed object

Sample Request Body structure for NF Communication Profile Import and Export operations:

```
{
  "systemVersion": "string",
  "topic": "string",
  "sourceVersion": "string",
  "date": "string",
  "exportData": [
    {
      "nfCommunicationProfileName": "String",
      "policyNfCommunicationModel": "CUSTOM",
      "nfDiscoverySettings": {
        "discoveryParameters": [
          {
            "paramName": "TARGET_NF_SET_ID",
            "paramValue": "string"
          }
        ],
        "sendDiscoveryHeaderInitMsg": false,
        "sendDiscoveryHeaderSubsMsg": false,
        "sendTargetApiRootHeaderInitMsg": false
      },
      "onDemandDiscoveryCaching": {
        "ignoreCacheAndForceDiscovery": 0,
        "forceDiscovery": 0,
        "retentionPeriod": 10000
      },
      "nfBindingSettings": {
        "bindingLevel": "NF_SET",
        "sendBindingHeader": false,
        "sendRoutingBindingHeader": false,

```

```

        "sendCallbackHeader": false,
        "sendServiceName": false
    },
    "nfServerSettings": {
        "sendServerHeader": true,
        "serverHeaderErrorCodes": [
            0
        ]
    },
    "retryAndAlternateRoutingSettings": {
        "retryProfileInitMsg": "string",
        "retryProfileSubsMsg": "string"
    },
    "nfCorrelationSettings": {
        "sendCorrelationHeader": true,
        "allowedCorrelationInfoIdType": [
            "imsi"
        ]
    },
    "nfPeerInfoSettings": {
        "sendNfPeerInfo": true,
        "includeSrcServInst": false
    },
    "reattemptSettings": {
        "enableNFServiceOperationReattempt": true,
        "nfServiceOperationProfiles": [
            {
                "nfServiceOperation": "AMFDiscovery",
                "reattemptProfile": "string"
            }
        ]
    }
},
"errors": [
    {
        "name": "string",
        "message": "string"
    }
]
}

```

2.84 PDS Settings

Table 2-451 Supported REST APIs

Description	HTTP Method or Custom Operation	Resource URI	Possible Result Code
Export PDS Settings	GET	{apiRoot}/oc-cnpolicy-configuration/v1/services/pds/pdsSettings/export	See Table A-1

Table 2-451 (Cont.) Supported REST APIs

Description	HTTP Method or Custom Operation	Resource URI	Possible Result Code
Import PDS Settings	POST	{apiRoot}/oc-cnpolicy-configuration/v1/services/pds/pdsSettings/import	See Table A-3
Get PDS Settings	GET	{apiRoot}/oc-cnpolicy-configuration/v1/services/pds/pdsSettings	See Table A-1
Update PDS Settings	PUT	{apiRoot}/oc-cnpolicy-configuration/v1/services/pds/pdsSettings	See Table A-2

Get and Update PDS Settings**Table 2-452 Request/Response Body Parameters**

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
audit.enable	boolean	O	Specifies whether to send registration request to Audit service or not.
audit.notificationRate	integer	M	Specifies the number of stale records which Audit service notifies to PDS service in one second.
audit.pdsProfileMinAuditPassInterval	integer	M	Specifies the minimum interval (in minutes) between start times of two consecutive audit passes for the pdssubscriber table.
audit.pdsProfileAge	integer	M	Specifies the age (in minutes) of PDS profile (GPSI-SUPI-NAI mapping) after which the profile is considered to be stale in Policy and PDS subscriber table is queried for presence of such associations.
audit.pdsProfileMaxAge	integer	M	Specifies the age (in minutes) of PDS profile (GPSI-SUPI-NAI mapping) after which the profile is purged from the database without sending any queries to PDS subscriber table.
audit.subscriberMinAuditPassInterval	integer	M	Specifies the minimum interval (in minutes) between start times of two consecutive audit passes for the pdssubscriber table.

Table 2-452 (Cont.) Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
audit.subscriberSessionAge	integer	M	Specifies the age (in minutes) of PDS subscriber entry after which a record is considered to be stale on Policy and services (SM, AM, UE, and PCRF Core) are queried for presence of such associations.
audit.subscriberSessionMaxAge	integer	M	Specifies the age (in minutes) of PDS subscriber entry after which a record is purged from the database and no query requests are sent to services for presence of such associations.
audit.policyDataSubscriptionExpiry.policyDataSubsEnabled	Boolean	O	Determines whether to enable or disable the handling of Policy Data subscription expiry. Default value: false
audit.policyDataSubscriptionExpiry.policyDataSubsPreExpiryPeriod	integer	O	Specifies the duration (time in minutes) for which the Re-subscription can be triggered for Policy data. Default value: 180 Range: 1 to 20160
audit.policyDataSubscriptionExpiry.policyDataSubsExpiryAuditNotificationRate	integer	O	Specifies the Policy Data Subscription Expiry notification processing rate. Default value: 50 Range: 20-300
audit.policyDataSubscriptionExpiry.policyDataSubsExpiryMaxAge	integer	O	Specifies the Audit window limited to local site. The local site triggers the audit until the maximum Policy association age is reached. Once maximum Policy association age is reached, the replicated site becomes eligible to perform the audit. Default value: 50 Range: 1-100
audit.policyDataSubscriptionExpiry.policyDataSubsExpiryMinAuditPassInterval	integer	O	Specifies the minimum interval between Policy Data Subscription expiry audits. Default value: 10 Range: 1-1440
common.enableFetchAndResubscribe	boolean	O	If the value for this parameter is set to true, PDS refetches the data and revalidates the subscription when the number of sessions exceeds the configured limit at PDS.

Table 2-452 (Cont.) Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
common.enableHttp2	boolean	O	If the value for this parameter is set to true, the HTTP2 remains enabled. By default, HTTP2 remains disabled.
common.requestTimeout	string	O	If PDS Setting is updated then set the timeout as 3000 for the initial flow to succeed.
common.sessionCountPerDnnList	SessionCountPerDnnList	O	If enableFetchAndResubscribe parameter is set to true, user can configure the number of sessions per DNN using this group of parameters.
common.enableConfigurableTimeout	string	O	If this parameter is enabled the following interface-level timeouts (optional) are displayed: • UDR Request Timeout • CHF Request Timeout • LDAP Request Timeout • OCS Request Timeout • Bulwark Request Timeout • PRE Request Timeout • Notification Request Timeout • Audit Request Timeout Note: When the enableConfigurableTimeout parameter is disabled, it defaults to the Global Request Timeout. Similarly, if interface-level timeouts are not set, they will also use the Global Request Timeout as a fallback.
common.dataCompressionScheme	string	O	Specifies the data compression scheme used by PDS. Following are the allowed values for this field: • Disabled • Application Compressed By default, this value remains disabled.
remoteSSVRootPath.amPolicyData	array(string)	M	Specifies the root path of subscriber state variables under amPolicyData.
remoteSSVRootPath.enableEndSessionSSVRemoteToUDR	boolean	O	Specifies if the dynamic write should happen at the time of policy execution or at the end of the last session for a subscriber.
remoteSSVRootPath.operatorSpecificData	array(string)	M	Specifies the paths of subscriber state variables under operatorSpecificData.

Table 2-452 (Cont.) Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
remoteSSVRootPath.smPolicyData	array(string)	M	Specifies the paths of subscriber state variables under SMPolicyData.
remoteSSVRootPath.spendingLimitData	array(string)	M	Specifies the path of subscriber state variables under SpendingLimitData.
remoteSSVRootPath.uePolicySet	array(string)	M	Specifies the path of subscriber state variables under uePolicySet.

Note

The **Type of Search** (`common.typeOfSearch`) and **Preference Order** (`common.preferenceOrder`) parameters are not imported or updated through PDS Settings, either using the CNC Console or REST API. These configurations must be updated using PDS UE ID Configuration. For more information, see [PDS UE ID Configuration Settings](#).

Table 2-453 SessionCountPerDnnList

Parameter Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
dnn	string	O	Specifies the Data Network Name. The allowed expression for DNN is <code>^[A-Za-z0-9-]+\$. Spaces and other characters are not allowed. (NA allowed)</code>
maxSessionsCount	integer	O	Specifies the number of sessions after which PDS refetches and revalidates subscriptions. You can enter a number from 1 to 20.
sd	string	O	Specifies the Slice Differentiator Name. The allowed expression for SD is <code>^[A-Fa-f0-9-]+\$. Spaces and other characters are not allowed.</code>
sst	string	O	Specifies the Slice or Service Type name in the S-NSSAI. You can enter a number from 0 to 255 or NA.

Sample Request body structure for PUT and PATCH operations:

```
{
  "remoteSSVRootPath": {
    "operatorSpecificData": [
      "operatorSpecificData.vendorSpecific-1.dynamicAttrs"
```

```

    ],
    "enableEndSessionSSVRemoteToUDR": false
  },
  "common": {
    "enableHttp2": false,
    "requestTimeout": "1000",
    "enableConfigurableTimeout": false,
    "typeOfSearch": "Multi-UE ID Search",
    "dataCompressionScheme": "0",
    "enableFetchAndResubscribe": false
  },
  "audit": {
    "enable": true,
    "notificationRate": 50,
    "subscriberSessionAge": 1500,
    "subscriberSessionMaxAge": 2940,
    "subscriberMinAuditPassInterval": 10,
    "pdsProfileAge": 4500,
    "pdsProfileMaxAge": 8820,
    "pdsProfileMinAuditPassInterval": 10,
    "policyDataSubscriptionExpiry": {
      "policyDataSubsEnabled": false,
      "policyDataSubsPreExpiryPeriod": 180,
      "policyDataSubsExpiryAuditNotificationRate": 50,
      "policyDataSubsExpiryMaxAge": 50,
      "policyDataSubsExpiryMinAuditPassInterval": 10
    }
  },
  "advancedSettings": []
}

```

Sample Response body structure for GET and PUT operations:

```

{
  "remoteSSVRootPath": {
    "smPolicyData": [
      "string"
    ],
    "amPolicyData": [
      "string"
    ],
    "uePolicySet": [
      "string"
    ],
    "operatorSpecificData": [
      "string"
    ],
    "spendingLimitData": [
      "string"
    ],
    "enableEndSessionSSVRemoteToUDR": true
  },
  "common": {
    "preferenceOrder": [
      "SUPI"
    ]
  }
}

```

```

    ],
    "enableHttp2": true,
    "requestTimeout": "string",
    "enableConfigurableTimeout": true,
    "udrRequestTimeout": "string",
    "chfRequestTimeout": "string",
    "ldapRequestTimeout": "string",
    "ocsRequestTimeout": "string",
    "bulwarkRequestTimeout": "string",
    "preRequestTimeout": "string",
    "auditRequestTimeout": "string",
    "notificationRequestTimeout": "string",
    "enableFetchAndResubscribe": true,
    "sessionCountPerDnnList": [
      {
        "sst": "NA",
        "sd": "NA",
        "dnn":
"85zeTWLz5Bi.Xmke5NSG5dIH3KueRDwne4DASJFKMoXUuzikdHVYMLpGZ2xl3ALop.GfdccSS1RKU
M",
        "maxSessionsCount": 1
      }
    ],
    "dataCompressionScheme": "string"
  },
  "audit": {
    "enable": true,
    "notificationRate": 50,
    "subscriberSessionAge": 1500,
    "subscriberSessionMaxAge": 2940,
    "subscriberMinAuditPassInterval": 390,
    "pdsProfileAge": 4500,
    "pdsProfileMaxAge": 8820,
    "pdsProfileMinAuditPassInterval": 1170,
    "policyDataSubscriptionExpiry": {
      "policyDataSubsEnabled": true,
      "policyDataSubsPreExpiryPeriod": 180,
      "policyDataSubsExpiryAuditNotificationRate": 50,
      "policyDataSubsExpiryMaxAge": 50,
      "policyDataSubsExpiryMinAuditPassInterval": 10
    }
  },
  "advancedSettings": [
    {
      "key": "zHa1K1uC8LYRE2rPGohel.t@4nkah@Ze0r03pLUqRl.um3e2x9u$fccVg",
      "value": "string"
    }
  ]
}

```

For more information on the Advanced Settings "Keys" and "Values", see "**PDS settings**" section of "Configuring Policy Using CNC Console" in *Oracle Communications Cloud Native Core, Converged Policy User Guide*.

Export and Import PDS Settings

Table 2-454 Request and Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
date	string		Current timestamp
exportData	array	M	Exported list of PDS settings.
sourceVersion	string		System version of the product from which data is exported
topic	string	M	Topic of each managed object

Sample Request Body structure for Import and Export operations:

```
{
  "topic": "pds.public.settings",
  "sourceVersion": "26.1.200-nb-20260326",
  "date": "2026-03-31T05:30:54Z",
  "exportData": {
    "remoteSSVRootPath": {
      "smPolicyData": [
        "string"
      ],
      "amPolicyData": [
        "string"
      ],
      "uePolicySet": [
        "string"
      ],
      "operatorSpecificData": [
        "string"
      ],
      "spendingLimitData": [
        "string"
      ],
      "enableEndSessionSSVRemoteToUDR": true
    },
    "common": {
      "enableHttp2": true,
      "requestTimeout": "string",
      "enableConfigurableTimeout": true,
      "udrRequestTimeout": "string",
      "chfRequestTimeout": "string",
      "ldapRequestTimeout": "string",
      "ocsRequestTimeout": "string",
      "bulwarkRequestTimeout": "string",
      "preRequestTimeout": "string",
      "auditRequestTimeout": "string",
      "notificationRequestTimeout": "string",
      "typeOfSearch": "Multi-UE ID Search",

```

```

    "dataCompressionScheme": "string",
    "preferenceOrder": [
      "SUPI"
    ],
    "enableFetchAndResubscribe": true,
    "sessionCountPerDnnList": [
      {
        "sst": "NA",
        "sd": "C0eFAD5Ba6e68e6a0fECb84ca6D",
        "dnn": "zB4nl795zWX3gxYz9Ilq.YwXrrYhw2Apl6yZruNiw-LUKazqx.H",
        "maxSessionsCount": 1
      }
    ]
  },
  "audit": {
    "enable": true,
    "notificationRate": 50,
    "subscriberSessionAge": 1500,
    "subscriberSessionMaxAge": 2940,
    "subscriberMinAuditPassInterval": 390,
    "pdsProfileAge": 4500,
    "pdsProfileMaxAge": 8820,
    "pdsProfileMinAuditPassInterval": 1170,
    "policyDataSubscriptionExpiry": {
      "policyDataSubsEnabled": true,
      "policyDataSubsPreExpiryPeriod": 180,
      "policyDataSubsExpiryAuditNotificationRate": 50,
      "policyDataSubsExpiryMaxAge": 50,
      "policyDataSubsExpiryMinAuditPassInterval": 10
    }
  },
  "advancedSettings": [
    {
      "key":
"8+RW4&$z1G&GnSASgcsmo5pPt2ZRckILVG9lGbgFyvsxMMuRj+UGeoAr&89vCDH.rJsQaymm084dK
BX+d5mVA@PZIF",
      "value": "string"
    }
  ]
}

```

2.85 PDS Workflow

Table 2-455 Supported REST APIs

Description	HTTP Method or Custom Operation	Resource URI	Possible Result Code
Export PDS Workflows	GET	{apiRoot}/oc-cnpolicy-configuration/v1/services/pds/pdsWorkflow/export	See Table A-1

Table 2-455 (Cont.) Supported REST APIs

Description	HTTP Method or Custom Operation	Resource URI	Possible Result Code
Import PDS Workflows	POST	{apiRoot}/oc-cnpolicy-configuration/v1/services/pds/pdsWorkflow/import	See Table A-3
Get PDS Workflows	GET	{apiRoot}/oc-cnpolicy-configuration/v1/services/pds/pdsWorkflow	See Table A-1
Update PDS Workflows	PUT	{apiRoot}/oc-cnpolicy-configuration/v1/services/pds/pdsWorkflow	See Table A-2
Delete PDS Workflow	DELETE	{apiRoot}/oc-cnpolicy-configuration/v1/services/pds/pdsWorkflow	See Table A-4

Get and Update PDS Workflows

Table 2-456 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
workflows	boolean		Specifies the PDS workflow.
type	string		Specifies the PDS workflow type. The values can be chosen as: • Default - On selecting this option, the default PDS behavior applies. • Charging Profile selection based on User Profile - On selecting this option, you can configure whether to select user profile from LDAP or UDR. • Charging Profile selection based on Notification - On selecting this option, you can configure to select user profile based on Notification from UDR. • Datasource selection based on PRE - On selecting this option, you can configure to select datasource based on PRE. • Custom - For a custom workflow, contact Oracle Policy engineering team and paste the workflow in JSON format provided by the team.

Table 2-456 (Cont.) Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
subtype	string		On selecting the Charging Profile selection based on Notification workflow type, the Profile type can be selected as: • LDAP • UDR

Sample Request/Response body structure for GET and PUT operations:

```
{
  "workflows": {},
  "type": "string",
  "subtype": "string"
}
```

Export/Import PDS Workflows

Table 2-457 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
date	string		Current timestamp
exportData	array	M	Exported list of PDS Workflows.
sourceVersion	string		System version of the product from which data is exported
topic	string	M	Topic of each managed object

Sample Request Body structure for Import/Export operations:

```
{
  "topic": "string",
  "sourceVersion": "string",
  "date": "string",
  "exportData": {
    "workflows": {},
    "type": "string",
    "subtype": "string"
  }
}
```

2.86 Policy Engine

Table 2-458 Supported REST APIs

Description	HTTP Method or Custom Operation	Resource URI	Possible Result Code
Export Policy Engine	GET	{apiRoot}/oc-cnpolicy-configuration/v1/services/policyengine/export	See Table A-1
Import Policy Engine	POST	{apiRoot}/oc-cnpolicy-configuration/v1/services/policyengine/import	See Table A-3

Export/Import Policy Engine

Table 2-459 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/Optional(O)/Conditional(C)	Description
date	string		Current timestamp
exportData.loglevel	string		
exportData.supportedServices.relativeUrl	string		
exportData.supportedServices.serviceLabel	string		
exportData.supportedServices.serviceName	string		
sourceVersion	string		System version of the product from which data is exported
topic	string	M	Topic of each managed object

Sample Request Body structure for Import/Export operations:

```
{
  "date": "string",
  "exportData": {
    "logLevel": "WARN",
    "supportedServices": [
      {
        "relativeUrl": "string",
        "serviceLabel": "string",
        "serviceName": "string"
      }
    ]
  },
  "sourceVersion": "string",
```

```

    "topic": "string"
  }

```

2.87 NWDAF Agent

Table 2-460 Supported REST APIs

Description	HTTP Method or Custom Operation	Resource URI	Possible Result Code
Get NWDAF Agent Service configuration	GET	{apiRoot}/oc-cnpolicy-configuration/v1/services/nwdafAgent	See Table A-1
Update NWDAF Agent Service configuration	PUT	{apiRoot}/oc-cnpolicy-configuration/v1/services/nwdafAgent	See Table A-2
Export NWDAF Agent Service configuration	GET	{apiRoot}/oc-cnpolicy-configuration/v1/services/nwdafAgent/export	See Table A-1
Import NWDAF Agent Service configuration	POST	{apiRoot}/oc-cnpolicy-configuration/v1/services/nwdafAgent/import	See Table A-3
Create Autonomous Subscription	POST	{apiRoot}/oc-cnpolicy-configuration/v1/autonomousSubscription/sliceLoadLevel	See Table A-3
Get Autonomous Subscription	GET	{apiRoot}/oc-cnpolicy-configuration/v1/autonomousSubscription/sliceLoadLevel/{sliceLoad}	See Table A-1
Update Autonomous Subscription	PUT	{apiRoot}/oc-cnpolicy-configuration/v1/autonomousSubscription/sliceLoadLevel/{sliceLoad}	See Table A-2
Delete Autonomous Subscription	DELETE	{apiRoot}/oc-cnpolicy-configuration/v1/autonomousSubscription/sliceLoadLevel/{sliceLoad}	See Table A-4
Get All Autonomous Subscription	GET	{apiRoot}/oc-cnpolicy-configuration/v1/autonomousSubscription/sliceLoadLevel/export	See Table A-1
Import Autonomous Subscription	POST	{apiRoot}/oc-cnpolicy-configuration/v1/autonomousSubscription/sliceLoadLevel/import	See Table A-3

Get and Update NWDAF Agent

Table 2-461 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)	Description
advancedSettings	array	M	List of key/value pair

Table 2-462 SmAdvancedSettings

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
key	string	O	Specifies the key name.
value	string	O	Specifies the value of the key.

Sample Request body structure for GET and PUT operations:

```
{
  "advancedSettings": [
    {
      "key": "string",
      "value": "string"
    }
  ]
}
```

Export/Import Session Management Service

Table 2-463 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
date	String	O	Current timestamp
exportData.advancedSettings	array	O	List of key/value pair
exportData.advancedSettings.key	string	O	Specifies the key name
exportData.advancedSettings.value	string	O	Specifies the value of the key
sourceVersion	String	O	Version of the source
systemVersion	String	O	Version of the system
topic	String	M	

Sample Request Body structure for Import/Export operations:

```
{
  "date": "string",
  "exportData": {
```

```

    "advancedSettings": [
      {
        "key": "string",
        "value": "string"
      }
    ],
    "sourceVersion": "string",
    "systemVersion": "string",
    "topic": "string"
  }

```

Slice Load Level

Table 2-464 Get, Put, Post, and Update Slice Load Level

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
immRep	Boolean	O	Indication of immediate reporting
snssai	String	M	Identification of network slice to which the subscription applies.
threshold	Integer	M	Indication of slice load level in percentage

Sample Request body structure for GET and PUT operations:

```

{
  "immRep": true,
  "snssai": "string",
  "threshold": 0
}

```

Export/Import Slice Load Level

Table 2-465 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
Date	string	O	Current timestamp
Errors	array	O	List of errors
Errors.Message	string	O	Error message
Errors.Name	string	O	Name of the error
exportData	array	O	Exported list of session rule profiles.
exportData.immRep	Boolean	O	Indication of immediate reporting

Table 2-465 (Cont.) Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
exportData.snssai	String	O	Identification of network slice to which the subscription applies.
exportData.threshold	Integer	O	Indication of slice load level in percentage
sourceVersion	string	O	System version of product from which data is exported
topic	string	M	Topic of each managed object

Sample Request Body structure for Import/Export operations:

```
[
  {
    "date": "string",
    "errors": [
      {
        "message": "string",
        "name": "string"
      }
    ],
    "exportData": [
      {
        "immRep": true,
        "snssai": "string",
        "threshold": 0
      }
    ],
    "sourceVersion": "string",
    "topic": "string"
  }
]
```

2.88 Notifier Service

This section describes the APIs used to configure Notifier Service.

2.88.1 Notifier Configurations

This URI is used to configure the Notifier Service from CNC Console to send SMPP messages to external notification servers.

Table 2-466 Supported REST APIs that can be configured from CNC Console

Description	HTTP Method or Custom Operation	Resource URI
To update Notifier Service configuration	PUT	{apiRoot}/oc-cnpolicy-configuration/v1/services/notifier For details on Request/Response Body Parameters for PUT notify, see Table 2-467 .
To get individual Notifier Service configuration	GET	{apiRoot}/oc-cnpolicy-configuration/v1/services/notifier For details on Request/Response Body Parameters for GET smsGateway, see Table 2-467 .
To export Notifier Service configuration.	GET	{apiRoot}/oc-cnpolicy-configuration/v1/services/notifier / export
To import Notifier Service configuration.	POST	{apiRoot}/oc-cnpolicy-configuration/v1/services/notifier/import For details on Request/Response Body Parameters for POST smsGateway, see Table 2-467

Table 2-467 Request/Response Body Parameters for Notifier Configurations

Field Name	Data Type	Mandatory(M) / Optional(O) Conditional(C)	Description
smppConfiguration.isEnabled	string	M	Enables the Subscriber Notification using SMPP Protocol. Default Value: false
smppConfiguration.sourceAddress	string	O	ESME Source Address. By default this field is empty.
smppConfiguration.defaultSmsGatewayGroup	String	M	All the SMS Gateways that are created in SMS GATEWAY CONFIGURATION page.
smppConfiguration.connectTimeoutMillis	String	M	Indicates the SMS Gateway Connection Timeout in milliseconds. Range: 1-60000 Default Value: 30000
smppConfiguration.responseTimeoutMillis	String	M	Indicates the timeout (in milliseconds) for the response going towards SMS Gateway. Range: 1-60000 Default Value: 10000

Table 2-467 (Cont.) Request/Response Body Parameters for Notifier Configurations

Field Name	Data Type	Mandatory(M) / Optional(O) Conditional(C)	Description
smppConfiguration.sourceAddrTon	string	O	Indicates the ESME Source address type of number: - UNKNOWN - INTERNATIONAL - NATIONAL - NETWORK_SPECIFIC - SUBSCRIBER_NUMBER - ALPHANUMERIC - ABBREVIATED Default Value: UNKNOWN
smppConfiguration.sourceAddrNpi	String	O	ESME Source Address Number Plan Indicator: - UNKNOWN - ISDN (E163/E164) - DATA (X, 121) - TELEX - LAND_MOBILE - NATIONAL - PRIVATE - ERMES - INTERNET - WAP Default Value: UNKNOWN
advancedSettings			To configure the Keys and values for advanced settings.

Sample Request/Response body structure for PUT operation:

```
{
  "smppConfiguration": {
    "isEnabled": true,
    "sourceAddr": "3.3.2.2",
    "defaultSmsGatewayGroup": "gateway1",
    "connectTimeoutMillis": 30000,
    "responseTimeoutMillis": 10000,
    "sourceAddrTon": "UNKNOWN",
    "sourceAddrNpi": "UNKNOWN"
  },
  "advancedSettings": []
}
```

2.88.2 SMS Gateway

This URI is used to configure the SMS Gateway.

Table 2-468 Supported REST APIs to configure SMS Gateway

Description	HTTP Method or Custom Operation	Resource URI
To get the configuration of a particular SMS Gateway.	GET	{apiRoot}/oc-cnpolicy-configuration/v1/smsGateway/{smsGatewayName} Where <smsGatewayName> is the SMS Gateway name.
To delete the configuration of a particular SMS Gateway.	DELETE	{apiRoot}/oc-cnpolicy-configuration/v1/smsGateway/{smsGatewayName} Where <smsGatewayName> is the SMS Gateway name.
To update the configuration of a particular SMS Gateway.	PUT	{apiRoot}/oc-cnpolicy-configuration/v1/smsGateway/{smsGatewayName} Where <smsGatewayName> is the SMS Gateway name. For details on Request/Response Body Parameters for PUT smsGateway, see Table 2-469
To create a new SMS Gateway.	POST	{apiRoot}/oc-cnpolicy-configuration/v1/smsGateway For details on Request/Response Body Parameters for POST smsGateway, see Table 2-469
To export the list of all the SMS Gateways.	GET	{apiRoot}/oc-cnpolicy-configuration/v1/smsGateway/export
To import the list of all the SMS Gateways.	POST	{apiRoot}/oc-cnpolicy-configuration/v1/smsGateway/import For details on Request/Response Body Parameters for POST smsGateway.import, see Table 2-469

Table 2-469 Request/Response Body Parameters for PUT/POST operations on smsGateway

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
description	string	O	Free-form text that identifies the SMS Gateway server within the network. Enter up to 250 characters. By default, the value is left empty.

Table 2-469 (Cont.) Request/Response Body Parameters for PUT/POST operations on smsGateway

Field Name	Data Type	Mandatory(M)/Optional(O)/Conditional(C)	Description
name		M	Enter the name of the SMS Gateway server. The name can be lower case alphanumeric characters, '-' or '.', and must start and end with an alphanumeric character. By default, the value is left empty.
primarySmscHost		M	Enter the Host Name of the primary SMSC Host server. By default, the value is left empty.
requestDeliveryReceipt		O	Specify the mode of delivery receipt. This field accepts the following integer values: 0 to indicate REQUEST_DELIVERY_RECEIPT_NO 1 to indicate REQUEST_DELIVERY_RECEIPT_SUCCESS_FAILURE 2 to indicate REQUEST_DELIVERY_RECEIPT_FAILURE Default Value: 0
maxByteLength		O	Maximum number of bytes allowed for the message. The length of the message can range between 1 to 254 bytes. Default Value: 140
longMsgMaxByteLength		O	Maximum number of bytes allowed in a long message. The length of the message can range between 1 to 999 bytes. Default Value: 500
longMessageEnabled		M	Enables the long messages. Default Value: true
longMessageDeliveryMethod		M	Specify the long message delivery method. It can take the following integer values: 0 to indicate SEGMENTATION AND REASSEMBLY (SAR) to deliver the long messages in segments 1 to indicate the MESSAGE_PAYLOAD to deliver the long messages in payload Default Value: 0
truncateLongMessages		M	Indicates whether to truncate messages longer than the specified length. Default Value: false
failMaxMessageSize		M	Specifies the maximum length of the message after which the message fails. Default Value: true

Sample Request/Response body structure for PUT smsGateWay operation:

```
{
  "description": "testing",
  "name": "test",
  "primarySmscHost": "host_3",
  "requestDeliveryReceipt": 2,
  "maxByteLength": 140,
  "longMsgMaxByteLength": 500,
  "longMessageEnabled": true,
  "longMessageDeliveryMethod": 0,
  "truncateLongMessages": false,
  "failMaxMessageSize": true
}
```

Sample Request/Response body structure for POST smsGateWay.import operation:

```
{
  "topic": "common.notifierservice.msggateway",
  "sourceVersion": "1.6.0",
  "date": "2023-03-14T08:01:48Z",
  "exportData": [
    {
      "description": "testing",
      "name": "test",
      "primarySmscHost": "host_3",
      "requestDeliveryReceipt": 2,
      "maxByteLength": 140,
      "longMsgMaxByteLength": 500,
      "longMessageEnabled": true,
      "longMessageDeliveryMethod": 0,
      "truncateLongMessages": false,
      "failMaxMessageSize": true
    }
  ]
}
```

2.88.3 SMSC HOST Info

This URI is used to configure the SMSC Host.

Table 2-470 Supported REST APIs to configure SMS Gateway

Description	HTTP Method or Custom Operation	Resource URI
To get the SMSC Host name.	GET	{apiRoot}/oc-cnpolicy-configuration/v1/smscHostInfo/{smscHostName}
To delete the SMSC Host name.	DELETE	{apiRoot}/oc-cnpolicy-configuration/v1/smscHostInfo/{smscHostName}
To update the configuration of a particular SMSC Host.	PUT	{apiRoot}/oc-cnpolicy-configuration/v1/smscHostInfo/{smscHostName} For details on Request/Response Body Parameters for PUT smscHostInfo.smscHostName, see Table 2-471
To create a new SMSC Host.	POST	{apiRoot}/oc-cnpolicy-configuration/v1/smscHostInfo/{smscHostName} For details on Request/Response Body Parameters for POST smscHostInfo.smscHostName, see Table 2-471
To export the list of all the SMSC Hosts.	GET	{apiRoot}/oc-cnpolicy-configuration/v1/smscHostInfo/{export}
To import the list of all the SMSC Hosts.	POST	{apiRoot}/oc-cnpolicy-configuration/v1/smscHostInfo/{import} For details on Request/Response Body Parameters for POST smsHostInfo.import, see Table 2-471

Table 2-471 Request/Response Body Parameters for PUT/POST smscHostInfo.smscHostName.

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
name	string	M	Enter the name of the SMSC Host server. The name can be lower case alphanumeric characters, '-' or '.', and must start and end with an alphanumeric character. By default, the value is left empty.
host	String	M	Enter the Host Name of the SMSC server. The host can be Ipv4, Ipv6 or FQDN with optional port value. By default, the value is left empty.

**Table 2-471 (Cont.) Request/Response Body Parameters for PUT/POST
smscHostInfo.smscHostName.**

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
port	Integer	M	Enter the Port number of the SMSC server. Range: 0-65535 By default, the value is left empty.

Sample Request/Response body structure for PUT/POST operations:

```
{
  "name": "host_2",
  "host": "1.1.1.9",
  "port": 8002
}
```

Sample Request/Response body structure for POST operation to import the details:

```
{
  "topic": "common.notifierservice.smschost",
  "sourceVersion": "1.6.0",
  "date": "2023-03-15T13:21:02Z",
  "exportData": [
    {
      "name": "host_4",
      "host": "1.1.1.7",
      "port": "8000"
    }
  ]
}
```

2.89 Usage Monitoring

This section describes the APIs used to configure Usage Monitoring service.

2.89.1 Usage Monitoring Service

Table 2-472 Supported operations

HTTP Method or Custom Operation	Description	Resource URI
GET	Get Usage Monitoring Service	{apiRoot}/oc-cnpolicy-configuration/v1/services/pcfum For details on the Request/Response Body Parameters, see Table 2-473
PUT	Update Usage Monitoring Service	{apiRoot}/oc-cnpolicy-configuration/v1/services/pcfum For details on the Request/Response Body Parameters, see Table 2-473
POST	Import Usage Monitoring Service	{apiRoot}/oc-cnpolicy-configuration/v1/services/pcfum/import For details on the Request/Response Body Parameters, see Table 2-473
GET	Export Usage Monitoring Service	{apiRoot}/oc-cnpolicy-configuration/v1/services/pcfum/export For details on the Request/Response Body Parameters, see Table 2-473

Table 2-473 Request/Response Body Parameters for GET/PUT/POST operations

Field Name	Data Type	Mandatory(M)/Optional (O)/Conditional (C)	Description
enablePRE	Boolean	M	Indicates whether to enable or disable interaction with PRE for Policy evaluation as per the match list.
dataRolloverProfile	String	O	Indicates the default data rollover profile to use for UDR provided data limits for which rollover is applicable. That is, "Data Rollover" attribute is set to "true" and a separate "Data Rollover Profile" attribute is not provided.

Table 2-473 (Cont.) Request/Response Body Parameters for GET/PUT/POST operations

Field Name	Data Type	Mandatory(M)/ Optional (O)/ Conditional (C)	Description
enableQuotaMigration	String	O	Indicates whether 4G to 5G UDR Quota Data Migration is in progress. If so, Policy considers the custom attributes from 4G UDR for quota calculation and update. Default value: false Note: Disabling this flag while 4G to 5G Subscriber Data Migration is incomplete may result in Quota loss. It is recommended to not fallback to 4G PCRF once this flag is disabled as after this, the data provided to 4G PCRF may NOT be up to date.
reversePriority	String	O	Indicates the priority consideration order. When this flag is enabled: Higher number indicates lower priority When this flag is disabled: Higher number indicates higher priority Default value: true
enableProRatedQuota	String	O	Indicates whether pro-rated data calculation should be applied to the selected plan at a time of activation or not. Default value: false
enableProRatedQuotaForBillingDayChange	String	O	Indicates whether pro-rated data calculation should be applied to the selected plan at a time of billing day change. Default value: false

Table 2-473 (Cont.) Request/Response Body Parameters for GET/PUT/POST operations

Field Name	Data Type	Mandatory(M)/ Optional (O)/ Conditional (C)	Description
minimumVolumeGrant	Integer	M	Enter the minimum grant value (in bytes) that can be approved for volume based usage monitoring. If the grant value published by PRE is less than the value for this field, then Policy considers the minimum grant value out of the two. After deducting the current grant, if the remaining grant value is less than the minimum grant value, then the remaining grant is also added to the current grant. Default value: 2048 Range: 512 - 1048576 (1MB)
maximumVolumeGrant	Integer	M	Enter the maximum grant value (in bytes) that can be approved for volume based usage monitoring. If the grant value published by PRE is greater than the value for this field, then Policy considers the maximum grant value out of the two. Default value: 2048 Range: 1024 - 107374182400 (100 GB)

Table 2-473 (Cont.) Request/Response Body Parameters for GET/PUT/POST operations

Field Name	Data Type	Mandatory(M)/ Optional (O)/ Conditional (C)	Description
minimumTimeGrant	Integer	M	Enter the minimum grant value (in seconds) that can be approved for time based usage monitoring. If the grant value published by PRE is less than the value for this field, then Policy considers the minimum grant value out of the two. After deducting the current grant, if the remaining grant value is less than the minimum grant value, then the remaining grant is also added to the current grant. Default value: 300 Range: 30 - 3600 (1 hour)
maximumTimeGrant	Integer	M	Enter the maximum grant value (in seconds) that can be approved for time based usage monitoring. If the grant value published by PRE is greater than the value for this field, then Policy considers the maximum grant value out of the two. Default value: 300 Range: 60 - 86400 (1 hour)
inactivityTime	Integer	O	Enter the time interval (in seconds) during which if no packets are received for a given monitoring key, PGW or SMF stops measuring the time. Default value: 86400 Range: 0 - 604800 (7 Days)

Table 2-473 (Cont.) Request/Response Body Parameters for GET/PUT/POST operations

Field Name	Data Type	Mandatory(M)/ Optional (O)/ Conditional (C)	Description
usageAccumulationStart DateTime	Enumeration	O	Select the start time and date from when the Usage Monitoring service starts counting the usage reset periodicity. The values are: - Plan Start Date and Time: Counted from the plan start date and time as provisioned on the UDR. - Plan Activation Date and Time: Counted from the plan activation date and time as provisioned on the UDR. - Period Start Date and Time: Counted from the period start date and time.
applyBillingDay	String	O	Indicates if the flexible billing cycle option is enabled. The accepted values are: - Current Billing Cycle - Next Billing Cycle Default value: Next Billing Cycle

Table 2-473 (Cont.) Request/Response Body Parameters for GET/PUT/POST operations

Field Name	Data Type	Mandatory(M)/ Optional (O)/ Conditional (C)	Description
dataCompressionScheme	String	O	Used to configure the data compression in UmContext table. This flag accepts the following values: • Disabled: Indicates that the data will not be compressed and will be stored in the column in uncompressed format. The value of COMPRESSION_SCHEME for that row is set to the default value 0. • MySQL Compressed: Indicates that the data will be compressed using MySQL and will be stored in the column in compressed format. The value of COMPRESSION_SCHEME for that row is set to 1. • Application Compressed: Indicates that the data will be compressed using Zlib and will be stored in the column in compressed format. The value of COMPRESSION_SCHEME for that row is set to 2. Default value: Disabled When accessing the data from UmContext .v, the application determines the compression status based on the value of COMPRESSION_SCHEME and does the decompression accordingly.

Table 2-473 (Cont.) Request/Response Body Parameters for GET/PUT/POST operations

Field Name	Data Type	Mandatory(M)/ Optional (O)/ Conditional (C)	Description
			For more details on data compression, see <i>Usage Monitoring on Gx Interface in Oracle Communications Cloud Native Core, Converged Policy User Guide</i> .
weekStartDay	Enumeration	O	Enter the starting day of the week. Default value: Sunday
defaultVolumeGrant.grantVolumeSource	Enumeration	O	Note: This field becomes active when you select Grant Unit as Percent. Accepts one of the following values: - Initial Volume: Calculate grant volume from the initial volume. - Used Volume: Calculate grant volume from the used volume. - Remaining Volume: Calculate grant volume from the remaining volume. Default value: Initial Volume
defaultVolumeGrant.grantVolumeUnit	Enumeration	O	Accepts one of the following values: - Percent: Grant volume is calculated as a percentage. - Bytes: Grant volume is calculated as an absolute value. Default value: Percent

Table 2-473 (Cont.) Request/Response Body Parameters for GET/PUT/POST operations

Field Name	Data Type	Mandatory(M)/ Optional (O)/ Conditional (C)	Description
defaultVolumeGrant.grantVolumeValue	Integer	M	If Grant Unit is Percent: Enter the default Grant Volume in percentage, which is considered when PRE is not invoked or PRE does not return a decision. This value is applied to the Total Volume and divided equally among the Uplink and Downlink Volumes when available. Default value: 10 Range: 1-100 When the grant value is 0 and Grant is not calculated by PRE, then volume based Usage Monitoring is disabled for the session. If Grant Unit is Bytes: Enter the default Grant Volume in Bytes, which is considered when PRE is not invoked or PRE does not return a decision. This value is applied to the Total Volume and divided equally among the Uplink and Downlink Volumes when available. Default value: 2048 Range: 512 - 1048576 (1 MB) When the grant value is 0 and Grant is not calculated by PRE, then volume based Usage Monitoring is disabled for the session.

Table 2-473 (Cont.) Request/Response Body Parameters for GET/PUT/POST operations

Field Name	Data Type	Mandatory(M)/ Optional (O)/ Conditional (C)	Description
defaultTimeGrant.grantTimeSource	Enumeration	O	Note: This field becomes active when you select Grant Unit as Percent. Accepts one of the following values: - Initial Duration: Calculate grant time from the initial duration. - Used Duration: Calculate grant time from the used duration. - Remaining Duration: Calculate grant time from the remaining duration. Default value: Initial Volume
defaultTimeGrant.grantTimeUnit	Enumeration	O	Accepts one of the following values: - Percent: Grant time is calculated as a percentage. - Seconds: Grant time is calculated as an absolute value. Default value: Percent

Table 2-473 (Cont.) Request/Response Body Parameters for GET/PUT/POST operations

Field Name	Data Type	Mandatory(M)/ Optional (O)/ Conditional (C)	Description
defaultTimeGrant.grantTimeValue	Integer	M	If Grant Unit is Percent: Enter the default Grant time in percentage, which is considered when PRE is not invoked or PRE does not return a decision. Default value: 10 Range: 1-100 When the grant value is 0 and grant is not calculated by PRE, then time based Usage Monitoring is disabled for the session. If Grant Unit is Seconds: Enter the default Grant time in seconds, which is considered when PRE is not invoked or PRE does not return a decision. Default value: 3600 Range: 30 - 86400 (1 day) When the grant value is 0 and grant is not calculated by PRE, then time based Usage Monitoring is disabled for the session.
defaultUsageLevels.minorUsageLevel	Integer	M	Enter threshold value in percentage indicating minor usage. Default value: 50
defaultUsageLevels.majorUsageLevel	Integer	M	Enter threshold value in percentage indicating major usage. Default value: 75
defaultUsageLevels.criticalUsageLevel	Integer	M	Enter threshold value in percentage indicating critical usage. Default value: 95

Table 2-473 (Cont.) Request/Response Body Parameters for GET/PUT/POST operations

Field Name	Data Type	Mandatory(M)/ Optional (O)/ Conditional (C)	Description
defaultUsageLevels.exhaustedUsageLevel	Integer	M	Enter threshold value in percentage indicating usage level has exhausted allowed limit. Default value: 100
customAttributeMapping.resetDay	String	O	Enter a string identifying the custom attribute in UDR response that represents the usage reset day. Example: SmPolicyData/umDataLimits/{limitId}/billingDay
customAttributeMapping.dataPlanName	String	O	Maps the custom attribute available in the UDR provided data limit to name. A "name" associated with the data limit can be used in a Selection Profile to select the plan to apply when multiple active plans are found. Default value: SmPolicyData/umDataLimits/{limitId}/name
customAttributeMapping.dataPlanPriority	String	O	Maps the custom attribute available in the UDR provided data limit to priority. A "priority" associated with the data limit would help to select the plan to apply when multiple active plans are found. Possible values allowed in this field in UDR Data Limit are: any integer. Default value: SmPolicyData/umDataLimits/{limitId}/priority

Table 2-473 (Cont.) Request/Response Body Parameters for GET/PUT/POST operations

Field Name	Data Type	Mandatory(M)/ Optional (O)/ Conditional (C)	Description
customAttributeMapping .dataPlanType	String	O	Maps the custom attribute available in the UDR provided data limit to type. A "type" associated with the data limit would help to order the selection of the plan. Possible values allowed in this field in UDR Data Limit are: "base", "pass", "top-up". A separate configuration would order the selection, for example: Pass > Base Plan > Top-up. Default value: SmPolicyData/ umDataLimits/{limitId}/ type Default value to apply if this mapped attribute is absent: base The Plan Type, Priority within that Plan Type and the Selection Order of Plan Types together decide the order of selection of Data Plans.
customAttributeMapping .dataRollover	String	O	Maps the custom attribute available in the UDR provided data limit to indicate whether rollover is enabled for this data limit. Possible values allowed in this field in UDR Data Limit are: "true" and "false". Default value: SmPolicyData/ umDataLimits/{limitId}/ rollover Default value to apply if this mapped attribute is absent: false

Table 2-473 (Cont.) Request/Response Body Parameters for GET/PUT/POST operations

Field Name	Data Type	Mandatory(M)/ Optional (O)/ Conditional (C)	Description
customAttributeMapping .dataRolloverProfileLimit	String	O	Maps the custom attribute available in the UDR provided data limit to a pre-configured rollover profile. See "Data Rollover Profile" for more information. Possible values allowed in this field in UDR Data Limit are: A "Data Rollover Profile" name pre-configured on Policy. Default value: SmPolicyData/ umDataLimits/{limitId}/ rolloverProfile

Table 2-473 (Cont.) Request/Response Body Parameters for GET/PUT/POST operations

Field Name	Data Type	Mandatory(M)/Optional (O)/Conditional (C)	Description
conflictResolution.enableEtag	Boolean	O	Indicates if the ETag functionality is enabled or disabled between PDS and UDR. By default, this is disabled. Following scenarios may occur if it is enabled: - When the Usage Monitoring service sends a GET request for the first time, then PDS will fetch latest ETag details from UDR and update it in THE pdssubscriber table. - when the Usage Monitoring service sends PATCH request to PDS, PDS sends the request to UDR using if-match header. UDR matches the ETag of PDS with UDR. If it matches, then UDR replies with the latest ETag that gets updated on PDS. - If the If-Match headers fail, it means ETag on PDS does not match with UDR. UDR replies with 412 error response and based on the response code, Usage Monitoring service sends a force request to PDS to get the latest ETag from UDR and update it on PDS database.
conflictResolution.conflictRetryAttempt	Integer	O	Specifies the number of retry the Usage Monitoring service will do when if-match will fail on UDR.Default value: 5

Table 2-473 (Cont.) Request/Response Body Parameters for GET/PUT/POST operations

Field Name	Data Type	Mandatory(M)/ Optional (O)/ Conditional (C)	Description
dataLimitSelection.defaultDataLimitSelectionProfile	String	O	Indicates the default data limit selection profile to use while selecting a data limit among more than one active data limits provided by UDR.
dataLimitSelection.defaultDataLimitProfile	String	O	Indicates the default data limit profile to apply when no (usable) data limits were obtained from UDR and no (usable) data limits were applied by policy.
dataLimitSelection.defaultDataLimitSortProfile	String	O	Indicates the default data limit sorting profile to use while selecting a data limit among more than one active data limits provided by UDR.
dataLimitSelection.selectionOrder1	String	O	Selection Order determines the order/priority of selection of different types of plans. Default Value of Selection Order 1 : Pass
dataLimitSelection.selectionOrder2	String	O	Default Value of Selection Order 2 : Base Plan
dataLimitSelection.selectionOrder3	String	O	Default Value of Selection Order 3: Top-Up
audit.enable	Boolean	O	Used to enable or disable the Audit registration for Usage Monitoring service. When this field is enabled, Usage Monitoring sends registration request to Audit service. When this field is disabled, Usage Monitoring sends de-registration request to Audit service. Default value: true
audit.notificationRate	Integer	O	Indicates the number of stale records that Audit service notifies to Usage Monitoring service in one second.

Table 2-473 (Cont.) Request/Response Body Parameters for GET/PUT/POST operations

Field Name	Data Type	Mandatory(M)/ Optional (O)/ Conditional (C)	Description
audit.ttl	Integer	O	Indicates the age of a Usage Monitoring session, after which the session is considered to be stale and the PCRF Core service is queried for the presence of such associations. Note: This value should be higher than the Gx session audit.
audit.maxTtl	Integer	O	Indicates the maximum age of a UMPolicyAssociation, after which the session is purged from UMContext database without sending further queries. Note: This value should be higher than the Gx session audit.
audit.minAuditAttempts	Integer	O	Indicates the minimum number of queries to PCRF Core service before deleting a session.
audit.frequency	Integer	O	Defines the time when next audit for the Usage Monitoring service table is done after delta time if auditing this table has been finished before this specified time.

Table 2-474 MessageDefaultPriority

Field Name	Data Type	Mandatory(M)/ Optional (O)/ Conditional (C)	Description
umCreateAPI	Integer	O	Set request priority for UM session creation (CCR-I) request. Allowed Values: 0-31 Default Value: 20

Table 2-474 (Cont.) MessageDefaultPriority

Field Name	Data Type	Mandatory(M)/ Optional (O)/ Conditional (C)	Description
umUpdateAPI	Integer	O	Set request priority for UM session update (CCR-U) request. Allowed Values: 0-31 Default Value: 17
umTerminateAPI	Integer	O	Set request priority for UM session terminate (CCR-T) request. Allowed Values: 0-31 Default Value: 15
umNotifyAPI	Integer	O	Set request priority for UM session notification request. Allowed Values: 0-31 Default Value: 17
umSessionSearchSubscriberAPI	Integer	O	Set request priority for UM session search for subscriber request. Allowed Values: 0-31 Default Value: 30
umSessionAuditNotifyAPI	Integer	O	Set request priority for terminate session (CCR-T) request. Allowed Values: 0-31 Default Value: 31
umCongestionErrorCode	String	O	Configure the response code of the rejected messages by Usage Monitoring due to congestion state. By default, Usage Monitoring service sends 503 as response code. If configured then it shall be 5xx only. Allowed Values: 5xx Default Value: 503

Sample Request/Response body structure for GET operation:

```
{
  "enablePRE": false,
  "minimumVolumeGrant": 2048,
  "maximumVolumeGrant": 2048,
  "minimumTimeGrant": 300,
  "maximumTimeGrant": 300,
  "inactivityTime": 86400,
  "dataRolloverProfile": "string",
```

```

"enableQuotaMigration": "string",
"reversePriority": "string",
"enableProRatedQuota": "string",
"enableProRatedQuotaForBillingDayChange": "string",
"usageAccumulationStartDateTime": "PLAN_START",
"weekStartDay": "SUNDAY",
"applyBillingDay": "NEXT_BILLING_CYCLE",
"dataCompressionScheme": "0",
"defaultVolumeGrant": {
  "grantVolumeSource": "INITIAL_VOLUME",
  "grantVolumeUnit": "VOLUME_PERCENT",
  "grantVolumeValue": 0
},
"defaultTimeGrant": {
  "grantTimeSource": "INITIAL_DURATION",
  "grantTimeUnit": "TIME_PERCENT",
  "grantTimeValue": 0
},
"defaultUsageLevels": {
  "minorUsageLevel": 50,
  "majorUsageLevel": 75,
  "criticalUsageLevel": 95,
  "exhaustedUsageLevel": 100
},
"customAttributeMapping": {
  "resetDay": "SmPolicyData/umDataLimits/{limitId}/billingDay",
  "dataPlanName": "SmPolicyData/umDataLimits/{limitId}/name",
  "dataPlanPriority": "SmPolicyData/umDataLimits/{limitId}/priority",
  "dataRollover": "SmPolicyData/umDataLimits/{limitId}/rollover",
  "dataRolloverProfileLimit": "SmPolicyData/umDataLimits/{limitId}/
rolloverProfile",
  "dataPlanType": "SmPolicyData/umDataLimits/{limitId}/type"
},
"conflictResolution": {
  "enableEtag": true,
  "conflictRetryAttempt": 0
},
"dataLimitSelection": {
  "sortingRules": [
    {
      "index": 0,
      "parameterName": "RESET_PERIOD",
      "order": "ASC"
    }
  ],
  "selectionOrder1": "SELECTION_ORDER_BASE_PLAN",
  "selectionOrder2": "SELECTION_ORDER_BASE_PLAN",
  "selectionOrder3": "SELECTION_ORDER_BASE_PLAN",
  "selectionRules": [
    {
      "priority": 0,
      "limitIdentifier": "string",
      "conditions": [
        {
          "parameterName": "SERVING_NODE_LOCATION",
          "operator": "MATCH",

```



```

        "value": "string"
      }
    ]
  }
},
"defaultDataLimitSelectionProfile": "string",
"defaultDataLimitProfile": "string",
"defaultDataLimitSortProfile": "string"
},
"audit": {
  "enable": true,
  "notificationRate": 50,
  "ttl": 1440,
  "maxTtl": 7200,
  "frequency": 330,
  "minAuditAttempts": 5
},
"messageDefaultPriority": {
  "umCreateAPI": "20",
  "umUpdateAPI": "17",
  "umTerminateAPI": "15",
  "umNotifyAPI": "17",
  "umSessionSearchSubscriberAPI": "30",
  "umSessionAuditNotifyAPI": "31",
  "umCongestionErrorCode": "503"
},
"advancedSettings": [
  {
    "key": "string",
    "value": "string"
  }
]
}

```

For more information on the Advanced Settings "Keys" and "Values", see "**Configuring Usage Monitoring**" section of "Configuring Policy Using CNC Console" in *Oracle Communications Cloud Native Core, Converged Policy User Guide*.

2.89.2 Attribute Forwarding Profile

Table 2-475 Supported operations

HTTP Method or Custom Operation	Description	Resource URI
GET	Get Attribute Forwarding Profile	{apiRoot}/oc-cnpolicy-configuration/v1/services/common/attributeForwardingProfiles/{attributeForwardingProfileName} where <attributeForwardingProfileName> is the attribute forwarding profile name.

Table 2-475 (Cont.) Supported operations

HTTP Method or Custom Operation	Description	Resource URI
PUT	Update Attribute Forwarding Profile	{apiRoot}/oc-cnpolicy-configuration/v1/services/common/attributeForwardingProfiles/{attributeForwardingProfileName} where <attributeForwardingProfileName> is the attribute forwarding profile name.
DELETE	Delete Attribute Forwarding Profile	{apiRoot}/oc-cnpolicy-configuration/v1/services/common/attributeForwardingProfiles/{attributeForwardingProfileName} where <attributeForwardingProfileName> is the attribute forwarding profile name.
POST	Create Attribute Forwarding Profile	{apiRoot}/oc-cnpolicy-configuration/v1/services/common/attributeForwardingProfiles/ For details on the Request/Response Body Parameters, see Table 2-476 .
POST	Import Attribute Forwarding Profile	{apiRoot}/oc-cnpolicy-configuration/v1/services/common/attributeForwardingProfiles/import For details on the Request/Response Body Parameters, see Table 2-476 .
GET	Export Attribute Forwarding Profile	{apiRoot}/oc-cnpolicy-configuration/v1/services/common/attributeForwardingProfiles/export For details on the Request/Response Body Parameters, see Table 2-476 .

Table 2-476 Request/Response Body Parameters for GET and POST operations

Field Name	Data Type	Mandatory(M)/ Optional (O)/ Conditional (C)	Description
forwardedAttribute.attributeName	String	C	Name of the attribute.

Table 2-476 (Cont.) Request/Response Body Parameters for GET and POST operations

Field Name	Data Type	Mandatory(M)/ Optional (O)/ Conditional (C)	Description
forwardedAttribute.attributeSource	Enumeration	M	Source of the attribute to be forwarded. Attribute Source provides the following options: - Request Message: The incoming request message such as Gx CCR message or SM Policy Association Create message. - User Data: Data received from different data sources such as UDR and CHF. - Session Data: Data saved in the session (association) previously, such as saved APN/DNN value.
forwardedAttribute.attributeSelection	Enumeration	M	Attribute Selection can be: - Predefined - Custom
forwardedAttribute.predefinedAttributeLocation	String	C	This parameter can be filled when the Attribute Selection is of Predefined type. It indicates the path/location at which this attribute can be found by the source (forwarder) micro-service.
forwardedAttribute.attributeLocation	String	C	This parameter can be filled when the Attribute Selection is of Custom type. It indicates the path/location at which this attribute can be found by the source (forwarder) micro-service.

Sample Request/Response body structure for GET operation:

```
{
  "name": "string",
  "forwardedAttribute": [
```

```

    {
      "attributeName": "string",
      "attributeSource": "enter any one value from
[\"REQUEST\", \"UDR\", \"SESSION\"] ",
      "attributeSelection": "enter value from [\"PREDEFINED\", \"CUSTOM\"]",
      "predefinedAttributeLocation": "string",
      "attributeLocation": "string"
    }
  ]
}

```

2.89.3 UM Data Limit Selection Profile

Table 2-477 Supported Operations

HTTP Method or Custom Operation	Description	Resource URI
GET	Get Usage Monitoring Data Limit Selection Profile	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/usagemon/datalimitselectionprofiles/{umDataLimitSelectionProfileName} where <umDataLimitSelectionProfileName> is the Data Limit Selection profile name.
PUT	Update Usage Monitoring Data Limit Selection Profile	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/usagemon/datalimitselectionprofiles/{umDataLimitSelectionProfileName} where <umDataLimitSelectionProfileName> is the Data Limit Selection profile name.
DELETE	Delete Usage Monitoring Data Limit Selection Profile	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/usagemon/datalimitselectionprofiles/{umDataLimitSelectionProfileName} where <umDataLimitSelectionProfileName> is the Data Limit Selection profile name.
POST	Create Usage Monitoring Data Limit Selection Profile	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/usagemon/datalimitselectionprofiles For details on the Request/Response Body Parameters, see Table 2-478 .

Table 2-477 (Cont.) Supported Operations

HTTP Method or Custom Operation	Description	Resource URI
POST	Import Usage Monitoring Data Limit Selection Profile	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/usagemon/datalimitselectionprofiles/import For details on the Request/Response Body Parameters, see Table 2-478 .
GET	Export Usage Monitoring Data Limit Selection Profile	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/usagemon/datalimitselectionprofiles/export For details on the Request/Response Body Parameters, see Table 2-478 .

Table 2-478 Request/Response Body Parameters for GET operation

Field Name	Data Type	Mandatory(M)/Optional (O)/Conditional (C)	Description
name	String	M	Unique name to identify the Data Limit Selection Profile.
selectionRules.type	Enumeration	O	Indicates the selection rules type.
selectionRules.priority	Integer	M	Indicates the selection rule priority.
selectionRules.alwaysMatch	Boolean	M	When this is true, no conditions shall be evaluated. This can be used as a CATCH ALL Selection Rule. Default: False
selectionRules.dataLimitProfile	String	C	Uniquely identifies the UM Data Limit Profile by a name. This field is for configuration purpose only and not transmitted over the network.
selectionRules.limitIdentifier	String	C	Specifies the limit identifier. Multiple limit identifiers may have the same priority.
selectionRules.conditions	Object	M	

Table 2-478 (Cont.) Request/Response Body Parameters for GET operation

Field Name	Data Type	Mandatory(M)/ Optional (O)/ Conditional (C)	Description
selectionRules.condition s.parameterType			Indicates the type of parameter on which the condition will be applied. - Forwarded Attribute - An attribute forwarded by the core service, for e.g. Serving Gateway MCCMNC / IP Address, APN etc. - Policy Decision Tag - A Tag applied by the policy.
selectionRules.condition s.attributeName	String	C	This field is displayed when Parameter Type is "Forwarded Attribute".
selectionRules.condition s.operator			Accepts the following values: - Equals - Not Equals - Less Than - Greater Than - Matches
selectionRules.condition s.value	String		Displays the list of configured Match Lists when the Operator is "Matches".

Sample Request/Response body structure for GET operation:

```
{
  "name": "string",
  "selectionRules": [
    {
      "type": "DATA_LIMIT_PROFILE",
      "priority": 0,
      "alwaysMatch": true,
      "dataLimitProfile": "string",
      "limitIdentifier": "string",
      "conditions": [
        {
          "application": "Gx",
          "message": "CCR",
          "preDefinedAVPConditions": [
            {
              "conditionName": "CC-Request-Type",
              "conditionCSIDValue": [
                "5PuJi0lfDwxZihAhm6NDNp3rY7ikjSQ0zH.x0CSRJcJciVjiGvx7Iom880llacqa4nYh5Hjka8AT6GH5PX7lEvmEBk?N3H-7.S.-,3GBkb1pSVVDAPUUpkVc6pdLFV0JmRFVj9gsX?"
              ]
            }
          ]
        }
      ]
    }
  ]
}
```

19G200oWAuUz,pte7QohKf*D.ktAh7vnMv, EynrpYPQeH?EUuRKReKIKzkF,
YEUMYAUC9gPPdz4j6Y**j?BLP3Xa7CJsQZRUB5PdSBPsn2tsB6a-
sqJFU*dX89.wtQcLY.9AazpdxzYG0FTWxCGvm, 1a?dm?z5w2jrJyKG-
GZbVLzYufX.t,1oVj3QJbMK4Y*vLph?KhAsd7ruIAXTueMkvR940BhHAQuvrjJaIarfiY?
EsIIQSOsRL04,Q-AWRGLoHqn*2QEW3gMnUftB.pK,PvSQenBHhQCXX1LXa06DFScU?k9kZowN.YJj?
0, 0RDkmNRXEBVSw1M8-8EDltiNZC.McRX?6kFUHb?um0PMokL,09zwYjVPlz79CMcV7y-
*o*mbDcjpWQz,5dCwwVMVL.C07oLXnHHeMmovtGtJg0R1Mtb15E7ChzIq?
hd6sXVNs0xIPf8W2anEce3daMbokR,PjRd9Gp?yAest8tbPHqTiT?
6Hby*k6YoTIZ9c20ckZvoBBN,I780p0n5.olzVYArGFC-oc1G5, lID?
nm0FRiMgFswFZUruE1QV26oRPbuIQskynUrL.jwi9ZlBfI6lf.5DGKK.dDizZ0,LYG1?
JmHmlKoOQ.mWN1al.GhPtLkh340aUjcDN?er84neX07yoLFz-TfBL1vd0oR?
6Ss9fLohSegQotbN*n7Ry4tk0zaMaMXE, F0dwTd?
mfoi2KJgq5Soq4CMBJCPJh3*Bjz.I5iX9zJPnCK5sqA2I70qT9zINN?
MS7SBfcEU.65oDMKSLi9pXf, 9J.bxbhlzXS*uL,7zQxMU7-E0.UvSswCvehTx.zSdro?
iPUfjEIyx8aU0n3RUN58S7E*k0Bhdv7Pt?3G9l6gTR.lBb2EgyIpQV*h,XLqE?m*t1YlgeTb,
J9124-LKRRWOP,kfpW*4k?P8wT-cBowa,Dwj*Esm1m23.J0Gw1Ed-TQF*SSoVaEav?-
UqPFXV6nvArIUBnBzJMUqCQwMXDLcM,6vUUhJmyDW?vcnu, euBYyTo5IBxAG0vEya*WBDjnGiw?
NEqP*QIjoAjdoAjSKA,FdbezK3Cjy4tAHG0ra.7JRyuNT5yxP.vou214201aSy*YeYWhXad?.Vid*x
Ows44hAWT7JByXr4Af8sfvj48nLiGN, AKmPvd7EYo-N.mOYShwpTs-
Vi6UmxtL9u5tli*0b5RbyNUS,GpnM, LY*juuKhM9Sgu?jksAds3IS8.2Qzp,
C6BRbywARSHJb6ba4ml20DY.7LIVsKPCG8G.emPqN29sfXnuXAIi3*SL35CTGQp?q6E-
jZwe.45LZt4ILLYt68r*thkd8v32ot,7rQAjNHVB?
U0.o7YvNmkt0x.ciYr7Gj3xq700249ni1SSgauK-QCxCowcUW9Z.I1jfGzu8wpyeZYxQqvKaRhm?
17ua42r6A,XvLzXPbuf0ctdRw*w3s4B2x7Al*wVJJ9Ia?5k4xvdPKTGi,UZVg-
ru6HaNWMSl816b5xHTjg068kdRGT1TaS1Zt1XZ.G20huosmClCYURb,
4qGLNr6Ta.95ralc46qHwLHQSwFwTtQnAD13LW.4*7WDQnk,
tyIXQuZ610fA*tNRMQg,iUB0Nvd8LPxmR1M, 5GLY.9.fGiWcl-
mnubYWUOVKxta,Ut5EY8hyPckHzCUL09c54Bx-Vp3s0I0PTJujddv*nNAPG?hhXb-
lB.Ft02LEH4SknKOWT-44rkVkyZF3msz4oskJpwARCCec1, *nY.qw?WeL,
j*S9zMJHwvpsdPoV.46dW044eIwNyYT7YzQXaSt1q-
f1IRNy0uGC4fPPQg.U0BzVkiqC0IcDI2r8ME09haDGB6EU, XNZAJ.HivrB0tMr3LFvCOKIyN?
tXayw-CCS*PEg,
IwQnNRcICfUnAnIidRhj,ES3eJo2*3xhNc6lJRv*51Ho0RhDPCpdVgJ.IUV*jpgMLVzkVT4oeR?
5tH0n-F,XtoBTW8j90sZWf36kV6VFxe,qdLVk6SEDSegGunGEZhvuLLf01L8.?
ADZ0o*OrfCUIzJefu5j4LMjGheNtnjgh4B5,A2LKDqSkT3DkXVbJu5Q8YQhEESjSKCmR,1F8TLHDG4
BAVnq5*anQpC5tK7hHy.I*Pftn4UZuE0j, a, v4zUGHixr.r*St16Xncs3QKFIAU.T,nCt-4uF,
PhRFYU8G4Nc7VHJpvFQEXLMA7sQL4ls-nkFtMuBjMX0*6V.?P6Xg, .yJbwc-2P8T-,-
FAlpkvcmBATTv88nK.10uJNuQeglkE4xqs,JryE0c-
SmixRXk3GJfPf,*cN.Zr6n3IlckTnLlnIaQ.ysiquptvniG0r0ZpSjpBVYK?7u.E-
JKWAhvH8nMrZC6nhVpGpmnnvsHzz.qfQ0JIdsdthm6YLuSZ, 1i7jHTDyNSj-
T90.mT3egbaVBr*n8-eZVeUfhavn.yELKjBEPsuygrH93pZnZsLXlxcI4afvV1jw8po0lt,0f,
i7YK68T6dqZ6j*WbK6zgPQ73ARnPP01cN0, XvUUiwH00?9?
Rz4Hp4UCE9gxHnGy,dWaT7*5ibyG,Jq6MZk8PQzR0LJl5mWhiAndpb8rhy8cPemL7PF?
OPyhFDJdI,Dbh1?*zybcqAmBg9-E4PzG0.oSRraGwv11ND-0Y?dhVgaUj6VJpnHk6N, N?
p7AXv.-8mA6JfG-yc15tnHhgyPBCpMBc1S0,yFPLmHFhQCTKy4TMwbyD8FvwC6bIYNDZdNLF62?
5Zy5L,qX..0-
ommdbaAPmD9kint6SdjIPrblI2,yw1--71B0eSjY6jGNpNR8FNR91rLMch7oZgetxM*gtK,
1CyvRijp,9p0LA,ESEfBchgXXx1b0KkIV7A55J4mNlcIDaTwZUXqrpiG-sMMG6cxhk6T-
otFghPnd4,A-JAshdlc4.yJP*XuyZHOldrCnf, HhsPiLy?NmixbpEx-6Hf1s6du7UEpFV?
CFVv3PupWL*bllQk4L454d-zm4xWkaVGWqbtQVqfAY3t4mFxtVCQbvPh2uffhfe,
ZrbXhJTz5IFnm26BTIcpB,FPsCxBP9mNmWT?bySieohK0YR?
Fp7hXIobGruyPKzTkNvFKVvVamb73V7?sJ7NTLiGSr2L4xIt5saE1p.AKW.P,W1WfcshFbi?
cT3Khh-
wiziCS5fz4nZd2uWnd-1FSd1rcJoIB5vnTkcQjQJ9z29y.MH8K0f6Yq,zAWXxKnF5yXSX8iFpqz4jn
J1if?*N6LncXDTs6Z, -TShlFXHvYol786*39e3o9?425Q,
0CzKiUXp5N7FtBLEbn8pxdL1DDjgK,JmzzXR7RfG.qE8bidWw07PayykvzcvHH3kyfPbY6xMUGLwtH

```

938qQ3t6t0GGvz15ZCWR?kUC?Kcu10j?YXkA3,R3gxDFWiEb4ITqFSEw, E5RBdIP,
dJM9GsKtsUZlILub2005*UAN7c-
BIEczWwGKz0a2zfr7tySHmcxbXRM9Tex3gdv6utZwUCkrVji8pj950UwM07vprAU"
    ],
    "conditionCCRTValue": "UPDATE_REQUEST",
    "conditionRxRTValue": [
        "INITIAL_REQUEST"
    ],
    "conditionServiceURNIDValue": [
        "r,Vnj9p.MZlxvBFiLr*YRHT0xCfC*Y*kGmw-kB-8j1JqfnDcgqkfeKHFN1-
GdHS4fvPx*AX5EagP4Xvx0Q2w*dBJrOpT5V, hF847pVFbHqx*yMYr7svKCj2TC?utLpLemQsq?
Ikm0AINKaYbcr0zyZb3AZX?W-i.dnbl7iY80Wvd2.vL1V-5,NBBoxA-
MTK67f9wQ2HDnNsizzFCD8lqH.T,jMurIbEhksKqTZkiaNWodBq8rTw9tBmRVJGeafW?
BjsKNUoM4*F4R-o?, oi-J*D.Bj?JAv0puz0A2ESszsijiU6A-
z2vHqpecCqzKCUsRlToqsNc893aVA.ew3P0fG,H5P*BMKAhUpwTrtYHw0C3.?-
hbGuJ0SwwmDl6hKgc, 2a*xOi56aFNLcDPndiz,
w3QBy95lwZe0c*TJw.2B7lG9L2um0sE59cToEvuu0SUNLMX4rKaPMqT6*.*VrN*XF,
oUQYzJEEpZSPtmCWU-Ykowuh,jMcmrcRw-nRrBlu7Ci-EDqWw*?wjgbL-
W2ODRfUXW*iIcIFKJwhuW0jk4p10lJYf03m*7THq4GsdjhF-
QNHYv,7jaCi70sg.XPXsqne9d,3J1Rl*-dfTT4m8?E.D.eYb4h8y*jqmYhblDv08HSF-
T13eXUqOi0KBEvE--rMN,bo?H09Iy--
wXkBktsx9GB0WZFBcvfGFhUHADsi.lOLRKVBuIVaqQMm6i700feaUpMpFtaiVDw11K??0r8I.r?
stWQ4U,cxKXwGZSZhclPy?XlZQGwGxkyhu1bKm9VXDj5nmAACInhZgk, 3ekMCjB..re2u4?
2Dj0yoCNz0J0SJ0eemy9cUPVJx9y7ION8YTvThy7wPsPKQSZvmZe-Ba9bQ*k,mExi2kiTTTtVbNid-
m9jZkH0e5bcR?I2ICD7qvUwlbMLRg1*6pw.MwB5wwX0K8bnoA6LFXd0JfzS7Rmz-
l3wIbjjAFg53U,?RXQ8lQ6LyNVfCut-
WX9eadTgpW1iQy*a3ZtL5l7JJrVDsK7gB980Wj8Mxs9kuRUV,VQVRh0iRHPf21c2HoL1J7uqNQVpfX
JgL?4lM2KhbIHajKxfvbsV.v5UD8Cl,
vEDZjr9N3PW3DgUgnwlsfpIE8dSv5lrFTYcmfm5xY4HISpgvLcwo0nR*9yj.,Vja26gB7J0A3N,OBM
eELFhseaZ4bvRWizJeUoc3t4YSo., 3zDXsJ3p8uX7WC?LmYfdo6y, GHoE?
2EVniTNRmeaPL7*gnzv3voUCRCJ64xepuMWQDbA5GGyTfQ4ZB?ekWUNsw"
    ],
    "conditionMPSIdValue": [
        "string"
    ],
    "conditionMCPTTIdValue": [
        "string"
    ],
    "conditionMCVideoIdValue": [
        "string"
    ],
    "conditionReservPriorityValue": [
        "string"
    ],
    "conditionSNRTypeValue": [
        "ABORT_SESSION_REQUEST"
    ]
}
}
}
}
},
"sortingRules": [
    {
        "index": 0,

```



```

        "parameterType": "START_DATE",
        "attributeName": "string",
        "order": "string"
    }
]
}

```

2.89.4 UM Data Limit Profile

Table 2-479 Supported operations

HTTP Method or Custom Operation	Description	Resource URI
GET	Get Usage Monitoring Data Limit Profile	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/usagemon/datalimitprofiles/{umDataLimitProfileName} where <umDataLimitProfileName> is the Data Limit profile name.
PUT	Update Usage Monitoring Data Limit Profile	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/usagemon/datalimitprofiles/{umDataLimitProfileName} where <umDataLimitProfileName> is the Data Limit profile name.
DELETE	Delete Usage Monitoring Data Limit Profile	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/usagemon/datalimitprofiles/{umDataLimitProfileName} where <umDataLimitProfileName> is the Data Limit profile name.
POST	Create Usage Monitoring Data Limit Profile	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/usagemon/datalimitprofiles For details on the Request/Response Body Parameters, see Table 2-480 .
POST	Import Usage Monitoring Data Limit Profile	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/usagemon/datalimitprofiles/import For details on the Request/Response Body Parameters, see Table 2-480 .
GET	Export Usage Monitoring Data Limit Profile	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/usagemon/datalimitprofiles/export For details on the Request/Response Body Parameters, see Table 2-480 .

Table 2-480 Request/Response Body Parameters for GET and POST operations

Field Name	Data Type	Mandatory(M)/ Optional (O)/ Conditional (C)	Description
name	String	M	Uniquely identifies the UM Data Limit Profile by a name. This field is for configuration purpose only and not transmitted over the network.
limitId	String	O	Specifies the limit identifier. Multiple limit identifiers may have the same priority.
monitoringKey	String	O	Uniquely identifies the UM Data Limit Profile by a Monitoring Key. If its value is not explicitly provided, then the data limit profile's limitId will be used as the monitoring Key of that profile.
priority	Integer	O	A Priority to weigh it with other Data Limit Profiles and/or UDR provisioned Data Limits of the same Plan Type. The priority can be used by Policy or Data Limit Selection Profile for choosing among different candidate profiles. The Plan Type, Priority within that Plan Type and the Selection Order of Plan Types together decide the order of selection of Data Plans.
validityDuration	Integer	O	Indicates the length of usage time in seconds. Range: 3600 - 31536000 (1 Year) Note: Validity Duration is applicable only for plans, which has Periodicity as NEVER. There is no validity for the recurring plans.

Table 2-480 (Cont.) Request/Response Body Parameters for GET and POST operations

Field Name	Data Type	Mandatory(M)/ Optional (O)/ Conditional (C)	Description
inactivityTime	Integer	O	Enter the time interval (in seconds) during which if no packets are received for a given monitoring key, PGW or SMF stops measuring the time. Default value: 86400 Range: 0 - 604800 (7 Days)
dataRolloverProfile	String	O	A reference to a Data Rollover Profile. If not configured, Data Rollover will be disabled for this Data Plan.
allowExcessUsage	Boolean	O	Indicates whether or not excess usage is allowed for this Data Limit Profile. When Excess Usage is allowed, Usage Monitoring shall continue to grant and accumulate usage even after consuming 100% of allocated volume/time. The QoS, Charging etc. parameters can be controlled at PCRF Core Policy on account of the consumed usage. Default value: False
umLevel	Enumeration	M	Indicates the level of the usage monitoring instance (PDU Session level or per Service). Default value: Session Level
profileType	Enumeration	M	Type of the Data Limit Profile. Default value: SUBSCRIBER Note: Striked-out entries are for future.

Table 2-480 (Cont.) Request/Response Body Parameters for GET and POST operations

Field Name	Data Type	Mandatory(M)/ Optional (O)/ Conditional (C)	Description
planType	Enumeration	M	Type of the Plan such as Base, Top-up, and Pass. This help to determine the priority in selecting the plan over other types. The priority is configurable in service configuration screen. Default value: Base
parentPlan	String	O	Identifies a Data Limit Profile as a parent data plan. Any attribute that is not explicitly configured in this plan shall be taken from the parent plan (if present). Note: Parent Plan cannot be the same as the Profile Name .
usageLimit.duration	Integer	O	Indicates the length of time in seconds. Range: 3600- 2592000
usageLimit.totalVolume	Integer	O	Specifies the total data octets for both downlink and uplink. Range: 512 - 1000000000000
usageLimit.uplinkVolume	Integer	O	Specifies the uplink data octets. Range: 512 - 1000000000000; 512 - 1000000000000
usageLimit.downlinkVolume	Integer	O	Specifies the downlink data octets. Range: 512 - 1000000000000
resetPeriod.period	Enumeration	O	Indicates whether the periodicity is "YEARLY", "MONTHLY", "WEEKLY", "DAILY" or "HOURLY". Default value: Monthly
resetPeriod.maximumNumberOfPeriods	Integer	O	Indicates the maximum number of periods after which the usage monitoring instance does not apply. If omitted, there is no limit in the number of periods.

Table 2-480 (Cont.) Request/Response Body Parameters for GET and POST operations

Field Name	Data Type	Mandatory(M)/ Optional (O)/ Conditional (C)	Description
BillingDay.type	String	O	Indicates which day of the period to reset the usage limit. Default value: LAST_DAY Note: If this configuration is updated, the new configuration shall be applied in the next billing cycle.
BillingDay.day	Integer	O	Indicates the specific day of the period. Day count starts from 1. If the Day entered is beyond the last day of a period (for example 31 for the month of April), the last day shall be considered. Required when "SPECIFIC_DAY" is selected in the Type field. Note: If this configuration is updated, the new configuration shall be applied in the next billing cycle.
BillingDay.time	String	O	Indicates the specific time of day in "HH:MM:SS". Default value: "00:00:00" Note: If this configuration is updated, the new configuration shall be applied in the next billing cycle.
excessUsageLimit.percentage	Integer	O	Indicates the percentage of base volume/time up to which excess usage is allowed. Range: 100 - 1500 Note: If all the Excess Usage Limit fields are left empty, the grant shall continue indefinitely.

Table 2-480 (Cont.) Request/Response Body Parameters for GET and POST operations

Field Name	Data Type	Mandatory(M)/ Optional (O)/ Conditional (C)	Description
excessUsageLimit.duration	Integer	O	Indicates the length of time in seconds. This is inclusive of the base duration. That is the value in this field indicates the total duration to be consumed including base + excess. Range: 3600 - 31536000 (1 Year) Note: If all the Excess Usage Limit fields are left empty, the grant shall continue indefinitely.
excessUsageLimit.volumeTotal	Integer	O	Total data octets for both downlink and uplink. This is inclusive of the base total volume. Range: 512 - 1073741824000 (1000 GB) Note: If all the Excess Usage Limit fields are left empty, the grant shall continue indefinitely.
excessUsageLimit.volumeUplink	Integer	O	Uplink data octets. This is inclusive of the base uplink volume. Range: 512 - 1073741824000 (1000 GB) Note: If all the Excess Usage Limit fields are left empty, the grant shall continue indefinitely.
excessUsageLimit.volumeDownlink	Integer	O	Downlink data octets. This is inclusive of the base downlink volume. Range: 512 - 1073741824000 (1000 GB) Note: If all the Excess Usage Limit fields are left empty, the grant shall continue indefinitely.

Sample Request/Response body structure for GET operation:

```
{
  "name": "string",
```

```

    "limitId": "string",
    "monitoringKey": "string",
    "priority": "string",
    "validityDuration": 3600,
    "inactivityTime": "86400",
    "allowExcessUsage": false,
    "umLevel": "SESSION_LEVEL",
    "profileType": "SUBSCRIBER",
    "type": "base",
    "usageLimit": {
      "duration": 3600,
      "totalVolume": 512,
      "uplinkVolume": 512,
      "downlinkVolume": 512
    },
    "resetPeriod": {
      "period": "MONTHLY"
    },
    "resetDay": {
      "type": "LAST_DAY",
      "day": 0,
      "time": "00:00:00"
    },
    "excessUsageLimit": {
      "percentage": 100,
      "duration": 3600,
      "volumeTotal": 512,
      "volumeUplink": 512,
      "volumeDownlink": 512
    }
  }
}

```

2.89.5 Data Limit Sorting Profile

Table 2-481 Supported operations

HTTP Method or Custom Operation	Description	Resource URI
GET	Get Data Limit Sorting Profile	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/usagemon/dataLimitSortingProfiles/{dataLimitSortingProfileName} where <dataLimitSortingProfileName> is the Data Limit Sorting profile name.

Table 2-481 (Cont.) Supported operations

HTTP Method or Custom Operation	Description	Resource URI
PUT	Update Data Limit Sorting Profile	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/usagemon/dataLimitSortingProfiles/{dataLimitSortingProfileName} where <dataLimitSortingProfileName> is the Data Limit Sorting profile name.
DELETE	Delete Data Limit Sorting Profile	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/usagemon/dataLimitSortingProfiles/{dataLimitSortingProfileName} where <dataLimitSortingProfileName> is the Data Limit Sorting profile name.
POST	Create Data Limit Sorting Profile	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/usagemon/dataLimitSortingProfiles For details on the Request/Response Body Parameters, see Table 2-482 .
POST	Import Data Limit Sorting Profile	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/usagemon/dataLimitSortingProfiles/import For details on the Request/Response Body Parameters, see Table 2-482 .
GET	Export Data Limit Sorting Profile	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/usagemon/dataLimitSortingProfiles/export For details on the Request/Response Body Parameters, see Table 2-482 .

Table 2-482 Request/Response Body Parameters for GET and POST operations

Field Name	Data Type	Mandatory(M)/ Optional (O)/ Conditional (C)	Description
name	String	M	A name to uniquely identify the Data Limit Selection Profile.
sortingRules.index	Integer	M	Specifies the index. The sorting rules are applied in the order of index.

Table 2-482 (Cont.) Request/Response Body Parameters for GET and POST operations

Field Name	Data Type	Mandatory(M)/ Optional (O)/ Conditional (C)	Description
sortingRules.parameter Type	String	O	Specifies the type of the parameter. Possible values are: - Start Date - End Date - Priority - Periodicity - Data Limit Custom Attributes
sortingRules.attributeNa me	String	C	Specifies the name of the attribute. It is displayed when the value of Parameter Type is set to Data Limit Custom Attributes .
sortingRules.order	String	O	Specifies the order. Possible values are: - ASC - DSC

Sample Request/Response body structure for GET operation:

```
{
  "name": "string",
  "sortingRules": [
    {
      "index": 0,
      "parameterType": "START_DATE",
      "attributeName": "string",
      "order": "string"
    }
  ]
}
```

2.89.6 Data Rollover Profile

Table 2-483 Supported operations

HTTP Method or Custom Operation	Description	Resource URI
GET	Get Data Rollover Profile	{apiRoot}/oc-cnpolicy- configuration/v1/policydata/ usagemon/dataRolloverProfiles/ {dataRolloverProfileName} where <dataRolloverProfileName> is the Data Rollover profile name.

Table 2-483 (Cont.) Supported operations

HTTP Method or Custom Operation	Description	Resource URI
PUT	Update Data Rollover Profile	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/usagemon/dataRolloverProfiles/{dataRolloverProfileName} where <dataRolloverProfileName> is the Data Rollover profile name.
DELETE	Delete Data Rollover Profile	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/usagemon/dataRolloverProfiles/{dataRolloverProfileName} where <dataRolloverProfileName> is the Data Rollover profile name.
POST	Create Data Rollover Profile	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/usagemon/dataRolloverProfile For details on the Request/Response Body Parameters, see Table 2-484 .
POST	Import Data Rollover Profile	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/usagemon/dataRolloverProfiles/import For details on the Request/Response Body Parameters, see Table 2-484 .
GET	Export Data Rollover Profile	{apiRoot}/oc-cnpolicy-configuration/v1/policydata/usagemon/dataRolloverProfiles/export For details on the Request/Response Body Parameters, see Table 2-484 .

Table 2-484 Request/Response Body Parameters for GET and POST operations

Field Name	Data Type	Mandatory(M)/Optional (O)/Conditional (C)	Description
name	String	M	Uniquely identifies the Data Rollover Profile by a name.
dataRolloverEnabled	Boolean	M	Indicates whether to enable or disable the data rollover.
rolloverDataConsumption	Enumeration	M	Indicates when to consume the rollover data.

Table 2-484 (Cont.) Request/Response Body Parameters for GET and POST operations

Field Name	Data Type	Mandatory(M)/ Optional (O)/ Conditional (C)	Description
maximumNumberOfRoll overs	Integer	M	Indicates how many cycles the data plan can rollover. A value of 0 means there is not limit to the number of cycles the left over data can rollover. Range: 0 to 24 Default value: 0 (No limit)
dataRolloverPercentage	Integer	M	This field indicates the percentage of left over data volume/time to rollover to the next cycle. Range: 0 to 100 Default value: 100.
rolloverCap	Boolean	M	Indicates whether to enable or disable a cap (maximum limit) on the total data volume/time to be allotted for the next billing cycle or period. The maximum cap shall be applied on the total of base plan volume/time and total accumulated rolled over volume/time.
maximunRolloverThresh old.baseDataPercentage	Integer	O	Indicates the percentage of base plan data volume/time that is allowed as rollover data volume/time. Range: 0 to 100
maximunRolloverThresh old.maximunDurationThr eshold	Integer	O	Indicates the length of time in seconds. Range: 3600 - 2592000 (30 Days)
maximunRolloverThresh old.maximunVolumeTotal Threshold	Integer	O	Total data octets for both downlink and uplink. Range: 512 - 107374182400 (100 GB)
maximunRolloverThresh old.maximunVolumeUpli nkThreshold	Integer	O	Uplink data octets. Range: 512 - 107374182400 (100 GB)
maximunRolloverThresh old.maximunVolumeDow nlinkThreshold	Integer	O	Downlink data octets. Range: 512 - 107374182400 (100 GB)

Table 2-484 (Cont.) Request/Response Body Parameters for GET and POST operations

Field Name	Data Type	Mandatory(M)/ Optional (O)/ Conditional (C)	Description
minimunRolloverThresho Id.minimunDurationThre shold	Integer	O	Indicates the length of time in seconds. The remaining duration if applicable shall be rolled over to the next period if it is greater than the threshold value configured here. Range: 0 - 2592000 (30 Days)
minimunRolloverThresho Id.minimunVolumeTotalT hreshold	Integer	O	Total data octets for both downlink and uplink. The remaining total volume if applicable shall be rolled over to the next period if it is greater than the threshold value configured here. Range: 0 - 107374182400 (100 GB)
minimunRolloverThresho Id.minimunVolumeUplink Threshold	Integer	O	Uplink data octets. The remaining uplink volume if applicable shall be rolled over to the next period if it is greater than the threshold value configured here. Range: 0 - 107374182400 (100 GB)
minimunRolloverThresho Id.minimunVolumeDownli nkThreshold	Integer	O	Downlink data octets. The remaining downlink volume if applicable shall be rolled over to the next period if it is greater than the threshold value configured here. Range: 0 - 107374182400 (100 GB)
rolloverCapSettings.dura tion	Integer	C	Indicates the length of time in seconds. Range: 3600 - 2592000 (30 Days)
rolloverCapSettings.volu meTotal	Integer	C	Total data octets for both downlink and uplink. Range: 512 - 107374182400 (100 GB)
rolloverCapSettings.volu meUplink	Integer	C	Uplink data octets. Range: 512 - 107374182400 (100 GB)

Table 2-484 (Cont.) Request/Response Body Parameters for GET and POST operations

Field Name	Data Type	Mandatory(M)/ Optional (O)/ Conditional (C)	Description
rolloverCapSettings.volumeDownlink	Integer	C	Downlink data octets. Range: 512 - 107374182400 (100 GB)

Sample Request/Response body structure for GET operation:

```
{
  "name": "string",
  "dataRolloverEnabled": true,
  "rolloverDataConsumption": "BEFORE_PARENT_PLAN",
  "maximumNumberOfRollovers": 0,
  "dataRolloverPercentage": 0,
  "rolloverCap": true,
  "maximumRolloverThreshold": {
    "baseDataPercentage": 100,
    "maximumDurationThreshold": 2592000,
    "maximumVolumeTotalThreshold": 107374182400,
    "maximumVolumeUplinkThreshold": 107374182400,
    "maximumVolumeDownlinkThreshold": 107374182400
  },
  "minimumRolloverThreshold": {
    "minimumDurationThreshold": 2592000,
    "minimumVolumeTotalThreshold": 107374182400,
    "minimumVolumeUplinkThreshold": 107374182400,
    "minimumVolumeDownlinkThreshold": 107374182400
  },
  "rolloverCapSettings": {
    "duration": 2592000,
    "volumeTotal": 107374182400,
    "volumeUplink": 107374182400,
    "volumeDownlink": 107374182400
  }
}
```

2.90 Rx Reauth Profiles

Table 2-485 Supported REST APIs - Rx Reauth Profiles

Description	HTTP Method or Custom Operation	Resource URI	Possible Result Code
Create Rx Reauth Profile	POST	/oc-cnpolicy-configuration/v1/services/common/rx-reauth-profiles	See Table A-3

Table 2-485 (Cont.) Supported REST APIs - Rx Reauth Profiles

Description	HTTP Method or Custom Operation	Resource URI	Possible Result Code
Get Rx Reauth Profile	GET	{apiRoot}/oc-cnpolicy-configuration/v1/services/common/rx-reauth-profiles/{rxReauthProfileName}	See Table A-1
Update Rx Reauth Profile	PUT	{apiRoot}/oc-cnpolicy-configuration/v1/services/common/rx-reauth-profiles/{rxReauthProfileName}	See Table A-2
Export Rx Reauth Profile	GET	/oc-cnpolicy-configuration/v1/services/common/rx-reauth-profiles/export	See Table A-1
Import Rx Reauth Profile	POST	/oc-cnpolicy-configuration/v1/services/common/rx-reauth-profiles/import	See Table A-3
Delete Rx Reauth Profile	DELETE	{apiRoot}/oc-cnpolicy-configuration/v1/services/common/rx-reauth-profiles/{rxReauthProfileName}	See Table A-4

Get, Create, and Update Rx Reauth Profile

This section describes the request and response parameters used in NF communication profile APIs.

Table 2-486 Request and Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
Name	string	M	-
Settings	-	O	-
mediaType	string	M	Enter the name of the media type. Allowed Values: ALL, AUDIO, DATA, APPLICATION, VIDEO, CONTROL, TEXT, MESSAGE, NOMEDIATYPE, OTHER Default Value: All

Table 2-486 (Cont.) Request and Response Body Parameters

Field Name	Data Type	Mandatory(M)/Optional(O)/Conditional(C)	Description
precedence (when mediaType is other than ALL)	integer	M	When the Notify-Update triggered by Rx request towards SMF fails and the request comes with multiple media components then use this precedence value to determine which of these will determine the final Reauth Action. Allowed Values: 1-99 Default Value: Null
acceptAllErrors	boolean	O	When the Notify-Update triggered by Rx request towards SMF fails with any error code or cause and this field is set as True, then we would say that the ErrorCode and ErrorCause matched successfully. Allowed Values: False Default Value: True, False
errors	boolean	O	When the Notify-Update triggered by Rx request towards SMF fails with any error code or cause and the Accept All Errors field is set as False, check the Table 2-487 example table and match the ErrorCode and ErrorCause of the failure. Note: If the ErrorCode is configured and ErrorCause is left empty, PCF will compare only the ErrorCode and allow any ErrorCause for that specific error to match. Default Value: Empty List
exceptions	string	M	When the Notify-Update triggered by Rx Request towards SMF fails with any exception, then match the exception of the failure. Default Value: Empty List
reauthAction	string	O	Given that all following conditions for current setting are met: 1. MediaType specified matches 2. Error matched successfully or Exception matches successfully Then PCF can take the Reauth Action. Allowed Values: SEND_ASR, SUPPRESS_ASR, SEND_RAR Default Value: SEND_ASR

Table 2-487 ErrorCode and ErrorCause Combination

Configuration	ErrorCode	ErrorCause	Expectation
Nothing configured	5xx/4xx	NA	No match
{ "error code": 503, "error cause": "" }	503	...	Match
	503	SERVICE_UNAVAILABL E	Match
	503	CUSTOM_503	Match
	404	...	No match
{ "error code": 503, "error cause": "SERVICE_UNAVAILA BLE", "error code": 503, "error cause": "NF_CONGESTED", "error code": 503, "error cause": "CUSTOM_503", "error code": 404, "error cause": "NOT_FOUND", } }	503	...	Match
	503	SERVICE_UNAVAILABL E	Match
	404	...	Match
{ "error code": 503, "error cause": "SERVICE_UNAVAILA BLE", "error code": 404, "error cause": "NOT_FOUND", "error code": 503, "error cause": "", } }	503	SERVICE_UNAVAILABL E	Match
	503	CUSTOM_503	Match
	404	NOT_FOUND	Match

Sample Request body for Rx Reauth Profile POST and PUT operations:

```
{
  "name": "string",
  "settings": [
```



```

    {
      "mediaType": "ALL",
      "precedence": 99,
      "acceptAllErrors": true,
      "errors": [
        {
          "errorCode": 999,
          "errorCause": "string"
        }
      ],
      "exceptions": [
        {
          "exception": "TIMEOUT_EXCEPTION"
        }
      ],
      "reauthAction": "SEND_ASR"
    }
  ]
}

```

Sample Response body structure for Rx Reauth Profile GET, POST, and PUT operation:

```

{
  "name": "string",
  "settings": [
    {
      "mediaType": "ALL",
      "precedence": 99,
      "acceptAllErrors": true,
      "errors": [
        {
          "errorCode": 999,
          "errorCause": "string"
        }
      ],
      "exceptions": [
        {
          "exception": "TIMEOUT_EXCEPTION"
        }
      ],
      "reauthAction": "SEND_ASR"
    }
  ]
}

```

Sample Request Body structure for Rx Reauth Profile Import and Export operations:

```

{
  "name": "string",
  "settings": [
    {
      "mediaType": "ALL",
      "precedence": 99,

```

```

    "acceptAllErrors": true,
    "errors": [
      {
        "errorCode": 999,
        "errorCause": "string"
      }
    ],
    "exceptions": [
      {
        "exception": "TIMEOUT_EXCEPTION"
      }
    ],
    "reauthAction": "SEND_ASR"
  }
}

```

2.91 Diameter Connector

The Diameter Connector API allows to configure Diameter Connector.

Table 2-488 Supported REST APIs

HTTP Method or Custom Operation	Description	Resource URI
GET	Get Diameter Connector service	oc-cnpolicy-configuration/v1/services/diamConnector
PUT	Update Diameter Connector service	oc-cnpolicy-configuration/v1/services/diamConnector
POST	Import Diameter Connector service	oc-cnpolicy-configuration/v1/services/diamConnector/import
GET	Export Diameter Connector service	oc-cnpolicy-configuration/v1/services/diamConnector/export

Table 2-489 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
general	object	O	Allows to configure Diameter Connector.
staleRequestCleanup	object	O	Allows to configure stale request cleanup for Diameter Connector.

Table 2-490 General Configuration

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
ratTypeNRRedCapEnabled	boolean	O	When this parameter is enabled and if the RAT Type in the PDU session is NR_REDCAP, PCF sends the RATType AVP with value NR_REDCAP to P-CSCF in AAA and RAR messages. When this parameter is disabled and Rx session is established for the RedCap devices for which the RAT Type of the PDU session is NR_REDCAP: - Policy accepts the session and sends AAA and RAR messages to P-CCSCF without RATType AVP. - Policy increments diam_avp_dropped metric. Default value: false
advancedSettings	AdvancedSettings	O	To add additional advanced settings keys to the settings.

Table 2-491 staleRequestCleanup Configuration

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
enableLateArrival	boolean	O	Indicates whether to validate an incoming request if it is stale during arrival. Enable this field to stop processing the incoming requests to Diameter Connector if it already stale. Default value: true

Table 2-491 (Cont.) staleRequestCleanup Configuration

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
enableLateProcessing	boolean	O	Indicates whether to validate a request at Diameter Connector if it is stale during processing. Enable this field to stop processing the requests at Diameter Connector if it becomes stale during processing. Default value: true
sbiTimerEnabled	boolean	O	Indicates whether to handle HTTP SBI headers that are attached to incoming request. Default value: true
skipLateProcessingForTerminate	boolean	O	Indicates whether to skip validating requests of type DELETE if the request becomes stale during arrival and processing. Default value: false

Table 2-492 AdvancedSettings

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
key	string	O	Specifies the key name.
value	string	O	Specifies the value of the key.

Sample Request/Response parameters for GET operation:

```
{
  "general": {
    "ratTypeNRRedCapEnabled": false
  },
  "staleRequestCleanup": {
    "enableLateArrival": true,
    "enableLateProcessing": true,
    "skipLateProcessingForTerminate": false,
    "sbiTimerEnabled": true
  },
  "advancedSettings": [
    {
```

```

        "key": "key",
        "value": "value"
    }
]
}

```

cURL Commands

The following is a sample cURL command for GET operation:

```
curl -X 'GET' \ 'http://100.77.63.77:30331/oc-cnpolicy-configuration/v1/
services/diamConnector' \ -H 'accept: application/json'
```

2.92 PDS UE ID Configuration Settings

The PDS UE ID Configuration Settings API allows to configure UE ID based query on PolicyDS database.

Table 2-493 Supported REST APIs

HTTP Method or Custom Operation	Description	Resource URI
GET	Get PDS UE ID Configuration settings	oc-cnpolicy-configuration/v1/services/pds/pdsUEIdConfiguration
PUT	Update PDS UE ID Configuration settings	oc-cnpolicy-configuration/v1/services/pds/pdsUEIdConfiguration
POST	Import PDS UE ID Configuration settings	oc-cnpolicy-configuration/v1/services/pds/pdsUEIdConfiguration/import
GET	Export PDS UE ID Configuration settings	oc-cnpolicy-configuration/v1/services/pds/pdsUEIdConfiguration/export

Table 2-494 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
typeOfSearch	string	O	Indicates the type of query to be performed on the PolicyDS database. This field provides a dropdown list with the following options: • Multi_UE_ID_SEARCH: Specifies a key preference for PDS search query used to look up for a Pdsprofile record. When Multi-UE ID Search is selected the search query uses OR criteria and the search time will be higher. • PREFERENTIAL_SEARCH: When Preferential Search is selected, Preference Order field is displayed. It allows to query based on preferred primary key. • SINGLE_UE_ID_PREFERENTIAL_SEARCH: Specifies a key preference for PDS search query used to look up for a PDSSubscriber record.

Table 2-494 (Cont.) Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
preferenceOrder	string	O	This parameter must be configured when typeOfSearch parameter is configured as PREFERENTIAL_SEARCH. The value of preferenceOrder parameter specifies the preferred order of keys used for querying the database. • SUPI: Query based on SUPI value. It is mandatory to provide a valid SUPI value. • GPSI: Query based on GPSI value. It is mandatory to provide a valid GPSI value. • SUPI, GPSI: Query on SUPI first and then on GPSI. It is mandatory to provide at least a valid SUPI or GPSI value. • GPSI, SUPI: Query on GPSI first and then on SUPI. It is mandatory to provide at least a valid SUPI or GPSI value.
primaryKeyCombination	string	O	Specifies the required primary key combination. The primary key combination can be SUPI,GPSI or SUPI/GPSI. On selecting the required primary key combination, the requests to PDS is expected to mandatorily contain that ID. Otherwise, the request is rejected with 400 HTTP error code.

Table 2-494 (Cont.) Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
migrationInProgress	boolean	O	The Migration In Progress flag is applicable only when switching between MULTI_UE_ID_SEARCH/PREFERENTIAL_SEARCH and SINGLE_UE_ID_PREFERENTIAL_SEARCH. This flag is enabled when the records are being migrated from PDSPProfile to PDSSubscriber. This flag can be disabled once the migration of all the records are complete. The expectation is that all records must be migrated to updated format. While disabling Migration In Progress, Policy console displays the following warning: "Migration should be disabled only when all the records have been migrated. Are you sure you want to disable it?" If Migration In Progress flag is disabled while the migration of records is still in progress, the non-migrated records will go stale and can be cleaned up by Audit. Note In case of multi-site deployment: • Migration In Progress flag can be disabled for a site only if migration is enabled in all the sites with the updated configuration. Otherwise, migration cannot be disabled.

Table 2-494 (Cont.) Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
			• Migration should be disabled in all the sites almost simultaneously to avoid stale subscriptions being left in PDS. • Migration from Single to Single with different Primary Key combinations should be done in all sites almost simultaneously to avoid stale subscription being left in PDS
skipValidation	boolean	O	This section is used to verify the migration status at each site.

Sample Request/Response parameters for PUT operation:

```
{
  "typeOfSearch": "string",
  "preferenceOrder": [
    "string"
  ],
  "primaryKeyCombination": "string",
  "migrationInProgress": true,
  "skipValidation": true
}
```

cURL Commands

The following is a sample cURL command for PUT operation:

```
curl -X 'PUT' \
  'http://<host>:<port>/oc-cnpolicy-configuration/v1/services/pds/
pdsUEIdConfiguration' \
  -H 'accept: application/json' \
  -H 'Content-Type: application/json' \
  -d '{
    "typeOfSearch": "string",
    "preferenceOrder": [
      "string"
    ],
    "primaryKeyCombination": "string",
    "migrationInProgress": true,
```

```
"skipValidation": true
}'
```

2.93 Force Cleanup API

When importing a Policy configuration, if the import task remains in the IN_PROGRESS state for any reason, no new import can be initiated since only one import can run at a time. In such cases, new import cannot be initiated until stale cleanup timeout (30 minutes by default). After this timeout, the import is automatically cleaned up, and a new import can be initiated.

In order to reset the import status immediately (without waiting for the default 30-minute timeout), the Force Cleanup API can be used. This allows the stuck import data to be cleaned up instantly, enabling a new import to start right away.

Table 2-495 Possible operations for Force Cleanup API

HTTP Method or Custom Operation	Description	Resource URI	Possible Result Code
DELETE	Forcefully cleans up the Policy configuration import task.	{apiRoot}/oc-cnpolicy-query/v1/administration/import/stale/reset	The expected response is HTTP 204 (No Content), indicating that the stale import task was successfully reset.

```
curl -X 'DELETE' \
  'http://10.148.208.40:32373/oc-cnpolicy-configuration/v1/administration/
import/stale/reset' \
  -H 'accept: */*'
```

This API does not contain any request parameter.

2.94 DNN

The DNN API allows to configure DNN Profiles, which can be used to configure Message Profiles.

Table 2-496 Supported REST APIs

HTTP Method or Custom Operation	Description	Resource URI
GET	Get DNN Profile	oc-cnpolicy-configuration/v1/services/common/dnn/{dnnId}
POST	Create DNN Profile	oc-cnpolicy-configuration/v1/services/common/dnn
PUT	Update DNN Profile	oc-cnpolicy-configuration/v1/services/common/dnn/{dnnId}
POST	Import DNN Profile	oc-cnpolicy-configuration/v1/services/common/dnn/import
GET	Export DNN Profile	oc-cnpolicy-configuration/v1/services/common/dnn/export

Table 2-496 (Cont.) Supported REST APIs

HTTP Method or Custom Operation	Description	Resource URI
DELETE	Delete DNN Profile	oc-cnpolicy-configuration/v1/services/common/dnn/{dnnId}

Table 2-497 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/Optional(O)/Conditional(C)	Description
dnnId	Integer	M	Numeric identifier that uniquely represents a DNN entry. A unique ID must be assigned within the allowed range. Range: 1 to 255
dnn	String	M	Represents the DNN. This value uniquely identifies each DNN for configuration and reference within the system.

Sample Request/Response parameters for GET and POST operation:

```
{
  "dnnId": 255,
  "dnn": "internet"
}
```

2.95 SNSSAI

The SNSSAI API allows to configure S-NSSAI Profiles, which can be used to configure Message Profiles.

Table 2-498 Supported REST APIs

HTTP Method or Custom Operation	Description	Resource URI
GET	Get S-NSSAI Profile	oc-cnpolicy-configuration/v1/services/common/snssai/{snssaiId}
POST	Create S-NSSAI Profile	oc-cnpolicy-configuration/v1/services/common/snssai
PUT	Update S-NSSAI Profile	oc-cnpolicy-configuration/v1/services/common/snssai/{snssaiId}

Table 2-498 (Cont.) Supported REST APIs

HTTP Method or Custom Operation	Description	Resource URI
POST	Import S-NSSAI Profile	oc-cnpolicy-configuration/v1/services/common/snssai/import
GET	Export S-NSSAI Profile	oc-cnpolicy-configuration/v1/services/common/snssai/export
DELETE	Delete S-NSSAI Profile	oc-cnpolicy-configuration/v1/services/common/snssai/{snssaiId}

Table 2-499 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
snssaiId	Integer	M	Unique identifier for the S-NSSAI entry.
sst	String	M	The Slice or Service Type value associated with the S-NSSAI.
sd	String	M	Slice Differentiator value for the S-NSSAI.

Sample Request/Response parameters for GET and POST operation:

```
{
  "snssaiId": 100,
  "sst": "253",
  "sd": "1A2B3C"
}
```

2.96 Service URN

The Service URN API allows to configure Service URN, which can be used to configure Message Profiles.

Table 2-500 Supported REST APIs

HTTP Method or Custom Operation	Description	Resource URI
GET	Get Service URN	oc-cnpolicy-configuration/v1/services/common/serviceUrn/{serviceUrnId}
POST	Create Service URN	oc-cnpolicy-configuration/v1/services/common/serviceUrn
PUT	Update Service URN	oc-cnpolicy-configuration/v1/services/common/serviceUrn/{serviceUrnId}

Table 2-500 (Cont.) Supported REST APIs

HTTP Method or Custom Operation	Description	Resource URI
POST	Import Service URN	oc-cnpolicy-configuration/v1/services/common/serviceUrn/import
GET	Export Service URN	oc-cnpolicy-configuration/v1/services/common/serviceUrn/export
DELETE	Delete Service URN	oc-cnpolicy-configuration/v1/services/common/serviceUrn/{serviceUrnId}

Table 2-501 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/Optional(O)/Conditional(C)	Description
serviceUrnId	Integer	M	Specifies the identifier for each Service URN. Range: 1–255
serviceUrn	String	M	Specifies the Uniform Resource Name (URN) for the service. A maximum of 255 unique Service URNs can be created. For example: urn:service:sos.ambulance

Sample Request/Response parameters for GET and POST operation:

```
{
  "serviceUrnId": 255,
  "serviceUrn": "ims.mnc012.mcc345.3gppnetwork.org"
}
```

2.97 Message Profile

The Message Profile API allows to configure the Message Profiles, which are used to configure Overload control at Policy microservices.

Table 2-502 Supported REST APIs

HTTP Method or Custom Operation	Description	Resource URI
GET	Get Message Profile	oc-cnpolicy-configuration/v1/services/common/messageProfiles/{messageProfileName}
POST	Create Message Profile	oc-cnpolicy-configuration/v1/services/common/messageProfiles
PUT	Update Message Profile	oc-cnpolicy-configuration/v1/services/common/messageProfiles/{messageProfileName}
POST	Import Message Profile	oc-cnpolicy-configuration/v1/services/common/messageProfiles/import
GET	Export Message Profile	oc-cnpolicy-configuration/v1/services/common/messageProfiles/export
DELETE	Delete Message Profile	oc-cnpolicy-configuration/v1/services/common/messageProfiles/{messageProfileName}

Table 2-503 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/Optional(O)/Conditional(C)	Description
messageProfileName	String	M	Message profile name, which must be mapped with overload configurations.
serviceType	String	O	Select the service type for which the message profile is to be created. • PCF Session Management • Binding service • UDR Connector • CHF Connector
messageProfileAttributes	Array	O	Specifies the message profile attribute configurations as explained in Table 2-504 .

Table 2-504 Request/Response Body Parameters to configure message profile attributes

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
messageProfileAttributes.messageID	String	M	A unique identifier representing specific message rule parameters, including interface type, message type, and priority. Multiple Message IDs can be configured per profile. When a request is received, the configured Message Profile based on message attributes is parsed to identify the appropriate MessageID. The Enhanced Overload Actions rules associated with that MessageID determines whether a Reject or Assume Positive or both actions are executed.
messageProfileAttributes.rulePriority	Integer	M	A numeric value that uniquely identifies a rule when multiple rules have similar configurations. Range: 1–65535

Table 2-504 (Cont.) Request/Response Body Parameters to configure message profile attributes

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
messageProfileAttributes.interfaceType	String	M	Defines the network interface through which the message is transmitted For example, Npcf_SMPolicyControl, Npcf_PolicyAuthorization, Diameter_Rx, and Other. For interface types Npcf_SMPolicyControl, Npcf_PolicyAuthorization, and Diameter_Rx, the supported message types are 'Create','Update' and 'Delete'. For Other interface type, the supported message type is Bsf_Audit_Notification.

Table 2-504 (Cont.) Request/Response Body Parameters to configure message profile attributes

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
messageProfileAttributes.messageType	String	M	Denotes the type of message for the selected interface. The supported values of Message Type depends on the Interface Type. For example one of the following Message Type can be selected when the Interface Type is Npcf_SMPolicyControl: - Any (Any of the message types listed below) - Create - Update - Delete - Update_Notify - Terminate_Notify For the complete list of message types supported by each interface type, see <i>Message Attributes Supported for Different Service Types and Interface Types</i> in <i>Message Profiles</i> section in <i>Oracle Communications Cloud Native Core, Converged Policy User Guide</i>.
messageProfileAttributes.messageProfileFilterConditions	String	O	Configure the message profile filter conditions to filter out rules that matches these attributes as explained in Table 2-505. Note: Message Profile Filter Conditions is not a mandatory attribute for rules.

Table 2-504 (Cont.) Request/Response Body Parameters to configure message profile attributes

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
messageProfileAttribute s.requestPriorityOverride	String	M	Determines the behavior for overwriting the incoming message's priority with the priority defined in the profile. Possible values: • Always • Never • IfNotPresent Default: Never Note: For the Diameter_Rx interface type, priority is always sent to the endpoint service and cannot be removed. Therefore, priority will always be present in SM service. Based on this behavior, the IfNotPresent option for priority override is not required for handling Diameter Rx messages.
messageProfileAttribute s.requestPriorityValue	String	C	Specifies the numeric priority value to apply when Request Priority Override is set to Always or IfNotPresent. Range: 0–31

Table 2-504 (Cont.) Request/Response Body Parameters to configure message profile attributes

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
messageProfileAttributes.responsePriorityAssign	String	C	It specifies the rule to specify response priority value. Possible values are: • Never: Indicates not to assign any response priority. • Custom: Allows to use specify the desired response priority in the Response Priority Assign field. • EvaluatedRequestPriority: Indicates that whatever is the final request priority, the same gets assigned to the response. Default value: Never

Note

The value for rulePriority, requestPriorityValue, and responsePriorityValue can be provided either as a JSON number, for example 10, or as a numeric string, for example "10". Numeric strings are converted to integers before processing.

Table 2-505 Request/Response Body Parameters to configure message profile filter conditions

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
messageProfileAttribute s.messageProfileFilterC onditions.attributeName	String	C	Specifies the name of the attribute. Depending upon the value of Interface Type, message attributes list will be displayed. The following are some of the supported attribute names: • DNN • SNSSAI • ServiceURN • 3gpp-sbi-message-priority • oc-message-priority For detailed list of message attributes supported for each interface type, see <i>Message Attributes Supported for Different Service Types and Interface Types in Message Profiles in Oracle Communications Cloud Native Core, Converged Policy User Guide</i>. While providing DNN or SNSSAI as Message profile filter conditions, a comma separated list can be given to support overload actions to support multiple DNN or SNSSAI in one rule. A max of 10 unique DNN's can be created under one rule. Similarly a max of 10 unique SNSSAI can be created under one rule. Note: For a given Message Profile rule, if both message attributes, DNN and SNSSAI for the Npcf_SMPolicyControl interface, or DNN and ServiceURN for the Diameter Rx or Npcf_PolicyAuthorizatio

Table 2-505 (Cont.) Request/Response Body Parameters to configure message profile filter conditions

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
			n interface are configured, they function as an 'AND' condition. That is, both the attributes must match the corresponding parameters in the incoming request body to identify the correct MessageID. If no Message Attribute is configured for a given rule, all the messages having any DNN or SNSSAI are considered for that rule.

Table 2-505 (Cont.) Request/Response Body Parameters to configure message profile filter conditions

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
messageProfileAttributes.messageProfileFilterConditions.attributeValue	String	C	This field is used to mention the value of the attribute. The Attribute values for the selected attribute field is derived from the respective DNN Profile, SNSSAI Profile, and ServiceUrn Profile. When attributeName is DNN, SNSSAI, or ServiceURN, attributeValue must contain a list of configured IDs for the selected attribute. for example, <pre>{ "attributeName": "DNN/SNSSAI/ServiceURN", "attributeValue": [1, 2, 3] }</pre> When attributeName is 3gpp-sbi-message-priority or oc-message-priority, attributeValue must contain exactly one value in the list. The value can be either a single priority value between 0 and 31, for example "1", or a priority range between 0 and 31, for example "1-12". for example, <pre>{ "attributeName": "3gpp-sbi-message-priority", "attributeValue": ["1"] } { "attributeName": "oc-message-priority", "attributeValue": ["1-12"] }</pre> When attributeName is policyData, attributeValue must be ["SmPolicyData"] for example, <pre>{ "attributeName": "policyData", "attributeValue": ["SmPolicyData"] }</pre>

Sample cURL command to create a Message Profile

```

curl -X 'POST' \
  'http://10.123.179.120:32033/oc-cnpolicy-configuration/v1/services/common/
messageProfiles' \
  -H 'accept: application/json' \
  -H 'Content-Type: application/json' \
  -d '{
    "messageProfileName": "string",
    "serviceType": "PCF_SM",
    "messageProfileAttributes": [
      {
        "messageID": "msg_1",
        "rulePriority": 45,
        "interfaceType": "Npcf_SMPolicyControl",
        "messageType": "Create",
        "messageProfileFilterConditions": [
          {
            "attributeName": "DNN",
            "attributeValue": [
              1
            ]
          }
        ],
        "requestPriorityOverride": "Never"
        "responsePriorityAssign": "Never"
      }
    ]
  }'
```

Sample Request/Response parameters for GET and POST operation:

```

{
  "messageProfileName": "string",
  "serviceType": "PCF_SM",
  "messageProfileAttributes": [
    {
      "messageID": "msg_1",
      "rulePriority": 45,
      "interfaceType": "Npcf_SMPolicyControl",
      "messageType": "Create",
      "messageProfileFilterConditions": [
        {
          "attributeName": "DNN",
          "attributeValue": [
            1
          ]
        }
      ],
      "requestPriorityOverride": "Never"
      "responsePriorityAssign": "Never"
    }
  ]
}
```

2.98 Service Profiles

The Service Profiles API allows to create and configure Service Profiles which can be used to configure assume positive action for overload control handling at Policy microservices.

Table 2-506 Supported REST APIs

HTTP Method or Custom Operation	Description	Resource URI
GET	Get Service Profiles	oc-cnpolicy-configuration/v1/services/common/serviceProfiles/{serviceProfilesName}
POST	Create Service Profiles	oc-cnpolicy-configuration/v1/services/common/serviceProfiles
PUT	Update Service Profiles	oc-cnpolicy-configuration/v1/services/common/serviceProfiles/{serviceProfilesName}
POST	Import Service Profiles	oc-cnpolicy-configuration/v1/services/common/serviceProfiles/import
GET	Export Service Profiles	oc-cnpolicy-configuration/v1/services/common/serviceProfiles/export
DELETE	Delete Service Profiles	oc-cnpolicy-configuration/v1/services/common/serviceProfiles/{serviceProfilesName}

Table 2-507 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/Optional(O)/Conditional(C)	Description
serviceProfileName	String	M	Specifies the unique name of the Service Profile. This Service Profile is later selected when associating the profile to an Overload rule for Assume Positive handling.
serviceType	String	M	Specifies the service for which this Service Profile applies. Service Profiles are used to control which internal interactions are allowed or skipped during overload handling for Policy microservice. Note: Currently Policy supports only PCF Session Management service.

Table 2-507 (Cont.) Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
interfaceType	String	M	Specifies the interface that the Service Profile governs. Note: Currently Policy supports only Npcf_SMPolicyControl.
serviceInteractions.policyEvaluation	Boolean	O	Indicates whether SM service interacts with PRE for policy evaluation when a request is processed under an Assume Positive overload rule. Possible values are true, false. When the value of this field is false, that is, when it is disabled, the response behavior of SM service is driven by the configured Default Processing Profile . For example, default PCC/session rules and related behaviors.
serviceInteractions.userDataInteraction	Boolean	O	Indicates whether SM service interacts with PDS for User Data retrieval or subscription. Possible values are true, false. When this field is disabled, SM service does not perform User Data interactions (for example, GET/Subscribe), and User Data source communication is suppressed for overload recovery.

Table 2-507 (Cont.) Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
serviceInteractions.spendingLimitDataInteraction	Boolean	O	Indicates whether SM service interacts with PDS for Spending Limit Data (CHF/OCS data) retrieval or subscription. Possible values are true, false. When this field is disabled, CHF-related interactions (sync/async) are suppressed as part of overload recovery.

Sample Request/Response parameters for GET and POST operation:

```
{
  "serviceProfileName": "string",
  "serviceType": "PCF_SM",
  "interfaceType": "Npcf_SMPolicyControl",
  "serviceInteractions": {
    "policyEvaluation": true,
    "userDataInteraction": true,
    "spendingLimitDataInteraction": true
  }
}
```

2.99 Default Processing Profile

The Default Processing Profiles API allows to create and configure Default Processing Profiles, which can be used to configure the Default Processing for Policy microservices.

Table 2-508 Supported REST APIs

HTTP Method or Custom Operation	Description	Resource URI
GET	Get Default Processing Profiles	oc-cnpolicy-configuration/v1/ services/common/ defaultProcessingProfiles/ {dpProfileName}
POST	Create Default Processing Profiles	oc-cnpolicy-configuration/v1/ services/common/ defaultProcessingProfiles
PUT	Update Default Processing Profiles	oc-cnpolicy-configuration/v1/ services/common/ defaultProcessingProfiles/ {dpProfileName}

Table 2-508 (Cont.) Supported REST APIs

HTTP Method or Custom Operation	Description	Resource URI
POST	Import Default Processing Profiles	oc-cnpolicy-configuration/v1/services/common/defaultProcessingProfiles/import
GET	Export Default Processing Profiles	oc-cnpolicy-configuration/v1/services/common/defaultProcessingProfiles/export
DELETE	Delete Default Processing Profiles	oc-cnpolicy-configuration/v1/services/common/defaultProcessingProfiles/{dpProfileName}

Table 2-509 Request/Response Body Parameters to Configure Default Processing Profiles

Field Name	Data Type	Mandatory(M)/Optional(O)/Conditional(C)	Description
dpProfileName	String	M	Specifies a unique name of the Default Processing Profile. This profile is later mapped under PCF Session Management page to control the default response behavior when PRE policy evaluation is not performed (for example, due to Assume Positive restrictions or PRE failures). This is a mandatory field.
serviceType	String	M	Specifies the service to which this Default Processing Profile applies. Currently, Policy supports only PCF Session Management service.
interfaceType	Integer	M	Specifies the interface on which the default processing behavior is applied. Currently, Policy supports only Npcf_SMPolicyControl interface with Default Processing Profile.

Table 2-509 (Cont.) Request/Response Body Parameters to Configure Default Processing Profiles

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
messageProfile	Integer	M	Specifies the Message Profile used to supply the list of MessageIDs that can be mapped to the default processing actions such as PCC rules, session rules, BSF registration, and CHF counter-fetch behavior.
messageProfileMapping. messageID	Integer	M	This is a mandatory field. This field specifies the MessageID selected from the Message Profile. A MessageID represents a unique combination of interface type, message type, message attributes (for example, DNN and/or SNSSAI), and priority, and is used to determine which default actions are applied. The value for this field must be selected from the list of MessageIDs created for Message Profiles.
messageProfileMapping. pccRules	String	M	Specifies the default PCC rules to include in the response when policy evaluation is not performed by PRE (for example when Assume Positive feature disables policy evaluation, PRE is disabled, or PRE returns an error).
messageProfileMapping. sessionRules	String	M	Specifies the default session rules to include in the response when policy evaluation is not performed by PRE.

Table 2-509 (Cont.) Request/Response Body Parameters to Configure Default Processing Profiles

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
messageProfileMapping. bindingRegistration	Boolean	M	Indicates whether to enable or disable BSF (binding) registration for the selected MessageID when default processing is applied. Possible values: - enable: BSF (binding) registration is performed for the selected MessageID when default processing is applied. - disable: BSF (binding) registration is not performed for the selected MessageID when default processing is applied. Default value: disabled
messageProfileMapping. bindingRegistrationMode	String	C	This field appears when BSF Registration is enabled. BSF Registration Mode is used to interact with the Binding/BSF service when BSF Registration is enabled. Possible values: - Synchronous - Asynchronous
messageProfileMapping. spendingLimitInteraction	String	M	This field is used to control CHF interaction for Policy counter retrieval when the default processing is applied. Possible values are: - None - CHF Default value: None

Table 2-509 (Cont.) Request/Response Body Parameters to Configure Default Processing Profiles

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
messageProfileMapping. fetchCounter	Array	C	This field appears when Spending Limit Interaction is CHF. It specifies whether to fetch all the counters or only specific counters from CHF. Possible values are: • All: to fetch all the Policy counters from CHF. • Specific: to fetch only the specific counters from CHF.
messageProfileMapping. policyCounterIds	String	C	Appears when Specific option is chosen for Fetch Counter field. This field provides the list of Policy counter IDs to fetch from CHF.

Sample Request/Response parameters for GET and POST operation:

```
{
  "dpProfileName": "string",
  "serviceType": "PCF_SM",
  "interfaceType": "Npcf_SMPolicyControl",
  "messageProfile": "string",
  "messageProfileMapping": [
    {
      "messageID": "string",
      "pccRules": [
        "string"
      ],
      "sessionRules": [
        "string"
      ],
      "bindingRegistration": "Enable",
      "bindingRegistrationMode": "Synchronous",
      "spendingLimitInteraction": "None",
      "fetchCounter": "All",
      "policyCounterIds": [
        "string"
      ]
    }
  ]
}
```

2.100 Overload Configurations

The Overload Configurations API allows to perform overload control configurations.

Table 2-510 Supported REST APIs

HTTP Method or Custom Operation	Description	Resource URI
GET	Get Overload Configurations	oc-cnpolicy-configuration/v1/services/common/overloadConfigurations/{overloadConfigurationsName}
POST	Create Overload Configurations	oc-cnpolicy-configuration/v1/services/common/overloadConfigurations
PUT	Update Overload Configurations	oc-cnpolicy-configuration/v1/services/common/overloadConfigurations/{overloadConfigurationsName}
POST	Import Overload Configurations	oc-cnpolicy-configuration/v1/services/common/overloadConfigurations/import
GET	Export Overload Configurations	oc-cnpolicy-configuration/v1/services/common/overloadConfigurations/export
DELETE	Delete Overload Configurations	oc-cnpolicy-configuration/v1/services/common/overloadConfigurations/{overloadConfigurationsName}

Table 2-511 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/Optional(O)/Conditional(C)	Description
name	String	M	Unique name to represent Overload configuration profile created.
serviceType	String	M	Specifies the Policy microservice for which the Overload Configurations are applied. Currently, Policy supports only PCF Session Management service.

Table 2-511 (Cont.) Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
messageProfile	String	M	The associated message profile containing rules for handling different message types and their attributes during overload. Provides a dropdown selection from pre-configured message profiles.
configureOverLoadRules	Array	O	Overload Rules are be created where mapping of system 'Load Level' is done with 'MessageIds', along with Conditional Message Priority and reject Percentage will be defined for the rule as well. Define the overload rules as described in Table 2-512 table. Note: Before deleting any Message Profile, make sure to verify and remove existing associations of the Message Profile with any of the Overload Rules.

Table 2-512 Request/Response Body Parameters to configure overload rules

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
configureOverLoadRule s.level	Integer	O	Specifies the overload severity level at which the mapped rule must be applied. Select any of the following values using the drop-down list: • L1 • L2 • L3 • L4 • L5 • L6 • L7 • L8 • L9 • 10
configureOverLoadRule s.messageID	String	M	Unique identifier representing a combination of message rule parameters, including request type, message type, attributes, interface type, and priority. Message ID must map to a configured message profile.
configureOverLoadRule s.rulePriority	Integer	M	Indicates the evaluation priority among multiple overload rules. Higher priority rules are matched first.
configureOverLoadRule s.messagePriority	Integer	O	Priority assigned to the message for overload processing. Message Priority can be configured to override incoming priority ("Always", "Never", "If Not Present"). If overridden, the numerical priority can range from 0 to 31. If not set to override, the field is not displayed.
configureOverLoadRule s.serviceProfile	String	M	This field allows to select one of the service profiles created on Service Profile page.

Table 2-512 (Cont.) Request/Response Body Parameters to configure overload rules

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
configureOverLoadRule s.apPercentage	Integer	M	This field appears when the Service Profile field is configured. Specifies the percentage of messages selected to perform 'Assume Positive' action where service interactions are skipped for the configured Overload rule. Note: Service Profile Apply Percentage together with Reject Percentage should not exceed 100%. Range: 0 to 100
configureOverLoadRule s.rejectPercentage	Integer	O	Specifies the percentage of matching messages to be rejected when the overload level is triggered. Default value: 0 (no rejection unless specified in the rule) Range: 0 to 100
configureOverLoadRule s.errorCode	String	O	Specifies the error code returned to requests when the reject percentage triggers rejection due to overload. This value is selected from a predefined list of error codes relevant to each message type and protocol being handled.

Sample Request/Response parameters for GET and POST operation:

```
{
  "name": "string",
  "serviceType": "PCF_SM",
  "messageProfile": "string",
  "configureOverLoadRules": [
    {
      "level": "L1",
      "messageID": "string",
      "rulePriority": 0,
      "messagePriority": 0,

```

```

        "serviceProfile": "string",
        "apPercentage": 0,
        "rejectPercentage": 0,
        "errorCode": "string"
    }
  ]
}

```

2.101 Yaml Schema API

The Yaml Schema API allows you to create, import, and export the Yaml schema.

Table 2-513 Supported REST APIs

HTTP Method or Custom Operation	Description	Resource URI	Possible Result Code
POST	Create Yaml Schema	oc-cnpolicy-configuration/v1/policydata/common/schemas/yamlschema	See Table A-3
GET	Export Yaml Schema	oc-cnpolicy-configuration/v1/policydata/common/schemas/yamlschema/export	See Table A-1
POST	Import Yaml Schema	oc-cnpolicy-configuration/v1/policydata/common/schemas/yamlschema/import?action={action}	See Table A-3

- **Post - Create Yaml Schema:** This method is used to add a schema to the Yaml Schema section in UI. You need to provide the yaml schema you want to upload/create. This will be a similar action to the one the user can perform in the UI by using the Import function in the **Yaml Schema** page. For more information about the Yaml Schema page, see Yaml Schema section in *Oracle Communications Cloud Native Core Converged Policy User Guide*. Please use the below code snippet for reference:

```

openapi: 3.0.0
info:
  description: UDRBlob
  version: 0.0.1
  title: UDRBlob
paths:
  /:
    get:
      operationId: get
      summary: get
      tags:
        - get
      responses:
        "200":
          description: OK

```

```

        content:
          application/json:
            schema:
              $ref: "#/components/schemas/UDRBlob"
components:
  schemas:
    UDRBlob:
      type: object
      properties:
        smPolicyAttrs:
          $ref: "#/components/schemas/SmPolicyAttrs"
        dynamicAttrs:
          $ref: "#/components/schemas/dynamicAttrs"
        validIds:
          $ref: "#/components/schemas/ValidIds"
        consumerAttrs:
          $ref: "#/components/schemas/ConsumerAttrs"
        testAttrs:
          $ref: "#/components/schemas/TestAttrs"
    SmPolicyAttrs:
      type: object
      properties:
        vzSmPolicyItemId:
          type: string
        blobValue:
          $ref: "#/components/schemas/SmPolicyBlobValue"
    SmPolicyBlobValue:
      type: object
      properties:
        PlanType:
          type: string
        DataThr2:
          type: string
        DataThr2UWB:
          type: string
        VidOpt:
          type: string
        VidOptUWB:
          type: string
        Timestamp:
          type: string
    dynamicAttrs:
      type: object
      properties:
        vzSmPolicyItemId:
          type: string
        blobValue:
          $ref: "#/components/schemas/DynamicPolicyBlobValue"
    DynamicPolicyBlobValue:
      type: object
      properties:
        DATAH:
          type: string
        UWB-DATAH:
          type: string
        TETRH:

```

```

        type: string
    UWB-TETRH:
        type: string
    Timestamp:
        type: string
ValidIds:
    type: object
    properties:
        vzSmPolicyItemId:
            type: string
        blobValue:
            $ref: "#/components/schemas/ValIdBlobValue"
ValIdBlobValue:
    type: object
    properties:
        SUPI:
            type: string
        GPSI:
            type: string
ConsumerAttrs:
    type: object
    properties:
        vzSmPolicyItemId:
            type: string
        blobValue:
            $ref: "#/components/schemas/ConsAttrBlobValue"
ConsAttrBlobValue:
    type: object
    properties:
        PlanType:
            type: string
TestAttrs:
    type: object
    properties:
        vzSmPolicyItemId:
            type: string
        blobValue:
            $ref: "#/components/schemas/TestBlobValue"
TestBlobValue:
    type: object
    properties:
        PlanType:
            type: string
        DataThr2:
            type: string
        DataThr2UWB:
            type: string
        VidOpt:
            type: string
        VidOptUWB:
            type: string
        Timestamp:
            type: string

```

- **Get - Export Yaml Schema:** This method is used for retrieving all the schemas uploaded to the Yaml Schema section in UI, no parameter is needed. It will be a similar action to the

Bulk Export selecting only the Yaml Schema section under the Administration -> Export & Import. For more information, see Export & Import section in *Oracle Communications Cloud Native Core Converged Policy User's Guide*.

- **Post - Import Yaml Schema:** This method is similar to the *Create Yaml Schema*, this is used with bulk data.

Supported Actions for Importing Yaml Schema

Following are the actions supported by Policy when the user imports Yaml Schema:

- **ignore:** On selecting the ignore option, no changes are made to the existing Yaml schema. The Yaml schema in the imported file is ignored or skipped. No changes are made to the Yaml schema with this option.
- **replace:** On selecting the replace option, the existing Yaml schema is completely replaced with the Yaml schema in the imported file.

Sample Request Body structure for Import method::

```
{
  "topic": "public.yaml.schema",
  "sourceVersion": "26.1.200-ocngf-pre-dev-titans",
  "date": "2026-01-28T23:12:05Z",
  "exportData": [
    {
      "key": "UDRObj",
      "tag": [],
      "yaml": {
        "openapi": "3.0.0",
        "info": {
          "description": "UDRObj",
          "version": "0.0.1",
          "title": "UDRObj"
        },
        "paths": {
          "/": {
            "get": {
              "operationId": "get",
              "summary": "get",
              "tags": [
                "get"
              ],
              "responses": {
                "200": {
                  "description": "OK",
                  "content": {
                    "application/json": {
                      "schema": {
                        "$ref": "#/components/schemas/UDRObj"
                      }
                    }
                  }
                }
              }
            }
          }
        }
      }
    }
  ]
}
```

```

"components": {
  "schemas": {
    "UDRObj": {
      "type": "object",
      "properties": {
        "smPolicyAttrs": {
          "$ref": "#/components/schemas/
SmPolicyAttrs"

          },
        "testAttrs": {
          "$ref": "#/components/schemas/TestAttrs"
        },
        "dynamicAttrs": {
          "$ref": "#/components/schemas/
DynamicAttrs"

          },
        "validIds": {
          "$ref": "#/components/schemas/ValidIds"
        }
      }
    },
    "SmPolicyAttrs": {
      "type": "object",
      "properties": {
        "vzSmPolicyItemId": {
          "type": "string"
        },
        "blobValue": {
          "type": "string"
        }
      }
    },
    "DynamicAttrs": {
      "type": "object",
      "properties": {
        "vzSmPolicyItemId": {
          "type": "string"
        },
        "blobValue": {
          "type": "string"
        }
      }
    },
    "TestAttrs": {
      "type": "object",
      "properties": {
        "vzSmPolicyItemId": {
          "type": "string"
        },
        "blobValue": {
          "type": "string"
        }
      }
    },
    "ValidIds": {
      "type": "object",

```

```

        "properties": {
          "vzSmPolicyItemId": {
            "type": "string"
          },
          "blobValue": {
            "$ref": "#/components/schemas/
ValidBlobValue"
          }
        }
      },
      "ValidBlobValue": {
        "type": "object",
        "properties": {
          "SUPI": {
            "type": "string"
          },
          "GPSI": {
            "type": "string"
          }
        }
      }
    }
  },
  {
    "key": "UDRBlob",
    "tag": [],
    "yaml": {
      "openapi": "3.0.0",
      "info": {
        "description": "UDRBlob",
        "version": "0.0.1",
        "title": "UDRBlob"
      },
      "paths": {
        "/": {
          "get": {
            "operationId": "get",
            "summary": "get",
            "tags": [
              "get"
            ],
            "responses": {
              "200": {
                "description": "OK",
                "content": {
                  "application/json": {
                    "schema": {
                      "$ref": "#/components/schemas/
UDRBlob"
                    }
                  }
                }
              }
            }
          }
        }
      }
    }
  }
}

```



```

    }
  },
  "components": {
    "schemas": {
      "UDRBlob": {
        "type": "object",
        "properties": {
          "smPolicyAttrs": {
            "$ref": "#/components/schemas/
SmPolicyAttrs"
          },
          "dynamicAttrs": {
            "$ref": "#/components/schemas/
dynamicAttrs"
          },
          "validIds": {
            "$ref": "#/components/schemas/ValidIds"
          },
          "consumerAttrs": {
            "$ref": "#/components/schemas/
ConsumerAttrs"
          },
          "testAttrs": {
            "$ref": "#/components/schemas/TestAttrs"
          }
        }
      },
      "SmPolicyAttrs": {
        "type": "object",
        "properties": {
          "vzSmPolicyItemId": {
            "type": "string"
          },
          "blobValue": {
            "$ref": "#/components/schemas/
SmPolicyBlobValue"
          }
        }
      },
      "SmPolicyBlobValue": {
        "type": "object",
        "properties": {
          "PlanType": {
            "type": "string"
          },
          "DataThr2": {
            "type": "string"
          },
          "DataThr2UWB": {
            "type": "string"
          },
          "VidOpt": {
            "type": "string"
          },
          "VidOptUWB": {

```

```

        "type": "string"
      },
      "Timestamp": {
        "type": "string"
      }
    }
  },
  "dynamicAttrs": {
    "type": "object",
    "properties": {
      "vzSmPolicyItemId": {
        "type": "string"
      },
      "blobValue": {
        "$ref": "#/components/schemas/
DynamicPolicyBlobValue"
      }
    }
  },
  "DynamicPolicyBlobValue": {
    "type": "object",
    "properties": {
      "DATAH": {
        "type": "string"
      },
      "UWB-DATAH": {
        "type": "string"
      },
      "TETRH": {
        "type": "string"
      },
      "UWB-TETRH": {
        "type": "string"
      },
      "Timestamp": {
        "type": "string"
      }
    }
  },
  "ValidIds": {
    "type": "object",
    "properties": {
      "vzSmPolicyItemId": {
        "type": "string"
      },
      "blobValue": {
        "$ref": "#/components/schemas/
ValidBlobValue"
      }
    }
  },
  "ValidBlobValue": {
    "type": "object",
    "properties": {
      "SUPI": {
        "type": "string"
      }
    }
  }
}

```

```

        },
        "GPSI": {
            "type": "string"
        }
    },
    },
    "ConsumerAttrs": {
        "type": "object",
        "properties": {
            "vzSmPolicyItemId": {
                "type": "string"
            },
            "blobValue": {
                "$ref": "#/components/schemas/
ConsAttrBlobValue"
            }
        }
    },
    "ConsAttrBlobValue": {
        "type": "object",
        "properties": {
            "PlanType": {
                "type": "string"
            }
        }
    },
    "TestAttrs": {
        "type": "object",
        "properties": {
            "vzSmPolicyItemId": {
                "type": "string"
            },
            "blobValue": {
                "$ref": "#/components/schemas/
TestBlobValue"
            }
        }
    },
    "TestBlobValue": {
        "type": "object",
        "properties": {
            "PlanType": {
                "type": "string"
            },
            "DataThr2": {
                "type": "string"
            },
            "DataThr2UWB": {
                "type": "string"
            },
            "VidOpt": {
                "type": "string"
            },
            "VidOptUWB": {
                "type": "string"
            }
        }
    },

```

```

        "Timestamp": {
          "type": "string"
        }
      }
    }
  }
},
{
  "key": "UDRObjUE",
  "tag": [],
  "yaml": {
    "openapi": "3.0.0",
    "info": {
      "description": "UDRObjUE",
      "version": "0.0.1",
      "title": "UDRObjUE"
    },
    "paths": {
      "/": {
        "get": {
          "operationId": "get",
          "summary": "get",
          "tags": [
            "get"
          ],
          "responses": {
            "200": {
              "description": "OK",
              "content": {
                "application/json": {
                  "schema": {
                    "$ref": "#/components/schemas/
UDRObjUE"
                  }
                }
              }
            }
          }
        }
      }
    },
    "components": {
      "schemas": {
        "UDRObjUE": {
          "type": "object",
          "properties": {
            "uePolicyAttrs": {
              "$ref": "#/components/schemas/
UePolicyAttrs"
            },
            "testAttrs": {
              "$ref": "#/components/schemas/TestAttrs"
            },
            "dynamicAttrs": {

```

```

DynamicAttrs"
    "$ref": "#/components/schemas/
    },
    "validIds": {
      "$ref": "#/components/schemas/ValidIds"
    }
  },
  "UePolicyAttrs": {
    "type": "object",
    "properties": {
      "vzSmPolicyItemId": {
        "type": "string"
      },
      "blobValue": {
        "type": "string"
      }
    }
  },
  "DynamicAttrs": {
    "type": "object",
    "properties": {
      "vzSmPolicyItemId": {
        "type": "string"
      },
      "blobValue": {
        "type": "string"
      }
    }
  },
  "TestAttrs": {
    "type": "object",
    "properties": {
      "vzSmPolicyItemId": {
        "type": "string"
      },
      "blobValue": {
        "type": "string"
      }
    }
  },
  "ValidIds": {
    "type": "object",
    "properties": {
      "vzSmPolicyItemId": {
        "type": "string"
      },
      "blobValue": {
        "$ref": "#/components/schemas/
ValidBlobValue"
      }
    }
  },
  "ValidBlobValue": {
    "type": "object",
    "properties": {

```

```

        "SUPI": {
            "type": "string"
        },
        "GPSI": {
            "type": "string"
        }
    }
}
}
}
},
{
    "key": "custom_amPolicyData",
    "tag": [
        "User"
    ],
    "yaml": {
        "openapi": "3.0.0",
        "info": {
            "version": "-",
            "title": "Unified Data Repository Service API file for AM
policy data",
            "description": "The API version is defined in 3GPP TS
29.504© 2020, 3GPP Organizational Partners (ARIB, ATIS, CCSA, ETSI, TSDSI,
TTA, TTC).All rights reserved."
        },
        "components": {
            "schemas": {
                "custom_amPolicyData": {
                    "description": "Contains the AM policy data for a
given subscriber.",
                    "type": "object",
                    "properties": {
                        "vendorSpecific": {
                            "type": "array",
                            "items": {
                                "$ref": "#/components/schemas/
VendorSpecific"
                            },
                            "minItems": "1"
                        }
                    }
                },
                "VendorSpecific": {
                    "type": "object",
                    "properties": {
                        "abPolicyItemId": {
                            "type": "string"
                        },
                        "blobValue": {
                            "$ref": "#/components/schemas/blobValue"
                        }
                    }
                }
            }
        },
        "blobValue": {

```

```

        "type": "object",
        "properties": {
            "snssai": {
                "type": "string"
            },
            "olddnn": {
                "type": "string"
            },
            "newdnn": {
                "type": "string"
            }
        }
    },
    "01PolicyItem": {
        "type": "object",
        "description": "Contains a Vendor-specific AMF
policy data item",
        "properties": {
            "01PolicyItemId": {
                "type": "string"
            },
            "blobValue": {
                "type": "object",
                "additionalProperties": {
                    "$ref": "#/components/schemas/
blobValue"
                },
                "minItems": "1"
            }
        },
        "required": [
            "01PolicyItemId",
            "blobValue"
        ]
    }
}
}
}
}
]
}

```

2.102 HTTP Server API

The HTTP Server API allows you to to add and manage HTTP Server.

Table 2-514 Supported REST APIs

HTTP Method or Custom Operation	Description	Resource URI	Possible Result Code
POST	Create HTTP Server	/oc-cnpolicy-configuration/v1/httpServer	See Table A-3

Table 2-514 (Cont.) Supported REST APIs

HTTP Method or Custom Operation	Description	Resource URI	Possible Result Code
GET	Get All HTTP Server	/oc-cnpolicy-configuration/v1/httpServer/export	See Table A-1
POST	Import HTTP Server s	/oc-cnpolicy-configuration/v1/httpServer/import?action={action}	See Table A-3
GET	Get HTTP Server	/oc-cnpolicy-configuration/v1/httpServer	See Table A-1
PUT	Update HTTP Server	/oc-cnpolicy-configuration/v1/httpServer	See Table A-2
DELETE	Delete HTTP Server	/oc-cnpolicy-configuration/v1/httpServer	See Table A-4

Sample Request Body structure for Create or Update operations:

```
{
  "name": "notif_server_01",
  "description": "Primary notifier endpoint",
  "host": "api.example.com:443",
  "altHost": "backup.example.com:443",
  "uriPath": "/notify/v1/events",
  "scheme": "HTTPS",
  "version": "1.1",
  "header": [

    {
      "key": "Authorization",
      "value": "Bearer <token>"
    },

    {
      "key": "Content-Type",
      "value": "application/json"
    }
  ]
}
```

Sample Request Body Structure for import operation:

```
{
  "topic": "common.notifierservice.httpserver",
  "version": "<system-version>",
  "exportData": [
    {
      "name": "notif_server_01",
      "description": "Primary notifier endpoint",
      "host": "api.example.com:443",
```



```
      "altHost": "backup.example.com:443",
      "uriPath": "/notify/v1/events",
      "scheme": "HTTPS",
      "version": "1.1",
      "header": [

        {
          "key": "Authorization",
          "value": "Bearer
<token>"
        },

        {
          "key": "Content-Type",
          "value": "application/
json"
        }
      ]
    }
  ]
}
```

2.103 Policy DB Cluster State Query

The Policy DB Cluster State Query API is used to view the real time cnDBTier cluster state exposed for service health visibility.

Table 2-515 Supported REST APIs

HTTP Method or Custom Operation	Description	Resource URI	Possible Result Code
GET	Get DB cluster state	{apiRoot}/oc-cnpolicy-configuration/v1/dbClusterState	• 200: OK • 400: Bad Request • 401: Unauthorized • 403: Forbidden • 404: Not Found • 429: Too Many Requests • 500: Internal Server Error • 503: Service Unavailable

Curl command to run the API:

```
curl -X 'GET' \
'http://10.148.210.41:8000/oc-cnpolicy-configuration/v1/dbClusterState' \
-H 'accept: application/json'
```

There are no request parameters for this API.

3

Common Services REST Specifications

This chapter provides information about the REST specifications for Common Services used in Oracle Communications Cloud Native Core Converged Policy. You can use the following APIs to update configurations related to the Overload Control feature.

3.1 OAuth Validator REST API Configuration

This REST API configuration is required for enabling access token validation using NRF Instance ID and key-ID (K-ID).

Before this configuration, perform the prerequisite steps and helm configuration explained in "Configuring Secrets to Enable Access Token " section in *Oracle Communications Cloud Native Core, Converged Policy Installation, Upgrade and Fault Recovery Guide*.

After the Helm configuration, send the REST requests to Ingress Gateway to use configured public key certificates. Using REST-based configuration, you can distinguish between the certificates configured on different NRFs and can use these certificates to validate the token received from a specific NRF.

This REST API configuration is required for enabling access token validation using NRF Instance ID and key-ID (K-ID). This URI can be used to update oauth configuration that is used for validating token sent in request to Ingress Gateway. By default, the `instanceIdlist` and `keyIdList` are null and validation mode is `INSTANCEID_ONLY`.

Table 3-1 OAuth Validator Configuration

Description	HT TP Me tho d or Cu sto m Op era tio n	Resource URI	Content Type
Update or Add oauth configuration that will be used for validating token sent in request to Ingress Gateway. Note: By default, instanceIdList, keyIdList are null and validation mode is INSTANCEID_ONLY. This configuration is only applicable when oauth feature is enabled via Helm chart.	P U T	/{nfType}/nf-common-component/v1/{serviceName}/oauthvalidatorconfiguration Example: http://10.75.152.236:8000/pcf/nf-common-component/v1/igw/oauthValidatorConfiguration	applicati on/json

Sample JSON:

```
"oauthValidatorConfiguration": {
  "type": "object",
  "description": "Validator configurations for OAuth",
  "properties": {
    "keyIdList": {
      "type": ["array", "null"],
      "uniqueItems": true,
      "maxItems": 150,
      "description": "Array containing KID based configuration",
      "items": {
        "anyOf": [
```

```

        {
            "type": "object",
            "properties": {
                "keyId": {"type": "string", "minLength": 1, "maxLength":
36, "pattern": "[a-zA-Z0-9]"},
                "kSecretName": {"type": "string"},
                "certName": {"type": "string"},
                "certAlgorithm": {"type": "string"}
            },
            "required": [
                "keyId",
                "kSecretName",
                "certName",
                "certAlgorithm"
            ]
        }
    ],
    },
    "instanceIdList": {
        "type": ["array", "null"],
        "uniqueItems": true,
        "maxItems": 150,
        "description": "Array containing Instance Id based configuration",
        "items": {
            "anyOf": [
                {
                    "type": "object",
                    "properties": {
                        "instanceId": {"type": "string"},
                        "kSecretName": {"type": "string"},
                        "certName": {"type": "string"},
                        "certAlgorithm": {"type": "string"}
                    },
                    "required": [
                        "instanceId",
                        "kSecretName",
                        "certName",
                        "certAlgorithm"
                    ]
                }
            ]
        }
    },
    "oauthValidationMode": {
        "type": "string",
        "enum": [
            "KID_ONLY",
            "INSTANCEID_ONLY",
            "KID_PREFERRED"
        ],
        "description": "Mode of validation"
    }
}

```

3.2 CCA Header Validation

Table 3-2 CCA Header Validation APIs

API Description	HTTP Method or Custom Operation	Resource URI	Description	Possible Result Code
GET CCA header information.	GET	{apiRoot}/ {nfType}/nf- common- component/v1/igw/ ccaheader Content Type: application/json	Gets the details stored in DB for property ccaheader.	See Table A-1
Update the CCA details using PUT.	PUT	{apiRoot}/ {nfType}/nf- common- component/v1/igw/ ccaheader Content Type: application/json	Replaces the existing values with the new value sent.	See Table A-2
Update the CCA details using PATCH.	PATCH	{apiRoot}/ {nfType}/nf- common- component/v1/igw/ ccaheader Content Type: application/json	Updates the value of the parameters modified.	See Table A-2

Get and Update Operations

Table 3-3 Request/Response Body Parameters

Attribute Name	Data Type	Mandatory(M)/Optional(O)/Conditional(C)	Description
enabled	boolean	M	Indicates if the CCA validation feature flag is enabled or disabled. Note: This is a read-only parameter. If you want to enable this feature, use <code>metadata.ccaHeaderValidation.enabled</code> parameter in <code>routesConfig</code> for <code>accesstoken_mapping</code> id in Helm. Constraints: true, false Default Value: false
minExpiryTime	integer	NA	Indicates the minimum time of expiry for the CA Root certificate. Default Value: 0
maxTokenAge	integer	M	Indicates the maximum token age allowed. Note: It skips the check if the value is 0. Constraints: 0 - 86400 seconds Default Value: 0

Table 3-3 (Cont.) Request/Response Body Parameters

Attribute Name	Data Type	Mandatory(M)/Optional(O)/Conditional(C)	Description
role	string	M	Indicates the CCA token validator role to match the audience claim in the header. Note: This is a read-only parameter. Default Value: NRF
subKey	string	M	Indicates if the certificate extension name to be read in the public key certificate received in CCA request. Note: This is a read-only parameter. Default Value: subjectAltName
validationRule	string	M	Indicates the CCA validation rule. - strict: NRF validation rules are applied. - relaxed: "Issued At" validation is not mandatory. Validation rules are applied to Producer NF. Constraints: strict, relaxed Default Value: strict
k8SecretName	string	M	Indicates the name of the Kubernetes secret in which the CA bundle is present. Note: After fresh installation, these attributes must be configured with appropriate values as per the system requirement using the Rest API as these values are sample ones. Example k8SecretName: ocnrfacesstoken-secret
k8NameSpace	string	M	Indicates the Kubernetes namespace in which CA bundle is present. Note: After fresh installation, these attributes must be configured with appropriate values as per the system requirement using the Rest API as these values are sample ones. Example k8NameSpace: b2-gate-zeta-13775736-pcf1
fileName	string	M	Indicates the name of the CA bundle file used for CCA. This is the file generated by certificate and key generation steps. Note: After fresh installation, these attributes must be configured with appropriate values as per the system requirement using the Rest API as these values are sample ones. Example: fileName: caroot.cer

Sample Body Request:

```

"role": "NRF",
"subKey": "subjectAltName",
"enabled": true,
"fileName": "caroot.cer",
"k8NameSpace": "b2-gate-zeta-13775736-pcf1",

```

```
"maxTokenAge":10,
"k8SecretName":"ocnrfacesstoken-secret",
"minExpiryTime":1000,
"validationRule":"strict"
```

3.3 XFCC Header Validation

Table 3-4 XFCC Header Validation APIs

API Description	HTTP Method or Custom Operation	Resource URI	Description	Possible Result Code
GET XFCC Header Validation	GET	/nfType/nf-common-component/v1/{serviceName}/xfccheadervalidation	Fetches the details stored in db for property xfccheadervalidation.	See Table A-1
PUT XFCC Header Validation	PUT	{apiRoot}/nfType/nf-common-component/v1/igw/ccaheader	Replaces the existing parameter values with the new values.	See Table A-2

Get and Put Operations

Table 3-5 Request/Response Body Parameters

Attribute Name	Data Type	Mandatory(M)/Optional(O)/Conditional(C)	Description
extract	boolean	M	For more information, see Table 3-6
validation			For more information, see Table 3-7
matchcerts		M (If xfccheader validation is enabled)	The number of certificates that need to be validated starting from the right most entry in the XFCC header
matchfield		M (If xfccheader validation is enabled)	Field in a XFCC header against which the configured nfList FQDN validation needs to be performed
dnsresolutioninterval		M	This will be used for triggering dns resolution scheduler as per time interval configured.

Table 3-6 Extract

Attribute Name	Data Type	Mandatory(M)/Optional(O)/Conditional(C)	Description
extract.enabled	boolean	M	

Table 3-6 (Cont.) Extract

Attribute Name	Data Type	Mandatory(M)/Optional(O)/Conditional(C)	Description
extract.extractfield		M	
extract.certextractfield	integer	M	

Table 3-7 validation

Attribute Name	Data Type	Mandatory(M)/Optional(O)/Conditional(C)	Description
validation.enabled		O	Determines if incoming xfcc header needs to be validated
validation.peerlist		M (If xfccheader validation is enabled)	List of configured NF FQDN's against which the matchField entry configured, present in XFCC Header will be validated. For example, name, enabled, scheme, and type. For more information, see Table 3-8

Table 3-8 peerlist

Attribute Name	Data Type	Mandatory(M)/Optional(O)/Conditional(C)	Description
name	string	O	
enabled	boolean	O	
scheme	string	O	
type	string	O	

Sample Body Request:

```
{
  "extract": {
    "enabled": false,
    "extractfield": "DNS",
    "extractindex": 0,
    "certextractindex": 0
  },
  "validation": {
    "enabled": true,
    "peerList": [
      {
        "name": "xyz.test.com",
        "enabled": true,
        "scheme": "http",
        "type": "virtual"
      },
      {
        "name": "abc.test.com",
        "enabled": true,

```



```

        "scheme": "https",
        "type": "virtual"
    },
    {
        "name": "scp1.com",
        "enabled": true
    },
    {
        "name": "scp2.com",
    },
    {
        "name": "scp3.com",
        "enabled": false
    }
  ],
  "matchcerts": -1,
  "matchfield": "DNS",
  "dnsresolutioninterval": 300000
}
}

```

3.4 Egress Gateway for SCP Health

Peer Configuration

Table 3-9 Peer Configuration supported REST APIs details:

Description	HTTP Method or Custom Operation	Resource URI	Content Type	Possible Result Codes
Get Peer Configuration	GET	/nfType/nf-common-component/v1/{serviceName}/peerconfiguration	application/json	See Table A-1
Update Peer Configuration	PUT	/nfType/nf-common-component/v1/{serviceName}/peerconfiguration	application/json	See Table A-2
Get All Peer Configuration	GET	/nfType/nf-common-component/v1/{serviceName}/{instanceId}/peerconfiguration	application/json	See Table A-1
Update All Peer Configurations	PUT	/nfType/nf-common-component/v1/{serviceName}/{instanceId}/peerconfiguration	application/json	See Table A-2

Table 3-10 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
id	string	O	Peer identifier Note: Unique value in peerconfiguration
host	string	O	Host details of a peer.It can be IPv4, IPv6 and FQDN details.
virtualHost	string	O	Host details of a remote peer. For SLF feature, the virtualHost is SCP peer details. It must be a valid FQDN.This FQDN is sent to Alternate Route Service for DNS SRV resolution.
port	string	O	Port details of a peer.
apiPrefix	string	O	API prefix details of a peer. Note: Keep the value as '/' only
healthApiPath	string	O	Path of health API / scp-api-root/v1/status. This attribute is added to maintain the health status of the API. This attribute is added as part of monitoring the availability of SCP health status.

Peer Monitoring Configuration**Table 3-11 Peer Monitoring Configuration supported REST APIs details:**

Description	HTTP Method or Custom Operation	Resource URI	Content Type	Possible Result Codes
Get Peer Monitoring Configuration	GET	/nfType/nf-common-component/v1/{serviceName}/peermonitoringconfiguration	application/json	See Table A-1
Update Peer Monitoring Configuration	PUT	/nfType/nf-common-component/v1/{serviceName}/peermonitoringconfiguration	application/json	See Table A-2

Table 3-11 (Cont.) Peer Monitoring Configuration supported REST APIs details:

Description	HTTP Method or Custom Operation	Resource URI	Content Type	Possible Result Codes
Get All of Peer Monitoring Configuration	GET	/nfType}/nf-common-component/v1/{serviceName}/{instanceId}/peermonitoringconfiguration	application/json	See Table A-1
Update All of Peer Monitoring Configurations	PUT	/nfType}/nf-common-component/v1/{serviceName}/{instanceId}/peermonitoringconfiguration	application/json	See Table A-2

Table 3-12 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/Optional(O)/Conditional(C)	Description
enabled	Boolean	O	Attribute to enable or disable monitoring at a global level. Default value: false
timeout	Long	O	Flag to configure the duration after which calls to the SCP health API is timed out. This is provided in milliseconds. The allowed value ranges from 300 milliseconds to 10000 milliseconds. Default value: 1000
frequency	Long	O	Indicates the frequency or interval at which Egress Gateway microservice initiates health check calls toward SCP. This is provided in milliseconds. The allowed value ranges from 300 milliseconds to 10000 milliseconds. Default value: 2000

Table 3-12 (Cont.) Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
failureThreshold	Integer	O	Indicates the number of consecutive failure responses after which a healthy SCP can be marked as unhealthy. The allowed value ranges 1 to 10. The maximum number of attempts to mark SCP unhealthy is 10. Default value: 3
successThreshold	Integer	O	Indicates the number of successful responses after which an unhealthy SCP can be marked as healthy. Health API call to given SCP shall succeed consecutively to these many attempts before it is marked as Available from UNAVAILABLE. The allowed value ranges 1 to 10. Default value: 3

Sample body:

```
{
  "enabled":true,
  "timeout":1000,
  "frequency":2000,
  "failureThreshold":3,
  "successThreshold":3
}
```

Peer Set Configuration

Table 3-13 Peerset Configuration supported REST APIs details:

Description	HTTP Method or Custom Operation	Resource URI	Content Type	Possible Result Codes
Get Peerset Configuration	GET	{apiRoot}/egw/healthStatus/peerSet/{peerSetId}	application/json	See Table A-1
List of Peerset Configuration	GET	{apiRoot}/egw/healthStatus/peerSet	application/json	See Table A-1

Table 3-13 (Cont.) Peerset Configuration supported REST APIs details:

Description	HTTP Method or Custom Operation	Resource URI	Content Type	Possible Result Codes
Get the list of peer sets wherein each peer set consists of ID and list of http or https instances.	GET	/{{nfType}}/nf-common-component/v1/{serviceName}/peersetconfiguration	application/json	See Table A-1
Add or update the list of peer sets wherein each peer set consists of ID and list of http or https instances.	PUT, PATCH,	/{{nfType}}/nf-common-component/v1/{serviceName}/peersetconfiguration	application/json	see Table A-2

Table 3-14 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/Optional(O)/Conditional(C)	Description
id	string	O	Identifier for Peer Set
httpConfiguration	array(PeerIdentifierConfiguration)	O	Configuration for HTTP based Peers. This value will be selected, if 3GPPAPIRootScheme value is http
httpsConfiguration	array(PeerIdentifierConfiguration)	O	Configuration for HTTPS based Peers. This value will be selected, if 3GPPAPIRootScheme value is https

Table 3-15 PeerIdentifierConfiguration

Field Name	Data Type	Mandatory(M)/Optional(O)/Conditional(C)	Description
priority	integer	O	Priority of peer to be used in a peer set
peerIdentifier	string	O	Peer identifier is the value of peer configured during PeerConfiguration

Sample body:

```
peerSetConfiguration[
  {
    "id": "set0",
    "httpConfiguration": [
      {
```

```

    "priority": 1,
      "peerIdentifier": "peer1"
    }],
    "httpsConfiguration":[
    {
    "priority": 1,
      "peerIdentifier": "peer1"
    }
  ]

```

3.5 OC Policy Mapping

This URI can be used to update service names and corresponding policy name for the service which is mapped to "ocDiscardPolicies" based on "policyName" and also to enable/disable the Overload Control feature and the sampling period in overload control. By default, the Overload Control feature is disabled and the sampling period is the 60s. To enable the feature, REST API needs to be invoked and update the enabled flag to true.

Table 3-16 Supported REST APIs

Description	HTTP Method or Custom Operation	Resource URI
Get OC Policy Mapping	GET	PCF/nf-common-component/v1/{serviceName}/ocpolycymapping
Update OC Policy Mapping	PUT	PCF/nf-common-component/v1/{serviceName}/ocpolycymapping
Partially OC Policy Mapping	PATCH	PCF/nf-common-component/v1/{serviceName}/ocpolycymapping

Get, Update, and Patch OCPolicyMapping

Table 3-17 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)aints	Description
enabled	boolean	M	To enable or disable Overload Control feature. Set values to: - true: To enable - false: To disable
mappings.svcName	string	M	The SVC entry to determine a mapping between service and discard policy name per service.
mappings.policyName	string	M	The discard policy entry to determine a mapping between service and discard policy name per service.

Table 3-17 (Cont.) Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)aints	Description
samplingPeriod	integer	M	Time frame for each cycle of Overload Control per service. Its value is in milliseconds.

Sample Request/Response body structure for GET, PUT, and PATCH operations:

```
{
  "enabled": true,
  "mappings": [
    {
      "svcName": "sm.pcf.com",
      "policyName": "OCDP1"
    },
    {
      "svcName": "cm.pcf.com",
      "policyName": "OCDP2"
    },
    {
      "svcName": "localhost",
      "policyName": "OCDP3"
    }
  ],
  "samplingPeriod": 200
}
```

3.6 Error Code Profiles

This URI can be used to update the errorCodeProfiles that are used in Overload Control feature for populating details in error responses when a request is discarded.

By default, the errorCodeProfiles remains null.

Table 3-18 Supported REST APIs

Description	HTTP Method or Custom Operation	Resource URI
Get error code profiles	GET	PCF/nf-common-component/v1/{serviceName}/errorcodeprofiles
Update error code profiles	PUT	PCF/nf-common-component/v1/{serviceName}/{instanceId}/errorcodeprofiles
Partially update the error code profiles	PATCH	PCF/nf-common-component/v1/{serviceName}/{instanceId}/errorcodeprofiles

Get, Update, and Patch errorCodeProfile

Table 3-19 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/Optional(O)/Conditional(C)	Description
name	string	M	Error name.
errorCode	integer	M	errorCode field in an errorScenario determines the HttpStatusCode that needs to be populated in ProblemDetails (HttpStatus field) response from IGW when the exception occurred at IGW matches the configured errorScenario's exceptionType field.
errorCause	string	O	errorCause field in an errorScenario determines the error cause that needs to be populated in ProblemDetails (Cause field) response from IGW when the exception occurred at IGW matches the configured errorScenario's exceptionType parameter.
errorTitle	string	O	errorTitle field in an errorScenario determines the title that needs to be populated in ProblemDetails (Title field) response from IGW when the exception occurred at IGW matches the configured errorScenario's exceptionType parameter.
redirectURL	string	O	redirectUrl field in an errorScenario determines the redirection URL, this value is populated in LOCATION header while sending response from IGW. The header is populated only when the exception occurred at IGW matches the configured errorScenario's exceptionType parameter, the errorCode configured for the particular errorScenario lies in 3xx error series and the redirectUrl field for the particular errorScenario is configured appropriately.
retry-after	string	O	retryAfter field in an errorScenario determines the value in seconds/ particular date after which the service should be retried, this value is populated in Retry-After header while sending response from IGW. The header is populated only when the exception occurred at IGW matches the configured errorScenario's exceptionType parameter, the errorCode configured for the particular errorScenario lies in 3xx error series and the retryAfter field for the particular errorScenario is configured appropriately in seconds.
errorDescription	string	O	errorDescription field in an errorScenario determines the description that needs to be populated in ProblemDetails (Detail field) response from IGW when the exception occurred at IGW matches the configured errorScenario's exceptionType field.

Sample Request/Response body structure for GET, PUT, and PATCH operations:

```
[
{
```



```

    "name": "error300",
    "errorCode": 300,
    "errorCause": "",
    "errorTitle": "",
    "redirectURL": "",
    "retry-after": "",
    "errorDescription": ""
  },
  {
    "name": "error500",
    "errorCode": 500,
    "errorCause": "",
    "errorTitle": "",
    "redirectURL": "",
    "retry-after": "",
    "errorDescription": ""
  },
  {
    "name": "error429",
    "errorCode": 429,
    "errorCause": "",
    "errorTitle": "",
    "redirectURL": "",
    "retry-after": "",
    "errorDescription": ""
  }
]

```

3.7 OC Discard Policies

This URI can be used to update discard policies that will be used in overload control to select the appropriate policy from the configured list based on the load level of a particular service. By default, ocDiscardPolicies will be null.

Table 3-20 Supported REST APIs

Description	HTTP Method or Custom Operation	Resource URI
Get Discard Policies	GET	PCF/nf-common-component/v1/{serviceName}/ocdiscardpolicies
Update Discard Policy	PUT	PCF/nf-common-component/v1/{serviceName}/ocdiscardpolicies
Partially update the Discard Policy	PATCH	PCF/nf-common-component/v1/{serviceName}/ocdiscardpolicies

Get, Update, and Patch OCDiscardData

Table 3-21 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/Optional(O)/Conditional(C)	Description
name	string	M	Name of the discarded policy.
scheme	string The value can be: - PriorityBased - PercentageBased	M	Discarded policy scheme.
policies.value	integer	M	Value of priority above which requests are considered as potential candidates for drop. Percentage of requests to drop in the current sampling period over the calculated rate in the previous sampling period.
policies.action	string The value can be: RejectWithErrorCode	O	Defines the action to be taken on selected requests rejection based on error code.
policies.level	string	O	Defines the overload level.
policies.errorCodeProfile	string	O	The error code profiles.

Sample Request/Response body structure for GET, PUT, and PATCH operations:

```
[
{
  "name": "OCDP2",
  "scheme": "PercentageBased",
  "policies": [
    {
      "value": 20,
      "action": "RejectWithErrorCode",
      "level": "L1",
      "errorCodeProfile": "error411"
    },
    {
      "value": 40,
      "action": "RejectWithErrorCode",
      "level": "L2",
      "errorCodeProfile": "error412"
    },
    {
      "value": 60,
      "action": "RejectWithErrorCode",
      "level": "L3",
```

```

        "errorCodeProfile": "error413"
    },
    {
        "value": 80,
        "action": "RejectWithErrorCode",
        "level": "L4",
        "errorCodeProfile": "error414"
    },
    {
        "value": 95,
        "action": "RejectWithErrorCode",
        "level": "L5",
        "errorCodeProfile": "error415"
    }
  ]
},
{
  "name": "OCDP1",
  "scheme": "PriorityBased",
  "policies": [
    {
      "value": 30,
      "action": "RejectWithErrorCode",
      "level": "Minor",
      "errorCodeProfile": "error300"
    },
    {
      "value": 20,
      "action": "RejectWithErrorCode",
      "level": "Critical",
      "errorCodeProfile": "error500"
    }
  ]
}
]

```

3.8 Overload Level Threshold

This URI can be used to configure the Overload Threshold Level. The data is saved in a line with service_name perf-info and used by the overload manager.

Table 3-22 Supported REST APIs

Description	HTTP Method or Custom Operation	Resource URI
Get Overload Threshold Value of the required SVC (Backend service).	GET	/PCF/nf-common-component/v1/perf-info/overloadLevelThreshold
Update the Overload Threshold Value of the required SVC (Backend service).	PUT	/PCF/nf-common-component/v1/perf-info/overloadLevelThreshold
Delete the Overload Threshold Value of the required SVC (Backend service).	DELETE	/PCF/nf-common-component/v1/perf-info/overloadLevelThreshold

Update overloadLevelThreshold

Table 3-23 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M) / Optional(O) Conditional(C)	Description
svcName	string	M	Name of the backend service (svcName). You can configure the threshold values for the following services: • PCRF Core • Diameter Connector • PCF Session Management • PCF Access and Mobility • PCF UE Policy • CHF Connector • UDR Connector Note For PCRF-CORE deployment mode, configuring overload level threshold for SM Service, AM Service, and UE Policy Service is not required. For PCF deployment mode, configuring the overload level threshold for PCRF Core is not required.
metricsThresholdList	array	M	List of criteria used to calculate the load level.
metricsThresholdList.metricsName	string	M	Name of criteria: • cpu • svc_pending_count • svc_failure_count • memory
metricsThresholdList.levelThresholdList	array	M	List of threshold values
metricsThresholdList.levelThresholdList.level	string	M	Specifies the name of the level: L1/L2/L3

Table 3-23 (Cont.) Request/Response Body Parameters

Field Name	Data Type	Mandatory(M) / Optional(O) Conditional(C)	Description
metricsThresholdList.levelThresholdList.abatementValue	integer	M	If the metric level goes below this value, load level goes to a lower value. The abatement values for each of the metrics are as follows: - cpu (Calculated in percentage (%)) and ranges between 1-100 - svc_pending_count (Accepts an integer value) and ranges between 1 to 1000000 - svc_failure_count (Accepts an integer value) and ranges between 1 to 1000000 - memory (Calculated in percentage (%)) and ranges between 1-100
metricsThresholdList.levelThresholdList.onsetValue	integer	M	If the metric level goes above this value, load level is set. The onset value of L1 is less than the abatement value of L2 and the onset value of L2 is less than the abatement value of L3. The onset values for each of the metrics are as follows: - cpu (Calculated in percentage (%)) and ranges between 1-100 - svc_pending_count (Accepts an integer value) and ranges between 1 to 1000000 - svc_failure_count (Accepts an integer value) and ranges between 1 to 1000000 - memory (Calculated in percentage (%)) and ranges between 1-100

Sample Request/Response body structure for GET/PUT operation:

```
[
  {
    "svcName": "ztt-overload-ocnp-pcf-sm",
    "metricsThresholdList": [
      {
        "metricsName": "svc_pending_count",
        "levelThresholdList": [
          {
            "level": "L1",
            "onsetValue": 50,
            "abatementValue": 40
          },
          {
            "level": "L2",
            "onsetValue": 200,
            "abatementValue": 180
          },
          {
            "level": "L3",
```

```

        "onsetValue": 400,
        "abatementValue": 360
    },
    {
        "level": "L4",
        "onsetValue": 600,
        "abatementValue": 540
    },
    {
        "level": "L5",
        "onsetValue": 800,
        "abatementValue": 720
    }
]
}
}
]

```

3.8.1 Overload Level Threshold Profiles

This URI can be used to configure the Overload Threshold Level Profiles. The data is saved in a line with service_name perf-info and used by the overload manager.

Table 3-24 Supported REST APIs

Description	HTTP Method or Custom Operation	Resource URI
Get the Overload Threshold Profile of the required SVC (Backend service).	GET	/oc-cnpolicy-configuration/v1/overloadlevelThreshold/activeProfile For details on Request/Response Body Parameters for GET activeProfile, see Table 3-25
Activate the Overload Threshold Profile	PUT	/oc-cnpolicy-configuration/v1/overloadlevelThreshold/activeProfile For details on Request/Response Body Parameters for PUT activeProfile, see Table 3-25
Get all the overload threshold profiles names which includes default and custom profiles	GET	/oc-cnpolicy-configuration/v1/overloadlevelThreshold/profiles For details on Request/Response Body Parameters for GET profiles, see Table 3-26
Get Overload Threshold Value for particular profile.	GET	/oc-cnpolicy-configuration/v1/overloadlevelThreshold/profiles/{name} For details on Request/Response Body Parameters for GET profiles/{name}, see Table 3-27

Table 3-24 (Cont.) Supported REST APIs

Description	HTTP Method or Custom Operation	Resource URI
Adds a new Overload Threshold Profile	POST	/oc-cnpolicy-configuration/v1/overloadlevelThreshold/profiles/{name} For details on Request/Response Body Parameters for POST profiles/{name}, see Table 3-27
Update the profile.	PUT	/oc-cnpolicy-configuration/v1/overloadlevelThreshold/profiles/{name} For details on Request/Response Body Parameters for PUT profiles/{name}, see Table 3-27
Delete the Overload Threshold Profile of the required SVC (Backend service).	DELETE	/oc-cnpolicy-configuration/v1/overloadlevelThreshold/profiles/{name}
Migrate the data from standalone to profile i.e if any overloadlevelThreshold data is already configured then it will migrate that data to profile name - Name of the profile activate - if after migration , profile should be activated	POST	/oc-cnpolicy-configuration/v1/overloadlevelThreshold/migrate For details on Request/Response Body Parameters for POST migrate, see Table 3-28
Exports the Overload Threshold Profile.	GET	/oc-cnpolicy-configuration/v1/overloadlevelThreshold/export
Imports the Overload Threshold Profile.	POST	/oc-cnpolicy-configuration/v1/overloadlevelThreshold/import For details on Request/Response Body Parameters for POST (import), see Table 3-29 .

Table 3-25 Request/Response Body Parameters for GET/PUT activeProfile

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
name	string	M	Name of the active profile.

Sample Request/Response for GET/PUT activeProfile

```
{
  "name": "custom"
}
```

Table 3-26 Request/Response Body Parameters for GET profiles

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
name	string	M	Name of the profile.
isCustomProfile	string	M	To specify the type of profile: default or custom

Sample Request/Response for GET profiles

```
[
  {
    "name":"default",
    "isCustomProfile":false
  },{
    "name":"custom",
    "isCustomProfile":true
  }
]
```

Table 3-27 Request/Response Body Parameters for GET/PUT/POST profiles/{name}

Field Name	Data Type	Mandatory(M) /Optional(O) Conditional(C)	Description
name	string	M	Name of the profile.

**Table 3-27 (Cont.) Request/Response Body Parameters for GET/PUT/POST profiles/
{name}**

Field Name	Data Type	Mandatory(M))/ Optional(O)/ Conditional(C)	Description
value.svcName	string	M	Name of the backend service (svcName). You can configure the threshold values for the following services: • PCRF Core • Diameter Connector • PCF Session Management • PCF Access and Mobility • PCF UE Policy • CHF Connector • UDR Connector
value.metricsThresholdList	array	M	List of criteria used to calculate the load level.
value.metricsThresholdList.metricsName	string	M	Name of criteria: • cpu • svc_pending_count • svc_failure_count • memory
value.metricsThresholdList.levelThresholdList	array	M	List of threshold values
value.metricsThresholdList.levelThresholdList.level	string	M	Specifies the name of the level: L1/L2/L3.

Note

For PCRF-CORE deployment mode, configuring overload level threshold for SM Service, AM Service, and UE Policy Service is not required.

For PCF deployment mode, configuring the overload level threshold for PCRF Core is not required.

Table 3-27 (Cont.) Request/Response Body Parameters for GET/PUT/POST profiles/{name}

Field Name	Data Type	Mandatory(M) Optional(O) Conditional(C)	Description
value.metricsThresholdList.abatementValue	integer	M	If the metric level goes below this value, load level goes to a lower value. The abatement values for each of the metrics are as follows: - cpu (Calculated in percentage (%)) and ranges between 1-100 - svc_pending_count (Accepts an integer value) and ranges between 1 to 1000000 - svc_failure_count (Accepts an integer value) and ranges between 1 to 1000000 - memory (Calculated in percentage (%)) and ranges between 1-100
value.metricsThresholdList.onsetValue	integer	M	If the metric level goes above this value, load level is set. The onset value of L1 is less than the abatement value of L2 and the onset value of L2 is less than the abatement value of L3. The onset values for each of the metrics are as follows: - cpu (Calculated in percentage (%)) and ranges between 1-100 - svc_pending_count (Accepts an integer value) and ranges between 1 to 1000000 - svc_failure_count (Accepts an integer value) and ranges between 1 to 1000000 - memory (Calculated in percentage (%)) and ranges between 1-100

Sample Request/Response for GET/PUT/POST profiles/{name}

```
{
  "name": "custom",
  "value": [
    {
      "svcName": "service-name-pcrf-core",
      "metricsThresholdList": [
        {
          "metricsName": "cpu",
          "levelThresholdList": [
            {
              "level": "L1",
              "onsetValue": 49,
              "abatementValue": 41
            },
            {
              "level": "L2",
              "onsetValue": 48,
              "abatementValue": 47
            }
          ]
        }
      ]
    }
  ]
}
```

```

{
  "level": "L3",
  "onsetValue": 52,
  "abatementValue": 50
}
]
}
]
}
]
}
]
}

```

Table 3-28 Request/Response Body Parameters for POST migrate

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
name	string	M	Name of the profile to migrate.
activate	string	M	To activate the profile. Set value to: • true: To activate • false: Not to activate

Sample request/response for GET profiles list

```

{
  "name": "migrate_profile",
  "activate": true/false
}

```

Table 3-29 Request/Response Body Parameters for POST (import)

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
exportData.name	string	M	Name of the profile.

Table 3-29 (Cont.) Request/Response Body Parameters for POST (import)

Field Name	Data Type	Mandatory(M) / Optional(O) Conditional(C)	Description
exportData.value.svcName	string	M	Name of the backend service (svcName). You can configure the threshold values for the following services: • PCRF Core • Diameter Connector • PCF Session Management • PCF Access and Mobility • PCF UE Policy • CHF Connector • UDR Connector Note For PCRF-CORE deployment mode, configuring overload level threshold for SM Service, AM Service, and UE Policy Service is not required. For PCF deployment mode, configuring the overload level threshold for PCRF Core is not required.
exportData.value.metricsThresholdList	array	M	List of criteria used to calculate the load level.
exportData.value.metricsThresholdList.metricsName	string	M	Name of criteria: • cpu • svc_pending_count • svc_failure_count • memory
exportData.value.metricsThresholdList.levelThresholdList	array	M	List of threshold values
exportData.value.metricsThresholdList.levelThresholdList.level	string	M	Specifies the name of the level: L1/L2/L3.

Table 3-29 (Cont.) Request/Response Body Parameters for POST (import)

Field Name	Data Type	Mandatory(M) / Optional(O) Conditional(C)	Description
exportData.value.metricsThresholdList.levelThresholdList.abatementValue	integer	M	If the metric level goes below this value, load level goes to a lower value. The abatement values for each of the metrics are as follows: - cpu (Calculated in percentage (%)) and ranges between 1-100 - svc_pending_count (Accepts an integer value) and ranges between 1 to 1000000 - svc_failure_count (Accepts an integer value) and ranges between 1 to 1000000 - memory (Calculated in percentage (%)) and ranges between 1-100
exportData.value.metricsThresholdList.levelThresholdList.onsetValue	integer	M	If the metric level goes above this value, load level is set. The onset value of L1 is less than the abatement value of L2 and the onset value of L2 is less than the abatement value of L3. The onset values for each of the metrics are as follows: - cpu (Calculated in percentage (%)) and ranges between 1-100 - svc_pending_count (Accepts an integer value) and ranges between 1 to 1000000 - svc_failure_count (Accepts an integer value) and ranges between 1 to 1000000 - memory (Calculated in percentage (%)) and ranges between 1-100

Sample Request/Response Body Parameters for POST (import)

```

"exportData": [
  {
    "name": "TestProfile",
    "value": [
      {
        "svcName": "pcrf-core",
        "metricsThresholdList": [
          {
            "metricsName": "cpu",
            "levelThresholdList": [
              {
                "level": "L1",
                "abatementValue": 41,
                "onsetValue": 44
              },
              {
                "level": "L2",
                "abatementValue": 47,
                "onsetValue": 49
              }
            ]
          }
        ]
      }
    ]
  }
]

```

```

    },
    {
      "level": "L3",
      "abatementValue": 50,
      "onsetValue": 52
    }
  ]
},
}

```

3.9 NF profile registration with NRF

These URIs can be used to update or retrieve PCF NF profile to be registered with Network Repository Function (NRF).

Table 3-30 Supported REST APIs

Description	HTTP Method or Custom Operation	Resource URI
Get PCF NfProfile	GET	PCF/nf-common-component/v1/nrf-client-nfmanagement/nfProfileList
Update PCF NfProfile	PUT	PCF/nf-common-component/v1/nrf-client-nfmanagement/nfProfileList

The sample request body structure for GET and PUT operation is as follows:

```

[
  {
    "nfInstanceId": "fe7d992b-0541-4c7d-ab84-c6d70b1b0123",
    "nfType": "PCF",
    "nfStatus": "REGISTERED",
    "plmnList": null,
    "nsiList": null,
    "fqdn": "occp-ocpm-ingress-gateway.ocpcf.svc",
    "interPlmnFqdn": null,
    "ipv4Addresses": null,
    "ipv6Addresses": null,
    "priority": null,
    "capacity": null,
    "load": 80,
    "locality": null,
    "pcfInfo": {
      "dnnList": [
        "internet",
        "volte"
      ],
      "supiRanges": [
        {
          "start": "12123444444",
          "end": "232332323323232",
          "pattern": null
        }
      ]
    }
  }
]

```

```

    ]
  },
  "customInfo":null,
  "recoveryTime":null,
  "nfServices":[
    {
      "serviceInstanceId":"03063893-cf9e-4f7a-9827-067f6fa9dd01",
      "serviceName":"npcf-am-policy-control",
      "versions":[
        {
          "apiVersionInUri":"v1",
          "apiFullVersion":"1.0.0",
          "expiry":null
        }
      ],
      "scheme":"http",
      "nfServiceStatus":"REGISTERED",
      "fqdn":"occpn-ocpm-ingress-gateway.ocpcf.svc",
      "interPlmnFqdn":null,
      "ipEndpoints":null,
      "apiPrefix":null,
      "defaultNotificationSubscriptions":null,
      "allowedPlmns":null,
      "allowedNfTypes":[
        "AMF",
        "NEF"
      ],
      "allowedNfDomains":null,
      "allowedNssais":null,
      "priority":null,
      "capacity":null,
      "load":null,
      "recoveryTime":null,
      "supportedFeatures":null
    },
    {
      "serviceInstanceId":"03063893-cf9e-4f7a-9827-067f6fa9dd02",
      "serviceName":"npcf-smpolicycontrol",
      "versions":[
        {
          "apiVersionInUri":"v1",
          "apiFullVersion":"1.0.0",
          "expiry":null
        }
      ],
      "scheme":"http",
      "nfServiceStatus":"REGISTERED",
      "fqdn":"occpn-ocpm-ingress-gateway.ocpcf.svc",
      "interPlmnFqdn":null,
      "ipEndpoints":null,
      "apiPrefix":null,
      "defaultNotificationSubscriptions":null,
      "allowedPlmns":null,
      "allowedNfTypes":[
        "SMF",
        "NEF",

```

```

        "AF"
    ],
    "allowedNfDomains":null,
    "allowedNssais":null,
    "priority":null,
    "capacity":null,
    "load":null,
    "recoveryTime":null,
    "supportedFeatures":null
  },
  {
    "serviceInstanceId":"03063893-cf9e-4f7a-9827-067f6fa9dd03",
    "serviceName":"npcf-ue-policy-control",
    "versions":[
      {
        "apiVersionInUri":"v1",
        "apiFullVersion":"1.0.0",
        "expiry":null
      }
    ],
    "scheme":"http",
    "nfServiceStatus":"REGISTERED",
    "fqdn":"occpn-ocpm-ingress-gateway.ocpcf.svc",
    "interPlmnFqdn":null,
    "ipEndpoints":null,
    "apiPrefix":null,
    "defaultNotificationSubscriptions":null,
    "allowedPlmns":null,
    "allowedNfTypes":[
      "AMF"
    ],
    "allowedNfDomains":null,
    "allowedNssais":null,
    "priority":null,
    "capacity":null,
    "load":null,
    "recoveryTime":null,
    "supportedFeatures":null
  }
]

```

3.10 Server Header at Ingress Gateway

This section describes the Common Config Server URIs that you can use to enable and configure server header at Ingress Gateway. The server header is included in the error responses sent by Ingress Gateway for the errors generated at Ingress Gateway as well as backend microservices.

Note

You can configure server header at both global and route level. However, if you define server header configuration at both global and route level, the route level configuration (irrespective of being enabled or disabled) takes precedence over the global level configuration.

Error Code Series List

The following table describes the URIs available to define and retrieve error code series list:

Table 3-31 Supported REST APIs for Error Code Series List

Description	HTTP Method or Custom Operation	Resource URI
Get Error Code Series List	GET	{apiRoot}/PCF/nf-common-component/v1/igw/errorcodeserieslist
Define Error Code Series List	PUT	{apiRoot}/PCF/nf-common-component/v1/igw/errorcodeserieslist
Delete Error Code Series List	PUT To delete the configurations, put an empty json in the request. []	{apiRoot}/PCF/nf-common-component/v1/igw/errorcodeserieslist

The sample request body structure for PUT operation is as follows:

```
[
  {
    "id": "E1",
    "errorCodeSeries":
    [
      {
        "errorSet": "4xx",
        "errorCodes": [400, 408]
      },
      {
        "errorSet": "5xx",
        "errorCodes": [500, 503]
      }
    ]
  },
  {
    "id": "E2",
    "errorCodeSeries":
    [
      {
        "errorSet": "4xx",
        "errorCodes": [-1]
      }
    ]
  }
]
```

```

    }
  ]
]

```

Table 3-32 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
id	string	M	Specifies the unique ID that is used in the errorCodeSeriesId while configuring server header at global or route level.
errorCodeSeries.errorSet	string	M	Specifies an errorSet (4XX, 5XX) in errorCodeSeries for matching server response.
errorCodeSeries.errorCodes	array	M	Specifies the error codes in a specific error set against which the server response is validated for populating server header.

Configuring Server header (global level)

The following table describes the URIs available to enable and configure server header at global level:

Table 3-33 Supported REST APIs

Description	HTTP Method or Custom Operation	Resource URI
Get Server Header	GET	/PCF/nf-common-component/v1/igw/serverheaderdetails
Define Server Header	PUT	/PCF/nf-common-component/v1/igw/serverheaderdetails

The sample request body structure for PUT operation is as follows:

```

{
    "enabled": false,           # Set to false if we want Server Header
                                # to be generated at Route Level
    "errorCodeSeriesId": "E1",  # See "errorcodeserieslist" resource
                                # above for more details.
    "configuration": {
        "nfType": "PCF",
        "nfInstanceId": "123456" # NF Instance Id of the PCF
    }
}

```

Table 3-34 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/Optional(O)/Conditional(C)	Description
enabled	boolean	M	When the value for this parameter is set to true, server headers are generated at a global level. To generate server headers at route level, set the value to false.
errorCodeSeriesId	string	M	Specifies the error list IDs. For more information, see Table 3-31 .
configuration.nftype	string	M	Specifies the type of network function. Default value: PCF
configuration.nfInstanceId	string	M	Specifies the NF Instance ID of the PCF.

Configuring Server header (route level)

The following table describes the URIs available to enable and configure server header at route level:

Table 3-35 Supported REST APIs

Description	HTTP Method or Custom Operation	Resource URI
Get Route Level Configuration	GET	/PCF/nf-common-component/v1/igw/routesconfiguration
Define Server Header at Route Level	PUT	/PCF/nf-common-component/v1/igw/routesconfiguration

The sample request body structure for PUT operation is as follows:

```
[{
  "id": "sm_create_session_route",
  "serverHeaderDetails": {
    "enabled": true,
    "errorCodeSeriesId": "E1"
  }
}]
```

The sample request body structure to clear route using PUT operation is as follows:

```
[]
```

Table 3-36 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/Optional(O)/Conditional(C)	Description
id	string	M	Specifies the route IDs for which you need to define server header. You can define the server header at route level for any of the following supported route IDs: - sm_create_session_route - sm_delete_session_route - sm_update_session_route - udr_notify_route - chf_terminate_route - chf_notify_route - pa_create_session_route - pa_delete_session_route - pa_update_session_route - pa_events_subscription_route - reverse_ue_service - reverse_user_udr_notify_service - reverse_user_chf_notify_service - reverse_nrf_discovery_service - reverse_nrf_management_service - reverse_nrf_notify_service - reverse_soapconnector_service - reverse_ue_service_notify - am_create_session_route - am_delete_session_route - am_update_session_route
serverHeaderDetails.enabled	boolean	M	Set the value for this parameter to true if you want to define server header at the route level.
serverHeaderDetails.errorCodesId	string	M	Specifies the error list IDs. For more information, see Table 3-31 .

The sample request body structure for GET operation is as follows:

```
[{
  "id":"sm_create_session_route"
}]
```

3.11 Rate Limiting

3.11.1 Rate Limiting at Ingress Gateway

This section describes the URIs that you can use to configure route level rate limiting in persistent configuration at Ingress Gateway.

Error Code Profiles

The following table describes the URIs available to define and retrieve error code profiles in persistent configuration:

Table 3-37 Supported REST APIs for Error Code Profiles

Description	HTTP Method or Custom Operation	Resource URI
Get Error Code Profiles	GET	{apiRoot}/PCF/nf-common-component/v1/igw/errorcodeprofiles
Define Error Code Profiles	PUT	{apiRoot}/PCF/nf-common-component/v1/igw/errorcodeprofiles

The sample request body structure for PUT operation is as follows:

```
[{
  "name": "error429",
  "errorCode": 429,
  "errorCause": "Too Many Request",
  "errorTitle": "",
  "redirectURL": "",
  "retry-after": "",
  "errorDescription": ""
}]
```

Table 3-38 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/Optional(O)/Conditional(C)	Description
name	string	M	Specifies the unique name for the error profile.
errorCode	string	M	errorCode field in an errorScenario determines the HttpStatusCode that needs to be populated in ProblemDetails (HttpStatus field) response from IGW when the exception occurred at IGW matches the configured errorScenario's exceptionType field.
errorCause	string	M	errorCause field in an errorScenario determines the error cause that needs to be populated in ProblemDetails (Cause field) response from IGW when the exception occurred at IGW matches the configured errorScenario's exceptionType parameter.
errorTitle	string	O	errorTitle field in an errorScenario determines the title that needs to be populated in ProblemDetails (Title field) response from IGW when the exception occurred at IGW matches the configured errorScenario's exceptionType parameter.

Table 3-38 (Cont.) Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/Optional(O)/Conditional(C)	Description
redirectURL	string	O	redirectUrl field in an errorScenario determines the redirection URL, this value is populated in LOCATION header while sending response from IGW. The header is populated only when the exception occurred at IGW matches the configured errorScenario's exceptionType parameter, the errorCode configured for the particular errorScenario lies in 3xx error series and the redirectUrl field for the particular errorScenario is configured appropriately.
retry-after	string	O	retryAfter field in an errorScenario determines the value in seconds/ particular date after which the service should be retried, this value is populated in Retry-After header while sending response from IGW. The header is populated only when the exception occurred at IGW matches the configured errorScenario's exceptionType parameter, the errorCode configured for the particular errorScenario lies in 3xx error series and the retryAfter field for the particular errorScenario is configured appropriately in seconds.
errorDescription	string	O	errorDescription field in an errorScenario determines the description that needs to be populated in ProblemDetails (Detail field) response from IGW when the exception occurred at IGW matches the configured errorScenario's exceptionType field.

Configuring Rate Limit for Policy

The following table describes the URIs available to enable and configure ratelimit:

Table 3-39 Supported REST APIs

Description	HTTP Method or Custom Operation	Resource URI
Get Rate Limit	GET	{apiRoot}/PCF/nf-common-component/v1/igw/routelevelratelimiting
Define Rate Limit	PUT	{apiRoot}/PCF/nf-common-component/v1/igw/routelevelratelimiting

The sample request body structure for PUT operation is as follows:

```
{
  "enabled": true,
  "samplingPeriod": 2000,
  "rateLimitPolicies": [
```

```

{
  "name": "R1",
  "value": 5,
  "action": "RejectWithErrorCode",
  "scheme": "PriorityBased",
  "errorCodeProfile": "error429"
}
]
}

```

Table 3-40 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
enabled	boolean	M	Specifies whether to enable or disable rate limiting feature.
samplingPeriod		M	Specifies the duration for each cycle of route rate limit. The value of sampling period is defined in milliseconds.
rateLimitPolicies.name	string	M	Specifies the unique name of the discard policy.
rateLimitPolicies.value	integer	M	Specifies the value of priority above which requests are considered as potential candidates for drop.
rateLimitPolicies.action	string	M	Specifies the action such as silent drop or rejection for the selected requests.
rateLimitPolicies.scheme	string	M	Specifies the scheme on the basis of which requests are selected to be dropped. The only supported value for this parameter is PriorityBased.
rateLimitPolicies.errorCodeProfile	string	M	Specifies the error code profile. For more information, see Table 3-37 .

Configuring Rate Limit for Policy at route level

For details on configuring rate limit for policy at route level, see [Route Level Configuration](#).

3.12 Failure Count at Ingress Gateway

This section describes the URIs that you can use to configure failure count at Ingress Gateway.

Configuring Failure Count Overload**Error Code Series List**

The following table describes the URIs available to define and retrieve error code series list:

Table 3-41 Supported REST APIs for Error Code Series

Description	HTTP Method or Custom Operation	Resource URI
Get Error Code Series List	GET	{apiRoot}/PCF/nf-common-component/v1/igw/errorcodeserieslist
Define Error Code Series List	PUT	{apiRoot}/PCF/nf-common-component/v1/igw/errorcodeserieslist
Delete Error Code Series List	PUT To delete the configurations, put an empty json in the request. []	{apiRoot}/PCF/nf-common-component/v1/igw/errorcodeserieslist

The sample request body structure for PUT operation is as follows:

```
[
  {
    "id": "E1",
    "errorCodeSeries": [
      {
        "errorSet": "4xx",
        "errorCodes": [
          400,
          408
        ]
      },
      {
        "errorCodes": [
          500,
          503
        ]
      }
    ]
  },
  {
    "id": "E2",
    "errorCodeSeries": [
      {
        "errorSet": "5xx",
        "errorCodes": [
          -1
        ]
      }
    ]
  }
]
```


Table 3-42 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/Optional(O)/Conditional(C)	Description
id	string	M	Specifies the unique ID that is used in the errorCodeSeriesId while configuring server header at global or route level.
errorCodeSeries.errorSet	string	M	Specifies an errorSet (4XX, 5XX) in errorCodeSeries for matching server response.
errorCodeSeries.errorCodes	array	M	Specifies the error codes in a specific error set against which the server response is validated for populating server header.

Failure Count for Policy at Route Level

The following table describes the URIs available to define and retrieve failure count at route level:

Table 3-43 Supported REST APIs for Failure Count at Route Level

Description	HTTP Method or Custom Operation	Resource URI
Get failure count at route level Configuration	GET	{apiRoot}/PCF/nf-common-component/v1/igw/routesconfiguration
Define failure count at route level Configuration	PUT	{apiRoot}/PCF/nf-common-component/v1/igw/routesconfiguration

For details on configuring the failure count for Policy at route level, see [Route Level Configuration](#).

Configuring both Failure Count and Rate Limiting Overload**Error Code Series List for Failure Count**

For details on configuring error code series list for failure count, see *Error Code Series List* under *Configuring Failure Count Overload* section.

Error Code Profile for Rate Limiting

For details on configuring error code profile for failure count, see *Error Code Profiles* in [Rate Limiting at Ingress Gateway](#).

Rate Limit for Policy

For details on configuring rate limit for Policy, see *Configuring Rate Limit for Policy* in [Rate Limiting at Ingress Gateway](#).

Route Level for Failure Count and Rate Limiting

For details on configuring the route level for failure count and rate limiting, see [Route Level Configuration](#).

3.13 Route Level Configuration

The following table describes the URIs available to enable and configure rate-limit at route level:

Table 3-44 Supported REST APIs

Description	HTTP Method or Custom Operation	Resource URI
Get Rate Limit at route level Configuration	GET	{apiRoot}/PCF/nf-common-component/v1/igw/routesconfiguration
Define Rate Limit at route level Configuration	PUT	{apiRoot}/PCF/nf-common-component/v1/igw/routesconfiguration

The sample request body structure for PUT operation is as follows:

```
[
  {
    "id": "sm_create_session_route",
    "rateLimiting": {
      "methods": [
        {
          "name": "POST",
          "rate": 3,
          "rateLimitPolicy": "R1"
        }
      ]
    },
    "failureReqCountErrorCodeSeriesId": "E1"
  },
  {
    "id": "sm_update_session_route",
    "rateLimiting": {
      "methods": [
        {
          "name": "POST",
          "rate": 6,
          "rateLimitPolicy": "R1"
        }
      ]
    },
    "failureReqCountErrorCodeSeriesId": "E1"
  },
  {
    "id": "sm_delete_session_route",
    "rateLimiting": {
      "methods": [
        {
          "name": "POST",
          "rate": 3,
          "rateLimitPolicy": "R1"
        }
      ]
    }
  }
]
```

```

    }
  ],
  "failureReqCountErrorCodeSeriesId": "E1"
}
]

```

Table 3-45 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
id	string	M	Specifies the route IDs for which you need to define the rate limit. You can define the rate limit at route level for any of the following supported route IDs. For the list of supported route IDs for each service, see <i>Overload Control</i> section in <i>Oracle Communications Cloud Native Core, Converged Policy User Guide</i> .
rateLimiting.methods.name	string	O	Specifies the name of the HTTP method such as GET, DELETE, or POST. The rate limit is calculated by considering the method along with the route ID.
rateLimiting.methods.rate	integer	O	Specifies the rate for route level rate limit. Any requests with sbi-priority header with a value greater than the configured number are discarded.
rateLimiting.methods.rateLimitPolicy	string	O	Specifies the unique rate limit policy name. For more information, see Table 3-39 .
failureReqCountErrorCodeSeriesId	string	O	Specifies the mapping between error series and failure count.

3.14 Controlled Shutdown at Ingress and Diameter Gateway

This section describes the URIs that you can use to enable and configure Controlled Shutdown at Ingress and Diameter Gateway.

Operational State

The following table describes the URIs available to define and retrieve operational state:

Table 3-46 Supported REST APIs for Operational State

Description	HTTP Method or Custom Operation	Resource URI
GET Operational State	GET	{apiRoot}/oc-cnpolicy-configuration/v1/controlledshutdown/operationalState

Table 3-46 (Cont.) Supported REST APIs for Operational State

Description	HTTP Method or Custom Operation	Resource URI
PUT Operational State	PUT	{apiRoot}/oc-cnpolicy-configuration/v1/controlledshutdown/operationalState

The sample request body structure for PUT operation is as follows:

```
{
  "operationalState": "NORMAL"
}
```

Table 3-47 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/Optional(O)/Conditional(C)	Description
Operational State	Enum - NORMAL - PARTIAL_SHUTDOWN - COMPLETE_SHUTDOWN	M	Specifies the operational state

Operational State History

The following table describes the URIs available to retrieve operational state history:

Table 3-48 Supported REST APIs for Operational State History

Description	HTTP Method or Custom Operation	Resource URI
GET Operational State History	GET	{apiRoot}/oc-cnpolicy-configuration/v1/controlledshutdown/operationalStateHistory

The sample response body structure for GET operation is as follows:

```
[
  {
    "id": "6eb68d0e-d5ef-4daa-ab19-cb8997cab85f",
    "type": "operationalState",
    "value": "{\"state\":\"NORMAL\"}",
    "timeStamp": "2026-07-06T17:31:19.925722",
  }
]
```

```

    "status": "SUCCESS"
  }
]

```

Table 3-49 Request/Response Body Parameters

Field Name	Data Type	Description
id	UUID	Auto-generated ID
type	String	Type of historical data
value	String	Operational state value
timeStamp	Date	Logs the timestamp when the operational state event took place
status	String	- Success: Successful in switching of operational state - Failure: Fail in switching of operational state

Table 3-50 Request Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
Offset	Integer	O	Offset is a position in the set of records.
Limit	Integer	O	Limit as an option allows to limit the number of rows returned from a query.
Page	Integer	O	Page shows the number of records.

Note

If offset and Limit are not provided in the API, then the query fetches all the records from the database.

Controlled Shutdown Error Mapping

The following table describes the URIs available to define and retrieve Controlled Shutdown Error Mapping:

Table 3-51 Supported REST APIs for Controlled Shutdown Error Mapping

Description	HTTP Method or Custom Operation	Resource URI
GET Controlled Shutdown Error Mapping	GET	{apiRoot}/oc-cnpolicy-configuration/v1/controlledshutdown/errorMapping
PUT Controlled Shutdown Error Mapping	PUT	{apiRoot}/oc-cnpolicy-configuration/v1/controlledshutdown/errorMapping

The sample request body structure for PUT operation is as follows:

```
{
  "routeErrorProfileList": [
    {
      "errorProfileName": "ERR_400",
      "routeIds": [
        "sm_update_session_route"
      ]
    },
    {
      "errorProfileName": "ERR_100",
      "routeIds": [
        "sm_create_session_route"
      ]
    },
    {
      "routeIds": [
        "sm_delete_session_route",
        "udr_notify_route"
      ],
      "errorProfileName": "ERR_1200"
    }
  ]
}
```

Table 3-52 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
routeErrorProfileList	Array	M	Specifies the route error profile list.

Table 3-52 (Cont.) Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/Optional(O)/Conditional(C)	Description
routeErrorProfileList.routeIds	Array	M	Specifies the route Id. You can define the server header at route level for any of the following supported route Ids: • sm_create_session_route • sm_delete_session_route • sm_update_session_route • udr_notify_route • chf_terminate_route • chf_notify_route • pa_create_session_route • pa_delete_session_route • pa_update_session_route • pa_events_subscription_route • pa_events_unsubscription_route • am_create_session_route • am_delete_session_route • am_update_session_route • ue_create_session_route • ue_update_session_route • ue_delete_session_route • n1_message_notify • reverse_soapconnector_service • reverse_nrf_notify_service • binding_audit_notify_route • udr_um_notify_route
routeErrorProfileList.errorProfileName	String	M	Specifies the error code profile.

Message Type

The following table describes the URIs available to define and retrieve Message Type:

Table 3-53 Supported REST APIs for Message Type

Description	HTTP Method or Custom Operation	Resource URI
GET Message Type	GET	{apiRoot}/oc-cnpolicy-configuration/v1/diameter/controlledshutdown/error mappings/{messageType}
PUT Message Type	PUT	{apiRoot}/oc-cnpolicy-configuration/v1/diameter/controlledshutdown/error mappings/{messageType}

The sample request body structure for PUT operation is as follows:

```
{
  "messageType": "CER",
  "ansWithResultCode": "CUSTOM_RESULT_CODE",
  "resultCode": "7899",
  "useExperimentalResultCode": true,
  "vendorId": "2"
}
```

Table 3-54 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
messageType	String	M	Type of the request. The supported values are: - Gx_CCR_I - Rx_AAR_I - CER
ansWithResultCode	Enum	M	Specifies the result code, returned in the answer response. The supported values are: - DIAMETER_TOO_BUSY - DIAMETER_UNABLE_TO_COMPLY - DIAMETER_UNABLE_TO_DELIVER - CUSTOM_RESULT_CODE
resultCode	Integer	M	Specify a value for this parameter when you choose CUSTOM_RESULT_CODE value for the ansWithResultCode parameter. Specifies the custom result code, which is returned in the answer response.
useExperimentalResultCode	Boolean	O	Specify a value for this parameter when you choose CUSTOM_RESULT_CODE value for the ansWithResultCode parameter. Specifies the value of result code by user according to their requirement. Result code associates with the vendor ID, when the useExperimentalResultCode is true.
vendorId	Integer	O	Specify a value for this parameter when you choose CUSTOM_RESULT_CODE value for the ansWithResultCode parameter and useExperimentalResultCode is true.

Export/Import

The following table describes the URIs available to define and retrieve Export/Import:

Table 3-55 Supported REST APIs for Export/Import

Description	HTTP Method or Custom Operation	Resource URI
Export	GET	{apiRoot}/oc-cnpolicy-configuration/v1/diameter/controlledshutdown/errormappings/export
Import	POST	{apiRoot}/oc-cnpolicy-configuration/v1/diameter/controlledshutdown/errormappings/import

Sample request body:

```
{
  "topic": "common.public.diamcontrolledshutdown",
  "sourceVersion": " 22.3.0",
  "date": "2022-07-14T10:03:03Z",
  "exportData": [
    {
      "messageType": "Gx_CCR_I",
      "ansWithResultCode": "CUSTOM_RESULT_CODE",
      "useExperimentalResultCode": false,
      "resultCode": "1300"
    },
    {
      "messageType": "Rx_AAR_I",
      "ansWithResultCode": "DIAMETER_TOO_BUSY",
      "useExperimentalResultCode": false
    },
    {
      "messageType": "CER",
      "ansWithResultCode": "CUSTOM_RESULT_CODE",
      "useExperimentalResultCode": true,
      "resultCode": "2109",
      "vendorId": "1"
    }
  ]
}
```

Table 3-56 Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/ Optional(O)/ Conditional(C)	Description
exportData.messageType	String	M	Type of the request

Table 3-56 (Cont.) Request/Response Body Parameters

Field Name	Data Type	Mandatory(M)/Optional(O)/Conditional(C)	Description
exportData.ansWithResultCode	Enum The supported values are: - DIAMETER_TOO_BUSY - DIAMETER_UNABLE_TO_COMPLY - DIAMETER_UNABLE_TO_DELIVER - CUSTOM_RESULT_CODE	M	Specifies the result code, returned in the answer response.
exportData.resultCode	Integer	M	Specify a value for this parameter when you choose CUSTOM_RESULT_CODE value for the ansWithResultCode parameter. Specifies the custom result code, which is returned in the answer response.
exportData.useExperimentalResultCode	Boolean	O	Specify a value for this parameter when you choose CUSTOM_RESULT_CODE value for the ansWithResultCode parameter. Specifies the value of result code by user according to their requirement. Result code associates with the vendor ID, when the useExperimentalResultCode is true.
exportData.vendorId	Integer	O	Specify a value for this parameter when you choose CUSTOM_RESULT_CODE value for the ansWithResultCode parameter and useExperimentalResultCode is true.

3.15 NF Scoring for a Site

The following table describes the URI available to define NF Scoring:

Table 3-57 REST API for NF Scoring

Description	HTTP Method or Custom Operation	Resource API
GET for NF Score	GET	/oc-cnpolicy-configuration/v1/nfscore

Table 3-58 Fields

Field Name	Mandatory (M)/ Optional(O)/ Conditional(C)	Datatype	Description
NF Score	M	Float	The score of a site based on NF-specific factors (metrics, alerts, and so on).
detailedReport	M	NA	Detailed report of NFScore calculation.
scoringFactors	M	NA	Comprises the factors that contributed to the NFScore
criteria	C	NA	Factors involved in NFScore calculation Criteria are present for a specific factor If it is enabled for NF-Scoring.
maxScore	C	Integer	Max score of that factor maxScore is present for a specific factor If it is enabled for NF-Scoring.
calculatedScore	C	Float	calculated score of that factor calculatedScore are present for a specific factor If it is enabled for NF-Scoring.
additionalInfo	O	NA	additional info related to factor's score calculation.
configuredValue	C	Integer	An expected value configured for a factor configuredValue is present for a specific factor If it is enabled for NF-Scoring.
actualValue	C	Float	An actual value for a particular factor after doing factor-specific configuration. actualValue is present for a specific factor If it is enabled for NF-Scoring.
totalSvcs	C	Integer	Total configured services. totalSvcs is present when the factor SVC-Health is enabled

Table 3-58 (Cont.) Fields

Field Name	Mandatory (M)/ Optional(O)/ Conditional(C)	Datatype	Description
upSvcs	C	Integer	Total running services. upSvcs is present when the factor SVC-Health is enabled
totalSites	C	Integer	Total configured sites totalSites is present when the factor replicationHealth is enabled.
availableLinks	C	Integer	Total healthy sites availableLinks is present when the factor replicationHealth is enabled.
critical	C	Integer	Critical alert's contribution to alert's calculated score This attribute is present when ActiveAlerts are enabled as NF-Scoring factor
major	C	Float	Major alert's contribution to alert's calculated score This attribute is present when ActiveAlerts are enabled as NF-Scoring factor
minor	C	Float	Minor alert's contribution to alert's calculated score This attribute is present when ActiveAlerts are enabled as NF-Scoring factor
failedFactors	C	Float	Enabled factors that failed to contribute to NF Score This attribute is present when an application fails to calculate the score for 1 or more factors.
detail	C	NA	Factor's failure reason This attribute is present when there are 1 or more failed factors.

Note: When the Enable flag is true for any criteria, then its related fields will be shown.

Sample Response Body for GET NF Score:

```
{
  "NFScore": 129,
  "detailedReport": {
    "scoringFactors": [
      {
        "criteria": "tps",
        "maxScore": 100,
        "calculatedScore": 75,
        "additionalInfo": {
          "configuredValue": 4000,
          "actualValue": 3000
        }
      },
      {
        "criteria": "serviceHealth",
        "maxScore": 100,
        "calculatedScore": 70,
        "additionalInfo": {
          "totalSvcs": 10,
          "upSvcs": 7
        }
      },
      {
        "criteria": "signallingConnections",
        "maxScore": 100,
        "calculatedScore": 50,
        "additionalInfo": {
          "configuredValue": 50,
          "actualValue": 25
        }
      },
      {
        "criteria": "replicationHealth",
        "maxScore": 100,
        "calculatedScore": 50,
        "additionalInfo": {
          "totalSites": 3,
          "availableLinks": 1
        }
      },
      {
        "criteria": "localityPreference",
        "maxScore": 100, #remove
        "calculatedScore": 100
      },
      {
        "criteria": "activeAlert",
        "score": -30, #rename to "calculatedScore"
        "additionalInfo": {
          "critical": -10,
          "major": -20,
          "minor": 0
        }
      }
    ]
  }
}
```

```

    ]
  },
  "failedFactors": [
    {
      "criteria": "replicationHealth",
      "detail": "failed to calculate replicationHealth score"
    }
  ]
}

```

3.16 Configuration for User-Agent Header Generation at Egress Gateway

Configuring User-Agent Header in Egress Gateway

This section describes the URIs that you can configure for user-agent header generation at Egress Gateway.

The configuration to enable and disable the generation of the user-agent header can be done using REST API exposed by the config-service when sending the following JSON body.

Table 3-59 Supported REST APIs for User-Agent Generation

Description	HTTP Method or Custom Operation	Resource URI
PUT User-Agent Generation	PUT	http://<config-service IP>:<config-service PORT>/pcf/nf-common-component/v1/egw/useragentheader

CURL command for PUT Operation: `curl -X PUT http://10.75.232.35:8000/pcf/nf-common-component/v1/egw/useragentheader -H "Content-Type: application/json" -d`

The sample request body structure for PUT operation is as follows:

```

{
  "enabled": true,
  "nfType": "PCF",
  "nfInstanceId": "fe7d992b-0541-4c7d-ab84-c6d70b1b0555",
  "nfFqdn": "pcf.oracle.org",
  "addFqdnToHeader": true,
  "overwriteHeader": true
}

```

Table 3-60 Request Body Parameters

Field Name	Data Type	Mandatory(M)/Optional(O)/Conditional(C)	Description
egress-gateway.userAgentHeader.enabled	Boolean	M	Specifies whether the feature is enabled or disabled. By default, the value is set to false.
egress-gateway.userAgentHeader.nfType	String	M	This parameter holds the nfType that will be used to generate the user agent header.
egress-gateway.userAgentHeader.nfInstanceId	String	O	This parameter represents the UUID of the CNPCF deployment that will be used to generate the user agent header.
egress-gateway.userAgentHeader.addFqdnToHeader	Boolean	M	This parameter specifies if the user agent will use the FQDN information under the module to append it when generating the user agent header. The default value is set to 'false' meaning that the FQDN information will not be encoded into the user agent header during its generation. By default, the value is set to false.
egress-gateway.userAgentHeader.nfFqdn	String	O	This is an optional parameter and can be present or not, if operators want to include the FQDN string configured under this section then the parameter userAgentHeader.addFqdnToHeader needs to be enabled.
egress-gateway.userAgentHeader.overwriteHeader	Boolean	M	This parameter is used to govern if we want to include the User-Agent header generated at CNPCF Egress Gateway or forward the User-Agent received from service request. By default it will be set to true as CNPCF always generates its own service requests.

A

Result Codes

This section provides detailed information about result codes.

GET HTTP Method

The following table describes the possible result codes for GET method:

Table A-1 Result Codes for GET

Code	Description
200	OK
204	Successful
400	Bad Request
401	Unauthorized
403	Forbidden
404	Not Found
429	Too Many Requests
500	Internal Server Error
503	Service Unavailable

PUT HTTP Method

The following table describes the possible result codes for PUT method:

Table A-2 Result Codes for PUT

Code	Description
200	Updated
201	Created
204	Successfully updated
400	Bad Request
401	Unauthorized
403	Forbidden
404	Not Found
405	Method Not Allowed
406	Not Acceptable
408	Request Timeout
409	Conflict
412	Precondition Failed
500	Internal Server Error
503	Service Unavailable
504	Gateway Timeout

POST HTTP Method

The following table describes the possible result codes for POST method:

Table A-3 Result Codes for POST

Code	Description
200	OK
201	Imported/Created
204	Successfully created
400	Bad Request
401	Unauthorized
403	Forbidden
404	Not Found
405	Method Not Allowed
406	Not Acceptable
408	Request Timeout
409	Conflict
412	Precondition Failed
500	Internal Server Error
503	Service Unavailable
504	Gateway Timeout

DELETE HTTP Method

The following table describes the possible result codes for DELETE method:

Table A-4 Result Codes for DELETE

Code	Description
200	OK
204	Successfully Deleted
400	Bad Request
401	Unauthorized
403	Forbidden
404	Not Found
429	Too Many Requests
500	Internal Server Error
503	Service Unavailable