

# Oracle® Communications Order and Service Management Cartridges for Application Integration Architecture

## Cloud Native Deployment Guide

Release 2.1.3

G48847-01

December 2025

---

## Cloud Native Deployment Guide

Order-to-Activate 2.1.3 cartridges support deploying OSM instances in a cloud native environment. The integration pack generates all the required artifacts to be used by the OSM cloud native toolkit.

You perform the following tasks to use the Order-to-Activate cartridges for OSM cloud native deployments:

- Downloading and Extracting the Pre-Generated OSM Cloud Native Artifacts for the Order-to-Activate Solution. See "[Downloading and Extracting the Pre-Generated OSM Cloud Native Artifacts for the Order-to-Activate Solution](#)".
- Generate the OSM cloud native artifacts for the Order-to-Activate solution. See "[Generating the OSM Cloud Native Artifacts for the Order-to-Activate Solution](#)".
- Extend the OSM container image with the additional Order-to-Activate applications. See "[Extending the OSM Docker Image with Additional Order-to-Activate Applications](#)".
- Configure the specifications. See "[Configuring the Specifications](#)".
- Create the Order-to-Activate credentials and accounts. See "[Creating Order-to-Activate Credentials and Accounts](#)".
- Deploy the Order-to-Activate solution cartridge to the OSM cloud native instance's database. See *OSM Cloud Native Deployment Guide* for instructions about deploying cartridges to the OSM database.
- Bring up the OSM instance.

## Downloading and Extracting the Pre-Generated OSM Cloud Native Artifacts for the Order-to-Activate Solution

The Order-to-Activate integration pack includes a pre-built O2A COM SOM CSO solution with a SimpleTopology configuration, enabling deployment on OSM Cloud Native environments. For all the other combinations of solution topology, see "[Generating the OSM Cloud Native Artifacts for the Order-to-Activate Solution](#)". The pre-generated cloud native artifacts solution is packaged as a zip file titled **OracleComms\_OSM\_O2A\_CN\_Artifacts\_O2A Version.build-no.zip**. Download this file and extract the contents to

**OracleComms\_OSM\_O2A\_CN\_Artifacts\_2.1.3.0.0.build-no.** Once extracted, you will see the following structure:

```
OracleComms_OSM_O2A_CN_Artifacts_2.1.3.0.0.build-no
|
+-- application
|   |
|   + -- create-o2a-base-image.sh
|   |
|   +-- Dockerfile
|   |
|   +-- o2a-wdt-app-archive.zip
|
+-- project
|   |
|   +-- o2a_project.yaml
|   |
|   +-- o2a_users.yaml
|   |
|   +-- o2a_users_embedded_ldap.txt
|   |
|   +-- o2a-wdt-app-archive.30.yaml
|
+-- OracleComms_OSM_O2A_COMSOM_CS0_Solution.par
```

The extracted folder has the following files:

- **create-o2a-base-image.sh**: This is the Linux shell script that uses the application archive and docker file to extend an OSM image for Order-to-Activate.
- **Docker file**: This is the Docker build file which extends the base OSM image to include the **o2a-wdt-app-archive.zip** file.
- **o2a-wdt-app-archive.zip**: This is the application archive file which contains the error handler, COM SOM AIA emulators and SOM CSO emulators.
- **o2a-wdt-app-archive.30.yaml**: This is the yaml fragment file which contains application deployment description for the applications error handler, COM SOM AIA emulators and SOM CSO emulators. Copy this fragment into your project specification file.
- **o2a\_project.yaml**: This is the yaml fragment file which contains all JMS resources and SAF queues. Copy this fragment into your project specification file.
- **o2a\_users.yaml**: This is the yaml fragment file of all cartridge users defined for the solution. Copy this fragment into your project specification file.
- **o2a\_users\_embedded\_ldap.txt**: This user information text file is used by the **manage-cartridge-credentials.sh** script in the OSM cloud native toolkit to create Kubernetes secrets for the specified cartridges. These secrets are then loaded into the WebLogic embedded LDAP when the instance is created.

# Generating the OSM Cloud Native Artifacts for the Order-to-Activate Solution

The Order-to-Activate integration pack generates all the required artifacts to be used by the OSM cloud native toolkit. You use the **config\_ALL\_CloudNative** configuration option in the **SolutionConfig.xml** Order-to-Activate configuration script to generate the artifacts.

Before generating the OSM cloud native artifacts, ensure that you have installed Design Studio and OSM plugins and that a workspace has already been created. For details about installing the Order-to-Activate components, see "Performing an Interactive Installation of the Order-to-Activate Components" in *Order and Service Management Cartridge Guide for Oracle Application Integration Architecture*.

To generate the OSM cloud native artifacts:

1. Create a working folder and download the **OracleComms\_OSM\_O2A\_CartridgesInstaller\_2.1.3.0.0.xxx.zip** Order-to-Activate installer into the working folder.
2. Unzip the Order-to-Activate installer ZIP file within the working folder.
3. From Design Studio, import the *working\_folder/OSM.PIP/OracleComms\_OSM\_O2A\_Install.zip* archive file as an existing project.
4. Import COM, SOM, or COM and SOM together with the solution cartridge into the workspace and upgrade the model. See "Performing an Interactive Installation of the Order-to-Activate Components" in *Order and Service Management Cartridge Guide for Oracle Application Integration Architecture*.
5. Add the **SolutionConfig.xml** file from the solution cartridge that you imported to Ant view and configure it to run as the same JRE as the Eclipse workspace.
6. Run the **config\_All\_CloudNative** Ant target.
7. When prompted, enter **d** for development or **p** for production.
8. Choose the topology and complex topology options as desired. The **config\_All\_CloudNative** target also runs the **config\_Metadata\_And\_ModelVariable** target. Hence, there is no need to run it separately.  
After **config\_All\_CloudNative** is run successfully, the cloud native artifacts are generated. If you chose the CSO option, the artifacts are generated under **OracleComms\_OSM\_O2A\_XXX\_CSO\_Solution/cloud-native**.
9. Save the generated artifacts.
10. Build your solution. If you chose the CSO option, build **OracleComms\_OSM\_O2A\_XXX\_CSO\_Solution**.

If you chose the CSO option, the par file is generated at:  
**OracleComms\_OSM\_O2A\_XXX\_CSO\_Solution/cartridgeBin/OracleComms\_OSM\_O2A\_XXX\_CSO\_Solution.par**.

You use the OSM cloud native toolkit to deploy the par file to the OSM database directly.

For each solution, the generated cloud native artifacts include the following:

- **o2a\_project.yaml**: The yaml fragment containing all JMS resources and SAF queues. Copy this fragment into your project specification file.
- **o2a\_project-instance.yaml**: The yaml fragment containing all SAF connection configuration. Copy this fragment into your instance specification file.
- **o2a\_users.yaml**: The yaml fragment of all cartridge users defined for the solution. Copy this fragment into your project specification file.
- **o2a\_users\_embedded\_ldap.txt**: User information text file to be used by the **manage-cartridge-credentials.sh** OSM cloud native toolkit script to create Kubernetes secrets for all cartridges. These secrets are added to WebLogic embedded LDAP when the instance is created.
- **o2a-wdt-app-archive.zip**: The application archive that contains the error handler for the solution. If the Order-to-Activate config option `development` or `CSO` is selected, then emulators for AIA and the CSO solution are included as well.
- Dockerfile: The Docker build file to extend a base OSM image to include the **o2a-wdt-app-archive.zip** file.
- **create-o2a-base-image.sh**: The Linux shell script that uses the application archive and dockerfile to extend an OSM image for Order-to-Activate use.

## Extending the OSM Docker Image with Additional Order-to-Activate Applications

To extend the base OSM Docker image:

1. Change the working directory to the directory where the cloud native artifacts are generated.
  - If you choose pre-generated cloud native artifacts, change the working directory to **OracleComms\_OSM\_O2A\_CN\_Artifacts\_2.1.3.0.0.build-no**.
  - If you choose CSO solution, change the working directory to **OracleComms\_OSM\_O2A\_XXX\_CSO\_Solution/cloud-native/application**.
2. Build the new Docker image containing the archive by running the **create-o2a-base-image.sh** script.

The following sample shows the usage:

Usage:

```
create-o2a-base-image.sh <parameters>
  -t o2a-image-tag-name : mandatory, the image tag name to be
  created.
  -i osm-base-image-name : mandatory, the base osm image to be
  extended.
  -a o2a-app-archive : mandatory, the application archive that
  contains O2A app artifacts.
```

For example....

```
$ ./create-o2a-base-image.sh \  
-t o2a-domain:7.4.1 -i osm-base:7.4.1 -a o2a-wdt-app-archive.zip
```

## Configuring the Specifications

In addition to the regular setup required for an instance defined by the OSM cloud native toolkit, you must perform the following additional steps:

1. If you chose pre-generated cloud native artifacts, merge the contents of the **OracleComms\_OSM\_O2A\_CN\_Artifacts\_2.1.3.0.0.build-no/project/o2a\_project.yaml** file into your **project\_name.yaml** file.
2. For both production and development environments, merge the contents of your Order-to-Activate solution project yaml file into your **project\_name.yaml** file. If you chose CSO, merge the contents of the **OracleComms\_OSM\_O2A\_XXX\_CSO\_Solution/cloud-native/project/o2a\_project.yaml** file into your **project\_name.yaml** file.
3. For production environments, if you chose product mode when running **config\_ALL\_CloudNative**, merge the contents of your Order-to-Activate solution project file OR the **OracleComms\_OSM\_O2A\_XXX\_CSO\_Solution/cloud-native/project/o2a\_project-instance.yaml** file into your **project\_name-instance\_name.yaml** file.
4. Edit the specification files as follows:

```
$ vi spec_path/project_name.yaml # update image and add credential  
store as shown.
```

```
image: O2A_image_name_and_tag
```

```
#External Credentials Store, O2A cartridge user secret  
externalCredStore:
```

```
  # Uncomment and specify Kubernetes secret suffix for external/peer  
  applications. The prefix project_name-instance_name will be derived  
  # The suffix must be in the "osmcn-cred-mapName" format
```

```
  secrets:
```

```
    mapNames:
```

```
      - osm
```

```
      - uim
```

If you chose product mode when running **config\_ALL\_CloudNative**, modify your **project\_name-instance\_name.yaml** to add `customSecrets` and `safConnectionConfig` sections to set up the secrets and SAF end point URL for the SAF connection.

```
$ vi spec_path/project_name-instance_name.yaml  
# add the Order-to-Activate credentials store as shown
```

```
#Customer Credentials Store, a secret used in SAF remote connect to  
AIA, UIM and TOM
```

```
# Replace all ${DOMAIN_UID} with project_name-instance_name
```

```

instance:
  customSecrets:
    secretNames:
      - "${DOMAIN_UID}-saf-credentials-aia"
      - "${DOMAIN_UID}-saf-credentials-uim"
      - "${DOMAIN_UID}-saf-credentials-tom"

$ vi spec_path/project_name-instance_name.yaml
# provide the AIA t3Url under O2A_SAFImportedDestinations,
# UIM t3Url under O2A_UIM_SAFImportedDestinations and
# TOM t3Url under O2A_TOM_SAFImportedDestinations.
# Replace all ${DOMAIN_UID} with project_name-instance_name

# SAF connection configuration for O2A
safConnectionConfig:
  - name: O2A_SAFImportedDestinations
    t3Url: t3://t3_host:t3_port
    secretName: ${DOMAIN_UID}-saf-credentials-aia
  - name: O2A_UIM_SAFImportedDestinations
    t3Url: t3://t3_host:t3_port
    secretName: ${DOMAIN_UID}-saf-credentials-uim
  - name: O2A_TOM_SAFImportedDestinations
    t3Url: t3://t3_host:t3_port
    secretName: ${DOMAIN_UID}-saf-credentials-tom

```

## Creating Order-to-Activate Credentials and Accounts

You create the following secrets to carry credential and account information for Order-to-Activate:

- Secrets used by SAF connection to AIA, UIM, and OSM TOM
- Secrets used by automation in OSM and Order-to-Activate to communicate to OSM and other systems

### Creating Secrets for SAF Connection to AIA, UIM and OSM TOM

#### Note

Perform this task for production environments only. When configuring the `config_ALL_CloudNative` option, if you chose `development` or if you are using pre-generated artifacts, the solution uses emulators and you do not need to create secrets for SAF connection.

The credentials used to obtain connection to other systems via SAF are stored as Kubernetes secrets.

To create the secrets for SAF remote context to AIA, UIM, and TOM, run the following command:

```
kubectl create secret generic project_name-instance_name-saf-credentials-aia -n project_name --from-literal=username='aia_weblogic_user_name' --from-literal=password='aia_weblogic_user_password'
```

```
kubectl create secret generic project_name-instance_name-saf-credentials-uim -n project_name --from-literal=username='uim_weblogic_user_name' --from-literal=password='uim_weblogic_user_password'
```

```
kubectl create secret generic project_name-instance_name-saf-credentials-tom -n project_name --from-literal=username='tom_weblogic_user_name' --from-literal=password='tom_weblogic_user_password'
```

### Creating Secrets for Order-to-Automate Automation Users

The Order-to-Activate user credentials are persisted to a cartridge credential secret in Kubernetes. This uses the `osm` map name and is available via the OSM automation framework in the cartridge automation plugin code. In addition, the automation users must have accounts in embedded LDAP.

To create the secret and embedded user accounts:

1. Populate your `project.yaml` file with the list of `cartridgeUsers` from the `o2a_users.yaml` file.
  - For pre-generated cloud native artifacts, the list of users is located in the `OracleComms_OSM_O2A_CN_Artifacts_2.1.3.0.0.build-no/project/o2a_users.yaml`.
  - If you choose the CSO Solution, the list of cartridge users is located in the `OracleComms_OSM_O2A_XXX_CSO_Solution/cloud-native/project/o2a_users.yaml` file.
2. Copy the `o2a_users_embedded_ldap.txt` Order-to-Activate user file to `$OSM_CNTK/samples/credentials`.
  - For pre-generated cloud native artifacts, the user file is located in the `OracleComms_OSM_O2A_CN_Artifacts_2.1.3.0.0.build-no/project` directory.
  - If you choose the CSO Solution, the user file is located in the `OracleComms_OSM_O2A_XXX_CSO_Solution/cloud-native/project` directory.
3. Run the `$OSM_CNTK/samples/credentials/manage-cartridge-credentials.sh` script to create the Kubernetes secret:

```
$ chmod 777 $OSM_CNTK/samples/credentials/manage-cartridge-credentials.sh
$ $OSM_CNTK/samples/credentials/manage-cartridge-credentials.sh -p
```

```
project_name -i instance_name -c create -f $OSM_CNTK/samples/  
credentials/o2a_users_embedded_ldap.txt
```

## Documentation Accessibility

For information about Oracle's commitment to accessibility, visit the Oracle Accessibility Program website at <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=docacc>.

## Access to Oracle Support

Oracle customer access to and use of Oracle support services will be pursuant to the terms and conditions specified in their Oracle order for the applicable services.

---

### Oracle Communications Order and Service Management Cartridges for Application Integration Architecture Cloud Native Deployment Guide, Release 2.1.3

G48847-01

Copyright © 2021, 2025, Oracle and/or its affiliates.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this is software, software documentation, data (as defined in the Federal Acquisition Regulation), or related documentation that is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, then the following notice is applicable:

U.S. GOVERNMENT END USERS: Oracle programs (including any operating system, integrated software, any programs embedded, installed, or activated on delivered hardware, and modifications of such programs) and Oracle computer documentation or other Oracle data delivered to or accessed by U.S. Government end users are "commercial computer software," "commercial computer software documentation," or "limited rights data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, reproduction, duplication, release, display, disclosure, modification, preparation of derivative works, and/or adaptation of i) Oracle programs (including any operating system, integrated software, any programs embedded, installed, or activated on delivered hardware, and modifications of such programs), ii) Oracle computer documentation and/or iii) other Oracle data, is subject to the rights and limitations specified in the license contained in the applicable contract. The terms governing the U.S. Government's use of Oracle cloud services are defined by the applicable contract for such services. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

Oracle®, Java, MySQL, and NetSuite are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Inside are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. AMD, Epyc, and the AMD logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark of The Open Group.

This software or hardware and documentation may provide access to or information about content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services unless otherwise set forth in an applicable agreement between you and Oracle. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services, except as set forth in an applicable agreement between you and Oracle.