

Oracle Utilities Testing Accelerator
Reference Guide for Oracle Utilities Customer
Care and Billing Cloud Service

Release 24B

G12268-01

August 2024

Oracle Utilities Testing Accelerator Release 24B Reference Guide for Oracle Utilities Customer Care and Billing Cloud Service

G12268-01

Copyright © 2000, 2024 Oracle and/or its affiliates.

Contents

Preface	i-i
Audience	i-ii
Related Documents	i-ii
Updates to the Documentation	i-ii
Documentation Accessibility	i-ii
Conventions.....	i-iii
Abbreviations	i-iii
 Chapter 1	
Component Reference	1-1
Overview	1-2
Components	1-2
 Appendix A	
Inbound Web Services	A-1
 Appendix B	
Identifying Fields For a Web Service Request	B-1
Debug Mode in the Application.....	B-2
IE Development Tool Bar	B-4
SOAP UI.....	B-8

Preface

Welcome to the Oracle Utilities Testing Accelerator Reference Guide for Oracle Utilities Customer Care and Billing Cloud Service for release 24B.

This guide describes the Oracle Utilities Customer Care and Billing Cloud Service 24B components and function libraries used to create those components in Oracle Utilities Testing Accelerator. These components are used to build test flows in Oracle Utilities Testing Accelerator Workbench.

The preface focuses on the following:

- [Audience](#)
- [Related Documents](#)
- [Updates to the Documentation](#)
- [Documentation Accessibility](#)
- [Conventions](#)
- [Abbreviations](#)

Audience

This guide is intended for QA/Test Engineers and Automation Developers to understand the various components and libraries available for them to automate the business test flows for Oracle Utilities Customer Care and Billing Cloud Service using Oracle Utilities Testing Accelerator for Oracle Utilities Customer Care and Billing Cloud Service.

Related Documents

For more information, refer to the following Oracle resources.

- *Oracle Utilities Testing Accelerator User's Guide for Cloud*
- *Oracle Utilities Testing Accelerator Reference Guide for Core*
- *Oracle Utilities Testing Accelerator Reference Guide for Oracle Utilities Customer Cloud Service*
- *Oracle Utilities Testing Accelerator Reference Guide for Oracle Utilities Billing Cloud Service*
- *Oracle Utilities Testing Accelerator Reference Guide for Oracle Utilities Rate Cloud Service*
- *Oracle Utilities Testing Accelerator Reference Guide for Oracle Utilities Customer Care and Billing Cloud Service*
- *Oracle Utilities Testing Accelerator Reference Guide for Oracle Utilities Meter Solution Cloud Service*
- *Oracle Utilities Testing Accelerator Reference Guide for Oracle Utilities Work and Asset Cloud Service*
- *Oracle Utilities Testing Accelerator Reference Guide for Oracle Utilities Digital Asset Cloud Service*

Also, see the following documentation libraries at [Oracle Help Center](#):

- Oracle Utilities Customer Care and Billing

Updates to the Documentation

Documentation updates are posted on [Oracle Help Center](#) as they become available.

Documentation Accessibility

For information about Oracle's commitment to accessibility, visit the [Oracle's Accessibility Program](#) website.

Access to Oracle Support

Oracle customers have access to electronic support through [My Oracle Support](#). If you are hearing impaired, visit the [Oracle Accessibility Learning and Support](#) website for more information.

Conventions

The following text conventions are used in this document:

Convention	Meaning
boldface	Boldface type indicates graphical user interface elements associated with an action, or terms defined in text or the glossary.
<i>italic</i>	Italic type indicates book titles, emphasis, or placeholder variables for which you supply particular values.
monospace	Monospace type indicates commands within a paragraph, URLs, code in examples, text that appears on the screen, or text that you enter.

Abbreviations

The following terms are used in this document:

Term	Expanded Form
CCBCS/OUCCBCS	Oracle Utilities Customer Care and Billing Cloud Service
UTA/OUTA	Oracle Utilities Testing Accelerator

Chapter 1

Component Reference

This chapter lists the Oracle Utilities Customer Care and Billing Cloud Service starter components available to create flows in Oracle Utilities Testing Accelerator Workbench for testing the Oracle Utilities Customer Care and Billing Cloud Service application.

It includes the following sections:

- [Overview](#)
- [Components](#)

Overview

Oracle Utilities Testing Accelerator for Oracle Utilities Customer Care and Billing Cloud Service is a test starter pack built on top of Oracle Utilities Testing Accelerator that generates test automation scripts using Oracle Utilities Testing Accelerator Workbench.

Oracle Utilities Testing Accelerator for Oracle Utilities Customer Care and Billing Cloud Service contains out-of-the-box product-specific components used to build new test flows in Oracle Utilities Testing Accelerator Workbench to test the Oracle Utilities Customer Care and Billing Cloud Service applications. These out-of-the-box components correspond to specific business entities, such as business objects, service scripts, or business services used for interfacing with the application. Users can use these components as available or can extend them. Users can also create new components to be used to create flows. This starter pack also contains a set of function libraries that can be used for creating custom components.

Consider this pack to be a starter kit which can be expanded and built upon. A few sample flows are included as an example.

For more information about creating components and flows, refer to the *Oracle Utilities Testing Accelerator User's Guide* available on the [Oracle Utilities Testing Accelerator for Cloud Services](#) page on [Oracle Help Center](#).

Components

This section lists the starter components available for Oracle Utilities Customer Care and Billing Cloud Service.

Pre-requisites: The Inbound Web Service using the respective business object should be available in the application.

Additional Notes: Failure while creating, reading, or updating the component is logged in the test execution report, thus facilitating debugging/analysis of the problem.

The components are categorized under the following functional areas:

- [Admin](#)
- [Credit and Collection](#)
- [Customer Information](#)
- [Data Synchronization](#)
- [DSS](#)
- [DSS-SST](#)
- [Field Order](#)
- [Financial](#)
- [General](#)
- [Interval Billing](#)
- [Letter Template](#)
- [Meter](#)

- [Meter Read](#)
- [Rate Schedule](#)
- [Sales and Marketing](#)
- [Service Order Management](#)
- [Usage](#)
- [Umbrella Agreement Management](#)
- [Master Configuration](#)
- [Self-Service](#)
- [Service Task Type](#)
- [Contract and Products](#)
- [CX - API \(REST\)](#)

Admin

Component	Description
C1-AdjustmentTypeAdd	Used to add an Adjustment Type record. This component invokes the ATC1AdjustmentType Inbound Web Service using the C1-AdjTypePhysicalBO Business Object.
C1-AdjustmentTypeRead	Used to read an Adjustment Type record. This component invokes the ATC1AdjustmentType Inbound Web Service using the C1-AdjTypePhysicalBO Business Object.
C1-AdjustmentTypeUpdate	Used to update an Adjustment Type record. This component invokes the ATC1AdjustmentType Inbound Web Service using the C1-AdjTypePhysicalBO Business Object.
C1-AdjustmentTypeDelete	Used to delete an Adjustment Type record. This component invokes the ATC1AdjustmentType Inbound Web Service using the C1-AdjTypePhysicalBO Business Object.
C1-AutoPaySourceAdd	Used to add an Auto Pay Source record. This component invokes the ATC1AutoPaySource Inbound Web Service using the C1-AutoPaySourcePhysicalBO Business Object.

Component	Description
C1-AutoPaySourceDelete	Used to delete an Auto Pay Source record. This component invokes the ATC1AutoPaySource Inbound Web Service using the C1-AutoPaySourcePhysicalBO Business Object.
C1-AutoPaySourceRead	Used to read an Auto Pay Source record. This component invokes the ATC1AutoPaySource Inbound Web Service using the C1-AutoPaySourcePhysicalBO Business Object.
C1-AutoPaySourceUpdate	Used to Update an Auto Pay Source record. This component invokes the ATC1AutoPaySource Inbound Web Service using the C1-AutoPaySourcePhysicalBO Business Object.
C1-AutoPayRouteTypeAdd	Used to add an Auto Pay Route Type record. This component invokes the ATC1AutoPayRouteType Inbound Web Service using the C1-AutoPayRouteTypePhysicalBO Business Object.
C1-AutoPayRouteRead	Used to read an Auto Pay Route Type record. This component invokes the ATC1AutoPayRouteType Inbound Web Service using the C1-AutoPayRouteTypePhysicalBO Business Object.
C1-AutoPayRouteUpdate	Used to update an Auto Pay Route Type record. This component invokes the ATC1AutoPayRouteType Inbound Web Service using the C1-AutoPayRouteTypePhysicalBO Business Object.
C1-AutoPayRouteDelete	Used to delete an Auto Pay Route Type record. This component invokes the ATC1AutoPayRouteType Inbound Web Service using the C1-AutoPayRouteTypePhysicalBO Business Object.
C1-CaseTypeAdd	Used to add a Case Type record. This component invokes the ATC1CaseType Inbound Web Service using the C1-CaseTypePhysicalBO Business Object.
C1-CaseTypeRead	Used to read a Case Type record. This component invokes the ATC1CaseType Inbound Web Service using the C1-CaseTypePhysicalBO Business Object.

Component	Description
C1-CaseTypeUpdate	Used to update a Case Type record. This component invokes the ATC1CaseType Inbound Web Service using the C1-CaseTypePhysicalBO Business Object.
C1-CaseTypeDelete	Used to delete a Case Type record. This component invokes the ATC1CaseType Inbound Web Service using the C1-CaseTypePhysicalBO Business Object.
C1-AdjustmentTypeProfileAdd	Used to add an Adjustment Type Profile record. This component invokes the ATC1AdjustmentTypeProfile Inbound Web Service using the C1-AdjTypeProfPhysicalBO Business Object.
C1-AdjustmentTypeProfileDelete	Used to delete an Adjustment Type Profile record. This component invokes the ATC1AdjustmentTypeProfile Inbound Web Service using the C1-AdjTypeProfPhysicalBO Business Object.
C1-AdjustmentTypeProfileRead	Used to read an Adjustment Type Profile record. This component invokes the ATC1AdjustmentTypeProfile Inbound Web Service using the C1-AdjTypeProfPhysicalBO Business Object.
C1-AdjustmentTypeProfileUpdate	Used to update an Adjustment Type Profile record. This component invokes the ATC1AdjustmentTypeProfile Inbound Web Service using the C1-AdjTypeProfPhysicalBO Business Object.
C1-BillRouteTypeAdd	Used to add a Bill Route Type record. This component invokes the ATC1BillRouteType Inbound Web Service using the C1-BillRouteTypePhysicalBO Business Object.
C1-BillRouteTypeDelete	Used to delete a Bill Route Type record. This component invokes the ATC1BillRouteType Inbound Web Service using the C1-BillRouteTypePhysicalBO Business Object.
C1-BillRouteTypeRead	Used to read a Bill Route Type record. This component invokes the ATC1BillRouteType Inbound Web Service using the C1-BillRouteTypePhysicalBO Business Object.

Component	Description
C1-BillRouteTypeUpdate	Used to update a Bill Route Type record. This component invokes the ATC1BillRouteType Inbound Web Service using the C1-BillRouteTypePhysicalBO Business Object.
C1-CharacteristicTypeAdd	Used to add a Characteristic Type record. This component invokes the ATC1CharacteristicType Inbound Web Service using the F1-CharTypePhysicalBO Business Object.
C1-CharacteristicTypeDelete	Used to delete a Characteristic Type record. This component invokes the ATC1CharacteristicType Inbound Web Service using the F1-CharTypePhysicalBO Business Object.
C1-CharacteristicTypeRead	Used to read a Characteristic Type record. This component invokes the ATC1CharacteristicType Inbound Web Service using the F1-CharTypePhysicalBO Business Object.
C1-CharacteristicTypeUpdate	Used to update a Characteristic Type record. This component invokes the ATC1CharacteristicType Inbound Web Service using the F1-CharTypePhysicalBO Business Object.
C1-CollectionClassControlAdd	Used to add a Collection Class Control record. This component invokes the ATC1CollectionClassControl Inbound Web Service using the C1-CollClassControlPhysicalBO Business Object.
C1-CollectionClassControlDelete	Used to delete a Collection Class Control record. This component invokes the ATC1CollectionClassControl Inbound Web Service using the C1-CollClassControlPhysicalBO Business Object.
C1-CollectionClassControlRead	Used to read a Collection Class Control record. This component invokes the ATC1CollectionClassControl Inbound Web Service using the C1-CollClassControlPhysicalBO Business Object.
C1-CollectionClassControlUpdate	Used to update a Collection Class Control record. This component invokes the ATC1CollectionClassControl Inbound Web Service using the C1-CollClassControlPhysicalBO Business Object.

Component	Description
C1-CSRTQuestionAdd	Used to add a CSR Type Question record. This component invokes the ATC1CSRTQuestion Inbound Web Service using the C1-CSRTQuestion Business Object.
C1-CSRTQuestionDelete	Used to delete a CSR Type Question record. This component invokes the ATC1CSRTQuestion Inbound Web Service using the C1-CSRTQuestion Business Object.
C1-CSRTQuestionRead	Used to read a CSR Type Question record. This component invokes the ATC1CSRTQuestion Inbound Web Service using the C1-CSRTQuestion Business Object.
C1-CSRTQuestionUpdate	Used to update a CSR Type Question record. This component invokes the ATC1CSRTQuestion Inbound Web Service using the C1-CSRTQuestion Business Object.
C1-CustSvcRequestResponseAdd	Used to add a Cust Svc Request Response record. This component invokes the ATC1CustSvcRequestResponse Inbound Web Service using the C1-CustSvcRequestResponse Business Object.
C1-CustSvcRequestResponseDelete	Used to delete a Cust Svc Request Response record. This component invokes the ATC1CustSvcRequestResponse Inbound Web Service using the C1-CustSvcRequestResponse Business Object.
C1-CustSvcRequestResponseRead	Used to read a Cust Svc Request Response record. This component invokes the ATC1CustSvcRequestResponse Inbound Web Service using the C1-CustSvcRequestResponse Business Object.
C1-CustSvcRequestResponseUpdate	Used to update a Cust Svc Request Response record. This component invokes the ATC1CustSvcRequestResponse Inbound Web Service using the C1-CustSvcRequestResponse Business Object.

Component	Description
C1-DistributionCodeAdd	Used to add a Distribution Code record. This component invokes the ATC1DistributionCode Inbound Web Service using the C1-DistributionCodePhysicalBO Business Object.
C1-DistributionCodeDelete	Used to delete a Distribution Code record. This component invokes the ATC1DistributionCode Inbound Web Service using the C1-DistributionCodePhysicalBO Business Object.
C1-DistributionCodeRead	Used to read a Distribution Code record. This component invokes the ATC1DistributionCode Inbound Web Service using the C1-DistributionCodePhysicalBO Business Object.
C1-DistributionCodeUpdate	Used to update a Distribution Code record. This component invokes the ATC1DistributionCode Inbound Web Service using the C1-DistributionCodePhysicalBO Business Object.
C1-CISDivisionAdd	Used to add a CIS Division record. This component invokes the ATC1CISDivision Inbound Web Service using the C1-CISDivisionPhysicalBO Business Object.
C1-CISDivisionRead	Used to read a CIS Division record. This component invokes the ATC1CISDivision Inbound Web Service using the C1-CISDivisionPhysicalBO Business Object.
C1-CISDivisionUpdate	Used to update a CIS Division record. This component invokes the ATC1CISDivision Inbound Web Service using the C1-CISDivisionPhysicalBO Business Object.
C1-CISDivisionDelete	Used to delete a CIS Division record. This component invokes the ATC1CISDivision Inbound Web Service using the C1-CISDivisionPhysicalBO Business Object.

Component	Description
C1-CustContactTypeAdd	Used to add a Customer Contact Type record. This component invokes the ATC1CustContactType Inbound Web Service using the C1-CustContactTypePhysicalBO Business Object.
C1-CustContactTypeRead	Used to read a Customer Contact Type record. This component invokes the ATC1CustContactType Inbound Web Service using the C1-CustContactTypePhysicalBO Business Object.
C1-CustContactTypeUpdate	Used to update a Customer Contact Type record. This component invokes the ATC1CustContactType Inbound Web Service using the C1-CustContactTypePhysicalBO Business Object.
C1-CustContactTypeDelete	Used to delete a Customer Contact Type record. This component invokes the ATC1CustContactType Inbound Web Service using the C1-CustContactTypePhysicalBO Business Object.
C1-DispatchGroupAdd	Used to add a Dispatch Group record. This component invokes the ATC1DispatchGroup Inbound Web Service using the C1-DispatchGroupPhysicalBO Business Object.
C1-DispatchGroupRead	Used to read a Dispatch Group record. This component invokes the ATC1DispatchGroup Inbound Web Service using the C1-DispatchGroupPhysicalBO Business Object.
C1-DispatchGroupUpdate	Used to update a Dispatch Group record. This component invokes the ATC1DispatchGroup Inbound Web Service using the C1-DispatchGroupPhysicalBO Business Object.
C1-DispatchGroupDelete	Used to delete a Dispatch Group record. This component invokes the ATC1DispatchGroup Inbound Web Service using the C1-DispatchGroupPhysicalBO Business Object.
C1-GeographicTypeAdd	Used to add a Geographic Type record. This component invokes the ATC1GeographicType Inbound Web Service using the F1-GeographicTypePhysicalBO Business Object.

Component	Description
C1-GeographicTypeDelete	Used to delete a Geographic Type record. This component invokes the ATC1GeographicType Inbound Web Service using the F1-GeographicTypePhysicalBO Business Object.
C1-GeographicTypeRead	Used to read a Geographic Type record. This component invokes the ATC1GeographicType Inbound Web Service using the F1-GeographicTypePhysicalBO Business Object.
C1-GeographicTypeUpdate	Used to update a Geographic Type record. This component invokes the ATC1GeographicType Inbound Web Service using the F1-GeographicTypePhysicalBO Business Object.
C1-IdentifierTypeAdd	Used to add an Identifier Type record. This component invokes the ATC1IdentifierType Inbound Web Service using the C1-IdentifierTypePhysicalBO Business Object.
C1-IdentifierTypeRead	Used to read an Identifier Type record. This component invokes the ATC1IdentifierType Inbound Web Service using the C1-IdentifierTypePhysicalBO Business Object.
C1-IdentifierTypeUpdate	Used to update an Identifier Type record. This component invokes the ATC1IdentifierType Inbound Web Service using the C1-IdentifierTypePhysicalBO Business Object.
C1-IdentifierTypeDelete	Used to delete an Identifier Type record. This component invokes the ATC1IdentifierType Inbound Web Service using the C1-IdentifierTypePhysicalBO Business Object.
C1-InsightGroupAdd	Used to add an Insight Group record. This component invokes the ATC1InsightGroup Inbound Web Service using the F1-InsightGroupPhysicalBO Business Object.
C1-InsightGroupDelete	Used to delete an Insight Group record. This component invokes the ATC1InsightGroup Inbound Web Service using the F1-InsightGroupPhysicalBO Business Object.

Component	Description
C1-InsightGroupRead	Used to read an Insight Group record. This component invokes the ATC1InsightGroup Inbound Web Service using the F1-InsightGroupPhysicalBO Business Object.
C1-InsightGroupUpdate	Used to update an Insight Group record. This component invokes the ATC1InsightGroup Inbound Web Service using the F1-InsightGroupPhysicalBO Business Object.
C1-ItemTypeAdd	Used to add an Item Type record. This component invokes the ATC1ItemType Inbound Web Service using the C1-ItemTypePhysicalBO Business Object.
C1-ItemTypeRead	Used to read an Item Type record. This component invokes the ATC1ItemType Inbound Web Service using the C1-ItemTypePhysicalBO Business Object.
C1-ItemTypeUpdate	Used to update an Item Type record. This component invokes the ATC1ItemType Inbound Web Service using the C1-ItemTypePhysicalBO Business Object.
C1-ItemTypeDelete	Used to delete an Item Type record. This component invokes the ATC1ItemType Inbound Web Service using the C1-ItemTypePhysicalBO Business Object.
C1-MktSATypeSARelationshipTypeAdd	Used to add a Market SA Type SA Relationship Type. This component invokes the ATC1MktSATypeSARelationshipType Inbound Web Service the using C1-MktSATypeSARelationshipType Business Object.
C1-MktSATypeSARelationshipTypeDelete	Used to delete a Market SA Type SA Relationship Type. This component invokes the ATC1MktSATypeSARelationshipType Inbound Web Service the using C1-MktSATypeSARelationshipType Business Object.

Component	Description
C1-MktSATypeSARelationshipTypeRead	Used to read a Market SA Type SA Relationship Type. This component invokes the ATC1MktSATypeSARelationshipType Inbound Web Service the using C1-MktSATypeSARelationshipType Business Object.
C1-MktSATypeSARelationshipTypeUpdate	Used to update a Market SA Type SA Relationship Type. This component invokes the ATC1MktSATypeSARelationshipType Inbound Web Service the using C1-MktSATypeSARelationshipType Business Object.
C1-NotificationTypeAdd	Used to add a Notification Type. This component invokes the ATC1NotificationType Inbound Web Service using the C1-NotificationType Business Object.
C1-NotificationTypeRead	Used to read a Notification Type. This component invokes the ATC1NotificationType Inbound Web Service using the C1-NotificationType Business Object.
C1-NotificationTypeDelete	Used to delete a Notification Type. This component invokes the ATC1NotificationType Inbound Web Service using the C1-NotificationType Business Object.
C1-NotificationTypeUpdate	Used to update a Notification Type. This component invokes the ATC1NotificationType Inbound Web Service using the C1-NotificationType Business Object.
C1-NotifTypeTmplIndividualPushAdd	Used to add a Template-Based Individual Push Notification Type. This component invokes the ATC1NotifTypeTmplIndividualPush Inbound Web Service using the C1-NotifTypeTmplIndividualPush Business Object.
C1-NotifTypeTmplIndividualPushDelete	Used to delete a Template-Based Individual Push Notification Type. This component invokes the ATC1NotifTypeTmplIndividualPush Inbound Web Service using the C1-NotifTypeTmplIndividualPush Business Object.

Component	Description
C1-NotifTypeTmplIndividualPushRead	Used to read a Template-Based Individual Push Notification Type. This component invokes the ATC1NotifTypeTmplIndividualPush Inbound Web Service using the C1-NotifTypeTmplIndividualPush Business Object.
C1-NotifTypeTmplIndividualPushUpdate	Used to update a Template-Based Individual Push Notification Type. This component invokes the ATC1NotifTypeTmplIndividualPush Inbound Web Service using the C1-NotifTypeTmplIndividualPush Business Object.
C1-NotifTypeTmplParentPushAdd	Used to add a Template-Based Parent Push Notification Type. This component invokes the ATC1NotifTypeTmplParentPush Inbound Web Service using the C1-NotifTypeTmplParentPush Business Object.
C1-NotifTypeTmplParentPushDelete	Used to delete a Template-Based Parent Push Notification Type. This component invokes the ATC1NotifTypeTmplParentPush Inbound Web Service using the C1-NotifTypeTmplParentPush Business Object.
C1-NotifTypeTmplParentPushRead	Used to Read a Template-Based Parent Push Notification Type. This component invokes the ATC1NotifTypeTmplParentPush Inbound Web Service using the C1-NotifTypeTmplParentPush Business Object.
C1-NotifTypeTmplParentPushUpdate	Used to update a Template-Based Parent Push Notification Type. This component invokes the ATC1NotifTypeTmplParentPush Inbound Web Service using the C1-NotifTypeTmplParentPush Business Object.
C1-NotifTypeTmplSubscriptionAdd	Used to add a Template-Based Subscription Notification Type. This component invokes the ATC1NotifTypeTmplSubscription Inbound Web Service using the C1-NotifTypeTmplSubscription Business Object.

Component	Description
C1-NotifTypeTmplSubscriptionDelete	Used to delete a Template-Based Subscription Notification Type. This component invokes the ATC1NotifTypeTmplSubscription Inbound Web Service using the C1-NotifTypeTmplSubscription Business Object.
C1-NotifTypeTmplSubscriptionRead	Used to read a Template-Based Subscription Notification Type. This component invokes the ATC1NotifTypeTmplSubscription Inbound Web Service using the C1-NotifTypeTmplSubscription Business Object.
C1-NotifTypeTmplSubscriptionUpdate	Used to update a Template-Based Subscription Notification Type. This component invokes the ATC1NotifTypeTmplSubscription Inbound Web Service using the C1-NotifTypeTmplSubscription Business Object.
C1-NotificationEventTypeAdd	Used to read a Notification Event Type record. This component invokes the ATC1NotificationEventType Inbound Web Service using the C1-NotificationEventType Business Object.
C1-NotificationEventTypeRead	Used to read a Notification Event Type record. This component invokes the ATC1NotificationEventType Inbound Web Service using the C1-NotificationEventType Business Object.
C1-NotificationEventTypeUpdate	Used to update a Notification Event Type record. This component invokes the ATC1NotificationEventType Inbound Web Service using the C1-NotificationEventType Business Object.
C1-NotificationEventTypeDelete	Used to delete a Notification Event Type record. This component invokes the ATC1NotificationEventType Inbound Web Service using the C1-NotificationEventType Business Object.

Component	Description
C1-MarketAdd	Used to add a Market record. This component invokes the ATC1Market Inbound Web Service using the C1-MarketPhysicalBO Business Object.
C1-MarketDelete	Used to delete a Market record. This component invokes the ATC1Market Inbound Web Service using the C1-MarketPhysicalBO Business Object.
C1-MarketRead	Used to read a Market record. This component invokes the ATC1Market Inbound Web Service using the C1-MarketPhysicalBO Business Object.
C1-MarketUpdate	Used to update a Market record. This component invokes the ATC1Market Inbound Web Service using the C1-MarketPhysicalBO Business Object.
C1-MktProvConfigOptAdd	Used to add a Mkt Prov Config Opt record. This component invokes the ATC1MktProvConfigOpt Inbound Web Service using the C1-MktProvConfigOpt Business Object.
C1-MktProvConfigOptDelete	Used to delete a Mkt Prov Config Opt record. This component invokes the ATC1MktProvConfigOpt Inbound Web Service using the C1-MktProvConfigOpt Business Object.
C1-MktProvConfigOptRead	Used to read a Mkt Prov Config Opt record. This component invokes the ATC1MktProvConfigOpt Inbound Web Service using the C1-MktProvConfigOpt Business Object.
C1-MktProvConfigOptUpdate	Used to update a Mkt Prov Config Opt record. This component invokes the ATC1MktProvConfigOpt Inbound Web Service using the C1-MktProvConfigOpt Business Object.
C1-PaymentTypeLookupAdd	Used to add a Payment Type Lookup record. This component invokes the ATC1PaymentTypeLookup Inbound Web Service using the C1-PaymentTypeLookup Business Object.

Component	Description
C1-PaymentTypeLookupRead	Used to read a Payment Type Lookup record. This component invokes the ATC1PaymentTypeLookup Inbound Web Service using the C1-PaymentTypeLookup Business Object.
C1-PaymentTypeLookupUpdate	Used to update a Payment Type Lookup record. This component invokes the ATC1PaymentTypeLookup Inbound Web Service using the C1-PaymentTypeLookup Business Object.
C1-PaymentTypeLookupDelete	Used to delete a Payment Type Lookup record. This component invokes the ATC1PaymentTypeLookup Inbound Web Service using the C1-PaymentTypeLookup Business Object.
C1-PersonContactTypeAdd	Used to add a Person Contact Type. This component invokes the ATC1PersonContactType Inbound Web Service using the C1-PersonContactType Business Object.
C1-PersonContactTypeRead	Used to read a Person Contact Type. This component invokes the ATC1PersonContactType Inbound Web Service using the C1-PersonContactType Business Object.
C1-PersonContactTypeUpdate	Used to update a Person Contact Type. This component invokes the ATC1PersonContactType Inbound Web Service using the C1-PersonContactType Business Object.
C1-PersonContactTypeDelete	Used to delete a Person Contact Type. This component invokes the ATC1PersonContactType Inbound Web Service using the C1-PersonContactType Business Object.
C1-PremiseTypeAdd	Used to read a Premise Type record. This component invokes the ATC1PremiseType Inbound Web Service using the C1-PremiseTypePhysicalBO Business Object.
C1-PremiseTypeRead	Used to read a Premise Type record. This component invokes the ATC1PremiseType Inbound Web Service using the C1-PremiseTypePhysicalBO Business Object.

Component	Description
C1-PremiseTypeUpdate	Used to update a Premise Type record. This component invokes the ATC1PremiseType Inbound Web Service using the C1-PremiseTypePhysicalBO Business Object.
C1-PremiseTypeDelete	Used to Delete a Premise Type record. This component invokes the ATC1PremiseType Inbound Web Service using the C1-PremiseTypePhysicalBO Business Object.
C1-ProviderConfigurationOptionAdd	Used to add a Provider Configuration Option record. This component invokes the ATC1ProviderConfigurationOption Inbound Web Service using the C1-ProviderConfigurationOptionBusiness Service.
C1-ProviderConfigurationOptionDelete	Used to delete a Provider Configuration Option record. This component invokes the ATC1ProviderConfigurationOption Inbound Web Service using the C1-ProviderConfigurationOptionBusiness Service.
C1-ProviderConfigurationOptionRead	Used to read a Provider Configuration Option record. This component invokes the ATC1ProviderConfigurationOption Inbound Web Service using the C1-ProviderConfigurationOptionBusiness Service.
C1-ProviderConfigurationOptionUpdate	Used to update a Provider Configuration Option record. This component invokes the ATC1ProviderConfigurationOption Inbound Web Service using the C1-ProviderConfigurationOptionBusiness Service.
C1-QuestionAdd	Used to add a Question - CCB record. This component invokes the ATC1Question Inbound Web Service using the C1-Question Business Object.
C1-QuestionDelete	Used to delete a Question - CCB record. This component invokes the ATC1Question Inbound Web Service using the C1-Question Business Object.

Component	Description
C1-QuestionRead	Used to read a Question - CCB record. This component invokes the ATC1Question Inbound Web Service using the C1-Question Business Object.
C1-QuestionUpdate	Used to add a Question - CCB record. This component invokes the ATC1Question Inbound Web Service using the C1-Question Business Object.
C1-SATypeAdd	Used to add a SA Type record. This component invokes the ATC1SPTYPE Inbound Web Service using the C1-SPTYPEPhysicalBO Business Object.
C1-SATypeRead	Used to read a SA Type record. This component invokes the ATC1SPTYPE Inbound Web Service using the C1-SPTYPEPhysicalBO Business Object.
C1-SATypeUpdate	Used to update a SA Type record. This component invokes the ATC1SPTYPE Inbound Web Service using the C1-SPTYPEPhysicalBO Business Object.
C1-SATypeDelete	Used to Delete a SA Type record. This component invokes the ATC1SPTYPE Inbound Web Service using the C1-SPTYPEPhysicalBO Business Object.
C1-SATypeSARelationshipTypeAdd	Used to add a SA Type SA Relationship Type record. This component invokes the ATC1SATypeSARelationshipType Inbound Web Service using the C1-SATypeSARelationshipType Business Object.
C1-SATypeSARelationshipTypeRead	Used to read a SA Type Relationship Type Record. This component invokes the ATC1SATypeSARelationshipType Inbound Web Service using the C1-SATypeSARelationshipType Business Object.
C1-SATypeSARelationshipTypeUpdate	Used to update a SA Type Relationship Type record. This component invokes the ATC1SATypeSARelationshipType Inbound Web Service using the C1-SATypeSARelationshipType Business Object.

Component	Description
C1-SATypeSARelationshipTypeDelete	Used to Delete a SA Type Relationship Type record. This component invokes the ATC1SATypeSARelationshipType Inbound Web Service using the C1-SATypeSARelationshipType Business Object.
C1-SARelTypeAdd	Used to add a SA Relationship Type record. This component invokes the ATC1SARelType Inbound Web Service using the C1-SARelTypePhysicalBO Business Object.
C1-SARelTypeDelete	Used to delete a SA Relationship Type record. This component invokes the ATC1SARelType Inbound Web Service using the C1-SARelTypePhysicalBO Business Object.
C1-SARelTypeRead	Used to read a SA Relationship Type record. This component invokes the ATC1SARelType Inbound Web Service using the C1-SARelTypePhysicalBO Business Object.
C1-SARelTypeUpdate	Used to update a SA Relationship Type record. This component invokes the ATC1SARelType Inbound Web Service using the C1-SARelTypePhysicalBO Business Object.
C1-ServiceCallCommMethodAdd	Used for adding a Service Call Communication Action Method. This component invokes the ATC1ServiceCallCommMethod Inbound Web Service using the Service Call Communication Action Method Business Object.
C1-ServiceCallCommMethodRead	Used for reading a Service Call Communication Action Method. This component invokes the ATC1ServiceCallCommMethod Inbound Web Service using the C1-ServiceCallCommMethod Business Object.
C1-ServiceCallCommMethodUpdate	Used for updating a Service Call Communication Action Method. This component invokes the ATC1ServiceCallCommMethod Inbound Web Service using the C1-ServiceCallCommMethod Business Object.

Component	Description
C1-ServiceCallCommMethodDelete	Used for deleting a Service Call Communication Action Method. This component invokes the ATC1ServiceCallCommMethod Inbound Web Service using the C1-ServiceCallCommMethod Business Object.
C1-ServiceCodeAdd	Used to add a Service Code - CCB record. This component invokes the ATC1ServiceCode Inbound Web Service using the C1-ServiceCode Business Object.
C1-ServiceCodeDelete	Used for updating a Service Code - CCB record. This component invokes the ATC1ServiceCode Inbound Web Service using the C1-ServiceCode Business Object.
C1-ServiceCodeUpdate	Used for updating a Service Code - CCB record. This component invokes the ATC1ServiceCode Inbound Web Service using the C1-ServiceCode Business Object.
C1-ServiceCodeRead	Used for reading a Service Code - CCB record. This component invokes the ATC1ServiceCode Inbound Web Service using the C1-ServiceCode Business Object.
C1-SPTTypeAdd	Used to add a SP Type record. This component invokes the ATC1SPTType Inbound Web Service using the C1-SPTTypePhysicalBO Business Object.
C1-SPTTypeRead	Used to Read a SP Type record. This component invokes the ATC1SPTType Inbound Web Service using the C1-SPTTypePhysicalBO Business Object.
C1-SPTTypeUpdate	Used to Update a SP Type record. This component invokes the ATC1SPTType Inbound Web Service using the C1-SPTTypePhysicalBO Business Object.
C1-SPTTypeDelete	Used to Delete a SP Type record. This component invokes the ATC1SPTType Inbound Web Service using the C1-SPTTypePhysicalBO Business Object.

Component	Description
C1-StatementCycleAdd	Used to add a Statement Cycle record. This component invokes the ATC1StatementCycle Inbound Web Service using the C1-StatementCyclePhysicalBO Business Object.
C1-StatementCycleRead	Used to read a Statement Cycle record. This component invokes the ATC1StatementCycle Inbound Web Service using the C1-StatementCyclePhysicalBO Business Object.
C1-StatementCycleUpdate	Used to update a Statement Cycle record. This component invokes the ATC1StatementCycle Inbound Web Service using the C1-StatementCyclePhysicalBO Business Object.
C1-StatementCycleDelete	Used to delete a Statement Cycle record. This component invokes the ATC1StatementCycle Inbound Web Service using the C1-StatementCyclePhysicalBO Business Object.
C1-StartServiceRequestTypeAdd	Used to add a Start Service Request Type record. This component invokes the ATC1StartServiceRequestType Inbound Web Service using the C1-StartServiceRequestType Business Object.
C1-StartServiceRequestTypeDelete	Used to delete a Start Service Request Type record. This component invokes the ATC1StartServiceRequestType Inbound Web Service using the C1-StartServiceRequestType Business Object.
C1-StartServiceRequestTypeRead	Used to Read a Start Service Request Type record. This component invokes the ATC1StartServiceRequestType Inbound Web Service using the C1-StartServiceRequestType Business Object.
C1-StartServiceRequestTypeUpdate	Used to Read a Start Service Request Type record. This component invokes the ATC1StartServiceRequestType Inbound Web Service using the C1-StartServiceRequestType Business Object.

Component	Description
C1-StartServiceActionMethodAdd	Used for adding a Start Service Action Method record. This component invokes the ATC1StartServiceActionMethod Inbound Web Service using the C1-StartStopActionMethod Business Object.
C1-StartServiceActionMethodDelete	Used for deleting a Start Service Action Method record. This component invokes the ATC1StartServiceActionMethod Inbound Web Service using the C1-StartStopActionMethod Business Object.
C1-StartServiceActionMethodRead	Used for reading a Start Service Action Method record. This component invokes the ATC1StartServiceActionMethod Inbound Web Service using the C1-StartStopActionMethod Business Object.
C1-StartServiceActionMethodUpdate	Used for updating a Start Service Action Method record. This component invokes the ATC1StartServiceActionMethod Inbound Web Service using the C1-StartStopActionMethod Business Object.
C1-StopServiceActionMethodAdd	Used for adding a Stop Service Action Method record. This component invokes the ATC1StopServiceActionMethod Inbound Web Service using the C1-StartStopActionMethod Business Object.
C1-StopServiceActionMethodDelete	Used for deleting a Stop Service Action Method record. This component invokes the ATC1StopServiceActionMethod Inbound Web Service using the C1-StartStopActionMethod Business Object.
C1-StopServiceActionMethodRead	Used for reading a Stop Service Action Method record. This component invokes the ATC1StopServiceActionMethod Inbound Web Service using the C1-StartStopActionMethod Business Object.

Component	Description
C1-StopServiceActionMethodUpdate	Used for updating a Stop Service Action Method record. This component invokes the ATC1StopServiceActionMethod Inbound Web Service using the C1-StartStopActionMethod Business Object.
C1-SATypeStartOptionAdd	Used for adding a SA Type Start Option record. This component invokes the ATC1SATypeStartOption Inbound Web Service using the C1-SATypeStartOptionPhysicalBO Business Object.
C1-SATypeStartOptionDelete	Used for deleting a SA Type Start Option record. This component invokes the ATC1SATypeStartOption Inbound Web Service using the C1-SATypeStartOptionPhysicalBO Business Object.
C1-SATypeStartOptionRead	Used for reading a SA Type Start Option record. This component invokes the ATC1SATypeStartOption Inbound Web Service using the C1-SATypeStartOptionPhysicalBO Business Object.
C1-SATypeStartOptionUpdate	Used for updating a SA Type Start Option record. This component invokes the ATC1SATypeStartOption Inbound Web Service using the C1-SATypeStartOptionPhysicalBO Business Object.
C1-SvcProvMktOptAdd	Used to add a Svc Prov Mkt Opt record. This component invokes the ATC1SvcProvMktOpt Inbound Web Service using the C1-SvcProvMktOpt Business Object.
C1-SvcProvMktOptDelete	Used to delete a Svc Prov Mkt Opt record. This component invokes the ATC1SvcProvMktOpt Inbound Web Service using the C1-SvcProvMktOpt Business Object.
C1-SvcProvMktOptRead	Used to read a Svc Prov Mkt Opt record. This component invokes the ATC1SvcProvMktOpt Inbound Web Service using the C1-SvcProvMktOpt Business Object.

Component	Description
C1-SvcProvMktOptUpdate	Used to update a Svc Prov Mkt Opt record. This component invokes the ATC1SvcProvMktOpt Inbound Web Service using the C1-SvcProvMktOpt Business Object.
C1-TransferServiceActionMethodAdd	Used for adding a Transfer Service Action Method record. This component invokes the ATC1TransferServiceActionMethod Inbound Web Service using the C1-StartStopActionMethod Business Object.
C1-TransferServiceActionMethodDelete	Used for deleting a Transfer Service Action Method record. This component invokes the ATC1TransferServiceActionMethod Inbound Web Service using the C1-StartStopActionMethod Business Object.
C1-TransferServiceActionMethodRead	Used for reading a Transfer Service Action Method record. This component invokes the ATC1TransferServiceActionMethod Inbound Web Service using the C1-StartStopActionMethod Business Object.
C1-TransferServiceActionMethodUpdate	Used for updating a Transfer Service Action Method record. This component invokes the ATC1TransferServiceActionMethod Inbound Web Service using the C1-StartStopActionMethod Business Object.
C1-TransferServiceRequestTypeAdd	Used to add a Start Service Request Type record. This component invokes the ATC1TransferServiceRequestType Inbound Web Service using the C1-TransferServiceRequestType Business Object.
C1-TransferServiceRequestTypeDelete	Used to delete a Start Service Request Type record. This component invokes the ATC1TransferServiceRequestType Inbound Web Service using the C1-TransferServiceRequestType Business Object.

Component	Description
C1-TransferServiceRequestTypeRead	Used to Read a Start Service Request Type record. This component invokes the ATC1TransferServiceRequestType Inbound Web Service using the C1-TransferServiceRequestType Business Object.
C1-TransferServiceRequestTypeUpdate	Used to Update a Start Service Request Type record. This component invokes the ATC1TransferServiceRequestType Inbound Web Service using the C1-TransferServiceRequestType Business Object.
C1-UserMiscRead	Used to Read a User Miscellaneous record. This component invokes the ATC1UserMisc Inbound Web Service using the C1-UserMisc Business Object.
C1-UserMiscUpdate	Used to Update a User Miscellaneous record. This component invokes the ATC1UserMisc Inbound Web Service using the C1-UserMisc Business Object.
C1-WorkCalendarAdd	Used for adding a Work Calendar record. This component invokes the ATC1WorkCalendar Inbound Web Service using the F1-WorkCalendarPhysicalBO Business Object.
C1-WorkCalendarDelete	Used for deleting a Work Calendar record. This component invokes the ATC1WorkCalendar Inbound Web Service using the F1-WorkCalendarPhysicalBO Business Object.
C1-WorkCalendarRead	Used for reading a Work Calendar record. This component invokes the ATC1WorkCalendar Inbound Web Service using the F1-WorkCalendarPhysicalBO Business Object.
C1-WorkCalendarUpdate	Used for updating a Work Calendar record. This component invokes the ATC1WorkCalendar Inbound Web Service using the F1-WorkCalendarPhysicalBO Business Object.

Credit and Collection

Component	Description
C1-CollAgencyReferralAdd	Used to add a collection agency referral record. This component invokes the ATC1CollectionAgencyReferral Inbound Web Service using the C1CollAgencyRefAdd Business Service.
C1-CollAgencyReferralDelete	Used to delete a collection agency referral record. This component invokes the ATC1CollectionAgencyReferral Inbound Web Service using the C1CollAgencyRefDelete Business Service.
C1-CollAgencyReferralRead	Used to read a collection agency referral record. This component invokes the ATC1CollectionAgencyReferral Inbound Web Service using the C1CollAgencyRefRead Business Service.
C1-CollAgencyReferralUpdate	Used to update a collection agency referral record. This component invokes the Inbound Web Service ATC1CollectionAgencyReferral using the C1CollAgencyRefUpdate Business Service.
C1-CollectionProcessAdd	Used to add a collection process record. This component invokes the Inbound Web Service ATC1CollectionProcess using the C1CollectionProcAdd Business Service.
C1-CollectionProcessRead	Used to read a collection process record. This component invokes the Inbound Web Service ATC1CollectionProcess using the C1CollectionProcRead Business Service.
C1-CollectionProcessUpdate	Used to update a collection process record. This component invokes the Inbound Web Service ATC1CollectionProcess using the C1CollectionProcUpdate Business Service.
C1-CutProcessRead	Used to read a cut process record. This component invokes the ATC1CutProcess Inbound Web Service using the C1CutProcRead Business Service.
C1-CutProcessUpdate	Used to update a cut process record. This component invokes the Inbound Web Service ATC1CutProcess using the C1CutProcUpdate Business Service.

Component	Description
C1-OverdueProcessRead	Used to read an overdue process record. This component invokes the Inbound Web Service ATC1OverdueProcess using the C1OverdueProcessRead Business Service.
C1-OverdueProcessUpdate	Used to update an overdue process record. This component invokes the Inbound Web Service ATC1OverdueProcess using the C1OverdueProcessUpdate Business Service.
C1-PayPlanAdd	Used to add a pay plan record. This component invokes the Inbound Web Service ATC1PayPlan using the C1PayPlanAdd Business Service.
C1-PayPlanRead	Used to read a pay plan record. This component invokes the Inbound Web Service ATC1PayPlan using the C1PayPlanRead Business Service.
C1-PayPlanUpdate	Used to update a pay plan record. This component invokes the Inbound Web Service ATC1PayPlan using the C1PayPlanUpdate Business Service.
C1-PaymentArrangementAdd	Used to add a payment arrangement record. This component invokes the Inbound Web Service ATC1PayArrangement using C1PayArrangementAdd Business Service.
C1-PaymentArrangementRead	Used to read a payment arrangement record. This component invokes the Inbound Web Service ATC1PayArrangement using C1PayArrangementRead Business Service.
C1-PaymentArrangementUpdate	Used to update a payment arrangement record. This component invokes the Inbound Web Service ATC1PayArrangement using the C1PayArrangementUpdate Business Service.
C1-PayArrangementByBillAdd	Used to add a payment arrangement by bill record. This component invokes the Inbound Web Service ATC1PaymentArrangementByBill using the C1PayArrangeByBillAdd Business Service.

Component	Description
C1-PayArrangementByBillRead	Used to read a payment arrangement by bill record. This component invokes the Inbound Web Service ATC1PayArrangeByBill using the C1PayArrangeByBillRead Business Service.
C1-PayArrangementByBillUpdate	Used to update a payment arrangement by bill record. This component invokes the Inbound Web Service ATC1PayArrangeByBill using the C1PayArrangeByBillUpdate business service.
C1-SeveranceProcessRead	Used to read a severance process record. This component invokes the Inbound Web Service ATC1SeveranceProcess using the C1SeveranceProcessRead Business Service.
C1-SeveranceProcessUpdate	Used to update a severance process record. This component invokes the Inbound Web Service ATC1SeveranceProcess using the C1SeveranceProcessUpdate Business Service.
C1-WriteOffRead	Used to read a write off record. This component invokes the Inbound Web Service ATC1WriteOff using the C1WriteOffRead Business Service.
C1-WriteOffUpdate	Used to update a write off record. This component invokes the Inbound Web Service ATC1WriteOff using the C1WriteOffUpdate Business Service.
C1-WriteOffProcessAdd	Used to update a pay plan record. This component invokes the Inbound Web Service ATC1WriteOffProcess using the C1WriteOffProcessAdd Business Service.
C1-WriteOffProcessRead	Used to update a pay plan record. This component invokes the Inbound Web Service ATC1WriteOffProcess using the C1WriteOffProcessRead Business Service.
C1-WriteOffProcessUpdate	Used to update a pay plan record. This component invokes the Inbound Web Service ATC1WriteOffProcess using the C1WriteOffProcessUpdate Business Service.

Customer Information

Component	Description
C1-AccountAdd	Used to create an Account record. This component invokes the ATC1Account Inbound Web Service using the C1AccountPhysical Business Object.
C1-AccountBSRead	Used to read an existing Account record. This component invokes the ATC1AccountBS Inbound Web Service using the C1-AccountRead Business Service.
C1-AccountBSUpdate	Used to update an existing Account record. This component invokes the ATC1AccountBS Inbound Web Service using the C1-AccountUpdate Business Service.
C1-AccountUpdate	Used to update an existing Account record. This component invokes the ATC1Account Inbound Web Service using the C1AccountPhysical Business Object.
C1-AccountDelete	Used to delete an existing Account record. This component invokes the ATC1Account Inbound Web Service using the C1AccountPhysical Business Object.
C1-AccountRead	Used to read an existing Account record. This component invokes the ATC1Account Inbound Web Service using the C1AccountPhysical Business Object.
C1-CaseAdd	Used to create a Case record. This component invokes the ATC1Case Inbound Web Service using the C1CasePhysical Business Object.
C1-CaseUpdate	Used to update an existing Case record. This component invokes the ATC1Case Inbound Web Service using the C1CasePhysical Business Object.
C1-CaseRead	Used to read an existing Case record. This component invokes the ATC1Case Inbound Web Service using the C1CasePhysical Business Object.

Component	Description
C1-CaseBOAdd	Used to create a Case record. This component invokes the ATC1CaseBO Inbound Web Service using the C1-Case Business Object.
C1-CaseBOUpdate	Used to update an existing Case record. This component invokes the ATC1CaseBO Inbound Web Service using the C1-Case Business Object.
C1-CaseBORead	Used to read an existing Case record. This component invokes the ATC1CaseBO Inbound Web Service using the C1-Case Business Object.
C1-ContractOptionAdd	Used to create a Contract Option record. This component invokes the ATC1ContractOption Inbound Web Service using the C1ContractOptionPhysical Business Object.
C1-ContractOptionDelete	Used to delete an existing Contract Option record. This component invokes the ATC1ContractOption Inbound Web Service using the C1ContractOptionPhysical Business Object.
C1-ContractOptionUpdate	Used to update (Update, Freeze and Cancel) an existing Contract Option record. This component invokes the ATC1ContractOption Inbound Web Service using the C1ContractOptionPhysical Business Object.
C1-ContractOptionRead	Used to read an existing Contract Option record. This component invokes the ATC1ContractOption Inbound Web Service using the C1ContractOptionPhysical Business Object.
C1-CreateSARelationshipSubSA	Used to create SA Relationship Sub SA record. This component invokes the ATC1CreateSARelationshipSubSA Inbound Web Service using the C1CreateSARelationshipSubSA Service Script.
C1-CustomerContactAdd	Used to create a Customer Contact record. This component invokes the ATC1CustomerContact Inbound Web Service using the C1CustomerContactPhysical Business Object.

Component	Description
C1-CustomerContactUpdate	Used to update an existing Customer Contact record. This component invokes the ATC1CustomerContact Inbound Web Service using the C1CustomerContactPhysical Business Object.
C1-CustomerContactRead	Used to read an existing Customer Contact record. This component invokes the ATC1CustomerContact Inbound Web Service using the C1CustomerContactPhysical Business Object.
C1-DeclarationAdd	Used to create a Declaration record. This component invokes the ATC1Declaration Inbound Web Service using the C1DeclarationPhysical Business Object.
C1-DeclarationUpdate	Used to update an existing Declaration record. This component invokes the ATC1Declaration Inbound Web Service using the C1DeclarationPhysical Business Object.
C1-DeclarationDelete	Used to delete an existing Declaration record. This component invokes the ATC1Declaration Inbound Web Service using the C1DeclarationPhysical Business Object.
C1-DeclarationRead	Used to read an existing Declaration record. This component invokes the ATC1Declaration Inbound Web Service using the C1DeclarationPhysical Business Object.
C1-DepClassRecommendDeposit	Used to calculate a Deposit Class Recommend Deposit amount. This component invokes the ATC1DepClassRecommendDeposit Inbound Web Service using the Business Object.
C1-LandlordAgreementAdd	Used to create a Landlord Agreement record. This component invokes the ATC1LandlordAgreement Inbound Web Service using the C1LandlordAgreementPhysical Business Object.

Component	Description
C1-LandlordAgreementUpdate	Used to update an existing Landlord Agreement record. This component invokes the ATC1LandlordAgreement Inbound Web Service using the C1LandlordAgreementPhysical Business Object.
C1-LandlordAgreementRead	Used to read an existing Landlord Agreement record. This component invokes the ATC1LandlordAgreement Inbound Web Service using the C1LandlordAgreementPhysical Business Object.
C1-LoanUpdate	Used to update an existing Loan record. This component invokes the ATC1Loan Inbound Web Service using the ATC1Loan Business Service.
C1-LoanRead	Used to read an existing Loan record. This component invokes the ATC1Loan Inbound Web Service using the ATC1Loan Business Service.
C1-NonBilledBudgetAdd	Used to add a Non-billed Budget record. This component invokes the ATC1NonBilledBudget Inbound Web Service using the C1NBBAAdd Business Service.
C1-NonBilledBudgetUpdate	Used to update an existing Non-billed Budget record. This component invokes the ATC1NonBilledBudget Inbound Web Service using the C1NBBAUpdate Business Service.
C1-NonBilledBudgetRead	Used to read an existing Non-billed Budget record. This component invokes the ATC1NonBilledBudget Inbound Web Service using the C1NBBARead Business Service.
C1-NtfContactPreferenceAdd	Used to add a Notification Contact Preference. This component invokes the ATC1NotificationContactPreference Inbound Web Service using the C1-NtfContactPreference Business Object.

Component	Description
C1-NtfContactPreferenceRead	Used to read a Notification Contact Preference. This component invokes the ATC1NotificationContactPreference Inbound Web Service using the C1-NtfContactPreference Business Object.
C1-NtfContactPreferenceUpdate	Used to update a Notification Contact Preference. This component invokes the ATC1NotificationContactPreference Inbound Web Service using the C1-NtfContactPreference Business Object.
C1-NtfContactPreferenceDelete	Used to delete a Notification Contact Preference. This component invokes the ATC1NotificationContactPreference Inbound Web Service using the C1-NtfContactPreference Business Object.
C1-PersonAdd	Used to create a Person record. This component invokes the ATC1Person Inbound Web Service using the C1PersonPhysical Business Object.
C1-PersonDelete	Used to delete an existing Person record. This component invokes the ATC1Person Inbound Web Service using the C1PersonPhysical Business Object.
C1-PersonRead	Used to read an existing Person record. This component invokes the ATC1Person Inbound Web Service using the C1PersonPhysical Business Object.
C1-PersonUpdate	Used to update an existing Person record. This component invokes the ATC1Person Inbound Web Service using the C1PersonPhysical Business Object.
C1-PersonBSAdd	Used to add a Person record. This component invokes the ATC1PersonBS Inbound Web Service using the C1-PersonAdd Business Service.
C1-PersonBSRead	Used to read a Person record. This component invokes the ATC1PersonBS Inbound Web Service using the C1-PersonRead Business Service.

Component	Description
C1-PersonBSUpdate	Used to update a Person record. This component invokes the ATC1PersonBS Inbound Web Service using the C1-PersonUpdate Business Service.
C1-PersonContactUpdate	Used to add, update, and delete a Person Contact. This component invokes the ATC1PersonContact Inbound Web Service using the C1-PersonContact Business Object.
C1-PersonContactRead	Used to read a Person Contact Type. This component invokes the ATC1PersonContact Inbound Web Service using the C1-PersonContact Business Object.
C1-PremiseAdd	Used to create a Premise record. This component invokes the ATC1Premise Inbound Web Service using the C1PremisePhysical Business Object.
C1-PremiseUpdate	Used to update an existing Premise record. This component invokes the ATC1Premise Inbound Web Service using the C1PremisePhysical Business Object.
C1-PremiseDelete	Used to delete an existing Premise record. This component invokes the ATC1Premise Inbound Web Service using the C1PremisePhysical Business Object.
C1-PremiseRead	Used to read an existing Premise record. This component invokes the ATC1Premise Inbound Web Service using the C1PremisePhysical Business Object.
C1-PremiseManagementUpdate	Used to invoke the Premise Management functionality, including update, create, assign landlord, assign parent premise, remove landlord, remove parent premise, stop and start service on premise actions). This component invokes the ATC1PremiseManagement Inbound Web Service using the C1PremiseManagementUpdate Business Service.

Component	Description
C1-PremiseReplicatorUpdate	Used to invoke the Premise Replicator functionality. This component invokes the ATC1PremiseReplicator Inbound Web Service using the C1PremiseReplicatorUpdate Business Service.
C1-PushNotificationOptOutAdd	Used to add a Push Notification Opt Out. This component invokes the ATC1PushNotificationOptOut Inbound Web Service using the C1-PushNotificationOptOut Business Object.
C1-PushNotificationOptOutRead	Used to read a Push Notification Opt Out. This component invokes the ATC1PushNotificationOptOut Inbound Web Service using the C1-PushNotificationOptOut Business Object.
C1-PushNotificationOptOutDel	Used to delete a Push Notification Opt Out. This component invokes the ATC1PushNotificationOptOut Inbound Web Service using the C1-PushNotificationOptOut Business Object.
C1-RebateClaimAdd	Used to create a Rebate Claim record. This component invokes the ATC1RebateClaim Inbound Web Service using the C1-RebateClaim Business Object.
C1-RebateClaimUpdate	Used to update an existing Rebate Claim record. This component invokes the ATC1RebateClaim Inbound Web Service using the C1-RebateClaim Business Object.
C1-RebateClaimRead	Used to read an existing Rebate Claim record. This component invokes the ATC1RebateClaim Inbound Web Service using the C1-RebateClaim Business Object.
C1-RebateClaimDelete	Used to delete an existing Rebate Claim record. This component invokes the ATC1RebateClaim Inbound Web Service using the C1-RebateClaim Business Object.
C1-RebateClaimLineAdd	Used to create a Rebate Claim Line record. This component invokes the ATC1RebateClaimLine Inbound Web Service using the C1RebateClaimLinePhysical Business Object.

Component	Description
C1-RebateClaimLineUpdate	Used to update an existing Rebate Claim Line record. This component invokes the ATC1RebateClaimLine Inbound Web Service using the C1RebateClaimLinePhysical Business Object.
C1-RebateClaimLineRead	Used to read an existing Rebate Claim Line record. This component invokes the ATC1RebateClaimLine Inbound Web Service using the C1RebateClaimLinePhysical Business Object.
C1-RebateClaimLineDelete	Used to delete an existing Rebate Claim Line record. This component invokes the ATC1RebateClaimLine Inbound Web Service using the C1RebateClaimLinePhysical Business Object.
C1-RebateClaimLogsAdd	Used to add a Rebate Claim Log record. This component invokes the ATC1RebateClaimLogs Inbound Web Service using the C1RebateClaimPhysical Business Object.
C1-RebateClaimLogsRead	Used to read a Rebate Claim Log record. This component invokes the ATC1RebateClaimLogs Inbound Web Service using the C1RebateClaimPhysical Business Object.
C1-RecommendBudget	Used to Recommend Budget. This component invokes the ATC1Recommend Budget Inbound Web Service using the C1-RecommendBudget Business Service.
C1-SARelationshipAdd	Used to create an SA Relationship record. This component invokes the ATC1SARelationship Inbound Web Service using the C1-MaintSARelationship Service Script.
C1-SARelationshipUpdate	Used to update (update, activate, cancel, create sub SA) an existing SA Relationship record. This component invokes the ATC1SARelationship Inbound Web Service using the C1-SARelationshipPhysicalBO Business Object.
C1-SARelationshipRead	Used to read an existing SA Relationship record. This component invokes the ATC1SARelationship Inbound Web Service using the C1-SARelationshipPhysicalBO Business Object.

Component	Description
C1-ServiceAgreementAdd	Used to create a Service Agreement record. This component invokes the ATC1ServiceAgreement Inbound Web Service using the C1ServiceAgreementPhysical Business Object.
C1-ServiceAgreementRead	Used to read an existing Service Agreement record. This component invokes the ATC1ServiceAgreement Inbound Web Service using the C1ServiceAgreementPhysical Business Object.
C1-ServiceAgreementUpdate	Used to update (activate, apply new start option, cancel, close, cancel proposal SA, accept proposal SA, decline proposal SA, activate proposal SA, reactivate, stop) an existing Service Agreement record. This component invokes the ATC1ServiceAgreementUpdate Inbound Web Service using the C1ServiceAgreementUpdate Business Service.
C1-ServiceCreditEventAdd	Used to create a Service Credit Event record. This component invokes the ATC1ServiceCreditEvent Inbound Web Service using the C1ServiceCreditEventPhysical Business Object.
C1-ServiceCreditEventUpdate	Used to update an existing (cancel, complete, transfer) Service Credit Event record. This component invokes the ATC1ServiceCreditEvent Inbound Web Service using the C1ServiceCreditEventPhysical Business Object.
C1-ServiceCreditEventDelete	Used to delete an existing Service Credit Event record. This component invokes the ATC1ServiceCreditEvent Inbound Web Service using the C1ServiceCreditEventPhysical Business Object.
C1-ServiceCreditEventRead	Used to read an existing Service Credit Event record. This component invokes the ATC1ServiceCreditEvent Inbound Web Service using the C1ServiceCreditEventPhysical Business Object.

Component	Description
C1-SCMembershipAdd	Used to create a Service Credit Membership record. This component invokes the ATC1ServiceCreditMembership Inbound Web Service using the C1SCMPPhysical Business Object.
C1-SCMembershipUpdate	Used to update (activate, cancel) an existing Service Credit Membership record. This component invokes the ATC1ServiceCreditMembership Inbound Web Service using the C1SCMPPhysical Business Object.
C1-SCMembershipDelete	Used to delete an existing Service Credit Membership record. This component invokes the ATC1ServiceCreditMembership Inbound Web Service using the C1SCMPPhysical Business Object.
C1-SCMembershipRead	Used to read an existing Service Credit Membership record. This component invokes the ATC1ServiceCreditMembership Inbound Web Service using the C1SCMPPhysical Business Object.
C1-ServicePointAdd	Used to create a Service Point record. This component invokes the ATC1ServicePoint Inbound Web Service using the C1ServicePointPhysical Business Object.
C1-ServicePointUpdate	Used to update an existing Service Point record. This component invokes the ATC1ServicePoint Inbound Web Service using the C1ServicePointPhysical Business Object.
C1-ServicePointDelete	Used to delete an existing Service Point record. This component invokes the ATC1ServicePoint Inbound Web Service using the C1ServicePointPhysical Business Object.
C1-ServicePointRead	Used to read an existing Service Point record. This component invokes the ATC1ServicePoint Inbound Web Service using the C1ServicePointPhysical Business Object.

Component	Description
C1-ServiceProviderSARelUpdate	Used to update (update, create, expire) an existing Service Provider SA Relationship record. This component invokes the ATC1ServiceProviderSARelationship Inbound Web Service using the C1ServiceProviderSARelUpdate Business Service.
C1-ServiceProviderSARelRead	Used to query an existing Service Provider SA Relationship record. This component invokes the ATC1ServiceProviderSARelationship Inbound Web Service using the C1ServiceProviderSARelRead Business Service.
C1-StartStopUpdate	Used to invoke the Start Stop functionality including the cancel, stop and start actions. This component invokes the ATC1StartStop Inbound Web Service using the C1StartStopUpdate Business Service.
C1-StartStopRead	Used to read a Start Stop record. This component invokes the ATC1StartStop Inbound Web Service using the C1StartStopRead Business Service.
C1-StatementConstructAdd	Used to create a Statement Construct record. This component invokes the ATC1StatementConstruct Inbound Web Service using the C1StatementConstructPhysical Business Object.
C1-StatementConstructUpdate	Used to update an existing Statement Construct record. This component invokes the ATC1StatementConstruct Inbound Web Service using the C1StatementConstructPhysical Business Object.
C1-StatementConstructDelete	Used to delete an existing Statement Construct record. This component invokes the ATC1StatementConstruct Inbound Web Service using the C1StatementConstructPhysical Business Object.

Component	Description
C1-StatementConstructRead	Used to query an existing Statement Construct record. This component invokes the ATC1StatementConstruct Inbound Web Service using the C1StatementConstructPhysical Business Object.
C1-CSRTSvcEligCriteriaAdd	Used to create CS Request Type Svc Eligibility Criteria record. This component invokes the ATC1CSRTSvcEligCriteria Inbound Web Service using the C1-CSRTSvcEligCriteria Business Object.
C1-CSRTSvcEligCriteriaDelete	Used to delete CS Request Type Svc Eligibility Criteria record. This component invokes the ATC1CSRTSvcEligCriteria Inbound Web Service using the C1-CSRTSvcEligCriteria Business Object.
C1-CSRTSvcEligCriteriaRead	Used to read CS Request Type Svc Eligibility Criteria record. This component invokes the ATC1CSRTSvcEligCriteria Inbound Web Service using the C1-CSRTSvcEligCriteria Business Object.
C1-CSRTSvcEligCriteriaUpdate	Update to delete CS Request Type Svc Eligibility Criteria record. This component invokes the ATC1CSRTSvcEligCriteria Inbound Web Service using the C1-CSRTSvcEligCriteria Business Object.
C1-CSRTRelUpdAdd	Used to add a CS Request Type Related Update record. This component invokes the ATC1CSRTRelUpd Inbound Web Service using the C1-CSRTRelUpd Business Object.
C1-CSRTRelUpdDelete	Used to delete a CS Request Type Related Update record. This component invokes the ATC1CSRTRelUpd Inbound Web Service using the C1-CSRTRelUpd Business Object.
C1-CSRTRelUpdRead	Used to read a CS Request Type Related Update record. This component invokes the ATC1CSRTRelUpd Inbound Web Service using the C1-CSRTRelUpd Business Object.

Component	Description
C1-CSRTRelUpdUpdate	Used to update a CS Request Type Related Update record. This component invokes the ATC1CSRTRelUpd Inbound Web Service using the C1-CSRTRelUpd Business Object.

Data Synchronization

Component	Description
C1-StartStopBSRead	Used to read a Start Stop record. This component invokes the ATC1StartStopBS Inbound Web Service using the C1-StartStopMaintenanceRead Business Service.
C1-FASyncRequestRead	Used to read an FA Sync Request record. This component invokes the ATC1FASyncRequestRead Inbound Web Service using the C1-FASyncRequest Business Object.
C1-FASyncRequestUpdate	Used to update an FA Sync Request record. This component invokes the ATC1FASyncRequestUpdate Inbound Web Service using the C1-FASyncRequest Business Object.
C1-MDM2MtrConfigSyncReqRead	Used to read an MDM2 Meter Configuration Sync Request record. This component invokes the ATC1MDM2MtrConfigSyncReqRead Inbound Web Service using the C1-MDM2MtrConfigSyncRequest Business Object.
C1-MDM2PersonSyncRequestRead	Used to read an MDM2 Person Sync Request record. This component invokes the ATC1MDM2PersonSyncRequestRead Inbound Web Service using the C1-MDM2PersonSyncRequest Business Object.
C1-MDM2SASyncRequestRead	Used to read an MDM2 SA Sync Request record. This component invokes the ATC1MDM2SASyncRequestRead Inbound Web Service using the C1-MDM2SASyncRequest Business Object.

Component	Description
C1-MDM2SARelSyncRequest	Used to read a SA Relationship Sync Request record. This component invokes the ATC1MDM2SARelSyncRequestRead Inbound Web Service using the Business Object “C1-MDM2SARelSyncRequest”.
C1-GetSyncRequestId	Used to get the sync request ID of a given primary key ID (for example: Premise, SP, Meter, Meter Config, etc) using a specific query zone. The following zones can be used: • C1-GETSPSYNC - Get Sync Request ID using SP ID • C1-GETPERSYN - Get Sync Request ID using Person ID • C1-GETMRSYN - Get Sync Request ID using Meter Read ID • C1-GETMTRCFS - Get Sync Request ID using Meter Configuration ID • C1-GETSASYN - Get Sync Request ID using Service Agreement ID • C1-GETSPMHSY - Get Sync Request ID using SP Meter History ID • C1-GETMTRSYN - Get Sync Request ID using Meter ID • C1-GETFASYN - Get Sync Request ID using Field Activity ID • C1-GETSYNCRQ - Get Sync Request ID using External ID • C1-GETSYNCU1 - Get Sync Req ID using Bill Cycle • C1-GETSYNCU2 - Get Sync Req ID using Contract Option Event ID • C1-GETSYNCU3 - Get Sync Req ID using Contract Option ID • C1-GETACTSYN - Get Sync Req ID using Account ID This component invokes the ATC1GetSyncRequestId Inbound Web Service using the C1-GetSyncRequestId Business Service.
C1-MDM2MRSyncRequestRead	Used to read an MDM2 Meter Read Sync Request record. This component invokes the ATC1MDM2MRSyncRequestRead Inbound Web Service using the C1-MDM2MRSyncRequest Business Object.

Component	Description
C1-MDM2SPSyncRequestRead	Used to read an MDM2 Service Point Sync Request record. This component invokes the ATC1MDM2SPSyncRequestRead Inbound Web Service using the C1-MDM2SPSyncRequest Business Object.
C1-MDM2SpMtrHistSyncReqRead	Used to read an MDM2 SP Meter History Sync Request record. This component invokes the ATC1MDM2SpMtrHistSyncReqRead Inbound Web Service using the C1-MDM2SpMtrHistSyncRequest Business Object.
C1-MDM2MtrSyncRequestRead	Used to read an MDM2 Meter Sync Request record. This component invokes the ATC1MDM2MtrSyncRequestRead Inbound Web Service using the C1-MDM2MtrSyncRequest Business Object.
C1-MDM2BillCycleSyncReqRead	Used to read an MDM2 Bill Cycle Sync Request record. This component invokes the ATC1MDM2BillCycleSyncRequestRead Inbound Web Service using the C1-MDM2BillCycleSyncRequest Business Object.
C1-MDM2ContOptEvtSyncReqRead	Used to read an MDM2 Contract Option Event Sync Request record. This component invokes the ATC1MDM2ContrOptEvtSyncReqRead Inbound Web Service using the C1-MDM2ContrOptEvtSyncRequest Business Object.
C1-MDM2ContractOptSyncReqRead	Used to read an MDM2 Contract Option Sync Request record. This component invokes the ATC1MDM2ContractOptSyncReqRead Inbound Web Service using the C1-MDM2ContractOptSyncRequest Business Object.
C1-NMSSPPerCntSyncRequestRead	Used to read an NMS SP Person Contact Sync Request record. This component invokes the ATC1NMSSPPerCntSyncRequestRead Inbound Web Service using the C1-NMSSPPerCntSyncRequest Business Object.

Component	Description
C1-NMSSPSyncRequestRead	Used to read an NMS SP Sync Request record. This component invokes the ATC1NMSSPSyncRequestRead Inbound Web Service using the C1-NMSSPSyncRequest Business Object.
C1-ODMSPSyncRequestRead	Used to read an ODM SP Sync Request record. This component invokes the ATC1ODMSPSyncRequestRead Inbound Web Service using the C1-ODMSPSyncRequest Business Object.
C1-SyncRequestUpdate	Used to update the message of Sync Request BO. This component also transitions the BO to: • The default next state, if the message list is not populated, or • The exception state, if message list is populated. This component invokes the ATC1SyncRequestUpdate Inbound Web Service using the F1-UpdateSyncRequest Business Service.
C1-MDM2MRSyncRequestRead	Used to read an MDM2 Meter Read Sync Request record. This component invokes the ATC1MDM2MRSyncRequestRead Inbound Web Service using the C1-MDM2MRSyncRequest Business Object.
C1-ExternalRepoPlusBillingSyncRead	Used to read a Billing Segment Sync Request record. This component invokes the ATC1ExternalRepoPlusBillingSyncRead Inbound Web Service using the C1-ExternalRepoPlusBillingSync Business Object.
C1-ExternalRepoPlusSPMeterSyncRead	Used to read a Service Point Sync Request record. This component invokes the ATC1ExternalRepoPlusSPMeterSync Inbound Web Service using the C1-ExternalRepoPlusSPMeterSync Business Object.
C1-ExternalRepoPlusSPMeterSyncUpdate	Used to update a Service Point Sync Request record. This component invokes the ATC1ExternalRepoPlusSPMeterSync Inbound Web Service using the C1-ExternalRepoPlusSPMeterSync Business Object.

Component	Description
C1-ExternalRepoPlusCusDataSyncRead	Used to read a Service Agreement Sync Request record. This component invokes the ATC1ExternalRepoPlusCusDataSyncRead Inbound Web Service using the C1-ExternalRepoPlusCusDataSync Business Object.
C1-ExternalRepoPlusBillSegSyncRead	Used to read a Bill Segment Sync Request record. This component invokes the ATC1ExternalRepoPlusBillSegSync Inbound Web Service using the C1-ExternalRepoPlusBillSegSync Business Object.
C1-ExternalRepoPlusBillSegSyncUpdate	Used to update a Bill Segment Sync Request record. This component invokes the ATC1ExternalRepoPlusBillSegSync Inbound Web Service using the C1-ExternalRepoPlusBillSegSync Business Object.
C1-ExternalRepoPlusBillSyncRead	Used to read a Bill Sync Request record. This component invokes the ATC1ExternalRepoPlusBillSync Inbound Web Service using the C1-ExternalRepoPlusBillSync Business Object.
C1-ExternalRepoPlusBillSyncUpdate	Used to update a Bill Sync Request record. This component invokes the ATC1ExternalRepoPlusBillSync Inbound Web Service using the C1-ExternalRepoPlusBillSync Business Object.
C1-ExternalRepoPlusMailAddSync Update	Used to read a Mailing Address Data for DataConnect v1+ sync. This component invokes the ATC1ExternalRepoPlusMailAddSync Inbound Web Service using the C1-ExternalRepoPlusMailAddSync Business Object.
C1-ExternalRepoPlusSASPSyncRead	Used to read a SA/SP Data Sync for DataConnect v1+. This component invokes the ATC1ExternalRepoPlusSASPSync Inbound Web Service using the C1-ExternalRepoSASPSync Business Object.

Component	Description
C1-ExternalRepoPlusSASPSyncUpdate	Used to update a SA/SP Data Sync for DataConnect v1+. This component invokes the ATC1ExternalRepoPlusSASPSync Inbound Web Service using the C1-ExternalRepoSASPSync Business Object.
C1-NtfContactPreferenceSyncRead	Used to read a Notification Contact Preference Sync Request. This component invokes the ATC1NtfContactPreferenceSyncUpdate Inbound Web Service using the C1NtfContactPreferenceSyncRead Business Service.
C1-NtfContactPreferenceSyncUpdate	Used to update a Notification Contact Preference Sync Request. This component invokes the ATC1NtfContactPreferenceSyncRead Inbound Web Service using the C1-NtfContactPreferenceSync Business Object.
F1-GenericDataSyncAdd	Used to add a Generic Sync Request record. This component invokes the ATF1GenericDataSync Inbound Web Service using the F1-GenericDataSync Business Object.
F1-GenericDataSyncDelete	Used to delete a Generic Sync Request record. This component invokes the ATF1GenericDataSync Inbound Web Service using the F1-GenericDataSync Business Object.
F1-GenericDataSyncRead	Used to read a Generic Sync Request record. This component invokes the ATF1GenericDataSync Inbound Web Service using the F1-GenericDataSync Business Object.
F1-GenericDataSyncUpdate	Used to update a Generic Sync Request record. This component invokes the ATF1GenericDataSync Inbound Web Service using the F1-GenericDataSync Business Object.

DSS

Component	Description
C1-ThirdPartyOneTimePayNotification	This creates Third Party One Time Payment Notification. This component invokes the C1-ThirdPartyOneTimePayNotification Inbound Web Service using the C1-TPPayNotf Service Script.
CX-AccountChargesSummaryRetriever	Retrieve Account Charges Summary. This component invokes the CXAccountChargesSummaryRetriever Inbound Web Service using the WX-RAcctSumm Service Script.
CX-AccountLookUp	Search for Account details based on input. This component invokes the CXAccountLookUp Inbound Web Service using the C1AcctLookup Service Script.
CX-BillPayHistoryRetriever	View Bill/Payment History. This component invokes the CXBillPayHistoryRetriever Inbound Web Service using the WX-BillPayHs Service Script.
CX-BillSegmentHistoryRetriever	Bill Segment History -Amount and Quantity. This component invokes the CXBillSegmentHistoryRetriever Inbound Web Service using the CX-BsegHist Service Script.
CX-BillView	View Bill. This component invokes the CXBillView Inbound Web Service using the WX-ViewBill Service Script.
CX-CancelSchedPay	Cancel Scheduled One-Time Payment. This component invokes the CXCancelSchedPay Inbound Web Service using the WX-CanSchPay Service Script.
CX-ConnectedAccountsDetails	Retrieve the List of Connected Accounts. This component invokes the CXConnectedAccountsDetails Inbound Web Service using the CXConAccDtls Service Script.
CX-ConnectedAccountsWithGuests	Connected accounts with guest users. This component invokes the CXConnectedAccountsWithGuests Inbound Web Service using the CXConActWGst Service Script.

Component	Description
CX-ContextInfo	Get Self Service Context Information. This component invokes the CXContextInfo Inbound Web Service using the CX-CntxtInfo Service Script.
CX-CreateMeterRead	Create Meter Read. This component invokes the CXCreateMeterRead Inbound Web Service using the WX-CreSSMR Service Script.
CX-FinancialHistoryDownload	Account's Financial History Download. This component invokes the CXFinancialHistoryDownload Inbound Web Service using the CX-AcctFinHD Service Script.
CX-FinancialHistoryRetriever	Get Account's Financial History. This component invokes the CXFinancialHistoryRetriever Inbound Web Service using the CX-AcctFinHs Service Script.
CX-FormsList	Forms List. This component invokes the CXFormsList Inbound Web Service using the CX-FormsList Service Script.
CX-FormsManagement	Forms Management. This component invokes the CXFormsManagement Inbound Web Service using the WX-FormsMgmt Service Script.
CX-GetConsumptionSummary	Get Consumption Summary. This component invokes the CXGetConsumptionSummary Inbound Web Service using the WX-GetConS Service Script.
CX-ReportOutage	Report Outage. This component invokes the CXReportOutage Inbound Web Service using the C1RepOutage Service Script.
CX-RetOutageJobHistory	Retrieve Outage Job History Details. This component invokes the CXRetOutageJobHistory Inbound Web Service using the C1RetJobHist Service Script.

Component	Description
CX-GetDSSAlerts	Returns DSS Alerts. This component invokes the CXGetDSSAlerts Inbound Web Service using the CX-SSAlerts Service Script.
CX-GetMeteredOrBDSAs	List of Metered or Bill Determinant SA. This component invokes the CXGetMeteredOrBDSAs Inbound Web Service using the CX-RETSASPCL Service Script.
CX-GetSelfServiceLabels	Retrieve Self-Service Field Labels. This component invokes the CXGetSelfServiceLabels Inbound Web Service using the CX-GetSSLbl Service Script.
CX-MaintainCommPreferences	Maintain Communication Preferences. This component invokes the CXMaintainCommPreferences Inbound Web Service using the WX-CommPref Service Script.
CX-MaintainMailingAddressInfo	Maintain Mailing Address Information. This component invokes the CXMaintainMailingAddressInfo Inbound Web Service using the WX-MAddMain Service Script.
CX-MaintainPersonLanguageTimeZone	Maintain Person Language and Time Zone. This component invokes the CXMaintainPersonLanguageTimeZone Inbound Web Service using the WX-MPerLngTZ Service Script.
CX-MaintainWebUser	Maintain Self Service Web User. This component invokes the CXMaintainWebUser Inbound Web Service using the CXWebUsrMain Service Script.
CX-MaintainWebUserAccount	Maintain Self Service Web User Account. This component invokes the CXMaintainWebUserAccount Inbound Web Service using the CXWebUsrAcct Service Script.
CX-MakePayment	Multi Account Payments. This component invokes the CXMakePayment Inbound Web Service using the WX-MakePay Service Script.

Component	Description
CX-MakePayment_upd	Multi Account Payments. This component invokes the CXMakePayment Inbound Web Service using the WX-MakePay Service Script.
CX-ManageCharities	Manage Auto Pay Charities. This component invokes the CXManageCharities Inbound Web Service using the C1PrcChrtAP Service Script.
CX-ManagePaymentOptions	Manage Self-Service Payment Options. This component invokes the CXManagePaymentOptions Inbound Web Service using the C1MngPayOpt Service Script.
CX-PaymentExtensionRequest	Payment Extension Request. This component invokes the CXPaymentExtensionRequest Inbound Web Service using the C1ProcPayExt Service Script.
CX-PreferredPayDateRequest	Process Preferred Pay Date Request. This component invokes the CXPreferredPayDateRequest Inbound Web Service using the C1PrefPayDt Service Script.
CX-PremiseSearch	Premise Search. This component invokes the CXPremiseSearch Inbound Web Service using the WX-PremSrch Service Script.
CX-ProcessBudgetRequest	Process Budget Request. This component invokes the CXProcessBudgetRequest Inbound Web Service using the WX-BudgetReq Service Script.
CX-ProcessInvitation	Process Invitation. This component invokes the CXProcessInvitation Inbound Web Service using the CXProcInvite Service Script.
CX-ProcessPayArrangementRequest	Process Payment Arrangement Request. This component invokes the CXProcessPayArrangementRequest Inbound Web Service using the WX-PayArrReq Service Script.

Component	Description
CX-ProcessStartStopRequest	Process Start Stop Request. This component invokes the CXProcessStartStopRequest Inbound Web Service using the WX-StrStpReq Service Script.
CX-RateAnalysis	Perform Rate Analysis. This component invokes the CXRateAnalysis Inbound Web Service using the WX-RateAnlys Service Script.
CX-RetrieveScalarUsage	Retrieve Scalar Usage. This component invokes the CXRetrieveScalarUsage Inbound Web Service using the WX-RetScaUsg Service Script.
CX-SetBillNotifyPreference	Setup Billing Notification Preferences. This component invokes the CXSetBillNotifyPreference Inbound Web Service using the WX-BNPSet Service Script.
CX-SetNotificationPreferences	Set Notification Preferences. This component invokes the CXSetNotificationPreferences Inbound Web Service using the WX-SetNtPref Service Script.
CX-UsageChargesProjected	Retrieve Projected Charges. This component invokes the CXUsageChargesProjected Inbound Web Service using the WX-ProjChrg Service Script.
CX-UsageChargesToDate	Retrieve Usage Charges to Date. This component invokes the CXUsageChargesToDate Inbound Web Service using the WX-UsgChrgDt Service Script.
CX-VerifyAccount	Account Verification(AND/OR). This component invokes the CXVerifyAccount Inbound Web Service using the CX-VerAcct Service Script.
CX-WebUserSearch	Web User Search. This component invokes the CXWebUserSearch Inbound Web Service using the CXWebUsrSrch Service Script.

Component	Description
F1-FeatureConfigPhysicalBO	Feature Configuration This component invokes the F1-FeatureConfigPhysicalBO Inbound Web Service using the F1-FeatureConfigPhysicalBO Physical Business Object.
WX-ProcessStartStopRequest	Process Start Stop Request. This component invokes the WXProcessStartStopRequest Inbound Web Service using the WX-StrStpReq Service Script.

DSS-SST

Component	Description
C1-ServiceEligibility	Used to determine if a customer is eligible to start service. This component invokes the C1-StartStopTransferTasks Inbound Web Service using the C1SSSvcElig Service Script.
C1-ServicesToStart	Used to Determine Services To Start. This component invokes the C1-StartStopTransferTasks Inbound Web Service using the C1SSSvcStrt Service Script.
C1-ServiceToStartProcessing	Used to Process Services To Start. This component invokes the C1-StartSopTransferTasks Inbound Web Service using the C1SSPreSvcSt Service Script.
C1-StopSASelectionValidation	Used to Validate Stop Service Agreement Selection. This component invokes the C1-StartSopTransferTasks Inbound Web Service using the C1SSVStopSAS Service Script.
C1-StopableServiceDetails	Used to Retrieve Services To Stop. This component invokes the C1-StartSopTransferTasks Inbound Web Service using the C1SSStpSvcSD Service Script.
C1-StopServiceFinalization	Used to Stop Service Finalization. This component invokes the C1-StartSopTransferTasks Inbound Web Service using the C1SSFinStopS Service Script.

Component	Description
C1-TransferServiceFinalization	Used to Transfer Service Finalization. This component invokes the C1-StartSopTransferTasks Inbound Web Service using the C1SSFinTranS Service Script.
C1-DepositAssessment	Used to determines the deposit requirements. This component invokes the C1-StartSopTransferTasks Inbound Web Service using the C1DepositAss Service Script.
C1-OtherPersonProcessing	Used to Process Other Person. This component invokes the C1-StartSopTransferTasks Inbound Web Service using the C1SSPrCtPer Service Script.
C1-OtherPersonReset	Used to Clear Other Person. This component invokes the C1-StartStopTransferTasks Inbound Web Service using the C1SSClrOtPer Service Script.
C1-RequestTypeDetails	Used to Retrieve Request Type Details. This component invokes the C1-StartStopTransferTasks Inbound Web Service using the C1SSRqTyRead Business Object.
C1-ServiceRelatedCustomerDetails	Used to Retrieve Service-Related Customer Details. This component invokes the C1-StartStopTransferTasks Inbound Web Service using the C1SSCustRead Service Script.

Field Order

Component	Description
C1-AppointmentRead	Used to read an existing Appointment record. This component invokes the ATC1Appointment Inbound Web Service using the C1AppointmentRead Business Service.
C1-AppointmentUpdate	Used to update an existing Appointment record. This component invokes the ATC1Appointment Inbound Web Service using the C1AppointmentUpdate Business Service.

Component	Description
C1-DispatchFieldActivityRead	Used to read an existing Dispatch Field Activity record. This component invokes the ATC1DispatchFA Inbound Web Service using the C1DispatchFARead Business Service.
C1-DispatchFieldActivityUpdate	Used to update an existing Dispatch Field Activity record. This component invokes the ATC1DispatchFA Inbound Web Service using the C1DispatchFAUpdate Business Service.
C1-GenerateFreezeApprAdjustment	Used to generate and freeze an Approval Adjustment record. This component invokes the ATC1GenerateFreezeApprAdjustment Inbound Web Service using the C1-CreateAdjustmentWithAppr Business Service.
C1-FAUploadStagingAdd	Used to create an FA Upload Staging record. This component invokes the ATC1FAUploadStaging Inbound Web Service using the C1FAUploadStagingAdd Business Service.
C1-FieldOrderRead	Used to read an existing Field Order record. This component invokes the ATC1FieldOrder Inbound Web Service using the C1FieldOrderPhysical Business Object.
C1-OutageCallWithoutPremAdd	Used to add an Outage Call without Premise record. This component invokes the ATC1OutageCallWithoutPrem Inbound Web Service using the C1-OutageCallWithoutPremise Business Object.
C1-OutageCallWithoutPremRead	Used to read an existing Outage Call without Premise record. This component invokes the ATC1OutageCallWithoutPrem Inbound Web Service using the C1-OutageCallWithoutPremise Business Object.
C1-OutageCallWithPremAdd	Used to add an Outage Call with Premise record. This component invokes the ATC1OutageCallWithPrem Inbound Web Service using the C1-OutageCallWithPremise Business Object.

Component	Description
C1-OutageCallWithoutPremRead	Used to read an existing Outage Call with Premise record. This component invokes the ATC1OutageCallWithPrem Inbound Web Service using the C1-OutageCallWithPremise Business Object.
C1-ServiceCallCommunicationAdd	Used for adding a Service Call Communication record. This component invokes the ATC1ServiceCallCommunication Inbound Web Service using the C1-ServiceCallCommunication Business Object.
C1-ServiceCallCommunicationRead	Used for reading a Service Call Communication record. This component invokes the ATC1ServiceCallCommunication Inbound Web Service using the C1-ServiceCallCommunication Business Object.
C1-ServiceCallCommunicationUpdate	Used for updating a Service Call Communication record. This component invokes the ATC1ServiceCallCommunication Inbound Web Service using the C1-ServiceCallCommunication Business Object.
C1-UpdateServiceCallCommunication	Used to Update a Service Call Communication Synchronization record. This component invokes the ATC1-UpdateServiceCallCommunication Inbound Web Service using the C1SvccUpdExc Service Script.

Financial

Component	Description
C1-AdjSearchByAcctId	Used for retrieving an Adjustment using an Account ID. This component invokes the ATC1AdjSearchByAcctId Inbound Web Service using the C1-AdjustmentSearchByAcctId Business Service.

Component	Description
C1-AdjustmentAdd	Used to adding an Adjustment record. This component invokes the ATC1Adjustment Inbound Web Service using the C1AdjustmentAdd Business Service.
C1-AdjustmentDelete	Used to delete an Adjustment. This component invokes the ATC1Adjustment Inbound Web Service using the C1AdjustmentDelete Business Service.
C1-AdjustmentRead	Used to read an Adjustment. This component invokes the ATC1Adjustment Inbound Web Service using the C1AdjustmentRead Business Service.
C1-AdjustmentUpdate	Used to update an Adjustment record. This component invokes the ATC1Adjustment Inbound Web Service using the C1AdjustmentUpdate Business Service.
C1-AdjustmentStgControlAdd	Used to adding an Adjustment Staging Control record. This component invokes the ATC1AdjustmentStagingControl Inbound Web Service using the C1-AdjustmentStgControlAdd Business Service.
C1-AdjustmentStgControlDelete	Used to delete an Adjustment Staging Control record. This component invokes the ATC1AdjustmentStagingControl Inbound Web Service using the C1-AdjustmentStgControlDelete Business Service.
C1-AdjustmentStgControlRead	Used to read an Adjustment Staging Control record. This component invokes the ATC1AdjustmentStagingControl Inbound Web Service using the C1-AdjustmentStgControlRead Business Service.
C1-AdjustmentStgControlUpdate	Used to update an Adjustment Staging Control record. This component invokes the ATC1AdjustmentStagingControl Inbound Web Service using the C1-AdjustmentStgControlUpdate Business Service.

Component	Description
C1-AdjustmentUploadStgUpdate	Used to update an Adjustment Upload Staging record. This component invokes the ATC1AdjustmentUploadStaging Inbound Web Service using the C1AdjustmentRead Business Service.
C1-ApCheckRequestUpdate	Used to update an A/P Check Request record. This component invokes the ATC1APCheckRequest REST Web Service using the C1-UpdAPChkI Service Script.
C1-BillAdd	Used to add a Bill record. This component invokes the ATC1Bill Inbound Web Service using the C1BillAdd Business Service.
C1-BillDelete	Used to delete a Bill record This component invokes the ATC1Bill Inbound Web Service using the C1BillDelete Business Service.
C1-BillRead	Used to read a Bill record. This component invokes the ATC1Bill Inbound Web Service using the C1BillRead Business Service.
C1-BillUpdate	Used to update a Bill record. This component invokes the ATC1Bill Inbound Web Service using the C1BillUpdate Business Service.
C1-BillSegmentAdd	Used to add a Bill Segment record. This component invokes the ATC1BillSegment Inbound Web Service using the C1BillSegmentAdd Business Service.
C1-BillSegmentRead	Used to read a Bill Segment record. This component invokes the ATC1BillSegment Inbound Web Service using the C1BillSegmentRead Business Service.
C1-BillSegmentUpdate	Used to update a Bill Segment record. This component invokes the ATC1BillSegment Inbound Web Service using the C1BillSegmentUpdate Business Service.

Component	Description
C1-BillableChargeAdd	Used to add a Billable Charge record. This component invokes the ATC1BillableCharge Inbound Web Service using the C1BillableChargeAdd Business Service.
C1-BillableChargeRead	Used to read a Billable Charge record. This component invokes the ATC1BillableCharge Inbound Web Service using the C1BillableChargeRead Business Service.
C1-BillableChargeUpdate	Used to read a Billable Charge record. This component invokes the ATC1BillableCharge Inbound Web Service using the C1BillableChargeUpdate Business Service.
C1-CCBOneTimePaymentTaskAdd	Used to add a One Time Payment Task. This component invokes the ATC1CCBOneTimePaymentTask Inbound Web Service using the C1-OneTimePaymentTask Business Object.
C1-CCBOneTimePaymentTaskRead	Used to read a One Time Payment Task. This component invokes the ATC1CCBOneTimePaymentTask Inbound Web Service using the C1-OneTimePaymentTask Business Object.
C1-CCBOneTimePaymentTaskUpdate	Used to update a One Time Payment Task. This component invokes the ATC1CCBOneTimePaymentTask Inbound Web Service using the C1-OneTimePaymentTask Business Object.
C1-DepositControlAdd	Used to add a Deposit Control record. This component invokes the ATC1DepositControl Inbound Web Service using the C1DepositControlAdd Business Service.
C1-DepositControlAdd	Used to add a Deposit Control record. This component invokes the ATC1DepositControl Inbound Web Service using the C1DepositControlAdd Business Service.
C1-DepositControlRead	Used to read a Deposit Control. This component invokes the ATC1DepositControl Inbound Web Service using the C1DepositControlRead Business Service.

Component	Description
C1-DepositControlUpdate	Used to update a Deposit Control record. This component invokes the ATC1DepositControl Inbound Web Service using the C1DepositControlUpdate Business Service.
C1-FTRead	Used to read a Financial Transaction record. This component invokes the ATC1FT Inbound Web Service using the C1FTRead Business Service.
C1-FTUpdate	Used to update a Financial Transaction record. This component invokes the ATC1FinancialTransaction Inbound Web Service using the C1FTUpdate Business Service.
C1-MatchEventAdd	Used to add a Match Event record. This component invokes the ATC1MatchEvent Inbound Web Service using the C1MatchEventAdd Business Service.
C1-MatchEventDelete	Used to delete a Match Event record. This component invokes the ATC1MatchEvent Inbound Web Service using the C1MatchEventDelete Business Service.
C1-MatchEventRead	Used to read a Match Event record. This component invokes the ATC1MatchEvent Inbound Web Service using the C1MatchEventRead Business Service.
C1-MatchEventUpdate	Used to update a Match Event record. This component invokes the ATC1MatchEvent Inbound Web Service using the C1MatchEventUpdate Business Service.
C1-MultiCancelRebillRead	Used to read a Multi Cancel Rebill record. This component invokes the ATC1MultiCancelRebill Inbound Web Service using the C1MultiCancelRebillRead Business Service.
C1-MultiCancelRebillUpdate	Used to update a Multi Cancel Rebill record. This component invokes the ATC1MultiCancelRebill Inbound Web Service using the C1MultiCancelRebillUpdate Business Service.

Component	Description
C1-PaymentAdd	Used to add a Payment record. This component invokes the ATC1Payment Inbound Web Service using the C1PaymentAdd Business Service.
C1-PaymentDelete	Used to delete a Payment. This component invokes the ATC1Payment Inbound Web Service using the C1PaymentDelete Business Service.
C1-PaymentRead	Used to read a Payment. This component invokes the ATC1Payment Inbound Web Service using the C1PaymentRead Business Service.
C1-PaymentUpdate	Used to update a Payment record. This component invokes the ATC1Payment Inbound Web Service using the C1PaymentUpdate Business Service.
C1-PaymentEventAdd	Used to add a Payment Event record. This component invokes the ATC1PaymentEvent Inbound Web Service using the C1PaymentEventAdd Business Service.
C1-PaymentEventDelete	Used to delete a Payment Event record. This component invokes the ATC1PaymentEvent Inbound Web Service using the C1PaymentEventDelete Business Service.
C1-PaymentEventRead	Used to read a Payment Event record. This component invokes the ATC1PaymentEvent Inbound Web Service using the C1PaymentEventRead Business Service.
C1-PaymentEventUpdate	Used to update a Payment Event record. This component invokes the ATC1PaymentEvent Inbound Web Service using the C1PaymentEventUpdate Business Service.
C1-PaymentEventBORead	Use to read for Pay Event record. This component invokes the ATC1PayEventPhysicalBO Inbound Web Service using the C1-PayEventPhysicalBO Business Object.

Component	Description
C1-PaymentEventQuickAddAdd	Used to add a Payment Event Quick Add record. This component invokes the ATC1PaymentEventQuickAdd Inbound Web Service using the C1PaymentEventQuickAddAdd Business Service.
C1-PaymentQuickAddAdd	Used to add a Payment Quick Add record. This component invokes the ATC1PaymentEventQuickAdd Inbound Web Service using the C1PaymentQuickAddAdd Business Service.
C1-PAResultAdd	Used to add a PA Request. This component invokes the ATC1PAResult Inbound Web Service using the C1-PAResult Business Object.
C1-PAResultDelete	Used to delete a PA Request. This component invokes the ATC1PAResult Inbound Web Service using the C1-PAResult Business Object.
C1-PAResultRead	Used to read a PA Request. This component invokes the ATC1PAResult Inbound Web Service using the C1-PAResult Business Object.
C1-PAResultUpdate	Used to update a PA Request. This component invokes the ATC1PAResult Inbound Web Service using the C1-PAResult Business Object.
C1-OffCycleBillGeneratorRead	Used to read an Off Cycle Bill Generator. This component invokes the ATC1OffCycleBillGenerator Inbound Web Service using the C1OffCycleBillGenPhysical Business Object.
C1-OffCycleBillGeneratorUpdate	Used to update an Off Cycle Bill Generator record. This component invokes the ATC1OffCycleBillGenerator Inbound Web Service using the C1OffCycleBillGenPhysical Business Object.

Component	Description
C1-OffCycleBillGeneratorDelete	Used to delete an Off Cycle Bill Generator record. This component invokes the ATC1OffCycleBillGenerator Inbound Web Service using the C1OffCycleBillGenPhysical Business Object.
C1-StatementAdd	Used to add a Statement record. This component invokes the ATC1Statement Inbound Web Service using the C1StatementAdd Business Service.
C1-StatementDelete	Used to delete a Statement record. This component invokes the ATC1Statement Inbound Web Service using the C1StatementDelete Business Service.
C1-StatementRead	Used to read a Statement record. This component invokes the ATC1Statement Inbound Web Service using the C1StatementRead Business Service.
C1-StatementUpdate	Used to update a Statement record. This component invokes the ATC1Statement Inbound Web Service using the C1StatementUpdate Business Service.
C1-TenderControlAdd	Used to add a Tender Control record. This component invokes the ATC1TenderControl Inbound Web Service using the C1TenderControlAdd Business Service.
C1-TenderControlRead	Used to read a Tender Control record. This component invokes the ATC1TenderControl Inbound Web Service using the C1TenderControlRead Business Service.
C1-TenderCtrlSearchByAllUser	Used to search an open Tender Control record. This component invokes the ATC1TenderCtrlSearchByAllUser Inbound Web Service using the C1TenderCtrlSearchByAllUser Business Service.
C1-TenderControlUpdate	Used to update a Tender Control record. This component invokes the ATC1TenderControl Inbound Web Service using the C1TenderControlUpdate Business Service.

Component	Description
C1-OffCycleBillGeneratorAdd	Used to add an Off Cycle Bill Generator record. This component invokes the ATC1OffCycleBillGenerator Inbound Web Service using the C1OffCycleBillGenPhysical Business Object.
C1-BillCorrectionAdd	Used to add a Bill Correction record. This component invokes the ATC1BillCorrection Inbound Web Service using the C1BillCorrectionAdd Business Object.
C1-BillCorrectionDelete	Used to delete a Bill Correction record. This component invokes the ATC1BillCorrection Inbound Web Service using the C1BillCorrectionDelete Business Object.
C1-BillCorrectionRead	Used to read a Bill Correction record. This component invokes the ATC1BillCorrection Inbound Web Service using the C1BillCorrectionRead Business Object.
C1-BillCorrectionUpdate	Used to update a Bill Correction record. This component invokes the ATC1BillCorrection Inbound Web Service using the C1BillCorrectionUpdate Business Object.

General

Component	Description
C1-AccountSearchByNameAddress	Used for Account Search by Name or Address and it will have the ability to retrieve a record. This component invokes the ATC1AccountSearchByNameAddress Inbound Web Service using the C1-NameAddressSearch Business Service.
C1-CtrlCenSearchByAccountId	Used for Control Central Search by Account ID. This component invokes the ATC1CtrlCenSearchByAccountId Inbound Web Service using the C1-CtrlCenSearchByAcctId Business Service.

Component	Description
C1-CtrlCenSearchByNameAddress	Used for Control Central Search by name and address. This component invokes the ATC1CtrlCenSearchByNameAddress Inbound Web Service using the C1-CtrlCenSearchByNameAddress Business Service.
C1-CtrlCentralSearchByAddress	Used for Control Central Search by address. This component invokes the ATC1CtrlCenSearchByAddress Inbound Web Service using the C1-CtrlCenSearchByAddress Business Service.
C1-GetPersonCustomerContact	Used for retrieving Person's Customer Contact. This component invokes the ATC1GetPersonCustContact Inbound Web Service using the C1-GETPERCC Business Service.
C1-GetNotificationType	Used to retrieve Notification Type in Notification Master Configuration > Edge Application Notification. This component invokes the ATC1GetNotificationType Inbound Web Service using the C1-GETNTFTYP Business Service.
C1-GetOutboundMsgType	Used for Retrieving Outbound Message Type in Notification Preference Master Configuration > Edge Application Notification. This component invokes the ATC1GetNotificationType Inbound Web Service using the C1RetOutMsg Service Script.
C1-NotificationPreferencesForAccounts Post	Used for Retrieving Active Notification Preferences for Account. This component invokes the C1-NotificationPreferencesForAccounts REST Inbound Web Service using the C1AccNtfPref Service Script.
C1-RetrieveActiveSA	Used for retrieving Service Agreements on Account. This component invokes the ATC1RetrieveActiveSa Inbound Web Service using the C1-RetrieveActiveSa Business Service.

Component	Description
C1-ServicePointQuery	Used for Retrieving for existing Service Points. This component invokes the C1ServicePointQuery Inbound Web Service using the C1ServicePointQuery Business Service.

Interval Billing

Component	Description
C1-ContractOptEventAdd	Used to create a Contract Option Event record. This component invokes the ATC1ContractOptEvent Inbound Web Service using the C1-ContractOptEventAdd Business Service.
C1-ContractOptEventRead	Used to query an existing Contract Option Event record. This component invokes the ATC1ContractOptEvent Inbound Web Service using the C1-ContractOptEventRead Business Service.
C1-ContractOptEventUpdate	Used to update an existing Contract Option Event record. This component invokes the ATC1ContractOptEvent Inbound Web Service using the C1-ContractOptEventUpdate Business Service.
C1-ContractOptEventDelete	Used to delete an existing Contract Option Event record. This component invokes the ATC1ContractOptEvent Inbound Web Service using the C1-ContractOptEventDelete Business Service.

Letter Template

Component	Description
C1-AcctBalLetterExtractAdd	Used to add an Account Balance Letter Extract record. This component invokes the ATC1AcctBalLetterExtract Inbound Web Service using the C1-AcctBalLetterExtractRecord Business Object.

Component	Description
C1-AcctBalLetterExtractRead	Used to read an Account Balance Letter Extract record. This component invokes the ATC1AcctBalLetterExtract Inbound Web Service using the C1-AcctBalLetterExtractRecord Business Object.
C1-AcctBalLetterExtractDel	Used to delete an Account Balance Letter Extract record. This component invokes the ATC1AcctBalLetterExtract Inbound Web Service using the C1-AcctBalLetterExtractRecord Business Object.
C1-AcctBalLetterExtractUpd	Used to update an Account Balance Letter Extract record. This component invokes the ATC1AcctBalLetterExtract Inbound Web Service using the C1-AcctBalLetterExtractRecord Business Object.
C1-AccountLetterExtractAdd	Used to add an Account Letter Extract record. This component invokes the ATC1AccountLetterExtract Inbound Web Service using the C1-AccountLetterExtractRecord Business Object.
C1-AccountLetterExtractRead	Used to read an Account Letter Extract record. This component invokes the ATC1AccountLetterExtract Inbound Web Service using the C1-AccountLetterExtractRecord Business Object.
C1-AccountLetterExtractDel	Used to delete an Account Letter Extract record. This component invokes the ATC1AccountLetterExtract Inbound Web Service using the C1-AccountLetterExtractRecord Business Object.
C1-AdjLetterExtractAdd	Used to add an Adjustment Letter Extract record. This component invokes the ATC1AdjLetterExtract Inbound Web Service using the C1-AdjLetterExtractRecord Business Object.
C1-AdjLetterExtractRead	Used to read an Adjustment Letter Extract record. This component invokes the ATC1AdjLetterExtract Inbound Web Service using the C1-AdjLetterExtractRecord Business Object.

Component	Description
C1-AdjLetterExtractUpdate	Used to update an Adjustment Letter Extract record. This component invokes the ATC1AdjLetterExtract Inbound Web Service using the C1-AdjLetterExtractRecord Business Object.
C1-AdjLetterExtractDelete	Used to delete an Adjustment Letter Extract record. This component invokes the ATC1AdjLetterExtract Inbound Web Service using the C1-AdjLetterExtractRecord Business Object.
C1-AutoPayLetterExtractAdd	Used to add an Auto Pay Letter Extract record. This component invokes the ATC1AutoPayLetterExtract Inbound Web Service using the C1-AutoPayLetterExtractRecord Business Object.
C1-AutoPayLetterExtractRead	Used to read an Auto Pay Letter Extract record. This component invokes the ATC1AutoPayLetterExtract Inbound Web Service using the C1-AutoPayLetterExtractRecord Business Object.
C1-AutoPayLetterExtractUpd	Used to update an Auto Pay Letter Extract record. This component invokes the ATC1AutoPayLetterExtract Inbound Web Service using the C1-AutoPayLetterExtractRecord Business Object.
C1-AutoPayLetterExtractDel	Used to delete an Auto Pay Letter Extract record. This component invokes the ATC1AutoPayLetterExtract Inbound Web Service using the C1-AutoPayLetterExtractRecord Business Object.
C1-BillLetterExtractAdd	Used to add a Bill Letter Extract record. This component invokes the ATC1BillLetterExtract Inbound Web Service using the C1-BillLetterExtractRecord Business Object.
C1-BillLetterExtractRead	Used to read a Bill Letter Extract record. This component invokes the ATC1BillLetterExtract Inbound Web Service using the C1-BillLetterExtractRecord Business Object.

Component	Description
C1-BillLetterExtractUpdate	Used to update a Bill Letter Extract record. This component invokes the ATC1BillLetterExtract Inbound Web Service using the C1-BillLetterExtractRecord Business Object.
C1-BillLetterExtractDelete	Used to delete a Bill Letter Extract record. This component invokes the ATC1BillLetterExtract Inbound Web Service using the C1-BillLetterExtractRecord Business Object.
C1-CollLetterExtractAdd	Used to add a Collection Letter Extract record. This component invokes the ATC1CollLetterExtract Inbound Web Service using the C1-CollLetterExtractRecord Business Object.
C1-CollLetterExtractRead	Used to read a Collection Letter Extract record. This component invokes the ATC1CollLetterExtract Inbound Web Service using the C1-CollLetterExtractRecord Business Object.
C1-CollLetterExtractUpdate	Used to update a Collection Letter Extract record. This component invokes the ATC1CollLetterExtract Inbound Web Service using the C1-CollLetterExtractRecord Business Object.
C1-CollLetterExtractDelete	Used to delete a Collection Letter Extract record. This component invokes the ATC1CollLetterExtract Inbound Web Service using the C1-CollLetterExtractRecord Business Object.
C1-CustConLetterExtractAdd	Used to add a Customer Contact Letter Extract record. This component invokes the ATC1CustConLetterExtract Inbound Web Service using the C1-CustConLetterExtractRecord Business Object.
C1-CustConLetterExtractRead	Used to read a Customer Contact Letter Extract record. This component invokes the ATC1CustConLetterExtract Inbound Web Service using the C1-CustConLetterExtractRecord Business Object.

Component	Description
C1-CustConLetterExtractUpd	Used to update a Customer Contact Letter Extract record. This component invokes the ATC1CustConLetterExtract Inbound Web Service using the C1-CustConLetterExtractRecord Business Object.
C1-CustConLetterExtractDel	Used to delete a Customer Contact Letter Extract record. This component invokes the ATC1CustConLetterExtract Inbound Web Service using the C1-CustConLetterExtractRecord Business Object.
C1-EndOfLetterExtractAdd	Used to add an End of Letter Extract record. This component invokes the ATC1EndOfLetterExtract Inbound Web Service using the C1-EndOfLetterExtractRecord Business Object.
C1-EndOfLetterExtractRead	Used to read an End of Letter Extract record. This component invokes the ATC1EndOfLetterExtract Inbound Web Service using the C1-EndOfLetterExtractRecord Business Object.
C1-EndOfLetterExtractUpd	Used to update an End of Letter Extract record. This component invokes the ATC1EndOfLetterExtract Inbound Web Service using the C1-EndOfLetterExtractRecord Business Object.
C1-EndOfLetterExtractDel	Used to delete an End of Letter Extract record. This component invokes the ATC1EndOfLetterExtract Inbound Web Service using the C1-EndOfLetterExtractRecord Business Object.
C1-LetterTemplateAdd	Used to add a Letter Template Extract record. This component invokes the ATC1LetterTemplate Inbound Web Service using the C1-LetterTemplate Business Object.
C1-LetterTemplateRead	Used to read a Letter Template Extract record. This component invokes the ATC1LetterTemplate Inbound Web Service using the C1-LetterTemplate Business Object.

Component	Description
C1-LetterTemplateUpdate	Used to update a Letter Template Extract record. This component invokes the ATC1LetterTemplate Inbound Web Service using the C1-LetterTemplate Business Object.
C1-LetterTemplateDelete	Used to delete a Letter Template Extract record. This component invokes the ATC1LetterTemplate Inbound Web Service using the C1-LetterTemplate Business Object.
C1-MailInfoLetterExtractAdd	Used to add a Mailing Information Letter Extract record. This component invokes the ATC1MailInfoLetterExtractInbound Web Service using the C1-MailInfoLetterExtractRecord Business Object.
C1-MailInfoLetterExtractRead	Used to read a Mailing Information Letter Extract record. This component invokes the ATC1MailInfoLetterExtractInbound Web Service using the C1-MailInfoLetterExtractRecord Business Object.
C1-MailInfoLetterExtractUpd	Used to update a Mailing Information Letter Extract record. This component invokes the ATC1MailInfoLetterExtractInbound Web Service using the C1-MailInfoLetterExtractRecord Business Object.
C1-MailInfoLetterExtractDel	Used to delete a Mailing Information Letter Extract record. This component invokes the ATC1MailInfoLetterExtractInbound Web Service using the C1-MailInfoLetterExtractRecord Business Object.
C1-PaymentLetterExtractAdd	Used to add a Payment Letter Extract record. This component invokes the ATC1PaymentLetterExtractInbound Web Service using the C1-PaymentLetterExtractRecord Business Object.

Component	Description
C1-PaymentLetterExtractRead	Used to read a Payment Letter Extract record. This component invokes the ATC1PaymentLetterExtractInbound Web Service using the C1-PaymentLetterExtractRecord Business Object.
C1-PaymentLetterExtractUpd	Used to update a Payment Letter Extract record. This component invokes the ATC1PaymentLetterExtractInbound Web Service using the C1-PaymentLetterExtractRecord Business Object.
C1-PaymentLetterExtractDel	Used to delete a Payment Letter Extract record. This component invokes the ATC1PaymentLetterExtractInbound Web Service using the C1-PaymentLetterExtractRecord Business Object.
C1-PayTndrLetterExtractAdd	Used to add a Payment Tender Letter Extract record. This component invokes the ATC1PayTndrLetterExtract Inbound Web Service using the C1-PayTndrLetterExtractRecord Business Object.
C1-PayTndrLetterExtractRead	Used to read a Payment Tender Letter Extract record. This component invokes the ATC1PayTndrLetterExtract Inbound Web Service using the C1-PayTndrLetterExtractRecord Business Object.
C1-PayTndrLetterExtractUpd	Used to update a Payment Tender Letter Extract record. This component invokes the ATC1PayTndrLetterExtract Inbound Web Service using the C1-PayTndrLetterExtractRecord Business Object.
C1-PayTndrLetterExtractDel	Used to delete a Payment Tender Letter Extract record. This component invokes the ATC1PayTndrLetterExtract Inbound Web Service using the C1-PayTndrLetterExtractRecord Business Object.

Component	Description
C1-PersonLetterExtractAdd	Used to add a Person Letter Extract record. This component invokes the ATC1PersonLetterExtract Inbound Web Service using the C1-PersonLetterExtractRecord Business Object.
C1-PersonLetterExtractRead	Used to read a Person Letter Extract record. This component invokes the ATC1PersonLetterExtract Inbound Web Service using the C1-PersonLetterExtractRecord Business Object.
C1-PersonLetterExtractUpd	Used to update a Person Letter Extract record. This component invokes the ATC1PersonLetterExtract Inbound Web Service using the C1-PersonLetterExtractRecord Business Object.
C1-PersonLetterExtractDel	Used to Delete a Person Letter Extract record. This component invokes the ATC1PersonLetterExtract Inbound Web Service using the C1-PersonLetterExtractRecord Business Object.
C1-PremiseLetterExtractAdd	Used to add a Premise Letter Extract record. This component invokes the ATC1PremiseLetterExtract Inbound Web Service using the C1-PremiseLetterExtractRecord Business Object.
C1-PremiseLetterExtractRead	Used to read a Premise Letter Extract record. This component invokes the ATC1PremiseLetterExtract Inbound Web Service using the C1-PremiseLetterExtractRecord Business Object.
C1-PremiseLetterExtractUpd	Used to update a Premise Letter Extract record. This component invokes the ATC1PremiseLetterExtract Inbound Web Service using the C1-PremiseLetterExtractRecord Business Object.
C1-PremiseLetterExtractDel	Used to Delete a Premise Letter Extract record. This component invokes the ATC1PremiseLetterExtract Inbound Web Service using the C1-PremiseLetterExtractRecord Business Object.

Component	Description
C1-SevLetterExtractAdd	Used to add a Severance Letter Extract record. This component invokes the ATC1SevLetterExtract Inbound Web Service using the C1-SevLetterExtractRecord Business Object.
C1-SevLetterExtractRead	Used to read a Severance Letter Extract record. This component invokes the ATC1SevLetterExtract Inbound Web Service using the C1-SevLetterExtractRecord Business Object.
C1-SevLetterExtractUpd	Used to update a Severance Letter Extract record. This component invokes the ATC1SevLetterExtract Inbound Web Service using the C1-SevLetterExtractRecord Business Object.
C1-SevLetterExtractDel	Used to Delete a Severance Letter Extract record. This component invokes the ATC1SevLetterExtract Inbound Web Service using the C1-SevLetterExtractRecord Business Object.
C1-SummaryLetterExtractAdd	Used to add a Summary Letter Extract record. This component invokes the ATC1SummaryLetterExtract Inbound Web Service using the C1-SummaryLetterExtractRecord Business Object.
C1-SummaryLetterExtractRead	Used to read a Summary Letter Extract record. This component invokes the ATC1SummaryLetterExtract Inbound Web Service using the C1-SummaryLetterExtractRecord Business Object.
C1-SummaryLetterExtractUpd	Used to update a Summary Letter Extract record. This component invokes the ATC1SummaryLetterExtract Inbound Web Service using the C1-SummaryLetterExtractRecord Business Object.
C1-SummaryLetterExtractDel	Used to Delete a Summary Letter Extract record. This component invokes the ATC1SummaryLetterExtract Inbound Web Service using the C1-SummaryLetterExtractRecord Business Object.

Component	Description
C1-WriteOffLetterExtractAdd	Used to add a Write Off Letter Extract record. This component invokes the ATC1WriteOffLetterExtract Inbound Web Service using the C1-WriteOffLetterExtractRecord Business Object.
C1-WriteOffLetterExtractRead	Used to read a Write Off Letter Extract record. This component invokes the ATC1WriteOffLetterExtract Inbound Web Service using the C1-WriteOffLetterExtractRecord Business Object.
C1-WriteOffLetterExtractUpd	Used to update a Write Off Letter Extract record. This component invokes the ATC1WriteOffLetterExtract Inbound Web Service using the C1-WriteOffLetterExtractRecord Business Object.
C1-WriteOffLetterExtractDel	Used to delete a Write Off Letter Extract record. This component invokes the ATC1WriteOffLetterExtract Inbound Web Service using the C1-WriteOffLetterExtractRecord Business Object.

Meter

Component	Description
C1-DeviceTestAdd	Used to add a Device Test record. This component invokes the ATC1DeviceTest Inbound Web Service using the C1DeviceTestPhysical Business Object.
C1-DeviceTestRead	Used to read a Device Test record. This component invokes the ATC1DeviceTest Inbound Web Service using the C1DeviceTestPhysical Business Object.
C1-DeviceTestUpdate	Used to update a Device Test record. This component invokes the ATC1DeviceTest Inbound Web Service using the C1DeviceTestPhysical Business Object.

Component	Description
C1-DeviceTestSelectionAdd	Used to add a Device Test record. This component invokes the ATC1DeviceTestSelection Inbound Web Service using the C1DeviceTestSelectionPhysical Business Object.
C1-DeviceTestSelectionRead	Used to read a Device Test Selection record. This component invokes the ATC1DeviceTestSelection Inbound Web Service using the C1DeviceTestSelectionPhysical Business Object.
C1-DeviceTestSelectionUpdate	Used to update a Device Test record. This component invokes the ATC1DeviceTestSelection Inbound Web Service using the C1DeviceTestSelectionPhysical Business Object.
C1-ItemAdd	Used to add an Item record. This component invokes the ATC1ItemPhysical Inbound Web Service using the C1ItemPhysical Business Object.
C1-ItemDelete	Used to delete an Item record. This component invokes the ATC1ItemPhysical Inbound Web Service using the C1ItemPhysical Business Object.
C1-ItemRead	Used to read an Item record. This component invokes the ATC1ItemPhysical Inbound Web Service using the C1ItemPhysical Business Object.
C1-ItemUpdate	Used to update an Item record. This component invokes the ATC1ItemPhysical Inbound Web Service using the C1ItemPhysical Business Object.
C1-ItemReplicatorUpdate	Used to update an Item Replicator record. This component invokes the ATC1ItemReplicator Inbound Web Service using the C1ItemReplicatorUpdate Business Service.
C1-MeterAdd	Used to add a Meter record. This component invokes the ATC1Meter Inbound Web Service using the C1MeterPhysical Business Object.

Component	Description
C1-MeterDelete	Used to delete a Meter record. This component invokes the ATC1Meter Inbound Web Service using the C1MeterPhysical Business Object.
C1-MeterRead	Used to read a Meter record. This component invokes the ATC1Meter Inbound Web Service using the C1MeterPhysical Business Object.
C1-MeterUpdate	Used to update a Meter record. This component invokes the ATC1Meter Inbound Web Service using the C1MeterPhysical Business Object.
C1-MeterConfigurationAdd	Used to add a Meter Configuration record. This component invokes the ATC1MeterConfiguration Inbound Web Service using the C1MeterConfigurationPhysical Business Object.
C1-MeterConfigurationDelete	Used to delete a Meter Configuration record. This component invokes the ATC1MeterConfiguration Inbound Web Service using the C1MeterConfigurationPhysical Business Object.
C1-MeterConfigurationRead	Used to read a Meter Configuration record. This component invokes the ATC1MeterConfiguration Inbound Web Service using the C1MeterConfigurationPhysical Business Object.
C1-MeterConfigurationUpdate	Used to update a Meter Configuration record. This component invokes the ATC1MeterConfiguration Inbound Web Service using the C1MeterConfigurationPhysical Business Object.
C1-MeterReplicatorUpdate	Used to update a Meter Replicator record. This component invokes the ATC1MeterReplicator Inbound Web Service using the C1MeterReplicatorUpdate Business Service.
C1-ItemInstallationAdd	Used to add an Item Installation record. This component invokes the ATC1ItemInstallation Inbound Web Service using the C1ItemInstallationAdd Business Service.

Component	Description
C1-ItemInstallationRead	Used to read an Item Installation record. This component invokes the ATC1ItemInstallation Inbound Web Service using the C1ItemInstallationRead Business Service.
C1-ItemInstallationUpdate	Used to update an Item Installation record. This component invokes the ATC1ItemInstallation Inbound Web Service using the C1ItemInstallationUpdate Business Service.
C1-SpMeterInstallationAdd	Used to add a Meter Installation record. This component invokes the ATC1SPMeterInstallation Inbound Web Service using the C1SpMeterInstallAdd Business Service.
C1-SpMeterInstallationRead	Used to read a Meter Installation record. This component invokes the ATC1SPMeterInstallation Inbound Web Service using the C1SpMeterInstallRead Business Service.
C1-SpMeterInstallationUpdate	Used to update a Meter Installation record. This component invokes the ATC1SPMeterInstallation Inbound Web Service using the C1SpMeterInstallUpdate Business Service.
C1-StockLocationAdd	Used to add a Stock Location record. This component invokes the ATC1StockLocation Inbound Web Service using the C1-StockLocationPhysicalBO Business Object.
C1-StockLocationDelete	Used to delete a Stock Location record. This component invokes the ATC1StockLocation Inbound Web Service using the C1-StockLocationPhysicalBO Business Object.
C1-StockLocationRead	Used to read a Stock Location record. This component invokes the ATC1StockLocation Inbound Web Service using the C1-StockLocationPhysicalBO Business Object.
C1-StockLocationUpdate	Used to update a Stock Location record. This component invokes the ATC1StockLocation Inbound Web Service using the C1-StockLocationPhysicalBO Business Object.

Component	Description
C1-StockLocationInventoryRead	Used to read a Stock Location Inventory record. This component invokes the ATC1StockLocInventory Inbound Web Service using the C1StockLocInventoryRead Business Service.
C1-StockLocationInventoryUpdate	Used to update a Stock Location Inventory record. This component invokes the ATC1StockLocInventory Inbound Web Service using the C1StockLocInventoryUpdate Business Service.

Meter Read

Component	Description
C1-ServiceRouteTransferRead	Used to read a Service Route Transfer record. This component invokes the ATC1ServiceRouteTransfer Inbound Web Service using the C1ServiceRteTransRead Business Service.
C1-ServiceRouteTransferUpdate	Used to update a Service Route Transfer record. This component invokes the ATC1ServiceRouteTransfer Inbound Web Service using the C1ServiceRteTransUpdate Business Service.
C1-MRUploadStagingAdd	Used to add a Meter Read Upload Staging record. This component invokes the ATC1MRUploadStaging Inbound Web Service using the C1MRUploadStagingAdd Business Service.
C1-MRUploadStagingDelete	Used to delete a Meter Read Upload Staging record. This component invokes the ATC1MRUploadStaging Inbound Web Service using the C1MRUploadStagingDelete Business Service.
C1-MRUploadStagingRead	Used to read a Meter Read Staging record. This component invokes the ATC1MRUploadStaging Inbound Web Service using the C1MRUploadStagingRead Business Service.

Component	Description
C1-MRUploadStagingUpdate	Used to update a Meter Read Upload Staging record. This component invokes the ATC1MRUploadStaging Inbound Web Service using the C1MRUploadStagingUpdate Business Service.
C1-MeterReadAdd	Used to add a Meter Read record. This component invokes the ATC1MeterRead Inbound Web Service using the C1MeterReadPhysical Business Object.
C1-MeterReadDelete	Used to delete a Meter Read record. This component invokes the ATC1MeterRead Inbound Web Service using the C1MeterReadPhysical Business Object.
C1-MeterReadRead	Used to read a Meter Read record. This component invokes the ATC1MeterRead Inbound Web Service using the C1MeterReadPhysical Business Object.
C1-MeterReadUpdate	Used to update a Meter Read record. This component invokes the ATC1MeterUpdate Inbound Web Service using the C1MeterReadPhysical Business Object.
C1-RenumberServiceRouteSeqRead	Used to read a Renumber Service Route Sequence record. This component invokes the ATC1RenumberMRRouteSequence Inbound Web Service using the C1RenumberMRSeqRead Business Service.
C1-RenumberServiceRouteSeqUpd	Used to update a Renumber Service Route Sequence record. This component invokes the ATC1RenumberMRRouteSequence Inbound Web Service using the C1RenumberMRSeqUpdate Business Service.
C1-TrendAdd	Used to add a trend record. This component invokes the ATC1Trend Inbound Web Service using the C1TrendAdd Business Service.

Component	Description
C1-TrendRead	Used to read a trend record. This component invokes the ATC1Trend Inbound Web Service using the C1TrendRead Business Service.
C1-TrendUpdate	Used to update a trend record. This component invokes the ATC1Trend Inbound Web Service using the C1TrendUpdate Business Service.

Rate Schedule

Component	Description
C1-ApplyToAdd	Used to add a calculation using Apply To Calculation rule. This component invokes the ATC1ApplyTo Inbound Web Service using the C1-ApplyTo Business Object.
C1-ApplyToRead	Used to read a calculation using Apply To Calculation rule. This component invokes the ATC1ApplyTo Inbound Web Service using the C1-ApplyTo Business Object.
C1-ApplyToUpdate	Used to update a calculation using Apply To Calculation rule. This component invokes the ATC1ApplyTo Inbound Web Service using the C1-ApplyTo Business Object.
C1-ApplyToDelete	Used to delete a Bill Factor TOU Value. This component invokes the ATC1BillFactorTOUValue Inbound Web Service using the C1-BillFactorTOUValAdd Business Object.
C1-ApplyCCLChargesAdd	Used to add calculation using Calculate Climate Change Levy and Relief Charges Calculation Rule. This component invokes the ATC1ApplyCCLCharges Inbound Web Service using the C1-ApplyCCLCharges Business Object.

Component	Description
C1-ApplyCCLChargesRead	Used to read calculation using Calculate Climate Change Levy and Relief Charges Calculation Rule. This component invokes the ATC1ApplyCCLCharges Inbound Web Service using the C1-ApplyCCLCharges Business Object.
C1-ApplyCCLChargesUpdate	Used to update calculation using Calculate Climate Change Levy and Relief Charges Calculation Rule. This component invokes the ATC1ApplyCCLCharges Inbound Web Service using the C1-ApplyCCLCharges Business Object.
C1-ApplyCCLChargesDelete	Used to delete calculation using Calculate Climate Change Levy and Relief Charges Calculation Rule. This component invokes the ATC1ApplyCCLCharges Inbound Web Service using the C1-ApplyCCLCharges Business Object.
C1-ApplyVatToCrossRefChargeAdd	Used to add a calculation using Apply VAT to Cross Referenced Charges calculation rule. This component invokes the ATC1ApplyTo Inbound Web Service using the C1-ApplyVatToCrossRefCharge Business Object.
C1-ApplyVatToCrossRefChargeDelete	Used to delete a calculation using Apply To Calculation rule. This component invokes the ATC1ApplyVatToCrossRefCharge Inbound Web Service using the C1-ApplyVatToCrossRefCharge Business Object.
C1-ApplyVatToCrossRefChargeUpdate	Used to update a calculation using Apply To Calculation rule. This component invokes the ATC1ApplyVatToCrossRefCharge Inbound Web Service using the C1-ApplyVatToCrossRefCharge Business Object.
C1-ApplyVatToCrossRefChargeRead	Used to read a calculation using Apply To Calculation Rule. This component invokes the ATC1ApplyVatToCrossRefCharge Inbound Web Service using the C1-ApplyVatToCrossRefCharge Business Object.

Component	Description
C1-BillFactorAdd	Used to add a Bill Factor. This component invokes the ATC1BillFactor Inbound Web Service using the C1-BillFactorPhysicalBO Business Object.
C1-BillFactorRead	Used to read a Bill Factor. This component invokes the ATC1BillFactor Inbound Web Service using the C1-BillFactorPhysicalBO Business Object.
C1-BillFactorUpdate	Used to update a Bill Factor. This component invokes the ATC1BillFactor Inbound Web Service using the C1-BillFactorPhysicalBO Business Object.
C1-BillFactorDelete	Used to delete a Bill Factor. This component invokes the ATC1BillFactor Inbound Web Service using the C1-BillFactorPhysicalBO Business Object.
C1-BillFactorValueAdd	Used to add a Bill Factor Value. This component invokes the ATC1BillFactorValue Inbound Web Service using the C1-BillFactorValuePhysicalBO Business Object.
C1-BillFactorValueRead	Used to read a Bill Factor Value. This component invokes the ATC1BillFactorValue Inbound Web Service using the C1-BillFactorValuePhysicalBO Business Object.
C1-BillFactorValueUpdate	Used to update a Bill Factor Value. This component invokes the ATC1BillFactorValue Inbound Web Service using the C1-BillFactorValuePhysicalBO Business Object.
C1-BillFactorValueDelete	Used to delete a Bill Factor Value. This component invokes the ATC1BillFactorValue Inbound Web Service using the C1-BillFactorValuePhysicalBO Business Object.
C1-BillFactorTOUValAdd	Used to add a Bill Factor TOU Value. This component invokes the ATC1BillFactorTOUValue Inbound Web Service using the C1-BillFactorTOUValAdd Business Object.

Component	Description
C1-BillFactorTOUValRead	Used to read a Bill Factor TOU Value. This component invokes the ATC1BillFactorTOUValue Inbound Web Service using the C1-BillFactorTOUValAdd Business Object.
C1-BillFactorTOUValUpdate	Used to update a Bill Factor TOU Value. This component invokes the ATC1BillFactorTOUValue Inbound Web Service using the C1-BillFactorTOUValAdd Business Object.
C1-BillFactorTOUValDelete	Used to delete a Bill Factor TOU Value. This component invokes the ATC1BillFactorTOUValue Inbound Web Service using the C1-BillFactorTOUValAdd Business Object.
C1-BillFactorIntervalValueAdd	Used to add a Bill Factor Interval Value. This component invokes the ATC1IntervaValueSet Inbound Web Service using the C1-IntervalValueSetPhysicalBO Business Object.
C1-BillFactorIntervalValueDelete	Used to delete a Bill Factor Interval Value. This component invokes the ATC1IntervaValueSet Inbound Web Service using the C1-IntervalValueSetPhysicalBO Business Object.
C1-BillFactorIntervalValueRead	Used to read a Bill Factor Interval Value. This component invokes the ATC1IntervaValueSet Inbound Web Service using the C1-IntervalValueSetPhysicalBO Business Object.
C1-BillFactorIntervalValueUpdate	Used to update a Bill Factor Interval Value. This component invokes the ATC1IntervaValueSet Inbound Web Service using the C1-IntervalValueSetPhysicalBO Business Object.
C1-CalculateServiceQuantityAdd	Used to add Calculate Service Quantity record. This component invokes the ATC1CalculateServiceQuantity Inbound Web Service using the C1-CalculateServiceQuantity Business Object.

Component	Description
C1-CalculateServiceQuantityDelete	Used to delete a Calculate Service Quantity record. This component invokes the ATC1CalculateServiceQuantity Inbound Web Service using the C1-CalculateServiceQuantity Business Object.
C1-CalculateServiceQuantityUpdate	Used to update a Calculate Service Quantity record. This component invokes the ATC1CalculateServiceQuantity Inbound Web Service using the C1-CalculateServiceQuantity Business Object.
C1-CalculateServiceQuantityRead	Used to read a Calculate Service Quantity record. This component invokes the ATC1CalculateServiceQuantity Inbound Web Service using the C1-CalculateServiceQuantity Business Object.
C1-CalculationGroupAdd	Used to add a Calculation Group. This component invokes the ATC1CalculationGroup Inbound Web Service using the C1-CalcGroupPhysicalBO Physical Business Object.
C1-CalculationGroupDelete	Used to delete a Calculation Group. This component invokes the ATC1CalculationGroup Inbound Web Service using the C1-CalcGroupPhysicalBO Physical Business Object.
C1-CalculationGroupRead	Used to read a Calculation Group. This component invokes the ATC1CalculationGroup Inbound Web Service using the C1-CalcGroupPhysicalBO Physical Business Object.
C1-CalculationGroupUpdate	Used to update a Calculation Group. This component invokes the ATC1CalculationGroup Inbound Web Service using the C1-CalcGroupPhysicalBO Physical Business Object.
C1-CalcLineCategoryAdd	Used to add a Calculation Line Category Type. This component invokes the ATC1CalcLineCat Inbound Web Service using the C1-CalcLineCatPhysicalBO Physical Business Object.

Component	Description
C1-CalcLineCategoryDelete	Used to delete a Calculation Line Category Type. This component invokes the ATC1CalcLineCat Inbound Web Service using the C1-CalcLineCatPhysicalBO Physical Business Object.
C1-CalcLineCategoryUpdate	Used to update a Calculation Line Category Type. This component invokes the ATC1CalcLineCat Inbound Web Service using the C1-CalcLineCatPhysicalBO Physical Business Object.
C1-CalcLineCategoryRead	Used to read a Calculation Line Category Type. This component invokes the ATC1CalcLineCat Inbound Web Service using the C1-CalcLineCatPhysicalBO Physical Business Object.
C1-CalcRuleEligibilityCriteriaAdd	Used to add a Calculation Rule Eligibility Criteria. This component invokes the ATC1CalcRuleElCrt Inbound Web Service using the C1-CalcRuleElCrtPhysicalBO Physical Business Object.
C1-CalcRuleEligibilityCriteriaDelete	Used to delete a Calculation Rule Eligibility Criteria. This component invokes the ATC1CalcRuleElCrt Inbound Web Service using the C1-CalcRuleElCrtPhysicalBO Physical Business Object.
C1-CalcRuleEligibilityCriteriaUpdate	Used to delete a Calculation Rule Eligibility Criteria. This component invokes the ATC1CalcRuleElCrt Inbound Web Service using the C1-CalcRuleElCrtPhysicalBO Physical Business Object.
C1-CalcRuleEligibilityCriteriaRead	Used to read a Calculation Rule Eligibility Criteria. This component invokes the ATC1CalcRuleElCrt Inbound Web Service using the C1-CalcRuleElCrtPhysicalBO Physical Business Object.
C1-CalcRuleReferredCalcGroupAdd	Used to add a Calculation Rule Eligibility Criteria. This component invokes the ATC1CalcRuleReferredCalcGroup Inbound Web Service using the C1-CalcRuleElCrtPhysicalBO Physical Business Object.
C1-CalcRuleReferredCalcGroupDelete	Used to delete a Calculation Rule Eligibility Criteria. This component invokes the ATC1CalcRuleReferredCalcGroup Inbound Web Service using the C1-CalcRuleElCrtPhysicalBO Physical Business Object.

Component	Description
C1- CalcRuleReferredCalcGroupUpdate	Used to update a Calculation Rule Eligibility Criteria. This component invokes the ATC1CalcRuleReferredCalcGroup Inbound Web Service using the C1-CalcRuleElCrtPhysicalBO Physical Business Object.
C1-CalcRuleReferredCalcGroupRead	Used to update a Calculation Rule Eligibility Criteria. This component invokes the ATC1CalcRuleReferredCalcGroup Inbound Web Service using the C1-CalcRuleElCrtPhysicalBO Physical Business Object.
C1-CalculateFinalValueAdd	Used to add a calculation using Calculate final reading values Calculation Rule. This component invokes the ATC1CalculateFinalValue Inbound Web Service using the C1-CalculateFinalValue Business Object.
C1-CalculateFinalValueDelete	Used to delete a calculation using Calculate final reading values Calculation Rule. This component invokes the ATC1CalculateFinalValue Inbound Web Service using the C1-CalculateFinalValue Business Object.
C1-CalculateFinalValueUpdate	Used to delete a calculation using Calculate final reading values Calculation Rule. This component invokes the ATC1CalculateFinalValue Inbound Web Service using the C1-CalculateFinalValue Business Object.
C1-CalculateFinalValueDelete	Used to delete a calculation using Calculate final reading values Calculation Rule. This component invokes the ATC1CalculateFinalValue Inbound Web Service using the C1-CalculateFinalValue Business Object.
C1-CalcMiscellaneousChargeAdd	Used to add a calculation using Miscellaneous Charges Calculation Rule. This component invokes the ATC1CalculateMiscellaneousCharg Inbound Web Service using the C1-CalculateMiscellaneousCharg Business Object.

Component	Description
C1-CalcMiscellaneousChargeDelete	Used to delete a calculation using Miscellaneous Charges Calculation Rule. This component invokes the ATC1CalculateMiscellaneousCharg Inbound Web Service using the C1-CalculateMiscellaneousCharg Business Object.
C1-CalcMiscellaneousChargeUpdate	Used to delete a calculation using Miscellaneous Charges Calculation Rule. This component invokes the ATC1CalculateMiscellaneousCharg Inbound Web Service using the C1-CalculateMiscellaneousCharg Business Object.
C1-CalcMiscellaneousChargeRead	Used to read a calculation using Miscellaneous Charges Calculation Rule. This component invokes the ATC1CalculateMiscellaneousCharg Inbound Web Service using the C1-CalculateMiscellaneousCharg Business Object.
C1-CopySQFromMasterBillSegmentAdd	Used to read a calculation using Miscellaneous Charges Calculation Rule. This component invokes the ATC1CopySQFromMasterBillSegment Inbound Web Service using the C1-CopySQFromMasterBillSegment Business Object.
C1-CopySQFromMasterBillSegment Delete	Used to delete a calculation using Miscellaneous Charges Calculation Rule. This component invokes the ATC1CopySQFromMasterBillSegment Inbound Web Service using the C1-CopySQFromMasterBillSegment Business Object.
C1-CopySQFromMasterBillSegment Update	Used to update a calculation using Miscellaneous Charges Calculation Rule. This component invokes the ATC1CopySQFromMasterBillSegment Inbound Web Service using the C1-CopySQFromMasterBillSegment Business Object.
C1-CopySQFromMasterBillSegment Read	Used to read a calculation using Miscellaneous Charges Calculation Rule. This component invokes the ATC1CopySQFromMasterBillSegment Inbound Web Service using the C1-CopySQFromMasterBillSegment Business Object.

Component	Description
C1-CopySQFromMasterBillSegmentAdd	Used to read a calculation using Miscellaneous Charges Calculation Rule. This component invokes the ATC1CopySQFromMasterBillSegment Inbound Web Service using the C1-CopySQFromMasterBillSegment Business Object.
C1-CopySQFromMasterBillSegment Delete	Used to delete a calculation using Miscellaneous Charges Calculation Rule. This component invokes the ATC1CopySQFromMasterBillSegment Inbound Web Service using the C1-CopySQFromMasterBillSegment Business Object.
C1-CopySQFromMasterBillSegment Update	Used to update a calculation using Miscellaneous Charges Calculation Rule. This component invokes the ATC1CopySQFromMasterBillSegment Inbound Web Service using the C1-CopySQFromMasterBillSegment Business Object.
C1-CopySQFromMasterBillSegment Read	Used to read a calculation using Miscellaneous Charges Calculation Rule. This component invokes the ATC1CopySQFromMasterBillSegment Inbound Web Service using the C1-CopySQFromMasterBillSegment Business Object.
C1-DetermineDemandValueToPrice Add	Used to add a calculation using Determine Demand Value To Price Calculation Rule. This component invokes the ATC1DetermineDemandValueToPrice Inbound Web Service using the C1-DetermineDemandValueToPrice Business Object.
C1-DetermineDemandValueToPrice Delete	Used to delete a calculation using Determine Demand Value To Price Calculation Rule. This component invokes the ATC1DetermineDemandValueToPrice Inbound Web Service using the C1-DetermineDemandValueToPrice Business Object.
C1-DetermineDemandValueToPrice Update	Used to update a calculation using Determine Demand Value To Price Calculation Rule. This component invokes the ATC1DetermineDemandValueToPrice Inbound Web Service using the C1-DetermineDemandValueToPrice Business Object.

Component	Description
C1-DetermineDemandValueToPriceRead	Used to read a calculation using Determine Demand Value To Price Calculation Rule. This component invokes the ATC1DetermineDemandValueToPrice Inbound Web Service using the C1-DetermineDemandValueToPrice Business Object.
C1-FlatChargeAdd	Used to add a calculation using Flat Charge calculation rule. This component invokes the ATC1FlatCharge Inbound Web Service using the C1-FlatCharge Business Object.
C1-FlatChargeDelete	Used to delete a calculation using Flat Charge calculation rule. This component invokes the ATC1FlatCharge Inbound Web Service using the C1-FlatCharge Business Object.
C1-FlatChargeUpdate	Used to delete a calculation using Flat Charge calculation rule. This component invokes the ATC1FlatCharge Inbound Web Service using the C1-FlatCharge Business Object.
C1-FlatChargeRead	Used to delete a calculation using Flat Charge calculation rule. This component invokes the ATC1FlatCharge Inbound Web Service using the C1-FlatCharge Business Object.
C1-GetSubUsageRequestSQAdd	Used to add a calculation using Get Sub-Usage Request SQ Calculation Rule. This component invokes the ATC1GetSubUsageRequestSQ Inbound Web Service using the C1-GetSubUsageRequestSQ Business Object.
C1-GetSubUsageRequestSQDelete	Used to delete a calculation using Get Sub-Usage Request SQ Calculation Rule. This component invokes the ATC1GetSubUsageRequestSQ Inbound Web Service using the C1-GetSubUsageRequestSQ Business Object.

Component	Description
C1-GetSubUsageRequestSQUpdate	Used to update a calculation using Get Sub-Usage Request SQ Calculation Rule. This component invokes the ATC1GetSubUsageRequestSQ Inbound Web Service using the C1-GetSubUsageRequestSQ Business Object.
C1-GetSubUsageRequestSQRead	Used to read a calculation using Get Sub-Usage Request SQ Calculation Rule. This component invokes the ATC1GetSubUsageRequestSQ Inbound Web Service using the C1-GetSubUsageRequestSQ Business Object.
C1-ItemTypeChargeAdd	Used to read a calculation using Item Type Charge Calculation rule. This component invokes the ATC1ItemTypeCharge Inbound Web Service using the C1-ItemType Business Object.
C1-ItemTypeChargeDelete	Used to delete a calculation using Item Type Charge Calculation rule. This component invokes the ATC1ItemTypeCharge Inbound Web Service using the C1-ItemType Business Object.
C1-ItemTypeChargeUpdate	Used to update a calculation using Item Type Charge Calculation rule. This component invokes the ATC1ItemTypeCharge Inbound Web Service using the C1-ItemType Business Object.
C1-ItemTypeChargeRead	Used to read a calculation using Item Type Charge Calculation rule. This component invokes the ATC1ItemTypeCharge Inbound Web Service using the C1-ItemType Business Object.
C1-MathAdd	Used to add a calculation using Math Calculation rule. This component invokes the ATC1Math Inbound Web Service using the C1-Math Business Object.
C1-MathDelete	Used to delete a calculation using Math Calculation rule. This component invokes the ATC1Math Inbound Web Service using the C1-Math Business Object.

Component	Description
C1-MathUpdate	Used to update a calculation using Math Calculation rule. This component invokes the ATC1Math Inbound Web Service using the C1-Math Business Object.
C1-MathRead	Used to read a calculation using Math Calculation rule. This component invokes the ATC1Math Inbound Web Service using the C1-Math Business Object.
C1-MaximumAdd	Used to read a calculation using maximum Calculation rule. This component invokes the ATC1Maximum Inbound Web Service using the C1-Maximum Business Object.
C1-MaximumDelete	Used to read a calculation using maximum Calculation rule. This component invokes the ATC1Maximum Inbound Web Service using the C1-Maximum Business Object.
C1-MaximumUpdate	Used to update a calculation using maximum Calculation rule. This component invokes the ATC1Maximum Inbound Web Service using the C1-Maximum Business Object.
C1-MaximumUpdate	Used to delete a calculation using Maximum Calculation rule. This component invokes the ATC1Maximum Inbound Web Service using the C1-Maximum Business Object.
C1-MinimumAdd	Used to add a calculation using Minimum Calculation rule. This component invokes the ATC1Minimum Inbound Web Service using the C1-Minimum Business Object.
C1-MinimumDelete	Used to delete a calculation using Minimum Calculation rule. This component invokes the ATC1Minimum Inbound Web Service using the C1-Minimum Business Object.

Component	Description
C1-MinimumUpdate	Used to update a calculation using Minimum Calculation rule. This component invokes the ATC1Minimum Inbound Web Service using the C1-Minimum Business Object.
C1-MinimumRead	Used to read a calculation using Minimum Calculation rule. This component invokes the ATC1Minimum Inbound Web Service using the C1-Minimum Business Object.
C1-RateCheck	Used for Rate Checking. This component invokes the ATC1RateCheck Inbound Web Service using the C1-RateApplication Business Service.
C1-RateComponentAdd	Used to add a Rate Component record. This component invokes the ATC1RateComponent Inbound Web Service using the C1-RateComponentPhysicalBO Physical Business Object.
C1-RateComponentDelete	Used to delete a Rate Component record. This component invokes the ATC1RateComponent Inbound Web Service using the C1-RateComponentPhysicalBO Physical Business Object.
C1-RateComponentRead	Used to read a Rate Component record. This component invokes the ATC1RateComponent Inbound Web Service using the C1-RateComponentPhysicalBO Physical Business Object.
C1-RateComponentUpdate	Used to update a Rate Component record. This component invokes the ATC1RateComponent Inbound Web Service using the C1-RateComponentPhysicalBO Physical Business Object.
C1-RateScheduleV1Add	Used to add a Rate Schedule V1 record. This component invokes the ATC1RateScheduleV1 Inbound Web Service using the C1-RateSchedulePhysicalBO Physical Business Object.

Component	Description
C1-RateScheduleV1Delete	Used to delete a Rate Schedule V1 record. This component invokes the ATC1RateScheduleV1 Inbound Web Service using the C1-RateSchedulePhysicalBO Physical Business Object.
C1-RateScheduleV1Read	Used to read a Rate Schedule V1 record. This component invokes the ATC1RateScheduleV1 Inbound Web Service using the C1-RateSchedulePhysicalBO Physical Business Object.
C1-RateScheduleV1Update	Used to update a Rate Schedule V1 record. This component invokes the ATC1RateScheduleV1 Inbound Web Service using the C1-RateSchedulePhysicalBO Physical Business Object.
C1-RateScheduleV2Add	Used to add a Rate Schedule V1 record. This component invokes the ATC1RateScheduleV2 Inbound Web Service using the C1-RateScheduleV2 Business Object.
C1-RateScheduleV2Read	Used to read a Rate Schedule V1 record. This component invokes the ATC1RateScheduleV2 Inbound Web Service using the C1-RateScheduleV2 Business Object.
C1-RateScheduleV2Read	Used to read a Rate Schedule V1 record. This component invokes the ATC1RateScheduleV2 Inbound Web Service using the C1-RateScheduleV2 Business Object.
C1-RateScheduleV2Update	Used to update a Rate Schedule V1 record. This component invokes the ATC1RateScheduleV2 Inbound Web Service using the C1-RateScheduleV2 Business Object.
C1-RateVersionAdd	Used to add a Rate Version record. This component invokes the ATC1RateVersion Inbound Web Service using the C1-RateVersionPhysicalBO Physical Business Object.
C1-RateVersionDelete	Used to delete a Rate Version record. This component invokes the ATC1RateVersion Inbound Web Service using the C1-RateVersionPhysicalBO Physical Business Object.

Component	Description
C1-RateVersionRead	Used to read a Rate Version record. This component invokes the ATC1RateVersion Inbound Web Service using the C1-RateVersionPhysicalBO Physical Business Object.
C1-RateVersionUpdate	Used to update a Rate Version record. This component invokes the ATC1RateVersion Inbound Web Service using the C1-RateVersionPhysicalBO Physical Business Object.
C1-ServiceQuantityAdd	Used to add a Service Quantity charge record. This component invokes the ATC1ServiceQuantity Inbound Web Service using the Business Object.
C1-ServiceQuantityDelete	Used to delete a Service Quantity charge record. This component invokes the ATC1ServiceQuantity Inbound Web Service using the Business Object.
C1-ServiceQuantityRead	Used to read a Service Quantity charge record. This component invokes the ATC1ServiceQuantity Inbound Web Service using the Business Object.
C1-ServiceQuantityUpdate	Used to update a Service Quantity charge record. This component invokes the ATC1ServiceQuantity Inbound Web Service using the Business Object.
C1-SimpleSummaryAdd	Used to add a Simple Summary charge record. This component invokes the ATC1SimpleSummary Inbound Web Service using the Business Object.
C1-SimpleSummaryDelete	Used to delete a Simple Summary charge record. This component invokes the ATC1SimpleSummary Inbound Web Service using the Business Object.
C1-SimpleSummaryRead	Used to read a Simple Summary charge record. This component invokes the ATC1SimpleSummary Inbound Web Service using the Business Object.
C1-SimpleSummaryUpdate	Used to update a Simple Summary charge record. This component invokes the ATC1SimpleSummary Inbound Web Service using the Business Object.
C1-SteppedSQAdd	Used to add a Stepped SQ charge record. This component invokes the ATC1SteppedSQ Inbound Web Service using the Business Object.

Component	Description
C1-SteppedSQDelete	Used to add read a Stepped SQ charge record. This component invokes the ATC1SteppedSQ Inbound Web Service using the Business Object.
C1-SteppedSQRead	Used to read a Stepped SQ charge record. This component invokes the ATC1SteppedSQ Inbound Web Service using the Business Object.
C1-SteppedSQUpdate	Used to update a Stepped SQ charge record. This component invokes the ATC1SteppedSQ Inbound Web Service using the Business Object.
C1-SummaryAdd	Used to add a Summary charge record. This component invokes the ATC1Summary Inbound Web Service using the Business Object.
C1-SummaryDelete	Used to delete a Summary charge record. This component invokes the ATC1Summary Inbound Web Service using the Business Object.
C1-SummaryRead	Used to read a Summary charge record. This component invokes the ATC1Summary Inbound Web Service using the Physical Business Object.
C1-SummaryUpdate	Used to update a Summary charge record. This component invokes the ATC1Summary Inbound Web Service using the Business Object.

Sales and Marketing

Component	Description
C1-CampaignAdd	Used to add a Campaign record. This component invokes the ATC1Campaign Inbound Web Service using the C1-CampaignAdd Business Service.
C1-CampaignRead	Used to read a Campaign record. This component invokes the ATC1Campaign Inbound Web Service using the C1-CampaignRead Business Service.

Component	Description
C1-CampaignUpdate	Used to update a Campaign record. This component invokes the ATC1Campaign Inbound Web Service using the C1-CampaignUpdate Business Service.
C1-CampaignDelete	Used to delete a Campaign record. This component invokes the ATC1Campaign Inbound Web Service using the C1-CampaignDelete Business Service.
C1-LeadAccountAdd	Used to add a Lead Account record. This component invokes the ATC1LeadAccount Inbound Web Service using the C1-LeadAccount Business Object.
C1-LeadAccountRead	Used to read a Lead Account record. This component invokes the ATC1LeadAccount Inbound Web Service using the C1-LeadAccount Business Object.
C1-LeadAccountUpdate	Used to update a Lead Account record. This component invokes the ATC1LeadAccount Inbound Web Service using the C1-LeadAccount Business Object.
C1-LeadAccountDelete	Used to delete a Lead Account record. This component invokes the ATC1LeadAccount Inbound Web Service using the C1-LeadAccount Business Object.
C1-PackageAdd	Used to add a Package record. This component invokes the ATC1PackageBS Inbound Web Service using the C1-PackageAdd Business Service.
C1-PackageRead	Used to read a Package record. This component invokes the ATC1Package Inbound Web Service using the C1-PackagePhysical Business Object.
C1-PackageUpdate	Used to update a Package record. This component invokes the ATC1PackageBS Inbound Web Service using the C1-PackagePhysical Business Service.

Component	Description
C1-PackageDelete	Used to delete a Package record. This component invokes the ATC1Package Inbound Web Service using the C1-PackagePhysical Business Object.
C1-ThirdPartyRepAdd	Used to add a Third Party Representative record. This component invokes the ATC1ThirdPartyRep Inbound Web Service using the C1-ThirdPartyRepresentative Business Object.
C1-ThirdPartyRepRead	Used to read a Third Party Representative record. This component invokes the ATC1ThirdPartyRep Inbound Web Service using the C1-ThirdPartyRepresentative Business Object.
C1-ThirdPartyRepUpdate	Used to update a Third Party Representative record. This component invokes the ATC1ThirdPartyRep Inbound Web Service using the C1-ThirdPartyRepresentative Business Object.
C1-ThirdPartyRepDelete	Used to delete a Third Party Representative record. This component invokes the ATC1ThirdPartyRep Inbound Web Service using the C1-ThirdPartyRepresentative Business Object.
C1-SalesRepIndividualAdd	Used to add an Individual Sales Representative record. This component invokes the ATC1SalesRepIndividual Inbound Web Service using the C1-SRpInPost Service Script.
C1-SalesRepIndividualRead	Used to read an Individual Sales Representative record. This component invokes the ATC1SalesRepIndividualRead Inbound Web Service using the C1-SRInd Service Script.
C1-SalesRepIndividualUpdate	Used to update an Individual Sales Representative record. This component invokes the ATC1SalesRepIndividual Inbound Web Service using the C1-SRpInPost Service Script.
C1-SalesRepIndividualDelete	Used to delete an Individual Sales Representative record. This component invokes the ATC1SalesRepIndividual Inbound Web Service using the C1-SRpInPost Service Script.

Component	Description
C1-SalesRepGroupAdd	Used to add a Group Sales Representative record. This component invokes the ATC1SalesRepGroup Inbound Web Service using the C1-SalesRepGroup Business Object.
C1-SalesRepGroupRead	Used to read a Group Sales Representative record. This component invokes the ATC1SalesRepGroup Inbound Web Service using the C1-SalesRepGroup Business Object.
C1-SalesRepGroupUpdate	Used to update an Individual Sales Representative record. This component invokes the ATC1SalesRepGroup Inbound Web Service using the C1-SalesRepGroup Business Object.
C1-SalesRepGroupDelete	Used to delete an Individual Sales Representative record. This component invokes the ATC1SalesRepIndividual Inbound Web Service using the C1-SalesRepGroup Business Object.
C1-SalesRepLogsRead	Used to read a Sales Representative Log record. This component invokes the ATC1SalesRepLogs Inbound Web Service using the C1-SalesRepLogs Business Object.
C1-SalesRepLogsAdd	Used to add a Sales Representative Log record. This component invokes the ATC1SalesRepLogs Inbound Web Service using the C1-SalesRepLogs Business Object.
C1-CampaignInitiativeAdd	Used to add a Campaign Initiative record. This component invokes the ATC1CampaignInitiative Inbound Web Service using the C1-InitiativeService Business Object.
C1-CampaignInitiativeRead	Used to read a Campaign Initiative record. This component invokes the ATC1CampaignInitiative Inbound Web Service using the C1-InitiativeService Business Object.
C1-CampaignInitiativeUpdate	Used to update a Campaign Initiative record. This component invokes the ATC1CampaignInitiative Inbound Web Service using the C1-InitiativeService Business Object.

Component	Description
C1-CampaignInitiativeDelete	Used to delete a Campaign Initiative record. This component invokes the ATC1CampaignInitiative Inbound Web Service using the C1-InitiativeService Business Object.
C1-ContractOptInitiativeAdd	Used to add a Contract Option Initiative record. This component invokes the ATC1ContractOptInitiative Inbound Web Service using the C1-InitiativeService Business Object.
C1-ContractOptInitiativeRead	Used to read a Contract Option Initiative record. This component invokes the ATC1ContractOptInitiative Inbound Web Service using the C1-InitiativeService Business Object.
C1-ContractOptInitiativeUpdate	Used to update a Contract Option Initiative record. This component invokes the ATC1ContractOptInitiative Inbound Web Service using the C1-InitiativeService Business Object.
C1-ContractOptInitiativeDelete	Used to delete a Contract Option Initiative record. This component invokes the ATC1ContractOptInitiative Inbound Web Service using the C1-InitiativeService Business Object.
C1-ConservationInitiativeAdd	Used to add a Conservation Initiative record. This component invokes the ATC1ConservationInitiative Inbound Web Service using the C1-InitiativeConservationProg Business Object.
C1-ConservationInitiativeRead	Used to read a Conservation Initiative record. This component invokes the ATC1ConservationInitiative Inbound Web Service using the C1-InitiativeConservationProg Business Object.
C1-ConservationInitiativeUpd	Used to update a Conservation Initiative record. This component invokes the ATC1ConservationInitiative Inbound Web Service using the C1-InitiativeConservationProg Business Object.
C1-ConservationInitiativeDel	Used to delete a Conservation Initiative record. This component invokes the ATC1ConservationInitiative Inbound Web Service using the C1-InitiativeConservationProg Business Object.

Component	Description
C1-InitiativeLogsRead	Used to read an Initiative Log record. This component invokes the ATC1InitiativeLogs Inbound Web Service using the C1-InitiativeLogs Business Object.
C1-InitiativeLogsAdd	Used to add an Initiative Log record. This component invokes the ATC1InitiativeLogs Inbound Web Service using the C1-InitiativeLogs Business Object.
C1-MyLeads	Used to get the representative link to the user. This component also retrieves all group representatives linked to the representative. This component invokes the ATC1MyLead Inbound Web Service using the C1-MyLead Service Script.
C1-LeadQuery	Used to get the lead details depending on the search group used, by filling up the correct schema group. This component invokes the ATC1LeadQuery Inbound Web Service using the C1-LeadQuery Business Service.
C1-InitiativeQuery	Used to get the initiative details based on the C1-INTVQ1 zone. This component invokes the ATC1InitiativeQuery Inbound Web Service using the C1-InitiativeQuery Business Service.
C1-LeadAdd	Used to create a Lead record. This component invokes the ATC1Lead Inbound Web Service using the C1LeadPhysical Business Object.
C1-LeadRead	Used to read an existing Lead record. This component invokes the ATC1Lead Inbound Web Service using the C1LeadPhysical Business Object.
C1-LeadUpdate	Used to update an existing Lead record. This component invokes the ATC1Lead Inbound Web Service using the C1LeadPhysical Business Object.
C1-LeadDelete	Used to delete an existing Lead record. This component invokes the ATC1Lead Inbound Web Service using the C1LeadPhysical Business Object.

Component	Description
C1-LeadEventAdd	Used to create a Lead Event record. This component invokes the ATC1LeadEvent Inbound Web Service using the C1LeadEventPhysical Business Object.
C1-LeadEventRead	Used to read an existing Lead Event record. This component invokes the ATC1LeadEvent Inbound Web Service using the C1LeadEventPhysical Business Object.
C1-LeadEventUpdate	Used to update an existing Lead Event record. This component invokes the ATC1LeadEvent Inbound Web Service using the C1LeadEventPhysical Business Object.
C1-OrderAdd	Used to create an Order record. This component invokes the ATC1Order Inbound Web Service using the C1OrderAdd Business Service.
C1-OrderRead	Used to read an existing Order record. This component invokes the ATC1Order Inbound Web Service using the C1OrderRead Business Service.
C1-OrderUpdate	Used to update an existing Order record. This component invokes the ATC1Order Inbound Web Service using the C1OrderUpdate Business Service.
C1-QuoteAdd	Used to create a Quote record. This component invokes the ATC1Quote Inbound Web Service using the C1QuoteAdd Business Service.
C1-QuoteRead	Used to read an existing Quote record. This component invokes the ATC1Quote Inbound Web Service using the C1QuoteRead Business Service.
C1-QuoteUpdate	Used to update an existing Quote record. This component invokes the ATC1Quote Inbound Web Service using the C1QuoteUpdate Business Service.

Component	Description
C1-QuoteDelete	Used to delete an existing Quote record. This component invokes the ATC1Quote Inbound Web Service using the C1QuoteDelete Business Service.

Service Order Management

Component	Description
C1-ActivityInformation	Used to read an Activity Information. This component invokes the ATC1ActivityInformation Inbound Web Service using the C1-ActvtyInf Service Script.
C1-DefaultUsage	Used to retrieve the Default Usage. This component invokes the ATC1DefaultUsage Inbound Web Service using the C1-DfltUsage Service Script.
C1-DeviceInformation	Used to retrieve the Device Information. This component invokes the ATC1DeviceInformation Inbound Web Service using the C1-DeviceInf Service Script.
C1-FACompletionMessage	Used for the FA Completion Message. This component invokes the ATC1FACompletionMessage Inbound Web Service using the C1-FACmplMsg Service Script.
C1-PremiseFAGTT	Used to insert the Premise Activities to GTT. This component invokes the ATC1PremFAGTT Inbound Web Service using the C1-PremFAGTT Service Script.
C1-ServiceRequestUpdate	Used to update a SOM Request. This component invokes the ATC1ServiceRequestUpdate Inbound Web Service using the C1-SvcReqUpd Service Script.

Usage

Component	Description
C1-GetUsageId	Used to get the usage request ID of given a person name. This component invokes the ATC1GetUsageId Inbound Web Service using the C1-GetUsageId Business Service.
C1-UsageReqCyclicalBillingRead	Used to read an Usage Request Cyclical Billing record. This component invokes the ATC1UsageReqCyclicalBillingRead Inbound Web Service using the C1-UsageRequestCyclicalBilling Business Object.
C1-UsageRequestNonCyclicalRead	Used to read an Usage Request Non-Cyclical Billing record. This component invokes the ATC1UsageRequestNonCyclical Inbound Web Service using the C1-UsageRequestNonCyclical Business Object.

Umbrella Agreement Management

Component	Description
C1-UmbrellaAgreementAdd	Used to create an Umbrella Agreement record. This component invokes the ATC1UmbrellaAgreement Inbound Web Service using the C1UmbrellaAgreementPhysical Business Object.
C1-UmbrellaAgreementRead	Used to read an existing Umbrella Agreement record. This component invokes the ATC1UmbrellaAgreement Inbound Web Service using the C1UmbrellaAgreementPhysical Business Object.
C1-UmbrellaAgreementUpdate	Used to update an existing Umbrella Agreement record. This component invokes the ATC1UmbrellaAgreement Inbound Web Service using the C1UmbrellaAgreementUpdate Business Service.

Component	Description
C1-UmbrellaAgreementDelete	Used to delete an existing Umbrella Agreement record. This component invokes the ATC1UmbrellaAgreement Inbound Web Service using the C1UmbrellaAgreementPhysical Business Object.
C1-TermsOfServiceAdd	Used to create a Terms of Service record. This component invokes the ATC1TermsOfService Inbound Web Service using the C1TermsOfServicePhysical Business Object.
C1-TermsOfServiceRead	Used to read an existing Terms of Service record. This component invokes the ATC1TermsOfService Inbound Web Service using the C1TermsOfServicePhysical Business Object.
C1-TermsOfServiceUpdate	Used to update an existing Terms of Service record. This component invokes the ATC1TermsOfService Inbound Web Service using the C1TermsOfServiceUpdate Business Service.
C1-TermsOfServiceDelete	Used to delete an existing Terms of Service record. This component invokes the ATC1TermsOfService Inbound Web Service using the C1TermsOfServicePhysical Business Object.

Master Configuration

Component	Description
C1-ThirdPartyPaymntIntegrationAdd	Used to add a Third Party Payment Integration. This component invokes the ATC1ThirdPartyPaymntIntegration Inbound Web Service using the C1-ThirdPartyPaymntIntegration Business Object.
C1-ThirdPartyPaymntIntegrationRead	Used to read a Third Party Payment Integration. This component invokes the ATC1ThirdPartyPaymntIntegration Inbound Web Service using the C1-ThirdPartyPaymntIntegration Business Object.

Component	Description
C1-ThirdPartyPaymntIntegrationUpdate	Used to update a Third Party Payment Integration. This component invokes the ATC1ThirdPartyPaymntIntegration Inbound Web Service using the C1-ThirdPartyPaymntIntegration Business Object.
C1-BillingExtractPlusConfigAdd	Used to add a Billing Extract Master Config for DataConnect v1+. This component invokes the ATC1BillingExtractPlusConfig Inbound Web Service using the C1-BillingExtractPlusConfig Business Object.
C1-BillingExtractPlusConfigRead	Used to read a Billing Extract Master Config for DataConnect v1+. This component invokes the ATC1BillingExtractPlusConfig Inbound Web Service using the C1-BillingExtractPlusConfig Business Object.
C1-BillingExtractPlusConfigUpdate	Used to update a Billing Extract Master Config for DataConnect v1+. This component invokes the ATC1BillingExtractPlusConfig Inbound Web Service using the C1-BillingExtractPlusConfig Business Object.
C1-C360ConfigurationAdd	This component can be used for adding a Billing and Usage Display Configuration record. This component invokes the Business Object “C1-C360Configuration” using the Inbound Web Service of ATC1C360Configuration.
C1-C360ConfigurationRead	This component can be used for reading a Billing and Usage Display Configuration record. This component invokes the Business Object “C1-C360Configuration” using the Inbound Web Service of ATC1C360Configuration.
C1-C360ConfigurationUpdate	This component can be used for reading a Billing and Usage Display Configuration record. This component invokes the Business Object “C1-C360Configuration” using the Inbound Web Service of ATC1C360Configuration.

Component	Description
C1-DisplayIconOverrideConfigAdd	This component can be used for adding a Display Icon Override Configuration record. This component invokes the Inbound Web Service “ATC1DisplayIconOverrideConfig” using the Business Object “C1-DisplayIconOverrideConfig”.
C1-DisplayIconOverrideConfigRead	This component can be used for reading a Display Icon Override Configuration record. This component invokes the Inbound Web Service “ATC1DisplayIconOverrideConfig” using the Business Object “C1-DisplayIconOverrideConfig”.
C1-DisplayIconOverrideConfigUpdate	This component can be used for updating a Display Icon Override Configuration record. This component invokes the Inbound Web Service “ATC1DisplayIconOverrideConfig” using the Business Object “C1-DisplayIconOverrideConfig”.
C1-MigrationAssistantConfigAdd	Used for adding a Migration Assistant Config record. This component invokes the ATC1MigrationAssistantConfig Inbound Web Service using the F1-MigrationAssistantConfig Business Object.
C1-MigrationAssistantConfigDelete	Used for deleting a Migration Assistant Config record. This component invokes the ATC1MigrationAssistantConfig Inbound Web Service using the F1-MigrationAssistantConfig Business Object.
C1-MigrationAssistantConfigRead	Used for reading a Migration Assistant Config record. This component invokes the ATC1MigrationAssistantConfig Inbound Web Service using the F1-MigrationAssistantConfig Business Object.
C1-MigrationAssistantConfigUpdate	Used for updating a Migration Assistant Config record. This component invokes the ATC1MigrationAssistantConfig Inbound Web Service using the F1-MigrationAssistantConfig Business Object.

Component	Description
C1-NMSMasterConfigAdd	This component can be used for adding a NMS Outage Integration Master Config record. This component invokes the ATC1NMSIntegrationMasterConfig Inbound Web Service using the C1-NMSMasterConfig Business Object.
C1-NMSMasterConfigRead	This component can be used for reading a NMS Outage Integration Master Config record. This component invokes the ATC1NMSIntegrationMasterConfig Inbound Web Service using the C1-NMSMasterConfig Business Object.
C1-NMSMasterConfigUpdate	This component can be used for updating a NMS Outage Integration Master Config record. This component invokes the ATC1NMSIntegrationMasterConfig Inbound Web Service using the C1-NMSMasterConfig Business Object.
C1-WAMMasterConfigAdd	This component can be used for adding a CCB WAM Integration record. This component invokes the Business Object “C1-WAMIntegrationMasterConfig” using the Inbound Web Service of ATC1WAMIntegrationMasterConfig.
C1-WAMMasterConfigRead	This component can be used for reading a CCB WAM Integration record. This component invokes the Business Object “C1-WAMIntegrationMasterConfig” using the Inbound Web Service of ATC1WAMIntegrationMasterConfig.
C1-WAMMasterConfigUpdate	This component can be used for updating a CCB WAM Integration record. This component invokes the Business Object “C1-WAMIntegrationMasterConfig” using the Inbound Web Service of ATC1WAMIntegrationMasterConfig.
C1-RateEngineConfigAdd	This component can be used for adding a Rate Engine Configuration Record. This component invokes the Business Object “C1-RateEngineConfig” using the Inbound Web Service of ATC1RateEngineConfig.

Component	Description
C1-RateEngineConfigRead	This component can be used for adding a Rate Engine Configuration Record. This component invokes the Business Object “C1-RateEngineConfig” using the Inbound Web Service of ATC1RateEngineConfig.
C1-RateEngineConfig	This component can be used for adding a Rate Engine Configuration Record. This component invokes the Business Object “C1-RateEngineConfig” using the Inbound Web Service of ATC1RateEngineConfig.

Self-Service

Component	Description
C1-OneTimePaymentTaskAdd	Used to add One Time Payment Service Task. This component invokes the WXMakePayment Inbound Web Service using the WX-OneTimePayTask Business Object.
C1-OneTimePaymentTaskRead	Used to read a One Time Payment Service Task. This component invokes the ATC1OneTimePaymentTask Inbound Web Service using the WX-OneTimePayTask Business Object.
C1-RetrieveServiceTask	Used to retrieve Service Task record. This component invokes the ATC1RetrieveServiceTask Inbound Web Service using the C1-RETSVCTSK Business Service.
C1-SSStartStopXferServiceTaskAdd	Used to add a Start Stop Transfer Service Task. This component invokes the ATC1SSStartStopXferServiceTask Inbound Web Service using the C1-SSStartStopXferServiceTask Business Object.
C1-SSStartStopXferServiceTaskDelete	Used to delete a Start Stop Transfer Service Task. This component invokes the ATC1SSStartStopXferServiceTask Inbound Web Service using the C1-SSStartStopXferServiceTask Business Object.

Component	Description
C1-SSStartStopXferServiceTaskRead	Used to read a Start Stop Transfer Service Task. This component invokes the ATC1SSStartStopXferServiceTask Inbound Web Service using the C1-SSStartStopXferServiceTask Business Object.
C1-SSStartStopXferServiceTaskUpdate	Used to update a Start Stop Transfer Service Task. This component invokes the ATC1SSStartStopXferServiceTask Inbound Web Service using the C1-SSStartStopXferServiceTask Business Object.
C1-SSAddServiceRequestTypeAdd	Used to add Self-Service Add Service Request Type. This component invokes the ATC1SSAddServiceRequestType Inbound Web Service using the C1-SSAddServiceRequestType Business Object.
C1-SSAddServiceRequestTypeDelete	Used to delete Self-Service Add Service Request Type. This component invokes the ATC1SSAddServiceRequestType Inbound Web Service using the C1-SSAddServiceRequestType Business Object.
C1-SSAddServiceRequestTypeRead	Used to read Self-Service Add Service Request Type. This component invokes the ATC1SSAddServiceRequestType Inbound Web Service using the C1-SSAddServiceRequestType Business Object.
C1-SSAddServiceRequestTypeUpdate	Used to update Self-Service Add Service Request Type. This component invokes the ATC1SSAddServiceRequestType Inbound Web Service using the C1-SSAddServiceRequestType Business Object.
C1-SSNewServiceRequestTypeAdd	Used to add Self-Service New Service Request Type. This component invokes the ATC1SSNewServiceRequestType Inbound Web Service using the C1-SSNewServiceRequestType Business Object.

Component	Description
C1-SSNewServiceRequestTypeDelete	Used to delete Self-Service New Service Request Type. This component invokes the ATC1SSNewServiceRequestType Inbound Web Service using the C1-SSNewServiceRequestType Business Object.
C1-SSNewServiceRequestTypeRead	Used to read Self-Service New Service Request Type. This component invokes the ATC1SSNewServiceRequestType Inbound Web Service using the C1-SSNewServiceRequestType Business Object.
C1-SSNewServiceRequestTypeUpdate	Used to update Self-Service New Service Request Type. This component invokes the ATC1SSNewServiceRequestType Inbound Web Service using the C1-SSNewServiceRequestType Business Object.
C1-SSStopServiceRequestTypeAdd	Used to add Self-Service Stop Service Request Type. This component invokes the ATC1SSStopServiceRequestType Inbound Web Service using the C1-SSStopServiceRequestType Business Object.
C1-SSStopServiceRequestTypeDelete	Used to delete Self-Service Stop Service Request Type. This component invokes the ATC1SSStopServiceRequestType Inbound Web Service using the C1-SSStopServiceRequestType Business Object.
C1-SSStopServiceRequestTypeRead	Used to read Self-Service Stop Service Request Type. This component invokes the ATC1SSStopServiceRequestType Inbound Web Service using the C1-SSStopServiceRequestType Business Object.
C1-SSStopServiceRequestTypeUpdate	Used to Update Self-Service Stop Service Request Type. This component invokes the ATC1SSStopServiceRequestType Inbound Web Service using the C1-SSStopServiceRequestType Business Object.

Component	Description
C1-SSTransferServiceReqTypeAdd	Used to add Self-Service Transfer Service Request Type. This component invokes the ATC1SSTransferServiceReqType Inbound Web Service using the C1-SSTransferServiceReqType Business Object.
C1-SSTransferServiceReqTypeDelete	Used to delete Self-Service Transfer Service Request Type. This component invokes the ATC1SSTransferServiceReqType Inbound Web Service using the C1-SSTransferServiceReqType Business Object.
C1-SSTransferServiceReqTypeRead	Used to read Self-Service Transfer Service Request Type. This component invokes the ATC1SSTransferServiceReqType Inbound Web Service using the C1-SSTransferServiceReqType Business Object.
C1-SSTransferServiceReqTypeUpdate	Used to update Self-Service Transfer Service Request Type. This component invokes the ATC1SSTransferServiceReqType Inbound Web Service using the C1-SSTransferServiceReqType Business Object.
C1-StartServiceRequestSAAdd	Used to add a Start Service Request SA record. This component invokes the ATC1StartServiceRequestSA Inbound Web Service using the C1-StartServiceRequestSA Business Object.
C1-StartServiceRequestSADelete	Used to delete a Start Service Request SA record. This component invokes the ATC1StartServiceRequestSA Inbound Web Service using the C1-StartServiceRequestSA Business Object.
C1-StartServiceRequestSARead	Used to read a Start Service Request SA record. This component invokes the ATC1StartServiceRequestSA Inbound Web Service using the C1-StartServiceRequestSA Business Object.

Component	Description
C1-StartServiceRequestSAUpdate	Used to update a Start Service Request SA record. This component invokes the ATC1StartServiceRequestSA Inbound Web Service using the C1-StartServiceRequestSA Business Object.
C1-StopServiceRequestSAAdd	Used to add a Stop Service Request SA record. This component invokes the ATC1StopServiceRequestSA Inbound Web Service using the C1-StopServiceRequestSA Business Object.
C1-StopServiceRequestSADelete	Used to delete a Stop Service Request SA record. This component invokes the ATC1StopServiceRequestSA Inbound Web Service using the C1-StopServiceRequestSA Business Object.
C1-StopServiceRequestSARead	Used to read a Stop Service Request SA record. This component invokes the ATC1StopServiceRequestSA Inbound Web Service using the C1-StopServiceRequestSA Business Object.
C1-StopServiceRequestSADelete	Used to delete a Stop Service Request SA record. This component invokes the ATC1StopServiceRequestSA Inbound Web Service using the C1-StopServiceRequestSA Business Object.
C1-ThirdPartyAcctVerificationTaskRead	Used to read a Third Party Account Verification Task. This component invokes the ATC1ThirdPartyAcctVerifTask Inbound Web Service using the C1-ThirdPartyAcctVerifTaskRead Business Object.
C1-ThirdPartyAutoPaySetupAdd	Used to add a Third Party Auto Pay Setup. This component invokes the ATC1ThirdPartyAutoPaySetup Inbound Web Service using the C1-TPApaySet Service Script.
C1-ThirdPartyAutoPaySetupCancel	Used to cancel a Third Party Auto Pay Setup. This component invokes the ATC1ThirdPartyAutoPaySetup Inbound Web Service using the C1-TPApaySet Service Script.

Component	Description
C1-ThirdPartyAutoPaySetupUpdate	Used to cancel a Third Party Auto Pay Setup. This component invokes the ATC1ThirdPartyAutoPaySetup Inbound Web Service using the C1-TPApaySet Service Script.
C1-ThirdPartyAutoPayTaskRead	Used to read a Third Party Auto Pay Task. This component invokes the ATC1ThirdPartyAutoPayTask Inbound Web Service using the C1-ThirdPartyAutoPayTask Business Object.
C1-ThirdPartyOneTimePayNotifAdd	Used to add a Third Party One Time Payment. This component invokes the ATC1ThirdPartyPaymntIntegration Inbound Web Service using the C1-TPPayNotf Service Script.
C1-ThirdPartyOneTimePayNotifCancel	Used to cancel a Third Party One Time Payment. This component invokes the ATC1ThirdPartyPaymntIntegration Inbound Web Service using the C1-TPPayNotf Service Script.
C1-ThirdPartyOneTimePayNotifProcess	Used to process a Third Party One Time Payment. This component invokes the ATC1ThirdPartyPaymntIntegration Inbound Web Service using the C1-TPPayNotf Service Script.
C1-ThirdPartyOneTimePayNotifUpdate	Used to update a Third Party One Time Payment. This component invokes the ATC1ThirdPartyPaymntIntegration Inbound Web Service using the C1-TPPayNotf Service Script.
C1-ThirdPartyOneTimePayTaskRead	Used to read a Third Party One Time Payment Task. This component invokes the ATC1ThirdPartyOneTimePayTask Inbound Web Service using the C1-ThirdPartyOneTimePayTask Business Object.
C1-ThirdPartyVerifyAccount	Used to verify a Third Party Account. This component invokes the ATC1ThirdPartyVerifyAccount Inbound Web Service using the C1-TPVerAcct Service Script.

Component	Description
C1-AutoPaySetupAdd	Used to add an Auto Pay Setup. This component invokes the WXAUTOpaySetup Inbound Web Service using the WX-ApaySet Service Script.
C1-AutoPaySetupUpdate	Used to update a Auto Pay Setup. This component invokes the WXAUTOpaySetup Inbound Web Service using the WX-ApaySet Service Script.
C1-AutoPayTaskRead	Used to read an Auto Pay Setup Service Task. This component invokes the ATC1AutoPayTask Inbound Web Service using the WX-AutoPayTask Business Object.
C1-OneTimePaymentTaskAdd	Used to add One Time Payment Service Task. This component invokes the WXMakePayment Inbound Web Service using the WX-OneTimePayTask Business Object.
C1-OneTimePaymentTaskRead	Used to read a One Time Payment Service Task. This component invokes the ATC1OneTimePaymentTask Inbound Web Service using the WX-OneTimePayTask Business Object.

Service Task Type

Component	Description
C1-CCBOneTimeTaskTypeAdd	Used for adding a One Time Task Type record. This component invokes the ATC1CCBOneTimePaymentTaskType Inbound Web Service using the C1-OneTimePaymentTaskType Business Object.
C1-CCBOneTimeTaskTypeDelete	Used for deleting a One Time Task Type record. This component invokes the ATC1CCBOneTimePaymentTaskType Inbound Web Service using the C1-OneTimePaymentTaskType Business Object.

Component	Description
C1-CCBOneTimeTaskTypeRead	Used for reading a One Time Task Type record. This component invokes the ATC1CCBOneTimePaymentTaskType Inbound Web Service using the C1-OneTimePaymentTaskType Business Object.
C1-CCBOneTimeTaskTypeUpdate	Used for updating a One Time Task Type record. This component invokes the ATC1CCBOneTimePaymentTaskType Inbound Web Service using the C1-OneTimePaymentTaskType Business Object.
C1-ThirdPartyAcctVerifTaskTypeAdd	Used to add a Third Party Account Verification Task Type. This component invokes the ATC1ThirdPartyAcctVerificationTaskType Inbound Web Service using the C1-ThirdPartyAcctVerifTaskType Business Object.
C1-ThirdPartyAcctVerifTaskTypeDelete	Used to delete a Third Party Account Verification Task Type. This component invokes the ATC1ThirdPartyAcctVerificationTaskType Inbound Web Service using the C1-ThirdPartyAcctVerifTaskType Business Object.
C1-ThirdPartyAcctVerifTaskTypeRead	Used to read a Third Party Account Verification Task Type. This component invokes the ATC1ThirdPartyAcctVerificationTaskType Inbound Web Service using the C1-ThirdPartyAcctVerifTaskType Business Object.
C1-ThirdPartyAcctVerifTaskTypeUpdate	Used to update a Third Party Account Verification Task Type. This component invokes the ATC1ThirdPartyAcctVerificationTaskType Inbound Web Service using the C1-ThirdPartyAcctVerifTaskType Business Object.
C1-ThirdPartyAutoPayTaskTypeAdd	Used to add a Third Party Auto Pay Task Type. This component invokes the ATC1ThirdPartyAutoPayTaskType Inbound Web Service using the C1-ThirdPartyAutoPayTaskType Business Object.

Component	Description
C1-ThirdPartyAutoPayTaskTypeDelete	Used to delete a Third Party Auto Pay Task Type. This component invokes the ATC1ThirdPartyAutoPayTaskType Inbound Web Service using the C1-ThirdPartyAutoPayTaskType Business Object.
C1-ThirdPartyAutoPayTaskTypeRead	Used to read a Third Party Auto Pay Task Type. This component invokes the ATC1ThirdPartyAutoPayTaskType Inbound Web Service using the C1-ThirdPartyAutoPayTaskType Business Object.
C1-ThirdPartyAutoPayTaskTypeUpdate	Used to update a Third Party Auto Pay Task Type. This component invokes the ATC1ThirdPartyAutoPayTaskType Inbound Web Service using the C1-ThirdPartyAutoPayTaskType Business Object.
C1-ThirdPartyOneTimePayTaskTypeAdd	Used to add a Third Party One Time Payment Task Type. This component invokes the ATC1ThirdPartyOneTimePyTaskType Inbound Web Service using the C1-ThirdPartyOneTimePyTaskType Business Object.
C1-ThirdPartyOneTimePayTaskTypeDelete	Used to delete a Third Party One Time Payment Task Type. This component invokes the ATC1ThirdPartyOneTimePyTaskType Inbound Web Service using the C1-ThirdPartyOneTimePyTaskType Business Object.
C1-ThirdPartyOneTimePayTaskTypeRead	Used to delete a Third Party One Time Payment Task Type. This component invokes the ATC1ThirdPartyOneTimePyTaskType Inbound Web Service using the C1-ThirdPartyOneTimePyTaskType Business Object.
C1-ThirdPartyOneTimePayTaskTypeUpdate	Used to update a Third Party One Time Payment Task Type. This component invokes the ATC1ThirdPartyOneTimePyTaskType Inbound Web Service using the C1-ThirdPartyOneTimePyTaskType Business Object.

Component	Description
C1-OutageCallTypeAdd	Used to add an Outage Call Type record. This component invokes the ATC1OutageCallType Inbound Web Service using the C1-OutageCallType Business Object.
C1-OutageCallTypeRead	Used to read an existing Outage Call Type record. This component invokes the ATC1OutageCallType Inbound Web Service using the C1-OutageCallType Business Object.
C1-OutageCallTypeUpdate	Used to update an existing Outage Call Type record. This component invokes the ATC1OutageCallType Inbound Web Service using the C1-OutageCallType Business Object.
C1-OutageCallTypeDelete	Used to delete an existing Outage Call Type record. This component invokes the ATC1OutageCallType Inbound Web Service using the C1-OutageCallType Business Object.
C1-SSStartStopXferServiceTaskTypeAdd	Used to add a Start Stop Transfer Service Task Type. This component invokes the ATC1SSStartStopXferSvcTaskType Inbound Web Service using the C1-SSStartStopXferSvcTaskType Business Object.
C1-SSStartStopXferServiceTaskType Delete	Used to delete a Start Stop Transfer Service Task Type. This component invokes the ATC1SSStartStopXferSvcTaskType Inbound Web Service using the C1-SSStartStopXferSvcTaskType Business Object.
C1-SSStartStopXferServiceTaskTypeRead	Used to read a Start Stop Transfer Service Task Type. This component invokes the ATC1SSStartStopXferSvcTaskType Inbound Web Service using the C1-SSStartStopXferSvcTaskType Business Object.
C1-SSStartStopXferServiceTaskType Update	Used to update Start Stop Transfer Service Task Type. This component invokes the ATC1SSStartStopXferSvcTaskType Inbound Web Service using the C1-SSStartStopXferSvcTaskType Business Object.

Contract and Products

Component	Description
C1-ConsumerContractAdd	Used to add a Consumer Contract. This component invokes the ATC1ConsumerContract Inbound Web Service using the C1-ConsumerContract Business Object.
C1-ConsumerContractDelete	Used to delete a Consumer Contract. This component invokes the ATC1ConsumerContract Inbound Web Service using the C1-ConsumerContract Business Object.
C1-ConsumerContractRead	Used to read a Consumer Contract. This component invokes the ATC1ConsumerContract Inbound Web Service using the C1-ConsumerContract Business Object.
C1-ConsumerContractUpdate	Used to update a Consumer Contract. This component invokes the ATC1ConsumerContract Inbound Web Service using the C1-ConsumerContract Business Object.
C1-GetCSRPerson	Used for retrieving the Person ID from Customer Service Request Person. This component invokes the ATC1GetCSRPerson Inbound Web Service using the C1-GETCSRPER Business Service.
C1-GetCSRAccount	Used for retrieving the Account ID from Customer Service Request Person. This component invokes the ATC1GetCSRAccount Inbound Web Service using the C1-GETCSRACC Business Service.
C1-GetCSRPremise	Used for retrieving the Premise ID from Customer Service Request Premise. This component invokes the ATC1GetCSRPremise Inbound Web Service using the C1-GETCSRPRE Business Service.
C1-GetCSRContract	Used for retrieving the Contract ID from Customer Service Request Contract. This component invokes the ATC1GetCSRContract Inbound Web Service using the C1-GETCSRCON Business Service.

Component	Description
C1-GetCSRContractProduct	Used for retrieving the Contract Product ID from Customer Service Request Contract. This component invokes the ATC1GetCSRProduct Inbound Web Service using the C1-GETCSRPRO Business Service.
C1-GetCSRServiceLocation	Used for Update Service Location. This component invokes the ATC1GetCSRServiceLocation Inbound Web Service using the C1-GETCSRSE Business Service.
C1-AddCSR	Used for adding a Customer Service Request record. This component invokes the ATC1CreateCSR Inbound Web Service using the C1-AddCoChRe Service Script.
C1-GetBOStatus	This business service receives a maintenance object code and primary key(s) and returns its business object along with its lifecycle business object and current status, if applicable. This component invokes the ATC1GetBOStatus Inbound Web Service using the F1-DetermineBo Business Service.
C1-GetEligibleProductContractType	Used for retrieving the list of Eligible Products for a Contract Type. This component invokes the ATC1GetEligibleProduct Inbound Web Service using the C1-RetElPdCT Business Service.
C1-GetProdAttributeContract	Used for retrieving the product attributes for a Contract. This component invokes the ATC1GetProdAttributeContract Inbound Web Service using the C1-RePrAttCt Service Script.
C1-GetProductAttributes	Used for retrieving the product attributes for Operand Values. This component invokes the ATC1ProdAttOperandValues Inbound Web Service using the C1-RetPAttOV Service Script.
C1-TransitionBOStatus	Used to transition Business Object status. This component invokes the ATC1TransitionBOStatus Inbound Web Service using the C1-TransitBO Service Script.

Component	Description
C1-CSRPersonAdd	Used for Customer Service Request Person Add. This component invokes the ATC1CSRPerson Inbound Web Service using the C1-ContractChangeReqPersnBasic Business Object.
C1-CSRPersonDelete	Used for Customer Service Request Person Delete. This component invokes the ATC1CSRPerson Inbound Web Service using the C1-ContractChangeReqPersnBasic Business Object.
C1-CSRPersonRead	Used for Customer Service Request Person Read. This component invokes the ATC1CSRPerson Inbound Web Service using the C1-ContractChangeReqPersnBasic Business Object.
C1-CSRPersonUpdate	Used for Customer Service Request Person Update. This component invokes the ATC1CSRPerson Inbound Web Service using the C1-ContractChangeReqPersnBasic Business Object.
C1-CSRAccountAdd	Used for Customer Service Request Account Add. This component invokes the ATC1CSRAccount Inbound Web Service using the C1-ContractChngeReqAcctBasic Business Object.
C1-CSRAccountDelete	Used for Customer Service Request Account Delete. This component invokes the ATC1CSRAccount Inbound Web Service using the C1-ContractChngeReqAcctBasic Business Object.
C1-CSRAccountRead	Used for Customer Service Request Account Read. This component invokes the ATC1CSRAccount Inbound Web Service using the C1-ContractChngeReqAcctBasic Business Object.
C1-CSRAccountUpdate	Used for Customer Service Request Account Update. This component invokes the ATC1CSRAccount Inbound Web Service using the C1-ContractChangeReqPersnBasic Business Object.
C1-CSRPremiseAdd	Used for Customer Service Request Premise Add. This component invokes the ATC1CSRPremise Inbound Web Service using the C1-ContrctChngeReqPremiseBasic Business Object.

Component	Description
C1-CSRPremiseDelete	Used for Customer Service Request Premise Delete. This component invokes the ATC1CSRPremise Inbound Web Service using the C1-ContrctChngeReqPremiseBasic Business Object.
C1-CSRPremiseRead	Used for Customer Service Request Premise Read. This component invokes the ATC1CSRPremise Inbound Web Service using the C1-ContrctChngeReqPremiseBasic Business Object.
C1-CSRPremiseUpdate	Used for Customer Service Request Premise Update. This component invokes the ATC1CSRPremise Inbound Web Service using the C1-ContrctChngeReqPremiseBasic Business Object.
C1-CSRContractAdd	Used for Customer Service Request for Contract Add. This component invokes the ATC1CSRContract Inbound Web Service using the C1-ContractChangeReqContRoot Business Object.
C1-CSRContractDelete	Used for Customer Service Request for Contract Delete. This component invokes the ATC1CSRContract Inbound Web Service using the C1-ContractChangeReqContRoot Business Object.
C1-CSRContractRead	Used for Customer Service Request for Contract Delete. This component invokes the ATC1CSRContract Inbound Web Service using the C1-ContractChangeReqContRoot Business Object.
C1-CSRContractUpdate	Used for Customer Service Request for Contract Update. This component invokes the ATC1CSRContract Inbound Web Service using the C1-ContractChangeReqContRoot Business Object.
C1-CSRContractProductAdd	Used for Customer Service Request for Contract Product Add. This component invokes the ATC1CSRContractProduct Inbound Web Service using the C1-ContractChangeReqCnProdRoot Business Object.

Component	Description
C1-CSRContractProductDelete	Used for Customer Service Request for Contract Product Delete. This component invokes the ATC1CSRContractProduct Inbound Web Service using the C1-ContractChangeReqCnProdRoot Business Object.
C1-CSRContractProductRead	Used for Customer Service Request for Contract Product Delete. This component invokes the ATC1CSRContractProduct Inbound Web Service using the C1-ContractChangeReqCnProdRoot Business Object.
C1-CSRContractProductUpdate	Used for Customer Service Request for Contract Product Delete. This component invokes the ATC1CSRContractProduct Inbound Web Service using the C1-ContractChangeReqCnProdRoot Business Object.
C1-CSRServiceLocationMktProcAdd	Used for Customer Service Request for Service Location Market Process Add. This component invokes the ATC1CSRServiceLocationMktProc Inbound Web Service using the C1-CsrSvcLocMarketProcessRoot Business Object.
C1-CSRServiceLocationMktProcDelete	Used for Customer Service Request for Service Location Market Process Delete. This component invokes the ATC1CSRServiceLocationMktProc Inbound Web Service using the C1-CsrSvcLocMarketProcessRoot Business Object.
C1-CSRServiceLocationMktProcRead	Used for Customer Service Request for Service Location Market Process Read. This component invokes the ATC1CSRServiceLocationMktProc Inbound Web Service using the C1-CsrSvcLocMarketProcessRoot Business Object.
C1-CSRServiceLocationMktProcUpdate	Used for Customer Service Request for Service Location Market Process Update. This component invokes the ATC1CSRServiceLocationMktProc Inbound Web Service using the C1-CsrSvcLocMarketProcessRoot Business Object.

Component	Description
C1-RegistrationPointAdd	Used to Add Registration Point. This component invokes the ATC1RegistrationPoint Inbound Web Service using the C1-RegistrationPoint Business Object.
C1-RegistrationPointDelete	Used to Delete Registration Point. This component invokes the ATC1RegistrationPoint Inbound Web Service using the C1-RegistrationPoint Business Object.
C1-RegistrationPointRead	Used to Read Registration Point. This component invokes the ATC1RegistrationPoint Inbound Web Service using the C1-RegistrationPoint Business Object.
C1-RegistrationPointUpdate	Used to Update Registration Point. This component invokes the ATC1RegistrationPoint Inbound Web Service using the C1-RegistrationPoint Business Object.
C1-ContractChangeRequestAdd	Used to Add Contract Change Request. This component invokes the ATC1ContractChangeRequest Inbound Web Service using the C1-ContractChangeRequest Business Object.
C1-ContractChangeRequestDelete	Used to Delete Contract Change Request. This component invokes the ATC1ContractChangeRequest Inbound Web Service using the C1-ContractChangeRequest Business Object.
C1-ContractChangeRequestRead	Used to Read Contract Change Request. This component invokes the ATC1ContractChangeRequest Inbound Web Service using the C1-ContractChangeRequest Business Object.
C1-ContractChangeRequestUpdate	Used to Update Contract Change Request. This component invokes the ATC1ContractChangeRequest Inbound Web Service using the C1-ContractChangeRequest Business Object.
C1-StartServiceRequestAdd	Used to add a Start Service Request. This component invokes the ATC1StartServiceRequest Inbound Web Service using the C1-StartServiceRequest Business Object.

Component	Description
C1-StartServiceRequestDelete	Used to delete a Start Service Request. This component invokes the ATC1StartServiceRequest Inbound Web Service using the C1-StartServiceRequest Business Object.
C1-StartServiceRequestRead	Used to read a Start Service Request. This component invokes the ATC1StartServiceRequest Inbound Web Service using the C1-StartServiceRequest Business Object.
C1-StartServiceRequestUpdate	Used to update a Start Service Request. This component invokes the ATC1StartServiceRequest Inbound Web Service using the C1-StartServiceRequest Business Object.
C1-StopServiceRequestAdd	Used to add a Stop Service Request. This component invokes the ATC1StopServiceRequest Inbound Web Service using the C1-StopServiceRequest Business Object.
C1-StopServiceRequestDelete	Used to delete a Stop Service Request. This component invokes the ATC1StopServiceRequest Inbound Web Service using the C1-StopServiceRequest Business Object.
C1-StopServiceRequestRead	Used to read a Stop Service Request. This component invokes the ATC1StopServiceRequest Inbound Web Service using the C1-StopServiceRequest Business Object.
C1-StopServiceRequestUpdate	Used to update a Stop Service Request. This component invokes the ATC1StopServiceRequest Inbound Web Service using the C1-StopServiceRequest Business Object.
C1-TransferServiceRequestAdd	Used to add a Transfer Service Request. This component invokes the ATC1TransferServiceRequest Inbound Web Service using the C1-TransferServiceRequest Business Object.
C1-TransferServiceRequestDelete	Used to delete a Transfer Service Request. This component invokes the ATC1StartServiceRequest Inbound Web Service using the C1-StartServiceRequest Business Object.

Component	Description
C1-TransferServiceRequestRead	Used to read a Transfer Service Request. This component invokes the ATC1TransferServiceRequest Inbound Web Service using the C1-TransferServiceRequest Business Object.
C1-TransferServiceRequestUpdate	Used to update a Transfer Service Request. This component invokes the ATC1TransferServiceRequest Inbound Web Service using the C1-TransferServiceRequest Business Object.

CX - API (REST)

Component	Description
C1-AccountDataRestIWS	Used to get an Account Financial Data. This component invokes the C1-AccountData Inbound Web Service using the C1FinDetails Service Script.
C1-AccountRestIWS	Used to get an Account and it's child APIs. This component invokes the C1-Account Inbound Web Service using the C1-GtAccount Service Script.
C1-ActionBudgetRestIWS	Used to Update Budget. This component invokes the C1-Budget Inbound Web Service using the C1BudgetData Service Script.
C1-ActionCutProcessRestIWS	Used to Update Cut Process. This component invokes the C1-CutProcess Inbound Web Service using the C1CutProcess Service Script.
C1-ActionOverdueProcessRestIWS	Used to Update Overdue Process. This component invokes the C1-OverdueProcess Inbound Web Service using the C1OverduePro Service Script.
C1-ActionFinancialStatisticsRestIWS	Used to Retrieve Account Data. This component invokes the C1-AccountData Inbound Web Service using the C1FinStats Service Script.

Component	Description
C1-ActionSearchRestIWS	Used to search Account. This component invokes the C1-BillingContext Inbound Web Service using the C1ActForPers Service Script.
C1-AdjustmentSummaryRestIWS	Used to retrieve Adjustment Summary. This component invokes the C1-Adjustment Inbound Web Service using the C1AdjSumry Service Script.
C1-BillSegmentSummaryRestIWS	Used to retrieve Bill Segment Summary. This component invokes the C1-BillSegment Inbound Web Service using the C1BilSegSmry Service Script.
C1-BillSearchRestIWS	Used to Search Bill. This component invokes the C1-Bill Inbound Web Service using the C1BillsForAc Service Script.
C1-BillSegmentsSearchRestIWS	Used to Search Bill Segment. This component invokes the C1-BillSegment Inbound Web Service using the C1BilSegSrch Service Script.
C1-BillSummaryRestIWS	Used to Get Bill Summary. This component invokes the C1-Bill Inbound Web Service using the C1BillSumry Service Script.
C1--BusinessPersonQueriesSummary RestIWS	Used to retrieve Business Person Queries. This component invokes the C1-PersonQueries Inbound Web Service using the C1PersonSumm Service Script.
C1-BusinessSearch	Used to search CX4U Key Account Mgt. (KAM) This component invokes the C1-BusinessSearch Inbound Web Service using the C1BusinSrch Service Script.
C1-CaseSearchRestIWS	Used to Search Case. This component invokes the C1-Case Inbound Web Service using the C1CaseSearch Service Script.
C1-CreateAccountRestIWS	Used to create an Account. This component invokes the C1-Account Inbound Web Service using the C1-CrAccount Service Script.

Component	Description
C1-CreateBillCharacteristicRestIWS	Used to Create Bill Characteristics. This component invokes the C1-Bill Inbound Web Service using the C1-CrBilChar Service Script.
C1-CreateBillMessagesRestIWS	Used to Create Bill Messages. This component invokes the C1-Bill Inbound Web Service using the C1-CrBilMsg Service Script.
C1-CreateBillRestIWS	Used to Create Bill. This component invokes the C1-Bill Inbound Web Service using the C1-CreBill Service Script.
C1-CreateBillRoutingsRestIWS	Used to Create Bill Routings. This component invokes the C1-Bill Inbound Web Service using the C1-CrBilRtng Service Script.
C1-CreateBillSegmentItems	Used to Create Bill Segments Items. This component invokes the C1-BillSegment Inbound Web Service using the C1-CreBSItem Service Script.
C1-CreateBillSegmentMessages	Used to Create Bill Segments Messages. This component invokes the C1-BillSegment Inbound Web Service using the C1-CreBSMsg Service Script.
C1-CreateBillSegmentRestIWS	Used to Create Bill Segments. This component invokes the C1-BillSegment Inbound Web Service using the C1-CrBilSeg Service Script.
C1-CreateBillSegmentServiceQuantities	Used to Create Bill Segments Service Quantities. This component invokes the C1-BillSegment Inbound Web Service using the C1-CrBSSeQts Service Script.
C1-CreatePaymentChar	Used to Create Payment Characteristics. This component invokes the C1-Payment Inbound Web Service using the C1-CtPytChar Service Script.
C1-CreatePaymentTender	Used to Create Payment Tender. This component invokes the C1-PaymentTender Inbound Web Service using the C1CreatPayTe Service Script.

Component	Description
C1-CreatePaymentTenderChar	Used to Create Payment Tender Characteristics. This component invokes the C1-PaymentTender Inbound Web Service using the C1CreatPayTe Service Script.
C1-CreatePersonContactDetails	Used to Create Person Contact. This component invokes the C1-Person Inbound Web Service using the C1-Person Service Script.
C1-CreatePersonRestIWS	Used to Create Person. This component invokes the C1-Person Inbound Web Service using the C1-Person Service Script.
C1-CreatePremiseRestIWS	Used to create a Premise. This component invokes the C1-Premise Inbound Web Service using the C1-CrPremise Service Script.
C1-CreateServiceAgreementRestIWS	Used to create a Service Agreement. This component invokes the C1-ServiceAgreement Inbound Web Service using the C1-CreateSA Service Script.
C1-CreateWriteOffProcessRestIWS	Used to create a Write Off Process. This component invokes the C1-WriteOffProcess Inbound Web Service using the C1WriteOffPr Service Script.
C1-CustomerContactDelete	Used to delete a Customer Contact. This component invokes the C1-Person Inbound Web Service using the C1-DelCustCt Service Script.
C1-CustomerContactPost	Used to create a Customer Contact. This component invokes the C1-CustomerContact Inbound Web Service using the C1-CreCustCt Service Script.
C1-CustomerContactPut	Used to update a Customer Contact. This component invokes the C1-CustomerContact Inbound web Service using the C1-UpdCustCt Service Script.
C1-CustomerContactRestIWS	Used to get a Customer Contact and it's child APIs. This component invokes the C1-CustomerContact Inbound Web Service using the C1-GetCustCt Script.

Component	Description
C1-DeleteAccount	Used to delete an Account. This component invokes the C1-Account Inbound Web Service using the C1-DelAcc Service Script.
C1-DeletePaymentEvent	Used to Delete Payment Event. This component invokes the C1-PaymentEvent Inbound Web Service using the C1-DelPayEvt Service Script.
C1-DeletePerson	Used to delete a Person. This component invokes the C1-Person Inbound Web Service using the C1-DelPerson Script.
C1-DeletePremiseRestIWS	Used to delete a Premise. This component invokes the C1-Premise Inbound Web Service using the C1-DePremise Service Script.
C1-DeleteServiceAgreementRestIWS	Used to delete a Service Agreement. This component invokes the C1-ServiceAgreement Inbound Web Service using the C1-DeleteSA Service Script.
C1-ExpandTreeRestIWS	Used to Expand Tree. This component invokes the F1-ExpandTree Inbound Web Service using the F1-ExpandTree Service Script.
C1-EntityReferencesRestIWS	Used to support of selected CX4U Entities This component invokes the C1-EntityReferences Inbound Web Service using the C1EntRefSumm Service Script.
C1-GetAccountFinancialHistory	Used to Get Account Financial History. This component invokes the C1-Bill Inbound Web Service using the C1-CreBill Service Script.
C1-GetBillBillSegmentRestIWS	Used to Get Bill Bill Segments. This component invokes the C1-BillSegment Inbound Web Service using the C1-GetBilSeg Service Script.
C1-GetBillRestIWS	Used to Get Bill. This component invokes the C1-Bill Inbound Web Service using the C1-GetBill Service Script.

Component	Description
C1-GetBillSegmentRestIWS	Used to Get Bill Segment. This component invokes the C1-BillSegment Inbound Web Service using the C1-BillSegm Service Script.
C1-GetBudgetRestIWS	Used to Get Budget. This component invokes the C1-Budget Inbound Web Service using the C1BudgetDeta Service Script.
C1-GetCutProcessRestIWS	Used to Get Cut Process. This component invokes the C1-CutProcess Inbound Web Service using the C1CutProcess Service Script.
C1-GetLandlordAgreementsPremisesList	Used to Get Land Lord Agreement Premise List. This component invokes the C1-LandlordAgreement Inbound Web Service using the C1LandlordAg Service Script.
C1-GetOverdueProcessRestIWS	Used to Get Overdue Process. This component invokes the C1-OverdueProcess Inbound Web Service using the C1OverduePro Service Script.
C1-GetPaymentChar	Used to Get Payment Characteristics. This component invokes the C1-Payment Inbound Web Service using the C1-GtPytChar Service Script.
C1-GetPaymentPaySegmentRestIWS	Used to Get Payment Segment in Payment. This component invokes the C1-Payment Inbound Web Service using the C1-CxPayment Service Script.
C1-GetWriteOffProcessRestIWS	Used to Get Write Off Process. This component invokes the C1-WriteoffProcess Inbound Web Service using the C1WriteOffPr Service Script.
C1-DeleteLandlordAgreement	Used to delete a Landlord record. This component invokes the C1-LandlordAgreement Inbound Web Service using the C1LandlordAg Service Script.

Component	Description
C1-GetLandlordAgreement	Used to get a Landlord record. This component invokes the C1-LandlordAgreement Inbound Web Service using the C1LandlordAg Service Script.
C1-UpdateLandlordAgreement	Used to update a Landlord record. This component invokes the C1-LandlordAgreement Inbound Web Service using the C1LandlordAg Service Script.
C1-MultiAccountStatisticsRestIWS	Used to Get Multi Account Statistics. This component invokes the C1-AccountData Inbound Web Service using the C1FinStats Service Script.
C1-MultiAccountUsageSummaryRestIWS	Used to Get Multi Account Usage Summary. This component invokes the C1-BilledUsageData Inbound Web Service using the C1MlAcUsgSum Service Script.
C1-GetSeveranceProcessRestIWs	Used to lead to the severance of a service agreement. This component invokes the C1-SeveranceProcess Inbound Web Service using the C1SeveraProc Service Script.
C1-PaymentEventGet	Used to Get Payment Event. This component invokes the C1-PaymentEvent Inbound Web Service using the C1-PayEvent Service Script.
C1-PaymentEventPaymentsRestIWS	Used to Get Payments of Payment Event. This component invokes the C1-PaymentEvent Inbound Web Service using the C1PayEvtPay Service Script.
C1-PaymentEventPost	Used to Create Payment Event. This component invokes the C1-PaymentEvent Inbound Web Service using the C1-PayEvent Service Script.
C1-PaymentGet	Used to Get Payment. This component invokes the C1-Payment Inbound Web Service using the C1-GetPaymnt Service Script.

Component	Description
C1-PaymentPost	Used to Create Payment. This component invokes the C1-Payment Inbound Web Service using the C1-CrPymtHdr Service Script.
C1-PaymentPut	Used to Update Payment. This component invokes the C1-Payment Inbound Web Service using the C1-UpdPymt Service Script.
C1-PaymentSummaryRestIWS	Used to Retrieve the Payment Summary. This component invokes the C1-Payment Inbound Web Service using the C1-UpdPymt Service Script.
C1-PayPlanRestIWS	Used to create a Payment Tender. This component invokes the C1-PayPlan Inbound Web Service using the C1PayPlan Service Script.
C1-PaymentTenderRestIWS	Used to Get Payment Tender. This component invokes the C1-PaymentTender Inbound Web Service using the C1-GetPayTen Service Script.
C1-PersonPost	Used to create a Person. This component invokes the C1-Person Inbound Web Service using the C1-CrePerson Service Script.
C1-PersonRestIWS	Used to get a Person and its child APIs. This component invokes the C1-Person Inbound Web Service using the C1-GetPerson Service Script.
C1-PersonSearchRestIWS	Used to search a Person. This component invokes the C1-PersonSearch Inbound Web Service using the C1PersonSrch Service Script.
C1-PostCustomerContactChar	Used to create a Customer Contact Characteristics. This component invokes the C1-CustomerContact Inbound Web Service using the C1-CustCntct Service Script.
C1-PostCustomerContactlogs	Used to create a Customer Contact Characteristics. This component invokes the C1-CustomerContact Inbound Web Service using the C1-CustCntct Service Script.

Component	Description
C1-PostPremiseAltAddr	Used to Create Premise with Alternate Address. This component invokes the C1-Premise Inbound web Service using the C1-Premise Service Script.
C1-PostPremiseChar	Used to Create Premise with Characteristics. This component invokes the C1-Premise Inbound web Service using the C1-Premise Service Script.
C1-PostPremiseGeoLoc	Used to Create Premise with Geographic Location. This component invokes the C1-Premise Inbound web Service using the C1-Premise Service Script.
C1-PostSABillMsg	Used to Create SA with Bill Message. This component invokes the C1-ServiceAgreement Inbound web Service using the C1-ServiceAg Service Script.
C1-PostSAChar	Used to Create SA with Characteristics. This component invokes the C1-ServiceAgreement Inbound web Service using the C1-ServiceAg Service Script.
C1-PostSAConsumerContPro	Used to Create SA with Consumer Contract Product. This component invokes the C1-ServiceAgreement Inbound web Service using the C1-ServiceAg Service Script.
C1-PostSAContractOption	Used to Create SA with Contract Options. This component invokes the C1-ServiceAgreement Inbound web Service using the C1-ServiceAg Service Script.
C1-PostSAContractQuant	Used to Create SA with Contract Quantities. This component invokes the C1-ServiceAgreement Inbound web Service using the C1-ServiceAg Service Script.
C1-PostSAContractTherms	Used to Create SA with Contract Therms. This component invokes the C1-ServiceAgreement Inbound web Service using the C1-ServiceAg Service Script.
C1-PostSARateSchedHist	Used to Create SA with Rate Schedule History. This component invokes the C1-ServiceAgreement Inbound web Service using the C1-ServiceAg Service Script.

Component	Description
C1-PostSARecurrCharHist	Used to Create SA with Recurring Charge History. This component invokes the C1-ServiceAgreement Inbound web Service using the C1-ServiceAg Service Script.
C1-PostSAServicePoints	Used to create a Service Agreement with Service Points. This component invokes the C1-ServiceAgreement Inbound web Service using the C1-ServiceAg Service Script.
C1-PostSATermsCond	Used to create a Service Agreement with Terms and Condition. This component invokes the C1-ServiceAgreement Inbound web Service using the C1-ServiceAg Service Script.
C1-PremiseRestIWS	Used to get a Premise and its child APIs. This component invokes the C1-Premise Inbound Web Service using the C1-GtPremise Service Script.
C1-PremiseTest	Used to get a Premise and its child APIs. This component invokes the C1-Premise Inbound Web Service using the C1-GtPremise Service Script.
C1-PutCustomerContactChar	Used to update a Customer Contact Characteristics. This component invokes the C1-CustomerContact Inbound Web Service using the C1-CustCntct Service Script.
C1-PutCustomerContactlogs	Used to update Customer Contact Characteristics. This component invokes the C1-CustomerContact Inbound Web Service using the C1-CustCntct Service Script.
C1-PutPremiseAltAddr	Used to update a Premise with Alternate Address. This component invokes the C1-Premise Inbound web Service using the C1-Premise Service Script.
C1-PutPremiseChar	Used to update a Premise with Characteristics. This component invokes the C1-Premise Inbound web Service using the C1-Premise Service Script.
C1-PutPremiseGeoLoc	Used to update a Premise with Geographic Location. This component invokes the C1-Premise Inbound web Service using the C1-Premise Service Script.

Component	Description
C1-PutSABillMsg	Used to Update SA with Bill Message. This component invokes the C1-ServiceAgreement Inbound web Service using the C1-ServiceAg Service Script.
C1-PutSACChar	Used to update a Service Agreement with Characteristics. This component invokes the C1-ServiceAgreement Inbound Web Service using the C1-ServiceAg Service Script.
C1-PutSAConsumerContPro	Used to update a Service Agreement with Consumer Contract Product. This component invokes the C1-ServiceAgreement Inbound web Service using the C1-ServiceAg Service Script.
C1-PutSAContractOption	Used to update a Service Agreement with Contract Options. This component invokes the C1-ServiceAgreement Inbound web Service using the C1-ServiceAg Service Script.
C1-PutSAContractQuant	Used to update a Service Agreement with Contract Quantities. This component invokes the C1-ServiceAgreement Inbound web Service using the C1-ServiceAg Service Script.
C1-PutSAContractTherms	Used to update a Service Agreement with Contract Therms. This component invokes the C1-ServiceAgreement Inbound web Service using the C1-ServiceAg Service Script.
C1-PutSARateSchedHist	Used to update a Service Agreement with Rate Schedule History. This component invokes the C1-ServiceAgreement Inbound web Service using the C1-ServiceAg Service Script.
C1-PutSARecurrCharHist	Used to update a Service Agreement with Recurring Charge History. This component invokes the C1-ServiceAgreement Inbound web Service using the C1-ServiceAg Service Script.

Component	Description
C1-PutSAServicePoints	Used to update a Service Agreement with Service Points. This component invokes the C1-ServiceAgreement Inbound web Service using the C1-ServiceAg Service Script.
C1-PutSATermsCond	Used to update a Service Agreement with Terms and Condition. This component invokes the C1-ServiceAgreement Inbound web Service using the C1-ServiceAg Service Script.
C1-ServiceAgreementRestIWS	Used to get a Service Agreement and its child APIs. This component invokes the C1-ServiceAgreement Inbound Web Service using the C1-GetSA Service Script.
C1-ServicePointCreate	Used to create a Service Point. This component invokes the C1-ServicePoint Inbound Web Service using the C1-CreateSP Service Script.
C1-ServicePointDelete	Used to delete a Service Point. This component invokes the C1-ServicePoint Inbound Web Service using the C1-DeleteSP Service Script.
C1-ServicePointPut	Used to update a Service Point. This component invokes the C1-ServicePoint Inbound Web Service using the C1-UpdateSP Service Script.
C1-ServicePointRestIWS	Used to get a Service Point and its child APIs. This component invokes the C1-ServicePoint Inbound Web Service using the C1-GetSP Service Script.
C1-ServicePointSearchRestIWS	Used to search Service Point. This component invokes the C1-ServicePointSearch Inbound Web Service using the C1ServPtSrch Script.
C1-UpdateAccountRestIWS	Used to update an Account. This component invokes the C1-Account Inbound Web Service using the C1-UpAccount Service Script.

Component	Description
C1-UpdateBillCharacteristicRestIWS	Used to update Bill Characteristics. This component invokes the C1-Bill Inbound Web Service using the C1-CrBilChar Service Script.
C1-UpdateBillMessagesRestIWS	Used to update Bill Messages. This component invokes the C1-Bill Inbound Web Service using the C1-CrBilMsg Service Script.
C1-UpdateBillRestIWS	Used to update a Bill. This component invokes the C1-Bill Inbound Web Service using the C1-CreBill Service Script.
C1-UpdateBillRoutingsRestIWS	Used to update Bill Routings. This component invokes the C1-Bill Inbound Web Service using the C1-CrBilRtng Service Script.
C1-UpdateBillSegmentRestIWS	Used to update Bill Segments. This component invokes the C1-BillSegment Inbound Web Service using the C1ActBillSeg Service Script.
C1-UpdateBillSegmentItems	Used to update Bill Segment Items. This component invokes the C1-BillSegment Inbound Web Service using the C1ActBillSeg Service Script.
C1-UpdateBillSegmentMessages	Used to update Bill Segment Messages. This component invokes the C1-BillSegment Inbound Web Service using the C1ActBillSeg Service Script.
C1-UpdateCutProcessRestIWS	Used to update a Cut Process. This component invokes the C1-CutProcess Inbound Web Service using the C1CutProcess Service Script.
C1-UpdateOverdueProcessRestIWS	Used to update an Overdue Process. This component invokes the C1-OverdueProcess Inbound Web Service using the C1OverduePro Service Script.
C1-UpdatePaymentTender	Used to update a Payment Tender. This component invokes the C1-PaymentTender Inbound Web Service using the C1-UpPyTndrs Service Script.

Component	Description
C1-UpdatePaymentTenderChar	Used to update a Payment Tender Char. This component invokes the C1-PaymentTender Inbound Web Service using the C1-UpPyTndCh Service Script.
C1-UpdatePerson	Used to update a Person. This component invokes the C1-Person Inbound Web Service using the C1-UpdPerson Service Script.
C1-UpdatePersonCharacteristics	Used to update a Person Characteristics. This component invokes the C1-Person Inbound Web Service using the C1-UpdPerson Service Script.
C1-UpdatePersonIdentifiers	Used to update a Person Identifiers. This component invokes the C1-Person Inbound Web Service using the C1-UpdPerson Service Script.
C1-UpdatePersonNames	Used to update a Person Names. This component invokes the C1-Person Inbound Web Service using the C1-UpdPerson Service Script.
C1-UpdatePersonNameOptions	Used to update a Person Name Options. This component invokes the C1-Person Inbound Web Service using the C1-UpdPerson Service Script.
C1-UpdatePersonPhones	Used to update a Person Phones. This component invokes the C1-Person Inbound Web Service using the C1-UpdPerson Service Script.
C1-UpdatePersonRelationships	Used to update a Person Relationships. This component invokes the C1-Person Inbound Web Service using the C1-UpdPerson Service Script.
C1-UpdatePersonSeasonalAddress	Used to update a Person Seasonal Address. This component invokes the C1-Person Inbound Web Service using the C1-UpdPerson Service Script.

Component	Description
C1-UpdatePremiseRestIWS	Used to update a Premise. This component invokes the C1-Premise Inbound Web Service using the C1-UpPremise Service Script.
C1-UpdateServiceAgreementRestIWS	Used to update a Service Agreement. This component invokes the C1-ServiceAgreement Inbound Web Service using the C1-UpdateSA Service Script.
C1-UpdateServicePointOperationAreas	Used to update a Service Point Operation Areas. This component invokes the C1-ServicePoint Inbound Web Service using the C1-UpdateSP Service Script.
C1-UpdateWriteOffProcessRestIWS	Used to update a Write Off Process. This component invokes the C1-WriteoffProcess Inbound Web Service using the C1WriteOffPr Service Script.
D1-UpdateBillSegment	Used to update a Bill Segment. This component invokes the C1-BillSegment Inbound Web Service using the C1ActBillSeg Service Script.
C1-AccountSearchRestIWS	Used to search Account. This component invokes the C1-BillingContext Inbound Web Service using the C1ActForPers Service Script.
C1-BillSegmentsSearchRestIWS	Used to search Bill Segment. This component invokes the C1-BillSegment Inbound Web Service using the C1BilSegSrch Service Script.
C1-ExpandTreeRestIWS	Used to trigger Expand Tree. This component invokes the F1-ExpandTree Inbound Web Service using the F1ExpandTree Service Script.
C1-GetAccountFinancialHistory	Used to get Account Financial History. This component invokes the C1-AccountData Inbound Web Service using the C1FinHistRest Service Script.

Component	Description
C1-GetPersonAccountsRestIWS	Used to get Person Accounts. This component invokes the C1-BillingContext Inbound Web Service using the C1GetPerActs Service Script.
C1-GetServiceAgreementStatisticsRestIWS	Used to get Service Agreement Statistics. This component invokes the C1-SADData Inbound Web Service using the C1SASStats Service Script.
C1-PersonSearchRestIWS	Used to search Person. This component invokes the C1-PersonSearch Inbound Web Service using the C1PersonSrch Service Script.
C1-ServiceAgreementBilledUsageRestIWS	Used to get Service Agreement Billed Usage. This component invokes the C1-BilledUsageData Inbound Web Service using the C1BillUsagSA Service Script.
C1-SingleServiceSummaryRestIWS	Used to get Single Service Summary. This component invokes the C1-BilledUsageData Inbound Web Service using the C1GetBiUsag Service Script.
C1-RatesRestIWS	Used to search Rate Schedules. This component invokes the C1-Rates Inbound Web Service using the C1RetRSSATyD Service Script.
C1-SATypeRestIWS	Used to retrieve SA Type List for SP Type and CIS Division. This component invokes the C1-SAType Inbound Web Service using the C1ReSATySPTD Service Script.

Appendix A

Inbound Web Services

The Oracle Utilities Customer Care and Billing Cloud Service components are developed using Web services method, and these components require Inbound Web Services to be defined in the application.

For instructions to create, import, or search an Inbound Web Service, see **Setting Up Inbound Web Services** in the *Oracle Utilities Testing Accelerator User's Guide* included in this release. Refer to the [Oracle Utilities Testing Accelerator for Cloud Services](#) page on [Oracle Help Center](#).

Below is a list of Inbound Web Services used with delivered components and flows:

- ATC1Account
- ATC1AccountBS
- ATC1AcctBalLetterExtract
- ATC1AccountLetterExtract
- ATC1ActivityInformation
- ATC1Adjustment
- ATC1AdjustmentType
- ATC1AdjustmentTypeProfile
- ATC1AdjustmentStagingControl
- ATC1AdjustmentUploadStaging
- ATC1AdjLetterExtract
- ATC1AdjSearchByAcctId
- ATC1AutoPayLetterExtract
- ATC1AutoPaySource
- ATC1AutoPayTask
- ATC1AutoPayTaskType
- ATC1AutoPayRouteType
- ATC1ApplyCCLCharges
- ATC1ApplyTo
- ATC1ApplyVatToCrossRefCharge

- ATC1Appointment
- ATC1Bill
- ATC1BillCorrection
- ATC1BillFactor
- ATC1BillFactorValue
- ATC1BillFactorTOUValue
- ATC1BillLetterExtract
- ATC1BillSegment
- ATC1BillableCharge
- ATC1BillingExtractPlusConfig
- ATC1BillRouteType
- ATC1C360Configuration
- ATC1CalcLine
- ATC1CalcRuleElCrt
- ATC1CalcRuleReferredCalcGroup
- ATC1CalculateFinalValue
- ATC1CalculateMiscellaneousCharg
- ATC1CalculateServiceQuantity
- ATC1CalculationGroup
- ATC1Campaign
- ATC1CampaignInitiative
- ATC1Case
- ATC1CaseBO
- ATC1CaseType
- ATC1CCBOneTimePaymentTaskType
- ATC1CCBOneTimePaymentTask
- ATC1CharacteristicType
- ATC1CISDivision
- ATC1CollectionAgencyReferral
- ATC1CollectionClassControl
- ATC1CollectionProcess
- ATC1CollLetterExtract
- ATC1ConservationInitiative
- ATC1ContractOption
- ATC1ContractOptEvent
- ATC1ContractOptInitiative

- ATC1CopySQFromMasterBillSegment
- ATC1CreateAdjustmentWithAppr
- ATC1CtrlCenSearchByAddress
- ATC1CtrlCenSearchByNameAddress
- ATC1CtrlCenSearchByAccountId
- ATC1CreateCSR
- ATC1CreateSARelationshipSubSA
- ATC1ConsumerContract
- ATC1ContractChangeRequest
- ATC1CSRAccount
- ATC1CSRContract
- ATC1CSRContractProduct
- ATC1CSRPerson
- ATC1CSRPremise
- ATC1SCRServiceLocationMktProc
- ATC1CSRTSvcEligCriteria
- ATC1CSRTQuestion
- ATC1CSRTRelUpd
- ATC1CustContactType
- ATC1CustomerContact
- ATC1CustConLetterExtract
- ATC1CutProcess
- ATC1CustSvcRequestResponse
- ATC1Declaration
- ATC1DepositControl
- ATC1DetermineDemandValueToPrice
- ATC1DeviceInformation
- ATC1DeviceTest
- ATC1DeviceTestSelection
- ATC1DefaultUsage
- ATC1DispatchFA
- ATC1DispatchGroup
- ATC1DisplayIconOverrideConfig
- ATC1DistributionCode
- ATC1ExternalRepoPlusBillSegSync
- ATC1ExternalRepoPlusBillSync

- ATC1ExternalRepoPlusCusDataSyncRead
- ATC1ExternalRepoPlusBillingSyncRead
- ATC1ExternalRepoPlusMailAddSync
- ATC1ExternalRepoPlusSASPSync
- ATC1ExternalRepoPlusSPMeterSync
- ATC1EndOfLetterExtract
- ATC1FACompletion
- ATC1FACompletionMessage
- ATC1FASyncRequestRead
- ATC1FAUploadStaging
- ATC1FieldActivity
- ATC1FlatCharge
- ATC1FT
- ATC1GeographicType
- ATC1GetBOStatus
- ATC1GetCSRAccount
- ATC1GetCSRContract
- ATC1GetCSRPerson
- ATC1GetCSRPremise
- ATC1GetCSRProduct
- ATC1GetCSRServiceLocation
- ATC1GetEligibleProduct
- ATC1GetProdAttributeContract
- ATC1GetPersonCustContact
- ATC1GetSubUsageRequestSQ
- ATC1GetSyncRequestId
- ATC1GetUsageId
- ATC1InsightGroup
- ATC1IdentifierType
- ATC1InitiativeLogs
- ATC1InitiativeQuery
- ATC1IntervalValueSet
- ATC1Item
- ATC1ItemInstallation
- ATC1ItemReplicator
- ATC1ItemType

- ATC1ItemTypeCharge
- ATC1LandlordAgreement
- ATC1Lead
- ATC1LeadAccount
- ATC1LeadEvent
- ATC1LeadQuery
- ATC1LetterTemplate
- ATC1Loan
- ATC1Market
- ATC1MailInfoLetterExtract
- ATC1MRUploadStaging
- ATC1Math
- ATC1MatchEvent
- ATC1Maximum
- ATC1MDM2PersonSyncRequestRead
- ATC1MDM2MRSyncRequestRead
- ATC1MDM2MtrConfigSyncReqRead
- ATC1MDM2SASyncRequestRead
- ATC1MDM2SPSyncRequestRead
- ATC1MDM2SpMtrHistSyncReqRead
- ATC1MDM2MtrSyncRequestRead
- ATC1MDM2BillCycleSyncRequestRead
- ATC1MDM2ContrOptEvtSyncReqRead
- ATC1MDM2ContractOptSyncReqRead
- ATC1MDM2SARelSyncRequestRead
- ATC1Meter
- ATC1MeterConfiguration
- ATC1MeterRead
- ATC1MeterReplicator
- ATC1MigrationAssistantConfig
- ATC1Minimum
- ATC1MktSATypeSARelationshipType
- ATC1MktProvConfigOpt
- ATC1MultiCancelRebill
- ATC1MyLead
- ATC1NonBilledBudget

- ATC1NotificationEventType
- ATC1NotificationType
- ATC1NotifTypeTmplIndividualPush
- ATC1NotifTypeTmplParentPush
- ATC1NotifTypeTmplSubscription
- ATC1NMSIntegrationMasterConfig
- ATC1NtfContactPreference
- ATC1NtfContactPreferenceSync
- ATC1NMSSPPerCntSyncRequestRead
- ATC1NMSSPSyncRequestRead
- ATC1OffCycleBillGenerator
- ATC1OutageCallType
- ATC1OutageCallWithoutPrem
- ATC1OutageCallWithPrem
- ATC1Order
- ATC1OneTimePaymentTask
- ATC1OneTimePaymentTaskType
- ATC1OverdueProcess
- ATC1ODMSPSyncRequestRead
- ATC1Package
- ATC1PackageBS
- ATC1PARrequest
- ATC1PayArrangement
- ATC1PayPlan
- ATC1Payment
- ATC1PayArrangeByBill
- ATC1PayEventPhysicalBO
- ATC1PaymentEvent
- ATC1PaymentEventQuickAdd
- ATC1PaymentLetterExtract
- ATC1PaymentQuickAdd
- ATC1PayTndrLetterExtract
- ATC1PaymentTypeLookup
- ATC1Person
- ATC1PersonBS
- ATC1PersonContact

- ATC1PersonContactType
- ATC1PersonLetterExtract
- ATC1Premise
- ATC1PremiseLetterExtract
- ATC1PremiseManagement
- ATC1PremiseReplicator
- ATC1PremiseType
- ATC1PremFAGTT
- ATC1ProviderConfigurationOption
- ATC1PushNotificationOptOut
- ATC1Question
- ATC1Quote
- ATC1RateCheck
- ATC1RateScheduleV1
- ATC1RateScheduleV2
- ATC1RateVersion
- ATC1RebateClaim
- ATC1RebateClaimLine
- ATC1RebateClaimLogs
- ATC1RecommendBudget
- ATC1RegistrationPoint
- ATC1RenumberMRRRouteSequence
- ATC1RetrieveServiceTask
- ATC1SARelationship
- ATC1SARelType
- ATC1SaleRepGroup
- ATC1SalesRepIndividual
- ATC1SalesRepIndividualRead
- ATC1SalesRepLogs
- ATC1SaType
- ATC1SATypeSARelationshipType
- ATC1SPMeterInstallation
- ATC1SPType
- ATC1ServiceAgreement
- ATC1ServiceAgreementUpdate
- ATC1ServiceCallCommMethod

- ATC1ServiceCallCommTaskType
- ATC1ServiceCallCommunication
- ATC1ServiceCategory
- ATC1ServiceCode
- ATC1ServiceCreditEvent
- ATC1ServiceCreditMembership
- ATC1ServiceCallCommunication
- ATC1ServiceCode
- ATC1ServicePoint
- ATC1ServiceProviderSARelationship
- ATC1ServiceQuantity
- ATC1ServiceRteTransfer
- ATC1ServiceRequestUpdate
- ATC1SeveranceProcess
- ATC1SevLetterExtract
- ATC1SimpleSummary
- ATC1StartServiceActionMethod
- ATC1StartServiceRequestType
- ATC1StartServiceRequestSA
- ATC1StopServiceRequestSA
- ATC1StartStop
- ATC1StartStopBS
- ATC1Statement
- ATC1StatementConstruct
- ATC1SteppedSQ
- ATC1StockLocation
- ATC1StockLocationInventory
- ATC1StopServiceActionMethod
- ATC1StopServiceRequestType
- ATC1SSAddServiceRequestType
- ATC1SSNewServiceRequestType
- ATC1SSStopServiceRequestType
- ATC1SSTransferServiceReqType
- ATC1SSStartStopXferServiceTask
- ATC1SSStartStopXferSvcTaskType
- ATC1StopServiceRequest

- ATC1StopServiceRequestType
- ATC1Summary
- ATC1SummaryLetterExtract
- ATC1SyncRequestUpdate
- ATC1SvcProvMktOpt
- ATC1TenderControl
- ATC1TenderCtrlSearchByAllUser
- ATC1TermsOfService
- ATC1ThirdPartyAcctVerificationTaskType
- ATC1ThirdPartyAutoPaySetup
- ATC1ThirdPartyAutoPayTask
- ATC1ThirdPartyAutoPayTaskType
- ATC1ThirdPartyOneTimePayNotification
- ATC1ThirdPartyOneTimePayTask
- ATC1ThirdPartyOneTimePyTaskType
- ATC1ThirdPartyRep
- ATC1ThirdPartyVerifyAccount
- ATC1TransferServiceActionMethod
- ATC1TransferServiceRequest
- ATC1TransferServiceRequestType
- ATC1TransitionBOStatus
- ATC1Trend
- ATC1UmbrellaAgreement
- ATC1UsageReqCyclicalBilling
- ATC1UsageRequestTransition
- ATC1UserMisc
- ATC1WAMIntegrationMasterConfig
- ATC1WriteOff
- ATC1WriteOffLetterExtract
- ATC1WriteOffProcess
- ATF1GenericDataSync

DSS

- CXAccountLookup
- CXReportOutage
- CXRetOutageJobHistory

REST SERVICES

- C1-Account
- C1-Person
- C1-CustomerContact
- C1-Premise
- C1-ServiceAgreement
- C1-ServicePoint
- C1-Bill
- C1-BillingContext
- C1-BillSegment
- C1-BilledUsageData
- C1-BusinessSearch
- C1-CollectionProcess
- C1-EntityReference
- C1-LandlordAgreement
- C1-PaymentEvent
- C1-Payment
- C1-PersonSearch
- C1-PersonQueries
- C1-PaymentTender
- C1-PayPlan
- C1-SeveranceProcess
- C1-WebUser
- C1-WebUserAccount
- C1-SelfServiceTask
- C1-ServicePointSearch
- C1-CustomerActivityHistory
- C1-CommunicationsPreferences
- C1-GetPerCtxt
- C1-UpdateServiceCallCommunication
- C1-SAData
- C1-AccountDat

Appendix B

Identifying Fields For a Web Service Request

The requisite fields need to be filled up with data in order to map the value on a given schema.

Example: When a person is added online, only the field description is shown, but the exact field mapping is hidden from the user.

Following are the methods you can use to identify fields for a web service request and add data in those fields:

- [Debug Mode in the Application](#)
- [IE Development Tool Bar](#)
- [SOAP UI](#)


Debug Mode in the Application

The debug mode enables users to check the field mapping on a given maintenance page. This is actually the easiest among the different possible ways; however some clients may have system restriction (such as access restriction) on using debug mode.

To enter test data in the requisite fields using the debug method:

1. Login to the Oracle Utilities Customer Care and Billing Cloud Service application in the 'debug' mode.
2. Navigate to target page and click the Debug mode switch.

Example: Person maintenance page



3. Perform the required action. Click **Save**.

Example: The figure below shows where to add a person's information, such as names, phones, contacts, ID, and so on.

The screenshot shows the 'Person' entity form in the Oracle Utilities Testing Accelerator application. The form is in 'Debug Mode' and displays the following sections:

- Person Information:** Includes fields for 'Person ID' (None), 'Person/Business' (Person), and 'Life Support / Sensitive Load' (None).
- Person Names:** Includes a table with columns 'Name Type' and 'Person Name'. The first row shows 'Primary' and 'Sanity,48173'.
- Person Phones:** Includes a table with columns 'Phone Type', 'Phone Number', 'Extension', and 'Phone Format'.
- Person Contacts:** Includes a table with columns 'Contact Routing', 'Person Contact Type', 'Contact Information', 'Extension', 'Format', 'Primary', and 'Do Not'.
- Person IDs:** Includes a table with columns 'Primary ID', 'ID Type', 'ID Number', and 'Identifier Format'. The first row shows 'Primary ID' (checked), 'ID Type' (Social security number), 'ID Number' (523-65-5514), and 'Identifier Format' (999-99-9999).

The schema window with the populated values is displayed.


```

https://slc06gbm.us.oracle.com:10701/ousf/cisMain.jsp?language=ENG
<field name="IN_CITY_LIM_LBL">In City Limit</field>
<field name="GEO_CODE_LBL">Geographic Code</field>
<list name="PER_IDENTIFIER">
  <listHeader>
    <field name="PER_ID"></field>
    <field name="LAST_ID_TYPE_CD"></field>
    <field name="moreRows">false</field>
    <field name="remainingRows">0</field>
    <field name="lastInfo"></field>
  </listHeader>
  <listBody action="A">
    <field name="PER_ID"></field>
    <field name="ID_TYPE_CD">SSN</field>
    <field name="PER_ID_NBR">523-65-5514</field>
    <field name="PRIM_SW">true</field>
    <field name="VERSION">0</field>
    <field name="ENCR_PER_ID_NBR"></field>
    <field name="HASH_PER_ID_NBR"></field>
    <field name="IDENTIFIER_FMT">999-99-9999</field>
  </listBody>
</list>
<list name="PER_NAME">
  <listHeader>
    <field name="PER_ID"></field>
    <field name="LAST_SEQ_NUM">0</field>
    <field name="moreRows">false</field>
    <field name="remainingRows">0</field>
    <field name="lastInfo"></field>
  </listHeader>
  <listBody action="A">
    <field name="ENTITY_NAME_UPR"></field>
    <field name="PER_ID"></field>
    <field name="SEQ_NUM">0</field>
    <field name="ENTITY_NAME">Sanity,48173</field>
    <field name="NAME_TYPE_FLG">PRIM</field>
    <field name="VERSION">0</field>
    <field name="PRIM_NAME_SW">false</field>
  </listBody>
</list>
<list name="PER_CHAR">
  <listHeader>
    <field name="PER_ID"></field>
    <field name="LAST_CHAR_TYPE_CD"></field>
    <field name="LAST_EFFDT"></field>
    <field name="moreRows">false</field>
    <field name="remainingRows">0</field>
    <field name="lastInfo"></field>
  </listHeader>
  <listBody action="A">

```

4. Navigate to the Business Object or Business Service look up window for the requisite field.

Example: In the figure below, ENTITY_NAME is named as entityName.



5. In the flow, search for the requisite field and enter the component test data.

WS-SETXMLLISTELEMNT			uppercaseEntityName	☐	
WS-SETXMLLISTELEMNT			personId	☐	
WS-SETXMLLISTELEMNT			sequence	☐	
WS-SETXMLLISTELEMNT			entityName	☐	Sanity.UserTesting3
WS-SETXMLLISTELEMNT			nameType	☐	PRIM
WS-SETXMLLISTELEMNT			version	☐	
WS-SETXMLLISTELEMNT			isPrimaryName	☐	

6. Click **Save** to save the test data.


IE Development Tool Bar

The IE Development tool bar, available in IE11, enables users to inspect the page and its field mapping. It is on a 1:1 basis, meaning one inspect = one field.


To enter test data in the requisite fields using the IE Development tool bar, follow these steps:

1. Login to Oracle Utilities Customer Care and Billing Cloud Service using Internet Explorer 11.
2. Navigate to the page where the requisite field needs to be updated with data.


Example: The figure below shows the Account page where the **Characteristic Value** field on the **Characteristics** tab needs to be updated.



3. Press **F12**. The browser displays the F12 developer tools that help in building and debugging web pages.




- On the F12 tools menu, select the **DOM Explorer** tab and click the **Select element** icon.



- On the application page, click the field for which you need to enter the data. The DOM Explorer shows the HTML for the selected field.

Example: Click the **Characteristic Value** field on the **Account** page. The DOM Explorer shows the **ID** of that field.



- On the object lookup window, search the requisite field.

Example: Search for CHAR_VAL_FK1.

```

<version dataType="number" mapField="VERSION"/>
</accountAlert>
<accountAutopay type="list" mapChild="CI_ACCT_APAY">
  <accountAutoPayId mapField="ACCT_APAY_ID"/>
  <accountId mapField="ACCT_ID"/>
  <startDate dataType="date" mapField="START_DT"/>
  <endDate dataType="date" mapField="END_DT"/>
  <autopaySource mapField="APAY_SRC_CD"/>
  <externalAccountId mapField="EXT_ACCT_ID"/>
  <expireDate dataType="date" mapField="EXPIRE_DT"/>
  <entityName mapField="ENTITY_NAME"/>
  <comments mapField="COMMENTS"/>
  <version dataType="number" mapField="VERSION"/>
  <autopayMaxWithdrawalAmount dataType="money" mapField="APAY_MAX_WDRWL_AMT"/>
  <autoPayMethod dataType="lookup" mapField="APAY_METHOD_FLG" lookup="APAY_METHOD_FLG"/>
  <encryptedExternalAccountId mapField="ENCR_EXT_ACCT_ID"/>
</accountAutopay>
<accountCharacteristic type="list" mapChild="CI_ACCT_CHAR">
  <accountId mapField="ACCT_ID"/>
  <characteristicType mapField="CHAR_TYPE_CD"/>
  <effectiveDate dataType="date" mapField="EFFDT"/>
  <characteristicValue mapField="CHAR_VAL"/>
  <adhocCharacteristicValue mapField="ADHOC_CHAR_VAL"/>
  <version dataType="number" mapField="VERSION"/>
  <characteristicValueForeignKey1 mapField="CHAR_VAL_FK1"/>
  <characteristicValueFK2 mapField="CHAR_VAL_FK2"/>
  <characteristicValueFK3 mapField="CHAR_VAL_FK3"/>
  <characteristicValueFK4 mapField="CHAR_VAL_FK4"/>
  <characteristicValueFK5 mapField="CHAR_VAL_FK5"/>
  <searchCharacteristicValue mapField="SRCH_CHAR_VAL"/>
</accountCharacteristic>
<accountMessage type="list" mapChild="CI_ACCT_MSG">
  <accountId mapField="ACCT_ID"/>

```

7. In the flow, add the necessary data into the field.

WS-SETXMLELEMENT			characteristicValue	2047163110
WS-SETXMLELEMENT			adhocCharacteristic...	
WS-SETXMLELEMENT			version	
WS-SETXMLELEMENT			characteristicValueF...	
WS-SETXMLELEMENT			characteristicValueFK2	
WS-SETXMLELEMENT			characteristicValueFK3	
WS-SETXMLELEMENT			characteristicValueFk4	
WS-SETXMLELEMENT			characteristicValueFK5	

8. Click **Save** to save the data.

SOAP UI

This method is an alternative to the other methods mentioned above if the user is familiar with SOAP UI.

To identify the requisite fields using SOAP UI:


1. Login to the Oracle Utilities Customer Care and Billing Cloud Service application.
2. Navigate to the page where the test data has to added. Add the data in the respective fields.

Example: The figure below shows the **Case** page where **Characteristics Type** and **Characteristic Value** are added in the **Characteristics** section.

The screenshot displays the 'Case' page in the Oracle Utilities Customer Care and Billing Cloud Service application. The page includes a navigation bar at the top with links for Home, Menu, Admin, History, Control Central, and Account Information. Below the navigation bar, there are tabs for 'Main', 'Case Portal', and 'Log'. The 'Main' tab is selected, showing case details for 'TEST CASE INFO' with status 'STATUS A'. The 'Characteristics' section at the bottom contains a table with three rows:

Characteristic Type	Characteristic Value
Short comment	TEST CHARTYPE INFO
Bill Amount	100
Callback Date / Time	01-01-2008-00:01:00

3. On the SOAP UI, perform a Read using the data that has been added on the **Case** page (in step 2). The result is displayed in the right pane.



- Copy the values and paste them in the respective fields on the flow.

Example: COMMENT and TEST CHARTYPE INFO are the values for characteristicType and adhocCharacteristicValue fields.

Note: Not all fields populated on the SOAP response needs to be populated on the flow. (Example: version, info, other type of description, etc).

WS-SETXMLLISTELEMENT			Add	caseCharacteristic	
WS-SETXMLLISTELEMENT				toDoCaseId	
WS-SETXMLLISTELEMENT				characteristicType	COMMENT
WS-SETXMLLISTELEMENT				sequence	1
WS-SETXMLLISTELEMENT				searchCharacteristicValue	
WS-SETXMLLISTELEMENT				characteristicValueF5	
WS-SETXMLLISTELEMENT				characteristicValueF4	
WS-SETXMLLISTELEMENT				characteristicValueF3	
WS-SETXMLLISTELEMENT				characteristicValueF2	
WS-SETXMLLISTELEMENT				characteristicValueForei...	
WS-SETXMLLISTELEMENT				adhocCharacteristicValue	TEST CHARTYPE INFO
WS-SETXMLLISTELEMENT				characteristicValue	
WS-SETXMLLISTELEMENT				version	

- Click **Save**.