

Oracle® Banking Trade Finance Products Database Practices Db 19c



Release 14.8.2.0.0

G50979-02

April 2026

The Oracle logo, consisting of a solid red square with the word "ORACLE" in white, uppercase, sans-serif font centered within it.

ORACLE®

Oracle Banking Trade Finance Products Database Practices Db 19c, Release 14.8.2.0.0

G50979-02

Copyright © 2007, 2026, Oracle and/or its affiliates.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this is software, software documentation, data (as defined in the Federal Acquisition Regulation), or related documentation that is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, then the following notice is applicable:

U.S. GOVERNMENT END USERS: Oracle programs (including any operating system, integrated software, any programs embedded, installed, or activated on delivered hardware, and modifications of such programs) and Oracle computer documentation or other Oracle data delivered to or accessed by U.S. Government end users are "commercial computer software," "commercial computer software documentation," or "limited rights data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, reproduction, duplication, release, display, disclosure, modification, preparation of derivative works, and/or adaptation of i) Oracle programs (including any operating system, integrated software, any programs embedded, installed, or activated on delivered hardware, and modifications of such programs), ii) Oracle computer documentation and/or iii) other Oracle data, is subject to the rights and limitations specified in the license contained in the applicable contract. The terms governing the U.S. Government's use of Oracle cloud services are defined by the applicable contract for such services. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

Oracle®, Java, MySQL, and NetSuite are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Inside are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. AMD, Epyc, and the AMD logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark of The Open Group.

This software or hardware and documentation may provide access to or information about content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services unless otherwise set forth in an applicable agreement between you and Oracle. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services, except as set forth in an applicable agreement between you and Oracle.

Contents

Preface

Purpose	i
Audience	i
Documentation Accessibility	i
Critical Patches	i
Diversity and Inclusion	i
Conventions	ii
Related Resources	ii
Screenshot Disclaimer	ii

1 Introduction

2 Database Initialization Parameters

2.1	ALLOW_LEVEL_WITHOUT_CONNECT_BY	1
2.2	LM_RES_HASH_BUCKET	2
2.3	CURSOR_SHARING	2
2.4	DB_CACHE_ADVICE	2
2.5	FAST_START_MTTR_TARGET	3
2.6	JOB_QUEUE_PROCESSES	3
2.7	LOG_BUFFER	3
2.8	MEMORY_TARGET/MEMORY_MAX_TARGET	3
2.9	NLS_DATE_FORMAT	4
2.10	OPEN_CURSORS	4
2.11	OPTIMIZER_DYNAMIC_SAMPLING	4
2.12	OPTIMIZER_INDEX_CACHING	5
2.13	OPTIMIZER_INDEX_COST_ADJ	5
2.14	PARALLEL_MAX_SERVERS	5
2.15	PGA_AGGREGATE_LIMIT	6
2.16	PLSQL_CODE_TYPE	6
2.17	PROCESSES	6
2.18	REMOTE_DEPENDENCIES_MODE	7
2.19	SESSION_CACHED_CURSORS	7

2.20	SKIP_UNUSABLE_INDEXES	7
2.21	UNDO_RETENTION	8
3	Redo Log Files	
4	PLSQL Optimizer Level	
5	Statistics Collection for Oracle Banking Trade Finance Schema (Recommended Method)	
5.1	Customizing Default Statistics Collection Schedule	1
5.2	Customizing Statistics Gathering for FLECUBE	3
5.2.1	Statistics Histograms	3
6	Oracle Banking Trade Finance Database Storage Recommendations	
6.1	Key benefits of ASM	1
7	Oracle Banking Trade Finance Database Backup Recommendations	
7.1	RMAN Vs Conventional Backup	1
7.2	Benefits of Using RMAN	2
7.3	Backup Strategy Recommendation	2
8	Known Issues	
9	Known Issues	
9.1	Script to Check Histograms on Oracle Banking Trade Finance Schema	1
9.2	Script to Remove Histograms on Oracle Banking Trade Finance Schema	1

Preface

- [Purpose](#)
- [Audience](#)
- [Documentation Accessibility](#)
- [Critical Patches](#)
- [Diversity and Inclusion](#)
- [Conventions](#)
- [Related Resources](#)
- [Screenshot Disclaimer](#)

Purpose

This guide helps the user to define standard database initialization parameters that have been derived after performing the required benchmark tests (Performance Load tests).

Audience

This guide is intended for anyone responsible for installing Oracle Banking Application.

Documentation Accessibility

For information about Oracle's commitment to accessibility, visit the Oracle Accessibility Program website at <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=docacc>.

Access to Oracle Support

Oracle customer access to and use of Oracle support services will be pursuant to the terms and conditions specified in their Oracle order for the applicable services.

Critical Patches

Oracle advises customers to get all their security vulnerability information from the Oracle Critical Patch Update Advisory, which is available at [Critical Patches, Security Alerts and Bulletins](#). All critical patches should be applied in a timely manner to ensure effective security, as strongly recommended by [Oracle Software Security Assurance](#).

Diversity and Inclusion

Oracle is fully committed to diversity and inclusion. Oracle respects and values having a diverse workforce that increases thought leadership and innovation. As part of our initiative to

build a more inclusive culture that positively impacts our employees, customers, and partners, we are working to remove insensitive terms from our products and documentation. We are also mindful of the necessity to maintain compatibility with our customers' existing technologies and the need to ensure continuity of service as Oracle's offerings and industry standards evolve. Because of these technical constraints, our effort to remove insensitive terms is ongoing and will take time and external cooperation.

Conventions

The following text conventions are used in this document:

Convention	Meaning
boldface	Boldface type indicates graphical user interface elements associated with an action, or terms defined in text.
<i>italic</i>	Italic type indicates book titles, emphasis, or placeholder variables for which you supply particular values.
monospace	Monospace type indicates commands within a paragraph, URLs, code in examples, text that appears on the screen, or text that you enter.

Related Resources

For more information, see these Oracle Banking Trade Finance resources:

- [Oracle Banking Trade Finance Release Notes](#)
- [Oracle Banking Trade Finance Install & Upgrade](#)

Screenshot Disclaimer

Personal information used in the interface or documents is dummy and does not exist in the real world. It is only for reference purposes.

1

Introduction

This document details the database setting which is common across all the Oracle Banking Trade Finance products which include Oracle Banking Trade Finance Solution, Oracle Banking Payments, Oracle Banking Trade Finance Enterprise Limits and Collateral Management, Oracle Banking Trade Finance Investor Servicing, Oracle Banking Corporate Lending, Oracle Banking Trade Finance Process Management and Oracle Banking Treasury Management.

For product related database setting, please refer to the product specific database best practice document as well.

2

Database Initialization Parameters

Oracle standard database initialization parameters have been derived after performing the required benchmark tests (Performance Load tests). We recommend installing Oracle Banking Trade Finance in Pluggable database and few of these parameters need to be set at PDB level.

Note

Since some of the initialization parameters values are specific to customer volume, parameters should be derived using **Oracle Banking Trade Finance -Disk-Layouts-initparams-19c.xlsx** excel sheet baselined along with this document.

- [ALLOW_LEVEL_WITHOUT_CONNECT_BY](#)
- [LM_RES_HASH_BUCKET](#)
- [CURSOR_SHARING](#)
- [DB_CACHE_ADVICE](#)
- [FAST_START_MTTR_TARGET](#)
- [JOB_QUEUE_PROCESSES](#)
- [LOG_BUFFER](#)
- [MEMORY_TARGET/MEMORY_MAX_TARGET](#)
- [NLS_DATE_FORMAT](#)
- [OPEN_CURSORS](#)
- [OPTIMIZER_DYNAMIC_SAMPLING](#)
- [OPTIMIZER_INDEX_CACHING](#)
- [OPTIMIZER_INDEX_COST_ADJ](#)
- [PARALLEL_MAX_SERVERS](#)
- [PGA_AGGREGATE_LIMIT](#)
- [PLSQL_CODE_TYPE](#)
- [PROCESSES](#)
- [REMOTE_DEPENDENCIES_MODE](#)
- [SESSION_CACHED_CURSORS](#)
- [SKIP_UNUSABLE_INDEXES](#)
- [UNDO_RETENTION](#)

2.1 [ALLOW_LEVEL_WITHOUT_CONNECT_BY](#)

Recommended Value: TRUE

This parameter is set to avoid following error,

- After Upgrading To Oracle 10g, Getting ORA-01788 When Running A Query That Includes The LEVEL Pseudo Column [ID 455953.1]

2.2 LM_RES_HASH_BUCKET

Recommended Value: 8192

To avoid "LATCH: GES RESOURCE HASH LIST" waits in 19c RAC environment, we need to set this parameter.

2.3 CURSOR_SHARING

Determines what kind of SQL statements can share the same cursors.

Property	Description
Parameter type	String
Default value	EXACT
Recommended Value	Force

Oracle Banking Trade Finance relevance

Some of the Oracle Banking Trade Finance sql statements are generated dynamically. So they contain literal values in the WHERE clause conditions. This results in large numbers of nearly identical statements with separate parse trees in Oracle's library cache, which can slow performance and cause latch problems.

By setting cursor_sharing to FORCE database convert literals to bind variables before parsing the statement.

2.4 DB_CACHE_ADVICE

This enables or disables statistics gathering used for predicting behavior with different cache sizes through the V\$DB_CACHE_ADVICE performance view.

Property	Description
Parameter type	String
Syntax	DB_CACHE_ADVICE = { ON READY OFF }
Default value	If STATISTICS_LEVEL is set to TYPICAL / ALL, then ON If STATISTICS_LEVEL is set to BASIC, then OFF
Recommended Value	OFF (Should be ON while Performance Monitoring)

Oracle Banking Trade Finance relevance

Turning ON advisory will have an extra overhead. Please note it should be ON, only during performance monitoring.

2.5 FAST_START_MTTR_TARGET

This enables you to specify the number of seconds the database takes to perform crash recovery of a single instance. When specified, FAST_START_MTTR_TARGET is overridden by LOG_CHECKPOINT_INTERVAL.

Property	Description
Parameter type	Integer
Default value	0
Range of values	0 to 3600 seconds
Recommended Values	300

Oracle Banking Trade Finance relevance

If FAST_START_MTTR_TARGET is not set to 300 then run time performance for write/redo generation intensive workloads will not be optimized. This will reduce checkpoint writes from DBWR processes, making more room for LGWR IO. To optimize run time performance for write/redo generation intensive workloads, increase the FAST_START_MTTR_TARGET initialization parameter to 300.

2.6 JOB_QUEUE_PROCESSES

This specifies the maximum number of processes that can be created for the execution of jobs. It specifies the number of job queue processes per instance (J000, J999).

Property	Description
Parameter type	Integer
Default value	4000
Range of values	0 to 1000
Recommended Values	Refer Oracle Banking Trade Finance -Disk-Layouts-initparams-19c.xlsx

Oracle Banking Trade Finance relevance

This parameter has to be set with respect to the maximum number of scheduler jobs. To arrive at the right value, refer Oracle Banking Trade Finance-Disk-Layouts-initparams-19c.xlsx excel.

2.7 LOG_BUFFER

Recommended Value: Refer **Oracle Banking Trade Finance -Disk-Layouts-initparams-19c.xlsx**

Oracle Banking Trade Finance relevance

The default log buffer size is too small as Oracle Banking Trade Finance performs heavy DML during batch processing.

2.8 MEMORY_TARGET/MEMORY_MAX_TARGET

Recommended Value: Refer **Oracle Banking Trade Finance-Disk-Layouts-initparams-19c.xlsx**.

For linux systems, make sure that the value of operating system /dev/shm mount is set to appropriate value to accommodate memory_target.

2.9 NLS_DATE_FORMAT

This specifies the default date format to use with the TO_CHAR and TO_DATE functions.

Property	Description
Parameter type	String
Syntax	NLS_DATE_FORMAT = "format"
Default value	Derived from NLS_TERRITORY
Recommended Values	DD-MON-RRRR

Oracle Banking Trade Finance relevance

Oracle Banking Trade Finance standard date format.

2.10 OPEN_CURSORS

This specifies the maximum number of open cursors (handles to private SQL areas) a session can have at once. You can use this parameter to prevent a session from opening an excessive number of cursors.

Property	Description
Parameter type	Integer
Default value	50
Modifiable	ALTER SYSTEM
Range of values	1 to 4294967295 (4 GB -1)
Recommended Values	5000

Oracle Banking Trade Finance relevance

It is important to set the value of OPEN_CURSORS high enough to prevent Oracle Banking Trade Finance application from running out of open cursors (ORA-01000: maximum open cursors exceeded).

2.11 OPTIMIZER_DYNAMIC_SAMPLING

This controls the level of dynamic sampling performed by the optimizer.

Property	Description
Parameter type	Integer
Default value	If OPTIMIZER_FEATURES_ENABLE is set to 10.0.0 or higher, then 2 If OPTIMIZER_FEATURES_ENABLE is set to 9.2.0, then 1 If OPTIMIZER_FEATURES_ENABLE is set to 9.0.1 or lower, then 0
Recommended Values	1
Range of values	0 to 10

Oracle Banking Trade Finance relevance

Dynamic Sampling is a method of gathering additional statistics during optimization by recursively sampling statements. When dynamic sampling is enabled, queries are recursively generated by Oracle to test various selectivity based upon real values in order to improve their accuracy. This can result in the production of better explain plans.

Value 1 Sample all tables that have not been analyzed that meet certain criteria.

2.12 OPTIMIZER_INDEX_CACHING

This lets you adjust the behavior of cost-based optimization to favor nested loops joins and IN-list iterators.

Property	Description
Parameter type	Integer
Default value	0
Recommended Values	90
Range of values	0 to 100

Oracle Banking Trade Finance relevance

The cost of executing an index using IN-list iterators or of executing nested loops join when an index is used to access the inner table depends on the caching of that index in the buffer cache. Oracle Banking Trade Finance favors nested loop joins by setting optimizer_index_caching to 90.

2.13 OPTIMIZER_INDEX_COST_ADJ

This lets you tune optimizer behavior for access path selection to be more or less index friendly - that is, to make the optimizer more or less prone to selecting an index access path over a full table scan.

Property	Description
Parameter type	Integer
Default value	100
Recommended Values	50
Range of values	1 to 10000

Oracle Banking Trade Finance relevance

Oracle Banking Trade Finance favors index read over full table scan as it is very useful when optimizer favors to give a lower cost to index scans over full-table scans.

2.14 PARALLEL_MAX_SERVERS

This specifies the maximum number of parallel execution processes and parallel recovery processes for an instance. As demand increases, Oracle Database increases the number of processes from the number created at instance startup up to this value.

Property	Description
Parameter type	Integer

Property	Description
Default value	Derived from the values of CPU_COUNT, PARALLEL_THREADS_PER_CPU, and PGA_AGGREGATE_TARGET
Recommended Values	Refer Oracle Banking Trade Finance-Disk-Layouts-initparams-19c.xlsx
Range of values	0 to 3600
Real Application Clusters	Multiple instances can have different values

Oracle Banking Trade Finance relevance

To arrive right value, refer **Oracle Banking Trade Finance-Disk-Layouts-initparams-19c.xlsx** excel.

2.15 PGA_AGGREGATE_LIMIT

Recommended Value: 0

Oracle Banking Trade Finance relevance

Setting this parameter limits the pga consumed by the instance, hence might cause failure to few of the running processes.

2.16 PLSQL_CODE_TYPE

This specifies the compilation mode of the PL/SQL units.

Property	Description
Parameter type	String
Default value	INTERPRETED
Recommended values	NATIVE
Range of values	INTERPRETED, NATIVE

Oracle Banking Trade Finance relevance

The PL SQL interpreter overhead will be minimal when set to NATIVE.

2.17 PROCESSES

This specifies the maximum number of operating system user processes that can simultaneously connect to Oracle. Its value should allow for all background processes such as locks, job queue processes, and parallel execution processes.

Property	Description
Parameter type	Integer
Default value	100
Range of values	6 to operating system dependent
Recommended values	Refer Oracle Banking Trade Finance-Disk-Layouts-initparams-19c.xlsx

Oracle Banking Trade Finance relevance

This parameter can set be set with respect to maximum no of sessions connected to DB.

2.18 REMOTE_DEPENDENCIES_MODE

Specifies how Oracle should handle dependencies upon remote PL/SQL stored procedures.

Property	Description
Parameter type	String
Syntax	REMOTE_DEPENDENCIES_MODE = { TIMESTAMP SIGNATURE }
Default value	TIMESTAMP
Recommended values	SIGNATURE

Oracle Banking Trade Finance relevance

Oracle allows the procedure to execute as long as the signatures are considered safe. This setting allows client PL/SQL applications to be run without recompilation.

2.19 SESSION_CACHED_CURSORS

Specifies the number of session cursors to cache. Repeated parse calls of the same SQL statement cause the session cursor for that statement to be moved into the session cursor cache. Subsequent parse calls will find the cursor in the cache and do not need to reopen the cursor. Oracle uses a least recently used algorithm to remove entries in the session cursor cache to make room for new entries when needed.

Property	Description
Parameter type	Integer
Default value	50
Recommended values	400
Range of values	0 to operating system-dependent

Oracle Banking Trade Finance relevance

This helps to cache the cursor thus avoid parsing of the cursor which heavy CPU intensive particularly in batch.

2.20 SKIP_UNUSABLE_INDEXES

Enables or disables the use and reporting of tables with unusable indexes or index partitions.

Property	Description
Parameter type	Boolean
Default value	True
Recommended values	FALSE
Range of values	true / false

Oracle Banking Trade Finance relevance

TRUE enables error reporting of indexes marked UNUSABLE. This setting does not allow inserts, deletes, and updates on tables with unusable indexes or index partitions. IT is set to false because Oracle Banking Trade Finance application should throw error if any of the indexes become UNUSABLE.

2.21 UNDO_RETENTION

This specifies (in seconds) the low threshold value of undo retention. For AUTOEXTEND undo tablespaces, the system retains undo for at least the time specified in this parameter, and automatically tunes the undo retention period to satisfy the undo requirements of the queries. For fixed- size undo tablespaces, the system automatically tunes for the maximum possible undo retention period, based on undo tablespace size and usage history, and ignores UNDO_RETENTION unless retention guarantee is enabled.

The UNDO_RETENTION parameter can only be honored if the current undo tablespace has enough space. If an active transaction requires undo space and the undo tablespace does not have available space, then the system starts reusing unexpired undo space. This action can potentially cause some queries to fail with a "snapshot too old" message.

Property	Description
Parameter type	Integer
Default value	900
Range of values	0 to 231 – 1
Recommended values	1800

Oracle Banking Trade Finance relevance

Increased value along with automatic undo management helps to avoid “snapshot too old error”.

3

Redo Log Files

The default number of redo log files groups and its size is inadequate to run Oracle Banking Trade Finance. Hence, the recommended are:

- 6 redo log groups
- Redo log file size
 - 1 GB each for the DB size up to 1 TB
 - 2 GB each for DB size more than 1 TB

4

PLSQL Optimizer Level

The `plsql_optimize_level` value for all the pl/sql units should be same which would be the value set in `plsql_optimize_level` init parameter.

Following sql gives the PLSQL optimizer level for Oracle Banking Trade Finance schema plsql units:

```
Select PLSQL_OPTIMIZE_LEVEL,type,count(*) "Count" from user_plsql_object_settings group by PLSQL_OPTIMIZE_LEVEL,type;
```

PLSQL_OPTIMIZE_LEVEL for all the objects should be same which should be value set in `plsql_optimize_level` init parameter. If there is a difference then the objects should be recompiled. This can be done using `dbms_utility.compile_schema` procedure.

E.g.: - `exec dbms_utility.compile_schema('FCCBM2')`

Here, 'FCCBM2' refers to the Oracle Banking Trade Finance schema.

Note

The '`dbms_utility.compile_schema`' procedure invalidates and recompiles all the plsql units.

5

Statistics Collection for Oracle Banking Trade Finance Schema (Recommended Method)

Oracle 19c provides a default scheduled job to collect statistics for the entire database and is default scheduled to run every night. Given that the Oracle Banking Trade Finance batch as well runs in the night it is critical that the statistics gathering is not run during the batch.

It is recommended to use the default database scheduled job that is shipped with Oracle Database to collect statistics for Oracle Banking Trade Finance Schema.

Statistics collection recommendation is specific to Oracle Banking Trade Finance schema. Other available statistics like System statistics, Fixed table statistics, dictionary statistics, etc. are not part of this recommendation and are required to be executed on need basis.

Note

This document assumes that there is no other tool or a program is scheduled to collect statistics for the Database.

- [Customizing Default Statistics Collection Schedule](#)
- [Customizing Statistics Gathering for FLECUBE](#)

5.1 Customizing Default Statistics Collection Schedule

The Default Scheduler is to be customized for the following:

- Ensure that the default statistics gathering program is configured and Running.
SELECT STATUS
FROM DBA_AUTOTASK_CLIENT
WHERE CLIENT_NAME='auto optimizer stats collection';
Should return - ENABLED
- Ensure that the default statistics gathering program is configured to run only on weekends.
/* Start of Script – Script to be executed as SYS*/
BEGIN
DBMS_AUTO_TASK_ADMIN.ENABLE(
CLIENT_NAME => 'auto optimizer stats collection',
OPERATION => NULL,
WINDOW_NAME => 'SATURDAY_WINDOW');
DBMS_AUTO_TASK_ADMIN.ENABLE(
CLIENT_NAME => 'auto optimizer stats collection',
OPERATION => NULL,

```

WINDOW_NAME => 'SUNDAY_WINDOW');
END;
/
/* End of Script */

```

- Default schedule is daily. So disable the daily schedules for optimizer statistics.
/* Start of Script – Script to be executed as SYS*/

```

BEGIN
DBMS_AUTO_TASK_ADMIN.DISABLE(
CLIENT_NAME => 'auto optimizer stats collection',
OPERATION => NULL,
WINDOW_NAME => 'MONDAY_WINDOW');
DBMS_AUTO_TASK_ADMIN.DISABLE(
CLIENT_NAME => 'auto optimizer stats collection',
OPERATION => NULL,
WINDOW_NAME => 'TUESDAY_WINDOW');
DBMS_AUTO_TASK_ADMIN.DISABLE(
CLIENT_NAME => 'auto optimizer stats collection',
OPERATION => NULL,
WINDOW_NAME => 'WEDNESDAY_WINDOW');
DBMS_AUTO_TASK_ADMIN.DISABLE(
CLIENT_NAME => 'auto optimizer stats collection',
OPERATION => NULL,
WINDOW_NAME => 'THURSDAY_WINDOW');
DBMS_AUTO_TASK_ADMIN.DISABLE(
CLIENT_NAME => 'auto optimizer stats collection',
OPERATION => NULL,
WINDOW_NAME => 'FRIDAY_WINDOW');
END;
/
/* End of Script */

```

Verify the setup using the following SQL

```

SELECT WINDOW_NAME,OPTIMIZER_STATS
FROM DBA_AUTOTASK_WINDOW_CLIENTS;

```

Should return

```

MONDAY_WINDOW DISABLED
TUESDAY_WINDOW DISABLED
WEDNESDAY_WINDOW DISABLED
THURSDAY_WINDOW DISABLED

```

```
FRIDAY_WINDOW DISABLED
SATURDAY_WINDOW ENABLED
SUNDAY_WINDOW ENABLED
```

5.2 Customizing Statistics Gathering for FLECUBE

The default statistics gathering is designed to be generic. It is recommended to customize the default statistics gathering to suit Oracle Banking Trade Finance online and batch.

Following are the areas that would need customization for Oracle Banking Trade Finance:

- Statistics Histograms
- [Statistics Histograms](#)

5.2.1 Statistics Histograms

Note the following:

- The default statistics gathering routine decides to collect histograms on specific tables based on certain criteria that are not documented.
- Statistics Histograms are not recommended for Oracle Banking Trade Finance tables.

Configure the default statistics gathered without Histograms.

```
/* Start of Script – Script to be executed as SYS*/
```

```
BEGIN
```

```
DBMS_STATS.SET_PARAM ('METHOD_OPT','FOR ALL COLUMNS SIZE 1');
```

```
END;
```

```
/
```

```
/*End of Script */
```

Verify the setup using

```
SELECT DBMS_STATS.GET_PARAM ('METHOD_OPT') FROM DUAL;
```

Should return

```
FOR ALL COLUMNS SIZE 1
```

6

Oracle Banking Trade Finance Database Storage Recommendations

Oracle database 10g release 2 onwards, Automatic Storage Management (ASM) is the recommended storage option for Oracle Banking Trade Finance database. ASM is an integrated cluster aware volume manager and a file system designed and optimized for managing Oracle database files. ASM is the realization of the Oracle Stripe and Mirror Everything (SAME) storage management methodology researched and established as best practices for Oracle database environment over many years.

Note

For configuring ASM refer Automatic storage management best practice document provided by Oracle for your database version.

- [Key benefits of ASM](#)

6.1 Key benefits of ASM

- I/O is spread evenly across all available disk drives to prevent hot spots and maximize performance.
- ASM eliminates the need for over provisioning and maximizes storage resource utilization facilitating database consolidation.
- Inherent large file support.
- Performs automatic online redistribution after the incremental addition or removal of storage capacity.
- Maintains redundant copies of data to provide high availability, or leverage 3rd party RAID functionality.
- Supports Oracle Database 19c as well as Oracle Real Application Clusters (RAC).
- Capable of leveraging 3rd party multipathing technologies.
- For simplicity and easier migration to ASM, an Oracle Database 19c database can contain ASM and non-ASM files. Any new files can be created as ASM files whilst existing files can also be migrated to ASM.
- RMAN commands enable non-ASM managed files to be relocated to an ASM disk group.
- Oracle Database 19c Enterprise Manager can be used to manage ASM disk and file management activities.

7

Oracle Banking Trade Finance Database Backup Recommendations

Backup Policy is a very important ingredient of any High Availability system. Oracle recommends RMAN utility for database backup.

RMAN is acronym for Recovery Manager, is Oracle utility which will backup, restore, and recover oracle data files. RMAN is an Oracle provided utility for efficiently performing Backup and Recovery. RMAN is available as a part of the standard Installation and no separate installation is required.

Recovery Manager is a client/server application that uses database server sessions to perform backup and recovery. It stores metadata about its operations in the control file of the target database and, optionally, in a recovery catalog schema in an Oracle database.

You can invoke RMAN as a command-line executable from the operating system prompt or use some RMAN features through the Enterprise Manager GUI.

- [RMAN Vs Conventional Backup](#)
- [Benefits of Using RMAN](#)
- [Backup Strategy Recommendation](#)

7.1 RMAN Vs Conventional Backup

- During a conventional hot backup, the amount of Redo generated during the backup would be more due to the fact that the redo logs during the hot backup store the entire block images rather than the change vectors.
- RMAN doesn't place the tablespace in a backup mode and hence the amount of Redo generated during the RMAN backup is considerably low.
- RMAN can identify block corruption during backup operations and RMAN supports Block recovery.
- RMAN automatically detects new data files and will backup them. Also, RMAN supports incremental backup method.
- RMAN backs up only the blocks that have been used at least once. Unused blocks are never backed up. Unused block here refers to the blocks where in the block header is zeroed
- RMAN enables us to test the backup without actually restoring the backup.
- RMAN can verify physical and logical structures of the database without actually performing backup.
- Usage of Shared Pool and Large Pool for RMAN
- RMAN uses DBMS_RCVMAN and DBMS_BACKUP_RESTORE packages for backup and recovery. These packages would be loaded in the shared pool for backup and restore operation. RMAN uses the PGA for backup and restore operation.
- RMAN Requires LARGE_POOL only if TAPE_IO_SLAVES and DBWR_IO_SLAVES are defined.

- **Sizing Large Pool** - $LARGE_POOL = (\text{Number of Channels}) * (16 \text{ MB} + \text{Tape Buffer})$

7.2 Benefits of Using RMAN

- RMAN is an intelligent tool that comes at no extra cost. It is available free with the Oracle Database.
- RMAN introduced in Oracle 8 it has become simpler with newer versions and easier than user managed backups.
- Provides proper security for Backups.
- You can be 100% sure your database has been backed up.
- Control file and Spfile of the database can be configured to be automatically backed up by RMAN.
- It contains detail of the backups taken etc. in its central repository Facility for testing validity of backups also commands like crosscheck to check the status of backup.
- Faster backups and restores compared to backups without RMAN.
- RMAN is the only native backup tool which supports incremental backups.
- Oracle 19c has got further optimized incremental backup which has resulted in improvement of performance during backup and recovery time.
- Parallel operations (Multiple Channels for Backup and Restore) are supported.
- Better querying facility for knowing different details of backup.
- No extra redo is generated when backup is performed, compared to conventional online backup.
- Maintains repository of backup metadata.
- Remembers backup set location.
- Knows what need to backed up.
- Knows what is required for recovery.
- Knows what backup are redundant.
- RMAN can back up the Database to Disk or directly to Tape. It is recommended that RMAN backup is performed to disk and then copied to tape.

7.3 Backup Strategy Recommendation

RMAN will not backup the below files so it is advised to take the copy of the below files on regular basis (weekly/any change/addition to the file).

- Tnsnames.ora
- Listener.ora
- Password file
- Init.ora

The Best practice is to take create the pfile once the spfile is updated.

Below is the recommended strategy.

8

Known Issues

After upgrading to Oracle database 19.6 from 19.3 base, pluggable database upon opening moves to restricted mode. This is a known issue. Oracle Support has released patch 30881407 for the same, which needs to be applied on top of 19.6.

9

Known Issues

After upgrading to Oracle database 19.6 from 19.3 base, pluggable database upon opening moves to restricted mode. This is a known issue. Oracle Support has released patch 30881407 for the same, which needs to be applied on top of 19.6.

- [Script to Check Histograms on Oracle Banking Trade Finance Schema](#)
- [Script to Remove Histograms on Oracle Banking Trade Finance Schema](#)

9.1 Script to Check Histograms on Oracle Banking Trade Finance Schema

Following script would have to be executed in the Oracle Banking Trade Finance schema:

```
select distinct table_name
from
(
select table_name from user_tab_columns where histogram!='NONE'
)
```

Should return **No Records**

9.2 Script to Remove Histograms on Oracle Banking Trade Finance Schema

Following script would have to be executed in the Oracle Banking Trade Finance schema if there are any rows:

```
declare
cursor cur_tables is
select distinct table_name
from
(
select table_name from user_tab_columns where histogram!='NONE'
);
begin
for rec_tables in cur_tables
loop
```

```
dbms_stats.gather_table_stats(ownname=>USER,tabname=>rec_tables.table_name,METHO  
D_OPT=>'FOR ALL COLUMNS SIZE  
1',CASCADE=>TRUE,DEGREE=>2,ESTIMATE_PERCENT=>NULL);  
end loop;  
end;
```