Oracle® Banking Collections and Recovery Installation Guide





Oracle Banking Collections and Recovery Installation Guide, Release 14.7.2.0.0

F93455-01

Copyright © 2023, Oracle and/or its affiliates.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this is software, software documentation, data (as defined in the Federal Acquisition Regulation), or related documentation that is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, then the following notice is applicable:

U.S. GOVERNMENT END USERS: Oracle programs (including any operating system, integrated software, any programs embedded, installed, or activated on delivered hardware, and modifications of such programs) and Oracle computer documentation or other Oracle data delivered to or accessed by U.S. Government end users are "commercial computer software," "commercial computer software documentation," or "limited rights data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, reproduction, duplication, release, display, disclosure, modification, preparation of derivative works, and/or adaptation of i) Oracle programs (including any operating system, integrated software, any programs embedded, installed, or activated on delivered hardware, and modifications of such programs), ii) Oracle computer documentation and/or iii) other Oracle data, is subject to the rights and limitations specified in the license contained in the applicable contract. The terms governing the U.S. Government's use of Oracle cloud services are defined by the applicable contract for such services. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

Oracle®, Java, MySQL and NetSuite are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Inside are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. AMD, Epyc, and the AMD logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark of The Open Group.

This software or hardware and documentation may provide access to or information about content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services unless otherwise set forth in an applicable agreement between you and Oracle. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services, except as set forth in an applicable agreement between you and Oracle.

Contents

		,
Audience Document	ration Accessibility	,
	and Inclusion	,
Related R		,
Conventio		V
Databa	se Setup	
Produc	t Installation Using Installer	
2.1 Prod	duct Setup	2-
2.1.1	Update Properties File	2-
2.1.2	Update Roles File	2-
2.1.3	Execute Installer Script	2-
Data So	ource Verification	
	ments Verification and Kafka Setup	
	<u> </u>	



8 Patchset Setup

8.1 Fc	oundation Setup Upgrade	8-1
8.1.1	1 Download Installer	8-1
8.1.2	2 Update Properties File	8-2
8.1.3	3 Update Roles File	8-4
8.2 Or	racle Banking Collections and Recovery Patch Installation	8-5
8.2.1	1 Update Properties File	8-6
8.2.2	2 Update Roles File	8-6
Troub	leshooting	
9.1 Tr	oubleshooting for OBMA Patch Installation	9-1
9.2 Tr	oubleshooting for plato-apigateway-router	9-1
Kafka	Related Details	
A.1 Ka	afka SSL Setup and Verification	A-1
A.2 Ka	afka Databags Update	A-5



Preface

This guide helps to install the Oracle Banking Collections and Recovery services on designated environment.

This guide facilitates you to install the following services in the specified sequence:

- 1. OBCR-ACTION-SERVICES
- 2. OBCR-ACTIVITY-SERVICES
- 3. OBCR-COMMON-SERVICES
- 4. OBCR-CORRESPONDENCE-SERVICES
- 5. OBCR-ENTITY-SERVICES
- 6. OBCR-NOTES-SERVICES
- 7. OBCR-PTP-SERVICES
- 8. OBCR-SEGMENTATION-SERVICES
- 9. OBCR-SEGMENT-MAINT-SERVICES
- 10. OBCR-STRATEGY-MAINT-SERVICES
- 11. OBCR-STRATEGY-SERVICES
- 12. OBCR-TASK-MAINT-SERVICES
- 13. OBCR-TASK-SERVICES
- 14. OBCR-USER-MANAGEMENT-SERVICES
- 15. OBCR-DASHBOARD-SERVICES



For the exact version to be installed, see section **System Requirements and Technology Stack** of *Oracle Banking Collections and Recovery Release Notes*.

User Interface

Follow the below steps to migrate from existing app-shell build to Foundation app-shell. The UI war is split into individual component server war files. All the component server war files should be deployed in the same managed server.

For app-shell and components server, deploy the war files mentioned below:

- app-shell
- cmc-component-server
- moc-component-server



sms-component-server

For Domain Specific component server, deploy the following war file:

- obcr-component-server
- Audience
- Documentation Accessibility
- Diversity and Inclusion
- Related Resources
- Conventions

Audience

This guide is intended for WebLogic admin or ops-web team who are responsible for installing the OFSS banking products.

Documentation Accessibility

For information about Oracle's commitment to accessibility, visit the Oracle Accessibility Program website at http://www.oracle.com/pls/topic/lookup?ctx=acc&id=docacc.

Access to Oracle Support

Oracle customers that have purchased support have access to electronic support through My Oracle Support. For information, visit http://www.oracle.com/pls/topic/lookup?ctx=acc&id=trs if you are hearing impaired.

Diversity and Inclusion

Oracle is fully committed to diversity and inclusion. Oracle respects and values having a diverse workforce that increases thought leadership and innovation. As part of our initiative to build a more inclusive culture that positively impacts our employees, customers, and partners, we are working to remove insensitive terms from our products and documentation. We are also mindful of the necessity to maintain compatibility with our customers' existing technologies and the need to ensure continuity of service as Oracle's offerings and industry standards evolve. Because of these technical constraints, our effort to remove insensitive terms is ongoing and will take time and external cooperation.

Related Resources

For more information, see these related Oracle resources:

- Oracle Banking Collections and Recovery Initial Setup Guide
- Oracle Banking Collections and Recovery Pre-Installation Guide



Conventions

The following text conventions are used in this document:

Convention	Meaning
Convention	wicaning
boldface	Boldface type indicates graphical user interface elements associated with an action, or terms defined in text or the glossary.
italic	Italic type indicates book titles, emphasis, or placeholder variables for which you supply particular values.
monospace	Monospace type indicates commands within a paragraph, URLs, code in examples, text that appears on the screen, or text that you enter.



1

Database Setup

This topic describes the database setup for Oracle Banking Collections and Recovery installation.

It is recommended to create a different schema for each application. The below setup is designed to work with the separate schema for each application.

Prerequisites

Before proceeding with the below setup, make sure that the required schemas are provided.



Product Installation Using Installer

This topic describes the information for Oracle Banking Collections and Recovery installation using Installer.

Prerequisites

Before proceeding with the installation setup, make sure that the database installation is completed and the required schemas are created.

Installer Path

You can download the installer from Oracle Software Delivery Cloud (OSDC). The following table provides the download path of the installer.

Table 2-1 Installer Path

Application	Archive Name	OSDC Path
OBMA Installer	obma.zip	INSTALLER/
OBCR Installer	obcr.zip	INSTALLER/



To install OBMA foundation using Installer, refer to *Oracle Banking Microservices Architecture Installer Guide.* To install Oracle Banking Collections and Recovery product using Installer, refer to the below steps.

Product Setup

2.1 Product Setup

Please perform the steps mentioned in chapter Download and Setup Installer of Oracle Banking Microservices Architecture Installer Guide. Post completion of Download and Setup Installer tasks for VM identified for Product Setup, perform the below mentioned configurations.

- · Update Properties File
- · Update Roles File
- Execute Installer Script

2.1.1 Update Properties File

To update properties file:

- 1. Navigate to the path /scratch/obma installer/chef-repo/.
- 2. Open the respective product properties file. Here, we will update obcr properties.rb with details as explained in further steps.
- 3. Update the local user and its group.

Figure 2-1 Update Local User and Group

```
#Standard Values
INSTALL_USER = "obedmqa"
INSTALL GROUP = "dba"

USER_ROOT = "root"
GROUP_ROOT = "root"
INSTALL_BASE_DIR = "/scratch"
EXTRACT_LOC = "/scratch/extract"
```

4. Verify the version of java, update if required, and ensure the same version is available in the software's directory.

Figure 2-2 Verify Java Version

```
#Java Installation Details

JAVA_INSTALLER_SOURCE = "filesystem"

JAVA_INSTALLER_PATH = "/java/"

JAVA_INSTALLATION_DIR = INSTALL_BASE_DIR + "/obma"

JAVA_VERSION = "11.0"

JDK_INSTALLER_VERSION = "jdk-11.0.16"

JDK_INSTALLER_FILE = "jdk-11.0.16_linux-x64_bin.tar.gz"

CERTS_DIRNAME = INSTALL_BASE_DIR + "/ssl/cacerts"
```

5. Verify the version of weblogic server, update if required, and ensure the same version is available in the software's directory.

Figure 2-3 Verify Weblogic Server Version

```
#Weblogic Infra Installation Details
ORACLE_INVENTORY = "/scratch/app/oraInventory"
WLS_VERSION = "14.1.1"
WLS_INSTALLER_SOURCE = "filesystem"
WLS_INSTALLER_PATH = "/wls/"
WLS_PACKAGE_BASENAME = "fmw_14.1.1.0.0_wls.jar"
WLS_INSTALLER_FILE = "fmw_14.1.1.0.0_wls_Diskl_lof1.zip"
WLS_INSTALLER_FILE = "fmw_14.1.1.0.0_wls_Diskl_lof1.zip"
WLS_INSTALL_DIR = INSTALL_BASE_DIR + "/obma/fmw"
WLS_INSTALLER_TYPE = 'Complete with Examples'
```

Update the OBMA Foundation hostname and verify various ports, and update if required.

Figure 2-4 Update OBMA Foundation Host Name and Verify Ports

```
#Product specific parameters
PROTOCOL = "https"
PLATO_HOST = "ofss-mum-2057.snbomprshared1.gbucdsint02bom.oraclevcn.com"
PLATO_CONFIG_PORT = "8002"
DISCOVERY_PORT = "8004"
API_GATEWAY_PORT = "8006"
SMS_PORT = "8026"
```

7. For Oracle Banking Collections and Recovery, the default servers and their ports are already defined. Any new addition of server or datasource details needs to be appended here under "OBCR Flyway Placeholder Details".



Snapshot of Oracle Banking Collections and Recovery Configuration Details is given for reference.

Figure 2-5 Flyway Placeholder

```
# OBCR FLYWAY PLACEHOLDER DETAILS
# OBCR Server Ports Details
OBCR1 MAN SERVER LISTEN PORT = "8501"
OBCR1 MAN SERVER SSL PORT = "8502"
OBCR2 MAN SERVER LISTEN PORT = "8503"
OBCR2 MAN SERVER SSL PORT = "8504"
#OBCR CR ACTIVITY Datasource Details
CR_ACTIVITY_SCHEMA = "CR ACTIVITY"
CR_ACTIVITY_JNDI = "jdbc/CR_ACTIVITY"
CR ACTIVITY DS TARGET = "obcr cluster1, obcr cluster2"
#OBCR CR ACTION Datasource Details
CR ACTION SCHEMA = "CR ACTION"
CR ACTION JNDI = "jdbc/CR ACTION"
CR ACTION DS TARGET = "obcr cluster1"
#OBCR CR CMN Datasource Details
CR CMN SCHEMA = "CR CMN"
CR CMN JNDI = "jdbc/CR CMN"
CR CMN DS TARGET = "obcr cluster1"
#OBCR CR_ENTITY Datasource Details
CR ENTITY SCHEMA = "CR ENTITY"
CR ENTITY JNDI = "jdbc/CR ENTITY"
CR_ENTITY_DS_TARGET = "obcr_cluster1"
```



Note:

The password for all the default schema's is "wlcome1". In case, there is change in the password for the schemas, user needs to update the same in databag. For more information, see section Password Update in Databag of Oracle Banking Microservices Architecture Installer Guide.

8. Update the database details under "#Database details for weblogic datasource configuration".

Figure 2-6 Update Database Details

```
#DB TNS details for weblogic datasource configuration

ORACLE PDB_SID = "PDB1335A"

ORACLE PDB_HOSTNAME = "ofss-mum-2995.snbomprshared1.gbucdsint02bom.oraclevcn.com"

ORACLE_PDB_PORT = "1521"

ORACLE_DRIVER = "oracle.jdbc.driver.OracleDriver"
```

2.1.2 Update Roles File

To update roles file:

- 1. Navigate to the path /scratch/obma_installer/chef-repo/roles/ and open the OBCR role file. Here, we will consider obcr mw.rb for reference.
- 2. In case of addition or changes to the existing cluster configuration, modify the same under "cluster_config".

Figure 2-7 Modify Cluster Configuration

```
plato_service_logging_path: APPLICATION_LOGGING_PATH,
    plato service env: APPLICATION ENVIRONMENT,
cluster configure: CONFIGURE WLS CLUSTER,
is node primary: "true",
    cluster config: {
        obcr cluster1:
        managed servers: {
        obcr server1: {
            listen port: OBCR1 MAN SERVER LISTEN PORT,
                    ssl port: OBCR1 MAN SERVER SSL PORT,
                    java memory min: "6144",
                    java memory max: "8192",
        obcr cluster2:
        managed servers: {
            obcr server2: {
            listen port: OBCR2 MAN SERVER LISTEN PORT,
                    ssl port: OBCR2 MAN SERVER SSL PORT,
                    java memory min: "6144",
                    java memory max: "8192",
```

In case of addition or changes to the existing data source configuration, modify the same under "datasource config".

Figure 2-8 Modify Datasource Configuration

```
datasource configure: "true",
datasource config: {
    PLATO: {
        database name: ORACLE PDB SID,
        driver class: "oracle.jdbc.OracleDriver",
        jndi_name: PLATO_JNDI,
        host name: ORACLE PDB HOSTNAME,
        port: ORACLE PDB PORT,
        global_transaction_protocol: "OnePhaseCommit",
        database user name: PLATO SCHEMA,
        target: OBCR PLATO DS TARGET
       },
    PLATOBATCH: {
        database name: ORACLE PDB SID,
        driver_class: "oracle.jdbc.OracleDriver",
        jndi_name: PLATO_BATCH_JNDI,
        host_name: ORACLE_PDB_HOSTNAME,
        port: ORACLE PDB PORT,
        global_transaction_protocol: "OnePhaseCommit",
        database_user_name: PLATO_BATCH_SCHEMA,
        target: OBCR PLATO BATCH DS TARGET
       },
    PLATORULE: {
        database_name: ORACLE_PDB_SID,
        driver_class: "oracle.jdbc.OracleDriver",
        jndi name: PLATO RULE JNDI,
        host name: ORACLE PDB HOSTNAME,
        port: ORACLE PDB PORT,
        global_transaction_protocol: "OnePhaseCommit",
        database user name: PLATO RULE SCHEMA,
        target: OBCR PLATO RULE DS TARGET
       },
```

4. In case of addition or changes to the existing services or war files, modify the same under "app deployment".

Figure 2-9 Modify Wars in App Deployment

```
app deployment: {
  appl: {
         app_file_path: "/obma_installer/deployables/apps/obcr",
         app_file_name: "obcr-activity-services-9.1.0.war",
         app target name: "obcr cluster1"
    },
     app2: {
         app file path: "/obma installer/deployables/apps/obcr",
         app file name: "obcr-action-services-9.1.0.war",
         app_target_name: "obcr cluster1"
    },
    app3: {
        app_file_path: "/obma_installer/deployables/apps/obcr",
        app_file_name: "obcr-common-services-9.1.0.war",
        app_target_name: "obcr_cluster1"
    },
    app4: {
        app file path: "/obma installer/deployables/apps/obcr",
        app file name: "obcr-entity-services-9.1.0.war",
        app target name: "obcr cluster1"
    },
    app5: {
        app file path: "/obma installer/deployables/apps/obcr",
        app file_name: "obcr-ptp-services-9.1.0.war",
        app target name: "obcr cluster1"
    },
    app6: {
        app file path: "/obma installer/deployables/apps/obcr",
        app file name: "obcr-segmentation-services-9.1.0.war",
        app_target_name: "obcr_cluster1"
```

- 5. Navigate to the bottom of the file and verify the recipes to be executed. All the listed recipes will be executed in sequential order as shown below.
 - CASE 1: If both foundation and product are on same VM, use the below runlist.

```
run_list
['recipe[obma_weblogic::domain]','recipe[obma_weblogic::startadmi
n]','recipe[obma_weblogic::startnm]','recipe[obma_weblogic::ssl_a
dmin]','recipe[obma_weblogic::stopadmin]','recipe[obma_weblogic::
ssl_nodemanager]','recipe[obma_weblogic::restartadmin]','recipe[o
bma_weblogic::cluster]','recipe[obma_weblogic::addjdbcconnections
_obcr]','recipe[obma_weblogic::setuseroverridesupdate]','recipe[o
bma_weblogic::startman]','recipe[obma_weblogic::deployapp]']
```

- CASE 2: If foundation and product are on separate VMs, perform the below steps.
 - a. Execute the below runlist.

```
run_list
['recipe[obma_java::_install_java]','recipe[obma_java::create
_certs]','recipe[obma_weblogic::install_wls]','recipe[obma_we
blogic::install_wls_patch]','recipe[obma_weblogic::domain]','
recipe[obma_weblogic::startadmin]','recipe[obma_weblogic::sta
```



```
rtnm]','recipe[obma_weblogic::ssl_admin]','recipe[obma_weblogic::st
opadmin]','recipe[obma_weblogic::ssl_nodemanager]','recipe[obma_web
logic::restartadmin]','recipe[obma_weblogic::cluster]','recipe[obma
_weblogic::addjdbcconnections_obcr]','recipe[obma_weblogic::setuser
overridesupdate]','recipe[obma_weblogic::startman]']
```

- b. Perform steps mentioned in section #unique_23 of Oracle Banking Microservices Architecture Installer Guide.
- c. Execute below runlist.

```
run_list ['recipe[obma_weblogic::deployapp]']
```

2.1.3 Execute Installer Script

Perform the following steps for silent installation of Oracle Banking Collections and Recovery:

- 1. Launch putty and login to product VM with NIS user and then switch to root user.
- 2. Navigate to the chef-repo path by executing the below command:

```
cd /scratch/obma installer/chef-repo
```

3. Execute the installer script by executing the below command:

```
./obcr_installer.sh
```



Data Source Verification

This topic describes the data source verification for Oracle Banking Collections and Recovery installation.

Prerequisites

Before proceeding with deployment setup, make sure that the database and application setup for Oracle Banking Microservices Architecture is done.

Data Sources List

The table below lists the data sources created as a part of product installation.

Table 3-1 Data Sources List

Serial Number	Data Source Name	Data Source JNDI	Targets
1	PLATO	jdbc/PLATO	obcr_server1
	PLATOBATCH	jdbc/PLATOBATCH	obcr_server1
	PLATOFEED	jdbc/PLATOFEED	obcr_server1
	PLATO_UI	jdbc/ PLATO_UI_CONFIG	obcr_server1
	SMS	jdbc/sms	obcr_server1
	PLATORULE	jdbc/PLATORULE	obcr_server1
	PLATOSEC	jdbc/PLATOSECURITY	obcr_server1
	CMNCORE	jdbc/CMNCORE	obcr_server1
	CR_ACTION	jdbc/CR_ACTION	obcr_server1
	CR_ACTIVITY	jdbc/CR_ACTIVITY	obcr_server1
	CR_CMN	jdbc/CR_CMN	obcr_server1
	CR_CORR	jdbc/CR_CORR	obcr_server1
	CR_ENTITY	jdbc/CR_ENTITY	obcr_server1
	CR_NOTES	jdbc/CR_NOTES	obcr_server1
	CR_PTP	jdbc/CR_PTP	obcr_server1
	CR_SEG	dbc/CR_SEG	obcr_server1
2	PLATO	jdbc/PLATO	obcr_server2
	PLATOBATCH	jdbc/PLATOBATCH	obcr_server2
	PLATOFEED	jdbc/PLATOFEED	obcr_server2
	PLATO_UI	jdbc/ PLATO_UI_CONFIG	obcr_server2
	SMS	jdbc/sms	obcr_server2
	PLATORULE	jdbc/PLATORULE	obcr_server2
	PLATOSEC	jdbc/PLATOSECURITY	obcr_server2
	CMNCORE	jdbc/CMNCORE	obcr_server2
	CR_SEGMAINT	jdbc/CR_SEGMAINT	obcr_server2



Table 3-1 (Cont.) Data Sources List

Serial Number	Data Source Name	Data Source JNDI	Targets
	CR_STRTGY	jdbc/CR_STRTGY	obcr_server2
	CR_STRTGYMAINT	jdbc/ CR_STRTGYMAINT	obcr_server2
	CR_TASK	jdbc/CR_TASK	obcr_server2
	CR_TASKMAINT	jdbc/CR_TASKMAINT	obcr_server2
	CR_USERMGMT	jdbc/CR_USERMGMT	obcr_server2
	CR_DASHBOARD	jdbc/ CR_DASHBOARD	obcr_server2



For creating data source, see section Create Datasource of Configuration and Deployment Guide.



4

Deployments Verification and Kafka Setup

This topic describes the deployments for Oracle Banking Collections and Recovery installation.

Prerequisites

- Before proceeding with the below setup, make sure that Kafka is configured and the related properties are present in PLATO schema. For more information, see section Kafka SSL Setup and Verification.
- To avail feature of record level approval functionality in Plato-Feed, the below property
 would need to be maintained as part of weblogic VM argument by each product domain
 including plato. If not maintained, the default behavior will be of file level approval only.
 Property name feed.recordLevelApprovalReqd

Property value - true or false

Default value - false

Deployments List

The below table gives details of the deployments required on each domain to run the Oracle Banking Collections and Recovery application. It also provides path where application war files are located at Oracle Software Delivery Cloud (OSDC).



For the exact version of the archive name, refer to the OSDC file available as part of the release.

Table 4-1 Deployments List

Application	Archive Name	OSDC Path	Targets
OBCR Activity Services	obcr-activity-services- {version}.war	OBCR_SERVICES/	OBCR Server1
OBCR Action Services	obcr-action-services- {version}.war	OBCR_SERVICES/	OBCR Server1
OBCR Common Services	obcr-common-services- {version}.war	OBCR_SERVICES/	OBCR Server1
OBCR Entity Services	obcr-entity-services- {version}.war	OBCR_SERVICES/	OBCR Server1
OBCR PTP Services	obcr-ptp-services- {version}.war	OBCR_SERVICES/	OBCR Server1
OBCR Segmentation Services	obcr-segmentation- services-{version}.war	OBCR_SERVICES/	OBCR Server1
OBCR Correspondence Services	obcr-correspondence- services-{version}.war	OBCR_SERVICES/	OBCR Server1



Table 4-1 (Cont.) Deployments List

Application	Archive Name	OSDC Path	Targets
OBCR Segment Maintenance Services	obcr-segment-maint- services-{version}.war	OBCR_SERVICES/	OBCR Server2
OBCR Strategy Services	obcr-strategy-services- {version}.war	OBCR_SERVICES/	OBCR Server2
OBCR Strategy Maintenance Services	obcr-strategy-maint- services-{version}.war	OBCR_SERVICES/	OBCR Server2
OBCR Task Services	obcr-task-services- {version}.war	OBCR_SERVICES/	OBCR Server2
OBCR Task Maintenance Services	obcr-task-maint- services-{version}.war	OBCR_SERVICES/	OBCR Server2
OBCR User Management Services	obcr-user-management- services-{version}.war	OBCR_SERVICES/	OBCR Server2
OBCR Notes Services	obcr-notes-services- {version}.war	OBCR_SERVICES/	OBCR Server2
OBCR Dashboard Services	obcr-dashboard- services- {version}.war	OBCR_SERVICES/	OBCR Server2
OBCR UI	 app-shell- {version}.war cmc-component- server-{version}.war sms-component- server-{version}.war obcr-component- server-{version}.war 	UI/	API Gateway Server



5

Initial Setup

This topic describes the initial setup for Oracle Banking Collections and Recovery installation.

Once everything is deployed, run the CMC and SMS initial setup scripts from the below mentioned paths at Oracle Software Delivery Cloud to create the required maintenances.

- OBCR_INITIAL_SETUP/cmc_initial_setup.sql To be compiled in Common Core schema.
- OBCR_INITIAL_SETUP/obcr_role_creation.sql
 To be compiled in SMS schema for OBCR specific admin role creation.
- OBCR_INITIAL_SETUP/sms_initial_setup.sql To be compiled in SMS schema.
- OBCR_INITIAL_SETUP/obma_role_seed.sql To be compiled in SMS schema.
- OBCR_INITIAL_SETUP/obcr_role.sql To be compiled in SMS schema.
- OBCR_INITIAL_SETUP/ plato_properties_script.sql To be compiled in PLATO schema.
- OBCR_INITIAL_SETUP/ dms_properties_script.sql To be compiled in PLATO schema.
- OBCR_INITIAL_SETUP/ platofeed_script.sql To be compiled in PLATOFEED schema.

CMC Initial Setup

This script would prompt a user to enter the below values.

Table 5-1 CMC Initial Setup - Field Description

Serial Number	Field	Description
1	Bank Code	A four-letter Bank Code
2	Bank Description	Description of the Bank Code
3	Branch Code	A three letter Branch Code
4	Branch Name	Name of the Branch
5	Branch Address Line 1	Address line 1 of the branch
6	Branch Address Line 2	Address line 2 of the branch
7	Branch Address Line 3	Address line 3 of the branch
8	Branch Currency	A three letter ISO Currency Code
9	Branch Currency Description	The description of the branch currency
10	Country Code	A two letter ISO Country Code
11	Walk-In Customer	Walk-in customer number



Table 5-1 (Cont.) CMC Initial Setup - Field Description

Serial Number	Field	Description
12	Host Code	Host code of the Branch
13	Host Description	Host code description
14	Host Process Time Zone	Host code time zone (GMT+5.30)
15	Source System	External source system
16	Source System Description	Source system description
17	Source System Branch	Branch code as in the source system
18	Previous Working Day	Previous working day of the Branch
19	Current Working Day	Current working day of the Branch
20	Next Working Day	Next working day of the Branch

OBCR Role Creation

The script would create an OBCR specific admin role COLL_MNGR_ROLE.

SMS Initial Setup

This script would prompt the user to create two admin users.

Table 5-2 SMS Initial Setup - Field Description

Serial Numbe r	Field	Description
1	User Login ID 1	Login ID of the first User
2	User Name 1	Name of the first User
3	User Login ID 2	Login ID of the second User
4	User Name 2	Name of the second User
5	Users Home Branch Code	A three letter Home-Branch Code of the users
6	Users Locale	Users locale (2 letter ISO country code)
7	Start Date	Start date
8	End Date	End date

These users are assigned the default COLL_MNGR_ROLE, and the PLATO, SMS, CMC and the other functional activities are mapped.

PLATO Additional Setup

This script would prompt the user for the following details regarding correspondence.

Table 5-3 PLATO Additional Setup - Field Description

Serial Numbe r	Field	Description
1	Sender email Id	Email Id of the sender for communication



Table 5-3 (Cont.) PLATO Additional Setup - Field Description

Serial Numbe r	Field	Description
2	Branch Code	A three letter Branch Code
3	User ID	Admin User ID

DMS server Setup

This script would prompt the user for the following details regarding correspondence. These scripts are to be run only if you are using DMS server of document upload. This script is to be executed only if the values for these fields are not already present/updated in the database.

Table 5-4 DMS server Setup - Field Description

Serial Number	Field	Description
1	Dms Service URL	URL of the document management server
2	Dms Service Username	Login Id of the document management server
3	Dms Service Password	Password of the document management server

PLATOFEED Additional Setup

This script would prompt the user for the following details regarding plato feed.

Table 5-5 SMS Initial Setup - Field Description

Serial Number	Field	Description	
1	Branch code	A three letter Branch Code	

LDAP Setup

The users created using the SMS script must also be created in the LDAP server.



For LDAP setup, see Configuration and Deployment Guide.

Fact Creation

For creating facts, download the <code>obcr_facts.csv</code> file from this path:

OBCR_INITIAL_SETUP/obcr_facts.csv at Oracle Software Delivery Cloud. The

obcr_facts.csv file contains the list of facts that are used to configure rules in the system.

To create facts:



- 1. From the main menu in the Oracle Banking Collections and Recovery application, navigate to Rule and then click Fact.
- 2. From the Fact menu , click Create Fact.
- 3. Click Bulk Upload.
- 4. Click **Drag and Drop** to browse to the required folder and select the obcr facts.csv for upload.
- 5. Click Upload.

The ${\tt obcr_facts.csv}$ file contains the list of facts as mentioned below.

Table 5-6 List of Facts for Oracle Banking Collections and Recovery

Code	Description	Product Processor	Туре
AccountOpeningORIntitialDisbursementD ate	Account Opening OR Intitial Disbursement Date	OBCR	DATE
AccountWriteOffAmount	Account WriteOff Amount	OBCR	NUMBER
AccountWriteOffDate	Account WriteOff Date	OBCR	DATE
AccuralStatus	Accrual Status	OBCR	TEXT
AddressCountry	Address Country	OBCR	TEXT
AddressState	Address State	OBCR	TEXT
ApplicationScore	Application Score	OBCR	NUMBER
AssetClassificationCode	Asset Classification Code	OBCR	TEXT
AvailableForDisbursement	Available For Disbursement	OBCR	TEXT
BICOEFlag	BICOE Flag	OBCR	TEXT
BehaviourScore	Behavior Score	OBCR	NUMBER
BusinessDate	Business Date	OBCR	DATE
CaseID	Case Id	OBCR	Case Id
ChargeOffAmount	ChargeOff Amount	OBCR	NUMBER
CollateralType	Collateral Type	OBCR	TEXT
CollectionStatus	Collection Status	OBCR	TEXT
CustomerRiskScore	Customer Risk Score	OBCR	NUMBER
DaysChargeOff	Days Charge Off	OBCR	NUMBER
DaysPastDue	Days Past Due	OBCR	NUMBER
DaysSinceAccountLinkagetoCase	Days Since Account Linkage to Case	OBCR	NUMBER
DaysSinceCaseCreation	Days Since Case Creation	OBCR	NUMBER
DelinquencyStartDate	Delinquency Start Date	OBCR	DATE
DisbursedAmount	Disbursed Amount	OBCR	NUMBER
ExistPromiseCount	Existing Promise Amount	OBCR	NUMBER
ForcedAccountSwitch	Forced Account Flag	OBCR	TEXT



Table 5-6 (Cont.) List of Facts for Oracle Banking Collections and Recovery

Code	Description	Product Processor	Туре
HomeBranchCode	Home Branch Code	OBCR	TEXT
InsuredSwitch	Insured Switch	OBCR	TEXT
InterestRate	Interest Rate	OBCR	NUMBER
LastPaymentAmount	Last Payment Amount	OBCR	NUMBER
LastPaymentDate	Last Payment Date	OBCR	DATE
LoanMaturityORLimitExpiryDate	Loan Maturity OR Limit Expiry Date	OBCR	DATE
MaxPTPInstallCount	Max PTP Instalment Count	OBCR	NUMBER
NewPromiseCount	New Promise Count	OBCR	NUMBER
OutstandingAmount	Outstanding Amount	OBCR	NUMBER
OverdueAmount	Overdue Amount	OBCR	NUMBER
PartyType	Party Type	OBCR	TEXT
ProductProcessorCd	Product Processor Code	OBCR	TEXT
ProductSubType	Product Sub Type	OBCR	TEXT
ProductType	Product Type	OBCR	TEXT
PromiseAmount	Promise Amount	OBCR	NUMBER
PromiseDate	Promise Date	OBCR	DATE
SecuredSwitch	Secured Switch	OBCR	TEXT
Segmen	Segment Code	OBCR	TEXT
SystemAccountStatus	System Account Status	OBCR	TEXT
TotalCollateralAssessedValue	Total Collateral Assessed Value	OBCR	NUMBER
UnClearedPaymentAmount	UnCleared Payment Amount	OBCR	NUMBER
UserDefinedAccountStatus	User Defined Account Status	OBCR	TEXT
VIPFlag	VIP Flag	OBCR	TEXT

Config update for report service

Next, for the plato-report-service, please make sure the below configurations done on the OBMA server.

Note:

This step is to be performed if not already done.

Create a directory by the name report-fop-config under /scratch/env directory.

Then, copy the file fop.xconf from the location <code>/THIRD_PARTY_SOFTWARE/report-fop-config</code> inside the package to the above created location.



Once done please run the below command

chmod 0755 /scratch/env/report-fop-config/fop.xconf



6

Restart and Refresh

This topic describes the procedure to restart and refresh the servers.

Once everything is deployed, restart all the managed servers. For each application, call path /refresh to refresh the configuration properties.

Restart Server

To restart the server, see chapter Restart Server of Configuration and Deployment Guide.



7

Logging Area

This chapter describes the logging area of Oracle Banking Collections and Recovery applications in server.

The logging area is configurable. The user can configure any path within the server, where you want to write the Oracle Banking Collections and Recovery application logs. Oracle Banking Collections and Recovery applications write the logs in the configured path with the name: **Application name>.logs.** For example, if application name is **obcr-action-services**, then the logs file name would be obcr-action-servies.log.



Patchset Setup

This topic describes about the Patchset setup using Oracle Banking Microservices Architecture Installer.

Prerequisites

- 1. Check for existing setup or the environment is available.
- 2. Updated Patch Set Installation script with respective to the current release upgrade is available in the respective VM's. If not copy the required scripts from SVN.
- Foundation Setup Upgrade
- Oracle Banking Collections and Recovery Patch Installation

8.1 Foundation Setup Upgrade

Installer Path

You can download the installer from Oracle Software Delivery Cloud (OSDC). The following table provides the download path of the installer.

Table 8-1 Installer Path

Application	Archive Name	OSDC Path
OBMA patch Installer	obma_patch.zip	INSTALLER/
OBCR patch Installer	obcr_patch.zip	INSTALLER/

- Download Installer
- Update Properties File
- Update Roles File

8.1.1 Download Installer

The patch installer is available in OSDC zip of each product.

To download the installer:

1. Launch putty and login to the VM (where the installation is planned) with OS user.

2. Create a directory obma_patch_installer in /scratch.

```
mkdir -p /scratch/obma_patch_installer
chmod 755 /scratch/obma_patch_installer
```

- 3. Navigate to the new directory obma_patch_installer. cd /scratch/obma patch installer
- Download the patch installer zip file from the OSDC zip to obma_patch_installer directory.
- 5. Unzip installer zip file by executing the below command.

```
unzip cproduct zip file>
```

Before you proceed, please refer section Kafka Databags Update for Kafka SSL and Kafka scram passwords update.

8.1.2 Update Properties File

To update properties file:

- Navigate to the path /scratch/obma_patch_installer/chef-repo/.
 Open the respective OBMA properties file and update the obma patch properties.rb with below details.
- 2. Update the local user and its group.

Figure 8-1 Update Local User and Group

```
#Standard Values
INSTALL_USER = "obcrdev"
INSTALL_GROUP = "dba"
USER_ROOT = "root"
GROUP_ROOT = "root"
INSTALL_BASE_DIR = "/scratch"
EXTRACT_LOC = "/scratch/extract"
```

3. Verify the version of java, update if required, and ensure the same version is available in the software's directory.

Figure 8-2 Verify Java Version

```
#Java Installation Details
JAVA_INSTALLER_SOURCE = "filesystem"
JAVA_INSTALLER_PATH = "/java/"
JAVA_INSTALLATION_DIR = INSTALL_BASE_DIR + "/obma"
JAVA_VERSION = "11.0"
JDK_INSTALLER_VERSION = "jdk-11.0.16"
JDK_INSTALLER_FILE = "jdk-11.0.16_linux-x64_bin.tar.gz"
CERTS_DIRNAME = INSTALL_BASE_DIR + "/ssl/cacerts"
```

4. Verify the configuration service details, update if required.

Figure 8-3 Verify Configuration Details

```
#Path where Oracle Banking product bundle is extracted

PRODUCT_BUNDLE_HOME = "/scratch"

PLATO_CONFIG_SERVICES_URI = "https://ofss-mum-2672.snbomprshared1.gbucdsint02bom.oraclevcn.com"

PLATO_CONFIG_SERVICES_PORT = "8002"

APPLICATION_LOGGING_PATH = "/scratch/work_area/logs"
```

5. Verify the Java home and certificate names.

Figure 8-4 Verify Java Home and Certificate Names

```
#Java Path

JAVA_HOME = "/scratch/obma/jdk-11.0.16"

CERTS_DIRNAME = "/scratch/ssl/cacerts"

CUSTOM_IDENTITY_JKS = "ofss-mum-2672.snbomprshared1.gbucdsint02bom.oraclevcn.com_identity.jks"

CUSTOM_TRUST_JKS = "ofss-mum-2672.snbomprshared1.gbucdsint02bom.oraclevcn.com_trust.jks"

CUSTOM_TRUST_CRT = "ofss-mum-2672.crt" # This can be crt or cer

KEYSTORETYPE = "JKS"
```

6. Verify the Kafka details as below.

Figure 8-5 Verify Kafka Details

```
#ZOOKEEPER/KAFKA Installation Details (Upgrade Version)
KAFKA_ZOOKEEPER_INSTALLER_FILE = "kafka_2.13-3.4.0.tgz"
KAFKA_VERSION = "3.4.0"
KAFKA_SCALA_VERSION = "2.13"
KAFKA_INSTALL_USER_HOME = INSTALL_BASE_DIR
KAFKA_INSTALL_DIR = INSTALL_BASE_DIR + "/obma/kafka_zookeeper"
KAFKA_INSTALLER_PATH = SOFTWARE_INSTALLER_HOME + "/kafka_zookeeper"
KAFKA_CERTS_DIRNAME = INSTALL_BASE_DIR + "/ssl/kafka_cert"
```

7. Verify the plato router details, update if required.

Figure 8-6 Verify Plato Router

```
#APIGATEWAY_ROUTER_DETAILS
PLATO_APIGATEWAY_ROUTER_PORT = "8080"

APIGATEWAY_ROUTER_JAR_NAME = "plato-apigateway-router-9.1.0.jar"

APIGATEWAY_ROUTER_JAR_LOCATION = "/scratch/obma_patch_installer/deployables/apps/platoinfra"

# Encrypted Values for Certificate and SALT are present in apigateway_router databag
```

8. Update database details under "#Database details for weblogic datasource configuration".

Figure 8-7 Update Database Details

```
#Database details for weblogic datasource configuration
ORACLE_PDB_SID = "PDB1323B"
ORACLE_PDB_HOSTNAME = "ofss-mum-2629.snbomprshared1.gbucdsint02bom.oraclevcn.com"
ORACLE_PDB_PORT = "1521"
ORACLE_DRIVER = "oracle.jdbc.driver.OracleDriver"
```

8.1.3 Update Roles File

To update roles file:

- Navigate to the path /scratch/obma_patch_installer/chef-repo/roles.
 Update the obma patch install.rb with below details.
- 2. If you are upgrading from one version to another, then the version to be undeployed needs to be added in the below section app_undeployment.

Figure 8-8 App Undeployment

```
app_undeployment: {
    app1: {
        app_file_path: "/obma_installer/deployables/apps/platoinfra",
        app_file_name: "plato_config_service-8.2.0.war",
        app_target_name: "plato_config_cluster"
    },
    app2: {
        app_file_path: "/obma_installer/deployables/apps/platoinfra",
        app_file_name: "plato_discovery_service-8.2.0.war",
        app_target_name: "plato_discovery_cluster"
    },
    app3: {
        app_file_path: "/obma_installer/deployables/apps/platoinfra",
        app_file_name: "plato_api_gateway-8.2.0.war",
        app_target_name: "plato_api_gateway_cluster"
    },
```

3. In the app_deployment section, update the new version to be deployed.

Figure 8-9 App Deployment

```
app_deployment: {
     app1: {
         app file path: "/obma patch installer/deployables/apps/platoinfra",
         app_file_name: "plato-config-service-9.1.0.war",
         app_target_name: "plato_config_cluster"
     app2: {
        app file path: "/obma patch installer/deployables/apps/platoinfra",
         app_file_name: "plato-discovery-service-9.1.0.war",
         app target name: "plato discovery cluster"
     },
     app3: {
         app_file_path: "/obma_patch_installer/deployables/apps/platoinfra",
         app file name: "plato-api-gateway-9.1.0.war",
         app target name: "plato api gateway cluster"
    },
     app4: {
         app file path: "/obma patch installer/deployables/apps/platoinfra",
         app file_name: "plato-ui-config-services-9.1.0.war",
         app target name: "plato ui config cluster"
```

4. Navigate to the bottom of the file and verify the recipes to be executed. All the listed recipes will be executed in sequential order as shown below. For execution, please switch to root user from OS user and then run the below commands.

```
cd /scratch/obma_patch_installer/chef-repo
sh obma_patch_installer.sh
```

a. run_list
 ['recipe[obma_patchset::undeployapp]','recipe[obma_patchset::stopman]'
 ,'recipe[obma_patchset::updatesetuseroverrides_patch]','recipe[obma_patchset::startman]','recipe[obma_patchset::deployapp]']

Once successfully run, please make sure all services are up. Upon verification, please make update the runlist to as below and re-run the obma_patch_installer.sh command.

b. run list ['recipe[obma patchset::deployapigateway router]']

This step would bring up the plato-apigateway-router at the port specified. To confirm the same please visit the router logs at the location /scratch/work area/logs.

8.2 Oracle Banking Collections and Recovery Patch Installation

To upgrade the OBCR product using patch installer, first perform steps mentioned in section Download Installer.

- Update Properties File
- Update Roles File



8.2.1 Update Properties File

To update properties file:

- Navigate to the path /scratch/obma_patch_installer/chef-repo/.
 Open the respective product properties file and update the obcr patch properties.rb with below details.
- 2. Update the local user and its group.

Figure 8-10 Update Local User and Group

```
#Standard Values
INSTALL_USER = "obcrdev"
INSTALL_GROUP = "dba"
USER_ROOT = "root"
GROUP_ROOT = "root"
INSTALL_BASE_DIR = "/scratch"
EXTRACT_LOC = "/scratch/extract"
```

3. Verify Java home and certificate names.

Figure 8-11 Verify Java Home

```
#Java Path

JAVA_HOME = "/scratch/obma/jdk-11.0.16"

CERTS_DIRNAME = "/scratch/ssl/cacerts"

CUSTOM_IDENTITY_JKS = "ofss-mum-2550.snbomprshared1.gbucdsint02bom.oraclevcn.com_identity.jks"

CUSTOM_TRUST_JKS = "ofss-mum-2550.snbomprshared1.gbucdsint02bom.oraclevcn.com_trust.jks"

KEYSTORETYPE = "JKS"
```

8.2.2 Update Roles File

To update roles file:

- Navigate to the path /scratch/obma_patch_installer/chef-repo/roles and update obcr patch install.rb file with below details.
- If you are upgrading from one version to another, then the version to be undeployed needs to be added in the below section app_undeployment.



Figure 8-12 App Undeployment

```
app_undeployment: {
    app1: {
        app_file_path: "/obma_installer/deployables/apps/obcr",
            app_file_name: "obcr_activity-services-8.2.0.war",
            app_target_name: "obcr_cluster1"
        },
        app_file_path: "/obma_installer/deployables/apps/obcr",
            app_file_name: "obcr_action-services-8.2.0.war",
            app_target_name: "obcr_cluster1"
        },
        app_file_path: "/obma_installer/deployables/apps/obcr",
        app_file_name: "obcr_common-services-8.2.0.war",
        app_file_name: "obcr_common-services-8.2.0.war",
        app_target_name: "obcr_cluster1"
        },
```

3. In the **app_deployment** section, update the new version to be deployed.

Figure 8-13 App Deployment

4. Navigate to the bottom of the file and verify the recipes to be executed. All the listed recipes will be executed in sequential order as shown below.

```
run_list
['recipe[obma_patchset::undeployapp]','recipe[obma_patchset::stopman]','re
cipe[obma_patchset::updatesetuseroverrides_patch]','recipe[obma_patchset::
startman]','recipe[obma_patchset::deployapp]']
```

For execution, please switch to root user from OS user and then run the below commands.

```
cd /scratch/obma_patch_installer/chef-repo
sh obcr_patch_installer.sh

run_list
['recipe[obma_patchset::undeployapp]','recipe[obma_patchset::stopman]','recipe
e[obma_patchset::addjdbcconnections_plato]','recipe[obma_patchset::updatesetu
```



```
seroverrides_patch]','recipe[obma_patchset::startman]','recipe[obma_patchset::deployapp]']
```

Once everything is deployed, run the initial setup scripts from the below mentioned paths at Oracle Software Delivery Cloud to create the required maintenances. The descriptions for each of these have been provided in the Initial setup section of this document.

If a new role/user needs to be created, then run the below two scripts in Section-A followed by scripts from Section-B.

If no new role/user needs to be created, then only run scripts from Section-B.

Post Section-A & B please run Section-C & D if and only if you need to fill a certain maintenance for correspondence. Please read the descriptions for these scripts from Initial setup section of this document before executing.

Especially, for section-D the script only needs to be executed if the values for these properties are not already present in the database.

Section-A

- OBCR_INITIAL_SETUP/obcr_role_creation.sql
 To be compiled in SMS schema for OBCR specific admin role creation.
- OBCR_INITIAL_SETUP/sms_initial_setup.sql To be compiled in SMS schema.

Section-B

- OBCR_INITIAL_SETUP/obma_role_seed.sql To be compiled in SMS schema.
- OBCR_INITIAL_SETUP/obcr_role.sql To be compiled in SMS schema.

Section-C

- OBCR_INITIAL_SETUP/ plato_properties_script.sql To be compiled in PLATO schema.
- OBCR_INITIAL_SETUP/ platofeed_script.sql To be compiled in PLATOFEED schema.

Section-D

• OBCR_INITIAL_SETUP/ dms_properties_script.sql To be compiled in PLATO schema.



9

Troubleshooting

- Troubleshooting for OBMA Patch Installation
- · Troubleshooting for plato-apigateway-router

9.1 Troubleshooting for OBMA Patch Installation

If the OBMA services are not up after patch installation, please check the plato-config-server logs at the below location for further analysis.

```
/scratch/obma/domain/PlatoInfra/servers/Config Server1/logs
```

If you see an error like "args list too long", please navigate to the below file setUserOverrides.sh at location /scratch/obma/domain/PlatoInfra/bin and remove the unwanted properties. Then, please restart Config_Server1 on weblogic followed by the other managed servers. Once done, make OBMA services are up and running.

9.2 Troubleshooting for plato-apigateway-router

If you observe any SSL related issues in the plato-apigateway-router logs, then follow the below steps.

- 1. Stop the router by killing the router process.
- 2. Import the crt files into the java trust store on the VM on which the router is installed (the foundation machine ideally).
- 3. One crt file will be of the same foundation machine, while the other crt file(s) will be of the machine(s), the foundation machine has performed a sync with. Replace the password placeholder with the actual one.

```
cd /scratch/ssl/cacerts
keytool -importcert -file ofss-mum-2672.crt -keystore /scratch/obma/
jdk-11.0.16/lib/security/cacerts -storepass <password> -noprompt
keytool -importcert -alias domainCertForRouter -file ofss-mum-2550.crt -
keystore /scratch/obma/jdk-11.0.16/lib/security/cacerts -storepass
<password> -noprompt
```

4. Restart the router using through the OBMA installer using the below runlist.

```
run list ['recipe[obma weblogic::deployapigateway router]']
```



A

Kafka Related Details

- Kafka SSL Setup and Verification
- Kafka Databags Update

A.1 Kafka SSL Setup and Verification

To configure Kafka SSL, follow below steps:

 Verify that /scratch/obma/kafka_zookeeper/kafka_2.13-3.4.0/config/ server.properties, password, ssl truststore and keystorelocation is correct.

Figure A-1 Verify Server Properties

 Verify /scratch/obma/kafka_zookeeper/kafka_2.13-3.4.0/config/ssl.properties, ssl.truststore.password, username, password is correct.

Figure A-2 Verify SSL Properties

```
ssl.truststore.location=/scratch/ssl/kafka_cert/KafkaClientTrustStore.jks
ssl.truststore.password=orcl@123
security.protocol=SASL_SSL
ssl.endpoint.identification.algorithm=
sasl.mechanism=SCRAM-SHA-256
sasl.jaas.config=org.apache.kafka.common.security.scram.ScramLoginModule required \
username="obcr" \
password="obedx-secret";
```

3. Update kafka properties for product services. Execute below queries on PLATO schema (replace machine name and port as per env).

```
update properties set value='ofss-mum-xxxx.snbomprshared1.gbucdsint02bom.oraclevcn.com:9092' where key like '%spring.cloud.stream.kafka.binder.brokers%' and application like 'obcr-%';

update properties set value='ofss-mum-xxxx.snbomprshared1.gbucdsint02bom.oraclevcn.com:2181' where key like
```

```
'%spring.cloud.stream.kafka.binder.zknodes%' and application like 'obcr-%';
```

4. In case, you are running Foundation and Product on two separate VMs, please copy the Kafka certificates present at the location /scratch/ssl/kafka_cert on the Foundation machine to /scratch/ssl/kafka_cert location on the Product machine. (Create the folder location if not already present and provide ownership of the kafka cert folder to the VM user using below command).

```
cd /scratch/ssl
chown -R <VM user> kafka cert
```

5. Login to the OBCR product weblogic and restart both the managed servers obcr_server1 and obcr_server2.

Troubleshooting

- 1. Verify the start log at location /scratch/obma/kafka_zookeeper/ kafka_2.13-3.4.0/bin/start_server.log (if SSL handshake error exists, then follow step 2)
- Login to OBMA foundation weblogic, restart server Plato_Others_Server1 and CMC_Server4 which contains below services.
 - plato-alerts-management-services
 - plato-batch-servers
 - · cmc-advice-services

Verify the log at /scratch/work_area/logs to confirm that kafka error no more exists.

Restart Kafka

If for any reason Kafka restart is required, you need to stop zookeeper and kafka and then restart Kafka.

To restart Kafka:

- In Putty, go to location /scratch/obma/kafka_zookeeper/ kafka_2.13-3.4.0/bin and run the commands as given below.
 - a. To stop Kafka run the below command twice:

```
./kafka-server-stop.sh
```

The message Verify: No Kafka server to stop appears.

b. To stop Zookeeper run the below command twice:

```
./zookeeper-server-stop.sh
```

The message **Verify: No zookeeperserver to stop** appears.

c. If still Kafka or Zookeeper does not stop, run the below command to stop Kafka:



• ps -ef|grep kafka 2.13-3.4.0

For specific process ID use the below command:

```
jps | grep Kafka | awk '{print $1}'
```

Once you run the command, kill the process ID with below command:

```
kill -9 cess ID>
```

ps -ef|grep zookeeper

For specific process ID use the below command:

```
ps aux | grep "org.apache.zookeeper.server.quorum.QuorumPeerMain"
| grep -v grep | awk '{print $2}'
```

Once you run the command, kill the process ID with below command:

```
kill -9 cess ID>
```

2. In Putty, go to this location /scratch/obma/kafka_zookeeper/kafka_2.13-3.4.0/bin and start zookeeper using command.

```
nohup ./zookeeper-server-start.sh ../config/zookeeper.properties &
```

3. In Putty, go to location /scratch/obma/kafka_zookeeper/kafka 2.13-3.4.0/bin and and start kafka using command:

```
nohup /scratch/obma/kafka_zookeeper/kafka_2.13-3.4.0/bin/kafka-server-
start.sh /scratch/obma/kafka_zookeeper/kafka_2.13-3.4.0/config/
server.properties > /scratch/obma/kafka_zookeeper/kafka_2.13-3.4.0/bin/
start server.log&
```

If the above steps don't work and kafka is still not running, then perform the below steps:

- 1. Stop the zookeeper.
- 2. Delete kafka logs from this location (/scratch/obma/kafka_zookeeper/logs and /scratch/obma/kafka_zookeeper/kafka_2.13-3.4.0/logs) and zookeeper logs (/tmp/zookeeper).
- 3. Start the zookeeper using the command mentioned in the above section.
- 4. In Putty, go to the location /scratch/obma/kafka_zookeeper/kafka_2.13-3.4.0/bin and execute the below commands (replace machine name and the password in this command command)

```
./kafka-configs.sh --zookeeper ofss-mum-xxxx.snbomprshared1.gbucdsint02bom.oraclevcn.com:2181 --alter --add-
```



```
config "SCRAM-SHA-256=[password=admin-secret], SCRAM-
SHA-512=[password=admin-secret]" --entity-type users --entity-name
admin

./kafka-configs.sh --zookeeper ofss-mum-
xxxx.snbomprshared1.gbucdsint02bom.oraclevcn.com:2181 --alter --
add- config "SCRAM-SHA-256=[password=obedx-secret], SCRAM-
SHA-512=[password=obedx-secret]" --entity-type users --entity-name
obcr
```

5. Start the kafka using the command mentioned in the above section.

Verify Kafka is Up

1. Execute below command:

```
ps -ef|grep kafka 2.13-3.4.0
```

It should show pid running.

- 2. Check logs at scratch/obma/kafka_zookeeper/kafka_2.13-3.4.0/bin/start server.log. No SSL error should exist in this file.
- Check logs at /scratch/obma/kafka_zookeeper/kafka_2.13-3.4.0/logs. It should display topic names.

Alternatively, you can check using below commands:

```
netstat -tlnp | grep :9092
```

Verify Kafka Health

Run the below command and verify:

```
$ netstat -tlnp | grep 9092
```



9092 is default port of kafka

Verify Zookeeper Health

Kafka instance will not start if Zookeeper is not yet started.

1. Run the below command and verify.

```
\ netstat tlnp \mid grep :2181 (2181 is default port of zookeeper) top6 0 0 :::2181 :::* LISTEN 19936/java
```

2. To debug, check if the permissions of Kafka log folder are correct.

The log folder path can be found by looking at the value of the property log-dirs in the server.properties file of Kafka installation.



A.2 Kafka Databags Update

To update kafka databags:

- Navigate to existing kafka configs location /scratch/obma/kafka/ kafka 2.13-2.8.1/config.
- Open the ssl.properties file and note the below highlighted values. Kafka SSL credentials and the Kafka SSL SCRAM credentials as shown in screenshot below.

Figure A-3 Kafka Databags Update

```
| ssl.truststore.location=/scratch/ssl/kafka_cert/KafkaClientTrustStore.jks
| ssl.truststore.password=Oracle@123
| security.protocol=SASL_SSL
| ssl.endpoint.identification.algorithm=
| sasl.mechanism=SCRAM-SHA-256
| sasl.jaas.config=org.apache.kafka.common.security.scram.ScramLoginModule required \underscrame="obcr" \underscrame="obcr" \underscrame" obcr-secret";
```

3. Navigate to /scratch/obma_patch_installer/chef-repo/data_bags folder in putty and run the below commands to extract the SSL and the scram passwords, respectively. If they don't match the ones in the previous step, please update the databags to match the existing passwords.

```
export EDITOR=vim
```

knife data bag edit -z --local-mode obma_jk_kafka_upgrade kafka_ssl -secret-file /scratch/obma patch installer/chef-repo/secrets/secret key

knife data bag edit -z --local-mode obma_jk_kafka_upgrade
kafka_sasl_scram_creds --secret-file /scratch/obma_patch_installer/chefrepo/secrets/secret_key

