

Oracle® FLEXCUBE Investor Servicing Development of Online Forms



Release 14.7.7.0.0
G33249-01
April 2025

ORACLE®

Copyright © 2007, 2025, Oracle and/or its affiliates.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this is software, software documentation, data (as defined in the Federal Acquisition Regulation), or related documentation that is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, then the following notice is applicable:

U.S. GOVERNMENT END USERS: Oracle programs (including any operating system, integrated software, any programs embedded, installed, or activated on delivered hardware, and modifications of such programs) and Oracle computer documentation or other Oracle data delivered to or accessed by U.S. Government end users are "commercial computer software," "commercial computer software documentation," or "limited rights data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, reproduction, duplication, release, display, disclosure, modification, preparation of derivative works, and/or adaptation of i) Oracle programs (including any operating system, integrated software, any programs embedded, installed, or activated on delivered hardware, and modifications of such programs), ii) Oracle computer documentation and/or iii) other Oracle data, is subject to the rights and limitations specified in the license contained in the applicable contract. The terms governing the U.S. Government's use of Oracle cloud services are defined by the applicable contract for such services. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

Oracle®, Java, MySQL, and NetSuite are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Inside are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. AMD, Epyc, and the AMD logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark of The Open Group.

This software or hardware and documentation may provide access to or information about content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services unless otherwise set forth in an applicable agreement between you and Oracle. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services, except as set forth in an applicable agreement between you and Oracle.

Contents

Preface

Purpose	v
Audience	v
Documentation Accessibility	vi
Critical Patches	vi
Diversity and Inclusion	vi
Conventions	vi
Screenshot Disclaimer	vii
Prerequisite	vii
Related Resources	vii

1 Overview of Online Form

2 Screen Development

2.1	Header Information	2-1
2.2	Preferences	2-3
2.3	Data Sources	2-4
2.4	Data Blocks	2-5
2.5	Screens	2-8
2.6	Field Sets	2-10
2.7	Actions	2-10
2.8	Launch Forms	2-11
2.9	Call Forms	2-12
2.9.1	Sub System Pickup/Processing	2-13
2.10	Summary	2-14
2.11	Preview	2-15

3 Generated Units

3.1	Front End Units	3-1
3.1.1	Language xml	3-1
3.1.2	SYS JavaScript File	3-1

3.1.3	Release Type Specific JavaScript File	3-1
3.2	Data Base Units	3-2
3.2.1	Static Scripts	3-2
3.2.2	System Packages	3-2
3.2.3	Hook Packages	3-3
3.3	Other Units	3-3
3.3.1	Xsd	3-3

4 Extensible Development

4.1	Extensibility in JavaScript Coding	4-1
4.2	Extensibility in Backend Coding	4-1

Preface

Oracle FLEXCUBE Investor Servicing is a comprehensive mutual funds automation software from Oracle® Financial Servicing Software Ltd.©.

You can use the system to achieve optimum automation of all your mutual fund investor servicing processes, as it provides guidelines for specific tasks, descriptions of various features and processes, and general information.

This topic contains the following sub-topics:

- [Purpose](#)
- [Audience](#)
- [Documentation Accessibility](#)
- [Critical Patches](#)
- [Diversity and Inclusion](#)
- [Conventions](#)
- [Screenshot Disclaimer](#)
- [Prerequisite](#)
- [Related Resources](#)

Purpose

This manual is designed to help FLEXCUBE Application developers/users to familiarize with ORACLE FLEXCUBE Development Workbench for Investor Servicing.

Audience

This document is intended for FLEXCUBE Application developers/users that use Development Workbench to develop various FLEXCUBE components.

To Use this manual, you need conceptual and working knowledge of the below:

Table 1 Proficiency and Resources

Proficiency	Resources
FLEXCUBE Functional Architecture	Training programs from Oracle Financial Software Services.
FLEXCUBE Technical Architecture	Training programs from Oracle Financial Software Services.
FLEXCUBE Object Naming Conventions	Development Overview Guide

Table 1 (Cont.) Proficiency and Resources

Proficiency	Resources
Working knowledge of Web based Applications	Self-Acquired
Working knowledge of Oracle Database	Oracle Documentations
Working knowledge of PLSQL developer	Respective vendor documents
Working knowledge of PLSQL and SQL Language	Self-Acquired
Working knowledge of XML files	Self-Acquired

Documentation Accessibility

For information about Oracle's commitment to accessibility, visit the Oracle Accessibility Program website at <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=docacc>.

Access to Oracle Support

Oracle customers that have purchased support have access to electronic support through My Oracle Support. For information, visit <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=info> or visit <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=trs> if you are hearing impaired.

Critical Patches

Oracle advises customers to get all their security vulnerability information from the Oracle Critical Patch Update Advisory, which is available at [Critical Patches](#), [Security Alerts and Bulletins](#). All critical patches should be applied in a timely manner to ensure effective security, as strongly recommended by [Oracle Software Security Assurance](#).

Diversity and Inclusion

Oracle is fully committed to diversity and inclusion. Oracle respects and values having a diverse workforce that increases thought leadership and innovation. As part of our initiative to build a more inclusive culture that positively impacts our employees, customers, and partners, we are working to remove insensitive terms from our products and documentation. We are also mindful of the necessity to maintain compatibility with our customers' existing technologies and the need to ensure continuity of service as Oracle's offerings and industry standards evolve. Because of these technical constraints, our effort to remove insensitive terms is ongoing and will take time and external cooperation.

Conventions

The following text conventions are used in this document:

Convention	Meaning
boldface	Boldface type indicates graphical user interface elements associated with an action, or terms defined in text or the glossary.
<i>italic</i>	Italic type indicates book titles, emphasis, or placeholder variables for which you supply particular values.
<code>monospace</code>	Monospace type indicates commands within a paragraph, URLs, code in examples, text that appears on the screen, or text that you enter.

Screenshot Disclaimer

Personal information used in the interface or documents is dummy and does not exist in the real world. It is only for reference purposes.

Prerequisite

Specify **User ID** and **Password**, and log in to **Home Screen**.

Related Resources

The functions of ORACLE FLEXCUBE Development Workbench for Investor Servicing system is organized into various guides, each discussing a component.

For more information, see these Open Development Tool documents:

- *Open Development Tool Installation*
- *Development Workbench - Getting Started*
- *Development Workbench - Administration*
- *Development Workbench - Screen Development I*
- *Development Workbench - Screen Development II*
- *Development Workbench - Screen Customizer*
- *Development Workbench - Notifications*
- *Development Workbench - Bulk Generation*
- *Development Workbench - Source Upgrade*
- *Development Workbench - Tracking Changes*
- *Child and Screen Childs - Concept and Design*
- *Development of Maintenance Form*
- *Development of Online Form*
- *Development of Call Form*
- *Development of Launch Forms and Other Screens*
- *Development of Dashboard Form*
- *Development Workbench Service XML Development*
- *Development Workbench Performance Tuning Enhancements*
- *Development Workbench - Rest Services Development*

1

Overview of Online Form

This topic provides an overview on Online Forms.

Online Forms are function Id's (screens) which is used for creating Contracts for respective modules. Same contracts can be processed further for Payments, Availments, Amendments, Reassignments and Authorizations also using Online forms.

All the transaction processing in FLEXCUBE is carried out through Online screens Online form screens should be launched independently.

On launching the Online form screen, user has to input the respective values to create the contract. Form may have the different user-defined actions like Product-Default, Enrich, and Subsystem-Pickup while creating contract. Once all the user-defined actions performed finally user has to save the contract.

Example Letter Of Credit (LC) contract

An LC contract is an instruction wherein a customer requests the bank to issue, advise, or confirm a credit letter for a trade transaction. An LC substitutes a bank's name and credit for the parties involved. The bank thus undertakes to pay the seller/beneficiary even if the remitter fails to pay.

Thus for each module, we should develop different function Id's for creating contracts and other online forms for other operations like Payments, Availments, Amendments, Reassignments, and Authorizations.

Below are the list of LC contract function ID's:

- LCDTRONL - Contract Input
- LCDAMEND - Amend Confirmation Input
- LCDAVMNT - Availment Input
- LCDTRPAY - Payment Input
- LCDTRANF - Transfer Input
- LCDEPMNT - Manual Liquidation Input
- LCDTREAS - Contract Reassign
- LCDTRAUT - Amend Confirmation Input



Note:

The above function ID's are given as an example only.

2

Screen Development

The design and development of an Online Form function id are similar to any other function ids.

This topic describes the following sub-topics:

- Function Generation
- Preferences

For more information, refer to the topic *Development Workbench - Screen Development I*.

- [Header Information](#)
This topic describes about defining the header information for Online Forms.
- [Preferences](#)
This topic describes about defining the preferences for Online Forms.
- [Data Sources](#)
This topic describes about defining the data sources for Online Forms.
- [Data Blocks](#)
This topic describes about defining the data blocks for Online Forms.
- [Screens](#)
This topic describes about designing the screens for Call Forms.
- [Field Sets](#)
This topic describes about defining the field sets for Online Forms.
- [Actions](#)
This topic describes about the actions screen for Online Forms.
- [Launch Forms](#)
This topic describes about the launch forms.
- [Call Forms](#)
This topic describes about the call forms.
- [Summary](#)
This topic describes about the summary screen.
- [Preview](#)
This topic describes about the preview.


2.1 Header Information

This topic describes about defining the header information for Online Forms.

1. On **Expand Menu** of the Development Workbench for Universal Banking, click **Function Generation** node.

The **Function Generation** screen displays.

Figure 2-1 Function Generation



- On the **Function Generation** screen, specify the following fields in the **Header** section for **Online Forms**.

For more information on fields, refer to the field description table.

Table 2-1 Function Generation - Field Description

Field	Description
Function ID	It is the name of the Online Form. Online Form name has to have the third character as D . Ideally, the length of the name should be 8 characters Example: UTDTXN01 etc. are valid online form names.
Function Category	It is the Online Form Category. It has to be Transaction .
Footer Template	Select the footer template from the drop-down list. • None • Maint Audit • Maint Process • Process Footer template can be provided as required. Note for Transaction screens, footer template has to be selected as None . System does not provide any default template for transaction screens; hence developer has to design the footer portion of the screen manually. Developer has to make sure that footer designed has generic fields like transaction status (TXNSTAT), authorization status (AUTHSTAT) etc., For Online Process Flow Screens footer template should be selected as Process .
Function Type	Parent and child functionality is supported for online forms.

Figure 2-2 Online Form header Information

The screenshot shows the 'Function Generation' window. At the top, there are several input fields and dropdown menus: 'Action' (set to 'New'), 'Function Id' (set to 'UTDTX001'), 'Function Type' (set to 'Parent'), 'Function Category' (set to 'Transaction'), 'Header Template' (set to 'None'), and 'Footer Template' (set to 'None'). Below these fields is a 'Save XML Path' button. On the left side, there is a vertical menu with options: 'Search', 'Preferences', 'DataSource', 'ListOfValues', 'DataBlocks', 'Screens', 'FieldSets', 'Actions', 'CallForms', 'LaunchForms', and 'Summary'. The 'Preferences' option is currently selected.

2.2 Preferences

This topic describes about defining the preferences for Online Forms.

1. Specify the menu details in the **Preferences** screen.

Figure 2-3 Online Form Preferences

The screenshot shows the 'Oracle FLEXCUBE Development Workbench for Universal Banking' interface. The 'Function Generation' window is open, and the 'Preferences' tab is selected. The 'Preferences' section contains a list of checkboxes for various settings: 'Head Office Function', 'Logging Required', 'Auto Authorization', 'Module Auto Authorization' (checked), 'Tank Modifications', 'Field Log Required', 'Multi Branch Access', 'Excel Export Required', 'Java Functions', and 'DateWay Screen'. Below this list, there are two tabs: 'Menu Details' and 'Parameter Value Mappings'. The 'Menu Details' tab is active, showing a table with columns 'Function Id', 'Module', and 'Module Description'. The table contains two entries: 'UTDTX001' with 'UT' as the module and 'Unit Trust' as the module description, and 'UTSTX001' with 'UT' as the module and 'Unit Trust' as the module description. The 'Module' and 'Module Description' fields are highlighted with red boxes.

2. On the **Preferences** screen, specify the following fields in the **Header** section for **Online Forms**.

For more information on fields, refer to the field description table.

Table 2-2 Preferences - Field Description

Field	Description
Module	Module name is a mandatory field and has to be provided. It is recommended that the first two letters of the function id is kept as same as the module name. Naming of the generated package will be derived from the module code maintained.

- Script for the following tables will be generated by Workbench (menu details) which are essential for launching of an Online screen.
 - SMTB_MENU
 - SMTB_FCC_FCJ_MAPPING
 - SMTB_FUNCTION_DESCRIPTION
 - SMTB_ROLE_DETAILS

Type string of the Online screens will be generated as **O** in smtb_menu table.

- Transaction specific action codes has to checked in the control string whichever applicable.

Example: LIQUIDATE, ROLLOVER, REVERSAL etc.


2.3 Data Sources

This topic describes about defining the data sources for Online Forms.

On the **Function Generation** screen menu, click **DataSource**.

Identify the tables/views for the Online form. Define data sources and add data source fields as required.

Figure 2-4 Adding data sources and maintaining properties




Note the following while creating data sources:

- Master Data Source has to be a single entry data source.
- Logical Relationships has to be maintained for all data sources except the parent.
- Provide **PK Cols** and **PK Types** for all data sources. If the data source is a multi-record block, then make sure it has at least one more pk than its parent which helps to identify each record of multi-record block uniquely.

- Minimize the use of views in the data sources. For transaction screens, system generated upload logic (fn_sys_upload_db) is not called within the system package. It is up to the developer to decide whether the system generated code can be used or not. If views are used in data sources, then this function should not be used by the developer.
- Usually for Online forms, a separate view can be used for summary purpose. This view will have all the fields required to be displayed in the summary. Example: **UTDTXN01_SUMMARY**.

Figure 2-5 Adding data sources fields and its properties



Note:


Max length of the data source field can be modified as per requirement.

2.4 Data Blocks

This topic describes about defining the data blocks for Online Forms.


1. Determine the block structure for the function id. Define Data Blocks as per the design in the **Block Properties** screen.

Figure 2-6 Defining Data Blocks and maintaining its properties



2. Master Data Block has to be a single entry data block.
3. Provide **XSD Node** name if the block is normal and is required in gateway request.

Figure 2-7 Attaching Block Fields and maintaining its properties




4. Block order and block field order can be changed by rearranging blocks and block fields in the browser tree (drag and drop).

 Note:

Note that all units will have to be regenerated if block or block field order is changed (including xsd's).

5. Related currency fields should be placed above the amount field in the tree.
Add block fields to the data block as required.

Figure 2-8 Attaching Block Fields and maintaining its properties



The screenshot shows the 'Block Field Properties' dialog in the Oracle Flexcube Development Workbench. The field being configured is 'FUNDID'. The 'Return Fields Mapping' table at the bottom is as follows:

Query Column	Block Name	Return Field Name
☐ FUNDID	BLK_TRANSACTION_DETAILS	FUNDID
☐ FUNDIDENTIFICATIONNUM	BLK_TRANSACTION_DETAILS	FUNDIDENTIFICATIONNUM
☐ FUNDNAME	BLK_TRANSACTION_DETAILS	FUNDNAME
☒ FUNDBASECURRENCY	BLK_TRANSACTION_DETAILS	FUNDBASECURRENCY

6. In case the block is not required in XSD, select the **Not Required in XSD** checkbox.
7. Ensure that Related Block and Related Field are given for Amount Fields.
8. Minimize the use of query data sources by using DESC fields wherever possible.

 Note:

Query data sources is rarely required for a Online Form screen; as launch form can be used for query only screens.

9. Master block should contain reserved field names like AUTHSTAT, RECORDSTAT, ONCEAUTH, MODNO, MAKERID, CHECKERID, MAKERDTSTAMP and CHECKERDTSTAMP are added as part of the footer of the screen.

Figure 2-9 Master Block

2.5 Screens


This topic describes about designing the screens for Call Forms.

1. Design the screen layout based on the requirement in the **Screen Details**.

Figure 2-10 Designing Screens and providing Screen Properties

2. Identify one screen as the main screen; if multiple screens are present.
3. Add Tabs, sections and partitions as per the screen design.

Figure 2-11 Creating Tabs and maintaining Properties




4. When creating tabs and sections for the screen, if the screen does not have multiple tabs, then only the TAB_MAIN needs to be used. TAB_HEADER should not contain any sections in this scenario.
 5. Use all the tabs for Online forms. Since online forms are large screens with multiple tabs. TAB_HEADER should contain the header information. TAB_MAIN should be the first tab in the body. Other tabs have to be added in the body portion as required.
 6. Provide sections in TAB_FOOTER as required.
- The developer often designs footers for Online forms.

 Note:

In large screens, footer supports four partitions while other portions support three partitions.

Figure 2-12 Section Properties




Multiple Screens can be designed if required.

2.6 Field Sets

This topic describes about defining the field sets for Online Forms.

In the **Fieldset Properties** screen, create Fieldsets and attach the fields to the field sets as required.

Figure 2-13 Field Sets



Note the following when attaching field to a field set:

If a field is not required in the screen, but kept as hidden and value defaulted; then **The field has to be made invisible and attached to a field set**. If it is not attached to any fields set, the screen html won't contain the field and may result in script error while accessing the field.

2.7 Actions

This topic describes about the actions screen for Online Forms.

Mention the web service and amendable information in the **Form Actions** screen.

Figure 2-14 Actions Screen

Web Service	Action Code	Operation Code	Action Stage Type	Rest Enabled	Amendables	Comment Col
☒	QUERY	QueryIPSubscription	☒	☒	Amendables	Comments
☒	NEW	CreateIPSubscription	☒	☒	Amendables	Comments
☒	MODIFY	ModifyIPSubscription	☒	☒	Amendables	Comments
☒	AUTHORIZE	AuthorizeIPSubscription	☐	☒	Amendables	Comments
☒	DELETE	DeleteIPSubscription	☐	☒	Amendables	Comments
☐	CLOSE		☐	☐	Amendables	Comments
☐	REOPEN		☐	☐	Amendables	Comments
☒	REVERSE	ReverseIPSubscription	☐	☒	Amendables	Comments
☐	ROLLOVER		☐	☐	Amendables	Comments
☐	CONFIRM		☐	☐	Amendables	Comments
☐	LIQUIDATE		☐	☐	Amendables	Comments
☐	SUMMARYQUERY		☐	☐		Comments

Create Fieldsets and attach the fields to the field sets as required.

Mention the web service and amendable information in Actions Screen.


While maintaining web services and amendable information, note the following:

- Online forms will generate Type XSD and Message XSD. Operation-specific message xsd's will be generated. For example, name of the xsd generated will be:
 - LC-Contract-Types.xsd (Type XSD for LC Contract)
 - LC-CreateContract-Req-Full-MSG.xsd (Create Message XSD for LC Contract)
 - LC-CreateContract-Req-IO-MSG.xsd (Create Message XSD for LC Contract)
 - LC-CreateContract-Res-Full-MSG.xsd (Create Message XSD for LC Contract)
 - LC-CreateContract-Res-PK-MSG.xsd (Create Message XSD for LC Contract)
- Operation Id and Operation Code need to be maintained for the above reasons.
- Amendable information has to be maintained similar to any other function ids.


2.8 Launch Forms

This topic describes about the launch forms.

Launch Forms can be attached to Online form screen.

Figure 2-15 Launch Forms can be attached to Online form screen

Screen Arguments should be maintained for the launch form to query the proper contract record from the main online functions.


Figure 2-16 Process to attach launch forms is similar to any other function Id's

2.9 Call Forms

This topic describes about the call forms.

Call forms can be attached to Online form. Each call form should be mapped to Parent Data Block, Parent Data Source and proper relations should be maintained with parent data source of main online form.

Figure 2-17 Call Forms



Screen Arguments should be given to each callform. So that the call form will display the respective data of calling main function. Dependent Fields are required to re default the call form values when the user changes input data in the main form. Each of the subsystem pickup logic will have to be coded by the developer in release specific packages. Processing logic (sub system pickup) for the attached call forms has to be called from the main form package.

- [Sub System Pickup/Processing](#)
This topic describes about the sub system pickup/processing.

2.9.1 Sub System Pickup/Processing

This topic describes about the sub system pickup/processing.

Subsystem pickup refers to the process of picking up the values in sub systems. Normally values in sub systems will be defaulted based on the data given in the main screen of the online form.

1. Defaulting of sub system: After providing values in the main screen, user may click on any sub system to view or change the value. On clicking the sub system for the first time, sub system values will be defaulted based on the values provided in the main screen. Action code passed will be SUBSYSPKP. The code for defaulting will have to be written by the developer in corresponding hook packages in function.

Fn_Post_Subsys_Pickup

In this case SUBSYSSTAT for all subsystems will go as 'D' and processing done based on this flag for each sub system (call form). Note that SUBSYSPKP action will default values for all subsystems and not only the sub system being launched

Example: MICTRMIS:D; ISCTRSTL:D; TACTRTAX:D; CSCTRUDF:D; CFCTROCH:D; CSCTR ADV:D; FTCCGCLM:D;

If user saves the contract without visiting any call forms, then all the sub systems will be defaulted before saving

2. Uploading of sub system: If after launching the subsystem with defaulted values; User changes the value in subsystem; the new user input values has to be uploaded to the system. Hence while saving, the subsystems which has been modified by user will be uploaded while others will be defaulted. In this case SUBSYSSTAT for the subsystem which

has been modified will go as 'U'. Developer has to write code for processing based on the flag.

- *Example: if user changes MIS details (MICTRMIS) from what was defaulted; then SUBSYSSTAT will go as*
 - *MICTRMIS:U;ISCTRSTL:D;TACTRTAX:D;CSCTRUDF:D;CFCTROCH:D;CSCTRADV:D;FTCCGCLM:D;*
3. Re-defaulting of sub system: After launching and changing subsystem values; if user changes any values in main screen which are dependent field for the subsystem: subsystem values will have to be defaulted again based on the new main screen values. Hence the sub system will be re defaulted. In this case value entered by the user in sub system will be lost. In this case SUBSYSSTAT for the subsystem whose dependent fields has been modified will go as 'R'. Developer has to write code for processing based on the flag.
- *Example: In a Funds Transfer Contract Input Screen, assume that charge subsystem (CFCTROCH) is dependent on the values entered for debit and credit account. After launching the sub system and changing the charges manually; if user changes the account again the charges will have to re defaulted. The manually entered charges will not be considered. SUBSYSSTAT will go as*
 - *MICTRMIS:U;ISCTRSTL:D;TACTRTAX:D;CSCTRUDF:D;CFCTROCH:R;CSCTRADV:D;FTCCGCLM:D;*


Values for other subsystems will depend on each of their dependencies

2.10 Summary

This topic describes about the summary screen.

Summary screens can be designed for Online Form if required.

Figure 2-18 Summary



2.11 Preview

This topic describes about the preview.

The figure shows the preview of the Online form Input screen developed.

Figure 2-19 Input screen developed

The screenshot displays a software application window for entering transaction details. The window is titled 'New' and has a menu bar with 'Enter Query'. The main content area is organized into two primary sections: 'Transaction Information' and 'Transaction Value'. The 'Transaction Information' section contains multiple input fields for identifying the transaction, including Unit Holder ID, Fund ID, Order Received Date, Order Received Time Zone, Transaction Date, Payment Mode, Payment Mode Description, Transaction Number, Transaction Currency, Reference Number, Order Received Time (H4:Q4 M), Transaction Type, Description, and Transaction Category. The 'Transaction Value' section includes fields for Transaction Mode (set to 'Amount'), Units Applied, Amount Applied, and Percent Applied, along with buttons for 'Enrich Transaction' and 'Reset Transaction'. Below these sections is a tabbed interface with tabs for 'Unit And Fund', 'Transaction', 'Other', 'Intermediary', 'Load Override', 'KYC And Document', 'Add Info', 'Fee Payment', 'Certificate', and 'Unit Order'. The 'Unit And Fund' tab is currently active and shows fields for CF Number, Unit Deal, Unit Holder Name, Unit Signature, ISIN No, Fund Name, Fund Base Currency, and Price Currency. At the bottom of the window, there are fields for 'Input By', 'Authorized By', 'DateTime', 'Mod No', 'Authorization Status' (set to 'Unauthorized'), and 'Record Status' (set to 'Open'). 'Ok' and 'Exit' buttons are located in the bottom right corner.

Figure 2-20 Summary screen developed

Execute Query Advanced Search Reset Clear All

Authorization Status
Transaction Number
Fund ID
Currency of Expression
Transaction
Transaction Mode Not Selected
Dealing Date
Transaction Status Not Selected

Record Status
Reference Number
Unit Holder ID
Transaction Type
Transaction Date 2
Limit Order
Transaction Currency

Records per page 15 1 of 1 Go to Page

	Authorization Status	Record Status	Status	Transaction Number	Reference Number	Fund ID	Unit Holder ID	Curre
☐								
☐								
☐								
☐								
☐								
☐								

Find UH Authorize Delete Reverse Override

Exit

Generate the units for Online form and deploy them in the FLEXCUBE server for unit testing.

3

Generated Units

This topics describes about the generated units.

This topic contains the following sub-topics:

- [Front End Units](#)
This topic consists of front end units.
- [Data Base Units](#)
This topic describes about the data base units.
- [Other Units](#)
This topic describes about the other units used in the module.

3.1 Front End Units

This topic consists of front end units.

This topic consists of sub-topics:

- [Language xml](#)
This topic describes about the language xml.
- [SYS JavaScript File](#)
This topic describes about the SYS javaScript file.
- [Release Type Specific JavaScript File](#)
This topic describes about the release type specific javascript file.

3.1.1 Language xml

This topic describes about the language xml.

This file is an XML markup of presentation details, for the designed Call Form specific to a language.

Example – **UTDTXN01.xml** (UIXML for UT Screen).

3.1.2 SYS JavaScript File

This topic describes about the SYS javaScript file.

This JavaScript file mainly contains a list of declared variables required for the functioning of the screen.

Example – **UTDTXN01_SYS.js** (JS for UT Screen).

3.1.3 Release Type Specific JavaScript File

This topic describes about the release type specific javascript file.

This file won't be generated by the Tool. It has to be manually written by the developer if he has to write any code specific in that release.

Example – UTDTXN01_KERNEL.js (JS for KERNEL Release).

Example – UTDTXN01_CLUSTER.js (JS for CLUSTER Release).

Example – UTDTXN01_CUSTOM.js (JS for CUSTOM Release).

3.2 Data Base Units

This topic describes about the data base units.

This topic consists of sub-topics:

- [Static Scripts](#)
This topic describes about the static scripts.
- [System Packages](#)
This topic describes about the system packages.
- [Hook Packages](#)
This topic describes about the hook packages.

3.2.1 Static Scripts

This topic describes about the static scripts.

The following static scripts generated are required for the proper functioning of an Online Form screen. Refer document on generated units for detailed explanation.

3.2.2 System Packages

This topic describes about the system packages.

Main package would be generated by the Tool and should not be modified by the developer.

There is small change in the structure of the package depending on the type of the call form (Maintenance or Transaction).

Unlike normal maintenance function ids, call form packages does not have any call to the business logic within itself (similar to transaction function id). If developer wishes to uses any functions within the main package , call has to be made from the release specific package.

Main package contains functions for :

- Converting Ts to PL/SQL Composite Type
- Calling fn_main.
- Mandatory checks (fn_check_mandatory).
- Default and validation(fn_default_and_validate)
- Querying(fn_query)
- Converting the Modified Composite Type again to TS

Except the functions for type conversions, others functions calls the respective hook functions in hook packages of the call forms. Thus no processing logic within the main package is used It is to be noted that each of these functions are called from the main package of the main function id (where this call form is used) during respective stages.

But the package contains many other system generated functions for operations like

- Mandatory checks(fn_sys_check_mandatory)
- Default and validation(fn_sys_default_and_validate)
- Uploading to DB(fn_sys_upload_db)
- Query operation (fn_sys_query) etc

These functions are not called anywhere in the package. These functions if required can be called by the developer from the release specific package. Otherwise developer can write his own logic for the same in the Hook Packages

3.2.3 Hook Packages

This topic describes about the hook packages.

Release specific packages will be generated based on the release type (KERNEL.CLUSTER or CUSTOM). The structure of the package depends on the type of call form (Maintenance or Transaction). Developer can add his code in the release specific hook package.

Example –utpks_utdtxn01_kernel.spc, utpks_utdtxn01_kernel.sql (Kernel Package)utpks_utdtxn01_cluster.spc, utpks_utdtxn01_cluster.sql (Cluster Package)
utpks_utdtxn01_custom.spc, utpks_utdtxn01_custom.sql (Custom Package).

3.3 Other Units

This topic describes about the other units used in the module.

This topic consists of sub-topics:

- [Xsd](#)
This topic describes about the Xsd.

3.3.1 Xsd

This topic describes about the Xsd.

Only Type XSD will be generated for a Call Form function Id. Subscript **Subys** will be added before XSD Type identifier in the name of the generated xsd.

This type xsd will be used in the type xsd of any function which uses the particular call form.

Example – UT-FCISTransaction-Types.xsd (Type XSD for UT)UT-CreateTransaction -Req-Full-MSG.xsd (Create Message XSD for UT)UT-CreateTransaction -Req-PK-MSG.xsd (Create Message XSD for UT)UT-CreateTransaction -Res-Full-MSG.xsd (Create Message XSD for UT)
UT-CreateTransaction -Res-PK-MSG.xsd (Create Message XSD for UT).

4

Extensible Development

This topic describes about the extensible development.

Developer can add his code in hook packages and release specific JavaScript file.

This topic contains the following sub-topics:

- [Extensibility in JavaScript Coding](#)
This topic describes about the extensibility in javascript coding.
- [Extensibility in Backend Coding](#)
This topic describes about the extensibility in backend coding.

4.1 Extensibility in JavaScript Coding

This topic describes about the extensibility in javascript coding.

For release specific JavaScript coding, code has to be written in release specific JavaScript file. It follows the naming convention as : (Function Id)_(Release Type).js

Example: Code in **UTDTXN01_CLUSTER.js** is exclusive to cluster release

This JavaScript file allows developer to add functional code and is specific to release. The functions in this file are generally triggered by screen events. A developer working in cluster release would add functions based on two categories:

- Functions triggered by screen loading events
Example: **fnPreLoad_CLUSTER()**, **fnPostLoad_CLUSTER()**
- Functions triggered by screen action events
Example: **fnPreNew_CLUSTER ()**, **fnPostNew_CLUSTER ()**

4.2 Extensibility in Backend Coding

This topic describes about the extensibility in backend coding.

For online forms, generated code does not provide any business logic. Insert statements won't be present as part of generated code in online packages. Developer has to write the business logic in release specific packages (or make call to server functions from release specific packages).

Hooks will be provided in the following stages Resolving reference numbers:

- Checking mandatory fields
- Defaulting and validating
- Uploading to db
- Process
- Subsystem pickup
- Enrich

- Product Default
- Query




Note:

The system generated code for uploading; defaulting etc. (*fn_sys_default_and_validate*, *fn_sys_upload_db* etc.) won't be called by the main package in online flow. If it is required, developer has to call it explicitly from release specific packages.

In online flow, upload to base tables happens first and processing is done on the inserted data after uploading. After processing, the response type will be build.

Note that in online flow, upload to base tables happens first and processing is done on the inserted data after uploading. After processing, the response type will be build.

Figure 4-1 Flow of control in an Online main package



Release specific code has to be written in the Hook Packages generated. The different functions available in the Hook Package of an Online Form are:

1. Skip Handler : Pr_Skip_Handler

This can be used to skip the logic written in another release.

Example: logic written in **KERNEL** release can be skipped in **CLUSTER** release

2. Fn Main

This is called from the *fn_main* in main package.

3. **Fn_pre_resolve_ref_numbers**
4. **Fn_post_resolve_ref_numbers**
This function validates the reference number. It is called from `fn_resolve_ref_numbers` of the main package.
5. **Fn_pre_unlock**
6. **Fn_post_unlock**
This function holds the contract level validations and modification logic for existing contract. It is called from `fn_unlock` of main package.
7. **Fn_pre_check_mandatory**
8. **Fn_post_check_mandatory**
Any mandatory checks can be validated here. It is called from `fn_chchk_mandatory` of main package.
9. **Fn_pre_query**
10. **Fn_post_query**
Any specific logic while querying can be written in these functions. It is called from `fn_query` of the main package.
11. **Fn_pre_product_default**
12. **Fn_post_product_default**
This function has the logic to default the values for the contract based on the product maintenance. It is called from `fn_product_default` of main package.
13. **Fn_pre_subsys_pickup**
14. **Fn_post_subsys_pickup**
This function does the subsystem pickup for the subsystem's (call form's) as per product maintenance for the contract. It is called from `fn_subsys_pickup` of main package.
15. **Fn_pre_enrich**
16. **Fn_post_enrich**
After product default, user can default others values. That logic can be put here. it is called from `fn_enrich` of main package.
17. **Fn_pre_default_and_validate**
18. **Fn_post_default_and_validate**
Any release specific logic for defaulting and validation can be written here. It is called from the `fn_default_and_validate` in the main package.
19. **Fn_pre_upload_db**
20. **Fn_post_upload_db**
Any logic while uploading data to tables can be written here. It is called from `fn_upload_db` of main package.
21. **Fn_pre_process**
22. **Fn_post_process**
These hook functions are specific to transaction online form screens. This function should have the call to all the server functions which process the input data for the contract as per the functionality. These are called from **fn_process** of the main package.