

Oracle® FLEXCUBE Investor Servicing REST API Services Deployment in WebLogic



Release 14.8.0.0.0
G32104-02
April 2025

ORACLE®

Copyright © 2007, 2025, Oracle and/or its affiliates.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this is software, software documentation, data (as defined in the Federal Acquisition Regulation), or related documentation that is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, then the following notice is applicable:

U.S. GOVERNMENT END USERS: Oracle programs (including any operating system, integrated software, any programs embedded, installed, or activated on delivered hardware, and modifications of such programs) and Oracle computer documentation or other Oracle data delivered to or accessed by U.S. Government end users are "commercial computer software," "commercial computer software documentation," or "limited rights data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, reproduction, duplication, release, display, disclosure, modification, preparation of derivative works, and/or adaptation of i) Oracle programs (including any operating system, integrated software, any programs embedded, installed, or activated on delivered hardware, and modifications of such programs), ii) Oracle computer documentation and/or iii) other Oracle data, is subject to the rights and limitations specified in the license contained in the applicable contract. The terms governing the U.S. Government's use of Oracle cloud services are defined by the applicable contract for such services. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

Oracle®, Java, MySQL, and NetSuite are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Inside are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. AMD, Epyc, and the AMD logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark of The Open Group.

This software or hardware and documentation may provide access to or information about content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services unless otherwise set forth in an applicable agreement between you and Oracle. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services, except as set forth in an applicable agreement between you and Oracle.

Contents

Preface

Purpose	i
Audience	i
Documentation Accessibility	i
Critical Patches	ii
Diversity and Inclusion	ii
Conventions	ii
Screenshot Disclaimer	ii
Acronyms and Abbreviations	ii

1 REST Services Deployment in WebLogic

1.1	REST EJB Services Full Deployment	1
1.2	REST WebServices Full Deployment	7
1.3	Enable Logs for REST Application	14

Preface

Oracle FLEXCUBE Investor Servicing is a comprehensive mutual funds automation software from Oracle® Financial Servicing Software Ltd.©.

You can use the system to achieve optimum automation of all your mutual fund investor servicing processes, as it provides guidelines for specific tasks, descriptions of various features and processes, and general information.

This topic contains the following sub-topics:

- [Purpose](#)
- [Audience](#)
- [Documentation Accessibility](#)
- [Critical Patches](#)
- [Diversity and Inclusion](#)
- [Conventions](#)
- [Screenshot Disclaimer](#)
- [Acronyms and Abbreviations](#)

Purpose

This manual is designed to help acquaint you with the installation of **Oracle FLEXCUBE Investor Servicing** application.

Audience

This manual is intended for the following User/User Roles:

Table 1 Users and Roles

Users	Roles
Implementation team	Implementation of Oracle FLEXCUBE Investor Servicing
Presales team	Install Oracle FLEXCUBE Investor Servicing for demo purpose
Bank personnel	Who installs Oracle FLEXCUBE Investor Servicing

Documentation Accessibility

For information about Oracle's commitment to accessibility, visit the Oracle Accessibility Program website at <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=docacc>.

Access to Oracle Support

Oracle customer access to and use of Oracle support services will be pursuant to the terms and conditions specified in their Oracle order for the applicable services.

Critical Patches

Oracle advises customers to get all their security vulnerability information from the Oracle Critical Patch Update Advisory, which is available at [Critical Patches, Security Alerts and Bulletins](#). All critical patches should be applied in a timely manner to ensure effective security, as strongly recommended by [Oracle Software Security Assurance](#).

Diversity and Inclusion

Oracle is fully committed to diversity and inclusion. Oracle respects and values having a diverse workforce that increases thought leadership and innovation. As part of our initiative to build a more inclusive culture that positively impacts our employees, customers, and partners, we are working to remove insensitive terms from our products and documentation. We are also mindful of the necessity to maintain compatibility with our customers' existing technologies and the need to ensure continuity of service as Oracle's offerings and industry standards evolve. Because of these technical constraints, our effort to remove insensitive terms is ongoing and will take time and external cooperation.

Conventions

The following text conventions are used in this document:

Convention	Meaning
boldface	Boldface type indicates graphical user interface elements associated with an action, or terms defined in text or the glossary.
<i>italic</i>	Italic type indicates book titles, emphasis, or placeholder variables for which you supply particular values.
<code>monospace</code>	Monospace type indicates commands within a paragraph, URLs, code in examples, text that appears on the screen, or text that you enter.

Screenshot Disclaimer

Personal information used in the interface or documents is dummy and does not exist in the real world. It is only for reference purposes.

Acronyms and Abbreviations

The list of the acronyms and abbreviations used are as follows:

Table 2 Acronyms and Abbreviations

Abbreviation	Description
FCIS	Oracle FLEXCUBE Investor Servicing
OEM	Oracle Enterprise Manager

Table 2 (Cont.) Acronyms and Abbreviations

Abbreviation	Description
EMS	Electronic Messaging Service
EJB	Enterprise Java Bean
MDB	Message Driven Beans

1

REST Services Deployment in WebLogic

This topic describes the steps to install REST Services into WebLogic Application Server.

This topic contains the following sub-topics:

- [REST EJB Services Full Deployment](#)
This topic provides the systematic instructions to deploy REST EJB Services into weblogic server in full deployment mode.
- [REST WebServices Full Deployment](#)
This topic provides the systematic instructions to deploy REST WebServices into weblogic server in full deployment mode.
- [Enable Logs for REST Application](#)
This topic provides the systematic instructions to enable logging properties need to be set in the logging.xml.

1.1 REST EJB Services Full Deployment

This topic provides the systematic instructions to deploy REST EJB Services into weblogic server in full deployment mode.


Create a Datasource `jdbc/FCJDevDSSMS` that will be referring to the API DB before deploying the EAR.

Refer to the topic *Resource Creation* for more details on creating the data source.

1. Start **WebLogic Console**.

The following screen is displayed.

Figure 1-1 WebLogic Console



2. On **WebLogic Console** screen, enter the following details to log in WebLogic server.

Refer to the table for WebLogic Console details.


Table 1-1 WebLogic Console

Field	Description
Username	Enter WebLogic user name.
Password	Enter password for WebLogic.

- Click **Login**.

The following screen is displayed.


Figure 1-2 Home Screen



- Select **Deployments** from **Domain Structure**.

The following screen is displayed.


Figure 1-3 Domain Structure_Deployments



- Click **Install** from the **Deployments** to install a new module or application.

The following screen is displayed.

Figure 1-4 Deployments_Install




- You can click **Update** or **Delete** to update or delete the installed applications by selecting the checkbox next to the application name.
- Enter the complete path of the EAR.

Note

Only valid file paths are displayed.


- Choose the option **Upload your file(s)**, if deployment files could not be found in the path.

Figure 1-5 Click Upload your files



- Click **Next** to upload a deployment.
The following screen is displayed.


Figure 1-6 Upload a deployment to the Administration Server_No File Selected



10. Click **Browse** button to select an application or module. When you have located the file, click **Next** to upload this deployment to the Administration Server.

On successful deployment, the following screen is displayed.

Figure 1-7 Upload a deployment to the Administration Server_File uploaded




11. Choose installation type and scope. Select if the deployment should be installed as an application or library.

The options available are:


- Install this deployment as an application
- Install this deployment as a library
- Install this deployment as an application, but target the components individually

Figure 1-8 Installation Type




12. Select a **Scope** in which you want to install the deployment.

Figure 1-9 Scope




13. Click **Next** to select deployment targets.

Figure 1-10 Select Deployment Targets




14. Select the appropriate server where you want to deploy the EAR.
The following screen is displayed.

Figure 1-11 Servers




15. Click **Next** to modify or accept the default details such as Name, Security, and Source Accessibility.

Figure 1-12 Deployment Settings



16. Click **Finish** to complete the deployment.
The following screen is displayed.

Figure 1-13 Click Finish Button




17. Click **Save**.

On successful updation, below messages are displayed:

- All changes have been activated. No restarts are necessary.
- Settings updated successfully.

The following screen is displayed.

Figure 1-14 Click Save




1.2 REST WebServices Full Deployment

This topic provides the systematic instructions to deploy REST WebServices into weblogic server in full deployment mode.

1. Start **WebLogic console**.

The following screen is displayed.

Figure 1-15 WebLogic Console

2. On **WebLogic Console** screen, enter the following details to log in WebLogic server.

Refer to the table for WebLogic Console details.


Table 1-2 WebLogic Console

Field	Description
Username	Enter WebLogic user name.
Password	Enter password for WebLogic.

3. Click **Login**.

The following screen is displayed.


Figure 1-16 Home Screen



4. Select **Deployments** from **Domain Structure**.

The following screen is displayed.


Figure 1-17 Domain Structure_Deployments



5. Click **Install** from the **Deployments** to install a new module or application.

The following screen is displayed.

Figure 1-18 Deployments_Install




6. You can click **Update** or **Delete** to update or delete the installed applications by selecting the checkbox next to the application name.
7. Enter the complete path of the EAR.

Note

Only valid file paths are displayed below.


8. Choose the option **Upload your files**, if deployment files could not be found in the path.

Figure 1-19 Click Upload your files



9. Click **Next** to upload a deployment.
The following screen is displayed.


Figure 1-20 Upload a deployment to the Administration Server_No File Selected



10. Click **Browse** button to select an application or module. When you have located the file, click **Next** to upload this deployment to the Administration Server.

On successful deployment, the following screen is displayed.

Figure 1-21 Upload a deployment to the Administration Server_File uploaded




11. Choose installation type and scope. Select if the deployment should be installed as an application or library.

The options available are:


- Install this deployment as an application
- Install this deployment as a library
- Install this deployment as an application, but target the components individually

Figure 1-22 Installation Type




12. Select a **Scope** in which you want to install the deployment.

Figure 1-23 Scope




13. Click **Next** to select deployment targets.

Figure 1-24 Select Deployment Targets




14. Select the appropriate server where you want to deploy the EAR.
The following screen is displayed.

Figure 1-25 Servers




15. Click **Next** to modify or accept the default details such as Name, Security, and Source Accessibility.

Figure 1-26 Deployment Settings



16. Click **Finish** to complete the deployment.
The following screen is displayed.

Figure 1-27 Click Finish Button



17. Click **Save**.

On successful updation, below message is displayed All changes have been activated. No restarts are necessary.

The following screen is displayed.

Figure 1-28 Click Save




18. Click **Testing** tab to get wadl link.

Figure 1-29 Testing Tab

19. Select the servicename and click `/application.wadl` in the deployment tests table.

Some deployment types support test points, that can be used to verify that a deployment was successful and that the module is ready for use.

Figure 1-30 Deployment Tests



1.3 Enable Logs for REST Application

This topic provides the systematic instructions to enable logging properties need to be set in the logging.xml.

Log File

All the logs are stored in the file `ofss-rest-api.log` once the parameters are set.

Provide the below entry in the file, `{domain.home}\config\fmwconfig\servers\{server.name}\logging.xml`.

Syntax

```
<log_handler name='ofss-handler'
class='oracle.core.ojdl.logging.ODLHandlerFactory' level='TRACE:1'>

<property name='path'
value='${domain.home}/servers/${weblogic.Name}/logs/ofss-rest-api.log' />

<property name='maxFileSize' value='10485760' />

<property name='maxLogSize' value='104857600' />

<property name='encoding' value='UTF-8' />

<property name='useThreadName' value='true' />

<property name='supplementalAttributes'
value='DSID,J2EE_APP.name,J2EE_MODULE.name,WEBSERVICE.name,WEBSERVICE_PORT,
name,oracle.soa.tracking.FlowId,oracle.soa.tracking.InstanceId,oracle.soa.trackin
g.SCAEntityId,oracle .soa.tracking.FaultId,oracle.soa.tracking.RetryCount,composi
te_name' />

</log_handler>

<logger name='com.ofss' level='TRACE:1' useParentHandlers='false'>

<handler name='ofss-handler' />

</logger>
```