

Oracle Financial Services

Public APIs for Profitability and Balance Sheet Management Cloud Service



Release 23.09.01

F83683-03

October 2023

The Oracle logo, consisting of the word "ORACLE" in white, uppercase, sans-serif font, centered within a solid red square.

ORACLE®

Oracle Financial Services Public APIs for Profitability and Balance Sheet Management Cloud Service,
Release 23.09.01

F83683-03

Copyright © 2023, Oracle and/or its affiliates.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this is software, software documentation, data (as defined in the Federal Acquisition Regulation), or related documentation that is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, then the following notice is applicable:

U.S. GOVERNMENT END USERS: Oracle programs (including any operating system, integrated software, any programs embedded, installed, or activated on delivered hardware, and modifications of such programs) and Oracle computer documentation or other Oracle data delivered to or accessed by U.S. Government end users are "commercial computer software," "commercial computer software documentation," or "limited rights data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, reproduction, duplication, release, display, disclosure, modification, preparation of derivative works, and/or adaptation of i) Oracle programs (including any operating system, integrated software, any programs embedded, installed, or activated on delivered hardware, and modifications of such programs), ii) Oracle computer documentation and/or iii) other Oracle data, is subject to the rights and limitations specified in the license contained in the applicable contract. The terms governing the U.S. Government's use of Oracle cloud services are defined by the applicable contract for such services. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

Oracle®, Java, and MySQL are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Inside are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. AMD, Epyc, and the AMD logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark of The Open Group.

This software or hardware and documentation may provide access to or information about content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services unless otherwise set forth in an applicable agreement between you and Oracle. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services, except as set forth in an applicable agreement between you and Oracle.

Contents

1 Get Help

Access Help Content	1-1
Watch Video	1-1
Additional Resources	1-1
Learn About Accessibility	1-1
Get Support	1-1
Get Training	1-2
Join Our Community	1-2
Share Your Feedback	1-2

2 Getting Started

Prerequisites	2-1
Obtain Account Information	2-1
Authentication	2-1
Download the Application Certificate	2-2
Supported Methods	2-2
Media Types	2-2
Supported Headers	2-2
Status Code	2-3

3 Generating PAR URL for File Operations

Generating PAR URL for File Upload	3-1
End Point Details	3-1
Calling the API to Generate the URL	3-1
Request JSON Parameters	3-2
Response JSON Parameters	3-3
Viewing List of Uploaded Files	3-4

4 Generating PAR URL For File Download

Calling the API to Generate PAR URL for File Download Using File Name	4-1
---	-----

Calling the API to Generate PAR URL for File Download Using File ID 4-2

5 Invoking Export API

End Point Details 5-1

Response JSON Parameters 5-1

6 Invoking Import API

End Point Details 6-1

Response JSON Parameters 6-1

7 Get Export Status API

End Point Details 7-1

Response JSON Parameters 7-1

8 Get Status for Import API

End Point Details 8-1

Response JSON Parameters 8-1

9 Generate Report API

End Point Details 9-1

Request JSON Parameters 9-1

Response JSON Parameters 9-2

10 Get Report Generation Status and PAR URL Link API

End Point Details 10-1

Response JSON Parameters 10-1

List of Tables

2-1	Table: Supported Headers	2-2
2-2	Status Code	2-3
3-1	Request JSON Parameters	3-2
3-2	POST JSON Response	3-3

1

Get Help

This section describes the Get Help options in the AFCS application.

Access Help Content

Use the Help icon



to access help in the application. If you do not see any help icons on your page, click your avatar or name in the global header and select Show Help Icons.

Note that not all pages have help icons. You can also access the [Oracle Help Center](#) to find guides and videos.

Watch Video



Watch: This video tutorial shows you how to find and use help.

You can also [read about it](#) instead.

Additional Resources

- **Community:** Use [Oracle Cloud Customer Connect](#) to get information from experts at Oracle, the partner community, and other users.
- **Training:** Take courses on Oracle Cloud from [Oracle University](#).

Learn About Accessibility

For information about Oracle's commitment to accessibility, visit the [Oracle Accessibility Program](#). Videos included in this guide are provided as a media alternative for text-based topics also available in this guide.

Get Support

You can get support at [My Oracle Support](#).

For accessible support, visit [Oracle Accessibility Learning and Support](#).

Get Training

Increase your knowledge of Oracle Cloud by taking courses at the [Oracle University](#).

Join Our Community

Use [Cloud Customer Connect](#) to get information from industry experts at Oracle and in the partner community. You can join forums to connect with other customers, post questions, and watch events.

Share Your Feedback

We welcome your feedback about Oracle Applications user assistance. If you need clarification, find an error, or just want to tell us what you found helpful, we'd like to hear from you.

You can email your feedback to [My Oracle Support](#).

Thanks for helping us improve our user assistance!

2

Getting Started

Before executing the Rest APIs and performing various tasks, refer to the following topics to meet the necessary requirements.

- [Prerequisites](#)
- [Authentication](#)
- [Support Methods](#)
- [Support Headers](#)
- [Status Codes](#)

Prerequisites

The following are the set of prerequisites required for executing/invoking Rest APIs.

- Access to the Profitability and Balance Sheet Management Cloud Service.
- Appropriate User Privileges to access the services.
- Technical and Functional knowledge to understand and execute the REST APIs and configuration knowledge.
- Knowledge of REST Concepts, JSON, and browser-based REST Client.
- Knowledge of interactive and automatic tools to verify the APIs such as Postman and Command Line Interfaces (CLI).

Obtain Account Information

You can get the Identity Domain name from the account creation email sent by Oracle Support.

You can also contact your Service Administrator, to get the account information.

Authentication

The Authentication Process involves the use of cURL Commands in a CLI Tool to generate the access token and invoke REST APIs. The Authentication Token is generated through the OAuth Client ID and Secret Credentials created in IAM/IDCS during Provisioning. The Authentication Token does not require that you log in to the AFCS Application to invoke the REST APIs from external applications.

Ensure that you have the appropriate log-in credentials to access the Profitability and Balance Sheet Management Cloud Service and the appropriate roles to perform specific operations using the API Resources. The following is the list of steps for Authentication and further subsections provide the details: **check and change**

1. [Download the Application Certificate](#)
2. [Get the OAuth Client ID and Client Secret](#)

3. [Generate the Access Token](#)
4. [Invoke the API using the Access Token](#)
5. [#unique_31](#)

Download the Application Certificate

The Application Certificate is required for verification purposes when you use cURL commands. You may choose not to download the certificate if you plan to turn off the cURL Certificate Verification and use an insecure connection (if you add the `--insecure` flag to the cURL command).

To download the Application Certificate, do as follows:

1. Log in to the PBSM Application.
2. Click the **View site information/Verified by** icon in the Browser URL Address Bar.
3. Select **More information**.
4. Click **View Certificate** and then click **PEM(cert)** to download the certificate.

Supported Methods

- **GET**: Retrieve information about the service instance.
- **POST**: Create, scale, backup, start, and stop the service instance.

Media Types

The following media type is supported by the Accounting Foundation Cloud Service REST APIs:

- `application/json`

Supported Headers

The REST API supports headers that may be passed in the header section of an HTTP Request or Response.

Table 2-1 Table: Supported Headers

Headers	Description	Example
Content-Type	The media type of the body of the request. Required for POST and PUT requests, and the supported types vary with each endpoint.	Content-Type: application/json
Accept	The media type of the body of the response.	Accept: application/json

Status Code

When you call the Accounting Foundation Cloud Service REST APIs Resources, the Response Header returns one of the standard HTTP Status Codes.

Table 2-2 Status Code

HTTP Status Code	Description
200 OK	The request was successfully completed. A 200 status is returned for a successful GET or POST Method.
201 Created	The request has been fulfilled and resulted in a new resource being created. The response includes a Location Header containing the canonical URI for the newly created resource. A 201 status is returned from a synchronous resource creation or an asynchronous resource creation that was completed before the response was returned.
202 Accepted	The request has been accepted for processing, but the processing has not been completed. The request may or may not eventually be acted upon, as it may be disallowed at the time the processing takes place. When specifying an Asynchronous (<code>__detached=true</code>) Resource creation (for example, when deploying an application), or update (for example, when redeploying an application), a 202 is returned if the operation is still in progress. If <code>__detached=false</code> , a 202 may be returned if the underlying operation does not complete in a reasonable amount of time.
400 Bad Request	The request could not be processed because it contains missing or invalid information (such as a validation error on an input field, a missing required value, and so on).
401 Unauthorized	The request is not authorized. The Authentication Credentials included with this request are missing or invalid.
403 Forbidden	The user cannot be authenticated. The user does not have the authorization to perform this request.
404 Not Found	The request includes a resource URI that does not exist.
405 Method Not Allowed	The HTTP verb specified in the request (DELETE, GET, POST, PUT) is not supported for this request URI.

Table 2-2 (Cont.) Status Code

HTTP Status Code	Description
406 Not Acceptable	<p>The resource identified by this request is not capable of generating a representation corresponding to one of the media types in the Accept Header of the request.</p> <p>For example, the client's Accept Header request XML be returned, but the resource can only return JSON.</p>
409 Conflict	<p>The client's ContentType Header is not correct (for example, the client attempts to send the request in XML, but the resource can only accept JSON).</p>
415 Not Acceptable	<p>The client's ContentType Header is not correct (for example, the client attempts to send the request in XML, but the resource can only accept JSON).</p>
500 Internal Server Error	<p>The server encountered an unexpected condition that prevented it from fulfilling the request.</p>
503 Service Unavailable	<p>The server is unable to handle the request due to temporary overloading or maintenance of the server.</p> <p>The REST Web Application is not currently running.</p>

3

Generating PAR URL for File Operations

The PAR URL for File Operations API creates a PAR File that you can use to perform file operations in the Object Store for end-to-end integrations.

Generating PAR URL for File Upload

You can use this REST API to generate the PAR URL for File Upload. See the following sections for information on how to perform the POST operation.

Related Topics

- [Calling the API to Generate the URL](#)

End Point Details

- **Method** – POST
- **URL** - `https://<HOST_NAME:PORT>/<TENANT>/utils-service/v1/file/uploadfile/parURL?prefix=<prefix>`
- **Content-Type** - Application/Json

Calling the API to Generate the URL

To call the API, follow these steps:

1. Open a relevant tool, such as via cURL command.
2. Prepare a cURL command with the authentication token and other details. For more information refer to the following code.

Syntax

```
curl -k --location --request POST 'https://<hostname>/<TENANT-ID>/utils-service/v1/file/uploadfile/parURL?prefix=' \
--data-raw '{"fileName": "<remote filename>", "fileSize": <file size>, "mimeType": "<file type>"}' \
--header 'ofs_remote_user: <USERID>' \
--header 'locale: en-US' \
--header 'ofs_tenant_id: <TENANT-ID>' \
--header 'ofs_workspace_id: WS001' \
--header 'content-type: application/json' \
--header 'Authorization: Bearer <TOKEN>'
```

Example (truncated)

```
curl -k --location --request POST 'https://<hostname>/<TENANT-ID>/utils-service/v1/file/uploadfile/parURL?prefix=' \
--data-raw '{"fileName": "idcs_log1.txt", "fileSize": 100, "mimeType":
```

```

"text/plain"}' \
--header 'ofs_remote_user: cneadmin' \
--header 'locale: en-US' \
--header 'ofs_tenant_id: aaitestdev1001-prd' \
--header 'ofs_workspace_id: WS001' \
--header 'content-type: application/json' \
--header 'Authorization: Bearer
eyJ4NXQjUzI1NiI6Ildia25rQUR5TUZIMlhlQ1pKcTY1c3o4VzdEVWhKa0s4MldYY0ha
dk4wWkkiLCJ4
...
...
sQXj0iohsSIEmQXVvwjhhqnc4eJNnmCjx8Tb7TXjx1MIQLe0IcfrIj5gkzoMKX94_7US
xHv-6LhBzw'

```

Request JSON Parameters

This section provides the list of parameters in the JSON Request.

Table 3-1 Request JSON Parameters

Name	Type	Required	Description
fileName	STRING	Yes	<p>The name of the file to be uploaded.</p> <p>The following are the conditions for to enter in this field:</p> <ul style="list-style-type: none"> • Must start with an Alphanumeric Character • Allowed characters are alphabets, numbers, and special characters - hyphen(-), dot(.), and underscore(_) • Length of characters must not be greater than 255 characters

Table 3-1 (Cont.) Request JSON Parameters

Name	Type	Required	Description
fileSize	INTEGER	Yes	The size of the file (in Bytes) to be uploaded. The size of the file should be greater than 1 Byte and should be less than 10 TB. It is recommended to use multipart upload for uploading files of size more than 100 MB. For more information about uploading large objects and multipart uploads, refer to Working with Pre-Authenticated Requests .
contentType	STRING	Yes	The mime type to be uploaded. The following mime types are allowed: <ul style="list-style-type: none"> • Text/CSV • Text/plain • DAT

Request JSON Sample

```
[{
  "fileName": "File.csv",
  "fileSize": 7654,
  "contentType": "text/csv"
}]
```

Response JSON Parameters

This section provides the list of parameters in the JSON Response.

Table 3-2 POST JSON Response

Name	Type	Description
fileName	STRING	The name of the file to be uploaded.
uploadURL	STRING	The generated pre-authenticated URL to upload a file.
fileId	INTEGER	The unique File Identifier.

Response JSON Sample

```
{
  "payload": {
    "uploadURL": "https://objectstorage.us-
phoenix-1.oraclecloud.com/p/bdSI-
hzigiAoUU0lyEKnuK0YGs05L172gt_woZAgqNFYmUFQeexV3BDfT097mhBI/n/
oraclegbudevcorp/b/fsgbu_pbsm_cndevcorp_ftpqa101231-prd_default/o/
default/2023-01-31/jfr/f9ce031f-4a42-471d-b4da-d0577f3eca15",
    "createUser": "user1",
    "stripeName": "default",
    "fileId": 5025,
    "createDate": "2023-01-31T09:14:16",
    "token": "",
    "status": "success"
  }
}
```

Viewing List of Uploaded Files

Run the following cURL command to generate and view all the files that are uploaded using PAR URL.

Syntax

```
curl -k --location --request GET 'https://<hostname>/<TENANT-ID>/utils-
service/v1/listfiles stripeName=default' \
--header 'locale: en-US' \
--header 'ofs_remote_user: <user id>' \
--header 'ofs_tenant_id: < TENANT-ID >' \
--header 'ofs_workspace_id: WS001' \
--header "Authorization: Bearer <TOKEN>"
```

Example

```
curl -k --location --request GET 'https://dc.pbsmcloud.us-
phoenix-1.ocs.oc-test.com/aaitestdev1001-prd/utils-service/v1/
listfiles?stripeName=default' \
--header 'locale: en-US' \
--header 'ofs_remote_user: cneadmin' \
--header 'ofs_tenant_id: aaitestdev1001-prd' \
--header 'ofs_workspace_id: WS001' \
--header "Authorization: Bearer ${TOKEN}"
```

Response

```
{
  "payload": [
    {
      "v_file_name": "Idcs_log3.txt",
      "n_file_id": 9916,
      "d_upload_date": "31-
JAN-23
06:33:43 AM",
      "v_stripe_name": "default"
    },
    {
      "v_file_name": "Idcs_log4.txt",
      "n_file_id": 9917,
      "d_upload_date": "31-
```

```
JAN-23  
  06:40:25 AM,"v_stripe_name":"default"}}, "count":2}
```


4

Generating PAR URL For File Download

You can use this REST API to generate the PAR URL for File Download. See the following sections for information on how to perform the post operation.

Calling the API to Generate PAR URL for File Download Using File Name

To call the API, follow these steps:

1. Open a relevant tool, such as via the cURL command.
2. Prepare a cURL command with the authentication token and other details. For more information refer to the following code.

Syntax

```
curl -k --location --request GET < 'https://<hostname>/<TENANT-ID>/utils-  
service/v1/file/download?fileName=<file name>&stripeName=default&prefix='  
\  
--header 'ofs_remote_user: <userid>' \  
--header 'locale: en-US' \  
--header 'ofs_tenant_id: <TENANT-ID>' \  
--header 'ofs_workspace_id: WS001' \  
--header "Authorization: Bearer <TOKEN>"
```

Example

```
curl -k --location --request GET 'https://<hostname>/<TENANT-ID>/utils-  
service/v1/file/download?fileName=test3GB.xml&stripeName=default&prefix='  
\  
--header 'ofs_remote_user: cneadmin' \  
--header 'locale: en-US' \  
--header 'ofs_tenant_id: aaitestdev1001-prd' \  
--header 'ofs_workspace_id: WS001' \  
--header "Authorization: Bearer ${TOKEN}"
```

Response

```
{ "payload": { "downloadURL": "https://objectstorage.us-  
phoenix-1.oraclecloud.com/p/8R68eVcQAxQjNjK__S04MZjS-  
v4BqEbWSILvu0w40kJNrzfKeCB8vWBwugW5XvsK/n/oraclegbudevcorp/b/  
fsgbu_pbsm_cndevcorp_aaitestdev1001-prd_default/o/default/2023-01-20/rnz/  
6c023e75-09e2-4265-815e-32cedcd2415e?  
httpResponseContentDisposition=ATTACHMENT%3B%20filename%3Dtest3GB.xml" } }
```

Calling the API to Generate PAR URL for File Download Using File ID

To call the API, follow these steps:

1. Open a relevant tool, such as via the cURL command.
2. Prepare a cURL command with the authentication token and other details. For more information, refer to the following code.

Syntax

```
curl -k --location --request GET 'https://<hostname>/<TENANT-ID> /
utils-service/v1/file/downloadfile/<file id>' \
--header 'ofs_remote_user: <userid>' \
--header 'locale: en-US' \
--header 'ofs_tenant_id: < TENANT-ID> ' \
--header 'ofs_workspace_id: WS001' \
--header "Authorization: Bearer <TOKEN>"
```

Example

```
curl -k --location --request GET 'https://<hostname>/<TENANT-ID>/
utils-service/v1/file/downloadfile/9916' \
--header 'ofs_remote_user: cneadmin' \
--header 'locale: en-US' \
--header 'ofs_tenant_id: aaitestdev1001-prd' \
--header 'ofs_workspace_id: WS001' \
--header "Authorization: Bearer ${TOKEN}"
```

Response

```
{"payload":{"downloadURL":"https://objectstorage.us-
phoenix-1.oraclecloud.com/p/
gTxxzhqLEea4Or2TRkBqTqHxt_JogVFfa9G_0wtN8NYy_op0Zk4lvKGDxxeXGhLq7/n/
oraclegbudevcorp/b/fsgbu_pbsm_cndevcorp_aaitestdev1001-
prd_default/o/default/2023-01-31/fae/2d63d2fe-2090-4fb7-
a4c8-9940d22987db?
httpResponseContentDisposition=ATTACHMENT%3B%20filename%3DIids_log3.
txt"}}
```

5

Invoking Export API

You can use Invoke Export API to export migration definitions that are created using the application interface.

For more information about Invoke Export API, refer to

- [Endpoint details](#)
- [Response JSON Parameters - Invoke Export API](#)

End Point Details

- **Method** – POST
- **REST Endpoint** -/public/migrate/export/{code}, where code is the migration ID.
- **Content-Type** - application/json

Request Headers Details

The following table lists the Request Headers:

- **ofs_tenant_id** - Tenant ID of the Application.
- **Locale** - Local language in the language code format. For example, en-US.
- **ofs_remote_user** - User ID of the user.
- **ofs_workspace_id** - Workspace ID of the Application. The default value is WS001 and same should be passed each time.

Response JSON Parameters

This section provides the list of parameters in the JSON Response.

Sample Response

```
Success:200
{
  "errorMessage": "Object Migration Triggered",
  "statusCode": "TRIGGERED_SUCCESS",
  "status": "SUCCESS"
}
Error: 400
{
  "errorMessage": "Export already completed",
  "statusCode": "EXPORT_ALREADY_COMPLETE",
  "status": "FAILED"
}
{
  "errorMessage": "Code does not exist",
  "statusCode": "INVALID_INPUT",
```

```
"status": "FAILED"  
}  
{  
  "errorMessage": "Export in progress",  
  "statusCode": "EXPORT_INPROGRESS",  
  "status": "INPROGRESS"  
}  
Error :500  
{  
  "errorMessage": "Internal Server Error",  
  "statusCode": "INTERNAL_ERROR",  
  "status": "FAILED"  
}
```

6

Invoking Import API

You can use Invoke Import API to import migration definitions that are created using the application interface.

For more information about Invoke Import API, refer to

- [Endpoint details](#)
- [Response JSON Parameters - Invoke Import API](#)

End Point Details

- **Method** – POST
- **REST Endpoint** -/public/migrate/import/ {code}, where code is the migration ID.
- **Content-Type** - application/json

Request Headers Details

The following table lists the Request Headers:

- **ofs_tenant_id** - Tenant ID of the Application.
- **Locale** - Local language in the language code format. For example, en-US.
- **ofs_remote_user** - User ID of the user.
- **ofs_workspace_id** - Workspace ID of the Application. The default value is WS001 and same should be passed each time.

Response JSON Parameters

This section provides the list of parameters in the JSON Response.

Sample Response

```
Success:200
{
  "errorMessage": "Object Migration Triggered",
  "statusCode": "TRIGGERED_SUCCESS",
  "status": "SUCCESS"
}
Error: 400
{
  "errorMessage": "Import already completed",
  "statusCode": "IMPORT_ALREADY_COMPLETE",
  "status": "FAILED"
}
{
  "errorMessage": "Code does not exist",
  "statusCode": "INVALID_INPUT",
```

```
"status": "FAILED"  
}  
{  
  "errorMessage": "Import in progress",  
  "statusCode": "IMPORT_INPROGRESS",  
  "status": "INPROGRESS"  
}  
Error :500  
{  
  "errorMessage": "Internal Server Error",  
  "statusCode": "INTERNAL_ERROR",  
  "status": "FAILED"  
}
```

7

Get Export Status API

You can use Get Export Status API to view the export status of an ongoing migration .

For more information about the API, refer to

- [Endpoint details](#)
- [Response JSON Parameters - Get Export Status API](#)

End Point Details

- **Method** – GET
- **REST Endpoint** -/Public/status/export/{code}, where code is the migration ID.
- **Content-Type** - application/json

Request Headers Details

The following table lists the Request Headers:

- **ofs_tenant_id** - Tenant ID of the Application.
- **Locale** - Local language in the language code format. For example, en-US.
- **ofs_remote_user** - User ID of the user.
- **ofs_workspace_id** - Workspace ID of the Application. The default value is WS001 and same should be passed each time.

Response JSON Parameters

This section provides the list of parameters in the JSON Response.

Sample Response

```
Success:200
{
  "errorMessage": "Status fetched Successfully",
  "statusCode": "SUCCESS",
  "status": "SUCCESS"
}
Error: 400
{
  "errorMessage": "Code does not exist",
  "statusCode": "INVALID_INPUT",
  "status": "FAILED"
}
{
  "errorMessage":"Code does not exist",
  "statusCode": "INVALID_INPUT",
  "status": "FAILED"
```

```
}  
Error :500  
{  
  "errorMessage": "Internal Server Error",  
  "statusCode": "INTERNAL_ERROR",  
  "status": "FAILED"  
}
```


8

Get Status for Import API

You can use Get Import Status API to view the import status of an ongoing migration .

For more information about Get Import Status API, refer to

- [Endpoint details](#)
- [Response JSON Parameters - Get Import Status API](#)

End Point Details

- **Method** – GET
- **REST Endpoint** -/public/status/import/ {code}, where code is the migration ID.
- **Content-Type** - application/json

Request Headers Details

The following table lists the Request Headers:

- **ofs_tenant_id** - Tenant ID of the Application.
- **Locale** - Local language in the language code format. For example, en-US.
- **ofs_remote_user** - User ID of the user.
- **ofs_workspace_id** - Workspace ID of the Application. The default value is WS001 and same should be passed each time.

Response JSON Parameters

This section provides the list of parameters in the JSON Response.

Sample Response

```
Success:200
{
  "errorMessage": "Status fetched Successfully",
  "statusCode": "SUCCESS",
  "status": "SUCCESS"
}
Error: 400
{
  "errorMessage": "Code does not exist",
  "statusCode": "INVALID_INPUT",
  "status": "FAILED"
}
{
  "errorMessage":"Code does not exist",
  "statusCode": "INVALID_INPUT",
  "status": "FAILED"
```

```
}  
Error :500  
{  
  "errorMessage": "Internal Server Error",  
  "statusCode": "INTERNAL_ERROR",  
  "status": "FAILED"  
}
```

9

Generate Report API

Use Generate Report API, to generate report based on the given input data.

For more information about Generate Report API, refer to

- [Endpoint Details](#)
- [Request JSON Parameters](#)
- [Response JSON Parameters](#)

End Point Details

- **Method** – POST
- **REST Endpoint** - /aai-dmi-service/vw/v1/repgen
- **Content-type** - application/json

Request Headers Details

- **ofs_remote_user** - (String). User ID of the user.
- **ofs_service_id** - (String). The unique service ID associated with the report.
- **ofs_workspace_id** - (String). The Workspace ID of the Application. It is defaulted to “WS001” and same should be passed each time.
- **Locale** - (String). The local language in the language code format. For example, en-US.
- **reportcode** - (String). The auto-generated code for the specific report. You can get this code from the Report Details page.
- **reportType** - (String). The report file format.
- **appid** - (String). Respective application ID of the cloud service
- **reportDefType** - (String). The report definition type. By default this value is set to **V** (View).

Request JSON Parameters

Request JSON Parameters for Generate Report API

- **filterCriteria** - The filter conditions set to include a specific set of data in the report, using the defined expressions. You can add the filter criteria in the Filter Conditions page.

Request JSON Sample when there is no filter

```
{  
  "filterCriteria": ""  
  "placeholderFilter": ""  
}
```

Request JSON Sample when filter applied

```
{
  "filterCriteria": "FSI_ACCID_HEALTH_INS_CO_CD.CREATED_BY =
    'DMIUSER1'"
}
{
  "filterCriteria": "FSI_ACCID_HEALTH_INS_CO_CD.CREATED_BY = 'DMIUSER1'
AND
  FSI_ACCID_HEALTH_INS_CO_CD.CO_ID IN ('100', '200') "
}
{ "filterCriteria": "FSI_ACCID_HEALTH_INS_CO_CD.CREATED_BY =
'DMIUSER1' AND
  FSI_ACCID_HEALTH_INS_CO_CD.CO_ID IN ('100', '200') ",
  "placeholderFilter":
  "FSI_ACCID_HEALTH_INS_CO_CD.CURRENCY = PLACEHODER1 AND
FSI_ACCID_HEALTH_INS_CO_CD.COUNTRY =
  'IND' AND FSI_ACCID_HEALTH_INS_CO_CD.AS_OF_DATE = PLACEHOLDER2 "
}
```

Response JSON Parameters

Sample Response

```
{
  "status": "PENDING",
  "requestInstanceId": "100"
}
```

10

Get Report Generation Status and PAR URL Link API

View the report generation status and also get a pre-authenticated URL (PAR URL), to download the report in CSV format, using the Get Report Generation Status and PAR URL Link API.

The status response can contain the following values:

- **COMPLETED** - When the export API execution is completed successfully and response is generated.
- **PENDING** - denotes that the report export is yet to start and is in the queue.
- **RUNNING** - When the API execution is in progress.
- **FAILED** - When the Export API execution is not completed successfully.

For more information about this API,

- [Endpoint Details](#)
- [Response JSON Parameters](#)

End Point Details

- **Method** – POST
- **REST Endpoint** - aai-dmi-service/vw/v1/repgenstatus
- **Content-type** - application/json

Request Headers Details

- **ofs_remote_user** - (String). User ID of the user.
- **ofs_service_id** - (String). The unique service ID associated with the report.
- **ofs_workspace_id** - (String). The Workspace ID of the Application. It is defaulted to "WS001" and same should be passed each time.
- **Locale** - (String). The local language in the language code format. For example, en-US
- **reportcode** - (String). The auto-generated code for the specific report. You can get this code from the Report Details page.
- **reportInstanceID** - (Integer). The instance ID of the report which is being exported. You can get the report /request instance ID from [Response JSON Parameters](#) of [Generate Report API](#).

Response JSON Parameters

This section provides the list of parameters in the JSON Response.

- **requestInstanceID** - (String). Request Instance ID of the export process

- **downloadlink** - (String). Click the link to download the document.
- **status** - (String). Status of the export

Sample Response

- The following sample response is generated, when the Download report request is in progress.

```
Report Request Accepted
{
  "status": "PENDING",
  "requestInstanceId": "100"
}
Report Request is being processed
{
  "status": "RUNNING",
  "requestInstanceId": "100"}
Report Request Generation Failed
{
  "status": "FAIL",
  "reportInstanceId": "100"}
Report Request Generation Completed - for higher volume
{
  "status": "COMPLETE",
  "reportInstanceId": "100",
  "downloadLink": "<url>"
}
```

- The following sample response is generated , when the download request is processed and the PAR URL to download the report is included in the response. You can copy the PAR URL and paste it in a Web browser, to download the report in CSV format.

```
"requestInstanceId": "183",
"downloadLink": "<URL>",
"status": "COMPLETE"
```

- The following sample response is generated , when the download request is in pending status.

```
{"requestInstanceId": "161", "status": "PENDING"}
```