# **Oracle®**

# Oracle Financial Services Model Management and Governance Installation and Configuration Guide





Oracle Oracle Financial Services Model Management and Governance Installation and Configuration Guide, Release 8.1.3.2.0

G18356-08

Copyright © 2014, 2025, Oracle and/or its affiliates.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this is software, software documentation, data (as defined in the Federal Acquisition Regulation), or related documentation that is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, then the following notice is applicable:

U.S. GOVERNMENT END USERS: Oracle programs (including any operating system, integrated software, any programs embedded, installed, or activated on delivered hardware, and modifications of such programs) and Oracle computer documentation or other Oracle data delivered to or accessed by U.S. Government end users are "commercial computer software," "commercial computer software documentation," or "limited rights data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, reproduction, duplication, release, display, disclosure, modification, preparation of derivative works, and/or adaptation of i) Oracle programs (including any operating system, integrated software, any programs embedded, installed, or activated on delivered hardware, and modifications of such programs), ii) Oracle computer documentation and/or iii) other Oracle data, is subject to the rights and limitations specified in the license contained in the applicable contract. The terms governing the U.S. Government's use of Oracle cloud services are defined by the applicable contract for such services. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

Oracle®, Java, MySQL, and NetSuite are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Inside are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. AMD, Epyc, and the AMD logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark of The Open Group.

This software or hardware and documentation may provide access to or information about content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services unless otherwise set forth in an applicable agreement between you and Oracle. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services, except as set forth in an applicable agreement between you and Oracle.

# Contents

Pre	eface	
1.1	Audience	1-1
1.2	Additional Resources	1-1
1.3	Conventions	1-1
1.4	Abbreviations	1-2
Intr	oduction	
2.1	Components of Oracle Financial Services Model Management and Governance	2-1
2.2	Installation Check List	2-2
На	rdware and Software Requirements	
3.1	License Information	3-1
Pre	einstallation	
4.1	Oracle Database Instance Settings	4-1
4.2	Create the Database Schema on Oracle Database	4-1
	4.2.1 Creating an Oracle User	4-1
	4.2.2 Creating the Application Configuration Schema	4-2
	4.2.3 Create the MMG Studio Schema	4-2
	4.2.4 Create MMG Graph Schema	4-3
4.3	Create the Installation, Download, and Metadata Repository Directories	4-4
4.4	Configure the OS File System Settings and Environment Settings in the .profile File	4-4
	4.4.1 Configure Operating System and File System Settings	4-5
	4.4.2 Configure the Environment Settings	4-6
	4.4.2.1 Java Settings	4-6
	4.4.2.2 Oracle Database Server and Client Settings	4-7
	4.4.2.3 TNS entries in the tnsnames.ora file for Non-TCPS	4-7
	4.4.2.4 Time Zone Settings	4-8
4.5	Prerequisite for Data Pipeline	4-8
4.6	Setup Password Stores with Oracle Wallet	4-9
	4.6.1 Setup the Password Stores for Database User Accounts	4-9



# 5 Installation

5.1 Prerequisites	5-1
5.2 Download the OFS MMG Installer Kit	5-1
5.3 Extract the Software	5-2
5.4 Configure the config.sh file	5-3
5.4.1 Import Server Certificate to Java Keystore	5-30
5.5 Run the MMG Installer	5-30
5.6 Starting MMG Services	5-32
5.7 Stopping MMG Services	5-33
5.8 Generate GRAPH-KEYSTORE.P12	5-33
5.9 Installing Conda	5-34
5.10 Installing Python Library	5-34
5.10.1 Prerequisites	5-34
5.10.2 Procedure	5-35
5.11 Setting up the Environment for Hive Data Sourcing	5-37
5.12 Remote MMG Studio Configuration	5-39
5.13 PGX Installation	5-40
5.13.1 Configure the config.sh File of PGX	5-41
5.13.2 Starting PGX Server	5-43
5.13.3 Stopping PGX Server	5-43
5.14 R Interpreter	5-43
5.14.1 Installing Oracle R Distribution	5-44
5.14.2 R 4.1.2 Installation	5-44
5.14.3 MMG Connection Objects Library Setup	5-44
5.14.3.1 Installing ROracle Library	5-44
5.14.3.2 Installing RODBC Library	5-45
5.14.4 Installing the IRkernel	5-46
5.14.5 Configuring R Interpreter	5-47
5.14.6 Using MMG Studio to Oracle Connection Objects	5-47
5.14.6.1 Workspaces	5-47
5.14.6.2 Connections	5-48
5.15 Multi Level Approval	5-48
5.16 Kafka Installation	5-49
Post-installation Steps	
6.1 Access the Application	6-1
6.2 Create Application Users	6-1
6.3 Map Application User(s) to User Group	6-1



6

	6.4 Model Techniques/ Model Library	6-3
	6.5 .PEM file creation for Model Service	6-3
	6.6 Access and Permissioning Management	6-3
	6.6.1 Access MMG using AAI Realm	6-4
	6.6.1.1 Prerequisites	6-5
	6.6.2 Access MMG using SAMLRealm	6-6
	6.7 AAI User Provisioning SQL Scripts Generator Utility	6-7
	6.8 IDCS Server Configuration	6-7
7	Upgrade Installation	
	7.1 Upgrading to 8.1.3.2.0	7-1
8	Update Utility to Reconfigure Installation Parameters	
0	Claring the MMC Instance	
9	Cloning the MMG Instance	
	9.1 Copying the Directories	9-1
	9.2 Copying the Database Schemas	9-1
	9.3 Configuring Password Store with Oracle Wallet	9-1
	9.4 Updating the Host Details	9-2
	9.5 Update LOG_HOME and FTPSHARE	9-2
	9.6 Setting up the SSL Keystore	9-3
	9.7 Updating Wallet Aliases for Oracle Schemas	9-3
	9.8 Updating Context and Ports	9-3
	9.9 Starting MMG Services	9-4
	9.10 Cloning the Environment	9-4
10	Frequently Asked Questions (FAQs) and Error Dictiona	ary
	10.1 Frequently Asked Questions	10-1
	10.1.1 Frequently Asked Questions	10-1
	10.1.2 Application Pack 8.1.3.1.0 FAOs	10-17



1

# **Preface**

This section provides information about the Oracle Financial Services Model Management and Governance (OFS MMG) Installation and Configuration Guide.

#### **Topics:**

### 1.1 Audience

OFS MMG Installation and Configuration Guide is intended for Administrators and Implementation Consultants who handle installing and maintaining the Application Pack Components.

This document assumes that you have experience in installing Enterprise Components and basic knowledge about the following:

- OFS AAI Components
- OFSAA Architecture
- UNIX Commands
- Database Concepts
- Web Server or Web Application Server

# 1.2 Additional Resources

This section identifies additional resources to the OFS MMG Application. You can access the following documents from the Oracle Help Center:

- OFS Model Management and Governance Release Notes
- OFS Model Management and Governance User Guide

Additional related documents are as follows:

OFS Analytical Applications 8.1.2.0.0 Technology Matrix



In the Tech Matrix, the Java Version column is no longer applicable for release 8.1.3.1.0. Instead, Java "17" 2021-09-14 LTS is applicable.

# 1.3 Conventions

The following text conventions are used in this document:

**Table 1-1 Document Conventions** 

Convention	Meaning
boldface	Boldface type indicates graphical user interface elements associated with an action or terms defined in text or the glossary.
italic	Italic type indicates book titles, emphasis, or placeholder variables for which you supply particular values.
monospace	Monospace type indicates commands within a paragraph, URLs, code in examples, file names, text that appears on the screen, or text that you enter.
Hyperlink	Hyperlink type indicates the links to external websites, internal document links to sections.

# 1.4 Abbreviations

The following table lists the Abbreviations used in this document:

**Table 1-2 Abbreviations** 

Abbreviation	Meaning
BDP	Big Data Processing
DBA	Database Administrator
DDL	Data Definition Language
DEFQ	Data Entry Forms and Queries
DML	Data Manipulation Language
EAR	Enterprise Archive
EJB	Enterprise JavaBean
ERM	Enterprise Resource Management
FTP	File Transfer Protocol
HDFS	Hadoop Distributed File System
HTTPS	Hypertext Transfer Protocol Secure
J2C	J2EE Connector
J2EE	Java 2 Enterprise Edition
JCE	Java Cryptography Extension
JDBC	Java Database Connectivity
JDK	Java Development Kit
JNDI	Java Naming and Directory Interface
JRE	Java Runtime Environment
JVM	Java Virtual Machine
LDAP	Lightweight Directory Access Protocol
LHS	Left Hand Side
MFA	Multi-Factor Authentication
MOS	My Oracle Support
OFSAA	Oracle Financial Services Analytical Applications
OFS AAI	Oracle Financial Services Analytical Application Infrastructure



Table 1-2 (Cont.) Abbreviations

Abbreviation	Meaning
OFS MMG	Oracle Financial Services Model Management and Governance Application
OHC	Oracle Help Center
OLAP	On-Line Analytical Processing
OLH	Oracle Loader for Hadoop
ORAAH	Oracle R Advanced Analytics for Hadoop
OS	Operating System
RAM	Random Access Memory
RDBMS	Relational Database Management System
RHEL	Red Hat Enterprise Linux
SFTP	Secure File Transfer Protocol
SID	System Identifier
SSL	Secure Sockets Layer
TNS	Transparent Network Substrate
URL	Uniform Resource Locator
VM	Virtual Machine
WAR	Web Archive
XML	Extensible Markup Language
PGX	Parallel Graph AnalytiX
FQDN	Fully Qualified Domain Name



# Introduction

Financial Institutions require models that work on traditional statistical techniques, modern machine-learning methods, computational and simulation models. Oracle Financial Services Model Management and Governance leverage the Data Studio environment to develop, deploy, and manage models at the enterprise level.

The OFS Model Management and Governance Application enables institutions to implement their IT policies while providing flexibility and freedom that Data Scientists and Statistical Modelers desire. OFS MMG's design facilitates financial institutions to manage external regulatory and internal governance policies by building testing models in a workspace environment. A workspace is provisioned and authorized for use (usually by an Administrator) before making it available to modelers. Administrative users grant analysts and modelers access to workspaces along with a subset of production data to build models. Validated and approved models can then be promoted from workspaces to the enterprise model repository. Models in the repository can then be woven into analytical application flows crafted by mixing data management tasks, model execution, and deterministic business logic.

#### Topics:

# 2.1 Components of Oracle Financial Services Model Management and Governance

The following are the components of Oracle Financial Services Model Management and Governance Application:

- Workspace Management
- Model Management
- Dataset
- Model Pipelines
- Model Actions
- Graphs
- Scheduler Service
- Audit Trail
- Data Studio Options
- Object Migration
- Model Training

For more information on how to use the application, see the OFS Model Management and Governance User Guide.

# 2.2 Installation Check List

To complete the installation process, you must perform the following steps listed in the Preinstall Checklist. Use this checklist to verify whether these steps are completed or not.

Table 2-1 Installation Checklist

SI. No.	Activity
Pre-installation Steps	
1	Install all the prerequisite <i>hardware and software</i> as per the OFS Analytical Applications 8.1.2.0.0 Technology Matrix.
2	Configure the Database Instance Settings.
	In the Tech Matrix, the Java Version column is no longer applicable for release 8.1.3.1.0. Instead, Java 17.x is applicable.
3	Create the Installation, Download, and Metadata Repository Directories:
	<ul> <li>Installation Directory</li> <li>Temporary Directory</li> <li>Staging Area/Metadata Repository</li> <li>Download Directory</li> </ul>
4	Configure the following Operating System and File System Settings:
	File Descriptor
	Total number of processes
	<ul><li>Port(s)</li><li>.profile file permissions</li></ul>
	Add FTP or SFTP Configuration for file transfer (to access Staging Area and Metadata Directory)
5	Update the following Environment Settings as required for the installation in the .profile file:
	<ul> <li>Java Settings</li> <li>Oracle Database Server and Client Settings</li> </ul>
	<ul> <li>Add TNS entries in the TNSNAMES.ORA file</li> </ul>
	<ul> <li>Time Zone Settings</li> </ul>
Installation Steps	
6	Download the Installer Kit.
7	Extract the Installer Kit.
8	Configure the config.sh file.



Table 2-1 (Cont.) Installation Checklist

SI. No.	Activity
9	Trigger the Application Installation.
Post-Installation Steps	
10	Access the MMG Application.
11	Create Application Users.
12	Map Application User(s) to User Groups.



MMG v8.1.3.1.0 and MMG v8.1.3.2.0 supports Python 3.9.x, Python 3.10.x, Python 3.11.x, and Python 3.12.x. Apache link packages are not supported with Python 3.12.x.



# Hardware and Software Requirements

The following are the hardware and software requirements:

Table 3-1 Hardware and Software Requirements

Category	Version
Processor Type	Linux x86-64
OS Version	Oracle Linux Server release 8.4 and later versions
Java Version	OpenJDK 17.0.x
Database Server	Oracle Database 19c (19.3+) Enterprise Ed.
Java	Version 17 and 21
Oracle Database	Version 19 and 23
Python	Version 3.8-12
Python	Version 3.10
OS	OEL9, OEL8 and Solaris

# 3.1 License Information

For details on the third-party software tools used, see the OFSAA Licensing Information User Manual Release 8.1.2.0.0.



Beginning with release 8.1.3.1.0, the Java Version column in the Tech Matrix is no longer applicable. Java 17.x is now the only supported version for this release.



Support for Java 17 and 21 from Release 8.1.3.2.0

4

# Preinstallation

This section lists all the prerequisites to install OFS MMG.

# 4.1 Oracle Database Instance Settings

Ensure that the following database instance settings are configured:

- NLS\_CHARACTERSET to AL32UTF8
- NLS\_LENGTH\_SEMANTICS to BYTE
- OPEN CURSORS limit to greater than 1000

# 4.2 Create the Database Schema on Oracle Database

Create the following Database Schemas:

- MMG Studio Schema
- MMG Graph Schema

#### **Tablespace**

You can either use the existing Tablespace or can create a new Tablespace during schema creation using the following script:

#### **Permanent Tablespace**

```
CREATE TABLESPACE <tablespace_name >

DATAFILE '<tablespace_name >.dat'

SIZE 1G

ONLINE;
```

#### **Temporary Tablespace**

```
CREATE TEMPORARY TABLESPACE <tablespace_name >
TEMPFILE '<tablespace_name >.dbf'
SIZE 100M;
```

# 4.2.1 Creating an Oracle User

You can create an Oracle user using the following script:

CREATE USER <oracle\_user\_name> IDENTIFIED BY <password> DEFAULT TABLESPACE USERS TEMPORARY TABLESPACE TEMP QUOTA <quota size>|UNLIMITED ON USERS

# 4.2.2 Creating the Application Configuration Schema

Create the STSA Application Schema. You must create an Oracle User to create the STSA Application Schema. For more details, see Creating an Oracle User section. This section discusses the various grants required for the Oracle Database User.

#### **Assign the Grants**

#### Assign the following grants:

```
grant create SESSION to <oracle database user>;
grant create PROCEDURE to <oracle database user>;
grant create SEQUENCE to <oracle database user>;
grant create TABLE to cracle_database_user>;
grant create TRIGGER to <oracle database user>;
grant create VIEW to <oracle database user>;
grant create MATERIALIZED VIEW to <oracle database user>;
grant select on SYS.V $PARAMETER to <oracle database user>;
grant create SYNONYM to <oracle database user>;
grant select on sys.v_$parameter to <oracle_database_user>;
grant select on sys.dba free space to <oracle database user>;
grant select on sys.dba_tables to <oracle_database_user>;
grant select on sys.Dba tab columns to <oracle database user>;
grant create RULE to <oracle database user>;
grant create any trigger to <oracle database user>;
grant drop any trigger to <oracle database user>;
grant select on SYS.DBA RECYCLEBIN to <oracle database user>;
create or replace DIRECTORY fs_list_logs_dir AS '/file_store/fs_list/logs/';
grant read, write on DIRECTORY fs list logs dir TO schema name;
create or replace DIRECTORY fs list script dir AS '/file store/fs list/script/';
grant read, execute on DIRECTORY fs list script dir TO schema name;
create or replace DIRECTORY fs list control dir AS '/file store/fs list/
control/';
grant read on DIRECTORY fs list control dir TO schema name;
```

# 4.2.3 Create the MMG Studio Schema

You must create an Oracle User to create the MMG Studio Schema. For more details, see Creating an Oracle User section.

Assign the following grants:



```
GRANT CONNECT, CREATE TABLE, CREATE VIEW, CREATE SEQUENCE TO <mmgstudio schema name>;
```

A new user group created in MMG which requires permission for Studio operations, is to be added in the following files:

- mmgstudio/conf/application.yml
- mmgstudio/conf/ofsaa-permissions.init.yml



Make sure the groups are in upper case, as AAI groups are always in upper case.

## 4.2.4 Create MMG Graph Schema

Ensure that create an Oracle User to create the MMG Graph Schema. For more details, see Creating an Oracle User section.

#### **Assign Grants**

This section discusses the various grants required for the Graph Schemas.

Assign the following grants for the schema:

1. Pre-installation grants for Graph Schema:

```
GRANT CREATE SESSION TO <GRAPH_SCHEMA>;

GRANT CREATE TABLE TO <GRAPH_SCHEMA>;

GRANT CREATE VIEW TO <GRAPH_SCHEMA>;

GRANT CREATE ANY PROCEDURE TO <GRAPH_SCHEMA>;

GRANT CREATE SEQUENCE TO <GRAPH_SCHEMA>;

GRANT CREATE JOB TO <GRAPH_SCHEMA>;

GRANT CREATE MATERIALIZED VIEW TO <GRAPH_SCHEMA>;

GRANT EXECUTE ON DBMS_SCHEDULER to <GRAPH_SCHEMA>;

GRANT EXECUTE ON DBMS_COMPARISON TO <GRAPH_SCHEMA>;

GRANT EXECUTE ON DBMS_RLS TO <GRAPH_SCHEMA>;

GRANT EXECUTE ON SYS.DBMS_SESSION TO <GRAPH_SCHEMA>;

GRANT EXECUTE ON DBMS_RLS TO <GRAPH_SCHEMA>;

GRANT EXECUTE ON SYS.DBMS_SESSION TO <GRAPH_SCHEMA>;

GRANT EXECUTE ON SYS.DBMS_REDEFINITION TO <GRAPH_SCHEMA>;

GRANT SELECT ON SYS.V_$PARAMETER TO <GRAPH_SCHEMA>;

GRANT SELECT ON <DATA SOURCE SCHEMA>.<TABLE NAME> TO <GRAPH SCHEMA>;
```

#### **Example:**

Change the <DATA SOURCE SCHEMA> to the schema used in the Graph pipeline.



If a user has to execute the custom graph, the same permissions have to be provided for the input tables referred in Custom Graph Pipeline.

# 4.3 Create the Installation, Download, and Metadata Repository Directories

To install the application, create the following directories:

- OFS MMG Download Directory (Optional): This is the directory where the downloaded installer or patches can be copied. Create a download directory and copy the OFS MMG Application Pack Installer File (archive). Assign 755 permission to this directory.
- **Temporary Directory:** This is the default temporary directory where the installation files are stored for a short time to support faster installation. Configure adequate space on the /tmp directory. It is recommended to allocate more than 10 GB of space. Assign 755 permission to this directory and disable the NOEXEC option.

#### Note:

If the NOEXEC option is enabled, the extraction of files by the installer into the / tmp directory is prevented and the binaries will not execute in the directory, hence resulting in failure of the installation.

- **OFS MMG Installation Directory (Mandatory):** Create an installation directory where the product binaries are installed. Assign 755-user permission to the Installation Directory.
- OFS MMG Staging/Metadata Directory (Mandatory): This is a directory to hold the
  application metadata artifacts and additionally, act as the staging area for the flat files. This
  directory is also referred to as FTPSHARE. Create a Staging or Metadata Repository
  Directory to copy data files, save data extracts, and so on.
  You can configure this directory on a different mount or under a different user profile.

#### Note:

Ensure that the OFS MMG Staging Directory is not set to the same path as the OFS MMG Installation Directory and is not a sub-directory inside the OFS MMG Installation Directory.

# 4.4 Configure the OS File System Settings and Environment Settings in the .profile File

A .profile file is a start-up file of a UNIX User. Create the .profile file at the home directory of the logged-in user if it is not already available. The user must have 755 permission on the file to execute it. This file consists of various parameters for Environment Settings, OS, and File System Settings.



To set the parameters for the .profile file, login as a non-root user, and configure the environment settings.



#### **WARNING:**

Do not modify any other parameters other than the parameters mentioned in the following subsections.

# 4.4.1 Configure Operating System and File System Settings

To install the application, configure the operating system and file system settings refer the parameters and configuration actions.

Table 4-1 Configure operating system and file system settings

Parameter	Configuration Action
File Descriptor Settings	In the sysctl.conf file, to change the number of file descriptors, do the following as the root user:
	1. Edit the following line in the /etc/sysctl.conf file:
	<ul> <li>fs.file-max = <value> where <value> is greater than 15000</value></value></li> <li>Apply the change by running the following command: #/sbin/ sysctl -p</li> </ul>



The value specified here is the minimum value to be set for the installation process to go forward. For other modules, this value may depend on the available resources and the number of processes executed in parallel.



Table 4-1 (Cont.) Configure operating system and file system settings

Parameter	Configuration Action
Total Number of Process Settings	In the sysctl.conf file, set the value to greater than 4096.



The value specified here is the minimum value to be set for the installation process to go forward. For other modules, this value may depend on the available resources and the number of processes executed in parallel.

# 4.4.2 Configure the Environment Settings

Environment Settings refers to values related to the current environment, like the Operating System or user sessions. To configure the environment settings refer the following topics.

## 4.4.2.1 Java Settings

To configure the Java Settings, refer the following table:

Table 4-2 Java Settings

Description	Example Value
In the .profile file, set JAVA_BIN to include the JDK absolute path.	For example: JAVA 17

Table 4-3 Java Settings

Description	Example Value	
In the .profile file, set the Java tool options for all versionsJDK-17 and above updates.  Ensure that SYMBOLIC links to JAVA installation are not set in the PATH variable.	<pre>JAVA_TOOL_OPTIONS=" - Djdk.util.zip.disableZip64ExtraFieldVal idation=true"</pre>	
In the .profile file, set JAVA_BIN to include the JDK absolute path.	export JAVA_TOOL_OPTIONS  For example: JAVA_BIN =/usr/java/ jdk-17/bin	
	export JAVA_BIN	



#### 4.4.2.2 Oracle Database Server and Client Settings

To configure the Oracle Database Server and Client Settings, refer to the following table:

Table 4-4 Oracle Database Server and Client Settings

Description	Example Value
In the .profile file, set TNS_ADMIN pointing to the appropriate tnsnames.ora file.	TNS_ADMIN=\$HOME/tns
In the .profile file, set ORACLE_HOME pointing to the appropriate Oracle Client installation.	ORACLE_HOME=/scratch/oraofss/ app_client19c/product/ 19.0.0/client_1
In the .profile file, set PATH to include the appropriate \$ORACLE_HOME/bin path.	PATH=\$JAVA_HOME/bin:\$ORACLE_HOME/bin

#### 4.4.2.3 TNS entries in the tnsnames.ora file for Non-TCPS

You must configure the TNS entries in the tnsnames.ora file for Non-TCPS.

#### 4.4.2.3.1 Non-TCPS

To configure the TNS entries in the tnsnames.ora file for Non-TCPS, refer to the following table:

Table 4-5 TNS entries in the TNSNAMES.ORA file for Non-TCPS

Description	Example Value
Ensure that an entry (with SID or SERVICE NAME) is added in the tnsnames.ora file on the OFSAA server.	<pre> <sid_name> = DESCRIPTION = (ADDRESS_LIST</sid_name></pre>

```
<SID NAME> =

(DESCRIPTION =

(ADDRESS_LIST =

(ADDRESS = (PROTOCOL = TCP) (HOST = <HOST NAME>) (PORT = <PORT NUMBER>))
) (CONNECT_DATA =

(SERVICE_NAME = <SID NAME>)
)

<ATOMICSCHEMANAME> =
```



```
(DESCRIPTION =
(ADDRESS_LIST =
(ADDRESS = (PROTOCOL = TCP) (HOST = <HOST NAME>) (PORT = <PORT NUMBER>))
(CONNECT_DATA =
(SERVICE_NAME = <SID NAME>)
)
```

### 4.4.2.4 Time Zone Settings

In the .profile file, set the Time Zone Parameter to indicate the time zone of your region or location.

For more information, see Oracle Financial Service Stress Testing and Scenario Analytics User's Guide.

Table 4-6 Time Zone Settings

Description	Example Value
Time Zone	TZ=Asia/Calcutta

# 4.5 Prerequisite for Data Pipeline

The below are prerequisites for Data Pipeline. The steps need to be executed before triggering MMG Installer.

- 1. Log in as DB user(ex: fccmdb) in your DB server (For example: 1759).
- 2. Create one directory with preferred reference name (For example: datapipline) at the preferred location.
- Now execute below commands in putty session of DB server:
  - mkdir -p ##location of dir created in step 2##/file\_store/ fs\_list/logs # A directory by the external table to write the logs.
  - mkdir -p ##location of dir created in step 2##/file\_store/ fs\_list/script # A directory to hold a pre-processor script used to list the files in a directory. This needs Read-Execute permissions.
  - mkdir -p ##location of dir created in step 2##/file\_store/ fs\_list/control # A directory to hold files to control which directories can be listed. This needs Read permissions.
  - mkdir -p ##location of dir created in step 2##/file\_store/ fs list/fccm-data # A directory to store the csv files.
- 4. After that login to DB server(For example: 1759) as sysadmin( For example: sys) in sqldeveloper or any preferred application execute below:
  - CREATE OR REPLACE DIRECTORY fs\_list\_logs\_dir AS '##location of dir created in step 2##/file store/fs list/logs';

- GRANT READ, WRITE ON DIRECTORY fs\_list\_logs\_dir TO ##MMG Application Schema##;
- CREATE OR REPLACE DIRECTORY fs\_list\_script\_dir AS '##location of dir created in step 2##/file\_store/fs\_list/script';
- GRANT READ, EXECUTE ON DIRECTORY fs\_list\_script\_dir TO ## MMG Application Schema##;
- CREATE OR REPLACE DIRECTORY fs\_list\_control\_dir AS '##location of dir created in step 2##/file store/fs list/control';
- GRANT READ ON DIRECTORY fs\_list\_control\_dir TO ##MMG Application Schema##;
- CREATE OR REPLACE DIRECTORY external\_tables\_dir AS '##location of dir created in step 2##/file store/fs list/fccm-data';
- GRANT READ ON DIRECTORY external\_tables\_dir TO ## MMG Application Schema##;
- GRANT CREATE TABLE TO ##MMG Application Schema##;

Once the above steps are done, trigger the installation of Compliance Studio build.



- If the new schema is residing on any-other DB server other than the one on which above steps were performed. Please perform all the above steps on that respective server.
- Once configured the DB server, if new schema is created on it. Need to perform the step for the respective schema.

# 4.6 Setup Password Stores with Oracle Wallet

This section describes the steps to create a wallet and the aliases for the database user accounts. For more information on configuring authentication and password stores, see theOracle Database Security Guide.

As part of an Application Installation, Administrators must set up password stores for Database User Accounts using Oracle Wallet. These password stores must be installed on the Application Database side. The Installer handles much of this process. The Administrators must perform some additional steps.

# 4.6.1 Setup the Password Stores for Database User Accounts

After the database is installed and the default Database User Accounts are set up, Administrators must set up a password store using the Oracle Wallet. This involves assigning an alias for the username and associated password for each Database User Account. The alias is used later during the application installation. This password store must be created on the system where the Application Server and database client are installed.



Note:

In this section, <wallet\_location> is a placeholder text for illustration purposes. Before running the command, ensure that you have already created the <wallet\_location> directory where you want to create and store the wallet.

The wallet is created in the <wallet\_location> directory with the auto-login feature enabled. This feature enables the database client to access the wallet contents without using the password. For more information, see Oracle Database Security Guide.

To create a wallet, follow these steps:

- Login to the server as a Linux user.
- 2. Create a wallet in the <wallet\_location> using the following command:
   mkstore -wrl <wallet location> -create

Note:

The mkstore utility is included in the Oracle Database Client Installation.

After you run the command, a prompt appears. Enter a password for the Oracle Wallet in the prompt.

A prompt appears to re-enter the password. Re-enter the password.

#### Figure 4-1 Wallet Creation

```
$ mkstore -wrl /scratch/ofsasftp/pgx server/wallet -create
Oracle Secret Store Tool Release 19.0.0.0.0 - Production
Version 19.3.0.0.0
Copyright (c) 2004, 2019, Oracle and/or its affiliates. All rights reserved.

Enter password:
Enter password again:
$ mkstore -wrl /scratch/ofsasftp/pgx server/wallet -createCredential MMGConfigSchema_Alias MMG_Config_Schema
Oracle Secret Store Tool Release 19.0.0.0.0 - Production
Version 19.3.0.0.0
Copyright (c) 2004, 2019, Oracle and/or its affiliates. All rights reserved.

Your secret/Password is missing in the command line
Enter your secret/Password:
Re-enter your secret/Password:
Enter your secret/Password:
Enter your secret/Password:
Enter wallet password:
$ mkstore -wrl /scratch/ofsasftp/pgx server/wallet -createCredential MMGStudio_Schema_Alias MMG_Studio_Schema
Oracle Secret Store Tool Release 19.0.0.0.0 - Production
Version 19.3.0.0.0
Copyright (c) 2004, 2019, Oracle and/or its affiliates. All rights reserved.

Your secret/Password is missing in the command line
Enter your secret/Password:
Re-enter your secret/Password:
Re-ent
```

4. Create the database connection credentials for the MMG Schema using the following command:

mkstore -wrl <wallet\_location> -createCredential <alias-name> <mmgschema-name>

Here, MMG Schema is the same as explained in Create the MMG Schema section.

After you run the command, a prompt appears. Enter the password associated with the Database User Account in the prompt. You are prompted to re-enter the password. You are prompted for the wallet password used in Step 1.



In this manner, create a wallet and associated database connection credentials for all the Database User Accounts including Graph and Studio Schema.

After the wallet is created, go to the <wallet\_location> directory and click Refresh to view the created wallet folder.

The wallet folder contains two files: ewallet.p12 and cwallet.sso.

After you run the command, a prompt appears. Enter the password associated with the Database User Account in the prompt. You are prompted to re-enter the password. You are prompted for the wallet password used in Step 1.

#### Note:

In this manner, create a wallet and associated database connection credentials for all the Database User Accounts including Graph and Studio Schema.

After the wallet is created, go to the <wallet\_location> directory and click Refresh to view the created wallet folder.

#### Note:

In addition to creating wallet aliases for MMG Studio and Graph, you must also create wallet aliases for the production schemas; specifically, the config and atomic schemas. Ensure these aliases are added to the tnsnames.ora file.

The wallet folder contains two files: ewallet.p12 and cwallet.sso.

5. In the <wallet\_location> directory, configure the the thinnames.ora file to include the entry for each alias name to be set up. Alias name can be renamed as wallet db alias name.

#### Note:

- You can either update the existing thrsnames.ora file with the above details or create new thrsnames.ora file and add the required entries.
- <alias-name> is a user-defined value.
- 6. Create a sqlnet.ora file in the wallet directory using the following content: WALLET\_LOCATION = (SOURCE = (METHOD = FILE) (METHOD\_DATA = (DIRECTORY = <Wallet\_Location>))) SQLNET.WALLET\_OVERRIDE=TRUE SSL CLIENT AUTHENTICATION=FALSE

Here, <Wallet Location> should be in below format:

```
WALLET_LOCATION = (SOURCE = (METHOD = FILE) (METHOD_DATA =
(DIRECTORY = <WALLET PATH>) ) )
```

# 4.6.2 Verify the Connectivity of the Wallet

To verify the connectivity of the wallet, follow these steps:

1. Test the connectivity using the following command:



The ORACLE\_HOME used with the wallet must be the same version or higher than the wallet created.

```
$ export WALLET_LOCATION=<wallet_location>
$ export TNS_ADMIN=<tnsnames.ora_location>. If you have created a new
tnsnames.ora file, provide the location of the new file.
$ sqlplus /0<alias name>
```

#### The output is similar to:

```
SQL*Plus: Release 11
Connected to:
Oracle Database 12c
```

#### To verify if you are connected to the correct user:

```
SQL> show user
The output is similar to:
USER is "<database-user-name>"
```

5

# Installation

This section provides detailed steps to install the application.

# 5.1 Prerequisites

The list of prerequisites are as follows:

Port Details

MMG Studio uses the following ports by default, so make sure these are free:

Graph Service: 7059

Server: 7008

Markdown-Interpreter: 7009, 7029 Python-Interpreter: 7012, 7032, 6012

Shell-Interpreter: 7013, 7033

Plainr-Interpreter 7019, 7039, 6311 (Rserve port- configurable in plainr.Json)

PGX Server: 7007

PGX-Interpreter: 7022, 7042 JDBC-Interpreter: 7011, 7031 Coherence Cluster: 7574



These are default ports provided in the installation kit. You can modify them in the configuration files if required to avoid conflicts with existing services.

#### **Enhancements for Preinstall Check**

Warning messages for below validations:

- To validate whether the given hostname is valid or not.
- To validate whether given hostname and hostname in keystore are matching.
- Error messages and failing the preinstall check for below validations.
- To check sso\_token is present or not.
- To check for public and private key are present in the mmghome/conf location.

# 5.2 Download the OFS MMG Installer Kit

To download the software as a .zip folder, download the mandatory minor release patch **38167815** from My Oracle Support (MOS).

Download the installer archive and copy (in Binary Mode) to the download directory that exists in the OFS MMG Installation Setup.

#### 5.3 Extract the Software

You must be logged in to the UNIX Operating System as a Non-Root User to perform the following steps. To extract the software, follow these steps:

1. Download the unzip (OS-specific) unzip\_<os>.zip and copy it in Binary Mode to the directory that is included in your PATH variable.

If you already have an unzip utility to extract the contents of the downloaded archive, skip this step. Uncompress the unzip installer file with the command:

uncompress unzip <os>.Z

#### Note:

If an error message "uncompress: not found [No such file or directory]" is displayed, contact your UNIX Administrator.

2. Assign execute (751) to the file with the following command:

```
chmod 751 unzip <OS>
```

For example: chmod 751 unzip sparc

3. Extract the contents of the OFS MMG Application Pack Release 8.1.3.1.0 installer archive file in the download directory with the following command:

```
unzip OFS MMG 8.1.3.1.0 <OS>.zip
```

After unzipping the OFS\_MMG\_8.1.3.1.0 folder, following zip folders are displayed under OFS MMG folder.

- mmg-installer.zip
- mmg-metadata-manager.zip
- mmg-pgx.zip
- OFSMMG\_8.1.3.1.0\_Readme.html

Unzip mmg-installer.zip and the following components are available under / OFS\_MMG/mmg-installer.zip:

- mmg-ui
- mmg-studio
- mmg-service
- mmg-schema-creator
- mmg-pipeline
- mmg-load-to-graph
- lib
- bin
- conf
- mmg-gateway



4. Navigate to the download directory and assign execute permission to the installer directory with the following command:

```
chmod -R 750 OFS_MMG
```

# 5.4 Configure the config.sh file

To configure the config.sh file for installing MMG, follow these steps:

- Login to the server as a non-root user.
- 2. Navigate to the <installation directory>/OFS MMG/bin directory.
- 3. Configure the applicable config.sh attributes as shown here:

Sample config.sh files:

```
#!/bin/sh ##
export APPLICATION NAME=##APPLICATION NAME##
export WALLET LOCATION=##WALLET LOCATION##
export TNS ADMIN PATH=##TNS ADMIN PATH##
export WALLET ALIAS=##WALLET ALIAS## export LOG HOME=##LOG HOME##
export FTPSHARE=##FTPSHARE##
export LOG_TIMEZONE=##LOG_TIMEZONE##
##By default, Data Studio is assumed to run on the same server. If it is
running on a different host, uncomment the line below and provide the
appropriate URL. #export DATASTUDIO URL=##DATASTUDIO URL##
export BE HOSTNAME=##
BE HOSTNAME##
export BE PORT=##BE PORT##
export UI PORT=##
UI_PORT## export SCHEMA_PORT=##SCHEMA_PORT##
export CONTEXT PATH=##CONTEXT PATH##
export STUDIO AUTH TYPE=##STUDIO AUTH TYPE##
export
RESTRICT_UNMAPPED_DATASTORES_ACCESS=##RESTRICT_UNMAPPED_DATASTORES_ACCESS##
export SSL ENABLED=##SSL ENABLED##
export SSL KEYSTORE=##SSL KEYSTORE##
export SSL KS SECRET=##SSL KS SECRET##
export SSL_KS_TYPE=##SSL_KS_TYPE##
export SSL KS ALIAS=##SSL KS ALIAS##
export SESSION TOKEN CREDENTIALS=##SESSION TOKEN CREDENTIALS##
export FCC API USER=##FCC API USER##
export MMG DATASOURCE MAX POOL SIZE=10
export MMG_DATASOURCE_IDLE_TIMEOUT=30000
export MMG DATASOURCE CONN TIMEOUT=80000
```

```
export EXT DATASOURCE MAX POOL SIZE=10
export EXT DATASOURCE IDLE TIMEOUT=30000
export EXT DATASOURCE CONN TIMEOUT=80000
export MMG HTTP MAX CONN=20
export MMG_HTTP MAX CONN PER ROUTE=2
export MMG HTTP CONNECT TIMEOUT=30000
export MMG_HTTP_READ_TIMEOUT=120000
export APPLICATION ID=##APPLICATION ID##
## Properties for MMG-ui
export APPLICATION FAVICON PATH=##APPLICATION FAVICON PATH##
export UI AUTH TYPE=##AUTH TYPE##
export AAI AUTH URL=##AAI AUTH URL##
export SAML IDP URL=##SAML IDP URL##
export SAML SP ENTITY=##SAML SP ENTITY##
export SAML_SRV_URL=##SAML_SRV_URL##
export SAML LOGOUT URL=##SAML LOGOUT URL##
export SAML SIGN AUTHN REQ=##SAML SIGN AUTHN REQ##
export SAML PRIVATE KEY PATH=##SAML PRIVATE KEY PATH##
export SAML_SP_X509_CERT_PATH=##SAML_SP_X509_CERT_PATH##
export SAML SIGN ALGORITHM=##SAML SIGN ALGORITHM##
export AUTH SAML REQUEST TYPE=##AUTH SAML REQUEST TYPE##
export AUTH SAML INCLUDE SP CERT=##AUTH SAML INCLUDE SP CERT##
export LDAP URL=##LDAP URL##
export LDAP SEARCH BASE=##LDAP SEARCH BASE##
export LDAP USER FILTER=##LDAP USER FILTER##
export LDAP USER SEARCH FILTER=##LDAP USER SEARCH FILTER##
export LDAP_GROUP_SEARCH FILTER=##LDAP GROUP SEARCH FILTER##
export LDAP GROUP SEARCH BASE=##LDAP GROUP SEARCH BASE##
export LDAP GROUP MEMBER=##LDAP GROUP MEMBER##
```

#### Note:

Accepted Values for SAML\_SIGN\_ALGORITHM Property:

- http://www.w3.org/2001/04/xmldsig-more#rsa-sha512
- http://www.w3.org/2001/04/xmldsig-more#rsa-sha384
- http://www.w3.org/2001/04/xmldsig-more#rsa-sha256
- http://www.w3.org/2000/09/xmldsig#rsa-sha1

## Properties for enabling AAI Authorization. Applicable for SAML/LDAP Profiles

```
## This is disabled by default. Set AAI AUTHZ ENABLED to true to enable.
## AAI AUTH URL must be set.
export AAI_AUTHZ_ENABLED=##AAI_AUTHZ_ENABLED##
export AAI CLIENT ID=##AAI CLIENT ID##
export AAI CLIENT SECRET=##AAI CLIENT SECRET##
export SERVER_COOKIE DOMAIN=##SERVER COOKIE DOMAIN##
export SERVER COOKIE NAME=##SERVER COOKIE NAME##
export SERVER COOKIE TIMEOUT=##SERVER COOKIE TIMEOUT##
export SERVER COOKIE IS SECURE=##SERVER COOKIE IS SECURE##
##Properties for MMG-Service
export BE AUTH TYPE=public
export MMG PYTHON INTERPRETER=##MMG PYTHON INTERPRETER##
##Properties for MMG-Studio
export DATASTUDIO SCHEMA WALLET ALIAS=##DATASTUDIO SCHEMA WALLET ALIAS##
export LOGIN SHOW=##LOGIN SHOW##
export SESSION MODE=##SESSION MODE##
export STUDIO REALM=##STUDIO REALM##
export OFSAA URL=##OFSAA URL##
export API_USERS=##API USERS##
export VALID ROLES=##VALID ROLES##
export STUDIO_LOG LEVEL=##STUDIO LOG LEVEL##
export PYTHON HOME=##PYTHON HOME##
#Following are spark specific configurations, Leave as it is if not applicable
export MMG SPARK ENABLED=##MMG SPARK ENABLED## #will be false by default
export SPARK HOME=##SPARK HOME## #required if MMG SPARK ENABLED is true
export HADOOP HOME=##HADOOP HOME## #only needed if running spark with hadoop
cluster
export SPARK MASTER=##SPARK MASTER## #required if MMG SPARK ENABLED is true
export SPARK DEPLOY MODE=##SPARK DEPLOY MODE## #required if MMG SPARK ENABLED
is true
export DATASTUDIO SPARK INTERPRETER PORT=##DATASTUDIO SPARK INTERPRETER PORT##
#required if MMG SPARK ENABLED is true
export R ENABLED=##R ENABLED## export R PYTHON HOME=##R PYTHON HOME##
# Following are fcc services specific configurations, Leave as it is if not
applicable
export TEMPLATE_CONFIG PATH=##TEMPLATE CONFIG PATH##
export TEMPLATE DEFAULT LINK=##TEMPLATE DEFAULT LINK##
export AUTH SERVICE URL=##AUTH SERVICE URL##
export META SERVICE URL=##META SERVICE URL##
export ER_SERVICE URL=##ER SERVICE URL##
export BATCH SERVICE URL=##BATCH SERVICE URL##
```

```
export SAML ISSUER=##SAML ISSUER##
export SAML DESTINATION=##SAML DESTINATION##
export SAML ASSERTION=##SAML ASSERTION##
export SAML ROLE ATTRIBUTE=##SAML ROLE ATTRIBUTE##
export SAML STUDIO LOGOUT URL=##SAML STUDIO LOGOUT URL##
export SAML COOKIE DOMAIN=##SAML COOKIE DOMAIN##
# Following are pipeline services specific configurations, Leave as it is if
not applicable
export DATAPIPELINE SERVICE PORT1=##DATAPIPELINE SERVICE PORT1##
export DATAPIPELINE_SERVICE PORT2=##DATAPIPELINE SERVICE PORT2##
DATAPIPELINE METADATA ARCHIVE PATH=##DATAPIPELINE METADATA ARCHIVE PATH##
DATAPIPELINE_METADATA_IMPORT_SERVICE PORT=##DATAPIPELINE METADATA IMPORT SERVI
CE PORT##
export DATAPIPELINE ERXMLPATH=##DATAPIPELINE ERXMLPATH##
export DATAPIPELINE GATEWAY SERVICE PORT=##DATAPIPELINE GATEWAY SERVICE PORT##
export PIPELINE UI SERVICE PORT=##PIPELINE UI SERVICE PORT##
export DATA PIPELINE UI SERVICE PORT=##DATA PIPELINE UI SERVICE PORT##
export DATAPIPELINE HAZELCAST PORT=##DATAPIPELINE HAZELCAST PORT##
#URLS for pipeline, ER and matching service. Leave as it is if not applicable.
Will impact the pipeline that could be added to a graph
export MATCHRULE BASE URL=##MATCHRULE BASE URL##
export LOADGRAPH BASE URL=##LOADGRAPH BASE URL##
export MATCHSRVC UI URL=##MATCHSRVC UI URL##
#URLS for index service. Leave as it is if not applicable. Will impact the
pipeline that could be added to a graph
export GRAPH_INDEX_BASE_URL=##GRAPH_INDEX_BASE_URL##
export LOADINDEX UI URL=##LOADINDEX UI URL##
export MATCHING MECHANISM=##MATCHING MECHANISM##
export CANDIDATE SELECTION SERVICE URL=##CANDIDATE SELECTION SERVICE URL##
export LOAD TO OS URL=##LOAD TO OS URL## #Changes for auth services + mmg keys
export AAI COOKIE DOMAIN=##AAI COOKIE DOMAIN##
export MMG KEYS LOC=##MMG KEYS LOC##
#Properties to package Load to Graph (L2G) service inside MMG
## Start of L2G Properties
## export GRAPH INSTALLATION PATH=##GRAPH INSTALLATION PATH##
export GRAPH KEYSTORE PASSWORD=##GRAPH KEYSTORE PASSWORD##
export GRAPH SERVICE PORT=##GRAPH SERVICE PORT##
## Graph Schema Configurations
export MMG DB SERVER NAME=##MMG DB SERVER NAME##
export MMG DB PORT=##MMG DB PORT##
```

```
export MMG DB SERVICE NAME=##MMG DB SERVICE NAME##
export PGX SERVER URLS=##PGX SERVER URLS##
#### PGX data memory limits configurations ##
Overall Configuration
export MAX TOTAL SHARED DATA MEMORY SIZE=##MAX TOTAL SHARED DATA MEMORY SIZE##
MAX TOTAL PRIVATE DATA MEMORY SIZE=##MAX TOTAL PRIVATE DATA MEMORY SIZE##
export MAX PER SESSION DATA MEMORY SIZE=##MAX PER SESSION DATA MEMORY SIZE##
## Role wise data memory limits
export MAX DATA MEMORY SIZE DSUSRGRP=##MAX DATA MEMORY SIZE DSUSRGRP##
export MAX DATA MEMORY SIZE DSBATCH=##MAX DATA MEMORY SIZE DSBATCH##
export MAX DATA MEMORY SIZE DSINTER=##MAX DATA MEMORY SIZE DSINTER##
export MAX DATA MEMORY SIZE DSAPPROVER=##MAX DATA MEMORY SIZE DSAPPROVER##
export MAX DATA MEMORY SIZE DSUSER=##MAX DATA MEMORY SIZE DSUSER##
export MAX DATA MEMORY SIZE IHUSRGRP=##MAX DATA MEMORY SIZE IHUSRGRP##
export GRAPH SERVICE CACHE SERVER PORT=##GRAPH SERVICE CACHE SERVER PORT##
#end of Properties configurations for L2G
##Schema details for graph service. This is configured as a temporary/target
space for DP to create target tables which will act as input to L2G
export GRAPH SCHEMA WALLET ALIAS=##GRAPH SCHEMA WALLET ALIAS##
export GRAPH SCHEMA DB SCHEMA NAME=##GRAPH SCHEMA DB SCHEMA NAME##
#Additional MMG Features
export
MMG MODEL PIPELINE SANDBOX DEFAULT VIEW=##MMG MODEL PIPELINE SANDBOX DEFAULT V
## The following properties are optional and enabled by default. If needed,
you can uncomment them and set them to false.
#export MMG_HTTP2_ENABLED=##MMG_HTTP2_ENABLED##
#export MMG_SERVER_ACCESS_LOG ENABLED=##MMG SERVER ACCESS LOG ENABLED##
## The following properties are optional and disabled by default. If needed,
you can uncomment them and set them to true.
#export OJET_CDN_ENABLED=##OJET_CDN_ENABLED##
##The following Properties are related to EST export
EST ENABLED=##EST ENABLED##
export EST UI URL=##EST UI URL##
export EST SERVICE URL=##EST SERVICE URL##
export DATACATALOG SERVICE URL=##DATACATALOG SERVICE URL##
##DEFAULT CONNECTION POOLING CONFIGURATION FOR EXTERNAL SCHEMA (Time in
ISO-8601 format)
export GRAPH EXT SCHEMA ENABLE CP=##GRAPH EXT SCHEMA ENABLE CP##
export GRAPH EXT SCHEMA CP MAX IDLE=##GRAPH EXT SCHEMA CP MAX IDLE##
export GRAPH EXT SCHEMA CP MIN IDLE=##GRAPH EXT SCHEMA CP MIN IDLE##
export GRAPH EXT SCHEMA CP INITIAL SIZE=##GRAPH EXT SCHEMA CP INITIAL SIZE##
```

```
export GRAPH EXT SCHEMA CP MAX TOTAL=##GRAPH EXT SCHEMA CP MAX TOTAL##
export.
GRAPH EXT SCHEMA CP MAX WAIT MILLIS=##GRAPH EXT SCHEMA CP MAX WAIT MILLIS##
GRAPH EXT SCHEMA CP MIN EVICTABLE IDLE TIME=##GRAPH EXT SCHEMA CP MIN EVICTABL
E IDLE TIME##
export
GRAPH EXT SCHEMA CP SOFT MIN EVICTABLE IDLE TIME=##GRAPH EXT SCHEMA CP SOFT MI
N EVICTABLE IDLE TIME##
export GRAPH DOCUMENT DOWNLOAD PATH=##GRAPH DOCUMENT DOWNLOAD PATH##
##Proxy Configurations
export GRAPH NO PROXY=##GRAPH NO PROXY##
##Data Studio Ports
## Following are the default ports 7008, 7009, 7012,-1. If needed, you can
change the port numbers other than the default values.
export DATASTUDIO SERVER PORT=##DATASTUDIO SERVER PORT##
export
DATASTUDIO MARKDOWN INTERPRETER PORT=##DATASTUDIO MARKDOWN INTERPRETER PORT##
DATASTUDIO PYTHON INTERPRETER PORT=##DATASTUDIO PYTHON INTERPRETER PORT##
export DATASTUDIO R INTERPRETER PORT=##DATASTUDIO R INTERPRETER PORT##
export DATASTUDIO JDBC INTERPRETER PORT=##DATASTUDIO JDBC INTERPRETER PORT##
DATASTUDIO PYTHON INTERPRETER REST SERVER PORT=##DATASTUDIO PYTHON INTERPRETER
REST SERVER PORT##
DATASTUDIO PGX PYTHON INTERPRETER REST SERVER PORT=##DATASTUDIO PGX PYTHON INT
ERPRETER REST SERVER PORT##
export
DATASTUDIO THRIFT EVENT HANDLER PORT=##DATASTUDIO THRIFT EVENT HANDLER PORT##
export DATASTUDIO PGX INTERPRETER PORT=##DATASTUDIO PGX INTERPRETER PORT##
export MMG COHERENCE CLUSTER PORT=##MMG COHERENCE CLUSTER PORT##
##MMG Gateway Configuration
export MMG GATEWAY ENABLED=##MMG GATEWAY ENABLED##
export MMG GATEWAY PORT=##MMG GATEWAY PORT##
## If Gateway is enabled, the following property can be set to control the
pages where MMG can be embedded:
# Set to 'self' to allow embedding only from the same origin (recommended for
most setups).
# Set to 'all' or '*' to allow embedding from any origin. (less secure)
# Set to a comma-separated list of origins to allow embedding from those
specified origins and from the same origin.
# By default, this is set to 'self'. export
MMG CSP FRAME ANCESTORS=##MMG CSP FRAME ANCESTORS##
# If the Gateway is enabled, this property can be set to control the pages
```



where Data Studio can be embedded:

- # Set to '\*' to allow embedding from any origin (less secure).
- # Set to a comma-separated list of origins to allow embedding from those specified origins and from the same origin.
- # By default, this is set to MMG Gateway URL.
- # If a load balancer or an external gateway is configured for MMG Gateway, the URL must be included in the list of origins.
- export DATASTUDIO CSP FRAME ANCESTORS=##DATASTUDIO CSP FRAME ANCESTORS##

#### ##MMG Model Serving Configuration

export.

MMG\_MODEL\_ENDPOINT\_RESTART\_INTERVAL=##MMG MODEL ENDPOINT RESTART INTERVAL##

# ##Enhanced Configurability for Data Studio Performance and Session Parameters ##Interpreter Idle Session Timeout and Cleanup

export

DATASTUDIO\_INTERPRETER\_IDLE\_SESSION\_TIMEOUT=##DATASTUDIO\_INTERPRETER\_IDLE\_SESSION\_TIMEOUT##

export

DATASTUDIO\_INTERPRETER\_CLEANUP\_ENABLED=##DATASTUDIO\_INTERPRETER\_CLEANUP\_ENABLED##

export

DATASTUDIO INTERPRETER CLEANUP CRON="##DATASTUDIO INTERPRETER CLEANUP CRON##"

#### # Studio Server Thread Pool Size

export

DATASTUDIO\_SERVER\_ASYNC\_THREADPOOL\_SIZE=##DATASTUDIO\_SERVER\_ASYNC\_THREADPOOL\_SIZE##

export

DATASTUDIO\_SERVER\_SCHED\_THREADPOOL\_SIZE=##DATASTUDIO\_SERVER\_SCHED\_THREADPOOL\_SIZE##

#### # Hikari Pool Configurations

export DATASTUDIO HIKARI MAXPOOLSIZE=##DATASTUDIO HIKARI MAXPOOLSIZE##

export DATASTUDIO\_HIKARI\_CONN\_TIMEOUT\_MS=##DATASTUDIO\_HIKARI\_CONN\_TIMEOUT\_MS##

export DATASTUDIO HIKARI MINIMUM IDLE=##DATASTUDIO HIKARI MINIMUM IDLE##

export DATASTUDIO HIKARI MAX LIFE TIME=##DATASTUDIO HIKARI MAX LIFE TIME##

#### # Tomcat Threads

export

DATASTUDIO SERVER TOMCAT THREADS MAX=##DATASTUDIO SERVER TOMCAT THREADS MAX##

#### # Zeppelin Scheduler Threadpool Size

export

DATASTUDIO\_ZPLN\_SCHED\_THREADPOOL\_SIZE=##DATASTUDIO\_ZPLN\_SCHED\_THREADPOOL\_SIZE###



#### Note:

Gateway is enabled by default and gateway port is mandatory to access gateway enabled UI.

#### GIT Repository Access Functionality

```
export GIT_ENV_ID=##GIT_ENV_ID##
export GIT_USERNAME=##GIT_USERNAME##
export GIT_PAT_SECRET=##GIT_PAT_SECRET##
export GIT_PROXY_URL=##GIT_PROXY_URL##
export GIT_PROXY_PORT=##GIT_PROXY_PORT##
```

#### Note:

Only tokens (classic) is supported now. Fine grained is not yet supported.

A new group GITADMIN is created which is mapped to GIT\_ADV role which is mapped to below functions. Kindly map the above group to the user to access the required GIT functionality:

- GITVIEW
- GITPUSH
- GITPULL

#ENDOFFILE#

Table 5-1 config.sh file

Parameter	Description	Is Mandatory	Comments
##APPLICATION_NAM E##	Title of the application; if not replaced, default is: Model Management and Governance.	YES	It defaults to "Model Management and Governance."
			<b>Note:</b> Provide double quotes for the application name if it is long or contains spaces.
##WALLET_LOCATION ##	The wallet is the folder containing the sqlnet.ora, wallet.sso, and .p12 files.	YES	/scratch/users/wallet
##TNS_ADMIN_PATH# #	The folder that contains the tnsnames.ora file.	YES	/scratch/users/tns
##WALLET_ALIAS##	The wallet alias name configured for the MMG application config schema.	YES	MMG CONFIG



Table 5-1 (Cont.) config.sh file

Parameter	Description	Is Mandatory	Comments
##LOG_HOME##	A writable folder designated for storing application and MMG Studio logs.	YES	/scratch/users/logs <b>Note</b> : Ensure that log folder is created before installation.
##FTPSHARE##	This can be any writable folder	YES	/scratch/users/ftpshare
	accessible to the process owner.		Ensure that ftpshare folder is created before installation.
			This should be same as the metadata directory mentioned above.
##LOG_TIMEZONE##	Specifies the timezone used for displaying log timestamps	YES	GMT+05:30, GMT-04:00, Asia/ Kolkata
##DATASTUDIO_URL# #	URL for MMG Studio.	YES	By default, Data Studio is assumed to run on the same server. If it is running on a different host, uncomment the line below and provide the appropriate URL. https:// <hostname <="" td=""></hostname>
			<b>NOTE:</b> The default port for MMG Studio is 7008 and should not be modified.
##BE_HOSTNAME##	Hostname on which the backend service (mmg-service) runs.	YES	HostIP or FQDN
	Use the same hostname wherever applicable.		
##BE_PORT##	Port on which the backend service (mmg-service) needs to run.	YES	7002
##UI_PORT##	Port on which UI service (mmg-ui) needs to run.	YES	7001
##SCHEMA_PORT##	Port on which Schema Creator service needs to run.	YES	7003
##CONTEXT_PATH##	Context path of the application.	YES	MMG
##STUDIO_AUTH_TYP E##	<ul> <li>FCC_SSO – for SAMLRealm based authentication in FCC Studio</li> <li>MMG_AAI- AAI</li> </ul>	YES	Can be either MMG_AAI or FCC_SSO
	based authentication for MMG Studio		

Table 5-1 (Cont.) config.sh file

Parameter	Description	Is Mandatory	Comments
##SSO_TOKEN##	SSO Token value for Studio authentication. Applicable only when STUDIO_AUTH_TYPE is FCC_SSO and MMG_AAI. For FCC_SSO, refer to the Oracle Financial Services Compliance Studio Installation	YES	Note: Token generation is now automated and stored into a separate file in "install-helper/tmp/ssotoken.log".
	Guide.	\ <del>-</del>	
##SSL_ENABLED##	This enables HTTPS.	YES	Example: true
##SSL_KEYSTORE##	Absolute path for the keystore file.  Note: Run the following command to create a keystore: keytool -genkey -v - alias demoalias -keyalg RSA -keysize 2048 - keystore server.keystore -validity 3650 -keypass secret - storepass secret - storetype PKCS12	YES	/conf/server.keystore. Include the file name in the path.  NOTE: If ##SSL_ENABLED## is set to false, you must configure keystore for mmg-studio, as it is SSL-enabled by default. MMG application and MMG Studio can share the same SSL configuration if set up
##001 V0 0F0DFT##	Voyatore equit	YES	on the same server.
##SSL_KS_SECRET##	The value passed in the aforementioned command for -keypass	1123	Example: secret
##SSL_KS_TYPE##	Keystore type The value passed in the aforementioned command for -storetype Can be either JKS or PKCS12	YES	Example: PKCS12
##SSL_KS_ALIAS##	Keystore alias The value passed in the aforementioned command for -alias	YES	Example: demoalias
##SESSION_TOKEN_ CREDENTIALS##	The password used to generate the Authorization header token to communicate with mmg-services.	YES	<b>NOTE:</b> If not applicable, enter NA
##FCC_API_USER##	API user for FCC Studio.	YES	<b>NOTE</b> : If not applicable, enter NA
##MMG_DATASOURC E_MAX_POOL_SIZE##	Maximum connection pool size allowed for Config Datasource.	YES	It defaults to 10. You can edit it if required.

Table 5-1 (Cont.) config.sh file

Parameter	Description	Is Mandatory	Comments
##MMG_DATASOURC E_IDLE_TIMEOUT##	Idle timeout for config Datasource.	YES	It defaults to 30000. You can edit it if required.
##MMG_DATASOURC E_CONN_TIMEOUT##	Connection timeout for Config Datasource.	YES	It defaults to 80000. You can edit it if required.
##EXT_DATASOURCE _MAX_POOL_SIZE##	Maximum connection pool size allowed for meta/data schemas.	YES	It defaults to 10. You can edit it if required.
##EXT_DATASOURCE _IDLE_TIMEOUT##	Idle timeout for meta/ data schemas.	YES	It defaults to 30000. You can edit it if required.
##EXT_DATASOURCE _CONN_TIMEOUT##	Connection timeout for meta/data schemas.	YES	It defaults to 80000. You can edit it if required.
##MMG_HTTP_MAX_ CONN##	The maximum number of connections allowed across all routes.	YES	It defaults to 20.
## MMG_HTTP_MAX_CO NN_PER_ROUTE##	The maximum number of HTTP connections allowed for a route.	YES	It defaults to 2.
##MMG_HTTP_CONN ECT_TIMEOUT##	The connection timeout for HTTP connection. A timeout value of 0 specifies an infinite timeout.	YES	It defaults to 30000.
##MMG_HTTP_READ_ TIMEOUT##	The socket read timeout for HTTP connection. A timeout value of 0 specifies an infinite timeout.	YES	It defaults to 120000.
##APPLICATION_ID##	The id will be stored as app_id and must be the same as mentioned in the APP_ID column of MMG_PATCHES table. Currently the UI displays the MMG Version <version application="" number="" of=""> and last applied MMG version.</version>	YES	The APPLICATION_ID should be without spaces.
##APPLICATION_FAVI CON_PATH##	Icon for the application. If not specified, it will default to the icon at the following location: css/images/favicon.ico	NO	css/images/ favicon.ico



Table 5-1 (Cont.) config.sh file

Parameter	Description	Is Mandatory	Comments
##UI_AUTH_TYPE##	aai – if using an existing AAI instance as the identity provider. saml – for saml based authentication	YES	Can be one of the following: aai, or saml or Idap.
	Idap – for Idap based authentication		
	<b>NOTE:</b> This is case sensitive.		
##AAI_AUTH_URL##	Base URL of the AAI instance.	YES	http(s):// whfxxxxx.in.oracle.com:
	Will be used for ##UI_AUTH_TYPE## = aai		7110/mmg
	<b>Note:</b> If the target AAI is https, then it is necessary to import the AAI host certificate into the MMG server Java keystore.		
AUTH_SAML_REQUE ST_TYPE	This can be set to REDIRECT (default) / POST.	NA	NA
AUTH_SAML_INCLUD E_SP_CERT	This can be set to True/False (default).	NA	NA
##SAML_IDP_URL##	This is the endpoint on the IDP side where SAML requests are posted. The Service Provider (SP) needs to obtain this information from the Identity Provider (IDP).	YES	http(s)://idcs- xxxx.com/fed/v1/idp/sso This is used only if ##UI_AUTH_TYPE## is SAML.
##SAML_SP_ENTITY# #	name for SAML entity. It typically takes the URL	YES	http(s):// <ui_host>:<ui_por T&gt;/mmg</ui_por </ui_host>
	of an identity provider or a service provider as a value.		This is used only if ##UI_AUTH_TYPE## is SAML.
##SAML_SRV_URL##	UI Landing Page URL.	YES	http(s):// <ui_host>:<ui_por T&gt;/mmg/home</ui_por </ui_host>
			This is used only if ##UI_AUTH_TYPE## is SAML.
##SAML_LOGOUT_UR L##	Initiated SAML Single Logout URL.	YES	http(s)://idcs- xxxx.com/sso/v1/user/ logout
			This is used only if ##UI_AUTH_TYPE## is SAML.



Table 5-1 (Cont.) config.sh file

Parameter	Description	Is Mandatory	Comments
##LDAP_URL##	LDAP URL Will be used for ##UI_AUTH_TYPE## = LDAP	YES	ldap://whf00xyz:3060/
##LDAP_SEARCH_BA SE##	LDAP Search Base Will be used for ##UI_AUTH_TYPE## = LDAP	YES	"cn=Users,dc=oracle,dc =com"
##LDAP_USER_FILTE R##	LDAP User Filter Will be used for ##UI_AUTH_TYPE## = LDAP	YES	"cn={0}"
#LDAP_USER_SEARC H_FILTER##	LDAP User Search Filter Will be used for ##UI_AUTH_TYPE## = LDAP	YES	NA
##LDAP_GROUP_SEA RCH_FILTER##	LDAP Group Search Filter Will be used for ##UI_AUTH_TYPE## = LDAP	YES	NA
##LDAP_GROUP_SEA RCH_BASE##	LDAP Group Search Base Will be used for ##UI_AUTH_TYPE## = LDAP	YES	NA
##LDAP_GROUP_ME MBER#	LDAP Group Member Will be used for ##UI_AUTH_TYPE## = LDAP	YES	NA
##SERVER_COOKIE_ DOMAIN##	The domain name.	YES	This should be the domain name of the host server.  Example: .in.xyz.com  Note: If the MMG application is configured with the IP address, then provide the same.
##SERVER_COOKIE_ NAME##	The name for the cookie.	YES	If not set it will default to ORA_OLDS_SESSION
##SERVER_COOKIE_ TIMEOUT##	Timeout/expiry duration in seconds.	YES	If not set, it defaults to 999999



Table 5-1 (Cont.) config.sh file

Parameter	Description	Is Mandatory	Comments
##SERVER_COOKIE_I S_SECURE##	Specifies if we are using cookies to add an additional security layer to prevent cross-origin requests.  Can be either true or false	YES	If not set, it defaults to true.
##BE_AUTH_TYPE##	Auth Type on which the backend service (mmg-service) runs.	YES	It defaults to public.
##MMG_PYTHON_INT ERPRETER##	A comma separated value without whitespaces that specifies python interpreter python,fcc-ml4aml	YES	If not set, it defaults to python.
##DATACATALOG_SER VICE_URL##		NO	NA
##STUDIO_WALLET_E NABLED##	Set as true when using a wallet for the MMG Studio Schema.	YES	true/TRUE
	Can be either true/ TRUE or false/FALSE (all caps or all small)		
##LOGIN_SHOW##	Can be either true/ TRUE or false/FALSE (all caps or all small) Note: Set as true when the login screen of Studio is required. This property should be set as true if MMG application is non-SSL.	YES	It defaults to true.
##SESSION_MODE##	Can be either NOTEBOOK or NOTEBOOK_USER.	YES	If not set, it defaults to NOTEBOOK.
##STUDIO_REALM##	Can be either OFSAARealm or saml.OFSAASamlReal m	YES	OFSAARealm – the default realm for studio auth type FCC_AAI, MMG_AAIauth.saml.OFSAASaml Realm – for SAML specific studio authentication



Table 5-1 (Cont.) config.sh file

Parameter	Description	Is Mandatory	Comments
##OFSAA_URL##	AAI login IDM Service URL. This is applicable only if ## STUDIO_AUTH_TYPE	YES	Format: http:// <ofsa- web-host&gt;:<port>/ <context>/rest-api</context></port></ofsa- 
	## is " MMG_AAI ".		For example, http:// ABC00abc:4325/LLFP/ rest-api
			The /rest-api is mandatory for OFSAA URL.
##API_USERS##	This is the API user with which the token is generated; if not set, it defaults to MMG_API_USER.	YES	MMG_API_USER
	<b>Note</b> : Use the same <api_user> as given in the ##SSO_TOKEN##</api_user>		
##VALID_ROLES##	MDLUSR,MDLREV,MD LAPPR	YES	MDLBATCHUSR, DSUSRGRP,
	The comma separated values for Studio- related roles in USER- ROLE mapping.		DSREDACTGRP
##DATASOURCE_URL ##	The connection address to the database where the MMG Studio Schema is created.	YES	NA
	When ##WALLET_ENABLED ## is false-		
	jdbc:oracle:thin:@ <hos t&gt;:<port>/ <service_name></service_name></port></hos 		
	When ##WALLET_ENABLED ## is true-		
	jdbc:oracle:thin:@ <ds ALIAS&gt;</ds 		
	where <ds_alias> is the wallet alias configured for the MMG Studio Schema.</ds_alias>		
##DATASOURCE_USE RNAME##	MMG Studio Schema/ User name; required only when ##WALLET_ENABLED ## is false	YES	dsschema



Table 5-1 (Cont.) config.sh file

Parameter	Description	Is Mandatory	Comments
##DATASOURCE_PAS SWORD##	MMG Studio Schema/ User Password; required only when ##WALLET_ENABLED ## is false	YES	password
##DATASOURCE_DRI VER##	Database Driver used in connection	YES	oracle.jdbc.OracleDrive r
##JPA_DB_PLATFOR M##	Hibernate Class or SQL Dialect used in Database	YES	org.hibernate.dialect.Or acle12cDialect
##STUDIO_LOG_LEV EL##	Logging level for logs.	YES	info, warn, debug or error logs
##PYTHON_HOME##	Home Path of Python Library. It defaults to python3 during installation. For a custom installation of python3 where the soft link is not configured, you can mention the complete path up to python3.	YES	python3
##SPARK_HOME##	Absolute path of Apache Spark Library.	NO	NA
##R_ENABLED##	This can be set to TRUE/true or FALSE/ false depending on which R interpreter will be started and will be present in the interpreters list.  Note:	YES	The default is False.
	If you are using an older Studio schema with an R-interpreter already present and then install with R_ENABLED set as FALSE; the R-interpreter will remain in the interpreter's menu of Studio and must be deleted from there.		
##RS_CONF_PATH##	Absolute path to Rserve.conf file for running Rserve.	YES	/scratch/users/ datastudio/conf/ Rserve.conf
##RS_KEYSTORE##	Absolute path for the Keystore file made for Rserve.conf.	YES	/scratch/users/ datastudio/conf/ rinterpreterkeystore
##RS_KS_SECRET##	Keypass for rinterpreterkeystore.	YES	Example: changeit



Table 5-1 (Cont.) config.sh file

Parameter	Description	Is Mandatory	Comments
##TEMPLATE_CONFI G_PATH##	Configuration path of the Template.	NO	NA
##TEMPLATE_DEFAU LT_LINK##	Default link of the template.	NO	NA
##AUTH_SERVICE_U RL##	The AUTH service URL that is activated after the fccstudio.sh file runs.	NO	Example: https:// <hostname>:7041/ authservice</hostname>
##META_SERVICE_U RL##	The metaservice URL that is activated after the fccstudio.sh file runs.	NO	Example: https:// <hostname>:7045/ metaservice</hostname>
##ER_SERVICE_URL# #	Used for the entity resolution service.	NO	Example: https:// <hostname>:<port></port></hostname>
##BATCH_SERVICE_U RL##	Used for the batch service.	NO	Example: https:// <hostname>:<port>/ batchservice</port></hostname>
##SAML_ISSUER##	The SAML entity ID (Studio URL) configured in the IDP.	YES	https:// <hostname>.xyz.com:7 008</hostname>
##SAML_DESTINATIO N##	The SAML IDP URL that the Identity Provider provides after creating the SAML application.	YES	https://idcs- xyzgvh.com/fed/v1/idp/ sso
##SAML_ASSERTION ##	The SAML Consume URL (Studio/URL/saml/consume) that is configured in IDP.	YES	https:// <hostname>.xyz.com:7 008/saml/consume</hostname>
##SAML_ROLE_ATTRI BUTE##	The SAML client identifier provided by the SAML Administrator for the role and attributes information while creating the SAML application for MMG Studio.	YES	Example: group
	The attribute will contain the role required for the application.		
##SAML_STUDIO_LO GOUT_URL##	The SAML client identifier provided by the SAML Administrator for the Logout URL information, while creating the SAML application for MMG Studio.	YES	https://idcs- xyzgvh.com/sso/v1/ user/logout
##SAML_COOKIE_DO MAIN##	Domain of the server.	YES	Example: in.xyz.com
pipeline services specific	configurations		

Table 5-1 (Cont.) config.sh file

Parameter	Description	Is Mandatory	Comments
##DATAPIPELINE_SER VICE_PORT1##	The port where the pipeline service resides.	YES	By default, it is set as 18005.
##DATAPIPELINE_SER VICE_PORT2##	The port where the data pipeline service resides.	YES	By default, it is set as 18006.
##DATA PIPELINE_METADATA _ARCHIVE_PATH##	The dump path for the pipeline service.	YES	/OFS_MMG/mmg- pipeline/pipeline/ pipeline-service- x.x.x.x.x.
##DATA PIPELINE_METADATA _IMPORT_SERVICE_P ORT##	Meta data import service port.	YES	By default, it is set as 18007.
##DATAPIPELINE_ERX MLPATH##	The XML path in which the schema details are stored.	NO	NA
##DATAPIPELINE_GAT EWAY_SERVICE_POR T##	,	YES	NA
##PIPELINE_UI_SERV ICE_PORT##	Pipeline UI service port.	YES	NA
##DATA_PIPELINE_UI _SERVICE_PORT##	Data pipeline UI service port	YES	NA
##MATCHRULE_BASE _URL##	The host and port where the match rule service resides.	NO	http(s):// abc.in.xyz.com:7051
##LOADGRAPH_BASE _URL##	The host and port where the load graph service resides.	YES	http(s)://abc.in.xyz.com: 7059/graph-service
##MATCHSRVC_UI_U RL##	Matching Service UI resource path.	NO	NA



Table 5-1 (Cont.) config.sh file

Parameter	Description	Is Mandatory	Comments	
##GRAPH_INDEX_BA SE_URL##	Indicates the Graph Index resource path.	NO	NA	I
GL_OI\L##	index resource pain.			t
				ļ S
				)
				:
				/
				ł
				C
				t
				r a
				r
				;
				>
				) Z
				(
				r :
				7
				( 5
				3
				/ I
				(
				6
				- t
				(
				-
				1
				6
				t
				i
				-
				9
				a r
				(
##I OADINDEY 111 115	Indicatos the Craph	NO	NA	ł
##LOADINDEX_UI_UR L##	Load Index UI resource path.	NO.	INA	

Table 5-1 (Cont.) config.sh file

		-	
Parameter	Description	Is Mandatory	Comments
##MATCHING_MECHA NISM##	mechanism for Entity Resolution and Graph Enter the value that is used for matching mechanism for Entity Resolution and Graph. The options are OS, and OT. Where OS refers to OpenSearch, and OT refers to Candidate Selection with Oracle Text matching. By default, the value of the parameter is OT.	NO	NA
	For MATCHING_MECHANI SM = OT, no additional installation or configuration is required as it is part of the Oracle Database.		
	<b>NOTE:</b> This is applicable for Compliance Studio.		
##CANDIDATE_SELEC TION_SERVICE_URL# #		NO	NA
##LOAD_TO_OS_URL ##	Provide the URL for Entity Resolution and Graph use cases when MATCHING_MECHANI SM is set to OT.  NOTE: This is applicable for Compliance Studio.	NO	NA
##AAI_COOKIE_DOM AIN##	The domain of the server.	YES	Example: in.xyz.com
##MMG_KEYS_LOC##	Indicates public and private key location.	YES	Example:< MMG Installation Path> / OFS_MMG/conf
##GRAPH_INSTALLATI ON_PATH##	The installation path of the Graph.	YES	<pre><mmg installation="" path="">/ OFS_MMG/ mmg-load-to-graph/ graph-service</mmg></pre>
##GRAPH_KEYSTOR E_PASSWORD##	Graph Keystore Password.	YES	Password

Table 5-1 (Cont.) config.sh file

Parameter	Description	Is Mandatory	Comments
##GRAPH_SERVICE_ PORT##	Graph Service Port	YES	By default, it is set as 7059. You should not modify the Graph Service Port if graphs are already created and executed.
##MMG_DB_SERVER _NAME##	Name of the MMG Database Server.	YES	NA
##MMG_DB_PORT##	The port of the MMG database server.	YES	NA
##MMG_DB_SERVICE _NAME##	Name of the MMG Database Service.	YES	NA
##PGX_SERVER_URL S##	Indicates the pgx server resource path.  Skip this if not installing pgx.	YES	http(s):// <hostname>.xyz.com:&lt; pgx port&gt;/<pgx context<br="">name&gt;</pgx></hostname>
##MAX_TOTAL_SHAR ED_DATA_MEMORY_S IZE##	Maximum total shared data memory size.	YES	Edit if required; default value is 20 GB.
##MAX_TOTAL_PRIVA TE_DATA_MEMORY_S IZE##		YES	Edit if required; default value is 8 GB.
##MAX_PER_SESSIO N_DATA_MEMORY_SI ZE##	Maximum per session data memory size.	YES	Edit if required; default value is 700 MB.
##MAX_DATA_MEMOR Y_SIZE_DSUSRGRP# #	Maximum data memory size allowed for DSUSRGRP.	YES	Edit if required; default value is 10 GB.
##MAX_DATA_MEMOR Y_SIZE_DSBATCH##	Maximum data memory size allowed for DSBATCH.	YES	Edit if required; default value is 10 GB.
##MAX_DATA_MEMOR Y_SIZE_DSINTER##	Maximum data memory size allowed for DSINTER.	YES	Edit if required; default value is 5 GB.
##MAX_DATA_MEMOR Y_SIZE_DSAPPROVE R##	Maximum data memory size allowed for DSAPPROVER.	YES	Edit if required; default value is 5 GB.
##MAX_DATA_MEMOR Y_SIZE_DSUSER##	Maximum data memory size allowed for DSUSER.	YES	Edit if required; default value is 5 GB.
##GRAPH_SCHEMA_ WALLET_ALIAS##	Wallet alias created for the Graph Schema.	YES	NA
##GRAPH_SCHEMA_ DB_SCHEMA_NAME# #	Name of the Graph schema.	YES	NA
##EST_ENABLED##	Only used when EST application is integrated with MMG.	YES	The default value is FALSE.
##EST_UI_URL##	The URL of EST application. This is set based on ##EST_ENABLED## property.	NO	NA

Table 5-1 (Cont.) config.sh file

Parameter	Description	Is Mandatory	Comments	
##DATASTUDIO_SERV ER_PORT##	The port of the Data Studio server.	NO	The default value is 7008.	
##DATASTUDIO_MAR KDOWN_INTERPRET ER_PORT##	The port of the Data Studio Markdown Interpreter.	NO	The default values are 7009, 7029.	
##DATASTUDIO_PYTH ON_INTERPRETER_P ORT##		NO	The default values are 7012, 7032, 6012.	
##DATASTUDIO_JDBC _INTERPRETER_POR T##	The port of the Data Studio JDBC Interpreter.	NO	The default values are 7011, 7031.	
##DATASTUDIO_PYTH ON_INTERPRETER_R EST_SERVER_PORT# #	Studio Python	NO	The default value is 6012	
##DATASTUDIO_PGX_ PYTHON_INTERPRET ER_REST_SERVER_P ORT##	Studio PGX Python	NO	The default value is 6022	
##DATASTUDIO_THRI FT_EVENT_HANDLER _PORT##	The port of the Data Studio Thrift Event handler.	NO	The default value is 8432	
##DATASTUDIO_PGX_ INTERPRETER_PORT ##		NO	The default value is 7022.	
##MMG_COHERENCE _CLUSTER_PORT##	This is the port where the Coherence Cluster for the Notification service runs. By default, this value is 7574.	YES	NA	
##MMG Gateway Config				
##MMG_GATEWAY_E NABLED##	Enables or disables the MMG Gateway. By default, this is set to 'self'.	YES	NA	
	Gateway is enabled by default and gateway port is mandatory to access gateway enabled UI.			
##MMG_GATEWAY_P ORT##	Specifies the port on which the MMG Gateway will run.	YES	NA	

Table 5-1 (Cont.) config.sh file

Parameter	Description	le Mandatory	Comments
##MMG_CSP_FRAME _ANCESTORS##	Configure this attribute to all or the AAI origin when MMG has to be embedded from AAI. By default, MMG pages cannot be embedded if Gateway is enabled. This is to prevent CLickjacking	YES	NA NA
##DATASTUDIO_CSP_ FRAME_ANCESTORS ##	•	YES	NA
export SAML_SIGN_AUTHN_ REQ	NA	YES	NA
export SAML_PRIVATE_KEY_ PATH	NA	NA	/scratch/mmg8131/ config/sp- privatekey.pem
export SAML_SP_X509_CER T_PATH	NA	NA	/scratch/mmg8131/ config/sp-certificate.cer
export SAML_SIGN_ALGORI THM	NA	NA	##SAML_SIGN_ALGO RITHM##
export AUTH_SAML_REQUE ST_TYPE	NA	NA	##AUTH_SAML_REQU EST_TYPE##
export AUTH_SAML_INCLUD E_SP_CERT	NA	NA	##AUTH_SAML_INCLU DE_SP_CERT##



Table 5-1 (Cont.) config.sh file

Parameter	Description	Is Mandatory	Comments
export GIT_ENV_ID	This variable represents the environment in which your GIT operations or deployments are being performed. Common environment names include dev (development), QA (quality assurance), SIT (system integration testing), PROD (production), and so on. It helps you to understand with which branch you need to work.	NA	##GIT_ENV_ID##
export GIT_USERNAME	This is your GitHub username.	NA	##GIT_USERNAME##
export GIT_PAT_SECRET	This variable stores your GitHub Personal Access Token (PAT). A PAT is a secret token used for authenticating API requests or GIT operations over HTTPS instead of a password.	NA	##GIT_PAT_SECRET# #
export GIT_PROXY_URL	If your environment requires you to access external resources like GitHub through a proxy server, this variable defines the proxy server's hostname or IP Address.	NA	##GIT_PROXY_URL##
export GIT_PROXY_PORT	This defines the port number on which the proxy server listens. It works together with GIT_PROXY_URL to route your Git traffic through the proxy.	NA	##GIT_PROXY_PORT# #



Table 5-1 (Cont.) config.sh file

Parameter	Description	Is Mandatory	Comments
_	RESTRICT_UNMAPPE D_DATASTORES_ACC ESS is introduced in NEXTGENEMF_CONFI G table, by default the access to all datastore is allowed (value false). If user wants to restrict the access then the value of this property needs to be changed to true. If the value is set as true, only the current workspace attached data stores will be allowed to be connected from the respective workspace notebook sessions using get_conn(). This will only work if the session-mode in application.yml is set to NOTEBOOK_USER. Only true/false is allowed.	NA	##RESTRICT_UNMAP PED_DATASTORES_A CCESS##

If changes are done directly on UI and then restart is done then in that case overwrite will not be triggered so configuration would not change, it is only dependent on file system JSON).



- In case of ##OFSAA\_URL## and ##MMG\_SVC\_URL##, do not add any ending '/' in the URLs
- If pool size, connection timeout and idle timeout are not configured, then it will proceed with default Hikari Configurations.
- The default session timeout is 3600 seconds (60 mins). You can configure timeout using server.servlet.session.timeout property.
- If the AUTH type specified is AAI, make sure the AAI System has appropriate user groups mapped for the users. WKSPADMIN, IDNTYADMN, IDNTYAUTH need minimally to be present for a successful subsequent logins.
- The name for MMG Studio cookie is ORA OLDS SESSION.
- If the ##SSL\_ENABLED## is set to false, keystore configuration must be done for mmg-studio as it is SSL enabled by default. MMG application and MMG Studio can use the same SSL configuration if configured in the same server.
- The wallet is same for all the MMG services including MMG Studio. So, if you
  want to use the MMG Studio with wallet configurations, then configure in the
  same wallet.
- If the MMG Studio is remotely configured, then the MMG Application Configuration Schema wallet alias and the the thick or file entries need to be added to the MMG Studio configured wallet and the the thick or file.
- If MMG application is Non SSL, set the below property to "false" in the application.yml file inside the MMG Studio and restart the services. security:

cookies:

secure: false



### **Setting both Timeouts**

Data Studio user Login sessions to be logged out automatically after a set amount of time:

It is recommended to set both the relative and absolute session timeouts.

With the following properties, a user session will expire after one hour of inactivity or the maximum duration of 24 hours.

#### Studio-Server:

#### Security:

Absolute-session-timeout-ms: 86400000 // 24 hours

Session-timeout-ms: 3600000 // 1 hour

#### **Paragraph Execution Timeout**

Automatically cancel a paragraph execution after a set amount of time:

Studio-server:

Interpreter:

Execution:

Run-timeout: 24 hours

You can set the timeout to 0 to disable the timeout entirely. When the timeout is disabled, paragraphs will run either until they finish or are being manually cancelled.

With the following properties, a paragraph will be timed out after 24 hours.

### **Synchronous Run Timeout**

Timeout for synchronous code running (this is used for pipeline executions in MMG):

Studio-server:

Rest:

Code:

Maximum Runtime Sync: 20 minutes

With the following configuration, the synchronous run will be timed out after 20 minutes.

### Note:

The flag \*IS\_SELF\_USR\_GRP\_AUTH\_ALLOWED\* in NEXTGENEMF\_CONFIG table is used to check if the Self Groups Approvers/Reviewers are allowed or not. If it is 'Y', the Requested User as well Approvers and Reviewers can belong to the same user group. Otherwise, 'Self User Group Authorization is not allowed' is returned.

Support of Alphanumeric Name in SAML Entity ID for SAML Configuration



MMG Application: mmg\_ui/application.properties file contains SAML entity ¿saml.auth.sp.entity; placeholder that contains value like ¿https://<FQDN of compliance server>:7001/cs;

However, the requirement is to have this parameter value to ¿amlcs8126¿ i.e. support of SAML Entity ID as alphanumeric name.

The expected value from SAML team: saml.auth.sp.entity="amlcs8126":

Entity ID should not contain below special character as per ForgeRock MF Authentication (Policy sets in the UI: ForgeRock Identity Cloud docs).

The regex allowed is:  $^{A-Za-z0-9}$ , .\\/:@&?\\- ]+\$, and it should be passed in string.

## 5.4.1 Import Server Certificate to Java Keystore

You must import the server certificate (.cer) file to the Java keystore.

To import the server certificate, perform the following steps:

1. Create a .cer file from the server.keystore.

```
keytool -export -alias <alias>-file <filename>.cer -keystore
<path_to_Keystore>/server.keystore -storepass secret
```

#### **Example:**

keytool -export -alias demo\_alias -file server.cer -keystore OFS\_MMG/config/ server.keystore -storepass secret

2. Import .cer file generated from the above step to java keystore.

```
keytool -import -file "<path_to_Keystore>/<filename>.cer" -alias <alias>-
keystore "<java home>/lib/security/cacerts" -storepass "changeit"
```



The above step should be performed by the Root user.

## 5.5 Run the MMG Installer

To run the MMG Installer, follow these steps:

1. Navigate to following path:

Go to < MMG INSTALLATION PATH > / bin directory.

2. Run the following command:

./install.sh



When ./install.sh command is triggered, pre-installation utility validates install configurations such as availability of ports, ftpshare/log folders, database connections, and so on.

This step will install the configurations and has to be executed only once per deployment. This will also bring up the Schema Creator Service in nohup mode.

A message similar to following means a successful startup:

<MMG INSTALLATION PATH>/OFS MMG/bin>./install.sh

PIPELINE HOME: <MMG INSTALLATION PATH>/OFS MMG/mmg-pipeline/pipeline

<MMG INSTALLATION PATH>/OFS MMG/mmg-pipeline/pipeline

PIPELINE\_HOME: <MMG\_INSTALLATION\_PATH>/OFS\_MMG/mmg-pipeline/pipeline

Installing Pipeline Data Model. Please Wait ...

Pipeline Data Model installation finished.

Starting Gateway ...

Starting Pipeline UI Service ...

Starting Pipeline Service ...

Starting Data Pipeline UI Service ...

Starting Data pipeline services ...

Inserting DataMeta Data ...

Stopping Graph-Service service...

Graph-Service stopped.

Schema Creator executed successfully for config schema

Schema Creator for config executed successfully.

If Graph Schema is configured, the below message is displayed.

Now triggering for graph-schema

./../mmg-schema-creator/bin/startup.sh: line 70: 126438 Killed nohup java -jar -Doracle.net.tns admin=/scratch/ofsaadb -Doracle.net.wallet location=/scratch/ofsaadb/ wallet -Dspring.config.location=../conf/ -Dspring.datasource.url=jdbc:oracle:thin:@conf als -Dspring.liquibase.change-log=file:../scripts/changelog-master.xml \$JAVA OPTS ../lib/ mmg-schema-creator.war > nohup.out 2>&1

Schema Creator executed successfully for graph schema

nohup: ignoring input and redirecting stderr to stdout

Stopping Graph-Service service...

Graph-Service stopped.

nohup: ignoring input and redirecting stderr to stdout

You can check mmg-schema-creator/bin/nohup.out to check if the service comes up properly.

Started BuildSchemaCreatorApplication in 20.317 seconds (JVM running for 21.26)



### WARNING:

If you notice any errors, do not proceed further. Contact My Oracle Support (MOS) and provide the applicable error code and log files.



3. Execute shutdown.sh and trigger startup.sh for the services to come up. For more details, refer to the below sections.



The MMG Application is installed with or without OFSAA, depending on the configuration provided in the config.sh file.

# 5.6 Starting MMG Services

To start the MMG service, run the following command:

• Navigate to <MMG\_INSTALLATION\_PATH>/bin directory. ./startup.sh

A message similar to following means a successful startup:

Starting MMG UI...

MMG UI started successfully.

Starting MMG Service...

MMG Service started successfully.

Starting Data Studio...

Data Studio started successfully.

Starting Gateway ...

Starting Pipeline UI Service ...

Starting Pipeline Service ...

Starting Data Pipeline UI Service ...

Starting Data pipeline services ...

You may check <MMG\_INSTALLATION\_PATH>/mmg-ui/bin/nohup.out to check if the UI service comes up properly.

A message similar to following means a successful startup:

Started BuildUIServiceApplication in 27.981 seconds (JVM running for 29.365)

You can check <MMG\_INSTALLATION\_PATH>/mmg-service/bin/nohup.out to check if the backend service comes up properly.

A message similar to following means a successful startup:

Started BuildServiceBuildApplication in 20.317 seconds (JVM running for 21.26)

You can check <MMG\_INSTALLATION\_PATH>/mmg-studio/bin/nohup.out to check if the backend service comes up properly.

A message similar to following means a successful startup:

05:06:02.155 Thread-9] INFO oracle.datastudio.starter.App - Data Studio Server is ready to use

This will start the successful installation of application.



### WARNING:

If you notice any errors, do not proceed further. Contact My Oracle Support (MOS) and provide the applicable error code and log files.

### Note:

Unset the https/http proxy details before starting the services.

Add the relevant entries in no proxy with mmg hosted server details.

## 5.7 Stopping MMG Services

To stop the MMG services, run the following command: ./shutdown.sh

A message similar to following means a successful shutdown:

Stopping Graph-Service service...

Graph-Service stopped.

MMG UI shutdown is complete.

MMG Service shutdown is complete.

MMG Schema Creator shutdown is complete.

Data Studio shutdown is complete.

Data Pipeline Service shutdown is complete.

## 5.8 Generate GRAPH-KEYSTORE.P12

Graph services should be up and running.

To generate GRAPH-KEYSTORE.P12 file, perform the below steps:



The Keystore generation fails if graph service is down.

- **Execute** graph-keystore-generator.sh using PUTTY.
- Enter the values as below when prompted.

Enter Wallet Alias: <GRAPH\_SCHEMA\_WALLET\_ALIAS> as given in the config.sh file.

Enter Password: <GRAPH\_SCHEMA\_DB\_SCHEMA> password

Enter Keystore alias: <GRAPH\_SCHEMA\_DB\_SCHEMA\_NAME> as given in the config.sh file.

Check the below location for the graph-keystore.p12

<mmq installation path>/OFS MMG/mmq-load-to-graph/graph-service/conf/



## 5.9 Installing Conda

Conda as a package manager helps you to find and install packages. With the capability of environment manager, you can set up a totally separate environment to run different versions of Python. In addition, you can continue to run your usual version of Python in your normal environment.



The supported version is 4.14.0.

To install the Conda, perform the following:

- 1. Download the miniconda.
- 2. Copy it to your server where the Conda needs to be installed.
- 3. Grant execute permission to the Conda folder.
- 4. Execute the following command: \$ ./Miniconda3-latest-Linux-x86 64.sh
- 5. Update the PATH variable with miniconda installation path:

<install path>/miniconda3/bin



In the current release, the Conda feature is not supported in Solaris Operating System.

For more details on the Roles and privileges, see MMG User Guide.

## 5.10 Installing Python Library

This section provides detailed steps to install the Python Library.

## 5.10.1 Prerequisites

Python 3.8.x and above



Ensure the libraries, bzip2-devel, sqlite-devel, ncurses-devel, and xz-devel, libffidevel are installed before you install the Python package.

For Example:

Install the below libraries as a root user.

- bzip2-devel: Execute the command yum install bzip2-devel
- sqlite-devel: Install as a root user using the command yum install sqlite-devel
- ncurses-devel: Install as a root user using the command yum install ncurses-devel
- xz-devel: Install as a root user using the command yum install xz-devel
- libffi-devel: Install as a root user using the command yum install libffidevel

### Note:

In order to download the latest python packages after MMG upgrade, the pip cache in the server user home directory needs to be cleared.

Path: \$HOME/.cache/pip

#### Note:

Documentation of Mandatory Parameter to be passed as part of Python environment install.sh Installation

Now, parameters is supported as below for python-env-install.sh file:

The user needs to be passed in case the packages has to be installed at a user level. The above is not required in case of CONDA environment. In this case make sure the Python3 is pointed to proper Conda environments.

### 5.10.2 Procedure

- 1. Set system python3 to the one that is to be used. Navigate to bin folder.
- 2. To install the mmg library with dependencies from <code>conf/requirements.txt</code>, execute the following command:

./python-env-install.sh

The following parameter is supported for python-env-install.sh file:

--user need to be passed in case the packages has to be installed at user level.

This is not required in case of Conda environment but python3 must be configured to the appropriate Conda environments.



Expose Python variables/functions to derive File Path when saving files directly from Notebook script (without using Save Widget).

**3.** To install the mmg library with flexible dependencies or using already installed dependent packages, execute the following command:

```
./python-env-install.sh -S
```

#### OR

./python-env-install.sh --skip

This will skip the installation of dependency based on the version mentioned in the conf/requirements.txt. The installation will be with whatever version available in the pypi server.

4. To install the Apache Flink packages, execute the following command:

```
./python-env-install.sh --include-flink
```



Ignore the below error message during Apache Flink package installation. ERROR: pip's dependency resolver does not currently take into account packages that are installed. This behavior is the source of the following dependency conflicts. modin 0.19.0 requires pandas==1.5.3, but you have pandas 1.3.5 which is incompatible. Successfully installed numpy-1.21.4 pandas-1.3.5 pythondateutil-2.8.0 Installing with dependencies ERROR: pip's dependency resolver does not currently take into account all the packages that are installed. This behavior is the source of the following dependency conflicts. pemja 0.2.6 requires numpy==1.21.4, but you have numpy 1.24.2 which is incompatible. apache-flink 1.16.1 requires numpy<1.22.0,>=1.21.4; python full version >= "3.7", but you have numpy 1.24.2 which is incompatible. apache-flink 1.16.1 requires pandas<1.4.0,>=1.3.0; python full version >= "3.7", but you have pandas 1.5.3 which is incompatible. apache-flink 1.16.1 requires python-dateutil==2.8.0, but you have python-dateutil 2.8.2 which is incompatible. apache-beam 2.38.0 requires numpy<1.23.0,>=1.14.3, but you have numpy1.24.2 which is incompatible.

## 5.11 Setting up the Environment for Hive Data Sourcing

This section is applicable if you want to use Hive Data Source.

In the MMG Home directory, a lib folder is available for the Hive specific jars and a conf folder is available for the Kerberos Configuration and Keytab files.

#### **Hive Source Connection Requirements:**

MMG\_HOME/conf: kbank.keytab and krb5.conf files

MMG\_HOME/lib: hive-jdbc-uber-2.6.3.0-235.jar

MMG-Studio/conf: kbank.keytab, krb5.conf and hive-jdbc-driver.jar

The Datastudio placement of jars are for creating a connection from python library and the other is from java, for data sourcing.

### **Configure the Hive Jars and Configuration Files**

For Hadoop version 3.1.1 and hive version 3.1.2, below is the list of jar files that needs to be copied into the OFS MMG/lib location:

zookeeper-3.4.9.jar

woodstox-core-5.0.3.jar

stax2-api-3.1.4.jar

slf4j-log4j12-1.7.25.jar

slf4j-api-1.7.25.jar

re2j-1.1.jar

log4j-1.2.17.jar

libthrift-0.9.3.jar

libfb303-0.9.3.jar

httpcore-4.4.4.jar

httpclient-4.5.2.jar

htrace-core4-4.1.0-incubating.jar

hive-service-3.1.2.jar

hive-metastore-3.1.2.jar

hive-jdbc-3.1.2.jar

hive-exec-3.1.2.jar

hadoop-hdfs-client-3.1.1.jar

hadoop-common-3.1.1.jar

hadoop-auth-3.1.1.jar

curator-client-2.12.0.jar

commons-logging-1.0.4.jar

commons-io-2.4.jar

commons-configuration2-2.1.1.jar

commons-collections-3.2.2.jar

commons-cli-1.2.jar

The MMG service requires a restart after copying the Hive jars and configuration files. For more information, see the MMG User Guide.



## 5.12 Remote MMG Studio Configuration

For Solaris Operating System, the MMG Studio has to be configured in Linux machine remotely. The MMG Studio URL must be the same as that of the remote studio during MMG Application Installation.

In the  ${\tt OFS\_MMG/bin/config.sh}$ , update the following properties with the remote server where the MMG Studio will be running:

Copy the mmg-studio folder to the remote machine where you want to configure the same.

Navigate to mmg-studio/bin and update the config.sh file with respect to studio server values. For more details, see the Configure the config.sh file section.

```
export DATASTUDIO_URL=##DATASTUDIO_URL##
export SSL_KEYSTORE=##SSL_KEYSTORE##
export SSL_KS_SECRET=##SSL_KS_SECRET##
export SSL_KS_TYPE=##SSL_KS_TYPE##
export SSL_KS_ALIAS=##SSL_KS_ALIAS##
```

### Note:

The keystore must be generated for the remote machine and the path must be present in the remote server.

```
export DS_TNS_ADMIN_PATH=##DS_TNS_ADMIN_PATH##
export DS WALLET LOCATION=##DS WALLET LOCATION##
```

TNS admin and wallet must be configured in the remote server and the wallet must contain the mmg config schema wallet configurations.

```
export MMG_TNS_ADMIN_PATH=##MMG_TNS_ADMIN_PATH##
export MMG_LIB_WALLET_ALIAS=##MMG_LIB_WALLET_ALIAS##
```



The Self signed certificate needs to be generated and imported to the Java keystore. In case self-signed certificate is being used, perform the below step:

 Delete the already imported certificate from the Java keystore using the below command keytool:

-delete -noprompt -alias <alias\_name> -keystore "<java\_home>/lib/ security/cacerts" -storepass "changeit"

2. Run the following command to re-create a Java keystore:

keytool -genkey -v -alias <alias\_name> -keyalg RSA -keysize 2048 keystore server.keystore -validity 3650 -keypass secret -storepass
secret -storetype PKCS12

**Example**: keytool -export -alias demo\_alias -file server.cer -keystore OFS MMG/config/server.keystore -storepass secret

4. Import .cer file generated from the above step to java keystore. keytool -import -file "<path\_to\_Keystore>/<filename>.cer" -alias <alias>-keystore "<java\_home>/lib/security/cacerts" -storepass "changeit"

### Note:

The above step should be performed by the Root user.

### Note:

The token is automated. Once the token is generated, ignore '-e' character present in the token.out file.

## 5.13 PGX Installation

### Note:

PGX Installation is recommended to be installed in a different server other than the MMG Installation Server.

To install the PGX, follow these steps:

- 1. Copy the mmg-pgx.zip file from MMG Server and copy it to the target server where PGX has to be installed remotely to MMG.
- 2. Unzip the mmg-pgx.zip file.

For Example: unzip -a mmg-pgx.zip.



The below files will be displayed:

- bin
- conf
- pgx-23.4.6
- Give 0755 permission to mmg-pgx folder.
- Configure the config.sh of pgx. For more details, see Configure the config.sh File of PGX section.
- Copy the graph-keystore.p12 from MMG Installation server to <pgx installation path>/mmgpgx/conf. For more details, see Generate GRAPH-KEYSTORE.P12 section.
- Copy the below key files from <MMG Installation path>/OFS\_MMG/conf to <pgx installation path>/mmg-pgx/conf.
  - public.key
  - private.key
- Run the install.sh from <pgx installation path>/mmg-pgx/bin
- 8. Update the pgx-server URL in config.sh for ##PGX\_SERVER\_URLS## in the <MMG Installation path>/bin and run the install.sh -u command and restart the MMG services. For more details, see Configure the config.sh File of PGX section.
- 9. Start the Server. For more details, see Starting PGX Server section.
- 10. Stop the Server. For more details, see Stopping PGX Server section.

## 5.13.1 Configure the config.sh File of PGX

To configure the config.sh file for installing PGX with MMG, follow these steps:

- 1. Login to the server as a non-root user.
- 2. Navigate to the <OFS MMG>/mmg-pgx/bin directory.
- 3. Configure the applicable config.sh attributes as shown in the following table:

#### Sample Config.sh file

```
#!/bin/sh
export PGX_PORT=##PGX_PORT##
export PGX_CONTEXT_PATH=##PGX_CONTEXT_PATH##
export PGX_SSL_ENABLED=##PGX_SSL_ENABLED##
export PGX_SSL_KEYSTORE=##PGX_SSL_KEYSTORE##
export PGX_SSL_KS_SECRET=##MMG_SSL_KS_SECRET##
export PGX_SSL_KS_TYPE=## PGX_SSL_KS_TYPE ##
export PGX_SSL_KS_ALIAS=## PGX_SSL_KS_ALIAS##
export GRAPH_SERVICE_URL=## GRAPH_SERVICE_URL##
export GRAPH_KEYSTORE_PASSWORD=## GRAPH_KEYSTORE_PASSWORD##
export LOG_HOME=##LOG_HOME##
export LOG_HOME=##LOG_HOME##
```



Table 5-2 Config.sh file of PGX

Parameter	Description	Is Mandatory	Comments
##PGX_PORT##	Port on which PGX server needs to be run.	YES	If not set, Port defaults to 7007.
##PGX_CONTEXT_PA TH##	Context path of PGX server	YES	If not set, Context path defaults to PGX.
##PGX_SSL_ENABLE D##	The values can be true /false.	YES	
	If true, follow the below steps if Self Signed is being used:		
	<ul> <li>Import PGX server.cer file to MMG server java keystore</li> </ul>		
	<ul> <li>Import MMGserver.cer file to PGX server java keystore</li> </ul>		
	For more details, see Import Server Certificate to Java Keystore section.		
Properties if ##PGX_SS	SL_ENABLED## is set to	true.	
##PGX_SSL_KEYSTO RE##	Absolute path for the keystore file.	YES	/conf/server.keystore. Include the file name in
	This is applicable only if ##PGX_SSL_ENABLE D## is set to true.		the path.
	NOTE:		
	Run the following command to create a keystore:		
	keytool -genkey -v - alias demoalias -keyalg RSA -keysize 2048 - keystore		
	server.keystore -validity 3650 -keypass secret - storepass secret - storetype PKCS12		
##PGX_SSL_KS_SEC RET##	Value passed in above command for keypass.	YES	Keystore password
	This is applicable only if ##PGX_SSL_ENABLE D## is set to true.		
##PGX_SSL_KS_TYP E##	The type of the PGX keystore.	YES	PKCS12
	This is applicable only if ##PGX_SSL_ENABLE D## is set to true.		



Table 5-2 (Cont.) Config.sh file of PGX

Parameter	Description	Is Mandatory	Comments	
##PGX_SSL_KS_ALIA S##	The Alias of the PGX keystore.	YES	password123	
	This is applicable only if ##PGX_SSL_ENABLE D## is set to true.			
Properties for graph service				
##	Graph Service URL.	YES	http(s):// <mmg< td=""></mmg<>	
GRAPH_SERVICE_UR L ##	The value is same as ##LOADGRAPH_BASE _URL## in the MMG.config.sh		Host>: <graph port="" service="">/graph-service</graph>	
## GRAPH_KEYSTORE_	Graph Keystore password.	YES	password123	
PASSWORD ##	The value is same as ##GRAPH_KEYSTOR E_PASSWORD## in the MMG.config.sh			
Properties for setting log path				
##LOG_HOME##	A writable folder that stores PGX logs.		/scratch/users/logs	
##LOG_LEVEL##			The values can be DEBUG/INFO/WARN	

## 5.13.2 Starting PGX Server

To start the PGX Server, run the following command:

Navigate to < MMG INSTALLATION PATH > / bin directory. ./startup.sh

You may check <mmg-pgx/pgx-<pgx-version/bin/nohup.out to check if the UI service comes up properly.

A message similar to following means a successful startup:

INFO: Starting ProtocolHandler ["http-nio-7007"]

This will start the successful installation of PGX Server.

## 5.13.3 Stopping PGX Server

To stop the PGX Server, run the following command:

./shutdown.sh

A message similar to following means a successful shutdown:

PGX Server shutdown is complete.

## 5.14 R Interpreter

You can configure the R Interpreter support either with ORD-3.6.1 or R 4.1.2.

## 5.14.1 Installing Oracle R Distribution

https://docs.oracle.com/en/database/oracle/machine-learning/oml4r/2.0.0/oread/install-oracle-r-distribution-linux.html

- Check installation:
  - 1. R --version

### 5.14.2 R 4.1.2 Installation



This setup might update some of the older root level files and using Non-Oracle Yum Repository for getting R rpm files.

To install R 4.1.2, follow these steps:

- 1. Set Proxy, (pseudo user):
  - a. curl -O https://dl.fedoraproject.org/pub/epel/epel-release-latest-7.noarch.rpm
  - b. yum install epel-release-latest-7.noarch.rpm
  - c. curl -O https://cdn.rstudio.com/r/centos-7/pkgs/R-\${R\_VERSION}-1-1.x86\_64.rpm
  - d. sudo yum install R-\${R\_VERSION}-1-1.x86\_64.rpm
  - e. sudo In -s /opt/R/\${R\_VERSION}/bin/R /usr/bin/R
- 2. Check installation:
  - a. R --version

## 5.14.3 MMG Connection Objects Library Setup

This section describes the MMG Connection Objects Library Setup.

For detailed description on installation and installation of Oracle R Enterprise Client libraries (ROracle, and so on), check following link:

https://docs.oracle.com/cd/E83411 01/OREAD/installing-ORE-client.htm#OREAD167

## 5.14.3.1 Installing ROracle Library

### **Prerequisites**

DBI is one of the dependencies for using this library.

- Installing DBI
  - 1. curl O https://cran.r-project.org/src/contrib/Archive/DBI/DBI\_1.1.1.tar.gz
  - 2. R CMD INSTALL DBI\_1.1.1.tar.gz

#### **Procedure**

To install ROracle Library, follow these steps:

For ORD 3.6.1/R 4.1.2



- curl O https://cran.r-project.org/src/contrib/ROracle 1.3-1.1.tar.gz
- 2. Install Oracle Instant Client Sdk Package. This is required for additional header files and an example makefile for developing Oracle Applications with Instant Client.
- 3. Oracle client lib must be present in PATH. In the .profile file, set PATH to include the appropriate \$ORACLE HOME/bin path.

### For example:

PATH=\$JAVA HOME/bin:\$ORACLE HOME/bin

4. R CMD INSTALL --configure-args='--with-oci-lib=<absolute-path-to-oracle-client-lib> --with-oci-inc=<absolute path to instantclient\_21\_5>/include' ROracle 1.3-1.1.tar.gz

#### For example:

R CMD INSTALL --configure-args='--with-oci-lib=/scratch/users/oracle/app/oracle/product/19.3.0/client\_1/lib --with-oci-inc=/scratch/users/oracle/instantclient-sdk/instantclient\_21\_5/sdk/include' ROracle\_1.3-1.1.tar.gz

## 5.14.3.2 Installing RODBC Library

- For ORD 3.6.1
  - 1. curl -O https://cran.r-project.org/src/contrib/Archive/RODBC/RODBC\_1.3-16.tar.gz
  - 2. R CMD INSTALL RODBC 1.3-16.tar.gz



It needs write permission to  $\widtharping{'usr/lib64/R/library'}$  or similar root directory for system installation.

- For R 4.1.2
  - 1. curl -O https://cran.r-project.org/src/contrib/Archive/RODBC\_1.3-16.tar.gz
  - 2. R CMD INSTALL RODBC 1.3-16.tar.gz



LD\_LIBRARY\_PATH should contain path to <code>\$ORACLE\_HOME/lib</code> and check that file 'libsqora.so.19.1' exists in <code>\$ORACLE\_HOME/lib</code>. Now, set an environment variable named <code>RODBC\_DRIVER</code> with value 'libsqora.so.19.1' whichever is present in <code>\$ORACLE\_HOME/lib/</code> directory based on the Oracle Client Version Installation.

Now for RODBC Connection to work for Sandbox, check the <code>TNS\_ADMIN</code> path set, and then in <code>tnsnames.ora</code>, add the connection string details with alias as Sandbox Name. For example, if Sandbox Name is SAND1 for which the datasource is on host abc.in.oracle.com , port 1234 and service name – ABCXYZ, then in <code>tnsnames.ora</code> file add the following entry-

```
SAND1 =
(DESCRIPTION =
(ADDRESS_LIST =
(ADDRESS = (PROTOCOL =
TCP) (HOST=abc.in.oracle.com) (PORT=1234))
)
(CONNECT_DATA =
(SERVICE_NAME = ABCXYZ)
)
)
```

If this only does not resolve the connections, then configure odbcinst.ini. / odbc.ini files as well as mentioned in Oracle Client Installation and Setup (figured by: > odbcinst.j)

## 5.14.4 Installing the IRkernel

To configure IRkernel, follow these steps:

1. The IRkernel requires jupyter installed. Create a conda environment with the IRkernel dependencies:

```
conda create -p <PATH TO YOUR CONDA ENV> -y --override-channels -c <CHANNEL URL> jupyter_client==7.2.2 grpcio protobuf
```

Install the IRkernel in R: Open your R REPL (R does not have to be installed with conda) and run:

```
install.packages('IRkernel')
```

3. Softlink jupyter and register IRkernel:

```
ln -s <PATH TO YOUR CONDA ENV> /usr/bin/jupyter && R -e
"IRkernel::installspec(user = FALSE)"
```



## 5.14.5 Configuring R Interpreter

Make sure to configure the interpreter config and set the correct path for R binary (zeppelin.R.cmd) and the path to Python environment which has the IRkernel installed (zeppelin.python).

In config.sh there is a new parameter:

export R\_PYTHON\_HOME=##R\_PYTHON\_HOME##

This is the Python Conda environment path till <PATH TO YOUR CONDA ENV>/bin/python created following steps mentioned in 5.9, which will set the zeppelin.python property in mmg-studio/server/builtin/interpreters/r.json file.

The other property mentioned for R binary (zeppelin.R.cmd) is also set in above path the default value is R so make sure that the user starting the services has access to R and alias is set or change the property according to the path of R binary.



Steps to enable TLS during R Interpreter Installation

Steps to enable TLS during R Interpreter Installation:

- Download Rserve\_1.8-10.tar.gz from this link: https://cran.r-project.org/src/contrib/ Archive/Rserve/
- 2. Install openssl-devel [yum install openssl-devel]
- 3. Execute below cmd:

```
R CMD INSTALL --configure-args="--with-ssl-headers=/usr/include --with-ssl-libraries=/usr/lib64" Rserve 1.8-10.tar.gz
```

The below steps can be executed from R session to check that Rserve configuration is working before starting the services:

Start R from Terminal/Putty and execute the below commands:

- library(Rserve)
- Rserve(args="--RS-conf <Rserve.conf file location including file name> --no-save")

## 5.14.6 Using MMG Studio to Oracle Connection Objects

This section describes the Using MMG Studio to Oracle Connection Objects.

### 5.14.6.1 Workspaces

- 1. mmg.list\_workspaces(): Used to fetch a vector of all workspaces.
  For example: vec <- mmg.list workspaces() vec will be vector object</pre>
- 2. mmg.attach\_workspace("workspace\_name"): A method used to set workspace.

  Sets a global mmg attached WS variable with value of workspace name

Sets a mmg\_DS\_Vec Vector Object with name and order of all datasources for attached workspace.

Sets a  $mmg_WL_Vec$  Vector Object with name and wallet of all datasources for attached workspace.

For example:

mmg.attach workspace("SB1")

### 5.14.6.2 Connections

Following is the list of datasources related to workspace using:

 mmg.list\_datasources ("SB1", 1): will list datasources related to SB1 workspace with order 1 as passed in second argument

mmg.list\_datasources("workspace\_name", order) order is integer for specific order or null for all datasources.

For example:

df <- mmg.list\_datasources("workspace\_name",order) df will be Data.Frame Object.

From the datasource name or order for the attached workspace, we can get the **ROracle** or **RODBC** Connection Object.

mmg.get connection():

datasource\_name is the string name of the datasource, order is integer, library is one of "RODBC" or "ROracle"

```
conn <- mmg.get_connection(datasource=order,conn_type="library");
conn <- mmg.get_connection(datasource="datasource_name",conn_type="library");
conn <- mmg.get_connection(datasource=order,"library");
conn <- mmg.get_connection(datasource=order,"library");
conn <- mmg.get_connection("datasource_name",conn_type="library");
conn <- mmg.get_connection(order,conn_type="library");
conn <- mmg.get_connection("datasource_name","library");
conn <- mmg.get_connection(order,"library");</pre>
```

sets the conn variable to connection object of relevant library

## 5.15 Multi Level Approval

Model Pipeline deployment process by default requires one level of approval for every stage including model pipeline acceptance, promotion to production, and so on.

The requestor is allowed to select Reviewer and Approver user groups. All the user groups with MDLREVIEW function mapped to them are displayed in the Reviewers selector field. Similarly, the user groups with the MDLAPPROVE function mapped to them are displayed in the Approvers selector field. Applicable Pending requests are shown in the Reviewer/Approver tabs.

To add multi level approvers or reviewers, perform the following:

1. Navigate to <installation directory>/MMG/OFSMMG/conf/workflow/model-pipeline/default.yml

Following are the default values: workflow:

workflow-name: Default Workflow



```
num-approver-levels: 1
levels:
- level: 1
approvers:
escalation-approvers:
escalation-trigger-time: 0
lock-approver-selection: false
enable-approver-notification: true

Modify the approver levels based on your requirements as shown below.
```

Figure 5-1 Multi level approval

```
workflow:
workflow-name: Default Workflow
num-approver-levels: 2
levels:
- level: 1
approvers: APPROVER1
escalation-approvers: MDLAPPR
- level: 2
approvers: APPROVER2
escalation-approvers: MDLAPPR
escalation-trigger-time: 12
enable-approver-notification: true
lock-approver-selection: true
```

### 5.16 Kafka Installation

#### Windows

#### Apache Zookeeper (Download the bin tar):

https://shaaslam.medium.com/installing-apache-zookeeper-on-windows-45eda303e835#.fgofwm6n6

#### **Apache Kafka:**

https://shaaslam.medium.com/installing-apache-kafka-on-windows-495f6f2fd3c8

#### Linux

**Method 1(Using separate zookeeper)** 

#### **Apache Zookeeper**

- 1. Download Apache Zookeeper bin files from https://www.apache.org/dyn/closer.lua/zookeeper/zookeeper-3.7.1/apache-zookeeper-3.7.1-bin.tar.gz
- 2. Untar apache-zookeeper-3.7.1-bin.tar.gz tar -zxvf apache-zookeeper-3.7.1-bin.tar.gz
- 3. In conf folder, rename zoo-sample.cfg to zoo.cfg



- 4. Make a folder named data in /scratch/users/ofsaa/zookeeper/apache-zookeeper-3.7.1-bin
- 5. Change the value of dataDir in zoo.cfg to dataDir=/scratch/users/ofsaa/ zookeeper/apache-zookeeper-3.7.1-bin/data
- 6. Open a terminal and set the below values:

```
export ZOOKEEPER_HOME=/scratch/users/ofsaa/zookeeper/apache-
zookeeper-3.7.1-bin
```

export PATH=/scratch/users/ofsaa/zookeeper/apache-zookeeper-3.7.1bin/bin:\$PATH

7. Start the zookeeper server:cd /scratch/users/ofsaa/zookeeper/apache-zookeeper-3.7.1-bin/bin ./zkServer.sh start

#### A few commands for zookeeper server:

- ./zkServer.sh start
- ./zkServer.sh start-foreground
- ./zkServer.sh stop
- ./zkServer.sh status

#### Apache Kafka

- Download Apache Kafka bin files
  - wget https://downloads.apache.org/kafka/3.3.1/kafka 2.13-3.2.0.tgz
- Untar kafka\_2.13-3.2.0.tgz
   tar -zxvf kafka\_2.13-3.2.0.tgz
- Make a folder "logs" in the directory /scratch/users/ofsaa/kafka/kafka\_2.13-3.2.0/.
- Go to config folder in Apache Kafka and edit server.properties using any text editor. Change value of logs.dir to log.dirs=/scratch/users/ofsaa/kafka/kafka\_2.13-3.2.0/logs in server.properties
- Go to config folder in Apache Kafka and edit zookeeper.properties using any text editor. Change value of dataDir dataDir=/scratch/users/ofsaa/zookeeper/apache-zookeeper-3.7.1-bin/data
- Start Apache Kafka broker

```
cd /scratch/users/ofsaa/kafka/kafka_2.13-3.2.0/bin/
```

### ./kafka-server-start.sh ../config/server.properties

Method 2(Using zookeeper shipped with Apache Kafka)

#### Apache Zookeeper and Kafka

- Download Apache Kafka bin files
  - wget https://downloads.apache.org/kafka/3.3.1/kafka 2.13-3.2.0.tgz
- Untar kafka\_2.13-3.2.0.tgz
   tar -zxvf kafka\_2.13-3.2.0.tgz
- Go to config folder in Apache Kafka and edit zookeeper.properties using any text editor. Change value of dataDir to dataDir=/scratch/users/ofsaa/zookeeper/apache-zookeeper-3.7.1-bin/data or any folder where the snapshot of zookeeper metadata can be stored.
- Make a folder "logs" in the directory /scratch/users/ofsaa/kafka/kafka 2.13-3.2.0/.



- Go to config folder in Apache Kafka and edit server.properties using any text editor. Change value of logs.dir to log.dirs=/scratch/users/ofsaa/kafka/kafka 2.13-3.2.0/logs in server.properties.
- Start Apache Zookeeper

cd /scratch/users/ofsaa/kafka/kafka/kafka 2.13-3.2.0

bin/zookeeper-server-start.sh config/zookeeper.properties

Start Apache Kafka Broker

cd /scratch/users/ofsaa/kafka/kafka 2.13-3.2.0

bin/kafka-server-start.sh /config/server.properties

#### **Create Keys and Certificates**

- keytool -keystore kafka.server.keystore.jks -alias localhost -keyalg RSA -validity 365 -genkey -storepass oracle123 -keypass oracle123 -ext SAN=DNS:ofss-mum-1035.snbomprshared1.gbucdsint02bom.oraclevcn.com
- openssl req -new -x509 -keyout ca-key -out ca-cert -days 365
- keytool -keystore kafka.client.truststore.jks -alias CARoot -storepass oracle123 -keypass oracle123 -importcert -file ca-cert keytool -keystore kafka.server.truststore.jks -alias CARoot -storepass oracle123 -keypass oracle123 -importcert -file ca-cert
- keytool -keystore kafka.server.keystore.jks -alias localhost -storepass oracle123 -keypass oracle123 -certreg -file cert-file
- openssl x509 -req -CA ca-cert -CAkey ca-key -in cert-file -out cert-signed days 365 -CAcreateserial -passin pass:oracle123
- keytool -keystore kafka.server.keystore.jks -alias CARoot -storepass oracle123
   -keypass oracle123 -importcert -file ca-cert keytool -keystore
   kafka.server.keystore.jks -alias localhost -storepass oracle123 -keypass
   oracle123 -importcert -file cert-signed

#### Converting Keystore file from jks to pem

- keytool -exportcert -alias localhost -keystore kafka.server.keystore.jks -rfc
   -file certificate.pem -storepass oracle123
- keytool -v -importkeystore -srckeystore kafka.server.keystore.jks -srcalias localhost -keystore cert\_and\_key.p12 -storetype PKCS12 -storepass oracle123 srcstorepass oracle123
- openssl pkcs12 -in cert\_and\_key.p12 -nodes -nocerts -out key.pem -passin pass:oracle123
- keytool -exportcert -alias CARoot -keystore kafka.server.keystore.jks -rfc file CARoot.pem -storepass oracle123

Inside the Kafka/config path we have to create client-ssl.properties and server-ssl.properties.

#### The client-ssl.properties file contains the following:

- security.protocol=SSL
- ssl.truststore.location=/scratch/mmg8131/kafka/ssl/kafka.server.truststore.jks
- ssl.truststore.password=oracle123
- ssl.keystore.location=/scratch/mmg8131/kafka/ssl/kafka.server.keystore.jks
- ssl.keystore.password=oracle123



• ssl.key.password=oracle123

server-ssl.properties contains the same content as server.properties, but we have to update the ssl parameters in it.



6

# Post-installation Steps


On successful installation of the application, refer to the below topics for post-installation procedures.

### 6.1 Access the Application

To access the application, follow these steps:

Open a browser and enter the URL in the following format:





For more information, see the User Access and Permissioning Management section.

# 6.2 Create Application Users

Create the application users in the setup before starting to use the application. For more information, see the User Access and Permissioning Management section.

# 6.3 Map Application User(s) to User Group

User Groups seeded with the OFS MMG Application Pack are listed in the Seeded User Groups table.

Table 6-1 Seeded User Groups

User Group Name	User Group Description	
MDLREV	The Modeling Reviewer Group.	
	Users mapped to this group have access to the menu items in the OFS MMG Application that are related to model review activities.	
MDLAPPR	The Modeling Approver Group.	
	Users mapped to this group have the rights to approve models created by the users.	
MDLBATCHUSR	The Modeling Batch User. Scheduler can use this Group for executing batches.	
WKSPADMIN	The Workspace Administrator Group.	
	Users mapped to this group have access to all the menu items in the OFS MMG Application. Additionally, they have authorization rights to create and populate workspaces.	
MDLUSR	The Modeling User Group.	
	Users mapped to this group have access to all the menu items in the OFS MMG Application that is related to model creation.	
DSUSRGRP	General Role	
	Users mapped to this group have permission to access/modify MMG Studio Interpreter Configurations.	
DSREDACTGRP	Roles for applying redaction in graph. This group will be applicable to only those users for whom graph redaction is required.	
OBJMIGADMIN	Users mapped to this group have access to Object Migration links and UI to perform import or export of objects.	
GRPADMIN	The Graph Administrator Group. Users mapped to this group have access to all the menu items in the OFS MMG Application related to graph and Pipeline/Refresh graphs related health services.	
GRPUSR	The Graph User Group. Users mapped to this group have access to all the menu items in the OFS MMG Application related to graph and Pipeline/Refresh graphs related health services.	

### Note:

Admin link in the application home page is accessible only if the below seeded groups are mapped to the user:

- IDNTYADMN
- IDNTYAUTH



### 6.4 Model Techniques/ Model Library

Following are the prerequisites to use the model techniques from the older version when you upgrade to 8.1.2.4.0 version.



MMG\_TECHNIQUE\_MASTER table had no V\_WORKSPACE\_ID column, which has been added in this release and then the primary key is updated to (V\_TECHNIQUE\_ID, V\_WORKSPACE\_ID).

To use the existing Techniques in the upgraded setup, perform the below:

The V\_WORKSPACE\_ID column will have the value set as ##WORKSPACE## for the existing records by default. If the same records has to be used in the latest version of MMG, you must update the table MMG\_TECHNIQUE\_MASTER with relevant Workspace ID.

### 6.5 .PEM file creation for Model Service

You must create **server.pem** file from **server.keystore** in the same path where server.keystore file is present using the below command:

```
openssl pkcs12 -in <Path_To_server.keystore> -out <Path_To_Server.pem> -nodes
For Example:
openssl pkcs12 -in
/scratch/users/ofsaa/dev_home/config/server.keystore -out
/scratch/users/ofsaa/dev_home/config/server.pem -nodes
```

# 6.6 Access and Permissioning Management

MMG uses a realm based on unique authentication and authorization for its users. Realm indicates the functional grouping of Database Schemas and roles that must be secured for an application. Realms protect data from access through system privileges and do not provide its owner or participants additional privileges. Realm based authorization establishes a set of database accounts and roles that can manage, or access objects protected in realms and are authorized to use its system privileges. It provides a runtime mechanism to check logically if a user's command can access objects specified in the command and proceed with its execution. Realms (AAIRealm, SAMLRealm) are selected based on the Identity Provider (IDP) during the installation. For more information, see the OFS MMG Installation Guide. After you select the realms, you can register a set of schema objects or roles (secured objects) for realm protection and authorize a set of users or roles to access the secured objects. The MMG Application is accessed using the following realms that you have selected during the installation of the MMG Application:

AAIRealm: This uses Oracle Financial Services Analytical Applications Infrastructure
(OFSAAI) Identity Management System for User Authentication. Users, Roles, and Groups
are created in the OFSAAI. The OFSAAI facilitates System Administrators to provide
access, monitor, and administer users along with the infrastructure metadata operations.

The required permissions to roles or groups are authorized in the MMG applications using the Permission feature.

SAMLRealm: The SAMLRealm uses an identity provider (IDP) Identity Management
System for User Authentication. Security Assertion Markup Language (SAML) is an open
standard that allows Identity Providers (IDP) to pass authorization credentials to Service
Providers (SP). IDP acts as the Single Sign-On (SSO) service. Users and Roles are
created in the IDP. The required permissions to Users and Roles are authorized in the
MMG Applications using the Permission feature.




Figure 6-2 Authentication and Authorization process in MMG

### 6.6.1 Access MMG using AAI Realm

This section provides information on creating users who can access MMG using the AAI Realm method of authentication through Oracle Financial Services Analytical Applications Infrastructure (OFSAAI). The users with SYSADMN and SYSAUTH roles in OFSAAI can create and authorize users, respectively.

Identity Management in the OFSAAI facilitates System Administrators to provide access, monitor, and administer users along with the infrastructure metadata operations. The Security Management System (SMS) component is incorporated with Password Encryption, Single Logon, Role and DataBased Security, Access Control, and Audit Trail feature to provide a highly flexible security envelope. Administrators can create, map, and authorize users defining a security framework that can restrict access to the data and meta-data in the warehouse, based on a fine-grained access control mechanism. These activities are done at the initial stage and then on a required basis. For more information on creating and authorizing users in OFSAAI, see the Oracle Financial Services Analytical Applications Infrastructure User Guide. The following table describes the ready-to-use roles and the corresponding user groups who can access MMG using AAIRealm.



Only in AAIRealm, users are mapped to user groups. The default permissions mapped to these users and user groups are available in the Permission section. However, these permissions can be added or modified.



### 6.6.1.1 Prerequisites

1. Configuring WebLogic for REST Services Authorization.

To enable REST API authorization by OFSAA in WebLogic server, perform the following steps:

- a. Open the config.xml file located in the domain where OFSAA is deployed that is: <domain home>/config/config.xml.
- b. Add the following in the security-configuration tag: <enforce-valid-basic-auth-credentials>false</enforce-valid-basic-authcredentials>.
- In OFSAA Application, Allow user to log in from multiple machines option should be enabled.

#### **REST API Calls**

There is need for Model Scripts to access input parameters passed by REST API Calls:

- **a.** The REST API optional parameters are mapped to runtime parameters , this mapping needs to be documented. It is not apparent from runtime parameter section.
- b. The mapped simple params can be accessed with script segment like below, but it is not supporting base64 encoding and/or json hp = '\${hyperparams}' cnf = '\${conf}' 3.the enhancement against json is retracted as we can do base64 encrypted value passing

```
"RUN ID": 2,
"RUN CODE": 200440,
"PARAM SET": {
"CALL TYPE": "PASS THROUGH RATE",
"BOLLINGER PERIOD": 3,
"BOLLINGER COEFFICIENT": 1,
"DATA SNAP FREQ": 1,
"DATA SNAP FREQ MULTIPLIER": "D",
"MISSING VALUE TECH": "inpol",
"MISSING THRESHOLD_PERCENTAGE": 30,
"START DATE": 20230131,
"END DATE": 20230431,
"EXECUTED BY": "TESTUSR",
"REFRESH DATA": "Yes"
},
"SLICE": [
"SEQ": 1,
"LOGICAL PARTITION NAME": "DEFAULT",
"TABLE NAME": "FSI I NM MLSTAGE"
```

```
],
"OUTPUT_DATA": {
"PLOTS_TAB": "FSI_O_NM_PLOTS",
"MILESTONE_TAB": "FSI_O_NM_MILESTONE",
"SCORE_TAB": "FSI_O_NM_MODEL"
}
```

For example: base64 encryption

### 6.6.2 Access MMG using SAMLRealm

This section provides information on managing users who can access MMG with Identity Provider (IdP or IDP). An Identity Provider (IdP) is a service that stores and verifies user identity. IdPs are cloud-hosted services, and they often work with single sign-on (SSO) providers to authenticate users. An Identity Provider stores and manages users' digital identities. An IdP checks user identities via username-password combinations and other factors, or it may simply provide a list of user identities that another Service Provider (like an SSO) checks. The following are the ready-to-use roles that can access MMG using SAMLRealm. To integrate MMG with IdP as the SSO Provider, follow these steps:

1. Create the following roles in the IDP System:

#### For MMG:

- IDNTYADMN
- IDNTYAUTH
- MDLREV
- MDLAPPR
- MDLBATCHUSR
- WKSPADMIN
- MDLUSR
- DSUSRGRP
- DSREDACTGRP
- GRPADMIN
- GRPUSR



IDNTYADMN role is required only if you need the Admin Access.

Map the user groups to the respective user based on the user roles. The default permissions mapped to these users are available in the Permission section. However, these permissions can be added or modified.





It is recommended to use AAIRealm or SAMLRealm.

### 6.7 AAI User Provisioning SQL Scripts Generator Utility

This utility allows you to use AAI for authN in MMG. Identity administrators can create new user groups or roles, perform appropriate roles, usergroup and domain mapping, and so on.

This is provided as a SQL generator utility. This SQL scripts is executed in the AAI's configuration schema to create the required metadata.

Ensure that you run this script multiple times against each username. Additionally, generate the merge scripts accordingly.

Execute the following command from <mmq-home>/bin folder

./userprovisioning-script-generator.sh <user> <comma separated listof user groups or ALL> <infodom> <segment>

#### Sample Commands:


- ./userprovisioning-script-generator.sh SCRIPTUSER ALL OFSAAAIINFO EMFLD
- ./userprovisioning-script-generator.sh SCRIPTUSER MDLREV,MDLUSR,IDENTITY\_ADMIN
  OFSAAAIINFO EMFLD

### 6.8 IDCS Server Configuration

To perform IDCS Server Configuration, follow these steps:

- 1. Navigate to SAML IDCS Admin.
- 2. Navigate to Details section and add the app details in IDCS Server as shown below:

Figure 6-3 IDCS Server



Navigate to SSO Configuration section and add the app details in IDCS Server as shown below:




Figure 6-4 SSO Configuration section





#### Figure 6-5 IDCS Server





The following attributes such as username, email, and ofs\_mapped\_groups needs to configured as shown in the above image.


The user has to upload the certificate.

The user can generate the certificate by following these steps:

- Create .cer and .pem file from the below command.
- Upload the same .cer to the idcs Signing certificate option as well: openssl req -x509 -nodes -days 365 -newkey rsa:2048 -keyout sp-privatekey.pem -out sp-certificate.cer
- 4. Navigate to Group section and Configure User Groups.



Figure 6-6 Configure User Groups in Group section



7

# **Upgrade Installation**

This chapter describes the Upgrade Installation.

## 7.1 Upgrading to 8.1.3.2.0

To update an already installed MMG Application, perform the following steps:

#### Prerequisite:

- A valid working setup should be available before performing the upgrade.
- Use the MMG Config Schema, MMG Graph Schema, and MMG Datastudio Schema, from the existing version, along with the wallet configurations.
- Shutdown all the services of the existing installation using shutdown.sh.
- Backup the existing MMG Installation to a backup folder.

#### Upgrade:

Follow steps mentioned in the Installation section.



Compare and copy the placeholder values from the existing installed MMG.config.sh to the new one mentioned in the Installation section.

# Update Utility to Reconfigure Installation Parameters

If you need to update any of the existing configuration related values, perform the following steps:



This Utility is applicable from 8.1.2.3.0 version onwards.

#### **Procedure:**

- 1. Shut down all the services using shutdown.sh command.
- Reconfigure the config.sh file with the required changes.
- 3. Execute the command install.sh -u from the following path: <mmg installation path>/OFS MMG/bin

A successful update message as follows:

4. Start all the MMG services using startup.sh command.

9

# Cloning the MMG Instance

There is a consistent requirement for a faster and effective approach of replicating an existing MMG Instance for further project developments. The approach is to set up the MMG Instances that are exact copies of the current MMG Instance.

## 9.1 Copying the Directories

The Installation Directory structure in the base environment has to be replicated in the clone environment.

 Copy the MMG base directory (OFS\_MMG, by default) in the base environment with all of its contents to the clone environment.

The base directory in the clone environment will have the following folders upon copying:

- mmg-ui
- mmg-studio
- mmg-service
- mmg-schema-creator
- mmg-pipeline
- lib
- bin
- conf



You need to copy LOG and FTPSHARE directories to the cloned environment.

# 9.2 Copying the Database Schemas

To copy the Database Schemas:

Create a copy each of the MMG Config Schema and the Data Studio Schema.
 You may use Oracle Data Pump Export/Import or the Database Copy feature of Oracle
 SQL Developer. For more details, see Database Copy using Oracle SQL Developer.

The Cloned Schemas can be created either in the same database instance or in a different one.

Similarly, create copies of Workspace Schemas or other Data Source Schemas as required.

### 9.3 Configuring Password Store with Oracle Wallet

To configure the password store with Oracle Wallet:

 Setup an Oracle wallet in the clone environment. For more details, see Setup Password Stores with Oracle Wallet.



It is recommended to use the same wallet aliases used in the base environment.

#### Updating the WALLET\_LOCATION and TNS\_ADMIN\_PATH

Update the WALLET\_LOCATION and TNS\_ADMIN\_PATH values in config.sh file present in the following path:  $OFS\_MMG/bin$  with configured corresponding values of the cloned environment.

### 9.4 Updating the Host Details

Update the HOST and PORT values in config.sh file present in the following path: OFS MMG/bin with configured corresponding values of the cloned environment.



It is recommended to use the same ports and context used in the base environment.

Replace the placeholders and update the host name in the MMG Config schema using the following command:

```
update NEXTGENEMF_CONFIG set V_VALUE =
'http(s)://##HOST_NAME##:##BE_PORT##/##CONTEXT##' where V_NAME in ( '
BASE_URL', 'EMFSTUDIO_SERVICE_URL')
/

update NEXTGENEMF_CONFIG set V_VALUE =
'http(s)://##HOST_NAME##:7008/##CONTEXT##' where V_NAME = 'DATASTUDIO_URL'
/

update AAICL_SS_BATCH_URL set V_URL =
'http(s)://##HOST_NAME##:##BE_PORT##/##CONTEXT##' whereV_URL_NAME in
('CS_SERVICE_URL', 'MMG_SERVICE_URL', 'WORKSPACE_URL')
/
```

### 9.5 Update LOG\_HOME and FTPSHARE

Update the LOG\_HOME and FTPSHARE values in config.sh file present in the following path:

OFS MMG/bin with configured corresponding values of the cloned environment.

Replace the ##LOG\_HOME## and ##FTPSHARE## placeholders and update the LOG\_HOME and FTPSHARE values in the MMG Config Schema using the following command:

```
update NEXTGENEMF_CONFIG set V_VALUE = '##LOG_HOME##' where V_NAME = 'LOG_HOME'
/
update NEXTGENEMF_CONFIG set V_VALUE = '##FTPSHARE##' where V_NAME = 'FTPSHARE'
/
```

## 9.6 Setting up the SSL Keystore

To run on HTTPS, you must create a Keystore for MMG Application. For more details, see the SSL Keystore in the Configure the config.sh file.

Update the Keystore path, Password and Storetype values in config.sh file present in the following path: OFS\_MMG/bin with configured corresponding values of the cloned environment.

### 9.7 Updating Wallet Aliases for Oracle Schemas



It is recommended to use the same wallet aliases used in the base environment.

In case if the same wallet aliases cannot be used, perform the following:

- Update the MMG Config Schema Wallet Alias values in config.sh file present in the following path: OFS\_MMG/bin with configured corresponding values of the cloned environment.
- 2. Replace the placeholders and update the wallet alias for Workspace Schemas or other Oracle datasources using the following command:

```
update MMG_DB_MASTER set V_PROPERTY_VALUE = \##WALLET_ALIAS##' where
V_PROPERTY_NAME = \WALLET_ALIAS' and V_DB_NAME = \##DATASOURCE NAME##'
//
```

# 9.8 Updating Context and Ports



It is recommended to use the same context and ports used in the base environment.

In case if the same context and ports aliases cannot be used, perform the following:

- Update the references of context path and port values in config.sh file present in the following path: OFS\_MMG/bin with configured corresponding values of the cloned environment.
- 2. Replace the ##CONTEXT## and ##BE\_PORT## placeholders.

For more details, see Updating the Host Details.



For MMG authentication, port access should be enabled for MMG ports to access OFSAA ports.

### 9.9 Starting MMG Services

Post updating all the required parameters in the new config.sh.file, start the services by using the following command: ./install.sh -u

### 9.10 Cloning the Environment

We will not have to manually update the entries or Database details/service URLs for most of the tables.

This can be done in two parts:

#### Part I

- Execute a utility that updates most of the entries in config tables and configuration/ properties in the file system.
- In the DR setup, after cloning, configure the <base>/mmg-home/bin/config.sh with new values of:
  - WALLET LOCATION (pointing to DR db)
  - TNS\_ADMIN\_PATH (pointing to DR db)
  - FTPSHARE (Ensure contents of ftpshare are also synced up between Prod and DR instances).



All other values, as applicable (If they differ between Prod and DR environments).

Execute the update script: <base>/mmq-home/bin/install.sh -u



This is not going to install again. Instead this will just update the configuration values in config tables and files.

#### Part II

For rest of the tables, additionally we can execute sql to update the following:

Replace the PARAMVALUE for PARAMNAME = ¿ER\_SERVICE\_URL;

 $\label{loc_pgx_m_config} $$ $$ $ \mathbb{V}_{RAPH_PATH}$: Replace this if it is not null; as this is applicable only for IN-Memory graphs. $$ | MMG_MENU|V_MENU_URL| For example:$ 

Table 9-1 Param Value for Param Name with Service URL

V_MENU_CODE	V_MENU_NAME	V_MENU_URL
C003	Match Rules	https://ofss- mum-1750.snbomprshared1.gbuc dsint02bom.oraclevcn.com:7061/f cc/matchrulesetsummary.jsp
C004	Merge Rules	https://ofss- mum-1750.snbomprshared1.gbuc dsint02bom.oraclevcn.com:7061/f cc/mergerulesetsummary.jsp
C005	Data Survival	https://ofss- mum-1750.snbomprshared1.gbuc dsint02bom.oraclevcn.com:7061/f cc/datasurvivalsummary.jsp
C001	Manual Decisioning	https://ofss- mum-1750.snbomprshared1.gbuc dsint02bom.oraclevcn.com:7061/f cc/manualdecisioning.jsp
C006	Merge and Split Global Entities	https://ofss- mum-1750.snbomprshared1.gbuc dsint02bom.oraclevcn.com:7061/f cc/mergeandsplit.jsp



10

# Frequently Asked Questions (FAQs) and Error Dictionary

This section consists of resolution to the Frequently Asked Questions and Error Codes noticed during the installation.

#### Topics:

### 10.1 Frequently Asked Questions

You can refer to the Frequently Asked Questions, which is developed with the interest to help you resolve some of the installation and configuration issues. This intends to share the knowledge of problem resolution to a few of the known issues. This is not an official support document and just attempts to share the knowledge of problem resolution to a few of the known issues.

### 10.1.1 Frequently Asked Questions

- Why does my console show an unsuccessful message during wallet creation?
   Please check if you have run the following commands correctly. For more information on wallet creation, see Setup Password Stores with Oracle Wallet.
  - a. mkstore -wrl <wallet\_location> -create //creates a wallet in the specified location.
  - b. mkstore -wrl <wallet\_location> -createCredential <alias-name> <database-user-name> //creates an alias in the Studio Schema.
  - c. mkstore -wrl <wallet\_location> -createCredential <alias-name> <databaseuser-name> //creates an alias in the Atomic Schema.
  - **d.** mkstore -wrl <wallet\_location> -createCredential <alias-name> <database-user-name> //creates an alias in the configuration schema.

If your issue is still not resolved, contact My Oracle Support (MOS).

Where can I find my created wallet? Your wallet will be in the directory you have set as your wallet location.

If your issue is still not resolved, contact My Oracle Support (MOS).

3. When should I create a Database link, and if yes, how do I do it? Create a Database link to connect the Atomic and Configuration Database Schemas to the Studio Database Schema if the databases are different. You must create the link in the Studio Database.

In the following example, a link has been created from the Configuration Schema to the Atomic Schema by running the following script:

```
create public database link <studio database link> connect to <Config Schema>
identified by password using ' (DESCRIPTION = ADDRESS_LIST = (ADDRESS =
    (PROTOCOL = TCP) (HOST =<host name> (PORT = <port number>)) (CONNECT_DATA =
    (SERVICE NAME = <service name>))) ';
```

```
Config Schema : <Config Schema>/password ' (DESCRIPTION = ADDRESS_LIST =
  (ADDRESS = (PROTOCOL = TCP) (HOST =<host name> (PORT = <port number>))
  (CONNECT DATA = (SERVICE NAME = <service name>))) ';
```

After running the script, run the FCDM Connector and ICIJ Connector jobs.

- 4. Why does my installed studio setup not have any notebooks? Some default notebooks are ready to use when you install Compliance Studio. If you do not see any notebooks when you log in to the application, you may not be assigned any roles. Check the <COMPLIANCE\_STUDIO\_INSTALLATION\_PATH>/deployed/logs directory to see if you have been assigned any roles, and if not, contact your Administrator. If your issue is still not resolved, contact My Oracle Support (MOS).
- 5. What can I do if the Schema Creation fails? If the Atomic Schema creation fails, login to the BD and ECM Atomic Schemas and run the following query: select \* from fcc\_orahive\_datatypemapping; The fcc\_orahive\_datatypemapping table must not have duplicate data types. If the Studio schema creation fails, login as a Studio user and run the following query: select \* from fcc\_datastudio\_schemaobjects Run the following query to replace all Y values with ": update fcc\_datastudio\_schemaobjects set SCHEMA\_OBJ\_GENERATED=" After the schema creation is successful, the value of the SCHEMA\_OBJ\_GENERATED attribute changes to Y. You can also check for errors in the application log file in the <COMPLIANCE\_STUDIO\_INSTALLATION\_PATH>/deployed/logs directory. If your issue is still not resolved, contact My Oracle Support (MOS).
- 6. What can I do if the Import\_training\_model batch execution fails? Batch Execution Status always displays success in case of success or failure.

You can also check for errors in the application log file in the <COMPLIANCE\_STUDIO\_INSTALLATION\_PATH>/deployed/logs directory. You can fix the failure according to the log details and run the same batch again.

- 7. Why is the sqoop job not successful? The Sqoop job may fail if some of the applicable values are null or if the service name or SID value is not provided. Do one of the following:
  - Check if there are any null values for the applicable configurations in the config.sh and FCC\_DATASTUDIO\_CONFIG tables. If there are any null values, add the required value.
  - Check for any errors in the application log file in the <COMPLIANCE\_STUDIO\_INSTALLATION\_PATH>/deployed/logs directory. If your issue is still not resolved, contact My Oracle Support (MOS).
- 8. Why am I getting the following error when I run the sgoop job:

```
Error: Could not find or load main class
com.oracle.ofss.fccm.studio.batchclient.client.BatchExecute
```

Set the FIC\_DB\_HOME path in the <COMPLIANCE\_STUDIO\_INSTALLATION\_PATH>/deployed/ficdb directory.

You can also check for any errors in the application log file in the <COMPLIANCE STUDIO INSTALLATION PATH>/deployed/logs directory.

- 9. 11. Why is the PGX server is not starting even though the graph service is up and running? Grant execution rights to the PGX folder to start the PGX server.
- 10. Why is the PGX Server not starting? The PGX server starts only after the FCDM tables are created after the FCDM Connector Job is run. Check if all FCDM tables are created and then start the PGX Server. You can also check for any errors in the application log file in the

<COMPLIANCE\_STUDIO\_INSTALLATION\_PATH>/deployed/logs directory. If your issue is still not resolved, contact My Oracle Support (MOS).

#### 11. Why is the ICIJ Connector job failing?

This can happen because of a missing csv file path in the FCC\_STUDIO\_ETL\_FILES table. Add the CSV file path. You can also check for any errors in the application log file in the <COMPLIANCE\_STUDIO\_INSTALLATION\_PATH>/deployed/logs directory. If your issue is still not resolved, contact My Oracle Support (MOS).

12. What should I do if there is a below Error while selecting edges in manual Decision UI? java.lang.IllegalStateException: Unable to create PgxSessionWrapperjava.lang.IllegalStateException: Unable to create PgxSessionWrapper at oracle.datastudio.interpreter.pgx.CombinedPgxDriver.getOrCreateSession(Combine dPgxDriver.java:147) at oracle.pqx.graphviz.driver.PqxDriver.getGraph(PqxDriver.java:334) at oracle.pgx.graphviz.library.QueryEnhancer.createEnhancer(QueryEnhancer.java:22 3) at oracle.pgx.graphviz.library.QueryEnhancer.createEnhancer(QueryEnhancer.java:20 9) at oracle.pgx.graphviz.library.QueryEnhancer.query(QueryEnhancer.java:150) at oracle.pgx.graphviz.library.QueryEnhancer.execute(QueryEnhancer.java:136) oracle.pgx.graphviz.interpreter.PgqlInterpreter.interpret (PgqlInterpreter.java :131) at oracle.datastudio.interpreter.pgx.PgxInterpreter.interpret (PgxInterpreter.java :120) at org.apache.zeppelin.interpreter.LazyOpenInterpreter.interpret (LazyOpenInterpre ter.java:103) at org.apache.zeppelin.interpreter.remote.RemoteInterpreterServer\$InterpretJob.jo bRun (RemoteInterpreterServer.java:632) at org.apache.zeppelin.scheduler.Job.run(Job.java:188) at org.apache.zeppelin.scheduler.FIFOScheduler\$1.run(FIFOScheduler.java:140) at java.util.concurrent.Executors\$RunnableAdapter.call(Executors.java:515) at java.base/java.util.concurrent.FutureTask.run(FutureTask.java:264) at java.base/ java.util.concurrent.ScheduledThreadPoolExecutor\$ScheduledFutureTask.run(Sched uledThreadPoolExecutor.java:304) at java.base/ java.util.concurrent.ThreadPoolExecutor.runWorker(ThreadPoolExecutor.java:1128 ) at java.base/ java.util.concurrent.ThreadPoolExecutor\$Worker.run(ThreadPoolExecutor.java:628 ) at java.base/java.lang.Thread.run(Thread.java:834)Caused by: java.util.concurrent.ExecutionException: oracle.pgx.common.auth.AuthorizationException: PgxUser(FCCMDSADMIN) does not own session 6007f00a-8305-4576-9a56-9fa0f061586f or the session does not exist code: PGX-ERROR-CQAZPV67UM4H at java.base/ java.util.concurrent.CompletableFuture.reportGet(CompletableFuture.java:395) at java.base/ java.util.concurrent.CompletableFuture.get(CompletableFuture.java:1999) at oracle.pgx.api.PgxFuture.get(PgxFuture.java:99) at oracle.pgx.api.ServerInstance.getSession(ServerInstance.java:670) oracle.datastudio.interpreter.pgx.CombinedPgxDriver.getOrCreateSession(Combine dPgxDriver.java:145) ... 17 moreCaused by: oracle.pgx.common.auth.AuthorizationException: PgxUser(FCCMDSADMIN) does not own session 6007f00a-8305-4576-9a56-9fa0f061586f or the session does not exist code: PGX-ERROR-CQAZPV67UM4H at

oracle.pgx.common.marshalers.ExceptionMarshaler.toUnserializedException(Except

```
ionMarshaler.java:107) at
oracle.pqx.common.marshalers.ExceptionMarshaler.unmarshal(ExceptionMarshaler.j
ava:123) at
oracle.pgx.client.RemoteUtils.parseExceptionalResponse(RemoteUtils.java:130)
oracle.pgx.client.HttpRequestExecutor.executeRequest(HttpRequestExecutor.java:
198) at
oracle.pgx.client.HttpRequestExecutor.get(HttpRequestExecutor.java:165) at
oracle.pgx.client.RemoteControlImpl$10.request(RemoteControlImpl.java:313) at
oracle.pqx.client.RemoteControlImpl$ControlRequest.request(RemoteControlImpl.j
ava:119) at
oracle.pgx.client.RemoteControlImpl$ControlRequest.request(RemoteControlImpl.j
ava:110) at
oracle.pgx.client.AbstractAsyncRequest.execute(AbstractAsyncRequest.java:47)
at oracle.pgx.client.RemoteControlImpl.request(RemoteControlImpl.java:107) at
oracle.pgx.client.RemoteControlImpl.getSessionInfo(RemoteControlImpl.java:296)
oracle.pgx.api.ServerInstance.lambda$getSessionInfoAsync$14(ServerInstance.jav
a:490) at java.base/
java.util.concurrent.CompletableFuture.uniComposeStage(CompletableFuture.java:
1106) at java.base/
java.util.concurrent.CompletableFuture.thenCompose(CompletableFuture.java:2235
) at oracle.pgx.api.PgxFuture.thenCompose(PgxFuture.java:158)
```

Then, perform the below steps as a workaround -

Export the "Manual Decision" Notebook

Add the link parameter just below Description

for Ex - "link": "manualDecision",


#### Figure 10-1 Manual Decision

```
[ {
    "name" : "manual Decision",
    "description" : null,
    "link": "manualDecision",
    "tags" : null,
    "version" : "5",
    "layout" : "zeppelin",
    "type" : "Default",
    "readOnly" : false,
```

Truncate the table "fcc\_er\_paragraph\_manual" in Studio Schema. Import the modified notebook again.


- 13. Data Extraction is truncated to default limit (Approx 197 records) in Python paragraph widget output in MMG. Setting the ZEPPELIN\_LIMIT\_INTERPETER\_OUTPUT in Python Interpreter
  - a. From UI: Using Wizard screen
     Go to Interpreters screen in MMG-Studio from Datastudio Options tab.

Figure 10-2 Datastudio Options tab




**b.** Once on the interpreters option screen select the Python Interpreter for which we want to configure the zeppelin.limit.interpreter.output.

Figure 10-3 Interpreter screen



Select python from the LHS options.


Figure 10-4 Python Interpreter






d. Now scroll down in the RHS side and click on the oracle.datastudio.python.DsPythonInterpreter under Interpreter Client Configurations it will open a popup.

Figure 10-5 Interpreter Client Configurations



e. In the popup scroll down and click on + Properties under Properties as shown:


Figure 10-6 Properties screen



f. Another popup will open fill the options as shown and set the default value according to your needs if you are not able to see the Create and Cancel button, click on the part of the popup pointed by red arrow. The default value for zeppelin.interpreter.output.limit if not set is 102400 (in bytes).



Figure 10-7 Popup box




#### Note:

Increasing the default option from 102400 to some bigger value will slow down the rendering of outputs of python paragraphs.


- g. Once filled click on Create (you will see zeppelin.interpreter.output.limit under the Properties section), then click on **Confirm** (if you are not able to see the Confirm button on the UI, either click on the same shaded area on popup as highlighted in above image or zoom out in UI of browser) and then click on Update in the lower right side of the screen.
- h. After following all the above steps, restart the MMG-Studio for changes to reflect.
- a. Using JSON screen
  - i. Follow the steps i, ii and iii from above, then click on the following icon on UI pointed by red arrow and following json config view will open.

Figure 10-8 JSON Config View




ii. Scroll down under interpreterClientConfigs with className oracle.datastudio.python.DsPythonInterpreter you will find following properties section with bunch of zeppelin configurations.

Figure 10-9 Interpreter Client Config



iii. After the last entry in properties add the zeppelin.interpreter.output.limit also as shown in the following image:

Figure 10-10 Properties screen



- iv. After doing the change the Update button will get enabled in the bottom right corner click on it, you will get a message as "python interpreter updated".
- v. Now restart the MMG-Studio service for changes to reflect.
- b. From filesystem: (Datastudio version 23.4.x onwards)
  - i. Go to the Python Interpreter option as pointed out in From UI using wizard screen option above, if you have already ran the MMG services before you will see the python interpreter listed there. Delete it, if you are running the MMG Application for the first time on a fresh schema then you do not need to do this step.
  - ii. After deleting the Python Interpreter or if start has not been done yet, go to filesystem inside mmg-home/mmg-studio/server/builtin/interpreters, open python.json in a text editor.
  - iii. Scroll down under interpreter ClientConfigs with className oracle.datastudio.python.DsPythonInterpreter you will find following properties section with bunch of Zeppelin configurations. After the last entry in properties add the Zeppelin Interpreter.output.limit also as shown in step iii) of 1) From UI b) using JSON screen (last image of From UI way). Save the python.json with the desired default value and the changes done.

iv. Now restart/start the MMG-Studio for your changes to reflect.



If you have configured the python environment for MMG-Studio (basically you have installed pandas and numpy which are subset of libraries required by MMG as pre-req), you can run the below script on python paragraph.

%python

import pandas as pd

import numpy as np


# Create 1000 rows of random data for 20 columns

data = np.random.randn(1000, 20)

- # Create column names columns = [f"Column\_{i+1}" for i in range(20)]
- # Create DataFrame df = pd.DataFrame(data, columns=columns)
- # Display the DataFrame
- z.show(df)

Output in table view

Figure 10-11 Output in table view



You can see the ZEPPELIN\_INTERPRETER\_OUTPUT\_LIMIT value as warning if the table content is more than the set default value for zeppelin.interpreter.output.limit and accordingly you can modify the default value for same.

- 14. What should I do when the result set is truncated if the size goes above '102400' bytes? Perform the following steps:
  - a. Login to Compliance Studio.
  - b. Navigate to interpreter zeppelin.interpreter.output.limit.

Figure 10-12 Zeppelin Interpreter



- c. Set the value to the required size.
- d. Restart the Studio Application.
- 15. What should I do if there is a below KubernetesClientException in load-to-elasticsearch.log, matching-service.log files after Compliance Studio installation? configServicePropertySourceLocator - Could not locate PropertySource: I/O error on GET request for "http://localhost:8888/<Service Name>/default": Connection refused (Connection refused); nested exception is java.net.ConnectException: Connection refused (Connection refused) onfigServicePropertySourceLocator - Could not locate PropertySource: I/O error on GET request for "http://localhost:8888/<Service Name>/default": Connection refused (Connection refused); nested exception is java.net.ConnectException: Connection refused (Connection refused) 20:04:55.686 [ main] WARN .cloud.kubernetes.config.ConfigMapPropertySource - Can't read configMap with name: [<Service Name>] in namespace:[null]. Ignoring.io.fabric8.kubernetes.client.KubernetesClientException: Operation: [get] for kind: [ConfigMap] with name: [<Service Name>] in namespace: [null] failed. at io.fabric8.kubernetes.client.KubernetesClientException.launderThrowable(Kubern etesClientException.java:64) ~[kubernetes-client-4.4.1.jar!/:?] at io.fabric8.kubernetes.client.KubernetesClientException.launderThrowable(Kubern etesClientException.java:72) ~[kubernetes-client-4.4.1.jar!/:?] at io.fabric8.kubernetes.client.dsl.base.BaseOperation.getMandatory(BaseOperation .java:229) ~[kubernetes-client-4.4.1.jar!/:?] at io.fabric8.kubernetes.client.dsl.base.BaseOperation.get(BaseOperation.java:162 ) ~[kubernetes-client-4.4.1.jar!/:?] at org.springframework.cloud.kubernetes.config.ConfigMapPropertySource.getData(Co nfigMapPropertySource.java:96) ~[spring-cloud-kubernetesconfig-1.1.3.RELEASE.jar!/:1.1.3.

You can ignore the error when the following message is displayed at the end of the log; if you do not see this message, contact My Oracle Support (MOS) and provide the applicable error code and log:

```
13:52:57.698 [main] INFO org.apache.catalina.core.StandardService - Starting service [Tomcat] 13:52:57.699 [ main] INFO org.apache.catalina.core.StandardEngine - Starting Servlet engine: [Apache Tomcat/9.0.43]
```

What happens if a new sandbox workspace is created?
When a new sandbox workspace is created, the folders of the older workspace are by default being copied into the new workspace. Here, folder means the Model Objectives. The Model Objectives are global objects and will be visible across the workspaces. However, the models created within those objectives will be private. This has been done purposely as you expect multiple modelers working on the common objective in their private workspaces.

- 17. Not able to access any models in the copied folders in the new workspace the folders are being copied as empty folders?
  - Yes, you should not be able to access other workspace's private models. Also, as long as other users are working on the objective and have their models in there, you will not be able to delete the objectives.
- 18. What should you do when UI pages does not load due to less network speed? The default time to load all the modules of OJET/REDWOOD page is 1 minute. Reload the page to view the UI pages.
- **19.** What are the Workspace parameters used in MMG Python Scripts? The following parameters are used:
  - workspace.list\_workspaces(): Used to fetch a list of all workspaces. This list is
    populated in the dropdown menu of datastudio.
  - workspace.check\_aif(): A method used to check if AIF is enabled or not
  - workspace.attach\_workspace("SANDBOX123"): A method used to set workspace
  - workspace.get\_workspace(): Used to fetch the selected workspace (for example, SB1)
  - get\_mmg\_studio\_service\_url(): Used to fetch the base URL (for example, http://whf999yyy:0000/mmg)
  - get\_user(): Used to fetch current user (for example, mmguser)
- 20. How to take connections for Data access?

You need access to the data to work on it. For the workspace, there are some underlying Data Schemas. You can also create a workspace that allows to select multiple underlying Data Schemas. You can use or remove multiple Data Schemas like multi combo box, where 1, 2, 3, and 4, 5 are schemas underlying. When you work with the models, you can access the notebook to fetch data for all these Data Schemas and create some data frames out of it. That can be used for model reading or other purposes.

This happens in workspace of the sandbox where you are building a Notebook. The same Notebooks gets promoted to production workspace. Therefore, the workspace production has its own set of underlying Data Schemas. When you build the model with getting connection for the underlying Schema 1 and 2, and getting the data and building, it makes rules work and will not be affected if the same Notebooks gets promoted to production or deployment is cloned.

Therefore, the Notebook needs to run which should not be fetching this data because it will be working on any 1 and 2 Schemas.

To avoid this issue, you can use connection feature to connect with a schema. This is a wrapper function where you can specify which workspace you are connecting to.

You can enter the workspace details to get the connection and that starts fetching the data.

When you create the Notebook to production, a script runs to not to connect the workspace. This also uses overloaded methods. This method tells how to get the connection. Simple get connection gets the primary connection as first Data Schema which you are using without any overload.

The second connection gets an ID as the name the Data Source which you are using and for the current one will passes as get connection 1.

In the sandbox, this script looks for 1 and it creates a connection and moves to production.

It will again look for an equivalent 1 and tries to get a connection.

Therefore, whatever you select first, becomes the first Data Schema, Second Schema, Third Schema, therefore, Primary, Secondary, Tertiary and so on. You can also pass the

number while getting the connection to get the first primary Data Schema as a secondary Data Schema. Therefore, when it runs in sandbox, it gets the Secondary Schema. When it runs in the production, it fetches a Secondary Data Schema of production.

- 21. What are parameters to establish the Connection for data access? The following section lists the connection details such as the Data Sources and so on: workspace.get connection(): fetches connection object for the Primary Data Source of the workspace. This is equivalent to executing workspace.get connection(1). workspace.get connection('id'): fetches connection for the Data Source by name. For example, workspace.getconnection ('ws\_data\_1') - here 'ws\_data\_1' is one of the underlying Data Source for the workspace. workspace.get connection(n): fetches connection for the Data Source by order. For example, workspace.getconnection(2) - this will fetch connection for the Secondary Data Source. The following section lists the workspace details: After a workspace is attached, we can list Data Sources related to that using: workspace.list datasources(): will list Data Sources related to attached workspace with default order 1 For example, {'Data Source': [{'name': 'newdatasource1', 'order': '1'}]} workspace.list datasources("SB1"): will list Data Sources related to SB1 workspace with default order 1 For example, {'Data Source': [{'name': 'ds1', 'order': '1'}]} workspace.list datasources("SB1", 1): will list Data Sources related to SB1 workspace with order 1 as passed in second argument For example, {'Data Source': [{'name': 'ds1', 'order': '1'}}} Note: This is applicable for Python and Python variants interpreters, and not on any other interpreters.
- 22. What should I do if the Python installation displays the following error message, " If ModuleNotFoundError: No module named '\_lzma'"? You must install xz-devel library before installing the Python. For more details, see Install MMG Python Library section.

To install, perform the following step:

\$yum install -y xz-devel.

23. What should I do to reconfigure DS Studio server port and its interpreter's default port to available ports?

#### To reconfigure port numbers:

- a. Run the command install.sh -u to change the current studio port to the desired port number in the configuration files/tables.
- b. Run the t startup.sh script of Studio at the location: OFS\_MMG/mmg-studio/bin/ and modify the line numbers 24/25 of OFS-MMG/mmg-studio/bin/startup.sh to specify the interpreter name and port number.

#### DS version 22.4.3

nohup "\$DIR"/datastudio --jdbc -1 --eventjdbc -1 --shell -1 --eventshell -1 --graalvm -1 --eventgraalvm -1 --pgx -1 --eventpgx -1 --external --port 8008 --jdbc 3011 --eventjdbc 3031 --python 3012 --eventpython 3032 --markdown 3009 --eventmarkdown 3029 --spark 3014 --eventspark 3034 &> "\$DIR"/nohup.out &

For PGX Interpreter, modify: OFS\_MMG/mmg-studio/interpreter-server/pgx-interpreter-22.4.3/bin/pgx-interpreter file "\${1:-7022}" "\${2:-7042}" values to "\${1:-3022}" "\${2:-3042}"

#### DS version 23.3.5

nohup "\$DIR"/datastudio --jdbc -1 --shell -1 --external --port 8008 --jdbc 3011 --python 3012 --markdown 3009 --spark 3014 --pgx 3022 &> "\$DIR"/nohup.out

#### For event ports in DS 23.3.5

Set the environment variables DS\_EVENT\_HANDLER\_HOST and DS\_EVENT\_HANDLER\_PORT before launching the interpreters, else, default values will be used. You can modify these ports in the startup.sh of the Studio.

#### **Example:**

export DS\_EVENT\_HANDLER\_HOST=localhost

export DS\_EVENT\_HANDLER\_PORT=3432

To change the ports configured for events in the Data Studio server, modify the following server configuration:

studio-server:

thrift-server: enabled: true

port: <desired port -defaulted to 8432>

mode: TCP
NOTE:

#### **Python Interpreter**

Beginning with Data Studio 21.4.0, 6012 is default port on which the REST server for the Python interpreter listens. To overwrite this, set the STUDIO\_INTERPRETER\_PYTHON\_INTERPRETER\_REST\_SERVER\_PORT environment variable.

#### **PGX-Python Interpreter**

Beginning with Data Studio 23.1.0, 6022 is the default port on which the REST server for the PGX-Python interpreter listens. To overwrite this, set the STUDIO\_INTERPRETER\_PGX\_PYTHON\_INTERPRETER\_REST\_SERVER\_PORT environment variable.

Modify the startup.sh to:

export

STUDIO\_INTERPRETER\_PYTHON\_INTERPRETER\_REST\_SERVER\_PORT=3038

export

STUDIO\_INTERPRETER\_PGX\_PYTHON\_INTERPRETER\_REST\_SERVER\_PORT= 3039

This configuration changes the default interpreter ports to new ports.

- c. Ports mentioned in the interpreter json files should be reconfigured. The interpreter file location is: "OFS MMG/mmg-studio/server/builtin/interpreters/<interpreter>.json" file.
- d. Execute startup.sh and check the studio/interpreter ports.
- e. Similarly, execute ./datastudio.sh –help from OFS\_MMG/mmg-studio/bin/ for all available options.

DS Studio Server port and its interpreters default port can be reconfigured to any available ports by following these steps:

- a. Change the Datastudio URL with the desired DS port. install.sh -u must be triggered to change the current studio port to 8008 in the configuration files/tables.
- b. After successful execution of install.sh. The ports can be updated by the user in the startup.sh of studio in the path OFS MMG/mmg-studio/bin/.

i. Edit line no 24/25 of OFS-MMG/mmg-studio/bin/startup.sh and change as below by specifying the interpreter name and port to be modified.

#### In DS version 22.4.3

nohup "\$DIR"/datastudio --jdbc -1 --eventjdbc -1 --shell -1 --eventshell -1 --graalvm -1 --eventgraalvm -1 --pgx -1 --eventpgx -1 --external --port 8008 --jdbc 3011 --eventjdbc 3031 --python 3012 --eventpython 3032 --markdown 3009 --eventmarkdown 3029 --spark 3014 --eventspark 3034 &> "\$DIR"/ nohup.out

#### For PGX Interpreter

Change it directly in the OFS\_MMG/mmg-studio/interpreter-server/pgx-interpreter-22.4.3/bin/pgx-interpreter file "\${1:-7022}" "\${2:-7042}" values to "\${1:-3022}" "\${2:-3042}"

#### In DS version 23.3.5

nohup "\$DIR"/datastudio --jdbc -1 --shell -1 --external --port 8008 --jdbc 3011 --python 3012 --markdown 3009 --spark 3014 --pgx 3022 &> "\$DIR"/nohup.out & For event ports in DS 23.3.5 You need to set the environment variables DS\_EVENT\_HANDLER\_HOST and DS\_EVENT\_HANDLER\_PORT before interpreters are launched. Otherwise, the default values are used. This can be mentioned in the startup.sh of studio. example:

- export DS\_EVENT\_HANDLER\_HOST=localhost
- export DS\_EVENT\_HANDLER\_PORT=3432

In order to change the port listening for events in the Data Studio server, adapt following server configuration:

- studio-server:
  - \* thrift-server:
    - \* enabled: true
    - \* port: <desired port -defaulted to 8432>
    - \* mode: TCP

#### Generic Notes

#### **Python Interpreter**

Starting from Data Studio 21.4.0, the REST server for the Python interpreter listens on port 6012 by default. One can overwrite this by setting the STUDIO\_INTERPRETER\_PYTHON\_INTERPRETER\_REST\_SERVER\_POR T environment variable.

#### **PGX-Python Interpreter**

Starting from Data Studio 23.1.0, the REST server for the PGX-Python interpreter listens on port 6022 by default. One can overwrite this by setting the

STUDIO\_INTERPRETER\_PGX\_PYTHON\_INTERPRETER\_REST\_SERVER\_PORT environment variable.

The above can be mentioned in the startup.sh of studio as export STUDIO\_INTERPRETER\_PYTHON\_INTERPRETER\_REST\_SERVER\_POR T=3038 export

STUDIO\_INTERPRETER\_PGX\_PYTHON\_INTERPRETER\_REST\_SERVER\_ PORT=3039 The above configuration will change the default interpreter ports and reconfigure to listen to the new ports. (For example: As mentioned in the below table).

- ii. Ports mentioned in the interpreter json files also needs to be reconfigured. The interpreter file locations can be found at "OFS\_MMG/mmg-studio/server/builtin/interpreters/<interpreter>.json" file.
- iii. Execute startup.sh and check the studio/interpreter ports.
- iv. Similarly you can execute as ./datastudio.sh –help from OFS\_MMG/mmgstudio/bin/ location for all the available options.

The above steps will reconfigure Server/Interpreter to these ports:

- Server/Interpreters Modified Port
- DS Studio port 8008
- Jdbc 3011
- eventidbc 3031
- python 3012
- eventpython 3032
- markdown 3009
- eventmarkdown 3029
- spark 3014
- eventspark 3034
- pgx 3022
- eventpgx 3042
- 24. Dataset issue with the latest version of pydantic package (2.18.7)

  Pydantic package (2.18.7) is incompatibile with MMG functionality. So, when you reinstall the package the uninstall and reinstall pydantic package version 1.10.13.
  - python3 -m pip uninstall pydantic
  - python3 -m pip install pydantic==1.10.13 --user
- 25. Installation of Python Packages from Local Repository In order to install the python dependencies in mmg-8.1.2.6.0.tar.gz from a local repository, use the following command.python3 -m pip install mmg-8.1.2.6.0.tar.gz.tar.gz --index-url http://artifactory.XYZ.com/artifactory/api/pypi/XYZ-py-local/simple --extra-index-url http://artifactory.XYZ.com/artifactory/api/pypi/XYZ-py-local/simple --trusted-host artifactory.XYZ.com
- 26. MMG Configuration steps for Interpreters
  - a. For JDBC

Update the below proeprty in jdbc.json underOFS\_MMG/mmg-studio/server/builtin/interpreters

"propertyName": "default.url"

"defaultValue": "<JDBC URL>"

**For example:** jdbc:oracle:thin:@ofss-mum-1033.snbomprshared1.gbucdsint02bom.oraclevcn.com:15 21/MMG19PDB

"propertyName": "default.user",



"defaultValue": "<schameusername>"

**For example:** The schema user to which you want to connect, for example: datastudio schema name,

"propertyName": "default.password",

"defaultValue": "<schemapassword>"

For example: Password of the provided schema user.

Start the jdbc interpreter by executing below command under //OFS\_MMG/mmg-studio/interpreter-server/jdbc-interpreter-22.4.3/bin ./

jdbc-interpreter

If the jdbc interpreter needs to be included in the datastudio startup script remove the below entry from /OFS MMG/mmg-studio/bin/startup.sh --jdbc -1.

#### For Spark

Configuration with Kerberos enabled remote spark cluster:

- a. Copy the configured Spark directory from hadoop cluster to <MMG Studio>/interpreter-server/spark-interpreter/extralibs. For example: spark-2.4.8-bin-hadoop2.7
- b. Copy the below files to the <MMG Studio>/interpreter-server/spark-interpreter/extralibs krb5.conf <keytabfile>.keytab
- c. To run Spark in yarn-client mode, configure the following parameters in this file OFS\_MMG/mmg-studio/server/builtin/interpreters/spark.json spark.master = yarn-client

spark.driver.bindAddress = 0.0.0.0

spark.driver.host = <host> -> Apache Spark host

#### Note:

When using the Kubernetes interpreter lifecycle, <host> can be the IP address or hostname of any node in your Kubernetes cluster. When using the Host interpreter lifecycle, <host> should be the IP address or hostname of the node that runs the Spark interpreter.

#### Note:

When connecting to a YARN cluster, the Spark driver authenticates as the UNIX user that runs the Spark interpreter. You can set the HADOOP\_USER\_NAME environment variable to make the Spark driver authenticate as a different user. If you use the Host interpreter lifecycle, then you can do this by exporting the HADOOP\_USER\_NAME environment variable before starting the Spark interpreter process. If you us the Kubernetes interpreter lifecycle, then you can do this by setting the HADOOP\_USER\_NAME environment variable in the resource manifest (spark.yml).

 Update file spark-defaults.conf keytab location to the location where <keytabfile>.keytab file is copied

- Update file spark-env.sh with the krb5.conf location to the location where krb5.conf file is copied.
  - For example: Djava.security.krb5.conf=/OFS\_MMG/mmg-studio/interpreter-server/spark-interpreter-22.4.2/extralibs/krb5.conf".
- 27. MMG SAAS OFS\_SRV\_ACCT USER is seeded in the User Profile tables: OFS\_SRV\_ACCT user is available in the following tables as a seeded user:
  - aaicl\_sms\_user\_profile
  - aaicl\_sms\_user\_profile\_u

### 10.1.2 Application Pack 8.1.3.1.0 FAQs

- 1. If the cx\_Oracle connection is failing in DS with below error in OEL 8.

  Fail to execute line 4: cx\_Oracle.connect(dsn=dsn\_alias)\nTraceback (most recent call last):\n File "/tmp/1638454321889-0/zeppelin\_python.py", line 163, in <module>\n exec(code, \_zcUserQueryNameSpace)\n File "<stdin>", line 4, in <module>\ncx\_Oracle.DatabaseError: DPI-1047: Cannot locate a 64-bit Oracle Client library: "libnsl.so.1: cannot open shared object file: No such file or directory". Install the libnsl package as below: yum install libnsl or sudo yum install libnsl
- 2. Incase of Python Interpreter fails With `py4j` Error When running interpreters locally, they assume all the dependencies to be already installed and available. Python Interpreter needs `py4j` Package, exact steps to install it depend on the Operating System. If you use `pip`, it can be done with ```bash pip install --user py4j ``` Install the package for all users, root user can run this command without `--user`.
- 3. What is the reason for the http error code 401 when I successfully log in to the MMG Application while MMG Studio is down?

  If MMG Studio is not up during the MMG application login, the mmg-ui logs capture the http error code: 401. Since the cookie creation is done during MMG application login, the user must re login to the MMG application once the Studio is up and running.
- 4. What should I do when the following error message is displayed, and the SSL module is unavailable for Linux 8? urllib3.exceptions.SSLError: Can't connect to HTTPS URL because the SSL module is not available. During handling of the above expectation, another exception occurred:
  - a. Install the compat-openssl10 module on Linux 8.
  - b. Log in to the server as a root user where MMG Application is installed.
  - c. Run the following Shell command: yum -y install compat-openssl10.