

Oracle® Fusion Middleware

Release Notes for Oracle Fusion Middleware Infrastructure



12c (12.2.1.4.0)

E95157-04

July 2020

The Oracle logo, consisting of a solid red square with the word "ORACLE" in white, uppercase, sans-serif font centered within it.

ORACLE®

Oracle Fusion Middleware Release Notes for Oracle Fusion Middleware Infrastructure, 12c (12.2.1.4.0)

E95157-04

Copyright © 2017, 2020, Oracle and/or its affiliates.

Primary Author: Oracle Corporation

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this is software or related documentation that is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, then the following notice is applicable:

U.S. GOVERNMENT END USERS: Oracle programs (including any operating system, integrated software, any programs embedded, installed or activated on delivered hardware, and modifications of such programs) and Oracle computer documentation or other Oracle data delivered to or accessed by U.S. Government end users are "commercial computer software" or "commercial computer software documentation" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, reproduction, duplication, release, display, disclosure, modification, preparation of derivative works, and/or adaptation of i) Oracle programs (including any operating system, integrated software, any programs embedded, installed or activated on delivered hardware, and modifications of such programs), ii) Oracle computer documentation and/or iii) other Oracle data, is subject to the rights and limitations specified in the license contained in the applicable contract. The terms governing the U.S. Government's use of Oracle cloud services are defined by the applicable contract for such services. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Inside are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. AMD, Epyc, and the AMD logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark of The Open Group.

This software or hardware and documentation may provide access to or information about content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services unless otherwise set forth in an applicable agreement between you and Oracle. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services, except as set forth in an applicable agreement between you and Oracle.

Contents

Preface

Audience	vi
Documentation Accessibility	vi
Related Documents	vi
Conventions	vi

1 Introduction

Latest Release Information	1-1
Purpose of this Document	1-1
System Requirements and Specifications	1-1
Certification Information	1-1
Oracle Support	1-1
Deprecated Features	1-2

2 Install and Configure

Issues Related to Product Installation	2-1
Checking for Available Software Patches and Product Information	2-1
Downloading and Applying Required Patches	2-2
Updated Database Client Software Patch Identification Numbers	2-2
Mnemonics for Buttons are Not Read Using JAWS 2019	2-2
Issues Related to Product Configuration	2-2
A Partition with Japanese Name Cannot Be Created from Fusion Middleware Control	2-2
Issues Related to Product Installation and Configuration Documentation	2-3
Registering Node Manager as a Windows Service	2-3
Additional Domain Configuration	2-3
Compatibility of Oracle Business Intelligence with Oracle Fusion Middleware	2-4
Product Installation and Configuration on Autonomous Transaction Processing-Dedicated Database	2-4
ATP-D Support for Fusion Middleware Products	2-4
SYS DBA Privileges Warning After Applying Patches	2-4

UCM Server Logs	2-4
Documentation Errata	2-5

3 Patching and Upgrade

Issues Related to Product Upgrade	3-1
Incorrect Version Numbers After a Reduced Downtime Upgrade	3-1
Error Detecting MDS Schema in IPM-only Domain	3-1
Upgrade Assistant Fails to Load All Schemas Used by a Domain for Audit Schema Users	3-2
Upgrade Assistant Cannot Read a Domain with Multi-Data Sources Defined	3-2
Standard Workspace Dashboards Missing Participant Information After Upgrade	3-3
SAXParseException May Occur During Reconfiguration	3-3
MissingResourceException May Occur During Reconfiguration	3-3
EDN-JMS Backlogged Events Do Not Migrate During Upgrade	3-3
Issues Related to Product Patching	3-3
OPatch Does Not Restore Regenerated Libraries Even After User Quits the Patching Process	3-4

4 Oracle Fusion Middleware Administration

General Issues and Workarounds	4-1
MDS purgeMetadata Command Can Take a Long Time	4-1
Node Manager May Return An Error About ADR	4-1
Configuration Issues and Workarounds	4-2
Fusion Middleware Control Incorrectly Refers to Shared Service Tables	4-2
Deprecated and Desupported Features	4-2
Documentation Errata for Administering Oracle Fusion Middleware	4-2
Using WLST with the Lifecycle Management Tools	4-2

5 Web Services

Upgrade Fails When OWSM Data Source Is Configured as a Multi Data Source	5-2
Using a Repository Backed by a Hardened Oracle Database	5-3
Using Multibyte User Credentials with the wss_http_token_* Policy	5-3
Performing a Bulk Upload of Policies	5-3
Removing Post-Deployment Customizations	5-3
Reviewing Localization Limitations	5-4
Fusion Middleware Control Does Not List Policies When Two Servers Are SSL Enabled (Two-way SSL)	5-4
Web Service Test Page Cannot Test Input Arguments Bound to SOAP Headers	5-4
Possible Limitation When Using Custom Exactly-one Policies	5-5

Security Policies Do Not Work on Subscriber Mediator Component	5-5
Policy Table Might Not Show Attached Policies for Some Locales	5-5
Restart Applications to Get an Accurate Policy Usage Count	5-5
Performance Improvements In Web Services Policy Pages	5-5
Bulk Attachment of Policies Is not Supported In the Current Release	5-6
Fusion Middleware Control Returns You to the OWSM Policies Page After You Edit a Client Policy	5-6
Domain Configuration Is Not Supported in Classpath Mode	5-6
Avoiding XML Encryption Attacks	5-6
USERNAME_ID_PROPAGATION Policies Deprecated	5-7
Deprecated Commands for Oracle Infrastructure Web Services	5-7
A Test Web Service Page Does Not Generate the Correct Date or Date Time Patterns When Importing a Locally Saved Payload	5-15
A Test Web Service Page Does Not Save Loaded Payloads in the Correct Format	5-15
Using the Automatic Policy Configuration for STS May Not Result in a Compatible Policy for a Web Service Client	5-15
Incompatible Policies Are Listed for Web Services and Clients Using SOAP Over JMS Transport	5-16
NoSuchObjectException When the Server Hosting WSM-PM is Shut Down	5-16
NullPointerException After Stopping the WebCenter Portal Managed Server	5-16
ConnectException when the Server Hosting WSM-PM is Down	5-17
The Repository Write Timestamp Cannot Be Retrieved When the Server Hosting WSM-PM Is Shut Down	5-17
Harmless Warning Message When You Create Policy Sets	5-17
About Difference between Installed and Upgraded Configuration Files	5-17
Oracle Infrastructure Web Service Applications Built in 11g Containing WebServiceRef Annotation Fails	5-18
WADL for OPSS and OWSM REST API Is Not Generated from the Browser	5-19
Disable XML External Entity Expansion (XXE) When Using MDDS API	5-19
java.security.NoSuchAlgorithmException When Using the FIPS 140 Algorithms	5-19

Preface

Oracle Fusion Middleware Infrastructure release notes summarizes the release information related to the issues fixed, general issues and their workaround, deprecated and removed functionalities, and more.

- [Audience](#)
- [Documentation Accessibility](#)
- [Related Documents](#)
- [Conventions](#)

Audience

This document is intended for users of Oracle Fusion Middleware 12 c.

Documentation Accessibility

For information about Oracle's commitment to accessibility, visit the Oracle Accessibility Program website at <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=docacc>.

Access to Oracle Support

Oracle customers that have purchased support have access to electronic support through My Oracle Support. For information, visit <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=info> or visit <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=trs> if you are hearing impaired.

Related Documents

For more information, see the following resources:

- [Oracle Fusion Middleware Documentation](#)
This contains all documentation for all Oracle Fusion Middleware 12c products.
- [Oracle Technology Network](#)
This site contains additional documentation that is not included as part of the documentation libraries.

Conventions

The following text conventions are used in this document:

Convention	Meaning
boldface	Boldface type indicates graphical user interface elements associated with an action, or terms defined in text or the glossary.
<i>italic</i>	Italic type indicates book titles, emphasis, or placeholder variables for which you supply particular values.
monospace	Monospace type indicates commands within a paragraph, URLs, code in examples, text that appears on the screen, or text that you enter.

1

Introduction

This chapter contains the information about the latest release. It has the links to the latest System Requirements and Certifications.

Topics

- [Latest Release Information](#)
- [Purpose of this Document](#)
- [System Requirements and Specifications](#)
- [Certification Information](#)
- [Oracle Support](#)
- [Deprecated Features](#)

Latest Release Information

This document is accurate at the time of publication. Oracle will update the release notes periodically after the software release. You can access the latest information and additions to these release notes on the Oracle Help Center.

<http://docs.oracle.com/en/>

Purpose of this Document

This document contains the release information for Oracle Fusion Middleware Infrastructure 12c (12.2.1.4.0).

System Requirements and Specifications

Oracle Fusion Middleware installation and configuration will not complete successfully unless users meet the hardware and software prerequisite requirements before installation. For more information, see System Requirements and Specifications.

Certification Information

To see versions of platforms and related software for which Oracle Fusion Middleware is certified and supported, go to [Oracle Fusion Middleware Supported System Configurations](#)

Oracle Support

Oracle customers that have purchased support have access to electronic support through My Oracle Support at <https://support.oracle.com>.

Deprecated Features

This section covers the deprecated features of Oracle Oracle Fusion Middleware products.

Deprecated Features in 12c (12.2.1.4.0)

The table lists the deprecated features or components and their description.

Feature/Component	Description
OPatchAuto	<p>OPatchAutoFMW (installed in <code>OPatch/auto/fmw</code> directory) is deprecated and will be removed from the next release.</p> <p>You can continue to use OPatchAutoCore (installed in <code>OPatch/auto/core</code> directory) for auto updates during Fusion Middleware installation.</p>
Oracle Traffic Director	<p>Oracle Traffic Director is deprecated and will be removed from the next release.</p> <p>In the future, for equivalent functionality, use Oracle HTTP Server, Microsoft IIS Web Server, or Apache HTTP Server plug-ins, or a native Kubernetes load balancer, such as Traefik.</p>

Deprecated Feature in 12c (12.2.1.3.0)

The following feature is deprecated:

- The Fusion Middleware Lifecycle Management Tools is no longer available, and will be removed from the next release.

2

Install and Configure

This chapter describes issues that are related to Oracle Fusion Middleware product installation and configuration.

The following topics are covered in this chapter:

- [Issues Related to Product Installation](#)
- [Issues Related to Product Configuration](#)
- [Issues Related to Product Installation and Configuration Documentation](#)
- [Documentation Errata](#)

Issues Related to Product Installation

This section contains the following topics:

- [Checking for Available Software Patches and Product Information](#)
- [Downloading and Applying Required Patches](#)
- [Updated Database Client Software Patch Identification Numbers](#)
- [Mnemonics for Buttons are Not Read Using JAWS 2019](#)

Checking for Available Software Patches and Product Information

Before you install any Oracle Fusion Middleware product, it is good practice to review the product information available on My Oracle Support:

<http://support.oracle.com/>

When you register for My Oracle Support, you have easy access to important information about available patches and other important Oracle Fusion Middleware product information.

 **Note:**

For example, you can access the following generic install jar file names and quickstart jar file names:

- **fmw_12.2.1.4.0_idm.jar**
- **fmw_12.2.1.4.0_idmquickstart.jar**
- **fmw_12.2.1.4.0_idmquickstart2.jar**

Downloading and Applying Required Patches

After you install Oracle Fusion Middleware 12c (12.2.1.4.0), there might be cases where additional patches are required to address specific known issues.

Patches for Oracle Fusion Middleware 12c are available from My Oracle Support:

<http://support.oracle.com>

To download a patch:

1. Log in to [My Oracle Support](#).
2. Click the **Patches & Updates** tab.
3. In the Patch Search area, select **Patch Name or Number**.
4. Enter the patch number.
5. Click **Search**. The Patch Search Results page appears.
6. Download and install the patch.

Updated Database Client Software Patch Identification Numbers

The Oracle Fusion Middleware 12c (12.2.1.4.0) installation includes an update to the database client software that includes the database patch set 12.1.0.2.190716.

When you execute the command `opatch lsinventory`, the patch identification number for this update appears as 29494060 on Linux/Unix and 30220086 on Microsoft Windows.

Mnemonics for Buttons are Not Read Using JAWS 2019

For UA and Install screens, in JAWS 2019, short cut keys (mnemonics) to carry out some functions are not echoed while typing.

For example, in JAWS 2019, you cannot hear "ALT+N" shortcut key to activate the Next button.

As a workaround, you can use JAWS 2018 to carry out these functions.

Issues Related to Product Configuration

This section contains the following topic:

- [A Partition with Japanese Name Cannot Be Created from Fusion Middleware Control](#)

A Partition with Japanese Name Cannot Be Created from Fusion Middleware Control

A partition with a Japanese name cannot be created by using Fusion Middleware Control.

As a workaround, you can either use Fusion Middleware Control to create a partition that uses an English name or use the WebLogic Server Administration Console to create a partition with a Japanese name.

Issues Related to Product Installation and Configuration Documentation

This section contains the following topics:

- [Registering Node Manager as a Windows Service](#)
- [Additional Domain Configuration](#)
- [Compatibility of Oracle Business Intelligence with Oracle Fusion Middleware](#)
- [Product Installation and Configuration on Autonomous Transaction Processing-Dedicated Database](#)

Registering Node Manager as a Windows Service

To register Node Manager as a Windows Service serving either one of the following:

- A standalone OHS domain
- A domain with a collocated ODI agent

Do the following after you have created the domain:

1. Set the `JAVA_OPTIONS` environment variable so that it points to the proper Oracle home and Domain home directories.

```
set JAVA_OPTIONS=-Dohs.product.home=ORACLE_HOME -  
Dweblogic.RootDirectory=DOMAIN_HOME
```

For example:

```
set JAVA_OPTIONS=-Dohs.product.home=C:\Oracle\product\OHS\OracleHome -  
Dweblogic.RootDirectory=C:\Oracle\config\domains\OHSDomain
```

2. Go to the Domain home directory and run the following command:

```
installNodeMgrSvc.cmd
```

Additional Domain Configuration

Use the configuration wizard to update the newly created domain.

1. Restart the configuration wizard by issuing the command: `IGD_ORACLE_HOME/oracle_common/common/bin/config.sh`
The configuration screen is displayed.
2. In the **Configuration Type** screen, select **Update an existing domain**.
3. In the **Domain Location** field, specify the Domain home directory (**IGD_ASERVER_HOME**).
4. Click **Next**.
5. On the **Templates** screen, select **Update Domain Using Custom Template**.

6. In the **Template location** field, specify: `IGD_ORACLE_HOME/soa/common/templates/wls/oracle.soa.classic.domain_template.jar`
7. Click **Next**.
8. On the **Gridlink Oracle RAC Component Schema** Page, click **Next**.
9. On the **JDBC Component Test Schema Test** screen, click **Next**.
10. On the **Advanced Configuration** screen, click **Next**.
11. On the **Configuration summary** screen, click **Next**.
12. Once the domain is extended, click **Next** on the **Configuration Progress** screen.
13. Click **Finish** on the **End of Configuration** screen.

Compatibility of Oracle Business Intelligence with Oracle Fusion Middleware

You must install Oracle Business Intelligence 12c (12.2.1.4.0) with Oracle Fusion Middleware 12.2.1.3.0.

You cannot install Oracle Business Intelligence 12.2.1.4.0 in the same Oracle home directory as Oracle Fusion Middleware 12.2.1.4.0.

Product Installation and Configuration on Autonomous Transaction Processing-Dedicated Database

This section includes the following topics:

- [ATP-D Support for Fusion Middleware Products](#)
- [SYS DBA Privileges Warning After Applying Patches](#)
- [UCM Server Logs](#)

ATP-D Support for Fusion Middleware Products

ATP-D database is not supported for Oracle Data Integrator and Oracle Enterprise Data Quality products.

SYS DBA Privileges Warning After Applying Patches

Bug Number: 31690699

After applying the patches 23732643 and 23726506 on Oracle Home, when you start the RCU on ATP-D database, you receive the SYS DBA privileges warning on the **Database Connection Details** screen. You must click **Ignore** and continue with the schema creation. For more information, see [Troubleshooting Tips for Schema Creation on Autonomous Transaction Processing-Dedicated Database](#)

UCM Server Logs

The error messages in the UCM_server logs are:

- general exception:

```
java.sql.SQLException: ORA-01031: insufficient privileges.
```

- data exception:

Caused by: Error : 1450, Position : 0, Sql = CREATE TABLE Subscription

- data exception:

Caused by: Error : 942, Position : 48, Sql = CREATE INDEX
dRTLlastModified_RunTFB30128Ata ON RunTimeConfigData (dRTLlastModified)

- data exception:

Caused by: Error : 1450, Position : 0, Sql = CREATE TABLE RunTimeConfigData

 **Note:**

The errors in the server logs are due to warnings that are displayed in RCU content server schema creation on ATP-D database.

Documentation Errata

There are no known issues at this time.

3

Patching and Upgrade

This chapter describes issues related to the Infrastructure upgrade. The following topics are covered in this chapter:

- [Issues Related to Product Upgrade](#)
- [Issues Related to Product Patching](#)

Issues Related to Product Upgrade

This section contains the following topics:

- [Incorrect Version Numbers After a Reduced Downtime Upgrade](#)
Depending on the upgrade procedure you use to upgrade to 12c (12.2.1.4.0), you may notice that the post-upgrade version number and copyright year remain the same in Oracle Enterprise Manager. This is not an error.
- [Error Detecting MDS Schema in IPM-only Domain](#)
- [Upgrade Assistant Fails to Load All Schemas Used by a Domain for Audit Schema Users](#)
- [Upgrade Assistant Cannot Read a Domain with Multi-Data Sources Defined](#)
- [Standard Workspace Dashboards Missing Participant Information After Upgrade](#)
- [SAXParseException May Occur During Reconfiguration](#)
- [MissingResourceException May Occur During Reconfiguration](#)
- [EDN-JMS Backlogged Events Do Not Migrate During Upgrade](#)

Incorrect Version Numbers After a Reduced Downtime Upgrade

Depending on the upgrade procedure you use to upgrade to 12c (12.2.1.4.0), you may notice that the post-upgrade version number and copyright year remain the same in Oracle Enterprise Manager. This is not an error.

After performing a successful reduced downtime upgrade, you will see incorrect copyright year and version numbers when accessing the Oracle Enterprise Manager. These incorrect versions are a known issue and do not require running the upgrade again. You can safely ignore the following:

- The copyright version year will still show 2017 instead of 2019
- The version will be 12.2.1.3.0 and the runtime version will be 12.2.1.4.0

Error Detecting MDS Schema in IPM-only Domain

If the application extension framework (AXF) is configured along with Oracle Imaging and Process Management (Oracle I/PM), then the MDS datasource gets created in the

domain. If AXF is not configured, then the MDS datasource will not be created in 11g domain.

Therefore, when domain assisted schema upgrade is used in UA, MDS schema will not be detected. You can continue the upgrade without the MDS datasource.

Upgrade Assistant Fails to Load All Schemas Used by a Domain for Audit Schema Users

When upgrading from 11g (11.1.1.9) to 12.2.1.4, the Upgrade Assistant fails to load schemas associated with the domain when **All schemas used by a Domain** is selected.

The following exception is logged:

```
Exception
-----
UPGAST- 00214 - Unable to connect to database as schema user <prefix>_IAU.
Listener refused the connection with the following error :
.
ORA-12504, TNS : Listener was not given the SID in CONNECT_DATA
.
Cause : The database connection failed for the specified reason.
Action : Correct the problem using information provided in the log file; then
retry the operation. In particular if the indicated reason is "Login has
timed out" verify that the host and port are correct and make sure the
database is up and is configured for network access.
```

To work around this issue:

Restart the Upgrade Assistant, enter the 11g domain location, select **Individually Selected Schemas**, and select the correct **_IAU**, **_SOAINFRA**, and **_OPSS** schemas.

Selecting the SOA and OPSS schemas will ensure that Audit Services, User Messaging Service and MDS schemas are selected automatically.

Upgrade Assistant Cannot Read a Domain with Multi-Data Sources Defined

If you receive the following error from the Upgrade Assistant, then you must edit the ua.bat script:

```
ConnectionHelper: CIE config framework not located/initialized.
```

Specifically, to workaround this error you must edit the `oracle_common/upgrade/bin/ua [ua.bat]` script and change the following jar file names: `cieCfg_wls_external_lib.jar` must be changed to `cieCfg_wls_lib.jar`
`cieCfg_cam_external_lib.jar` must be changed to `cieCfg_cam_lib.jar`

Standard Workspace Dashboards Missing Participant Information After Upgrade

After an upgrade to 12c, the Performance Per Participant graph that is displayed on standard Workspace dashboards will only be available for new 12c instances and will not be available for in-flight, hybrid, or completed (closed) 11g instances. However, custom 12c Workspace dashboards will continue to display the participant information.

SAXParseException May Occur During Reconfiguration

The following exception appears in the `reconfig.log` file after invoking the Reconfiguration Wizard with `-log_priority=ALL`:

```
[org.xml.sax.SAXParseException; lineNumber: 3; columnNumber: 77; cvc-elt.1: Cannot find the declaration of element 'stringSubsInfo'.]
```

You can ignore this exception.

MissingResourceException May Occur During Reconfiguration

The following exception appears in the `reconfig.log` file after invoking the Reconfiguration Wizard with `-log_priority=ALL`:

```
java.util.MissingResourceException: No bundle found for base name config-template
```

You can ignore this exception.

EDN-JMS Backlogged Events Do Not Migrate During Upgrade

Backlogged events in the EDN-JMS queue do not migrate when you upgrade from Oracle Fusion Middleware 11g to Oracle Fusion Middleware 12c.

Before you upgrade, check if there are any backlogged events in the JMS queue. After you finish upgrading, verify that these backlogged events are not in the queue.

You can verify if there are any backlogged events in the JMS queue via the Oracle WebLogic Server Administration Console:

1. From the **Domain Structure**, select **soainfra**, then **Services, Messaging, JMS Modules, SOAJMSModule**, and **EDNQueue**.
2. Select **Monitoring** tab.
3. Select **SOAJMSModule** and **EDNQueue**, and then click **Show Messages**.

Issues Related to Product Patching

This section contains the following topic:

- [OPatch Does Not Restore Regenerated Libraries Even After User Quits the Patching Process](#)

OPatch Does Not Restore Regenerated Libraries Even After User Quits the Patching Process

If the OPatch postscript fails and users choose not to proceed with the patching process and quit, OPatch does not restore regenerated libraries correctly.

Check the OPatch log to determine whether or not library regeneration has occurred. If the library regeneration has occurred, apply the patch again. If the OPatch postscript fails again, choose `y` to proceed with the patching process. OPatch will not roll back the patch automatically this time; the user needs to roll back OPatch manually to restore the pre-patch environment.

For information on how to roll back a patch, see [Using OPatch to Patch Oracle Fusion Middleware in *Patching with OPatch*](#).

4

Oracle Fusion Middleware Administration

This chapter describes issues associated with Oracle Fusion Middleware administration. It includes the following topics:

- [General Issues and Workarounds](#)
- [Configuration Issues and Workarounds](#)
- [Deprecated and Desupported Features](#)
- [Documentation Errata for Administering Oracle Fusion Middleware](#)

General Issues and Workarounds

This section describes configuration issues and their workarounds. It includes the following topics:

- [MDS purgeMetadata Command Can Take a Long Time](#)
- [Node Manager May Return An Error About ADR](#)

MDS purgeMetadata Command Can Take a Long Time

When autopurge is not enabled or manual purge is not frequently executed, the MDS database repository may have a lot of older (non-tip) versions accumulated. In this situation, the next purge operation may take a very long time (possibly hours). You may need to terminate the purge operation to avoid affecting the system performance. Currently, it is not possible to terminate the purge operation using Oracle Fusion Middleware tools. Instead, you must terminate the operation at the database level.

To terminate the purge operation, contact the DBA. The DBA can identify the database session where the purgeMetadata operation is executing and kill the session to stop the purge. Note that MDS purges 300 documents in each iteration, commits the change, and repeats until all purgeable documents are processed. As a result, killing the database session does not affect already committed purge iterations.

Node Manager May Return An Error About ADR

In some circumstances, when you start a Managed Server from the Administration Console, an error similar to the following is logged on the Node Manager console. It indicates an issue while initializing Automatic Diagnostic Repository (ADR).

```
SEVERE: failure initializing ADR oracle.dfw.common.DiagnosticsException: failure loading adrci binary from the system path: null  
Cause: DFW-40112: There was an error executing adrci commands; the following errors have been found "null"
```

You can ignore this error because Node Manager does not use ADR.

Configuration Issues and Workarounds

This section describes configuration issues and workarounds. It includes the following topic:

- [Fusion Middleware Control Incorrectly Refers to Shared Service Tables](#)

Fusion Middleware Control Incorrectly Refers to Shared Service Tables

The Service table page of Fusion Middleware Control contains a mention of shared service tables. Shared service tables are not supported.

Deprecated and Desupported Features

The following administrative feature is desupported beginning in 12c (12.2.1.3):

- Moving from test to production.

The scripts and procedures used to move your environment from a test to a production environment is no longer supported. However, if you want to change the network configuration, such as host name, network domain name, or IP address, you can use the `chghost` utility, as described in [About Changing the Network Configuration](#) in *Administering Oracle Fusion Middleware*.

Documentation Errata for *Administering Oracle Fusion Middleware*

The following lists the documentation errata for administration issues:

- [Using WLST with the Lifecycle Management Tools](#)

Using WLST with the Lifecycle Management Tools

Issue

In an SSL-only domain, to connect to a server using WLST, you must set some properties for the start, stop, and discovery actions to succeed.

```
[ -Dweblogic.security.SSL.ignoreHostnameVerification=true  
-Dweblogic.security.TrustKeyStore=DemoTrust ] [ -  
Dweblogic.security.JavaStandardTrustKeyStorePassPhrase=password] [ -  
Dweblogic.security.CustomTrustKeyStoreFileName=filename  
-Dweblogic.security.TrustKeystoreType=jks [ -  
Dweblogic.security.CustomTrustKeyStorePassPhrase=password]] [ -  
Dweblogic.security.SSL.hostnameVerifier=classname]
```

For more information about setting the properties, see [Using the WebLogic Scripting Tool](#) in *Understanding the WebLogic Scripting Tool*.

For more information about the start, stop, and discovery actions, see Additional Information About Standard Actions in *Configuring Oracle Fusion Middleware Using Lifecycle Management Tools*.

5

Web Services

This chapter describes issues associated with Web services development, security, and administration, including Oracle Web Services Manager. It includes the following topics:

 **Note:**

To resolve WebLogic Web Services issues, see *Web Services and XML Issues and Workarounds* in the *Oracle Fusion Middleware Release Notes for Oracle WebLogic Server*.

- [Upgrade Fails When OWSM Data Source Is Configured as a Multi Data Source](#)
- [Using a Repository Backed by a Hardened Oracle Database](#)
- [Using Multibyte User Credentials with the wss_http_token_* Policy](#)
- [Performing a Bulk Upload of Policies](#)
- [Removing Post-Deployment Customizations](#)
- [Reviewing Localization Limitations](#)
- [Fusion Middleware Control Does Not List Policies When Two Servers Are SSL Enabled \(Two-way SSL\)](#)
- [Web Service Test Page Cannot Test Input Arguments Bound to SOAP Headers](#)
- [Possible Limitation When Using Custom Exactly-one Policies](#)
- [Security Policies Do Not Work on Subscriber Mediator Component](#)
- [Policy Table Might Not Show Attached Policies for Some Locales](#)
- [Restart Applications to Get an Accurate Policy Usage Count](#)
- [Performance Improvements In Web Services Policy Pages](#)
- [Bulk Attachment of Policies Is not Supported In the Current Release](#)
- [Fusion Middleware Control Returns You to the OWSM Policies Page After You Edit a Client Policy](#)
- [Domain Configuration Is Not Supported in Classpath Mode](#)
- [Avoiding XML Encryption Attacks](#)
- [USERNAME_ID_PROPAGATION Policies Deprecated](#)
- [Deprecated Commands for Oracle Infrastructure Web Services](#)
- [A Test Web Service Page Does Not Generate the Correct Date or Date Time Patterns When Importing a Locally Saved Payload](#)
- [A Test Web Service Page Does Not Save Loaded Payloads in the Correct Format](#)

- Using the Automatic Policy Configuration for STS May Not Result in a Compatible Policy for a Web Service Client
- Incompatible Policies Are Listed for Web Services and Clients Using SOAP Over JMS Transport
- NoSuchObjectException When the Server Hosting WSM-PM is Shut Down
- NullPointerException After Stopping the WebCenter Portal Managed Server
- ConnectException when the Server Hosting WSM-PM is Down
- The Repository Write Timestamp Cannot Be Retrieved When the Server Hosting WSM-PM Is Shut Down
- Harmless Warning Message When You Create Policy Sets
- About Difference between Installed and Upgraded Configuration Files
- Oracle Infrastructure Web Service Applications Built in 11g Containing WebServiceRef Annotation Fails
- WADL for OPSS and OWSM REST API Is Not Generated from the Browser
- Disable XML External Entity Expansion (XXE) When Using MDDS API
- java.security.NoSuchAlgorithmException When Using the FIPS 140 Algorithms

Upgrade Fails When OWSM Data Source Is Configured as a Multi Data Source

When you attempt to upgrade Oracle Weblogic and Oracle SOA Suite from 11g to 12c (12.1.3) and later, if the 11g instance uses a mds-owsm datasource that is configured to be a multi data source, the Upgrade Assistant fails with the following error:

```
WSM] [INCIDENT_ERROR] [] [upgrade.WSM.WSMPLUGIN] [tid: 63] [ecid: 235be93f-
e646-47fb-b960-34947fed8f86-00000001,0] [[
oracle.ias.update.exception.UpgradeException: WSMERROR-00015: Failed to read the
Oracle WSM datasource connection details.
at
oracle.wsm.lifecycle.upgrade.impl.WSMUpgradePlugin.initializePluginData(WSMUpgrad
ePlugin.java:227)
at
oracle.wsm.lifecycle.upgrade.impl.WSMUpgradePlugin.upgrade(WSMUpgradePlugin.java:
263)
at oracle.ias.update.plugin.Plugin.upgrade(Plugin.java:576)
at oracle.ias.update.plan.PlanStep.upgrade(PlanStep.java:377)
at oracle.ias.update.UpgradeDriver.doUpgrades(UpgradeDriver.java:947)
at oracle.ias.update.gui.UAUpgradeThread.run(UAUpgradeThread.java:41)
```



Note:

This error occurs even after you apply patch 19865550 to prevent a message warning you of an unsupported multi data source.

To work around this issue, perform the following steps:

1. Modify the mds-owsm data source, changing it from a multi data source to a generic data source.

2. Run the Upgrade Assistant.
3. Once the upgrade completes successfully, if necessary, modify the data source back to its original configuration.

Using a Repository Backed by a Hardened Oracle Database

Oracle Web Services Manager uses an MDS repository to store metadata such as policies, assertion templates, and policy usage data.

Oracle Web Services Manager 12c (12.2.1) is certified to work with a repository backed by a hardened Oracle Database.

See *Managing the OWSM Repository in Securing Web Services and Managing Policies with Oracle Web Services Manager*

Using Multibyte User Credentials with the `wss_http_token_*` Policy

In this release, multibyte user credentials are not supported for the `wss_http_token_*` policies. If multibyte user credentials are required, use a different policy, such as `wss_username_token_*` policy. For more information about the available policies, see *Predefined Policies in Securing Web Services and Managing Policies with Oracle Web Services Manager*.

Performing a Bulk Upload of Policies

When you perform a bulk import of policies to the MDS repository, if the operation does not succeed initially, retry the operation until the bulk import succeeds.

For the most part, this can occur for an Oracle RAC database when the database is switched during the metadata upload. If there are n databases in the Oracle RAC database, then you may need to retry this operation n times.

For more information about bulk import of policies, see *Migrating Policies in the Administering Web Services*.

Removing Post-Deployment Customizations

When the `connections.xml` file is changed after deployment by using the `AdfConnection` MBean, the complete connection is saved as a customization. This means that changes to the connection in a redeployed application are overwritten by the customization.

When you use Fusion Middleware Control to make changes to an application's `connections.xml` file after deployment, a new `connections.xml` file is created as a customization and stored in the MDS repository. This customization persists for the life of the application. Therefore, if you redeploy the application, the customized `connections.xml` file continues to be applied as a customization on the application.

To allow the redeployed application's `connections.xml` file to be applied without the prior customization (from Fusion Middleware Control), you must explicitly remove the `connections.xml` customizations from the MDS repository.

For example, if you deploy an application with a Web services data control, then use Fusion Middleware Control to attach the `username_token_client_policy`, and subsequently detach the policy. Then, you return to JDeveloper to edit the application and attach the `http_token_client_policy`, and redeploy the application. When you view the application using Fusion Middleware Control, you see that it is not using the `http_token_client_policy` that you attached. That is because it is using the customized `connections.xml` file that you previously created using Fusion Middleware Control.

If you remove the `connections.xml` customizations from the MDS repository, the application will use the its own `connections.xml` file.

Reviewing Localization Limitations

The following information is supported in **English only** in this release of Oracle Enterprise Manager:

- All fields in the policy and assertion template except the `orawsp:displayName` field.
- If using the `?orawSDL` browser address, the `orawsp:description` field.

Fusion Middleware Control Does Not List Policies When Two Servers Are SSL Enabled (Two-way SSL)

When a Managed Server is Two-way enabled SSL (for example, a SOA server hosting OWSM Policy Manager over Two-way SSL) and the Administration Server hosting Fusion Middleware Control is correctly configured to access the Two-way SSL-enabled Managed Server, Fusion Middleware Control still does not list the OWSM policies.

Web Service Test Page Cannot Test Input Arguments Bound to SOAP Headers

For Web services that have any input arguments bound to SOAP headers, the Test Web Service page in the Fusion Middleware Control console cannot show the message. Therefore, such operations cannot be tested with the **Test Web Service** page.

For example, if the input for a multi-part WSDL is viewed through Fusion Middleware Control, and one input argument is bound to a SOAP header, the composite instance fails with the following exception because the other part of the message was missing in the input:

```
ORAMED-01203:[No Part]No part exist with name "request1" in source message
```

To resolve such an issue, select XML View for Input Arguments and edit the payload to pass input for both parts of the WSDL.

Possible Limitation When Using Custom Exactly-one Policies

In some cases, there can be a limitation when using custom Exactly-one policies. For a set of assertions within the exactly-one policy, if a request message satisfies the first assertion, then the first assertion gets executed and a response is sent accordingly. However, this may not be the desired behavior in some cases because the request may be intended for the subsequent assertions.

For example, you may have a client policy that has `Timestamp=ON` and a service exactly-one policy that has a `wss11 username token with message protection` assertions: the first has `Timestamp=OFF`; the second has `Timestamp=ON`. Therefore, the first assertion in the service exactly-one policy is not expecting the `Timestamp` in the request, yet the second assertion does expect it. In this case, the first assertion gets executed and the response is sent with no `Timestamp`. However, the client-side processing then fails because it expects the `Timestamp` that was sent in the request.

This limitation can exist with any cases where a client policy expects a greater number of elements to be signed and a service policy does not.

Security Policies Do Not Work on Subscriber Mediator Component

Component Authorization `denyall` policy does not work at subscriber mediator component. Authorization policy works for other normal mediator component cases.

Policy Table Might Not Show Attached Policies for Some Locales

The Directly Attached Polices table may not display the attached policies for the following locales: `zh-cn`, `zh-tw`, `ja`, `pt-br`, `es`, `fr`, `ko`.

This issue may occur when you attach a policy to the Web service endpoint in the Web service application in Fusion Middleware Control.

As a workaround, enlarge the columns.

Restart Applications to Get an Accurate Policy Usage Count

If a policy that is being referred to by a Web Service is deleted and then reimported, then its usage count is not correct and applications must be restarted to obtain an accurate usage count.

Performance Improvements In Web Services Policy Pages

Performance improvements have been made to the Web Services Policy pages in Fusion Middleware Control by removing the unnecessary role query.

Bulk Attachment of Policies Is not Supported In the Current Release

Attaching one or more policies to one or more Web services by using the bulk attachment feature is not supported in the current release. Use the Policy Set feature instead. For more information on Policy Sets, see *Attaching Policies Globally Using Policy Sets Using WLST and Schema Reference for Policy Sets in Securing Web Services and Managing Policies with Oracle Web Services Manager*.

Fusion Middleware Control Returns You to the OWSM Policies Page After You Edit a Client Policy

When you generate client policies in Enterprise Manager, the Generate Client Policies page appears and the generated policies are shown as not saved. After you save the policies, and then edit one of them, you are returned to the OWSM Policies page. This is an error in Enterprise Manager. You should be returned to the Generate Client Policies page.

To edit additional policies, use the search feature in the OWSM Policies page to locate the client policy that you wish to edit.

For more information, see *Generating Client Policies from a WSDL in Securing Web Services and Managing Policies with Oracle Web Services Manager*.

Domain Configuration Is Not Supported in Classpath Mode

If the Policy Manager URL is configured as a classpath, then domain-level configuration is not supported. All domain-level configuration information is stored in the OWSM repository, and not in the JAR file that is included in the classpath. For information about configuring the Policy Manager URL, see the following sections in *Securing Web Services and Managing Policies with Oracle Web Services Manager*:

- [Configuring the Policy Manager Connection Using Fusion Middleware Control](#)
- [Configuring the Policy Manager Connection Using WLST](#)

If you wish to manage domain-level configuration, configure the Policy Manager URL to specify a remote domain or use `auto` mode. After you have configured the new Policy Manager URL mode, you must restart the server for it to take effect.

Avoiding XML Encryption Attacks

In past releases, OWSM sent different fault codes (for example, `FailedAuthentication`, `InvalidSecurityToken`, and `FailedCheck`) for different error cases. In the current release, this default behavior has been changed. OWSM now sends the `InvalidSecurity` fault code for all error cases. This has been done to avoid XML encryption attacks. An encryption attack is possible if the service sends different fault codes for different types of errors (for example, `FailedAuthentication`, `InvalidSecurityToken`, `FailedCheck`, and so on). This default behavior can be changed by setting the domain-wide agent property `use.unified.fault.code` to `false`. However, this is not recommended, because it might allow XML encryption

attacks. The default value for this property, "true", will cause OWSM to send the `InvalidSecurity` fault code for all error cases. For more information on the `use.unified.fault.code` property, see [Configuring Security Policy Enforcement Using WLST](#) in *Securing Web Services and Managing Policies with Oracle Web Services Manager*.

USERNAME_ID_PROPAGATION Policies Deprecated

The following `USERNAME_ID_PROPAGATION` policies are deprecated in Release 12c (12.2.1):

```
wss10_username_id_propagation_with_msg_protection_client_policy
wss10_username_id_propagation_with_msg_protection_service_policy
```

For details about these policies, see "Oracle Web Services Manager Predefined Policies" in *Securing Web Services and Managing Policies with Oracle Web Services Manager*.

Deprecated Commands for Oracle Infrastructure Web Services

[Table 5-1](#) lists the WLST commands for Oracle Infrastructure Web Services (or clients) that were available in Oracle Fusion Middleware 11g release and which have been deprecated in 12c (12.1.2). In addition, the table lists the new WLST command equivalent and provides an example of how you can update your code to use the new command.

For more information about the WLST commands, see Web Services Custom WLST Commands in *WLST Command Reference for Infrastructure Components*.

Table 5-1 Deprecated Commands for Oracle Infrastructure Web Services

Deprecated Command (11g)	Recommended Command (12c)	Updating Your Code
<code>abortRepositorySession</code>	<code>abortWSMSession</code>	<p>11g Release (for Repository operations):</p> <pre>wls:/jrfServer_domain/ serverConfig> abortRepositorySession()</pre> <p>12c Release (for both Repository and PolicySubject operations):</p> <pre>wls:/jrfServer_domain/ serverConfig> abortWSMSession()</pre>

Table 5-1 (Cont.) Deprecated Commands for Oracle Infrastructure Web Services

Deprecated Command (11g)	Recommended Command (12c)	Updating Your Code
attachPolicySet	setWSMPolicySetScope	<p>11g Release:</p> <pre>wls:/jrfServer_domain/ serverConfig> attachPolicySet ('Domain("base_domain")')</pre> <p>12c Release:</p> <pre>wls:/jrfServer_domain/ serverConfig> setWSMPolicySetScope ('Domain("base_domain")')</pre>
attachPolicySetPolicy	attachWSMPolicy attachWSMPolicies	<p>11g Release (for both Repository and PolicySubject operation on policy set):</p> <pre>wls:/jrfServer_domain/ serverConfig> attachPolicySetPolicy ('oracle/ wss_username_token_service_policy')</pre> <p>12c Release:</p> <pre>wls:/jrfServer_domain/ serverConfig> attachWSMPolicy('oracle/ wss_username_token_service_policy')</pre> <pre>wls:/wls-domain/ serverConfig>attachWSMPolicies(["oracle/ wss_username_token_client_polic y","oracle/log_policy"])</pre>
beginRespositorySession	beginWSMSession	<p>11g Release (for Repository operations):</p> <pre>wls:/jrfServer_domain/ serverConfig> beginRepositorySession()</pre> <p>12c Release (for both Repository and PolicySubject operations):</p> <pre>wls:/jrfServer_domain/ serverConfig> beginWSMSession()</pre>

Table 5-1 (Cont.) Deprecated Commands for Oracle Infrastructure Web Services

Deprecated Command (11g)	Recommended Command (12c)	Updating Your Code
<code>clonePolicySet</code>	<code>cloneWSMPolicySet</code>	<p>11g Release:</p> <pre>wls:/jrfServer_domain/ serverConfig> clonePolicySet ('myNewPolicySet', 'myPolicySet')</pre> <p>12c Release:</p> <pre>wls:/jrfServer_domain/ serverConfig> cloneWSMPolicySet ('myNewPolicySet', 'myPolicySet')</pre>
<code>commitRepositorySession</code>	<code>commitWSMSession</code>	<p>11g Release (for Repository operations):</p> <pre>wls:/jrfServer_domain/ serverConfig> commitRepositorySession()</pre> <p>12c Release (for both Repository and PolicySubject operations):</p> <pre>wls:/jrfServer_domain/ serverConfig> commitWSMSession()</pre>
<code>createPolicySet</code>	<code>createWSMPolicySet</code>	<p>11g Release:</p> <pre>wls:/jrfServer_domain/ serverConfig> createPolicySet('myPolicySet', 'ws-service', 'Domain("base_domain")')</pre> <p>12c Release:</p> <pre>wls:/jrfServer_domain/ serverConfig> createWSMPolicySet ('myPolicySet', 'ws-service', 'Domain("base_domain")')</pre>
<code>deletePolicySet</code>	<code>deleteWSMPolicySet</code>	<p>11g Release:</p> <pre>wls:/jrfServer_domain/ serverConfig> deletePolicySet('myPolicySet')</pre> <p>12c Release:</p> <pre>wls:/jrfServer_domain/ serverConfig> deleteWSMPolicySet ('myPolicySet')</pre>

Table 5-1 (Cont.) Deprecated Commands for Oracle Infrastructure Web Services

Deprecated Command (11g)	Recommended Command (12c)	Updating Your Code
describeRespositorySession	describeWSMSession	<p>11g Release (for Repository operations):</p> <pre>wls:/jrfServer_domain/ serverConfig> describeRespositorySession()</pre> <p>11g Release (for PolicySubject operations): N/A</p> <p>12c Release (for both Repository and PolicySubject operations):</p> <pre>wls:/jrfServer_domain/ serverConfig> describeWSMSession()</pre>
detachPolicySet	detachWSMPolicy detachWSMPolicies	<p>11g Release (for both Repository and PolicySubject operation on policy set):</p> <pre>wls:/jrfServer_domain/ serverConfig> detachPolicySet ('oracle/ wss_username_token_service_policy')</pre> <p>12c Release:</p> <pre>wls:/jrfServer_domain/ serverConfig> detachWSMPolicy('oracle/ wss_username_token_service_policy')</pre> <pre>wls:/wls-domain/ serverConfig>detachWSMPolicies(["oracle/log_policy", "oracle/ wss_username_token_client_polic y"])</pre>
displayPolicySet	displayWSMPolicySet	<p>11g Release:</p> <pre>wls:/jrfServer_domain/ serverConfig> displayPolicySet('myPolicySet')</pre> <p>12c Release:</p> <pre>wls:/jrfServer_domain/ serverConfig> displayWSMPolicySet ('myPolicySet')</pre>

Table 5-1 (Cont.) Deprecated Commands for Oracle Infrastructure Web Services

Deprecated Command (11g)	Recommended Command (12c)	Updating Your Code
<code>enablePolicySet</code>	<code>enableWSMPolicySet</code>	<p>11g Release:</p> <pre>wls:/jrfServer_domain/ serverConfig> enablePolicySet(true)</pre> <p>12c Release:</p> <pre>wls:/jrfServer_domain/ serverConfig> enableWSMPolicySet(true)</pre>
<code>enablePolicySetPolicy</code>	<code>enableWSMPolicy</code> <code>enableWSMPolicies</code>	<p>11g Release:</p> <pre>wls:/wls-domain/ serverConfig>enablePolicySetPolic y('/oracle/log_policy',false)</pre> <p>12c Release:</p> <pre>wls:/wls-domain/ serverConfig>enableWSMPolicy('/ oracle/log_policy',false)</pre> <pre>wls:/wls-domain/ serverConfig>enableWSMPolicies(["oracle/log_policy", "oracle/ wss_username_token_client_polic y"], true)</pre>
<code>exportRepository</code>	<code>exportWSMRepository</code>	<p>11g Release:</p> <pre>wls:/jrfServer_domain/ serverConfig> exportRepository ("/tmp/repo.zip")</pre> <p>12c Release:</p> <pre>wls:/jrfServer_domain/ serverConfig> exportWSMRepository ("/tmp/repo.zip")</pre>
<code>importRepository</code>	<code>importWSMArchive</code>	<p>11g Release (for repository documents):</p> <pre>wls:/jrfServer_domain/ serverConfig> importRepository ("/tmp/repo.zip")</pre> <p>12c Release (for repository documents):</p> <pre>wls:/jrfServer_domain/ serverConfig> importWSMArchive ("/tmp/repo.zip")</pre>

Table 5-1 (Cont.) Deprecated Commands for Oracle Infrastructure Web Services

Deprecated Command (11g)	Recommended Command (12c)	Updating Your Code
<code>listPolicySets</code>	<code>listWSMPolicySets</code>	<p>11g Release:</p> <pre>wls:/wls-domain/ serverConfig>listPolicySets('sca- reference')</pre> <p>12c Release:</p> <pre>wls:/wls-domain/ serverConfig>listWSMPolicySets('sc a-reference')</pre>
<code>migrateAttachments</code>	<code>migrateWSMAttachments</code>	<p>11g Release:</p> <pre>wls:/jrfServer_domain/ serverConfig> migrateAttachments()</pre> <p>12c Release:</p> <pre>wls:/jrfServer_domain/ serverConfig> migrateWSMAttachments()</pre>
<code>modifyPolicySet</code>	<code>selectWSMPolicySet</code>	<p>11g Release:</p> <pre>wls:/jrfServer_domain/ serverConfig> modifyPolicySet('myPolicySet')</pre> <p>12c Release:</p> <pre>wls:/jrfServer_domain/ serverConfig> selectWSMPolicySet ('myPolicySet')</pre>
<code>resetWSMPolicyRepository</code>	<code>restWSMRepository</code>	<p>11g Release:</p> <pre>wls:/jrfServer_domain/ serverConfig> resetWSMPolicyRepository()</pre> <p>12c Release:</p> <pre>wls:/jrfServer_domain/ serverConfig> resetWSMRepository()</pre>

Table 5-1 (Cont.) Deprecated Commands for Oracle Infrastructure Web Services

Deprecated Command (11g)	Recommended Command (12c)	Updating Your Code
setConfiguration	setWSMConfiguration	<p>11g Release</p> <pre>wls:/jrfServer_domain/ serverConfig> setConfiguration('/WLS/myDomain')</pre> <p>12c Release</p> <pre>wls:/jrfServer_domain/ serverConfig> displayWSMConfiguration('WLS/ base_domain')</pre>
setPolicySetConstraint	setWSMPolicySetConstraint	<p>11g Release:</p> <pre>wls:/jrfServer_domain/ serverConfig> setPolicySetConstraint ('HTTPHeader("VIRTUAL_HOST_TYPE", external")')</pre> <p>12c Release:</p> <pre>wls:/jrfServer_domain/ serverConfig> setWSMPolicySetConstraint ('HTTPHeader("VIRTUAL_HOST_TYPE", external")')</pre>
setPolicySetDescription	setWSMPolicySetDescription	<p>11g Release:</p> <pre>wls:/jrfServer_domain/ serverConfig> setPolicySetDescription ('Global policy set for web service endpoint.')</pre> <p>12c Release:</p> <pre>wls:/jrfServer_domain/ serverConfig> setWSMPolicySetDescription ('Global policy set for web service endpoint.')</pre>

Table 5-1 (Cont.) Deprecated Commands for Oracle Infrastructure Web Services

Deprecated Command (11g)	Recommended Command (12c)	Updating Your Code
setWebServicePolicyOverride	setWSMPolicyOverride	<p>11g Release:</p> <pre>wls:/jrfServer_domain/ serverConfig> setWebServicePolicyOverride ('/ base_domain/server1/ HelloWorld#1_0','j2wbasicPolicy', 'web', '{http:// namespace/}WssUsernameService','JR FWssUsernamePort', 'oracle/ wss_username_token_service_policy' , 'reference.priority', '10')</pre> <p>12c Release:</p> <pre>wls:/jrfServer_domain/ serverConfig> setWSMPolicyOverride ('oracle/ wss_username_token_service_policy' , 'reference.priority', '10')</pre>
setPolicySetPolicyOverride	setWSMPolicyOverride	<p>11g Release (for both Repository and PolicySubject operation on policy set):</p> <pre>wls:/jrfServer_domain/ serverConfig> setPolicySetPolicyOverride ('oracle/ wss_username_token_service_policy' , 'reference.priority', '10')</pre> <p>12c Release:</p> <pre>wls:/jrfServer_domain/ serverConfig> setWSMPolicyOverride ('oracle/ wss_username_token_service_policy' , 'reference.priority', '10')</pre>
upgradeWSMPolicyRepository	upgradeWSMRepository	<p>11g Release:</p> <pre>wls:/jrfServer_domain/ serverConfig> upgradeWSMPolicyRepository()</pre> <p>12c Release:</p> <pre>wls:/jrfServer_domain/ serverConfig> upgradeWSMRepository()</pre>

Table 5-1 (Cont.) Deprecated Commands for Oracle Infrastructure Web Services

Deprecated Command (11g)	Recommended Command (12c)	Updating Your Code
validatePolicySet	validateWSMPolicySet	<p>11g Release:</p> <pre>wls:/jrfServer_domain/ serverConfig> validatePolicySet ('myPolicySet')</pre> <p>12c Release:</p> <pre>wls:/jrfServer_domain/ serverConfig> validateWSMPolicySet ('myPolicySet')</pre>

A Test Web Service Page Does Not Generate the Correct Date or Date Time Patterns When Importing a Locally Saved Payload

In Fusion Middleware Control, when you test a SOAP web service on the Test Web Service page, the **Import Payload** option does not generate the correct date/date time type patterns when importing a payload XML file, as follows:

- Tree View – The date time value is always formatted to a US pattern, such as Tue Dec 30 00:00:00 PST 2014, when the correct pattern should be YYYY-MM-ddTHH:mm:ss or YYYY-MM-dd.
- XML View – The server time zone is always incorrectly appended to the date, such as 2014-12-30-08:00, which is not part of the imported value.

Workaround:

Clear the imported date and date time values, and then manually enter the correct values before you submit the payload.

A Test Web Service Page Does Not Save Loaded Payloads in the Correct Format

In Fusion Middleware Control, when you test a SOAP web service on the Test Web Service page, the **Save Payload** option incorrectly saves the loaded payload in Server Locale format (ISO-8859-1) instead of in UTF-8 format.

Using the Automatic Policy Configuration for STS May Not Result in a Compatible Policy for a Web Service Client

Using the automatic policy configuration for STS (Security Token Service) in OWSM may not result in a compatible policy.

Workaround:

Manually configure the STS config policy from a web service client, as described in "Manually Configuring the STS Config Policy From the Web Service Client: Main Steps" in *Securing Web Services and Managing Policies with Oracle Web Services Manager*.

Incompatible Policies Are Listed for Web Services and Clients Using SOAP Over JMS Transport

In Fusion Middleware Control, when you attach OWSM policies to web services and clients that use SOAP over JMS transport, the list of available policies includes policies that are not compatible.

See, "Which OWSM Policies Are Supported for Web Services and Clients That Use SOAP Over JMS Transport" in *Securing Web Services and Managing Policies with Oracle Web Services Manager*.

NoSuchObjectException When the Server Hosting WSM-PM is Shut Down

When the server on which the wsm-pm application is running in a WebLogic domain is shut down before servers on other domains are shut down, you will see an exception as follows:

```
<Error> <oracle.wsm.resources.policymanager>  
<WSM-02313> <The documents used by a policy subject cannot be recorded due to  
underlying error "Exception during invoke."  
java.rmi.NoSuchObjectException: Exception during invoke.
```

This error occurs when agents on other domains try to continue to talk to wsm-pm and are unable to do so.

This is expected behavior when wsm-pm is not available due to shutdown of the WebLogic server where it is deployed. No user action is needed.

NullPointerException After Stopping the WebCenter Portal Managed Server

After you stop the WebCenter Portal Managed Server, the following error message may appear:

```
Failed while destroying filter: OWSM Security Filter.  
java.lang.NullPointerException
```

There is no impact to functionality, and no user action is needed.

ConnectException when the Server Hosting WSM-PM is Down

When the server on which the wsm-pm application is running in a WebLogic domain is shut down before servers on other domains are shut down, you see an exception as follows:

```
java.rmi.ConnectException
```

This error occurs if the wsm-pm application is unreachable.

This is expected behavior when wsm-pm is not available due to shutdown of the WebLogic server where it is deployed. No user action is needed.

The Repository Write Timestamp Cannot Be Retrieved When the Server Hosting WSM-PM Is Shut Down

When you shut down the server on which the wsm-pm application is deployed before you shut down the Administration Server, you see the following exception:

```
The repository write timestamp cannot be retrieved due to underlying error
```

This is expected behavior. No user action is needed.

Harmless Warning Message When You Create Policy Sets

When you create policy sets for resource type of SOAP Web Service or SOAP Web Service Client" with non-security policy references attached, you will see a warning message:

```
"Non-Security policies do not apply to Java EE Web Services."
```

This warning message can be ignored.

About Difference between Installed and Upgraded Configuration Files

The following domain configuration files appear different in a new 12.2.1 install compared to an upgraded WebCenter Portal:

```
config/fmwconfig/audit-store.xml  
config/fmwconfig/jps-config.xml  
config/fmwconfig/jps-config-jse.xml
```

This occurs because, during upgrade, the configuration is moved to wsm-config.xml but not removed from the original files including jps-config.xml. There is no impact to functionality and the variation can be safely ignored.

Oracle Infrastructure Web Service Applications Built in 11g Containing WebServiceRef Annotation Fails

Oracle Infrastructure Web Services do not support the `WebServiceRef` annotation. In Release 11g, generated example code included this annotation. If you included this generated example code in your applications, they built and ran successfully because the annotation was ignored. In the CDI implementation in Java EE 7 in 12c (12.2.1), all annotations are processed. As a result, any applications built in Release 11g that contain these generated example classes (`[Service]PortClient.java`) fails.

Note that Oracle Infrastructure Web Service applications built in 12c do not contain this annotation and do not exhibit this problem.

Workaround

Use one of the following solutions:

- Remove the `WebServiceRef` annotation from the generated source code in the application or library.

In the 11g Oracle Infrastructure Web Service WSA generated example client classes, the class name is always `<Port Name>Client.java`. You can remove the annotation by:

- Searching within your source code to find terms such as `"*Client.java"`, or
- Writing a helper class to search the JAR/WAR/EAR code. For example:

```
private final static Class DefaultAnnotationTypeClass =
    javax.xml.ws.WebServiceRef.class;
    private void findAnnotation(Class targetClass, Class
annotationTypeClass)
    throws Exception {
        if (targetClass == null || annotationTypeClass == null) {
            return;
        }
        if (targetClass.getAnnotation(annotationTypeClass) != null) {
            throw new Exception("Found " + annotationTypeClass + " in
class "
+ targetClass.getName());
        }
        for (Field field : targetClass.getDeclaredFields()) {
            if (field != null &&
field.getAnnotation(annotationTypeClass) !=
null) {
                throw new Exception("Found " + annotationTypeClass + " in
class " + targetClass.getName());
            }
        }
        ...
        findAnnotation( userPortClientClass , DefaultAnnotationTypeClass );
    }
```

- For each WAR /JAR file, providing a `beans.xml` that disables CDI annotation scanning for the application. The necessary `beans.xml` snippet to turn off CDI annotation scanning is as follows:

```
<beans xmlns="http://xmlns.jcp.org/xml/ns/javaee"
      xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
      xsi:schemaLocation="http://xmlns.jcp.org/xml/ns/javaee
      http://xmlns.jcp.org/xml/ns/javaee/beans_1_1.xsd"
      bean-discovery-mode="none">
</beans>
```

WADL for OPSS and OWSM REST APIs Not Generated from the Browser

WADL for OPSS REST APIs and OWSM REST APIs is not generated from the browser because of the loading of the XSL stylesheet.

Workaround

Instead of generating WADL from the browser by visiting URLs such as the following, use the Mozilla REST client to visit these URLs:

```
http://myhost.mydomain.com:7001/idaas/platform/admin/v1/application.wadl
http://myhost.mydomain.com:7001/idaas/webservice/admin/v1/application.wadl
```

The response will give the XML contents of WADL.

Disable XML External Entity Expansion (XXE) When Using MDDS API

If you are using the MDDS API, disable XXE in the WSDL by setting the `oracle.j2ee.ws.mdds.preventXXE` option to `Boolean.TRUE` as shown in the following example:

```
modelFactory.setOption("oracle.j2ee.ws.mdds.preventXXE", Boolean.TRUE);
```

java.security.NoSuchAlgorithmException When Using the FIPS 140 Algorithms

When using the FIPS 140 algorithms, the following error message may appear:

```
java.security.NoSuchAlgorithmException: Cannot find any provider
supporting RSA/ECB/OAEPWithSHA-1AndMGF1Padding
at javax.crypto.Cipher.getInstance(Cipher.java:529)
```

This is a known issue. No user action is needed.