

Oracle Unified Directory Bundle Patch Readme

This document describes Bundle Patch 12.2.1.4.210406 for Oracle Unified Directory.

This readme document requires base installation of Oracle Unified Directory 12c (12.2.1.4.0). It includes the following sections:

Note:

For issues documented after the release of OUD Bundle Patch 12.2.1.4.210406, log into [My Oracle Support](#). In the Search Knowledge Base field, enter 2602696.1. This is the ID of the document that describes the Oracle Fusion Middleware 12.2.1.4.0 Known Issues.

- [Understanding Bundle Patches](#)
- [Bundle Patch Recommendation](#)
- [Bundle Patch Requirements](#)
- [Before Applying the Bundle Patch](#)
- [Using the Oracle Patch Mechanism \(Opatch\)](#)
- [Applying the Bundle Patch](#)
- [After Applying the Bundle Patch](#)
- [Creating the File based Access Control Log Publisher](#)
- [Removing the Bundle Patch](#)
- [Resolved Issues](#)
- [Known Issues and Workarounds](#)
- [Documentation Updates](#)
- [Related Documents](#)
- [Documentation Accessibility](#)

New Features and Enhancements in OUD Bundle Patch 12.2.1.4.210406

Oracle Unified Directory 12.2.1.4.210406 BP includes the following new features and enhancements:

Configure Password Validators and Password Generators

The Password Validators and Password Generators can now be created as Subentries and can attach to a Subentry Password Policy. The Password Policies, Password Validators, or Password Generators that are created as Subentries (that is, as part of the data) are replicated. For details about the Password Policies, see [Managing Password Policies](#).

Keystore and Truststore Enhancements

This release onwards the pin to keystores and truststores will not be stored in PIN files. Instead it will be stored in encrypted form in the corresponding configuration entry within Oracle Unified Directory. For details about keystores, see [Configuring Key Manager Providers](#). For details about truststores, see [Configuring Trust Manager Providers](#).

The `dsconfig` utility is enhanced to include a new argument `--showKeystorePassword` to retrieve the password for the keystore or truststore. When you run the `dsconfig` utility by passing the `--showKeystorePassword` argument, the password is decrypted and is displayed in clear text on the terminal. You can no longer obtain the password directly from the PIN file. For details about the `--showKeystorePassword` argument, see [dsconfig](#).

Support for FIPS 140-2 and TLS v1.3

This release is compliant with the latest FIPS and TLS standards and versions. For details about FIPS and TLS, see [Enabling FIPS Mode on OUD Server](#) and [Supported System Default TLS Protocols by Oracle Unified Directory](#).

Understanding Bundle Patches

This section describes bundle patches and explains differences between bundle patches, interim patches (also known as patch set exceptions), and patch sets.

- [Stack Patch Bundle](#)
- [Bundle Patch](#)
- [Interim Patch](#)
- [Patch Set](#)

Stack Patch Bundle

Stack patch Bundle deploys the IDM product and dependent FMW patches using a tool. For more information about these patches, see *Quarterly Stack Patch Bundles (Doc ID 2657920.1)* at <https://support.oracle.com>.

Bundle Patch

A bundle patch is an official Oracle patch for Oracle Unified Directory. In a bundle patch release string, the fifth digit indicated the bundle patch number. Effective November 2015, the version numbering format has changed. The new format replaces the numeric fifth digit of the bundle version with a release date in the form "YYMMDD" where:

- YY is the last 2 digits of the year
- MM is the numeric month (2 digits)
- DD is the numeric day of the month (2 digits)

Each bundle patch includes libraries and files that have been rebuilt to implement one or more fixes. All of the fixes in a bundle patch are tested and certified to work with one another. Each bundle patch is cumulative. That is, the latest bundle patch includes all fixes in earlier bundle patches for the same release.

Interim Patch

In contrast to a bundle patch, an interim patch addressed only one issue for a single component. Although each interim patch was an official Oracle patch, it was not a complete product distribution and did not include packages for every component. An interim patch included only the libraries and files that had been rebuilt to implement a specific fix for a specific component.

You may also know an interim patch as: security one-off, exception release, x-fix, PSE, MLR, or hotfix.

Patch Set

A patch set is a mechanism for delivering fully tested and integrated product fixes. A patch set can include new functionality. Each patch set includes the libraries and files that have been rebuilt to implement bug fixes (and new functions, if any). However, a patch set might not be a complete software distribution and might not include packages for every component on every platform. All of the fixes in a patch set are tested and certified to work with one another on the specified platforms.

Bundle Patch Recommendation

Oracle has certified the dependent Middleware component patches for Identity Management products and recommends that Customers apply these certified patches. For more information on these patches, see the note Certification of Underlying or Shared Component Patches for Identity Management Products (Doc ID 2627261.1) at <https://support.oracle.com>.

Bundle Patch Requirements

Before you run OPatch, find the OPatch utility in the Oracle home (ORACLE_HOME) and verify that you have the latest version.

Complete the following steps before you apply the bundle patch:

- Verify that the OPatch version is 13.9.4.2.4 or higher.
 1. Access and log into My Oracle Support at the following location:
<https://support.oracle.com/>
 2. In the Search Knowledge Base field, enter **1587524.1**. This is the ID of the document that describes Using OUI NextGen OPatch 13 for Oracle Fusion Middleware 12c.
 3. In the search results, click the link corresponding to document ID **1587524.1**.
 4. In the document, click the **Patch 28186730** link which will take you to the screen where you can obtain the OPatch 13.9.4.2.4.

- Verify the OUI Inventory:

OPatch needs access to a valid OUI inventory to apply patches. Validate the OUI inventory with the following commands:

Unix

```
$ opatch lsinventory
```

Windows

```
opatch.bat lsinventory
```

If the command throws errors than contact Oracle Support and work to validate and verify the inventory setup before proceeding.

- Confirm the executables appear in your system PATH.

Unix

```
$ which opatch
```

```
$ which unzip
```

Windows

```
where opatch.bat
```

```
where unzip
```

If the command errors out, contact Oracle Support and work to validate and verify the inventory setup before proceeding. If either of these executables do not show in the PATH, correct the problem before proceeding.

- Create a location for storing the unzipped patch. This location will be referred to later in the document as PATCH_TOP.

Before Applying the Bundle Patch

Before you apply the bundle patch for Oracle Unified Directory 12c (12.2.1.4.0), you must set the environment variable and stop all the Directory Server instances and domains.

 **Note:**

You must read about the OUDSM auto redeployment instructions in [Documentation Updates](#) before applying this bundle patch.

 **Note:**

Before applying the bundle patch, you must take a tar backup of the configuration file of an OUD instance.

You must complete the following prerequisites for applying the bundle patch:

1. Set `ORACLE_HOME` environment variable to Oracle Middleware Home Location (under which OUD is installed).

For example:

Unix

```
$ <bash> export ORACLE_HOME="Oracle Middleware Home Location"
```

Windows

```
<prompt> set ORACLE_HOME="Oracle Middleware Home Location"
```

2. Verify that `ORACLE_HOME` is set correctly by running the following command.

Unix

```
ls $ORACLE_HOME/OPatch/opatch
```

Windows

```
dir %ORACLE_HOME%\OPatch\opatch.bat
```

3. Stop all the Directory Server instances and domains where Oracle Unified Directory Services Manager (OUDSM) is installed, depending upon the domain configuration.

Stop Standalone Oracle Unified Directory Server

If you installed Oracle Unified Directory in a Standalone Oracle Unified Directory Server (Managed independently of WebLogic server) mode, stop all the Directory Server instances using the `stop-ds` command.

Unix

```
ORACLE_HOME/INSTANCE_NAME/OUd/bin/stop-ds
```

Windows

```
ORACLE_HOME\INSTANCE_NAME\OUD\bat\stop-ds.bat
```

Stop Collocated Oracle Unified Directory Server

If you installed Oracle Unified Directory in a Collocated Oracle Unified Directory Server (Managed through WebLogic server) mode, complete the following steps:

- a. Stop the OUD instance by running the following command from command line interface.

Unix

```
DOMAIN_HOME/bin/stopComponent.sh INSTANCE_NAME
```

Windows

```
DOMAIN_HOME\bin\stopComponent.bat INSTANCE_NAME
```

- b. Stop the node manager.

Unix

```
DOMAIN_HOME/bin/stopNodeManager.sh
```

Windows

```
DOMAIN_HOME\bin\stopNodeManager.cmd
```

- c. Stop the Oracle WebLogic Administration Server.

Unix

```
DOMAIN_HOME/bin/stopWebLogic.sh
```

Windows

```
DOMAIN_HOME\bin\stopWebLogic.cmd
```

Stop the Oracle Directory Integration Platform and OUDSM Configured in a Single Domain

If you added OUDSM and Oracle Directory Integration Platform in a single domain, you must stop the Admin Server and Managed Server.

- a. Stop the Oracle Directory Integration Platform Managed Server:

Unix

```
DOMAIN_HOME/bin/stopManagedWebLogic.sh
```

Windows

```
DOMAIN_HOME\bin\stopManagedWebLogic.cmd
```

- b. Stop the Oracle WebLogic Administration Server:

Unix

```
DOMAIN_HOME/bin/stopWebLogic.sh
```

Windows

```
DOMAIN_HOME\bin\stopWebLogic.cmd
```

Note:

See [Understanding the Oracle Unified Directory Installation Directories](#) to know about OUD installation directories.

Using the Oracle Patch Mechanism (Opatch)

Use OPatch to perform the necessary steps for applying a patch to an Oracle home.

Note:

You must have the latest version of Opatch (version 13.9.4.2.4) from [My Oracle Support](#). Opatch requires access to a valid Oracle Universal Installer (OUI) Inventory to apply patches.


The patching process uses both unzip and Opatch executables. After sourcing the `ORACLE_HOME` environment, Oracle recommends that you confirm that both of these exist before patching. Opatch is accessible at:

```
$ORACLE_HOME/OPatch/opatch
```

When Opatch starts, it validates the patch to ensure there are no conflicts with the software already installed in your `$ORACLE_HOME`:

- If you find conflicts with a patch already applied to the `$ORACLE_HOME`, stop the patch installation and contact Oracle Support Services.
- If you find conflicts with a subset patch already applied to the `$ORACLE_HOME`, continue Bundle Patch application. The subset patch is automatically rolled back before installation of the new patch begins. The latest Bundle Patch contains all fixes from the previous Bundle Patch in `$ORACLE_HOME`.

This Bundle Patch is not `-auto` flag enabled. Without the `-auto` flag, no servers need to be running. The Machine Name & Listen Address can be blank on a default install.

 **See Also:**
[Patching with OPatch](#)

Identifying the Version of OPatch Included with Oracle Unified Directory 12c

In general, there is a version of OPatch available for each version of the Oracle Universal Installer software.

To identify the version of OPatch:

1. Change directory to the following directory:

```
cd ORACLE_HOME/OPatch/
```

2. Run the following command:

```
./opatch version
```

For example:

```
./opatch version  
OPatch Version: 13.9.4.2.4  
  
OPatch succeeded.
```

Applying the Bundle Patch

Unzip the patch zip file and run OPatch to apply the patch.

To apply the bundle patch, complete the following steps:

1. Unzip the patch zip file into the `PATCH_TOP`, where `PATCH_TOP` is a directory path that temporarily contains the patch for installation.

Unix

```
$ unzip -d PATCH_TOP p32730494_122140_Generic.zip
```

Windows

```
unzip -d PATCH_TOP p32730494_122140_Generic.zip
```


 **Note:**

On Windows, the unzip command has a limitation of 256 characters in the path name. If you encounter this, use an alternate ZIP utility such as 7-Zip to unzip the patch. For example, run the following command to unzip using 7-Zip:

```
"c:\Program Files\7-Zip\7z.exe" x
p32730494_122140_Generic.zip
```

2. Set your current directory to the directory where the patch is located. For example:

Unix

```
$ cd PATCH_TOP/32730494
```

Windows

```
cd PATCH_TOP\32730494
```

3. Run OPatch to apply the patch.

Unix

```
$ [ORACLE_HOME]/OPatch/opatch apply
```

Windows

```
[ORACLE_HOME]\OPatch\opatch.bat apply
```

ORACLE_HOME

- Conflicts with a patch already applied to the ORACLE_HOME.
In this case, stop the patch installation, and contact Oracle Support Services.
- Conflicts with subset patch already applied to the ORACLE_HOME.
In this case, continue the install, as the new patch contains all the fixes from the existing patch in the ORACLE_HOME.

After Applying the Bundle Patch

You need to perform certain tasks after applying the bundle patch.

Perform the following steps after applying the bundle patch:

1. Verify if the Oracle Unified Directory installation has been patched by running the `start-ds` command.

For example:

Unix

```
$ [ORACLE_HOME]/<dsInstanceName>/OUD/bin/start-ds -F
```

Windows

```
[ORACLE_HOME]\<dsInstanceName>\OUD\bat\start-ds.bat -F
```

Note:

OID patch version can be determined from the output, based on the values for Build ID, Platform Version and Label Identifier fields.

2. Upgrade Oracle Unified Directory server instances that are associated with the ORACLE_HOME directory.

For example:

Unix

```
$ [ORACLE_HOME]/<OUD-Instance-Path>/OUD/bin/start-ds --upgrade
```

Windows

```
[ORACLE_HOME]/<OUD-Instance-Path>\OUD\bat\start-ds.bat --upgrade
```

The preceding step is executed to upgrade OUD instance according to the patched version of OUD in ORACLE_HOME. If start-ds is executed to start OUD instance without executing start-ds --upgrade, following message will be displayed: Instance needs to be upgraded. Please run the start-ds command with the option "--upgrade"

3. Restart all the Directory Server instances depending upon the domain configuration.

Restart Standalone Oracle Unified Directory Server

If you installed Oracle Unified Directory in a Standalone Oracle Unified Directory Server (Managed independently of WebLogic server) mode, restart all the Directory Server instances using the start-ds command. For example:

Unix

```
$ [ORACLE_HOME]/<dsInstanceName>/OUD/bin/start-ds
```

Windows

```
[ORACLE_HOME]\<dsInstanceName>\OUD\bat\start-ds.bat
```

Restart Collocated Oracle Unified Directory Server

If you installed Oracle Unified Directory in a Collocated Oracle Unified Directory Server (Managed through WebLogic server) mode, complete the following steps:

- a. Restart the Oracle WebLogic Administration Server.

Unix

```
DOMAIN_NAME/bin/startWebLogic.sh
```

Windows

```
DOMAIN_HOME\bin\startWebLogic.cmd
```

- b. Start the node manager.

Unix

```
$DOMAIN_NAME/bin/startNodeManager.sh
```

Windows

```
DOMAIN_HOME\bin\startNodeManager.cmd
```

- c. Start the OUD instance by running the following command from command line interface.

Unix

```
startComponent.sh INSTANCE_NAME
```

For example:

```
$DOMAIN_HOME/bin/startComponent.sh oud1
```

where `oud1` is the instance name/server name created using WLST

Windows

```
startComponent.bat INSTANCE_NAME
```

For example:

```
DOMAIN_HOME\bin\startComponent.bat oud1
```

where `oud1` is the instance name/server name created using WLST

4. If you created and configured a Weblogic domain for OUDSM then you must restart the Administration Server. Allow the application server instance to redeploy the new `oudsm.ear` file in the patch.

 **Note:**

On WebLogic, start the Administration Server (the WebLogic domain used for OUDSM).

See OUDSM Auto Redeployment Instructions in [New Features and Enhancements in OUD Bundle Patch 12.2.1.4.210406](#).

5. If you added OUDSM and Oracle Directory Integration Platform in a single domain, you must start the Admin Server and Managed Server.
 - a. Restart the Oracle WebLogic Administration Server.

Unix

```
DOMAIN_HOME/bin/startWebLogic.sh
```

Windows

```
DOMAIN_HOME\bin\startWebLogic.cmd
```

- b. Start the Oracle Directory Integration Platform Managed Server:

Unix

```
DOMAIN_HOME/bin/startManagedWebLogic.sh <wls_ods1>  
<ADMIN_SERVER_URL>
```

Windows

```
DOMAIN_HOME\bin\startManagedWebLogic.cmd <wls_ods1>  
<ADMIN_SERVER_URL>
```

Where `managed_server_name` specifies the name of the Managed Server (The default value is `wls_ods1`.) and `admin_url` specifies the listen address (host name, IP address, or DNS name) and port number of the domain's Administration Server.

6. You may need to update `Config.ldif` file to remove PIN file.
 - a. The attributes `ds-cfg-key-store-pin-file`, `ds-cfg-trust-store-pin-file`, and `ds-cfg-key-pin-file` are not removed for an upgraded instance for backward compatibility. You will see a warning during upgrade process stating that those attributes are still populated. Use `dsconfig` to remove the value of the attributes after upgrade has been done successfully.
 - b. If a truststore configuration entry does not have its pin attribute populated then you will see a warning during upgrade and server startup. Use `dsconfig` to update the pin attribute with the password of the truststore to prevent those warnings.

- c. While creating a new instance with SSL port disabled, the default configuration entry for any disabled keystore or truststore would still have attribute `ds-cfg-key-store-pin-file` populated. This can be ignored. Whenever you enable that keystore or truststore then you will have to reset the pin-file attribute. You need to provide the pin of the keystore or truststore by using the pin attribute only.

Creating the File based Access Control Log Publisher

This step is optional. You can create a File Based Access Control Log publisher for diagnosing ACI evaluation. This publisher should be disabled as soon as diagnostic is over as it impacts server performance.

Note:

Once this publisher is created, the de-installation of this patch will not be possible as the server would no longer be able to start.

To create the File Based Access Control Log publisher, a server administrator must invoke the following `dsconfig` command against a server instance that is already up and running:

```
dsconfig create-log-publisher \  
  --publisher-name "ACI logger" \  
  --type file-based-access-control \  
  --set enabled:true \  
  --set log-file:logs/acilog \  
  --hostname serverHostName --port 4444 \  
  --trustAll --bindDN cn=Directory\ Manager \  
  --bindPasswordFile passwordFile \  
  --no-prompt
```

The following entry is created in the `config.ldif`: server configuration file:

```
dn: cn=ACI logger,cn=Loggers,cn=config  
  objectClass: ds-cfg-log-publisher  
  objectClass: ds-cfg-access-control-log-publisher  
  objectClass: ds-cfg-file-based-access-control-log-publisher  
  objectClass: top  
  ds-cfg-enabled: true  
  ds-cfg-java-class:  
org.openserver.loggers.accesscontrol.TextAccessControlLogPublisher  
  ds-cfg-asynchronous: true  
  cn: ACI logger  
  ds-cfg-log-file-permissions: 640  
  ds-cfg-log-file: logs/acilog
```

Removing the Bundle Patch

If you experience any problems after installing the bundle patch, you can remove the bundle patch.

Execute the following commands to remove the bundle patch:

1. Set the `ORACLE_HOME` environment variable for Oracle Middleware Home Location (Where Oracle Unified Directory is installed).

Unix

```
$ <bash> export ORACLE_HOME="Oracle Home Location"
```

Windows

```
<prompt> set ORACLE_HOME="Oracle Home Location"
```

2. Verify the OUI inventory by running the following command:

Unix

```
$ [ORACLE_HOME]/OPatch/opatch lsinventory
```

Windows

```
[ORACLE_HOME]\OPatch\opatch.bat lsinventory
```

3. Run `OPatch` to deinstall the patch:

Unix

```
$ [ORACLE_HOME]/OPatch/opatch rollback -id 32730494
```

Windows

```
[ORACLE_HOME]\OPatch\opatch.bat rollback -id 32730494
```

4. In the case of a Directory Server instance created after the application of this patch, once the patch is removed, the instance `buildinfo` still looks like:

```
$ cat [ORACLE_HOME]/<dsInstanceName>/OUD/config/buildinfo  
12.2.1.4.210406.2104060218
```

5. The instance `buildinfo` must be manually changed back:

```
$ cp [ORACLE_HOME]/oud/config/buildinfo [ORACLE_HOME]/  
<dsInstanceName>/OUD/config/buildinfo
```

For example,

```
$ cat [ORACLE_HOME]/<dsInstanceName>/OUD/config/buildinfo  
12.2.1.4.210406.2104060218
```

6. After removing the bundle patch, start the OUD instance by running the following command:

Unix

```
$ [ORACLE_HOME]/<dsInstanceName>/OUD/bin/start-ds
```

Windows

```
[ORACLE_HOME]\<dsInstanceName>\OUD\bat\start-ds.bat
```

Post Action After Rollback

After roll-backup, restore configuration and schema from the backup before you start an OUD instance. Normally after rolling back, OUD would be on base version (12.2.1.4). So, you need to apply the previous OUD Bundle Patch again.

Resolved Issues

This section lists the issues resolved in 12c (12.2.1.4.0) Release.

- [Resolved Issues in OUD Bundle Patch \(12.2.1.4.210406\)](#)
- [Resolved Issues in OUD Bundle Patch \(12.2.1.4.200827\)](#)
- [Resolved Issues in OUD Bundle Patch \(12.2.1.4.200526\)](#)
- [Resolved Issues in OUD Bundle Patch 12.2.1.4.200204](#)

Resolved Issues in OUD Bundle Patch (12.2.1.4.210406)

The following table lists the issues resolved in OUD Bundle Patch 12.2.1.4.210406:

Table 1-1 Issues Resolved in 12c Release (12.2.1.4.210406)

Bug Number	Description
32562107	ODSEE-ODU 12.2.1.4 CERTIFICATES GET CORRUPTED THROUGH THE REPLICATION GATEWAY
25471403	FIX FOR 25471403
31851470	ODU 12C: ISMEMBER SEARCH RECEIVES STACKOVERFLOWERROR
29651080	REPLICATION SUMMARY SHOWS INCORRECT DATA WITH OEM13C AND OUD 12.2.1.3.0
31745920	ODU UNION PROXY SEARCHES RECEIVE A RESULT=4 WHEN PAGE-SIZE=0 FOR WFE
30513440	SUPPORT PASSWORD VALIDATORS AND GENERATORS IN SUBENTRY PASSWORD POLICY

Table 1-1 (Cont.) Issues Resolved in 12c Release (12.2.1.4.210406)

Bug Number	Description
29530047	PASSWORD VISIBLE IN ACCESS LOG FOR DB WORKFLOWS
32547317	FORWARD MERGE OF BUG 29376960 TO MAIN VIEW
32208265	CRYPTO MANAGER ORDERS CIPHERS ALPHABETICALLY (DIFFERENT THEN OTHER SSL HANDLERS)
32065140	REPLICATION IGNORES SCHEMA VIOLATION
31546491	CPU SPIKES AND UTILIZATION RESULTING IN TIMETHREAD ERROR
31878749	STACKING TRANSFORMATIONS MODIFY OPERATION FAILS
31931564	ODU 12C - LOG-CONNECTION-DETAILS CONFIG INCORRECTLY SHOWING IN FILE BASED AUDIT LOGGER MENU
32019006	SUPPORTING PWDMINLENGTH IN PASSWORD POLICY AT SUBENTRY LEVEL
30666508	NPE WHEN EXECUTING LDAPSEARCH ON OUD PROXY WITH PAGESIZE SET IN LDAPSERVEREXTENSION
31666925	THE OUD-SETUP SCRIPT DOES NOT RECOGNIZE A EXABYTE FS

Resolved Issues in OUD Bundle Patch (12.2.1.4.200827)

The following table lists the issues resolved in OUD Bundle Patch 12.2.1.4.200827:

Table 1-2 Issues Resolved in 12c Release (12.2.1.4.200827)

Bug Number	Description
28401694	ADD OPTION FOR ADDITIONAL BINDDN, CLIENTIP, AND PROTOCOL TO LOGGERS
29868285	OU DSM CRASHES WHEN ACCESSING CORE CONFIG, WITH LATEST BP 28569189
30386441	(JE 7.0.7) INTERRUPTED EXCEPTION MAY CAUSE INCORRECT INTERNAL STATE
30403293	CANNOT UPGRADE 11G BECAUSE OF THE "DS-CFG-FETCH-AUTHENTICATED-USER" PROPERTY
30767720	EXCLUDE SEARCH FILTER IN WORKFLOW CONFIG RETURNS RESULT: 50 OR 80
30832284	ODU 12C VIRTUAL ATTRIBUTE SUB CONTAINER PASSWORD POLICY INCONSISTENTLY APPLIED

Table 1-2 (Cont.) Issues Resolved in 12c Release (12.2.1.4.200827)

Bug Number	Description
30871004	OLD 12.2.1.4 RETURN-BIND-ERROR-MESSAGES=TRUE NOT WORKING
30963266	OLD 12C PASSWORD INVALID WHEN USING BRACE SPECIAL CHARACTER
31013245	ER OLD - S_CONN VALUES IN PROXY ACCESS LOGS SHOULD SHOW HOSTNAME OF DS SERVER
31239817	UNION WF DOES NOT SHOW OUTPUT IN DATA BROWSER TAB OF OUDSM
31246776	OLD12CPS4: COMPLEX QUERIES USING NONEXISTING GROUP MEMBERSHIP RETURN ALL USERS
31336975	UNABLE TO ADD OR MODIFY OBJECT CLASSES AND ATTRIBUTES TO OLD 12C PS4
31377876	REBUILD-INDEX DISABLES BACKEND WHEN USING MIXED DEFINED/NOTDEFINED ATTRIBUTES
31490532	OLD 12CPS4 JULY2020 BP - UPGRADE OF 12CPS3JULY'20 BP OLD DS INSTANCE TO 12CPS4JULY'20 BP IS FAILING

Resolved Issues in OUD Bundle Patch (12.2.1.4.200526)

The following table lists the issues resolved in OUD Bundle Patch 12.2.1.4.200526:

Table 1-3 Issues Resolved in 12c Release (12.2.1.4.200526)

Bug Number	Description
29971908	OLD 12C - DSREPLICATION STATUS IGNORES -I ADMINUID WHEN SPECIFIED VIA CLI
30668734	UNABLE TO USE UNDERSCORES IN DNS
30012998	SETTING DEPRECATED PASSWORD STORAGE SCHEME AND ADMIN PWD RESET CLEARS PWDRESET
28467589	START-DS IN DMZ SLOW
30854158	CODE CORRECTION FOR BUG 29676093
29757041	OLD 12C: DIGEST-MD5 SASL AUTH FAILS WITH LDAP 80 IF SEARCHING JOIN VIEW CONTEXT
30651541	OLD 12C - CUSTOM PASSWORD POLICY AND VALIDATOR IGNORED ON ACCOUNT CREATION

Table 1-3 (Cont.) Issues Resolved in 12c Release (12.2.1.4.200526)

Bug Number	Description
30440259	OLD INVALID PWDGRACEUSETIME ATTRIBUTE CREATED BY EUS.
30521914	AFTER INITIALIZATION THE RGW STATUS SHOWS AS "BAD DATA SET"
30534318	OLD 11G: HIGH CPU AND CAUSING LOSS OF SERVICE
29026772	ISSUE WITH FORCE-CHANGE-ON-ADD AFTER APPLYING BUNDLE PATCH 11.1.2.3.181016

Resolved Issues in OUD Bundle Patch 12.2.1.4.200204

The following table lists the issues resolved in OUD Bundle Patch 12.2.1.4.200204:

Table 1-4 Issues Resolved in OUD Bundle Patch 12.2.1.4.200204:

Bug Number	Description
30645038	OLD 12.2.1.3 JAN'20 BP - COUPLE OF NEWLY ADDED CORE-ENTRYCACHE TESTS FAILING IN FARM EXECUTION
30265103	OLD11G - BEFORE BP DS-RLIM-IDLE-TIME-LIMIT ATT. WAS IN SECS AFTER BP IS MS
30367492	UNINSTALL FAILS DUE TO RESOLVING HOST TO 0.0.0.0
29885985	OLD ALLOWS ADDING USER INTO GROUP EVEN IF USER DOESN'T EXIST WHEN RI IS ENABLED
29661762	CUSTOM PASSWORD POLICIES REQUIRE A INDIVIDUAL "PASSWORDSTORAGESCHEME"
30074000	Fix for Bug 30074000
29682036	FORKJOIN WFE WITH LEFT-OUTER-JOIN DOES NOT WORK
28135591	UNABLE TO SPECIFY A DENIED-CLIENT HOSTNAME THAT BEGINS WITH A NUMERIC VALUE
29945677	ISMEMBEROF SUBSTRING SEARCH FILTER RETURNS NO ENTRIES
30094884	REGRESSION FOR BUG 29724794
29418242	(JE 7.0.7) ENVIRONMENT MUST BE CLOSED, CAUSED BY: COM.SLEEPYCAT.JE.THREADINTERRU

Known Issues and Workarounds

For known issues and workarounds, log in to [My Oracle Support](#), and then search for 2602696.1, which is the ID of the document, Oracle Fusion Middleware 12.2.1.4.0 Known Issues.

For Known Issues specific to Oracle Unified Directory Bundle Patches, search for Doc ID 2636943.1 in [My Oracle Support](#).

For information about OPatch issues, log in to [My Oracle Support](#) and use the OPatch version provided with the product.

Related Documents

For more information, see the following resources:

- [Oracle Fusion Middleware Documentation](#)
This contains documentation for all Oracle Fusion Middleware 12c products.
- [Oracle Technology Network](#)
This site contains additional documentation that is not included as part of the documentation libraries.

Documentation Accessibility

For information about Oracle's commitment to accessibility, visit the Oracle Accessibility Program website at <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=docacc>.

Access to Oracle Support

Oracle customers that have purchased support have access to electronic support through My Oracle Support. For information, visit <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=info> or visit <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=trs> if you are hearing impaired.

Oracle Fusion Middleware Oracle Unified Directory Bundle Patch Readme, 12c (12.2.1.4.210406)

F41558-02

Copyright © 2021, Oracle and/or its affiliates. All rights reserved.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this is software or related documentation that is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, then the following notice is applicable:

U.S. GOVERNMENT END USERS: Oracle programs (including any operating system, integrated software, any programs embedded, installed or activated on delivered hardware, and modifications of such programs) and Oracle computer documentation or other Oracle data delivered to or accessed by U.S. Government end users are "commercial computer software" or "commercial computer software documentation" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, reproduction, duplication, release, display, disclosure, modification, preparation of derivative works, and/or adaptation of i) Oracle programs (including any operating system, integrated software, any programs embedded, installed or activated on delivered hardware, and modifications of such programs), ii) Oracle computer documentation and/or iii) other Oracle data, is subject to the rights and limitations specified in the license contained in the applicable contract. The terms governing the U.S. Government's use of Oracle cloud services are defined by the applicable contract for such services. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

Oracle, Java, and MySQL are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Inside are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. AMD, Epyc, and the AMD logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark of The Open Group.

This software or hardware and documentation may provide access to or information about content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services unless otherwise set forth in an applicable agreement between you and Oracle. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services, except as set forth in an applicable agreement between you and Oracle.

This documentation is in pre-General Availability status and is intended for demonstration and preliminary use only. It may not be specific to the hardware on which you are using the software. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to this documentation and will not be responsible for any loss, costs, or damages incurred due to the use of this documentation.

The information contained in this document is for informational sharing purposes only and should be considered in your capacity as a customer advisory board member or pursuant to your pre-General Availability trial agreement only. It is not a commitment to deliver any material, code, or functionality, and should not be relied upon in making purchasing decisions. The development, release, timing, and pricing of any features or functionality described in this document may change and remains at the sole discretion of Oracle.

This document in any form, software or printed matter, contains proprietary information that is the exclusive property of Oracle. Your access to and use of this confidential material is subject to the terms and conditions of your Oracle Master Agreement, Oracle License and Services Agreement, Oracle PartnerNetwork Agreement, Oracle distribution agreement, or other license agreement which has been executed by you and Oracle and with which you agree to comply. This document and information contained herein may not be disclosed, copied, reproduced, or distributed to anyone outside Oracle without prior written consent of Oracle. This document is not part of your license agreement nor can it be incorporated into any contractual agreement with Oracle or its subsidiaries or affiliates.