

Oracle® Argus Mart
Installation and Administration Guide
Release 8.2
E96567-01

August 2018

Oracle Argus Mart Installation and Administration Guide, Release 8.2

E96567-01

Copyright © 2011, 2018, Oracle and/or its affiliates. All rights reserved.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this is software or related documentation that is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, then the following notice is applicable:

U.S. GOVERNMENT END USERS: Oracle programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, delivered to U.S. Government end users are "commercial computer software" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, shall be subject to license terms and license restrictions applicable to the programs. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Xeon are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. AMD, Opteron, the AMD logo, and the AMD Opteron logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark of The Open Group.

This software or hardware and documentation may provide access to or information about content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services unless otherwise set forth in an applicable agreement between you and Oracle. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services, except as set forth in an applicable agreement between you and Oracle.

Contents

Contents iii

Preface	vii
Where to Find More Information.....	vii
Documentation Accessibility	vii
Part I Installation	
1 Install the Argus Mart Application	
1.1 Before Installing the Argus Mart Application	1-1
1.2 Install the Argus Mart Components.....	1-2
2 Create the Argus Mart Database Structure	
2.1 Overview of the dbinstaller.properties file	2-1
2.2 Install Argus Mart.....	2-3
2.2.1 Prerequisites	2-3
2.2.2 Create User for the Argus Safety Database.....	2-4
2.2.3 Create the Install User	2-4
2.2.4 Create a Fresh Argus Mart Schema.....	2-5
2.2.5 Validate the Schema	2-7
2.3 Create Database Links.....	2-7
2.3.1 From Argus Mart to Argus Safety (manually)	2-8
2.3.2 From Argus Mart to Argus Insight	2-8
2.4 Create Argus Mart Read-only User.....	2-9
3 Create Multiple Enterprises in Multi-tenant Environment	
4 Configure ODI Settings	
4.1 Minimum Components Required	4-1
4.2 Install and Configure ODI	4-1
4.3 Create and Test the Data Server Connection	4-4
4.4 Create a New Physical Schema	4-5
4.5 Set Up the Physical Agent for Context CTX_ARGUSMART	4-6
4.6 Validate the Load Plan	4-6

5 Configure the Argus Mart Application

6 Upgrade Argus Mart

6.1	Prepare for the Database Upgrade	6-1
6.2	Upgrade the Database	6-1

7 Extract, Transform, and Load Data

7.1	Manage Initial ETL Process: ODI Studio	7-1
7.1.1	Run the ETL	7-2
7.1.2	Stop the ETL	7-3
7.1.3	Restart the ETL	7-3
7.1.4	Process a Failed ETL	7-5
7.1.4.1	Continue the Failed Initial ETL	7-5
7.1.4.2	Restart the Failed Initial ETL	7-5
7.2	Monitor Initial ETL Process: ODI Studio	7-6
7.2.1	View the Steps of Load Plan	7-6
7.2.2	Monitor the ETL	7-6
7.2.3	Debug the Failed ETL	7-7
7.2.4	Monitor the Restarted ETL (Resume)	7-8
7.3	Manage Initial ETL Process: ODI Console	7-9
7.3.1	Run the Initial ETL	7-9
7.3.2	Stop the Initial ETL	7-10
7.3.3	Restart the Initial ETL	7-11
7.3.4	Process a Failed ETL	7-11
7.3.4.1	Continue the Failed Initial ETL	7-12
7.3.4.2	Restart the Failed Initial ETL	7-12
7.4	Monitor Initial ETL Process: ODI Console	7-12
7.4.1	View the Steps of Load Plan	7-12
7.4.2	Monitor the ETL	7-12
7.4.3	Debug the Failed ETL	7-13
7.4.4	Monitoring the Restarted ETL (Resume)	7-13
7.5	Run the Incremental ETL	7-14

8 Uninstall the Argus Mart Application

Part II Administration

9 Set Up Context in a Multi-tenant Environment

10 Secure Unblinding in Argus Mart

11 Rebuild a Case in Argus Mart

12 Work with Incremental ETL in ODI Studio

12.1	Schedule an Incremental ETL	12-1
------	-----------------------------------	------

12.2	Monitor the Incremental ETL Process.....	12-2
12.3	Manage the Incremental ETL Process.....	12-2
12.3.1	Run the Incremental ETL.....	12-2
12.3.2	Run the Incremental ETL with Clear Cache	12-3
12.3.3	Stop the Incremental ETL	12-5
12.3.4	Restart the Incremental ETL.....	12-6
12.3.5	Process a Stopped or a Failed ETL	12-6
12.3.5.1	Continue the Failed Incremental ETL.....	12-7
12.3.5.2	Restart the Failed Incremental ETL.....	12-7
13	Work with Incremental ETL in ODI Console	
13.1	Schedule an ETL.....	13-1
13.2	Monitor the Incremental ETL Process.....	13-1
13.3	Manage the Incremental ETL Process.....	13-1
13.3.1	Run the Incremental ETL.....	13-1
13.3.2	Stop the Incremental ETL	13-2
13.3.3	Restart the Incremental ETL.....	13-3
13.3.4	Process a Stopped or a Failed ETL	13-3
14	Re-initialize the ETL Process	
15	Troubleshooting	
15.1	Dictionary Reload Error	15-1
15.2	ETL Execution Pre-Requisite Check Failed Error	15-2
15.3	FR Consistency Log Error.....	15-3
15.4	MedDRA Mismatch Error	15-3
15.5	Multiple Enterprise Creation Messages.....	15-4
15.5.1	Source Enterprise Does Not Exist In Mart	15-4
15.5.2	Enterprise Does Not Exist In Argus Safety	15-4
15.5.3	Enterprise Does Not Exist For Configuration In Mart	15-5
15.6	SMQ-CMQ Loop Error.....	15-5
A	Configure Standalone Installation Topology for Standalone Agent	
A	Prerequisite	A-1
A	To configure a standalone agent:.....	A-1
B	Configure Standard Installation Topology for Java EE Agent	
B	Prerequisite	B-1
B	To configure a Java EE agent:.....	B-1

Preface

Oracle Argus Mart (AM) is a data source software product that can be used for analysis and reporting in medical product safety and pharmacovigilance. The primary data for Argus Mart are the adverse event cases managed by Oracle Argus Safety. Argus Mart product consists of:

- A pre-defined Argus Mart data model containing Signal and Reporting tables
- Pre-built ODI based interfaces that are linked to Oracle PL/SQL based packages

Argus Safety serves as the primary source of data for Argus Mart. The ODI software extracts the data from Argus Safety database, transforms, and loads the data into Argus Mart. When the ODI tool loads the data into Argus Mart, it is available for Argus Mart users for querying, and reporting activities.

Where to Find More Information

Oracle Help Center

The latest user documentation for Oracle Health Sciences products is available at <http://docs.oracle.com/en/industries/health-sciences/>.

My Oracle Support

The latest release notes, patches and white papers are on My Oracle Support (MOS) at <https://support.oracle.com>. For help with using MOS, see https://docs.oracle.com/cd/E74665_01/MOSHPTOC.htm.

Documentation Accessibility

For information about Oracle's commitment to accessibility, visit the Oracle Accessibility Program website at <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=docacc>.

Access to Oracle Support

Oracle customers that have purchased support have access to electronic support through My Oracle Support. For information, visit <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=info> or visit <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=trs> if you are hearing impaired.

Part I

Installation

This part of the guide introduces you with the Oracle Argus Mart software product. In addition, it also gives you an outline of all the tasks that are required to install and configure Oracle Argus Mart, and explains the organization of these tasks in this guide. The Oracle Argus Mart is referred to as AM and Oracle Data Integrator as ODI in all the later sections of the guide.

Install the Argus Mart Application

This chapter explains how to use the installation wizard to install Argus Mart, including ODI Repository and the Schema Creation Tool.

1.1 Before Installing the Argus Mart Application

- Verify that the Argus Mart database instance has been created and is running. In addition, verify that the database has been created using the character set of your Argus Safety database.
- You must install the required software components, as mentioned in the following table:

Table 1–1 Argus Mart Software Requirements

Specification	Oracle Data Integrator Server	Database	DBInstaller	Client
Operating System	As certified by the ODI	As certified by the ODI (Supports both CDB-PDB/Non CDB)	Microsoft Windows Server 2012 Standard Microsoft Windows Server 2012 R2 Standard	Windows 2016 Standard Windows 10 Windows 8.1 Windows 7 (Both 32 and 64 bit)
Oracle Database		Oracle RAC Exadata 12c R1 (with 12.1.0.2 or 12.2.0.1) Oracle 12c (12.1.0.2 or 12.2.0.1) (Standard Edition 2 (SE2)/Enterprise Edition) Note: Oracle database Standard Edition 2 (SE2) is supported for single tenant deployment only.		
Oracle Data Integrator (ODI)	12.2.1.3			

Note: Oracle Client Patch required for the Schema Creation Tool

1. Download the patch 21821214: WINDOWS DB BUNDLE PATCH 12.1.0.2 from the Oracle Support.
 2. Install the patch, and apply the following workaround:
 - a. Set the **oracle_home** as your client home location. For example:
`SET ORACLE_HOME=C:\app\client32\product\12.1.0\client_1`
 - i. On the client machine, go to %oracle_home%\bin\
 - ii. From \p21821214_121020_WINNT\21821214\files\bin\, copy the file **oranfsodm12.dll**, and paste it under %oracle_home%\bin
 - b. Run **sqlldr help=y** or **sqlldr.exe**.
-

- Make sure that you have installed the following software on the machine where Argus Mart is being installed:
 - Microsoft .NET 3.5 Framework
 - Oracle Client 12.1.0.2 or 12.2.0.1 (Administrator Installation type)

Only one version of Oracle Client should be installed on the server. Argus Mart Installer will not work in case there are multiple versions of Oracle Client are installed on the same machine.

1.2 Install the Argus Mart Components

To run the installation wizard and install the Argus Mart components:

1. Log in to the Argus Mart Server as a user with administrator privileges.
2. Download the Argus Mart software from Oracle E-delivery and copy the software to the Argus Mart Server.
3. Click **setup.exe**.

The Welcome screen of the installation wizard appears with the following options:

- a. **About Oracle Universal Installer**—Specifies information about the Oracle Universal Installer.
 - b. **Installed Products**—Displays the list of installed products.
4. On the Welcome screen, click **Next**.

The Specify Home Details screen appears.

5. In the **Name** field, enter the name for the product installation.
6. In the **Path** field, specify the location of the folder where the Argus Mart will be installed.
 - To install Argus Mart into the default folder, click **Next**.
 - To install Argus Mart into a different folder, click **Browse**, select another folder, and click **Next**.

The Oracle Home Location screen appears.

7. Click **Browse**, and navigate to the location of Oracle Home that identifies the TNSNAMES.ORA file.

Example: C:\app\product\11.2.0\client_1

8. Click Next.

The Database Details screen appears.

9. Enter the following parameters:

- In the **AM Database Server** field, enter name or IP address.
- In the **AM Database Instance** field, enter the database instance name.
- In the **AM Database Port** field, enter the database listener port number.

When the Installation process is complete, you may validate these database inputs by navigating to the **TNSNAMES.ORA** file, saved at the following path:

<ORACLE_HOME>\NETWORK\ADMIN

10. Click Next.

The Summary screen appears.

11. Click Install to start the installation.

A message appears — Argus Mart is configuring your new software.

When installation is complete, the End Of Installation screen appears.

12. To verify the successful installation of Argus Mart, click Installed Products.

The Inventory screen appears.

13. Navigate to Contents > Independent Products.

Oracle Argus Mart appears in the list of products.

14. Click Close.

15. Click Exit.

A confirmation dialog box appears.

16. Click Yes to close the Installer wizard screen.

Create the Argus Mart Database Structure

The Argus Mart is now installed in silent-mode through Liquibase.

Liquibase is a refactoring tool that enables Argus Mart to be in synchronization with the closest major release, and subsequently upgrades the product to the required minor versions of the product

The Argus Mart Liquibase install enables you to create the Argus Mart schema structure. It creates a link between the safety database and the new Argus Mart database. The Extract, Transform, and Load (ETL) process uses this link to transfer data from source (Argus Safety) database to the Argus Mart database. When transferred, this data can be used for querying and reporting purposes.

2.1 Overview of the dbinstaller.properties file

Open the DBInstaller\dbinstaller.properties file, and view or modify the following parameters to make sure that Liquibase runs properly.

Parameter	Description	Modify	Default or Sample Value
db_connect_string	Jdbc Url to connect to the Target Database.	Yes	url=abc.in.oracle.com:1521/AM82DB Or, url=abc.in.oracle.com:1521/AM82DB.IN.ORACLE.COM
dba_User	Name of the Target Database DBA user	Yes	dba_User=am_dba_user
logLevel	Log level setting related to liquibase for smooth run. Possible values: <ul style="list-style-type: none"> ■ DEBUG ■ INFO 	Yes	logLevel=info
appSchema_sm_mart	Argus Mart schema Owner name and password	No	appSchema_mart_user=am_mart/pwd
appSchema_sm_stage	Argus Mart Staging schema Owner	No	appSchema_sm_stage=am_stage
appSchem_sm_app	Argus ILinkMart Application schema Owner name and password	No	appSchema_sm_app=am_app/pwd

Parameter	Description	Modify	Default or Sample Value
appSchema_etl_user	Argus Mart Etl User and password	No	appSchema_etl_user=am_etl/pwd
appSchema_ri_s_user	Argus Mart VPD schema Owner name and password	No	appSchema_ri_s_user=am_vpd/pwd
appSchema_bi_user	Argus Mart BI schema Owner name and password	No	appSchema_bi_user=am_bi/pwd
#Mart Database Role am_vpd_admin_role	Admin role given to AM_ETL_USER	Yes	am_vpd_admin_role=AM_VPD_ADMIN_ROLE
Safety_db	Argus Safety Database TNS	Yes	safety_db=SAF82DB or safety_db=SAF82DB.US.EXAMPLE.COM
Safety_RO_User	Argus Mart read-only user name in Argus Safety	Yes	Safety_RO_User=am_ro_user
#Datafile directory location	Location of the default datafiles directory.	Yes	default_datafile_destination= <i>c:/app/oradata/AM82DB</i>
#Argus Mart Stage User Datafiles	Location of Argus Mart stage user datafiles.	Yes	<ul style="list-style-type: none"> ■ stage_data_ts_ datafile=C:\app\oradata\AM81MTF2\AM_STAGE_DATA_01.DBF ■ stage_ind_ts_ datafile=C:\app\oradata\AM81MTF2\AM_STAGE_INDEX_01.DBF ■ stage_lob_ts_ datafile=C:\app\oradata\AM81MTF2\AM_STAGE_LOB_01.DBF
#Argus Mart > Mart User Datafiles	Location of Argus Mart > Mart user datafiles.	Yes	<ul style="list-style-type: none"> ■ mart_data_ts_ datafile=C:\app\oradata\AM81MTF2\AM_MART_DATA_01.DBF ■ mart_ind_ts_ datafile=C:\app\oradata\AM81MTF2\AM_MART_INDEX_01.DBF ■ mart_lob_ts_ datafile=C:\app\oradata\AM81MTF2\AM_MART_LOB_01.DBF

Parameter	Description	Modify	Default or Sample Value
#Argus Mart Apr User Datafiles	Location of Argus Mart APR user datafiles	Yes	<ul style="list-style-type: none"> ■ apr_user_data_ts_datafile=C:\app\oradata\AM81MTF2\AM_APP_DATA_01.DBF ■ apr_user_ind_ts_datafile=C:\app\oradata\AM81MTF2\AM_APP_INDEX_01.DBF ■ apr_user_lob_ts_datafile=C:\app\oradata\AM81MTF2\AM_APP_LOB_01.DBF
Default and Temporary tablespaces	Defines default and temporary tablespace name	No	<ul style="list-style-type: none"> ■ default_ts=USERS ■ temp_ts=TEMP
Tablespace Encryption	Specifies the logic used for default encryption	Yes	<tablespace_encryption=<blank> <text>,="" <ul="" or="" style="list-style-type: none;" where=""> ■ blank—no encryption ■ text— like encryption using 'AES256' default storage (encrypt) </tablespace_encryption=<blank>>
Tablespace Parameters	Specifies the details of the tablespace	Yes	<ul style="list-style-type: none"> ■ tablespace_initial_size=10M ■ tablespace_autoextend=ON ■ tablespace_next_size=10M ■ tablespace_block_size=8K

2.2 Install Argus Mart

This section gives you a brief introduction about all the options that are available when you run the Argus Mart Liquibase install.

To start the Argus Mart installation, execute the following steps:

1. [Prerequisites](#)
2. [Creating the Safety Read Only user for Argus Mart. See Create User for the Argus Safety Database.](#)
3. [Create the Install User in Argus Mart](#)
4. [Create a Fresh Argus Mart Schema](#)
5. [Validate the Schema](#)

2.2.1 Prerequisites

You must check the following settings before you run the Argus Mart installation:

- **GLOBAL_NAMES**

Value of parameter GLOBAL_NAMES must be same in Argus Safety and Argus Mart (either TRUE for both or FALSE for both).

If GLOBAL_NAMES is set to TRUE, the Database Name reflected in the table GLOBAL_NAME, must have the same domain for both Argus Safety and Argus Mart databases (like, us.example.com).

- NLS_LENGTH_SEMANTICS is set to CHAR for the Argus Mart Schema Creation Tool to run.
- TNS Name for the Argus Safety Database must be present in the Oracle Database Client > tnsnames.ora file at the following path:

... \network\admin\tnsnames.ora.

2.2.2 Create User for the Argus Safety Database

1. To create the Safety Read-only user for Mart, execute the following script from the folder DBInstaller\Utilities\Create_Safety_Ro_User:
 - For Windows—Use the batch script sm_argus_read_only{user}.bat
 - For Linux—Use the shell script sm_argus_read_only{user}
2. When prompted, enter the following parameters:
 - Name of the Safety Database instance
 - Name of DBA User in Safety Database
 - DBA user password in Safety Database
 - Name of the Safety Read Only User to be created for Mart
 - Password of the Safety Read Only User
 - Role to be associated with Safety Read-only User
 - Default Tablespace for Safety Read-only User—For example, USERS
 - Temporary Tablespace for Safety Read-only User—For example, TEMP

The process of creating a Safety Read-only user begins.
3. When a confirmation message appears, review the log file and check for any errors from:

\DBInstaller\Utilities\Create_Safety_RO_User

2.2.3 Create the Install User

Note: You must execute this script to install Argus Mart database, even if you are using the SYSTEM user. This script provides additional grants to the existing user.

To create an Install user that has privileges same as the SYSTEM user for installation:

1. Execute the following script from the folder DBInstaller\Utilities\Create_Dba_User:
 - For Windows—Use the batch script am_create_dba_user.bat
 - For Linux—Use the shell script am_create_dba_user
2. When prompted, enter the following parameters:
 - Argus Mart Database instance name

- SYS or an equivalent SYSDBA user on this database
- SYSDBA user password
- Name of the Install User—For example, SYSTEM or AM_DBA_USER
- Install user password

If you provide a non-existing user name, then the script creates this as a new user, and provides the necessary grants to this user.

If you provide an already existing user name, then the script provides the necessary additional grants to the existing user.

When done, a message appears as:

Install User created.

3. Verify the status from the log file.

```
C:\Program Files
(x86)\Oracle\ArgusMart\Database\DBInstaller\Utilities\Create_Dba_User\am_
dba_user_mmddyyyy_hh24miss.log
```

4. Press **Exit**.

Recommendation: For security reasons, Oracle recommends to drop the Install user from the database after successful installation of Argus Mart as this user will have Install privileges.

To drop this user, connect to the respective database as a privileged user, and execute the following command:

```
DROP USER <INSTALL_USER> CASCADE;
```

2.2.4 Create a Fresh Argus Mart Schema

1. Log in to the Argus Mart Server with administrator privileges.
2. Navigate to Programs > Oracle > Argus Mart > Database > DBInstaller.
3. Open Dbinstaller\dbinstaller.properties file.
4. Modify the following parameters:
 - **Mart Database:**
 - db_connect_string—connects to the Argus Mart database.
Syntax: db_connect_string=<host>:<port>/<SID>
For example, server.us.xx.com:1521/AM82MT
Or, server.us.xx.com:1521/AM82MT.us.xx.com
 - dba_user—specifies the name of the Install user to run Argus Mart Liquibase Install.
See [Section 2.2.3, "Create the Install User."](#)
 - default_datafile_directory—default location on the database server, where datafiles will be created.
 - **Mart User** of each schema, where password is optional:
 - appschema_sm_mart

- appschema_sm_stage
- appschema_sm_app
- appschema_etl_user
- appschema_riis_user
- appschema_bi_user
- **Safety Database:**
 - safety_db—Argus Safety database instance name
 - safety_ro_user—Argus Mart Read-only user created in Argus Safety

Note: For more information on these parameters, see [Section 2.1, "Overview of the dbinstaller.properties file."](#)

It is recommended that you preserve the default names for tablespaces and roles.

5. From the command prompt, go to DBInstaller directory.
6. Type dbinstaller.bat, and press **Enter**.
The Liquibase install begins, and the parameters (as entered) appear on the command prompt screen with password in the hidden mode (***).
7. Keep monitoring the Liquibase progress by querying the Liquibase Log table **mart_dbchangelog**, created in AM_MART_USER schema.
8. When the process is complete, a confirmation message appears with the latest version of Argus Mart.

The following is created as per the values specified in the dbinstaller.properties file:

- **Users**
 - AM_MART_USER
 - AM_STAGE_USER
 - AM_APP_USER
 - AM_ETL_USER
 - AM_VPD_USER
 - AM_BI_USER
- **Roles**
 - AM_VPD_ADMIN_ROLE
- **Factory Data**
 - Out of the box Factory data is loaded into tables such as ETL_SIGNAL_TABLE_MAPPING, RM_CMN_PROFILE_GLOBAL, etc.
- **Database Links, DB_LINK_ARGUS:**
 - From AM_STAGE_USER of Argus Mart to ARGUS_APP of Safety
- **Tablespaces**

Note that the tablespace names begin with AM.

The Schema Creation Tool creates the following tablespaces for the Argus Mart database, when you create Argus Mart schema:

AM_APP_DATA_01	AM_APP_INDEX_01	AM_APP_LOB_01
AM_MART_DATA_01	AM_MART_INDEX_01	AM_MART_LOB_01
AM_STAGE_DATA_01	AM_STAGE_INDEX_01	AM_STAGE_LOB_01

2.2.5 Validate the Schema

1. Navigate to Database > DBInstaller > ValidateSchema.
2. Run the batch script **validate_schema.bat**.
3. When prompted, enter the following parameters:
 - Enter instance name: <Argus Mart Database Instance name>
 - Enter DBA User Name: <Install user of Argus Mart>
 - Enter Password for DBA User: <Install user password in Argus Mart>
 - Enter Validation Data File Name: The validation control file name (without the .CTL extension)
For example, VLDN_AM_8.2
 - Enter the destination where the log file is to be placed:
<C:\AM_82\Database\DBInstaller\ValidateSchema>
 - Enter the log file name for recording the schema differences:
<VLDN_AM_8.2_diff.log>
 - Enter Validation Output File Name: The validation output file name to record the validation progress:
<VLDN_AM_8.2_out.log>
4. Enter the password for the Argus Mart SYSTEM or Install user, and press **Enter**.
5. When the validation process is complete, a confirmation message appears.
 - To view any schema discrepancies, such as missing objects, use the Difference Log File.
 - To view the list of errors, which occurred during schema validation, use the Output Log File.

Note: If Argus Mart read-only user is created, then ignore the schema validation differences, where

- Objects are RO% views/columns
 - GRANTEE is Argus Mart Read-only user
-

2.3 Create Database Links

2.3.1 From Argus Mart to Argus Safety (manually)

During Fresh installation, the database link from Argus Mart to Argus Safety (DB_LINK_ARGUS) is created as a part of the installation process. However, you can manually recreate the link DB_LINK_ARGUS.

1. Navigate to DBInstaller\Utilities\Create_Safety_RO_User:
 - For Windows—execute the batch script sm_create_db_link_argus.bat
 - For Linux—execute the shell script sm_create_db_link_argus
2. When prompted, enter the following parameters:
 - Enter the name of the Safety Database instance: Safety Database Instance Name
 - Enter the name of the Mart Database instance: Mart Database Instance Name
 - Enter the name of DBA User in Mart DB: Mart Install user
 - Enter the password for user Mart DBA User: Mart Install user password
 - Enter the name of the Read Only User in Safety DB: Safety Read-only user for Mart
 - Enter the password for Read Only user in Safety: Read-only user password
 - Enter the name of the stage owner in Mart: Stage user of Mart
 - Enter the password for Stage user: Stage user password
3. Verify that the script is successfully connected as <Mart Install user/Mart Install user pwd>@<Argus Mart>, and press **Enter**.

Wait until a message *Created <Safety DB Global Name>@DB_LINK_ARGUS* appears for Stage user.

The key DB_LINK_ARGUS of RM_CMN_PROFILE_GLOBAL in the Argus Mart database contains the DB link name.

For example, a DB link is:

SAF82DB@DB_LINK_ARGUS, or

SAF82DB.US.CORP.COM@DB_LINK_ARGUS

4. Press **Exit** to close the Mart to Argus Database Link Creation window.
5. Verify the log files for status from:
 - DBInstaller\Utilities\Create_Safety_RO_User
 - DB_LINK_ARGUS_MMDDYYYY_HH24MISS.log

2.3.2 From Argus Mart to Argus Insight

1. When Argus Insight and Argus Mart are on different database instances, execute the script from the folder *DBInstaller\Utilities\Database_Links\ai_am_db_link*:
 - For Windows—execute the batch script am_insight_db_link_setup.bat
 - For Linux—execute the shell script am_insight_db_link_setup
2. When prompted, enter the following parameters:
 - Enter the Argus Mart Database Instance name
 - Enter the INSTALL user name in Argus Mart, like AM_DBA_USER

- Enter the password for the above user
- Enter the Argus Mart application user name, like AM_APP_USER
- Enter the password for the above user
- Enter the Argus Mart Schema user name, like AM_MART_USER
- Enter the password for the above user
- Enter the Argus Insight Database Name
- Enter the Argus Insight Application User name, like APR_APP
- Enter the Password for the above user
- Enter the Argus Insight Readonly User name, like APR_LINK_USER
- Enter the Password for the above user

The process of creating the database links begins.

3. The following database links are created (by dropping the existing links if any, with the same name.

- *<Insight DB Global Name>*@DB_LINK_INSIGHT—From Argus Mart AM_APP_USER > Argus Insight APR_APP

The key DB_LINK_INSIGHT of RM_CMN_PROFILE_GLOBAL in the Argus Mart database is updated with this DB link name.

- *<Insight DB Global Name>*@ARGUS_MART_TO_INSIGHT_MART—From Argus Mart AM_MART_USER > Argus Insight APR_LINK_USER

The key DB_LINK_AM_MART_TO_AI_MART of RM_CMN_PROFILE_GLOBAL in the Argus Mart database is updated with this DB link name.

4. Review the following log file, and check for any errors, when a confirmation message appears.

MART_TO_INSIGHT_DB_LINK_MMDDYYYY_HH24MISS.log

2.4 Create Argus Mart Read-only User

You can create a read-only schema in Argus Mart. This schema will have read-only (SELECT) access on all the tables and views of the AM_MART schema. Besides, this read-only schema can also be used for customized reporting purpose.

1. Open DBInstaller\Utilities\Create_Mart_Ro_User file.
 - For Windows—execute the batch script am_ro_user.bat
 - For Linux—execute the shell script am_ro_user
2. When prompted, enter the following parameters:
 - Enter TNSNAME Entry to connect to the ARGUS MART Database: < ARGUS MART Database name>
 - Enter the name of Custom DBA user in Mart Database: < Argus Mart Install user>
 - Enter password for install user in Mart Database: <Install user password>
 - Enter Read Only user to be created in Mart Database: <Read-only user to be created in Mart>

- Enter password for Read Only user of Mart Database: <Mart Read-only user password>
3. When the process is complete, press **Exit**.
4. Verify the log files for status information from:
DBInstaller\Utilities\Create_Mart_Ro_User\AM_RO_User_MMDDYYYY_
HH24MISS.log

Create Multiple Enterprises in Multi-tenant Environment

When you run ETL to transfer data from the Argus Safety database to Argus Mart, a default enterprise is automatically fetched into Argus Mart. In addition to the default enterprise, Argus Mart also enables you to create multiple enterprises by using:

- The configuration of default enterprise.
- The configuration of any other existing enterprise in Argus Safety Database.

This chapter explains the step-by-step procedure that you need to execute to create multiple enterprises in Argus Mart in a multi-tenant environment.

Note: In case of a Multi-tenant setup, you can create additional enterprises after initial or incremental ETL as well.

To create multiple enterprises in Argus Mart:

1. Fetch a new enterprise from Argus Safety to Argus Mart by executing the script from:
DBInstaller\Utilities\ create_enterprise
 - For Windows—execute the batch script am_create_enterprise.bat
 - For Linux—execute the shell script am_create_enterprise
2. When prompted, enter the following parameters:
 - Enter the Argus Mart Database instance
 - Enter the name of ETL User in the above instance, like AM_ETL_USER
 - Enter Password for ETL User in the above instance
 - Enter comma separated enterprise short names to be copied over from Safety, like ENT1,ENT2,ENT3
 - Enter the enterprise short name in Mart, from which data is to be copied, like ENT_ABBREV

Note that the Default enterprise in Argus Mart will be used to copy the base values, if no use input is provided.
3. Before bringing over the new enterprise to Argus Mart, the following checks are performed, whether:
 - the set-up is multi-tenant

-
- the Factory data is loaded in the specified Argus Mart database
 - the new enterprise exists in Argus Safety
 - the new enterprise does not already exist in Argus Mart
 - the base enterprise from which data is to be copied over, exists in Argus Mart

When all these Prerequisites are satisfied, the process of enterprise addition into Argus Mart begins.

4. Review the following log file, and check for any errors, when a confirmation message appears.

MART_TO_INSIGHT_DB_LINK_MMDDYYYY_HH24MISS.log.

Configure ODI Settings

After you have installed Oracle Data Integrator (ODI), you must configure certain settings to be able to use it to run the ETL process.

All the ODI related data has been zipped into a file, which is a part of the installation package and is available at the following path:

...\ArgusMart\ODI\AM.zip

However, there are certain tasks that you need to execute before and after importing this zip file. All these tasks are covered in sequence in the later sections.

This chapter explains the step-by-step procedure to configure all the ODI related tasks using the ODI Studio. The configuration of these tasks using the ODI Console is not supported for this release.

4.1 Minimum Components Required

The following are the minimum components required to setup ODI for Argus Mart:

- ODI Studio
- ODI Agent

4.2 Install and Configure ODI

To install and configure the ODI components (ODI Studio and ODI Agent):


Reference: To view the *Oracle® Fusion Middleware Installing and Configuring Oracle Data Integrator Guide*, refer to the following:

- For ODI 12.1.3
<https://docs.oracle.com/middleware/1213/core/ODIN G/toc.htm>
 - For ODI 12.2.1
<https://docs.oracle.com/middleware/1221/core/ODIN G/toc.htm>
-
-

1. Understand the ODI Topology—To understand the ODI agent topologies for the best suitable installation, refer to the *Oracle® Fusion Middleware Installing and Configuring Oracle Data Integrator Guide > Section: Planning the Oracle Data Integrator Installation*.

2. Install the ODI—Refer to the *Oracle® Fusion Middleware Installing and Configuring Oracle Data Integrator Guide > Section: Installing Oracle Data Integrator*.
3. Create the Master and Work Repository Schema—Refer to the *Oracle® Fusion Middleware Installing and Configuring Oracle Data Integrator Guide > Section Creating the Master and Work Repository Schema*.
4. Create Repository Login—Create a login name for the Master or Work Repository.
 - a. On the Oracle Data Integrator Login screen, click the + icon.
The Repository Connection Information screen appears.
 - b. On the Repository Connection Information screen:
 - a. In the **Login Name** field, enter a login name for the repository.
 - b. In the **User** field, enter the name of the SUPERVISOR user.
 - c. In the **Password** field, enter the password for the SUPERVISOR user.
Enter the same password as provided for the SUPERVISOR while installing the ODI.
 - d. In the Database Connection section, enter the Master Repository User Name and Password.
Enter the same User Name and Password as provided while installing the ODI.
 - e. Enter the database details in the **Driver List** (Oracle JDBC Driver), **Driver Name** (oracle.jdbc.OracleDriver) and **URL** (jdbc:oracle:thin:@<host>:<port>:<sid>) fields.
You may also click the Search icon next to the **Driver List** and **URL** fields to search for the required Driver List and URL.
 - f. In **Work Repository** section:
 - Select **Master Repository Only** option, if the login is being created for the Master Repository.
 - Select the **Work Repository** option, and enter the name of the Work Repository in the adjacent text box (for example, WORKREP1).
You may also click the Search icon next to the Work Repository name text box.
 - g. Click **OK**.
The login name is created.
5. Import Argus Mart Schema Objects
 - a. Open the ODI, and connect to the repository using the Work Repository credentials that you have just created, as mentioned in the previous section.
 - b. From the Designer tab, click the down arrow.
A drop-down menu appears.

Figure 4–1 Import Link



- c. Click **Import**.
The Import Selection dialog box appears.
- d. Select **Smart Import**, and click **OK**.
The Smart Import dialog box appears.
- e. Click the Search icon next to the **File Selection** field.
The Select an import file dialog box appears.
- f. Navigate to the AM.zip file, saved at the following location:
... \ArgusMart\ODI\AM.zip
- g. Select the **AM.zip** file, and click **Open**.
The complete path of the zip file appears in the **File Selection** field.
Keep the **Response file** field as blank.
- h. Click **Next**.
The Please wait dialog box appears with a Matching Import Objects message.
Subsequently, the Smart Import dialog box appears listing the components that will be imported from the zip file using the Import Actions screen.
- i. Click **Next**.
The Summary screen appears with the No issues message if there are no errors in the import process.
- j. Click **Finish**.
The Please wait dialog box appears with a Import in progress message.
Subsequently, the Smart Import Report screen appears listing the objects imported using the zip file.
- k. Click **Save**.
The Save Report dialog box appears.
- l. Click the Search icon next to the **Name of the target file** field.
The Save dialog box appears.
- m. Navigate to the path where you want to save the report, and in the **File Name** field, enter the name for the report.
- n. Click **Save**.
The name of the report file appears along with the complete path in the **Name of the target file** field.
- o. Click **OK**.

The Information dialog box appears with the path where the report file has been saved.

- p. Click **OK**.

This completes the steps to import the AM zip file.

You may verify this from ODI > Designer tab. The Argus Mart specific folders now appears in the Designer tab under Projects section, such as **ARGUSMART<version number>**.

6. Setup the Physical Agent

- a. Open the ODI Studio, and login to the Work Repository Connection created in the Step 4.
- b. Go to the Topology tab, from the left side pane, navigate to the Physical Architecture > Agents.
- c. Double -click **PA_AM**.
- d. From the Definition Vertical tab, in the **Host** field, enter the IP address of the ODI Server.

If you configure a Standalone Agent, then leave the Agent Name as PA_AM, and configure the Standalone Agent in the next step with same name.

If you configure a Java EE Agent, then change the Agent Name to OracleDIAgent (as by default), and the Agent Name for Java EE Agent will be created as OracleDIAgent. For more information, refer to *Oracle® Fusion Middleware Installing and Configuring Oracle Data Integrator > 5 Configuring the Domain for the Java EE Agent > 5.3 Creating a Java EE Agent in the Master Repository Using ODI Studio*.

Make sure to use the same port number in ODI Studio as well as Agent configured.

7. Configure the Domain for the ODI Agent

Note: For Argus Mart, configure either one of the ODI Agents (Standalone, or Java EE).

- To configure the domain for the Standalone Agent, refer to the [Appendix A, "Configure Standalone Installation Topology for Standalone Agent."](#)
- To configure the domain for the Java EE Agent, refer to the [Appendix B, "Configure Standard Installation Topology for Java EE Agent."](#)

4.3 Create and Test the Data Server Connection

To create and test the Data Server connection, execute the following procedure:

1. Select the Topology tab.

In the Physical Architecture section, under Oracle folder, double-click **DS_AM_ARGUSMART**.

The connection details appears in the right pane, with **Definition** selected by default.

2. In the **User** field, enter the name of the Argus ETL user (**AM_ETL_USER**).

This user was created in the [Section 2.2.4, Create a Fresh Argus Mart Schema](#).

3. In the **Password** field, enter the password for the Argus ETL User.
4. Select **JDBC** in the right pane, and enter database details of the Argus Mart schema in the **JDBC Driver** (oracle.jdbc.OracleDriver) and **JDBC URL** (jdbc:oracle:thin:@<Argus_Mart_DB_Server_Name>:<Argus_Mart_DB_Listener_Port>:<Argus_Mart_DB_SID>) fields.

You may also click the Search icon next to these fields to search for the required value.
5. Click **Test Connection**.
A confirmation message appears to save data before testing the connection.
6. Click **OK**.
The Test Connection dialog box appears.
7. From the **Physical Agent** drop-down list, select **Local**, and click **Test**.
The Information dialog box appears with the Successful Connection message.
8. Click **OK**.
9. From the **Physical Agent** drop-down list, select the **Physical Agent**, and click **Test**.
The Information dialog box appears with the Successful Connection message.
10. Click **OK**.
This completes the steps to create and test the Data Server connection.

4.4 Create a New Physical Schema

To fetch data by ODI ETL, you must create a new physical schema.

1. Select the Topology tab.
In the Physical Architecture section, under Oracle folder, right-click **DS_AM_ARGUSMART**.
2. Select **New Physical Schema**.
The Physical Schema screen appears, where **Definition** is selected by default.
3. From the **Schema** drop-down list, select the Argus ETL User (**AM_ETL_USER**).
This user was created in [Section 2.2.4, Create a Fresh Argus Mart Schema](#).
4. From the **Schema (Work Schema)** drop-down list, select the Argus ETL User (**AM_ETL_USER**) again.
5. From the left-pane, select **Context**, and click the + icon.
A new row is added in the empty space below the **Context** and **Logical Schema** options.
6. From the **Context** drop-down list, select **CTX_ARGUSMART**.
7. From the **Logical Schema** drop-down list, select **LS_AM_ARGUSMART**.
8. Click **Save** on the menu bar.
The new physical schema appears under Physical Architecture section, in Oracle folder.

4.5 Set Up the Physical Agent for Context CTX_ARGUSMART

To associate the physical agent with the context:

1. Select the Topology tab.
2. To open the context, from the **Contexts** section, double click **CTX_ARGUSMART**.
3. Navigate to Agents.
4. For the Logical Agent **LA_AM**, from the **Physical Agent** drop-down list, select the physical agent that was created while configuring the ODI. For example, **PA_AM**.
5. Click **Save**.

4.6 Validate the Load Plan

To validate the Load Plan, execute the following steps:

1. Select Operator tab.
2. In the Load Plans and Scenarios > LP_ARGUSMART82 section, double-click the **LP_INI_AM** Load Plan.

If the Object Locking dialog box appears, click **No** and proceed with the Validation process.

The Load Plan details appears in the right pane.

3. Click **Validate**.

A confirmation message appears, if there are no issues associated with the Load Plan.

Configure the Argus Mart Application

Before running the Initial ETL (Extract, Transform, and Load) process, you need to configure the Argus Mart Common Profile Switches to have control over the data that you want to transfer from the Argus Safety database to the Argus Mart database. These Common Profile Switches are configured using the Argus Safety Console.

This section explains these Common Profile Switches along with the step-by-step procedure to configure these profile switches using the Argus Safety Console.

To configure the Common Profile Switches using the Argus Safety Console:

1. Log on to the Argus Safety Console and navigate to **System Configuration > System Management (Common Profile Switches)**.

The Common Profile screen appears with the list of configuration options in the left pane.

2. Click **Argus Mart**.

The Modify Argus Mart screen appears with the list of Argus Mart Common Profile Switches that you need to configure, in the right pane.

You can configure these Common Profile Switches using this screen.

See [Table 5-1](#) for description about these profile switches along with their type (Global or Enterprise-specific).

The Global switches are visible only if you are logged in from a default enterprise.

If you are logged in from a non-default enterprise, only the enterprise-specific switches are visible in the list of Common Profile Switches.

3. Enter the required input in the text box (or select the radio buttons in case of the **ENABLE SM PROCESSING** profile switch) adjacent to the name of each profile switch, and click **Save**.

Note: The Global Switches, as mentioned in the table below, impact all enterprises configured for Argus Mart whereas the Enterprise specific Switches impact the enterprise to which user is logged in, to access the Argus Safety console.

The following table lists the Common Profile Switches that you can configure for Argus Mart, their type, and their description:

Table 5–1 Common Profile Switches for Argus Mart

Profile Switch	Type	Description
ENABLE SM PROCESSING	Global switch	<p>This switch is used to enable or disable SM Processing for Argus Mart.</p> <p>Yes - Enable SM Processing for Argus Mart.</p> <p>No - Disable SM Processing for Argus Mart.</p> <p>The value for this switch cannot be changed once initial ETL has been executed.</p>
ENABLE_AI_PROCESSING	Global switch	<p>This switch is used to enable or disable Argus Insight Processing for Argus Mart.</p> <p>0 - Do not populate Argus Insight data in Argus Mart.</p> <p>1 - Populate Argus Insight data in Argus Mart.</p>
REVISIONS TO PROCESS	Global switch	<p>This switch refers to the Configuration Flag to process maximum number of revisions in an incremental ETL run.</p> <p>Setting the value as 0 for this switch represents that the Configuration Flag is not set.</p>
FIRST HUMAN LANGUAGE	Enterprise specific switch	<p>This switch refers to first human language for derived decoded items. This value should not be changed after data mart is initialized.</p> <p>For information on the First Human Language profile switch columns in SM Tables, refer to the ETL Mapping document.</p>
SECOND HUMAN LANGUAGE	Enterprise specific switch	<p>This switch refers to second human language for derived decoded items. This value should not be changed after data mart is initialized.</p> <p>For information on the Second Human Language profile switch columns in SM Tables, refer to the ETL Mapping document.</p>
CUSTOM DATASHEET FOR LISTEDNESS	Enterprise specific switch	<p>This switch refers to the specific datasheet value to be used for the SM_EVENT_PRODUCT.LISTEDNESS_CDS_VE column. This value should not be changed after data mart is initialized.</p>
SMQ/CMQ FOR FATAL TERMS	Enterprise specific switch	<p>This switch refers to the specific SMQ/CMQ to be used for determining fatal terms for the FATAL_YN_DV column. This value should not be changed after data mart is initialized.</p>
CUSTOM ROUTINE BEFORE STAGE TABLES POPULATION	Global switch	<p>This switch refers to the full path of the custom routine to be executed before population of the Signal Staging Tables. If this routine fails or is not found, the ETL is not run and an error message is displayed.</p>

Table 5–1 (Cont.) Common Profile Switches for Argus Mart

Profile Switch	Type	Description
CUSTOM ROUTINE BEFORE REPORTING TABLES POPULATION	Global switch	This switch refers to the full path of the custom routine to be executed before population of Signal Reporting Tables. If this routine fails or is not found, the ETL is not run and an error message is displayed.
CUSTOM ROUTINE AFTER REPORTING TABLES POPULATION	Global switch	This switch refers to the full path of the custom routine to be executed after population of Signal Reporting Tables. If this routine fails or is not found, the ETL is not run and an error message is displayed.
CUSTOM ROUTINE BEFORE SIGNAL HELPER TABLES POPULATION	Global switch	This switch refers to the full path of the custom routine to be executed before population of Signal Helper Tables. If this routine fails or is not found, the ETL is not run and an error message is displayed.
CUSTOM ROUTINE AFTER SIGNAL HELPER TABLES POPULATION	Global switch	This switch refers to the full path of the custom routine to be executed after population of Signal Helper Tables. If this routine fails or is not found, the ETL is not run and an error message is displayed.
CUSTOM ROUTINE AFTER ETL	Global switch	This switch refers to the full path of the custom routine to be executed after Initial/Incremental ETL (post ETL commit). If this routine fails or is not found, the ETL is not run and an error message is displayed.
MISSING_CODE_DISPLAY_VALUE	Global switch	This switch refers to the missing display value corresponding to the code.



Upgrade Argus Mart

Argus Mart upgrade process has been moved from Schema Creation Tool to Liquibase. Liquibase is a refactoring tool that is utilized to enable a silent installation.

6.1 Prepare for the Database Upgrade

1. Recreate the Safety RO User of Argus Mart.
2. Recreate the DB_LINK_ARGUS manually, from Argus Mart to Argus Safety (see [Section 2.3.1, "From Argus Mart to Argus Safety \(manually\)."](#)).

6.2 Upgrade the Database

1. Log in to Argus Mart Web Server.
2. Navigate to Programs > Oracle > Argus Mart > Database > DBInstaller.
3. Open DBInstaller.properties file.
4. Modify the following parameters:
 - **Mart Database:**
 - db_connect_string—connects to the Argus Mart database.
Syntax: db_connect_string=<host>:<port>/<SID>
For example, db_connect_string=server.us.xx.com:1521/AM82MT
Or, db_connect_string=server.us.xx.com:1521/AM82MT.us.xx.com
 - dba_user—specifies the name of the Install user to run Argus Mart Liquibase Install.
See [Section 2.2.3, "Create the Install User."](#)
 - **Mart User** of each schema, where password is optional:
 - appschema_sm_mart
 - appschema_sm_stage
 - appschema_sm_app
 - appschema_etl_user
 - appschema_riis_user
 - appschema_bi_user
 - **Safety Database:**

- safety_db—Argus Safety database instance name
- safety_ro_user—Argus Mart read-only user created in Argus Safety

Note: For more information on these parameters, see [Section 2.1, "Overview of the dbinstaller.properties file."](#)

5. From the command prompt, go to DBInstaller directory.
6. Type dbinstaller.bat, and press **Enter**.
The Liquibase upgrade begins, and the parameters (as entered) appear on the command prompt screen with password in the hidden mode (***).
7. Keep monitoring the Liquibase progress by querying the Liquibase Log table **mart_dbchangelog**, created in AM_MART_USER schema.
8. When the process is complete, a confirmation message appears with the latest version of Argus Mart.
9. Validate Schema using the schema validation control file VLDN_AM_8.2.CTL. See [Section 2.2.5, "Validate the Schema."](#)

Extract, Transform, and Load Data

This chapter describes the steps to run the Extract, Transform, and Load (ETL) process using the Oracle Data Integrator (ODI) Studio and ODI Console.

The following table illustrates some of the terms along with the name of the Load Plan that has been used to refer the different types of ETL in the later sections of this chapter:

Table 7-1 Describing ETL Types


Type of ETL	Description	Name of the Load Plan
Initial ETL	The Initial ETL process involves full load of data from Argus Safety and DLP to Argus Mart. It can be described as the first ETL run that is executed for a fresh setup.	LP_INI_AM
Incremental ETL	The Incremental ETL brings changed case data, from last ETL run till start of current ETL run, from Argus Safety and DLP. The LM/CFG data is reloaded only if any change in record(s) is identified. Dictionary data is always reloaded in case of an Incremental ETL. If a new enterprise is added, the Incremental ETL loads complete data of the new enterprise along with delta data of other enterprises.	LP_INC_AM
Incremental ETL with BI Clear Cache	The Incremental ETL brings changed case data, from last ETL run till start of current ETL run, from Argus Safety and DLP. The LM/CFG data is reloaded only if any change in record(s) is identified. Dictionary data is always reloaded in case of an Incremental ETL. If a new enterprise is added, the Incremental ETL loads complete data of the new enterprise along with delta data of other enterprises and clears the BI cache.	LP_INC_AM_ with_ClearCache

7.1 Manage Initial ETL Process: ODI Studio

7.1.1 Run the ETL

1. Open the ODI Studio, and click **Connect to Repository**.
The Oracle Data Integrator Login screen appears.
2. In the **Oracle Data Integrator Login** screen:
 - a. From the **Login Name** drop-down list, select the ODI Work Repository name.
 - b. In the **User** field, enter the name of the ODI user.
 - c. In the **Password** field, enter the password for the ODI user.
Enter the SUPERVISOR password as provided while configuring the ODI.
 - d. Click **OK**.
The **Oracle Data Integrator** screen appears.
3. Select the **Operator** tab in the left pane.
4. Expand the **Load Plans and Scenarios** section.
5. Expand **LP_ARGUSMART82**, and scroll-down to **LP_INI_AM**.
This option in this section represents the load plan for the initial ETL process for Argus Mart.
6. Right-click the **LP_INI_AM** option, from the drop-down menu select **Run**.
The Start Load Plan screen appears.
7. In the Start Load Plan screen:
 - a. From the **Context** drop-down list, select **CTX_ARGUSMART**.
 - b. From the **Logical Agent** drop-down list, select **LA_AM**.
 - c. From the **Log Level** drop-down list, select the desired log level.
 - d. Click **OK**.
The Information dialog box appears with the Load Plan Started confirmation message.
8. Click **OK**.
To verify the status of the ETL process, navigate to the Load Plan Executions section, and expand the **Load Plan** folder. The status of the Load Plan appears in Green color, which signifies that the ETL session is in progress.

Figure 7-1 Status of the Load Plan



7.1.2 Stop the ETL

1. In Load Plan Executions section, **Load Plan** folder, right-click the Load Plan, which you want to stop.

A drop-down menu appears.

2. Select **Stop Normal**.

The Stop Load Plan dialog box appears.


3. From the **Physical Agent** drop-down list, select **PA_AM**.

4. Click **OK**.

The execution of the Load Plan is stopped.

To verify the status of the ETL process, navigating to the Load Plan Executions section and expand the **Load Plan** folder. The status of the Load Plan appears in Red color with the **X** symbol, which signifies that the ETL session is not in progress.

Figure 7-2 Stopped Initial ETL Session




Note: You must verify in Argus Mart database if the ETL session has been successfully ended after this step.

7.1.3 Restart the ETL

Restarting the Initial ETL process enables you to start the ETL process from the last execution step where it was stopped or failed.

1. In Load Plan Executions section, **Load Plan** folder, right-click the Load Plan, which you want to restart.

The drop-down menu appears.

Figure 7-3 Restarting the Initial ETL

2. Click **Restart**.

The Restart Load Plan dialog box appears.

3. From the **Physical Agent** drop-down list, select **PA_AM**.


4. From the **Log Level** drop-down list, select the required log level.

5. Click **OK**.

The Information dialog box appears with the Load Plan restarted message.


6. Click **OK**.

Another Load Plan is added with the same name as that of the stopped ETL, in the Load Plan folder. However, this instance of the ETL Process appears in Green color, which signifies that the ETL is in progress.

Figure 7-4 Restarted Load Plan

Once the ETL process is complete, the Load Plan is appear in Green color with a check mark.

Figure 7-5 Completed Load Plan



7.1.4 Process a Failed ETL

If an ETL process fails, you have the option of continuing the process from the failed step or executing it again from the beginning of ETL.

This section explains the steps to continue a failed ETL from the failed step and to execute it again from the beginning of ETL.

7.1.4.1 Continue the Failed Initial ETL

The process to continue the failed Initial ETL from the failed step is exactly the same as that of the process of restarting the Initial ETL after stopping it.

See [Section 7.1.3, "Restart the ETL"](#) for the step-by-step procedure to continue the failed Initial ETL from the failed step.

7.1.4.2 Restart the Failed Initial ETL

The process to restart the failed Initial ETL from the beginning is exactly the same as that of the process of running the Initial ETL.

However, before restarting the ETL you must log on to the Oracle SQL Developer using the Argus ETL User credentials and execute the following statements:

- EXEC pkg_sm_stage_util.p_set_cmn_profile_value ('DATABASE', 'ODI_ETL_STATUS', '0');
- EXEC pkg_sm_stage_util.p_set_cmn_profile_value ('DATABASE', 'ETL_SM_ITERATION_NUMBER', NULL);
- COMMIT;

To verify the successful execution of these statements, you may execute the following Select statements:

- SELECT * FROM rm_cmn_profile_global WHERE KEY = 'ODI_ETL_STATUS';

The entry for the **Value** column must be **0** after executing this statement.

Figure 7-6 Select Statement 1 to Verify Successful Execution

```
SELECT * FROM rm_cmn_profile_global WHERE KEY = 'ODI_ETL_STATUS';
```

SECTION	KEY	VALUE	TREE_NAME	KEY_TYPE	KEY_LABEL
1 DATABASE	ODI_ETL_STATUS	0			

- `SELECT * FROM rm_cmn_profile_global WHERE KEY = 'ETL_SM_ITERATION_NUMBER';`

The entry for the **Value** column must be blank after executing this statement.

Figure 7-7 Select Statement 2 to Verify Successful Execution

```
SELECT * FROM rm_cmn_profile_global WHERE KEY = 'ETL_SM_ITERATION_NUMBER';
```

SECTION	KEY	VALUE	TREE_NAME	KEY_TYPE	KEY_LABEL
1 DATABASE	ETL_SM_ITERATION_NUMBER				

See the [Section 7.1.1, "Run the ETL"](#) section for the step-by-step procedure to restart the failed Initial ETL from the beginning of ETL.

7.2 Monitor Initial ETL Process: ODI Studio

7.2.1 View the Steps of Load Plan

Before executing the Initial ETL, you may view the steps of the Load Plan for the Initial and the Incremental ETL.

To view the Load Plan steps, execute the following steps:

1. Open the Oracle Data Integrator Studio, and click **Connect To Repository**.
2. Log on to the ODI Work Repository using the ODI User credentials.
3. Select the Designer tab, and expand the Load Plans and Scenarios section.
4. Double-click the **LP_INC_AM** load plan.
5. Select the **Steps** option in the right pane.

All the steps of the Load Plan appears.

Similarly, you may also view the steps for the Incremental Load Plan by navigating to **Designer** tab > Load Plans and Scenarios section, and double-click LP_INC_AM.

7.2.2 Monitor the ETL


To monitor the progress of the Initial ETL after executing the **LP_INI_AM** Load Plan, execute the following steps:

1. Select the Operator tab, in the Load Plan Executions section expand the **Load Plan** folder.

- Expand the LP_INI_AM load plan to view the ETL process in progress.

The status of the Load Plan appears in Green color, which signifies that the process is running properly.

Figure 7-8 Viewing the Status of the ETL Process



- Double-click the ETL session, highlighted in the figure above, and select **Steps** in the right pane.


The list of steps for the Load Plan appears along with the steps that have been completed successfully. The green check mark represents the successful completion of the step.

7.2.3 Debug the Failed ETL

To view the step where the ETL process failed and also the error message related to the ETL process failure, execute the following steps:

- In the Operator tab > Load Plan Executions section, expand the Load Plan folder to view the current status of the ETL process.

Figure 7-9 Viewing the Failed ETL Process



The status of the Load Plan appears in Red color with the X symbol, which signifies that the ETL session is not in progress.

2. Double-click the Load Plan, and select **Steps**.

The list of steps for the Load Plan appears in the right pane. The step because of which the ETL process has failed, is highlighted in Red color with the X symbol.


- Hover over the cursor over the error message to view the complete message.
- For more information about the error message, click **Execute**.
- To view the error message, log on to the Oracle SQL Developer using the Argus ETL user credentials, and execute either or both of the following queries:
 - SELECT * FROM etl_stage_log ORDER BY id DESC;
 - SELECT * FROM etl_mart_log ORDER BY id DESC;

7.2.4 Monitor the Restarted ETL (Resume)

To view the status of the process after restarting a stopped ETL process, execute the following steps:

1. In the Operator tab > Load Plan Executions section, expand the **Load Plan** folder.

Figure 7–10 Viewing the Restarted ETL Process Status



The status of the restarted ETL process appears in Green color, which signifies that the ETL is in progress again.

To view the status of the remaining steps in the process, in the LP_INI_AM folder, double-click the Load Plan, and selecting **Steps**.

Figure 7–11 Viewing the Steps of the Restarted ETL

#	Steps Hierarchy	Status	Duration	Start	End	Scenario/Variable	Session ID	Return...	Error Message
107	SCN_set_smq_termcodes	✓	00:17	15:15:32	15:15:49	SCN_set_smq_termcodes Version 001	3224	0	
108	SCN_populate_rm_profile_switches	✓	00:00	15:15:49	15:15:49	SCN_populate_rm_profile_switches ...	3225	0	
109	SCN_populate_helbers_RM_LM_STUDIES	✓	00:00	15:15:49	15:15:49	SCN_populate_helbers_RM_LM_STU...	3226	0	
110	Mart Parallel - CFG CL LXP tables	✓	00:00	15:27:24	15:27:24			0	
119	Mart Parallel - LM Tables	✓	03:05	15:27:24	15:30:29			0	
130	SCN_pop_user_access_site	✓	00:00	15:30:29	15:30:29	SCN_pop_user_access_site Version ...	3255	0	
131	SCN_pop_cfg_user_enterprise_apps	✓	00:00	15:30:30	15:30:30	SCN_pop_cfg_user_enterprise_apps...	3256	0	
132	Mart Parallel - Report Tables	✓	00:02	15:30:30	15:30:32			0	
138	SCN_delete_bi_tables	✓	00:00	15:30:32	15:30:32	SCN_delete_bi_tables Version 001	3262	0	
139	Mart Parallel - CASE Tables	✓	01:06	15:30:32	15:31:38			0	
228	SCN_pop_rm_case_revision_data	✓	00:02	15:31:38	15:31:40	SCN_pop_rm_case_revision_data Ve...	3341	0	
229	SCN_pop_fr_consistency_log	✓	00:01	15:31:41	15:31:42	SCN_pop_fr_consistency_log Versio...	3342	0	
230	SCN_pop_fr_consistency_log_hist	✓	00:00	15:31:43	15:31:43	SCN_pop_fr_consistency_log_hist V...	3343	0	
231	SCN_pop_etl_su_cases_to_process	✓	00:00	15:31:43	15:31:43	SCN_pop_etl_su_cases_to_process ...	3344	0	
232	SCN_pop_rm_su_case_study_drug	✓	00:03	15:31:43	15:31:46	SCN_pop_rm_su_case_study_drug V...	3345	0	
233	SCN_p_case_series_interoperability	✓	00:00	15:31:47	15:31:47	SCN_p_case_series_interoperability ...	3346	0	
234	SCN_populate_case_locked_rev	✓	00:00	15:31:47	15:31:47	SCN_populate_case_locked_rev Ver...	3347	0	
235	SCN_manage_sm_indexes(1,0)	✓	00:03	15:31:47	15:31:50	SCN_manage_sm_indexes(1,0) Versi...	3348	0	
236	SCN_manage_constraints(1,0)	✓	00:02	15:31:51	15:31:53	SCN_manage_constraints(1,0) Versi...	3349	0	
237	SCN_analyze_tables(0)	✓	00:58	15:31:53	15:32:51	SCN_analyze_tables(0) Version 001	3350	0	
238	SCN_exec_etl_custom_hooks_POST_REPO	✓	00:00	15:32:52	15:32:52	SCN_exec_etl_custom_hooks_POST...	3351	0	
239	SCN_manage_constraints(0,2)	✓	00:01	15:32:52	15:32:53	SCN_manage_constraints(0,2) Versi...	3352	0	
240	SCN_manage_sm_indexes(0,2)	✓	00:19	15:32:54	15:33:13	SCN_manage_sm_indexes(0,2) Versi...	3353	0	
241	SCN_etl_sm_cases_to_process	✓	00:00	15:33:14	15:33:14	SCN_etl_sm_cases_to_process Versi...	3354	0	
242	SCN_etl_sm_cases_to_process_log	✓	00:00	15:33:14	15:33:14	SCN_etl_sm_cases_to_process_log...	3355	0	
243	SCN_etl_sm_set_switches	✓	00:00	15:33:15	15:33:15	SCN_etl_sm_set_switches Version 001	3356	0	
244	SCN_update_etl_proc_status(0,0)	✓	00:00	15:33:15	15:33:15	SCN_update_etl_proc_status(0,0)...	3357	0	
245	SCN_execute_sm_loop_procs(0)	✓	03:12	15:33:15	15:36:27	SCN_execute_sm_loop_procs(0) Ver...	3358	0	
246	SCN_manage_sm_indexes(1,2)	✓							

7.3 Manage Initial ETL Process: ODI Console

7.3.1 Run the Initial ETL

1. Open the ODI Console.

The Oracle Data Integrator Console Sign In screen appears.

2. In the Oracle Data Integrator Sign In screen:

- a. From the **Repository** drop-down list, select the ODI Work Repository name.
- b. In the **User Id** field, enter the name of the ODI user.
- c. In the **Password** field, enter the password for the ODI user.
- d. Click **Sign In**.

The Oracle Data Integrator Console screen appears.

3. Select the Browse tab in the left pane.

4. Navigate to **Runtime > Scenarios/Load Plans > Folders > LP_ARGUSMART82 > LP_INI_AM**.

The LP_INI_AM option in this section represents the load plan for the initial ETL process for Argus Mart.

5. Click **Execute**.



The Execute Load Plan screen appears.

6. In the Execute Load Plan screen:

- a. From the **Logical Agent** drop-down list, select **LA_AM**.
- b. From the **Context** drop-down list, select **CTX_ARGUSMART**.
- c. From the **Log Level** drop-down list, select the desired log level.
- d. Click **Execute Load Plan**.

The Information dialog box appears with confirmation message — Load Plan Execution submitted successfully.


7. Click **OK**.

To verify the status of the ETL process, in the Sessions/Load Plan Executions section, expand the **Load Plan Executions** folder. The status of the Load Plan appears in green color with tilted **S**, which signifies that the ETL session is in progress.

7.3.2 Stop the Initial ETL

1. In the Sessions/Load Plan Executions section > Load Plan Executions folder, select the Load Plan, which you want to stop, and click **Stop**.

Figure 7–12 Stopping the Initial ETL




The Stop Load Plan Execution dialog box appears.

2. From the **Stop Type** drop-down list, select **Normal**.
3. From the **Physical Agent** drop-down list, select **OracleDI Agent**.
4. Click **Stop**.

The Information dialog box appears with confirmation message — Load Plan was Stopped Successfully.

5. Click **OK**.

To verify the status of the ETL process, navigate to **Sessions/Load Plan Executions section > Load Plan Executions** folder. The status of the Load Plan appears in red color with the **X** symbol, which signifies that the ETL session is not in progress.

Figure 7–13 Stopped Initial ETL Session

Note: You must verify in Argus Mart database if the ETL session has been successfully ended after this step.

7.3.3 Restart the Initial ETL

Restarting the Initial ETL process enables you to start the ETL process from the last execution step where it was stopped or failed.

To restart the Initial ETL, execute the following steps:

1. In the Sessions/Load Plan Executions section > Load Plan Executions folder, select the Load Plan, which you want to restart, and click **Restart**.



The Restart Load Plan Execution dialog box appears.

2. From the **Physical Agent** drop-down list, select **OracleDIAGENT**.
3. From the **Log Level** drop-down list, select the required log level.
4. Click **Restart**.

The Information dialog box appears with confirmation message— Load Plan restarted successfully.

5. Click **OK**.

Another Load Plan is added with the same name as that of the stopped ETL, in the **Sessions/Load Plan Executions section > Load Plan Executions folder**. However, this instance of the Load plan appears in green color, which signifies that the ETL is in progress.

7.3.4 Process a Failed ETL

If an ETL process fails, you have the option of continuing the process from the failed step or executing it again from the beginning of ETL.

This section explains the steps to continue a failed ETL from the failed step and to execute it again from the beginning of ETL.

7.3.4.1 Continue the Failed Initial ETL

The process to continue the failed Initial ETL from the failed step is exactly the same as that of the process of restarting the Initial ETL after stopping it.

See the [Section 7.3.3, "Restart the Initial ETL"](#) for the step-by-step procedure to continue the failed Initial ETL from the failed step.

7.3.4.2 Restart the Failed Initial ETL

The process to restart the failed Initial ETL from the beginning is exactly the same as that of the process of running the Initial ETL.

However, you need to execute certain steps before restarting the Failed Initial ETL, refer to the [Section 7.1.4.2, "Restart the Failed Initial ETL"](#) for the complete details.

See the [Section 7.3.1, "Run the Initial ETL"](#) for the step-by-step procedure to restart the failed Initial ETL from the beginning of ETL.

7.4 Monitor Initial ETL Process: ODI Console

7.4.1 View the Steps of Load Plan

Before executing the Initial ETL, you may view the steps of the Load Plan for the Initial and the Incremental ETL.

To view the steps of Load Plan, execute the following steps:

1. Log on the Oracle Data Integrator Console, and select the Management tab.
2. Navigate to **Runtime > Scenarios/Load Plans > Folders > LP_ARGUSMART82**.
3. Right-click **LP_INI_AM** (Load Plan for Initial ETL) or **LP_INC_AM** (Load Plan for Incremental ETL), and select **View**.


The steps for the Load Plan appears in the Relationships section in the right pane.

7.4.2 Monitor the ETL

To monitor the progress of the initial ETL after executing the **LP_INI_AM** Load Plan, execute the following steps:

1. Select the Browse tab, and navigate to **Runtime > Sessions/Load Plan Executions > Load Plan Executions**.

A tilted **S** in green color appears, which signifies that the ETL process is running properly.



2. In the Relationships section, right-click the session, and select **View**, to view the list of all the steps along with the steps that have been completed.

7.4.3 Debug the Failed ETL

To view the step where the ETL process failed and also the error message related to the ETL process failure, execute the following steps:

1. In the Browse tab, navigate to **Runtime > Sessions/Load Plan Executions > Load Plan Executions**.

The status of the Load Plan appears in red color with the **X** symbol, which signifies that the ETL session is not in progress.

2. Double-click the Load Plan.

The list of steps for the Load Plan appears in the Relationship section. The step because of which the ETL process has failed, is highlighted in red color with the **X** symbol.

- Hover over the error message to view the complete message.
- Alternatively, navigate to **Runtime > Sessions/Load Plan Executions > Sessions**, right-click the stopped session, highlighted in Red color with the **!** symbol, and select **View**.

The error details appears in the right pane.

- To view the error message, log on to the Oracle SQL Developer using the Argus ETL user credentials, and execute either or both of the following queries:
 - `SELECT * FROM etl_stage_log ORDER BY id DESC;`
 - `SELECT * FROM etl_mart_log ORDER BY id DESC;`

7.4.4 Monitoring the Restarted ETL (Resume)

Once you have restarted a stopped ETL process, you can view the status of the process using the following steps:

1. In the Browse tab, navigate to **Runtime > Sessions/Load Plan Executions > Load Plan Executions** section.

The status of the restarted ETL process appears in green color, which signifies that the ETL is in progress again.

To view the status of the steps completed before restarting the ETL, and the steps after restarting the ETL, double-clicking the session in progress.

The steps appears in the Relationship section in the right pane.

Relationships

Steps Variables Sessions

Steps before Restarting ETL

Steps Hierarchy	Step Number	Status	Duration	Start	End	Scenario/Variabl	Session ID
root_step	0		01:02	6:35:37 PM			
SCN_1	1		00:00	6:27:40 PM	6:27:40 PM		3627
SCN_2	2		00:01	6:27:41 PM	6:27:42 PM		3628
SCN_3	3		00:00	6:27:43 PM	6:27:43 PM		3629
SCN_4	4		07:54	6:27:43 PM	6:35:37 PM		3630
SCN_5	5		00:00	6:35:38 PM	6:35:38 PM		3631
SCN_6	6		00:00	6:35:38 PM	6:35:38 PM		3632

Steps after Restarting

7.5 Run the Incremental ETL

For step-by-step information related to the Incremental ETL tasks such as Running, Stopping, and Restarting the Incremental ETL through:

- ODI Studio, see [Section 12.3, "Manage the Incremental ETL Process"](#)
- ODI Console, see [Section 13.3, "Manage the Incremental ETL Process"](#)

Uninstall the Argus Mart Application

To uninstall the Argus Mart application, execute the following steps:

1. Double-click **Setup.exe** to open the Oracle Universal Installer, available at the following location:
`<ArgusMart_HOME>\Disk1\install`
The Welcome screen appears.
2. Click **Deinstall Products**.
The Inventory screen appears.
3. In Contents tab, expand **Independent Products**.
The list of Independent Products appears.
4. Select **Oracle Argus Mart <version number>** check box.
Note the installation location displayed under the **Product Information** frame.
For example: Location C:\ArgusMart82\oracle.hsgbu.am specifies installation path as C:\ArgusMart82
5. Click **Remove**.
A confirmation message appears.
6. Click **Yes**.
A progress bar appears and subsequently removes Argus Mart from the list of Independent Products.
7. Click **Close** to exit from the Inventory screen.
8. Click **Cancel** in the Oracle Universal Installer screen to exit.
9. Delete the folder, where the Argus Mart was installed, from the local file system.
Example: C:\AM
10. Navigate to **start > All Programs > Oracle > Oracle Argus Mart**.
11. Right-click **Oracle Argus Mart**, and from the drop-down menu, click **Delete**.
12. To Remove Database Components for Argus Mart:
 - a. Remove Database Schemas from Argus Mart Database.
Connect to SYSTEM or DBA user of Argus Mart Database, and execute the following commands to drop Argus Mart Users, Tablespaces, and other objects.

```
connect SYSTEM/<password>@<ArgusMartDB>
```

```

DROP USER "AM_APP_USER" CASCADE;
DROP USER "AM_BI_USER" CASCADE;
DROP USER "AM_ETL_USER" CASCADE;
DROP USER "AM_MART_USER" CASCADE;
DROP USER "AM_STAGE_USER" CASCADE;
DROP USER "AM_VPD_USER" CASCADE;

DROP ROLE "AM_VPD_ADMIN_ROLE";

DROP PUBLIC SYNONYM "RM_CMN_PROFILE_GLOBAL";

ALTER TABLESPACE "AM_APP_DATA_01" COALESCE;
ALTER TABLESPACE "AM_APP_INDEX_01" COALESCE;
ALTER TABLESPACE "AM_APP_LOB_01" COALESCE;
ALTER TABLESPACE "AM_MART_DATA_01" COALESCE;
ALTER TABLESPACE "AM_MART_INDEX_01" COALESCE;
ALTER TABLESPACE "AM_MART_LOB_01" COALESCE;
ALTER TABLESPACE "AM_STAGE_DATA_01" COALESCE;
ALTER TABLESPACE "AM_STAGE_INDEX_01" COALESCE;
ALTER TABLESPACE "AM_STAGE_LOB_01" COALESCE;

DROP TABLESPACE AM_APP_DATA_01 INCLUDING CONTENTS;
DROP TABLESPACE AM_APP_INDEX_01 INCLUDING CONTENTS;
DROP TABLESPACE AM_APP_LOB_01 INCLUDING CONTENTS;
DROP TABLESPACE AM_MART_DATA_01 INCLUDING CONTENTS;
DROP TABLESPACE AM_MART_INDEX_01 INCLUDING CONTENTS;
DROP TABLESPACE AM_MART_LOB_01 INCLUDING CONTENTS;
DROP TABLESPACE AM_STAGE_DATA_01 INCLUDING CONTENTS;
DROP TABLESPACE AM_STAGE_INDEX_01 INCLUDING CONTENTS;
DROP TABLESPACE AM_STAGE_LOB_01 INCLUDING CONTENTS;

```

- b. Remove Argus Mart Schema on Argus Safety Database (AS_MART_USER) from Argus Safety Database created for Argus Mart.

Connect to SYSTEM or DBA user of Argus Safety Database.

```

connect SYSTEM/<password>@<ArgusSafetyDB>
DROP USER "AS_MART_USER" CASCADE;

```

13. Remove the TNS entry of the Argus Mart database from the given Oracle Home path (see Section 2.2 > Step 6) located at

```

..\network\admin\tnsnames.ora

```

14. Restart the system.

Note: If you are re-installing Argus Mart on the same server, you must provide the same folder path that was specified during the previous installation process.

For example, if you installed Argus Mart at the **C:\AM** location and uninstall it using the steps mentioned above, you must enter the same folder path (for example, **C:\AM**) that was entered in the previous installation process.

Part II

Administration

This part of the Oracle Argus Mart Installation and Administration Guide describes administrative tasks that enables you to manage Oracle Argus Mart.

Set Up Context in a Multi-tenant Environment

In a multi-tenant setup, you can view only one enterprise data at a time for which context has been set.

To set the context for an enterprise, execute the following steps:

1. Connect to the Argus Mart User (AM_MART_USER).
2. Execute the following command:

```
pkg_rls.set_context(:LoginUserName, :Enterpriseid, 'ARGUS_MART', NULL);
```

Where,

- **LoginUserName** refers to the User Name
- **Enterpriseid** refers to the ID for the enterprise
- **ARGUS_MART** refers to the Application Name

This completes the steps to set the context for the enterprise.

Example 9-1 Setting Context for an Enterprise

Execute `pkg_rls.set_context('admin',3,'ARGUS_MART',NULL);`

Secure Unblinding in Argus Mart

This chapter explains the concept of Blinded Security for certain table columns in Argus Mart for a drug study.

The value for some of the table columns in Argus Mart is dependent upon the selection of **Business Configuration > Studies Configuration > Study is eligible for Unblinding** checkbox, in Argus Safety.

The screenshot shows the Oracle Argus Safety 'STUDIES CONFIGURATION' interface. The 'Study is eligible for Unblinding' checkbox is checked and highlighted with a red box. The interface displays various configuration options for a study, including Study Name, Study Type, Product License, and a table of Products.

#	Product Name	Dosage Form	Strength	Units	Blinded
1.	Test Drug 2 - Product Name	Granule	20	ad	<input checked="" type="checkbox"/>
2.	prod1	Injection	50	ml	<input checked="" type="checkbox"/>

If the this checkbox is selected, the actual values for all the blinded columns is displayed in Argus Mart tables.

However, if this checkbox is not selected, the actual values for all the blinded columns are replaced by NULL, Blinded, or any other value in the Argus Mart tables.

In case of the Reporting Mart, there are three views which comprise the Blinded information: `v_rm_su_case_product`, `v_rm_su_case_prod_drugs`, and `v_rm_su_case_dose_regimens`. These views display the actual data only if the **Study is eligible for Unblinding** checkbox is selected.

Similarly, in case of a Signal Mart, there are certain table columns which comprise the Blinded information. The name of these columns end with `_su`, which represents Secure Unblinding. These table columns display the actual data only if the **Study is eligible for Unblinding** checkbox is selected.



Rebuild a Case in Argus Mart

During the incremental ETL execution, you may need to re-populate certain cases from the scratch due to DLP data corruption or migration of cases in chunk.

To rebuild the entire information for the selected cases:

1. Specify ENTERPRISE_ID/CASE_ID of such cases in the table ETL_MANUAL_RBLD_CASE_LIST.
2. During the Incremental ETL, these cases will be deleted from Reporting Mart (RM) and Signal Mart (SM) tables, and rebuilt from the scratch.

Note that the cases that are not part of this table, will be processed only for delta data as before.

3. When a case that is rebuilt has an effective start date earlier than the current value in switches START_DATE_CURRENT_DATA_SUPPORT and START_DATE_LOCKED_REVISION_SUPPORT, these switch values will be over-written with the rebuild case effective start date.

Note: When the case is rebuilt, any reference data change that is present in the case revisions will be lost.

Recommendation: Oracle recommends to use this feature cautiously and on need basis only.



Work with Incremental ETL in ODI Studio

This chapter describes the steps required to administer the ETL process using the Oracle Data Integrator Studio (ODI Studio).

12.1 Schedule an Incremental ETL

The **AM.zip** file contains pre-configured ETL scheduling in **Inactive** mode.

The Incremental ETL is used to load the delta data. You can execute an Incremental ETL either by executing Load Plan **LP_INC_AM**, or scheduling an ETL to run at the configured time interval.

To schedule a Load Plan, execute the following steps:

1. In the **Designer** tab, navigate to **Load Plans and Scenarios** section and expand **LP_INC_AM** (Load Plan for Incremental ETL).
2. Right-click **Scheduling** and select **New Scheduling**.

The **Load Plan Scheduling** dialog box appears.

The screenshot shows the 'Scheduling [Load Plan: LP_INC_AM]' configuration window. The 'Status' section includes radio buttons for 'Active', 'Inactive', and 'Active for the period'. Under 'Active for the period', there are checkboxes for 'Starting', 'Ending', 'Every day between', 'Except these days of the month', and 'Except these days of the week'. The 'Execution' section includes radio buttons for 'On startup', 'Simple', 'Hourly', 'Daily', 'Weekly', 'Monthly (day of the month)', 'Monthly (week day)', and 'Yearly'. Both sections have date and time pickers.

You can set options given in the **Status** and **Execution** sections, according to the requirements to schedule the Load Plan.

12.2 Monitor the Incremental ETL Process

The process of monitoring the Incremental ETL using the Oracle Database Integrator Studio is same as the process of monitoring the Initial ETL.

For step-by-step information related to monitoring the Incremental ETL process using the ODI Studio, see [Section 7.2, "Monitor Initial ETL Process: ODI Studio."](#)

12.3 Manage the Incremental ETL Process

This section describes the steps required to manage the Incremental ETL process using the Oracle Database Integrator Studio.

12.3.1 Run the Incremental ETL

1. Open the Oracle Data Integrator Studio, and click **Connect to Repository**.
The **Oracle Data Integrator Login** dialog box appears.
2. In the **Oracle Data Integrator Login** window:
 - a. From the **Login Name** drop-down list, select the ODI Work Repository name.
 - b. In the **User** field, enter the name of the ODI user.
 - c. In the **Password** field, enter the password for the ODI user.
 - d. Click **OK**.


The **Oracle Data Integrator** screen.

3. From the left pane, select the **Operator** tab.
4. Expand the **Load Plans and Scenarios** section.
The **LP_INC_AM** option represents the load plan for the Incremental ETL process for Argus Mart.
5. Right-click the **LP_INC_AM** option, and from the drop-down menu, click **Run**.
The **Start Load Plan** dialog box appears.
6. Click **Run**.
7. In the **Start Load Plan** screen:
 - a. From the **Context** drop-down list, select **CTX_ARGUSMART**.
 - b. From the **Logical Agent** drop-down list, select **LA_AM**.
 - c. From the **Log Level** drop-down list, select a user session task log level.
 - d. Click **OK**.

The **Information** dialog box with the *Load Plan Started* confirmation message appears.

8. Click **OK**.

You can verify the status of the ETL process by navigating to the **Load Plan Executions** section and expanding the **Load Plan** folder. You can view the status of the Load Plan in **Green** color with tilted **s**, which signifies that the ETL session is in progress.



12.3.2 Run the Incremental ETL with Clear Cache

Note:

- Execute this procedure only if you require the OBIEE Clear Cache option.
 - OBIEE Clear Cache option works only when OBIEE and ODI are installed on the same machine.
-
-

1. Import the file AM.zip as per the steps specified in section 'Import Argus Mart Schema Objects' of section 4.2

2. Refresh the Designer tab and verify that:
 - A new load plan named LP_INC_AM_with_ClearCache is available.
 - PKG_BI_CLEAR_CACHE component is added to this new Load Plan.
 - The following new variables are available:
 - VAR_ALN_BI_DOMAIN_PATH
 - VAR_ALN_BI_SQL_PATH
 - VAR_ALN_BI_USER
 - VAR_ALN_BI_PWD
3. Set up the **bi_clear_cache.sql**.
 - a. Copy the **bi_clear_cache.sql** from the ODI folder.
 - b. Place the file to a location from where OBIEE can access it. For example:
 - Linux: /u01/obieecache/bi_clear_cache.sql
 - Windows c:\obieecache\bi_clear_cache.sql
 - c. Make sure the OS user that installs OBIEE has the required permissions for the bi_clear_cache.sql file.
 - d. Edit the SQL file as required:

To...	Add
Clear the entire cache	call SAPurgeAllCache();
Purge the cache of OPVA_DWH database	call SAPurgeCachebyDatabase('OPVA_DWH');
Purge the cache of AI80_SRC database	call SAPurgeCachebyDatabase('AI80_SRC');
Purge the cache of multiple databases	call SAPurgeCachebyDatabase('OPVA_DWH'); call SAPurgeCachebyDatabase('AI80_SRC');

Note: Here, the OPVA_DWH and AI80_SRC are the database names in the physical architecture inside OBIEE RPD.

4. Configure ODI for OBIEE Clear Cache.
 - a. Login to ODI Studio.
 - b. Connect to Argus Mart Work Repository.
 - c. Navigate to the Designer tab.
 - d. Open the package PKG_BI_CACHE.
 - e. Navigate to the Diagram sub-tab, and select **odiOSCommand_ClearCache**.
 - f. Configure the following based on your environment:

Parameter	Action
Command To Execute (Only for Windows)	Update the command to have relative folder paths as per the Windows OS convention. For example: <pre>#ARGUSMART.VAR_ALN_BI_DOMAIN_PATH/bitools/bin/nqcmd.cmd -d AnalyticsWeb -u #ARGUSMART.VAR_ALN_BI_USER -p #ARGUSMART.VAR_ALN_BI_PWD -s #ARGUSMART.VAR_ALN_BI_SQL_PATH\bi_clear_cache.sql</pre>
Output File	Update the file location.
Error File	Update the file location.

- g. Save the changes.
 - h. Navigate to Overview > Scenarios tab, right-click the **PKG_BI_CACHE Version 001** scenario, and select **Regenerate**.
 - i. In the Regenerate Scenario pop-up window, click **OK**.
 - j. In the Scenario Variables window, click **OK**.
5. Login to ODI Studio.
 6. Connect to Argus Mart Work Repository.
 7. Navigate to the Operator tab.
 8. Go to Load Plan and Scenarios > LP_ARGUSMART82 and right-click the load plan **LP_INC_AM_with_ClearCache**.
 9. Enter the values for following variables:

Variable	Description	Sample Value
VAR_ALN_BI_DOMAIN_PATH:	Defines OBIEE Domain Home Path.	/u01/app/oracle/Middleware/user_projects/domains/bi
VAR_ALN_BI_SQL_PATH:	Defines complete directory path where bi_clear_cache.sql is available.	/u01/obieecache
VAR_ALN_BI_USER:	Defines the Login ID of the OBIEE admin user.	weblogic
VAR_ALN_BI_PWD:	Defines password of the OBIEE admin user.	—

10. To start the load plan execution click **OK**.

12.3.3 Stop the Incremental ETL

1. Right-click the Load Plan, which you want to stop, in the **Load Plan** folder of the **Load Plan Executions** section.

2. From the drop-down menu, select **Stop Normal**.

The **Stop Load Plan** dialog box appears.

3. Select **PA_AM** from the **Physical Agent** drop-down list.
4. Click **OK**. This stops the execution of the Load Plan.

You can verify the status of the ETL process by navigating to the **Load Plan Executions** section and expanding the **Load Plan** folder. You can view the status of the Load Plan in **Red** color with the X symbol, which signifies that the ETL session is not in progress.

Note: You must verify in Argus Mart database if the ETL session has been successfully ended after this step.

12.3.4 Restart the Incremental ETL

Restarting the Incremental ETL process enables you to start the ETL process from the last execution step where it was stopped or failed.

1. Right-click the Load Plan, which you want to restart, in the **Load Plan** folder of the **Load Plan Executions** section.
2. From the drop-down menu, click **Restart**.
The **Restart Load Plan** dialog box appears.
3. Select **PA_AM** from the **Physical Agent** drop-down list.
4. Select the required log level from the **Log Level** drop-down list.
5. Click **OK**. This displays the **Information** dialog box with the **Load Plan restarted** message.
6. Click **OK**.

This adds another Load Plan, with the same name as that of the stopped ETL, in the **Load Plan** folder of the **Load Plan Executions** section. However, this instance of the ETL Process is in Green color, which signifies that the ETL is in progress.

Once the ETL process is complete, the Load Plan is displayed in Green color with a check mark.

12.3.5 Process a Stopped or a Failed ETL

The complete ETL process is divided into two major phases: Staging and Mart. The Mart phase starts only when the Staging phase is complete.

If an ETL process fails, you have the option of continuing the process from the failed step or executing it again from the beginning of ETL.

This section explains the steps to resume a failed ETL from the failed step and to execute it again from the beginning of ETL.

This section comprises the following sub-sections:

- [Continue the Failed Incremental ETL](#)
- [Restart the Failed Incremental ETL](#)

12.3.5.1 Continue the Failed Incremental ETL

If the last execution step of the failed or stopped ETL belongs to the Staging phase, the ETL resumes from the failed or stopped point, as shown in the following figure:

Figure 12–1 Staging Phase: Incremental ETL Resumes from Failed or Stopped Point

ID	TABLE_NAME	DESCRIPTION	ORA_ERR_DESC
1	171717p_populate_control_table - CONTROL_TABLE	Data population for SCOUTROL_TABLE started.	
2	171717p_populate_control_table	Error during data population in SCOUTROL_TABLE.	ORA-00942: table or view does not exist:ORA-04512: at 'AM_STAGE'
3	171719p_populate_control_table - CONTROL_TABLE	Data population for SCOUTROL_TABLE started.	
4	171720p_populate_control_table - CONTROL_TABLE	Data population for SCOUTROL_TABLE completed successfully. 1 row(s) processed.	
5	171721p_truncate_dict_tables	Truncation of Dictionary tables started.	
6	171722p_truncate_dict_tables	Truncation of Dictionary tables completed successfully.	

If the last execution step of the failed or stopped ETL belongs to the Mart phase, the ETL resumes from the first step of the Mart phase and not from the failed or stopped point.

Figure 12–2 Mart Phase: Incremental ETL Resumes from the First Step of Mart

ID	TABLE_NAME	DESCRIPTION	ORA_ERR_DESC
1	43405p_pop_rm_su_case_study_drug	Data population for RM_SU_CASE_STUDY_DRUG started.	
2	43406p_pop_rm_su_case_study_drug	Error during data population in RM_SU_CASE_STUDY_DRUG.	ORA-00911: invalid character:ORA-04512: at 'AM_MART_POP_S'
3	43407p_populate_smq_backup_tables	Populating Data in ETL_MEDORA_SMQ_HELPER_TABLE for enterprises whose global_dict_id mapping has changed/Not changed	
4	43408p_populate_smq_backup_tables	Populating Data in etl_meddra_smq_helper_table for enterprises whose global_dict_id mapping has changed/Not changed completed	
5	43409p_populate_smq_backup_tables	Populating Data for ETL_MED_SMQ_TERM_DETAIL_DATA	
6	43410p_populate_smq_backup_tables	Data population for ETL_MED_SMQ_TERM_DETAIL_DATA completed successfully 406180 row(s) processed.	
7	43411p_populate_rm_tables	Data deletion for RM_MEDORA_SMQ_CONTENT started.	

The process to continue the failed Incremental ETL from the failed step is exactly the same as that of the process of restarting the Incremental ETL after stopping it.

See the [Restart the Incremental ETL](#) section for the step-by-step procedure to continue the failed Incremental ETL from the failed step.

12.3.5.2 Restart the Failed Incremental ETL

The process to restart the failed Incremental ETL from the beginning is exactly the same as that of the process of running the Incremental ETL.

However, before restarting the ETL, you must log on to the Oracle SQL Developer or SQLPlus (or SQL Prompt) using the Argus ETL User credentials and execute the following statements:

```
EXEC pkg_sm_stage_util.p_set_cmn_profile_value ('DATABASE', 'ODI_ETL_STATUS', '0');
```

```
EXEC pkg_sm_stage_util.p_set_cmn_profile_value ('DATABASE', 'ETL_SM_ITERATION_NUMBER', NULL);
```

```
COMMIT;
```

To verify the successful execution of these statements, you can execute the following Select statements:

- `SELECT * FROM rm_cmn_profile_global WHERE KEY = 'ODI_ETL_STATUS';`

The entry for the **Value** column must be **0** after executing this statement.

Figure 12–3 Select Statement 1 to Verify Successful Execution

The screenshot shows a SQL query window with the following text: `SELECT * FROM rm_cmn_profile_global WHERE KEY = 'ODI_ETL_STATUS';` Below the query, a 'Query Result' window displays the following table:

SECTION	KEY	VALUE	TREE_NAME	KEY_TYPE	KEY_LABEL
1 DATABASE	ODI_ETL_STATUS	0			

- `SELECT * FROM rm_cmn_profile_global WHERE KEY = 'ETL_SM_ITERATION_NUMBER';`

The entry for the **Value** column must be blank after executing this statement.

Figure 12–4 Select Statement 2 to Verify Successful Execution

The screenshot shows a SQL query window with the following text: `SELECT * FROM rm_cmn_profile_global WHERE KEY = 'ETL_SM_ITERATION_NUMBER';` Below the query, a 'Query Result' window displays the following table:

SECTION	KEY	VALUE	TREE_NAME	KEY_TYPE	KEY_LABEL
1 DATABASE	ETL_SM_ITERATION_NUMBER				

See the [Run the Incremental ETL](#) section for the step-by-step procedure to restart the failed Incremental ETL from the beginning of ETL.

Work with Incremental ETL in ODI Console

This chapter describes the steps required to administer the ETL process using the Oracle Data Integrator Console (ODI Console).

13.1 Schedule an ETL

The ETL can be scheduled through ODI Studio only.

To schedule an ETL, see [Section 12.1, "Schedule an Incremental ETL"](#).

13.2 Monitor the Incremental ETL Process

The process of monitoring the Incremental ETL using the Oracle Database Integrator Console is same as the process of monitoring the Initial ETL.

For step-by-step information related to monitoring the Incremental ETL process using the ODI Console, see [Section 7.4, "Monitor Initial ETL Process: ODI Console."](#)

13.3 Manage the Incremental ETL Process

This section describes the steps required to manage the Incremental ETL process using the Database Integrator Console.

13.3.1 Run the Incremental ETL


1. Open the Oracle Data Integrator Console. This displays the **Oracle Data Integrator Console Sign In** window.
2. In the **Oracle Data Integrator Sign In** window:
 - a. Select the ODI Work Repository name from the **Repository** drop-down list.
 - b. Enter the name of the ODI user in the **User Id** field.
 - c. Enter the password for the ODI user in the **Password** field.
 - d. Click **Sign In**.

The **Oracle Data Integrator Console** screen appears.

3. Select the **Browse** tab in the left pane.
4. Expand the **Runtime** folder, and navigate to **Runtime > Scenarios/Load Plans > Folder > LP_ARGUSMART82**, and select **LP_INC_AM**.

The **LP_INC_AM** option in this section represents the load plan for the Incremental ETL process for Argus Mart.

- Click **Execute**.




- In the **Execute Load Plan** window:
 - Select **LA_AM** from the **Logical Agent** drop-down list.
 - Select **CTX_ARGUSMART** from the **Context** drop-down list.
 - Select the desired log level from the **Log Level** drop-down list.
 - Click **Execute**. This displays the **Information** dialog box with the **Load Plan Execution submitted successfully** confirmation message.
- Click **OK**.

You can verify the status of the ETL process by expanding the **Load Plan Executions** folder in the **Sessions/Load Plan Executions** section. You can view the status of the Load Plan in **Green** color with tilted **s**, which signifies that the ETL session is in progress.

13.3.2 Stop the Incremental ETL

- Select the Load Plan, which you want to stop, by expanding the **Load Plan Executions** folder of the **Sessions/Load Plan Executions** section and click **Stop**.



- In the **Stop Load Plan Execution** dialog box, from the **Stop Type** drop-down list, select **Normal**.
 - Select **OracleDI Agent** from the **Physical Agent** drop-down list.
 - Click **Stop**.
- The **Information** dialog box appears with the **Load Plan was Stopped Successfully** confirmation message.
- Click **OK**.

You can verify the status of the ETL process by navigating to the **Load Plan Executions** folder in the **Sessions/Load Plan Executions** section. You can view the


status of the Load Plan in **Red** color with the X symbol, which signifies that the ETL session is not in progress.

Note: You must verify in Argus Mart database if the ETL session has been successfully ended after this step.

13.3.3 Restart the Incremental ETL

Restarting the Incremental ETL process enables you to start the ETL process from the last execution step where it was stopped or failed.

1. Select the Load Plan, which you want to restart, in the **Load Plan Executions** folder of the **Sessions/Load Plan Executions** section and click **Restart**.



2. In the **Restart Load Plan Execution** dialog box, from the **Physical Agent** drop-down list, select **OracleDIAgent**.
3. Select the required log level from the **Log Level** drop-down list.
4. Click **Restart**. This displays the **Information** dialog box with the **Load Plan restarted** message.
5. Click **OK**.

This adds another Load Plan, with the same name as that of the stopped ETL, in the **Load Plan Executions** folder of the **Sessions/Load Plan Executions** section. However, this instance of the Load plan is in Green color, which signifies that the ETL is in progress.

13.3.4 Process a Stopped or a Failed ETL

The processing of a stopped or a failed ETL in ODI Console is same as the processing of a stopped or a failed ETL in ODI Studio.

For detailed information, see [Section 12.3.5, "Process a Stopped or a Failed ETL"](#).

Re-initialize the ETL Process

When you have successfully executed the Initial ETL process on a database, you cannot execute it again till the time you reset the mart environment. To facilitate this, you need to execute a Re-initial script. It is a Batch file, which re-initializes the database, so that you can run the Initial ETL on the database again.

Note: When you run the re-initial ETL, the data of Argus Mart is truncated and reloaded in RM and SM tables. Revision created due to reference data changes will be lost.

To execute the Re-initial script, execute the following steps:

1. Double-click the **am_environment_reset.bat** file available at the following path:

... \ArgusMart \Database \Utils \am_environment_reset.bat

This displays a warning message, which serves as a confirmation from you that you want to reset the Mart environment.

2. Enter **Y**, which represents **Yes**, in the **Do You Want to Continue (Y/N)?** field, if you want to continue with resetting the Mart environment to be able to run the Initial ETL on the database again.

Or

Enter **N**, which represent **No**, if you want to quit the process of resetting the Mart environment.

If you have entered **Y**, the **Reset Environment to Re-Run Initial ETL** Screen is displayed.

3. Enter the TNS Name to connect to the Argus Mart database in the **Enter Database TNS** field and press **Enter**.
4. Enter the following parameters for the user who have administrator rights to access the ETL process.

Note: This user is referred to as Argus ETL User. If the user is not the database owner with the administrator rights for the ETL process, the system displays an error message.

- a. Enter the Argus Mart Database Owner in the **Enter Argus ETL User** field, and press **Enter**.
- b. Enter the password in the **Enter Password for User** field, and press **Enter**.

-
- c. Enter the name of the log file in the **Enter log file name** field, and press **Enter**.
The system displays a **Connecting** status message and once connected displays **Connected**.
 5. Press **Enter** to complete writing the logs.
 6. Press **Enter** to exit from the window.

This chapter lists some of the error messages that might be displayed while working with Argus Mart, the cause for those messages, and the resolution.

15.1 Dictionary Reload Error

Error Message

The following error message is displayed during the ETL process, whenever the dictionary is reloaded in Argus Safety:

Figure 15–1 Dictionary Reload Error Message

The screenshot shows the 'Load Plan Run' window with the following details:

Instance ID:	32589	Run #:	1
Load Plan Name:	LP_INIT_AM	Started By:	SUPERVISOR
Physical Agent:	PA_AM	Context:	CTX_ARGUSMART
Start:	Dec 3, 2012 2:57:34 PM IST	End:	Dec 3, 2012 2:59:28 PM IST
Duration:	00:01:54		
Status:	Error	Return Code:	ODI-1519

Error Message:

```

ODI-1519: Serial step "root_step (InternalID:1589)" failed because child step "SCN_populate_meddra_tables (InternalID:21589)" is in error.
ODI-1217: Session SCN_populate_meddra_tables (2043589) fails with return code 20010.
ODI-1226: Step PRC_populate_meddra_tables fails after 1 attempt(s).
ODI-1232: Procedure PRC_populate_meddra_tables execution fails.
ODI-1228: Task PRC_populate_meddra_tables (Procedure) fails on the target ORACLE connection DS_AM_ARGUSMART.
Caused By: java.sql.SQLException: ORA-20010: ORA-20001: Unable to access Argus Safety table/view MEDDRA_HLGT_HLT_COMP. Check all required grants are present.
ORA-06512: at "AM_STAGE.PKG_SM_DTOS", line 655
ORA-06512: at "AM_STAGE.PKG_SM_DTOS", line 736
  
```

You can also view this error message by logging on to the SQL Developer as the AM_MART_USER, as shown in the following figure:

Figure 15–2 Dictionary Reload Error Message: SQL Developer

The screenshot shows the SQL Developer interface with a query result table. The query is: `SELECT * FROM eti_stage_log ORDER BY 1 DESC;`

ID	TABLE_NAME	DESCRIPTION	ORA_ERR_DESC
150	62p_populate_meddra_tables	Data population for MEDDRA dictionary tables started.	
151	61p_populate_meddra_tables	Error during data population from MEDRA_150_USER.MEDDRA_HLGT_HLT_C...	ORA-20001: Unable to access Argus Safety table/view MEDDRA_HLGT_HLT_COMP. Check all requir...
152	60p_populate_meddra_tables	Data population for MEDDRA dictionary tables started.	

Cause of Error

Whenever there is a dictionary reload in Argus Safety, some of the required privileges for the Argus Safety user, which you created, using the Schema Creation Tool during the Installation Process, are lost.

Resolution

You must give the required privileges to the Argus Safety user. To do so, click the **Argus User Creation** link on the Schema Creation Tool, select the user that you created during the installation process in the **Argus Safety User Creation** dialog box, enter the name of the log file and click **OK** to give the required privileges to the user.


You can refer to Section 3.5.1, Creating User for the Argus Safety Database, for more information.

15.2 ETL Execution Pre-Requisite Check Failed Error

Error Message

There are some Pre-requisite checks that you must do before the execution of the ETL. The following is the error message, which is displayed if any of the Prerequisites checks are not done:

Figure 15–3 Pre-Requisite Check Failed Error



Cause of Error

The following are the possible causes of this error message:

- If you are trying to run the Initial ETL on a database again without executing the Re-initial script.
- If you are trying to execute the Incremental ETL prior to the Initial ETL.
- If you have not configured the First Human Language Profile Switch using the Argus Safety console for the enterprises configured in Argus Mart. You must not leave the value for the First Human Language Profile Switch, as Blank.
- If the previous instance of the ETL is still not complete for the Load Plan.

Resolution

To resolve this error message, you must:

- Ensure that you run the Initial ETL on a database again only if you have already executed the Re-initial script. For more information on Re-initial script, see [Chapter 14, "Re-initialize the ETL Process."](#)
- If you are trying to run the Incremental ETL on a database, ensure that the Initial ETL has already been executed on it.
- Ensure that you have not left the value for the First Human Language Profile Switch for the enterprises configured in Argus Mart, as Blank.
- Ensure that the Previous Instance of the ETL process is complete. You can either resume the ETL process if it is in Stopped state, or you can execute the re-initial script on the database and restart the ETL process from the first step.

For more information on resuming or restarting the ETL process, see [Chapter 7, "Extract, Transform, and Load Data."](#)

15.3 FR Consistency Log Error

Error Message

You can run the following query using the SQL developer to view the Flexible Re-categorization (FR) Consistency warning message:

```
SELECT enterprise_id, code_list_id, decode_context, code, fr_type, log_message, log_date_time FROM etl_fr_consistency_log ORDER BY enterprise_id, code_list_id
```

The following is the error message:

Figure 15–4 FR Consistency Error

ENTERPRISE_ID	CODE_LIST_ID	DECODE_CONTEXT	CODE	FR_TYPE	LOG_MESSAGE
3	ACTION_TAKEN	E2B	10000101	DISCRETE	Warning: The ACTION_TAKEN : 10000101 has display value as NULL in E2B decode_context
3	ACTION_TAKEN	E2B	10000301	DISCRETE	Warning: The ACTION_TAKEN : 10000301 has display value as NULL in E2B decode_context
3	ACTION_TAKEN	E2B	10000501	DISCRETE	Warning: The ACTION_TAKEN : 10000501 has display value as NULL in E2B decode_context

Cause of Error

The display value for a codelist is NULL in the `rm_code_list_detail_discrete` table in Argus Safety.

Resolution

You must update the value for the codelist in the `rm_code_list_detail_discrete` table in Argus Safety and re-run the ETL.

15.4 MedDRA Mismatch Error

Error Message

You can run the following query using the SQL developer to view the MedDRA mismatch warning message in the `etl_mart_log` table:

```
SELECT * FROM am_mart_user.etl_mart_log WHERE table_name = 'p_check_signal_meddra_schema' ORDER BY 1 DESC;
```

The following is the error message:

Figure 15–5 MedDRA Mismatch Error

```
select * from AM_MART_user.etl_mart_log where table_name='p_check_signal_meddra_schema' order by 1 desc;
```

ID	TABLE_NAME	DESCRIPTION	ORA_ERR_DESC
1	p_check_signal_meddra_schema	Warning: The Empirica Signal MedDRA version is different from Argus Safety MedDRA version for Enterprise ID(s) 3	
2	p_check_signal_meddra_schema	Check MedDRA schema and version configuration for Empirical Signal	

Cause of Error

During the ETL process, a check is done between the Argus Safety and the Argus Mart database to ensure that they are using the same MedDRA version. This warning message is displayed when these values do not match.

Resolution

You must update the value for the MedDRA version in the **SIGNAL_MEDDRA_VER** table to ensure that it matches with the Argus Safety database value.

15.5 Multiple Enterprise Creation Messages

The following is the list of validation messages that are displayed while creating multiple enterprises in Argus Mart:

- [Source Enterprise Does Not Exist In Mart](#)
- [Enterprise Does Not Exist In Argus Safety](#)
- [Enterprise Does Not Exist For Configuration In Mart](#)

15.5.1 Source Enterprise Does Not Exist In Mart

Error Message

Given Source enterprise does not exist in Mart. Close the window and run application again.

Cause of Error

While creating multiple enterprises in Argus Mart, you must enter an enterprise name which can be used as a template to create other enterprises. This enterprise is referred to as the Source Enterprise.

If the name of the Source Enterprise that you have entered while creating multiple enterprises does not exist in Argus Mart, this validation message is displayed.

Resolution

The name of the Source Enterprise that you enter while creating multiple enterprises must exist in Argus Mart.

15.5.2 Enterprise Does Not Exist In Argus Safety

Error Message

From the list provided, no enterprise exists in Argus Safety. Close the window and run application again.

Cause of Error

The name of the enterprises that you enter while creating multiple enterprises in Argus Mart must also exist in the Argus Safety database.

If these enterprise names do not exist in Argus Safety, this validation message is displayed.

Resolution

You must ensure that the name of the enterprises that you enter while creating multiple enterprises in Argus Mart exist in the Argus Safety database.

15.5.3 Enterprise Does Not Exist For Configuration In Mart

Error Message

From the list provided, no enterprise is valid for configuration in Mart. Close the window and run application again.

Cause of Error

This validation message is displayed if all the enterprise names that you have entered on the Multiple Enterprise Creation screen already exist in the Argus Mart database.

Resolution

You must ensure that the enterprise names that you want to create in Argus Mart using the Multiple Enterprise Creation screen do not already exist in Argus Mart.

15.6 SMQ-CMQ Loop Error

Error Message

Error in p_set_Child_Record while processing term code self referencing parent child relationship leading to an infinite loop

Cause of Error

There is an SMQ, which is a Parent in the hierarchy, and has also been referenced as a Child in the hierarchy. This is termed as the Self Referencing Parent Child relationship, which leads to an infinite loop.

Resolution

You must ensure that an SMQ, which serves as a Parent in the hierarchy, must not also be present as a Child in the hierarchy.

Configure Standalone Installation Topology for Standalone Agent

Prerequisite


Oracle Data Integrator Master and Work Repository Schema are already created.

For more details, see

https://docs.oracle.com/middleware/1212/odi/ODING/create_schemas.htm#ODING860 >
Chapter 3 Creating the Oracle Data Integrator Master and Work Repository Schema.

To configure a standalone agent:

1. Start the configuration wizard.
To begin domain configuration, navigate to the `ORACLE_HOME/oracle_common/common/bin` directory, and start the WebLogic Server Configuration Wizard.
 - On Unix—`./config.sh`
 - On Windows—`config.cmd`The Configuration Wizard appears.
2. Create Domain—Select **Create a new Domain**, verify the domain location, and click **Next**.
3. Templates—From the list of available templates, select **Oracle Data Integrator - Standalone Agent - 12.2.1.0 [odi]**, and click **Next**.
4. JDK Selection—Select the **JDK** installed on Host, and click **Next**.
5. Database Configuration Type—Select **RCU**.
Enter the Repository Details, and click **Get RCU Configuration**.
When the **Connection Result log** displays the message *Successfully Done*, click **Next**.



6. Component Datasources—The details of schemas created using RCU appears. Verify the schema details, and click **Next**.
7. JDBC Test—Test the database connection, and click **Next**.
8. System Components—Make sure that the System Components is same as the name of the physical agent present in the ODI Studio. That is, the Physical Agent Name in the ODI Studio must be same as System Component (Agent Name).
Click **Next**.
9. ODI Server Configuration—Select **Server Listen Address** as the IP address of the Host
Enter **Server Listen Port** as the port number defined for the physical agent in the ODI Studio.
Click **Next**.
10. Node Manager—Select **Per Domain Custom Location**, verify the path, and click **Next**.
11. Configuration Summary—The Agent Name appears under System Component > ODI.
Click **Create**.
12. Configuration Progress—The progress of the domain creation process appears.
On successful completion of the Agent, a message stating *Domain Created Successfully*. appear.
Click **Next**.
13. End of Configuration—Domain Configuration Succeeded appears with the Domain Name and the Domain Location.
Click **Finish** to exit the wizard.

Configure Standard Installation Topology for Java EE Agent

Prerequisite

Oracle Data Integrator Master and Work Repository Schema are already created.

For more details, see


https://docs.oracle.com/middleware/1212/odi/ODING/create_schemas.htm#ODING860 >
Chapter 3 Creating the Oracle Data Integrator Master and Work Repository Schema.

To configure a Java EE agent:

1. Start the configuration wizard.
To begin domain configuration, navigate to the `ORACLE_HOME/oracle_common/common/bin` directory, and start the WebLogic Server Configuration Wizard.
 - On Unix—`./config.sh`
 - On Windows—`config.cmd`The Configuration Wizard appears.
2. Create Domain—Select **Create a new Domain**, verify the domain location, and click **Next**.
3. Templates—From the list of available templates, select the following templates, and click **Next**.
 - Oracle Enterprise Manager - 12.2.1 [em]
 - Oracle Data Integrator - Console - 12.2.1.0 [odi]
 - Oracle Data Integrator - Agent - 12.2.1.0 [odi]
 - Oracle Data Integrator - Agent Libraries - 12.2.1.0 [odi]
4. Application Location—Verify the Domain, and the Application location, and click **Next**.
5. Domain Mode and JDK Selection—Specify the Username and Password for the Administrator Account, and click **Next**.
6. Database Configuration Type—Select **RCU**.

Enter the Repository Details, and click **Get RCU Configuration**.

When the **Connection Result log** displays the message *Successfully Done*, click **Next**.



7. Component Datasources—The details of schemas created using RCU appears. Verify the schema details, and click **Next**.
8. JDBC Test—Test the database connection, and click **Next**.
9. Credentials—Enter the username and password, and click **Next**.
10. Advanced Configuration—Select the following, and click **Next**.
 - Administration Server
 - Node Manager
 - Managed Server, Clusters and Coherence
 - Deployment and Services
11. Administration Server—Change the **Listen Address** to the IP address of the host.
12. Node Manager—Select the Node Manager Type as **Per Domain Custom Location**. For Node Manager Credentials, enter the **Username** and **Password**, and click **Next**.
13. Managed Server—Specify the managed server details, and click **Next**.
 - **Server Name:** <Any Name>
 - **Port:** <Port of the Agent as configured in the ODI Studio>
 - **Server Groups:** Select **JFR-MAN-SVR**
14. (Optional) Clusters—Specify the cluster details, if required, and click **Next**.
15. Coherence Cluster—Make no changes, and click **Next**.

16. Machines—Click **Add**, enter the following details, and click **Next**.
 - Enter Name: <Any Name>
 - Node Manager Listen Address: Select IP Address of the Host
 - Node Manager Listen Port: Any unused Port
17. Assign Server to Machines—Click > button to move the **Admin Server** and **ODI_Server** to the Machine, and click **Next**.
18. Deployment Targeting—Click > button to move the **Deployments** to **Targets**.
Similarly, select the **Library** and **Application** folder (one at a time), and move them to the **Targets**.
Click **Next**.
19. Service Targeting—Click > button to move **Services** into **Targets**.
Move all the available services one by one into Targets.
Click **Next**.
20. Configuration Summary—Verify the details, and click **Create**.
21. Configuration Progress—The progress of the domain creation process appears.
On successful completion, click **Next**.
22. End of Configuration—A message appears as Oracle Weblogic Server Configuration Completed with the Domain Location and the URL for the Admin Server.

(Optional) To start the Admin Server immediately after exiting the wizard, select the check box **Start Admin Server**.
Click **Finish** to exit the wizard.