

## **Oracle® Fusion Middleware**

Developer's Guide for Identity Governance Framework

11g Release 1 (11.1.1)

**E56836-01**

April 2015

This guide provides an introduction to the Identity Governance Framework (IGF) initiative that enables secure exchange of identity-related information between users and applications and service providers. It describes how to develop with the Identity Governance Framework based developer APIs Oracle has made available.

Oracle Fusion Middleware Developer's Guide for Identity Governance Framework, 11g Release 1 (11.1.1)

E56836-01

Copyright © 2011, 2015, Oracle and/or its affiliates. All rights reserved.

Primary Author: Devanshi Mohan

Contributor: Venkat Medam

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this is software or related documentation that is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, then the following notice is applicable:

U.S. GOVERNMENT END USERS: Oracle programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, delivered to U.S. Government end users are "commercial computer software" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, shall be subject to license terms and license restrictions applicable to the programs. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Xeon are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. AMD, Opteron, the AMD logo, and the AMD Opteron logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark of The Open Group.

This software or hardware and documentation may provide access to or information about content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services unless otherwise set forth in an applicable agreement between you and Oracle. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services, except as set forth in an applicable agreement between you and Oracle.

---

---

# Contents

<b>Preface</b> .....	ix
Audience .....	ix
Documentation Accessibility .....	ix
Related Documents .....	ix
Conventions .....	ix
<b>What's New</b> .....	xi
New Features for 11gR1 PS7 (11.1.1.9.0) .....	xi
New Features for 11gR1 PS 6 (11.1.1.7) .....	xi
<b>1 Introduction to Identity Governance Framework</b>	
1.1 About the Identity Governance Framework .....	1-1
1.1.1 Benefits to Organizations .....	1-1
1.1.2 Benefits to Developers .....	1-2
1.2 About the Identity Governance Framework APIs .....	1-2
1.3 System Requirements and Certification .....	1-3
<b>2 Using the Identity Directory API</b>	
2.1 About Identity Directory API .....	2-1
2.1.1 About the Identity Directory Service .....	2-2
2.1.2 Identity Directory Service Architecture .....	2-2
2.2 Configuring Identity Directory API .....	2-3
2.2.1 Logical Entity Configuration .....	2-3
2.2.2 Physical Identity Store Configuration .....	2-5
2.2.3 Operational Configuration .....	2-5
2.3 Design Recommendations .....	2-5
2.3.1 Keep the defaultFetch Attributes Minimal .....	2-5
2.3.2 Initialize the Identity Directory Once .....	2-6
2.4 Examples .....	2-6
2.4.1 Initialize and Obtain Identity Directory Handle .....	2-6
2.4.2 Initialize and Obtain Identity Directory Handle from JPS Context .....	2-7
2.4.3 Initialize and Obtain In-Memory Identity Directory Handle .....	2-8
2.4.4 Add User .....	2-10
2.4.5 Get User for Given Principal .....	2-10
2.4.6 Modify User .....	2-11

2.4.7	Get User for Given ID Value .....	2-11
2.4.8	Search Users Using Complex Search Filter .....	2-11
2.4.9	Change User Password .....	2-12
2.4.10	Reset User Password .....	2-12
2.4.11	Authenticate User .....	2-13
2.4.12	Delete User.....	2-13
2.4.13	Create Group .....	2-13
2.4.14	Search Groups .....	2-14
2.4.15	Get Management Chain .....	2-14
2.4.16	Get Reportees of a User.....	2-14
2.4.17	Add a Member to a Group .....	2-15
2.4.18	Delete a Member From Group.....	2-15
2.4.19	Get All The Groups User is a Member .....	2-16

### 3 Using the ArisID API

3.1	About ArisID API .....	3-1
3.2	Configuring ArisID API.....	3-3
3.2.1	Configuring CARML Files.....	3-3
3.2.2	Configuring the Identity Repository.....	3-3
3.2.3	Configuring the Mapping File .....	3-3
3.3	Design Recommendations .....	3-4
3.3.1	Choose a LoginID .....	3-4
3.3.2	Choose a UniqueKey.....	3-4
3.3.3	Specify Multiple Language Support .....	3-5
3.3.4	Handle Large Results .....	3-5
3.3.5	Secure the Application .....	3-6
3.3.5.1	Domain Level Credentials.....	3-6
3.3.5.2	Application Level Credentials .....	3-6
3.3.6	Configure the Timeout Interval.....	3-7
3.3.7	Specifying Wildcard Characters in Search Filters.....	3-8
3.4	Generating ArisID Beans .....	3-8
3.5	Sample Application Using IDX User and Role Beans .....	3-9
3.5.1	SearchUsers.jsp.....	3-9
3.5.2	SearchUsers.html .....	3-10
3.6	OpenLDAP Considerations.....	3-11

### 4 Migrating to Identity Directory API

4.1	Introduction .....	4-1
4.2	Migrate the Application .....	4-1
4.2.1	API Initialization.....	4-2
4.2.2	Getting UserManager and GroupManager Handle .....	4-2
4.2.3	Search Filter .....	4-2
4.2.4	CRUD Operations.....	4-3
4.2.4.1	Finding a User.....	4-3
4.2.4.2	Searching Users.....	4-3
4.2.4.3	Creating a User .....	4-3
4.2.4.4	Deleting a User.....	4-3

4.2.4.5	Authenticating a User .....	4-4
4.2.4.6	Modifying Users and Managing Related Entities.....	4-4
4.3	Comparison Between User and Role API and IDS API .....	4-5
4.3.1	User-Related APIs.....	4-5
4.3.2	Role-Related APIs.....	4-7
4.4	Moving From a Test to a Production Environment.....	4-9
4.4.1	Overview of Moving Between Environments .....	4-10
4.4.2	Modifying Identity Directory Service/libOVD Move Plan.....	4-10
4.4.2.1	Locating Identity Directory Service/libOVD configGroup Elements .....	4-10
4.4.2.2	Identifying Identity Directory Service/libOVD Move Plan Properties .....	4-12
4.5	Tuning Configuration Parameters for IDS.....	4-12
4.5.1	Configuration Parameters .....	4-13
4.5.2	Setting Tuning Parameters Using File-Based Configuration .....	4-13
4.5.3	Setting Tuning Parameters Using In-Memory Configuration .....	4-14
4.5.4	Handling Firewall and Load Balancer Timeout Errors.....	4-15

## List of Examples

3-1	Code Sample: adapters.os_xml .....	3-6
3-2	Code Sample: adapters.os_xml .....	3-7

## List of Figures

2-1	Identity Directory API Architecture.....	2-2
2-2	Identity Directory API Components.....	2-3
3-1	IGF ArisID API Architecture.....	3-2





---

---

# Preface

This guide provides an introduction to Identity Governance Framework and describes how to use the related developer APIs Oracle has made available. It describes the Identity Directory API, which is a common service for identity management applications to access and manage identity information.

## Audience

This document is intended for developers who are writing applications that use the Oracle Fusion Middleware Identity Governance Framework based APIs.

## Documentation Accessibility

For information about Oracle's commitment to accessibility, visit the Oracle Accessibility Program website at <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=docacc>.

### Access to Oracle Support

Oracle customers that have purchased support have access to electronic support through My Oracle Support. For information, visit <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=info> or visit <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=trs> if you are hearing impaired.

## Related Documents

For more information, see the following documents:

- *Oracle Fusion Middleware Identity Governance Framework Identity Directory Java API Reference*
- *Oracle Fusion Middleware Identity Governance Framework IDXUserRole Java API Reference*
- *Oracle Fusion Middleware Identity Governance Framework UserRole Java API Reference*
- *Oracle Fusion Middleware Application Security Guide*
- Javadocs for Project Aristotle - ArisID Attribute Services, at: [http://arisid.sourceforge.net/javadocs/arisId\\_1.1\\_javadoc/](http://arisid.sourceforge.net/javadocs/arisId_1.1_javadoc/)

## Conventions

The following text conventions are used in this document:

---

<b>Convention</b>	<b>Meaning</b>
<b>boldface</b>	Boldface type indicates graphical user interface elements associated with an action, or terms defined in text or the glossary.
<i>italic</i>	Italic type indicates book titles, emphasis, or placeholder variables for which you supply particular values.
monospace	Monospace type indicates commands within a paragraph, URLs, code in examples, text that appears on the screen, or text that you enter.

---

---

---

# What's New

The new features of the Identity Governance Framework based Oracle APIs are listed here, for both the present release and the previous releases.

## **New Features for 11gR1 PS7 (11.1.1.9.0)**

- Introduces the Identity Directory Service/libOVD properties that you need to modify while moving from a test environment to production environment. See, [Section 4.4, "Moving From a Test to a Production Environment."](#)
- Provides support for wildcard characters in search filters. See [Section 3.3.7, "Specifying Wildcard Characters in Search Filters."](#)

## **New Features for 11gR1 PS 6 (11.1.1.7)**

11g Release 1 (11.1.1) provides the Identity Directory API, a common service for identity management applications to access and manage identity information. The service can be used in both Java EE and Java SE modes. For more information, see [Chapter 2, "Using the Identity Directory API"](#). For information about migration to the Identity Directory API, see [Chapter 4, "Migrating to Identity Directory API."](#)



---

# Introduction to Identity Governance Framework

The Identity Governance Framework (IGF) initiative enables secure exchange of identity-related information between users and applications and service providers. It provides privacy and governance semantics to applications and services infrastructure. This chapter provides an introduction to the Identity Governance Framework and the related developer APIs Oracle has made available. This chapter contains the following topics:

- [Section 1.1, "About the Identity Governance Framework"](#)
- [Section 1.2, "About the Identity Governance Framework APIs"](#)
- [Section 1.3, "System Requirements and Certification"](#)

## 1.1 About the Identity Governance Framework

The Identity Governance Framework is an open initiative designed to meet the following goals:

- To simplify the development of identity information access regardless of where that information is stored.
- To simplify the management (also known as **governance**) of how applications use identity data, in particular, sensitive data.

As part of this initiative, Oracle has contributed key initial specifications and is making them available to the community. These specifications provide a common framework for defining usage policies, attribute requirements, and developer APIs pertaining to the use of identity related information. These enable businesses to ensure full documentation, control, and auditing regarding the use, storage, and propagation of identity-related data across systems and applications.

This section contains the following topics:

- [Section 1.1.1, "Benefits to Organizations"](#)
- [Section 1.1.2, "Benefits to Developers"](#)

### 1.1.1 Benefits to Organizations

Organizations need to maintain control and integrity of sensitive personal information about their customers, employees, and partners. Data related to social security numbers, credit card numbers, medical history and more are increasingly under scrutiny by regulations seeking to prevent abuse or theft of such information. Privacy conscious organizations frequently have reacted to these requirements by enforcing

overly strict controls and processes that hinder business operations and impact productivity, flexibility, and efficiency. At the opposite end of the spectrum, some organizations do not take the care needed to safeguard this information, potentially putting identity-related data at risk without sufficient oversight and control. The Identity Governance Framework enables a standards-based mechanism for enterprises to establish "contracts" between their applications so that identity related information can be shared securely and with confidence that this data will not be abused, compromised, or misplaced. Using this framework, organizations have complete visibility into how identity information is stored, used, and propagated throughout their business. This enables organizations to automate controls to streamline business processes without fear of compromising the confidentiality of sensitive identity related information.

### 1.1.2 Benefits to Developers

The Identity Governance Framework is an agreed-upon process for specifying how identity-related data is treated when writing applications. This provides developers a standards-based way to easily write applications that use this data so that governing policies can be used to control it. This will result in faster development of privacy aware applications.

IGF enables the decoupling of identity-aware applications from a specific deployment infrastructure. Specifically, using IGF enables developers to defer deciding how identity related information will be stored and accessed by their application. Developers do not need to worry about whether they should use a SQL database, an LDAP directory, or other system. In the past, developers were forced to write highly specific code, driving technology and vendor lock-in.

For example, The Identity Directory API provides methods for accessing and managing identity information in a directory server that is the domain identity store. Entity definitions, entity relationships, and the physical identity store details can be configured using either the Identity Directory Configuration APIs or Mbeans. The Identity Directory API is used to initialize the Identity Directory Service. The Identity Directory Service provides an interface to both access and modify users and group information from different identity stores. For more information, see [Chapter 2, "Using the Identity Directory API"](#).

Another example is the ArisID API, which handles the hard work of data retrieval, transformation, and policy-enforcement when it comes to identity-based information. By using a Client Attribute Requirement Markup Language (CARML) file and declarations, applications will support flexible deployment in a wide range of environments without the need for ongoing specialized developer enhancements. For more information, see [Chapter 3, "Using the ArisID API"](#).

## 1.2 About the Identity Governance Framework APIs

Oracle has made the following APIs available that are based on the Identity Governance Framework:

- **Identity Directory API**

The Identity Directory API is a common service for identity management applications to access and manage identity information. The service can be used in both Java EE and Java SE modes. For more information, see [Chapter 2, "Using the Identity Directory API"](#).

- **ArisID API**

The ArisID API provides enterprise developers and system architects a library for building identity-enabled applications using multiple identity protocols. The ArisID API enables developers to specify requirements for identity attributes, roles, and search filters by using Client Attribute Requirements Markup Language (CARML). For more information, see [Chapter 3, "Using the ArisID API"](#).

## 1.3 System Requirements and Certification

Refer to the system requirements and certification documentation for information about hardware and software requirements, platforms, databases, and other information. Both of these documents are available on Oracle Technology Network (OTN).

The system requirements document covers information such as hardware and software requirements, minimum disk space and memory requirements, and required system libraries, packages, or patches:

<http://www.oracle.com/technetwork/middleware/ias/downloads/fusion-requirements-100147.html>

The certification document covers supported installation types, platforms, operating systems, databases, JDKs, and third-party products:

<http://www.oracle.com/technetwork/middleware/ias/downloads/fusion-certification-100350.html>





---

---

## Using the Identity Directory API

This chapter describes the architecture and key functionality of the Identity Governance Framework Identity Directory API (Identity Directory API) and Identity Directory Service. The Identity Directory API supports accessing and managing users, groups, organizations, and can be extended to support new entity types with relationships defined between these entities. This chapter contains the following topics:

- [Section 2.1, "About Identity Directory API"](#)
- [Section 2.2, "Configuring Identity Directory API"](#)
- [Section 2.3, "Design Recommendations"](#)
- [Section 2.4, "Examples"](#)

### 2.1 About Identity Directory API

The Identity Directory API provides a service for identity management applications to access and manage identity information. The API is flexible and fully configurable by clients supporting heterogeneous identity stores having standard and specific schemas, and is robust with both high-availability and failover support.

The API uses the Identity Governance Framework and provides all the benefits of Identity Governance. The API can be used in both Java EE and Java SE modes. For more information about the Identity Governance Framework, see [Chapter 1, "Introduction to Identity Governance Framework"](#).

The API supports the following actions:

- Create/Read/Update/Delete (CRUD) operations on User, Group, Org, and generic entities
- Get operation on User Account State
- Identity Directory API configuration sharing
- Support for directory servers such as Oracle Internet Directory, Oracle Unified Directory, Oracle Directory Server EE, and AD.

Identity Directory Service consists of the following:

- **Identity Directory API**

The Identity Directory API provide methods for accessing and managing identity information in a directory server that is the domain identity store. Entity definitions, entity relationships, and the physical identity store details can be configured using either the Identity Directory Configuration APIs or Mbeans. Directory service instance capabilities can be queried using getter methods.

- **Identity Directory API Configuration**

Identity Directory API configuration comprises logical entity configuration and physical identity store configuration.

### 2.1.1 About the Identity Directory Service

The Identity Directory Service is a common service used by identity management products to access and manage an Identity Directory. The Identity Directory API is used to initialize the Identity Directory Service. The Identity Directory Service provides an interface to both access and modify users and group information from different identity stores. An Identity Directory is an instance of the Identity Directory Service having:

- a unique name (IDS name)
- a logical entity configuration
- a physical identity store configuration

### 2.1.2 Identity Directory Service Architecture

Figure 2–2 shows the logical architecture of the Identity Directory API.

**Figure 2–1 Identity Directory API Architecture**





Figure 2–2 shows the relationship between the Identity Directory API components.

**Figure 2–2 Identity Directory API Components**

## 2.2 Configuring Identity Directory API

The Identity Directory API provides an interface to access and modify users and group information from different identity stores.

The Identity Directory Service configuration is a combination of the logical entity configuration, the physical identity store configuration, and operational configuration.

The logical entity configuration and operational configuration is stored in `ids-config.xml`. This file is located in the same directory as `jps-config.xml`. For example, in a Java EE environment the location is:

```
DOMAIN_HOME/config/fmwconfig/ids-config.xml
```

The physical identity store configuration is stored in `ovd/ids/adapters.os.xml`. For example, in a Java EE environment the `ovd` directory is located in:

```
DOMAIN_HOME/config/fmwconfig
```

This section contains the following topics:

- Section 2.2.1, "Logical Entity Configuration"
- Section 2.2.2, "Physical Identity Store Configuration"
- Section 2.2.3, "Operational Configuration"

### 2.2.1 Logical Entity Configuration

Table 2–1 describes the logical entity configuration properties.

**Table 2–1 Logical Entity Configuration Properties**

Name	Description
<code>name</code>	Name that uniquely identifies the Identity Directory Service.
<code>description</code>	Detailed description of the Identity Directory Service.
<code>ovd.context</code>	Valid values are <code>default</code> or <code>ids</code> . Use <code>default</code> for connecting to the same identity store configured in OPSS. Use <code>ids</code> to connect to any physical identity store configured independent of OPSS. Only out-of-the-box identity directories, that is <code>userrole</code> and <code>idxuserrole</code> , use <code>default</code> value.
<code>app.name</code>	Optional property to specify the specific application for which the Identity Directory Service is being configured.

Table 2–2 describes the logical attributes.

**Table 2–2 Logical Entity Attributes**

Name	Description
name	Logical attribute name.
dataType	Valid data type values are as follows: string, boolean, integer, double, datetime, binary, x500name, and rfc822name.
description	Detailed description of the logical attribute.
readOnly	Default is false. Use true if the attribute is read-only.
pwdAttr	Default is false. Use true if the attribute is a password attribute.

Table 2–3 describes the properties required in each logical entity definition.

**Table 2–3 Logical Entity Definition Properties**

Name	Description
name	Name of the entity.
type	Valid entity values are as follows: user, group, org and other.
idAttr	Logical attribute that uniquely identifies the entity.
create	Use true if creating this entity is allowed. Use false otherwise.
modify	Use true if modifying this entity is allowed. Use false otherwise.
delete	Use true if deleting this entity is allowed. Use false otherwise.
search	Use true if search of this entity to be allowed. Use false otherwise.
Attribute References	List of entity attribute references that contain the following details: <ul style="list-style-type: none"> <li>▪ name: Logical attribute name.</li> <li>▪ defaultFetch: Default value is true. Use true if the attribute will be fetched by default. For example, when the entity is read using Identity Directory API, this attribute value is fetched from the identity store even though this attribute is not included in the requested attributes.</li> <li>▪ filter: Search filter type with one of the following valid values: none, dynamic, equals, notequals, beginswith, contains, doesnotcontain, endswith, greaterequal, lessequal, greaterthan, and lessthan. Value none means no filter support.</li> </ul>

Table 2–4 describes the properties required in each logical entity relationship definition.

**Table 2–4 Logical Entity Relationship Properties**

Name	Description
name	Name of the entity relationship.
type	Valid entity values are as follows: OneToOne, OneToMany, ManyToOne, and ManyToMany.
fromEntity	Name of the first entity in the Entity Relationship.

**Table 2–4 (Cont.) Logical Entity Relationship Properties**

Name	Description
fromAttr	The first entity's attribute. Value of this attribute relates to the second entity in the relationship.
toEntity	Name of the second entity in the Entity Relationship.
toAttr	The second entity's attribute. Value of the fromAttr property maps to this attribute in second entity.
recursive	Use true if the entity relationship is recursive. Default is false.

## 2.2.2 Physical Identity Store Configuration

Table 2–5 describes the physical identity store configuration properties.

**Table 2–5 Physical Identity Store Configuration Properties**

Name	Description
Host and Port	Host and Port information of the Identity Store. Alternate Host and Port details also can be setup for failover.
Directory Type	Type of directory. Valid values are: <code>OID</code> , <code>ACTIVE_DIRECTORY</code> , <code>IPLANET</code> , <code>EDIRECTORY</code> , <code>OPEN_LDAP</code> , <code>WLS_OVD</code> , and <code>ODU</code> .
Bind DN and Password	Credentials to connect to the directory.

## 2.2.3 Operational Configuration

The operational configuration contains mainly `base`, `name` attribute, and `objectclass` configuration for each of the entities.

Table 2–6 describes the operational configuration entities.

**Table 2–6 Operational Configuration Entities**

Name	Description
entity.searchbase	Container under which the entity should be searched.
entity.createbase	Container where the new entity will be created.
entity.name.attr	RDN attribute of the entity.
entity.filter.objclasses	The <code>objectclass</code> filters to be used while searching this entity.
entity.create.objclasses	The <code>objectclasses</code> to be added while creating this new entity.

## 2.3 Design Recommendations

This section contains the following topics:

- [Section 2.3.1, "Keep the defaultFetch Attributes Minimal"](#)
- [Section 2.3.2, "Initialize the Identity Directory Once"](#)

### 2.3.1 Keep the defaultFetch Attributes Minimal

While configuring a new Identity Directory, try to keep the number of entity `defaultFetch` attributes minimal. Also, try to have large attributes like `jpegphoto` configured with a `defaultFetch` value of `false`. The reason is every time the entity is read from the backend, all the `defaultFetch` attributes from backend directory will be retrieved. Too many `defaultFetch` attributes will affect the performance.

## 2.3.2 Initialize the Identity Directory Once

Initialization of Identity Directory has some overhead to initialize the entire ArisId stack. As a result, applications should initialize the Identity Directory once, preferably on application startup, and use only one handle throughout.

## 2.4 Examples

This section provides the following code samples:

- Section 2.4.1, "Initialize and Obtain Identity Directory Handle"
- Section 2.4.2, "Initialize and Obtain Identity Directory Handle from JPS Context"
- Section 2.4.3, "Initialize and Obtain In-Memory Identity Directory Handle"
- Section 2.4.4, "Add User"
- Section 2.4.5, "Get User for Given Principal"
- Section 2.4.6, "Modify User"
- Section 2.4.7, "Get User for Given ID Value"
- Section 2.4.8, "Search Users Using Complex Search Filter"
- Section 2.4.9, "Change User Password"
- Section 2.4.10, "Reset User Password"
- Section 2.4.11, "Authenticate User"
- Section 2.4.12, "Delete User"
- Section 2.4.13, "Create Group"
- Section 2.4.14, "Search Groups"
- Section 2.4.15, "Get Management Chain"
- Section 2.4.16, "Get Reportees of a User"
- Section 2.4.17, "Add a Member to a Group"
- Section 2.4.18, "Delete a Member From Group"
- Section 2.4.19, "Get All The Groups User is a Member"

### 2.4.1 Initialize and Obtain Identity Directory Handle

The following code sample initializes and obtains a handle to the identity directory:

```
import oracle.igf.ids.UserManager;
import oracle.igf.ids.GroupManager;
import oracle.igf.ids.config.OperationalConfig;
import oracle.igf.ids.IdentityDirectoryFactory;
import oracle.igf.ids.IdentityDirectory;
import oracle.igf.ids.IDSEException;

public class IdsSample {

    private IdentityDirectory ids;
    private UserManager uMgr;
    private GroupManager gMgr;

    public IdsSample() throws IDSEException {
```

```

        // Set Operational Config
        OperationalConfig opConfig = new OperationalConfig();

        // Set the application credentials (optional). This
        overrides the credentials set in
        // physical ID store configuration
        opConfig.setApplicationUser("cn=user1,dc=us,dc=example,dc=com");
        opConfig.setApplicationPassword("password".toCharArray());

        // Set search/crate base, name, objclass, etc. config
        (optional). This overrides default operational configuration
        in IDS
        opConfig.setEntityProperty("User", opConfig.SEARCH_BASE,
        "dc=us,dc=example,dc=com");
        opConfig.setEntityProperty("User", opConfig.CREATE_BASE,
        "dc=us,dc=example,dc=com");
        opConfig.setEntityProperty("User", opConfig.FILTER
        _OBJCLASSES, "person");
        opConfig.setEntityProperty("User", opConfig.CREATE
        _OBJCLASSES, "inetorgperson");
        opConfig.setEntityProperty("Group", opConfig.SEARCH
        _BASE, "cn=groups,dc=us,dc=example,dc=com");
        opConfig.setEntityProperty("Group", opConfig.CREATE
        _BASE, "cn=groups,dc=us,dc=example,dc=com");
        opConfig.setEntityProperty("Group", opConfig.FILTER
        _OBJCLASSES, "groupofuniquenames");
        opConfig.setEntityProperty("Group", opConfig.CREATE
        _OBJCLASSES, "groupofuniquenames");

        // Get IdentityDirectory "ids1" configured in IDS config
        IdentityDirectoryFactory factory = new
        IdentityDirectoryFactory();
        ids = factory.getIdentityDirectory("ids1", opConfig);

        // Get UserManager and GroupManager handles
        uMgr = ids.getUserManager();
        gMgr = ids.getGroupManager();
    }
}

```

## 2.4.2 Initialize and Obtain Identity Directory Handle from JPS Context

The following code sample initializes and obtains the identity directory handle from JPS context.

```

import oracle.igf.ids.UserManager;
import oracle.igf.ids.GroupManager;
import oracle.igf.ids.config.OperationalConfig;
import oracle.igf.ids.IdentityDirectoryFactory;
import oracle.igf.ids.IdentityDirectory;
import oracle.igf.ids.IDSException;

import oracle.security.jps.JpsContext;
import oracle.security.jps.JpsContextFactory;
import oracle.security.jps.service.idstore.IdentityStoreService;

public class IdsSample {

    private IdentityDirectory ids;
    private UserManager uMgr;

```

```

private GroupManager gMgr;

public IdsSample() throws IDSEException {

    // Get IdentityDirectory from JpsContext
    try {
        JpsContext context =
JpsContextFactory.getContextFactory().getContext();
        IdentityStoreService idstore = (IdentityStoreService)
context.getServiceInstance(IdentityStoreService.class);
        ids = idstore.getIdentityStore();
    } catch (Exception e) {
        throw new IDSEException(e);
    }

    // Get UserManager and GroupManager handles
    uMgr = ids.getUserManager();
    gMgr = ids.getGroupManager();
}
}

```

### 2.4.3 Initialize and Obtain In-Memory Identity Directory Handle

The following code sample initializes and obtains the in-memory identity directory handle.

```

import java.util.ArrayList;
import java.util.List;

import oracle.igf.ids.UserManager;
import oracle.igf.ids.GroupManager;
import oracle.igf.ids.config.AttributeDef;
import oracle.igf.ids.config.AttributeRef;
import oracle.igf.ids.config.EntityDef;
import oracle.igf.ids.config.EntitiesConfig;
import oracle.igf.ids.config.EntityRelationship;
import oracle.igf.ids.config.IdentityStoreConfig;
import oracle.igf.ids.config.OperationalConfig;
import oracle.igf.ids.IdentityDirectoryFactory;
import oracle.igf.ids.IdentityDirectory;
import oracle.igf.ids.IDSEException;

public class IdsSample {

    private IdentityDirectory ids;
    private UserManager uMgr;
    private GroupManager gMgr;
    public IdsSample() throws IDSEException {

        // Add Attribute definitions
        List<AttributeDef> attrDefs = new ArrayList<AttributeDef>();
        attrDefs.add(new AttributeDef("cn", AttributeDef.DataType.STRING));
        attrDefs.add(new AttributeDef("firstname", AttributeDef.DataType.STRING));
        attrDefs.add(new AttributeDef("sn", AttributeDef.DataType.STRING));
        attrDefs.add(new AttributeDef("telephonenumber",
AttributeDef.DataType.STRING));
        attrDefs.add(new AttributeDef("uid", AttributeDef.DataType.STRING));
        attrDefs.add(new AttributeDef("uniquemember",
AttributeDef.DataType.STRING));
    }
}

```



```

// Add User entity definition
List<EntityDef> entityDefs = new ArrayList<EntityDef>();
EntityDef userEntityDef = new EntityDef("User", EntityDef.EntityType.USER,
"cn");
userEntityDef.addAttribute(new AttributeRef("cn"));
userEntityDef.addAttribute(new AttributeRef("firstname"));
userEntityDef.addAttribute(new AttributeRef("sn"));
userEntityDef.addAttribute(new AttributeRef("telephonenumber"));
userEntityDef.addAttribute(new AttributeRef("uid"));
entityDefs.add(userEntityDef);

// Add Group entity definition
EntityDef groupEntityDef = new EntityDef("Group",
EntityDef.EntityType.GROUP, "cn");
groupEntityDef.addAttribute(new AttributeRef("cn"));
groupEntityDef.addAttribute(new AttributeRef("uniquemember", false,
AttributeRef.FilterType.EQUALS));
entityDefs.add(groupEntityDef);

// Add Entity relationship definition
List<EntityRelationship> entityRelations = new
ArrayList<EntityRelationship>();
entityRelations.add(new EntityRelationship("user_memberOfGroup",
EntityRelationship.RelationshipType.MANYTOMANY, "User",
"principal", "Group", "uniquemember"));
entityRelations.add(new EntityRelationship("group_memberOfGroup",
EntityRelationship.RelationshipType.MANYTOMANY, "Group",
"principal", "Group", "uniquemember", true));
EntitiesConfig entityCfg = new EntitiesConfig(attrDefs,
entityDefs, entityRelations);

// Create physical Identity Store configuration
IdentityStoreConfig idStoreCfg = new IdentityStoreConfig(
"ldap://host1:389,ldap://host2:389", "cn=orcladmin",
"password".toCharArray(), IdentityStoreConfig.IdentityStoreType.OID);

idStoreCfg.setHighAvailabilityOption(IdentityStoreConfig.HAOption.FAILOVER);
idStoreCfg.setProperty(IdentityStoreConfig.HEARTBEAT_INTERVAL, "60");
idStoreCfg.setProperty(IdentityStoreConfig.CONN_TIMEOUT, "30000"); //
milli sec
idStoreCfg.setProperty(IdentityStoreConfig.MIN_POOLSIZE, "5");
idStoreCfg.setProperty(IdentityStoreConfig.MAX_POOLSIZE, "10");
idStoreCfg.setProperty(IdentityStoreConfig.MAX_POOLWAIT, "1000"); //
milli sec
idStoreCfg.setProperty(IdentityStoreConfig.MAX_POOLCHECKS, "10");
idStoreCfg.setProperty(IdentityStoreConfig.FOLLOW_REFERRAL, "false");
idStoreCfg.setAttrMapping("firstname", "givenname");

// Set operational config
OperationalConfig opConfig = new OperationalConfig();
opConfig.setEntityProperty(opConfig.USER_ENTITY, opConfig.SEARCH_BASE,
"cn=users,dc=us,dc=example,dc=com");
opConfig.setEntityProperty(opConfig.USER_ENTITY, opConfig.CREATE_BASE,
"cn=users,dc=us,dc=example,dc=com");
opConfig.setEntityProperty(opConfig.USER_ENTITY, opConfig.NAME_ATTR,
"cn");
opConfig.setEntityProperty(opConfig.USER_ENTITY, opConfig.FILTER
_OBJCLASSES, "inetorgperson");

```

```

        opConfig.setEntityProperty(opConfig.USER_ENTITY, opConfig.CREATE
_OBJCLASSES, "inetorgperson");
        opConfig.setEntityProperty(opConfig.GROUP_ENTITY, opConfig.SEARCH_BASE,
"cn=groups,dc=us,dc=example,dc=com");
        opConfig.setEntityProperty(opConfig.GROUP_ENTITY, opConfig.CREATE_BASE,
"cn=groups,dc=us,dc=example,dc=com");
        opConfig.setEntityProperty(opConfig.GROUP_ENTITY, opConfig.NAME_ATTR,
"cn");
        opConfig.setEntityProperty(opConfig.GROUP_ENTITY, opConfig.FILTER
_OBJCLASSES, "groupofuniquenames");
        opConfig.setEntityProperty(opConfig.GROUP_ENTITY, opConfig.CREATE
_OBJCLASSES, "groupofuniquenames");

        // Initialize Identity Store Service
        IdentityDirectoryFactory factory = new IdentityDirectoryFactory();
        ids = factory.getIdentityDirectory("ids1", entityCfg, idStoreCfg,
opConfig);

        // Get UserManager and GroupManager handles
        uMgr = ids.getUserManager();
        gMgr = ids.getGroupManager();
    }
}

```

## 2.4.4 Add User

The following code sample adds a user to the identity store:

```

Principal principal = null;

List<Attribute> attrs = new ArrayList<Attribute>();
attrs.add(new Attribute("commonname", "test1_user1"));
attrs.add(new Attribute("password", "mypassword".toCharArray()));
attrs.add(new Attribute("firstname", "test1"));
attrs.add(new Attribute("lastname", "user1"));
attrs.add(new Attribute("mail", "test1.user1@example.com"));
attrs.add(new Attribute("telephone", "1 650 123 0001"));
attrs.add(new Attribute("title", "Senior Director"));
attrs.add(new Attribute("uid", "tuser1"));

try {
    CreateOptions createOpts = new CreateOptions();

    principal = uMgr.createUser(attrs, createOpts);

    System.out.println("Created user " + principal.getName());

} catch (Exception e) {
    System.out.println(e.getMessage());
    e.printStackTrace();
}

```

## 2.4.5 Get User for Given Principal

The following code sample gets a user for a given principal.

```

User user = null;

    try {
        ReadOptions readOpts = new ReadOptions();

        user = uMgr.getUser(principal, readOpts);

    } catch (Exception e) {
        System.out.println(e.getMessage());
        e.printStackTrace();
    }

```

## 2.4.6 Modify User

The following code sample modifies a user in the identity directory.

```

try {

    ModifyOptions modifyOpts = new ModifyOptions();

    List<ModAttribute> attrs = new ArrayList<ModAttribute>();
    attrs.add(new ModAttribute("description", "modified test user 1"));

    user.modify(attrs, modifyOpts);

    System.out.println("Modified user " + user.getName());
} catch (Exception e) {
    System.out.println(e.getMessage());
    e.printStackTrace();
}

```

## 2.4.7 Get User for Given ID Value

The following code sample gets a user matching the given identity value.

```

try {

    ReadOptions readOpts = new ReadOptions();

    User user = uMgr.searchUser("tuser1", readOpts);

} catch (Exception e) {
    System.out.println(e.getMessage());
    e.printStackTrace();
}

```

## 2.4.8 Search Users Using Complex Search Filter

The following code sample shows how to search for users using a complex search filter.

```

try {

    // Complex search filter with nested AND and OR conditions
    SearchFilter filter = new SearchFilter(
        SearchFilter.LogicalOp.OR,
        new SearchFilter(SearchFilter.LogicalOp.AND,
            new SearchFilter("firstname", SearchFilter.Operator.BEGINS_WITH,
                "test"),
            new SearchFilter("telephone", SearchFilter.Operator.CONTAINS,

```

```

"650")),
        new SearchFilter(SearchFilter.LogicalOp.AND,
            new SearchFilter("firstname", SearchFilter.Operator.BEGINS_WITH,
"demo"),
            new SearchFilter(SearchFilter.LogicalOp.OR,
                new SearchFilter("orgunit", SearchFilter.Operator.BEGINS_WITH,
"hr"),
                new SearchFilter("orgunit", SearchFilter.Operator.BEGINS_WITH,
"it"),
            new SearchFilter("telephone", SearchFilter.Operator.CONTAINS,
"650")));

    // Requesting attributes
    List<String> reqAttrs = new ArrayList<String>();
    reqAttrs.add("jpegphoto");

    SearchOptions searchOpts = new SearchOptions();
    searchOpts.setPageSize(100);
    searchOpts.setRequestedAttrs(reqAttrs);
    searchOpts.setSortAttrs(new String[] {"firstname"});

    ResultSet<User> sr = uMgr.searchUsers(filter, searchOpts);
    while (sr.hasMore()) {
        User user = sr.getNext();
        System.out.println(user.getSubjectName());
    }

} catch (Exception e) {
    System.out.println(e.getMessage());
    e.printStackTrace();
}
}

```

## 2.4.9 Change User Password

The following code sample shows how to change a user password.

```

ModifyOptions modOpts = new ModifyOptions();

try {
    user.changePassword("welcome123".toCharArray(),
"welcome1".toCharArray(), modOpts);
    System.out.println("Changed user password");
} catch (Exception e) {
    System.out.println("Failed to change user password");
    e.printStackTrace();
}
}

```

## 2.4.10 Reset User Password

The following code sample shows how to reset a user password.

```

ModifyOptions modOpts = new ModifyOptions();

try {
    user.resetPassword("welcome123".toCharArray(), modOpts);
    System.out.println("Reset user password");
} catch (Exception e) {
}
}

```

```

        System.out.println("Failed to reset user password");
        e.printStackTrace();
    }
}

```

### 2.4.11 Authenticate User

The following code sample shows how to authenticate a user.

```

ReadOptions readOpts = new ReadOptions();
try {
    User user = uMgr.authenticateUser("tuser1",
    "mypassword".toCharArray(), readOpts);
    System.out.println("authentication success");
} catch (Exception e) {
    System.out.println("Authentication failed. " + e.getMessage());
    e.printStackTrace();
}

```

### 2.4.12 Delete User

The following code sample shows how to delete a user.

```

try {
    DeleteOptions deleteOpts = new DeleteOptions();

    uMgr.deleteUser(principal, deleteOpts);

    System.out.println("Deleted user " + principal.getName());

} catch (Exception e) {
    System.out.println(e.getMessage());
    e.printStackTrace();
}

```

### 2.4.13 Create Group

The following code sample shows how to create a group.

```

Principal principal = null;

List<Attribute> attrs = new ArrayList<Attribute>();
attrs.add(new Attribute("name", "test1_group1"));
attrs.add(new Attribute("description", "created test group 1"));
attrs.add(new Attribute("displayname", "test1 group1"));
try {
    CreateOptions createOpts = new CreateOptions();

    principal = gMgr.createGroup(attrs, createOpts);

    System.out.println("Created group " + principal.getName());
} catch (Exception e) {
    System.out.println(e.getMessage());
    e.printStackTrace();
}

```

## 2.4.14 Search Groups

The following code sample shows how to search groups.

```
public void searchGroups() {

    try {
        SearchFilter filter = new SearchFilter("name",
            SearchFilter.Operator.BEGINS_WITH, "test");

        SearchOptions searchOpts = new SearchOptions();
        searchOpts.setPageSize(10);

        ResultSet<Group> sr = gMgr.searchGroups(filter, searchOpts);
        while (sr.hasMore()) {
            Group group = sr.getNext();
            System.out.println(group.getSubjectName());
        }

    } catch (Exception e) {
        System.out.println(e.getMessage());
        e.printStackTrace();
    }
}
```

## 2.4.15 Get Management Chain

The following code sample shows how to get a management chain.

```
try {

    ReadOptions readOpts = new ReadOptions();
    User user = uMgr.searchUser("tuser1", readOpts);

    SearchOptions searchOpts = new SearchOptions();
    searchOpts.setPageSize(10);
    int nLevels = 0;

    ResultSet<User> sr = user.getManagementChain(nLevels, searchOpts);
    while (sr.hasMore()) {
        User u = sr.getNext();
        System.out.println(u.getSubjectName());
    }

} catch (Exception e) {
    System.out.println(e.getMessage());
    e.printStackTrace();
}
```

## 2.4.16 Get Reportees of a User

The following code sample shows how to get the reportees of user.

```
// Get Reportees with target search filter
public void getReportees() {

    try {
        ReadOptions readOpts = new ReadOptions();
        User user = uMgr.searchUser("tuser1", readOpts);

        SearchOptions searchOpts = new SearchOptions();
```

```

        searchOpts.setPageSize(20);
        int nLevels = 0;

        // get all the direct/indirect reporting of tuser1 who are
        "developers"
        SearchFilter filter = new SearchFilter("title",
        SearchFilter.Operator.CONTAINS, "developer");
        ResultSet<User> sr = user.getReportees(nLevels, filter, searchOpts);
        while (sr.hasMore()) {
            User u = sr.getNext();
            System.out.println(u.getSubjectName());
        }
    } catch (Exception e) {
        System.out.println(e.getMessage());
        e.printStackTrace();
    }
}

```

### 2.4.17 Add a Member to a Group

The following code sample adds a member to a group.

```

try {
    ReadOptions readOpts = new ReadOptions();
    User user = uMgr.searchUser("tuser1", readOpts);
    Group group = gMgr.searchGroup("test1_group1", readOpts);

    ModifyOptions modOpts = new ModifyOptions();
    user.addMemberOf(group, modOpts);

    System.out.println("added tuser1 as a member of test1_group1");

} catch (Exception e) {
    System.out.println(e.getMessage());
    e.printStackTrace();
}

```

### 2.4.18 Delete a Member From Group

The following code sample deletes a member from a group.

```

try {
    ReadOptions readOpts = new ReadOptions();
    User user = uMgr.searchUser("tuser1", readOpts);
    Group group = gMgr.searchGroup("test1_group1", readOpts);

    ModifyOptions modOpts = new ModifyOptions();
    group.deleteMember(user, modOpts);

    System.out.println("deleted tuser1 from the group test1_group1");

} catch (Exception e) {
    System.out.println(e.getMessage());
    e.printStackTrace();
}

```

---

---

**Note:** Identity Governance Framework/Identity Directory Service group membership search evaluates both static and dynamic groups. However, membership updates (addition/deletion) are not supported for dynamic groups. For instance, if you wish to delete a member from a group and the member is a dynamic member of that group, then the delete operation is not supported for the dynamic group.

---

---

### 2.4.19 Get All The Groups User is a Member

The following code sample gets all the groups in which user is a member.

```
try {
    ReadOptions readOpts = new ReadOptions();
    User user = uMgr.searchUser("tuser1", readOpts);

    SearchOptions searchOpts = new SearchOptions();
    searchOpts.setPageSize(10);
    int nLevels = 0;

    ResultSet<Group> sr = user.getMemberOfGroups(nLevels, null,
searchOpts);
    while (sr.hasMore()) {
        Group group = sr.getNext();
        System.out.println(group.getSubjectName());
    }

} catch (Exception e) {
    System.out.println(e.getMessage());
    e.printStackTrace();
}
```



---

## Using the ArisID API

This chapter describes the architecture and key functionality of the Identity Governance Framework ArisID API (ArisID API). The ArisID API provides enterprise developers and system architects a library for building identity-enabled applications using multiple identity protocols. The ArisID API enables developers to specify requirements for identity attributes, roles, and search filters by using Client Attribute Requirements Markup Language (CARML). This chapter contains the following topics:

- Section 3.1, "About ArisID API"
- Section 3.2, "Configuring ArisID API"
- Section 3.3, "Design Recommendations"
- Section 3.4, "Generating ArisID Beans"
- Section 3.5, "Sample Application Using IDX User and Role Beans"
- Section 3.6, "OpenLDAP Considerations"

### 3.1 About ArisID API

The Identity Governance Framework ArisID API represents a common core service through which all identity information exchanged should be passed. While not an official name, the ArisID API is often referred to as Identity Beans by developers.

The 11g Release 1 (11.1.1) release of the ArisID API is a subset of the configuration proposed at:

[http://www.openliberty.org/wiki/index.php/ArisID\\_Configuration](http://www.openliberty.org/wiki/index.php/ArisID_Configuration).

If you have installed Oracle WebLogic Server and Oracle Identity Management, all the necessary jar files for developing applications with this API are already installed on your computer.

**See Also:** *Oracle Fusion Middleware Installation Guide for Oracle Identity Management* for information about installing Oracle Identity Management.

The Identity Governance Framework open source API jar files are as follows:

- **openliberty.arisId\_1.1.jar** — Provides the core ArisID API with library functions and providers that can be used to retrieve identity subjects that contain collections of attributes. For more information, see [http://arisid.sourceforge.net/javadocs/arisId\\_1.1\\_javadoc/](http://arisid.sourceforge.net/javadocs/arisId_1.1_javadoc/).

- **org.openliberty.arisIdBeans\_1.1.jar** — Provides the ArisID beans, which provide Java object abstractions on top of the ArisID API. These convert the transactional approach of the ArisID API to an object or bean approach. For more information, see [http://arisid.sourceforge.net/javadocs/arisId\\_1.1\\_javadoc/](http://arisid.sourceforge.net/javadocs/arisId_1.1_javadoc/).


The ArisID API jar files are as follows:

- **idxuserrole.jar** — Provides the Standard User and Role identity read-only operations. This jar is generated from the standard idxuserrole.xml CARML file. For more information, see *Oracle Fusion Middleware Identity Governance Framework IDXUserRole Java API Reference*.
- **userrole.jar** — Provides the User and Role identity read/write operations for updating identity information. For more information, see *Oracle Fusion Middleware Identity Governance Framework UserRole Java API Reference*.
- **arisId-stack-ovd.jar** — This jar file is an implementation of the IAttrSvcStack interface with the Oracle Virtualization library to connect to different backends and provide an abstract view of the identity store entities.

The ArisID beans provide the Java APIs required for initialization and accessing CARML interactions. The bean generator generates a set of java files for each entity in the CARML file using Apache Velocity. The CARML file is a declarative document that describes the attribute usage requirements of your application. The ArisID beans are in the jar files idxuserrole.jar and userrole.jar.

The following figure provides a high-level view of the ArisID API architecture.

**Figure 3–1 IGF ArisID API Architecture**



## 3.2 Configuring ArisID API

The Identity Governance Framework ArisID supports the basic development process Create > Modify > Test > Deploy. Creation requires CARML XML files and modifying them to suit your environment. Testing the application can be done in Oracle WebLogic Server embedded LDAP directory server.

This section contains the following topics:

- [Section 3.2.1, "Configuring CARML Files"](#)
- [Section 3.2.2, "Configuring the Identity Repository"](#)
- [Section 3.2.3, "Configuring the Mapping File"](#)

### 3.2.1 Configuring CARML Files

Determine whether the existing ArisID beans meet your application's needs by examining the CARML files `idxuserrole.xml` (read-only operations) and `userrole.xml` (read-only and read/write operations). These files are located in `DOMAIN_HOME/config/fmwconfig/carml`.

### 3.2.2 Configuring the Identity Repository

The identity repository to be used by the ArisID beans must be available. You can use the Oracle WebLogic Server embedded LDAP-based directory server or any LDAP directory supported by 11g Oracle Virtual Directory. The ArisID API is integrated with Oracle Platform Security Services. It automatically connects to the LDAP-based identity store configured in Oracle Platform Security Services. For more information about the identity stores supported by Oracle Platform Security Services, see [Section 1.3, "System Requirements and Certification."](#)

For more information about Oracle Platform Security Services, see *Oracle Fusion Middleware Application Security Guide*.

If you must use a different identity store from the Oracle Platform Security Services identity store, then set the following system property:

```
igf.ovd.config.dir=DOMAIN_HOME/config/fmwconfig/arisidprovider/conf
```

Next, edit the `adapters.os_xml` file to include the `host`, `port` and credentials of the directory to be connected to. The `igf.ovd.config.dir` property can be set to any other directory containing `adapters.os_xml` and other configuration files with the right settings.

#### Directory Limitations

The following LDAP directory limitations apply:

- When using OpenLDAP 2.2 or Novell eDirectory, there is no paging support. Paging APIs, for example, `searchUsersbyPage()`, `searchRolesbyPage()`, etc., do not work. There is no Multiple Language Support (MLS).
- When using Oracle WebLogic Server embedded LDAP-based directory server, there is no Multiple Language Support (MLS).

### 3.2.3 Configuring the Mapping File

When a CARML file is created a corresponding mapping file is created in the same location. The default mapping file has attribute details specific to Oracle WebLogic Server embedded directory server, which is the Oracle Platform Security Services

default identity store. If you are using a default CARML file and the Oracle Platform Security Services identity store, you do not need to configure mapping. The configuration parameters in Oracle Platform Security Services override the parameters in the mapping file.

## 3.3 Design Recommendations

The default CARML and mapping files make certain assumptions about the deployment scenario. You may need to modify these details depending on your deployment requirements. The configuration parameters that can be modified are discussed in this section.

This section contains the following topics:

- [Section 3.3.1, "Choose a LoginID"](#)
- [Section 3.3.2, "Choose a UniqueKey"](#)
- [Section 3.3.3, "Specify Multiple Language Support"](#)
- [Section 3.3.4, "Handle Large Results"](#)
- [Section 3.3.5, "Secure the Application"](#)
- [Section 3.3.6, "Configure the Timeout Interval"](#)
- [Section 3.3.7, "Specifying Wildcard Characters in Search Filters"](#)

### 3.3.1 Choose a LoginID

In the default configuration, `email` is used as a unique identifier for identifying user entries. When you are searching for a user, the default attribute expected for search is `email`. For example:

```
SearchUser( String uniqueid, Map<String, Object>)
```

For performance reasons, the attribute used as a unique identifier must be a searchable attribute in the backend. The mapping between the application's choice of `uniquekey` and the backend attribute is handled at configuration time. This is a configuration in Oracle Virtual Directory mapping. The `HashMap` is used to provide the optional context information to be used while performing the operation. In the current release it supports the following options:

- The Principal user that performs the search - (`ArisIdConstants.APP_CTX_AUTHUSER`, `(Principal)user`)
- The language constraint if any - (`ArisIdConstants.APP_CTX_LOCALE`, `"fr"`)
- Pagination support if any - (`ArisIdConstants.APP_CTX_PAGESIZE`, `10`)

### 3.3.2 Choose a UniqueKey

An application occasionally stores the entries accessed from the identity repository's backend in their own application-specific repository. In such cases, you must carefully consider which attribute should be persisted. For instance, if the backend is an LDAP-based repository, you should use the `GUID` attribute as the persisting attribute because this is the only unique key on the LDAP-based backend. All other LDAP attributes are modifiable.

If the backend is a relational database, choose an attribute on which uniqueness constraint is enforced as the unique key. You can specify this in the `ArisID` mapping property file. The method to search for a user based on the unique key is:

```
searchUserOnUniqueKey(String UniqueKey, Map<String, Object>)
```

The `HashMap` is used to provide the optional context information to be used while performing the operation. In the current release it supports the following options:

- The Principal user that performs the search -  
(`ArisIdConstants.APP_CTX_AUTHUSER`, (`Principal`)`user`)
- The language constraint if any - (`ArisIdConstants.APP_CTX_LOCALE`, "`fr`")
- Pagination support if any - (`ArisIdConstants.APP_CTX_PAGESIZE`, "`10`")

### 3.3.3 Specify Multiple Language Support

Multiple Language Support (MLS) is provided for applications that need locale-specific results. The attributes and the appropriate MLS code are stored in the `ArisID` properties file in the `multiLanguageAttributes` element.

```
<multiLanguageAttributes>...</multiLanguageAttribute>
```

Because `displayname` is the most commonly used multiple language attribute, it is configured by default as a multi-language attribute. Other attributes can be added as needed in the `ArisID` mapping file.

#### Restrictions

Any API to which locale is specified as an argument will return the locale-specific values for all the attributes listed in the `ArisID` properties file as `<multiLanguageAttributes>` that have locale-specific values. For all other attributes it returns the default values stored.

In the backend system, the data is returned in a form conforming to ISO-3166. For example, if there is a French locale (in addition to English), it is stored as `cn, : fr` for the `cn` attribute. The locale for the client applications should be specified in the properties `HashMap` as `ArisIdConstants.APP_CTX_LOCALE`, "`fr`" and the `ArisID` properties file should contain `cn` as `multiLanguageAttribute` and map this attribute.

### 3.3.4 Handle Large Results

When applications access identity data, the result set for a search is frequently too large to be handled by the application. In such cases you have the option of dividing the result into manageable sized pages. You do this by defining the number of objects to be returned in the page.

The following example shows a typical usage pattern:

```
RoleManager rm = new RoleManager(env);
List<PropertyFilterValue> attrFilters = new ArrayList<PropertyFilterValue>();
attrFilters.add(new PropertyFilterValue(Role.NAME, "admin",
AttributeFilter.OP_CONTAINS));

HashMap<String, Object> map = new HashMap<String, Object>();
map.put("ArisIdConstants.APP_CTX_PAGESIZE", "2");
SearchResults<Role> sr = rm.searchRolesbyPage(attrFilters, map);

while(sr.hasMore())
{
    List<Role> roles = sr.getNextSet();

    for (int i=0; i<roles.size(); i++)
        //do the operations with roles.get(i)
```

}

### 3.3.5 Secure the Application

Two security scenarios are available for executing create, read, update, and delete (CRUD) operations on the target system. They are:

- Domain level credentials
- Application level credentials

Proxy authentication is not supported in this release.

#### 3.3.5.1 Domain Level Credentials

In this scenario, all applications in a domain use common credentials to connect to the target system and perform operations with those credentials. The application does not maintain a footprint in the target system.

The LDAP Adapter's configuration file, `adapters.os_xml`, contains credentials to connect to the backend directory, along with the host and port details. If you do not provide any other credentials during initialization, the application connects to the target system using the credentials in the LDAP Adapter's configuration file.

If proxy user (logged in user id) is not specified in the API's application context, ArisID operation will be executed with the credentials that are in LDAP Adapter's configuration file.

If your application connects using common credentials, you must build security into the application itself so that it displays or modifies data only for an authorized user.

#### **Example 3-1 Code Sample: `adapters.os_xml`**

The LDAP Adapter's configuration file `adapters.os_xml` is configured with domain level userid and encrypted password to connect to backend directory. The following is a snippet of `adapters.os_xml`.

```
<binddn>cn=admin</binddn>
<bindpass>{OMASK}C2QXW1Nmfs=</bindpass>
```

While initializing the ArisID API do not provide any credentials.

```
Map env = new HashMap();
// Do not set UserManager.SECURITY_PRINCIPAL & SECURITY_CREDENTIALS
UserManager uMgr = new UserManager(env);
...
...
// Search Operation (with no proxy user in app context)
List<PropertyFilterValue> attrFilters = new ArrayList<PropertyFilterValue>();
attrFilters.add(new PropertyFilterValue("User.FIRSTNAME", "app1",
AttributeFilter.OP_CONTAINS));
attrFilters.add(new PropertyFilterValue("User.LASTNAME", "user1",
AttributeFilter.OP_BGNWITH));
Map<String, Object> appCtx = null;
users = um.searchUsers(attrFilters, appCtx);
```

#### 3.3.5.2 Application Level Credentials

In this scenario, each application uses application level credentials to connect to the target system and performs CRUD operations with those credentials.

In this case you provide the application's user id and password while initializing the ArisID API. When you do that, the application connects to the target system using those credentials.

If no proxy user is specified in the API's application context then ArisID operation will be executed with the application's credentials.

This scenario has the following features:

- Each application has different privileges to view and update the data in the target system
- You can audit the modifications performed by each application in the target system

### **Example 3–2 Code Sample: adapters.os\_xml**

The LDAP Adapter's configuration file `adapters.os_xml` is configured with domain level userid and encrypted password to connect to backend directory. The following is a snippet of `adapters.os_xml`.

```
<binddn>cn=admin</binddn>
  <bindpass>{OMASK}C2QXW1NmF+s=</bindpass>
```

While initializing the ArisID API, provide the application user credentials.

```
Map env = new HashMap();
env.put(UserManager.SECURITY_PRINCIPAL,
"cn=appl_user,cn=users,dc=example,dc=com");
env.put(UserManager.SECURITY_CREDENTIALS, "mypassword");
UserManager uMgr = new UserManager(env);
...
// Search Operation (with no proxy user in app context)
List<PropertyFilterValue> attrFilters = new ArrayList<PropertyFilterValue>();
attrFilters.add(new PropertyFilterValue("User.FIRSTNAME", "app1",
AttributeFilter.OP_CONTAINS));
attrFilters.add(new PropertyFilterValue("User.LASTNAME", "user1",
AttributeFilter.OP_BGNWITH));
Map<String, Object> appCtx = null;
users = um.searchUsers(attrFilters, appCtx);
```

## **3.3.6 Configure the Timeout Interval**

The default connect/read timeout is configured to be 15 seconds. For example, if the LDAP operation on `IdentityStore` is taking more than 15 seconds, the operation will timeout and throw the following IGF exception:

```
org.openliberty.arisid.stack.ConnectionException
```

If the `IdentityStore` has a many entries and the applications are using filters with "contains" and search with paging/sorting, those queries may timeout.

The recommendation is to set the timeout value to 0 (no timeout) and increase the pool size to 20. If the preference is for the application has some timeout interval, set the value to greater than 0.

To configure the timeout interval:

1. Run the following WLST command to list all adapters.

```
listAdapters()
```

2. Run the following command for each adapter to set timeout and maxpoolsize.

- a. `modifyLDAPAdapter('<ADAPTER NAME>', 'OperationTimeout', 0)`
  - b. `modifyLDAPAdapter('<ADAPTER NAME>', 'MaxPoolSize', 20)`
3. Restart WebLogic Server.

### 3.3.7 Specifying Wildcard Characters in Search Filters

Oracle Internet Directory supports wildcard search for DN attributes. However, directories other than Oracle directories might not support wildcard search. Therefore, if you perform a `searchUsers` operation through Identity Governance Framework API with say Microsoft Active Directory as the backend and using a DN in a search filter, then you must provide the `AttributeFilter.OP_EQUALS` operator to successfully execute the operation.

## 3.4 Generating ArisID Beans

Generate ArisID beans as follows:

```
java BeanGenerator [-genmap] <package name> <output dir> [<relationship file>]
<carml file>
```

where:

- `-genmap`: Generates the CARML-ArisIDStack map file in the same location where the CARML file is.
- `package name`: Is the package name for the generated bean classes.
- `output dir`: Location to write the generated bean classes.
- `relationship file`: File containing the relationship definitions between entities.
- `carml file`: The CARML declaration file.

To build ORG beans from a CARML file:

1. Create a CARML file name `org.xml` with the appropriate attributes/interactions for ORG entity.
2. Generate `org` beans (`OrgManager.java` and `Org.java`) using the Bean Generator. The `build.xml` file should resemble the following sample:

```
<path id="ArisIDBeans.classpath">
  <pathelement
location="MW_HOME/oracle_common/modules/velocity-dep-1.4.jar" />
  <pathelement
location="MW_HOME/oracle_common/modules/oracle.jrf_11.1.1/jrf.jar" />
</path>
<property name="BeanGeneratorClassPath" refid="ArisIDBeans.classpath"/>
<target name="generatebeans" description="generate arisid beans">
  <java classname="org.openliberty.arisidbeans.BeanGenerator"
dir="{generatedsource.dir}" fork="true">
    <arg value="{generatedbean.userrole.packagename}"/>
    <arg value="." />
    <arg value="{carml.dir}/org.xml" />
    <classpath>
      <pathelement path="{BeanGeneratorClassPath}" />
    </classpath>
    <sysproperty key="org.openliberty.arisid.policy.wspolicy.class"

value="org.openliberty.arisid.policy.neethi.PolicyImpl" />
  </java>
```



```
</target>
```

3. Compile the generated java files `Org.java` and `OrgManager.java`.
4. Edit the generated mapping file (`igf-map-config.xml`) to update `basearch`, `objectclass`, `OVD` attribute names with their values.
5. An application can use the generated `ORG` APIs for the interactions defined in the `CARML` file (`org.xml`). After the application is deployed in application server:
  - a. Copy the mapping file under `DOMAIN_HOME/config/fmwconfig/arisidprovider/conf`, and
  - b. Copy the `CARML` file under `DOMAIN_HOME/config/fmwconfig/carm`

## 3.5 Sample Application Using IDX User and Role Beans

The following sample application uses IDX User/Role Beans.

### 3.5.1 SearchUsers.jsp

```
<%@ page language="java" contentType="text/html; charset=ISO-8859-1"
pageEncoding="ISO-8859-1"%>
<!DOCTYPE html PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
<%@page import="org.openliberty.arisid.*"%>
<%@page import="org.openliberty.arisidbeans.*"%>
<%@page import="oracle.igf.userrole.*"%>
<%@page import="java.util.*"%>
<%@page import="java.net.URI"%>
<%!public static UserManager uMgr = null;
{
    try {
        uMgr = new UserManager(null);
    } catch (Exception e) {
        e.printStackTrace();
    }
}
%>
<html>
<head>
<title>Search Users</title>
<%

String firstname = request.getParameter("firstname");
String lastname = request.getParameter("lastname");
String telephone = request.getParameter("telephone");

List<PropertyFilterValue> attrFilters = new ArrayList<PropertyFilterValue>();
attrFilters.add(new PropertyFilterValue("firstname", firstname,
AttributeFilter.OP_BGNSWITH));
attrFilters.add(new PropertyFilterValue("lastname", lastname,
AttributeFilter.OP_BGNSWITH));
attrFilters.add(new PropertyFilterValue("telephone", telephone,
AttributeFilter.OP_CONTAINS));

List<User> subjs = uMgr.searchUsers(attrFilters);
```

```

%>
</head>
<body>

<a href="SearchUsers.html">Home</a>
<center>List of Users with FirstName starting with "<%=firstname%>", LastName
starting with "<%=lastname%>" and TelephoneNumber containing
"<%=telephone%>"</center>

<%
Iterator<User> sIter = subjs.iterator();
while (sIter.hasNext()) {
    User subj = sIter.next();

    Map<String, IAttributeValue> vals = subj.getAllAttributes();
    Iterator<IAttributeValue> iter = vals.values().iterator();
%>
<table border="0">
    <tr>
        <th>Item</th>
        <th>Value</th>
    </tr>
    <%
        while (iter.hasNext()) {
            IAttributeValue val = iter.next();
            String name = val.getNameIdRef();
            String value = null;
            if (val.size() > 0)
                value = val.get(0);

if (value != null)
{
    %>
    <tr>
        <td><%=name%></td>
        <td><%=value%></td>
    </tr>
    <%
}
        }
    %>
</table>
<%
}
%>
<br>
<br>
<br>
<a href="SearchUsers.html">Home</a>
</body>
</html>

```

### 3.5.2 SearchUsers.html

```

<!DOCTYPE html PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
<HTML>
<HEAD><TITLE>Search Users</TITLE></HEAD>
<BODY>
<FORM METHOD=POST ACTION="SearchUsers.jsp">

```

```
First Name Starting with <INPUT TYPE=TEXT NAME=firstname SIZE=30><BR><BR>
Last Name Starting with <INPUT TYPE=TEXT NAME=lastname SIZE=30><BR><BR>
Telephone Number containing <INPUT TYPE=TEXT NAME=telephone SIZE=15><BR><BR>
<P><INPUT TYPE=SUBMIT>
</FORM>
</BODY>
</HTML>
```

## 3.6 OpenLDAP Considerations

For OpenLDAP, `Role.MEMBER` is a mandatory attribute for the following APIs:

- `createRole(List<PropertyValue> attrVals, Map<String, Object> appCtxMap)`
- `createRole(List<PropertyValue> attrVals)`

If the `Role.MEMBER` is not included in the input `attrVals` list, role creation will fail.



---

---

## Migrating to Identity Directory API

This chapter describes how to migrate applications from the User and Role API to the Identity Directory API. This chapter contains the following topics:

- [Section 4.1, "Introduction"](#)
- [Section 4.2, "Migrate the Application"](#)
- [Section 4.3, "Comparison Between User and Role API and IDS API"](#)
- [Section 4.4, "Moving From a Test to a Production Environment"](#)
- [Section 4.5, "Tuning Configuration Parameters for IDS"](#)

### 4.1 Introduction

If you have an application that uses the User and Role API described in *Oracle Fusion Middleware Application Security Guide* and *Oracle Fusion Middleware User and Role Java API Reference for Oracle Platform Security Services*, you can modify it to use Identity Directory API instead.

The Identity Directory API also picks up the LDAP-based identity store confirmation from the `jps-config` file. As such, when migrating an application from the User and Role API to the Identity Directory API you do not need to change the configuration in the `jps-config` file.

Applications that initialize the User and Role API with a programmatic configuration can use a similar method to initialize the Identity Directory API. For more information, see [Section 2.4.3, "Initialize and Obtain In-Memory Identity Directory Handle."](#)

### 4.2 Migrate the Application

Application migrating from the User and Role API to the Identity Directory API need to make the following code changes:

- [Section 4.2.1, "API Initialization"](#)
- [Section 4.2.2, "Getting UserManager and GroupManager Handle"](#)
- [Section 4.2.3, "Search Filter"](#)
- [Section 4.2.4, "CRUD Operations"](#)
- [Section 4.3.1, "User-Related APIs"](#)
- [Section 4.3.2, "Role-Related APIs"](#)

## 4.2.1 API Initialization

Process is similar to using `IdentityStoreService.GetIdmStore()` for getting `oracle.security.idm.IdentityStore` handle. Identity Directory API uses `IdentityStoreService.getIdentityStore()` to get `IdentityDirectory` handle. For example:

```
import oracle.igf.ids.IdentityDirectory;
import oracle.igf.ids.IDSException;
import oracle.security.jps.JpsContext;
import oracle.security.jps.JpsContextFactory;
import oracle.security.jps.service.idstore.IdentityStoreService;

// Get IdentityDirectory from JpsContext
JpsContext context = JpsContextFactory.getContextFactory().getContext();
IdentityStoreService idstore = (IdentityStoreService)
context.getServiceInstance(IdentityStoreService.class);
IdentityDirectory ids = idstore.getIdentityStore();
```

## 4.2.2 Getting UserManager and GroupManager Handle

User related CRUD operations can be performed with `oracle.igf.ids.UserManager` and Role related CRUD operations can be performed with `oracle.igf.ids.GroupManager`. `UserManager` and `GroupManager` handles can be obtained from `IdentityDirectory` object. For example:

```
import oracle.igf.ids.UserManager;
import oracle.igf.ids.GroupManager;

// Get UserManager and GroupManager handles
UserManager uMgr = ids.getUserManager();
GroupManager gMgr = ids.getGroupManager();
```

## 4.2.3 Search Filter

A simple or complex search filter can be built using `oracle.igf.ids.SearchFilter`. For example:

```
import oracle.igf.ids.SearchFilter;

// Simple search filter for (firstname equals "john")

SearchFilter filter1 = new SearchFilter("firstname",
SearchFilter.Operator.EQUALS, "john");

// Complex search filter for
((title contains "manager") and (org equals "amer")) or
((title contains "senior manager") and (org equals "apac"))

SearchFilter filter = new SearchFilter(
SearchFilter.LogicalOp.OR,
new SearchFilter(SearchFilter.LogicalOp.AND,
new SearchFilter("manager", SearchFilter.Operator.CONTAINS,
"manager"),
new SearchFilter("org", SearchFilter.Operator.EQUALS, "amer")),
new SearchFilter(SearchFilter.LogicalOp.AND,
new SearchFilter("manager", SearchFilter.Operator.CONTAINS,
"senior manager"),
new SearchFilter("org", SearchFilter.Operator.EQUALS, "apac")));
```

## 4.2.4 CRUD Operations

Create/Read/Update/Delete (CRUD) operations on User, Group, Org, and generic entities are discussed in the following sections:

- [Section 4.2.4.1, "Finding a User"](#)
- [Section 4.2.4.2, "Searching Users"](#)
- [Section 4.2.4.3, "Creating a User"](#)
- [Section 4.2.4.4, "Deleting a User"](#)
- [Section 4.2.4.5, "Authenticating a User"](#)
- [Section 4.2.4.6, "Modifying Users and Managing Related Entities"](#)

### 4.2.4.1 Finding a User

The following APIs are used for finding a user:

- Get user for given principal identifier. For example:  

```
User getUser(Principal principal, ReadOptions opts)
```
- Search for user matching given id attribute value that uniquely identifies the user. For example:  

```
User searchUser(String id, ReadOptions opts)
```
- Finds user matching given attribute name and value. For example:  

```
User searchUser(String attrName, String attrVal, ReadOptions opts)
```
- Search for user matching given GUID value that uniquely identifies the user. For example:  

```
searchUserByGuid(String guid, ReadOptions opts)
```

### 4.2.4.2 Searching Users

The following is an example of the API for searching a user.

```
ResultSet<User> searchUsers(SearchFilter filter, SearchOptions opts)
```

### 4.2.4.3 Creating a User

The following is an example of the API for creating a user.

```
Principal createUser(List<Attribute> attrVals, CreateOptions opts)
```

### 4.2.4.4 Deleting a User

The following are examples of the API for deleting a user.

- Delete the user given the principal identifier.  

```
void deleteUser(Principal principal, DeleteOptions opts)
```
- Delete the user given the id attribute value.  

```
void deleteUser(String id, DeleteOptions opts)
```

#### 4.2.4.5 Authenticating a User

The following are examples of the API for user authentication.

- Authenticate the user matching the given id attribute value.  
`User authenticateUser(String id, char[] password, ReadOptions opts)`
- Authenticate the user for given principal identifier.  
`boolean authenticateUser(Principal principal, char[] password)`

#### 4.2.4.6 Modifying Users and Managing Related Entities

The APIs for modifying user attributes and for getting the related entities are in `User` object instead of `UserManager`.

**4.2.4.6.1 Modifying a User** The following are examples of the API for modifying a user.

- Modify user attributes.  
`void User.modify(List<ModAttribute> attrVals, ModifyOptions opts)`
- Set the user attribute value.  
`void User.setAttributeValue(String attrName, String attrVal, ModifyOptions opts)`

**4.2.4.6.2 Managing Related Entities** The following are examples of the APIs for managing entities.

- Get the management chain.  
`ResultSet<User> getManagementChain(int nLevels, SearchOptions opts)`
- Check if the given user is manager of this user.  
`boolean isManager(User user, boolean direct, ReadOptions opts)`
- Set the given user as manager of this user.  
`void setManager(User user, ModifyOptions opts)`
- Get all the reportees of this user.  
`ResultSet<User> getReportees(int nLevels, SearchFilter targetFilter, SearchOptions opts)`
- Get all the groups this user is a member of and matching the given filter criteria.  
`ResultSet<Group> getMemberOfGroups(int nLevels, SearchFilter targetFilter, SearchOptions opts)`
- Check if this user is a member of the given group.  
`boolean isMemberOf(Group group, boolean direct, ReadOptions opts)`
- Add this user as a member to given group.  
`void addMemberOf(Group group, ModifyOptions opts)`
- Delete this user as a member to given group.  
`void deleteMemberOf(Group group, ModifyOptions opts)`



## 4.3 Comparison Between User and Role API and IDS API

The differences between the User and Role API and Identity Directory API are discussed in the following topics:

- [Section 4.3.1, "User-Related APIs"](#)
- [Section 4.3.2, "Role-Related APIs"](#)

### 4.3.1 User-Related APIs

[Table 4–1](#) provides a comparison between the User-related API method and the corresponding Identity Directory API API method.

**Table 4–1 Comparison Between User-Related API and Identity Directory API**

Functionality	User/Role API Method	Identity Directory API Method
User Creation	User UserManager.createUser(String name, char[] password)  User UserManager.createUser(String name, char[] password, PropertySet pset)	Principal UserManager.createUser(List<Attribute> attrVals, CreateOptions opts)
Delete User	void UserManager.dropUser(User Profile user)  void UserManager.dropUser(User user);	void UserManager.deleteUser(Principal principal, DeleteOptions opts)  void UserManager.deleteUser(String id, DeleteOptions opts)
Authenticate User	User UserManager.authenticateUser(String user_id, char[] passwd)  User UserManager.authenticateUser(User user, char[] passwd)  User UserManager.authenticateUser(String user_id, String authProperty, char[] passwd)	User UserManager.authenticateUser(String id, char[] password, ReadOptions opts)  boolean UserManager.authenticateUser(Principal principal, char[] password)
Check if create User is supported	boolean UserManager.isCreateUserSupported()	boolean UserManager.getCapabilities().isCreateCapable()
Check if modify User is supported	boolean UserManager.isModifyUserSupported()	boolean UserManager.getCapabilities().isUpdateCapable()
Check if drop User is supported	boolean UserManager.isDropUserSupported()	boolean UserManager.getCapabilities().isDeleteCapable()
Search Users by given search criteria	SearchResponse IdentityStore.searchUsers(SearchParameters params)	ResultSet<User> UserManager.searchUsers(SearchFilter filter, SearchOptions opts)

**Table 4–1 (Cont.) Comparison Between User-Related API and Identity Directory API**

Functionality	User/Role API Method	Identity Directory API Method
Search an User by name/unique name/guid	User IdentityStore.searchUser(String name)	User UserManager.searchUser(String id, ReadOptions opts)  User UserManager.searchUser(String attrName, String attrVal, ReadOptions opts)
Check if User exists in the repository for a given User object	boolean IdentityStore.exists (User user)	User.getPrincipal() if the following method returns null user doesn't exist; otherwise exists  User getUser(Principal principal, ReadOptions opts)
Simple search filter (search based on a single attribute name, type and value)	SimpleSearchFilter	SearchFilter(String propertyName, Operator op, String propertyVal)
Complex Search Filter (search based on more than one attribute with filter conditions and nested filters)	ComplexSearchFilter	SearchFilter(LogicalOp op, SearchFilter... searchFilters)
Getting a property value for a given property name	String User.getPropertyVal(String propName)  (User Role API fetches the attribute values from cache. If it misses cache, it fetches from repository)	String User.getAttributeValue(String attrName)  Limitation: Returns attribute values from User object that has been already fetched from the repository.
Getting the User property for a given property name	Property User.getProperty(String propName)	Attribute User.getAttribute(String attrName)
Getting the user properties for a given set of property names	Map User.getProperties()	Map<String, Attribute> User.getAllAttributes()
Get all user properties from the repository for a user	PropertySet User.getAllUserProperties()	Map<String, Attribute> User.getAllAttributes()
Get all user property names from the schema	List IdentityStore.getUserPropertyNames()  Returns the names of all the properties in the schema	List<String> UserManager.getEntityAttributes()
Changing the attribute value in the repository of an user	void User.setProperty(ModProperty mprop)	void User.setAttributeValue(String attrName, String attrVal, ModifyOptions opts)

**Table 4–1 (Cont.) Comparison Between User-Related API and Identity Directory API**

Functionality	User/Role API Method	Identity Directory API Method
Changing the set of attribute values in the repository for an user	void User.setProperties(ModProperty[] modPropObjs)  void User.setProperties(LdapContext ctx, ModProperty[] modPropObjs)	void User.modify(List<ModAttribute> attrVals, ModifyOptions opts)
Get all the reportees of an User either direct or indirect	SearchResponse User.getReportees(boolean direct)	ResultSet<User> User.getReportees(int nLevels, SearchFilter targetFilter, SearchOptions opts)
Get Management chain of an user	List User.getManagementChain(int max, String upToManagerName, String upToTitle)	ResultSet<User> User.getManagementChain(int nLevels, SearchOptions opts)  List<User> User.getManagementChain(int nLevels, String manager, String title, SearchOptions opts)
Get/Set of Binary Attributes	Available  Property in User/Role API supports binary attributes byte[] user.getJPEPhoto()  void user.setJPEPhoto(String imgpath)	Returns base64 encoded value  While setting the value either base64 encoded value or byte[] can be used for creating ModAttribute.
Selecting the Realm	Available  env.put(OIDIdentityStoreFactory.RT_SUBSCRIBER_NAME, "<realm dn>");  IdentityStoreFactory.getIdentityStoreInstance(env);	This is part of IDS Operational configuration. At API level searchbase and createbase can be specified as well.

### 4.3.2 Role-Related APIs

Table 4–2 provides a comparison between the Role-related API method and the corresponding Identity Directory API method.

**Table 4–2 Comparison Between Role-Related API and Identity Directory API**

Functionality	User/Role API Method	Identity Directory API Method
Creating a Role	Role RoleManager.createRole(String name, int scope)  Role RoleManager.createRole(String name)	Principal GroupManager.createGroup(List<Attribute> attrVals, CreateOptions opts)
Deleting a Role	void RoleManager.dropRole(RoleProfile role)  void RoleManager.dropRole(Role role)	void GroupManager.deleteGroup(Principal principal, DeleteOptions opts)

**Table 4–2 (Cont.) Comparison Between Role-Related API and Identity Directory API**

<b>Functionality</b>	<b>User/Role API Method</b>	<b>Identity Directory API Method</b>
Check if create role is supported	boolean RoleManager.isCreateRoleSupported()	boolean GroupManager.getCapabilities().isCreateCapable()
Check if modify role is supported	boolean RoleManager.isModifyRoleSupported()	boolean GroupManager.getCapabilities().isUpdateCapable()
Check if delete role is supported	boolean RoleManager.isDropRoleSupported()	boolean GroupManager.getCapabilities().isDeleteCapable()
Is the Group owned by a User	boolean RoleManager.isGranted(Role parent, Principal principal)	boolean Group.isMember(User user, boolean direct, ReadOptions opts)  boolean User.isMemberOf(Group group, boolean direct, ReadOptions opts)
Is the Group owned by a User	boolean RoleManager.isOwnedBy(Role parent, Principal principal)	boolean User.isOwnerOf(Group group, boolean direct, ReadOptions opts)
Is the group managed by a User	boolean RoleManager.isManagedBy(Role parent, Principal principal)	Not supported
Get all the members of a Role either direct / indirect	SearchResponse Role.getGrantees(SearchFilter filter, boolean direct)	ResultSet<User> Group.getMembers(int nLevels, SearchFilter targetFilter, SearchOptions opts)
Add an user as a member to a role	void RoleManager.grantRole(Role parent, Principal principal)	void Group.addMember(User user, ModifyOptions opts)
Remove a user from being member of a role	void RoleManager.revokeRole(Role parent, Principal principal)	void Group.deleteMember(User user, ModifyOptions opts)
Get all the owners of a specific Role either direct / indirect	SearchResponse Role.getOwners(SearchFilter filter, boolean direct)  SearchResponse Role.getOwners(SearchFilter filter)	ResultSet<User> Group.getOwners(int nLevels, SearchFilter targetFilter, SearchOptions opts)
Add a user as a owner of a role	void Role.addOwner(Principal principal)	void Group.addOwner(User user, ModifyOptions opts)
Remove a user from being a owner of a Role	void Role.removeOwner(Principal principal)	void Group.deleteOwner(User user, ModifyOptions opts)
Get all the managers of a Role either direct / indirect	SearchResponse Role.getManagers(SearchFilter filter, boolean direct)  SearchResponse Role.getManagers(SearchFilter filter)	Not Supported
Add a user as a manager of a Role	void Role.addManager(Principal principal)	Not Supported

**Table 4–2 (Cont.) Comparison Between Role-Related API and Identity Directory API**

Functionality	User/Role API Method	Identity Directory API Method
Remove a user from being manager of a Role	void Role.removeManager(Principal principal)	Not Supported
Getting the role property	Property Role.getProperty(String propName)  Note: User Role API fetches these attribute values from cache. If it misses cache, it fetches from repository.	Attribute Group.getAttribute(String attrName)
Determine the Role Type	Role.isApplicationRole Role.isEnterpriseRole Role.isSeeded	Not Supported
Search Roles for a given search criteria	SearchResponse IdentityStore.searchRoles(int scope, SearchParameters params)	ResultSet<Group> GroupManager.searchGroups(SearchFilter filter, SearchOptions opts)
Search a Role by name/unique name /guid	Role IdentityStore.searchRole(int searchType, String value)	Group searchGroup(String id, ReadOptions opts) Group searchGroup(String attrName, String attrVal, ReadOptions opts)
Search both User and Roles for a given filter	SearchResponse IdentityStore.search(SearchParameters params)	Available through separate methods: UserManager.searchUsers GroupManager.searchGroups
Get all the roles assigned to user/group	SearchResponse getGrantedRoles(Principal principal, boolean direct)	ResultSet<Group> User.getMemberOfGroups(int nLevels, SearchFilter targetFilter, SearchOptions opts)  ResultSet<Group> Group.getMemberOfGroups(int nLevels, SearchFilter targetFilter, SearchOptions opts)
Get all the roles owned by user/group	SearchResponse getOwnedRoles(Principal principal, boolean direct)	ResultSet<Group> User.getOwnedGroups(int nLevels, SearchFilter targetFilter, SearchOptions opts)  ResultSet<Group> Group.getOwnedGroups(int nLevels, SearchFilter targetFilter, SearchOptions opts)
Get all the roles managed by user/group	SearchResponse getManagedRoles(Principal principal, boolean direct)	Not supported

## 4.4 Moving From a Test to a Production Environment

Moving from one environment to another, especially from a test environment to production environment, provides you the flexibility to test applications in a test environment and then roll them out in the production environment.

This section describes the Identity Directory Service/libOVD properties that you need to modify while moving from a test environment to production environment, and contains the following topics:

- [Section 4.4.1, "Overview of Moving Between Environments"](#)
- [Section 4.4.2, "Modifying Identity Directory Service/libOVD Move Plan"](#)

### 4.4.1 Overview of Moving Between Environments

Moving Identity Directory Service/libOVD installation diminishes the amount of work that would otherwise be required to reapply all the customization and configuration changes made in one environment to another. You can install, configure, customize, and validate Identity Directory Service/libOVD in a test environment. Once the system is stable and performs as required, you can create the production environment by moving a copy of the server and its configuration from the test environment, instead of redoing all the changes that were incorporated into the test environment.

### 4.4.2 Modifying Identity Directory Service/libOVD Move Plan

A move plan contains configuration settings of the source environment. When you move between environments, you run the `extractMovePlan` script to create a move plan for the entity that you are moving. The `extractMovePlan` script extracts configuration information from the archive into a move plan. It also extracts any needed configuration plans. Before you apply the archive to the target, you must edit the move plan to reflect the values of the target environment.

---

---

**Note:** You can modify certain configuration parameters by editing the move plan. When you run the `extractMovePlan` script, it contains a list of all the adapters. However, when you run the `pasteConfig` script, then it should contain the configuration information of the libOVD adapter for which the `LDAP_URL` has changed. Therefore, the adapters for which the configuration has not changed should be removed from the move plan.

---

---

You can modify properties with the scope of `READ_WRITE`. Do not modify the properties with the scope of `READ_ONLY`. For a comprehensive description and the procedure to follow for moving between environments, see "Moving from a Test to a Production Environment" section in the *Oracle Fusion Middleware Administrator's Guide*.

This section contains the following topics:

- [Section 4.4.2.1, "Locating Identity Directory Service/libOVD configGroup Elements"](#)
- [Section 4.4.2.2, "Identifying Identity Directory Service/libOVD Move Plan Properties"](#)

#### 4.4.2.1 Locating Identity Directory Service/libOVD configGroup Elements

Move plans usually contain multiple `configGroup` elements. To locate Identity Directory Service/libOVD `ConfigGroup`, in the generated move plan, you must look for `<type>LIBOVD_ADAPTERS</type>`. This tag provides comprehensive information about the libOVD adapter properties that you might have to update. A property is associated with a particular `configGroup` element.

Each adapter is represented by a configProperty id tag of the form:

```
"LDAP:<context_name>:<adapter_name>"
```

Consider the following example: "LDAP:ids:myOID"

Table 4–3 shows the properties for the move plan for libOVD.

The following example shows a section of the move plan for Identity Directory Service/libOVD, with portion of the LIBOVD\_ADAPTERS configGroup elements:

```
<configGroup>
  <type>LIBOVD_ADAPTERS</type>
  <configProperty id="LDAP:ids:myOID">
    <configProperty>
      <name>Context Name</name>
      <value>ids</value>
      <itemMetadata>
        <dataType>STRING</dataType>
        <scope>READ_ONLY</scope>
      </itemMetadata>
    </configProperty>
    <configProperty>
      <name>Adapter Name</name>
      <value>myOID</value>
      <itemMetadata>
        <dataType>STRING</dataType>
        <scope>READ_ONLY</scope>
      </itemMetadata>
    </configProperty>
    <configProperty>
      <name>LDAP URL</name>
      <value>ldap://hostname:1389</value>
      <itemMetadata>
        <dataType>STRING</dataType>
        <scope>READ_WRITE</scope>
      </itemMetadata>
    </configProperty>
    <configProperty>
      <name>LDAP Host Read Only</name>
      <value>>false</value>
      <itemMetadata>
        <dataType>STRING</dataType>
        <scope>READ_WRITE</scope>
      </itemMetadata>
    </configProperty>
    <configProperty>
      <name>LDAP Host Percentage</name>
      <value>100</value>
      <itemMetadata>
        <dataType>STRING</dataType>
        <scope>READ_WRITE</scope>
      </itemMetadata>
    </configProperty>
    <configProperty>
      <name>DN</name>
      <value>cn=orcladmin</value>
      <itemMetadata>
        <dataType>STRING</dataType>
        <scope>READ_WRITE</scope>
      </itemMetadata>
    </configProperty>
  </configProperty>
</configGroup>
```

```

<configProperty>
  <name>Password File</name>
  <value/>
  <itemMetadata>
    <dataType>STRING</dataType>
    <password>>true</password>
    <scope>READ_WRITE</scope>
  </itemMetadata>
</configProperty>
</configProperty>
</configGroup>

```

#### 4.4.2.2 Identifying Identity Directory Service/libOVD Move Plan Properties

The [Table 4–3](#) in this section describes the move plan properties you can customize for Identity Directory Service/libOVD adapter.

**Table 4–3** *Move Plan Properties for libOVD*

Property	Description	Sample Value
Context Name	The libOVD context to use with which the adapter is associated. This is a read-only property.	ids
Adapter Name	The name of the adapter. This is a read-only property.	myOID
LDAP URL	The LDAP URL value for the adapter in the form of ldap://host:port. This is a read-write property.	ldap://slc05ky m:1389
DN	The DN of the user to connect to the backend LDAP. This is a read-write property.	cn=orcladmin
Password File	The absolute path to the secure file containing the password of the user. This is a read-write property.	/tmp/p.txt
LDAP Host Read Only	The flag indicating if the given host is read only. The default value is false. This is a read-write property.	false
LDAP Host Percentage	It specifies the load percentage value for the given LDAP host. The default value is 100. This is a read-write property.	100

## 4.5 Tuning Configuration Parameters for IDS

Tuning is the adjustment or modification of parameters to meet specific deployment requirements. The default IDS configuration must be tuned for your deployment scenario.

You must review the requirements and recommendations in this section carefully.

This section contains the following topics:

- [Section 4.5.1, "Configuration Parameters"](#)
- [Section 4.5.2, "Setting Tuning Parameters Using File-Based Configuration"](#)
- [Section 4.5.3, "Setting Tuning Parameters Using In-Memory Configuration"](#)
- [Section 4.5.4, "Handling Firewall and Load Balancer Timeout Errors"](#)



## 4.5.1 Configuration Parameters

Table 4–4 lists the configuration parameters that require turning in a real deployment scenario for IDS.

**Table 4–4 Configuration Parameters for IDS**

Parameter	Description
InitialPoolSize	The initial number of LDAP connections created when the LDAP connection pool is set up.
MaxPoolSize	The maximum number of LDAP connections allowed in the LDAP connection pool.  <b>Note:</b> If a deployment has numerous concurrent requests coming in, then you must set this value appropriately to prevent running out of connections or waiting for a connection during an operation.
MaxPoolWait MaxPoolChecks	These parameters determine the waiting time for free LDAP connection when all the LDAP connections in the connection pool are in use. IDS waits for MAX_POOLWAIT and MAX_POOLCHECKS milliseconds for a free connection to be available first and then tries to expand the connection pool.
PoolCleanupInterval	This is the timer interval (in seconds) used by the LDAP connection pool cleanup timer. The LDAP connection pool cleanup timer runs using this timer interval to perform pool cleanup tasks like shrinking the connection pool based on the idle connection if needed.
MaxPoolConnectionIdleTime	This specifies the maximum idle time for an LDAP connection. In an LDAP connection remains idle for this amount of time, it will be closed when the next LDAP connection pool cleanup timer runs.
OperationTimeout	The amount of time in milliseconds IDS waits for an LDAP request to be acknowledged by the LDAP remote host. The same property is used for LDAP connection timeout as well as LDAP read timeout.
HeartbeatInterval	This is the interval in seconds to check the availability of backend LDAP.
SocketOptions	These parameters set SO_TIMEOUT (in seconds), SO_REUSEADDR, TCP_NODELAY, SO_KEEPALIVE properties for the underlying JNDI sockets in the LDAP connection.

## 4.5.2 Setting Tuning Parameters Using File-Based Configuration

The configuration information is stored in XML file. In such a scenario, you can use the WebLogic Scripting Tool (WLST) to modify the configuration parameters.

This section describes how to configure the tuning parameters using the WLST command.

---



---

**Note:** In all the WLST command examples in this section, ADAPTER\_NAME refers to the name of the IDS repository. For instance, the libOVD adapter name.

---



---

- For InitialPoolSize:

```
modifyLDAPAdapter(adapterName='ADAPTER_NAME', attribute='InitialPoolSize',
value=10, contextName='ids')
```

- For MaxPoolSize:

```
modifyLDAPAdapter(adapterName='ADAPTER_NAME', attribute='MaxPoolSize',
value=100, contextName='ids')
```

- For MaxPoolWait and MaxPoolCheck:

```
modifyLDAPAdapter(adapterName='ADAPTER_NAME', attribute='MaxPoolWait',
value=1000, contextName='ids')
```

```
modifyLDAPAdapter(adapterName='ADAPTER_NAME', attribute='MaxPoolChecks',
value=10, contextName='ids')
```

- For PoolCleanupInterval:

```
modifyLDAPAdapter(adapterName='ADAPTER_NAME', attribute='PoolCleanupInterval',
value=300, contextName='ids')
```

- For MaxPoolConnectionIdleTime:

```
modifyLDAPAdapter(adapterName='ADAPTER_NAME',
attribute='MaxPoolConnectionIdleTime', value=3600, contextName='ids')
```

- For OperationTimeout:

```
modifyLDAPAdapter(adapterName='ADAPTER_NAME', attribute='OperationTimeout',
value=120000, contextName='ids')
```

- For HeartbeatInterval:

```
modifyLDAPAdapter(adapterName='ADAPTER_NAME', attribute='HeartBeatInterval',
value=60, contextName='ids')
```

- For SocketOption:

```
modifySocketOptions(adapterName='ADAPTER_NAME', reuseAddress=false,
keepAlive=false, tcpNoDelay=true, readTimeout=1800, contextName='ids')
```

---



---

**Note:** You must run the `activateLibOVDConfigChanges('ids')` WLST command or restart the WebLogic server for configuration changes to take effect.

---



---

### 4.5.3 Setting Tuning Parameters Using In-Memory Configuration

The configuration information is stored by the IDS consumer and is passed during run-time to IDS by invoking the `IdentityStoreConfig` class. For more information about using the class and its properties, see *Oracle Fusion Middleware Java API Reference for Identity Governance Framework Identity Directory*.

You can modify the following configuration parameters using the Java API class:

**Table 4–5 Field Name for Configuration Parameters**

Parameter	Field Name to Modify
InitialPoolSize	IdentityStoreConfig.INITIAL_POOLSIZE
MaxPoolSize	IdentityStoreConfig.MAX_POOLSIZE

**Table 4–5 (Cont.) Field Name for Configuration Parameters**

<b>Parameter</b>	<b>Field Name to Modify</b>
MaxPoolWait	IdentityStoreConfig.MAX_POOLWAIT
MaxPoolChecks	IdentityStoreConfig.MAX_POOLCHECK
PoolCleanupInterval	IdentityStoreConfig.POOL_CLEANUP_INTERVAL
MaxPoolConnectionIdleTime	IdentityStoreConfig.MAX_POOL_CONNECTION_IDLE_TIME
OperationTimeout	IdentityStoreConfig.CONN_TIMEOUT
HeartbeatInterval	IdentityStoreConfig.HEARTBEAT_INTERVAL
SocketOptions	IdentityStoreConfig.SOCKET_READTIMEOUT IdentityStoreConfig.SOCKET_REUSEADDRESS IdentityStoreConfig.SOCKET_KEEPAIVE IdentityStoreConfig.SOCKET_TCPNODELAY

#### 4.5.4 Handling Firewall and Load Balancer Timeout Errors

SocketOptions setting helps detect and safely close orphan socket connections caused by remote server failure. TCP waits for the configured duration of time for a response from the remote server before closing the socket. However, when there is a firewall or a Load Balancer between libOVD and the backend LDAP, then you must set the readTimeout value in the SocketOptions appropriately to prevent timeout errors. It is recommended that you set this value to a value which is less than the firewall or the Load Balancer timeout.

