

Oracle® Fusion Middleware

Command Reference for Oracle WebLogic Server

12c (12.2.1.2.0)

E77953-03

January 2017

This document describes Oracle WebLogic Server command-line reference features and Java utilities and how to use them to administer Oracle WebLogic Server.

Copyright © 2007, 2017, Oracle and/or its affiliates. All rights reserved.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this is software or related documentation that is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, then the following notice is applicable:

U.S. GOVERNMENT END USERS: Oracle programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, delivered to U.S. Government end users are "commercial computer software" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, shall be subject to license terms and license restrictions applicable to the programs. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Xeon are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. AMD, Opteron, the AMD logo, and the AMD Opteron logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark of The Open Group.

This software or hardware and documentation may provide access to or information about content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services unless otherwise set forth in an applicable agreement between you and Oracle. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services, except as set forth in an applicable agreement between you and Oracle.

Contents

Preface	vii
Documentation Accessibility	vii
Conventions.....	vii
1 Introduction and Roadmap	
1.1 Document Scope and Audience.....	1-1
1.2 Guide to This Document.....	1-1
1.3 Related Documentation	1-1
1.4 New and Changed Features in This Release	1-2
2 Using the Oracle WebLogic Server Java Utilities	
2.1 appc.....	2-3
2.2 AppletArchiver	2-3
2.2.1 Syntax.....	2-3
2.3 autotype (deprecated).....	2-3
2.4 BuildXMLGen	2-3
2.5 CertGen	2-3
2.5.1 Syntax.....	2-4
2.5.2 Example	2-6
2.6 ClientDeployer	2-6
2.7 clientgen	2-7
2.8 Conversion (deprecated)	2-7
2.9 dbping.....	2-7
2.9.1 Creating a DB2 Package with dbping.....	2-7
2.9.2 Syntax.....	2-7
2.9.3 Examples.....	2-9
2.10 ddcreate (deprecated).....	2-10
2.11 DDInit	2-10
2.11.1 WebInit.....	2-10
2.11.2 EarInit (deprecated)	2-10
2.12 Deployer.....	2-10
2.13 der2pem.....	2-11

2.13.1	Syntax.....	2-11
2.13.2	Example	2-11
2.14	Derby	2-11
2.15	ejbc (deprecated).....	2-12
2.16	EJBGen.....	2-12
2.17	encrypt.....	2-12
2.17.1	Syntax.....	2-12
2.17.2	Examples.....	2-13
2.18	getProperty	2-13
2.18.1	Syntax.....	2-13
2.18.2	Example	2-13
2.19	host2ior.....	2-14
2.19.1	Syntax.....	2-14
2.20	ImportPrivateKey	2-14
2.20.1	Syntax.....	2-14
2.20.2	Example	2-15
2.21	jhtml2jsp	2-16
2.21.1	Syntax.....	2-16
2.22	jspc (deprecated).....	2-17
2.23	logToZip.....	2-17
2.23.1	Syntax.....	2-17
2.23.2	Examples.....	2-17
2.24	MBean Commands	2-18
2.25	MulticastTest	2-18
2.25.1	Syntax.....	2-18
2.25.2	Example	2-19
2.26	myip.....	2-19
2.26.1	Syntax.....	2-19
2.26.2	Example	2-19
2.27	pem2der.....	2-20
2.27.1	Syntax.....	2-20
2.27.2	Example	2-20
2.28	rmic	2-20
2.29	Schema.....	2-20
2.29.1	Syntax.....	2-20
2.29.2	Example	2-21
2.30	servicegen (deprecated).....	2-21
2.31	SearchAndBuild	2-21
2.31.1	Example	2-22
2.32	source2wsdd (deprecated).....	2-22
2.33	system.....	2-22
2.33.1	Syntax.....	2-22
2.33.2	Example	2-22

2.34	ValidateCertChain	2-23
2.35	verboseToZip	2-23
2.35.1	Syntax	2-23
2.35.2	Example	2-24
2.36	WebLogicMBeanMaker	2-24
2.36.1	Syntax	2-24
2.37	wlappc	2-24
2.38	wlcompile	2-24
2.39	wlconfig	2-25
2.40	wldeploy	2-25
2.41	wlpackage	2-25
2.42	wlserver	2-25
2.43	wSDL2Service	2-25
2.44	wSDLgen (deprecated)	2-25
2.45	wSPackage (deprecated)	2-25

3 weblogic.Server Command-Line Reference

3.1	Required Environment and Syntax for weblogic.Server	3-1
3.1.1	Environment	3-1
3.1.2	Modifying the Classpath	3-2
3.1.3	Syntax	3-3
3.2	Default Behavior	3-3
3.3	weblogic.Server Configuration Options	3-4
3.3.1	JVM Parameters	3-4
3.3.2	Location of Configuration Data	3-5
3.3.3	Options that Override a Server's Configuration	3-7
3.4	Using the weblogic.Server Command Line to Start a Server Instance	3-23
3.5	Using the weblogic.Server Command Line to Create a Domain	3-24
3.6	Verifying Attribute Values That Are Set on the Command Line	3-25

Preface

This preface describes the document accessibility features and conventions used in this guide—*Command Reference for Oracle WebLogic Server*.

Documentation Accessibility

For information about Oracle's commitment to accessibility, visit the Oracle Accessibility Program website at <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=docacc>.

Access to Oracle Support

Oracle customers that have purchased support have access to electronic support through My Oracle Support. For information, visit <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=info> or visit <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=trs> if you are hearing impaired.

Conventions

The following text conventions are used in this document:

Convention	Meaning
boldface	Boldface type indicates graphical user interface elements associated with an action, or terms defined in text or the glossary.
<i>italic</i>	Italic type indicates book titles, emphasis, or placeholder variables for which you supply particular values.
monospace	Monospace type indicates commands within a paragraph, URLs, code in examples, text that appears on the screen, or text that you enter.

Introduction and Roadmap

This chapter describes the contents and organization of this guide—*Command Reference for Oracle WebLogic Server*.

This chapter includes the following sections:

- [Document Scope and Audience](#)
- [Guide to This Document](#)
- [Related Documentation](#)
- [New and Changed Features in This Release](#)

1.1 Document Scope and Audience

This document describes Oracle WebLogic Server command-line reference features and Java utilities and how to use them to administer Oracle WebLogic Server.

This document is written for system administrators and application developers deploying e-commerce applications using the Java Platform, Enterprise Edition (Java EE). It is assumed that readers are familiar with Web technologies and the operating system and platform where Oracle WebLogic Server is installed.

1.2 Guide to This Document

The document is organized as follows:

- This chapter, [Introduction and Roadmap](#) describes the scope of this guide and lists related documentation.
- [Using the Oracle WebLogic Server Java Utilities](#), describes various Java utilities you can use to manage and troubleshoot an Oracle WebLogic Server domain.
- [weblogic.Server Command-Line Reference](#), describes how to start Oracle WebLogic Server instances from a command shell or from a script.

1.3 Related Documentation

- [Using Ant Tasks to Configure and Use a WebLogic Server Domain in *Developing Applications with Oracle WebLogic Server*](#)
- [Understanding the WebLogic Scripting Tool](#)
- [Administering Server Environments for Oracle WebLogic Server](#)
- [Oracle WebLogic Server Administration Console Online Help](#)

1.4 New and Changed Features in This Release

For a comprehensive listing of the new WebLogic Server features introduced in this release, see *What's New in Oracle WebLogic Server 12.2.1.2.0*.

Using the Oracle WebLogic Server Java Utilities

Oracle WebLogic Server provides a number of Java utilities and Ant tasks for performing administrative and programming tasks. This chapter describes those Java utilities and Ant tasks.

To use these utilities and tasks, you must set your CLASSPATH correctly. For more information, see [Modifying the Classpath](#).

Oracle WebLogic Server provides several Java programs that simplify installation and configuration tasks, provide services, and offer convenient shortcuts. The Java utilities provided with Oracle WebLogic Server are all described below. The command-line syntax is specified for all utilities and, for some, examples are provided.

Oracle WebLogic Server also provides a number of Ant tasks that automate common application server programming tasks. The Apache Web site provides other useful Ant tasks as well, including tasks for packaging EAR, WAR, and JAR files. For more information, see <http://jakarta.apache.org/ant/manual/>.

This chapter includes the following sections:

- [appc](#)
- [AppletArchiver](#)
- [autotype](#) (deprecated)
- [BuildXMLGen](#)
- [CertGen](#)
- [ClientDeployer](#)
- [clientgen](#)
- [Conversion](#) (deprecated)
- [dbping](#)
- [ddcreate](#) (deprecated)
- [DDInit](#)
- [Deployer](#)
- [der2pem](#)
- [Derby](#)
- [ejbc](#) (deprecated)

-
- EJBCGen
 - encrypt
 - getProperty
 - host2ior
 - ImportPrivateKey
 - jhtml2jsp
 - jspc (deprecated)
 - logToZip
 - MBean Commands
 - MulticastTest
 - myip
 - pem2der
 - rmic
 - Schema
 - servicegen (deprecated)
 - SearchAndBuild
 - source2wsdd (deprecated)
 - system
 - ValidateCertChain
 - verboseToZip
 - WebLogicMBeanMaker
 - wlappc
 - wlcompile
 - wlconfig
 - wldeploy
 - wlpackage
 - wlserver
 - wsdl2Service
 - wsdlgen (deprecated)
 - wspackage (deprecated)

2.1 appc

The `appc` compiler generates and compiles the classes needed to deploy EJBs and JSPs to Oracle WebLogic Server. It also validates the deployment descriptors for compliance with the current specifications at both the individual module level and the application level. See `appc` Reference in *Developing Enterprise JavaBeans, Version 2.1, for Oracle WebLogic Server*.

2.2 AppletArchiver

The `AppletArchiver` utility runs an applet in a separate frame, keeps a record of all of the downloaded classes and resources used by the applet, and packages these into either a `.jar` file or a `.cab` file. (The `cabarc` utility is available from Microsoft.)

2.2.1 Syntax

```
$ java utils.applet.archiver.AppletArchiver URL filename
```

[Table 2-1](#) describes the arguments passed to the `AppletArchiver` utility.

Table 2-1 AppletArchiver Arguments

Argument	Definition
<i>URL</i>	URL for the applet.
<i>filename</i>	Local filename that is the destination for the <code>.jar</code> / <code>.cab</code> archive.

2.3 autotype (deprecated)

Use the `autotype` Ant task to generate non-built-in data type components, such as the serialization class, for Web Services. The fully qualified name for the `autotype` Ant task is `weblogic.ant.taskdefs.webservices.javaschema.JavaSchema`.

For a complete list of Web Services Ant tasks, see Ant Task Reference in *WebLogic Web Services Reference for Oracle WebLogic Server*.

2.4 BuildXMLGen

Use `BuildXMLGen` to generate a `build.xml` file for enterprise applications in the split-directory structure. For complete documentation of this utility, see Building Applications in a Split Development Directory in *Developing Applications for Oracle WebLogic Server*.

2.5 CertGen

The `CertGen` utility generates certificates that should only be used for demonstration or testing purposes, not in a production environment.

As of version 12.1.2 of WebLogic Server, the `CertGen` utility generates certificates with the following attributes by default:

- 2048-bit public key.
- SHA256 message digest algorithm.
- Subject Key Identifier extension.
- Authority Key Identifier extension (if the CA certificate contains a Subject Key ID.)

2.5.1 Syntax

```
$ java utils.CertGen
  -certfile <cert_file> -keyfile <private_key_file>
  -keyfilepass <private_key_password>
  [-cacert <ca_cert_file>][-cakey <ca_key_file>]
  [-cakeypass <ca_key_password>]
  [-selfsigned][-strength <key_strength>]
  [-digestalgorithm] <message digest algorithm>
  [-e <email_address>][-cn <common_name>]
  [-ou <org_unit>][-o <organization>]
  [-l <locality>][-s <state>][-c <country_code>]
  [-keyusage [digitalSignature,nonRepudiation,keyEncipherment,
  dataEncipherment,keyAgreement,keyCertSign,
  cRLSign,encipherOnly,decipherOnly]]
  [-keyusagecritical true|false]
  [-noskid]
  [-subjectkeyid <subject_key_identifier>]
  [-subjectkeyidformat UTF-8|BASE64]
  [-help]
```

Table 2-2 describes the arguments that are passed to the CertGen utility.

Table 2-2 CertGen Arguments

Argument	Definition
-certfile <i>cert_file</i> -keyfile <i>private_key_file</i>	Respectively, the output file names without extensions of the generated public certificate and private key. The appropriate extensions are appended when the pem and der files are created.
-keyfilepass <i>private_key_password</i>	The password for the generated private key.
-cacert <i>ca_cert_file</i> -cakey <i>ca_key_file</i> -cakeypass <i>ca_key_password</i>	Respectively, the public certificate, private key file, and private key password of the CA that will be used as the issuer of the generated certificate. If one or more of these options are not specified, the relevant demonstration CA files will be used: CertGenCA.der and CertGenCAKey.der. The CertGen utility first looks in the current working directory, then in the <i>WL_HOME/lib</i> directory.
-selfsigned	Generates a self-signed certificate that can be used as a trusted CA certificate. If this argument is specified, the <i>ca_cert_filename</i> , <i>ca_key_filename</i> , and <i>ca_key_password</i> arguments should not be specified.

Table 2-2 (Cont.) CertGen Arguments

Argument	Definition
<code>-digestalgorithm [message digest algorithm]</code>	The message digest algorithm used with the signature algorithm to sign the certificate. The default is SHA256. Supported values are MD5, SHA1, SHA256, SHA384, and SHA512.
<code>-strength <i>key_strength</i></code>	The length (in bits) of the keys to be generated. The default is 2048 bits. The longer the key, the more difficult it is for someone to break the encryption. Generating a certificate with an RSA key length less than 1024 bits may not work in JDK 7u40+. See http://www.oracle.com/technetwork/java/javase/7u40-relnotes-2004172.html for additional information.
<code>-e <i>email_address</i></code>	The email address associated with the generated certificate.
<code>-cn <i>common_name</i></code>	The name associated with the generated certificate.
<code>-ou <i>org_unit</i></code>	The name of the organizational unit associated with the generated certificate.
<code>-o <i>organization</i></code>	The name of the organization associated with the generated certificate.
<code>-l <i>locality</i></code>	The name of a city or town.
<code>-s <i>state</i></code>	The name of the state or province in which the organizational unit (ou) operates if your organization is in the United States or Canada, respectively. Do not abbreviate.
<code>-c <i>country_code</i></code>	Two-letter ISO code for your country. The code for the United States is US.
<code>-keyusage [digitalSignature, nonRepudiation, keyEncipherment, dataEncipherment, keyAgreement, keyCertSign, cRLSign, encipherOnly, decipherOnly]</code>	Generate certificate with a key usage extension, and with bits set according to the comma-separated list of bit names. Specify a key usage when you want to restrict the operation for a key that could be used for more than one operation.
<code>-keyusagecritical true false</code>	By default, a key usage extension is marked critical. To generate a certificate with a non-critical extension, use <code>-keyusagecritical false</code> .

Table 2-2 (Cont.) CertGen Arguments

Argument	Definition
-noskid	Prevents a subject key identifier extension in the certificate from being generated. CertGen ignores -subjectkeyid and -subjectkeyidformat if you specify -noskid.
-subjectkeyid <i>subject_key_identifier</i>	Generates a certificate with the specified subject key identifier.
-subjectkeyidformat UTF-8 BASE64	The format of the subjectkeyid value; UTF-8 is the default.

2.5.2 Example

By default, the CertGen utility looks for the CertGenCA.der and CertGenCAKey.der files in the current directory, or in the *WL_HOME* directory, as specified in the *weblogic.home* system property or the CLASSPATH. Alternatively, you can specify CA files on the command line.

Enter the following command to generate certificate files named *testcert* with private key files named *testkey*:

```
$ java utils.CertGen -keyfilepass mykeypass
-certificate testcert -keyfile testkey
Generating a certificate with common name machine-name and key strength 2048
issued by CA with certificate from CertGenCA.der file and key from CertGenCAKey.der
file
```

2.6 ClientDeployer

You use *weblogic.ClientDeployer* to extract the client-side JAR file from a Java EE EAR file, creating a deployable JAR file. The *weblogic.ClientDeployer* class is executed on the Java command line with the following syntax:

```
java weblogic.ClientDeployer ear-file client
```

The *ear-file* argument is an expanded directory (or Java archive file with a .ear extension) that contains one or more client application JAR files.

For example:

```
java weblogic.ClientDeployer app.ear myclient
```

In the preceding example, *app.ear* is the EAR file that contains a Java EE client packaged in *myclient.jar*.

Once the client-side JAR file is extracted from the EAR file, use the *weblogic.j2eeclient.Main* utility to bootstrap the client-side application and point it to a WebLogic Server instance as follows:

```
java weblogic.j2eeclient.Main clientjar URL [application args]
```

For example:

```
java weblogic.j2eeclient.Main helloWorld.jar t3://localhost:7001 Greetings
```

2.7 clientgen

Use `clientgen` to generate the client-side artifacts, such as the JAX-RPC stubs, needed to invoke a Web Service. See Ant Task Reference in *WebLogic Web Services Reference for Oracle WebLogic Server*.

2.8 Conversion (deprecated)

WebLogic Server 9.0 does not support conversion or upgrading from a pre-6.0 version of Oracle WebLogic Server. To upgrade from version 6.1 or later, see *Upgrading Oracle WebLogic Server*.

2.9 dbping

The `dbping` command-line utility tests the connection between a DBMS and your client machine via a JDBC driver. You must complete the installation of the driver before attempting to use this utility. For more information on how to install a driver, see the documentation from your driver vendor. Also see *Using Third-Party Drivers with WebLogic Server* in *Developing JDBC Applications for Oracle WebLogic Server*.

2.9.1 Creating a DB2 Package with dbping

With the WebLogic Type 4 JDBC Driver for DB2, you can also use the `dbping` utility to create a package on the DB2 server. When you ping the database with the `dbping` utility, the driver automatically creates the default package on the database server if it does not already exist. If the default package already exists on the database server, the `dbping` utility uses the existing package.

The default DB2 package includes 200 dynamic sections. You can specify a different number of dynamic sections to create in the DB2 package with the `-d` option. The `-d` option also sets `CreateDefaultPackage=true` and `ReplacePackage=true` on the connection used in the connection test, which forces the DB2 driver to replace the DB2 package on the DB2 server. (See *Using DataDirect Documentation* in *Developing JDBC Applications for Oracle WebLogic Server* for more information.) You can use the `-d` option with dynamic sections set at 200 to forcibly recreate a default package on the DB2 server.

Note:

When you specify the `-d` option, the `dbping` utility *recreates* the default package and uses the value you specify for the number of dynamic sections. It does not modify the existing package.

To create a DB2 package, the user that you specify must have CREATE PACKAGE privileges on the database.

2.9.2 Syntax

```
$ java utils.dbping DBMS [-d dynamicSections] user password DB
```

[Table 2-3](#) describes the arguments that are passed to the `dbping` command-line utility.

Table 2-3 dbping Arguments

Argument	Definition
<i>DBMS</i>	<p>Varies by DBMS and JDBC driver:</p> <p>DB2B—WebLogic Type 4 JDBC Driver for DB2</p> <p>DERBY—Embedded Derby driver</p> <p>JCONN2—Sybase JConnect 5.5 (JDBC 2.0) driver</p> <p>JCONN3—Sybase JConnect 6.0 (JDBC 2.0) driver</p> <p>JCONNECT—Sybase JConnect driver</p> <p>INFORMIXB—WebLogic Type 4 JDBC Driver for Informix</p> <p>MSSQLSERVER4—WebLogic jDriver for Microsoft SQL Server</p> <p>MSSQLSERVERB—WebLogic Type 4 JDBC Driver for Microsoft SQL Server</p> <p>MYSQL—MySQL's Type 4 Driver</p> <p>ORACLE—WebLogic jDriver for Oracle</p> <p>ORACLEB—WebLogic Type 4 JDBC Driver for Oracle</p> <p>ORACLE_THIN—Oracle Thin Driver</p> <p>POINTBASE—PointBase Universal Driver</p> <p>SYBASEB—WebLogic Type 4 JDBC Driver for Sybase</p>
<code>[-d <i>dynamicSections</i>]</code>	<p>Specifies the number of dynamic sections to create in the DB2 package. This option is for use with the WebLogic Type 4 JDBC Driver for DB2 only.</p> <p>If the <code>-d</code> option is specified, the driver automatically sets <code>CreateDefaultPackage=true</code> and <code>ReplacePackage=true</code> on the connection and creates a DB2 package with the number of dynamic sections specified.</p>
<i>user</i>	<p>Valid database username for login. Use the same values you use with <code>isql</code>, <code>sqlplus</code>, or other SQL command-line tools.</p> <p>For DB2 with the <code>-d</code> option, the user must have <code>CREATE PACKAGE</code> privileges on the database.</p>
<i>password</i>	<p>Valid database password for the user. Use the same values you use with <code>isql</code> or <code>sqlplus</code>.</p>

Table 2-3 (Cont.) dbping Arguments

Argument	Definition
<i>DB</i>	<p>Name and location of the database. Use the following format, depending on which JDBC driver you use:</p> <p>DB2B—Host:Port/DBName</p> <p>DERBY—Host:Port/DBName</p> <p>JCONN2—Host:Port/DBName</p> <p>JCONN3—Host:Port/DBName</p> <p>JCONNECT—Host:Port/DBName</p> <p>INFORMIXB—Host:Port/DBName/InformixServer</p> <p>MSSQLSERVER4—Host:Port/DBName or [DBName@]Host[:Port]</p> <p>MSSQLSERVERB—Host:Port/DBName</p> <p>MYSQL—Host:Port/DBName</p> <p>ORACLE—DBName (as listed in tnsnames.ora)</p> <p>ORACLEB—Host:Port/DBName</p> <p>ORACLE_THIN—Host:Port/DBName</p> <p>POINTBASE—Host[:Port]/DBName</p> <p>SYBASEB—Host:Port/DBName</p> <p>Where:</p> <ul style="list-style-type: none"> • <i>Host</i> is the name of the machine hosting the DBMS. • <i>Port</i> is port on the database host where the DBMS is listening for connections. • <i>DBName</i> is the name of a database on the DBMS. • <i>InFormixServer</i> is an Informix-specific environment variable that identifies the Informix DBMS server.

2.9.3 Examples

The following is an example using the Oracle Thin Driver.

```
C:\>java utils.dbping ORACLE_THIN scott tiger dbserver1:1561:demo

**** Success!!! ****
```

You can connect to the database in your app using:

```
java.util.Properties props = new java.util.Properties();
props.put("user", "scott");
props.put("password", "tiger");
props.put("dll", "ocijdbc9");
props.put("protocol", "thin");
java.sql.Driver d =
    Class.forName("oracle.jdbc.driver.OracleDriver").newInstance();
java.sql.Connection conn =
    Driver.connect("jdbc:oracle:thin:@dbserver1:1561:demo", props);
```

The following is an example using the Derby driver. Derby is an open source relational database management system bundled with WebLogic Server for use by the sample applications and code examples as a demonstration database.

```
$ java utils.dbping DERBY examples examples localhost:1527/demo
**** Success!!! ****
```

You can connect to the database in your app using:

```
java.util.Properties props = new java.util.Properties();
props.put("user", "examples");
props.put("password", "examples");
java.sql.Driver d =
    Class.forName("org.apache.derby.jdbc.ClientDriver").newInstance();
java.sql.Connection conn =
    Driver.connect("jdbc:derby://localhost:1527/demo", props);
```

2.10 ddcreate (deprecated)

This Ant task calls `EarInit`, which generates an `application.xml` and a `weblogic-application.xml` file for an EAR. For more information, see [EarInit \(deprecated\)](#).

2.11 DDInit

`DDInit` is a utility for generating deployment descriptors for applications to be deployed on Oracle WebLogic Server. Target a module's archive or folder and `DDInit` uses information from the module's class files to create appropriate deployment descriptor files.

In its command-line version, `DDInit` writes new files that overwrite existing descriptor files. If `META-INF` or `WEB-INF` does not exist, `DDInit` creates it.

Specify the type of Java EE deployable unit (either Web Application or Enterprise Application) for which you want deployment descriptors generated by using the `DDInit` command specific to the type, as described below.

2.11.1 WebInit

Target a WAR file or a folder containing files that you intend to archive as a WAR file, and `WebInit` will create `web.xml` and `weblogic.xml` files for the module.

```
prompt> java weblogic.marathon.ddinit.WebInit <module>
```

2.11.2 EarInit (deprecated)

The `EarInit` tool is deprecated in this version of Oracle WebLogic Server. As a result, you should not:

- Use the `DDInit` utility to generate deployment descriptors for Enterprise applications.
- Use the `ddcreate` ant task, which calls `EarInit`.

Generate an `application.xml` and a `weblogic-application.xml` file for an EAR using this command. Target an existing EAR or a folder containing JAR or WAR files you intend to archive into an EAR file.

```
prompt> java weblogic.marathon.ddinit.EarInit <module>
```

2.12 Deployer

Using the `weblogic.Deployer` tool, you can deploy Java EE applications and components to WebLogic Servers in a command-line or scripting environment. For detailed information on using this tool, see `weblogic.Deployer Command-Line Reference` in *Deploying Applications to Oracle WebLogic Server*.

The `weblogic.Deployer` utility replaces the `weblogic.deploy` utility, which has been deprecated.

2.13 der2pem

The `der2pem` utility converts an X509 certificate from DER format to PEM format. The `.pem` file is written in the same directory and has the same filename as the source `.der` file.

2.13.1 Syntax

```
$ java utils.der2pem derFile [headerFile] [footerFile]
```

Table 2-4 describes the arguments that are passed to the `der2pem` utility.

Table 2-4 *der2pem Arguments*

Argument	Description
<i>derFile</i>	The name of the file to convert. The filename must end with a <code>.der</code> extension, and must contain a valid certificate in <code>.der</code> format.
<i>headerFile</i>	The header to place in the PEM file. The default header is "-----BEGIN CERTIFICATE-----". Use a header file if the DER file being converted is a private key file, and create the header file containing one of the following: <ul style="list-style-type: none"> "-----BEGIN RSA PRIVATE KEY-----" for an unencrypted private key. "-----BEGIN ENCRYPTED PRIVATE KEY-----" for an encrypted private key. Note: There must be a new line at the end of the header line in the file.
<i>footerFile</i>	The header to place in the PEM file. The default header is "-----END CERTIFICATE-----". Use a footer file if the DER file being converted is a private key file, and create the footer file containing one of the following in the header: <ul style="list-style-type: none"> "-----END RSA PRIVATE KEY-----" for an unencrypted private key. "-----END ENCRYPTED PRIVATE KEY-----" for an encrypted private key. Note: There must be a new line at the end of the header line in the file.

2.13.2 Example

```
$ java utils.der2pem graceland_org.der
Decoding
.....
```

2.14 Derby

Derby is an open source relational database management system based on Java, JDBC, and SQL standards. It is bundled with WebLogic Server for use by the sample applications and code examples as a demonstration database. For more information about Derby, see <http://db.apache.org/derby>.

2.15 ejbc (deprecated)

See appc Reference in *Developing Enterprise JavaBeans, Version 2.1, for Oracle WebLogic Server*.

2.16 EJBGen

EJBGen is an Enterprise JavaBeans 2.0 code generator. You can annotate your Bean class file with javadoc tags and then use EJBGen to generate the Remote and Home classes and the deployment descriptor files for an EJB application, reducing to one the number of EJB files you need to edit and maintain.

See EJBGen Reference in *Developing Enterprise JavaBeans, Version 2.1, for Oracle WebLogic Server*.

2.17 encrypt

The `weblogic.security.Encrypt` utility encrypts clear text strings for use with Oracle WebLogic Server. The utility uses the encryption service of the current directory, or the encryption service for a specified Oracle WebLogic Server domain root directory.

Note:

An encrypted string must have been encrypted by the encryption service in the Oracle WebLogic Server domain where it will be used. If not, the server will not be able to decrypt the string.

You can only run the `weblogic.security.Encrypt` utility on a machine that has at least one server instance in an Oracle WebLogic Server domain; it cannot be run from a client.

Note:

Oracle recommends running the utility from the Administration Server domain directory or on the machine hosting the Administration Server and specifying a domain root directory.

2.17.1 Syntax

```
java [-Dweblogic.RootDirectory=dirname]
      [-Dweblogic.management.allowPasswordEcho=true]
      weblogic.security.Encrypt [password]
```

[Table 2-5](#) describes the arguments that are passed to the `weblogic.security.Encrypt` utility.

Table 2-5 Encrypt Arguments

Argument	Definition
<i>dirname</i>	Optional. Oracle WebLogic Server domain directory in which the encrypted string will be used. If not specified, the default domain root directory is the current directory (the directory in which the utility is being run).
<code>weblogic.management.allowPasswordEcho</code>	Optional. Allows echoing characters entered on the command line. <code>weblogic.security.Encrypt</code> expects that no-echo is available; if no-echo is not available, set this property to <code>true</code> .
<i>password</i>	Optional. Cleartext string to be encrypted. If omitted from the command line, you will be prompted to enter a password.

2.17.2 Examples

The utility returns an encrypted string using the encryption service of the domain located in the current directory.

```
java weblogic.security.Encrypt xxxxxx
{AES}yWv/i0qhfM4/IvzoghZjHj/xpJUkQPF80WuSfh0f0Ss=
```

The utility returns an encrypted string using the encryption service of the specified domain location.

```
java -Dweblogic.RootDirectory=./mydomain weblogic.security.Encrypt xxxxxx
{AES}wr86u9Z5Dhr+5p7WIbzTDSy4M/sl7EYnX/K5xzcarDQ=
```

The utility returns an encrypted string in the current directory, without echoing the password.

```
java weblogic.security.Encrypt
Password:
{AES}LIX8hoiStcAph0PGCpveouw/0U001ciODuj+TQh/bs=
```

2.18 getProperty

The `getProperty` utility gives you details about your Java setup and your system. It takes no arguments.

2.18.1 Syntax

```
$ java utils.getProperty
```

2.18.2 Example

```
$ java utils.getProperty
-- listing properties --
user.language=en
java.home=c:\javall\bin\..
awt.toolkit=sun.awt.windows.WToolkit
file.encoding.pkg=sun.io
java.version=1.1_Final
file.separator=\
line.separator=
```

```
user.region=US
file.encoding=8859_1
java.vendor=Sun Microsystems Inc.
user.timezone=PST
user.name=mary
os.arch=x86
os.name=Windows NT
java.vendor.url=http://www.sun.com/
user.dir=C:\weblogic
java.class.path=c:\weblogic\classes;c:\java\lib\cla...
java.class.version=45.3
os.version=4.0
path.separator=;
user.home=C:\
```

2.19 host2ior

The `host2ior` utility obtains the Interoperable Object Reference (IOR) of an Oracle WebLogic Server.

2.19.1 Syntax

```
$ java utils.host2ior hostname port
```

2.20 ImportPrivateKey

The `ImportPrivateKey` utility is used to load a private key into a private keystore file.

2.20.1 Syntax

```
$ java utils.ImportPrivateKey
  -certfile <cert_file> -keyfile <private_key_file>
  [-keyfilepass <private_key_password>]
  -keystore <keystore> -storepass <storepass> [-storetype <storetype>]
  -alias <alias> [-keypass <keypass>]
  [-help]
```

[Table 2-6](#) describes the arguments that are passed to the `ImportPrivateKey` utility.

Table 2-6 *ImportPrivateKey Arguments*

Argument	Definition
<i>cert_file</i>	The name of the certificate associated with the private key.
<i>private_key_file</i>	The name of the generated private key file.
<i>private_key_password</i>	The password for the private key.
<i>keystore</i>	The name of the keystore file. A new keystore is created if one does not exist.

Table 2-6 (Cont.) ImportPrivateKey Arguments

Argument	Definition
<i>storepass</i>	The password for the keystore.
<i>storetype</i>	<p>The type (format) of the keystore.</p> <p>The <i>storetype</i> argument, which is the same as that used by the <i>keytool</i> command, specifies the type of Java keystore. The default <i>storetype</i> is <i>jks</i>, defined by the <i>keystore.type</i> property in the <i>java.security</i> file:</p> <pre>keystore.type=jks</pre> <p>You can specify another <i>storetype</i> (for example, <i>pcks12</i> or <i>nCipher.SWorld</i>) if a configured security provider supports that type.</p>
<i>alias</i>	The name that is used for looking up the certificate and private key being imported into the keystore.
<i>keypass</i>	The password of the private key entry being imported into the keystore. If <i>keypass</i> is not specified, the first default is <i>private_key_password</i> , and the second default is <i>storepass</i> .

Note:

If you used CertGen to create a private key file protected by a password (`-keyfilepass private_key_password`), that password is the one required by ImportPrivateKey to extract the key from the key file and insert the key in the newly created keystore (which will contain both the certificate(s) from *cert_file* and the private key from *private_key_file*).

2.20.2 Example

Use the following steps to:

- Generate a certificate and private key using the CertGen utility
- Create a keystore and store a private key using the ImportPrivateKey utility

Note:

By default, the CertGen utility looks for the *CertGenCA.der* and *CertGenCAKey.der* files in the current directory, or in the *WL_HOME/server/lib* directory, as specified in the *weblogic.home* system property or the CLASSPATH.

Alternatively, you can specify CA files on the command line. If you want to use the default settings, there is no need to specify CA files on the command line.

To generate a certificate:

1. Enter the following command to generate certificate files named `testcert` with private key files named `testkey`:

```
$ java utils.CertGen -keyfilepass mykeyfilepass
-certfile testcert -keyfile testkey
Generating a certificate with common name return and key strength 1024
issued by CA with certificate from CertGenCA.der file and key from
CertGenCAKey.der file
```

2. Convert the certificate from DER format to PEM format.

```
$ java utils.der2pem CertGenCA.der
```

3. Concatenate the certificate and the Certificate Authority (CA).

```
$ cat testcert.pem CertGenCA.pem >> newcerts.pem
```

4. Create a new keystore named `mykeystore` and load the private key located in the `testkey.pem` file.

```
$ java utils.ImportPrivateKey -keystore mykeystore -storepass mypasswd
-keyfile mykey -keyfilepass mykeyfilepass -certfile newcerts.pem -keyfile
testkey.pem -alias passalias
```

```
No password was specified for the key entry
Key file password will be used
```

```
Imported private key testkey.pem and certificate newcerts.pem
into a new keystore mykeystore of type jks under alias passalias
```

2.21 jhtml2jsp

Converts JHTML files to JSP files. Be sure to inspect the results carefully. Given the unpredictable nature the JHTML code, `jhtml2jsp` does not necessarily produce flawless translations.

The output is a new JSP file named after the original file.

The HTTP servlets auto-generated from JSP pages differ from the regular HTTP servlets generated from JHTML. JSP servlets extend `weblogic.servlet.jsp.JspBase`, and so do not have access to the methods available to a regular HTTP servlet.

If your JHTML pages reference these methods to access the `servlet context` or `config` objects, you must substitute these methods with the reserved words in JSP that represent these implicit objects.

If your JHTML uses variables that have the same name as the reserved words in JSP, the tool will output a warning. You must edit your Java code in the generated JSP page to change the variable name to something other than a reserved word.

2.21.1 Syntax

```
$ java weblogic.utils.jhtml2jsp [-d directory] filename.jhtml
```

[Table 2-7](#) describes the argument that is passed to the `jhtml2jsp` tool.

Table 2-7 *html2jsp Arguments*

Argument	Definition
<code>-d directory</code>	Optional. The target directory. If the target directory isn't specified, output is written to the current directory.

2.22 jspc (deprecated)

JSP-specific compiler task. Use [appc](#).

2.23 logToZip

The `logToZip` utility searches an HTTP server log file, finds the Java classes loaded into it by the server, and creates an uncompressed `.zip` file that contains those Java classes. It is executed from the document root directory of your HTTP server.

To use this utility, you must have access to the log files created by the HTTP server.

2.23.1 Syntax

```
$ java utils.logToZip logfile codebase zipfile
```

[Table 2-8](#) describes the arguments that are passed to the `logToZip` utility.

Table 2-8 *logToZip Arguments*

Argument	Definition
<code>logfile</code>	Required. Fully-qualified pathname of the log file.
<code>codebase</code>	Required. Code base for the applet, or <code>" "</code> if there is no code base. By concatenating the code base with the full package name of the applet, you get the full pathname of the applet (relative to the HTTP document root).
<code>zipfile</code>	Required. Name of the <code>.zip</code> file to create. The resulting <code>.zip</code> file is created in the directory in which you run the program. The path name for the specified file can be relative or absolute. In the examples shown below, a relative path name is given, so the <code>.zip</code> file is created in the current directory.

2.23.2 Examples

The following example shows how a `.zip` file is created for an applet that resides in the document root itself, that is, with no code base:

```
$ cd /HTTP/Serv/docs
$ java utils.logToZip /HTTP/Serv/logs/access " " app2.zip
```

The following example shows how a `.zip` file is created for an applet that resides in a subdirectory of the document root:

```
C:\>cd \HTTP\Serv
C:\HTTP\Serv>java utils.logToZip \logs\applets\classes app3.zip
```

2.24 MBean Commands

Use the MBean commands (CREATE, DELETE, GET, INVOKE, and SET) to administer MBeans. See Editing Commands in *WLST Command Reference for WebLogic Server*.

2.25 MulticastTest

The `MulticastTest` utility helps you debug multicast problems when configuring a WebLogic Cluster. The utility sends out multicast packets and returns information about how effectively multicast is working on your network. Specifically, `MulticastTest` displays the following types of information via standard output:

1. A confirmation and sequence ID for each message sent out by the current server.
2. The sequence and sender ID of each message received from any clustered server, including the current server.
3. A missed-sequenced warning when a message is received out of sequence.
4. A missed-message warning when an expected message is not received.

To use `MulticastTest`, start one copy of the utility on each node on which you want to test multicast traffic.

Tip:

Do NOT run the `MulticastTest` utility by specifying the same multicast address (the `-a` parameter) as that of a currently running WebLogic Cluster. The utility is intended to verify that multicast is functioning properly before starting your clustered WebLogic Servers.

For information about setting up multicast, see the configuration documentation for the operating system and hardware of the WebLogic Server host machine. For more information about configuring a cluster, see *Administering Clusters for Oracle WebLogic Server*.

2.25.1 Syntax

```
$ java utils.MulticastTest -n name -a address [-p portnumber]
    [-t timeout] [-s send]
```

[Table 2-9](#) describes the arguments that are passed to the `MulticastTest` utility.

Table 2-9 MulticastTest Arguments

Argument	Definition
<code>-n name</code>	Required. A name that identifies the sender of the sequenced messages. Use a different name for each test process you start.
<code>-a address</code>	The multicast address on which: (a) the sequenced messages should be broadcast; and (b) the servers in the clusters are communicating with each other. (The default is 237.0.0.1.)

Table 2-9 (Cont.) MulticastTest Arguments

Argument	Definition
<code>-p portnumber</code>	Optional. The multicast port on which all the servers in the cluster are communicating. (The multicast port is the same as the listen port set for WebLogic Server, which defaults to 7001 if not set.)
<code>-t timeout</code>	Optional. Idle timeout, in seconds, if no multicast messages are received. If not set, the default is 600 seconds (10 minutes). If a timeout is exceeded, a positive confirmation of the timeout is sent to stdout.
<code>-s send</code>	Optional. Interval, in seconds, between sends. If not set, the default is 2 seconds. A positive confirmation of each message sent out is sent to stdout.

2.25.2 Example

```
$ java utils.MulticastTest -N server100 -A 237.155.155.1
Set up to send and receive on Multicast on Address 237.155.155.1 on port 7001
Will send a sequenced message under the name server100 every 2 seconds.
Received message 506 from server100
Received message 533 from server200
  I (server100) sent message num 507
Received message 507 from server100
Received message 534 from server200
  I (server100) sent message num 508
Received message 508 from server100
Received message 535 from server200
  I (server100) sent message num 509
Received message 509 from server100
Received message 536 from server200
  I (server100) sent message num 510
Received message 510 from server100
Received message 537 from server200
  I (server100) sent message num 511
Received message 511 from server100
Received message 538 from server200
  I (server100) sent message num 512
Received message 512 from server100
Received message 539 from server200
  I (server100) sent message num 513
Received message 513 from server100
```

2.26 myip

The myip utility returns the IP address of the host.

2.26.1 Syntax

```
$ java utils.myip
```

2.26.2 Example

```
$ java utils.myip
Host toyboat.toybox.com is assigned IP address: 192.0.0.1
```

2.27 pem2der

The `pem2der` utility converts an X509 certificate from PEM format to DER format. The `.der` file is written in the same directory as the source `.pem` file.

2.27.1 Syntax

```
$ java utils.pem2der pemFile
```

Table 2-10 describes the argument that is passed to the `pem2der` utility.

Table 2-10 pem2der Arguments

Argument	Description
<code>pemFile</code>	The name of the file to be converted. The filename must end with a <code>.pem</code> extension, and it must contain a valid certificate in <code>.pem</code> format.

2.27.2 Example

```
$ java utils.pem2der graceland_org.pem
Decoding
.....
.....
.....
.....
.....
```

2.28 rmic

The WebLogic RMI compiler is a command-line utility for generating and compiling remote objects. Use `weblogic.rmic` to generate dynamic proxies on the client-side for custom remote object interfaces in your application, and to provide hot code generation for server-side objects. See *Using the WebLogic RMI Compiler in Developing RMI Applications for Oracle WebLogic Server*.

2.29 Schema

The Schema utility lets you upload SQL statements to a database using the WebLogic JDBC drivers. For additional information about database connections, see *Developing JDBC Applications for Oracle WebLogic Server*.

2.29.1 Syntax

```
$ java utils.Schema driverURL driverClass [-u username]
      [-p password] [-verbose] SQLfile
```

Table 2-11 describes the arguments that are passed to the Schema utility.

Table 2-11 Schema Arguments

Argument	Definition
<code>driverURL</code>	Required. URL for the JDBC driver.
<code>driverClass</code>	Required. Pathname of the JDBC driver class.
<code>-u username</code>	Optional. Valid username.
<code>-p password</code>	Optional. Valid password for the user.
<code>-verbose</code>	Optional. Prints SQL statements and database messages.
<code>SQLfile</code>	Required. Text file with SQL statements.

2.29.2 Example

The following code shows a Schema command line for the `examples.utils` package:

```
$ java utils.Schema
"jdbc:derby://localhost:1527/demo"
"org.apache.derby.jdbc.ClientDriver" -u examples
-p examples examples/utils/ddl/demo.ddl
```

```
utils.Schema will use these parameters:
  url: jdbc:derby://localhost:1527/demo
  driver: org.apache.derby.jdbc.ClientDriver
  user: examples
  password: examples
  SQL file: examples/utils/ddl/demo.ddl
```

2.30 servicegen (deprecated)

The `servicegen` Ant task takes as input an EJB JAR file or a list of Java classes, and creates all the needed Web Service components and packages them into a deployable EAR file.

Web Services are now a Java EE standard, which has resulted in many changes between 8.1 and 9.0 WebLogic Web Services.

For a complete list of Web Services Ant tasks, see Ant Task Reference in *WebLogic Web Services Reference for Oracle WebLogic Server*.

2.31 SearchAndBuild

This Ant task executes `build.xml` files that are included within the `FileSet`. The task assumes that all of the files defined in `FileSet` are valid build files, and executes the Ant task of each of them.

Make certain that your `FileSet` filtering is correct. If you include the `build.xml` file that `SearchAndBuildTask` is being called from, you will be stuck in an infinite loop as this task will execute the top level build file—*itself*—forever.

2.31.1 Example

```
<project name="all_modules" default="all" basedir=".">
<taskdef name="buildAll"
classname="weblogic.ant.taskdefs.build.SearchAndBuildTask"/>
<target name="all">
<buildAll>
<fileset dir="${basedir}">
<include name="**\build.xml"/>
<exclude name="build.xml"/>
</fileset>
</buildAll>
</target>
</project>
```

2.32 source2wsdd (deprecated)

Generates a `web-services.xml` deployment descriptor file from the Java source file for a Java class-implemented WebLogic Web Service.

Web Services are now a Java EE standard, which has resulted in many changes between 8.1 and 9.0 WebLogic Web Services.

For a complete list of Web Services Ant tasks, see Ant Task Reference in *WebLogic Web Services Reference for Oracle WebLogic Server*.

2.33 system

The `system` utility displays basic information about your computer's operating environment, including the manufacturer and version of your JDK, your `CLASSPATH`, and details about your operating system.

2.33.1 Syntax

```
$ java utils.system
```

2.33.2 Example

```
$ java utils.system
* * * * * java.version * * * * *
1.5.0_03
* * * * * java.vendor * * * * *

* * * * * java.class.path * * * * *
C:\Oracle\Middleware\wlserver_10.3\server\classes;
C:\dev\src\build\JROCKI-2.0_0\lib\tools.jar;
...
* * * * * os.name * * * * *
Windows 2000
* * * * * os.arch * * * * *
x86
* * * * * os.version * * * * *
5.0
```

2.34 ValidateCertChain

WebLogic Server provides the `ValidateCertChain` utility to check whether or not an existing certificate chain will be rejected by WebLogic Server. The utility uses certificate chains from PEM files, PKCS-12 files, PKCS-12 keystores, and JKS keystores. A complete certificate chain must be used with the utility. The following is the syntax for the `ValidateCertChain` utility:

```
java utils.ValidateCertChain -file pemcertificatefilenamejava
utils.ValidateCertChain -pem pemcertificatefilenamejava
utils.ValidateCertChain -pkcs12store pkcs12storefilenamejava
utils.ValidateCertChain -pkcs12file pkcs12filename passwordjava
utils.ValidateCertChain -jks alias storefilename [storePass]
```

Example of valid certificate chain:

```
java utils.ValidateCertChain -pem zippychain.pemCert[0]: CN=zippy,
OU=FORTESTINGONLY,O=MyOrganization,L=MyTown,ST=MyState,C=USCert[1]:
CN=CertGenCAB,OU=FOR TESTINGONLY,O=MyOrganization,L=MyTown,ST=MyState,C=US
```

Certificate chain appears valid

Example of invalid certificate chain:

```
java utils.ValidateCertChain -jks mykey mykeystoreCert[0]: CN=corbal,
OU=FOR TESTING ONLY, O=MyOrganization,L=MyTown,ST=MyState,C=US
```

```
CA cert not marked with critical BasicConstraint indicating it is a
CACert[1]: CN=CACERT,OU=FOR TESTING ONLY,
O=MyOrganization,L=MyTown,ST=MyState,C=USCertificate chain is invalid
```

2.35 verboseToZip

When executed from the document root directory of your HTTP server, `verboseToZip` takes the standard output from a Java application run in verbose mode, finds the Java classes referenced, and creates an uncompressed `.zip` file that contains those Java classes.

2.35.1 Syntax

```
$ java utils.verboseToZip inputFile zipFileToCreate
```

[Table 2-12](#) describes the arguments that are passed to `verboseToZip`.

Table 2-12 *verboseToZip Arguments*

Argument	Definition
<i>inputFile</i>	Required. Temporary file that contains the output of the application running in verbose mode.
<i>zipFileToCreate</i>	Required. Name of the <code>.zip</code> file to be created. The resulting <code>.zip</code> file is be created in the directory in which you run the program.

2.35.2 Example

```
$ java -verbose myapplication > & classList.tmp
$ java utils.verboseToZip classList.tmp app2.zip
```

2.36 WebLogicMBeanMaker

This utility takes an XML MBean Description File (MDF) and outputs some intermediate Java files, including an MBean interface, an MBean implementation, and an associated MBean information file. Together, these intermediate files form the MBean type for a custom security provider.

For more information about the WebLogic MBeanMaker utility, see *Understand What the WebLogic MBeanMaker Provides* in *Developing Security Providers for Oracle WebLogic Server*.

2.36.1 Syntax

```
$ java -DMDF=xmlfile -Dfiles=filesdir -DcreateStubs=true|false
weblogic.management.commo.WebLogicMBeanMaker
```

[Table 2-13](#) describes the arguments that are passed to WebLogicMBeanMaker.

Table 2-13 WebLogicMBeanMaker Arguments

Argument	Description
-DMDF= <i>xmlfile</i>	Specifies that the WebLogic MBeanMaker utility should translate the MDF file, represented by <i>xmlfile</i> , into code. Whenever <i>xmlfile</i> is specified, a new set of output files is generated.
-Dfiles= <i>filesdir</i>	Specifies the location, represented by <i>filesdir</i> , where the WebLogic MBeanMaker utility places the intermediate files for the MBean type.
-DcreateStubs=true false	Specifies whether the WebLogic MBeanMaker utility overwrites any existing MBean implementation file.

2.37 wlappc

This utility compiles and validates a Java EE EAR file, an EJB JAR file, or a WAR file for deployment.

For more information, see *Building Modules and Applications Using wlappc* in *Developing Applications for Oracle WebLogic Server*.

2.38 wlcompile

Use the `wlcompile` Ant task to invoke the `javac` compiler to compile your application's Java files in a split development directory structure. See *Building Applications in a Split Development Directory* in *Developing Applications for Oracle WebLogic Server*.

2.39 wlconfig

The `wlconfig` Ant task enables you to configure a WebLogic Server domain by creating, querying, or modifying configuration MBeans on a running Administration Server instance. For complete documentation on this Ant task, see *Using Ant Tasks to Configure a WebLogic Server Domain* in *Developing Applications for Oracle WebLogic Server*.

2.40 wldeploy

The `wldeploy` Ant task enables you to perform Deployer functions (see [Deployer](#)) using attributes specified in an Ant task. See *Deploying and Packaging from a Split Development Directory* in *Developing Applications for Oracle WebLogic Server*.

2.41 wlpackage

You use the `wlpackage` Ant task to package your split development directory application as a traditional EAR file that can be deployed to WebLogic Server. See *Deploying and Packaging from a Split Development Directory* in *Developing Applications for Oracle WebLogic Server*.

2.42 wlservlet

The `wlservlet` Ant task enables you to start, reboot, shutdown, or connect to a WebLogic Server instance. The server instance may already exist in a configured WebLogic Server domain, or you can create a new single-server domain for development by using the `generateconfig=true` attribute. For complete documentation on this Ant task, see *Starting Servers and Creating Domains Using the wlservlet Ant Task* in *Developing Applications for Oracle WebLogic Server*.

2.43 wsdl2Service

The `wsdl2Service` Ant task is a Web Services tool that takes as input an existing WSDL file and generates the Java interface that represents the implementation of your Web Service and the `web-services.xml` file that describes the Web Service. See *Developing WebLogic Web Services Starting From a WSDL File: Main Steps* in *Developing JAX-WS Web Services for Oracle WebLogic Server*.

2.44 wsdlgen (deprecated)

The `wsdlgen` Ant task is a Web Services tool that generates a WSDL file from the EAR and WAR files that implement your Web Service.

Web Services are now a Java EE standard, which has resulted in many changes between 8.1 and 9.0 WebLogic Web Services.

For a complete list of Web Services Ant tasks, see *Ant Task Reference* in *WebLogic Web Services Reference for Oracle WebLogic Server*.

2.45 wspackage (deprecated)

Use the Web Services `wspackage` Ant task to package the various components of a WebLogic Web Service into a new deployable EAR file and add extra components to an already existing EAR file.

Web Services are now a Java EE standard, which has resulted in many changes between 8.1 and 9.0 WebLogic Web Services.

For a complete list of Web Services Ant tasks, see Ant Task Reference in *WebLogic Web Services Reference for Oracle WebLogic Server*.

weblogic.Server Command-Line Reference

This chapter describes the use of the `weblogic.Server` class.

The `weblogic.Server` class is the main class for a WebLogic Server instance. You start a server instance by invoking `weblogic.Server` in a Java command. You can invoke the class directly in a command prompt (shell), indirectly through scripts, or through the Node Manager.

Oracle recommends using `java weblogic.Server` primarily for initial development but not as a standard mechanism for starting production systems for the following reasons:

- `java weblogic.Server` will not function if you select a product directory outside of the `ORACLE_HOME` directory.
- When executing `java weblogic.Server`, patches will not be recognized by the WebLogic Server run time.

This chapter includes the following sections:

- [Required Environment and Syntax for weblogic.Server](#)
- [Default Behavior](#)
- [weblogic.Server Configuration Options](#)
- [Using the weblogic.Server Command Line to Start a Server Instance](#)
- [Using the weblogic.Server Command Line to Create a Domain](#)
- [Verifying Attribute Values That Are Set on the Command Line](#)

For information about using scripts to start an instance of WebLogic Server, see *Starting an Administration Server with a Startup Script and Starting Managed Servers With a Startup Script* in *Administering Server Startup and Shutdown for Oracle WebLogic Server*.

For information about using the Node Manager to start an instance of WebLogic Server, see *Using Node Manager to Control Servers* in the *Administering Node Manager for Oracle WebLogic Server*.

3.1 Required Environment and Syntax for weblogic.Server

This section describes the environment that you must set up before you can start a server instance. Then it describes the syntax for invoking `weblogic.Server`.

3.1.1 Environment

To set up your environment for the `weblogic.Server` command:

1. Install and configure the WebLogic Server software, as described in *Installing and Configuring Oracle WebLogic Server and Coherence*.
2. If desired, modify the CLASSPATH environment variable, as described in [Modifying the Classpath](#).
3. Include a Java Virtual Machine (JVM) in your PATH environment variable. You can use any JVM that is listed in Supported Configurations.

If you do not include a JVM in the PATH environment variable, you must provide a pathname for the Java executable file that the JVM provides.

3.1.2 Modifying the Classpath

After installation, WebLogic Server's classpath is already set, but you may choose to modify it for a number of reasons such as adding a patch to WebLogic Server, updating the version of Derby you are using, or adding support for Log4j logging.

To apply a patch to ALL of your WebLogic Server domains without the need to modify the classpath of a domain, give the patch JAR file the name, `weblogic_sp.jar`, and copy it into the `WL_HOME/server/lib` directory. The `commEnv.cmd/sh` script will automatically include a JAR named `weblogic_sp` on the classpath for you.

If you would rather not use the name `weblogic_sp.jar` for your patch file or you would just like to make sure a JAR file, such as one mentioned below, comes before `weblogic.jar` on the classpath:

- For ALL domains, edit the `commEnv.cmd/sh` script in `WL_HOME/common/bin` and prepend your JAR file to the `WEBLOGIC_CLASSPATH` environment variable.
- To apply a patch to a SPECIFIC WebLogic Server domain, edit the `setDomainEnv.cmd/sh` script in that domain's `bin` directory, and prepend the JAR file to the `PRE_CLASSPATH` environment variable.

Note:

`setDomainEnv` is designed to be sourced from other scripts, such as the `startWebLogic` script. `setDomainEnv` should not be called directly from within an interactive shell. Doing so can cause unpredictable issues in the domain.

If you use Derby, the open-source all-Java database management system included with Oracle WebLogic Server for use by the sample applications and code examples, include the following files on the classpath:

- `WL_HOME/common/derby/lib/derbyclient.jar` - for the driver on the client side
- `WL_HOME/common/derby/lib/derbynet.jar` and `WL_HOME/common/derby/lib/derby.jar` - for running the Derby network server

If you use WebLogic Enterprise Connectivity, include the following files on the classpath:

`WL_HOME/server/lib/wlepool.jar`

`WL_HOME/server/lib/wleorb.jar`

If you use Log4j logging, include the following file on the classpath:

```
WL_HOME/server/lib/log4j.jar
```

The shell environment in which you run a server determines which character you use to separate path elements. On Windows, you typically use a semicolon (;). In a BASH shell, you typically use a colon (:).

3.1.3 Syntax

The syntax for invoking `weblogic.Server` is as follows:

```
java [options] weblogic.Server [-help]
```

The `java weblogic.Server -help` command returns a list of frequently used options.

3.2 Default Behavior

If you have set up the required environment described in [Environment](#), when you enter the command `java weblogic.Server` with no options, WebLogic Server does the following:

1. Looks in the `domain_name/config` directory for a file named `config.xml`.
2. If `config.xml` exists in the `domain_name/config` directory, WebLogic Server does the following:
 - a. If only one server instance is defined in `config/config.xml`, it starts that server instance.

For example, if you issue `java weblogic.Server` from `ORACLE_HOME\user_projects\domains\medrec`, WebLogic Server starts the MedRec server.
 - b. If there are multiple server instances defined in `config/config.xml`:
 - If an Administration Server is defined, it looks for the server with that name.
 - If an Administration Server is not defined, it looks for a server configuration named `myserver`. If it finds such a server configuration, it starts the `myserver` instance.
 - If it does not find a server named `myserver`, WebLogic Server exits the `weblogic.Server` process and generates an error message.
3. If there is no `config.xml` file in the current directory, WebLogic Server prompts you to create one. If you respond `y`, WebLogic Server does the following:
 - a. Creates a server configuration named `myserver`, and persists the configuration in a file named `config/config.xml`.

Any options that you specify are persisted to the `config.xml` file. For example, if you specify `-Dweblogic.ListenPort=8001`, then WebLogic Server saves 8001 in the `config.xml` file. For any options that you do not specify, the server instance uses default values.

You can configure WebLogic Server to make backup copies of the configuration files. This facilitates recovery in cases where configuration

changes need to be reversed or the unlikely case that configuration files become corrupted. For more information, see *Configuration File Archiving in Understanding Domain Configuration for Oracle WebLogic Server*.

- b. Uses the username and password that you supply to create a user with administrative privileges. It stores the definition of this user along with other basic, security-related data in `domain_name/security` files named `DefaultAuthenticatorInit.ldift`, `DefaultRoleMapperInit.ldift`, and `SerializedSystemIni.dat`.

WebLogic Server also encrypts and stores your username and password in a `server_name/security/boot.properties` file, which enables you to bypass the login prompt during subsequent instantiations of the server. For more information, see *Boot Identity Files in Administering Server Startup and Shutdown for Oracle WebLogic Server*.
- c. Creates two scripts, `bin/startWebLogic.cmd` and `bin/startWebLogic.sh`, which you can use to start subsequent instantiations of the server. You can use a text editor to modify startup options such as whether the server starts in production mode or development mode. The `startWebLogic` script contains comments that describe each option.

Note that the server starts as an Administration Server in a new domain. There are no other servers in this domain, nor are any of your deployments or third-party solutions included. You can add them as you would add them to any WebLogic domain.

3.3 weblogic.Server Configuration Options

You can use `weblogic.Server` options to configure the attributes of a server instance. The following attributes are commonly used when starting a server instance:

- [JVM Parameters](#)
- [Location of Configuration Data](#)
- [Options that Override a Server's Configuration](#)

WebLogic Server provides other startup options that enable you to temporarily override a server's saved configuration. For information about these startup options, see [Options that Override a Server's Configuration](#).

Unless you are creating a new domain as described in [Using the weblogic.Server Command Line to Create a Domain](#), all startup options apply to the current server instantiation; they do not modify the persisted values in an existing `config.xml` file. Use the WebLogic Server Administration Console or WebLogic Scripting Tool (WLST) to modify the `config.xml` file. See *Creating Domains Using WLST Offline in Understanding the WebLogic Scripting Tool*.

For information on verifying the WebLogic Server attribute values that you set, see [Verifying Attribute Values That Are Set on the Command Line](#).

3.3.1 JVM Parameters

[Table 3-1](#) describes frequently used options that configure the Java Virtual Machine (JVM) in which the server instance runs. For a complete list of JVM options, see the documentation for your specific JVM. For a list of JVMs that can be used with WebLogic Server, see *Supported Configurations*.

Table 3-1 Frequently Used Options for Setting JVM Parameters

Option	Description
-Xms and -Xmx	<p>Specify the minimum and maximum values (in megabytes) for Java heap memory.</p> <p>For example, you might want to start the server with the default allocation of 256 megabytes of Java heap memory to the WebLogic Server. To do so, start the server using the <code>java -Xms256m</code> and <code>-Xmx512m</code> options.</p> <p>The values assigned to these parameters can dramatically affect the performance of your WebLogic Server and are provided here only as general defaults. In a production environment you should carefully consider the correct memory heap size to use for your applications and environment.</p>
-classpath	<p>The minimum content for this option is described under Modifying the Classpath.</p> <p>Instead of using this argument, you can use the <code>CLASSPATH</code> environment variable to specify the classpath.</p>
-client -server	<p>Used by some JVMs to start a HotSpot virtual machine, which enhances performance. For a list of JVMs that can be used with WebLogic Server, see Supported Configurations.</p>
-Dfile.encoding= <i>Canonical Name</i> weblogic.Server	<p>To display special characters on Linux browsers, set the JVM <code>file.encoding</code> system property to <code>ISO8859_1</code>. For example:</p> <pre>java -Dfile.encoding=ISO8859_1 weblogic.Server</pre> <p>For a complete listing, see the Supported Encodings page available at http://docs.oracle.com/javase/7/docs/technotes/guides/intl/encoding.doc.html.</p>

3.3.2 Location of Configuration Data

All server instances must have access to configuration data. [Table 3-2](#) provides options for indicating the location of this data.

Table 3-2 Options for Indicating the Location of Configuration Data

Option	Description
-Dweblogic.home= <i>WL_HOME</i>	<p>Specifies the location of the WebLogic home directory, which contains essential information.</p> <p>By default, <code>weblogic.Server</code> determines the location of the WebLogic home directory based on values in the classpath.</p>

Table 3-2 (Cont.) Options for Indicating the Location of Configuration Data

Option	Description
<code>-Dweblogic.RootDirectory=path</code>	Specifies the server's root directory. See A Server's Root Directory in <i>Understanding Domain Configuration for Oracle WebLogic Server</i> . By default, the root directory is the directory from which you issue the start command.
<code>-Dweblogic.management.GenerateDefaultConfig=true</code>	Prevents the <code>weblogic.Server</code> class from prompting for confirmation when creating a <code>config.xml</code> file. Valid only if you invoke <code>weblogic.Server</code> in an empty directory. See Default Behavior .
<code>-Dweblogic.Domain=domain</code>	Specifies the name of the domain. If you are using <code>weblogic.Server</code> to create a domain, you can use this option to give the domain a specific name. In addition, this option supports a directory structure that WebLogic Server required in releases prior to 7.0 and continues to support in current releases. Prior to 7.0, all configuration files were required to be located in the following pathname: <code>.../config/domain_name/config.xml</code> where <code>domain_name</code> is the name of the domain. If your domain's configuration file conforms to that pathname, and if you invoke the <code>weblogic.Server</code> command from a directory other than <code>config/domain_name</code> , you can include the <code>-Dweblogic.Domain=domain</code> argument to cause WebLogic Server to search for a <code>config.xml</code> file in a pathname that matches <code>config/domain_name/config.xml</code> .

For information on how a Managed Server retrieves its configuration data, see the `-Dweblogic.management.server` entry in [Table 3-3](#).

The WebLogic Server Administration Console does not display values that you set on the command line. For information on verifying the attribute values that you set, see [Verifying Attribute Values That Are Set on the Command Line](#).

3.3.2.1 Example

The following example starts a Managed Server instance named `SimpleManagedServer`. Specifying a `config.xml` file is not valid because Managed Servers contact the Administration Server for their configuration data. Multiple instances of WebLogic Server can use the same root directory. However, if your server instances share a root directory, make sure that all relative filenames are unique. In this example, `SimpleManagedServer` shares its root directory with `SimpleServer`. The command itself is issued from the `D:\` directory after running `WL_HOME\server\bin\setWLSEnv.cmd`:

```
D:\> java -Dweblogic.Name=SimpleManagedServer
-Dweblogic.management.server=http://localhost:7001
-Dweblogic.RootDirectory=c:\my_domains\SimpleDomain weblogic.Server
```

3.3.3 Options that Override a Server's Configuration

In most cases, you do not use startup options to override the configuration that is saved in the domain's `config.xml` file. However, in some extraordinary cases you might need to do so.


Tip:

When you use a startup option to override a configuration value, the server instance uses this value for the duration of its life cycle. Even if you use the WebLogic Server Administration Console, the WebLogic Scripting Tool, or some other utility to change the value in the configuration, the value will remain overridden until you restart the server without using the override.

For example, in a production environment, your organization might have a policy against modifying the domain's `config.xml` file, but you need to shut down the Administration Server and restart it using a temporary listen port. In this case, when you use the `weblogic.Server` command to start the Administration Server, you can include the `-Dweblogic.ListenPort=7501` startup option to change the listen port for the current server session. The server instance initializes its configuration MBeans from the `config.xml` file but substitutes 7501 as the value of its listen port. When you subsequently restart the server without passing the startup option, it will revert to using the value from the `config.xml` file, 8010. (See [Figure 3-1](#).)

Figure 3-1 Overriding `config.xml` Values

1. At startup, servers initialize configuration MBeans with data from the configuration files.



2. Startup options override the values in the configuration files.

The following options temporarily override a server's configuration:

- [Server Communication](#)
- [SSL](#)
- [Security](#)
- [Message Output and Logging](#)

- [Other Server Configuration Options](#)
- [Clusters](#)
- [Deployment](#)

3.3.3.1 Server Communication

Table 3-3 describes the options for configuring how servers communicate.

Table 3-3 Options for Configuring Server Communication

Option	Description
<code>-Dweblogic.management.server=[protocol://]Admin-host:port</code>	<p>Starts a server instance as a Managed Server and specifies the Administration Server that will configure and manage the server instance.</p> <p>The domain's configuration file does not specify whether a server configuration is an Administration Server or a Managed Server. You determine whether a server instance is in the role of Administration Server or Managed Server with the options that you use to start the instance. If you omit the <code>-Dweblogic.management.server</code> option in the start command, the server starts as an Administration Server (although within a given domain, there can be only one active Administration Server instance). Once an Administration Server is running, you must start all other server configurations as Managed Servers by including the <code>-Dweblogic.management.server</code> option in the start command.</p> <p>For <code>protocol</code>, specify HTTP, HTTPS, T3, or T3S. The T3S and HTTPS protocols require you to enable SSL on the Managed Server and the Administration Server and specify the Administration Server's SSL listen port.</p> <p>Note: Regardless of which protocol you specify, the initial download of a Managed Server's configuration is over HTTP or HTTPS. After the RMI subsystem initializes, the server instance can use the T3 or T3S protocol.</p> <p>For <code>Admin-host</code>, specify localhost or the DNS name or IP address of the machine where the Administration Server is running.</p> <p>For <code>port</code>, specify the Administration Server's listen port. If you set up the domain-wide administration port, <code>port</code> must specify the domain-wide administration port.</p> <p>For more information on configuring a connection to the Administration Server, see Configuring Managed Server Connections to the Administration Server in <i>Administering Server Startup and Shutdown for Oracle WebLogic Server</i>.</p>

Table 3-3 (Cont.) Options for Configuring Server Communication

Option	Description
<code>-Dweblogic.ListenAddress=host</code>	<p>Specifies the address at which this server instance listens for requests. The <i>host</i> value must be either the DNS name or the IP address of the computer that is hosting the server instance.</p> <p>This startup option overrides any listen address value specified in the <code>config.xml</code> file. The override applies to the current server instantiation; it does not modify the value in the <code>config.xml</code> file. Use any of the administration tools listed in Summary of System Administration Tools and APIs in <i>Understanding Oracle WebLogic Server</i> to modify the <code>config.xml</code> file.</p> <p>For more information, see Configure listen addresses in the <i>Oracle WebLogic Server Administration Console Online Help</i> and <i>Creating Domains Using WLST Offline</i> in <i>Understanding the WebLogic Scripting Tool</i>.</p>
<code>-Dweblogic.ListenPort=portnumber</code>	<p>Enables and specifies the plain-text (non-SSL) listen port for the server instance.</p> <p>This startup option overrides any listen port value specified in the <code>config.xml</code> file. The override applies to the current server instantiation; it does not modify the value in the <code>config.xml</code> file. Use any of the administration tools listed in Summary of System Administration Tools and APIs in <i>Understanding Oracle WebLogic Server</i> to modify the <code>config.xml</code> file.</p> <p>The default listen port is 7001.</p> <p>For more information, see Configure listen ports in the <i>Oracle WebLogic Server Administration Console Online Help</i> and <i>Creating Domains Using WLST Offline</i> in <i>Understanding the WebLogic Scripting Tool</i>.</p>
<code>-Dweblogic.ssl.ListenPort=portnumber</code>	<p>Enables and specifies the port at which this WebLogic Server instance listens for SSL connection requests.</p> <p>This startup option overrides any SSL listen port value specified in the <code>config.xml</code> file. The override applies to the current server instantiation; it does not modify the value in the <code>config.xml</code> file. Use any of the administration tools listed in Summary of System Administration Tools and APIs in <i>Understanding Oracle WebLogic Server</i> to modify the <code>config.xml</code> file.</p> <p>The default SSL listen port is 7002.</p> <p>For more information, see Configure listen ports in the <i>Oracle WebLogic Server Administration Console Online Help</i> and <i>Creating Domains Using WLST Offline</i> in <i>Understanding the WebLogic Scripting Tool</i>.</p>

Table 3-3 (Cont.) Options for Configuring Server Communication

Option	Description
-Dweblogic.management.discover={true false}	<p>Note: This option was removed as of WebLogic Server 9.0. Determines whether an Administration Server recovers control of a domain after the server fails and is restarted. A <code>true</code> value causes an Administration Server to communicate with all known Managed Servers and inform them that the Administration Server is running. A <code>false</code> value prevents an Administration Server from communicating with any Managed Servers that are currently active in the domain.</p> <p>Tip: Specify <code>false</code> for this option only in the development environment of a single server. Specifying <code>false</code> can cause server instances in the domain to have an inconsistent set of deployed modules.</p> <p>In WebLogic Server 9.0, this command is deprecated because if an Administration Server stops running while the Managed Servers in the domain continue to run, each Managed Server will periodically attempt to reconnect to the Administration Server at the interval specified by the <code>ServerMBean</code> attribute <code>AdminReconnectIntervalSecs</code>. For more information, see <i>Administering Server Startup and Shutdown for Oracle WebLogic Server</i>.</p>

The WebLogic Server Administration Console does not display values that you set on the command line. For information on verifying the attribute values that you set, see [Verifying Attribute Values That Are Set on the Command Line](#).

3.3.3.2 SSL

Each Weblogic Server instance uses an instance of `weblogic.management.configuration.SSLMBean` to represent its SSL configuration.

All of the options in the following table that start with `-Dweblogic.security.SSL` modify the configuration of the server's `SSLMBean`. For example, the `-Dweblogic.security.SSL.ignoreHostnameVerification` option sets the value of the `SSLMBean`'s `ignoreHostnameVerification` attribute.

[Table 3-4](#) describes the options for configuring a server to communicate using Secure Sockets Layer (SSL).

Note:

As of WebLogic Server version 12.1.1, JSSE is the only SSL implementation that is supported. The Certicom-based SSL implementation is removed and is no longer supported in WebLogic Server.

Table 3-4 Options for Configuring SSL

Option	Description
<pre>-Dweblogic.security.SSL. ignoreHostnameVerification=true</pre>	<p>Disables host name verification, which enables you to use the demonstration digital certificates that are shipped with WebLogic Server.</p> <p>By default, when a WebLogic Server instance is in the role of SSL client (it is trying to connect to some other server or application via SSL), it verifies that the host name that the SSL server returns in its digital certificate matches the host name of the URL used to connect to the SSL server. If the host names do not match, the connection is dropped.</p> <p>If you disable host name verification, either by using this option or by modifying the server's configuration in the <code>config.xml</code> file, the server instance does not verify host names when it is in the role of SSL client.</p> <p>Note: Oracle does not recommend using the demonstration digital certificates or turning off host name verification in a production environment.</p> <p>This startup option overrides any Host Name Verification setting in the <code>config.xml</code> file. The override applies to the current server instantiation; it does not modify the value in the <code>config.xml</code> file. Use the WebLogic Server Administration Console or WLST to modify the <code>config.xml</code> file.</p> <p>For more information, see Using Hostname Verification in <i>Administering Security for Oracle WebLogic Server</i>.</p>
<pre>-Dweblogic.security.SSL.HostnameVerifier= hostnameverifierimplementation</pre>	<p>Specifies the name of a custom Host Name Verifier class. The class must implement the <code>weblogic.security.SSL.HostnameVerifier</code> interface.</p>
<pre>-Dweblogic.security.SSL.sessionCache.ttl= sessionCacheTimeToLive</pre>	<p>Modifies the default server-session time-to-live for SSL session caching.</p> <p>The <code>sessionCacheTimeToLive</code> value specifies (in milliseconds) the time to live for the SSL session. The default value is 90000 milliseconds (90 seconds). This means if a client accesses the server again (via the same session ID) within 90 seconds, WebLogic Server will use the existing SSL session. You can change this value by setting <code>-Dweblogic.security.SSL.sessionCache.ttl</code> in the server startup script.</p> <p>For <code>sessionCache.ttl</code>:</p> <ul style="list-style-type: none"> • The minimum value is 1 • The maximum value is <code>Integer.MAX_VALUE</code> • The default value is 90000

Table 3-4 (Cont.) Options for Configuring SSL

Option	Description
-Dweblogic.security.SSL.CertificateCallback=callback-handler	<p>Specifies a certificate callback handler class, which evaluates details contained the end-user certificate passed in a secure connection request to WebLogic Server.</p> <p>Depending on the details contained in the certificate, the callback handler returns a <code>true</code> or <code>false</code>, which determines whether authentication is successful.</p> <p>Note: If you use a certificate callback implementation in WebLogic Server, a callback is generated whenever a request is received over a secure port. As a result, using certificate callbacks may impose a performance overhead that should be taken into consideration. For more information, see <i>Checking the Validity of End User Certificates</i> in <i>Administering Security for Oracle WebLogic Server</i>.</p>
-Dweblogic.management.pkpassword=pkpassword	<p>Specifies the password for retrieving SSL private keys from an encrypted flat file.</p> <p>Use this option if you store private keys in an encrypted flat file.</p>
-Dweblogic.security.SSL.trustedCAKeyStore=path	<p>Deprecated.</p> <p>If you configure a server instance to use the SSL features that were available before WebLogic Server 8.1, you can use this argument to specify the certificate authorities that the server or client trusts. The <code>path</code> value must be a relative or qualified name to the Sun JKS keystore file (contains a repository of keys and certificates).</p> <p>If a server instance is using the SSL features that were available before 8.1, and if you do not specify this argument, the WebLogic Server or client trusts all of the certificates that are specified in <code>JAVA_HOME\jre\lib\security</code>.</p> <p>Oracle recommends that you do not use the demonstration certificate authorities in any type of production deployment.</p> <p>For more information, see <i>Configuring SSL</i> in <i>Administering Security for Oracle WebLogic Server</i>.</p>
-Dsecurity.use.interopCA=true	<p>If you are using WebLogic Server together with a version of WebLogic Server prior to 12.1.2, be aware that the demo trust keystore of the previous versions does not contain the demo CA certificate used as of version 12.1.2. Therefore, if an instance of WebLogic Server sends its public certificate to an instance of WebLogic Server running a prior version, that public certificate will not automatically be trusted.</p> <p>Use this system property to generate interoperable demo certificates signed by the previous demo CA certificate.</p>

Table 3-4 (Cont.) Options for Configuring SSL

Option	Description
-Dweblogic.security.SSL.protocolVersion= <i>protocol</i>	<p>Specifies the protocol that is used for SSL connections. The <i>protocol</i> value can be one of the following:</p> <ul style="list-style-type: none"> • SSL3 — Only SSL V3.0 messages are sent and accepted. • TLS1 — Only TLS V1 messages are sent and accepted. • ALL — Only SSL V3.0 and/or TLS V1 messages are sent and accepted. (This is the default.) <p>For more information, see Using the <code>weblogic.security.SSL.protocolVersion</code> System Property in <i>Administering Security for Oracle WebLogic Server</i>.</p>
-Dweblogic.security.SSL.minimumProtocolVersion= <i>protocol</i>	<p>Specifies the <i>minimum protocol version</i> that is used for SSL connections. The <i>protocol</i> value can be one of the following:</p> <ul style="list-style-type: none"> • SSLv3 — Specifies SSL V3.0 as the minimum protocol version enabled in SSL connections. • TLSv1 — Specifies TLS V1.0 as the minimum protocol version enabled in SSL connections. • TLSvx.y — Specifies TLS Vx.y as the minimum protocol version enabled in SSL connections, where <i>x</i> is between 1 and 9, and <i>y</i> is between 0 and 9, inclusive. <p>For more information, see Using the <code>weblogic.security.SSL.minimumProtocolVersion</code> System Property in <i>Administering Security for Oracle WebLogic Server</i>.</p>

The WebLogic Server Administration Console does not display values that you set on the command line. For information on verifying the attribute values that you set, see [Verifying Attribute Values That Are Set on the Command Line](#).

3.3.3.2.1 Setting Additional SSL Attributes

To set additional SSL attributes from the startup command, do the following:

1. To determine which SSL attributes can be configured from startup options, view the WebLogic Server Javadoc for the [SSLMBean](#) and [ServerMBean](#), described in *MBean Reference for Oracle WebLogic Server*. The Javadoc also indicates valid values for each attribute.

Each attribute that `SSLMBean` and `ServerMBean` expose as a setter method can be set by a startup option.

2. To set attributes in the `SSLMBean`, add the following option to the start command:

```
-Dweblogic.ssl.attribute-name=value
```

where *attribute-name* is the name of the MBean's setter method without the `set` prefix.

3. To set attributes in the `ServerMBean`, add the following option to the start command:

```
-Dweblogic.server.attribute-name=value
```

where *attribute-name* is the name of the MBean's setter method without the set prefix.

For example, the SSLMBean exposes its Enabled attribute with the following setter method:

```
setEnabled()
```

To enable SSL for a server instance named MedRecServer, use the following command when you start MedRecServer:

```
java -Dweblogic.Name=MedRecServer
      -Dweblogic.ssl.Enabled=true weblogic.Server
```

The WebLogic Server Administration Console does not display values that you set on the command line. For information on verifying the attribute values that you set, see [Verifying Attribute Values That Are Set on the Command Line](#).

3.3.3.3 Security

[Table 3-5](#) describes the options for configuring general security parameters.

Table 3-5 Options for General Security Parameters

Option	Description
<code>-Dweblogic.management.username=username</code>	<p>Specifies the username under which the server instance will run.</p> <p>As of WebLogic Server 12.1.1, the boot username property <code>weblogic.management.username</code> has been deprecated and will be removed in a future release, and you will no longer be able to specify the username in the command for starting WebLogic Server in production mode.</p> <p>As an alternative, Oracle recommends that you use the <code>boot.properties</code> file to specify the boot username for WebLogic Server. For more information about the <code>boot.properties</code> file, see <i>Boot Identity Files in Administering Server Startup and Shutdown for Oracle WebLogic Server</i>.</p> <p>For information about other methods you can use to provide user credentials, see <i>Provide User Credentials to Start and Stop Servers in Administering Server Startup and Shutdown for Oracle WebLogic Server</i>.</p>

Table 3-5 (Cont.) Options for General Security Parameters

Option	Description
-Dweblogic.management.password=password	<p>Specifies the user password.</p> <p>As of WebLogic Server 12.1.1, the boot password system property <code>weblogic.management.password</code> has been deprecated and will be removed in a future release, and you will no longer be able to specify the password in the command for starting WebLogic Server in production mode.</p> <p>As an alternative, Oracle recommends that you use the <code>boot.properties</code> file to specify the boot password for WebLogic Server. For more information about the <code>boot.properties</code> file, see <i>Boot Identity Files in Administering Server Startup and Shutdown for Oracle WebLogic Server</i>.</p> <p>For information about other methods you can use to provide user credentials, see <i>Provide User Credentials to Start and Stop Servers in Administering Server Startup and Shutdown for Oracle WebLogic Server</i>.</p>
-Dweblogic.system.StoreBootIdentity=true	<p>Creates a <code>boot.properties</code> file in the server's root directory. The file contains the username and an encrypted version of the password that was used to start the server.</p> <p>Do not specify this argument in a server's <code>ServerStartMBean</code>. For more information, see <i>Specifying User Credentials When Starting a Server with the Node Manager in Administering Server Startup and Shutdown for Oracle WebLogic Server</i>.</p> <p>Oracle recommends that you do not add this argument to a startup script. Instead, use it only when you want to create a <code>boot.properties</code> file.</p> <p>For more information, see <i>Boot Identity Files in Administering Server Startup and Shutdown for Oracle WebLogic Server</i>.</p>
-Dweblogic.system.BootIdentityFile= filename	<p>Specifies a boot identity file that contains a username and password.</p> <p>The <code>filename</code> value must be the fully qualified pathname of a valid boot identity file. For example:</p> <pre data-bbox="802 1430 1458 1507">-Dweblogic.system.BootIdentityFile= WL_HOME\mydomain\servers\myserver\security \boot.properties</pre> <p>If you do not specify a filename, a server instance, or the <code>WLST SHUTDOWN</code> command, use the <code>boot.properties</code> file in the server's root directory.</p> <p>If there is no boot identity file, when starting a server, the server instance prompts you to enter a username and password.</p>
-Dweblogic.system.RemoveBootIdentity=true	Removes the boot identity file after a server starts.

Table 3-5 (Cont.) Options for General Security Parameters

Option	Description
-Dweblogic.security.anonymousUserName= <i>name</i>	<p>Assigns a user ID to anonymous users. By default, all anonymous users are identified with the string <code><anonymous></code>.</p> <p>To emulate the security behavior of WebLogic Server 6.x, specify <code>guest</code> for the <i>name</i> value and create a user named <code>guest</code> in your security realm.</p> <p>For more information, see <i>Users, Groups, and Security Roles in Securing Resources Using Roles and Policies for Oracle WebLogic Server</i>.</p>
-Djava.security.manager -Djava.security.policy[<i>=</i>]= <i>filename</i>	<p>Standard Java EE options that enable the Java Security Manager and specify a filename (using a relative or fully-qualified pathname) that contains Java 2 security policies.</p> <p>To use the WebLogic Server sample policy file, specify <code>WL_HOME\server\lib\weblogic.policy</code>.</p> <p>Using <code>-Djava.security.policy==<i>filename</i></code> (note the double equal sign (<code>==</code>)) causes the policy file to override any default security policy. When JACC is enabled, this property causes WebLogic Server to ignore any policy files that are used for servlet and EJB authorization. A single equal sign (<code>=</code>) causes the policy file to be appended to an existing security policy.</p> <p>Note: The WebLogic JACC provider does not require the Java Security Manager to be enabled.</p> <p>For more information, see <i>Using the Java Security Manager to Protect WebLogic Resources in Developing Applications with the WebLogic Security Service</i>.</p>
-Dweblogic.security. fullyDelegateAuthorization=true	<p>By default, roles and security policies cannot be set for an EJB or Web application through the WebLogic Server Administration Console unless security constraints were defined in the deployment descriptor for the EJB or Web application.</p> <p>Use this option when starting WebLogic Server to override this problem.</p> <p>This startup option does not work with EJBs or EJB methods that use <code><unchecked></code> or <code><restricted></code> tags or Web applications that do not have a role-name specified in the <code><auth-constraint></code> tag.</p>

Table 3-5 (Cont.) Options for General Security Parameters

Option	Description
<pre>-Dweblogic.management. anonymousAdminLookupEnabled=true</pre>	<p>Enables you to retrieve an MBeanHome interface without specifying user credentials. The MBeanHome interface is part of the WebLogic Server JMX API.</p> <p>If you retrieve MBeanHome without specifying user credentials, the interface gives you read-only access to the value of any MBean attribute that is not explicitly marked as protected by the Weblogic Server MBean authorization process.</p> <p>This startup option overrides the Anonymous Admin Lookup Enabled setting on the <i>domain_name</i> > Security > General page in the WebLogic Server Administration Console.</p> <p>By default, the MBeanHome API allows access to MBeans only for WebLogic users who are in one of the default security roles. more information, see Users, Groups, and Security Roles in <i>Securing Resources Using Roles and Policies for Oracle WebLogic Server</i>.</p>
<pre>-Dweblogic.security. identityAssertionTTL=seconds</pre>	<p>Configures the number of seconds that the Identity Assertion cache stores a Subject.</p> <p>When using an Identity Assertion provider (either for an X.509 certificate or some other type of token), Subjects are cached within the server. This greatly enhances performance for servlets and EJB methods with <code><run-as></code> tags as well as for other places where identity assertion is used but not cached (for example, signing and encrypting XML documents). There might be some cases where this caching violates the desired semantics.</p> <p>By default, Subjects remain in the cache for 300 seconds, which is also the maximum allowed value. Setting the value to <code>-1</code> disables the cache.</p> <p>Setting a high value generally improves the performance of identity assertion, but makes the Identity Assertion provider less responsive to changes in the configured Authentication provider. For example, a change in the user's group will not be reflected until the Subject is flushed from the cache and recreated.</p>

Table 3-5 (Cont.) Options for General Security Parameters

Option	Description
<pre>- Djavax.security.jacc.PolicyConfigurationFactory .provider=weblogic.security.jacc.simpleprovider .PolicyConfigurationFactoryImpl -Djavax.security.jacc.policy.provider= weblogic.security.jacc.simpleprovider .SimpleJACCPolicy - Dweblogic.security.jacc.RoleMapperFactory.provider= weblogic.security.jacc.simpleprovider .RoleMapperFactoryImpl</pre>	<p>Defining these three system properties is required to enable the use of the Java Authorization Contract for Containers in the security realm. When these providers are in use, JACC handles authorization decisions for the EJB and servlet containers for external applications. Any other authorization decisions for internal applications are handled by the authorization in the WebLogic Security framework.</p> <p>Note: JACC authorization does not require the use of Java SE security.</p> <p>The WebLogic JACC implementation expects that the policy object is the default <code>sun.security.provider.PolicyFile</code> class.</p> <p>When starting, WebLogic Server attempts to locate and instantiate the classes specified by the JACC startup properties and fails if it cannot find or instantiate them (if, for example, the files specified by the startup properties are not valid classes).</p> <p>For more information, see Using the Java Authorization Contract for Containers in <i>Developing Applications with the WebLogic Security Service</i></p>
<pre>-Dweblogic.security.ldap. maxSize=<max bytes></pre>	<p>Limits the size of the data file used by the embedded LDAP server. When the data file exceeds the specified size, WebLogic Server eliminates from the data file space occupied by deleted entries.</p>
<pre>-Dweblogic.security.ldap. changeLogThreshold=<number of entries></pre>	<p>Limits the size of the change log file used by the embedded LDAP server. When the change log file exceeds the specified number of entries, WebLogic Server truncates the change log by removing all entries that have been sent to all Managed Servers.</p>
<pre>- Dweblogic.security.providers.authentication. ldap.socketTimeout=seconds</pre>	<p>Sets a timeout value for the LDAP Authentication provider connection to an LDAP server. If multiple LDAP servers are specified in the <code>LDAPServerMBean.Host</code> attribute, the socket timeout applies to each individual LDAP server connection attempt that is made. The default value is 0, which sets no socket timeout on connections.</p> <p>Note that the <code>LDAPServerMBean.ConnectTimeout</code> attribute sets the timeout limit for <i>all</i> connection attempts that are made. Typically the socket timeout is used in conjunction with the connect timeout and the parallel connect delay. For more information, see Configuring Failover for LDAP Authentication Providers in <i>Administering Security for Oracle WebLogic Server</i>.</p>

The WebLogic Server Administration Console does not display values that you set on the command line. For information on verifying the attribute values that you set, see [Verifying Attribute Values That Are Set on the Command Line](#).

3.3.3.4 Message Output and Logging

Table 3-6 describes options for configuring a server instance's message output.

Table 3-6 Options for Configuring Message Output

Option	Description
-Dweblogic.Stdout=" <i>filename</i> "	<p>Redirects the server and JVM standard output stream to a file. You can specify a pathname that is fully qualified or relative to the WebLogic Server root directory.</p> <p>For more information, see Redirect JVM output in the <i>Oracle WebLogic Server Administration Console Online Help</i>.</p>
-Dweblogic.Stderr=" <i>filename</i> "	<p>Redirects the server and JVM standard error stream to a file. You can specify a pathname that is fully qualified or relative to the WebLogic Server root directory.</p> <p>For more information, see Redirecting JVM Output in Configuring Log Files and Filtering Log Messages for Oracle WebLogic Server.</p>
-Dweblogic.AdministrationMBeanAuditingEnabled={true false}	<p>Determines whether the Administration Server emits configuration auditing log messages when a user changes the configuration or invokes management operations on any resource within a domain.</p> <p>By default, the Administration Server does not emit configuration auditing messages.</p> <p>See Enable configuration auditing in the <i>Oracle WebLogic Server Administration Console Online Help</i>.</p>

The WebLogic Server Administration Console does not display values that you set on the command line. For information on verifying the attribute values that you set, see [Verifying Attribute Values That Are Set on the Command Line](#).

3.3.3.4.1 Setting Logging Attributes

Each Weblogic Server instance uses an instance of `weblogic.management.configuration.LogMBean` to represent the configuration of its logging services.

To set values for `LogMBean` attributes from the startup command, do the following:

1. To determine which log attributes can be configured from startup options, see [LogMBean](#) in *MBean Reference for Oracle WebLogic Server*. The Javadoc also indicates valid values for each attribute.

Each attribute that the `LogMBean` exposes as a setter method can be set by a startup option.

2. Add the following option to the start command:

```
-Dweblogic.log.attribute-name=value
```

where *attribute-name* is the name of the MBean's setter method without the `set` prefix.

The `LogMBean` exposes its `FileName` attribute with the following setter method:

```
setFileName()
```

To specify the name of the `MedRecServer` instance's local log file, use the following command when you start `MedRecServer`:

```
java -Dweblogic.Name=MedRecServer
     -Dweblogic.log.FileName="C:\logfiles\myServer.log"
     weblogic.Server
```

The WebLogic Server Administration Console does not display values that you set on the command line. For information on verifying the attribute values that you set, see [Verifying Attribute Values That Are Set on the Command Line](#).

3.3.3.5 Clusters

[Table 3-7](#) describes options for configuring additional attributes of a cluster.

Table 3-7 Options for Configuring Cluster Attributes

Option	Description
<code>-Dweblogic.cluster.multicastAddress</code>	<p>Determines the Multicast Address that clustered servers use to send and receive cluster-related communications. By default, a clustered server refers to the Multicast Address that is defined in the <code>config.xml</code> file. Use this option to override the value in <code>config.xml</code>.</p> <p>Note: The WebLogic Server Administration Console does not display values that you set on the command line. For information on verifying the attribute values that you set, see Verifying Attribute Values That Are Set on the Command Line.</p> <p>Regardless of how you set the Multicast Address, all servers in a cluster must communicate at the same Multicast Address.</p>

3.3.3.6 Deployment

[Table 3-8](#) describes options for configuring additional attributes for deployment.

Table 3-8 Options for Configuring Deployment Attributes

Option	Description
<code>-Dweblogic.deployment.IgnorePrepareStateFailures=true</code>	<p>Overrides the default deployment behavior by allowing a server to transition to <code>Running</code> even with static deployment <code>Prepare</code> failures.</p> <p>Note: This server level flag may cause inconsistent deployment behavior within clusters, such as issues with <code>HttpSessionReplication</code> or <code>SFSB</code> replication.</p>

3.3.3.7 Other Server Configuration Options

[Table 3-9](#) describes options for configuring additional attributes of a server instance.

Table 3-9 Options for Configuring Server Attributes

Option	Description
<code>-Dweblogic.Name=servername</code>	<p>Specifies the name of the server instance that you want to start. The specified value must refer to the name of a server that has been defined in the domain's <code>config.xml</code> file.</p>

Table 3-9 (Cont.) Options for Configuring Server Attributes

Option	Description
<pre>-Dweblogic.ProductionModeEnabled={true false}</pre>	<p>This attribute is deprecated in WebLogic Server 9.0.</p> <p>Determines whether a server starts in production mode.</p> <p>A true value prevents a WebLogic Server from automatically deploying and updating applications that are in the <i>domain_name</i>/autodeploy directory.</p> <p>If you do not specify this option, the assumed value is false.</p> <p>To enable production mode, you can use WLST to set <code>DomainMBean.isProductionModeEnabled</code> to true, or use the WebLogic Server Administration Console. See Change to production mode in the <i>Oracle WebLogic Server Administration Console Online Help</i>.</p> <p>Note: It is recommended that you enable production mode via the WebLogic Server Administration Console, in <code>config.xml</code>, or by supplying the <code>production</code> argument to <code>startWebLogic</code> script, for example, <code>startWebLogic.cmd production</code>. You should only enable production mode from the command line on the Administration Server.</p> <p>Note: It is important to note that when <code>ProductionModeEnabled</code> is set from the command line on the Administration Server, this value is propagated to all Managed Servers.</p>
<pre>-Dweblogic.management.startupMode=MODE</pre>	<p>The argument <i>MODE</i> represents either of the following:</p> <ul style="list-style-type: none"> • STANDBY — Starts a server and places it in the STANDBY state. See <i>Administering Server Startup and Shutdown for Oracle WebLogic Server</i>. <p>To use this startup argument, the domain must be configured to use the domain-wide administration port.</p> <p>For information about administration ports, see Administration Port and Administrative Channel in <i>Administering Server Environments for Oracle WebLogic Server</i> and Configure the domain-wide administration port in the <i>Oracle WebLogic Server Administration Console Online Help</i>.</p> <ul style="list-style-type: none"> • ADMIN — Starts a server and places it in the ADMIN state. See <i>Administering Server Startup and Shutdown for Oracle WebLogic Server</i>. <p>Specifying the startup mode startup option overrides any startup mode setting in the <code>config.xml</code> file. The override applies to the current server instantiation; it does not modify the value in the <code>config.xml</code> file. Use the WebLogic Server Administration Console or WLST to modify the <code>config.xml</code> file.</p> <p>If you do not specify this value (either on the command line or in <code>config.xml</code>), the default is to start in the RUNNING state.</p>

Table 3-9 (Cont.) Options for Configuring Server Attributes

Option	Description
-Dweblogic.apache.xerces.maxentityrefs= numerical-value	Limits the number of entities in an XML document that the WebLogic XML parser resolves. If you do not specify this option, the XML parser that WebLogic Server installs resolves 10,000 entity references in an XML document, regardless of how many an XML document contains.
-Dweblogic.jsp.windows.caseSensitive=true	Causes the JSP compiler on Windows systems to preserve case when it creates output files names. See Using the WebLogic JSP Compiler in <i>Developing Web Applications, Servlets, and JSPs for Oracle WebLogic Server</i> .
-Dweblogic.servlet.optimisticSerialization= true	When optimistic-serialization is turned on, WebLogic Server does not serialize-deserialize context and request attributes upon <code>getAttribute(name)</code> when the request is dispatched across servlet contexts. This means that you must make sure that the attributes common to Web applications are scoped to a common parent classloader (application scoped) or you must place them in the system classpath if the two Web applications do not belong to the same application. When optimistic-serialization is turned off (default value), WebLogic Server serialize-deserializes context and request attributes upon <code>getAttribute(name)</code> to avoid the possibility of <code>ClassCastExceptions</code> . The optimistic-serialization value can also be specified at domain level in the <code>WebAppContainerMBean</code> , which applies for all Web applications. The value in <code>weblogic.xml</code> , if specified, overrides the domain level value. The default value is false.
-Dweblogic.jdbc.qualifyRMName=false	When set, restores pre-WebLogic Server 11gR1 (10.3.1) behavior of not qualifying the JTA registration name with the domain name.
-Dweblogic.ScatteredReadsEnabled=true and -Dweblogic.GatheredWritesEnabled=true	When each is set to true, increases efficiency during I/O in environments with high network throughput. These command options are used together to optimize WebLogic Server performance for use with Oracle Exalogic. For more information, see the <i>Oracle Exalogic Enterprise Deployment Guide</i> .
- Dweblogic.replication.enableLazyDeserializat ion=true	When set to true, increases efficiency with session replication. This command option is used to optimize WebLogic Server performance for use with Oracle Exalogic. For more information, see the <i>Oracle Exalogic Enterprise Deployment Guide</i> .
- Dweblogic.resourcepool.max_test_wait_secs=se conds	The amount of time, in seconds, WebLogic Server waits before considering a connection test failed. By default, a server instance is assigned a value of 10 seconds. If set to zero, the server instance waits indefinitely.

Table 3-9 (Cont.) Options for Configuring Server Attributes

Option	Description
<code>-Dweblogic.wsee.client.ssl.usejdk=true</code>	<p>When set to true, switches from <code>WlsSSLAdapter</code> to <code>JdkSSLAdapter</code>.</p> <p>By default, WebLogic Server Web services use the <code>weblogic.wsee.connection.transport.https.WlsSSLAdapter</code> class for the SSL adapter. Setting the flag to true forces the use of <code>JdkSSLAdapter</code> from <code>weblogic.wsee.connection.transport.https.JdkSSLAdapter</code>.</p> <p>The <code>weblogic.wsee.connection.transport.https.HTTPSClientTransport</code> class that defines the <code>USE_JDK_SSL_PROPERTY</code> is used only in JAX-RPC. The property is not currently supported in JAX-WS.</p>
<code>-Dweblogic.http.URIDecodeEncoding=charset-name</code>	<p>The argument <code>charset-name</code> specifies the encoding used by the WebLogic Server Web container to decode the URI of an HTTP request or to encode the <code>Location</code> header in an HTTP response. The default value is <code>UTF-8</code>.</p> <p>For more information, see Determining the Encoding of an HTTP Request in <i>Developing Web Applications, Servlets, and JSPs for Oracle WebLogic Server</i>.</p>
<code>-Dweblogic.utils.http.requestparams.useArrayMap=true</code>	<p>When set to true in the server startup command, HTTP request parameters are stored using an <code>ArrayMap</code>. By default, HTTP request parameters are stored in a <code>TreeMap</code>.</p>

The WebLogic Server Administration Console does not display values that you set on the command line. For information on verifying the attribute values that you set, see [Verifying Attribute Values That Are Set on the Command Line](#).

3.4 Using the weblogic.Server Command Line to Start a Server Instance

A simple way to start a server instance is as follows:

1. In a command shell, set up the required environment variables by running the following script:

```
WL_HOME\server\bin\setWLSEnv.cmd (on Windows)
```

```
WL_HOME/server/bin/setWLSEnv.sh (on UNIX)
```

where `WL_HOME` is the directory in which you installed the WebLogic Server software.

2. In the command shell, change to the root of the domain directory, usually `ORACLE_HOME\user_projects\domains\DOMAIN_NAME`. For example, change to the `ORACLE_HOME\user_projects\domains\medrec` directory.
3. To start an Administration Server, enter the following command:

```
java weblogic.Server
```

Note:

The password you use must be a string of at least 8 case-sensitive characters. The space character is not supported. For more information, see *Creating a WebLogic Domain in [Creating WebLogic Domains Using the Configuration Wizard](#)*.

4. If the domain's Administration Server is already running, and if you have already defined a Managed Server in the `config.xml` file, you can start a Managed Server as follows:

```
java -Dweblogic.Name=managed-server-name
-Dweblogic.management.server=url-for-Administration-Server
weblogic.Server
```

For example, if you create a Managed Server named `MedRecManagedServer` in the `MedRec` domain, you can enter the following command:

```
java -Dweblogic.Name=MedRecManagedServer
-Dweblogic.management.server=localhost:7011
weblogic.Server
```

Note:

If you are using the demo certificates in a multi-server domain, Managed Server instances will fail to boot if you specify the fully-qualified DNS name of the Administration Server host machine, as in the argument `url-for-Administration-Server`. For information about this limitation and suggested workarounds, see *Limitation on CertGen Usage in [Administering Security for Oracle WebLogic Server](#)*.

3.5 Using the `weblogic.Server` Command Line to Create a Domain

You can use `weblogic.Server` to create a domain that contains a single server instance. You cannot use `weblogic.Server` to add Managed Server instances to a domain, nor can you use `weblogic.Server` to modify an existing domain.

As described in [Default Behavior](#), if `weblogic.Server` is unable to find a `config.xml` file, it offers to create the file. Any command option that you specify and that corresponds to an attribute that is persisted in the `config.xml` file will be persisted. For example, the `-Dweblogic.Name` and `-Dweblogic.Domain` options specify the name of a server configuration and the name of a domain. If `weblogic.Server` is unable to find a `config.xml` file, both of these values are persisted in `config.xml`. However, the `-Dweblogic.system.BootIdentityFile` option, which specifies a file that contains user credentials for starting a server instance, is not an attribute that the `config.xml` file persists.

To create and instantiate a simple example domain and server, do the following:

1. In a command shell, set up the required environment variables by running the following script:

```
WL_HOME\server\bin\setWLSEnv.cmd (on Windows)
WL_HOME/server/bin/setWLSEnv.sh (on UNIX)
```

where *WL_HOME* is the directory in which you installed the WebLogic Server software.

2. In the command shell, create an empty directory.
3. In the empty directory, enter the following command:

```
java -Dweblogic.Domain=SimpleDomain -Dweblogic.Name=SimpleServer  
-Dweblogic.management.username=weblogic -Dweblogic.management.password=password  
-Dweblogic.ListenPort=7001 weblogic.Server
```

After you enter this command, WebLogic Server asks if you want to create a new `config.xml` file. If you enter `y`, it then instantiates a domain named `SimpleDomain`. The domain's Administration Server is configured as follows:

- The name of the Administration Server is `SimpleServer`.
- The domain's security realm defines one administrative user, `weblogic`, with a password of `password`.
- For the listen address of the Administration Server, you can use `localhost`, the IP address of the host computer, or the DNS name of the host computer. For more information about setting the listen address, see [Configure listen addresses](#) in the *Oracle WebLogic Server Administration Console Online Help*.
- The Administration Server listens on port 7001.

Entering the `weblogic.Server` command as described in this section creates the following files:

- `config.xml`
- `DefaultAuthenticatorInit.ldif`, `DefaultRoleMapperInit.ldif`, and `SerializedSystemIni.dat`, which store basic security-related data.
- `boot.properties` file, which contains the username and password in an encrypted format. This file enables you to bypass the prompt for username and password when you start the server. For more information, see *Boot Identity Files* in *Administering Server Startup and Shutdown for Oracle WebLogic Server*.
- `startWebLogic.cmd` and `startWebLogic.sh`, that you can use to start subsequent instantiations of the server.

Note:

Invoking `weblogic.Server` in an empty directory results in implicit domain creation which uses the same configuration process as WLST offline and the Configuration Wizard and thus ensures that you always see uniform domains. As a result, implicitly creating a domain in an empty directory using `weblogic.Server` may take around 15 seconds.

3.6 Verifying Attribute Values That Are Set on the Command Line

The WebLogic Server Administration Console does not display values that you set on the command line because the startup options set attribute values for the server's local configuration MBean. To see the values that are in a server's local configuration MBean, use WLST as follows:

1. Complete the procedure described in Main Steps for Using WLST in Interactive or Script Mode in *Understanding the WebLogic Scripting Tool*.

```
>java weblogic.WLST
```

2. Start a WebLogic Server instance (see Starting and Stopping Servers in *Administering Server Startup and Shutdown for Oracle WebLogic Server*) and connect WLST to the server using the `connect` command. For detailed information about the `connect` command, see `connect` in the *WLST Command Reference for WebLogic Server*.

```
wls://(offline)> connect('username','password','t3s://localhost:7002')
Connecting to weblogic server instance running at t3s://localhost:7002 as
username weblogic ...
```

```
wls:/mydomain/serverConfig>
```

3. For example, to determine the multicast address that a cluster member is using, connect WLST to that server instance and enter the following commands:

```
wls:/mydomain/serverConfig> cd('Clusters/cluster_name')
wls:/mydomain/serverConfig/Clusters/mycluster> cmo.getMulticastAddress()

'239.192.0.0'
```

4. To determine the severity level of messages that the server instance prints to standard out, connect WLST to that server instance and enter the following commands:

```
wls:/mydomain/serverConfig> cd('Servers/server_name/Log/server_name')
wls:/mydomain/serverConfig/Servers/myserver/Log/myserver>cmo.getStdoutSeverity()

'Notice'
```

For more information on using WLST, see *Understanding the WebLogic Scripting Tool*. For more information about configuration MBeans, see *Understanding WebLogic Server MBeans in Developing Custom Management Utilities Using JMX for Oracle WebLogic Server*.