

Oracle® Fusion Middleware

RESTful Edit Reference for Oracle WebLogic Server

12c (12.2.1.3.0)

E80384-01

August 2017

This reference describes the RESTful edit resources that are used to manage WebLogic Server.

Copyright © 2015, 2017, Oracle and/or its affiliates. All rights reserved.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this is software or related documentation that is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, then the following notice is applicable:

U.S. GOVERNMENT END USERS: Oracle programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, delivered to U.S. Government end users are "commercial computer software" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, shall be subject to license terms and license restrictions applicable to the programs. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Xeon are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. AMD, Opteron, the AMD logo, and the AMD Opteron logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark of The Open Group.

This software or hardware and documentation may provide access to or information about content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services unless otherwise set forth in an applicable agreement between you and Oracle. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services, except as set forth in an applicable agreement between you and Oracle.

Contents

Preface	cxxix
----------------------	-------

1 Resources

/management/weblogic.....	1-2
/management/weblogic/{version}	1-6
/management/weblogic/{version}/currentUser.....	1-10
/management/weblogic/{version}/edit	1-13
/management/weblogic/{version}/edit/adminConsole	1-26
/management/weblogic/{version}/edit/appDeployments	1-29
/management/weblogic/{version}/edit/appDeployments/{name}	1-36
/management/weblogic/{version}/edit/appDeployments/{name}/createPlan	1-42
/management/weblogic/{version}/edit/appDeployments/{name}/redploy	1-44
/management/weblogic/{version}/edit/appDeployments/{name}/subDeploymentCreateForm	1-47
/management/weblogic/{version}/edit/appDeployments/{name}/subDeployments.....	1-49
/management/weblogic/{version}/edit/appDeployments/{name}/subDeployments/{name}	1-52
/management/weblogic/{version}/edit/appDeployments/{name}/subDeployments/{name}/subDeployments	1-56
/management/weblogic/{version}/edit/appDeployments/{name}/subDeployments/{name}/subDeployments/{name}	1-58
/management/weblogic/{version}/edit/appDeployments/{name}/update	1-61
/management/weblogic/{version}/edit/arePartitionsPresent	1-63
/management/weblogic/{version}/edit/batchConfig	1-65
/management/weblogic/{version}/edit/cdiContainer	1-68
/management/weblogic/{version}/edit/changeManager	1-71
/management/weblogic/{version}/edit/changeManager/activate	1-73
/management/weblogic/{version}/edit/changeManager/cancelEdit.....	1-75
/management/weblogic/{version}/edit/changeManager/forceResolve	1-77

/management/weblogic/{version}/edit/changeManager/safeResolve	1-79
/management/weblogic/{version}/edit/changeManager/startEdit.....	1-81
/management/weblogic/{version}/edit/clustercreateForm.....	1-83
/management/weblogic/{version}/edit/clusters	1-85
/management/weblogic/{version}/edit/clusters/{name}	1-88
/management/weblogic/{version}/edit/clusters/{name}/coherenceTier	1-93
/management/weblogic/{version}/edit/clusters/{name}/databaseLessLeasingBasis.....	1-96
/management/weblogic/{version}/edit/clusters/{name}/dynamicServers	1-99
/management/weblogic/{version}/edit/clusters/{name}/JTACluster	1-102
/management/weblogic/{version}/edit/clusters/{name}/overloadProtection	1-105
/management/weblogic/{version}/edit/clusters/{name}/overloadProtection/serverFailureTrigger	1-108
/management/weblogic/{version}/edit/clusters/{name}/overloadProtection/serverFailureTriggercreateForm	1-112
/management/weblogic/{version}/edit/coherenceClusterSystemResourcecreateForm	1-114
/management/weblogic/{version}/edit/coherenceClusterSystemResources	1-116
/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}.....	1-119
/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceCacheConfigcreateForm	1-124
/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceCacheConfigs	1-126
/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceCacheConfigs/{name}	1-129
/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceCacheConfigs/{name}/importCacheConfigurationFile	1-133
/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource	1-135
/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceAddressProviders	1-138
/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceAddressProviders/coherenceAddressProvidercreateForm	1-140
/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceAddressProviders/coherenceAddressProviders	1-142

/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceAddressProviders/coherenceAddressProviders/{name}/coherenceSocketAddressCreateForm 1-145

/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceAddressProviders/coherenceAddressProviders/{name}/coherenceSocketAddresses 1-148

/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceAddressProviders/coherenceAddressProviders/{name}/coherenceSocketAddresses/{name} 1-150

/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceAddressProviders/coherenceAddressProviders/{name}/coherenceSocketAddresses/{name} 1-153

/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceClusterParams 1-157

/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceClusterParams/coherenceCacheCreateForm 1-161

/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceClusterParams/coherenceCaches 1-163

/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceClusterParams/coherenceCaches/{name} 1-166

/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceClusterParams/coherenceClusterWellKnownAddresses 1-170

/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceClusterParams/coherenceClusterWellKnownAddresses/coherenceClusterWellKnownAddressCreateForm 1-172

/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceClusterParams/coherenceClusterWellKnownAddresses/coherenceClusterWellKnownAddresses 1-174

/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceClusterParams/coherenceClusterWellKnownAddresses/coherenceClusterWellKnownAddresses/{name} 1-177

/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceClusterParams/coherenceIdentityAsserter 1-181

/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceClusterParams/coherenceIdentityAsserter 1-181

renceClusterResource/coherenceClusterParams/coherenceIdentityAsserter/coherenceInitParamCreateForm 1-184

/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceClusterParams/coherenceIdentityAsserter/coherenceInitParams 1-186

/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceClusterParams/coherenceIdentityAsserter/coherenceInitParams/{name} 1-189

/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceClusterParams/coherenceKeystoreParams 1-193

/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceClusterParams/coherenceServiceCreateForm 1-196

/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceClusterParams/coherenceServices 1-198

/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceClusterParams/coherenceServices/{name} 1-201

/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceFederationParams 1-205

/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceLoggingParams 1-208

/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherencePersistenceParams 1-211

/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/importCustomClusterConfigurationFile 1-214

/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/subDeploymentCreateForm 1-216

/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/subDeployments 1-218

/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/subDeployments/{name} 1-221

/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/subDeployments/{name}/subDeployments 1-225

/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/subDeployments/{name}/subDeployments/{name} 1-227

/management/weblogic/{version}/edit/coherenceManagementClusterCreateForm.....	
1-230	
/management/weblogic/{version}/edit/coherenceManagementClusters	1-232
/management/weblogic/{version}/edit/coherenceManagementClusters/{name} ..	1-235
/management/weblogic/{version}/edit/coherenceManagementClusters/{name}/coherenceManagementAddressProviderCreateForm	1-239
/management/weblogic/{version}/edit/coherenceManagementClusters/{name}/coherenceManagementAddressProviders	1-241
/management/weblogic/{version}/edit/coherenceManagementClusters/{name}/coherenceManagementAddressProviders/{name}	1-244
/management/weblogic/{version}/edit/coherenceServerCreateForm.....	1-248
/management/weblogic/{version}/edit/coherenceServers.....	1-250
/management/weblogic/{version}/edit/coherenceServers/{name}	1-253
/management/weblogic/{version}/edit/coherenceServers/{name}/coherenceServerStart	1-257
/management/weblogic/{version}/edit/configurationProperties.....	1-260
/management/weblogic/{version}/edit/configurationProperties/{name}.....	1-263
/management/weblogic/{version}/edit/configurationPropertyCreateForm	1-267
/management/weblogic/{version}/edit/customResourceCreateForm.....	1-269
/management/weblogic/{version}/edit/customResources.....	1-271
/management/weblogic/{version}/edit/customResources/{name}	1-274
/management/weblogic/{version}/edit/customResources/{name}/customResource.....	1-278
/management/weblogic/{version}/edit/customResources/{name}/subDeploymentCreateForm	1-280
/management/weblogic/{version}/edit/customResources/{name}/subDeployments.....	1-282
/management/weblogic/{version}/edit/customResources/{name}/subDeployments/{name}	1-285
/management/weblogic/{version}/edit/customResources/{name}/subDeployments/{name}/subDeployments	1-289
/management/weblogic/{version}/edit/customResources/{name}/subDeployments/{name}/subDeployments/{name}	1-291
/management/weblogic/{version}/edit/debugPatches	1-294
/management/weblogic/{version}/edit/deploymentConfiguration	1-297
/management/weblogic/{version}/edit/deploymentConfiguration/deploymentValidationPlugin	1-300

/management/weblogic/{version}/edit/deploymentConfiguration/deploymentValidationPlugin/parameterCreateForm 1-303

/management/weblogic/{version}/edit/deploymentConfiguration/deploymentValidationPlugin/parameters 1-305

/management/weblogic/{version}/edit/deploymentConfiguration/deploymentValidationPlugin/parameters/{name} 1-308

/management/weblogic/{version}/edit/embeddedLDAP 1-312

/management/weblogic/{version}/edit/fileStoreCreateForm 1-315

/management/weblogic/{version}/edit/fileStores 1-317

/management/weblogic/{version}/edit/fileStores/{name} 1-320

/management/weblogic/{version}/edit/findConfigBeansWithTags 1-324

/management/weblogic/{version}/edit/findPartitionByID 1-327

/management/weblogic/{version}/edit/foreignJNDIProviderCreateForm 1-329

/management/weblogic/{version}/edit/foreignJNDIProviders 1-331

/management/weblogic/{version}/edit/foreignJNDIProviders/{name} 1-334

/management/weblogic/{version}/edit/foreignJNDIProviders/{name}/foreignJNDILinkCreateForm 1-338

/management/weblogic/{version}/edit/foreignJNDIProviders/{name}/foreignJNDILinks 1-340

/management/weblogic/{version}/edit/foreignJNDIProviders/{name}/foreignJNDILinks/{name} 1-343

/management/weblogic/{version}/edit/interceptors 1-347

/management/weblogic/{version}/edit/interceptors/interceptorCreateForm 1-350

/management/weblogic/{version}/edit/interceptors/interceptors 1-352

/management/weblogic/{version}/edit/interceptors/interceptors/{name} 1-355

/management/weblogic/{version}/edit/internalAppDeployments 1-359

/management/weblogic/{version}/edit/internalAppDeployments/{name} 1-361

/management/weblogic/{version}/edit/internalAppDeployments/{name}/createPlan 1-364

/management/weblogic/{version}/edit/internalAppDeployments/{name}/redeploy 1-366

/management/weblogic/{version}/edit/internalAppDeployments/{name}/subDeploymentCreateForm 1-368

/management/weblogic/{version}/edit/internalAppDeployments/{name}/subDeployments 1-370

/management/weblogic/{version}/edit/internalAppDeployments/{name}/subDeployments/{name} 1-373

/management/weblogic/{version}/edit/internalAppDeployments/{name}/subDeployments/{name}/subDeployments	1-377
/management/weblogic/{version}/edit/internalAppDeployments/{name}/subDeployments/{name}/subDeployments/{name}	1-379
/management/weblogic/{version}/edit/internalAppDeployments/{name}/update	1-382
/management/weblogic/{version}/edit/internalLibraries	1-384
/management/weblogic/{version}/edit/internalLibraries/{name}	1-386
/management/weblogic/{version}/edit/internalLibraries/{name}/createPlan	1-389
/management/weblogic/{version}/edit/internalLibraries/{name}/redeploy	1-391
/management/weblogic/{version}/edit/internalLibraries/{name}/subDeploymentCreateForm	1-393
/management/weblogic/{version}/edit/internalLibraries/{name}/subDeployments	1-395
/management/weblogic/{version}/edit/internalLibraries/{name}/subDeployments/{name}	1-398
/management/weblogic/{version}/edit/internalLibraries/{name}/subDeployments/{name}/subDeployments	1-402
/management/weblogic/{version}/edit/internalLibraries/{name}/subDeployments/{name}/subDeployments/{name}	1-404
/management/weblogic/{version}/edit/JDBCStoreCreateForm	1-407
/management/weblogic/{version}/edit/JDBCStores	1-409
/management/weblogic/{version}/edit/JDBCStores/{name}	1-412
/management/weblogic/{version}/edit/JDBCSystemResourceCreateForm	1-416
/management/weblogic/{version}/edit/JDBCSystemResources	1-418
/management/weblogic/{version}/edit/JDBCSystemResources/{name}	1-421
/management/weblogic/{version}/edit/JDBCSystemResources/{name}/JDBCResource	1-425
/management/weblogic/{version}/edit/JDBCSystemResources/{name}/JDBCResource/internalProperties	1-428
/management/weblogic/{version}/edit/JDBCSystemResources/{name}/JDBCResource/internalProperties/properties	1-430
/management/weblogic/{version}/edit/JDBCSystemResources/{name}/JDBCResource/internalProperties/properties/{name}	1-433
/management/weblogic/{version}/edit/JDBCSystemResources/{name}/JDBCResource/internalProperties/propertyCreateForm	1-437

/management/weblogic/{version}/edit/JDBCSystemResources/{name}/JDBCResource/
JDBCConnectionPoolParams 1-439

/management/weblogic/{version}/edit/JDBCSystemResources/{name}/JDBCResource/
JDBCDataSourceParams 1-442

/management/weblogic/{version}/edit/JDBCSystemResources/{name}/JDBCResource/
JDBCDriverParams 1-445

/management/weblogic/{version}/edit/JDBCSystemResources/{name}/JDBCResource/
JDBCDriverParams/properties 1-448

/management/weblogic/{version}/edit/JDBCSystemResources/{name}/JDBCResource/
JDBCDriverParams/properties/properties 1-450

/management/weblogic/{version}/edit/JDBCSystemResources/{name}/JDBCResource/
JDBCDriverParams/properties/properties/{name} 1-453

/management/weblogic/{version}/edit/JDBCSystemResources/{name}/JDBCResource/
JDBCDriverParams/properties/propertyCreateForm 1-457

/management/weblogic/{version}/edit/JDBCSystemResources/{name}/JDBCResource/
JDBCOracleParams 1-459

/management/weblogic/{version}/edit/JDBCSystemResources/{name}/JDBCResource/
JDBCXAParams 1-462

/management/weblogic/{version}/edit/JDBCSystemResources/{name}/subDeployment
CreateForm 1-465

/management/weblogic/{version}/edit/JDBCSystemResources/{name}/subDeployment
s 1-467

/management/weblogic/{version}/edit/JDBCSystemResources/{name}/subDeployment
s/{name} 1-470

/management/weblogic/{version}/edit/JDBCSystemResources/{name}/subDeployment
s/{name}/subDeployments 1-474

/management/weblogic/{version}/edit/JDBCSystemResources/{name}/subDeployment
s/{name}/subDeployments/{name} 1-476

/management/weblogic/{version}/edit/JMSBridgeDestinationCreateForm 1-479

/management/weblogic/{version}/edit/JMSBridgeDestinations..... 1-481

/management/weblogic/{version}/edit/JMSBridgeDestinations/{name}..... 1-484

/management/weblogic/{version}/edit/JMSInteropModuleCreateForm 1-488

/management/weblogic/{version}/edit/JMSInteropModules..... 1-490

/management/weblogic/{version}/edit/JMSInteropModules/{name} 1-493

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource
1-497

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/con
nectionFactories 1-502

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/con
nectionFactories/{name} 1-505

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/con
nectionFactories/{name}/clientParams 1-509

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/con
nectionFactories/{name}/defaultDeliveryParams 1-512

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/con
nectionFactories/{name}/flowControlParams 1-515

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/con
nectionFactories/{name}/loadBalancingParams 1-518

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/con
nectionFactories/{name}/securityParams 1-521

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/con
nectionFactories/{name}/transactionParams 1-524

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/con
nectionFactoryCreateForm 1-527

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/dest
inationKeyCreateForm 1-529

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/dest
inationKeys 1-531

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/dest
inationKeys/{name} 1-534

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/fore
ignServerCreateForm 1-538

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/fore
ignServers 1-540

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/fore
ignServers/{name} 1-543

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/foreignServers/{name}/foreignConnectionFactories 1-547

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/foreignServers/{name}/foreignConnectionFactories/{name} 1-550

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/foreignServers/{name}/foreignConnectionFactoryCreateForm 1-554

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/foreignServers/{name}/foreignDestinationCreateForm 1-556

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/foreignServers/{name}/foreignDestinations 1-558

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/foreignServers/{name}/foreignDestinations/{name} 1-561

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/foreignServers/{name}/JNDIProperties 1-565

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/foreignServers/{name}/JNDIProperties/{key} 1-568

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/foreignServers/{name}/JNDIPropertyCreateForm 1-572

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/queueCreateForm 1-574

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/queues 1-576

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/queues/{name} 1-579

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/queues/{name}/deliveryFailureParams 1-583

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/queues/{name}/deliveryFailureParams/findSubDeploymentName 1-586

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/queues/{name}/deliveryParamsOverrides 1-588

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/queues/{name}/messageLoggingParams 1-591

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/ques/{name}/thresholds 1-594

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/quotaCreateForm 1-597

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/quotas 1-599

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/quotas/{name} 1-602

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/SAFErrorHandlingCreateForm 1-606

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/SAFErrorHandlings 1-608

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/SAFErrorHandlings/{name} 1-611

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/SAFImportedDestinationCreateForm 1-615

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/SAFImportedDestinations 1-617

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/SAFImportedDestinations/{name} 1-620

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/SAFImportedDestinations/{name}/messageLoggingParams 1-625

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/SAFImportedDestinations/{name}/SAFQueueCreateForm 1-628

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/SAFImportedDestinations/{name}/SAFQueues 1-630

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/SAFImportedDestinations/{name}/SAFQueues/{name} 1-633

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/SAFImportedDestinations/{name}/SAFQueues/{name}/messageLoggingParams 1-637

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/SAFImportedDestinations/{name}/SAFTopicCreateForm 1-640

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/SAFImportedDestinations/{name}/SAFTopics 1-642

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/SAFImportedDestinations/{name}/SAFTopics/{name} 1-645

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/SAFImportedDestinations/{name}/SAFTopics/{name}/messageLoggingParams 1-649

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/SAFRemoteContextCreateForm 1-652

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/SAFRemoteContexts 1-654

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/SAFRemoteContexts/{name} 1-657

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/SAFRemoteContexts/{name}/SAFLoginContext 1-661

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/templateCreateForm 1-664

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/templates 1-666

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/templates/{name} 1-669

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/templates/{name}/deliveryFailureParams 1-674

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/templates/{name}/deliveryFailureParams/findSubDeploymentName 1-677

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/templates/{name}/deliveryParamsOverrides 1-679

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/templates/{name}/findErrorDestination 1-682

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/templates/{name}/groupParamCreateForm 1-684

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/templates/{name}/groupParams 1-686

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/templates/{name}/groupParams/{subDeploymentName} 1-689

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/templates/{name}/messageLoggingParams 1-693

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/templates/{name}/multicast 1-696

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/templates/{name}/thresholds 1-699

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/templates/{name}/topicSubscriptionParams 1-702

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/topicCreateForm 1-705

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/topics 1-707

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/topics/{name} 1-710

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/topics/{name}/deliveryFailureParams 1-715

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/topics/{name}/deliveryFailureParams/findSubDeploymentName 1-718

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/topics/{name}/deliveryParamsOverrides 1-720

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/topics/{name}/messageLoggingParams 1-723

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/topics/{name}/multicast 1-726

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/topics/{name}/thresholds 1-729

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/topics/{name}/topicSubscriptionParams 1-732

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/uniformDistributedQueueCreateForm 1-735

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/uniformDistributedQueues 1-737

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/uniformDistributedQueues/{name} 1-740

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/uniformDistributedQueues/{name}/deliveryFailureParams 1-744

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/uniformDistributedQueues/{name}/deliveryFailureParams/findSubDeploymentName 1-747

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/uniformDistributedQueues/{name}/deliveryParamsOverrides 1-749

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/uniformDistributedQueues/{name}/messageLoggingParams 1-752

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/uniformDistributedQueues/{name}/thresholds 1-755

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/uniformDistributedTopicCreateForm 1-758

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/uniformDistributedTopics 1-760

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/uniformDistributedTopics/{name} 1-763

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/uniformDistributedTopics/{name}/deliveryFailureParams 1-768

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/uniformDistributedTopics/{name}/deliveryFailureParams/findSubDeploymentName 1-771

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/uniformDistributedTopics/{name}/deliveryParamsOverrides 1-773

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/uniformDistributedTopics/{name}/messageLoggingParams 1-776

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/uniformDistributedTopics/{name}/multicast 1-779

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/uniformDistributedTopics/{name}/thresholds 1-782

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/uniformDistributedTopics/{name}/topicSubscriptionParams 1-785

/management/weblogic/{version}/edit/JMSInteropModules/{name}/subDeploymentCreateForm 1-788

/management/weblogic/{version}/edit/JMSInteropModules/{name}/subDeployments... 1-790

/management/weblogic/{version}/edit/JMSInteropModules/{name}/subDeployments/{name} 1-793

/management/weblogic/{version}/edit/JMSInteropModules/{name}/subDeployments/{name}/subDeployments 1-797

/management/weblogic/{version}/edit/JMSInteropModules/{name}/subDeployments/{name}/subDeployments/{name} 1-799

/management/weblogic/{version}/edit/JMSServerCreateForm 1-802

/management/weblogic/{version}/edit/JMSServers 1-804

/management/weblogic/{version}/edit/JMSServers/{name}..... 1-807

/management/weblogic/{version}/edit/JMSServers/{name}/JMSMessageLogFile 1-811

/management/weblogic/{version}/edit/JMSSystemResourceCreateForm 1-814

/management/weblogic/{version}/edit/JMSSystemResources..... 1-816

/management/weblogic/{version}/edit/JMSSystemResources/{name} 1-819

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource 1-823

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/connectionFactories 1-828

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/connectionFactories/{name} 1-831

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}/clientParams 1-835

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}/defaultDeliveryParams 1-838

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}/flowControlParams 1-841

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}/loadBalancingParams 1-844

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}/securityParams 1-847

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}/transactionParams 1-850

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/connectionFactoryCreateForm 1-853

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/destinationKeyCreateForm 1-855

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/destinationKeys 1-857

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/destinationKeys/{name} 1-860

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/foreignServerCreateForm 1-864

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/foreignServers 1-866

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/foreignServers/{name} 1-869

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignConnectionFactories 1-873

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignConnectionFactories/{name} 1-876

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignConnectionFactoryCreateForm 1-880

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignDestinationCreateForm 1-882

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignDestinations 1-884

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignDestinations/{name} 1-887

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/JNDIProperties 1-891

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/JNDIProperties/{key} 1-894

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/JNDIPropertyCreateForm 1-898

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/queueCreateForm 1-900

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/queues 1-902

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/queues/{name} 1-905

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/queues/{name}/deliveryFailureParams 1-909

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/queues/{name}/deliveryFailureParams/findSubDeploymentName 1-912

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/queues/{name}/deliveryParamsOverrides 1-914

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/queues/{name}/messageLoggingParams 1-917

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/queues/{name}/thresholds 1-920

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/quotasCreateForm 1-923

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/quotas 1-925

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/quotas/{name} 1-928

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/SAAErrorHandlingCreateForm 1-932

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/SAAErrorHandlings 1-934

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/SAAErrorHandlings/{name} 1-937

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/SAAImportedDestinationCreateForm 1-941

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/S
A
FIImportedDestinations 1-943

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/S
A
FIImportedDestinations/{name} 1-946

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/S
A
FIImportedDestinations/{name}/messageLoggingParams 1-951

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/S
A
FIImportedDestinations/{name}/SAFQueueCreateForm 1-954

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/S
A
FIImportedDestinations/{name}/SAFQueues 1-956

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/S
A
FIImportedDestinations/{name}/SAFQueues/{name} 1-959

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/S
A
FIImportedDestinations/{name}/SAFQueues/{name}/messageLoggingParams 1-963

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/S
A
FIImportedDestinations/{name}/SAFTopicCreateForm 1-966

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/S
A
FIImportedDestinations/{name}/SAFTopics 1-968

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/S
A
FIImportedDestinations/{name}/SAFTopics/{name} 1-971

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/S
A
FIImportedDestinations/{name}/SAFTopics/{name}/messageLoggingParams 1-975

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/S
A
FRemoteContextCreateForm 1-978

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/S
A
FRemoteContexts 1-980

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/S
A
FRemoteContexts/{name} 1-983

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/S
A
FRemoteContexts/{name}/SAFLoginContext 1-987

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/te
mplateCreateForm 1-990

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/templates 1-992

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/templates/{name} 1-995

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/templates/{name}/deliveryFailureParams 1-1000

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/templates/{name}/deliveryFailureParams/findSubDeploymentName 1-1003

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/templates/{name}/deliveryParamsOverrides 1-1005

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/templates/{name}/findErrorDestination 1-1008

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/templates/{name}/groupParamCreateForm 1-1010

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/templates/{name}/groupParams 1-1012

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/templates/{name}/groupParams/{subDeploymentName} 1-1015

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/templates/{name}/messageLoggingParams 1-1019

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/templates/{name}/multicast 1-1022

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/templates/{name}/thresholds 1-1025

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/templates/{name}/topicSubscriptionParams 1-1028

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/topicCreateForm 1-1031

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/topics 1-1033

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/topics/{name} 1-1036

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/topics/{name}/deliveryFailureParams 1-1041

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/topics/{name}/deliveryFailureParams/findSubDeploymentName 1-1044

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/topics/{name}/deliveryParamsOverrides 1-1046

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/topics/{name}/messageLoggingParams 1-1049

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/topics/{name}/multicast 1-1052

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/topics/{name}/thresholds 1-1055

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/topics/{name}/topicSubscriptionParams 1-1058

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/uniformDistributedQueueCreateForm 1-1061

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues 1-1063

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues/{name} 1-1066

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues/{name}/deliveryFailureParams 1-1070

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues/{name}/deliveryFailureParams/findSubDeploymentName 1-1073

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues/{name}/deliveryParamsOverrides 1-1075

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues/{name}/messageLoggingParams 1-1078

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues/{name}/thresholds 1-1081

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/uniformDistributedTopicCreateForm 1-1084

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/uni
formDistributedTopics 1-1086

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/uni
formDistributedTopics/{name} 1-1089

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/uni
formDistributedTopics/{name}/deliveryFailureParams 1-1094

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/uni
formDistributedTopics/{name}/deliveryFailureParams/findSubDeploymentName
1-1097

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/uni
formDistributedTopics/{name}/deliveryParamsOverrides 1-1099

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/uni
formDistributedTopics/{name}/messageLoggingParams 1-1102

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/uni
formDistributedTopics/{name}/multicast 1-1105

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/uni
formDistributedTopics/{name}/thresholds 1-1108

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/uni
formDistributedTopics/{name}/topicSubscriptionParams 1-1111

/management/weblogic/{version}/edit/JMSSystemResources/{name}/subDeploymentC
reateForm 1-1114

/management/weblogic/{version}/edit/JMSSystemResources/{name}/subDeployments
1-1116

/management/weblogic/{version}/edit/JMSSystemResources/{name}/subDeployments
/{name} 1-1119

/management/weblogic/{version}/edit/JMSSystemResources/{name}/subDeployments
/{name}/subDeployments 1-1123

/management/weblogic/{version}/edit/JMSSystemResources/{name}/subDeployments
/{name}/subDeployments/{name} 1-1125

/management/weblogic/{version}/edit/JMX..... 1-1128

/management/weblogic/{version}/edit/joltConnectionPoolCreateForm..... 1-1131

/management/weblogic/{version}/edit/joltConnectionPools 1-1133

/management/weblogic/{version}/edit/joltConnectionPools/{name} 1-1136

/management/weblogic/{version}/edit/JPA..... 1-1140

/management/weblogic/{version}/edit/JTA..... 1-1143

/management/weblogic/{version}/edit/libraries	1-1146
/management/weblogic/{version}/edit/libraries/{name}	1-1149
/management/weblogic/{version}/edit/libraries/{name}/createPlan.....	1-1153
/management/weblogic/{version}/edit/libraries/{name}/redeploy	1-1155
/management/weblogic/{version}/edit/libraries/{name}/subDeploymentCreateForm	1-1157
/management/weblogic/{version}/edit/libraries/{name}/subDeployments.....	1-1159
/management/weblogic/{version}/edit/libraries/{name}/subDeployments/{name}	1-1162
/management/weblogic/{version}/edit/libraries/{name}/subDeployments/{name}/subDeployments	1-1166
/management/weblogic/{version}/edit/libraries/{name}/subDeployments/{name}/subDeployments/{name}	1-1168
/management/weblogic/{version}/edit/lifecycleManagerConfig	1-1171
/management/weblogic/{version}/edit/lifecycleManagerConfig/configuredEndPointCreateForm	1-1174
/management/weblogic/{version}/edit/lifecycleManagerConfig/configuredEndpoints ...	1-1176
/management/weblogic/{version}/edit/lifecycleManagerConfig/configuredEndpoints/{name}	1-1179
/management/weblogic/{version}/edit/listTags	1-1183
/management/weblogic/{version}/edit/log	1-1185
/management/weblogic/{version}/edit/logFilterCreateForm.....	1-1188
/management/weblogic/{version}/edit/logFilters	1-1190
/management/weblogic/{version}/edit/logFilters/{name}	1-1193
/management/weblogic/{version}/edit/lookupSystemResource	1-1197
/management/weblogic/{version}/edit/lookupTarget.....	1-1199
/management/weblogic/{version}/edit/machineCreateForm.....	1-1201
/management/weblogic/{version}/edit/machines	1-1203
/management/weblogic/{version}/edit/machines/{name}	1-1206
/management/weblogic/{version}/edit/machines/{name}/nodeManager	1-1210
/management/weblogic/{version}/edit/mailSessionCreateForm.....	1-1213
/management/weblogic/{version}/edit/mailSessions	1-1215
/management/weblogic/{version}/edit/mailSessions/{name}	1-1218
/management/weblogic/{version}/edit/managedExecutorServiceCreateForm.....	1-1222
/management/weblogic/{version}/edit/managedExecutorServices	1-1224
/management/weblogic/{version}/edit/managedExecutorServices/{name}	1-1227
/management/weblogic/{version}/edit/managedExecutorServiceTemplateCreateForm ...	1-1231
/management/weblogic/{version}/edit/managedExecutorServiceTemplates	1-1233

/management/weblogic/{version}/edit/managedExecutorServiceTemplates/{name}.....	
1-1236	
/management/weblogic/{version}/edit/managedScheduledExecutorServiceCreateForm .	
1-1240	
/management/weblogic/{version}/edit/managedScheduledExecutorServices.....	1-1242
/management/weblogic/{version}/edit/managedScheduledExecutorServices/{name}.....	
1-1245	
/management/weblogic/{version}/edit/managedScheduledExecutorServiceTemplateCreateForm	1-1249
/management/weblogic/{version}/edit/managedScheduledExecutorServiceTemplates....	
1-1251	
/management/weblogic/{version}/edit/managedScheduledExecutorServiceTemplates/{name}	1-1254
/management/weblogic/{version}/edit/managedThreadFactories.....	1-1258
/management/weblogic/{version}/edit/managedThreadFactories/{name}.....	1-1261
/management/weblogic/{version}/edit/managedThreadFactoryCreateForm	1-1265
/management/weblogic/{version}/edit/managedThreadFactoryTemplateCreateForm	1-1267
/management/weblogic/{version}/edit/managedThreadFactoryTemplates.....	1-1269
/management/weblogic/{version}/edit/managedThreadFactoryTemplates/{name}.....	1-1272
/management/weblogic/{version}/edit/messagingBridgeCreateForm	1-1276
/management/weblogic/{version}/edit/messagingBridges	1-1278
/management/weblogic/{version}/edit/messagingBridges/{name}.....	1-1281
/management/weblogic/{version}/edit/migratableTargetCreateForm	1-1285
/management/weblogic/{version}/edit/migratableTargets	1-1287
/management/weblogic/{version}/edit/migratableTargets/{name}.....	1-1290
/management/weblogic/{version}/edit/optionalFeatureDeployment.....	1-1294
/management/weblogic/{version}/edit/optionalFeatureDeployment/optionalFeatureCreateForm	1-1297
/management/weblogic/{version}/edit/optionalFeatureDeployment/optionalFeatures ...	
1-1299	
/management/weblogic/{version}/edit/optionalFeatureDeployment/optionalFeatures/{name}	1-1302
/management/weblogic/{version}/edit/osgiFrameworkCreateForm.....	1-1306
/management/weblogic/{version}/edit/osgiFrameworks	1-1308
/management/weblogic/{version}/edit/osgiFrameworks/{name}	1-1311
/management/weblogic/{version}/edit/partitionCreateForm	1-1315
/management/weblogic/{version}/edit/partitions.....	1-1317
/management/weblogic/{version}/edit/partitions/{name}.....	1-1320
/management/weblogic/{version}/edit/partitions/{name}/adminVirtualTarget.	1-1327

/management/weblogic/{version}/edit/partitions/{name}/adminVirtualTarget/webServer 1-1330

/management/weblogic/{version}/edit/partitions/{name}/adminVirtualTarget/webServer/webServerLog 1-1333

/management/weblogic/{version}/edit/partitions/{name}/coherencePartitionCacheConfigCreateForm 1-1336

/management/weblogic/{version}/edit/partitions/{name}/coherencePartitionCacheConfigs 1-1338

/management/weblogic/{version}/edit/partitions/{name}/coherencePartitionCacheConfigs/{name} 1-1341

/management/weblogic/{version}/edit/partitions/{name}/coherencePartitionCacheConfigs/{name}/coherencePartitionCacheProperties 1-1345

/management/weblogic/{version}/edit/partitions/{name}/coherencePartitionCacheConfigs/{name}/coherencePartitionCacheProperties/{name} 1-1348

/management/weblogic/{version}/edit/partitions/{name}/coherencePartitionCacheConfigs/{name}/coherencePartitionCachePropertyCreateForm 1-1352

/management/weblogic/{version}/edit/partitions/{name}/configurationProperties 1-1354

/management/weblogic/{version}/edit/partitions/{name}/configurationProperties/{name} 1-1357

/management/weblogic/{version}/edit/partitions/{name}/configurationPropertyCreateForm 1-1361

/management/weblogic/{version}/edit/partitions/{name}/dataSourcePartition. 1-1363

/management/weblogic/{version}/edit/partitions/{name}/findEffectiveServerNames..... 1-1366

/management/weblogic/{version}/edit/partitions/{name}/foreignJNDIProviderOverrideCreateForm 1-1368

/management/weblogic/{version}/edit/partitions/{name}/foreignJNDIProviderOverrides 1-1370

/management/weblogic/{version}/edit/partitions/{name}/foreignJNDIProviderOverrides/{name} 1-1373

/management/weblogic/{version}/edit/partitions/{name}/foreignJNDIProviderOverrides/{name}/foreignJNDILinkCreateForm 1-1377

/management/weblogic/{version}/edit/partitions/{name}/foreignJNDIProviderOverrides/{name}/foreignJNDILinks 1-1379

/management/weblogic/{version}/edit/partitions/{name}/foreignJNDIProviderOverrid
es/{name}/foreignJNDILinks/{name} 1-1382

/management/weblogic/{version}/edit/partitions/{name}/internalAppDeployments.....
1-1386

/management/weblogic/{version}/edit/partitions/{name}/internalAppDeployments/{n
ame} 1-1388

/management/weblogic/{version}/edit/partitions/{name}/internalAppDeployments/{n
ame}/createPlan 1-1391

/management/weblogic/{version}/edit/partitions/{name}/internalAppDeployments/{n
ame}/redeploy 1-1393

/management/weblogic/{version}/edit/partitions/{name}/internalAppDeployments/{n
ame}/subDeploymentCreateForm 1-1395

/management/weblogic/{version}/edit/partitions/{name}/internalAppDeployments/{n
ame}/subDeployments 1-1397

/management/weblogic/{version}/edit/partitions/{name}/internalAppDeployments/{n
ame}/subDeployments/{name} 1-1400

/management/weblogic/{version}/edit/partitions/{name}/internalAppDeployments/{n
ame}/subDeployments/{name}/subDeployments 1-1404

/management/weblogic/{version}/edit/partitions/{name}/internalAppDeployments/{n
ame}/subDeployments/{name}/subDeployments/{name} 1-1406

/management/weblogic/{version}/edit/partitions/{name}/internalAppDeployments/{n
ame}/update 1-1409

/management/weblogic/{version}/edit/partitions/{name}/internalLibraries..... 1-1411

/management/weblogic/{version}/edit/partitions/{name}/internalLibraries/{name}.....
1-1413

/management/weblogic/{version}/edit/partitions/{name}/internalLibraries/{name}/cre
atePlan 1-1416

/management/weblogic/{version}/edit/partitions/{name}/internalLibraries/{name}/re
deploy 1-1418

/management/weblogic/{version}/edit/partitions/{name}/internalLibraries/{name}/su
bDeploymentCreateForm 1-1420

/management/weblogic/{version}/edit/partitions/{name}/internalLibraries/{name}/su
bDeployments 1-1422

/management/weblogic/{version}/edit/partitions/{name}/internalLibraries/{name}/subDeployments/{name} 1-1425

/management/weblogic/{version}/edit/partitions/{name}/internalLibraries/{name}/subDeployments/{name}/subDeployments 1-1429

/management/weblogic/{version}/edit/partitions/{name}/internalLibraries/{name}/subDeployments/{name}/subDeployments/{name} 1-1431

/management/weblogic/{version}/edit/partitions/{name}/JDBCSystemResourceOverrides/CreateForm 1-1434

/management/weblogic/{version}/edit/partitions/{name}/JDBCSystemResourceOverrides 1-1436

/management/weblogic/{version}/edit/partitions/{name}/JDBCSystemResourceOverrides/{name} 1-1439

/management/weblogic/{version}/edit/partitions/{name}/JDBCSystemResourceOverrides/{name}/JDBCPropertyOverrideCreateForm 1-1443

/management/weblogic/{version}/edit/partitions/{name}/JDBCSystemResourceOverrides/{name}/JDBCPropertyOverrides 1-1445

/management/weblogic/{version}/edit/partitions/{name}/JDBCSystemResourceOverrides/{name}/JDBCPropertyOverrides/{name} 1-1448

/management/weblogic/{version}/edit/partitions/{name}/JMSSystemResourceOverrideCreateForm 1-1452

/management/weblogic/{version}/edit/partitions/{name}/JMSSystemResourceOverrides 1-1454

/management/weblogic/{version}/edit/partitions/{name}/JMSSystemResourceOverrides/{name} 1-1457

/management/weblogic/{version}/edit/partitions/{name}/JMSSystemResourceOverrides/{name}/foreignServerCreateForm 1-1461

/management/weblogic/{version}/edit/partitions/{name}/JMSSystemResourceOverrides/{name}/foreignServers 1-1463

/management/weblogic/{version}/edit/partitions/{name}/JMSSystemResourceOverrides/{name}/foreignServers/{name} 1-1466

/management/weblogic/{version}/edit/partitions/{name}/JMSSystemResourceOverrides/{name}/foreignServers/{name}/foreignConnectionFactory 1-1470

/management/weblogic/{version}/edit/partitions/{name}/JMSSystemResourceOverrides/{name}/foreignServers/{name}/foreignConnectionFactory/{name} 1-1473

/management/weblogic/{version}/edit/partitions/{name}/JMSSystemResourceOverrides/{name}/foreignServers/{name}/foreignConnectionFactoryCreateForm 1-1477

/management/weblogic/{version}/edit/partitions/{name}/JMSSystemResourceOverrides/{name}/foreignServers/{name}/foreignDestinationCreateForm 1-1479

/management/weblogic/{version}/edit/partitions/{name}/JMSSystemResourceOverrides/{name}/foreignServers/{name}/foreignDestinations 1-1481

/management/weblogic/{version}/edit/partitions/{name}/JMSSystemResourceOverrides/{name}/foreignServers/{name}/foreignDestinations/{name} 1-1484

/management/weblogic/{version}/edit/partitions/{name}/JMSSystemResourceOverrides/{name}/foreignServers/{name}/JNDIProperties 1-1488

/management/weblogic/{version}/edit/partitions/{name}/JMSSystemResourceOverrides/{name}/foreignServers/{name}/JNDIProperties/{name} 1-1491

/management/weblogic/{version}/edit/partitions/{name}/JMSSystemResourceOverrides/{name}/foreignServers/{name}/JNDIPropertyCreateForm 1-1495

/management/weblogic/{version}/edit/partitions/{name}/JTAPartition..... 1-1497

/management/weblogic/{version}/edit/partitions/{name}/lookupAvailableTarget..... 1-1500

/management/weblogic/{version}/edit/partitions/{name}/mailSessionOverrideCreateForm 1-1502

/management/weblogic/{version}/edit/partitions/{name}/mailSessionOverrides..... 1-1504

/management/weblogic/{version}/edit/partitions/{name}/mailSessionOverrides/{name} 1-1507

/management/weblogic/{version}/edit/partitions/{name}/managedExecutorServiceTemplateCreateForm 1-1511

/management/weblogic/{version}/edit/partitions/{name}/managedExecutorServiceTemplates 1-1513

/management/weblogic/{version}/edit/partitions/{name}/managedExecutorServiceTemplates/{name} 1-1516

/management/weblogic/{version}/edit/partitions/{name}/managedScheduledExecutorServiceTemplateCreateForm 1-1520

/management/weblogic/{version}/edit/partitions/{name}/managedScheduledExecutorServiceTemplates 1-1522

/management/weblogic/{version}/edit/partitions/{name}/managedScheduledExecutorServiceTemplates/{name} 1-1525

/management/weblogic/{version}/edit/partitions/{name}/managedThreadFactoryTemplateCreateForm 1-1529

/management/weblogic/{version}/edit/partitions/{name}/managedThreadFactoryTemplates 1-1531

/management/weblogic/{version}/edit/partitions/{name}/managedThreadFactoryTemplates/{name} 1-1534

/management/weblogic/{version}/edit/partitions/{name}/partitionLog..... 1-1538

/management/weblogic/{version}/edit/partitions/{name}/partitionWorkManager 1-1541

/management/weblogic/{version}/edit/partitions/{name}/partitionWorkManagerCreateForm 1-1545

/management/weblogic/{version}/edit/partitions/{name}/resourceGroupCreateForm ... 1-1547

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups..... 1-1549

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name} 1-1552

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/appDeployments 1-1559

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/appDeployments/{name} 1-1563

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/appDeployments/{name}/createPlan 1-1567

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/appDeployments/{name}/redeploy 1-1569

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/appDeployments/{name}/subDeploymentCreateForm 1-1571

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/appDeployments/{name}/subDeployments 1-1573

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/appDeployments/{name}/subDeployments/{name} 1-1576

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/app
Deployments/{name}/subDeployments/{name}/subDeployments 1-1580

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/app
Deployments/{name}/subDeployments/{name}/subDeployments/{name} 1-1582

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/app
Deployments/{name}/update 1-1585

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/file
StoreCreateForm 1-1587

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/file
Stores 1-1589

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/file
Stores/{name} 1-1592

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/fin
dEffectiveTargets 1-1596

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/for
eignJNDIProviderCreateForm 1-1598

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/for
eignJNDIProviders 1-1600

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/for
eignJNDIProviders/{name} 1-1603

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/for
eignJNDIProviders/{name}/foreignJNDILinkCreateForm 1-1607

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/for
eignJNDIProviders/{name}/foreignJNDILinks 1-1609

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/for
eignJNDIProviders/{name}/foreignJNDILinks/{name} 1-1612

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDB
CStoreCreateForm 1-1616

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDB
CStores 1-1618

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDB
CStores/{name} 1-1621

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResourceCreateForm 1-1625

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources 1-1627

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources/{name} 1-1630

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource 1-1634

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource/internalProperties 1-1637

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource/internalProperties/properties 1-1639

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource/internalProperties/properties/{name} 1-1642

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource/internalProperties/propertyCreateForm 1-1646

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource/JDBCConnectionPoolParams 1-1648

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource/JDBCDataSourceParams 1-1651

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource/JBCDriverParams 1-1654

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource/JBCDriverParams/properties 1-1657

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource/JBCDriverParams/properties/properties 1-1659

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource/JBCDriverParams/properties/properties/{name} 1-1662

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource/JBCDriverParams/properties/propertyCreateForm 1-1666

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource/JDBCOracleParams 1-1668

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource/JDBCXAParams 1-1671

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources/{name}/subDeploymentCreateForm 1-1674

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources/{name}/subDeployments 1-1676

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources/{name}/subDeployments/{name} 1-1679

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources/{name}/subDeployments/{name}/subDeployments 1-1683

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources/{name}/subDeployments/{name}/subDeployments/{name} 1-1685

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSBridgeDestinationCreateForm 1-1688

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSBridgeDestinations 1-1690

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSBridgeDestinations/{name} 1-1693

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSServerCreateForm 1-1697

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSServers 1-1699

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSServers/{name} 1-1702

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSServers/{name}/JMSMessageLogFile 1-1706

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResourceCreateForm 1-1709

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources 1-1711

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name} 1-1714

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource 1-1718

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories 1-1723

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories/{name} 1-1726

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}/clientParams 1-1731

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}/defaultDeliveryParams 1-1734

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}/flowControlParams 1-1737

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}/loadBalancingParams 1-1740

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}/securityParams 1-1743

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}/transactionParams 1-1746

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/connectionFactoryCreateForm 1-1749

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/destinationKeyCreateForm 1-1751

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/destinationKeys 1-1753

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/destinationKeys/{name} 1-1756

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServerCreateForm 1-1760

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers 1-1762

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name} 1-1765

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignConnectionFactory 1-1770

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignConnectionFactory/{name} 1-1773

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignConnectionFactoryCreateForm 1-1777

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignDestinationCreateForm 1-1779

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignDestinations 1-1781

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignDestinations/{name} 1-1784

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/JNDIProperties 1-1788

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/JNDIProperties/{key} 1-1791

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/JNDIPropertyCreateForm 1-1795

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/queueCreateForm 1-1797

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/queues 1-1799

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/queues/{name} 1-1802

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/queues/{name}/deliveryFailureParams 1-1806

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/queues/{name}/deliveryFailureParams/findSubDeploymentName 1-1809

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/queues/{name}/deliveryParamsOverrides 1-1811

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/queues/{name}/messageLoggingParams 1-1814

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/queues/{name}/thresholds 1-1817

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/quotaCreateForm 1-1820

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/quotas 1-1822

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/quotas/{name} 1-1825

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFEErrorHandlingCreateForm 1-1829

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFEErrorHandlings 1-1831

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFEErrorHandlings/{name} 1-1834

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinationCreateForm 1-1838

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations 1-1840

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name} 1-1843

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/messageLoggingParams 1-1848

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFQueueCreateForm 1-1851

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFQueues 1-1853

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFQueues/{name} 1-1856

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFQueues/{name}/messageLoggingParams 1-1860

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFTopicCreateForm 1-1863

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFTopics 1-1865

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFTopics/{name} 1-1868

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFTopics/{name}/messageLoggingParams 1-1872

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFRemoteContextCreateForm 1-1875

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFRemoteContexts 1-1877

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFRemoteContexts/{name} 1-1880

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFRemoteContexts/{name}/SAFLoginContext 1-1884

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templateCreateForm 1-1887

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates 1-1889

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name} 1-1892

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/deliveryFailureParams 1-1897

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/deliveryFailureParams/findSubDeploymentName 1-1900

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/deliveryParamsOverrides 1-1902

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/findErrorDestination 1-1905

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/groupParamCreateForm 1-1907

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/groupParams 1-1909

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/groupParams/{subDeploymentName} 1-1912

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/messageLoggingParams 1-1916

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/multicast 1-1919

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/thresholds 1-1922

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/topicSubscriptionParams 1-1925

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/topicCreateForm 1-1928

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/topics 1-1930

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/topics/{name} 1-1933

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/topics/{name}/deliveryFailureParams 1-1938

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/topics/{name}/deliveryFailureParams/findSubDeploymentName 1-1941

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/topics/{name}/deliveryParamsOverrides 1-1943

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/topics/{name}/messageLoggingParams 1-1946

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/topics/{name}/multicast 1-1949

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/topics/{name}/thresholds 1-1952

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/topics/{name}/topicSubscriptionParams 1-1955

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedQueueCreateForm 1-1958

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues 1-1960

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues/{name} 1-1963

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues/{name}/deliveryFailureParams 1-1968

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JM

SSystemResources/{name}/JMSResource/uniformDistributedQueues/{name}/deliveryFailureParams/findSubDeploymentName 1-1971

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues/{name}/deliveryParamsOverrides 1-1973

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues/{name}/messageLoggingParams 1-1976

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues/{name}/thresholds 1-1979

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopicCreateForm 1-1982

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics 1-1984

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name} 1-1987

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}/deliveryFailureParams 1-1992

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}/deliveryFailureParams/findSubDeploymentName 1-1995

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}/deliveryParamsOverrides 1-1997

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}/messageLoggingParams 1-2000

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}/multicast 1-2003

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}/thresholds 1-2006

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}/topicSubscriptionParams 1-2009

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/subDeploymentCreateForm 1-2012

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/subDeployments 1-2014

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/subDeployments/{name} 1-2017

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/subDeployments/{name}/subDeployments 1-2021

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/subDeployments/{name}/subDeployments/{name} 1-2023

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/libraries 1-2026

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/libraries/{name} 1-2029

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/libraries/{name}/createPlan 1-2033

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/libraries/{name}/redeploy 1-2035

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/libraries/{name}/subDeploymentCreateForm 1-2037

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/libraries/{name}/subDeployments 1-2039

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/libraries/{name}/subDeployments/{name} 1-2042

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/libraries/{name}/subDeployments/{name}/subDeployments 1-2046

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/libraries/{name}/subDeployments/{name}/subDeployments/{name} 1-2048

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/lookupTarget 1-2051

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/mailSessionCreateForm 1-2053

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/mailSessions 1-2055

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/mailSessions/{name} 1-2058

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/managedExecutorServiceCreateForm 1-2062

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/managedExecutorServices 1-2064

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/managedExecutorServices/{name} 1-2067

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/managedScheduledExecutorServiceCreateForm 1-2071

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/managedScheduledExecutorServices 1-2073

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/managedScheduledExecutorServices/{name} 1-2076

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/managedThreadFactories 1-2080

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/managedThreadFactories/{name} 1-2083

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/managedThreadFactoryCreateForm 1-2087

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/messagingBridgeCreateForm 1-2089

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/messagingBridges 1-2091

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/messagingBridges/{name} 1-2094

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/osgiFrameworkCreateForm 1-2098

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/osgiFrameworks 1-2100

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/osgiFrameworks/{name} 1-2103

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/SAFAgentCreateForm 1-2107

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/SAFAgents 1-2109

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/SAFAgents/{name} 1-2112

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/SAFAgents/{name}/JMSSAFMessageLogFile 1-2116

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDSystemResourceCreateForm 1-2119

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDSystemResources 1-2121

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDSystemResources/{name} 1-2124

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDSystemResources/{name}/subDeploymentCreateForm 1-2128

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDSystemResources/{name}/subDeployments 1-2130

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDSystemResources/{name}/subDeployments/{name} 1-2133

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDSystemResources/{name}/subDeployments/{name}/subDeployments 1-2137

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDSystemResources/{name}/subDeployments/{name}/subDeployments/{name} 1-2139

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDSystemResources/{name}/WLDResource 1-2142

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDSystemResources/{name}/WLDResource/harvester 1-2144

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDSystemResources/{name}/WLDResource/harvester/harvestedTypeCreateForm 1-2147

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDSystemResources/{name}/WLDFResource/harvester/harvestedTypes 1-2149

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDSystemResources/{name}/WLDFResource/harvester/harvestedTypes/{name} 1-2152

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDSystemResources/{name}/WLDFResource/instrumentation 1-2156

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDSystemResources/{name}/WLDFResource/instrumentation/WLDFInstrumentationMonitorCreateForm 1-2159

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDSystemResources/{name}/WLDFResource/instrumentation/WLDFInstrumentationMonitors 1-2161

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDSystemResources/{name}/WLDFResource/instrumentation/WLDFInstrumentationMonitors/{name} 1-2164

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDSystemResources/{name}/WLDFResource/watchNotification 1-2168

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDSystemResources/{name}/WLDFResource/watchNotification/actionCreateForm 1-2174

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDSystemResources/{name}/WLDFResource/watchNotification/actions 1-2176

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDSystemResources/{name}/WLDFResource/watchNotification/actions/{name} 1-2179

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/arrayProperties 1-2184

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/arrayProperties/{name} 1-2187

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/arrayPropertyCreateForm 1-2191

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/configurationProperties 1-2193

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDSystemResources/{name}/WLDResource/watchNotification/actions/{name}/configurationProperties/{name} 1-2195

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDSystemResources/{name}/WLDResource/watchNotification/actions/{name}/encryptedProperties 1-2197

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDSystemResources/{name}/WLDResource/watchNotification/actions/{name}/encryptedProperties/{name} 1-2200

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDSystemResources/{name}/WLDResource/watchNotification/actions/{name}/encryptedPropertyCreateForm 1-2204

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDSystemResources/{name}/WLDResource/watchNotification/actions/{name}/mapProperties 1-2206

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDSystemResources/{name}/WLDResource/watchNotification/actions/{name}/mapProperties/{name} 1-2209

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDSystemResources/{name}/WLDResource/watchNotification/actions/{name}/mapProperties/{name}/configurationProperties 1-2213

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDSystemResources/{name}/WLDResource/watchNotification/actions/{name}/mapProperties/{name}/configurationProperties/{name} 1-2215

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDSystemResources/{name}/WLDResource/watchNotification/actions/{name}/mapProperties/{name}/encryptedProperties 1-2217

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDSystemResources/{name}/WLDResource/watchNotification/actions/{name}/mapProperties/{name}/encryptedProperties/{name} 1-2220

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDSystemResources/{name}/WLDResource/watchNotification/actions/{name}/mapProperties/{name}/encryptedPropertyCreateForm 1-2224

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDSystemResources/{name}/WLDResource/watchNotification/actions/{name}/mapProperties/{name}/properties 1-2226

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLD

DFSsystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/properties/{name} 1-2229

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/propertyCreateForm 1-2233

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapPropertyCreateForm 1-2235

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/properties 1-2237

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/properties/{name} 1-2240

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/propertyCreateForm 1-2244

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/heapDumpActionCreateForm 1-2246

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/heapDumpActions 1-2248

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/heapDumpActions/{name} 1-2251

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/imageNotificationCreateForm 1-2255

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/imageNotifications 1-2257

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/imageNotifications/{name} 1-2260

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMSNotificationCreateForm 1-2264

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDSystemResources/{name}/WLDFResource/watchNotification/JMSNotifications
1-2266

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDSystemResources/{name}/WLDFResource/watchNotification/JMSNotifications/{name}
e} 1-2269

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDSystemResources/{name}/WLDFResource/watchNotification/JMXNotificationCreateForm
1-2273

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDSystemResources/{name}/WLDFResource/watchNotification/JMXNotifications
1-2275

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDSystemResources/{name}/WLDFResource/watchNotification/JMXNotifications/{name}
e} 1-2278

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDSystemResources/{name}/WLDFResource/watchNotification/logActionCreateForm
1-2282

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDSystemResources/{name}/WLDFResource/watchNotification/logActions 1-2284

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDSystemResources/{name}/WLDFResource/watchNotification/logActions/{name}
1-2287

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDSystemResources/{name}/WLDFResource/watchNotification/lookupActions 1-2291

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDSystemResources/{name}/WLDFResource/watchNotification/lookupNotification
1-2293

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDSystemResources/{name}/WLDFResource/watchNotification/RESTNotificationCreateForm
1-2295

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDSystemResources/{name}/WLDFResource/watchNotification/RESTNotifications
1-2297

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDSystemResources/{name}/WLDFResource/watchNotification/RESTNotifications/{name}
1-2300

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDSystemResources/{name}/WLDFResource/watchNotification/scaleDownActionCreateForm 1-2304

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDSystemResources/{name}/WLDFResource/watchNotification/scaleDownActions 1-2306

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDSystemResources/{name}/WLDFResource/watchNotification/scaleDownActions/{name} 1-2309

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDSystemResources/{name}/WLDFResource/watchNotification/scaleUpActionCreateForm 1-2313

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDSystemResources/{name}/WLDFResource/watchNotification/scaleUpActions 1-2315

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDSystemResources/{name}/WLDFResource/watchNotification/scaleUpActions/{name} 1-2318

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDSystemResources/{name}/WLDFResource/watchNotification/scriptActionCreateForm 1-2322

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDSystemResources/{name}/WLDFResource/watchNotification/scriptActions 1-2324

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDSystemResources/{name}/WLDFResource/watchNotification/scriptActions/{name} 1-2327

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDSystemResources/{name}/WLDFResource/watchNotification/SMTPNotificationCreateForm 1-2331

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDSystemResources/{name}/WLDFResource/watchNotification/SMTPNotifications 1-2333

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDSystemResources/{name}/WLDFResource/watchNotification/SMTPNotifications/{name} 1-2336

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDSystemResources/{name}/WLDFResource/watchNotification/SNMPNotificationCreateForm 1-2340

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDSystemResources/{name}/WLDFResource/watchNotification/SNMPNotifications
1-2342

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDSystemResources/{name}/WLDFResource/watchNotification/SNMPNotifications/{name} 1-2345

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDSystemResources/{name}/WLDFResource/watchNotification/threadDumpActionCreateForm 1-2349

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDSystemResources/{name}/WLDFResource/watchNotification/threadDumpActions
1-2351

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDSystemResources/{name}/WLDFResource/watchNotification/threadDumpActions/{name} 1-2354

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDSystemResources/{name}/WLDFResource/watchNotification/watchCreateForm
1-2358

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDSystemResources/{name}/WLDFResource/watchNotification/watches 1-2360

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDSystemResources/{name}/WLDFResource/watchNotification/watches/{name}
1-2363

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDSystemResources/{name}/WLDFResource/watchNotification/watches/{name}/schedule 1-2367

/management/weblogic/{version}/edit/partitions/{name}/resourceManager 1-2370

/management/weblogic/{version}/edit/partitions/{name}/resourceManager/cpuUtilization 1-2375

/management/weblogic/{version}/edit/partitions/{name}/resourceManager/cpuUtilization/fairShareConstraint 1-2379

/management/weblogic/{version}/edit/partitions/{name}/resourceManager/cpuUtilization/fairShareConstraintCreateForm 1-2383

/management/weblogic/{version}/edit/partitions/{name}/resourceManager/cpuUtilization/triggerCreateForm 1-2385

/management/weblogic/{version}/edit/partitions/{name}/resourceManager/cpuUtilization/triggers 1-2387

/management/weblogic/{version}/edit/partitions/{name}/resourceManager/cpuUtilization/triggers/{name} 1-2390

/management/weblogic/{version}/edit/partitions/{name}/resourceManager/cpuUtilizationCreateForm 1-2394

/management/weblogic/{version}/edit/partitions/{name}/resourceManager/fileOpen... 1-2396

/management/weblogic/{version}/edit/partitions/{name}/resourceManager/fileOpen/triggerCreateForm 1-2400

/management/weblogic/{version}/edit/partitions/{name}/resourceManager/fileOpen/triggers 1-2402

/management/weblogic/{version}/edit/partitions/{name}/resourceManager/fileOpen/triggers/{name} 1-2405

/management/weblogic/{version}/edit/partitions/{name}/resourceManager/fileOpen/createForm 1-2409

/management/weblogic/{version}/edit/partitions/{name}/resourceManager/heapRetained 1-2411

/management/weblogic/{version}/edit/partitions/{name}/resourceManager/heapRetained/fairShareConstraint 1-2415

/management/weblogic/{version}/edit/partitions/{name}/resourceManager/heapRetained/fairShareConstraintCreateForm 1-2419

/management/weblogic/{version}/edit/partitions/{name}/resourceManager/heapRetained/triggerCreateForm 1-2421

/management/weblogic/{version}/edit/partitions/{name}/resourceManager/heapRetained/triggers 1-2423

/management/weblogic/{version}/edit/partitions/{name}/resourceManager/heapRetained/triggers/{name} 1-2426

/management/weblogic/{version}/edit/partitions/{name}/resourceManager/heapRetainedCreateForm 1-2430

/management/weblogic/{version}/edit/partitions/{name}/resourceManager/restartLoopProtection 1-2432

/management/weblogic/{version}/edit/partitions/{name}/resourceManagerCreateForm 1-2435

/management/weblogic/{version}/edit/partitions/{name}/selfTuning 1-2437

/management/weblogic/{version}/edit/partitions/{name}/selfTuning/capacities.....
1-2441

/management/weblogic/{version}/edit/partitions/{name}/selfTuning/capacities/{name
} 1-2444

/management/weblogic/{version}/edit/partitions/{name}/selfTuning/capacityCreateFo
rm 1-2448

/management/weblogic/{version}/edit/partitions/{name}/selfTuning/contextRequestCl
assCreateForm 1-2450

/management/weblogic/{version}/edit/partitions/{name}/selfTuning/contextRequestCl
asses 1-2452

/management/weblogic/{version}/edit/partitions/{name}/selfTuning/contextRequestCl
asses/{name} 1-2455

/management/weblogic/{version}/edit/partitions/{name}/selfTuning/contextRequestCl
asses/{name}/contextCaseCreateForm 1-2459

/management/weblogic/{version}/edit/partitions/{name}/selfTuning/contextRequestCl
asses/{name}/contextCases 1-2461

/management/weblogic/{version}/edit/partitions/{name}/selfTuning/contextRequestCl
asses/{name}/contextCases/{name} 1-2464

/management/weblogic/{version}/edit/partitions/{name}/selfTuning/contextRequestCl
asses/{name}/contextCases/{name}/fairShareRequestClass 1-2468

/management/weblogic/{version}/edit/partitions/{name}/selfTuning/contextRequestCl
asses/{name}/contextCases/{name}/fairShareRequestClassCreateForm 1-2472

/management/weblogic/{version}/edit/partitions/{name}/selfTuning/contextRequestCl
asses/{name}/contextCases/{name}/responseTimeRequestClass 1-2474

/management/weblogic/{version}/edit/partitions/{name}/selfTuning/contextRequestCl
asses/{name}/contextCases/{name}/responseTimeRequestClassCreateForm 1-2478

/management/weblogic/{version}/edit/partitions/{name}/selfTuning/fairShareRequest
ClassCreateForm 1-2480

/management/weblogic/{version}/edit/partitions/{name}/selfTuning/fairShareRequest
Classes 1-2482

/management/weblogic/{version}/edit/partitions/{name}/selfTuning/fairShareRequest
Classes/{name} 1-2485

/management/weblogic/{version}/edit/partitions/{name}/selfTuning/maxThreadsConstraintCreateForm 1-2489

/management/weblogic/{version}/edit/partitions/{name}/selfTuning/maxThreadsConstraints 1-2491

/management/weblogic/{version}/edit/partitions/{name}/selfTuning/maxThreadsConstraints/{name} 1-2494

/management/weblogic/{version}/edit/partitions/{name}/selfTuning/minThreadsConstraintCreateForm 1-2498

/management/weblogic/{version}/edit/partitions/{name}/selfTuning/minThreadsConstraints 1-2500

/management/weblogic/{version}/edit/partitions/{name}/selfTuning/minThreadsConstraints/{name} 1-2503

/management/weblogic/{version}/edit/partitions/{name}/selfTuning/responseTimeRequestClassCreateForm 1-2507

/management/weblogic/{version}/edit/partitions/{name}/selfTuning/responseTimeRequestClasses 1-2509

/management/weblogic/{version}/edit/partitions/{name}/selfTuning/responseTimeRequestClasses/{name} 1-2512

/management/weblogic/{version}/edit/partitions/{name}/selfTuning/workManagerCreateForm 1-2516

/management/weblogic/{version}/edit/partitions/{name}/selfTuning/workManagers... 1-2518

/management/weblogic/{version}/edit/partitions/{name}/selfTuning/workManagers/{name} 1-2521

/management/weblogic/{version}/edit/partitions/{name}/selfTuning/workManagers/{name}/workManagerShutdownTrigger 1-2526

/management/weblogic/{version}/edit/partitions/{name}/selfTuning/workManagers/{name}/workManagerShutdownTriggerCreateForm 1-2530

/management/weblogic/{version}/edit/partitions/{name}/systemFileSystem..... 1-2532

/management/weblogic/{version}/edit/partitions/{name}/userFileSystem 1-2535

/management/weblogic/{version}/edit/partitions/{name}/webService 1-2538

/management/weblogic/{version}/edit/partitions/{name}/webService/webServiceBuffering 1-2541

/management/weblogic/{version}/edit/partitions/{name}/webService/webServiceBuffering/webServiceRequestBufferingQueue 1-2544

/management/weblogic/{version}/edit/partitions/{name}/webService/webServiceBuffering/webServiceResponseBufferingQueue 1-2547

/management/weblogic/{version}/edit/partitions/{name}/webService/webServicePersistence 1-2550

/management/weblogic/{version}/edit/partitions/{name}/webService/webServicePersistence/webServiceLogicalStoreCreateForm 1-2553

/management/weblogic/{version}/edit/partitions/{name}/webService/webServicePersistence/webServiceLogicalStores 1-2555

/management/weblogic/{version}/edit/partitions/{name}/webService/webServicePersistence/webServiceLogicalStores/{name} 1-2558

/management/weblogic/{version}/edit/partitions/{name}/webService/webServicePersistence/webServicePhysicalStoreCreateForm 1-2562

/management/weblogic/{version}/edit/partitions/{name}/webService/webServicePersistence/webServicePhysicalStores 1-2564

/management/weblogic/{version}/edit/partitions/{name}/webService/webServicePersistence/webServicePhysicalStores/{name} 1-2567

/management/weblogic/{version}/edit/partitions/{name}/webService/webServiceReliability 1-2571

/management/weblogic/{version}/edit/partitionWorkManagerCreateForm 1-2574

/management/weblogic/{version}/edit/partitionWorkManagers..... 1-2576

/management/weblogic/{version}/edit/partitionWorkManagers/{name}..... 1-2579

/management/weblogic/{version}/edit/resourceGroupCreateForm..... 1-2583

/management/weblogic/{version}/edit/resourceGroups 1-2585

/management/weblogic/{version}/edit/resourceGroups/{name} 1-2588

/management/weblogic/{version}/edit/resourceGroups/{name}/appDeployments 1-2595

/management/weblogic/{version}/edit/resourceGroups/{name}/appDeployments/{name} 1-2599

/management/weblogic/{version}/edit/resourceGroups/{name}/appDeployments/{name}/createPlan 1-2603

/management/weblogic/{version}/edit/resourceGroups/{name}/appDeployments/{name}/redeploy 1-2605

/management/weblogic/{version}/edit/resourceGroups/{name}/appDeployments/{name}/subDeploymentCreateForm 1-2607

/management/weblogic/{version}/edit/resourceGroups/{name}/appDeployments/{name}/subDeployments 1-2609

/management/weblogic/{version}/edit/resourceGroups/{name}/appDeployments/{name}/subDeployments/{name} 1-2612

/management/weblogic/{version}/edit/resourceGroups/{name}/appDeployments/{name}/subDeployments/{name}/subDeployments 1-2616

/management/weblogic/{version}/edit/resourceGroups/{name}/appDeployments/{name}/subDeployments/{name}/subDeployments/{name} 1-2618

/management/weblogic/{version}/edit/resourceGroups/{name}/appDeployments/{name}/update 1-2621

/management/weblogic/{version}/edit/resourceGroups/{name}/fileStoreCreateForm 1-2623

/management/weblogic/{version}/edit/resourceGroups/{name}/fileStores..... 1-2625

/management/weblogic/{version}/edit/resourceGroups/{name}/fileStores/{name}..... 1-2628

/management/weblogic/{version}/edit/resourceGroups/{name}/findEffectiveTargets 1-2632

/management/weblogic/{version}/edit/resourceGroups/{name}/foreignJNDIProviderCreateForm 1-2634

/management/weblogic/{version}/edit/resourceGroups/{name}/foreignJNDIProviders. 1-2636

/management/weblogic/{version}/edit/resourceGroups/{name}/foreignJNDIProviders/{name} 1-2639

/management/weblogic/{version}/edit/resourceGroups/{name}/foreignJNDIProviders/{name}/foreignJNDILinkCreateForm 1-2643

/management/weblogic/{version}/edit/resourceGroups/{name}/foreignJNDIProviders/{name}/foreignJNDILinks 1-2645

/management/weblogic/{version}/edit/resourceGroups/{name}/foreignJNDIProviders/{name}/foreignJNDILinks/{name} 1-2648

/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCStoreCreateForm 1-2652

/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCStores..... 1-2654

/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCStores/{name}..... 1-2657

/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResource
CreateForm 1-2661

/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources
1-2663

/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources
/{name} 1-2666

/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources
/{name}/JDBCResource 1-2670

/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources
/{name}/JDBCResource/internalProperties 1-2673

/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources
/{name}/JDBCResource/internalProperties/properties 1-2675

/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources
/{name}/JDBCResource/internalProperties/properties/{name} 1-2678

/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources
/{name}/JDBCResource/internalProperties/propertyCreateForm 1-2682

/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources
/{name}/JDBCResource/JDBCConnectionPoolParams 1-2684

/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources
/{name}/JDBCResource/JDBCDataSourceParams 1-2687

/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources
/{name}/JDBCResource/JBCDriverParams 1-2690

/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources
/{name}/JDBCResource/JBCDriverParams/properties 1-2693

/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources
/{name}/JDBCResource/JBCDriverParams/properties/properties 1-2695

/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources
/{name}/JDBCResource/JBCDriverParams/properties/properties/{name} 1-2698

/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources
/{name}/JDBCResource/JBCDriverParams/properties/propertyCreateForm 1-2702

/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources
/{name}/JDBCResource/JBCOracleParams 1-2704

/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources
/{name}/JDBCResource/JDBCXAParams 1-2707

/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources
/{name}/subDeploymentCreateForm 1-2710

/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources
/{name}/subDeployments 1-2712

/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources
/{name}/subDeployments/{name} 1-2715

/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources
/{name}/subDeployments/{name}/subDeployments 1-2719

/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources
/{name}/subDeployments/{name}/subDeployments/{name} 1-2721

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSBridgeDestination
CreateForm 1-2724

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSBridgeDestinations
1-2726

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSBridgeDestinations
/{name} 1-2729

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSServerCreateForm
1-2733

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSServers..... 1-2735

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSServers/{name}.....
1-2738

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSServers/{name}/J
MSMessageLogFile 1-2742

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResourceCr
eateForm 1-2745

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources..
1-2747

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/
{name} 1-2750

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/
{name}/JMSResource 1-2754

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/
{name}/JMSResource/connectionFactories 1-2759

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/
{name}/JMSResource/connectionFactories/{name} 1-2762

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/
{name}/JMSResource/connectionFactories/{name}/clientParams 1-2766

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/
{name}/JMSResource/connectionFactories/{name}/defaultDeliveryParams 1-2769

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/
{name}/JMSResource/connectionFactories/{name}/flowControlParams 1-2772

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/
{name}/JMSResource/connectionFactories/{name}/loadBalancingParams 1-2775

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/
{name}/JMSResource/connectionFactories/{name}/securityParams 1-2778

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/
{name}/JMSResource/connectionFactories/{name}/transactionParams 1-2781

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/
{name}/JMSResource/connectionFactoryCreateForm 1-2784

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/
{name}/JMSResource/destinationKeyCreateForm 1-2786

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/
{name}/JMSResource/destinationKeys 1-2788

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/
{name}/JMSResource/destinationKeys/{name} 1-2791

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/
{name}/JMSResource/foreignServerCreateForm 1-2795

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/
{name}/JMSResource/foreignServers 1-2797

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/
{name}/JMSResource/foreignServers/{name} 1-2800

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/
{name}/JMSResource/foreignServers/{name}/foreignConnectionFactories 1-2805

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/
{name}/JMSResource/foreignServers/{name}/foreignConnectionFactories/{name}
1-2808

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/
{name}/JMSResource/foreignServers/{name}/foreignConnectionFactoryCreateForm
1-2812

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/
{name}/JMSResource/foreignServers/{name}/foreignDestinationCreateForm 1-2814

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/
{name}/JMSResource/foreignServers/{name}/foreignDestinations 1-2816

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/
{name}/JMSResource/foreignServers/{name}/foreignDestinations/{name} 1-2819

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/
{name}/JMSResource/foreignServers/{name}/JNDIProperties 1-2823

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/
{name}/JMSResource/foreignServers/{name}/JNDIProperties/{key} 1-2826

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/
{name}/JMSResource/foreignServers/{name}/JNDIPropertyCreateForm 1-2830

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/
{name}/JMSResource/queueCreateForm 1-2832

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/
{name}/JMSResource/queues 1-2834

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/
{name}/JMSResource/queues/{name} 1-2837

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/
{name}/JMSResource/queues/{name}/deliveryFailureParams 1-2841

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/
{name}/JMSResource/queues/{name}/deliveryFailureParams/findSubDeploymentName
1-2844

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/
{name}/JMSResource/queues/{name}/deliveryParamsOverrides 1-2846

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/
{name}/JMSResource/queues/{name}/messageLoggingParams 1-2849

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/
{name}/JMSResource/queues/{name}/thresholds 1-2852

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/
{name}/JMSResource/quotaCreateForm 1-2855

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/
{name}/JMSResource/quotas 1-2857

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/
{name}/JMSResource/quotas/{name} 1-2860

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/
{name}/JMSResource/SAFErrorHandlingCreateForm 1-2864

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/
{name}/JMSResource/SAFErrorHandlings 1-2866

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/
{name}/JMSResource/SAFErrorHandlings/{name} 1-2869

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/
{name}/JMSResource/SAFImportedDestinationCreateForm 1-2873

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/
{name}/JMSResource/SAFImportedDestinations 1-2875

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/
{name}/JMSResource/SAFImportedDestinations/{name} 1-2878

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/
{name}/JMSResource/SAFImportedDestinations/{name}/messageLoggingParams
1-2883

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/
{name}/JMSResource/SAFImportedDestinations/{name}/SAFQueueCreateForm 1-2886

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/
{name}/JMSResource/SAFImportedDestinations/{name}/SAFQueues 1-2888

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/
{name}/JMSResource/SAFImportedDestinations/{name}/SAFQueues/{name} 1-2891

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/
{name}/JMSResource/SAFImportedDestinations/{name}/SAFQueues/{name}/messageL
oggingParams 1-2895

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/
{name}/JMSResource/SAFImportedDestinations/{name}/SAFTopicCreateForm 1-2898

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/
{name}/JMSResource/SAFImportedDestinations/{name}/SAFTopics 1-2900

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/
{name}/JMSResource/SAFImportedDestinations/{name}/SAFTopics/{name} 1-2903

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/
{name}/JMSResource/SAFImportedDestinations/{name}/SAFTopics/{name}/messageLo
ggingParams 1-2907

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/
{name}/JMSResource/SAFRemoteContextCreateForm 1-2910

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/
{name}/JMSResource/SAFRemoteContexts 1-2912

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/
{name}/JMSResource/SAFRemoteContexts/{name} 1-2915

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/
{name}/JMSResource/SAFRemoteContexts/{name}/SAFLoginContext 1-2919

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/
{name}/JMSResource/templateCreateForm 1-2922

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/
{name}/JMSResource/templates 1-2924

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/
{name}/JMSResource/templates/{name} 1-2927

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/
{name}/JMSResource/templates/{name}/deliveryFailureParams 1-2932

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/
{name}/JMSResource/templates/{name}/deliveryFailureParams/findSubDeploymentNa
me 1-2935

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/
{name}/JMSResource/templates/{name}/deliveryParamsOverrides 1-2937

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/
{name}/JMSResource/templates/{name}/findErrorDestination 1-2940

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/
{name}/JMSResource/templates/{name}/groupParamCreateForm 1-2942

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/
{name}/JMSResource/templates/{name}/groupParams 1-2944

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/
{name}/JMSResource/templates/{name}/groupParams/{subDeploymentName} 1-2947

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/
{name}/JMSResource/templates/{name}/messageLoggingParams 1-2951

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/
{name}/JMSResource/templates/{name}/multicast 1-2954

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/
{name}/JMSResource/templates/{name}/thresholds 1-2957

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/
{name}/JMSResource/templates/{name}/topicSubscriptionParams 1-2960

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/
{name}/JMSResource/topicCreateForm 1-2963

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/
{name}/JMSResource/topics 1-2965

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/
{name}/JMSResource/topics/{name} 1-2968

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/
{name}/JMSResource/topics/{name}/deliveryFailureParams 1-2973

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/
{name}/JMSResource/topics/{name}/deliveryFailureParams/findSubDeploymentName
1-2976

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/
{name}/JMSResource/topics/{name}/deliveryParamsOverrides 1-2978

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/
{name}/JMSResource/topics/{name}/messageLoggingParams 1-2981

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/
{name}/JMSResource/topics/{name}/multicast 1-2984

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/
{name}/JMSResource/topics/{name}/thresholds 1-2987

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/
{name}/JMSResource/topics/{name}/topicSubscriptionParams 1-2990

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/
{name}/JMSResource/uniformDistributedQueueCreateForm 1-2993

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/
{name}/JMSResource/uniformDistributedQueues 1-2995

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/
{name}/JMSResource/uniformDistributedQueues/{name} 1-2998

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/
{name}/JMSResource/uniformDistributedQueues/{name}/deliveryFailureParams
1-3002

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/
{name}/JMSResource/uniformDistributedQueues/{name}/deliveryFailureParams/findSu
bDeploymentName 1-3005

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/
{name}/JMSResource/uniformDistributedQueues/{name}/deliveryParamsOverrides
1-3007

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/
{name}/JMSResource/uniformDistributedQueues/{name}/messageLoggingParams
1-3010

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/
{name}/JMSResource/uniformDistributedQueues/{name}/thresholds 1-3013

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/
{name}/JMSResource/uniformDistributedTopicCreateForm 1-3016

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/
{name}/JMSResource/uniformDistributedTopics 1-3018

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/
{name}/JMSResource/uniformDistributedTopics/{name} 1-3021

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/
{name}/JMSResource/uniformDistributedTopics/{name}/deliveryFailureParams 1-3026

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/
{name}/JMSResource/uniformDistributedTopics/{name}/deliveryFailureParams/findSu
bDeploymentName 1-3029

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/
{name}/JMSResource/uniformDistributedTopics/{name}/deliveryParamsOverrides
1-3031

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/
{name}/JMSResource/uniformDistributedTopics/{name}/messageLoggingParams
1-3034

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/
{name}/JMSResource/uniformDistributedTopics/{name}/multicast 1-3037

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/
{name}/JMSResource/uniformDistributedTopics/{name}/thresholds 1-3040

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/

{name}/JMSResource/uniformDistributedTopics/{name}/topicSubscriptionParams
1-3043

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/
{name}/subDeploymentCreateForm 1-3046

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/
{name}/subDeployments 1-3048

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/
{name}/subDeployments/{name} 1-3051

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/
{name}/subDeployments/{name}/subDeployments 1-3055

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/
{name}/subDeployments/{name}/subDeployments/{name} 1-3057

/management/weblogic/{version}/edit/resourceGroups/{name}/libraries..... 1-3060

/management/weblogic/{version}/edit/resourceGroups/{name}/libraries/{name}.....
1-3063

/management/weblogic/{version}/edit/resourceGroups/{name}/libraries/{name}/creat
ePlan 1-3067

/management/weblogic/{version}/edit/resourceGroups/{name}/libraries/{name}/rede
ploy 1-3069

/management/weblogic/{version}/edit/resourceGroups/{name}/libraries/{name}/subD
eploymentCreateForm 1-3071

/management/weblogic/{version}/edit/resourceGroups/{name}/libraries/{name}/subD
eployments 1-3073

/management/weblogic/{version}/edit/resourceGroups/{name}/libraries/{name}/subD
eployments/{name} 1-3076

/management/weblogic/{version}/edit/resourceGroups/{name}/libraries/{name}/subD
eployments/{name}/subDeployments 1-3080

/management/weblogic/{version}/edit/resourceGroups/{name}/libraries/{name}/subD
eployments/{name}/subDeployments/{name} 1-3082

/management/weblogic/{version}/edit/resourceGroups/{name}/lookupTarget. 1-3085

/management/weblogic/{version}/edit/resourceGroups/{name}/mailSessionCreateFor
m 1-3087

/management/weblogic/{version}/edit/resourceGroups/{name}/mailSessions .. 1-3089

/management/weblogic/{version}/edit/resourceGroups/{name}/mailSessions/{name} ..
1-3092

/management/weblogic/{version}/edit/resourceGroups/{name}/managedExecutorServiceCreateForm 1-3096

/management/weblogic/{version}/edit/resourceGroups/{name}/managedExecutorServices 1-3098

/management/weblogic/{version}/edit/resourceGroups/{name}/managedExecutorServices/{name} 1-3101

/management/weblogic/{version}/edit/resourceGroups/{name}/managedScheduledExecutorServiceCreateForm 1-3105

/management/weblogic/{version}/edit/resourceGroups/{name}/managedScheduledExecutorServices 1-3107

/management/weblogic/{version}/edit/resourceGroups/{name}/managedScheduledExecutorServices/{name} 1-3110

/management/weblogic/{version}/edit/resourceGroups/{name}/managedThreadFactories 1-3114

/management/weblogic/{version}/edit/resourceGroups/{name}/managedThreadFactories/{name} 1-3117

/management/weblogic/{version}/edit/resourceGroups/{name}/managedThreadFactoryCreateForm 1-3121

/management/weblogic/{version}/edit/resourceGroups/{name}/messagingBridgeCreateForm 1-3123

/management/weblogic/{version}/edit/resourceGroups/{name}/messagingBridges..... 1-3125

/management/weblogic/{version}/edit/resourceGroups/{name}/messagingBridges/{name} 1-3128

/management/weblogic/{version}/edit/resourceGroups/{name}/osgiFrameworkCreateForm 1-3132

/management/weblogic/{version}/edit/resourceGroups/{name}/osgiFrameworks 1-3134

/management/weblogic/{version}/edit/resourceGroups/{name}/osgiFrameworks/{name} 1-3137

/management/weblogic/{version}/edit/resourceGroups/{name}/SAFAgentCreateForm. 1-3141

/management/weblogic/{version}/edit/resourceGroups/{name}/SAFAGents..... 1-3143

/management/weblogic/{version}/edit/resourceGroups/{name}/SAFAGents/{name} 1-3146

/management/weblogic/{version}/edit/resourceGroups/{name}/SAFAgents/{name}/JMSSAFMessageLogFile 1-3150

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/CreateForm 1-3153

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources 1-3155

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name} 1-3158

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/subDeploymentCreateForm 1-3162

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/subDeployments 1-3164

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/subDeployments/{name} 1-3167

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/subDeployments/{name}/subDeployments 1-3171

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/subDeployments/{name}/subDeployments/{name} 1-3173

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource 1-3176

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/harvester 1-3178

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/harvester/harvestedTypeCreateForm 1-3181

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/harvester/harvestedTypes 1-3183

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/harvester/harvestedTypes/{name} 1-3186

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/instrumentation 1-3190

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/instrumentation/WLDFInstrumentationMonitorCreateForm 1-3193

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/instrumentation/WLDFInstrumentationMonitors 1-3195

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/instrumentation/WLDFInstrumentationMonitors/{name} 1-3198

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification 1-3202

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actionCreateForm 1-3208

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions 1-3210

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name} 1-3213

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/arrayProperties 1-3218

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/arrayProperties/{name} 1-3221

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/arrayPropertyCreateForm 1-3225

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/configurationProperties 1-3227

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/configurationProperties/{name} 1-3229

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/encryptedProperties 1-3231

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/encryptedProperties/{name} 1-3234

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/encryptedPropertyCreateForm 1-3238

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties 1-3240

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name} 1-3243

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/configurationProperties 1-3246

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/configurationProperties/{name} 1-3248

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/encryptedProperties 1-3250

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/encryptedProperties/{name} 1-3253

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/encryptedPropertyCreateForm 1-3257

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/properties 1-3259

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/properties/{name} 1-3262

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/propertyCreateForm 1-3266

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapPropertyCreateForm 1-3268

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/properties 1-3270

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/properties/{name} 1-3273

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/propertycreateForm 1-3277

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/heapDumpActioncreateForm 1-3279

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/heapDumpActions 1-3281

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/heapDumpActions/{name} 1-3284

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/imageNotificationcreateForm 1-3288

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/imageNotifications 1-3290

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/imageNotifications/{name} 1-3293

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMSNotificationcreateForm 1-3297

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMSNotifications 1-3299

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMSNotifications/{name} 1-3302

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMXNotificationcreateForm 1-3306

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMXNotifications 1-3308

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMXNotifications/{name} 1-3311

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/logActioncreateForm 1-3315

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/logActions 1-3317

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/logActions/{name} 1-3320

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/lookupActions 1-3324

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/lookupNotification 1-3326

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/RESTNotificationCreateForm 1-3328

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/RESTNotifications 1-3330

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/RESTNotifications/{name} 1-3333

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleDownActionCreateForm 1-3337

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleDownActions 1-3339

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleDownActions/{name} 1-3342

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleUpActionCreateForm 1-3346

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleUpActions 1-3348

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleUpActions/{name} 1-3351

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scriptActionCreateForm 1-3355

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scriptActions 1-3357

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scriptActions/{name} 1-3360

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/SMTPNotificationCreateForm 1-3364

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/SMTPNotifications 1-3366

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/SMTPNotifications/{name} 1-3369

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/SNMPNotificationCreateForm 1-3373

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/SNMPNotifications 1-3375

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/SNMPNotifications/{name} 1-3378

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/threadDumpActionCreateForm 1-3382

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/threadDumpActions 1-3384

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/threadDumpActions/{name} 1-3387

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/watchCreateForm 1-3391

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/watches 1-3393

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/watches/{name} 1-3396

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/watches/{name}/schedule 1-3400

/management/weblogic/{version}/edit/resourceGroupTemplateCreateForm 1-3403

/management/weblogic/{version}/edit/resourceGroupTemplates..... 1-3405

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}..... 1-3408

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/appDeployments 1-3414

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/appDeployments/{name} 1-3418

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/appDeployments/{name}/createPlan 1-3422

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/appDeployments/{name}/redeploy 1-3424

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/appDeployments/{name}/subDeploymentCreateForm 1-3426

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/appDeployments/{name}/subDeployments 1-3428

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/appDeployments/{name}/subDeployments/{name} 1-3431

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/appDeployments/{name}/subDeployments/{name}/subDeployments 1-3435

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/appDeployments/{name}/subDeployments/{name}/subDeployments/{name} 1-3437

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/appDeployments/{name}/update 1-3440

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/fileStoreCreateForm 1-3442

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/fileStores..... 1-3444

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/fileStores/{name} 1-3447

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/foreignJNDIProviderCreateForm 1-3451

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/foreignJNDIProviders 1-3453

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/foreignJNDIProviders/{name} 1-3456

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/foreignJNDIProviders/{name}/foreignJNDILinkCreateForm 1-3460

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/foreignJNDIProviders/{name}/foreignJNDILinks 1-3462

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/foreignJNDIProviders/{name}/foreignJNDILinks/{name} 1-3465

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCStoreCreateForm 1-3469

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCStores... 1-3471

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCStores/{name} 1-3474

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResourceCreateForm 1-3478

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources 1-3480

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources/{name} 1-3483

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources/{name}/JDBCResource 1-3487

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources/{name}/JDBCResource/internalProperties 1-3490

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources/{name}/JDBCResource/internalProperties/properties 1-3492

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources/{name}/JDBCResource/internalProperties/properties/{name} 1-3495

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources/{name}/JDBCResource/internalProperties/propertyCreateForm 1-3499

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources/{name}/JDBCResource/JDBCConnectionPoolParams 1-3501

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources/{name}/JDBCResource/JDBCDataSourceParams 1-3504

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources/{name}/JDBCResource/JDBCdriverParams 1-3507

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources/{name}/JDBCResource/JDBCdriverParams/properties 1-3510

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources/{name}/JDBCResource/JDBCdriverParams/properties/properties 1-3512

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources/{name}/JDBCResource/JDBCdriverParams/properties/properties/{name} 1-3515

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources/{name}/JDBCResource/JDBCdriverParams/properties/propertyCreateForm 1-3519

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources/{name}/JDBCResource/JDBCOracleParams 1-3521

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources/{name}/JDBCResource/JDBCXAParams 1-3524

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources/{name}/subDeploymentCreateForm 1-3527

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources/{name}/subDeployments 1-3529

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources/{name}/subDeployments/{name} 1-3532

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources/{name}/subDeployments/{name}/subDeployments 1-3536

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources/{name}/subDeployments/{name}/subDeployments/{name} 1-3538

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSBridgeDestinationCreateForm 1-3541

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSBridgeDestinations 1-3543

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSBridgeDestinations/{name} 1-3546

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSServerCreateForm 1-3550

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSServers... 1-3552

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSServers/{name} 1-3555

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSServers/{name}/JMSMessageLogFile 1-3559

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResourceCreateForm 1-3562

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources 1-3564

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name} 1-3567

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource 1-3571

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories 1-3576

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories/{name} 1-3579

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}/clientParams 1-3584

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}/defaultDeliveryParams 1-3587

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}/flowControlParams 1-3590

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}/loadBalancingParams 1-3593

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}/securityParams 1-3596

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}/transactionParams 1-3599

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/connectionFactoryCreateForm 1-3602

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/destinationKeyCreateForm 1-3604

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/destinationKeys 1-3606

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/destinationKeys/{name} 1-3609

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/foreignServerCreateForm 1-3613

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/foreignServers 1-3615

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name} 1-3618

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignConnectionFactories 1-3623

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignConnectionFactories/{name} 1-3626

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignConnectionFactoryCreateForm 1-3630

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignDestinationCreateForm 1-3632

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignDestinations 1-3634

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignDestinations/{name} 1-3637

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/JNDIProperties 1-3641

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/JNDIProperties/{key} 1-3644

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/JNDIPropertyCreateForm 1-3648

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/queueCreateForm 1-3650

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/queues 1-3652

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/queues/{name} 1-3655

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/queues/{name}/deliveryFailureParams 1-3659

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemRe

`sources/{name}/JMSResource/queues/{name}/deliveryFailureParams/findSubDeploymentName` 1-3662

`/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/queues/{name}/deliveryParamsOverrides` 1-3664

`/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/queues/{name}/messageLoggingParams` 1-3667

`/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/queues/{name}/thresholds` 1-3670

`/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/quotaCreateForm` 1-3673

`/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/quotas` 1-3675

`/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/quotas/{name}` 1-3678

`/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/SAFErrorHandlingCreateForm` 1-3682

`/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/SAFErrorHandlings` 1-3684

`/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/SAFErrorHandlings/{name}` 1-3687

`/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinationCreateForm` 1-3691

`/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations` 1-3693

`/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}` 1-3696

`/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/messageLoggingParams` 1-3701

`/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFQueueCreateForm` 1-3704

`/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFQueues` 1-3706

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFQueues/{name} 1-3709

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFQueues/{name}/messageLoggingParams 1-3713

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFTopicCreateForm 1-3716

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFTopics 1-3718

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFTopics/{name} 1-3721

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFTopics/{name}/messageLoggingParams 1-3725

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/SAFRemoteContextCreateForm 1-3728

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/SAFRemoteContexts 1-3730

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/SAFRemoteContexts/{name} 1-3733

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/SAFRemoteContexts/{name}/SAFLoginContext 1-3737

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/templateCreateForm 1-3740

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/templates 1-3742

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/templates/{name} 1-3745

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/deliveryFailureParams 1-3750

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemRe

`sources/{name}/JMSResource/templates/{name}/deliveryFailureParams/findSubDeploymentName` 1-3753

`/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/deliveryParamsOverrides` 1-3755

`/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/findErrorDestination` 1-3758

`/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/groupParamCreateForm` 1-3760

`/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/groupParams` 1-3762

`/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/groupParams/{subDeploymentName}` 1-3765

`/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/messageLoggingParams` 1-3769

`/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/multicast` 1-3772

`/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/thresholds` 1-3775

`/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/topicSubscriptionParams` 1-3778

`/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/topicCreateForm` 1-3781

`/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/topics` 1-3783

`/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/topics/{name}` 1-3786

`/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/topics/{name}/deliveryFailureParams` 1-3791

`/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/topics/{name}/deliveryFailureParams/findSubDeploymentName` 1-3794

`/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/topics/{name}/deliveryParamsOverrides` 1-3796

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/topics/{name}/messageLoggingParams 1-3799

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/topics/{name}/multicast 1-3802

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/topics/{name}/thresholds 1-3805

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/topics/{name}/topicSubscriptionParams 1-3808

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedQueueCreateForm 1-3811

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues 1-3813

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues/{name} 1-3816

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues/{name}/deliveryFailureParams 1-3820

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues/{name}/deliveryFailureParams/findSubDeploymentName 1-3823

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues/{name}/deliveryParamsOverrides 1-3825

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues/{name}/messageLoggingParams 1-3828

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues/{name}/thresholds 1-3831

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopicCreateForm 1-3834

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics 1-3836

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name} 1-3839

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}/deliveryFailureParams 1-3844

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}/deliveryFailureParams/findSubDeploymentName 1-3847

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}/deliveryParamsOverrides 1-3849

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}/messageLoggingParams 1-3852

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}/multicast 1-3855

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}/thresholds 1-3858

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}/topicSubscriptionParams 1-3861

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/subDeploymentCreateForm 1-3864

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/subDeployments 1-3866

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/subDeployments/{name} 1-3869

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/subDeployments/{name}/subDeployments 1-3873

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/subDeployments/{name}/subDeployments/{name} 1-3875

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/libraries..... 1-3878

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/libraries/{name} 1-3881

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/libraries/{name}/createPlan 1-3885

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/libraries/{name}/redeploy 1-3887

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/libraries/{name}/subDeploymentCreateForm 1-3889

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/libraries/{name}/subDeployments 1-3891

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/libraries/{name}/subDeployments/{name} 1-3894

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/libraries/{name}/subDeployments/{name}/subDeployments 1-3898

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/libraries/{name}/subDeployments/{name}/subDeployments/{name} 1-3900

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/mailSessionCreateForm 1-3903

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/mailSessions. 1-3905

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/mailSessions/{name} 1-3908

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/managedExecutorServiceCreateForm 1-3912

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/managedExecutorServices 1-3914

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/managedExecutorServices/{name} 1-3917

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/managedScheduledExecutorServiceCreateForm 1-3921

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/managedScheduledExecutorServices 1-3923

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/managedScheduledExecutorServices/{name} 1-3926

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/managedThreadFactories 1-3930

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/managedThreadFactories/{name} 1-3933

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/managedThreadFactoryCreateForm 1-3937

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/messagingBridgeCreateForm 1-3939

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/messagingBridges 1-3941

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/messagingBridges/{name} 1-3944

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/osgiFrameworkCreateForm 1-3948

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/osgiFrameworks 1-3950

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/osgiFrameworks/{name} 1-3953

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/SAFAgentCreateForm 1-3957

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/SAFAgents ... 1-3959

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/SAFAgents/{name} 1-3962

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/SAFAgents/{name}/JMSSAFMessageLogFile 1-3966

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResourceCreateForm 1-3969

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources 1-3971

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name} 1-3974

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/subDeploymentCreateForm 1-3978

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/subDeployments 1-3980

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/subDeployments/{name} 1-3983

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/subDeployments/{name}/subDeployments 1-3987

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/subDeployments/{name}/subDeployments/{name} 1-3989

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource 1-3992

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/harvester 1-3994

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/harvester/harvestedTypeCreateForm 1-3997

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/harvester/harvestedTypes 1-3999

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/harvester/harvestedTypes/{name} 1-4002

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/instrumentation 1-4006

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/instrumentation/WLDFInstrumentationMonitorCreateForm 1-4009

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/instrumentation/WLDFInstrumentationMonitors 1-4011

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/instrumentation/WLDFInstrumentationMonitors/{name} 1-4014

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification 1-4018

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actionCreateForm 1-4024

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions 1-4026

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name} 1-4029

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/arrayProperties 1-4034

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/arrayProperties/{name} 1-4037

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/arrayPropertyCreateForm 1-4041

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/configurationProperties 1-4043

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/configurationProperties/{name} 1-4045

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/encryptedProperties 1-4047

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/encryptedProperties/{name} 1-4050

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/encryptedPropertyCreateForm 1-4054

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties 1-4056

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name} 1-4059

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/configurationProperties 1-4062

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/configurationProperties/{name} 1-4064

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/encryptedProperties 1-4066

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/encryptedProperties/{name} 1-4069

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/encryptedPropertyCreateForm 1-4073

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/properties 1-4075

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/properties/{name} 1-4078

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/propertyCreateForm 1-4082

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapPropertyCreateForm 1-4084

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/properties 1-4086

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/properties/{name} 1-4089

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/propertyCreateForm 1-4093

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/heapDumpActionCreateForm 1-4095

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/heapDumpActions 1-4097

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/heapDumpActions/{name} 1-4100

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/imageNotificationCreateForm
1-4104

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/imageNotifications 1-4106

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/imageNotifications/{name}
1-4109

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMSNotificationCreateForm
1-4113

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMSNotifications 1-4115

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMSNotifications/{name} 1-4118

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMXNotificationCreateForm
1-4122

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMXNotifications 1-4124

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMXNotifications/{name}
1-4127

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/logActionCreateForm 1-4131

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/logActions 1-4133

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/logActions/{name} 1-4136

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/lookupActions 1-4140

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/lookupNotification 1-4142

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/RESTNotificationCreateForm
1-4144

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/RESTNotifications 1-4146

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/RESTNotifications/{name} 1-4149

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleDownActionCreateForm 1-4153

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleDownActions 1-4155

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleDownActions/{name} 1-4158

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleUpActionCreateForm 1-4162

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleUpActions 1-4164

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleUpActions/{name} 1-4167

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scriptActionCreateForm 1-4171

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scriptActions 1-4173

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scriptActions/{name} 1-4176

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/SMTPNotificationCreateForm 1-4180

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/SMTPNotifications 1-4182

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/SMTPNotifications/{name} 1-4185

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystem

Resources/{name}/WLDResource/watchNotification/SNMPNotificationCreateForm
1-4189

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDSystem
Resources/{name}/WLDResource/watchNotification/SNMPNotifications 1-4191

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDSystem
Resources/{name}/WLDResource/watchNotification/SNMPNotifications/{name}
1-4194

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDSystem
Resources/{name}/WLDResource/watchNotification/threadDumpActionCreateForm
1-4198

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDSystem
Resources/{name}/WLDResource/watchNotification/threadDumpActions 1-4200

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDSystem
Resources/{name}/WLDResource/watchNotification/threadDumpActions/{name}
1-4203

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDSystem
Resources/{name}/WLDResource/watchNotification/watchCreateForm 1-4207

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDSystem
Resources/{name}/WLDResource/watchNotification/watches 1-4209

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDSystem
Resources/{name}/WLDResource/watchNotification/watches/{name} 1-4212

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDSystem
Resources/{name}/WLDResource/watchNotification/watches/{name}/schedule
1-4216

/management/weblogic/{version}/edit/resourceManagement 1-4219

/management/weblogic/{version}/edit/resourceManagement/resourceManagerCreateF
orm 1-4222

/management/weblogic/{version}/edit/resourceManagement/resourceManagers
1-4224

/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name
} 1-4227

/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name
}/cpuUtilization 1-4231

/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name
}/cpuUtilization/fairShareConstraint 1-4235

/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/cpuUtilization/fairShareConstraintCreateForm 1-4239

/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/cpuUtilization/triggerCreateForm 1-4241

/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/cpuUtilization/triggers 1-4243

/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/cpuUtilization/triggers/{name} 1-4246

/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/cpuUtilizationCreateForm 1-4250

/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/fileOpen 1-4252

/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/fileOpen/triggerCreateForm 1-4256

/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/fileOpen/triggers 1-4258

/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/fileOpen/triggers/{name} 1-4261

/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/fileOpenCreateForm 1-4265

/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/heapRetained 1-4267

/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/heapRetained/fairShareConstraint 1-4271

/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/heapRetained/fairShareConstraintCreateForm 1-4275

/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/heapRetained/triggerCreateForm 1-4277

/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/heapRetained/triggers 1-4279

/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/heapRetained/triggers/{name} 1-4282

/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/heapRetainedCreateForm 1-4286

/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/restartLoopProtection 1-4288

/management/weblogic/{version}/edit/restfulManagementServices..... 1-4291

/management/weblogic/{version}/edit/SAFAgentCreateForm 1-4294

/management/weblogic/{version}/edit/SAFAGents..... 1-4296

/management/weblogic/{version}/edit/SAFAGents/{name}..... 1-4299

/management/weblogic/{version}/edit/SAFAGents/{name}/JMSSAFMessageLogFile 1-4303

/management/weblogic/{version}/edit/search 1-4306

/management/weblogic/{version}/edit/securityConfiguration..... 1-4308

/management/weblogic/{version}/edit/securityConfiguration/certRevoc..... 1-4311

/management/weblogic/{version}/edit/securityConfiguration/certRevoc/certRevocCaCreateForm 1-4314

/management/weblogic/{version}/edit/securityConfiguration/certRevoc/certRevocCas 1-4316

/management/weblogic/{version}/edit/securityConfiguration/certRevoc/certRevocCas/{name} 1-4319

/management/weblogic/{version}/edit/securityConfiguration/JASPIC..... 1-4323

/management/weblogic/{version}/edit/securityConfiguration/JASPIC/authConfigProviderCreateForm 1-4326

/management/weblogic/{version}/edit/securityConfiguration/JASPIC/authConfigProviders 1-4328

/management/weblogic/{version}/edit/securityConfiguration/JASPIC/authConfigProviders/{name} 1-4331

/management/weblogic/{version}/edit/securityConfiguration/realmCreateForm..... 1-4335

/management/weblogic/{version}/edit/securityConfiguration/realms 1-4337

/management/weblogic/{version}/edit/securityConfiguration/realms/{name} .. 1-4340

/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/adjudicator 1-4345

/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/adjudicatorCreateForm 1-4348

/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/auditorCreateForm 1-4350

/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/auditors 1-4352

/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/auditors/{name} 1-4355

/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/authenticationProviderCreateForm 1-4358

/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/authenticationProviders 1-4360

/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/authenticationProviders/{name} 1-4363

/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/authorizerCreateForm 1-4366

/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/authorizers 1-4368

/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/authorizers/{name} 1-4371

/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/certPathProviderCreateForm 1-4374

/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/certPathProviders 1-4376

/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/certPathProviders/{name} 1-4379

/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/credentialMapperCreateForm 1-4382

/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/credentialMappers 1-4384

/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/credentialMappers/{name} 1-4387

/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/passwordValidatorCreateForm 1-4390

/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/passwordValidators 1-4392

/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/passwordValidators/{name} 1-4395

/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/RDBMSSecurityStore 1-4398

/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/RDBMSSecurityStoreCreateForm 1-4404

/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/roleMapperCreateForm 1-4407

/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/roleMappers 1-4409

/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/roleMappers/{name} 1-4412

/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/userLogoutManager 1-4415

/management/weblogic/{version}/edit/securityConfiguration/secureMode..... 1-4418

/management/weblogic/{version}/edit/selfTuning..... 1-4421

/management/weblogic/{version}/edit/selfTuning/capacities 1-4425

/management/weblogic/{version}/edit/selfTuning/capacities/{name} 1-4428

/management/weblogic/{version}/edit/selfTuning/capacityCreateForm..... 1-4432

/management/weblogic/{version}/edit/selfTuning/contextRequestClassCreateForm..... 1-4434

/management/weblogic/{version}/edit/selfTuning/contextRequestClasses 1-4436

/management/weblogic/{version}/edit/selfTuning/contextRequestClasses/{name} 1-4439

/management/weblogic/{version}/edit/selfTuning/contextRequestClasses/{name}/contextCaseCreateForm 1-4443

/management/weblogic/{version}/edit/selfTuning/contextRequestClasses/{name}/contextCases 1-4445

/management/weblogic/{version}/edit/selfTuning/contextRequestClasses/{name}/contextCases/{name} 1-4448

/management/weblogic/{version}/edit/selfTuning/contextRequestClasses/{name}/contextCases/{name}/fairShareRequestClass 1-4452

/management/weblogic/{version}/edit/selfTuning/contextRequestClasses/{name}/contextCases/{name}/fairShareRequestClassCreateForm 1-4456

/management/weblogic/{version}/edit/selfTuning/contextRequestClasses/{name}/contextCases/{name}/responseTimeRequestClass 1-4458

/management/weblogic/{version}/edit/selfTuning/contextRequestClasses/{name}/contextCases/{name}/responseTimeRequestClassCreateForm 1-4462

/management/weblogic/{version}/edit/selfTuning/fairShareRequestClassCreateForm...
 1-4464
 /management/weblogic/{version}/edit/selfTuning/fairShareRequestClasses 1-4466
 /management/weblogic/{version}/edit/selfTuning/fairShareRequestClasses/{name}
 1-4469
 /management/weblogic/{version}/edit/selfTuning/maxThreadsConstraintCreateForm ..
 1-4473
 /management/weblogic/{version}/edit/selfTuning/maxThreadsConstraints 1-4475
 /management/weblogic/{version}/edit/selfTuning/maxThreadsConstraints/{name}
 1-4478
 /management/weblogic/{version}/edit/selfTuning/minThreadsConstraintCreateForm ...
 1-4482
 /management/weblogic/{version}/edit/selfTuning/minThreadsConstraints 1-4484
 /management/weblogic/{version}/edit/selfTuning/minThreadsConstraints/{name}
 1-4487

 /management/weblogic/{version}/edit/selfTuning/responseTimeRequestClassCreateFo
 rm 1-4491
 /management/weblogic/{version}/edit/selfTuning/responseTimeRequestClasses
 1-4493

 /management/weblogic/{version}/edit/selfTuning/responseTimeRequestClasses/{name
 } 1-4496
 /management/weblogic/{version}/edit/selfTuning/workManagerCreateForm ... 1-4500
 /management/weblogic/{version}/edit/selfTuning/workManagers 1-4502
 /management/weblogic/{version}/edit/selfTuning/workManagers/{name} 1-4505

 /management/weblogic/{version}/edit/selfTuning/workManagers/{name}/workMana
 gerShutdownTrigger 1-4510

 /management/weblogic/{version}/edit/selfTuning/workManagers/{name}/workMana
 gerShutdownTriggerCreateForm 1-4514
 /management/weblogic/{version}/edit/serverCreateForm..... 1-4516
 /management/weblogic/{version}/edit/servers 1-4521
 /management/weblogic/{version}/edit/servers/{name} 1-4525
 /management/weblogic/{version}/edit/servers/{name}/coherenceMemberConfig
 1-4532
 /management/weblogic/{version}/edit/servers/{name}/configurationProperties.....
 1-4535
 /management/weblogic/{version}/edit/servers/{name}/configurationProperties/{name}
 1-4538

 /management/weblogic/{version}/edit/servers/{name}/configurationPropertyCreateFo
 rm 1-4542
 /management/weblogic/{version}/edit/servers/{name}/dataSource 1-4544

/management/weblogic/{version}/edit/servers/{name}/dataSource/dataSourceLogFile.
 1-4547

/management/weblogic/{version}/edit/servers/{name}/defaultFileStore..... 1-4550
 /management/weblogic/{version}/edit/servers/{name}/executeQueues..... 1-4553
 /management/weblogic/{version}/edit/servers/{name}/executeQueues/{name} 1-4555
 /management/weblogic/{version}/edit/servers/{name}/federationServices 1-4558
 /management/weblogic/{version}/edit/servers/{name}/IIOP 1-4561
 /management/weblogic/{version}/edit/servers/{name}/JTAMigratableTarget... 1-4564
 /management/weblogic/{version}/edit/servers/{name}/log 1-4567

/management/weblogic/{version}/edit/servers/{name}/networkAccessPointCreateForm 1-4570
 /management/weblogic/{version}/edit/servers/{name}/networkAccessPoints... 1-4572
 /management/weblogic/{version}/edit/servers/{name}/networkAccessPoints/{name}...
 1-4575
 /management/weblogic/{version}/edit/servers/{name}/overloadProtection..... 1-4579

/management/weblogic/{version}/edit/servers/{name}/overloadProtection/serverFailureTrigger 1-4582

/management/weblogic/{version}/edit/servers/{name}/overloadProtection/serverFailureTriggerCreateForm 1-4586
 /management/weblogic/{version}/edit/servers/{name}/serverDebug..... 1-4588

/management/weblogic/{version}/edit/servers/{name}/serverDebug/debugScopeCreateForm 1-4591
 /management/weblogic/{version}/edit/servers/{name}/serverDebug/debugScopes
 1-4593

/management/weblogic/{version}/edit/servers/{name}/serverDebug/debugScopes/{name} 1-4596
 /management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig.....
 1-4600

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/lookupWLDFDataRetirement 1-4603

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean 1-4605

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/harvester 1-4607

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/harvester/harvestedTypeCreateForm 1-4610

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/harvester/harvestedTypes 1-4612

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDF
BuiltinSystemResourceDescriptorBean/harvester/harvestedTypes/{name} 1-4615

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDF
BuiltinSystemResourceDescriptorBean/instrumentation 1-4619

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDF
BuiltinSystemResourceDescriptorBean/instrumentation/WLDFInstrumentationMonitorC
reateForm 1-4622

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDF
BuiltinSystemResourceDescriptorBean/instrumentation/WLDFInstrumentationMonitors
1-4624

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDF
BuiltinSystemResourceDescriptorBean/instrumentation/WLDFInstrumentationMonitors/
{name} 1-4627

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDF
BuiltinSystemResourceDescriptorBean/watchNotification 1-4631

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDF
BuiltinSystemResourceDescriptorBean/watchNotification/actionCreateForm 1-4637

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDF
BuiltinSystemResourceDescriptorBean/watchNotification/actions 1-4639

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDF
BuiltinSystemResourceDescriptorBean/watchNotification/actions/{name} 1-4642

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDF
BuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/arrayPropertie
s 1-4647

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDF
BuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/arrayPropertie
s/{name} 1-4650

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDF
BuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/arrayProperty
CreateForm 1-4654

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDF
BuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/configuration
Properties 1-4656

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDF
BuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/configuration
Properties/{name} 1-4658

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDF
BuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/encryptedPro
perties 1-4660

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDF
BuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/encryptedPro
perties/{name} 1-4663

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDF
BuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/encryptedPro
pertyCreateForm 1-4667

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDF
BuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapPropertie
s 1-4669

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDF
BuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapPropertie
s/{name} 1-4672

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDF
BuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapPropertie
s/{name}/configurationProperties 1-4675

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDF
BuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapPropertie
s/{name}/configurationProperties/{name} 1-4677

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDF
BuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapPropertie
s/{name}/encryptedProperties 1-4679

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDF
BuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapPropertie
s/{name}/encryptedProperties/{name} 1-4682

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDF
BuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapPropertie
s/{name}/encryptedPropertyCreateForm 1-4686

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDF
BuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapPropertie
s/{name}/properties 1-4688

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDF
BuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapPropertie
s/{name}/properties/{name} 1-4691

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDF

BuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapProperties/{name}/propertyCreateForm 1-4695

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDF BuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapPropertyCreateForm 1-4697

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDF BuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/properties 1-4699

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDF BuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/properties/{name} 1-4702

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDF BuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/propertyCreateForm 1-4706

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDF BuiltinSystemResourceDescriptorBean/watchNotification/heapDumpActionCreateForm 1-4708

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDF BuiltinSystemResourceDescriptorBean/watchNotification/heapDumpActions 1-4710

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDF BuiltinSystemResourceDescriptorBean/watchNotification/heapDumpActions/{name} 1-4713

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDF BuiltinSystemResourceDescriptorBean/watchNotification/imageNotificationCreateForm 1-4717

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDF BuiltinSystemResourceDescriptorBean/watchNotification/imageNotifications 1-4719

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDF BuiltinSystemResourceDescriptorBean/watchNotification/imageNotifications/{name} 1-4722

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDF BuiltinSystemResourceDescriptorBean/watchNotification/JMSNotificationCreateForm 1-4726

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDF BuiltinSystemResourceDescriptorBean/watchNotification/JMSNotifications 1-4728

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDF

BuiltinSystemResourceDescriptorBean/watchNotification/JMSNotifications/{name}
1-4731

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDF
BuiltinSystemResourceDescriptorBean/watchNotification/JMXNotificationCreateForm
1-4735

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDF
BuiltinSystemResourceDescriptorBean/watchNotification/JMXNotifications 1-4737

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDF
BuiltinSystemResourceDescriptorBean/watchNotification/JMXNotifications/{name}
1-4740

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDF
BuiltinSystemResourceDescriptorBean/watchNotification/logActionCreateForm 1-4744

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDF
BuiltinSystemResourceDescriptorBean/watchNotification/logActions 1-4746

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDF
BuiltinSystemResourceDescriptorBean/watchNotification/logActions/{name} 1-4749

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDF
BuiltinSystemResourceDescriptorBean/watchNotification/lookupActions 1-4753

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDF
BuiltinSystemResourceDescriptorBean/watchNotification/lookupNotification 1-4755

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDF
BuiltinSystemResourceDescriptorBean/watchNotification/RESTNotificationCreateForm
1-4757

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDF
BuiltinSystemResourceDescriptorBean/watchNotification/RESTNotifications 1-4759

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDF
BuiltinSystemResourceDescriptorBean/watchNotification/RESTNotifications/{name}
1-4762

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDF
BuiltinSystemResourceDescriptorBean/watchNotification/scaleDownActionCreateForm
1-4766

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDF
BuiltinSystemResourceDescriptorBean/watchNotification/scaleDownActions 1-4768

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDF
BuiltinSystemResourceDescriptorBean/watchNotification/scaleDownActions/{name}
1-4771

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDF
BuiltinSystemResourceDescriptorBean/watchNotification/scaleUpActionCreateForm
1-4775

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDF
BuiltinSystemResourceDescriptorBean/watchNotification/scaleUpActions 1-4777

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDF
BuiltinSystemResourceDescriptorBean/watchNotification/scaleUpActions/{name}
1-4780

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDF
BuiltinSystemResourceDescriptorBean/watchNotification/scriptActionCreateForm
1-4784

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDF
BuiltinSystemResourceDescriptorBean/watchNotification/scriptActions 1-4786

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDF
BuiltinSystemResourceDescriptorBean/watchNotification/scriptActions/{name} 1-4789

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDF
BuiltinSystemResourceDescriptorBean/watchNotification/SMPNotificationCreateForm
1-4793

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDF
BuiltinSystemResourceDescriptorBean/watchNotification/SMPNotifications 1-4795

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDF
BuiltinSystemResourceDescriptorBean/watchNotification/SMPNotifications/{name}
1-4798

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDF
BuiltinSystemResourceDescriptorBean/watchNotification/SNMPNotificationCreateForm
1-4802

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDF
BuiltinSystemResourceDescriptorBean/watchNotification/SNMPNotifications 1-4804

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDF
BuiltinSystemResourceDescriptorBean/watchNotification/SNMPNotifications/{name}
1-4807

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDF
BuiltinSystemResourceDescriptorBean/watchNotification/threadDumpActionCreateForm
1-4811

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDF
BuiltinSystemResourceDescriptorBean/watchNotification/threadDumpActions 1-4813

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDF
BuiltinSystemResourceDescriptorBean/watchNotification/threadDumpActions/{name}
1-4816

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDF
BuiltinSystemResourceDescriptorBean/watchNotification/watchCreateForm 1-4820

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDF
BuiltinSystemResourceDescriptorBean/watchNotification/watches 1-4822

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDF
BuiltinSystemResourceDescriptorBean/watchNotification/watches/{name} 1-4825

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDF
BuiltinSystemResourceDescriptorBean/watchNotification/watches/{name}/schedule
1-4829

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDF
DataRetirementByAgeCreateForm 1-4832

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDF
DataRetirementByAges 1-4834

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDF
DataRetirementByAges/{name} 1-4837

/management/weblogic/{version}/edit/servers/{name}/serverStart..... 1-4841

/management/weblogic/{version}/edit/servers/{name}/singleSignOnServices... 1-4844

/management/weblogic/{version}/edit/servers/{name}/SSL 1-4847

/management/weblogic/{version}/edit/servers/{name}/transactionLogJDBCStore
1-4851

/management/weblogic/{version}/edit/servers/{name}/webServer 1-4854

/management/weblogic/{version}/edit/servers/{name}/webServer/webServerLog.....
1-4857

/management/weblogic/{version}/edit/servers/{name}/webService..... 1-4860

/management/weblogic/{version}/edit/servers/{name}/webService/webServiceBufferi
ng 1-4863

/management/weblogic/{version}/edit/servers/{name}/webService/webServiceBufferi
ng/webServiceRequestBufferingQueue 1-4866

/management/weblogic/{version}/edit/servers/{name}/webService/webServiceBufferi
ng/webServiceResponseBufferingQueue 1-4869

/management/weblogic/{version}/edit/servers/{name}/webService/webServicePersiste
nce 1-4872

/management/weblogic/{version}/edit/servers/{name}/webService/webServicePersistence/webServiceLogicalStoreCreateForm 1-4875

/management/weblogic/{version}/edit/servers/{name}/webService/webServicePersistence/webServiceLogicalStores 1-4877

/management/weblogic/{version}/edit/servers/{name}/webService/webServicePersistence/webServiceLogicalStores/{name} 1-4880

/management/weblogic/{version}/edit/servers/{name}/webService/webServicePersistence/webServicePhysicalStoreCreateForm 1-4884

/management/weblogic/{version}/edit/servers/{name}/webService/webServicePersistence/webServicePhysicalStores 1-4886

/management/weblogic/{version}/edit/servers/{name}/webService/webServicePersistence/webServicePhysicalStores/{name} 1-4889

/management/weblogic/{version}/edit/servers/{name}/webService/webServiceReliability 1-4893

/management/weblogic/{version}/edit/serverTemplateCreateForm 1-4896

/management/weblogic/{version}/edit/serverTemplates 1-4898

/management/weblogic/{version}/edit/serverTemplates/{name} 1-4901

/management/weblogic/{version}/edit/serverTemplates/{name}/coherenceMemberConfig 1-4907

/management/weblogic/{version}/edit/serverTemplates/{name}/configurationProperties 1-4910

/management/weblogic/{version}/edit/serverTemplates/{name}/configurationProperties/{name} 1-4913

/management/weblogic/{version}/edit/serverTemplates/{name}/configurationPropertyCreateForm 1-4917

/management/weblogic/{version}/edit/serverTemplates/{name}/dataSource 1-4919

/management/weblogic/{version}/edit/serverTemplates/{name}/dataSource/dataSourceLogFile 1-4922

/management/weblogic/{version}/edit/serverTemplates/{name}/defaultFileStore 1-4925

/management/weblogic/{version}/edit/serverTemplates/{name}/executeQueues 1-4928

/management/weblogic/{version}/edit/serverTemplates/{name}/executeQueues/{name} } 1-4930

/management/weblogic/{version}/edit/serverTemplates/{name}/federationServices
 1-4933

/management/weblogic/{version}/edit/serverTemplates/{name}/IIOP..... 1-4936

/management/weblogic/{version}/edit/serverTemplates/{name}/JTAMigratableTarget .
 1-4939

/management/weblogic/{version}/edit/serverTemplates/{name}/log 1-4942

/management/weblogic/{version}/edit/serverTemplates/{name}/networkAccessPointC
 reateForm 1-4945

/management/weblogic/{version}/edit/serverTemplates/{name}/networkAccessPoints .
 1-4947

/management/weblogic/{version}/edit/serverTemplates/{name}/networkAccessPoints/
 {name} 1-4950

/management/weblogic/{version}/edit/serverTemplates/{name}/overloadProtection
 1-4954

/management/weblogic/{version}/edit/serverTemplates/{name}/overloadProtection/se
 rverFailureTrigger 1-4957

/management/weblogic/{version}/edit/serverTemplates/{name}/overloadProtection/se
 rverFailureTriggerCreateForm 1-4961

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDebug . 1-4963

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDebug/debugSc
 opeCreateForm 1-4966

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDebug/debugSc
 opes 1-4968

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDebug/debugSc
 opes/{name} 1-4971

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfi
 g 1-4975

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfi
 g/lookupWLDFFDataRetirement 1-4978

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfi
 g/WLDFBuiltinSystemResourceDescriptorBean 1-4980

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfi
 g/WLDFBuiltinSystemResourceDescriptorBean/harvester 1-4982

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfi
 g/WLDFBuiltinSystemResourceDescriptorBean/harvester/harvestedTypeCreateForm
 1-4985

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/harvester/harvestedTypes 1-4987

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/harvester/harvestedTypes/{name} 1-4990

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/instrumentation 1-4994

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/instrumentation/WLDFInstrumentationMonitorCreateForm 1-4997

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/instrumentation/WLDFInstrumentationMonitors 1-4999

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/instrumentation/WLDFInstrumentationMonitors/{name} 1-5002

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification 1-5006

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actionCreateForm 1-5012

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions 1-5014

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name} 1-5017

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/arrayProperties 1-5022

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/arrayProperties/{name} 1-5025

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/arrayPropertyCreateForm 1-5029

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig

g/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/configurationProperties 1-5031

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/configurationProperties/{name} 1-5033

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/encryptedProperties 1-5035

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/encryptedProperties/{name} 1-5038

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/encryptedPropertyCreateForm 1-5042

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapProperties 1-5044

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapProperties/{name} 1-5047

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapProperties/{name}/configurationProperties 1-5051

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapProperties/{name}/configurationProperties/{name} 1-5053

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapProperties/{name}/encryptedProperties 1-5055

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapProperties/{name}/encryptedProperties/{name} 1-5058

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapProperties/{name}/encryptedPropertyCreateForm 1-5062

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapProperties/{name}/properties 1-5064

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapProperties/{name}/properties/{name} 1-5067

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapProperties/{name}/propertyCreateForm 1-5071

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapPropertyCreateForm 1-5073

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/properties 1-5075

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/properties/{name} 1-5078

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/propertyCreateForm 1-5082

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/heapDumpActionCreateForm 1-5084

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/heapDumpActions 1-5086

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/heapDumpActions/{name} 1-5089

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/imageNotificationCreateForm 1-5093

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/imageNotifications 1-5095

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/imageNotifications/{name} 1-5098

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig

g/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/JMSNotificationCreateForm 1-5102

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/JMSNotifications 1-5104

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/JMSNotifications/{name} 1-5107

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/JMXNotificationCreateForm 1-5111

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/JMXNotifications 1-5113

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/JMXNotifications/{name} 1-5116

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/logActionCreateForm 1-5120

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/logActions 1-5122

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/logActions/{name} 1-5125

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/lookupActions 1-5129

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/lookupNotification 1-5131

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/RESTNotificationCreateForm 1-5133

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/RESTNotifications 1-5135

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig

g/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/RESTNotifications/{name} 1-5138

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/scaleDownActionCreateForm 1-5142

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/scaleDownActions 1-5144

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/scaleDownActions/{name} 1-5147

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/scaleUpActionCreateForm 1-5151

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/scaleUpActions 1-5153

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/scaleUpActions/{name} 1-5156

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/scriptActionCreateForm 1-5160

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/scriptActions 1-5162

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/scriptActions/{name} 1-5165

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/SMTPNotificationCreateForm 1-5169

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/SMTPNotifications 1-5171

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/SMTPNotifications/{name} 1-5174

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/SNMPNotificationCreateForm 1-5178

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/SNMPNotifications 1-5180

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/SNMPNotifications/{name} 1-5183

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/threadDumpActionCreateForm 1-5187

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/threadDumpActions 1-5189

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/threadDumpActions/{name} 1-5192

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/watchCreateForm 1-5196

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/watches 1-5198

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/watches/{name} 1-5201

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/watches/{name}/schedule 1-5205

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFDataRetirementByAgeCreateForm 1-5208

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFDataRetirementByAges 1-5210

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFDataRetirementByAges/{name} 1-5213

/management/weblogic/{version}/edit/serverTemplates/{name}/serverStart..... 1-5217

/management/weblogic/{version}/edit/serverTemplates/{name}/singleSignOnServices. 1-5220

/management/weblogic/{version}/edit/serverTemplates/{name}/SSL	1-5223
/management/weblogic/{version}/edit/serverTemplates/{name}/transactionLogJDBCStore	1-5226
/management/weblogic/{version}/edit/serverTemplates/{name}/webServer	1-5229
/management/weblogic/{version}/edit/serverTemplates/{name}/webServer/webServerLog	1-5232
/management/weblogic/{version}/edit/serverTemplates/{name}/webService....	1-5235
/management/weblogic/{version}/edit/serverTemplates/{name}/webService/webServiceBuffering	1-5238
/management/weblogic/{version}/edit/serverTemplates/{name}/webService/webServiceBuffering/webServiceRequestBufferingQueue	1-5241
/management/weblogic/{version}/edit/serverTemplates/{name}/webService/webServiceBuffering/webServiceResponseBufferingQueue	1-5244
/management/weblogic/{version}/edit/serverTemplates/{name}/webService/webServicePersistence	1-5247
/management/weblogic/{version}/edit/serverTemplates/{name}/webService/webServicePersistence/webServiceLogicalStoreCreateForm	1-5250
/management/weblogic/{version}/edit/serverTemplates/{name}/webService/webServicePersistence/webServiceLogicalStores	1-5252
/management/weblogic/{version}/edit/serverTemplates/{name}/webService/webServicePersistence/webServiceLogicalStores/{name}	1-5255
/management/weblogic/{version}/edit/serverTemplates/{name}/webService/webServicePersistence/webServicePhysicalStoreCreateForm	1-5259
/management/weblogic/{version}/edit/serverTemplates/{name}/webService/webServicePersistence/webServicePhysicalStores	1-5261
/management/weblogic/{version}/edit/serverTemplates/{name}/webService/webServicePersistence/webServicePhysicalStores/{name}	1-5264
/management/weblogic/{version}/edit/serverTemplates/{name}/webService/webServiceReliability	1-5268
/management/weblogic/{version}/edit/shutdownClassCreateForm	1-5271
/management/weblogic/{version}/edit/shutdownClasses.....	1-5273
/management/weblogic/{version}/edit/shutdownClasses/{name}.....	1-5276
/management/weblogic/{version}/edit/singletonServiceCreateForm.....	1-5280
/management/weblogic/{version}/edit/singletonServices.....	1-5282
/management/weblogic/{version}/edit/singletonServices/{name}	1-5285

/management/weblogic/{version}/edit/SNMPAgent	1-5289
/management/weblogic/{version}/edit/SNMPAgent/SNMPAttributeChangeCreateForm	1-5293
/management/weblogic/{version}/edit/SNMPAgent/SNMPAttributeChanges ..	1-5295
/management/weblogic/{version}/edit/SNMPAgent/SNMPAttributeChanges/{name}...	1-5298
/management/weblogic/{version}/edit/SNMPAgent/SNMPCounterMonitorCreateForm	1-5302
/management/weblogic/{version}/edit/SNMPAgent/SNMPCounterMonitors ...	1-5304
/management/weblogic/{version}/edit/SNMPAgent/SNMPCounterMonitors/{name} ...	1-5307
/management/weblogic/{version}/edit/SNMPAgent/SNMPGaugeMonitorCreateForm..	1-5311
/management/weblogic/{version}/edit/SNMPAgent/SNMPGaugeMonitors	1-5313
/management/weblogic/{version}/edit/SNMPAgent/SNMPGaugeMonitors/{name}	1-5316
/management/weblogic/{version}/edit/SNMPAgent/SNMPLogFilterCreateForm.....	1-5320
/management/weblogic/{version}/edit/SNMPAgent/SNMPLogFilters	1-5322
/management/weblogic/{version}/edit/SNMPAgent/SNMPLogFilters/{name} .	1-5325
/management/weblogic/{version}/edit/SNMPAgent/SNMPProxies	1-5329
/management/weblogic/{version}/edit/SNMPAgent/SNMPProxies/{name}	1-5332
/management/weblogic/{version}/edit/SNMPAgent/SNMPProxyCreateForm...	1-5336
/management/weblogic/{version}/edit/SNMPAgent/SNMPStringMonitorCreateForm...	1-5338
/management/weblogic/{version}/edit/SNMPAgent/SNMPStringMonitors	1-5340
/management/weblogic/{version}/edit/SNMPAgent/SNMPStringMonitors/{name}	1-5343
/management/weblogic/{version}/edit/SNMPAgent/SNMPTrapDestinationCreateForm	1-5347
/management/weblogic/{version}/edit/SNMPAgent/SNMPTrapDestinations....	1-5349
/management/weblogic/{version}/edit/SNMPAgent/SNMPTrapDestinations/{name}....	1-5352
/management/weblogic/{version}/edit/SNMPAgentDeploymentCreateForm	1-5356
/management/weblogic/{version}/edit/SNMPAgentDeployments	1-5358
/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}.....	1-5361
/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPAttributeChangeCreateForm	1-5366
/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPAttributeChanges	1-5368
/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPAttributeChanges/{name}	1-5371

/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPCounterMonitorCreateForm 1-5375

/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPCounterMonitors 1-5377

/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPCounterMonitors/{name} 1-5380

/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPGaugeMonitorCreateForm 1-5384

/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPGaugeMonitors 1-5386

/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPGaugeMonitors/{name} 1-5389

/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPLogFilterCreateForm 1-5393

/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPLogFilters 1-5395

/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPLogFilters/{name} 1-5398

/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPProxies 1-5402

/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPProxies/{name} 1-5405

/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPProxyCreateForm 1-5409

/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPStringMonitorCreateForm 1-5411

/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPStringMonitors 1-5413

/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPStringMonitors/{name} 1-5416

/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPTrapDestinationCreateForm 1-5420

/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPTrapDestinations	1-5422
/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPTrapDestinations/{name}	1-5425
/management/weblogic/{version}/edit/startupClassCreateForm.....	1-5429
/management/weblogic/{version}/edit/startupClasses.....	1-5431
/management/weblogic/{version}/edit/startupClasses/{name}.....	1-5434
/management/weblogic/{version}/edit/systemComponentConfigurationCreateForm.....	1-5438
/management/weblogic/{version}/edit/systemComponentConfigurations.....	1-5440
/management/weblogic/{version}/edit/systemComponentConfigurations/{name}.....	1-5443
/management/weblogic/{version}/edit/systemComponentCreateForm.....	1-5447
/management/weblogic/{version}/edit/systemComponents.....	1-5449
/management/weblogic/{version}/edit/systemComponents/{name}.....	1-5452
/management/weblogic/{version}/edit/systemComponents/{name}/systemComponentStart	1-5456
/management/weblogic/{version}/edit/virtualHostCreateForm.....	1-5459
/management/weblogic/{version}/edit/virtualHosts.....	1-5461
/management/weblogic/{version}/edit/virtualHosts/{name}.....	1-5464
/management/weblogic/{version}/edit/virtualHosts/{name}/webServerLog.....	1-5468
/management/weblogic/{version}/edit/virtualTargetCreateForm.....	1-5471
/management/weblogic/{version}/edit/virtualTargets.....	1-5473
/management/weblogic/{version}/edit/virtualTargets/{name}.....	1-5476
/management/weblogic/{version}/edit/virtualTargets/{name}/webServer.....	1-5480
/management/weblogic/{version}/edit/virtualTargets/{name}/webServer/webServerLog	1-5483
/management/weblogic/{version}/edit/webAppContainer.....	1-5486
/management/weblogic/{version}/edit/webAppContainer/gzipCompression....	1-5489
/management/weblogic/{version}/edit/webserviceSecurities.....	1-5492
/management/weblogic/{version}/edit/webserviceSecurities/{name}.....	1-5495
/management/weblogic/{version}/edit/webserviceSecurities/{name}/webserviceCredentialProviderCreateForm	1-5499
/management/weblogic/{version}/edit/webserviceSecurities/{name}/webserviceCredentialProviders	1-5501
/management/weblogic/{version}/edit/webserviceSecurities/{name}/webserviceCredentialProviders/{name}	1-5504

/management/weblogic/{version}/edit/webserviceSecurities/{name}/webserviceCredentialProviders/{name}/configurationProperties 1-5508

/management/weblogic/{version}/edit/webserviceSecurities/{name}/webserviceCredentialProviders/{name}/configurationProperties/{name} 1-5511

/management/weblogic/{version}/edit/webserviceSecurities/{name}/webserviceCredentialProviders/{name}/configurationPropertyCreateForm 1-5515

/management/weblogic/{version}/edit/webserviceSecurities/{name}/webserviceSecurityTokenCreateForm 1-5517

/management/weblogic/{version}/edit/webserviceSecurities/{name}/webserviceSecurityTokens 1-5519

/management/weblogic/{version}/edit/webserviceSecurities/{name}/webserviceSecurityTokens/{name} 1-5522

/management/weblogic/{version}/edit/webserviceSecurities/{name}/webserviceSecurityTokens/{name}/configurationProperties 1-5526

/management/weblogic/{version}/edit/webserviceSecurities/{name}/webserviceSecurityTokens/{name}/configurationProperties/{name} 1-5529

/management/weblogic/{version}/edit/webserviceSecurities/{name}/webserviceSecurityTokens/{name}/configurationPropertyCreateForm 1-5533

/management/weblogic/{version}/edit/webserviceSecurities/{name}/webserviceTimestamp 1-5535

/management/weblogic/{version}/edit/webserviceSecurities/{name}/webserviceTokenHandlerCreateForm 1-5538

/management/weblogic/{version}/edit/webserviceSecurities/{name}/webserviceTokenHandlers 1-5540

/management/weblogic/{version}/edit/webserviceSecurities/{name}/webserviceTokenHandlers/{name} 1-5543

/management/weblogic/{version}/edit/webserviceSecurities/{name}/webserviceTokenHandlers/{name}/configurationProperties 1-5547

/management/weblogic/{version}/edit/webserviceSecurities/{name}/webserviceTokenHandlers/{name}/configurationProperties/{name} 1-5550

/management/weblogic/{version}/edit/webserviceSecurities/{name}/webserviceTokenHandlers/{name}/configurationPropertyCreateForm 1-5554

/management/weblogic/{version}/edit/webserviceSecurityCreateForm 1-5556

/management/weblogic/{version}/edit/webserviceTestpage	1-5558
/management/weblogic/{version}/edit/WLDFSystemResourceCreateForm	1-5561
/management/weblogic/{version}/edit/WLDFSystemResources	1-5563
/management/weblogic/{version}/edit/WLDFSystemResources/{name}	1-5566
/management/weblogic/{version}/edit/WLDFSystemResources/{name}/subDeploymentCreateForm	1-5570
/management/weblogic/{version}/edit/WLDFSystemResources/{name}/subDeployments	1-5572
/management/weblogic/{version}/edit/WLDFSystemResources/{name}/subDeployments/{name}	1-5575
/management/weblogic/{version}/edit/WLDFSystemResources/{name}/subDeployments/{name}/subDeployments	1-5579
/management/weblogic/{version}/edit/WLDFSystemResources/{name}/subDeployments/{name}/subDeployments/{name}	1-5581
/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource	1-5584
/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/harvester	1-5586
/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/harvester/harvestedTypeCreateForm	1-5589
/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/harvester/harvestedTypes	1-5591
/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/harvester/harvestedTypes/{name}	1-5594
/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/instrumentation	1-5598
/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/instrumentation/WLDFInstrumentationMonitorCreateForm	1-5601
/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/instrumentation/WLDFInstrumentationMonitors	1-5603
/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/instrumentation/WLDFInstrumentationMonitors/{name}	1-5606
/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification	1-5610

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/actionCreateForm 1-5615

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions 1-5617

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name} 1-5620

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/arrayProperties 1-5625

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/arrayProperties/{name} 1-5628

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/arrayPropertyCreateForm 1-5632

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/configurationProperties 1-5634

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/configurationProperties/{name} 1-5636

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/encryptedProperties 1-5638

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/encryptedProperties/{name} 1-5641

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/encryptedPropertyCreateForm 1-5645

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties 1-5647

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name} 1-5650

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/configurationProperties 1-5653

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/configurationProperties/{name} 1-5655

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource

e/watchNotification/actions/{name}/mapProperties/{name}/encryptedProperties
1-5657

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/encryptedProperties/{name} 1-5660

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/encryptedPropertyCreateForm 1-5664

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/properties 1-5666

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/properties/{name} 1-5669

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/propertyCreateForm
1-5673

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapPropertyCreateForm 1-5675

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/properties 1-5677

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/properties/{name} 1-5680

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/propertyCreateForm 1-5684

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/heapDumpActionCreateForm 1-5686

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/heapDumpActions 1-5688

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/heapDumpActions/{name} 1-5691

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/imageNotificationCreateForm 1-5695

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/imageNotifications 1-5697

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/imageNotifications/{name} 1-5700

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMSNotificationCreateForm 1-5704

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMSNotifications 1-5706

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMSNotifications/{name} 1-5709

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMXNotificationCreateForm 1-5713

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMXNotifications 1-5715

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMXNotifications/{name} 1-5718

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/logActionCreateForm 1-5722

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/logActions 1-5724

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/logActions/{name} 1-5727

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/lookupActions 1-5731

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/lookupNotification 1-5733

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/RESTNotificationCreateForm 1-5735

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/RESTNotifications 1-5737

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/RESTNotifications/{name} 1-5740

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleDownActionCreateForm 1-5744

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleDownActions 1-5746

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleDownActions/{name} 1-5749

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleUpActionCreateForm 1-5753

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleUpActions 1-5755

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleUpActions/{name} 1-5758

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/scriptActionCreateForm 1-5762

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/scriptActions 1-5764

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/scriptActions/{name} 1-5767

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/SMTPLNotificationCreateForm 1-5771

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/SMTPLNotifications 1-5773

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/SMTPLNotifications/{name} 1-5776

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/SNMPNotificationCreateForm 1-5780

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/SNMPNotifications 1-5782

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/SNMPNotifications/{name} 1-5785

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/threadDumpActionCreateForm 1-5789

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/threadDumpActions 1-5791

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/threadDumpActions/{name} 1-5794

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/watchCreateForm 1-5798

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/watches 1-5800

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/watches/{name} 1-5803

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/watches/{name}/schedule 1-5807

/management/weblogic/{version}/edit/WSReliableDeliveryPolicies..... 1-5810

/management/weblogic/{version}/edit/WSReliableDeliveryPolicies/{name}..... 1-5813

/management/weblogic/{version}/edit/WSReliableDeliveryPolicyCreateForm ... 1-5817

/management/weblogic/{version}/edit/WTCServerCreateForm 1-5819

/management/weblogic/{version}/edit/WTCServers 1-5821

/management/weblogic/{version}/edit/WTCServers/{name} 1-5824

/management/weblogic/{version}/edit/WTCServers/{name}/WTCEXportCreateForm....
1-5829

/management/weblogic/{version}/edit/WTCServers/{name}/WTCEXports 1-5831

/management/weblogic/{version}/edit/WTCServers/{name}/WTCEXports/{name}
1-5834

/management/weblogic/{version}/edit/WTCServers/{name}/WTCImportCreateForm ...
1-5838

/management/weblogic/{version}/edit/WTCServers/{name}/WTCImports..... 1-5840

/management/weblogic/{version}/edit/WTCServers/{name}/WTCImports/{name}
1-5843

/management/weblogic/{version}/edit/WTCServers/{name}/WTCLocalTuxDomCreate
Form 1-5847

/management/weblogic/{version}/edit/WTCServers/{name}/WTCLocalTuxDoms.....
1-5849

/management/weblogic/{version}/edit/WTCServers/{name}/WTCLocalTuxDoms/{na
me} 1-5852

/management/weblogic/{version}/edit/WTCServers/{name}/WTCPasswordCreateFor
m 1-5856

/management/weblogic/{version}/edit/WTCServers/{name}/WTCPasswords... 1-5858

/management/weblogic/{version}/edit/WTCServers/{name}/WTCPasswords/{name}...
1-5861

/management/weblogic/{version}/edit/WTCServers/{name}/WTCRemoteTuxDomCrea
teForm 1-5865

/management/weblogic/{version}/edit/WTCServers/{name}/WTCRemoteTuxDoms.....
1-5867

/management/weblogic/{version}/edit/WTCservers/{name}/WTCRemoteTuxDoms/{name}	1-5870
/management/weblogic/{version}/edit/WTCservers/{name}/WTCResources....	1-5874
/management/weblogic/{version}/edit/WTCservers/{name}/WTCResourcesCreateForm	1-5878
/management/weblogic/{version}/edit/WTCservers/{name}/WTCtBridgeGlobal.....	1-5880
/management/weblogic/{version}/edit/WTCservers/{name}/WTCtBridgeGlobalCreateForm	1-5884
/management/weblogic/{version}/edit/WTCservers/{name}/WTCtBridgeRedirectCreateForm	1-5886
/management/weblogic/{version}/edit/WTCservers/{name}/WTCtBridgeRedirects.....	1-5888
/management/weblogic/{version}/edit/WTCservers/{name}/WTCtBridgeRedirects/{name}	1-5891
/management/weblogic/{version}/edit/XMLEntityCacheCreateForm.....	1-5895
/management/weblogic/{version}/edit/XMLEntityCaches.....	1-5897
/management/weblogic/{version}/edit/XMLEntityCaches/{name}.....	1-5900
/management/weblogic/{version}/edit/XMLRegistries.....	1-5904
/management/weblogic/{version}/edit/XMLRegistries/{name}.....	1-5907
/management/weblogic/{version}/edit/XMLRegistries/{name}/XMLEntitySpecRegistryEntries	1-5911
/management/weblogic/{version}/edit/XMLRegistries/{name}/XMLEntitySpecRegistryEntries/{name}	1-5914
/management/weblogic/{version}/edit/XMLRegistries/{name}/XMLEntitySpecRegistryEntryCreateForm	1-5918
/management/weblogic/{version}/edit/XMLRegistries/{name}/XMLParserSelectRegistryEntries	1-5920
/management/weblogic/{version}/edit/XMLRegistries/{name}/XMLParserSelectRegistryEntries/{name}	1-5923
/management/weblogic/{version}/edit/XMLRegistries/{name}/XMLParserSelectRegistryEntryCreateForm	1-5927
/management/weblogic/{version}/edit/XMLRegistryCreateForm.....	1-5929

2 Entities

java.util.Properties.....	2-1
weblogic.coherence.descriptor.wl.CoherenceAddressProviderBean.....	2-1

weblogic.coherence.descriptor.wl.CoherenceAddressProvidersBean.....	2-1
weblogic.coherence.descriptor.wl.CoherenceCacheBean.....	2-1
weblogic.coherence.descriptor.wl.CoherenceClusterParamsBean.....	2-2
weblogic.coherence.descriptor.wl.CoherenceClusterWellKnownAddressBean.....	2-3
weblogic.coherence.descriptor.wl.CoherenceClusterWellKnownAddressesBean.....	2-3
weblogic.coherence.descriptor.wl.CoherenceFederationParamsBean.....	2-3
weblogic.coherence.descriptor.wl.CoherenceIdentityAsserterBean.....	2-4
weblogic.coherence.descriptor.wl.CoherenceInitParamBean.....	2-4
weblogic.coherence.descriptor.wl.CoherenceKeystoreParamsBean.....	2-4
weblogic.coherence.descriptor.wl.CoherenceLoggingParamsBean.....	2-5
weblogic.coherence.descriptor.wl.CoherencePersistenceParamsBean.....	2-5
weblogic.coherence.descriptor.wl.CoherenceServiceBean.....	2-6
weblogic.coherence.descriptor.wl.CoherenceSocketAddressBean.....	2-6
weblogic.coherence.descriptor.wl.WeblogicCoherenceBean.....	2-7
weblogic.diagnostics.descriptor.WLDFActionBean.....	2-7
weblogic.diagnostics.descriptor.WLDFArrayPropertyBean.....	2-8
weblogic.diagnostics.descriptor.WLDFConfigurationPropertiesBean.....	2-9
weblogic.diagnostics.descriptor.WLDFConfigurationPropertyBean.....	2-9
weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean.....	2-9
weblogic.diagnostics.descriptor.WLDFHarvestedTypeBean.....	2-10
weblogic.diagnostics.descriptor.WLDFHarvesterBean.....	2-11
weblogic.diagnostics.descriptor.WLDFHeapDumpActionBean.....	2-12
weblogic.diagnostics.descriptor.WLDFImageNotificationBean.....	2-13
weblogic.diagnostics.descriptor.WLDFInstrumentationBean.....	2-13
weblogic.diagnostics.descriptor.WLDFInstrumentationMonitorBean.....	2-14
weblogic.diagnostics.descriptor.WLDFJMSNotificationBean.....	2-16
weblogic.diagnostics.descriptor.WLDFJMXNotificationBean.....	2-17
weblogic.diagnostics.descriptor.WLDFLogActionBean.....	2-18
weblogic.diagnostics.descriptor.WLDFPropertyBean.....	2-19
weblogic.diagnostics.descriptor.WLDFRESTNotificationBean.....	2-19
weblogic.diagnostics.descriptor.WLDFResourceBean.....	2-20
weblogic.diagnostics.descriptor.WLDFSMTPNotificationBean.....	2-21
weblogic.diagnostics.descriptor.WLDFSNMPNotificationBean.....	2-22
weblogic.diagnostics.descriptor.WLDFScaleDownActionBean.....	2-23
weblogic.diagnostics.descriptor.WLDFScaleUpActionBean.....	2-23
weblogic.diagnostics.descriptor.WLDFScheduleBean.....	2-24
weblogic.diagnostics.descriptor.WLDFScriptActionBean.....	2-26
weblogic.diagnostics.descriptor.WLDFThreadDumpActionBean.....	2-27
weblogic.diagnostics.descriptor.WLDFWatchBean.....	2-27
weblogic.diagnostics.descriptor.WLDFWatchNotificationBean.....	2-29
weblogic.j2ee.descriptor.wl.ClientParamsBean.....	2-30
weblogic.j2ee.descriptor.wl.DefaultDeliveryParamsBean.....	2-34
weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean.....	2-37
weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean.....	2-39
weblogic.j2ee.descriptor.wl.DestinationKeyBean.....	2-40
weblogic.j2ee.descriptor.wl.FlowControlParamsBean.....	2-42
weblogic.j2ee.descriptor.wl.ForeignConnectionFactoryBean.....	2-44

weblogic.j2ee.descriptor.wl.ForeignDestinationBean	2-45
weblogic.j2ee.descriptor.wl.ForeignServerBean.....	2-46
weblogic.j2ee.descriptor.wl.GroupParamsBean.....	2-47
weblogic.j2ee.descriptor.wl.JDBCConnectionPoolParamsBean	2-48
weblogic.j2ee.descriptor.wl.JDBCDataSourceBean	2-56
weblogic.j2ee.descriptor.wl.JDBCDataSourceParamsBean	2-57
weblogic.j2ee.descriptor.wl.JBCDriverParamsBean	2-59
weblogic.j2ee.descriptor.wl.JBCOracleParamsBean	2-60
weblogic.j2ee.descriptor.wl.JBCPropertiesBean.....	2-62
weblogic.j2ee.descriptor.wl.JBCPropertyBean	2-63
weblogic.j2ee.descriptor.wl.JBCXAParamsBean.....	2-63
weblogic.j2ee.descriptor.wl.JMSBean	2-65
weblogic.j2ee.descriptor.wl.JMSConnectionFactoryBean.....	2-66
weblogic.j2ee.descriptor.wl.LoadBalancingParamsBean.....	2-67
weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean	2-68
weblogic.j2ee.descriptor.wl.MulticastParamsBean.....	2-68
weblogic.j2ee.descriptor.wl.PropertyBean.....	2-69
weblogic.j2ee.descriptor.wl.QueueBean.....	2-69
weblogic.j2ee.descriptor.wl.QuotaBean	2-76
weblogic.j2ee.descriptor.wl.SAFErrorHandlerBean.....	2-78
weblogic.j2ee.descriptor.wl.SAFImportedDestinationsBean	2-80
weblogic.j2ee.descriptor.wl.SAFLoginContextBean.....	2-82
weblogic.j2ee.descriptor.wl.SAFQueueBean	2-82
weblogic.j2ee.descriptor.wl.SAFRemoteContextBean.....	2-84
weblogic.j2ee.descriptor.wl.SAFTopicBean	2-85
weblogic.j2ee.descriptor.wl.SecurityParamsBean.....	2-88
weblogic.j2ee.descriptor.wl.TemplateBean.....	2-88
weblogic.j2ee.descriptor.wl.ThresholdParamsBean	2-91
weblogic.j2ee.descriptor.wl.TopicBean.....	2-93
weblogic.j2ee.descriptor.wl.TopicSubscriptionParamsBean	2-100
weblogic.j2ee.descriptor.wl.TransactionParamsBean	2-100
weblogic.j2ee.descriptor.wl.UniformDistributedQueueBean	2-101
weblogic.j2ee.descriptor.wl.UniformDistributedTopicBean	2-107
weblogic.management.configuration.AdminConsoleMBean	2-114
weblogic.management.configuration.AdminVirtualTargetMBean	2-115
weblogic.management.configuration.AppDeploymentMBean	2-117
weblogic.management.configuration.AuthConfigProviderMBean	2-122
weblogic.management.configuration.BatchConfigMBean	2-123
weblogic.management.configuration.CapacityMBean	2-124
weblogic.management.configuration.CdiContainerMBean	2-126
weblogic.management.configuration.CertRevocCaMBean.....	2-127
weblogic.management.configuration.CertRevocMBean.....	2-131
weblogic.management.configuration.ClusterMBean	2-134
weblogic.management.configuration.CoherenceCacheConfigMBean	2-144
weblogic.management.configuration.CoherenceClusterSystemResourceMBean	2-146
weblogic.management.configuration.CoherenceManagementAddressProviderMBean	2-149
weblogic.management.configuration.CoherenceManagementClusterMBean	2-150

weblogic.management.configuration.CoherenceMemberConfigMBean	2-152
weblogic.management.configuration.CoherencePartitionCacheConfigMBean	2-154
weblogic.management.configuration.CoherencePartitionCachePropertyMBean	2-155
weblogic.management.configuration.CoherenceServerMBean	2-156
weblogic.management.configuration.CoherenceServerStartMBean	2-158
weblogic.management.configuration.CoherenceTierMBean	2-161
weblogic.management.configuration.ConfigurationPropertyMBean	2-162
weblogic.management.configuration.ContextCaseMBean	2-163
weblogic.management.configuration.ContextRequestClassMBean	2-165
weblogic.management.configuration.CpuUtilizationMBean	2-166
weblogic.management.configuration.CustomResourceMBean	2-167
weblogic.management.configuration.DataSourceLogFileMBean	2-170
weblogic.management.configuration.DataSourceMBean	2-173
weblogic.management.configuration.DataSourcePartitionMBean	2-174
weblogic.management.configuration.DatabaseLessLeasingBasisMBean	2-175
weblogic.management.configuration.DebugPatchesMBean	2-176
weblogic.management.configuration.DebugScopeMBean	2-177
weblogic.management.configuration.DefaultFileStoreMBean	2-178
weblogic.management.configuration.DeploymentConfigurationMBean	2-184
weblogic.management.configuration.DeploymentValidationPluginMBean	2-186
weblogic.management.configuration.DeterminerCandidateResourceInfoVBean	2-187
weblogic.management.configuration.DomainMBean	2-188
weblogic.management.configuration.DynamicServersMBean	2-194
weblogic.management.configuration.EmbeddedLDAPMBean	2-197
weblogic.management.configuration.ExecuteQueueMBean	2-200
weblogic.management.configuration.FairShareConstraintMBean	2-202
weblogic.management.configuration.FairShareRequestClassMBean	2-203
weblogic.management.configuration.FederationServicesMBean	2-205
weblogic.management.configuration.FileOpenMBean	2-209
weblogic.management.configuration.FileStoreMBean	2-210
weblogic.management.configuration.ForeignConnectionFactoryOverrideMBean	2-220
weblogic.management.configuration.ForeignDestinationOverrideMBean	2-221
weblogic.management.configuration.ForeignJNDILinkMBean	2-222
weblogic.management.configuration.ForeignJNDILinkOverrideMBean	2-223
weblogic.management.configuration.ForeignJNDIProviderMBean	2-225
weblogic.management.configuration.ForeignJNDIProviderOverrideMBean	2-226
weblogic.management.configuration.ForeignServerOverrideMBean	2-228
weblogic.management.configuration.GzipCompressionMBean	2-230
weblogic.management.configuration.HeapRetainedMBean	2-231
weblogic.management.configuration.IIOPMBean	2-232
weblogic.management.configuration.InterceptorMBean	2-234
weblogic.management.configuration.InterceptorsMBean	2-236
weblogic.management.configuration.JASPICMBean	2-237
weblogic.management.configuration.JDBCPropertyOverrideMBean	2-238
weblogic.management.configuration.JDBCStoreMBean	2-239
weblogic.management.configuration.JDBCSystemResourceMBean	2-248
weblogic.management.configuration.JDBCSystemResourceOverrideMBean	2-250

weblogic.management.configuration.JMSBridgeDestinationMBean	2-251
weblogic.management.configuration.JMSInteropModuleMBean.....	2-254
weblogic.management.configuration.JMSMessageLogFileMBean	2-256
weblogic.management.configuration.JMSSAFMessageLogFileMBean.....	2-259
weblogic.management.configuration.JMSServerMBean	2-261
weblogic.management.configuration.JMSSystemResourceMBean.....	2-272
weblogic.management.configuration.JMSSystemResourceOverrideMBean.....	2-274
weblogic.management.configuration.JMXMBean	2-275
weblogic.management.configuration.JPAMBean	2-279
weblogic.management.configuration.JTAClusterMBean	2-280
weblogic.management.configuration.JTAMBean	2-286
weblogic.management.configuration.JTAMigratableTargetMBean	2-293
weblogic.management.configuration.JTAPartitionMBean.....	2-296
weblogic.management.configuration.JoltConnectionPoolMBean.....	2-297
weblogic.management.configuration.LibraryMBean.....	2-302
weblogic.management.configuration.LifecycleManagerConfigMBean	2-308
weblogic.management.configuration.LifecycleManagerEndPointMBean.....	2-310
weblogic.management.configuration.LogFilterMBean.....	2-312
weblogic.management.configuration.LogMBean	2-313
weblogic.management.configuration.MachineMBean.....	2-319
weblogic.management.configuration.MailSessionMBean.....	2-320
weblogic.management.configuration.MailSessionOverrideMBean.....	2-322
weblogic.management.configuration.ManagedExecutorServiceMBean.....	2-323
weblogic.management.configuration.ManagedExecutorServiceTemplateMBean	2-325
weblogic.management.configuration.ManagedScheduledExecutorServiceMBean	2-327
weblogic.management.configuration.ManagedScheduledExecutorServiceTemplateMBean.	2-328
weblogic.management.configuration.ManagedThreadFactoryMBean	2-330
weblogic.management.configuration.ManagedThreadFactoryTemplateMBean.....	2-332
weblogic.management.configuration.MaxThreadsConstraintMBean	2-333
weblogic.management.configuration.MessagingBridgeMBean	2-335
weblogic.management.configuration.MigratableTargetMBean	2-344
weblogic.management.configuration.MinThreadsConstraintMBean.....	2-348
weblogic.management.configuration.NetworkAccessPointMBean.....	2-349
weblogic.management.configuration.NodeManagerMBean	2-358
weblogic.management.configuration.OptionalFeatureDeploymentMBean.....	2-361
weblogic.management.configuration.OptionalFeatureMBean	2-362
weblogic.management.configuration.OsgiFrameworkMBean	2-363
weblogic.management.configuration.OverloadProtectionMBean	2-365
weblogic.management.configuration.ParameterMBean.....	2-367
weblogic.management.configuration.PartitionFileSystemMBean	2-368
weblogic.management.configuration.PartitionLogMBean.....	2-369
weblogic.management.configuration.PartitionMBean.....	2-370
weblogic.management.configuration.PartitionPropertyMBean.....	2-374
weblogic.management.configuration.PartitionUserFileSystemMBean	2-375
weblogic.management.configuration.PartitionWorkManagerMBean.....	2-376
weblogic.management.configuration.ResourceGroupMBean	2-378
weblogic.management.configuration.ResourceGroupTemplateMBean	2-380

weblogic.management.configuration.ResourceManagementMBean	2-381
weblogic.management.configuration.ResourceManagerMBean	2-382
weblogic.management.configuration.ResponseTimeRequestClassMBean.....	2-383
weblogic.management.configuration.RestartLoopProtectionMBean	2-385
weblogic.management.configuration.RestfulManagementServicesMBean.....	2-386
weblogic.management.configuration.SAFAgentMBean.....	2-388
weblogic.management.configuration.SNMPAgentDeploymentMBean	2-397
weblogic.management.configuration.SNMPAgentMBean	2-403
weblogic.management.configuration.SNMPAttributeChangeMBean	2-409
weblogic.management.configuration.SNMPCounterMonitorMBean	2-411
weblogic.management.configuration.SNMPGaugeMonitorMBean	2-414
weblogic.management.configuration.SNMPLogFilterMBean	2-416
weblogic.management.configuration.SNMPProxyMBean	2-418
weblogic.management.configuration.SNMPStringMonitorMBean	2-420
weblogic.management.configuration.SNMPTrapDestinationMBean	2-423
weblogic.management.configuration.SSLMBean	2-425
weblogic.management.configuration.SecureModeMBean	2-430
weblogic.management.configuration.SecurityConfigurationMBean	2-432
weblogic.management.configuration.SelfTuningMBean.....	2-437
weblogic.management.configuration.ServerDebugMBean.....	2-439
weblogic.management.configuration.ServerFailureTriggerMBean	2-476
weblogic.management.configuration.ServerMBean.....	2-477
weblogic.management.configuration.ServerStartMBean	2-502
weblogic.management.configuration.ServerTemplateMBean	2-505
weblogic.management.configuration.ShutdownClassMBean	2-531
weblogic.management.configuration.SingleSignOnServicesMBean	2-532
weblogic.management.configuration.SingletonServiceMBean.....	2-540
weblogic.management.configuration.StartupClassMBean	2-542
weblogic.management.configuration.SubDeploymentMBean	2-544
weblogic.management.configuration.SystemComponentConfigurationMBean	2-546
weblogic.management.configuration.SystemComponentMBean	2-547
weblogic.management.configuration.SystemComponentStartMBean	2-549
weblogic.management.configuration.TransactionLogJDBCStoreMBean.....	2-551
weblogic.management.configuration.TriggerMBean.....	2-560
weblogic.management.configuration.VirtualHostMBean	2-561
weblogic.management.configuration.VirtualTargetMBean	2-566
weblogic.management.configuration.WLDFDataRetirementByAgeMBean	2-568
weblogic.management.configuration.WLDFServerDiagnosticMBean	2-570
weblogic.management.configuration.WLDFSystemResourceMBean	2-575
weblogic.management.configuration.WSReliableDeliveryPolicyMBean	2-577
weblogic.management.configuration.WTCExportMBean.....	2-579
weblogic.management.configuration.WTCImportMBean	2-581
weblogic.management.configuration.WTCLocalTuxDomMBean	2-582
weblogic.management.configuration.WTCPasswordMBean	2-589
weblogic.management.configuration.WTCRemoteTuxDomMBean	2-591
weblogic.management.configuration.WTCResourcesMBean.....	2-597
weblogic.management.configuration.WTCServerMBean	2-599

weblogic.management.configuration.WTCtBridgeGlobalMBean.....	2-601
weblogic.management.configuration.WTCtBridgeRedirectMBean.....	2-605
weblogic.management.configuration.WebAppContainerMBean.....	2-607
weblogic.management.configuration.WebServerLogMBean.....	2-613
weblogic.management.configuration.WebServerMBean.....	2-616
weblogic.management.configuration.WebServiceBufferingMBean.....	2-621
weblogic.management.configuration.WebServiceLogicalStoreMBean.....	2-622
weblogic.management.configuration.WebServiceMBean.....	2-623
weblogic.management.configuration.WebServicePersistenceMBean.....	2-625
weblogic.management.configuration.WebServicePhysicalStoreMBean.....	2-626
weblogic.management.configuration.WebServiceReliabilityMBean.....	2-627
weblogic.management.configuration.WebServiceRequestBufferingQueueMBean....	2-629
weblogic.management.configuration.WebServiceResponseBufferingQueueMBean..	2-630
weblogic.management.configuration.WebserviceCredentialProviderMBean.....	2-632
weblogic.management.configuration.WebserviceSecurityMBean.....	2-633
weblogic.management.configuration.WebserviceSecurityTokenMBean.....	2-634
weblogic.management.configuration.WebserviceTestpageMBean.....	2-636
weblogic.management.configuration.WebserviceTimestampMBean.....	2-637
weblogic.management.configuration.WebserviceTokenHandlerMBean.....	2-639
weblogic.management.configuration.WorkManagerMBean.....	2-640
weblogic.management.configuration.WorkManagerShutdownTriggerMBean.....	2-643
weblogic.management.configuration.XMLEntityCacheMBean.....	2-644
weblogic.management.configuration.XMLEntitySpecRegistryEntryMBean.....	2-645
weblogic.management.configuration.XMLParserSelectRegistryEntryMBean.....	2-647
weblogic.management.configuration.XMLRegistryMBean.....	2-650
weblogic.management.rest.bean.model.ChangeManager.....	2-653
weblogic.management.rest.bean.model.CurrentUser.....	2-654
weblogic.management.rest.bean.model.Version.....	2-654
weblogic.management.security.RDBMSSecurityStoreMBean.....	2-655
weblogic.management.security.RealmMBean.....	2-657
weblogic.management.security.audit.AuditorMBean.....	2-663
weblogic.management.security.authentication.AuthenticationProviderMBean.....	2-664
weblogic.management.security.authentication.PasswordValidatorMBean.....	2-665
weblogic.management.security.authentication.UserLockoutManagerMBean.....	2-666
weblogic.management.security.authorization.AdjudicatorMBean.....	2-667
weblogic.management.security.authorization.AuthorizerMBean.....	2-668
weblogic.management.security.authorization.RoleMapperMBean.....	2-669
weblogic.management.security.credentials.CredentialMapperMBean.....	2-669
weblogic.management.security.pk.CertPathProviderMBean.....	2-670

Preface

This preface describes the document accessibility features and conventions used in this guide, *RESTful Edit Reference for Oracle WebLogic Server*.

Documentation Accessibility

For information about Oracle's commitment to accessibility, visit the Oracle Accessibility Program website at <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=docacc>.

Access to Oracle Support

Oracle customers that have purchased support have access to electronic support through My Oracle Support. For information, visit <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=info> or visit <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=trs> if you are hearing impaired.

Conventions

The following text conventions are used in this document:

Convention	Meaning
boldface	Boldface type indicates graphical user interface elements associated with an action, or terms defined in text or the glossary.
<i>italic</i>	Italic type indicates book titles, emphasis, or placeholder variables for which you supply particular values.
monospace	Monospace type indicates commands within a paragraph, URLs, code in examples, text that appears on the screen, or text that you enter.

Resources

This documentation describes the Oracle WebLogic Server RESTful edit resources that are used to view and modify the domain configuration.

For a complete listing of the WLS REST reference documents and descriptions of their use, see *Administering Oracle WebLogic Server with RESTful Management Services*.

/management/weblogic

This resource is used to access the different versions of the resources in this domain.

The latest version is 12.2.1.3.0. The other versions, which are deprecated, are 12.2.1.0.0, 12.2.1.1.0, 12.2.1.2.0.

For future releases, `latest` always refers to the most recent release.

All new and non-deprecated MBean features are available in all versions. Any MBean features that were deprecated in a version will not be available in that version or later versions, but will still be available using earlier versions.

To always use the latest resources, use `latest` in the URLs. Note that this might require updating a client when moving to a newer version of WebLogic Server. To fix the version so that an update is not required, use `12.2.1.3.0` in the URLs.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.rest.bean.model.Version](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.rest.bean.model.Version](#) entities.

This method can return the following links:

- **uri=/management/weblogic rel=canonical**
This resource.
- **uri=/management/weblogic/12.2.1.3.0 rel=current**
Access the latest version of the WLS resources in the this domain.
- **uri=/management/weblogic rel=self**
This resource.

Example

Example 1 View the versions collection.

This example uses the GET method to display the version instances in this collection.

Example Request

```
curl -v \  
--user admin:admin123 \  
-H X-Requested-By:MyClient \  
-H Accept:application/json \  
-X GET http://localhost:7001/management/weblogic
```

Example Response

```
HTTP/1.1 200 OK
```

Response Body:

```
{  
  "links": [  
    {  
      "rel": "self",  
      "href": "http://localhost:7001/management/weblogic"  
    },  
    {  
      "rel": "canonical",  
      "href": "http://localhost:7001/management/weblogic"  
    },  
    {  
      "rel": "current",  
      "href": "http://localhost:7001/management/weblogic/12.2.1.3.0"  
    }  
  ],  
  "items": [  
    {
```

```
    "links": [
      {
        "rel": "self",
        "href":
"http://localhost:7001/management/weblogic/12.2.1.0.0"
      },
      {
        "rel": "canonical",
        "href":
"http://localhost:7001/management/weblogic/12.2.1.0.0"
      }
    ],
    "version": "12.2.1.0.0",
    "isLatest": false,
    "lifecycle": "deprecated"
  },
  {
    "links": [
      {
        "rel": "self",
        "href":
"http://localhost:7001/management/weblogic/12.2.1.1.0"
      },
      {
        "rel": "canonical",
        "href":
"http://localhost:7001/management/weblogic/12.2.1.1.0"
      }
    ],
    "version": "12.2.1.1.0",
    "isLatest": false,
    "lifecycle": "deprecated"
  },
  {
    "links": [
      {
        "rel": "self",
        "href":
"http://localhost:7001/management/weblogic/12.2.1.2.0"
      },
      {
        "rel": "canonical",
        "href":
"http://localhost:7001/management/weblogic/12.2.1.2.0"
      }
    ],
    "version": "12.2.1.2.0",
    "isLatest": false,
    "lifecycle": "deprecated"
  },
  {
    "links": [
      {
        "rel": "self",
        "href":
"http://localhost:7001/management/weblogic/12.2.1.3.0"
      },
      {
        "rel": "canonical",
        "href":
```

```
"http://localhost:7001/management/weblogic/12.2.1.3.0"  
  }  
  ],  
  "version": "12.2.1.3.0",  
  "isLatest": true,  
  "lifecycle": "active"  
  }  
  ]  
}
```

/management/weblogic/{version}

This resource describes the resource trees that are used to manage a WebLogic Server domain and its managed servers. The resource trees mimic the bean trees in WLST and allow you to view and edit configuration and monitor runtime behavior.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.rest.bean.model.Version](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.rest.bean.model.Version](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/currentUser](#) **rel**=currentUser
- **uri**=[/management/weblogic/{version}/domainConfig](#) **rel**=domainConfig
- **uri**=[/management/weblogic/{version}/domainRuntime](#) **rel**=domainRuntime
- **uri**=[/management/weblogic/{version}/edit](#) **rel**=edit
- **uri**=[/management/weblogic](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}](#) **rel**=self
This resource.
- **uri**=[/management/weblogic/{version}/serverConfig](#) **rel**=serverConfig
- **uri**=[/management/weblogic/{version}/serverRuntime](#) **rel**=serverRuntime

Example

Example 1 View the latest version.

This example uses the GET method to display the latest version.

Example Request

```
curl -v \
--user admin:admin123 \
-H X-Requested-By:MyClient \
-H Accept:application/json \
-X GET http://localhost:7001/management/weblogic/latest
```

Example Response

HTTP/1.1 200 OK

Response Body:

```
{
  "links": [
    {
      "rel": "parent",
      "href": "http://localhost:7001/management/weblogic"
    },
    {
```

```

        "rel": "self",
        "href": "http://localhost:7001/management/weblogic/latest"
    },
    {
        "rel": "canonical",
        "href": "http://localhost:7001/management/weblogic/latest"
    },
    {
        "rel": "edit",
        "href": "http://localhost:7001/management/weblogic/latest/edit"
    },
    {
        "rel": "domainConfig",
        "href":
"http://localhost:7001/management/weblogic/latest/domainConfig"
    },
    {
        "rel": "domainRuntime",
        "href":
"http://localhost:7001/management/weblogic/latest/domainRuntime"
    },
    {
        "rel": "serverRuntime",
        "href":
"http://localhost:7001/management/weblogic/latest/serverRuntime"
    },
    {
        "rel": "serverConfig",
        "href":
"http://localhost:7001/management/weblogic/latest/serverConfig"
    },
    {
        "rel": "currentUser",
        "href":
"http://localhost:7001/management/weblogic/latest/currentUser"
    }
],
"version": "12.2.1.3.0",
"isLatest": true,
"lifecycle": "active"
}

```

Example 2 View a specific version.

This example uses the GET method to display a specific version.

Example Request

```

curl -v \
--user admin:admin123 \
-H X-Requested-By:MyClient \
-H Accept:application/json \
-X GET http://localhost:7001/management/weblogic/12.2.1.3.0

```

Example Response

HTTP/1.1 200 OK

Response Body:

```

{
  "links": [

```



```
{
  "rel": "parent",
  "href": "http://localhost:7001/management/weblogic"
},
{
  "rel": "self",
  "href": "http://localhost:7001/management/weblogic/12.2.1.3.0"
},
{
  "rel": "canonical",
  "href": "http://localhost:7001/management/weblogic/12.2.1.3.0"
},
{
  "rel": "edit",
  "href": "http://localhost:7001/management/weblogic/12.2.1.3.0/edit"
},
{
  "rel": "domainConfig",
  "href":
"http://localhost:7001/management/weblogic/12.2.1.3.0/domainConfig"
},
{
  "rel": "domainRuntime",
  "href":
"http://localhost:7001/management/weblogic/12.2.1.3.0/domainRuntime"
},
{
  "rel": "serverRuntime",
  "href":
"http://localhost:7001/management/weblogic/12.2.1.3.0/serverRuntime"
},
{
  "rel": "serverConfig",
  "href":
"http://localhost:7001/management/weblogic/12.2.1.3.0/serverConfig"
},
{
  "rel": "currentUser",
  "href":
"http://localhost:7001/management/weblogic/12.2.1.3.0/currentUser"
}
],
"version": "12.2.1.3.0",
"isLatest": true,
"lifecycle": "active"
}
```

/management/weblogic/{version}/currentUser

This resource represents an authenticated user in the domain.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.rest.bean.model.CurrentUser](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.rest.bean.model.CurrentUser](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/currentUser](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/currentUser](#) **rel**=self
This resource.

Example

Example 1 Viewing the [weblogic.management.rest.bean.model.CurrentUser](#) Instance

This example uses the GET method to view this [weblogic.management.rest.bean.model.CurrentUser](#) instance.

Example Request

```
curl -v \  
--user admin:admin123 \  
-H X-Requested-By:MyClient \  
-H Accept:application/json \  
-X GET http://localhost:7001/management/weblogic/latest/currentUser
```

Example Response

```
HTTP/1.1 200 OK
```

```
Response Body:
```

```
{  
  "links": [  
    {  
      "rel": "parent",  
      "href": "http://localhost:7001/management/weblogic/latest"  
    },  
    {  
      "rel": "self",  
      "href":  
"http://localhost:7001/management/weblogic/latest/currentUser"  
    },  
    {  
      "rel": "canonical",  
      "href":  
"http://localhost:7001/management/weblogic/latest/currentUser"
```

```
    }  
  ],  
  "partitionId": "0",  
  "partitionName": "DOMAIN",  
  "user": "admin"  
}
```

/management/weblogic/{version}/edit

This resource is used to edit the WebLogic Server configuration.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.DomainMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.DomainMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/JDBCStoreCreateForm](#)
rel=JDBCStoreCreateForm
The create form resource for this resource's JDBCStores collection resource.
- **uri**=[/management/weblogic/{version}/edit/JDBCStores](#) **rel**=JDBCStores
This resource's JDBCStores collection resource.
- **uri**=[/management/weblogic/{version}/edit/JDBCSystemResourceCreateForm](#)
rel=JDBCSystemResourceCreateForm
The create form resource for this resource's JDBCSystemResources collection resource.
- **uri**=[/management/weblogic/{version}/edit/JDBCSystemResources](#)
rel=JDBCSystemResources
This resource's JDBCSystemResources collection resource.
- **uri**=[/management/weblogic/{version}/edit/JMSBridgeDestinationCreateForm](#)
rel=JMSBridgeDestinationCreateForm
The create form resource for this resource's JMSBridgeDestinations collection resource.
- **uri**=[/management/weblogic/{version}/edit/JMSBridgeDestinations](#)
rel=JMSBridgeDestinations
This resource's JMSBridgeDestinations collection resource.
- **uri**=[/management/weblogic/{version}/edit/JMSInteropModuleCreateForm](#)
rel=JMSInteropModuleCreateForm
The create form resource for this resource's JMSInteropModules collection resource.
- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules](#)
rel=JMSInteropModules
This resource's JMSInteropModules collection resource.
- **uri**=[/management/weblogic/{version}/edit/JMSServerCreateForm](#)
rel=JMSServerCreateForm
The create form resource for this resource's JMSServers collection resource.
- **uri**=[/management/weblogic/{version}/edit/JMSServers](#) **rel**=JMSServers
This resource's JMSServers collection resource.

- **uri=/management/weblogic/{version}/edit/JMSSystemResourceCreateForm**
rel=JMSSystemResourceCreateForm
The create form resource for this resource's JMSSystemResources collection resource.
- **uri=/management/weblogic/{version}/edit/JMSSystemResources**
rel=JMSSystemResources
This resource's JMSSystemResources collection resource.
- **uri=/management/weblogic/{version}/edit/JMX** **rel=JMX**
This resource's JMX singleton resource.
- **uri=/management/weblogic/{version}/edit/JPA** **rel=JPA**
This resource's JPA singleton resource.
- **uri=/management/weblogic/{version}/edit/JTA** **rel=JTA**
This resource's JTA singleton resource.
- **uri=/management/weblogic/{version}/edit/SAFAgentCreateForm**
rel=SAFAgentCreateForm
The create form resource for this resource's SAFAgents collection resource.
- **uri=/management/weblogic/{version}/edit/SAFAgents** **rel=SAFAgents**
This resource's SAFAgents collection resource.
- **uri=/management/weblogic/{version}/edit/SNMPAgent** **rel=SNMPAgent**
This resource's SNMPAgent singleton resource.
- **uri=/management/weblogic/{version}/edit/SNMPAgentDeploymentCreateForm**
rel=SNMPAgentDeploymentCreateForm
The create form resource for this resource's SNMPAgentDeployments collection resource.
- **uri=/management/weblogic/{version}/edit/SNMPAgentDeployments**
rel=SNMPAgentDeployments
This resource's SNMPAgentDeployments collection resource.
- **uri=/management/weblogic/{version}/edit/WLDFSystemResourceCreateForm**
rel=WLDFSystemResourceCreateForm
The create form resource for this resource's WLDFSystemResources collection resource.
- **uri=/management/weblogic/{version}/edit/WLDFSystemResources**
rel=WLDFSystemResources
This resource's WLDFSystemResources collection resource.
- **uri=/management/weblogic/{version}/edit/WSReliableDeliveryPolicies**
rel=WSReliableDeliveryPolicies
This resource's WSReliableDeliveryPolicies collection resource.
- **uri=/management/weblogic/{version}/edit/WSReliableDeliveryPolicyCreateForm**
rel=WSReliableDeliveryPolicyCreateForm
The create form resource for this resource's WSReliableDeliveryPolicies collection resource.

- **uri**=[/management/weblogic/{version}/edit/WTCServerCreateForm](#)
rel=WTCServerCreateForm
The create form resource for this resource's WTCServers collection resource.
- **uri**=[/management/weblogic/{version}/edit/WTCServers](#) **rel**=WTCServers
This resource's WTCServers collection resource.
- **uri**=[/management/weblogic/{version}/edit/XMLEntityCacheCreateForm](#)
rel=XMLEntityCacheCreateForm
The create form resource for this resource's XMLEntityCaches collection resource.
- **uri**=[/management/weblogic/{version}/edit/XMLEntityCaches](#)
rel=XMLEntityCaches
This resource's XMLEntityCaches collection resource.
- **uri**=[/management/weblogic/{version}/edit/XMLRegistries](#) **rel**=XMLRegistries
This resource's XMLRegistries collection resource.
- **uri**=[/management/weblogic/{version}/edit/XMLRegistryCreateForm](#)
rel=XMLRegistryCreateForm
The create form resource for this resource's XMLRegistries collection resource.
- **uri**=[/management/weblogic/{version}/edit/arePartitionsPresent](#) **rel**=action
title=arePartitionsPresent
This resource's arePartitionsPresent action resource.
- **uri**=[/management/weblogic/{version}/edit/findConfigBeansWithTags](#)
rel=action **title**=findConfigBeansWithTags
This resource's findConfigBeansWithTags action resource.
- **uri**=[/management/weblogic/{version}/edit/findPartitionByID](#) **rel**=action
title=findPartitionByID
This resource's findPartitionByID action resource.
- **uri**=[/management/weblogic/{version}/edit/listTags](#) **rel**=action **title**=listTags
This resource's listTags action resource.
- **uri**=[/management/weblogic/{version}/edit/lookupSystemResource](#) **rel**=action
title=lookupSystemResource
This resource's lookupSystemResource action resource.
- **uri**=[/management/weblogic/{version}/edit/lookupTarget](#) **rel**=action
title=lookupTarget
This resource's lookupTarget action resource.
- **uri**=[/management/weblogic/{version}/edit/adminConsole](#) **rel**=adminConsole
This resource's adminConsole singleton resource.
- **uri**=[/management/weblogic/{version}/edit/appDeployments](#)
rel=appDeployments
This resource's appDeployments collection resource.
- **uri**=[/management/weblogic/{version}/edit/batchConfig](#) **rel**=batchConfig
This resource's batchConfig singleton resource.

- **uri=/management/weblogic/{version}/edit rel=canonical**
This resource.
- **uri=/management/weblogic/{version}/edit/cdiContainer rel=cdiContainer**
This resource's cdiContainer singleton resource.
- **uri=/management/weblogic/{version}/edit/changeManager rel=changeManager**
This resource's changeManager resource.
- **uri=/management/weblogic/{version}/edit/clustercreateForm rel=clustercreateForm**
The create form resource for this resource's clusters collection resource.
- **uri=/management/weblogic/{version}/edit/clusters rel=clusters**
This resource's clusters collection resource.
- **uri=/management/weblogic/{version}/edit/coherenceClusterSystemResourceCreateForm rel=coherenceClusterSystemResourceCreateForm**
The create form resource for this resource's coherenceClusterSystemResources collection resource.
- **uri=/management/weblogic/{version}/edit/coherenceClusterSystemResources rel=coherenceClusterSystemResources**
This resource's coherenceClusterSystemResources collection resource.
- **uri=/management/weblogic/{version}/edit/coherenceManagementClustercreateForm rel=coherenceManagementClustercreateForm**
The create form resource for this resource's coherenceManagementClusters collection resource.
- **uri=/management/weblogic/{version}/edit/coherenceManagementClusters rel=coherenceManagementClusters**
This resource's coherenceManagementClusters collection resource.
- **uri=/management/weblogic/{version}/edit/coherenceServercreateForm rel=coherenceServercreateForm**
The create form resource for this resource's coherenceServers collection resource.
- **uri=/management/weblogic/{version}/edit/coherenceServers rel=coherenceServers**
This resource's coherenceServers collection resource.
- **uri=/management/weblogic/{version}/edit/configurationProperties rel=configurationProperties**
This resource's configurationProperties collection resource.
- **uri=/management/weblogic/{version}/edit/configurationPropertycreateForm rel=configurationPropertycreateForm**
The create form resource for this resource's configurationProperties collection resource.
- **uri=/management/weblogic/{version}/edit/customResourcecreateForm rel=customResourcecreateForm**
The create form resource for this resource's customResources collection resource.

- **uri**=/management/weblogic/{version}/edit/customResources
rel=customResources
This resource's customResources collection resource.
- **uri**=/management/weblogic/{version}/edit/debugPatches **rel**=debugPatches
This resource's debugPatches singleton resource.
- **uri**=/management/weblogic/{version}/edit/deploymentConfiguration
rel=deploymentConfiguration
This resource's deploymentConfiguration singleton resource.
- **uri**=/management/weblogic/{version}/edit/embeddedLDAP
rel=embeddedLDAP
This resource's embeddedLDAP singleton resource.
- **uri**=/management/weblogic/{version}/edit/fileStoreCreateForm
rel=fileStoreCreateForm
The create form resource for this resource's fileStores collection resource.
- **uri**=/management/weblogic/{version}/edit/fileStores **rel**=fileStores
This resource's fileStores collection resource.
- **uri**=/management/weblogic/{version}/edit/foreignJNDIProviderCreateForm
rel=foreignJNDIProviderCreateForm
The create form resource for this resource's foreignJNDIProviders collection resource.
- **uri**=/management/weblogic/{version}/edit/foreignJNDIProviders
rel=foreignJNDIProviders
This resource's foreignJNDIProviders collection resource.
- **uri**=/management/weblogic/{version}/edit/interceptors **rel**=interceptors
This resource's interceptors singleton resource.
- **uri**=/management/weblogic/{version}/edit/internalAppDeployments
rel=internalAppDeployments
This resource's internalAppDeployments collection resource.
- **uri**=/management/weblogic/{version}/edit/internalLibraries
rel=internalLibraries
This resource's internalLibraries collection resource.
- **uri**=/management/weblogic/{version}/edit/joltConnectionPoolCreateForm
rel=joltConnectionPoolCreateForm
The create form resource for this resource's joltConnectionPools collection resource.
- **uri**=/management/weblogic/{version}/edit/joltConnectionPools
rel=joltConnectionPools
This resource's joltConnectionPools collection resource.
- **uri**=/management/weblogic/{version}/edit/libraries **rel**=libraries
This resource's libraries collection resource.

- **uri**=/management/weblogic/{version}/edit/lifecycleManagerConfig
rel=lifecycleManagerConfig

This resource's lifecycleManagerConfig singleton resource.
- **uri**=/management/weblogic/{version}/edit/log **rel**=log

This resource's log singleton resource.
- **uri**=/management/weblogic/{version}/edit/logFilterCreateForm
rel=logFilterCreateForm

The create form resource for this resource's logFilters collection resource.
- **uri**=/management/weblogic/{version}/edit/logFilters **rel**=logFilters

This resource's logFilters collection resource.
- **uri**=/management/weblogic/{version}/edit/machineCreateForm
rel=machineCreateForm

The create form resource for this resource's machines collection resource.
- **uri**=/management/weblogic/{version}/edit/machines **rel**=machines

This resource's machines collection resource.
- **uri**=/management/weblogic/{version}/edit/mailSessionCreateForm
rel=mailSessionCreateForm

The create form resource for this resource's mailSessions collection resource.
- **uri**=/management/weblogic/{version}/edit/mailSessions **rel**=mailSessions

This resource's mailSessions collection resource.
- **uri**=/management/weblogic/{version}/edit/managedExecutorServiceCreateForm
rel=managedExecutorServiceCreateForm

The create form resource for this resource's managedExecutorServices collection resource.
- **uri**=/management/weblogic/{version}/edit/managedExecutorServiceTemplateCreateForm **rel**=managedExecutorServiceTemplateCreateForm

The create form resource for this resource's managedExecutorServiceTemplates collection resource.
- **uri**=/management/weblogic/{version}/edit/managedExecutorServiceTemplates
rel=managedExecutorServiceTemplates

This resource's managedExecutorServiceTemplates collection resource.
- **uri**=/management/weblogic/{version}/edit/managedExecutorServices
rel=managedExecutorServices

This resource's managedExecutorServices collection resource.
- **uri**=/management/weblogic/{version}/edit/managedScheduledExecutorServiceCreateForm **rel**=managedScheduledExecutorServiceCreateForm

The create form resource for this resource's managedScheduledExecutorServices collection resource.
- **uri**=/management/weblogic/{version}/edit/managedScheduledExecutorServiceTemplateCreateForm **rel**=managedScheduledExecutorServiceTemplateCreateForm

The create form resource for this resource's managedScheduledExecutorServiceTemplates collection resource.

- **uri**=/management/weblogic/{version}/edit/managedScheduledExecutorServiceTemplates **rel**=managedScheduledExecutorServiceTemplates
This resource's managedScheduledExecutorServiceTemplates collection resource.
- **uri**=/management/weblogic/{version}/edit/managedScheduledExecutorServices **rel**=managedScheduledExecutorServices
This resource's managedScheduledExecutorServices collection resource.
- **uri**=/management/weblogic/{version}/edit/managedThreadFactories **rel**=managedThreadFactories
This resource's managedThreadFactories collection resource.
- **uri**=/management/weblogic/{version}/edit/managedThreadFactoryCreateForm **rel**=managedThreadFactoryCreateForm
The create form resource for this resource's managedThreadFactories collection resource.
- **uri**=/management/weblogic/{version}/edit/managedThreadFactoryTemplateCreateForm **rel**=managedThreadFactoryTemplateCreateForm
The create form resource for this resource's managedThreadFactoryTemplates collection resource.
- **uri**=/management/weblogic/{version}/edit/managedThreadFactoryTemplates **rel**=managedThreadFactoryTemplates
This resource's managedThreadFactoryTemplates collection resource.
- **uri**=/management/weblogic/{version}/edit/messagingBridgeCreateForm **rel**=messagingBridgeCreateForm
The create form resource for this resource's messagingBridges collection resource.
- **uri**=/management/weblogic/{version}/edit/messagingBridges **rel**=messagingBridges
This resource's messagingBridges collection resource.
- **uri**=/management/weblogic/{version}/edit/migratableTargetCreateForm **rel**=migratableTargetCreateForm
The create form resource for this resource's migratableTargets collection resource.
- **uri**=/management/weblogic/{version}/edit/migratableTargets **rel**=migratableTargets
This resource's migratableTargets collection resource.
- **uri**=/management/weblogic/{version}/edit/optionalFeatureDeployment **rel**=optionalFeatureDeployment
This resource's optionalFeatureDeployment singleton resource.
- **uri**=/management/weblogic/{version}/edit/osgiFrameworkCreateForm **rel**=osgiFrameworkCreateForm
The create form resource for this resource's osgiFrameworks collection resource.
- **uri**=/management/weblogic/{version}/edit/osgiFrameworks **rel**=osgiFrameworks
This resource's osgiFrameworks collection resource.
- **uri**=/management/weblogic/{version} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/partitionCreateForm
rel=partitionCreateForm

The create form resource for this resource's partitions collection resource.

- **uri**=/management/weblogic/{version}/edit/partitionWorkManagerCreateForm
rel=partitionWorkManagerCreateForm

The create form resource for this resource's partitionWorkManagers collection resource.

- **uri**=/management/weblogic/{version}/edit/partitionWorkManagers
rel=partitionWorkManagers

This resource's partitionWorkManagers collection resource.

- **uri**=/management/weblogic/{version}/edit/partitions **rel**=partitions

This resource's partitions collection resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupCreateForm
rel=resourceGroupCreateForm

The create form resource for this resource's resourceGroups collection resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplateCreateForm
rel=resourceGroupTemplateCreateForm

The create form resource for this resource's resourceGroupTemplates collection resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates
rel=resourceGroupTemplates

This resource's resourceGroupTemplates collection resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups **rel**=resourceGroups

This resource's resourceGroups collection resource.

- **uri**=/management/weblogic/{version}/edit/resourceManagement
rel=resourceManagement

This resource's resourceManagement singleton resource.

- **uri**=/management/weblogic/{version}/edit/restfulManagementServices
rel=restfulManagementServices

This resource's restfulManagementServices singleton resource.

- **uri**=/management/weblogic/{version}/edit/search **rel**=search

This resource's search resource.

- **uri**=/management/weblogic/{version}/edit/securityConfiguration
rel=securityConfiguration

This resource's securityConfiguration singleton resource.

- **uri**=/management/weblogic/{version}/edit **rel**=self

This resource.

- **uri**=/management/weblogic/{version}/edit/selfTuning **rel**=selfTuning

This resource's selfTuning singleton resource.

- **uri**=/management/weblogic/{version}/edit/serverCreateForm
rel=serverCreateForm
The create form resource for this resource's servers collection resource.
- **uri**=/management/weblogic/{version}/edit/serverTemplateCreateForm
rel=serverTemplateCreateForm
The create form resource for this resource's serverTemplates collection resource.
- **uri**=/management/weblogic/{version}/edit/serverTemplates
rel=serverTemplates
This resource's serverTemplates collection resource.
- **uri**=/management/weblogic/{version}/edit/servers **rel**=servers
This resource's servers collection resource.
- **uri**=/management/weblogic/{version}/edit/shutdownClassCreateForm
rel=shutdownClassCreateForm
The create form resource for this resource's shutdownClasses collection resource.
- **uri**=/management/weblogic/{version}/edit/shutdownClasses
rel=shutdownClasses
This resource's shutdownClasses collection resource.
- **uri**=/management/weblogic/{version}/edit/singletonServiceCreateForm
rel=singletonServiceCreateForm
The create form resource for this resource's singletonServices collection resource.
- **uri**=/management/weblogic/{version}/edit/singletonServices
rel=singletonServices
This resource's singletonServices collection resource.
- **uri**=/management/weblogic/{version}/edit/startupClassCreateForm
rel=startupClassCreateForm
The create form resource for this resource's startupClasses collection resource.
- **uri**=/management/weblogic/{version}/edit/startupClasses **rel**=startupClasses
This resource's startupClasses collection resource.
- **uri**=/management/weblogic/{version}/edit/systemComponentConfigurationCreateForm **rel**=systemComponentConfigurationCreateForm
The create form resource for this resource's systemComponentConfigurations collection resource.
- **uri**=/management/weblogic/{version}/edit/systemComponentConfigurations
rel=systemComponentConfigurations
This resource's systemComponentConfigurations collection resource.
- **uri**=/management/weblogic/{version}/edit/systemComponentCreateForm
rel=systemComponentCreateForm
The create form resource for this resource's systemComponents collection resource.
- **uri**=/management/weblogic/{version}/edit/systemComponents
rel=systemComponents
This resource's systemComponents collection resource.

- **uri**=/management/weblogic/{version}/edit/virtualHostCreateForm
rel=virtualHostCreateForm
The create form resource for this resource's virtualHosts collection resource.
- **uri**=/management/weblogic/{version}/edit/virtualHosts **rel**=virtualHosts
This resource's virtualHosts collection resource.
- **uri**=/management/weblogic/{version}/edit/virtualTargetCreateForm
rel=virtualTargetCreateForm
The create form resource for this resource's virtualTargets collection resource.
- **uri**=/management/weblogic/{version}/edit/virtualTargets **rel**=virtualTargets
This resource's virtualTargets collection resource.
- **uri**=/management/weblogic/{version}/edit/webAppContainer
rel=webAppContainer
This resource's webAppContainer singleton resource.
- **uri**=/management/weblogic/{version}/edit/webserviceSecurities
rel=webserviceSecurities
This resource's webserviceSecurities collection resource.
- **uri**=/management/weblogic/{version}/edit/webserviceSecurityCreateForm
rel=webserviceSecurityCreateForm
The create form resource for this resource's webserviceSecurities collection resource.
- **uri**=/management/weblogic/{version}/edit/webserviceTestpage
rel=webserviceTestpage
This resource's webserviceTestpage singleton resource.

Example

Example 1 Viewing the weblogic.management.configuration.DomainMBean Instance

This example uses the GET method to view this weblogic.management.configuration.DomainMBean instance.

Example Request

```
curl -v \
--user admin:admin123 \
-H X-Requested-By:MyClient \
-H Accept:application/json \
-X GET
http://localhost:7001/management/weblogic/latest/edit?fields=administrationProtocol,productionModeEnabled&links=self
```

Example Response

HTTP/1.1 200 OK

Response Body:

```
{
  "links": [{
    "rel": "self",
    "href": "http://localhost:7001/management/weblogic/latest/edit"
```

```
  },  
  "administrationProtocol": "t3s",  
  "productionModeEnabled": false  
}
```


POST

Update this [weblogic.management.configuration.DomainMBean](#) instance.

Request Body

Must contain a [weblogic.management.configuration.DomainMBean](#) entity.

/management/weblogic/{version}/edit/adminConsole

This resource manages a [weblogic.management.configuration.AdminConsoleMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.AdminConsoleMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.AdminConsoleMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/adminConsole](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/adminConsole](#) **rel**=self
This resource.

POST

POST

Update this [weblogic.management.configuration.AdminConsoleMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.AdminConsoleMBean](#) entity.

/management/weblogic/{version}/edit/appDeployments

This resource manages a collection of [weblogic.management.configuration.AppDeploymentMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.AppDeploymentMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.AppDeploymentMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/appDeployments](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/appDeployments](#) **rel**=self
This resource.

POST

The resource supports the following methods:

- [POST accepting application/json](#)
- [POST accepting multipart/form-data](#)

POST accepting application/json

This resource deploys is used to deploy applications that are already on the administration server. The application must be a supported package type (for example, an EAR or WAR module).

This method supports both asynchronous and best effort synchronous invocations. The behavior is controlled by the 'Prefer' header. See [About Synchronous and Asynchronous Operations](#).

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.AppDeploymentMBean](#) entity.

To deploy an application you must provide the name of the application, the path to the source of the deployable unit on the administration server, and the targets to which the application will be deployed.

If the source path is relative, it is resolved relative to *InstallDir/app* if *InstallDir* is not null; otherwise, it is resolved relative to the domain root.

Example

Example 1 Synchronously Create the weblogic.management.configuration.AppDeploymentMBean Instance

This example uses the POST method to synchronously create a new [weblogic.management.configuration.AppDeploymentMBean](#) instance in this collection.

Example Request

```
curl -v \
--user admin:admin123 \
-H X-Requested-By:MyClient \
-H Accept:application/json \
-H Content-Type:application/json \
-d "{
  name: 'fairShare',
  sourcePath: '/deployments/fairShare.war',
  targets: [
    { identity: [ 'servers', 'AdminServer' ] },
    { identity: [ 'clusters', 'Cluster-0' ] }
  ]
}" \
-X POST
http://localhost:7001/management/weblogic/latest/edit/appDeployments?links=job,abort&fields=completed,progress,error,state,operationType,applicationName
```

Example Response

HTTP/1.1 201 Created

Location:

<http://localhost:7001/management/weblogic/latest/edit/appDeployments/fairShare>

Response Body:

```
{
  "links": [{
    "rel": "job",
    "href":
"http://localhost:7001/management/weblogic/latest/domainRuntime/deploymentManager
/deploymentProgressObjects/fairShare"
  }],
  "operationType": 3,
  "state": "STATE_COMPLETED",
  "applicationName": "fairShare",
  "progress": "success",
  "completed": true
}
```

Example 2 Asynchronously Create the `weblogic.management.configuration.AppDeploymentMBean` Instance

This example uses the POST method to asynchronously create a new `weblogic.management.configuration.AppDeploymentMBean` instance in this collection.

Example Request

```
curl -v \
--user admin:admin123 \
-H X-Requested-By:MyClient \
-H Accept:application/json \
-H Content-Type:application/json \
-d "{
  name: 'fairShare',
  sourcePath: '/deployments/fairShare.war',
  targets: [
    { identity: [ 'servers', 'AdminServer' ] },
    { identity: [ 'clusters', 'Cluster-0' ] }
  ]
}" \
-H "Prefer:respond-async" \
-X POST
http://localhost:7001/management/weblogic/latest/edit/appDeployments?links=job,abort&fields=completed,progress,error,state,operationType,applicationName
```

Example Response

HTTP/1.1 202 Accepted

Location:

<http://localhost:7001/management/weblogic/latest/domainRuntime/deploymentManager/deploymentProgressObjects/fairShare>

Response Body:

```
{
  "links": [{
```



```

        "rel": "job",
        "href":
"http://localhost:7001/management/weblogic/latest/domainRuntime/deploymentManager
/deploymentProgressObjects/fairShare"
    }],
    "operationType": 3,
    "state": "STATE_RUNNING",
    "applicationName": "fairShare",
    "progress": "processing",
    "completed": false
}

```

POST accepting multipart/form-data

Use the multi-part form to upload an application from the client to the server and then deploy it.

- `sourcePath`: the deployment to upload (required)
- `planPath`: the deployment plan to upload (optional)
- `model`: `JSONObject` containing an `AppDeploymentMBean` entity that contains the rest of the deployment information (however, deployment/plan information is ignored) (required)

This method supports both asynchronous and best effort synchronous invocations. The behavior is controlled by the 'Prefer' header. See About Synchronous and Asynchronous Operations.

Roles

Admin, Deployer

Request Body

Use the multi-part form to deploy an application.

- `sourcePath`: the deployment to upload (required)
- `planPath`: the deployment plan to upload (optional)
- `model`: `JSONObject` containing an `AppDeploymentMBean` entity that contains the rest of the deployment information. However, deployment/plan information is ignored. (required)

Example

Example 1 Synchronously Create the `weblogic.management.configuration.AppDeploymentMBean` Instance

This example uses the POST method to synchronously create a new `weblogic.management.configuration.AppDeploymentMBean` instance in this collection.

Example Request

```

curl -v \
--user admin:admin123 \
-H X-Requested-By:MyClient \
-H Accept:application/json \
-H Content-Type:multipart/form-data \

```

```
-F "model={
  name: 'myapp',
  targets: [ { identity: [ 'servers', 'AdminServer' ] } ]
}" \
-F "sourcePath=@/deployments/MyApp/app/MyApp.ear" \
-X POST
http://localhost:7001/management/weblogic/latest/edit/appDeployments?links=job,abort&fields=completed,progress,error,state,operationType,applicationName
```

Example Response

HTTP/1.1 100 Continue HTTP/1.1 201 Created

Location:

http://localhost:7001/management/weblogic/latest/edit/appDeployments/myapp

Response Body:

```
{
  "links": [{
    "rel": "job",
    "href":
"http://localhost:7001/management/weblogic/latest/domainRuntime/deploymentManager
/deploymentProgressObjects/myapp"
  }],
  "operationType": 3,
  "state": "STATE_COMPLETED",
  "applicationName": "myapp",
  "progress": "success",
  "completed": true
}
```

Example 2 Asynchronously Create the weblogic.management.configuration.AppDeploymentMBean Instance

This example uses the POST method to asynchronously create a new weblogic.management.configuration.AppDeploymentMBean instance in this collection.

Example Request

```
curl -v \
--user admin:admin123 \
-H X-Requested-By:MyClient \
-H Accept:application/json \
-H Content-Type:multipart/form-data \
-F "model={
  name: 'myapp',
  targets: [ { identity: [ 'servers', 'AdminServer' ] } ]
}" \
-F "sourcePath=@/deployments/MyApp/app/MyApp.ear" \
-H "Prefer:respond-async" \
-X POST
http://localhost:7001/management/weblogic/latest/edit/appDeployments?links=job,abort&fields=completed,progress,error,state,operationType,applicationName
```

Example Response

HTTP/1.1 100 Continue HTTP/1.1 202 Accepted

Location:

http://localhost:7001/management/weblogic/latest/domainRuntime/deploymentManager/d

ploymentProgressObjects/myapp

Response Body:

```
{
  "links": [{
    "rel": "job",
    "href":
"http://localhost:7001/management/weblogic/latest/domainRuntime/deploymentManager
/deploymentProgressObjects/myapp"
  }],
  "operationType": 3,
  "state": "STATE_RUNNING",
  "applicationName": "myapp",
  "progress": "processing",
  "completed": false
}
```

/management/weblogic/{version}/edit/appDeployments/{name}

This resource manages a [weblogic.management.configuration.AppDeploymentMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Undeploy an application.

This method supports both asynchronous and best effort synchronous invocations. The behavior is controlled by the 'Prefer' header. See About Synchronous and Asynchronous Operations.

Roles

Admin, Deployer

Example

Example 1 Synchronously Delete the weblogic.management.configuration.AppDeploymentMBean Instance

This example uses the DELETE method to synchronously remove a weblogic.management.configuration.AppDeploymentMBean instance.

Example Request

```
curl -v \  
--user admin:admin123 \  
-H X-Requested-By:MyClient \  
-H Accept:application/json \  
-X DELETE  
http://localhost:7001/management/weblogic/latest/edit/appDeployments/fairShare?links=job,abort&fields=completed,progress,error,state,operationType,applicationName
```

Example Response

HTTP/1.1 200 OK

Response Body:

```
{  
  "links": [{  
    "rel": "job",  
    "href":  
"http://localhost:7001/management/weblogic/latest/domainRuntime/deploymentManager/  
deploymentProgressObjects/fairShare"  
  }],  
  "operationType": 5,  
  "state": "STATE_COMPLETED",  
  "applicationName": "fairShare",  
  "progress": "success",  
  "completed": true  
}
```

Example 2 Asynchronously Delete the weblogic.management.configuration.AppDeploymentMBean Instance

This example uses the DELETE method to asynchronously remove a weblogic.management.configuration.AppDeploymentMBean instance.

Example Request

```
curl -v \  
--user admin:admin123 \  
-H X-Requested-By:MyClient \  
-X DELETE
```

DELETE

```
-H Accept:application/json \  
-H "Prefer:respond-async" \  
-X DELETE  
http://localhost:7001/management/weblogic/latest/edit/appDeployments/fairShare?links=job,abort&fields=completed,progress,error,state,operationType,applicationName
```

Example Response

HTTP/1.1 202 Accepted

Location:

http://localhost:7001/management/weblogic/latest/domainRuntime/deploymentManager/deploymentProgressObjects/fairShare

Response Body:

```
{  
  "links": [{  
    "rel": "job",  
    "href":  
"http://localhost:7001/management/weblogic/latest/domainRuntime/deploymentManager/  
/deploymentProgressObjects/fairShare"  
  }],  
  "operationType": 5,  
  "state": "STATE_RUNNING",  
  "applicationName": "fairShare",  
  "progress": "processing",  
  "completed": false  
}
```

GET

Get this [weblogic.management.configuration.AppDeploymentMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.AppDeploymentMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/appDeployments/{name}/createPlan
rel=action **title**=createPlan
This resource's createPlan action resource.
- **uri**=/management/weblogic/{version}/edit/appDeployments/{name}
rel=canonical
This resource.
- **uri**=/management/weblogic/{version}/edit/appDeployments **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/edit/appDeployments/{name}/redeploy
rel=redeploy
This resource's redeploy resource.
- **uri**=/management/weblogic/{version}/edit/appDeployments/{name} **rel**=self
This resource.
- **uri**=/management/weblogic/{version}/edit/appDeployments/{name}/subDeploymentCreateForm **rel**=subDeploymentCreateForm
The create form resource for this resource's subDeployments collection resource.
- **uri**=/management/weblogic/{version}/edit/appDeployments/{name}/subDeployments **rel**=subDeployments
This resource's subDeployments collection resource.
- **uri**=/management/weblogic/{version}/edit/appDeployments/{name}/update
rel=update
This resource's update resource.

Example

Example 1 Viewing the [weblogic.management.configuration.AppDeploymentMBean](#) Instance

This example uses the GET method to view this [weblogic.management.configuration.AppDeploymentMBean](#) instance.

Example Request

```
curl -v \  
--user admin:admin123 \  
-H X-Requested-By:MyClient \  

```

```
-H Accept:application/json \  
-X GET  
http://localhost:7001/management/weblogic/latest/edit/appDeployments/fairShare?links=none&fields=name,versionIdentifier,targets
```

Example Response

HTTP/1.1 200 OK

Response Body:

```
{  
  "versionIdentifier": null,  
  "name": "fairShare",  
  "targets": [  
    {"identity": [  
      "servers",  
      "AdminServer"  
    ]},  
    {"identity": [  
      "clusters",  
      "Cluster-0"  
    ]}  
  ]  
}
```


POST

Update this [weblogic.management.configuration.AppDeploymentMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.AppDeploymentMBean](#) entity.

/management/weblogic/{version}/edit/appDeployments/{name}/createPlan

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

POST

Create a deployment plan in the specified directory.

Roles

Admin, Deployer

Request Body

Must contain a JSON object with the following fields:

planPath

planPath

Type: string

Response Body

Contains a JSON object with a string return field.

POST

Create a deployment plan in a default directory

Roles

Admin, Deployer

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/edit/appDeployments/{name}/redeploy

The resource supports the following methods:

- [POST](#)

POST

Use the multi-part form to redeploy this application.

- `sourcePath`: the deployment to upload (required)
- `planPath`: the deployment plan to upload (optional)
- `model`: JSONObject containing an `AppDeploymentMBean` entity that contains the rest of the deployment information. However, `deployment/plan` information is ignored. (required)

This method supports both asynchronous and best effort synchronous invocations. The behavior is controlled by the 'Prefer' header. See [About Synchronous and Asynchronous Operations](#).

Roles

Admin, Deployer

Example

Example 1 Synchronously Invoke the redeploy Action

This example uses the POST method to synchronously invoke the redeploy action.

Example Request

```
curl -v \  
--user admin:admin123 \  
-H X-Requested-By:MyClient \  
-H Accept:application/json \  
-H Content-Type:application/json \  
-d "{}" \  
-X POST  
http://localhost:7001/management/weblogic/latest/edit/appDeployments/fairShare/red  
eploy?links=job,abort&fields=completed,progress,error,state,operationType,applicat  
ionName
```

Example Response

HTTP/1.1 200 OK

Response Body:

```
{  
  "links": [{  
    "rel": "job",  
    "href":  
"http://localhost:7001/management/weblogic/latest/domainRuntime/deploymentManager  
/deploymentProgressObjects/fairShare"  
  }],  
  "operationType": 4,  
  "state": "STATE_COMPLETED",  
  "applicationName": "fairShare",  
  "progress": "success",  
  "completed": true  
}
```

Example 2 Asynchronously Invoke the redeploy Action

This example uses the POST method to asynchronously invoke the redeploy action.

Example Request

```
curl -v \  
--user admin:admin123 \  
-H X-Requested-By:MyClient \  
-H Accept:application/json \  
-H Content-Type:application/json \  
-d "{}" \  
-H "Prefer:respond-async" \  
-X POST  
http://localhost:7001/management/weblogic/latest/edit/appDeployments/fairShare/red  
eploy?links=job,abort&fields=completed,progress,error,state,operationType,applicat  
ionName
```

Example Response

HTTP/1.1 202 Accepted

Location:

http://localhost:7001/management/weblogic/latest/domainRuntime/deploymentManager/d
eploymentProgressObjects/fairShare

Response Body:

```
{  
  "links": [{  
    "rel": "job",  
    "href":  
"http://localhost:7001/management/weblogic/latest/domainRuntime/deploymentManager  
/deploymentProgressObjects/fairShare"  
  }],  
  "operationType": 4,  
  "state": "STATE_RUNNING",  
  "applicationName": "fairShare",  
  "progress": "processing",  
  "completed": false  
}
```

/management/weblogic/{version}/edit/appDeployments/{name}/subDeploymentCreateForm

This resource manages the create forms for the subDeployments collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.SubDeploymentMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the subDeployments collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/appDeployments/{name}/subDeploymentCreateForm](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/appDeployments/{name}/subDeployments](#) **rel**=create
The collection resource for this create form resource.
- **uri**=[/management/weblogic/{version}/edit/appDeployments/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/appDeployments/{name}/subDeploymentCreateForm](#) **rel**=self
This resource.

/management/weblogic/{version}/edit/appDeployments/{name}/subDeployments

This resource manages a collection of [weblogic.management.configuration.SubDeploymentMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.SubDeploymentMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.SubDeploymentMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/appDeployments/{name}/subDeployments](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/appDeployments/{name}/subDeploymentCreateForm](#) **rel**=create-form
The create form resource for this collection resource.
- **uri**=[/management/weblogic/{version}/edit/appDeployments/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/appDeployments/{name}/subDeployments](#) **rel**=self
This resource.

POST

Add a new [weblogic.management.configuration.SubDeploymentMBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

/management/weblogic/{version}/edit/appDeployments/{name}/subDeployments/{name}

This resource manages a [weblogic.management.configuration.SubDeploymentMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/appDeployments/{name}/subDeployments/{name}](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/appDeployments/{name}/subDeployments](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/appDeployments/{name}/subDeployments/{name}](#) **rel=self**

This resource.

- [uri=/management/weblogic/{version}/edit/appDeployments/{name}/subDeployments/{name}/subDeployments](#) **rel=subDeployments**

This resource's subDeployments collection resource.

POST

Update this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

/management/weblogic/{version}/edit/appDeployments/{name}/subDeployments/{name}/subDeployments

This resource manages a collection of [weblogic.management.configuration.SubDeploymentMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.configuration.SubDeploymentMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.SubDeploymentMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/appDeployments/{name}/subDeployments/{name}/subDeployments](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/appDeployments/{name}/subDeployments/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/appDeployments/{name}/subDeployments/{name}/subDeployments](#) **rel=self**
This resource.

/management/weblogic/{version}/edit/appDeployments/{name}/subDeployments/{name}/subDeployments/{name}

This resource manages a [weblogic.management.configuration.SubDeploymentMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/appDeployments/{name}/subDeployments/{name}/subDeployments/{name}](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/appDeployments/{name}/subDeployments/{name}/subDeployments](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/appDeployments/{name}/subDeployments/{name}/subDeployments/{name}](#) **rel=self**

This resource.

- [uri=/management/weblogic/{version}/edit/appDeployments/{name}/subDeployments/{name}/subDeployments/{name}/subDeployments](#) **rel=subDeployments**

This resource's subDeployments collection resource.

POST

Update this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

/management/weblogic/{version}/edit/appDeployments/{name}/update

The resource supports the following methods:

- [POST](#)

POST

Update this application.

This method supports both asynchronous and best effort synchronous invocations. The behavior is controlled by the 'Prefer' header. See [About Synchronous and Asynchronous Operations](#).

Roles

Admin, Deployer

/management/weblogic/{version}/edit/arePartitionsPresent

The resource supports the following methods:

- [POST](#)

POST

Specifies whether at least one partition has been configured.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/edit/batchConfig

This resource manages a [weblogic.management.configuration.BatchConfigMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.BatchConfigMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.BatchConfigMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/batchConfig](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/batchConfig](#) **rel**=self
This resource.

POST

Update this [weblogic.management.configuration.BatchConfigMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.BatchConfigMBean](#) entity.

/management/weblogic/{version}/edit/cdiContainer

This resource manages a [weblogic.management.configuration.CdiContainerMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.CdiContainerMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.CdiContainerMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/cdiContainer](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/cdiContainer](#) **rel**=self
This resource.

POST

Update this [weblogic.management.configuration.CdiContainerMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.CdiContainerMBean](#) entity.

/management/weblogic/{version}/edit/changeManager

The changeManager resource returns information about edit sessions. Use this resource to explicitly manage an edit session:

- Use the changeManager to start an edit session.
- Use other resources to make any number of configuration changes, such as configuring data sources and deploying applications.
- Use the changeManager to either cancel all the changes in the edit session or activate them.

This strategy batches all the changes together which is typically most useful in a production environment when a number of configuration changes need to be made together before they are ready to be exposed to clients.

With implicit edit sessions, instead of using the changeManager, just use other resources to change the configuration (for example, create a data source). Each REST call to change the configuration will start its own edit session, make the change, and then activate the change. This is useful for small tweaks to the configuration as typically performed in development environments.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.rest.bean.model.ChangeManager](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.rest.bean.model.ChangeManager](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/changeManager/activate](#)
rel=activate
- **uri**=[/management/weblogic/{version}/edit/changeManager/cancelEdit](#)
rel=cancelEdit
- **uri**=[/management/weblogic/{version}/edit/changeManager](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/changeManager/forceResolve](#)
rel=forceResolve
- **uri**=[/management/weblogic/{version}/edit](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/changeManager/safeResolve](#)
rel=safeResolve
- **uri**=[/management/weblogic/{version}/edit/changeManager](#) **rel**=self
This resource.
- **uri**=[/management/weblogic/{version}/edit/changeManager/startEdit](#)
rel=startEdit

/management/weblogic/{version}/edit/changeManager/activate

The resource supports the following methods:

- [POST](#)

POST

POST

This resource saves and activates the changes to the current edit session

Roles

Admin, Deployer

/management/weblogic/{version}/edit/changeManager/cancelEdit

The resource supports the following methods:

- [POST](#)

POST

POST

This resource cancels the current edit session.

Roles

Admin, Deployer

/management/weblogic/{version}/edit/changeManager/forceResolve

The resource supports the following methods:

- [POST](#)

POST

This edit session forcibly resolves all changes between the default edit session and the global configuration.

Roles

Admin, Deployer

/management/weblogic/{version}/edit/changeManager/safeResolve

The resource supports the following methods:

- [POST](#)

POST

This edit session resolves non-conflicting changes between the default edit session and the global configuration.

Roles

Admin, Deployer

/management/weblogic/{version}/edit/changeManager/startEdit

The resource supports the following methods:

- [POST](#)

POST

POST

This resource starts an edit session.

Roles

Admin, Deployer

/management/weblogic/{version}/edit/clustercreateForm

This resource manages the create forms for the clusters collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.ClusterMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the clusters collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ClusterMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/clustercreateForm](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/clusters](#) **rel**=create
The collection resource for this create form resource.
- **uri**=[/management/weblogic/{version}/edit](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/clustercreateForm](#) **rel**=self
This resource.

/management/weblogic/{version}/edit/clusters

This resource manages a collection of [weblogic.management.configuration.ClusterMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.ClusterMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.ClusterMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/clusters](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/clustercreateForm](#) **rel**=create-form
The create form resource for this collection resource.
- **uri**=[/management/weblogic/{version}/edit](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/clusters](#) **rel**=self
This resource.

POST

Add a new [weblogic.management.configuration.ClusterMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.ClusterMBean](#) entity.

/management/weblogic/{version}/edit/clusters/{name}

This resource manages a [weblogic.management.configuration.ClusterMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.ClusterMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.ClusterMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ClusterMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/clusters/{name}/JTACluster](#)
rel=JTACluster
This resource's JTACluster singleton resource.
- **uri**=[/management/weblogic/{version}/edit/clusters/{name}](#) **rel**=canonical
This resource.
- **rel**=coherenceClusterSystemResource
This resource's coherenceClusterSystemResource reference to a [weblogic.management.configuration.CoherenceClusterSystemResourceMBean](#) resource.
- **uri**=[/management/weblogic/{version}/edit/clusters/{name}/coherenceTier](#)
rel=coherenceTier
This resource's coherenceTier singleton resource.
- **rel**=dataSourceForAutomaticMigration
This resource's dataSourceForAutomaticMigration reference to a [weblogic.management.configuration.JDBCSystemResourceMBean](#) resource.
- **rel**=dataSourceForJobScheduler
This resource's dataSourceForJobScheduler reference to a [weblogic.management.configuration.JDBCSystemResourceMBean](#) resource.
- **rel**=dataSourceForSessionPersistence
This resource's dataSourceForSessionPersistence reference to a [weblogic.management.configuration.JDBCSystemResourceMBean](#) resource.
- **uri**=[/management/weblogic/{version}/edit/clusters/{name}/databaseLessLeasingBasis](#) **rel**=databaseLessLeasingBasis
This resource's databaseLessLeasingBasis singleton resource.
- **uri**=[/management/weblogic/{version}/edit/clusters/{name}/dynamicServers](#)
rel=dynamicServers
This resource's dynamicServers singleton resource.
- **uri**=[/management/weblogic/{version}/edit/clusters/{name}/overloadProtection](#)
rel=overloadProtection
This resource's overloadProtection singleton resource.
- **uri**=[/management/weblogic/{version}/edit/clusters](#) **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/clusters/{name} **rel**=self

This resource.

POST

Update this [weblogic.management.configuration.ClusterMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.ClusterMBean](#) entity.

/management/weblogic/{version}/edit/clusters/{name}/coherenceTier

This resource manages a [weblogic.management.configuration.CoherenceTierMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.CoherenceTierMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.CoherenceTierMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/clusters/{name}/coherenceTier](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/clusters/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/clusters/{name}/coherenceTier](#)
rel=self
This resource.

POST

Update this [weblogic.management.configuration.CoherenceTierMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.CoherenceTierMBean](#) entity.

/management/weblogic/{version}/edit/clusters/{name}/databaseLessLeasingBasis

This resource manages a [weblogic.management.configuration.DatabaseLessLeasingBasisMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.DatabaseLessLeasingBasisMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.DatabaseLessLeasingBasisMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/clusters/{name}/databaseLessLeasingBasis](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/clusters/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/clusters/{name}/databaseLessLeasingBasis](#) **rel**=self
This resource.

POST

Update this [weblogic.management.configuration.DatabaseLessLeasingBasisMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.DatabaseLessLeasingBasisMBean](#) entity.

/management/weblogic/{version}/edit/clusters/{name}/dynamicServers

This resource manages a [weblogic.management.configuration.DynamicServersMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.DynamicServersMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.DynamicServersMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/clusters/{name}/dynamicServers](#)
rel=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/clusters/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/clusters/{name}/dynamicServers](#)
rel=self

This resource.

- **rel**=serverTemplate

This resource's serverTemplate reference to a [weblogic.management.configuration.ServerTemplateMBean](#) resource.

POST

Update this [weblogic.management.configuration.DynamicServersMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.DynamicServersMBean](#) entity.

/management/weblogic/{version}/edit/clusters/{name}/JTACluster

This resource manages a [weblogic.management.configuration.JTAClusterMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.JTAClusterMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.JTAClusterMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/clusters/{name}/JTACluster](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/clusters/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/clusters/{name}/JTACluster](#) **rel**=self
This resource.

POST

Update this [weblogic.management.configuration.JTAClusterMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.JTAClusterMBean](#) entity.

/management/weblogic/{version}/edit/clusters/{name}/overloadProtection

This resource manages a [weblogic.management.configuration.OverloadProtectionMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.OverloadProtectionMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.OverloadProtectionMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/clusters/{name}/overloadProtection](#)
rel=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/clusters/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/clusters/{name}/overloadProtection](#)
rel=self

This resource.

- **uri**=[/management/weblogic/{version}/edit/clusters/{name}/overloadProtection/serverFailureTrigger](#) **rel**=serverFailureTrigger

This resource's serverFailureTrigger singleton resource.

- **uri**=[/management/weblogic/{version}/edit/clusters/{name}/overloadProtection/serverFailureTriggerCreateForm](#) **rel**=serverFailureTriggerCreateForm

The create form resource for this resource's serverFailureTrigger optional singleton resource.

POST

Update this [weblogic.management.configuration.OverloadProtectionMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.OverloadProtectionMBean](#) entity.

/management/weblogic/{version}/edit/clusters/{name}/overloadProtection/serverFailureTrigger

This resource manages a [weblogic.management.configuration.ServerFailureTriggerMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.ServerFailureTriggerMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.ServerFailureTriggerMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ServerFailureTriggerMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/clusters/{name}/overloadProtection/serverFailureTrigger](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/clusters/{name}/overloadProtection/serverFailureTriggerCreateForm](#) **rel**=create-form

The create form resource for this optional singleton resource.

- **uri**=[/management/weblogic/{version}/edit/clusters/{name}/overloadProtection](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/clusters/{name}/overloadProtection/serverFailureTrigger](#) **rel**=self

This resource.

POST

Update this [weblogic.management.configuration.ServerFailureTriggerMBean](#) instance if it exists; otherwise, create it.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.ServerFailureTriggerMBean](#) entity.

/management/weblogic/{version}/edit/clusters/{name}/overloadProtection/serverFailureTriggerCreateForm

This resource manages the create forms for the serverFailureTrigger optional singleton instance.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.ServerFailureTriggerMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the [serverFailureTrigger](#) optional singleton resource to create a new instance if it currently does not exist.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ServerFailureTriggerMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/clusters/{name}/overloadProtection/serverFailureTriggerCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/clusters/{name}/overloadProtection/serverFailureTriggerCreateForm](#) **rel=create**

The optional singleton resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/clusters/{name}/overloadProtection](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/clusters/{name}/overloadProtection/serverFailureTriggerCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/coherenceClusterSystemResourceCreateForm

This resource manages the create forms for the coherenceClusterSystemResources collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.CoherenceClusterSystemResourceMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the coherenceClusterSystemResources collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.CoherenceClusterSystemResourceMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/coherenceClusterSystemResourceCreateForm rel=canonical](#)
This resource.
- [uri=/management/weblogic/{version}/edit/coherenceClusterSystemResources rel=create](#)
The collection resource for this create form resource.
- [uri=/management/weblogic/{version}/edit rel=parent](#)
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/coherenceClusterSystemResourceCreateForm rel=self](#)
This resource.

/management/weblogic/{version}/edit/coherenceClusterSystemResources

This resource manages a collection of [weblogic.management.configuration.CoherenceClusterSystemResourceMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.CoherenceClusterSystemResourceMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.CoherenceClusterSystemResourceMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/coherenceClusterSystemResources](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/coherenceClusterSystemResourceCreateForm](#) **rel**=create-form
The create form resource for this collection resource.
- **uri**=[/management/weblogic/{version}/edit](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/coherenceClusterSystemResources](#)
rel=self
This resource.

POST

Add a new [weblogic.management.configuration.CoherenceClusterSystemResourceMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.CoherenceClusterSystemResourceMBean](#) entity.

/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}

This resource manages a [weblogic.management.configuration.CoherenceClusterSystemResourceMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.CoherenceClusterSystemResourceMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.CoherenceClusterSystemResourceMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.CoherenceClusterSystemResourceMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/importCustomClusterConfigurationFile](#) **rel=action**
title=importCustomClusterConfigurationFile
This resource's importCustomClusterConfigurationFile action resource.
- [uri=/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceCacheConfigCreateForm](#) **rel=coherenceCacheConfigCreateForm**
The create form resource for this resource's coherenceCacheConfigs collection resource.
- [uri=/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceCacheConfigs](#) **rel=coherenceCacheConfigs**
This resource's coherenceCacheConfigs collection resource.
- [uri=/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource](#) **rel=coherenceClusterResource**
This resource's coherenceClusterResource singleton resource.
- [uri=/management/weblogic/{version}/edit/coherenceClusterSystemResources](#) **rel=parent**
The parent resource of this resource.
- **rel=resource**
This resource's resource reference to a weblogic.descriptor.DescriptorBean resource.
- [uri=/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}](#) **rel=self**
This resource.
- [uri=/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/subDeploymentCreateForm](#) **rel=subDeploymentCreateForm**
The create form resource for this resource's subDeployments collection resource.

- **uri**=/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/subDeployments **rel**=subDeployments

This resource's subDeployments collection resource.

POST

Update this [weblogic.management.configuration.CoherenceClusterSystemResourceMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.CoherenceClusterSystemResourceMBean](#) entity.

/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceCacheConfigCreateForm

This resource manages the create forms for the coherenceCacheConfigs collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.CoherenceCacheConfigMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the coherenceCacheConfigs collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.CoherenceCacheConfigMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceCacheConfigCreateForm **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceCacheConfigs **rel**=create

The collection resource for this create form resource.

- **uri**=/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceCacheConfigCreateForm **rel**=self

This resource.

/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceCacheConfigs

This resource manages a collection of [weblogic.management.configuration.CoherenceCacheConfigMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.CoherenceCacheConfigMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.CoherenceCacheConfigMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceCacheConfigs](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceCacheConfigCreateForm](#) **rel=create-form**

The create form resource for this collection resource.

- [uri=/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceCacheConfigs](#) **rel=self**

This resource.

POST

Add a new [weblogic.management.configuration.CoherenceCacheConfigMBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.CoherenceCacheConfigMBean](#) entity.

/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceCacheConfigs/{name}

This resource manages a [weblogic.management.configuration.CoherenceCacheConfigMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.CoherenceCacheConfigMBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.management.configuration.CoherenceCacheConfigMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.CoherenceCacheConfigMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceCacheConfigs/{name}/importCacheConfigurationFile **rel**=action
title=importCacheConfigurationFile

This resource's importCacheConfigurationFile action resource.

- **uri**=/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceCacheConfigs/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceCacheConfigs **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceCacheConfigs/{name} **rel**=self

This resource.

POST

Update this [weblogic.management.configuration.CoherenceCacheConfigMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.CoherenceCacheConfigMBean](#) entity.

/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceCacheConfigs/{name}/importCacheConfigurationFile

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

POST

Imports the file to be used as the cache configuration file from the resource `getCacheConfigurationFile()`.

Roles

Admin, Deployer

Response Body

Contains an empty JSON object.

POST

Imports the file to be used as the cache configuration file.

Roles

Admin, Deployer

Request Body

Must contain a JSON object with the following fields:

file
the name of the file

Type: string

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource

This resource manages a [weblogic.coherence.descriptor.wl.WeblogicCoherenceBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.coherence.descriptor.wl.WeblogicCoherenceBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.coherence.descriptor.wl.WeblogicCoherenceBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceAddressProviders **rel**=coherenceAddressProviders

This resource's coherenceAddressProviders singleton resource.

- **uri**=/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceClusterParams **rel**=coherenceClusterParams

This resource's coherenceClusterParams singleton resource.

- **uri**=/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceFederationParams **rel**=coherenceFederationParams

This resource's coherenceFederationParams singleton resource.

- **uri**=/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceLoggingParams **rel**=coherenceLoggingParams

This resource's coherenceLoggingParams singleton resource.

- **uri**=/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherencePersistenceParams **rel**=coherencePersistenceParams

This resource's coherencePersistenceParams singleton resource.

- **uri**=/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource **rel**=self

This resource.

POST

Update this [weblogic.coherence.descriptor.wl.WeblogicCoherenceBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.coherence.descriptor.wl.WeblogicCoherenceBean](#) entity.

/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceAddressProviders

This resource manages a [weblogic.coherence.descriptor.wl.CoherenceAddressProvidersBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.coherence.descriptor.wl.CoherenceAddressProvidersBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.coherence.descriptor.wl.CoherenceAddressProvidersBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceAddressProviders](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceAddressProviders/coherenceAddressProviderCreateForm](#) **rel=coherenceAddressProviderCreateForm**

The create form resource for this resource's coherenceAddressProviders collection resource.

- [uri=/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceAddressProviders/coherenceAddressProviders](#) **rel=coherenceAddressProviders**

This resource's coherenceAddressProviders collection resource.

- [uri=/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceAddressProviders](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceAddressProviders/coherenceAddressProviderCreateForm

This resource manages the create forms for the coherenceAddressProviders collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.coherence.descriptor.wl.CoherenceAddressProviderBean](#) entity populated with default values that can be customized then posted (using the POST method) to the coherenceAddressProviders collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.coherence.descriptor.wl.CoherenceAddressProviderBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceAddressProviders/coherenceAddressProviderCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceAddressProviders/coherenceAddressProviders](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceAddressProviders](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceAddressProviders/coherenceAddressProviderCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceAddressProviders/coherenceAddressProviders

This resource manages a collection of [weblogic.coherence.descriptor.wl.CoherenceAddressProviderBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.coherence.descriptor.wl.CoherenceAddressProviderBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.coherence.descriptor.wl.CoherenceAddressProviderBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceAddressProviders/coherenceAddressProviders](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceAddressProviders/coherenceAddressProviderCreateForm](#) **rel=create-form**

The create form resource for this collection resource.

- [uri=/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceAddressProviders](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceAddressProviders/coherenceAddressProviders](#) **rel=self**

This resource.

POST

Add a new [weblogic.coherence.descriptor.wl.CoherenceAddressProviderBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.coherence.descriptor.wl.CoherenceAddressProviderBean](#) entity.

/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceAddressProviders/coherenceAddressProviders/{name}

This resource manages a [weblogic.coherence.descriptor.wl.CoherenceAddressProviderBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)

DELETE

Delete this [weblogic.coherence.descriptor.wl.CoherenceAddressProviderBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.coherence.descriptor.wl.CoherenceAddressProviderBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.coherence.descriptor.wl.CoherenceAddressProviderBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceAddressProviders/coherenceAddressProviders/{name}](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceAddressProviders/coherenceAddressProviders/{name}/coherenceSocketAddressCreateForm](#) **rel=coherenceSocketAddressCreateForm**

The create form resource for this resource's coherenceSocketAddresses collection resource.

- [uri=/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceAddressProviders/coherenceAddressProviders/{name}/coherenceSocketAddresses](#) **rel=coherenceSocketAddresses**

This resource's coherenceSocketAddresses collection resource.

- [uri=/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceAddressProviders/coherenceAddressProviders](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceAddressProviders/coherenceAddressProviders/{name}](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceAddressProviders/coherenceAddressProviders/{name}/coherenceSocketAddressCreateForm

This resource manages the create forms for the coherenceSocketAddresses collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.coherence.descriptor.wl.CoherenceSocketAddressBean](#) entity populated with default values that can be customized then posted (using the POST method) to the coherenceSocketAddresses collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.coherence.descriptor.wl.CoherenceSocketAddressBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceAddressProviders/coherenceAddressProviders/{name}/coherenceSocketAddressCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceAddressProviders/coherenceAddressProviders/{name}/coherenceSocketAddresses](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceAddressProviders/coherenceAddressProviders/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceAddressProviders/coherenceAddressProviders/{name}/coherenceSocketAddressCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceAddressProviders/coherenceAddressProviders/{name}/coherenceSocketAddresses

This resource manages a collection of [weblogic.coherence.descriptor.wl.CoherenceSocketAddressBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.coherence.descriptor.wl.CoherenceSocketAddressBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.coherence.descriptor.wl.CoherenceSocketAddressBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceAddressProviders/coherenceAddressProviders/{name}/coherenceSocketAddresses **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceAddressProviders/coherenceAddressProviders/{name}/coherenceSocketAddressCreateForm **rel**=create-form

The create form resource for this collection resource.

- **uri**=/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceAddressProviders/coherenceAddressProviders/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceAddressProviders/coherenceAddressProviders/{name}/coherenceSocketAddresses **rel**=self

This resource.

POST

Add a new [weblogic.coherence.descriptor.wl.CoherenceSocketAddressBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.coherence.descriptor.wl.CoherenceSocketAddressBean](#) entity.

/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceAddressProviders/coherenceAddressProviders/{name}/coherenceSocketAddresses/{name}

This resource manages a [weblogic.coherence.descriptor.wl.CoherenceSocketAddressBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.coherence.descriptor.wl.CoherenceSocketAddressBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.coherence.descriptor.wl.CoherenceSocketAddressBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.coherence.descriptor.wl.CoherenceSocketAddressBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceAddressProviders/{name}/coherenceSocketAddresses/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceAddressProviders/{name}/coherenceSocketAddresses **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceAddressProviders/{name}/coherenceSocketAddresses/{name} **rel**=self

This resource.

POST

POST

Update this [weblogic.coherence.descriptor.wl.CoherenceSocketAddressBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.coherence.descriptor.wl.CoherenceSocketAddressBean](#) entity.

/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceClusterParams

This resource manages a [weblogic.coherence.descriptor.wl.CoherenceClusterParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.coherence.descriptor.wl.CoherenceClusterParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.coherence.descriptor.wl.CoherenceClusterParamsBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceClusterParams](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceClusterParams/coherenceCacheCreateForm](#) **rel=coherenceCacheCreateForm**

The create form resource for this resource's coherenceCaches collection resource.

- [uri=/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceClusterParams/coherenceCaches](#) **rel=coherenceCaches**

This resource's coherenceCaches collection resource.

- [uri=/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceClusterParams/coherenceClusterWellKnownAddresses](#) **rel=coherenceClusterWellKnownAddresses**

This resource's coherenceClusterWellKnownAddresses singleton resource.

- [uri=/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceClusterParams/coherenceIdentityAssertter](#) **rel=coherenceIdentityAssertter**

This resource's coherenceIdentityAssertter singleton resource.

- [uri=/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceClusterParams/coherenceKeystoreParams](#) **rel=coherenceKeystoreParams**

This resource's coherenceKeystoreParams singleton resource.

- [uri=/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceClusterParams/coherenceServiceCreateForm](#) **rel=coherenceServiceCreateForm**

The create form resource for this resource's coherenceServices collection resource.

- [uri=/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceClusterParams/coherenceServices](#) **rel=coherenceServices**

This resource's coherenceServices collection resource.

- [uri=/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource](#) **rel=parent**

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceClusterParams **rel**=self

This resource.

POST

POST

Update this [weblogic.coherence.descriptor.wl.CoherenceClusterParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.coherence.descriptor.wl.CoherenceClusterParamsBean](#) entity.

/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceClusterParams/coherenceCacheCreateForm

This resource manages the create forms for the coherenceCaches collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.coherence.descriptor.wl.CoherenceCacheBean](#) entity populated with default values that can be customized then posted (using the POST method) to the coherenceCaches collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.coherence.descriptor.wl.CoherenceCacheBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceClusterParams/coherenceCacheCreateForm rel=canonical](#)

This resource.

- [uri=/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceClusterParams/coherenceCaches rel=create](#)

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceClusterParams rel=parent](#)

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceClusterParams/coherenceCacheCreateForm rel=self](#)

This resource.

/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceClusterParams/coherenceCaches

This resource manages a collection of [weblogic.coherence.descriptor.wl.CoherenceCacheBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.coherence.descriptor.wl.CoherenceCacheBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.coherence.descriptor.wl.CoherenceCacheBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceClusterParams/coherenceCaches](#)
rel=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceClusterParams/coherenceCacheCreateForm](#) **rel**=create-form

The create form resource for this collection resource.

- **uri**=[/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceClusterParams](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceClusterParams/coherenceCaches](#)
rel=self

This resource.

POST

Add a new [weblogic.coherence.descriptor.wl.CoherenceCacheBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.coherence.descriptor.wl.CoherenceCacheBean](#) entity.

/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceClusterParams/coherenceCaches/{name}

This resource manages a [weblogic.coherence.descriptor.wl.CoherenceCacheBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.coherence.descriptor.wl.CoherenceCacheBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.coherence.descriptor.wl.CoherenceCacheBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.coherence.descriptor.wl.CoherenceCacheBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceClusterParams/coherenceCaches/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceClusterParams/coherenceCaches](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceClusterParams/coherenceCaches/{name}](#) **rel**=self

This resource.

POST

Update this [weblogic.coherence.descriptor.wl.CoherenceCacheBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.coherence.descriptor.wl.CoherenceCacheBean](#) entity.

/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceClusterParams/coherenceClusterWellKnownAddresses

This resource manages a [weblogic.coherence.descriptor.wl.CoherenceClusterWellKnownAddressesBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.coherence.descriptor.wl.CoherenceClusterWellKnownAddressesBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.coherence.descriptor.wl.CoherenceClusterWellKnownAddressesBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceClusterParams/coherenceClusterWellKnownAddresses](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceClusterParams/coherenceClusterWellKnownAddresses/coherenceClusterWellKnownAddressCreateForm](#) **rel=coherenceClusterWellKnownAddressCreateForm**

The create form resource for this resource's coherenceClusterWellKnownAddresses collection resource.

- [uri=/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceClusterParams/coherenceClusterWellKnownAddresses/coherenceClusterWellKnownAddresses](#) **rel=coherenceClusterWellKnownAddresses**

This resource's coherenceClusterWellKnownAddresses collection resource.

- [uri=/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceClusterParams](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceClusterParams/coherenceClusterWellKnownAddresses](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceClusterParams/coherenceClusterWellKnownAddresses/coherenceClusterWellKnownAddressCreateForm

This resource manages the create forms for the coherenceClusterWellKnownAddresses collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.coherence.descriptor.wl.CoherenceClusterWellKnownAddressBean](#) entity populated with default values that can be customized then posted (using the POST method) to the [coherenceClusterWellKnownAddresses](#) collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.coherence.descriptor.wl.CoherenceClusterWellKnownAddressBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceClusterParams/coherenceClusterWellKnownAddresses/coherenceClusterWellKnownAddressCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceClusterParams/coherenceClusterWellKnownAddresses/coherenceClusterWellKnownAddresses](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceClusterParams/coherenceClusterWellKnownAddresses](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceClusterParams/coherenceClusterWellKnownAddresses/coherenceClusterWellKnownAddressCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceClusterParams/coherenceClusterWellKnownAddresses/coherenceClusterWellKnownAddresses

This resource manages a collection of [weblogic.coherence.descriptor.wl.CoherenceClusterWellKnownAddressBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.coherence.descriptor.wl.CoherenceClusterWellKnownAddressBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.coherence.descriptor.wl.CoherenceClusterWellKnownAddressBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceClusterParams/coherenceClusterWellKnownAddresses/coherenceClusterWellKnownAddresses **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceClusterParams/coherenceClusterWellKnownAddresses/coherenceClusterWellKnownAddressCreateForm **rel**=create-form

The create form resource for this collection resource.

- **uri**=/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceClusterParams/coherenceClusterWellKnownAddresses **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceClusterParams/coherenceClusterWellKnownAddresses/coherenceClusterWellKnownAddresses **rel**=self

This resource.

POST

Add a new [weblogic.coherence.descriptor.wl.CoherenceClusterWellKnownAddressBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.coherence.descriptor.wl.CoherenceClusterWellKnownAddressBean](#) entity.

/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceClusterParams/coherenceClusterWellKnownAddresses/coherenceClusterWellKnownAddresses/{name}

This resource manages a [weblogic.coherence.descriptor.wl.CoherenceClusterWellKnownAddressBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.coherence.descriptor.wl.CoherenceClusterWellKnownAddressBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.coherence.descriptor.wl.CoherenceClusterWellKnownAddressBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.coherence.descriptor.wl.CoherenceClusterWellKnownAddressBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceClusterParams/coherenceClusterWellKnownAddresses/coherenceClusterWellKnownAddresses/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceClusterParams/coherenceClusterWellKnownAddresses/coherenceClusterWellKnownAddresses **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceClusterParams/coherenceClusterWellKnownAddresses/coherenceClusterWellKnownAddresses/{name} **rel**=self

This resource.

POST

Update this [weblogic.coherence.descriptor.wl.CoherenceClusterWellKnownAddressBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.coherence.descriptor.wl.CoherenceClusterWellKnownAddressBean](#) entity.

/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceClusterParams/coherenceIdentityAsserter

This resource manages a [weblogic.coherence.descriptor.wl.CoherenceIdentityAsserterBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.coherence.descriptor.wl.CoherenceIdentityAsserterBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.coherence.descriptor.wl.CoherenceIdentityAsserterBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceClusterParams/coherenceIdentityAsserter](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceClusterParams/coherenceIdentityAsserter/coherenceInitParamCreateForm](#) **rel**=coherenceInitParamCreateForm

The create form resource for this resource's coherenceInitParams collection resource.

- **uri**=[/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceClusterParams/coherenceIdentityAsserter/coherenceInitParams](#) **rel**=coherenceInitParams

This resource's coherenceInitParams collection resource.

- **uri**=[/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceClusterParams](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceClusterParams/coherenceIdentityAsserter](#) **rel**=self

This resource.

POST

Update this [weblogic.coherence.descriptor.wl.CoherenceIdentityAsserterBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.coherence.descriptor.wl.CoherenceIdentityAsserterBean](#) entity.

/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceClusterParams/coherenceIdentityAsserter/coherenceInitParamCreateForm

This resource manages the create forms for the coherenceInitParams collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.coherence.descriptor.wl.CoherenceInitParamBean](#) entity populated with default values that can be customized then posted (using the POST method) to the coherenceInitParams collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.coherence.descriptor.wl.CoherenceInitParamBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceClusterParams/coherenceIdentityAsserter/coherenceInitParamCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceClusterParams/coherenceIdentityAsserter/coherenceInitParams](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceClusterParams/coherenceIdentityAsserter](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceClusterParams/coherenceIdentityAsserter/coherenceInitParamCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceClusterParams/coherenceIdentityAsserter/coherenceInitParams

This resource manages a collection of [weblogic.coherence.descriptor.wl.CoherenceInitParamBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.coherence.descriptor.wl.CoherenceInitParamBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.coherence.descriptor.wl.CoherenceInitParamBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceClusterParams/coherenceIdentityAsserter/coherenceInitParams](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceClusterParams/coherenceIdentityAsserter/coherenceInitParamCreateForm](#) **rel=create-form**

The create form resource for this collection resource.

- [uri=/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceClusterParams/coherenceIdentityAsserter](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceClusterParams/coherenceIdentityAsserter/coherenceInitParams](#) **rel=self**

This resource.

POST

Add a new [weblogic.coherence.descriptor.wl.CoherenceInitParamBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.coherence.descriptor.wl.CoherenceInitParamBean](#) entity.

/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceClusterParams/coherenceIdentityAsserter/coherenceInitParams/{name}

This resource manages a [weblogic.coherence.descriptor.wl.CoherenceInitParamBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.coherence.descriptor.wl.CoherenceInitParamBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.coherence.descriptor.wl.CoherenceInitParamBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.coherence.descriptor.wl.CoherenceInitParamBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceClusterParams/coherenceIdentityAsserter/coherenceInitParams/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceClusterParams/coherenceIdentityAsserter/coherenceInitParams **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceClusterParams/coherenceIdentityAsserter/coherenceInitParams/{name} **rel**=self

This resource.

POST

Update this [weblogic.coherence.descriptor.wl.CoherenceInitParamBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.coherence.descriptor.wl.CoherenceInitParamBean](#) entity.

/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceClusterParams/coherenceKeystoreParams

This resource manages a [weblogic.coherence.descriptor.wl.CoherenceKeystoreParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.coherence.descriptor.wl.CoherenceKeystoreParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.coherence.descriptor.wl.CoherenceKeystoreParamsBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceClusterParams/coherenceKeystoreParams](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceClusterParams](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceClusterParams/coherenceKeystoreParams](#) **rel**=self

This resource.

POST

Update this [weblogic.coherence.descriptor.wl.CoherenceKeystoreParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.coherence.descriptor.wl.CoherenceKeystoreParamsBean](#) entity.

/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceClusterParams/coherenceServiceC reateForm

This resource manages the create forms for the coherenceServices collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.coherence.descriptor.wl.CoherenceServiceBean](#) entity populated with default values that can be customized then posted (using the POST method) to the coherenceServices collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.coherence.descriptor.wl.CoherenceServiceBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceClusterParams/coherenceServiceCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceClusterParams/coherenceServices](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceClusterParams](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceClusterParams/coherenceServiceCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceClusterParams/coherenceServices

This resource manages a collection of [weblogic.coherence.descriptor.wl.CoherenceServiceBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.coherence.descriptor.wl.CoherenceServiceBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.coherence.descriptor.wl.CoherenceServiceBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceClusterParams/coherenceServices](#)
rel=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceClusterParams/coherenceServiceCreateForm](#) **rel**=create-form

The create form resource for this collection resource.

- **uri**=[/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceClusterParams](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceClusterParams/coherenceServices](#)
rel=self

This resource.

POST

Add a new [weblogic.coherence.descriptor.wl.CoherenceServiceBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.coherence.descriptor.wl.CoherenceServiceBean](#) entity.

/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceClusterParams/coherenceServices/{name}

This resource manages a [weblogic.coherence.descriptor.wl.CoherenceServiceBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

DELETE

Delete this [weblogic.coherence.descriptor.wl.CoherenceServiceBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.coherence.descriptor.wl.CoherenceServiceBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.coherence.descriptor.wl.CoherenceServiceBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceClusterParams/coherenceServices/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceClusterParams/coherenceServices **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceClusterParams/coherenceServices/{name} **rel**=self

This resource.

POST

Update this [weblogic.coherence.descriptor.wl.CoherenceServiceBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.coherence.descriptor.wl.CoherenceServiceBean](#) entity.

/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceFederationParams

This resource manages a [weblogic.coherence.descriptor.wl.CoherenceFederationParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.coherence.descriptor.wl.CoherenceFederationParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.coherence.descriptor.wl.CoherenceFederationParamsBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceFederationParams](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceFederationParams](#) **rel**=self

This resource.

POST

Update this [weblogic.coherence.descriptor.wl.CoherenceFederationParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.coherence.descriptor.wl.CoherenceFederationParamsBean](#) entity.

/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceLoggingParams

This resource manages a [weblogic.coherence.descriptor.wl.CoherenceLoggingParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.coherence.descriptor.wl.CoherenceLoggingParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.coherence.descriptor.wl.CoherenceLoggingParamsBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceLoggingParams](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherenceLoggingParams](#) **rel=self**
This resource.

POST

Update this [weblogic.coherence.descriptor.wl.CoherenceLoggingParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.coherence.descriptor.wl.CoherenceLoggingParamsBean](#) entity.

/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherencePersistenceParams

This resource manages a [weblogic.coherence.descriptor.wl.CoherencePersistenceParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.coherence.descriptor.wl.CoherencePersistenceParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.coherence.descriptor.wl.CoherencePersistenceParamsBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherencePersistenceParams](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/coherenceClusterResource/coherencePersistenceParams](#) **rel**=self

This resource.

POST

Update this [weblogic.coherence.descriptor.wl.CoherencePersistenceParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.coherence.descriptor.wl.CoherencePersistenceParamsBean](#) entity.

/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/importCustomClusterConfigurationFile

The resource supports the following methods:

- [POST](#)

POST

Allows you to specify a custom Coherence cluster configuration file. The file must be present locally on the Administration Server.

Roles

Admin, Deployer

Request Body

Must contain a JSON object with the following fields:

file

Absolute path to the custom Coherence cluster configuration file

Type: string

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/subDeploymentCreateForm

This resource manages the create forms for the subDeployments collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.SubDeploymentMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the subDeployments collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/subDeploymentCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/subDeployments](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/subDeploymentCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/subDeployments

This resource manages a collection of [weblogic.management.configuration.SubDeploymentMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.SubDeploymentMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.SubDeploymentMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/subDeployments](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/subDeploymentCreateForm](#) **rel**=create-form
The create form resource for this collection resource.
- **uri**=[/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/subDeployments](#) **rel**=self
This resource.

POST

Add a new [weblogic.management.configuration.SubDeploymentMBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/subDeployments/{name}

This resource manages a [weblogic.management.configuration.SubDeploymentMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/subDeployments/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/subDeployments **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/subDeployments/{name} **rel**=self

This resource.

- **uri**=/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/subDeployments/{name}/subDeployments **rel**=subDeployments

This resource's subDeployments collection resource.

POST

Update this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/subDeployments/{name}/subDeployments

This resource manages a collection of [weblogic.management.configuration.SubDeploymentMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.configuration.SubDeploymentMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.SubDeploymentMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/subDeployments/{name}/subDeployments](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/subDeployments/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/subDeployments/{name}/subDeployments](#) **rel**=self

This resource.

/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/subDeployments/{name}/subDeployments/{name}

This resource manages a [weblogic.management.configuration.SubDeploymentMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/subDeployments/{name}/subDeployments/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/subDeployments/{name}/subDeployments](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/subDeployments/{name}/subDeployments/{name}](#) **rel**=self

This resource.

- **uri**=[/management/weblogic/{version}/edit/coherenceClusterSystemResources/{name}/subDeployments/{name}/subDeployments/{name}/subDeployments](#) **rel**=subDeployments

This resource's subDeployments collection resource.

POST

Update this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

/management/weblogic/{version}/edit/coherenceManagementClusterCreateForm

This resource manages the create forms for the coherenceManagementClusters collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.CoherenceManagementClusterMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the coherenceManagementClusters collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.CoherenceManagementClusterMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/coherenceManagementClusterCreateForm](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/coherenceManagementClusters](#) **rel=create**
The collection resource for this create form resource.
- [uri=/management/weblogic/{version}/edit](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/coherenceManagementClusterCreateForm](#) **rel=self**
This resource.

/management/weblogic/{version}/edit/coherenceManagementClusters

This resource manages a collection of [weblogic.management.configuration.CoherenceManagementClusterMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.CoherenceManagementClusterMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.CoherenceManagementClusterMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/coherenceManagementClusters](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/coherenceManagementClusterCreateForm](#) **rel**=create-form
The create form resource for this collection resource.
- **uri**=[/management/weblogic/{version}/edit](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/coherenceManagementClusters](#)
rel=self
This resource.

POST

POST

Add a new [weblogic.management.configuration.CoherenceManagementClusterMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.CoherenceManagementClusterMBean](#) entity.

/management/weblogic/{version}/edit/coherenceManagementClusters/{name}

This resource manages a [weblogic.management.configuration.CoherenceManagementClusterMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.CoherenceManagementClusterMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.CoherenceManagementClusterMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.CoherenceManagementClusterMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/coherenceManagementClusters/{name}](#)
rel=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/coherenceManagementClusters/{name}/coherenceManagementAddressProviderCreateForm](#)
rel=coherenceManagementAddressProviderCreateForm

The create form resource for this resource's coherenceManagementAddressProviders collection resource.

- **uri**=[/management/weblogic/{version}/edit/coherenceManagementClusters/{name}/coherenceManagementAddressProviders](#)
rel=coherenceManagementAddressProviders

This resource's coherenceManagementAddressProviders collection resource.

- **uri**=[/management/weblogic/{version}/edit/coherenceManagementClusters](#)
rel=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/coherenceManagementClusters/{name}](#)
rel=self

This resource.

POST

POST

Update this [weblogic.management.configuration.CoherenceManagementClusterMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.CoherenceManagementClusterMBean](#) entity.

/management/weblogic/{version}/edit/coherenceManagementClusters/{name}/coherenceManagementAddressProviderCreateForm

This resource manages the create forms for the coherenceManagementAddressProviders collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.CoherenceManagementAddressProviderMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the `coherenceManagementAddressProviders` collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.CoherenceManagementAddressProviderMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/coherenceManagementClusters/{name}/coherenceManagementAddressProviderCreateForm](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/coherenceManagementClusters/{name}/coherenceManagementAddressProviders](#) **rel**=create

The collection resource for this create form resource.

- **uri**=[/management/weblogic/{version}/edit/coherenceManagementClusters/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/coherenceManagementClusters/{name}/coherenceManagementAddressProviderCreateForm](#) **rel**=self

This resource.

/management/weblogic/{version}/edit/coherenceManagementClusters/{name}/coherenceManagementAddressProviders

This resource manages a collection of [weblogic.management.configuration.CoherenceManagementAddressProviderMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.CoherenceManagementAddressProviderMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.CoherenceManagementAddressProviderMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/coherenceManagementClusters/{name}/coherenceManagementAddressProviders](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/coherenceManagementClusters/{name}/coherenceManagementAddressProviderCreateForm](#) **rel**=create-form

The create form resource for this collection resource.

- **uri**=[/management/weblogic/{version}/edit/coherenceManagementClusters/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/coherenceManagementClusters/{name}/coherenceManagementAddressProviders](#) **rel**=self

This resource.

POST

Add a new [weblogic.management.configuration.CoherenceManagementAddressProviderMBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.CoherenceManagementAddressProviderMBean](#) entity.

/management/weblogic/{version}/edit/coherenceManagementClusters/{name}/coherenceManagementAddressProviders/{name}

This resource manages a [weblogic.management.configuration.CoherenceManagementAddressProviderMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this

[weblogic.management.configuration.CoherenceManagementAddressProviderMBean](#)
instance.

Roles

Admin, Deployer

GET

Get this [weblogic.management.configuration.CoherenceManagementAddressProviderMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.CoherenceManagementAddressProviderMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/coherenceManagementClusters/{name}/coherenceManagementAddressProviders/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/coherenceManagementClusters/{name}/coherenceManagementAddressProviders **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/coherenceManagementClusters/{name}/coherenceManagementAddressProviders/{name} **rel**=self

This resource.

POST

Update this [weblogic.management.configuration.CoherenceManagementAddressProviderMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.CoherenceManagementAddressProviderMBean](#) entity.

/management/weblogic/{version}/edit/coherenceServerCreateForm

This resource manages the create forms for the coherenceServers collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.CoherenceServerMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the coherenceServers collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.CoherenceServerMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/coherenceServerCreateForm](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/coherenceServers](#) **rel**=create
The collection resource for this create form resource.
- **uri**=[/management/weblogic/{version}/edit](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/coherenceServerCreateForm](#) **rel**=self
This resource.

/management/weblogic/{version}/edit/coherenceServers

This resource manages a collection of [weblogic.management.configuration.CoherenceServerMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.CoherenceServerMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.CoherenceServerMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/coherenceServers](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/coherenceServerCreateForm](#)
rel=create-form
The create form resource for this collection resource.
- **uri**=[/management/weblogic/{version}/edit](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/coherenceServers](#) **rel**=self
This resource.

POST

Add a new [weblogic.management.configuration.CoherenceServerMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.CoherenceServerMBean](#) entity.

/management/weblogic/{version}/edit/coherenceServers/{name}

This resource manages a [weblogic.management.configuration.CoherenceServerMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

DELETE

Delete this [weblogic.management.configuration.CoherenceServerMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.CoherenceServerMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.CoherenceServerMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/coherenceServers/{name}](#)
rel=canonical
This resource.
- **rel**=coherenceClusterSystemResource
This resource's coherenceClusterSystemResource reference to a [weblogic.management.configuration.CoherenceClusterSystemResourceMBean](#) resource.
- **uri**=[/management/weblogic/{version}/edit/coherenceServers/{name}/coherenceServerStart](#) **rel**=coherenceServerStart
This resource's coherenceServerStart singleton resource.
- **rel**=machine
This resource's machine reference to a [weblogic.management.configuration.MachineMBean](#) resource.
- **uri**=[/management/weblogic/{version}/edit/coherenceServers](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/coherenceServers/{name}](#) **rel**=self
This resource.

POST

POST

Update this [weblogic.management.configuration.CoherenceServerMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.CoherenceServerMBean](#) entity.

/management/weblogic/{version}/edit/coherenceServers/{name}/coherenceServerStart

This resource manages a [weblogic.management.configuration.CoherenceServerStartMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.CoherenceServerStartMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.CoherenceServerStartMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/coherenceServers/{name}/coherenceServerStart](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/coherenceServers/{name}](#)
rel=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/coherenceServers/{name}/coherenceServerStart](#) **rel**=self
This resource.

POST

Update this [weblogic.management.configuration.CoherenceServerStartMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.CoherenceServerStartMBean](#) entity.

/management/weblogic/{version}/edit/configurationProperties

This resource manages a collection of [weblogic.management.configuration.ConfigurationPropertyMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.ConfigurationPropertyMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.ConfigurationPropertyMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/configurationProperties](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/configurationPropertyCreateForm](#)
rel=create-form
The create form resource for this collection resource.
- **uri**=[/management/weblogic/{version}/edit](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/configurationProperties](#) **rel**=self
This resource.

POST

Add a new [weblogic.management.configuration.ConfigurationPropertyMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.ConfigurationPropertyMBean](#) entity.

/management/weblogic/{version}/edit/configurationProperties/{name}

This resource manages a [weblogic.management.configuration.ConfigurationPropertyMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.ConfigurationPropertyMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.ConfigurationPropertyMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ConfigurationPropertyMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/configurationProperties/{name}](#)
rel=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/configurationProperties](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/configurationProperties/{name}](#)
rel=self

This resource.

POST

Update this [weblogic.management.configuration.ConfigurationPropertyMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.ConfigurationPropertyMBean](#) entity.

/management/weblogic/{version}/edit/configurationPropertyCreateForm

This resource manages the create forms for the configurationProperties collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.ConfigurationPropertyMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the configurationProperties collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ConfigurationPropertyMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/configurationPropertyCreateForm](#)
rel=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/configurationProperties](#) **rel**=create

The collection resource for this create form resource.

- **uri**=[/management/weblogic/{version}/edit](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/configurationPropertyCreateForm](#)
rel=self

This resource.

/management/weblogic/{version}/edit/customResourceCreateForm

This resource manages the create forms for the customResources collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.CustomResourceMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the customResources collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.CustomResourceMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/customResourceCreateForm](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/customResources](#) **rel**=create
The collection resource for this create form resource.
- **uri**=[/management/weblogic/{version}/edit](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/customResourceCreateForm](#) **rel**=self
This resource.

/management/weblogic/{version}/edit/customResources

This resource manages a collection of [weblogic.management.configuration.CustomResourceMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.CustomResourceMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.CustomResourceMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/customResources](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/customResourceCreateForm](#)
rel=create-form
The create form resource for this collection resource.
- **uri**=[/management/weblogic/{version}/edit](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/customResources](#) **rel**=self
This resource.

POST

Add a new [weblogic.management.configuration.CustomResourceMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.CustomResourceMBean](#) entity.

/management/weblogic/{version}/edit/customResources/{name}

This resource manages a [weblogic.management.configuration.CustomResourceMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.CustomResourceMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.CustomResourceMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.CustomResourceMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/customResources/{name}](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/customResources/{name}/customResource](#) **rel**=customResource
This resource's customResource singleton resource.
- **uri**=[/management/weblogic/{version}/edit/customResources](#) **rel**=parent
The parent resource of this resource.
- **rel**=resource
This resource's resource reference to a [weblogic.descriptor.DescriptorBean](#) resource.
- **uri**=[/management/weblogic/{version}/edit/customResources/{name}](#) **rel**=self
This resource.
- **uri**=[/management/weblogic/{version}/edit/customResources/{name}/subDeploymentCreateForm](#) **rel**=subDeploymentCreateForm
The create form resource for this resource's subDeployments collection resource.
- **uri**=[/management/weblogic/{version}/edit/customResources/{name}/subDeployments](#) **rel**=subDeployments
This resource's subDeployments collection resource.

POST

Update this [weblogic.management.configuration.CustomResourceMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.CustomResourceMBean](#) entity.

/management/weblogic/{version}/edit/customResources/{name}/customResource

This resource manages a `weblogic.descriptor.DescriptorBean` instance.

The resource supports the following methods:

- [GET](#)

GET

Get this weblogic.descriptor.DescriptorBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.descriptor.DescriptorBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/customResources/{name}/customResource **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/edit/customResources/{name} **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/edit/customResources/{name}/customResource **rel**=self
This resource.

/management/weblogic/{version}/edit/customResources/{name}/subDeploymentCreateForm

This resource manages the create forms for the subDeployments collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.SubDeploymentMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the subDeployments collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/customResources/{name}/subDeploymentCreateForm](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/customResources/{name}/subDeployments](#) **rel=create**
The collection resource for this create form resource.
- [uri=/management/weblogic/{version}/edit/customResources/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/customResources/{name}/subDeploymentCreateForm](#) **rel=self**
This resource.

/management/weblogic/{version}/edit/customResources/{name}/subDeployments

This resource manages a collection of [weblogic.management.configuration.SubDeploymentMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.SubDeploymentMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.SubDeploymentMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/customResources/{name}/subDeployments](#) [rel=canonical](#)
This resource.
- [uri=/management/weblogic/{version}/edit/customResources/{name}/subDeploymentCreateForm](#) [rel=create-form](#)
The create form resource for this collection resource.
- [uri=/management/weblogic/{version}/edit/customResources/{name}](#) [rel=parent](#)
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/customResources/{name}/subDeployments](#) [rel=self](#)
This resource.

POST

Add a new [weblogic.management.configuration.SubDeploymentMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

/management/weblogic/{version}/edit/customResources/{name}/subDeployments/{name}

This resource manages a [weblogic.management.configuration.SubDeploymentMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/customResources/{name}/subDeployments/{name}](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/customResources/{name}/subDeployments](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/customResources/{name}/subDeployments/{name}](#) **rel**=self
This resource.
- **uri**=[/management/weblogic/{version}/edit/customResources/{name}/subDeployments/{name}/subDeployments](#) **rel**=subDeployments
This resource's subDeployments collection resource.

POST

Update this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

/management/weblogic/{version}/edit/customResources/{name}/subDeployments/{name}/subDeployments

This resource manages a collection of [weblogic.management.configuration.SubDeploymentMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.configuration.SubDeploymentMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.SubDeploymentMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/customResources/{name}/subDeployments/{name}/subDeployments](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/customResources/{name}/subDeployments/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/customResources/{name}/subDeployments/{name}/subDeployments](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/customResources/{name}/subDeployments/{name}/subDeployments/{name}

This resource manages a [weblogic.management.configuration.SubDeploymentMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/customResources/{name}/subDeployments/{name}/subDeployments/{name}](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/customResources/{name}/subDeployments/{name}/subDeployments](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/customResources/{name}/subDeployments/{name}/subDeployments/{name}](#) **rel=self**
This resource.
- [uri=/management/weblogic/{version}/edit/customResources/{name}/subDeployments/{name}/subDeployments/{name}/subDeployments](#) **rel=subDeployments**
This resource's subDeployments collection resource.

POST

Update this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

/management/weblogic/{version}/edit/debugPatches

This resource manages a [weblogic.management.configuration.DebugPatchesMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.DebugPatchesMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.DebugPatchesMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/debugPatches](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/debugPatches](#) **rel**=self
This resource.

POST

Update this [weblogic.management.configuration.DebugPatchesMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.DebugPatchesMBean](#) entity.

/management/weblogic/{version}/edit/deploymentConfiguration

This resource manages a [weblogic.management.configuration.DeploymentConfigurationMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.DeploymentConfigurationMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.DeploymentConfigurationMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/deploymentConfiguration](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/deploymentConfiguration/deploymentValidationPlugin](#) **rel**=deploymentValidationPlugin
This resource's deploymentValidationPlugin singleton resource.
- **uri**=[/management/weblogic/{version}/edit](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/deploymentConfiguration](#) **rel**=self
This resource.

POST

Update this [weblogic.management.configuration.DeploymentConfigurationMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.DeploymentConfigurationMBean](#) entity.

/management/weblogic/{version}/edit/deploymentConfiguration/deploymentValidationPlugin

This resource manages a [weblogic.management.configuration.DeploymentValidationPluginMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.DeploymentValidationPluginMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.DeploymentValidationPluginMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/deploymentConfiguration/deploymentValidationPlugin](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/deploymentConfiguration/deploymentValidationPlugin/parameterCreateForm](#) **rel=parameterCreateForm**

The create form resource for this resource's parameters collection resource.

- [uri=/management/weblogic/{version}/edit/deploymentConfiguration/deploymentValidationPlugin/parameters](#) **rel=parameters**

This resource's parameters collection resource.

- [uri=/management/weblogic/{version}/edit/deploymentConfiguration](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/deploymentConfiguration/deploymentValidationPlugin](#) **rel=self**

This resource.

POST

POST

Update this [weblogic.management.configuration.DeploymentValidationPluginMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.DeploymentValidationPluginMBean](#) entity.

/management/weblogic/{version}/edit/deploymentConfiguration/deploymentValidationPlugin/parameterCreateForm

This resource manages the create forms for the parameters collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.ParameterMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the parameters collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ParameterMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/deploymentConfiguration/deploymentValidationPlugin/parameterCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/deploymentConfiguration/deploymentValidationPlugin/parameters](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/deploymentConfiguration/deploymentValidationPlugin](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/deploymentConfiguration/deploymentValidationPlugin/parameterCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/deploymentConfiguration/deploymentValidationPlugin/parameters

This resource manages a collection of [weblogic.management.configuration.ParameterMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.ParameterMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.ParameterMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/deploymentConfiguration/deploymentValidationPlugin/parameters](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/deploymentConfiguration/deploymentValidationPlugin/parameterCreateForm](#) **rel=create-form**

The create form resource for this collection resource.

- [uri=/management/weblogic/{version}/edit/deploymentConfiguration/deploymentValidationPlugin](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/deploymentConfiguration/deploymentValidationPlugin/parameters](#) **rel=self**

This resource.

POST

Add a new [weblogic.management.configuration.ParameterMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.ParameterMBean](#) entity.

/management/weblogic/{version}/edit/deploymentConfiguration/deploymentValidationPlugin/parameters/{name}

This resource manages a [weblogic.management.configuration.ParameterMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.ParameterMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.ParameterMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ParameterMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/deploymentConfiguration/deploymentValidationPlugin/parameters/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/deploymentConfiguration/deploymentValidationPlugin/parameters](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/deploymentConfiguration/deploymentValidationPlugin/parameters/{name}](#) **rel**=self

This resource.

POST

Update this [weblogic.management.configuration.ParameterMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.ParameterMBean](#) entity.

/management/weblogic/{version}/edit/embeddedLDAP

This resource manages a [weblogic.management.configuration.EmbeddedLDAPMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.EmbeddedLDAPMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.EmbeddedLDAPMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/embeddedLDAP](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/embeddedLDAP](#) **rel**=self
This resource.

POST

Update this [weblogic.management.configuration.EmbeddedLDAPMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.EmbeddedLDAPMBean](#) entity.

/management/weblogic/{version}/edit/fileStoreCreateForm

This resource manages the create forms for the fileStores collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.FileStoreMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the fileStores collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.FileStoreMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/fileStoreCreateForm](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/fileStores](#) **rel**=create
The collection resource for this create form resource.
- **uri**=[/management/weblogic/{version}/edit](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/fileStoreCreateForm](#) **rel**=self
This resource.

/management/weblogic/{version}/edit/fileStores

This resource manages a collection of [weblogic.management.configuration.FileStoreMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.FileStoreMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.FileStoreMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/fileStores](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/fileStoreCreateForm](#) **rel**=create-form
The create form resource for this collection resource.
- **uri**=[/management/weblogic/{version}/edit](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/fileStores](#) **rel**=self
This resource.

POST

Add a new [weblogic.management.configuration.FileStoreMBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.FileStoreMBean](#) entity.

/management/weblogic/{version}/edit/fileStores/{name}

This resource manages a [weblogic.management.configuration.FileStoreMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.FileStoreMBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.management.configuration.FileStoreMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.FileStoreMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/fileStores/{name}](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/fileStores](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/fileStores/{name}](#) **rel**=self
This resource.

POST

Update this [weblogic.management.configuration.FileStoreMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.FileStoreMBean](#) entity.

/management/weblogic/{version}/edit/findConfigBeansWithTags

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

POST

Find all ConfigurationMBeans of the specified config bean type that have the specified tag(s). The tag param may be a single tag or multiple tags. The config bean must have a matching tag for every tag specified. The type may be an empty string to get all types of config beans with the specified tags. The tag may include white spaces. White spaces will not be treated specially. If the user specifies the tags param as "santa clara", this is considered to be a single tag 'santa clara', not two. Spaces are not delimiters.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

type

type of the MBean (shortened version of the class name less the MBean)

Type: string

tags

tags

Type: array of string

Response Body

Contains a JSON object with a array of weblogic.management.configuration.ConfigurationMBean references return field.

POST

Find all ConfigurationMBeans of the specified config bean type that have the specified tag(s). The tag param may be a single tag or multiple tags. If matchAll is true the config bean must have a matching tag for every tag specified. If matchAll is false the config bean may match on any single tag specified. The type may be an empty string to get all types of config beans with the specified tags. The tag may include white spaces. White spaces will not be treated specially. If the user specifies the tags param as "santa clara", this is considered to be a single tag 'santa clara', not two. Spaces are not delimiters.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

type

type of the MBean (shortened version of the class name less the MBean)

Type: string

matchAll

false to match on any single tag, true to match on all tags

Type: boolean

tags

tags

Type: array of string

Response Body

Contains a JSON object with a array of `weblogic.management.configuration.ConfigurationMBean` references return field.

/management/weblogic/{version}/edit/findPartitionByID

The resource supports the following methods:

- [POST](#)

POST

Looks up a partition by the partition ID. The ID is a unique string that is NOT necessarily the same as the MBean name.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

id
the id of the partition to find

Type: string

Response Body

Contains a JSON object with a `weblogic.management.configuration.PartitionMBean` reference return field.

/management/weblogic/{version}/edit/foreignJNDIPProviderCreateForm

This resource manages the create forms for the foreignJNDIProviders collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.ForeignJNDIProviderMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the [foreignJNDIProviders](#) collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ForeignJNDIProviderMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/foreignJNDIProviderCreateForm](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/foreignJNDIProviders](#) **rel**=create
The collection resource for this create form resource.
- **uri**=[/management/weblogic/{version}/edit](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/foreignJNDIProviderCreateForm](#)
rel=self
This resource.

/management/weblogic/{version}/edit/foreignJNDIProviders

This resource manages a collection of [weblogic.management.configuration.ForeignJNDIProviderMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.ForeignJNDIProviderMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.ForeignJNDIProviderMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/foreignJNDIProviders](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/foreignJNDIProviderCreateForm](#)
rel=create-form
The create form resource for this collection resource.
- **uri**=[/management/weblogic/{version}/edit](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/foreignJNDIProviders](#) **rel**=self
This resource.

POST

Add a new [weblogic.management.configuration.ForeignJNDIProviderMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.ForeignJNDIProviderMBean](#) entity.

/management/weblogic/{version}/edit/foreignJNDIProviders/{name}

This resource manages a [weblogic.management.configuration.ForeignJNDIProviderMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.ForeignJNDIProviderMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.ForeignJNDIPProviderMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ForeignJNDIPProviderMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/foreignJNDIProviders/{name}](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/foreignJNDIProviders/{name}/foreignJNDILinkCreateForm](#) **rel**=foreignJNDILinkCreateForm
The create form resource for this resource's foreignJNDILinks collection resource.
- **uri**=[/management/weblogic/{version}/edit/foreignJNDIProviders/{name}/foreignJNDILinks](#) **rel**=foreignJNDILinks
This resource's foreignJNDILinks collection resource.
- **uri**=[/management/weblogic/{version}/edit/foreignJNDIProviders](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/foreignJNDIProviders/{name}](#)
rel=self
This resource.

POST

Update this [weblogic.management.configuration.ForeignJNDIProviderMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.ForeignJNDIProviderMBean](#) entity.

/management/weblogic/{version}/edit/foreignJNDIProviders/{name}/foreignJNDILinkCreateForm

This resource manages the create forms for the foreignJNDILinks collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.ForeignJNDILinkMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the foreignJNDILinks collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ForeignJNDILinkMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/foreignJNDIProviders/{name}/foreignJNDILinkCreateForm](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/foreignJNDIProviders/{name}/foreignJNDILinks](#) **rel**=create
The collection resource for this create form resource.
- **uri**=[/management/weblogic/{version}/edit/foreignJNDIProviders/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/foreignJNDIProviders/{name}/foreignJNDILinkCreateForm](#) **rel**=self
This resource.

/management/weblogic/{version}/edit/foreignJNDIProviders/{name}/foreignJNDILinks

This resource manages a collection of [weblogic.management.configuration.ForeignJNDILinkMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.ForeignJNDILinkMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.ForeignJNDILinkMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/foreignJNDIProviders/{name}/foreignJNDILinks](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/foreignJNDIProviders/{name}/foreignJNDILinkCreateForm](#) **rel=create-form**
The create form resource for this collection resource.
- [uri=/management/weblogic/{version}/edit/foreignJNDIProviders/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/foreignJNDIProviders/{name}/foreignJNDILinks](#) **rel=self**
This resource.

POST

Add a new [weblogic.management.configuration.ForeignJNDILinkMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.ForeignJNDILinkMBean](#) entity.

/management/weblogic/{version}/edit/foreignJNDIProviders/{name}/foreignJNDILinks/{name}

This resource manages a [weblogic.management.configuration.ForeignJNDILinkMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.ForeignJNDILinkMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.ForeignJNDILinkMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ForeignJNDILinkMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/foreignJNDIProviders/{name}/foreignJNDILinks/{name}](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/foreignJNDIProviders/{name}/foreignJNDILinks](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/foreignJNDIProviders/{name}/foreignJNDILinks/{name}](#) **rel=self**
This resource.

POST

Update this [weblogic.management.configuration.ForeignJNDILinkMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.ForeignJNDILinkMBean](#) entity.

/management/weblogic/{version}/edit/interceptors

This resource manages a [weblogic.management.configuration.InterceptorsMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.InterceptorsMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.InterceptorsMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/interceptors](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/interceptors/interceptorCreateForm](#)
rel=interceptorCreateForm
The create form resource for this resource's interceptors collection resource.
- **uri**=[/management/weblogic/{version}/edit/interceptors/interceptors](#)
rel=interceptors
This resource's interceptors collection resource.
- **uri**=[/management/weblogic/{version}/edit](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/interceptors](#) **rel**=self
This resource.

POST

Update this [weblogic.management.configuration.InterceptorsMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.InterceptorsMBean](#) entity.

/management/weblogic/{version}/edit/interceptors/interceptorCreateForm

This resource manages the create forms for the interceptors collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.InterceptorMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the interceptors collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.InterceptorMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/interceptors/interceptorCreateForm](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/interceptors/interceptors](#) **rel**=create
The collection resource for this create form resource.
- **uri**=[/management/weblogic/{version}/edit/interceptors](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/interceptors/interceptorCreateForm](#)
rel=self
This resource.

/management/weblogic/{version}/edit/interceptors/interceptors

This resource manages a collection of [weblogic.management.configuration.InterceptorMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.InterceptorMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.InterceptorMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/interceptors/interceptors](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/interceptors/interceptorCreateForm](#)
rel=create-form
The create form resource for this collection resource.
- **uri**=[/management/weblogic/{version}/edit/interceptors](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/interceptors/interceptors](#) **rel**=self
This resource.

POST

Add a new [weblogic.management.configuration.InterceptorMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.InterceptorMBean](#) entity.

/management/weblogic/{version}/edit/interceptors/interceptors/{name}

This resource manages a [weblogic.management.configuration.InterceptorMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.InterceptorMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.InterceptorMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.InterceptorMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/interceptors/interceptors/{name}](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/interceptors/interceptors](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/interceptors/interceptors/{name}](#)
rel=self
This resource.

POST

Update this [weblogic.management.configuration.InterceptorMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.InterceptorMBean](#) entity.

/management/weblogic/{version}/edit/internalAppDeployments

This resource manages a collection of [weblogic.management.configuration.AppDeploymentMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.configuration.AppDeploymentMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.AppDeploymentMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/internalAppDeployments](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/internalAppDeployments](#) **rel**=self
This resource.

/management/weblogic/{version}/edit/internalAppDeployments/{name}

This resource manages a [weblogic.management.configuration.AppDeploymentMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.AppDeploymentMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.AppDeploymentMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/internalAppDeployments/{name}/createPlan](#) **rel**=action **title**=createPlan
This resource's createPlan action resource.
- **uri**=[/management/weblogic/{version}/edit/internalAppDeployments/{name}](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/internalAppDeployments](#)
rel=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/internalAppDeployments/{name}/redploy](#) **rel**=redploy
This resource's redploy resource.
- **uri**=[/management/weblogic/{version}/edit/internalAppDeployments/{name}](#)
rel=self
This resource.
- **uri**=[/management/weblogic/{version}/edit/internalAppDeployments/{name}/subDeploymentCreateForm](#) **rel**=subDeploymentCreateForm
The create form resource for this resource's subDeployments collection resource.
- **uri**=[/management/weblogic/{version}/edit/internalAppDeployments/{name}/subDeployments](#) **rel**=subDeployments
This resource's subDeployments collection resource.
- **uri**=[/management/weblogic/{version}/edit/internalAppDeployments/{name}/update](#) **rel**=update
This resource's update resource.

POST

Update this [weblogic.management.configuration.AppDeploymentMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.AppDeploymentMBean](#) entity.

/management/weblogic/{version}/edit/internalAppDeployments/{name}/createPlan

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

POST

Create a deployment plan in the specified directory.

Roles

Admin, Deployer

Request Body

Must contain a JSON object with the following fields:

planPath

planPath

Type: string

Response Body

Contains a JSON object with a string return field.

POST

Create a deployment plan in a default directory

Roles

Admin, Deployer

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/edit/internalAppDeployments/{name}/redeploy

The resource supports the following methods:

- [POST](#)

POST

Use the multi-part form to redeploy this application.

- `sourcePath`: the deployment to upload (required)
- `planPath`: the deployment plan to upload (optional)
- `model`: JSONObject containing an `AppDeploymentMBean` entity that contains the rest of the deployment information. However, `deployment/plan` information is ignored. (required)

This method supports both asynchronous and best effort synchronous invocations. The behavior is controlled by the 'Prefer' header. See [About Synchronous and Asynchronous Operations](#).

Roles

Admin, Deployer

/management/weblogic/{version}/edit/internalAppDeployments/{name}/subDeploymentCreateForm

This resource manages the create forms for the subDeployments collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.SubDeploymentMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the subDeployments collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/internalAppDeployments/{name}/subDeploymentCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/internalAppDeployments/{name}/subDeployments](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/internalAppDeployments/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/internalAppDeployments/{name}/subDeploymentCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/internalAppDeployments/{name}/subDeployments

This resource manages a collection of [weblogic.management.configuration.SubDeploymentMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.SubDeploymentMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.SubDeploymentMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/internalAppDeployments/{name}/subDeployments](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/internalAppDeployments/{name}/subDeploymentCreateForm](#) **rel=create-form**
The create form resource for this collection resource.
- [uri=/management/weblogic/{version}/edit/internalAppDeployments/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/internalAppDeployments/{name}/subDeployments](#) **rel=self**
This resource.

POST

Add a new [weblogic.management.configuration.SubDeploymentMBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

/management/weblogic/{version}/edit/internalAppDeployments/{name}/subDeployments/{name}

This resource manages a [weblogic.management.configuration.SubDeploymentMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/internalAppDeployments/{name}/subDeployments/{name}](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/internalAppDeployments/{name}/subDeployments](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/internalAppDeployments/{name}/subDeployments/{name}](#) **rel=self**
This resource.
- [uri=/management/weblogic/{version}/edit/internalAppDeployments/{name}/subDeployments/{name}/subDeployments](#) **rel=subDeployments**
This resource's subDeployments collection resource.

POST

Update this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

/management/weblogic/{version}/edit/internalAppDeployments/{name}/subDeployments/{name}/subDeployments

This resource manages a collection of [weblogic.management.configuration.SubDeploymentMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.configuration.SubDeploymentMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.SubDeploymentMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/internalAppDeployments/{name}/subDeployments/{name}/subDeployments](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/internalAppDeployments/{name}/subDeployments/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/internalAppDeployments/{name}/subDeployments/{name}/subDeployments](#) **rel**=self

This resource.

/management/weblogic/{version}/edit/internalAppDeployments/{name}/subDeployments/{name}/subDeployments/{name}

This resource manages a [weblogic.management.configuration.SubDeploymentMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/internalAppDeployments/{name}/subDeployments/{name}/subDeployments/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/internalAppDeployments/{name}/subDeployments/{name}/subDeployments](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/internalAppDeployments/{name}/subDeployments/{name}/subDeployments/{name}](#) **rel**=self

This resource.

- **uri**=[/management/weblogic/{version}/edit/internalAppDeployments/{name}/subDeployments/{name}/subDeployments/{name}/subDeployments](#)
rel=subDeployments

This resource's subDeployments collection resource.

POST

Update this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

/management/weblogic/{version}/edit/internalAppDeployments/{name}/update

The resource supports the following methods:

- [POST](#)

POST

Update this application.

This method supports both asynchronous and best effort synchronous invocations. The behavior is controlled by the 'Prefer' header. See *About Synchronous and Asynchronous Operations*.

Roles

Admin, Deployer

/management/weblogic/{version}/edit/internalLibraries

This resource manages a collection of [weblogic.management.configuration.LibraryMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.configuration.LibraryMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.LibraryMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/internalLibraries](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/internalLibraries](#) **rel**=self
This resource.

/management/weblogic/{version}/edit/internalLibraries/{name}

This resource manages a [weblogic.management.configuration.LibraryMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.LibraryMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.LibraryMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/internalLibraries/{name}/createPlan **rel**=createPlan
This resource's createPlan action resource.
- **uri**=/management/weblogic/{version}/edit/internalLibraries/{name} **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/edit/internalLibraries **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/edit/internalLibraries/{name}/redeploy **rel**=redeploy
This resource's redeploy resource.
- **uri**=/management/weblogic/{version}/edit/internalLibraries/{name} **rel**=self
This resource.
- **uri**=/management/weblogic/{version}/edit/internalLibraries/{name}/subDeploymentsCreateForm **rel**=subDeploymentCreateForm
The create form resource for this resource's subDeployments collection resource.
- **uri**=/management/weblogic/{version}/edit/internalLibraries/{name}/subDeployments **rel**=subDeployments
This resource's subDeployments collection resource.

POST

Update this [weblogic.management.configuration.LibraryMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.LibraryMBean](#) entity.

/management/weblogic/{version}/edit/internalLibraries/{name}/createPlan

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

POST

Create a deployment plan in the specified directory.

Roles

Admin, Deployer

Request Body

Must contain a JSON object with the following fields:

planPath

planPath

Type: string

Response Body

Contains a JSON object with a string return field.

POST

Create a deployment plan in a default directory

Roles

Admin, Deployer

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/edit/internalLibraries/{name}/redeploy

The resource supports the following methods:

- [POST](#)

POST

Use the multi-part form to redeploy a library.

- `sourcePath`: the deployment to upload (required)
- `model`: JSONObject containing a `LibraryMBean` entity that contains the rest of the deployment information (required)

This method supports both asynchronous and best effort synchronous invocations. The behavior is controlled by the 'Prefer' header. See [About Synchronous and Asynchronous Operations](#).

Roles

Admin, Deployer

/management/weblogic/{version}/edit/internalLibraries/{name}/subDeploymentCreateForm

This resource manages the create forms for the subDeployments collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.SubDeploymentMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the subDeployments collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/internalLibraries/{name}/subDeploymentsCreateForm](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/internalLibraries/{name}/subDeployments](#) **rel**=create
The collection resource for this create form resource.
- **uri**=[/management/weblogic/{version}/edit/internalLibraries/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/internalLibraries/{name}/subDeploymentsCreateForm](#) **rel**=self
This resource.

/management/weblogic/{version}/edit/internalLibraries/{name}/subDeployments

This resource manages a collection of [weblogic.management.configuration.SubDeploymentMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.SubDeploymentMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.SubDeploymentMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/internalLibraries/{name}/subDeployments](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/internalLibraries/{name}/subDeploymentCreateForm](#) **rel**=create-form

The create form resource for this collection resource.

- **uri**=[/management/weblogic/{version}/edit/internalLibraries/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/internalLibraries/{name}/subDeployments](#) **rel**=self

This resource.

POST

Add a new [weblogic.management.configuration.SubDeploymentMBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

/management/weblogic/{version}/edit/internalLibraries/{name}/subDeployments/{name}

This resource manages a [weblogic.management.configuration.SubDeploymentMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/internalLibraries/{name}/subDeployments/{name}](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/internalLibraries/{name}/subDeployments](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/internalLibraries/{name}/subDeployments/{name}](#) **rel**=self
This resource.
- **uri**=[/management/weblogic/{version}/edit/internalLibraries/{name}/subDeployments/subDeployments](#) **rel**=subDeployments
This resource's subDeployments collection resource.

POST

Update this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

/management/weblogic/{version}/edit/internalLibraries/{name}/subDeployments/{name}/subDeployments

This resource manages a collection of [weblogic.management.configuration.SubDeploymentMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.configuration.SubDeploymentMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.SubDeploymentMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/internalLibraries/{name}/subDeployments/{name}/subDeployments](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/internalLibraries/{name}/subDeployments/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/internalLibraries/{name}/subDeployments/{name}/subDeployments](#) **rel=self**
This resource.

/management/weblogic/{version}/edit/internalLibraries/{name}/subDeployments/{name}/subDeployments/{name}

This resource manages a [weblogic.management.configuration.SubDeploymentMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/internalLibraries/{name}/subDeployments/{name}/subDeployments/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/internalLibraries/{name}/subDeployments/{name}/subDeployments **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/internalLibraries/{name}/subDeployments/{name}/subDeployments/{name} **rel**=self

This resource.

- **uri**=/management/weblogic/{version}/edit/internalLibraries/{name}/subDeployments/{name}/subDeployments/{name}/subDeployments **rel**=subDeployments

This resource's subDeployments collection resource.

POST

Update this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

/management/weblogic/{version}/edit/JDBCStoreCreateForm

This resource manages the create forms for the JDBCStores collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.JDBCStoreMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the JDBCStores collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.JDBCStoreMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/JDBCStoreCreateForm](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/JDBCStores](#) **rel**=create
The collection resource for this create form resource.
- **uri**=[/management/weblogic/{version}/edit](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/JDBCStoreCreateForm](#) **rel**=self
This resource.

/management/weblogic/{version}/edit/JDBCStores

This resource manages a collection of [weblogic.management.configuration.JDBCStoreMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.JDBCStoreMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.JDBCStoreMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/JDBCStores](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/JDBCStoreCreateForm](#)
rel=create-form
The create form resource for this collection resource.
- **uri**=[/management/weblogic/{version}/edit](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/JDBCStores](#) **rel**=self
This resource.

POST

Add a new [weblogic.management.configuration.JDBCStoreMBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.JDBCStoreMBean](#) entity.

/management/weblogic/{version}/edit/JDBCStores/{name}

This resource manages a [weblogic.management.configuration.JDBCStoreMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.JDBCStoreMBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.management.configuration.JDBCStoreMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.JDBCStoreMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/JDBCStores/{name}](#) **rel**=canonical
This resource.
- **rel**=dataSource
This resource's dataSource reference to a [weblogic.management.configuration.JDBCSystemResourceMBean](#) resource.
- **uri**=[/management/weblogic/{version}/edit/JDBCStores](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/JDBCStores/{name}](#) **rel**=self
This resource.

POST

Update this [weblogic.management.configuration.JDBCStoreMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.JDBCStoreMBean](#) entity.

/management/weblogic/{version}/edit/JDBCSystemResourceCreateForm

This resource manages the create forms for the JDBCSystemResources collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.JDBCSystemResourceMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the JDBCSystemResources collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.JDBCSystemResourceMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/JDBCSystemResourceCreateForm](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/JDBCSystemResources](#) **rel**=create
The collection resource for this create form resource.
- **uri**=[/management/weblogic/{version}/edit](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/JDBCSystemResourceCreateForm](#)
rel=self
This resource.

/management/weblogic/{version}/edit/JDBCSystemResources

This resource manages a collection of [weblogic.management.configuration.JDBCSystemResourceMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.JDBCSystemResourceMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.JDBCSystemResourceMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/JDBCSystemResources](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/JDBCSystemResourceCreateForm](#)
rel=create-form
The create form resource for this collection resource.
- **uri**=[/management/weblogic/{version}/edit](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/JDBCSystemResources](#) **rel**=self
This resource.

POST

Add a new [weblogic.management.configuration.JDBCSystemResourceMBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.JDBCSystemResourceMBean](#) entity.

/management/weblogic/{version}/edit/JDBCSystemResources/{name}

This resource manages a [weblogic.management.configuration.JDBCSystemResourceMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

DELETE

Delete this [weblogic.management.configuration.JDBCSystemResourceMBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.management.configuration.JDBCSystemResourceMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.JDBCSystemResourceMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/JDBCSystemResources/{name}/JDBCResource](#) **rel**=JDBCResource
This resource's JDBCResource singleton resource.
- **uri**=[/management/weblogic/{version}/edit/JDBCSystemResources/{name}](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/JDBCSystemResources](#) **rel**=parent
The parent resource of this resource.
- **rel**=resource
This resource's resource reference to a [weblogic.descriptor.DescriptorBean](#) resource.
- **uri**=[/management/weblogic/{version}/edit/JDBCSystemResources/{name}](#) **rel**=self
This resource.
- **uri**=[/management/weblogic/{version}/edit/JDBCSystemResources/{name}/subDeploymentCreateForm](#) **rel**=subDeploymentCreateForm
The create form resource for this resource's subDeployments collection resource.
- **uri**=[/management/weblogic/{version}/edit/JDBCSystemResources/{name}/subDeployments](#) **rel**=subDeployments
This resource's subDeployments collection resource.

POST

Update this [weblogic.management.configuration.JDBCSystemResourceMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.JDBCSystemResourceMBean](#) entity.

/management/weblogic/{version}/edit/JDBCSystemResources/{name}/JDBCResource

This resource manages a [weblogic.j2ee.descriptor.wl.JDBCDataSourceBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.JDBCDataSourceBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.JDBCDataSourceBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/JDBCSystemResources/{name}/JDBCResource/JDBCConnectionPoolParams **rel**=JDBCConnectionPoolParams
This resource's JDBCConnectionPoolParams singleton resource.
- **uri**=/management/weblogic/{version}/edit/JDBCSystemResources/{name}/JDBCResource/JDBCDataSourceParams **rel**=JDBCDataSourceParams
This resource's JDBCDataSourceParams singleton resource.
- **uri**=/management/weblogic/{version}/edit/JDBCSystemResources/{name}/JDBCResource/JBCDriverParams **rel**=JBCDriverParams
This resource's JBCDriverParams singleton resource.
- **uri**=/management/weblogic/{version}/edit/JDBCSystemResources/{name}/JDBCResource/JBCOracleParams **rel**=JBCOracleParams
This resource's JBCOracleParams singleton resource.
- **uri**=/management/weblogic/{version}/edit/JDBCSystemResources/{name}/JDBCResource/JBCXAParams **rel**=JBCXAParams
This resource's JBCXAParams singleton resource.
- **uri**=/management/weblogic/{version}/edit/JDBCSystemResources/{name}/JDBCResource **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/edit/JDBCSystemResources/{name}/JDBCResource/internalProperties **rel**=internalProperties
This resource's internalProperties singleton resource.
- **uri**=/management/weblogic/{version}/edit/JDBCSystemResources/{name} **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/edit/JDBCSystemResources/{name}/JDBCResource **rel**=self
This resource.

POST

Update this [weblogic.j2ee.descriptor.wl.JDBCDataSourceBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.JDBCDataSourceBean](#) entity.

/management/weblogic/{version}/edit/JDBCSystemResources/{name}/JDBCResource/internalProperties

This resource manages a [weblogic.j2ee.descriptor.wl.JDBCPropertiesBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.j2ee.descriptor.wl.JDBCPropertiesBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.JDBCPropertiesBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/JDBCSystemResources/{name}/JDBCResource/internalProperties](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/JDBCSystemResources/{name}/JDBCResource](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/JDBCSystemResources/{name}/JDBCResource/internalProperties/properties](#) **rel=properties**
This resource's properties collection resource.
- [uri=/management/weblogic/{version}/edit/JDBCSystemResources/{name}/JDBCResource/internalProperties/propertyCreateForm](#) **rel=propertyCreateForm**
The create form resource for this resource's properties collection resource.
- [uri=/management/weblogic/{version}/edit/JDBCSystemResources/{name}/JDBCResource/internalProperties](#) **rel=self**
This resource.

/management/weblogic/{version}/edit/JDBCSystemResources/{name}/JDBCResource/internalProperties/properties

This resource manages a collection of [weblogic.j2ee.descriptor.wl.JDBCPropertyBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.j2ee.descriptor.wl.JDBCPropertyBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.j2ee.descriptor.wl.JDBCPropertyBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/JDBCSystemResources/{name}/JDBCResource/internalProperties/properties](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/JDBCSystemResources/{name}/JDBCResource/internalProperties/propertyCreateForm](#) **rel=create-form**

The create form resource for this collection resource.

- [uri=/management/weblogic/{version}/edit/JDBCSystemResources/{name}/JDBCResource/internalProperties](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/JDBCSystemResources/{name}/JDBCResource/internalProperties/properties](#) **rel=self**

This resource.

POST

Add a new [weblogic.j2ee.descriptor.wl.JDBCPropertyBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.JDBCPropertyBean](#) entity.

/management/weblogic/{version}/edit/JDBCSystemResources/{name}/JDBCResource/internalProperties/properties/{name}

This resource manages a [weblogic.j2ee.descriptor.wl.JDBCPropertyBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.j2ee.descriptor.wl.JDBCPropertyBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.j2ee.descriptor.wl.JDBCPropertyBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.JDBCPropertyBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/JDBCSystemResources/{name}/JDBCResource/internalProperties/properties/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/JDBCSystemResources/{name}/JDBCResource/internalProperties/properties **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/JDBCSystemResources/{name}/JDBCResource/internalProperties/properties/{name} **rel**=self

This resource.

POST

Update this [weblogic.j2ee.descriptor.wl.JDBCPropertyBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.JDBCPropertyBean](#) entity.

/management/weblogic/{version}/edit/JDBCSystemResources/{name}/JDBCResource/internalProperties/propertyCreateForm

This resource manages the create forms for the properties collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.j2ee.descriptor.wl.JDBCPropertyBean](#) entity populated with default values that can be customized then posted (using the POST method) to the properties collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.JDBCPropertyBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/JDBCSystemResources/{name}/JDBCResource/internalProperties/propertyCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/JDBCSystemResources/{name}/JDBCResource/internalProperties/properties](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/JDBCSystemResources/{name}/JDBCResource/internalProperties](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/JDBCSystemResources/{name}/JDBCResource/internalProperties/propertyCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/JDBCSystemResources/{name}/JDBCResource/JDBCConnectionPoolParams

This resource manages a [weblogic.j2ee.descriptor.wl.JDBCConnectionPoolParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.JDBCConnectionPoolParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.JDBCConnectionPoolParamsBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/JDBCSystemResources/{name}/JDBCResource/JDBCConnectionPoolParams](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/JDBCSystemResources/{name}/JDBCResource](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/JDBCSystemResources/{name}/JDBCResource/JDBCConnectionPoolParams](#) **rel=self**

This resource.

POST

Update this [weblogic.j2ee.descriptor.wl.JDBCConnectionPoolParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.JDBCConnectionPoolParamsBean](#) entity.

/management/weblogic/{version}/edit/JDBCSystemResources/{name}/JDBCResource/JDBCDataSourceParams

This resource manages a [weblogic.j2ee.descriptor.wl.JDBCDataSourceParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.JDBCDataSourceParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.JDBCDataSourceParamsBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/JDBCSystemResources/{name}/JDBCResource/JDBCDataSourceParams **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/edit/JDBCSystemResources/{name}/JDBCResource **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/edit/JDBCSystemResources/{name}/JDBCResource/JDBCDataSourceParams **rel**=self
This resource.

POST

Update this [weblogic.j2ee.descriptor.wl.JDBCDataSourceParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.JDBCDataSourceParamsBean](#) entity.

GET

Get this [weblogic.j2ee.descriptor.wl.JDBCDataSource](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.JDBCDataSource](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/JDBCSystemResources/{name}/JDBCResource/JDBCDataSource rel=canonical](#)

This resource.

- [uri=/management/weblogic/{version}/edit/JDBCSystemResources/{name}/JDBCResource rel=parent](#)

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/JDBCSystemResources/{name}/JDBCResource/JDBCDataSource/properties rel=properties](#)

This resource's properties singleton resource.

- [uri=/management/weblogic/{version}/edit/JDBCSystemResources/{name}/JDBCResource/JDBCDataSource rel=self](#)

This resource.

POST

Update this [weblogic.j2ee.descriptor.wl.JDBCdriverParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.JDBCdriverParamsBean](#) entity.

GET

Get this [weblogic.j2ee.descriptor.wl.JDBCPropertiesBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.JDBCPropertiesBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/JDBCSystemResources/{name}/JDBCResource/JDBCDriverParams/properties **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/JDBCSystemResources/{name}/JDBCResource/JDBCDriverParams **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/JDBCSystemResources/{name}/JDBCResource/JDBCDriverParams/properties/properties **rel**=properties

This resource's properties collection resource.

- **uri**=/management/weblogic/{version}/edit/JDBCSystemResources/{name}/JDBCResource/JDBCDriverParams/properties/propertyCreateForm **rel**=propertyCreateForm

The create form resource for this resource's properties collection resource.

- **uri**=/management/weblogic/{version}/edit/JDBCSystemResources/{name}/JDBCResource/JDBCDriverParams/properties **rel**=self

This resource.

GET

Get this collection of [weblogic.j2ee.descriptor.wl.JDBCPropertyBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.j2ee.descriptor.wl.JDBCPropertyBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/JDBCSystemResources/{name}/JDBCResource/JDBCDriverParams/properties/properties **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/JDBCSystemResources/{name}/JDBCResource/JDBCDriverParams/properties/propertyCreateForm **rel**=create-form

The create form resource for this collection resource.

- **uri**=/management/weblogic/{version}/edit/JDBCSystemResources/{name}/JDBCResource/JDBCDriverParams/properties **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/JDBCSystemResources/{name}/JDBCResource/JDBCDriverParams/properties/properties **rel**=self

This resource.

POST

Add a new [weblogic.j2ee.descriptor.wl.JDBCPropertyBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.JDBCPropertyBean](#) entity.

/management/weblogic/{version}/edit/JDBCSystemResources/{name}/JDBCResource/JBCDriverParams/properties/properties/{name}

This resource manages a [weblogic.j2ee.descriptor.wl.JDBCPropertyBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

DELETE

Delete this [weblogic.j2ee.descriptor.wl.JDBCPropertyBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.j2ee.descriptor.wl.JDBCPropertyBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.JDBCPropertyBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/JDBCSystemResources/{name}/JDBCResource/JDBCDriverParams/properties/properties/{name} **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/edit/JDBCSystemResources/{name}/JDBCResource/JDBCDriverParams/properties/properties **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/edit/JDBCSystemResources/{name}/JDBCResource/JDBCDriverParams/properties/properties/{name} **rel**=self
This resource.

POST

Update this [weblogic.j2ee.descriptor.wl.JDBCPropertyBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.JDBCPropertyBean](#) entity.

/management/weblogic/{version}/edit/JDBCSystemResources/{name}/JDBCResource/JDBCDriverParams/properties/propertyCreateForm

This resource manages the create forms for the properties collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.j2ee.descriptor.wl.JDBCPropertyBean](#) entity populated with default values that can be customized then posted (using the POST method) to the properties collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.JDBCPropertyBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/JDBCSystemResources/{name}/JDBCResource/JBCDriverParams/properties/propertyCreateForm **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/edit/JDBCSystemResources/{name}/JDBCResource/JBCDriverParams/properties/properties **rel**=create
The collection resource for this create form resource.
- **uri**=/management/weblogic/{version}/edit/JDBCSystemResources/{name}/JDBCResource/JBCDriverParams/properties **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/edit/JDBCSystemResources/{name}/JDBCResource/JBCDriverParams/properties/propertyCreateForm **rel**=self
This resource.

/management/weblogic/{version}/edit/JDBCSystemResources/{name}/JDBCResource/JDBCOracleParams

This resource manages a [weblogic.j2ee.descriptor.wl.JDBCOracleParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.JDBCOracleParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.JDBCOracleParamsBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/JDBCSystemResources/{name}/JDBCResource/JDBCOracleParams](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/JDBCSystemResources/{name}/JDBCResource](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/JDBCSystemResources/{name}/JDBCResource/JDBCOracleParams](#) **rel**=self

This resource.

POST

Update this [weblogic.j2ee.descriptor.wl.JDBCOracleParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.JDBCOracleParamsBean](#) entity.

/management/weblogic/{version}/edit/JDBCSystemResources/{name}/JDBCResource/JDBCXAParams

This resource manages a [weblogic.j2ee.descriptor.wl.JDBCXAParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.JDBCXAParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.JDBCXAParamsBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/JDBCSystemResources/{name}/JDBCResource/JDBCXAParams](#) [rel=canonical](#)
This resource.
- [uri=/management/weblogic/{version}/edit/JDBCSystemResources/{name}/JDBCResource](#) [rel=parent](#)
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/JDBCSystemResources/{name}/JDBCResource/JDBCXAParams](#) [rel=self](#)
This resource.

POST

Update this [weblogic.j2ee.descriptor.wl.JDBCXAParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.JDBCXAParamsBean](#) entity.

/management/weblogic/{version}/edit/JDBCSystemResources/{name}/subDeploymentCreateForm

This resource manages the create forms for the subDeployments collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.SubDeploymentMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the subDeployments collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/JDBCSystemResources/{name}/subDeploymentCreateForm rel=canonical](#)
This resource.
- [uri=/management/weblogic/{version}/edit/JDBCSystemResources/{name}/subDeployments rel=create](#)
The collection resource for this create form resource.
- [uri=/management/weblogic/{version}/edit/JDBCSystemResources/{name} rel=parent](#)
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/JDBCSystemResources/{name}/subDeploymentCreateForm rel=self](#)
This resource.

/management/weblogic/{version}/edit/JDBCSystemResources/{name}/subDeployments

This resource manages a collection of [weblogic.management.configuration.SubDeploymentMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.SubDeploymentMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.SubDeploymentMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/JDBCSystemResources/{name}/subDeployments](#) [rel=canonical](#)
This resource.
- [uri=/management/weblogic/{version}/edit/JDBCSystemResources/{name}/subDeploymentCreateForm](#) [rel=create-form](#)
The create form resource for this collection resource.
- [uri=/management/weblogic/{version}/edit/JDBCSystemResources/{name}](#) [rel=parent](#)
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/JDBCSystemResources/{name}/subDeployments](#) [rel=self](#)
This resource.

POST

Add a new [weblogic.management.configuration.SubDeploymentMBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

/management/weblogic/{version}/edit/JDBCSystemResources/{name}/subDeployments/{name}

This resource manages a [weblogic.management.configuration.SubDeploymentMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/JDBCSystemResources/{name}/subDeployments/{name}](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/JDBCSystemResources/{name}/subDeployments](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/JDBCSystemResources/{name}/subDeployments/{name}](#) **rel=self**
This resource.
- [uri=/management/weblogic/{version}/edit/JDBCSystemResources/{name}/subDeployments/{name}/subDeployments](#) **rel=subDeployments**
This resource's subDeployments collection resource.

POST

Update this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

/management/weblogic/{version}/edit/JDBCSystemResources/{name}/subDeployments/{name}/subDeployments

This resource manages a collection of [weblogic.management.configuration.SubDeploymentMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.configuration.SubDeploymentMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.SubDeploymentMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/JDBCSystemResources/{name}/subDeployments/{name}/subDeployments](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/JDBCSystemResources/{name}/subDeployments/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/JDBCSystemResources/{name}/subDeployments/{name}/subDeployments](#) **rel=self**
This resource.

/management/weblogic/{version}/edit/JDBCSystemResources/{name}/subDeployments/{name}/subDeployments/{name}

This resource manages a [weblogic.management.configuration.SubDeploymentMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/JDBCSystemResources/{name}/subDeployments/{name}/subDeployments/{name} **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/edit/JDBCSystemResources/{name}/subDeployments/{name}/subDeployments **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/edit/JDBCSystemResources/{name}/subDeployments/{name}/subDeployments/{name} **rel**=self
This resource.
- **uri**=/management/weblogic/{version}/edit/JDBCSystemResources/{name}/subDeployments/{name}/subDeployments/{name}/subDeployments **rel**=subDeployments
This resource's subDeployments collection resource.

POST

Update this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

/management/weblogic/{version}/edit/JMSBridgeDestinationCreateForm

This resource manages the create forms for the JMSBridgeDestinations collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.JMSBridgeDestinationMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the JMSBridgeDestinations collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.JMSBridgeDestinationMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/JMSBridgeDestinationCreateForm](#)
rel=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/JMSBridgeDestinations](#) **rel**=create

The collection resource for this create form resource.

- **uri**=[/management/weblogic/{version}/edit](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/JMSBridgeDestinationCreateForm](#)
rel=self

This resource.

/management/weblogic/{version}/edit/JMSBridgeDestinations

This resource manages a collection of [weblogic.management.configuration.JMSBridgeDestinationMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.JMSBridgeDestinationMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.JMSBridgeDestinationMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/JMSBridgeDestinations](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/JMSBridgeDestinationCreateForm](#)
rel=create-form
The create form resource for this collection resource.
- **uri**=[/management/weblogic/{version}/edit](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/JMSBridgeDestinations](#) **rel**=self
This resource.

POST

Add a new [weblogic.management.configuration.JMSBridgeDestinationMBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.JMSBridgeDestinationMBean](#) entity.

/management/weblogic/{version}/edit/JMSBridgeDestinations/{name}

This resource manages a [weblogic.management.configuration.JMSBridgeDestinationMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.JMSBridgeDestinationMBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.management.configuration.JMSBridgeDestinationMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.JMSBridgeDestinationMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/JMSBridgeDestinations/{name}](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/JMSBridgeDestinations](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/JMSBridgeDestinations/{name}](#)
rel=self
This resource.

POST

Update this [weblogic.management.configuration.JMSBridgeDestinationMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.JMSBridgeDestinationMBean](#) entity.

/management/weblogic/{version}/edit/JMSInteropModuleCreateForm

This resource manages the create forms for the JMSInteropModules collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.JMSInteropModuleMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the JMSInteropModules collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.JMSInteropModuleMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/JMSInteropModuleCreateForm](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules](#) **rel**=create
The collection resource for this create form resource.
- **uri**=[/management/weblogic/{version}/edit](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/JMSInteropModuleCreateForm](#)
rel=self
This resource.

/management/weblogic/{version}/edit/JMSInteropModules

This resource manages a collection of [weblogic.management.configuration.JMSInteropModuleMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.JMSInteropModuleMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.JMSInteropModuleMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/JMSInteropModuleCreateForm](#)
rel=create-form
The create form resource for this collection resource.
- **uri**=[/management/weblogic/{version}/edit](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules](#) **rel**=self
This resource.

POST

Add a new [weblogic.management.configuration.JMSInteropModuleMBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.JMSInteropModuleMBean](#) entity.

/management/weblogic/{version}/edit/JMSInteropModules/{name}

This resource manages a [weblogic.management.configuration.JMSInteropModuleMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.JMSInteropModuleMBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.management.configuration.JMSInteropModuleMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.JMSInteropModuleMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource](#) **rel**=JMSResource
This resource's JMSResource singleton resource.
- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules](#) **rel**=parent
The parent resource of this resource.
- **rel**=resource
This resource's resource reference to a [weblogic.descriptor.DescriptorBean](#) resource.
- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}](#) **rel**=self
This resource.
- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/subDeploymentCreateForm](#) **rel**=subDeploymentCreateForm
The create form resource for this resource's subDeployments collection resource.
- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/subDeployments](#) **rel**=subDeployments
This resource's subDeployments collection resource.

POST

POST

Update this [weblogic.management.configuration.JMSInteropModuleMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.JMSInteropModuleMBean](#) entity.

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource

This resource manages a [weblogic.j2ee.descriptor.wl.JMSBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.JMSBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.JMSBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/SAFErrorHandlingCreateForm](#) **rel**=SAFErrorHandlingCreateForm
The create form resource for this resource's SAFErrorHandlings collection resource.
- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/SAFErrorHandlings](#) **rel**=SAFErrorHandlings
This resource's SAFErrorHandlings collection resource.
- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/SAFImportedDestinationCreateForm](#) **rel**=SAFImportedDestinationCreateForm
The create form resource for this resource's SAFImportedDestinations collection resource.
- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/SAFImportedDestinations](#) **rel**=SAFImportedDestinations
This resource's SAFImportedDestinations collection resource.
- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/SAFRemoteContextCreateForm](#) **rel**=SAFRemoteContextCreateForm
The create form resource for this resource's SAFRemoteContexts collection resource.
- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/SAFRemoteContexts](#) **rel**=SAFRemoteContexts
This resource's SAFRemoteContexts collection resource.
- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/connectionFactories](#) **rel**=connectionFactories
This resource's connectionFactories collection resource.
- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/connectionFactoryCreateForm](#) **rel**=connectionFactoryCreateForm
The create form resource for this resource's connectionFactories collection resource.

- **uri**=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/destinationKeyCreateForm **rel**=destinationKeyCreateForm
The create form resource for this resource's destinationKeys collection resource.
- **uri**=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/destinationKeys **rel**=destinationKeys
This resource's destinationKeys collection resource.
- **uri**=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/foreignServerCreateForm **rel**=foreignServerCreateForm
The create form resource for this resource's foreignServers collection resource.
- **uri**=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/foreignServers **rel**=foreignServers
This resource's foreignServers collection resource.
- **uri**=/management/weblogic/{version}/edit/JMSInteropModules/{name} **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/queueCreateForm **rel**=queueCreateForm
The create form resource for this resource's queues collection resource.
- **uri**=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/queues **rel**=queues
This resource's queues collection resource.
- **uri**=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/quotaCreateForm **rel**=quotaCreateForm
The create form resource for this resource's quotas collection resource.
- **uri**=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/quotas **rel**=quotas
This resource's quotas collection resource.
- **uri**=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource **rel**=self
This resource.
- **uri**=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/templateCreateForm **rel**=templateCreateForm
The create form resource for this resource's templates collection resource.
- **uri**=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/templates **rel**=templates
This resource's templates collection resource.
- **uri**=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/topicCreateForm **rel**=topicCreateForm
The create form resource for this resource's topics collection resource.
- **uri**=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/topics **rel**=topics
This resource's topics collection resource.

- **uri**=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/uniformDistributedQueueCreateForm
rel=uniformDistributedQueueCreateForm
The create form resource for this resource's uniformDistributedQueues collection resource.
- **uri**=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/uniformDistributedQueues **rel**=uniformDistributedQueues
This resource's uniformDistributedQueues collection resource.
- **uri**=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/uniformDistributedTopicCreateForm
rel=uniformDistributedTopicCreateForm
The create form resource for this resource's uniformDistributedTopics collection resource.
- **uri**=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/uniformDistributedTopics **rel**=uniformDistributedTopics
This resource's uniformDistributedTopics collection resource.

POST

Update this [weblogic.j2ee.descriptor.wl.JMSBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.JMSBean](#) entity.

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/connectionFactories

This resource manages a collection of [weblogic.j2ee.descriptor.wl.JMSConnectionFactoryBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.j2ee.descriptor.wl.JMSConnectionFactoryBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.j2ee.descriptor.wl.JMSConnectionFactoryBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/connectionFactories](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/connectionFactoryCreateForm](#) **rel=create-form**

The create form resource for this collection resource.

- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/connectionFactories](#) **rel=self**

This resource.

POST

Add a new [weblogic.j2ee.descriptor.wl.JMSConnectionFactoryBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.JMSConnectionFactoryBean](#) entity.

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/connectionFactories/{name}

This resource manages a [weblogic.j2ee.descriptor.wl.JMSConnectionFactoryBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

DELETE

Delete this [weblogic.j2ee.descriptor.wl.JMSConnectionFactoryBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.j2ee.descriptor.wl.JMSConnectionFactoryBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.JMSConnectionFactoryBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/connectionFactories/{name}](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/connectionFactories/{name}/clientParams](#) **rel=clientParams**
This resource's clientParams singleton resource.
- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/connectionFactories/{name}/defaultDeliveryParams](#) **rel=defaultDeliveryParams**
This resource's defaultDeliveryParams singleton resource.
- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/connectionFactories/{name}/flowControlParams](#) **rel=flowControlParams**
This resource's flowControlParams singleton resource.
- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/connectionFactories/{name}/loadBalancingParams](#) **rel=loadBalancingParams**
This resource's loadBalancingParams singleton resource.
- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/connectionFactories](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/connectionFactories/{name}/securityParams](#) **rel=securityParams**
This resource's securityParams singleton resource.
- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/connectionFactories/{name}](#) **rel=self**
This resource.
- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/connectionFactories/{name}/transactionParams](#) **rel=transactionParams**
This resource's transactionParams singleton resource.

POST

Update this [weblogic.j2ee.descriptor.wl.JMSConnectionFactoryBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.JMSConnectionFactoryBean](#) entity.

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/connectionFactories/{name}/clientParams

This resource manages a [weblogic.j2ee.descriptor.wl.ClientParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.ClientParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.ClientParamsBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/connectionFactories/{name}/clientParams](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/connectionFactories/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/connectionFactories/{name}/clientParams](#) **rel**=self

This resource.

POST

Update this [weblogic.j2ee.descriptor.wl.ClientParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.ClientParamsBean](#) entity.

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/connectionFactories/{name}/defaultDeliveryParams

This resource manages a [weblogic.j2ee.descriptor.wl.DefaultDeliveryParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.DefaultDeliveryParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.DefaultDeliveryParamsBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/connectionFactories/{name}/defaultDeliveryParams](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/connectionFactories/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/connectionFactories/{name}/defaultDeliveryParams](#) **rel**=self

This resource.

POST

Update this [weblogic.j2ee.descriptor.wl.DefaultDeliveryParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.DefaultDeliveryParamsBean](#) entity.

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/connectionFactories/{name}/flowControlParams

This resource manages a [weblogic.j2ee.descriptor.wl.FlowControlParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.FlowControlParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.FlowControlParamsBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/connectionFactories/{name}/flowControlParams](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/connectionFactories/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/connectionFactories/{name}/flowControlParams](#) **rel**=self

This resource.

POST

Update this [weblogic.j2ee.descriptor.wl.FlowControlParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.FlowControlParamsBean](#) entity.

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/connectionFactories/{name}/loadBalancingParams

This resource manages a [weblogic.j2ee.descriptor.wl.LoadBalancingParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.LoadBalancingParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.LoadBalancingParamsBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/connectionFactories/{name}/loadBalancingParams](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/connectionFactories/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/connectionFactories/{name}/loadBalancingParams](#) **rel=self**

This resource.

POST

Update this [weblogic.j2ee.descriptor.wl.LoadBalancingParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.LoadBalancingParamsBean](#) entity.

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/connectionFactories/{name}/securityParams

This resource manages a [weblogic.j2ee.descriptor.wl.SecurityParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.SecurityParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.SecurityParamsBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/connectionFactories/{name}/securityParams](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/connectionFactories/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/connectionFactories/{name}/securityParams](#) **rel**=self

This resource.

POST

Update this [weblogic.j2ee.descriptor.wl.SecurityParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.SecurityParamsBean](#) entity.

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/connectionFactories/{name}/transactionParams

This resource manages a [weblogic.j2ee.descriptor.wl.TransactionParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.TransactionParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.TransactionParamsBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/connectionFactories/{name}/transactionParams](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/connectionFactories/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/connectionFactories/{name}/transactionParams](#) **rel=self**

This resource.

POST

Update this [weblogic.j2ee.descriptor.wl.TransactionParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.TransactionParamsBean](#) entity.

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/connectionFactoryCreateForm

This resource manages the create forms for the connectionFactories collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.j2ee.descriptor.wl.JMSConnectionFactoryBean](#) entity populated with default values that can be customized then posted (using the POST method) to the connectionFactories collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.JMSConnectionFactoryBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/connectionFactoryCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/connectionFactories](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/connectionFactoryCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/destinationKeyCreateForm

This resource manages the create forms for the destinationKeys collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.j2ee.descriptor.wl.DestinationKeyBean](#) entity populated with default values that can be customized then posted (using the POST method) to the `destinationKeys` collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.DestinationKeyBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/destinationKeyCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/destinationKeys](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/destinationKeyCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/destinationKeys

This resource manages a collection of [weblogic.j2ee.descriptor.wl.DestinationKeyBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.j2ee.descriptor.wl.DestinationKeyBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.j2ee.descriptor.wl.DestinationKeyBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/destinationKeys](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/destinationKeyCreateForm](#) **rel**=create-form

The create form resource for this collection resource.

- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/destinationKeys](#) **rel**=self

This resource.

POST

Add a new [weblogic.j2ee.descriptor.wl.DestinationKeyBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.DestinationKeyBean](#) entity.

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/destinationKeys/{name}

This resource manages a [weblogic.j2ee.descriptor.wl.DestinationKeyBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.j2ee.descriptor.wl.DestinationKeyBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.j2ee.descriptor.wl.DestinationKeyBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.DestinationKeyBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/destinationKeys/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/destinationKeys](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/destinationKeys/{name}](#) **rel**=self

This resource.

POST

Update this [weblogic.j2ee.descriptor.wl.DestinationKeyBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.DestinationKeyBean](#) entity.

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/foreignServerCreateForm

This resource manages the create forms for the foreignServers collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.j2ee.descriptor.wl.ForeignServerBean](#) entity populated with default values that can be customized then posted (using the POST method) to the `foreignServers` collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.ForeignServerBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/foreignServerCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/foreignServers](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/foreignServerCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/foreignServers

This resource manages a collection of [weblogic.j2ee.descriptor.wl.ForeignServerBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.j2ee.descriptor.wl.ForeignServerBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.j2ee.descriptor.wl.ForeignServerBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/foreignServers](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/foreignServerCreateForm](#) **rel=create-form**

The create form resource for this collection resource.

- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/foreignServers](#) **rel=self**

This resource.

POST

Add a new [weblogic.j2ee.descriptor.wl.ForeignServerBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.ForeignServerBean](#) entity.

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/foreignServers/{name}

This resource manages a [weblogic.j2ee.descriptor.wl.ForeignServerBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.j2ee.descriptor.wl.ForeignServerBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.j2ee.descriptor.wl.ForeignServerBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.ForeignServerBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/foreignServers/{name}/JNDIProperties](#) **rel=JNDIProperties**
This resource's JNDIProperties collection resource.
- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/foreignServers/{name}/JNDIPropertyCreateForm](#) **rel=JNDIPropertyCreateForm**
The create form resource for this resource's JNDIProperties collection resource.
- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/foreignServers/{name}](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/foreignServers/{name}/foreignConnectionFactories](#) **rel=foreignConnectionFactories**
This resource's foreignConnectionFactories collection resource.
- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/foreignServers/{name}/foreignConnectionFactoryCreateForm](#) **rel=foreignConnectionFactoryCreateForm**
The create form resource for this resource's foreignConnectionFactories collection resource.
- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/foreignServers/{name}/foreignDestinationCreateForm](#) **rel=foreignDestinationCreateForm**
The create form resource for this resource's foreignDestinations collection resource.
- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/foreignServers/{name}/foreignDestinations](#) **rel=foreignDestinations**
This resource's foreignDestinations collection resource.
- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/foreignServers](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/foreignServers/{name}](#) **rel=self**
This resource.

POST

Update this [weblogic.j2ee.descriptor.wl.ForeignServerBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.ForeignServerBean](#) entity.

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/foreignServers/{name}/foreignConnectionFactories

This resource manages a collection of [weblogic.j2ee.descriptor.wl.ForeignConnectionFactoryBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.j2ee.descriptor.wl.ForeignConnectionFactoryBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.j2ee.descriptor.wl.ForeignConnectionFactoryBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/foreignServers/{name}/foreignConnectionFactories](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/foreignServers/{name}/foreignConnectionFactoryCreateForm](#) **rel**=create-form

The create form resource for this collection resource.

- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/foreignServers/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/foreignServers/{name}/foreignConnectionFactories](#) **rel**=self

This resource.

POST

Add a new [weblogic.j2ee.descriptor.wl.ForeignConnectionFactoryBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.ForeignConnectionFactoryBean](#) entity.

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/foreignServers/{name}/foreignConnectionFactory/{name}

This resource manages a [weblogic.j2ee.descriptor.wl.ForeignConnectionFactoryBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.j2ee.descriptor.wl.ForeignConnectionFactoryBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.j2ee.descriptor.wl.ForeignConnectionFactoryBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.ForeignConnectionFactoryBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/foreignServers/{name}/foreignConnectionFactories/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/foreignServers/{name}/foreignConnectionFactories](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/foreignServers/{name}/foreignConnectionFactories/{name}](#) **rel**=self

This resource.

POST

Update this [weblogic.j2ee.descriptor.wl.ForeignConnectionFactoryBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.ForeignConnectionFactoryBean](#) entity.

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/foreignServers/{name}/foreignConnectionFactoryCreateForm

This resource manages the create forms for the foreignConnectionFactories collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.j2ee.descriptor.wl.ForeignConnectionFactoryBean](#) entity populated with default values that can be customized then posted (using the POST method) to the `foreignConnectionFactories` collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.ForeignConnectionFactoryBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/foreignServers/{name}/foreignConnectionFactoryCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/foreignServers/{name}/foreignConnectionFactories](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/foreignServers/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/foreignServers/{name}/foreignConnectionFactoryCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/foreignServers/{name}/foreignDestinationCreateForm

This resource manages the create forms for the foreignDestinations collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.j2ee.descriptor.wl.ForeignDestinationBean](#) entity populated with default values that can be customized then posted (using the POST method) to the foreignDestinations collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.ForeignDestinationBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/foreignServers/{name}/foreignDestinationCreateForm](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/foreignServers/{name}/foreignDestinations](#) **rel=create**
The collection resource for this create form resource.
- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/foreignServers/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/foreignServers/{name}/foreignDestinationCreateForm](#) **rel=self**
This resource.

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/foreignServers/{name}/foreignDestinations

This resource manages a collection of [weblogic.j2ee.descriptor.wl.ForeignDestinationBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.j2ee.descriptor.wl.ForeignDestinationBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.j2ee.descriptor.wl.ForeignDestinationBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/foreignServers/{name}/foreignDestinations](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/foreignServers/{name}/foreignDestinationCreateForm](#) **rel=create-form**

The create form resource for this collection resource.

- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/foreignServers/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/foreignServers/{name}/foreignDestinations](#) **rel=self**

This resource.

POST

Add a new [weblogic.j2ee.descriptor.wl.ForeignDestinationBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.ForeignDestinationBean](#) entity.

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/foreignServers/{name}/foreignDestinations/{name}

This resource manages a [weblogic.j2ee.descriptor.wl.ForeignDestinationBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.j2ee.descriptor.wl.ForeignDestinationBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.j2ee.descriptor.wl.ForeignDestinationBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.ForeignDestinationBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/foreignServers/{name}/foreignDestinations/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/foreignServers/{name}/foreignDestinations](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/foreignServers/{name}/foreignDestinations/{name}](#) **rel**=self

This resource.

POST

Update this [weblogic.j2ee.descriptor.wl.ForeignDestinationBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.ForeignDestinationBean](#) entity.

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/foreignServers/{name}/JNDIProperties

This resource manages a collection of [weblogic.j2ee.descriptor.wl.PropertyBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.j2ee.descriptor.wl.PropertyBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.j2ee.descriptor.wl.PropertyBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/foreignServers/{name}/JNDIProperties](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/foreignServers/{name}/JNDIPropertyCreateForm](#) **rel**=create-form

The create form resource for this collection resource.

- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/foreignServers/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/foreignServers/{name}/JNDIProperties](#) **rel**=self

This resource.

POST

Add a new [weblogic.j2ee.descriptor.wl.PropertyBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.PropertyBean](#) entity.

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/foreignServers/{name}/JNDIProperties/{key}

This resource manages a [weblogic.j2ee.descriptor.wl.PropertyBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.j2ee.descriptor.wl.PropertyBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.j2ee.descriptor.wl.PropertyBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.PropertyBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/foreignServers/{name}/JNDIProperties/{key}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/foreignServers/{name}/JNDIProperties](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/foreignServers/{name}/JNDIProperties/{key}](#) **rel**=self

This resource.

POST

Update this [weblogic.j2ee.descriptor.wl.PropertyBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.PropertyBean](#) entity.

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/foreignServers/{name}/JNDIPropertyCreateForm

This resource manages the create forms for the JNDIProperties collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.j2ee.descriptor.wl.PropertyBean](#) entity populated with default values that can be customized then posted (using the POST method) to the JNDIProperties collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.PropertyBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/foreignServers/{name}/JNDIPropertyCreateForm](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/foreignServers/{name}/JNDIProperties](#) **rel=create**
The collection resource for this create form resource.
- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/foreignServers/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/foreignServers/{name}/JNDIPropertyCreateForm](#) **rel=self**
This resource.

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/queueCreateForm

This resource manages the create forms for the queues collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.j2ee.descriptor.wl.QueueBean](#) entity populated with default values that can be customized then posted (using the POST method) to the queues collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.QueueBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/queueCreateForm rel=canonical](#)

This resource.

- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/queues rel=create](#)

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource rel=parent](#)

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/queueCreateForm rel=self](#)

This resource.

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/queues

This resource manages a collection of [weblogic.j2ee.descriptor.wl.QueueBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.j2ee.descriptor.wl.QueueBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.j2ee.descriptor.wl.QueueBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/queues rel=canonical](#)
This resource.
- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/queuecreateForm rel=create-form](#)
The create form resource for this collection resource.
- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource rel=parent](#)
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/queues rel=self](#)
This resource.

POST

Add a new [weblogic.j2ee.descriptor.wl.QueueBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.QueueBean](#) entity.

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/queues/{name}

This resource manages a [weblogic.j2ee.descriptor.wl.QueueBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.j2ee.descriptor.wl.QueueBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.j2ee.descriptor.wl.QueueBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.QueueBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/queues/{name}](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/queues/{name}/deliveryFailureParams](#) **rel=deliveryFailureParams**
This resource's `deliveryFailureParams` singleton resource.
- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/queues/{name}/deliveryParamsOverrides](#) **rel=deliveryParamsOverrides**
This resource's `deliveryParamsOverrides` singleton resource.
- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/queues/{name}/messageLoggingParams](#) **rel=messageLoggingParams**
This resource's `messageLoggingParams` singleton resource.
- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/queues](#) **rel=parent**
The parent resource of this resource.
- **rel=quota**
This resource's quota reference to a `weblogic.j2ee.descriptor.wl.QuotaBean` resource.
- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/queues/{name}](#) **rel=self**
This resource.
- **rel=template**
This resource's template reference to a `weblogic.j2ee.descriptor.wl.TemplateBean` resource.
- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/queues/{name}/thresholds](#) **rel=thresholds**
This resource's `thresholds` singleton resource.

POST

Update this [weblogic.j2ee.descriptor.wl.QueueBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.QueueBean](#) entity.

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/queues/{name}/deliveryFailureParams

This resource manages a [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/queues/{name}/deliveryFailureParams/findSubDeploymentName](#) **rel**=action **title**=findSubDeploymentName
This resource's findSubDeploymentName action resource.
- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/queues/{name}/deliveryFailureParams](#) **rel**=canonical
This resource.
- **rel**=errorDestination
This resource's errorDestination reference to a [weblogic.j2ee.descriptor.wl.DestinationBean](#) resource.
- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/queues/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/queues/{name}/deliveryFailureParams](#) **rel**=self
This resource.
- **rel**=templateBean
This resource's templateBean reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) entity.

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/queues/{name}/deliveryFailureParams/findSubDeploymentName

The resource supports the following methods:

- [POST](#)

POST

This is used to find the sub-deployment-name for this destination.

Roles

Admin, Deployer

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/queues/{name}/deliveryParamsOverrides

This resource manages a [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/queues/{name}/deliveryParamsOverrides **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/queues/{name} **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/queues/{name}/deliveryParamsOverrides **rel**=self
This resource.
- **rel**=templateBean
This resource's templateBean reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) entity.

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/queues/{name}/messageLoggingParams

This resource manages a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/queues/{name}/messageLoggingParams](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/queues/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/queues/{name}/messageLoggingParams](#) **rel**=self

This resource.

- **rel**=templateBean

This resource's `templateBean` reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) entity.

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/queues/{name}/thresholds

This resource manages a [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/queues/{name}/thresholds **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/queues/{name} **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/queues/{name}/thresholds **rel**=self
This resource.
- **rel**=templateBean
This resource's templateBean reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) entity.

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/quotaCreateForm

This resource manages the create forms for the quotas collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.j2ee.descriptor.wl.QuotaBean](#) entity populated with default values that can be customized then posted (using the POST method) to the quotas collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.QuotaBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/quotaCreateForm](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/quotas](#) **rel**=create

The collection resource for this create form resource.

- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/quotaCreateForm](#) **rel**=self

This resource.

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/quotas

This resource manages a collection of [weblogic.j2ee.descriptor.wl.QuotaBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.j2ee.descriptor.wl.QuotaBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.j2ee.descriptor.wl.QuotaBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/quotas](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/quotaCreateForm](#) **rel**=create-form

The create form resource for this collection resource.

- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/quotas](#) **rel**=self

This resource.

POST

Add a new [weblogic.j2ee.descriptor.wl.QuotaBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.QuotaBean](#) entity.

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/quotas/{name}

This resource manages a [weblogic.j2ee.descriptor.wl.QuotaBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.j2ee.descriptor.wl.QuotaBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.j2ee.descriptor.wl.QuotaBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.QuotaBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/quotas/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/quotas](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/quotas/{name}](#) **rel**=self

This resource.

POST

Update this [weblogic.j2ee.descriptor.wl.QuotaBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.QuotaBean](#) entity.

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/SAFErorHandlingCreateForm

This resource manages the create forms for the SAFErorHandlings collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.j2ee.descriptor.wl.SAFErrorHandlingBean](#) entity populated with default values that can be customized then posted (using the POST method) to the SAFErrorHandlings collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.SAFErrorHandlingBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/SAFErrorHandlingCreateForm **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/SAFErrorHandlings **rel**=create

The collection resource for this create form resource.

- **uri**=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/SAFErrorHandlingCreateForm **rel**=self

This resource.

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/SAFEErrorHandlings

This resource manages a collection of [weblogic.j2ee.descriptor.wl.SAFEErrorHandlingBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.j2ee.descriptor.wl.SAFErrorHandlingBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.j2ee.descriptor.wl.SAFErrorHandlingBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/SAFErrorHandlings](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/SAFErrorHandlingCreateForm](#) **rel=create-form**

The create form resource for this collection resource.

- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/SAFErrorHandlings](#) **rel=self**

This resource.

POST

Add a new [weblogic.j2ee.descriptor.wl.SAFErrorHandlingBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.SAFErrorHandlingBean](#) entity.

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/SAFEErrorHandlings/{name}

This resource manages a [weblogic.j2ee.descriptor.wl.SAFEErrorHandlingBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

DELETE

Delete this [weblogic.j2ee.descriptor.wl.SAErrorHandlingBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.j2ee.descriptor.wl.SAFEErrorHandlingBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.SAFEErrorHandlingBean](#) entity.

This method can return the following links:

- **rel=SAFEErrorDestination**
This resource's SAFEErrorDestination reference to a [weblogic.j2ee.descriptor.wl.SAFDestinationBean](#) resource.
- **uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/SAFEErrorHandlings/{name} rel=canonical**
This resource.
- **uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/SAFEErrorHandlings rel=parent**
The parent resource of this resource.
- **uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/SAFEErrorHandlings/{name} rel=self**
This resource.

POST

Update this [weblogic.j2ee.descriptor.wl.SAFErrorHandlingBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.SAFErrorHandlingBean](#) entity.

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/SAFImportedDestinationCreateForm

This resource manages the create forms for the SAFImportedDestinations collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.j2ee.descriptor.wl.SAFImportedDestinationsBean](#) entity populated with default values that can be customized then posted (using the POST method) to the SAFImportedDestinations collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.SAFImportedDestinationsBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/SAFImportedDestinationCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/SAFImportedDestinations](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/SAFImportedDestinationCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/SAFImportedDestinations

This resource manages a collection of [weblogic.j2ee.descriptor.wl.SAFImportedDestinationsBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.j2ee.descriptor.wl.SAFImportedDestinationsBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.j2ee.descriptor.wl.SAFImportedDestinationsBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/SAFImportedDestinations](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/SAFImportedDestinationCreateForm](#) **rel**=create-form

The create form resource for this collection resource.

- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/SAFImportedDestinations](#) **rel**=self

This resource.

POST

Add a new [weblogic.j2ee.descriptor.wl.SAFImportedDestinationsBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.SAFImportedDestinationsBean](#) entity.

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/SAFImportedDestinations/{name}

This resource manages a [weblogic.j2ee.descriptor.wl.SAFImportedDestinationsBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.j2ee.descriptor.wl.SAFImportedDestinationsBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.j2ee.descriptor.wl.SAFImportedDestinationsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.SAFImportedDestinationsBean](#) entity.

This method can return the following links:

- **rel=SAFErrorHandling**
This resource's SAFErrorHandling reference to a [weblogic.j2ee.descriptor.wl.SAFErrorHandlingBean](#) resource.
- **uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/SAFImportedDestinations/{name}/SAFQueueCreateForm**
rel=SAFQueueCreateForm
The create form resource for this resource's SAFQueues collection resource.
- **uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/SAFImportedDestinations/{name}/SAFQueues** **rel=SAFQueues**
This resource's SAFQueues collection resource.
- **rel=SAFRemoteContext**
This resource's SAFRemoteContext reference to a [weblogic.j2ee.descriptor.wl.SAFRemoteContextBean](#) resource.
- **uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/SAFImportedDestinations/{name}/SAFTopicCreateForm**
rel=SAFTopicCreateForm
The create form resource for this resource's SAFTopics collection resource.
- **uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/SAFImportedDestinations/{name}/SAFTopics** **rel=SAFTopics**
This resource's SAFTopics collection resource.
- **uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/SAFImportedDestinations/{name}** **rel=canonical**
This resource.
- **uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/SAFImportedDestinations/{name}/messageLoggingParams**
rel=messageLoggingParams
This resource's messageLoggingParams singleton resource.
- **uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/SAFImportedDestinations** **rel=parent**
The parent resource of this resource.
- **uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/SAFImportedDestinations/{name}** **rel=self**

This resource.

POST

Update this [weblogic.j2ee.descriptor.wl.SAFImportedDestinationsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.SAFImportedDestinationsBean](#) entity.

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/SAFImportedDestinations/{name}/messageLoggingParams

This resource manages a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/SAFImportedDestinations/{name}/messageLoggingParams](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/SAFImportedDestinations/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/SAFImportedDestinations/{name}/messageLoggingParams](#) **rel**=self

This resource.

- **rel**=templateBean

This resource's `templateBean` reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) entity.

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/SAFImportedDestinations/{name}/SAFQueueCreateForm

This resource manages the create forms for the SAFQueues collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.j2ee.descriptor.wl.SAFQueueBean](#) entity populated with default values that can be customized then posted (using the POST method) to the SAFQueues collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.SAFQueueBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/SAFImportedDestinations/{name}/SAFQueueCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/SAFImportedDestinations/{name}/SAFQueues](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/SAFImportedDestinations/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/SAFImportedDestinations/{name}/SAFQueueCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/SAFImportedDestinations/{name}/SAFQueues

This resource manages a collection of [weblogic.j2ee.descriptor.wl.SAFQueueBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.j2ee.descriptor.wl.SAFQueueBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.j2ee.descriptor.wl.SAFQueueBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/SAFImportedDestinations/{name}/SAFQueues](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/SAFImportedDestinations/{name}/SAFQueueCreateForm](#) **rel=create-form**
The create form resource for this collection resource.
- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/SAFImportedDestinations/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/SAFImportedDestinations/{name}/SAFQueues](#) **rel=self**
This resource.

POST

Add a new [weblogic.j2ee.descriptor.wl.SAFQueueBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.SAFQueueBean](#) entity.

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/SAFImportedDestinations/{name}/SAFQueues/{name}

This resource manages a [weblogic.j2ee.descriptor.wl.SAFQueueBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.j2ee.descriptor.wl.SAFQueueBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.j2ee.descriptor.wl.SAFQueueBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.SAFQueueBean](#) entity.

This method can return the following links:

- **rel=SAFErrorHandling**
This resource's SAFErrorHandling reference to a [weblogic.j2ee.descriptor.wl.SAFErrorHandlingBean](#) resource.
- **uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/SAFImportedDestinations/{name}/SAFQueues/{name} rel=canonical**
This resource.
- **uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/SAFImportedDestinations/{name}/SAFQueues/{name}/messageLoggingParams rel=messageLoggingParams**
This resource's messageLoggingParams singleton resource.
- **uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/SAFImportedDestinations/{name}/SAFQueues rel=parent**
The parent resource of this resource.
- **uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/SAFImportedDestinations/{name}/SAFQueues/{name} rel=self**
This resource.

POST

Update this [weblogic.j2ee.descriptor.wl.SAFQueueBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.SAFQueueBean](#) entity.

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/SAFImportedDestinations/{name}/SAFQueues/{name}/messageLoggingParams

This resource manages a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/SAFImportedDestinations/{name}/SAFQueues/{name}/messageLoggingParams](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/SAFImportedDestinations/{name}/SAFQueues/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/SAFImportedDestinations/{name}/SAFQueues/{name}/messageLoggingParams](#) **rel**=self

This resource.

- **rel**=templateBean

This resource's `templateBean` reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) entity.

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/SAFImportedDestinations/{name}/SAFTopicCreateForm

This resource manages the create forms for the SAFTopics collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.j2ee.descriptor.wl.SAFTopicBean](#) entity populated with default values that can be customized then posted (using the POST method) to the SAFTopics collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.SAFTopicBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/SAFImportedDestinations/{name}/SAFTopicCreateForm](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/SAFImportedDestinations/{name}/SAFTopics](#) **rel=create**
The collection resource for this create form resource.
- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/SAFImportedDestinations/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/SAFImportedDestinations/{name}/SAFTopicCreateForm](#) **rel=self**
This resource.

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/SAFImportedDestinations/{name}/SAFTopics

This resource manages a collection of [weblogic.j2ee.descriptor.wl.SAFTopicBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.j2ee.descriptor.wl.SAFTopicBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.j2ee.descriptor.wl.SAFTopicBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/SAFImportedDestinations/{name}/SAFTopics](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/SAFImportedDestinations/{name}/SAFTopicCreateForm](#) **rel=create-form**

The create form resource for this collection resource.

- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/SAFImportedDestinations/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/SAFImportedDestinations/{name}/SAFTopics](#) **rel=self**

This resource.

POST

Add a new [weblogic.j2ee.descriptor.wl.SAFTopicBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.SAFTopicBean](#) entity.

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/SAFImportedDestinations/{name}/SAFTopics/{name}

This resource manages a [weblogic.j2ee.descriptor.wl.SAFTopicBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.j2ee.descriptor.wl.SAFTopicBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.j2ee.descriptor.wl.SAFTopicBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.SAFTopicBean](#) entity.

This method can return the following links:

- **rel=SAFErrorHandling**
This resource's SAFErrorHandling reference to a [weblogic.j2ee.descriptor.wl.SAFErrorHandlingBean](#) resource.
- **uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/SAFImportedDestinations/{name}/SAFTopics/{name} rel=canonical**
This resource.
- **uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/SAFImportedDestinations/{name}/SAFTopics/{name}/messageLoggingParams rel=messageLoggingParams**
This resource's messageLoggingParams singleton resource.
- **uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/SAFImportedDestinations/{name}/SAFTopics rel=parent**
The parent resource of this resource.
- **uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/SAFImportedDestinations/{name}/SAFTopics/{name} rel=self**
This resource.

POST

Update this [weblogic.j2ee.descriptor.wl.SAFTopicBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.SAFTopicBean](#) entity.

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/SAFImportedDestinations/{name}/SAFTopics/{name}/messageLoggingParams

This resource manages a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/SAFImportedDestinations/{name}/SAFTopics/{name}/messageLoggingParams](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/SAFImportedDestinations/{name}/SAFTopics/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/SAFImportedDestinations/{name}/SAFTopics/{name}/messageLoggingParams](#) **rel**=self

This resource.

- **rel**=templateBean

This resource's `templateBean` reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) entity.

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/SAFRemoteContextCreateForm

This resource manages the create forms for the SAFRemoteContexts collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.j2ee.descriptor.wl.SAFRemoteContextBean](#) entity populated with default values that can be customized then posted (using the POST method) to the SAFRemoteContexts collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.SAFRemoteContextBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/SAFRemoteContextCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/SAFRemoteContexts](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/SAFRemoteContextCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/SAFRemoteContexts

This resource manages a collection of [weblogic.j2ee.descriptor.wl.SAFRemoteContextBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.j2ee.descriptor.wl.SAFRemoteContextBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.j2ee.descriptor.wl.SAFRemoteContextBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/SAFRemoteContexts](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/SAFRemoteContextCreateForm](#) **rel=create-form**
The create form resource for this collection resource.
- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/SAFRemoteContexts](#) **rel=self**
This resource.

POST

Add a new [weblogic.j2ee.descriptor.wl.SAFRemoteContextBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.SAFRemoteContextBean](#) entity.

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/SAFRemoteContexts/{name}

This resource manages a [weblogic.j2ee.descriptor.wl.SAFRemoteContextBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

DELETE

Delete this [weblogic.j2ee.descriptor.wl.SAFRemoteContextBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.j2ee.descriptor.wl.SAFRemoteContextBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.SAFRemoteContextBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/SAFRemoteContexts/{name}/SAFLoginContext rel=SAFLoginContext](#)
This resource's SAFLoginContext singleton resource.
- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/SAFRemoteContexts/{name} rel=canonical](#)
This resource.
- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/SAFRemoteContexts rel=parent](#)
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/SAFRemoteContexts/{name} rel=self](#)
This resource.

POST

Update this [weblogic.j2ee.descriptor.wl.SAFRemoteContextBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.SAFRemoteContextBean](#) entity.

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/SAFRemoteContexts/{name}/SAFLoginContext

This resource manages a [weblogic.j2ee.descriptor.wl.SAFLoginContextBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.SAFLoginContextBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.SAFLoginContextBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/SAFRemoteContexts/{name}/SAFLoginContext](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/SAFRemoteContexts/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/SAFRemoteContexts/{name}/SAFLoginContext](#) **rel**=self

This resource.

POST

Update this [weblogic.j2ee.descriptor.wl.SAFLoginContextBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.SAFLoginContextBean](#) entity.

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/templateCreateForm

This resource manages the create forms for the templates collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.j2ee.descriptor.wl.TemplateBean](#) entity populated with default values that can be customized then posted (using the POST method) to the templates collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.TemplateBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/templateCreateForm rel=canonical](#)

This resource.

- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/templates rel=create](#)

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource rel=parent](#)

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/templateCreateForm rel=self](#)

This resource.

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/templates

This resource manages a collection of [weblogic.j2ee.descriptor.wl.TemplateBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.j2ee.descriptor.wl.TemplateBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.j2ee.descriptor.wl.TemplateBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/templates rel=canonical](#)
This resource.
- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/templateCreateForm rel=create-form](#)
The create form resource for this collection resource.
- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource rel=parent](#)
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/templates rel=self](#)
This resource.

POST

Add a new [weblogic.j2ee.descriptor.wl.TemplateBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.TemplateBean](#) entity.

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/templates/{name}

This resource manages a [weblogic.j2ee.descriptor.wl.TemplateBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.j2ee.descriptor.wl.TemplateBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.j2ee.descriptor.wl.TemplateBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.TemplateBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/templates/{name}/findErrorDestination](#) **rel=action**
title=findErrorDestination
This resource's findErrorDestination action resource.
- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/templates/{name}](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/templates/{name}/deliveryFailureParams](#) **rel=deliveryFailureParams**
This resource's deliveryFailureParams singleton resource.
- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/templates/{name}/deliveryParamsOverrides](#) **rel=deliveryParamsOverrides**
This resource's deliveryParamsOverrides singleton resource.
- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/templates/{name}/groupParamCreateForm](#) **rel=groupParamCreateForm**
The create form resource for this resource's groupParams collection resource.
- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/templates/{name}/groupParams](#) **rel=groupParams**
This resource's groupParams collection resource.
- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/templates/{name}/messageLoggingParams](#) **rel=messageLoggingParams**
This resource's messageLoggingParams singleton resource.
- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/templates/{name}/multicast](#) **rel=multicast**
This resource's multicast singleton resource.
- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/templates](#) **rel=parent**
The parent resource of this resource.
- **rel=quota**
This resource's quota reference to a [weblogic.j2ee.descriptor.wl.QuotaBean](#) resource.

- **uri**=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/templates/{name} **rel**=self

This resource.

- **uri**=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/templates/{name}/thresholds **rel**=thresholds

This resource's thresholds singleton resource.

- **uri**=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/templates/{name}/topicSubscriptionParams **rel**=topicSubscriptionParams

This resource's topicSubscriptionParams singleton resource.

POST

Update this [weblogic.j2ee.descriptor.wl.TemplateBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.TemplateBean](#) entity.

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/templates/{name}/deliveryFailureParams

This resource manages a [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/templates/{name}/deliveryFailureParams/findSubDeploymentName](#) **rel**=action **title**=findSubDeploymentName
This resource's findSubDeploymentName action resource.
- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/templates/{name}/deliveryFailureParams](#) **rel**=canonical
This resource.
- **rel**=errorDestination
This resource's errorDestination reference to a [weblogic.j2ee.descriptor.wl.DestinationBean](#) resource.
- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/templates/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/templates/{name}/deliveryFailureParams](#) **rel**=self
This resource.
- **rel**=templateBean
This resource's templateBean reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) entity.

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/templates/{name}/deliveryFailureParams/findSubDeploymentName

The resource supports the following methods:

- [POST](#)

POST

This is used to find the sub-deployment-name for this destination.

Roles

Admin, Deployer

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/templates/{name}/deliveryParamsOverrides

This resource manages a [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/templates/{name}/deliveryParamsOverrides](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/templates/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/templates/{name}/deliveryParamsOverrides](#) **rel**=self

This resource.

- **rel**=templateBean

This resource's templateBean reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) entity.

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/templates/{name}/findErrorDestination

The resource supports the following methods:

- [POST](#)

POST

Finds the name of the error destination to use when a destination comes from a specific group

Roles

Admin, Deployer

Request Body

Must contain a JSON object with the following fields:

subDeploymentName

The subDeployment for which to find the quota

Type: string

Response Body

Contains a JSON object with a weblogic.j2ee.descriptor.wl.DestinationBean reference return field.

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/templates/{name}/groupParamCreateForm

This resource manages the create forms for the groupParams collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.j2ee.descriptor.wl.GroupParamsBean](#) entity populated with default values that can be customized then posted (using the POST method) to the groupParams collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.GroupParamsBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/templates/{name}/groupParamCreateForm **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/templates/{name}/groupParams **rel**=create

The collection resource for this create form resource.

- **uri**=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/templates/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/templates/{name}/groupParamCreateForm **rel**=self

This resource.

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/templates/{name}/groupParams

This resource manages a collection of [weblogic.j2ee.descriptor.wl.GroupParamsBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.j2ee.descriptor.wl.GroupParamsBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.j2ee.descriptor.wl.GroupParamsBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/templates/{name}/groupParams](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/templates/{name}/groupParamCreateForm](#) **rel=create-form**

The create form resource for this collection resource.

- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/templates/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/templates/{name}/groupParams](#) **rel=self**

This resource.

POST

Add a new [weblogic.j2ee.descriptor.wl.GroupParamsBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.GroupParamsBean](#) entity.

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/templates/{name}/groupParams/{subDeploymentName}

This resource manages a [weblogic.j2ee.descriptor.wl.GroupParamsBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.j2ee.descriptor.wl.GroupParamsBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.j2ee.descriptor.wl.GroupParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.GroupParamsBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/templates/{name}/groupParams/{subDeploymentName}](#) **rel**=canonical
This resource.
- **rel**=errorDestination
This resource's errorDestination reference to a [weblogic.j2ee.descriptor.wl.DestinationBean](#) resource.
- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/templates/{name}/groupParams](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/templates/{name}/groupParams/{subDeploymentName}](#) **rel**=self
This resource.

POST

Update this [weblogic.j2ee.descriptor.wl.GroupParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.GroupParamsBean](#) entity.

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/templates/{name}/messageLoggingParams

This resource manages a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/templates/{name}/messageLoggingParams](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/templates/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/templates/{name}/messageLoggingParams](#) **rel**=self

This resource.

- **rel**=templateBean

This resource's `templateBean` reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) entity.

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/templates/{name}/multicast

This resource manages a [weblogic.j2ee.descriptor.wl.MulticastParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.MulticastParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.MulticastParamsBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/templates/{name}/multicast](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/templates/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/templates/{name}/multicast](#) **rel=self**
This resource.
- **rel=templateBean**
This resource's `templateBean` reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.MulticastParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.MulticastParamsBean](#) entity.

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/templates/{name}/thresholds

This resource manages a [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/templates/{name}/thresholds](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/templates/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/templates/{name}/thresholds](#) **rel**=self

This resource.

- **rel**=templateBean

This resource's templateBean reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) entity.

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/templates/{name}/topicSubscriptionParams

This resource manages a [weblogic.j2ee.descriptor.wl.TopicSubscriptionParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.TopicSubscriptionParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.TopicSubscriptionParamsBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/templates/{name}/topicSubscriptionParams **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/templates/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/templates/{name}/topicSubscriptionParams **rel**=self

This resource.

- **rel**=templateBean

This resource's templateBean reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.TopicSubscriptionParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.TopicSubscriptionParamsBean](#) entity.

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/topicCreateForm

This resource manages the create forms for the topics collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.j2ee.descriptor.wl.TopicBean](#) entity populated with default values that can be customized then posted (using the POST method) to the topics collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.TopicBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/topicCreateForm rel=canonical](#)

This resource.

- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/topics rel=create](#)

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource rel=parent](#)

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/topicCreateForm rel=self](#)

This resource.

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/topics

This resource manages a collection of [weblogic.j2ee.descriptor.wl.TopicBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.j2ee.descriptor.wl.TopicBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.j2ee.descriptor.wl.TopicBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/topics](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/topicCreateForm](#) **rel**=create-form

The create form resource for this collection resource.

- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/topics](#) **rel**=self

This resource.

POST

Add a new [weblogic.j2ee.descriptor.wl.TopicBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.TopicBean](#) entity.

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/topics/{name}

This resource manages a [weblogic.j2ee.descriptor.wl.TopicBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.j2ee.descriptor.wl.TopicBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.j2ee.descriptor.wl.TopicBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.TopicBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/topics/{name}](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/topics/{name}/deliveryFailureParams](#) **rel**=deliveryFailureParams
This resource's deliveryFailureParams singleton resource.
- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/topics/{name}/deliveryParamsOverrides](#) **rel**=deliveryParamsOverrides
This resource's deliveryParamsOverrides singleton resource.
- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/topics/{name}/messageLoggingParams](#) **rel**=messageLoggingParams
This resource's messageLoggingParams singleton resource.
- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/topics/{name}/multicast](#) **rel**=multicast
This resource's multicast singleton resource.
- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/topics](#) **rel**=parent
The parent resource of this resource.
- **rel**=quota
This resource's quota reference to a [weblogic.j2ee.descriptor.wl.QuotaBean](#) resource.
- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/topics/{name}](#) **rel**=self
This resource.
- **rel**=template
This resource's template reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.
- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/topics/{name}/thresholds](#) **rel**=thresholds
This resource's thresholds singleton resource.
- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/topics/{name}/topicSubscriptionParams](#) **rel**=topicSubscriptionParams

This resource's topicSubscriptionParams singleton resource.

POST

Update this [weblogic.j2ee.descriptor.wl.TopicBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.TopicBean](#) entity.

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/topics/{name}/deliveryFailureParams

This resource manages a [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/topics/{name}/deliveryFailureParams/findSubDeploymentName](#) **rel**=action **title**=findSubDeploymentName
This resource's findSubDeploymentName action resource.
- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/topics/{name}/deliveryFailureParams](#) **rel**=canonical
This resource.
- **rel**=errorDestination
This resource's errorDestination reference to a [weblogic.j2ee.descriptor.wl.DestinationBean](#) resource.
- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/topics/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/topics/{name}/deliveryFailureParams](#) **rel**=self
This resource.
- **rel**=templateBean
This resource's templateBean reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) entity.

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/topics/{name}/deliveryFailureParams/findSubDeploymentName

The resource supports the following methods:

- [POST](#)

POST

This is used to find the sub-deployment-name for this destination.

Roles

Admin, Deployer

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/topics/{name}/deliveryParamsOverrides

This resource manages a [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/topics/{name}/deliveryParamsOverrides](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/topics/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/topics/{name}/deliveryParamsOverrides](#) **rel**=self
This resource.
- **rel**=templateBean
This resource's templateBean reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) entity.

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/topics/{name}/messageLoggingParams

This resource manages a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/topics/{name}/messageLoggingParams](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/topics/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/topics/{name}/messageLoggingParams](#) **rel**=self

This resource.

- **rel**=templateBean

This resource's templateBean reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) entity.

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/topics/{name}/multicast

This resource manages a [weblogic.j2ee.descriptor.wl.MulticastParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.MulticastParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.MulticastParamsBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/topics/{name}/multicast](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/topics/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/topics/{name}/multicast](#) **rel**=self
This resource.
- **rel**=templateBean
This resource's templateBean reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.MulticastParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.MulticastParamsBean](#) entity.

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/topics/{name}/thresholds

This resource manages a [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/topics/{name}/thresholds](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/topics/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/topics/{name}/thresholds](#) **rel**=self

This resource.

- **rel**=templateBean

This resource's templateBean reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) entity.

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/topics/{name}/topicSubscriptionParams

This resource manages a [weblogic.j2ee.descriptor.wl.TopicSubscriptionParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.TopicSubscriptionParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.TopicSubscriptionParamsBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/topics/{name}/topicSubscriptionParams **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/topics/{name} **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/topics/{name}/topicSubscriptionParams **rel**=self
This resource.
- **rel**=templateBean
This resource's templateBean reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.TopicSubscriptionParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.TopicSubscriptionParamsBean](#) entity.

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/uniformDistributedQueueCreateForm

This resource manages the create forms for the uniformDistributedQueues collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.j2ee.descriptor.wl.UniformDistributedQueueBean](#) entity populated with default values that can be customized then posted (using the POST method) to the `uniformDistributedQueues` collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.UniformDistributedQueueBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/uniformDistributedQueueCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/uniformDistributedQueues](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/uniformDistributedQueueCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/uniformDistributedQueues

This resource manages a collection of [weblogic.j2ee.descriptor.wl.UniformDistributedQueueBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.j2ee.descriptor.wl.UniformDistributedQueueBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.j2ee.descriptor.wl.UniformDistributedQueueBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/uniformDistributedQueues](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/uniformDistributedQueueCreateForm](#) **rel=create-form**

The create form resource for this collection resource.

- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/uniformDistributedQueues](#) **rel=self**

This resource.

POST

Add a new [weblogic.j2ee.descriptor.wl.UniformDistributedQueueBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.UniformDistributedQueueBean](#) entity.

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/uniformDistributedQueues/{name}

This resource manages a [weblogic.j2ee.descriptor.wl.UniformDistributedQueueBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.j2ee.descriptor.wl.UniformDistributedQueueBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.j2ee.descriptor.wl.UniformDistributedQueueBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.UniformDistributedQueueBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/uniformDistributedQueues/{name}](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/uniformDistributedQueues/{name}/deliveryFailureParams](#) **rel**=deliveryFailureParams
This resource's deliveryFailureParams singleton resource.
- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/uniformDistributedQueues/{name}/deliveryParamsOverrides](#) **rel**=deliveryParamsOverrides
This resource's deliveryParamsOverrides singleton resource.
- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/uniformDistributedQueues/{name}/messageLoggingParams](#) **rel**=messageLoggingParams
This resource's messageLoggingParams singleton resource.
- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/uniformDistributedQueues](#) **rel**=parent
The parent resource of this resource.
- **rel**=quota
This resource's quota reference to a [weblogic.j2ee.descriptor.wl.QuotaBean](#) resource.
- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/uniformDistributedQueues/{name}](#) **rel**=self
This resource.
- **rel**=template
This resource's template reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.
- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/uniformDistributedQueues/{name}/thresholds](#) **rel**=thresholds
This resource's thresholds singleton resource.

POST

Update this [weblogic.j2ee.descriptor.wl.UniformDistributedQueueBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.UniformDistributedQueueBean](#) entity.

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/uniformDistributedQueues/{name}/deliveryFailureParams

This resource manages a [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/uniformDistributedQueues/{name}/deliveryFailureParams/findSubDeploymentName **rel**=action **title**=findSubDeploymentName
This resource's findSubDeploymentName action resource.
- **uri**=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/uniformDistributedQueues/{name}/deliveryFailureParams **rel**=canonical
This resource.
- **rel**=errorDestination
This resource's errorDestination reference to a [weblogic.j2ee.descriptor.wl.DestinationBean](#) resource.
- **uri**=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/uniformDistributedQueues/{name} **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/uniformDistributedQueues/{name}/deliveryFailureParams **rel**=self
This resource.
- **rel**=templateBean
This resource's templateBean reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) entity.

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/uniformDistributedQueues/{name}/deliveryFailureParams/findSubDeploymentName

The resource supports the following methods:

- [POST](#)

POST

This is used to find the sub-deployment-name for this destination.

Roles

Admin, Deployer

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/uniformDistributedQueues/{name}/deliveryParamsOverrides

This resource manages a [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/uniformDistributedQueues/{name}/deliveryParamsOverrides](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/uniformDistributedQueues/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/uniformDistributedQueues/{name}/deliveryParamsOverrides](#) **rel**=self
This resource.
- **rel**=templateBean
This resource's templateBean reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) entity.

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/uniformDistributedQueues/{name}/messageLoggingParams

This resource manages a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/uniformDistributedQueues/{name}/messageLoggingParams](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/uniformDistributedQueues/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/uniformDistributedQueues/{name}/messageLoggingParams](#) **rel**=self
This resource.
- **rel**=templateBean
This resource's templateBean reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) entity.

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/uniformDistributedQueues/{name}/thresholds

This resource manages a [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/uniformDistributedQueues/{name}/thresholds](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/uniformDistributedQueues/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/uniformDistributedQueues/{name}/thresholds](#) **rel**=self

This resource.

- **rel**=templateBean

This resource's templateBean reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) entity.

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/uniformDistributedTopicCreateForm

This resource manages the create forms for the uniformDistributedTopics collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.j2ee.descriptor.wl.UniformDistributedTopicBean](#) entity populated with default values that can be customized then posted (using the POST method) to the `uniformDistributedTopics` collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.UniformDistributedTopicBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/uniformDistributedTopicCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/uniformDistributedTopics](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/uniformDistributedTopicCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/uniformDistributedTopics

This resource manages a collection of [weblogic.j2ee.descriptor.wl.UniformDistributedTopicBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.j2ee.descriptor.wl.UniformDistributedTopicBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.j2ee.descriptor.wl.UniformDistributedTopicBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/uniformDistributedTopics rel=canonical](#)

This resource.

- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/uniformDistributedTopicCreateForm rel=create-form](#)

The create form resource for this collection resource.

- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource rel=parent](#)

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/uniformDistributedTopics rel=self](#)

This resource.

POST

Add a new [weblogic.j2ee.descriptor.wl.UniformDistributedTopicBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.UniformDistributedTopicBean](#) entity.

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/uniformDistributedTopics/{name}

This resource manages a [weblogic.j2ee.descriptor.wl.UniformDistributedTopicBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

DELETE

Delete this [weblogic.j2ee.descriptor.wl.UniformDistributedTopicBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.j2ee.descriptor.wl.UniformDistributedTopicBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.UniformDistributedTopicBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/uniformDistributedTopics/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/uniformDistributedTopics/{name}/deliveryFailureParams **rel**=deliveryFailureParams

This resource's deliveryFailureParams singleton resource.

- **uri**=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/uniformDistributedTopics/{name}/deliveryParamsOverrides **rel**=deliveryParamsOverrides

This resource's deliveryParamsOverrides singleton resource.

- **uri**=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/uniformDistributedTopics/{name}/messageLoggingParams **rel**=messageLoggingParams

This resource's messageLoggingParams singleton resource.

- **uri**=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/uniformDistributedTopics/{name}/multicast **rel**=multicast

This resource's multicast singleton resource.

- **uri**=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/uniformDistributedTopics **rel**=parent

The parent resource of this resource.

- **rel**=quota

This resource's quota reference to a [weblogic.j2ee.descriptor.wl.QuotaBean](#) resource.

- **uri**=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/uniformDistributedTopics/{name} **rel**=self

This resource.

- **rel**=template

This resource's template reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

- **uri**=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/uniformDistributedTopics/{name}/thresholds **rel**=thresholds

This resource's thresholds singleton resource.

- **uri**=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/uniformDistributedTopics/{name}/topicSubscriptionParams
rel=topicSubscriptionParams

This resource's topicSubscriptionParams singleton resource.

POST

Update this [weblogic.j2ee.descriptor.wl.UniformDistributedTopicBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.UniformDistributedTopicBean](#) entity.

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/uniformDistributedTopics/{name}/deliveryFailureParams

This resource manages a [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/uniformDistributedTopics/{name}/deliveryFailureParams/findSubDeploymentName **rel**=action **title**=findSubDeploymentName
This resource's findSubDeploymentName action resource.
- **uri**=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/uniformDistributedTopics/{name}/deliveryFailureParams **rel**=canonical
This resource.
- **rel**=errorDestination
This resource's errorDestination reference to a [weblogic.j2ee.descriptor.wl.DestinationBean](#) resource.
- **uri**=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/uniformDistributedTopics/{name} **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/uniformDistributedTopics/{name}/deliveryFailureParams **rel**=self
This resource.
- **rel**=templateBean
This resource's templateBean reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) entity.

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/uniformDistributedTopics/{name}/deliveryFailureParams/findSubDeploymentName

The resource supports the following methods:

- [POST](#)

POST

This is used to find the sub-deployment-name for this destination.

Roles

Admin, Deployer

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/uniformDistributedTopics/{name}/deliveryParamsOverrides

This resource manages a [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/uniformDistributedTopics/{name}/deliveryParamsOverrides](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/uniformDistributedTopics/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/uniformDistributedTopics/{name}/deliveryParamsOverrides](#) **rel**=self
This resource.
- **rel**=templateBean
This resource's templateBean reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) entity.

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/uniformDistributedTopics/{name}/messageLoggingParams

This resource manages a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/uniformDistributedTopics/{name}/messageLoggingParams](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/uniformDistributedTopics/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/uniformDistributedTopics/{name}/messageLoggingParams](#) **rel**=self
This resource.
- **rel**=templateBean
This resource's templateBean reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) entity.

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/uniformDistributedTopics/{name}/multicast

This resource manages a [weblogic.j2ee.descriptor.wl.MulticastParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.MulticastParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.MulticastParamsBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/uniformDistributedTopics/{name}/multicast](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/uniformDistributedTopics/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/uniformDistributedTopics/{name}/multicast](#) **rel**=self

This resource.

- **rel**=templateBean

This resource's templateBean reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.MulticastParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.MulticastParamsBean](#) entity.

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/uniformDistributedTopics/{name}/thresholds

This resource manages a [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/uniformDistributedTopics/{name}/thresholds **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/uniformDistributedTopics/{name} **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/uniformDistributedTopics/{name}/thresholds **rel**=self
This resource.
- **rel**=templateBean
This resource's templateBean reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) entity.

/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/uniformDistributedTopics/{name}/topicSubscriptionParams

This resource manages a [weblogic.j2ee.descriptor.wl.TopicSubscriptionParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.TopicSubscriptionParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.TopicSubscriptionParamsBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/uniformDistributedTopics/{name}/topicSubscriptionParams](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/uniformDistributedTopics/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/JMSResource/uniformDistributedTopics/{name}/topicSubscriptionParams](#) **rel**=self

This resource.

- **rel**=templateBean

This resource's templateBean reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.TopicSubscriptionParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.TopicSubscriptionParamsBean](#) entity.

/management/weblogic/{version}/edit/JMSInteropModules/{name}/subDeploymentCreateForm

This resource manages the create forms for the subDeployments collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.SubDeploymentMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the subDeployments collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/subDeploymentCreateForm](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/subDeployments](#) **rel=create**
The collection resource for this create form resource.
- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/subDeploymentCreateForm](#) **rel=self**
This resource.

/management/weblogic/{version}/edit/JMSInteropModules/{name}/subDeployments

This resource manages a collection of [weblogic.management.configuration.SubDeploymentMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.SubDeploymentMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.SubDeploymentMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/subDeployments](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/subDeploymentCreateForm](#) **rel=create-form**
The create form resource for this collection resource.
- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/subDeployments](#) **rel=self**
This resource.

POST

Add a new [weblogic.management.configuration.SubDeploymentMBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

/management/weblogic/{version}/edit/JMSInteropModules/{name}/subDeployments/{name}

This resource manages a [weblogic.management.configuration.SubDeploymentMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/subDeployments/{name} rel=canonical](#)
This resource.
- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/subDeployments rel=parent](#)
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/subDeployments/{name} rel=self](#)
This resource.
- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/subDeployments/{name}/subDeployments rel=subDeployments](#)
This resource's subDeployments collection resource.

POST

Update this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

/management/weblogic/{version}/edit/JMSInteropModules/{name}/subDeployments/{name}/subDeployments

This resource manages a collection of [weblogic.management.configuration.SubDeploymentMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.configuration.SubDeploymentMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.SubDeploymentMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/subDeployments/{name}/subDeployments](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/subDeployments/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/JMSInteropModules/{name}/subDeployments/{name}/subDeployments](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/JMSInteropModules/{name}/subDeployments/{name}/subDeployments/{name}

This resource manages a [weblogic.management.configuration.SubDeploymentMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/subDeployments/{name}/subDeployments/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/subDeployments/{name}/subDeployments](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/subDeployments/{name}/subDeployments/{name}](#) **rel**=self

This resource.

- **uri**=[/management/weblogic/{version}/edit/JMSInteropModules/{name}/subDeployments/{name}/subDeployments/{name}/subDeployments](#) **rel**=subDeployments

This resource's subDeployments collection resource.

POST

Update this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

/management/weblogic/{version}/edit/JMSServerCreateForm

This resource manages the create forms for the JMSServers collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.JMSServerMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the JMSServers collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.JMSServerMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/JMSServerCreateForm](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/JMSServers](#) **rel=create**
The collection resource for this create form resource.
- [uri=/management/weblogic/{version}/edit](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/JMSServerCreateForm](#) **rel=self**
This resource.

/management/weblogic/{version}/edit/JMSServers

This resource manages a collection of [weblogic.management.configuration.JMSServerMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.JMSServerMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.JMSServerMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/JMSServers](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/JMSServerCreateForm](#)
rel=create-form
The create form resource for this collection resource.
- **uri**=[/management/weblogic/{version}/edit](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/JMSServers](#) **rel**=self
This resource.

POST

Add a new [weblogic.management.configuration.JMServerMBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.JMServerMBean](#) entity.

/management/weblogic/{version}/edit/JMSServers/{name}

This resource manages a [weblogic.management.configuration.JMSServerMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.JMServerMBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.management.configuration.JMSServerMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.JMSServerMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/JMSServers/{name}/JMSSMessageLogFile](#) **rel**=JMSSMessageLogFile
This resource's JMSSMessageLogFile singleton resource.
- [uri=/management/weblogic/{version}/edit/JMSServers/{name}](#) **rel**=canonical
This resource.
- [uri=/management/weblogic/{version}/edit/JMSServers](#) **rel**=parent
The parent resource of this resource.
- **rel**=persistentStore
This resource's persistentStore reference to a [weblogic.management.configuration.PersistentStoreMBean](#) resource.
- [uri=/management/weblogic/{version}/edit/JMSServers/{name}](#) **rel**=self
This resource.

POST

Update this [weblogic.management.configuration.JMSServerMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.JMSServerMBean](#) entity.

/management/weblogic/{version}/edit/JMSServers/{name}/JMSMessageLogFile

This resource manages a [weblogic.management.configuration.JMSMessageLogFileMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.JMSMessageLogFileMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.JMSMessageLogFileMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/JMSServers/{name}/JMSMessageLogFile](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/JMSServers/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/JMSServers/{name}/JMSMessageLogFile](#) **rel=self**
This resource.

POST

Update this [weblogic.management.configuration.JMSMessageLogFileMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.JMSMessageLogFileMBean](#) entity.

/management/weblogic/{version}/edit/JMSSystemResourceCreateForm

This resource manages the create forms for the JMSSystemResources collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.JMSSystemResourceMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the JMSSystemResources collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.JMSSystemResourceMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResourceCreateForm](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources](#) **rel**=create
The collection resource for this create form resource.
- **uri**=[/management/weblogic/{version}/edit](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/JMSSystemResourceCreateForm](#)
rel=self
This resource.

/management/weblogic/{version}/edit/JMSSystemResources

This resource manages a collection of [weblogic.management.configuration.JMSSystemResourceMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.JMSSystemResourceMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.JMSSystemResourceMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/JMSSystemResourceCreateForm](#)
rel=create-form
The create form resource for this collection resource.
- **uri**=[/management/weblogic/{version}/edit](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources](#) **rel**=self
This resource.

POST

Add a new [weblogic.management.configuration.JMSSystemResourceMBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.JMSSystemResourceMBean](#) entity.

/management/weblogic/{version}/edit/JMSSystemResources/{name}

This resource manages a [weblogic.management.configuration.JMSSystemResourceMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.JMSSystemResourceMBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.management.configuration.JMSSystemResourceMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.JMSSystemResourceMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource](#) **rel**=JMSResource
This resource's JMSResource singleton resource.
- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources](#) **rel**=parent
The parent resource of this resource.
- **rel**=resource
This resource's resource reference to a [weblogic.descriptor.DescriptorBean](#) resource.
- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}](#) **rel**=self
This resource.
- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/subDeploymentCreateForm](#) **rel**=subDeploymentCreateForm
The create form resource for this resource's subDeployments collection resource.
- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/subDeployments](#) **rel**=subDeployments
This resource's subDeployments collection resource.

POST

POST

Update this [weblogic.management.configuration.JMSSystemResourceMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.JMSSystemResourceMBean](#) entity.

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource

This resource manages a [weblogic.j2ee.descriptor.wl.JMSBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.JMSBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.JMSBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/SAFErrorHandlingCreateForm **rel**=SAFErrorHandlingCreateForm
The create form resource for this resource's SAFErrorHandlings collection resource.
- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/SAFErrorHandlings **rel**=SAFErrorHandlings
This resource's SAFErrorHandlings collection resource.
- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/SAFImportedDestinationCreateForm **rel**=SAFImportedDestinationCreateForm
The create form resource for this resource's SAFImportedDestinations collection resource.
- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations **rel**=SAFImportedDestinations
This resource's SAFImportedDestinations collection resource.
- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/SAFRemoteContextCreateForm **rel**=SAFRemoteContextCreateForm
The create form resource for this resource's SAFRemoteContexts collection resource.
- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/SAFRemoteContexts **rel**=SAFRemoteContexts
This resource's SAFRemoteContexts collection resource.
- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/connectionFactories **rel**=connectionFactories
This resource's connectionFactories collection resource.
- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/connectionFactoryCreateForm **rel**=connectionFactoryCreateForm
The create form resource for this resource's connectionFactories collection resource.

- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/destinationKeyCreateForm **rel**=destinationKeyCreateForm
The create form resource for this resource's destinationKeys collection resource.
- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/destinationKeys **rel**=destinationKeys
This resource's destinationKeys collection resource.
- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/foreignServerCreateForm **rel**=foreignServerCreateForm
The create form resource for this resource's foreignServers collection resource.
- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/foreignServers **rel**=foreignServers
This resource's foreignServers collection resource.
- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name} **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/queueCreateForm **rel**=queueCreateForm
The create form resource for this resource's queues collection resource.
- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/queues **rel**=queues
This resource's queues collection resource.
- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/quotaCreateForm **rel**=quotaCreateForm
The create form resource for this resource's quotas collection resource.
- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/quotas **rel**=quotas
This resource's quotas collection resource.
- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource **rel**=self
This resource.
- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/templateCreateForm **rel**=templateCreateForm
The create form resource for this resource's templates collection resource.
- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/templates **rel**=templates
This resource's templates collection resource.
- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/topicCreateForm **rel**=topicCreateForm
The create form resource for this resource's topics collection resource.
- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/topics **rel**=topics
This resource's topics collection resource.

- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/uniformDistributedQueueCreateForm
rel=uniformDistributedQueueCreateForm
The create form resource for this resource's uniformDistributedQueues collection resource.
- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues **rel**=uniformDistributedQueues
This resource's uniformDistributedQueues collection resource.
- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/uniformDistributedTopicCreateForm
rel=uniformDistributedTopicCreateForm
The create form resource for this resource's uniformDistributedTopics collection resource.
- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics **rel**=uniformDistributedTopics
This resource's uniformDistributedTopics collection resource.

POST

Update this [weblogic.j2ee.descriptor.wl.JMSBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.JMSBean](#) entity.

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/connectionFactories

This resource manages a collection of [weblogic.j2ee.descriptor.wl.JMSConnectionFactoryBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.j2ee.descriptor.wl.JMSConnectionFactoryBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.j2ee.descriptor.wl.JMSConnectionFactoryBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/connectionFactories](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/connectionFactoryCreateForm](#) **rel**=create-form

The create form resource for this collection resource.

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/connectionFactories](#) **rel**=self

This resource.

POST

Add a new [weblogic.j2ee.descriptor.wl.JMSConnectionFactoryBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.JMSConnectionFactoryBean](#) entity.

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}

This resource manages a [weblogic.j2ee.descriptor.wl.JMSConnectionFactoryBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

DELETE

Delete this [weblogic.j2ee.descriptor.wl.JMSConnectionFactoryBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.j2ee.descriptor.wl.JMSConnectionFactoryBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.JMSConnectionFactoryBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}/clientParams](#) **rel=clientParams**

This resource's clientParams singleton resource.

- [uri=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}/defaultDeliveryParams](#) **rel=defaultDeliveryParams**

This resource's defaultDeliveryParams singleton resource.

- [uri=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}/flowControlParams](#) **rel=flowControlParams**

This resource's flowControlParams singleton resource.

- [uri=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}/loadBalancingParams](#) **rel=loadBalancingParams**

This resource's loadBalancingParams singleton resource.

- [uri=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/connectionFactories](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}/securityParams](#) **rel=securityParams**

This resource's securityParams singleton resource.

- [uri=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}](#) **rel=self**

This resource.

- [uri=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}/transactionParams](#) **rel=transactionParams**

This resource's transactionParams singleton resource.

POST

Update this [weblogic.j2ee.descriptor.wl.JMSConnectionFactoryBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.JMSConnectionFactoryBean](#) entity.

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}/clientParams

This resource manages a [weblogic.j2ee.descriptor.wl.ClientParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.ClientParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.ClientParamsBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}/clientParams](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}/clientParams](#) **rel**=self

This resource.

POST

Update this [weblogic.j2ee.descriptor.wl.ClientParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.ClientParamsBean](#) entity.

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}/defaultDeliveryParams

This resource manages a [weblogic.j2ee.descriptor.wl.DefaultDeliveryParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.DefaultDeliveryParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.DefaultDeliveryParamsBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}/defaultDeliveryParams](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}/defaultDeliveryParams](#) **rel**=self
This resource.

POST

Update this [weblogic.j2ee.descriptor.wl.DefaultDeliveryParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.DefaultDeliveryParamsBean](#) entity.

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}/flowControlParams

This resource manages a [weblogic.j2ee.descriptor.wl.FlowControlParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.FlowControlParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.FlowControlParamsBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}/flowControlParams](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}/flowControlParams](#) **rel**=self

This resource.

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}/flowControl-

POST

Update this [weblogic.j2ee.descriptor.wl.FlowControlParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.FlowControlParamsBean](#) entity.

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}/loadBalancingParams

This resource manages a [weblogic.j2ee.descriptor.wl.LoadBalancingParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.LoadBalancingParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.LoadBalancingParamsBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}/loadBalancingParams **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/connectionFactories/{name} **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}/loadBalancingParams **rel**=self
This resource.

POST

Update this [weblogic.j2ee.descriptor.wl.LoadBalancingParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.LoadBalancingParamsBean](#) entity.

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}/securityParams

This resource manages a [weblogic.j2ee.descriptor.wl.SecurityParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.SecurityParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.SecurityParamsBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}/securityParams](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}/securityParams](#) **rel**=self

This resource.

POST

Update this [weblogic.j2ee.descriptor.wl.SecurityParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.SecurityParamsBean](#) entity.

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}/transactionParams

This resource manages a [weblogic.j2ee.descriptor.wl.TransactionParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.TransactionParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.TransactionParamsBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}/transactionParams **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/connectionFactories/{name} **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}/transactionParams **rel**=self
This resource.

POST

Update this [weblogic.j2ee.descriptor.wl.TransactionParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.TransactionParamsBean](#) entity.

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/connectionFactoryCreateForm

This resource manages the create forms for the connectionFactories collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.j2ee.descriptor.wl.JMSConnectionFactoryBean](#) entity populated with default values that can be customized then posted (using the POST method) to the connectionFactories collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.JMSConnectionFactoryBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/connectionFactoryCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/connectionFactories](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/connectionFactoryCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/destinationKeyCreateForm

This resource manages the create forms for the destinationKeys collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.j2ee.descriptor.wl.DestinationKeyBean](#) entity populated with default values that can be customized then posted (using the POST method) to the [destinationKeys](#) collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.DestinationKeyBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSSResource/destinationKeyCreateForm](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSSResource/destinationKeys](#) **rel**=create

The collection resource for this create form resource.

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSSResource](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSSResource/destinationKeyCreateForm](#) **rel**=self

This resource.

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/destinationKeys

This resource manages a collection of [weblogic.j2ee.descriptor.wl.DestinationKeyBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.j2ee.descriptor.wl.DestinationKeyBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.j2ee.descriptor.wl.DestinationKeyBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSSResource/destinationKeys](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSSResource/destinationKeyCreateForm](#) **rel**=create-form

The create form resource for this collection resource.

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSSResource](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSSResource/destinationKeys](#) **rel**=self

This resource.

POST

Add a new [weblogic.j2ee.descriptor.wl.DestinationKeyBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.DestinationKeyBean](#) entity.

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/destinationKeys/{name}

This resource manages a [weblogic.j2ee.descriptor.wl.DestinationKeyBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.j2ee.descriptor.wl.DestinationKeyBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.j2ee.descriptor.wl.DestinationKeyBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.DestinationKeyBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/destinationKeys/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/destinationKeys](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/destinationKeys/{name}](#) **rel**=self

This resource.

POST

Update this [weblogic.j2ee.descriptor.wl.DestinationKeyBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.DestinationKeyBean](#) entity.

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/foreignServerCreateForm

This resource manages the create forms for the foreignServers collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.j2ee.descriptor.wl.ForeignServerBean](#) entity populated with default values that can be customized then posted (using the POST method) to the `foreignServers` collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.ForeignServerBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/foreignServerCreateForm](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/foreignServers](#) **rel**=create

The collection resource for this create form resource.

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/foreignServerCreateForm](#) **rel**=self

This resource.

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/foreignServers

This resource manages a collection of [weblogic.j2ee.descriptor.wl.ForeignServerBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.j2ee.descriptor.wl.ForeignServerBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.j2ee.descriptor.wl.ForeignServerBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/foreignServers **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/foreignServerCreateForm **rel**=create-form

The create form resource for this collection resource.

- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/foreignServers **rel**=self

This resource.

POST

Add a new [weblogic.j2ee.descriptor.wl.ForeignServerBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.ForeignServerBean](#) entity.

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/foreignServers/{name}

This resource manages a [weblogic.j2ee.descriptor.wl.ForeignServerBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

DELETE

Delete this [weblogic.j2ee.descriptor.wl.ForeignServerBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.j2ee.descriptor.wl.ForeignServerBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.ForeignServerBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/JNDIProperties](#) **rel=JNDIProperties**
This resource's JNDIProperties collection resource.
- [uri=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/JNDIPropertyCreateForm](#) **rel=JNDIPropertyCreateForm**
The create form resource for this resource's JNDIProperties collection resource.
- [uri=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/foreignServers/{name}](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignConnectionFactories](#) **rel=foreignConnectionFactories**
This resource's foreignConnectionFactories collection resource.
- [uri=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignConnectionFactoryCreateForm](#) **rel=foreignConnectionFactoryCreateForm**
The create form resource for this resource's foreignConnectionFactories collection resource.
- [uri=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignDestinationCreateForm](#) **rel=foreignDestinationCreateForm**
The create form resource for this resource's foreignDestinations collection resource.
- [uri=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignDestinations](#) **rel=foreignDestinations**
This resource's foreignDestinations collection resource.
- [uri=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/foreignServers](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/foreignServers/{name}](#) **rel=self**
This resource.

POST

Update this [weblogic.j2ee.descriptor.wl.ForeignServerBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.ForeignServerBean](#) entity.

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignConnectionFactories

This resource manages a collection of [weblogic.j2ee.descriptor.wl.ForeignConnectionFactoryBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.j2ee.descriptor.wl.ForeignConnectionFactoryBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.j2ee.descriptor.wl.ForeignConnectionFactoryBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignConnectionFactories](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignConnectionFactoryCreateForm](#) **rel**=create-form

The create form resource for this collection resource.

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/foreignServers/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignConnectionFactories](#) **rel**=self

This resource.

POST

Add a new [weblogic.j2ee.descriptor.wl.ForeignConnectionFactoryBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.ForeignConnectionFactoryBean](#) entity.

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignConnectionFactory/{name}

This resource manages a [weblogic.j2ee.descriptor.wl.ForeignConnectionFactoryBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.j2ee.descriptor.wl.ForeignConnectionFactoryBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.j2ee.descriptor.wl.ForeignConnectionFactoryBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.ForeignConnectionFactoryBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignConnectionFactories/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignConnectionFactories](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignConnectionFactories/{name}](#) **rel**=self

This resource.

POST

Update this [weblogic.j2ee.descriptor.wl.ForeignConnectionFactoryBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.ForeignConnectionFactoryBean](#) entity.

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignConnectionFactoryCreateForm

This resource manages the create forms for the foreignConnectionFactories collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.j2ee.descriptor.wl.ForeignConnectionFactoryBean](#) entity populated with default values that can be customized then posted (using the POST method) to the `foreignConnectionFactories` collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.ForeignConnectionFactoryBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignConnectionFactoryCreateForm
rel=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignConnectionFactories **rel**=create

The collection resource for this create form resource.

- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/foreignServers/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignConnectionFactoryCreateForm **rel**=self

This resource.

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignDestinationCreateForm

This resource manages the create forms for the foreignDestinations collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.j2ee.descriptor.wl.ForeignDestinationBean](#) entity populated with default values that can be customized then posted (using the POST method) to the foreignDestinations collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.ForeignDestinationBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignDestinationCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignDestinations](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/foreignServers/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignDestinationCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignDestinations

This resource manages a collection of [weblogic.j2ee.descriptor.wl.ForeignDestinationBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.j2ee.descriptor.wl.ForeignDestinationBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.j2ee.descriptor.wl.ForeignDestinationBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignDestinations **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignDestinationCreateForm **rel**=create-form

The create form resource for this collection resource.

- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/foreignServers/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignDestinations **rel**=self

This resource.

POST

Add a new [weblogic.j2ee.descriptor.wl.ForeignDestinationBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.ForeignDestinationBean](#) entity.

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignDestinations/{name}

This resource manages a [weblogic.j2ee.descriptor.wl.ForeignDestinationBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.j2ee.descriptor.wl.ForeignDestinationBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.j2ee.descriptor.wl.ForeignDestinationBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.ForeignDestinationBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignDestinations/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignDestinations **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignDestinations/{name} **rel**=self

This resource.

POST

Update this [weblogic.j2ee.descriptor.wl.ForeignDestinationBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.ForeignDestinationBean](#) entity.

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/JNDIProperties

This resource manages a collection of [weblogic.j2ee.descriptor.wl.PropertyBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.j2ee.descriptor.wl.PropertyBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.j2ee.descriptor.wl.PropertyBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/JNDIProperties](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/JNDIPropertyCreateForm](#) **rel**=create-form

The create form resource for this collection resource.

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/foreignServers/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/JNDIProperties](#) **rel**=self

This resource.

POST

Add a new [weblogic.j2ee.descriptor.wl.PropertyBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.PropertyBean](#) entity.

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/JNDIProperties/{key}

This resource manages a [weblogic.j2ee.descriptor.wl.PropertyBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.j2ee.descriptor.wl.PropertyBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.j2ee.descriptor.wl.PropertyBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.PropertyBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/JNDIProperties/{key} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/JNDIProperties **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/JNDIProperties/{key} **rel**=self

This resource.

POST

Update this [weblogic.j2ee.descriptor.wl.PropertyBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.PropertyBean](#) entity.

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/JNDIPropertyCreateForm

This resource manages the create forms for the JNDIProperties collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.j2ee.descriptor.wl.PropertyBean](#) entity populated with default values that can be customized then posted (using the POST method) to the JNDIProperties collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.PropertyBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/JNDIPropertyCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/JNDIProperties](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/foreignServers/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/JNDIPropertyCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/queueCreateForm

This resource manages the create forms for the queues collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.j2ee.descriptor.wl.QueueBean](#) entity populated with default values that can be customized then posted (using the POST method) to the queues collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.QueueBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/queueCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/queues](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/queueCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/queues

This resource manages a collection of [weblogic.j2ee.descriptor.wl.QueueBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.j2ee.descriptor.wl.QueueBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.j2ee.descriptor.wl.QueueBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/queues](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/queuecreateForm](#) **rel**=create-form
The create form resource for this collection resource.
- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/queues](#) **rel**=self
This resource.

POST

Add a new [weblogic.j2ee.descriptor.wl.QueueBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.QueueBean](#) entity.

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/queues/{name}

This resource manages a [weblogic.j2ee.descriptor.wl.QueueBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.j2ee.descriptor.wl.QueueBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.j2ee.descriptor.wl.QueueBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.QueueBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/queues/{name}](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/queues/{name}/deliveryFailureParams](#) **rel=deliveryFailureParams**
This resource's `deliveryFailureParams` singleton resource.
- [uri=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/queues/{name}/deliveryParamsOverrides](#) **rel=deliveryParamsOverrides**
This resource's `deliveryParamsOverrides` singleton resource.
- [uri=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/queues/{name}/messageLoggingParams](#) **rel=messageLoggingParams**
This resource's `messageLoggingParams` singleton resource.
- [uri=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/queues](#) **rel=parent**
The parent resource of this resource.
- **rel=quota**
This resource's quota reference to a `weblogic.j2ee.descriptor.wl.QuotaBean` resource.
- [uri=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/queues/{name}](#) **rel=self**
This resource.
- **rel=template**
This resource's template reference to a `weblogic.j2ee.descriptor.wl.TemplateBean` resource.
- [uri=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/queues/{name}/thresholds](#) **rel=thresholds**
This resource's `thresholds` singleton resource.

POST

Update this [weblogic.j2ee.descriptor.wl.QueueBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.QueueBean](#) entity.

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/queues/{name}/deliveryFailureParams

This resource manages a [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/queues/{name}/deliveryFailureParams/findSubDeploymentName](#) **rel**=action **title**=findSubDeploymentName
This resource's findSubDeploymentName action resource.
- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/queues/{name}/deliveryFailureParams](#) **rel**=canonical
This resource.
- **rel**=errorDestination
This resource's errorDestination reference to a [weblogic.j2ee.descriptor.wl.DestinationBean](#) resource.
- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/queues/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/queues/{name}/deliveryFailureParams](#) **rel**=self
This resource.
- **rel**=templateBean
This resource's templateBean reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) entity.

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/queues/{name}/deliveryFailureParams/findSubDeploymentName

The resource supports the following methods:

- [POST](#)

POST

This is used to find the sub-deployment-name for this destination.

Roles

Admin, Deployer

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/queues/{name}/deliveryParamsOverrides

This resource manages a [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/queues/{name}/deliveryParamsOverrides **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/queues/{name} **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/queues/{name}/deliveryParamsOverrides **rel**=self
This resource.
- **rel**=templateBean
This resource's templateBean reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) entity.

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/queues/{name}/messageLoggingParams

This resource manages a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/queues/{name}/messageLoggingParams **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/queues/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/queues/{name}/messageLoggingParams **rel**=self

This resource.

- **rel**=templateBean

This resource's templateBean reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) entity.

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/queues/{name}/thresholds

This resource manages a [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/queues/{name}/thresholds **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/queues/{name} **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/queues/{name}/thresholds **rel**=self
This resource.
- **rel**=templateBean
This resource's templateBean reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) entity.

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/quotaCreateForm

This resource manages the create forms for the quotas collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.j2ee.descriptor.wl.QuotaBean](#) entity populated with default values that can be customized then posted (using the POST method) to the quotas collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.QuotaBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/quotaCreateForm](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/quotas](#) **rel**=create

The collection resource for this create form resource.

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/quotaCreateForm](#) **rel**=self

This resource.

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/quotas

This resource manages a collection of [weblogic.j2ee.descriptor.wl.QuotaBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.j2ee.descriptor.wl.QuotaBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.j2ee.descriptor.wl.QuotaBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/quotas](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/quoteCreateForm](#) **rel**=create-form

The create form resource for this collection resource.

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/quotas](#) **rel**=self

This resource.

POST

Add a new [weblogic.j2ee.descriptor.wl.QuotaBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.QuotaBean](#) entity.

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/quotas/{name}

This resource manages a [weblogic.j2ee.descriptor.wl.QuotaBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.j2ee.descriptor.wl.QuotaBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.j2ee.descriptor.wl.QuotaBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.QuotaBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSSResource/quotas/{name}](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSSResource/quotas](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSSResource/quotas/{name}](#) **rel**=self
This resource.

POST

Update this [weblogic.j2ee.descriptor.wl.QuotaBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.QuotaBean](#) entity.

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/SAFEErrorHandlingCreateForm

This resource manages the create forms for the SAFEErrorHandlings collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.j2ee.descriptor.wl.SAFEErrorHandlingBean](#) entity populated with default values that can be customized then posted (using the POST method) to the [SAFEErrorHandlings](#) collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.SAFEErrorHandlingBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/SAFEErrorHandlingCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/SAFEErrorHandlings](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/SAFEErrorHandlingCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/SAFEErrorHandlings

This resource manages a collection of [weblogic.j2ee.descriptor.wl.SAFEErrorHandlingBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.j2ee.descriptor.wl.SAFErrorHandlingBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.j2ee.descriptor.wl.SAFErrorHandlingBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/SAFErrorHandlings](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/SAFErrorHandlingCreateForm](#) **rel**=create-form

The create form resource for this collection resource.

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/SAFErrorHandlings](#) **rel**=self

This resource.

POST

Add a new [weblogic.j2ee.descriptor.wl.SAFErrorHandlingBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.SAFErrorHandlingBean](#) entity.

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/SAFEErrorHandlings/{name}

This resource manages a [weblogic.j2ee.descriptor.wl.SAFEErrorHandlingBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.j2ee.descriptor.wl.SAErrorHandlingBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.j2ee.descriptor.wl.SAFEErrorHandlingBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.SAFEErrorHandlingBean](#) entity.

This method can return the following links:

- **rel=SAFEErrorDestination**
This resource's SAFEErrorDestination reference to a [weblogic.j2ee.descriptor.wl.SAFDestinationBean](#) resource.
- **uri=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/SAFEErrorHandlings/{name} rel=canonical**
This resource.
- **uri=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/SAFEErrorHandlings rel=parent**
The parent resource of this resource.
- **uri=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/SAFEErrorHandlings/{name} rel=self**
This resource.

POST

Update this [weblogic.j2ee.descriptor.wl.SAFErrorHandlingBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.SAFErrorHandlingBean](#) entity.

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/SAFImportedDestinationCreateForm

This resource manages the create forms for the SAFImportedDestinations collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.j2ee.descriptor.wl.SAFImportedDestinationsBean](#) entity populated with default values that can be customized then posted (using the POST method) to the SAFImportedDestinations collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.SAFImportedDestinationsBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSSResource/SAFImportedDestinationCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSSResource/SAFImportedDestinations](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSSResource](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSSResource/SAFImportedDestinationCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations

This resource manages a collection of [weblogic.j2ee.descriptor.wl.SAFImportedDestinationsBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.j2ee.descriptor.wl.SAFImportedDestinationsBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.j2ee.descriptor.wl.SAFImportedDestinationsBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/SAFImportedDestinationCreateForm](#) **rel**=create-form

The create form resource for this collection resource.

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations](#) **rel**=self

This resource.

POST

Add a new [weblogic.j2ee.descriptor.wl.SAFImportedDestinationsBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.SAFImportedDestinationsBean](#) entity.

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}

This resource manages a [weblogic.j2ee.descriptor.wl.SAFImportedDestinationsBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.j2ee.descriptor.wl.SAFImportedDestinationsBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.j2ee.descriptor.wl.SAFImportedDestinationsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.SAFImportedDestinationsBean](#) entity.

This method can return the following links:

- **rel=SAFErrorHandling**
This resource's SAFErrorHandling reference to a [weblogic.j2ee.descriptor.wl.SAFErrorHandlingBean](#) resource.
- **uri=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFQueueCreateForm**
rel=SAFQueueCreateForm
The create form resource for this resource's SAFQueues collection resource.
- **uri=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFQueues** **rel=SAFQueues**
This resource's SAFQueues collection resource.
- **rel=SAFRemoteContext**
This resource's SAFRemoteContext reference to a [weblogic.j2ee.descriptor.wl.SAFRemoteContextBean](#) resource.
- **uri=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFTopicCreateForm**
rel=SAFTopicCreateForm
The create form resource for this resource's SAFTopics collection resource.
- **uri=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFTopics** **rel=SAFTopics**
This resource's SAFTopics collection resource.
- **uri=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}** **rel=canonical**
This resource.
- **uri=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/messageLoggingParams**
rel=messageLoggingParams
This resource's messageLoggingParams singleton resource.
- **uri=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations** **rel=parent**
The parent resource of this resource.
- **uri=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}** **rel=self**

This resource.

POST

Update this [weblogic.j2ee.descriptor.wl.SAFImportedDestinationsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.SAFImportedDestinationsBean](#) entity.

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/messageLoggingParams

This resource manages a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/messageLoggingParams](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/messageLoggingParams](#) **rel**=self
This resource.
- **rel**=templateBean
This resource's `templateBean` reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) entity.

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFQueueCreateForm

This resource manages the create forms for the SAFQueues collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.j2ee.descriptor.wl.SAFQueueBean](#) entity populated with default values that can be customized then posted (using the POST method) to the SAFQueues collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.SAFQueueBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFQueueCreateForm **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFQueues **rel**=create

The collection resource for this create form resource.

- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFQueueCreateForm **rel**=self

This resource.

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFQueues

This resource manages a collection of [weblogic.j2ee.descriptor.wl.SAFQueueBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.j2ee.descriptor.wl.SAFQueueBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.j2ee.descriptor.wl.SAFQueueBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFQueues **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFQueueCreateForm **rel**=create-form
The create form resource for this collection resource.
- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name} **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFQueues **rel**=self
This resource.

POST

Add a new [weblogic.j2ee.descriptor.wl.SAFQueueBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.SAFQueueBean](#) entity.

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFQueues/{name}

This resource manages a [weblogic.j2ee.descriptor.wl.SAFQueueBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.j2ee.descriptor.wl.SAFQueueBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.j2ee.descriptor.wl.SAFQueueBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.SAFQueueBean](#) entity.

This method can return the following links:

- **rel=SAFErrorHandling**
This resource's SAFErrorHandling reference to a [weblogic.j2ee.descriptor.wl.SAFErrorHandlingBean](#) resource.
- **uri=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFQueues/{name} rel=canonical**
This resource.
- **uri=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFQueues/{name}/messageLoggingParams rel=messageLoggingParams**
This resource's messageLoggingParams singleton resource.
- **uri=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFQueues rel=parent**
The parent resource of this resource.
- **uri=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFQueues/{name} rel=self**
This resource.

POST

Update this [weblogic.j2ee.descriptor.wl.SAFQueueBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.SAFQueueBean](#) entity.

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFQueues/{name}/messageLoggingParams

This resource manages a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFQueues/{name}/messageLoggingParams](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFQueues/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFQueues/{name}/messageLoggingParams](#) **rel**=self

This resource.

- **rel**=templateBean

This resource's `templateBean` reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) entity.

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFTopicCreateForm

This resource manages the create forms for the SAFTopics collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.j2ee.descriptor.wl.SAFTopicBean](#) entity populated with default values that can be customized then posted (using the POST method) to the SAFTopics collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.SAFTopicBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFTopicCreateForm **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFTopics **rel**=create

The collection resource for this create form resource.

- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFTopicCreateForm **rel**=self

This resource.

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFTopics

This resource manages a collection of [weblogic.j2ee.descriptor.wl.SAFTopicBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.j2ee.descriptor.wl.SAFTopicBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.j2ee.descriptor.wl.SAFTopicBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFTopics **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFTopicCreateForm **rel**=create-form

The create form resource for this collection resource.

- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFTopics **rel**=self

This resource.

POST

Add a new [weblogic.j2ee.descriptor.wl.SAFTopicBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.SAFTopicBean](#) entity.

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFTopics/{name}

This resource manages a [weblogic.j2ee.descriptor.wl.SAFTopicBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.j2ee.descriptor.wl.SAFTopicBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.j2ee.descriptor.wl.SAFTopicBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.SAFTopicBean](#) entity.

This method can return the following links:

- **rel=SAFErrorHandling**
This resource's SAFErrorHandling reference to a [weblogic.j2ee.descriptor.wl.SAFErrorHandlingBean](#) resource.
- **uri=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFTopics/{name} rel=canonical**
This resource.
- **uri=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFTopics/{name}/messageLoggingParams rel=messageLoggingParams**
This resource's messageLoggingParams singleton resource.
- **uri=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFTopics rel=parent**
The parent resource of this resource.
- **uri=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFTopics/{name} rel=self**
This resource.

POST

Update this [weblogic.j2ee.descriptor.wl.SAFTopicBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.SAFTopicBean](#) entity.

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFTopics/{name}/messageLoggingParams

This resource manages a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFTopics/{name}/messageLoggingParams](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFTopics/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFTopics/{name}/messageLoggingParams](#) **rel**=self

This resource.

- **rel**=templateBean

This resource's templateBean reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) entity.

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/SAFRemoteContextCreateForm

This resource manages the create forms for the SAFRemoteContexts collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.j2ee.descriptor.wl.SAFRemoteContextBean](#) entity populated with default values that can be customized then posted (using the POST method) to the SAFRemoteContexts collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.SAFRemoteContextBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/SAFRemoteContextCreateForm](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/SAFRemoteContexts](#) **rel**=create
The collection resource for this create form resource.
- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/SAFRemoteContextCreateForm](#) **rel**=self
This resource.

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/SAFRemoteContexts

This resource manages a collection of [weblogic.j2ee.descriptor.wl.SAFRemoteContextBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.j2ee.descriptor.wl.SAFRemoteContextBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.j2ee.descriptor.wl.SAFRemoteContextBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/SAFRemoteContexts](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/SAFRemoteContextCreateForm](#) **rel**=create-form
The create form resource for this collection resource.
- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/SAFRemoteContexts](#) **rel**=self
This resource.

POST

Add a new [weblogic.j2ee.descriptor.wl.SAFRemoteContextBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.SAFRemoteContextBean](#) entity.

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/SAFRemoteContexts/{name}

This resource manages a [weblogic.j2ee.descriptor.wl.SAFRemoteContextBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

DELETE

Delete this [weblogic.j2ee.descriptor.wl.SAFRemoteContextBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.j2ee.descriptor.wl.SAFRemoteContextBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.SAFRemoteContextBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/SAFRemoteContexts/{name}/SAFLoginContext](#) **rel=SAFLoginContext**
This resource's SAFLoginContext singleton resource.
- [uri=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/SAFRemoteContexts/{name}](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/SAFRemoteContexts](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/SAFRemoteContexts/{name}](#) **rel=self**
This resource.

POST

Update this [weblogic.j2ee.descriptor.wl.SAFRemoteContextBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.SAFRemoteContextBean](#) entity.

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/SAFRemoteContexts/{name}/SAFLoginContext

This resource manages a [weblogic.j2ee.descriptor.wl.SAFLoginContextBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.SAFLoginContextBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.SAFLoginContextBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/SAFRemoteContexts/{name}/SAFLoginContext](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/SAFRemoteContexts/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/SAFRemoteContexts/{name}/SAFLoginContext](#) **rel**=self

This resource.

POST

Update this [weblogic.j2ee.descriptor.wl.SAFLoginContextBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.SAFLoginContextBean](#) entity.

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/templateCreateForm

This resource manages the create forms for the templates collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.j2ee.descriptor.wl.TemplateBean](#) entity populated with default values that can be customized then posted (using the POST method) to the templates collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.TemplateBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/templateCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/templates](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/templateCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/templates

This resource manages a collection of [weblogic.j2ee.descriptor.wl.TemplateBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.j2ee.descriptor.wl.TemplateBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.j2ee.descriptor.wl.TemplateBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/templates](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/templateCreateForm](#) **rel=create-form**
The create form resource for this collection resource.
- [uri=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/templates](#) **rel=self**
This resource.

POST

Add a new [weblogic.j2ee.descriptor.wl.TemplateBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.TemplateBean](#) entity.

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/templates/{name}

This resource manages a [weblogic.j2ee.descriptor.wl.TemplateBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.j2ee.descriptor.wl.TemplateBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.j2ee.descriptor.wl.TemplateBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.TemplateBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/templates/{name}/findErrorDestination](#) **rel**=action
title=findErrorDestination
This resource's findErrorDestination action resource.
- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/templates/{name}](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/templates/{name}/deliveryFailureParams](#) **rel**=deliveryFailureParams
This resource's deliveryFailureParams singleton resource.
- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/templates/{name}/deliveryParamsOverrides](#) **rel**=deliveryParamsOverrides
This resource's deliveryParamsOverrides singleton resource.
- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/templates/{name}/groupParamCreateForm](#) **rel**=groupParamCreateForm
The create form resource for this resource's groupParams collection resource.
- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/templates/{name}/groupParams](#) **rel**=groupParams
This resource's groupParams collection resource.
- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/templates/{name}/messageLoggingParams](#) **rel**=messageLoggingParams
This resource's messageLoggingParams singleton resource.
- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/templates/{name}/multicast](#) **rel**=multicast
This resource's multicast singleton resource.
- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/templates](#) **rel**=parent
The parent resource of this resource.
- **rel**=quota
This resource's quota reference to a [weblogic.j2ee.descriptor.wl.QuotaBean](#) resource.

- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/templates/{name} **rel**=self

This resource.

- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/templates/{name}/thresholds **rel**=thresholds

This resource's thresholds singleton resource.

- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/templates/{name}/topicSubscriptionParams **rel**=topicSubscriptionParams

This resource's topicSubscriptionParams singleton resource.

POST

Update this [weblogic.j2ee.descriptor.wl.TemplateBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.TemplateBean](#) entity.

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/templates/{name}/deliveryFailureParams

This resource manages a [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/templates/{name}/deliveryFailureParams/findSubDeploymentName
rel=action **title**=findSubDeploymentName
This resource's findSubDeploymentName action resource.
- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/templates/{name}/deliveryFailureParams **rel**=canonical
This resource.
- **rel**=errorDestination
This resource's errorDestination reference to a [weblogic.j2ee.descriptor.wl.DestinationBean](#) resource.
- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/templates/{name} **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/templates/{name}/deliveryFailureParams **rel**=self
This resource.
- **rel**=templateBean
This resource's templateBean reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) entity.

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/templates/{name}/deliveryFailureParams/findSubDeploymentName

The resource supports the following methods:

- [POST](#)

POST

This is used to find the sub-deployment-name for this destination.

Roles

Admin, Deployer

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/templates/{name}/deliveryParamsOverrides

This resource manages a [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/templates/{name}/deliveryParamsOverrides](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/templates/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/templates/{name}/deliveryParamsOverrides](#) **rel**=self

This resource.

- **rel**=templateBean

This resource's `templateBean` reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) entity.

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/templates/{name}/findErrorDestination

The resource supports the following methods:

- [POST](#)

POST

Finds the name of the error destination to use when a destination comes from a specific group

Roles

Admin, Deployer

Request Body

Must contain a JSON object with the following fields:

subDeploymentName

The subDeployment for which to find the quota

Type: string

Response Body

Contains a JSON object with a weblogic.j2ee.descriptor.wl.DestinationBean reference return field.

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/templates/{name}/groupParamCreateForm

This resource manages the create forms for the groupParams collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.j2ee.descriptor.wl.GroupParamsBean](#) entity populated with default values that can be customized then posted (using the POST method) to the groupParams collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.GroupParamsBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/templates/{name}/groupParamCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/templates/{name}/groupParams](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/templates/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/templates/{name}/groupParamCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/templates/{name}/groupParams

This resource manages a collection of [weblogic.j2ee.descriptor.wl.GroupParamsBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.j2ee.descriptor.wl.GroupParamsBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.j2ee.descriptor.wl.GroupParamsBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/templates/{name}/groupParams **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/templates/{name}/groupParamCreateForm **rel**=create-form

The create form resource for this collection resource.

- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/templates/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/templates/{name}/groupParams **rel**=self

This resource.

POST

Add a new [weblogic.j2ee.descriptor.wl.GroupParamsBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.GroupParamsBean](#) entity.

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/templates/{name}/groupParams/{subDeploymentName}

This resource manages a [weblogic.j2ee.descriptor.wl.GroupParamsBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.j2ee.descriptor.wl.GroupParamsBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.j2ee.descriptor.wl.GroupParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.GroupParamsBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/templates/{name}/groupParams/{subDeploymentName} **rel**=canonical
This resource.
- **rel**=errorDestination
This resource's errorDestination reference to a [weblogic.j2ee.descriptor.wl.DestinationBean](#) resource.
- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/templates/{name}/groupParams **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/templates/{name}/groupParams/{subDeploymentName} **rel**=self
This resource.

POST

Update this [weblogic.j2ee.descriptor.wl.GroupParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.GroupParamsBean](#) entity.

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/templates/{name}/messageLoggingParams

This resource manages a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/templates/{name}/messageLoggingParams](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/templates/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/templates/{name}/messageLoggingParams](#) **rel**=self

This resource.

- **rel**=templateBean

This resource's `templateBean` reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) entity.

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/templates/{name}/multicast

This resource manages a [weblogic.j2ee.descriptor.wl.MulticastParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.MulticastParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.MulticastParamsBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/templates/{name}/multicast **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/templates/{name} **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/templates/{name}/multicast **rel**=self
This resource.
- **rel**=templateBean
This resource's templateBean reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.MulticastParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.MulticastParamsBean](#) entity.

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/templates/{name}/thresholds

This resource manages a [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/templates/{name}/thresholds](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/templates/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/templates/{name}/thresholds](#) **rel**=self

This resource.

- **rel**=templateBean

This resource's templateBean reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) entity.

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/templates/{name}/topicSubscriptionParams

This resource manages a [weblogic.j2ee.descriptor.wl.TopicSubscriptionParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.TopicSubscriptionParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.TopicSubscriptionParamsBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/templates/{name}/topicSubscriptionParams **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/templates/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/templates/{name}/topicSubscriptionParams **rel**=self

This resource.

- **rel**=templateBean

This resource's templateBean reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.TopicSubscriptionParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.TopicSubscriptionParamsBean](#) entity.

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/topicCreateForm

This resource manages the create forms for the topics collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.j2ee.descriptor.wl.TopicBean](#) entity populated with default values that can be customized then posted (using the POST method) to the topics collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.TopicBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/topicCreateForm](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/topics](#) **rel**=create

The collection resource for this create form resource.

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/topicCreateForm](#) **rel**=self

This resource.

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/topics

This resource manages a collection of [weblogic.j2ee.descriptor.wl.TopicBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.j2ee.descriptor.wl.TopicBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.j2ee.descriptor.wl.TopicBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/topics](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/topicCreateForm](#) **rel**=create-form

The create form resource for this collection resource.

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/topics](#) **rel**=self

This resource.

POST

Add a new [weblogic.j2ee.descriptor.wl.TopicBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.TopicBean](#) entity.

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/topics/{name}

This resource manages a [weblogic.j2ee.descriptor.wl.TopicBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.j2ee.descriptor.wl.TopicBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.j2ee.descriptor.wl.TopicBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.TopicBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/topics/{name} **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/topics/{name}/deliveryFailureParams **rel**=deliveryFailureParams
This resource's deliveryFailureParams singleton resource.
- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/topics/{name}/deliveryParamsOverrides **rel**=deliveryParamsOverrides
This resource's deliveryParamsOverrides singleton resource.
- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/topics/{name}/messageLoggingParams **rel**=messageLoggingParams
This resource's messageLoggingParams singleton resource.
- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/topics/{name}/multicast **rel**=multicast
This resource's multicast singleton resource.
- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/topics **rel**=parent
The parent resource of this resource.
- **rel**=quota
This resource's quota reference to a [weblogic.j2ee.descriptor.wl.QuotaBean](#) resource.
- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/topics/{name} **rel**=self
This resource.
- **rel**=template
This resource's template reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.
- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/topics/{name}/thresholds **rel**=thresholds
This resource's thresholds singleton resource.
- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/topics/{name}/topicSubscriptionParams **rel**=topicSubscriptionParams

This resource's topicSubscriptionParams singleton resource.

POST

Update this [weblogic.j2ee.descriptor.wl.TopicBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.TopicBean](#) entity.

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/topics/{name}/deliveryFailureParams

This resource manages a [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/topics/{name}/deliveryFailureParams/findSubDeploymentName](#) **rel**=action **title**=findSubDeploymentName
This resource's findSubDeploymentName action resource.
- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/topics/{name}/deliveryFailureParams](#) **rel**=canonical
This resource.
- **rel**=errorDestination
This resource's errorDestination reference to a [weblogic.j2ee.descriptor.wl.DestinationBean](#) resource.
- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/topics/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/topics/{name}/deliveryFailureParams](#) **rel**=self
This resource.
- **rel**=templateBean
This resource's templateBean reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) entity.

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/topics/{name}/deliveryFailureParams/findSubDeploymentName

The resource supports the following methods:

- [POST](#)

POST

This is used to find the sub-deployment-name for this destination.

Roles

Admin, Deployer

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/topics/{name}/deliveryParamsOverrides

This resource manages a [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/topics/{name}/deliveryParamsOverrides **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/topics/{name} **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/topics/{name}/deliveryParamsOverrides **rel**=self
This resource.
- **rel**=templateBean
This resource's templateBean reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) entity.

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/topics/{name}/messageLoggingParams

This resource manages a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/topics/{name}/messageLoggingParams](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/topics/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/topics/{name}/messageLoggingParams](#) **rel**=self

This resource.

- **rel**=templateBean

This resource's `templateBean` reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) entity.

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/topics/{name}/multicast

This resource manages a [weblogic.j2ee.descriptor.wl.MulticastParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.MulticastParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.MulticastParamsBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/topics/{name}/multicast](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/topics/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/topics/{name}/multicast](#) **rel**=self
This resource.
- **rel**=templateBean
This resource's templateBean reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.MulticastParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.MulticastParamsBean](#) entity.

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/topics/{name}/thresholds

This resource manages a [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/topics/{name}/thresholds](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/topics/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/topics/{name}/thresholds](#) **rel**=self
This resource.
- **rel**=templateBean
This resource's templateBean reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) entity.

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/topics/{name}/topicSubscriptionParams

This resource manages a [weblogic.j2ee.descriptor.wl.TopicSubscriptionParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.TopicSubscriptionParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.TopicSubscriptionParamsBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/topics/{name}/topicSubscriptionParams **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/topics/{name} **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/topics/{name}/topicSubscriptionParams **rel**=self
This resource.
- **rel**=templateBean
This resource's templateBean reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.TopicSubscriptionParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.TopicSubscriptionParamsBean](#) entity.

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/uniformDistributedQueueCreateForm

This resource manages the create forms for the uniformDistributedQueues collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.j2ee.descriptor.wl.UniformDistributedQueueBean](#) entity populated with default values that can be customized then posted (using the POST method) to the `uniformDistributedQueues` collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.UniformDistributedQueueBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/uniformDistributedQueueCreateForm](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues](#) **rel**=create

The collection resource for this create form resource.

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/uniformDistributedQueueCreateForm](#) **rel**=self

This resource.

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues

This resource manages a collection of [weblogic.j2ee.descriptor.wl.UniformDistributedQueueBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.j2ee.descriptor.wl.UniformDistributedQueueBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.j2ee.descriptor.wl.UniformDistributedQueueBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/uniformDistributedQueueCreateForm](#) **rel**=create-form

The create form resource for this collection resource.

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues](#) **rel**=self

This resource.

POST

Add a new [weblogic.j2ee.descriptor.wl.UniformDistributedQueueBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.UniformDistributedQueueBean](#) entity.

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues/{name}

This resource manages a [weblogic.j2ee.descriptor.wl.UniformDistributedQueueBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.j2ee.descriptor.wl.UniformDistributedQueueBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.j2ee.descriptor.wl.UniformDistributedQueueBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.UniformDistributedQueueBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues/{name}](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues/{name}/deliveryFailureParams](#) **rel**=deliveryFailureParams
This resource's deliveryFailureParams singleton resource.
- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues/{name}/deliveryParamsOverrides](#) **rel**=deliveryParamsOverrides
This resource's deliveryParamsOverrides singleton resource.
- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues/{name}/messageLoggingParams](#) **rel**=messageLoggingParams
This resource's messageLoggingParams singleton resource.
- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues](#) **rel**=parent
The parent resource of this resource.
- **rel**=quota
This resource's quota reference to a [weblogic.j2ee.descriptor.wl.QuotaBean](#) resource.
- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues/{name}](#) **rel**=self
This resource.
- **rel**=template
This resource's template reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.
- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues/{name}/thresholds](#) **rel**=thresholds
This resource's thresholds singleton resource.

POST

Update this [weblogic.j2ee.descriptor.wl.UniformDistributedQueueBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.UniformDistributedQueueBean](#) entity.

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues/{name}/deliveryFailureParams

This resource manages a [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues/{name}/deliveryFailureParams/findSubDeploymentName rel=action title=findSubDeploymentName](#)
This resource's findSubDeploymentName action resource.
- [uri=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues/{name}/deliveryFailureParams rel=canonical](#)
This resource.
- [rel=errorDestination](#)
This resource's errorDestination reference to a [weblogic.j2ee.descriptor.wl.DestinationBean](#) resource.
- [uri=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues/{name} rel=parent](#)
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues/{name}/deliveryFailureParams rel=self](#)
This resource.
- [rel=templateBean](#)
This resource's templateBean reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) entity.

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues/{name}/deliveryFailureParams/findSubDeploymentName

The resource supports the following methods:

- [POST](#)

POST

This is used to find the sub-deployment-name for this destination.

Roles

Admin, Deployer

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues/{name}/deliveryParamsOverrides

This resource manages a [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues/{name}/deliveryParamsOverrides](#)
rel=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues/{name}/deliveryParamsOverrides](#) **rel**=self

This resource.

- **rel**=templateBean

This resource's templateBean reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) entity.

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues/{name}/messageLoggingParams

This resource manages a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues/{name}/messageLoggingParams](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues/{name}/messageLoggingParams](#) **rel=self**
This resource.
- **rel=templateBean**
This resource's `templateBean` reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) entity.

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues/{name}/thresholds

This resource manages a [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues/{name}/thresholds](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues/{name}/thresholds](#) **rel**=self

This resource.

- **rel**=templateBean

This resource's `templateBean` reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues/{name}/thresh-

POST

Update this [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) entity.

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/uniformDistributedTopicCreateForm

This resource manages the create forms for the uniformDistributedTopics collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.j2ee.descriptor.wl.UniformDistributedTopicBean](#) entity populated with default values that can be customized then posted (using the POST method) to the `uniformDistributedTopics` collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.UniformDistributedTopicBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/uniformDistributedTopicCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/uniformDistributedTopicCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics

This resource manages a collection of [weblogic.j2ee.descriptor.wl.UniformDistributedTopicBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.j2ee.descriptor.wl.UniformDistributedTopicBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.j2ee.descriptor.wl.UniformDistributedTopicBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/uniformDistributedTopicCreateForm **rel**=create-form

The create form resource for this collection resource.

- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics **rel**=self

This resource.

POST

Add a new [weblogic.j2ee.descriptor.wl.UniformDistributedTopicBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.UniformDistributedTopicBean](#) entity.

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}

This resource manages a [weblogic.j2ee.descriptor.wl.UniformDistributedTopicBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.j2ee.descriptor.wl.UniformDistributedTopicBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.j2ee.descriptor.wl.UniformDistributedTopicBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.UniformDistributedTopicBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}/deliveryFailureParams](#) **rel=deliveryFailureParams**
This resource's `deliveryFailureParams` singleton resource.
- [uri=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}/deliveryParamsOverrides](#) **rel=deliveryParamsOverrides**
This resource's `deliveryParamsOverrides` singleton resource.
- [uri=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}/messageLoggingParams](#) **rel=messageLoggingParams**
This resource's `messageLoggingParams` singleton resource.
- [uri=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}/multicast](#) **rel=multicast**
This resource's `multicast` singleton resource.
- [uri=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics](#) **rel=parent**
The parent resource of this resource.
- **rel=quota**
This resource's `quota` reference to a `weblogic.j2ee.descriptor.wl.QuotaBean` resource.
- [uri=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}](#) **rel=self**
This resource.
- **rel=template**
This resource's `template` reference to a `weblogic.j2ee.descriptor.wl.TemplateBean` resource.
- [uri=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}/thresholds](#) **rel=thresholds**

This resource's thresholds singleton resource.

- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSSResource/uniformDistributedTopics/{name}/topicSubscriptionParams
rel=topicSubscriptionParams

This resource's topicSubscriptionParams singleton resource.

POST

Update this [weblogic.j2ee.descriptor.wl.UniformDistributedTopicBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.UniformDistributedTopicBean](#) entity.

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}/deliveryFailureParams

This resource manages a [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}/deliveryFailureParams/findSubDeploymentName **rel**=action **title**=findSubDeploymentName
This resource's findSubDeploymentName action resource.
- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}/deliveryFailureParams **rel**=canonical
This resource.
- **rel**=errorDestination
This resource's errorDestination reference to a [weblogic.j2ee.descriptor.wl.DestinationBean](#) resource.
- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name} **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}/deliveryFailureParams **rel**=self
This resource.
- **rel**=templateBean
This resource's templateBean reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) entity.

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}/deliveryFailureParams/findSubDeploymentName

The resource supports the following methods:

- [POST](#)

POST

This is used to find the sub-deployment-name for this destination.

Roles

Admin, Deployer

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}/deliveryParamsOverrides

This resource manages a [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}/deliveryParamsOverrides](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}/deliveryParamsOverrides](#) **rel**=self
This resource.
- **rel**=templateBean
This resource's templateBean reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) entity.

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}/messageLoggingParams

This resource manages a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}/messageLoggingParams **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name} **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}/messageLoggingParams **rel**=self
This resource.
- **rel**=templateBean
This resource's templateBean reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) entity.

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}/multicast

This resource manages a [weblogic.j2ee.descriptor.wl.MulticastParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.MulticastParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.MulticastParamsBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}/multicast](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}/multicast](#) **rel**=self

This resource.

- **rel**=templateBean

This resource's templateBean reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.MulticastParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.MulticastParamsBean](#) entity.

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}/thresholds

This resource manages a [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}/thresholds **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name} **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}/thresholds **rel**=self
This resource.
- **rel**=templateBean
This resource's templateBean reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) entity.

/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}/topicSubscriptionParams

This resource manages a [weblogic.j2ee.descriptor.wl.TopicSubscriptionParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.TopicSubscriptionParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.TopicSubscriptionParamsBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}/topicSubscriptionParams](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}/topicSubscriptionParams](#) **rel**=self
This resource.
- **rel**=templateBean
This resource's templateBean reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.TopicSubscriptionParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.TopicSubscriptionParamsBean](#) entity.

/management/weblogic/{version}/edit/JMSSystemResources/{name}/subDeploymentCreateForm

This resource manages the create forms for the subDeployments collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.SubDeploymentMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the subDeployments collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/JMSSystemResources/{name}/subDeploymentCreateForm](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/JMSSystemResources/{name}/subDeployments](#) **rel=create**
The collection resource for this create form resource.
- [uri=/management/weblogic/{version}/edit/JMSSystemResources/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/JMSSystemResources/{name}/subDeploymentCreateForm](#) **rel=self**
This resource.

/management/weblogic/{version}/edit/JMSSystemResources/{name}/subDeployments

This resource manages a collection of [weblogic.management.configuration.SubDeploymentMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.SubDeploymentMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.SubDeploymentMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/JMSSystemResources/{name}/subDeployments](#) [rel=canonical](#)
This resource.
- [uri=/management/weblogic/{version}/edit/JMSSystemResources/{name}/subDeploymentCreateForm](#) [rel=create-form](#)
The create form resource for this collection resource.
- [uri=/management/weblogic/{version}/edit/JMSSystemResources/{name}](#) [rel=parent](#)
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/JMSSystemResources/{name}/subDeployments](#) [rel=self](#)
This resource.

POST

Add a new [weblogic.management.configuration.SubDeploymentMBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

/management/weblogic/{version}/edit/JMSSystemResources/{name}/subDeployments/{name}

This resource manages a [weblogic.management.configuration.SubDeploymentMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/subDeployments/{name} **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/subDeployments **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/subDeployments/{name} **rel**=self
This resource.
- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/subDeployments/{name}/subDeployments **rel**=subDeployments
This resource's subDeployments collection resource.

POST

Update this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

/management/weblogic/{version}/edit/JMSSystemResources/{name}/subDeployments/{name}/subDeployments

This resource manages a collection of [weblogic.management.configuration.SubDeploymentMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.configuration.SubDeploymentMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.SubDeploymentMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/subDeployments/{name}/subDeployments](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/subDeployments/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/JMSSystemResources/{name}/subDeployments/{name}/subDeployments](#) **rel**=self

This resource.

/management/weblogic/{version}/edit/JMSSystemResources/{name}/subDeployments/{name}/subDeployments/{name}

This resource manages a [weblogic.management.configuration.SubDeploymentMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/subDeployments/{name}/subDeployments/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/subDeployments/{name}/subDeployments **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/subDeployments/{name}/subDeployments/{name} **rel**=self

This resource.

- **uri**=/management/weblogic/{version}/edit/JMSSystemResources/{name}/subDeployments/{name}/subDeployments/{name}/subDeployments **rel**=subDeployments

This resource's subDeployments collection resource.

POST

Update this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

/management/weblogic/{version}/edit/JMX

This resource manages a [weblogic.management.configuration.JMXMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.JMXBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.JMXBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/JMX](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/JMX](#) **rel**=self
This resource.

POST

POST

Update this [weblogic.management.configuration.JMXMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.JMXMBean](#) entity.

/management/weblogic/{version}/edit/joltConnectionPoolCreateForm

This resource manages the create forms for the joltConnectionPools collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.JoltConnectionPoolMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the `joltConnectionPools` collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.JoltConnectionPoolMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/joltConnectionPoolCreateForm](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/joltConnectionPools](#) **rel**=create
The collection resource for this create form resource.
- **uri**=[/management/weblogic/{version}/edit](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/joltConnectionPoolCreateForm](#)
rel=self
This resource.

/management/weblogic/{version}/edit/joltConnectionPools

This resource manages a collection of [weblogic.management.configuration.JoltConnectionPoolMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.JoltConnectionPoolMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.JoltConnectionPoolMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/joltConnectionPools](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/joltConnectionPoolCreateForm](#)
rel=create-form
The create form resource for this collection resource.
- **uri**=[/management/weblogic/{version}/edit](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/joltConnectionPools](#) **rel**=self
This resource.

POST

Add a new [weblogic.management.configuration.JoltConnectionPoolMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.JoltConnectionPoolMBean](#) entity.

/management/weblogic/{version}/edit/joltConnectionPools/{name}

This resource manages a [weblogic.management.configuration.JoltConnectionPoolMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.JoltConnectionPoolMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.JoltConnectionPoolMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.JoltConnectionPoolMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/joltConnectionPools/{name}](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/joltConnectionPools](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/joltConnectionPools/{name}](#) **rel**=self
This resource.

POST

Update this [weblogic.management.configuration.JoltConnectionPoolMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.JoltConnectionPoolMBean](#) entity.

/management/weblogic/{version}/edit/JPA

This resource manages a [weblogic.management.configuration.JPAMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.JPAMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.JPAMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/JPA](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/JPA](#) **rel**=self
This resource.

POST

POST

Update this [weblogic.management.configuration.JPAMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.JPAMBean](#) entity.

/management/weblogic/{version}/edit/JTA

This resource manages a [weblogic.management.configuration.JTAMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.JTAMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.JTAMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/JTA](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/JTA](#) **rel**=self
This resource.

POST

Update this [weblogic.management.configuration.JTAMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.JTAMBean](#) entity.

/management/weblogic/{version}/edit/libraries

This resource manages a collection of [weblogic.management.configuration.LibraryMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.LibraryMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.LibraryMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/libraries](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/libraries](#) **rel**=self
This resource.

POST

The resource supports the following methods:

- [POST accepting application/json](#)
- [POST accepting multipart/form-data](#)

POST accepting application/json

This resource is used to deploy libraries that are already on the administration server.

This method supports both asynchronous and best effort synchronous invocations. The behavior is controlled by the 'Prefer' header. See [About Synchronous and Asynchronous Operations](#).

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.LibraryMBean](#) entity.

To deploy a library, you must provide the name of the library, the path to the library, and the targets to which the library will be deployed.

Use the multi-part form to deploy a library.

- `sourcePath`: the deployment to upload (required)
- `model`: JSONObject containing a LibraryMBean entity that contains the rest of the deployment information (required)

POST accepting multipart/form-data

Upload a library from the client to the server then deploy it.

This method supports both asynchronous and best effort synchronous invocations. The behavior is controlled by the 'Prefer' header. See [About Synchronous and Asynchronous Operations](#).

Roles

Admin, Deployer

Request Body

Use the multi-part form to upload a library from the client to the server then deploy it.

- `sourcePath`: the deployment to upload (required)
- `model`: JSONObject containing a LibraryMBean entity that contains the rest of the deployment information (required)

/management/weblogic/{version}/edit/libraries/{name}

This resource manages a [weblogic.management.configuration.LibraryMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Undeploy a library.

This method supports both asynchronous and best effort synchronous invocations. The behavior is controlled by the 'Prefer' header. See [About Synchronous and Asynchronous Operations](#).

Roles

Admin, Deployer

GET

Get this [weblogic.management.configuration.LibraryMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.LibraryMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/libraries/{name}/createPlan](#)
[rel=action](#) [title=createPlan](#)
This resource's createPlan action resource.
- [uri=/management/weblogic/{version}/edit/libraries/{name}](#) [rel=canonical](#)
This resource.
- [uri=/management/weblogic/{version}/edit/libraries](#) [rel=parent](#)
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/libraries/{name}/redeploy](#)
[rel=redeploy](#)
This resource's redeploy resource.
- [uri=/management/weblogic/{version}/edit/libraries/{name}](#) [rel=self](#)
This resource.
- [uri=/management/weblogic/{version}/edit/libraries/{name}/subDeploymentCreateForm](#) [rel=subDeploymentCreateForm](#)
The create form resource for this resource's subDeployments collection resource.
- [uri=/management/weblogic/{version}/edit/libraries/{name}/subDeployments](#)
[rel=subDeployments](#)
This resource's subDeployments collection resource.

POST

Update this [weblogic.management.configuration.LibraryMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.LibraryMBean](#) entity.

/management/weblogic/{version}/edit/libraries/{name}/createPlan

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

POST

Create a deployment plan in the specified directory.

Roles

Admin, Deployer

Request Body

Must contain a JSON object with the following fields:

planPath

planPath

Type: string

Response Body

Contains a JSON object with a string return field.

POST

Create a deployment plan in a default directory

Roles

Admin, Deployer

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/edit/libraries/{name}/redeploy

The resource supports the following methods:

- [POST](#)

POST

Use the multi-part form to redeploy a library.

- `sourcePath`: the deployment to upload (required)
- `model`: JSONObject containing a LibraryMBean entity that contains the rest of the deployment information (required)

This method supports both asynchronous and best effort synchronous invocations. The behavior is controlled by the 'Prefer' header. See [About Synchronous and Asynchronous Operations](#).

Roles

Admin, Deployer

/management/weblogic/{version}/edit/libraries/{name}/subDeploymentCreateForm

This resource manages the create forms for the subDeployments collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.SubDeploymentMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the subDeployments collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/libraries/{name}/subDeploymentCreateForm](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/libraries/{name}/subDeployments](#) **rel**=create
The collection resource for this create form resource.
- **uri**=[/management/weblogic/{version}/edit/libraries/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/libraries/{name}/subDeploymentCreateForm](#) **rel**=self
This resource.

/management/weblogic/{version}/edit/libraries/{name}/subDeployments

This resource manages a collection of [weblogic.management.configuration.SubDeploymentMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.SubDeploymentMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.SubDeploymentMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/libraries/{name}/subDeployments](#)
rel=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/libraries/{name}/subDeploymentCreateForm](#) **rel**=create-form

The create form resource for this collection resource.

- **uri**=[/management/weblogic/{version}/edit/libraries/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/libraries/{name}/subDeployments](#)
rel=self

This resource.

POST

Add a new [weblogic.management.configuration.SubDeploymentMBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

/management/weblogic/{version}/edit/libraries/{name}/subDeployments/{name}

This resource manages a [weblogic.management.configuration.SubDeploymentMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/libraries/{name}/subDeployments/{name}](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/libraries/{name}/subDeployments](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/libraries/{name}/subDeployments/{name}](#) **rel**=self
This resource.
- **uri**=[/management/weblogic/{version}/edit/libraries/{name}/subDeployments/{name}/subDeployments](#) **rel**=subDeployments
This resource's subDeployments collection resource.

POST

Update this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

/management/weblogic/{version}/edit/libraries/{name}/subDeployments/{name}/subDeployments

This resource manages a collection of [weblogic.management.configuration.SubDeploymentMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.configuration.SubDeploymentMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.SubDeploymentMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/libraries/{name}/subDeployments/{name}/subDeployments](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/libraries/{name}/subDeployments/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/libraries/{name}/subDeployments/{name}/subDeployments](#) **rel=self**
This resource.

/management/weblogic/{version}/edit/libraries/{name}/subDeployments/{name}/subDeployments/{name}

This resource manages a [weblogic.management.configuration.SubDeploymentMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/libraries/{name}/subDeployments/{name}/subDeployments/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/libraries/{name}/subDeployments/{name}/subDeployments](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/libraries/{name}/subDeployments/{name}/subDeployments/{name}](#) **rel**=self

This resource.

- **uri**=[/management/weblogic/{version}/edit/libraries/{name}/subDeployments/{name}/subDeployments/{name}/subDeployments](#) **rel**=subDeployments

This resource's subDeployments collection resource.

POST

POST

Update this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

/management/weblogic/{version}/edit/lifecycleManagerConfig

This resource manages a [weblogic.management.configuration.LifecycleManagerConfigMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.LifecycleManagerConfigMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.LifecycleManagerConfigMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/lifecycleManagerConfig](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/lifecycleManagerConfig/configuredEndPointCreateForm](#) **rel**=configuredEndPointCreateForm
The create form resource for this resource's configuredEndpoints collection resource.
- **uri**=[/management/weblogic/{version}/edit/lifecycleManagerConfig/configuredEndpoints](#) **rel**=configuredEndpoints
This resource's configuredEndpoints collection resource.
- **uri**=[/management/weblogic/{version}/edit](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/lifecycleManagerConfig](#) **rel**=self
This resource.
- **rel**=target
This resource's target reference to a [weblogic.management.configuration.TargetMBean](#) resource.

POST

Update this [weblogic.management.configuration.LifecycleManagerConfigMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.LifecycleManagerConfigMBean](#) entity.

/management/weblogic/{version}/edit/lifecycleManagerConfig/configuredEndPointCreateForm

This resource manages the create forms for the configuredEndpoints collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.LifecycleManagerEndPointMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the [configuredEndpoints](#) collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.LifecycleManagerEndPointMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/lifecycleManagerConfig/configuredEndPointCreateForm](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/lifecycleManagerConfig/configuredEndpoints](#) **rel=create**
The collection resource for this create form resource.
- [uri=/management/weblogic/{version}/edit/lifecycleManagerConfig](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/lifecycleManagerConfig/configuredEndPointCreateForm](#) **rel=self**
This resource.

/management/weblogic/{version}/edit/lifecycleManagerConfig/configuredEndpoints

This resource manages a collection of [weblogic.management.configuration.LifecycleManagerEndPointMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.LifecycleManagerEndPointMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.LifecycleManagerEndPointMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/lifecycleManagerConfig/configuredEndpoints](#) [rel=canonical](#)
This resource.
- [uri=/management/weblogic/{version}/edit/lifecycleManagerConfig/configuredEndPointCreateForm](#) [rel=create-form](#)
The create form resource for this collection resource.
- [uri=/management/weblogic/{version}/edit/lifecycleManagerConfig](#) [rel=parent](#)
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/lifecycleManagerConfig/configuredEndpoints](#) [rel=self](#)
This resource.

POST

Add a new [weblogic.management.configuration.LifecycleManagerEndPointMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.LifecycleManagerEndPointMBean](#) entity.

/management/weblogic/{version}/edit/lifecycleManagerConfig/configuredEndpoints/{name}

This resource manages a [weblogic.management.configuration.LifecycleManagerEndPointMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.LifecycleManagerEndPointMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.LifecycleManagerEndPointMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.LifecycleManagerEndPointMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/lifecycleManagerConfig/configuredEndpoints/{name}](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/lifecycleManagerConfig/configuredEndpoints](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/lifecycleManagerConfig/configuredEndpoints/{name}](#) **rel=self**
This resource.

POST

POST

Update this [weblogic.management.configuration.LifecycleManagerEndPointMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.LifecycleManagerEndPointMBean](#) entity.

/management/weblogic/{version}/edit/listTags

The resource supports the following methods:

- [POST](#)

POST

List all tags of the specified config bean type. If the type param is empty string, then all tags used in the domain are returned.

Roles

Admin, Deployer, Monitor, Operator

Request Body

Must contain a JSON object with the following fields:

type

type of the MBean (shortened version of the class name less the MBean)

Type: string

Response Body

Contains a JSON object with a array of string return field.

/management/weblogic/{version}/edit/log

This resource manages a [weblogic.management.configuration.LogMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.LogMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.LogMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/log](#) **rel**=canonical
This resource.
- **rel**=domainLogBroadcastFilter
This resource's domainLogBroadcastFilter reference to a [weblogic.management.configuration.LogFilterMBean](#) resource.
- **rel**=logFileFilter
This resource's logFileFilter reference to a [weblogic.management.configuration.LogFilterMBean](#) resource.
- **uri**=[/management/weblogic/{version}/edit](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/log](#) **rel**=self
This resource.
- **rel**=stdoutFilter
This resource's stdoutFilter reference to a [weblogic.management.configuration.LogFilterMBean](#) resource.

POST

Update this [weblogic.management.configuration.LogMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.LogMBean](#) entity.

/management/weblogic/{version}/edit/logFilterCreateForm

This resource manages the create forms for the logFilters collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.LogFilterMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the logFilters collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.LogFilterMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/logFilterCreateForm](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/logFilters](#) **rel=create**
The collection resource for this create form resource.
- [uri=/management/weblogic/{version}/edit](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/logFilterCreateForm](#) **rel=self**
This resource.

/management/weblogic/{version}/edit/logFilters

This resource manages a collection of [weblogic.management.configuration.LogFilterMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.LogFilterMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.LogFilterMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/logFilters](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/logFilterCreateForm](#) **rel**=create-form
The create form resource for this collection resource.
- **uri**=[/management/weblogic/{version}/edit](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/logFilters](#) **rel**=self
This resource.

POST

Add a new [weblogic.management.configuration.LogFilterMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.LogFilterMBean](#) entity.

/management/weblogic/{version}/edit/logFilters/{name}

This resource manages a [weblogic.management.configuration.LogFilterMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

DELETE

Delete this [weblogic.management.configuration.LogFilterMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.LogFilterMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.LogFilterMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/logFilters/{name}](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/logFilters](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/logFilters/{name}](#) **rel**=self
This resource.

POST

Update this [weblogic.management.configuration.LogFilterMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.LogFilterMBean](#) entity.

/management/weblogic/{version}/edit/lookupSystemResource

The resource supports the following methods:

- [POST](#)

POST

Lookup a particular SystemResource in this domain.

Roles

Admin, Deployer

Request Body

Must contain a JSON object with the following fields:

name

name

Type: string

Response Body

Contains a JSON object with a
weblogic.management.configuration.SystemResourceMBean reference return field.

/management/weblogic/{version}/edit/lookupTarget

The resource supports the following methods:

- [POST](#)

POST

Roles

Admin, Deployer, Operator

Request Body

Must contain a JSON object with the following fields:

name

name

Type: string

Response Body

Contains a JSON object with a `weblogic.management.configuration.TargetMBean` reference return field.

/management/weblogic/{version}/edit/machinecreateForm

This resource manages the create forms for the machines collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.MachineMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the machines collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.MachineMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/machineCreateForm](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/machines](#) **rel**=create
The collection resource for this create form resource.
- **uri**=[/management/weblogic/{version}/edit](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/machineCreateForm](#) **rel**=self
This resource.

/management/weblogic/{version}/edit/machines

This resource manages a collection of [weblogic.management.configuration.MachineMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.MachineMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.MachineMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/machines](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/machinecreateForm](#) **rel**=create-form
The create form resource for this collection resource.
- **uri**=[/management/weblogic/{version}/edit](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/machines](#) **rel**=self
This resource.

POST

Add a new [weblogic.management.configuration.MachineMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.MachineMBean](#) entity.

/management/weblogic/{version}/edit/machines/{name}

This resource manages a [weblogic.management.configuration.MachineMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.MachineMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.MachineMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.MachineMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/machines/{name}](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/machines/{name}/nodeManager](#)
rel=nodeManager
This resource's nodeManager singleton resource.
- **uri**=[/management/weblogic/{version}/edit/machines](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/machines/{name}](#) **rel**=self
This resource.

POST

Update this [weblogic.management.configuration.MachineMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.MachineMBean](#) entity.

/management/weblogic/{version}/edit/machines/{name}/nodeManager

This resource manages a [weblogic.management.configuration.NodeManagerMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.NodeManagerMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.NodeManagerMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/machines/{name}/nodeManager](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/machines/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/machines/{name}/nodeManager](#)
rel=self
This resource.

POST

POST

Update this [weblogic.management.configuration.NodeManagerMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.NodeManagerMBean](#) entity.

/management/weblogic/{version}/edit/mailSessioncreateForm

This resource manages the create forms for the mailSessions collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.MailSessionMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the mailSessions collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.MailSessionMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/mailSessionCreateForm](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/mailSessions](#) **rel**=create
The collection resource for this create form resource.
- **uri**=[/management/weblogic/{version}/edit](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/mailSessionCreateForm](#) **rel**=self
This resource.

/management/weblogic/{version}/edit/mailSessions

This resource manages a collection of [weblogic.management.configuration.MailSessionMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.MailSessionMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.MailSessionMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/mailSessions](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/mailSessionCreateForm](#)
rel=create-form
The create form resource for this collection resource.
- **uri**=[/management/weblogic/{version}/edit](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/mailSessions](#) **rel**=self
This resource.

POST

Add a new [weblogic.management.configuration.MailSessionMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.MailSessionMBean](#) entity.

/management/weblogic/{version}/edit/mailSessions/{name}

This resource manages a [weblogic.management.configuration.MailSessionMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.MailSessionMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.MailSessionMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.MailSessionMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/mailSessions/{name}](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/mailSessions](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/mailSessions/{name}](#) **rel**=self
This resource.

POST

Update this [weblogic.management.configuration.MailSessionMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.MailSessionMBean](#) entity.

/management/weblogic/{version}/edit/managedExecutorServiceCreateForm

This resource manages the create forms for the managedExecutorServices collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.ManagedExecutorServiceMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the `managedExecutorServices` collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ManagedExecutorServiceMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/managedExecutorServiceCreateForm](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/managedExecutorServices](#)
rel=create
The collection resource for this create form resource.
- **uri**=[/management/weblogic/{version}/edit](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/managedExecutorServiceCreateForm](#)
rel=self
This resource.

/management/weblogic/{version}/edit/managedExecutorServices

This resource manages a collection of [weblogic.management.configuration.ManagedExecutorServiceMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.ManagedExecutorServiceMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.ManagedExecutorServiceMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/managedExecutorServices](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/managedExecutorServiceCreateForm](#)
rel=create-form
The create form resource for this collection resource.
- **uri**=[/management/weblogic/{version}/edit](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/managedExecutorServices](#) **rel**=self
This resource.

POST

Add a new [weblogic.management.configuration.ManagedExecutorServiceMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.ManagedExecutorServiceMBean](#) entity.

/management/weblogic/{version}/edit/managedExecutorServices/{name}

This resource manages a [weblogic.management.configuration.ManagedExecutorServiceMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.ManagedExecutorServiceMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.ManagedExecutorServiceMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ManagedExecutorServiceMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/managedExecutorServices/{name}](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/managedExecutorServices](#)
rel=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/managedExecutorServices/{name}](#)
rel=self
This resource.

POST

Update this [weblogic.management.configuration.ManagedExecutorServiceMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.ManagedExecutorServiceMBean](#) entity.

/management/weblogic/{version}/edit/managedExecutorServiceTemplateCreateForm

This resource manages the create forms for the managedExecutorServiceTemplates collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.ManagedExecutorServiceTemplateMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the `managedExecutorServiceTemplates` collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ManagedExecutorServiceTemplateMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/managedExecutorServiceTemplateCreateForm](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/managedExecutorServiceTemplates](#) **rel**=create
The collection resource for this create form resource.
- **uri**=[/management/weblogic/{version}/edit](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/managedExecutorServiceTemplateCreateForm](#) **rel**=self
This resource.

/management/weblogic/{version}/edit/managedExecutorServiceTemplates

This resource manages a collection of [weblogic.management.configuration.ManagedExecutorServiceTemplateMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.ManagedExecutorServiceTemplateMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.ManagedExecutorServiceTemplateMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/managedExecutorServiceTemplates](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/managedExecutorServiceTemplateCreateForm](#) **rel**=create-form
The create form resource for this collection resource.
- **uri**=[/management/weblogic/{version}/edit](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/managedExecutorServiceTemplates](#)
rel=self
This resource.

POST

Add a new [weblogic.management.configuration.ManagedExecutorServiceTemplateMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.ManagedExecutorServiceTemplateMBean](#) entity.

/management/weblogic/{version}/edit/managedExecutorServiceTemplates/{name}

This resource manages a [weblogic.management.configuration.ManagedExecutorServiceTemplateMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this

[weblogic.management.configuration.ManagedExecutorServiceTemplateMBean](#)
instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.ManagedExecutorServiceTemplateMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ManagedExecutorServiceTemplateMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/managedExecutorServiceTemplates/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/managedExecutorServiceTemplates](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/managedExecutorServiceTemplates/{name}](#) **rel**=self

This resource.

POST

Update this [weblogic.management.configuration.ManagedExecutorServiceTemplateMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.ManagedExecutorServiceTemplateMBean](#) entity.

/management/weblogic/{version}/edit/managedScheduledExecutorServiceCreateForm

This resource manages the create forms for the managedScheduledExecutorServices collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.ManagedScheduledExecutorServiceMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the managedScheduledExecutorServices collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ManagedScheduledExecutorServiceMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/managedScheduledExecutorServiceCreateForm](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/managedScheduledExecutorServices](#) **rel=create**
The collection resource for this create form resource.
- [uri=/management/weblogic/{version}/edit](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/managedScheduledExecutorServiceCreateForm](#) **rel=self**
This resource.

/management/weblogic/{version}/edit/managedScheduledExecutorServices

This resource manages a collection of [weblogic.management.configuration.ManagedScheduledExecutorServiceMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.ManagedScheduledExecutorServiceMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.ManagedScheduledExecutorServiceMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/managedScheduledExecutorServices](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/managedScheduledExecutorServiceCreateForm](#) **rel**=create-form
The create form resource for this collection resource.
- **uri**=[/management/weblogic/{version}/edit](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/managedScheduledExecutorServices](#) **rel**=self
This resource.

POST

Add a new [weblogic.management.configuration.ManagedScheduledExecutorServiceMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.ManagedScheduledExecutorServiceMBean](#) entity.

/management/weblogic/{version}/edit/managedScheduledExecutorServices/{name}

This resource manages a [weblogic.management.configuration.ManagedScheduledExecutorServiceMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.ManagedScheduledExecutorServiceMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.ManagedScheduledExecutorServiceMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ManagedScheduledExecutorServiceMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/managedScheduledExecutorServices/{name}](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/managedScheduledExecutorServices/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/managedScheduledExecutorServices/{name}](#) **rel**=self
This resource.

POST

Update this [weblogic.management.configuration.ManagedScheduledExecutorServiceMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.ManagedScheduledExecutorServiceMBean](#) entity.

/management/weblogic/{version}/edit/managedScheduledExecutorServiceTemplateCreateForm

This resource manages the create forms for the managedScheduledExecutorServiceTemplates collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.ManagedScheduledExecutorServiceTemplateMBEAN](#) entity populated with default values that can be customized then posted (using the POST method) to the `managedScheduledExecutorServiceTemplates` collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ManagedScheduledExecutorServiceTemplateMBEAN](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/managedScheduledExecutorServiceTemplateCreateForm](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/managedScheduledExecutorServiceTemplates](#) **rel=create**
The collection resource for this create form resource.
- [uri=/management/weblogic/{version}/edit](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/managedScheduledExecutorServiceTemplateCreateForm](#) **rel=self**
This resource.

/management/weblogic/{version}/edit/managedScheduledExecutorServiceTemplates

This resource manages a collection of [weblogic.management.configuration.ManagedScheduledExecutorServiceTemplateMB](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.ManagedScheduledExecutorServiceTemplateMBEAN](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.ManagedScheduledExecutorServiceTemplateMBEAN](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/managedScheduledExecutorServiceTemplates](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/managedScheduledExecutorServiceTemplateCreateForm](#) **rel**=create-form
The create form resource for this collection resource.
- **uri**=[/management/weblogic/{version}/edit](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/managedScheduledExecutorServiceTemplates](#) **rel**=self
This resource.

POST

Add a new

[weblogic.management.configuration.ManagedScheduledExecutorServiceTemplateMB](#)
[ean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a

[weblogic.management.configuration.ManagedScheduledExecutorServiceTemplateMB](#)
[ean](#) entity.

/management/weblogic/{version}/edit/managedScheduledExecutorServiceTemplates/{name}

This resource manages a [weblogic.management.configuration.ManagedScheduledExecutorServiceTemplateMBEAN](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this

[weblogic.management.configuration.ManagedScheduledExecutorServiceTemplateMB](#)
ean instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.ManagedScheduledExecutorServiceTemplateMBEAN](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ManagedScheduledExecutorServiceTemplateMBEAN](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/managedScheduledExecutorServiceTemplates/{name}](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/managedScheduledExecutorServiceTemplates](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/managedScheduledExecutorServiceTemplates/{name}](#) **rel**=self
This resource.

POST

Update this [weblogic.management.configuration.ManagedScheduledExecutorServiceTemplateMB](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.ManagedScheduledExecutorServiceTemplateMB](#) entity.

/management/weblogic/{version}/edit/managedThreadFactories

This resource manages a collection of [weblogic.management.configuration.ManagedThreadFactoryMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.ManagedThreadFactoryMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.ManagedThreadFactoryMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/managedThreadFactories](#)
[rel=canonical](#)
This resource.
- [uri=/management/weblogic/{version}/edit/managedThreadFactoryCreateForm](#)
[rel=create-form](#)
The create form resource for this collection resource.
- [uri=/management/weblogic/{version}/edit](#) [rel=parent](#)
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/managedThreadFactories](#) [rel=self](#)
This resource.

POST

Add a new [weblogic.management.configuration.ManagedThreadFactoryMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.ManagedThreadFactoryMBean](#) entity.

/management/weblogic/{version}/edit/managedThreadFactories/{name}

This resource manages a [weblogic.management.configuration.ManagedThreadFactoryMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.ManagedThreadFactoryMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.ManagedThreadFactoryMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ManagedThreadFactoryMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/managedThreadFactories/{name}](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/managedThreadFactories](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/managedThreadFactories/{name}](#)
rel=self
This resource.

POST

Update this [weblogic.management.configuration.ManagedThreadFactoryMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.ManagedThreadFactoryMBean](#) entity.

/management/weblogic/{version}/edit/managedThreadFactoryCreateForm

This resource manages the create forms for the managedThreadFactories collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.ManagedThreadFactoryMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the `managedThreadFactories` collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ManagedThreadFactoryMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/managedThreadFactoryCreateForm](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/managedThreadFactories](#) **rel**=create
The collection resource for this create form resource.
- **uri**=[/management/weblogic/{version}/edit](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/managedThreadFactoryCreateForm](#)
rel=self
This resource.

/management/weblogic/{version}/edit/managedThreadFactoryTemplateCreateForm

This resource manages the create forms for the managedThreadFactoryTemplates collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.ManagedThreadFactoryTemplateMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the managedThreadFactoryTemplates collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ManagedThreadFactoryTemplateMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/managedThreadFactoryTemplateCreateForm rel=canonical](#)
This resource.
- [uri=/management/weblogic/{version}/edit/managedThreadFactoryTemplates rel=create](#)
The collection resource for this create form resource.
- [uri=/management/weblogic/{version}/edit rel=parent](#)
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/managedThreadFactoryTemplateCreateForm rel=self](#)
This resource.

/management/weblogic/{version}/edit/managedThreadFactoryTemplates

This resource manages a collection of [weblogic.management.configuration.ManagedThreadFactoryTemplateMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.ManagedThreadFactoryTemplateMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.ManagedThreadFactoryTemplateMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/managedThreadFactoryTemplates](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/managedThreadFactoryTemplateCreateForm](#) **rel**=create-form
The create form resource for this collection resource.
- **uri**=[/management/weblogic/{version}/edit](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/managedThreadFactoryTemplates](#)
rel=self
This resource.

POST

Add a new [weblogic.management.configuration.ManagedThreadFactoryTemplateMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.ManagedThreadFactoryTemplateMBean](#) entity.

/management/weblogic/{version}/edit/managedThreadFactoryTemplates/{name}

This resource manages a [weblogic.management.configuration.ManagedThreadFactoryTemplateMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this

[weblogic.management.configuration.ManagedThreadFactoryTemplateMBean](#)
instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.ManagedThreadFactoryTemplateMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ManagedThreadFactoryTemplateMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/managedThreadFactoryTemplates/{name}](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/managedThreadFactoryTemplates](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/managedThreadFactoryTemplates/{name}](#) **rel**=self
This resource.

POST

Update this [weblogic.management.configuration.ManagedThreadFactoryTemplateMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.ManagedThreadFactoryTemplateMBean](#) entity.

/management/weblogic/{version}/edit/messagingBridgeCreateForm

This resource manages the create forms for the messagingBridges collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.MessagingBridgeMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the messagingBridges collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.MessagingBridgeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/messagingBridgeCreateForm](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/messagingBridges](#) **rel**=create
The collection resource for this create form resource.
- **uri**=[/management/weblogic/{version}/edit](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/messagingBridgeCreateForm](#)
rel=self
This resource.

/management/weblogic/{version}/edit/messagingBridges

This resource manages a collection of [weblogic.management.configuration.MessagingBridgeMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.MessagingBridgeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.MessagingBridgeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/messagingBridges](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/messagingBridgeCreateForm](#)
rel=create-form
The create form resource for this collection resource.
- **uri**=[/management/weblogic/{version}/edit](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/messagingBridges](#) **rel**=self
This resource.

POST

Add a new [weblogic.management.configuration.MessagingBridgeMBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.MessagingBridgeMBean](#) entity.

/management/weblogic/{version}/edit/messagingBridges/{name}

This resource manages a [weblogic.management.configuration.MessagingBridgeMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.MessagingBridgeMBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.management.configuration.MessagingBridgeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.MessagingBridgeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/messagingBridges/{name}](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/messagingBridges](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/messagingBridges/{name}](#) **rel**=self
This resource.
- **rel**=sourceDestination
This resource's sourceDestination reference to a [weblogic.management.configuration.BridgeDestinationCommonMBean](#) resource.
- **rel**=targetDestination
This resource's targetDestination reference to a [weblogic.management.configuration.BridgeDestinationCommonMBean](#) resource.

POST

Update this [weblogic.management.configuration.MessagingBridgeMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.MessagingBridgeMBean](#) entity.

/management/weblogic/{version}/edit/migratableTargetCreateForm

This resource manages the create forms for the migratableTargets collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.MigratableTargetMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the `migratableTargets` collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.MigratableTargetMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/migratableTargetCreateForm](#)
rel=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/migratableTargets](#) **rel**=create

The collection resource for this create form resource.

- **uri**=[/management/weblogic/{version}/edit](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/migratableTargetCreateForm](#)
rel=self

This resource.

/management/weblogic/{version}/edit/migratableTargets

This resource manages a collection of [weblogic.management.configuration.MigratableTargetMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.MigratableTargetMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.MigratableTargetMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/migratableTargets](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/migratableTargetCreateForm](#)
rel=create-form
The create form resource for this collection resource.
- **uri**=[/management/weblogic/{version}/edit](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/migratableTargets](#) **rel**=self
This resource.

POST

Add a new [weblogic.management.configuration.MigratableTargetMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.MigratableTargetMBean](#) entity.

/management/weblogic/{version}/edit/migratableTargets/{name}

This resource manages a [weblogic.management.configuration.MigratableTargetMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.MigratableTargetMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.MigratableTargetMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.MigratableTargetMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/migratableTargets/{name}](#) **rel**=canonical
This resource.
- **rel**=cluster
This resource's cluster reference to a [weblogic.management.configuration.ClusterMBean](#) resource.
- **rel**=hostingServer
This resource's hostingServer reference to a [weblogic.management.configuration.ServerMBean](#) resource.
- **uri**=[/management/weblogic/{version}/edit/migratableTargets](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/migratableTargets/{name}](#) **rel**=self
This resource.
- **rel**=userPreferredServer
This resource's userPreferredServer reference to a [weblogic.management.configuration.ServerMBean](#) resource.

POST

Update this [weblogic.management.configuration.MigratableTargetMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.MigratableTargetMBean](#) entity.

/management/weblogic/{version}/edit/optionalFeatureDeployment

This resource manages a [weblogic.management.configuration.OptionalFeatureDeploymentMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.OptionalFeatureDeploymentMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.OptionalFeatureDeploymentMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/optionalFeatureDeployment](#)
[rel=canonical](#)
This resource.
- [uri=/management/weblogic/{version}/edit/optionalFeatureDeployment/optionalFeatureCreateForm](#) [rel=optionalFeatureCreateForm](#)
The create form resource for this resource's optionalFeatures collection resource.
- [uri=/management/weblogic/{version}/edit/optionalFeatureDeployment/optionalFeatures](#) [rel=optionalFeatures](#)
This resource's optionalFeatures collection resource.
- [uri=/management/weblogic/{version}/edit](#) [rel=parent](#)
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/optionalFeatureDeployment](#) [rel=self](#)
This resource.

POST

POST

Update this [weblogic.management.configuration.OptionalFeatureDeploymentMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.OptionalFeatureDeploymentMBean](#) entity.

/management/weblogic/{version}/edit/optionalFeatureDeployment/optionalFeatureCreateForm

This resource manages the create forms for the optionalFeatures collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.OptionalFeatureMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the optionalFeatures collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.OptionalFeatureMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/optionalFeatureDeployment/optionalFeatureCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/optionalFeatureDeployment/optionalFeatures](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/optionalFeatureDeployment](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/optionalFeatureDeployment/optionalFeatureCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/optionalFeatureDeployment/optionalFeatures

This resource manages a collection of [weblogic.management.configuration.OptionalFeatureMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.OptionalFeatureMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.OptionalFeatureMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/optionalFeatureDeployment/optionalFeatures](#) [rel=canonical](#)

This resource.

- [uri=/management/weblogic/{version}/edit/optionalFeatureDeployment/optionalFeatureCreateForm](#) [rel=create-form](#)

The create form resource for this collection resource.

- [uri=/management/weblogic/{version}/edit/optionalFeatureDeployment](#) [rel=parent](#)

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/optionalFeatureDeployment/optionalFeatures](#) [rel=self](#)

This resource.

POST

Add a new [weblogic.management.configuration.OptionalFeatureMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.OptionalFeatureMBean](#) entity.

/management/weblogic/{version}/edit/optionalFeatureDeployment/optionalFeatures/{name}

This resource manages a [weblogic.management.configuration.OptionalFeatureMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.OptionalFeatureMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.OptionalFeatureMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.OptionalFeatureMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/optionalFeatureDeployment/optionalFeatures/{name}](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/optionalFeatureDeployment/optionalFeatures](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/optionalFeatureDeployment/optionalFeatures/{name}](#) **rel=self**

This resource.

POST

Update this [weblogic.management.configuration.OptionalFeatureMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.OptionalFeatureMBean](#) entity.

/management/weblogic/{version}/edit/osgiFrameworkCreateForm

This resource manages the create forms for the osgiFrameworks collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.OsgiFrameworkMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the `osgiFrameworks` collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.OsgiFrameworkMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/osgiFrameworkCreateForm](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/osgiFrameworks](#) **rel**=create
The collection resource for this create form resource.
- **uri**=[/management/weblogic/{version}/edit](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/osgiFrameworkCreateForm](#) **rel**=self
This resource.

/management/weblogic/{version}/edit/osgiFrameworks

This resource manages a collection of [weblogic.management.configuration.OsgiFrameworkMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.OsgiFrameworkMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.OsgiFrameworkMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/osgiFrameworks](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/osgiFrameworkCreateForm](#)
rel=create-form
The create form resource for this collection resource.
- **uri**=[/management/weblogic/{version}/edit](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/osgiFrameworks](#) **rel**=self
This resource.

POST

Add a new [weblogic.management.configuration.OsgiFrameworkMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.OsgiFrameworkMBean](#) entity.

/management/weblogic/{version}/edit/osgiFrameworks/{name}

This resource manages a [weblogic.management.configuration.OsgiFrameworkMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.OsgiFrameworkMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.OsgiFrameworkMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.OsgiFrameworkMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/osgiFrameworks/{name}](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/osgiFrameworks](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/osgiFrameworks/{name}](#) **rel**=self
This resource.

POST

POST

Update this [weblogic.management.configuration.OsgiFrameworkMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.OsgiFrameworkMBean](#) entity.

/management/weblogic/{version}/edit/partitioncreateForm

This resource manages the create forms for the partitions collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.PartitionMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the partitions collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.PartitionMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitionCreateForm](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/partitions](#) **rel**=create
The collection resource for this create form resource.
- **uri**=[/management/weblogic/{version}/edit](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/partitionCreateForm](#) **rel**=self
This resource.

/management/weblogic/{version}/edit/partitions

This resource manages a collection of [weblogic.management.configuration.PartitionMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.PartitionMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.PartitionMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/partitionCreateForm](#)
rel=create-form
The create form resource for this collection resource.
- **uri**=[/management/weblogic/{version}/edit](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/partitions](#) **rel**=self
This resource.

POST

Add a new [weblogic.management.configuration.PartitionMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.PartitionMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}

This resource manages a [weblogic.management.configuration.PartitionMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.PartitionMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.PartitionMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.PartitionMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/JDBCSystemResourceOverrideCreateForm](#) [rel=JDBCSystemResourceOverrideCreateForm](#)
The create form resource for this resource's JDBCSystemResourceOverrides collection resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/JDBCSystemResourceOverrides](#) [rel=JDBCSystemResourceOverrides](#)
This resource's JDBCSystemResourceOverrides collection resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/JMSSystemResourceOverrideCreateForm](#) [rel=JMSSystemResourceOverrideCreateForm](#)
The create form resource for this resource's JMSSystemResourceOverrides collection resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/JMSSystemResourceOverrides](#) [rel=JMSSystemResourceOverrides](#)
This resource's JMSSystemResourceOverrides collection resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/JTAPartition](#) [rel=JTAPartition](#)
This resource's JTAPartition singleton resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/findEffectiveServerNames](#) [rel=action](#) [title=findEffectiveServerNames](#)
This resource's findEffectiveServerNames action resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/lookupAvailableTarget](#) [rel=action](#) [title=lookupAvailableTarget](#)
This resource's lookupAvailableTarget action resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/adminVirtualTarget](#) [rel=adminVirtualTarget](#)
This resource's adminVirtualTarget singleton resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}](#) [rel=canonical](#)
This resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/coherencePartitionCacheConfigCreateForm](#) [rel=coherencePartitionCacheConfigCreateForm](#)
The create form resource for this resource's coherencePartitionCacheConfigs collection resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/coherencePartitionCacheConfigs **rel**=coherencePartitionCacheConfigs
This resource's coherencePartitionCacheConfigs collection resource.
- **uri**=/management/weblogic/{version}/edit/partitions/{name}/configurationProperties **rel**=configurationProperties
This resource's configurationProperties collection resource.
- **uri**=/management/weblogic/{version}/edit/partitions/{name}/configurationPropertyCreateForm **rel**=configurationPropertyCreateForm
The create form resource for this resource's configurationProperties collection resource.
- **rel**=dataSourceForJobScheduler
This resource's dataSourceForJobScheduler reference to a weblogic.management.configuration.JDBCSystemResourceMBean resource.
- **uri**=/management/weblogic/{version}/edit/partitions/{name}/dataSourcePartition **rel**=dataSourcePartition
This resource's dataSourcePartition singleton resource.
- **uri**=/management/weblogic/{version}/edit/partitions/{name}/foreignJNDIProviderOverrideCreateForm **rel**=foreignJNDIProviderOverrideCreateForm
The create form resource for this resource's foreignJNDIProviderOverrides collection resource.
- **uri**=/management/weblogic/{version}/edit/partitions/{name}/foreignJNDIProviderOverrides **rel**=foreignJNDIProviderOverrides
This resource's foreignJNDIProviderOverrides collection resource.
- **uri**=/management/weblogic/{version}/edit/partitions/{name}/internalAppDeployments **rel**=internalAppDeployments
This resource's internalAppDeployments collection resource.
- **uri**=/management/weblogic/{version}/edit/partitions/{name}/internalLibraries **rel**=internalLibraries
This resource's internalLibraries collection resource.
- **uri**=/management/weblogic/{version}/edit/partitions/{name}/mailSessionOverrideCreateForm **rel**=mailSessionOverrideCreateForm
The create form resource for this resource's mailSessionOverrides collection resource.
- **uri**=/management/weblogic/{version}/edit/partitions/{name}/mailSessionOverrides **rel**=mailSessionOverrides
This resource's mailSessionOverrides collection resource.
- **uri**=/management/weblogic/{version}/edit/partitions/{name}/managedExecutorServiceTemplateCreateForm **rel**=managedExecutorServiceTemplateCreateForm
The create form resource for this resource's managedExecutorServiceTemplates collection resource.
- **uri**=/management/weblogic/{version}/edit/partitions/{name}/managedExecutorServiceTemplates **rel**=managedExecutorServiceTemplates
This resource's managedExecutorServiceTemplates collection resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/managedScheduledExecutorServiceTemplateCreateForm
rel=managedScheduledExecutorServiceTemplateCreateForm
The create form resource for this resource's managedScheduledExecutorServiceTemplates collection resource.
- **uri**=/management/weblogic/{version}/edit/partitions/{name}/managedScheduledExecutorServiceTemplates **rel**=managedScheduledExecutorServiceTemplates
This resource's managedScheduledExecutorServiceTemplates collection resource.
- **uri**=/management/weblogic/{version}/edit/partitions/{name}/managedThreadFactoryTemplateCreateForm **rel**=managedThreadFactoryTemplateCreateForm
The create form resource for this resource's managedThreadFactoryTemplates collection resource.
- **uri**=/management/weblogic/{version}/edit/partitions/{name}/managedThreadFactoryTemplates **rel**=managedThreadFactoryTemplates
This resource's managedThreadFactoryTemplates collection resource.
- **uri**=/management/weblogic/{version}/edit/partitions **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/edit/partitions/{name}/partitionLog **rel**=partitionLog
This resource's partitionLog singleton resource.
- **uri**=/management/weblogic/{version}/edit/partitions/{name}/partitionWorkManager **rel**=partitionWorkManager
This resource's partitionWorkManager singleton resource.
- **uri**=/management/weblogic/{version}/edit/partitions/{name}/partitionWorkManagerCreateForm **rel**=partitionWorkManagerCreateForm
The create form resource for this resource's partitionWorkManager optional singleton resource.
- **rel**=partitionWorkManagerRef
This resource's partitionWorkManagerRef reference to a weblogic.management.configuration.PartitionWorkManagerMBean resource.
- **rel**=realm
This resource's realm reference to a weblogic.management.security.RealmMBean resource.
- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroupCreateForm **rel**=resourceGroupCreateForm
The create form resource for this resource's resourceGroups collection resource.
- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups **rel**=resourceGroups
This resource's resourceGroups collection resource.
- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceManager **rel**=resourceManager
This resource's resourceManager singleton resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceManagerCreateForm **rel**=resourceManagerCreateForm
The create form resource for this resource's resourceManager optional singleton resource.
- **rel**=resourceManagerRef
This resource's resourceManagerRef reference to a weblogic.management.configuration.ResourceManagerMBean resource.
- **uri**=/management/weblogic/{version}/edit/partitions/{name} **rel**=self
This resource.
- **uri**=/management/weblogic/{version}/edit/partitions/{name}/selfTuning **rel**=selfTuning
This resource's selfTuning singleton resource.
- **uri**=/management/weblogic/{version}/edit/partitions/{name}/systemFileSystem **rel**=systemFileSystem
This resource's systemFileSystem singleton resource.
- **uri**=/management/weblogic/{version}/edit/partitions/{name}/userFileSystem **rel**=userFileSystem
This resource's userFileSystem singleton resource.
- **uri**=/management/weblogic/{version}/edit/partitions/{name}/webService **rel**=webService
This resource's webService singleton resource.

POST

Update this [weblogic.management.configuration.PartitionMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.PartitionMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/adminVirtualTarget

This resource manages a [weblogic.management.configuration.AdminVirtualTargetMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.AdminVirtualTargetMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.AdminVirtualTargetMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/adminVirtualTarget](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/adminVirtualTarget](#)
rel=self
This resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/adminVirtualTarget/webServer](#) **rel**=webServer
This resource's webServer singleton resource.

POST

Update this [weblogic.management.configuration.AdminVirtualTargetMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.AdminVirtualTargetMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/adminVirtualTarget/webServer

This resource manages a [weblogic.management.configuration.WebServerMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.WebServerMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.WebServerMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/adminVirtualTarget/webServer rel=canonical](#)
This resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/adminVirtualTarget rel=parent](#)
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/adminVirtualTarget/webServer rel=self](#)
This resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/adminVirtualTarget/webServer/webServerLog rel=webServerLog](#)
This resource's webServerLog singleton resource.

POST

Update this [weblogic.management.configuration.WebServerMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.WebServerMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/adminVirtualTarget/webServer/webServerLog

This resource manages a [weblogic.management.configuration.WebServerLogMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.WebServerLogMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.WebServerLogMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/adminVirtualTarget/webServer/webServerLog](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/adminVirtualTarget/webServer](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/adminVirtualTarget/webServer/webServerLog](#) **rel**=self

This resource.

POST

Update this [weblogic.management.configuration.WebServerLogMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.WebServerLogMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/coherencePartitionCacheConfigCreateForm

This resource manages the create forms for the coherencePartitionCacheConfigs collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.CoherencePartitionCacheConfigMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the coherencePartitionCacheConfigs collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.CoherencePartitionCacheConfigMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/coherencePartitionCacheConfigCreateForm rel=canonical](#)
This resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/coherencePartitionCacheConfigs rel=create](#)
The collection resource for this create form resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name} rel=parent](#)
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/coherencePartitionCacheConfigCreateForm rel=self](#)
This resource.

/management/weblogic/{version}/edit/partitions/{name}/coherencePartitionCacheConfigs

This resource manages a collection of [weblogic.management.configuration.CoherencePartitionCacheConfigMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.CoherencePartitionCacheConfigMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.CoherencePartitionCacheConfigMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/coherencePartitionCacheConfigs](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/coherencePartitionCacheConfigCreateForm](#) **rel=create-form**
The create form resource for this collection resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/coherencePartitionCacheConfigs](#) **rel=self**
This resource.

POST

POST

Add a new [weblogic.management.configuration.CoherencePartitionCacheConfigMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.CoherencePartitionCacheConfigMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/coherencePartitionCacheConfigs/{name}

This resource manages a [weblogic.management.configuration.CoherencePartitionCacheConfigMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

DELETE

Delete this [weblogic.management.configuration.CoherencePartitionCacheConfigMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.CoherencePartitionCacheConfigMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.CoherencePartitionCacheConfigMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/coherencePartitionCacheConfigs/{name}](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/coherencePartitionCacheConfigs/{name}/coherencePartitionCacheProperties](#) **rel=coherencePartitionCacheProperties**

This resource's coherencePartitionCacheProperties collection resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/coherencePartitionCacheConfigs/{name}/coherencePartitionCachePropertyCreateForm](#) **rel=coherencePartitionCachePropertyCreateForm**

The create form resource for this resource's coherencePartitionCacheProperties collection resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/coherencePartitionCacheConfigs](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/coherencePartitionCacheConfigs/{name}](#) **rel=self**

This resource.

POST

POST

Update this [weblogic.management.configuration.CoherencePartitionCacheConfigMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.CoherencePartitionCacheConfigMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/coherencePartitionCacheConfigs/{name}/coherencePartitionCacheProperties

This resource manages a collection of [weblogic.management.configuration.CoherencePartitionCachePropertyMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.CoherencePartitionCachePropertyMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.CoherencePartitionCachePropertyMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/coherencePartitionCacheConfigs/{name}/coherencePartitionCacheProperties **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/coherencePartitionCacheConfigs/{name}/coherencePartitionCachePropertyCreateForm **rel**=create-form

The create form resource for this collection resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/coherencePartitionCacheConfigs/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/coherencePartitionCacheConfigs/{name}/coherencePartitionCacheProperties **rel**=self

This resource.

POST

Add a new [weblogic.management.configuration.CoherencePartitionCachePropertyMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.CoherencePartitionCachePropertyMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/coherencePartitionCacheConfigs/{name}/coherencePartitionCacheProperties/{name}

This resource manages a [weblogic.management.configuration.CoherencePartitionCachePropertyMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this

[weblogic.management.configuration.CoherencePartitionCachePropertyMBean](#)
instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.CoherencePartitionCachePropertyMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.CoherencePartitionCachePropertyMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/coherencePartitionCacheConfigs/{name}/coherencePartitionCacheProperties/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/coherencePartitionCacheConfigs/{name}/coherencePartitionCacheProperties](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/coherencePartitionCacheConfigs/{name}/coherencePartitionCacheProperties/{name}](#) **rel**=self

This resource.

POST

Update this [weblogic.management.configuration.CoherencePartitionCachePropertyMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.CoherencePartitionCachePropertyMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/coherencePartitionCacheConfigs/{name}/coherencePartitionCachePropertyCreateForm

This resource manages the create forms for the coherencePartitionCacheProperties collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.CoherencePartitionCachePropertyMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the coherencePartitionCacheProperties collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.CoherencePartitionCachePropertyMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/coherencePartitionCacheConfigs/{name}/coherencePartitionCachePropertyCreateForm](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/coherencePartitionCacheConfigs/{name}/coherencePartitionCacheProperties](#) **rel=create**
The collection resource for this create form resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/coherencePartitionCacheConfigs/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/coherencePartitionCacheConfigs/{name}/coherencePartitionCachePropertyCreateForm](#) **rel=self**
This resource.

/management/weblogic/{version}/edit/partitions/{name}/configurationProperties

This resource manages a collection of [weblogic.management.configuration.ConfigurationPropertyMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.ConfigurationPropertyMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.ConfigurationPropertyMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/configurationProperties](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/configurationPropertyCreateForm](#) **rel=create-form**
The create form resource for this collection resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/configurationProperties](#) **rel=self**
This resource.

POST

Add a new [weblogic.management.configuration.ConfigurationPropertyMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.ConfigurationPropertyMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/configurationProperties/{name}

This resource manages a [weblogic.management.configuration.ConfigurationPropertyMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.ConfigurationPropertyMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.ConfigurationPropertyMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ConfigurationPropertyMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/configurationProperties/{name} rel=canonical](#)
This resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/configurationProperties rel=parent](#)
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/configurationProperties/{name} rel=self](#)
This resource.

POST

Update this [weblogic.management.configuration.ConfigurationPropertyMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.ConfigurationPropertyMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/configurationPropertyCreateForm

This resource manages the create forms for the configurationProperties collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.ConfigurationPropertyMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the configurationProperties collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ConfigurationPropertyMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/configurationPropertyCreateForm](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/configurationProperties](#) **rel=create**
The collection resource for this create form resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/configurationPropertyCreateForm](#) **rel=self**
This resource.

/management/weblogic/{version}/edit/partitions/{name}/dataSourcePartition

This resource manages a [weblogic.management.configuration.DataSourcePartitionMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.DataSourcePartitionMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.DataSourcePartitionMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/dataSourcePartition](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/dataSourcePartition](#)
rel=self
This resource.

POST

Update this [weblogic.management.configuration.DataSourcePartitionMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.DataSourcePartitionMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/findEffectiveServerNames

The resource supports the following methods:

- [POST](#)

POST

Returns the names of servers for the partition's effective targets, with no duplicates.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a JSON object with a array of string return field.

/management/weblogic/{version}/edit/partitions/{name}/foreignJNDIProviderOverrideCreateForm

This resource manages the create forms for the foreignJNDIProviderOverrides collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.ForeignJNDIPProviderOverrideMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the [foreignJNDIPProviderOverrides](#) collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ForeignJNDIPProviderOverrideMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/foreignJNDIPProviderOverrideCreateForm](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/foreignJNDIPProviderOverrides](#) **rel=create**
The collection resource for this create form resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/foreignJNDIPProviderOverrideCreateForm](#) **rel=self**
This resource.

/management/weblogic/{version}/edit/partitions/{name}/foreignJNDIProviderOverrides

This resource manages a collection of [weblogic.management.configuration.ForeignJNDIProviderOverrideMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.ForeignJNDIProviderOverrideMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.ForeignJNDIProviderOverrideMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/foreignJNDIProviderOverrides](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/foreignJNDIProviderOverrideCreateForm](#) **rel=create-form**
The create form resource for this collection resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/foreignJNDIProviderOverrides](#) **rel=self**
This resource.

POST

POST

Add a new [weblogic.management.configuration.ForeignJNDIProviderOverrideMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.ForeignJNDIProviderOverrideMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/foreignJNDIPProviderOverrides/{name}

This resource manages a [weblogic.management.configuration.ForeignJNDIPProviderOverrideMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.ForeignJNDIProviderOverrideMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.ForeignJNDIPProviderOverrideMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ForeignJNDIPProviderOverrideMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/foreignJNDIPProviderOverrides/{name}](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/foreignJNDIPProviderOverrides/{name}/foreignJNDILinkCreateForm](#) **rel=foreignJNDILinkCreateForm**

The create form resource for this resource's foreignJNDILinks collection resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/foreignJNDIPProviderOverrides/{name}/foreignJNDILinks](#) **rel=foreignJNDILinks**

This resource's foreignJNDILinks collection resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/foreignJNDIPProviderOverrides](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/foreignJNDIPProviderOverrides/{name}](#) **rel=self**

This resource.

POST

POST

Update this [weblogic.management.configuration.ForeignJNDIProviderOverrideMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.ForeignJNDIProviderOverrideMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/foreignJNDIProviderO verrides/{name}/foreignJNDILinkCreateForm

This resource manages the create forms for the foreignJNDILinks collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.ForeignJNDILinkOverrideMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the [foreignJNDILinks](#) collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ForeignJNDILinkOverrideMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/foreignJNDIProvide](#)
[rOverrides/{name}/foreignJNDILinkCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/foreignJNDIProvide](#)
[rOverrides/{name}/foreignJNDILinks](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/foreignJNDIProvide](#)
[rOverrides/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/foreignJNDIProvide](#)
[rOverrides/{name}/foreignJNDILinkCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/partitions/{name}/foreignJNDIProviderOverrides/{name}/foreignJNDILinks

This resource manages a collection of [weblogic.management.configuration.ForeignJNDILinkOverrideMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.ForeignJNDILinkOverrideMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.ForeignJNDILinkOverrideMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/foreignJNDIProviderOverrides/{name}/foreignJNDILinks](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/foreignJNDIProviderOverrides/{name}/foreignJNDILinkCreateForm](#) **rel=create-form**

The create form resource for this collection resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/foreignJNDIProviderOverrides/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/foreignJNDIProviderOverrides/{name}/foreignJNDILinks](#) **rel=self**

This resource.

POST

Add a new [weblogic.management.configuration.ForeignJNDILinkOverrideMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.ForeignJNDILinkOverrideMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/foreignJNDIProviderOverrides/{name}/foreignJNDILinks/{name}

This resource manages a [weblogic.management.configuration.ForeignJNDILinkOverrideMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.ForeignJNDILinkOverrideMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.ForeignJNDILinkOverrideMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ForeignJNDILinkOverrideMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/foreignJNDIProviderOverrides/{name}/foreignJNDILinks/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/foreignJNDIProviderOverrides/{name}/foreignJNDILinks](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/foreignJNDIProviderOverrides/{name}/foreignJNDILinks/{name}](#) **rel**=self

This resource.

POST

Update this [weblogic.management.configuration.ForeignJNDILinkOverrideMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.ForeignJNDILinkOverrideMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/internalAppDeployments

This resource manages a collection of [weblogic.management.configuration.AppDeploymentMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.configuration.AppDeploymentMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.AppDeploymentMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/internalAppDeployments](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/internalAppDeployments](#) **rel**=self
This resource.

/management/weblogic/{version}/edit/partitions/{name}/internalAppDeployments/{name}

This resource manages a [weblogic.management.configuration.AppDeploymentMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.AppDeploymentMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.AppDeploymentMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/internalAppDeployments/{name}/createPlan](#) **rel=action** **title=createPlan**
This resource's createPlan action resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/internalAppDeployments/{name}](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/internalAppDeployments](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/internalAppDeployments/{name}/redeploy](#) **rel=redeploy**
This resource's redeploy resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/internalAppDeployments/{name}](#) **rel=self**
This resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/internalAppDeployments/{name}/subDeploymentCreateForm](#) **rel=subDeploymentCreateForm**
The create form resource for this resource's subDeployments collection resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/internalAppDeployments/{name}/subDeployments](#) **rel=subDeployments**
This resource's subDeployments collection resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/internalAppDeployments/{name}/update](#) **rel=update**
This resource's update resource.

POST

Update this [weblogic.management.configuration.AppDeploymentMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.AppDeploymentMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/internalAppDeployments/{name}/createPlan

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

POST

Create a deployment plan in the specified directory.

Roles

Admin, Deployer

Request Body

Must contain a JSON object with the following fields:

planPath

planPath

Type: string

Response Body

Contains a JSON object with a string return field.

POST

Create a deployment plan in a default directory

Roles

Admin, Deployer

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/edit/partitions/{name}/internalAppDeployments/{name}/redeploy

The resource supports the following methods:

- [POST](#)

POST

Use the multi-part form to redeploy this application.

- `sourcePath`: the deployment to upload (required)
- `planPath`: the deployment plan to upload (optional)
- `model`: JSONObject containing an `AppDeploymentMBean` entity that contains the rest of the deployment information. However, deployment/plan information is ignored. (required)

This method supports both asynchronous and best effort synchronous invocations. The behavior is controlled by the 'Prefer' header. See [About Synchronous and Asynchronous Operations](#).

Roles

Admin, Deployer

/management/weblogic/{version}/edit/partitions/{name}/internalAppDeployments/{name}/subDeploymentCreateForm

This resource manages the create forms for the subDeployments collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.SubDeploymentMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the subDeployments collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/internalAppDeployments/{name}/subDeploymentCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/internalAppDeployments/{name}/subDeployments](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/internalAppDeployments/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/internalAppDeployments/{name}/subDeploymentCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/partitions/{name}/internalAppDeployments/{name}/subDeployments

This resource manages a collection of [weblogic.management.configuration.SubDeploymentMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.SubDeploymentMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.SubDeploymentMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/internalAppDeployments/{name}/subDeployments](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/internalAppDeployments/{name}/subDeploymentCreateForm](#) **rel=create-form**

The create form resource for this collection resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/internalAppDeployments/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/internalAppDeployments/{name}/subDeployments](#) **rel=self**

This resource.

POST

Add a new [weblogic.management.configuration.SubDeploymentMBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/internalAppDeployments/{name}/subDeployments/{name}

This resource manages a [weblogic.management.configuration.SubDeploymentMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/internalAppDeployments/{name}/subDeployments/{name}](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/internalAppDeployments/{name}/subDeployments](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/internalAppDeployments/{name}/subDeployments/{name}](#) **rel=self**

This resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/internalAppDeployments/{name}/subDeployments/{name}/subDeployments](#) **rel=subDeployments**

This resource's subDeployments collection resource.

POST

Update this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/internalAppDeployments/{name}/subDeployments/{name}/subDeployments

This resource manages a collection of [weblogic.management.configuration.SubDeploymentMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.configuration.SubDeploymentMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.SubDeploymentMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/internalAppDeployments/{name}/subDeployments/{name}/subDeployments](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/internalAppDeployments/{name}/subDeployments/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/internalAppDeployments/{name}/subDeployments/{name}/subDeployments](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/partitions/{name}/internalAppDeployments/{name}/subDeployments/{name}/subDeployments/{name}

This resource manages a [weblogic.management.configuration.SubDeploymentMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/internalAppDeployments/{name}/subDeployments/{name}/subDeployments/{name}](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/internalAppDeployments/{name}/subDeployments/{name}/subDeployments](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/internalAppDeployments/{name}/subDeployments/{name}/subDeployments/{name}](#) **rel=self**
This resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/internalAppDeployments/{name}/subDeployments/{name}/subDeployments/{name}/subDeployments](#) **rel=subDeployments**
This resource's subDeployments collection resource.

POST

Update this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/internalAppDeployments/{name}/update

The resource supports the following methods:

- [POST](#)

POST

Update this application.

This method supports both asynchronous and best effort synchronous invocations. The behavior is controlled by the 'Prefer' header. See [About Synchronous and Asynchronous Operations](#).

Roles

Admin, Deployer

/management/weblogic/{version}/edit/partitions/{name}/internalLibraries

This resource manages a collection of [weblogic.management.configuration.LibraryMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.configuration.LibraryMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.LibraryMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/internalLibraries](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/internalLibraries](#)
rel=self
This resource.

/management/weblogic/{version}/edit/partitions/{name}/internalLibraries/{name}

This resource manages a [weblogic.management.configuration.LibraryMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.LibraryMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.LibraryMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/internalLibraries/{name}/createPlan](#) **rel**=action **title**=createPlan
This resource's createPlan action resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/internalLibraries/{name}](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/internalLibraries](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/internalLibraries/{name}/redeploy](#) **rel**=redeploy
This resource's redeploy resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/internalLibraries/{name}](#) **rel**=self
This resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/internalLibraries/{name}/subDeploymentCreateForm](#) **rel**=subDeploymentCreateForm
The create form resource for this resource's subDeployments collection resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/internalLibraries/{name}/subDeployments](#) **rel**=subDeployments
This resource's subDeployments collection resource.

POST

Update this [weblogic.management.configuration.LibraryMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.LibraryMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/internalLibraries/{name}/createPlan

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

POST

Create a deployment plan in the specified directory.

Roles

Admin, Deployer

Request Body

Must contain a JSON object with the following fields:

planPath

planPath

Type: string

Response Body

Contains a JSON object with a string return field.

POST

Create a deployment plan in a default directory

Roles

Admin, Deployer

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/edit/partitions/{name}/internalLibraries/{name}/redeploy

The resource supports the following methods:

- [POST](#)

POST

Use the multi-part form to redeploy a library.

- `sourcePath`: the deployment to upload (required)
- `model`: `JSONObject` containing a `LibraryMBean` entity that contains the rest of the deployment information (required)

This method supports both asynchronous and best effort synchronous invocations. The behavior is controlled by the 'Prefer' header. See [About Synchronous and Asynchronous Operations](#).

Roles

Admin, Deployer

/management/weblogic/{version}/edit/partitions/{name}/internalLibraries/{name}/subDeploymentCreateForm

This resource manages the create forms for the subDeployments collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.SubDeploymentMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the subDeployments collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/internalLibraries/{name}/subDeploymentCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/internalLibraries/{name}/subDeployments](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/internalLibraries/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/internalLibraries/{name}/subDeploymentCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/partitions/{name}/internalLibraries/{name}/subDeployments

This resource manages a collection of [weblogic.management.configuration.SubDeploymentMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.SubDeploymentMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.SubDeploymentMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/internalLibraries/{name}/subDeployments](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/internalLibraries/{name}/subDeploymentCreateForm](#) **rel**=create-form

The create form resource for this collection resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/internalLibraries/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/internalLibraries/{name}/subDeployments](#) **rel**=self

This resource.

POST

Add a new [weblogic.management.configuration.SubDeploymentMBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/internalLibraries/{name}/subDeployments/{name}

This resource manages a [weblogic.management.configuration.SubDeploymentMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/internalLibraries/{name}/subDeployments/{name}](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/internalLibraries/{name}/subDeployments](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/internalLibraries/{name}/subDeployments/{name}](#) **rel=self**

This resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/internalLibraries/{name}/subDeployments/{name}/subDeployments](#) **rel=subDeployments**

This resource's subDeployments collection resource.

POST

Update this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/internalLibraries/{name}/subDeployments/{name}/subDeployments

This resource manages a collection of [weblogic.management.configuration.SubDeploymentMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.configuration.SubDeploymentMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.SubDeploymentMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/internalLibraries/{name}/subDeployments/{name}/subDeployments](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/internalLibraries/{name}/subDeployments/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/internalLibraries/{name}/subDeployments/{name}/subDeployments](#) **rel**=self

This resource.

/management/weblogic/{version}/edit/partitions/{name}/internalLibraries/{name}/subDeployments/{name}/subDeployments/{name}

This resource manages a [weblogic.management.configuration.SubDeploymentMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/internalLibraries/{name}/subDeployments/{name}/subDeployments/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/internalLibraries/{name}/subDeployments/{name}/subDeployments **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/internalLibraries/{name}/subDeployments/{name}/subDeployments/{name} **rel**=self

This resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/internalLibraries/{name}/subDeployments/{name}/subDeployments/{name}/subDeployments **rel**=subDeployments

This resource's subDeployments collection resource.

POST

Update this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/JDBCSystemResourceOverrideCreateForm

This resource manages the create forms for the JDBCSystemResourceOverrides collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.JDBCSystemResourceOverrideMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the JDBCSystemResourceOverrides collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.JDBCSystemResourceOverrideMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/JDBCSystemResourceOverrideCreateForm](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/JDBCSystemResourceOverrides](#) **rel=create**
The collection resource for this create form resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/JDBCSystemResourceOverrideCreateForm](#) **rel=self**
This resource.

/management/weblogic/{version}/edit/partitions/{name}/JDBCSystemResourceOverrides

This resource manages a collection of [weblogic.management.configuration.JDBCSystemResourceOverrideMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.JDBCSystemResourceOverrideMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.JDBCSystemResourceOverrideMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/JDBCSystemResourceOverrides](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/JDBCSystemResourceOverrideCreateForm](#) **rel=create-form**
The create form resource for this collection resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/JDBCSystemResourceOverrides](#) **rel=self**
This resource.

POST

Add a new [weblogic.management.configuration.JDBCSystemResourceOverrideMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.JDBCSystemResourceOverrideMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/JDBCSystemResourceOverrides/{name}

This resource manages a [weblogic.management.configuration.JDBCSystemResourceOverrideMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.JDBCSystemResourceOverrideMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.JDBCSystemResourceOverrideMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.JDBCSystemResourceOverrideMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/JDBCSystemResourceOverrides/{name}/JDBCPropertyOverrideCreateForm](#)
[rel=JDBCPropertyOverrideCreateForm](#)

The create form resource for this resource's JDBCPropertyOverrides collection resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/JDBCSystemResourceOverrides/{name}/JDBCPropertyOverrides](#) [rel=JDBCPropertyOverrides](#)

This resource's JDBCPropertyOverrides collection resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/JDBCSystemResourceOverrides/{name}](#) [rel=canonical](#)

This resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/JDBCSystemResourceOverrides](#) [rel=parent](#)

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/JDBCSystemResourceOverrides/{name}](#) [rel=self](#)

This resource.

POST

POST

Update this [weblogic.management.configuration.JDBCSystemResourceOverrideMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.JDBCSystemResourceOverrideMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/JDBCSystemResourceOverrides/{name}/JDBCPropertyOverrideCreateForm

This resource manages the create forms for the JDBCPropertyOverrides collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.JDBCPropertyOverrideMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the JDBCPropertyOverrides collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.JDBCPropertyOverrideMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/JDBCSystemResourceOverrides/{name}/JDBCPropertyOverrideCreateForm **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/JDBCSystemResourceOverrides/{name}/JDBCPropertyOverrides **rel**=create

The collection resource for this create form resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/JDBCSystemResourceOverrides/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/JDBCSystemResourceOverrides/{name}/JDBCPropertyOverrideCreateForm **rel**=self

This resource.

/management/weblogic/{version}/edit/partitions/{name}/JDBCSystemResourceOverrides/{name}/JDBCPropertyOverrides

This resource manages a collection of [weblogic.management.configuration.JDBCPropertyOverrideMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.JDBCPropertyOverrideMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.JDBCPropertyOverrideMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/JDBCSystemResourceOverrides/{name}/JDBCPropertyOverrides](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/JDBCSystemResourceOverrides/{name}/JDBCPropertyOverrideCreateForm](#) **rel**=create-form
The create form resource for this collection resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/JDBCSystemResourceOverrides/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/JDBCSystemResourceOverrides/{name}/JDBCPropertyOverrides](#) **rel**=self
This resource.

POST

Add a new [weblogic.management.configuration.JDBCPropertyOverrideMBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.JDBCPropertyOverrideMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/JDBCSystemResourceOverrides/{name}/JDBCPropertyOverrides/{name}

This resource manages a [weblogic.management.configuration.JDBCPropertyOverrideMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.JDBCPropertyOverrideMBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.management.configuration.JDBCPropertyOverrideMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.JDBCPropertyOverrideMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/JDBCSystemResourceOverrides/{name}/JDBCPropertyOverrides/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/JDBCSystemResourceOverrides/{name}/JDBCPropertyOverrides](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/JDBCSystemResourceOverrides/{name}/JDBCPropertyOverrides/{name}](#) **rel**=self

This resource.

POST

Update this [weblogic.management.configuration.JDBCPropertyOverrideMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.JDBCPropertyOverrideMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/JMSSystemResourceOverrideCreateForm

This resource manages the create forms for the JMSSystemResourceOverrides collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.JMSSystemResourceOverrideMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the JMSSystemResourceOverrides collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.JMSSystemResourceOverrideMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/JMSSystemResourceOverrideCreateForm](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/JMSSystemResourceOverrides](#) **rel=create**
The collection resource for this create form resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/JMSSystemResourceOverrideCreateForm](#) **rel=self**
This resource.

/management/weblogic/{version}/edit/partitions/{name}/JMSSystemResourceOverrides

This resource manages a collection of [weblogic.management.configuration.JMSSystemResourceOverrideMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.JMSSystemResourceOverrideMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.JMSSystemResourceOverrideMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/JMSSystemResourceOverrides](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/JMSSystemResourceOverrideCreateForm](#) **rel=create-form**
The create form resource for this collection resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/JMSSystemResourceOverrides](#) **rel=self**
This resource.

POST

Add a new [weblogic.management.configuration.JMSSystemResourceOverrideMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.JMSSystemResourceOverrideMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/JMSSystemResourceOverrides/{name}

This resource manages a [weblogic.management.configuration.JMSSystemResourceOverrideMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.JMSSystemResourceOverrideMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.JMSSystemResourceOverrideMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.JMSSystemResourceOverrideMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/JMSSystemResourceOverrides/{name} rel=canonical](#)

This resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/JMSSystemResourceOverrides/{name}/foreignServerCreateForm rel=foreignServerCreateForm](#)

The create form resource for this resource's foreignServers collection resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/JMSSystemResourceOverrides/{name}/foreignServers rel=foreignServers](#)

This resource's foreignServers collection resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/JMSSystemResourceOverrides rel=parent](#)

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/JMSSystemResourceOverrides/{name} rel=self](#)

This resource.

POST

Update this [weblogic.management.configuration.JMSSystemResourceOverrideMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.JMSSystemResourceOverrideMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/JMSSystemResourceOverrides/{name}/foreignServerCreateForm

This resource manages the create forms for the foreignServers collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.ForeignServerOverrideMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the `foreignServers` collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ForeignServerOverrideMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/JMSSystemResource Overrides/{name}/foreignServerCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/JMSSystemResource Overrides/{name}/foreignServers](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/JMSSystemResource Overrides/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/JMSSystemResource Overrides/{name}/foreignServerCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/partitions/{name}/JMSSystemResourceOverrides/{name}/foreignServers

This resource manages a collection of [weblogic.management.configuration.ForeignServerOverrideMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.ForeignServerOverrideMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.ForeignServerOverrideMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/JMSSystemResource Overrides/{name}/foreignServers](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/JMSSystemResource Overrides/{name}/foreignServerCreateForm](#) **rel=create-form**

The create form resource for this collection resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/JMSSystemResource Overrides/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/JMSSystemResource Overrides/{name}/foreignServers](#) **rel=self**

This resource.

POST

Add a new [weblogic.management.configuration.ForeignServerOverrideMBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.ForeignServerOverrideMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/JMSSystemResourceOverrides/{name}/foreignServers/{name}

This resource manages a [weblogic.management.configuration.ForeignServerOverrideMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.ForeignServerOverrideMBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.management.configuration.ForeignServerOverrideMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ForeignServerOverrideMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/JMSSystemResource Overrides/{name}/foreignServers/{name}/JNDIProperties](#) **rel**=JNDIProperties

This resource's JNDIProperties collection resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/JMSSystemResource Overrides/{name}/foreignServers/{name}/JNDIPropertyCreateForm](#) **rel**=JNDIPropertyCreateForm

The create form resource for this resource's JNDIProperties collection resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/JMSSystemResource Overrides/{name}/foreignServers/{name}](#) **rel**=canonical

This resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/JMSSystemResource Overrides/{name}/foreignServers/{name}/foreignConnectionFactories](#) **rel**=foreignConnectionFactories

This resource's foreignConnectionFactories collection resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/JMSSystemResource Overrides/{name}/foreignServers/{name}/foreignConnectionFactoryCreateForm](#) **rel**=foreignConnectionFactoryCreateForm

The create form resource for this resource's foreignConnectionFactories collection resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/JMSSystemResource Overrides/{name}/foreignServers/{name}/foreignDestinationCreateForm](#) **rel**=foreignDestinationCreateForm

The create form resource for this resource's foreignDestinations collection resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/JMSSystemResource Overrides/{name}/foreignServers/{name}/foreignDestinations](#) **rel**=foreignDestinations

This resource's foreignDestinations collection resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/JMSSystemResource Overrides/{name}/foreignServers](#) **rel**=parent

The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/JMSSystemResource Overrides/{name}/foreignServers/{name}](#) **rel**=self

This resource.

POST

Update this [weblogic.management.configuration.ForeignServerOverrideMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.ForeignServerOverrideMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/JMSSystemResource Overrides/{name}/foreignServers/{name}/foreignConnectionFactories

This resource manages a collection of [weblogic.management.configuration.ForeignConnectionFactoryOverrideMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.ForeignConnectionFactoryOverrideMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.ForeignConnectionFactoryOverrideMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/JMSSystemResource Overrides/{name}/foreignServers/{name}/foreignConnectionFactories **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/JMSSystemResource Overrides/{name}/foreignServers/{name}/foreignConnectionFactoryCreateForm **rel**=create-form

The create form resource for this collection resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/JMSSystemResource Overrides/{name}/foreignServers/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/JMSSystemResource Overrides/{name}/foreignServers/{name}/foreignConnectionFactories **rel**=self

This resource.

POST

Add a new [weblogic.management.configuration.ForeignConnectionFactoryOverrideMBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.ForeignConnectionFactoryOverrideMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/JMSSystemResource Overrides/{name}/foreignServers/{name}/foreignConnectionFactory/{name}

This resource manages a [weblogic.management.configuration.ForeignConnectionFactoryOverrideMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.ForeignConnectionFactoryOverrideMBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.management.configuration.ForeignConnectionFactoryOverrideMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ForeignConnectionFactoryOverrideMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/JMSSystemResourceOverrides/{name}/foreignServers/{name}/foreignConnectionFactories/{name}
rel=canonical
This resource.
- **uri**=/management/weblogic/{version}/edit/partitions/{name}/JMSSystemResourceOverrides/{name}/foreignServers/{name}/foreignConnectionFactories
rel=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/edit/partitions/{name}/JMSSystemResourceOverrides/{name}/foreignServers/{name}/foreignConnectionFactories/{name}
rel=self
This resource.

POST

Update this [weblogic.management.configuration.ForeignConnectionFactoryOverrideMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.ForeignConnectionFactoryOverrideMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/JMSSystemResourceOverrides/{name}/foreignServers/{name}/foreignConnectionFactoryCreateForm

This resource manages the create forms for the foreignConnectionFactories collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.ForeignConnectionFactoryOverrideMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the `foreignConnectionFactories` collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ForeignConnectionFactoryOverrideMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/JMSSystemResource Overrides/{name}/foreignServers/{name}/foreignConnectionFactoryCreateForm rel=canonical](#)

This resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/JMSSystemResource Overrides/{name}/foreignServers/{name}/foreignConnectionFactories rel=create](#)

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/JMSSystemResource Overrides/{name}/foreignServers/{name} rel=parent](#)

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/JMSSystemResource Overrides/{name}/foreignServers/{name}/foreignConnectionFactoryCreateForm rel=self](#)

This resource.

/management/weblogic/{version}/edit/partitions/{name}/JMSSystemResourceOverrides/{name}/foreignServers/{name}/foreignDestinationCreateForm

This resource manages the create forms for the foreignDestinations collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.ForeignDestinationOverrideMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the `foreignDestinations` collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ForeignDestinationOverrideMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/JMSSystemResource Overrides/{name}/foreignServers/{name}/foreignDestinationCreateForm](#)
rel=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/JMSSystemResource Overrides/{name}/foreignServers/{name}/foreignDestinations](#) **rel**=create

The collection resource for this create form resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/JMSSystemResource Overrides/{name}/foreignServers/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/JMSSystemResource Overrides/{name}/foreignServers/{name}/foreignDestinationCreateForm](#)
rel=self

This resource.

/management/weblogic/{version}/edit/partitions/{name}/JMSSystemResource Overrides/{name}/foreignServers/{name}/foreignDestinations

This resource manages a collection of [weblogic.management.configuration.ForeignDestinationOverrideMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.ForeignDestinationOverrideMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.ForeignDestinationOverrideMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/JMSSystemResource Overrides/{name}/foreignServers/{name}/foreignDestinations **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/JMSSystemResource Overrides/{name}/foreignServers/{name}/foreignDestinationCreateForm **rel**=create-form

The create form resource for this collection resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/JMSSystemResource Overrides/{name}/foreignServers/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/JMSSystemResource Overrides/{name}/foreignServers/{name}/foreignDestinations **rel**=self

This resource.

POST

Add a new [weblogic.management.configuration.ForeignDestinationOverrideMBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.ForeignDestinationOverrideMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/JMSSystemResource Overrides/{name}/foreignServers/{name}/foreignDestinations/{name}

This resource manages a [weblogic.management.configuration.ForeignDestinationOverrideMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.ForeignDestinationOverrideMBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.management.configuration.ForeignDestinationOverrideMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ForeignDestinationOverrideMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/JMSSystemResource Overrides/{name}/foreignServers/{name}/foreignDestinations/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/JMSSystemResource Overrides/{name}/foreignServers/{name}/foreignDestinations **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/JMSSystemResource Overrides/{name}/foreignServers/{name}/foreignDestinations/{name} **rel**=self

This resource.

/management/weblogic/{version}/edit/partitions/{name}/JMSSystemResourceOverrides/{name}/foreignServers/{name}/foreignD

POST

Update this [weblogic.management.configuration.ForeignDestinationOverrideMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.ForeignDestinationOverrideMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/JMSSystemResource Overrides/{name}/foreignServers/{name}/JNDIProperties

This resource manages a collection of [weblogic.management.configuration.PartitionPropertyMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.PartitionPropertyMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.PartitionPropertyMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/JMSSystemResourceOverrides/{name}/foreignServers/{name}/JNDIProperties](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/JMSSystemResourceOverrides/{name}/foreignServers/{name}/JNDIPropertyCreateForm](#) **rel=create-form**

The create form resource for this collection resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/JMSSystemResourceOverrides/{name}/foreignServers/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/JMSSystemResourceOverrides/{name}/foreignServers/{name}/JNDIProperties](#) **rel=self**

This resource.

POST

Add a new [weblogic.management.configuration.PartitionPropertyMBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.PartitionPropertyMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/JMSSystemResource Overrides/{name}/foreignServers/{name}/JNDIProperties/{name}

This resource manages a [weblogic.management.configuration.PartitionPropertyMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.PartitionPropertyMBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.management.configuration.PartitionPropertyMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.PartitionPropertyMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/JMSSystemResourceOverrides/{name}/foreignServers/{name}/JNDIProperties/{name} **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/edit/partitions/{name}/JMSSystemResourceOverrides/{name}/foreignServers/{name}/JNDIProperties **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/edit/partitions/{name}/JMSSystemResourceOverrides/{name}/foreignServers/{name}/JNDIProperties/{name} **rel**=self
This resource.

POST

Update this [weblogic.management.configuration.PartitionPropertyMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.PartitionPropertyMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/JMSSystemResourceOverrides/{name}/foreignServers/{name}/JNDIPropertyCreateForm

This resource manages the create forms for the JNDIProperties collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.PartitionPropertyMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the JNDIProperties collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.PartitionPropertyMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/JMSSystemResource Overrides/{name}/foreignServers/{name}/JNDIPropertyCreateForm](#)
rel=canonical

This resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/JMSSystemResource Overrides/{name}/foreignServers/{name}/JNDIProperties](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/JMSSystemResource Overrides/{name}/foreignServers/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/JMSSystemResource Overrides/{name}/foreignServers/{name}/JNDIPropertyCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/partitions/{name}/JTAPartition

This resource manages a [weblogic.management.configuration.JTAPartitionMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.JTAPartitionMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.JTAPartitionMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/JTAPartition](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/JTAPartition](#)
rel=self
This resource.

POST

Update this [weblogic.management.configuration.JTAPartitionMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.JTAPartitionMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/lookupAvailableTarget

The resource supports the following methods:

- [POST](#)

POST

Looks up the named available target.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

name

the name of the target to find

Type: string

Response Body

Contains a JSON object with a weblogic.management.configuration.TargetMBean reference return field.

/management/weblogic/{version}/edit/partitions/{name}/mailSessionOverrideCreateForm

This resource manages the create forms for the mailSessionOverrides collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.MailSessionOverrideMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the mailSessionOverrides collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.MailSessionOverrideMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/mailSessionOverrideCreateForm](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/mailSessionOverrides](#) **rel=create**
The collection resource for this create form resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/mailSessionOverrideCreateForm](#) **rel=self**
This resource.

/management/weblogic/{version}/edit/partitions/{name}/mailSessionOverrides

This resource manages a collection of [weblogic.management.configuration.MailSessionOverrideMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.MailSessionOverrideMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.MailSessionOverrideMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/mailSessionOverrides](#) [rel=canonical](#)
This resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/mailSessionOverrideCreateForm](#) [rel=create-form](#)
The create form resource for this collection resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}](#) [rel=parent](#)
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/mailSessionOverrides](#) [rel=self](#)
This resource.

POST

Add a new [weblogic.management.configuration.MailSessionOverrideMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.MailSessionOverrideMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/mailSessionOverrides/{name}

This resource manages a [weblogic.management.configuration.MailSessionOverrideMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

DELETE

Delete this [weblogic.management.configuration.MailSessionOverrideMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.MailSessionOverrideMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.MailSessionOverrideMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/mailSessionOverrides/{name} rel=canonical](#)
This resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/mailSessionOverrides rel=parent](#)
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/mailSessionOverrides/{name} rel=self](#)
This resource.

POST

Update this [weblogic.management.configuration.MailSessionOverrideMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.MailSessionOverrideMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/managedExecutorServiceTemplateCreateForm

This resource manages the create forms for the managedExecutorServiceTemplates collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.ManagedExecutorServiceTemplateMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the `managedExecutorServiceTemplates` collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ManagedExecutorServiceTemplateMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/managedExecutorServiceTemplateCreateForm](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/managedExecutorServiceTemplates](#) **rel**=create
The collection resource for this create form resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/managedExecutorServiceTemplateCreateForm](#) **rel**=self
This resource.

/management/weblogic/{version}/edit/partitions/{name}/managedExecutorServiceTemplates

This resource manages a collection of [weblogic.management.configuration.ManagedExecutorServiceTemplateMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.ManagedExecutorServiceTemplateMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.ManagedExecutorServiceTemplateMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/managedExecutorServiceTemplates](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/managedExecutorServiceTemplateCreateForm](#) **rel**=create-form
The create form resource for this collection resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/managedExecutorServiceTemplates](#) **rel**=self
This resource.

POST

Add a new [weblogic.management.configuration.ManagedExecutorServiceTemplateMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.ManagedExecutorServiceTemplateMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/managedExecutorServiceTemplates/{name}

This resource manages a [weblogic.management.configuration.ManagedExecutorServiceTemplateMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this

[weblogic.management.configuration.ManagedExecutorServiceTemplateMBean](#)
instance.

Roles

Admin

GET

Get this

[weblogic.management.configuration.ManagedExecutorServiceTemplateMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a

[weblogic.management.configuration.ManagedExecutorServiceTemplateMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/managedExecutorServiceTemplates/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/managedExecutorServiceTemplates](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/managedExecutorServiceTemplates/{name}](#) **rel**=self

This resource.

POST

Update this [weblogic.management.configuration.ManagedExecutorServiceTemplateMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.ManagedExecutorServiceTemplateMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/managedScheduledExecutorServiceTemplateCreateForm

This resource manages the create forms for the managedScheduledExecutorServiceTemplates collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.ManagedScheduledExecutorServiceTemplateMB](#) entity populated with default values that can be customized then posted (using the POST method) to the [managedScheduledExecutorServiceTemplates](#) collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ManagedScheduledExecutorServiceTemplateMB](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/managedScheduledExecutorServiceTemplateCreateForm](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/managedScheduledExecutorServiceTemplates](#) **rel=create**
The collection resource for this create form resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/managedScheduledExecutorServiceTemplateCreateForm](#) **rel=self**
This resource.

/management/weblogic/{version}/edit/partitions/{name}/managedScheduledExecutorServiceTemplates

This resource manages a collection of [weblogic.management.configuration.ManagedScheduledExecutorServiceTemplateMBEAN](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.ManagedScheduledExecutorServiceTemplateMB](#) [ean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.ManagedScheduledExecutorServiceTemplateMB](#) [ean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/managedScheduledExecutorServiceTemplates](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/managedScheduledExecutorServiceTemplateCreateForm](#) **rel=create-form**
The create form resource for this collection resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/managedScheduledExecutorServiceTemplates](#) **rel=self**
This resource.

POST

Add a new [weblogic.management.configuration.ManagedScheduledExecutorServiceTemplateMB](#) [ean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.ManagedScheduledExecutorServiceTemplateMB](#) [ean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/managedScheduledExecutorServiceTemplates/{name}

This resource manages a [weblogic.management.configuration.ManagedScheduledExecutorServiceTemplateMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this

[weblogic.management.configuration.ManagedScheduledExecutorServiceTemplateMB](#)
ean instance.

Roles

Admin

GET

Get this

[weblogic.management.configuration.ManagedScheduledExecutorServiceTemplateMB](#)
[ean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a

[weblogic.management.configuration.ManagedScheduledExecutorServiceTemplateMB](#)
[ean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/managedScheduledExecutorServiceTemplates/{name}](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/managedScheduledExecutorServiceTemplates](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/managedScheduledExecutorServiceTemplates/{name}](#) **rel=self**

This resource.

POST

Update this [weblogic.management.configuration.ManagedScheduledExecutorServiceTemplateMB](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.ManagedScheduledExecutorServiceTemplateMB](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/managedThreadFactoryTemplateCreateForm

This resource manages the create forms for the managedThreadFactoryTemplates collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.ManagedThreadFactoryTemplateMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the `managedThreadFactoryTemplates` collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ManagedThreadFactoryTemplateMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/managedThreadFactoryTemplateCreateForm](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/managedThreadFactoryTemplates](#) **rel**=create
The collection resource for this create form resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/managedThreadFactoryTemplateCreateForm](#) **rel**=self
This resource.

/management/weblogic/{version}/edit/partitions/{name}/managedThreadFactoryTemplates

This resource manages a collection of [weblogic.management.configuration.ManagedThreadFactoryTemplateMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.ManagedThreadFactoryTemplateMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.ManagedThreadFactoryTemplateMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/managedThreadFactoryTemplates](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/managedThreadFactoryTemplateCreateForm](#) **rel**=create-form
The create form resource for this collection resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/managedThreadFactoryTemplates](#) **rel**=self
This resource.

POST

Add a new [weblogic.management.configuration.ManagedThreadFactoryTemplateMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.ManagedThreadFactoryTemplateMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/managedThreadFactoryTemplates/{name}

This resource manages a [weblogic.management.configuration.ManagedThreadFactoryTemplateMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this

[weblogic.management.configuration.ManagedThreadFactoryTemplateMBean](#)
instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.ManagedThreadFactoryTemplateMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ManagedThreadFactoryTemplateMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/managedThreadFactoryTemplates/{name}](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/managedThreadFactoryTemplates](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/managedThreadFactoryTemplates/{name}](#) **rel**=self
This resource.

POST

Update this [weblogic.management.configuration.ManagedThreadFactoryTemplateMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.ManagedThreadFactoryTemplateMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/partitionLog

This resource manages a [weblogic.management.configuration.PartitionLogMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.PartitionLogMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.PartitionLogMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/partitionLog](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/partitionLog](#)
rel=self
This resource.

POST

POST

Update this [weblogic.management.configuration.PartitionLogMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.PartitionLogMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/partitionWorkManager

This resource manages a [weblogic.management.configuration.PartitionWorkManagerMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.PartitionWorkManagerMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.PartitionWorkManagerMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.PartitionWorkManagerMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/partitionWorkManager](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/partitionWorkManagerCreateForm](#) **rel=create-form**
The create form resource for this optional singleton resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/partitionWorkManager](#) **rel=self**
This resource.

POST

Update this [weblogic.management.configuration.PartitionWorkManagerMBean](#) instance if it exists; otherwise, create it.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.PartitionWorkManagerMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/partitionWorkManager CreateForm

This resource manages the create forms for the partitionWorkManager optional singleton instance.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.PartitionWorkManagerMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the `partitionWorkManager` optional singleton resource to create a new instance if it currently does not exist.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.PartitionWorkManagerMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/partitionWorkManagerCreateForm](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/partitionWorkManagerCreateForm](#) **rel**=create
The optional singleton resource for this create form resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/partitionWorkManagerCreateForm](#) **rel**=self
This resource.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroupCreateForm

This resource manages the create forms for the resourceGroups collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.ResourceGroupMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the resourceGroups collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ResourceGroupMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroupCreateForm](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups](#) **rel**=create
The collection resource for this create form resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroupCreateForm](#) **rel**=self
This resource.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups

This resource manages a collection of [weblogic.management.configuration.ResourceGroupMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.ResourceGroupMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.ResourceGroupMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroupCreateForm](#) **rel**=create-form
The create form resource for this collection resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups](#)
rel=self
This resource.

POST

Add a new [weblogic.management.configuration.ResourceGroupMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.ResourceGroupMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}

This resource manages a [weblogic.management.configuration.ResourceGroupMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.ResourceGroupMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.ResourceGroupMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ResourceGroupMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCStoreCreateForm](#) **rel=JDBCStoreCreateForm**
The create form resource for this resource's JDBCStores collection resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCStores](#) **rel=JDBCStores**
This resource's JDBCStores collection resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResourceCreateForm](#) **rel=JDBCSystemResourceCreateForm**
The create form resource for this resource's JDBCSystemResources collection resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources](#) **rel=JDBCSystemResources**
This resource's JDBCSystemResources collection resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSBridgeDestinationCreateForm](#) **rel=JMSBridgeDestinationCreateForm**
The create form resource for this resource's JMSBridgeDestinations collection resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSBridgeDestinations](#) **rel=JMSBridgeDestinations**
This resource's JMSBridgeDestinations collection resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSServerCreateForm](#) **rel=JMSServerCreateForm**
The create form resource for this resource's JMSServers collection resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSServers](#) **rel=JMSServers**
This resource's JMSServers collection resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResourceCreateForm](#) **rel=JMSSystemResourceCreateForm**
The create form resource for this resource's JMSSystemResources collection resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources](#) **rel=JMSSystemResources**

This resource's JMSSystemResources collection resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/SAFAgentCreateForm **rel**=SAFAgentCreateForm

The create form resource for this resource's SAFAgents collection resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/SAFAgents **rel**=SAFAgents

This resource's SAFAgents collection resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResourceCreateForm **rel**=WLDFSystemResourceCreateForm

The create form resource for this resource's WLDFSystemResources collection resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources **rel**=WLDFSystemResources

This resource's WLDFSystemResources collection resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/findEffectiveTargets **rel**=action **title**=findEffectiveTargets

This resource's findEffectiveTargets action resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/lookupTarget **rel**=action **title**=lookupTarget

This resource's lookupTarget action resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/appDeployments **rel**=appDeployments

This resource's appDeployments collection resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/fileStoreCreateForm **rel**=fileStoreCreateForm

The create form resource for this resource's fileStores collection resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/fileStores **rel**=fileStores

This resource's fileStores collection resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/foreignJNDIProviderCreateForm **rel**=foreignJNDIProviderCreateForm

The create form resource for this resource's foreignJNDIProviders collection resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/foreignJNDIProviders **rel**=foreignJNDIProviders

This resource's foreignJNDIProviders collection resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/libraries **rel**=libraries

This resource's libraries collection resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/mailSessionCreateForm **rel**=mailSessionCreateForm
The create form resource for this resource's mailSessions collection resource.
- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/mailSessions **rel**=mailSessions
This resource's mailSessions collection resource.
- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/managedExecutorServiceCreateForm **rel**=managedExecutorServiceCreateForm
The create form resource for this resource's managedExecutorServices collection resource.
- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/managedExecutorServices **rel**=managedExecutorServices
This resource's managedExecutorServices collection resource.
- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/managedScheduledExecutorServiceCreateForm **rel**=managedScheduledExecutorServiceCreateForm
The create form resource for this resource's managedScheduledExecutorServices collection resource.
- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/managedScheduledExecutorServices **rel**=managedScheduledExecutorServices
This resource's managedScheduledExecutorServices collection resource.
- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/managedThreadFactories **rel**=managedThreadFactories
This resource's managedThreadFactories collection resource.
- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/managedThreadFactoryCreateForm **rel**=managedThreadFactoryCreateForm
The create form resource for this resource's managedThreadFactories collection resource.
- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/messagingBridgeCreateForm **rel**=messagingBridgeCreateForm
The create form resource for this resource's messagingBridges collection resource.
- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/messagingBridges **rel**=messagingBridges
This resource's messagingBridges collection resource.
- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/osgiFrameworkCreateForm **rel**=osgiFrameworkCreateForm
The create form resource for this resource's osgiFrameworks collection resource.
- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/osgiFrameworks **rel**=osgiFrameworks
This resource's osgiFrameworks collection resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups
rel=parent
The parent resource of this resource.
- **rel**=resourceGroupTemplate
This resource's resourceGroupTemplate reference to a
weblogic.management.configuration.ResourceGroupTemplateMBean resource.
- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{n
ame} **rel**=self
This resource.

POST

POST

Update this [weblogic.management.configuration.ResourceGroupMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.ResourceGroupMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/appDeployments

This resource manages a collection of [weblogic.management.configuration.AppDeploymentMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.AppDeploymentMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.AppDeploymentMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/appDeployments](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/appDeployments](#) **rel**=self

This resource.

POST

The resource supports the following methods:

- [POST accepting application/json](#)
- [POST accepting multipart/form-data](#)

POST accepting application/json

This resource deploy is used to deploy applications that are already on the administration server. The application must be a supported package type (for example, an EAR or WAR module).

This method supports both asynchronous and best effort synchronous invocations. The behavior is controlled by the 'Prefer' header. See [About Synchronous and Asynchronous Operations](#).

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.AppDeploymentMBean](#) entity.

To deploy an application you must provide the name of the application, the path to the source of the deployable unit on the administration server, and the targets to which the application will be deployed.

If the source path is relative, it is resolved relative to *InstallDir/app* if *InstallDir* is not null; otherwise, it is resolved relative to the domain root.

POST accepting multipart/form-data

Use the multi-part form to upload an application from the client to the server and then deploy it.

- `sourcePath`: the deployment to upload (required)
- `planPath`: the deployment plan to upload (optional)
- `model`: JSONObject containing an `AppDeploymentMBean` entity that contains the rest of the deployment information (however, `deployment/plan` information is ignored) (required)

This method supports both asynchronous and best effort synchronous invocations. The behavior is controlled by the 'Prefer' header. See [About Synchronous and Asynchronous Operations](#).

Roles

Admin, Deployer

Request Body

Use the multi-part form to deploy an application.

- `sourcePath`: the deployment to upload (required)
- `planPath`: the deployment plan to upload (optional)

- model: JSONObject containing an AppDeploymentMBean entity that contains the rest of the deployment information. However, deployment/plan information is ignored. (required)

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/appDeployments/{name}

This resource manages a [weblogic.management.configuration.AppDeploymentMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Undeploy an application.

This method supports both asynchronous and best effort synchronous invocations. The behavior is controlled by the 'Prefer' header. See [About Synchronous and Asynchronous Operations](#).

Roles

Admin, Deployer

GET

Get this [weblogic.management.configuration.AppDeploymentMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.AppDeploymentMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/appDeployments/{name}/createPlan](#) **rel=action** **title=createPlan**
This resource's createPlan action resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/appDeployments/{name}](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/appDeployments](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/appDeployments/{name}/redeploy](#) **rel=redeploy**
This resource's redeploy resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/appDeployments/{name}](#) **rel=self**
This resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/appDeployments/{name}/subDeploymentCreateForm](#) **rel=subDeploymentCreateForm**
The create form resource for this resource's subDeployments collection resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/appDeployments/{name}/subDeployments](#) **rel=subDeployments**
This resource's subDeployments collection resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/appDeployments/{name}/update](#) **rel=update**
This resource's update resource.

POST

Update this [weblogic.management.configuration.AppDeploymentMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.AppDeploymentMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/appDeployments/{name}/createPlan

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

POST

Create a deployment plan in the specified directory.

Roles

Admin, Deployer

Request Body

Must contain a JSON object with the following fields:

planPath

planPath

Type: string

Response Body

Contains a JSON object with a string return field.

POST

Create a deployment plan in a default directory

Roles

Admin, Deployer

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/appDeployments/{name}/redeploy

The resource supports the following methods:

- [POST](#)

POST

Use the multi-part form to redeploy this application.

- `sourcePath`: the deployment to upload (required)
- `planPath`: the deployment plan to upload (optional)
- `model`: JSONObject containing an `AppDeploymentMBean` entity that contains the rest of the deployment information. However, deployment/plan information is ignored. (required)

This method supports both asynchronous and best effort synchronous invocations. The behavior is controlled by the 'Prefer' header. See [About Synchronous and Asynchronous Operations](#).

Roles

Admin, Deployer

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/appDeployments/{name}/subDeploymentCreateForm

This resource manages the create forms for the subDeployments collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.SubDeploymentMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the subDeployments collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/appDeployments/{name}/subDeploymentCreateForm](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/appDeployments/{name}/subDeployments](#) **rel**=create

The collection resource for this create form resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/appDeployments/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/appDeployments/{name}/subDeploymentCreateForm](#) **rel**=self

This resource.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/appDeployments/{name}/subDeployments

This resource manages a collection of [weblogic.management.configuration.SubDeploymentMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.SubDeploymentMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.SubDeploymentMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/appDeployments/{name}/subDeployments](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/appDeployments/{name}/subDeploymentCreateForm](#) **rel**=create-form

The create form resource for this collection resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/appDeployments/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/appDeployments/{name}/subDeployments](#) **rel**=self

This resource.

POST

Add a new [weblogic.management.configuration.SubDeploymentMBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/appDeployments/{name}/subDeployments/{name}

This resource manages a [weblogic.management.configuration.SubDeploymentMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/appDeployments/{name}/subDeployments/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/appDeployments/{name}/subDeployments](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/appDeployments/{name}/subDeployments/{name}](#) **rel**=self

This resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/appDeployments/{name}/subDeployments/{name}/subDeployments](#) **rel**=subDeployments

This resource's subDeployments collection resource.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/appDeployments/{name}/subDeploy-

POST

Update this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/appDeployments/{name}/subDeployments/{name}/subDeployments

This resource manages a collection of [weblogic.management.configuration.SubDeploymentMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.configuration.SubDeploymentMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.SubDeploymentMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/appDeployments/{name}/subDeployments/{name}/subDeployments](#)
rel=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/appDeployments/{name}/subDeployments/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/appDeployments/{name}/subDeployments/{name}/subDeployments](#)
rel=self

This resource.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/appDeployments/{name}/subDeployments/{name}/subDeployments/{name}

This resource manages a [weblogic.management.configuration.SubDeploymentMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/appDeployments/{name}/subDeployments/{name}/subDeployments/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/appDeployments/{name}/subDeployments/{name}/subDeployments **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/appDeployments/{name}/subDeployments/{name}/subDeployments/{name} **rel**=self

This resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/appDeployments/{name}/subDeployments/{name}/subDeployments/{name}/subDeployments **rel**=subDeployments

This resource's subDeployments collection resource.

POST

Update this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/appDeployments/{name}/update

The resource supports the following methods:

- [POST](#)

POST

Update this application.

This method supports both asynchronous and best effort synchronous invocations. The behavior is controlled by the 'Prefer' header. See [About Synchronous and Asynchronous Operations](#).

Roles

Admin, Deployer

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/fileStoreCreateForm

This resource manages the create forms for the fileStores collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.FileStoreMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the fileStores collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.FileStoreMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/fileStoreCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/fileStores](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/fileStoreCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/fileStores

This resource manages a collection of [weblogic.management.configuration.FileStoreMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.FileStoreMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.FileStoreMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/fileStores](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/fileStoreCreateForm](#) **rel=create-form**

The create form resource for this collection resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/fileStores](#) **rel=self**

This resource.

POST

Add a new [weblogic.management.configuration.FileStoreMBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.FileStoreMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/fileStores/{name}

This resource manages a [weblogic.management.configuration.FileStoreMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.FileStoreMBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.management.configuration.FileStoreMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.FileStoreMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/fileStores/{name}](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/fileStores](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/fileStores/{name}](#) **rel=self**

This resource.

POST

Update this [weblogic.management.configuration.FileStoreMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.FileStoreMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/findEffectiveTargets

The resource supports the following methods:

- [POST](#)

POST

Returns the targets actually used by this resource group, accounting for partition-level defaulting.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a JSON object with a array of `weblogic.management.configuration.TargetMBean` references return field.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/foreignJNDIPProviderCreateForm

This resource manages the create forms for the foreignJNDIPProviders collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.ForeignJNDIPProviderMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the [foreignJNDIPProviders](#) collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ForeignJNDIPProviderMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/foreignJNDIPProviderCreateForm](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/foreignJNDIPProviders](#) **rel=create**
The collection resource for this create form resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/foreignJNDIPProviderCreateForm](#) **rel=self**
This resource.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/foreignJNDIProviders

This resource manages a collection of [weblogic.management.configuration.ForeignJNDIProviderMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.ForeignJNDIProviderMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.ForeignJNDIProviderMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/foreignJNDIProviders](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/foreignJNDIProviderCreateForm](#) **rel=create-form**
The create form resource for this collection resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/foreignJNDIProviders](#) **rel=self**
This resource.

POST

Add a new [weblogic.management.configuration.ForeignJNDIPProviderMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.ForeignJNDIPProviderMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/foreignJNDIProviders/{name}

This resource manages a [weblogic.management.configuration.ForeignJNDIProviderMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

DELETE

Delete this [weblogic.management.configuration.ForeignJNDIProviderMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.ForeignJNDIProviderMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ForeignJNDIProviderMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/foreignJNDIProviders/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/foreignJNDIProviders/{name}/foreignJNDILinkCreateForm **rel**=foreignJNDILinkCreateForm

The create form resource for this resource's foreignJNDILinks collection resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/foreignJNDIProviders/{name}/foreignJNDILinks **rel**=foreignJNDILinks

This resource's foreignJNDILinks collection resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/foreignJNDIProviders **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/foreignJNDIProviders/{name} **rel**=self

This resource.

POST

Update this [weblogic.management.configuration.ForeignJNDIProviderMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.ForeignJNDIProviderMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/foreignJNDIProviders/{name}/foreignJNDILinkCreateForm

This resource manages the create forms for the foreignJNDILinks collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.ForeignJNDILinkMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the `foreignJNDILinks` collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ForeignJNDILinkMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/foreignJNDIProviders/{name}/foreignJNDILinkCreateForm](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/foreignJNDIProviders/{name}/foreignJNDILinks](#) **rel**=create

The collection resource for this create form resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/foreignJNDIProviders/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/foreignJNDIProviders/{name}/foreignJNDILinkCreateForm](#) **rel**=self

This resource.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/foreignJNDIProviders/{name}/foreignJNDILinks

This resource manages a collection of [weblogic.management.configuration.ForeignJNDILinkMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of `weblogic.management.configuration.ForeignJNDILinkMBean` instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of `weblogic.management.configuration.ForeignJNDILinkMBean` entities.

This method can return the following links:

- `uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/foreignJNDIProviders/{name}/foreignJNDILinks` `rel=canonical`

This resource.

- `uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/foreignJNDIProviders/{name}/foreignJNDILinkCreateForm` `rel=create-form`

The create form resource for this collection resource.

- `uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/foreignJNDIProviders/{name}` `rel=parent`

The parent resource of this resource.

- `uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/foreignJNDIProviders/{name}/foreignJNDILinks` `rel=self`

This resource.

POST

Add a new [weblogic.management.configuration.ForeignJNDILinkMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.ForeignJNDILinkMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/foreignJNDIProviders/{name}/foreignJNDILinks/{name}

This resource manages a [weblogic.management.configuration.ForeignJNDILinkMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.ForeignJNDILinkMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.ForeignJNDILinkMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ForeignJNDILinkMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/foreignJNDIProviders/{name}/foreignJNDILinks/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/foreignJNDIProviders/{name}/foreignJNDILinks](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/foreignJNDIProviders/{name}/foreignJNDILinks/{name}](#) **rel**=self

This resource.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/foreignJNDIProviders/{name}/foreignJNDIL-

POST

Update this [weblogic.management.configuration.ForeignJNDILinkMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.ForeignJNDILinkMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCStoreCreateForm

This resource manages the create forms for the JDBCStores collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.JDBCStoreMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the JDBCStores collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.JDBCStoreMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCStoreCreateForm rel=canonical](#)

This resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCStores rel=create](#)

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name} rel=parent](#)

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCStoreCreateForm rel=self](#)

This resource.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCStores

This resource manages a collection of [weblogic.management.configuration.JDBCStoreMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.JDBCStoreMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.JDBCStoreMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCStores](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCStoreCreateForm](#) **rel=create-form**
The create form resource for this collection resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCStores](#) **rel=self**
This resource.

POST

Add a new [weblogic.management.configuration.JDBCStoreMBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.JDBCStoreMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCStores/{name}

This resource manages a [weblogic.management.configuration.JDBCStoreMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.JDBCStoreMBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.management.configuration.JDBCStoreMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.JDBCStoreMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCStores/{name}](#) **rel**=canonical
This resource.
- **rel**=dataSource
This resource's dataSource reference to a [weblogic.management.configuration.JDBCSystemResourceMBean](#) resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCStores](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCStores/{name}](#) **rel**=self
This resource.

POST

Update this [weblogic.management.configuration.JDBCStoreMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.JDBCStoreMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResourceCreateForm

This resource manages the create forms for the JDBCSystemResources collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.JDBCSystemResourceMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the [JDBCSystemResources](#) collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.JDBCSystemResourceMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResourceCreateForm](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources](#) **rel**=create

The collection resource for this create form resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResourceCreateForm](#) **rel**=self

This resource.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources

This resource manages a collection of [weblogic.management.configuration.JDBCSystemResourceMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.JDBCSystemResourceMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.JDBCSystemResourceMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResourceCreateForm](#) **rel**=create-form

The create form resource for this collection resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources](#) **rel**=self

This resource.

POST

Add a new [weblogic.management.configuration.JDBCSystemResourceMBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.JDBCSystemResourceMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources/{name}

This resource manages a [weblogic.management.configuration.JDBCSystemResourceMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.JDBCSystemResourceMBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.management.configuration.JDBCSystemResourceMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.JDBCSystemResourceMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource](#) **rel**=JDBCResource
This resource's JDBCResource singleton resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources/{name}](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources](#) **rel**=parent
The parent resource of this resource.
- **rel**=resource
This resource's resource reference to a [weblogic.descriptor.DescriptorBean](#) resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources/{name}](#) **rel**=self
This resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources/{name}/subDeploymentCreateForm](#) **rel**=subDeploymentCreateForm
The create form resource for this resource's subDeployments collection resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources/{name}/subDeployments](#) **rel**=subDeployments
This resource's subDeployments collection resource.

POST

Update this [weblogic.management.configuration.JDBCSystemResourceMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.JDBCSystemResourceMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource

This resource manages a [weblogic.j2ee.descriptor.wl.JDBCDataSourceBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.JDBCDataSourceBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.JDBCDataSourceBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource/JDBCConnectionPoolParams rel=JDBCConnectionPoolParams](#)
This resource's JDBCConnectionPoolParams singleton resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource/JDBCDataSourceParams rel=JDBCDataSourceParams](#)
This resource's JDBCDataSourceParams singleton resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource/JBCDriverParams rel=JBCDriverParams](#)
This resource's JBCDriverParams singleton resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource/JBCOracleParams rel=JBCOracleParams](#)
This resource's JBCOracleParams singleton resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource/JBCXAParams rel=JBCXAParams](#)
This resource's JBCXAParams singleton resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource rel=canonical](#)
This resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource/internalProperties rel=internalProperties](#)
This resource's internalProperties singleton resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources/{name} rel=parent](#)
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource rel=self](#)
This resource.

POST

Update this [weblogic.j2ee.descriptor.wl.JDBCDataSourceBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.JDBCDataSourceBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource/internalProperties

This resource manages a [weblogic.j2ee.descriptor.wl.JDBCPropertiesBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.j2ee.descriptor.wl.JDBCPropertiesBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.JDBCPropertiesBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource/internalProperties](#)
rel=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource/internalProperties/properties](#) **rel**=properties

This resource's properties collection resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource/internalProperties/propertyCreateForm](#) **rel**=propertyCreateForm

The create form resource for this resource's properties collection resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource/internalProperties](#) **rel**=self

This resource.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource/internalProperties/properties

This resource manages a collection of [weblogic.j2ee.descriptor.wl.JDBCPropertyBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.j2ee.descriptor.wl.JDBCPropertyBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.j2ee.descriptor.wl.JDBCPropertyBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource/internalProperties/properties](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource/internalProperties/propertyCreateForm](#) **rel**=create-form

The create form resource for this collection resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource/internalProperties](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource/internalProperties/properties](#) **rel**=self

This resource.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResourc

POST

Add a new [weblogic.j2ee.descriptor.wl.JDBCPropertyBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.JDBCPropertyBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource/internalProperties/properties/{name}

This resource manages a [weblogic.j2ee.descriptor.wl.JDBCPropertyBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.j2ee.descriptor.wl.JDBCPropertyBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.j2ee.descriptor.wl.JDBCPropertyBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.JDBCPropertyBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource/internalProperties/properties/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource/internalProperties/properties](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource/internalProperties/properties/{name}](#) **rel**=self

This resource.

POST

Update this [weblogic.j2ee.descriptor.wl.JDBCPropertyBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.JDBCPropertyBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource/internalProperties/property CreateForm

This resource manages the create forms for the properties collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.j2ee.descriptor.wl.JDBCPropertyBean](#) entity populated with default values that can be customized then posted (using the POST method) to the properties collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.JDBCPropertyBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource/internalProperties/propertyCreateForm **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource/internalProperties/properties **rel**=create

The collection resource for this create form resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource/internalProperties **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource/internalProperties/propertyCreateForm **rel**=self

This resource.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource/JDBCConnectionPoolParams

This resource manages a [weblogic.j2ee.descriptor.wl.JDBCConnectionPoolParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.JDBCConnectionPoolParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.JDBCConnectionPoolParamsBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource/JDBCConnectionPoolParams](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource/JDBCConnectionPoolParams](#) **rel=self**

This resource.

POST

Update this [weblogic.j2ee.descriptor.wl.JDBCConnectionPoolParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.JDBCConnectionPoolParamsBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource/JDBCDataSourceParams

This resource manages a [weblogic.j2ee.descriptor.wl.JDBCDataSourceParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.JDBCDataSourceParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.JDBCDataSourceParamsBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource/JDBCDataSourceParams](#)
rel=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource/JDBCDataSourceParams](#)
rel=self

This resource.

POST

Update this [weblogic.j2ee.descriptor.wl.JDBCDataSourceParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.JDBCDataSourceParamsBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource/JDBCResourceParams

This resource manages a [weblogic.j2ee.descriptor.wl.JDBCResourceParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.JDBCResource](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.JDBCResource](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource/JDBCResource
rel=canonical
This resource.
- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource
rel=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource/JDBCResource/JDBCResource/properties
rel=properties
This resource's properties singleton resource.
- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource/JDBCResource
rel=self
This resource.

POST

Update this [weblogic.j2ee.descriptor.wl.JDBCDataSourceParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.JDBCDataSourceParamsBean](#) entity.

GET

Get this [weblogic.j2ee.descriptor.wl.JDBCPropertiesBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.JDBCPropertiesBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource/JDBCDriverParams/properties rel=canonical](#)

This resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource/JDBCDriverParams rel=parent](#)

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource/JDBCDriverParams/properties/properties rel=properties](#)

This resource's properties collection resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource/JDBCDriverParams/properties/propertyCreateForm rel=propertyCreateForm](#)

The create form resource for this resource's properties collection resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource/JDBCDriverParams/properties rel=self](#)

This resource.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResourc

POST

Add a new [weblogic.j2ee.descriptor.wl.JDBCPropertyBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.JDBCPropertyBean](#) entity.

DELETE

Delete this [weblogic.j2ee.descriptor.wl.JDBCPropertyBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.j2ee.descriptor.wl.JDBCPropertyBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.JDBCPropertyBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource/JDBCDriverParams/properties/properties/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource/JDBCDriverParams/properties/properties](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource/JDBCDriverParams/properties/properties/{name}](#) **rel**=self

This resource.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResourc

POST

Update this [weblogic.j2ee.descriptor.wl.JDBCPropertyBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.JDBCPropertyBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource/JDBCDriverParams/properties/propertyCreateForm

This resource manages the create forms for the properties collection resource.

The resource supports the following methods:

- [GET](#)

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource/JDBCOracleParams

This resource manages a [weblogic.j2ee.descriptor.wl.JDBCOracleParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.JDBCOracleParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.JDBCOracleParamsBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource/JDBCOracleParams
rel=canonical
This resource.
- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource/JDBCOracleParams **rel**=self
This resource.

POST

Update this [weblogic.j2ee.descriptor.wl.JDBCOracleParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.JDBCOracleParamsBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource/JDBCXAParams

This resource manages a [weblogic.j2ee.descriptor.wl.JDBCXAParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.JDBCXAParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.JDBCXAParamsBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource/JDBCXAParams](#)
rel=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource/JDBCXAParams](#) **rel**=self

This resource.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResourc

POST

Update this [weblogic.j2ee.descriptor.wl.JDBCXAParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.JDBCXAParamsBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources/{name}/subDeploymentCreateForm

This resource manages the create forms for the subDeployments collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.SubDeploymentMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the subDeployments collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources/{name}/subDeploymentCreateForm **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources/{name}/subDeployments **rel**=create

The collection resource for this create form resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources/{name}/subDeploymentCreateForm **rel**=self

This resource.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources/{name}/subDeployments

This resource manages a collection of [weblogic.management.configuration.SubDeploymentMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.SubDeploymentMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.SubDeploymentMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources/{name}/subDeployments **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources/{name}/subDeploymentCreateForm **rel**=create-form

The create form resource for this collection resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources/{name}/subDeployments **rel**=self

This resource.

POST

Add a new [weblogic.management.configuration.SubDeploymentMBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources/{name}/subDeployments/{name}

This resource manages a [weblogic.management.configuration.SubDeploymentMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources/{name}/subDeployments/{name} **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources/{name}/subDeployments **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources/{name}/subDeployments/{name} **rel**=self
This resource.
- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources/{name}/subDeployments/{name}/subDeployments **rel**=subDeployments
This resource's subDeployments collection resource.

POST

Update this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources/{name}/subDeployments/{name}/subDeployments

This resource manages a collection of [weblogic.management.configuration.SubDeploymentMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.configuration.SubDeploymentMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.SubDeploymentMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources/{name}/subDeployments/{name}/subDeployments](#)
rel=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources/{name}/subDeployments/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources/{name}/subDeployments/{name}/subDeployments](#)
rel=self

This resource.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources/{name}/subDeployments/{name}/subDeployments/{name}

This resource manages a [weblogic.management.configuration.SubDeploymentMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources/{name}/subDeployments/{name}/subDeployments/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources/{name}/subDeployments/{name}/subDeployments](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources/{name}/subDeployments/{name}/subDeployments/{name}](#) **rel**=self

This resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources/{name}/subDeployments/{name}/subDeployments/{name}/subDeployments](#) **rel**=subDeployments

This resource's subDeployments collection resource.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JDBCSystemResources/{name}/subDeploymen

POST

Update this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSBridgeDestinationCreateForm

This resource manages the create forms for the JMSBridgeDestinations collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.JMSBridgeDestinationMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the [JMSBridgeDestinations](#) collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.JMSBridgeDestinationMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSBridgeDestinationCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSBridgeDestinations](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSBridgeDestinationCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSBridgeDestinations

This resource manages a collection of [weblogic.management.configuration.JMSBridgeDestinationMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.JMSBridgeDestinationMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.JMSBridgeDestinationMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSBridgeDestinations](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSBridgeDestinationCreateForm](#) **rel=create-form**
The create form resource for this collection resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSBridgeDestinations](#) **rel=self**
This resource.

POST

Add a new [weblogic.management.configuration.JMSBridgeDestinationMBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.JMSBridgeDestinationMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSBridgeDestinations/{name}

This resource manages a [weblogic.management.configuration.JMSBridgeDestinationMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.JMSBridgeDestinationMBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.management.configuration.JMSBridgeDestinationMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.JMSBridgeDestinationMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSBridgeDestinations/{name}](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSBridgeDestinations](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSBridgeDestinations/{name}](#) **rel=self**

This resource.

POST

Update this [weblogic.management.configuration.JMSBridgeDestinationMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.JMSBridgeDestinationMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSServerCreateForm

This resource manages the create forms for the JMSservers collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.JMSServerMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the JMSServers collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.JMSServerMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSServerCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSServers](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSServerCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSServers

This resource manages a collection of [weblogic.management.configuration.JMSServerMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.JMSServerMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.JMSServerMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSServers](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSServerCreateForm](#) **rel=create-form**

The create form resource for this collection resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSServers](#) **rel=self**

This resource.

POST

Add a new [weblogic.management.configuration.JMSServerMBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.JMSServerMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSServers/{name}

This resource manages a [weblogic.management.configuration.JMSServerMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.JMSServerMBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.management.configuration.JMSServerMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.JMSServerMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSServers/{name}/JMSMessageLogFile](#) **rel**=JMSMessageLogFile
This resource's JMSMessageLogFile singleton resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSServers/{name}](#) **rel**=canonical
This resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSServers](#) **rel**=parent
The parent resource of this resource.
- **rel**=persistentStore
This resource's persistentStore reference to a [weblogic.management.configuration.PersistentStoreMBean](#) resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSServers/{name}](#) **rel**=self
This resource.

POST

Update this [weblogic.management.configuration.JMSServerMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.JMSServerMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSServers/{name}/JMSMessageLogFile

This resource manages a [weblogic.management.configuration.JMSMessageLogFileMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.JMSMessageLogFileMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.JMSMessageLogFileMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSServers/{name}/JMSMessageLogFile **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSServers/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSServers/{name}/JMSMessageLogFile **rel**=self

This resource.

POST

POST

Update this [weblogic.management.configuration.JMSMessageLogFileMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.JMSMessageLogFileMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResourceCreateForm

This resource manages the create forms for the JMSSystemResources collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.JMSSystemResourceMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the JMSSystemResources collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.JMSSystemResourceMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResourceCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResourceCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources

This resource manages a collection of [weblogic.management.configuration.JMSSystemResourceMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.JMSSystemResourceMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.JMSSystemResourceMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResourceCreateForm](#) **rel**=create-form

The create form resource for this collection resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources](#) **rel**=self

This resource.

POST

Add a new [weblogic.management.configuration.JMSSystemResourceMBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.JMSSystemResourceMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}

This resource manages a [weblogic.management.configuration.JMSSystemResourceMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.JMSSystemResourceMBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.management.configuration.JMSSystemResourceMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.JMSSystemResourceMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource](#) **rel**=JMSResource
This resource's JMSResource singleton resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources](#) **rel**=parent
The parent resource of this resource.
- **rel**=resource
This resource's resource reference to a [weblogic.descriptor.DescriptorBean](#) resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}](#) **rel**=self
This resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/subDeploymentCreateForm](#) **rel**=subDeploymentCreateForm
The create form resource for this resource's subDeployments collection resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/subDeployments](#) **rel**=subDeployments
This resource's subDeployments collection resource.

POST

Update this [weblogic.management.configuration.JMSSystemResourceMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.JMSSystemResourceMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource

This resource manages a [weblogic.j2ee.descriptor.wl.JMSBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.JMSBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.JMSBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFErrorHandlingCreateForm](#) [rel=SAFErrorHandlingCreateForm](#)

The create form resource for this resource's SAFErrorHandlings collection resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFErrorHandlings](#) [rel=SAFErrorHandlings](#)

This resource's SAFErrorHandlings collection resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinationCreateForm](#) [rel=SAFImportedDestinationCreateForm](#)

The create form resource for this resource's SAFImportedDestinations collection resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations](#) [rel=SAFImportedDestinations](#)

This resource's SAFImportedDestinations collection resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFRemoteContextCreateForm](#) [rel=SAFRemoteContextCreateForm](#)

The create form resource for this resource's SAFRemoteContexts collection resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFRemoteContexts](#) [rel=SAFRemoteContexts](#)

This resource's SAFRemoteContexts collection resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource](#) [rel=canonical](#)

This resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories](#) [rel=connectionFactories](#)

This resource's connectionFactories collection resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/connectionFactoryCreateForm
rel=connectionFactoryCreateForm
The create form resource for this resource's connectionFactories collection resource.
- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/destinationKeyCreateForm
rel=destinationKeyCreateForm
The create form resource for this resource's destinationKeys collection resource.
- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/destinationKeys
rel=destinationKeys
This resource's destinationKeys collection resource.
- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServerCreateForm
rel=foreignServerCreateForm
The create form resource for this resource's foreignServers collection resource.
- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers
rel=foreignServers
This resource's foreignServers collection resource.
- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name} **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/queueCreateForm
rel=queueCreateForm
The create form resource for this resource's queues collection resource.
- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/queues **rel**=queues
This resource's queues collection resource.
- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/quotaCreateForm
rel=quotaCreateForm
The create form resource for this resource's quotas collection resource.
- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/quotas **rel**=quotas
This resource's quotas collection resource.
- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource **rel**=self
This resource.
- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templateCreateForm
rel=templateCreateForm

The create form resource for this resource's templates collection resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates **rel**=templates

This resource's templates collection resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/topicCreateForm **rel**=topicCreateForm

The create form resource for this resource's topics collection resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/topics **rel**=topics

This resource's topics collection resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedQueueCreateForm **rel**=uniformDistributedQueueCreateForm

The create form resource for this resource's uniformDistributedQueues collection resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues **rel**=uniformDistributedQueues

This resource's uniformDistributedQueues collection resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopicCreateForm **rel**=uniformDistributedTopicCreateForm

The create form resource for this resource's uniformDistributedTopics collection resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics **rel**=uniformDistributedTopics

This resource's uniformDistributedTopics collection resource.

POST

Update this [weblogic.j2ee.descriptor.wl.JMSBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.JMSBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories

This resource manages a collection of [weblogic.j2ee.descriptor.wl.JMSConnectionFactoryBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.j2ee.descriptor.wl.JMSConnectionFactoryBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.j2ee.descriptor.wl.JMSConnectionFactoryBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories](#)
rel=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/connectionFactoryCreateForm](#)
rel=create-form

The create form resource for this collection resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories](#) **rel**=self

This resource.

POST

Add a new [weblogic.j2ee.descriptor.wl.JMSConnectionFactoryBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.JMSConnectionFactoryBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}

This resource manages a [weblogic.j2ee.descriptor.wl.JMSConnectionFactoryBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.j2ee.descriptor.wl.JMSConnectionFactoryBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.j2ee.descriptor.wl.JMSConnectionFactoryBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.JMSConnectionFactoryBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}/clientParams](#) **rel**=clientParams
This resource's clientParams singleton resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}/defaultDeliveryParams](#) **rel**=defaultDeliveryParams
This resource's defaultDeliveryParams singleton resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}/flowControlParams](#) **rel**=flowControlParams
This resource's flowControlParams singleton resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}/loadBalancingParams](#) **rel**=loadBalancingParams
This resource's loadBalancingParams singleton resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories](#)
rel=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}/securityParams](#) **rel**=securityParams
This resource's securityParams singleton resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}](#)
rel=self
This resource.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/c

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}/transactionParams **rel**=transactionParams

This resource's transactionParams singleton resource.

POST

Update this [weblogic.j2ee.descriptor.wl.JMSConnectionFactoryBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.JMSConnectionFactoryBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}/clientParams

This resource manages a [weblogic.j2ee.descriptor.wl.ClientParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.ClientParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.ClientParamsBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}/clientParams](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}/clientParams](#) **rel**=self

This resource.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/c

POST

Update this [weblogic.j2ee.descriptor.wl.ClientParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.ClientParamsBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}/defaultDeliveryParams

This resource manages a [weblogic.j2ee.descriptor.wl.DefaultDeliveryParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.DefaultDeliveryParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.DefaultDeliveryParamsBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}/defaultDeliveryParams **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}/defaultDeliveryParams **rel**=self

This resource.

POST

Update this [weblogic.j2ee.descriptor.wl.DefaultDeliveryParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.DefaultDeliveryParamsBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}/flowControlParams

This resource manages a [weblogic.j2ee.descriptor.wl.FlowControlParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.FlowControlParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.FlowControlParamsBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}/flowControlParams](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}/flowControlParams](#) **rel**=self

This resource.

POST

Update this [weblogic.j2ee.descriptor.wl.FlowControlParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.FlowControlParamsBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}/loadBalancingParams

This resource manages a [weblogic.j2ee.descriptor.wl.LoadBalancingParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.LoadBalancingParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.LoadBalancingParamsBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}/loadBalancingParams](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}/loadBalancingParams](#) **rel=self**

This resource.

POST

Update this [weblogic.j2ee.descriptor.wl.LoadBalancingParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.LoadBalancingParamsBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}/securityParams

This resource manages a [weblogic.j2ee.descriptor.wl.SecurityParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.SecurityParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.SecurityParamsBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}/securityParams](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}/securityParams](#) **rel**=self

This resource.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/c

POST

Update this [weblogic.j2ee.descriptor.wl.SecurityParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.SecurityParamsBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}/transactionParams

This resource manages a [weblogic.j2ee.descriptor.wl.TransactionParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.TransactionParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.TransactionParamsBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}/transactionParams **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}/transactionParams **rel**=self

This resource.

POST

Update this [weblogic.j2ee.descriptor.wl.TransactionParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.TransactionParamsBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/connectionFactoryCreateForm

This resource manages the create forms for the connectionFactories collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.j2ee.descriptor.wl.JMSConnectionFactoryBean](#) entity populated with default values that can be customized then posted (using the POST method) to the connectionFactories collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.JMSConnectionFactoryBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/connectionFactoryCreateForm
rel=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories
rel=create

The collection resource for this create form resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource
rel=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/connectionFactoryCreateForm
rel=self

This resource.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/destinationKeyCreateForm

This resource manages the create forms for the destinationKeys collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.j2ee.descriptor.wl.DestinationKeyBean](#) entity populated with default values that can be customized then posted (using the POST method) to the destinationKeys collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.DestinationKeyBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/destinationKeyCreateForm](#)
rel=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/destinationKeys](#) **rel**=create

The collection resource for this create form resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/destinationKeyCreateForm](#)
rel=self

This resource.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/destinationKeys

This resource manages a collection of [weblogic.j2ee.descriptor.wl.DestinationKeyBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.j2ee.descriptor.wl.DestinationKeyBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.j2ee.descriptor.wl.DestinationKeyBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/destinationKeys](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/destinationKeyCreateForm](#)
rel=create-form
The create form resource for this collection resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/destinationKeys](#) **rel**=self
This resource.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/d

POST

Add a new [weblogic.j2ee.descriptor.wl.DestinationKeyBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.DestinationKeyBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/destinationKeys/{name}

This resource manages a [weblogic.j2ee.descriptor.wl.DestinationKeyBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.j2ee.descriptor.wl.DestinationKeyBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.j2ee.descriptor.wl.DestinationKeyBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.DestinationKeyBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/destinationKeys/{name}](#)
rel=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/destinationKeys](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/destinationKeys/{name}](#)
rel=self

This resource.

POST

Update this [weblogic.j2ee.descriptor.wl.DestinationKeyBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.DestinationKeyBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServerCreateForm

This resource manages the create forms for the foreignServers collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.j2ee.descriptor.wl.ForeignServerBean](#) entity populated with default values that can be customized then posted (using the POST method) to the foreignServers collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.ForeignServerBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServerCreateForm
rel=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers **rel**=create

The collection resource for this create form resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServerCreateForm
rel=self

This resource.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers

This resource manages a collection of [weblogic.j2ee.descriptor.wl.ForeignServerBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.j2ee.descriptor.wl.ForeignServerBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.j2ee.descriptor.wl.ForeignServerBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServerCreateForm **rel**=create-form
The create form resource for this collection resource.
- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers **rel**=self
This resource.

POST

Add a new [weblogic.j2ee.descriptor.wl.ForeignServerBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.ForeignServerBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}

This resource manages a [weblogic.j2ee.descriptor.wl.ForeignServerBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.j2ee.descriptor.wl.ForeignServerBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.j2ee.descriptor.wl.ForeignServerBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.ForeignServerBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/JNDIProperties](#) **rel=JNDIProperties**
This resource's JNDIProperties collection resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/JNDIPropertyCreateForm](#) **rel=JNDIPropertyCreateForm**
The create form resource for this resource's JNDIProperties collection resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignConnectionFactories](#) **rel=foreignConnectionFactories**
This resource's foreignConnectionFactories collection resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignConnectionFactoryCreateForm](#) **rel=foreignConnectionFactoryCreateForm**
The create form resource for this resource's foreignConnectionFactories collection resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignDestinationCreateForm](#) **rel=foreignDestinationCreateForm**
The create form resource for this resource's foreignDestinations collection resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignDestinations](#) **rel=foreignDestinations**
This resource's foreignDestinations collection resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers](#) **rel=parent**
The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}
rel=self

This resource.

POST

Update this [weblogic.j2ee.descriptor.wl.ForeignServerBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.ForeignServerBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignConnectionFactories

This resource manages a collection of [weblogic.j2ee.descriptor.wl.ForeignConnectionFactoryBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.j2ee.descriptor.wl.ForeignConnectionFactoryBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.j2ee.descriptor.wl.ForeignConnectionFactoryBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignConnectionFactories](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignConnectionFactoryCreateForm](#) **rel=create-form**

The create form resource for this collection resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignConnectionFactories](#) **rel=self**

This resource.

POST

Add a new [weblogic.j2ee.descriptor.wl.ForeignConnectionFactoryBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.ForeignConnectionFactoryBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignConnectionFactories/{name}

This resource manages a [weblogic.j2ee.descriptor.wl.ForeignConnectionFactoryBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

DELETE

Delete this [weblogic.j2ee.descriptor.wl.ForeignConnectionFactoryBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.j2ee.descriptor.wl.ForeignConnectionFactoryBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.ForeignConnectionFactoryBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignConnectionFactories/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignConnectionFactories **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignConnectionFactories/{name} **rel**=self

This resource.

POST

Update this [weblogic.j2ee.descriptor.wl.ForeignConnectionFactoryBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.ForeignConnectionFactoryBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignConnectionFactoryCreateForm

This resource manages the create forms for the foreignConnectionFactories collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.j2ee.descriptor.wl.ForeignConnectionFactoryBean](#) entity populated with default values that can be customized then posted (using the POST method) to the `foreignConnectionFactories` collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.ForeignConnectionFactoryBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignConnectionFactoryCreateForm](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignConnectionFactories](#) **rel**=create

The collection resource for this create form resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}](#)
rel=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignConnectionFactoryCreateForm](#) **rel**=self

This resource.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignDestinationCreateForm

This resource manages the create forms for the foreignDestinations collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.j2ee.descriptor.wl.ForeignDestinationBean](#) entity populated with default values that can be customized then posted (using the POST method) to the `foreignDestinations` collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.ForeignDestinationBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignDestinationCreateForm](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignDestinations](#) **rel**=create

The collection resource for this create form resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}](#)
rel=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignDestinationCreateForm](#) **rel**=self

This resource.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignDestinations

This resource manages a collection of [weblogic.j2ee.descriptor.wl.ForeignDestinationBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.j2ee.descriptor.wl.ForeignDestinationBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.j2ee.descriptor.wl.ForeignDestinationBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignDestinations](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignDestinationCreateForm](#) **rel**=create-form

The create form resource for this collection resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}](#)
rel=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignDestinations](#) **rel**=self

This resource.

POST

Add a new [weblogic.j2ee.descriptor.wl.ForeignDestinationBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.ForeignDestinationBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignDestinations/{name}

This resource manages a [weblogic.j2ee.descriptor.wl.ForeignDestinationBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.j2ee.descriptor.wl.ForeignDestinationBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.j2ee.descriptor.wl.ForeignDestinationBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.ForeignDestinationBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignDestinations/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignDestinations](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignDestinations/{name}](#) **rel**=self

This resource.

POST

Update this [weblogic.j2ee.descriptor.wl.ForeignDestinationBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.ForeignDestinationBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/JNDIProperties

This resource manages a collection of [weblogic.j2ee.descriptor.wl.PropertyBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.j2ee.descriptor.wl.PropertyBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.j2ee.descriptor.wl.PropertyBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/JNDIProperties](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/JNDIPropertyCreateForm](#) **rel=create-form**

The create form resource for this collection resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/JNDIProperties](#) **rel=self**

This resource.

POST

Add a new [weblogic.j2ee.descriptor.wl.PropertyBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.PropertyBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/JNDIPr operties/{key}

This resource manages a [weblogic.j2ee.descriptor.wl.PropertyBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.j2ee.descriptor.wl.PropertyBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.j2ee.descriptor.wl.PropertyBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.PropertyBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/JNDIProperties/{key} rel=canonical](#)

This resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/JNDIProperties rel=parent](#)

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/JNDIProperties/{key} rel=self](#)

This resource.

POST

Update this [weblogic.j2ee.descriptor.wl.PropertyBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.PropertyBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/JNDIPropertyCreateForm

This resource manages the create forms for the JNDIProperties collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.j2ee.descriptor.wl.PropertyBean](#) entity populated with default values that can be customized then posted (using the POST method) to the JNDIProperties collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.PropertyBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/JNDIPropertyCreateForm **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/JNDIProperties **rel**=create

The collection resource for this create form resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/JNDIPropertyCreateForm **rel**=self

This resource.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/queueCreateForm

This resource manages the create forms for the queues collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.j2ee.descriptor.wl.QueueBean](#) entity populated with default values that can be customized then posted (using the POST method) to the queues collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.QueueBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/queuecreateForm **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/queues **rel**=create

The collection resource for this create form resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/queuecreateForm **rel**=self

This resource.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/queues

This resource manages a collection of [weblogic.j2ee.descriptor.wl.QueueBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.j2ee.descriptor.wl.QueueBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.j2ee.descriptor.wl.QueueBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/queues](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/queuecreateForm](#) **rel**=create-form

The create form resource for this collection resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/queues](#) **rel**=self

This resource.

POST

Add a new [weblogic.j2ee.descriptor.wl.QueueBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.QueueBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/queues/{name}

This resource manages a [weblogic.j2ee.descriptor.wl.QueueBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.j2ee.descriptor.wl.QueueBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.j2ee.descriptor.wl.QueueBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.QueueBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/queues/{name}](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/queues/{name}/deliveryFailureParams](#) **rel=deliveryFailureParams**
This resource's [deliveryFailureParams](#) singleton resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/queues/{name}/deliveryParamsOverrides](#) **rel=deliveryParamsOverrides**
This resource's [deliveryParamsOverrides](#) singleton resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/queues/{name}/messageLoggingParams](#) **rel=messageLoggingParams**
This resource's [messageLoggingParams](#) singleton resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/queues](#) **rel=parent**
The parent resource of this resource.
- **rel=quota**
This resource's [quota](#) reference to a [weblogic.j2ee.descriptor.wl.QuotaBean](#) resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/queues/{name}](#) **rel=self**
This resource.
- **rel=template**
This resource's [template](#) reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/queues/{name}/thresholds](#) **rel=thresholds**
This resource's [thresholds](#) singleton resource.

POST

Update this [weblogic.j2ee.descriptor.wl.QueueBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.QueueBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/queues/{name}/deliveryFailureParams

This resource manages a [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/queues/{name}/deliveryFailureParams/findSubDeploymentName](#) **rel=action** **title=findSubDeploymentName**
This resource's findSubDeploymentName action resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/queues/{name}/deliveryFailureParams](#) **rel=canonical**
This resource.
- **rel=errorDestination**
This resource's errorDestination reference to a [weblogic.j2ee.descriptor.wl.DestinationBean](#) resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/queues/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/queues/{name}/deliveryFailureParams](#) **rel=self**
This resource.
- **rel=templateBean**
This resource's templateBean reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/queues/{name}/deliveryFailureParams/findSubDeploymentName

The resource supports the following methods:

- [POST](#)

POST

This is used to find the sub-deployment-name for this destination.

Roles

Admin, Deployer

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/queues/{name}/deliveryParamsOverrides

This resource manages a [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/queues/{name}/deliveryParamsOverrides](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/queues/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/queues/{name}/deliveryParamsOverrides](#) **rel**=self

This resource.

- **rel**=templateBean

This resource's templateBean reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/q

POST

Update this [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/queues/{name}/messageLoggingParams

This resource manages a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/queues/{name}/messageLoggingParams **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/queues/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/queues/{name}/messageLoggingParams **rel**=self

This resource.

- **rel**=templateBean

This resource's templateBean reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/queues/{name}/thresholds

This resource manages a [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/queues/{name}/thresholds](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/queues/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/queues/{name}/thresholds](#)
rel=self
This resource.
- **rel**=templateBean
This resource's templateBean reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/q

POST

Update this [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/quotaCreateForm

This resource manages the create forms for the quotas collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.j2ee.descriptor.wl.QuotaBean](#) entity populated with default values that can be customized then posted (using the POST method) to the quotas collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.QuotaBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/quotaCreateForm
rel=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/quotas **rel**=create

The collection resource for this create form resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/quotaCreateForm **rel**=self

This resource.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/quotas

This resource manages a collection of [weblogic.j2ee.descriptor.wl.QuotaBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.j2ee.descriptor.wl.QuotaBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.j2ee.descriptor.wl.QuotaBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/quotas **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/quotaCreateForm **rel**=create-form
The create form resource for this collection resource.
- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/quotas **rel**=self
This resource.

POST

Add a new [weblogic.j2ee.descriptor.wl.QuotaBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.QuotaBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/quotas/{name}

This resource manages a [weblogic.j2ee.descriptor.wl.QuotaBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.j2ee.descriptor.wl.QuotaBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.j2ee.descriptor.wl.QuotaBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.QuotaBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/quotas/{name}](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/quotas](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/quotas/{name}](#) **rel**=self
This resource.

POST

Update this [weblogic.j2ee.descriptor.wl.QuotaBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.QuotaBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFEErrorHandlingCreateForm

This resource manages the create forms for the SAFEErrorHandlings collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.j2ee.descriptor.wl.SAFErrorHandlingBean](#) entity populated with default values that can be customized then posted (using the POST method) to the SAFErrorHandlings collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.SAFErrorHandlingBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFErrorHandlingCreateForm **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFErrorHandlings **rel**=create

The collection resource for this create form resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFErrorHandlingCreateForm **rel**=self

This resource.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFEErrorHandlings

This resource manages a collection of [weblogic.j2ee.descriptor.wl.SAFEErrorHandlingBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.j2ee.descriptor.wl.SAFErrorHandlingBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.j2ee.descriptor.wl.SAFErrorHandlingBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFErrorHandlings](#)
rel=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFErrorHandlingCreateForm](#) **rel**=create-form

The create form resource for this collection resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFErrorHandlings](#) **rel**=self

This resource.

POST

Add a new [weblogic.j2ee.descriptor.wl.SAFEErrorHandlingBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.SAFEErrorHandlingBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFErrorHandlings/{name}

This resource manages a [weblogic.j2ee.descriptor.wl.SAFErrorHandlingBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.j2ee.descriptor.wl.SAFEErrorHandlingBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.j2ee.descriptor.wl.SAFErrorHandlingBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.SAFErrorHandlingBean](#) entity.

This method can return the following links:

- **rel**=SAFErrorDestination
This resource's SAFErrorDestination reference to a [weblogic.j2ee.descriptor.wl.SAFDestinationBean](#) resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFErrorHandlings/{name}](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFErrorHandlings](#)
rel=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFErrorHandlings/{name}](#)
rel=self
This resource.

POST

Update this [weblogic.j2ee.descriptor.wl.SAFEErrorHandlingBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.SAFEErrorHandlingBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinationCreateForm

This resource manages the create forms for the SAFImportedDestinations collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.j2ee.descriptor.wl.SAFImportedDestinationsBean](#) entity populated with default values that can be customized then posted (using the POST method) to the SAFImportedDestinations collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.SAFImportedDestinationsBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinationCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinationCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations

This resource manages a collection of [weblogic.j2ee.descriptor.wl.SAFImportedDestinationsBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.j2ee.descriptor.wl.SAFImportedDestinationsBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.j2ee.descriptor.wl.SAFImportedDestinationsBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinationCreateForm](#) **rel**=create-form

The create form resource for this collection resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations](#) **rel**=self

This resource.

POST

Add a new [weblogic.j2ee.descriptor.wl.SAFImportedDestinationsBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.SAFImportedDestinationsBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}

This resource manages a [weblogic.j2ee.descriptor.wl.SAFImportedDestinationsBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.j2ee.descriptor.wl.SAFImportedDestinationsBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.j2ee.descriptor.wl.SAFImportedDestinationsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.SAFImportedDestinationsBean](#) entity.

This method can return the following links:

- **rel=SAFErrorHandling**
This resource's SAFErrorHandling reference to a [weblogic.j2ee.descriptor.wl.SAFErrorHandlingBean](#) resource.
- **uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFQueueCreateForm rel=SAFQueueCreateForm**
The create form resource for this resource's SAFQueues collection resource.
- **uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFQueues rel=SAFQueues**
This resource's SAFQueues collection resource.
- **rel=SAFRemoteContext**
This resource's SAFRemoteContext reference to a [weblogic.j2ee.descriptor.wl.SAFRemoteContextBean](#) resource.
- **uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFTopicCreateForm rel=SAFTopicCreateForm**
The create form resource for this resource's SAFTopics collection resource.
- **uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFTopics rel=SAFTopics**
This resource's SAFTopics collection resource.
- **uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name} rel=canonical**
This resource.
- **uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/messageLoggingParams rel=messageLoggingParams**
This resource's messageLoggingParams singleton resource.
- **uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations rel=parent**

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name} **rel**=self

This resource.

POST

Update this [weblogic.j2ee.descriptor.wl.SAFImportedDestinationsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.SAFImportedDestinationsBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/messageLoggingParams

This resource manages a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/messageLoggingParams **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/messageLoggingParams **rel**=self

This resource.

- **rel**=templateBean

This resource's templateBean reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFQueueCreateForm

This resource manages the create forms for the SAFQueues collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.j2ee.descriptor.wl.SAFQueueBean](#) entity populated with default values that can be customized then posted (using the POST method) to the SAFQueues collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.SAFQueueBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFQueueCreateForm **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFQueues **rel**=create

The collection resource for this create form resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFQueueCreateForm **rel**=self

This resource.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFQueues

This resource manages a collection of [weblogic.j2ee.descriptor.wl.SAFQueueBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of `weblogic.j2ee.descriptor.wl.SAFQueueBean` instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of `weblogic.j2ee.descriptor.wl.SAFQueueBean` entities.

This method can return the following links:

- `uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFQueues` `rel=canonical`

This resource.

- `uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFQueueCreateForm` `rel=create-form`

The create form resource for this collection resource.

- `uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}` `rel=parent`

The parent resource of this resource.

- `uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFQueues` `rel=self`

This resource.

POST

Add a new [weblogic.j2ee.descriptor.wl.SAFQueueBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.SAFQueueBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFQueues/{name}

This resource manages a [weblogic.j2ee.descriptor.wl.SAFQueueBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.j2ee.descriptor.wl.SAFQueueBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.j2ee.descriptor.wl.SAFQueueBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.SAFQueueBean](#) entity.

This method can return the following links:

- **rel=SAFErrorHandling**
This resource's SAFErrorHandling reference to a [weblogic.j2ee.descriptor.wl.SAFErrorHandlingBean](#) resource.
- **uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFQueues/{name} rel=canonical**
This resource.
- **uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFQueues/{name}/messageLoggingParams rel=messageLoggingParams**
This resource's messageLoggingParams singleton resource.
- **uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFQueues rel=parent**
The parent resource of this resource.
- **uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFQueues/{name} rel=self**
This resource.

POST

Update this [weblogic.j2ee.descriptor.wl.SAFQueueBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.SAFQueueBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFQueues/{name}/messageLoggingParams

This resource manages a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFQueues/{name}/messageLoggingParams **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFQueues/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFQueues/{name}/messageLoggingParams **rel**=self

This resource.

- **rel**=templateBean

This resource's templateBean reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFTopicCreateForm

This resource manages the create forms for the SAFTopics collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.j2ee.descriptor.wl.SAFTopicBean](#) entity populated with default values that can be customized then posted (using the POST method) to the SAFTopics collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.SAFTopicBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFTopicCreateForm **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFTopics **rel**=create

The collection resource for this create form resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFTopicCreateForm **rel**=self

This resource.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFTopics

This resource manages a collection of [weblogic.j2ee.descriptor.wl.SAFTopicBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.j2ee.descriptor.wl.SAFTopicBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.j2ee.descriptor.wl.SAFTopicBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFTopics](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFTopicCreateForm](#) **rel**=create-form

The create form resource for this collection resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFTopics](#) **rel**=self

This resource.

POST

Add a new [weblogic.j2ee.descriptor.wl.SAFTopicBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.SAFTopicBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFTopics/{name}

This resource manages a [weblogic.j2ee.descriptor.wl.SAFTopicBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.j2ee.descriptor.wl.SAFTopicBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.j2ee.descriptor.wl.SAFTopicBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.SAFTopicBean](#) entity.

This method can return the following links:

- **rel=SAFErrorHandling**
This resource's SAFErrorHandling reference to a [weblogic.j2ee.descriptor.wl.SAFErrorHandlingBean](#) resource.
- **uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFTopics/{name} rel=canonical**
This resource.
- **uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFTopics/{name}/messageLoggingParams rel=messageLoggingParams**
This resource's messageLoggingParams singleton resource.
- **uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFTopics rel=parent**
The parent resource of this resource.
- **uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFTopics/{name} rel=self**
This resource.

POST

Update this [weblogic.j2ee.descriptor.wl.SAFTopicBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.SAFTopicBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFTopics/{name}/messageLoggingParams

This resource manages a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFTopics/{name}/messageLoggingParams **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFTopics/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFTopics/{name}/messageLoggingParams **rel**=self

This resource.

- **rel**=templateBean

This resource's templateBean reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFRemoteContextCreateForm

This resource manages the create forms for the SAFRemoteContexts collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.j2ee.descriptor.wl.SAFRemoteContextBean](#) entity populated with default values that can be customized then posted (using the POST method) to the SAFRemoteContexts collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.SAFRemoteContextBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFRemoteContextCreateForm](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFRemoteContexts](#) **rel**=create

The collection resource for this create form resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFRemoteContextCreateForm](#) **rel**=self

This resource.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFRemoteContexts

This resource manages a collection of [weblogic.j2ee.descriptor.wl.SAFRemoteContextBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.j2ee.descriptor.wl.SAFRemoteContextBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.j2ee.descriptor.wl.SAFRemoteContextBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFRemoteContexts](#)
rel=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFRemoteContextCreateForm](#) **rel**=create-form

The create form resource for this collection resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFRemoteContexts](#) **rel**=self

This resource.

POST

Add a new [weblogic.j2ee.descriptor.wl.SAFRemoteContextBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.SAFRemoteContextBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFRemoteContexts/{name}

This resource manages a [weblogic.j2ee.descriptor.wl.SAFRemoteContextBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.j2ee.descriptor.wl.SAFRemoteContextBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.j2ee.descriptor.wl.SAFRemoteContextBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.SAFRemoteContextBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFRemoteContexts/{name}/SAFLoginContext](#) **rel**=SAFLoginContext

This resource's SAFLoginContext singleton resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFRemoteContexts/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFRemoteContexts](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFRemoteContexts/{name}](#) **rel**=self

This resource.

POST

Update this [weblogic.j2ee.descriptor.wl.SAFRemoteContextBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.SAFRemoteContextBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFRemoteContexts/{name}/SAFLoginContext

This resource manages a [weblogic.j2ee.descriptor.wl.SAFLoginContextBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.SAFLoginContextBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.SAFLoginContextBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFRemoteContexts/{name}/SAFLoginContext **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFRemoteContexts/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFRemoteContexts/{name}/SAFLoginContext **rel**=self

This resource.

POST

Update this [weblogic.j2ee.descriptor.wl.SAFLoginContextBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.SAFLoginContextBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templateCreateForm

This resource manages the create forms for the templates collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.j2ee.descriptor.wl.TemplateBean](#) entity populated with default values that can be customized then posted (using the POST method) to the templates collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.TemplateBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templateCreateForm](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates](#) **rel**=create
The collection resource for this create form resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templateCreateForm](#) **rel**=self
This resource.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates

This resource manages a collection of [weblogic.j2ee.descriptor.wl.TemplateBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.j2ee.descriptor.wl.TemplateBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.j2ee.descriptor.wl.TemplateBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templateCreateForm](#) **rel**=create-form

The create form resource for this collection resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates](#) **rel**=self

This resource.

POST

Add a new [weblogic.j2ee.descriptor.wl.TemplateBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.TemplateBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}

This resource manages a [weblogic.j2ee.descriptor.wl.TemplateBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.j2ee.descriptor.wl.TemplateBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.j2ee.descriptor.wl.TemplateBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.TemplateBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/findErrorDestination](#) **rel=action** **title=findErrorDestination**
This resource's findErrorDestination action resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/deliveryFailureParams](#) **rel=deliveryFailureParams**
This resource's deliveryFailureParams singleton resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/deliveryParamsOverrides](#) **rel=deliveryParamsOverrides**
This resource's deliveryParamsOverrides singleton resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/groupParamCreateForm](#) **rel=groupParamCreateForm**
The create form resource for this resource's groupParams collection resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/groupParams](#) **rel=groupParams**
This resource's groupParams collection resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/messageLoggingParams](#) **rel=messageLoggingParams**
This resource's messageLoggingParams singleton resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/multicast](#) **rel=multicast**
This resource's multicast singleton resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates](#) **rel=parent**

The parent resource of this resource.

- **rel=quota**

This resource's quota reference to a weblogic.j2ee.descriptor.wl.QuotaBean resource.

- **uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name} rel=self**

This resource.

- **uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/thresholds rel=thresholds**

This resource's thresholds singleton resource.

- **uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/topicSubscriptionParams rel=topicSubscriptionParams**

This resource's topicSubscriptionParams singleton resource.

POST

Update this [weblogic.j2ee.descriptor.wl.TemplateBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.TemplateBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/deliveryFailureParams

This resource manages a [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/deliveryFailureParams/findSubDeploymentName](#) **rel**=action
title=findSubDeploymentName

This resource's findSubDeploymentName action resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/deliveryFailureParams](#) **rel**=canonical

This resource.

- **rel**=errorDestination

This resource's errorDestination reference to a [weblogic.j2ee.descriptor.wl.DestinationBean](#) resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/deliveryFailureParams](#) **rel**=self

This resource.

- **rel**=templateBean

This resource's templateBean reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/deliveryFailureParams/findSubDeploymentName

The resource supports the following methods:

- [POST](#)

POST

This is used to find the sub-deployment-name for this destination.

Roles

Admin, Deployer

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/deliveryParamsOverrides

This resource manages a [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/deliveryParamsOverrides **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/deliveryParamsOverrides **rel**=self

This resource.

- **rel**=templateBean

This resource's templateBean reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/findErrorDestination

The resource supports the following methods:

- [POST](#)

POST

Finds the name of the error destination to use when a destination comes from a specific group

Roles

Admin, Deployer

Request Body

Must contain a JSON object with the following fields:

subDeploymentName

The subDeployment for which to find the quota

Type: string

Response Body

Contains a JSON object with a `weblogic.j2ee.descriptor.wl.DestinationBean` reference return field.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/groupParamCreateForm

This resource manages the create forms for the groupParams collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.j2ee.descriptor.wl.GroupParamsBean](#) entity populated with default values that can be customized then posted (using the POST method) to the groupParams collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.GroupParamsBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/groupParamCreateForm rel=canonical](#)

This resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/groupParams rel=create](#)

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name} rel=parent](#)

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/groupParamCreateForm rel=self](#)

This resource.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/groupParams

This resource manages a collection of [weblogic.j2ee.descriptor.wl.GroupParamsBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.j2ee.descriptor.wl.GroupParamsBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.j2ee.descriptor.wl.GroupParamsBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/groupParams rel=canonical](#)

This resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/groupParamCreateForm rel=create-form](#)

The create form resource for this collection resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name} rel=parent](#)

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/groupParams rel=self](#)

This resource.

POST

Add a new [weblogic.j2ee.descriptor.wl.GroupParamsBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.GroupParamsBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/groupParams/{subDeploymentName}

This resource manages a [weblogic.j2ee.descriptor.wl.GroupParamsBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.j2ee.descriptor.wl.GroupParamsBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.j2ee.descriptor.wl.GroupParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.GroupParamsBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/groupParams/{subDeploymentName}](#) **rel**=canonical

This resource.

- **rel**=errorDestination

This resource's errorDestination reference to a [weblogic.j2ee.descriptor.wl.DestinationBean](#) resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/groupParams](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/groupParams/{subDeploymentName}](#) **rel**=self

This resource.

POST

Update this [weblogic.j2ee.descriptor.wl.GroupParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.GroupParamsBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/messageLoggingParams

This resource manages a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/messageLoggingParams **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name} **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/messageLoggingParams **rel**=self
This resource.
- **rel**=templateBean
This resource's templateBean reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/multicast

This resource manages a [weblogic.j2ee.descriptor.wl.MulticastParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.MulticastParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.MulticastParamsBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/multicast](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/multicast](#)
rel=self
This resource.
- **rel**=templateBean
This resource's templateBean reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.MulticastParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.MulticastParamsBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/thresholds

This resource manages a [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/thresholds
rel=canonical
This resource.
- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name} **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/thresholds
rel=self
This resource.
- **rel**=templateBean
This resource's templateBean reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/topicSubscriptionParams

This resource manages a [weblogic.j2ee.descriptor.wl.TopicSubscriptionParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.TopicSubscriptionParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.TopicSubscriptionParamsBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/topicSubscriptionParams](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/topicSubscriptionParams](#) **rel**=self

This resource.

- **rel**=templateBean

This resource's templateBean reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.TopicSubscriptionParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.TopicSubscriptionParamsBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/topicCreateForm

This resource manages the create forms for the topics collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.j2ee.descriptor.wl.TopicBean](#) entity populated with default values that can be customized then posted (using the POST method) to the topics collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.TopicBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/topicCreateForm
rel=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/topics **rel**=create

The collection resource for this create form resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/topicCreateForm **rel**=self

This resource.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/topics

This resource manages a collection of [weblogic.j2ee.descriptor.wl.TopicBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.j2ee.descriptor.wl.TopicBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.j2ee.descriptor.wl.TopicBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/topics **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/topicCreateForm **rel**=create-form

The create form resource for this collection resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/topics **rel**=self

This resource.

POST

Add a new [weblogic.j2ee.descriptor.wl.TopicBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.TopicBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/topics/{name}

This resource manages a [weblogic.j2ee.descriptor.wl.TopicBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

DELETE

Delete this [weblogic.j2ee.descriptor.wl.TopicBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.j2ee.descriptor.wl.TopicBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.TopicBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/topics/{name}](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/topics/{name}/deliveryFailureParams](#) **rel=deliveryFailureParams**
This resource's `deliveryFailureParams` singleton resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/topics/{name}/deliveryParamsOverrides](#) **rel=deliveryParamsOverrides**
This resource's `deliveryParamsOverrides` singleton resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/topics/{name}/messageLoggingParams](#) **rel=messageLoggingParams**
This resource's `messageLoggingParams` singleton resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/topics/{name}/multicast](#) **rel=multicast**
This resource's `multicast` singleton resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/topics](#) **rel=parent**
The parent resource of this resource.
- **rel=quota**
This resource's `quota` reference to a `weblogic.j2ee.descriptor.wl.QuotaBean` resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/topics/{name}](#) **rel=self**
This resource.
- **rel=template**
This resource's `template` reference to a `weblogic.j2ee.descriptor.wl.TemplateBean` resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/topics/{name}/thresholds
rel=thresholds

This resource's thresholds singleton resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/topics/{name}/topicSubscriptionParams **rel**=topicSubscriptionParams

This resource's topicSubscriptionParams singleton resource.

POST

Update this [weblogic.j2ee.descriptor.wl.TopicBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.TopicBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/topics/{name}/deliveryFailureParams

This resource manages a [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/topics/{name}/deliveryFailureParams/findSubDeploymentName **rel**=action **title**=findSubDeploymentName
This resource's findSubDeploymentName action resource.
- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/topics/{name}/deliveryFailureParams **rel**=canonical
This resource.
- **rel**=errorDestination
This resource's errorDestination reference to a [weblogic.j2ee.descriptor.wl.DestinationBean](#) resource.
- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/topics/{name} **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/topics/{name}/deliveryFailureParams **rel**=self
This resource.
- **rel**=templateBean
This resource's templateBean reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/topics/{name}/deliveryFailureParams/findSubDeploymentName

The resource supports the following methods:

- [POST](#)

POST

This is used to find the sub-deployment-name for this destination.

Roles

Admin, Deployer

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/topics/{name}/deliveryParams Overrides

This resource manages a [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/topics/{name}/deliveryParamsOverrides](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/topics/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/topics/{name}/deliveryParamsOverrides](#) **rel**=self

This resource.

- **rel**=templateBean

This resource's templateBean reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/topics/{name}/messageLoggingParams

This resource manages a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/topics/{name}/messageLoggingParams](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/topics/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/topics/{name}/messageLoggingParams](#) **rel=self**

This resource.

- **rel=templateBean**

This resource's `templateBean` reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/topics/{name}/multicast

This resource manages a [weblogic.j2ee.descriptor.wl.MulticastParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.MulticastParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.MulticastParamsBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/topics/{name}/multicast](#)
rel=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/topics/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/topics/{name}/multicast](#)
rel=self

This resource.

- **rel**=templateBean

This resource's templateBean reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.MulticastParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.MulticastParamsBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/topics/{name}/thresholds

This resource manages a [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/topics/{name}/thresholds
rel=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/topics/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/topics/{name}/thresholds
rel=self

This resource.

- **rel**=templateBean

This resource's templateBean reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/topics/{name}/topicSubscriptionParams

This resource manages a [weblogic.j2ee.descriptor.wl.TopicSubscriptionParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.TopicSubscriptionParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.TopicSubscriptionParamsBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/topics/{name}/topicSubscriptionParams](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/topics/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/topics/{name}/topicSubscriptionParams](#) **rel**=self

This resource.

- **rel**=templateBean

This resource's templateBean reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.TopicSubscriptionParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.TopicSubscriptionParamsBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedQueueCreateForm

This resource manages the create forms for the uniformDistributedQueues collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.j2ee.descriptor.wl.UniformDistributedQueueBean](#) entity populated with default values that can be customized then posted (using the POST method) to the `uniformDistributedQueues` collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.UniformDistributedQueueBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedQueueCreateForm **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues **rel**=create

The collection resource for this create form resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedQueueCreateForm **rel**=self

This resource.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues

This resource manages a collection of [weblogic.j2ee.descriptor.wl.UniformDistributedQueueBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.j2ee.descriptor.wl.UniformDistributedQueueBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.j2ee.descriptor.wl.UniformDistributedQueueBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues](#)
rel=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedQueueCreateForm](#) **rel**=create-form

The create form resource for this collection resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues](#)
rel=self

This resource.

POST

Add a new [weblogic.j2ee.descriptor.wl.UniformDistributedQueueBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.UniformDistributedQueueBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues/{name}

This resource manages a [weblogic.j2ee.descriptor.wl.UniformDistributedQueueBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

DELETE

Delete this [weblogic.j2ee.descriptor.wl.UniformDistributedQueueBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.j2ee.descriptor.wl.UniformDistributedQueueBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.UniformDistributedQueueBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues/{name}](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues/{name}/deliveryFailureParams](#) **rel=deliveryFailureParams**

This resource's `deliveryFailureParams` singleton resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues/{name}/deliveryParamsOverrides](#) **rel=deliveryParamsOverrides**

This resource's `deliveryParamsOverrides` singleton resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues/{name}/messageLoggingParams](#) **rel=messageLoggingParams**

This resource's `messageLoggingParams` singleton resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues](#) **rel=parent**

The parent resource of this resource.

- **rel=quota**

This resource's quota reference to a [weblogic.j2ee.descriptor.wl.QuotaBean](#) resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues/{name}](#) **rel=self**

This resource.

- **rel=template**

This resource's template reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues/{name}/thresholds](#) **rel=thresholds**

This resource's thresholds singleton resource.

POST

Update this [weblogic.j2ee.descriptor.wl.UniformDistributedQueueBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.UniformDistributedQueueBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues/{name}/deliveryFailureParams

This resource manages a [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues/{name}/deliveryFailureParams/findSubDeploymentName **rel**=action
title=findSubDeploymentName

This resource's findSubDeploymentName action resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues/{name}/deliveryFailureParams **rel**=canonical

This resource.

- **rel**=errorDestination

This resource's errorDestination reference to a [weblogic.j2ee.descriptor.wl.DestinationBean](#) resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues/{name}/deliveryFailureParams **rel**=self

This resource.

- **rel**=templateBean

This resource's templateBean reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues/{name}/deliveryFailureParams/findSubDeploymentName

The resource supports the following methods:

- [POST](#)

POST

This is used to find the sub-deployment-name for this destination.

Roles

Admin, Deployer

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues/{name}/deliveryParamsOverrides

This resource manages a [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues/{name}/deliveryParamsOverrides](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues/{name}/deliveryParamsOverrides](#) **rel**=self

This resource.

- **rel**=templateBean

This resource's templateBean reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/u

POST

Update this [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues/{name}/messageLoggingParams

This resource manages a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues/{name}/messageLoggingParams **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues/{name}/messageLoggingParams **rel**=self

This resource.

- **rel**=templateBean

This resource's templateBean reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues/{name}/thresholds

This resource manages a [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues/{name}/thresholds](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues/{name}/thresholds](#) **rel**=self

This resource.

- **rel**=templateBean

This resource's templateBean reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopicCreateForm

This resource manages the create forms for the uniformDistributedTopics collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.j2ee.descriptor.wl.UniformDistributedTopicBean](#) entity populated with default values that can be customized then posted (using the POST method) to the `uniformDistributedTopics` collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.UniformDistributedTopicBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopicCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopicCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics

This resource manages a collection of [weblogic.j2ee.descriptor.wl.UniformDistributedTopicBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.j2ee.descriptor.wl.UniformDistributedTopicBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.j2ee.descriptor.wl.UniformDistributedTopicBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics](#)
rel=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopicCreateForm](#) **rel**=create-form

The create form resource for this collection resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics](#)
rel=self

This resource.

POST

Add a new [weblogic.j2ee.descriptor.wl.UniformDistributedTopicBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.UniformDistributedTopicBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}

This resource manages a [weblogic.j2ee.descriptor.wl.UniformDistributedTopicBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.j2ee.descriptor.wl.UniformDistributedTopicBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.j2ee.descriptor.wl.UniformDistributedTopicBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.UniformDistributedTopicBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}/deliveryFailureParams](#) **rel=deliveryFailureParams**
This resource's `deliveryFailureParams` singleton resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}/deliveryParamsOverrides](#) **rel=deliveryParamsOverrides**
This resource's `deliveryParamsOverrides` singleton resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}/messageLoggingParams](#) **rel=messageLoggingParams**
This resource's `messageLoggingParams` singleton resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}/multicast](#) **rel=multicast**
This resource's `multicast` singleton resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics](#) **rel=parent**
The parent resource of this resource.
- **rel=quota**
This resource's quota reference to a [weblogic.j2ee.descriptor.wl.QuotaBean](#) resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}](#) **rel=self**
This resource.
- **rel=template**

This resource's template reference to a `weblogic.j2ee.descriptor.wl.TemplateBean` resource.

- **uri**=`/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}/thresholds` **rel**=`thresholds`

This resource's `thresholds` singleton resource.

- **uri**=`/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}/topicSubscriptionParams` **rel**=`topicSubscriptionParams`

This resource's `topicSubscriptionParams` singleton resource.

POST

Update this [weblogic.j2ee.descriptor.wl.UniformDistributedTopicBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.UniformDistributedTopicBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}/deliveryFailureParams

This resource manages a [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}/deliveryFailureParams/findSubDeploymentName **rel**=action
title=findSubDeploymentName

This resource's findSubDeploymentName action resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}/deliveryFailureParams **rel**=canonical

This resource.

- **rel**=errorDestination

This resource's errorDestination reference to a [weblogic.j2ee.descriptor.wl.DestinationBean](#) resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}/deliveryFailureParams **rel**=self

This resource.

- **rel**=templateBean

This resource's templateBean reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}/deliveryFailureParams/findSubDeploymentName

The resource supports the following methods:

- [POST](#)

POST

This is used to find the sub-deployment-name for this destination.

Roles

Admin, Deployer

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}/deliveryParamsOverrides

This resource manages a [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}/deliveryParamsOverrides](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}/deliveryParamsOverrides](#) **rel**=self

This resource.

- **rel**=templateBean

This resource's templateBean reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/u

POST

Update this [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}/messageLoggingParams

This resource manages a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}/messageLoggingParams **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}/messageLoggingParams **rel**=self

This resource.

- **rel**=templateBean

This resource's templateBean reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}/multicast

This resource manages a [weblogic.j2ee.descriptor.wl.MulticastParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.MulticastParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.MulticastParamsBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}/multicast](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}/multicast](#) **rel**=self

This resource.

- **rel**=templateBean

This resource's templateBean reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/u

POST

Update this [weblogic.j2ee.descriptor.wl.MulticastParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.MulticastParamsBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}/thresholds

This resource manages a [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}/thresholds](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}/thresholds](#) **rel=self**

This resource.

- **rel=templateBean**

This resource's `templateBean` reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}/topicSubscriptionParams

This resource manages a [weblogic.j2ee.descriptor.wl.TopicSubscriptionParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.TopicSubscriptionParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.TopicSubscriptionParamsBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}/topicSubscriptionParams](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}/topicSubscriptionParams](#) **rel**=self

This resource.

- **rel**=templateBean

This resource's templateBean reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.TopicSubscriptionParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.TopicSubscriptionParamsBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/subDeploymentCreateForm

This resource manages the create forms for the subDeployments collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.SubDeploymentMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the subDeployments collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/subDeploymentCreateForm **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/subDeployments **rel**=create

The collection resource for this create form resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/subDeploymentCreateForm **rel**=self

This resource.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/subDeployments

This resource manages a collection of [weblogic.management.configuration.SubDeploymentMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.SubDeploymentMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.SubDeploymentMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/subDeployments **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/subDeploymentCreateForm **rel**=create-form

The create form resource for this collection resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/subDeployments **rel**=self

This resource.

POST

Add a new [weblogic.management.configuration.SubDeploymentMBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/subDeployments/{name}

This resource manages a [weblogic.management.configuration.SubDeploymentMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/subDeployments/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/subDeployments **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/subDeployments/{name} **rel**=self

This resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/subDeployments/{name}/subDeployments **rel**=subDeployments

This resource's subDeployments collection resource.

POST

Update this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/subDeployments/{name}/subDeployments

This resource manages a collection of [weblogic.management.configuration.SubDeploymentMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.configuration.SubDeploymentMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.SubDeploymentMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/subDeployments/{name}/subDeployments](#)
rel=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/subDeployments/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/subDeployments/{name}/subDeployments](#)
rel=self

This resource.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/subDeployments/{name}/subDeployments/{name}

This resource manages a [weblogic.management.configuration.SubDeploymentMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/subDeployments/{name}/subDeployments/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/subDeployments/{name}/subDeployments](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/subDeployments/{name}/subDeployments/{name}](#) **rel**=self

This resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/subDeployments/{name}/subDeployments/{name}/subDeployments](#) **rel**=subDeployments

This resource's subDeployments collection resource.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/JMSSystemResources/{name}/subDeployment

POST

Update this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/libraries

This resource manages a collection of [weblogic.management.configuration.LibraryMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.LibraryMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.LibraryMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/libraries rel=canonical](#)
This resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name} rel=parent](#)
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/libraries rel=self](#)
This resource.

POST

The resource supports the following methods:

- [POST accepting application/json](#)
- [POST accepting multipart/form-data](#)

POST accepting application/json

This resource is used to deploy libraries that are already on the administration server.

This method supports both asynchronous and best effort synchronous invocations. The behavior is controlled by the 'Prefer' header. See [About Synchronous and Asynchronous Operations](#).

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.LibraryMBean](#) entity.

To deploy a library, you must provide the name of the library, the path to the library, and the targets to which the library will be deployed.

Use the multi-part form to deploy a library.

- `sourcePath`: the deployment to upload (required)
- `model`: JSONObject containing a LibraryMBean entity that contains the rest of the deployment information (required)

POST accepting multipart/form-data

Upload a library from the client to the server then deploy it.

This method supports both asynchronous and best effort synchronous invocations. The behavior is controlled by the 'Prefer' header. See [About Synchronous and Asynchronous Operations](#).

Roles

Admin, Deployer

Request Body

Use the multi-part form to upload a library from the client to the server then deploy it.

- `sourcePath`: the deployment to upload (required)
- `model`: JSONObject containing a LibraryMBean entity that contains the rest of the deployment information (required)

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/libraries/{name}

This resource manages a [weblogic.management.configuration.LibraryMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Undeploy a library.

This method supports both asynchronous and best effort synchronous invocations. The behavior is controlled by the 'Prefer' header. See [About Synchronous and Asynchronous Operations](#).

Roles

Admin, Deployer

GET

Get this [weblogic.management.configuration.LibraryMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.LibraryMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/libraries/{name}/createPlan **rel**=action **title**=createPlan
This resource's createPlan action resource.
- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/libraries/{name} **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/libraries **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/libraries/{name}/redeploy **rel**=redeploy
This resource's redeploy resource.
- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/libraries/{name} **rel**=self
This resource.
- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/libraries/{name}/subDeploymentCreateForm **rel**=subDeploymentCreateForm
The create form resource for this resource's subDeployments collection resource.
- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/libraries/{name}/subDeployments **rel**=subDeployments
This resource's subDeployments collection resource.

POST

Update this [weblogic.management.configuration.LibraryMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.LibraryMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/libraries/{name}/createPlan

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

POST

Create a deployment plan in the specified directory.

Roles

Admin, Deployer

Request Body

Must contain a JSON object with the following fields:

planPath

planPath

Type: string

Response Body

Contains a JSON object with a string return field.

POST

Create a deployment plan in a default directory

Roles

Admin, Deployer

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/libraries/{name}/redeploy

The resource supports the following methods:

- [POST](#)

POST

Use the multi-part form to redeploy a library.

- `sourcePath`: the deployment to upload (required)
- `model`: JSONObject containing a LibraryMBean entity that contains the rest of the deployment information (required)

This method supports both asynchronous and best effort synchronous invocations. The behavior is controlled by the 'Prefer' header. See [About Synchronous and Asynchronous Operations](#).

Roles

Admin, Deployer

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/libraries/{name}/subDeploymentCreateForm

This resource manages the create forms for the subDeployments collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.SubDeploymentMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the subDeployments collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/libraries/{name}/subDeploymentCreateForm **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/libraries/{name}/subDeployments **rel**=create

The collection resource for this create form resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/libraries/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/libraries/{name}/subDeploymentCreateForm **rel**=self

This resource.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/libraries/{name}/subDeployments

This resource manages a collection of [weblogic.management.configuration.SubDeploymentMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.SubDeploymentMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.SubDeploymentMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/libraries/{name}/subDeployments](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/libraries/{name}/subDeploymentCreateForm](#) **rel=create-form**

The create form resource for this collection resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/libraries/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/libraries/{name}/subDeployments](#) **rel=self**

This resource.

POST

Add a new [weblogic.management.configuration.SubDeploymentMBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/libraries/{name}/subDeployments/{name}

This resource manages a [weblogic.management.configuration.SubDeploymentMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/libraries/{name}/subDeployments/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/libraries/{name}/subDeployments](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/libraries/{name}/subDeployments/{name}](#) **rel**=self

This resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/libraries/{name}/subDeployments/{name}/subDeployments](#)
rel=subDeployments

This resource's subDeployments collection resource.

POST

Update this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/libraries/{name}/subDeployments/{name}/subDeployments

This resource manages a collection of [weblogic.management.configuration.SubDeploymentMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.configuration.SubDeploymentMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.SubDeploymentMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/libraries/{name}/subDeployments/{name}/subDeployments **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/libraries/{name}/subDeployments/{name} **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/libraries/{name}/subDeployments/{name}/subDeployments **rel**=self
This resource.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/libraries/{name}/subDeployments/{name}/subDeployments/{name}

This resource manages a [weblogic.management.configuration.SubDeploymentMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/libraries/{name}/subDeployments/{name}/subDeployments/{name}
rel=canonical
This resource.
- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/libraries/{name}/subDeployments/{name}/subDeployments **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/libraries/{name}/subDeployments/{name}/subDeployments/{name}
rel=self
This resource.
- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/libraries/{name}/subDeployments/{name}/subDeployments/{name}/subDeployments **rel**=subDeployments
This resource's subDeployments collection resource.

POST

POST

Update this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/lookupTarget

The resource supports the following methods:

- [POST](#)

POST

Find a particular target with a given name.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

name

the name of the target to find

Type: string

Response Body

Contains a JSON object with a `weblogic.management.configuration.TargetMBean` reference return field.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/mailSessionCreateForm

This resource manages the create forms for the mailSessions collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.MailSessionMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the mailSessions collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.MailSessionMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/mailSessionCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/mailSessions](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/mailSessionCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/mailSessions

This resource manages a collection of [weblogic.management.configuration.MailSessionMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.MailSessionMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.MailSessionMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/mailSessions](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/mailSessionCreateForm](#) **rel**=create-form

The create form resource for this collection resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/mailSessions](#) **rel**=self

This resource.

POST

Add a new [weblogic.management.configuration.MailSessionMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.MailSessionMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/mailSessions/{name}

This resource manages a [weblogic.management.configuration.MailSessionMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.MailSessionMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.MailSessionMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.MailSessionMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/mailSessions/{name}](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/mailSessions](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/mailSessions/{name}](#) **rel=self**

This resource.

POST

Update this [weblogic.management.configuration.MailSessionMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.MailSessionMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/managedExecutorServiceCreateForm

This resource manages the create forms for the managedExecutorServices collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.ManagedExecutorServiceMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the `managedExecutorServices` collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ManagedExecutorServiceMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/managedExecutorServiceCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/managedExecutorServices](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/managedExecutorServiceCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/managedExecutorServices

This resource manages a collection of [weblogic.management.configuration.ManagedExecutorServiceMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.ManagedExecutorServiceMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.ManagedExecutorServiceMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/managedExecutorServices](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/managedExecutorServiceCreateForm](#) **rel=create-form**

The create form resource for this collection resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/managedExecutorServices](#) **rel=self**

This resource.

POST

Add a new [weblogic.management.configuration.ManagedExecutorServiceMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.ManagedExecutorServiceMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/managedExecutorServices/{name}

This resource manages a [weblogic.management.configuration.ManagedExecutorServiceMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.ManagedExecutorServiceMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.ManagedExecutorServiceMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ManagedExecutorServiceMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/managedExecutorServices/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/managedExecutorServices](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/managedExecutorServices/{name}](#) **rel**=self

This resource.

POST

Update this [weblogic.management.configuration.ManagedExecutorServiceMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.ManagedExecutorServiceMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/managedScheduledExecutorServiceCreateForm

This resource manages the create forms for the managedScheduledExecutorServices collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.ManagedScheduledExecutorServiceMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the `managedScheduledExecutorServices` collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ManagedScheduledExecutorServiceMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/managedScheduledExecutorServiceCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/managedScheduledExecutorServices](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/managedScheduledExecutorServiceCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/managedScheduledExecutorServices

This resource manages a collection of [weblogic.management.configuration.ManagedScheduledExecutorServiceMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.ManagedScheduledExecutorServiceMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.ManagedScheduledExecutorServiceMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/managedScheduledExecutorServices](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/managedScheduledExecutorServiceCreateForm](#) **rel=create-form**
The create form resource for this collection resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/managedScheduledExecutorServices](#) **rel=self**
This resource.

POST

Add a new [weblogic.management.configuration.ManagedScheduledExecutorServiceMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.ManagedScheduledExecutorServiceMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/managedScheduledExecutorServices/{name}

This resource manages a [weblogic.management.configuration.ManagedScheduledExecutorServiceMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this

[weblogic.management.configuration.ManagedScheduledExecutorServiceMBean](#)
instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.ManagedScheduledExecutorServiceMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ManagedScheduledExecutorServiceMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/managedScheduledExecutorServices/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/managedScheduledExecutorServices](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/managedScheduledExecutorServices/{name}](#) **rel**=self

This resource.

POST

Update this [weblogic.management.configuration.ManagedScheduledExecutorServiceMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.ManagedScheduledExecutorServiceMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/managedThreadFactories

This resource manages a collection of [weblogic.management.configuration.ManagedThreadFactoryMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.ManagedThreadFactoryMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.ManagedThreadFactoryMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/managedThreadFactories](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/managedThreadFactoryCreateForm](#) **rel=create-form**
The create form resource for this collection resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/managedThreadFactories](#) **rel=self**
This resource.

POST

Add a new [weblogic.management.configuration.ManagedThreadFactoryMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.ManagedThreadFactoryMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/managedThreadFactories/{name}

This resource manages a [weblogic.management.configuration.ManagedThreadFactoryMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.ManagedThreadFactoryMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.ManagedThreadFactoryMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ManagedThreadFactoryMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/managedThreadFactories/{name} **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/managedThreadFactories **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/managedThreadFactories/{name} **rel**=self
This resource.

POST

Update this [weblogic.management.configuration.ManagedThreadFactoryMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.ManagedThreadFactoryMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/managedThreadFactoryCreateForm

This resource manages the create forms for the managedThreadFactories collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.ManagedThreadFactoryMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the `managedThreadFactories` collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ManagedThreadFactoryMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/managedThreadFactoryCreateForm](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/managedThreadFactories](#) **rel**=create

The collection resource for this create form resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/managedThreadFactoryCreateForm](#) **rel**=self

This resource.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/messagingBridgeCreateForm

This resource manages the create forms for the messagingBridges collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.MessagingBridgeMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the `messagingBridges` collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.MessagingBridgeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/messagingBridgeCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/messagingBridges](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/messagingBridgeCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/messagingBridges

This resource manages a collection of [weblogic.management.configuration.MessagingBridgeMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.MessagingBridgeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.MessagingBridgeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/messagingBridges](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/messagingBridgeCreateForm](#) **rel=create-form**

The create form resource for this collection resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/messagingBridges](#) **rel=self**

This resource.

POST

Add a new [weblogic.management.configuration.MessagingBridgeMBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.MessagingBridgeMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/messagingBridges/{name}

This resource manages a [weblogic.management.configuration.MessagingBridgeMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.MessagingBridgeMBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.management.configuration.MessagingBridgeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.MessagingBridgeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/messagingBridges/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/messagingBridges](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/messagingBridges/{name}](#) **rel**=self

This resource.

- **rel**=sourceDestination

This resource's sourceDestination reference to a [weblogic.management.configuration.BridgeDestinationCommonMBean](#) resource.

- **rel**=targetDestination

This resource's targetDestination reference to a [weblogic.management.configuration.BridgeDestinationCommonMBean](#) resource.

POST

Update this [weblogic.management.configuration.MessagingBridgeMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.MessagingBridgeMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/osgiFrameworkCreateForm

This resource manages the create forms for the osgiFrameworks collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.OsgiFrameworkMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the `osgiFrameworks` collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.OsgiFrameworkMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/osgiFrameworkCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/osgiFrameworks](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/osgiFrameworkCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/osgiFrameworks

This resource manages a collection of [weblogic.management.configuration.OsgiFrameworkMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.OsgiFrameworkMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.OsgiFrameworkMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/osgiFrameworks **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/osgiFrameworkCreateForm **rel**=create-form
The create form resource for this collection resource.
- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name} **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/osgiFrameworks **rel**=self
This resource.

POST

Add a new [weblogic.management.configuration.OsgiFrameworkMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.OsgiFrameworkMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/osgiFrameworks/{name}

This resource manages a [weblogic.management.configuration.OsgiFrameworkMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.OsgiFrameworkMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.OsgiFrameworkMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.OsgiFrameworkMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/osgiFrameworks/{name}](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/osgiFrameworks](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/osgiFrameworks/{name}](#) **rel=self**
This resource.

POST

Update this [weblogic.management.configuration.OsgiFrameworkMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.OsgiFrameworkMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/SAFAgentCreateForm

This resource manages the create forms for the SAFAgents collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.SAFAgentMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the SAFAgents collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SAFAgentMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/SAFAgentCreateForm](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/SAFAgents](#) **rel=create**
The collection resource for this create form resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/SAFAgentCreateForm](#) **rel=self**
This resource.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/SAFAgents

This resource manages a collection of [weblogic.management.configuration.SAFAgentMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.SAFAgentMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.SAFAgentMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/SAFAgents](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/SAFAgentCreateForm](#) **rel**=create-form

The create form resource for this collection resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/SAFAgents](#) **rel**=self

This resource.

POST

Add a new [weblogic.management.configuration.SAFAgentMBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.SAFAgentMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/SAFAgents/{name}

This resource manages a [weblogic.management.configuration.SAFAMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.SAFAgentMBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.management.configuration.SAFAgentMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SAFAgentMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/SAFAgents/{name}/JMSSAFMessageLogFile](#) **rel**=JMSSAFMessageLogFile
This resource's JMSSAFMessageLogFile singleton resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/SAFAgents/{name}](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/SAFAgents](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/SAFAgents/{name}](#) **rel**=self
This resource.
- **rel**=store
This resource's store reference to a [weblogic.management.configuration.PersistentStoreMBean](#) resource.

POST

Update this [weblogic.management.configuration.SAFAgentMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.SAFAgentMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/SAFAgents/{name}/JMSSAFMessageLogFile

This resource manages a [weblogic.management.configuration.JMSSAFMessageLogFileMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.JMSSAFMessageLogFileMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.JMSSAFMessageLogFileMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/SAFAgents/{name}/JMSSAFMessageLogFile](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/SAFAgents/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/SAFAgents/{name}/JMSSAFMessageLogFile](#) **rel**=self

This resource.

POST

Update this [weblogic.management.configuration.JMSSAFMessageLogFileMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.JMSSAFMessageLogFileMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResourceCreateForm

This resource manages the create forms for the WLDFSystemResources collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.WLDFSystemResourceMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the [WLDFSystemResources](#) collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.WLDFSystemResourceMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResourceCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResourceCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources

This resource manages a collection of [weblogic.management.configuration.WLDFSystemResourceMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.WLDFSystemResourceMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.WLDFSystemResourceMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResourceCreateForm](#) **rel**=create-form

The create form resource for this collection resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources](#) **rel**=self

This resource.

POST

Add a new [weblogic.management.configuration.WLDFSystemResourceMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.WLDFSystemResourceMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}

This resource manages a [weblogic.management.configuration.WLDFSystemResourceMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.WLDFSystemResourceMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.WLDFSystemResourceMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.WLDFSystemResourceMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource](#) **rel**=WLDFResource
This resource's WLDFResource singleton resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources](#) **rel**=parent
The parent resource of this resource.
- **rel**=resource
This resource's resource reference to a [weblogic.descriptor.DescriptorBean](#) resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}](#) **rel**=self
This resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/subDeploymentCreateForm](#) **rel**=subDeploymentCreateForm
The create form resource for this resource's subDeployments collection resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/subDeployments](#) **rel**=subDeployments
This resource's subDeployments collection resource.

POST

Update this [weblogic.management.configuration.WLDFSystemResourceMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.WLDFSystemResourceMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/subDeploymentCreateForm

This resource manages the create forms for the subDeployments collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.SubDeploymentMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the subDeployments collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/subDeploymentCreateForm](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/subDeployments](#) **rel=create**
The collection resource for this create form resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/subDeploymentCreateForm](#) **rel=self**
This resource.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/subDeployments

This resource manages a collection of [weblogic.management.configuration.SubDeploymentMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.SubDeploymentMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.SubDeploymentMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/subDeployments **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/subDeploymentCreateForm **rel**=create-form

The create form resource for this collection resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/subDeployments **rel**=self

This resource.

POST

Add a new [weblogic.management.configuration.SubDeploymentMBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/subDeployments/{name}

This resource manages a [weblogic.management.configuration.SubDeploymentMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/subDeployments/{name}](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/subDeployments](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/subDeployments/{name}](#) **rel=self**

This resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/subDeployments/{name}/subDeployments](#) **rel=subDeployments**

This resource's subDeployments collection resource.

POST

Update this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/subDeployments/{name}/subDeployments

This resource manages a collection of [weblogic.management.configuration.SubDeploymentMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.configuration.SubDeploymentMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.SubDeploymentMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/subDeployments/{name}/subDeployments](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/subDeployments/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/subDeployments/{name}/subDeployments](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/subDeployments/{name}/subDeployments/{name}

This resource manages a [weblogic.management.configuration.SubDeploymentMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/subDeployments/{name}/subDeployments/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/subDeployments/{name}/subDeployments](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/subDeployments/{name}/subDeployments](#) **rel**=self

This resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/subDeployments/{name}/subDeployments](#) **rel**=subDeployments

This resource's subDeployments collection resource.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/subDeployme

POST

Update this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource

This resource manages a [weblogic.diagnostics.descriptor.WLDFResourceBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.diagnostics.descriptor.WLDFResourceBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFResourceBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/harvester **rel**=harvester
This resource's harvester singleton resource.
- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/instrumentation **rel**=instrumentation
This resource's instrumentation singleton resource.
- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name} **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource **rel**=self
This resource.
- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification **rel**=watchNotification
This resource's watchNotification singleton resource.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/harvester

This resource manages a [weblogic.diagnostics.descriptor.WLDFHarvesterBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.diagnostics.descriptor.WLDFHarvesterBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFHarvesterBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/harvester](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/harvester/harvestedTypeCreateForm](#) **rel=harvestedTypeCreateForm**

The create form resource for this resource's harvestedTypes collection resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/harvester/harvestedTypes](#) **rel=harvestedTypes**

This resource's harvestedTypes collection resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/harvester](#) **rel=self**

This resource.

POST

Update this [weblogic.diagnostics.descriptor.WLDFHarvesterBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFHarvesterBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/harvester/harvestedTypeC reateForm

This resource manages the create forms for the harvestedTypes collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFHarvestedTypeBean](#) entity populated with default values that can be customized then posted (using the POST method) to the harvestedTypes collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFHarvestedTypeBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/harvester/harvestedTypeCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/harvester/harvestedTypes](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/harvester](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/harvester/harvestedTypeCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/harvester/harvestedTypes

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFHarvestedTypeBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFHarvestedTypeBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFHarvestedTypeBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/harvester/harvestedTypes](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/harvester/harvestedTypes/CreateForm](#) **rel**=create-form

The create form resource for this collection resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/harvester](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/harvester/harvestedTypes](#) **rel**=self

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFHarvestedTypeBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFHarvestedTypeBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/harvester/harvestedTypes/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFHarvestedTypeBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFHarvestedTypeBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.diagnostics.descriptor.WLDFHarvestedTypeBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFHarvestedTypeBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/harvester/harvestedTypes/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/harvester/harvestedTypes](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/harvester/harvestedTypes/{name}](#) **rel**=self

This resource.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDSystemResources/{name}/WLDResource

POST

Update this [weblogic.diagnostics.descriptor.WLDFHarvestedTypeBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFHarvestedTypeBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/instrumentation

This resource manages a [weblogic.diagnostics.descriptor.WLDFInstrumentationBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.diagnostics.descriptor.WLDFInstrumentationBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFInstrumentationBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/instrumentation/WLDFInstrumentationMonitorCreateForm
rel=WLDFInstrumentationMonitorCreateForm

The create form resource for this resource's WLDFInstrumentationMonitors collection resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/instrumentation/WLDFInstrumentationMonitors **rel**=WLDFInstrumentationMonitors

This resource's WLDFInstrumentationMonitors collection resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/instrumentation **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/instrumentation **rel**=self

This resource.

POST

Update this [weblogic.diagnostics.descriptor.WLDFInstrumentationBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFInstrumentationBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/instrumentation/WLDFInstrumentationMonitorCreateForm

This resource manages the create forms for the WLDFInstrumentationMonitors collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFInstrumentationMonitorBean](#) entity populated with default values that can be customized then posted (using the POST method) to the [WLDFInstrumentationMonitors](#) collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFInstrumentationMonitorBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/instrumentation/WLDFInstrumentationMonitorCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/instrumentation/WLDFInstrumentationMonitors](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/instrumentation](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/instrumentation/WLDFInstrumentationMonitorCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/instrumentation/WLDFInstrumentationMonitors

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFInstrumentationMonitorBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFInstrumentationMonitorBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFInstrumentationMonitorBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/instrumentation/WLDFInstrumentationMonitors](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/instrumentation/WLDFInstrumentationMonitorCreateForm](#) **rel**=create-form

The create form resource for this collection resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/instrumentation](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/instrumentation/WLDFInstrumentationMonitors](#) **rel**=self

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFInstrumentationMonitorBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFInstrumentationMonitorBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/instrumentation/WLDFInstrumentationMonitors/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFInstrumentationMonitorBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFInstrumentationMonitorBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.diagnostics.descriptor.WLDFInstrumentationMonitorBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFInstrumentationMonitorBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/instrumentation/WLDFInstrumentationMonitors/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/instrumentation/WLDFInstrumentationMonitors](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/instrumentation/WLDFInstrumentationMonitors/{name}](#) **rel**=self

This resource.

POST

Update this [weblogic.diagnostics.descriptor.WLDFInstrumentationMonitorBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFInstrumentationMonitorBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification

This resource manages a [weblogic.diagnostics.descriptor.WLDFWatchNotificationBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.diagnostics.descriptor.WLDFWatchNotificationBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFWatchNotificationBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMSNotificationCreateForm](#) **rel**=JMSNotificationCreateForm

The create form resource for this resource's JMSNotifications collection resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMSNotifications](#) **rel**=JMSNotifications

This resource's JMSNotifications collection resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMXNotificationCreateForm](#) **rel**=JMXNotificationCreateForm

The create form resource for this resource's JMXNotifications collection resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMXNotifications](#) **rel**=JMXNotifications

This resource's JMXNotifications collection resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/RESTNotificationCreateForm](#) **rel**=RESTNotificationCreateForm

The create form resource for this resource's RESTNotifications collection resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/RESTNotifications](#) **rel**=RESTNotifications

This resource's RESTNotifications collection resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/SMTPNotificationCreateForm](#) **rel**=SMTPNotificationCreateForm

The create form resource for this resource's SMTPNotifications collection resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/SMTPNotifications](#) **rel**=SMTPNotifications

This resource's SMTPNotifications collection resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/SNMPNotificationCreateForm **rel**=SNMPNotificationCreateForm
The create form resource for this resource's SNMPNotifications collection resource.
- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/SNMPNotifications **rel**=SNMPNotifications
This resource's SNMPNotifications collection resource.
- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/lookupActions **rel**=action **title**=lookupActions
This resource's lookupActions action resource.
- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/lookupNotification **rel**=action **title**=lookupNotification
This resource's lookupNotification action resource.
- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actionCreateForm **rel**=actionCreateForm
The create form resource for this resource's actions collection resource.
- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions **rel**=actions
This resource's actions collection resource.
- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/heapDumpActionCreateForm **rel**=heapDumpActionCreateForm
The create form resource for this resource's heapDumpActions collection resource.
- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/heapDumpActions **rel**=heapDumpActions
This resource's heapDumpActions collection resource.
- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/imageNotificationCreateForm **rel**=imageNotificationCreateForm
The create form resource for this resource's imageNotifications collection resource.
- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/imageNotifications **rel**=imageNotifications
This resource's imageNotifications collection resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/logActionCreateForm **rel**=logActionCreateForm

The create form resource for this resource's logActions collection resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/logActions **rel**=logActions

This resource's logActions collection resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleDownActionCreateForm **rel**=scaleDownActionCreateForm

The create form resource for this resource's scaleDownActions collection resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleDownActions **rel**=scaleDownActions

This resource's scaleDownActions collection resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleUpActionCreateForm **rel**=scaleUpActionCreateForm

The create form resource for this resource's scaleUpActions collection resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleUpActions **rel**=scaleUpActions

This resource's scaleUpActions collection resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scriptActionCreateForm **rel**=scriptActionCreateForm

The create form resource for this resource's scriptActions collection resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scriptActions **rel**=scriptActions

This resource's scriptActions collection resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification **rel**=self

This resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/threadDumpActionCreateForm **rel**=threadDumpActionCreateForm

The create form resource for this resource's threadDumpActions collection resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/threadDumpActions **rel**=threadDumpActions

This resource's threadDumpActions collection resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/watcheCreateForm **rel**=watcheCreateForm

The create form resource for this resource's watches collection resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/watches **rel**=watches

This resource's watches collection resource.

POST

Update this [weblogic.diagnostics.descriptor.WLDFWatchNotificationBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFWatchNotificationBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actionCreateForm

This resource manages the create forms for the actions collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFActionBean](#) entity populated with default values that can be customized then posted (using the POST method) to the actions collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFActionBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actionCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actionCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFActionBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFActionBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFActionBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actionCreateForm](#) **rel=create-form**

The create form resource for this collection resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions](#) **rel=self**

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFActionBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFActionBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFActionBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFActionBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.diagnostics.descriptor.WLDFActionBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFActionBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/arrayProperties](#) **rel=arrayProperties**

This resource's arrayProperties collection resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/arrayPropertyCreateForm](#) **rel=arrayPropertyCreateForm**

The create form resource for this resource's arrayProperties collection resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/configurationProperties](#) **rel=configurationProperties**

This resource's configurationProperties collection resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/encryptedProperties](#) **rel=encryptedProperties**

This resource's encryptedProperties collection resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/encryptedPropertyCreateForm](#) **rel=encryptedPropertyCreateForm**

The create form resource for this resource's encryptedProperties collection resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties](#) **rel=mapProperties**

This resource's mapProperties collection resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapPropertyCreateForm](#) **rel=mapPropertyCreateForm**

The create form resource for this resource's mapProperties collection resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDSystemResources/{name}/WLDResource/watchNotification/actions **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDSystemResources/{name}/WLDResource/watchNotification/actions/{name}/properties **rel**=properties

This resource's properties collection resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDSystemResources/{name}/WLDResource/watchNotification/actions/{name}/propertyCreateForm **rel**=propertyCreateForm

The create form resource for this resource's properties collection resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDSystemResources/{name}/WLDResource/watchNotification/actions/{name} **rel**=self

This resource.

POST

Update this [weblogic.diagnostics.descriptor.WLDFActionBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFActionBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/arrayProperties

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFArrayPropertyBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFArrayPropertyBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFArrayPropertyBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/arrayProperties **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/arrayPropertyCreateForm **rel**=create-form

The create form resource for this collection resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/arrayProperties **rel**=self

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFArrayPropertyBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFArrayPropertyBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/arrayProperties/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFArrayPropertyBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFArrayPropertyBean](#) instance.

Roles

Admin

GET

Get this [weblogic.diagnostics.descriptor.WLDFArrayPropertyBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFArrayPropertyBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/arrayProperties/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/arrayProperties **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/arrayProperties/{name} **rel**=self

This resource.

POST

Update this [weblogic.diagnostics.descriptor.WLDFArrayPropertyBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFArrayPropertyBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/arrayPropertyCreateForm

This resource manages the create forms for the arrayProperties collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFArrayPropertyBean](#) entity populated with default values that can be customized then posted (using the POST method) to the arrayProperties collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFArrayPropertyBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/arrayPropertyCreateForm **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/arrayProperties **rel**=create

The collection resource for this create form resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/arrayPropertyCreateForm **rel**=self

This resource.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/configurationProperties

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFConfigurationPropertyBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFConfigurationPropertyBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFConfigurationPropertyBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/configurationProperties](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/configurationProperties](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/configurationProperties/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFConfigurationPropertyBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.diagnostics.descriptor.WLDFConfigurationPropertyBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFConfigurationPropertyBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/configurationProperties/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/configurationProperties](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/configurationProperties/{name}](#) **rel**=self

This resource.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/encryptedProperties

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/encryptedProperties](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/encryptedPropertyCreateForm](#) **rel**=create-form

The create form resource for this collection resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/encryptedProperties](#) **rel**=self

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/encryptedProperties/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) instance.

Roles

Admin

GET

Get this [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/encryptedProperties/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/encryptedProperties](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/encryptedProperties/{name}](#) **rel**=self

This resource.

POST

Update this [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/encryptedPropertyCreateForm

This resource manages the create forms for the encryptedProperties collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) entity populated with default values that can be customized then posted (using the POST method) to the encryptedProperties collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/encryptedPropertyCreateForm **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/encryptedProperties **rel**=create

The collection resource for this create form resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/encryptedPropertyCreateForm **rel**=self

This resource.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFConfigurationPropertiesBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFConfigurationPropertiesBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFConfigurationPropertiesBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapPropertyCreateForm **rel**=create-form

The create form resource for this collection resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties **rel**=self

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFConfigurationPropertiesBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFConfigurationPropertiesBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFConfigurationPropertiesBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFConfigurationPropertiesBean](#) instance.

Roles

Admin

GET

Get this [weblogic.diagnostics.descriptor.WLDFConfigurationPropertiesBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFConfigurationPropertiesBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/configurationProperties **rel**=configurationProperties

This resource's configurationProperties collection resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/encryptedProperties **rel**=encryptedProperties

This resource's encryptedProperties collection resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/encryptedPropertyCreateForm **rel**=encryptedPropertyCreateForm

The create form resource for this resource's encryptedProperties collection resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/properties **rel**=properties

This resource's properties collection resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/propertyCreateForm **rel**=propertyCreateForm

The create form resource for this resource's properties collection resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name} **rel**=self

This resource.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/configurationProperties

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFConfigurationPropertyBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFConfigurationPropertyBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFConfigurationPropertyBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/configurationProperties](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/configurationProperties](#) **rel**=self

This resource.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/configurationProperties/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFConfigurationPropertyBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.diagnostics.descriptor.WLDFConfigurationPropertyBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFConfigurationPropertyBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/configurationProperties/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/configurationProperties](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/configurationProperties/{name}](#) **rel**=self

This resource.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/encryptedProperties

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/encryptedProperties](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/encryptedPropertyCreateForm](#) **rel**=create-form

The create form resource for this collection resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/encryptedProperties](#) **rel**=self

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/encryptedProperties/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/encryptedProperties/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/encryptedProperties](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/encryptedProperties/{name}](#) **rel**=self

This resource.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDSystemResources/{name}/WLDResource

POST

Update this [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/encryptedPropertyCreateForm

This resource manages the create forms for the encryptedProperties collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) entity populated with default values that can be customized then posted (using the POST method) to the encryptedProperties collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/encryptedPropertyCreateForm **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/encryptedProperties **rel**=create

The collection resource for this create form resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/encryptedPropertyCreateForm **rel**=self

This resource.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/properties

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/properties](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/propertyCreateForm](#) **rel=create-form**

The create form resource for this collection resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/properties](#) **rel=self**

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/properties/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/properties/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/properties **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/properties/{name} **rel**=self

This resource.

POST

Update this [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/propertyCreateForm

This resource manages the create forms for the properties collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) entity populated with default values that can be customized then posted (using the POST method) to the properties collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/propertycreateForm](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/properties](#) **rel**=create

The collection resource for this create form resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/propertycreateForm](#) **rel**=self

This resource.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapPropertyCreateForm

This resource manages the create forms for the mapProperties collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFConfigurationPropertiesBean](#) entity populated with default values that can be customized then posted (using the POST method) to the `mapProperties` collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFConfigurationPropertiesBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapPropertyCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapPropertyCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/properties

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/properties](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/propertyCreateForm](#) **rel**=create-form

The create form resource for this collection resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/properties](#) **rel**=self

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/properties/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDPropertyBean](#) instance.

Roles

Admin

GET

Get this [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/properties/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/properties](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/properties/{name}](#) **rel**=self

This resource.

POST

Update this [weblogic.diagnostics.descriptor.WLDPropertyBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDPropertyBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/propertyCreateForm

This resource manages the create forms for the properties collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) entity populated with default values that can be customized then posted (using the POST method) to the properties collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/propertycreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/properties](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/propertycreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/heapDumpActionCreateForm

This resource manages the create forms for the heapDumpActions collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFHeapDumpActionBean](#) entity populated with default values that can be customized then posted (using the POST method) to the heapDumpActions collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFHeapDumpActionBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/heapDumpActionCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/heapDumpActions](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/heapDumpActionCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/heapDumpActions

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFHeapDumpActionBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFHeapDumpActionBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFHeapDumpActionBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/heapDumpActions](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/heapDumpActionCreateForm](#) **rel=create-form**

The create form resource for this collection resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/heapDumpActions](#) **rel=self**

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFHeapDumpActionBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFHeapDumpActionBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/heapDumpActions/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFHeapDumpActionBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFHeapDumpActionBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.diagnostics.descriptor.WLDFHeapDumpActionBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFHeapDumpActionBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/heapDumpActions/{name}](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/heapDumpActions](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/heapDumpActions/{name}](#) **rel=self**

This resource.

POST

POST

Update this [weblogic.diagnostics.descriptor.WLDFHeapDumpActionBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFHeapDumpActionBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/imageNotificationCreateForm

This resource manages the create forms for the imageNotifications collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFImageNotificationBean](#) entity populated with default values that can be customized then posted (using the POST method) to the `imageNotifications` collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFImageNotificationBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/imageNotificationCreateForm](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/imageNotifications](#) **rel**=create

The collection resource for this create form resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/imageNotificationCreateForm](#) **rel**=self

This resource.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/imageNotifications

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFImageNotificationBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFImageNotificationBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFImageNotificationBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/imageNotifications](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/imageNotificationCreateForm](#) **rel=create-form**

The create form resource for this collection resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/imageNotifications](#) **rel=self**

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFImageNotificationBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFImageNotificationBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/imageNotifications/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFImageNotificationBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDImageNotificationBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.diagnostics.descriptor.WLDFImageNotificationBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFImageNotificationBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/imageNotifications/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/imageNotifications](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/imageNotifications/{name}](#) **rel**=self

This resource.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDSystemResources/{name}/WLDResource

POST

Update this [weblogic.diagnostics.descriptor.WLDImageNotificationBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDImageNotificationBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMSNotificationCreateForm

This resource manages the create forms for the JMSNotifications collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFJMSNotificationBean](#) entity populated with default values that can be customized then posted (using the POST method) to the JMSNotifications collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFJMSNotificationBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMSNotificationCreateForm **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMSNotifications **rel**=create

The collection resource for this create form resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMSNotificationCreateForm **rel**=self

This resource.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMSNotifications

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFJMSNotificationBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFJMSNotificationBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFJMSNotificationBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMSNotifications **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMSNotificationCreateForm **rel**=create-form

The create form resource for this collection resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMSNotifications **rel**=self

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFJMSNotificationBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFJMSNotificationBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMSNotifications/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFJMSNotificationBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFJMSNotificationBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.diagnostics.descriptor.WLDFJMSNotificationBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFJMSNotificationBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMSNotifications/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMSNotifications **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMSNotifications/{name} **rel**=self

This resource.

POST

Update this [weblogic.diagnostics.descriptor.WLDFJMSNotificationBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFJMSNotificationBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMXNotificationCreateForm

This resource manages the create forms for the JMXNotifications collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFJMXNotificationBean](#) entity populated with default values that can be customized then posted (using the POST method) to the JMXNotifications collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFJMXNotificationBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMXNotificationCreateForm](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMXNotifications](#) **rel**=create

The collection resource for this create form resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMXNotificationCreateForm](#) **rel**=self

This resource.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMXNotifications

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFJMXNotificationBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFJMXNotificationBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFJMXNotificationBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMXNotifications](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMXNotificationCreateForm](#) **rel=create-form**

The create form resource for this collection resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMXNotifications](#) **rel=self**

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFJMXNotificationBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFJMXNotificationBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMXNotifications/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFJMXNotificationBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFJMXNotificationBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.diagnostics.descriptor.WLDFJMXNotificationBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFJMXNotificationBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMXNotifications/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMXNotifications](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMXNotifications/{name}](#) **rel**=self

This resource.

POST

Update this [weblogic.diagnostics.descriptor.WLDFJMXNotificationBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFJMXNotificationBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/logActionCreateForm

This resource manages the create forms for the logActions collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFLogActionBean](#) entity populated with default values that can be customized then posted (using the POST method) to the logActions collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFLogActionBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/logActionCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/logActions](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/logActionCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/logActions

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFLogActionBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFLogActionBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFLogActionBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/logActions](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/logActionCreateForm](#) **rel=create-form**

The create form resource for this collection resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/logActions](#) **rel=self**

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFLogActionBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFLogActionBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/logActions/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFLogActionBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFLogActionBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.diagnostics.descriptor.WLDFLogActionBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFLogActionBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/logActions/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/logActions **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/logActions/{name} **rel**=self

This resource.

POST

Update this [weblogic.diagnostics.descriptor.WLDFLogActionBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFLogActionBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/lookupActions

The resource supports the following methods:

- [POST](#)

POST

Roles

Admin, Deployer

Request Body

Must contain a JSON object with the following fields:

typeName

typeName

Type: string

Response Body

Contains a JSON object with a array of
weblogic.diagnostics.descriptor.WLDFActionBean references return field.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/lookupNotification

The resource supports the following methods:

- [POST](#)

POST

Looks up an action with the given name.

Roles

Admin, Deployer

Request Body

Must contain a JSON object with the following fields:

name

name

Type: string

Response Body

Contains a JSON object with a `weblogic.diagnostics.descriptor.WLDFNotificationBean` reference return field.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/RESTNotificationCreateForm

This resource manages the create forms for the RESTNotifications collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFRESTNotificationBean](#) entity populated with default values that can be customized then posted (using the POST method) to the RESTNotifications collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFRESTNotificationBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/RESTNotificationCreateForm](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/RESTNotifications](#) **rel**=create

The collection resource for this create form resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/RESTNotificationCreateForm](#) **rel**=self

This resource.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/RESTNotifications

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFRESTNotificationBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFRESTNotificationBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFRESTNotificationBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/RESTNotifications](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/RESTNotificationCreateForm](#) **rel=create-form**

The create form resource for this collection resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/RESTNotifications](#) **rel=self**

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFRESTNotificationBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFRESTNotificationBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/RESTNotifications/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFRESTNotificationBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFRESTNotificationBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.diagnostics.descriptor.WLDFRESTNotificationBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFRESTNotificationBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/RESTNotifications/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/RESTNotifications](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/RESTNotifications/{name}](#) **rel**=self

This resource.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDSystemResources/{name}/WLDResource

POST

Update this [weblogic.diagnostics.descriptor.WLDFRESTNotificationBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFRESTNotificationBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleDownActionCreateForm

This resource manages the create forms for the scaleDownActions collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFScaleDownActionBean](#) entity populated with default values that can be customized then posted (using the POST method) to the scaleDownActions collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFScaleDownActionBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleDownActionCreateForm **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleDownActions **rel**=create

The collection resource for this create form resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleDownActionCreateForm **rel**=self

This resource.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleDownActions

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFScaleDownActionBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFScaleDownActionBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFScaleDownActionBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleDownActions](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleDownActionCreateForm](#) **rel=create-form**

The create form resource for this collection resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleDownActions](#) **rel=self**

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFScaleDownActionBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFScaleDownActionBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleDownActions/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFScaleDownActionBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFScaleDownActionBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.diagnostics.descriptor.WLDFScaleDownActionBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFScaleDownActionBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleDownActions/{name}](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleDownActions](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleDownActions/{name}](#) **rel=self**

This resource.

POST

POST

Update this [weblogic.diagnostics.descriptor.WLDFScaleDownActionBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFScaleDownActionBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleUpActionCreateForm

This resource manages the create forms for the scaleUpActions collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFScaleUpActionBean](#) entity populated with default values that can be customized then posted (using the POST method) to the `scaleUpActions` collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFScaleUpActionBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleUpActionCreateForm](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleUpActions](#) **rel**=create

The collection resource for this create form resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleUpActionCreateForm](#) **rel**=self

This resource.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleUp Actions

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFScaleUpActionBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFScaleUpActionBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFScaleUpActionBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleUpActions](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleUpActionCreateForm](#) **rel=create-form**

The create form resource for this collection resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleUpActions](#) **rel=self**

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFScaleUpActionBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFScaleUpActionBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleUpActions/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFScaleUpActionBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFScaleUpActionBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.diagnostics.descriptor.WLDFScaleUpActionBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFScaleUpActionBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleUpActions/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleUpActions](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleUpActions/{name}](#) **rel**=self

This resource.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResourc

POST

Update this [weblogic.diagnostics.descriptor.WLDFScaleUpActionBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFScaleUpActionBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scriptActionCreateForm

This resource manages the create forms for the scriptActions collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFScriptActionBean](#) entity populated with default values that can be customized then posted (using the POST method) to the scriptActions collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFScriptActionBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scriptActionCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scriptActions](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scriptActionCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scriptActions

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFScriptActionBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFScriptActionBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFScriptActionBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scriptActions **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scriptActionCreateForm **rel**=create-form

The create form resource for this collection resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scriptActions **rel**=self

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFScriptActionBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFScriptActionBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scriptActions/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFScriptActionBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFScriptActionBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.diagnostics.descriptor.WLDFScriptActionBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFScriptActionBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scriptActions/{name}](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scriptActions](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scriptActions/{name}](#) **rel=self**

This resource.

POST

Update this [weblogic.diagnostics.descriptor.WLDFScriptActionBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFScriptActionBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/SMTPNotificationCreateForm

This resource manages the create forms for the SMTPNotifications collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFSMTPNotificationBean](#) entity populated with default values that can be customized then posted (using the POST method) to the SMTPNotifications collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFSMTPNotificationBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/SMTPNotificationCreateForm](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/SMTPNotifications](#) **rel**=create

The collection resource for this create form resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/SMTPNotificationCreateForm](#) **rel**=self

This resource.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/SMTPNotifications

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFSMTPNotificationBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFSMTPNotificationBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFSMTPNotificationBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/SMTPNotifications](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/SMTPNotificationCreateForm](#) **rel=create-form**

The create form resource for this collection resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/SMTPNotifications](#) **rel=self**

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFSMTPNotificationBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFSMTPNotificationBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/SMTPTNotifications/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFSMTPNotificationBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFSMTPNotificationBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.diagnostics.descriptor.WLDFSMTPNotificationBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFSMTPNotificationBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/SMTPNotifications/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/SMTPNotifications](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/SMTPNotifications/{name}](#) **rel**=self

This resource.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResourc

POST

Update this [weblogic.diagnostics.descriptor.WLDFSMTPNotificationBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFSMTPNotificationBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/SNMPNotificationCreateForm

This resource manages the create forms for the SNMPNotifications collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFSNMPNotificationBean](#) entity populated with default values that can be customized then posted (using the POST method) to the SNMPNotifications collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFSNMPNotificationBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/SNMPNotificationCreateForm **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/SNMPNotifications **rel**=create

The collection resource for this create form resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/SNMPNotificationCreateForm **rel**=self

This resource.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/SNMPNotifications

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFSNMPNotificationBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFSNMPNotificationBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFSNMPNotificationBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/SNMPNotifications](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/SNMPNotificationCreateForm](#) **rel=create-form**

The create form resource for this collection resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/SNMPNotifications](#) **rel=self**

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFSNMPNotificationBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFSNMPNotificationBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/SNMPNotifications/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFSNMPNotificationBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFSNMPNotificationBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.diagnostics.descriptor.WLDFSNMPNotificationBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFSNMPNotificationBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/SNMPNotifications/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/SNMPNotifications **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/SNMPNotifications/{name} **rel**=self

This resource.

POST

Update this [weblogic.diagnostics.descriptor.WLDFSNMPNotificationBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFSNMPNotificationBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/threadDumpActionCreateForm

This resource manages the create forms for the threadDumpActions collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFThreadDumpActionBean](#) entity populated with default values that can be customized then posted (using the POST method) to the threadDumpActions collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFThreadDumpActionBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/threadDumpActionCreateForm](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/threadDumpActions](#) **rel**=create

The collection resource for this create form resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/threadDumpActionCreateForm](#) **rel**=self

This resource.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/threadDumpActions

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFThreadDumpActionBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFThreadDumpActionBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFThreadDumpActionBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/threadDumpActions](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/threadDumpActionCreateForm](#) **rel**=create-form

The create form resource for this collection resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/threadDumpActions](#) **rel**=self

This resource.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDSystemResources/{name}/WLDResource

POST

Add a new [weblogic.diagnostics.descriptor.WLDThreadDumpActionBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDThreadDumpActionBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/threadDumpActions/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFThreadDumpActionBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFThreadDumpActionBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.diagnostics.descriptor.WLDFThreadDumpActionBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFThreadDumpActionBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/threadDumpActions/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/threadDumpActions](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/threadDumpActions/{name}](#) **rel**=self

This resource.

POST

Update this [weblogic.diagnostics.descriptor.WLDThreadDumpActionBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDThreadDumpActionBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/watcher/createForm

This resource manages the create forms for the watches collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFWatchBean](#) entity populated with default values that can be customized then posted (using the POST method) to the watches collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFWatchBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/watcheCreateForm rel=canonical](#)

This resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/watches rel=create](#)

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification rel=parent](#)

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/watcheCreateForm rel=self](#)

This resource.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/watches

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFWatchBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFWatchBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFWatchBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/watches **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/watcheCreateForm **rel**=create-form

The create form resource for this collection resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/watches **rel**=self

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFWatchBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFWatchBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/watches/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFWatchBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFWatchBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.diagnostics.descriptor.WLDFWatchBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFWatchBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/watches/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/watches **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/watches/{name}/schedule **rel**=schedule

This resource's schedule singleton resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/watches/{name} **rel**=self

This resource.

POST

Update this [weblogic.diagnostics.descriptor.WLDFWatchBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFWatchBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/watches/{name}/schedule

This resource manages a [weblogic.diagnostics.descriptor.WLDFScheduleBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.diagnostics.descriptor.WLDFScheduleBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFScheduleBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/watches/{name}/schedule](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/watches/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/watches/{name}/schedule](#) **rel**=self

This resource.

POST

Update this [weblogic.diagnostics.descriptor.WLDFScheduleBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFScheduleBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceManager

This resource manages a [weblogic.management.configuration.ResourceManagerMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.ResourceManagerMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.ResourceManagerMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ResourceManagerMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceManagerMBean](#) **rel**=canonical

This resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceManager/cpuUtilization](#) **rel**=cpuUtilization

This resource's cpuUtilization singleton resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceManager/cpuUtilizationCreateForm](#) **rel**=cpuUtilizationCreateForm

The create form resource for this resource's cpuUtilization optional singleton resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceManager/createForm](#) **rel**=create-form

The create form resource for this optional singleton resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceManager/fileOpen](#) **rel**=fileOpen

This resource's fileOpen singleton resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceManager/fileOpenCreateForm](#) **rel**=fileOpenCreateForm

The create form resource for this resource's fileOpen optional singleton resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceManager/heapRetained](#) **rel**=heapRetained

This resource's heapRetained singleton resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceManager/heapRetainedCreateForm](#) **rel**=heapRetainedCreateForm

The create form resource for this resource's heapRetained optional singleton resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}](#) **rel**=parent

The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceManager/restartLoopProtection](#) **rel**=restartLoopProtection

This resource's restartLoopProtection singleton resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceManager
l=self
This resource.

POST

Update this [weblogic.management.configuration.ResourceManagerMBean](#) instance if it exists; otherwise, create it.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.ResourceManagerMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceManager/cpuUtilization

This resource manages a [weblogic.management.configuration.CpuUtilizationMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.CpuUtilizationMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.CpuUtilizationMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.CpuUtilizationMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceManager/cpuUtilization](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceManager/cpuUtilizationCreateForm](#) **rel=create-form**
The create form resource for this optional singleton resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceManager/cpuUtilization/fairShareConstraint](#) **rel=fairShareConstraint**
This resource's fairShareConstraint singleton resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceManager/cpuUtilization/fairShareConstraintCreateForm](#) **rel=fairShareConstraintCreateForm**
The create form resource for this resource's fairShareConstraint optional singleton resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceManager/cpuUtilization](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceManager/cpuUtilization](#) **rel=self**
This resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceManager/cpuUtilization/triggerCreateForm](#) **rel=triggerCreateForm**
The create form resource for this resource's triggers collection resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceManager/cpuUtilization/triggers](#) **rel=triggers**
This resource's triggers collection resource.

POST

Update this [weblogic.management.configuration.CpuUtilizationMBean](#) instance if it exists; otherwise, create it.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.CpuUtilizationMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceManager/cpuUtilization/fairShareConstraint

This resource manages a [weblogic.management.configuration.FairShareConstraintMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.FairShareConstraintMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.FairShareConstraintMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.FairShareConstraintMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceManager/cpuUtilization/fairShareConstraint](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceManager/cpuUtilization/fairShareConstraintCreateForm](#) **rel=create-form**
The create form resource for this optional singleton resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceManager/cpuUtilization](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceManager/cpuUtilization/fairShareConstraint](#) **rel=self**
This resource.

POST

Update this [weblogic.management.configuration.FairShareConstraintMBean](#) instance if it exists; otherwise, create it.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.FairShareConstraintMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceManager/cpuUtilization/fairShareConstraintCreateForm

This resource manages the create forms for the fairShareConstraint optional singleton instance.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.FairShareConstraintMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the [fairShareConstraint](#) optional singleton resource to create a new instance if it currently does not exist.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.FairShareConstraintMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceManager/cpuUtilization/fairShareConstraintCreateForm rel=canonical](#)
This resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceManager/cpuUtilization/fairShareConstraintCreateForm rel=create](#)
The optional singleton resource for this create form resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceManager/cpuUtilization rel=parent](#)
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceManager/cpuUtilization/fairShareConstraintCreateForm rel=self](#)
This resource.

/management/weblogic/{version}/edit/partitions/{name}/resourceManager/cpuUtilization/triggerCreateForm

This resource manages the create forms for the triggers collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.TriggerMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the triggers collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.TriggerMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceManager/cpuUtilization/triggerCreateForm](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceManager/cpuUtilization/triggers](#) **rel=create**
The collection resource for this create form resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceManager/cpuUtilization](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceManager/cpuUtilization/triggerCreateForm](#) **rel=self**
This resource.

/management/weblogic/{version}/edit/partitions/{name}/resourceManager/cpuUtilization/triggers

This resource manages a collection of [weblogic.management.configuration.TriggerMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.TriggerMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.TriggerMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceManager/cpuUtilization/triggers](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceManager/cpuUtilization/triggerCreateForm](#) **rel=create-form**

The create form resource for this collection resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceManager/cpuUtilization](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceManager/cpuUtilization/triggers](#) **rel=self**

This resource.

POST

Add a new [weblogic.management.configuration.TriggerMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.TriggerMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceManager/cpuUtilization/triggers/{name}

This resource manages a [weblogic.management.configuration.TriggerMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.TriggerMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.TriggerMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.TriggerMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceManager/cpuUtilization/triggers/{name} rel=canonical](#)
This resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceManager/cpuUtilization/triggers rel=parent](#)
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceManager/cpuUtilization/triggers/{name} rel=self](#)
This resource.

POST

Update this [weblogic.management.configuration.TriggerMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.TriggerMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceManager/cpuUtilizationCreateForm

This resource manages the create forms for the cpuUtilization optional singleton instance.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.CpuUtilizationMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the `cpuUtilization` optional singleton resource to create a new instance if it currently does not exist.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.CpuUtilizationMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceManager/cpuUtilizationCreateForm](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceManager/cpuUtilizationCreateForm](#) **rel=create**
The optional singleton resource for this create form resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceManager/parent](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceManager/cpuUtilizationCreateForm](#) **rel=self**
This resource.

/management/weblogic/{version}/edit/partitions/{name}/resourceManager/fileOpen

This resource manages a [weblogic.management.configuration.FileOpenMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.FileOpenMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.FileOpenMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.FileOpenMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceManager/fileOpen](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceManager/fileOpen/createForm](#) **rel=create-form**
The create form resource for this optional singleton resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceManager/fileOpen](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceManager/fileOpen](#) **rel=self**
This resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceManager/fileOpen/triggers/createForm](#) **rel=triggerCreateForm**
The create form resource for this resource's triggers collection resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceManager/fileOpen/triggers](#) **rel=triggers**
This resource's triggers collection resource.

POST

Update this [weblogic.management.configuration.FileOpenMBean](#) instance if it exists; otherwise, create it.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.FileOpenMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceManager/fileOpen/triggerCreateForm

This resource manages the create forms for the triggers collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.TriggerMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the triggers collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.TriggerMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceManager/fileOpen/triggerCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceManager/fileOpen/triggers](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceManager/fileOpen](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceManager/fileOpen/triggerCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/partitions/{name}/resourceManager/fileOpen/triggers

This resource manages a collection of [weblogic.management.configuration.TriggerMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.TriggerMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.TriggerMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceManager/fileOpen/triggers](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceManager/fileOpen/triggerCreateForm](#) **rel=create-form**

The create form resource for this collection resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceManager/fileOpen](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceManager/fileOpen/triggers](#) **rel=self**

This resource.

POST

Add a new [weblogic.management.configuration.TriggerMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.TriggerMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceManager/fileOpen/triggers/{name}

This resource manages a [weblogic.management.configuration.TriggerMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.TriggerMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.TriggerMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.TriggerMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceManager/fileOpen/triggers/{name} **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceManager/fileOpen/triggers **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/edit/partitions/{name}/resourceManager/fileOpen/triggers/{name} **rel**=self
This resource.

POST

Update this [weblogic.management.configuration.TriggerMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.TriggerMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceManager/fileOpenCreateForm

This resource manages the create forms for the fileOpen optional singleton instance.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.FileOpenMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the fileOpen optional singleton resource to create a new instance if it currently does not exist.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.FileOpenMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceManager/fileOpenCreateForm](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceManager/fileOpenCreateForm](#) **rel=create**
The optional singleton resource for this create form resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceManager/](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceManager/fileOpenCreateForm](#) **rel=self**
This resource.

/management/weblogic/{version}/edit/partitions/{name}/resourceManager/heapRetained

This resource manages a [weblogic.management.configuration.HeapRetainedMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.HeapRetainedMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.HeapRetainedMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.HeapRetainedMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceManager/heapRetained](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceManager/heapRetainedCreateForm](#) **rel=create-form**
The create form resource for this optional singleton resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceManager/heapRetained/fairShareConstraint](#) **rel=fairShareConstraint**
This resource's fairShareConstraint singleton resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceManager/heapRetained/fairShareConstraintCreateForm](#) **rel=fairShareConstraintCreateForm**
The create form resource for this resource's fairShareConstraint optional singleton resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceManager/heapRetained](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceManager/heapRetained](#) **rel=self**
This resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceManager/heapRetained/triggerCreateForm](#) **rel=triggerCreateForm**
The create form resource for this resource's triggers collection resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceManager/heapRetained/triggers](#) **rel=triggers**
This resource's triggers collection resource.

POST

Update this [weblogic.management.configuration.HeapRetainedMBean](#) instance if it exists; otherwise, create it.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.HeapRetainedMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceManager/heapRetained/fairShareConstraint

This resource manages a [weblogic.management.configuration.FairShareConstraintMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.FairShareConstraintMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.FairShareConstraintMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.FairShareConstraintMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceManager/heapRetained/fairShareConstraint](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceManager/heapRetained/fairShareConstraintCreateForm](#) **rel=create-form**
The create form resource for this optional singleton resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceManager/heapRetained](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceManager/heapRetained/fairShareConstraint](#) **rel=self**
This resource.

POST

Update this [weblogic.management.configuration.FairShareConstraintMBean](#) instance if it exists; otherwise, create it.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.FairShareConstraintMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceManager/heapRetained/fairShareConstraintCreateForm

This resource manages the create forms for the fairShareConstraint optional singleton instance.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.FairShareConstraintMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the [fairShareConstraint](#) optional singleton resource to create a new instance if it currently does not exist.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.FairShareConstraintMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceManager/heapRetained/fairShareConstraintCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceManager/heapRetained/fairShareConstraintCreateForm](#) **rel=create**

The optional singleton resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceManager/heapRetained](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceManager/heapRetained/fairShareConstraintCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/partitions/{name}/resourceManager/heapRetained/triggerCreateForm

This resource manages the create forms for the triggers collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.TriggerMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the triggers collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.TriggerMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceManager/heapRetained/triggerCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceManager/heapRetained/triggers](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceManager/heapRetained](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceManager/heapRetained/triggerCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/partitions/{name}/resourceManager/heapRetained/triggers

This resource manages a collection of [weblogic.management.configuration.TriggerMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.TriggerMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.TriggerMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceManager/heapRetained/triggers](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceManager/heapRetained/triggerCreateForm](#) **rel=create-form**

The create form resource for this collection resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceManager/heapRetained](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceManager/heapRetained/triggers](#) **rel=self**

This resource.

POST

Add a new [weblogic.management.configuration.TriggerMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.TriggerMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceManager/heapRetained/triggers/{name}

This resource manages a [weblogic.management.configuration.TriggerMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.TriggerMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.TriggerMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.TriggerMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceManager/heapRetained/triggers/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceManager/heapRetained/triggers](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceManager/heapRetained/triggers/{name}](#) **rel**=self

This resource.

POST

Update this [weblogic.management.configuration.TriggerMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.TriggerMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceManager/heapRetainedCreateForm

This resource manages the create forms for the heapRetained optional singleton instance.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.HeapRetainedMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the heapRetained optional singleton resource to create a new instance if it currently does not exist.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.HeapRetainedMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceManager/heapRetainedCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceManager/heapRetainedCreateForm](#) **rel=create**

The optional singleton resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceManager/heapRetainedCreateForm](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceManager/heapRetainedCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/partitions/{name}/resourceManager/restartLoopProtection

This resource manages a [weblogic.management.configuration.RestartLoopProtectionMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.RestartLoopProtectionMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.RestartLoopProtectionMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceManager/restartLoopProtection](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceManager](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/resourceManager/restartLoopProtection](#) **rel=self**
This resource.

POST

Update this [weblogic.management.configuration.RestartLoopProtectionMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.RestartLoopProtectionMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/resourceManagerCreateForm

This resource manages the create forms for the resourceManager optional singleton instance.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.ResourceManagerMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the resourceManager optional singleton resource to create a new instance if it currently does not exist.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ResourceManagerMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceManagerCreateForm](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceManagerCreateForm](#) **rel**=create
The optional singleton resource for this create form resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/resourceManagerCreateForm](#) **rel**=self
This resource.

/management/weblogic/{version}/edit/partitions/{name}/selfTuning

This resource manages a [weblogic.management.configuration.SelfTuningMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.SelfTuningMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SelfTuningMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/selfTuning](#)
[rel=canonical](#)
This resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/selfTuning/capacities](#)
[rel=capacities](#)
This resource's capacities collection resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/selfTuning/capacityCreateForm](#)
[rel=capacityCreateForm](#)
The create form resource for this resource's capacities collection resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/selfTuning/contextRequestClassCreateForm](#)
[rel=contextRequestClassCreateForm](#)
The create form resource for this resource's contextRequestClasses collection resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/selfTuning/contextRequestClasses](#)
[rel=contextRequestClasses](#)
This resource's contextRequestClasses collection resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/selfTuning/fairShareRequestClassCreateForm](#)
[rel=fairShareRequestClassCreateForm](#)
The create form resource for this resource's fairShareRequestClasses collection resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/selfTuning/fairShareRequestClasses](#)
[rel=fairShareRequestClasses](#)
This resource's fairShareRequestClasses collection resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/selfTuning/maxThreadsConstraintCreateForm](#)
[rel=maxThreadsConstraintCreateForm](#)
The create form resource for this resource's maxThreadsConstraints collection resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/selfTuning/maxThreadsConstraints](#)
[rel=maxThreadsConstraints](#)
This resource's maxThreadsConstraints collection resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/selfTuning/minThreadsConstraintCreateForm](#)
[rel=minThreadsConstraintCreateForm](#)

The create form resource for this resource's minThreadsConstraints collection resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/selfTuning/minThreadsConstraints **rel**=minThreadsConstraints

This resource's minThreadsConstraints collection resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/selfTuning/responseTimeRequestClassCreateForm **rel**=responseTimeRequestClassCreateForm

The create form resource for this resource's responseTimeRequestClasses collection resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/selfTuning/responseTimeRequestClasses **rel**=responseTimeRequestClasses

This resource's responseTimeRequestClasses collection resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/selfTuning **rel**=self

This resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/selfTuning/workManagerCreateForm **rel**=workManagerCreateForm

The create form resource for this resource's workManagers collection resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/selfTuning/workManagers **rel**=workManagers

This resource's workManagers collection resource.

POST

POST

Update this [weblogic.management.configuration.SelfTuningMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.SelfTuningMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/selfTuning/capacities

This resource manages a collection of [weblogic.management.configuration.CapacityMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.CapacityMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.CapacityMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/selfTuning/capacities](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/selfTuning/capacityCreateForm](#) **rel**=create-form
The create form resource for this collection resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/selfTuning](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/selfTuning/capacities](#) **rel**=self
This resource.

POST

Add a new [weblogic.management.configuration.CapacityMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.CapacityMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/selfTuning/capacities/{name}

This resource manages a [weblogic.management.configuration.CapacityMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.CapacityMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.CapacityMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.CapacityMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/selfTuning/capacities/{name}](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/selfTuning/capacities](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/selfTuning/capacities/{name}](#) **rel**=self
This resource.

POST

Update this [weblogic.management.configuration.CapacityMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.CapacityMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/selfTuning/capacityCreateForm

This resource manages the create forms for the capacities collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.CapacityMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the capacities collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.CapacityMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/selfTuning/capacityCreateForm](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/selfTuning/capacities](#) **rel=create**
The collection resource for this create form resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/selfTuning](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/selfTuning/capacityCreateForm](#) **rel=self**
This resource.

/management/weblogic/{version}/edit/partitions/{name}/selfTuning/contextRequestClassCreateForm

This resource manages the create forms for the contextRequestClasses collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.ContextRequestClassMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the contextRequestClasses collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ContextRequestClassMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/selfTuning/contextRequestClassCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/selfTuning/contextRequestClasses](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/selfTuning](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/selfTuning/contextRequestClassCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/partitions/{name}/selfTuning/contextRequestClasses

This resource manages a collection of [weblogic.management.configuration.ContextRequestClassMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.ContextRequestClassMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.ContextRequestClassMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/selfTuning/contextRequestClasses](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/selfTuning/contextRequestClassCreateForm](#) **rel=create-form**
The create form resource for this collection resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/selfTuning](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/selfTuning/contextRequestClasses](#) **rel=self**
This resource.

POST

Add a new [weblogic.management.configuration.ContextRequestClassMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.ContextRequestClassMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/selfTuning/contextRequestClasses/{name}

This resource manages a [weblogic.management.configuration.ContextRequestClassMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

DELETE

Delete this [weblogic.management.configuration.ContextRequestClassMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.ContextRequestClassMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ContextRequestClassMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/selfTuning/contextRequestClasses/{name}](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/selfTuning/contextRequestClasses/{name}/contextCaseCreateForm](#) **rel=contextCaseCreateForm**
The create form resource for this resource's contextCases collection resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/selfTuning/contextRequestClasses/{name}/contextCases](#) **rel=contextCases**
This resource's contextCases collection resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/selfTuning/contextRequestClasses](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/selfTuning/contextRequestClasses/{name}](#) **rel=self**
This resource.

POST

Update this [weblogic.management.configuration.ContextRequestClassMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.ContextRequestClassMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/selfTuning/contextRequestClasses/{name}/contextCaseCreateForm

This resource manages the create forms for the contextCases collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.ContextCaseMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the contextCases collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ContextCaseMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/selfTuning/contextRequestClasses/{name}/contextCaseCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/selfTuning/contextRequestClasses/{name}/contextCases](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/selfTuning/contextRequestClasses/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/selfTuning/contextRequestClasses/{name}/contextCaseCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/partitions/{name}/selfTuning/contextRequestClasses/{name}/contextCases

This resource manages a collection of [weblogic.management.configuration.ContextCaseMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.ContextCaseMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.ContextCaseMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/selfTuning/contextRequestClasses/{name}/contextCases](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/selfTuning/contextRequestClasses/{name}/contextCaseCreateForm](#) **rel=create-form**

The create form resource for this collection resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/selfTuning/contextRequestClasses/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/selfTuning/contextRequestClasses/{name}/contextCases](#) **rel=self**

This resource.

POST

Add a new [weblogic.management.configuration.ContextCaseMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.ContextCaseMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/selfTuning/contextRequestClasses/{name}/contextCases/{name}

This resource manages a [weblogic.management.configuration.ContextCaseMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.ContextCaseMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.ContextCaseMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ContextCaseMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/selfTuning/contextRequestClasses/{name}/contextCases/{name}](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/selfTuning/contextRequestClasses/{name}/contextCases/{name}/fairShareRequestClass](#) **rel=fairShareRequestClass**

This resource's fairShareRequestClass singleton resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/selfTuning/contextRequestClasses/{name}/contextCases/{name}/fairShareRequestClassCreateForm](#) **rel=fairShareRequestClassCreateForm**

The create form resource for this resource's fairShareRequestClass optional singleton resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/selfTuning/contextRequestClasses/{name}/contextCases](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/selfTuning/contextRequestClasses/{name}/contextCases/{name}/responseTimeRequestClass](#) **rel=responseTimeRequestClass**

This resource's responseTimeRequestClass singleton resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/selfTuning/contextRequestClasses/{name}/contextCases/{name}/responseTimeRequestClassCreateForm](#) **rel=responseTimeRequestClassCreateForm**

The create form resource for this resource's responseTimeRequestClass optional singleton resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/selfTuning/contextRequestClasses/{name}/contextCases/{name}](#) **rel=self**

This resource.

POST

Update this [weblogic.management.configuration.ContextCaseMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.ContextCaseMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/selfTuning/contextRequestClasses/{name}/contextCases/{name}/fairShareRequestClass

This resource manages a [weblogic.management.configuration.FairShareRequestClassMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.FairShareRequestClassMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.FairShareRequestClassMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.FairShareRequestClassMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/selfTuning/contextRequestClasses/{name}/contextCases/{name}/fairShareRequestClass](#)
rel=canonical

This resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/selfTuning/contextRequestClasses/{name}/contextCases/{name}/fairShareRequestClassCreateForm](#)
rel=create-form

The create form resource for this optional singleton resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/selfTuning/contextRequestClasses/{name}/contextCases/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/selfTuning/contextRequestClasses/{name}/contextCases/{name}/fairShareRequestClass](#) **rel=self**

This resource.

POST

Update this [weblogic.management.configuration.FairShareRequestClassMBean](#) instance if it exists; otherwise, create it.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.FairShareRequestClassMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/selfTuning/contextRequestClasses/{name}/contextCases/{name}/fairShareRequestClassCreateForm

This resource manages the create forms for the fairShareRequestClass optional singleton instance.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.FairShareRequestClassMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the [fairShareRequestClass](#) optional singleton resource to create a new instance if it currently does not exist.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.FairShareRequestClassMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/selfTuning/contextRequestClasses/{name}/contextCases/{name}/fairShareRequestClassCreateForm](#)
rel=canonical

This resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/selfTuning/contextRequestClasses/{name}/contextCases/{name}/fairShareRequestClassCreateForm](#)
rel=create

The optional singleton resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/selfTuning/contextRequestClasses/{name}/contextCases/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/selfTuning/contextRequestClasses/{name}/contextCases/{name}/fairShareRequestClassCreateForm](#)
rel=self

This resource.

/management/weblogic/{version}/edit/partitions/{name}/selfTuning/contextRequestClasses/{name}/contextCases/{name}/responseTimeRequestClass

This resource manages a [weblogic.management.configuration.ResponseTimeRequestClassMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.ResponseTimeRequestClassMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.ResponseTimeRequestClassMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ResponseTimeRequestClassMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/selfTuning/contextRequestClasses/{name}/contextCases/{name}/responseTimeRequestClass](#)
rel=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/selfTuning/contextRequestClasses/{name}/contextCases/{name}/responseTimeRequestClassCreateForm](#) **rel**=create-form

The create form resource for this optional singleton resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/selfTuning/contextRequestClasses/{name}/contextCases/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/selfTuning/contextRequestClasses/{name}/contextCases/{name}/responseTimeRequestClass](#)
rel=self

This resource.

POST

Update this [weblogic.management.configuration.ResponseTimeRequestClassMBean](#) instance if it exists; otherwise, create it.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.ResponseTimeRequestClassMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/selfTuning/contextRequestClasses/{name}/contextCases/{name}/responseTimeRequestClassCreateForm

This resource manages the create forms for the responseTimeRequestClass optional singleton instance.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.ResponseTimeRequestClassMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the responseTimeRequestClass optional singleton resource to create a new instance if it currently does not exist.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ResponseTimeRequestClassMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/selfTuning/contextRequestClasses/{name}/contextCases/{name}/responseTimeRequestClassCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/selfTuning/contextRequestClasses/{name}/contextCases/{name}/responseTimeRequestClassCreateForm](#) **rel=create**

The optional singleton resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/selfTuning/contextRequestClasses/{name}/contextCases/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/selfTuning/contextRequestClasses/{name}/contextCases/{name}/responseTimeRequestClassCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/partitions/{name}/selfTuning/fairShareRequestClassCreateForm

This resource manages the create forms for the fairShareRequestClasses collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.FairShareRequestClassMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the [fairShareRequestClasses](#) collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.FairShareRequestClassMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/selfTuning/fairShareRequestClassCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/selfTuning/fairShareRequestClasses](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/selfTuning](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/selfTuning/fairShareRequestClassCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/partitions/{name}/selfTuning/fairShareRequestClasses

This resource manages a collection of [weblogic.management.configuration.FairShareRequestClassMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.FairShareRequestClassMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.FairShareRequestClassMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/selfTuning/fairShareRequestClasses](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/selfTuning/fairShareRequestClassCreateForm](#) **rel=create-form**
The create form resource for this collection resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/selfTuning](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/selfTuning/fairShareRequestClasses](#) **rel=self**
This resource.

POST

Add a new [weblogic.management.configuration.FairShareRequestClassMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.FairShareRequestClassMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/selfTuning/fairShareRequestClasses/{name}

This resource manages a [weblogic.management.configuration.FairShareRequestClassMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.FairShareRequestClassMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.FairShareRequestClassMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.FairShareRequestClassMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/selfTuning/fairShareRequestClasses/{name}](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/selfTuning/fairShareRequestClasses](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/selfTuning/fairShareRequestClasses/{name}](#) **rel=self**

This resource.

POST

Update this [weblogic.management.configuration.FairShareRequestClassMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.FairShareRequestClassMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/selfTuning/maxThreadsConstraintCreateForm

This resource manages the create forms for the maxThreadsConstraints collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.MaxThreadsConstraintMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the `maxThreadsConstraints` collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.MaxThreadsConstraintMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/selfTuning/maxThreadsConstraintCreateForm](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/selfTuning/maxThreadsConstraints](#) **rel**=create

The collection resource for this create form resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/selfTuning](#)
rel=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/selfTuning/maxThreadsConstraintCreateForm](#) **rel**=self

This resource.

/management/weblogic/{version}/edit/partitions/{name}/selfTuning/maxThreadsConstraints

This resource manages a collection of [weblogic.management.configuration.MaxThreadsConstraintMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.MaxThreadsConstraintMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.MaxThreadsConstraintMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/selfTuning/maxThreadsConstraints](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/selfTuning/maxThreadsConstraintCreateForm](#) **rel**=create-form

The create form resource for this collection resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/selfTuning](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/selfTuning/maxThreadsConstraints](#) **rel**=self

This resource.

POST

Add a new [weblogic.management.configuration.MaxThreadsConstraintMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.MaxThreadsConstraintMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/selfTuning/maxThreadsConstraints/{name}

This resource manages a [weblogic.management.configuration.MaxThreadsConstraintMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.MaxThreadsConstraintMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.MaxThreadsConstraintMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.MaxThreadsConstraintMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/selfTuning/maxThreadsConstraints/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/selfTuning/maxThreadsConstraints](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/selfTuning/maxThreadsConstraints/{name}](#) **rel**=self

This resource.

POST

Update this [weblogic.management.configuration.MaxThreadsConstraintMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.MaxThreadsConstraintMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/selfTuning/minThreadsConstraintCreateForm

This resource manages the create forms for the minThreadsConstraints collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.MinThreadsConstraintMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the minThreadsConstraints collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.MinThreadsConstraintMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/selfTuning/minThreadsConstraintCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/selfTuning/minThreadsConstraints](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/selfTuning](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/selfTuning/minThreadsConstraintCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/partitions/{name}/selfTuning/minThreadsConstraints

This resource manages a collection of [weblogic.management.configuration.MinThreadsConstraintMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.MinThreadsConstraintMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.MinThreadsConstraintMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/selfTuning/minThreadsConstraints](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/selfTuning/minThreadsConstraintCreateForm](#) **rel=create-form**
The create form resource for this collection resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/selfTuning](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/selfTuning/minThreadsConstraints](#) **rel=self**
This resource.

POST

Add a new [weblogic.management.configuration.MinThreadsConstraintMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.MinThreadsConstraintMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/selfTuning/minThreadsConstraints/{name}

This resource manages a [weblogic.management.configuration.MinThreadsConstraintMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.MinThreadsConstraintMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.MinThreadsConstraintMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.MinThreadsConstraintMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/selfTuning/minThreadsConstraints/{name}](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/selfTuning/minThreadsConstraints](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/selfTuning/minThreadsConstraints/{name}](#) **rel**=self
This resource.

POST

Update this [weblogic.management.configuration.MinThreadsConstraintMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.MinThreadsConstraintMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/selfTuning/responseTimeRequestClassCreateForm

This resource manages the create forms for the responseTimeRequestClasses collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.ResponseTimeRequestClassMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the [responseTimeRequestClasses](#) collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ResponseTimeRequestClassMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/selfTuning/responseTimeRequestClassCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/selfTuning/responseTimeRequestClasses](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/selfTuning](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/selfTuning/responseTimeRequestClassCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/partitions/{name}/selfTuning/responseTimeRequestClasses

This resource manages a collection of [weblogic.management.configuration.ResponseTimeRequestClassMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.ResponseTimeRequestClassMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.ResponseTimeRequestClassMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/selfTuning/responseTimeRequestClasses](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/selfTuning/responseTimeRequestClassCreateForm](#) **rel**=create-form
The create form resource for this collection resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/selfTuning](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/selfTuning/responseTimeRequestClasses](#) **rel**=self
This resource.

POST

Add a new [weblogic.management.configuration.ResponseTimeRequestClassMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.ResponseTimeRequestClassMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/selfTuning/responseTimeRequestClasses/{name}

This resource manages a [weblogic.management.configuration.ResponseTimeRequestClassMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.ResponseTimeRequestClassMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.ResponseTimeRequestClassMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ResponseTimeRequestClassMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/selfTuning/responseTimeRequestClasses/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/selfTuning/responseTimeRequestClasses](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/selfTuning/responseTimeRequestClasses/{name}](#) **rel**=self

This resource.

POST

Update this [weblogic.management.configuration.ResponseTimeRequestClassMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.ResponseTimeRequestClassMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/selfTuning/workManagerCreateForm

This resource manages the create forms for the workManagers collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.WorkManagerMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the workManagers collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.WorkManagerMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/selfTuning/workManagerCreateForm](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/selfTuning/workManagers](#) **rel=create**
The collection resource for this create form resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/selfTuning](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/selfTuning/workManagerCreateForm](#) **rel=self**
This resource.

/management/weblogic/{version}/edit/partitions/{name}/selfTuning/workManagers

This resource manages a collection of [weblogic.management.configuration.WorkManagerMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.WorkManagerMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.WorkManagerMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/selfTuning/workManagers](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/selfTuning/workManagerCreateForm](#) **rel=create-form**
The create form resource for this collection resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/selfTuning](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/selfTuning/workManagers](#) **rel=self**
This resource.

POST

Add a new [weblogic.management.configuration.WorkManagerMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.WorkManagerMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/selfTuning/workManagers/{name}

This resource manages a [weblogic.management.configuration.WorkManagerMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

DELETE

Delete this [weblogic.management.configuration.WorkManagerMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.WorkManagerMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.WorkManagerMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/selfTuning/workManagers/{name}](#) **rel**=canonical
This resource.
- **rel**=capacity
This resource's capacity reference to a [weblogic.management.configuration.CapacityMBean](#) resource.
- **rel**=contextRequestClass
This resource's contextRequestClass reference to a [weblogic.management.configuration.ContextRequestClassMBean](#) resource.
- **rel**=fairShareRequestClass
This resource's fairShareRequestClass reference to a [weblogic.management.configuration.FairShareRequestClassMBean](#) resource.
- **rel**=maxThreadsConstraint
This resource's maxThreadsConstraint reference to a [weblogic.management.configuration.MaxThreadsConstraintMBean](#) resource.
- **rel**=minThreadsConstraint
This resource's minThreadsConstraint reference to a [weblogic.management.configuration.MinThreadsConstraintMBean](#) resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/selfTuning/workManagers](#) **rel**=parent
The parent resource of this resource.
- **rel**=responseTimeRequestClass
This resource's responseTimeRequestClass reference to a [weblogic.management.configuration.ResponseTimeRequestClassMBean](#) resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/selfTuning/workManagers/{name}](#) **rel**=self
This resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/selfTuning/workManagers/{name}/workManagerShutdownTrigger](#) **rel**=workManagerShutdownTrigger
This resource's workManagerShutdownTrigger singleton resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/selfTuning/workManagers/{name}/workManagerShutdownTriggerCreateForm
rel=workManagerShutdownTriggerCreateForm

The create form resource for this resource's workManagerShutdownTrigger optional singleton resource.

POST

Update this [weblogic.management.configuration.WorkManagerMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.WorkManagerMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/selfTuning/workManagers/{name}/workManagerShutdownTrigger

This resource manages a [weblogic.management.configuration.WorkManagerShutdownTriggerMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this

[weblogic.management.configuration.WorkManagerShutdownTriggerMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.WorkManagerShutdownTriggerMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.WorkManagerShutdownTriggerMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/selfTuning/workManagers/{name}/workManagerShutdownTrigger **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/selfTuning/workManagers/{name}/workManagerShutdownTriggerCreateForm **rel**=create-form

The create form resource for this optional singleton resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/selfTuning/workManagers/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/selfTuning/workManagers/{name}/workManagerShutdownTrigger **rel**=self

This resource.

POST

Update this [weblogic.management.configuration.WorkManagerShutdownTriggerMBean](#) instance if it exists; otherwise, create it.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.WorkManagerShutdownTriggerMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/selfTuning/workManagers/{name}/workManagerShutdownTriggerCreateForm

This resource manages the create forms for the workManagerShutdownTrigger optional singleton instance.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.WorkManagerShutdownTriggerMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the workManagerShutdownTrigger optional singleton resource to create a new instance if it currently does not exist.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.WorkManagerShutdownTriggerMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/selfTuning/workManagers/{name}/workManagerShutdownTriggerCreateForm](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/selfTuning/workManagers/{name}/workManagerShutdownTriggerCreateForm](#) **rel=create**
The optional singleton resource for this create form resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/selfTuning/workManagers/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/selfTuning/workManagers/{name}/workManagerShutdownTriggerCreateForm](#) **rel=self**
This resource.

/management/weblogic/{version}/edit/partitions/{name}/systemFileSystem

This resource manages a [weblogic.management.configuration.PartitionFileSystemMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.PartitionFileSystemMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.PartitionFileSystemMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/systemFileSystem](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/systemFileSystem](#)
rel=self
This resource.

POST

POST

Update this [weblogic.management.configuration.PartitionFileSystemMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.PartitionFileSystemMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/userFileSystem

This resource manages a [weblogic.management.configuration.PartitionUserFileSystemMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.PartitionUserFileSystemMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.PartitionUserFileSystemMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/userFileSystem](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/userFileSystem](#)
rel=self
This resource.

POST

Update this [weblogic.management.configuration.PartitionUserFileSystemMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.PartitionUserFileSystemMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/webService

This resource manages a [weblogic.management.configuration.WebServiceMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.WebServiceMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.WebServiceMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/webService](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/webService](#)
rel=self
This resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/webService/webServiceBuffering](#) **rel**=webServiceBuffering
This resource's webServiceBuffering singleton resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/webService/webServicePersistence](#) **rel**=webServicePersistence
This resource's webServicePersistence singleton resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/webService/webServiceReliability](#) **rel**=webServiceReliability
This resource's webServiceReliability singleton resource.

POST

POST

Update this [weblogic.management.configuration.WebServiceMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.WebServiceMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/webService/webServiceBuffering

This resource manages a [weblogic.management.configuration.WebServiceBufferingMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.WebServiceBufferingMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.WebServiceBufferingMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/webService/webServiceBuffering](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/webService](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/webService/webServiceBuffering](#) **rel**=self

This resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/webService/webServiceBuffering/webServiceRequestBufferingQueue](#) **rel**=webServiceRequestBufferingQueue

This resource's webServiceRequestBufferingQueue singleton resource.

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/webService/webServiceBuffering/webServiceResponseBufferingQueue](#) **rel**=webServiceResponseBufferingQueue

This resource's webServiceResponseBufferingQueue singleton resource.

POST

Update this [weblogic.management.configuration.WebServiceBufferingMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.WebServiceBufferingMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/webService/webServiceBuffering/webServiceRequestBufferingQueue

This resource manages a [weblogic.management.configuration.WebServiceRequestBufferingQueueMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.WebServiceRequestBufferingQueueMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.WebServiceRequestBufferingQueueMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/webService/webServiceBuffering/webServiceRequestBufferingQueue](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/webService/webServiceBuffering](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/webService/webServiceBuffering/webServiceRequestBufferingQueue](#) **rel=self**

This resource.

POST

Update this [weblogic.management.configuration.WebServiceRequestBufferingQueueMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.WebServiceRequestBufferingQueueMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/webService/webServiceBuffering/webServiceResponseBufferingQueue

This resource manages a [weblogic.management.configuration.WebServiceResponseBufferingQueueMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.WebServiceResponseBufferingQueueMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.WebServiceResponseBufferingQueueMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/webService/webServiceBuffering/webServiceResponseBufferingQueue](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/webService/webServiceBuffering](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/webService/webServiceBuffering/webServiceResponseBufferingQueue](#) **rel**=self
This resource.

POST

Update this [weblogic.management.configuration.WebServiceResponseBufferingQueueMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.WebServiceResponseBufferingQueueMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/webService/webServicePersistence

This resource manages a [weblogic.management.configuration.WebServicePersistenceMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.WebServicePersistenceMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.WebServicePersistenceMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/webService/webServicePersistence](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/webService](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/webService/webServicePersistence](#) **rel=self**
This resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/webService/webServicePersistence/webServiceLogicalStoreCreateForm](#) **rel=webServiceLogicalStoreCreateForm**
The create form resource for this resource's webServiceLogicalStores collection resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/webService/webServicePersistence/webServiceLogicalStores](#) **rel=webServiceLogicalStores**
This resource's webServiceLogicalStores collection resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/webService/webServicePersistence/webServicePhysicalStoreCreateForm](#) **rel=webServicePhysicalStoreCreateForm**
The create form resource for this resource's webServicePhysicalStores collection resource.
- [uri=/management/weblogic/{version}/edit/partitions/{name}/webService/webServicePersistence/webServicePhysicalStores](#) **rel=webServicePhysicalStores**
This resource's webServicePhysicalStores collection resource.

POST

Update this [weblogic.management.configuration.WebServicePersistenceMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.WebServicePersistenceMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/webService/webServicePersistence/webServiceLogicalStoreCreateForm

This resource manages the create forms for the webServiceLogicalStores collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.WebServiceLogicalStoreMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the [webServiceLogicalStores](#) collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.WebServiceLogicalStoreMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/webService/webServicePersistence/webServiceLogicalStoreCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/webService/webServicePersistence/webServiceLogicalStores](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/webService/webServicePersistence](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/webService/webServicePersistence/webServiceLogicalStoreCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/partitions/{name}/webService/webServicePersistence/webServiceLogicalStores

This resource manages a collection of [weblogic.management.configuration.WebServiceLogicalStoreMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.WebServiceLogicalStoreMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.WebServiceLogicalStoreMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/webService/webServicePersistence/webServiceLogicalStores **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/webService/webServicePersistence/webServiceLogicalStoreCreateForm **rel**=create-form

The create form resource for this collection resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/webService/webServicePersistence **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/webService/webServicePersistence/webServiceLogicalStores **rel**=self

This resource.

POST

Add a new [weblogic.management.configuration.WebServiceLogicalStoreMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.WebServiceLogicalStoreMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/webService/webServicePersistence/webServiceLogicalStores/{name}

This resource manages a [weblogic.management.configuration.WebServiceLogicalStoreMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.WebServiceLogicalStoreMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.WebServiceLogicalStoreMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.WebServiceLogicalStoreMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/webService/webServicePersistence/webServiceLogicalStores/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/webService/webServicePersistence/webServiceLogicalStores **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/webService/webServicePersistence/webServiceLogicalStores/{name} **rel**=self

This resource.

POST

Update this [weblogic.management.configuration.WebServiceLogicalStoreMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.WebServiceLogicalStoreMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/webService/webServicePersistence/webServicePhysicalStoreCreateForm

This resource manages the create forms for the webServicePhysicalStores collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.WebServicePhysicalStoreMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the `webServicePhysicalStores` collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.WebServicePhysicalStoreMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/webService/webServicePersistence/webServicePhysicalStoreCreateForm](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/webService/webServicePersistence/webServicePhysicalStores](#) **rel**=create
The collection resource for this create form resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/webService/webServicePersistence](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/webService/webServicePersistence/webServicePhysicalStoreCreateForm](#) **rel**=self
This resource.

/management/weblogic/{version}/edit/partitions/{name}/webService/webServicePersistence/webServicePhysicalStores

This resource manages a collection of [weblogic.management.configuration.WebServicePhysicalStoreMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.WebServicePhysicalStoreMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.WebServicePhysicalStoreMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitions/{name}/webService/webServicePersistence/webServicePhysicalStores](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/webService/webServicePersistence/webServicePhysicalStoreCreateForm](#) **rel=create-form**

The create form resource for this collection resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/webService/webServicePersistence](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/partitions/{name}/webService/webServicePersistence/webServicePhysicalStores](#) **rel=self**

This resource.

POST

Add a new [weblogic.management.configuration.WebServicePhysicalStoreMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.WebServicePhysicalStoreMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/webService/webServicePersistence/webServicePhysicalStores/{name}

This resource manages a [weblogic.management.configuration.WebServicePhysicalStoreMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.WebServicePhysicalStoreMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.WebServicePhysicalStoreMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.WebServicePhysicalStoreMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/webService/webServicePersistence/webServicePhysicalStores/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/webService/webServicePersistence/webServicePhysicalStores **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/partitions/{name}/webService/webServicePersistence/webServicePhysicalStores/{name} **rel**=self

This resource.

POST

Update this [weblogic.management.configuration.WebServicePhysicalStoreMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.WebServicePhysicalStoreMBean](#) entity.

/management/weblogic/{version}/edit/partitions/{name}/webService/webServiceReliability

This resource manages a [weblogic.management.configuration.WebServiceReliabilityMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.WebServiceReliabilityMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.WebServiceReliabilityMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/webService/webServiceReliability](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/webService](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/partitions/{name}/webService/webServiceReliability](#) **rel**=self
This resource.

POST

Update this [weblogic.management.configuration.WebServiceReliabilityMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.WebServiceReliabilityMBean](#) entity.

/management/weblogic/{version}/edit/partitionWorkManagerCreateForm

This resource manages the create forms for the partitionWorkManagers collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.PartitionWorkManagerMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the `partitionWorkManagers` collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.PartitionWorkManagerMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitionWorkManagerCreateForm](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/partitionWorkManagers](#) **rel**=create
The collection resource for this create form resource.
- **uri**=[/management/weblogic/{version}/edit](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/partitionWorkManagerCreateForm](#)
rel=self
This resource.

/management/weblogic/{version}/edit/partitionWorkManagers

This resource manages a collection of [weblogic.management.configuration.PartitionWorkManagerMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.PartitionWorkManagerMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.PartitionWorkManagerMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/partitionWorkManagers](#)
[rel=canonical](#)
This resource.
- [uri=/management/weblogic/{version}/edit/partitionWorkManagerCreateForm](#)
[rel=create-form](#)
The create form resource for this collection resource.
- [uri=/management/weblogic/{version}/edit](#) [rel=parent](#)
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/partitionWorkManagers](#) [rel=self](#)
This resource.

POST

Add a new [weblogic.management.configuration.PartitionWorkManagerMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.PartitionWorkManagerMBean](#) entity.

/management/weblogic/{version}/edit/partitionWorkManagers/{name}

This resource manages a [weblogic.management.configuration.PartitionWorkManagerMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.PartitionWorkManagerMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.PartitionWorkManagerMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.PartitionWorkManagerMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/partitionWorkManagers/{name}](#)
rel=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/partitionWorkManagers](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/partitionWorkManagers/{name}](#)
rel=self

This resource.

POST

Update this [weblogic.management.configuration.PartitionWorkManagerMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.PartitionWorkManagerMBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupCreateForm

This resource manages the create forms for the resourceGroups collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.ResourceGroupMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the resourceGroups collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ResourceGroupMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroupCreateForm](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroups](#) **rel**=create
The collection resource for this create form resource.
- **uri**=[/management/weblogic/{version}/edit](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroupCreateForm](#) **rel**=self
This resource.

/management/weblogic/{version}/edit/resourceGroups

This resource manages a collection of [weblogic.management.configuration.ResourceGroupMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.ResourceGroupMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.ResourceGroupMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroups](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroupCreateForm](#)
rel=create-form
The create form resource for this collection resource.
- **uri**=[/management/weblogic/{version}/edit](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroups](#) **rel**=self
This resource.

POST

Add a new [weblogic.management.configuration.ResourceGroupMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.ResourceGroupMBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}

This resource manages a [weblogic.management.configuration.ResourceGroupMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.ResourceGroupMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.ResourceGroupMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ResourceGroupMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCStoreCreateForm](#) [rel=JDBCStoreCreateForm](#)

The create form resource for this resource's JDBCStores collection resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCStores](#) [rel=JDBCStores](#)

This resource's JDBCStores collection resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResourceCreateForm](#) [rel=JDBCSystemResourceCreateForm](#)

The create form resource for this resource's JDBCSystemResources collection resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources](#) [rel=JDBCSystemResources](#)

This resource's JDBCSystemResources collection resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSBridgeDestinationCreateForm](#) [rel=JMSBridgeDestinationCreateForm](#)

The create form resource for this resource's JMSBridgeDestinations collection resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSBridgeDestinations](#) [rel=JMSBridgeDestinations](#)

This resource's JMSBridgeDestinations collection resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSServerCreateForm](#) [rel=JMSServerCreateForm](#)

The create form resource for this resource's JMSServers collection resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSServers](#) [rel=JMSServers](#)

This resource's JMSServers collection resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResourceCreateForm](#) [rel=JMSSystemResourceCreateForm](#)

The create form resource for this resource's JMSSystemResources collection resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources](#) [rel=JMSSystemResources](#)

This resource's JMSSystemResources collection resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/SAFAgentCreateForm **rel**=SAFAgentCreateForm

The create form resource for this resource's SAFAgents collection resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/SAFAgentCreateForm **rel**=SAFAgentCreateForm

This resource's SAFAgents collection resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResourceCreateForm **rel**=WLDFSystemResourceCreateForm

The create form resource for this resource's WLDFSystemResources collection resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources **rel**=WLDFSystemResources

This resource's WLDFSystemResources collection resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/findEffectiveTargets **rel**=action **title**=findEffectiveTargets

This resource's findEffectiveTargets action resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/lookupTarget **rel**=action **title**=lookupTarget

This resource's lookupTarget action resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/appDeployments **rel**=appDeployments

This resource's appDeployments collection resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/fileStoreCreateForm **rel**=fileStoreCreateForm

The create form resource for this resource's fileStores collection resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/fileStores **rel**=fileStores

This resource's fileStores collection resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/foreignJNDIProviderCreateForm **rel**=foreignJNDIProviderCreateForm

The create form resource for this resource's foreignJNDIProviders collection resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/foreignJNDIProviders **rel**=foreignJNDIProviders

This resource's foreignJNDIProviders collection resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/libraries **rel**=libraries

This resource's libraries collection resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/mailSessionCreateForm **rel**=mailSessionCreateForm
The create form resource for this resource's mailSessions collection resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/mailSessions **rel**=mailSessions
This resource's mailSessions collection resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/managedExecutorServiceCreateForm **rel**=managedExecutorServiceCreateForm
The create form resource for this resource's managedExecutorServices collection resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/managedExecutorServices **rel**=managedExecutorServices
This resource's managedExecutorServices collection resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/managedScheduledExecutorServiceCreateForm **rel**=managedScheduledExecutorServiceCreateForm
The create form resource for this resource's managedScheduledExecutorServices collection resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/managedScheduledExecutorServices **rel**=managedScheduledExecutorServices
This resource's managedScheduledExecutorServices collection resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/managedThreadFactories **rel**=managedThreadFactories
This resource's managedThreadFactories collection resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/managedThreadFactoryCreateForm **rel**=managedThreadFactoryCreateForm
The create form resource for this resource's managedThreadFactories collection resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/messagingBridgeCreateForm **rel**=messagingBridgeCreateForm
The create form resource for this resource's messagingBridges collection resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/messagingBridges **rel**=messagingBridges
This resource's messagingBridges collection resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/osgiFrameworkCreateForm **rel**=osgiFrameworkCreateForm
The create form resource for this resource's osgiFrameworks collection resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/osgiFrameworks **rel**=osgiFrameworks
This resource's osgiFrameworks collection resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroups **rel**=parent
The parent resource of this resource.

- **rel=resourceGroupTemplate**
This resource's resourceGroupTemplate reference to a weblogic.management.configuration.ResourceGroupTemplateMBean resource.
- **uri=/management/weblogic/{version}/edit/resourceGroups/{name} rel=self**
This resource.

POST

Update this [weblogic.management.configuration.ResourceGroupMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.ResourceGroupMBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/appDeployments

This resource manages a collection of [weblogic.management.configuration.AppDeploymentMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.AppDeploymentMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.AppDeploymentMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/appDeployments](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/appDeployments](#) **rel**=self
This resource.

POST

The resource supports the following methods:

- [POST accepting application/json](#)
- [POST accepting multipart/form-data](#)

POST accepting application/json

This resource deploy is used to deploy applications that are already on the administration server. The application must be a supported package type (for example, an EAR or WAR module).

This method supports both asynchronous and best effort synchronous invocations. The behavior is controlled by the 'Prefer' header. See [About Synchronous and Asynchronous Operations](#).

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.AppDeploymentMBean](#) entity.

To deploy an application you must provide the name of the application, the path to the source of the deployable unit on the administration server, and the targets to which the application will be deployed.

If the source path is relative, it is resolved relative to *InstallDir/app* if *InstallDir* is not null; otherwise, it is resolved relative to the domain root.

POST accepting multipart/form-data

Use the multi-part form to upload an application from the client to the server and then deploy it.

- `sourcePath`: the deployment to upload (required)
- `planPath`: the deployment plan to upload (optional)
- `model`: JSONObject containing an `AppDeploymentMBean` entity that contains the rest of the deployment information (however, `deployment/plan` information is ignored) (required)

This method supports both asynchronous and best effort synchronous invocations. The behavior is controlled by the 'Prefer' header. See [About Synchronous and Asynchronous Operations](#).

Roles

Admin, Deployer

Request Body

Use the multi-part form to deploy an application.

- `sourcePath`: the deployment to upload (required)
- `planPath`: the deployment plan to upload (optional)

- model: JSONObject containing an AppDeploymentMBean entity that contains the rest of the deployment information. However, deployment/plan information is ignored. (required)

/management/weblogic/{version}/edit/resourceGroups/{name}/appDeployments/{name}

This resource manages a [weblogic.management.configuration.AppDeploymentMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Undeploy an application.

This method supports both asynchronous and best effort synchronous invocations. The behavior is controlled by the 'Prefer' header. See [About Synchronous and Asynchronous Operations](#).

Roles

Admin, Deployer

GET

Get this [weblogic.management.configuration.AppDeploymentMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.AppDeploymentMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/appDeployments/{name}/createPlan](#) **rel=action** **title=createPlan**
This resource's createPlan action resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/appDeployments/{name}](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/appDeployments](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/appDeployments/{name}/redeploy](#) **rel=redeploy**
This resource's redeploy resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/appDeployments/{name}](#) **rel=self**
This resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/appDeployments/{name}/subDeploymentCreateForm](#) **rel=subDeploymentCreateForm**
The create form resource for this resource's subDeployments collection resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/appDeployments/{name}/subDeployments](#) **rel=subDeployments**
This resource's subDeployments collection resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/appDeployments/{name}/update](#) **rel=update**
This resource's update resource.

POST

Update this [weblogic.management.configuration.AppDeploymentMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.AppDeploymentMBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/appDeployments/{name}/createPlan

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

POST

Create a deployment plan in the specified directory.

Roles

Admin, Deployer

Request Body

Must contain a JSON object with the following fields:

planPath

planPath

Type: string

Response Body

Contains a JSON object with a string return field.

POST

Create a deployment plan in a default directory

Roles

Admin, Deployer

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/edit/resourceGroups/{name}/appDeployments/{name}/redeploy

The resource supports the following methods:

- [POST](#)

POST

Use the multi-part form to redeploy this application.

- `sourcePath`: the deployment to upload (required)
- `planPath`: the deployment plan to upload (optional)
- `model`: JSONObject containing an `AppDeploymentMBean` entity that contains the rest of the deployment information. However, deployment/plan information is ignored. (required)

This method supports both asynchronous and best effort synchronous invocations. The behavior is controlled by the 'Prefer' header. See [About Synchronous and Asynchronous Operations](#).

Roles

Admin, Deployer

/management/weblogic/{version}/edit/resourceGroups/{name}/appDeployments/{name}/subDeploymentCreateForm

This resource manages the create forms for the subDeployments collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.SubDeploymentMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the subDeployments collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/appDeployments/{name}/subDeploymentCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/appDeployments/{name}/subDeployments](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/appDeployments/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/appDeployments/{name}/subDeploymentCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/resourceGroups/{name}/appDeployments/{name}/subDeployments

This resource manages a collection of [weblogic.management.configuration.SubDeploymentMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.SubDeploymentMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.SubDeploymentMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/appDeployments/{name}/subDeployments](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/appDeployments/{name}/subDeploymentCreateForm](#) **rel**=create-form

The create form resource for this collection resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/appDeployments/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/appDeployments/{name}/subDeployments](#) **rel**=self

This resource.

POST

Add a new [weblogic.management.configuration.SubDeploymentMBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/appDeployments/{name}/subDeployments/{name}

This resource manages a [weblogic.management.configuration.SubDeploymentMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/appDeployments/{name}/subDeployments/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/appDeployments/{name}/subDeployments](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/appDeployments/{name}/subDeployments/{name}](#) **rel**=self

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/appDeployments/{name}/subDeployments/{name}/subDeployments](#) **rel**=subDeployments

This resource's subDeployments collection resource.

POST

Update this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/appDeployments/{name}/subDeployments/{name}/subDeployments

This resource manages a collection of [weblogic.management.configuration.SubDeploymentMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.configuration.SubDeploymentMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.SubDeploymentMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/appDeployments/{name}/subDeployments/{name}/subDeployments](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/appDeployments/{name}/subDeployments/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/appDeployments/{name}/subDeployments/{name}/subDeployments](#) **rel**=self

This resource.

/management/weblogic/{version}/edit/resourceGroups/{name}/appDeployments/{name}/subDeployments/{name}/subDeployments/{name}

This resource manages a [weblogic.management.configuration.SubDeploymentMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/appDeployments/{name}/subDeployments/{name}/subDeployments/{name} **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/appDeployments/{name}/subDeployments/{name}/subDeployments **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/appDeployments/{name}/subDeployments/{name}/subDeployments/{name} **rel**=self
This resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/appDeployments/{name}/subDeployments/{name}/subDeployments/{name}/subDeployments **rel**=subDeployments
This resource's subDeployments collection resource.

POST

POST

Update this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/appDeployments/{name}/update

The resource supports the following methods:

- [POST](#)

POST

Update this application.

This method supports both asynchronous and best effort synchronous invocations. The behavior is controlled by the 'Prefer' header. See [About Synchronous and Asynchronous Operations](#).

Roles

Admin, Deployer

/management/weblogic/{version}/edit/resourceGroups/{name}/fileStoreCreateForm

This resource manages the create forms for the fileStores collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.FileStoreMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the fileStores collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.FileStoreMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/fileStoreCreateForm](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/fileStores](#) **rel**=create
The collection resource for this create form resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/fileStoreCreateForm](#) **rel**=self
This resource.

/management/weblogic/{version}/edit/resourceGroups/{name}/fileStores

This resource manages a collection of [weblogic.management.configuration.FileStoreMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.FileStoreMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.FileStoreMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/fileStores](#)
rel=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/fileStoreCreateForm](#) **rel**=create-form

The create form resource for this collection resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/fileStores](#)
rel=self

This resource.

POST

Add a new [weblogic.management.configuration.FileStoreMBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.FileStoreMBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/fileStores/{name}

This resource manages a [weblogic.management.configuration.FileStoreMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.FileStoreMBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.management.configuration.FileStoreMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.FileStoreMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/fileStores/{name}](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/fileStores](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/fileStores/{name}](#) **rel**=self
This resource.

POST

Update this [weblogic.management.configuration.FileStoreMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.FileStoreMBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/findEffectiveTargets

The resource supports the following methods:

- [POST](#)

POST

Returns the targets actually used by this resource group, accounting for partition-level defaulting.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a JSON object with a array of weblogic.management.configuration.TargetMBean references return field.

/management/weblogic/{version}/edit/resourceGroups/{name}/foreignJNDIProviderCreateForm

This resource manages the create forms for the foreignJNDIProviders collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.ForeignJNDIPProviderMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the [foreignJNDIPProviders](#) collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ForeignJNDIPProviderMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/foreignJNDIPProviderCreateForm](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/foreignJNDIPProviders](#) **rel=create**
The collection resource for this create form resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/foreignJNDIPProviderCreateForm](#) **rel=self**
This resource.

/management/weblogic/{version}/edit/resourceGroups/{name}/foreignJNDIProviders

This resource manages a collection of [weblogic.management.configuration.ForeignJNDIProviderMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.ForeignJNDIProviderMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.ForeignJNDIProviderMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/foreignJNDIProviders](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/foreignJNDIProviderCreateForm](#) **rel=create-form**
The create form resource for this collection resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/foreignJNDIProviders](#) **rel=self**
This resource.

POST

Add a new [weblogic.management.configuration.ForeignJNDIProviderMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.ForeignJNDIProviderMBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/foreignJNDIProviders/{name}

This resource manages a [weblogic.management.configuration.ForeignJNDIProviderMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

DELETE

Delete this [weblogic.management.configuration.ForeignJNDIProviderMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.ForeignJNDIProviderMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ForeignJNDIProviderMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/foreignJNDIProviders/{name}](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/foreignJNDIProviders/{name}/foreignJNDILinkCreateForm](#) **rel=foreignJNDILinkCreateForm**
The create form resource for this resource's foreignJNDILinks collection resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/foreignJNDIProviders/{name}/foreignJNDILinks](#) **rel=foreignJNDILinks**
This resource's foreignJNDILinks collection resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/foreignJNDIProviders](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/foreignJNDIProviders/{name}](#) **rel=self**
This resource.

POST

Update this [weblogic.management.configuration.ForeignJNDIProviderMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.ForeignJNDIProviderMBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/foreignJNDIProviders/{name}/foreignJNDILinkCreateForm

This resource manages the create forms for the foreignJNDILinks collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.ForeignJNDILinkMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the [foreignJNDILinks](#) collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ForeignJNDILinkMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/foreignJNDIProversiders/{name}/foreignJNDILinkCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/foreignJNDIProversiders/{name}/foreignJNDILinks](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/foreignJNDIProversiders/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/foreignJNDIProversiders/{name}/foreignJNDILinkCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/resourceGroups/{name}/foreignJNDIProviders/{name}/foreignJNDILinks

This resource manages a collection of [weblogic.management.configuration.ForeignJNDILinkMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.ForeignJNDILinkMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.ForeignJNDILinkMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/foreignJNDIProversiders/{name}/foreignJNDILinks](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/foreignJNDIProversiders/{name}/foreignJNDILinkCreateForm](#) **rel=create-form**

The create form resource for this collection resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/foreignJNDIProversiders/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/foreignJNDIProversiders/{name}/foreignJNDILinks](#) **rel=self**

This resource.

POST

Add a new [weblogic.management.configuration.ForeignJNDILinkMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.ForeignJNDILinkMBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/foreignJNDIProviders/{name}/foreignJNDILinks/{name}

This resource manages a [weblogic.management.configuration.ForeignJNDILinkMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.ForeignJNDILinkMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.ForeignJNDILinkMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ForeignJNDILinkMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/foreignJNDIProversiders/{name}/foreignJNDILinks/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/foreignJNDIProversiders/{name}/foreignJNDILinks](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/foreignJNDIProversiders/{name}/foreignJNDILinks/{name}](#) **rel**=self

This resource.

POST

Update this [weblogic.management.configuration.ForeignJNDILinkMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.ForeignJNDILinkMBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCStoreCreateForm

This resource manages the create forms for the JDBCStores collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.JDBCStoreMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the JDBCStores collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.JDBCStoreMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCStoreCreateForm](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCStores](#) **rel=create**
The collection resource for this create form resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCStoreCreateForm](#) **rel=self**
This resource.

/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCStores

This resource manages a collection of [weblogic.management.configuration.JDBCStoreMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.JDBCStoreMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.JDBCStoreMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCStores](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCStoreCreateForm](#) **rel**=create-form
The create form resource for this collection resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCStores](#)
rel=self
This resource.

POST

Add a new [weblogic.management.configuration.JDBCStoreMBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.JDBCStoreMBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCStores/{name}

This resource manages a [weblogic.management.configuration.JDBCStoreMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

DELETE

Delete this [weblogic.management.configuration.JDBCStoreMBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.management.configuration.JDBCStoreMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.JDBCStoreMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCStores/{name}](#) **rel**=canonical
This resource.
- **rel**=dataSource
This resource's dataSource reference to a [weblogic.management.configuration.JDBCSystemResourceMBean](#) resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCStores/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCStores/{name}](#) **rel**=self
This resource.

POST

Update this [weblogic.management.configuration.JDBCStoreMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.JDBCStoreMBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResourceCreateForm

This resource manages the create forms for the JDBCSystemResources collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.JDBCSystemResourceMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the [JDBCSystemResources](#) collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.JDBCSystemResourceMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResourceCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResourceCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources

This resource manages a collection of [weblogic.management.configuration.JDBCSystemResourceMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.JDBCSystemResourceMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.JDBCSystemResourceMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResourceCreateForm](#) **rel=create-form**
The create form resource for this collection resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources](#) **rel=self**
This resource.

POST

Add a new [weblogic.management.configuration.JDBCSystemResourceMBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.JDBCSystemResourceMBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources/{name}

This resource manages a [weblogic.management.configuration.JDBCSystemResourceMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.JDBCSystemResourceMBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.management.configuration.JDBCSystemResourceMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.JDBCSystemResourceMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource](#) **rel**=JDBCResource
This resource's JDBCResource singleton resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources/{name}](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources](#) **rel**=parent
The parent resource of this resource.
- **rel**=resource
This resource's resource reference to a [weblogic.descriptor.DescriptorBean](#) resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources/{name}](#) **rel**=self
This resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources/{name}/subDeploymentCreateForm](#) **rel**=subDeploymentCreateForm
The create form resource for this resource's subDeployments collection resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources/{name}/subDeployments](#) **rel**=subDeployments
This resource's subDeployments collection resource.

POST

Update this [weblogic.management.configuration.JDBCSystemResourceMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.JDBCSystemResourceMBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource

This resource manages a [weblogic.j2ee.descriptor.wl.JDBCDataSourceBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.JDBCDataSourceBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.JDBCDataSourceBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource/JDBCConnectionPoolParams
rel=JDBCConnectionPoolParams
This resource's JDBCConnectionPoolParams singleton resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource/JDBCDataSourceParams
rel=JDBCDataSourceParams
This resource's JDBCDataSourceParams singleton resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource/JBCDriverParams **rel**=JBCDriverParams
This resource's JBCDriverParams singleton resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource/JBCOracleParams **rel**=JBCOracleParams
This resource's JBCOracleParams singleton resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource/JBCXAParams **rel**=JBCXAParams
This resource's JBCXAParams singleton resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource/internalProperties **rel**=internalProperties
This resource's internalProperties singleton resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources/{name} **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource **rel**=self
This resource.

POST

Update this [weblogic.j2ee.descriptor.wl.JDBCDataSourceBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.JDBCDataSourceBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource/internalProperties

This resource manages a [weblogic.j2ee.descriptor.wl.JDBCPropertiesBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.j2ee.descriptor.wl.JDBCPropertiesBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.JDBCPropertiesBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource/internalProperties](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource/internalProperties/properties](#) **rel**=properties

This resource's properties collection resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource/internalProperties/propertyCreateForm](#) **rel**=propertyCreateForm

The create form resource for this resource's properties collection resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource/internalProperties](#) **rel**=self

This resource.

/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource/internalProperties/properties

This resource manages a collection of [weblogic.j2ee.descriptor.wl.JDBCPropertyBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.j2ee.descriptor.wl.JDBCPropertyBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.j2ee.descriptor.wl.JDBCPropertyBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource/internalProperties/properties](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource/internalProperties/propertyCreateForm](#) **rel**=create-form

The create form resource for this collection resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource/internalProperties](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource/internalProperties/properties](#) **rel**=self

This resource.

/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource/internalProper-

POST

Add a new [weblogic.j2ee.descriptor.wl.JDBCPropertyBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.JDBCPropertyBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource/internalProperties/properties/{name}

This resource manages a [weblogic.j2ee.descriptor.wl.JDBCPropertyBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.j2ee.descriptor.wl.JDBCPropertyBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.j2ee.descriptor.wl.JDBCPropertyBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.JDBCPropertyBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource/internalProperties/properties/{name}](#)
rel=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource/internalProperties/properties](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource/internalProperties/properties/{name}](#) **rel**=self

This resource.

POST

Update this [weblogic.j2ee.descriptor.wl.JDBCPropertyBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.JDBCPropertyBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource/internalProperties/propertyCreateForm

This resource manages the create forms for the properties collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.j2ee.descriptor.wl.JDBCPropertyBean](#) entity populated with default values that can be customized then posted (using the POST method) to the properties collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.JDBCPropertyBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource/internalProperties/propertyCreateForm](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource/internalProperties/properties](#) **rel=create**
The collection resource for this create form resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource/internalProperties](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource/internalProperties/propertyCreateForm](#) **rel=self**
This resource.

/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource/JDBCConnectionPoolParams

This resource manages a [weblogic.j2ee.descriptor.wl.JDBCConnectionPoolParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.JDBCConnectionPoolParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.JDBCConnectionPoolParamsBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource/JDBCConnectionPoolParams **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource/JDBCConnectionPoolParams **rel**=self
This resource.

POST

Update this [weblogic.j2ee.descriptor.wl.JDBCConnectionPoolParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.JDBCConnectionPoolParamsBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource/JDBCDataSourceParams

This resource manages a [weblogic.j2ee.descriptor.wl.JDBCDataSourceParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.JDBCDataSourceParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.JDBCDataSourceParamsBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource/JDBCDataSourceParams](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource/JDBCDataSourceParams](#) **rel**=self

This resource.

/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource/JDBCDataSour-

POST

Update this [weblogic.j2ee.descriptor.wl.JDBCDataSourceParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.JDBCDataSourceParamsBean](#) entity.

POST

Update this [weblogic.j2ee.descriptor.wl.JDBCDataSourceParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.JDBCDataSourceParamsBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource/JDBCResourceParams/properties

This resource manages a [weblogic.j2ee.descriptor.wl.JDBCPropertiesBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.j2ee.descriptor.wl.JDBCPropertiesBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.JDBCPropertiesBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource/JBCDriverParams/properties](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource/JBCDriverParams](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource/JBCDriverParams/properties/properties](#) **rel=properties**

This resource's properties collection resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource/JBCDriverParams/properties/propertyCreateForm](#) **rel=propertyCreateForm**

The create form resource for this resource's properties collection resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource/JBCDriverParams/properties](#) **rel=self**

This resource.

GET

Get this collection of [weblogic.j2ee.descriptor.wl.JDBCPropertyBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.j2ee.descriptor.wl.JDBCPropertyBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource/JBCDriverParams/properties/properties](#)
rel=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource/JBCDriverParams/properties/propertyCreateForm](#) **rel**=create-form

The create form resource for this collection resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource/JBCDriverParams/properties](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource/JBCDriverParams/properties/properties](#)
rel=self

This resource.

/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource/JDBCDriverParams/properties/properties/{name}

This resource manages a [weblogic.j2ee.descriptor.wl.JDBCPropertyBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.JDBCPropertyBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.JDBCPropertyBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource/JDBCDriverParams/properties/properties/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource/JDBCDriverParams/properties/properties](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource/JDBCDriverParams/properties/properties/{name}](#) **rel**=self

This resource.

/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource/JDBCDriverParams/properties/propertyCreateForm

This resource manages the create forms for the properties collection resource.

The resource supports the following methods:

- [GET](#)

/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource/JDBCOracleParams

This resource manages a [weblogic.j2ee.descriptor.wl.JDBCOracleParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.JDBCOracleParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.JDBCOracleParamsBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource/JDBCOracleParams **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource/JDBCOracleParams **rel**=self

This resource.

POST

Update this [weblogic.j2ee.descriptor.wl.JDBCOracleParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.JDBCOracleParamsBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource/JDBCXAParams

This resource manages a [weblogic.j2ee.descriptor.wl.JDBCXAParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.JDBCXAParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.JDBCXAParamsBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource/JDBCXAParams **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources/{name}/JDBCResource/JDBCXAParams **rel**=self

This resource.

POST

Update this [weblogic.j2ee.descriptor.wl.JDBCXAParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.JDBCXAParamsBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources/{name}/subDeploymentCreateForm

This resource manages the create forms for the subDeployments collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.SubDeploymentMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the subDeployments collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources/{name}/subDeploymentCreateForm **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources/{name}/subDeployments **rel**=create
The collection resource for this create form resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources/{name} **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources/{name}/subDeploymentCreateForm **rel**=self
This resource.

/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources/{name}/subDeployments

This resource manages a collection of [weblogic.management.configuration.SubDeploymentMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.SubDeploymentMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.SubDeploymentMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources/{name}/subDeployments](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources/{name}/subDeploymentCreateForm](#) **rel=create-form**

The create form resource for this collection resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources/{name}/subDeployments](#) **rel=self**

This resource.

POST

Add a new [weblogic.management.configuration.SubDeploymentMBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources/{name}/subDeployments/{name}

This resource manages a [weblogic.management.configuration.SubDeploymentMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

DELETE

Delete this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources/{name}/subDeployments/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources/{name}/subDeployments **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources/{name}/subDeployments/{name} **rel**=self

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources/{name}/subDeployments/{name}/subDeployments **rel**=subDeployments

This resource's subDeployments collection resource.

POST

Update this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources/{name}/subDeployments/{name}/subDeployments

This resource manages a collection of [weblogic.management.configuration.SubDeploymentMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.configuration.SubDeploymentMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.SubDeploymentMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources/{name}/subDeployments/{name}/subDeployments **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources/{name}/subDeployments/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources/{name}/subDeployments/{name}/subDeployments **rel**=self

This resource.

/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources/{name}/subDeployments/{name}/subDeployments/{name}

This resource manages a [weblogic.management.configuration.SubDeploymentMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources/{name}/subDeployments/{name}/subDeployments/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources/{name}/subDeployments/{name}/subDeployments **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources/{name}/subDeployments/{name}/subDeployments/{name} **rel**=self

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources/{name}/subDeployments/{name}/subDeployments/{name}/subDeployments **rel**=subDeployments

This resource's subDeployments collection resource.

/management/weblogic/{version}/edit/resourceGroups/{name}/JDBCSystemResources/{name}/subDeployments/{name}/subDep

POST

Update this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSBridgeDestinationCreateForm

This resource manages the create forms for the JMSBridgeDestinations collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.JMSBridgeDestinationMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the [JMSBridgeDestinations](#) collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.JMSBridgeDestinationMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSBridgeDestinationCreateForm](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSBridgeDestinations](#) **rel=create**
The collection resource for this create form resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSBridgeDestinationCreateForm](#) **rel=self**
This resource.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSBridgeDestinations

This resource manages a collection of [weblogic.management.configuration.JMSBridgeDestinationMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.JMSBridgeDestinationMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.JMSBridgeDestinationMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSBridgeDestinations](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSBridgeDestinationCreateForm](#) **rel=create-form**
The create form resource for this collection resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSBridgeDestinations](#) **rel=self**
This resource.

POST

Add a new [weblogic.management.configuration.JMSBridgeDestinationMBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.JMSBridgeDestinationMBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSBridgeDestinations/{name}

This resource manages a [weblogic.management.configuration.JMSBridgeDestinationMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.JMSBridgeDestinationMBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.management.configuration.JMSBridgeDestinationMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.JMSBridgeDestinationMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSBridgeDestinations/{name}](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSBridgeDestinations](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSBridgeDestinations/{name}](#) **rel=self**
This resource.

POST

Update this [weblogic.management.configuration.JMSBridgeDestinationMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.JMSBridgeDestinationMBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSServerCreateForm

This resource manages the create forms for the JMSServers collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.JMSServerMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the JMSServers collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.JMSServerMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSServerCreateForm](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSServers](#) **rel=create**
The collection resource for this create form resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSServerCreateForm](#) **rel=self**
This resource.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSServers

This resource manages a collection of [weblogic.management.configuration.JMSServerMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.JMSServerMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.JMSServerMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JMSServerMBeans](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JMSServerCreateForm](#) **rel**=create-form

The create form resource for this collection resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JMSServerMBeans](#) **rel**=self

This resource.

POST

Add a new [weblogic.management.configuration.JMSServerMBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.JMSServerMBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSServers/{name}

This resource manages a [weblogic.management.configuration.JMSServerMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.JMSServerMBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.management.configuration.JMSServerMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.JMSServerMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JMSServers/{name}/JMSMessageLogFile](#) **rel**=JMSMessageLogFile
This resource's JMSMessageLogFile singleton resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JMSServers/{name}](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JMSServers/{name}](#) **rel**=parent
The parent resource of this resource.
- **rel**=persistentStore
This resource's persistentStore reference to a [weblogic.management.configuration.PersistentStoreMBean](#) resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JMSServers/{name}](#) **rel**=self
This resource.

POST

Update this [weblogic.management.configuration.JMSServerMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.JMSServerMBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSServers/{name}/JMSMessageLogFile

This resource manages a [weblogic.management.configuration.JMSMessageLogFileMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.JMSMessageLogFileMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.JMSMessageLogFileMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSServers/{name}/JMSMessageLogFile **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSServers/{name} **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSServers/{name}/JMSMessageLogFile **rel**=self
This resource.

POST

POST

Update this [weblogic.management.configuration.JMSMessageLogFileMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.JMSMessageLogFileMBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResourceCreateForm

This resource manages the create forms for the JMSSystemResources collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.JMSSystemResourceMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the JMSSystemResources collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.JMSSystemResourceMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResourceCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResourceCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources

This resource manages a collection of [weblogic.management.configuration.JMSSystemResourceMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.JMSSystemResourceMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.JMSSystemResourceMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResourceCreateForm](#) **rel**=create-form
The create form resource for this collection resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources](#) **rel**=self
This resource.

POST

Add a new [weblogic.management.configuration.JMSSystemResourceMBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.JMSSystemResourceMBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}

This resource manages a [weblogic.management.configuration.JMSSystemResourceMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.JMSSystemResourceMBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.management.configuration.JMSSystemResourceMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.JMSSystemResourceMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource **rel**=JMSResource
This resource's JMSResource singleton resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name} **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources **rel**=parent
The parent resource of this resource.
- **rel**=resource
This resource's resource reference to a weblogic.descriptor.DescriptorBean resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name} **rel**=self
This resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/subDeploymentCreateForm **rel**=subDeploymentCreateForm
The create form resource for this resource's subDeployments collection resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/subDeployments **rel**=subDeployments
This resource's subDeployments collection resource.

POST

Update this [weblogic.management.configuration.JMSSystemResourceMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.JMSSystemResourceMBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource

This resource manages a [weblogic.j2ee.descriptor.wl.JMSBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.JMSBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.JMSBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFEErrorHandlingCreateForm](#)
[rel=SAFEErrorHandlingCreateForm](#)

The create form resource for this resource's SAFEErrorHandlings collection resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFEErrorHandlings](#) [rel=SAFEErrorHandlings](#)

This resource's SAFEErrorHandlings collection resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinationCreateForm](#)
[rel=SAFImportedDestinationCreateForm](#)

The create form resource for this resource's SAFImportedDestinations collection resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations](#)
[rel=SAFImportedDestinations](#)

This resource's SAFImportedDestinations collection resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFRemoteContextCreateForm](#)
[rel=SAFRemoteContextCreateForm](#)

The create form resource for this resource's SAFRemoteContexts collection resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFRemoteContexts](#) [rel=SAFRemoteContexts](#)

This resource's SAFRemoteContexts collection resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource](#) [rel=canonical](#)

This resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories](#) [rel=connectionFactories](#)

This resource's connectionFactories collection resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/connectionFactoryCreateForm](#)
[rel=connectionFactoryCreateForm](#)

The create form resource for this resource's connectionFactories collection resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/destinationKeyCreateForm
rel=destinationKeyCreateForm

The create form resource for this resource's destinationKeys collection resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/destinationKeys **rel**=destinationKeys

This resource's destinationKeys collection resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServerCreateForm
rel=foreignServerCreateForm

The create form resource for this resource's foreignServers collection resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers **rel**=foreignServers

This resource's foreignServers collection resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/queueCreateForm **rel**=queueCreateForm

The create form resource for this resource's queues collection resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/queues **rel**=queues

This resource's queues collection resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/quotaCreateForm **rel**=quotaCreateForm

The create form resource for this resource's quotas collection resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/quotas **rel**=quotas

This resource's quotas collection resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource **rel**=self

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templateCreateForm **rel**=templateCreateForm

The create form resource for this resource's templates collection resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates **rel**=templates

This resource's templates collection resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/topicCreateForm **rel**=topicCreateForm

The create form resource for this resource's topics collection resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/topics **rel**=topics

This resource's topics collection resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedQueueCreateForm **rel**=uniformDistributedQueueCreateForm

The create form resource for this resource's uniformDistributedQueues collection resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues **rel**=uniformDistributedQueues

This resource's uniformDistributedQueues collection resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopicCreateForm **rel**=uniformDistributedTopicCreateForm

The create form resource for this resource's uniformDistributedTopics collection resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics **rel**=uniformDistributedTopics

This resource's uniformDistributedTopics collection resource.

POST

Update this [weblogic.j2ee.descriptor.wl.JMSBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.JMSBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories

This resource manages a collection of [weblogic.j2ee.descriptor.wl.JMSConnectionFactoryBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.j2ee.descriptor.wl.JMSConnectionFactoryBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.j2ee.descriptor.wl.JMSConnectionFactoryBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/connectionFactoryCreateForm](#) **rel**=create-form

The create form resource for this collection resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories](#) **rel**=self

This resource.

POST

Add a new [weblogic.j2ee.descriptor.wl.JMSConnectionFactoryBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.JMSConnectionFactoryBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}

This resource manages a [weblogic.j2ee.descriptor.wl.JMSConnectionFactoryBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.j2ee.descriptor.wl.JMSConnectionFactoryBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.j2ee.descriptor.wl.JMSConnectionFactoryBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.JMSConnectionFactoryBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}/clientParams **rel**=clientParams

This resource's clientParams singleton resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}/defaultDeliveryParams **rel**=defaultDeliveryParams

This resource's defaultDeliveryParams singleton resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}/flowControlParams **rel**=flowControlParams

This resource's flowControlParams singleton resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}/loadBalancingParams **rel**=loadBalancingParams

This resource's loadBalancingParams singleton resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}/securityParams **rel**=securityParams

This resource's securityParams singleton resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories/{name} **rel**=self

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}/transactionParams **rel**=transactionParams

This resource's transactionParams singleton resource.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/connectionFacto-

POST

Update this [weblogic.j2ee.descriptor.wl.JMSConnectionFactoryBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.JMSConnectionFactoryBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}/clientParams

This resource manages a [weblogic.j2ee.descriptor.wl.ClientParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.ClientParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.ClientParamsBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}/clientParams
rel=canonical
This resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}
rel=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}/clientParams
rel=self
This resource.

POST

Update this [weblogic.j2ee.descriptor.wl.ClientParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.ClientParamsBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}/defaultDeliveryParams

This resource manages a [weblogic.j2ee.descriptor.wl.DefaultDeliveryParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.DefaultDeliveryParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.DefaultDeliveryParamsBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}/defaultDeliveryParams **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}/defaultDeliveryParams **rel**=self

This resource.

POST

Update this [weblogic.j2ee.descriptor.wl.DefaultDeliveryParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.DefaultDeliveryParamsBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}/flowControlParams

This resource manages a [weblogic.j2ee.descriptor.wl.FlowControlParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.FlowControlParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.FlowControlParamsBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}/flowControlParams
rel=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}/flowControlParams
rel=self

This resource.

POST

Update this [weblogic.j2ee.descriptor.wl.FlowControlParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.FlowControlParamsBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}/loadBalancingParams

This resource manages a [weblogic.j2ee.descriptor.wl.LoadBalancingParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.LoadBalancingParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.LoadBalancingParamsBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}/loadBalancingParams](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}/loadBalancingParams](#) **rel**=self

This resource.

POST

Update this [weblogic.j2ee.descriptor.wl.LoadBalancingParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.LoadBalancingParamsBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}/securityParams

This resource manages a [weblogic.j2ee.descriptor.wl.SecurityParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.SecurityParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.SecurityParamsBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}/securityParams
rel=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}/securityParams
rel=self

This resource.

POST

Update this [weblogic.j2ee.descriptor.wl.SecurityParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.SecurityParamsBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}/transactionParams

This resource manages a [weblogic.j2ee.descriptor.wl.TransactionParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.TransactionParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.TransactionParamsBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}/transactionParams
rel=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}/transactionParams
rel=self

This resource.

POST

Update this [weblogic.j2ee.descriptor.wl.TransactionParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.TransactionParamsBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/connectionFactoryCreateForm

This resource manages the create forms for the connectionFactories collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.j2ee.descriptor.wl.JMSConnectionFactoryBean](#) entity populated with default values that can be customized then posted (using the POST method) to the connectionFactories collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.JMSConnectionFactoryBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/connectionFactoryCreateForm **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories **rel**=create

The collection resource for this create form resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/connectionFactoryCreateForm **rel**=self

This resource.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/destinationKeyCreateForm

This resource manages the create forms for the destinationKeys collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.j2ee.descriptor.wl.DestinationKeyBean](#) entity populated with default values that can be customized then posted (using the POST method) to the destinationKeys collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.DestinationKeyBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/destinationKeyCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/destinationKeys](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/destinationKeyCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/destinationKeys

This resource manages a collection of [weblogic.j2ee.descriptor.wl.DestinationKeyBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.j2ee.descriptor.wl.DestinationKeyBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.j2ee.descriptor.wl.DestinationKeyBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/destinationKeys](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/destinationKeyCreateForm](#) **rel=create-form**

The create form resource for this collection resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/destinationKeys](#) **rel=self**

This resource.

POST

POST

Add a new [weblogic.j2ee.descriptor.wl.DestinationKeyBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.DestinationKeyBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/destinationKeys/{name}

This resource manages a [weblogic.j2ee.descriptor.wl.DestinationKeyBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.j2ee.descriptor.wl.DestinationKeyBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.j2ee.descriptor.wl.DestinationKeyBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.DestinationKeyBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/destinationKeys/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/destinationKeys **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/destinationKeys/{name} **rel**=self

This resource.

POST

Update this [weblogic.j2ee.descriptor.wl.DestinationKeyBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.DestinationKeyBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServerCreateForm

This resource manages the create forms for the foreignServers collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.j2ee.descriptor.wl.ForeignServerBean](#) entity populated with default values that can be customized then posted (using the POST method) to the `foreignServers` collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.ForeignServerBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServerCreateForm](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers](#) **rel**=create

The collection resource for this create form resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServerCreateForm](#) **rel**=self

This resource.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers

This resource manages a collection of [weblogic.j2ee.descriptor.wl.ForeignServerBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.j2ee.descriptor.wl.ForeignServerBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.j2ee.descriptor.wl.ForeignServerBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServerCreateForm](#) **rel**=create-form

The create form resource for this collection resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers](#) **rel**=self

This resource.

POST

Add a new [weblogic.j2ee.descriptor.wl.ForeignServerBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.ForeignServerBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}

This resource manages a [weblogic.j2ee.descriptor.wl.ForeignServerBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.j2ee.descriptor.wl.ForeignServerBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.j2ee.descriptor.wl.ForeignServerBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.ForeignServerBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/JNDIProperties
rel=JNDIProperties

This resource's JNDIProperties collection resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/JNDIPropertyCreateForm
rel=JNDIPropertyCreateForm

The create form resource for this resource's JNDIProperties collection resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignConnectionFactoryCollections
rel=foreignConnectionFactoryCollections

This resource's foreignConnectionFactoryCollections collection resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignConnectionFactoryCreateForm
rel=foreignConnectionFactoryCreateForm

The create form resource for this resource's foreignConnectionFactoryCollections collection resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignDestinationCreateForm
rel=foreignDestinationCreateForm

The create form resource for this resource's foreignDestinations collection resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignDestinations
rel=foreignDestinations

This resource's foreignDestinations collection resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name} **rel**=self

This resource.

POST

Update this [weblogic.j2ee.descriptor.wl.ForeignServerBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.ForeignServerBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignConnectionFactoryes

This resource manages a collection of [weblogic.j2ee.descriptor.wl.ForeignConnectionFactoryBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of `weblogic.j2ee.descriptor.wl.ForeignConnectionFactoryBean` instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of `weblogic.j2ee.descriptor.wl.ForeignConnectionFactoryBean` entities.

This method can return the following links:

- **uri**=`/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignConnectionFactoryies` **rel**=canonical

This resource.

- **uri**=`/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignConnectionFactoryCreateForm` **rel**=create-form

The create form resource for this collection resource.

- **uri**=`/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}` **rel**=parent

The parent resource of this resource.

- **uri**=`/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignConnectionFactoryies` **rel**=self

This resource.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{na

POST

Add a new [weblogic.j2ee.descriptor.wl.ForeignConnectionFactoryBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.ForeignConnectionFactoryBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignConnectionFactoryies/{name}

This resource manages a [weblogic.j2ee.descriptor.wl.ForeignConnectionFactoryBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.j2ee.descriptor.wl.ForeignConnectionFactoryBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.j2ee.descriptor.wl.ForeignConnectionFactoryBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.ForeignConnectionFactoryBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignConnections/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignConnections](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignConnections/{name}](#) **rel**=self

This resource.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{na

POST

Update this [weblogic.j2ee.descriptor.wl.ForeignConnectionFactoryBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.ForeignConnectionFactoryBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignConnectionFactoryCreateForm

This resource manages the create forms for the foreignConnectionFactories collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.j2ee.descriptor.wl.ForeignConnectionFactoryBean](#) entity populated with default values that can be customized then posted (using the POST method) to the `foreignConnectionFactories` collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.ForeignConnectionFactoryBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignConnectionFactoryCreateForm **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignConnectionFactoryCreateForm **rel**=create

The collection resource for this create form resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignConnectionFactoryCreateForm **rel**=self

This resource.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignDestinationCreate Form

This resource manages the create forms for the foreignDestinations collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.j2ee.descriptor.wl.ForeignDestinationBean](#) entity populated with default values that can be customized then posted (using the POST method) to the foreignDestinations collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.ForeignDestinationBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignDestinationCreateForm **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignDestinations **rel**=create

The collection resource for this create form resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignDestinationCreateForm **rel**=self

This resource.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignDestinations

This resource manages a collection of [weblogic.j2ee.descriptor.wl.ForeignDestinationBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.j2ee.descriptor.wl.ForeignDestinationBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.j2ee.descriptor.wl.ForeignDestinationBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignDestinations
rel=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignDestinationCreateForm
rel=create-form

The create form resource for this collection resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignDestinations
rel=self

This resource.

POST

Add a new [weblogic.j2ee.descriptor.wl.ForeignDestinationBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.ForeignDestinationBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignDestinations/{name}

This resource manages a [weblogic.j2ee.descriptor.wl.ForeignDestinationBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.j2ee.descriptor.wl.ForeignDestinationBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.j2ee.descriptor.wl.ForeignDestinationBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.ForeignDestinationBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignDestinations/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignDestinations **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignDestinations/{name} **rel**=self

This resource.

POST

Update this [weblogic.j2ee.descriptor.wl.ForeignDestinationBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.ForeignDestinationBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/JNDIProperties

This resource manages a collection of [weblogic.j2ee.descriptor.wl.PropertyBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.j2ee.descriptor.wl.PropertyBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.j2ee.descriptor.wl.PropertyBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/JNDIProperties](#)
rel=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/JNDIPropertyCreateForm](#)
rel=create-form

The create form resource for this collection resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/JNDIProperties](#) **rel**=self

This resource.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{na

POST

Add a new [weblogic.j2ee.descriptor.wl.PropertyBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.PropertyBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/JNDIProperties/{key}

This resource manages a [weblogic.j2ee.descriptor.wl.PropertyBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.j2ee.descriptor.wl.PropertyBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.j2ee.descriptor.wl.PropertyBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.PropertyBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/JNDIProperties/{key}](#)
rel=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/JNDIProperties](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/JNDIProperties/{key}](#)
rel=self

This resource.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{na

POST

Update this [weblogic.j2ee.descriptor.wl.PropertyBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.PropertyBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/JNDIPropertyCreateForm

This resource manages the create forms for the JNDIProperties collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.j2ee.descriptor.wl.PropertyBean](#) entity populated with default values that can be customized then posted (using the POST method) to the JNDIProperties collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.PropertyBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/JNDIPropertyCreateForm
rel=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/JNDIProperties **rel**=create

The collection resource for this create form resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/JNDIPropertyCreateForm
rel=self

This resource.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/queueCreateForm

This resource manages the create forms for the queues collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.j2ee.descriptor.wl.QueueBean](#) entity populated with default values that can be customized then posted (using the POST method) to the queues collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.QueueBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/queueCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/queues](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/queueCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/queues

This resource manages a collection of [weblogic.j2ee.descriptor.wl.QueueBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.j2ee.descriptor.wl.QueueBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.j2ee.descriptor.wl.QueueBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/queues **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/queuecreateForm **rel**=create-form

The create form resource for this collection resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/queues **rel**=self

This resource.

POST

Add a new [weblogic.j2ee.descriptor.wl.QueueBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.QueueBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/queues/{name}

This resource manages a [weblogic.j2ee.descriptor.wl.QueueBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

DELETE

Delete this [weblogic.j2ee.descriptor.wl.QueueBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.j2ee.descriptor.wl.QueueBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.QueueBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/queues/{name}](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/queues/{name}/deliveryFailureParams](#) **rel=deliveryFailureParams**
This resource's `deliveryFailureParams` singleton resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/queues/{name}/deliveryParamsOverrides](#) **rel=deliveryParamsOverrides**
This resource's `deliveryParamsOverrides` singleton resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/queues/{name}/messageLoggingParams](#) **rel=messageLoggingParams**
This resource's `messageLoggingParams` singleton resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/queues](#) **rel=parent**
The parent resource of this resource.
- **rel=quota**
This resource's quota reference to a `weblogic.j2ee.descriptor.wl.QuotaBean` resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/queues/{name}](#) **rel=self**
This resource.
- **rel=template**
This resource's template reference to a `weblogic.j2ee.descriptor.wl.TemplateBean` resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/queues/{name}/thresholds](#) **rel=thresholds**
This resource's `thresholds` singleton resource.

POST

Update this [weblogic.j2ee.descriptor.wl.QueueBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.QueueBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/queues/{name}/deliveryFailureParams

This resource manages a [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/queues/{name}/deliveryFailureParams/findSubDeploymentName](#) **rel**=action **title**=findSubDeploymentName
This resource's findSubDeploymentName action resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/queues/{name}/deliveryFailureParams](#) **rel**=canonical
This resource.
- **rel**=errorDestination
This resource's errorDestination reference to a [weblogic.j2ee.descriptor.wl.DestinationBean](#) resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/queues/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/queues/{name}/deliveryFailureParams](#) **rel**=self
This resource.
- **rel**=templateBean
This resource's templateBean reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/queues/{name}/deli

POST

Update this [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/queues/{name}/deliveryFailureParams/findSubDeploymentName

The resource supports the following methods:

- [POST](#)

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/queues/{name}/deli

POST

This is used to find the sub-deployment-name for this destination.

Roles

Admin, Deployer

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/queues/{name}/deliveryParamsOverrides

This resource manages a [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/queues/{name}/deliveryParamsOverrides
rel=canonical
This resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/queues/{name} **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/queues/{name}/deliveryParamsOverrides **rel**=self
This resource.
- **rel**=templateBean
This resource's templateBean reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/queues/{name}/messageLoggingParams

This resource manages a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/queues/{name}/messageLoggingParams](#)
rel=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/queues/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/queues/{name}/messageLoggingParams](#) **rel**=self

This resource.

- **rel**=templateBean

This resource's templateBean reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/queues/{name}/me

POST

Update this [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/queues/{name}/thresholds

This resource manages a [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/queues/{name}/thresholds **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/queues/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/queues/{name}/thresholds **rel**=self

This resource.

- **rel**=templateBean

This resource's templateBean reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/quotaCreateForm

This resource manages the create forms for the quotas collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.j2ee.descriptor.wl.QuotaBean](#) entity populated with default values that can be customized then posted (using the POST method) to the quotas collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.QuotaBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/quotaCreateForm **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/quotas **rel**=create

The collection resource for this create form resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/quotaCreateForm **rel**=self

This resource.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/quotas

This resource manages a collection of [weblogic.j2ee.descriptor.wl.QuotaBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.j2ee.descriptor.wl.QuotaBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.j2ee.descriptor.wl.QuotaBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/quotas](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/quotaCreateForm](#) **rel**=create-form

The create form resource for this collection resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/quotas](#) **rel**=self

This resource.

POST

Add a new [weblogic.j2ee.descriptor.wl.QuotaBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.QuotaBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/quotas/{name}

This resource manages a [weblogic.j2ee.descriptor.wl.QuotaBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.j2ee.descriptor.wl.QuotaBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.j2ee.descriptor.wl.QuotaBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.QuotaBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/quotas/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/quotas](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/quotas/{name}](#) **rel**=self

This resource.

POST

Update this [weblogic.j2ee.descriptor.wl.QuotaBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.QuotaBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFEErrorHandlingCreateForm

This resource manages the create forms for the SAFEErrorHandlings collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.j2ee.descriptor.wl.SAFEErrorHandlingBean](#) entity populated with default values that can be customized then posted (using the POST method) to the SAFEErrorHandlings collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.SAFEErrorHandlingBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFEErrorHandlingCreateForm](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFEErrorHandlings](#) **rel=create**
The collection resource for this create form resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFEErrorHandlingCreateForm](#) **rel=self**
This resource.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFEErrorHandlings

This resource manages a collection of [weblogic.j2ee.descriptor.wl.SAFEErrorHandlingBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.j2ee.descriptor.wl.SAFEErrorHandlingBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.j2ee.descriptor.wl.SAFEErrorHandlingBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFEErrorHandlings **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFEErrorHandlingCreateForm **rel**=create-form

The create form resource for this collection resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFEErrorHandlings **rel**=self

This resource.

POST

Add a new [weblogic.j2ee.descriptor.wl.SAFErrorHandlingBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.SAFErrorHandlingBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFEErrorHandlings/{name}

This resource manages a [weblogic.j2ee.descriptor.wl.SAFEErrorHandlingBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.j2ee.descriptor.wl.SAErrorHandlingBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.j2ee.descriptor.wl.SAFEErrorHandlingBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.SAFEErrorHandlingBean](#) entity.

This method can return the following links:

- **rel=SAFEErrorDestination**
This resource's SAFEErrorDestination reference to a [weblogic.j2ee.descriptor.wl.SAFDestinationBean](#) resource.
- **uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFEErrorHandlings/{name} rel=canonical**
This resource.
- **uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFEErrorHandlings rel=parent**
The parent resource of this resource.
- **uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFEErrorHandlings/{name} rel=self**
This resource.

POST

Update this [weblogic.j2ee.descriptor.wl.SAFErrorHandlingBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.SAFErrorHandlingBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinationCreateForm

This resource manages the create forms for the SAFImportedDestinations collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.j2ee.descriptor.wl.SAFImportedDestinationsBean](#) entity populated with default values that can be customized then posted (using the POST method) to the SAFImportedDestinations collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.SAFImportedDestinationsBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinationCreateForm
rel=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations **rel**=create

The collection resource for this create form resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinationCreateForm **rel**=self

This resource.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations

This resource manages a collection of [weblogic.j2ee.descriptor.wl.SAFImportedDestinationsBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.j2ee.descriptor.wl.SAFImportedDestinationsBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.j2ee.descriptor.wl.SAFImportedDestinationsBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinationCreateForm](#) **rel**=create-form

The create form resource for this collection resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations](#) **rel**=self

This resource.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDesti-

POST

Add a new [weblogic.j2ee.descriptor.wl.SAFImportedDestinationsBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.SAFImportedDestinationsBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}

This resource manages a [weblogic.j2ee.descriptor.wl.SAFImportedDestinationsBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.j2ee.descriptor.wl.SAFImportedDestinationsBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.j2ee.descriptor.wl.SAFImportedDestinationsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.SAFImportedDestinationsBean](#) entity.

This method can return the following links:

- **rel=SAFErrorHandling**
This resource's SAFErrorHandling reference to a [weblogic.j2ee.descriptor.wl.SAFErrorHandlingBean](#) resource.
- **uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFQueueCreateForm rel=SAFQueueCreateForm**
The create form resource for this resource's SAFQueues collection resource.
- **uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFQueues rel=SAFQueues**
This resource's SAFQueues collection resource.
- **rel=SAFRemoteContext**
This resource's SAFRemoteContext reference to a [weblogic.j2ee.descriptor.wl.SAFRemoteContextBean](#) resource.
- **uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFTopicCreateForm rel=SAFTopicCreateForm**
The create form resource for this resource's SAFTopics collection resource.
- **uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFTopics rel=SAFTopics**
This resource's SAFTopics collection resource.
- **uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name} rel=canonical**
This resource.
- **uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/messageLoggingParams rel=messageLoggingParams**
This resource's messageLoggingParams singleton resource.
- **uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations rel=parent**
The parent resource of this resource.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDesti-

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name} **rel**=self

This resource.

POST

Update this [weblogic.j2ee.descriptor.wl.SAFImportedDestinationsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.SAFImportedDestinationsBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/messageLoggingParams

This resource manages a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/messageLoggingParams](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/messageLoggingParams](#) **rel**=self

This resource.

- **rel**=templateBean

This resource's `templateBean` reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFIImportedDesti

POST

Update this [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFQueueCreateForm

This resource manages the create forms for the SAFQueues collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.j2ee.descriptor.wl.SAFQueueBean](#) entity populated with default values that can be customized then posted (using the POST method) to the SAFQueues collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.SAFQueueBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFQueueCreateForm **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFQueues **rel**=create

The collection resource for this create form resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFQueueCreateForm **rel**=self

This resource.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFQueues

This resource manages a collection of [weblogic.j2ee.descriptor.wl.SAFQueueBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.j2ee.descriptor.wl.SAFQueueBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.j2ee.descriptor.wl.SAFQueueBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFQueues
rel=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFQueueCreateForm **rel**=create-form

The create form resource for this collection resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFQueues
rel=self

This resource.

POST

Add a new [weblogic.j2ee.descriptor.wl.SAFQueueBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.SAFQueueBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFQueues/{name}

This resource manages a [weblogic.j2ee.descriptor.wl.SAFQueueBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.j2ee.descriptor.wl.SAFQueueBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.j2ee.descriptor.wl.SAFQueueBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.SAFQueueBean](#) entity.

This method can return the following links:

- **rel=SAFErrorHandling**
This resource's SAFErrorHandling reference to a [weblogic.j2ee.descriptor.wl.SAFErrorHandlingBean](#) resource.
- **uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFQueues/{name} rel=canonical**
This resource.
- **uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFQueues/{name}/messageLoggingParams rel=messageLoggingParams**
This resource's messageLoggingParams singleton resource.
- **uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFQueues rel=parent**
The parent resource of this resource.
- **uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFQueues/{name} rel=self**
This resource.

POST

Update this [weblogic.j2ee.descriptor.wl.SAFQueueBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.SAFQueueBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFQueues/{name}/messageLoggingParams

This resource manages a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFQueues/{name}/messageLoggingParams](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFQueues/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFQueues/{name}/messageLoggingParams](#) **rel**=self

This resource.

- **rel**=templateBean

This resource's `templateBean` reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFTopicCreateForm

This resource manages the create forms for the SAFTopics collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.j2ee.descriptor.wl.SAFTopicBean](#) entity populated with default values that can be customized then posted (using the POST method) to the SAFTopics collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.SAFTopicBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFTopicCreateForm **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFTopics **rel**=create

The collection resource for this create form resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFTopicCreateForm **rel**=self

This resource.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFTopics

This resource manages a collection of [weblogic.j2ee.descriptor.wl.SAFTopicBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.j2ee.descriptor.wl.SAFTopicBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.j2ee.descriptor.wl.SAFTopicBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFTopics
rel=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFTopicCreateForm
rel=create-form

The create form resource for this collection resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFTopics
rel=self

This resource.

POST

Add a new [weblogic.j2ee.descriptor.wl.SAFTopicBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.SAFTopicBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFTopics/{name}

This resource manages a [weblogic.j2ee.descriptor.wl.SAFTopicBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

DELETE

Delete this [weblogic.j2ee.descriptor.wl.SAFTopicBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.j2ee.descriptor.wl.SAFTopicBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.SAFTopicBean](#) entity.

This method can return the following links:

- **rel=SAFErrorHandling**
This resource's SAFErrorHandling reference to a [weblogic.j2ee.descriptor.wl.SAFErrorHandlingBean](#) resource.
- **uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFTopics/{name} rel=canonical**
This resource.
- **uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFTopics/{name}/messageLoggingParams rel=messageLoggingParams**
This resource's messageLoggingParams singleton resource.
- **uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFTopics rel=parent**
The parent resource of this resource.
- **uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFTopics/{name} rel=self**
This resource.

POST

Update this [weblogic.j2ee.descriptor.wl.SAFTopicBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.SAFTopicBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFTopics/{name}/messageLoggingParams

This resource manages a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFTopics/{name}/messageLoggingParams](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFTopics/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFTopics/{name}/messageLoggingParams](#) **rel**=self

This resource.

- **rel**=templateBean

This resource's templateBean reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFRemoteContextCreateForm

This resource manages the create forms for the SAFRemoteContexts collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.j2ee.descriptor.wl.SAFRemoteContextBean](#) entity populated with default values that can be customized then posted (using the POST method) to the SAFRemoteContexts collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.SAFRemoteContextBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFRemoteContextCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFRemoteContexts](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFRemoteContextCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFRemoteContexts

This resource manages a collection of [weblogic.j2ee.descriptor.wl.SAFRemoteContextBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.j2ee.descriptor.wl.SAFRemoteContextBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.j2ee.descriptor.wl.SAFRemoteContextBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFRemoteContexts](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFRemoteContextCreateForm](#) **rel=create-form**
The create form resource for this collection resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFRemoteContexts](#) **rel=self**
This resource.

POST

Add a new [weblogic.j2ee.descriptor.wl.SAFRemoteContextBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.SAFRemoteContextBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFRemoteContexts/{name}

This resource manages a [weblogic.j2ee.descriptor.wl.SAFRemoteContextBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.j2ee.descriptor.wl.SAFRemoteContextBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.j2ee.descriptor.wl.SAFRemoteContextBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.SAFRemoteContextBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFRemoteContexts/{name}/SAFLoginContext
rel=SAFLoginContext
This resource's SAFLoginContext singleton resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFRemoteContexts/{name} **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFRemoteContexts **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFRemoteContexts/{name} **rel**=self
This resource.

POST

Update this [weblogic.j2ee.descriptor.wl.SAFRemoteContextBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.SAFRemoteContextBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFRemoteContexts/{name}/SAFLoginContext

This resource manages a [weblogic.j2ee.descriptor.wl.SAFLoginContextBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.SAFLoginContextBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.SAFLoginContextBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFRemoteContexts/{name}/SAFLoginContext
rel=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFRemoteContexts/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/SAFRemoteContexts/{name}/SAFLoginContext
rel=self

This resource.

POST

Update this [weblogic.j2ee.descriptor.wl.SAFLoginContextBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.SAFLoginContextBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templateCreateForm

This resource manages the create forms for the templates collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.j2ee.descriptor.wl.TemplateBean](#) entity populated with default values that can be customized then posted (using the POST method) to the templates collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.TemplateBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templateCreateForm](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates](#) **rel=create**
The collection resource for this create form resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templateCreateForm](#) **rel=self**
This resource.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates

This resource manages a collection of [weblogic.j2ee.descriptor.wl.TemplateBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.j2ee.descriptor.wl.TemplateBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.j2ee.descriptor.wl.TemplateBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templateCreateForm **rel**=create-form

The create form resource for this collection resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates **rel**=self

This resource.

POST

Add a new [weblogic.j2ee.descriptor.wl.TemplateBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.TemplateBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}

This resource manages a [weblogic.j2ee.descriptor.wl.TemplateBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

DELETE

Delete this [weblogic.j2ee.descriptor.wl.TemplateBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.j2ee.descriptor.wl.TemplateBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.TemplateBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/findErrorDestination
rel=action **title**=findErrorDestination
This resource's findErrorDestination action resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name} **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/deliveryFailureParams
rel=deliveryFailureParams
This resource's deliveryFailureParams singleton resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/deliveryParamsOverrides
rel=deliveryParamsOverrides
This resource's deliveryParamsOverrides singleton resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/groupParamCreateForm
rel=groupParamCreateForm
The create form resource for this resource's groupParams collection resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/groupParams
rel=groupParams
This resource's groupParams collection resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/messageLoggingParams
rel=messageLoggingParams
This resource's messageLoggingParams singleton resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/multicast **rel**=multicast
This resource's multicast singleton resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates **rel**=parent
The parent resource of this resource.

- **rel=quota**
This resource's quota reference to a `weblogic.j2ee.descriptor.wl.QuotaBean` resource.
- **uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name} rel=self**
This resource.
- **uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/thresholds rel=thresholds**
This resource's thresholds singleton resource.
- **uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/topicSubscriptionParams rel=topicSubscriptionParams**
This resource's topicSubscriptionParams singleton resource.

POST

Update this [weblogic.j2ee.descriptor.wl.TemplateBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.TemplateBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/deliveryFailureParams

This resource manages a [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/deliveryFailureParams/findSubDeploymentName **rel**=action **title**=findSubDeploymentName
This resource's findSubDeploymentName action resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/deliveryFailureParams **rel**=canonical
This resource.
- **rel**=errorDestination
This resource's errorDestination reference to a [weblogic.j2ee.descriptor.wl.DestinationBean](#) resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name} **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/deliveryFailureParams **rel**=self
This resource.
- **rel**=templateBean
This resource's templateBean reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/deliveryFailureParams/findSubDeploymentName

The resource supports the following methods:

- [POST](#)

POST

This is used to find the sub-deployment-name for this destination.

Roles

Admin, Deployer

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/deliveryParamsOverrides

This resource manages a [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/deliveryParamsOverrides](#)
rel=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/deliveryParamsOverrides](#)
rel=self

This resource.

- **rel**=templateBean

This resource's `templateBean` reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/d

POST

Update this [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/findErrorDestination

The resource supports the following methods:

- [POST](#)

POST

Finds the name of the error destination to use when a destination comes from a specific group

Roles

Admin, Deployer

Request Body

Must contain a JSON object with the following fields:

subDeploymentName

The subDeployment for which to find the quota

Type: string

Response Body

Contains a JSON object with a weblogic.j2ee.descriptor.wl.DestinationBean reference return field.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/groupParamCreateForm

This resource manages the create forms for the groupParams collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.j2ee.descriptor.wl.GroupParamsBean](#) entity populated with default values that can be customized then posted (using the POST method) to the groupParams collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.GroupParamsBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/groupParamCreateForm
rel=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/groupParams **rel**=create

The collection resource for this create form resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/groupParamCreateForm
rel=self

This resource.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/groupParams

This resource manages a collection of [weblogic.j2ee.descriptor.wl.GroupParamsBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.j2ee.descriptor.wl.GroupParamsBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.j2ee.descriptor.wl.GroupParamsBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/groupParams **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/groupParamCreateForm **rel**=create-form

The create form resource for this collection resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/groupParams **rel**=self

This resource.

POST

Add a new [weblogic.j2ee.descriptor.wl.GroupParamsBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.GroupParamsBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/groupParams/{subDeploymentName}

This resource manages a [weblogic.j2ee.descriptor.wl.GroupParamsBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

DELETE

Delete this [weblogic.j2ee.descriptor.wl.GroupParamsBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.j2ee.descriptor.wl.GroupParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.GroupParamsBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/groupParams/{subDeploymentName} **rel**=canonical
This resource.
- **rel**=errorDestination
This resource's errorDestination reference to a [weblogic.j2ee.descriptor.wl.DestinationBean](#) resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/groupParams **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/groupParams/{subDeploymentName} **rel**=self
This resource.

POST

Update this [weblogic.j2ee.descriptor.wl.GroupParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.GroupParamsBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/messageLoggingParams

This resource manages a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/messageLoggingParams](#)
rel=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/messageLoggingParams](#)
rel=self

This resource.

- **rel**=templateBean

This resource's templateBean reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/

POST

Update this [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/multicast

This resource manages a [weblogic.j2ee.descriptor.wl.MulticastParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.MulticastParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.MulticastParamsBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/multicast **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/multicast **rel**=self

This resource.

- **rel**=templateBean

This resource's templateBean reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.MulticastParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.MulticastParamsBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/thresholds

This resource manages a [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/thresholds](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/thresholds](#) **rel**=self

This resource.

- **rel**=templateBean

This resource's templateBean reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/topicSubscriptionParams

This resource manages a [weblogic.j2ee.descriptor.wl.TopicSubscriptionParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.TopicSubscriptionParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.TopicSubscriptionParamsBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/topicSubscriptionParams
rel=canonical
This resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name} **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/topicSubscriptionParams
rel=self
This resource.
- **rel**=templateBean
This resource's templateBean reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.TopicSubscriptionParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.TopicSubscriptionParamsBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/topicCreateForm

This resource manages the create forms for the topics collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.j2ee.descriptor.wl.TopicBean](#) entity populated with default values that can be customized then posted (using the POST method) to the topics collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.TopicBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/topicCreateForm **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/topics **rel**=create

The collection resource for this create form resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/topicCreateForm **rel**=self

This resource.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/topics

This resource manages a collection of [weblogic.j2ee.descriptor.wl.TopicBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.j2ee.descriptor.wl.TopicBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.j2ee.descriptor.wl.TopicBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/topics **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/topicCreateForm **rel**=create-form

The create form resource for this collection resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/topics **rel**=self

This resource.

POST

Add a new [weblogic.j2ee.descriptor.wl.TopicBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.TopicBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/topics/{name}

This resource manages a [weblogic.j2ee.descriptor.wl.TopicBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.j2ee.descriptor.wl.TopicBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.j2ee.descriptor.wl.TopicBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.TopicBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/topics/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/topics/{name}/deliveryFailureParams **rel**=deliveryFailureParams

This resource's deliveryFailureParams singleton resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/topics/{name}/deliveryParamsOverrides **rel**=deliveryParamsOverrides

This resource's deliveryParamsOverrides singleton resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/topics/{name}/messageLoggingParams **rel**=messageLoggingParams

This resource's messageLoggingParams singleton resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/topics/{name}/multicast **rel**=multicast

This resource's multicast singleton resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/topics **rel**=parent

The parent resource of this resource.

- **rel**=quota

This resource's quota reference to a [weblogic.j2ee.descriptor.wl.QuotaBean](#) resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/topics/{name} **rel**=self

This resource.

- **rel**=template

This resource's template reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/topics/{name}/thresholds **rel**=thresholds

This resource's thresholds singleton resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/topics/{name}/topicSubscriptionParams
rel=topicSubscriptionParams

This resource's topicSubscriptionParams singleton resource.

POST

Update this [weblogic.j2ee.descriptor.wl.TopicBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.TopicBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/topics/{name}/deliveryFailureParams

This resource manages a [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/topics/{name}/deliveryFailureParams/findSubDeploymentName](#) **rel**=action **title**=findSubDeploymentName
This resource's findSubDeploymentName action resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/topics/{name}/deliveryFailureParams](#) **rel**=canonical
This resource.
- **rel**=errorDestination
This resource's errorDestination reference to a [weblogic.j2ee.descriptor.wl.DestinationBean](#) resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/topics/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/topics/{name}/deliveryFailureParams](#) **rel**=self
This resource.
- **rel**=templateBean
This resource's templateBean reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/topics/{name}/deliv

POST

Update this [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/topics/{name}/deliveryFailureParams/findSubDeploymentName

The resource supports the following methods:

- [POST](#)

POST

This is used to find the sub-deployment-name for this destination.

Roles

Admin, Deployer

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/topics/{name}/deliveryParamsOverrides

This resource manages a [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/topics/{name}/deliveryParamsOverrides
rel=canonical
This resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/topics/{name} **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/topics/{name}/deliveryParamsOverrides **rel**=self
This resource.
- **rel**=templateBean
This resource's templateBean reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/topics/{name}/messageLoggingParams

This resource manages a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/topics/{name}/messageLoggingParams](#)
rel=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/topics/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/topics/{name}/messageLoggingParams](#) **rel**=self

This resource.

- **rel**=templateBean

This resource's templateBean reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/topics/{name}/mes

POST

Update this [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/topics/{name}/multicast

This resource manages a [weblogic.j2ee.descriptor.wl.MulticastParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.MulticastParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.MulticastParamsBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/topics/{name}/multicast **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/topics/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/topics/{name}/multicast **rel**=self

This resource.

- **rel**=templateBean

This resource's templateBean reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.MulticastParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.MulticastParamsBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/topics/{name}/thresholds

This resource manages a [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/topics/{name}/thresholds](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/topics/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/topics/{name}/thresholds](#) **rel**=self

This resource.

- **rel**=templateBean

This resource's templateBean reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/topics/{name}/topicSubscriptionParams

This resource manages a [weblogic.j2ee.descriptor.wl.TopicSubscriptionParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.TopicSubscriptionParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.TopicSubscriptionParamsBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/topics/{name}/topicSubscriptionParams
rel=canonical
This resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/topics/{name}
rel=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/topics/{name}/topicSubscriptionParams
rel=self
This resource.
- **rel**=templateBean
This resource's templateBean reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.TopicSubscriptionParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.TopicSubscriptionParamsBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedQueueCreateForm

This resource manages the create forms for the uniformDistributedQueues collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.j2ee.descriptor.wl.UniformDistributedQueueBean](#) entity populated with default values that can be customized then posted (using the POST method) to the `uniformDistributedQueues` collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.UniformDistributedQueueBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedQueueCreateForm](#)
rel=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues](#) **rel**=create

The collection resource for this create form resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedQueueCreateForm](#) **rel**=self

This resource.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues

This resource manages a collection of [weblogic.j2ee.descriptor.wl.UniformDistributedQueueBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.j2ee.descriptor.wl.UniformDistributedQueueBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.j2ee.descriptor.wl.UniformDistributedQueueBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedQueueCreateForm](#) **rel**=create-form

The create form resource for this collection resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues](#) **rel**=self

This resource.

POST

Add a new [weblogic.j2ee.descriptor.wl.UniformDistributedQueueBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.UniformDistributedQueueBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues/{name}

This resource manages a [weblogic.j2ee.descriptor.wl.UniformDistributedQueueBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.j2ee.descriptor.wl.UniformDistributedQueueBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.j2ee.descriptor.wl.UniformDistributedQueueBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.UniformDistributedQueueBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues/{name}](#) **rel=canonical**
 This resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues/{name}/deliveryFailureParams](#) **rel=deliveryFailureParams**
 This resource's [deliveryFailureParams](#) singleton resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues/{name}/deliveryParamsOverrides](#) **rel=deliveryParamsOverrides**
 This resource's [deliveryParamsOverrides](#) singleton resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues/{name}/messageLoggingParams](#) **rel=messageLoggingParams**
 This resource's [messageLoggingParams](#) singleton resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues](#) **rel=parent**
 The parent resource of this resource.
- **rel=quota**
 This resource's [quota](#) reference to a [weblogic.j2ee.descriptor.wl.QuotaBean](#) resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues/{name}](#) **rel=self**
 This resource.
- **rel=template**
 This resource's [template](#) reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues/{name}/thresholds](#) **rel=thresholds**
 This resource's [thresholds](#) singleton resource.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributed-

POST

Update this [weblogic.j2ee.descriptor.wl.UniformDistributedQueueBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.UniformDistributedQueueBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues/{name}/deliveryFailureParams

This resource manages a [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues/{name}/deliveryFailureParams/findSubDeploymentName **rel**=action **title**=findSubDeploymentName
This resource's findSubDeploymentName action resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues/{name}/deliveryFailureParams **rel**=canonical
This resource.
- **rel**=errorDestination
This resource's errorDestination reference to a [weblogic.j2ee.descriptor.wl.DestinationBean](#) resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues/{name} **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues/{name}/deliveryFailureParams **rel**=self
This resource.
- **rel**=templateBean
This resource's templateBean reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues/{name}/deliveryFailureParams/findSubDeploymentName

The resource supports the following methods:

- [POST](#)

POST

This is used to find the sub-deployment-name for this destination.

Roles

Admin, Deployer

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues/{name}/deliveryParamsOverrides

This resource manages a [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues/{name}/deliveryParamsOverrides](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues/{name}/deliveryParamsOverrides](#) **rel**=self

This resource.

- **rel**=templateBean

This resource's `templateBean` reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues/{name}/messageLoggingParams

This resource manages a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues/{name}/messageLoggingParams **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues/{name}/messageLoggingParams **rel**=self

This resource.

- **rel**=templateBean

This resource's templateBean reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues/{name}/thresholds

This resource manages a [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues/{name}/thresholds](#)
rel=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues/{name}/thresholds](#)
rel=self

This resource.

- **rel**=templateBean

This resource's templateBean reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopicCreateForm

This resource manages the create forms for the uniformDistributedTopics collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.j2ee.descriptor.wl.UniformDistributedTopicBean](#) entity populated with default values that can be customized then posted (using the POST method) to the uniformDistributedTopics collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.UniformDistributedTopicBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopicCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopicCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics

This resource manages a collection of [weblogic.j2ee.descriptor.wl.UniformDistributedTopicBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.j2ee.descriptor.wl.UniformDistributedTopicBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.j2ee.descriptor.wl.UniformDistributedTopicBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopicCreateForm **rel**=create-form

The create form resource for this collection resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics **rel**=self

This resource.

POST

Add a new [weblogic.j2ee.descriptor.wl.UniformDistributedTopicBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.UniformDistributedTopicBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}

This resource manages a [weblogic.j2ee.descriptor.wl.UniformDistributedTopicBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

DELETE

Delete this [weblogic.j2ee.descriptor.wl.UniformDistributedTopicBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.j2ee.descriptor.wl.UniformDistributedTopicBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.UniformDistributedTopicBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}/deliveryFailureParams](#) **rel=deliveryFailureParams**
This resource's `deliveryFailureParams` singleton resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}/deliveryParamsOverrides](#) **rel=deliveryParamsOverrides**
This resource's `deliveryParamsOverrides` singleton resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}/messageLoggingParams](#) **rel=messageLoggingParams**
This resource's `messageLoggingParams` singleton resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}/multicast](#) **rel=multicast**
This resource's `multicast` singleton resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics](#) **rel=parent**
The parent resource of this resource.
- **rel=quota**
This resource's `quota` reference to a `weblogic.j2ee.descriptor.wl.QuotaBean` resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}](#) **rel=self**
This resource.
- **rel=template**
This resource's `template` reference to a `weblogic.j2ee.descriptor.wl.TemplateBean` resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}/thresholds
rel=thresholds

This resource's thresholds singleton resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}/topicSubscriptionParams **rel**=topicSubscriptionParams

This resource's topicSubscriptionParams singleton resource.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributed-

POST

Update this [weblogic.j2ee.descriptor.wl.UniformDistributedTopicBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.UniformDistributedTopicBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}/deliveryFailureParams

This resource manages a [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}/deliveryFailureParams/findSubDeploymentName **rel**=action **title**=findSubDeploymentName
This resource's findSubDeploymentName action resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}/deliveryFailureParams **rel**=canonical
This resource.
- **rel**=errorDestination
This resource's errorDestination reference to a [weblogic.j2ee.descriptor.wl.DestinationBean](#) resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name} **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}/deliveryFailureParams **rel**=self
This resource.
- **rel**=templateBean
This resource's templateBean reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}/deliveryFailureParams/findSubDeploymentName

The resource supports the following methods:

- [POST](#)

POST

This is used to find the sub-deployment-name for this destination.

Roles

Admin, Deployer

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}/deliveryParamsOverrides

This resource manages a [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}/deliveryParamsOverrides](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}/deliveryParamsOverrides](#) **rel**=self

This resource.

- **rel**=templateBean

This resource's `templateBean` reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}/messageLoggingParams

This resource manages a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}/messageLoggingParams **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name} **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}/messageLoggingParams **rel**=self
This resource.
- **rel**=templateBean
This resource's templateBean reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}/multicast

This resource manages a [weblogic.j2ee.descriptor.wl.MulticastParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.MulticastParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.MulticastParamsBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}/multicast](#)
rel=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}/multicast](#)
rel=self

This resource.

- **rel**=templateBean

This resource's `templateBean` reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.MulticastParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.MulticastParamsBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}/thresholds

This resource manages a [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}/thresholds
rel=canonical
This resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name} **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}/thresholds
rel=self
This resource.
- **rel**=templateBean
This resource's templateBean reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}/topicSubscriptionParams

This resource manages a [weblogic.j2ee.descriptor.wl.TopicSubscriptionParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.TopicSubscriptionParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.TopicSubscriptionParamsBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}/topicSubscriptionParams](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}/topicSubscriptionParams](#) **rel**=self

This resource.

- **rel**=templateBean

This resource's templateBean reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.TopicSubscriptionParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.TopicSubscriptionParamsBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/subDeploymentCreateForm

This resource manages the create forms for the subDeployments collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.SubDeploymentMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the subDeployments collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/subDeploymentCreateForm rel=canonical](#)
This resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/subDeployments rel=create](#)
The collection resource for this create form resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name} rel=parent](#)
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/subDeploymentCreateForm rel=self](#)
This resource.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/subDeployments

This resource manages a collection of [weblogic.management.configuration.SubDeploymentMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.SubDeploymentMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.SubDeploymentMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/subDeployments](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/subDeploymentCreateForm](#) **rel=create-form**

The create form resource for this collection resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/subDeployments](#) **rel=self**

This resource.

POST

Add a new [weblogic.management.configuration.SubDeploymentMBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/subDeployments/{name}

This resource manages a [weblogic.management.configuration.SubDeploymentMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

DELETE

Delete this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/subDeployments/{name} **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/subDeployments **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/subDeployments/{name} **rel**=self
This resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/subDeployments/{name}/subDeployments **rel**=subDeployments
This resource's subDeployments collection resource.

POST

Update this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/subDeployments/{name}/subDeployments

This resource manages a collection of [weblogic.management.configuration.SubDeploymentMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.configuration.SubDeploymentMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.SubDeploymentMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/subDeployments/{name}/subDeployments **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/subDeployments/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/subDeployments/{name}/subDeployments **rel**=self

This resource.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/subDeployments/{name}/subDeployments/{name}

This resource manages a [weblogic.management.configuration.SubDeploymentMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/subDeployments/{name}/subDeployments/{name}](#)
rel=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/subDeployments/{name}/subDeployments](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/subDeployments/{name}/subDeployments/{name}](#) **rel**=self

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/subDeployments/{name}/subDeployments/{name}/subDeployments](#) **rel**=subDeployments

This resource's subDeployments collection resource.

/management/weblogic/{version}/edit/resourceGroups/{name}/JMSSystemResources/{name}/subDeployments/{name}/subDe-

POST

Update this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/libraries

This resource manages a collection of [weblogic.management.configuration.LibraryMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.LibraryMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.LibraryMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/libraries](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/libraries](#)
rel=self
This resource.

POST

The resource supports the following methods:

- [POST accepting application/json](#)
- [POST accepting multipart/form-data](#)

POST accepting application/json

This resource is used to deploy libraries that are already on the administration server.

This method supports both asynchronous and best effort synchronous invocations. The behavior is controlled by the 'Prefer' header. See [About Synchronous and Asynchronous Operations](#).

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.LibraryMBean](#) entity.

To deploy a library, you must provide the name of the library, the path to the library, and the targets to which the library will be deployed.

Use the multi-part form to deploy a library.

- `sourcePath`: the deployment to upload (required)
- `model`: JSONObject containing a LibraryMBean entity that contains the rest of the deployment information (required)

POST accepting multipart/form-data

Upload a library from the client to the server then deploy it.

This method supports both asynchronous and best effort synchronous invocations. The behavior is controlled by the 'Prefer' header. See [About Synchronous and Asynchronous Operations](#).

Roles

Admin, Deployer

Request Body

Use the multi-part form to upload a library from the client to the server then deploy it.

- `sourcePath`: the deployment to upload (required)
- `model`: JSONObject containing a LibraryMBean entity that contains the rest of the deployment information (required)

/management/weblogic/{version}/edit/resourceGroups/{name}/libraries/{name}

This resource manages a [weblogic.management.configuration.LibraryMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Undeploy a library.

This method supports both asynchronous and best effort synchronous invocations. The behavior is controlled by the 'Prefer' header. See [About Synchronous and Asynchronous Operations](#).

Roles

Admin, Deployer

GET

Get this [weblogic.management.configuration.LibraryMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.LibraryMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/libraries/{name}/createPlan](#) **rel=action** **title=createPlan**
This resource's createPlan action resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/libraries/{name}](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/libraries](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/libraries/{name}/redeploy](#) **rel=redeploy**
This resource's redeploy resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/libraries/{name}](#) **rel=self**
This resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/libraries/{name}/subDeploymentCreateForm](#) **rel=subDeploymentCreateForm**
The create form resource for this resource's subDeployments collection resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/libraries/{name}/subDeployments](#) **rel=subDeployments**
This resource's subDeployments collection resource.

POST

Update this [weblogic.management.configuration.LibraryMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.LibraryMBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/libraries/{name}/createPlan

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

POST

Create a deployment plan in the specified directory.

Roles

Admin, Deployer

Request Body

Must contain a JSON object with the following fields:

planPath

planPath

Type: string

Response Body

Contains a JSON object with a string return field.

POST

Create a deployment plan in a default directory

Roles

Admin, Deployer

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/edit/resourceGroups/{name}/libraries/{name}/redeploy

The resource supports the following methods:

- [POST](#)

POST

Use the multi-part form to redeploy a library.

- `sourcePath`: the deployment to upload (required)
- `model`: JSONObject containing a LibraryMBean entity that contains the rest of the deployment information (required)

This method supports both asynchronous and best effort synchronous invocations. The behavior is controlled by the 'Prefer' header. See [About Synchronous and Asynchronous Operations](#).

Roles

Admin, Deployer

/management/weblogic/{version}/edit/resourceGroups/{name}/libraries/{name}/subDeploymentCreateForm

This resource manages the create forms for the subDeployments collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.SubDeploymentMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the subDeployments collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/libraries/{name}/subDeploymentCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/libraries/{name}/subDeployments](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/libraries/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/libraries/{name}/subDeploymentCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/resourceGroups/{name}/libraries/{name}/subDeployments

This resource manages a collection of [weblogic.management.configuration.SubDeploymentMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.SubDeploymentMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.SubDeploymentMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/libraries/{name}/subDeployments](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/libraries/{name}/subDeploymentCreateForm](#) **rel=create-form**

The create form resource for this collection resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/libraries/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/libraries/{name}/subDeployments](#) **rel=self**

This resource.

POST

Add a new [weblogic.management.configuration.SubDeploymentMBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/libraries/{name}/subDeployments/{name}

This resource manages a [weblogic.management.configuration.SubDeploymentMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/libraries/{name}/subDeployments/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/libraries/{name}/subDeployments **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/libraries/{name}/subDeployments/{name} **rel**=self

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/libraries/{name}/subDeployments/{name}/subDeployments **rel**=subDeployments

This resource's subDeployments collection resource.

POST

Update this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/libraries/{name}/subDeployments/{name}/subDeployments

This resource manages a collection of [weblogic.management.configuration.SubDeploymentMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.configuration.SubDeploymentMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.SubDeploymentMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/libraries/{name}/subDeployments/{name}/subDeployments](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/libraries/{name}/subDeployments/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/libraries/{name}/subDeployments/{name}/subDeployments](#) **rel**=self

This resource.

/management/weblogic/{version}/edit/resourceGroups/{name}/libraries/{name}/subDeployments/{name}/subDeployments/{name}

This resource manages a [weblogic.management.configuration.SubDeploymentMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/libraries/{name}/subDeployments/{name}/subDeployments/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/libraries/{name}/subDeployments/{name}/subDeployments **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/libraries/{name}/subDeployments/{name}/subDeployments/{name} **rel**=self

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/libraries/{name}/subDeployments/{name}/subDeployments/{name}/subDeployments **rel**=subDeployments

This resource's subDeployments collection resource.

POST

Update this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/lookupTarget

The resource supports the following methods:

- [POST](#)

POST

Find a particular target with a given name.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

name

the name of the target to find

Type: string

Response Body

Contains a JSON object with a `weblogic.management.configuration.TargetMBean` reference return field.

/management/weblogic/{version}/edit/resourceGroups/{name}/mailSessionCreateForm

This resource manages the create forms for the mailSessions collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.MailSessionMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the mailSessions collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.MailSessionMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/mailSessionC
reateForm rel=canonical](#)
This resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/mailSessions
rel=create](#)
The collection resource for this create form resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name} rel=parent](#)
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/mailSessionC
reateForm rel=self](#)
This resource.

/management/weblogic/{version}/edit/resourceGroups/{name}/mailSessions

This resource manages a collection of [weblogic.management.configuration.MailSessionMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.MailSessionMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.MailSessionMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/mailSessions](#)
rel=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/mailSessionC](#)
[reateForm](#) **rel**=create-form

The create form resource for this collection resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/mailSessions](#)
rel=self

This resource.

POST

Add a new [weblogic.management.configuration.MailSessionMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.MailSessionMBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/mailSessions/{name}

This resource manages a [weblogic.management.configuration.MailSessionMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.MailSessionMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.MailSessionMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.MailSessionMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/mailSessions/{name}](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/mailSessions](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/mailSessions/{name}](#) **rel**=self
This resource.

POST

Update this [weblogic.management.configuration.MailSessionMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.MailSessionMBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/managedExecutorServiceCreateForm

This resource manages the create forms for the managedExecutorServices collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.ManagedExecutorServiceMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the `managedExecutorServices` collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ManagedExecutorServiceMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/managedExecutorServiceCreateForm](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/managedExecutorServices](#) **rel=create**
The collection resource for this create form resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/managedExecutorServiceCreateForm](#) **rel=self**
This resource.

/management/weblogic/{version}/edit/resourceGroups/{name}/managedExecutorServices

This resource manages a collection of [weblogic.management.configuration.ManagedExecutorServiceMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.ManagedExecutorServiceMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.ManagedExecutorServiceMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/managedExecutorServices](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/managedExecutorServiceCreateForm](#) **rel=create-form**
The create form resource for this collection resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/managedExecutorServices](#) **rel=self**
This resource.

POST

Add a new [weblogic.management.configuration.ManagedExecutorServiceMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.ManagedExecutorServiceMBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/managedExecutorServices/{name}

This resource manages a [weblogic.management.configuration.ManagedExecutorServiceMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.ManagedExecutorServiceMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.ManagedExecutorServiceMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ManagedExecutorServiceMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/managedExecutorServices/{name}](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/managedExecutorServices](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/managedExecutorServices/{name}](#) **rel=self**
This resource.

POST

Update this [weblogic.management.configuration.ManagedExecutorServiceMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.ManagedExecutorServiceMBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/managedScheduledExecutorServiceCreateForm

This resource manages the create forms for the managedScheduledExecutorServices collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.ManagedScheduledExecutorServiceMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the `managedScheduledExecutorServices` collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ManagedScheduledExecutorServiceMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/managedScheduledExecutorServiceCreateForm](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/managedScheduledExecutorServices](#) **rel**=create
The collection resource for this create form resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/managedScheduledExecutorServiceCreateForm](#) **rel**=self
This resource.

/management/weblogic/{version}/edit/resourceGroups/{name}/managedScheduledExecutorServices

This resource manages a collection of [weblogic.management.configuration.ManagedScheduledExecutorServiceMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.ManagedScheduledExecutorServiceMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.ManagedScheduledExecutorServiceMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/managedScheduledExecutorServices](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/managedScheduledExecutorServiceCreateForm](#) **rel=create-form**
The create form resource for this collection resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/managedScheduledExecutorServices](#) **rel=self**
This resource.

POST

Add a new [weblogic.management.configuration.ManagedScheduledExecutorServiceMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.ManagedScheduledExecutorServiceMBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/managedScheduledExecutorServices/{name}

This resource manages a [weblogic.management.configuration.ManagedScheduledExecutorServiceMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this

[weblogic.management.configuration.ManagedScheduledExecutorServiceMBean](#)
instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.ManagedScheduledExecutorServiceMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ManagedScheduledExecutorServiceMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/managedScheduledExecutorServices/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/managedScheduledExecutorServices](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/managedScheduledExecutorServices/{name}](#) **rel**=self

This resource.

POST

Update this [weblogic.management.configuration.ManagedScheduledExecutorServiceMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.ManagedScheduledExecutorServiceMBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/managedThreadFactories

This resource manages a collection of [weblogic.management.configuration.ManagedThreadFactoryMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.ManagedThreadFactoryMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.ManagedThreadFactoryMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/managedThreadFactories](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/managedThreadFactoryCreateForm](#) **rel=create-form**
The create form resource for this collection resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/managedThreadFactories](#) **rel=self**
This resource.

POST

Add a new [weblogic.management.configuration.ManagedThreadFactoryMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.ManagedThreadFactoryMBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/managedThreadFactories/{name}

This resource manages a [weblogic.management.configuration.ManagedThreadFactoryMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.ManagedThreadFactoryMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.ManagedThreadFactoryMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ManagedThreadFactoryMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/managedThreadFactories/{name} **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/managedThreadFactories **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/managedThreadFactories/{name} **rel**=self
This resource.

POST

Update this [weblogic.management.configuration.ManagedThreadFactoryMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.ManagedThreadFactoryMBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/managedThreadFactoryCreateForm

This resource manages the create forms for the managedThreadFactories collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.ManagedThreadFactoryMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the `managedThreadFactories` collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ManagedThreadFactoryMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/managedThreadFactoryCreateForm](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/managedThreadFactories](#) **rel**=create
The collection resource for this create form resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/managedThreadFactoryCreateForm](#) **rel**=self
This resource.

/management/weblogic/{version}/edit/resourceGroups/{name}/messagingBridgeCreateForm

This resource manages the create forms for the messagingBridges collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.MessagingBridgeMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the `messagingBridges` collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.MessagingBridgeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/messagingBridgeCreateForm](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/messagingBridges](#) **rel=create**
The collection resource for this create form resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/messagingBridgeCreateForm](#) **rel=self**
This resource.

/management/weblogic/{version}/edit/resourceGroups/{name}/messagingBridges

This resource manages a collection of [weblogic.management.configuration.MessagingBridgeMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.MessagingBridgeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.MessagingBridgeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/messagingBridges](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/messagingBridgeCreateForm](#) **rel=create-form**
The create form resource for this collection resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/messagingBridges](#) **rel=self**
This resource.

POST

Add a new [weblogic.management.configuration.MessagingBridgeMBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.MessagingBridgeMBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/messagingBridges/{name}

This resource manages a [weblogic.management.configuration.MessagingBridgeMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.MessagingBridgeMBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.management.configuration.MessagingBridgeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.MessagingBridgeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/messagingBridges/{name}](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/messagingBridges](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/messagingBridges/{name}](#) **rel**=self
This resource.
- **rel**=sourceDestination
This resource's sourceDestination reference to a [weblogic.management.configuration.BridgeDestinationCommonMBean](#) resource.
- **rel**=targetDestination
This resource's targetDestination reference to a [weblogic.management.configuration.BridgeDestinationCommonMBean](#) resource.

POST

Update this [weblogic.management.configuration.MessagingBridgeMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.MessagingBridgeMBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/osgiFrameworkCreateForm

This resource manages the create forms for the osgiFrameworks collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.OsgiFrameworkMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the `osgiFrameworks` collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.OsgiFrameworkMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/osgiFrameworkCreateForm](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/osgiFrameworks](#) **rel=create**
The collection resource for this create form resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/osgiFrameworkCreateForm](#) **rel=self**
This resource.

/management/weblogic/{version}/edit/resourceGroups/{name}/osgiFramework s

This resource manages a collection of [weblogic.management.configuration.OsgiFrameworkMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.OsgiFrameworkMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.OsgiFrameworkMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/osgiFrameworks](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/osgiFrameworkCreateForm](#) **rel=create-form**
The create form resource for this collection resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/osgiFrameworks](#) **rel=self**
This resource.

POST

Add a new [weblogic.management.configuration.OsgiFrameworkMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.OsgiFrameworkMBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/osgiFrameworks/{name}

This resource manages a [weblogic.management.configuration.OsgiFrameworkMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

DELETE

Delete this [weblogic.management.configuration.OsgiFrameworkMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.OsgiFrameworkMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.OsgiFrameworkMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/osgiFrameworks/{name}](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/osgiFrameworks](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/osgiFrameworks/{name}](#) **rel=self**
This resource.

POST

POST

Update this [weblogic.management.configuration.OsgiFrameworkMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.OsgiFrameworkMBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/SAFAgentCreateForm

This resource manages the create forms for the SAFAgents collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.SAFAgentMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the SAFAgents collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SAFAgentMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/SAFAgentCreateForm](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/SAFAgentCreateForm](#) **rel=create**
The collection resource for this create form resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/SAFAgentCreateForm](#) **rel=self**
This resource.

/management/weblogic/{version}/edit/resourceGroups/{name}/SAFAgents

This resource manages a collection of [weblogic.management.configuration.SAFAgentMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.SAFAgentMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.SAFAgentMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/SAFAgentMBean](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/SAFAgentCreateForm](#) **rel**=create-form

The create form resource for this collection resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/SAFAgentMBean](#) **rel**=self

This resource.

POST

Add a new [weblogic.management.configuration.SAFAgentMBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.SAFAgentMBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/SAFAgents/{name}

This resource manages a [weblogic.management.configuration.SAFAMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.SAFAgentMBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.management.configuration.SAFAgentMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SAFAgentMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/SAFAgents/{name}/JMSSAFMessageLogFile](#) **rel**=JMSSAFMessageLogFile
This resource's JMSSAFMessageLogFile singleton resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/SAFAgents/{name}](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/SAFAgents/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/SAFAgents/{name}](#) **rel**=self
This resource.
- **rel**=store
This resource's store reference to a [weblogic.management.configuration.PersistentStoreMBean](#) resource.

POST

Update this [weblogic.management.configuration.SAFAgentMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.SAFAgentMBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/SAFAgents/{name}/JMSSAFMessageLogFile

This resource manages a [weblogic.management.configuration.JMSSAFMessageLogFileMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.JMSSAFMessageLogFileMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.JMSSAFMessageLogFileMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/SAFAgents/{name}/JMSSAFMessageLogFile **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/SAFAgents/{name} **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/SAFAgents/{name}/JMSSAFMessageLogFile **rel**=self
This resource.

POST

Update this [weblogic.management.configuration.JMSSAFMessageLogFileMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.JMSSAFMessageLogFileMBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResourceCreateForm

This resource manages the create forms for the WLDFSystemResources collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.WLDFSystemResourceMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the [WLDFSystemResources](#) collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.WLDFSystemResourceMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResourceCreateForm](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources](#) **rel**=create
The collection resource for this create form resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResourceCreateForm](#) **rel**=self
This resource.

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources

This resource manages a collection of [weblogic.management.configuration.WLDFSystemResourceMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.WLDFSystemResourceMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.WLDFSystemResourceMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResourceCreateForm](#) **rel=create-form**
The create form resource for this collection resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources](#) **rel=self**
This resource.

POST

Add a new [weblogic.management.configuration.WLDFSystemResourceMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.WLDFSystemResourceMBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}

This resource manages a [weblogic.management.configuration.WLDFSystemResourceMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.WLDFSystemResourceMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.WLDFSystemResourceMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.WLDFSystemResourceMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource](#) **rel**=WLDFResource
This resource's WLDFResource singleton resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}](#) **rel**=canonical
This resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources](#) **rel**=parent
The parent resource of this resource.
- **rel**=resource
This resource's resource reference to a [weblogic.descriptor.DescriptorBean](#) resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}](#) **rel**=self
This resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/subDeploymentCreateForm](#) **rel**=subDeploymentCreateForm
The create form resource for this resource's subDeployments collection resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/subDeployments](#) **rel**=subDeployments
This resource's subDeployments collection resource.

POST

Update this [weblogic.management.configuration.WLDFSystemResourceMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.WLDFSystemResourceMBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/subDeploymentCreateForm

This resource manages the create forms for the subDeployments collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.SubDeploymentMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the subDeployments collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/subDeploymentCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/subDeployments](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/subDeploymentCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/subDeployments

This resource manages a collection of [weblogic.management.configuration.SubDeploymentMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.SubDeploymentMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.SubDeploymentMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/subDeployments](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/subDeploymentCreateForm](#) **rel=create-form**
The create form resource for this collection resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/subDeployments](#) **rel=self**
This resource.

POST

Add a new [weblogic.management.configuration.SubDeploymentMBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/subDeployments/{name}

This resource manages a [weblogic.management.configuration.SubDeploymentMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

DELETE

Delete this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/subDeployments/{name}](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/subDeployments](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/subDeployments/{name}](#) **rel=self**

This resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/subDeployments/{name}/subDeployments](#) **rel=subDeployments**

This resource's subDeployments collection resource.

POST

Update this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/subDeployments/{name}/subDeployments

This resource manages a collection of [weblogic.management.configuration.SubDeploymentMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.configuration.SubDeploymentMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.SubDeploymentMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/subDeployments/{name}/subDeployments](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/subDeployments/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/subDeployments/{name}/subDeployments](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/subDeployments/{name}/subDeployments/{name}

This resource manages a [weblogic.management.configuration.SubDeploymentMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/subDeployments/{name}/subDeployments/{name}](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/subDeployments/{name}/subDeployments](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/subDeployments/{name}/subDeployments/{name}](#) **rel**=self
This resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/subDeployments/{name}/subDeployments/{name}/subDeployments](#) **rel**=subDeployments
This resource's subDeployments collection resource.

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/subDeployments/{name}/subDe

POST

Update this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource

This resource manages a [weblogic.diagnostics.descriptor.WLDFResourceBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.diagnostics.descriptor.WLDFResourceBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFResourceBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/harvester](#) **rel=harvester**
This resource's harvester singleton resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/instrumentation](#) **rel=instrumentation**
This resource's instrumentation singleton resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource](#) **rel=self**
This resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification](#) **rel=watchNotification**
This resource's watchNotification singleton resource.

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/harvester

This resource manages a [weblogic.diagnostics.descriptor.WLDFHarvesterBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.diagnostics.descriptor.WLDFHarvesterBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFHarvesterBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/harvester](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/harvester/harvestedTypecreateForm](#) **rel=harvestedTypecreateForm**

The create form resource for this resource's harvestedTypes collection resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/harvester/harvestedTypes](#) **rel=harvestedTypes**

This resource's harvestedTypes collection resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/harvester](#) **rel=self**

This resource.

POST

Update this [weblogic.diagnostics.descriptor.WLDFHarvesterBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFHarvesterBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/harvester/harvestedTypeCreateForm

This resource manages the create forms for the harvestedTypes collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFHarvestedTypeBean](#) entity populated with default values that can be customized then posted (using the POST method) to the `harvestedTypes` collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFHarvestedTypeBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/harvester/harvestedTypeCreateForm](#)
rel=canonical

This resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/harvester/harvestedTypes](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/harvester](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/harvester/harvestedTypeCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/harvester/harvestedTypes

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFHarvestedTypeBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFHarvestedTypeBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFHarvestedTypeBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/harvester/harvestedTypes](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/harvester/harvestedTypeCreateForm](#) **rel=create-form**

The create form resource for this collection resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/harvester](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/harvester/harvestedTypes](#) **rel=self**

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFHarvestedTypeBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFHarvestedTypeBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/harvester/harvestedTypes/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFHarvestedTypeBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFHarvestedTypeBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.diagnostics.descriptor.WLDFHarvestedTypeBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFHarvestedTypeBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/harvester/harvestedTypes/{name}](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/harvester/harvestedTypes](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/harvester/harvestedTypes/{name}](#) **rel**=self
This resource.

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/harvester/harve

POST

Update this [weblogic.diagnostics.descriptor.WLDFHarvestedTypeBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFHarvestedTypeBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/instrumentation

This resource manages a [weblogic.diagnostics.descriptor.WLDFInstrumentationBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.diagnostics.descriptor.WLDFInstrumentationBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFInstrumentationBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/instrumentation/WLDFInstrumentationMonitorCreateForm](#) **rel**=WLDFInstrumentationMonitorCreateForm

The create form resource for this resource's WLDFInstrumentationMonitors collection resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/instrumentation/WLDFInstrumentationMonitors](#) **rel**=WLDFInstrumentationMonitors

This resource's WLDFInstrumentationMonitors collection resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/instrumentation](#) **rel**=canonical

This resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource](#) **rel**=parent

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/instrumentation](#) **rel**=self

This resource.

POST

Update this [weblogic.diagnostics.descriptor.WLDFInstrumentationBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFInstrumentationBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/instrumentation/WLDFInstrumentationMonitorCreateForm

This resource manages the create forms for the WLDFInstrumentationMonitors collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFInstrumentationMonitorBean](#) entity populated with default values that can be customized then posted (using the POST method) to the [WLDFInstrumentationMonitors](#) collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFInstrumentationMonitorBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/instrumentation/WLDFInstrumentationMonitorCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/instrumentation/WLDFInstrumentationMonitors](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/instrumentation](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/instrumentation/WLDFInstrumentationMonitorCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/instrumentation/WLDFInstrumentationMonitors

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFInstrumentationMonitorBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFInstrumentationMonitorBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFInstrumentationMonitorBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/instrumentation/WLDFInstrumentationMonitors](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/instrumentation/WLDFInstrumentationMonitorCreateForm](#) **rel=create-form**

The create form resource for this collection resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/instrumentation](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/instrumentation/WLDFInstrumentationMonitors](#) **rel=self**

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFInstrumentationMonitorBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFInstrumentationMonitorBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/instrumentation/WLDFInstrumentationMonitors/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFInstrumentationMonitorBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFInstrumentationMonitorBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.diagnostics.descriptor.WLDFInstrumentationMonitorBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFInstrumentationMonitorBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/instrumentation/WLDFInstrumentationMonitors/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/instrumentation/WLDFInstrumentationMonitors](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/instrumentation/WLDFInstrumentationMonitors/{name}](#) **rel**=self

This resource.

POST

Update this [weblogic.diagnostics.descriptor.WLDFInstrumentationMonitorBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFInstrumentationMonitorBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification

This resource manages a [weblogic.diagnostics.descriptor.WLDFWatchNotificationBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.diagnostics.descriptor.WLDFWatchNotificationBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFWatchNotificationBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMSNotificationCreateForm](#) **rel=JMSNotificationCreateForm**

The create form resource for this resource's JMSNotifications collection resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMSNotifications](#) **rel=JMSNotifications**

This resource's JMSNotifications collection resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMXNotificationCreateForm](#) **rel=JMXNotificationCreateForm**

The create form resource for this resource's JMXNotifications collection resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMXNotifications](#) **rel=JMXNotifications**

This resource's JMXNotifications collection resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/RESTNotificationCreateForm](#) **rel=RESTNotificationCreateForm**

The create form resource for this resource's RESTNotifications collection resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/RESTNotifications](#) **rel=RESTNotifications**

This resource's RESTNotifications collection resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/SMTPNotificationCreateForm](#) **rel=SMTPNotificationCreateForm**

The create form resource for this resource's SMTPNotifications collection resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/SMTPNotifications](#) **rel=SMTPNotifications**

This resource's SMTPNotifications collection resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/SNMPNotificationCreateForm **rel**=SNMPNotificationCreateForm
The create form resource for this resource's SNMPNotifications collection resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/SNMPNotifications **rel**=SNMPNotifications
This resource's SNMPNotifications collection resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/lookupActions **rel**=action **title**=lookupActions
This resource's lookupActions action resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/lookupNotification **rel**=action **title**=lookupNotification
This resource's lookupNotification action resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actionCreateForm **rel**=actionCreateForm
The create form resource for this resource's actions collection resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions **rel**=actions
This resource's actions collection resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/heapDumpActionCreateForm **rel**=heapDumpActionCreateForm
The create form resource for this resource's heapDumpActions collection resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/heapDumpActions **rel**=heapDumpActions
This resource's heapDumpActions collection resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/imageNotificationCreateForm **rel**=imageNotificationCreateForm
The create form resource for this resource's imageNotifications collection resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/imageNotifications **rel**=imageNotifications
This resource's imageNotifications collection resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/logActionCreateForm
rel=logActionCreateForm
The create form resource for this resource's logActions collection resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/logActions **rel**=logActions
This resource's logActions collection resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleDownActionCreateForm **rel**=scaleDownActionCreateForm
The create form resource for this resource's scaleDownActions collection resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleDownActions **rel**=scaleDownActions
This resource's scaleDownActions collection resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleUpActionCreateForm **rel**=scaleUpActionCreateForm
The create form resource for this resource's scaleUpActions collection resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleUpActions **rel**=scaleUpActions
This resource's scaleUpActions collection resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scriptActionCreateForm **rel**=scriptActionCreateForm
The create form resource for this resource's scriptActions collection resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scriptActions **rel**=scriptActions
This resource's scriptActions collection resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification **rel**=self
This resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/threadDumpActionCreateForm **rel**=threadDumpActionCreateForm
The create form resource for this resource's threadDumpActions collection resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/threadDumpActions
rel=threadDumpActions

This resource's threadDumpActions collection resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/watchCreateForm
rel=watchCreateForm

The create form resource for this resource's watches collection resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/watches **rel**=watches

This resource's watches collection resource.

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotifica-

POST

Update this [weblogic.diagnostics.descriptor.WLDFWatchNotificationBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFWatchNotificationBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actionCreateForm

This resource manages the create forms for the actions collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFActionBean](#) entity populated with default values that can be customized then posted (using the POST method) to the actions collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFActionBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actionCreateForm](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions](#) **rel=create**
The collection resource for this create form resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actionCreateForm](#) **rel=self**
This resource.

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFActionBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFActionBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFActionBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actionCreateForm](#) **rel=create-form**
The create form resource for this collection resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions](#) **rel=self**
This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFActionBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFActionBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFActionBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFActionBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.diagnostics.descriptor.WLDFActionBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFActionBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/arrayProperties rel=arrayProperties](#)
This resource's arrayProperties collection resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/arrayPropertyCreateForm rel=arrayPropertyCreateForm](#)
The create form resource for this resource's arrayProperties collection resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name} rel=canonical](#)
This resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/configurationProperties rel=configurationProperties](#)
This resource's configurationProperties collection resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/encryptedProperties rel=encryptedProperties](#)
This resource's encryptedProperties collection resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/encryptedPropertyCreateForm rel=encryptedPropertyCreateForm](#)
The create form resource for this resource's encryptedProperties collection resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties rel=mapProperties](#)
This resource's mapProperties collection resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapPropertyCreateForm rel=mapPropertyCreateForm](#)
The create form resource for this resource's mapProperties collection resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDSystemResources/{name}/WLDResource/watchNotification/actions **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDSystemResources/{name}/WLDResource/watchNotification/actions/{name}/properties **rel**=properties
This resource's properties collection resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDSystemResources/{name}/WLDResource/watchNotification/actions/{name}/propertyCreateForm **rel**=propertyCreateForm
The create form resource for this resource's properties collection resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDSystemResources/{name}/WLDResource/watchNotification/actions/{name} **rel**=self
This resource.

POST

Update this [weblogic.diagnostics.descriptor.WLDFActionBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFActionBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/arrayProperties

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFArrayPropertyBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFArrayPropertyBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFArrayPropertyBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/arrayProperties](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/arrayPropertyCreateForm](#) **rel=create-form**

The create form resource for this collection resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/arrayProperties](#) **rel=self**

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFArrayPropertyBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFArrayPropertyBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/arrayProperties/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFArrayPropertyBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFArrayPropertyBean](#) instance.

Roles

Admin

GET

Get this [weblogic.diagnostics.descriptor.WLDFArrayPropertyBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFArrayPropertyBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/arrayProperties/{name}](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/arrayProperties](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/arrayProperties/{name}](#) **rel=self**

This resource.

POST

Update this [weblogic.diagnostics.descriptor.WLDFArrayPropertyBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFArrayPropertyBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/arrayPropertyCreateForm

This resource manages the create forms for the arrayProperties collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFArrayPropertyBean](#) entity populated with default values that can be customized then posted (using the POST method) to the arrayProperties collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFArrayPropertyBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/arrayPropertyCreateForm](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/arrayProperties](#) **rel**=create

The collection resource for this create form resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/arrayPropertyCreateForm](#) **rel**=self

This resource.

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/configurationProperties

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFConfigurationPropertyBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFConfigurationPropertyBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFConfigurationPropertyBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/configurationProperties](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}](#)
rel=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/configurationProperties](#) **rel**=self

This resource.

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/configurationProperties/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFConfigurationPropertyBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.diagnostics.descriptor.WLDFConfigurationPropertyBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFConfigurationPropertyBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/configurationProperties/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/configurationProperties](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/configurationProperties/{name}](#) **rel**=self

This resource.

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/encrypted Properties

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/encryptedProperties](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/encryptedPropertyCreateForm](#) **rel=create-form**

The create form resource for this collection resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/encryptedProperties](#) **rel=self**

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/encryptedProperties/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) instance.

Roles

Admin

GET

Get this [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/encryptedProperties/{name} rel=canonical](#)

This resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/encryptedProperties rel=parent](#)

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/encryptedProperties/{name} rel=self](#)

This resource.

POST

Update this [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/encryptedPropertyCreateForm

This resource manages the create forms for the encryptedProperties collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) entity populated with default values that can be customized then posted (using the POST method) to the encryptedProperties collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/encryptedPropertyCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/encryptedProperties](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/encryptedPropertyCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFConfigurationPropertiesBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFConfigurationPropertiesBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFConfigurationPropertiesBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapPropertyCreateForm](#) **rel=create-form**

The create form resource for this collection resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties](#) **rel=self**

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFConfigurationPropertiesBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFConfigurationPropertiesBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFConfigurationPropertiesBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFConfigurationPropertiesBean](#) instance.

Roles

Admin

GET

Get this [weblogic.diagnostics.descriptor.WLDFConfigurationPropertiesBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFConfigurationPropertiesBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/configurationProperties](#) **rel=configurationProperties**

This resource's configurationProperties collection resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/encryptedProperties](#) **rel=encryptedProperties**

This resource's encryptedProperties collection resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/encryptedPropertyCreateForm](#) **rel=encryptedPropertyCreateForm**

The create form resource for this resource's encryptedProperties collection resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/properties](#) **rel=properties**

This resource's properties collection resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/propertyCreateForm](#) **rel=propertyCreateForm**

The create form resource for this resource's properties collection resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/configurationProperties

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFConfigurationPropertyBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFConfigurationPropertyBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFConfigurationPropertyBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/configurationProperties **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/configurationProperties **rel**=self

This resource.

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/configurationProperties/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFConfigurationPropertyBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.diagnostics.descriptor.WLDFConfigurationPropertyBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFConfigurationPropertyBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/configurationProperties/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/configurationProperties **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/configurationProperties/{name} **rel**=self

This resource.

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/encryptedProperties

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/encryptedProperties](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/encryptedPropertyCreateForm](#) **rel=create-form**

The create form resource for this collection resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/encryptedProperties](#) **rel=self**

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/encryptedProperties/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/encryptedProperties/{name}](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/encryptedProperties](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/encryptedProperties/{name}](#) **rel=self**

This resource.

POST

POST

Update this [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/encryptedPropertyCreateForm

This resource manages the create forms for the encryptedProperties collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) entity populated with default values that can be customized then posted (using the POST method) to the encryptedProperties collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/encryptedPropertyCreateForm **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/encryptedProperties **rel**=create

The collection resource for this create form resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/encryptedPropertyCreateForm **rel**=self

This resource.

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/properties

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/properties](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/propertyCreateForm](#) **rel**=create-form

The create form resource for this collection resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}](#) **rel**=self

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/properties/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/properties/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/properties](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/properties/{name}](#) **rel**=self

This resource.

POST

Update this [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/propertyCreateForm

This resource manages the create forms for the properties collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) entity populated with default values that can be customized then posted (using the POST method) to the properties collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/propertyCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/properties](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/propertyCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapPropertyCreateForm

This resource manages the create forms for the mapProperties collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFConfigurationPropertiesBean](#) entity populated with default values that can be customized then posted (using the POST method) to the mapProperties collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFConfigurationPropertiesBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapPropertyCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapPropertyCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/properties

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/properties](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/propertyCreateForm](#) **rel=create-form**

The create form resource for this collection resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/properties](#) **rel=self**

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/properties/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) instance.

Roles

Admin

GET

Get this [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/properties/{name} rel=canonical](#)

This resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/properties rel=parent](#)

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/properties/{name} rel=self](#)

This resource.

POST

Update this [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/propertyCreateForm

This resource manages the create forms for the properties collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) entity populated with default values that can be customized then posted (using the POST method) to the properties collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/propertyCreateForm](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/properties](#) **rel**=create

The collection resource for this create form resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/propertyCreateForm](#) **rel**=self

This resource.

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/heapDumpActionCreateForm

This resource manages the create forms for the heapDumpActions collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFHeapDumpActionBean](#) entity populated with default values that can be customized then posted (using the POST method) to the heapDumpActions collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFHeapDumpActionBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/heapDumpActionCreateForm **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/heapDumpActions **rel**=create

The collection resource for this create form resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/heapDumpActionCreateForm **rel**=self

This resource.

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/heapDumpActions

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFHeapDumpActionBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFHeapDumpActionBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFHeapDumpActionBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/heapDumpActions](#)
rel=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/heapDumpActionCreateForm](#) **rel**=create-form

The create form resource for this collection resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/heapDumpActions](#)
rel=self

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFHeapDumpActionBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFHeapDumpActionBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/heapDumpActions/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFHeapDumpActionBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFHeapDumpActionBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.diagnostics.descriptor.WLDFHeapDumpActionBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFHeapDumpActionBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/heapDumpActions/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/heapDumpActions](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/heapDumpActions/{name}](#) **rel**=self

This resource.

POST

Update this [weblogic.diagnostics.descriptor.WLDFHeapDumpActionBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFHeapDumpActionBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/imageNotificationCreateForm

This resource manages the create forms for the imageNotifications collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFImageNotificationBean](#) entity populated with default values that can be customized then posted (using the POST method) to the imageNotifications collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFImageNotificationBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/imageNotificationCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/imageNotifications](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/imageNotificationCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/imageNotifications

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFImageNotificationBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFImageNotificationBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFImageNotificationBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/imageNotifications](#)
rel=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/imageNotificationCreateForm](#)
rel=create-form

The create form resource for this collection resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/imageNotifications](#)
rel=self

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFImageNotificationBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFImageNotificationBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/imageNotifications/{name} **}**

This resource manages a [weblogic.diagnostics.descriptor.WLDFImageNotificationBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFImageNotificationBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.diagnostics.descriptor.WLDFImageNotificationBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFImageNotificationBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/imageNotifications/{name}](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/imageNotifications](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/imageNotifications/{name}](#) **rel=self**

This resource.

POST

Update this [weblogic.diagnostics.descriptor.WLDFImageNotificationBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFImageNotificationBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMSNotificationCreateForm

This resource manages the create forms for the JMSNotifications collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFJMSNotificationBean](#) entity populated with default values that can be customized then posted (using the POST method) to the JMSNotifications collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFJMSNotificationBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMSNotificationCreateForm rel=canonical](#)

This resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMSNotifications rel=create](#)

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification rel=parent](#)

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMSNotificationCreateForm rel=self](#)

This resource.

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMSNotifications

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFJMSNotificationBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFJMSNotificationBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFJMSNotificationBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMSNotifications](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMSNotificationCreateForm](#) **rel=create-form**

The create form resource for this collection resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMSNotifications](#) **rel=self**

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFJMSNotificationBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFJMSNotificationBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMSNotifications/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFJMSNotificationBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFJMSNotificationBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.diagnostics.descriptor.WLDFJMSNotificationBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFJMSNotificationBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMSNotifications/{name}](#)
rel=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMSNotifications](#)
rel=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMSNotifications/{name}](#)
rel=self

This resource.

POST

Update this [weblogic.diagnostics.descriptor.WLDFJMSNotificationBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFJMSNotificationBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMXNotificationCreateForm

This resource manages the create forms for the JMXNotifications collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFJMXNotificationBean](#) entity populated with default values that can be customized then posted (using the POST method) to the JMXNotifications collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFJMXNotificationBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMXNotificationCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMXNotifications](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMXNotificationCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMXNotifications

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFJMXNotificationBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFJMXNotificationBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFJMXNotificationBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMXNotifications](#)
rel=canonical

This resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMXNotificationCreateForm](#)
rel=create-form

The create form resource for this collection resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification](#)
rel=parent

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMXNotifications](#)
rel=self

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFJMXNotificationBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFJMXNotificationBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMXNotifications/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFJMXNotificationBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFJMXNotificationBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.diagnostics.descriptor.WLDFJMXNotificationBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFJMXNotificationBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMXNotifications/{name}
rel=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMXNotifications
rel=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMXNotifications/{name}
rel=self

This resource.

POST

Update this [weblogic.diagnostics.descriptor.WLDFJMXNotificationBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFJMXNotificationBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/logActionCreateForm

This resource manages the create forms for the logActions collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFLogActionBean](#) entity populated with default values that can be customized then posted (using the POST method) to the logActions collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFLogActionBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/logActionCreateForm
rel=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/logActions **rel**=create

The collection resource for this create form resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/logActionCreateForm
rel=self

This resource.

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/logActions

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFLogActionBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFLogActionBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFLogActionBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/logActions](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/logActionCreateForm](#) **rel=create-form**
The create form resource for this collection resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/logActions](#) **rel=self**
This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFLogActionBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFLogActionBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/logActions/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFLogActionBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFLogActionBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.diagnostics.descriptor.WLDFLogActionBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFLogActionBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/logActions/{name}](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/logActions](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/logActions/{name}](#)
rel=self
This resource.

POST

Update this [weblogic.diagnostics.descriptor.WLDFLogActionBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFLogActionBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/lookupActions

The resource supports the following methods:

- [POST](#)

POST

Roles

Admin, Deployer

Request Body

Must contain a JSON object with the following fields:

typeName

typeName

Type: string

Response Body

Contains a JSON object with a array of weblogic.diagnostics.descriptor.WLDFActionBean references return field.

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/lookupNotification

The resource supports the following methods:

- [POST](#)

POST

Looks up an action with the given name.

Roles

Admin, Deployer

Request Body

Must contain a JSON object with the following fields:

name

name

Type: string

Response Body

Contains a JSON object with a weblogic.diagnostics.descriptor.WLDFNotificationBean reference return field.

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/RESTNotificationCreateForm

This resource manages the create forms for the RESTNotifications collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFRESTNotificationBean](#) entity populated with default values that can be customized then posted (using the POST method) to the RESTNotifications collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFRESTNotificationBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/RESTNotificationCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/RESTNotifications](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/RESTNotificationCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/RESTNotifications

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFRESTNotificationBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFRESTNotificationBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFRESTNotificationBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/RESTNotifications](#)
rel=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/RESTNotificationCreateForm](#) **rel**=create-form

The create form resource for this collection resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/RESTNotifications](#)
rel=self

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFRESTNotificationBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFRESTNotificationBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/RESTNotifications/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFRESTNotificationBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFRESTNotificationBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.diagnostics.descriptor.WLDFRESTNotificationBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFRESTNotificationBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/RESTNotifications/{name}
rel=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/RESTNotifications
rel=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/RESTNotifications/{name}
rel=self

This resource.

POST

Update this [weblogic.diagnostics.descriptor.WLDFRESTNotificationBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFRESTNotificationBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleDownActionCreateForm

This resource manages the create forms for the scaleDownActions collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFScaleDownActionBean](#) entity populated with default values that can be customized then posted (using the POST method) to the `scaleDownActions` collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFScaleDownActionBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleDownActionCreateForm](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleDownActions](#) **rel**=create

The collection resource for this create form resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleDownActionCreateForm](#) **rel**=self

This resource.

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleDownActions

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFScaleDownActionBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFScaleDownActionBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFScaleDownActionBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleDownActions](#)
rel=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleDownActionCreateForm](#) **rel**=create-form

The create form resource for this collection resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleDownActions](#)
rel=self

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFScaleDownActionBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFScaleDownActionBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleDownActions/{name} **}**

This resource manages a [weblogic.diagnostics.descriptor.WLDFScaleDownActionBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFScaleDownActionBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.diagnostics.descriptor.WLDFScaleDownActionBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFScaleDownActionBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleDownActions/{name}](#)
rel=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleDownActions](#)
rel=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleDownActions/{name}](#)
rel=self

This resource.

POST

Update this [weblogic.diagnostics.descriptor.WLDFScaleDownActionBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFScaleDownActionBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleUpActionCreateForm

This resource manages the create forms for the scaleUpActions collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFScaleUpActionBean](#) entity populated with default values that can be customized then posted (using the POST method) to the scaleUpActions collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFScaleUpActionBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleUpActionCreateForm rel=canonical](#)

This resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleUpActions rel=create](#)

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification rel=parent](#)

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleUpActionCreateForm rel=self](#)

This resource.

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleUpActions

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFScaleUpActionBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFScaleUpActionBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFScaleUpActionBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleUpActions](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleUpActionCreateForm](#) **rel=create-form**

The create form resource for this collection resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleUpActions](#) **rel=self**

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFScaleUpActionBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFScaleUpActionBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleUpActions/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFScaleUpActionBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFScaleUpActionBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.diagnostics.descriptor.WLDFScaleUpActionBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFScaleUpActionBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleUpActions/{name}
rel=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleUpActions
rel=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleUpActions/{name}
rel=self

This resource.

POST

Update this [weblogic.diagnostics.descriptor.WLDFScaleUpActionBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFScaleUpActionBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scriptActionCreateForm

This resource manages the create forms for the scriptActions collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFScriptActionBean](#) entity populated with default values that can be customized then posted (using the POST method) to the scriptActions collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFScriptActionBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scriptActionCreateForm
rel=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scriptActions **rel**=create

The collection resource for this create form resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scriptActionCreateForm
rel=self

This resource.

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scriptActions

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFScriptActionBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFScriptActionBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFScriptActionBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scriptActions](#)
rel=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scriptActionCreateForm](#)
rel=create-form

The create form resource for this collection resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scriptActions](#) **rel**=self

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFScriptActionBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFScriptActionBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scriptActions/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFScriptActionBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFScriptActionBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.diagnostics.descriptor.WLDFScriptActionBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFScriptActionBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scriptActions/{name}](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scriptActions](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scriptActions/{name}](#)
rel=self
This resource.

POST

Update this [weblogic.diagnostics.descriptor.WLDFScriptActionBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFScriptActionBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/SMTPNotificationCreateForm

This resource manages the create forms for the SMTPNotifications collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFSMTPNotificationBean](#) entity populated with default values that can be customized then posted (using the POST method) to the SMTPNotifications collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFSMTPNotificationBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/SMTPNotificationCreateForm **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/SMTPNotifications **rel**=create

The collection resource for this create form resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/SMTPNotificationCreateForm **rel**=self

This resource.

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/SMTPNotifications

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFSMTPNotificationBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFSMTPNotificationBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFSMTPNotificationBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/SMTPNotifications](#)
rel=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/SMTPNotificationCreateForm](#)
rel=create-form

The create form resource for this collection resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/SMTPNotifications](#)
rel=self

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFSMTPNotificationBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFSMTPNotificationBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/SMTPNotifications/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFSMTPNotificationBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFSMTPNotificationBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.diagnostics.descriptor.WLDFSMTPNotificationBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFSMTPNotificationBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/SMTPNotifications/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/SMTPNotifications **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/SMTPNotifications/{name} **rel**=self

This resource.

POST

Update this [weblogic.diagnostics.descriptor.WLDFSMTPNotificationBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFSMTPNotificationBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/SNMPNotificationCreateForm

This resource manages the create forms for the SNMPNotifications collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFSNMPNotificationBean](#) entity populated with default values that can be customized then posted (using the POST method) to the SNMPNotifications collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFSNMPNotificationBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/SNMPNotificationCreateForm **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/SNMPNotifications **rel**=create

The collection resource for this create form resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/SNMPNotificationCreateForm **rel**=self

This resource.

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/SNMPNotifications

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFSNMPNotificationBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFSNMPNotificationBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFSNMPNotificationBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/SNMPNotifications](#)
rel=canonical

This resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/SNMPNotificationCreateForm](#) **rel=create-form**

The create form resource for this collection resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/SNMPNotifications](#)
rel=self

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFSNMPNotificationBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFSNMPNotificationBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/SNMPNotifications/{name}
}

This resource manages a [weblogic.diagnostics.descriptor.WLDFSNMPNotificationBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFSNMPNotificationBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.diagnostics.descriptor.WLDFSNMPNotificationBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFSNMPNotificationBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/SNMPNotifications/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/SNMPNotifications](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/SNMPNotifications/{name}](#) **rel**=self

This resource.

POST

Update this [weblogic.diagnostics.descriptor.WLDFSNMPNotificationBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFSNMPNotificationBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/threadDumpActionCreateForm

This resource manages the create forms for the threadDumpActions collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFThreadDumpActionBean](#) entity populated with default values that can be customized then posted (using the POST method) to the threadDumpActions collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFThreadDumpActionBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/threadDumpActionCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/threadDumpActions](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/threadDumpActionCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/threadDumpActions

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFThreadDumpActionBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFThreadDumpActionBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFThreadDumpActionBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/threadDumpActions](#)
rel=canonical

This resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/threadDumpActionCreateForm](#)
rel=create-form

The create form resource for this collection resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification](#)
rel=parent

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/threadDumpActions](#)
rel=self

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFThreadDumpActionBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFThreadDumpActionBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/threadDumpActions/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFThreadDumpActionBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFThreadDumpActionBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.diagnostics.descriptor.WLDFThreadDumpActionBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFThreadDumpActionBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/threadDumpActions/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/threadDumpActions **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/threadDumpActions/{name} **rel**=self

This resource.

POST

Update this [weblogic.diagnostics.descriptor.WLDFThreadDumpActionBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFThreadDumpActionBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/watchCreateForm

This resource manages the create forms for the watches collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFWatchBean](#) entity populated with default values that can be customized then posted (using the POST method) to the watches collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFWatchBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/watchCreateForm](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/watches](#) **rel**=create
The collection resource for this create form resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/watchCreateForm](#)
rel=self
This resource.

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/watches

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFWatchBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFWatchBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFWatchBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/watches](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/watchCreateForm](#) **rel=create-form**
The create form resource for this collection resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/watches](#) **rel=self**
This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFWatchBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFWatchBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/watches/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFWatchBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFWatchBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.diagnostics.descriptor.WLDFWatchBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFWatchBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/watches/{name}](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/watches](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/watches/{name}/schedule](#) **rel**=schedule
This resource's schedule singleton resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/watches/{name}](#) **rel**=self
This resource.

POST

Update this [weblogic.diagnostics.descriptor.WLDFWatchBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFWatchBean](#) entity.

/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/watches/{name}/schedule

This resource manages a [weblogic.diagnostics.descriptor.WLDFScheduleBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.diagnostics.descriptor.WLDFScheduleBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFScheduleBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/watches/{name}/schedule](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/watches/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/resourceGroups/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/watches/{name}/schedule](#) **rel=self**

This resource.

POST

Update this [weblogic.diagnostics.descriptor.WLDFScheduleBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFScheduleBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplateCreateForm

This resource manages the create forms for the resourceGroupTemplates collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.ResourceGroupTemplateMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the resourceGroupTemplates collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ResourceGroupTemplateMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplateCreateForm](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates](#) **rel**=create
The collection resource for this create form resource.
- **uri**=[/management/weblogic/{version}/edit](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplateCreateForm](#)
rel=self
This resource.

/management/weblogic/{version}/edit/resourceGroupTemplates

This resource manages a collection of [weblogic.management.configuration.ResourceGroupTemplateMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.ResourceGroupTemplateMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.ResourceGroupTemplateMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplateCreateForm](#)
rel=create-form
The create form resource for this collection resource.
- **uri**=[/management/weblogic/{version}/edit](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates](#) **rel**=self
This resource.

POST

Add a new [weblogic.management.configuration.ResourceGroupTemplateMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.ResourceGroupTemplateMBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}

This resource manages a [weblogic.management.configuration.ResourceGroupTemplateMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.ResourceGroupTemplateMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.ResourceGroupTemplateMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ResourceGroupTemplateMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCStoreCreateForm](#) **rel**=JDBCStoreCreateForm
The create form resource for this resource's JDBCStores collection resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCStores](#) **rel**=JDBCStores
This resource's JDBCStores collection resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResourceCreateForm](#) **rel**=JDBCSystemResourceCreateForm
The create form resource for this resource's JDBCSystemResources collection resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources](#) **rel**=JDBCSystemResources
This resource's JDBCSystemResources collection resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSBridgeDestinationCreateForm](#) **rel**=JMSBridgeDestinationCreateForm
The create form resource for this resource's JMSBridgeDestinations collection resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSBridgeDestinations](#) **rel**=JMSBridgeDestinations
This resource's JMSBridgeDestinations collection resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSServerCreateForm](#) **rel**=JMSServerCreateForm
The create form resource for this resource's JMSServers collection resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSServers](#) **rel**=JMSServers
This resource's JMSServers collection resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResourceCreateForm](#) **rel**=JMSSystemResourceCreateForm
The create form resource for this resource's JMSSystemResources collection resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources **rel**=JMSSystemResources
This resource's JMSSystemResources collection resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/SAFAgentCreateForm **rel**=SAFAgentCreateForm
The create form resource for this resource's SAFAgents collection resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/SAFAgents **rel**=SAFAgents
This resource's SAFAgents collection resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResourceCreateForm **rel**=WLDFSystemResourceCreateForm
The create form resource for this resource's WLDFSystemResources collection resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources **rel**=WLDFSystemResources
This resource's WLDFSystemResources collection resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/appDeployments **rel**=appDeployments
This resource's appDeployments collection resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name} **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/fileStoreCreateForm **rel**=fileStoreCreateForm
The create form resource for this resource's fileStores collection resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/fileStores **rel**=fileStores
This resource's fileStores collection resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/foreignJNDIPProviderCreateForm **rel**=foreignJNDIPProviderCreateForm
The create form resource for this resource's foreignJNDIPProviders collection resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/foreignJNDIPProviders **rel**=foreignJNDIPProviders
This resource's foreignJNDIPProviders collection resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/libraries **rel**=libraries
This resource's libraries collection resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/mailSessionCreateForm **rel**=mailSessionCreateForm
The create form resource for this resource's mailSessions collection resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/mailSessions **rel**=mailSessions
This resource's mailSessions collection resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/managedExecutorServiceCreateForm **rel**=managedExecutorServiceCreateForm
The create form resource for this resource's managedExecutorServices collection resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/managedExecutorServices **rel**=managedExecutorServices
This resource's managedExecutorServices collection resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/managedScheduledExecutorServiceCreateForm **rel**=managedScheduledExecutorServiceCreateForm
The create form resource for this resource's managedScheduledExecutorServices collection resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/managedScheduledExecutorServices **rel**=managedScheduledExecutorServices
This resource's managedScheduledExecutorServices collection resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/managedThreadFactories **rel**=managedThreadFactories
This resource's managedThreadFactories collection resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/managedThreadFactoryCreateForm **rel**=managedThreadFactoryCreateForm
The create form resource for this resource's managedThreadFactories collection resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/messagingBridgeCreateForm **rel**=messagingBridgeCreateForm
The create form resource for this resource's messagingBridges collection resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/messagingBridges **rel**=messagingBridges
This resource's messagingBridges collection resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/osgiFrameworkCreateForm **rel**=osgiFrameworkCreateForm
The create form resource for this resource's osgiFrameworks collection resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/osgiFrameworks **rel**=osgiFrameworks
This resource's osgiFrameworks collection resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name} **rel**=self
This resource.

POST

Update this [weblogic.management.configuration.ResourceGroupTemplateMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.ResourceGroupTemplateMBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/appDeployments

This resource manages a collection of [weblogic.management.configuration.AppDeploymentMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.AppDeploymentMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.AppDeploymentMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/appDeployments](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/appDeployments](#) **rel=self**
This resource.

POST

The resource supports the following methods:

- [POST accepting application/json](#)
- [POST accepting multipart/form-data](#)

POST accepting application/json

This resource is used to deploy applications that are already on the administration server. The application must be a supported package type (for example, an EAR or WAR module).

This method supports both asynchronous and best effort synchronous invocations. The behavior is controlled by the 'Prefer' header. See [About Synchronous and Asynchronous Operations](#).

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.AppDeploymentMBean](#) entity.

To deploy an application you must provide the name of the application, the path to the source of the deployable unit on the administration server, and the targets to which the application will be deployed.

If the source path is relative, it is resolved relative to *InstallDir/app* if *InstallDir* is not null; otherwise, it is resolved relative to the domain root.

POST accepting multipart/form-data

Use the multi-part form to upload an application from the client to the server and then deploy it.

- `sourcePath`: the deployment to upload (required)
- `planPath`: the deployment plan to upload (optional)
- `model`: JSONObject containing an `AppDeploymentMBean` entity that contains the rest of the deployment information (however, deployment/plan information is ignored) (required)

This method supports both asynchronous and best effort synchronous invocations. The behavior is controlled by the 'Prefer' header. See [About Synchronous and Asynchronous Operations](#).

Roles

Admin, Deployer

Request Body

Use the multi-part form to deploy an application.

- `sourcePath`: the deployment to upload (required)
- `planPath`: the deployment plan to upload (optional)

- model: JSONObject containing an AppDeploymentMBean entity that contains the rest of the deployment information. However, deployment/plan information is ignored. (required)

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/appDeployments/{name}

This resource manages a [weblogic.management.configuration.AppDeploymentMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Undeploy an application.

This method supports both asynchronous and best effort synchronous invocations. The behavior is controlled by the 'Prefer' header. See *About Synchronous and Asynchronous Operations*.

Roles

Admin, Deployer

GET

Get this [weblogic.management.configuration.AppDeploymentMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.AppDeploymentMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/appDeployments/{name}/createPlan **rel**=action **title**=createPlan
This resource's createPlan action resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/appDeployments/{name} **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/appDeployments **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/appDeployments/{name}/redeploy **rel**=redeploy
This resource's redeploy resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/appDeployments/{name} **rel**=self
This resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/appDeployments/{name}/subDeploymentCreateForm **rel**=subDeploymentCreateForm
The create form resource for this resource's subDeployments collection resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/appDeployments/{name}/subDeployments **rel**=subDeployments
This resource's subDeployments collection resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/appDeployments/{name}/update **rel**=update
This resource's update resource.

POST

Update this [weblogic.management.configuration.AppDeploymentMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.AppDeploymentMBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/appDeployments/{name}/createPlan

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

POST

Create a deployment plan in the specified directory.

Roles

Admin, Deployer

Request Body

Must contain a JSON object with the following fields:

planPath

planPath

Type: string

Response Body

Contains a JSON object with a string return field.

POST

Create a deployment plan in a default directory

Roles

Admin, Deployer

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/appDeployments/{name}/redeploy

The resource supports the following methods:

- [POST](#)

POST

Use the multi-part form to redeploy this application.

- `sourcePath`: the deployment to upload (required)
- `planPath`: the deployment plan to upload (optional)
- `model`: JSONObject containing an `AppDeploymentMBean` entity that contains the rest of the deployment information. However, `deployment/plan` information is ignored. (required)

This method supports both asynchronous and best effort synchronous invocations. The behavior is controlled by the 'Prefer' header. See [About Synchronous and Asynchronous Operations](#).

Roles

Admin, Deployer

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/appDeployments/{name}/subDeploymentCreateForm

This resource manages the create forms for the subDeployments collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.SubDeploymentMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the subDeployments collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/appDeployments/{name}/subDeploymentCreateForm](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/appDeployments/{name}/subDeployments](#) **rel=create**
The collection resource for this create form resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/appDeployments/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/appDeployments/{name}/subDeploymentCreateForm](#) **rel=self**
This resource.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/appDeployments/{name}/subDeployments

This resource manages a collection of [weblogic.management.configuration.SubDeploymentMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.SubDeploymentMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.SubDeploymentMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/appDeployments/{name}/subDeployments](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/appDeployments/{name}/subDeploymentCreateForm](#) **rel=create-form**

The create form resource for this collection resource.

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/appDeployments/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/appDeployments/{name}/subDeployments](#) **rel=self**

This resource.

POST

Add a new [weblogic.management.configuration.SubDeploymentMBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/appDeployments/{name}/subDeployments/{name}

This resource manages a [weblogic.management.configuration.SubDeploymentMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

DELETE

Delete this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/appDeployments/{name}/subDeployments/{name}](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/appDeployments/{name}/subDeployments](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/appDeployments/{name}/subDeployments/{name}](#) **rel=self**
This resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/appDeployments/{name}/subDeployments/{name}/subDeployments](#) **rel=subDeployments**
This resource's subDeployments collection resource.

POST

Update this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/appDeployments/{name}/subDeployments/{name}/subDeployments

This resource manages a collection of [weblogic.management.configuration.SubDeploymentMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.configuration.SubDeploymentMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.SubDeploymentMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/appDeployments/{name}/subDeployments/{name}/subDeployments](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/appDeployments/{name}/subDeployments/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/appDeployments/{name}/subDeployments/{name}/subDeployments](#) **rel=self**
This resource.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/appDeployments/{name}/subDeployments/{name}/subDeployments/{name}

This resource manages a [weblogic.management.configuration.SubDeploymentMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/appDeployments/{name}/subDeployments/{name}/subDeployments/{name}](#)
rel=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/appDeployments/{name}/subDeployments/{name}/subDeployments](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/appDeployments/{name}/subDeployments/{name}/subDeployments/{name}](#)
rel=self

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/appDeployments/{name}/subDeployments/{name}/subDeployments/{name}/subDeployments](#) **rel**=subDeployments

This resource's subDeployments collection resource.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/appDeployments/{name}/subDeployments/{name}/subD

POST

Update this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/appDeployments/{name}/update

The resource supports the following methods:

- [POST](#)

POST

Update this application.

This method supports both asynchronous and best effort synchronous invocations. The behavior is controlled by the 'Prefer' header. See *About Synchronous and Asynchronous Operations*.

Roles

Admin, Deployer

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/fileStoreCreateForm

This resource manages the create forms for the fileStores collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.FileStoreMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the fileStores collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.FileStoreMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/fileStoreCreateForm **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/fileStores **rel**=create

The collection resource for this create form resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/fileStoreCreateForm **rel**=self

This resource.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/fileStores

This resource manages a collection of [weblogic.management.configuration.FileStoreMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.FileStoreMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.FileStoreMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/fileStores](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/fileStoreCreateForm](#) **rel**=create-form
The create form resource for this collection resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/fileStores](#) **rel**=self
This resource.

POST

Add a new [weblogic.management.configuration.FileStoreMBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.FileStoreMBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/fileStores/{name}

This resource manages a [weblogic.management.configuration.FileStoreMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.FileStoreMBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.management.configuration.FileStoreMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.FileStoreMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/fileStores/{name}](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/fileStores](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/fileStores/{name}](#) **rel**=self
This resource.

POST

Update this [weblogic.management.configuration.FileStoreMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.FileStoreMBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/foreignJNDIPProviderCreateForm

This resource manages the create forms for the foreignJNDIPProviders collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.ForeignJNDIProviderMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the [foreignJNDIProviders](#) collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ForeignJNDIProviderMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/foreignJNDIProviderCreateForm](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/foreignJNDIProviders](#) **rel**=create
The collection resource for this create form resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/foreignJNDIProviderCreateForm](#) **rel**=self
This resource.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/foreignJNDIProviders

This resource manages a collection of [weblogic.management.configuration.ForeignJNDIProviderMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.ForeignJNDIProviderMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.ForeignJNDIProviderMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/foreignJNDIProviders](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/foreignJNDIProviderCreateForm](#) **rel**=create-form
The create form resource for this collection resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/foreignJNDIProviders](#) **rel**=self
This resource.

POST

Add a new [weblogic.management.configuration.ForeignJNDIProviderMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.ForeignJNDIProviderMBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/foreignJNDIProviders/{name}

This resource manages a [weblogic.management.configuration.ForeignJNDIProviderMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.ForeignJNDIProviderMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.ForeignJNDIPProviderMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ForeignJNDIPProviderMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/foreignJNDIProviders/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/foreignJNDIProviders/{name}/foreignJNDILinkCreateForm](#)
rel=foreignJNDILinkCreateForm

The create form resource for this resource's foreignJNDILinks collection resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/foreignJNDIProviders/{name}/foreignJNDILinks](#) **rel**=foreignJNDILinks

This resource's foreignJNDILinks collection resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/foreignJNDIProviders](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/foreignJNDIProviders/{name}](#) **rel**=self

This resource.

POST

Update this [weblogic.management.configuration.ForeignJNDIProviderMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.ForeignJNDIProviderMBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/foreignJNDIProviders/{name}/foreignJNDILinkCreateForm

This resource manages the create forms for the foreignJNDILinks collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.ForeignJNDILinkMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the foreignJNDILinks collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ForeignJNDILinkMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/foreignJNDIProviders/{name}/foreignJNDILinkCreateForm](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/foreignJNDIProviders/{name}/foreignJNDILinks](#) **rel=create**
The collection resource for this create form resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/foreignJNDIProviders/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/foreignJNDIProviders/{name}/foreignJNDILinkCreateForm](#) **rel=self**
This resource.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/foreignJNDIProviders/{name}/foreignJNDILinks

This resource manages a collection of [weblogic.management.configuration.ForeignJNDILinkMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.ForeignJNDILinkMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.ForeignJNDILinkMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/foreignJNDIProviders/{name}/foreignJNDILinks](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/foreignJNDIProviders/{name}/foreignJNDILinkCreateForm](#) **rel=create-form**
The create form resource for this collection resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/foreignJNDIProviders/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/foreignJNDIProviders/{name}/foreignJNDILinks](#) **rel=self**
This resource.

POST

Add a new [weblogic.management.configuration.ForeignJNDILinkMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.ForeignJNDILinkMBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/foreignJNDIProviders/{name}/foreignJNDILinks/{name}

This resource manages a [weblogic.management.configuration.ForeignJNDILinkMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

DELETE

Delete this [weblogic.management.configuration.ForeignJNDILinkMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.ForeignJNDILinkMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ForeignJNDILinkMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/foreignJNDIProviders/{name}/foreignJNDILinks/{name} **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/foreignJNDIProviders/{name}/foreignJNDILinks **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/foreignJNDIProviders/{name}/foreignJNDILinks/{name} **rel**=self
This resource.

POST

POST

Update this [weblogic.management.configuration.ForeignJNDILinkMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.ForeignJNDILinkMBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCStoreCreateForm

This resource manages the create forms for the JDBCStores collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.JDBCStoreMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the JDBCStores collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.JDBCStoreMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCStoreCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCStores](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCStoreCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCStores

This resource manages a collection of [weblogic.management.configuration.JDBCStoreMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.JDBCStoreMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.JDBCStoreMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCStores](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCStoreCreateForm](#) **rel**=create-form

The create form resource for this collection resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCStores](#) **rel**=self

This resource.

POST

Add a new [weblogic.management.configuration.JDBCStoreMBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.JDBCStoreMBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCStores/{name}

This resource manages a [weblogic.management.configuration.JDBCStoreMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.JDBCStoreMBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.management.configuration.JDBCStoreMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.JDBCStoreMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCStores/{name}](#) **rel**=canonical
This resource.
- **rel**=dataSource
This resource's dataSource reference to a [weblogic.management.configuration.JDBCSystemResourceMBean](#) resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCStores](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCStores/{name}](#) **rel**=self
This resource.

POST

Update this [weblogic.management.configuration.JDBCStoreMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.JDBCStoreMBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResourceCreateForm

This resource manages the create forms for the JDBCSystemResources collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.JDBCSystemResourceMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the JDBCSystemResources collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.JDBCSystemResourceMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResourceCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResourceCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources

This resource manages a collection of [weblogic.management.configuration.JDBCSystemResourceMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.JDBCSystemResourceMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.JDBCSystemResourceMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResourceCreateForm](#) **rel=create-form**
The create form resource for this collection resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources](#) **rel=self**
This resource.

POST

Add a new [weblogic.management.configuration.JDBCSystemResourceMBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.JDBCSystemResourceMBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources/{name}

This resource manages a [weblogic.management.configuration.JDBCSystemResourceMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

DELETE

Delete this [weblogic.management.configuration.JDBCSystemResourceMBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.management.configuration.JDBCSystemResourceMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.JDBCSystemResourceMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources/{name}/JDBCResource](#) **rel**=JDBCResource
This resource's JDBCResource singleton resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources/{name}](#) **rel**=canonical
This resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources](#) **rel**=parent
The parent resource of this resource.
- **rel**=resource
This resource's resource reference to a [weblogic.descriptor.DescriptorBean](#) resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources/{name}](#) **rel**=self
This resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources/{name}/subDeploymentCreateForm](#) **rel**=subDeploymentCreateForm
The create form resource for this resource's subDeployments collection resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources/{name}/subDeployments](#) **rel**=subDeployments
This resource's subDeployments collection resource.

POST

Update this [weblogic.management.configuration.JDBCSystemResourceMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.JDBCSystemResourceMBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources/{name}/JDBCResource

This resource manages a [weblogic.j2ee.descriptor.wl.JDBCDataSourceBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.JDBCDataSourceBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.JDBCDataSourceBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources/{name}/JDBCResource/JDBCConnectionPoolParams](#)
rel=JDBCConnectionPoolParams
This resource's JDBCConnectionPoolParams singleton resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources/{name}/JDBCResource/JDBCDataSourceParams](#)
rel=JDBCDataSourceParams
This resource's JDBCDataSourceParams singleton resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources/{name}/JDBCResource/JBCDriverParams](#)
rel=JBCDriverParams
This resource's JBCDriverParams singleton resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources/{name}/JDBCResource/JDBCOracleParams](#)
rel=JDBCOracleParams
This resource's JDBCOracleParams singleton resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources/{name}/JDBCResource/JDBCXAParams](#) **rel**=JDBCXAParams
This resource's JDBCXAParams singleton resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources/{name}/JDBCResource](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources/{name}/JDBCResource/internalProperties](#)
rel=internalProperties
This resource's internalProperties singleton resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources/{name}/JDBCResource](#) **rel**=self
This resource.

POST

Update this [weblogic.j2ee.descriptor.wl.JDBCDataSourceBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.JDBCDataSourceBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources/{name}/JDBCResource/internalProperties

This resource manages a [weblogic.j2ee.descriptor.wl.JDBCPropertiesBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.j2ee.descriptor.wl.JDBCPropertiesBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.JDBCPropertiesBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources/{name}/JDBCResource/internalProperties **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources/{name}/JDBCResource **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources/{name}/JDBCResource/internalProperties/properties **rel**=properties

This resource's properties collection resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources/{name}/JDBCResource/internalProperties/propertyCreateForm **rel**=propertyCreateForm

The create form resource for this resource's properties collection resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources/{name}/JDBCResource/internalProperties **rel**=self

This resource.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources/{name}/JDBCResource/internalProperties/properties

This resource manages a collection of [weblogic.j2ee.descriptor.wl.JDBCPropertyBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.j2ee.descriptor.wl.JDBCPropertyBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.j2ee.descriptor.wl.JDBCPropertyBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources/{name}/JDBCResource/internalProperties/properties](#)
rel=canonical

This resource.

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources/{name}/JDBCResource/internalProperties/propertyCreateForm](#)
rel=create-form

The create form resource for this collection resource.

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources/{name}/JDBCResource/internalProperties](#)
rel=parent

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources/{name}/JDBCResource/internalProperties/properties](#)
rel=self

This resource.

POST

Add a new [weblogic.j2ee.descriptor.wl.JDBCPropertyBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.JDBCPropertyBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources/{name}/JDBCResource/internalProperties/properties/{name} **}**

This resource manages a [weblogic.j2ee.descriptor.wl.JDBCPropertyBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

DELETE

Delete this [weblogic.j2ee.descriptor.wl.JDBCPropertyBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.j2ee.descriptor.wl.JDBCPropertyBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.JDBCPropertyBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources/{name}/JDBCResource/internalProperties/properties/{name}
rel=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources/{name}/JDBCResource/internalProperties/properties
rel=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources/{name}/JDBCResource/internalProperties/properties/{name}
rel=self

This resource.

POST

Update this [weblogic.j2ee.descriptor.wl.JDBCPropertyBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.JDBCPropertyBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources/{name}/JDBCResource/internalProperties/propertyCreateForm

This resource manages the create forms for the properties collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.j2ee.descriptor.wl.JDBCPropertyBean](#) entity populated with default values that can be customized then posted (using the POST method) to the properties collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.JDBCPropertyBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources/{name}/JDBCResource/internalProperties/propertyCreateForm](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources/{name}/JDBCResource/internalProperties/properties](#) **rel**=create

The collection resource for this create form resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources/{name}/JDBCResource/internalProperties](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources/{name}/JDBCResource/internalProperties/propertyCreateForm](#) **rel**=self

This resource.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources/{name}/JDBCResource/JDBCConnectionPoolParams

This resource manages a [weblogic.j2ee.descriptor.wl.JDBCConnectionPoolParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.JDBCConnectionPoolParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.JDBCConnectionPoolParamsBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources/{name}/JDBCResource/JDBCConnectionPoolParams](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources/{name}/JDBCResource](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources/{name}/JDBCResource/JDBCConnectionPoolParams](#) **rel**=self
This resource.

POST

Update this [weblogic.j2ee.descriptor.wl.JDBCConnectionPoolParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.JDBCConnectionPoolParamsBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources/{name}/JDBCResource/JDBCDataSourceParams

This resource manages a [weblogic.j2ee.descriptor.wl.JDBCDataSourceParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.JDBCDataSourceParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.JDBCDataSourceParamsBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources/{name}/JDBCResource/JDBCDataSourceParams
rel=canonical
This resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources/{name}/JDBCResource **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources/{name}/JDBCResource/JDBCDataSourceParams **rel**=self
This resource.

POST

Update this [weblogic.j2ee.descriptor.wl.JDBCDataSourceParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.JDBCDataSourceParamsBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources/{name}/JDBCResource/JDBCDriverParams

This resource manages a [weblogic.j2ee.descriptor.wl.JDBCDriverParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources/{name}/JDBCResource/JDBC-

POST

Update this [weblogic.j2ee.descriptor.wl.JDBCDriverParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.JDBCDriverParamsBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources/{name}/JDBCResource/JDBCDriverParams/properties

This resource manages a [weblogic.j2ee.descriptor.wl.JDBCPropertiesBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.j2ee.descriptor.wl.JDBCPropertiesBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.JDBCPropertiesBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources/{name}/JDBCResource/JDBCDriverParams/properties
rel=canonical
This resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources/{name}/JDBCResource/JDBCDriverParams **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources/{name}/JDBCResource/JDBCDriverParams/properties/properties **rel**=properties
This resource's properties collection resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources/{name}/JDBCResource/JDBCDriverParams/properties/propertyCreateForm **rel**=propertyCreateForm
The create form resource for this resource's properties collection resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources/{name}/JDBCResource/JDBCDriverParams/properties **rel**=self
This resource.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources/{name}/JDBCResource/JDBCDriverParams/properties/properties

This resource manages a collection of [weblogic.j2ee.descriptor.wl.JDBCPropertyBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.j2ee.descriptor.wl.JDBCPropertyBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.j2ee.descriptor.wl.JDBCPropertyBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources/{name}/JDBCResource/JDBCDriverParams/properties/properties **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources/{name}/JDBCResource/JDBCDriverParams/properties/propertyCreateForm **rel**=create-form

The create form resource for this collection resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources/{name}/JDBCResource/JDBCDriverParams/properties **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources/{name}/JDBCResource/JDBCDriverParams/properties/properties **rel**=self

This resource.

POST

Add a new [weblogic.j2ee.descriptor.wl.JDBCPropertyBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.JDBCPropertyBean](#) entity.

DELETE

Delete this [weblogic.j2ee.descriptor.wl.JDBCPropertyBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.j2ee.descriptor.wl.JDBCPropertyBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.JDBCPropertyBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources/{name}/JDBCResource/JBCDriverParams/properties/properties/{name}](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources/{name}/JDBCResource/JBCDriverParams/properties/properties](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources/{name}/JDBCResource/JBCDriverParams/properties/properties/{name}](#) **rel=self**

This resource.

POST

Update this [weblogic.j2ee.descriptor.wl.JDBCPropertyBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.JDBCPropertyBean](#) entity.

GET

This resource returns a [weblogic.j2ee.descriptor.wl.JDBCPropertyBean](#) entity populated with default values that can be customized then posted (using the POST method) to the properties collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.JDBCPropertyBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources/{name}/JDBCResource/JDBCDriverParams/properties/propertyCreateForm](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources/{name}/JDBCResource/JDBCDriverParams/properties/properties](#) **rel**=create

The collection resource for this create form resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources/{name}/JDBCResource/JDBCDriverParams/properties](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources/{name}/JDBCResource/JDBCDriverParams/properties/propertyCreateForm](#) **rel**=self

This resource.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources/{name}/JDBCResource/JDBCOracleParams

This resource manages a [weblogic.j2ee.descriptor.wl.JDBCOracleParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.JDBCOracleParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.JDBCOracleParamsBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources/{name}/JDBCResource/JDBCOracleParams](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources/{name}/JDBCResource](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources/{name}/JDBCResource/JDBCOracleParams](#) **rel**=self
This resource.

POST

Update this [weblogic.j2ee.descriptor.wl.JDBCOracleParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.JDBCOracleParamsBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources/{name}/JDBCResource/JDBCXAParams

This resource manages a [weblogic.j2ee.descriptor.wl.JDBCXAParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.JDBCXAParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.JDBCXAParamsBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources/{name}/JDBCResource/JDBCXAParams **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources/{name}/JDBCResource **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources/{name}/JDBCResource/JDBCXAParams **rel**=self
This resource.

POST

Update this [weblogic.j2ee.descriptor.wl.JDBCXAParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.JDBCXAParamsBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources/{name}/subDeploymentCreateForm

This resource manages the create forms for the subDeployments collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.SubDeploymentMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the subDeployments collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources/{name}/subDeploymentCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources/{name}/subDeployments](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources/{name}/subDeploymentCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources/{name}/subDeployments

This resource manages a collection of [weblogic.management.configuration.SubDeploymentMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.SubDeploymentMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.SubDeploymentMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources/{name}/subDeployments](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources/{name}/subDeploymentCreateForm](#) **rel=create-form**

The create form resource for this collection resource.

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources/{name}/subDeployments](#) **rel=self**

This resource.

POST

Add a new [weblogic.management.configuration.SubDeploymentMBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources/{name}/subDeployments/{name}

This resource manages a [weblogic.management.configuration.SubDeploymentMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources/{name}/subDeployments/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources/{name}/subDeployments](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources/{name}/subDeployments/{name}](#) **rel**=self

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources/{name}/subDeployments/{name}/subDeployments](#)
rel=subDeployments

This resource's subDeployments collection resource.

POST

Update this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBC SystemResources/{name}/subDeployments/{name}/subDeployments

This resource manages a collection of [weblogic.management.configuration.SubDeploymentMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.configuration.SubDeploymentMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.SubDeploymentMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources/{name}/subDeployments/{name}/subDeployments](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources/{name}/subDeployments/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources/{name}/subDeployments/{name}/subDeployments](#) **rel**=self
This resource.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBC SystemResources/{name}/subDeployments/{name}/subDeployments/{name}

This resource manages a [weblogic.management.configuration.SubDeploymentMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources/{name}/subDeployments/{name}/subDeployments/{name}
rel=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources/{name}/subDeployments/{name}/subDeployments
rel=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources/{name}/subDeployments/{name}/subDeployments/{name}
rel=self

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JDBCSystemResources/{name}/subDeployments/{name}/subDeployments/{name}/subDeployments
rel=subDeployments

This resource's subDeployments collection resource.

POST

Update this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSBridgeDestinationCreateForm

This resource manages the create forms for the JMSBridgeDestinations collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.JMSBridgeDestinationMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the [JMSBridgeDestinations](#) collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.JMSBridgeDestinationMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSBridgeDestinationCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSBridgeDestinations](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSBridgeDestinationCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSBridgeDestinations

This resource manages a collection of [weblogic.management.configuration.JMSBridgeDestinationMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.JMSBridgeDestinationMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.JMSBridgeDestinationMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSBridgeDestinations](#) [rel=canonical](#)

This resource.

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSBridgeDestinationCreateForm](#) [rel=create-form](#)

The create form resource for this collection resource.

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}](#) [rel=parent](#)

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSBridgeDestinations](#) [rel=self](#)

This resource.

POST

Add a new [weblogic.management.configuration.JMSBridgeDestinationMBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.JMSBridgeDestinationMBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSBridgeDestinations/{name}

This resource manages a [weblogic.management.configuration.JMSBridgeDestinationMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.JMSBridgeDestinationMBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.management.configuration.JMSBridgeDestinationMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.JMSBridgeDestinationMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSBridgeDestinations/{name}](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSBridgeDestinations](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSBridgeDestinations/{name}](#) **rel=self**

This resource.

POST

Update this [weblogic.management.configuration.JMSBridgeDestinationMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.JMSBridgeDestinationMBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSServerCreateForm

This resource manages the create forms for the JMServers collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.JMSServerMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the JMSServers collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.JMSServerMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSServerCreateForm](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSServers](#) **rel=create**
The collection resource for this create form resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSServerCreateForm](#) **rel=self**
This resource.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSServers

This resource manages a collection of [weblogic.management.configuration.JMSServerMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.JMSServerMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.JMSServerMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSServers](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSServerCreateForm](#) **rel=create-form**
The create form resource for this collection resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSServers](#) **rel=self**
This resource.

POST

Add a new [weblogic.management.configuration.JMSServerMBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.JMSServerMBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSServers/{name}

This resource manages a [weblogic.management.configuration.JMSServerMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

DELETE

Delete this [weblogic.management.configuration.JMSServerMBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.management.configuration.JMSServerMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.JMSServerMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSServers/{name}/JMSMessageLogFile](#) **rel**=JMSMessageLogFile
This resource's JMSMessageLogFile singleton resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSServers/{name}](#) **rel**=canonical
This resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSServers](#) **rel**=parent
The parent resource of this resource.
- **rel**=persistentStore
This resource's persistentStore reference to a [weblogic.management.configuration.PersistentStoreMBean](#) resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSServers/{name}](#) **rel**=self
This resource.

POST

Update this [weblogic.management.configuration.JMSServerMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.JMSServerMBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSServers/{name}/JMSMessageLogFile

This resource manages a [weblogic.management.configuration.JMSMessageLogFileMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.JMSMessageLogFileMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.JMSMessageLogFileMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMS Servers/{name}/JMSMessageLogFile rel=canonical](#)
This resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMS Servers/{name} rel=parent](#)
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMS Servers/{name}/JMSMessageLogFile rel=self](#)
This resource.

POST

Update this [weblogic.management.configuration.JMSMessageLogFileMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.JMSMessageLogFileMBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResourceCreateForm

This resource manages the create forms for the JMSSystemResources collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.JMSSystemResourceMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the JMSSystemResources collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.JMSSystemResourceMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResourceCreateForm](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources](#) **rel=create**
The collection resource for this create form resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResourceCreateForm](#) **rel=self**
This resource.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources

This resource manages a collection of [weblogic.management.configuration.JMSSystemResourceMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.JMSSystemResourceMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.JMSSystemResourceMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResourceCreateForm](#) **rel=create-form**
The create form resource for this collection resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources](#) **rel=self**
This resource.

POST

Add a new [weblogic.management.configuration.JMSSystemResourceMBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.JMSSystemResourceMBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}

This resource manages a [weblogic.management.configuration.JMSSystemResourceMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

DELETE

Delete this [weblogic.management.configuration.JMSSystemResourceMBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.management.configuration.JMSSystemResourceMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.JMSSystemResourceMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource](#) **rel**=JMSResource
This resource's JMSResource singleton resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}](#) **rel**=canonical
This resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources](#) **rel**=parent
The parent resource of this resource.
- **rel**=resource
This resource's resource reference to a [weblogic.descriptor.DescriptorBean](#) resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}](#) **rel**=self
This resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/subDeploymentCreateForm](#) **rel**=subDeploymentCreateForm
The create form resource for this resource's subDeployments collection resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/subDeployments](#) **rel**=subDeployments
This resource's subDeployments collection resource.

POST

POST

Update this [weblogic.management.configuration.JMSSystemResourceMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.JMSSystemResourceMBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource

This resource manages a [weblogic.j2ee.descriptor.wl.JMSBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.JMSBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.JMSBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/SAFErrorHandlingCreateForm](#)
rel=SAFErrorHandlingCreateForm
The create form resource for this resource's SAFErrorHandlings collection resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/SAFErrorHandlings](#)
rel=SAFErrorHandlings
This resource's SAFErrorHandlings collection resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinationCreateForm](#)
rel=SAFImportedDestinationCreateForm
The create form resource for this resource's SAFImportedDestinations collection resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations](#)
rel=SAFImportedDestinations
This resource's SAFImportedDestinations collection resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/SAFRemoteContextCreateForm](#)
rel=SAFRemoteContextCreateForm
The create form resource for this resource's SAFRemoteContexts collection resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/SAFRemoteContexts](#)
rel=SAFRemoteContexts
This resource's SAFRemoteContexts collection resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories](#)
rel=connectionFactories
This resource's connectionFactories collection resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/connectionFactoryCreateForm
rel=connectionFactoryCreateForm
The create form resource for this resource's connectionFactories collection resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/destinationKeyCreateForm
rel=destinationKeyCreateForm
The create form resource for this resource's destinationKeys collection resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/destinationKeys **rel**=destinationKeys
This resource's destinationKeys collection resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/foreignServerCreateForm
rel=foreignServerCreateForm
The create form resource for this resource's foreignServers collection resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/foreignServers **rel**=foreignServers
This resource's foreignServers collection resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name} **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/queueCreateForm **rel**=queueCreateForm
The create form resource for this resource's queues collection resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/queues **rel**=queues
This resource's queues collection resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/quotaCreateForm **rel**=quotaCreateForm
The create form resource for this resource's quotas collection resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/quotas **rel**=quotas
This resource's quotas collection resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource **rel**=self
This resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/templateCreateForm
rel=templateCreateForm
The create form resource for this resource's templates collection resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/templates **rel**=templates

This resource's templates collection resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/topicCreateForm **rel**=topicCreateForm

The create form resource for this resource's topics collection resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/topics **rel**=topics

This resource's topics collection resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedQueueCreateForm **rel**=uniformDistributedQueueCreateForm

The create form resource for this resource's uniformDistributedQueues collection resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues **rel**=uniformDistributedQueues

This resource's uniformDistributedQueues collection resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopicCreateForm **rel**=uniformDistributedTopicCreateForm

The create form resource for this resource's uniformDistributedTopics collection resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics **rel**=uniformDistributedTopics

This resource's uniformDistributedTopics collection resource.

POST

Update this [weblogic.j2ee.descriptor.wl.JMSBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.JMSBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories

This resource manages a collection of [weblogic.j2ee.descriptor.wl.JMSConnectionFactoryBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.j2ee.descriptor.wl.JMSConnectionFactoryBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.j2ee.descriptor.wl.JMSConnectionFactoryBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/connectionFactoryCreateForm](#) **rel=create-form**
The create form resource for this collection resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories](#) **rel=self**
This resource.

POST

Add a new [weblogic.j2ee.descriptor.wl.JMSConnectionFactoryBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.JMSConnectionFactoryBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}

This resource manages a [weblogic.j2ee.descriptor.wl.JMSConnectionFactoryBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

DELETE

Delete this [weblogic.j2ee.descriptor.wl.JMSConnectionFactoryBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.j2ee.descriptor.wl.JMSConnectionFactoryBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.JMSConnectionFactoryBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}](#)
[rel=canonical](#)

This resource.

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}/clientParams](#)
[rel=clientParams](#)

This resource's clientParams singleton resource.

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}/defaultDeliveryParams](#)
[rel=defaultDeliveryParams](#)

This resource's defaultDeliveryParams singleton resource.

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}/flowControlParams](#)
[rel=flowControlParams](#)

This resource's flowControlParams singleton resource.

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}/loadBalancingParams](#)
[rel=loadBalancingParams](#)

This resource's loadBalancingParams singleton resource.

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories](#)
[rel=parent](#)

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}/securityParams](#)
[rel=securityParams](#)

This resource's securityParams singleton resource.

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}](#)
[rel=self](#)

This resource.

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}/transactionParams](#)
[rel=transactionParams](#)

This resource's transactionParams singleton resource.

POST

Update this [weblogic.j2ee.descriptor.wl.JMSConnectionFactoryBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.JMSConnectionFactoryBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}/clientParams

This resource manages a [weblogic.j2ee.descriptor.wl.ClientParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.ClientParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.ClientParamsBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}/clientParams **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories/{name} **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}/clientParams **rel**=self
This resource.

POST

POST

Update this [weblogic.j2ee.descriptor.wl.ClientParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.ClientParamsBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}/defaultDeliveryParams

This resource manages a [weblogic.j2ee.descriptor.wl.DefaultDeliveryParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.DefaultDeliveryParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.DefaultDeliveryParamsBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}/defaultDeliveryParams](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}/defaultDeliveryParams](#) **rel**=self

This resource.

POST

Update this [weblogic.j2ee.descriptor.wl.DefaultDeliveryParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.DefaultDeliveryParamsBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}/flowControlParams

This resource manages a [weblogic.j2ee.descriptor.wl.FlowControlParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.FlowControlParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.FlowControlParamsBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}/flowControlParams **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}/flowControlParams **rel**=self

This resource.

POST

Update this [weblogic.j2ee.descriptor.wl.FlowControlParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.FlowControlParamsBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}/loadBalancingParams

This resource manages a [weblogic.j2ee.descriptor.wl.LoadBalancingParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.LoadBalancingParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.LoadBalancingParamsBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMS SystemResources/{name}/JMSResource/connectionFactories/{name}/loadBalancingParams](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMS SystemResources/{name}/JMSResource/connectionFactories/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMS SystemResources/{name}/JMSResource/connectionFactories/{name}/loadBalancingParams](#) **rel**=self
This resource.

POST

Update this [weblogic.j2ee.descriptor.wl.LoadBalancingParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.LoadBalancingParamsBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}/securityParams

This resource manages a [weblogic.j2ee.descriptor.wl.SecurityParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.SecurityParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.SecurityParamsBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}/securityParams **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}/securityParams **rel**=self

This resource.

POST

Update this [weblogic.j2ee.descriptor.wl.SecurityParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.SecurityParamsBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}/transactionParams

This resource manages a [weblogic.j2ee.descriptor.wl.TransactionParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.TransactionParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.TransactionParamsBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}/transactionParams](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories/{name}/transactionParams](#) **rel**=self

This resource.

POST

Update this [weblogic.j2ee.descriptor.wl.TransactionParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.TransactionParamsBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/connectionFactoryCreateForm

This resource manages the create forms for the connectionFactories collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.j2ee.descriptor.wl.JMSConnectionFactoryBean](#) entity populated with default values that can be customized then posted (using the POST method) to the connectionFactories collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.JMSConnectionFactoryBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/connectionFactoryCreateForm](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/connectionFactories](#) **rel=create**
The collection resource for this create form resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/connectionFactoryCreateForm](#) **rel=self**
This resource.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/destinationKeyCreateForm

This resource manages the create forms for the destinationKeys collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.j2ee.descriptor.wl.DestinationKeyBean](#) entity populated with default values that can be customized then posted (using the POST method) to the destinationKeys collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.DestinationKeyBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/destinationKeyCreateForm](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/destinationKeys](#) **rel=create**
The collection resource for this create form resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/destinationKeyCreateForm](#) **rel=self**
This resource.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/destinationKeys

This resource manages a collection of [weblogic.j2ee.descriptor.wl.DestinationKeyBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.j2ee.descriptor.wl.DestinationKeyBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.j2ee.descriptor.wl.DestinationKeyBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/destinationKeys](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/destinationKeyCreateForm](#)
rel=create-form
The create form resource for this collection resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/destinationKeys](#) **rel**=self
This resource.

POST

POST

Add a new [weblogic.j2ee.descriptor.wl.DestinationKeyBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.DestinationKeyBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/destinationKeys/{name}

This resource manages a [weblogic.j2ee.descriptor.wl.DestinationKeyBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.j2ee.descriptor.wl.DestinationKeyBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.j2ee.descriptor.wl.DestinationKeyBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.DestinationKeyBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/destinationKeys/{name}](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/destinationKeys](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/destinationKeys/{name}](#) **rel=self**
This resource.

POST

Update this [weblogic.j2ee.descriptor.wl.DestinationKeyBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.DestinationKeyBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/foreignServerCreateForm

This resource manages the create forms for the foreignServers collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.j2ee.descriptor.wl.ForeignServerBean](#) entity populated with default values that can be customized then posted (using the POST method) to the `foreignServers` collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.ForeignServerBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/foreignServerCreateForm](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/foreignServers](#) **rel=create**
The collection resource for this create form resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/foreignServerCreateForm](#) **rel=self**
This resource.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/foreignServers

This resource manages a collection of [weblogic.j2ee.descriptor.wl.ForeignServerBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.j2ee.descriptor.wl.ForeignServerBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.j2ee.descriptor.wl.ForeignServerBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/foreignServers](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/foreignServerCreateForm](#)
rel=create-form

The create form resource for this collection resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/foreignServers](#) **rel**=self

This resource.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/foreign-

POST

Add a new [weblogic.j2ee.descriptor.wl.ForeignServerBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.ForeignServerBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}

This resource manages a [weblogic.j2ee.descriptor.wl.ForeignServerBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.j2ee.descriptor.wl.ForeignServerBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.j2ee.descriptor.wl.ForeignServerBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.ForeignServerBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/JNDIProperties](#)
[rel=JNDIProperties](#)
This resource's JNDIProperties collection resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/JNDIPropertyCreateForm](#) [rel=JNDIPropertyCreateForm](#)
The create form resource for this resource's JNDIProperties collection resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}](#) [rel=canonical](#)
This resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignConnectionFactories](#) [rel=foreignConnectionFactories](#)
This resource's foreignConnectionFactories collection resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignConnectionFactoryCreateForm](#) [rel=foreignConnectionFactoryCreateForm](#)
The create form resource for this resource's foreignConnectionFactories collection resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignDestinationCreateForm](#) [rel=foreignDestinationCreateForm](#)
The create form resource for this resource's foreignDestinations collection resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignDestinations](#) [rel=foreignDestinations](#)
This resource's foreignDestinations collection resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/foreignServers](#) [rel=parent](#)
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}](#) [rel=self](#)

This resource.

POST

Update this [weblogic.j2ee.descriptor.wl.ForeignServerBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.ForeignServerBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignConnectionFactories

This resource manages a collection of [weblogic.j2ee.descriptor.wl.ForeignConnectionFactoryBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.j2ee.descriptor.wl.ForeignConnectionFactoryBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.j2ee.descriptor.wl.ForeignConnectionFactoryBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignConnectionsFactories](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignConnectionFactoryCreateForm](#) **rel**=create-form

The create form resource for this collection resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignConnectionsFactories](#) **rel**=self

This resource.

POST

Add a new [weblogic.j2ee.descriptor.wl.ForeignConnectionFactoryBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.ForeignConnectionFactoryBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignConnectionFactoryFactories/{name}

This resource manages a [weblogic.j2ee.descriptor.wl.ForeignConnectionFactoryBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.j2ee.descriptor.wl.ForeignConnectionFactoryBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.j2ee.descriptor.wl.ForeignConnectionFactoryBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.ForeignConnectionFactoryBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignConnectionsFactories/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignConnectionsFactories](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignConnectionsFactories/{name}](#) **rel**=self

This resource.

POST

Update this [weblogic.j2ee.descriptor.wl.ForeignConnectionFactoryBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.ForeignConnectionFactoryBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignConnectionFactoryCreateForm

This resource manages the create forms for the foreignConnectionFactories collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.j2ee.descriptor.wl.ForeignConnectionFactoryBean](#) entity populated with default values that can be customized then posted (using the POST method) to the [foreignConnectionFactories](#) collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.ForeignConnectionFactoryBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignConnectionFactoryCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignConnectionFactories](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignConnectionFactoryCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignDestinationCreateForm

This resource manages the create forms for the foreignDestinations collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.j2ee.descriptor.wl.ForeignDestinationBean](#) entity populated with default values that can be customized then posted (using the POST method) to the foreignDestinations collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.ForeignDestinationBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignDestinations/createForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignDestinations](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignDestinations/createForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignDestinations

This resource manages a collection of [weblogic.j2ee.descriptor.wl.ForeignDestinationBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.j2ee.descriptor.wl.ForeignDestinationBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.j2ee.descriptor.wl.ForeignDestinationBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignDestinations **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignDestinations/createForm **rel**=create-form

The create form resource for this collection resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignDestinations **rel**=self

This resource.

POST

Add a new [weblogic.j2ee.descriptor.wl.ForeignDestinationBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.ForeignDestinationBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignDestinations/{name}

This resource manages a [weblogic.j2ee.descriptor.wl.ForeignDestinationBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

DELETE

Delete this [weblogic.j2ee.descriptor.wl.ForeignDestinationBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.j2ee.descriptor.wl.ForeignDestinationBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.ForeignDestinationBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignDestinations/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignDestinations **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/foreignDestinations/{name} **rel**=self

This resource.

POST

Update this [weblogic.j2ee.descriptor.wl.ForeignDestinationBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.ForeignDestinationBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/JNDIProperties

This resource manages a collection of [weblogic.j2ee.descriptor.wl.PropertyBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.j2ee.descriptor.wl.PropertyBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.j2ee.descriptor.wl.PropertyBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/JNDIProperties](#)
rel=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/JNDIPropertyCreateForm](#) **rel**=create-form

The create form resource for this collection resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/JNDIProperties](#)
rel=self

This resource.

POST

Add a new [weblogic.j2ee.descriptor.wl.PropertyBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.PropertyBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/JNDIProperties/{key}

This resource manages a [weblogic.j2ee.descriptor.wl.PropertyBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.j2ee.descriptor.wl.PropertyBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.j2ee.descriptor.wl.PropertyBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.PropertyBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/JNDIProperties/{key}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/JNDIProperties](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/JNDIProperties/{key}](#) **rel**=self

This resource.

POST

Update this [weblogic.j2ee.descriptor.wl.PropertyBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.PropertyBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/JNDIPropertyCreateForm

This resource manages the create forms for the JNDIProperties collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.j2ee.descriptor.wl.PropertyBean](#) entity populated with default values that can be customized then posted (using the POST method) to the JNDIProperties collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.PropertyBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/JNDIPropertyCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/JNDIProperties](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/foreignServers/{name}/JNDIPropertyCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/queueCreateForm

This resource manages the create forms for the queues collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.j2ee.descriptor.wl.QueueBean](#) entity populated with default values that can be customized then posted (using the POST method) to the queues collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.QueueBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/queuecreateForm](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/queues](#) **rel=create**
The collection resource for this create form resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/queuecreateForm](#) **rel=self**
This resource.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/queues

This resource manages a collection of [weblogic.j2ee.descriptor.wl.QueueBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.j2ee.descriptor.wl.QueueBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.j2ee.descriptor.wl.QueueBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/queues](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/queueCreateForm](#) **rel=create-form**
The create form resource for this collection resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/queues](#) **rel=self**
This resource.

POST

Add a new [weblogic.j2ee.descriptor.wl.QueueBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.QueueBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/queues/{name}

This resource manages a [weblogic.j2ee.descriptor.wl.QueueBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

DELETE

Delete this [weblogic.j2ee.descriptor.wl.QueueBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.j2ee.descriptor.wl.QueueBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.QueueBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/queues/{name}](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/queues/{name}/deliveryFailureParams](#) **rel=deliveryFailureParams**
This resource's deliveryFailureParams singleton resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/queues/{name}/deliveryParamsOverrides](#) **rel=deliveryParamsOverrides**
This resource's deliveryParamsOverrides singleton resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/queues/{name}/messageLoggingParams](#) **rel=messageLoggingParams**
This resource's messageLoggingParams singleton resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/queues](#) **rel=parent**
The parent resource of this resource.
- **rel=quota**
This resource's quota reference to a [weblogic.j2ee.descriptor.wl.QuotaBean](#) resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/queues/{name}](#) **rel=self**
This resource.
- **rel=template**
This resource's template reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/queues/{name}/thresholds](#) **rel=thresholds**
This resource's thresholds singleton resource.

POST

Update this [weblogic.j2ee.descriptor.wl.QueueBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.QueueBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/queues/{name}/deliveryFailureParams

This resource manages a [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/queues/{name}/deliveryFailureParams/findSubDeploymentName **rel**=action **title**=findSubDeploymentName
This resource's findSubDeploymentName action resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/queues/{name}/deliveryFailureParams **rel**=canonical
This resource.
- **rel**=errorDestination
This resource's errorDestination reference to a [weblogic.j2ee.descriptor.wl.DestinationBean](#) resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/queues/{name} **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/queues/{name}/deliveryFailureParams **rel**=self
This resource.
- **rel**=templateBean
This resource's templateBean reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/queues/{n

POST

Update this [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/queues/{name}/deliveryFailureParams/findSubDeploymentName

The resource supports the following methods:

- [POST](#)

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/queues/{n

POST

This is used to find the sub-deployment-name for this destination.

Roles

Admin, Deployer

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/queues/{name}/deliveryParamsOverrides

This resource manages a [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/queues/{name}/deliveryParamsOverrides](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/queues/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/queues/{name}/deliveryParamsOverrides](#) **rel=self**
This resource.
- **rel=templateBean**
This resource's `templateBean` reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/queues/{name}/messageLoggingParams

This resource manages a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMS SystemResources/{name}/JMSResource/queues/{name}/messageLoggingParams](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMS SystemResources/{name}/JMSResource/queues/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMS SystemResources/{name}/JMSResource/queues/{name}/messageLoggingParams](#)
rel=self
This resource.
- **rel**=templateBean
This resource's templateBean reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/queues/{n

POST

Update this [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/queues/{name}/thresholds

This resource manages a [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/queues/{name}/thresholds](#)
rel=canonical
This resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/queues/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/queues/{name}/thresholds](#) **rel=self**
This resource.
- **rel=templateBean**
This resource's `templateBean` reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/quotaCreateForm

This resource manages the create forms for the quotas collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.j2ee.descriptor.wl.QuotaBean](#) entity populated with default values that can be customized then posted (using the POST method) to the quotas collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.QuotaBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/quotaCreateForm rel=canonical](#)
This resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/quotas rel=create](#)
The collection resource for this create form resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource rel=parent](#)
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/quotaCreateForm rel=self](#)
This resource.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/quotas

This resource manages a collection of [weblogic.j2ee.descriptor.wl.QuotaBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.j2ee.descriptor.wl.QuotaBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.j2ee.descriptor.wl.QuotaBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/quotas](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/quotaCreateForm](#) **rel=create-form**

The create form resource for this collection resource.

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/quotas](#) **rel=self**

This resource.

POST

Add a new [weblogic.j2ee.descriptor.wl.QuotaBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.QuotaBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/quotas/{name}

This resource manages a [weblogic.j2ee.descriptor.wl.QuotaBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.j2ee.descriptor.wl.QuotaBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.j2ee.descriptor.wl.QuotaBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.QuotaBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/quotas/{name}](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/quotas](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/quotas/{name}](#) **rel**=self
This resource.

POST

Update this [weblogic.j2ee.descriptor.wl.QuotaBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.QuotaBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/SAFEErrorHandlingCreateForm

This resource manages the create forms for the SAFEErrorHandlings collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.j2ee.descriptor.wl.SAFErrorHandlingBean](#) entity populated with default values that can be customized then posted (using the POST method) to the SAFErrorHandlings collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.SAFErrorHandlingBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/SAFErrorHandlingCreateForm](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/SAFErrorHandlings](#) **rel=create**
The collection resource for this create form resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/SAFErrorHandlingCreateForm](#) **rel=self**
This resource.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/SAFEErrorHandlings

This resource manages a collection of [weblogic.j2ee.descriptor.wl.SAFEErrorHandlingBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.j2ee.descriptor.wl.SAFErrorHandlingBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.j2ee.descriptor.wl.SAFErrorHandlingBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/SAFErrorHandlings](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/SAFErrorHandlingCreateForm](#) **rel**=create-form
The create form resource for this collection resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/SAFErrorHandlings](#) **rel**=self
This resource.

POST

Add a new [weblogic.j2ee.descriptor.wl.SAFErrorHandlingBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.SAFErrorHandlingBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/SAFErrorHandlings/{name}

This resource manages a [weblogic.j2ee.descriptor.wl.SAFErrorHandlingBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

DELETE

Delete this [weblogic.j2ee.descriptor.wl.SAErrorHandlingBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.j2ee.descriptor.wl.SAFErrorHandlingBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.SAFErrorHandlingBean](#) entity.

This method can return the following links:

- **rel=SAFErrorDestination**
This resource's SAFErrorDestination reference to a [weblogic.j2ee.descriptor.wl.SAFDestinationBean](#) resource.
- **uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/SAFErrorHandlings/{name}**
rel=canonical
This resource.
- **uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/SAFErrorHandlings** **rel=parent**
The parent resource of this resource.
- **uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/SAFErrorHandlings/{name}** **rel=self**
This resource.

POST

Update this [weblogic.j2ee.descriptor.wl.SAFErrorHandlingBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.SAFErrorHandlingBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinationCreateForm

This resource manages the create forms for the SAFImportedDestinations collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.j2ee.descriptor.wl.SAFImportedDestinationsBean](#) entity populated with default values that can be customized then posted (using the POST method) to the SAFImportedDestinations collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.SAFImportedDestinationsBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMS SystemResources/{name}/JMSResource/SAFImportedDestinationCreateForm](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMS SystemResources/{name}/JMSResource/SAFImportedDestinations](#) **rel**=create
The collection resource for this create form resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMS SystemResources/{name}/JMSResource](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMS SystemResources/{name}/JMSResource/SAFImportedDestinationCreateForm](#)
rel=self
This resource.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations

This resource manages a collection of [weblogic.j2ee.descriptor.wl.SAFImportedDestinationsBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.j2ee.descriptor.wl.SAFImportedDestinationsBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.j2ee.descriptor.wl.SAFImportedDestinationsBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinationCreateForm](#) **rel**=create-form
The create form resource for this collection resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations](#) **rel**=self
This resource.

POST

Add a new [weblogic.j2ee.descriptor.wl.SAFImportedDestinationsBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.SAFImportedDestinationsBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}

This resource manages a [weblogic.j2ee.descriptor.wl.SAFImportedDestinationsBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.j2ee.descriptor.wl.SAFImportedDestinationsBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.j2ee.descriptor.wl.SAFImportedDestinationsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.SAFImportedDestinationsBean](#) entity.

This method can return the following links:

- **rel=SAFErrorHandling**
This resource's SAFErrorHandling reference to a [weblogic.j2ee.descriptor.wl.SAFErrorHandlingBean](#) resource.
- **uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMS SystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAF QueueCreateForm rel=SAFQueueCreateForm**
The create form resource for this resource's SAFQueues collection resource.
- **uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMS SystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAF Queues rel=SAFQueues**
This resource's SAFQueues collection resource.
- **rel=SAFRemoteContext**
This resource's SAFRemoteContext reference to a [weblogic.j2ee.descriptor.wl.SAFRemoteContextBean](#) resource.
- **uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMS SystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAF TopicCreateForm rel=SAFTopicCreateForm**
The create form resource for this resource's SAFTopics collection resource.
- **uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMS SystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAF Topics rel=SAFTopics**
This resource's SAFTopics collection resource.
- **uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMS SystemResources/{name}/JMSResource/SAFImportedDestinations/{name} rel=canonical**
This resource.
- **uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMS SystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/messageLoggingParams rel=messageLoggingParams**
This resource's messageLoggingParams singleton resource.
- **uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMS SystemResources/{name}/JMSResource/SAFImportedDestinations rel=parent**
The parent resource of this resource.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/SAFImpor

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}
rel=self

This resource.

POST

POST

Update this [weblogic.j2ee.descriptor.wl.SAFImportedDestinationsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.SAFImportedDestinationsBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/messageLoggingParams

This resource manages a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/messageLoggingParams](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/messageLoggingParams](#) **rel**=self

This resource.

- **rel**=templateBean

This resource's templateBean reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFQueueCreateForm

This resource manages the create forms for the SAFQueues collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.j2ee.descriptor.wl.SAFQueueBean](#) entity populated with default values that can be customized then posted (using the POST method) to the SAFQueues collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.SAFQueueBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFQueueCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFQueues](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFQueueCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFQueues

This resource manages a collection of [weblogic.j2ee.descriptor.wl.SAFQueueBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.j2ee.descriptor.wl.SAFQueueBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.j2ee.descriptor.wl.SAFQueueBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFQueues **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFQueueCreateForm **rel**=create-form

The create form resource for this collection resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFQueues **rel**=self

This resource.

POST

Add a new [weblogic.j2ee.descriptor.wl.SAFQueueBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.SAFQueueBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFQueues/{name}

This resource manages a [weblogic.j2ee.descriptor.wl.SAFQueueBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.j2ee.descriptor.wl.SAFQueueBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.j2ee.descriptor.wl.SAFQueueBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.SAFQueueBean](#) entity.

This method can return the following links:

- **rel=SAFErrorHandling**
This resource's SAFErrorHandling reference to a [weblogic.j2ee.descriptor.wl.SAFErrorHandlingBean](#) resource.
- **uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFQueues/{name} rel=canonical**
This resource.
- **uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFQueues/{name}/messageLoggingParams rel=messageLoggingParams**
This resource's messageLoggingParams singleton resource.
- **uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFQueues rel=parent**
The parent resource of this resource.
- **uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFQueues/{name} rel=self**
This resource.

POST

Update this [weblogic.j2ee.descriptor.wl.SAFQueueBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.SAFQueueBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFQueues/{name}/messageLoggingParams

This resource manages a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFQueues/{name}/messageLoggingParams](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFQueues/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFQueues/{name}/messageLoggingParams](#) **rel**=self

This resource.

- **rel**=templateBean

This resource's `templateBean` reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFTopicCreateForm

This resource manages the create forms for the SAFTopics collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.j2ee.descriptor.wl.SAFTopicBean](#) entity populated with default values that can be customized then posted (using the POST method) to the SAFTopics collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.SAFTopicBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFTopicCreateForm **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFTopics **rel**=create

The collection resource for this create form resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFTopicCreateForm **rel**=self

This resource.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFTopics

This resource manages a collection of [weblogic.j2ee.descriptor.wl.SAFTopicBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.j2ee.descriptor.wl.SAFTopicBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.j2ee.descriptor.wl.SAFTopicBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFTopics **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFTopicCreateForm **rel**=create-form

The create form resource for this collection resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFTopics **rel**=self

This resource.

POST

Add a new [weblogic.j2ee.descriptor.wl.SAFTopicBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.SAFTopicBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFTopics/{name}

This resource manages a [weblogic.j2ee.descriptor.wl.SAFTopicBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.j2ee.descriptor.wl.SAFTopicBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.j2ee.descriptor.wl.SAFTopicBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.SAFTopicBean](#) entity.

This method can return the following links:

- **rel=SAFErrorHandling**
This resource's SAFErrorHandling reference to a [weblogic.j2ee.descriptor.wl.SAFErrorHandlingBean](#) resource.
- **uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFTopics/{name} rel=canonical**
This resource.
- **uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFTopics/{name}/messageLoggingParams rel=messageLoggingParams**
This resource's messageLoggingParams singleton resource.
- **uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFTopics rel=parent**
The parent resource of this resource.
- **uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFTopics/{name} rel=self**
This resource.

POST

Update this [weblogic.j2ee.descriptor.wl.SAFTopicBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.SAFTopicBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAFTopics/{name}/messageLoggingParams

This resource manages a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMS SystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAF Topics/{name}/messageLoggingParams](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMS SystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAF Topics/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMS SystemResources/{name}/JMSResource/SAFImportedDestinations/{name}/SAF Topics/{name}/messageLoggingParams](#) **rel**=self

This resource.

- **rel**=templateBean

This resource's `templateBean` reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/SAFRemoteContextCreateForm

This resource manages the create forms for the SAFRemoteContexts collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.j2ee.descriptor.wl.SAFRemoteContextBean](#) entity populated with default values that can be customized then posted (using the POST method) to the SAFRemoteContexts collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.SAFRemoteContextBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/SAFRemoteContextCreateForm](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/SAFRemoteContexts](#) **rel=create**
The collection resource for this create form resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/SAFRemoteContextCreateForm](#) **rel=self**
This resource.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/SAFRemoteContexts

This resource manages a collection of [weblogic.j2ee.descriptor.wl.SAFRemoteContextBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.j2ee.descriptor.wl.SAFRemoteContextBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.j2ee.descriptor.wl.SAFRemoteContextBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/SAFRemoteContexts](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/SAFRemoteContextCreateForm](#) **rel=create-form**
The create form resource for this collection resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/SAFRemoteContexts](#) **rel=self**
This resource.

POST

Add a new [weblogic.j2ee.descriptor.wl.SAFRemoteContextBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.SAFRemoteContextBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/SAFRemoteContexts/{name}

This resource manages a [weblogic.j2ee.descriptor.wl.SAFRemoteContextBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

DELETE

Delete this [weblogic.j2ee.descriptor.wl.SAFRemoteContextBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.j2ee.descriptor.wl.SAFRemoteContextBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.SAFRemoteContextBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/SAFRemoteContexts/{name}/SAFLoginContext **rel**=SAFLoginContext
This resource's SAFLoginContext singleton resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/SAFRemoteContexts/{name} **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/SAFRemoteContexts **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/SAFRemoteContexts/{name} **rel**=self
This resource.

POST

Update this [weblogic.j2ee.descriptor.wl.SAFRemoteContextBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.SAFRemoteContextBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/SAFRemoteContexts/{name}/SAFLoginContext

This resource manages a [weblogic.j2ee.descriptor.wl.SAFLoginContextBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.SAFLoginContextBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.SAFLoginContextBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/SAFRemoteContexts/{name}/SAFLoginContext](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/SAFRemoteContexts/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/SAFRemoteContexts/{name}/SAFLoginContext](#) **rel**=self

This resource.

POST

Update this [weblogic.j2ee.descriptor.wl.SAFLoginContextBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.SAFLoginContextBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/templateCreateForm

This resource manages the create forms for the templates collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.j2ee.descriptor.wl.TemplateBean](#) entity populated with default values that can be customized then posted (using the POST method) to the templates collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.TemplateBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/templateCreateForm](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/templates](#) **rel=create**
The collection resource for this create form resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/templateCreateForm](#) **rel=self**
This resource.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/templates

This resource manages a collection of [weblogic.j2ee.descriptor.wl.TemplateBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.j2ee.descriptor.wl.TemplateBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.j2ee.descriptor.wl.TemplateBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/templates](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/templateCreateForm](#) **rel=create-form**
The create form resource for this collection resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/templates](#) **rel=self**
This resource.

POST

Add a new [weblogic.j2ee.descriptor.wl.TemplateBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.TemplateBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}

This resource manages a [weblogic.j2ee.descriptor.wl.TemplateBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

DELETE

Delete this [weblogic.j2ee.descriptor.wl.TemplateBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.j2ee.descriptor.wl.TemplateBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.TemplateBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/findErrorDestination](#) **rel=action** **title=findErrorDestination**
This resource's findErrorDestination action resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/deliveryFailureParams](#) **rel=deliveryFailureParams**
This resource's deliveryFailureParams singleton resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/deliveryParamsOverrides](#) **rel=deliveryParamsOverrides**
This resource's deliveryParamsOverrides singleton resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/groupParamCreateForm](#) **rel=groupParamCreateForm**
The create form resource for this resource's groupParams collection resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/groupParams](#) **rel=groupParams**
This resource's groupParams collection resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/messageLoggingParams](#) **rel=messageLoggingParams**
This resource's messageLoggingParams singleton resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/multicast](#) **rel=multicast**
This resource's multicast singleton resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/templates](#) **rel=parent**

The parent resource of this resource.

- **rel**=quota

This resource's quota reference to a `weblogic.j2ee.descriptor.wl.QuotaBean` resource.

- **uri**=`/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}` **rel**=self

This resource.

- **uri**=`/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/thresholds`
rel=thresholds

This resource's thresholds singleton resource.

- **uri**=`/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/topicSubscriptionParams` **rel**=topicSubscriptionParams

This resource's topicSubscriptionParams singleton resource.

POST

Update this [weblogic.j2ee.descriptor.wl.TemplateBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.TemplateBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/deliveryFailureParams

This resource manages a [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/deliveryFailureParams/findSubDeploymentName **rel**=action **title**=findSubDeploymentName
This resource's findSubDeploymentName action resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/deliveryFailureParams **rel**=canonical
This resource.
- **rel**=errorDestination
This resource's errorDestination reference to a [weblogic.j2ee.descriptor.wl.DestinationBean](#) resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/templates/{name} **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/deliveryFailureParams **rel**=self
This resource.
- **rel**=templateBean
This resource's templateBean reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/deliveryFailureParams/findSubDeploymentName

The resource supports the following methods:

- [POST](#)

POST

This is used to find the sub-deployment-name for this destination.

Roles

Admin, Deployer

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/deliveryParamsOverrides

This resource manages a [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/deliveryParamsOverrides](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/deliveryParamsOverrides](#) **rel**=self

This resource.

- **rel**=templateBean

This resource's templateBean reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/findErrorDestination

The resource supports the following methods:

- [POST](#)

POST

Finds the name of the error destination to use when a destination comes from a specific group

Roles

Admin, Deployer

Request Body

Must contain a JSON object with the following fields:

subDeploymentName

The subDeployment for which to find the quota

Type: string

Response Body

Contains a JSON object with a weblogic.j2ee.descriptor.wl.DestinationBean reference return field.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/groupParamCreateForm

This resource manages the create forms for the groupParams collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.j2ee.descriptor.wl.GroupParamsBean](#) entity populated with default values that can be customized then posted (using the POST method) to the groupParams collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.GroupParamsBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/groupParamCreateForm **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/groupParams **rel**=create

The collection resource for this create form resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/templates/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/groupParamCreateForm **rel**=self

This resource.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/groupParams

This resource manages a collection of [weblogic.j2ee.descriptor.wl.GroupParamsBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.j2ee.descriptor.wl.GroupParamsBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.j2ee.descriptor.wl.GroupParamsBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/groupParams](#)
rel=canonical

This resource.

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/groupParamCreateForm](#)
rel=create-form

The create form resource for this collection resource.

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}](#)
rel=parent

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/groupParams](#)
rel=self

This resource.

POST

Add a new [weblogic.j2ee.descriptor.wl.GroupParamsBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.GroupParamsBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/groupParams/{subDeploymentName}

This resource manages a [weblogic.j2ee.descriptor.wl.GroupParamsBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.j2ee.descriptor.wl.GroupParamsBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.j2ee.descriptor.wl.GroupParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.GroupParamsBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/groupParams/{subDeploymentName} **rel**=canonical
This resource.
- **rel**=errorDestination
This resource's errorDestination reference to a [weblogic.j2ee.descriptor.wl.DestinationBean](#) resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/groupParams **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/groupParams/{subDeploymentName} **rel**=self
This resource.

POST

Update this [weblogic.j2ee.descriptor.wl.GroupParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.GroupParamsBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/messageLoggingParams

This resource manages a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/messageLoggingParams](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/messageLoggingParams](#) **rel**=self

This resource.

- **rel**=templateBean

This resource's templateBean reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/multicast

This resource manages a [weblogic.j2ee.descriptor.wl.MulticastParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.MulticastParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.MulticastParamsBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/multicast](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/multicast](#) **rel**=self
This resource.
- **rel**=templateBean
This resource's templateBean reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.MulticastParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.MulticastParamsBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/thresholds

This resource manages a [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/thresholds](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/thresholds](#) **rel**=self
This resource.
- **rel**=templateBean
This resource's templateBean reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/topicSubscriptionParams

This resource manages a [weblogic.j2ee.descriptor.wl.TopicSubscriptionParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.TopicSubscriptionParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.TopicSubscriptionParamsBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/topicSubscriptionParams **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/templates/{name} **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/templates/{name}/topicSubscriptionParams **rel**=self
This resource.
- **rel**=templateBean
This resource's templateBean reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.TopicSubscriptionParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.TopicSubscriptionParamsBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/topicCreateForm

This resource manages the create forms for the topics collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.j2ee.descriptor.wl.TopicBean](#) entity populated with default values that can be customized then posted (using the POST method) to the topics collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.TopicBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/topicCreateForm](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/topics](#) **rel=create**
The collection resource for this create form resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/topicCreateForm](#) **rel=self**
This resource.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/topics

This resource manages a collection of [weblogic.j2ee.descriptor.wl.TopicBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.j2ee.descriptor.wl.TopicBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.j2ee.descriptor.wl.TopicBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/topics](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/topicCreateForm](#) **rel=create-form**

The create form resource for this collection resource.

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/topics](#) **rel=self**

This resource.

POST

Add a new [weblogic.j2ee.descriptor.wl.TopicBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.TopicBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/topics/{name}

This resource manages a [weblogic.j2ee.descriptor.wl.TopicBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.j2ee.descriptor.wl.TopicBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.j2ee.descriptor.wl.TopicBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.TopicBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMS SystemResources/{name}/JMSResource/topics/{name}](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMS SystemResources/{name}/JMSResource/topics/{name}/deliveryFailureParams](#) **rel**=deliveryFailureParams
This resource's deliveryFailureParams singleton resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMS SystemResources/{name}/JMSResource/topics/{name}/deliveryParamsOverrides](#) **rel**=deliveryParamsOverrides
This resource's deliveryParamsOverrides singleton resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMS SystemResources/{name}/JMSResource/topics/{name}/messageLoggingParams](#) **rel**=messageLoggingParams
This resource's messageLoggingParams singleton resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMS SystemResources/{name}/JMSResource/topics/{name}/multicast](#) **rel**=multicast
This resource's multicast singleton resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMS SystemResources/{name}/JMSResource/topics](#) **rel**=parent
The parent resource of this resource.
- **rel**=quota
This resource's quota reference to a [weblogic.j2ee.descriptor.wl.QuotaBean](#) resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMS SystemResources/{name}/JMSResource/topics/{name}](#) **rel**=self
This resource.
- **rel**=template
This resource's template reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMS SystemResources/{name}/JMSResource/topics/{name}/thresholds](#) **rel**=thresholds

This resource's thresholds singleton resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/topics/{name}/topicSubscriptionParams
rel=topicSubscriptionParams

This resource's topicSubscriptionParams singleton resource.

POST

Update this [weblogic.j2ee.descriptor.wl.TopicBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.TopicBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/topics/{name}/deliveryFailureParams

This resource manages a [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/topics/{name}/deliveryFailureParams/findSubDeploymentName **rel**=action **title**=findSubDeploymentName
This resource's findSubDeploymentName action resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/topics/{name}/deliveryFailureParams **rel**=canonical
This resource.
- **rel**=errorDestination
This resource's errorDestination reference to a [weblogic.j2ee.descriptor.wl.DestinationBean](#) resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/topics/{name} **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/topics/{name}/deliveryFailureParams **rel**=self
This resource.
- **rel**=templateBean
This resource's templateBean reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/topics/{name}/deliveryFailureParams/findSubDeploymentName

The resource supports the following methods:

- [POST](#)

POST

This is used to find the sub-deployment-name for this destination.

Roles

Admin, Deployer

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/topics/{name}/deliveryParamsOverrides

This resource manages a [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/topics/{name}/deliveryParamsOverrides **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/topics/{name} **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/topics/{name}/deliveryParamsOverrides **rel**=self
This resource.
- **rel**=templateBean
This resource's templateBean reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/topics/{name}/messageLoggingParams

This resource manages a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/topics/{name}/messageLoggingParams](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/topics/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/topics/{name}/messageLoggingParams](#)
rel=self
This resource.
- **rel**=templateBean
This resource's templateBean reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/topics/{name}/multicast

This resource manages a [weblogic.j2ee.descriptor.wl.MulticastParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.MulticastParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.MulticastParamsBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/topics/{name}/multicast **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/topics/{name} **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/topics/{name}/multicast **rel**=self
This resource.
- **rel**=templateBean
This resource's templateBean reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.MulticastParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.MulticastParamsBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/topics/{name}/thresholds

This resource manages a [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/topics/{name}/thresholds](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/topics/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/topics/{name}/thresholds](#) **rel=self**
This resource.
- **rel=templateBean**
This resource's `templateBean` reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/topics/{name}/topicSubscriptionParams

This resource manages a [weblogic.j2ee.descriptor.wl.TopicSubscriptionParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.TopicSubscriptionParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.TopicSubscriptionParamsBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/topics/{name}/topicSubscriptionParams](#)
[rel=canonical](#)
This resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/topics/{name}](#) [rel=parent](#)
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/topics/{name}/topicSubscriptionParams](#)
[rel=self](#)
This resource.
- [rel=templateBean](#)
This resource's `templateBean` reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.TopicSubscriptionParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.TopicSubscriptionParamsBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedQueueCreateForm

This resource manages the create forms for the uniformDistributedQueues collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.j2ee.descriptor.wl.UniformDistributedQueueBean](#) entity populated with default values that can be customized then posted (using the POST method) to the `uniformDistributedQueues` collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.UniformDistributedQueueBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedQueueCreateForm](#)
rel=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues](#) **rel**=create

The collection resource for this create form resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedQueueCreateForm](#)
rel=self

This resource.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues

This resource manages a collection of [weblogic.j2ee.descriptor.wl.UniformDistributedQueueBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.j2ee.descriptor.wl.UniformDistributedQueueBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.j2ee.descriptor.wl.UniformDistributedQueueBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues](#)
rel=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedQueueCreateForm](#)
rel=create-form

The create form resource for this collection resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues](#) **rel**=self

This resource.

POST

Add a new [weblogic.j2ee.descriptor.wl.UniformDistributedQueueBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.UniformDistributedQueueBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues/{name}

This resource manages a [weblogic.j2ee.descriptor.wl.UniformDistributedQueueBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.j2ee.descriptor.wl.UniformDistributedQueueBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.j2ee.descriptor.wl.UniformDistributedQueueBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.UniformDistributedQueueBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMS SystemResources/{name}/JMSResource/uniformDistributedQueues/{name}](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMS SystemResources/{name}/JMSResource/uniformDistributedQueues/{name}/deliveryFailureParams](#) **rel**=deliveryFailureParams
This resource's deliveryFailureParams singleton resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMS SystemResources/{name}/JMSResource/uniformDistributedQueues/{name}/deliveryParamsOverrides](#) **rel**=deliveryParamsOverrides
This resource's deliveryParamsOverrides singleton resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMS SystemResources/{name}/JMSResource/uniformDistributedQueues/{name}/messageLoggingParams](#) **rel**=messageLoggingParams
This resource's messageLoggingParams singleton resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMS SystemResources/{name}/JMSResource/uniformDistributedQueues](#) **rel**=parent
The parent resource of this resource.
- **rel**=quota
This resource's quota reference to a [weblogic.j2ee.descriptor.wl.QuotaBean](#) resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMS SystemResources/{name}/JMSResource/uniformDistributedQueues/{name}](#)
rel=self
This resource.
- **rel**=template
This resource's template reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMS SystemResources/{name}/JMSResource/uniformDistributedQueues/{name}/thresholds](#) **rel**=thresholds
This resource's thresholds singleton resource.

POST

Update this [weblogic.j2ee.descriptor.wl.UniformDistributedQueueBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.UniformDistributedQueueBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues/{name}/deliveryFailureParams

This resource manages a [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues/{name}/deliveryFailureParams/findSubDeploymentName **rel**=action
title=findSubDeploymentName
This resource's findSubDeploymentName action resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues/{name}/deliveryFailureParams **rel**=canonical
This resource.
- **rel**=errorDestination
This resource's errorDestination reference to a [weblogic.j2ee.descriptor.wl.DestinationBean](#) resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues/{name} **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues/{name}/deliveryFailureParams **rel**=self
This resource.
- **rel**=templateBean
This resource's templateBean reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues/{name}/deliverFailureParams/findSubDeploymentName

The resource supports the following methods:

- [POST](#)

POST

This is used to find the sub-deployment-name for this destination.

Roles

Admin, Deployer

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues/{name}/deliveryParamsOverrides

This resource manages a [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues/{name}/deliveryParamsOverrides](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues/{name}/deliveryParamsOverrides](#) **rel**=self

This resource.

- **rel**=templateBean

This resource's templateBean reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues/{name}/messageLoggingParams

This resource manages a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues/{name}/messageLoggingParams **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues/{name}/messageLoggingParams **rel**=self

This resource.

- **rel**=templateBean

This resource's templateBean reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues/{name}/thresholds

This resource manages a [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues/{name}/thresholds](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues/{name}](#)
rel=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedQueues/{name}/thresholds](#) **rel**=self
This resource.
- **rel**=templateBean
This resource's templateBean reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopicCreateForm

This resource manages the create forms for the uniformDistributedTopics collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.j2ee.descriptor.wl.UniformDistributedTopicBean](#) entity populated with default values that can be customized then posted (using the POST method) to the `uniformDistributedTopics` collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.UniformDistributedTopicBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopicCreateForm
rel=canonical
This resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics **rel**=create
The collection resource for this create form resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopicCreateForm
rel=self
This resource.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics

This resource manages a collection of [weblogic.j2ee.descriptor.wl.UniformDistributedTopicBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.j2ee.descriptor.wl.UniformDistributedTopicBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.j2ee.descriptor.wl.UniformDistributedTopicBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopicCreateForm](#) **rel=create-form**
The create form resource for this collection resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics](#) **rel=self**
This resource.

POST

Add a new [weblogic.j2ee.descriptor.wl.UniformDistributedTopicBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.UniformDistributedTopicBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}

This resource manages a [weblogic.j2ee.descriptor.wl.UniformDistributedTopicBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.j2ee.descriptor.wl.UniformDistributedTopicBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.j2ee.descriptor.wl.UniformDistributedTopicBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.UniformDistributedTopicBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}
rel=canonical
This resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}/deliveryFailureParams **rel**=deliveryFailureParams
This resource's deliveryFailureParams singleton resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}/deliveryParamsOverrides **rel**=deliveryParamsOverrides
This resource's deliveryParamsOverrides singleton resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}/messageLoggingParams **rel**=messageLoggingParams
This resource's messageLoggingParams singleton resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}/multicast **rel**=multicast
This resource's multicast singleton resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics **rel**=parent
The parent resource of this resource.
- **rel**=quota
This resource's quota reference to a [weblogic.j2ee.descriptor.wl.QuotaBean](#) resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}
rel=self
This resource.
- **rel**=template
This resource's template reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}/thresholds **rel**=thresholds

This resource's thresholds singleton resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}/topicSubscriptionParams **rel**=topicSubscriptionParams

This resource's topicSubscriptionParams singleton resource.

POST

Update this [weblogic.j2ee.descriptor.wl.UniformDistributedTopicBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.UniformDistributedTopicBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}/deliveryFailureParams

This resource manages a [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}/deliveryFailureParams/findSubDeploymentName **rel**=action
title=findSubDeploymentName
This resource's findSubDeploymentName action resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}/deliveryFailureParams **rel**=canonical
This resource.
- **rel**=errorDestination
This resource's errorDestination reference to a [weblogic.j2ee.descriptor.wl.DestinationBean](#) resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name} **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}/deliveryFailureParams **rel**=self
This resource.
- **rel**=templateBean
This resource's templateBean reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}/deliveryFailureParams/findSubDeploymentName

The resource supports the following methods:

- [POST](#)

POST

This is used to find the sub-deployment-name for this destination.

Roles

Admin, Deployer

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}/deliveryParamsOverrides

This resource manages a [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}/deliveryParamsOverrides](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}/deliveryParamsOverrides](#) **rel**=self

This resource.

- **rel**=templateBean

This resource's templateBean reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}/messageLoggingParams

This resource manages a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}/messageLoggingParams **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}/messageLoggingParams **rel**=self

This resource.

- **rel**=templateBean

This resource's templateBean reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}/multicast

This resource manages a [weblogic.j2ee.descriptor.wl.MulticastParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.MulticastParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.MulticastParamsBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}/multicast](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}/multicast](#) **rel**=self

This resource.

- **rel**=templateBean

This resource's templateBean reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.MulticastParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.MulticastParamsBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}/thresholds

This resource manages a [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}/thresholds **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}/thresholds **rel**=self

This resource.

- **rel**=templateBean

This resource's templateBean reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.ThresholdParamsBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}/topicSubscriptionParams

This resource manages a [weblogic.j2ee.descriptor.wl.TopicSubscriptionParamsBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.j2ee.descriptor.wl.TopicSubscriptionParamsBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.j2ee.descriptor.wl.TopicSubscriptionParamsBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}/topicSubscriptionParams](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}](#)
rel=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/JMSResource/uniformDistributedTopics/{name}/topicSubscriptionParams](#) **rel**=self

This resource.

- **rel**=templateBean

This resource's templateBean reference to a [weblogic.j2ee.descriptor.wl.TemplateBean](#) resource.

POST

Update this [weblogic.j2ee.descriptor.wl.TopicSubscriptionParamsBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.j2ee.descriptor.wl.TopicSubscriptionParamsBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/subDeploymentCreateForm

This resource manages the create forms for the subDeployments collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.SubDeploymentMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the subDeployments collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/subDeploymentCreateForm](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/subDeployments](#) **rel=create**
The collection resource for this create form resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/subDeploymentCreateForm](#) **rel=self**
This resource.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/subDeployments

This resource manages a collection of [weblogic.management.configuration.SubDeploymentMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.SubDeploymentMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.SubDeploymentMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/subDeployments](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/subDeploymentCreateForm](#) **rel=create-form**
The create form resource for this collection resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/subDeployments](#) **rel=self**
This resource.

POST

Add a new [weblogic.management.configuration.SubDeploymentMBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/subDeployments/{name}

This resource manages a [weblogic.management.configuration.SubDeploymentMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/subDeployments/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/subDeployments **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/subDeployments/{name} **rel**=self

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/subDeployments/{name}/subDeployments **rel**=subDeployments

This resource's subDeployments collection resource.

POST

Update this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/subDeployments/{name}/subDeployments

This resource manages a collection of [weblogic.management.configuration.SubDeploymentMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.configuration.SubDeploymentMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.SubDeploymentMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMS SystemResources/{name}/subDeployments/{name}/subDeployments](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMS SystemResources/{name}/subDeployments/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMS SystemResources/{name}/subDeployments/{name}/subDeployments](#) **rel**=self
This resource.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/subDeployments/{name}/subDeployments/{name}

This resource manages a [weblogic.management.configuration.SubDeploymentMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMS SystemResources/{name}/subDeployments/{name}/subDeployments/{name}](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMS SystemResources/{name}/subDeployments/{name}/subDeployments](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMS SystemResources/{name}/subDeployments/{name}/subDeployments/{name}](#)
rel=self
This resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMS SystemResources/{name}/subDeployments/{name}/subDeployments/{name}/subDeployments](#) **rel**=subDeployments
This resource's subDeployments collection resource.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/JMSSystemResources/{name}/subDeployments/{name}/

POST

Update this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/libraries

This resource manages a collection of [weblogic.management.configuration.LibraryMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.LibraryMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.LibraryMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/libraries](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/libraries](#) **rel=self**
This resource.

POST

The resource supports the following methods:

- [POST accepting application/json](#)
- [POST accepting multipart/form-data](#)

POST accepting application/json

This resource is used to deploy libraries that are already on the administration server.

This method supports both asynchronous and best effort synchronous invocations. The behavior is controlled by the 'Prefer' header. See [About Synchronous and Asynchronous Operations](#).

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.LibraryMBean](#) entity.

To deploy a library, you must provide the name of the library, the path to the library, and the targets to which the library will be deployed.

Use the multi-part form to deploy a library.

- `sourcePath`: the deployment to upload (required)
- `model`: JSONObject containing a LibraryMBean entity that contains the rest of the deployment information (required)

POST accepting multipart/form-data

Upload a library from the client to the server then deploy it.

This method supports both asynchronous and best effort synchronous invocations. The behavior is controlled by the 'Prefer' header. See [About Synchronous and Asynchronous Operations](#).

Roles

Admin, Deployer

Request Body

Use the multi-part form to upload a library from the client to the server then deploy it.

- `sourcePath`: the deployment to upload (required)
- `model`: JSONObject containing a LibraryMBean entity that contains the rest of the deployment information (required)

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/libraries/{name}

This resource manages a [weblogic.management.configuration.LibraryMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Undeploy a library.

This method supports both asynchronous and best effort synchronous invocations. The behavior is controlled by the 'Prefer' header. See [About Synchronous and Asynchronous Operations](#).

Roles

Admin, Deployer

GET

Get this [weblogic.management.configuration.LibraryMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.LibraryMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/libraries/{name}/createPlan](#) **rel=action** **title=createPlan**
This resource's createPlan action resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/libraries/{name}](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/libraries](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/libraries/{name}/redeploy](#) **rel=redeploy**
This resource's redeploy resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/libraries/{name}](#) **rel=self**
This resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/libraries/{name}/subDeploymentCreateForm](#) **rel=subDeploymentCreateForm**
The create form resource for this resource's subDeployments collection resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/libraries/{name}/subDeployments](#) **rel=subDeployments**
This resource's subDeployments collection resource.

POST

Update this [weblogic.management.configuration.LibraryMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.LibraryMBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/libraries/{name}/createPlan

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

POST

Create a deployment plan in the specified directory.

Roles

Admin, Deployer

Request Body

Must contain a JSON object with the following fields:

planPath

planPath

Type: string

Response Body

Contains a JSON object with a string return field.

POST

Create a deployment plan in a default directory

Roles

Admin, Deployer

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/libraries/{name}/redeploy

The resource supports the following methods:

- [POST](#)

POST

Use the multi-part form to redeploy a library.

- `sourcePath`: the deployment to upload (required)
- `model`: JSONObject containing a LibraryMBean entity that contains the rest of the deployment information (required)

This method supports both asynchronous and best effort synchronous invocations. The behavior is controlled by the 'Prefer' header. See [About Synchronous and Asynchronous Operations](#).

Roles

Admin, Deployer

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/libraries/{name}/subDeploymentCreateForm

This resource manages the create forms for the subDeployments collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.SubDeploymentMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the subDeployments collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/libraries/{name}/subDeploymentCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/libraries/{name}/subDeployments](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/libraries/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/libraries/{name}/subDeploymentCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/libraries/{name}/subDeployments

This resource manages a collection of [weblogic.management.configuration.SubDeploymentMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.SubDeploymentMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.SubDeploymentMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/libraries/{name}/subDeployments](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/libraries/{name}/subDeploymentCreateForm](#) **rel**=create-form

The create form resource for this collection resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/libraries/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/libraries/{name}/subDeployments](#) **rel**=self

This resource.

POST

Add a new [weblogic.management.configuration.SubDeploymentMBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/libraries/{name}/subDeployments/{name}

This resource manages a [weblogic.management.configuration.SubDeploymentMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/libraries/{name}/subDeployments/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/libraries/{name}/subDeployments **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/libraries/{name}/subDeployments/{name} **rel**=self

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/libraries/{name}/subDeployments/{name}/subDeployments **rel**=subDeployments

This resource's subDeployments collection resource.

POST

Update this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/libraries/{name}/subDeployments/{name}/subDeployments

This resource manages a collection of [weblogic.management.configuration.SubDeploymentMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.configuration.SubDeploymentMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.SubDeploymentMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/libraries/{name}/subDeployments/{name}/subDeployments **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/libraries/{name}/subDeployments/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/libraries/{name}/subDeployments/{name}/subDeployments **rel**=self

This resource.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/libraries/{name}/subDeployments/{name}/subDeployments/{name}

This resource manages a [weblogic.management.configuration.SubDeploymentMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/libraries/{name}/subDeployments/{name}/subDeployments/{name}](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/libraries/{name}/subDeployments/{name}/subDeployments](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/libraries/{name}/subDeployments/{name}/subDeployments/{name}](#) **rel=self**
This resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/libraries/{name}/subDeployments/{name}/subDeployments/{name}/subDeployments](#) **rel=subDeployments**
This resource's subDeployments collection resource.

POST

Update this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/mailSessionCreateForm

This resource manages the create forms for the mailSessions collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.MailSessionMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the mailSessions collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.MailSessionMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/mailSessionCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/mailSessions](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/mailSessionCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/mailSessions

This resource manages a collection of [weblogic.management.configuration.MailSessionMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.MailSessionMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.MailSessionMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/mailSessions](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/mailSessionCreateForm](#) **rel**=create-form

The create form resource for this collection resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/mailSessions](#) **rel**=self

This resource.

POST

Add a new [weblogic.management.configuration.MailSessionMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.MailSessionMBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/mailSessions/{name}

This resource manages a [weblogic.management.configuration.MailSessionMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.MailSessionMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.MailSessionMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.MailSessionMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/mailSessions/{name}](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/mailSessions](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/mailSessions/{name}](#) **rel**=self
This resource.

POST

Update this [weblogic.management.configuration.MailSessionMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.MailSessionMBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/managedExecutorServiceCreateForm

This resource manages the create forms for the managedExecutorServices collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.ManagedExecutorServiceMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the `managedExecutorServices` collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ManagedExecutorServiceMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/managedExecutorServiceCreateForm](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/managedExecutorServices](#) **rel**=create
The collection resource for this create form resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/managedExecutorServiceCreateForm](#) **rel**=self
This resource.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/managedExecutorServices

This resource manages a collection of [weblogic.management.configuration.ManagedExecutorServiceMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.ManagedExecutorServiceMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.ManagedExecutorServiceMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/managedExecutorServices **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/managedExecutorServiceCreateForm **rel**=create-form
The create form resource for this collection resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name} **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/managedExecutorServices **rel**=self
This resource.

POST

Add a new [weblogic.management.configuration.ManagedExecutorServiceMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.ManagedExecutorServiceMBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/managedExecutorServices/{name}

This resource manages a [weblogic.management.configuration.ManagedExecutorServiceMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.ManagedExecutorServiceMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.ManagedExecutorServiceMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ManagedExecutorServiceMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/managedExecutorServices/{name}](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/managedExecutorServices](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/managedExecutorServices/{name}](#) **rel=self**
This resource.

POST

Update this [weblogic.management.configuration.ManagedExecutorServiceMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.ManagedExecutorServiceMBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/managedScheduledExecutorServiceCreateForm

This resource manages the create forms for the managedScheduledExecutorServices collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.ManagedScheduledExecutorServiceMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the `managedScheduledExecutorServices` collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ManagedScheduledExecutorServiceMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/managedScheduledExecutorServiceCreateForm](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/managedScheduledExecutorServices](#) **rel**=create

The collection resource for this create form resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}](#)
rel=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/managedScheduledExecutorServiceCreateForm](#) **rel**=self

This resource.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/managedScheduledExecutorServices

This resource manages a collection of [weblogic.management.configuration.ManagedScheduledExecutorServiceMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.ManagedScheduledExecutorServiceMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.ManagedScheduledExecutorServiceMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/managedScheduledExecutorServices](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/managedScheduledExecutorServiceCreateForm](#) **rel**=create-form
The create form resource for this collection resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/managedScheduledExecutorServices](#) **rel**=self
This resource.

POST

Add a new [weblogic.management.configuration.ManagedScheduledExecutorServiceMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.ManagedScheduledExecutorServiceMBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/managedScheduledExecutorServices/{name}

This resource manages a [weblogic.management.configuration.ManagedScheduledExecutorServiceMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this
[weblogic.management.configuration.ManagedScheduledExecutorServiceMBean](#)
instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.ManagedScheduledExecutorServiceMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ManagedScheduledExecutorServiceMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/managedScheduledExecutorServices/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/managedScheduledExecutorServices **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/managedScheduledExecutorServices/{name} **rel**=self

This resource.

POST

Update this [weblogic.management.configuration.ManagedScheduledExecutorServiceMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.ManagedScheduledExecutorServiceMBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/managedThreadFactories

This resource manages a collection of [weblogic.management.configuration.ManagedThreadFactoryMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.ManagedThreadFactoryMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.ManagedThreadFactoryMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/managedThreadFactories](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/managedThreadFactoryCreateForm](#) **rel=create-form**
The create form resource for this collection resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/managedThreadFactories](#) **rel=self**
This resource.

POST

Add a new [weblogic.management.configuration.ManagedThreadFactoryMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.ManagedThreadFactoryMBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/managedThreadFactories/{name}

This resource manages a [weblogic.management.configuration.ManagedThreadFactoryMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.ManagedThreadFactoryMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.ManagedThreadFactoryMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ManagedThreadFactoryMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/managedThreadFactories/{name}](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/managedThreadFactories](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/managedThreadFactories/{name}](#) **rel=self**
This resource.

POST

Update this [weblogic.management.configuration.ManagedThreadFactoryMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.ManagedThreadFactoryMBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/managedThreadFactoryCreateForm

This resource manages the create forms for the managedThreadFactories collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.ManagedThreadFactoryMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the `managedThreadFactories` collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ManagedThreadFactoryMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/managedThreadFactoryCreateForm](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/managedThreadFactories](#) **rel**=create

The collection resource for this create form resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/managedThreadFactoryCreateForm](#) **rel**=self

This resource.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/messagingBridgeCreateForm

This resource manages the create forms for the messagingBridges collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.MessagingBridgeMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the `messagingBridges` collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.MessagingBridgeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/messagingBridgeCreateForm](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/messagingBridges](#) **rel**=create
The collection resource for this create form resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/messagingBridgeCreateForm](#) **rel**=self
This resource.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/messagingBridges

This resource manages a collection of [weblogic.management.configuration.MessagingBridgeMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.MessagingBridgeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.MessagingBridgeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/messagingBridges](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/messagingBridgeCreateForm](#) **rel=create-form**
The create form resource for this collection resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/messagingBridges](#) **rel=self**
This resource.

POST

Add a new [weblogic.management.configuration.MessagingBridgeMBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.MessagingBridgeMBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/messagingBridges/{name}

This resource manages a [weblogic.management.configuration.MessagingBridgeMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.MessagingBridgeMBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.management.configuration.MessagingBridgeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.MessagingBridgeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/messagingBridges/{name}](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/messagingBridges](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/messagingBridges/{name}](#) **rel**=self
This resource.
- **rel**=sourceDestination
This resource's sourceDestination reference to a [weblogic.management.configuration.BridgeDestinationCommonMBean](#) resource.
- **rel**=targetDestination
This resource's targetDestination reference to a [weblogic.management.configuration.BridgeDestinationCommonMBean](#) resource.

POST

Update this [weblogic.management.configuration.MessagingBridgeMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.MessagingBridgeMBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/osgiFrameworkCreateForm

This resource manages the create forms for the osgiFrameworks collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.OsgiFrameworkMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the `osgiFrameworks` collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.OsgiFrameworkMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/osgiFrameworkCreateForm](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/osgiFrameworks](#) **rel=create**
The collection resource for this create form resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/osgiFrameworkCreateForm](#) **rel=self**
This resource.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/osgiFrameworks

This resource manages a collection of [weblogic.management.configuration.OsgiFrameworkMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.OsgiFrameworkMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.OsgiFrameworkMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/osgiFrameworks](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/osgiFrameworkCreateForm](#) **rel=create-form**
The create form resource for this collection resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/osgiFrameworks](#) **rel=self**
This resource.

POST

Add a new [weblogic.management.configuration.OsgiFrameworkMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.OsgiFrameworkMBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/osgiFrameworks/{name}

This resource manages a [weblogic.management.configuration.OsgiFrameworkMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

DELETE

Delete this [weblogic.management.configuration.OsgiFrameworkMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.OsgiFrameworkMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.OsgiFrameworkMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/osgiFrameworks/{name}](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/osgiFrameworks](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/osgiFrameworks/{name}](#) **rel=self**
This resource.

POST

POST

Update this [weblogic.management.configuration.OsgiFrameworkMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.OsgiFrameworkMBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/SAFAgentCreateForm

This resource manages the create forms for the SAFAgents collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.SAFAgentMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the SAFAgents collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SAFAgentMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/SAFAgentCreateForm](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/SAFAgents](#) **rel**=create

The collection resource for this create form resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/SAFAgentCreateForm](#) **rel**=self

This resource.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/SAFAGents

This resource manages a collection of [weblogic.management.configuration.SAFAgentMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.SAFAgentMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.SAFAgentMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/SAFAgents](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/SAFAgentCreateForm](#) **rel**=create-form

The create form resource for this collection resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/SAFAgents](#) **rel**=self

This resource.

POST

Add a new [weblogic.management.configuration.SAFAgentMBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.SAFAgentMBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/SAFAGents/{name}

This resource manages a [weblogic.management.configuration.SAFAgentMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.SAFAgentMBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.management.configuration.SAFAgentMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SAFAgentMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/SAFAgents/{name}/JMSSAFMessageLogFile](#) **rel**=JMSSAFMessageLogFile
This resource's JMSSAFMessageLogFile singleton resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/SAFAgents/{name}](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/SAFAgents](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/SAFAgents/{name}](#) **rel**=self
This resource.
- **rel**=store
This resource's store reference to a [weblogic.management.configuration.PersistentStoreMBean](#) resource.

POST

Update this [weblogic.management.configuration.SAFAgentMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.SAFAgentMBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/SAFAgents/{name}/JMSSAFMessageLogFile

This resource manages a [weblogic.management.configuration.JMSSAFMessageLogFileMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.JMSSAFMessageLogFileMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.JMSSAFMessageLogFileMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/SAFAgents/{name}/JMSSAFMessageLogFile](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/SAFAgents/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/SAFAgents/{name}/JMSSAFMessageLogFile](#) **rel=self**
This resource.

POST

Update this [weblogic.management.configuration.JMSSAFMessageLogFileMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.JMSSAFMessageLogFileMBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResourceCreateForm

This resource manages the create forms for the WLDFSystemResources collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.WLDFSystemResourceMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the [WLDFSystemResources](#) collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.WLDFSystemResourceMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResourceCreateForm](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources](#) **rel**=create

The collection resource for this create form resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResourceCreateForm](#) **rel**=self

This resource.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources

This resource manages a collection of [weblogic.management.configuration.WLDFSystemResourceMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.WLDFSystemResourceMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.WLDFSystemResourceMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResourceCreateForm](#) **rel**=create-form
The create form resource for this collection resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources](#) **rel**=self
This resource.

POST

Add a new [weblogic.management.configuration.WLDFSystemResourceMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.WLDFSystemResourceMBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}

This resource manages a [weblogic.management.configuration.WLDFSystemResourceMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.WLDFSystemResourceMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.WLDFSystemResourceMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.WLDFSystemResourceMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource](#) **rel**=WLDFResource
This resource's WLDFResource singleton resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}](#) **rel**=canonical
This resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources](#) **rel**=parent
The parent resource of this resource.
- **rel**=resource
This resource's resource reference to a [weblogic.descriptor.DescriptorBean](#) resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}](#) **rel**=self
This resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/subDeploymentCreateForm](#) **rel**=subDeploymentCreateForm
The create form resource for this resource's subDeployments collection resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/subDeployments](#) **rel**=subDeployments
This resource's subDeployments collection resource.

POST

Update this [weblogic.management.configuration.WLDFSystemResourceMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.WLDFSystemResourceMBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/subDeploymentCreateForm

This resource manages the create forms for the subDeployments collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.SubDeploymentMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the subDeployments collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/subDeploymentCreateForm](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/subDeployments](#) **rel=create**
The collection resource for this create form resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/subDeploymentCreateForm](#) **rel=self**
This resource.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/subDeployments

This resource manages a collection of [weblogic.management.configuration.SubDeploymentMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.SubDeploymentMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.SubDeploymentMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/subDeployments](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/subDeploymentCreateForm](#) **rel=create-form**
The create form resource for this collection resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/subDeployments](#) **rel=self**
This resource.

POST

Add a new [weblogic.management.configuration.SubDeploymentMBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/subDeployments/{name}

This resource manages a [weblogic.management.configuration.SubDeploymentMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

DELETE

Delete this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDSystemResources/{name}/subDeployments/{name} **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDSystemResources/{name}/subDeployments **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDSystemResources/{name}/subDeployments/{name} **rel**=self
This resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDSystemResources/{name}/subDeployments/{name}/subDeployments **rel**=subDeployments
This resource's subDeployments collection resource.

POST

Update this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/subDeployments/{name}/subDeployments

This resource manages a collection of [weblogic.management.configuration.SubDeploymentMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.configuration.SubDeploymentMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.SubDeploymentMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDSystemResources/{name}/subDeployments/{name}/subDeployments](#)
rel=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDSystemResources/{name}/subDeployments/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDSystemResources/{name}/subDeployments/{name}/subDeployments](#) **rel**=self

This resource.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/subDeployments/{name}/subDeployments/{name}

This resource manages a [weblogic.management.configuration.SubDeploymentMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDSystemResources/{name}/subDeployments/{name}/subDeployments/{name}](#)
rel=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDSystemResources/{name}/subDeployments/{name}/subDeployments](#)
rel=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDSystemResources/{name}/subDeployments/{name}/subDeployments/{name}](#)
rel=self

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDSystemResources/{name}/subDeployments/{name}/subDeployments/{name}/subDeployments](#) **rel**=subDeployments

This resource's subDeployments collection resource.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/subDeployments/{nam

POST

Update this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource

This resource manages a [weblogic.diagnostics.descriptor.WLDFResourceBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.diagnostics.descriptor.WLDFResourceBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFResourceBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/harvester **rel**=harvester
This resource's harvester singleton resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/instrumentation **rel**=instrumentation
This resource's instrumentation singleton resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name} **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource **rel**=self
This resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification **rel**=watchNotification
This resource's watchNotification singleton resource.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/harvester

This resource manages a [weblogic.diagnostics.descriptor.WLDFHarvesterBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.diagnostics.descriptor.WLDFHarvesterBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFHarvesterBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/harvester **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/harvester/harvestedTypeCreateForm **rel**=harvestedTypeCreateForm

The create form resource for this resource's harvestedTypes collection resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/harvester/harvestedTypes **rel**=harvestedTypes

This resource's harvestedTypes collection resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/harvester **rel**=self

This resource.

POST

Update this [weblogic.diagnostics.descriptor.WLDFHarvesterBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFHarvesterBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/harvester/harvestedTypeCreateForm

This resource manages the create forms for the harvestedTypes collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFHarvestedTypeBean](#) entity populated with default values that can be customized then posted (using the POST method) to the harvestedTypes collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFHarvestedTypeBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/harvester/harvestedTypeCreateForm](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/harvester/harvestedTypes](#) **rel**=create

The collection resource for this create form resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/harvester](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/harvester/harvestedTypeCreateForm](#) **rel**=self

This resource.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/harvester/harvestedTypes

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFHarvestedTypeBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFHarvestedTypeBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFHarvestedTypeBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/harvester/harvestedTypes](#)
rel=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/harvester/harvestedTypeCreateForm](#) **rel**=create-form

The create form resource for this collection resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/harvester](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/harvester/harvestedTypes](#) **rel**=self

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFHarvestedTypeBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFHarvestedTypeBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/harvester/harvestedTypes/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFHarvestedTypeBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFHarvestedTypeBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.diagnostics.descriptor.WLDFHarvestedTypeBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFHarvestedTypeBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/harvester/harvestedTypes/{name}
rel=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/harvester/harvestedTypes
rel=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/harvester/harvestedTypes/{name}
rel=self

This resource.

POST

Update this [weblogic.diagnostics.descriptor.WLDFHarvestedTypeBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFHarvestedTypeBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/instrumentation

This resource manages a [weblogic.diagnostics.descriptor.WLDFInstrumentationBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.diagnostics.descriptor.WLDFInstrumentationBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFInstrumentationBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/instrumentation/WLDFInstrumentationMonitorCreateForm](#) **rel**=WLDFInstrumentationMonitorCreateForm

The create form resource for this resource's WLDFInstrumentationMonitors collection resource.

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/instrumentation/WLDFInstrumentationMonitors](#) **rel**=WLDFInstrumentationMonitors

This resource's WLDFInstrumentationMonitors collection resource.

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/instrumentation](#) **rel**=canonical

This resource.

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource](#) **rel**=parent

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/instrumentation](#) **rel**=self

This resource.

POST

Update this [weblogic.diagnostics.descriptor.WLDFInstrumentationBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFInstrumentationBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/instrumentation/WLDFInstrumentationMonitorCreateForm

This resource manages the create forms for the WLDFInstrumentationMonitors collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFInstrumentationMonitorBean](#) entity populated with default values that can be customized then posted (using the POST method) to the [WLDFInstrumentationMonitors](#) collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFInstrumentationMonitorBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/instrumentation/WLDFInstrumentationMonitorCreateForm](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/instrumentation/WLDFInstrumentationMonitors](#) **rel**=create

The collection resource for this create form resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/instrumentation](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/instrumentation/WLDFInstrumentationMonitorCreateForm](#) **rel**=self

This resource.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/instrumentation/WLDFInstrumentationMonitors

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFInstrumentationMonitorBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFInstrumentationMonitorBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFInstrumentationMonitorBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/instrumentation/WLDFInstrumentationMonitors](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/instrumentation/WLDFInstrumentationMonitorCreateForm](#) **rel**=create-form

The create form resource for this collection resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/instrumentation](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/instrumentation/WLDFInstrumentationMonitors](#) **rel**=self

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFInstrumentationMonitorBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFInstrumentationMonitorBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/instrumentation/WLDFInstrumentationMonitors/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFInstrumentationMonitorBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFInstrumentationMonitorBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.diagnostics.descriptor.WLDFInstrumentationMonitorBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFInstrumentationMonitorBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/instrumentation/WLDFInstrumentationMonitors/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/instrumentation/WLDFInstrumentationMonitors](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/instrumentation/WLDFInstrumentationMonitors/{name}](#) **rel**=self

This resource.

POST

Update this [weblogic.diagnostics.descriptor.WLDFInstrumentationMonitorBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFInstrumentationMonitorBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification

This resource manages a [weblogic.diagnostics.descriptor.WLDFWatchNotificationBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.diagnostics.descriptor.WLDFWatchNotificationBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFWatchNotificationBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMSNotificationCreateForm](#) **rel**=JMSNotificationCreateForm

The create form resource for this resource's JMSNotifications collection resource.

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMSNotifications](#) **rel**=JMSNotifications

This resource's JMSNotifications collection resource.

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMXNotificationCreateForm](#) **rel**=JMXNotificationCreateForm

The create form resource for this resource's JMXNotifications collection resource.

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMXNotifications](#) **rel**=JMXNotifications

This resource's JMXNotifications collection resource.

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/RESTNotificationCreateForm](#) **rel**=RESTNotificationCreateForm

The create form resource for this resource's RESTNotifications collection resource.

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/RESTNotifications](#) **rel**=RESTNotifications

This resource's RESTNotifications collection resource.

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/SMTPNotificationCreateForm](#) **rel**=SMTPNotificationCreateForm

The create form resource for this resource's SMTPNotifications collection resource.

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/SMTPNotifications](#) **rel**=SMTPNotifications

This resource's SMTPNotifications collection resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDSystemResources/{name}/WLDResource/watchNotification/SNMPNotificationCreateForm **rel**=SNMPNotificationCreateForm
The create form resource for this resource's SNMPNotifications collection resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDSystemResources/{name}/WLDResource/watchNotification/SNMPNotifications **rel**=SNMPNotifications
This resource's SNMPNotifications collection resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDSystemResources/{name}/WLDResource/watchNotification/lookupActions **rel**=action **title**=lookupActions
This resource's lookupActions action resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDSystemResources/{name}/WLDResource/watchNotification/lookupNotification **rel**=action **title**=lookupNotification
This resource's lookupNotification action resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDSystemResources/{name}/WLDResource/watchNotification/actionCreateForm **rel**=actionCreateForm
The create form resource for this resource's actions collection resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDSystemResources/{name}/WLDResource/watchNotification/actions **rel**=actions
This resource's actions collection resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDSystemResources/{name}/WLDResource/watchNotification **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDSystemResources/{name}/WLDResource/watchNotification/heapDumpActionCreateForm **rel**=heapDumpActionCreateForm
The create form resource for this resource's heapDumpActions collection resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDSystemResources/{name}/WLDResource/watchNotification/heapDumpActions **rel**=heapDumpActions
This resource's heapDumpActions collection resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDSystemResources/{name}/WLDResource/watchNotification/imageNotificationCreateForm **rel**=imageNotificationCreateForm
The create form resource for this resource's imageNotifications collection resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDSystemResources/{name}/WLDResource/watchNotification/imageNotifications **rel**=imageNotifications
This resource's imageNotifications collection resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/logActionCreateForm **rel**=logActionCreateForm
The create form resource for this resource's logActions collection resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/logActions **rel**=logActions
This resource's logActions collection resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleDownActionCreateForm **rel**=scaleDownActionCreateForm
The create form resource for this resource's scaleDownActions collection resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleDownActions **rel**=scaleDownActions
This resource's scaleDownActions collection resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleUpActionCreateForm **rel**=scaleUpActionCreateForm
The create form resource for this resource's scaleUpActions collection resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleUpActions **rel**=scaleUpActions
This resource's scaleUpActions collection resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scriptActionCreateForm **rel**=scriptActionCreateForm
The create form resource for this resource's scriptActions collection resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scriptActions **rel**=scriptActions
This resource's scriptActions collection resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification **rel**=self
This resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/threadDumpActionCreateForm **rel**=threadDumpActionCreateForm
The create form resource for this resource's threadDumpActions collection resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDSystemResources/{name}/WLDResource/watchNotification/threadDumpActions **rel**=threadDumpActions

This resource's threadDumpActions collection resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDSystemResources/{name}/WLDResource/watchNotification/watchCreateForm **rel**=watchCreateForm

The create form resource for this resource's watches collection resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDSystemResources/{name}/WLDResource/watchNotification/watches **rel**=watches

This resource's watches collection resource.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watch-

POST

Update this [weblogic.diagnostics.descriptor.WLDFWatchNotificationBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFWatchNotificationBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actionCreateForm

This resource manages the create forms for the actions collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFActionBean](#) entity populated with default values that can be customized then posted (using the POST method) to the actions collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFActionBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actionCreateForm rel=canonical](#)

This resource.

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions rel=create](#)

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification rel=parent](#)

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actionCreateForm rel=self](#)

This resource.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFActionBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFActionBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFActionBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions
rel=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actionCreateForm
rel=create-form

The create form resource for this collection resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification
rel=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions
rel=self

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFActionBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFActionBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFActionBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFActionBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.diagnostics.descriptor.WLDFActionBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFActionBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/arrayProperties](#) **rel=arrayProperties**

This resource's arrayProperties collection resource.

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/arrayPropertyCreateForm](#) **rel=arrayPropertyCreateForm**

The create form resource for this resource's arrayProperties collection resource.

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/configurationProperties](#) **rel=configurationProperties**

This resource's configurationProperties collection resource.

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/encryptedProperties](#) **rel=encryptedProperties**

This resource's encryptedProperties collection resource.

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/encryptedPropertyCreateForm](#) **rel=encryptedPropertyCreateForm**

The create form resource for this resource's encryptedProperties collection resource.

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties](#) **rel=mapProperties**

This resource's mapProperties collection resource.

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapPropertyCreateForm](#) **rel=mapPropertyCreateForm**

The create form resource for this resource's mapProperties collection resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions
rel=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/properties **rel**=properties
This resource's properties collection resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/propertyCreateForm **rel**=propertyCreateForm
The create form resource for this resource's properties collection resource.
- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}
rel=self
This resource.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watch

POST

Update this [weblogic.diagnostics.descriptor.WLDFActionBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFActionBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/arrayProperties

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFArrayPropertyBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFArrayPropertyBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFArrayPropertyBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/arrayProperties **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/arrayPropertyCreateForm **rel**=create-form

The create form resource for this collection resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/arrayProperties **rel**=self

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFArrayPropertyBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFArrayPropertyBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/arrayProperties/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFArrayPropertyBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFArrayPropertyBean](#) instance.

Roles

Admin

GET

Get this [weblogic.diagnostics.descriptor.WLDFArrayPropertyBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFArrayPropertyBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/arrayProperties/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/arrayProperties **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/arrayProperties/{name} **rel**=self

This resource.

POST

Update this [weblogic.diagnostics.descriptor.WLDFArrayPropertyBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFArrayPropertyBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/arrayPropertyCreateForm

This resource manages the create forms for the arrayProperties collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFArrayPropertyBean](#) entity populated with default values that can be customized then posted (using the POST method) to the arrayProperties collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFArrayPropertyBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/arrayPropertyCreateForm **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/arrayProperties **rel**=create

The collection resource for this create form resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/arrayPropertyCreateForm **rel**=self

This resource.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/configurationProperties

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFConfigurationPropertyBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFConfigurationPropertyBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFConfigurationPropertyBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/configurationProperties](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/configurationProperties](#) **rel**=self

This resource.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/configurationProperties/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFConfigurationPropertyBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.diagnostics.descriptor.WLDFConfigurationPropertyBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFConfigurationPropertyBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/configurationProperties/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/configurationProperties](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/configurationProperties/{name}](#) **rel**=self

This resource.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/encryptedProperties

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/encryptedProperties](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/encryptedPropertyCreateForm](#) **rel**=create-form

The create form resource for this collection resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/encryptedProperties](#) **rel**=self

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/encryptedProperties/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) instance.

Roles

Admin

GET

Get this [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/encryptedProperties/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/encryptedProperties](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/encryptedProperties/{name}](#) **rel**=self

This resource.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watch

POST

Update this [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/encryptedPropertyCreateForm

This resource manages the create forms for the encryptedProperties collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) entity populated with default values that can be customized then posted (using the POST method) to the encryptedProperties collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/encryptedPropertyCreateForm **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/encryptedProperties **rel**=create

The collection resource for this create form resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/encryptedPropertyCreateForm **rel**=self

This resource.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFConfigurationPropertiesBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFConfigurationPropertiesBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFConfigurationPropertiesBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapPropertyCreateForm **rel**=create-form

The create form resource for this collection resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties **rel**=self

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFConfigurationPropertiesBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFConfigurationPropertiesBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFConfigurationPropertiesBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFConfigurationPropertiesBean](#) instance.

Roles

Admin

GET

Get this [weblogic.diagnostics.descriptor.WLDFConfigurationPropertiesBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFConfigurationPropertiesBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/configurationProperties **rel**=configurationProperties

This resource's configurationProperties collection resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/encryptedProperties **rel**=encryptedProperties

This resource's encryptedProperties collection resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/encryptedPropertyCreateForm **rel**=encryptedPropertyCreateForm

The create form resource for this resource's encryptedProperties collection resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/properties **rel**=properties

This resource's properties collection resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/propertyCreateForm **rel**=propertyCreateForm

The create form resource for this resource's properties collection resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name} **rel**=self

This resource.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/configurationProperties

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFConfigurationPropertyBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFConfigurationPropertyBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFConfigurationPropertyBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/configurationProperties **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/configurationProperties **rel**=self

This resource.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/configurationProperties/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFConfigurationPropertyBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.diagnostics.descriptor.WLDFConfigurationPropertyBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFConfigurationPropertyBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/configurationProperties/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/configurationProperties **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/configurationProperties/{name} **rel**=self

This resource.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/encryptedProperties

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/encryptedProperties **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/encryptedPropertyCreateForm **rel**=create-form

The create form resource for this collection resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/encryptedProperties **rel**=self

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/encryptedProperties/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/encryptedProperties/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/encryptedProperties **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/encryptedProperties/{name} **rel**=self

This resource.

POST

POST

Update this [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/encryptedPropertyCreateForm

This resource manages the create forms for the encryptedProperties collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) entity populated with default values that can be customized then posted (using the POST method) to the encryptedProperties collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/encryptedPropertyCreateForm **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/encryptedProperties **rel**=create

The collection resource for this create form resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/encryptedPropertyCreateForm **rel**=self

This resource.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/properties

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/properties](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/propertyCreateForm](#) **rel**=create-form

The create form resource for this collection resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/properties](#) **rel**=self

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/properties/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/properties/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/properties](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/properties/{name}](#) **rel**=self

This resource.

POST

Update this [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/propertyCreateForm

This resource manages the create forms for the properties collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) entity populated with default values that can be customized then posted (using the POST method) to the properties collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/propertycreateForm **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/properties **rel**=create

The collection resource for this create form resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/propertycreateForm **rel**=self

This resource.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapPropertyCreateForm

This resource manages the create forms for the mapProperties collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFConfigurationPropertiesBean](#) entity populated with default values that can be customized then posted (using the POST method) to the [mapProperties](#) collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFConfigurationPropertiesBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapPropertyCreateForm **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties **rel**=create

The collection resource for this create form resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapPropertyCreateForm **rel**=self

This resource.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/properties

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/properties **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/propertyCreateForm **rel**=create-form

The create form resource for this collection resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/properties **rel**=self

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/properties/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) instance.

Roles

Admin

GET

Get this [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/properties/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/properties **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/properties/{name} **rel**=self

This resource.

POST

POST

Update this [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/propertyCreateForm

This resource manages the create forms for the properties collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) entity populated with default values that can be customized then posted (using the POST method) to the properties collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/propertyCreateForm **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/properties **rel**=create

The collection resource for this create form resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/propertyCreateForm **rel**=self

This resource.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/heapDumpActionCreateForm

This resource manages the create forms for the heapDumpActions collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFHeapDumpActionBean](#) entity populated with default values that can be customized then posted (using the POST method) to the heapDumpActions collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFHeapDumpActionBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/heapDumpActionCreateForm **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/heapDumpActions **rel**=create

The collection resource for this create form resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/heapDumpActionCreateForm **rel**=self

This resource.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/heapDumpActions

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFHeapDumpActionBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFHeapDumpActionBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFHeapDumpActionBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/heapDumpActions](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/heapDumpActionCreateForm](#) **rel**=create-form

The create form resource for this collection resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/heapDumpActions](#) **rel**=self

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFHeapDumpActionBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFHeapDumpActionBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/heapDumpActions/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFHeapDumpActionBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFHeapDumpActionBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.diagnostics.descriptor.WLDFHeapDumpActionBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFHeapDumpActionBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/heapDumpActions/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/heapDumpActions](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/heapDumpActions/{name}](#) **rel**=self

This resource.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watch

POST

Update this [weblogic.diagnostics.descriptor.WLDFHeapDumpActionBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFHeapDumpActionBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/imageNotificationCreateForm

This resource manages the create forms for the imageNotifications collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFImageNotificationBean](#) entity populated with default values that can be customized then posted (using the POST method) to the imageNotifications collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFImageNotificationBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/imageNotificationCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/imageNotifications](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/imageNotificationCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/imageNotifications

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFImageNotificationBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFImageNotificationBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFImageNotificationBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/imageNotifications **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/imageNotifications/createForm **rel**=create-form

The create form resource for this collection resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/imageNotifications **rel**=self

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFImageNotificationBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFImageNotificationBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/imageNotifications/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFImageNotificationBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFImageNotificationBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.diagnostics.descriptor.WLDFImageNotificationBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFImageNotificationBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/imageNotifications/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/imageNotifications **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/imageNotifications/{name} **rel**=self

This resource.

POST

Update this [weblogic.diagnostics.descriptor.WLDFImageNotificationBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFImageNotificationBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMSNotificationCreateForm

This resource manages the create forms for the JMSNotifications collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFJMSNotificationBean](#) entity populated with default values that can be customized then posted (using the POST method) to the JMSNotifications collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFJMSNotificationBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMSNotificationCreateForm **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotifications **rel**=create

The collection resource for this create form resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMSNotificationCreateForm **rel**=self

This resource.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMSNotifications

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFJMSNotificationBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFJMSNotificationBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFJMSNotificationBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMSNotifications](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMSNotificationCreateForm](#) **rel**=create-form

The create form resource for this collection resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMSNotifications](#) **rel**=self

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFJMSNotificationBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFJMSNotificationBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMSNotifications/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFJMSNotificationBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFJMSNotificationBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.diagnostics.descriptor.WLDFJMSNotificationBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFJMSNotificationBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMSNotifications/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMSNotifications](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMSNotifications/{name}](#) **rel**=self

This resource.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watch

POST

Update this [weblogic.diagnostics.descriptor.WLDFJMSNotificationBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFJMSNotificationBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMXNotificationCreateForm

This resource manages the create forms for the JMXNotifications collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFJMXNotificationBean](#) entity populated with default values that can be customized then posted (using the POST method) to the JMXNotifications collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFJMXNotificationBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMXNotificationCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMXNotifications](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMXNotificationCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMXNotifications

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFJMXNotificationBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFJMXNotificationBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFJMXNotificationBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMXNotificationns **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMXNotificationCreateForm **rel**=create-form

The create form resource for this collection resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMXNotificationns **rel**=self

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFJMXNotificationBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFJMXNotificationBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMXNotifications/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFJMXNotificationBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFJMXNotificationBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.diagnostics.descriptor.WLDFJMXNotificationBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFJMXNotificationBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMXNotifications/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMXNotifications **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMXNotifications/{name} **rel**=self

This resource.

POST

Update this [weblogic.diagnostics.descriptor.WLDFJMXNotificationBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFJMXNotificationBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/logActionCreate Form

This resource manages the create forms for the logActions collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFLogActionBean](#) entity populated with default values that can be customized then posted (using the POST method) to the logActions collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFLogActionBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/logActionCreateForm **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/logActions **rel**=create

The collection resource for this create form resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/logActionCreateForm **rel**=self

This resource.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/logActions

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFLogActionBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFLogActionBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFLogActionBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/logActions](#)
rel=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/logActionCreateForm](#) **rel**=create-form

The create form resource for this collection resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/logActions](#)
rel=self

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFLogActionBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFLogActionBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/logActions/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFLogActionBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFLogActionBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.diagnostics.descriptor.WLDFLogActionBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFLogActionBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/logActions/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/logActions](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/logActions/{name}](#) **rel**=self

This resource.

POST

Update this [weblogic.diagnostics.descriptor.WLDFLogActionBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFLogActionBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/lookupActions

The resource supports the following methods:

- [POST](#)

POST

Roles

Admin, Deployer

Request Body

Must contain a JSON object with the following fields:

typeName

typeName

Type: string

Response Body

Contains a JSON object with a array of weblogic.diagnostics.descriptor.WLDFActionBean references return field.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/lookupNotification

The resource supports the following methods:

- [POST](#)

POST

Looks up an action with the given name.

Roles

Admin, Deployer

Request Body

Must contain a JSON object with the following fields:

name

name

Type: string

Response Body

Contains a JSON object with a weblogic.diagnostics.descriptor.WLDFNotificationBean reference return field.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/RESTNotificationCreateForm

This resource manages the create forms for the RESTNotifications collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFRESTNotificationBean](#) entity populated with default values that can be customized then posted (using the POST method) to the RESTNotifications collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFRESTNotificationBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/RESTNotificationCreateForm **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/RESTNotifications **rel**=create

The collection resource for this create form resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/RESTNotificationCreateForm **rel**=self

This resource.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/RESTNotifications

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFRESTNotificationBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFRESTNotificationBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFRESTNotificationBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/RESTNotification **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/RESTNotificationCreateForm **rel**=create-form

The create form resource for this collection resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/RESTNotification **rel**=self

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFRESTNotificationBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFRESTNotificationBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/RESTNotifications/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFRESTNotificationBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFRESTNotificationBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.diagnostics.descriptor.WLDFRESTNotificationBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFRESTNotificationBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/RESTNotifications/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/RESTNotifications **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/RESTNotifications/{name} **rel**=self

This resource.

POST

Update this [weblogic.diagnostics.descriptor.WLDFRESTNotificationBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFRESTNotificationBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleDownActionCreateForm

This resource manages the create forms for the scaleDownActions collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFScaleDownActionBean](#) entity populated with default values that can be customized then posted (using the POST method) to the `scaleDownActions` collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFScaleDownActionBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleDownActionCreateForm](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleDownActions](#) **rel**=create

The collection resource for this create form resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleDownActionCreateForm](#) **rel**=self

This resource.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleDownActions

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFScaleDownActionBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of `weblogic.diagnostics.descriptor.WLDFScaleDownActionBean` instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of `weblogic.diagnostics.descriptor.WLDFScaleDownActionBean` entities.

This method can return the following links:

- **uri**=`/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleDownActions` **rel**=canonical

This resource.

- **uri**=`/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleDownActionCreateForm` **rel**=create-form

The create form resource for this collection resource.

- **uri**=`/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification` **rel**=parent

The parent resource of this resource.

- **uri**=`/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleDownActions` **rel**=self

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFScaleDownActionBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFScaleDownActionBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleDownActions/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFScaleDownActionBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFScaleDownActionBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.diagnostics.descriptor.WLDFScaleDownActionBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFScaleDownActionBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleDownActions/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleDownActions](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleDownActions/{name}](#) **rel**=self

This resource.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watch

POST

Update this [weblogic.diagnostics.descriptor.WLDFScaleDownActionBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFScaleDownActionBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleUpActionCreateForm

This resource manages the create forms for the scaleUpActions collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFScaleUpActionBean](#) entity populated with default values that can be customized then posted (using the POST method) to the scaleUpActions collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFScaleUpActionBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleUpActionCreateForm **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleUpActions **rel**=create

The collection resource for this create form resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleUpActionCreateForm **rel**=self

This resource.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleUpActions

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFScaleUpActionBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFScaleUpActionBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFScaleUpActionBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleUpActions
rel=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleUpActionCreateForm
rel=create-form

The create form resource for this collection resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification
rel=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleUpActions
rel=self

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFScaleUpActionBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFScaleUpActionBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleUpActions/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFScaleUpActionBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFScaleUpActionBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.diagnostics.descriptor.WLDFScaleUpActionBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFScaleUpActionBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleUpActions/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleUpActions **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleUpActions/{name} **rel**=self

This resource.

POST

Update this [weblogic.diagnostics.descriptor.WLDFScaleUpActionBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFScaleUpActionBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scriptActionCreateForm

This resource manages the create forms for the scriptActions collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFScriptActionBean](#) entity populated with default values that can be customized then posted (using the POST method) to the scriptActions collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFScriptActionBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scriptActionCreateForm](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scriptActions](#) **rel**=create

The collection resource for this create form resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scriptActionCreateForm](#) **rel**=self

This resource.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scriptActions

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFScriptActionBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFScriptActionBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFScriptActionBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scriptActions](#)
rel=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scriptActionCreateForm](#) **rel**=create-form

The create form resource for this collection resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scriptActions](#)
rel=self

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFScriptActionBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFScriptActionBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scriptActions/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFScriptActionBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFScriptActionBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.diagnostics.descriptor.WLDFScriptActionBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFScriptActionBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scriptActions/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scriptActions](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/scriptActions/{name}](#) **rel**=self

This resource.

POST

Update this [weblogic.diagnostics.descriptor.WLDFScriptActionBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFScriptActionBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/SMTPNotificationCreateForm

This resource manages the create forms for the SMTPNotifications collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFSMTPNotificationBean](#) entity populated with default values that can be customized then posted (using the POST method) to the SMTPNotifications collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFSMTPNotificationBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/SMTPNotificationCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/SMTPNotifications](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/SMTPNotificationCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/SMTPNotifications

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFSMTPNotificationBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFSMTPNotificationBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFSMTPNotificationBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/SMTPNotifications **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/SMTPNotifications/createForm **rel**=create-form

The create form resource for this collection resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/SMTPNotifications **rel**=self

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFSMTPNotificationBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFSMTPNotificationBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/SMTPLocations/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFSMTPNotificationBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFSMTPNotificationBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.diagnostics.descriptor.WLDFSMTPNotificationBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFSMTPNotificationBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/SMTPNotifications/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/SMTPNotifications **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/SMTPNotifications/{name} **rel**=self

This resource.

POST

Update this [weblogic.diagnostics.descriptor.WLDFSMTPLNotificationBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFSMTPLNotificationBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/NotificationCreateForm

This resource manages the create forms for the Notification collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFSNMPNotificationBean](#) entity populated with default values that can be customized then posted (using the POST method) to the SNMPNotifications collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFSNMPNotificationBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/SNMPNotifications>CreateForm **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/SNMPNotifications **rel**=create

The collection resource for this create form resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/SNMPNotifications>CreateForm **rel**=self

This resource.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/SNMPNotifications

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFSNMPNotificationBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFSNMPNotificationBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFSNMPNotificationBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/SNMPNotifications](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/SNMPNotificationCreateForm](#) **rel**=create-form

The create form resource for this collection resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/SNMPNotifications](#) **rel**=self

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFSNMPNotificationBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFSNMPNotificationBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/SNMPNotifications/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFSNMPNotificationBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFSNMPNotificationBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.diagnostics.descriptor.WLDFSNMPNotificationBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFSNMPNotificationBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/SNMPNotifications/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/SNMPNotifications](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/SNMPNotifications/{name}](#) **rel**=self

This resource.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watch

POST

Update this [weblogic.diagnostics.descriptor.WLDFSNMPNotificationBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFSNMPNotificationBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/threadDumpActionCreateForm

This resource manages the create forms for the threadDumpActions collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFThreadDumpActionBean](#) entity populated with default values that can be customized then posted (using the POST method) to the threadDumpActions collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFThreadDumpActionBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/threadDumpActionCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/threadDumpActions](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/threadDumpActionCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/threadDumpActions

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFThreadDumpActionBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFThreadDumpActionBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFThreadDumpActionBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/threadDumpActions **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/threadDumpActionCreateForm **rel**=create-form

The create form resource for this collection resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/threadDumpActions **rel**=self

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFThreadDumpActionBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFThreadDumpActionBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/threadDumpActions/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFThreadDumpActionBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFThreadDumpActionBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.diagnostics.descriptor.WLDFThreadDumpActionBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFThreadDumpActionBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/threadDumpActions/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/threadDumpActions **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/threadDumpActions/{name} **rel**=self

This resource.

POST

POST

Update this [weblogic.diagnostics.descriptor.WLDFThreadDumpActionBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFThreadDumpActionBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/watchCreateForm

This resource manages the create forms for the watches collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFWatchBean](#) entity populated with default values that can be customized then posted (using the POST method) to the watches collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFWatchBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/watchCreateForm](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/watches](#) **rel**=create

The collection resource for this create form resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/watchCreateForm](#) **rel**=self

This resource.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/watches

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFWatchBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFWatchBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFWatchBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/watches](#)
rel=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/watchCreateForm](#) **rel**=create-form

The create form resource for this collection resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/watches](#)
rel=self

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFWatchBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFWatchBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/watches/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFWatchBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFWatchBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.diagnostics.descriptor.WLDFWatchBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFWatchBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/watches/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/watches](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/watches/{name}/schedule](#) **rel**=schedule

This resource's schedule singleton resource.

- **uri**=[/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/watches/{name}](#) **rel**=self

This resource.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watch

POST

Update this [weblogic.diagnostics.descriptor.WLDFWatchBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFWatchBean](#) entity.

/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/watches/{name}/schedule

This resource manages a [weblogic.diagnostics.descriptor.WLDFScheduleBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.diagnostics.descriptor.WLDFScheduleBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFScheduleBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/watches/{name}/schedule **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/watches/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/resourceGroupTemplates/{name}/WLDFSystemResources/{name}/WLDFResource/watchNotification/watches/{name}/schedule **rel**=self

This resource.

POST

Update this [weblogic.diagnostics.descriptor.WLDFScheduleBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFScheduleBean](#) entity.

/management/weblogic/{version}/edit/resourceManagement

This resource manages a [weblogic.management.configuration.ResourceManagementMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.ResourceManagementMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ResourceManagementMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceManagement](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/resourceManagement/resourceManagerCreateForm](#) **rel**=resourceManagerCreateForm
The create form resource for this resource's resourceManagers collection resource.
- **uri**=[/management/weblogic/{version}/edit/resourceManagement/resourceManagers](#) **rel**=resourceManagers
This resource's resourceManagers collection resource.
- **uri**=[/management/weblogic/{version}/edit/resourceManagement](#) **rel**=self
This resource.

POST

Update this [weblogic.management.configuration.ResourceManagementMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.ResourceManagementMBean](#) entity.

/management/weblogic/{version}/edit/resourceManagement/resourceManagerCreateForm

This resource manages the create forms for the resourceManagers collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.ResourceManagerMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the resourceManagers collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ResourceManagerMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceManagement/resourceManagerCreateForm rel=canonical](#)
This resource.
- [uri=/management/weblogic/{version}/edit/resourceManagement/resourceManagers rel=create](#)
The collection resource for this create form resource.
- [uri=/management/weblogic/{version}/edit/resourceManagement rel=parent](#)
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/resourceManagement/resourceManagerCreateForm rel=self](#)
This resource.

/management/weblogic/{version}/edit/resourceManagement/resourceManagers

This resource manages a collection of [weblogic.management.configuration.ResourceManagerMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.ResourceManagerMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.ResourceManagerMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceManagement/resourceManagers rel=canonical](#)
This resource.
- [uri=/management/weblogic/{version}/edit/resourceManagement/resourceManagerCreateForm rel=create-form](#)
The create form resource for this collection resource.
- [uri=/management/weblogic/{version}/edit/resourceManagement rel=parent](#)
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/resourceManagement/resourceManagers rel=self](#)
This resource.

POST

Add a new [weblogic.management.configuration.ResourceManagerMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.ResourceManagerMBean](#) entity.

/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}

This resource manages a [weblogic.management.configuration.ResourceManagerMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

DELETE

Delete this [weblogic.management.configuration.ResourceManagerMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.ResourceManagerMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ResourceManagerMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/cpuUtilization](#) **rel=cpuUtilization**
This resource's cpuUtilization singleton resource.
- [uri=/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/cpuUtilizationCreateForm](#) **rel=cpuUtilizationCreateForm**
The create form resource for this resource's cpuUtilization optional singleton resource.
- [uri=/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/fileOpen](#) **rel=fileOpen**
This resource's fileOpen singleton resource.
- [uri=/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/fileOpenCreateForm](#) **rel=fileOpenCreateForm**
The create form resource for this resource's fileOpen optional singleton resource.
- [uri=/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/heapRetained](#) **rel=heapRetained**
This resource's heapRetained singleton resource.
- [uri=/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/heapRetainedCreateForm](#) **rel=heapRetainedCreateForm**
The create form resource for this resource's heapRetained optional singleton resource.
- [uri=/management/weblogic/{version}/edit/resourceManagement/resourceManagers](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/restartLoopProtection](#) **rel=restartLoopProtection**
This resource's restartLoopProtection singleton resource.
- [uri=/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}](#) **rel=self**
This resource.

POST

POST

Update this [weblogic.management.configuration.ResourceManagerMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.ResourceManagerMBean](#) entity.

/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/cpuUtilization

This resource manages a [weblogic.management.configuration.CpuUtilizationMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.CpuUtilizationMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.CpuUtilizationMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.CpuUtilizationMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/cpuUtilization](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/cpuUtilizationCreateForm](#) **rel=create-form**
The create form resource for this optional singleton resource.
- [uri=/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/cpuUtilization/fairShareConstraint](#) **rel=fairShareConstraint**
This resource's fairShareConstraint singleton resource.
- [uri=/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/cpuUtilization/fairShareConstraintCreateForm](#) **rel=fairShareConstraintCreateForm**
The create form resource for this resource's fairShareConstraint optional singleton resource.
- [uri=/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/cpuUtilization](#) **rel=self**
This resource.
- [uri=/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/cpuUtilization/triggerCreateForm](#) **rel=triggerCreateForm**
The create form resource for this resource's triggers collection resource.
- [uri=/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/cpuUtilization/triggers](#) **rel=triggers**
This resource's triggers collection resource.

POST

Update this [weblogic.management.configuration.CpuUtilizationMBean](#) instance if it exists; otherwise, create it.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.CpuUtilizationMBean](#) entity.

/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/cpuUtilization/fairShareConstraint

This resource manages a [weblogic.management.configuration.FairShareConstraintMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

DELETE

Delete this [weblogic.management.configuration.FairShareConstraintMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.FairShareConstraintMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.FairShareConstraintMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/cpuUtilization/fairShareConstraint](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/cpuUtilization/fairShareConstraintCreateForm](#) **rel=create-form**

The create form resource for this optional singleton resource.

- [uri=/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/cpuUtilization](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/cpuUtilization/fairShareConstraint](#) **rel=self**

This resource.

POST

POST

Update this [weblogic.management.configuration.FairShareConstraintMBean](#) instance if it exists; otherwise, create it.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.FairShareConstraintMBean](#) entity.

/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/cpuUtilization/fairShareConstraintCreateForm

This resource manages the create forms for the fairShareConstraint optional singleton instance.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.FairShareConstraintMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the [fairShareConstraint](#) optional singleton resource to create a new instance if it currently does not exist.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.FairShareConstraintMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/cpuUtilization/fairShareConstraintCreateForm **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/cpuUtilization/fairShareConstraintCreateForm **rel**=create

The optional singleton resource for this create form resource.

- **uri**=/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/cpuUtilization **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/cpuUtilization/fairShareConstraintCreateForm **rel**=self

This resource.

/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/cpuUtilization/triggerCreateForm

This resource manages the create forms for the triggers collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.TriggerMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the triggers collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.TriggerMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/cpuUtilization/triggerCreateForm](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/cpuUtilization/triggers](#) **rel**=create

The collection resource for this create form resource.

- **uri**=[/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/cpuUtilization](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/cpuUtilization/triggerCreateForm](#) **rel**=self

This resource.

/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/cpuUtilization/triggers

This resource manages a collection of [weblogic.management.configuration.TriggerMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.TriggerMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.TriggerMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/cpuUtilization/triggers **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/cpuUtilization/triggerCreateForm **rel**=create-form

The create form resource for this collection resource.

- **uri**=/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/cpuUtilization **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/cpuUtilization/triggers **rel**=self

This resource.

POST

Add a new [weblogic.management.configuration.TriggerMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.TriggerMBean](#) entity.

/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/cpuUtilization/triggers/{name}

This resource manages a [weblogic.management.configuration.TriggerMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.TriggerMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.TriggerMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.TriggerMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/cpuUtilization/triggers/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/cpuUtilization/triggers](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/cpuUtilization/triggers/{name}](#) **rel**=self

This resource.

POST

Update this [weblogic.management.configuration.TriggerMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.TriggerMBean](#) entity.

/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/cpuUtilizationCreateForm

This resource manages the create forms for the cpuUtilization optional singleton instance.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.CpuUtilizationMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the `cpuUtilization` optional singleton resource to create a new instance if it currently does not exist.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.CpuUtilizationMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/cpuUtilizationCreateForm rel=canonical](#)

This resource.

- [uri=/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/cpuUtilizationCreateForm rel=create](#)

The optional singleton resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name} rel=parent](#)

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/cpuUtilizationCreateForm rel=self](#)

This resource.

/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/fileOpen

This resource manages a [weblogic.management.configuration.FileOpenMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.FileOpenMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.FileOpenMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.FileOpenMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/fileOpen](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/fileOpencreateForm](#) **rel**=create-form
The create form resource for this optional singleton resource.
- **uri**=[/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/fileOpen](#) **rel**=self
This resource.
- **uri**=[/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/fileOpen/triggerscreateForm](#) **rel**=triggercreateForm
The create form resource for this resource's triggers collection resource.
- **uri**=[/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/fileOpen/triggers](#) **rel**=triggers
This resource's triggers collection resource.

POST

Update this [weblogic.management.configuration.FileOpenMBean](#) instance if it exists; otherwise, create it.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.FileOpenMBean](#) entity.

/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/fileOpen/triggerCreateForm

This resource manages the create forms for the triggers collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.TriggerMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the triggers collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.TriggerMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/fileOpen/triggerCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/fileOpen/triggers](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/fileOpen](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/fileOpen/triggerCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/fileOpen/triggers

This resource manages a collection of [weblogic.management.configuration.TriggerMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.TriggerMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.TriggerMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/fileOpen/triggers](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/fileOpen/triggerCreateForm](#) **rel=create-form**

The create form resource for this collection resource.

- [uri=/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/fileOpen](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/fileOpen/triggers](#) **rel=self**

This resource.

POST

Add a new [weblogic.management.configuration.TriggerMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.TriggerMBean](#) entity.

/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/fileOpen/triggers/{name}

This resource manages a [weblogic.management.configuration.TriggerMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.TriggerMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.TriggerMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.TriggerMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/fileOpen/triggers/{name} **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/fileOpen/triggers **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/fileOpen/triggers/{name} **rel**=self
This resource.

POST

Update this [weblogic.management.configuration.TriggerMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.TriggerMBean](#) entity.

/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/fileOpenCreateForm

This resource manages the create forms for the fileOpen optional singleton instance.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.FileOpenMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the fileOpen optional singleton resource to create a new instance if it currently does not exist.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.FileOpenMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/fileOpenCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/fileOpenCreateForm](#) **rel=create**

The optional singleton resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/fileOpenCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/heapRetained

This resource manages a [weblogic.management.configuration.HeapRetainedMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.HeapRetainedMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.HeapRetainedMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.HeapRetainedMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/heapRetained](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/heapRetainedcreateForm](#) **rel=create-form**
The create form resource for this optional singleton resource.
- [uri=/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/heapRetained/fairShareConstraint](#) **rel=fairShareConstraint**
This resource's fairShareConstraint singleton resource.
- [uri=/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/heapRetained/fairShareConstraintcreateForm](#) **rel=fairShareConstraintcreateForm**
The create form resource for this resource's fairShareConstraint optional singleton resource.
- [uri=/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/heapRetained](#) **rel=self**
This resource.
- [uri=/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/heapRetained/triggercreateForm](#) **rel=triggercreateForm**
The create form resource for this resource's triggers collection resource.
- [uri=/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/heapRetained/triggers](#) **rel=triggers**
This resource's triggers collection resource.

POST

Update this [weblogic.management.configuration.HeapRetainedMBean](#) instance if it exists; otherwise, create it.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.HeapRetainedMBean](#) entity.

/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/heapRetained/fairShareConstraint

This resource manages a [weblogic.management.configuration.FairShareConstraintMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.FairShareConstraintMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.FairShareConstraintMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.FairShareConstraintMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/heapRetained/fairShareConstraint](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/heapRetained/fairShareConstraintCreateForm](#) **rel=create-form**

The create form resource for this optional singleton resource.

- [uri=/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/heapRetained](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/heapRetained/fairShareConstraint](#) **rel=self**

This resource.

POST

Update this [weblogic.management.configuration.FairShareConstraintMBean](#) instance if it exists; otherwise, create it.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.FairShareConstraintMBean](#) entity.

/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/heapRetained/fairShareConstraintCreateForm

This resource manages the create forms for the fairShareConstraint optional singleton instance.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.FairShareConstraintMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the [fairShareConstraint](#) optional singleton resource to create a new instance if it currently does not exist.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.FairShareConstraintMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/heapRetained/fairShareConstraintCreateForm **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/heapRetained/fairShareConstraintCreateForm **rel**=create
The optional singleton resource for this create form resource.
- **uri**=/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/heapRetained **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/heapRetained/fairShareConstraintCreateForm **rel**=self
This resource.

/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/heapRetained/triggerCreateForm

This resource manages the create forms for the triggers collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.TriggerMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the triggers collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.TriggerMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/heapRetained/triggerCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/heapRetained/triggers](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/heapRetained](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/heapRetained/triggerCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/heapRetained/triggers

This resource manages a collection of [weblogic.management.configuration.TriggerMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.TriggerMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.TriggerMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/heapRetained/triggers](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/heapRetained/triggerCreateForm](#) **rel=create-form**

The create form resource for this collection resource.

- [uri=/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/heapRetained](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/heapRetained/triggers](#) **rel=self**

This resource.

POST

Add a new [weblogic.management.configuration.TriggerMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.TriggerMBean](#) entity.

/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/heapRetained/triggers/{name}

This resource manages a [weblogic.management.configuration.TriggerMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.TriggerMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.TriggerMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.TriggerMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/heapRetained/triggers/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/heapRetained/triggers](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/heapRetained/triggers/{name}](#) **rel**=self

This resource.

POST

Update this [weblogic.management.configuration.TriggerMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.TriggerMBean](#) entity.

/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/heapRetainedCreateForm

This resource manages the create forms for the heapRetained optional singleton instance.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.HeapRetainedMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the heapRetained optional singleton resource to create a new instance if it currently does not exist.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.HeapRetainedMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/heapRetainedCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/heapRetainedCreateForm](#) **rel=create**

The optional singleton resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/heapRetainedCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/restartLoopProtection

This resource manages a [weblogic.management.configuration.RestartLoopProtectionMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.RestartLoopProtectionMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.RestartLoopProtectionMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/restartLoopProtection **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name} **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/edit/resourceManagement/resourceManagers/{name}/restartLoopProtection **rel**=self
This resource.

POST

Update this [weblogic.management.configuration.RestartLoopProtectionMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.RestartLoopProtectionMBean](#) entity.

/management/weblogic/{version}/edit/restfulManagementServices

This resource manages a [weblogic.management.configuration.RestfulManagementServicesMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.RestfulManagementServicesMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.RestfulManagementServicesMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/restfulManagementServices](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/restfulManagementServices](#) **rel**=self
This resource.

POST

Update this [weblogic.management.configuration.RestfulManagementServicesMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.RestfulManagementServicesMBean](#) entity.

/management/weblogic/{version}/edit/SAFAgentCreateForm

This resource manages the create forms for the SAFAgents collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.SAFAgentMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the SAFAgents collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SAFAgentMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/SAFAgentCreateForm](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/SAFAgents](#) **rel=create**
The collection resource for this create form resource.
- [uri=/management/weblogic/{version}/edit](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/SAFAgentCreateForm](#) **rel=self**
This resource.

/management/weblogic/{version}/edit/SAFAgents

This resource manages a collection of [weblogic.management.configuration.SAFAMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.SAFAgentMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.SAFAgentMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/SAFAgents](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/SAFAgentCreateForm](#)
rel=create-form
The create form resource for this collection resource.
- **uri**=[/management/weblogic/{version}/edit](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/SAFAgents](#) **rel**=self
This resource.

POST

Add a new [weblogic.management.configuration.SAFAgentMBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.SAFAgentMBean](#) entity.

/management/weblogic/{version}/edit/SAFAgents/{name}

This resource manages a [weblogic.management.configuration.SAFAgentMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.SAFAgentMBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.management.configuration.SAFAgentMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SAFAgentMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/SAFAgents/{name}/JMSSAFMessageLogFile](#) **rel**=JMSSAFMessageLogFile
This resource's JMSSAFMessageLogFile singleton resource.
- **uri**=[/management/weblogic/{version}/edit/SAFAgents/{name}](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/SAFAgents](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/SAFAgents/{name}](#) **rel**=self
This resource.
- **rel**=store
This resource's store reference to a [weblogic.management.configuration.PersistentStoreMBean](#) resource.

POST

Update this [weblogic.management.configuration.SAFAgentMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.SAFAgentMBean](#) entity.

/management/weblogic/{version}/edit/SAFAgents/{name}/JMSSAFMessageLogFile

This resource manages a [weblogic.management.configuration.JMSSAFMessageLogFileMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.JMSSAFMessageLogFileMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.JMSSAFMessageLogFileMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/SAFAgents/{name}/JMSSAFMessageLogFile](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/SAFAgents/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/SAFAgents/{name}/JMSSAFMessageLogFile](#) **rel**=self
This resource.

POST

Update this [weblogic.management.configuration.JMSSAFMessageLogFileMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.JMSSAFMessageLogFileMBean](#) entity.

/management/weblogic/{version}/edit/search

The resource supports the following methods:

- [POST](#)

POST

Search the edit tree.

Roles

Admin, Deployer, Monitor, Operator

Request Body

The search request body includes the search criteria.

Response Body

The search response includes the results of the search.

/management/weblogic/{version}/edit/securityConfiguration

This resource manages a [weblogic.management.configuration.SecurityConfigurationMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.SecurityConfigurationMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SecurityConfigurationMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/securityConfiguration/JASPIC](#)
rel=JASPIC
This resource's JASPIC singleton resource.
- **uri**=[/management/weblogic/{version}/edit/securityConfiguration](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/securityConfiguration/certRevoc](#)
rel=certRevoc
This resource's certRevoc singleton resource.
- **rel**=defaultRealm
This resource's defaultRealm reference to a [weblogic.management.security.RealmMBean](#) resource.
- **uri**=[/management/weblogic/{version}/edit](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/securityConfiguration/realmCreateForm](#) **rel**=realmCreateForm
The create form resource for this resource's realms collection resource.
- **uri**=[/management/weblogic/{version}/edit/securityConfiguration/realms](#)
rel=realms
This resource's realms collection resource.
- **uri**=[/management/weblogic/{version}/edit/securityConfiguration/secureMode](#)
rel=secureMode
This resource's secureMode singleton resource.
- **uri**=[/management/weblogic/{version}/edit/securityConfiguration](#) **rel**=self
This resource.

POST

Update this [weblogic.management.configuration.SecurityConfigurationMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.SecurityConfigurationMBean](#) entity.

/management/weblogic/{version}/edit/securityConfiguration/certRevoc

This resource manages a [weblogic.management.configuration.CertRevocMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.CertRevocMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.CertRevocMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/securityConfiguration/certRevoc](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/securityConfiguration/certRevoc/certRevocCaCreateForm](#) **rel**=certRevocCaCreateForm
The create form resource for this resource's certRevocCas collection resource.
- **uri**=[/management/weblogic/{version}/edit/securityConfiguration/certRevoc/certRevocCas](#) **rel**=certRevocCas
This resource's certRevocCas collection resource.
- **uri**=[/management/weblogic/{version}/edit/securityConfiguration](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/securityConfiguration/certRevoc](#)
rel=self
This resource.

POST

Update this [weblogic.management.configuration.CertRevocMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.CertRevocMBean](#) entity.

/management/weblogic/{version}/edit/securityConfiguration/certRevoc/certRevocCaCreateForm

This resource manages the create forms for the certRevocCas collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.CertRevocCaMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the certRevocCas collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.CertRevocCaMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/securityConfiguration/certRevoc/certRevocCaCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/securityConfiguration/certRevoc/certRevocCas](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/securityConfiguration/certRevoc](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/securityConfiguration/certRevoc/certRevocCaCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/securityConfiguration/certRevoc/certRevocCas

This resource manages a collection of [weblogic.management.configuration.CertRevocCaMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.CertRevocCaMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.CertRevocCaMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/securityConfiguration/certRevoc/certRevocCas](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/securityConfiguration/certRevoc/certRevocCaCreateForm](#) **rel=create-form**
The create form resource for this collection resource.
- [uri=/management/weblogic/{version}/edit/securityConfiguration/certRevoc](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/securityConfiguration/certRevoc/certRevocCas](#) **rel=self**
This resource.

POST

Add a new [weblogic.management.configuration.CertRevocCaMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.CertRevocCaMBean](#) entity.

/management/weblogic/{version}/edit/securityConfiguration/certRevoc/certRevocCas/{name}

This resource manages a [weblogic.management.configuration.CertRevocCaMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

DELETE

Delete this [weblogic.management.configuration.CertRevocCaMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.CertRevocCaMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.CertRevocCaMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/securityConfiguration/certRevoc/certRevocCas/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/securityConfiguration/certRevoc/certRevocCas **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/securityConfiguration/certRevoc/certRevocCas/{name} **rel**=self

This resource.

POST

POST

Update this [weblogic.management.configuration.CertRevocCaMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.CertRevocCaMBean](#) entity.

/management/weblogic/{version}/edit/securityConfiguration/JASPIC

This resource manages a [weblogic.management.configuration.JASPICMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.JASPICMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.JASPICMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/securityConfiguration/JASPIC/authConfigProviderCreateForm](#) **rel**=authConfigProviderCreateForm
The create form resource for this resource's authConfigProviders collection resource.
- **uri**=[/management/weblogic/{version}/edit/securityConfiguration/JASPIC/authConfigProviders](#) **rel**=authConfigProviders
This resource's authConfigProviders collection resource.
- **uri**=[/management/weblogic/{version}/edit/securityConfiguration/JASPIC](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/securityConfiguration](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/securityConfiguration/JASPIC](#) **rel**=self
This resource.

POST

Update this [weblogic.management.configuration.JASPICMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.JASPICMBean](#) entity.

/management/weblogic/{version}/edit/securityConfiguration/JASPIC/authConfigProviderCreateForm

This resource manages the create forms for the authConfigProviders collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.AuthConfigProviderMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the [authConfigProviders](#) collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.AuthConfigProviderMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/securityConfiguration/JASPIC/authConfigProviderCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/securityConfiguration/JASPIC/authConfigProviders](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/securityConfiguration/JASPIC](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/securityConfiguration/JASPIC/authConfigProviderCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/securityConfiguration/JASPIC/authConfigProviders

This resource manages a collection of [weblogic.management.configuration.AuthConfigProviderMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.AuthConfigProviderMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.AuthConfigProviderMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/securityConfiguration/JASPIC/authConfigProviders](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/securityConfiguration/JASPIC/authConfigProviderCreateForm](#) **rel=create-form**
The create form resource for this collection resource.
- [uri=/management/weblogic/{version}/edit/securityConfiguration/JASPIC](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/securityConfiguration/JASPIC/authConfigProviders](#) **rel=self**
This resource.

POST

Add a new [weblogic.management.configuration.AuthConfigProviderMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.AuthConfigProviderMBean](#) entity.

/management/weblogic/{version}/edit/securityConfiguration/JASPIC/authConfigProviders/{name}

This resource manages a [weblogic.management.configuration.AuthConfigProviderMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

DELETE

Delete this [weblogic.management.configuration.AuthConfigProviderMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.AuthConfigProviderMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.AuthConfigProviderMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/securityConfiguration/JASPIC/authConfigProviders/{name} **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/edit/securityConfiguration/JASPIC/authConfigProviders **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/edit/securityConfiguration/JASPIC/authConfigProviders/{name} **rel**=self
This resource.

POST

POST

Update this [weblogic.management.configuration.AuthConfigProviderMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.AuthConfigProviderMBean](#) entity.

/management/weblogic/{version}/edit/securityConfiguration/realmCreateForm

This resource manages the create forms for the realms collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.security.RealmMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the realms collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.security.RealmMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/securityConfiguration/realmCreateForm rel=canonical](#)
This resource.
- [uri=/management/weblogic/{version}/edit/securityConfiguration/realms rel=create](#)
The collection resource for this create form resource.
- [uri=/management/weblogic/{version}/edit/securityConfiguration rel=parent](#)
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/securityConfiguration/realmCreateForm rel=self](#)
This resource.

/management/weblogic/{version}/edit/securityConfiguration/realms

This resource manages a collection of [weblogic.management.security.RealmMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.security.RealmMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.security.RealmMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/securityConfiguration/realms](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/securityConfiguration/realmCreateForm](#) **rel**=create-form
The create form resource for this collection resource.
- **uri**=[/management/weblogic/{version}/edit/securityConfiguration](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/securityConfiguration/realms](#)
rel=self
This resource.

POST

Add a new [weblogic.management.security.RealmMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.security.RealmMBean](#) entity.

/management/weblogic/{version}/edit/securityConfiguration/realms/{name}

This resource manages a [weblogic.management.security.RealmMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.security.RealmMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.security.RealmMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.security.RealmMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/RDBMSSecurityStore](#) **rel=RDBMSSecurityStore**

This resource's RDBMSSecurityStore singleton resource.

- [uri=/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/RDBMSSecurityStoreCreateForm](#) **rel=RDBMSSecurityStoreCreateForm**

The create form resource for this resource's RDBMSSecurityStore optional singleton resource.

- [uri=/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/adjudicator](#) **rel=adjudicator**

This resource's adjudicator singleton resource.

- [uri=/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/adjudicatorCreateForm](#) **rel=adjudicatorCreateForm**

The create form resource for this resource's adjudicator optional singleton resource.

- [uri=/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/auditorCreateForm](#) **rel=auditorCreateForm**

The create form resource for this resource's auditors collection resource.

- [uri=/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/auditors](#) **rel=auditors**

This resource's auditors collection resource.

- [uri=/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/authenticationProviderCreateForm](#) **rel=authenticationProviderCreateForm**

The create form resource for this resource's authenticationProviders collection resource.

- [uri=/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/authenticationProviders](#) **rel=authenticationProviders**

This resource's authenticationProviders collection resource.

- [uri=/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/authorizerCreateForm](#) **rel=authorizerCreateForm**

The create form resource for this resource's authorizers collection resource.

- [uri=/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/authorizers](#) **rel=authorizers**

This resource's authorizers collection resource.

- **uri**=/management/weblogic/{version}/edit/securityConfiguration/realms/{name}
rel=canonical

This resource.

- **rel**=certPathBuilder

This resource's certPathBuilder reference to a weblogic.management.security.pk.CertPathBuilderMBean resource.

- **uri**=/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/certPathProviderCreateForm **rel**=certPathProviderCreateForm

The create form resource for this resource's certPathProviders collection resource.

- **uri**=/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/certPathProviders **rel**=certPathProviders

This resource's certPathProviders collection resource.

- **uri**=/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/credentialMapperCreateForm **rel**=credentialMapperCreateForm

The create form resource for this resource's credentialMappers collection resource.

- **uri**=/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/credentialMappers **rel**=credentialMappers

This resource's credentialMappers collection resource.

- **uri**=/management/weblogic/{version}/edit/securityConfiguration/realms
rel=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/passwordValidatorCreateForm **rel**=passwordValidatorCreateForm

The create form resource for this resource's passwordValidators collection resource.

- **uri**=/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/passwordValidators **rel**=passwordValidators

This resource's passwordValidators collection resource.

- **uri**=/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/roleMapperCreateForm **rel**=roleMapperCreateForm

The create form resource for this resource's roleMappers collection resource.

- **uri**=/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/roleMappers **rel**=roleMappers

This resource's roleMappers collection resource.

- **uri**=/management/weblogic/{version}/edit/securityConfiguration/realms/{name}
rel=self

This resource.

- **uri**=/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/userLockoutManager **rel**=userLockoutManager

This resource's userLockoutManager singleton resource.

POST

POST

Update this [weblogic.management.security.RealmMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.security.RealmMBean](#) entity.

/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/adjudicator

This resource manages a [weblogic.management.security.authorization.AdjudicatorMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)

DELETE

Delete this [weblogic.management.security.authorization.AdjudicatorMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.security.authorization.AdjudicatorMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.security.authorization.AdjudicatorMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/adjudicator](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/adjudicatorCreateForm](#) **rel**=create-form
The create form resource for this optional singleton resource.
- **uri**=[/management/weblogic/{version}/edit/securityConfiguration/realms/{name}](#) **rel**=parent
The parent resource of this resource.
- **rel**=realm
This resource's realm reference to a [weblogic.management.security.RealmMBean](#) resource.
- **uri**=[/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/adjudicator](#) **rel**=self
This resource.

/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/adjudicatorCreateForm

This resource manages the create forms for the adjudicator optional singleton instance.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.security.authorization.AdjudicatorMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the adjudicator optional singleton resource to create a new instance if it currently does not exist.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.security.authorization.AdjudicatorMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/adjudicatorCreateForm](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/adjudicatorCreateForm](#) **rel=create**
The optional singleton resource for this create form resource.
- [uri=/management/weblogic/{version}/edit/securityConfiguration/realms/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/adjudicatorCreateForm](#) **rel=self**
This resource.

/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/auditorCreateForm

This resource manages the create forms for the auditors collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.security.audit.AuditorMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the auditors collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.security.audit.AuditorMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/auditorCreateForm](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/auditors](#) **rel=create**
The collection resource for this create form resource.
- [uri=/management/weblogic/{version}/edit/securityConfiguration/realms/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/auditorCreateForm](#) **rel=self**
This resource.

/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/auditors

This resource manages a collection of [weblogic.management.security.audit.AuditorMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.security.audit.AuditorMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.security.audit.AuditorMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/auditors](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/auditorcreateForm](#) **rel=create-form**
The create form resource for this collection resource.
- [uri=/management/weblogic/{version}/edit/securityConfiguration/realms/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/auditors](#) **rel=self**
This resource.

POST

Add a new [weblogic.management.security.audit.AuditorMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.security.audit.AuditorMBean](#) entity.

/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/auditors/{name}

This resource manages a [weblogic.management.security.audit.AuditorMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)

DELETE

Delete this [weblogic.management.security.audit.AuditorMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.security.audit.AuditorMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.security.audit.AuditorMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/auditors/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/auditors](#) **rel**=parent

The parent resource of this resource.

- **rel**=realm

This resource's realm reference to a [weblogic.management.security.RealmMBean](#) resource.

- **uri**=[/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/auditors/{name}](#) **rel**=self

This resource.

/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/authenticationProviderCreateForm

This resource manages the create forms for the authenticationProviders collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.security.authentication.AuthenticationProviderMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the authenticationProviders collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.security.authentication.AuthenticationProviderMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/authenticationProviderCreateForm](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/authenticationProviders](#) **rel=create**
The collection resource for this create form resource.
- [uri=/management/weblogic/{version}/edit/securityConfiguration/realms/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/authenticationProviderCreateForm](#) **rel=self**
This resource.

/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/authenticationProviders

This resource manages a collection of [weblogic.management.security.authentication.AuthenticationProviderMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.security.authentication.AuthenticationProviderMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.security.authentication.AuthenticationProviderMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/authenticationProviders](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/authenticationProviderCreateForm](#) **rel=create-form**
The create form resource for this collection resource.
- [uri=/management/weblogic/{version}/edit/securityConfiguration/realms/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/authenticationProviders](#) **rel=self**
This resource.

POST

Add a new [weblogic.management.security.authentication.AuthenticationProviderMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.security.authentication.AuthenticationProviderMBean](#) entity.

/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/authenticationProviders/{name}

This resource manages a [weblogic.management.security.authentication.AuthenticationProviderMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)

DELETE

DELETE

Delete this [weblogic.management.security.authentication.AuthenticationProviderMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.security.authentication.AuthenticationProviderMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.security.authentication.AuthenticationProviderMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/authenticationProviders/{name} **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/authenticationProviders **rel**=parent
The parent resource of this resource.
- **rel**=realm
This resource's realm reference to a [weblogic.management.security.RealmMBean](#) resource.
- **uri**=/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/authenticationProviders/{name} **rel**=self
This resource.

/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/authorizerCreateForm

This resource manages the create forms for the authorizers collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.security.authorization.AuthorizerMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the authorizers collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.security.authorization.AuthorizerMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/authorizerCreateForm rel=canonical](#)
This resource.
- [uri=/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/authorizers rel=create](#)
The collection resource for this create form resource.
- [uri=/management/weblogic/{version}/edit/securityConfiguration/realms/{name} rel=parent](#)
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/authorizerCreateForm rel=self](#)
This resource.

/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/authorizers

This resource manages a collection of [weblogic.management.security.authorization.AuthorizerMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.security.authorization.AuthorizerMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.security.authorization.AuthorizerMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/authorizers](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/authorizerCreateForm](#) **rel=create-form**
The create form resource for this collection resource.
- [uri=/management/weblogic/{version}/edit/securityConfiguration/realms/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/authorizers](#) **rel=self**
This resource.

POST

Add a new [weblogic.management.security.authorization.AuthorizerMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.security.authorization.AuthorizerMBean](#) entity.

/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/authorizers/{name}

This resource manages a [weblogic.management.security.authorization.AuthorizerMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)

DELETE

Delete this [weblogic.management.security.authorization.AuthorizerMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.security.authorization.AuthorizerMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.security.authorization.AuthorizerMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/authorizers/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/authorizers](#) **rel**=parent

The parent resource of this resource.

- **rel**=realm

This resource's realm reference to a [weblogic.management.security.RealmMBean](#) resource.

- **uri**=[/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/authorizers/{name}](#) **rel**=self

This resource.

/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/certPathProviderCreateForm

This resource manages the create forms for the certPathProviders collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.security.pk.CertPathProviderMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the certPathProviders collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.security.pk.CertPathProviderMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/certPathProviderCreateForm](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/certPathProviders](#) **rel=create**
The collection resource for this create form resource.
- [uri=/management/weblogic/{version}/edit/securityConfiguration/realms/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/certPathProviderCreateForm](#) **rel=self**
This resource.

/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/certPathProviders

This resource manages a collection of [weblogic.management.security.pk.CertPathProviderMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.security.pk.CertPathProviderMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.security.pk.CertPathProviderMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/certPathProviders](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/certPathProviderCreateForm](#) **rel=create-form**
The create form resource for this collection resource.
- [uri=/management/weblogic/{version}/edit/securityConfiguration/realms/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/certPathProviders](#) **rel=self**
This resource.

POST

Add a new [weblogic.management.security.pk.CertPathProviderMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.security.pk.CertPathProviderMBean](#) entity.

/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/certPathProviders/{name}

This resource manages a [weblogic.management.security.pk.CertPathProviderMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)

DELETE

DELETE

Delete this [weblogic.management.security.pk.CertPathProviderMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.security.pk.CertPathProviderMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.security.pk.CertPathProviderMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/certPathProviders/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/certPathProviders **rel**=parent

The parent resource of this resource.

- **rel**=realm

This resource's realm reference to a [weblogic.management.security.RealmMBean](#) resource.

- **uri**=/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/certPathProviders/{name} **rel**=self

This resource.

/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/credentialMapperCreateForm

This resource manages the create forms for the credentialMappers collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.security.credentials.CredentialMapperMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the credentialMappers collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.security.credentials.CredentialMapperMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/credentialMapperCreateForm](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/credentialMappers](#) **rel=create**
The collection resource for this create form resource.
- [uri=/management/weblogic/{version}/edit/securityConfiguration/realms/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/credentialMapperCreateForm](#) **rel=self**
This resource.

/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/credentialMappers

This resource manages a collection of [weblogic.management.security.credentials.CredentialMapperMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.security.credentials.CredentialMapperMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.security.credentials.CredentialMapperMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/credentialMappers](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/credentialMapperCreateForm](#) **rel=create-form**
The create form resource for this collection resource.
- [uri=/management/weblogic/{version}/edit/securityConfiguration/realms/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/credentialMappers](#) **rel=self**
This resource.

POST

Add a new [weblogic.management.security.credentials.CredentialMapperMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.security.credentials.CredentialMapperMBean](#) entity.

/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/credentialMappers/{name}

This resource manages a [weblogic.management.security.credentials.CredentialMapperMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)

DELETE

Delete this [weblogic.management.security.credentials.CredentialMapperMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.security.credentials.CredentialMapperMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.security.credentials.CredentialMapperMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/credentialMappers/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/credentialMappers](#) **rel**=parent

The parent resource of this resource.

- **rel**=realm

This resource's realm reference to a [weblogic.management.security.RealmMBean](#) resource.

- **uri**=[/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/credentialMappers/{name}](#) **rel**=self

This resource.

/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/passwordValidatorCreateForm

This resource manages the create forms for the passwordValidators collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.security.authentication.PasswordValidatorMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the passwordValidators collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.security.authentication.PasswordValidatorMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/passwordValidatorCreateForm](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/passwordValidators](#) **rel=create**
The collection resource for this create form resource.
- [uri=/management/weblogic/{version}/edit/securityConfiguration/realms/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/passwordValidatorCreateForm](#) **rel=self**
This resource.

/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/passwordValidators

This resource manages a collection of [weblogic.management.security.authentication.PasswordValidatorMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.security.authentication.PasswordValidatorMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.security.authentication.PasswordValidatorMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/passwordValidators](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/passwordValidatorCreateForm](#) **rel=create-form**
The create form resource for this collection resource.
- [uri=/management/weblogic/{version}/edit/securityConfiguration/realms/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/passwordValidators](#) **rel=self**
This resource.

POST

Add a new [weblogic.management.security.authentication.PasswordValidatorMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.security.authentication.PasswordValidatorMBean](#) entity.

/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/passwordValidators/{name}

This resource manages a [weblogic.management.security.authentication.PasswordValidatorMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)

DELETE

Delete this [weblogic.management.security.authentication.PasswordValidatorMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.security.authentication.PasswordValidatorMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.security.authentication.PasswordValidatorMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/passwordValidators/{name} rel=canonical](#)
This resource.
- [uri=/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/passwordValidators rel=parent](#)
The parent resource of this resource.
- [rel=realm](#)
This resource's realm reference to a [weblogic.management.security.RealmMBean](#) resource.
- [uri=/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/passwordValidators/{name} rel=self](#)
This resource.

/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/RDBMSSecurityStore

This resource manages a [weblogic.management.security.RDBMSSecurityStoreMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.security.RDBMSSecurityStoreMBean](#) instance.

Roles

Admin

Example

Example 1 Delete the weblogic.management.security.RDBMSSecurityStoreMBean Instance

This example uses the DELETE method to remove a [weblogic.management.security.RDBMSSecurityStoreMBean](#) instance.

Example Request

```
curl -v \  
--user admin:admin123 \  
-H X-Requested-By:MyClient \  
-H Accept:application/json \  
-X DELETE \  
http://localhost:7001/management/weblogic/latest/edit/securityConfiguration/realms/  
/myrealm/RDBMSSecurityStore
```

Example Response

```
HTTP/1.1 200 OK
```

```
Response Body:  
{}
```

GET

Get this [weblogic.management.security.RDBMSSecurityStoreMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.security.RDBMSSecurityStoreMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/RDBMSSecurityStore](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/RDBMSSecurityStoreCreateForm](#) **rel=create-form**

The create form resource for this optional singleton resource.

- [uri=/management/weblogic/{version}/edit/securityConfiguration/realms/{name}](#) **rel=parent**

The parent resource of this resource.

- **rel=realm**

This resource's realm reference to a [weblogic.management.security.RealmMBean](#) resource.

- [uri=/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/RDBMSSecurityStore](#) **rel=self**

This resource.

Example

Example 1 Viewing the [weblogic.management.security.RDBMSSecurityStoreMBean](#) Instance

This example uses the GET method to view this [weblogic.management.security.RDBMSSecurityStoreMBean](#) instance.

Example Request

```
curl -v \  
--user admin:admin123 \  
-H X-Requested-By:MyClient \  
-H Accept:application/json \  
-X GET \  
http://localhost:7001/management/weblogic/latest/edit/securityConfiguration/realms/  
myrealm/RDBMSSecurityStore
```

Example Response

```
HTTP/1.1 200 OK
```

Response Body:

```
{
```



```
    "links": [
      {
        "rel": "parent",
        "href":
"http://localhost:7001/management/weblogic/latest/edit/securityConfiguration/realms/myrealm"
      },
      {
        "rel": "realm",
        "href":
"http://localhost:7001/management/weblogic/latest/edit/securityConfiguration/realms/myrealm"
      },
      {
        "rel": "self",
        "href":
"http://localhost:7001/management/weblogic/latest/edit/securityConfiguration/realms/myrealm/RDBMSSecurityStore"
      },
      {
        "rel": "canonical",
        "href":
"http://localhost:7001/management/weblogic/latest/edit/securityConfiguration/realms/myrealm/RDBMSSecurityStore"
      },
      {
        "rel": "create-form",
        "href":
"http://localhost:7001/management/weblogic/latest/edit/securityConfiguration/realms/myrealm/RDBMSSecurityStoreCreateForm"
      }
    ],
    "identity": [
      "securityConfiguration",
      "realms",
      "myrealm",
      "RDBMSSecurityStore"
    ],
    "connectionProperties": null,
    "JMSTopicConnectionFactory": null,
    "password": null,
    "JMSTopic": null,
    "JNDIPassword": null,
    "name": "MyRDBMSSecurityStore",
    "JMSExceptionReconnectAttempts": 0,
    "connectionURL": "MyConnectionUrl",
    "driverName": "MyDriverName",
    "JNDIUsername": null,
    "notificationProperties": null,
    "username": "MyUserName",
    "realm": [
      "securityConfiguration",
      "realms",
      "myrealm"
    ]
  }
}
```

POST

Update this [weblogic.management.security.RDBMSSecurityStoreMBean](#) instance if it exists; otherwise, create it.

Roles

Admin

Request Body

Must contain a [weblogic.management.security.RDBMSSecurityStoreMBean](#) entity.

Example

Example 1 Create the weblogic.management.security.RDBMSSecurityStoreMBean Optional Singleton Instance

This example uses the POST method to create a `weblogic.management.security.RDBMSSecurityStoreMBean` optional singleton instance.

Example Request

```
curl -v \  
--user admin:admin123 \  
-H X-Requested-By:MyClient \  
-H Accept:application/json \  
-H Content-Type:application/json \  
-d "{  
  name:          'MyRDBMSSecurityStore',  
  connectionURL: 'MyConnectionUrl',  
  driverName:    'MyDriverName',  
  username:      'MyUserName'  
}" \  
-X POST  
http://localhost:7001/management/weblogic/latest/edit/securityConfiguration/realms  
/myrealm/RDBMSSecurityStore
```

Example Response

HTTP/1.1 201 Created

Location:

<http://localhost:7001/management/weblogic/latest/edit/securityConfiguration/realms/myrealm/RDBMSSecurityStore>

Response Body:

```
{}
```

Example 2 Update the weblogic.management.security.RDBMSSecurityStoreMBean Optional Singleton Instance

This example uses the POST method to update a `weblogic.management.security.RDBMSSecurityStoreMBean` optional singleton instance.

Example Request

```
curl -v \  
--user admin:admin123 \  
-H X-Requested-By:MyClient \  
-H Accept:application/json \  
-H Content-Type:application/json \  
-d "{  
  driverName: 'YourDriverName',  
  username: 'YourUserName'  
}" \  
-X POST  
http://localhost:7001/management/weblogic/latest/edit/securityConfiguration/realms  
/myrealm/RDBMSSecurityStore
```

Example Response

```
HTTP/1.1 200 OK
```

```
Response Body:  
{}
```

/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/RDBMSSecurityStoreCreateForm

This resource manages the create forms for the RDBMSSecurityStore optional singleton instance.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.security.RDBMSSecurityStoreMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the RDBMSSecurityStore optional singleton resource to create a new instance if it currently does not exist.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.security.RDBMSSecurityStoreMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/RDBMSSecurityStoreCreateForm rel=canonical](#)
This resource.
- [uri=/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/RDBMSSecurityStoreCreateForm rel=create](#)
The optional singleton resource for this create form resource.
- [uri=/management/weblogic/{version}/edit/securityConfiguration/realms/{name} rel=parent](#)
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/RDBMSSecurityStoreCreateForm rel=self](#)
This resource.

Example

Example 1 Get a weblogic.management.security.RDBMSSecurityStoreMBean Create Form

This example uses the GET method to retrieve a pre-populated [weblogic.management.security.RDBMSSecurityStoreMBean](#) entity that can be modified and posted (using the POST method) to corresponding singleton to create a new [weblogic.management.security.RDBMSSecurityStoreMBean](#) instance.

Example Request

```
curl -v \  
--user admin:admin123 \  
-H X-Requested-By:MyClient \  
-H Accept:application/json \  
-X GET \  
http://localhost:7001/management/weblogic/latest/edit/securityConfiguration/realms/myrealm/RDBMSSecurityStoreCreateForm
```

Example Response

```
HTTP/1.1 200 OK
```

Response Body:

```
{
  "links": [
    {
      "rel": "parent",
      "href":
"http://localhost:7001/management/weblogic/latest/edit/securityConfiguration/real
ms/myrealm"
    },
    {
      "rel": "self",
      "href":
"http://localhost:7001/management/weblogic/latest/edit/securityConfiguration/real
ms/myrealm/RDBMSSecurityStoreCreateForm"
    },
    {
      "rel": "canonical",
      "href":
"http://localhost:7001/management/weblogic/latest/edit/securityConfiguration/real
ms/myrealm/RDBMSSecurityStoreCreateForm"
    },
    {
      "rel": "create",
      "href":
"http://localhost:7001/management/weblogic/latest/edit/securityConfiguration/real
ms/myrealm/RDBMSSecurityStore"
    }
  ],
  "connectionProperties": null,
  "JMSTopicConnectionFactory": null,
  "password": null,
  "JMSTopic": null,
  "JNDIPassword": null,
  "JMSEExceptionReconnectAttempts": 0,
  "connectionURL": null,
  "driverName": null,
  "JNDIUsername": null,
  "notificationProperties": null,
  "username": null,
  "name": null
}
```

/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/roleMapperCreateForm

This resource manages the create forms for the roleMappers collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.security.authorization.RoleMapperMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the roleMappers collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.security.authorization.RoleMapperMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/roleMapperCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/roleMappers](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/securityConfiguration/realms/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/roleMapperCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/roleMappers

This resource manages a collection of [weblogic.management.security.authorization.RoleMapperMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.security.authorization.RoleMapperMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.security.authorization.RoleMapperMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/roleMappers](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/roleMapperCreateForm](#) **rel**=create-form

The create form resource for this collection resource.

- **uri**=[/management/weblogic/{version}/edit/securityConfiguration/realms/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/roleMappers](#) **rel**=self

This resource.

POST

Add a new [weblogic.management.security.authorization.RoleMapperMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.security.authorization.RoleMapperMBean](#) entity.

/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/roleMappers/{name}

This resource manages a [weblogic.management.security.authorization.RoleMapperMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)

DELETE

Delete this [weblogic.management.security.authorization.RoleMapperMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.security.authorization.RoleMapperMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.security.authorization.RoleMapperMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/roleMappers/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/roleMappers](#) **rel**=parent

The parent resource of this resource.

- **rel**=realm

This resource's realm reference to a [weblogic.management.security.RealmMBean](#) resource.

- **uri**=[/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/roleMappers/{name}](#) **rel**=self

This resource.

/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/userLockoutManager

This resource manages a [weblogic.management.security.authentication.UserLockoutManagerMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.security.authentication.UserLockoutManagerMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.security.authentication.UserLockoutManagerMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/userLockoutManager](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/securityConfiguration/realms/{name}](#) **rel**=parent

The parent resource of this resource.

- **rel**=realm

This resource's realm reference to a [weblogic.management.security.RealmMBean](#) resource.

- **uri**=[/management/weblogic/{version}/edit/securityConfiguration/realms/{name}/userLockoutManager](#) **rel**=self

This resource.

POST

Update this [weblogic.management.security.authentication.UserLockoutManagerMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.security.authentication.UserLockoutManagerMBean](#) entity.

/management/weblogic/{version}/edit/securityConfiguration/secureMode

This resource manages a [weblogic.management.configuration.SecureModeMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.SecureModeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SecureModeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/securityConfiguration/secureMode](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/securityConfiguration](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/securityConfiguration/secureMode](#)
rel=self
This resource.

POST

POST

Update this [weblogic.management.configuration.SecureModeMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.SecureModeMBean](#) entity.

/management/weblogic/{version}/edit/selfTuning

This resource manages a [weblogic.management.configuration.SelfTuningMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.SelfTuningMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SelfTuningMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/selfTuning](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/selfTuning/capacities](#) **rel**=capacities
This resource's capacities collection resource.
- **uri**=[/management/weblogic/{version}/edit/selfTuning/capacityCreateForm](#)
rel=capacityCreateForm
The create form resource for this resource's capacities collection resource.
- **uri**=[/management/weblogic/{version}/edit/selfTuning/contextRequestClassCreateForm](#) **rel**=contextRequestClassCreateForm
The create form resource for this resource's contextRequestClasses collection resource.
- **uri**=[/management/weblogic/{version}/edit/selfTuning/contextRequestClasses](#)
rel=contextRequestClasses
This resource's contextRequestClasses collection resource.
- **uri**=[/management/weblogic/{version}/edit/selfTuning/fairShareRequestClassCreateForm](#) **rel**=fairShareRequestClassCreateForm
The create form resource for this resource's fairShareRequestClasses collection resource.
- **uri**=[/management/weblogic/{version}/edit/selfTuning/fairShareRequestClasses](#)
rel=fairShareRequestClasses
This resource's fairShareRequestClasses collection resource.
- **uri**=[/management/weblogic/{version}/edit/selfTuning/maxThreadsConstraintCreateForm](#) **rel**=maxThreadsConstraintCreateForm
The create form resource for this resource's maxThreadsConstraints collection resource.
- **uri**=[/management/weblogic/{version}/edit/selfTuning/maxThreadsConstraints](#)
rel=maxThreadsConstraints
This resource's maxThreadsConstraints collection resource.
- **uri**=[/management/weblogic/{version}/edit/selfTuning/minThreadsConstraintCreateForm](#) **rel**=minThreadsConstraintCreateForm
The create form resource for this resource's minThreadsConstraints collection resource.

- **uri**=/management/weblogic/{version}/edit/selfTuning/minThreadsConstraints
rel=minThreadsConstraints
This resource's minThreadsConstraints collection resource.
- **uri**=/management/weblogic/{version}/edit **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/edit/selfTuning/responseTimeRequestClass
CreateForm **rel**=responseTimeRequestClassCreateForm
The create form resource for this resource's responseTimeRequestClasses collection resource.
- **uri**=/management/weblogic/{version}/edit/selfTuning/responseTimeRequestClass
es **rel**=responseTimeRequestClasses
This resource's responseTimeRequestClasses collection resource.
- **uri**=/management/weblogic/{version}/edit/selfTuning **rel**=self
This resource.
- **uri**=/management/weblogic/{version}/edit/selfTuning/workManagerCreateForm
rel=workManagerCreateForm
The create form resource for this resource's workManagers collection resource.
- **uri**=/management/weblogic/{version}/edit/selfTuning/workManagers
rel=workManagers
This resource's workManagers collection resource.

POST

POST

Update this [weblogic.management.configuration.SelfTuningMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.SelfTuningMBean](#) entity.

/management/weblogic/{version}/edit/selfTuning/capacities

This resource manages a collection of [weblogic.management.configuration.CapacityMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.CapacityMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.CapacityMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/selfTuning/capacities](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/selfTuning/capacityCreateForm](#)
rel=create-form
The create form resource for this collection resource.
- **uri**=[/management/weblogic/{version}/edit/selfTuning](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/selfTuning/capacities](#) **rel**=self
This resource.

POST

Add a new [weblogic.management.configuration.CapacityMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.CapacityMBean](#) entity.

/management/weblogic/{version}/edit/selfTuning/capacities/{name}

This resource manages a [weblogic.management.configuration.CapacityMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.CapacityMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.CapacityMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.CapacityMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/selfTuning/capacities/{name}](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/selfTuning/capacities](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/selfTuning/capacities/{name}](#)
rel=self
This resource.

POST

Update this [weblogic.management.configuration.CapacityMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.CapacityMBean](#) entity.

/management/weblogic/{version}/edit/selfTuning/capacityCreateForm

This resource manages the create forms for the capacities collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.CapacityMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the capacities collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.CapacityMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/selfTuning/capacityCreateForm](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/selfTuning/capacities](#) **rel**=create
The collection resource for this create form resource.
- **uri**=[/management/weblogic/{version}/edit/selfTuning](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/selfTuning/capacityCreateForm](#)
rel=self
This resource.

/management/weblogic/{version}/edit/selfTuning/contextRequestClassCreateForm

This resource manages the create forms for the contextRequestClasses collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.ContextRequestClassMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the contextRequestClasses collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ContextRequestClassMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/selfTuning/contextRequestClassCreateForm rel=canonical](#)
This resource.
- [uri=/management/weblogic/{version}/edit/selfTuning/contextRequestClasses rel=create](#)
The collection resource for this create form resource.
- [uri=/management/weblogic/{version}/edit/selfTuning rel=parent](#)
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/selfTuning/contextRequestClassCreateForm rel=self](#)
This resource.

/management/weblogic/{version}/edit/selfTuning/contextRequestClasses

This resource manages a collection of [weblogic.management.configuration.ContextRequestClassMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.ContextRequestClassMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.ContextRequestClassMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/selfTuning/contextRequestClasses](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/selfTuning/contextRequestClassCreateForm](#) **rel**=create-form
The create form resource for this collection resource.
- **uri**=[/management/weblogic/{version}/edit/selfTuning](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/selfTuning/contextRequestClasses](#)
rel=self
This resource.

POST

Add a new [weblogic.management.configuration.ContextRequestClassMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.ContextRequestClassMBean](#) entity.

/management/weblogic/{version}/edit/selfTuning/contextRequestClasses/{name}

This resource manages a [weblogic.management.configuration.ContextRequestClassMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

DELETE

Delete this [weblogic.management.configuration.ContextRequestClassMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.ContextRequestClassMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ContextRequestClassMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/selfTuning/contextRequestClasses/{name}](#) [rel=canonical](#)
This resource.
- [uri=/management/weblogic/{version}/edit/selfTuning/contextRequestClasses/{name}/contextCaseCreateForm](#) [rel=contextCaseCreateForm](#)
The create form resource for this resource's contextCases collection resource.
- [uri=/management/weblogic/{version}/edit/selfTuning/contextRequestClasses/{name}/contextCases](#) [rel=contextCases](#)
This resource's contextCases collection resource.
- [uri=/management/weblogic/{version}/edit/selfTuning/contextRequestClasses](#) [rel=parent](#)
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/selfTuning/contextRequestClasses/{name}](#) [rel=self](#)
This resource.

POST

Update this [weblogic.management.configuration.ContextRequestClassMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.ContextRequestClassMBean](#) entity.

/management/weblogic/{version}/edit/selfTuning/contextRequestClasses/{name}/contextCaseCreateForm

This resource manages the create forms for the contextCases collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.ContextCaseMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the contextCases collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ContextCaseMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/selfTuning/contextRequestClasses/{name}/contextCaseCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/selfTuning/contextRequestClasses/{name}/contextCases](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/selfTuning/contextRequestClasses/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/selfTuning/contextRequestClasses/{name}/contextCaseCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/selfTuning/contextRequestClasses/{name}/contextCases

This resource manages a collection of [weblogic.management.configuration.ContextCaseMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.ContextCaseMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.ContextCaseMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/selfTuning/contextRequestClasses/{name}/contextCases](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/selfTuning/contextRequestClasses/{name}/contextCaseCreateForm](#) **rel**=create-form

The create form resource for this collection resource.

- **uri**=[/management/weblogic/{version}/edit/selfTuning/contextRequestClasses/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/selfTuning/contextRequestClasses/{name}/contextCases](#) **rel**=self

This resource.

POST

Add a new [weblogic.management.configuration.ContextCaseMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.ContextCaseMBean](#) entity.

/management/weblogic/{version}/edit/selfTuning/contextRequestClasses/{name}/contextCases/{name}

This resource manages a [weblogic.management.configuration.ContextCaseMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.ContextCaseMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.ContextCaseMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ContextCaseMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/selfTuning/contextRequestClasses/{name}/contextCases/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/selfTuning/contextRequestClasses/{name}/contextCases/{name}/fairShareRequestClass](#) **rel**=fairShareRequestClass

This resource's fairShareRequestClass singleton resource.

- **uri**=[/management/weblogic/{version}/edit/selfTuning/contextRequestClasses/{name}/contextCases/{name}/fairShareRequestClassCreateForm](#)
rel=fairShareRequestClassCreateForm

The create form resource for this resource's fairShareRequestClass optional singleton resource.

- **uri**=[/management/weblogic/{version}/edit/selfTuning/contextRequestClasses/{name}/contextCases](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/selfTuning/contextRequestClasses/{name}/contextCases/{name}/responseTimeRequestClass](#)
rel=responseTimeRequestClass

This resource's responseTimeRequestClass singleton resource.

- **uri**=[/management/weblogic/{version}/edit/selfTuning/contextRequestClasses/{name}/contextCases/{name}/responseTimeRequestClassCreateForm](#)
rel=responseTimeRequestClassCreateForm

The create form resource for this resource's responseTimeRequestClass optional singleton resource.

- **uri**=[/management/weblogic/{version}/edit/selfTuning/contextRequestClasses/{name}/contextCases/{name}](#) **rel**=self

This resource.

POST

Update this [weblogic.management.configuration.ContextCaseMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.ContextCaseMBean](#) entity.

/management/weblogic/{version}/edit/selfTuning/contextRequestClasses/{name}/contextCases/{name}/fairShareRequestClass

This resource manages a [weblogic.management.configuration.FairShareRequestClassMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.FairShareRequestClassMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.FairShareRequestClassMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.FairShareRequestClassMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/selfTuning/contextRequestClasses/{name}/contextCases/{name}/fairShareRequestClass **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/selfTuning/contextRequestClasses/{name}/contextCases/{name}/fairShareRequestClassCreateForm **rel**=create-form

The create form resource for this optional singleton resource.

- **uri**=/management/weblogic/{version}/edit/selfTuning/contextRequestClasses/{name}/contextCases/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/selfTuning/contextRequestClasses/{name}/contextCases/{name}/fairShareRequestClass **rel**=self

This resource.

POST

Update this [weblogic.management.configuration.FairShareRequestClassMBean](#) instance if it exists; otherwise, create it.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.FairShareRequestClassMBean](#) entity.

/management/weblogic/{version}/edit/selfTuning/contextRequestClasses/{name}/contextCases/{name}/fairShareRequestClassCreateForm

This resource manages the create forms for the fairShareRequestClass optional singleton instance.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.FairShareRequestClassMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the [fairShareRequestClass](#) optional singleton resource to create a new instance if it currently does not exist.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.FairShareRequestClassMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/selfTuning/contextRequestClasses/{name}/contextCases/{name}/fairShareRequestClassCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/selfTuning/contextRequestClasses/{name}/contextCases/{name}/fairShareRequestClassCreateForm](#) **rel=create**

The optional singleton resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/selfTuning/contextRequestClasses/{name}/contextCases/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/selfTuning/contextRequestClasses/{name}/contextCases/{name}/fairShareRequestClassCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/selfTuning/contextRequestClasses/{name}/contextCases/{name}/responseTimeRequestClass

This resource manages a [weblogic.management.configuration.ResponseTimeRequestClassMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.ResponseTimeRequestClassMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.ResponseTimeRequestClassMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ResponseTimeRequestClassMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/selfTuning/contextRequestClasses/{name}/contextCases/{name}/responseTimeRequestClass](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/selfTuning/contextRequestClasses/{name}/contextCases/{name}/responseTimeRequestClassCreateForm](#) **rel**=create-form

The create form resource for this optional singleton resource.

- **uri**=[/management/weblogic/{version}/edit/selfTuning/contextRequestClasses/{name}/contextCases/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/selfTuning/contextRequestClasses/{name}/contextCases/{name}/responseTimeRequestClass](#) **rel**=self

This resource.

POST

Update this [weblogic.management.configuration.ResponseTimeRequestClassMBean](#) instance if it exists; otherwise, create it.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.ResponseTimeRequestClassMBean](#) entity.

/management/weblogic/{version}/edit/selfTuning/contextRequestClasses/{name}/contextCases/{name}/responseTimeRequestClassCreateForm

This resource manages the create forms for the responseTimeRequestClass optional singleton instance.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.ResponseTimeRequestClassMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the [responseTimeRequestClass](#) optional singleton resource to create a new instance if it currently does not exist.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ResponseTimeRequestClassMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/selfTuning/contextRequestClasses/{name}/contextCases/{name}/responseTimeRequestClassCreateForm](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/selfTuning/contextRequestClasses/{name}/contextCases/{name}/responseTimeRequestClassCreateForm](#) **rel=create**
The optional singleton resource for this create form resource.
- [uri=/management/weblogic/{version}/edit/selfTuning/contextRequestClasses/{name}/contextCases/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/selfTuning/contextRequestClasses/{name}/contextCases/{name}/responseTimeRequestClassCreateForm](#) **rel=self**
This resource.

/management/weblogic/{version}/edit/selfTuning/fairShareRequestClassCreateForm

This resource manages the create forms for the fairShareRequestClasses collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.FairShareRequestClassMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the `fairShareRequestClasses` collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.FairShareRequestClassMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/selfTuning/fairShareRequestClassCreateForm](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/selfTuning/fairShareRequestClasses](#) **rel**=create
The collection resource for this create form resource.
- **uri**=[/management/weblogic/{version}/edit/selfTuning](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/selfTuning/fairShareRequestClassCreateForm](#) **rel**=self
This resource.

/management/weblogic/{version}/edit/selfTuning/fairShareRequestClasses

This resource manages a collection of [weblogic.management.configuration.FairShareRequestClassMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.FairShareRequestClassMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.FairShareRequestClassMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/selfTuning/fairShareRequestClasses](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/selfTuning/fairShareRequestClassCreateForm](#) **rel**=create-form
The create form resource for this collection resource.
- **uri**=[/management/weblogic/{version}/edit/selfTuning](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/selfTuning/fairShareRequestClasses](#)
rel=self
This resource.

POST

Add a new [weblogic.management.configuration.FairShareRequestClassMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.FairShareRequestClassMBean](#) entity.

/management/weblogic/{version}/edit/selfTuning/fairShareRequestClasses/{name}

This resource manages a [weblogic.management.configuration.FairShareRequestClassMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.FairShareRequestClassMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.FairShareRequestClassMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.FairShareRequestClassMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/selfTuning/fairShareRequestClasses/{name}](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/selfTuning/fairShareRequestClasses](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/selfTuning/fairShareRequestClasses/{name}](#) **rel=self**
This resource.

POST

Update this [weblogic.management.configuration.FairShareRequestClassMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.FairShareRequestClassMBean](#) entity.

/management/weblogic/{version}/edit/selfTuning/maxThreadsConstraintCreateForm

This resource manages the create forms for the maxThreadsConstraints collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.MaxThreadsConstraintMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the `maxThreadsConstraints` collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.MaxThreadsConstraintMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/selfTuning/maxThreadsConstraintCreateForm](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/selfTuning/maxThreadsConstraints](#) **rel=create**
The collection resource for this create form resource.
- [uri=/management/weblogic/{version}/edit/selfTuning](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/selfTuning/maxThreadsConstraintCreateForm](#) **rel=self**
This resource.

/management/weblogic/{version}/edit/selfTuning/maxThreadsConstraints

This resource manages a collection of [weblogic.management.configuration.MaxThreadsConstraintMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.MaxThreadsConstraintMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.MaxThreadsConstraintMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/selfTuning/maxThreadsConstraints](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/selfTuning/maxThreadsConstraintCreateForm](#) **rel**=create-form
The create form resource for this collection resource.
- **uri**=[/management/weblogic/{version}/edit/selfTuning](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/selfTuning/maxThreadsConstraints](#)
rel=self
This resource.

POST

Add a new [weblogic.management.configuration.MaxThreadsConstraintMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.MaxThreadsConstraintMBean](#) entity.

/management/weblogic/{version}/edit/selfTuning/maxThreadsConstraints/{name}

This resource manages a [weblogic.management.configuration.MaxThreadsConstraintMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.MaxThreadsConstraintMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.MaxThreadsConstraintMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.MaxThreadsConstraintMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/selfTuning/maxThreadsConstraints/{name}](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/selfTuning/maxThreadsConstraints](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/selfTuning/maxThreadsConstraints/{name}](#) **rel**=self
This resource.

POST

Update this [weblogic.management.configuration.MaxThreadsConstraintMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.MaxThreadsConstraintMBean](#) entity.

/management/weblogic/{version}/edit/selfTuning/minThreadsConstraintCreateForm

This resource manages the create forms for the minThreadsConstraints collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.MinThreadsConstraintMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the minThreadsConstraints collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.MinThreadsConstraintMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/selfTuning/minThreadsConstraintCreateForm](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/selfTuning/minThreadsConstraints](#) **rel**=create
The collection resource for this create form resource.
- **uri**=[/management/weblogic/{version}/edit/selfTuning](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/selfTuning/minThreadsConstraintCreateForm](#) **rel**=self
This resource.

/management/weblogic/{version}/edit/selfTuning/minThreadsConstraints

This resource manages a collection of [weblogic.management.configuration.MinThreadsConstraintMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.MinThreadsConstraintMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.MinThreadsConstraintMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/selfTuning/minThreadsConstraints](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/selfTuning/minThreadsConstraintCreateForm](#) **rel**=create-form
The create form resource for this collection resource.
- **uri**=[/management/weblogic/{version}/edit/selfTuning](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/selfTuning/minThreadsConstraints](#)
rel=self
This resource.

POST

Add a new [weblogic.management.configuration.MinThreadsConstraintMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.MinThreadsConstraintMBean](#) entity.

/management/weblogic/{version}/edit/selfTuning/minThreadsConstraints/{name}

This resource manages a [weblogic.management.configuration.MinThreadsConstraintMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.MinThreadsConstraintMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.MinThreadsConstraintMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.MinThreadsConstraintMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/selfTuning/minThreadsConstraints/{name}](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/selfTuning/minThreadsConstraints](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/selfTuning/minThreadsConstraints/{name}](#) **rel**=self
This resource.

POST

Update this [weblogic.management.configuration.MinThreadsConstraintMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.MinThreadsConstraintMBean](#) entity.

/management/weblogic/{version}/edit/selfTuning/responseTimeRequestClass CreateForm

This resource manages the create forms for the responseTimeRequestClasses collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.ResponseTimeRequestClassMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the responseTimeRequestClasses collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ResponseTimeRequestClassMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/selfTuning/responseTimeRequestClassCreateForm](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/selfTuning/responseTimeRequestClasses](#) **rel=create**
The collection resource for this create form resource.
- [uri=/management/weblogic/{version}/edit/selfTuning](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/selfTuning/responseTimeRequestClassCreateForm](#) **rel=self**
This resource.

/management/weblogic/{version}/edit/selfTuning/responseTimeRequestClasses

This resource manages a collection of [weblogic.management.configuration.ResponseTimeRequestClassMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.ResponseTimeRequestClassMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.ResponseTimeRequestClassMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/selfTuning/responseTimeRequestClasses](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/selfTuning/responseTimeRequestClassCreateForm](#) **rel**=create-form
The create form resource for this collection resource.
- **uri**=[/management/weblogic/{version}/edit/selfTuning](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/selfTuning/responseTimeRequestClasses](#) **rel**=self
This resource.

POST

Add a new [weblogic.management.configuration.ResponseTimeRequestClassMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.ResponseTimeRequestClassMBean](#) entity.

/management/weblogic/{version}/edit/selfTuning/responseTimeRequestClasses/{name}

This resource manages a [weblogic.management.configuration.ResponseTimeRequestClassMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.ResponseTimeRequestClassMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.ResponseTimeRequestClassMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ResponseTimeRequestClassMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/selfTuning/responseTimeRequestClasses/{name}](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/selfTuning/responseTimeRequestClasses](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/selfTuning/responseTimeRequestClasses/{name}](#) **rel**=self
This resource.

POST

Update this [weblogic.management.configuration.ResponseTimeRequestClassMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.ResponseTimeRequestClassMBean](#) entity.

/management/weblogic/{version}/edit/selfTuning/workManagerCreateForm

This resource manages the create forms for the workManagers collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.WorkManagerMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the workManagers collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.WorkManagerMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/selfTuning/workManagerCreateForm](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/selfTuning/workManagers](#)
rel=create
The collection resource for this create form resource.
- **uri**=[/management/weblogic/{version}/edit/selfTuning](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/selfTuning/workManagerCreateForm](#)
rel=self
This resource.

/management/weblogic/{version}/edit/selfTuning/workManagers

This resource manages a collection of [weblogic.management.configuration.WorkManagerMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.WorkManagerMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.WorkManagerMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/selfTuning/workManagers](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/selfTuning/workManagerCreateForm](#)
rel=create-form
The create form resource for this collection resource.
- **uri**=[/management/weblogic/{version}/edit/selfTuning](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/selfTuning/workManagers](#) **rel**=self
This resource.

POST

POST

Add a new [weblogic.management.configuration.WorkManagerMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.WorkManagerMBean](#) entity.

/management/weblogic/{version}/edit/selfTuning/workManagers/{name}

This resource manages a [weblogic.management.configuration.WorkManagerMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

DELETE

Delete this [weblogic.management.configuration.WorkManagerMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.WorkManagerMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.WorkManagerMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/selfTuning/workManagers/{name}](#)
rel=canonical
This resource.
- **rel**=capacity
This resource's capacity reference to a [weblogic.management.configuration.CapacityMBean](#) resource.
- **rel**=contextRequestClass
This resource's contextRequestClass reference to a [weblogic.management.configuration.ContextRequestClassMBean](#) resource.
- **rel**=fairShareRequestClass
This resource's fairShareRequestClass reference to a [weblogic.management.configuration.FairShareRequestClassMBean](#) resource.
- **rel**=maxThreadsConstraint
This resource's maxThreadsConstraint reference to a [weblogic.management.configuration.MaxThreadsConstraintMBean](#) resource.
- **rel**=minThreadsConstraint
This resource's minThreadsConstraint reference to a [weblogic.management.configuration.MinThreadsConstraintMBean](#) resource.
- **uri**=[/management/weblogic/{version}/edit/selfTuning/workManagers](#)
rel=parent
The parent resource of this resource.
- **rel**=responseTimeRequestClass
This resource's responseTimeRequestClass reference to a [weblogic.management.configuration.ResponseTimeRequestClassMBean](#) resource.
- **uri**=[/management/weblogic/{version}/edit/selfTuning/workManagers/{name}](#)
rel=self
This resource.
- **uri**=[/management/weblogic/{version}/edit/selfTuning/workManagers/{name}/workManagerShutdownTrigger](#) **rel**=workManagerShutdownTrigger
This resource's workManagerShutdownTrigger singleton resource.

- **uri**=/management/weblogic/{version}/edit/selfTuning/workManagers/{name}/workManagerShutdownTriggerCreateForm
rel=workManagerShutdownTriggerCreateForm

The create form resource for this resource's workManagerShutdownTrigger optional singleton resource.

POST

Update this [weblogic.management.configuration.WorkManagerMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.WorkManagerMBean](#) entity.

/management/weblogic/{version}/edit/selfTuning/workManagers/{name}/workManagerShutdownTrigger

This resource manages a [weblogic.management.configuration.WorkManagerShutdownTriggerMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this

[weblogic.management.configuration.WorkManagerShutdownTriggerMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.WorkManagerShutdownTriggerMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.WorkManagerShutdownTriggerMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/selfTuning/workManagers/{name}/workManagerShutdownTrigger](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/selfTuning/workManagers/{name}/workManagerShutdownTriggerCreateForm](#) **rel**=create-form

The create form resource for this optional singleton resource.

- **uri**=[/management/weblogic/{version}/edit/selfTuning/workManagers/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/selfTuning/workManagers/{name}/workManagerShutdownTrigger](#) **rel**=self

This resource.

POST

Update this [weblogic.management.configuration.WorkManagerShutdownTriggerMBean](#) instance if it exists; otherwise, create it.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.WorkManagerShutdownTriggerMBean](#) entity.

/management/weblogic/{version}/edit/selfTuning/workManagers/{name}/workManagerShutdownTriggerCreateForm

This resource manages the create forms for the workManagerShutdownTrigger optional singleton instance.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.WorkManagerShutdownTriggerMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the `workManagerShutdownTrigger` optional singleton resource to create a new instance if it currently does not exist.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.WorkManagerShutdownTriggerMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/selfTuning/workManagers/{name}/workManagerShutdownTriggerCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/selfTuning/workManagers/{name}/workManagerShutdownTriggerCreateForm](#) **rel=create**

The optional singleton resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/selfTuning/workManagers/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/selfTuning/workManagers/{name}/workManagerShutdownTriggerCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/servercreateForm

This resource manages the create forms for the servers collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.ServerMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the servers collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ServerMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/serverCreateForm](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/servers](#) **rel**=create
The collection resource for this create form resource.
- **uri**=[/management/weblogic/{version}/edit](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/serverCreateForm](#) **rel**=self
This resource.

Example

Example 1 Get a [weblogic.management.configuration.ServerMBean](#) Create Form

This example uses the GET method to retrieve a pre-populated [weblogic.management.configuration.ServerMBean](#) entity that can be modified and posted (using the POST method) to the corresponding collection to create a new [weblogic.management.configuration.ServerMBean](#) instance in the collection.

Example Request

```
curl -v \  
--user admin:admin123 \  
-H X-Requested-By:MyClient \  
-H Accept:application/json \  
-X GET http://localhost:7001/management/weblogic/latest/edit/serverCreateForm
```

Example Response

```
HTTP/1.1 200 OK
```

Response Body:

```
{  
  "links": [  
    {  
      "rel": "parent",  
      "href": "http://localhost:7001/management/weblogic/latest/edit"  
    },  
    {
```

```
        "rel": "self",
        "href":
"http://localhost:7001/management/weblogic/latest/edit/servercreateForm"
    },
    {
        "rel": "canonical",
        "href":
"http://localhost:7001/management/weblogic/latest/edit/servercreateForm"
    },
    {
        "rel": "create",
        "href":
"http://localhost:7001/management/weblogic/latest/edit/servers"
    }
    ],
    "maxOpenSockCount": -1,
    "interfaceAddress": null,
    "startupTimeout": 0,
    "idleConnectionTimeout": 65,
    "resolveDNSName": false,
    "ignoreSessionsDuringShutdown": false,
    "adminReconnectIntervalSeconds": 10,
    "preferredSecondaryGroup": null,
    "defaultSecureProtocol": "t3s",
    "maxMessageSize": 10000000,
    "stagingDirectoryName": null,
    "outboundPrivateKeyEnabled": false,
    "defaultTGIOPassword": null,
    "httpTraceSupportEnabled": false,
    "classpathServletSecureModeEnabled": false,
    "tags": null,
    "useEnhancedIncrementAdvisor": true,
    "completeMessageTimeout": 60,
    "managedServerIndependenceEnabled": true,
    "isolatePartitionThreadLocals": false,
    "retryIntervalBeforeMSIMode": 5,
    "nativeIOEnabled": true,
    "startupMode": "RUNNING",
    "externalDNSName": null,
    "JMSConnectionFactoryUnmappedResRefMode": "ReturnDefault",
    "extraEjbcOptions": null,
    "autoMigrationEnabled": false,
    "tunnelingClientPingSecs": 45,
    "instrumentStackTraceEnabled": true,
    "customIdentityKeyStorePassPhrase": null,
    "gracefulShutdownTimeout": 0,
    "outboundEnabled": false,
    "javaStandardTrustKeyStorePassPhrase": null,
    "buzzAddress": null,
    "classpathServletDisabled": false,
    "healthCheckStartDelaySeconds": 120,
    "clientCertProxyEnabled": false,
    "defaultInternalServletsDisabled": false,
    "customIdentityKeyStoreType": null,
    "restartIntervalSeconds": 3600,
    "notes": null,
    "serverLifecycleTimeoutVal": 30,
    "httpdEnabled": true,
    "javaCompilerPostClassPath": null,
    "buzzPort": 0,
```

```
"keyStores": "DemoIdentityAndDemoTrust",
"defaultTGIOPUser": "guest",
"use81StyleExecuteQueues": false,
"uploadDirectoryName": null,
"tunnelingClientTimeoutSecs": 40,
"listenThreadStartDelaySecs": 60,
"tunnelingEnabled": false,
"listenAddress": null,
"acceptBacklog": 300,
"listenPortEnabled": true,
"eagerThreadLocalCleanup": false,
"connectTimeout": 0,
"printStackTraceInProduction": false,
"useFusionForLLR": false,
"clusterWeight": 100,
"customTrustKeyStorePassPhrase": null,
"restartDelaySeconds": 0,
"transactionLogFilePrefix": ".\\/",
"maxConcurrentLongRunningRequests": 100,
"customTrustKeyStoreFileName": null,
"socketReaders": -1,
"threadPoolPercentSocketReaders": 33,
"JDBCLoginTimeoutSeconds": 0,
"customTrustKeyStoreType": null,
"loginTimeoutMillis": 5000,
"messageIdPrefixEnabled": true,
"healthCheckIntervalSeconds": 180,
"useEnhancedPriorityQueueForRequestManager": false,
"reverseDNSAllowed": false,
"periodLength": 60000,
"socketBufferSizeAsChunkSize": false,
"JDBCLLRTableName": null,
"buzzEnabled": false,
"weblogicPluginEnabled": false,
"useDetailedThreadName": false,
"stuckThreadTimerInterval": 60,
"TGIOPEnabled": true,
"listenersBindEarly": false,
"JNDITransportableObjectFactoryList": null,
"NMSocketCreateTimeoutInMillis": 180000,
"DGCIdlePeriodsUntilTimeout": 5,
"defaultIIOPUser": null,
"logRemoteExceptionsEnabled": false,
"transactionLogFileWritePolicy": "Direct-Write",
"defaultProtocol": "t3",
"replicationPorts": null,
"autoRestart": true,
"extraRmicOptions": null,
"customIdentityKeyStoreFileName": null,
"restartMax": 2,
"replicationGroup": null,
"defaultIIOPPassword": null,
"IIOPEnabled": true,
"maxConcurrentNewThreads": 100,
"numOfRetriesBeforeMSIMode": 3,
"JMSDefaultConnectionFactoryEnabled": true,
"sitConfigPollingInterval": 5,
"allowShrinkingPriorityRequestQueue": true,
"COMEnabled": false,
"javaCompilerPreClassPath": null,
```

```
"idlePeriodsUntilTimeout": 4,  
"listenPort": 7001,  
"javaCompiler": "javac",  
"cluster": null,  
"reliableDeliveryPolicy": null,  
"machine": null,  
"XMLEntityCache": null,  
"XMLRegistry": null,  
"coherenceClusterSystemResource": null,  
"serverTemplate": null,  
"candidateMachines": [],  
"name": null  
}
```


/management/weblogic/{version}/edit/servers

This resource manages a collection of [weblogic.management.configuration.ServerMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.ServerMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.ServerMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/servers](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/servercreateForm](#) **rel**=create-form
The create form resource for this collection resource.
- **uri**=[/management/weblogic/{version}/edit](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/servers](#) **rel**=self
This resource.

Example

Example 1 View the [weblogic.management.configuration.ServerMBean](#) Collection

This example uses the GET method to display the [weblogic.management.configuration.ServerMBean](#) instances in this collection.

Example Request

```
curl -v \  
--user admin:admin123 \  
-H X-Requested-By:MyClient \  
-H Accept:application/json \  
-X GET  
http://localhost:7001/management/weblogic/latest/edit/servers?fields=name,listenPort,listenAddress,listenPortEnabled,machine,candidateMachines&links=self
```

Example Response

```
HTTP/1.1 200 OK
```

Response Body:

```
{  
  "links": [{  
    "rel": "self",  
    "href": "http://localhost:7001/management/weblogic/latest/edit/servers"  
  }],  
  "items": [  
    {  
      "links": [{  
        "rel": "self",  
        "href":
```

```
"http://localhost:7001/management/weblogic/latest/edit/servers/AdminServer"
  },
  "listenAddress": "localhost",
  "listenPortEnabled": true,
  "name": "AdminServer",
  "listenPort": 7001,
  "machine": null,
  "candidateMachines": []
},
{
  "links": [{
    "rel": "self",
    "href":
"http://localhost:7001/management/weblogic/latest/edit/servers/server1"
  }],
  "listenAddress": "lhost",
  "listenPortEnabled": true,
  "name": "server1",
  "listenPort": 7777,
  "machine": [
    "machines",
    "machine1"
  ],
  "candidateMachines": [
    { "identity": [
      "machines",
      "machine1"
    ] },
    { "identity": [
      "machines",
      "machine2"
    ] }
  ]
}
]
```

POST

Add a new [weblogic.management.configuration.ServerMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.ServerMBean](#) entity.

Example

Example 1 Create the [weblogic.management.configuration.ServerMBean](#) Instance

This example uses the POST method to create a new [weblogic.management.configuration.ServerMBean](#) instance in this collection.

Example Request

```
curl -v \  
--user admin:admin123 \  
-H X-Requested-By:MyClient \  
-H Accept:application/json \  
-H Content-Type:application/json \  
-d "{  
  name:          'server1',  
  listenPort:    7654,  
  listenAddress: 'lhost'  
}" \  
-X POST http://localhost:7001/management/weblogic/latest/edit/servers
```

Example Response

HTTP/1.1 201 Created

Location: <http://localhost:7001/management/weblogic/latest/edit/servers/server1>

Response Body:

```
{}
```

/management/weblogic/{version}/edit/servers/{name}

This resource manages a [weblogic.management.configuration.ServerMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.ServerMBean](#) instance.

Roles

Admin

Example

Example 1 Delete the weblogic.management.configuration.ServerMBean Instance

This example uses the DELETE method to remove a [weblogic.management.configuration.ServerMBean](#) instance.

Example Request

```
curl -v \  
--user admin:admin123 \  
-H X-Requested-By:MyClient \  
-H Accept:application/json \  
-X DELETE http://localhost:7001/management/weblogic/latest/edit/servers/server1
```

Example Response

```
HTTP/1.1 200 OK
```

```
Response Body:  
{}
```

GET

Get this [weblogic.management.configuration.ServerMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ServerMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/IIOP](#) **rel**=IIOP
This resource's IIOP singleton resource.
- **uri**=[/management/weblogic/{version}/edit/servers/{name}/JTAMigratableTarget](#) **rel**=JTAMigratableTarget
This resource's JTAMigratableTarget singleton resource.
- **uri**=[/management/weblogic/{version}/edit/servers/{name}/SSL](#) **rel**=SSL
This resource's SSL singleton resource.
- **rel**=XMLEntityCache
This resource's XMLEntityCache reference to a [weblogic.management.configuration.XMLEntityCacheMBean](#) resource.
- **rel**=XMLRegistry
This resource's XMLRegistry reference to a [weblogic.management.configuration.XMLRegistryMBean](#) resource.
- **uri**=[/management/weblogic/{version}/edit/servers/{name}](#) **rel**=canonical
This resource.
- **rel**=cluster
This resource's cluster reference to a [weblogic.management.configuration.ClusterMBean](#) resource.
- **rel**=coherenceClusterSystemResource
This resource's coherenceClusterSystemResource reference to a [weblogic.management.configuration.CoherenceClusterSystemResourceMBean](#) resource.
- **uri**=[/management/weblogic/{version}/edit/servers/{name}/coherenceMemberConfig](#) **rel**=coherenceMemberConfig
This resource's coherenceMemberConfig singleton resource.
- **uri**=[/management/weblogic/{version}/edit/servers/{name}/configurationProperties](#) **rel**=configurationProperties
This resource's configurationProperties collection resource.
- **uri**=[/management/weblogic/{version}/edit/servers/{name}/configurationPropertyCreateForm](#) **rel**=configurationPropertyCreateForm

The create form resource for this resource's configurationProperties collection resource.

- **uri**=/management/weblogic/{version}/edit/servers/{name}/dataSource
rel=dataSource
 This resource's dataSource singleton resource.
- **uri**=/management/weblogic/{version}/edit/servers/{name}/defaultFileStore
rel=defaultFileStore
 This resource's defaultFileStore singleton resource.
- **uri**=/management/weblogic/{version}/edit/servers/{name}/executeQueues
rel=executeQueues
 This resource's executeQueues collection resource.
- **uri**=/management/weblogic/{version}/edit/servers/{name}/federationServices
rel=federationServices
 This resource's federationServices singleton resource.
- **uri**=/management/weblogic/{version}/edit/servers/{name}/log **rel**=log
 This resource's log singleton resource.
- **rel**=machine
 This resource's machine reference to a weblogic.management.configuration.MachineMBean resource.
- **uri**=/management/weblogic/{version}/edit/servers/{name}/networkAccessPointCreateForm **rel**=networkAccessPointCreateForm
 The create form resource for this resource's networkAccessPoints collection resource.
- **uri**=/management/weblogic/{version}/edit/servers/{name}/networkAccessPoints
rel=networkAccessPoints
 This resource's networkAccessPoints collection resource.
- **uri**=/management/weblogic/{version}/edit/servers/{name}/overloadProtection
rel=overloadProtection
 This resource's overloadProtection singleton resource.
- **uri**=/management/weblogic/{version}/edit/servers **rel**=parent
 The parent resource of this resource.
- **rel**=reliableDeliveryPolicy
 This resource's reliableDeliveryPolicy reference to a weblogic.management.configuration.WSReliableDeliveryPolicyMBean resource.
- **uri**=/management/weblogic/{version}/edit/servers/{name} **rel**=self
 This resource.
- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDebug
rel=serverDebug
 This resource's serverDebug singleton resource.
- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig **rel**=serverDiagnosticConfig

This resource's serverDiagnosticConfig singleton resource.

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverStart
rel=serverStart

This resource's serverStart singleton resource.

- **rel**=serverTemplate

This resource's serverTemplate reference to a weblogic.management.configuration.ServerTemplateMBean resource.

- **uri**=/management/weblogic/{version}/edit/servers/{name}/singleSignOnServices
rel=singleSignOnServices

This resource's singleSignOnServices singleton resource.

- **uri**=/management/weblogic/{version}/edit/servers/{name}/transactionLogJDBCStore
rel=transactionLogJDBCStore

This resource's transactionLogJDBCStore singleton resource.

- **uri**=/management/weblogic/{version}/edit/servers/{name}/webServer
rel=webServer

This resource's webServer singleton resource.

- **uri**=/management/weblogic/{version}/edit/servers/{name}/webService
rel=webService

This resource's webService singleton resource.

Example

Example 1 Viewing the weblogic.management.configuration.ServerMBean Instance

This example uses the GET method to view this weblogic.management.configuration.ServerMBean instance.

Example Request

```
curl -v \  
--user admin:admin123 \  
-H X-Requested-By:MyClient \  
-H Accept:application/json \  
-X GET  
http://localhost:7001/management/weblogic/latest/edit/servers/server1?fields=name,  
listenPort,listenAddress,listenPortEnabled,machine,candidateMachines&links=self
```

Example Response

HTTP/1.1 200 OK

Response Body:

```
{  
  "links": [{  
    "rel": "self",  
    "href":  
"http://localhost:7001/management/weblogic/latest/edit/servers/server1"  
  }],  
  "listenAddress": "lhost",  
  "listenPortEnabled": true,  
  "name": "server1",  
  "listenPort": 7777,
```

```
"machine": [
  "machines",
  "machine1"
],
"candidateMachines": [
  {"identity": [
    "machines",
    "machine1"
  ]},
  {"identity": [
    "machines",
    "machine2"
  ]}
]
}
```

POST

Update this [weblogic.management.configuration.ServerMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.ServerMBean](#) entity.

Example

Example 1 Update the [weblogic.management.configuration.ServerMBean](#) Instance

This example uses the POST method to update this [weblogic.management.configuration.ServerMBean](#) instance.

Example Request

```
curl -v \  
--user admin:admin123 \  
-H X-Requested-By:MyClient \  
-H Accept:application/json \  
-H Content-Type:application/json \  
-d "{  
  listenPort:      7777,  
  machine:         [ 'machines', 'machine1' ],  
  candidateMachines: [  
    { identity: [ 'machines', 'machine1' ] },  
    { identity: [ 'machines', 'machine2' ] }  
  ]  
}" \  
-X POST http://localhost:7001/management/weblogic/latest/edit/servers/server1
```

Example Response

HTTP/1.1 200 OK

Response Body:

```
{}
```

/management/weblogic/{version}/edit/servers/{name}/coherenceMemberConfig

This resource manages a [weblogic.management.configuration.CoherenceMemberConfigMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.CoherenceMemberConfigMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.CoherenceMemberConfigMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/servers/{name}/coherenceMemberConfig rel=canonical](#)
This resource.
- [uri=/management/weblogic/{version}/edit/servers/{name} rel=parent](#)
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/servers/{name}/coherenceMemberConfig rel=self](#)
This resource.

POST

POST

Update this [weblogic.management.configuration.CoherenceMemberConfigMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.CoherenceMemberConfigMBean](#) entity.

/management/weblogic/{version}/edit/servers/{name}/configurationProperties

This resource manages a collection of [weblogic.management.configuration.ConfigurationPropertyMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.ConfigurationPropertyMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.ConfigurationPropertyMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/servers/{name}/configurationProperties](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/servers/{name}/configurationPropertyCreateForm](#) **rel=create-form**
The create form resource for this collection resource.
- [uri=/management/weblogic/{version}/edit/servers/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/servers/{name}/configurationProperties](#) **rel=self**
This resource.

POST

Add a new [weblogic.management.configuration.ConfigurationPropertyMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.ConfigurationPropertyMBean](#) entity.

/management/weblogic/{version}/edit/servers/{name}/configurationProperties/{name}

This resource manages a [weblogic.management.configuration.ConfigurationPropertyMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.ConfigurationPropertyMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.ConfigurationPropertyMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ConfigurationPropertyMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/configurationProperties/{name}](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/servers/{name}/configurationProperties](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/servers/{name}/configurationProperties/{name}](#) **rel**=self
This resource.

POST

Update this [weblogic.management.configuration.ConfigurationPropertyMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.ConfigurationPropertyMBean](#) entity.

/management/weblogic/{version}/edit/servers/{name}/configurationPropertyCreateForm

This resource manages the create forms for the configurationProperties collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.ConfigurationPropertyMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the configurationProperties collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ConfigurationPropertyMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/servers/{name}/configurationPropertyCreateForm](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/servers/{name}/configurationProperties](#) **rel=create**
The collection resource for this create form resource.
- [uri=/management/weblogic/{version}/edit/servers/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/servers/{name}/configurationPropertyCreateForm](#) **rel=self**
This resource.

/management/weblogic/{version}/edit/servers/{name}/dataSource

This resource manages a [weblogic.management.configuration.DataSourceMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.DataSourceMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.DataSourceMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/dataSource](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/servers/{name}/dataSource/dataSourceLogFile](#) **rel**=dataSourceLogFile
This resource's dataSourceLogFile singleton resource.
- **uri**=[/management/weblogic/{version}/edit/servers/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/servers/{name}/dataSource](#) **rel**=self
This resource.

POST

Update this [weblogic.management.configuration.DataSourceMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.DataSourceMBean](#) entity.

/management/weblogic/{version}/edit/servers/{name}/dataSource/dataSource LogFile

This resource manages a [weblogic.management.configuration.DataSourceLogFileMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.DataSourceLogFileMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.DataSourceLogFileMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/dataSource/dataSourceeLogFile](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/servers/{name}/dataSource](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/servers/{name}/dataSource/dataSourceeLogFile](#) **rel**=self
This resource.

POST

Update this [weblogic.management.configuration.DataSourceLogFileMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.DataSourceLogFileMBean](#) entity.

/management/weblogic/{version}/edit/servers/{name}/defaultFileStore

This resource manages a [weblogic.management.configuration.DefaultFileStoreMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.DefaultFileStoreMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.DefaultFileStoreMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/defaultFileStore](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/servers/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/servers/{name}/defaultFileStore](#)
rel=self
This resource.

POST

POST

Update this [weblogic.management.configuration.DefaultFileStoreMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.DefaultFileStoreMBean](#) entity.

/management/weblogic/{version}/edit/servers/{name}/executeQueues

This resource manages a collection of [weblogic.management.configuration.ExecuteQueueMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.configuration.ExecuteQueueMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.ExecuteQueueMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/executeQueues](#)
rel=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/servers/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/executeQueues](#)
rel=self

This resource.

/management/weblogic/{version}/edit/servers/{name}/executeQueues/{name}

This resource manages a [weblogic.management.configuration.ExecuteQueueMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.ExecuteQueueMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ExecuteQueueMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/executeQueues/{name}](#)
rel=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/executeQueues](#)
rel=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/executeQueues/{name}](#)
rel=self

This resource.

POST

Update this [weblogic.management.configuration.ExecuteQueueMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.ExecuteQueueMBean](#) entity.

/management/weblogic/{version}/edit/servers/{name}/federationServices

This resource manages a [weblogic.management.configuration.FederationServicesMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.FederationServicesMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.FederationServicesMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/federationServices](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/servers/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/servers/{name}/federationServices](#)
rel=self
This resource.

POST

POST

Update this [weblogic.management.configuration.FederationServicesMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.FederationServicesMBean](#) entity.

/management/weblogic/{version}/edit/servers/{name}/IOP

This resource manages a [weblogic.management.configuration.IOPMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.IIOPMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.IIOPMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/IIOP](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/servers/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/servers/{name}/IIOP](#) **rel**=self
This resource.

POST

Update this [weblogic.management.configuration.IOPMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.IOPMBean](#) entity.

/management/weblogic/{version}/edit/servers/{name}/JTAMigratableTarget

This resource manages a [weblogic.management.configuration.JTAMigratableTargetMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.JTAMigratableTargetMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.JTAMigratableTargetMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/JTAMigratableTarget](#)
rel=canonical
This resource.
- **rel**=cluster
This resource's cluster reference to a [weblogic.management.configuration.ClusterMBean](#) resource.
- **rel**=hostingServer
This resource's hostingServer reference to a [weblogic.management.configuration.ServerMBean](#) resource.
- **uri**=[/management/weblogic/{version}/edit/servers/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/servers/{name}/JTAMigratableTarget](#)
rel=self
This resource.
- **rel**=userPreferredServer
This resource's userPreferredServer reference to a [weblogic.management.configuration.ServerMBean](#) resource.

POST

POST

Update this [weblogic.management.configuration.JTAMigratableTargetMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.JTAMigratableTargetMBean](#) entity.

/management/weblogic/{version}/edit/servers/{name}/log

This resource manages a [weblogic.management.configuration.LogMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.LogMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.LogMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/log](#) **rel**=canonical
This resource.
- **rel**=domainLogBroadcastFilter
This resource's domainLogBroadcastFilter reference to a [weblogic.management.configuration.LogFilterMBean](#) resource.
- **rel**=logFileFilter
This resource's logFileFilter reference to a [weblogic.management.configuration.LogFilterMBean](#) resource.
- **uri**=[/management/weblogic/{version}/edit/servers/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/servers/{name}/log](#) **rel**=self
This resource.
- **rel**=stdoutFilter
This resource's stdoutFilter reference to a [weblogic.management.configuration.LogFilterMBean](#) resource.

POST

Update this [weblogic.management.configuration.LogMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.LogMBean](#) entity.

/management/weblogic/{version}/edit/servers/{name}/networkAccessPointCreateForm

This resource manages the create forms for the networkAccessPoints collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.NetworkAccessPointMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the `networkAccessPoints` collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.NetworkAccessPointMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/servers/{name}/networkAccessPointCreateForm](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/servers/{name}/networkAccessPoints](#) **rel=create**
The collection resource for this create form resource.
- [uri=/management/weblogic/{version}/edit/servers/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/servers/{name}/networkAccessPointCreateForm](#) **rel=self**
This resource.

/management/weblogic/{version}/edit/servers/{name}/networkAccessPoints

This resource manages a collection of [weblogic.management.configuration.NetworkAccessPointMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.NetworkAccessPointMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.NetworkAccessPointMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/networkAccessPoints](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/servers/{name}/networkAccessPointCreateForm](#) **rel**=create-form
The create form resource for this collection resource.
- **uri**=[/management/weblogic/{version}/edit/servers/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/servers/{name}/networkAccessPoints](#)
rel=self
This resource.

POST

Add a new [weblogic.management.configuration.NetworkAccessPointMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.NetworkAccessPointMBean](#) entity.

/management/weblogic/{version}/edit/servers/{name}/networkAccessPoints/{name}

This resource manages a [weblogic.management.configuration.NetworkAccessPointMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

DELETE

Delete this [weblogic.management.configuration.NetworkAccessPointMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.NetworkAccessPointMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.NetworkAccessPointMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/servers/{name}/networkAccessPoints/{name}](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/servers/{name}/networkAccessPoints](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/servers/{name}/networkAccessPoints/{name}](#) **rel=self**
This resource.

POST

Update this [weblogic.management.configuration.NetworkAccessPointMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.NetworkAccessPointMBean](#) entity.

/management/weblogic/{version}/edit/servers/{name}/overloadProtection

This resource manages a [weblogic.management.configuration.OverloadProtectionMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.OverloadProtectionMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.OverloadProtectionMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/overloadProtection](#)
rel=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/servers/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/overloadProtection](#)
rel=self

This resource.

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/overloadProtection/serverFailureTrigger](#) **rel**=serverFailureTrigger

This resource's serverFailureTrigger singleton resource.

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/overloadProtection/serverFailureTriggerCreateForm](#) **rel**=serverFailureTriggerCreateForm

The create form resource for this resource's serverFailureTrigger optional singleton resource.

POST

Update this [weblogic.management.configuration.OverloadProtectionMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.OverloadProtectionMBean](#) entity.

/management/weblogic/{version}/edit/servers/{name}/overloadProtection/serverFailureTrigger

This resource manages a [weblogic.management.configuration.ServerFailureTriggerMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.ServerFailureTriggerMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.ServerFailureTriggerMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ServerFailureTriggerMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/overloadProtection/serverFailureTrigger](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/overloadProtection/serverFailureTriggerCreateForm](#) **rel**=create-form

The create form resource for this optional singleton resource.

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/overloadProtection](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/overloadProtection/serverFailureTrigger](#) **rel**=self

This resource.

POST

Update this [weblogic.management.configuration.ServerFailureTriggerMBean](#) instance if it exists; otherwise, create it.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.ServerFailureTriggerMBean](#) entity.

/management/weblogic/{version}/edit/servers/{name}/overloadProtection/serverFailureTriggerCreateForm

This resource manages the create forms for the serverFailureTrigger optional singleton instance.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.ServerFailureTriggerMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the serverFailureTrigger optional singleton resource to create a new instance if it currently does not exist.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ServerFailureTriggerMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/servers/{name}/overloadProtection/serverFailureTriggerCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/servers/{name}/overloadProtection/serverFailureTriggerCreateForm](#) **rel=create**

The optional singleton resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/servers/{name}/overloadProtection](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/servers/{name}/overloadProtection/serverFailureTriggerCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/servers/{name}/serverDebug

This resource manages a [weblogic.management.configuration.ServerDebugMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.ServerDebugMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ServerDebugMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDebug](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDebug/debugScopeCreateForm](#) **rel**=debugScopeCreateForm
The create form resource for this resource's debugScopes collection resource.
- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDebug/debugScopes](#) **rel**=debugScopes
This resource's debugScopes collection resource.
- **uri**=[/management/weblogic/{version}/edit/servers/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDebug](#)
rel=self
This resource.
- **rel**=server
This resource's server reference to a [weblogic.management.configuration.ServerMBean](#) resource.

POST

Update this [weblogic.management.configuration.ServerDebugMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.ServerDebugMBean](#) entity.

/management/weblogic/{version}/edit/servers/{name}/serverDebug/debugScopeCreateForm

This resource manages the create forms for the debugScopes collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.DebugScopeMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the debugScopes collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.DebugScopeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDebug/debugScopeCreateForm](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDebug/debugScopes](#) **rel**=create

The collection resource for this create form resource.

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDebug](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDebug/debugScopeCreateForm](#) **rel**=self

This resource.

/management/weblogic/{version}/edit/servers/{name}/serverDebug/debugScopes

This resource manages a collection of [weblogic.management.configuration.DebugScopeMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.DebugScopeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.DebugScopeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDebug/debugScopes](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDebug/debugScopeCreateForm](#) **rel**=create-form
The create form resource for this collection resource.
- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDebug](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDebug/debugScopes](#) **rel**=self
This resource.

POST

Add a new [weblogic.management.configuration.DebugScopeMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.DebugScopeMBean](#) entity.

/management/weblogic/{version}/edit/servers/{name}/serverDebug/debugScopes/{name}

This resource manages a [weblogic.management.configuration.DebugScopeMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.DebugScopeMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.DebugScopeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.DebugScopeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDebug/debugScopes/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDebug/debugScopes](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDebug/debugScopes/{name}](#) **rel**=self

This resource.

POST

Update this [weblogic.management.configuration.DebugScopeMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.DebugScopeMBean](#) entity.

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig

This resource manages a [weblogic.management.configuration.WLDFServerDiagnosticMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.WLDFServerDiagnosticMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.WLDFServerDiagnosticMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean
rel=WLDFBuiltinSystemResourceDescriptorBean

This resource's WLDFBuiltinSystemResourceDescriptorBean singleton resource.
- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFDataRetirementByAgeCreateForm
rel=WLDFDataRetirementByAgeCreateForm

The create form resource for this resource's WLDFDataRetirementByAges collection resource.
- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFDataRetirementByAges **rel**=WLDFDataRetirementByAges

This resource's WLDFDataRetirementByAges collection resource.
- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/lookupWLDFDataRetirement **rel**=action **title**=lookupWLDFDataRetirement

This resource's lookupWLDFDataRetirement action resource.
- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig **rel**=canonical

This resource.
- **rel**=diagnosticJDBCResource

This resource's diagnosticJDBCResource reference to a weblogic.management.configuration.JDBCSystemResourceMBean resource.
- **uri**=/management/weblogic/{version}/edit/servers/{name} **rel**=parent

The parent resource of this resource.
- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig **rel**=self

This resource.

POST

Update this [weblogic.management.configuration.WLDFServerDiagnosticMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.WLDFServerDiagnosticMBean](#) entity.

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/ lookupWLDFDataRetirement

The resource supports the following methods:

- [POST](#)

POST

Look up WLDFDataRetirement object with given name

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

name

Name of the data retirement

Type: string

Response Body

Contains a JSON object with a `weblogic.management.configuration.WLDFDataRetirementMBean` reference return field.

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean

This resource manages a [weblogic.diagnostics.descriptor.WLDFResourceBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.diagnostics.descriptor.WLDFResourceBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFResourceBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/harvester](#) **rel**=harvester
This resource's harvester singleton resource.
- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/instrumentation](#) **rel**=instrumentation
This resource's instrumentation singleton resource.
- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean](#) **rel**=self
This resource.
- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification](#) **rel**=watchNotification
This resource's watchNotification singleton resource.

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/harvester

This resource manages a [weblogic.diagnostics.descriptor.WLDFHarvesterBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.diagnostics.descriptor.WLDFHarvesterBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFHarvesterBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/harvester](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/harvester/harvestedTypeCreateForm](#) **rel**=harvestedTypeCreateForm

The create form resource for this resource's harvestedTypes collection resource.

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/harvester/harvestedTypes](#) **rel**=harvestedTypes

This resource's harvestedTypes collection resource.

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/harvester](#) **rel**=self

This resource.

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/har-

POST

Update this [weblogic.diagnostics.descriptor.WLDFHarvesterBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFHarvesterBean](#) entity.

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/harvester/harvestedTypeCreateForm

This resource manages the create forms for the harvestedTypes collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFHarvestedTypeBean](#) entity populated with default values that can be customized then posted (using the POST method) to the harvestedTypes collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFHarvestedTypeBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/harvester/harvestedTypeCreateForm **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/harvester/harvestedTypes **rel**=create

The collection resource for this create form resource.

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/harvester **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/harvester/harvestedTypeCreateForm **rel**=self

This resource.

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/ WLDFBuiltinSystemResourceDescriptorBean/harvester/harvestedTypes

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFHarvestedTypeBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFHarvestedTypeBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFHarvestedTypeBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/harvester/harvestedTypes
rel=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/harvester/harvestedTypeCreateForm
rel=create-form

The create form resource for this collection resource.

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/harvester
rel=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/harvester/harvestedTypes
rel=self

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFHarvestedTypeBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFHarvestedTypeBean](#) entity.

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/harvester/harvestedTypes/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFHarvestedTypeBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFHarvestedTypeBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.diagnostics.descriptor.WLDFHarvestedTypeBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFHarvestedTypeBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/harvester/harvestedTypes/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/harvester/harvestedTypes **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/harvester/harvestedTypes/{name} **rel**=self

This resource.

POST

Update this [weblogic.diagnostics.descriptor.WLDFHarvestedTypeBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFHarvestedTypeBean](#) entity.

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/instrumentation

This resource manages a [weblogic.diagnostics.descriptor.WLDFInstrumentationBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.diagnostics.descriptor.WLDFInstrumentationBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFInstrumentationBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/instrumentation/WLDFInstrumentationMonitorCreateForm](#) **rel**=[WLDFInstrumentationMonitorCreateForm](#)

The create form resource for this resource's [WLDFInstrumentationMonitors](#) collection resource.

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/instrumentation/WLDFInstrumentationMonitors](#) **rel**=[WLDFInstrumentationMonitors](#)

This resource's [WLDFInstrumentationMonitors](#) collection resource.

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/instrumentation](#) **rel**=[canonical](#)

This resource.

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean](#) **rel**=[parent](#)

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/instrumentation](#) **rel**=[self](#)

This resource.

POST

Update this [weblogic.diagnostics.descriptor.WLDFInstrumentationBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFInstrumentationBean](#) entity.

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/instrumentation/WLDFInstrumentationMonitorCreateForm

This resource manages the create forms for the WLDFInstrumentationMonitors collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFInstrumentationMonitorBean](#) entity populated with default values that can be customized then posted (using the POST method) to the [WLDFInstrumentationMonitors](#) collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFInstrumentationMonitorBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/instrumentation/WLDFInstrumentationMonitorCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/instrumentation/WLDFInstrumentationMonitors](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/instrumentation](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/instrumentation/WLDFInstrumentationMonitorCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/instrumentation/WLDFInstrumentationMonitors

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFInstrumentationMonitorBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFInstrumentationMonitorBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFInstrumentationMonitorBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/instrumentation/WLDFInstrumentationMonitors **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/instrumentation/WLDFInstrumentationMonitorCreateForm **rel**=create-form

The create form resource for this collection resource.

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/instrumentation **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/instrumentation/WLDFInstrumentationMonitors **rel**=self

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFInstrumentationMonitorBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFInstrumentationMonitorBean](#) entity.

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/instrumentation/WLDFInstrumentationMonitors/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFInstrumentationMonitorBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFInstrumentationMonitorBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.diagnostics.descriptor.WLDFInstrumentationMonitorBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFInstrumentationMonitorBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/instrumentation/WLDFInstrumentationMonitors/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/instrumentation/WLDFInstrumentationMonitors **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/instrumentation/WLDFInstrumentationMonitors/{name} **rel**=self

This resource.

POST

Update this [weblogic.diagnostics.descriptor.WLDFInstrumentationMonitorBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFInstrumentationMonitorBean](#) entity.

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification

This resource manages a [weblogic.diagnostics.descriptor.WLDFWatchNotificationBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.diagnostics.descriptor.WLDFWatchNotificationBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFWatchNotificationBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/JMSNotificationCreateForm](#) **rel**=JMSNotificationCreateForm

The create form resource for this resource's JMSNotifications collection resource.

- [uri=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/JMSNotifications](#) **rel**=JMSNotifications

This resource's JMSNotifications collection resource.

- [uri=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/JMXNotificationCreateForm](#) **rel**=JMXNotificationCreateForm

The create form resource for this resource's JMXNotifications collection resource.

- [uri=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/JMXNotifications](#) **rel**=JMXNotifications

This resource's JMXNotifications collection resource.

- [uri=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/RESTNotificationCreateForm](#) **rel**=RESTNotificationCreateForm

The create form resource for this resource's RESTNotifications collection resource.

- [uri=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/RESTNotifications](#) **rel**=RESTNotifications

This resource's RESTNotifications collection resource.

- [uri=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/SMTPNotificationCreateForm](#) **rel**=SMTPNotificationCreateForm

The create form resource for this resource's SMTPNotifications collection resource.

- [uri=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/SMTPNotifications](#) **rel**=SMTPNotifications

This resource's SMTPNotifications collection resource.

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/SNMPNotificationCreateForm **rel**=SNMPNotificationCreateForm

The create form resource for this resource's SNMPNotifications collection resource.

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/SNMPNotifications **rel**=SNMPNotifications

This resource's SNMPNotifications collection resource.

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/lookupActions **rel**=action **title**=lookupActions

This resource's lookupActions action resource.

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/lookupNotification **rel**=action **title**=lookupNotification

This resource's lookupNotification action resource.

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actionCreateForm **rel**=actionCreateForm

The create form resource for this resource's actions collection resource.

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions **rel**=actions

This resource's actions collection resource.

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/heapDumpActionCreateForm **rel**=heapDumpActionCreateForm

The create form resource for this resource's heapDumpActions collection resource.

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/heapDumpActions **rel**=heapDumpActions

This resource's heapDumpActions collection resource.

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/imageNotificationCreateForm **rel**=imageNotificationCreateForm

The create form resource for this resource's imageNotifications collection resource.

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/imageNotifications **rel**=imageNotifications

This resource's imageNotifications collection resource.

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/logActionCreateForm **rel**=logActionCreateForm
The create form resource for this resource's logActions collection resource.
- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/logActions **rel**=logActions
This resource's logActions collection resource.
- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/scaleDownActionCreateForm **rel**=scaleDownActionCreateForm
The create form resource for this resource's scaleDownActions collection resource.
- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/scaleDownActions **rel**=scaleDownActions
This resource's scaleDownActions collection resource.
- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/scaleUpActionCreateForm **rel**=scaleUpActionCreateForm
The create form resource for this resource's scaleUpActions collection resource.
- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/scaleUpActions **rel**=scaleUpActions
This resource's scaleUpActions collection resource.
- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/scriptActionCreateForm **rel**=scriptActionCreateForm
The create form resource for this resource's scriptActions collection resource.
- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/scriptActions **rel**=scriptActions
This resource's scriptActions collection resource.
- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification **rel**=self
This resource.
- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/threadDumpActionCreateForm **rel**=threadDumpActionCreateForm
The create form resource for this resource's threadDumpActions collection resource.

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/threadDumpActions **rel**=threadDumpActions

This resource's threadDumpActions collection resource.

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/watchCreateForm **rel**=watchCreateForm

The create form resource for this resource's watches collection resource.

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/watches **rel**=watches

This resource's watches collection resource.

POST

POST

Update this [weblogic.diagnostics.descriptor.WLDFWatchNotificationBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFWatchNotificationBean](#) entity.

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actionCreateForm

This resource manages the create forms for the actions collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFActionBean](#) entity populated with default values that can be customized then posted (using the POST method) to the actions collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFActionBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actionCreateForm](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions](#) **rel**=create

The collection resource for this create form resource.

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actionCreateForm](#) **rel**=self

This resource.

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFActionBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFActionBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFActionBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions](#)
rel=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actionCreateForm](#) **rel**=create-form

The create form resource for this collection resource.

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions](#)
rel=self

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFActionBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFActionBean](#) entity.

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFActionBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFActionBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.diagnostics.descriptor.WLDFActionBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFActionBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/arrayProperties **rel**=arrayProperties

This resource's arrayProperties collection resource.

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/arrayPropertyCreateForm **rel**=arrayPropertyCreateForm

The create form resource for this resource's arrayProperties collection resource.

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/configurationProperties **rel**=configurationProperties

This resource's configurationProperties collection resource.

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/encryptedProperties **rel**=encryptedProperties

This resource's encryptedProperties collection resource.

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/encryptedPropertyCreateForm **rel**=encryptedPropertyCreateForm

The create form resource for this resource's encryptedProperties collection resource.

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapProperties **rel**=mapProperties

This resource's mapProperties collection resource.

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapPropertyCreateForm **rel**=mapPropertyCreateForm

The create form resource for this resource's mapProperties collection resource.

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions
rel=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/properties **rel**=properties

This resource's properties collection resource.

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/propertyCreateForm **rel**=propertyCreateForm

The create form resource for this resource's properties collection resource.

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name} **rel**=self

This resource.

POST

Update this [weblogic.diagnostics.descriptor.WLDFActionBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFActionBean](#) entity.

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/arrayProperties

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFArrayPropertyBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFArrayPropertyBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFArrayPropertyBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/arrayProperties](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/arrayPropertyCreateForm](#) **rel**=create-form

The create form resource for this collection resource.

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/arrayProperties](#) **rel**=self

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFArrayPropertyBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFArrayPropertyBean](#) entity.

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/arrayProperties/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFArrayPropertyBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFArrayPropertyBean](#) instance.

Roles

Admin

GET

Get this [weblogic.diagnostics.descriptor.WLDFArrayPropertyBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFArrayPropertyBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/arrayProperties/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/arrayProperties](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/arrayProperties/{name}](#) **rel**=self

This resource.

POST

Update this [weblogic.diagnostics.descriptor.WLDFArrayPropertyBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFArrayPropertyBean](#) entity.

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/arrayPropertyCreateForm

This resource manages the create forms for the arrayProperties collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFArrayPropertyBean](#) entity populated with default values that can be customized then posted (using the POST method) to the arrayProperties collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFArrayPropertyBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/arrayPropertyCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/arrayProperties](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/arrayPropertyCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/configurationProperties

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFConfigurationPropertyBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFConfigurationPropertyBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFConfigurationPropertyBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/configurationProperties **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/configurationProperties **rel**=self

This resource.

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/configurationProperties/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFConfigurationPropertyBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.diagnostics.descriptor.WLDFConfigurationPropertyBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFConfigurationPropertyBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/configurationProperties/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/configurationProperties **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/configurationProperties/{name} **rel**=self

This resource.

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/encryptedProperties

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/encryptedProperties **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/encryptedPropertyCreateForm **rel**=create-form

The create form resource for this collection resource.

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/encryptedProperties **rel**=self

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) entity.

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/encryptedProperties/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) instance.

Roles

Admin

GET

Get this [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/encryptedProperties/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/encryptedProperties **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/encryptedProperties/{name} **rel**=self

This resource.

POST

POST

Update this [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) entity.

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/encryptedPropertyCreateForm

This resource manages the create forms for the encryptedProperties collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) entity populated with default values that can be customized then posted (using the POST method) to the encryptedProperties collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/encryptedPropertyCreateForm **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/encryptedProperties **rel**=create

The collection resource for this create form resource.

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/encryptedPropertyCreateForm **rel**=self

This resource.

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapProperties

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFConfigurationPropertiesBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFConfigurationPropertiesBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFConfigurationPropertiesBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapProperties](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapPropertyCreateForm](#) **rel**=create-form

The create form resource for this collection resource.

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapProperties](#) **rel**=self

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFConfigurationPropertiesBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFConfigurationPropertiesBean](#) entity.

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapProperties/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFConfigurationPropertiesBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFConfigurationPropertiesBean](#) instance.

Roles

Admin

GET

Get this [weblogic.diagnostics.descriptor.WLDFConfigurationPropertiesBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFConfigurationPropertiesBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapProperties/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapProperties/{name}/configurationProperties **rel**=configurationProperties

This resource's configurationProperties collection resource.

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapProperties/{name}/encryptedProperties **rel**=encryptedProperties

This resource's encryptedProperties collection resource.

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapProperties/{name}/encryptedPropertyCreateForm **rel**=encryptedPropertyCreateForm

The create form resource for this resource's encryptedProperties collection resource.

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapProperties **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapProperties/{name}/properties **rel**=properties

This resource's properties collection resource.

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapProperties/{name}/propertyCreateForm **rel**=propertyCreateForm

The create form resource for this resource's properties collection resource.

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapProperties/{name} **rel**=self

This resource.

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapProperties/{name}/configurationProperties

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFConfigurationPropertyBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFConfigurationPropertyBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFConfigurationPropertyBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapProperties/{name}/configurationProperties](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapProperties/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapProperties/{name}/configurationProperties](#) **rel**=self

This resource.

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapProperties/{name}/configurationProperties/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFConfigurationPropertyBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.diagnostics.descriptor.WLDFConfigurationPropertyBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFConfigurationPropertyBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapProperties/{name}/configurationProperties/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapProperties/{name}/configurationProperties](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapProperties/{name}/configurationProperties/{name}](#) **rel**=self

This resource.

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapProperties/{name}/encryptedProperties

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapProperties/{name}/encryptedProperties](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapProperties/{name}/encryptedPropertyCreateForm](#) **rel**=create-form

The create form resource for this collection resource.

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapProperties/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapProperties/{name}/encryptedProperties](#) **rel**=self

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) entity.

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapProperties/{name}/encryptedProperties/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapProperties/{name}/encryptedProperties/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapProperties/{name}/encryptedProperties](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapProperties/{name}/encryptedProperties/{name}](#) **rel**=self

This resource.

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/wat

POST

Update this [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) entity.

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapProperties/{name}/encryptedPropertyCreateForm

This resource manages the create forms for the encryptedProperties collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) entity populated with default values that can be customized then posted (using the POST method) to the encryptedProperties collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapProperties/{name}/encryptedPropertyCreateForm **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapProperties/{name}/encryptedProperties **rel**=create

The collection resource for this create form resource.

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapProperties/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapProperties/{name}/encryptedPropertyCreateForm **rel**=self

This resource.

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapProperties/{name}/properties

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapProperties/{name}/properties **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapProperties/{name}/propertycreateForm **rel**=create-form

The create form resource for this collection resource.

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapProperties/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapProperties/{name}/properties **rel**=self

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) entity.

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapProperties/{name}/properties/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapProperties/{name}/properties/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapProperties/{name}/properties **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapProperties/{name}/properties/{name} **rel**=self

This resource.

POST

Update this [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) entity.

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapProperties/{name}/propertyCreateForm

This resource manages the create forms for the properties collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) entity populated with default values that can be customized then posted (using the POST method) to the properties collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapProperties/{name}/propertycreateForm **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapProperties/{name}/properties **rel**=create

The collection resource for this create form resource.

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapProperties/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapProperties/{name}/propertycreateForm **rel**=self

This resource.

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapPropertyCreateForm

This resource manages the create forms for the mapProperties collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFConfigurationPropertiesBean](#) entity populated with default values that can be customized then posted (using the POST method) to the `mapProperties` collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFConfigurationPropertiesBean](#) entity.

This method can return the following links:

- **uri**=`/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapPropertyCreateForm` **rel**=canonical

This resource.

- **uri**=`/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapProperties` **rel**=create

The collection resource for this create form resource.

- **uri**=`/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}` **rel**=parent

The parent resource of this resource.

- **uri**=`/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapPropertyCreateForm` **rel**=self

This resource.

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/properties

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/properties](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/propertyCreateForm](#) **rel**=create-form

The create form resource for this collection resource.

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/properties](#) **rel**=self

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) entity.

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/properties/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) instance.

Roles

Admin

GET

Get this [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/properties/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/properties **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/properties/{name} **rel**=self

This resource.

POST

Update this [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) entity.

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/propertyCreateForm

This resource manages the create forms for the properties collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) entity populated with default values that can be customized then posted (using the POST method) to the properties collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/propertyCreateForm **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/properties **rel**=create

The collection resource for this create form resource.

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/propertyCreateForm **rel**=self

This resource.

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/heapDumpActionCreateForm

This resource manages the create forms for the heapDumpActions collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFHeapDumpActionBean](#) entity populated with default values that can be customized then posted (using the POST method) to the heapDumpActions collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFHeapDumpActionBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/heapDumpActionCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/heapDumpActions](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/heapDumpActionCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/heapDumpActions

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFHeapDumpActionBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFHeapDumpActionBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFHeapDumpActionBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/heapDumpActions](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/heapDumpActionCreateForm](#) **rel=create-form**

The create form resource for this collection resource.

- [uri=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/heapDumpActions](#) **rel=self**

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFHeapDumpActionBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFHeapDumpActionBean](#) entity.

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/heapDumpActions/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFHeapDumpActionBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFHeapDumpActionBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.diagnostics.descriptor.WLDFHeapDumpActionBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFHeapDumpActionBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/heapDumpActions/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/heapDumpActions **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/heapDumpActions/{name} **rel**=self

This resource.

POST

POST

Update this [weblogic.diagnostics.descriptor.WLDFHeapDumpActionBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFHeapDumpActionBean](#) entity.

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/imageNotificationCreateForm

This resource manages the create forms for the imageNotifications collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFImageNotificationBean](#) entity populated with default values that can be customized then posted (using the POST method) to the imageNotifications collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFImageNotificationBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/imageNotificationCreateForm rel=canonical](#)

This resource.

- [uri=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/imageNotifications rel=create](#)

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification rel=parent](#)

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/imageNotificationCreateForm rel=self](#)

This resource.

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/imageNotifications

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFImageNotificationBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFImageNotificationBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFImageNotificationBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/imageNotifications](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/imageNotificationCreateForm](#) **rel**=create-form

The create form resource for this collection resource.

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/imageNotifications](#) **rel**=self

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFImageNotificationBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFImageNotificationBean](#) entity.

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/imageNotifications/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFImageNotificationBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFImageNotificationBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.diagnostics.descriptor.WLDFImageNotificationBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFImageNotificationBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/imageNotifications/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/imageNotifications](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/imageNotifications/{name}](#) **rel**=self

This resource.

POST

Update this [weblogic.diagnostics.descriptor.WLDFImageNotificationBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFImageNotificationBean](#) entity.

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/JMSNotificationCreateForm

This resource manages the create forms for the JMSNotifications collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFJMSNotificationBean](#) entity populated with default values that can be customized then posted (using the POST method) to the JMSNotifications collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFJMSNotificationBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/JMSNotifications/createForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/JMSNotifications](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/JMSNotifications/createForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/JMSNotifications

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFJMSNotificationBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFJMSNotificationBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFJMSNotificationBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/JMSNotifications rel=canonical](#)

This resource.

- [uri=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/JMSNotifications/createForm rel=create-form](#)

The create form resource for this collection resource.

- [uri=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification rel=parent](#)

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/JMSNotifications rel=self](#)

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFJMSNotificationBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFJMSNotificationBean](#) entity.

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/JMSNotifications/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFJMSNotificationBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFJMSNotificationBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.diagnostics.descriptor.WLDFJMSNotificationBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFJMSNotificationBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/JMSNotifications/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/JMSNotifications **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/JMSNotifications/{name} **rel**=self

This resource.

POST

Update this [weblogic.diagnostics.descriptor.WLDFJMSNotificationBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFJMSNotificationBean](#) entity.

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/JMXNotificationCreateForm

This resource manages the create forms for the JMXNotifications collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFJMXNotificationBean](#) entity populated with default values that can be customized then posted (using the POST method) to the JMXNotifications collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFJMXNotificationBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/JMXNotifications/createForm **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/JMXNotifications **rel**=create

The collection resource for this create form resource.

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/JMXNotifications/createForm **rel**=self

This resource.

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/JMXNotification

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFJMXNotificationBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFJMXNotificationBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFJMXNotificationBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/JMXNotifications](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/JMXNotifications/createForm](#) **rel**=create-form

The create form resource for this collection resource.

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/JMXNotifications](#) **rel**=self

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFJMXNotificationBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFJMXNotificationBean](#) entity.

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/JMXNotifications/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFJMXNotificationBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFJMXNotificationBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.diagnostics.descriptor.WLDFJMXNotificationBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFJMXNotificationBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/JMXNotifications/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/JMXNotifications](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/JMXNotifications/{name}](#) **rel**=self

This resource.

POST

Update this [weblogic.diagnostics.descriptor.WLDFJMXNotificationBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFJMXNotificationBean](#) entity.

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/logActionCreateForm

This resource manages the create forms for the logActions collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFLogActionBean](#) entity populated with default values that can be customized then posted (using the POST method) to the logActions collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFLogActionBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/logActionCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/logActions](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/logActionCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/logActions

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFLogActionBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFLogActionBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFLogActionBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/logActions
rel=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/logActionCreateForm **rel**=create-form

The create form resource for this collection resource.

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/logActions
rel=self

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFLogActionBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFLogActionBean](#) entity.

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/logActions/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFLogActionBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFLogActionBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.diagnostics.descriptor.WLDFLogActionBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFLogActionBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/logActions/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/logActions **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/logActions/{name} **rel**=self

This resource.

POST

Update this [weblogic.diagnostics.descriptor.WLDFLogActionBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFLogActionBean](#) entity.

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/lookupAction S

The resource supports the following methods:

- [POST](#)

POST

Roles

Admin, Deployer

Request Body

Must contain a JSON object with the following fields:

typeName

typeName

Type: string

Response Body

Contains a JSON object with a array of
weblogic.diagnostics.descriptor.WLDFActionBean references return field.

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/lookupNotification

The resource supports the following methods:

- [POST](#)

POST

Looks up an action with the given name.

Roles

Admin, Deployer

Request Body

Must contain a JSON object with the following fields:

name

name

Type: string

Response Body

Contains a JSON object with a `weblogic.diagnostics.descriptor.WLDFNotificationBean` reference return field.

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/RESTNotificationCreateForm

This resource manages the create forms for the RESTNotifications collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFRESTNotificationBean](#) entity populated with default values that can be customized then posted (using the POST method) to the RESTNotifications collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFRESTNotificationBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/RESTNotificationCreateForm](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/RESTNotifications](#) **rel**=create

The collection resource for this create form resource.

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/RESTNotificationCreateForm](#) **rel**=self

This resource.

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/RESTNotifications

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFRESTNotificationBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFRESTNotificationBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFRESTNotificationBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/RESTNotifications](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/RESTNotificationCreateForm](#) **rel=create-form**

The create form resource for this collection resource.

- [uri=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/RESTNotifications](#) **rel=self**

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFRESTNotificationBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFRESTNotificationBean](#) entity.

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/RESTNotifications/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFRESTNotificationBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFRESTNotificationBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.diagnostics.descriptor.WLDFRESTNotificationBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFRESTNotificationBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/RESTNotifications/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/RESTNotifications](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/RESTNotifications/{name}](#) **rel**=self

This resource.

POST

Update this [weblogic.diagnostics.descriptor.WLDFRESTNotificationBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFRESTNotificationBean](#) entity.

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/scaleDownActionCreateForm

This resource manages the create forms for the scaleDownActions collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFScaleDownActionBean](#) entity populated with default values that can be customized then posted (using the POST method) to the scaleDownActions collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFScaleDownActionBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/scaleDownActionCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/scaleDownActions](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/scaleDownActionCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/scaleDownActions

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFScaleDownActionBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFScaleDownActionBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFScaleDownActionBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/scaleDownActions rel=canonical](#)

This resource.

- [uri=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/scaleDownActionCreateForm rel=create-form](#)

The create form resource for this collection resource.

- [uri=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification rel=parent](#)

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/scaleDownActions rel=self](#)

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFScaleDownActionBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFScaleDownActionBean](#) entity.

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/scaleDownActions/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFScaleDownActionBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFScaleDownActionBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.diagnostics.descriptor.WLDFScaleDownActionBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFScaleDownActionBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/scaleDownActions/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/scaleDownActions **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/scaleDownActions/{name} **rel**=self

This resource.

POST

Update this [weblogic.diagnostics.descriptor.WLDFScaleDownActionBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFScaleDownActionBean](#) entity.

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/scaleUpActionCreateForm

This resource manages the create forms for the scaleUpActions collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFScaleUpActionBean](#) entity populated with default values that can be customized then posted (using the POST method) to the `scaleUpActions` collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFScaleUpActionBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/scaleUpActionCreateForm](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/scaleUpActions](#) **rel**=create

The collection resource for this create form resource.

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/scaleUpActionCreateForm](#) **rel**=self

This resource.

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/scaleUpActions

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFScaleUpActionBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFScaleUpActionBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFScaleUpActionBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/scaleUpActions rel=canonical](#)

This resource.

- [uri=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/scaleUpActionCreateForm rel=create-form](#)

The create form resource for this collection resource.

- [uri=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification rel=parent](#)

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/scaleUpActions rel=self](#)

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFScaleUpActionBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFScaleUpActionBean](#) entity.

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/scaleUpActions/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFScaleUpActionBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFScaleUpActionBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.diagnostics.descriptor.WLDFScaleUpActionBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFScaleUpActionBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/scaleUpActions/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/scaleUpActions](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/scaleUpActions/{name}](#) **rel**=self

This resource.

POST

Update this [weblogic.diagnostics.descriptor.WLDFScaleUpActionBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFScaleUpActionBean](#) entity.

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/scriptActionC reateForm

This resource manages the create forms for the scriptActions collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFScriptActionBean](#) entity populated with default values that can be customized then posted (using the POST method) to the scriptActions collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFScriptActionBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/scriptActionCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/scriptActions](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/scriptActionCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/scriptActions

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFScriptActionBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFScriptActionBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFScriptActionBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/scriptActions](#)
rel=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/scriptActionCreateForm](#) **rel**=create-form

The create form resource for this collection resource.

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/scriptActions](#)
rel=self

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFScriptActionBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFScriptActionBean](#) entity.

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/scriptActions/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFScriptActionBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFScriptActionBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.diagnostics.descriptor.WLDFScriptActionBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFScriptActionBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/scriptActions/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/scriptActions **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/scriptActions/{name} **rel**=self

This resource.

POST

Update this [weblogic.diagnostics.descriptor.WLDFScriptActionBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFScriptActionBean](#) entity.

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/SMTPNotificationCreateForm

This resource manages the create forms for the SMTPNotifications collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFSMTPLNotificationBean](#) entity populated with default values that can be customized then posted (using the POST method) to the SMTPNotifications collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFSMTPLNotificationBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/SMTPNotificationCreateForm **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/SMTPNotifications **rel**=create

The collection resource for this create form resource.

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/SMTPNotificationCreateForm **rel**=self

This resource.

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/SMTPNotifica tions

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFSMTPLNotificationBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFSMTPNotificationBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFSMTPNotificationBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/SMTPNotifications](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/SMTPNotificationCreateForm](#) **rel**=create-form

The create form resource for this collection resource.

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/SMTPNotifications](#) **rel**=self

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFSMTPNotificationBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFSMTPNotificationBean](#) entity.

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/SMTPNotifications/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFSMTPLNotificationBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFSMTPNotificationBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.diagnostics.descriptor.WLDFSMTPLNotificationBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFSMTPLNotificationBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/SMTPLNotifications/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/SMTPLNotifications](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/SMTPLNotifications/{name}](#) **rel**=self

This resource.

POST

Update this [weblogic.diagnostics.descriptor.WLDFSMTPNotificationBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFSMTPNotificationBean](#) entity.

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/SNMPNotificationCreateForm

This resource manages the create forms for the SNMPNotifications collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFSNMPNotificationBean](#) entity populated with default values that can be customized then posted (using the POST method) to the SNMPNotifications collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFSNMPNotificationBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/SNMPNotificationCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/SNMPNotifications](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/SNMPNotificationCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/SNMPNotifications

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFSNMPNotificationBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFSNMPNotificationBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFSNMPNotificationBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/SNMPNotifications **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/SNMPNotificationCreateForm **rel**=create-form

The create form resource for this collection resource.

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/SNMPNotifications **rel**=self

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFSNMPNotificationBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFSNMPNotificationBean](#) entity.

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/SNMPNotifications/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFSNMPNotificationBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFSNMPNotificationBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.diagnostics.descriptor.WLDFSNMPNotificationBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFSNMPNotificationBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/SNMPNotifications/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/SNMPNotifications **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/SNMPNotifications/{name} **rel**=self

This resource.

POST

Update this [weblogic.diagnostics.descriptor.WLDFSNMPNotificationBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFSNMPNotificationBean](#) entity.

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/threadDumpActionCreateForm

This resource manages the create forms for the threadDumpActions collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFThreadDumpActionBean](#) entity populated with default values that can be customized then posted (using the POST method) to the threadDumpActions collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFThreadDumpActionBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/threadDumpActionCreateForm **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/threadDumpActions **rel**=create

The collection resource for this create form resource.

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/threadDumpActionCreateForm **rel**=self

This resource.

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/threadDumpActions

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFThreadDumpActionBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFThreadDumpActionBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFThreadDumpActionBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/threadDumpActions](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/threadDumpActionCreateForm](#) **rel**=create-form

The create form resource for this collection resource.

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/threadDumpActions](#) **rel**=self

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFThreadDumpActionBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFThreadDumpActionBean](#) entity.

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/threadDumpActions/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFThreadDumpActionBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFThreadDumpActionBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.diagnostics.descriptor.WLDFThreadDumpActionBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFThreadDumpActionBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/threadDumpActions/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/threadDumpActions](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/threadDumpActions/{name}](#) **rel**=self

This resource.

POST

Update this [weblogic.diagnostics.descriptor.WLDFThreadDumpActionBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFThreadDumpActionBean](#) entity.

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/watchCreateForm

This resource manages the create forms for the watches collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFWatchBean](#) entity populated with default values that can be customized then posted (using the POST method) to the watches collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFWatchBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/watchCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/watches](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/watchCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/watches

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFWatchBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFWatchBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFWatchBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/watches](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/watchCreateForm](#) **rel**=create-form
The create form resource for this collection resource.
- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/watches](#)
rel=self
This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFWatchBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFWatchBean](#) entity.

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/watches/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFWatchBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFWatchBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.diagnostics.descriptor.WLDFWatchBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFWatchBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/watches/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/watches **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/watches/{name}/schedule **rel**=schedule

This resource's schedule singleton resource.

- **uri**=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/watches/{name} **rel**=self

This resource.

POST

POST

Update this [weblogic.diagnostics.descriptor.WLDFWatchBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFWatchBean](#) entity.

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/watches/{name}/schedule

This resource manages a [weblogic.diagnostics.descriptor.WLDFScheduleBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.diagnostics.descriptor.WLDFScheduleBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFScheduleBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/watches/{name}/schedule](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/watches/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/watches/{name}/schedule](#) **rel**=self

This resource.

POST

Update this [weblogic.diagnostics.descriptor.WLDFScheduleBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFScheduleBean](#) entity.

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFDataRetirementByAgeCreateForm

This resource manages the create forms for the WLDFDataRetirementByAges collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.WLDFDataRetirementByAgeMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the [WLDFDataRetirementByAges](#) collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.WLDFDataRetirementByAgeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFDataRetirementByAgeCreateForm](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFDataRetirementByAges](#) **rel=create**
The collection resource for this create form resource.
- [uri=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFDataRetirementByAgeCreateForm](#) **rel=self**
This resource.

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFDataRetirementByAges

This resource manages a collection of [weblogic.management.configuration.WLDFDataRetirementByAgeMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.WLDFDataRetirementByAgeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.WLDFDataRetirementByAgeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFDataRetirementByAges](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFDataRetirementByAgeCreateForm](#) **rel=create-form**
The create form resource for this collection resource.
- [uri=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFDataRetirementByAges](#) **rel=self**
This resource.

POST

POST

Add a new [weblogic.management.configuration.WLDFDataRetirementByAgeMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.WLDFDataRetirementByAgeMBean](#) entity.

/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFDataRetirementByAges/{name}

This resource manages a [weblogic.management.configuration.WLDFDataRetirementByAgeMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.WLDFDataRetirementByAgeMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.WLDFDataRetirementByAgeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.WLDFDataRetirementByAgeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFDataRetirementByAges/{name}](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFDataRetirementByAges](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/servers/{name}/serverDiagnosticConfig/WLDFDataRetirementByAges/{name}](#) **rel=self**
This resource.

POST

POST

Update this [weblogic.management.configuration.WLDFDataRetirementByAgeMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.WLDFDataRetirementByAgeMBean](#) entity.

/management/weblogic/{version}/edit/servers/{name}/serverStart

This resource manages a [weblogic.management.configuration.ServerStartMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.ServerStartMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ServerStartMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverStart](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/servers/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/servers/{name}/serverStart](#) **rel**=self
This resource.

POST

Update this [weblogic.management.configuration.ServerStartMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.ServerStartMBean](#) entity.

/management/weblogic/{version}/edit/servers/{name}/singleSignOnServices

This resource manages a [weblogic.management.configuration.SingleSignOnServicesMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.SingleSignOnServicesMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SingleSignOnServicesMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/singleSignOnServices](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/servers/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/servers/{name}/singleSignOnServices](#)
rel=self
This resource.

POST

Update this [weblogic.management.configuration.SingleSignOnServicesMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.SingleSignOnServicesMBean](#) entity.

/management/weblogic/{version}/edit/servers/{name}/SSL

This resource manages a [weblogic.management.configuration.SSLMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.SSLMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SSLMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/SSL](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/servers/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/servers/{name}/SSL](#) **rel**=self
This resource.

Example

Example 1 Viewing the [weblogic.management.configuration.SSLMBean](#) Instance

This example uses the GET method to view this [weblogic.management.configuration.SSLMBean](#) instance.

Example Request

```
curl -v \  
--user admin:admin123 \  
-H X-Requested-By:MyClient \  
-H Accept:application/json \  
-X GET  
http://localhost:7001/management/weblogic/latest/edit/servers/AdminServer/SSL
```

Example Response

```
HTTP/1.1 200 OK
```

Response Body:

```
{  
  "links": [  
    {  
      "rel": "parent",  
      "href":  
"http://localhost:7001/management/weblogic/latest/edit/servers/AdminServer"  
    },  
    {  
      "rel": "self",  
      "href":  
"http://localhost:7001/management/weblogic/latest/edit/servers/AdminServer/SSL"  
    },  
    {  
      "rel": "canonical",
```



```
        "href":
"http://localhost:7001/management/weblogic/latest/edit/servers/AdminServer/SSL"
    }
],
"identity": [
    "servers",
    "AdminServer",
    "SSL"
],
"hostnameVerificationIgnored": false,
"notes": null,
"outboundPrivateKeyPassPhrase": null,
"identityAndTrustLocations": "KeyStores",
"serverPrivateKeyAlias": null,
"hostnameVerifier": null,
"clientCertAlias": null,
"type": "SSL",
"inboundCertificateValidation": "BuiltinSSLValidationOnly",
"enabled": false,
"serverPrivateKeyPassPhrase": null,
"SSLRejectionLoggingEnabled": true,
"clientCertPrivateKeyPassPhrase": null,
"allowUnencryptedNullCipher": false,
"id": 0,
"dynamicallyCreated": false,
"outboundPrivateKeyAlias": null,
"SSLv2HelloEnabled": true,
"exportKeyLifespan": 500,
"acceptKSSDemoCertsEnabled": true,
"twoWaySSLEnabled": false,
"ciphersuites": [],
"tags": [],
"outboundCertificateValidation": "BuiltinSSLValidationOnly",
"JSSEEnabled": true,
"clientCertificateEnforced": false,
"loginTimeoutMillis": 25000,
"useServerCerts": false,
"useClientCertForOutbound": false,
"clientInitSecureRenegotiationAccepted": false,
"minimumTLSProtocolVersion": null,
"name": "AdminServer",
"listenPort": 7002
}
```

POST

Update this [weblogic.management.configuration.SSLMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.SSLMBean](#) entity.

Example

Example 1 Update the weblogic.management.configuration.SSLMBean Instance

This example uses the POST method to update this [weblogic.management.configuration.SSLMBean](#) instance.

Example Request

```
curl -v \  
--user admin:admin123 \  
-H X-Requested-By:MyClient \  
-H Accept:application/json \  
-H Content-Type:application/json \  
-d "{ loginTimeoutMillis: 23456 }" \  
-X POST  
http://localhost:7001/management/weblogic/latest/edit/servers/AdminServer/SSL
```

Example Response

```
HTTP/1.1 200 OK
```

```
Response Body:
```

```
{}
```

/management/weblogic/{version}/edit/servers/{name}/transactionLogJDBCStore

This resource manages a [weblogic.management.configuration.TransactionLogJDBCStoreMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.TransactionLogJDBCStoreMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.TransactionLogJDBCStoreMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/transactionLogJDBCStore](#) **rel**=canonical
This resource.
- **rel**=dataSource
This resource's dataSource reference to a [weblogic.management.configuration.JDBCSystemResourceMBean](#) resource.
- **uri**=[/management/weblogic/{version}/edit/servers/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/servers/{name}/transactionLogJDBCStore](#) **rel**=self
This resource.

POST

Update this [weblogic.management.configuration.TransactionLogJDBCStoreMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.TransactionLogJDBCStoreMBean](#) entity.

/management/weblogic/{version}/edit/servers/{name}/webServer

This resource manages a [weblogic.management.configuration.WebServerMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.WebServerMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.WebServerMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/webServer](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/servers/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/servers/{name}/webServer](#) **rel**=self
This resource.
- **uri**=[/management/weblogic/{version}/edit/servers/{name}/webServer/webServerLog](#) **rel**=webServerLog
This resource's webServerLog singleton resource.

POST

Update this [weblogic.management.configuration.WebServerMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.WebServerMBean](#) entity.

/management/weblogic/{version}/edit/servers/{name}/webServer/webServerLog

This resource manages a [weblogic.management.configuration.WebServerLogMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.WebServerLogMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.WebServerLogMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/servers/{name}/webServer/webServerLog](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/servers/{name}/webServer](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/servers/{name}/webServer/webServerLog](#) **rel=self**
This resource.

POST

Update this [weblogic.management.configuration.WebServerLogMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.WebServerLogMBean](#) entity.

/management/weblogic/{version}/edit/servers/{name}/webService

This resource manages a [weblogic.management.configuration.WebServiceMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.WebServiceMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.WebServiceMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/webService](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/servers/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/servers/{name}/webService](#) **rel**=self
This resource.
- **uri**=[/management/weblogic/{version}/edit/servers/{name}/webService/webServiceBuffering](#) **rel**=webServiceBuffering
This resource's webServiceBuffering singleton resource.
- **uri**=[/management/weblogic/{version}/edit/servers/{name}/webService/webServicePersistence](#) **rel**=webServicePersistence
This resource's webServicePersistence singleton resource.
- **uri**=[/management/weblogic/{version}/edit/servers/{name}/webService/webServiceReliability](#) **rel**=webServiceReliability
This resource's webServiceReliability singleton resource.

POST

POST

Update this [weblogic.management.configuration.WebServiceMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.WebServiceMBean](#) entity.

/management/weblogic/{version}/edit/servers/{name}/webService/webServiceBuffering

This resource manages a [weblogic.management.configuration.WebServiceBufferingMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.WebServiceBufferingMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.WebServiceBufferingMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/servers/{name}/webService/webServiceBuffering](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/servers/{name}/webService](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/servers/{name}/webService/webServiceBuffering](#) **rel=self**

This resource.

- [uri=/management/weblogic/{version}/edit/servers/{name}/webService/webServiceBuffering/webServiceRequestBufferingQueue](#) **rel=webServiceRequestBufferingQueue**

This resource's `webServiceRequestBufferingQueue` singleton resource.

- [uri=/management/weblogic/{version}/edit/servers/{name}/webService/webServiceBuffering/webServiceResponseBufferingQueue](#) **rel=webServiceResponseBufferingQueue**

This resource's `webServiceResponseBufferingQueue` singleton resource.

POST

Update this [weblogic.management.configuration.WebServiceBufferingMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.WebServiceBufferingMBean](#) entity.

/management/weblogic/{version}/edit/servers/{name}/webService/webServiceBuffering/webServiceRequestBufferingQueue

This resource manages a [weblogic.management.configuration.WebServiceRequestBufferingQueueMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.WebServiceRequestBufferingQueueMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.WebServiceRequestBufferingQueueMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/servers/{name}/webService/webServiceBuffering/webServiceRequestBufferingQueue **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/servers/{name}/webService/webServiceBuffering **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/servers/{name}/webService/webServiceBuffering/webServiceRequestBufferingQueue **rel**=self

This resource.

POST

POST

Update this [weblogic.management.configuration.WebServiceRequestBufferingQueueMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.WebServiceRequestBufferingQueueMBean](#) entity.

/management/weblogic/{version}/edit/servers/{name}/webService/webServiceBuffering/webServiceResponseBufferingQueue

This resource manages a [weblogic.management.configuration.WebServiceResponseBufferingQueueMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.WebServiceResponseBufferingQueueMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.WebServiceResponseBufferingQueueMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/webService/webServiceBuffering/webServiceResponseBufferingQueue](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/webService/webServiceBuffering](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/webService/webServiceBuffering/webServiceResponseBufferingQueue](#) **rel**=self

This resource.

POST

Update this [weblogic.management.configuration.WebServiceResponseBufferingQueueMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.WebServiceResponseBufferingQueueMBean](#) entity.

/management/weblogic/{version}/edit/servers/{name}/webService/webServicePersistence

This resource manages a [weblogic.management.configuration.WebServicePersistenceMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.WebServicePersistenceMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.WebServicePersistenceMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/webService/webServicePersistence](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/servers/{name}/webService](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/servers/{name}/webService/webServicePersistence](#) **rel**=self
This resource.
- **uri**=[/management/weblogic/{version}/edit/servers/{name}/webService/webServicePersistence/webServiceLogicalStoreCreateForm](#) **rel**=webServiceLogicalStoreCreateForm
The create form resource for this resource's webServiceLogicalStores collection resource.
- **uri**=[/management/weblogic/{version}/edit/servers/{name}/webService/webServicePersistence/webServiceLogicalStores](#) **rel**=webServiceLogicalStores
This resource's webServiceLogicalStores collection resource.
- **uri**=[/management/weblogic/{version}/edit/servers/{name}/webService/webServicePersistence/webServicePhysicalStoreCreateForm](#) **rel**=webServicePhysicalStoreCreateForm
The create form resource for this resource's webServicePhysicalStores collection resource.
- **uri**=[/management/weblogic/{version}/edit/servers/{name}/webService/webServicePersistence/webServicePhysicalStores](#) **rel**=webServicePhysicalStores
This resource's webServicePhysicalStores collection resource.

POST

Update this [weblogic.management.configuration.WebServicePersistenceMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.WebServicePersistenceMBean](#) entity.

/management/weblogic/{version}/edit/servers/{name}/webService/webServicePersistence/webServiceLogicalStoreCreateForm

This resource manages the create forms for the webServiceLogicalStores collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.WebServiceLogicalStoreMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the [webServiceLogicalStores](#) collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.WebServiceLogicalStoreMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/webService/webServicePersistence/webServiceLogicalStoreCreateForm](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/webService/webServicePersistence/webServiceLogicalStores](#) **rel**=create

The collection resource for this create form resource.

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/webService/webServicePersistence](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/webService/webServicePersistence/webServiceLogicalStoreCreateForm](#) **rel**=self

This resource.

/management/weblogic/{version}/edit/servers/{name}/webService/webServicePersistence/webServiceLogicalStores

This resource manages a collection of [weblogic.management.configuration.WebServiceLogicalStoreMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.WebServiceLogicalStoreMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.WebServiceLogicalStoreMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/webService/webServicePersistence/webServiceLogicalStores](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/webService/webServicePersistence/webServiceLogicalStoreCreateForm](#) **rel**=create-form

The create form resource for this collection resource.

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/webService/webServicePersistence](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/webService/webServicePersistence/webServiceLogicalStores](#) **rel**=self

This resource.

POST

Add a new [weblogic.management.configuration.WebServiceLogicalStoreMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.WebServiceLogicalStoreMBean](#) entity.

/management/weblogic/{version}/edit/servers/{name}/webService/webServicePersistence/webServiceLogicalStores/{name}

This resource manages a [weblogic.management.configuration.WebServiceLogicalStoreMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.WebServiceLogicalStoreMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.WebServiceLogicalStoreMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.WebServiceLogicalStoreMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/webService/webServicePersistence/webServiceLogicalStores/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/webService/webServicePersistence/webServiceLogicalStores](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/webService/webServicePersistence/webServiceLogicalStores/{name}](#) **rel**=self

This resource.

POST

Update this [weblogic.management.configuration.WebServiceLogicalStoreMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.WebServiceLogicalStoreMBean](#) entity.

/management/weblogic/{version}/edit/servers/{name}/webService/webServicePersistence/webServicePhysicalStoreCreateForm

This resource manages the create forms for the webServicePhysicalStores collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.WebServicePhysicalStoreMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the `webServicePhysicalStores` collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.WebServicePhysicalStoreMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/servers/{name}/webService/webServicePersistence/webServicePhysicalStoreCreateForm **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/edit/servers/{name}/webService/webServicePersistence/webServicePhysicalStores **rel**=create
The collection resource for this create form resource.
- **uri**=/management/weblogic/{version}/edit/servers/{name}/webService/webServicePersistence **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/edit/servers/{name}/webService/webServicePersistence/webServicePhysicalStoreCreateForm **rel**=self
This resource.

/management/weblogic/{version}/edit/servers/{name}/webService/webServicePersistence/webServicePhysicalStores

This resource manages a collection of [weblogic.management.configuration.WebServicePhysicalStoreMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.WebServicePhysicalStoreMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.WebServicePhysicalStoreMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/servers/{name}/webService/webServicePersistence/webServicePhysicalStores](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/servers/{name}/webService/webServicePersistence/webServicePhysicalStoreCreateForm](#) **rel=create-form**

The create form resource for this collection resource.

- [uri=/management/weblogic/{version}/edit/servers/{name}/webService/webServicePersistence](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/servers/{name}/webService/webServicePersistence/webServicePhysicalStores](#) **rel=self**

This resource.

POST

Add a new [weblogic.management.configuration.WebServicePhysicalStoreMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.WebServicePhysicalStoreMBean](#) entity.

/management/weblogic/{version}/edit/servers/{name}/webService/webServicePersistence/webServicePhysicalStores/{name}

This resource manages a [weblogic.management.configuration.WebServicePhysicalStoreMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.WebServicePhysicalStoreMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.WebServicePhysicalStoreMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.WebServicePhysicalStoreMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/webService/webServicePersistence/webServicePhysicalStores/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/webService/webServicePersistence/webServicePhysicalStores](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/webService/webServicePersistence/webServicePhysicalStores/{name}](#) **rel**=self

This resource.

POST

Update this [weblogic.management.configuration.WebServicePhysicalStoreMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.WebServicePhysicalStoreMBean](#) entity.

/management/weblogic/{version}/edit/servers/{name}/webService/webServiceReliability

This resource manages a [weblogic.management.configuration.WebServiceReliabilityMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.WebServiceReliabilityMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.WebServiceReliabilityMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/webService/webServiceReliability](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/webService](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/servers/{name}/webService/webServiceReliability](#) **rel**=self

This resource.

POST

Update this [weblogic.management.configuration.WebServiceReliabilityMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.WebServiceReliabilityMBean](#) entity.

/management/weblogic/{version}/edit/serverTemplateCreateForm

This resource manages the create forms for the serverTemplates collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.ServerTemplateMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the serverTemplates collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ServerTemplateMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/serverTemplateCreateForm](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/serverTemplates](#) **rel**=create
The collection resource for this create form resource.
- **uri**=[/management/weblogic/{version}/edit](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/serverTemplateCreateForm](#) **rel**=self
This resource.

/management/weblogic/{version}/edit/serverTemplates

This resource manages a collection of [weblogic.management.configuration.ServerTemplateMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.ServerTemplateMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.ServerTemplateMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/serverTemplates](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/serverTemplateCreateForm](#)
rel=create-form
The create form resource for this collection resource.
- **uri**=[/management/weblogic/{version}/edit](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/serverTemplates](#) **rel**=self
This resource.

POST

Add a new [weblogic.management.configuration.ServerTemplateMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.ServerTemplateMBean](#) entity.

/management/weblogic/{version}/edit/serverTemplates/{name}

This resource manages a [weblogic.management.configuration.ServerTemplateMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

DELETE

Delete this [weblogic.management.configuration.ServerTemplateMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.ServerTemplateMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ServerTemplateMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/IIOP](#)
rel=IIOP
This resource's IIOP singleton resource.
- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/JTAMigratableTarget](#) **rel**=JTAMigratableTarget
This resource's JTAMigratableTarget singleton resource.
- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/SSL](#)
rel=SSL
This resource's SSL singleton resource.
- **rel**=XMLEntityCache
This resource's XMLEntityCache reference to a [weblogic.management.configuration.XMLEntityCacheMBean](#) resource.
- **rel**=XMLRegistry
This resource's XMLRegistry reference to a [weblogic.management.configuration.XMLRegistryMBean](#) resource.
- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}](#)
rel=canonical
This resource.
- **rel**=cluster
This resource's cluster reference to a [weblogic.management.configuration.ClusterMBean](#) resource.
- **rel**=coherenceClusterSystemResource
This resource's coherenceClusterSystemResource reference to a [weblogic.management.configuration.CoherenceClusterSystemResourceMBean](#) resource.
- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/coherenceMemberConfig](#) **rel**=coherenceMemberConfig
This resource's coherenceMemberConfig singleton resource.
- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/configurationProperties](#) **rel**=configurationProperties
This resource's configurationProperties collection resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/configurationPropertyCreateForm **rel**=configurationPropertyCreateForm
The create form resource for this resource's configurationProperties collection resource.
- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/dataSource **rel**=dataSource
This resource's dataSource singleton resource.
- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/defaultFileStore **rel**=defaultFileStore
This resource's defaultFileStore singleton resource.
- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/executeQueues **rel**=executeQueues
This resource's executeQueues collection resource.
- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/federationServices **rel**=federationServices
This resource's federationServices singleton resource.
- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/log **rel**=log
This resource's log singleton resource.
- **rel**=machine
This resource's machine reference to a weblogic.management.configuration.MachineMBean resource.
- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/networkAccessPointCreateForm **rel**=networkAccessPointCreateForm
The create form resource for this resource's networkAccessPoints collection resource.
- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/networkAccessPoints **rel**=networkAccessPoints
This resource's networkAccessPoints collection resource.
- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/overloadProtection **rel**=overloadProtection
This resource's overloadProtection singleton resource.
- **uri**=/management/weblogic/{version}/edit/serverTemplates **rel**=parent
The parent resource of this resource.
- **rel**=reliableDeliveryPolicy
This resource's reliableDeliveryPolicy reference to a weblogic.management.configuration.WSReliableDeliveryPolicyMBean resource.
- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name} **rel**=self
This resource.
- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDebug **rel**=serverDebug
This resource's serverDebug singleton resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig **rel**=serverDiagnosticConfig
This resource's serverDiagnosticConfig singleton resource.
- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverStart **rel**=serverStart
This resource's serverStart singleton resource.
- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/singleSignOnServices **rel**=singleSignOnServices
This resource's singleSignOnServices singleton resource.
- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/transactionLogJDBCStore **rel**=transactionLogJDBCStore
This resource's transactionLogJDBCStore singleton resource.
- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/webServer **rel**=webServer
This resource's webServer singleton resource.
- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/webService **rel**=webService
This resource's webService singleton resource.

POST

Update this [weblogic.management.configuration.ServerTemplateMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.ServerTemplateMBean](#) entity.

/management/weblogic/{version}/edit/serverTemplates/{name}/coherenceMemberConfig

This resource manages a [weblogic.management.configuration.CoherenceMemberConfigMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.CoherenceMemberConfigMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.CoherenceMemberConfigMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/coherenceMemberConfig](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/coherenceMemberConfig](#) **rel**=self

This resource.

POST

Update this [weblogic.management.configuration.CoherenceMemberConfigMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.CoherenceMemberConfigMBean](#) entity.

/management/weblogic/{version}/edit/serverTemplates/{name}/configurationProperties

This resource manages a collection of [weblogic.management.configuration.ConfigurationPropertyMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.ConfigurationPropertyMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.ConfigurationPropertyMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/configurationProperties rel=canonical](#)
This resource.
- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/configurationPropertyCreateForm rel=create-form](#)
The create form resource for this collection resource.
- [uri=/management/weblogic/{version}/edit/serverTemplates/{name} rel=parent](#)
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/configurationProperties rel=self](#)
This resource.

POST

Add a new [weblogic.management.configuration.ConfigurationPropertyMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.ConfigurationPropertyMBean](#) entity.

/management/weblogic/{version}/edit/serverTemplates/{name}/configurationProperties/{name}

This resource manages a [weblogic.management.configuration.ConfigurationPropertyMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.ConfigurationPropertyMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.ConfigurationPropertyMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ConfigurationPropertyMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/configurationProperties/{name}](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/configurationProperties](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/configurationProperties/{name}](#) **rel=self**
This resource.

POST

Update this [weblogic.management.configuration.ConfigurationPropertyMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.ConfigurationPropertyMBean](#) entity.

/management/weblogic/{version}/edit/serverTemplates/{name}/configurationPropertyCreateForm

This resource manages the create forms for the configurationProperties collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.ConfigurationPropertyMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the configurationProperties collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ConfigurationPropertyMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/configurationPropertyCreateForm](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/configurationProperties](#) **rel=create**
The collection resource for this create form resource.
- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/configurationPropertyCreateForm](#) **rel=self**
This resource.

/management/weblogic/{version}/edit/serverTemplates/{name}/dataSource

This resource manages a [weblogic.management.configuration.DataSourceMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.DataSourceMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.DataSourceMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/dataSource](#)
rel=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/dataSource/dataSourceLogFile](#) **rel**=dataSourceLogFile

This resource's dataSourceLogFile singleton resource.

- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/dataSource](#)
rel=self

This resource.

POST

Update this [weblogic.management.configuration.DataSourceMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.DataSourceMBean](#) entity.

/management/weblogic/{version}/edit/serverTemplates/{name}/dataSource/dataSourceLogFile

This resource manages a [weblogic.management.configuration.DataSourceLogFileMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.DataSourceLogFileMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.DataSourceLogFileMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/dataSource/dataSourceLogFile](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/dataSource](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/dataSource/dataSourceLogFile](#) **rel=self**
This resource.

POST

POST

Update this [weblogic.management.configuration.DataSourceLogFileMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.DataSourceLogFileMBean](#) entity.

/management/weblogic/{version}/edit/serverTemplates/{name}/defaultFileStore

This resource manages a [weblogic.management.configuration.DefaultFileStoreMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.DefaultFileStoreMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.DefaultFileStoreMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/defaultFileStore](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/defaultFileStore](#) **rel=self**
This resource.

POST

Update this [weblogic.management.configuration.DefaultFileStoreMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.DefaultFileStoreMBean](#) entity.

/management/weblogic/{version}/edit/serverTemplates/{name}/executeQueues

This resource manages a collection of [weblogic.management.configuration.ExecuteQueueMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.configuration.ExecuteQueueMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.ExecuteQueueMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/executeQueues](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/executeQueues](#) **rel**=self
This resource.

/management/weblogic/{version}/edit/serverTemplates/{name}/executeQueues/{name}

This resource manages a [weblogic.management.configuration.ExecuteQueueMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.ExecuteQueueMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ExecuteQueueMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/executeQueues/{name} **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/executeQueues **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/executeQueues/{name} **rel**=self
This resource.

POST

Update this [weblogic.management.configuration.ExecuteQueueMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.ExecuteQueueMBean](#) entity.

/management/weblogic/{version}/edit/serverTemplates/{name}/federationServices

This resource manages a [weblogic.management.configuration.FederationServicesMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.FederationServicesMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.FederationServicesMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/federationServices](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/federationServices](#) **rel**=self
This resource.

POST

Update this [weblogic.management.configuration.FederationServicesMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.FederationServicesMBean](#) entity.

/management/weblogic/{version}/edit/serverTemplates/{name}/IOP

This resource manages a [weblogic.management.configuration.IOPMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.IIOPMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.IIOPMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/IIOP](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/IIOP](#)
rel=self
This resource.

POST

POST

Update this [weblogic.management.configuration.IOPMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.IOPMBean](#) entity.

/management/weblogic/{version}/edit/serverTemplates/{name}/JTAMigratable Target

This resource manages a [weblogic.management.configuration.JTAMigratableTargetMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.JTAMigratableTargetMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.JTAMigratableTargetMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/JTAMigratableTarget](#) **rel**=canonical
This resource.
- **rel**=cluster
This resource's cluster reference to a [weblogic.management.configuration.ClusterMBean](#) resource.
- **rel**=hostingServer
This resource's hostingServer reference to a [weblogic.management.configuration.ServerMBean](#) resource.
- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/JTAMigratableTarget](#) **rel**=self
This resource.
- **rel**=userPreferredServer
This resource's userPreferredServer reference to a [weblogic.management.configuration.ServerMBean](#) resource.

POST

Update this [weblogic.management.configuration.JTAMigratableTargetMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.JTAMigratableTargetMBean](#) entity.

/management/weblogic/{version}/edit/serverTemplates/{name}/log

This resource manages a [weblogic.management.configuration.LogMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.LogMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.LogMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/log](#)
rel=canonical
This resource.
- **rel**=domainLogBroadcastFilter
This resource's domainLogBroadcastFilter reference to a [weblogic.management.configuration.LogFilterMBean](#) resource.
- **rel**=logFileFilter
This resource's logFileFilter reference to a [weblogic.management.configuration.LogFilterMBean](#) resource.
- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/log](#)
rel=self
This resource.
- **rel**=stdoutFilter
This resource's stdoutFilter reference to a [weblogic.management.configuration.LogFilterMBean](#) resource.

POST

Update this [weblogic.management.configuration.LogMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.LogMBean](#) entity.

/management/weblogic/{version}/edit/serverTemplates/{name}/networkAccessPointCreateForm

This resource manages the create forms for the networkAccessPoints collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.NetworkAccessPointMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the `networkAccessPoints` collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.NetworkAccessPointMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/networkAccessPointCreateForm](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/networkAccessPoints](#) **rel**=create

The collection resource for this create form resource.

- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/networkAccessPointCreateForm](#) **rel**=self

This resource.

/management/weblogic/{version}/edit/serverTemplates/{name}/networkAccessPoints

This resource manages a collection of [weblogic.management.configuration.NetworkAccessPointMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.NetworkAccessPointMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.NetworkAccessPointMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/networkAccessPoints](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/networkAccessPointCreateForm](#) **rel**=create-form
The create form resource for this collection resource.
- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/networkAccessPoints](#) **rel**=self
This resource.

POST

Add a new [weblogic.management.configuration.NetworkAccessPointMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.NetworkAccessPointMBean](#) entity.

/management/weblogic/{version}/edit/serverTemplates/{name}/networkAccessPoints/{name}

This resource manages a [weblogic.management.configuration.NetworkAccessPointMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.NetworkAccessPointMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.NetworkAccessPointMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.NetworkAccessPointMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/networkAccessPoints/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/networkAccessPoints](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/networkAccessPoints/{name}](#) **rel**=self

This resource.

POST

Update this [weblogic.management.configuration.NetworkAccessPointMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.NetworkAccessPointMBean](#) entity.

/management/weblogic/{version}/edit/serverTemplates/{name}/overloadProtection

This resource manages a [weblogic.management.configuration.OverloadProtectionMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.OverloadProtectionMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.OverloadProtectionMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/overloadProtection](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/overloadProtection](#) **rel**=self
This resource.
- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/overloadProtection/serverFailureTrigger](#) **rel**=serverFailureTrigger
This resource's serverFailureTrigger singleton resource.
- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/overloadProtection/serverFailureTriggerCreateForm](#) **rel**=serverFailureTriggerCreateForm
The create form resource for this resource's serverFailureTrigger optional singleton resource.

POST

POST

Update this [weblogic.management.configuration.OverloadProtectionMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.OverloadProtectionMBean](#) entity.

/management/weblogic/{version}/edit/serverTemplates/{name}/overloadProtection/serverFailureTrigger

This resource manages a [weblogic.management.configuration.ServerFailureTriggerMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

DELETE

Delete this [weblogic.management.configuration.ServerFailureTriggerMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.ServerFailureTriggerMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ServerFailureTriggerMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/overloadProtection/serverFailureTrigger **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/overloadProtection/serverFailureTriggerCreateForm **rel**=create-form
The create form resource for this optional singleton resource.
- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/overloadProtection **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/overloadProtection/serverFailureTrigger **rel**=self
This resource.

POST

Update this [weblogic.management.configuration.ServerFailureTriggerMBean](#) instance if it exists; otherwise, create it.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.ServerFailureTriggerMBean](#) entity.

/management/weblogic/{version}/edit/serverTemplates/{name}/overloadProtection/serverFailureTriggerCreateForm

This resource manages the create forms for the serverFailureTrigger optional singleton instance.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.ServerFailureTriggerMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the [serverFailureTrigger](#) optional singleton resource to create a new instance if it currently does not exist.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ServerFailureTriggerMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/overloadProtection/serverFailureTriggerCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/overloadProtection/serverFailureTriggerCreateForm](#) **rel=create**

The optional singleton resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/overloadProtection](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/overloadProtection/serverFailureTriggerCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDebug

This resource manages a [weblogic.management.configuration.ServerDebugMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.ServerDebugMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ServerDebugMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/serverDebug](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/serverDebug/debugScopeCreateForm](#) **rel**=debugScopeCreateForm
The create form resource for this resource's debugScopes collection resource.
- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/serverDebug/debugScopes](#) **rel**=debugScopes
This resource's debugScopes collection resource.
- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/serverDebug](#)
rel=self
This resource.
- **rel**=server
This resource's server reference to a [weblogic.management.configuration.ServerMBean](#) resource.

POST

Update this [weblogic.management.configuration.ServerDebugMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.ServerDebugMBean](#) entity.

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDebug/debugScopecreateForm

This resource manages the create forms for the debugScopes collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.DebugScopeMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the debugScopes collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.DebugScopeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDebug/debugScopeCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDebug/debugScopes](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDebug](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDebug/debugScopeCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDebug/debugScopes

This resource manages a collection of [weblogic.management.configuration.DebugScopeMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.DebugScopeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.DebugScopeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDebug/debugScopes](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDebug/debugScopeCreateForm](#) **rel=create-form**
The create form resource for this collection resource.
- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDebug](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDebug/debugScopes](#) **rel=self**
This resource.

POST

Add a new [weblogic.management.configuration.DebugScopeMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.DebugScopeMBean](#) entity.

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDebug/debugScopes/{name}

This resource manages a [weblogic.management.configuration.DebugScopeMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.DebugScopeMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.DebugScopeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.DebugScopeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDebug/debugScopes/{name} **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDebug/debugScopes **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDebug/debugScopes/{name} **rel**=self
This resource.

POST

POST

Update this [weblogic.management.configuration.DebugScopeMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.DebugScopeMBean](#) entity.

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig

This resource manages a [weblogic.management.configuration.WLDFServerDiagnosticMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.WLDFServerDiagnosticMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.WLDFServerDiagnosticMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean](#)
rel=WLDFBuiltinSystemResourceDescriptorBean
This resource's WLDFBuiltinSystemResourceDescriptorBean singleton resource.
- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFDataRetirementByAgeCreateForm](#)
rel=WLDFDataRetirementByAgeCreateForm
The create form resource for this resource's WLDFDataRetirementByAges collection resource.
- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFDataRetirementByAges](#) **rel**=WLDFDataRetirementByAges
This resource's WLDFDataRetirementByAges collection resource.
- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/lookupWLDFDataRetirement](#) **rel**=action
title=lookupWLDFDataRetirement
This resource's lookupWLDFDataRetirement action resource.
- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig](#) **rel**=canonical
This resource.
- **rel**=diagnosticJDBCResource
This resource's diagnosticJDBCResource reference to a [weblogic.management.configuration.JDBCSystemResourceMBean](#) resource.
- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig](#) **rel**=self
This resource.

POST

Update this [weblogic.management.configuration.WLDFServerDiagnosticMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.WLDFServerDiagnosticMBean](#) entity.

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/lookupWLDFDataRetirement

The resource supports the following methods:

- [POST](#)

POST

Look up WLDFDataRetirement object with given name

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

name

Name of the data retirement

Type: string

Response Body

Contains a JSON object with a `weblogic.management.configuration.WLDFDataRetirementMBean` reference return field.

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean

This resource manages a [weblogic.diagnostics.descriptor.WLDFResourceBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.diagnostics.descriptor.WLDFResourceBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFResourceBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/harvester **rel**=harvester
This resource's harvester singleton resource.
- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/instrumentation **rel**=instrumentation
This resource's instrumentation singleton resource.
- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean **rel**=self
This resource.
- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification **rel**=watchNotification
This resource's watchNotification singleton resource.

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/harvester

This resource manages a [weblogic.diagnostics.descriptor.WLDFHarvesterBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.diagnostics.descriptor.WLDFHarvesterBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFHarvesterBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/harvester **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/harvester/harvestedTypeeCreateForm **rel**=harvestedTypeCreateForm

The create form resource for this resource's harvestedTypes collection resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/harvester/harvestedTypes **rel**=harvestedTypes

This resource's harvestedTypes collection resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/harvester **rel**=self

This resource.

POST

Update this [weblogic.diagnostics.descriptor.WLDFHarvesterBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFHarvesterBean](#) entity.

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/harvester/harvestedTypeCreateForm

This resource manages the create forms for the harvestedTypes collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFHarvestedTypeBean](#) entity populated with default values that can be customized then posted (using the POST method) to the harvestedTypes collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFHarvestedTypeBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/harvester/harvestedTypeCreateForm **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/harvester/harvestedTypes **rel**=create

The collection resource for this create form resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/harvester **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/harvester/harvestedTypeCreateForm **rel**=self

This resource.

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/harvester/harvestedTypes

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFHarvestedTypeBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFHarvestedTypeBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFHarvestedTypeBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/harvester/harvestedTypes](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/harvester/harvestedTypeeCreateForm](#) **rel**=create-form

The create form resource for this collection resource.

- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/harvester](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/harvester/harvestedTypes](#) **rel**=self

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFHarvestedTypeBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFHarvestedTypeBean](#) entity.

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/harvester/harvestedTypes/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFHarvestedTypeBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFHarvestedTypeBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.diagnostics.descriptor.WLDFHarvestedTypeBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFHarvestedTypeBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/harvester/harvestedTypes/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/harvester/harvestedTypes **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/harvester/harvestedTypes/{name} **rel**=self

This resource.

POST

Update this [weblogic.diagnostics.descriptor.WLDFHarvestedTypeBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFHarvestedTypeBean](#) entity.

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/instrumentation

This resource manages a [weblogic.diagnostics.descriptor.WLDFInstrumentationBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.diagnostics.descriptor.WLDFInstrumentationBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFInstrumentationBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/instrumentation/WLDFInstrumentationMonitorCreateForm
rel=WLDFInstrumentationMonitorCreateForm

The create form resource for this resource's WLDFInstrumentationMonitors collection resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/instrumentation/WLDFInstrumentationMonitors **rel**=WLDFInstrumentationMonitors

This resource's WLDFInstrumentationMonitors collection resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/instrumentation **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/instrumentation **rel**=self

This resource.

POST

Update this [weblogic.diagnostics.descriptor.WLDFInstrumentationBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFInstrumentationBean](#) entity.

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/instrumentation/WLDFInstrumentationMonitorCreateForm

This resource manages the create forms for the WLDFInstrumentationMonitors collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFInstrumentationMonitorBean](#) entity populated with default values that can be customized then posted (using the POST method) to the [WLDFInstrumentationMonitors](#) collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFInstrumentationMonitorBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/instrumentation/WLDFInstrumentationMonitorCreateForm](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/instrumentation/WLDFInstrumentationMonitors](#) **rel**=create

The collection resource for this create form resource.

- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/instrumentation](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/instrumentation/WLDFInstrumentationMonitorCreateForm](#) **rel**=self

This resource.

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/instrumentation/WLDFInstrumentationMonitors

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFInstrumentationMonitorBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFInstrumentationMonitorBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFInstrumentationMonitorBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/instrumentation/WLDFInstrumentationMonitors **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/instrumentation/WLDFInstrumentationMonitorCreateForm **rel**=create-form

The create form resource for this collection resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/instrumentation **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/instrumentation/WLDFInstrumentationMonitors **rel**=self

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFInstrumentationMonitorBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFInstrumentationMonitorBean](#) entity.

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/instrumentation/WLDFInstrumentationMonitors/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFInstrumentationMonitorBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFInstrumentationMonitorBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.diagnostics.descriptor.WLDFInstrumentationMonitorBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFInstrumentationMonitorBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/instrumentation/WLDFInstrumentationMonitors/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/instrumentation/WLDFInstrumentationMonitors](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/instrumentation/WLDFInstrumentationMonitors/{name}](#) **rel**=self

This resource.

POST

Update this [weblogic.diagnostics.descriptor.WLDFInstrumentationMonitorBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFInstrumentationMonitorBean](#) entity.

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification

This resource manages a [weblogic.diagnostics.descriptor.WLDFWatchNotificationBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.diagnostics.descriptor.WLDFWatchNotificationBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFWatchNotificationBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/JMSNotificationCreateForm](#) **rel**=JMSNotificationCreateForm

The create form resource for this resource's JMSNotifications collection resource.

- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/JMSNotifications](#) **rel**=JMSNotifications

This resource's JMSNotifications collection resource.

- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/JMXNotificationCreateForm](#) **rel**=JMXNotificationCreateForm

The create form resource for this resource's JMXNotifications collection resource.

- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/JMXNotifications](#) **rel**=JMXNotifications

This resource's JMXNotifications collection resource.

- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/RESTNotificationCreateForm](#) **rel**=RESTNotificationCreateForm

The create form resource for this resource's RESTNotifications collection resource.

- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/RESTNotifications](#) **rel**=RESTNotifications

This resource's RESTNotifications collection resource.

- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/SMTNotificationCreateForm](#) **rel**=SMTPNotificationCreateForm

The create form resource for this resource's SMTPNotifications collection resource.

- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/SMTNotifications](#) **rel**=SMTPNotifications

This resource's SMTPNotifications collection resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/SNMPNotificationCreateForm **rel**=SNMPNotificationCreateForm
The create form resource for this resource's SNMPNotifications collection resource.
- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/SNMPNotifications **rel**=SNMPNotifications
This resource's SNMPNotifications collection resource.
- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/lookupActions **rel**=action **title**=lookupActions
This resource's lookupActions action resource.
- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/lookupNotification **rel**=action **title**=lookupNotification
This resource's lookupNotification action resource.
- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actionCreateForm **rel**=actionCreateForm
The create form resource for this resource's actions collection resource.
- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions **rel**=actions
This resource's actions collection resource.
- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/heapDumpActionCreateForm **rel**=heapDumpActionCreateForm
The create form resource for this resource's heapDumpActions collection resource.
- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/heapDumpActions **rel**=heapDumpActions
This resource's heapDumpActions collection resource.
- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/imageNotificationCreateForm **rel**=imageNotificationCreateForm
The create form resource for this resource's imageNotifications collection resource.
- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/imageNotifications **rel**=imageNotifications
This resource's imageNotifications collection resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/logActionCreateForm **rel**=logActionCreateForm

The create form resource for this resource's logActions collection resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/logActions **rel**=logActions

This resource's logActions collection resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/scaleDownActionCreateForm **rel**=scaleDownActionCreateForm

The create form resource for this resource's scaleDownActions collection resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/scaleDownActions **rel**=scaleDownActions

This resource's scaleDownActions collection resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/scaleUpActionCreateForm **rel**=scaleUpActionCreateForm

The create form resource for this resource's scaleUpActions collection resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/scaleUpActions **rel**=scaleUpActions

This resource's scaleUpActions collection resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/scriptActionCreateForm **rel**=scriptActionCreateForm

The create form resource for this resource's scriptActions collection resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/scriptActions **rel**=scriptActions

This resource's scriptActions collection resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification **rel**=self

This resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/threadDumpActionCreateForm **rel**=threadDumpActionCreateForm

The create form resource for this resource's threadDumpActions collection resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/threadDumpActions **rel**=threadDumpActions

This resource's threadDumpActions collection resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/watchCreateForm **rel**=watchCreateForm

The create form resource for this resource's watches collection resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/watches **rel**=watches

This resource's watches collection resource.

POST

Update this [weblogic.diagnostics.descriptor.WLDFWatchNotificationBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFWatchNotificationBean](#) entity.

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actionCreateForm

This resource manages the create forms for the actions collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFActionBean](#) entity populated with default values that can be customized then posted (using the POST method) to the actions collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFActionBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actionCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actionCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFActionBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFActionBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFActionBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actionCreateForm **rel**=create-form

The create form resource for this collection resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions **rel**=self

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFActionBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFActionBean](#) entity.

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFActionBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFActionBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.diagnostics.descriptor.WLDFActionBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFActionBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/arrayProperties](#) **rel=arrayProperties**

This resource's arrayProperties collection resource.

- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/arrayPropertyCreateForm](#) **rel=arrayPropertyCreateForm**

The create form resource for this resource's arrayProperties collection resource.

- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/configurationProperties](#) **rel=configurationProperties**

This resource's configurationProperties collection resource.

- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/encryptedProperties](#) **rel=encryptedProperties**

This resource's encryptedProperties collection resource.

- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/encryptedPropertyCreateForm](#) **rel=encryptedPropertyCreateForm**

The create form resource for this resource's encryptedProperties collection resource.

- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapProperties](#) **rel=mapProperties**

This resource's mapProperties collection resource.

- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapPropertyCreateForm](#) **rel=mapPropertyCreateForm**

The create form resource for this resource's mapProperties collection resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/properties **rel**=properties

This resource's properties collection resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/propertyCreateForm **rel**=propertyCreateForm

The create form resource for this resource's properties collection resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name} **rel**=self

This resource.

POST

Update this [weblogic.diagnostics.descriptor.WLDFActionBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFActionBean](#) entity.

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/arrayProperties

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFArrayPropertyBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFArrayPropertyBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFArrayPropertyBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/arrayProperties **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/arrayPropertyCreateForm **rel**=create-form

The create form resource for this collection resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/arrayProperties **rel**=self

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFArrayPropertyBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFArrayPropertyBean](#) entity.

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/arrayProperties/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFArrayPropertyBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFArrayPropertyBean](#) instance.

Roles

Admin

GET

Get this [weblogic.diagnostics.descriptor.WLDFArrayPropertyBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFArrayPropertyBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/arrayProperties/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/arrayProperties **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/arrayProperties/{name} **rel**=self

This resource.

POST

Update this [weblogic.diagnostics.descriptor.WLDFArrayPropertyBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFArrayPropertyBean](#) entity.

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/arrayPropertyCreateForm

This resource manages the create forms for the arrayProperties collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFArrayPropertyBean](#) entity populated with default values that can be customized then posted (using the POST method) to the arrayProperties collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFArrayPropertyBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/arrayPropertyCreateForm **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/arrayProperties **rel**=create

The collection resource for this create form resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/arrayPropertyCreateForm **rel**=self

This resource.

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/configurationProperties

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFConfigurationPropertyBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFConfigurationPropertyBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFConfigurationPropertyBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/configurationProperties **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/configurationProperties **rel**=self

This resource.

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/configurationProperties/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFConfigurationPropertyBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.diagnostics.descriptor.WLDFConfigurationPropertyBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFConfigurationPropertyBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/configurationProperties/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/configurationProperties **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/configurationProperties/{name} **rel**=self

This resource.

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/encryptedProperties

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/encryptedProperties](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/encryptedPropertyCreateForm](#) **rel**=create-form

The create form resource for this collection resource.

- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/encryptedProperties](#) **rel**=self

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) entity.

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/encryptedProperties/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) instance.

Roles

Admin

GET

Get this [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/encryptedProperties/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/encryptedProperties **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/encryptedProperties/{name} **rel**=self

This resource.

POST

Update this [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) entity.

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/encryptedPropertyCreateForm

This resource manages the create forms for the encryptedProperties collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) entity populated with default values that can be customized then posted (using the POST method) to the encryptedProperties collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/encryptedPropertycreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/encryptedProperties](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/encryptedPropertycreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapProperties

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFConfigurationPropertiesBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFConfigurationPropertiesBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFConfigurationPropertiesBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapProperties](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapPropertyCreateForm](#) **rel=create-form**

The create form resource for this collection resource.

- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapProperties](#) **rel=self**

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFConfigurationPropertiesBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFConfigurationPropertiesBean](#) entity.

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapProperties/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFConfigurationPropertiesBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFConfigurationPropertiesBean](#) instance.

Roles

Admin

GET

Get this [weblogic.diagnostics.descriptor.WLDFConfigurationPropertiesBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFConfigurationPropertiesBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapProperties/{name}](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapProperties/{name}/configurationProperties](#) **rel=configurationProperties**

This resource's configurationProperties collection resource.

- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapProperties/{name}/encryptedProperties](#) **rel=encryptedProperties**

This resource's encryptedProperties collection resource.

- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapProperties/{name}/encryptedPropertyCreateForm](#) **rel=encryptedPropertyCreateForm**

The create form resource for this resource's encryptedProperties collection resource.

- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapProperties](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapProperties/{name}/properties](#) **rel=properties**

This resource's properties collection resource.

- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapProperties/{name}/propertyCreateForm](#) **rel=propertyCreateForm**

The create form resource for this resource's properties collection resource.

- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapProperties/{name}](#) **rel=self**

GET

This resource.

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapProperties/{name}/configurationProperties

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFConfigurationPropertyBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFConfigurationPropertyBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFConfigurationPropertyBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapProperties/{name}/configurationProperties **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapProperties/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapProperties/{name}/configurationProperties **rel**=self

This resource.

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapProperties/{name}/configurationProperties/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFConfigurationPropertyBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.diagnostics.descriptor.WLDFConfigurationPropertyBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFConfigurationPropertyBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapProperties/{name}/configurationProperties/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapProperties/{name}/configurationProperties **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapProperties/{name}/configurationProperties/{name} **rel**=self

This resource.

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapProperties/{name}/encryptedProperties

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapProperties/{name}/encryptedProperties](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapProperties/{name}/encryptedPropertyCreateForm](#) **rel**=create-form

The create form resource for this collection resource.

- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapProperties/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapProperties/{name}/encryptedProperties](#) **rel**=self

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) entity.

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapProperties/{name}/encryptedProperties/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapProperties/{name}/encryptedProperties/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapProperties/{name}/encryptedProperties **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapProperties/{name}/encryptedProperties/{name} **rel**=self

This resource.

POST

Update this [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) entity.

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapProperties/{name}/encryptedPropertyCreateForm

This resource manages the create forms for the encryptedProperties collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) entity populated with default values that can be customized then posted (using the POST method) to the encryptedProperties collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapProperties/{name}/encryptedPropertyCreateForm **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapProperties/{name}/encryptedProperties **rel**=create

The collection resource for this create form resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapProperties/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapProperties/{name}/encryptedPropertyCreateForm **rel**=self

This resource.

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapProperties/{name}/properties

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapProperties/{name}/properties **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapProperties/{name}/propertyCreateForm **rel**=create-form

The create form resource for this collection resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapProperties/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapProperties/{name}/properties **rel**=self

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) entity.

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapProperties/{name}/properties/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapProperties/{name}/properties/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapProperties/{name}/properties **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapProperties/{name}/properties/{name} **rel**=self

This resource.

POST

Update this [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) entity.

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapProperties/{name}/propertyCreateForm

This resource manages the create forms for the properties collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) entity populated with default values that can be customized then posted (using the POST method) to the properties collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapProperties/{name}/propertycreateForm **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapProperties/{name}/properties **rel**=create

The collection resource for this create form resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapProperties/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapProperties/{name}/propertycreateForm **rel**=self

This resource.

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapPropertyCreateForm

This resource manages the create forms for the mapProperties collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFConfigurationPropertiesBean](#) entity populated with default values that can be customized then posted (using the POST method) to the `mapProperties` collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFConfigurationPropertiesBean](#) entity.

This method can return the following links:

- **uri**=`/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapPropertycreateForm` **rel**=canonical

This resource.

- **uri**=`/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapProperties` **rel**=create

The collection resource for this create form resource.

- **uri**=`/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}` **rel**=parent

The parent resource of this resource.

- **uri**=`/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/mapPropertycreateForm` **rel**=self

This resource.

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/properties

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/properties **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/propertycreateForm **rel**=create-form

The create form resource for this collection resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/properties **rel**=self

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) entity.

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/properties/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) instance.

Roles

Admin

GET

Get this [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/properties/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/properties](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/properties/{name}](#) **rel**=self

This resource.

POST

Update this [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) entity.

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/propertyCreateForm

This resource manages the create forms for the properties collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) entity populated with default values that can be customized then posted (using the POST method) to the properties collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/propertycreateForm **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/properties **rel**=create

The collection resource for this create form resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/actions/{name}/propertycreateForm **rel**=self

This resource.

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/heapDumpActionCreateForm

This resource manages the create forms for the heapDumpActions collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFHeapDumpActionBean](#) entity populated with default values that can be customized then posted (using the POST method) to the heapDumpActions collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFHeapDumpActionBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/heapDumpActionCreateForm **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/heapDumpActions **rel**=create

The collection resource for this create form resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/heapDumpActionCreateForm **rel**=self

This resource.

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/heapDumpActions

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFHeapDumpActionBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFHeapDumpActionBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFHeapDumpActionBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/heapDumpActions **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/heapDumpActionCreateForm **rel**=create-form

The create form resource for this collection resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/heapDumpActions **rel**=self

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFHeapDumpActionBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFHeapDumpActionBean](#) entity.

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/heapDumpActions/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFHeapDumpActionBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFHeapDumpActionBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.diagnostics.descriptor.WLDFHeapDumpActionBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFHeapDumpActionBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/heapDumpActions/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/heapDumpActions **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/heapDumpActions/{name} **rel**=self

This resource.

POST

POST

Update this [weblogic.diagnostics.descriptor.WLDFHeapDumpActionBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFHeapDumpActionBean](#) entity.

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/imageNotificationCreateForm

This resource manages the create forms for the imageNotifications collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFImageNotificationBean](#) entity populated with default values that can be customized then posted (using the POST method) to the `imageNotifications` collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFImageNotificationBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/imageNotificationCreateForm](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/imageNotifications](#) **rel**=create

The collection resource for this create form resource.

- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/imageNotificationCreateForm](#) **rel**=self

This resource.

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/imageNotifications

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFImageNotificationBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFImageNotificationBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFImageNotificationBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/imageNotifications](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/imageNotificationCreateForm](#) **rel**=create-form

The create form resource for this collection resource.

- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/imageNotifications](#) **rel**=self

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFImageNotificationBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFImageNotificationBean](#) entity.

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/imageNotifications/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFImageNotificationBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFImageNotificationBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.diagnostics.descriptor.WLDFImageNotificationBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFImageNotificationBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/imageNotifications/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/imageNotifications **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/imageNotifications/{name} **rel**=self

This resource.

POST

Update this [weblogic.diagnostics.descriptor.WLDFImageNotificationBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFImageNotificationBean](#) entity.

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/JMSNotificationCreateForm

This resource manages the create forms for the JMSNotifications collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFJMSNotificationBean](#) entity populated with default values that can be customized then posted (using the POST method) to the JMSNotifications collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFJMSNotificationBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/JMSNotificationCreateForm **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/JMSNotifications **rel**=create

The collection resource for this create form resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/JMSNotificationCreateForm **rel**=self

This resource.

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/JMS Notifications

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFJMSNotificationBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFJMSNotificationBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFJMSNotificationBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/JMSNotifications **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/JMSNotificationCreateForm **rel**=create-form

The create form resource for this collection resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/JMSNotifications **rel**=self

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFJMSNotificationBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFJMSNotificationBean](#) entity.

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/JMS Notifications/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFJMSNotificationBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFJMSNotificationBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.diagnostics.descriptor.WLDFJMSNotificationBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFJMSNotificationBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/JMSNotifications/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/JMSNotifications **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/JMSNotifications/{name} **rel**=self

This resource.

POST

Update this [weblogic.diagnostics.descriptor.WLDFJMSNotificationBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFJMSNotificationBean](#) entity.

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/JMXNotificationCreateForm

This resource manages the create forms for the JMXNotifications collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFJMXNotificationBean](#) entity populated with default values that can be customized then posted (using the POST method) to the JMXNotifications collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFJMXNotificationBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/JMXNotificationCreateForm **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/JMXNotifications **rel**=create

The collection resource for this create form resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/JMXNotificationCreateForm **rel**=self

This resource.

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/JMX Notifications

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFJMXNotificationBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFJMXNotificationBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFJMXNotificationBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/JMXNotifications](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/JMXNotificationCreateForm](#) **rel**=create-form

The create form resource for this collection resource.

- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/JMXNotifications](#) **rel**=self

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFJMXNotificationBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFJMXNotificationBean](#) entity.

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/JMXNotifications/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFJMXNotificationBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFJMXNotificationBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.diagnostics.descriptor.WLDFJMXNotificationBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFJMXNotificationBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/JMXNotifications/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/JMXNotifications **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/JMXNotifications/{name} **rel**=self

This resource.

POST

Update this [weblogic.diagnostics.descriptor.WLDFJMXNotificationBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFJMXNotificationBean](#) entity.

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/logActionCreateForm

This resource manages the create forms for the logActions collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFLogActionBean](#) entity populated with default values that can be customized then posted (using the POST method) to the logActions collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFLogActionBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/logActionCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/logActions](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/logActionCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/logActions

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFLogActionBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFLogActionBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFLogActionBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/logActions **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/logActionCreateForm **rel**=create-form

The create form resource for this collection resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/logActions **rel**=self

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFLogActionBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFLogActionBean](#) entity.

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/logActions/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFLogActionBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFLogActionBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.diagnostics.descriptor.WLDFLogActionBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFLogActionBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/logActions/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/logActions **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/logActions/{name} **rel**=self

This resource.

POST

Update this [weblogic.diagnostics.descriptor.WLDFLogActionBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFLogActionBean](#) entity.

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/lookupActions

The resource supports the following methods:

- [POST](#)

POST

Roles

Admin, Deployer

Request Body

Must contain a JSON object with the following fields:

typeName

typeName

Type: string

Response Body

Contains a JSON object with a array of
weblogic.diagnostics.descriptor.WLDFActionBean references return field.

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/lookupNotification

The resource supports the following methods:

- [POST](#)

POST

Looks up an action with the given name.

Roles

Admin, Deployer

Request Body

Must contain a JSON object with the following fields:

name

name

Type: string

Response Body

Contains a JSON object with a `weblogic.diagnostics.descriptor.WLDFNotificationBean` reference return field.

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/RESTNotificationCreateForm

This resource manages the create forms for the RESTNotifications collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFRESTNotificationBean](#) entity populated with default values that can be customized then posted (using the POST method) to the RESTNotifications collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFRESTNotificationBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/RESTNotificationCreateForm **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/RESTNotifications **rel**=create

The collection resource for this create form resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/RESTNotificationCreateForm **rel**=self

This resource.

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/RESTNotifications

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFRESTNotificationBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFRESTNotificationBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFRESTNotificationBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/RESTNotifications](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/RESTNotificationCreateForm](#) **rel**=create-form

The create form resource for this collection resource.

- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/RESTNotifications](#) **rel**=self

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFRESTNotificationBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFRESTNotificationBean](#) entity.

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/RESTNotifications/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFRESTNotificationBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFRESTNotificationBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.diagnostics.descriptor.WLDFRESTNotificationBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFRESTNotificationBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/RESTNotifications/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/RESTNotifications](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/RESTNotifications/{name}](#) **rel**=self

This resource.

POST

Update this [weblogic.diagnostics.descriptor.WLDFRESTNotificationBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFRESTNotificationBean](#) entity.

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/scaleDownActionCreateForm

This resource manages the create forms for the scaleDownActions collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFScaleDownActionBean](#) entity populated with default values that can be customized then posted (using the POST method) to the `scaleDownActions` collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFScaleDownActionBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/scaleDownActionCreateForm **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/scaleDownActions **rel**=create

The collection resource for this create form resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/scaleDownActionCreateForm **rel**=self

This resource.

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/scaleDownActions

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFScaleDownActionBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFScaleDownActionBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFScaleDownActionBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/scaleDownActions **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/scaleDownActionCreateForm **rel**=create-form

The create form resource for this collection resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/scaleDownActions **rel**=self

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFScaleDownActionBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFScaleDownActionBean](#) entity.

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/scaleDownActions/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFScaleDownActionBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFScaleDownActionBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.diagnostics.descriptor.WLDFScaleDownActionBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFScaleDownActionBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/scaleDownActions/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/scaleDownActions **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/scaleDownActions/{name} **rel**=self

This resource.

POST

POST

Update this [weblogic.diagnostics.descriptor.WLDFScaleDownActionBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFScaleDownActionBean](#) entity.

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/scaleUpActionCreateForm

This resource manages the create forms for the scaleUpActions collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFScaleUpActionBean](#) entity populated with default values that can be customized then posted (using the POST method) to the `scaleUpActions` collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFScaleUpActionBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/scaleUpActionCreateForm](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/scaleUpActions](#) **rel**=create

The collection resource for this create form resource.

- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/scaleUpActionCreateForm](#) **rel**=self

This resource.

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/scalaUpActions

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFScaleUpActionBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFScaleUpActionBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFScaleUpActionBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/scaleUpActions](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/scaleUpActionCreateForm](#) **rel**=create-form

The create form resource for this collection resource.

- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/scaleUpActions](#) **rel**=self

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFScaleUpActionBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFScaleUpActionBean](#) entity.

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/scaleUpActions/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFScaleUpActionBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFScaleUpActionBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.diagnostics.descriptor.WLDFScaleUpActionBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFScaleUpActionBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/scaleUpActions/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/scaleUpActions **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/scaleUpActions/{name} **rel**=self

This resource.

POST

Update this [weblogic.diagnostics.descriptor.WLDFScaleUpActionBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFScaleUpActionBean](#) entity.

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/scriptActionCreateForm

This resource manages the create forms for the scriptActions collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFScriptActionBean](#) entity populated with default values that can be customized then posted (using the POST method) to the scriptActions collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFScriptActionBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/scriptActionCreateForm **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/scriptActions **rel**=create

The collection resource for this create form resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/scriptActionCreateForm **rel**=self

This resource.

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/scriptActions

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFScriptActionBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFScriptActionBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFScriptActionBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/scriptActions **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/scriptActionCreateForm **rel**=create-form

The create form resource for this collection resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/scriptActions **rel**=self

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFScriptActionBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFScriptActionBean](#) entity.

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/scriptActions/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFScriptActionBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFScriptActionBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.diagnostics.descriptor.WLDFScriptActionBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFScriptActionBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/scriptActions/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/scriptActions **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/scriptActions/{name} **rel**=self

This resource.

POST

Update this [weblogic.diagnostics.descriptor.WLDFScriptActionBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFScriptActionBean](#) entity.

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/SMT PNotificationCreateForm

This resource manages the create forms for the SMTPNotifications collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFSMTPNotificationBean](#) entity populated with default values that can be customized then posted (using the POST method) to the SMTPNotifications collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFSMTPNotificationBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/SMT
PNotificationCreateForm **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/SMT
PNotifications **rel**=create

The collection resource for this create form resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification
rel=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/SMT
PNotificationCreateForm **rel**=self

This resource.

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/SMT PNotifications

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFSMTNotificationBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFSMTPNotificationBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFSMTPNotificationBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/SMTNotifications](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/SMTNotificationCreateForm](#) **rel**=create-form

The create form resource for this collection resource.

- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/SMTNotifications](#) **rel**=self

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFSMTPNotificationBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFSMTPNotificationBean](#) entity.

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/SMT PNotifications/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFSMTNotificationBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFSMTPNotificationBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.diagnostics.descriptor.WLDFSMTPLNotificationBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFSMTPLNotificationBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/SMTPLNotifications/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/SMTPLNotifications](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/SMTPLNotifications/{name}](#) **rel**=self

This resource.

POST

Update this [weblogic.diagnostics.descriptor.WLDFSMTPNotificationBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFSMTPNotificationBean](#) entity.

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/SNMPNotificationCreateForm

This resource manages the create forms for the SNMPNotifications collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFSNMPNotificationBean](#) entity populated with default values that can be customized then posted (using the POST method) to the SNMPNotifications collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFSNMPNotificationBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/SNMPNotificationCreateForm **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/SNMPNotifications **rel**=create

The collection resource for this create form resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/SNMPNotificationCreateForm **rel**=self

This resource.

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/SNMPNotifications

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFSNMPNotificationBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFSNMPNotificationBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFSNMPNotificationBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/SNMPNotifications **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/SNMPNotificationCreateForm **rel**=create-form

The create form resource for this collection resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/SNMPNotifications **rel**=self

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFSNMPNotificationBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFSNMPNotificationBean](#) entity.

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/SNMPNotifications/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFSNMPNotificationBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFSNMPNotificationBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.diagnostics.descriptor.WLDFSNMPNotificationBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFSNMPNotificationBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/SNMPNotifications/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/SNMPNotifications **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/SNMPNotifications/{name} **rel**=self

This resource.

POST

Update this [weblogic.diagnostics.descriptor.WLDFSNMPNotificationBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFSNMPNotificationBean](#) entity.

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/threadDumpActionCreateForm

This resource manages the create forms for the threadDumpActions collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFThreadDumpActionBean](#) entity populated with default values that can be customized then posted (using the POST method) to the `threadDumpActions` collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFThreadDumpActionBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/threadDumpActionCreateForm](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/threadDumpActions](#) **rel**=create

The collection resource for this create form resource.

- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/threadDumpActionCreateForm](#) **rel**=self

This resource.

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/threadDumpActions

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFThreadDumpActionBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFThreadDumpActionBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFThreadDumpActionBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/threadDumpActions](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/threadDumpActionCreateForm](#) **rel**=create-form

The create form resource for this collection resource.

- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/threadDumpActions](#) **rel**=self

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFThreadDumpActionBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFThreadDumpActionBean](#) entity.

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/threadDumpActions/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFThreadDumpActionBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFThreadDumpActionBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.diagnostics.descriptor.WLDFThreadDumpActionBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFThreadDumpActionBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/threadDumpActions/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/threadDumpActions **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/threadDumpActions/{name} **rel**=self

This resource.

POST

Update this [weblogic.diagnostics.descriptor.WLDFThreadDumpActionBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFThreadDumpActionBean](#) entity.

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/watchCreateForm

This resource manages the create forms for the watches collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFWatchBean](#) entity populated with default values that can be customized then posted (using the POST method) to the watches collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFWatchBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/watchCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/watches](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/watchCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/watches

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFWatchBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFWatchBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFWatchBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/watchNotification](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/watchNotification/createForm](#) **rel=create-form**

The create form resource for this collection resource.

- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/watchNotification](#) **rel=self**

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFWatchBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFWatchBean](#) entity.

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/watches/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFWatchBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFWatchBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.diagnostics.descriptor.WLDFWatchBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFWatchBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/watches/{name} rel=canonical](#)

This resource.

- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/watches rel=parent](#)

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/watches/{name}/schedule rel=schedule](#)

This resource's schedule singleton resource.

- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/watches/{name} rel=self](#)

This resource.

POST

Update this [weblogic.diagnostics.descriptor.WLDFWatchBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFWatchBean](#) entity.

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/watches/{name}/schedule

This resource manages a [weblogic.diagnostics.descriptor.WLDFScheduleBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.diagnostics.descriptor.WLDFScheduleBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFScheduleBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/watches/{name}/schedule **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/watches/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFBuiltinSystemResourceDescriptorBean/watchNotification/watches/{name}/schedule **rel**=self

This resource.

POST

Update this [weblogic.diagnostics.descriptor.WLDFScheduleBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFScheduleBean](#) entity.

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFDataRetirementByAgeCreateForm

This resource manages the create forms for the WLDFDataRetirementByAges collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.WLDFDataRetirementByAgeMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the [WLDFDataRetirementByAges](#) collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.WLDFDataRetirementByAgeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFDataRetirementByAgeCreateForm rel=canonical](#)
This resource.
- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFDataRetirementByAges rel=create](#)
The collection resource for this create form resource.
- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig rel=parent](#)
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFDataRetirementByAgeCreateForm rel=self](#)
This resource.

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFDataRetirementByAges

This resource manages a collection of [weblogic.management.configuration.WLDFDataRetirementByAgeMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.WLDFDataRetirementByAgeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.WLDFDataRetirementByAgeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFDataRetirementByAges **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFDataRetirementByAgeCreateForm **rel**=create-form
The create form resource for this collection resource.
- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFDataRetirementByAges **rel**=self
This resource.

POST

POST

Add a new [weblogic.management.configuration.WLDFDataRetirementByAgeMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.WLDFDataRetirementByAgeMBean](#) entity.

/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFDataRetirementByAges/{name}

This resource manages a [weblogic.management.configuration.WLDFDataRetirementByAgeMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.WLDFDataRetirementByAgeMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.WLDFDataRetirementByAgeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.WLDFDataRetirementByAgeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFDataRetirementByAges/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFDataRetirementByAges **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/serverTemplates/{name}/serverDiagnosticConfig/WLDFDataRetirementByAges/{name} **rel**=self

This resource.

POST

POST

Update this [weblogic.management.configuration.WLDFDataRetirementByAgeMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.WLDFDataRetirementByAgeMBean](#) entity.

/management/weblogic/{version}/edit/serverTemplates/{name}/serverStart

This resource manages a [weblogic.management.configuration.ServerStartMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.ServerStartMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ServerStartMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/serverStartMBean](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/serverStartMBean](#)
rel=self
This resource.

POST

Update this [weblogic.management.configuration.ServerStartMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.ServerStartMBean](#) entity.

/management/weblogic/{version}/edit/serverTemplates/{name}/singleSignOnServices

This resource manages a [weblogic.management.configuration.SingleSignOnServicesMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.SingleSignOnServicesMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SingleSignOnServicesMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/singleSignOnServices](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/singleSignOnServices](#) **rel=self**
This resource.

POST

Update this [weblogic.management.configuration.SingleSignOnServicesMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.SingleSignOnServicesMBean](#) entity.

/management/weblogic/{version}/edit/serverTemplates/{name}/SSL

This resource manages a [weblogic.management.configuration.SSLMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.SSLMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SSLMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/SSL](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/SSL](#)
rel=self
This resource.

POST

Update this [weblogic.management.configuration.SSLMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.SSLMBean](#) entity.

/management/weblogic/{version}/edit/serverTemplates/{name}/transactionLogJDBCStore

This resource manages a [weblogic.management.configuration.TransactionLogJDBCStoreMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.TransactionLogJDBCStoreMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.TransactionLogJDBCStoreMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/transactionLogJDBCStore](#) **rel=canonical**
This resource.
- **rel=dataSource**
This resource's dataSource reference to a [weblogic.management.configuration.JDBCSystemResourceMBean](#) resource.
- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/transactionLogJDBCStore](#) **rel=self**
This resource.

POST

Update this [weblogic.management.configuration.TransactionLogJDBCStoreMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.TransactionLogJDBCStoreMBean](#) entity.

/management/weblogic/{version}/edit/serverTemplates/{name}/webServer

This resource manages a [weblogic.management.configuration.WebServerMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.WebServerMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.WebServerMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/webServerMBean](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/webServerMBean](#) **rel=self**
This resource.
- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/webServer/webServerLog](#) **rel=webServerLog**
This resource's webServerLog singleton resource.

POST

Update this [weblogic.management.configuration.WebServerMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.WebServerMBean](#) entity.

/management/weblogic/{version}/edit/serverTemplates/{name}/webServer/webServerLog

This resource manages a [weblogic.management.configuration.WebServerLogMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.WebServerLogMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.WebServerLogMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/webServer/webServerLog](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/webServer/webServerLog](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/webServer/webServerLog](#) **rel=self**
This resource.

POST

Update this [weblogic.management.configuration.WebServerLogMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.WebServerLogMBean](#) entity.

/management/weblogic/{version}/edit/serverTemplates/{name}/webService

This resource manages a [weblogic.management.configuration.WebServiceMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.WebServiceMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.WebServiceMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/webService](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/webService](#)
rel=self
This resource.
- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/webService/webServiceBuffering](#) **rel**=webServiceBuffering
This resource's webServiceBuffering singleton resource.
- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/webService/webServicePersistence](#) **rel**=webServicePersistence
This resource's webServicePersistence singleton resource.
- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/webService/webServiceReliability](#) **rel**=webServiceReliability
This resource's webServiceReliability singleton resource.

POST

Update this [weblogic.management.configuration.WebServiceMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.WebServiceMBean](#) entity.

/management/weblogic/{version}/edit/serverTemplates/{name}/webService/webServiceBuffering

This resource manages a [weblogic.management.configuration.WebServiceBufferingMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.WebServiceBufferingMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.WebServiceBufferingMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/webService/webServiceBuffering](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/webService](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/webService/webServiceBuffering](#) **rel=self**
This resource.
- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/webService/webServiceBuffering/webServiceRequestBufferingQueue](#) **rel=webServiceRequestBufferingQueue**
This resource's `webServiceRequestBufferingQueue` singleton resource.
- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/webService/webServiceBuffering/webServiceResponseBufferingQueue](#) **rel=webServiceResponseBufferingQueue**
This resource's `webServiceResponseBufferingQueue` singleton resource.

POST

Update this [weblogic.management.configuration.WebServiceBufferingMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.WebServiceBufferingMBean](#) entity.

/management/weblogic/{version}/edit/serverTemplates/{name}/webService/webServiceBuffering/webServiceRequestBufferingQueue

This resource manages a [weblogic.management.configuration.WebServiceRequestBufferingQueueMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.WebServiceRequestBufferingQueueMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.WebServiceRequestBufferingQueueMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/webService/webServiceBuffering/webServiceRequestBufferingQueue](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/webService/webServiceBuffering](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/webService/webServiceBuffering/webServiceRequestBufferingQueue](#) **rel**=self

This resource.

POST

Update this [weblogic.management.configuration.WebServiceRequestBufferingQueueMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.WebServiceRequestBufferingQueueMBean](#) entity.

/management/weblogic/{version}/edit/serverTemplates/{name}/webService/webServiceBuffering/webServiceResponseBufferingQueue

This resource manages a [weblogic.management.configuration.WebServiceResponseBufferingQueueMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.WebServiceResponseBufferingQueueMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.WebServiceResponseBufferingQueueMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/webService/webServiceBuffering/webServiceResponseBufferingQueue rel=canonical](#)
This resource.
- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/webService/webServiceBuffering rel=parent](#)
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/webService/webServiceBuffering/webServiceResponseBufferingQueue rel=self](#)
This resource.

POST

Update this [weblogic.management.configuration.WebServiceResponseBufferingQueueMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.WebServiceResponseBufferingQueueMBean](#) entity.

/management/weblogic/{version}/edit/serverTemplates/{name}/webService/webServicePersistence

This resource manages a [weblogic.management.configuration.WebServicePersistenceMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.WebServicePersistenceMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.WebServicePersistenceMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/webService/webServicePersistence](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/webService](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/webService/webServicePersistence](#) **rel=self**
This resource.
- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/webService/webServicePersistence/webServiceLogicalStoreCreateForm](#) **rel=webServiceLogicalStoreCreateForm**
The create form resource for this resource's `webServiceLogicalStores` collection resource.
- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/webService/webServicePersistence/webServiceLogicalStores](#) **rel=webServiceLogicalStores**
This resource's `webServiceLogicalStores` collection resource.
- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/webService/webServicePersistence/webServicePhysicalStoreCreateForm](#) **rel=webServicePhysicalStoreCreateForm**
The create form resource for this resource's `webServicePhysicalStores` collection resource.
- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/webService/webServicePersistence/webServicePhysicalStores](#) **rel=webServicePhysicalStores**
This resource's `webServicePhysicalStores` collection resource.

POST

Update this [weblogic.management.configuration.WebServicePersistenceMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.WebServicePersistenceMBean](#) entity.

/management/weblogic/{version}/edit/serverTemplates/{name}/webService/webServicePersistence/webServiceLogicalStoreCreateForm

This resource manages the create forms for the webServiceLogicalStores collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.WebServiceLogicalStoreMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the [webServiceLogicalStores](#) collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.WebServiceLogicalStoreMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/webService/webServicePersistence/webServiceLogicalStoreCreateForm](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/webService/webServicePersistence/webServiceLogicalStores](#) **rel=create**
The collection resource for this create form resource.
- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/webService/webServicePersistence](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/webService/webServicePersistence/webServiceLogicalStoreCreateForm](#) **rel=self**
This resource.

/management/weblogic/{version}/edit/serverTemplates/{name}/webService/webServicePersistence/webServiceLogicalStores

This resource manages a collection of [weblogic.management.configuration.WebServiceLogicalStoreMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.WebServiceLogicalStoreMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.WebServiceLogicalStoreMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/webService/webServicePersistence/webServiceLogicalStores](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/webService/webServicePersistence/webServiceLogicalStoreCreateForm](#) **rel=create-form**

The create form resource for this collection resource.

- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/webService/webServicePersistence](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/webService/webServicePersistence/webServiceLogicalStores](#) **rel=self**

This resource.

POST

Add a new [weblogic.management.configuration.WebServiceLogicalStoreMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.WebServiceLogicalStoreMBean](#) entity.

/management/weblogic/{version}/edit/serverTemplates/{name}/webService/webServicePersistence/webServiceLogicalStores/{name}

This resource manages a [weblogic.management.configuration.WebServiceLogicalStoreMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.WebServiceLogicalStoreMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.WebServiceLogicalStoreMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.WebServiceLogicalStoreMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/webService/webServicePersistence/webServiceLogicalStores/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/webService/webServicePersistence/webServiceLogicalStores](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/webService/webServicePersistence/webServiceLogicalStores/{name}](#) **rel**=self

This resource.

POST

Update this [weblogic.management.configuration.WebServiceLogicalStoreMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.WebServiceLogicalStoreMBean](#) entity.

/management/weblogic/{version}/edit/serverTemplates/{name}/webService/webServicePersistence/webServicePhysicalStoreCreateForm

This resource manages the create forms for the webServicePhysicalStores collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.WebServicePhysicalStoreMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the [webServicePhysicalStores](#) collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.WebServicePhysicalStoreMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/webService/webServicePersistence/webServicePhysicalStoreCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/webService/webServicePersistence/webServicePhysicalStores](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/webService/webServicePersistence](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/webService/webServicePersistence/webServicePhysicalStoreCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/serverTemplates/{name}/webService/webServicePersistence/webServicePhysicalStores

This resource manages a collection of [weblogic.management.configuration.WebServicePhysicalStoreMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.WebServicePhysicalStoreMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.WebServicePhysicalStoreMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/webService/webServicePersistence/webServicePhysicalStores](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/webService/webServicePersistence/webServicePhysicalStoreCreateForm](#) **rel=create-form**

The create form resource for this collection resource.

- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/webService/webServicePersistence](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/webService/webServicePersistence/webServicePhysicalStores](#) **rel=self**

This resource.

POST

Add a new [weblogic.management.configuration.WebServicePhysicalStoreMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.WebServicePhysicalStoreMBean](#) entity.

/management/weblogic/{version}/edit/serverTemplates/{name}/webService/webServicePersistence/webServicePhysicalStores/{name}

This resource manages a [weblogic.management.configuration.WebServicePhysicalStoreMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.WebServicePhysicalStoreMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.WebServicePhysicalStoreMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.WebServicePhysicalStoreMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/webService/webServicePersistence/webServicePhysicalStores/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/webService/webServicePersistence/webServicePhysicalStores](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/serverTemplates/{name}/webService/webServicePersistence/webServicePhysicalStores/{name}](#) **rel**=self

This resource.

POST

Update this [weblogic.management.configuration.WebServicePhysicalStoreMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.WebServicePhysicalStoreMBean](#) entity.

/management/weblogic/{version}/edit/serverTemplates/{name}/webService/webServiceReliability

This resource manages a [weblogic.management.configuration.WebServiceReliabilityMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.WebServiceReliabilityMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.WebServiceReliabilityMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/webService/webServiceReliability](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/webService](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/serverTemplates/{name}/webService/webServiceReliability](#) **rel=self**
This resource.

POST

Update this [weblogic.management.configuration.WebServiceReliabilityMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.WebServiceReliabilityMBean](#) entity.

/management/weblogic/{version}/edit/shutdownClassCreateForm

This resource manages the create forms for the shutdownClasses collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.ShutdownClassMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the shutdownClasses collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ShutdownClassMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/shutdownClassCreateForm](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/shutdownClasses](#) **rel**=create
The collection resource for this create form resource.
- **uri**=[/management/weblogic/{version}/edit](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/shutdownClassCreateForm](#) **rel**=self
This resource.

/management/weblogic/{version}/edit/shutdownClasses

This resource manages a collection of [weblogic.management.configuration.ShutdownClassMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.ShutdownClassMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.ShutdownClassMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/shutdownClasses](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/shutdownClassCreateForm](#)
rel=create-form
The create form resource for this collection resource.
- **uri**=[/management/weblogic/{version}/edit](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/shutdownClasses](#) **rel**=self
This resource.

POST

Add a new [weblogic.management.configuration.ShutdownClassMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.ShutdownClassMBean](#) entity.

/management/weblogic/{version}/edit/shutdownClasses/{name}

This resource manages a [weblogic.management.configuration.ShutdownClassMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.ShutdownClassMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.ShutdownClassMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ShutdownClassMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/shutdownClasses/{name}](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/shutdownClasses](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/shutdownClasses/{name}](#) **rel**=self
This resource.

POST

Update this [weblogic.management.configuration.ShutdownClassMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.ShutdownClassMBean](#) entity.

/management/weblogic/{version}/edit/SingletonServiceCreateForm

This resource manages the create forms for the singletonServices collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.SingletonServiceMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the singletonServices collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SingletonServiceMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/SingletonServiceCreateForm](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/SingletonServices](#) **rel**=create
The collection resource for this create form resource.
- **uri**=[/management/weblogic/{version}/edit](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/SingletonServiceCreateForm](#) **rel**=self
This resource.

/management/weblogic/{version}/edit/SingletonServices

This resource manages a collection of [weblogic.management.configuration.SingletonServiceMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.SingletonServiceMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.SingletonServiceMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/SingletonServices](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/SingletonServiceCreateForm](#)
rel=create-form
The create form resource for this collection resource.
- **uri**=[/management/weblogic/{version}/edit](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/SingletonServices](#) **rel**=self
This resource.

POST

Add a new [weblogic.management.configuration.SingletonServiceMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.SingletonServiceMBean](#) entity.

/management/weblogic/{version}/edit/SingletonServices/{name}

This resource manages a [weblogic.management.configuration.SingletonServiceMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.SingletonServiceMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.SingletonServiceMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SingletonServiceMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/SingletonServices/{name}](#)
rel=canonical
This resource.
- **rel**=cluster
This resource's cluster reference to a [weblogic.management.configuration.ClusterMBean](#) resource.
- **rel**=hostingServer
This resource's hostingServer reference to a [weblogic.management.configuration.ServerMBean](#) resource.
- **uri**=[/management/weblogic/{version}/edit/SingletonServices](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/SingletonServices/{name}](#) **rel**=self
This resource.
- **rel**=userPreferredServer
This resource's userPreferredServer reference to a [weblogic.management.configuration.ServerMBean](#) resource.

POST

POST

Update this [weblogic.management.configuration.SingletonServiceMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.SingletonServiceMBean](#) entity.

/management/weblogic/{version}/edit/SNMPAgent

This resource manages a [weblogic.management.configuration.SNMPAgentMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.SNMPAgentMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SNMPAgentMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/SNMPAgent/SNMPAttributeChangeCreateForm](#) **rel**=SNMPAttributeChangeCreateForm
The create form resource for this resource's SNMPAttributeChanges collection resource.
- **uri**=[/management/weblogic/{version}/edit/SNMPAgent/SNMPAttributeChanges](#) **rel**=SNMPAttributeChanges
This resource's SNMPAttributeChanges collection resource.
- **uri**=[/management/weblogic/{version}/edit/SNMPAgent/SNMPCounterMonitorCreateForm](#) **rel**=SNMPCounterMonitorCreateForm
The create form resource for this resource's SNMPCounterMonitors collection resource.
- **uri**=[/management/weblogic/{version}/edit/SNMPAgent/SNMPCounterMonitors](#) **rel**=SNMPCounterMonitors
This resource's SNMPCounterMonitors collection resource.
- **uri**=[/management/weblogic/{version}/edit/SNMPAgent/SNMPGaugeMonitorCreateForm](#) **rel**=SNMPGaugeMonitorCreateForm
The create form resource for this resource's SNMPGaugeMonitors collection resource.
- **uri**=[/management/weblogic/{version}/edit/SNMPAgent/SNMPGaugeMonitors](#) **rel**=SNMPGaugeMonitors
This resource's SNMPGaugeMonitors collection resource.
- **uri**=[/management/weblogic/{version}/edit/SNMPAgent/SNMPLogFilterCreateForm](#) **rel**=SNMPLogFilterCreateForm
The create form resource for this resource's SNMPLogFilters collection resource.
- **uri**=[/management/weblogic/{version}/edit/SNMPAgent/SNMPLogFilters](#) **rel**=SNMPLogFilters
This resource's SNMPLogFilters collection resource.
- **uri**=[/management/weblogic/{version}/edit/SNMPAgent/SNMPProxies](#) **rel**=SNMPProxies
This resource's SNMPProxies collection resource.
- **uri**=[/management/weblogic/{version}/edit/SNMPAgent/SNMPProxyCreateForm](#) **rel**=SNMPProxyCreateForm

The create form resource for this resource's SNMPProxies collection resource.

- **uri**=/management/weblogic/{version}/edit/SNMPAgent/SNMPStringMonitorCreateForm **rel**=SNMPStringMonitorCreateForm

The create form resource for this resource's SNMPStringMonitors collection resource.

- **uri**=/management/weblogic/{version}/edit/SNMPAgent/SNMPStringMonitors **rel**=SNMPStringMonitors

This resource's SNMPStringMonitors collection resource.

- **uri**=/management/weblogic/{version}/edit/SNMPAgent/SNMPTrapDestinationCreateForm **rel**=SNMPTrapDestinationCreateForm

The create form resource for this resource's SNMPTrapDestinations collection resource.

- **uri**=/management/weblogic/{version}/edit/SNMPAgent/SNMPTrapDestinations **rel**=SNMPTrapDestinations

This resource's SNMPTrapDestinations collection resource.

- **uri**=/management/weblogic/{version}/edit/SNMPAgent **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/SNMPAgent **rel**=self

This resource.

POST

POST

Update this [weblogic.management.configuration.SNMPAgentMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.SNMPAgentMBean](#) entity.

/management/weblogic/{version}/edit/SNMPAgent/SNMPAttributeChangeCreateForm

This resource manages the create forms for the SNMPAttributeChanges collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.SNMPAttributeChangeMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the [SNMPAttributeChanges](#) collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SNMPAttributeChangeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/SNMPAgent/SNMPAttributeChangeCreateForm](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/SNMPAgent/SNMPAttributeChanges](#) **rel=create**
The collection resource for this create form resource.
- [uri=/management/weblogic/{version}/edit/SNMPAgent](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/SNMPAgent/SNMPAttributeChangeCreateForm](#) **rel=self**
This resource.

/management/weblogic/{version}/edit/SNMPAgent/SNMPAttributeChanges

This resource manages a collection of [weblogic.management.configuration.SNMPAttributeChangeMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.SNMPAttributeChangeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.SNMPAttributeChangeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/SNMPAgent/SNMPAttributeChanges](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/SNMPAgent/SNMPAttributeChangeCreateForm](#) **rel**=create-form
The create form resource for this collection resource.
- **uri**=[/management/weblogic/{version}/edit/SNMPAgent](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/SNMPAgent/SNMPAttributeChanges](#)
rel=self
This resource.

POST

Add a new [weblogic.management.configuration.SNMPAttributeChangeMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.SNMPAttributeChangeMBean](#) entity.

/management/weblogic/{version}/edit/SNMPAgent/SNMPAttributeChanges/{name}

This resource manages a [weblogic.management.configuration.SNMPAttributeChangeMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.SNMPAttributeChangeMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.SNMPAttributeChangeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SNMPAttributeChangeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/SNMPAgent/SNMPAttributeChanges/{name}](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/SNMPAgent/SNMPAttributeChanges](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/SNMPAgent/SNMPAttributeChanges/{name}](#) **rel**=self
This resource.

POST

Update this [weblogic.management.configuration.SNMPAttributeChangeMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.SNMPAttributeChangeMBean](#) entity.

/management/weblogic/{version}/edit/SNMPAgent/SNMPCounterMonitorCreateForm

This resource manages the create forms for the SNMPCounterMonitors collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.SNMPCounterMonitorMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the [SNMPCounterMonitors](#) collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SNMPCounterMonitorMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/SNMPAgent/SNMPCounterMonitorCreateForm](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/SNMPAgent/SNMPCounterMonitors](#) **rel=create**
The collection resource for this create form resource.
- [uri=/management/weblogic/{version}/edit/SNMPAgent](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/SNMPAgent/SNMPCounterMonitorCreateForm](#) **rel=self**
This resource.

/management/weblogic/{version}/edit/SNMPAgent/SNMPCounterMonitors

This resource manages a collection of [weblogic.management.configuration.SNMPCounterMonitorMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.SNMPCounterMonitorMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.SNMPCounterMonitorMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/SNMPAgent/SNMPCounterMonitors](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/SNMPAgent/SNMPCounterMonitorCreateForm](#) **rel**=create-form
The create form resource for this collection resource.
- **uri**=[/management/weblogic/{version}/edit/SNMPAgent](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/SNMPAgent/SNMPCounterMonitors](#)
rel=self
This resource.

POST

Add a new [weblogic.management.configuration.SNMPCounterMonitorMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.SNMPCounterMonitorMBean](#) entity.

/management/weblogic/{version}/edit/SNMPAgent/SNMPCounterMonitors/{name}

This resource manages a [weblogic.management.configuration.SNMPCounterMonitorMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.SNMPCounterMonitorMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.SNMPCounterMonitorMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SNMPCounterMonitorMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/SNMPAgent/SNMPCounterMonitors/{name}](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/SNMPAgent/SNMPCounterMonitors](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/SNMPAgent/SNMPCounterMonitors/{name}](#) **rel**=self
This resource.

POST

Update this [weblogic.management.configuration.SNMPCounterMonitorMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.SNMPCounterMonitorMBean](#) entity.

/management/weblogic/{version}/edit/SNMPAgent/SNMPGaugeMonitorCreateForm

This resource manages the create forms for the SNMPGaugeMonitors collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.SNMPGaugeMonitorMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the [SNMPGaugeMonitors](#) collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SNMPGaugeMonitorMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/SNMPAgent/SNMPGaugeMonitorCreateForm](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/SNMPAgent/SNMPGaugeMonitors](#) **rel**=create
The collection resource for this create form resource.
- **uri**=[/management/weblogic/{version}/edit/SNMPAgent](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/SNMPAgent/SNMPGaugeMonitorCreateForm](#) **rel**=self
This resource.

/management/weblogic/{version}/edit/SNMPAgent/SNMPGaugeMonitors

This resource manages a collection of [weblogic.management.configuration.SNMPGaugeMonitorMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.SNMPGaugeMonitorMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.SNMPGaugeMonitorMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/SNMPAgent/SNMPGaugeMonitors](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/SNMPAgent/SNMPGaugeMonitorCreateForm](#) **rel**=create-form
The create form resource for this collection resource.
- **uri**=[/management/weblogic/{version}/edit/SNMPAgent](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/SNMPAgent/SNMPGaugeMonitors](#)
rel=self
This resource.

POST

Add a new [weblogic.management.configuration.SNMPGaugeMonitorMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.SNMPGaugeMonitorMBean](#) entity.

/management/weblogic/{version}/edit/SNMPAgent/SNMPGaugeMonitors/{name}

This resource manages a [weblogic.management.configuration.SNMPGaugeMonitorMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.SNMPGaugeMonitorMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.SNMPGaugeMonitorMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SNMPGaugeMonitorMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/SNMPAgent/SNMPGaugeMonitors/{name}](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/SNMPAgent/SNMPGaugeMonitors](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/SNMPAgent/SNMPGaugeMonitors/{name}](#) **rel**=self
This resource.

POST

Update this [weblogic.management.configuration.SNMPGaugeMonitorMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.SNMPGaugeMonitorMBean](#) entity.

/management/weblogic/{version}/edit/SNMPAgent/SNMPLogFilterCreateForm

This resource manages the create forms for the SNMPLogFilters collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.SNMPLogFilterMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the SNMPLogFilters collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SNMPLogFilterMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/SNMPAgent/SNMPLogFilterCreateForm rel=canonical](#)
This resource.
- [uri=/management/weblogic/{version}/edit/SNMPAgent/SNMPLogFilters rel=create](#)
The collection resource for this create form resource.
- [uri=/management/weblogic/{version}/edit/SNMPAgent rel=parent](#)
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/SNMPAgent/SNMPLogFilterCreateForm rel=self](#)
This resource.

/management/weblogic/{version}/edit/SNMPAgent/SNMPLogFilters

This resource manages a collection of [weblogic.management.configuration.SNMPLogFilterMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.SNMPLogFilterMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.SNMPLogFilterMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/SNMPAgent/SNMPLogFilters](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/SNMPAgent/SNMPLogFilterCreateForm](#) **rel**=create-form
The create form resource for this collection resource.
- **uri**=[/management/weblogic/{version}/edit/SNMPAgent](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/SNMPAgent/SNMPLogFilters](#)
rel=self
This resource.

POST

Add a new [weblogic.management.configuration.SNMPLogFilterMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.SNMPLogFilterMBean](#) entity.

/management/weblogic/{version}/edit/SNMPAgent/SNMPLogFilters/{name}

This resource manages a [weblogic.management.configuration.SNMPLogFilterMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

DELETE

Delete this [weblogic.management.configuration.SNMPLogFilterMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.SNMPLogFilterMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SNMPLogFilterMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/SNMPAgent/SNMPLogFilters/{name}](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/SNMPAgent/SNMPLogFilters](#)
rel=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/SNMPAgent/SNMPLogFilters/{name}](#)
rel=self
This resource.

POST

Update this [weblogic.management.configuration.SNMPLogFilterMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.SNMPLogFilterMBean](#) entity.

/management/weblogic/{version}/edit/SNMPAgent/SNMPProxies

This resource manages a collection of [weblogic.management.configuration.SNMPProxyMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.SNMPProxyMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.SNMPProxyMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/SNMPAgent/SNMPProxies](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/SNMPAgent/SNMPProxyCreateForm](#)
rel=create-form
The create form resource for this collection resource.
- **uri**=[/management/weblogic/{version}/edit/SNMPAgent](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/SNMPAgent/SNMPProxies](#) **rel**=self
This resource.

POST

Add a new [weblogic.management.configuration.SNMPProxyMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.SNMPProxyMBean](#) entity.

/management/weblogic/{version}/edit/SNMPAgent/SNMPProxies/{name}

This resource manages a [weblogic.management.configuration.SNMPProxyMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.SNMPProxyMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.SNMPProxyMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SNMPProxyMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/SNMPAgent/SNMPProxies/{name}](#)
rel=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/SNMPAgent/SNMPProxies](#)
rel=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/SNMPAgent/SNMPProxies/{name}](#)
rel=self

This resource.

POST

Update this [weblogic.management.configuration.SNMPProxyMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.SNMPProxyMBean](#) entity.

/management/weblogic/{version}/edit/SNMPAgent/SNMPProxyCreateForm

This resource manages the create forms for the SNMPProxies collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.SNMPProxyMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the SNMPProxies collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SNMPProxyMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/SNMPAgent/SNMPProxyCreateForm](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/SNMPAgent/SNMPProxies](#)
rel=create
The collection resource for this create form resource.
- **uri**=[/management/weblogic/{version}/edit/SNMPAgent](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/SNMPAgent/SNMPProxyCreateForm](#)
rel=self
This resource.

/management/weblogic/{version}/edit/SNMPAgent/SNMPStringMonitorCreateForm

This resource manages the create forms for the SNMPStringMonitors collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.SNMPStringMonitorMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the [SNMPStringMonitors](#) collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SNMPStringMonitorMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/SNMPAgent/SNMPStringMonitorCreateForm](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/SNMPAgent/SNMPStringMonitors](#) **rel**=create
The collection resource for this create form resource.
- **uri**=[/management/weblogic/{version}/edit/SNMPAgent](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/SNMPAgent/SNMPStringMonitorCreateForm](#) **rel**=self
This resource.

/management/weblogic/{version}/edit/SNMPAgent/SNMPStringMonitors

This resource manages a collection of [weblogic.management.configuration.SNMPStringMonitorMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.SNMPStringMonitorMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.SNMPStringMonitorMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/SNMPAgent/SNMPStringMonitors](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/SNMPAgent/SNMPStringMonitorCreateForm](#) **rel**=create-form
The create form resource for this collection resource.
- **uri**=[/management/weblogic/{version}/edit/SNMPAgent](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/SNMPAgent/SNMPStringMonitors](#)
rel=self
This resource.

POST

Add a new [weblogic.management.configuration.SNMPStringMonitorMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.SNMPStringMonitorMBean](#) entity.

/management/weblogic/{version}/edit/SNMPAgent/SNMPStringMonitors/{name} **}**

This resource manages a [weblogic.management.configuration.SNMPStringMonitorMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

DELETE

Delete this [weblogic.management.configuration.SNMPStringMonitorMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.SNMPStringMonitorMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SNMPStringMonitorMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/SNMPAgent/SNMPStringMonitors/{name}](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/SNMPAgent/SNMPStringMonitors](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/SNMPAgent/SNMPStringMonitors/{name}](#) **rel**=self
This resource.

POST

Update this [weblogic.management.configuration.SNMPStringMonitorMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.SNMPStringMonitorMBean](#) entity.

/management/weblogic/{version}/edit/SNMPAgent/SNMPTrapDestinationCreateForm

This resource manages the create forms for the SNMPTrapDestinations collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.SNMPTrapDestinationMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the [SNMPTrapDestinations](#) collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SNMPTrapDestinationMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/SNMPAgent/SNMPTrapDestinationCreateForm](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/SNMPAgent/SNMPTrapDestinations](#) **rel=create**
The collection resource for this create form resource.
- [uri=/management/weblogic/{version}/edit/SNMPAgent](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/SNMPAgent/SNMPTrapDestinationCreateForm](#) **rel=self**
This resource.

/management/weblogic/{version}/edit/SNMPAgent/SNMPTrapDestinations

This resource manages a collection of [weblogic.management.configuration.SNMPTrapDestinationMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.SNMPTrapDestinationMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.SNMPTrapDestinationMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/SNMPAgent/SNMPTrapDestinations](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/SNMPAgent/SNMPTrapDestinationCreateForm](#) **rel**=create-form
The create form resource for this collection resource.
- **uri**=[/management/weblogic/{version}/edit/SNMPAgent](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/SNMPAgent/SNMPTrapDestinations](#)
rel=self
This resource.

POST

Add a new [weblogic.management.configuration.SNMPTrapDestinationMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.SNMPTrapDestinationMBean](#) entity.

/management/weblogic/{version}/edit/SNMPAgent/SNMPTrapDestinations/{name}

This resource manages a [weblogic.management.configuration.SNMPTrapDestinationMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.SNMPTrapDestinationMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.SNMPTrapDestinationMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SNMPTrapDestinationMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/SNMPAgent/SNMPTrapDestinations/{name}](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/SNMPAgent/SNMPTrapDestinations](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/SNMPAgent/SNMPTrapDestinations/{name}](#) **rel**=self
This resource.

POST

Update this [weblogic.management.configuration.SNMPTrapDestinationMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.SNMPTrapDestinationMBean](#) entity.

/management/weblogic/{version}/edit/SNMPAgentDeploymentCreateForm

This resource manages the create forms for the SNMPAgentDeployments collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.SNMPAgentDeploymentMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the [SNMPAgentDeployments](#) collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SNMPAgentDeploymentMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/SNMPAgentDeploymentCreateForm](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/SNMPAgentDeployments](#) **rel=create**
The collection resource for this create form resource.
- [uri=/management/weblogic/{version}/edit](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/SNMPAgentDeploymentCreateForm](#) **rel=self**
This resource.

/management/weblogic/{version}/edit/SNMPAgentDeployments

This resource manages a collection of [weblogic.management.configuration.SNMPAgentDeploymentMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.SNMPAgentDeploymentMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.SNMPAgentDeploymentMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/SNMPAgentDeployments](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/SNMPAgentDeploymentCreateForm](#)
rel=create-form
The create form resource for this collection resource.
- **uri**=[/management/weblogic/{version}/edit](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/SNMPAgentDeployments](#) **rel**=self
This resource.

POST

Add a new [weblogic.management.configuration.SNMPAgentDeploymentMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.SNMPAgentDeploymentMBean](#) entity.

/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}

This resource manages a [weblogic.management.configuration.SNMPAgentDeploymentMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.SNMPAgentDeploymentMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.SNMPAgentDeploymentMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SNMPAgentDeploymentMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPAttributeChangeCreateForm](#) **rel=SNMPAttributeChangeCreateForm**
The create form resource for this resource's SNMPAttributeChanges collection resource.
- [uri=/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPAttributeChanges](#) **rel=SNMPAttributeChanges**
This resource's SNMPAttributeChanges collection resource.
- [uri=/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPCounterMonitorCreateForm](#) **rel=SNMPCounterMonitorCreateForm**
The create form resource for this resource's SNMPCounterMonitors collection resource.
- [uri=/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPCounterMonitors](#) **rel=SNMPCounterMonitors**
This resource's SNMPCounterMonitors collection resource.
- [uri=/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPGaugeMonitorCreateForm](#) **rel=SNMPGaugeMonitorCreateForm**
The create form resource for this resource's SNMPGaugeMonitors collection resource.
- [uri=/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPGaugeMonitors](#) **rel=SNMPGaugeMonitors**
This resource's SNMPGaugeMonitors collection resource.
- [uri=/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPLogFilterCreateForm](#) **rel=SNMPLogFilterCreateForm**
The create form resource for this resource's SNMPLogFilters collection resource.
- [uri=/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPLogFilters](#) **rel=SNMPLogFilters**
This resource's SNMPLogFilters collection resource.
- [uri=/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPProxies](#) **rel=SNMPProxies**
This resource's SNMPProxies collection resource.

- **uri**=/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPProxyCreateForm **rel**=SNMPProxyCreateForm
The create form resource for this resource's SNMPProxies collection resource.
- **uri**=/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPStringMonitorCreateForm **rel**=SNMPStringMonitorCreateForm
The create form resource for this resource's SNMPStringMonitors collection resource.
- **uri**=/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPStringMonitors **rel**=SNMPStringMonitors
This resource's SNMPStringMonitors collection resource.
- **uri**=/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPTrapDestinationCreateForm **rel**=SNMPTrapDestinationCreateForm
The create form resource for this resource's SNMPTrapDestinations collection resource.
- **uri**=/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPTrapDestinations **rel**=SNMPTrapDestinations
This resource's SNMPTrapDestinations collection resource.
- **uri**=/management/weblogic/{version}/edit/SNMPAgentDeployments/{name} **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/edit/SNMPAgentDeployments **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/edit/SNMPAgentDeployments/{name} **rel**=self
This resource.

POST

Update this [weblogic.management.configuration.SNMPAgentDeploymentMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.SNMPAgentDeploymentMBean](#) entity.

/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPAttributeChangeCreateForm

This resource manages the create forms for the SNMPAttributeChanges collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.SNMPAttributeChangeMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the [SNMPAttributeChanges](#) collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SNMPAttributeChangeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPAttributeChangeCreateForm](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPAttributeChanges](#) **rel**=create

The collection resource for this create form resource.

- **uri**=[/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPAttributeChangeCreateForm](#) **rel**=self

This resource.

/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPAttributeChanges

This resource manages a collection of [weblogic.management.configuration.SNMPAttributeChangeMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.SNMPAttributeChangeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.SNMPAttributeChangeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPAttributeChanges](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPAttributeChangeCreateForm](#) **rel=create-form**
The create form resource for this collection resource.
- [uri=/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPAttributeChanges](#) **rel=self**
This resource.

POST

Add a new [weblogic.management.configuration.SNMPAttributeChangeMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.SNMPAttributeChangeMBean](#) entity.

/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPAttributeChanges/{name}

This resource manages a [weblogic.management.configuration.SNMPAttributeChangeMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.SNMPAttributeChangeMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.SNMPAttributeChangeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SNMPAttributeChangeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPAttributeChanges/{name}](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPAttributeChanges](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPAttributeChanges/{name}](#) **rel=self**

This resource.

POST

Update this [weblogic.management.configuration.SNMPAttributeChangeMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.SNMPAttributeChangeMBean](#) entity.

/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPCounterMonitorCreateForm

This resource manages the create forms for the SNMPCounterMonitors collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.SNMPCounterMonitorMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the [SNMPCounterMonitors](#) collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SNMPCounterMonitorMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPCounterMonitorCreateForm](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPCounterMonitors](#) **rel**=create

The collection resource for this create form resource.

- **uri**=[/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPCounterMonitorCreateForm](#) **rel**=self

This resource.

/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPCounterMonitors

This resource manages a collection of [weblogic.management.configuration.SNMPCounterMonitorMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.SNMPCounterMonitorMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.SNMPCounterMonitorMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPCounterMonitors](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPCounterMonitorCreateForm](#) **rel**=create-form
The create form resource for this collection resource.
- **uri**=[/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPCounterMonitors](#) **rel**=self
This resource.

POST

Add a new [weblogic.management.configuration.SNMPCounterMonitorMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.SNMPCounterMonitorMBean](#) entity.

/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPCounterMonitors/{name}

This resource manages a [weblogic.management.configuration.SNMPCounterMonitorMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.SNMPCounterMonitorMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.SNMPCounterMonitorMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SNMPCounterMonitorMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPCounterMonitors/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPCounterMonitors](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPCounterMonitors/{name}](#) **rel**=self

This resource.

POST

Update this [weblogic.management.configuration.SNMPCounterMonitorMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.SNMPCounterMonitorMBean](#) entity.

/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPGaugeMonitorCreateForm

This resource manages the create forms for the SNMPGaugeMonitors collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.SNMPGaugeMonitorMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the [SNMPGaugeMonitors](#) collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SNMPGaugeMonitorMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPGaugeMonitorCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPGaugeMonitors](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPGaugeMonitorCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPGaugeMonitors

This resource manages a collection of [weblogic.management.configuration.SNMPGaugeMonitorMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.SNMPGaugeMonitorMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.SNMPGaugeMonitorMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPGaugeMonitors](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPGaugeMonitorCreateForm](#) **rel=create-form**
The create form resource for this collection resource.
- [uri=/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPGaugeMonitors](#) **rel=self**
This resource.

POST

Add a new [weblogic.management.configuration.SNMPGaugeMonitorMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.SNMPGaugeMonitorMBean](#) entity.

/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPGaugeMonitors/{name}

This resource manages a [weblogic.management.configuration.SNMPGaugeMonitorMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

DELETE

Delete this [weblogic.management.configuration.SNMPGaugeMonitorMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.SNMPGaugeMonitorMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SNMPGaugeMonitorMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPGaugeMonitors/{name}](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPGaugeMonitors](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPGaugeMonitors/{name}](#) **rel**=self
This resource.

POST

Update this [weblogic.management.configuration.SNMPGaugeMonitorMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.SNMPGaugeMonitorMBean](#) entity.

/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPLogFilterCreateForm

This resource manages the create forms for the SNMPLogFilters collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.SNMPLogFilterMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the SNMPLogFilters collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SNMPLogFilterMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPLogFilterCreateForm](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPLogFilters](#) **rel**=create

The collection resource for this create form resource.

- **uri**=[/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPLogFilterCreateForm](#) **rel**=self

This resource.

/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPLogFilters

This resource manages a collection of [weblogic.management.configuration.SNMPLogFilterMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.SNMPLogFilterMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.SNMPLogFilterMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPLogFilters](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPLogFilterCreateForm](#) **rel**=create-form

The create form resource for this collection resource.

- **uri**=[/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPLogFilters](#) **rel**=self

This resource.

POST

Add a new [weblogic.management.configuration.SNMPLogFilterMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.SNMPLogFilterMBean](#) entity.

/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPLogFilters/{name}

This resource manages a [weblogic.management.configuration.SNMPLogFilterMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.SNMPLogFilterMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.SNMPLogFilterMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SNMPLogFilterMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPLogFilters/{name}](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPLogFilters](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPLogFilters/{name}](#) **rel**=self
This resource.

POST

Update this [weblogic.management.configuration.SNMPLogFilterMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.SNMPLogFilterMBean](#) entity.

/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPProxies

This resource manages a collection of [weblogic.management.configuration.SNMPProxyMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.SNMPProxyMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.SNMPProxyMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPProxies](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPProxyCreateForm](#) **rel=create-form**
The create form resource for this collection resource.
- [uri=/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPProxies](#) **rel=self**
This resource.

POST

Add a new [weblogic.management.configuration.SNMPProxyMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.SNMPProxyMBean](#) entity.

/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPProxies/{name}

This resource manages a [weblogic.management.configuration.SNMPProxyMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.SNMPProxyMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.SNMPProxyMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SNMPProxyMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPProxies/{name}](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPProxies](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPProxies/{name}](#) **rel**=self
This resource.

POST

Update this [weblogic.management.configuration.SNMPProxyMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.SNMPProxyMBean](#) entity.

/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPProxyCreateForm

This resource manages the create forms for the SNMPProxies collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.SNMPProxyMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the SNMPProxies collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SNMPProxyMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPProxyCreateForm](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPProxies](#) **rel**=create

The collection resource for this create form resource.

- **uri**=[/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPProxyCreateForm](#) **rel**=self

This resource.

/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPStringMonitorCreateForm

This resource manages the create forms for the SNMPStringMonitors collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.SNMPStringMonitorMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the [SNMPStringMonitors](#) collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SNMPStringMonitorMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPStringMonitorCreateForm](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPStringMonitors](#) **rel**=create
The collection resource for this create form resource.
- **uri**=[/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPStringMonitorCreateForm](#) **rel**=self
This resource.

/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPStringMonitors

This resource manages a collection of [weblogic.management.configuration.SNMPStringMonitorMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.SNMPStringMonitorMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.SNMPStringMonitorMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPStringMonitors](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPStringMonitorCreateForm](#) **rel**=create-form
The create form resource for this collection resource.
- **uri**=[/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPStringMonitors](#) **rel**=self
This resource.

POST

Add a new [weblogic.management.configuration.SNMPStringMonitorMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.SNMPStringMonitorMBean](#) entity.

/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPStringMonitors/{name}

This resource manages a [weblogic.management.configuration.SNMPStringMonitorMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.SNMPStringMonitorMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.SNMPStringMonitorMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SNMPStringMonitorMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPStringMonitors/{name}](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPStringMonitors](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPStringMonitors/{name}](#) **rel**=self
This resource.

POST

Update this [weblogic.management.configuration.SNMPStringMonitorMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.SNMPStringMonitorMBean](#) entity.

/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPTrapDestinationCreateForm

This resource manages the create forms for the SNMPTrapDestinations collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.SNMPTrapDestinationMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the SNMPTrapDestinations collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SNMPTrapDestinationMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPTrapDestinationCreateForm](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPTrapDestinations](#) **rel**=create
The collection resource for this create form resource.
- **uri**=[/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPTrapDestinationCreateForm](#) **rel**=self
This resource.

/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPTrapDestinations

This resource manages a collection of [weblogic.management.configuration.SNMPTrapDestinationMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.SNMPTrapDestinationMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.SNMPTrapDestinationMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPTrapDestinations](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPTrapDestinationCreateForm](#) **rel=create-form**
The create form resource for this collection resource.
- [uri=/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPTrapDestinations](#) **rel=self**
This resource.

POST

Add a new [weblogic.management.configuration.SNMPTrapDestinationMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.SNMPTrapDestinationMBean](#) entity.

/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPTrapDestinations/{name}

This resource manages a [weblogic.management.configuration.SNMPTrapDestinationMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.SNMPTrapDestinationMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.SNMPTrapDestinationMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SNMPTrapDestinationMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPTrapDestinations/{name}](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPTrapDestinations](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/SNMPAgentDeployments/{name}/SNMPTrapDestinations/{name}](#) **rel**=self
This resource.

POST

Update this [weblogic.management.configuration.SNMPTrapDestinationMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.SNMPTrapDestinationMBean](#) entity.

/management/weblogic/{version}/edit/startupClassCreateForm

This resource manages the create forms for the startupClasses collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.StartupClassMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the startupClasses collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.StartupClassMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/startupClassCreateForm](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/startupClasses](#) **rel**=create
The collection resource for this create form resource.
- **uri**=[/management/weblogic/{version}/edit](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/startupClassCreateForm](#) **rel**=self
This resource.

/management/weblogic/{version}/edit/startupClasses

This resource manages a collection of [weblogic.management.configuration.StartupClassMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.StartupClassMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.StartupClassMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/startupClasses](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/startupClassCreateForm](#)
rel=create-form
The create form resource for this collection resource.
- **uri**=[/management/weblogic/{version}/edit](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/startupClasses](#) **rel**=self
This resource.

POST

Add a new [weblogic.management.configuration.StartupClassMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.StartupClassMBean](#) entity.

/management/weblogic/{version}/edit/startupClasses/{name}

This resource manages a [weblogic.management.configuration.StartupClassMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.StartupClassMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.StartupClassMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.StartupClassMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/startupClasses/{name}](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/startupClasses](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/startupClasses/{name}](#) **rel**=self
This resource.

POST

Update this [weblogic.management.configuration.StartupClassMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.StartupClassMBean](#) entity.

/management/weblogic/{version}/edit/systemComponentConfigurationCreateForm

This resource manages the create forms for the systemComponentConfigurations collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.SystemComponentConfigurationMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the `systemComponentConfigurations` collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SystemComponentConfigurationMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/systemComponentConfigurationCreateForm](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/systemComponentConfigurations](#) **rel=create**
The collection resource for this create form resource.
- [uri=/management/weblogic/{version}/edit](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/systemComponentConfigurationCreateForm](#) **rel=self**
This resource.

/management/weblogic/{version}/edit/systemComponentConfigurations

This resource manages a collection of [weblogic.management.configuration.SystemComponentConfigurationMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.SystemComponentConfigurationMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.SystemComponentConfigurationMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/systemComponentConfigurations](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/systemComponentConfigurationCreateForm](#) **rel**=create-form
The create form resource for this collection resource.
- **uri**=[/management/weblogic/{version}/edit](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/systemComponentConfigurations](#)
rel=self
This resource.

POST

Add a new [weblogic.management.configuration.SystemComponentConfigurationMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.SystemComponentConfigurationMBean](#) entity.

/management/weblogic/{version}/edit/systemComponentConfigurations/{name}

This resource manages a [weblogic.management.configuration.SystemComponentConfigurationMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.SystemComponentConfigurationMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.SystemComponentConfigurationMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SystemComponentConfigurationMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/systemComponentConfigurations/{name}](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/systemComponentConfigurations](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/systemComponentConfigurations/{name}](#) **rel**=self
This resource.

POST

Update this [weblogic.management.configuration.SystemComponentConfigurationMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.SystemComponentConfigurationMBean](#) entity.

/management/weblogic/{version}/edit/systemComponentCreateForm

This resource manages the create forms for the systemComponents collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.SystemComponentMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the systemComponents collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SystemComponentMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/systemComponentCreateForm](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/systemComponents](#) **rel**=create
The collection resource for this create form resource.
- **uri**=[/management/weblogic/{version}/edit](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/systemComponentCreateForm](#)
rel=self
This resource.

/management/weblogic/{version}/edit/systemComponents

This resource manages a collection of [weblogic.management.configuration.SystemComponentMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.SystemComponentMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.SystemComponentMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/systemComponents](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/systemComponentCreateForm](#)
rel=create-form
The create form resource for this collection resource.
- **uri**=[/management/weblogic/{version}/edit](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/systemComponents](#) **rel**=self
This resource.

POST

Add a new [weblogic.management.configuration.SystemComponentMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.SystemComponentMBean](#) entity.

/management/weblogic/{version}/edit/systemComponents/{name}

This resource manages a [weblogic.management.configuration.SystemComponentMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.SystemComponentMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.SystemComponentMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SystemComponentMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/systemComponents/{name}](#)
rel=canonical
This resource.
- **rel**=machine
This resource's machine reference to a [weblogic.management.configuration.MachineMBean](#) resource.
- **uri**=[/management/weblogic/{version}/edit/systemComponents](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/systemComponents/{name}](#) **rel**=self
This resource.
- **uri**=[/management/weblogic/{version}/edit/systemComponents/{name}/systemComponentStart](#) **rel**=systemComponentStart
This resource's systemComponentStart singleton resource.

POST

Update this [weblogic.management.configuration.SystemComponentMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.SystemComponentMBean](#) entity.

/management/weblogic/{version}/edit/systemComponents/{name}/systemComponentStart

This resource manages a [weblogic.management.configuration.SystemComponentStartMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.SystemComponentStartMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SystemComponentStartMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/systemComponents/{name}/systemComponentStart](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/systemComponents/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/systemComponents/{name}/systemComponentStart](#) **rel**=self
This resource.

POST

Update this [weblogic.management.configuration.SystemComponentStartMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.SystemComponentStartMBean](#) entity.

/management/weblogic/{version}/edit/virtualHostCreateForm

This resource manages the create forms for the virtualHosts collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.VirtualHostMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the virtualHosts collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.VirtualHostMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/virtualHostCreateForm](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/virtualHosts](#) **rel**=create
The collection resource for this create form resource.
- **uri**=[/management/weblogic/{version}/edit](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/virtualHostCreateForm](#) **rel**=self
This resource.

/management/weblogic/{version}/edit/virtualHosts

This resource manages a collection of [weblogic.management.configuration.VirtualHostMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.VirtualHostMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.VirtualHostMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/virtualHosts](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/virtualHostCreateForm](#)
rel=create-form
The create form resource for this collection resource.
- **uri**=[/management/weblogic/{version}/edit](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/virtualHosts](#) **rel**=self
This resource.

POST

Add a new [weblogic.management.configuration.VirtualHostMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.VirtualHostMBean](#) entity.

/management/weblogic/{version}/edit/virtualHosts/{name}

This resource manages a [weblogic.management.configuration.VirtualHostMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.VirtualHostMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.VirtualHostMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.VirtualHostMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/virtualHosts/{name}](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/virtualHosts](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/virtualHosts/{name}](#) **rel**=self
This resource.
- **uri**=[/management/weblogic/{version}/edit/virtualHosts/{name}/webServerLog](#) **rel**=webServerLog
This resource's webServerLog singleton resource.

POST

Update this [weblogic.management.configuration.VirtualHostMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.VirtualHostMBean](#) entity.

/management/weblogic/{version}/edit/virtualHosts/{name}/webServerLog

This resource manages a [weblogic.management.configuration.WebServerLogMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.WebServerLogMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.WebServerLogMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/virtualHosts/{name}/webServerLog](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/virtualHosts/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/virtualHosts/{name}/webServerLog](#)
rel=self
This resource.

POST

POST

Update this [weblogic.management.configuration.WebServerLogMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.WebServerLogMBean](#) entity.

/management/weblogic/{version}/edit/virtualTargetCreateForm

This resource manages the create forms for the virtualTargets collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.VirtualTargetMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the virtualTargets collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.VirtualTargetMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/virtualTargetCreateForm](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/virtualTargets](#) **rel**=create
The collection resource for this create form resource.
- **uri**=[/management/weblogic/{version}/edit](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/virtualTargetCreateForm](#) **rel**=self
This resource.

/management/weblogic/{version}/edit/virtualTargets

This resource manages a collection of [weblogic.management.configuration.VirtualTargetMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.VirtualTargetMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.VirtualTargetMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/virtualTargets](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/virtualTargetCreateForm](#)
rel=create-form
The create form resource for this collection resource.
- **uri**=[/management/weblogic/{version}/edit](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/virtualTargets](#) **rel**=self
This resource.

POST

Add a new [weblogic.management.configuration.VirtualTargetMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.VirtualTargetMBean](#) entity.

/management/weblogic/{version}/edit/virtualTargets/{name}

This resource manages a [weblogic.management.configuration.VirtualTargetMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.VirtualTargetMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.VirtualTargetMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.VirtualTargetMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/virtualTargets/{name}](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/virtualTargets](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/virtualTargets/{name}](#) **rel**=self
This resource.
- **uri**=[/management/weblogic/{version}/edit/virtualTargets/{name}/webServer](#)
rel=webServer
This resource's webServer singleton resource.

POST

Update this [weblogic.management.configuration.VirtualTargetMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.VirtualTargetMBean](#) entity.

/management/weblogic/{version}/edit/virtualTargets/{name}/webServer

This resource manages a [weblogic.management.configuration.WebServerMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.WebServerMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.WebServerMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/virtualTargets/{name}/webServer](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/virtualTargets/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/virtualTargets/{name}/webServer](#)
rel=self
This resource.
- **uri**=[/management/weblogic/{version}/edit/virtualTargets/{name}/webServer/webServerLog](#) **rel**=webServerLog
This resource's webServerLog singleton resource.

POST

Update this [weblogic.management.configuration.WebServerMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.WebServerMBean](#) entity.

/management/weblogic/{version}/edit/virtualTargets/{name}/webServer/webServerLog

This resource manages a [weblogic.management.configuration.WebServerLogMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.WebServerLogMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.WebServerLogMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/virtualTargets/{name}/webServer/webServerLog](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/virtualTargets/{name}/webServer](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/virtualTargets/{name}/webServer/webServerLog](#) **rel**=self
This resource.

POST

Update this [weblogic.management.configuration.WebServerLogMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.WebServerLogMBean](#) entity.

/management/weblogic/{version}/edit/webAppContainer

This resource manages a [weblogic.management.configuration.WebAppContainerMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.WebAppContainerMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.WebAppContainerMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/webAppContainer](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/webAppContainer/gzipCompression](#)
rel=gzipCompression
This resource's gzipCompression singleton resource.
- **uri**=[/management/weblogic/{version}/edit](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/webAppContainer](#) **rel**=self
This resource.

POST

POST

Update this [weblogic.management.configuration.WebAppContainerMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.WebAppContainerMBean](#) entity.

/management/weblogic/{version}/edit/webAppContainer/gzipCompression

This resource manages a [weblogic.management.configuration.GzipCompressionMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.GzipCompressionMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.GzipCompressionMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/webAppContainer/gzipCompression](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/webAppContainer](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/webAppContainer/gzipCompression](#)
rel=self
This resource.

POST

Update this [weblogic.management.configuration.GzipCompressionMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.GzipCompressionMBean](#) entity.

/management/weblogic/{version}/edit/webserviceSecurities

This resource manages a collection of [weblogic.management.configuration.WebserviceSecurityMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.WebserviceSecurityMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.WebserviceSecurityMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/webserviceSecurities](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/webserviceSecurityCreateForm](#)
rel=create-form
The create form resource for this collection resource.
- **uri**=[/management/weblogic/{version}/edit](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/webserviceSecurities](#) **rel**=self
This resource.

POST

POST

Add a new [weblogic.management.configuration.WebserviceSecurityMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.WebserviceSecurityMBean](#) entity.

/management/weblogic/{version}/edit/webserviceSecurities/{name}

This resource manages a [weblogic.management.configuration.WebserviceSecurityMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

DELETE

Delete this [weblogic.management.configuration.WebserviceSecurityMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.WebserviceSecurityMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.WebserviceSecurityMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/webserviceSecurities/{name}](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/webserviceSecurities](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/webserviceSecurities/{name}](#)
rel=self
This resource.
- **uri**=[/management/weblogic/{version}/edit/webserviceSecurities/{name}/webserviceCredentialProviderCreateForm](#) **rel**=webserviceCredentialProviderCreateForm
The create form resource for this resource's webserviceCredentialProviders collection resource.
- **uri**=[/management/weblogic/{version}/edit/webserviceSecurities/{name}/webserviceCredentialProviders](#) **rel**=webserviceCredentialProviders
This resource's webserviceCredentialProviders collection resource.
- **uri**=[/management/weblogic/{version}/edit/webserviceSecurities/{name}/webserviceSecurityTokenCreateForm](#) **rel**=webserviceSecurityTokenCreateForm
The create form resource for this resource's webserviceSecurityTokens collection resource.
- **uri**=[/management/weblogic/{version}/edit/webserviceSecurities/{name}/webserviceSecurityTokens](#) **rel**=webserviceSecurityTokens
This resource's webserviceSecurityTokens collection resource.
- **uri**=[/management/weblogic/{version}/edit/webserviceSecurities/{name}/webserviceTimestamp](#) **rel**=webserviceTimestamp
This resource's webserviceTimestamp singleton resource.
- **uri**=[/management/weblogic/{version}/edit/webserviceSecurities/{name}/webserviceTokenHandlerCreateForm](#) **rel**=webserviceTokenHandlerCreateForm
The create form resource for this resource's webserviceTokenHandlers collection resource.
- **uri**=[/management/weblogic/{version}/edit/webserviceSecurities/{name}/webserviceTokenHandlers](#) **rel**=webserviceTokenHandlers
This resource's webserviceTokenHandlers collection resource.

POST

POST

Update this [weblogic.management.configuration.WebserviceSecurityMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.WebserviceSecurityMBean](#) entity.

/management/weblogic/{version}/edit/webserviceSecurities/{name}/webserviceCredentialProviderCreateForm

This resource manages the create forms for the webserviceCredentialProviders collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.WebserviceCredentialProviderMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the [webserviceCredentialProviders](#) collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.WebserviceCredentialProviderMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/webserviceSecurities/{name}/webserviceCredentialProviderCreateForm](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/webserviceSecurities/{name}/webserviceCredentialProviders](#) **rel**=create

The collection resource for this create form resource.

- **uri**=[/management/weblogic/{version}/edit/webserviceSecurities/{name}](#)
rel=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/webserviceSecurities/{name}/webserviceCredentialProviderCreateForm](#) **rel**=self

This resource.

/management/weblogic/{version}/edit/webserviceSecurities/{name}/webserviceCredentialProviders

This resource manages a collection of [weblogic.management.configuration.WebserviceCredentialProviderMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.WebserviceCredentialProviderMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.WebserviceCredentialProviderMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/webServiceSecurities/{name}/webserviceCredentialProviders](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/webServiceSecurities/{name}/webserviceCredentialProviderCreateForm](#) **rel**=create-form

The create form resource for this collection resource.

- **uri**=[/management/weblogic/{version}/edit/webServiceSecurities/{name}](#)
rel=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/webServiceSecurities/{name}/webserviceCredentialProviders](#) **rel**=self

This resource.

POST

Add a new [weblogic.management.configuration.WebserviceCredentialProviderMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.WebserviceCredentialProviderMBean](#) entity.

/management/weblogic/{version}/edit/webserviceSecurities/{name}/webserviceCredentialProviders/{name}

This resource manages a [weblogic.management.configuration.WebserviceCredentialProviderMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.WebserviceCredentialProviderMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.WebserviceCredentialProviderMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.WebserviceCredentialProviderMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/webServiceSecurities/{name}/webserviceCredentialProviders/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/webServiceSecurities/{name}/webserviceCredentialProviders/{name}/configurationProperties](#) **rel**=configurationProperties

This resource's configurationProperties collection resource.

- **uri**=[/management/weblogic/{version}/edit/webServiceSecurities/{name}/webserviceCredentialProviders/{name}/configurationPropertyCreateForm](#) **rel**=configurationPropertyCreateForm

The create form resource for this resource's configurationProperties collection resource.

- **uri**=[/management/weblogic/{version}/edit/webServiceSecurities/{name}/webserviceCredentialProviders](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/webServiceSecurities/{name}/webserviceCredentialProviders/{name}](#) **rel**=self

This resource.

POST

Update this [weblogic.management.configuration.WebserviceCredentialProviderMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.WebserviceCredentialProviderMBean](#) entity.

/management/weblogic/{version}/edit/webserviceSecurities/{name}/webserviceCredentialProviders/{name}/configurationProperties

This resource manages a collection of [weblogic.management.configuration.ConfigurationPropertyMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.ConfigurationPropertyMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.ConfigurationPropertyMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/webserviceSecurities/{name}/webserviceCredentialProviders/{name}/configurationProperties](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/webserviceSecurities/{name}/webserviceCredentialProviders/{name}/configurationPropertyCreateForm](#) **rel**=create-form
The create form resource for this collection resource.
- **uri**=[/management/weblogic/{version}/edit/webserviceSecurities/{name}/webserviceCredentialProviders/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/webserviceSecurities/{name}/webserviceCredentialProviders/{name}/configurationProperties](#) **rel**=self
This resource.

POST

Add a new [weblogic.management.configuration.ConfigurationPropertyMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.ConfigurationPropertyMBean](#) entity.

/management/weblogic/{version}/edit/webserviceSecurities/{name}/webserviceCredentialProviders/{name}/configurationProperties/{name}

This resource manages a [weblogic.management.configuration.ConfigurationPropertyMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.ConfigurationPropertyMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.ConfigurationPropertyMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ConfigurationPropertyMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/webserviceSecurities/{name}/webserviceCredentialProviders/{name}/configurationProperties/{name}](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/webserviceSecurities/{name}/webserviceCredentialProviders/{name}/configurationProperties](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/webserviceSecurities/{name}/webserviceCredentialProviders/{name}/configurationProperties/{name}](#) **rel=self**
This resource.

POST

Update this [weblogic.management.configuration.ConfigurationPropertyMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.ConfigurationPropertyMBean](#) entity.

/management/weblogic/{version}/edit/webserviceSecurities/{name}/webserviceCredentialProviders/{name}/configurationPropertyCreateForm

This resource manages the create forms for the configurationProperties collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.ConfigurationPropertyMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the configurationProperties collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ConfigurationPropertyMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/webserviceSecurities/{name}/webserviceCredentialProviders/{name}/configurationPropertyCreateForm **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/edit/webserviceSecurities/{name}/webserviceCredentialProviders/{name}/configurationProperties **rel**=create
The collection resource for this create form resource.
- **uri**=/management/weblogic/{version}/edit/webserviceSecurities/{name}/webserviceCredentialProviders/{name} **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/edit/webserviceSecurities/{name}/webserviceCredentialProviders/{name}/configurationPropertyCreateForm **rel**=self
This resource.

/management/weblogic/{version}/edit/webserviceSecurities/{name}/webserviceSecurityTokenCreateForm

This resource manages the create forms for the webserviceSecurityTokens collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.WebserviceSecurityTokenMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the [webserviceSecurityTokens](#) collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.WebserviceSecurityTokenMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/webserviceSecurities/{name}/webserviceSecurityTokenCreateForm](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/webserviceSecurities/{name}/webserviceSecurityTokens](#) **rel**=create
The collection resource for this create form resource.
- **uri**=[/management/weblogic/{version}/edit/webserviceSecurities/{name}](#)
rel=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/webserviceSecurities/{name}/webserviceSecurityTokenCreateForm](#) **rel**=self
This resource.

/management/weblogic/{version}/edit/webserviceSecurities/{name}/webserviceSecurityTokens

This resource manages a collection of [weblogic.management.configuration.WebserviceSecurityTokenMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.WebserviceSecurityTokenMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.WebserviceSecurityTokenMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/webserviceSecurities/{name}/webserviceSecurityTokens](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/webserviceSecurities/{name}/webserviceSecurityTokenCreateForm](#) **rel**=create-form
The create form resource for this collection resource.
- **uri**=[/management/weblogic/{version}/edit/webserviceSecurities/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/webserviceSecurities/{name}/webserviceSecurityTokens](#) **rel**=self
This resource.

POST

Add a new [weblogic.management.configuration.WebserviceSecurityTokenMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.WebserviceSecurityTokenMBean](#) entity.

/management/weblogic/{version}/edit/webserviceSecurities/{name}/webserviceSecurityTokens/{name}

This resource manages a [weblogic.management.configuration.WebserviceSecurityTokenMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.WebserviceSecurityTokenMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.WebserviceSecurityTokenMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.WebserviceSecurityTokenMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/webserviceSecurities/{name}/webserviceSecurityTokens/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/webserviceSecurities/{name}/webserviceSecurityTokens/{name}/configurationProperties](#) **rel**=configurationProperties

This resource's configurationProperties collection resource.

- **uri**=[/management/weblogic/{version}/edit/webserviceSecurities/{name}/webserviceSecurityTokens/{name}/configurationPropertyCreateForm](#)
rel=configurationPropertyCreateForm

The create form resource for this resource's configurationProperties collection resource.

- **uri**=[/management/weblogic/{version}/edit/webserviceSecurities/{name}/webserviceSecurityTokens](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/webserviceSecurities/{name}/webserviceSecurityTokens/{name}](#) **rel**=self

This resource.

POST

Update this [weblogic.management.configuration.WebserviceSecurityTokenMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.WebserviceSecurityTokenMBean](#) entity.

/management/weblogic/{version}/edit/webserviceSecurities/{name}/webserviceSecurityTokens/{name}/configurationProperties

This resource manages a collection of [weblogic.management.configuration.ConfigurationPropertyMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.ConfigurationPropertyMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.ConfigurationPropertyMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/webserviceSecurities/{name}/webserviceSecurityTokens/{name}/configurationProperties](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/webserviceSecurities/{name}/webserviceSecurityTokens/{name}/configurationPropertyCreateForm](#) **rel**=create-form

The create form resource for this collection resource.

- **uri**=[/management/weblogic/{version}/edit/webserviceSecurities/{name}/webserviceSecurityTokens/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/webserviceSecurities/{name}/webserviceSecurityTokens/{name}/configurationProperties](#) **rel**=self

This resource.

POST

Add a new [weblogic.management.configuration.ConfigurationPropertyMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.ConfigurationPropertyMBean](#) entity.

/management/weblogic/{version}/edit/webserviceSecurities/{name}/webserviceSecurityTokens/{name}/configurationProperties/{name}

This resource manages a [weblogic.management.configuration.ConfigurationPropertyMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.ConfigurationPropertyMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.ConfigurationPropertyMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ConfigurationPropertyMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/webserviceSecurities/{name}/webserviceSecurityTokens/{name}/configurationProperties/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/webserviceSecurities/{name}/webserviceSecurityTokens/{name}/configurationProperties **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/webserviceSecurities/{name}/webserviceSecurityTokens/{name}/configurationProperties/{name} **rel**=self

This resource.

POST

Update this [weblogic.management.configuration.ConfigurationPropertyMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.ConfigurationPropertyMBean](#) entity.

/management/weblogic/{version}/edit/webserviceSecurities/{name}/webserviceSecurityTokens/{name}/configurationPropertyCreateForm

This resource manages the create forms for the configurationProperties collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.ConfigurationPropertyMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the configurationProperties collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ConfigurationPropertyMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/webserviceSecurities/{name}/webserviceSecurityTokens/{name}/configurationPropertyCreateForm **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/webserviceSecurities/{name}/webserviceSecurityTokens/{name}/configurationProperties **rel**=create

The collection resource for this create form resource.

- **uri**=/management/weblogic/{version}/edit/webserviceSecurities/{name}/webserviceSecurityTokens/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/webserviceSecurities/{name}/webserviceSecurityTokens/{name}/configurationPropertyCreateForm **rel**=self

This resource.

/management/weblogic/{version}/edit/webserviceSecurities/{name}/webserviceTimestamp

This resource manages a [weblogic.management.configuration.WebserviceTimestampMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.WebserviceTimestampMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.WebserviceTimestampMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/webserviceSecurities/{name}/webserviceTimestamp](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/webserviceSecurities/{name}](#)
rel=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/webserviceSecurities/{name}/webserviceTimestamp](#) **rel**=self

This resource.

POST

Update this [weblogic.management.configuration.WebserviceTimestampMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.WebserviceTimestampMBean](#) entity.

/management/weblogic/{version}/edit/webserviceSecurities/{name}/webserviceTokenHandlerCreateForm

This resource manages the create forms for the webserviceTokenHandlers collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.WebserviceTokenHandlerMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the [webserviceTokenHandlers](#) collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.WebserviceTokenHandlerMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/webserviceSecurities/{name}/webserviceTokenHandlerCreateForm](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/webserviceSecurities/{name}/webserviceTokenHandlers](#) **rel=create**
The collection resource for this create form resource.
- [uri=/management/weblogic/{version}/edit/webserviceSecurities/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/webserviceSecurities/{name}/webserviceTokenHandlerCreateForm](#) **rel=self**
This resource.

/management/weblogic/{version}/edit/webserviceSecurities/{name}/webserviceTokenHandlers

This resource manages a collection of [weblogic.management.configuration.WebserviceTokenHandlerMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.WebserviceTokenHandlerMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.WebserviceTokenHandlerMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/webserviceSecurities/{name}/webserviceTokenHandlers](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/webserviceSecurities/{name}/webserviceTokenHandlerCreateForm](#) **rel**=create-form

The create form resource for this collection resource.

- **uri**=[/management/weblogic/{version}/edit/webserviceSecurities/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/webserviceSecurities/{name}/webserviceTokenHandlers](#) **rel**=self

This resource.

POST

Add a new [weblogic.management.configuration.WebserviceTokenHandlerMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.WebserviceTokenHandlerMBean](#) entity.

/management/weblogic/{version}/edit/webserviceSecurities/{name}/webserviceTokenHandlers/{name}

This resource manages a [weblogic.management.configuration.WebserviceTokenHandlerMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.WebserviceTokenHandlerMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.WebserviceTokenHandlerMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.WebserviceTokenHandlerMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/webserviceSecurities/{name}/webserviceTokenHandlers/{name}](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/webserviceSecurities/{name}/webserviceTokenHandlers/{name}/configurationProperties](#) **rel=configurationProperties**

This resource's configurationProperties collection resource.

- [uri=/management/weblogic/{version}/edit/webserviceSecurities/{name}/webserviceTokenHandlers/{name}/configurationPropertyCreateForm](#) **rel=configurationPropertyCreateForm**

The create form resource for this resource's configurationProperties collection resource.

- [uri=/management/weblogic/{version}/edit/webserviceSecurities/{name}/webserviceTokenHandlers](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/webserviceSecurities/{name}/webserviceTokenHandlers/{name}](#) **rel=self**

This resource.

POST

Update this [weblogic.management.configuration.WebserviceTokenHandlerMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.WebserviceTokenHandlerMBean](#) entity.

/management/weblogic/{version}/edit/webserviceSecurities/{name}/webserviceTokenHandlers/{name}/configurationProperties

This resource manages a collection of [weblogic.management.configuration.ConfigurationPropertyMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.ConfigurationPropertyMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.ConfigurationPropertyMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/webserviceSecurities/{name}/webserviceTokenHandlers/{name}/configurationProperties **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/webserviceSecurities/{name}/webserviceTokenHandlers/{name}/configurationPropertyCreateForm **rel**=create-form

The create form resource for this collection resource.

- **uri**=/management/weblogic/{version}/edit/webserviceSecurities/{name}/webserviceTokenHandlers/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/webserviceSecurities/{name}/webserviceTokenHandlers/{name}/configurationProperties **rel**=self

This resource.

POST

Add a new [weblogic.management.configuration.ConfigurationPropertyMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.ConfigurationPropertyMBean](#) entity.

/management/weblogic/{version}/edit/webserviceSecurities/{name}/webserviceTokenHandlers/{name}/configurationProperties/{name}

This resource manages a [weblogic.management.configuration.ConfigurationPropertyMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.ConfigurationPropertyMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.ConfigurationPropertyMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ConfigurationPropertyMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/webserviceSecurities/{name}/webserviceTokenHandlers/{name}/configurationProperties/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/webserviceSecurities/{name}/webserviceTokenHandlers/{name}/configurationProperties **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/webserviceSecurities/{name}/webserviceTokenHandlers/{name}/configurationProperties/{name} **rel**=self

This resource.

POST

Update this [weblogic.management.configuration.ConfigurationPropertyMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.ConfigurationPropertyMBean](#) entity.

/management/weblogic/{version}/edit/webserviceSecurities/{name}/webserviceTokenHandlers/{name}/configurationPropertyCreateForm

This resource manages the create forms for the configurationProperties collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.ConfigurationPropertyMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the configurationProperties collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.ConfigurationPropertyMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/webserviceSecurities/{name}/webserviceTokenHandlers/{name}/configurationPropertyCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/webserviceSecurities/{name}/webserviceTokenHandlers/{name}/configurationProperties](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/webserviceSecurities/{name}/webserviceTokenHandlers/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/webserviceSecurities/{name}/webserviceTokenHandlers/{name}/configurationPropertyCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/webserviceSecurityCreateForm

This resource manages the create forms for the webserviceSecurities collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.WebserviceSecurityMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the [webserviceSecurities](#) collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.WebserviceSecurityMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/webserviceSecurityCreateForm](#)
rel=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/webserviceSecurities](#) **rel**=create

The collection resource for this create form resource.

- **uri**=[/management/weblogic/{version}/edit](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/webserviceSecurityCreateForm](#)
rel=self

This resource.

/management/weblogic/{version}/edit/webserviceTestpage

This resource manages a [weblogic.management.configuration.WebserviceTestpageMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.WebserviceTestpageMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.WebserviceTestpageMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/webserviceTestpage](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/webserviceTestpage](#) **rel**=self
This resource.

POST

POST

Update this [weblogic.management.configuration.WebserviceTestpageMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.WebserviceTestpageMBean](#) entity.

/management/weblogic/{version}/edit/WLDFSystemResourceCreateForm

This resource manages the create forms for the WLDFSystemResources collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.WLDFSystemResourceMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the [WLDFSystemResources](#) collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.WLDFSystemResourceMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/WLDFSystemResourceCreateForm](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/WLDFSystemResources](#) **rel**=create
The collection resource for this create form resource.
- **uri**=[/management/weblogic/{version}/edit](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/WLDFSystemResourceCreateForm](#)
rel=self
This resource.

/management/weblogic/{version}/edit/WLDFSystemResources

This resource manages a collection of [weblogic.management.configuration.WLDFSystemResourceMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.WLDFSystemResourceMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.WLDFSystemResourceMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/WLDFSystemResources](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/WLDFSystemResourceCreateForm](#)
rel=create-form
The create form resource for this collection resource.
- **uri**=[/management/weblogic/{version}/edit](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/WLDFSystemResources](#) **rel**=self
This resource.

POST

Add a new [weblogic.management.configuration.WLDFSystemResourceMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.WLDFSystemResourceMBean](#) entity.

/management/weblogic/{version}/edit/WLDFSystemResources/{name}

This resource manages a [weblogic.management.configuration.WLDFSystemResourceMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.WLDFSystemResourceMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.WLDFSystemResourceMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.WLDFSystemResourceMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource](#) [rel=WLDFResource](#)
This resource's WLDFResource singleton resource.
- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}](#) [rel=canonical](#)
This resource.
- [uri=/management/weblogic/{version}/edit/WLDFSystemResources](#) [rel=parent](#)
The parent resource of this resource.
- [rel=resource](#)
This resource's resource reference to a [weblogic.descriptor.DescriptorBean](#) resource.
- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}](#) [rel=self](#)
This resource.
- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/subDeploymentCreateForm](#) [rel=subDeploymentCreateForm](#)
The create form resource for this resource's subDeployments collection resource.
- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/subDeployments](#) [rel=subDeployments](#)
This resource's subDeployments collection resource.

POST

Update this [weblogic.management.configuration.WLDFSystemResourceMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.WLDFSystemResourceMBean](#) entity.

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/subDeploymentCreateForm

This resource manages the create forms for the subDeployments collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.SubDeploymentMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the subDeployments collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/subDeploymentCreateForm rel=canonical](#)
This resource.
- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/subDeployments rel=create](#)
The collection resource for this create form resource.
- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name} rel=parent](#)
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/subDeploymentCreateForm rel=self](#)
This resource.

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/subDeployments

This resource manages a collection of [weblogic.management.configuration.SubDeploymentMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.SubDeploymentMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.SubDeploymentMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/subDeployments](#) [rel=canonical](#)
This resource.
- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/subDeploymentCreateForm](#) [rel=create-form](#)
The create form resource for this collection resource.
- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}](#) [rel=parent](#)
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/subDeployments](#) [rel=self](#)
This resource.

POST

Add a new [weblogic.management.configuration.SubDeploymentMBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/subDeployments/{name}

This resource manages a [weblogic.management.configuration.SubDeploymentMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

DELETE

Delete this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/subDeployments/{name} **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/subDeployments **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/subDeployments/{name} **rel**=self
This resource.
- **uri**=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/subDeployments/{name}/subDeployments **rel**=subDeployments
This resource's subDeployments collection resource.

POST

POST

Update this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/subDeployments/{name}/subDeployments

This resource manages a collection of [weblogic.management.configuration.SubDeploymentMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.configuration.SubDeploymentMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.SubDeploymentMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/subDeployments/{name}/subDeployments](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/subDeployments/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/subDeployments/{name}/subDeployments](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/subDeployments/{name}/subDeployments/{name}

This resource manages a [weblogic.management.configuration.SubDeploymentMBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/WLDFSystemResources/{name}/subDeployments/{name}/subDeployments/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/WLDFSystemResources/{name}/subDeployments/{name}/subDeployments](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/WLDFSystemResources/{name}/subDeployments/{name}/subDeployments/{name}](#) **rel**=self

This resource.

- **uri**=[/management/weblogic/{version}/edit/WLDFSystemResources/{name}/subDeployments/{name}/subDeployments/{name}/subDeployments](#)
rel=subDeployments

This resource's subDeployments collection resource.

POST

Update this [weblogic.management.configuration.SubDeploymentMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.SubDeploymentMBean](#) entity.

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource

This resource manages a [weblogic.diagnostics.descriptor.WLDFResourceBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.diagnostics.descriptor.WLDResourceBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDResourceBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDResource](#) [rel=canonical](#)
This resource.
- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDResource/harvester](#) [rel=harvester](#)
This resource's harvester singleton resource.
- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDResource/instrumentation](#) [rel=instrumentation](#)
This resource's instrumentation singleton resource.
- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}](#) [rel=parent](#)
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDResource](#) [rel=self](#)
This resource.
- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDResource/watchNotification](#) [rel=watchNotification](#)
This resource's watchNotification singleton resource.

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/harvester

This resource manages a [weblogic.diagnostics.descriptor.WLDFHarvesterBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.diagnostics.descriptor.WLDFHarvesterBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFHarvesterBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDResource/harvester](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDResource/harvester/harvestedTypeCreateForm](#) **rel=harvestedTypeCreateForm**
The create form resource for this resource's harvestedTypes collection resource.
- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDResource/harvester/harvestedTypes](#) **rel=harvestedTypes**
This resource's harvestedTypes collection resource.
- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDResource](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDResource/harvester](#) **rel=self**
This resource.

POST

Update this [weblogic.diagnostics.descriptor.WLDFHarvesterBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFHarvesterBean](#) entity.

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/harvester/harvestedTypeCreateForm

This resource manages the create forms for the harvestedTypes collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFHarvestedTypeBean](#) entity populated with default values that can be customized then posted (using the POST method) to the `harvestedTypes` collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFHarvestedTypeBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFFResource/harvester/harvestedTypeCreateForm rel=canonical](#)
This resource.
- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFFResource/harvester/harvestedTypes rel=create](#)
The collection resource for this create form resource.
- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFFResource/harvester rel=parent](#)
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFFResource/harvester/harvestedTypeCreateForm rel=self](#)
This resource.

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/harvester/harvestedTypes

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFHarvestedTypeBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFHarvestedTypeBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFHarvestedTypeBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFFResource/harvester/harvestedTypes](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFFResource/harvester/harvestedTypeCreateForm](#) **rel=create-form**

The create form resource for this collection resource.

- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFFResource/harvester](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFFResource/harvester/harvestedTypes](#) **rel=self**

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFHarvestedTypeBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFHarvestedTypeBean](#) entity.

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/harvester/harvestedTypes/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFHarvestedTypeBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFHarvestedTypeBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.diagnostics.descriptor.WLDFHarvestedTypeBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFHarvestedTypeBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFFResource/harvester/harvestedTypes/{name}](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFFResource/harvester/harvestedTypes](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFFResource/harvester/harvestedTypes/{name}](#) **rel=self**

This resource.

POST

Update this [weblogic.diagnostics.descriptor.WLDFHarvestedTypeBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFHarvestedTypeBean](#) entity.

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/instrumentation

This resource manages a [weblogic.diagnostics.descriptor.WLDFInstrumentationBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.diagnostics.descriptor.WLDFInstrumentationBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFInstrumentationBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFFResource/instrumentation/WLDFInstrumentationMonitorCreateForm](#)
[rel=WLDFInstrumentationMonitorCreateForm](#)

The create form resource for this resource's WLDFInstrumentationMonitors collection resource.

- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFFResource/instrumentation/WLDFInstrumentationMonitors](#)
[rel=WLDFInstrumentationMonitors](#)

This resource's WLDFInstrumentationMonitors collection resource.

- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFFResource/instrumentation](#) [rel=canonical](#)

This resource.

- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFFResource](#) [rel=parent](#)

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFFResource/instrumentation](#) [rel=self](#)

This resource.

POST

POST

Update this [weblogic.diagnostics.descriptor.WLDFInstrumentationBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFInstrumentationBean](#) entity.

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDResource/instrumentation/WLDFInstrumentationMonitorCreateForm

This resource manages the create forms for the WLDFInstrumentationMonitors collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFInstrumentationMonitorBean](#) entity populated with default values that can be customized then posted (using the POST method) to the [WLDFInstrumentationMonitors](#) collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFInstrumentationMonitorBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFFResource/instrumentation/WLDFInstrumentationMonitorCreateForm](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFFResource/instrumentation/WLDFInstrumentationMonitors](#) **rel**=create
The collection resource for this create form resource.
- **uri**=[/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFFResource/instrumentation](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFFResource/instrumentation/WLDFInstrumentationMonitorCreateForm](#) **rel**=self
This resource.

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/instrumentation/WLDFInstrumentationMonitors

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFInstrumentationMonitorBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFInstrumentationMonitorBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFInstrumentationMonitorBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFFResource/instrumentation/WLDFInstrumentationMonitors](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFFResource/instrumentation/WLDFInstrumentationMonitorCreateForm](#) **rel**=create-form

The create form resource for this collection resource.

- **uri**=[/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFFResource/instrumentation](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFFResource/instrumentation/WLDFInstrumentationMonitors](#) **rel**=self

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFInstrumentationMonitorBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFInstrumentationMonitorBean](#) entity.

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/instrumentation/WLDFInstrumentationMonitors/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFInstrumentationMonitorBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFInstrumentationMonitorBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.diagnostics.descriptor.WLDFInstrumentationMonitorBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFInstrumentationMonitorBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFFResource/instrumentation/WLDFInstrumentationMonitors/{name}](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFFResource/instrumentation/WLDFInstrumentationMonitors](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFFResource/instrumentation/WLDFInstrumentationMonitors/{name}](#) **rel**=self
This resource.

POST

Update this [weblogic.diagnostics.descriptor.WLDFInstrumentationMonitorBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFInstrumentationMonitorBean](#) entity.

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification

This resource manages a [weblogic.diagnostics.descriptor.WLDFWatchNotificationBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.diagnostics.descriptor.WLDFWatchNotificationBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFWatchNotificationBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMSNotificationCreateForm](#)
[rel=JMSNotificationCreateForm](#)
The create form resource for this resource's JMSNotifications collection resource.
- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMSNotifications](#) [rel=JMSNotifications](#)
This resource's JMSNotifications collection resource.
- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMXNotificationCreateForm](#)
[rel=JMXNotificationCreateForm](#)
The create form resource for this resource's JMXNotifications collection resource.
- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMXNotifications](#) [rel=JMXNotifications](#)
This resource's JMXNotifications collection resource.
- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/RESTNotificationCreateForm](#)
[rel=RESTNotificationCreateForm](#)
The create form resource for this resource's RESTNotifications collection resource.
- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/RESTNotifications](#) [rel=RESTNotifications](#)
This resource's RESTNotifications collection resource.
- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/SMTPNotificationCreateForm](#)
[rel=SMTPNotificationCreateForm](#)
The create form resource for this resource's SMTPNotifications collection resource.
- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/SMTPNotifications](#) [rel=SMTPNotifications](#)
This resource's SMTPNotifications collection resource.
- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/SNMPNotificationCreateForm](#)
[rel=SNMPNotificationCreateForm](#)
The create form resource for this resource's SNMPNotifications collection resource.

- **uri**=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDResource/watchNotification/SNMPNotifications **rel**=SNMPNotifications
This resource's SNMPNotifications collection resource.
- **uri**=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDResource/watchNotification/lookupActions **rel**=action **title**=lookupActions
This resource's lookupActions action resource.
- **uri**=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDResource/watchNotification/lookupNotification **rel**=action **title**=lookupNotification
This resource's lookupNotification action resource.
- **uri**=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDResource/watchNotification/actionCreateForm **rel**=actionCreateForm
The create form resource for this resource's actions collection resource.
- **uri**=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDResource/watchNotification/actions **rel**=actions
This resource's actions collection resource.
- **uri**=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDResource/watchNotification **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDResource/watchNotification/heapDumpActionCreateForm **rel**=heapDumpActionCreateForm
The create form resource for this resource's heapDumpActions collection resource.
- **uri**=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDResource/watchNotification/heapDumpActions **rel**=heapDumpActions
This resource's heapDumpActions collection resource.
- **uri**=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDResource/watchNotification/imageNotificationCreateForm **rel**=imageNotificationCreateForm
The create form resource for this resource's imageNotifications collection resource.
- **uri**=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDResource/watchNotification/imageNotifications **rel**=imageNotifications
This resource's imageNotifications collection resource.
- **uri**=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDResource/watchNotification/logActionCreateForm **rel**=logActionCreateForm
The create form resource for this resource's logActions collection resource.
- **uri**=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDResource/watchNotification/logActions **rel**=logActions
This resource's logActions collection resource.
- **uri**=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDResource **rel**=parent
The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLD
FResource/watchNotification/scaleDownActionCreateForm
rel=scaleDownActionCreateForm
The create form resource for this resource's scaleDownActions collection resource.
- **uri**=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLD
FResource/watchNotification/scaleDownActions **rel**=scaleDownActions
This resource's scaleDownActions collection resource.
- **uri**=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLD
FResource/watchNotification/scaleUpActionCreateForm
rel=scaleUpActionCreateForm
The create form resource for this resource's scaleUpActions collection resource.
- **uri**=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLD
FResource/watchNotification/scaleUpActions **rel**=scaleUpActions
This resource's scaleUpActions collection resource.
- **uri**=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLD
FResource/watchNotification/scriptActionCreateForm
rel=scriptActionCreateForm
The create form resource for this resource's scriptActions collection resource.
- **uri**=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLD
FResource/watchNotification/scriptActions **rel**=scriptActions
This resource's scriptActions collection resource.
- **uri**=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLD
FResource/watchNotification **rel**=self
This resource.
- **uri**=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLD
FResource/watchNotification/threadDumpActionCreateForm
rel=threadDumpActionCreateForm
The create form resource for this resource's threadDumpActions collection
resource.
- **uri**=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLD
FResource/watchNotification/threadDumpActions **rel**=threadDumpActions
This resource's threadDumpActions collection resource.
- **uri**=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLD
FResource/watchNotification/watcheCreateForm **rel**=watcheCreateForm
The create form resource for this resource's watches collection resource.
- **uri**=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLD
FResource/watchNotification/watches **rel**=watches
This resource's watches collection resource.

POST

POST

Update this [weblogic.diagnostics.descriptor.WLDFWatchNotificationBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFWatchNotificationBean](#) entity.

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDResource/watchNotification/actionCreateForm

This resource manages the create forms for the actions collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFActionBean](#) entity populated with default values that can be customized then posted (using the POST method) to the actions collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFActionBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFFResource/watchNotification/actionCreateForm](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFFResource/watchNotification/actions](#) **rel=create**
The collection resource for this create form resource.
- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFFResource/watchNotification](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFFResource/watchNotification/actionCreateForm](#) **rel=self**
This resource.

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFActionBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFActionBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFActionBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFFResource/watchNotification/actions](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFFResource/watchNotification/actionCreateForm](#) **rel=create-form**

The create form resource for this collection resource.

- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFFResource/watchNotification](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFFResource/watchNotification/actions](#) **rel=self**

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFActionBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFActionBean](#) entity.

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFActionBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFActionBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.diagnostics.descriptor.WLDFActionBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFActionBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFFResource/watchNotification/actions/{name}/arrayProperties](#)
rel=arrayProperties

This resource's arrayProperties collection resource.

- **uri**=[/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFFResource/watchNotification/actions/{name}/arrayPropertyCreateForm](#)
rel=arrayPropertyCreateForm

The create form resource for this resource's arrayProperties collection resource.

- **uri**=[/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFFResource/watchNotification/actions/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFFResource/watchNotification/actions/{name}/configurationProperties](#)
rel=configurationProperties

This resource's configurationProperties collection resource.

- **uri**=[/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFFResource/watchNotification/actions/{name}/encryptedProperties](#)
rel=encryptedProperties

This resource's encryptedProperties collection resource.

- **uri**=[/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFFResource/watchNotification/actions/{name}/encryptedPropertyCreateForm](#)
rel=encryptedPropertyCreateForm

The create form resource for this resource's encryptedProperties collection resource.

- **uri**=[/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFFResource/watchNotification/actions/{name}/mapProperties](#) **rel**=mapProperties

This resource's mapProperties collection resource.

- **uri**=[/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFFResource/watchNotification/actions/{name}/mapPropertyCreateForm](#)
rel=mapPropertyCreateForm

The create form resource for this resource's mapProperties collection resource.

- **uri**=[/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFFResource/watchNotification/actions](#) **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDResource/watchNotification/actions/{name}/properties **rel**=properties

This resource's properties collection resource.

- **uri**=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDResource/watchNotification/actions/{name}/propertyCreateForm **rel**=propertyCreateForm

The create form resource for this resource's properties collection resource.

- **uri**=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDResource/watchNotification/actions/{name} **rel**=self

This resource.

POST

Update this [weblogic.diagnostics.descriptor.WLDFActionBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFActionBean](#) entity.

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/arrayProperties

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFArrayPropertyBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFArrayPropertyBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFArrayPropertyBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/arrayProperties](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/arrayPropertyCreateForm](#) **rel=create-form**

The create form resource for this collection resource.

- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/arrayProperties](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/array-

POST

Add a new [weblogic.diagnostics.descriptor.WLDFArrayPropertyBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFArrayPropertyBean](#) entity.

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/arrayProperties/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFArrayPropertyBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFArrayPropertyBean](#) instance.

Roles

Admin

GET

Get this [weblogic.diagnostics.descriptor.WLDFArrayPropertyBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFArrayPropertyBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/arrayProperties/{name}](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/arrayProperties](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/arrayProperties/{name}](#) **rel**=self
This resource.

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/arrayP

POST

Update this [weblogic.diagnostics.descriptor.WLDFArrayPropertyBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFArrayPropertyBean](#) entity.

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/arrayPropertyCreateForm

This resource manages the create forms for the arrayProperties collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFArrayPropertyBean](#) entity populated with default values that can be customized then posted (using the POST method) to the arrayProperties collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFArrayPropertyBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/arrayPropertyCreateForm](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/arrayProperties](#) **rel=create**
The collection resource for this create form resource.
- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/arrayPropertyCreateForm](#) **rel=self**
This resource.

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/configurationProperties

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFConfigurationPropertyBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFConfigurationPropertyBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFConfigurationPropertyBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDResource/watchNotification/actions/{name}/configurationProperties](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDResource/watchNotification/actions/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDResource/watchNotification/actions/{name}/configurationProperties](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/configurationProperties/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFConfigurationPropertyBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.diagnostics.descriptor.WLDFConfigurationPropertyBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFConfigurationPropertyBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDResource/watchNotification/actions/{name}/configurationProperties/{name}
rel=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDResource/watchNotification/actions/{name}/configurationProperties
rel=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDResource/watchNotification/actions/{name}/configurationProperties/{name}
rel=self

This resource.

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/encryptedProperties

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/encryptedProperties](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/encryptedPropertyCreateForm](#) **rel=create-form**
The create form resource for this collection resource.
- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/encryptedProperties](#) **rel=self**
This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) entity.

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/encryptedProperties/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) instance.

Roles

Admin

GET

Get this [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/encryptedProperties/{name}
rel=canonical
This resource.
- **uri**=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/encryptedProperties **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/encryptedProperties/{name}
rel=self
This resource.

POST

POST

Update this [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) entity.

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/encryptedPropertyCreateForm

This resource manages the create forms for the encryptedProperties collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) entity populated with default values that can be customized then posted (using the POST method) to the encryptedProperties collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFFResource/watchNotification/actions/{name}/encryptedPropertyCreateForm
rel=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFFResource/watchNotification/actions/{name}/encryptedProperties **rel**=create

The collection resource for this create form resource.

- **uri**=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFFResource/watchNotification/actions/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFFResource/watchNotification/actions/{name}/encryptedPropertyCreateForm
rel=self

This resource.

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFConfigurationPropertiesBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFConfigurationPropertiesBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFConfigurationPropertiesBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFFResource/watchNotification/actions/{name}/mapProperties](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFFResource/watchNotification/actions/{name}/mapPropertyCreateForm](#) **rel=create-form**

The create form resource for this collection resource.

- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFFResource/watchNotification/actions/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFFResource/watchNotification/actions/{name}/mapProperties](#) **rel=self**

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFConfigurationPropertiesBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFConfigurationPropertiesBean](#) entity.

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFConfigurationPropertiesBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFConfigurationPropertiesBean](#) instance.

Roles

Admin

GET

Get this [weblogic.diagnostics.descriptor.WLDFConfigurationPropertiesBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFConfigurationPropertiesBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFFResource/watchNotification/actions/{name}/mapProperties/{name}](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFFResource/watchNotification/actions/{name}/mapProperties/{name}/configurationProperties](#) **rel**=configurationProperties
This resource's configurationProperties collection resource.
- **uri**=[/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFFResource/watchNotification/actions/{name}/mapProperties/{name}/encryptedProperties](#) **rel**=encryptedProperties
This resource's encryptedProperties collection resource.
- **uri**=[/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFFResource/watchNotification/actions/{name}/mapProperties/{name}/encryptedPropertyCreateForm](#) **rel**=encryptedPropertyCreateForm
The create form resource for this resource's encryptedProperties collection resource.
- **uri**=[/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFFResource/watchNotification/actions/{name}/mapProperties](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFFResource/watchNotification/actions/{name}/mapProperties/{name}/properties](#) **rel**=properties
This resource's properties collection resource.
- **uri**=[/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFFResource/watchNotification/actions/{name}/mapProperties/{name}/propertyCreateForm](#) **rel**=propertyCreateForm
The create form resource for this resource's properties collection resource.
- **uri**=[/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFFResource/watchNotification/actions/{name}/mapProperties/{name}](#) **rel**=self
This resource.

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/configurationProperties

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFConfigurationPropertyBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFConfigurationPropertyBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFConfigurationPropertyBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFFResource/watchNotification/actions/{name}/mapProperties/{name}/configurationProperties](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFFResource/watchNotification/actions/{name}/mapProperties/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFFResource/watchNotification/actions/{name}/mapProperties/{name}/configurationProperties](#) **rel**=self

This resource.

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/configurationProperties/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFConfigurationPropertyBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.diagnostics.descriptor.WLDFConfigurationPropertyBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFConfigurationPropertyBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFFResource/watchNotification/actions/{name}/mapProperties/{name}/configurationProperties/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFFResource/watchNotification/actions/{name}/mapProperties/{name}/configurationProperties](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFFResource/watchNotification/actions/{name}/mapProperties/{name}/configurationProperties/{name}](#) **rel**=self

This resource.

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/encryptedProperties

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFFResource/watchNotification/actions/{name}/mapProperties/{name}/encryptedProperties](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFFResource/watchNotification/actions/{name}/mapProperties/{name}/encryptedPropertyCreateForm](#) **rel**=create-form

The create form resource for this collection resource.

- **uri**=[/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFFResource/watchNotification/actions/{name}/mapProperties/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFFResource/watchNotification/actions/{name}/mapProperties/{name}/encryptedProperties](#) **rel**=self

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) entity.

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/encryptedProperties/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFFResource/watchNotification/actions/{name}/mapProperties/{name}/encryptedProperties/{name} rel=canonical](#)

This resource.

- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFFResource/watchNotification/actions/{name}/mapProperties/{name}/encryptedProperties rel=parent](#)

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFFResource/watchNotification/actions/{name}/mapProperties/{name}/encryptedProperties/{name} rel=self](#)

This resource.

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapPr

POST

Update this [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) entity.

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/encryptedPropertyCreateForm

This resource manages the create forms for the encryptedProperties collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) entity populated with default values that can be customized then posted (using the POST method) to the encryptedProperties collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDResource/watchNotification/actions/{name}/mapProperties/{name}/encryptedPropertyCreateForm **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDResource/watchNotification/actions/{name}/mapProperties/{name}/encryptedProperties **rel**=create

The collection resource for this create form resource.

- **uri**=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDResource/watchNotification/actions/{name}/mapProperties/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDResource/watchNotification/actions/{name}/mapProperties/{name}/encryptedPropertyCreateForm **rel**=self

This resource.

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/properties

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/properties
rel=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/propertyCreateForm
rel=create-form

The create form resource for this collection resource.

- **uri**=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}
rel=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/properties
rel=self

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) entity.

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/properties/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/properties/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/properties **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/properties/{name} **rel**=self

This resource.

POST

Update this [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) entity.

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/propertyCreateForm

This resource manages the create forms for the properties collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) entity populated with default values that can be customized then posted (using the POST method) to the properties collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/propertyCreateForm](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/properties](#) **rel**=create

The collection resource for this create form resource.

- **uri**=[/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapProperties/{name}/propertyCreateForm](#) **rel**=self

This resource.

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/mapPropertyCreateForm

This resource manages the create forms for the mapProperties collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFConfigurationPropertiesBean](#) entity populated with default values that can be customized then posted (using the POST method) to the `mapProperties` collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFConfigurationPropertiesBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFFResource/watchNotification/actions/{name}/mapPropertyCreateForm](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFFResource/watchNotification/actions/{name}/mapProperties](#) **rel**=create
The collection resource for this create form resource.
- **uri**=[/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFFResource/watchNotification/actions/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFFResource/watchNotification/actions/{name}/mapPropertyCreateForm](#) **rel**=self
This resource.

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/properties

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/properties](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/propertyCreateForm](#) **rel**=create-form

The create form resource for this collection resource.

- **uri**=[/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/properties](#) **rel**=self

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) entity.

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/properties/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFFPropertyBean](#) instance.

Roles

Admin

GET

Get this [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/properties/{name} rel=canonical](#)
This resource.
- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/properties rel=parent](#)
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/properties/{name} rel=self](#)
This resource.

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/prop-

POST

Update this [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFPropertyBean](#) entity.

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/actions/{name}/propertyCreateForm

This resource manages the create forms for the properties collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFFPropertyBean](#) entity populated with default values that can be customized then posted (using the POST method) to the properties collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFFPropertyBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFFResource/watchNotification/actions/{name}/propertycreateForm](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFFResource/watchNotification/actions/{name}/properties](#) **rel=create**
The collection resource for this create form resource.
- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFFResource/watchNotification/actions/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFFResource/watchNotification/actions/{name}/propertycreateForm](#) **rel=self**
This resource.

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/heapDumpActionCreateForm

This resource manages the create forms for the heapDumpActions collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFHeapDumpActionBean](#) entity populated with default values that can be customized then posted (using the POST method) to the heapDumpActions collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFHeapDumpActionBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFFResource/watchNotification/heapDumpActionCreateForm](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFFResource/watchNotification/heapDumpActions](#) **rel=create**
The collection resource for this create form resource.
- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFFResource/watchNotification](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFFResource/watchNotification/heapDumpActionCreateForm](#) **rel=self**
This resource.

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/heapDumpActions

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFHeapDumpActionBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFHeapDumpActionBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFHeapDumpActionBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/heapDumpActions](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/heapDumpActionCreateForm](#) **rel=create-form**
The create form resource for this collection resource.
- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/heapDumpActions](#) **rel=self**
This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFHeapDumpActionBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFHeapDumpActionBean](#) entity.

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/heapDumpActions/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFHeapDumpActionBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFHeapDumpActionBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.diagnostics.descriptor.WLDFHeapDumpActionBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFHeapDumpActionBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFFResource/watchNotification/heapDumpActions/{name}](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFFResource/watchNotification/heapDumpActions](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFFResource/watchNotification/heapDumpActions/{name}](#) **rel**=self
This resource.

POST

Update this [weblogic.diagnostics.descriptor.WLDFHeapDumpActionBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFHeapDumpActionBean](#) entity.

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/imageNotificationCreateForm

This resource manages the create forms for the imageNotifications collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFImageNotificationBean](#) entity populated with default values that can be customized then posted (using the POST method) to the `imageNotifications` collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFImageNotificationBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFFResource/watchNotification/imageNotificationCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFFResource/watchNotification/imageNotifications](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFFResource/watchNotification](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFFResource/watchNotification/imageNotificationCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/imageNotifications

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFImageNotificationBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFImageNotificationBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFImageNotificationBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFFResource/watchNotification/imageNotifications](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFFResource/watchNotification/imageNotificationCreateForm](#) **rel=create-form**

The create form resource for this collection resource.

- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFFResource/watchNotification](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFFResource/watchNotification/imageNotifications](#) **rel=self**

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFImageNotificationBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFImageNotificationBean](#) entity.

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/imageNotifications/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFImageNotificationBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFImageNotificationBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.diagnostics.descriptor.WLDFImageNotificationBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFImageNotificationBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFFResource/watchNotification/imageNotifications/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFFResource/watchNotification/imageNotifications](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFFResource/watchNotification/imageNotifications/{name}](#) **rel**=self

This resource.

POST

Update this [weblogic.diagnostics.descriptor.WLDFImageNotificationBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFImageNotificationBean](#) entity.

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMSNotificationCreateForm

This resource manages the create forms for the JMSNotifications collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFJMSNotificationBean](#) entity populated with default values that can be customized then posted (using the POST method) to the JMSNotifications collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFJMSNotificationBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDResource/watchNotification/JMSNotificationCreateForm rel=canonical](#)
This resource.
- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDResource/watchNotification/JMSNotifications rel=create](#)
The collection resource for this create form resource.
- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDResource/watchNotification rel=parent](#)
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDResource/watchNotification/JMSNotificationCreateForm rel=self](#)
This resource.

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMSNotifications

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFJMSNotificationBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFJMSNotificationBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFJMSNotificationBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDResource/watchNotification/JMSNotifications](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDResource/watchNotification/JMSNotificationCreateForm](#) **rel=create-form**

The create form resource for this collection resource.

- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDResource/watchNotification](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDResource/watchNotification/JMSNotifications](#) **rel=self**

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFJMSNotificationBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFJMSNotificationBean](#) entity.

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMSNotifications/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFJMSNotificationBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFJMSNotificationBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.diagnostics.descriptor.WLDFJMSNotificationBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFJMSNotificationBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMSNotifications/{name} **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMSNotifications **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMSNotifications/{name} **rel**=self
This resource.

POST

Update this [weblogic.diagnostics.descriptor.WLDFJMSNotificationBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFJMSNotificationBean](#) entity.

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMXNotificationCreateForm

This resource manages the create forms for the JMXNotifications collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFJMXNotificationBean](#) entity populated with default values that can be customized then posted (using the POST method) to the JMXNotifications collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFJMXNotificationBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMXNotificationCreateForm rel=canonical](#)
This resource.
- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMXNotifications rel=create](#)
The collection resource for this create form resource.
- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification rel=parent](#)
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMXNotificationCreateForm rel=self](#)
This resource.

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMXNotifications

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFJMXNotificationBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFJMXNotificationBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFJMXNotificationBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMXNotifications](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMXNotificationCreateForm](#) **rel=create-form**

The create form resource for this collection resource.

- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMXNotifications](#) **rel=self**

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFJMXNotificationBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFJMXNotificationBean](#) entity.

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/JMXNotifications/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFJMXNotificationBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFJMXNotificationBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.diagnostics.descriptor.WLDFJMXNotificationBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFJMXNotificationBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFFResource/watchNotification/JMXNotifications/{name}](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFFResource/watchNotification/JMXNotifications](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFFResource/watchNotification/JMXNotifications/{name}](#) **rel**=self
This resource.

POST

Update this [weblogic.diagnostics.descriptor.WLDFJMXNotificationBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFJMXNotificationBean](#) entity.

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/logActionCreateForm

This resource manages the create forms for the logActions collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFLogActionBean](#) entity populated with default values that can be customized then posted (using the POST method) to the logActions collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFLogActionBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/logActionCreateForm rel=canonical](#)
This resource.
- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/logActions rel=create](#)
The collection resource for this create form resource.
- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification rel=parent](#)
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/logActionCreateForm rel=self](#)
This resource.

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/logActions

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFLogActionBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDLogActionBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDLogActionBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDResource/watchNotification/logActions](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDResource/watchNotification/logActionCreateForm](#) **rel=create-form**

The create form resource for this collection resource.

- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDResource/watchNotification](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDResource/watchNotification/logActions](#) **rel=self**

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFLogActionBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFLogActionBean](#) entity.

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/logActions/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFLogActionBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFLogActionBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.diagnostics.descriptor.WLDLogActionBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDLogActionBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDResource/watchNotification/logActions/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDResource/watchNotification/logActions **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDResource/watchNotification/logActions/{name} **rel**=self

This resource.

POST

Update this [weblogic.diagnostics.descriptor.WLDFLogActionBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFLogActionBean](#) entity.

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/lookupActions

The resource supports the following methods:

- [POST](#)

POST

Roles

Admin, Deployer

Request Body

Must contain a JSON object with the following fields:

typeName

typeName

Type: string

Response Body

Contains a JSON object with a array of
weblogic.diagnostics.descriptor.WLDFActionBean references return field.

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/lookupNotification

The resource supports the following methods:

- [POST](#)

POST

Looks up an action with the given name.

Roles

Admin, Deployer

Request Body

Must contain a JSON object with the following fields:

name

name

Type: string

Response Body

Contains a JSON object with a `weblogic.diagnostics.descriptor.WLDFNotificationBean` reference return field.

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDResource/watchNotification/RESTNotificationCreateForm

This resource manages the create forms for the RESTNotifications collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFRESTNotificationBean](#) entity populated with default values that can be customized then posted (using the POST method) to the RESTNotifications collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFRESTNotificationBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/RESTNotificationCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/RESTNotifications](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/RESTNotificationCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDResource/watchNotification/RESTNotifications

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFRESTNotificationBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFRESTNotificationBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFRESTNotificationBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/RESTNotifications](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/RESTNotificationCreateForm](#) **rel=create-form**

The create form resource for this collection resource.

- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/RESTNotifications](#) **rel=self**

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFRESTNotificationBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFRESTNotificationBean](#) entity.

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDResource/watchNotification/RESTNotifications/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFRESTNotificationBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFRESTNotificationBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.diagnostics.descriptor.WLDFRESTNotificationBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFRESTNotificationBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDResource/watchNotification/RESTNotifications/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDResource/watchNotification/RESTNotifications](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDResource/watchNotification/RESTNotifications/{name}](#) **rel**=self

This resource.

POST

Update this [weblogic.diagnostics.descriptor.WLDFRESTNotificationBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFRESTNotificationBean](#) entity.

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleDownActionCreateForm

This resource manages the create forms for the scaleDownActions collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFScaleDownActionBean](#) entity populated with default values that can be customized then posted (using the POST method) to the scaleDownActions collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFScaleDownActionBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleDownActionCreateForm](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleDownActions](#) **rel=create**
The collection resource for this create form resource.
- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleDownActionCreateForm](#) **rel=self**
This resource.

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleDownActions

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFScaleDownActionBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFScaleDownActionBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFScaleDownActionBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDResource/watchNotification/scaleDownActions](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDResource/watchNotification/scaleDownActionCreateForm](#) **rel=create-form**
The create form resource for this collection resource.
- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDResource/watchNotification](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDResource/watchNotification/scaleDownActions](#) **rel=self**
This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFScaleDownActionBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFScaleDownActionBean](#) entity.

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleDownActions/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFScaleDownActionBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFScaleDownActionBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.diagnostics.descriptor.WLDFScaleDownActionBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFScaleDownActionBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleDownActions/{name} **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleDownActions **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleDownActions/{name} **rel**=self
This resource.

POST

Update this [weblogic.diagnostics.descriptor.WLDFScaleDownActionBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFScaleDownActionBean](#) entity.

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleUpActionCreateForm

This resource manages the create forms for the scaleUpActions collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFScaleUpActionBean](#) entity populated with default values that can be customized then posted (using the POST method) to the `scaleUpActions` collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFScaleUpActionBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleUpActionCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleUpActions](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleUpActionCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleUpActions

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFScaleUpActionBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFScaleUpActionBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFScaleUpActionBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleUpActions](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleUpActionCreateForm](#) **rel=create-form**

The create form resource for this collection resource.

- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleUpActions](#) **rel=self**

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFScaleUpActionBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFScaleUpActionBean](#) entity.

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/scaleUpActions/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFScaleUpActionBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFScaleUpActionBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.diagnostics.descriptor.WLDFScaleUpActionBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFScaleUpActionBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFFResource/watchNotification/scaleUpActions/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFFResource/watchNotification/scaleUpActions](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFFResource/watchNotification/scaleUpActions/{name}](#) **rel**=self

This resource.

POST

Update this [weblogic.diagnostics.descriptor.WLDFScaleUpActionBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFScaleUpActionBean](#) entity.

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/scriptActionCreateForm

This resource manages the create forms for the scriptActions collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFScriptActionBean](#) entity populated with default values that can be customized then posted (using the POST method) to the scriptActions collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFScriptActionBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/scriptActionCreateForm](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/scriptActions](#) **rel=create**
The collection resource for this create form resource.
- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/scriptActionCreateForm](#) **rel=self**
This resource.

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/scriptActions

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFScriptActionBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFScriptActionBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFScriptActionBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFFResource/watchNotification/scriptActions rel=canonical](#)
This resource.
- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFFResource/watchNotification/scriptActionCreateForm rel=create-form](#)
The create form resource for this collection resource.
- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFFResource/watchNotification rel=parent](#)
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFFResource/watchNotification/scriptActions rel=self](#)
This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFScriptActionBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFScriptActionBean](#) entity.

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/scriptActions/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFScriptActionBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFScriptActionBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.diagnostics.descriptor.WLDFScriptActionBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFScriptActionBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDResource/watchNotification/scriptActions/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDResource/watchNotification/scriptActions](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDResource/watchNotification/scriptActions/{name}](#) **rel**=self

This resource.

POST

Update this [weblogic.diagnostics.descriptor.WLDFScriptActionBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFScriptActionBean](#) entity.

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/SMTPNotificationCreateForm

This resource manages the create forms for the SMTPNotifications collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFSMTPNotificationBean](#) entity populated with default values that can be customized then posted (using the POST method) to the SMTPNotifications collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFSMTPNotificationBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/SMTPNotificationCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/SMTPNotifications](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/SMTPNotificationCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/SMTPNotifications

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFSMTPNotificationBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFSMTPNotificationBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFSMTPNotificationBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/SMTPNotifications](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/SMTPNotificationCreateForm](#) **rel=create-form**

The create form resource for this collection resource.

- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/SMTPNotifications](#) **rel=self**

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFSMTPNotificationBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFSMTPNotificationBean](#) entity.

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/SMTPNotifications/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFSMTPNotificationBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFSMTPNotificationBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.diagnostics.descriptor.WLDFSMTPNotificationBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFSMTPNotificationBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDResource/watchNotification/SMTPNotifications/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDResource/watchNotification/SMTPNotifications](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDResource/watchNotification/SMTPNotifications/{name}](#) **rel**=self

This resource.

POST

Update this [weblogic.diagnostics.descriptor.WLDFSMTPNotificationBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFSMTPNotificationBean](#) entity.

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/SNMPNotificationCreateForm

This resource manages the create forms for the SNMPNotifications collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFSNMPNotificationBean](#) entity populated with default values that can be customized then posted (using the POST method) to the SNMPNotifications collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFSNMPNotificationBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDResource/watchNotification/SNMPNotificationCreateForm](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDResource/watchNotification/SNMPNotifications](#) **rel=create**
The collection resource for this create form resource.
- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDResource/watchNotification](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDResource/watchNotification/SNMPNotificationCreateForm](#) **rel=self**
This resource.

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/SNMPNotifications

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFSNMPNotificationBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFSNMPNotificationBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFSNMPNotificationBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDResource/watchNotification/SNMPNotifications](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDResource/watchNotification/SNMPNotificationCreateForm](#) **rel=create-form**
The create form resource for this collection resource.
- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDResource/watchNotification](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDResource/watchNotification/SNMPNotifications](#) **rel=self**
This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFSNMPNotificationBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFSNMPNotificationBean](#) entity.

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/SNMPNotifications/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFSNMPNotificationBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFSNMPNotificationBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.diagnostics.descriptor.WLDFSNMPNotificationBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFSNMPNotificationBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDResource/watchNotification/SNMPNotifications/{name} **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDResource/watchNotification/SNMPNotifications **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDResource/watchNotification/SNMPNotifications/{name} **rel**=self
This resource.

POST

POST

Update this [weblogic.diagnostics.descriptor.WLDFSNMPNotificationBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFSNMPNotificationBean](#) entity.

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/threadDumpActionCreateForm

This resource manages the create forms for the threadDumpActions collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFThreadDumpActionBean](#) entity populated with default values that can be customized then posted (using the POST method) to the `threadDumpActions` collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFThreadDumpActionBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFFResource/watchNotification/threadDumpActionCreateForm](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFFResource/watchNotification/threadDumpActions](#) **rel=create**

The collection resource for this create form resource.

- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFFResource/watchNotification](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFFResource/watchNotification/threadDumpActionCreateForm](#) **rel=self**

This resource.

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDResource/watchNotification/threadDumpActions

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFThreadDumpActionBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFThreadDumpActionBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFThreadDumpActionBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/threadDumpActions](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/threadDumpActionCreateForm](#) **rel=create-form**

The create form resource for this collection resource.

- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/threadDumpActions](#) **rel=self**

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFThreadDumpActionBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFThreadDumpActionBean](#) entity.

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/threadDumpActions/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFThreadDumpActionBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFThreadDumpActionBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.diagnostics.descriptor.WLDFThreadDumpActionBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFThreadDumpActionBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDResource/watchNotification/threadDumpActions/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDResource/watchNotification/threadDumpActions](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDResource/watchNotification/threadDumpActions/{name}](#) **rel**=self

This resource.

POST

Update this [weblogic.diagnostics.descriptor.WLDFThreadDumpActionBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFThreadDumpActionBean](#) entity.

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/watchCreateForm

This resource manages the create forms for the watches collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.diagnostics.descriptor.WLDFWatchBean](#) entity populated with default values that can be customized then posted (using the POST method) to the watches collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFWatchBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/watchCreateForm rel=canonical](#)
This resource.
- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/watches rel=create](#)
The collection resource for this create form resource.
- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification rel=parent](#)
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/watchCreateForm rel=self](#)
This resource.

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/watches

This resource manages a collection of [weblogic.diagnostics.descriptor.WLDFWatchBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.diagnostics.descriptor.WLDFWatchBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.descriptor.WLDFWatchBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/watches](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/watchCreateForm](#) **rel=create-form**

The create form resource for this collection resource.

- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/watches](#) **rel=self**

This resource.

POST

Add a new [weblogic.diagnostics.descriptor.WLDFWatchBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFWatchBean](#) entity.

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/watches/{name}

This resource manages a [weblogic.diagnostics.descriptor.WLDFWatchBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.diagnostics.descriptor.WLDFWatchBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.diagnostics.descriptor.WLDFWatchBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFWatchBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/watches/{name}](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/watches](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/watches/{name}/schedule](#) **rel=schedule**

This resource's schedule singleton resource.

- [uri=/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/watches/{name}](#) **rel=self**

This resource.

POST

Update this [weblogic.diagnostics.descriptor.WLDFWatchBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFWatchBean](#) entity.

/management/weblogic/{version}/edit/WLDFSystemResources/{name}/WLDFResource/watchNotification/watches/{name}/schedule

This resource manages a [weblogic.diagnostics.descriptor.WLDFScheduleBean](#) instance.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this [weblogic.diagnostics.descriptor.WLDFScheduleBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.descriptor.WLDFScheduleBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/WLDFSSystemResources/{name}/WLDResource/watchNotification/watches/{name}/schedule](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/WLDFSSystemResources/{name}/WLDResource/watchNotification/watches/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/WLDFSSystemResources/{name}/WLDResource/watchNotification/watches/{name}/schedule](#) **rel**=self
This resource.

POST

Update this [weblogic.diagnostics.descriptor.WLDFScheduleBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.diagnostics.descriptor.WLDFScheduleBean](#) entity.

/management/weblogic/{version}/edit/WSReliableDeliveryPolicies

This resource manages a collection of [weblogic.management.configuration.WSReliableDeliveryPolicyMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.WSReliableDeliveryPolicyMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.WSReliableDeliveryPolicyMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/WSReliableDeliveryPolicies](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/WSReliableDeliveryPolicyCreateForm](#)
rel=create-form
The create form resource for this collection resource.
- **uri**=[/management/weblogic/{version}/edit](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/WSReliableDeliveryPolicies](#) **rel**=self
This resource.

POST

Add a new [weblogic.management.configuration.WSReliableDeliveryPolicyMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.WSReliableDeliveryPolicyMBean](#) entity.

/management/weblogic/{version}/edit/WSReliableDeliveryPolicies/{name}

This resource manages a [weblogic.management.configuration.WSReliableDeliveryPolicyMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.WSReliableDeliveryPolicyMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.WSReliableDeliveryPolicyMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.WSReliableDeliveryPolicyMBean](#) entity.

This method can return the following links:

- **rel=JMSServer**
This resource's JMSServer reference to a [weblogic.management.configuration.JMSServerMBean](#) resource.
- **uri=/management/weblogic/{version}/edit/WSReliableDeliveryPolicies/{name}**
rel=canonical
This resource.
- **uri=/management/weblogic/{version}/edit/WSReliableDeliveryPolicies**
rel=parent
The parent resource of this resource.
- **uri=/management/weblogic/{version}/edit/WSReliableDeliveryPolicies/{name}**
rel=self
This resource.

POST

Update this [weblogic.management.configuration.WSReliableDeliveryPolicyMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.WSReliableDeliveryPolicyMBean](#) entity.

/management/weblogic/{version}/edit/WSReliableDeliveryPolicyCreateForm

This resource manages the create forms for the WSReliableDeliveryPolicies collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.WSReliableDeliveryPolicyMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the [WSReliableDeliveryPolicies](#) collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.WSReliableDeliveryPolicyMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/WSReliableDeliveryPolicyCreateForm](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/WSReliableDeliveryPolicies](#)
rel=create
The collection resource for this create form resource.
- **uri**=[/management/weblogic/{version}/edit](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/WSReliableDeliveryPolicyCreateForm](#)
rel=self
This resource.

/management/weblogic/{version}/edit/WTCServerCreateForm

This resource manages the create forms for the WTCServers collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.WTCTServerMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the WTCTServers collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.WTCTServerMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/WTCTServerCreateForm](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/WTCTServers](#) **rel**=create
The collection resource for this create form resource.
- **uri**=[/management/weblogic/{version}/edit](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/WTCTServerCreateForm](#) **rel**=self
This resource.

/management/weblogic/{version}/edit/WTCServers

This resource manages a collection of [weblogic.management.configuration.WTCServerMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.WTCTServerMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.WTCTServerMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/WTCTServers](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/WTCTServerCreateForm](#)
rel=create-form
The create form resource for this collection resource.
- **uri**=[/management/weblogic/{version}/edit](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/WTCTServers](#) **rel**=self
This resource.

POST

Add a new [weblogic.management.configuration.WTCServerMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.WTCServerMBean](#) entity.

/management/weblogic/{version}/edit/WTCServers/{name}

This resource manages a [weblogic.management.configuration.WTCServerMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.WTCServerMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.WTCTServerMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.WTCTServerMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/WTCTServers/{name}/WTCTExportCreateForm](#) [rel=WTCTExportCreateForm](#)
The create form resource for this resource's WTCTExports collection resource.
- [uri=/management/weblogic/{version}/edit/WTCTServers/{name}/WTCTExports](#) [rel=WTCTExports](#)
This resource's WTCTExports collection resource.
- [uri=/management/weblogic/{version}/edit/WTCTServers/{name}/WTCTImportCreateForm](#) [rel=WTCTImportCreateForm](#)
The create form resource for this resource's WTCTImports collection resource.
- [uri=/management/weblogic/{version}/edit/WTCTServers/{name}/WTCTImports](#) [rel=WTCTImports](#)
This resource's WTCTImports collection resource.
- [uri=/management/weblogic/{version}/edit/WTCTServers/{name}/WTCTLocalTuxDomCreateForm](#) [rel=WTCTLocalTuxDomCreateForm](#)
The create form resource for this resource's WTCTLocalTuxDoms collection resource.
- [uri=/management/weblogic/{version}/edit/WTCTServers/{name}/WTCTLocalTuxDoms](#) [rel=WTCTLocalTuxDoms](#)
This resource's WTCTLocalTuxDoms collection resource.
- [uri=/management/weblogic/{version}/edit/WTCTServers/{name}/WTCTPasswordCreateForm](#) [rel=WTCTPasswordCreateForm](#)
The create form resource for this resource's WTCTPasswords collection resource.
- [uri=/management/weblogic/{version}/edit/WTCTServers/{name}/WTCTPasswords](#) [rel=WTCTPasswords](#)
This resource's WTCTPasswords collection resource.
- [uri=/management/weblogic/{version}/edit/WTCTServers/{name}/WTCTRemoteTuxDomCreateForm](#) [rel=WTCTRemoteTuxDomCreateForm](#)
The create form resource for this resource's WTCTRemoteTuxDoms collection resource.
- [uri=/management/weblogic/{version}/edit/WTCTServers/{name}/WTCTRemoteTuxDoms](#) [rel=WTCTRemoteTuxDoms](#)
This resource's WTCTRemoteTuxDoms collection resource.

- **uri**=/management/weblogic/{version}/edit/WTCservers/{name}/WTCresources **rel**=WTCresources
This resource's WTCresources singleton resource.
- **uri**=/management/weblogic/{version}/edit/WTCservers/{name}/WTCresourcesCreateForm **rel**=WTCresourcesCreateForm
The create form resource for this resource's WTCresources optional singleton resource.
- **uri**=/management/weblogic/{version}/edit/WTCservers/{name}/WTCtBridgeGlobal **rel**=WTCtBridgeGlobal
This resource's WTCtBridgeGlobal singleton resource.
- **uri**=/management/weblogic/{version}/edit/WTCservers/{name}/WTCtBridgeGlobalCreateForm **rel**=WTCtBridgeGlobalCreateForm
The create form resource for this resource's WTCtBridgeGlobal optional singleton resource.
- **uri**=/management/weblogic/{version}/edit/WTCservers/{name}/WTCtBridgeRedirectCreateForm **rel**=WTCtBridgeRedirectCreateForm
The create form resource for this resource's WTCtBridgeRedirects collection resource.
- **uri**=/management/weblogic/{version}/edit/WTCservers/{name}/WTCtBridgeRedirects **rel**=WTCtBridgeRedirects
This resource's WTCtBridgeRedirects collection resource.
- **uri**=/management/weblogic/{version}/edit/WTCservers/{name} **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/edit/WTCservers **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/edit/WTCservers/{name} **rel**=self
This resource.

POST

Update this [weblogic.management.configuration.WTCTServerMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.WTCTServerMBean](#) entity.

/management/weblogic/{version}/edit/WTCServers/{name}/WTCEXportCreateForm

This resource manages the create forms for the WTCEXports collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.WTCEXportMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the WTCEXports collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.WTCEXportMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/WTCServers/{name}/WTCEXportCreateForm](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/WTCServers/{name}/WTCEXports](#) **rel**=create

The collection resource for this create form resource.

- **uri**=[/management/weblogic/{version}/edit/WTCServers/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/WTCServers/{name}/WTCEXportCreateForm](#) **rel**=self

This resource.

/management/weblogic/{version}/edit/WTCServers/{name}/WTCEExports

This resource manages a collection of [weblogic.management.configuration.WTCEExportMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.WTCEXportMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.WTCEXportMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/WTCservers/{name}/WTCEXports](#)
rel=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/WTCservers/{name}/WTCEXportCreateForm](#) **rel**=create-form

The create form resource for this collection resource.

- **uri**=[/management/weblogic/{version}/edit/WTCservers/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/WTCservers/{name}/WTCEXports](#)
rel=self

This resource.

POST

Add a new [weblogic.management.configuration.WTCEExportMBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.WTCEExportMBean](#) entity.

/management/weblogic/{version}/edit/WTCServers/{name}/WTCEExports/{name} **}**

This resource manages a [weblogic.management.configuration.WTCEExportMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.WTCEExportMBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.management.configuration.WTCEExportMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.WTCEExportMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/WTCServers/{name}/WTCEExports/{name}](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/WTCServers/{name}/WTCEExports](#)
rel=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/WTCServers/{name}/WTCEExports/{name}](#) **rel**=self
This resource.

POST

Update this [weblogic.management.configuration.WTCEExportMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.WTCEExportMBean](#) entity.

/management/weblogic/{version}/edit/WTCServers/{name}/WTCImportCreateForm

This resource manages the create forms for the WTCImports collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.WTCImportMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the WTCImports collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.WTCImportMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/WTCServers/{name}/WTCImportCreateForm](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/WTCServers/{name}/WTCImports](#) **rel=create**
The collection resource for this create form resource.
- [uri=/management/weblogic/{version}/edit/WTCServers/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/WTCServers/{name}/WTCImportCreateForm](#) **rel=self**
This resource.

/management/weblogic/{version}/edit/WTCServers/{name}/WTCImports

This resource manages a collection of [weblogic.management.configuration.WTCImportMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.WTCImportMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.WTCImportMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/WTCServers/{name}/WTCImports](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/WTCServers/{name}/WTCImportCreateForm](#) **rel**=create-form
The create form resource for this collection resource.
- **uri**=[/management/weblogic/{version}/edit/WTCServers/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/WTCServers/{name}/WTCImports](#)
rel=self
This resource.

POST

Add a new [weblogic.management.configuration.WTCImportMBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.WTCImportMBean](#) entity.

/management/weblogic/{version}/edit/WTCServers/{name}/WTCImports/{name} **}**

This resource manages a [weblogic.management.configuration.WTCImportMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.WTCImportMBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.management.configuration.WTCImportMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.WTCImportMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/WTCServers/{name}/WTCImports/{name}](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/WTCServers/{name}/WTCImports](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/WTCServers/{name}/WTCImports/{name}](#) **rel**=self
This resource.

POST

Update this [weblogic.management.configuration.WTCImportMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.WTCImportMBean](#) entity.

/management/weblogic/{version}/edit/WTCServers/{name}/WTCLocalTuxDom CreateForm

This resource manages the create forms for the WTCLocalTuxDoms collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.WTCLocalTuxDomMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the [WTCLocalTuxDoms](#) collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.WTCLocalTuxDomMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/WTCServers/{name}/WTCLocalTuxDomCreateForm](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/WTCServers/{name}/WTCLocalTuxDoms](#) **rel=create**
The collection resource for this create form resource.
- [uri=/management/weblogic/{version}/edit/WTCServers/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/WTCServers/{name}/WTCLocalTuxDomCreateForm](#) **rel=self**
This resource.

/management/weblogic/{version}/edit/WTCServers/{name}/WTCLocalTuxDoms

This resource manages a collection of [weblogic.management.configuration.WTCLocalTuxDomMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.WTCLocalTuxDomMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.WTCLocalTuxDomMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/WTCServers/{name}/WTCLocalTuxDomms](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/WTCServers/{name}/WTCLocalTuxDomCreateForm](#) **rel**=create-form
The create form resource for this collection resource.
- **uri**=[/management/weblogic/{version}/edit/WTCServers/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/WTCServers/{name}/WTCLocalTuxDomms](#) **rel**=self
This resource.

POST

Add a new [weblogic.management.configuration.WTCLocalTuxDomMBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.WTCLocalTuxDomMBean](#) entity.

/management/weblogic/{version}/edit/WTCServers/{name}/WTCLocalTuxDoms/{name}

This resource manages a [weblogic.management.configuration.WTCLocalTuxDomMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.WTCLocalTuxDomMBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.management.configuration.WTCLocalTuxDomMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.WTCLocalTuxDomMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/WTCServers/{name}/WTCLocalTuxDoms/{name} rel=canonical](#)

This resource.

- [uri=/management/weblogic/{version}/edit/WTCServers/{name}/WTCLocalTuxDoms rel=parent](#)

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/WTCServers/{name}/WTCLocalTuxDoms/{name} rel=self](#)

This resource.

POST

Update this [weblogic.management.configuration.WTCLocalTuxDomMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.WTCLocalTuxDomMBean](#) entity.

/management/weblogic/{version}/edit/WTCServers/{name}/WTCPasswordCreateForm

This resource manages the create forms for the WTCPasswords collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.WTCPasswordMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the WTCPasswords collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.WTCPasswordMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/WTCServers/{name}/WTCPasswordCreateForm](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/WTCServers/{name}/WTCPasswords](#) **rel=create**
The collection resource for this create form resource.
- [uri=/management/weblogic/{version}/edit/WTCServers/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/WTCServers/{name}/WTCPasswordCreateForm](#) **rel=self**
This resource.

/management/weblogic/{version}/edit/WTCServers/{name}/WTCPasswords

This resource manages a collection of [weblogic.management.configuration.WTCPasswordMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.WTCPasswordMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.WTCPasswordMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/WTCServers/{name}/WTCPasswords](#)
[rel=canonical](#)
This resource.
- [uri=/management/weblogic/{version}/edit/WTCServers/{name}/WTCPasswordCreateForm](#) [rel=create-form](#)
The create form resource for this collection resource.
- [uri=/management/weblogic/{version}/edit/WTCServers/{name}](#) [rel=parent](#)
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/WTCServers/{name}/WTCPasswords](#)
[rel=self](#)
This resource.

POST

Add a new [weblogic.management.configuration.WTCTPasswordMBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.WTCTPasswordMBean](#) entity.

/management/weblogic/{version}/edit/WTCServers/{name}/WTCPasswords/{name}

This resource manages a [weblogic.management.configuration.WTCPasswordMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.WTCTPasswordMBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.management.configuration.WTCPasswordMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.WTCPasswordMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/WTCServers/{name}/WTCPasswords/{name}](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/WTCServers/{name}/WTCPasswords](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/WTCServers/{name}/WTCPasswords/{name}](#) **rel**=self
This resource.

POST

Update this [weblogic.management.configuration.WTCTPasswordMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.WTCTPasswordMBean](#) entity.

/management/weblogic/{version}/edit/WTCServers/{name}/WTCRemoteTuxDomCreateForm

This resource manages the create forms for the WTCRemoteTuxDoms collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.WTCRemoteTuxDomMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the [WTCRemoteTuxDoms](#) collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.WTCRemoteTuxDomMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/WTCServers/{name}/WTCRemoteTuxDomcreateForm](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/WTCServers/{name}/WTCRemoteTuxDoms](#) **rel=create**
The collection resource for this create form resource.
- [uri=/management/weblogic/{version}/edit/WTCServers/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/WTCServers/{name}/WTCRemoteTuxDomcreateForm](#) **rel=self**
This resource.

/management/weblogic/{version}/edit/WTCServers/{name}/WTCRemoteTuxDoms

This resource manages a collection of [weblogic.management.configuration.WTCRemoteTuxDomMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.WTCRemoteTuxDomMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.WTCRemoteTuxDomMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/WTCServers/{name}/WTCRemoteTuxDoms](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/WTCServers/{name}/WTCRemoteTuxDomCreateForm](#) **rel**=create-form
The create form resource for this collection resource.
- **uri**=[/management/weblogic/{version}/edit/WTCServers/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/WTCServers/{name}/WTCRemoteTuxDoms](#) **rel**=self
This resource.

POST

Add a new [weblogic.management.configuration.WTCRemoteTuxDomMBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.WTCRemoteTuxDomMBean](#) entity.

/management/weblogic/{version}/edit/WTCServers/{name}/WTCRemoteTuxDoms/{name}

This resource manages a [weblogic.management.configuration.WTCRemoteTuxDomMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.WTCRemoteTuxDomMBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.management.configuration.WTCRemoteTuxDomMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.WTCRemoteTuxDomMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/WTCServers/{name}/WTCRemoteTuxDoms/{name}](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/WTCServers/{name}/WTCRemoteTuxDoms](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/WTCServers/{name}/WTCRemoteTuxDoms/{name}](#) **rel=self**

This resource.

POST

Update this [weblogic.management.configuration.WTCRemoteTuxDomMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.WTCRemoteTuxDomMBean](#) entity.

/management/weblogic/{version}/edit/WTCServers/{name}/WTCResources

This resource manages a [weblogic.management.configuration.WTCResourcesMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.WTCResourcesMBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.management.configuration.WTCResourcesMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.WTCResourcesMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/WTCServers/{name}/WTCResources](#)
rel=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/WTCServers/{name}/WTCResourcesC](#)
[reateForm](#) **rel**=create-form

The create form resource for this optional singleton resource.

- **uri**=[/management/weblogic/{version}/edit/WTCServers/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/WTCServers/{name}/WTCResources](#)
rel=self

This resource.

POST

Update this [weblogic.management.configuration.WTCResourcesMBean](#) instance if it exists; otherwise, create it.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.WTCResourcesMBean](#) entity.

/management/weblogic/{version}/edit/WTCServers/{name}/WTCResourcesCreateForm

This resource manages the create forms for the WTCResources optional singleton instance.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.WTCResourcesMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the WTCResources optional singleton resource to create a new instance if it currently does not exist.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.WTCResourcesMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/WTCServers/{name}/WTCResourcesC
reateForm rel=canonical](#)
This resource.
- [uri=/management/weblogic/{version}/edit/WTCServers/{name}/WTCResourcesC
reateForm rel=create](#)
The optional singleton resource for this create form resource.
- [uri=/management/weblogic/{version}/edit/WTCServers/{name} rel=parent](#)
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/WTCServers/{name}/WTCResourcesC
reateForm rel=self](#)
This resource.

/management/weblogic/{version}/edit/WTCservers/{name}/WTCTBridgeGlobal

This resource manages a [weblogic.management.configuration.WTCTBridgeGlobalMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.WTCtBridgeGlobalMBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.management.configuration.WTCTBridgeGlobalMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.WTCTBridgeGlobalMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/WTCServers/{name}/WTCTBridgeGlobal](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/WTCServers/{name}/WTCTBridgeGlobalCreateForm](#) **rel**=create-form

The create form resource for this optional singleton resource.

- **uri**=[/management/weblogic/{version}/edit/WTCServers/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/WTCServers/{name}/WTCTBridgeGlobal](#) **rel**=self

This resource.

POST

Update this [weblogic.management.configuration.WTCtBridgeGlobalMBean](#) instance if it exists; otherwise, create it.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.WTCtBridgeGlobalMBean](#) entity.

/management/weblogic/{version}/edit/WTCservers/{name}/WTcBridgeGlobalCreateForm

This resource manages the create forms for the WTcBridgeGlobal optional singleton instance.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.WTCtBridgeGlobalMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the WTCtBridgeGlobal optional singleton resource to create a new instance if it currently does not exist.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.WTCtBridgeGlobalMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/WTCsServers/{name}/WTCtBridgeGlobalCreateForm](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/WTCsServers/{name}/WTCtBridgeGlobalCreateForm](#) **rel=create**
The optional singleton resource for this create form resource.
- [uri=/management/weblogic/{version}/edit/WTCsServers/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/WTCsServers/{name}/WTCtBridgeGlobalCreateForm](#) **rel=self**
This resource.

/management/weblogic/{version}/edit/WTCservers/{name}/WTCTBridgeRedirectCreateForm

This resource manages the create forms for the WTCTBridgeRedirects collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.WTCtBridgeRedirectMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the [WTCtBridgeRedirects](#) collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.WTCtBridgeRedirectMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/WTCServers/{name}/WTCtBridgeRedirectCreateForm](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/WTCServers/{name}/WTCtBridgeRedirects](#) **rel=create**
The collection resource for this create form resource.
- [uri=/management/weblogic/{version}/edit/WTCServers/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/WTCServers/{name}/WTCtBridgeRedirectCreateForm](#) **rel=self**
This resource.

/management/weblogic/{version}/edit/WTCServers/{name}/WTCTBridgeRedirects

This resource manages a collection of [weblogic.management.configuration.WTCTBridgeRedirectMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.WTCtBridgeRedirectMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.WTCtBridgeRedirectMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/WTCServers/{name}/WTCtBridgeRedirects](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/WTCServers/{name}/WTCtBridgeRedirectCreateForm](#) **rel=create-form**
The create form resource for this collection resource.
- [uri=/management/weblogic/{version}/edit/WTCServers/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/WTCServers/{name}/WTCtBridgeRedirects](#) **rel=self**
This resource.

POST

Add a new [weblogic.management.configuration.WTCtBridgeRedirectMBean](#) instance to this collection.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.WTCtBridgeRedirectMBean](#) entity.

/management/weblogic/{version}/edit/WTCServers/{name}/WTCTBridgeRedirects/{name}

This resource manages a [weblogic.management.configuration.WTCTBridgeRedirectMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

DELETE

Delete this [weblogic.management.configuration.WTCtBridgeRedirectMBean](#) instance.

Roles

Admin, Deployer

GET

Get this [weblogic.management.configuration.WTCTBridgeRedirectMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.WTCTBridgeRedirectMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/WTCServers/{name}/WTCTBridgeRedirects/{name} rel=canonical](#)
This resource.
- [uri=/management/weblogic/{version}/edit/WTCServers/{name}/WTCTBridgeRedirects rel=parent](#)
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/WTCServers/{name}/WTCTBridgeRedirects/{name} rel=self](#)
This resource.

POST

Update this [weblogic.management.configuration.WTCtBridgeRedirectMBean](#) instance.

Roles

Admin, Deployer

Request Body

Must contain a [weblogic.management.configuration.WTCtBridgeRedirectMBean](#) entity.

/management/weblogic/{version}/edit/XMLEntityCacheCreateForm

This resource manages the create forms for the XMLEntityCaches collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.XMLEntityCacheMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the XMLEntityCaches collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.XMLEntityCacheMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/XMLEntityCacheCreateForm](#)
rel=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/XMLEntityCaches](#) **rel**=create

The collection resource for this create form resource.

- **uri**=[/management/weblogic/{version}/edit](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/XMLEntityCacheCreateForm](#)
rel=self

This resource.

/management/weblogic/{version}/edit/XMLEntityCaches

This resource manages a collection of [weblogic.management.configuration.XMLEntityCacheMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.XMLEntityCacheMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.XMLEntityCacheMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/XMLEntityCaches](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/XMLEntityCacheCreateForm](#)
rel=create-form
The create form resource for this collection resource.
- **uri**=[/management/weblogic/{version}/edit](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/XMLEntityCaches](#) **rel**=self
This resource.

POST

Add a new [weblogic.management.configuration.XMLEntityCacheMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.XMLEntityCacheMBean](#) entity.

/management/weblogic/{version}/edit/XMLEntityCaches/{name}

This resource manages a [weblogic.management.configuration.XMLEntityCacheMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.XMLEntityCacheMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.XMLEntityCacheMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.XMLEntityCacheMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/XMLEntityCaches/{name}](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/XMLEntityCaches](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/XMLEntityCaches/{name}](#) **rel**=self
This resource.

POST

Update this [weblogic.management.configuration.XMLEntityCacheMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.XMLEntityCacheMBean](#) entity.

/management/weblogic/{version}/edit/XMLRegistries

This resource manages a collection of [weblogic.management.configuration.XMLRegistryMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.XMLRegistryMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.XMLRegistryMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/XMLRegistries](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/XMLRegistryCreateForm](#)
rel=create-form
The create form resource for this collection resource.
- **uri**=[/management/weblogic/{version}/edit](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/XMLRegistries](#) **rel**=self
This resource.

POST

Add a new [weblogic.management.configuration.XMLRegistryMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.XMLRegistryMBean](#) entity.

/management/weblogic/{version}/edit/XMLRegistries/{name}

This resource manages a [weblogic.management.configuration.XMLRegistryMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

DELETE

Delete this [weblogic.management.configuration.XMLRegistryMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.XMLRegistryMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.XMLRegistryMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/XMLRegistries/{name}/XMLEntitySpecRegistryEntries](#) **rel**=XMLEntitySpecRegistryEntries
This resource's XMLEntitySpecRegistryEntries collection resource.
- **uri**=[/management/weblogic/{version}/edit/XMLRegistries/{name}/XMLEntitySpecRegistryEntryCreateForm](#) **rel**=XMLEntitySpecRegistryEntryCreateForm
The create form resource for this resource's XMLEntitySpecRegistryEntries collection resource.
- **uri**=[/management/weblogic/{version}/edit/XMLRegistries/{name}/XMLParserSelectRegistryEntries](#) **rel**=XMLParserSelectRegistryEntries
This resource's XMLParserSelectRegistryEntries collection resource.
- **uri**=[/management/weblogic/{version}/edit/XMLRegistries/{name}/XMLParserSelectRegistryEntryCreateForm](#) **rel**=XMLParserSelectRegistryEntryCreateForm
The create form resource for this resource's XMLParserSelectRegistryEntries collection resource.
- **uri**=[/management/weblogic/{version}/edit/XMLRegistries/{name}](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/XMLRegistries](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/XMLRegistries/{name}](#) **rel**=self
This resource.

POST

Update this [weblogic.management.configuration.XMLRegistryMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.XMLRegistryMBean](#) entity.

/management/weblogic/{version}/edit/XMLRegistries/{name}/XMLEntitySpecRegistryEntries

This resource manages a collection of [weblogic.management.configuration.XMLEntitySpecRegistryEntryMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.XMLEntitySpecRegistryEntryMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.XMLEntitySpecRegistryEntryMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/XMLRegistries/{name}/XMLEntitySpecRegistryEntries](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/XMLRegistries/{name}/XMLEntitySpecRegistryEntryCreateForm](#) **rel=create-form**
The create form resource for this collection resource.
- [uri=/management/weblogic/{version}/edit/XMLRegistries/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/XMLRegistries/{name}/XMLEntitySpecRegistryEntries](#) **rel=self**
This resource.

POST

Add a new [weblogic.management.configuration.XMLEntitySpecRegistryEntryMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.XMLEntitySpecRegistryEntryMBean](#) entity.

/management/weblogic/{version}/edit/XMLRegistries/{name}/XMLEntitySpecRegistryEntries/{name}

This resource manages a [weblogic.management.configuration.XMLEntitySpecRegistryEntryMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.XMLEntitySpecRegistryEntryMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.XMLEntitySpecRegistryEntryMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.XMLEntitySpecRegistryEntryMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/XMLRegistries/{name}/XMLEntitySpecRegistryEntries/{name}](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/XMLRegistries/{name}/XMLEntitySpecRegistryEntries](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/XMLRegistries/{name}/XMLEntitySpecRegistryEntries/{name}](#) **rel**=self
This resource.

POST

Update this [weblogic.management.configuration.XMLEntitySpecRegistryEntryMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.XMLEntitySpecRegistryEntryMBean](#) entity.

/management/weblogic/{version}/edit/XMLRegistries/{name}/XMLEntitySpecRegistryEntryCreateForm

This resource manages the create forms for the XMLEntitySpecRegistryEntries collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.XMLEntitySpecRegistryEntryMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the [XMLEntitySpecRegistryEntries](#) collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.XMLEntitySpecRegistryEntryMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/XMLRegistries/{name}/XMLEntitySpecRegistryEntryCreateForm](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/XMLRegistries/{name}/XMLEntitySpecRegistryEntries](#) **rel=create**
The collection resource for this create form resource.
- [uri=/management/weblogic/{version}/edit/XMLRegistries/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/XMLRegistries/{name}/XMLEntitySpecRegistryEntryCreateForm](#) **rel=self**
This resource.

/management/weblogic/{version}/edit/XMLRegistries/{name}/XMLParserSelectRegistryEntries

This resource manages a collection of [weblogic.management.configuration.XMLParserSelectRegistryEntryMBean](#) instances.

The resource supports the following methods:

- [GET](#)
- [POST](#)

GET

Get this collection of [weblogic.management.configuration.XMLParserSelectRegistryEntryMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.configuration.XMLParserSelectRegistryEntryMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/XMLRegistries/{name}/XMLParserSelectRegistryEntries](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/edit/XMLRegistries/{name}/XMLParserSelectRegistryEntryCreateForm](#) **rel=create-form**
The create form resource for this collection resource.
- [uri=/management/weblogic/{version}/edit/XMLRegistries/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/edit/XMLRegistries/{name}/XMLParserSelectRegistryEntries](#) **rel=self**
This resource.

POST

Add a new [weblogic.management.configuration.XMLParserSelectRegistryEntryMBean](#) instance to this collection.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.XMLParserSelectRegistryEntryMBean](#) entity.

/management/weblogic/{version}/edit/XMLRegistries/{name}/XMLParserSelectRegistryEntries/{name}

This resource manages a [weblogic.management.configuration.XMLParserSelectRegistryEntryMBean](#) instance.

The resource supports the following methods:

- [DELETE](#)
- [GET](#)
- [POST](#)

DELETE

Delete this [weblogic.management.configuration.XMLParserSelectRegistryEntryMBean](#) instance.

Roles

Admin

GET

Get this [weblogic.management.configuration.XMLParserSelectRegistryEntryMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.XMLParserSelectRegistryEntryMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/edit/XMLRegistries/{name}/XMLParserSelectRegistryEntries/{name}](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/edit/XMLRegistries/{name}/XMLParserSelectRegistryEntries](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/edit/XMLRegistries/{name}/XMLParserSelectRegistryEntries/{name}](#) **rel=self**

This resource.

POST

POST

Update this [weblogic.management.configuration.XMLParserSelectRegistryEntryMBean](#) instance.

Roles

Admin

Request Body

Must contain a [weblogic.management.configuration.XMLParserSelectRegistryEntryMBean](#) entity.

/management/weblogic/{version}/edit/XMLRegistries/{name}/XMLParserSelectRegistryEntryCreateForm

This resource manages the create forms for the XMLParserSelectRegistryEntries collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.XMLParserSelectRegistryEntryMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the [XMLParserSelectRegistryEntries](#) collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.XMLParserSelectRegistryEntryMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/XMLRegistries/{name}/XMLParserSelectRegistryEntryCreateForm](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/edit/XMLRegistries/{name}/XMLParserSelectRegistryEntries](#) **rel**=create

The collection resource for this create form resource.

- **uri**=[/management/weblogic/{version}/edit/XMLRegistries/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/edit/XMLRegistries/{name}/XMLParserSelectRegistryEntryCreateForm](#) **rel**=self

This resource.

/management/weblogic/{version}/edit/XMLRegistryCreateForm

This resource manages the create forms for the XMLRegistries collection resource.

The resource supports the following methods:

- [GET](#)

GET

This resource returns a [weblogic.management.configuration.XMLRegistryMBean](#) entity populated with default values that can be customized then posted (using the POST method) to the XMLRegistries collection resource to create a new instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.configuration.XMLRegistryMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/edit/XMLRegistryCreateForm](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/edit/XMLRegistries](#) **rel**=create
The collection resource for this create form resource.
- **uri**=[/management/weblogic/{version}/edit](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/edit/XMLRegistryCreateForm](#) **rel**=self
This resource.

The following sections describe the data models on which the REST resources operate. These data models describe the information exchanged in REST resources.

java.util.Properties

This entity represents a JSONObject with a property for each property in the properties object, where the key is the property's name the value is a string containing the property's value.

weblogic.coherence.descriptor.wl.CoherenceAddressProviderBean

A unique name that identifies an address provider for Coherence cluster member.

The properties of the weblogic.coherence.descriptor.wl.CoherenceAddressProviderBean entity are as follows:

name

A unique name that identifies this well known address provider of a Coherence cluster member.

Type: string

Constraints: Read Only

weblogic.coherence.descriptor.wl.CoherenceAddressProvidersBean

A unique name that identifies all the address providers for a Coherence cluster.

This entity has no properties.

weblogic.coherence.descriptor.wl.CoherenceCacheBean

Information that represents a Coherence cache.

The properties of the weblogic.coherence.descriptor.wl.CoherenceCacheBean entity are as follows:

name

A unique name that identifies this Coherence cache.

Type: string

Constraints: Read Only

partition

The partition to which the Coherence cache belongs to.

Type: string

weblogic.coherence.descriptor.wl.CoherenceClusterParamsBean

The properties of the weblogic.coherence.descriptor.wl.CoherenceClusterParamsBean entity are as follows:

clusterListenPort

The cluster listen port used by Coherence; Coherence cluster members use this port to discover and join, or create the cluster. If unspecified, the Coherence cluster multicast listen port will be used.

Type: integer/int32

Constraints: Has Default Value: 0, Minimum Value: 0, Maximum Value: 65535

clusteringMode

Specifies a clustering mode of either Unicast or Multicast. If multicast is undesirable or unavailable in an environment, or when an environment is not properly configured to support multicast, then setting up the Well Known Addresses (WKA) feature is required. All cluster multicast communication is disabled if WKA is enabled.

Type: string

Constraints: Has Default Value: unicast, Legal Values: multicast, unicast

multicastListenAddress

The IP address for the cluster multicast listener.

Type: string

securityFrameworkEnabled

Check if security framework is enabled

Type: boolean

timeToLive

Sets the time-to-live (TTL) setting for the multicast message. The TTL setting designates how far multicast UDP/IP packets can travel on a network. The TTL is expressed in terms of how many hops a packet survives; each network interface, router, and managed switch is considered one hop. The TTL value should be set to the lowest integer value that works. Setting the value too high can use unnecessary bandwidth on other LAN segments and can even cause the operating system or network devices to disable multicast traffic.

Typically, setting the TTL value to 1 works on a simple switched backbone. A value of 2 or more may be required on an advanced backbone with intelligent switching. A value of 0 is used for single server clusters that are used for development and testing.

Type: integer/int32

Constraints: Has Default Value: 4, Minimum Value: 0, Maximum Value: 255

transport

Specify the underlying transport protocol to use for cluster communication. TMB, SDMB, or IMB are only applicable to Exalogic environment.

Type: string

Constraints: Has Default Value: udp, Legal Values: udp, tcp, ssl, tmb, sdmb, imb

weblogic.coherence.descriptor.wl.CoherenceClusterWellKnownAddressBean

A unique name that identifies a well known address of a Coherence cluster member. Other members can use this address to enroll into the cluster.

The properties of the weblogic.coherence.descriptor.wl.CoherenceClusterWellKnownAddressBean entity are as follows:

listenAddress

The IP address.

Type: string

name

A unique name that identifies this well known address of a Coherence cluster member.

Type: string

Constraints: Read Only

weblogic.coherence.descriptor.wl.CoherenceClusterWellKnownAddressesBean

A unique name that identifies all the well known addresses for a Coherence cluster.

This entity has no properties.

weblogic.coherence.descriptor.wl.CoherenceFederationParamsBean

Bean to configure Federation configuration to be used.

The properties of the weblogic.coherence.descriptor.wl.CoherenceFederationParamsBean entity are as follows:

federationTopology

The federation topology.

Type: string

Constraints: Has Default Value: none, Legal Values: none, active-active, active-passive, passive-active

remoteCoherenceClusterListenPort

The Coherence Cluster Listen Port of the remote participant.

Type: integer/int32

Constraints: Has Default Value: 7574

remoteCoherenceClusterName

The Coherence Cluster Name of the remote participant cluster.

Type: string

remoteParticipantHosts

The list of remote participant hosts, who will be added as participants in the federation topology.

Type: array of string

weblogic.coherence.descriptor.wl.CoherenceIdentityAsserterBean

Parameters to define an instance of a Coherence `com.tangosol.net.security.IdentityAsserter`.

The properties of the `weblogic.coherence.descriptor.wl.CoherenceIdentityAsserterBean` entity are as follows:

className

The class that implements `com.tangosol.net.security.IdentityAsserter`. If `className` is empty, no `IdentityAsserter` will be configured.

Type: string

Constraints: Legal Null: true

weblogic.coherence.descriptor.wl.CoherenceInitParamBean

The properties of the `weblogic.coherence.descriptor.wl.CoherenceInitParamBean` entity are as follows:

name

A unique name that identifies this initialization parameter.

Type: string

Constraints: Read Only

paramType

The parameter type.

Type: string

Constraints: Has Default Value: string, Legal Values: string, `java.lang.String`, `boolean`, `java.lang.Boolean`, `int`, `java.lang.Integer`, `long`, `java.lang.Long`, `double`, `java.lang.Double`, `decimal`, `java.math.BigDecimal`, `file`, `java.io.File`, `date`, `java.sql.Date`, `time`, `java.sql.Time`, `datetime`, `java.sql.Timestamp`

paramValue

The parameter value.

Type: string

Constraints: Has Default Value:

weblogic.coherence.descriptor.wl.CoherenceKeystoreParamsBean

Information needed to access key material for Coherence Identity from the keystore.

The properties of the `weblogic.coherence.descriptor.wl.CoherenceKeystoreParamsBean` entity are as follows:

coherenceIdentityAlias

The string alias used to store and retrieve the Coherence Identity private key in the keystore. This private key is associated with the Coherence Identity digital certificate. If this alias is null, the Server SSL identity alias will be used.

Type: string

Constraints: Has Default Value: null

coherencePrivateKeyPassPhrase

The passphrase used to retrieve the private key for the Coherence Identity specified in the server configured keystore. This passphrase is assigned to the private key when the private key is generated.

Note that when you get the value of this attribute, WebLogic Server does the following:

1. Retrieves the value of the `CoherencePrivateKeyPassPhrase` attribute.
2. Decrypts the value and returns the unencrypted passphrase.

Type: string

Constraints: Encrypted, Has Default Value: null, Legal Null: true

weblogic.coherence.descriptor.wl.CoherenceLoggingParamsBean

The properties of the `weblogic.coherence.descriptor.wl.CoherenceLoggingParamsBean` entity are as follows:

enabled

Specifies whether custom Coherence logging is enabled.

Type: boolean

Constraints: Has Default Value: true

loggerName

The logger name for Coherence logs.

Type: string

Constraints: Has Default Value: com.oracle.coherence, Legal Null: true

messageFormat

The Coherence logs message format.

Type: string

Constraints: Has Default Value: {date}/{uptime} {product} {version} <{level}> (thread={thread}, member={member}): {text}

weblogic.coherence.descriptor.wl.CoherencePersistenceParamsBean

Bean to override default Persistence environments in Coherence

The properties of the `weblogic.coherence.descriptor.wl.CoherencePersistenceParamsBean` entity are as follows:

activeDirectory

The active directory for the default persistence environment. If no value is specified, the directory which will be used is the coherence/active sub-directory under Domain Home directory.

Type: string

defaultPersistenceMode

The default persistence mode.

Type: string

Constraints: Has Default Value: on-demand, Legal Values: on-demand, active

snapshotDirectory

The snapshot directory for the default persistence environment. If no value is specified, the directory which will be used is coherence/snapshot sub-directory under Domain Home directory.

Type: string

trashDirectory

The trash directory for the default persistence environment. If no value is specified, the directory which will be used is coherence/trash sub-directory under Domain Home directory.

Type: string

weblogic.coherence.descriptor.wl.CoherenceServiceBean

Information that represents a Coherence service.

The properties of the weblogic.coherence.descriptor.wl.CoherenceServiceBean entity are as follows:

name

A unique name that identifies this Coherence service.

Type: string

Constraints: Read Only

partition

The partition to which the Coherence service belongs to.

Type: string

weblogic.coherence.descriptor.wl.CoherenceSocketAddressBean

A socket address for the Coherence Address Provider

The properties of the weblogic.coherence.descriptor.wl.CoherenceSocketAddressBean entity are as follows:

address

The IP address.

Type: string

name

A unique name that identifies this Address Socket of an Address Provider.

Type: string

Constraints: Read Only

port

The listen port.

Type: integer/int32

Constraints: Minimum Value: 1, Maximum Value: 65535

weblogic.coherence.descriptor.wl.WeblogicCoherenceBean

The top of the Coherence Cluster System Resource bean tree.

The properties of the weblogic.coherence.descriptor.wl.WeblogicCoherenceBean entity are as follows:

customClusterConfigurationFileLastUpdatedTimestamp

The timestamp at which the custom cluster configuration file was last updated.

Type: integer/int64

Constraints: Read Only

customClusterConfigurationFileName

The name of a custom Coherence operational configuration override file.

Type: string

Constraints: Read Only

name

A unique name that identifies this system resource in the WebLogic domain.

Type: string

Constraints: Read Only

version

The version of this file.

Type: string

weblogic.diagnostics.descriptor.WLDFActionBean

WLDF action configuration bean. This is a configuration point for action extensions developed outside of WebLogic.

A WLDF action extension is an action that is managed by, but not owned by, to WLDF. It must have a "type" associated with it, which must be provided to the WLDFWatchNotificationBean#createAction(String, String) method when an instance of this object is created. An instance of a WLDFActionBean defines a single instance configuration of an action extension, which can be referenced from WLDFWatchBean instances like any other action/notification type.

It acts as a container of an action properties, each property being a name/value pair. An action can have simple properties of intrinsic Java types (String, int, float, etc), encrypted properties, Map properties, and array properties.

Map and array properties can not contain nested collections or complex objects; that is, the leaf values of those objects must be simple values represented as String values.

WLDF will map these properties to the proper configuration points on the target action instance. Each action type will have different configuration points, so consult the documentation for those actions to see what the valid configuration properties are for that action type.

The properties of the `weblogic.diagnostics.descriptor.WLDFActionBean` entity are as follows:

enabled

Specifies whether this action is enabled.

Type: boolean

Constraints: Has Default Value: true

id

Return the unique id of this bean instance.

Type: integer/int64

Constraints: Read Only

name

The name of the WebLogic Diagnostic Framework (WLDF) bean.

Type: string

Constraints: Read Only

timeout

The length of time, in seconds, that an action has to complete execution. By default, the timeout period is 0, which disables the action timeout.

Type: integer/int32

Constraints: Has Default Value: 0, Minimum Value: 0

type

Defines the action type.

Type: string

Constraints: Read Only

weblogic.diagnostics.descriptor.WLDFArrayPropertyBean

Represents a named property that consists of an array of values.

The properties of the `weblogic.diagnostics.descriptor.WLDFArrayPropertyBean` entity are as follows:

id

Return the unique id of this bean instance.

Type: integer/int64

Constraints: Read Only

name

The name of the WebLogic Diagnostic Framework (WLDF) bean.

Type: string

Constraints: Read Only

value

Returns the array of values of this property.

Type: array of string

Constraints: Has Default Value: []

weblogic.diagnostics.descriptor.WLDFConfigurationPropertiesBean

Represents a set of WLDFPropertyBean and WLDFEncryptedPropertyBean instances, akin to a `java.util.Properties` object.

The properties of the `weblogic.diagnostics.descriptor.WLDFConfigurationPropertiesBean` entity are as follows:

id

Return the unique id of this bean instance.

Type: integer/int64

Constraints: Read Only

name

The name of the WebLogic Diagnostic Framework (WLDF) bean.

Type: string

Constraints: Read Only

weblogic.diagnostics.descriptor.WLDFConfigurationPropertyBean

Parent interface of all child beans of `WLDFConfigurationPropertiesBean`.

The properties of the `weblogic.diagnostics.descriptor.WLDFConfigurationPropertyBean` entity are as follows:

id

Return the unique id of this bean instance.

Type: integer/int64

Constraints: Read Only

name

The name of the WebLogic Diagnostic Framework (WLDF) bean.

Type: string

Constraints: Read Only

weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean

Represents an encrypted configuration property

The properties of the `weblogic.diagnostics.descriptor.WLDFEncryptedPropertyBean` entity are as follows:

encryptedValue

Returns the decrypted value of the property.

When you get the value of this attribute, WebLogic Server does the following:

1. Retrieves the value of the `ValueEncrypted` attribute.
2. Decrypts the value and returns the unencrypted password as a `String`.

When you set the value of this attribute, WebLogic Server does the following:

1. Encrypts the value.
2. Sets the value of the `ValueEncrypted` attribute to the encrypted value.

Using this attribute is a potential security risk because the `String` object (which contains the unencrypted password) remains in the JVM's memory until garbage collection removes it and the memory is reallocated. Depending on how memory is allocated in the JVM, a significant amount of time could pass before this unencrypted data is removed from memory.

Type: `string`

Constraints: Encrypted, Has Default Value:

id

Return the unique id of this bean instance.

Type: `integer/int64`

Constraints: Read Only

name

The name of the WebLogic Diagnostic Framework (WLDF) bean.

Type: `string`

Constraints: Read Only

weblogic.diagnostics.descriptor.WLDFHarvestedTypeBean

Defines the set of types (beans) that are harvested. The WLDF framework allows the harvesting of all designated server-local Weblogic Server runtime MBeans, and most customer MBeans that are registered in the local server's runtime MBean server. Configuration MBeans cannot be harvested.

The properties of the `weblogic.diagnostics.descriptor.WLDFHarvestedTypeBean` entity are as follows:

enabled

Specifies whether this type is enabled. Note that enabling a type will have no effect unless the Harvester component is also enabled.

A `true` value means that this type is harvested. A `false` value indicates that this type is not harvested.

Type: `boolean`

Constraints: Has Default Value: `true`

harvestedAttributes

The harvested attributes for this type. If a list of attributes is provided, only those attributes are harvested; otherwise all harvestable attributes are harvested.

Type: `array of string`

Constraints: Has Default Value: `null`

harvestedInstances

The harvested instances of this type.

The configuration of a type can optionally provide a set of identifiers for specific instances. If this list is provided, only the provided instances are harvested; otherwise all instances of the type are harvested.

The identifier for an instance must be a valid JMX ObjectName or an ObjectName pattern.

Type: array of string

Constraints: Has Default Value: null

id

Return the unique id of this bean instance.

Type: integer/int64

Constraints: Read Only

knownType

Specifies whether this type is known at startup. Normally, if a type is not available, the Harvester will keep looking for it. If a type is designated as "known", the Harvester issues a validation fault if the type cannot be immediately resolved.

A `true` value means that this type is known. A `false` value indicates that this type may not be known.

This flag is useful for WebLogic Server types, where the type information is always available. In this case, setting the flag to true results in earlier detection and reporting of problems.

This flag is optional, but is recommended for WebLogic Server types.

Type: boolean

Constraints: Has Default Value: false

name

The type name. For WebLogic Server runtime MBeans, the type name is the fully qualified name of the defining interface. For customer MBeans, the type name is the fully qualified MBean implementation class.

Type: string

Constraints: Legal Null: true

namespace

The namespace for the harvested type definition.

Type: string

Constraints: Has Default Value: ServerRuntime, Legal Values: ServerRuntime, DomainRuntime, Legal Null: true

weblogic.diagnostics.descriptor.WLDFHarvesterBean

Configures the behavior of the Harvester component of the WebLogic Diagnostic Framework (WLDF).

The properties of the `weblogic.diagnostics.descriptor.WLDFHarvesterBean` entity are as follows:

enabled

Specifies whether the Harvester component is enabled.

If true, all types that are both configured and enabled are harvested. If false, nothing is harvested.

Type: boolean

Constraints: Has Default Value: true

id

Return the unique id of this bean instance.

Type: integer/int64

Constraints: Read Only

name

The name of the WebLogic Diagnostic Framework (WLDF) bean.

Type: string

Constraints: Read Only

samplePeriod

The interval, in milliseconds, between samples.

Type: integer/int64

Constraints: Has Default Value: 300000, Minimum Value: 1000

weblogic.diagnostics.descriptor.WLDFHeapDumpActionBean

The properties of the weblogic.diagnostics.descriptor.WLDFHeapDumpActionBean entity are as follows:

enabled

Specifies whether this action is enabled.

Type: boolean

Constraints: Has Default Value: true

id

Return the unique id of this bean instance.

Type: integer/int64

Constraints: Read Only

liveSetOnly

Indicates whether or not to include the set of live objects in the heap dump capture.

Type: boolean

Constraints: Has Default Value: true

name

The name of the WebLogic Diagnostic Framework (WLDF) bean.

Type: string

Constraints: Read Only

timeout

The length of time, in seconds, that an action has to complete execution. By default, the timeout period is 0, which disables the action timeout.

Type: integer/int32

Constraints: Has Default Value: 0, Minimum Value: 0

weblogic.diagnostics.descriptor.WLDFImageNotificationBean

Use this interface to configure an image action, which will be sent when a diagnostic policy evaluates to true

Note: As of WebLogic Server 12.2.1, the terms *watch* and *notification* are replaced by *policy* and *action*, respectively. However, the definition of these terms has not changed.

The properties of the weblogic.diagnostics.descriptor.WLDFImageNotificationBean entity are as follows:

enabled

Specifies whether this action is enabled.

Type: boolean

Constraints: Has Default Value: true

id

Return the unique id of this bean instance.

Type: integer/int64

Constraints: Read Only

imageLockout

The length of time, in minutes, during which no diagnostic images requests will be accepted; that is, the minimum amount of time between image capture requests.

Type: integer/int32

Constraints: Minimum Value: 0

name

The name of the WebLogic Diagnostic Framework (WLDF) bean.

Type: string

Constraints: Read Only

timeout

The length of time, in seconds, that an action has to complete execution. By default, the timeout period is 0, which disables the action timeout.

Type: integer/int32

Constraints: Has Default Value: 0, Minimum Value: 0

weblogic.diagnostics.descriptor.WLDFInstrumentationBean

Use this interface to configure server-scope and application-scope instrumentation for diagnostic monitors that will execute diagnostic code at selected locations in server or application code.

The properties of the `weblogic.diagnostics.descriptor.WLDFInstrumentationMonitorBean` entity are as follows:

enabled

The state of the instrumentation behavior for the server or application. If `false`, there will no weaving (inserting of diagnostic code) in the application or server code during class loading. In addition, if woven classes are already loaded, disabling instrumentation will disable all the monitors in this scope.

Type: boolean

excludes

Pattern expressions for classes that will be excluded from this instrumentation scope. If specified, classes matching given patterns will not be instrumented.

Type: array of string

id

Return the unique id of this bean instance.

Type: integer/int64

Constraints: Read Only

includes

Pattern expressions for classes that are included in this instrumentation scope. If specified, only included classes will be instrumented. If not specified, all classes loaded within the application and which are not explicitly excluded are eligible for instrumentation.

A pattern can end with an asterisk (`*`), in which case it will match with all classes whose fully qualified classname starts with the prefix of the pattern. For example, `weblogic.rmi.*` will match with all classes in `weblogic.rmi` and its subpackages.

Type: array of string

name

The name of the WebLogic Diagnostic Framework (WLDF) bean.

Type: string

Constraints: Read Only

weblogic.diagnostics.descriptor.WLDFInstrumentationMonitorBean

This interface defines a diagnostic monitor, which is applied at the specified locations within the included classes in an instrumentation scope.

The properties of the `weblogic.diagnostics.descriptor.WLDFInstrumentationMonitorBean` entity are as follows:

actions

The diagnostic actions attached to this monitor. Actions are relevant only for delegating and custom monitors. Valid actions are: `TraceAction`, `DisplayArgumentsAction`, `MethodInvocationStatisticsAction`, `MethodMemoryAllocationStatisticsAction`, `StackDumpAction`, `ThreadDumpAction`, `TraceElapsedTimeAction`, and `TraceMemoryAllocationAction`

Type: array of string

description

Optional description of this monitor.

Type: string

dyeFilteringEnabled

Specifies whether dye filtering is enabled for the diagnostic actions associated with this monitor.

Type: boolean

dyeMask

The dye mask for all diagnostic actions associated with this monitor.

Type: string

enabled

Specifies whether the monitor and its associated diagnostics actions are enabled.

Type: boolean

Constraints: Has Default Value: true

excludes

Pattern expressions for classes that will be excluded for this instrumentation monitor. If specified, classes matching given patterns will not be instrumented with this monitor.

Type: array of string

id

Return the unique id of this bean instance.

Type: integer/int64

Constraints: Read Only

includes

Pattern expressions for classes that are included for this instrumentation monitor. If specified, only included classes will be instrumented with this monitor. If not specified, all classes loaded within the application and which are not explicitly excluded are eligible for instrumentation with this monitor.

A pattern can end with an asterisk (*), in which case it will match with all classes whose fully qualified classname starts with the prefix of the pattern. For example, `weblogic.rmi.*` will match with all classes in `weblogic.rmi` and its subpackages.

Type: array of string

locationType

Attached actions are applied at selected locations: *before*, *after*, or *around* pointcuts. This is relevant only for custom monitors. (A location where diagnostic code is added is called a diagnostic joinpoint. A set of joinpoints, identified by an expression, is called a pointcut.)

Once a location type is set, it cannot be changed.

Type: string

Constraints: Has Default Value: before, Legal Values: before, after, around

name

The name of the WebLogic Diagnostic Framework (WLDF) bean.

Type: string

Constraints: Read Only

pointcut

The pointcut expression for this monitor. (A location where diagnostic code is added is called a diagnostic joinpoint. A set of joinpoints, identified by an expression, is called a pointcut.)

Setting a pointcut expression is relevant only for custom monitors; for standard and delegating monitors, this definition is implicitly defined by WLDF.

Once a pointcut expression is set, it cannot be changed.

Type: string

properties

Properties for this monitor. Properties are name=value pairs, one pair per line. For example, `USER1=foo ADDR1=127.0.0.1`

Type: string

weblogic.diagnostics.descriptor.WLDFJMSNotificationBean

Use this interface to define a JMS action, which is sent when a diagnostic policy evaluates to true

Note: As of WebLogic Server 12.2.1, the terms *watch* and *notification* are replaced by *policy* and *action*, respectively. However, the definition of these terms has not changed.

The properties of the weblogic.diagnostics.descriptor.WLDFJMSNotificationBean entity are as follows:

connectionFactoryJNDIName

The JNDI name of the JMS connection factory. If a name has not been specified, the default JMS connection factory is used.

Type: string

Constraints: Has Default Value: weblogic.jms.ConnectionFactory, Legal Null: true

destinationJNDIName

The JNDI name of the JMS destination.

Type: string

Constraints: Legal Null: true

enabled

Specifies whether this action is enabled.

Type: boolean

Constraints: Has Default Value: true

id

Return the unique id of this bean instance.

Type: integer/int64

Constraints: Read Only

name

The name of the WebLogic Diagnostic Framework (WLDF) bean.

Type: string

Constraints: Read Only

timeout

The length of time, in seconds, that an action has to complete execution. By default, the timeout period is 0, which disables the action timeout.

Type: integer/int32

Constraints: Has Default Value: 0, Minimum Value: 0

weblogic.diagnostics.descriptor.WLDFJMXNotificationBean

Use this interface to define a JMX notification, which is sent when a diagnostic policy evaluates to true

Note: As of WebLogic Server 12.2.1, the terms *watch* and *notification* are replaced by *policy* and *action*, respectively. However, the definition of these terms has not changed.

The properties of the weblogic.diagnostics.descriptor.WLDFJMXNotificationBean entity are as follows:

enabled

Specifies whether this action is enabled.

Type: boolean

Constraints: Has Default Value: true

id

Return the unique id of this bean instance.

Type: integer/int64

Constraints: Read Only

name

The name of the WebLogic Diagnostic Framework (WLDF) bean.

Type: string

Constraints: Read Only

notificationType

The JMX notification type assigned to the resulting JMX notification.

Type: string

Constraints: Has Default Value: weblogic.diagnostics.watch.defaultNotificationType

timeout

The length of time, in seconds, that an action has to complete execution. By default, the timeout period is 0, which disables the action timeout.

Type: integer/int32

Constraints: Has Default Value: 0, Minimum Value: 0

weblogic.diagnostics.descriptor.WLDFLogActionBean

Configures an action that can record a customized log record using the WebLogic Server `NonCatalogLogger`. The custom log message set via `setMessage(String)` can be either a literal String or a compound EL expression.

The properties of the `weblogic.diagnostics.descriptor.WLDFLogActionBean` entity are as follows:

enabled

Specifies whether this action is enabled.

Type: boolean

Constraints: Has Default Value: true

id

Return the unique id of this bean instance.

Type: integer/int64

Constraints: Read Only

message

Returns the customized log message for this action.

Type: string

Constraints: Legal Null: true

name

The name of the WebLogic Diagnostic Framework (WLDF) bean.

Type: string

Constraints: Read Only

severity

The severity of the log message recorded by this action.

default weblogic.i18n.logging.Severities.NOTICE_TEXT legalValues
weblogic.i18n.logging.Severities.INFO_TEXT,
weblogic.i18n.logging.Severities.WARNING_TEXT,
weblogic.i18n.logging.Severities.ERROR_TEXT,
weblogic.i18n.logging.Severities.NOTICE_TEXT,
weblogic.i18n.logging.Severities.CRITICAL_TEXT,
weblogic.i18n.logging.Severities.ALERT_TEXT,
weblogic.i18n.logging.Severities.EMERGENCY_TEXT

Type: string

Constraints: Has Default Value: Notice, Legal Values: Info, Warning, Error, Notice, Critical, Alert, Emergency

subsystemName

Returns the customized log message for this action.

Type: string

Constraints: Legal Null: true

timeout

The length of time, in seconds, that an action has to complete execution. By default, the timeout period is 0, which disables the action timeout.

Type: integer/int32

Constraints: Has Default Value: 0, Minimum Value: 0

weblogic.diagnostics.descriptor.WLDFPropertyBean

Represents a simple unencrypted configuration property.

The properties of the weblogic.diagnostics.descriptor.WLDFPropertyBean entity are as follows:

id

Return the unique id of this bean instance.

Type: integer/int64

Constraints: Read Only

name

The name of the WebLogic Diagnostic Framework (WLDF) bean.

Type: string

Constraints: Read Only

value

Specifies the value of the property.

Type: string

Constraints: Has Default Value:

weblogic.diagnostics.descriptor.WLDFRESTNotificationBean

Use this interface to define a REST action, which is sent when a diagnostic policy evaluates to true

Note: As of WebLogic Server 12.2.1, the terms *watch* and *notification* are replaced by *policy* and *action*, respectively. However, the definition of these terms has not changed.

The properties of the weblogic.diagnostics.descriptor.WLDFRESTNotificationBean entity are as follows:

acceptedResponseType

Configures the Accept header of the HTTP request to the REST end point. The response entity of the REST invocation is ignored by the server.

Type: string

Constraints: Has Default Value: application/json, Legal Values: application/json, text/plain, text/xml, text/html

customNotificationProperties

Allows customizing the JSON object delivered to the REST end point.

Type: java.util.Properties

enabled

Specifies whether this action is enabled.

Type: boolean

Constraints: Has Default Value: true

endpointURL

The REST end point URL which will be invoked with the action payload.

Type: string

httpAuthenticationMode

The HTTP authentication mode when invoking the REST end point URL.

Type: string

Constraints: Has Default Value: None, Legal Values: None, Basic

httpAuthenticationPassword

The HTTP authentication password when the REST end point is secured.

Type: string

Constraints: Encrypted

httpAuthenticationUserName

The HTTP authentication user name when the REST end point is secured.

Type: string

id

Return the unique id of this bean instance.

Type: integer/int64

Constraints: Read Only

name

The name of the WebLogic Diagnostic Framework (WLDF) bean.

Type: string

Constraints: Read Only

restInvocationMethodType

The REST method for invoking the end point.

Type: string

Constraints: Has Default Value: PUT, Legal Values: PUT, POST

timeout

The length of time, in seconds, that an action has to complete execution. By default, the timeout period is 0, which disables the action timeout.

Type: integer/int32

Constraints: Has Default Value: 0, Minimum Value: 0

weblogic.diagnostics.descriptor.WLDFResourceBean

The top of the WebLogic Diagnostic Framework (WLDF) module bean tree.

All WLDF modules have a WLDFResourceBean as their root bean (a bean with no parent).

The properties of the weblogic.diagnostics.descriptor.WLDFResourceBean entity are as follows:

id

Return the unique id of this bean instance.

Type: integer/int64

Constraints: Read Only

name

The name of the WebLogic Diagnostic Framework (WLDF) bean.

Type: string

Constraints: Read Only

weblogic.diagnostics.descriptor.WLDFSMTPLNotificationBean

Use this interface to define a SMTP action, which is sent when a diagnostic policy evaluates to true

Note: As of WebLogic Server 12.2.1, the terms *watch* and *notification* are replaced by *policy* and *action*, respectively. However, the definition of these terms has not changed.

The properties of the weblogic.diagnostics.descriptor.WLDFSMTPLNotificationBean entity are as follows:

body

The body for the mail message. If the body is not specified, a body is created from the action information.

Type: string

enabled

Specifies whether this action is enabled.

Type: boolean

Constraints: Has Default Value: true

id

Return the unique id of this bean instance.

Type: integer/int64

Constraints: Read Only

mailSessionJNDIName

The JNDI name of the mail session. This name must match the attribute in the corresponding MailSessionMBean.

Type: string

Constraints: Legal Null: true

name

The name of the WebLogic Diagnostic Framework (WLDF) bean.

Type: string

Constraints: Read Only

recipients

The address of the recipient or recipients of the SMTP action mail. The address uses the syntax defined in RFC822. Typical address syntax is of the form *userhostdomain* or

Personal Name. An address can include multiple recipients, separated by commas or spaces.

For more information, refer to the `javax.mail.internet.InternetAddress.parse` method.

Type: array of string

subject

The subject for the mail message. If the subject is not specified, a subject is created from the action information.

Type: string

timeout

The length of time, in seconds, that an action has to complete execution. By default, the timeout period is 0, which disables the action timeout.

Type: integer/int32

Constraints: Has Default Value: 0, Minimum Value: 0

weblogic.diagnostics.descriptor.WLDFSNMPNotificationBean

Use this interface to define an SNMP action, which is sent when a diagnostic policy evaluates to `true`

Note: As of WebLogic Server 12.2.1, the terms *watch* and *notification* are replaced by *policy* and *action*, respectively. However, the definition of these terms has not changed.

The properties of the `weblogic.diagnostics.descriptor.WLDFSNMPNotificationBean` entity are as follows:

enabled

Specifies whether this action is enabled.

Type: boolean

Constraints: Has Default Value: true

id

Return the unique id of this bean instance.

Type: integer/int64

Constraints: Read Only

name

The name of the WebLogic Diagnostic Framework (WLDF) bean.

Type: string

Constraints: Read Only

timeout

The length of time, in seconds, that an action has to complete execution. By default, the timeout period is 0, which disables the action timeout.

Type: integer/int32

Constraints: Has Default Value: 0, Minimum Value: 0

weblogic.diagnostics.descriptor.WLDFScaleDownActionBean

Defines a scale-down event that can be assigned to a WLDF policy.

The properties of the weblogic.diagnostics.descriptor.WLDFScaleDownActionBean entity are as follows:

clusterName

Indicates the name of the cluster to perform the scaling action on.

Type: string

Constraints: Legal Null: true

enabled

Specifies whether this action is enabled.

Type: boolean

Constraints: Has Default Value: true

id

Return the unique id of this bean instance.

Type: integer/int64

Constraints: Read Only

name

The name of the WebLogic Diagnostic Framework (WLDF) bean.

Type: string

Constraints: Read Only

scalingSize

Indicates the number of instances to scale by when the action is invoked.

Type: integer/int32

Constraints: Has Default Value: 1, Minimum Value: 1

timeout

The length of time, in seconds, that an action has to complete execution. By default, the timeout period is 0, which disables the action timeout.

Type: integer/int32

Constraints: Has Default Value: 0, Minimum Value: 0

weblogic.diagnostics.descriptor.WLDFScaleUpActionBean

Defines a scale-up event that can be assigned to a WLDF policy.

The properties of the weblogic.diagnostics.descriptor.WLDFScaleUpActionBean entity are as follows:

clusterName

Indicates the name of the cluster to perform the scaling action on.

Type: string

Constraints: Legal Null: true

enabled

Specifies whether this action is enabled.

Type: boolean

Constraints: Has Default Value: true

id

Return the unique id of this bean instance.

Type: integer/int64

Constraints: Read Only

name

The name of the WebLogic Diagnostic Framework (WLDF) bean.

Type: string

Constraints: Read Only

scalingSize

Indicates the number of instances to scale by when the action is invoked.

Type: integer/int32

Constraints: Has Default Value: 1, Minimum Value: 1

timeout

The length of time, in seconds, that an action has to complete execution. By default, the timeout period is 0, which disables the action timeout.

Type: integer/int32

Constraints: Has Default Value: 0, Minimum Value: 0

weblogic.diagnostics.descriptor.WLDFScheduleBean

Defines a timer schedule for use with WLDF policies and actions and Harvester.

Each field uses syntax as defined by the EJB Timer ScheduleExpression class.

The properties of the weblogic.diagnostics.descriptor.WLDFScheduleBean entity are as follows:

dayOfMonth

Indicates the day of the month for the schedule.

Defaults to "*" (every day).

Type: string

Constraints: Has Default Value: *

dayOfWeek

Indicates the day of the week for the schedule.

Defaults to "*" (every day).

Type: string

Constraints: Has Default Value: *

hour

Indicates the hour(s) of the day for the schedule.

Defaults to "*" (every hour).

Type: string

Constraints: Has Default Value: *

id

Return the unique id of this bean instance.

Type: integer/int64

Constraints: Read Only

minute

Indicates the minutes of the hour for the schedule.

Defaults to every five minutes of the hour.

Type: string

Constraints: Has Default Value: */5

month

Indicates the month for the schedule.

Defaults to "*" (every month).

Type: string

Constraints: Has Default Value: *

name

The name of the WebLogic Diagnostic Framework (WLDF) bean.

Type: string

Constraints: Read Only

second

Indicates the second(s) of the minute for the schedule.

Defaults to "0" (at the "0" second of each minute).

Type: string

Constraints: Has Default Value: 0

timezone

Indicates the time zone for the schedule.

Defaults to the default time zone for the local VM.

Type: string

Constraints: Has Default Value: null, Legal Null: true

year

Indicates the year for the schedule.

Defaults to "*" (every year).

Type: string

Constraints: Has Default Value: *

weblogic.diagnostics.descriptor.WLDFScriptActionBean

Configures an action that can execute an external command-line process. This action type can be used to execute custom scripts when a policy rule is triggered.

Note that any child process forked by an action of this type will have all the rights and privileges of the WebLogic Server process that spawns it. Care must be taken that the target script is available and can be read/executed by the system-level identity that owns the WebLogic Server process.

The properties of the weblogic.diagnostics.descriptor.WLDFScriptActionBean entity are as follows:

enabled

Specifies whether this action is enabled.

Type: boolean

Constraints: Has Default Value: true

environment

A map of environment variables to set for the child process.

Type: java.util.Properties

id

Return the unique id of this bean instance.

Type: integer/int64

Constraints: Read Only

name

The name of the WebLogic Diagnostic Framework (WLDF) bean.

Type: string

Constraints: Read Only

parameters

An array of ordered command-line arguments to the target script.

Type: array of string

pathToScript

The full path to the script to execute.

Type: string

Constraints: Legal Null: true

timeout

The length of time, in seconds, that an action has to complete execution. By default, the timeout period is 0, which disables the action timeout.

Type: integer/int32

Constraints: Has Default Value: 0, Minimum Value: 0

workingDirectory

The working directory for the child process. If not set the working directory will be the same as the WebLogic Server parent process.

Type: string

weblogic.diagnostics.descriptor.WLDFThreadDumpActionBean

The properties of the weblogic.diagnostics.descriptor.WLDFThreadDumpActionBean entity are as follows:

enabled

Specifies whether this action is enabled.

Type: boolean

Constraints: Has Default Value: true

id

Return the unique id of this bean instance.

Type: integer/int64

Constraints: Read Only

name

The name of the WebLogic Diagnostic Framework (WLDF) bean.

Type: string

Constraints: Read Only

threadDumpCount

The number of thread dumps to capture.

Type: integer/int32

Constraints: Has Default Value: 3, Minimum Value: 1, Maximum Value: 20

threadDumpDelaySeconds

The delay, in seconds, to pause between thread dump captures.

Type: integer/int32

Constraints: Has Default Value: 10, Minimum Value: 1

timeout

The length of time, in seconds, that an action has to complete execution. By default, the timeout period is 0, which disables the action timeout.

Type: integer/int32

Constraints: Has Default Value: 0, Minimum Value: 0

weblogic.diagnostics.descriptor.WLDFWatchBean

Defines policies and actions.

Note: As of WebLogic Server 12.2.1, the terms *watch* and *notification* are replaced by *policy* and *action*, respectively. However, the definition of these terms has not changed.

The properties of the weblogic.diagnostics.descriptor.WLDFWatchBean entity are as follows:

alarmResetPeriod

For automatic alarms, the time period, in milliseconds, to wait after the policy evaluates to true before the alarm is automatically reset.

The default reset period is 60000 milliseconds, which is equivalent to 60 seconds.

Type: integer/int32

Constraints: Has Default Value: 60000, Minimum Value: 1000

alarmType

The alarm type for the policy: manual or automatic. The default alarm type is manual.

Once a manually set alarm has triggered, it must be reset through the WebLogic Server Administration Console or programmatically before it can trigger again. An automatic reset alarm will reset after the specified time period has elapsed.

Type: string

Constraints: Has Default Value: None, Legal Values: None, ManualReset, AutomaticReset

enabled

Specifies whether this policy is enabled.

Type: boolean

Constraints: Has Default Value: true

expressionLanguage

Returns the expression language type used by the policy, either "EL" or "WLDF" (deprecated).

Type: string

id

Return the unique id of this bean instance.

Type: integer/int64

Constraints: Read Only

name

The name of the WebLogic Diagnostic Framework (WLDF) bean.

Type: string

Constraints: Read Only

notifications

The actions enabled for this policy.

Type: array of weblogic.diagnostics.descriptor.WLDFNotificationBean references

ruleExpression

The expression used to evaluate the policy.

Type: string

Constraints: Legal Null: true

ruleType

The expression type for the policy: HARVESTER_RULE_TYPE refers to harvested data, LOG_RULE_TYPE refers to server log entry data, DOMAIN_LOG_RULE_TYPE refers to domain log entry data, and EVENT_DATA_RULE_TYPE refers to instrumentation event data. The default type is HARVESTER_RULE_TYPE

For information on policy expressions, see "Using the Diagnostics Framework for Oracle WebLogic Server" at <http://docs.oracle.com/middleware/home/index.html>

Type: string

Constraints: Has Default Value: Harvester, Legal Values: Harvester, Log, DomainLog,EventData

severity

The severity level of the actions sent when this policy evaluates to `true`. When set, this level overrides the default value provided in the parent MBean. However, if no severity level is set (null), the value provided in the parent MBean is returned.

The severity levels are the same levels used by the logging framework and the `weblogic.logging.Severities` class.

Type: string

Constraints: Has Default Value: Notice, Legal Values: Info, Warning, Error, Notice, Critical, Alert, Emergency

weblogic.diagnostics.descriptor.WLDFWatchNotificationBean

Configures and controls the WebLogic Diagnostic Framework (WLDF) policy and action component; creates and deletes policy definitions; and defines the rules that apply to specific policies.

Note: As of WebLogic Server 12.2.1, the terms *watch* and *notification* are replaced by *policy* and *action*, respectively. However, the definition of these terms has not changed.

The properties of the `weblogic.diagnostics.descriptor.WLDFWatchNotificationBean` entity are as follows:

enabled

Specifies whether the policy and action component is enabled.

If `true` (the default), all configured policies are activated, incoming data or events are evaluated against the policies, and actions are generated when policy conditions are met. If `false`, all policies are rendered inactive.

Type: boolean

Constraints: Has Default Value: true

id

Return the unique id of this bean instance.

Type: integer/int64

Constraints: Read Only

logWatchSeverity

The threshold severity level of log messages evaluated by log policies. Messages with a lower severity than this value will be ignored and not evaluated against the policies.

Do not confuse `LogWatchSeverity` with `Severity`. `LogWatchSeverity` filters which log messages will be evaluated; `Severity` sets the default severity level for an action.

Type: string

Constraints: Has Default Value: Warning, Legal Values: Info, Warning, Error, Notice, Critical, Alert, Emergency

name

The name of the WebLogic Diagnostic Framework (WLDF) bean.

Type: string

Constraints: Read Only

notifications

The actions defined in this deployment.

Type: array of weblogic.diagnostics.descriptor.WLDFNotificationBean references

Constraints: Read Only

severity

The default action severity level for all policies. When a policy triggers, the severity level is delivered with the action.

The severity levels are the same levels used by the logging framework and the weblogic.logging.Severities class. If no level is specified, the default value is `Notice`

Type: string

Constraints: Has Default Value: Notice, Legal Values: Info, Warning, Error, Notice, Critical, Alert, Emergency

weblogic.j2ee.descriptor.wl.ClientParamsBean

This package provides parameters that govern JMS server behavior with regard to a client. For example, setting the client Id when using a particular connection factory.

The properties of the weblogic.j2ee.descriptor.wl.ClientParamsBean entity are as follows:

acknowledgePolicy

Acknowledge policy for non-transacted sessions that use the `CLIENT_ACKNOWLEDGE` mode. `All` indicates that calling `acknowledge` on a message acknowledges *all* unacknowledged messages received on the session. `Previous` specifies that calling `acknowledge` on a message acknowledges only unacknowledged messages up to, and including, the given message.

This parameter works around a change in the JMS specification and only applies to implementations that use the `CLIENT_ACKNOWLEDGE` acknowledge mode for a non-transacted session. Specifically, the specification allowed users to acknowledge all messages before and including the message being acknowledged. The specification was changed so that acknowledging any message acknowledges all messages ever received (even those received after the message being acknowledge).

`ACKNOWLEDGE_PREVIOUS` retains the old behavior (acknowledge all message up to and including the message being acknowledged). Whereas, `ACKNOWLEDGE_ALL` yields the new behavior, where all messages received by the given session are acknowledged regardless of which message is being used to effect the acknowledge.

This attribute is dynamic and can be changed at any time. However, changing the value does not affect existing connections. It only affects new connections made with this connection factory.

Type: string

Constraints: Has Default Value: All, Legal Values: All, Previous

allowCloseInOnMessage

Specifies whether a connection factory creates message consumers that allow a `close()` or `stop()` method to be issued within its `onMessage()` method call.

- If selected (set to true) on a custom connection factory, an `onMessage()` method callback is allowed to issue a `close()` method on its own `Session`, `Connection` and

JMSContext objects, or a `stop()` call on its own `Connection` and `JMSContext` objects. If false, these calls will throw an exception.

- Default JMS Connection Factories ("java:comp/DefaultJMSConnectionFactory", "weblogic.jms.ConnectionFactory", or "weblogic.jms.XAConnectionFactory") set this option to false and it cannot be modified.

Note: The `onMessage()` method of the Message Listener is allowed to call `close()` on its own `MessageConsumer` and `JMSConsumer` even when `AllowCloseInOnMessage` is set to false.

This value is dynamic and can be changed at any time. However, changing the value does not affect existing connections. It only affects new connections made with this connection factory.

Type: boolean

Constraints: Has Default Value: true

clientId

An optional Client ID for applications that use this JMS connection factory. If the Client ID Policy is set to `Restricted` (the default), then configuring a Client ID on the connection factory prevents more than one JMS client from using a connection from this factory.

This attribute is rarely configured and should normally be left at the default (blank), as JMS application programs can set their Client IDs dynamically using the standard JMS APIs `javax.jms.JMSContext.setClientID()` or `javax.jms.Connection.setClientID()`. The JMS application message processing containers (such as MDBs) normally make the Client ID configurable as part of container configuration.

This attribute is dynamic and can be changed at any time. However, changing the value does not affect existing connections. It only affects new connections made with this connection factory.

Type: string

Constraints: Legal Null: true

clientIdPolicy

The Client ID Policy indicates whether more than one JMS connection can use the same Client ID.

The valid values are:

- `CLIENT_ID_POLICY_RESTRICTED` - The default. Only one connection that uses this policy can exist in a cluster at any given time for a particular Client ID (if a connection already exists with a given Client ID, attempts to create new connections using this policy with the same Client ID fail with an exception).
- `CLIENT_ID_POLICY_UNRESTRICTED` - Connections created using this policy can specify any Client ID, even when other restricted or unrestricted connections already use the same Client ID. The Unrestricted Client ID capability was added in WebLogic 10.3.4 (11gR1PS3).

Notes:

- WebLogic JMS applications can override the Client ID Policy specified on the connection factory configuration by casting a `javax.jms.JMSContext` instance to `weblogic.jms.extensions.WLJMSContext` or a `javax.jms.Connection` instance to `weblogic.jms.extension.WLConnection` and calling `setClientID(String clientId, String clientIdPolicy)`

- Two connections with the same Client ID are treated as two different independent connections if they have a different Client ID Policy. This means a cluster can host a single Restricted Client ID Policy connection, and also concurrently host multiple Unrestricted Client ID Policy connections that have the same Client ID as the Restricted connection.
- Two durable subscriptions with the same Client ID and Subscription Name are treated as two different independent subscriptions if they have a different Client ID Policy. Similarly, two Sharable non-durable subscriptions with the same Client Id are treated as two different independent subscriptions if they have a different Client ID Policy.
- Durable subscriptions created using an Unrestricted Client Id must be unsubscribed using the `weblogic.jms.extensions.WLJMSContext.unsubscribe(Topic topic, String name)` instead of `javax.jms.JMSContext.unsubscribe(String name)` or using the `weblogic.jms.extensions.WLSession.unsubscribe(Topic topic, String name)`, instead of `javax.jms.Session.unsubscribe(String name)`

This attribute is dynamic and can be changed at any time. However, changing the value does not affect existing connections. It only affects new connections made with this connection factory.

Type: string

Constraints: Has Default Value: Restricted, Legal Values: Restricted, Unrestricted

messagesMaximum

The maximum number of messages that can exist for an asynchronous session and that have not yet been passed to the message listener. When the Synchronous Prefetch Mode is enabled, this value also affects synchronous sessions with a message consumer that will prefetch messages in one server access.

A value of -1 indicates that there is no limit on the number of messages. In this case, however, the limit is set to the amount of remaining virtual memory.

When the number of messages reaches the MessagesMaximum value:

- For multicast sessions, new messages are discarded according the policy specified by the `OverrunPolicy` parameter and a `DataOverrunException` is thrown.
- For non-multicast sessions, new messages are flow-controlled, or retained on the server until the application can accommodate the messages.

For multicast sessions, when a connection is stopped, messages will continue to be delivered, but only until the MessagesMaximum value is reached. Once this value is reached, messages will be discarded based on the Overrun policy.

This attribute is dynamic and can be changed at any time. However, changing the value does not affect existing connections. It only affects new connections made with this connection factory.

Type: integer/int32

Constraints: Has Default Value: 10

multicastOverrunPolicy

The policy to use when the number of outstanding multicast messages reaches the value specified in MessagesMaximum and some messages must be discarded.

- **Keep New** - Indicates that the most recent messages are given priority over the oldest messages, and the oldest messages are discarded, as needed.

- **Keep Old** - Indicates that the oldest messages are given priority over the most recent messages, and the most recent messages are discarded, as needed.

Message age is defined by the order of receipt, not by the `JMSTimestamp` value.

This attribute is dynamic and can be changed at any time. However, changing the value does not affect existing connections. It only affects new connections made with this connection factory.

Type: string

Constraints: Has Default Value: KeepOld, Legal Values: KeepOld, KeepNew

subscriptionSharingPolicy

Specifies the subscription sharing policy on this connection. Although this attribute is dynamic, the new values only take effect on future connections and have no impact to existing connections created before the value was changed.

The valid values are:

- **Exclusive** - The default. All subscribers created using this connection factory cannot share subscriptions with any other subscribers.
- **Sharable** - Subscribers created using this connection factory can share their subscriptions with other subscribers, regardless of whether those subscribers are created using the same connection factory or a different connection factory. Consumers can share a non-durable subscriptions only if they have the same Client ID and Client ID Policy; consumers can share a durable subscription only if they have the same Client ID, Client ID Policy, and Subscription Name. The Sharable Subscription Sharing capability was added in WebLogic 10.3.4 (11gR1PS3).

Notes:

- WebLogic JMS applications can override the Subscription Sharing Policy specified on the connection factory configuration by casting a `javax.jms.JMSText` instance to `weblogic.jms.extensions.WLJMSText` or a `javax.jms.Connection` instance to `weblogic.jms.extensions.WLConnection` and calling `setSubscriptionSharingPolicy(String subscriptionSharingPolicy)`
- Most applications with a Sharable Subscription Sharing Policy will also use an Unrestricted Client ID Policy in order to ensure that multiple connections with the same client ID can exist.
- Two durable subscriptions with the same Client ID and Subscription Name are treated as two different independent subscriptions if they have a different Client ID Policy. Similarly, two Sharable non-durable subscriptions with the same Client ID are treated as two different independent subscriptions if they have a different Client ID Policy.
- Durable subscriptions created using an Unrestricted Client Id must be unsubscribed using `weblogic.jms.extensions.WLJMSText.unsubscribe(Topic topic, String name)`, instead of `javax.jms.JMSText.unsubscribe(String name)` or using `weblogic.jms.extensions.WLSession.unsubscribe(Topic topic, String name)`, instead of `javax.jms.Session.unsubscribe(String name)`, regardless of the Subscription Sharing Policy (Exclusive or Sharable).

This attribute is dynamic and can be changed at any time. However, changing the value does not affect existing connections. It only affects new connections made with this connection factory.

Type: string

Constraints: Has Default Value: Exclusive, Legal Values: Exclusive, Sharable

synchronousPrefetchMode

Specifies whether a synchronous consumer will prefetch messages (that is, messages sent from the server to the client) in one server access.

- **Disabled** - Indicates that message prefetching is disabled.
- **Enabled** - Indicates that a synchronous consumer (queue receiver or topic subscriber) will prefetch messages. The amount of prefetched messages cannot exceed the maximum number of messages defined by the Messages Maximum parameter.
- **Topic Subscriber Only** - Indicates that only a synchronous topic subscriber will prefetch messages. The amount of prefetched messages cannot exceed the maximum number of messages defined by the Messages Maximum parameter.

Synchronous message prefetching does not support the following conditions, and will throw a JMS Exception when encountered:

- User (XA) transactions for synchronous message receives
- Multiple synchronous consumers per session (regardless of queue or topic)

This attribute is dynamic and can be changed at any time. However, changing the value does not affect existing connections. It only affects new connections made with this connection factory.

Type: string

Constraints: Has Default Value: disabled

weblogic.j2ee.descriptor.wl.DefaultDeliveryParamsBean

If a client does not specify certain parameters then the values that those parameters will take can be controlled with a default delivery parameters bean.

The properties of the weblogic.j2ee.descriptor.wl.DefaultDeliveryParamsBean entity are as follows:

defaultCompressionThreshold

The number of bytes for the serialized message body so any message exceeds this limit will trigger message compression when the message is sent or received by the JMS message producer or consumer.

The compression will occur either:

- On the JMS message producer's JVM if the JMS message producer's JVM is not collocated with the JMS provider's JVM and the message body size exceeds the threshold limit.
- On the JMS provider's JVM when the JMS message consumer's JVM is not collocated with the JMS provider's JVM and the message body size exceeds the threshold limit.

Type: integer/int32

Constraints: Has Default Value: 2147483647, Minimum Value: 0, Maximum Value: 2147483647

defaultDeliveryMode

The default delivery mode used for messages when a delivery mode is not explicitly defined.

All messages with a `DefaultDeliveryMode` of `null` that are produced on a connection created with this factory will receive this value. Message producers can get the delivery mode explicitly by calling the `javax.jms.MessageProducer.getDeliveryMode()` method.

This attribute is dynamic. It can be changed at any time. However, changing the value does not affect existing connections. It only affects new connections made with this connection factory.

Type: string

Constraints: Has Default Value: Persistent, Legal Values: Persistent, Non-Persistent

defaultPriority

The default priority used for messages when a priority is not explicitly defined.

All messages with a `DefaultPriority` of `-1` that are produced on a connection created with this factory will receive this value. Message producers can get the priority explicitly by calling the `javax.jms.MessageProducer.getPriority()` method.

This attribute is dynamic. It can be changed at any time. However, changing the value does not affect existing connections. It only affects new connections made with this connection factory.

Type: integer/int32

Constraints: Has Default Value: 4, Minimum Value: 0, Maximum Value: 9

defaultRedeliveryDelay

The delay time, in milliseconds, before rolled back or recovered messages are redelivered.

All messages consumed by a consumer created with this factory that have a `DefaultRedeliveryDelay` of `-1` will use this value.

Message consumers can get the redelivery delay explicitly by calling the `weblogic.jms.extensions.WLSession.getRedeliveryDelay()` method.

This attribute is dynamic. It can be changed at any time. However, changing the value does not affect existing connections. It only affects new connections made with this connection factory.

Type: integer/int64

Constraints: Has Default Value: 0, Minimum Value: 0, Maximum Value: 9223372036854775807

defaultTimeToDeliver

The delay time, in milliseconds, between when a message is produced and when it is made visible on its destination.

All messages produced by a producer created with this factory that have a `DefaultTimeToDeliver` of `-1` will use this value. Message producers can get the Time-to-Deliver explicitly by calling the `weblogic.jms.extensions.WLMessageProducer.getTimeToDeliver()` method.

This attribute is dynamic. It can be changed at any time. However, changing the value does not affect existing connections. It only affects new connections made with this connection factory.

Type: string

Constraints: Has Default Value: 0

defaultTimeToLive

The maximum length of time, in milliseconds, that a message exists. This value is used for messages when both the `time-to-live` is not explicitly set by the sender application that is using this connection factory and the `time-to-live` is not explicitly overridden by the destination's `TimeToLiveOverride` attribute. A value of 0 indicates that the message has an infinite amount time to live.

Message producer applications can set the `time-to-live` explicitly by calling the standard JMS `javax.jms.MessageProducer.setTimeToLive(long)` method. Note that programmatically setting `time-to-live` using `javax.jms.Message.setJMSExpiration()` has no effect - the message setter is ignored by the JMS send call as required by the JMS specification.

This attribute is dynamic. It can be changed at any time. However, changing the value does not affect existing connections. It only affects new connections made with this connection factory.

Type: integer/int64

Constraints: Has Default Value: 0, Minimum Value: 0, Maximum Value: 9223372036854775807

defaultUnitOfOrder

The default Unit-of-Order name for producers that connect using this connection factory. A Unit-of-Order allows for messages to be processed in a certain order, even among multiple recipients.

`System-generated` indicates that WebLogic Server will automatically generate a Unit-of-Order name. `User-Generated` indicates that the Unit-of-Order name will come from the name specified name in the `Unit-of-Order Name` field. If `None` is selected, no message ordering is enforced.

Type: string

Constraints: Legal Null: true

sendTimeout

The maximum length of time, in milliseconds, that a sender will wait when there isn't enough available space (no quota) on a destination to accommodate the message being sent.

The default time is 10 milliseconds. A value of 0 indicates that the sender does not want to wait for space.

This attribute is dynamic. It can be changed at any time. However, changing the value does not affect existing connections or their producers. It only affects new connections made with this connection factory. Producers inherit the setting from the connection factory used to create their session and connection. The value can then be overridden at run time by setting the value on the producer.

Type: integer/int64

Constraints: Has Default Value: 10, Minimum Value: 0, Maximum Value: 9223372036854775807

weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean

These parameters control what should happen to messages when failures occur. They allow the administrator to control error destinations, logging and other actions that might be taken when a message can not be delivered or when other failures are detected

The properties of the weblogic.j2ee.descriptor.wl.DeliveryFailureParamsBean entity are as follows:

errorDestination

The name of the target error destination for messages that have expired or reached their redelivery limit. If no error destination is configured, then such messages are simply dropped. If a message has expired or reached its redelivery limit, and the Expiration Policy is set to Redirect, then the message is moved to the specified Error Destination.

For standalone destinations, an error destination must be another standalone destination that is targeted to the same JMS server as the destinations for which the error destination is defined. For uniform distributed destinations (UDDs), the error destination must be another UDD that shares the same subdeployment (i.e., targets) as the current UDD.

This attribute is dynamically configurable, but only incoming messages are impacted; stored messages are not impacted.

Type: weblogic.j2ee.descriptor.wl.DestinationBean reference

expirationLoggingPolicy

The policy that defines what information about the message is logged when the Expiration Policy is set to Log. The valid logging policy values are:

- **%header%** - All JMS header fields are logged.
- **%properties%** - All user-defined properties are logged.
- **JMSDeliveryTime** - This WebLogic JMS-specific extended header field is logged.
- **JMSRedeliveryLimit** - This WebLogic JMS-specific extended header field is logged.
- **foo** - Any valid JMS header field or user-defined property is logged.

When specifying multiple values, enter them as a comma-separated list. The `%header%` and `%properties%` values are *not* case sensitive. For example, you could use `"%header%, %properties%"` for all the JMS header fields and user properties. However, the enumeration of individual JMS header fields and user-defined properties are case sensitive. To enumerate only individual JMS header fields you could use `"%header, name, address, city, state, zip"`

Note: The `JMSMessageID` field is always logged and cannot be turned off. Therefore, if the Expiration Logging Policy is not defined (i.e., null) or is defined as an empty string, then the output to the log file contains only the `JMSMessageID` of the message.

Type: string

Constraints: Has Default Value: null

expirationPolicy

The message Expiration Policy to use when an expired message is encountered on a destination. The valid expiration policies are:

None - Same as the Discard policy; expired messages are simply removed from the destination.

Discard - Removes expired messages from the messaging system. The removal is not logged and the message is not redirected to another location. If no value is defined for a given destination (i.e., None), then expired messages are discarded.

Log - Removes expired messages from the system and writes an entry to the server log file indicating that the messages have been removed from the system. The actual information that is logged is defined by the Expiration Logging Policy.

Redirect - Moves expired messages from their current location to the Error Destination defined for the destination. The message retains its body, and all of its properties. The message also retains all of its header fields, but with the following exceptions:

- The destination for the message becomes the error destination.
- All property overrides associated with the error destination are applied to the redirected message.
- If there is no Time-To-Live Override value for the error destination, then the message receives a new Expiration Time of zero (indicating that it will not expire again).

It is illegal to use the Redirect policy when there is no valid error destination defined for the destination. Similarly, it is illegal to remove the error destination for a destination that is using the Redirect policy.

Note: The Maximum Message quota is only enforced for sending new messages. It is ignored when moving messages because of the Redirect policy.

Type: string

Constraints: Has Default Value: Discard, Legal Values: Discard, Log, Redirect

redeliveryLimit

The number of redelivery tries a message can have before it is moved to the error destination. This setting overrides any redelivery limit set by the message sender. If the redelivery limit is configured, but no error destination is configured, then persistent and non-persistent messages are simply dropped (deleted) when they reach their redelivery limit.

The default value (-1) specifies that the destination will not override the message sender's redelivery limit setting.

Note: WebLogic Server supports the JMSXDeliveryCount message property, which specifies the number of message delivery attempts, where the first attempt is 1, the next attempt is 2, and so on. WebLogic Server makes a best effort to persist the delivery count, so that the delivery count does not reset back to 1 after a server reboot.

This attribute is dynamically configurable, but only incoming messages are impacted; previously sent messages continue to use their original redelivery limit.

Type: integer/int32

Constraints: Has Default Value: -1, Minimum Value: -1, Maximum Value: 2147483647

templateBean

This is used to find the template bean for this destination

Type: weblogic.j2ee.descriptor.wl.TemplateBean reference

Constraints: Read Only

weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean

Many delivery parameters can be set by the JMS client. These overrides, if set, will cause those specific parameters to be ignored and replaced by the value set here.

The properties of the weblogic.j2ee.descriptor.wl.DeliveryParamsOverridesBean entity are as follows:

deliveryMode

The delivery mode assigned to all messages that arrive at the destination regardless of the DeliveryMode specified by the message producer.

A value of No-Delivery specifies that the DeliveryMode will not be overridden.

Note: This attribute is dynamically configurable, but only incoming messages are impacted; stored messages are not impacted.

Type: string

Constraints: Has Default Value: No-Delivery, Legal Values: Persistent, Non-Persistent, No-Delivery

priority

The priority assigned to all messages that arrive at this destination, regardless of the Priority specified by the message producer. The default value (-1) specifies that the destination will not override the Priority set by the message producer.

Note: This attribute is dynamically configurable, but only incoming messages are impacted; stored messages are not impacted.

Type: integer/int32

Constraints: Has Default Value: -1, Minimum Value: -1, Maximum Value: 9

redeliveryDelay

The delay, in milliseconds, before rolled back or recovered messages are redelivered, regardless of the RedeliveryDelay specified by the consumer and/or connection factory. Redelivered queue messages are put back into their originating destination; redelivered topic messages are put back into their originating subscription. The default value (-1) specifies that the destination will not override the RedeliveryDelay setting specified by the consumer and/or connection factory.

Note: This attribute is dynamically configurable, but only incoming messages are impacted; stored messages are not impacted.

Note: Changing the RedeliveryDelay override only affects future rollbacks and recovers, it does not affect rollbacks and recovers that have already occurred.

Type: integer/int64

Constraints: Has Default Value: -1, Minimum Value: -1, Maximum Value: 9223372036854775807

templateBean

This is used to find the template bean for this destination

Type: weblogic.j2ee.descriptor.wl.TemplateBean reference

Constraints: Read Only

timeToDeliver

The default delay, either in milliseconds or as a schedule, between when a message is produced and when it is made visible on its target destination, regardless of the

delivery time specified by the producer and/or connection factory. The default value (-1) specifies that the destination will not override the TimeToDeliver setting specified by the producer and/or connection factory. The TimeToDeliver override can be specified either as a long or as a schedule.

Note: Changing the TimeToDeliver override only affects future message delivery, it does not affect message delivery of already produced messages.

Type: string

Constraints: Has Default Value: -1

timeToLive

The time-to-live assigned to all messages that arrive at this destination, regardless of the TimeToLive value specified by the message producer. The default value (-1) specifies that this setting will not override the TimeToLive setting specified by the message producer.

Range of Values: Between 0 and a positive 64-bit integer.

Note: This attribute is dynamically configurable, but only incoming messages are impacted; stored messages are not impacted.

Type: integer/int64

Constraints: Has Default Value: -1, Minimum Value: -1, Maximum Value: 9223372036854775807

weblogic.j2ee.descriptor.wl.DestinationKeyBean

Destination Key beans control the sorting criteria of JMS destinations

The properties of the weblogic.j2ee.descriptor.wl.DestinationKeyBean entity are as follows:

id

Return the unique identifier of this bean instance.

Type: integer/int64

Constraints: Read Only

keyType

The expected property type for this destination key.

Gets the "key-type" element

Type: string

Constraints: Has Default Value: String, Legal Values: Boolean, Byte, Short, Int, Long, Float, Double, String

name

The name of this entity, represented in XML as an attribute.

Many of the elements within the JMS module are named entities. All of the named entities encased by a type in the XML file must be unique. This is the identifier used to delineate a particular entity within the JMS module.

This attribute cannot be modified externally from the module (for example, with a deployment plan) because it may be used inside the module referentially.

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this named JMS descriptor bean.

JMS module saves this note in the JMS descriptor file as XML PCDATA. All left angle brackets (<) are converted to the XML entity <. Carriage returns/line feeds are preserved.

Note:

If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

property

Specifies a message property name or the name of a message header field on which to sort messages. Message header field keys ignore the key type and reference message header fields rather than message properties.

Note: For better performance, use message header fields as sorting keys, rather than message properties.

Range of Values:

The JMS Property name (including user properties) or message header fields that can be sorted on are:

- JMSMessageID
- JMSTimestamp
- JMSCorrelationID
- JMSPriority
- JMSExpiration
- JMSType
- JMSRedelivered
- JMSDeliveryTime
- JMS_BEA_Size
- JMS_BEA_UnitOfOrder

This attribute is not dynamically configurable. Gets the "property" element

Type: string

Constraints: Has Default Value: JMSMessageID

sortOrder

The direction (Ascending or Descending) in which this key will sort messages.

Selecting the *Ascending* option for the JMSMessageID property implies a FIFO (first in, first out) sort order (the default for destinations). Select the *Descending* option for a LIFO (last in, first out) sort order.

This attribute is not dynamically configurable.

Gets the "sort-order" element.

Type: string

Constraints: Has Default Value: Ascending, Legal Values: Ascending, Descending

weblogic.j2ee.descriptor.wl.FlowControlParamsBean

Many clients producing messages can cause the server to fall behind in processing messages. The flow control parameters can help by slowing down production of messages. Using flow control can help the overall throughput of the system.

The properties of the weblogic.j2ee.descriptor.wl.FlowControlParamsBean entity are as follows:

flowControlEnabled

Specifies whether a producer created using a connection factory allows flow control. If true, the associated message producers will be slowed down if a JMS server or a destination reaches its specified upper byte or message threshold.

Type: boolean

Constraints: Has Default Value: true

flowInterval

The adjustment period of time, in seconds, when a producer adjusts its flow from the FlowMaximum number of messages to the FlowMinimum amount, or vice versa.

When a producer is flow controlled, it is slowed down from its FlowMaximum to its FlowMinimum over the specified FlowInterval amount of seconds.

Type: integer/int32

Constraints: Has Default Value: 60, Minimum Value: 0, Maximum Value: 2147483647

flowMaximum

The maximum number of messages-per-second allowed for a producer that is experiencing a threshold condition. When a producer is flow controlled it will never be allowed to go faster than the FlowMaximum messages per second.

If a producer is not currently limiting its flow when a threshold condition is reached, the initial flow limit for that producer is set to FlowMaximum. If a producer is already limiting its flow when a threshold condition is reached (the flow limit is less than FlowMaximum), then the producer will continue at its current flow limit until the next time the flow is evaluated.

Note: Once a threshold condition has subsided, the producer is not permitted to ignore its flow limit. If its flow limit is less than the FlowMaximum, then the producer must gradually increase its flow to the FlowMaximum each time the flow is evaluated. When the producer finally reaches the FlowMaximum, it can then ignore its flow limit and send without limiting its flow.

Type: integer/int32

Constraints: Has Default Value: 500, Minimum Value: 1, Maximum Value: 2147483647

flowMinimum

The minimum number of messages-per-second allowed for a producer that is experiencing a threshold condition. This is the lower boundary of a producer's flow limit. That is, WebLogic JMS will not further slow down a producer whose message flow limit is at its FlowMinimum.

When a producer is flow controlled it will never be required to go slower than FlowMinimum messages per second.

Type: integer/int32

Constraints: Has Default Value: 50, Minimum Value: 1, Maximum Value: 2147483647

flowSteps

The number of steps used when a producer is adjusting its flow from the Flow Maximum amount of messages to the Flow Minimum amount, or vice versa. Specifically, the Flow Interval adjustment period is divided into the number of Flow Steps (for example, 60 seconds divided by 6 steps is 10 seconds per step).

Also, the movement (i.e., the rate of adjustment) is calculated by dividing the difference between the Flow Maximum and the Flow Minimum into steps. At each Flow Step, the flow is adjusted upward or downward, as necessary, based on the current conditions, as follows:

- The downward movement (the decay) is geometric over the specified period of time (Flow Interval) and according to the specified number of Flow Steps. (For example, 100, 50, 25, 12.5)
- The movement upward is linear. The difference is simply divided by the number of steps.

Type: integer/int32

Constraints: Has Default Value: 10, Minimum Value: 1, Maximum Value: 2147483647

oneWaySendMode

Specifies whether message producers created using this connection factory are allowed to do one-way message sends to improve typical non-persistent, non-transactional messaging performance. When enabled, the associated queue senders and/or topic publishers can send messages without internally waiting for a response from the target destination's host JMS server.

One-way sends are supported only when the connection factory hosting the producer and the JMS server hosting the target destination are targeted to the same WebLogic Server instance. In addition, one-way sends are not supported for higher quality-of-service (QOS) features, such as XA, transacted sessions, persistent messaging, unit-of-order, unit-of-work, distributed destinations, and client-side store-and-forward. If the producer and target destination are in separate domains, or if any of these higher QOS features are detected, then the one-way mode setting will be ignored and standard two-way sends will be used instead.

- **Disabled** One-way send is disabled.
- **Enabled** One-way send is permitted for queue senders or topic publishers.
- **Topic Only** Only topic publishers are permitted to do one-way sends.

Notes:

- One-way message sends are disabled if your connection factory is configured with `XA Connection Factory Enabled`. This setting disables one-way sends whether or not the sender actually uses transactions.
- To benefit from one-way performance, the default `OneWay Send Window Size` value must also be configured higher. After every `OneWaySendWindowSize - 1` number of messages, a two-way is used instead of a one-way, so all messages are actually two-way when the `OneWaySendWindowSize = 1`

Type: string

Constraints: Has Default Value: disabled

oneWaySendWindowSize

Specifies the maximum number of sent messages per window when One-Way Send Mode is set to allow queue senders and/or topic publishers to make one-way sends. The window size determines when a two-way message is required to regulate the producer before it can continue making additional one-way sends.

To benefit from one-way performance, the default One-Way Send Window Size value must be configured higher *in addition to* enabling one-way sends. After every `OneWaySendWindowSize - 1` number of messages, a two-way is used instead of a one-way, so all messages are actually two-way when the `OneWaySendWindowSize = 1`

Type: integer/int32

Constraints: Has Default Value: 1, Minimum Value: 1, Maximum Value: 2147483647

weblogic.j2ee.descriptor.wl.ForeignConnectionFactoryBean

This bean represents a connection factory from a remote JNDI context.

The properties of the `weblogic.j2ee.descriptor.wl.ForeignConnectionFactoryBean` entity are as follows:

connectionHealthChecking

Controls connection health checking for JMS resource reference pools that access this JMS foreign connection factory mapping. The default value is `Enabled`

Oracle recommends selecting `Disabled` only when directed to do so by customer support.

Type: string

Constraints: Has Default Value: enabled

id

Return the unique identifier of this bean instance.

Type: integer/int64

Constraints: Read Only

localJNDIName

The name that the remote object will be bound to in the local server's JNDI tree. This is the name that should be used to look up the object on the local server.

Type: string

name

The name of this entity, represented in XML as an attribute.

Many of the elements within the JMS module are named entities. All of the named entities encased by a type in the XML file must be unique. This is the identifier used to delineate a particular entity within the JMS module.

This attribute cannot be modified externally from the module (for example, with a deployment plan) because it may be used inside the module referentially.

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this named JMS descriptor bean.

JMS module saves this note in the JMS descriptor file as XML PCDATA. All left angle brackets (<) are converted to the XML entity <. Carriage returns/line feeds are preserved.

Note:

If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

password

The password used in conjunction with the user name specified in the `Username` parameter to access the remote connection factory.

Type: string

Constraints: Encrypted

remoteJNDIName

The name of the remote object that will be looked up in the remote JNDI directory.

Type: string

username

The user name that is passed when opening a connection to the remote server (represented by this foreign connection factory).

Type: string

weblogic.j2ee.descriptor.wl.ForeignDestinationBean

This bean represents a destination from a remote JNDI context.

The properties of the `weblogic.j2ee.descriptor.wl.ForeignDestinationBean` entity are as follows:

id

Return the unique identifier of this bean instance.

Type: integer/int64

Constraints: Read Only

localJNDIName

The name that the remote object will be bound to in the local server's JNDI tree. This is the name that should be used to look up the object on the local server.

Type: string

name

The name of this entity, represented in XML as an attribute.

Many of the elements within the JMS module are named entities. All of the named entities encased by a type in the XML file must be unique. This is the identifier used to delineate a particular entity within the JMS module.

This attribute cannot be modified externally from the module (for example, with a deployment plan) because it may be used inside the module referentially.

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this named JMS descriptor bean.

JMS module saves this note in the JMS descriptor file as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note:

If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

remoteJNDIName

The name of the remote object that will be looked up in the remote JNDI directory.

Type: string

weblogic.j2ee.descriptor.wl.ForeignServerBean

This bean represents foreign resources.

The properties of the `weblogic.j2ee.descriptor.wl.ForeignServerBean` entity are as follows:

JNDIPropertiesCredential

Any Credentials that must be set for the JNDI provider. These Credentials will be part of the properties will be passed directly to the constructor for the JNDI provider's `InitialContext` class.

Some foreign providers require other properties to be set while obtaining an initial naming context. These properties can be set with a property bean

Type: string

Constraints: Encrypted

connectionURL

The URL that WebLogic Server will use to contact the JNDI provider. The syntax of this URL depends on which JNDI provider is being used. For WebLogic JMS, leave this field blank if you are referencing WebLogic JMS objects within the same cluster.

This value corresponds to the standard JNDI property, `java.naming.provider.url`

Note: If this value is not specified, look-ups will be performed on the JNDI server within the WebLogic Server instance where this connection factory is deployed.

Type: string

Constraints: Legal Null: true

defaultTargetingEnabled

Specifies whether this JMS resource defaults to the parent module's targeting or uses the subdeployment targeting mechanism.

When set to true, this resource implicitly inherits the targeting of its parent module. When set to false, this resource gets targeted based its subdeployment's targets, if one is specified.

Type: boolean

Constraints: Has Default Value: false

id

Return the unique identifier of this bean instance.

Type: integer/int64

Constraints: Read Only

initialContextFactory

The name of the class that must be instantiated to access the JNDI provider. This class name depends on the JNDI provider and the vendor that are being used.

This value corresponds to the standard JNDI property, `java.naming.factory.initial`

Note: This value defaults to `weblogic.jndi.WLInitialContextFactory`, which is the correct value for WebLogic Server.

Type: string

Constraints: Has Default Value: `weblogic.jndi.WLInitialContextFactory`

name

The name of this entity, represented in XML as an attribute.

Many of the elements within the JMS module are named entities. All of the named entities encased by a type in the XML file must be unique. This is the identifier used to delineate a particular entity within the JMS module.

This attribute cannot be modified externally from the module (for example, with a deployment plan) because it may be used inside the module referentially.

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this named JMS descriptor bean.

JMS module saves this note in the JMS descriptor file as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note:

If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

subDeploymentName

Gets the name of the sub-deployment to use when targeting this entity

Entities are targeted using a sub-deployment with this name. The targets of the sub-deployment will be the targets of this entity.

Type: string

weblogic.j2ee.descriptor.wl.GroupParamsBean

The group params bean represents items that may be templated based on the sub-deployment of the host `DestinationBean`. While many attributes of a `Destination` can be templated regardless of where the `Destination` is targeted, others cannot. Those elements that must be templated based on the target group of the destination are represented in this bean. A `Destination` will use the values in a `GroupParamsBean` if and only if the corresponding value is not explicitly set in the `DestinationBean` AND

the sub-deployment-name of the Destination matches the sub-deployment-name attribute of this bean AND this GroupParamsBean is a child of the template pointed to by the Destination.

The properties of the weblogic.j2ee.descriptor.wl.GroupParamsBean entity are as follows:

errorDestination

Gets the name of the error destination that should be used for members who have the same sub-deployment-name. If this value is not set then the value from the templates DeliveryFailureParamsBean will be used if it is set.

Type: weblogic.j2ee.descriptor.wl.DestinationBean reference

subDeploymentName

The name of the subdeployment that template parameters apply to. A subdeployment with the specified name must exist in the topic or queue for the parameters to apply.

Type: string

Constraints: Read Only

weblogic.j2ee.descriptor.wl.JDBCConnectionPoolParamsBean

Contains the connection pool parameters of a data source.

Configuration parameters for a data source's connection pool are specified using the connection pool parameters bean.

The properties of the weblogic.j2ee.descriptor.wl.JDBCConnectionPoolParamsBean entity are as follows:

JDBCXADebugLevel

Specifies level of JDBC debugging for XA drivers, where larger values in the range provide more debugging information.

Type: integer/int32

Constraints: Has Default Value: 10, Minimum Value: 0, Maximum Value: 100

connectionCreationRetryFrequencySeconds

The number of seconds between attempts to establish connections to the database.

If you do not set this value, data source creation fails if the database is unavailable. If set and if the database is unavailable when the data source is created, WebLogic Server will attempt to create connections in the pool again after the number of seconds you specify, and will continue to attempt to create the connections until it succeeds.

When set to 0, connection retry is disabled.

Type: integer/int32

Constraints: Has Default Value: 0, Minimum Value: 0, Maximum Value: 2147483647

connectionHarvestMaxCount

The maximum number of connections that may be harvested when the connection harvesting occurs. The range of valid values is 1 to MaxCapacity.

Type: integer/int32

Constraints: Has Default Value: 1, Minimum Value: 1

connectionHarvestTriggerCount

Specifies the number of available connections (trigger value) used to determine when connection harvesting occurs.

- Harvesting occurs when the number of available connections is below the trigger value for a connection pool.
- The range of valid values is -1 to `MaxCapacity`
- Default value is -1
- Setting the value to -1 disables connection harvesting.

Type: integer/int32

Constraints: Has Default Value: -1, Minimum Value: -1

connectionLabelingCallback

The class name of the connection labeling callback. This is automatically passed to `registerConnectionLabelingCallback` when the datasource is created. The class must implement `oracle.ucp.ConnectionLabelingCallback`

Type: string

connectionReserveTimeoutSeconds

The number of seconds after which a call to reserve a connection from the connection pool will timeout.

When set to , a call will never timeout.

When set to -1, a call will timeout immediately.

Type: integer/int32

Constraints: Has Default Value: 10, Minimum Value: -1, Maximum Value: 2147483647

countOfRefreshFailuresTillDisable

Specifies the number of reconnect failures allowed before WebLogic Server disables a connection pool to minimize the delay in handling the connection request caused by a database failure. Zero means it is disabled.

Type: integer/int32

Constraints: Has Default Value: 2, Minimum Value: 0

countOfTestFailuresTillFlush

Specifies the number of test failures allowed before WebLogic Server closes all unused connections in a connection pool to minimize the delay caused by further database testing. Zero means it is disabled.

Type: integer/int32

Constraints: Has Default Value: 2, Minimum Value: 0

credentialMappingEnabled

Enables Set Client ID on connection for the data source. When an application requests a database connection, WebLogic Server sets a light-weight client ID on the database connection.

By default, it uses the credential mapping to map WebLogic Server user IDs to database user IDs. However, if `use-database-credentials` is set to true, then the credential mapping is not done and the ID is used directly as a database user ID.

It is currently supported for IBM DB2 driver and Oracle thin driver. Support for this feature will be dropped in a future Oracle thin driver release. Oracle recommends using proxy authentication instead of this feature.

Type: boolean

Constraints: Has Default Value: false

driverInterceptor

Specifies the absolute name of the application class used to intercept method calls to the JDBC driver. The application specified must implement the `weblogic.jdbc.extensions.DriverInterceptor` interface.

Weblogic Server will invoke the `preInvokeCallback()`, `postInvokeExceptionCallback()`, and `postInvokeCallback()` methods of the registered application before and after invoking any method inside the JDBC driver. You can use this feature to profile JDBC driver usage and monitor:

- Methods being executed
- Any exceptions thrown
- Time spent inside the driver executing methods

Type: string

fatalErrorCodes

Specifies a comma-separated list of error codes that are treated as fatal errors. These errors include deployment errors that cause a server to fail to boot and connection errors that prevent a connection from being put back in the connection pool.

This optional attribute is used to define fatal error codes, that when specified as the exception code within a `SQLException` (retrieved by `SQLException.getErrorCode()`), indicate that a fatal error has occurred and the connection is no longer usable. For Oracle databases the following fatal error codes are predefined within WLS and do not need to be placed in the configuration file:

- 3113: "end-of-file on communication channel"
- 3114: "not connected to ORACLE"
- 1033: "ORACLE initialization or shutdown in progress"
- 1034: "ORACLE not available"
- 1089: "immediate shutdown in progress - no operations are permitted"
- 1090: "shutdown in progress - connection is not permitted"
- 17002: "I/O exception"

Type: string

highestNumWaiters

The maximum number of connection requests that can concurrently block threads while waiting to reserve a connection from the data source's connection pool.

Type: integer/int32

Constraints: Has Default Value: 2147483647, Minimum Value: 0, Maximum Value: 2147483647

identityBasedConnectionPoolingEnabled

Enables identity-based-connection-pooling for the data source. When an application requests a database connection, WebLogic Server picks or creates a physical connection

with requested DBMS identity based on a map of WebLogic user IDs and database IDs.

You must also specify the map of WebLogic Server user IDs to database user IDs (credential mapping).

Type: boolean

Constraints: Has Default Value: false

ignoreInUseConnectionsEnabled

Enables the data source to be shutdown even if connections obtained from the pool are still in use.

Type: boolean

Constraints: Has Default Value: true

inactiveConnectionTimeoutSeconds

The number of inactive seconds on a reserved connection before WebLogic Server reclaims the connection and releases it back into the connection pool.

You can use the Inactive Connection Timeout feature to reclaim leaked connections - connections that were not explicitly closed by the application. Note that this feature is not intended to be used in place of properly closing connections.

When set to , the feature is disabled.

Type: integer/int32

Constraints: Has Default Value: 0, Minimum Value: 0, Maximum Value: 2147483647

initSql

SQL statement to execute that will initialize newly created physical database connections. Start the statement with SQL followed by a space.

If the Init SQL value begins with "SQL ", then the rest of the string following that leading token will be taken as a literal SQL statement that will be used to initialize database connections. If the Init SQL value does not begin with "SQL ", the value will be treated as the name of a table and the following SQL statement will be used to initialize connections:

```
"select count(*) from InitSQL"
```

The table `InitSQL` must exist and be accessible to the database user for the connection. Most database servers optimize this SQL to avoid a table scan, but it is still a good idea to set `InitSQL` to the name of a table that is known to have few rows, or even no rows.

Type: string

initialCapacity

The number of physical connections to create when creating the connection pool in the data source. If unable to create this number of connections, creation of the data source will fail.

Type: integer/int32

Constraints: Has Default Value: 1, Minimum Value: 0, Maximum Value: 2147483647

loginDelaySeconds

The number of seconds to delay before creating each physical database connection.

This delay supports database servers that cannot handle multiple connection requests in rapid succession.

The delay takes place both during initial data source creation and during the lifetime of the data source whenever a physical database connection is created.

Type: integer/int32

Constraints: Has Default Value: 0, Minimum Value: 0, Maximum Value: 2147483647

maxCapacity

The maximum number of physical connections that this connection pool can contain.

Type: integer/int32

Constraints: Has Default Value: 15, Minimum Value: 1, Maximum Value: 2147483647

minCapacity

The minimum number of physical connections that this connection pool can contain after it is initialized.

- Default: InitialCapacity
- Used only for connection pool shrinking calculations.
- For compatibility, InitialCapacity is used if MinCapacity is not configured.
- Once a data source has gone through a suspend/resume, the larger value of either MinCapacity or InitialCapacity is used.

Type: integer/int32

Constraints: Has Default Value: 1, Minimum Value: 0, Maximum Value: 2147483647

pinnedToThread

Enables an option to improve performance by enabling execute threads to keep a pooled database connection even after the application closes the logical connection.

When enabled:

- WebLogic Server pins a database connection from the connection pool to an execution thread the first time an application uses the thread to reserve a connection. When the application finishes using the connection and calls `connection.close()`, WebLogic Server keeps the connection with the execute thread and does not return it to the connection pool. When an application subsequently requests a connection using the same execute thread, WebLogic Server provides the connection already reserved by the thread.
- There is no locking contention on the connection pool that occurs when multiple threads attempt to reserve a connection at the same time. There is no contention for threads that attempt to reserve the same connection from a limited number of database connections.
- If an application concurrently reserves more than one connection from the connection pool using the same execute thread, WebLogic Server creates additional database connections and pins them to the thread.
- The maximum capacity of the connection pool (maximum number of database connections created in the connection pool) becomes the number of execute threads used to request a connection multiplied by the number of concurrent connections each thread reserves. This may exceed the `Maximum Capacity` specified for the connection pool. You may need to consider this larger number of connections in your system design and ensure that your database allows for additional associated resources. If your system cannot handle the additional resource requirements or if you see database resource errors after enabling

PinnedToThread, Oracle recommends not using PinnedToThread. See Using Pinned-To-Thread Property to Increase Performance

Type: boolean

Constraints: Has Default Value: false

profileConnectionLeakTimeoutSeconds

The number of seconds that a JDBC connection needs to be held by an application before triggering a connection leak diagnostic profiling record.

When set to , the timeout is disabled. This attribute only applies when the connection leak diagnostic profiling option is enabled.

Type: integer/int32

Constraints: Has Default Value: 0, Minimum Value: 0, Maximum Value: 2147483647

profileHarvestFrequencySeconds

The number of seconds between when WebLogic Server harvests profile data.

When set to , harvesting of data is disabled.

Type: integer/int32

Constraints: Has Default Value: 300, Minimum Value: 0, Maximum Value: 2147483647

profileType

Specifies that type of profile data to be collected for the JDBC subsystem.

You can specify combinations of the following profile types:

- weblogic.jdbc.common.internal.JDBCConstants.PROFILE_TYPE_CONN_USAGE - Profile threads currently using connections from the pool of connections in the data source.
- weblogic.jdbc.common.internal.JDBCConstants.PROFILE_TYPE_CONN_RESV_WAIT - Profile threads currently waiting to reserve a connection from the data source.
- weblogic.jdbc.common.internal.JDBCConstants.PROFILE_TYPE_CONN_LEAK - Profile threads that have reserved a connection from the data source and the connection leaked (was not properly returned to the pool of connections).
- weblogic.jdbc.common.internal.JDBCConstants.PROFILE_TYPE_CONN_RESV_FAIL - Profile threads that attempt to reserve a connection from the data source but fail.
- weblogic.jdbc.common.internal.JDBCConstants.PROFILE_TYPE_STMT_CACHE_ENTRY - Profile prepared and callable statements added to the statement cache, and profile the threads that originated the cached statements.
- weblogic.jdbc.common.internal.JDBCConstants.PROFILE_TYPE_STMT_USAGE - Profile threads currently executing SQL statements from the statement cache.
- weblogic.jdbc.common.internal.JDBCConstants.PROFILE_TYPE_CONN_LAST_USAGE - Profile the previous thread that last used the connection. This information is useful when debugging problems with connections infected with pending transactions that cause subsequent XA operations on the connections to fail.
- weblogic.jdbc.common.internal.JDBCConstants.PROFILE_TYPE_CONN_MT_USAGE - Profile threads that erroneously use a connection previously obtained by a different thread.

- `weblogic.jdbc.common.internal.JDBCConstants.PROFILE_TYPE_CONN_UNWRAP_USAGE` - Profile threads that have obtained the JDBC delegate object by invoking `unwrap` or `weblogic.common.wrapper.Wrapper.getVendorObj`.
- `weblogic.jdbc.common.internal.JDBCConstants.PROFILE_TYPE_CONN_LOCALTX_LEAK` - Profile threads that close JDBC connections that have an active local database transaction.
- `weblogic.jdbc.common.internal.JDBCConstants.PROFILE_TYPE_NONE` - Disable profiling for the data source.
- `weblogic.jdbc.common.internal.JDBCConstants.PROFILE_TYPE_ALL` - Enable all profile types for the data source.

Type: integer/int32

Constraints: Has Default Value: 0

removeInfectedConnections

Specifies whether a connection will be removed from the connection pool after the application uses the underlying vendor connection object.

If you disable removing infected connections, you must make sure that the database connection is suitable for reuse by other applications.

When set to `true` (the default), the physical connection is not returned to the connection pool after the application closes the logical connection. Instead, the physical connection is closed and recreated.

When set to `false`, when the application closes the logical connection, the physical connection is returned to the connection pool and can be reused by the application or by another application.

Type: boolean

Constraints: Has Default Value: true

secondsToTrustAnIdlePoolConnection

The number of seconds within a connection use that WebLogic Server trusts that the connection is still viable and will skip the connection test, either before delivering it to an application or during the periodic connection testing process.

This option is an optimization that minimizes the performance impact of connection testing, especially during heavy traffic.

Type: integer/int32

Constraints: Has Default Value: 10, Minimum Value: 0, Maximum Value: 2147483647

shrinkFrequencySeconds

The number of seconds to wait before shrinking a connection pool that has incrementally increased to meet demand.

When set to `0`, shrinking is disabled.

Type: integer/int32

Constraints: Has Default Value: 900, Minimum Value: 0, Maximum Value: 2147483647

statementCacheSize

The number of prepared and callable statements stored in the cache. (This may increase server performance.)

WebLogic Server can reuse statements in the cache without reloading the statements, which can increase server performance. Each connection in the connection pool has its own cache of statements.

Setting the size of the statement cache to 0 turns off statement caching.

Type: integer/int32

Constraints: Has Default Value: 10, Minimum Value: 0, Maximum Value: 1024

statementCacheType

The algorithm used for maintaining the prepared statements stored in the statement cache.

Options are:

- LRU - when a new prepared or callable statement is used, the least recently used statement is replaced in the cache.
- FIXED - the first fixed number of prepared and callable statements are cached.

Type: string

Constraints: Has Default Value: LRU, Legal Values: LRU, FIXED

statementTimeout

The time after which a statement currently being executed will time out.

StatementTimeout relies on underlying JDBC driver support. WebLogic Server passes the time specified to the JDBC driver using the

`java.sql.Statement.setQueryTimeout()` method. If your JDBC driver does not support this method, it may throw an exception and the timeout value is ignored.

A value of -1 disables this feature.

A value of means that statements will not time out.

Type: integer/int32

Constraints: Has Default Value: -1, Minimum Value: -1, Maximum Value: 2147483647

testConnectionsOnReserve

Enables WebLogic Server to test a connection before giving it to a client. (Requires that you specify a Test Table Name.)

The test adds a small delay in serving the client's request for a connection from the pool, but ensures that the client receives a viable connection.

Type: boolean

Constraints: Has Default Value: false

testFrequencySeconds

The number of seconds a WebLogic Server instance waits between attempts when testing unused connections. (Requires that you specify a Test Table Name.)

Connections that fail the test are closed and reopened to re-establish a valid physical connection. If the test fails again, the connection is closed.

In the context of multi data sources, this attribute controls the frequency at which WebLogic Server checks the health of data sources it had previously marked as unhealthy.

When set to , the feature is disabled.

Type: integer/int32

Constraints: Has Default Value: 120, Minimum Value: 0, Maximum Value: 2147483647

testTableName

The name of the database table to use when testing physical database connections. This name is required when you specify a Test Frequency and enable Test Reserved Connections.

The default SQL code used to test a connection is `select count(*) from TestTableName`

Most database servers optimize this SQL to avoid a table scan, but it is still a good idea to set the Test Table Name to the name of a table that is known to have few rows, or even no rows.

If the Test Table Name begins with `SQL`, then the rest of the string following that leading token will be taken as a literal SQL statement that will be used to test connections instead of the standard query. For example: `SQL BEGIN; Null; END;`

For an Oracle database, you can reduce the overhead of connection testing by setting Test Table Name to `SQL PINGDATABASE` which uses the `pingDatabase()` method to test the Oracle connection. For any JDBC 4.0 database, it is possible to use "SQL ISVALID" to use the `isValid()` method on the connection.

Type: string

wrapJdbc

By default, SQL objects for `CallableStatement`, `PreparedStatement`, `ResultSet`, `Statement`, and `DatabaseMetaData` are wrapped with a WebLogic wrapper. Wrapping allows features like debugging and connection usage to be performed by the server.

When `false`, wrapping is disabled. This improves performance, in some cases significantly, and allows for the application to use the native driver objects directly. A value of `false` also disables data type wrapping.

Type: boolean

Constraints: Has Default Value: true

wrapTypes

By default, data type objects for `Array`, `Blob`, `Clob`, `NClob`, `Ref`, `SQLXML`, and `Struct`, plus `ParameterMetaData` and `ResultSetMetaData` objects are wrapped with a WebLogic wrapper. This allows for features like debugging and connection usage to be done by the server.

The wrapping can be turned off by setting this value to `false`. This improves performance, in some cases significantly, and allows for the application to use the native driver objects directly.

Type: boolean

Constraints: Has Default Value: true

weblogic.j2ee.descriptor.wl.JDBCDataSourceBean

The top of the JDBC data source bean tree.

JDBC data sources all have a `JDBCDataSourceBean` as their root bean (a bean with no parent). The schema namespace that corresponds to this bean is `"http://xmlns.oracle.com/weblogic/jdbc-data-source"`

The properties of the `weblogic.j2ee.descriptor.wl.JDBCDataSourceBean` entity are as follows:

datasourceType

The data source type. Valid types are:

- GENERIC - generic data source
- MDS - multi data source
- AGL - Active GridLink data source
- UCP - Universal Connection Pool data source
- PROXY - proxy for multiple tenant data sources

Type: string

Constraints: Legal Values: GENERIC, MDS, AGL, UCP, PROXY

id

Gets the Id value

Type: integer/int64

Constraints: Read Only

name

A unique name that identifies this data source in the WebLogic domain.

Type: string

version

Gets the "version" attribute

Type: string

weblogic.j2ee.descriptor.wl.JDBCDataSourceParamsBean

Contains the basic usage parameters of a data source.

Configuration parameters for the basic usage of a data source are specified using a data source parameters bean.

The properties of the weblogic.j2ee.descriptor.wl.JDBCDataSourceParamsBean entity are as follows:

JNDINames

The JNDI path for this Data Source. By default, the JNDI name is the name of the data source.

Applications that look up the JNDI path get a `javax.sql.DataSource` instance that corresponds to this data source.

Type: array of string

algorithmType

The algorithm determines the connection request processing for the multi data source.

You can specify one of the following algorithm types:

- **Failover**

Connection requests are sent to the first data source in the list; if the request fails, the request is sent to the next data source in the list, and so forth. The process is repeated until a valid connection is obtained, or until the end of the list is reached, in which case an exception is thrown.

- **Load balancing**

The multi data source distributes connection requests evenly to its member data sources. With this algorithm, the multi data source also provides failover processing. That is, if a request fails, the multi data source sends the request to the next data source in the list until a valid connection is obtained, or until the end of the list is reached, in which case an exception is thrown.

Type: string

Constraints: Has Default Value: Failover, Legal Values: Load-Balancing, Failover

connectionPoolFailoverCallbackHandler

The name of the application class to handle the callback sent when a multi data source is ready to failover or fail back connection requests to another data source within the multi data source.

The name must be the absolute name of an application class that implements the `weblogic.jdbc.extensions.ConnectionPoolFailoverCallback` interface.

Type: string

Constraints: Has Default Value: null

dataSourceList

The list of data sources to which the multi data source will route connection requests. The order of data sources in the list determines the failover order.

Type: string

Constraints: Has Default Value: null

failoverRequestIfBusy

For multi data sources with the `failover` algorithm, enables the multi data source to failover connection requests to the next data source if all connections in the current data source are in use.

Type: boolean

Constraints: Has Default Value: false

globalTransactionsProtocol

Determines the transaction protocol (global transaction processing behavior) for the data source. Options include:

- `TwoPhaseCommit` - Standard XA transaction processing. Requires an XA driver.
- `LoggingLastResource` - A performance enhancement for one non-XA resource.
- `EmulateTwoPhaseCommit` - Enables one non-XA resource to participate in a global transaction, but has some risk to data.
- `OnePhaseCommit` - One-phase XA transaction processing using a non-XA driver. This is the default setting.
- `None` - Support for local transactions only.

Type: string

Constraints: Has Default Value: `OnePhaseCommit`, Legal Values: `TwoPhaseCommit`, `LoggingLastResource`, `EmulateTwoPhaseCommit`, `OnePhaseCommit`, `None`

keepConnAfterGlobalTx

Enables WebLogic Server to keep the physical database connection associated with the logical connection when committing a global transaction instead releasing it and getting another physical connection when needed.

Setting this option to true may require additional connections to be configured on the database.

Use this setting to work around specific problems with JDBC XA drivers.

Type: boolean

Constraints: Has Default Value: false

proxySwitchingCallback

The name of the switching callback class for a Proxy data source.

This class implements the `weblogic.jdbc.extensions.DataSourceSwitchingCallback` interface.

Type: string

Constraints: Has Default Value: null

proxySwitchingProperties

Specifies the switching properties passed to the switching callback method for a Proxy data source.

Type: string

Constraints: Has Default Value: null

scope

Specifies the scoping of the data source.

You can specify one of the following scopes:

- **Global**

Specifies that the data source is bound in the cluster-wide JNDI tree with the JNDIName specified so that the data source is available for use to any JDBC client across the cluster.

This is the default setting.

- **Application**

Specifies that the data source is bound in the application's local namespace with the JNDIName specified so that the data source is available for use only by JDBC clients within the application. This can only be used for packaged datasources and is ignored for JDBC System resources.

Type: string

Constraints: Has Default Value: Global, Legal Values: Global, Application

weblogic.j2ee.descriptor.wl.JDBCDriverParamsBean

Contains the driver parameters of a data source.

Configuration parameters for the JDBC Driver used by a data source are specified using a driver parameters bean.

The properties of the `weblogic.j2ee.descriptor.wl.JDBCDriverParamsBean` entity are as follows:

driverName

The full package name of JDBC driver class used to create the physical database connections in the connection pool in the data source.

For example: `oracle.jdbc.OracleDriver`

The driver must be the name of a class that implements the `java.sql.Driver` interface. Check the driver documentation to find the full pathname.

Note that the driver class must be in the classpath of any server to which the data source is deployed.

Type: string

password

The password attribute passed to the JDBC driver when creating physical database connections.

The value is stored in an encrypted form in the descriptor file and when displayed in an administration console.

Type: string

Constraints: Encrypted

url

The URL of the database to connect to. The format of the URL varies by JDBC driver.

The URL is passed to the JDBC driver to create the physical database connections.

Type: string

usePasswordIndirection

Specifies whether the database credentials are to be obtained from the credential mapper using the "user" property as the key. When true, the credentials are obtained from the credential mapper. When false, the database user name and password are obtained from the "user" property and Password element, respectively.

Type: boolean

Constraints: Has Default Value: false

useXaDataSourceInterface

Specifies that WebLogic Server should use the XA interface of the JDBC driver.

If the JDBC driver class used to create database connections implements both XA and non-XA versions of a JDBC driver, you can set this attribute to indicate that WebLogic Server should treat the JDBC driver as an XA driver or as a non-XA driver.

Type: boolean

Constraints: Has Default Value: true

weblogic.j2ee.descriptor.wl.JDBCOracleParamsBean

Contains the Oracle database-related parameters of a data source.

Configuration parameters for a data source's Oracle-specific behavior are specified using a Oracle parameters bean.

The properties of the `weblogic.j2ee.descriptor.wl.JDBCOracleParamsBean` entity are as follows:

activeGridlink

Indicates a configured Active GridLink datasource. This attribute is set to `true` when using the console to create an Active GridLink datasource. It is ignored if `FanEnabled` is `true` or `OnsNodeList` is a non-null string.

Type: boolean

Constraints: Has Default Value: false

affinityPolicy

Specifies the affinity policy for the datasource.

Options include:

- Transaction: Transaction affinity
- Session: Web-session affinity
- Data: Data affinity

The default value is Session.

Type: string

Constraints: Has Default Value: Session, Legal Values: Transaction, Session, Data, None

connectionInitializationCallback

The name of the Connection Initialization Callback class.

This name is automatically passed to `registerConnectionInitializationCallback` when a data source is created. The class must implement `oracle.ucp.jdbc.ConnectionInitializationCallback`

Type: string

fanEnabled

Enables the data source to subscribe to and process Oracle FAN events.

This attribute is only applicable for RAC configurations that publish FAN notification events using the ONS protocol.

Type: boolean

Constraints: Has Default Value: false

onsNodeList

A comma-separated list of ONS daemon listen addresses and ports to which connect to for receiving ONS-based FAN events. It is required when connecting to Oracle 11g databases and optional when connecting to Oracle database releases 12c and higher.

Type: string

onsWalletFile

The location of the Oracle wallet file in which the SSL certificates are stored. Only required when the ONS client is configured to communicate with ONS daemons using SSL.

Type: string

onsWalletPassword

The wallet password attribute that is included as part of the ONS client configuration string. This attribute is only required when ONS is configured to use the SSL protocol.

The value is stored in an encrypted form in the descriptor file and when displayed in an administration console.

Type: string

Constraints: Encrypted

oracleEnableJavaNetFastPath

Deprecated.

Type: boolean

Constraints: Has Default Value: false

oracleOptimizeUtf8Conversion

Enables the Oracle JDBC optimize UTF-8 conversion option.

Type: boolean

oracleProxySession

Enables Oracle JDBC Proxy Authentication.

- Only applicable for the Oracle driver.
- Requires WebLogic Server user IDs are mapped to database user IDs using credential mapping.

Type: boolean

Constraints: Has Default Value: false

replayInitiationTimeout

The amount of time, in seconds, a data source allows for Application Continuity replay processing before timing out and ending a replay session context.

- When set to zero (0) seconds, replay processing (failover) is disabled, although begin/endRequest are still called. You can use this for collecting coverage and measuring performance.
- The default value is 3600 seconds.
- See `oracle.ucp.jdbc.ConnectionInitializationCallback`

Type: integer/int32

Constraints: Has Default Value: 3600, Minimum Value: 0, Maximum Value: 2147483647

useDatabaseCredentials

If enabled, Oracle database credentials are used in `getConnection` instead of application server credentials. The database credentials are used to get a proxy session without requiring any work in the credential mapper.

Type: boolean

Constraints: Has Default Value: false

weblogic.j2ee.descriptor.wl.JDBCPropertiesBean

Contains a list of JDBC properties.

This entity has no properties.

weblogic.j2ee.descriptor.wl.JDBCPropertyBean

Represents a specific JDBC property.

The properties of the weblogic.j2ee.descriptor.wl.JDBCPropertyBean entity are as follows:

encryptedValue

The plaintext value of the encrypted property value.

The value is stored in an encrypted form in the descriptor file and when displayed in an administration console.

`setEncryptedValue('string')` works in online WLST but not offline WLST. Use `setEncryptedValueEncrypted(encrypt('string'))` for online or offline WLST.

Type: string

Constraints: Encrypted

name

The name of the property. The name of each property must be unique in the list of properties.

Type: string

Constraints: Read Only

sysPropValue

The value of the property defined as a system property.

Type: string

value

The value of the property.

Type: string

weblogic.j2ee.descriptor.wl.JDBCXAParamsBean

Contains the XA-related parameters of a data source.

Configuration parameters for a data source's XA-related behavior are specified using a XA parameters bean.

The properties of the weblogic.j2ee.descriptor.wl.JDBCXAParamsBean entity are as follows:

keepLogicalConnOpenOnRelease

Enables WebLogic Server to keep the logical JDBC connection open for a global transaction when the physical XA connection is returned to the connection pool.

Select this option if the XA driver used to create database connections or the DBMS requires that a logical JDBC connection be kept open while transaction processing continues (although the physical XA connection can be returned to the connection pool).

Only applies to data sources that use an XA driver.

Use this setting to work around specific problems with JDBC XA drivers.

Type: boolean

Constraints: Has Default Value: false

keepXaConnTillTxComplete

Enables WebLogic Server to associate the same XA database connection from the connection pool with a global transaction until the transaction completes.

Only applies to connection pools that use an XA driver.

Use this setting to work around specific problems with JDBC XA drivers.

Type: boolean

Constraints: Has Default Value: true

needTxCtxOnClose

Specifies whether the XA driver requires a distributed transaction context when closing various JDBC objects (result sets, statements, connections, and so forth). Only applies to connection pools that use an XA driver.

When enabled, SQL exceptions that are thrown while closing the JDBC objects without a transaction context will be suppressed.

Use this setting to work around specific problems with JDBC XA drivers.

Type: boolean

Constraints: Has Default Value: false

newXaConnForCommit

Specifies that a dedicated XA connection is used for commit and rollback processing for a global transaction.

Only applies to data sources that use an XA driver.

Use this setting to work around specific problems with JDBC XA drivers.

Type: boolean

Constraints: Has Default Value: false

recoverOnlyOnce

Specifies that the transaction manager calls recover on the resource only once. Only applies to data sources that use an XA driver.

Use this setting to work around specific problems with JDBC XA drivers.

Type: boolean

Constraints: Has Default Value: false

resourceHealthMonitoring

Enables JTA resource health monitoring for an XA data source. When enabled, if an XA resource fails to respond to an XA call within the period specified in `MaxXACallMillis`, WebLogic Server marks the data source as unhealthy and blocks any further calls to the resource.

This property applies to XA data sources only, and is ignored for data sources that use a non-XA driver.

Type: boolean

Constraints: Has Default Value: true

xaRetryDurationSeconds

Determines the duration in seconds for which the transaction manager will perform recover operations on the resource. A value of zero indicates that no retries will be performed.

Type: integer/int32

Constraints: Has Default Value: 0

xaRetryIntervalSeconds

The number of seconds between XA retry operations if XARetryDurationSeconds is set to a positive value.

Type: integer/int32

Constraints: Has Default Value: 60

xaSetTransactionTimeout

Enables WebLogic Server to set a transaction branch timeout based on the value for XaTransactionTimeout.

When enabled, the WebLogic Server Transaction Manager calls `XAResource.setTransactionTimeout()` before calling `XAResource.start`, and passes either the XA Transaction Timeout value or the global transaction timeout.

You may want to set a transaction branch timeout if you have long-running transactions that exceed the default timeout value on the XA resource.

Note: To use this feature, the resource manager (typically, the JDBC driver) must support the `javax.transaction.xa.XAResource.setTransactionTimeout()` method.

Type: boolean

Constraints: Has Default Value: false

xaTransactionTimeout

The number of seconds to set as the transaction branch timeout.

If set, this value is passed as the transaction timeout value in the `XAResource.setTransactionTimeout()` call on the XA resource manager, typically the JDBC driver.

When this value is set to , the WebLogic Server Transaction Manager passes the global WebLogic Server transaction timeout in seconds in the method.

If set, this value should be greater than or equal to the global WebLogic Server transaction timeout.

Note: You must enable XaSetTransactionTimeout to enable setting the transaction branch timeout.

Type: integer/int32

Constraints: Has Default Value: 0

weblogic.j2ee.descriptor.wl.JMSBean

The top of the JMS module bean tree.

JMS modules all have a JMSBean as their root bean (a bean with no parent). The schema namespace that corresponds to this bean is "http://xmlns.oracle.com/weblogic/weblogic-jms"

The properties of the weblogic.j2ee.descriptor.wl.JMSBean entity are as follows:

notes

Optional information that you can include to describe this JMS module.

JMS module saves this note in the JMS descriptor file as XML PCDATA. All left angle brackets (<) are converted to the XML entity <. Carriage returns/line feeds are preserved.

Note:

If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

version

The version of this file.

Type: integer/int32

Constraints: Has Default Value: 1

weblogic.j2ee.descriptor.wl.JMSConnectionFactoryBean

Connection factories are used to create connections for JMS clients. Connection factories can configure properties of the connections returned to the JMS client.

The properties of the weblogic.j2ee.descriptor.wl.JMSConnectionFactoryBean entity are as follows:

JNDIName

The global JNDI name used to look up a connection factory within a clustered JNDI namespace.

In a clustered environment, this name is propagated to the entire cluster. If you want the JNDI name to be bound only on the local server, and not propagated to the rest of the cluster, then use the `Local JNDI Name` setting.

If not specified, then the connection factory is not bound into a clustered JNDI namespace.

Type: string

defaultTargetingEnabled

Specifies whether this JMS resource defaults to the parent module's targeting or uses the subdeployment targeting mechanism.

When set to true, this resource implicitly inherits the targeting of its parent module. When set to false, this resource gets targeted based its subdeployment's targets, if one is specified.

Type: boolean

Constraints: Has Default Value: false

id

Return the unique identifier of this bean instance.

Type: integer/int64

Constraints: Read Only

localJNDIName

The local JNDI name used to look up the connection factory within the JNDI namespace of the server where the connection factory is targeted. In a clustered environment, this name is bound only on the local server instance and is not propagated to the rest of the cluster.

If not specified, then the connection factory is not bound into the local JNDI namespace.

Type: string

name

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this named JMS descriptor bean.

JMS module saves this note in the JMS descriptor file as XML PCDATA. All left angle brackets (<) are converted to the XML entity <. Carriage returns/line feeds are preserved.

Note:

If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

subDeploymentName

Gets the name of the sub-deployment to use when targeting this entity

Entities are targeted using a sub-deployment with this name. The targets of the sub-deployment will be the targets of this entity.

Type: string

weblogic.j2ee.descriptor.wl.LoadBalancingParamsBean

The load-balancing parameters allow client to choose how they wish to distribute the work to the configured servers.

The properties of the weblogic.j2ee.descriptor.wl.LoadBalancingParamsBean entity are as follows:

loadBalancingEnabled

Specifies whether non-anonymous producers created through a connection factory are load balanced within a distributed destination on a per-call basis.

- If enabled, the associated message producers are load balanced on every `send()` or `publish()`
- If disabled, the associated message producers are load balanced on the first `send()` or `publish()`

Type: boolean

Constraints: Has Default Value: true

serverAffinityEnabled

Specifies whether a server instance that is load balancing consumers or producers across multiple members destinations of a distributed destination, will first attempt to load balance across any other physical destinations that are also running on the same server instance.

Type: boolean

Constraints: Has Default Value: true

weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean

These parameters control what should happen to messages logging. They allow the administrator to control logging.

The properties of the `weblogic.j2ee.descriptor.wl.MessageLoggingParamsBean` entity are as follows:

messageLoggingEnabled

Specifies whether the module logs information about the message life cycle.

Type: boolean

Constraints: Has Default Value: false

messageLoggingFormat

Defines which information about the message is logged.

Valid values are:

- **%header%** - All JMS header fields are logged.
- **%properties%** - All user-defined properties are logged.
- **JMSDeliveryTime** - This WebLogic JMS-specific extended header field is logged.
- **JMSRedeliveryLimit** - This WebLogic JMS-specific extended header field is logged.
- **foo** - Any valid JMS header field or user-defined property is logged.

When specifying multiple values, enter them as a comma-separated list. The `%header%` and `%properties%` values are *not* case sensitive. For example, you could use "`%header%, %properties%`" for all the JMS header fields and user properties. However, the enumeration of individual JMS header fields and user-defined properties are case sensitive. To enumerate only individual JMS header fields you could use "`%header, name, address, city, state, zip`"

Note: The `JMSMessageID` field is always logged and cannot be turned off. Therefore, if the Message Logging Format is not defined (i.e., null) or is defined as an empty string, then the output to the log file contains only the `JMSMessageID` of the message. Gets the `message-logging-format` element.

Type: string

Constraints: Has Default Value: null

templateBean

Finds the template bean for this destination.

Type: `weblogic.j2ee.descriptor.wl.TemplateBean` reference

Constraints: Read Only

weblogic.j2ee.descriptor.wl.MulticastParamsBean

Topics with certain quality of service allowances can receive a significant performance boost by using multicast to receive messages rather than using a connection oriented protocol like TCP. These parameters can be configured with the bean returned.

The properties of the `weblogic.j2ee.descriptor.wl.MulticastParamsBean` entity are as follows:

multicastAddress

The IP address that this topic uses to transmit messages to multicast consumers.

Type: string

Constraints: Has Default Value:

multicastPort

The IP port that this topic uses to transmit messages to multicast consumers.

Type: integer/int32

Constraints: Has Default Value: 6001, Minimum Value: 1, Maximum Value: 65535

multicastTimeToLive

The number of routers that a message traverses en route to a consumer. A value of 1 limits the message to one subnet (which prevents it from traversing any routers).

This value is independent of the JMSExpirationTime value.

Type: integer/int32

Constraints: Has Default Value: 1, Minimum Value: 0, Maximum Value: 255

templateBean

Finds the template bean for this destination.

Type: weblogic.j2ee.descriptor.wl.TemplateBean reference

Constraints: Read Only

weblogic.j2ee.descriptor.wl.PropertyBean

When interfacing with a remote naming context it may be necessary to set key/value properties. This bean represents a single key/value pairing.

The properties of the weblogic.j2ee.descriptor.wl.PropertyBean entity are as follows:

key

Gets the key of this bean

Type: string

Constraints: Read Only

value

Gets the value associated with this bean

Type: string

weblogic.j2ee.descriptor.wl.QueueBean

Queues are used for asynchronous peer communications. A message delivered to a queue will be distributed to one consumer. Several aspects of a queues behavior can be configured with a queue bean.

The properties of the weblogic.j2ee.descriptor.wl.QueueBean entity are as follows:

JMSCreateDestinationIdentifier

A reference name for a destination or a member of a distributed destination that provides a way to lookup that destination without JNDI using `javax.jms.Session.createQueue` or `createTopic`. See "How to Lookup a Destination" in *Programming JMS* for more information on how to use this attribute.

This name must be unique within the scope of the JMS server to which this destination is targeted. However, it does not need to be unique within the scope of an entire JMS module or WebLogic Cluster. For example, two queues can have the same destination name as long as those queues are targeted to different JMS servers.

Note: Since this name must be unique within the scope of a JMS server, verify whether other JMS modules may contain destination names that conflict with this name. It is the responsibility of the deployer to resolve the destination names targeted to JMS servers.

Type: string

Constraints: Has Default Value: null

JNDIName

The global JNDI name used to look up the destination within the JNDI namespace.

In a clustered environment, this name is propagated to the entire cluster. If you want the JNDI name to be bound only on the local server, and not propagated to the rest of the cluster, then use the `Local JNDI Name` parameter.

If not specified, the destination name will not be advertised through the global JNDI namespace.

Type: string

Constraints: Has Default Value: null

SAFEexportPolicy

Specifies whether a user can send messages to a destination using Store-and-Forward.

- **All** All users can send messages to this destination using Store-and-Forward.
- **None** Remote users can not send messages to a destination using Store-and-Forward.

This attribute is dynamically configurable. A dynamic change of this attribute will affect only messages sent after the update has been made.

Type: string

Constraints: Has Default Value: All, Legal Values: All, None

attachSender

Specifies whether messages landing on this destination should attach the credential of the sending user. You should consult the `JMSXUserID` documentation in *Programming WebLogic JMS* before using this feature.

- **Supports** The `JMSXUserID` property is set with the security principal of the sending user if requested. The sender can request its identity to be attached to its messages by using a connection factory with the `AttachJMSXUserID` security property enabled.
- **Never** The `JMSXUserID` property is never set with the security principal of the sending user no matter how the `AttachJMSXUserID` property is configured on connection factories.
- **Always** The `JMSXUserID` property is always set with the security principal of the sending user no matter how the `AttachJMSXUserID` property is configured on connection factories.

This attribute is dynamically configurable. A dynamic change of this attribute will affect only messages received after the update has been made.

Type: string

Constraints: Has Default Value: supports, Legal Values: supports, never, always

consumptionPausedAtStartup

Specifies whether consumption is paused on a destination at startup.

- **default** If a JMS template is specified, then this value inherits the template's Consumption Paused At Startup value. If no JMS template is configured for the destination, then the Default value is equivalent to **false**
- **false** Consumption Paused is explicitly disabled for this destination.
- **true** Consumption Paused is explicitly turned on for this destination.

Type: boolean

Constraints: Has Default Value: false

defaultTargetingEnabled

Specifies whether this JMS resource defaults to the parent module's targeting or uses the subdeployment targeting mechanism.

When set to true, this resource implicitly inherits the targeting of its parent module. When set to false, this resource gets targeted based its subdeployment's targets, if one is specified.

Type: boolean

Constraints: Has Default Value: false

defaultUnitOfOrder

Specifies whether WebLogic Server creates a system-generated unit-of-order name based on the domain, JMS server, and destination name. Any message arriving at this destination that does not already belong to a unit-of-order is assigned this default name.

This field is recommended for advanced use. Generally, it is recommended to set a message unit-of-order using application calls or connection factory configuration. When relying on a destination default unit order to enforce ordering with a distributed destination, the application must be aware that unit-of-order routing doesn't apply. Instead the application must specifically ensure that any particular set of messages that must be processed in order are all sent to the same specific member destination even in the event of process failures or service migration.

Type: boolean

Constraints: Has Default Value: false

destinationKeys

The list of potential destination keys for sorting the messages that arrive on a JMS destination.

The keys are ordered from most significant to least significant. If more than one key is specified, a key based on the JMSMessageID can only be the last key in the list.

Note: If JMSMessageID is not defined in the key, it is implicitly assumed to be the last key and is set as "Ascending" (FIFO) for the sort order.

Type: array of string

forwardDelay

The number of seconds after which a uniform distributed queue member with no consumers will wait before forwarding its messages to other uniform distributed queue members that do have consumers.

The default value of -1 disables this feature so that no messages are forwarded to other uniform distributed queue members.

Note: This attribute is ignored by standalone/singleton Queues, it only applies to distributed queues.

Type: integer/int32

Constraints: Has Secure Value: -1, Has Default Value: -1

id

Return the unique identifier of this bean instance.

Type: integer/int64

Constraints: Read Only

incompleteWorkExpirationTime

Specifies the maximum length of time, in milliseconds, before undelivered messages in an incomplete UOW are expired. Such messages will then follow the expiration policy defined for undeliverable messages.

Note: An error destination for UOW messages cannot be configured with a Unit-of-Work Handling Policy of **Single Message Delivery** value.

This attribute is effective only if the Unit-of-Work Handling Policy is set to **Single Message Delivery** value. A value of -1 means that UOW messages will never expire.

Type: integer/int32

Constraints: Has Default Value: -1

insertionPausedAtStartup

Specifies whether new message insertion is paused on a destination at startup.

- **default** If a JMS template is specified, then this value inherits the template's Insertion Paused At Startup value. If no JMS template is configured for the destination, then the Default value is equivalent to **false**
- **false** Insertion Paused is explicitly disabled for this destination.
- **true** Insertion Paused is explicitly turned on for this destination.

Type: boolean

Constraints: Has Default Value: false

loadBalancingPolicy

Determines how messages are distributed to the members of this destination.

Choose from the following distribution techniques:

- **Round-Robin** The system maintains an ordering of physical topic members within the set by distributing the messaging load across the topic members one at a time in the order that they are defined in the configuration file. Each WebLogic Server instance maintains an identical ordering, but may be at a different point within the ordering. If weights are assigned to any of the topic members in the set, then those members appear multiple times in the ordering.

- Random** The weight assigned to the topic members is used to compute a weighted distribution for the members of the set. The messaging load is distributed across the topic members by pseudo-randomly accessing the distribution. In the short run, the load will not be directly proportional to the weight. In the long run, the distribution will approach the limit of the distribution. A pure random distribution can be achieved by setting all the weights to the same value, which is typically set to 1.

Note: This attribute is ignored by standalone/singleton Queues and Topics, it only applies to distributed destinations.

Type: string

Constraints: Has Default Value: Round-Robin, Legal Values: Round-Robin, Random

localJNDIName

The local JNDI name used to look up the destination within the JNDI namespace of the server where the destination resource is targeted. In a clustered environment, this name is bound only on the local server instance and is not propagated to the rest of the cluster.

A destination can have both a local JNDI name and a (global) JNDI name.

Type: string

Constraints: Has Default Value: null

maximumMessageSize

The maximum size of a message that is accepted from producers on this destination.

The message size includes the message body, any user-defined properties, and the user-defined JMS header fields: `JMSCorrelationID` and `JMSType`. Producers sending messages that exceed the configured maximum message size for the destination receive a `ResourceAllocationException`

The maximum message size is only enforced for the initial production of a message. Messages that are redirected to an error destination or forwarded to a member of a distributed destination are not checked for size. For instance, if a destination and its corresponding error destination are configured with a maximum message size of 128K bytes and 64K bytes, respectively, a message of 96K bytes could be redirected to the error destination (even though it exceeds the 64K byte maximum), but a producer could not directly send the 96K byte message to the error destination.

This attribute is dynamically configurable, but only incoming messages are impacted; stored messages are not impacted.

Type: integer/int32

Constraints: Has Default Value: 2147483647, Minimum Value: 0, Maximum Value: 2147483647

messagingPerformancePreference

Controls how long destinations are willing to wait to create full batches of available messages (if at all) for delivery to consumers. At the minimum value, batching is disabled; at the default value, less-than-full batches will not wait and are delivered immediately with currently available messages; tuning higher than the default value controls the maximum wait time for additional messages before less-than-full batches are delivered to consumers.

The maximum message count of a full batch is controlled by the JMS connection factory's Messages Maximum setting.

Type: integer/int32

Constraints: Has Default Value: 25, Minimum Value: 0, Maximum Value: 100

name

The name of this entity, represented in XML as an attribute.

Many of the elements within the JMS module are named entities. All of the named entities encased by a type in the XML file must be unique. This is the identifier used to delineate a particular entity within the JMS module.

This attribute cannot be modified externally from the module (for example, with a deployment plan) because it may be used inside the module referentially.

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this named JMS descriptor bean.

JMS module saves this note in the JMS descriptor file as XML PCDATA. All left angle brackets (<) are converted to the XML entity <. Carriage returns/line feeds are preserved.

Note:

If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

productionPausedAtStartup

Specifies whether new message production is paused on a destination at startup.

- **default** If a JMS template is specified, then this value inherits the template's Production Paused At Startup value. If no JMS template is configured for the destination, then the Default value is equivalent to **false**
- **false** Production Paused is explicitly disabled for this destination.
- **true** Production Paused is explicitly turned on for this destination.

Type: boolean

Constraints: Has Default Value: false

quota

A Quota controls the allotment of system resources available to destinations. For example, the number of bytes a destination is allowed to store can be configured with a Quota.

Type: weblogic.j2ee.descriptor.wl.QuotaBean reference

resetDeliveryCountOnForward

Determines whether or not the delivery count is reset during message forwarding between distributed queue members.

The default value of true resets the delivery counts on messages when they are forwarded to another distributed queue member.

Note: This attribute is ignored by standalone/singleton Queues, it only applies to distributed queues.

Type: boolean

Constraints: Has Default Value: true

subDeploymentName

Gets the name of the sub-deployment to use when targeting this entity

Entities are targeted using a sub-deployment with this name. The targets of the sub-deployment will be the targets of this entity.

Type: string

template

The JMS template from which the destination is derived. A template provides an efficient means of defining multiple destinations with similar configuration values.

If a JMS template is specified, destination parameters that are set to their default values will instead inherit their values from the JMS template at run-time. However, if a JMS template is not defined, then the configuration values for the destination must be specified as part of the destination.

Although you can dynamically modify the configuration of a JMS template, the configuration values on a destination are static.

Type: weblogic.j2ee.descriptor.wl.TemplateBean reference

Constraints: Restart Required

unitOfOrderRouting

Determines how a distributed destination member is selected as the destination for a message that is part of a unit-of-order. **Hash**, indicates that a message producer computes the member destination from the `hashCode` of the unit-of-order. **PathService** indicates that the configured Path Service determines the member destination.

Unit-of-Order Routing can be set programmatically with `WLProducer`, or administratively on the connection factory or destination.

Unit of Order Routing is not dynamically configurable.

Note: This attribute is ignored by standalone/singleton Queues and Topics, it only applies to distributed destinations.

Type: string

Constraints: Has Default Value: Hash

unitOfWorkHandlingPolicy

Specifies whether the Unit-of-Work (UOW) feature is enabled for this destination. A UOW is a set of messages that are processed as a single unit.

- **Pass-Through** By default, this destination does not treat messages as part of a UOW.
- **Single Message Delivery** This value should only be selected if UOW consumers are receiving messages on this destination. When selected, UOW messages are formed into a list and are consumed as an `ObjectMessage` containing the list.

Type: string

Constraints: Has Default Value: PassThrough, Legal Values: PassThrough, SingleMessageDelivery

weblogic.j2ee.descriptor.wl.QuotaBean

Quota beans control the allotment of system resources available to destinations. For example, the number of bytes a destination is allowed to store can be configured with a QuotaBean.

The properties of the weblogic.j2ee.descriptor.wl.QuotaBean entity are as follows:

bytesMaximum

The total number of bytes that can be stored in a destination that uses this quota.

A value of zero means that no messages can be placed on a destination without exceeding the quota. A value of -1 prevents WebLogic Server from imposing a limit.

Because excessive bytes volume can cause memory saturation, Oracle recommends that the maximum corresponds to the amount of system memory that is available after accounting for the rest of your application load.

No consideration is given to messages that are pending; that is, messages that are in-flight, delayed, or otherwise inhibited from delivery still count against the message and/or bytes quota.

.

This attribute is dynamic and can be changed at any time. If the quota is lowered and the quota object is now over quota, then subsequent requests for quota will be denied until quota is available. If the quota is raised, then this may allow the quota object to satisfy existing requests for quota.

Note: If a JMS template is used for distributed destination members, then this maximum applies only to those specific members and not the distributed destination set as a whole.

Type: integer/int64

Constraints: Has Default Value: 9223372036854775807, Minimum Value: -1, Maximum Value: 9223372036854775807

id

Return the unique identifier of this bean instance.

Type: integer/int64

Constraints: Read Only

messagesMaximum

The total number of messages that can be stored in a destination that uses this quota.

A value of zero means that no messages can be placed on a destination without exceeding the quota. A value of -1 prevents WebLogic Server from imposing a limit.

Because excessive bytes volume can cause memory saturation, Oracle recommends that the maximum corresponds to the amount of system memory that is available after accounting for the rest of your application load.

No consideration is given to messages that are pending; that is, messages that are in-flight, delayed, or otherwise inhibited from delivery still count against the message and/or bytes quota.

.

This attribute is dynamic and can be changed at any time. If the quota is lowered and the quota object is now over quota, then subsequent requests for quota will be denied

until quota is available. If the quota is raised, then this may allow the quota object to satisfy existing requests for quota.

Note: If a JMS template is used for distributed destination members, then this maximum applies only to those specific members and not the distributed destination set as a whole.

Type: integer/int64

Constraints: Has Default Value: 9223372036854775807, Minimum Value: -1, Maximum Value: 9223372036854775807

name

The name of this entity, represented in XML as an attribute.

Many of the elements within the JMS module are named entities. All of the named entities encased by a type in the XML file must be unique. This is the identifier used to delineate a particular entity within the JMS module.

This attribute cannot be modified externally from the module (for example, with a deployment plan) because it may be used inside the module referentially.

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this named JMS descriptor bean.

JMS module saves this note in the JMS descriptor file as XML PCDATA. All left angle brackets (<) are converted to the XML entity <. Carriage returns/line feeds are preserved.

Note:

If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

policy

For destinations that use this quota, this policy determines whether to deliver smaller messages before larger ones when a destination has exceeded its message quota.

FIFO (first-in, first-out) indicates that requests for quota are submitted in the order they are received. If a given request for quota cannot be satisfied, and the client requesting the quota is willing to wait, then that request will block all other requests for quota until the request is satisfied or times out. This prevents smaller messages from being delivered when larger requests are already waiting for space.

Preemptive indicates that subsequent requests can preempt previously unsatisfied requests. That is, if there is sufficient quota for the current request, then that space is used even if there are other requests waiting for quota. When quota is limited, the Preemptive policy can result in the starvation of larger requests.

Type: string

Constraints: Has Default Value: FIFO, Legal Values: FIFO, Preemptive

shared

Indicates whether this quota is shared by multiple destinations that refer to it.

If Shared is enabled (the default), all destinations referring to the quota object compete for resources the resources defined by that object. If one destination consumes a large

number of messages or bytes, then this will prevent other destinations from obtaining quota.

If `Shared` is disabled, the quota object behaves as a template. Each destination referring to the quota object gets its own internal instance of the object for tracking quota.

Destinations within the same JMS module may share quotas in any way they want. However, quota sharing only takes place for destinations within the same JMS server. In other words, if destinations `and` both share the same quota, and the quota has `Shared` enabled, then `and` will only share quota if both are deployed to the same JMS server.

Type: boolean

Constraints: Has Default Value: true

weblogic.j2ee.descriptor.wl.SAFErrorHandlingBean

Store-and-Forward (SAF) Error Handling defines the action to be taken when the delivery of a JMS message fails to be forwarded to a remote destination.

The properties of the `weblogic.j2ee.descriptor.wl.SAFErrorHandlingBean` entity are as follows:

SAFErrorDestination

Specifies the error destination when `Policy` is set to `Redirect`

Any change to this parameter affects only incoming messages; stored messages are not affected.

Type: `weblogic.j2ee.descriptor.wl.SAFDestinationBean` reference

Constraints: Restart Required

id

Return the unique identifier of this bean instance.

Type: integer/int64

Constraints: Read Only

logFormat

Specifies how information is logged when `Message Handling Policy` is set to `Log`

Any change to this parameter affects only incoming messages; stored messages are not affected.

The valid values are:

- `%header%` - All JMS header fields are logged.
- `%properties%` - All user-defined properties are logged.
- `JMSDeliveryTime` - This WebLogic JMS-specific extended header field is logged.
- `JMSRedeliveryLimit` - This WebLogic JMS-specific extended header field is logged.
- `foo` - Any valid JMS header field or user-defined property is logged.

When specifying multiple values, enter them as a comma-separated list. The `%header%` and `%properties%` values are *not* case sensitive. For example, you could use `"%header%, %properties%"` for all the JMS header fields and user properties. However, the enumeration of individual JMS header fields and user-defined properties are case

sensitive. To enumerate only individual JMS header fields you could use "%header, name, address, city, state, zip"

Note: The `JMSMessageID` field is always logged and cannot be turned off. Therefore, if the Log Format is not defined (i.e., null) or is defined as an empty string, then the output to the log file contains only the `JMSMessageID` of the message.

Type: string

name

The name of this entity, represented in XML as an attribute.

Many of the elements within the JMS module are named entities. All of the named entities encased by a type in the XML file must be unique. This is the identifier used to delineate a particular entity within the JMS module.

This attribute cannot be modified externally from the module (for example, with a deployment plan) because it may be used inside the module referentially.

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this named JMS descriptor bean.

JMS module saves this note in the JMS descriptor file as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note:

If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

policy

The error handling policy for this SAF error handling resource.

- Discard - By default, expired messages are simply removed from the system. The removal is not logged and the message is not redirected to another location.
- Log - Removes expired messages and writes an entry to the server log file indicating that the messages were removed from the system. You define the actual information that will be logged in the Log Format field.
- Redirect - Moves expired messages from their current location into the Error Destination defined for imported SAF destinations.
- Always-Forward - Ignores the SAF Default Time-to-Live value set on the imported destination and the expiration time set on the message, and so forwards the message to a remote destination even after it has expired.

Any change to this parameter affects only incoming messages; stored messages are not affected.

Type: string

Constraints: Has Default Value: Discard, Legal Values: Discard, Log, Redirect, Always-Forward, Legal Null: true

weblogic.j2ee.descriptor.wl.SAFImportedDestinationsBean

Store-and-Forward (SAF) Imported Destinations is a collection of a SAF queues and topics that reside in a different cluster or server. These sets of SAF queues and topics refer to the same SAF Remote Context. They can also share the same JNDI prefix, Time-To-Live default, and SAF Error Handling name.

The properties of the weblogic.j2ee.descriptor.wl.SAFImportedDestinationsBean entity are as follows:

JNDIPrefix

Specifies the string that will prefix the local JNDI name of a remote destination.

Any change to this prefix affects only incoming messages; stored messages are not affected.

Type: string

SAFErrorHandling

Specifies the error handling configuration used for the imported destinations.

Any change to this parameter affects only incoming messages; stored messages are not affected.

Type: weblogic.j2ee.descriptor.wl.SAFErrorHandlingBean reference

Constraints: Restart Required

SAFRemoteContext

Specifies the remote context used for the imported destinations.

Changing the remote context name affects both stored messages and incoming messages.

Type: weblogic.j2ee.descriptor.wl.SAFRemoteContextBean reference

defaultTargetingEnabled

Specifies whether this JMS resource defaults to the parent module's targeting or uses the subdeployment targeting mechanism.

When set to true, this resource implicitly inherits the targeting of its parent module. When set to false, this resource gets targeted based its subdeployment's targets, if one is specified.

Type: boolean

Constraints: Has Default Value: false

id

Return the unique identifier of this bean instance.

Type: integer/int64

Constraints: Read Only

name

The name of this entity, represented in XML as an attribute.

Many of the elements within the JMS module are named entities. All of the named entities encased by a type in the XML file must be unique. This is the identifier used to delineate a particular entity within the JMS module.

This attribute cannot be modified externally from the module (for example, with a deployment plan) because it may be used inside the module referentially.

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this named JMS descriptor bean.

JMS module saves this note in the JMS descriptor file as XML PCDATA. All left angle brackets (<) are converted to the XML entity <. Carriage returns/line feeds are preserved.

Note:

If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

subDeploymentName

Gets the name of the sub-deployment to use when targeting this entity

Entities are targeted using a sub-deployment with this name. The targets of the sub-deployment will be the targets of this entity.

Type: string

timeToLiveDefault

Specifies the default Time-to-Live value (expiration time), in milliseconds, for imported JMS messages. The expiration time set on JMS messages will override this value unless the `SAF Default Time-to-Live Enabled` field is switched on, which then overrides the expiration time in JMS messages on imported destinations.

Any change to this value affects only incoming messages; stored messages are not affected.

Type: integer/int64

Constraints: Has Default Value: 3600000, Minimum Value: -1

unitOfOrderRouting

Specifies the type of routing used to find a SAF agent when using the message Unit-of-Order feature.

- Hash indicates that message producers use the hash code of a message Unit-of-Order to find a SAF agent.
- PathService indicates that message producers use the Path Service to find a SAF agent.

Type: string

Constraints: Has Default Value: Hash, Legal Values: Hash, PathService

useSAFTimeToLiveDefault

Controls whether the Time-to-Live (expiration time) value set on imported JMS messages will be overridden by the value specified in the `SAF Default Time-to-Live` field.

Any change to this parameter affects only incoming messages; stored messages are not affected.

Type: boolean

Constraints: Has Default Value: false

weblogic.j2ee.descriptor.wl.SAFLoginContextBean

Store-and-Forward (SAF) Login Context specifies the remote URL and user credentials needed to log into and get authenticated and authorized in a remote cluster or server.

The properties of the weblogic.j2ee.descriptor.wl.SAFLoginContextBean entity are as follows:

loginURL

Specifies the URL to connect to when using this SAF Login Context.

SAFImportedDestinations are associated with a SAFRemoteContext that has a SAFLoginContext. This SAFLoginContext defines the URL to connect to.

Type: string

password

The password for the username used to log into the remote URL.

When Password is specified for a SAFLoginContext, then SAFPrincipalName is not specified.

Type: string

Constraints: Encrypted, Legal Null: true

username

The name used to log into the remote URL.

When Username is specified for a SAFLoginContext, then SAFPrincipalName is not specified.

Type: string

Constraints: Legal Null: true

weblogic.j2ee.descriptor.wl.SAFQueueBean

Store-and-Forward (SAF) queues are used for asynchronous and disconnected peer communications. A message delivered to a SAF queue will be forwarded to a remote JMS queue. Several aspects of a SAF queue's behavior can be configured with a SAF Destination bean.

The properties of the weblogic.j2ee.descriptor.wl.SAFQueueBean entity are as follows:

SAFErrorHandling

Specifies the error handling configuration used by this SAF destination.

Any change to this parameter affects only incoming messages; stored messages are not affected.

Type: weblogic.j2ee.descriptor.wl.SAFErrorHandlingBean reference

Constraints: Restart Required

id

Return the unique identifier of this bean instance.

Type: integer/int64

Constraints: Read Only

localJNDIName

The local JNDI name of the remote destination.

Type: string

name

The name of this entity, represented in XML as an attribute.

Many of the elements within the JMS module are named entities. All of the named entities encased by a type in the XML file must be unique. This is the identifier used to delineate a particular entity within the JMS module.

This attribute cannot be modified externally from the module (for example, with a deployment plan) because it may be used inside the module referentially.

Type: string

Constraints: Read Only, Legal Null: true

nonPersistentQos

Specifies the quality-of-service for non-persistent messages.

- `Exactly-Once` indicates that messages will be forwarded to the remote side once and only once except for any occurrence of server crashes.
- `At-Least-Once` indicates that messages will be forwarded to the remote side at least once. No message will be lost except for any occurrence of server crashes. However, messages may appear in the remote endpoint more than once.
- `At-Most-Once` indicates that messages will be forwarded to the remote side at most once. No message will appear in the remote endpoint more than once. However, messages may get lost.

Any change to this parameter affects only incoming messages; stored messages are not affected.

Type: string

Constraints: Has Default Value: `At-Least-Once`, Legal Values: `At-Most-Once`, `At-Least-Once`, `Exactly-Once`, Legal Null: true

notes

Optional information that you can include to describe this named JMS descriptor bean.

JMS module saves this note in the JMS descriptor file as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note:

If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

persistentQos

Specifies the quality-of-service for persistent messages.

- `Exactly-Once` indicates that messages will be forwarded to the remote side once and only once
- `At-Least-Once` indicates that messages will be forwarded to the remote side at least once. Messages may appear in the remote endpoint more than once.
- `At-Most-Once` indicates that messages will be forwarded to the remote side at most once. No message will appear in the remote endpoint more than once. However, messages may get lost.

Any change to this parameter affects only incoming messages; stored messages are not affected.

Type: string

Constraints: Has Default Value: Exactly-Once, Legal Values: At-Most-Once, At-Least-Once, Exactly-Once, Legal Null: true

remoteJNDIName

The remote JNDI name of the remote destination.

Type: string

timeToLiveDefault

Specifies the default Time-to-Live value (expiration time), in milliseconds, for imported JMS messages. The expiration time set on JMS messages will override this value unless the `SAF Default Time-to-Live Enabled` field is switched on, which then overrides the expiration time in JMS messages on imported destinations.

Any change to this value affects only incoming messages; stored messages are not affected.

Type: integer/int64

Constraints: Minimum Value: -1

unitOfOrderRouting

Specifies the type of routing used to find a SAF agent when using the message Unit-of-Order feature.

- `Hash` indicates that producers use the hash code of a message Unit-of-Order to find a SAF agent.
- `PathService` indicates that producers use the Path Service to find a SAF agent.

Type: string

Constraints: Legal Values: Hash, PathService, Legal Null: true

useSAFTimeToLiveDefault

Controls whether the Time-to-Live (expiration time) value set on imported JMS messages will be overridden by the value specified in the `SAF Default Time-to-Live` field.

Any change to this parameter affects only incoming messages; stored messages are not affected.

Type: boolean

weblogic.j2ee.descriptor.wl.SAFRemoteContextBean

Store-and-Forward (SAF) Remote Context specifies the SAF Login Context that the SAF Imported Queue or Topic use to connect to the remote Destination. SAF Remote Context also specifies the SAF Remote Context configured in the remote cluster or server that is used by the producer of the reply-to JMS Destination specified in the message sent to a SAF Imported Destination.

The properties of the `weblogic.j2ee.descriptor.wl.SAFRemoteContextBean` entity are as follows:

compressionThreshold

The number of bytes for a serialized message body so that any message that exceeds this limit triggers message compression when the message is about to be sent across a SAF agent's JVM boundary.

The compression will occur on the sending-side SAF agent's JVM if the message body size exceeds the threshold limit.

Type: integer/int32

Constraints: Has Default Value: 2147483647, Minimum Value: 0, Maximum Value: 2147483647

id

Return the unique identifier of this bean instance.

Type: integer/int64

Constraints: Read Only

name

The name of this entity, represented in XML as an attribute.

Many of the elements within the JMS module are named entities. All of the named entities encased by a type in the XML file must be unique. This is the identifier used to delineate a particular entity within the JMS module.

This attribute cannot be modified externally from the module (for example, with a deployment plan) because it may be used inside the module referentially.

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this named JMS descriptor bean.

JMS module saves this note in the JMS descriptor file as XML PCDATA. All left angle brackets (<) are converted to the XML entity <. Carriage returns/line feeds are preserved.

Note:

If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

replyToSAFRemoteContextName

Specifies the SAF Remote Context Name used by the replyTo destination in the remote cluster or server.

Type: string

weblogic.j2ee.descriptor.wl.SAFTopicBean

Store-and-Forward (SAF) topics are used for asynchronous and disconnected peer communications. A message delivered to a SAF topic will be forwarded to a remote JMS topic. Several aspects of a SAF topic's behavior can be configured with a SAFDestination bean.

The properties of the weblogic.j2ee.descriptor.wl.SAFTopicBean entity are as follows:

SAFErrorHandling

Specifies the error handling configuration used by this SAF destination.

Any change to this parameter affects only incoming messages; stored messages are not affected.

Type: weblogic.j2ee.descriptor.wl.SAFErrorHandlingBean reference

Constraints: Restart Required

id

Return the unique identifier of this bean instance.

Type: integer/int64

Constraints: Read Only

localJNDIName

The local JNDI name of the remote destination.

Type: string

name

The name of this entity, represented in XML as an attribute.

Many of the elements within the JMS module are named entities. All of the named entities encased by a type in the XML file must be unique. This is the identifier used to delineate a particular entity within the JMS module.

This attribute cannot be modified externally from the module (for example, with a deployment plan) because it may be used inside the module referentially.

Type: string

Constraints: Read Only, Legal Null: true

nonPersistentQos

Specifies the quality-of-service for non-persistent messages.

- **Exactly-Once** indicates that messages will be forwarded to the remote side once and only once except for any occurrence of server crashes.
- **At-Least-Once** indicates that messages will be forwarded to the remote side at least once. No message will be lost except for any occurrence of server crashes. However, messages may appear in the remote endpoint more than once.
- **At-Most-Once** indicates that messages will be forwarded to the remote side at most once. No message will appear in the remote endpoint more than once. However, messages may get lost.

Any change to this parameter affects only incoming messages; stored messages are not affected.

Type: string

Constraints: Has Default Value: At-Least-Once, Legal Values: At-Most-Once, At-Least-Once, Exactly-Once, Legal Null: true

notes

Optional information that you can include to describe this named JMS descriptor bean.

JMS module saves this note in the JMS descriptor file as XML PCDATA. All left angle brackets (<) are converted to the XML entity <. Carriage returns/line feeds are preserved.

Note:

If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

persistentQos

Specifies the quality-of-service for persistent messages.

- `Exactly-Once` indicates that messages will be forwarded to the remote side once and only once
- `At-Least-Once` indicates that messages will be forwarded to the remote side at least once. Messages may appear in the remote endpoint more than once.
- `At-Most-Once` indicates that messages will be forwarded to the remote side at most once. No message will appear in the remote endpoint more than once. However, messages may get lost.

Any change to this parameter affects only incoming messages; stored messages are not affected.

Type: string

Constraints: Has Default Value: `Exactly-Once`, Legal Values: `At-Most-Once`, `At-Least-Once`, `Exactly-Once`, Legal Null: true

remoteJNDIName

The remote JNDI name of the remote destination.

Type: string

timeToLiveDefault

Specifies the default Time-to-Live value (expiration time), in milliseconds, for imported JMS messages. The expiration time set on JMS messages will override this value unless the `SAF Default Time-to-Live Enabled` field is switched on, which then overrides the expiration time in JMS messages on imported destinations.

Any change to this value affects only incoming messages; stored messages are not affected.

Type: integer/int64

Constraints: Minimum Value: -1

unitOfOrderRouting

Specifies the type of routing used to find a SAF agent when using the message Unit-of-Order feature.

- `Hash` indicates that producers use the hash code of a message Unit-of-Order to find a SAF agent.
- `PathService` indicates that producers use the Path Service to find a SAF agent.

Type: string

Constraints: Legal Values: `Hash`, `PathService`, Legal Null: true

useSAFTimeToLiveDefault

Controls whether the Time-to-Live (expiration time) value set on imported JMS messages will be overridden by the value specified in the `SAF Default Time-to-Live` field.

Any change to this parameter affects only incoming messages; stored messages are not affected.

Type: boolean

weblogic.j2ee.descriptor.wl.SecurityParamsBean

Some clients may wish to customize the security information associated with them. They can use the security parameters bean to do so.

The properties of the weblogic.j2ee.descriptor.wl.SecurityParamsBean entity are as follows:

attachJMSXUserId

Specifies whether WebLogic Server attaches the authenticated user name to sent messages.

If enabled, the system will attach the authenticated username onto sent messages if the destination supports this behavior. The username is placed in the JMSXUserID user property. You should consult the JMSXUserID documentation in *Programming WebLogic JMS* before using this feature.

When dynamically changed this will affect all connections made using this connection factory after the change was made.

Type: boolean

Constraints: Has Default Value: false

weblogic.j2ee.descriptor.wl.TemplateBean

Template beans contain default values for destination attributes. If a destination defines a template and does not explicitly set the value of an attribute, then that attribute will take its value from the defined template.

The properties of the weblogic.j2ee.descriptor.wl.TemplateBean entity are as follows:

attachSender

Specifies whether messages landing on destinations that use this template should attach the credential of the sending user.

- **Supports** The JMSXUserID property is set with the security principal of the sending user if requested. The sender can request its identity to be attached to its messages by using a ConnectionFactory with `AttachJMSXUserID="true"`
- **Never** The JMSXUserID property is never be set with the security principal of the sending user.
- **Always** The JMSXUserID property is always set with the security principal of the sending user.

This property is dynamically configurable. A dynamic change will only affect messages received after the update has been made.

Type: string

Constraints: Has Default Value: supports, Legal Values: supports, never, always

consumptionPausedAtStartup

Specifies whether message consumption is paused on destinations that use this template at server startup.

- **false** Paused message consumption at server startup is disabled on this template.
- **true** Paused message consumption at server startup is enabled on this template.

Type: boolean

Constraints: Has Default Value: false

defaultUnitOfOrder

Specifies whether WebLogic Server creates a system-generated unit-of-order name based on the domain, JMS server, and destination name. Any message arriving at this destination that does not already belong to a unit-of-order is assigned this default name.

This field is recommended for advanced use. Generally, it is recommended to set a message unit-of-order using application calls or connection factory configuration. When relying on a destination default unit order to enforce ordering with a distributed destination, the application must be aware that unit-of-order routing doesn't apply. Instead the application must specifically ensure that any particular set of messages that must be processed in order are all sent to the same specific member destination even in the event of process failures or service migration.

Type: boolean

Constraints: Has Default Value: false

destinationKeys

The list of potential destination keys for sorting messages that arrive on destinations that use this JMS template.

The keys are ordered from most significant to least significant. If more than one key is specified, a key based on the JMSMessageID can only be the last key in the list.

Note: If JMSMessageID is not defined in the key, it is implicitly assumed to be the last key and is set as "Ascending" (FIFO) for the sort order.

Type: array of string

id

Return the unique identifier of this bean instance.

Type: integer/int64

Constraints: Read Only

incompleteWorkExpirationTime

Specifies the maximum amount of time, in milliseconds, before undelivered messages in an incomplete UOW are expired. Such messages will then follow the template's expiration policy defined for undeliverable messages.

Note: A template's error destination for UOW messages cannot be configured to use the **Single Message Delivery** value.

Type: integer/int32

Constraints: Has Default Value: -1

insertionPausedAtStartup

Specifies whether new message insertion is paused on destinations that use this template at server startup.

- **false** Paused message insertion at server startup is disabled on this template.
- **true** Paused message insertion at server startup is enabled on this template.

Type: boolean

Constraints: Has Default Value: false

maximumMessageSize

The maximum size of a message that will be accepted from producers on this destination. The message size includes the message body, any user-defined properties, and the user-defined JMS header fields: `JMSCorrelationID` and `JMSType`

Producers sending messages that exceed the configured maximum message size for the destination receive a `ResourceAllocationException`.

The maximum message size is only enforced for the initial production of a message. Messages that are redirected to an error destination or forwarded to a member of a distributed destination are not checked for size. For instance, if a destination and its corresponding error destination are configured with a maximum message size of 128K bytes and 64K bytes, respectively, a message of 96K bytes could be redirected to the error destination (even though it exceeds the 64K byte maximum), but a producer could not directly send the 96K byte message to the error destination.

Maximum Message Size is dynamically configurable, but only incoming messages are affected; stored messages are not affected.

Type: integer/int32

Constraints: Has Default Value: 2147483647, Minimum Value: 0, Maximum Value: 2147483647

messagingPerformancePreference

Controls how long destinations that use this template are willing to wait to create full batches of available messages (if at all) for delivery to consumers. At the minimum value, batching is disabled; at the default value, less-than-full batches will not wait and are delivered immediately with currently available messages; tuning higher than the default value controls the maximum wait time for additional messages before less-than-full batches are delivered to consumers.

The maximum message count of a full batch is controlled by the JMS connection factory's `MessagesMaximum` setting.

Type: integer/int32

Constraints: Has Default Value: 25, Minimum Value: 0, Maximum Value: 100

name

The name of this entity, represented in XML as an attribute.

Many of the elements within the JMS module are named entities. All of the named entities encased by a type in the XML file must be unique. This is the identifier used to delineate a particular entity within the JMS module.

This attribute cannot be modified externally from the module (for example, with a deployment plan) because it may be used inside the module referentially.

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this named JMS descriptor bean.

JMS module saves this note in the JMS descriptor file as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note:

If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

productionPausedAtStartup

Specifies whether new message production on destinations that use this template is paused on at server startup.

- **false** Paused message production at server startup is disabled on this template.
- **true** Paused message production at server startup is enabled on this template.

Type: boolean

Constraints: Has Default Value: false

quota

A Quota controls the allotment of system resources available to destinations. For example the number of bytes a destination is allowed to store can be configured with a QuotaBean.

Type: weblogic.j2ee.descriptor.wl.QuotaBean reference

safExportPolicy

Specifies whether a user can send messages to destinations that use this template using Store-and-Forward.

- **All** All users can send messages to destinations using Store-and-Forward.
- **None** Remote users cannot send messages to destinations using Store-and-Forward.

This property is dynamically configurable. A dynamic change will only affect messages sent after the update has been made.

Type: string

Constraints: Has Default Value: All, Legal Values: All, None

unitOfWorkHandlingPolicy

Specifies whether the Unit-of-Work (UOW) feature is enabled for destinations that use this template. A UOW is a set of messages that are processed as a single unit.

- **Pass-Through** By default, destinations that use this template do not treat messages as part of a UOW.
- **Single Message Delivery** This value should only be selected if UOW consumers are receiving messages on destinations that use this template. When selected, UOW messages are formed into a list and are consumed as an `ObjectMessage` containing the list.

Type: string

Constraints: Has Default Value: PassThrough, Legal Values: PassThrough, SingleMessageDelivery

weblogic.j2ee.descriptor.wl.ThresholdParamsBean

Thresholds are a point that must be exceeded in order to produce a given effect. These action points may cause logging or flow control or other actions, as defined by the specific points whose values have been exceeded.

The properties of the `weblogic.j2ee.descriptor.wl.ThresholdParamsBean` entity are as follows:

bytesHigh

The upper threshold (total number of bytes in this destination) that triggers logging or flow control events. The value of `java.lang.Long.MAX_VALUE` disables logging and flow control events for the destination.

If the number of bytes exceeds this threshold, the triggered events are:

- Log Messages
 - A message is logged on the server indicating a high threshold condition.
- Flow Control
 - If flow control is enabled, the destination becomes armed and instructs producers to begin decreasing their message flow.

Range of Values: \leq BytesMaximum; $>$ BytesThresholdLow

Any change to this threshold affects only incoming messages; stored messages are not affected.

Type: integer/int64

Constraints: Has Default Value: 9223372036854775807, Minimum Value: 0, Maximum Value: 9223372036854775807

bytesLow

The lower threshold (total number of bytes in this destination) that triggers logging or flow control events. The value of `java.lang.Long.MAX_VALUE` disables logging and flow control events for the destination.

If the number of bytes falls below this threshold, the triggered events are:

- Log Messages
 - A message is logged on the server indicating a low threshold condition.
- Flow Control
 - If flow control is enabled, the destination becomes disarmed and instructs producers to begin increasing their message flow.

Range of Values: $<$ BytesThresholdHigh

Any change to this threshold affects only incoming messages; stored messages are not affected.

Type: integer/int64

Constraints: Has Default Value: 9223372036854775807, Minimum Value: 0, Maximum Value: 9223372036854775807

messagesHigh

The upper threshold (total number of messages in this destination) that triggers logging or flow control events. The value of `java.lang.Long.MAX_VALUE` disables logging and flow control events for the destination.

If the number of messages exceeds this threshold, the triggered events are:

- Log Messages
 - A message is logged on the server indicating a high threshold condition.
- Flow Control

If flow control is enabled, the destination becomes armed and instructs producers to begin decreasing their message flow.

Range of Values: <= MessagesMaximum; >MessagesThresholdLow

Any change to this threshold affects only incoming messages; stored messages are not affected.

Type: integer/int64

Constraints: Has Default Value: 9223372036854775807, Minimum Value: 0, Maximum Value: 9223372036854775807

messagesLow

The lower threshold (total number of messages in this destination) that triggers logging or flow control events. The value of `java.lang.Long.MAX_VALUE` disables logging and flow control events for the destination.

If the number of messages falls below this threshold, the triggered events are:

- Log Messages
 - A message is logged on the server indicating a low threshold condition.
- Flow Control
 - If flow control is enabled, the destination becomes disarmed and instructs producers to begin increasing their message flow.

Range of Values: < MessagesThresholdHigh

Any change to this threshold affects only incoming messages; stored messages are not affected.

Type: integer/int64

Constraints: Has Default Value: 9223372036854775807, Minimum Value: 0, Maximum Value: 9223372036854775807

templateBean

Finds the template bean for this destination.

Type: weblogic.j2ee.descriptor.wl.TemplateBean reference

Constraints: Read Only

weblogic.j2ee.descriptor.wl.TopicBean

Topics are used for asynchronous peer communications. A message delivered to a topic will be distributed to all topic consumers. Several aspects of a topics behavior can be configured with a topic bean.

The properties of the `weblogic.j2ee.descriptor.wl.TopicBean` entity are as follows:

JMSCreateDestinationIdentifier

A reference name for a destination or a member of a distributed destination that provides a way to lookup that destination without JNDI using `javax.jms.Session.createQueue` or `createTopic`. See "How to Lookup a Destination" in *Programming JMS* for more information on how to use this attribute.

This name must be unique within the scope of the JMS server to which this destination is targeted. However, it does not need to be unique within the scope of an entire JMS module or WebLogic Cluster. For example, two queues can have the same destination name as long as those queues are targeted to different JMS servers.

Note: Since this name must be unique within the scope of a JMS server, verify whether other JMS modules may contain destination names that conflict with this name. It is the responsibility of the deployer to resolve the destination names targeted to JMS servers.

Type: string

Constraints: Has Default Value: null

JNDIName

The global JNDI name used to look up the destination within the JNDI namespace.

In a clustered environment, this name is propagated to the entire cluster. If you want the JNDI name to be bound only on the local server, and not propagated to the rest of the cluster, then use the `Local JNDI Name` parameter.

If not specified, the destination name will not be advertised through the global JNDI namespace.

Type: string

Constraints: Has Default Value: null

SAFEExportPolicy

Specifies whether a user can send messages to a destination using Store-and-Forward.

- **All** All users can send messages to this destination using Store-and-Forward.
- **None** Remote users can not send messages to a destination using Store-and-Forward.

This attribute is dynamically configurable. A dynamic change of this attribute will affect only messages sent after the update has been made.

Type: string

Constraints: Has Default Value: All, Legal Values: All, None

attachSender

Specifies whether messages landing on this destination should attach the credential of the sending user. You should consult the JMSXUserID documentation in *Programming WebLogic JMS* before using this feature.

- **Supports** The JMSXUserID property is set with the security principal of the sending user if requested. The sender can request its identity to be attached to its messages by using a connection factory with the AttachJMSXUserID security property enabled.
- **Never** The JMSXUserID property is never set with the security principal of the sending user no matter how the AttachJMSXUserID property is configured on connection factories.
- **Always** The JMSXUserID property is always set with the security principal of the sending user no matter how the AttachJMSXUserID property is configured on connection factories.

This attribute is dynamically configurable. A dynamic change of this attribute will affect only messages received after the update has been made.

Type: string

Constraints: Has Default Value: supports, Legal Values: supports, never, always

consumptionPausedAtStartup

Specifies whether consumption is paused on a destination at startup.

- **default** If a JMS template is specified, then this value inherits the template's Consumption Paused At Startup value. If no JMS template is configured for the destination, then the Default value is equivalent to **false**
- **false** Consumption Paused is explicitly disabled for this destination.
- **true** Consumption Paused is explicitly turned on for this destination.

Type: boolean

Constraints: Has Default Value: false

defaultTargetingEnabled

Specifies whether this JMS resource defaults to the parent module's targeting or uses the subdeployment targeting mechanism.

When set to true, this resource implicitly inherits the targeting of its parent module. When set to false, this resource gets targeted based its subdeployment's targets, if one is specified.

Type: boolean

Constraints: Has Default Value: false

defaultUnitOfOrder

Specifies whether WebLogic Server creates a system-generated unit-of-order name based on the domain, JMS server, and destination name. Any message arriving at this destination that does not already belong to a unit-of-order is assigned this default name.

This field is recommended for advanced use. Generally, it is recommended to set a message unit-of-order using application calls or connection factory configuration. When relying on a destination default unit order to enforce ordering with a distributed destination, the application must be aware that unit-of-order routing doesn't apply. Instead the application must specifically ensure that any particular set of messages that must be processed in order are all sent to the same specific member destination even in the event of process failures or service migration.

Type: boolean

Constraints: Has Default Value: false

destinationKeys

The list of potential destination keys for sorting the messages that arrive on a JMS destination.

The keys are ordered from most significant to least significant. If more than one key is specified, a key based on the JMSMessageID can only be the last key in the list.

Note: If JMSMessageID is not defined in the key, it is implicitly assumed to be the last key and is set as "Ascending" (FIFO) for the sort order.

Type: array of string

forwardingPolicy

The uniform distributed topic message Forwarding Policy specifies whether a sent message is forwarded to all members.

The valid values are:

- **Replicated** - The default. All physical topic members receive each sent message. If a message arrives at one of the physical topic members, a copy of this message is forwarded to the other members of that uniform distributed topic. A subscription on any one particular member will get a copy of any message sent to the uniform distributed topic logical name or to any particular uniform distributed topic member.
- **Partitioned** - The physical member receiving the message is the only member of the uniform distributed topic that is aware of the message. When a message is published to the logical name of a Partitioned uniform distributed topic, it will only arrive on one particular physical topic member. Once a message arrives on a physical topic member, the message is not forwarded to the rest of the members of the uniform distributed destination, and subscribers on other physical topic members do not get a copy of that message. The Partitioned capability was added in WebLogic 10.3.4 (11gR1PS3).

A publisher that uses a logical JNDI name of a Replicated distributed topic is created on one member and every send call publishes messages to the same member regardless the value of the `Load Balancing Enabled` attribute. This behavior is backward compatible with previous WebLogic Server releases when using a uniform distributed topic. Under the same conditions, a Partitioned distributed topic publishes to the same member only when the value of the `Load Balancing Enabled` attribute is set to false. If the value of the `Load Balancing Enabled` attribute is to true, a publisher to a Partitioned distributed topic publishes messages that are load balanced across all the members of the uniform distributed topic.

Most new applications will use the new Partitioned forwarding policy in combination with a logical subscription topology on a uniform distributed topic that consists of: (1) a same named physical subscription created directly on each physical member, (2) a Client ID Policy of Unrestricted, and (3) a Subscription Sharing Policy of Sharable. WL 10.3.4 Message Driven Beans (MDBs) provides a Topic Messages Distribution Mode option to automatically setup this kind of topology.

Note: This attribute is ignored by standalone/singleton Topics, it only applies to distributed topics.

Type: string

Constraints: Has Default Value: Replicated, Legal Values: Partitioned, Replicated

id

Return the unique identifier of this bean instance.

Type: integer/int64

Constraints: Read Only

incompleteWorkExpirationTime

Specifies the maximum length of time, in milliseconds, before undelivered messages in an incomplete UOW are expired. Such messages will then follow the expiration policy defined for undeliverable messages.

Note: An error destination for UOW messages cannot be configured with a Unit-of-Work Handling Policy of **Single Message Delivery** value.

This attribute is effective only if the Unit-of-Work Handling Policy is set to **Single Message Delivery** value. A value of -1 means that UOW messages will never expire.

Type: integer/int32

Constraints: Has Default Value: -1

insertionPausedAtStartup

Specifies whether new message insertion is paused on a destination at startup.

- **default** If a JMS template is specified, then this value inherits the template's Insertion Paused At Startup value. If no JMS template is configured for the destination, then the Default value is equivalent to **false**
- **false** Insertion Paused is explicitly disabled for this destination.
- **true** Insertion Paused is explicitly turned on for this destination.

Type: boolean

Constraints: Has Default Value: false

loadBalancingPolicy

Determines how messages are distributed to the members of this destination.

Choose from the following distribution techniques:

- **Round-Robin** The system maintains an ordering of physical topic members within the set by distributing the messaging load across the topic members one at a time in the order that they are defined in the configuration file. Each WebLogic Server instance maintains an identical ordering, but may be at a different point within the ordering. If weights are assigned to any of the topic members in the set, then those members appear multiple times in the ordering.
- **Random** The weight assigned to the topic members is used to compute a weighted distribution for the members of the set. The messaging load is distributed across the topic members by pseudo-randomly accessing the distribution. In the short run, the load will not be directly proportional to the weight. In the long run, the distribution will approach the limit of the distribution. A pure random distribution can be achieved by setting all the weights to the same value, which is typically set to 1.

Note: This attribute is ignored by standalone/singleton Queues and Topics, it only applies to distributed destinations.

Type: string

Constraints: Has Default Value: Round-Robin, Legal Values: Round-Robin, Random

localJNDIName

The local JNDI name used to look up the destination within the JNDI namespace of the server where the destination resource is targeted. In a clustered environment, this name is bound only on the local server instance and is not propagated to the rest of the cluster.

A destination can have both a local JNDI name and a (global) JNDI name.

Type: string

Constraints: Has Default Value: null

maximumMessageSize

The maximum size of a message that is accepted from producers on this destination.

The message size includes the message body, any user-defined properties, and the user-defined JMS header fields: `JMSCorrelationID` and `JMSType`. Producers sending messages that exceed the configured maximum message size for the destination receive a `ResourceAllocationException`

The maximum message size is only enforced for the initial production of a message. Messages that are redirected to an error destination or forwarded to a member of a

distributed destination are not checked for size. For instance, if a destination and its corresponding error destination are configured with a maximum message size of 128K bytes and 64K bytes, respectively, a message of 96K bytes could be redirected to the error destination (even though it exceeds the 64K byte maximum), but a producer could not directly send the 96K byte message to the error destination.

This attribute is dynamically configurable, but only incoming messages are impacted; stored messages are not impacted.

Type: integer/int32

Constraints: Has Default Value: 2147483647, Minimum Value: 0, Maximum Value: 2147483647

messagingPerformancePreference

Controls how long destinations are willing to wait to create full batches of available messages (if at all) for delivery to consumers. At the minimum value, batching is disabled; at the default value, less-than-full batches will not wait and are delivered immediately with currently available messages; tuning higher than the default value controls the maximum wait time for additional messages before less-than-full batches are delivered to consumers.

The maximum message count of a full batch is controlled by the JMS connection factory's Messages Maximum setting.

Type: integer/int32

Constraints: Has Default Value: 25, Minimum Value: 0, Maximum Value: 100

name

The name of this entity, represented in XML as an attribute.

Many of the elements within the JMS module are named entities. All of the named entities encased by a type in the XML file must be unique. This is the identifier used to delineate a particular entity within the JMS module.

This attribute cannot be modified externally from the module (for example, with a deployment plan) because it may be used inside the module referentially.

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this named JMS descriptor bean.

JMS module saves this note in the JMS descriptor file as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note:

If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

productionPausedAtStartup

Specifies whether new message production is paused on a destination at startup.

- **default** If a JMS template is specified, then this value inherits the template's Production Paused At Startup value. If no JMS template is configured for the destination, then the Default value is equivalent to **false**

- **false** Production Paused is explicitly disabled for this destination.
- **true** Production Paused is explicitly turned on for this destination.

Type: boolean

Constraints: Has Default Value: false

quota

A Quota controls the allotment of system resources available to destinations. For example, the number of bytes a destination is allowed to store can be configured with a Quota.

Type: weblogic.j2ee.descriptor.wl.QuotaBean reference

subDeploymentName

Gets the name of the sub-deployment to use when targeting this entity

Entities are targeted using a sub-deployment with this name. The targets of the sub-deployment will be the targets of this entity.

Type: string

template

The JMS template from which the destination is derived. A template provides an efficient means of defining multiple destinations with similar configuration values.

If a JMS template is specified, destination parameters that are set to their default values will instead inherit their values from the JMS template at run-time. However, if a JMS template is not defined, then the configuration values for the destination must be specified as part of the destination.

Although you can dynamically modify the configuration of a JMS template, the configuration values on a destination are static.

Type: weblogic.j2ee.descriptor.wl.TemplateBean reference

Constraints: Restart Required

unitOfOrderRouting

Determines how a distributed destination member is selected as the destination for a message that is part of a unit-of-order. **Hash**, indicates that a message producer computes the member destination from the `hashCode` of the unit-of-order. **PathService** indicates that the configured Path Service determines the member destination.

Unit-of-Order Routing can be set programmatically with `WLProducer`, or administratively on the connection factory or destination.

Unit of Order Routing is not dynamically configurable.

Note: This attribute is ignored by standalone/singleton Queues and Topics, it only applies to distributed destinations.

Type: string

Constraints: Has Default Value: Hash

unitOfWorkHandlingPolicy

Specifies whether the Unit-of-Work (UOW) feature is enabled for this destination. A UOW is a set of messages that are processed as a single unit.

- **Pass-Through** By default, this destination does not treat messages as part of a UOW.

- **Single Message Delivery** This value should only be selected if UOW consumers are receiving messages on this destination. When selected, UOW messages are formed into a list and are consumed as an `ObjectMessage` containing the list.

Type: string

Constraints: Has Default Value: `PassThrough`, Legal Values: `PassThrough`, `SingleMessageDelivery`

weblogic.j2ee.descriptor.wl.TopicSubscriptionParamsBean

These parameters allow the administrator to control the behavior of topic subscriptions, such as the maximum number of messages that can be stored in a subscription.

The properties of the `weblogic.j2ee.descriptor.wl.TopicSubscriptionParamsBean` entity are as follows:

messagesLimitOverride

The maximum number of messages that can be stored in a topic subscription.

If a new message arrives on subscriptions that have reached the specified limit, then the first-most available messages on these subscriptions will be deleted to make room for the new message. Subscription messages are immune from this deletion if they're participating in a pending transaction, have already been passed to a consumer and are awaiting acknowledgement, or if they are part of a Unit-of-Work that is still waiting to accumulate all of its messages. Note that if all messages are immune from deletion, then a new message can cause a subscription size to exceed its limit.

A value of -1 means no limit override.

Type: integer/int64

Constraints: Has Default Value: -1, Minimum Value: -1, Maximum Value: 9223372036854775807

templateBean

Finds the template bean for this destination.

Type: `weblogic.j2ee.descriptor.wl.TemplateBean` reference

Constraints: Read Only

weblogic.j2ee.descriptor.wl.TransactionParamsBean

The transaction parameters bean controls how transactions are handled.

The properties of the `weblogic.j2ee.descriptor.wl.TransactionParamsBean` entity are as follows:

XAConnectionFactoryEnabled

Indicates whether a XA queue or XA topic connection factory is returned, instead of a queue or topic connection factory. An XA connection factory can be used to create an `XAConnection`, which in turn may be used to create an `XASession`, which in turn may be used to obtain an `XAResource` for use inside a transaction manager.

In addition, this attribute indicates whether or not a connection factory creates sessions that are JTA aware. If true, the associated message producers and message consumers look into the running thread for a transaction context. Otherwise, the current JTA transaction will be ignored.

Note: Transacted sessions ignore the current threads transaction context in favor of their own internal transaction, regardless of the setting. This setting only affects non-transacted sessions.

Type: boolean

Constraints: Has Default Value: false

transactionTimeout

The timeout value (in seconds) for all transactions on connections created with this connection factory.

If a transacted session is still active after the timeout has elapsed, the transaction is rolled back. A value of 0 indicates that the default value will be used. If you have long-running transactions, you might want to adjust the value of this attribute to allow transactions to complete.

Type: integer/int64

Constraints: Has Default Value: 3600, Minimum Value: 0, Maximum Value: 2147483647

weblogic.j2ee.descriptor.wl.UniformDistributedQueueBean

A uniform distributed queue is a distributed queue whose members are configured as part of its configuration; since members share the same configuration, they are uniform. There is one member on each JMS Server that conforms to the targeting criteria of the uniform distributed queue. For example, if a uniform distributed queue is targeted to a cluster, then one member will be created on each JMS server in the cluster. Members are created and destroyed as the targeting is changed.

The properties of the weblogic.j2ee.descriptor.wl.UniformDistributedQueueBean entity are as follows:

JMSCreateDestinationIdentifier

A reference name for a destination or a member of a distributed destination that provides a way to lookup that destination without JNDI using `javax.jms.Session.createQueue` or `createTopic`. See "How to Lookup a Destination" in *Programming JMS* for more information on how to use this attribute.

This name must be unique within the scope of the JMS server to which this destination is targeted. However, it does not need to be unique within the scope of an entire JMS module or WebLogic Cluster. For example, two queues can have the same destination name as long as those queues are targeted to different JMS servers.

Note: Since this name must be unique within the scope of a JMS server, verify whether other JMS modules may contain destination names that conflict with this name. It is the responsibility of the deployer to resolve the destination names targeted to JMS servers.

Type: string

Constraints: Has Default Value: null

JNDIName

The global JNDI name used to look up the destination within the JNDI namespace.

In a clustered environment, this name is propagated to the entire cluster. If you want the JNDI name to be bound only on the local server, and not propagated to the rest of the cluster, then use the `Local JNDI Name` parameter.

If not specified, the destination name will not be advertised through the global JNDI namespace.

Type: string

Constraints: Has Default Value: null

SAFEexportPolicy

Specifies whether a user can send messages to a destination using Store-and-Forward.

- **All** All users can send messages to this destination using Store-and-Forward.
- **None** Remote users can not send messages to a destination using Store-and-Forward.

This attribute is dynamically configurable. A dynamic change of this attribute will affect only messages sent after the update has been made.

Type: string

Constraints: Has Default Value: All, Legal Values: All, None

attachSender

Specifies whether messages landing on this destination should attach the credential of the sending user. You should consult the JMSXUserID documentation in *Programming WebLogic JMS* before using this feature.

- **Supports** The JMSXUserID property is set with the security principal of the sending user if requested. The sender can request its identity to be attached to its messages by using a connection factory with the AttachJMSXUserID security property enabled.
- **Never** The JMSXUserID property is never set with the security principal of the sending user no matter how the AttachJMSXUserID property is configured on connection factories.
- **Always** The JMSXUserID property is always set with the security principal of the sending user no matter how the AttachJMSXUserID property is configured on connection factories.

This attribute is dynamically configurable. A dynamic change of this attribute will affect only messages received after the update has been made.

Type: string

Constraints: Has Default Value: supports, Legal Values: supports, never, always

consumptionPausedAtStartup

Specifies whether consumption is paused on a destination at startup.

- **default** If a JMS template is specified, then this value inherits the template's Consumption Paused At Startup value. If no JMS template is configured for the destination, then the Default value is equivalent to **false**
- **false** Consumption Paused is explicitly disabled for this destination.
- **true** Consumption Paused is explicitly turned on for this destination.

Type: boolean

Constraints: Has Default Value: false

defaultTargetingEnabled

Specifies whether this JMS resource defaults to the parent module's targeting or uses the subdeployment targeting mechanism.

When set to true, this resource implicitly inherits the targeting of its parent module. When set to false, this resource gets targeted based its subdeployment's targets, if one is specified.

Type: boolean

Constraints: Has Default Value: false

defaultUnitOfOrder

Specifies whether WebLogic Server creates a system-generated unit-of-order name based on the domain, JMS server, and destination name. Any message arriving at this destination that does not already belong to a unit-of-order is assigned this default name.

This field is recommended for advanced use. Generally, it is recommended to set a message unit-of-order using application calls or connection factory configuration. When relying on a destination default unit order to enforce ordering with a distributed destination, the application must be aware that unit-of-order routing doesn't apply. Instead the application must specifically ensure that any particular set of messages that must be processed in order are all sent to the same specific member destination even in the event of process failures or service migration.

Type: boolean

Constraints: Has Default Value: false

destinationKeys

The list of potential destination keys for sorting the messages that arrive on a JMS destination.

The keys are ordered from most significant to least significant. If more than one key is specified, a key based on the JMSMessageID can only be the last key in the list.

Note: If JMSMessageID is not defined in the key, it is implicitly assumed to be the last key and is set as "Ascending" (FIFO) for the sort order.

Type: array of string

forwardDelay

The number of seconds after which a uniform distributed queue member with no consumers will wait before forwarding its messages to other uniform distributed queue members that do have consumers.

The default value of -1 disables this feature so that no messages are forwarded to other uniform distributed queue members.

Note: This attribute is ignored by standalone/singleton Queues, it only applies to distributed queues.

Type: integer/int32

Constraints: Has Secure Value: -1, Has Default Value: -1

id

Return the unique identifier of this bean instance.

Type: integer/int64

Constraints: Read Only

incompleteWorkExpirationTime

Specifies the maximum length of time, in milliseconds, before undelivered messages in an incomplete UOW are expired. Such messages will then follow the expiration policy defined for undeliverable messages.

Note: An error destination for UOW messages cannot be configured with a Unit-of-Work Handling Policy of **Single Message Delivery** value.

This attribute is effective only if the Unit-of-Work Handling Policy is set to **Single Message Delivery** value. A value of -1 means that UOW messages will never expire.

Type: integer/int32

Constraints: Has Default Value: -1

insertionPausedAtStartup

Specifies whether new message insertion is paused on a destination at startup.

- **default** If a JMS template is specified, then this value inherits the template's Insertion Paused At Startup value. If no JMS template is configured for the destination, then the Default value is equivalent to **false**
- **false** Insertion Paused is explicitly disabled for this destination.
- **true** Insertion Paused is explicitly turned on for this destination.

Type: boolean

Constraints: Has Default Value: false

loadBalancingPolicy

Determines how messages are distributed to the members of this destination.

Choose from the following distribution techniques:

- **Round-Robin** The system maintains an ordering of physical topic members within the set by distributing the messaging load across the topic members one at a time in the order that they are defined in the configuration file. Each WebLogic Server instance maintains an identical ordering, but may be at a different point within the ordering. If weights are assigned to any of the topic members in the set, then those members appear multiple times in the ordering.
- **Random** The weight assigned to the topic members is used to compute a weighted distribution for the members of the set. The messaging load is distributed across the topic members by pseudo-randomly accessing the distribution. In the short run, the load will not be directly proportional to the weight. In the long run, the distribution will approach the limit of the distribution. A pure random distribution can be achieved by setting all the weights to the same value, which is typically set to 1.

Note: This attribute is ignored by standalone/singleton Queues and Topics, it only applies to distributed destinations.

Type: string

Constraints: Has Default Value: Round-Robin, Legal Values: Round-Robin, Random

localJNDIName

The local JNDI name used to look up the destination within the JNDI namespace of the server where the destination resource is targeted. In a clustered environment, this name is bound only on the local server instance and is not propagated to the rest of the cluster.

A destination can have both a local JNDI name and a (global) JNDI name.

Type: string

Constraints: Has Default Value: null

maximumMessageSize

The maximum size of a message that is accepted from producers on this destination.

The message size includes the message body, any user-defined properties, and the user-defined JMS header fields: `JMSCorrelationID` and `JMSType`. Producers sending messages that exceed the configured maximum message size for the destination receive a `ResourceAllocationException`

The maximum message size is only enforced for the initial production of a message. Messages that are redirected to an error destination or forwarded to a member of a distributed destination are not checked for size. For instance, if a destination and its corresponding error destination are configured with a maximum message size of 128K bytes and 64K bytes, respectively, a message of 96K bytes could be redirected to the error destination (even though it exceeds the 64K byte maximum), but a producer could not directly send the 96K byte message to the error destination.

This attribute is dynamically configurable, but only incoming messages are impacted; stored messages are not impacted.

Type: integer/int32

Constraints: Has Default Value: 2147483647, Minimum Value: 0, Maximum Value: 2147483647

messagingPerformancePreference

Controls how long destinations are willing to wait to create full batches of available messages (if at all) for delivery to consumers. At the minimum value, batching is disabled; at the default value, less-than-full batches will not wait and are delivered immediately with currently available messages; tuning higher than the default value controls the maximum wait time for additional messages before less-than-full batches are delivered to consumers.

The maximum message count of a full batch is controlled by the JMS connection factory's Messages Maximum setting.

Type: integer/int32

Constraints: Has Default Value: 25, Minimum Value: 0, Maximum Value: 100

name

The name of this entity, represented in XML as an attribute.

Many of the elements within the JMS module are named entities. All of the named entities encased by a type in the XML file must be unique. This is the identifier used to delineate a particular entity within the JMS module.

This attribute cannot be modified externally from the module (for example, with a deployment plan) because it may be used inside the module referentially.

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this named JMS descriptor bean.

JMS module saves this note in the JMS descriptor file as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note:

If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

productionPausedAtStartup

Specifies whether new message production is paused on a destination at startup.

- **default** If a JMS template is specified, then this value inherits the template's Production Paused At Startup value. If no JMS template is configured for the destination, then the Default value is equivalent to **false**
- **false** Production Paused is explicitly disabled for this destination.
- **true** Production Paused is explicitly turned on for this destination.

Type: boolean

Constraints: Has Default Value: false

quota

A Quota controls the allotment of system resources available to destinations. For example, the number of bytes a destination is allowed to store can be configured with a Quota.

Type: weblogic.j2ee.descriptor.wl.QuotaBean reference

resetDeliveryCountOnForward

Determines whether or not the delivery count is reset during message forwarding between distributed queue members.

The default value of true resets the delivery counts on messages when they are forwarded to another distributed queue member.

Note: This attribute is ignored by standalone/singleton Queues, it only applies to distributed queues.

Type: boolean

Constraints: Has Default Value: true

subDeploymentName

Gets the name of the sub-deployment to use when targeting this entity

Entities are targeted using a sub-deployment with this name. The targets of the sub-deployment will be the targets of this entity.

Type: string

template

The JMS template from which the destination is derived. A template provides an efficient means of defining multiple destinations with similar configuration values.

If a JMS template is specified, destination parameters that are set to their default values will instead inherit their values from the JMS template at run-time. However, if a JMS template is not defined, then the configuration values for the destination must be specified as part of the destination.

Although you can dynamically modify the configuration of a JMS template, the configuration values on a destination are static.

Type: weblogic.j2ee.descriptor.wl.TemplateBean reference

Constraints: Restart Required

unitOfOrderRouting

Determines how a distributed destination member is selected as the destination for a message that is part of a unit-of-order. **Hash**, indicates that a message producer computes the member destination from the `hashCode` of the unit-of-order. **PathService** indicates that the configured Path Service determines the member destination.

Unit-of-Order Routing can be set programmatically with `WLProducer`, or administratively on the connection factory or destination.

Unit of Order Routing is not dynamically configurable.

Note: This attribute is ignored by standalone/singleton Queues and Topics, it only applies to distributed destinations.

Type: string

Constraints: Has Default Value: Hash

unitOfWorkHandlingPolicy

Specifies whether the Unit-of-Work (UOW) feature is enabled for this destination. A UOW is a set of messages that are processed as a single unit.

- **Pass-Through** By default, this destination does not treat messages as part of a UOW.
- **Single Message Delivery** This value should only be selected if UOW consumers are receiving messages on this destination. When selected, UOW messages are formed into a list and are consumed as an `ObjectMessage` containing the list.

Type: string

Constraints: Has Default Value: PassThrough, Legal Values: PassThrough, SingleMessageDelivery

weblogic.j2ee.descriptor.wl.UniformDistributedTopicBean

A uniform distributed topic is a distributed topic whose members are configured as part of its configuration; since members share the same configuration, they are uniform. There is one member on each JMS Server that conforms to the targeting criteria of the uniform distributed topic. For example, if a uniform distributed topic is targeted to a cluster, then one member will be created on each JMS server in the cluster. Members are created and destroyed as the targeting is changed.

The properties of the `weblogic.j2ee.descriptor.wl.UniformDistributedTopicBean` entity are as follows:

JMSCreateDestinationIdentifier

A reference name for a destination or a member of a distributed destination that provides a way to lookup that destination without JNDI using `javax.jms.Session.createQueue` or `createTopic`. See "How to Lookup a Destination" in *Programming JMS* for more information on how to use this attribute.

This name must be unique within the scope of the JMS server to which this destination is targeted. However, it does not need to be unique within the scope of an entire JMS module or WebLogic Cluster. For example, two queues can have the same destination name as long as those queues are targeted to different JMS servers.

Note: Since this name must be unique within the scope of a JMS server, verify whether other JMS modules may contain destination names that conflict with this name. It is the responsibility of the deployer to resolve the destination names targeted to JMS servers.

Type: string

Constraints: Has Default Value: null

JNDIName

The global JNDI name used to look up the destination within the JNDI namespace.

In a clustered environment, this name is propagated to the entire cluster. If you want the JNDI name to be bound only on the local server, and not propagated to the rest of the cluster, then use the `Local JNDI Name` parameter.

If not specified, the destination name will not be advertised through the global JNDI namespace.

Type: string

Constraints: Has Default Value: null

SAFEExportPolicy

Specifies whether a user can send messages to a destination using Store-and-Forward.

- **All** All users can send messages to this destination using Store-and-Forward.
- **None** Remote users can not send messages to a destination using Store-and-Forward.

This attribute is dynamically configurable. A dynamic change of this attribute will affect only messages sent after the update has been made.

Type: string

Constraints: Has Default Value: All, Legal Values: All, None

attachSender

Specifies whether messages landing on this destination should attach the credential of the sending user. You should consult the JMSXUserID documentation in *Programming WebLogic JMS* before using this feature.

- **Supports** The JMSXUserID property is set with the security principal of the sending user if requested. The sender can request its identity to be attached to its messages by using a connection factory with the AttachJMSXUserID security property enabled.
- **Never** The JMSXUserID property is never set with the security principal of the sending user no matter how the AttachJMSXUserID property is configured on connection factories.
- **Always** The JMSXUserID property is always set with the security principal of the sending user no matter how the AttachJMSXUserID property is configured on connection factories.

This attribute is dynamically configurable. A dynamic change of this attribute will affect only messages received after the update has been made.

Type: string

Constraints: Has Default Value: supports, Legal Values: supports, never, always

consumptionPausedAtStartup

Specifies whether consumption is paused on a destination at startup.

- **default** If a JMS template is specified, then this value inherits the template's Consumption Paused At Startup value. If no JMS template is configured for the destination, then the Default value is equivalent to **false**

- **false** Consumption Paused is explicitly disabled for this destination.
- **true** Consumption Paused is explicitly turned on for this destination.

Type: boolean

Constraints: Has Default Value: false

defaultTargetingEnabled

Specifies whether this JMS resource defaults to the parent module's targeting or uses the subdeployment targeting mechanism.

When set to true, this resource implicitly inherits the targeting of its parent module. When set to false, this resource gets targeted based its subdeployment's targets, if one is specified.

Type: boolean

Constraints: Has Default Value: false

defaultUnitOfOrder

Specifies whether WebLogic Server creates a system-generated unit-of-order name based on the domain, JMS server, and destination name. Any message arriving at this destination that does not already belong to a unit-of-order is assigned this default name.

This field is recommended for advanced use. Generally, it is recommended to set a message unit-of-order using application calls or connection factory configuration. When relying on a destination default unit order to enforce ordering with a distributed destination, the application must be aware that unit-of-order routing doesn't apply. Instead the application must specifically ensure that any particular set of messages that must be processed in order are all sent to the same specific member destination even in the event of process failures or service migration.

Type: boolean

Constraints: Has Default Value: false

destinationKeys

The list of potential destination keys for sorting the messages that arrive on a JMS destination.

The keys are ordered from most significant to least significant. If more than one key is specified, a key based on the JMSMessageID can only be the last key in the list.

Note: If JMSMessageID is not defined in the key, it is implicitly assumed to be the last key and is set as "Ascending" (FIFO) for the sort order.

Type: array of string

forwardingPolicy

The uniform distributed topic message Forwarding Policy specifies whether a sent message is forwarded to all members.

The valid values are:

- **Replicated** - The default. All physical topic members receive each sent message. If a message arrives at one of the physical topic members, a copy of this message is forwarded to the other members of that uniform distributed topic. A subscription on any one particular member will get a copy of any message sent to the uniform distributed topic logical name or to any particular uniform distributed topic member.

- **Partitioned** - The physical member receiving the message is the only member of the uniform distributed topic that is aware of the message. When a message is published to the logical name of a Partitioned uniform distributed topic, it will only arrive on one particular physical topic member. Once a message arrives on a physical topic member, the message is not forwarded to the rest of the members of the uniform distributed destination, and subscribers on other physical topic members do not get a copy of that message. The Partitioned capability was added in WebLogic 10.3.4 (11gR1PS3).

A publisher that uses a logical JNDI name of a Replicated distributed topic is created on one member and every send call publishes messages to the same member regardless the value of the `Load Balancing Enabled` attribute. This behavior is backward compatible with previous WebLogic Server releases when using a uniform distributed topic. Under the same conditions, a Partitioned distributed topic publishes to the same member only when the value of the `Load Balancing Enabled` attribute is set to false. If the value of the `Load Balancing Enabled` attribute is to true, a publisher to a Partitioned distributed topic publishes messages that are load balanced across all the members of the uniform distributed topic.

Most new applications will use the new Partitioned forwarding policy in combination with a logical subscription topology on a uniform distributed topic that consists of: (1) a same named physical subscription created directly on each physical member, (2) a Client ID Policy of Unrestricted, and (3) a Subscription Sharing Policy of Sharable. WL 10.3.4 Message Driven Beans (MDBs) provides a Topic Messages Distribution Mode option to automatically setup this kind of topology.

Note: This attribute is ignored by standalone/singleton Topics, it only applies to distributed topics.

Type: string

Constraints: Has Default Value: Replicated, Legal Values: Partitioned, Replicated

id

Return the unique identifier of this bean instance.

Type: integer/int64

Constraints: Read Only

incompleteWorkExpirationTime

Specifies the maximum length of time, in milliseconds, before undelivered messages in an incomplete UOW are expired. Such messages will then follow the expiration policy defined for undeliverable messages.

Note: An error destination for UOW messages cannot be configured with a Unit-of-Work Handling Policy of **Single Message Delivery** value.

This attribute is effective only if the Unit-of-Work Handling Policy is set to **Single Message Delivery** value. A value of -1 means that UOW messages will never expire.

Type: integer/int32

Constraints: Has Default Value: -1

insertionPausedAtStartup

Specifies whether new message insertion is paused on a destination at startup.

- **default** If a JMS template is specified, then this value inherits the template's Insertion Paused At Startup value. If no JMS template is configured for the destination, then the Default value is equivalent to **false**

- **false** Insertion Paused is explicitly disabled for this destination.
- **true** Insertion Paused is explicitly turned on for this destination.

Type: boolean

Constraints: Has Default Value: false

loadBalancingPolicy

Determines how messages are distributed to the members of this destination.

Choose from the following distribution techniques:

- **Round-Robin** The system maintains an ordering of physical topic members within the set by distributing the messaging load across the topic members one at a time in the order that they are defined in the configuration file. Each WebLogic Server instance maintains an identical ordering, but may be at a different point within the ordering. If weights are assigned to any of the topic members in the set, then those members appear multiple times in the ordering.
- **Random** The weight assigned to the topic members is used to compute a weighted distribution for the members of the set. The messaging load is distributed across the topic members by pseudo-randomly accessing the distribution. In the short run, the load will not be directly proportional to the weight. In the long run, the distribution will approach the limit of the distribution. A pure random distribution can be achieved by setting all the weights to the same value, which is typically set to 1.

Note: This attribute is ignored by standalone/singleton Queues and Topics, it only applies to distributed destinations.

Type: string

Constraints: Has Default Value: Round-Robin, Legal Values: Round-Robin, Random

localJNDIName

The local JNDI name used to look up the destination within the JNDI namespace of the server where the destination resource is targeted. In a clustered environment, this name is bound only on the local server instance and is not propagated to the rest of the cluster.

A destination can have both a local JNDI name and a (global) JNDI name.

Type: string

Constraints: Has Default Value: null

maximumMessageSize

The maximum size of a message that is accepted from producers on this destination.

The message size includes the message body, any user-defined properties, and the user-defined JMS header fields: `JMSCorrelationID` and `JMSType`. Producers sending messages that exceed the configured maximum message size for the destination receive a `ResourceAllocationException`

The maximum message size is only enforced for the initial production of a message. Messages that are redirected to an error destination or forwarded to a member of a distributed destination are not checked for size. For instance, if a destination and its corresponding error destination are configured with a maximum message size of 128K bytes and 64K bytes, respectively, a message of 96K bytes could be redirected to the error destination (even though it exceeds the 64K byte maximum), but a producer could not directly send the 96K byte message to the error destination.

This attribute is dynamically configurable, but only incoming messages are impacted; stored messages are not impacted.

Type: integer/int32

Constraints: Has Default Value: 2147483647, Minimum Value: 0, Maximum Value: 2147483647

messagingPerformancePreference

Controls how long destinations are willing to wait to create full batches of available messages (if at all) for delivery to consumers. At the minimum value, batching is disabled; at the default value, less-than-full batches will not wait and are delivered immediately with currently available messages; tuning higher than the default value controls the maximum wait time for additional messages before less-than-full batches are delivered to consumers.

The maximum message count of a full batch is controlled by the JMS connection factory's Messages Maximum setting.

Type: integer/int32

Constraints: Has Default Value: 25, Minimum Value: 0, Maximum Value: 100

name

The name of this entity, represented in XML as an attribute.

Many of the elements within the JMS module are named entities. All of the named entities encased by a type in the XML file must be unique. This is the identifier used to delineate a particular entity within the JMS module.

This attribute cannot be modified externally from the module (for example, with a deployment plan) because it may be used inside the module referentially.

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this named JMS descriptor bean.

JMS module saves this note in the JMS descriptor file as XML PCDATA. All left angle brackets (<) are converted to the XML entity <. Carriage returns/line feeds are preserved.

Note:

If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

productionPausedAtStartup

Specifies whether new message production is paused on a destination at startup.

- **default** If a JMS template is specified, then this value inherits the template's Production Paused At Startup value. If no JMS template is configured for the destination, then the Default value is equivalent to **false**
- **false** Production Paused is explicitly disabled for this destination.
- **true** Production Paused is explicitly turned on for this destination.

Type: boolean

Constraints: Has Default Value: false

quota

A Quota controls the allotment of system resources available to destinations. For example, the number of bytes a destination is allowed to store can be configured with a Quota.

Type: weblogic.j2ee.descriptor.wl.QuotaBean reference

subDeploymentName

Gets the name of the sub-deployment to use when targeting this entity

Entities are targeted using a sub-deployment with this name. The targets of the sub-deployment will be the targets of this entity.

Type: string

template

The JMS template from which the destination is derived. A template provides an efficient means of defining multiple destinations with similar configuration values.

If a JMS template is specified, destination parameters that are set to their default values will instead inherit their values from the JMS template at run-time. However, if a JMS template is not defined, then the configuration values for the destination must be specified as part of the destination.

Although you can dynamically modify the configuration of a JMS template, the configuration values on a destination are static.

Type: weblogic.j2ee.descriptor.wl.TemplateBean reference

Constraints: Restart Required

unitOfOrderRouting

Determines how a distributed destination member is selected as the destination for a message that is part of a unit-of-order. **Hash**, indicates that a message producer computes the member destination from the hashCode of the unit-of-order. **PathService** indicates that the configured Path Service determines the member destination.

Unit-of-Order Routing can be set programmatically with WLPProducer, or administratively on the connection factory or destination.

Unit of Order Routing is not dynamically configurable.

Note: This attribute is ignored by standalone/singleton Queues and Topics, it only applies to distributed destinations.

Type: string

Constraints: Has Default Value: Hash

unitOfWorkHandlingPolicy

Specifies whether the Unit-of-Work (UOW) feature is enabled for this destination. A UOW is a set of messages that are processed as a single unit.

- **Pass-Through** By default, this destination does not treat messages as part of a UOW.
- **Single Message Delivery** This value should only be selected if UOW consumers are receiving messages on this destination. When selected, UOW messages are formed into a list and are consumed as an `ObjectMessage` containing the list.

Type: string

Constraints: Has Default Value: PassThrough, Legal Values: PassThrough, SingleMessageDelivery

weblogic.management.configuration.AdminConsoleMBean

AdminConsoleMBean is a console specific MBean to configure weblogic administration console attributes.

The properties of the weblogic.management.configuration.AdminConsoleMBean entity are as follows:

SSOLogoutURL

Returns the log out URL for the Administration Console in a single sign-on (SSO) environment. Only needed when you use the Console with an SSO provider that requires a log out URL so that it can clean up its SSO session state. See the SSO provider documentation for details on the URL value

Type: string

Constraints: Has Default Value: null

cookieName

Returns the Cookie Name used by the Administration Console.

Type: string

Constraints: Has Default Value: ADMINCONSOLESESSION

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

minThreads

Specify the minimum number of threads that should be dedicated to the Administration Console. These threads are used to interact with managed servers in parallel for improved responsiveness in large domains. 5 is the smallest accepted number.

Type: integer/int32

Constraints: Has Default Value: 101, Minimum Value: 5

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

`Name=user-specified-name`

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

protectedCookieEnabled

Set to true if the Administration Console's session cookie is protected so that it is only visible to the Console. This may prevent use of this shared cookie in other applications.

Type: boolean

Constraints: Has Default Value: true

sessionTimeout

Returns Session Timeout value (in seconds) for Administration Console.

Type: integer/int32

Constraints: Has Default Value: 3600

tags

Return all tags on this Configuration MBean

Type: array of string

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.AdminVirtualTargetMBean

The properties of the `weblogic.management.configuration.AdminVirtualTargetMBean` entity are as follows:

deploymentOrder

A priority that the server uses to determine when it deploys an item. The priority is relative to other deployable items of the same type.

For example, the server prioritizes and deploys all EJBs before it prioritizes and deploys startup classes.

Items with the lowest Deployment Order value are deployed first. There is no guarantee on the order of deployments with equal Deployment Order values. There is no guarantee of ordering across clusters.

Type: integer/int32

Constraints: Has Default Value: 1000, Minimum Value: 0, Maximum Value: 2147483647

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to `config.xml`

Type: boolean

Constraints: Read Only, Has Default Value: false

explicitPort

Get the explicit port for this virtual target.

Type: integer/int32

Constraints: Has Default Value: 0, Minimum Value: 0, Maximum Value: 65535

hostNames

Host names, separated by line breaks, for which this virtual target will serve requests.

Type: array of string

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

Name=user-specified-name

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

partitionChannel

The channel name to be used as a reference for creating a partition specific channel.

Type: string

Constraints: Has Default Value: PartitionChannel

portOffset

The port offset for this virtual target. If set to the minimum value, the port offset is not set.

Type: integer/int32

Constraints: Has Default Value: 0, Minimum Value: 0, Maximum Value: 65535

tags

Return all tags on this Configuration MBean

Type: array of string

targets

You must select a target from this list of the targets in the current domain. Targets must be either servers or clusters. The deployment will only occur once if the targets overlap. For example, if a deployment is deployed both on a cluster C and on a server S that is a member of that cluster, the deployment will be deployed on server S only once.

Type: array of weblogic.management.configuration.TargetMBean references

Constraints: Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

uriPrefix

The URI prefix for this virtual target.

Type: string

Constraints: Has Default Value: /

weblogic.management.configuration.AppDeploymentMBean

This MBean is used to configure all physical package types which can be deployed on a WebLogic domain, for instance, EAR files and standalone Java EE and non-Java EE modules.

The properties of the weblogic.management.configuration.AppDeploymentMBean entity are as follows:

absoluteAltDescriptorDir

The fully resolved location of this application's alternate descriptor directory on the Administration Server.

Type: string

Constraints: Read Only

absoluteAltDescriptorPath

The fully resolved location of this application's alternate descriptor on the Administration Server.

Type: string

Constraints: Read Only

absoluteInstallDir

The fully resolved location of this application's installation root directory on the Administration Server.

Type: string

Constraints: Read Only

absolutePlanDir

The fully resolved location of this application's deployment plan directory on the Administration Server.

Type: string

Constraints: Read Only

absolutePlanPath

The fully resolved location of this application's deployment plan on the Administration Server.

Type: string

Constraints: Read Only

absoluteSourcePath

The fully resolved location of this application's source files on the Administration Server.

Type: string

Constraints: Read Only

altDescriptorDir

The location of this application's configuration area. This directory can contain alternate descriptor files.

Rules:

If the alternate descriptor directory is a relative path, it is resolved relative to InstallDir if InstallDir is not null; otherwise, it is resolved relative to the domain root.

Use AbsoluteAltDescriptorDir to get a fully resolved value.

Type: string

Constraints: Read Only

applicationIdentifier

The Application Identifier of the application version uniquely identifies the application version across all versions of all applications. If the application is not versioned, the Application Identifier is the same as the application name.

Type: string

Constraints: Read Only

applicationName

The name of the application.

Note that the name of the current MBean is not the name of the application.

Type: string

Constraints: Read Only

cacheInAppDirectory

Type: boolean

compatibilityName

This is only set for beans created as a result of conversion from an 8.1 application configured using ApplicationMBean and ComponentMBean.

Standalone modules in 8.1 have both an ApplicationMBean name and ComponentMBean name. This attribute stores the name of the latter, to be used when the server creates the transient ComponentMBean for backward compatibility.

Type: string

deploymentOrder

An integer value that indicates when this unit is deployed, relative to other deployable units on a server, during startup.

Units with lower values are deployed before those with higher values.

Type: integer/int32

Constraints: Has Default Value: 100

deploymentPrincipalName

A string value that indicates the principal that should be used when deploying the file or archive during startup and shutdown. This principal will be used to set the current subject when calling out into application code for interfaces such as `ApplicationLifecycleListener`. If no principal name is specified, then the anonymous principal will be used.

Type: string

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to `config.xml`

Type: boolean

Constraints: Read Only, Has Default Value: false

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

installDir

The path to the application's install-root directory, relative to the `domain/config/deployments` directory.

When the installation directory is specified, `SourcePath`, `PlanDir`, and `PlanPath` are derived from this path and need not be specified.

The default value for this is the name of the deployment.

Type: string

Constraints: Read Only

moduleType

The values match those defined by `jsr88`. This attribute may move to another MBean.

Type: string

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

Name=user-specified-name

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

parallelDeployModules

Determines if the modules of applications will be deployed in parallel.

Type: boolean

planDir

The location of this application's configuration area. This directory can contain external descriptor files as specified within the deployment plan document.

Rules:

If the plan directory is a relative path, it is resolved relative to `InstallDir` if `InstallDir` is not null; otherwise, it is resolved relative to the domain root.

Use `AbsolutePlanDir` to get a fully resolved value.

Type: string

Constraints: Read Only

planPath

The path to the deployment plan document on the Administration Server.

Rules:

If the plan path is a relative path, it is resolved relative to `PlanDir` if `PlanDir` is not null; otherwise, it is resolved relative to the domain root.

Use `AbsolutePlanPath` to get a fully resolved value.

If there is no plan, this returns no plan specified.

Type: string

Constraints: Read Only

planStagingMode

Specifies whether an application's deployment plan is copied from a source on the Administration Server to the Managed Server's staging area during application preparation.

Plan staging mode for an application can only be set the first time the application is deployed. Once the plan staging mode for an application is set, it cannot be changed while the application is configured in the domain. The only way to change the plan staging mode is to undeploy and then redeploy the application.

This attribute overrides the server's plan staging mode.

Type: string

Constraints: Read Only, Has Default Value: null, Legal Values: nostage, stage, external_stage

securityDDModel

The security model that is used to secure a deployed module.

To set this value, you can use the `weblogic.Deployer` command-line tool, the Deployment Assistant in the Administration Console, the WebLogic Scripting Tool (WLST), or another JMX client.

If you deploy a module using one of the previously mentioned tools and you do not specify a security model value, the module is secured with the security realm's default model (see `weblogic.management.security.RealmMBean#getSecurityDDModel` `RealmMBean SecurityDDModel`).

If you deploy a module by modifying the domain's `config.xml` file and restarting the server, and if you do not specify a security model value for the module in `config.xml`, the module is secured with the `DDOnly` model, which is the default value of this `AppDeploymentMBean` attribute.

In summary, the order of precedence for the value of this attribute is as follows:

- If you deploy a module using a runtime deployment utility, the order of precedence is:
 1. The value set by the deployment utility.
 2. The value set as the security realm's default security model.
- If you deploy a module by modifying `config.xml` and restarting the server, the order of precedence is:
 1. The value that you specify for the module in `config.xml`
 2. The default value of this `AppDeploymentMBean SecurityDDModel` attribute.

Type: string

Constraints: Read Only, Has Default Value: `DDOnly`, Legal Values: `DDOnly`, `CustomRoles`, `CustomRolesAndPolicies`, `Advanced`

sourcePath

The path to the source of the deployable unit on the Administration Server.

Rules:

If the source path is relative, it is resolved relative to `InstallDir/app` if `InstallDir` is not null; otherwise, it is resolved relative to the domain root.

Use `AbsoluteSourcePath` to get a fully resolved value.

Type: string

Constraints: Read Only

stagingMode

Specifies whether a deployment's files are copied from a source on the Administration Server to the Managed Server's staging area during application preparation.

Staging mode for an application can only be set the first time the application is deployed. Once the staging mode for an application is set, it cannot be changed while the application is configured in the domain. The only way to change the staging mode is to undeploy and then redeploy the application.

This attribute overrides the server's staging mode.

Type: string

Constraints: Read Only, Has Default Value: null, Legal Values: `nostage`, `stage`, `external_stage`

tags

Return all tags on this Configuration MBean

Type: array of string

targets

You must select a target on which an MBean will be deployed from this list of the targets in the current domain on which this item can be deployed. Targets must be either servers or clusters. The deployment will only occur once if deployments overlap.

Type: array of weblogic.management.configuration.TargetMBean references

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

untargeted

Only relevant for deployments in resource group templates. This flag, when specified as true, indicates that the application deployment must not be deployed in the referring partition.

Type: boolean

Constraints: Has Default Value: false

validateDDSecurityData

This attribute is not used in the current release.

Type: boolean

Constraints: Has Default Value: false

versionIdentifier

Uniquely identifies the application version across all versions of the same application.

If the application is not versioned, this returns null.

Type: string

Constraints: Read Only

weblogic.management.configuration.AuthConfigProviderMBean

The properties of the weblogic.management.configuration.AuthConfigProviderMBean entity are as follows:

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

Name=user-specified-name

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

tags

Return all tags on this Configuration MBean

Type: array of string

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.BatchConfigMBean

This class represents the configuration for Batch Runtime.

The properties of the `weblogic.management.configuration.BatchConfigMBean` entity are as follows:

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to `config.xml`

Type: boolean

Constraints: Read Only, Has Default Value: false

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

Name=user-specified-name

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

schemaName

The schema name where the JobRepository tables have been created. Note that if the JobRepository data source is shared by applications, then this schema name must be the same name that the application expects.

Type: string

tags

Return all tags on this Configuration MBean

Type: array of string

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.CapacityMBean

CapacityMBean defines the maximum number of requests that can be enqueued by all the work managers that share it.

The server starts rejecting requests once the capacity threshold is reached. Note that the capacity includes all requests, queued or executing, from the constrained work set. This constraint is independent of the global queue threshold specified by `OverloadProtectionMBean#getSharedCapacityForWorkManagers()`.

Requests are rejected by performing overload actions. RMI work is rejected by sending back a recoverable exception to the clients. Servlet requests are rejected by sending back a 503 response.

The properties of the `weblogic.management.configuration.CapacityMBean` entity are as follows:

count

Total number of requests that can be enqueued.

Type: integer/int32

Constraints: Has Default Value: -1

deploymentOrder

A priority that the server uses to determine when it deploys an item. The priority is relative to other deployable items of the same type.

For example, the server prioritizes and deploys all EJBs before it prioritizes and deploys startup classes.

Items with the lowest Deployment Order value are deployed first. There is no guarantee on the order of deployments with equal Deployment Order values. There is no guarantee of ordering across clusters.

Type: integer/int32

Constraints: Has Default Value: 1000, Minimum Value: 0, Maximum Value: 2147483647

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

Name=user-specified-name

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

tags

Return all tags on this Configuration MBean

Type: array of string

targets

You must select a target on which an MBean will be deployed from this list of the targets in the current domain on which this item can be deployed. Targets must be either servers or clusters. The deployment will only occur once if deployments overlap.

Type: array of `weblogic.management.configuration.TargetMBean` references

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.CdiContainerMBean

This MBean is used to specify domain-wide defaults for the CDI container

The properties of the weblogic.management.configuration.CdiContainerMBean entity are as follows:

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

implicitBeanDiscoveryEnabled

This flag may be used to limit implicit Bean discovery

Type: boolean

Constraints: Has Default Value: true

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

Name=user-specified-name

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`;

Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

policy

Indicates the CDI policy. CDI can be "Enabled" (the default) or "Disabled". If CDI is disabled then no CDI processing will occur including scanning of pojos and initialization of Weld and CDI will not be available to the application via the CDI apis.

Type: string

Constraints: Has Default Value: Enabled, Legal Values: Enabled, Disabled

tags

Return all tags on this Configuration MBean

Type: array of string

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.CertRevocCaMBean

This MBean represents the configuration of certificate revocation checking for a specific certificate authority. Default values for attributes in this MBean are derived from CertRevocMBean

The properties of the weblogic.management.configuration.CertRevocCaMBean entity are as follows:

checkingDisabled

For this CA, determines whether certificate revocation checking is disabled.

Type: boolean

Constraints: Has Default Value: false

crIDpBackgroundDownloadEnabled

For this CA, determines whether the CRL Distribution Point background downloading, to automatically update the local CRL cache, is enabled.

Type: boolean

crIDpDownloadTimeout

For this CA, determines the overall timeout for the Distribution Point CRL download, expressed in seconds.

The valid range is 1 thru 300 seconds.

Type: integer/int64

Constraints: Minimum Value: 1, Maximum Value: 300

crIDpEnabled

For this CA, determines whether the CRL Distribution Point processing to update the local CRL cache is enabled.

Type: boolean

crIDpUrl

For this CA, determines the CRL Distribution Point URL to use as failover or override for the URL found in the CRLDistributionPoints extension in the certificate.

Type: string

Constraints: Has Default Value: null

crldpUriUsage

For this CA, determines how `getCrldpUrl` is used: as failover in case the URL in the certificate `CRLDistributionPoints` extension is invalid or not found, or as a value overriding the URL found in the certificate `CRLDistributionPoints` extension.

Type: string

Constraints: Has Default Value: FAILOVER, Legal Values: FAILOVER, OVERRIDE

distinguishedName

Determines the identity of this per-CA configuration using the distinguished name (defined in RFC 2253), which is used in certificates issued by the represented certificate authority.

For example:

```
"CN=CertGenCAB, OU=FOR TESTING ONLY, O=MyOrganization, L=MyTown,
ST=MyState, C=US"
```

This will be used to match this configuration to issued certificates requiring revocation checking.

Type: string

Constraints: Has Default Value: null

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to `config.xml`

Type: boolean

Constraints: Read Only, Has Default Value: false

failOnUnknownRevocStatus

For this CA, determines whether certificate path checking should fail, if revocation status could not be determined.

Type: boolean

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

methodOrder

For this CA, determines the certificate revocation checking method order.

NOTE THAT omission of a specific method disables that method.

Type: string

Constraints: Legal Values: OCSP, CRL, OCSP_THEN_CRL, CRL_THEN_OCSP

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

```
Name=user-specified-name
```

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

ocspNonceEnabled

For this CA, determines whether a nonce is sent with OCSF requests, to force a fresh (not pre-signed) response.

Type: boolean

ocspResponderCertIssuerName

For this CA, determines the explicitly trusted OCSF responder certificate issuer name, when the attribute returned by `getOcspResponderExplicitTrustMethod` is "USE_ISSUER_SERIAL_NUMBER".

The issuer name is formatted as a distinguished name per RFC 2253, for example "CN=CertGenCAB, OU=FOR TESTING ONLY, O=MyOrganization, L=MyTown, ST=MyState, C=US".

When `getOcspResponderCertIssuerName` returns a non-null value then the `getOcspResponderCertSerialNumber` must also be set.

Type: string

Constraints: Has Default Value: null

ocspResponderCertSerialNumber

For this CA, determines the explicitly trusted OCSF responder certificate serial number, when the attribute returned by `getOcspResponderExplicitTrustMethod` is "USE_ISSUER_SERIAL_NUMBER".

The serial number is formatted as a hexadecimal string, with optional colon or space separators, for example "2A:FF:00".

When `getOcspResponderCertSerialNumber` returns a non-null value then the `getOcspResponderCertIssuerName` must also be set.

Type: string

Constraints: Has Default Value: null

ocspResponderCertSubjectName

For this CA, determines the explicitly trusted OCSF responder certificate subject name, when the attribute returned by `getOcspResponderExplicitTrustMethod` is "USE_SUBJECT".

The subject name is formatted as a distinguished name per RFC 2253, for example "CN=CertGenCAB, OU=FOR TESTING ONLY, O=MyOrganization, L=MyTown, ST=MyState, C=US".

In cases where the subject name alone is not sufficient to uniquely identify the certificate, then both the `getOcspResponderCertIssuerName` and `getOcspResponderCertSerialNumber` may be used instead.

Type: string

Constraints: Has Default Value: null

ocspResponderExplicitTrustMethod

For this CA, determines whether the OCSP Explicit Trust model is enabled and how the trusted certificate is specified.

The valid values:

"NONE"

Explicit Trust is disabled

"USE_SUBJECT"

Identify the trusted certificate using the subject DN specified in the attribute `getOcspResponderCertSubjectName`

"USE_ISSUER_SERIAL_NUMBER"

Identify the trusted certificate using the issuer DN and certificate serial number specified in the attributes `getOcspResponderCertIssuerName` and `getOcspResponderCertSerialNumber`, respectively.

Type: string

Constraints: Has Default Value: NONE, Legal Values: NONE, USE_SUBJECT, USE_ISSUER_SERIAL_NUMBER

ocspResponderUrl

For this CA, determines the OCSP responder URL to use as failover or override for the URL found in the certificate AIA. The usage is determined by `getOcspResponderUrlUsage`

Type: string

Constraints: Has Default Value: null

ocspResponderUrlUsage

For this CA, determines how `getOcspResponderUrl` is used: as failover in case the URL in the certificate AIA is invalid or not found, or as a value overriding the URL found in the certificate AIA.

Type: string

Constraints: Has Default Value: FAILOVER, Legal Values: FAILOVER, OVERRIDE

ocspResponseCacheEnabled

For this CA, determines whether the OCSP response local cache is enabled.

Type: boolean

ocspResponseTimeout

For this CA, determines the timeout for the OCSP response, expressed in seconds.

The valid range is 1 thru 300 seconds.

Type: integer/int64

Constraints: Minimum Value: 1, Maximum Value: 300

ocspTimeTolerance

For this CA, determines the time tolerance value for handling clock-skew differences between clients and responders, expressed in seconds.

The validity period of the response is extended both into the future and into the past by the specified amount of time, effectively widening the validity interval.

The value is ≥ 0 and ≤ 900 . The maximum allowed tolerance is 15 minutes.

Type: integer/int32

Constraints: Minimum Value: 0, Maximum Value: 900

tags

Return all tags on this Configuration MBean

Type: array of string

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.CertRevocMBean

This MBean represents the configuration of the certificate revocation checking across all certificate authorities. Many of the attributes in this MBean may be overridden per certificate authority using the specific `CertRevocCaMBean`

The properties of the `weblogic.management.configuration.CertRevocMBean` entity are as follows:

checkingEnabled

Determines whether certificate revocation checking is enabled.

Type: boolean

Constraints: Has Default Value: false

crlCacheRefreshPeriodPercent

Determines the refresh period for the CRL local cache, expressed as a percentage of the validity period of the CRL.

For example, for a validity period of 10 hours, a value of 10% specifies a refresh every 1 hour.

The validity period is determined by the CRL, and is calculated as the (next reported update time) - (this update time).

The valid range is 1 through 100.

Type: integer/int32

Constraints: Has Default Value: 100, Minimum Value: 1, Maximum Value: 100

crlCacheType

Determines the type of CRL cache, related to the physical storage of the CRLs. The ldap CRL cache type can be specified, but is not currently supported.

The value specified in this attribute determines which related `CrlCacheType*` attributes apply.

Type: string

Constraints: Has Default Value: FILE, Legal Values: FILE, LDAP

crlDpBackgroundDownloadEnabled

Determines whether the CRL Distribution Point background downloading, to automatically update the local CRL cache, is enabled.

Type: boolean

Constraints: Has Default Value: false

crIDpDownloadTimeout

Determines the overall timeout for the Distribution Point CRL download, expressed in seconds.

The valid range is 1 thru 300 seconds.

Type: integer/int64

Constraints: Has Default Value: 10, Minimum Value: 1, Maximum Value: 300

crIDpEnabled

Determines whether the CRL Distribution Point processing to update the local CRL cache is enabled.

Type: boolean

Constraints: Has Default Value: true

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

failOnUnknownRevocStatus

Determines whether certificate path checking should fail, if revocation status could not be determined.

Type: boolean

Constraints: Has Default Value: false

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

methodOrder

Determines the certificate revocation checking method order.

NOTE that omission of a specific method disables that method.

Type: string

Constraints: Has Default Value: OCSP_THEN_CRL, Legal Values: OCSP, CRL, OCSP_THEN_CRL, CRL_THEN_OCSP

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

`Name=user-specified-name`

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

ocspNonceEnabled

Determines whether a nonce is sent with OCSP requests, to force a fresh (not pre-signed) response.

Type: boolean

Constraints: Has Default Value: false

ocspResponseCacheCapacity

Determines the maximum number of entries supported by the OCSP response local cache. The minimum value is 1.

Type: integer/int32

Constraints: Has Default Value: 1024, Minimum Value: 1, Maximum Value: 2147483647

ocspResponseCacheEnabled

Determines whether the OCSP response local cache is enabled.

Type: boolean

Constraints: Has Default Value: true

ocspResponseCacheRefreshPeriodPercent

Determines the refresh period for the OCSP response local cache, expressed as a percentage of the validity period of the response.

For example, for a validity period of 10 hours, a value of 10% specifies a refresh every 1 hour.

The validity period is determined by the OCSP response, and is calculated as the (next reported update time) - (this update time).

The valid range is 1 through 100.

Type: integer/int32

Constraints: Has Default Value: 100, Minimum Value: 1, Maximum Value: 100

ocspResponseTimeout

Determines the timeout for the OCSP response, expressed in seconds.

The valid range is 1 thru 300 seconds.

Type: integer/int64

Constraints: Has Default Value: 10, Minimum Value: 1, Maximum Value: 300

ocspTimeTolerance

Determines the time tolerance value for handling clock-skew differences between clients and responders, expressed in seconds.

The validity period of the response is extended both into the future and into the past by the specified amount of time, effectively widening the validity interval.

The value is ≥ 0 and ≤ 900 . The maximum allowed tolerance is 15 minutes.

Type: integer/int32

Constraints: Has Default Value: 0, Minimum Value: 0, Maximum Value: 900

tags

Return all tags on this Configuration MBean

Type: array of string

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.ClusterMBean

This bean represents a cluster in the domain. Servers join a cluster by calling `ServerMBean.setCluster` with the logical name of the cluster. A configuration may define zero or more clusters. They may be looked up by logical name.

The name of a cluster denotes its logical cluster name.

The properties of the `weblogic.management.configuration.ClusterMBean` entity are as follows:

WANSessionPersistenceTableName

Return the name of the table to be used for WAN session persistence.

Type: string

Constraints: Has Default Value: WLS_WAN_PERSISTENCE_TABLE

additionalAutoMigrationAttempts

A migratable server could fail to come up on every possible configured machine. This attribute controls how many further attempts, after the first one, should be tried.

Note that each attempt specified here indicates another full circuit of migrations amongst all the configured machines. So for a 3-server cluster, and the default value of 3, a total of 9 migrations will be attempted.

If it is set to -1, migrations will go on forever until the server starts.

Type: integer/int32

Constraints: Has Default Value: 3

asyncSessionQueueTimeout

Interval in seconds until the producer thread will wait for the `AsyncSessionQueue` to become unblocked. Should be similar to the `RequestTimeout` as that will determine the longest that the queue should remain full.

Type: integer/int32

Constraints: Has Default Value: 30

autoMigrationTableName

Return the name of the table to be used for server migration.

Type: string

Constraints: Has Default Value: ACTIVE

candidateMachinesForMigratableServers

The set of machines (and order of preference) on which Node Manager will restart failed servers. (Requires you to enable each server for automatic migration.)

Each server can specify a subset of these cluster-wide candidates, which limits the machines on which the server can be restarted. Servers can also specify their own order of preference.

Type: array of weblogic.management.configuration.MachineMBean references

Constraints: Restart Required

clientCertProxyEnabled

Specifies whether to honor the WL-Proxy-Client-Cert header coming with the request or not.

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

clusterAddress

The address that forms a portion of the URL a client uses to connect to this cluster, and that is used for generating EJB handles and entity EJB failover addresses. (This address may be either a DNS host name that maps to multiple IP addresses or a comma-separated list of single address host names or IP addresses.)

Defines the address to be used by clients to connect to this cluster. This address may be either a DNS host name that maps to multiple IP addresses or a comma separated list of single address host names or IP addresses. If network channels are configured, it is possible to set the cluster address on a per channel basis.

Type: string

clusterBroadcastChannel

Specifies the channel used to handle communications within a cluster. If no channel is specified the default channel is used.

ClusterBroadcastChannel is only are supported if the unicast messaging type is used.

Type: string

clusterMessagingMode

Specifies the messaging type used in the cluster.

Multicast messaging is provided for backwards compatibility.

Type: string

Constraints: Has Default Value: unicast, Legal Values: multicast, unicast

clusterType

Optimizes cross-cluster replication for the type of network that servers in the clusters use for administrative communication.

To enhance the reliability of HTTP sessions, you can configure servers in one cluster to replicate the session data to servers in a different cluster. In such an environment, configure the clusters to be one of the following types:

- man

If the clustered servers can send their data through a metro area network (man) in which latency is negligible. With this ClusterType value, servers replicate session state synchronously and in memory only. For example, when serverA in cluster1 starts an HTTP session, its backup server, serverB in cluster2, immediately replicates this session in memory to Server B.

- wan

If the clusters are far apart or send their data through a wide area network (wan) that experiences significant network latency. With this ClusterType value, a server replicates session state synchronously to the backup server in the same cluster and asynchronously to a server in the remote cluster. For example, when serverA in cluster1 starts an HTTP session, it sends the data to serverB in cluster1 and then asynchronously sends data to serverX in cluster 2. ServerX will persist the session state in the database.

If you persist session data in a replicating database, and if you prefer to use the database to replicate the data instead of WebLogic Server, choose a cluster type of wan and leave the remote cluster address undefined. WebLogic Server saves the session data to the local database and assumes that the database replicates data as needed.

Type: string

Constraints: Has Default Value: none, Legal Values: none, wan, man

coherenceClusterSystemResource

Coherence Cluster associated with this cluster.

Type: weblogic.management.configuration.CoherenceClusterSystemResourceMBean reference

Constraints: Restart Required

concurrentSingletonActivationEnabled

Specifies whether to allow the concurrent activation, deactivation, or restart of two or more singleton services.

Type: boolean

Constraints: Has Default Value: false

dataSourceForAutomaticMigration

The data source used by servers in the cluster during migration. (You must configure each Migratable Server within the cluster to use this data source.)

Type: weblogic.management.configuration.JDBCSystemResourceMBean reference

Constraints: Restart Required

dataSourceForJobScheduler

Data source required to support persistence of jobs scheduled with the job scheduler

Type: weblogic.management.configuration.JDBCSystemResourceMBean reference

Constraints: Restart Required

dataSourceForSessionPersistence

To support HTTP Session failover across data centers, a datasource is required to dump session state on disk.

Type: weblogic.management.configuration.JDBCSystemResourceMBean reference

Constraints: Restart Required

databaseLeasingBasisConnectionRetryCount

The maximum number of times Database Leasing will try to obtain a valid connection from the Data Source.

Type: integer/int32

Constraints: Has Default Value: 1, Minimum Value: 1

databaseLeasingBasisConnectionRetryDelay

The length of time, in milliseconds, Database Leasing will wait before attempting to obtain a new connection from the Data Source when a connection has failed.

Type: integer/int64

Constraints: Has Default Value: 1000

defaultLoadAlgorithm

Defines the algorithm to be used for load-balancing between replicated services if none is specified for a particular service. The round-robin algorithm cycles through a list of WebLogic Server instances in order. Weight-based load balancing improves on the round-robin algorithm by taking into account a pre-assigned weight for each server. In random load balancing, requests are routed to servers at random.

Type: string

Constraints: Has Default Value: round-robin, Legal Values: round-robin, weight-based, random, round-robin-affinity, weight-based-affinity, random-affinity

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

fencingGracePeriodMillis

During automatic migration, if the Cluster Master determines a server to be dead, it waits for this period of time (in milliseconds) before the Cluster Master migrates the service to another server in the cluster.

Type: integer/int32

Constraints: Has Default Value: 30000

frontendHTTPPort

The name of the HTTP port to which all redirected URLs will be sent.

Sets the FrontendHTTPPort for the default webserver (not virtual hosts) for all the servers in the cluster. Provides a method to ensure that the webapp will always have the correct PORT information, even when the request is coming through a firewall or a proxy. If this parameter is configured, the HOST header will be ignored and the information in this parameter will be used in its place, when constructing the absolute urls for redirects.

Type: integer/int32

Constraints: Has Default Value: 0

frontendHTTPSPort

The name of the secure HTTP port to which all redirected URLs will be sent.

Sets the FrontendHTTPSPort for the default webserver (not virtual hosts) for all the servers in the cluster. Provides a method to ensure that the webapp will always have

the correct PORT information, even when the request is coming through a firewall or a proxy. If this parameter is configured, the HOST header will be ignored and the information in this parameter will be used in its place, when constructing the absolute urls for redirects.

Type: integer/int32

Constraints: Has Default Value: 0

frontendHost

The name of the host to which all redirected URLs will be sent.

Sets the HTTP FrontendHost for the default webserver (not virtual hosts) for all the servers in the cluster. Provides a method to ensure that the webapp will always have the correct HOST information, even when the request is coming through a firewall or a proxy. If this parameter is configured, the HOST header will be ignored and the information in this parameter will be used in its place, when constructing the absolute urls for redirects.

Type: string

Constraints: Has Default Value: null

greedySessionFlushInterval

Interval in seconds until HTTP Sessions are periodically flushed to secondary server.

Type: integer/int32

Constraints: Has Default Value: 3

healthCheckIntervalMillis

Interval in milliseconds at which Migratable Servers and Cluster Masters prove their liveness via the database.

Type: integer/int32

Constraints: Has Default Value: 10000

healthCheckPeriodsUntilFencing

Maximum number of periods that a cluster member will wait before timing out a Cluster Master and also the maximum number of periods the Cluster Master will wait before timing out a Migratable Server.

Type: integer/int32

Constraints: Has Default Value: 3, Minimum Value: 2

httpTraceSupportEnabled

Returns the value of HttpTraceSupportEnabled.

Type: boolean

Constraints: Has Default Value: false

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

idlePeriodsUntilTimeout

Maximum number of periods that a cluster member will wait before timing out a member of a cluster.

Maximum number of periods that a cluster member will wait before timing out a member of a cluster.

Type: integer/int32

Constraints: Has Default Value: 3, Minimum Value: 3

interClusterCommLinkHealthCheckInterval

If the cluster link between two clusters goes down, a trigger will run periodically to see if the link is restored. The duration is specified in milliseconds.

Type: integer/int32

Constraints: Has Default Value: 30000

jobSchedulerTableName

The table name to use for storing timers active with the job scheduler

Type: string

Constraints: Has Default Value: WEBLOGIC_TIMERS

memberDeathDetectorEnabled

Enables faster Automatic Service Migration times with Database Leasing Basis.

Type: boolean

Constraints: Has Default Value: false

memberWarmupTimeoutSeconds

Maximum number of seconds that a cluster member will wait to discover and synchronize with other servers in the cluster. Normally, the member will be able to sync in 30 seconds. If the value of this attribute is higher, that does not necessarily mean that it will take longer for the member to warmup. Instead it defines an upper bound on the time that a server will wait to sync with the servers that it has discovered. If the value is set 0, servers will not attempt to discover other running server in the cluster during server initialization

Type: integer/int32

Constraints: Minimum Value: 0

messageOrderingEnabled

Forces unicast messages to be processed in order. There are scenarios where JMS may update JNDI very frequently. It will result in a lot of messages over unicast. Due to the close proximity of messages the probability of out of order handling of messages increases which would trigger frequent state dumps. Frequent JNDI tree refresh may result in NameNotFoundException. Use this property to prevent out of order handling of messages.

Type: boolean

Constraints: Has Default Value: true

migratableTargets

Returns all the MigratableTargets for this cluster

Type: array of weblogic.management.configuration.MigratableTargetMBean references

Constraints: Read Only

migrationBasis

Controls the mechanism used for server and service migration.

- **Database** -- Requires the availability of a high-availability database, such as Oracle RAC, to store leasing information.
- **Consensus** -- Stores the leasing information in-memory within a cluster member. This option requires Node Manager to be configured and running.

Note: Within a WebLogic Server installation, you can only use one type of leasing. Although it is possible to implement multiple features that use leasing within your environment, each must use the same kind of leasing.

Type: string

Constraints: Has Default Value: database, Legal Values: database, consensus

millisToSleepBetweenAutoMigrationAttempts

Controls how long of a pause there should be between the migration attempts described in `getAdditionalAutoMigrationAttempts()`. Note that this delay only happens when the server has failed to come up on every machine.

Type: integer/int64

Constraints: Has Default Value: 180000

multicastAddress

The multicast address used by cluster members to communicate with each other.

The valid range is from from 224.0.0.0 to 239.255.255.255. The default value used by WebLogic Server is 239.192.0.0. You should avoid using multicast addresses in the range x.0.0.1

This address should be unique to this cluster and should not be shared by other applications.

Type: string

Constraints: Has Default Value: 239.192.0.0

multicastBufferSize

The multicast socket send/receive buffer size (at least 64 kilobytes).

Returns the multicast socket send/receive buffer size.

Type: integer/int32

Constraints: Has Default Value: 64, Minimum Value: 64

multicastDataEncryption

Enables multicast data to be encrypted. Only the multicast data is encrypted. Multicast header information is not encrypted.

Type: boolean

Constraints: Has Default Value: false

multicastPort

The multicast port (between 1 and 65535) used by cluster members to communicate with each other.

Defines the multicast port used by cluster members to communicate with each other.

Type: integer/int32

Constraints: Has Default Value: 7001, Minimum Value: 1, Maximum Value: 65535

multicastSendDelay

The amount of time (between 0 and 250 milliseconds) to delay sending message fragments over multicast in order to avoid OS-level buffer overflow.

Defines the number of milliseconds to delay sending message fragments over multicast in order to avoid OS-level buffer overflow.

Type: integer/int32

Constraints: Has Default Value: 3, Minimum Value: 0, Maximum Value: 250

multicastTTL

The number of network hops (between 1 and 255) that a cluster multicast message is allowed to travel.

Defines the number of network hops that a cluster multicast message is allowed to travel. 1 restricts the cluster to one subnet.

Type: integer/int32

Constraints: Has Default Value: 1, Minimum Value: 1, Maximum Value: 255

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

Name=user-specified-name

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`; carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

numberOfServersInClusterAddress

Number of servers to be listed from this cluster when generating a cluster address automatically. This setting has no effect if Cluster Address is explicitly set.

Type: integer/int32

Constraints: Has Default Value: 3, Minimum Value: 1

oneWayRmiForReplicationEnabled

Indicates if one-way RMI is being used for replication. One-way RMI also requires configuring replication ports on each server in the cluster.

Type: boolean

Constraints: Has Default Value: false

persistSessionsOnShutdown

When shutting down servers, sessions are not updated. If the primary and secondary servers of a session are shut down with no session updates, the session will be lost.

Turning on `PersistSessionsOnShutdown` will save any active sessions to the database specified in `ClusterMBean#getDataSourceForSessionPersistence()` when a server is shutdown. The sessions will not be written at any other time. (For example, they are not saved via this mechanism if there is a server crash.)

This attribute is applicable both to session persistence on server shutdown or session persistence across a WAN.

Rolling upgrade can potentially have a bad interaction with traditional in-memory session replication. As managed servers are shutdown and upgraded, in-memory servlet sessions will be lost if both primary and secondary are rebooted before a new request arrives for the session.

Type: boolean

remoteClusterAddress

Set the foreign cluster. Cluster infrastructure uses this address to connect to foreign cluster for HTTP Session WAN/MAN failover.

Type: string

replicationChannel

The channel name to be used for replication traffic. Cluster infrastructure uses this channel to send updates for HTTP sessions and stateful session beans. If none is set then the default channel will be used.

In order for this feature to work, the named channel must exist on all members of the cluster and must be configured to use the same protocol. It is valid for the selected channel to be configured to use a secure protocol.

Type: string

Constraints: Has Default Value: `ReplicationChannel`

replicationTimeoutEnabled

Indicates if timeout should be applied to session replication calls.

Type: boolean

Constraints: Has Default Value: `true`

secureReplicationEnabled

Servers in a cluster replicate session data. If a replication channel is defined then the session data will be sent using the replication channel protocol and secured replication settings will be ignored. If no replication channel is defined and secured replication is enabled then session data for in-memory replication will be sent over SSL using the default secured channel. However, this added security for replication traffic comes with a significant cluster performance degradation. It should only be enabled if security is of greater concern than performance degradation.

Type: boolean

Constraints: Has Secure Value: `true`, Has Default Value: `false`

servers

The servers which have declared membership in this cluster.

Type: array of `weblogic.management.configuration.ServerMBean` references

Constraints: Read Only

serviceActivationRequestResponseTimeout

The maximum time, in milliseconds seconds, for services to wait for response from cluster members.

Type: integer/int32

Constraints: Has Default Value: 0

serviceAgeThresholdSeconds

The number of seconds (between 0 and 65534) by which the age of two conflicting services must differ before one is considered older than the other.

Defines the number of seconds by which the age of two conflicting services must differ before one is considered older than the other.

Type: integer/int32

Constraints: Has Default Value: 180, Minimum Value: 0, Maximum Value: 65534

sessionFlushInterval

Interval in seconds until HTTP Sessions are periodically flushed to the backup cluster to dump session state on disk.

Type: integer/int32

Constraints: Has Default Value: 180

sessionFlushThreshold

When number of sessions to be flushed reaches this threshold limit, sessions will be flushed to the backup cluster before the flush interval. This helps the server to flush sessions faster under load.

Type: integer/int32

Constraints: Has Default Value: 10000

sessionLazyDeserializationEnabled

Enables increased efficiency with session replication. Enabling this attribute should be used only when configuring a WebLogic domain for Oracle Exalogic.

Type: boolean

sessionStateQueryProtocolEnabled

Indicates if session state query protocol is enabled. The Session State Query protocol will query the local cluster for the location of a session state instance if a request arrives at a server that is neither the primary or secondary server.

Type: boolean

Constraints: Has Default Value: false

sessionStateQueryRequestTimeout

The maximum time, in seconds, for session state query request to wait for response from cluster members.

Type: integer/int32

Constraints: Has Default Value: 30, Minimum Value: 1

singletonServiceRequestTimeout

The maximum time, in milliseconds, for service activation requests will wait for response from cluster members.

A value of means that the request will wait indefinitely to complete.

Type: integer/int32

Constraints: Has Default Value: 30000

siteName

The name of the site this cluster is associated with.

Type: string

tags

Return all tags on this Configuration MBean

Type: array of string

txnAffinityEnabled

If enabled, a server's transaction requests go to servers in the cluster that are already participating in the global transaction.

Type: boolean

Constraints: Has Default Value: false

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

unicastReadTimeout

The specified read timeout, in milliseconds, on a unicast connection. A timeout of zero is interpreted as an infinite timeout, that is blocking read forever.

Type: integer/int32

Constraints: Has Default Value: 15000

weblogicPluginEnabled

Specifies if this cluster will receive requests from a proxy plug-in or `HttpClusterServlet`

Set this attribute to `true` if the cluster will receive requests from a proxy plug-in or `HttpClusterServlet`. A call to `getRemoteAddr` will return the address of the browser client from the proprietary `WL-Proxy-Client-IP` header instead of the Web server.

Set this attribute to `false` to disable the `weblogic-plugin-enabled` parameter, `weblogic-plugin-enabled=false`, in the `config.xml` file.

Note: If you are using Oracle HTTP Server, the WebLogic Proxy Plug-In, or Oracle Traffic Director to distribute client requests to a Managed Server or a cluster, Oracle recommends setting this attribute to `true`

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

weblogic.management.configuration.CoherenceCacheConfigMBean

Information that represents a Coherence cache configuration.

The properties of the `weblogic.management.configuration.CoherenceCacheConfigMBean` entity are as follows:

JNDIName

The JNDI name this resource will be bound to.

Type: string

cacheConfigurationFile

Return the cache configuration file being used by this CoherenceCacheConfigMBean.

Type: string

compatibilityName

This is only set for beans created as a result of conversion from an 8.1 application configured using ApplicationMBean and ComponentMBean.

Standalone modules in 8.1 have both an ApplicationMBean name and ComponentMBean name. This attribute stores the name of the latter, to be used when the server creates the transient ComponentMBean for backward compatibility.

Type: string

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

moduleType

The values match those defined by jsr88. This attribute may move to another MBean.

Type: string

name

Unique identifier for this bean instance.

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (config.xml) as XML PCDATA. All left angle brackets (<) are converted to the XML entity <. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

tags

Return all tags on this Configuration MBean

Type: array of string

targets

You must select a target on which an MBean will be deployed from this list of the targets in the current domain on which this item can be deployed. Targets must be either servers or clusters. The deployment will only occur once if deployments overlap.

Type: array of weblogic.management.configuration.TargetMBean references

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.CoherenceClusterSystemResourceMBean

This bean defines a system-level Coherence cluster resource. It links to a separate descriptor that specifies the definition.

The properties of the weblogic.management.configuration.CoherenceClusterSystemResourceMBean entity are as follows:

clusterHosts

The list of hostnames of the managed servers belonging to this Coherence cluster.

Type: array of string

Constraints: Read Only

compatibilityName

This is only set for beans created as a result of conversion from an 8.1 application configured using ApplicationMBean and ComponentMBean.

Standalone modules in 8.1 have both an ApplicationMBean name and ComponentMBean name. This attribute stores the name of the latter, to be used when the server creates the transient ComponentMBean for backward compatibility.

Type: string

customClusterConfigurationFileName

The external custom Coherence cluster configuration file.

Type: string

Constraints: Read Only

customConfigFileLastUpdatedTime

The time when the custom configuration file used by the cluster was last updated

Type: integer/int64

Constraints: Read Only

deploymentOrder

An integer value that indicates when this unit is deployed, relative to other deployable units on a server, during startup.

Units with lower values are deployed before those with higher values.

Type: integer/int32

Constraints: Has Default Value: 100

deploymentPrincipalName

A string value that indicates the principal that should be used when deploying the file or archive during startup and shutdown. This principal will be used to set the current subject when calling out into application code for interfaces such as `ApplicationLifecycleListener`. If no principal name is specified, then the anonymous principal will be used.

Type: string

descriptorFileName

The name of the file that contains the module configuration. By default the file resides in the `DOMAIN_DIR/config/coherence/bean_name` directory.

The module file derives its name from the bean name using the following pattern:

```
<beanName>.xml
```

Note that this is a read-only property that can only be set when the bean is created.

Type: string

Constraints: Read Only

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to `config.xml`

Type: boolean

Constraints: Read Only, Has Default Value: false

federationRemoteClusterListenPort

The Coherence Cluster Listen Port of the remote participant.

Type: integer/int32

Constraints: Read Only

federationRemoteClusterName

The Coherence Cluster Name of the remote participant cluster.

Type: string

Constraints: Read Only

federationRemoteParticipantHosts

The list of remote participant hosts, who will be added as participants in the federation topology.

Type: array of string

Constraints: Read Only

federationTopology

The federation topology.

Type: string

Constraints: Read Only

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

moduleType

The values match those defined by jsr88. This attribute may move to another MBean.

Type: string

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

Name=user-specified-name

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

persistenceActiveDirectory

The active directory for the default persistence environment. If no value is specified, the directory which will be used is the coherence/active sub-directory under Domain Home directory.

Type: string

Constraints: Read Only

persistenceDefaultMode

The default persistence mode.

Type: string

Constraints: Read Only

persistenceSnapshotDirectory

The snapshot directory for the default persistence environment. If no value is specified, the directory which will be used is coherence/snapshots sub-directory under Domain Home directory.

Type: string

Constraints: Read Only

persistenceTrashDirectory

The trash directory for the default persistence environment. If no value is specified, the directory which will be used is coherence/trash sub-directory under Domain Home directory.

Type: string

Constraints: Read Only

reportGroupFile

Get the report group file representing the superset of runtime metrics to be collected for this cluster.

Type: string

Constraints: Has Default Value: em/metadata/reports/coherence/report-group.xml

resource

Return the Descriptor for the system resource. This should be overridden by the derived system resources.

Type: weblogic.descriptor.DescriptorBean reference

Constraints: Read Only

sourcePath

Type: string

tags

Return all tags on this Configuration MBean

Type: array of string

targets

You must select a target on which an MBean will be deployed from this list of the targets in the current domain on which this item can be deployed. Targets must be either servers or clusters. The deployment will only occur once if deployments overlap.

Type: array of weblogic.management.configuration.TargetMBean references

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

usingCustomClusterConfigurationFile

Specifies whether you are using a custom external Coherence cluster configuration file.

Type: boolean

weblogic.management.configuration.CoherenceManagementAddressProviderMBean

This class holds the connection information needed to connect to a Coherence server. Copyright (c) 2014,2015, Oracle and/or its affiliates. All Rights Reserved.

The properties of the weblogic.management.configuration.CoherenceManagementAddressProviderMBean entity are as follows:

address

The IP address/Host

Type: string

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

Name=user-specified-name

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

port

Return the server port

Type: integer/int32

Constraints: Minimum Value: 1, Maximum Value: 65535

tags

Return all tags on this Configuration MBean

Type: array of string

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.CoherenceManagementClusterMBean

This class is used to hold JMX information about a coherence cluster in both the standalone case and WLS managed cluster case.

The properties of the weblogic.management.configuration.CoherenceManagementClusterMBean entity are as follows:

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

Name=user-specified-name

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

password

Get JMX connection password

Type: string

Constraints: Encrypted

reportGroupFile

Get the report group file representing the superset of metrics this bean will gather.

Type: string

Constraints: Has Default Value: `em/metadata/reports/coherence/report-group.xml`

tags

Return all tags on this Configuration MBean

Type: array of string

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

username

Get the JMX connection username

Type: string

weblogic.management.configuration.CoherenceMemberConfigMBean

This class represents Coherence Operational Configuration for a WLS Server that is part of a Coherence Cluster.

The properties of the `weblogic.management.configuration.CoherenceMemberConfigMBean` entity are as follows:

coherenceWebFederatedStorageEnabled

Specifies whether Federated Cache Storage is enabled for the Coherence Web cluster member

Type: boolean

Constraints: Has Default Value: false

coherenceWebLocalStorageEnabled

Specifies whether Local Storage is enabled for the Coherence Web cluster member

Type: boolean

Constraints: Has Default Value: false

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

localStorageEnabled

Specifies whether or not this member will contribute storage to the Coherence cluster i.e. maintain partitions. This attribute is used only when the WebLogic Server is not part of a WLS Cluster.

Type: boolean

Constraints: Has Default Value: true

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

`Name=user-specified-name`

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`.

Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

rackName

Specifies the location within a geographic site where this member is hosted.

Type: string

roleName

Specifies a name used to logically group similar members.

Type: string

siteName

Specifies the name of the geographic site where this member is hosted.

Type: string

tags

Return all tags on this Configuration MBean

Type: array of string

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

unicastListenAddress

The IP address for the Coherence unicast listener.

Type: string

unicastListenPort

The port for the Coherence unicast listener. A value of 0 indicates that the unicast listen port value will be assigned automatically to an ephemeral port.

Type: integer/int32

Constraints: Minimum Value: 0, Maximum Value: 65535

unicastPortAutoAdjustAttempts

Get the upper bound of the unicast port. A positive value indicates the unicast port is automatically incremented if the specified port cannot be bound because it is already in use.

Type: integer/int32

Constraints: Minimum Value: 0, Maximum Value: 65535

weblogic.management.configuration.CoherencePartitionCacheConfigMBean

The CoherencePartitionCacheConfigMBean is used to define which Coherence caches are shared/not-shared in an MT environment as well as specific cache properties that apply to deployments underneath a partition.

Note: the Name attribute is inherited from ConfigurationMBean and is a key only.

The properties of the weblogic.management.configuration.CoherencePartitionCacheConfigMBean entity are as follows:

applicationName

The name of the GAR application that this setting should apply to.

Type: string

cacheName

The name of the cache that the settings should apply to.

Type: string

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

Name=user-specified-name

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

shared

Specifies whether you want this cache to be shared.

Type: boolean

tags

Return all tags on this Configuration MBean

Type: array of string

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.CoherencePartitionCachePropertyMBean

The CoherencePartitionCachePropertyMBean is used to define specific properties, name and value that apply to a CoherenceMTCacheConfigMBean.

Note: the Name attribute is inherited from ConfigurationMBean.

The properties of the weblogic.management.configuration.CoherencePartitionCachePropertyMBean entity are as follows:

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

Name=user-specified-name

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

tags

Return all tags on this Configuration MBean

Type: array of string

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

value

Get the value of the parameter

Type: string

weblogic.management.configuration.CoherenceServerMBean

This class represents a Coherence stand-alone server.

The properties of the weblogic.management.configuration.CoherenceServerMBean entity are as follows:

autoRestart

Specifies whether the Node Manager can automatically restart this server if it crashes or otherwise goes down unexpectedly.

Type: boolean

Constraints: Has Default Value: true

coherenceClusterSystemResource

The system-level Coherence cluster resource associated with this server.

Type: weblogic.management.configuration.CoherenceClusterSystemResourceMBean reference

Constraints: Restart Required

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

machine

The WebLogic Server host computer (machine) on which this server is meant to run.

If you want to use a Node Manager to start this server, you must assign the server to a machine and you must configure the machine for the Node Manager.

You cannot change this value if a server instance is already running.

Type: weblogic.management.configuration.MachineMBean reference

Constraints: Restart Required

name

An alphanumeric name for this server instance. (Spaces are not valid.)

The name must be unique for all configuration objects in the domain. Within a domain, each server, machine, cluster, JDBC connection pool, virtual host, and any other resource type must be named uniquely and must not use the same name as the domain.

The server name is not used as part of the URL for applications that are deployed on the server. It is for your identification purposes only. The server name displays in the Administration Console, and if you use WebLogic Server command-line utilities or APIs, you use this name to identify the server.

After you have created a server, you cannot change its name. Instead, clone the server and provide a new name for the clone.

Type: string

Constraints: Read Only

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

restartDelaySeconds

The number of seconds the Node Manager should wait before restarting this server.

After killing a server process, the system might need several seconds to release the TCP port(s) the server was using. If Node Manager attempts to restart the Managed Server while its ports are still active, the startup attempt fails.

If AutoMigration is enabled and RestartDelaySeconds is 0, the RestartDelaySeconds is automatically set to the lease time. This prevents the server from failing to restart after migration when the previous lease is still valid.

Type: integer/int32

Constraints: Has Default Value: 0, Minimum Value: 0, Maximum Value: 2147483647

restartIntervalSeconds

The number of seconds during which this server can be restarted, up to the number of times specified in RestartMax.

Type: integer/int32

Constraints: Has Default Value: 3600, Minimum Value: 300, Maximum Value: 2147483647

restartMax

The number of times that the Node Manager can restart this server within the interval specified in RestartIntervalSeconds.

Type: integer/int32

Constraints: Has Default Value: 2, Minimum Value: 0, Maximum Value: 2147483647

tags

Return all tags on this Configuration MBean

Type: array of string

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

unicastListenAddress

The IP address for the cluster unicast listener.

This attribute may be used to override the value of the referenced Coherence cluster.

Type: string

unicastListenPort

The port for the cluster unicast listener.

Type: integer/int32

Constraints: Minimum Value: 1, Maximum Value: 65535

unicastPortAutoAdjustAttempts

Gets the upper bound of the unicast port. A positive value indicates the unicast port is automatically incremented if the specified port cannot be bound because it is already in use.

Type: integer/int32

Constraints: Has Default Value: 65535

weblogic.management.configuration.CoherenceServerStartMBean

This bean is used to configure the attributes necessary to start up a server on a remote machine.

The following describes how NodeManager applies each property when starting the Coherence server.

#getJavaVendor

The NodeManager does not pass this value invoking a java command line to start the server. It does pass this value in the environment variable JAVA_VENDOR to the start script.

#getJavaHome

This value can also be specified conveniently in the nodemanager .properties file using the coherence.startup.JavaHome or property. The NodeManager will pass this value to a start script using the JAVA_HOME environment variable. When issuing a java command line to start the server, the NodeManager will use the java executable from the specified location.

#getClassPath

The NodeManager will pass this value to a start script using the JAVA_OPTIONS environment variable containing -Djava.class.path. When issuing a java command line to start the server, the NodeManager will pass -Djava.class.path.

#getMWHome

This value can also be specified conveniently in the nodemanager .properties file using the coherence.startup.MWHome property. The NodeManager does not pass this value directly when starting a server. However, it uses this value to construct an appropriate classpath for starting the server.

#getArguments

This value can also be specified conveniently in the nodemanager .properties file using the coherence.startup.Arguments property. The NodeManager will pass this value to a start script using the JAVA_OPTIONS environment variable. When issuing a java command line to start the server, the NodeManager will pass the arguments as options.

The properties of the weblogic.management.configuration.CoherenceServerStartMBean entity are as follows:

MWHome

The MWHome directory (path on the machine running Node Manager) to use when starting this server.

Specify the directory on the Node Manager machine under which all of Oracle's MW products were installed. For example, c:\Oracle\Middleware\

Type: string

arguments

The arguments to use when starting this server.

These are the first arguments appended immediately after java portion of the startup command. For example, you can set Java heap memory or specify any weblogic.nodemanager.server.provider.WeblogicCacheServer option.

Separate arguments with a space.

Type: string

classPath

The classpath (path on the machine running Node Manager) to use when starting this server.

If you need to add user classes to the classpath, in addition you will need to add the following: FEATURES_HOME/weblogic.server.modules.coherence.server_10.3.4.0.jar:COHERENCE_HOME/lib/coherence.jar

where FEATURES_HOME is the features directory (typically \$MW_HOME/modules/features) and COHERENCE_HOME the coherence directory (typically \$MW_HOME/coherence_3.6) on the Node Manager machine. If you do not specify a classpath the above will be used automatically.

The operating system determines which character separates path elements. On Windows, use a semicolon (;). On UNIX a colon (:).

Type: string

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

javaHome

The Java home directory (path on the machine running Node Manager) to use when starting this server.

Specify the parent directory of the JDK's bin directory. For example, `c:\bea\jdk141`

Type: string

javaVendor

The Java Vendor value to use when starting this server.

If the server is part of a cluster and configured for automatic migration across possibly different platforms with different vendors providing the JDKs, then, both `JavaVendor` and `JavaHome` should be set in the generated configuration file instead.

Type: string

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's

`javax.management.ObjectName`

`Name=user-specified-name`

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`;

Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

rootDirectory

The directory that this server uses as its root directory. This directory must be on the computer that hosts the Node Manager. If you do not specify a Root Directory value, the domain directory is used by default.

Type: string

tags

Return all tags on this Configuration MBean

Type: array of string

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.CoherenceTierMBean

This class represents Coherence Tier. A Coherence Tier is formed by one WLS Cluster.

The properties of the weblogic.management.configuration.CoherenceTierMBean entity are as follows:

coherenceWebFederatedStorageEnabled

Specifies whether Federated Cache Storage is enabled for the Coherence Web cluster member

Type: boolean

Constraints: Has Default Value: false

coherenceWebLocalStorageEnabled

Specifies whether Local Storage is enabled for the Coherence*Web cluster tier

Type: boolean

Constraints: Has Default Value: false

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

localStorageEnabled

Specifies whether Local Storage is enabled

Type: boolean

Constraints: Has Default Value: true

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

Name=user-specified-name

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`.

Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

tags

Return all tags on this Configuration MBean

Type: array of string

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.ConfigurationPropertyMBean

Encapsulates information about a property, such as its value and whether it is encrypted.

The properties of the weblogic.management.configuration.ConfigurationPropertyMBean entity are as follows:

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

encryptValueRequired

Specifies whether the property should be encrypted.

By default, the value of a property is not encrypted and anyone using the Administration Console can view the value of the property. If this attribute is set to true, then the value of the property on the Administration Console will be set to all asterisks.

Type: boolean

Constraints: Has Default Value: false

encryptedValue

Specifies the decrypted value of the property.

Note: In release 10.3.1 of WebLogic Server, the behavior of the MBean encryption algorithm changed. In previous releases, if the newly set value was identical to the existing value, the encrypted value did not change. That is, you would always get the same encrypted value for a given password. The action was not treated as a (non-dynamic) change. The behavior has been modified so that use of the setter on any existing encrypted value is considered to be a (dynamic) change, regardless of whether the new value matches the old value. Therefore, even if you set the password to the existing value, the setter now generates a different encrypted value for the given password.

Use this attribute if you have specified that property should be encrypted.

Type: string

Constraints: Encrypted, Has Default Value:

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

Name=user-specified-name

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

tags

Return all tags on this Configuration MBean

Type: array of string

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

value

Specifies the value of the property.

If the property is encrypted, then attribute is null and one should use the `EncryptedValue` attribute to get the decrypted value.

Type: string

Constraints: Has Default Value:

weblogic.management.configuration.ContextCaseMBean

This mbean defines the mapping between the current context (security principal, group etc) and the request class to use.

The properties of the `weblogic.management.configuration.ContextCaseMBean` entity are as follows:

deploymentOrder

A priority that the server uses to determine when it deploys an item. The priority is relative to other deployable items of the same type.

For example, the server prioritizes and deploys all EJBs before it prioritizes and deploys startup classes.

Items with the lowest Deployment Order value are deployed first. There is no guarantee on the order of deployments with equal Deployment Order values. There is no guarantee of ordering across clusters.

Type: integer/int32

Constraints: Has Default Value: 1000, Minimum Value: 0, Maximum Value: 2147483647

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

groupName

The name of the user group whose requests are to be processed by the request class with the name specified in RequestClassName.

Type: string

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

`Name=user-specified-name`

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

requestClassName

The name of the request class to be used for processing requests for the specified user and/or group.

Type: string

tags

Return all tags on this Configuration MBean

Type: array of string

targets

You must select a target on which an MBean will be deployed from this list of the targets in the current domain on which this item can be deployed. Targets must be either servers or clusters. The deployment will only occur once if deployments overlap.

Type: array of weblogic.management.configuration.TargetMBean references

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

userName

The name of the user whose requests are to be processed by the request class with the name specified in RequestClassName.

Type: string

weblogic.management.configuration.ContextRequestClassMBean

This mbean defines the mapping between the current context (security principal, group) and the request class to use.

ContextRequestClass provides a mapping between security names/groups and request classes. During work schedule, the exact request class is determined by looking at the security information of the caller. ContextRequestClass is not a request class by itself and is used to hold the mapping of request classes.

The properties of the weblogic.management.configuration.ContextRequestClassMBean entity are as follows:

deploymentOrder

A priority that the server uses to determine when it deploys an item. The priority is relative to other deployable items of the same type.

For example, the server prioritizes and deploys all EJBs before it prioritizes and deploys startup classes.

Items with the lowest Deployment Order value are deployed first. There is no guarantee on the order of deployments with equal Deployment Order values. There is no guarantee of ordering across clusters.

Type: integer/int32

Constraints: Has Default Value: 1000, Minimum Value: 0, Maximum Value: 2147483647

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's

`javax.management.ObjectName`

`Name=user-specified-name`

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as

XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`.

Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

tags

Return all tags on this Configuration MBean

Type: array of string

targets

You must select a target on which an MBean will be deployed from this list of the targets in the current domain on which this item can be deployed. Targets must be either servers or clusters. The deployment will only occur once if deployments overlap.

Type: array of `weblogic.management.configuration.TargetMBean` references

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.CpuUtilizationMBean

A `{@code CpuUtilizationMBean}` represents a resource consumption management policy for the "CPU Utilization" resource type.

The "CPU Utilization" resource type tracks the percentage of CPU time utilized by a Domain Partition with respect to the available CPU time to the Server runtime.

Triggers (Usage limits) and Fair share policies can be defined for a "CPU Utilization" resource type through this MBean.

The valid set of recourse action types for the "CPU Utilization" resource type are:

- notify
- slow

- shutdown

The trigger value must be in the range [0..100]%.
 The properties of the weblogic.management.configuration.CpuUtilizationMBean entity are as follows:

The properties of the weblogic.management.configuration.CpuUtilizationMBean entity are as follows:

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

Name=user-specified-name

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

tags

Return all tags on this Configuration MBean

Type: array of string

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.CustomResourceMBean

A CustomResource is an untyped SystemResource for which creator of the bean defines the name of the class that will be used when the resource is deployed on the managed server.

The properties of the weblogic.management.configuration.CustomResourceMBean entity are as follows:

compatibilityName

This is only set for beans created as a result of conversion from an 8.1 application configured using ApplicationMBean and ComponentMBean.

Standalone modules in 8.1 have both an ApplicationMBean name and ComponentMBean name. This attribute stores the name of the latter, to be used when the server creates the transient ComponentMBean for backward compatibility.

Type: string

deploymentOrder

An integer value that indicates when this unit is deployed, relative to other deployable units on a server, during startup.

Units with lower values are deployed before those with higher values.

Type: integer/int32

Constraints: Has Default Value: 100

deploymentPrincipalName

A string value that indicates the principal that should be used when deploying the file or archive during startup and shutdown. This principal will be used to set the current subject when calling out into application code for interfaces such as ApplicationLifecycleListener. If no principal name is specified, then the anonymous principal will be used.

Type: string

descriptorBeanClass

Returns the interface of the bean that is returned by the #getResource method.

Type: string

descriptorFileName

The name of the file that contains the module. By default the file resides in the DOMAIN_DIR/config directory.

By default, the file name is derived from the bean name using the following pattern:

```
<beanName>.xml
```

Note that this is a read-only property that can only be set when the bean is created.

Type: string

Constraints: Read Only

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

moduleType

The values match those defined by jsr88. This attribute may move to another MBean.

Type: string

name

Unique identifier for this bean instance.

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

resource

Return the Descriptor for the system resource. This should be overridden by the derived system resources.

Type: `weblogic.descriptor.DescriptorBean` reference

Constraints: Read Only

resourceClass

This is the name of the class that is used to manage the lifecycle of the resource. An instance of the ResourceClass is created and is passed the DescriptorBean. If this value is not set then the resource does not participate in the deployment lifecycle and simply represent a distribution of configuration information to be used by other subsystems.

Type: string

sourcePath

Type: string

tags

Return all tags on this Configuration MBean

Type: array of string

targets

You must select a target on which an MBean will be deployed from this list of the targets in the current domain on which this item can be deployed. Targets must be either servers or clusters. The deployment will only occur once if deployments overlap.

Type: array of `weblogic.management.configuration.TargetMBean` references

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.DataSourceLogFileMBean

Defines the logging configuration for a DataSource.

The properties of the weblogic.management.configuration.DataSourceLogFileMBean entity are as follows:

bufferSizeKB

Gets the underlying log buffer size in kilobytes

Type: integer/int32

Constraints: Has Default Value: 8

dateFormatPattern

The date format pattern used for rendering dates in the log. The DateFormatPattern string conforms to the specification of the `java.text.SimpleDateFormat` class.

Type: string

Constraints: Legal Null: true

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

fileCount

The maximum number of log files that the server creates when it rotates the log. This number does not include the file that the server uses to store current messages. (Requires that you enable Number of Files Limited.)

Type: integer/int32

Constraints: Has Default Value: 7, Has Production Mode Default Value: 100, Minimum Value: 1, Maximum Value: 99999

fileMinSize

The size (1 - 2097150 kilobytes) that triggers the server to move log messages to a separate file. The default is 500 kilobytes. After the log file reaches the specified minimum size, the next time the server checks the file size, it will rename the current log file as `SERVER_NAME.lognnnn` and create a new one to store subsequent messages. (Requires that you specify a file rotation type of Size.)

Type: integer/int32

Constraints: Has Default Value: 500, Has Production Mode Default Value: 5000, Minimum Value: 1, Maximum Value: 2097150

fileName

The name of the file that stores datasource profile records. Usually it is a computed value based on the name of the parent of this MBean. For example, for a datasource profile log, it is `serverName.log`

However, if the name of the parent cannot be obtained, the file name is `weblogic.log`. If you specify a relative pathname, it is interpreted as relative to the server's root directory.

To include a time and date stamp in the file name when the log file is rotated, add `java.text.SimpleDateFormat` variables to the file name. Surround each variable with percentage (%) characters.

For example, if the file name is defined to be `myjmsserver_%yyyy%_%MM%_%dd%_%hh%_%mm%.log`, the log file will be named `myserver_yyyy_mm_dd_hh_mm.log`

When the log file is rotated, the rotated file name contains the date stamp. For example, if the log file is rotated on 2 April, 2005 at 10:05 AM, the log file that contains the old messages will be named `myserver_2005_04_02_10_05.log`

If you do not include a time and date stamp, the rotated log files are numbered in order of creation. For example, `myjmsserver.log00007`

Type: string

fileTimeSpan

The interval (in hours) at which the server saves old log messages to another file. (Requires that you specify a file rotation type of `TIME`.)

Type: integer/int32

Constraints: Has Default Value: 24, Minimum Value: 1

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

logFileRotationDir

The directory where the rotated log files will be stored. By default the rotated files are stored in the same directory where the log file is stored.

Type: string

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

Name=user-specified-name

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

numberOfFilesLimited

Indicates whether to limit the number of log files that this server instance creates to store old messages. (Requires that you specify a file rotation type of `SIZE` or `TIME`.)

After the server reaches this limit, it deletes the oldest log file and creates a new log file with the latest suffix.

If you do not enable this option, the server creates new files indefinitely and you must clean up these files as you require.

Type: boolean

Constraints: Has Default Value: true, Has Production Mode Default Value: true

rotateLogOnStartup

Specifies whether a server rotates its log file during its startup cycle. The default value in production mode is false.

Type: boolean

Constraints: Has Default Value: true, Has Production Mode Default Value: false

rotationTime

Determines the start time (hour and minute) for a time-based rotation sequence.

At the time that this value specifies, the server renames the current log file. Thereafter, the server renames the log file at an interval that you specify in File Time Span.

Note that WebLogic Server sets a threshold size limit of 500 MB before it forces a hard rotation to prevent excessive log file growth.

Use the following format: H:mm, where

- H is Hour in day (0-23)
- mm is the minute in hour

Type: string

Constraints: Has Default Value: 00:00

rotationType

Criteria for moving old log messages to a separate file.

- NONE Messages accumulate in a single file. You must erase the contents of the file when the size is too large. Note that WebLogic Server sets a threshold size limit of 500 MB before it forces a hard rotation to prevent excessive log file growth.
- SIZE When the log file reaches the size that you specify in FileMinSize, the server renames the file as *SERVER_NAME.lognnnn*
- TIME At each time interval that you specify in TimeSpan, the server renames the file as *SERVER_NAME.lognnnn*

After the server renames a file, subsequent messages accumulate in a new file with the name that you specified as the log file name.

Type: string

Constraints: Has Default Value: bySize, Legal Values: bySize, byTime, none

tags

Return all tags on this Configuration MBean

Type: array of string

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.DataSourceMBean

This bean represents a DataSource within a Weblogic Server instance.

The properties of the weblogic.management.configuration.DataSourceMBean entity are as follows:

defaultDataSource

The JNDI name of a system resource data source used to override the default datasource.

Type: string

deploymentOrder

A priority that the server uses to determine when it deploys an item. The priority is relative to other deployable items of the same type.

For example, the server prioritizes and deploys all EJBs before it prioritizes and deploys startup classes.

Items with the lowest Deployment Order value are deployed first. There is no guarantee on the order of deployments with equal Deployment Order values. There is no guarantee of ordering across clusters.

Type: integer/int32

Constraints: Has Default Value: 1000, Minimum Value: 0, Maximum Value: 2147483647

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's

`javax.management.ObjectName`

`Name=user-specified-name`

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`.

Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

rmiJDBCSecurity

The security protocol used by an RMI client to access a data source. Values are:

- **Secure:** All incoming JDBC calls require administrator authentication. All other subjects, including anonymous, are rejected. Requires a configured SSL listen port.
- **Compatibility:** Use an unsecure channel with the application's subject and no check for inbound administrator authentication when using RMI to access a data source. This setting reflects the legacy implementation behavior for RMI access to a data source and is a potential security vulnerability as it provides a client uncontrolled access to a database.
- The default value is Compatibility.

Type: string

Constraints: Has Default Value: Compatibility

tags

Return all tags on this Configuration MBean

Type: array of string

targets

You must select a target on which an MBean will be deployed from this list of the targets in the current domain on which this item can be deployed. Targets must be either servers or clusters. The deployment will only occur once if deployments overlap.

Type: array of weblogic.management.configuration.TargetMBean references

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.DataSourcePartitionMBean

This interface provides access to the DataSourcePartition configuration attributes. The methods defined herein are applicable for DataSource configuration at the partition level.

The properties of the weblogic.management.configuration.DataSourcePartitionMBean entity are as follows:

defaultDatasource

The JNDI name of a system resource data source used to override the default datasource.

Type: string

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

Name=user-specified-name

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

tags

Return all tags on this Configuration MBean

Type: array of string

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.DatabaseLessLeasingBasisMBean

DatabaseLessLeasingBasisMBean defines attributes related to the functioning of singleton services and server migration without the use of a HA database.

The properties of the `weblogic.management.configuration.DatabaseLessLeasingBasisMBean` entity are as follows:

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to `config.xml`

Type: boolean

Constraints: Read Only, Has Default Value: false

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

memberDiscoveryTimeout

Gets the MemberDiscoveryTimeout value. This value defines the amount of time a server waits during or after startup to discover members that belong to the same cluster. This information is used to join or form a new cluster.

Type: integer/int32

Constraints: Has Default Value: 30, Minimum Value: 10

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

Name=user-specified-name

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

tags

Return all tags on this Configuration MBean

Type: array of string

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.DebugPatchesMBean

Dynamic Debug patches configuration.

The properties of the `weblogic.management.configuration.DebugPatchesMBean` entity are as follows:

debugPatchDirectory

Type: string

Constraints: Has Default Value: `debug_patches`

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to `config.xml`

Type: boolean

Constraints: Read Only, Has Default Value: false

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

`Name=user-specified-name`

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

tags

Return all tags on this Configuration MBean

Type: array of string

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.DebugScopeMBean

This interface captures whether the enabled state of a debug scope. The name of a debug scope is the fully qualified scope name for example `weblogic.security.SSL`

The properties of the `weblogic.management.configuration.DebugScopeMBean` entity are as follows:

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to `config.xml`

Type: boolean

Constraints: Read Only, Has Default Value: false

enabled

Gets the enabled state of the debug scope mbean. By default a debug scope is disabled.

Type: boolean

Constraints: Has Default Value: false

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

name

It seems that the getter must be overridden because the setter is.

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

tags

Return all tags on this Configuration MBean

Type: array of string

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.DefaultFileStoreMBean

This MBean describes the configuration of the default file store. Each WebLogic Server instance has a default file store.

The properties of the `weblogic.management.configuration.DefaultFileStoreMBean` entity are as follows:

blockSize

The smallest addressable block, in bytes, of a file. When a native `wlfileio` driver is available and the block size has not been configured by the user, the store selects the minimum OS specific value for unbuffered (direct) I/O, if it is within the range [512, 8192].

A file store's block size does not change once the file store creates its files. Changes to block size only take effect for new file stores or after the current files have been deleted. See "Tuning the Persistent Store" in *Tuning Performance of Oracle WebLogic Server*

Type: integer/int32

Constraints: Has Default Value: -1, Minimum Value: -1, Maximum Value: 8192

cacheDirectory

The location of the cache directory for Direct-Write-With-Cache, ignored for other policies.

When Direct-Write-With-Cache is specified as the SynchronousWritePolicy, cache files are created in addition to primary files (see Directory for the location of primary files). If a cache directory location is specified, the cache file path is *CacheDirectory/WLStoreCache/StoreNameFileNum.DAT.cache*. When specified, Oracle recommends using absolute paths, but if the directory location is a relative path, then CacheDirectory is created relative to the WebLogic Server instance's home directory. If "" or Null is specified, the Cache Directory is located in the current operating system temp directory as determined by the java.io.tmpdir Java System property (JDK's default: /tmp on UNIX, %TEMP% on Windows) and is *TempDirectory/WLStoreCache/DomainNameunique-idStoreNameFileNum.DAT.cache*. The value of java.io.tmpdir varies between operating systems and configurations, and can be overridden by passing `-Djava.io.tmpdir=My_path` on the JVM command line.

Considerations:

- **Security:** Some users may want to set specific directory permissions to limit access to the cache directory, especially if there are custom configured user access limitations on the primary directory. For a complete guide to WebLogic security, see "Securing a Production Environment for Oracle WebLogic Server."
- **Additional Disk Space Usage:** Cache files consume the same amount of disk space as the primary store files that they mirror. See Directory for the location of primary store files.
- **Performance:** For the best performance, a cache directory should be located in local storage instead of NAS/SAN (remote) storage, preferably in the operating system's temp directory. Relative paths should be avoided, as relative paths are located based on the domain installation, which is typically on remote storage. It is safe to delete a cache directory while the store is not running, but this may slow down the next store boot.
- **Preventing Corruption and File Locking:** Two same named stores must not be configured to share the same primary or cache directory. There are store file locking checks that are designed to detect such conflicts and prevent corruption by failing the store boot, but it is not recommended to depend on the file locking feature for correctness. See Enable File Locking
- **Boot Recovery:** Cache files are reused to speed up the File Store boot and recovery process, but only if the store's host WebLogic Server instance has been shut down cleanly prior to the current boot. For example, cache files are not re-used and are instead fully recreated: after a `kill -9`, after an OS or JVM crash, or after an off-line change to the primary files, such as a store admin compaction. When cache files are recreated, a Warning log message 280102 is generated.
- **Fail-Over/Migration Recovery:** A file store safely recovers its data without its cache directory. Therefore, a cache directory does not need to be copied or otherwise made accessible after a fail-over or migration, and similarly does not need to be placed in NAS/SAN storage. A Warning log message 280102, which is generated to indicate the need to recreate the cache on the new host system, can be ignored.
- **Cache File Cleanup:** To prevent unused cache files from consuming disk space, test and developer environments should periodically delete cache files.

Type: string

Constraints: Has Default Value: null, Legal Null: true

directory

The path name to the file system directory where the file store maintains its data files.

- When targeting a file store to a migratable target, the store directory must be accessible from all candidate server members in the migratable target.
- For highest availability, use either a SAN (Storage Area Network) or other reliable shared storage.
- Use of NFS mounts is discouraged, but supported. Most NFS mounts are not transactionally safe by default, and, to ensure transactional correctness, need to be configured using your NFS vendor documentation in order to honor synchronous write requests.
- For `SynchronousWritePolicy` of `Direct-Write-With-Cache`, see `Cache Directory`.
- Additional O/S tuning may be required if the directory is hosted by Microsoft Windows, see `Synchronous Write Policy` for details.

Type: string

Constraints: Has Default Value: null, Legal Null: true

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

fileLockingEnabled

Determines whether OS file locking is used.

When file locking protection is enabled, a store boot fails if another store instance already has opened the store files. Do not disable this setting unless you have procedures in place to prevent multiple store instances from opening the same file. File locking is not required but helps prevent corruption in the event that two same-named file store instances attempt to operate in the same directories. This setting applies to both primary and cache files.

Type: boolean

Constraints: Has Default Value: true

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

initialSize

The initial file size, in bytes.

- Set `InitialSize` to pre-allocate file space during a file store boot. If `InitialSize` exceeds `MaxFileSize`, a store creates multiple files (number of files = $\text{InitialSize} / \text{MaxFileSize}$ rounded up).
- A file store automatically reuses the space from deleted records and automatically expands a file if there is not enough space for a new write request.

- Use `InitialSize` to limit or prevent file expansions during runtime, as file expansion introduces temporary latencies that may be noticeable under rare circumstances.
- Changes to initial size only take effect for new file stores, or after any current files have been deleted prior to restart.
- See `Maximum File Size`

Type: integer/int64

Constraints: Has Default Value: 0, Minimum Value: 0

ioBufferSize

The I/O buffer size, in bytes, automatically rounded down to the nearest power of 2.

- For the `Direct-Write-With-Cache` policy when a native `wfileio` driver is available, `IOBufferSize` describes the maximum portion of a cache view that is passed to a system call. This portion does not consume off-heap (native) or Java heap memory.
- For the `Direct-Write` and `Cache-Flush` policies, `IOBufferSize` is the size of a per store buffer which consumes off-heap (native) memory, where one buffer is allocated during run-time, but multiple buffers may be temporarily created during boot recovery.
- When a native `wfileio` driver is not available, the setting applies to off-heap (native) memory for all policies (including `Disabled`).
- For the best runtime performance, Oracle recommends setting `IOBufferSize` so that it is larger than the largest write (multiple concurrent store requests may be combined into a single write).
- For the best boot recovery time performance of large stores, Oracle recommends setting `IOBufferSize` to at least 2 megabytes.

See `AllocatedIOBufferBytes` to find out the actual allocated off-heap (native) memory amount. It is a multiple of `IOBufferSize` for the `Direct-Write` and `Cache-Flush` policies, or zero.

Type: integer/int32

Constraints: Has Default Value: -1, Minimum Value: -1, Maximum Value: 67108864

maxFileSize

The maximum file size, in bytes, of an individual data file.

- The `MaxFileSize` value affects the number of files needed to accommodate a store of a particular size (number of files = store size/`MaxFileSize` rounded up).
- A file store automatically reuses space freed by deleted records and automatically expands individual files up to `MaxFileSize` if there is not enough space for a new record. If there is no space left in existing files for a new record, a store creates an additional file.
- A small number of larger files is normally preferred over a large number of smaller files as each file allocates Window Buffer and file handles.
- If `MaxFileSize` is larger than $2^{24} * \text{BlockSize}$, then `MaxFileSize` is ignored, and the value becomes $2^{24} * \text{BlockSize}$. The default `BlockSize` is 512, and $2^{24} * 512$ is 8 GB.
- The minimum size for `MaxFileSize` is 10 MB when multiple data files are used by the store. If `InitialSize` is less than `MaxFileSize` then a single file will be created

of `InitialSize` bytes. If `InitialSize` is larger than `MaxFileSize` then $(InitialSize / MaxFileSize)$ files will be created of `MaxFileSize` bytes and an additional file if necessary to contain any remainder.

- See Initial Size

Type: integer/int64

Constraints: Has Default Value: 1342177280, Minimum Value: 1048576, Maximum Value: 2139095040

maxWindowBufferSize

The maximum amount of data, in bytes and rounded down to the nearest power of 2, mapped into the JVM's address space per primary store file. Applies to synchronous write policies `Direct-Write-With-Cache` and `Disabled` but only when the native `wfileio` library is loaded.

A window buffer does not consume Java heap memory, but does consume off-heap (native) memory. If the store is unable to allocate the requested buffer size, it allocates smaller and smaller buffers until it reaches `MinWindowBufferSize`, and then fails if cannot honor `MinWindowBufferSize`

Oracle recommends setting the max window buffer size to more than double the size of the largest write (multiple concurrently updated records may be combined into a single write), and greater than or equal to the file size, unless there are other constraints. 32-bit JVMs may impose a total limit of between 2 and 4GB for combined Java heap plus off-heap (native) memory usage.

- See store attribute `AllocatedWindowBufferBytes` to find out the actual allocated Window Buffer Size.
- See Maximum File Size and Minimum Window Buffer Size

Type: integer/int32

Constraints: Has Default Value: -1, Minimum Value: -1, Maximum Value: 1073741824

minWindowBufferSize

The minimum amount of data, in bytes and rounded down to the nearest power of 2, mapped into the JVM's address space per primary store file. Applies to synchronous write policies `Direct-Write-With-Cache` and `Disabled`, but only when a native `wfileio` library is loaded. See Maximum Window Buffer Size

Type: integer/int32

Constraints: Has Default Value: -1, Minimum Value: -1, Maximum Value: 1073741824

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

Name=user-specified-name

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

synchronousWritePolicy

The disk write policy that determines how the file store writes data to disk.

This policy also affects the JMS file store's performance, scalability, and reliability. Oracle recommends `Direct-Write-With-Cache` which tends to have the highest performance. The default value is `Direct-Write`. The valid policy options are:

- `Direct-Write` Direct I/O is supported on all platforms. When available, file stores in direct I/O mode automatically load the native I/O `wlfileio` driver. This option tends to out-perform `Cache-Flush` and tend to be slower than `Direct-Write-With-Cache`. This mode does not require a native store `wlfileio` driver, but performs faster when they are available.
- `Direct-Write-With-Cache` Store records are written synchronously to primary files in the directory specified by the `Directory` attribute and asynchronously to a corresponding cache file in the `Cache Directory`. The `Cache Directory` provides information about disk space, locking, security, and performance implications. This mode requires a native store `wlfileiocode` driver. If the native driver cannot be loaded, then the write mode automatically switches to `Direct-Write`. See `Cache Directory`
- `Cache-Flush` Transactions cannot complete until all of their writes have been flushed down to disk. This policy is reliable and scales well as the number of simultaneous users increases. Transactionally safe but tends to be a lower performer than direct-write policies.
- `Disabled` Transactions are complete as soon as their writes are cached in memory, instead of waiting for the writes to successfully reach the disk. This is the fastest policy because write requests do not block waiting to be synchronized to disk, but, unlike other policies, is not transactionally safe in the event of operating system or hardware failures. Such failures can lead to duplicate or lost data/messages. This option does not require native store `wlfileio` drivers, but may run faster when they are available. Some non-WebLogic JMS vendors default to a policy that is equivalent to `Disabled`

Notes:

- When available, file stores load WebLogic `wlfileio` native drivers, which can improve performance. These drivers are included with Windows, Solaris, Linux, and AIX WebLogic installations.
- Certain older versions of Microsoft Windows may incorrectly report storage device synchronous write completion if the Windows default `Write Cache Enabled` setting is used. This violates the transactional semantics of transactional products (not specific to Oracle), including file stores configured with a `Direct-Write` (default) or `Direct-Write-With-Cache` policy, as a system crash or power failure can lead to a loss or a duplication of records/messages. One of the visible symptoms is that this problem may manifest itself in high persistent message/transaction throughput exceeding the physical capabilities of your storage device. You can address the problem by applying a Microsoft supplied patch, disabling the Windows `Write Cache Enabled` setting, or by using a

power-protected storage device. See <http://support.microsoft.com/kb/281672> and <http://support.microsoft.com/kb/332023>.

- NFS storage note: On some operating systems, native driver memory-mapping is incompatible with NFS when files are locked. Stores with synchronous write policies `Direct-Write-With-Cache` or `Disabled`, and WebLogic JMS paging stores enhance performance by using the native `wlfileio` driver to perform memory-map operating system calls. When a store detects an incompatibility between NFS, file locking, and memory mapping, it automatically downgrades to conventional read/write system calls instead of memory mapping. For best performance, Oracle recommends investigating alternative NFS client drivers, configuring a non-NFS storage location, or in controlled environments and at your own risk, disabling the file locks (See `Enable File Locking`). For more information, see "Tuning the WebLogic Persistent Store" in *Tuning Performance of Oracle WebLogic Server*

Type: string

Constraints: Has Default Value: `Direct-Write`, Legal Values: `Disabled`, `Cache-Flush`, `Direct-Write`, `Direct-Write-With-Cache`

tags

Return all tags on this Configuration MBean

Type: array of string

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.DeploymentConfigurationMBean

Specifies the domain-level deployment configuration attributes.

The properties of the `weblogic.management.configuration.DeploymentConfigurationMBean` entity are as follows:

defaultMultiVersionAppRetireTimeout

Specifies the default retire timeout to be used for multi version apps. The value is in seconds

Type: integer/int32

Constraints: Has Default Value: 300, Minimum Value: 0

deploymentServiceMessageRetryCount

The maximum number of times the Deployment Service will retry sending a message if a connection exception occurs during the during a deployment or activate changes operation.

Type: integer/int32

Constraints: Has Default Value: 60, Minimum Value: 0

deploymentServiceMessageRetryInterval

The number of milliseconds between retry attempts if a connection exception occurs during the during the deployment or activate changes operation.

Type: integer/int32

Constraints: Has Default Value: 5000, Minimum Value: 0

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

longRunningRetireThreadDumpCount

The maximum number of times the thread dump generation will be retried on a long running Retire operation

Type: integer/int32

Constraints: Has Default Value: 3, Minimum Value: 0

longRunningRetireThreadDumpInterval

The number of milliseconds between thread dump retry on a long running Retire operation.

Type: integer/int64

Constraints: Has Default Value: 60000, Minimum Value: 0

longRunningRetireThreadDumpStartTime

The number of milliseconds a thread dump generation will start for a long running Retire operation.

Type: integer/int64

Constraints: Has Default Value: 1200000, Minimum Value: 0

maxRetiredTasks

Gets the value of the maximum number of retired tasks to save information for.

Type: integer/int32

Constraints: Has Default Value: 20

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

Name=user-specified-name

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

restageOnlyOnRedeploy

Specifies whether applications with staging mode of STAGE are restaged only during redeploy operation. If set to true, then applications will never restage during server startup and will only be restaged on an explicit redeploy operation.

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

tags

Return all tags on this Configuration MBean

Type: array of string

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.DeploymentValidationPluginMBean

Specifies the deployment validation plug-in configuration attributes. The plug-in factory must have a no-argument constructor and must implement this interface: `weblogic.deployment.configuration.DeploymentValidationPluginFactory`

The properties of the `weblogic.management.configuration.DeploymentValidationPluginMBean` entity are as follows:

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to `config.xml`

Type: boolean

Constraints: Read Only, Has Default Value: false

factoryClassname

Gets the classname of the plug-in factory used for validation. This is a fully qualified name. The class must be in the Administration Server classpath.

Type: string

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's
`javax.management.ObjectName`

`Name=user-specified-name`

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

tags

Return all tags on this Configuration MBean

Type: array of string

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.DeterminerCandidateResourceInfoVBean

DeterminerCandidateResourceInfoVBean interface

The properties of the
`weblogic.management.configuration.DeterminerCandidateResourceInfoVBean` entity
 are as follows:

determiner

determiner indicator

Type: boolean

Constraints: Read Only

displayName

display name

Type: string

Constraints: Read Only

internalName

internal name

Type: string

Constraints: Read Only

resourceType

resource type

Type: string**Constraints:** Read Only

weblogic.management.configuration.DomainMBean

A WebLogic Domain is a group of servers and/or clusters which are administered as a group.

The properties of the weblogic.management.configuration.DomainMBean entity are as follows:

adminServerName**Type:** string**administrationPort**

The common secure administration port for this WebLogic Server domain. (Requires you to enable the administration port.)

Type: integer/int32**Constraints:** Has Default Value: 9002, Minimum Value: 1, Maximum Value: 65535**administrationPortEnabled**

Specifies whether the domain-wide administration port should be enabled for this WebLogic Server domain. Because the administration port uses SSL, enabling the administration port requires that SSL must be configured for all servers in the domain.

The domain-wide administration port enables you to start a WebLogic Server instance in *STANDBY* state. It also allows you to separate administration traffic from application traffic in your domain. Because all servers in the domain must enable or disable the administration port at once, you configure the default administration port settings at the domain level.

If you enable the administration port:

- The administration port accepts only connections that specify administrator credentials.
- Connections that specify administrator credentials can use only the administration port.
- The command that starts managed servers must specify a secure protocol and the administration port: `-Dweblogic.management.server=https://admin_server:administration_port`

Type: boolean**Constraints:** Has Secure Value: true, Has Default Value: false**administrationProtocol**

The default protocol for communicating through the administration port or administration channels. (Requires you to enable the administration port or to create an administration channel.)

If requests through the administration port or an administration channel do not specify a protocol, WebLogic Server uses the protocol specified here.

Valid admin protocols are:

- t3s
- https
- iiops

Type: string

Constraints: Has Default Value: t3s

archiveConfigurationCount

The number of archival versions of `config.xml` saved by the Administration Server each time the domain configuration is modified.

Type: integer/int32

Constraints: Has Default Value: 0, Minimum Value: 0, Maximum Value: 2147483647

batchJobsDataSourceJndiName

Returns the Batch DataSource jndi name. This jndi name will be used to lookup an instance of a DataSource that will be used to store the Batch jobs data.

Type: string

batchJobsExecutorServiceName

Returns the name of the application-scoped ManagedExecutorService. This ManagedExecutorService instance will be used to run batch jobs that are submitted from applications deployed to the domain. The ManagedExecutorServiceTemplate by the same name must exist when a batch job is submitted in the domain. If this returns null, then the batch runtime will look to use the default Java EE ManagedExecutorService that is bound to the JNDI name:

`java:comp/DefaultManagedExecutorService`

Type: string

clusterConstraintsEnabled

Specifies that deployments targeted to a cluster succeed only if all servers in the cluster are running.

By default, cluster constraints are disabled and deployment is attempted only on the servers that are reachable at the time of deployment from the Administration Server. Any servers that have been shut down or are temporarily partitioned from the Administration Server will retrieve the deployment during server startup or shortly after the network partition is resolved.

Type: boolean

Constraints: Has Default Value: false

configBackupEnabled

If true, then backups of the configuration will be made during server boot.

Type: boolean

Constraints: Has Default Value: false

configurationAuditType

Returns the criteria used for auditing configuration events (configuration changes and other operations):

- `CONFIG_CHANGE_NONE` Configuration events will neither be written to the server log or directed to the Security Audit Framework.
- `CONFIG_CHANGE_LOG` Configuration events will be written to the server log.

- `CONFIG_CHANGE_AUDIT` Configuration events will be directed to the Security Audit Framework.
- `CONFIG_CHANGE_LOG_AND_AUDIT` Configuration events will be written to the server log and directed to the Security Audit Framework.

Type: string

Constraints: Has Secure Value: audit, Has Default Value: none, Legal Values: none, log, audit, logaudit

configurationVersion

The release identifier for the configuration. This identifier will be used to indicate the version of the configuration. All server generated configurations will be established with the release identifier of the running server. The form of the version is major.minor.servicepack.rollingpatch. Not all parts of the version are required. i.e. "7" is acceptable.

Type: string

Constraints: Has Default Value: null

consoleContextPath

The context path that you want to use in URLs that specify the Administration Console. (Requires you to enable the Administration Console for the current domain.)

To access the Administration Console, you use the following URL:

`http://listen-addresslisten-portcontext-path`. For example, if you set the context path to `myconsole`, then you use the following URL to access the Administration Console:
`http://localhost:7001/myconsole`

To specify the listen address and listen port that you use to access the Administration Console, configure the listen address and listen port of the Administration Server.

Type: string

Constraints: Has Default Value: console

consoleEnabled

Specifies whether the Administration Server automatically deploys the Administration Console in the current domain.

If the Administration Console is not deployed, you can still use the WebLogic Scripting Tool or the management APIs to configure and monitor the domain.

Type: boolean

Constraints: Has Recommended Secure Value: false, Has Default Value: true

consoleExtensionDirectory

Returns the directory path that console extensions are loaded from.

Type: string

Constraints: Has Default Value: console-ext

deployments

Returns the DeploymentsMBeans representing the deployments that have been deployed to be part of this domain.

Type: array of `weblogic.management.configuration.DeploymentMBean` references

Constraints: Read Only

diagnosticContextCompatibilityModeEnabled

Specifies whether WLDF sends a pre-12.2.1-style diagnostic context along with the current-style diagnostic context.

If outbound communication to pre-12.2.1 servers is possible, this setting should always be enabled to ensure that those servers receive a diagnostic context that they can process. Disabling this setting in those scenarios can result in correlation information being lost across tiers, and in information reported by WLDF and DMS to become of sync in some situations.

If there is no outbound communication to pre-12.2.1 servers possible, it is suggested to disable this mode as only the current-style diagnostic context is needed to be propagated outbound (propagating the old style will not cause a failure, but is unnecessary overhead in that situation).

This setting affects outbound only, inbound pre-12.2.1 style diagnostic contexts are always understood and handled.

Type: boolean

Constraints: Has Default Value: true

domainVersion

Defines the common version of all servers in a domain. In a domain containing servers that are not all at the same release version, this attribute is used to determine the feature level that servers will assume.

The value must be less than or equal to the version of any managed server in the domain.

If this value is not equal to the version of the release version of the admin server, then the admin server will not be allowed to make modifications to the configuration.

Type: string

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

enableEECompliantClassloadingForEmbeddedAdapters

Specifies the class loading behavior for embedded adapters. If you enable this option, embedded adapters deployed to all partitions in the domain will use Java EE compliant class loading. The embedded adapter's classes will be accessible from other modules in the same application.

Type: boolean

exalogicOptimizationsEnabled

Specifies whether optimizations for Oracle Exalogic should be enabled. Optimizations include improved thread management and request processing, and reduced lock contention. This attribute should be enabled only when configuring a WebLogic domain for Oracle Exalogic.

Type: boolean

Constraints: Has Default Value: false

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

internalAppsDeployOnDemandEnabled

Specifies whether internal applications such as the console, uddi, wlstestclient, and uddiexplorer are deployed on demand (first access) instead of during server startup.

Type: boolean

Constraints: Has Default Value: true

javaServiceConsoleEnabled

Specifies whether the Administration Server automatically deploys the Java Service Administration Console in the current domain.

Type: boolean

javaServiceEnabled

Specifies whether features to support the use of this WebLogic Server as a Java Service in a cloud environment should be enabled.

Type: boolean

Constraints: Has Default Value: false

lastModificationTime

Return the last time this domain was updated. This is guaranteed to be unique for a given transactional modification.

Type: integer/int64

Constraints: Read Only

logFormatCompatibilityEnabled

Configures whether log messages will be logged in legacy format without supplemental attributes.

Type: boolean

Constraints: Has Default Value: false

maxConcurrentLongRunningRequests

The maximum number of running long-running requests that can be submitted to all the Managed Executor Services or Managed Scheduled Executor Services in the global/domain partition on the current server.

Type: integer/int32

Constraints: Has Default Value: 50, Minimum Value: 0, Maximum Value: 65534

maxConcurrentNewThreads

The maximum number of running threads that can be created by all the Managed Thread Factories in the global/domain partition on the current server.

Type: integer/int32

Constraints: Has Default Value: 50, Minimum Value: 0, Maximum Value: 65534

name

An alphanumeric name for this domain.

For more information on domain naming conventions, see Domain and Server Name Restrictions in Understanding Domain Configuration for Oracle WebLogic Server.

This name is included as one of the key properties in the MBean's
`javax.management.ObjectName`

`Name=user-specified-name`

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

parallelDeployApplicationModules

Determines if the modules of applications will be deployed in parallel. This setting can be overridden at the per-partition or per-application levels. See `AppDeploymentMBean#isParallelDeployModules()`

Type: boolean

Constraints: Has Default Value: false

parallelDeployApplications

Determines if applications will be deployed in parallel. This setting can be overridden at the per-partition level. See `PartitionMBean#isParallelDeployApplications()`

Type: boolean

partitionUriSpace

The URI prefix used for partition administrative virtual targets.

Type: string

Constraints: Has Default Value: /partitions

productionModeEnabled

Specifies whether all servers in this domain run in production mode.

You can configure servers in your domain to start in one of two modes, development or production. You use development mode while you are developing your applications. Development mode uses a relaxed security configuration and enables you to auto-deploy applications. You use production mode when your application is running in its final form. A production domain uses full security and may use clusters or other advanced features.

The runtime mode is a domain-wide setting. As each Managed Server starts, it refers to the mode of the Administration Server to determine its runtime mode. If you configure the domain to run in production mode, the Administration Server saves this setting to the domain's configuration document.

Type: boolean

rootDirectory

Return the root directory for the domain. In other words for a server process [`ServerMBean.getRootDirectory`] or [`ServerMBean.getDomainDirectory`]

Type: string

Constraints: Read Only

serverMigrationHistorySize

Gets the history size of server migrations.

A value of -1 indicates that the history size is unlimited.

Type: integer/int32

Constraints: Has Default Value: 100, Minimum Value: -1, Maximum Value: 2147483647

serviceMigrationHistorySize

Gets the history size of service migrations.

A value of -1 indicates that the history size is unlimited.

Type: integer/int32

Constraints: Has Default Value: 100, Minimum Value: -1, Maximum Value: 2147483647

siteName

The name of the site this domain is associated with.

Type: string

systemResources

Return the SystemResourceMBeans in this Domain.

Type: array of weblogic.management.configuration.SystemResourceMBean references

Constraints: Read Only

tags

Return all tags on this Configuration MBean

Type: array of string

targets

Define targets for this Domain

Type: array of weblogic.management.configuration.TargetMBean references

Constraints: Read Only

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.DynamicServersMBean

Contains the properties used to control how dynamic servers are created. These properties allow you to control if listens ports are calculated, how servers are assigned to machines, and the number of dynamic servers to create.

The properties of the weblogic.management.configuration.DynamicServersMBean entity are as follows:

calculatedListenPorts

Specifies whether listen ports are calculated.

Type: boolean

Constraints: Has Default Value: true

calculatedMachineNames

The CalculatedMachineNames attribute controls how server instances in a dynamic cluster are assigned to a machine. If the attribute is not set, then the dynamic servers will not be assigned to a machine. If the attribute is set, then the MachineNameMatchExpression attribute is used to select the set of machines to use for the dynamic servers.

Type: boolean

Constraints: Has Default Value: false

dynamicClusterCooloffPeriodSeconds

Get the cool-off period (in seconds) used by the Elasticity Framework while performing scale up or scale down operations. If a scale up or scale down operation was performed, subsequent requests for scale up or down operations will be ignored by the Elasticity Framework during this period.

Type: integer/int32

Constraints: Has Default Value: 900, Minimum Value: 0

dynamicClusterShutdownTimeoutSeconds

Get the timeout period (in seconds) used by the Elasticity Framework while gracefully shutting down a server. If the server does not shut down before the specified timeout period, the server will be forcibly shut down. With a negative time value, no timeout will be applied.

Type: integer/int32

Constraints: Has Default Value: 0, Minimum Value: 0

dynamicClusterSize

Get the current size of the dynamic cluster (the number of dynamic server instances allowed to be created). The specified number of server instances are dynamically added to the configuration at runtime and associated ServerLifeCycleRuntimeMBeans are created.

Type: integer/int32

Constraints: Minimum Value: 0, Maximum Value: 800

dynamicServerNames

Return an array of all the dynamic server names

Type: array of string

Constraints: Read Only

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

ignoreSessionsDuringShutdown

Indicates if the Elasticity Framework should ignore inflight HTTP sessions while shutting down servers.

Type: boolean

Constraints: Has Default Value: false

machineMatchExpression

Get the machine tag expression to use when selecting machine names. If the MachineMatchType is "name", each value will either match a machine name exactly or, if specified with a trailing '*' suffix, will match multiple machine names. If the MachineMatchType is "tag", the values will match all of the machines that have all of the tag values.

Type: string

machineMatchType

Get the machine tag expression to use when selecting machine names. If the MachineMatchType is "name", each value will either match a machine name exactly or, if specified with a trailing '*' suffix, will match multiple machine names. If the MachineMatchType is "tag", the values will match all of the machines that have all of the tag values.

Type: string

Constraints: Has Default Value: name, Legal Values: name, tag

machineNameMatchExpression

The expression is used when determining machines to use for server assignments. If null, then all machines in the domain are used. If a expression is provided, then only the machines in the domain that match the expression will be used when assigning machine names to dynamic servers. The expression is a comma separated set of values that specify the machines to match. Each value will either match a machine name exactly or if specified with a trailing '*' suffix, the value will match multiple machine names.

Type: string

maxDynamicClusterSize

Get the upper bound on the DynamicClusterSize that the Elasticity Framework is allowed to assign to DynamicClusterSize.

Type: integer/int32

Constraints: Has Default Value: 8, Minimum Value: 0, Maximum Value: 800

minDynamicClusterSize

Get the minimum number of running server instances that the Elasticity Framework will attempt to keep in the dynamic cluster.

Type: integer/int32

Constraints: Has Default Value: 1, Minimum Value: 0, Maximum Value: 800

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

Name=*user-specified-name*

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

serverNamePrefix

The server name prefix is used to specify the naming convention when creating server names. When the server name prefix is defined, server names are calculated with the specified prefix followed by the index starting with 1.

Type: string

serverTemplate

The server template used to create dynamic servers.

Type: `weblogic.management.configuration.ServerTemplateMBean` reference

Constraints: Restart Required

tags

Return all tags on this Configuration MBean

Type: array of string

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

waitForAllSessionsDuringShutdown

Indicates if the Elasticity Framework should wait for all (persisted and non-persisted) HTTP sessions during inflight work handling while shutting down servers.

Type: boolean

Constraints: Has Default Value: false

weblogic.management.configuration.EmbeddedLDAPMBean

The MBean that defines the configuration properties for the embedded LDAP server for the WebLogic domain.

The properties of the `weblogic.management.configuration.EmbeddedLDAPMBean` entity are as follows:

anonymousBindAllowed

Specifies whether the embedded LDAP server should allow anonymous connections.

Type: boolean

Constraints: Has Default Value: false

backupCopies

The maximum number of backup copies that should be made for the embedded LDAP server.

This value limits the number of zip files in the ldap/backup directory.

Type: integer/int32

Constraints: Has Default Value: 7, Minimum Value: 0, Maximum Value: 65534

backupHour

The hour at which the embedded LDAP server should be backed up.

The Backup Hour value is used in conjunction with the Backup Minute value to determine the time at which the embedded LDAP server data files are backed up. At the specified time, WebLogic Server suspends writes to the embedded LDAP server, backs up the data files into a zip files in the ldap/backup directory, and then resumes writes.

Type: integer/int32

Constraints: Has Default Value: 23, Minimum Value: 0, Maximum Value: 23

backupMinute

The minute at which the embedded LDAP server should be backed up.

The Backup Minute value is used in conjunction with the Back Up Hour value to determine the time at which the embedded LDAP server data files are backed up

Type: integer/int32

Constraints: Has Default Value: 5, Minimum Value: 0, Maximum Value: 59

cacheEnabled

Specifies whether a cache is used with the embedded LDAP server.

This cache is used when a managed server is reading or writing to the master embedded LDAP server that is running on the Administration server.

Type: boolean

Constraints: Has Default Value: true

cacheSize

The size of the cache (in kilobytes) that is used with the embedded LDAP server.

Type: integer/int32

Constraints: Has Default Value: 32, Minimum Value: 0

cacheTTL

The time-to-live of the cache (in seconds) that is used with the embedded LDAP server.

Type: integer/int32

Constraints: Has Default Value: 60, Minimum Value: 0

credential

The credential (usually a password) used to connect to the embedded LDAP server.

If this credential has not been set, WebLogic Server generates a password at startup, initializes the attribute, and saves the configuration to the config.xml file. If you want

to connect to the embedded LDAP server using an external LDAP browser and the embedded LDAP administrator account (cn=Admin), change this attribute from the generated value.

As of 8.1 sp4, when you get the value of this attribute, WebLogic Server does the following:

1. Retrieves the value of the `CredentialEncrypted` attribute.
2. Decrypts the value and returns the unencrypted password as a String.

When you set the value of this attribute, WebLogic Server does the following:

1. Encrypts the value.
2. Sets the value of the `CredentialEncrypted` attribute to the encrypted value.

Using the `Credential` attribute is a potential security risk because the String object (which contains the unencrypted password) remains in the JVM's memory until garbage collection removes it and the memory is reallocated. Depending on how memory is allocated in the JVM, a significant amount of time could pass before this unencrypted data is removed from memory.

Instead of using this attribute, use `CredentialEncrypted()`

Type: string

Constraints: Encrypted

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

keepAliveEnabled

Whether keep alive is enabled in the socket connection

Type: boolean

Constraints: Has Default Value: false

masterFirst

Specifies whether a Managed Server should always connect to the master LDAP server (contained in the Administration Server), instead of connecting to the local replicated LDAP server (contained in the Managed Server).

Type: boolean

Constraints: Has Default Value: false

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

Name=user-specified-name

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

refreshReplicaAtStartup

Specifies whether a Managed Server should refresh all replicated data at boot time. (This is useful if you have made a large amount of changes when the Managed Server was not active, and you want to download the entire replica instead of having the Administration Server push each change to the Managed Server.)

Type: boolean

Constraints: Has Default Value: false

tags

Return all tags on this Configuration MBean

Type: array of string

timeout

Specifies the maximum number of seconds to wait for results from the embedded LDAP server before timing out. If this option is set to 0, there is no maximum time limit.

Type: integer/int32

Constraints: Has Default Value: 0, Minimum Value: 0

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.ExecuteQueueMBean

This bean is used to configure an execute queue and its associated thread pool.

The properties of the `weblogic.management.configuration.ExecuteQueueMBean` entity are as follows:

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to `config.xml`

Type: boolean

Constraints: Read Only, Has Default Value: false

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's

`javax.management.ObjectName`

Name=user-specified-name

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as

XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`.

Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

queueLength

The maximum number of simultaneous requests that this server can hold in the queue.

Type: integer/int32

Constraints: Has Default Value: 65536, Minimum Value: 256, Maximum Value: 1073741824

queueLengthThresholdPercent

The percentage of the Queue Length size that can be reached before this server indicates an overflow condition for the queue. If the overflow condition is reached and the current thread count has not reached the `ThreadsMaximum` value, then `ThreadsIncrease` number of threads are added.

Type: integer/int32

Constraints: Has Default Value: 90, Minimum Value: 1, Maximum Value: 99

tags

Return all tags on this Configuration MBean

Type: array of string

threadCount

The number of threads assigned to this queue.

Type: integer/int32

Constraints: Has Default Value: 15, Has Production Mode Default Value: 25, Minimum Value: 0, Maximum Value: 65536

threadsIncrease

Specifies the number of threads to increase the queue length when the queue length threshold is reached. This threshold is determined by the `QueueLengthThresholdPercent` value.

The following consideration applies to the dynamic nature of `ThreadsMaximum` and `ThreadsIncrease` attributes. If any of these attributes change during runtime, the changed value comes into effect when the next request is submitted to the execute queue and the scheduler decides to increase threads depending on the queue threshold conditions.

Type: integer/int32

Constraints: Has Default Value: 0, Minimum Value: 0, Maximum Value: 65536

threadsMaximum

The maximum number of threads that this queue is allowed to have; this value prevents WebLogic Server from creating an overly high thread count in the queue in response to continual overflow conditions.

A note about dynamic nature of `ThreadsMaximum` and `ThreadsIncrease` attributes. If any of these attributes change during runtime, the changed value comes into effect when the next request is submitted to the execute queue and the scheduler decides to increase threads depending on the queue threshold conditions. Imagine a scenario where the queue capacity has already reached the max threshold and the current thread count is already equal to `ThreadsMaximum` value. If more work is coming into the queue and the administrator wishes to increase the `ThreadsMaximum` a little to add a few more threads, he/she can do so by changing these attributes dynamically. Please note that the changed value is evaluated when the next request is submitted.

Type: integer/int32

Constraints: Has Default Value: 400, Minimum Value: 1, Maximum Value: 65536

threadsMinimum

The minimum number of threads that WebLogic Server will maintain in the queue.

Type: integer/int32

Constraints: Has Default Value: 5, Minimum Value: 0, Maximum Value: 65536

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.FairShareConstraintMBean

This mbean is used to configure a Fair Share based policy for a resource type.

The properties of the `weblogic.management.configuration.FairShareConstraintMBean` entity are as follows:

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to `config.xml`

Type: boolean

Constraints: Read Only, Has Default Value: false

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

Name=user-specified-name

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

tags

Return all tags on this Configuration MBean

Type: array of string

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

value

Gets the fair-share value associated with this resource type.

Type: integer/int32

Constraints: Minimum Value: 1, Maximum Value: 1000

weblogic.management.configuration.FairShareRequestClassMBean

This mbean defines the fair share value to use for this request class. One of the components of work managers is a request class that indicates the proportional of the total server thread use time this request class gets. The default fair share value is 50.

Fair shares are reflected in scheduling logic such that as long as multiple fair shares compete, the average number of threads used by each is in proportion to their fair share. For example, consider we only have two fair shares, A and B, having a fair share of 80 and 20, respectively. During a period in which both fair shares are sufficiently requested, say, zero think time and more clients than threads, the probability that a thread will work on behalf of A or B will tend toward 80% or 20%, respectively. The scheduling logic ensures this even when A tends to use a thread for much longer than B.

Fair share values can range from 1 to 1000. The default fair share value is 50.

The properties of the `weblogic.management.configuration.FairShareRequestClassMBean` entity are as follows:

deploymentOrder

A priority that the server uses to determine when it deploys an item. The priority is relative to other deployable items of the same type.

For example, the server prioritizes and deploys all EJBs before it prioritizes and deploys startup classes.

Items with the lowest Deployment Order value are deployed first. There is no guarantee on the order of deployments with equal Deployment Order values. There is no guarantee of ordering across clusters.

Type: integer/int32

Constraints: Has Default Value: 1000, Minimum Value: 0, Maximum Value: 2147483647

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

fairShare

Fair share value

Type: integer/int32

Constraints: Has Default Value: 50, Minimum Value: 1, Maximum Value: 1000

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

Name=user-specified-name

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

tags

Return all tags on this Configuration MBean

Type: array of string

targets

You must select a target on which an MBean will be deployed from this list of the targets in the current domain on which this item can be deployed. Targets must be either servers or clusters. The deployment will only occur once if deployments overlap.

Type: array of weblogic.management.configuration.TargetMBean references

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.FederationServicesMBean

This MBean represents configuration for SAML 1.1-based Federation Services, including the intersite transfer service, assertion consumer service, and assertion retrieval service.

The properties of the weblogic.management.configuration.FederationServicesMBean entity are as follows:

ACSRequiresSSL

Specifies whether the Assertion Consumer Service requires SSL.

Type: boolean

Constraints: Has Default Value: true

ARSRequiresSSL

Specifies whether the Assertion Retrieval Service requires SSL.

Type: boolean

Constraints: Has Default Value: true

ARSRequiresTwoWaySSL

Specifies whether the Assertion Retrieval Service requires two-way SSL authentication.

Type: boolean

Constraints: Has Default Value: false

ITSRequiresSSL

Specifies whether the Intersite Transfer Service requires SSL.

Type: boolean

Constraints: Has Default Value: true

POSTOneUseCheckEnabled

Specifies whether the POST one-use check is enabled.

Type: boolean

Constraints: Has Default Value: true

POSTRecipientCheckEnabled

Specifies whether the POST recipient check is enabled. When true, the recipient of the SAML Response must match the URL in the HTTP Request.

Type: boolean

Constraints: Has Default Value: true

SSLClientIdentityAlias

The alias used to store and retrieve the Destination Site's SSL client identity in the keystore.

Type: string

Constraints: Has Default Value: null

SSLClientIdentityPassPhrase

The passphrase used to retrieve the Destination Site's SSL client identity from the keystore.

Type: string

Constraints: Encrypted

assertionConsumerURIs

The Assertion Consumer URIs.

Type: array of string

Constraints: Has Default Value: [/samlacs/acs]

assertionRetrievalURIs

One or more URIs on which to listen for incoming assertion retrieval requests.

For artifact profile, the destination site receives a SAML artifact that represents a source site (why we need the source site ID values) and an assertion ID. The destination site sends a request containing the artifact to the source site's assertion retrieval URL, and the source site responds with the corresponding assertion. You may configure multiple URIs here, although typically one will be sufficient. The URI includes the application context, followed by the resource context. For example:

```
/my_application/saml/ars
```

which would be accessible from the outside as `https://my.example.com/my_application/saml/ars`

Type: array of string

Constraints: Has Default Value: [/samlars/ars]

assertionStoreClassName

The class that provides persistent storage for assertions, if you use an Assertion Store class other than the default class.

Type: string

Constraints: Has Default Value: null

assertionStoreProperties

Properties passed to Assertion Store class `initStore()` method.

This may be useful if you have implemented a custom Assertion Store class.

Type: java.util.Properties

Constraints: Has Default Value: null

destinationSiteEnabled

Specifies whether the Destination Site is enabled.

Type: boolean

Constraints: Has Default Value: false

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

intersiteTransferURIs

The Intersite Transfer URIs.

Type: array of string

Constraints: Has Default Value: [/samlits_ba/its, /samlits_ba/its/post, /samlits_ba/its/artifact, /samlits_cc/its, /samlits_cc/its/post, /samlits_cc/its/artifact]

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

Name=user-specified-name

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

signingKeyAlias

The alias used to store and retrieve the Source Site's signing key in the keystore. This key is used to sign POST profile responses.

Type: string

Constraints: Has Default Value: null

signingKeyPassPhrase

The passphrase used to retrieve the Source Site's signing key from the keystore.

Type: string

Constraints: Encrypted

sourceIdBase64

The Source Site ID base64-encoded.

This read-only value is a Base64 representation of a 20-byte binary value that is calculated from the `SourceSiteURL`. If you want to configure ARTIFACT profile with another site, you will need to give a `SourceId` value to the other site. This value is automatically updated when the `SourceSiteURL` changes.

Type: string

Constraints: Read Only

sourceIdHex

The Source Site ID in hexadecimal.

This read-only value is a hexadecimal representation of a 20-byte binary value that is calculated from the `SourceSiteURL`. If you want to configure ARTIFACT profile with another site, you will need to give a `SourceId` value to the other site. This value is automatically updated when the `SourceSiteURL` changes.

Type: string

Constraints: Read Only

sourceSiteEnabled

Indicates whether the Source Site is enabled.

Type: boolean

Constraints: Has Default Value: false

sourceSiteURL

The URL for the Source Site.

Type: string

Constraints: Has Default Value: null

tags

Return all tags on this Configuration MBean

Type: array of string

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

usedAssertionCacheClassName

The class used as the persistent store for the Used Assertion Cache. When no class is specified, the default Used Assertion Cache implementation is used.

Type: string

Constraints: Has Default Value: null

usedAssertionCacheProperties

Properties to be passed to the Used Assertion Cache class.

Type: java.util.Properties

Constraints: Has Default Value: null

weblogic.management.configuration.FileOpenMBean

A `FileOpenMBean` represents a resource consumption management policy for the "File Open" resource type.

The "File open" resource type governs the number of open files. This includes files that have been opened through `java.io` (`FileInputStream`, `FileOutputStream`, `RandomAccessFile` etc) and `java.nio` (NIO file channels) APIs.

Trigger (Usage limits) based policies can be defined for a "File Open" resource type through this MBean.

The valid set of recourse action types for the "File Open" resource type are:

- notify
- slow
- shutdown
- fail

The properties of the `weblogic.management.configuration.FileOpenMBean` entity are as follows:

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to `config.xml`

Type: boolean

Constraints: Read Only, Has Default Value: false

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

Name=user-specified-name

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

tags

Return all tags on this Configuration MBean

Type: array of string

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.FileStoreMBean

Defines an instance of the persistent store on the specified target that will keep its persistent objects in files on the filesystem. It may be used by JMS and by other subsystems.

The properties of the weblogic.management.configuration.FileStoreMBean entity are as follows:

XAResourceName

Overrides the name of the XAResource that this store registers with JTA.

You should not normally set this attribute. Its purpose is to allow the name of the XAResource to be overridden when a store has been upgraded from an older release and the store contained prepared transactions. The generated name should be used in all other cases.

Type: string

Constraints: Read Only, Has Default Value: null, Legal Null: true

blockSize

The smallest addressable block, in bytes, of a file. When a native `wlfileio` driver is available and the block size has not been configured by the user, the store selects the minimum OS specific value for unbuffered (direct) I/O, if it is within the range [512, 8192].

A file store's block size does not change once the file store creates its files. Changes to block size only take effect for new file stores or after the current files have been deleted. See "Tuning the Persistent Store" in *Tuning Performance of Oracle WebLogic Server*

Type: integer/int32

Constraints: Has Default Value: -1, Minimum Value: -1, Maximum Value: 8192

cacheDirectory

The location of the cache directory for Direct-Write-With-Cache, ignored for other policies.

When Direct-Write-With-Cache is specified as the `SynchronousWritePolicy`, cache files are created in addition to primary files (see `Directory` for the location of primary files). If a cache directory location is specified, the cache file path is `CacheDirectory/WLStoreCache/StoreNameFileNum.DAT.cache`. When specified, Oracle recommends using absolute paths, but if the directory location is a relative path, then `CacheDirectory` is created relative to the WebLogic Server instance's home directory. If "" or Null is specified, the `Cache Directory` is located in the current operating system `temp` directory as determined by the `java.io.tmpdir` Java System property (JDK's default: `/tmp` on UNIX, `%TEMP%` on Windows) and is `TempDirectory/WLStoreCache/DomainNameunique-idStoreNameFileNum.DAT.cache`. The value of `java.io.tmpdir` varies between operating systems and configurations,

and can be overridden by passing `-Djava.io.tmpdir=My_path` on the JVM command line.

Considerations:

- **Security:** Some users may want to set specific directory permissions to limit access to the cache directory, especially if there are custom configured user access limitations on the primary directory. For a complete guide to WebLogic security, see "Securing a Production Environment for Oracle WebLogic Server."
- **Additional Disk Space Usage:** Cache files consume the same amount of disk space as the primary store files that they mirror. See `Directory` for the location of primary store files.
- **Performance:** For the best performance, a cache directory should be located in local storage instead of NAS/SAN (remote) storage, preferably in the operating system's `temp` directory. Relative paths should be avoided, as relative paths are located based on the domain installation, which is typically on remote storage. It is safe to delete a cache directory while the store is not running, but this may slow down the next store boot.
- **Preventing Corruption and File Locking:** Two same named stores must not be configured to share the same primary or cache directory. There are store file locking checks that are designed to detect such conflicts and prevent corruption by failing the store boot, but it is not recommended to depend on the file locking feature for correctness. See `Enable File Locking`
- **Boot Recovery:** Cache files are reused to speed up the File Store boot and recovery process, but only if the store's host WebLogic Server instance has been shut down cleanly prior to the current boot. For example, cache files are not re-used and are instead fully recreated: after a `kill -9`, after an OS or JVM crash, or after an off-line change to the primary files, such as a store admin compaction. When cache files are recreated, a `Warning` log message 280102 is generated.
- **Fail-Over/Migration Recovery:** A file store safely recovers its data without its cache directory. Therefore, a cache directory does not need to be copied or otherwise made accessible after a fail-over or migration, and similarly does not need to be placed in NAS/SAN storage. A `Warning` log message 280102, which is generated to indicate the need to recreate the cache on the new host system, can be ignored.
- **Cache File Cleanup:** To prevent unused cache files from consuming disk space, test and developer environments should periodically delete cache files.

Type: string

Constraints: Has Default Value: null, Legal Null: true

deploymentOrder

A priority that the server uses to determine when it deploys an item. The priority is relative to other deployable items of the same type.

For example, the server prioritizes and deploys all EJBs before it prioritizes and deploys startup classes.

Items with the lowest Deployment Order value are deployed first. There is no guarantee on the order of deployments with equal Deployment Order values. There is no guarantee of ordering across clusters.

Type: integer/int32

Constraints: Has Default Value: 1000, Minimum Value: 0, Maximum Value: 2147483647

directory

The path name to the file system directory where the file store maintains its data files.

- When targeting a file store to a migratable target, the store directory must be accessible from all candidate server members in the migratable target.
- For highest availability, use either a SAN (Storage Area Network) or other reliable shared storage.
- Use of NFS mounts is discouraged, but supported. Most NFS mounts are not transactionally safe by default, and, to ensure transactional correctness, need to be configured using your NFS vendor documentation in order to honor synchronous write requests.
- For `SynchronousWritePolicy` of `Direct-Write-With-Cache`, see `Cache Directory`.
- Additional O/S tuning may be required if the directory is hosted by Microsoft Windows, see `Synchronous Write Policy` for details.

Type: string

Constraints: Has Default Value: null, Legal Null: true

distributionPolicy

Specifies how the instances of a configured JMS artifact are named and distributed when cluster-targeted. A JMS artifact is cluster-targeted when its target is directly set to a cluster, or when it is scoped to a resource group and the resource group is in turn targeted to a cluster. When this setting is configured on a store, it applies to all JMS artifacts that reference the store. Valid options:

- `Distributed` Creates an instance on each server JVM in a cluster. Required for all SAF agents and for cluster-targeted or resource-group-scoped JMS servers that host distributed destinations.
- `Singleton` Creates a single instance on a single server JVM within a cluster. Required for cluster-targeted or resource-group-scoped JMS servers that host standalone (non-distributed) destinations and for cluster-targeted or resource-group-scoped path services. The `Migration Policy` must be `On-Failure` or `Always` when using this option with a JMS server, `On-Failure` when using this option with a messaging bridge, and `Always` when using this option with a path service.

Instance Naming Note:

- The `DistributionPolicy` determines the instance name suffix for cluster-targeted JMS artifacts. The suffix for a cluster-targeted `Singleton` is `-01` and for a cluster-targeted `Distributed` is `@ClusterMemberName`.

Messaging Bridge Notes:

- When an instance per server is desired for a cluster-targeted messaging bridge, Oracle recommends setting the bridge `Distributed Policy` and `Migration Policy` to `Distributed/Off`, respectively; these are the defaults.
- When a single instance per cluster is desired for a cluster-targeted bridge, Oracle recommends setting the bridge `Distributed Policy` and `Migration Policy` to `Singleton/On-Failure`, respectively.

- If you cannot cluster-target a bridge and still need singleton behavior in a configured cluster, you can target the bridge to a migratable target and configure the `Migration Policy` on the migratable target to `Exactly-Once`.

Type: string

Constraints: Has Default Value: Distributed, Legal Values: Distributed, Singleton

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

failbackDelaySeconds

Specifies the amount of time, in seconds, to delay before failing a cluster-targeted JMS artifact instance back to its preferred server after the preferred server failed and was restarted.

This delay allows time for the system to stabilize and dependent services to be restarted, preventing a system failure during a reboot.

- A value `>` specifies the time, in seconds, to delay before failing a JMS artifact back to its user preferred server.
- A value of `0` indicates that the instance would never failback.
- A value of `-1` indicates that there is no delay and the instance would failback immediately.

Note: This setting only applies when the JMS artifact is cluster-targeted and the `Migration Policy` is set to `On-Failure` or `Always`

Type: integer/int64

Constraints: Has Default Value: -1

fileLockingEnabled

Determines whether OS file locking is used.

When file locking protection is enabled, a store boot fails if another store instance already has opened the store files. Do not disable this setting unless you have procedures in place to prevent multiple store instances from opening the same file. File locking is not required but helps prevent corruption in the event that two same-named file store instances attempt to operate in the same directories. This setting applies to both primary and cache files.

Type: boolean

Constraints: Has Default Value: true

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

initialBootDelaySeconds

Specifies the amount of time, in seconds, to delay before starting a cluster-targeted JMS instance on a newly booted WebLogic Server instance. When this setting is configured on a store, it applies to all JMS artifacts that reference the store.

This allows time for the system to stabilize and dependent services to be restarted, preventing a system failure during a reboot.

- A value `>` is the time, in seconds, to delay before before loading resources after a failure and restart.
- A value of `0` specifies no delay.

Note: This setting only applies when the JMS artifact is cluster-targeted and the Migration Policy is set to `On-Failure` or `Always`

Type: integer/int64

Constraints: Has Default Value: 60

initialSize

The initial file size, in bytes.

- Set `InitialSize` to pre-allocate file space during a file store boot. If `InitialSize` exceeds `MaxFileSize`, a store creates multiple files (number of files = $\text{InitialSize} / \text{MaxFileSize}$ rounded up).
- A file store automatically reuses the space from deleted records and automatically expands a file if there is not enough space for a new write request.
- Use `InitialSize` to limit or prevent file expansions during runtime, as file expansion introduces temporary latencies that may be noticeable under rare circumstances.
- Changes to initial size only take effect for new file stores, or after any current files have been deleted prior to restart.
- See `Maximum File Size`

Type: integer/int64

Constraints: Has Default Value: 0, Minimum Value: 0

ioBufferSize

The I/O buffer size, in bytes, automatically rounded down to the nearest power of 2.

- For the `Direct-Write-With-Cache` policy when a native `wlfileio` driver is available, `IOBufferSize` describes the maximum portion of a cache view that is passed to a system call. This portion does not consume off-heap (native) or Java heap memory.
- For the `Direct-Write` and `Cache-Flush` policies, `IOBufferSize` is the size of a per store buffer which consumes off-heap (native) memory, where one buffer is allocated during run-time, but multiple buffers may be temporarily created during boot recovery.
- When a native `wlfileio` driver is not available, the setting applies to off-heap (native) memory for all policies (including `Disabled`).
- For the best runtime performance, Oracle recommends setting `IOBufferSize` so that it is larger than the largest write (multiple concurrent store requests may be combined into a single write).
- For the best boot recovery time performance of large stores, Oracle recommends setting `IOBufferSize` to at least 2 megabytes.

See `AllocatedIOBufferBytes` to find out the actual allocated off-heap (native) memory amount. It is a multiple of `IOBufferSize` for the `Direct-Write` and `Cache-Flush` policies, or zero.

Type: integer/int32

Constraints: Has Default Value: -1, Minimum Value: -1, Maximum Value: 67108864

logicalName

The name used by subsystems to refer to different stores on different servers using the same name.

For example, an EJB that uses the timer service may refer to its store using the logical name, and this name may be valid on multiple servers in the same cluster, even if each server has a store with a different physical name.

Multiple stores in the same domain or the same cluster may share the same logical name. However, a given logical name may not be assigned to more than one store on the same server.

Type: string

Constraints: Has Default Value: null, Legal Null: true

maxFileSize

The maximum file size, in bytes, of an individual data file.

- The `MaxFileSize` value affects the number of files needed to accommodate a store of a particular size (number of files = store size/`MaxFileSize` rounded up).
- A file store automatically reuses space freed by deleted records and automatically expands individual files up to `MaxFileSize` if there is not enough space for a new record. If there is no space left in existing files for a new record, a store creates an additional file.
- A small number of larger files is normally preferred over a large number of smaller files as each file allocates Window Buffer and file handles.
- If `MaxFileSize` is larger than $2^{24} * \text{BlockSize}$, then `MaxFileSize` is ignored, and the value becomes $2^{24} * \text{BlockSize}$. The default `BlockSize` is 512, and $2^{24} * 512$ is 8 GB.
- The minimum size for `MaxFileSize` is 10 MB when multiple data files are used by the store. If `InitialSize` is less than `MaxFileSize` then a single file will be created of `InitialSize` bytes. If `InitialSize` is larger than `MaxFileSize` then $(\text{InitialSize} / \text{MaxFileSize})$ files will be created of `MaxFileSize` bytes and an additional file if necessary to contain any remainder.
- See Initial Size

Type: integer/int64

Constraints: Has Default Value: 1342177280, Minimum Value: 1048576, Maximum Value: 2139095040

maxWindowBufferSize

The maximum amount of data, in bytes and rounded down to the nearest power of 2, mapped into the JVM's address space per primary store file. Applies to synchronous write policies `Direct-Write-With-Cache` and `Disabled` but only when the native `wfileio` library is loaded.

A window buffer does not consume Java heap memory, but does consume off-heap (native) memory. If the store is unable to allocate the requested buffer size, it allocates smaller and smaller buffers until it reaches `MinWindowBufferSize`, and then fails if cannot honor `MinWindowBufferSize`

Oracle recommends setting the max window buffer size to more than double the size of the largest write (multiple concurrently updated records may be combined into a single write), and greater than or equal to the file size, unless there are other constraints. 32-bit JVMs may impose a total limit of between 2 and 4GB for combined Java heap plus off-heap (native) memory usage.

- See store attribute `AllocatedWindowBufferBytes` to find out the actual allocated Window Buffer Size.
- See Maximum File Size and Minimum Window Buffer Size

Type: integer/int32

Constraints: Has Default Value: -1, Minimum Value: -1, Maximum Value: 1073741824

migrationPolicy

Controls migration and restart behavior of cluster-targeted JMS service artifact instances. When this setting is configured on a cluster-targeted store, it applies to all JMS artifacts that reference the store. See the migratable target settings for enabling migration and restart on migratable-targeted JMS artifacts.

- `Off` Disables migration support for cluster-targeted JMS service objects, and changes the default for Restart In Place to false. If you want a restart to be enabled when the Migration Policy is Off, then Restart In Place must be explicitly configured to true. This policy cannot be combined with the Singleton Migration Policy.
- `On-Failure` Enables automatic migration and restart of instances on the failure of a subsystem Service or WebLogic Server instance, including automatic fail-back and load balancing of instances.
- `Always` Provides the same behavior as `On-Failure` and automatically migrates instances even in the event of a graceful shutdown or a partial cluster start.

Note: Cluster leasing must be configured for `On-Failure` and `Always`.

Messaging Bridge Notes:

- When an instance per server is desired for a cluster-targeted messaging bridge, Oracle recommends setting the bridge `Distributed Policy` and `Migration Policy` to `Distributed/Off`, respectively; these are the defaults.
- When a single instance per cluster is desired for a cluster-targeted bridge, Oracle recommends setting the bridge `Distributed Policy` and `Migration Policy` to `Singleton/On-Failure`, respectively.
- A `Migration Policy` of `Always` is not recommended for bridges.
- If you cannot cluster-target a bridge and still need singleton behavior in a configured cluster, you can target the bridge to a migratable target and configure the `Migration Policy` on the migratable target to `Exactly-Once`.

Type: string

Constraints: Has Default Value: Off, Legal Values: Off, On-Failure, Always

minWindowBufferSize

The minimum amount of data, in bytes and rounded down to the nearest power of 2, mapped into the JVM's address space per primary store file. Applies to synchronous write policies `Direct-Write-With-Cache` and `Disabled`, but only when a native `wfileio` library is loaded. See Maximum Window Buffer Size

Type: integer/int32

Constraints: Has Default Value: -1, Minimum Value: -1, Maximum Value: 1073741824

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's

`javax.management.ObjectName`

`Name=user-specified-name`

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as

XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`.

Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

numberOfRestartAttempts

Specifies the maximum number of restart attempts.

- A value > specifies the maximum number of restart attempts.
- A value of specifies the same behavior as setting `getRestartInPlace` to `false`
- A value of -1 means infinite retry restart until it either starts or the server instance shuts down.

Type: integer/int32

Constraints: Has Default Value: 6, Minimum Value: -1

partialClusterStabilityDelaySeconds

Specifies the amount of time, in seconds, to delay before a partially started cluster starts all cluster-targeted JMS artifact instances that are configured with a Migration Policy of `Always` or `On-Failure`.

Before this timeout expires or all servers are running, a cluster starts a subset of such instances based on the total number of servers running and the configured cluster size. Once the timeout expires or all servers have started, the system considers the cluster stable and starts any remaining services.

This delay ensures that services are balanced across a cluster even if the servers are started sequentially. It is ignored after a cluster is fully started (stable) or when individual servers are started.

- A value > specifies the time, in seconds, to delay before a partially started cluster starts dynamically configured services.
- A value of specifies no delay.

Type: integer/int64

Constraints: Has Default Value: 240

restartInPlace

Enables a periodic automatic in-place restart of failed cluster-targeted or standalone-server-targeted JMS artifact instance(s) running on healthy WebLogic Server instances. See the migratable target settings for in-place restarts of migratable-targeted JMS artifacts. When the Restart In Place setting is configured on a store, it applies to all JMS artifacts that reference the store.

- If the Migration Policy of the JMS artifact is set to `Off`, Restart In Place is disabled by default.
- If the Migration Policy of the JMS artifact is set to `On-Failure` or `Always`, Restart In Place is enabled by default.
- This attribute is not used by WebLogic messaging bridges which automatically restart internal connections as needed.
- For a JMS artifact that is cluster-targeted and the Migration Policy is set to `On-Failure` or `Always`, if restart fails after the configured maximum retry attempts, it will migrate to a different server within the cluster.

Type: boolean

secondsBetweenRestarts

Specifies the amount of time, in seconds, to wait in between attempts to restart a failed service instance.

Type: integer/int32

Constraints: Has Default Value: 30, Minimum Value: 1

synchronousWritePolicy

The disk write policy that determines how the file store writes data to disk.

This policy also affects the JMS file store's performance, scalability, and reliability. Oracle recommends `Direct-Write-With-Cache` which tends to have the highest performance. The default value is `Direct-Write`. The valid policy options are:

- `Direct-Write` Direct I/O is supported on all platforms. When available, file stores in direct I/O mode automatically load the native I/O `wlfileio` driver. This option tends to out-perform `Cache-Flush` and tend to be slower than `Direct-Write-With-Cache`. This mode does not require a native store `wlfileio` driver, but performs faster when they are available.
- `Direct-Write-With-Cache` Store records are written synchronously to primary files in the directory specified by the `Directory` attribute and asynchronously to a corresponding cache file in the `Cache Directory`. The `Cache Directory` provides information about disk space, locking, security, and performance implications. This mode requires a native store `wlfileiocode` driver. If the native driver cannot be loaded, then the write mode automatically switches to `Direct-Write`. See `Cache Directory`
- `Cache-Flush` Transactions cannot complete until all of their writes have been flushed down to disk. This policy is reliable and scales well as the number of simultaneous users increases. Transactionally safe but tends to be a lower performer than direct-write policies.
- `Disabled` Transactions are complete as soon as their writes are cached in memory, instead of waiting for the writes to successfully reach the disk. This is the fastest policy because write requests do not block waiting to be synchronized to disk, but, unlike other policies, is not transactionally safe in the event of operating system or hardware failures. Such failures can lead to duplicate or lost data/messages. This option does not require native store `wlfileio` drivers, but may run faster when

they are available. Some non-WebLogic JMS vendors default to a policy that is equivalent to `Disabled`

Notes:

- When available, file stores load WebLogic `wlfileio` native drivers, which can improve performance. These drivers are included with Windows, Solaris, Linux, and AIX WebLogic installations.
- Certain older versions of Microsoft Windows may incorrectly report storage device synchronous write completion if the Windows default `Write Cache Enabled` setting is used. This violates the transactional semantics of transactional products (not specific to Oracle), including file stores configured with a `Direct-Write` (default) or `Direct-Write-With-Cache` policy, as a system crash or power failure can lead to a loss or a duplication of records/messages. One of the visible symptoms is that this problem may manifest itself in high persistent message/transaction throughput exceeding the physical capabilities of your storage device. You can address the problem by applying a Microsoft supplied patch, disabling the Windows `Write Cache Enabled` setting, or by using a power-protected storage device. See <http://support.microsoft.com/kb/281672> and <http://support.microsoft.com/kb/332023>.
- NFS storage note: On some operating systems, native driver memory-mapping is incompatible with NFS when files are locked. Stores with synchronous write policies `Direct-Write-With-Cache` or `Disabled`, and WebLogic JMS paging stores enhance performance by using the native `wlfileio` driver to perform memory-map operating system calls. When a store detects an incompatibility between NFS, file locking, and memory mapping, it automatically downgrades to conventional read/write system calls instead of memory mapping. For best performance, Oracle recommends investigating alternative NFS client drivers, configuring a non-NFS storage location, or in controlled environments and at your own risk, disabling the file locks (See `Enable File Locking`). For more information, see "Tuning the WebLogic Persistent Store" in *Tuning Performance of Oracle WebLogic Server*

Type: string

Constraints: Has Default Value: `Direct-Write`, Legal Values: `Disabled`, `Cache-Flush`, `Direct-Write`, `Direct-Write-With-Cache`

tags

Return all tags on this Configuration MBean

Type: array of string

targets

The server instances, clusters, or migratable targets defined in the current domain that are candidates for hosting a file store, JDBC store, or replicated store. If scoped to a Resource Group or Resource Group Template, the target is inherited from the Virtual Target.

When selecting a cluster, the store must be targeted to the same cluster as the JMS server. When selecting a migratable target, the store must be targeted it to the same migratable target as the migratable JMS server or SAF agent. As a best practice, a path service should use its own custom store and share the same target as the store.

Type: array of `weblogic.management.configuration.TargetMBean` references

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.ForeignConnectionFactoryOverrideMBean

For each configuration entity that supports per-partition-override via a MBean, we have two MBeans, the original configure MBean and the corresponding override MBean, that eventually determine the effective settings of the configured resource. We mark an attribute of an override MBean "dynamic true" even though the original configure MBean masks it "dynamic false". This is to make sure that the overriding settings take effect on partition restart. Otherwise a server restart is required.

Defines partition-specific overrides for the most commonly overridden attributes in a ForeignConnectionFactory MBean. It overrides some of the settings in a same-named ForeignConnectionFactory MBean instance in the same multi-tenant scope to which this override MBean belongs.

The properties of the weblogic.management.configuration.ForeignConnectionFactoryOverrideMBean entity are as follows:

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's

`javax.management.ObjectName`

Name=user-specified-name

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`.

Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

password

The password used in conjunction with the user name specified in the Username parameter to access the remote connection factory.

Type: string

Constraints: Encrypted, Has Default Value: No-Override

remoteJNDIName

The name of the remote object that will be looked up in the remote JNDI directory.

Type: string

Constraints: Has Default Value: No-Override

tags

Return all tags on this Configuration MBean

Type: array of string

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

username

The user name that is passed when opening a connection to the remote server (represented by this foreign connection factory).

Type: string

Constraints: Has Default Value: No-Override

weblogic.management.configuration.ForeignDestinationOverrideMBean

For each configuration entity that supports per-partition-override via a MBean, we have two MBeans, the original configure MBean and the corresponding override MBean, that eventually determine the effective settings of the configured resource. We mark an attribute of an override MBean "dynamic true" even though the original configure MBean masks it "dynamic false". This is to make sure that the overriding settings take effect on partition restart. Otherwise a server restart is required.

Defines partition-specific overrides for the most commonly overridden attributes in a ForeignDestination MBean. It overrides some of the settings in a same-named ForeignDestination MBean instance in the same multi-tenant scope to which this override MBean belongs.

The properties of the weblogic.management.configuration.ForeignDestinationOverrideMBean entity are as follows:

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's

`javax.management.ObjectName`

`Name=user-specified-name`

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as

XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`;

Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

remoteJNDIName

The name of the remote object that will be looked up in the remote JNDI directory.

Type: string

Constraints: Has Default Value: No-Override

tags

Return all tags on this Configuration MBean

Type: array of string

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.ForeignJNDILinkMBean

This class represents a JNDI link that is outside the WebLogic server.

The properties of the `weblogic.management.configuration.ForeignJNDILinkMBean` entity are as follows:

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to `config.xml`

Type: boolean

Constraints: Read Only, Has Default Value: false

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

localJNDIName

The local JNDI name.

Type: string

Constraints: Legal Null: true

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

`Name=user-specified-name`

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

remoteJNDIName

The foreign JNDI name.

Type: string

Constraints: Legal Null: true

tags

Return all tags on this Configuration MBean

Type: array of string

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.ForeignJNDILinkOverrideMBean

Defines partition-specific overrides for the most commonly overridden attributes in a `ForeignJNDILink` MBean. It overrides some of the settings in a same-named `ForeignJNDILink` MBean instance in the same multi-tenant scope to which this override MBean belongs.

The properties of the `weblogic.management.configuration.ForeignJNDILinkOverrideMBean` entity are as follows:

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

localJNDIName

The local JNDI name.

Type: string

Constraints: Legal Null: true

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

Name=user-specified-name

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

remoteJNDIName

The foreign JNDI name.

Type: string

Constraints: Legal Null: true

tags

Return all tags on this Configuration MBean

Type: array of string

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.ForeignJNDIProviderMBean

This class represents a JNDI provider that is outside the WebLogic server.

The properties of the `weblogic.management.configuration.ForeignJNDIProviderMBean` entity are as follows:

deploymentOrder

A priority that the server uses to determine when it deploys an item. The priority is relative to other deployable items of the same type.

For example, the server prioritizes and deploys all EJBs before it prioritizes and deploys startup classes.

Items with the lowest Deployment Order value are deployed first. There is no guarantee on the order of deployments with equal Deployment Order values. There is no guarantee of ordering across clusters.

Type: integer/int32

Constraints: Has Default Value: 1000, Minimum Value: 0, Maximum Value: 2147483647

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to `config.xml`

Type: boolean

Constraints: Read Only, Has Default Value: false

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

initialContextFactory

The initial context factory to use to connect. This class name depends on the JNDI provider and the vendor you are using. The value corresponds to the standard JNDI property, `java.naming.factory.initial`

Type: string

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

Name=user-specified-name

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`.

Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

password

The remote server's user password.

Type: string

Constraints: Encrypted

properties

Any additional properties that must be set for the JNDI provider. These properties will be passed directly to the constructor for the JNDI provider's `InitialContext` class.

Note: This value must be filled in using a `name=value<return>name=value` format.

Type: `java.util.Properties`

providerURL

The foreign JNDI provider URL. This value corresponds to the standard JNDI property, `java.naming.provider.url`

Type: string

tags

Return all tags on this Configuration MBean

Type: array of string

targets

You must select a target on which an MBean will be deployed from this list of the targets in the current domain on which this item can be deployed. Targets must be either servers or clusters. The deployment will only occur once if deployments overlap.

Type: array of `weblogic.management.configuration.TargetMBean` references

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

user

The remote server's user name.

Type: string

weblogic.management.configuration.ForeignJNDIProviderOverrideMBean

Defines partition-specific overrides for the most commonly overridden attributes in a `ForeignJNDIProvider` MBean. It overrides some of the settings in a same-named `ForeignJNDIProvider` MBean instance in the same multi-tenant scope to which this override MBean belongs.

The properties of the `weblogic.management.configuration.ForeignJNDIProviderOverrideMBean` entity are as follows:

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

initialContextFactory

The initial context factory to use to connect. This class name depends on the JNDI provider and the vendor you are using. The value corresponds to the standard JNDI property, `java.naming.factory.initial`

Type: string

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

Name=user-specified-name

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

password

The remote server's user password.

Type: string

Constraints: Encrypted

properties

Any additional properties that must be set for the JNDI provider. These properties will be passed directly to the constructor for the JNDI provider's `InitialContext` class.

Note: This value must be filled in using a `name=value<return>name=value` format.

Type: `java.util.Properties`

providerURL

The foreign JNDI provider URL. This value corresponds to the standard JNDI property, `java.naming.provider.url`

Type: string

tags

Return all tags on this Configuration MBean

Type: array of string

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

user

The remote server's user name.

Type: string

weblogic.management.configuration.ForeignServerOverrideMBean

For each configuration entity that supports per-partition-override via a MBean, we have two MBeans, the original configure MBean and the corresponding override MBean, that eventually determine the effective settings of the configured resource. We mark an attribute of an override MBean "dynamic true" even though the original configure MBean masks it "dynamic false". This is to make sure that the overriding settings take effect on partition restart. Otherwise a server restart is required.

Defines partition-specific overrides for the most commonly overridden attributes in a ForeignServer MBean. It overrides some of the settings in a same-named ForeignServer MBean instance in the same multi-tenant scope to which this override MBean belongs.

The properties of the weblogic.management.configuration.ForeignServerOverrideMBean entity are as follows:

JNDIPropertiesCredential

Any credentials that must be set for the JNDI provider. These credentials will be part of the properties passed directly to the constructor for the JNDI provider's InitialContext class.

Some foreign providers require other properties to be set while obtaining an initial naming context. These properties can be set with a property bean.

Type: string

Constraints: Encrypted, Has Default Value: No-Override

connectionURL

The URL that WebLogic Server will use to contact the JNDI provider. The syntax of this URL depends on which JNDI provider is being used. For WebLogic JMS, leave this field blank if you are referencing WebLogic JMS objects within the same cluster.

This value corresponds to the standard JNDI property, `java.naming.provider.url`

Note: If this value is not specified, look-ups will be performed on the JNDI server within the WebLogic Server instance where this connection factory is deployed.

Type: string

Constraints: Has Default Value: No-Override, Legal Null: true

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

initialContextFactory

The name of the class that must be instantiated to access the JNDI provider. This class name depends on the JNDI provider and the vendor that are being used.

This value corresponds to the standard JNDI property, `java.naming.factory.initial`

Note: This value defaults to `weblogic.jndi.WLInitialContextFactory`, which is the correct value for WebLogic Server.

Type: string

Constraints: Has Default Value: No-Override

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

Name=user-specified-name

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

tags

Return all tags on this Configuration MBean

Type: array of string

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.GzipCompressionMBean

This MBean is used to specify domain-wide default values for GZIP compression support. In general, these properties can be overridden for a specific Web application (in the weblogic.xml file).

The properties of the weblogic.management.configuration.GzipCompressionMBean entity are as follows:

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

gzipCompressionContentType

Returns the type of content to be included in compression.

Type: array of string

Constraints: Has Default Value: [text/html, text/xml, text/plain]

gzipCompressionEnabled

This global property determines whether or not the container should provide GZIP compression.

Type: boolean

Constraints: Has Default Value: false

gzipCompressionMinContentLength

Returns the minimum content length to trigger GZIP compression. This allows you to bypass small-sized resources where compression does not yield a great return and uses unnecessary CPU.

Type: integer/int64

Constraints: Has Default Value: 2048

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

Name=user-specified-name

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

tags

Return all tags on this Configuration MBean

Type: array of string

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.HeapRetainedMBean

A `HeapRetainedMBean` represents a resource consumption management policy for the "Heap Retained" resource type.

The "Heap Retained" resource type tracks the amount of Heap memory retained (in use) by the Partition.

Triggers (Usage limits) and Fair share policies can be defined for a "Heap Retained" resource type through this MBean.

The valid set of recourse action types for the "Heap Retained" resource type are:

- notify
- slow
- shutdown

The properties of the `weblogic.management.configuration.HeapRetainedMBean` entity are as follows:

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to `config.xml`

Type: boolean

Constraints: Read Only, Has Default Value: false

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

Name=user-specified-name

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

tags

Return all tags on this Configuration MBean

Type: array of string

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.IIOPMBean

Configuration for IIOP properties.

The properties of the `weblogic.management.configuration.IIOPMBean` entity are as follows:

defaultCharCodeset

The standard character code set that this server will publish as its native code set. (Older ORBs may have trouble interoperating with anything other than the default.)

Type: string

Constraints: Has Default Value: US-ASCII, Legal Values: US-ASCII, UTF-8, ISO-8859-1

defaultMinorVersion

The default GIOP (General Inter-ORB Protocol) version that this server will negotiate for incoming connections. (You may have to modify the default to work with other vendor's ORBs.)

This attribute is useful for client orbs with broken GIOP 1.2 implementations.

Type: integer/int32

Constraints: Has Default Value: 2, Minimum Value: 0, Maximum Value: 2

defaultWideCharCodeset

The wide character code set that this server will publish as its native code set. (Older ORBs may have trouble interoperating with anything other than the default.)

Type: string

Constraints: Has Default Value: UCS-2, Legal Values: UCS-2, UTF-16, UTF-8, UTF-16BE, UTF-16LE

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to `config.xml`

Type: boolean

Constraints: Read Only, Has Default Value: false

enableIORServlet

Enable getior servlet used to publish COS Naming Service IORs

Type: boolean

Constraints: Has Default Value: false

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

Name=user-specified-name

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

systemSecurity

Specify the value System Security. The following variables are affected. `clientCertAuthentication`, `clientAuthentication`, `identityAssertion confidentiality`, `integrity`. The value set in this MBean would only be picked up if the value set in `RTD.xml` is "config".

Type: string

Constraints: Has Default Value: supported, Legal Values: none, supported, required

tags

Return all tags on this Configuration MBean

Type: array of string

txMechanism

The transaction mechanism used by IIOP invocations. The default is the Object Transaction Service (OTS) required by J2EE 1.3.

Type: string

Constraints: Has Default Value: OTS, Legal Values: OTS, JTA, OTSv11, none

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

useFullRepositoryIdList

Specify whether to use full Repository ID lists when sending value type information for custom-marshaled types. Full Repository ID lists allow C++ ORBs to truncate values to base types. For RMI-IIOP and Java ORBs doing this merely increases transmission overhead. JDK ORBs are known to have problems with these so setting this will prevent JDK ORB access from working.

Type: boolean

Constraints: Has Default Value: false

useJavaSerialization

Specify whether to use java serialization for marshalling objects. Setting this property improves performance when marshalling objects with very large object graphs.

Type: boolean

Constraints: Has Default Value: false

useSerialFormatVersion2

Specify whether to advertise RMI objects and EJBs as supporting RMI-IIOP serial format version 2 for custom marshaled objects.

Type: boolean

Constraints: Has Default Value: false

useStatefulAuthentication

Specify whether to advertise RMI objects and EJBs as supporting stateful CSIv2. Stateful CSIv2 is more efficient than stateless, requiring only a single authentication step for each remote principal. Stateless CSIv2 requires per-request authentication. Stateful CSIv2 is not required by J2EE 1.3 and so some ORBs do not support it. Stateful CSIv2 is enabled by default. This property can be changed at the object-level by changing the object's <stateful-authentication> runtime descriptor property.

Type: boolean

Constraints: Has Default Value: true

weblogic.management.configuration.InterceptorMBean

The properties of the weblogic.management.configuration.InterceptorMBean entity are as follows:

dependsOn

The set of interceptor names this interceptor depends on. The specified interceptors will appear before this interceptor in the invocation chain.

Type: array of string

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

interceptedOperationNames

The name of the operation / method that needs to be intercepted by this interceptor's method. If the return value is null or "*" then all operations are intercepted by this interceptor.

Type: array of string

interceptedTargetKey

The key associated with the intercepted target. This is the value that would have been specified in the @InterceptedTargetKey annotation. If this is null then this Interceptor is ignored.

Type: string

interceptorTypeName

The HK2 name of the interceptor class.

Type: string

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

`Name=user-specified-name`

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

priority

The priority of this intercepted method in the interceptor chain. An interceptor with a higher priority will be executed earlier than an interceptor with a lower priority.

Note: 1073741823 is actually `Integer.MAX_VALUE / 2` as defined in `InterceptorPriorities`.

Type: integer/int32

Constraints: Has Default Value: 1073741823

properties

A set of <name, value> pairs that needs to be passed to the interceptor.

Type: java.util.Properties

tags

Return all tags on this Configuration MBean

Type: array of string

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.InterceptorsMBean

The properties of the weblogic.management.configuration.InterceptorsMBean entity are as follows:

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

Name=user-specified-name

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

tags

Return all tags on this Configuration MBean

Type: array of string

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

whiteListingEnabled

Returns true if white listing feature is enabled. When white listing is enabled, only those Interceptors returned by `getInterceptors()` are enabled. If white listing is disabled, then the values returned by `getInterceptor()` overrides the values specified through annotations. For example the rank specified by an `InterceptorMethodMBean` overrides the rank specified using the

Type: boolean

weblogic.management.configuration.JASPICMBean

Provides configuration for JASPIC (JSR-196) Auth Config Providers on the domain.

The properties of the `weblogic.management.configuration.JASPICMBean` entity are as follows:

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to `config.xml`

Type: boolean

Constraints: Read Only, Has Default Value: false

enabled

Returns true if JASPIC is enabled, false otherwise.

Type: boolean

Constraints: Has Default Value: true

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

Name=user-specified-name

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`.

Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

tags

Return all tags on this Configuration MBean

Type: array of string

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.JDBCPropertyOverrideMBean

Defines a JDBC driver property override.

The properties of the `weblogic.management.configuration.JDBCPropertyOverrideMBean` entity are as follows:

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to `config.xml`

Type: boolean

Constraints: Read Only, Has Default Value: false

encryptedValue

The plaintext value of the encrypted property value.

The value is stored in an encrypted form in the descriptor file and when displayed in an administration console.

`setEncryptedValue('string')` works in online WLST but not offline WLST. Use `setEncryptedValueEncrypted(encrypt('string'))` for online or offline WLST.

Type: string

Constraints: Encrypted

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

Name=user-specified-name

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

sysPropValue

The value of the property defined as a system property.

Type: string

tags

Return all tags on this Configuration MBean

Type: array of string

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

value

The value of the property.

Type: string

weblogic.management.configuration.JDBCStoreMBean

Defines an instance of the persistent store that stores its persistent records in a JDBC-accessible database. It may be used by JMS and by other subsystems.

The properties of the `weblogic.management.configuration.JDBCStoreMBean` entity are as follows:

XAResourceName

Overrides the name of the XAResource that this store registers with JTA.

You should not normally set this attribute. Its purpose is to allow the name of the XAResource to be overridden when a store has been upgraded from an older release and the store contained prepared transactions. The generated name should be used in all other cases.

Type: string

Constraints: Read Only, Has Default Value: null, Legal Null: true

connectionCachingPolicy

Advanced use only: gets the connection caching policy for the JDBC store.

The return values will be one of:

- `JMSConstants.JDBCSTORE_CONNECTION_CACHING_POLICY_DEFAULT` ("DEFAULT")
- `JMSConstants.JDBCSTORE_CONNECTION_CACHING_POLICY_MINIMAL` ("MINIMAL")

- `JMSConstants.JDBCSTORE_CONNECTION_CACHING_POLICY_NONE` ("NONE")

IMPORTANT: See the below for additional usage information, particularly regarding NONE

DEFAULT

The default mode of operation for the JDBC store. The JDBC store will open two connections to the database and it will keep these connections open for the life of the store. In addition, if the worker count for the store is two or more, then it will open one connection for each of the workers and those connections will also stay open for the life of the JDBC store. If the worker count is 3 then the JDBC store will use 5 database connections. If the worker count is the default of 1 then the JDBC store will use just 2 connections. The DEFAULT setting is the recommended setting to be used when the database backing the JDBC store is not constrained with respect to the number of open connections.

MINIMAL

The JDBC store will open one connection to the database and it will keep that connection open for the life of the store. In addition, if the worker count for the store is two or more, then it will open one connection for each of the workers and those connections will also stay open for the life of the JDBC store. If the worker count is 3 then the JDBC store will use 4 database connections. If the worker count is the default of 1 then the JDBC store will use just 1 connection. The MINIMAL setting may result in a slight reduction of through-put for low concurrency messaging scenarios in comparison to DEFAULT.

NONE

The NONE connection caching policy is for 'advanced usage only'. The JDBC store will open one connection to the database on an as-needed basis to perform I/O and it will release that connection when the operation is complete. The NONE value is not compatible with a configured worker count of 2 or more and will result in a configuration validation exception. The NONE setting may result in a slight reduction of through-put for low concurrency messaging scenarios in comparison to DEFAULT or MINIMAL.

NOTE: It is strongly recommended that a JDBC store be configured with a dedicated data source when the store is configured with the NONE connection caching policy. A store that shares a data source with other non-store components or applications runs the risk of failing due to dead-locks. Please note that a JDBC store will require more than one connection when first started. As such, a data source should be configured to grow and shrink so that the JDBC store can initialize.

Type: string

Constraints: Has Default Value: DEFAULT, Legal Values: DEFAULT, MINIMAL, NONE

createTableDDLFile

Specifies the DDL (Data Definition Language) file to use for creating the JDBC store's backing table.

- This field is ignored when the JDBC store's backing table, `WLStore`, already exists.
- If a DDL file is not specified and the JDBC store detects that a backing table doesn't already exist, the JDBC store automatically creates the table by executing a preconfigured DDL file that is specific to the database vendor. These

preconfigured files are located in the `weblogic\store\io\jdbc\ddl` directory of the `MIDDLEWARE_HOME\modules\com.bea.core.store.jdbc_x.x.x.x.jar` file.

- If a DDL file is specified and the JDBC store detects that a backing table doesn't already exist, then the JDBC store searches for the DDL file in the file path first, and then if the file is not found, it searches for it in the CLASSPATH. Once found, the SQL within the DDL file is executed to create the JDBC store's database table. If the DDL file is not found and the backing table doesn't already exist, the JDBC store will fail to boot.

Type: string

Constraints: Has Default Value: null

dataSource

The JDBC data source used by this JDBC store to access its backing table.

The specified data source must use a non-XA JDBC driver since connection pools for XA JDBC drivers are not supported.

Type: `weblogic.management.configuration.JDBCSystemResourceMBean` reference

Constraints: Restart Required

deletesPerBatchMaximum

The maximum number of table rows that are deleted per database call.

- When possible, a JDBC store uses JDBC 3.0 batching to batch concurrent client requests.
- Both the maximum batch size for concurrent inserts and for concurrent writes are configurable.
- To disable JDBC 3.0 batching, set the maximum batch size to 1.
- The maximum batch size has no effect on the maximum number of concurrent client requests.

Type: integer/int32

Constraints: Has Default Value: 20, Minimum Value: 1, Maximum Value: 100

deletesPerStatementMaximum

The maximum number of table rows that are deleted per database call.

- Applies only when a JDBC store does not use JDBC 3.0 batching to batch concurrent client requests.
- The maximum deletes per statement has no effect on the maximum number of concurrent client requests.
- For some databases, the JDBC store may choose a lower value than the one configured.

Type: integer/int32

Constraints: Has Default Value: 20, Minimum Value: 1, Maximum Value: 100

deploymentOrder

A priority that the server uses to determine when it deploys an item. The priority is relative to other deployable items of the same type.

For example, the server prioritizes and deploys all EJBs before it prioritizes and deploys startup classes.

Items with the lowest Deployment Order value are deployed first. There is no guarantee on the order of deployments with equal Deployment Order values. There is no guarantee of ordering across clusters.

Type: integer/int32

Constraints: Has Default Value: 1000, Minimum Value: 0, Maximum Value: 2147483647

distributionPolicy

Specifies how the instances of a configured JMS artifact are named and distributed when cluster-targeted. A JMS artifact is cluster-targeted when its target is directly set to a cluster, or when it is scoped to a resource group and the resource group is in turn targeted to a cluster. When this setting is configured on a store, it applies to all JMS artifacts that reference the store. Valid options:

- **Distributed** Creates an instance on each server JVM in a cluster. Required for all SAF agents and for cluster-targeted or resource-group-scoped JMS servers that host distributed destinations.
- **Singleton** Creates a single instance on a single server JVM within a cluster. Required for cluster-targeted or resource-group-scoped JMS servers that host standalone (non-distributed) destinations and for cluster-targeted or resource-group-scoped path services. The `Migration Policy` must be `On-Failure` or `Always` when using this option with a JMS server, `On-Failure` when using this option with a messaging bridge, and `Always` when using this option with a path service.

Instance Naming Note:

- The `DistributionPolicy` determines the instance name suffix for cluster-targeted JMS artifacts. The suffix for a cluster-targeted `Singleton` is `-01` and for a cluster-targeted `Distributed` is `@ClusterMemberName`.

Messaging Bridge Notes:

- When an instance per server is desired for a cluster-targeted messaging bridge, Oracle recommends setting the bridge `Distributed Policy` and `Migration Policy` to `Distributed/Off`, respectively; these are the defaults.
- When a single instance per cluster is desired for a cluster-targeted bridge, Oracle recommends setting the bridge `Distributed Policy` and `Migration Policy` to `Singleton/On-Failure`, respectively.
- If you cannot cluster-target a bridge and still need singleton behavior in a configured cluster, you can target the bridge to a migratable target and configure the `Migration Policy` on the migratable target to `Exactly-Once`.

Type: string

Constraints: Has Default Value: Distributed, Legal Values: Distributed, Singleton

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

failbackDelaySeconds

Specifies the amount of time, in seconds, to delay before failing a cluster-targeted JMS artifact instance back to its preferred server after the preferred server failed and was restarted.

This delay allows time for the system to stabilize and dependent services to be restarted, preventing a system failure during a reboot.

- A value > specifies the time, in seconds, to delay before failing a JMS artifact back to its user preferred server.
- A value of indicates that the instance would never failback.
- A value of -1 indicates that there is no delay and the instance would failback immediately.

Note: This setting only applies when the JMS artifact is cluster-targeted and the Migration Policy is set to `On-Failure` or `Always`

Type: integer/int64

Constraints: Has Default Value: -1

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

initialBootDelaySeconds

Specifies the amount of time, in seconds, to delay before starting a cluster-targeted JMS instance on a newly booted WebLogic Server instance. When this setting is configured on a store, it applies to all JMS artifacts that reference the store.

This allows time for the system to stabilize and dependent services to be restarted, preventing a system failure during a reboot.

- A value > is the time, in seconds, to delay before before loading resources after a failure and restart.
- A value of specifies no delay.

Note: This setting only applies when the JMS artifact is cluster-targeted and the Migration Policy is set to `On-Failure` or `Always`

Type: integer/int64

Constraints: Has Default Value: 60

insertsPerBatchMaximum

The maximum number of table rows that are inserted per database call.

- When possible, a JDBC store uses JDBC 3.0 batching to batch concurrent client requests.
- Both the maximum batch size for concurrent inserts and for concurrent writes are configurable.
- To disable JDBC 3.0 batching, set the maximum batch size to 1.
- The maximum batch size has no effect on the maximum number of concurrent client requests.

Type: integer/int32

Constraints: Has Default Value: 20, Minimum Value: 1, Maximum Value: 100

logicalName

The name used by subsystems to refer to different stores on different servers using the same name.

For example, an EJB that uses the timer service may refer to its store using the logical name, and this name may be valid on multiple servers in the same cluster, even if each server has a store with a different physical name.

Multiple stores in the same domain or the same cluster may share the same logical name. However, a given logical name may not be assigned to more than one store on the same server.

Type: string

Constraints: Has Default Value: null, Legal Null: true

migrationPolicy

Controls migration and restart behavior of cluster-targeted JMS service artifact instances. When this setting is configured on a cluster-targeted store, it applies to all JMS artifacts that reference the store. See the migratable target settings for enabling migration and restart on migratable-targeted JMS artifacts.

- **Off** Disables migration support for cluster-targeted JMS service objects, and changes the default for Restart In Place to false. If you want a restart to be enabled when the Migration Policy is Off, then Restart In Place must be explicitly configured to true. This policy cannot be combined with the Singleton Migration Policy.
- **On-Failure** Enables automatic migration and restart of instances on the failure of a subsystem Service or WebLogic Server instance, including automatic fail-back and load balancing of instances.
- **Always** Provides the same behavior as On-Failure and automatically migrates instances even in the event of a graceful shutdown or a partial cluster start.

Note: Cluster leasing must be configured for On-Failure and Always.

Messaging Bridge Notes:

- When an instance per server is desired for a cluster-targeted messaging bridge, Oracle recommends setting the bridge `Distributed Policy` and `Migration Policy` to `Distributed/Off`, respectively; these are the defaults.
- When a single instance per cluster is desired for a cluster-targeted bridge, Oracle recommends setting the bridge `Distributed Policy` and `Migration Policy` to `Singleton/On-Failure`, respectively.
- A `Migration Policy` of `Always` is not recommended for bridges.
- If you cannot cluster-target a bridge and still need singleton behavior in a configured cluster, you can target the bridge to a migratable target and configure the `Migration Policy` on the migratable target to `Exactly-Once`.

Type: string

Constraints: Has Default Value: Off, Legal Values: Off, On-Failure, Always

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

`Name=user-specified-name`

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

numberOfRestartAttempts

Specifies the maximum number of restart attempts.

- A value > specifies the maximum number of restart attempts.
- A value of 0 specifies the same behavior as setting `getRestartInPlace` to `false`
- A value of -1 means infinite retry restart until it either starts or the server instance shuts down.

Type: integer/int32

Constraints: Has Default Value: 6, Minimum Value: -1

oraclePiggybackCommitEnabled

Enables committing a batch of INSERT or DELETE operations with the last operation of the transaction instead of issuing a separate commit call to database server which saves a server round trip. This feature benefits applications that have many transactions of a small number of operations or small messages. This feature should be used only when configuring a JDBC store in Oracle Exalogic environments.

Type: boolean

Constraints: Has Default Value: false

partialClusterStabilityDelaySeconds

Specifies the amount of time, in seconds, to delay before a partially started cluster starts all cluster-targeted JMS artifact instances that are configured with a Migration Policy of `Always` or `On-Failure`.

Before this timeout expires or all servers are running, a cluster starts a subset of such instances based on the total number of servers running and the configured cluster size. Once the timeout expires or all servers have started, the system considers the cluster stable and starts any remaining services.

This delay ensures that services are balanced across a cluster even if the servers are started sequentially. It is ignored after a cluster is fully started (stable) or when individual servers are started.

- A value > specifies the time, in seconds, to delay before a partially started cluster starts dynamically configured services.
- A value of 0 specifies no delay.

Type: integer/int64

Constraints: Has Default Value: 240

prefixName

The prefix for the JDBC store's database table (`WLStore`), in the following format:

`[[catalog.]schema.]prefix`

Each period symbol in the `[[catalog.]schema.]prefix` format is significant, where schema generally corresponds to username in many databases. When no prefix is specified, the JDBC store table name is simply `WLStore` and the database implicitly determines the schema according to the JDBC connection's user. As a best practice, you should always configure a prefix for the JDBC `WLStore` table name.

For specific guidelines about using JDBC store prefixes, refer to the "Using the WebLogic Store" section of *Designing and Configuring WebLogic Server Environments*

Type: string

Constraints: Has Default Value: null

reconnectRetryIntervalMillis

The length of time in milliseconds between reconnection attempts during the reconnection retry period.

The reconnection interval applies to JDBC connections regardless of the database that is used for the JDBC store.

The default value is 200 milliseconds

Type: integer/int32

Constraints: Has Default Value: 200, Minimum Value: 100, Maximum Value: 10000

reconnectRetryPeriodMillis

Returns the length of time in milliseconds during which the persistent store will attempt to re-establish a connection to the database. Successive reconnection attempts will be attempted after a fixed delay that is specified by the reconnection retry interval.

The reconnection period applies to JDBC connections regardless of the database that is used for the JDBC store.

The default value is 1000

Type: integer/int32

Constraints: Has Default Value: 1000, Minimum Value: 200, Maximum Value: 300000

restartInPlace

Enables a periodic automatic in-place restart of failed cluster-targeted or standalone-server-targeted JMS artifact instance(s) running on healthy WebLogic Server instances. See the migratable target settings for in-place restarts of migratable-targeted JMS artifacts. When the Restart In Place setting is configured on a store, it applies to all JMS artifacts that reference the store.

- If the Migration Policy of the JMS artifact is set to `Off`, Restart In Place is disabled by default.
- If the Migration Policy of the JMS artifact is set to `On-Failure` or `Always`, Restart In Place is enabled by default.
- This attribute is not used by WebLogic messaging bridges which automatically restart internal connections as needed.
- For a JMS artifact that is cluster-targeted and the Migration Policy is set to `On-Failure` or `Always`, if restart fails after the configured maximum retry attempts, it will migrate to a different server within the cluster.

Type: boolean

secondsBetweenRestarts

Specifies the amount of time, in seconds, to wait in between attempts to restart a failed service instance.

Type: integer/int32

Constraints: Has Default Value: 30, Minimum Value: 1

tags

Return all tags on this Configuration MBean

Type: array of string

targets

The server instances, clusters, or migratable targets defined in the current domain that are candidates for hosting a file store, JDBC store, or replicated store. If scoped to a Resource Group or Resource Group Template, the target is inherited from the Virtual Target.

When selecting a cluster, the store must be targeted to the same cluster as the JMS server. When selecting a migratable target, the store must be targeted it to the same migratable target as the migratable JMS server or SAF agent. As a best practice, a path service should use its own custom store and share the same target as the store.

Type: array of weblogic.management.configuration.TargetMBean references

threeStepThreshold

Specifies the threshold, in bytes, when the JDBC store uses 3 steps (insert, select, populate) instead of 1 step (insert) to populate an Oracle Blob data type.

Applies only to Oracle databases where a Blob data type is used instead of the default Long Raw data type for record data.

The default value is 200000.

Type: integer/int32

Constraints: Has Default Value: 200000, Minimum Value: 4000, Maximum Value: 2147483647

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

workerCount

The number of JDBC store worker threads to process the workload.

- A value of 1 indicates a single thread is used (the default).
- A value greater than 1 indicates that multiple threads are used.
- For Oracle databases, Oracle recommends users rebuild the primary key index into a reverse index for the JDBC Store table when the worker count is greater than 1.
- For non-Oracle databases, refer to the database provider's documentation for help with indexing.

Type: integer/int32

Constraints: Has Default Value: 1, Minimum Value: 1, Maximum Value: 1000

workerPreferredBatchSize

Specifies the batch size when the `Worker Count` attribute is configured to a value greater than 1.

Used to configure the workload the JDBC store incrementally puts on each worker thread. The workload consists of IO requests which are grouped and pushed to each JDBC worker thread for processing. If the IO request is very large (for example 1M), then tune this attribute to a smaller value.

Type: integer/int32

Constraints: Has Default Value: 10, Minimum Value: 1, Maximum Value: 2147483647

weblogic.management.configuration.JDBCSystemResourceMBean

This bean defines a system-level JDBC resource. It links a separate descriptor that specifies the definition.

The properties of the `weblogic.management.configuration.JDBCSystemResourceMBean` entity are as follows:

compatibilityName

This is only set for beans created as a result of conversion from an 8.1 application configured using `ApplicationMBean` and `ComponentMBean`.

Standalone modules in 8.1 have both an `ApplicationMBean` name and `ComponentMBean` name. This attribute stores the name of the latter, to be used when the server creates the transient `ComponentMBean` for backward compatibility.

Type: string

deploymentOrder

An integer value that indicates when this unit is deployed, relative to other deployable units on a server, during startup.

Units with lower values are deployed before those with higher values.

Type: integer/int32

Constraints: Has Default Value: 100

deploymentPrincipalName

A string value that indicates the principal that should be used when deploying the file or archive during startup and shutdown. This principal will be used to set the current subject when calling out into application code for interfaces such as `ApplicationLifecycleListener`. If no principal name is specified, then the anonymous principal will be used.

Type: string

descriptorFileName

The name of the file containing this configuration. This is a relative name rooted at `DOMAIN_DIR/config`. By default the file resides in the `jdbc` subdirectory and derives its name from the bean name using the following pattern:

```
<beanName>.xml
```

Note that this is a read-only property that can only be set when the bean is created.

Type: string

Constraints: Read Only

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

moduleType

The values match those defined by jsr88. This attribute may move to another MBean.

Type: string

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

Name=user-specified-name

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

resource

Return the Descriptor for the system resource. This should be overridden by the derived system resources.

Type: weblogic.descriptor.DescriptorBean reference

Constraints: Read Only

sourcePath

Type: string

tags

Return all tags on this Configuration MBean

Type: array of string

targets

You must select a target on which an MBean will be deployed from this list of the targets in the current domain on which this item can be deployed. Targets must be either servers or clusters. The deployment will only occur once if deployments overlap.

Type: array of weblogic.management.configuration.TargetMBean references

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.JDBCSystemResourceOverrideMBean

Defines a partition-specific JDBC data source attribute override of a data source descriptor referenced by a partition resource group definition.

The properties of the weblogic.management.configuration.JDBCSystemResourceOverrideMBean entity are as follows:

URL

The connection URL for the data source.

Type: string

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

initialCapacity

Returns the initial pool capacity for the partition datasource. The value -1 indicates that the attribute is not set.

Type: integer/int32

Constraints: Has Default Value: -1

maxCapacity

Returns the max pool capacity for the partition datasource. The value -1 indicates that the attribute is not set.

Type: integer/int32

Constraints: Has Default Value: -1

minCapacity

Returns the min pool capacity for the partition datasource. The value -1 indicates that the attribute is not set.

Type: integer/int32

Constraints: Has Default Value: -1

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

Name=user-specified-name

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

password

The password in clear text.

Type: string

Constraints: Encrypted

tags

Return all tags on this Configuration MBean

Type: array of string

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

user

The name of the user for the data source.

Type: string

weblogic.management.configuration.JMSBridgeDestinationMBean

This MBean represents a messaging bridge destination for a JMS messaging product. Each messaging bridge consists of two destinations that are being bridged:

- **Source:** The message producing destination. A bridge instance consumes messages from the source destination.
- **Target:** The destination where a bridge instance forwards messages produced by the source destination.

The properties of the `weblogic.management.configuration.JMSBridgeDestinationMBean` entity are as follows:

adapterJNDIName

The JNDI name of the adapter used to communicate with the specified destination.

This name is specified in the adapter's deployment descriptor file and is used by the WebLogic Server Connector container to bind the adapter in WebLogic Server JNDI.

Type: string

Constraints: Has Default Value: eis.jms.WLSConnectionFactoryJNDIXA, Legal Null: true

connectionFactoryJNDIName

The connection factory's JNDI name for this JMS bridge destination.

Type: string

connectionURL

The connection URL for this JMS bridge destination.

Type: string

destinationJNDIName

The destination JNDI name for this JMS bridge destination.

Type: string

destinationType

The destination type (queue or topic) for this JMS bridge destination.

Type: string

Constraints: Has Default Value: Queue, Legal Values: Queue, Topic

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

initialContextFactory

The initial context factory name for this JMS bridge destination.

Type: string

Constraints: Has Default Value: weblogic.jndi.WLInitialContextFactory

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

Name=user-specified-name

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

tags

Return all tags on this Configuration MBean

Type: array of string

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

userName

The optional user name the adapter uses to access the bridge destination.

All operations on the specified destination are done using this user name and the corresponding password. Therefore, the User Name/Password for the source and target destinations must have permission to the access the underlying destinations in order for the messaging bridge to work.

Type: string

userPassword

The user password that the adapter uses to access the bridge destination.

As of 8.1 sp4, when you get the value of this attribute, WebLogic Server does the following:

1. Retrieves the value of the `UserPasswordEncrypted` attribute.
2. Decrypts the value and returns the unencrypted password as a String.

When you set the value of this attribute, WebLogic Server does the following:

1. Encrypts the value.
2. Sets the value of the `UserPasswordEncrypted` attribute to the encrypted value.

Using this attribute (`UserPassword`) is a potential security risk because the String object (which contains the unencrypted password) remains in the JVM's memory until garbage collection removes it and the memory is reallocated. Depending on how memory is allocated in the JVM, a significant amount of time could pass before this unencrypted data is removed from memory.

Instead of using this attribute, use `UserPasswordEncrypted`

Type: string

Constraints: Encrypted

weblogic.management.configuration.JMSInteropModuleMBean

This bean defines a system-level JMS resource. It links a separate descriptor that specifies the definition.

The properties of the weblogic.management.configuration.JMSInteropModuleMBean entity are as follows:

compatibilityName

This is only set for beans created as a result of conversion from an 8.1 application configured using ApplicationMBean and ComponentMBean.

Standalone modules in 8.1 have both an ApplicationMBean name and ComponentMBean name. This attribute stores the name of the latter, to be used when the server creates the transient ComponentMBean for backward compatibility.

Type: string

deploymentOrder

An integer value that indicates when this unit is deployed, relative to other deployable units on a server, during startup.

Units with lower values are deployed before those with higher values.

Type: integer/int32

Constraints: Has Default Value: 100

deploymentPrincipalName

A string value that indicates the principal that should be used when deploying the file or archive during startup and shutdown. This principal will be used to set the current subject when calling out into application code for interfaces such as ApplicationLifecycleListener. If no principal name is specified, then the anonymous principal will be used.

Type: string

descriptorFileName

The name of the file that contains the module configuration. By default the file resides in the DOMAIN_DIR/config/jms directory.

The module file derives its name from the bean name using the following pattern:

<beanName>.xml

Note that this is a read-only property that can only be set when the bean is created.

Type: string

Constraints: Read Only

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

moduleType

The values match those defined by jsr88. This attribute may move to another MBean.

Type: string

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

Name=user-specified-name

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

resource

Return the Descriptor for the system resource. This should be overridden by the derived system resources.

Type: `weblogic.descriptor.DescriptorBean` reference

Constraints: Read Only

sourcePath

Type: string

tags

Return all tags on this Configuration MBean

Type: array of string

targets

You must select a target on which an MBean will be deployed from this list of the targets in the current domain on which this item can be deployed. Targets must be either servers or clusters. The deployment will only occur once if deployments overlap.

Type: array of `weblogic.management.configuration.TargetMBean` references

Constraints: Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.JMSMessageLogFileMBean

This defines the configuration aspects of the logs for a jms server.

The properties of the weblogic.management.configuration.JMSMessageLogFileMBean entity are as follows:

bufferSizeKB

Gets the underlying log buffer size in kilobytes

Type: integer/int32

Constraints: Has Default Value: 8

dateFormatPattern

The date format pattern used for rendering dates in the log. The DateFormatPattern string conforms to the specification of the `java.text.SimpleDateFormat` class.

Type: string

Constraints: Legal Null: true

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

fileCount

The maximum number of log files that the server creates when it rotates the log. This number does not include the file that the server uses to store current messages. (Requires that you enable Number of Files Limited.)

Type: integer/int32

Constraints: Has Default Value: 7, Has Production Mode Default Value: 100, Minimum Value: 1, Maximum Value: 99999

fileMinSize

The size (1 - 2097150 kilobytes) that triggers the server to move log messages to a separate file. The default is 500 kilobytes. After the log file reaches the specified minimum size, the next time the server checks the file size, it will rename the current log file as `SERVER_NAME.lognnnn` and create a new one to store subsequent messages. (Requires that you specify a file rotation type of Size.)

Type: integer/int32

Constraints: Has Default Value: 500, Has Production Mode Default Value: 5000, Minimum Value: 1, Maximum Value: 2097150

fileName

The name of the file that stores current JMS server log messages. Usually it is a computed value based on the name of the parent of this MBean. For example, for a JMS server log, it is `jmsserverName.log`

However, if the name of the parent cannot be obtained, the file name is `weblogic.log`. If you specify a relative pathname, it is interpreted as relative to the server's root directory.

To include a time and date stamp in the file name when the log file is rotated, add `java.text.SimpleDateFormat` variables to the file name. Surround each variable with percentage (%) characters.

For example, if the file name is defined to be `myjmsserver_%yyyy%_%MM%_%dd%_%hh%_%mm%.log`, the log file will be named `myserver_YYYY_mm_dd_hh_mm.log`

When the log file is rotated, the rotated file name contains the date stamp. For example, if the log file is rotated on 2 April, 2005 at 10:05 AM, the log file that contains the old messages will be named `myserver_2005_04_02_10_05.log`

If you do not include a time and date stamp, the rotated log files are numbered in order of creation. For example, `myjmsserver.log00007`

Type: string

fileTimeSpan

The interval (in hours) at which the server saves old log messages to another file. (Requires that you specify a file rotation type of `TIME`.)

Type: integer/int32

Constraints: Has Default Value: 24, Minimum Value: 1

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

logFileRotationDir

The directory where the rotated log files will be stored. By default the rotated files are stored in the same directory where the log file is stored.

Type: string

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

Name=user-specified-name

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

numberOfFilesLimited

Indicates whether to limit the number of log files that this server instance creates to store old messages. (Requires that you specify a file rotation type of `SIZE` or `TIME`.)

After the server reaches this limit, it deletes the oldest log file and creates a new log file with the latest suffix.

If you do not enable this option, the server creates new files indefinitely and you must clean up these files as you require.

Type: boolean

Constraints: Has Default Value: true, Has Production Mode Default Value: true

rotateLogOnStartup

Specifies whether a server rotates its log file during its startup cycle. The default value in production mode is false.

Type: boolean

Constraints: Has Default Value: true, Has Production Mode Default Value: false

rotationTime

Determines the start time (hour and minute) for a time-based rotation sequence.

At the time that this value specifies, the server renames the current log file. Thereafter, the server renames the log file at an interval that you specify in File Time Span.

Note that WebLogic Server sets a threshold size limit of 500 MB before it forces a hard rotation to prevent excessive log file growth.

Use the following format: H:mm, where

- H is Hour in day (0-23)
- mm is the minute in hour

Type: string

Constraints: Has Default Value: 00:00

rotationType

Criteria for moving old log messages to a separate file.

- NONE Messages accumulate in a single file. You must erase the contents of the file when the size is too large. Note that WebLogic Server sets a threshold size limit of 500 MB before it forces a hard rotation to prevent excessive log file growth.
- SIZE When the log file reaches the size that you specify in FileMinSize, the server renames the file as *SERVER_NAME.lognnnnn*
- TIME At each time interval that you specify in TimeSpan, the server renames the file as *SERVER_NAME.lognnnnn*

After the server renames a file, subsequent messages accumulate in a new file with the name that you specified as the log file name.

Type: string

Constraints: Has Default Value: bySize, Legal Values: bySize, byTime, none

tags

Return all tags on this Configuration MBean

Type: array of string

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.JMSSAFMessageLogFileMBean

This defines the configuration aspects of the logs for a jms server.

The properties of the `weblogic.management.configuration.JMSSAFMessageLogFileMBean` entity are as follows:

bufferSizeKB

Gets the underlying log buffer size in kilobytes

Type: integer/int32

Constraints: Has Default Value: 8

dateFormatPattern

The date format pattern used for rendering dates in the log. The `DateFormatPattern` string conforms to the specification of the `java.text.SimpleDateFormat` class.

Type: string

Constraints: Legal Null: true

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to `config.xml`

Type: boolean

Constraints: Read Only, Has Default Value: false

fileCount

The maximum number of log files that the server creates when it rotates the log. This number does not include the file that the server uses to store current messages. (Requires that you enable Number of Files Limited.)

Type: integer/int32

Constraints: Has Default Value: 7, Has Production Mode Default Value: 100, Minimum Value: 1, Maximum Value: 99999

fileMinSize

The size (1 - 2097150 kilobytes) that triggers the server to move log messages to a separate file. The default is 500 kilobytes. After the log file reaches the specified minimum size, the next time the server checks the file size, it will rename the current log file as `SERVER_NAME.lognnnnn` and create a new one to store subsequent messages. (Requires that you specify a file rotation type of `Size`.)

Type: integer/int32

Constraints: Has Default Value: 500, Has Production Mode Default Value: 5000, Minimum Value: 1, Maximum Value: 2097150

fileName

Type: string

fileTimeSpan

The interval (in hours) at which the server saves old log messages to another file. (Requires that you specify a file rotation type of `TIME`.)

Type: integer/int32

Constraints: Has Default Value: 24, Minimum Value: 1

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

logFileRotationDir

The directory where the rotated log files will be stored. By default the rotated files are stored in the same directory where the log file is stored.

Type: string

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

`Name=user-specified-name`

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

numberOfFilesLimited

Indicates whether to limit the number of log files that this server instance creates to store old messages. (Requires that you specify a file rotation type of `SIZE` or `TIME`.)

After the server reaches this limit, it deletes the oldest log file and creates a new log file with the latest suffix.

If you do not enable this option, the server creates new files indefinitely and you must clean up these files as you require.

Type: boolean

Constraints: Has Default Value: true, Has Production Mode Default Value: true

rotateLogOnStartup

Specifies whether a server rotates its log file during its startup cycle. The default value in production mode is false.

Type: boolean

Constraints: Has Default Value: true, Has Production Mode Default Value: false

rotationTime

Determines the start time (hour and minute) for a time-based rotation sequence.

At the time that this value specifies, the server renames the current log file. Thereafter, the server renames the log file at an interval that you specify in File Time Span.

Note that WebLogic Server sets a threshold size limit of 500 MB before it forces a hard rotation to prevent excessive log file growth.

Use the following format: H:mm, where

- H is Hour in day (0-23)
- mm is the minute in hour

Type: string

Constraints: Has Default Value: 00:00

rotationType

Criteria for moving old log messages to a separate file.

- NONE Messages accumulate in a single file. You must erase the contents of the file when the size is too large. Note that WebLogic Server sets a threshold size limit of 500 MB before it forces a hard rotation to prevent excessive log file growth.
- SIZE When the log file reaches the size that you specify in `FileMinSize`, the server renames the file as `SERVER_NAME.lognnnnn`
- TIME At each time interval that you specify in `TimeSpan`, the server renames the file as `SERVER_NAME.lognnnnn`

After the server renames a file, subsequent messages accumulate in a new file with the name that you specified as the log file name.

Type: string

Constraints: Has Default Value: bySize, Legal Values: bySize, byTime, none

tags

Return all tags on this Configuration MBean

Type: array of string

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.JMSServerMBean

This class represents a JMS server. A JMS server manages connections and message requests on behalf of clients.

The properties of the `weblogic.management.configuration.JMSServerMBean` entity are as follows:

allowsPersistentDowngrade

Specifies whether JMS clients will get an exception when sending persistent messages to a destination targeted to a JMS server that does not have a persistent store configured. This parameter only has effect when the `Store Enabled` parameter is disabled (false).

When set to false, the default, clients will get an exception when sending persistent messages to a JMS server with no store configured. When set to true, then persistent messages are downgraded to non-persistent; however, the send operations are allowed to continue.

Type: boolean

Constraints: Has Default Value: false

blockingSendPolicy

Determines whether the JMS server delivers smaller messages before larger ones when a destination has exceeded its maximum number of messages. `FIFO` prevents the JMS server from delivering smaller messages when larger ones are already waiting for space. `Preemptive` allows smaller send requests to preempt previous larger ones when there is sufficient space for smaller messages on the destination.

This policy is defined only for the JMS server; it cannot be set on individual destinations.

Additional information on the `FIFO` and `Preemptive` policies is provided below.

`FIFO` (first in, first out) indicates that all send requests for the same destination are queued up one behind the other until space is available. No send request is permitted to successfully complete if there is another send request waiting for space before it. When space is limited, the `FIFO` policy prevents the starvation of larger requests because smaller requests cannot continuously use the remaining available space. Smaller requests are delayed, though not starved, until the larger request can be completed. When space does become available, requests are considered in the order in which they were made. If there is sufficient space for a given request, then that request is completed and the next request is considered. If there is insufficient space for a given request, then no further requests are considered until sufficient space becomes available for the current request to complete.

`Preemptive` indicates that a send operation can preempt other blocking send operations if space is available. That is, if there is sufficient space for the current request, then that space is used even if there are other requests waiting for space. When space is limited, the `Preemptive` policy can result in the starvation of larger requests. For example, if there is insufficient available space for a large request, then it is queued up behind other existing requests. When space does become available, all requests are considered in the order in which they were originally made. If there is sufficient space for a given request, then that request is allowed to continue and the next request is considered. If there is insufficient space for a given request, then that request is skipped and the next request is considered.

Type: string

Constraints: Has Default Value: `FIFO`, Legal Values: `FIFO`, `Preemptive`

bytesMaximum

The maximum number of bytes that can be stored in this JMS server. A value of `-1` removes any WebLogic Server limits.

Because excessive bytes volume can cause memory saturation, Oracle recommends that this maximum corresponds to the total amount of system memory available after accounting for the rest of your application load.

Range of Values: \geq `BytesThresholdHigh`

Type: integer/int64

Constraints: Has Default Value: `-1`, Minimum Value: `-1`, Maximum Value: `9223372036854775807`

bytesThresholdHigh

The upper threshold (number of bytes stored in this JMS server) that triggers flow control and logging events. A value of `-1` disables the events for this JMS server.

The triggered events are:

- **Log Messages** - A message is logged on the server indicating a high threshold condition.
- **Flow Control** - If flow control is enabled, the JMS server becomes armed and instructs producers to begin decreasing their message flow.

Range of Values: <= BytesMaximum; >= BytesThresholdLow

Type: integer/int64

Constraints: Has Default Value: -1, Minimum Value: -1, Maximum Value: 9223372036854775807

bytesThresholdLow

The lower threshold (number of bytes stored in this JMS server) that triggers flow control and logging events. A value of -1 disables the events for this JMS server.

If the number of bytes falls below this threshold, the triggered events are:

- **Log Messages** - A message is logged on the server indicating that the threshold condition has cleared.
- **Flow Control** - If flow control is enabled, the JMS server becomes disarmed and instructs producers to begin increasing their message flow.

Range of Values: <= BytesThresholdHigh

Type: integer/int64

Constraints: Has Default Value: -1, Minimum Value: -1, Maximum Value: 9223372036854775807

consumptionPausedAtStartup

Indicates whether consumption is paused at startup on destinations targeted to this JMS server at startup. A destination cannot receive any new messages while it is paused.

When the value is set to `true`, then immediately after the host server instance is booted, then this JMS server and its targeted destinations are modified such that they are in a "consumption paused" state, which prevents any message consuming activity on those destinations.

To allow normal message consumption on the destinations, later you will have to change the state of this JMS server to a "consumption enabled" state by setting this value to `false`, and then either redeploy the JMS server or reboot the hosting server instance.

When the value is set to `default`, then the Consumption Paused At Startup is determined based on the corresponding setting on the individual destination.

If the value is changed and activated, you need to restart any servers to which the MBean is targeted before the value will take effect (even though you do not get a warning in the Console that the server needs to be restarted).

Type: string

Constraints: Has Default Value: default

deploymentOrder

A priority that the server uses to determine when it deploys an item. The priority is relative to other deployable items of the same type.

For example, the server prioritizes and deploys all EJBs before it prioritizes and deploys startup classes.

Items with the lowest Deployment Order value are deployed first. There is no guarantee on the order of deployments with equal Deployment Order values. There is no guarantee of ordering across clusters.

Type: integer/int32

Constraints: Has Default Value: 1000, Minimum Value: 0, Maximum Value: 2147483647

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

expirationScanInterval

The number of seconds between this JMS server's cycles of scanning local destinations for expired messages. A value of 0 disables active scanning. A very large scan interval effectively disables active scanning.

With scanning disabled, users still do not receive expired messages and any expired messages that are discovered by other system activities are removed. However, expired messages sitting in idle destinations (such as an inactive queue or disconnected durable subscriber) are not removed and continue to consume system resources.

The scanning cycle for expired messages occurs as follows:

- After the specified waiting period, the JMS server devotes a separate thread to scan all of its local destinations for expired messages.
- After the scanning is completed, all located expired messages are processed according to the specified Expiration Policy on the destination (Discard, Log, or Redirect).
- The entire process repeats after another specified waiting period.

Note: Because a new scan does not start until the current one is finished and until the specified waiting period ends, an expired message could still remain in the system for the maximum scan waiting period plus the amount of time it takes to perform the scan.

Type: integer/int32

Constraints: Has Default Value: 30, Minimum Value: 0, Maximum Value: 2147483647

hostingTemporaryDestinations

Specifies whether this JMS server can be used to host temporary destinations.

If this field is enabled and no **Temporary Template Name** is defined, then the temporary destinations created on this JMS server will use all default destination values. If this field is disabled, then the JMS template to be used for creating temporary destinations is specified by the **Temporary Template Name** field. If this field is disabled, then this JMS server will not host temporary destinations.

Type: boolean

Constraints: Has Default Value: true

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

insertionPausedAtStartup

Indicates whether insertion is paused at startup on destinations targeted to this JMS server. A destination cannot receive any new messages while it is paused.

When the value is set to `true`, then immediately after the host server instance is booted, then this JMS server and its targeted destinations are modified such that they are in a "insertion paused" state, which results preventing messages that are result of the "in-flight" work completion to arrive on those destinations.

Note: For a detailed definition of "in-flight" work/messages, see `weblogic.management.runtime.JMSServerRuntimeMBean#resumeInsertion` and `weblogic.management.runtime.JMSDestinationRuntime#resumeInsertion`

To allow in-flight work messages to appear on the destinations, later you will have to change the state of this JMS server to an "insertion enabled" state by setting this value to `false`, and then either redeploy the JMS server or reboot the hosting server instance.

When the value is set to `default`, then the Insertion Paused At Startup is determined based on the corresponding setting on the individual destination.

If the value is changed and activated, you need to restart any servers to which the MBean is targeted before the value will take effect (even though you do not get a warning in the Console that the server needs to be restarted).

Type: string

Constraints: Has Default Value: default

maximumMessageSize

The maximum number of bytes allowed in individual messages on this JMS server. The size of a message includes the message body, any user-defined properties, and the user-defined JMS header fields `JMSCorrelationID` and `JMSType`

The maximum message size is only enforced for the initial production of a message. Messages that are redirected to an error destination or forwarded to a member of a distributed destination are not checked for size. For instance, if a destination and its corresponding error destination are configured with a maximum message size of 128K bytes and 64K bytes, respectively, a message of 96K bytes could be redirected to the error destination (even though it exceeds the 64K byte maximum), but a producer could not directly send the 96K byte message to the error destination.

Note: Any change to this maximum affects only incoming messages; stored messages are not affected.

Type: integer/int32

Constraints: Has Default Value: 2147483647, Minimum Value: 0, Maximum Value: 2147483647

messageBufferSize

The amount of memory (in bytes) that this JMS server can use to store message bodies before it writes them to disk. When the JMS server writes the message bodies to disk, it clears them from memory.

A value of -1 (the default) specifies that the server will automatically determine a size based on the maximum heap size of the JVM. This default will be set to either one-third the maximum heap size, or 512 megabytes, whichever is smaller.

The larger the buffer, the more memory JMS will consume when many messages are waiting on queues or topics. Once the buffer is surpassed, JMS may write message bodies to the directory specified by `PagingDirectory` in an effort to reduce memory usage below this buffer.

Surpassing the buffer size does not stop the JMS server from accepting new messages. It is still possible to run out of memory if messages are arriving faster than they can be written to disk. Users with high messaging loads who wish to support the highest possible availability should consider setting a quota or setting a threshold and enabling flow control.

Paging is always supported.

Type: integer/int64

Constraints: Has Default Value: -1, Minimum Value: -1, Maximum Value: 9223372036854775807

messageCompressionOptions

Specifies the type of message compression used when JMS message body compression is enabled for Persistent Stores and JMS Paging Stores.

- Use `GZIP_DEFAULT_COMPRESSION` to enable message compression using the JDK GZIP API with `DEFAULT_COMPRESSION` level.
- Use `GZIP_BEST_COMPRESSION` to enable message compression using the JDK GZIP API with `BEST_COMPRESSION` level.
- Use `GZIP_BEST_SPEED` to enable message compression using the JDK GZIP API with `BEST_SPEED` level.
- Use `LZF` to enable message compression using Open Source LZF.

This attribute should be used only when configuring a WebLogic domain in an Oracle Exalogic environment.

Type: string

Constraints: Has Default Value: `GZIP_DEFAULT_COMPRESSION`, Legal Values: `GZIP_DEFAULT_COMPRESSION`, `GZIP_BEST_COMPRESSION`, `GZIP_BEST_SPEED`, `LZF`

messagesMaximum

The maximum number of messages that can be stored in this JMS server. A value of -1 removes any WebLogic Server limits.

Because excessive message volume can cause memory saturation, Oracle recommends that this value corresponds to the total amount of system memory available after accounting for the rest of your application load.

Range of Values: \geq `MessagesThresholdHigh`.

Type: integer/int64

Constraints: Has Default Value: -1, Minimum Value: -1, Maximum Value: 9223372036854775807

messagesThresholdHigh

The upper threshold (number of messages stored in this JMS server) that triggers flow control and logging events. A value of -1 disables the events for this JMS server.

If the number of messages exceeds this threshold, the triggered events are:

- **Log Messages** - A message is logged on the server indicating a high threshold condition.
- **Flow Control** - If flow control is enabled, the JMS server becomes armed and instructs producers to begin decreasing their message flow.

Range of Values: <= MessagesMaximum; >= MessagesThresholdLow.

Type: integer/int64

Constraints: Has Default Value: -1, Minimum Value: -1, Maximum Value: 9223372036854775807

messagesThresholdLow

The lower threshold (number of messages stored in this JMS server) that triggers flow control and logging events. A value of -1 disables the events for this JMS server.

If the number of messages falls below this threshold, the triggered events are:

- **Log Messages** - A message is logged on the server indicating that the threshold condition has cleared.
- **Flow Control** - If flow control is enabled, the JMS server becomes disarmed and instructs producers to begin increasing their message flow.

Note: This attribute is dynamically configurable.

Range of Values: <= MessagesThresholdHigh

Type: integer/int64

Constraints: Has Default Value: -1, Minimum Value: -1, Maximum Value: 9223372036854775807

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

Name=user-specified-name

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

pagingBlockSize

The smallest addressable block, in bytes, of a file. When a native `wlfileio` driver is available and the paging block size has not been configured by the user, the store selects the minimum OS specific value for unbuffered (direct) I/O, if it is within the range [512, 8192].

A paging store's block size does not change once the paging store creates its files. Changes to block size only take effect for new paging stores or after the current files have been deleted. See "Tuning the Persistent Store" in *Performance and Tuning for Oracle WebLogic Server*

If the value is changed and activated, you need to restart any servers to which the MBean is targeted before the value will take effect (even though you do not get a warning in the Console that the server needs to be restarted).

Type: integer/int32

Constraints: Has Default Value: -1, Minimum Value: -1, Maximum Value: 8192

pagingDirectory

Specifies where message bodies are written when the size of the message bodies in the JMS server exceeds the message buffer size.

If unspecified, messages are written to the default `tmp` directory inside the `server-name` subdirectory of a domain's root directory. For example, `domain-name/servers/server-name/tmp`, where `domain-name` is the root directory of your domain.

For best performance, this directory should not be the same as the directory used by the JMS server's persistent store.

If the value is changed and activated, you need to restart any servers to which the MBean is targeted before the value will take effect (even though you do not get a warning in the Console that the server needs to be restarted).

Type: string

Constraints: Has Default Value: null, Legal Null: true

pagingFileLockingEnabled

Determines whether OS file locking is used.

When file locking protection is enabled, a store boot fails if another store instance already has opened the store files. Do not disable this setting unless you have procedures in place to prevent multiple store instances from opening the same file. File locking is not required but helps prevent corruption in the event that two same-named file store instances attempt to operate in the same directories. This setting applies to both primary and cache files.

If the value is changed and activated, you need to restart any servers to which the MBean is targeted before the value will take effect (even though you do not get a warning in the Console that the server needs to be restarted).

Type: boolean

Constraints: Has Default Value: true

pagingIOBufferSize

The I/O buffer size, in bytes, automatically rounded down to the nearest power of 2.

- When a native `wfileio` driver is available, the setting applies to off-heap (native) memory.
- When a native `wfileio` driver is not available, the setting applies to JAVA heap memory.
- For the best runtime performance, Oracle recommends setting `PagingIOBufferSize` so that it is larger than the largest write (multiple concurrent store requests may be combined into a single write).

- See the JMS server runtime MBean attribute `PagingAllocatedIOBufferBytes` to find out the actual allocated off-heap (native) memory amount.

If the value is changed and activated, you need to restart any servers to which the MBean is targeted before the value will take effect (even though you do not get a warning in the Console that the server needs to be restarted).

Type: integer/int32

Constraints: Has Default Value: -1, Minimum Value: -1, Maximum Value: 67108864

pagingMaxFileSize

The paging maximum file size, in bytes.

- The `PagingMaxFileSize` value affects the number of files needed to accommodate a paging store of a particular size (number of files = paging store size/MaxFileSize rounded up).
- A paging store automatically reuses space freed by deleted records and automatically expands individual files up to `PagingMaxFileSize` if there is not enough space for a new record. If there is no space left in existing files for a new record, a paging store creates an additional file.
- A small number of larger files is normally preferred over a large number of smaller files as each file allocates Window Buffer and file handles.
- If `PagingMaxFileSize` is larger than $2^{24} * \text{PagingBlockSize}$, then `MaxFileSize` is ignored, and the value becomes $2^{24} * \text{PagingBlockSize}$. The default `PagingBlockSize` is 512, and $2^{24} * 512$ is 8 GB.

Oracle recommends not setting the Paging Max File Size above the default value of 1,342,177,280.

If the value is changed and activated, you need to restart any servers to which the MBean is targeted before the value will take effect (even though you do not get a warning in the Console that the server needs to be restarted).

Type: integer/int64

Constraints: Has Default Value: 1342177280, Minimum Value: 10485760

pagingMaxWindowBufferSize

The maximum amount of data, in bytes and rounded down to the nearest power of 2, mapped into the JVM's address space per paging store file. Applies only when a native `wfileio` library is loaded.

A window buffer does not consume Java heap memory, but does consume off-heap (native) memory. If the paging store is unable to allocate the requested buffer size, it allocates smaller and smaller buffers until it reaches `PagingMinWindowBufferSize`, and then fails if it cannot honor `PagingMinWindowBufferSize`.

Oracle recommends setting the max window buffer size to more than double the size of the largest write (multiple concurrently updated records may be combined into a single write), and greater than or equal to the file size, unless there are other constraints. 32-bit JVMs may impose a total limit of between 2 and 4GB for combined Java heap plus off-heap (native) memory usage.

See the JMS server runtime MBean attribute `PagingAllocatedWindowBufferBytes` to find out the actual allocated Window Buffer Size.

If the value is changed and activated, you need to restart any servers to which the MBean is targeted before the value will take effect (even though you do not get a warning in the Console that the server needs to be restarted).

Type: integer/int32

Constraints: Has Default Value: -1, Minimum Value: -1, Maximum Value: 1073741824

pagingMessageCompressionEnabled

Enables the JMS paging store to perform message body compression on persistent and non-persistent messages. When `false`, the default value, no compression is performed.

This attribute should be enabled only when configuring a WebLogic domain in an Oracle Exalogic environment.

Type: boolean

Constraints: Has Default Value: false

pagingMinWindowBufferSize

The minimum amount of data, in bytes and rounded down to the nearest power of 2, mapped into the JVM's address space per paging store file. Applies only when a native `wfileio` library is loaded. See Paging Maximum Window Buffer Size

If the value is changed and activated, you need to restart any servers to which the MBean is targeted before the value will take effect (even though you do not get a warning in the Console that the server needs to be restarted).

Type: integer/int32

Constraints: Has Default Value: -1, Minimum Value: -1, Maximum Value: 1073741824

persistentStore

The file or database in which this JMS server stores persistent messages. If unspecified, the JMS server uses the default persistent store that is configured on each targeted WebLogic Server instance. If the JMS server has a store configured, then the configured store is used to store persistent messages.

The disk-based file store or JDBC-accessible database store that you specify must be targeted to the same server, cluster, or migratable target instance as this JMS server. Multiple services on the same WebLogic Server instance, including multiple JMS servers, may share the same persistent store. Each service's persistent data will be kept apart.

If you specify a `PersistentStore`, the deprecated `Store` field must not be set. If neither the `PersistentStore` field nor the `Store` field are set, the JMS server supports persistent messaging using the default persistent store for the targeted WebLogic Server instance.

If the value is changed and activated, you need to restart any servers to which the MBean is targeted before the value will take effect (even though you do not get a warning in the Console that the server needs to be restarted).

Type: weblogic.management.configuration.PersistentStoreMBean reference

Constraints: Restart Required

productionPausedAtStartup

Specifies whether production is paused at server startup on destinations targeted to this JMS server. A destination cannot receive any new messages while it is paused.

When the value is set to `true`, then immediately after the host server instance is rebooted, then this JMS server and its targeted destinations are modified such that they are in a "production paused" state, which results in preventing new message production activities on those destinations.

To resume normal new message production activity, later you will have to change the state of this JMS server to a "production enabled" state by setting this value to `false`, and then either redeploy the JMS server or reboot the hosting server instance.

When the value is set to `default`, then the Production Paused At Startup is determined based on the corresponding setting on the individual destination.

If the value is changed and activated, you need to restart any servers to which the MBean is targeted before the value will take effect (even though you do not get a warning in the Console that the server needs to be restarted).

Type: string

Constraints: Has Default Value: default

storeEnabled

Specifies whether message persistence is supported for this JMS server.

- When set to `true`: If the JMS server has no store configured, the targeted WebLogic Server instance's default store is used to store persistent messages. If the JMS server has a store configured, then the configured store is used to store persistent messages.
- When set to `false`, then this JMS server does not support persistent messages, and instead downgrades them to non-persistent.
- The default value is `true`

Oracle recommends not setting this parameter to `false`. It is available to provide compatibility with older releases.

If the value is changed and activated, you need to restart any servers to which the MBean is targeted before the value will take effect (even though you do not get a warning in the Console that the server needs to be restarted).

Type: boolean

Constraints: Has Default Value: true

storeMessageCompressionEnabled

Enables the JMS store to perform message body compression. When set to `false`, the default value, no compression is performed.

This attribute should be enabled only when configuring a WebLogic domain in an Oracle Exalogic environment.

Type: boolean

Constraints: Has Default Value: false

tags

Return all tags on this Configuration MBean

Type: array of string

targets

The server instances, clusters, or a migratable targets defined in the current domain that are candidates for hosting the JMSSerer.

In a clustered environment, a recommended best practice is to use a cluster as a target or target a JMSServer to the same migratable target as the Persistent Store that it uses, so that a member server will not be a single point of failure. A JMSServer can also be configured to automatically migrate from an unhealthy server instance to a healthy server instance with the help of the automatic service migration feature.

Type: array of weblogic.management.configuration.TargetMBean references

temporaryTemplateName

The name of a configured JMS template that this JMS server uses to create temporary destinations.

Entering a template name, requires you to specify the JMS module that contains this template. However, a template name cannot be specified if the **Hosting Temporary Destinations** field is disabled.

Note: If the specified JMS template provides persistent store values, they are ignored because temporary destinations do not support persistent messaging.

Type: string

temporaryTemplateResource

The name of a JMS module that contains a template that this JMS server can use to create temporary destinations.

Entering a JMS module name requires you to specify a temporary template name. However, a module name cannot be specified if the **Hosting Temporary Destinations** field is disabled.

Type: string

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.JMSSystemResourceMBean

This bean defines a system-level JMS resource. It links a separate descriptor that specifies the definition.

The properties of the weblogic.management.configuration.JMSSystemResourceMBean entity are as follows:

compatibilityName

This is only set for beans created as a result of conversion from an 8.1 application configured using ApplicationMBean and ComponentMBean.

Standalone modules in 8.1 have both an ApplicationMBean name and ComponentMBean name. This attribute stores the name of the latter, to be used when the server creates the transient ComponentMBean for backward compatibility.

Type: string

deploymentOrder

An integer value that indicates when this unit is deployed, relative to other deployable units on a server, during startup.

Units with lower values are deployed before those with higher values.

Type: integer/int32

Constraints: Has Default Value: 100

deploymentPrincipalName

A string value that indicates the principal that should be used when deploying the file or archive during startup and shutdown. This principal will be used to set the current subject when calling out into application code for interfaces such as `ApplicationLifecycleListener`. If no principal name is specified, then the anonymous principal will be used.

Type: string

descriptorFileName

The name of the file that contains the module configuration. By default the file resides in the `DOMAIN_DIR/config/jms` directory.

The module file derives its name from the bean name using the following pattern:

```
<beanName>.xml
```

Note that this is a read-only property that can only be set when the bean is created.

Type: string

Constraints: Read Only

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to `config.xml`

Type: boolean

Constraints: Read Only, Has Default Value: false

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

moduleType

The values match those defined by jsr88. This attribute may move to another MBean.

Type: string

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

```
Name=user-specified-name
```

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

resource

Return the Descriptor for the system resource. This should be overridden by the derived system resources.

Type: weblogic.descriptor.DescriptorBean reference

Constraints: Read Only

sourcePath

Type: string

tags

Return all tags on this Configuration MBean

Type: array of string

targets

You must select a target on which an MBean will be deployed from this list of the targets in the current domain on which this item can be deployed. Targets must be either servers or clusters. The deployment will only occur once if deployments overlap.

Type: array of weblogic.management.configuration.TargetMBean references

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.JMSSystemResourceOverrideMBean

For each configuration entity that supports per-partition-override via a MBean, we have two MBeans, the original configure MBean and the corresponding override MBean, that eventually determine the effective settings of the configured resource. We mark an attribute of an override MBean "dynamic true" even though the original configure MBean masks it "dynamic false". This is to make sure that the overriding settings take effect on partition restart. Otherwise a server restart is required.

Defines partition-specific overrides for the most commonly overridden attributes in a JMS system resource descriptor file. It overrides some of the settings in a same-named JMSSystemResource MBean instance in the same multi-tenant scope to which this override MBean belongs.

The properties of the weblogic.management.configuration.JMSSystemResourceOverrideMBean entity are as follows:

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

Name=user-specified-name

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

tags

Return all tags on this Configuration MBean

Type: array of string

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.JMXMBean

Controls which JMX agents are initialized in the current WebLogic Server domain. Each JMX agent supports specific functions such as monitoring run-time statistics or modifying the domain's configuration.

The properties of the `weblogic.management.configuration.JMXMBean` entity are as follows:

compatibilityMBeanServerEnabled

Enables JMX clients to use the deprecated `MBeanHome` interface.

Prior to 9.0, WebLogic Server supported a typed API layer over its JMX layer. Your JMX application classes could import type-safe interfaces for WebLogic Server MBeans, retrieve a reference to the MBeans through the `weblogic.management.MBeanHome` interface, and invoke the MBean methods directly.

Type: boolean

Constraints: Has Default Value: true

domainMBeanServerEnabled

Specifies whether the Administration Server initializes the Domain MBean Server, which provides federated access to all run-time MBeans and read-only configuration MBeans in the domain. Through it, JMX clients can access all MBeans in a domain through a single connection.

The Administration Console and the WebLogic Scripting Tool use this MBean server for many (but not all) of their read operations.

This MBean server exists only on the Administration Server. The Administration Server initializes it the first time a JMX client requests a connection to it. If you set this attribute to `false`, the Administration Server will not start this MBean server and JMX clients cannot connect to it.

While this MBean server is instantiated lazily (only when requested), once it is instantiated it does use some memory and network traffic. Disabling this MBean server can conserve a minimal amount of resources, but the trade off is that JMX clients must maintain separate connections for each WebLogic Server's Runtime MBean Server.

Type: boolean

Constraints: Has Default Value: true

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

editMBeanServerEnabled

Specifies whether the Administration Server initializes the Edit MBean Server, which contains the hierarchy of MBeans used to make modifications to the domain's configuration. All JMX clients, including utilities such as the Administration Console and the WebLogic Scripting Tool, use the Edit MBean Server to modify a domain's configuration.

This MBean server exists only on the Administration Server. By default, when the Administration Server starts, it starts the Edit MBean Server. If you set the `EditMBeanServerEnabled` attribute to `false`, the Administration Server will not start this MBean server. If you disable this MBean server, JMX clients cannot modify the domain's configuration. You can, however, modify the domain configuration through the offline editing feature of WebLogic Scripting Tool.

Note:

Disabling the Edit MBean Server is not sufficient to prevent changes to a domain configuration. Because the WebLogic Server deployment service does not use JMX, the Administration Console and WLST can deploy or undeploy applications even if you have disabled the Edit MBean Server.

Type: boolean

Constraints: Has Default Value: true

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

invocationTimeoutSeconds

The number of seconds that internal WebLogic Server processes wait to connect to an MBean server, invoke an MBean server method, and return the results of the invocation. If the MBean server method does not complete (return) within the timeout period, WebLogic Server abandons its invocation attempt.

Some internal management processes within WebLogic Server require a server instance to connect to MBean servers in other WebLogic Server instances and invoke an MBean server method. The timeout period prevents the internal process from locking up if an MBean server cannot successfully return a method invocation.

A value of (zero) prevents the method invocation from timing out. With such a value, the internal process will wait indefinitely until the MBean server's method returns.

Type: integer/int32

Constraints: Has Default Value: 0, Minimum Value: 0, Maximum Value: 2147483647

managedServerNotificationsEnabled

Specifies whether the WebLogic Server Domain Runtime MBean Server will support notifications from the federated Runtime MBean Servers on the managed and administration servers.

Supporting notifications requires a significant amount of memory resources. A list of ObjectNames is maintained for each MBean from the Runtime MBean Servers. If notifications are not required for this domain, then disabling them will save on CPU and memory resources. This is particularly critical if there are large numbers of runtime MBeans and/or large numbers of servers.

Type: boolean

Constraints: Has Default Value: true

managementAppletCreateEnabled

Specifies whether the WebLogic Server MBean Servers will support creation of management applet (MLet) MBeans.

MLet MBeans allow a user to upload the MBean implementation from a remote server and should only be enabled if the environment and security manager restrict access to trusted JMX clients.

Type: boolean

Constraints: Has Default Value: false

managementEJBEnabled

Enables access to the Management EJB (MEJB), which is part of the Java EE Management APIs (JSR-77).

The Management API specification provides a standardized management data model for common resources on Java EE Web application servers.

The MEJB provides access to Java EE Managed Objects (JMOs), which describe the common Java EE resources. If you set this attribute to `false`, WebLogic Server does not register the MEJB in the JNDI tree, and effectively disables the Java EE Management APIs for the domain.

Type: boolean

Constraints: Has Default Value: true

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's

`javax.management.ObjectName`

`Name=user-specified-name`

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`;

Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

platformMBeanServerEnabled

Specifies whether each server instance initializes the JDK's platform MBean server. Enabling it, along with `isPlatformMBeanServerUsed`, causes WebLogic Server to use the platform MBean server as its Runtime MBean Server.

As of JDK 1.5, JVMs provide a platform MBean server that local processes can instantiate. There can be only one instance of the platform MBean server for each JVM. When a process instantiates this MBean server, the JVM creates several platform MXBeans that provide monitoring data for the JVM itself.

If you set this attribute to `true`, each WebLogic Server instance invokes the method `java.lang.management.ManagementFactory.getPlatformMBeanServer()` and thus causes the initialization of the JVM's MXBeans.

Type: boolean

Constraints: Has Default Value: false

platformMBeanServerUsed

Specifies whether WebLogic Server will use the platform MBean server for its Runtime MBean Server. Previously, WebLogic Server used the platform MBean server by default if it was enabled. This attribute provides a separation between enabling the platform MBean server and using it for WebLogic Server MBeans.

The default value for this attribute is based on the `DomainVersion` attribute of the `DomainMBean`. If the domain version is prior to 10.3.3.0, then the default value of this attribute is `false` and the platform MBean server is not used. If the domain version is 10.3.3.0 or higher, then the default value of this attribute is `true` and the platform MBean server is used.

In this case, the server's Runtime MBean Server uses the `MBeanServer` returned by `java.lang.management.ManagementFactory.getPlatformMBeanServer()` method as its MBean Server. This makes it possible to access the WebLogic Server MBeans and the JVM platform MXBeans from a single MBean server. In addition, if you enable the Runtime MBean Server to be the Platform MBean Server, local processes in the JVM can directly access this MBean server through the `MBeanServer` interface that `java.lang.management.ManagementFactory.getPlatformMBeanServer()` returns.

Type: boolean

runtimeMBeanServerEnabled

Specifies whether each server instance in the domain initializes its Runtime MBean Server, which provides access to a server's run-time MBeans and read-only configuration MBeans.

The Administration Console and the WebLogic Scripting Tool use this MBean server for some (but not all) of their read operations.

If `RuntimeMBeanServerEnabled` is true, each server starts its Runtime MBean Server during the server's startup cycle. If this attribute is false, no server instance in the domain will start its Runtime MBean Server.

Type: boolean

Constraints: Has Default Value: true

tags

Return all tags on this Configuration MBean

Type: array of string

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.JPAMBean

This interface provides access to the JPA configuration attributes. The methods defined herein are applicable for JPA configuration at the domain level.

The properties of the `weblogic.management.configuration.JPAMBean` entity are as follows:

defaultJPAProvider

The configured default JPA provider for the domain.

Type: string

Constraints: Has Default Value: `org.eclipse.persistence.jpa.PersistenceProvider`

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to `config.xml`

Type: boolean

Constraints: Read Only, Has Default Value: false

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

Name=user-specified-name

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

tags

Return all tags on this Configuration MBean

Type: array of string

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.JTAClusterMBean

This interface provides access to the JTA configuration attributes. The methods defined herein are applicable for JTA configuration at the cluster level.

The properties of the `weblogic.management.configuration.JTAClusterMBean` entity are as follows:

TLOGWriteWhenDeterminerExistsEnabled

Indicates two-phase transaction recovery logs are written even if one or more determiners are configured.

Type: boolean

Constraints: Has Default Value: false

WSATIssuedTokenEnabled

Specifies whether to use `issuedtoken` to enable authentication between the WS-AT coordinator and participant.

Type: boolean

Constraints: Has Default Value: false

WSATTransportSecurityMode

Specifies transport security mode required by WebService Transaction endpoints.

Transport Security options:

- **SSLNotRequired** All WebService Transaction protocol messages are exchanged over the HTTP channel.
- **SSLRequired** All WebService Transaction protocol messages are and can only be exchanged over the HTTPS.
- **ClientCertRequired** All WebService Transaction protocol messages are and can only be exchanged over the HTTPS, and WLS enforces the presence of client certificate

Type: string

Constraints: Has Default Value: SSLNotRequired, Legal Values: SSLNotRequired, SSLRequired, ClientCertRequired

abandonTimeoutSeconds

Specifies the maximum amount of time, in seconds, a transaction manager persists in attempting to complete the second phase of a two-phase commit transaction.

During the second phase of a two-phase commit transaction, the transaction manager continues to try to complete the transaction until all resource managers indicate that the transaction is completed. After the abandon transaction timer expires, no further attempt is made to resolve the transaction. If the transaction is in a prepared state before being abandoned, the transaction manager rolls back the transaction to release any locks held on behalf of the abandoned transaction.

Type: integer/int32

Constraints: Minimum Value: 1, Maximum Value: 2147483647

beforeCompletionIterationLimit

The maximum number of cycles that the transaction manager performs the `beforeCompletion` synchronization callback for this cluster.

Nothing prevents a Synchronization object from registering another during `beforeCompletion`, even those whose `beforeCompletions` have already been called. For example, an EJB can call another in its `ejbStore()` method. To accommodate this, the transaction manager calls all Synchronization objects, then repeats the cycle if new ones have been registered. This count sets a limit to the number of cycles that synchronization occurs.

Type: integer/int32

Constraints: Minimum Value: 1, Maximum Value: 2147483647

checkpointIntervalSeconds

The interval at which the transaction manager creates a new transaction log file and checks all old transaction log files to see if they are ready to be deleted.

Type: integer/int32

Constraints: Minimum Value: 10, Maximum Value: 1800

clusterwideRecoveryEnabled

Indicates that cluster-wide recovery is used for distributed transactions.

When enabled, recovery operations for a distributed transaction are applied to all the servers of the cluster hosting a `InterposedTransactionManager` rather than just the server hosting the `InterposedTransactionManager`.

Type: boolean

Constraints: Has Default Value: false

completionTimeoutSeconds

Specifies the maximum amount of time, in seconds, a transaction manager waits for all resource managers to respond and indicate if the transaction can be committed or rolled back.

- The default value is 0, which sets the value to approximately twice the default `transaction-timeout` value with a maximum value of 120 seconds. This value provides backward compatibility for prior releases without this setting.
- If the specified value is -1, the maximum value supported by this attribute is used.
- If the specified value exceeds the value set for `abandon-timeout-seconds`, the value of `abandon-timeout-seconds` is used.

Type: integer/int32

Constraints: Minimum Value: -1, Maximum Value: 2147483647

crossSiteRecoveryLeaseExpiration

The time after which a lease expires making it eligible for recovery by another site.

Type: integer/int32

Constraints: Has Default Value: 30, Minimum Value: 1, Maximum Value: 2147483647

crossSiteRecoveryLeaseUpdate

The time in seconds in which to update at lease timestamp.

Type: integer/int32

Constraints: Has Default Value: 10, Minimum Value: 1, Maximum Value: 2147483647

crossSiteRecoveryRetryInterval

The interval at which a lease for a given server in a recovery domain will be checked for takeover eligibility.

Type: integer/int32

Constraints: Has Default Value: 60, Minimum Value: 1, Maximum Value: 2147483647

determinerCandidateResourceInfoList

Returns a list of one or more transaction resources (determiners). A determiner's in-doubt transaction records are used during transaction recovery when a TLog is not present.

Type: array of

weblogic.management.configuration.DeterminerCandidateResourceInfoVBean

Constraints: Read Only

determiners

Specifies a list of one or more transaction resources (determiners) separated by line breaks. A determiner's in-doubt transaction records are used during transaction recovery when a TLog is not present.

Type: array of string

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

forgetHeuristics

Specifies whether the transaction manager automatically performs an XA Resource forget operation for heuristic transaction completions.

When enabled, the transaction manager automatically performs an XA Resource forget () operation for all resources as soon as the transaction learns of a heuristic outcome. Disable this feature only if you know what to do with the resource when it reports a heuristic decision.

Type: boolean

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

maxResourceRequestsOnServer

Maximum number of concurrent requests to resources allowed for each server.

Type: integer/int32

Constraints: Minimum Value: 10, Maximum Value: 2147483647

maxResourceUnavailableMillis

Maximum duration time, in milliseconds, that a resource is declared dead. After the duration, the resource is declared available again, even if the resource provider does not explicitly re-register the resource.

Type: integer/int64

Constraints: Minimum Value: 0, Maximum Value: 9223372036854775807

maxRetrySecondsBeforeDeterminerFail

The maximum amount of time, in seconds, WebLogic Server waits for the determiner to recover from a failure. If the determiner does not recover after this period, WebLogic Server sets the TLog health state to HEALTH_FAILED.

Type: integer/int32

Constraints: Has Default Value: 300, Minimum Value: 0, Maximum Value: 2147483647

maxTransactions

The maximum number of simultaneous in-progress transactions allowed on a server in this cluster.

Type: integer/int32

Constraints: Minimum Value: 1, Maximum Value: 2147483647

maxTransactionsHealthIntervalMillis

The interval for which the transaction map must be full for the JTA subsystem to declare its health as CRITICAL.

Type: integer/int64

Constraints: Minimum Value: 1000, Maximum Value: 9223372036854775807

maxUniqueNameStatistics

The maximum number of unique transaction names for which statistics are maintained.

The first 1001 unique transaction names are maintained as their own transaction name and stored in each statistic. After the 1001st transaction name is reached, the transaction name is stored as `weblogic.transaction.statistics.namedOverflow`, and the transaction statistic is also merged and maintained in `weblogic.transaction.statistics.namedOverflow`

A transaction name typically represents a category of business transactions, such as "funds-transfer."

Type: integer/int32

Constraints: Minimum Value: 0, Maximum Value: 2147483647

maxXACallMillis

Maximum allowed time duration, in milliseconds, for XA calls to resources. If a particular XA call to a resource exceeds the limit, the resource is declared unavailable.

Type: integer/int64

Constraints: Minimum Value: 0, Maximum Value: 9223372036854775807

migrationCheckpointIntervalSeconds

The time interval, in seconds, that the checkpoint is done for the migrated transaction logs (TLOGs).

Type: integer/int32

Constraints: Minimum Value: 1, Maximum Value: 2147483647

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

Name=user-specified-name

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

parallelXADispatchPolicy

The dispatch policy to use when performing XA operations in parallel.

Type: string

parallelXAEnabled

Indicates that XA calls are executed in parallel if there are available threads.

Type: boolean

purgeResourceFromCheckpointIntervalSeconds

The interval that a particular resource must be accessed within for it to be included in the checkpoint record.

Type: integer/int32

Constraints: Minimum Value: 0, Maximum Value: 2147483647

recoverySiteName

The name of the site whose transactions this site/domain will recover in the event that intra-cluster transaction service migration is not successful or efficient.

Type: string

recoveryThresholdMillis

The interval that recovery is attempted until the resource becomes available.

Type: integer/int64

Constraints: Minimum Value: 60000, Maximum Value: 9223372036854775807

securityInteropMode

Specifies the security mode of the communication channel used for XA calls between servers that participate in a global transaction. All server instances in a domain must have the same security mode setting.

Security Interoperability Mode options:

- **default** The transaction coordinator makes calls using the kernel identity over an admin channel if it is enabled, and `anonymous` otherwise. Man-in-the-middle attacks are possible if the admin channel is not enabled.
- **performance** The transaction coordinator makes calls using `anonymous` at all times. This implies a security risk since a malicious third party could then try to affect the outcome of transactions using a man-in-the-middle attack.
- **compatibility** The transaction coordinator makes calls as the kernel identity over an insecure channel. This is a high security risk because a successful man-in-the-middle attack would allow the attacker to gain administrative control over both domains. This setting should only be used when strong network security is in place.

Type: string

serializeEnlistmentsGCIntervalMillis

The time interval, in milliseconds, at which internal objects used to serialize resource enlistment are cleaned up.

Type: integer/int64

Constraints: Minimum Value: 0

shutdownGracePeriod

Indicates how long the server should wait for active transactions to complete before allowing shutdown.

Type: integer/int32

Constraints: Has Default Value: 180

tags

Return all tags on this Configuration MBean

Type: array of string

tightlyCoupledTransactionsEnabled

Indicates tight coupling of transaction branches that span different transaction manager systems.

When enabled, WebLogic uses the transaction identifier of a transaction imported by the `InterposedTransactionManager` for XA calls rather than an internally mapped `Xid`. This applies to inter-domain WebLogic transactions and transactions imported from Tuxedo. This allows for tight coupling of transaction branches for transactions that span across different transaction manager systems.

If a transaction between WebLogic and Tuxedo resources uses a GridLink Data Source with GridLink Affinity enabled, the XA Affinity context is automatically used for the transaction.

Type: boolean

Constraints: Has Default Value: false

timeoutSeconds

Specifies the maximum amount of time, in seconds, an active transaction is allowed to be in the first phase of a two-phase commit transaction. If the specified amount of time expires, the transaction is automatically rolled back.

Type: integer/int32

Constraints: Minimum Value: 1, Maximum Value: 2147483647

twoPhaseEnabled

Indicates that the two-phase commit protocol is used to coordinate transactions across two or more resource managers.

If not selected:

- Two-phase commit is disabled and any attempt to use two-phase commit results in a RollbackException being thrown.
- All transaction logging is disabled, including checkpoint records.

Type: boolean

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

unregisterResourceGracePeriod

The amount of time, in seconds, a transaction manager waits for transactions involving the resource to complete before unregistering a resource. This grace period helps minimize the risk of abandoned transactions because of an unregistered resource, such as a JDBC data source module packaged with an application.

During the specified grace period, the `unregisterResource` call blocks until the call returns and no new transactions are started for the associated resource. If the number of outstanding transactions for the resource goes to 0, the `unregisterResource` call returns immediately.

At the end of the grace period, if outstanding transactions are associated with the resource, the `unregisterResource` call returns and a log message is written to the server on which the resource was previously registered.

Type: integer/int32

Constraints: Minimum Value: 0, Maximum Value: 2147483647

weblogic.management.configuration.JTAMBean

This interface provides access to the JTA configuration attributes. The methods defined herein are applicable for JTA configuration at the domain level.

The properties of the `weblogic.management.configuration.JTAMBean` entity are as follows:

TLOGWriteWhenDeterminerExistsEnabled

Indicates two-phase transaction recovery logs are written even if one or more determiners are configured.

Type: boolean

Constraints: Has Default Value: false

WSATIssuedTokenEnabled

Specifies whether to use `issuedtoken` to enable authentication between the WS-AT coordinator and participant.

Type: boolean

Constraints: Has Default Value: false

WSATTransportSecurityMode

Specifies transport security mode required by WebService Transaction endpoints.

Transport Security options:

- **SSLNotRequired** All WebService Transaction protocol messages are exchanged over the HTTP channel.
- **SSLRequired** All WebService Transaction protocol messages are and can only be exchanged over the HTTPS.
- **ClientCertRequired** All WebService Transaction protocol messages are and can only be exchanged over the HTTPS, and WLS enforces the presence of client certificate

Type: string

Constraints: Has Default Value: SSLNotRequired, Legal Values: SSLNotRequired, SSLRequired, ClientCertRequired

abandonTimeoutSeconds

Specifies the maximum amount of time, in seconds, a transaction manager persists in attempting to complete the second phase of a two-phase commit transaction.

During the second phase of a two-phase commit transaction, the transaction manager continues to try to complete the transaction until all resource managers indicate that the transaction is completed. After the abandon transaction timer expires, no further attempt is made to resolve the transaction. If the transaction is in a prepared state before being abandoned, the transaction manager rolls back the transaction to release any locks held on behalf of the abandoned transaction.

Type: integer/int32

Constraints: Has Default Value: 86400, Minimum Value: 1, Maximum Value: 2147483647

beforeCompletionIterationLimit

The maximum number of cycles that the transaction manager performs the `beforeCompletion` synchronization callback for this WebLogic Server domain.

Nothing prevents a Synchronization object from registering another during `beforeCompletion`, even those whose `beforeCompletions` have already been called. For example, an EJB can call another in its `ejbStore()` method. To accommodate this, the transaction manager calls all Synchronization objects, then repeats the cycle if new ones have been registered. This count sets a limit to the number of cycles that synchronization occurs.

Type: integer/int32

Constraints: Has Default Value: 10, Minimum Value: 1, Maximum Value: 2147483647

checkpointIntervalSeconds

The interval at which the transaction manager creates a new transaction log file and checks all old transaction log files to see if they are ready to be deleted.

Type: integer/int32

Constraints: Has Default Value: 300, Minimum Value: 10, Maximum Value: 1800

clusterwideRecoveryEnabled

Indicates that cluster-wide recovery is used for distributed transactions.

When enabled, recovery operations for a distributed transaction are applied to all the servers of the cluster hosting a InterposedTransactionManager rather than just the server hosting the InterposedTransactionManager.

Type: boolean

Constraints: Has Default Value: false

completionTimeoutSeconds

Specifies the maximum amount of time, in seconds, a transaction manager waits for all resource managers to respond and indicate if the transaction can be committed or rolled back.

- The default value is 0, which sets the value to approximately twice the default transaction-timeout value with a maximum value of 120 seconds. This value provides backward compatibility for prior releases without this setting.
- If the specified value is -1, the maximum value supported by this attribute is used.
- If the specified value exceeds the value set for abandon-timeout-seconds, the value of abandon-timeout-seconds is used.

Type: integer/int32

Constraints: Has Default Value: 0, Minimum Value: -1, Maximum Value: 2147483647

crossSiteRecoveryLeaseExpiration

The time in seconds after which a lease expires making it eligible for recovery by another site.

Type: integer/int32

Constraints: Has Default Value: 30, Minimum Value: 1, Maximum Value: 2147483647

crossSiteRecoveryLeaseUpdate

The time in seconds in which to update a lease timestamp.

Type: integer/int32

Constraints: Has Default Value: 10, Minimum Value: 1, Maximum Value: 2147483647

crossSiteRecoveryRetryInterval

The interval at which a lease for a given server in a recovery domain will be checked for takeover eligibility.

Type: integer/int32

Constraints: Has Default Value: 60, Minimum Value: 1, Maximum Value: 2147483647

determinerCandidateResourceInfoList

Returns a list of one or more transaction resources (determiners). A determiner's in-doubt transaction records are used during transaction recovery when a TLog is not present.

Type: array of
weblogic.management.configuration.DeterminerCandidateResourceInfoVBean

Constraints: Read Only

determiners

Select a transaction resource (determiner) from the list of resources. For JMS, select WebLogic JMS as the determiner. When a determiner is configured, the determiner's in-doubt transaction records are used during transaction recovery.

Type: array of string

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

forgetHeuristics

Specifies whether the transaction manager automatically performs an XA Resource `forget` operation for heuristic transaction completions.

When enabled, the transaction manager automatically performs an XA Resource `forget()` operation for all resources as soon as the transaction learns of a heuristic outcome. Disable this feature only if you know what to do with the resource when it reports a heuristic decision.

Type: boolean

Constraints: Has Default Value: true

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

maxResourceRequestsOnServer

Maximum number of concurrent requests to resources allowed for each server.

Type: integer/int32

Constraints: Has Default Value: 50, Minimum Value: 10, Maximum Value: 2147483647

maxResourceUnavailableMillis

Maximum duration time, in milliseconds, that a resource is declared dead. After the duration, the resource is declared available again, even if the resource provider does not explicitly re-register the resource.

Type: integer/int64

Constraints: Has Default Value: 1800000, Minimum Value: 0, Maximum Value: 9223372036854775807

maxRetrySecondsBeforeDeterminerFail

The maximum amount of time, in seconds, WebLogic Server waits for the determiner to recover from a failure. If the determiner does not recover after this period, WebLogic Server sets the TLog health state to HEALTH_FAILED.

Type: integer/int32

Constraints: Has Default Value: 300, Minimum Value: 0, Maximum Value: 2147483647

maxTransactions

The maximum number of simultaneous in-progress transactions allowed on a server in this WebLogic Server domain.

Type: integer/int32

Constraints: Has Default Value: 10000, Minimum Value: 1, Maximum Value: 2147483647

maxUniqueNameStatistics

The maximum number of unique transaction names for which statistics are maintained.

The first 1001 unique transaction names are maintained as their own transaction name and stored in each statistic. After the 1001st transaction name is reached, the transaction name is stored as `weblogic.transaction.statistics.namedOverflow`, and the transaction statistic is also merged and maintained in `weblogic.transaction.statistics.namedOverflow`.

A transaction name typically represents a category of business transactions, such as "funds-transfer."

Type: integer/int32

Constraints: Has Default Value: 1000, Minimum Value: 0, Maximum Value: 2147483647

maxXACallMillis

Maximum allowed time duration, in milliseconds, for XA calls to resources. If a particular XA call to a resource exceeds the limit, the resource is declared unavailable.

Type: integer/int64

Constraints: Has Default Value: 120000, Minimum Value: 0, Maximum Value: 9223372036854775807

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

Name=user-specified-name

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

parallelXAEnabled

Indicates that XA calls are executed in parallel if there are available threads.

Type: boolean

Constraints: Has Default Value: true

recoverySiteName

The name of the site whose transactions this site/domain will recover in the event that intra-cluster transaction service migration is not successful or efficient.

Type: string

securityInteropMode

Specifies the security mode of the communication channel used for XA calls between servers that participate in a global transaction. All server instances in a domain must have the same security mode setting.

Security Interoperability Mode options:

- **default** The transaction coordinator makes calls using the kernel identity over an admin channel if it is enabled, and `anonymous` otherwise. Man-in-the-middle attacks are possible if the admin channel is not enabled.
- **performance** The transaction coordinator makes calls using `anonymous` at all times. This implies a security risk since a malicious third party could then try to affect the outcome of transactions using a man-in-the-middle attack.
- **compatibility** The transaction coordinator makes calls as the kernel identity over an insecure channel. This is a high security risk because a successful man-in-the-middle attack would allow the attacker to gain administrative control over both domains. This setting should only be used when strong network security is in place.

Type: string

Constraints: Has Default Value: default, Legal Values: default, performance, compatibility

serializeEnlistmentsGCIntervalMillis

The time interval, in milliseconds, at which internal objects used to serialize resource enlistment are cleaned up.

Type: integer/int64

Constraints: Has Default Value: 30000, Minimum Value: 0

shutdownGracePeriod

Indicates how long the server should wait for active transactions to complete before allowing shutdown.

Type: integer/int32

Constraints: Has Default Value: 180

tags

Return all tags on this Configuration MBean

Type: array of string

tightlyCoupledTransactionsEnabled

Indicates tight coupling of transaction branches that span different transaction manager systems.

When enabled, WebLogic uses the transaction identifier of a transaction imported by the InterposedTransactionManager for XA calls rather than an internally mapped Xid. This applies to inter-domain WebLogic transactions and transactions imported from Tuxedo. This allows for tight coupling of transaction branches for transactions that span across different transaction manager systems.

If a transaction between WebLogic and Tuxedo resources uses a GridLink Data Source with GridLink Affinity enabled, the XA Affinity context is automatically used for the transaction.

Type: boolean

Constraints: Has Default Value: false

timeoutSeconds

Specifies the maximum amount of time, in seconds, an active transaction is allowed to be in the first phase of a two-phase commit transaction. If the specified amount of time expires, the transaction is automatically rolled back.

Type: integer/int32

Constraints: Has Default Value: 30, Minimum Value: 1, Maximum Value: 2147483647

twoPhaseEnabled

Indicates that the two-phase commit protocol is used to coordinate transactions across two or more resource managers.

If not selected:

- Two-phase commit is disabled and any attempt to use two-phase commit results in a RollbackException being thrown.
- All transaction logging is disabled, including checkpoint records.

Type: boolean

Constraints: Has Default Value: true

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

unregisterResourceGracePeriod

The amount of time, in seconds, a transaction manager waits for transactions involving the resource to complete before unregistering a resource. This grace period helps minimize the risk of abandoned transactions because of an unregistered resource, such as a JDBC data source module packaged with an application.

During the specified grace period, the `unregisterResource` call blocks until the call returns and no new transactions are started for the associated resource. If the number of outstanding transactions for the resource goes to 0, the `unregisterResource` call returns immediately.

At the end of the grace period, if outstanding transactions are associated with the resource, the `unregisterResource` call returns and a log message is written to the server on which the resource was previously registered.

Type: integer/int32

Constraints: Has Default Value: 30, Minimum Value: 0, Maximum Value: 2147483647

weblogic.management.configuration.JTAMigratableTargetMBean

The target that is used internally to register the JTA recovery manager to the Migration Manager.

The properties of the weblogic.management.configuration.JTAMigratableTargetMBean entity are as follows:

additionalMigrationAttempts

A migratable service could fail to come up on every possible configured server. This attribute controls how many further attempts, after the service has failed on every server at least once, should be tried. Note that each attempt specified here indicates another full circuit of migrations amongst all the configured servers. So for a 3-server cluster, and a value of 2, a total of 4 additional migrations will be attempted. (the original server is never a valid destination)

Type: integer/int32

Constraints: Has Default Value: 2

allCandidateServers

The list of servers that are candidates to host the migratable services deployed to this migratable target. If the constrainedCandidateServers list is empty, all servers in the cluster are returned. If the constrainedCandidateServers list is not empty, only those servers will be returned. The user-preferred server will be the first element in the list.

Type: array of weblogic.management.configuration.ServerMBean references

cluster

Returns the cluster this singleton service is associated with.

Type: weblogic.management.configuration.ClusterMBean reference

Constraints: Restart Required

constrainedCandidateServers

The (user-restricted) list of servers that can host the migratable services deployed to this migratable target. The migratable service will not be allowed to migrate to a server that is not in the returned list of servers.

For example, this feature may be used to configure two servers that have access to a dual-ported disk. All servers in this list must be part of the cluster that is associated with the migratable target.

Type: array of weblogic.management.configuration.ServerMBean references

Constraints: Restart Required

critical

Returns true if the MigratableTarget is critical to the overall health of the WLS Server

Type: boolean

Constraints: Has Default Value: false

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

hostingServer

Returns the name of the server that currently hosts the singleton service.

Type: weblogic.management.configuration.ServerMBean reference

Constraints: Read Only

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

migrationPolicy

Type: string

Constraints: Has Default Value: manual, Legal Values: manual, failure-recovery, shutdown-recovery

millisToSleepBetweenAttempts

Controls how long of a pause there should be between the migration attempts described in `getAdditionalMigrationAttempts()`. Note that this delay only happens when the service has failed to come up on every server. It does not cause any sort of delay between attempts to migrate otherwise.

Type: integer/int32

Constraints: Has Default Value: 300000

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's

`javax.management.ObjectName`

`Name=user-specified-name`

Type: string

Constraints: Read Only, Legal Null: true

nonLocalPostAllowed

Specifies whether or not the post-deactivation script is allowed to run on a different machine.

Normally, when auto migration occurs, the post-deactivation script will be run on the service's current location, and the pre-activation script on the service's new location. If the current location is unreachable for some reason, this value will be checked to see if it is safe to run it on the service's new machine.

This is useful if the post-deactivation script controls access to a networked resource and does not need any data from the current machine.

Type: boolean

Constraints: Has Default Value: false

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

numberOfRestartAttempts

Specifies how many restart attempts to make before migrating the failed service.

Note that these are consecutive attempts. If the value is set to 6, and the service restart fails 5 times before succeeding, but then fails again later, it will not instantly migrate. Each failure gets its own count of restart attempts.

A value of 0 is identical to setting `getRestartOnFailure` to false. A value of -1 indicates the service should *never* be migrated; instead, it will be restarted until it either works or the server shuts down.

Type: integer/int32

Constraints: Has Default Value: 6

postScript

Specifies the path to the post-migration script to run after a migratable target is fully deactivated. The script *must* be in the `MIDDLEWARE_HOME/user_projects/domains/mydomain/bin/service_migration` directory.

After the migratable target is deactivated, if there is a script specified, *and* Node Manager is available, then the script will run. Specifying a script without an available Node Manager will result in an error upon migration.

Type: string

postScriptFailureFatal

Specifies whether or not a failure during execution of the post-deactivation script is fatal to the migration.

If it is fatal, the migratable target will *not* be automatically migrated until an administrator manually migrates it to a server, thus reactivating it.

Note: Enabling this value will result in weakening the exactly-once guarantee. It is provided to prevent more dangerous data corruption if the post-deactivation script fails. Also if this value is enabled, then the script may be called more than once by the migration framework after the Migratable Target is deactivated or the server or machine hosting the Migratable Target crashed or is network partitioned. The script is expected not to return different exit values when invoked multiple times in such scenarios.

Type: boolean

Constraints: Has Default Value: true

preScript

Specifies the path to the pre-migration script to run before a migratable target is actually activated. The script *must* be in the `MIDDLEWARE_HOME/user_projects/domains/mydomain/bin/service_migration` directory.

Before the migratable target is activated, if there is a script specified, *and* Node Manager is available, then the script will run. Specifying a script without an available Node Manager will result in an error upon migration.

If the script fails or cannot be found, migration will not proceed on the current server, and will be tried on the next suitable server. This could be the next server in the candidate server list, or in the cluster, if there is no candidate server list.

Type: string

restartOnFailure

Specifies whether or not a failed service will first be deactivated and reactivated in place, instead of being migrated.

The number of restart attempts is controlled by `getNumberOfRestartAttempts`. Once these restart attempts are exhausted, the service will migrate. A restarting migratable target will deactivate all services on it in order, then reactivate them all.

Type: boolean

Constraints: Has Default Value: false

secondsBetweenRestarts

Specifies how many seconds to wait in between attempts to restart the failed service.

Type: integer/int32

Constraints: Has Default Value: 30

strictOwnershipCheck

Whether continue to boot if cannot find the current owner of TRS to do failback. This attribute is only meaningful for servers in cluster.

If true: server will fail to boot under this situation.

If false: server will continue to boot without trying to do failback.

Type: boolean

Constraints: Has Default Value: false

tags

Return all tags on this Configuration MBean

Type: array of string

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

userPreferredServer

Returns the server that the user prefers the singleton service to be active on.

Type: weblogic.management.configuration.ServerMBean reference

weblogic.management.configuration.JTAPartitionMBean

This interface provides access to the JTAPartition configuration attributes. The methods defined herein are applicable for JTA configuration at the partition level.

The properties of the weblogic.management.configuration.JTAPartitionMBean entity are as follows:

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

Name=user-specified-name

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

tags

Return all tags on this Configuration MBean

Type: array of string

timeoutSeconds

Specifies the maximum amount of time, in seconds, an active transaction is allowed to be in the first phase of a two-phase commit transaction. If the specified amount of time expires, the transaction is automatically rolled back.

Type: integer/int32

Constraints: Minimum Value: 1, Maximum Value: 2147483647

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.JoltConnectionPoolMBean

This bean defines a Jolt connection pool.

The properties of the `weblogic.management.configuration.JoltConnectionPoolMBean` entity are as follows:

applicationPassword

The application password for this Jolt connection pool. (This is required only when the security level in the Tuxedo domain is `USER_AUTH`, `ACL` or `MANDATORY_ACL`).

As of 8.1 sp4, when you get the value of this attribute, WebLogic Server does the following:

1. Retrieves the value of the `ApplicationPasswordEncrypted` attribute.
2. Decrypts the value and returns the unencrypted password as a `String`.

When you set the value of this attribute, WebLogic Server does the following:

1. Encrypts the value.
2. Sets the value of the `ApplicationPasswordEncrypted` attribute to the encrypted value.

Using this attribute (`ApplicationPassword`) is a potential security risk because the `String` object (which contains the unencrypted password) remains in the JVM's memory until garbage collection removes it and the memory is reallocated. Depending on how memory is allocated in the JVM, a significant amount of time could pass before this unencrypted data is removed from memory.

Instead of using this attribute, use `ApplicationPasswordEncrypted`

Type: `string`

Constraints: `Encrypted`, `Has Secure Value`: `null`

deploymentOrder

A priority that the server uses to determine when it deploys an item. The priority is relative to other deployable items of the same type.

For example, the server prioritizes and deploys all EJBs before it prioritizes and deploys startup classes.

Items with the lowest `Deployment Order` value are deployed first. There is no guarantee on the order of deployments with equal `Deployment Order` values. There is no guarantee of ordering across clusters.

Type: `integer/int32`

Constraints: `Has Default Value`: 1000, `Minimum Value`: 0, `Maximum Value`: 2147483647

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to `config.xml`

Type: `boolean`

Constraints: `Read Only`, `Has Default Value`: `false`

failoverAddresses

The list of Jolt Server Listeners (JSLs) addresses that is used if the connection pool cannot establish connections to the Primary Addresses, or if the primary connections fail.

The format of each address is: `//hostname:port`. Multiple addresses should be separated by commas.

These JSLs need not reside on the same host as the primary JSLs.

Type: `array of string`

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

keyPassPhrase

The encrypted identity passphrase.

When you get the value of this attribute, WebLogic Server does the following:

1. Retrieves the value of the `KeyPassPhraseEncrypted` attribute.
2. Decrypts the value and returns the unencrypted password as a String.

When you set the value of this attribute, WebLogic Server does the following:

1. Encrypts the value.
2. Sets the value of the `KeyPassPhraseEncrypted` attribute to the encrypted value.

Using this attribute (`KeyPassPhrase`) is a potential security risk because the String object (which contains the unencrypted password) remains in the JVM's memory until garbage collection removes it and the memory is reallocated. Depending on how memory is allocated in the JVM, a significant amount of time could pass before this unencrypted data is removed from memory.

Instead of using this attribute, use `KeyPassPhraseEncrypted`

Type: string

Constraints: Encrypted

keyStoreName

The path and file name of the keystore containing the private key used in SSL mutual authentication.

Type: string

keyStorePassPhrase

The encrypted identity keystore's passphrase. If empty or null, then the keystore will be opened without a passphrase.

When you get the value of this attribute, WebLogic Server does the following:

1. Retrieves the value of the `KeyStorePassPhraseEncrypted` attribute.
2. Decrypts the value and returns the unencrypted password as a String.

When you set the value of this attribute, WebLogic Server does the following:

1. Encrypts the value.
2. Sets the value of the `KeyStorePassPhraseEncrypted` attribute to the encrypted value.

Using this attribute (`KeyStorePassPhrase`) is a potential security risk because the String object (which contains the unencrypted password) remains in the JVM's memory until garbage collection removes it and the memory is reallocated. Depending on how memory is allocated in the JVM, a significant amount of time could pass before this unencrypted data is removed from memory.

Instead of using this attribute, use `KeyStorePassPhraseEncrypted`

Type: string

Constraints: Encrypted

maximumPoolSize

The maximum number of connections that can be made from this Jolt connection pool.

Type: integer/int32

Constraints: Has Default Value: 1, Minimum Value: 1, Maximum Value: 2147483647

minimumPoolSize

The minimum number of connections to be added to this Jolt connection pool when WebLogic Server starts.

Type: integer/int32

Constraints: Has Default Value: 0, Minimum Value: 0, Maximum Value: 2147483647

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's

`javax.management.ObjectName`

`Name=user-specified-name`

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

primaryAddresses

The list of addresses for the primary Jolt Server Listeners (JSLs) on the Tuxedo system.

The format of each address is: `//hostname:port`. Multiple addresses should be separated by commas.

Type: array of string

recvTimeout

The number of seconds the client waits to receive a response before timing out.

Type: integer/int32

Constraints: Has Default Value: 0, Minimum Value: 0, Maximum Value: 2147483647

securityContextEnabled

Indicates whether this Jolt connection pool passes the connection pool's security context (user name, password and other information) from the WebLogic Server user to the Tuxedo domain.

If you enable the connection pool to pass the security context, you must start the Jolt Service Handler (JSH) with the `-a` option. When the JSH gets a message with the caller's identity, it calls `impersonate_user()` to get the appkey for the user. JSH caches

the appkey, so the next time the caller makes a request, the appkey is retrieved from the cache and the request is forwarded to the service. A cache is maintained by each JSH, which means that there will be a cache maintained for all the session pools connected to the same JSH.

You must enable Security Context if Tuxedo requires secured connections.

Type: boolean

Constraints: Has Secure Value: true, Has Default Value: false

tags

Return all tags on this Configuration MBean

Type: array of string

targets

You must select a target on which an MBean will be deployed from this list of the targets in the current domain on which this item can be deployed. Targets must be either servers or clusters. The deployment will only occur once if deployments overlap.

Type: array of weblogic.management.configuration.TargetMBean references

trustStoreName

The path and file name of the keystore containing the trust certificates.

Type: string

trustStorePassPhrase

The encrypted trust keystore's passphrase. If empty or null, then the keystore will be opened without a passphrase.

When you get the value of this attribute, WebLogic Server does the following:

1. Retrieves the value of the `TrustStorePassPhraseEncrypted` attribute.
2. Decrypts the value and returns the unencrypted password as a String.

When you set the value of this attribute, WebLogic Server does the following:

1. Encrypts the value.
2. Sets the value of the `TrustStorePassPhraseEncrypted` attribute to the encrypted value.

Using this attribute (`TrustStorePassPhrase`) is a potential security risk because the String object (which contains the unencrypted password) remains in the JVM's memory until garbage collection removes it and the memory is reallocated. Depending on how memory is allocated in the JVM, a significant amount of time could pass before this unencrypted data is removed from memory.

Instead of using this attribute, use `TrustStorePassPhraseEncrypted`

Type: string

Constraints: Encrypted

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

userName

A user name that applications specify to connect to this Jolt connection pool. If Security Context is enabled, this name must be the name of an authorized Tuxedo user. (Specifying a Tuxedo user name is required if the Tuxedo authentication level is USER_AUTH.)

Type: string

userPassword

The user password for this Jolt connection pool.

As of 8.1 sp4, when you get the value of this attribute, WebLogic Server does the following:

1. Retrieves the value of the `UserPasswordEncrypted` attribute.
2. Decrypts the value and returns the unencrypted password as a String.

When you set the value of this attribute, WebLogic Server does the following:

1. Encrypts the value.
2. Sets the value of the `UserPasswordEncrypted` attribute to the encrypted value.

Using this attribute (`UserPassword`) is a potential security risk because the String object (which contains the unencrypted password) remains in the JVM's memory until garbage collection removes it and the memory is reallocated. Depending on how memory is allocated in the JVM, a significant amount of time could pass before this unencrypted data is removed from memory.

Instead of using this attribute, use `UserPasswordEncrypted`

Type: string

Constraints: Encrypted

userRole

The Tuxedo user role for this Jolt connection pool. (This is required only when the security level in the Tuxedo domain is USER_AUTH, ACL, or MANDATORY_ACL).

Type: string

weblogic.management.configuration.LibraryMBean

Configuration bean for Libraries.

The properties of the `weblogic.management.configuration.LibraryMBean` entity are as follows:

absoluteAltDescriptorDir

The fully resolved location of this application's alternate descriptor directory on the Administration Server.

Type: string

Constraints: Read Only

absoluteAltDescriptorPath

The fully resolved location of this application's alternate descriptor on the Administration Server.

Type: string

Constraints: Read Only

absoluteInstallDir

The fully resolved location of this application's installation root directory on the Administration Server.

Type: string

Constraints: Read Only

absolutePlanDir

The fully resolved location of this application's deployment plan directory on the Administration Server.

Type: string

Constraints: Read Only

absolutePlanPath

The fully resolved location of this application's deployment plan on the Administration Server.

Type: string

Constraints: Read Only

absoluteSourcePath

The fully resolved location of this application's source files on the Administration Server.

Type: string

Constraints: Read Only

altDescriptorDir

The location of this application's configuration area. This directory can contain alternate descriptor files.

Rules:

If the alternate descriptor directory is a relative path, it is resolved relative to InstallDir if InstallDir is not null; otherwise, it is resolved relative to the domain root.

Use AbsoluteAltDescriptorDir to get a fully resolved value.

Type: string

Constraints: Read Only

applicationIdentifier

The Application Identifier of the application version uniquely identifies the application version across all versions of all applications. If the application is not versioned, the Application Identifier is the same as the application name.

Type: string

Constraints: Read Only

applicationName

The name of the application.

Note that the name of the current MBean is not the name of the application.

Type: string

Constraints: Read Only

cacheInAppDirectory

Type: boolean

compatibilityName

This is only set for beans created as a result of conversion from an 8.1 application configured using ApplicationMBean and ComponentMBean.

Standalone modules in 8.1 have both an ApplicationMBean name and ComponentMBean name. This attribute stores the name of the latter, to be used when the server creates the transient ComponentMBean for backward compatibility.

Type: string

deploymentOrder

An integer value that indicates when this unit is deployed, relative to other deployable units on a server, during startup.

Units with lower values are deployed before those with higher values.

Type: integer/int32

Constraints: Has Default Value: 100

deploymentPrincipalName

A string value that indicates the principal that should be used when deploying the file or archive during startup and shutdown. This principal will be used to set the current subject when calling out into application code for interfaces such as ApplicationLifecycleListener. If no principal name is specified, then the anonymous principal will be used.

Type: string

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

installDir

The path to the application's install-root directory, relative to the domain/config/deployments directory.

When the installation directory is specified, SourcePath, PlanDir, and PlanPath are derived from this path and need not be specified.

The default value for this is the name of the deployment.

Type: string

Constraints: Read Only

moduleType

The values match those defined by jsr88. This attribute may move to another MBean.

Type: string

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

Name=user-specified-name

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

parallelDeployModules

Determines if the modules of applications will be deployed in parallel.

Type: boolean

planDir

The location of this application's configuration area. This directory can contain external descriptor files as specified within the deployment plan document.

Rules:

If the plan directory is a relative path, it is resolved relative to `InstallDir` if `InstallDir` is not null; otherwise, it is resolved relative to the domain root.

Use `AbsolutePlanDir` to get a fully resolved value.

Type: string

Constraints: Read Only

planPath

The path to the deployment plan document on the Administration Server.

Rules:

If the plan path is a relative path, it is resolved relative to `PlanDir` if `PlanDir` is not null; otherwise, it is resolved relative to the domain root.

Use `AbsolutePlanPath` to get a fully resolved value.

If there is no plan, this returns no plan specified.

Type: string

Constraints: Read Only

planStagingMode

Specifies whether an application's deployment plan is copied from a source on the Administration Server to the Managed Server's staging area during application preparation.

Plan staging mode for an application can only be set the first time the application is deployed. Once the plan staging mode for an application is set, it cannot be changed while the application is configured in the domain. The only way to change the plan staging mode is to undeploy and then redeploy the application.

This attribute overrides the server's plan staging mode.

Type: string

Constraints: Read Only, Has Default Value: null, Legal Values: nostage, stage, external_stage

securityDDModel

The security model that is used to secure a deployed module.

To set this value, you can use the `weblogic.Deployer` command-line tool, the Deployment Assistant in the Administration Console, the WebLogic Scripting Tool (WLST), or another JMX client.

If you deploy a module using one of the previously mentioned tools and you do not specify a security model value, the module is secured with the security realm's default model (see `weblogic.management.security.RealmMBean#getSecurityDDModel` `RealmMBean SecurityDDModel`).

If you deploy a module by modifying the domain's `config.xml` file and restarting the server, and if you do not specify a security model value for the module in `config.xml`, the module is secured with the `DDOnly` model, which is the default value of this `AppDeploymentMBean` attribute.

In summary, the order of precedence for the value of this attribute is as follows:

- If you deploy a module using a runtime deployment utility, the order of precedence is:
 1. The value set by the deployment utility.
 2. The value set as the security realm's default security model.
- If you deploy a module by modifying `config.xml` and restarting the server, the order of precedence is:
 1. The value that you specify for the module in `config.xml`
 2. The default value of this `AppDeploymentMBean SecurityDDModel` attribute.

Type: string

Constraints: Read Only, Has Default Value: `DDOnly`, Legal Values: `DDOnly`, `CustomRoles`, `CustomRolesAndPolicies`, `Advanced`

sourcePath

The path to the source of the deployable unit on the Administration Server.

Rules:

If the source path is relative, it is resolved relative to `InstallDir/app` if `InstallDir` is not null; otherwise, it is resolved relative to the domain root.

Use `AbsoluteSourcePath` to get a fully resolved value.

Type: string

Constraints: Read Only

stagingMode

Specifies whether a deployment's files are copied from a source on the Administration Server to the Managed Server's staging area during application preparation.

Staging mode for an application can only be set the first time the application is deployed. Once the staging mode for an application is set, it cannot be changed while the application is configured in the domain. The only way to change the staging mode is to undeploy and then redeploy the application.

This attribute overrides the server's staging mode.

Type: string

Constraints: Read Only, Has Default Value: null, Legal Values: nostage, stage, external_stage

tags

Return all tags on this Configuration MBean

Type: array of string

targets

You must select a target on which an MBean will be deployed from this list of the targets in the current domain on which this item can be deployed. Targets must be either servers or clusters. The deployment will only occur once if deployments overlap.

Type: array of weblogic.management.configuration.TargetMBean references

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

untargeted

Only relevant for deployments in resource group templates. This flag, when specified as true, indicates that the application deployment must not be deployed in the referring partition.

Type: boolean

Constraints: Has Default Value: false

validateDDSecurityData

This attribute is not used in the current release.

Type: boolean

Constraints: Has Default Value: false

versionIdentifier

Uniquely identifies the application version across all versions of the same application.

If the application is not versioned, this returns null.

Type: string

Constraints: Read Only

weblogic.management.configuration.LifecycleManagerConfigMBean

LifecycleManagerConfigMBean maintains the information necessary to enable and configure a LifecycleManager instance associated with this domain. LifecycleManager instances may either be local or remote to this domain. User credentials may be configured to support authentication, especially important when interaction with a remote domain.

The properties of the weblogic.management.configuration.LifecycleManagerConfigMBean entity are as follows:

LCMInitiatedConnectTimeout

Returns setting for connect timeout for LCM initiated REST requests which may have been triggered by OOB, sync, patching. 0 return implies that the option is disabled (i.e., timeout of infinity).

Type: integer/int32

Constraints: Has Default Value: 0

LCMInitiatedConnectTimeoutForElasticity

Returns setting for connect timeout for LCM initiated REST requests triggered by Elasticity 0 return implies that the option is disabled (i.e., timeout of infinity).

Type: integer/int32

Constraints: Has Default Value: 0

LCMInitiatedReadTimeout

Type: integer/int32

Constraints: Has Default Value: 0

LCMInitiatedReadTimeoutForElasticity

Type: integer/int32

Constraints: Has Default Value: 0

configFileLockTimeout

Returns the Lifecycle configuration lock timeout. This is used when the persistence type is LifecycleManagerConfigMBean.PERSISTENCE_TYPE_XML, while attempting to lock the configuration file to persist configuration changes.

Type: integer/int64

Constraints: Has Default Value: 120000

dataSourceName

Returns the name of the DataSource that should be used when LifecycleManager is configured to maintain its configuration in a database.

Type: string

deploymentType

The deployment model for LifecycleManager services in this domain.

Type: string

Constraints: Has Default Value: none, Legal Values: none, admin, cluster

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

enabled

Determine if LifecycleManager features are available, either locally on this admin server or remotely via a configured endpoint.

Type: boolean

Constraints: Read Only

endPoints

Returns the REST endpoints for each LifecycleManager that is participating in the management of this domain.

Type: array of weblogic.management.configuration.LifecycleManagerEndPointMBean references

Constraints: Read Only

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

Name=user-specified-name

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

outOfBandEnabled

Determine if LifecycleManager should listen for configuration changes on this server.

Type: boolean

Constraints: Has Default Value: false

periodicSyncInterval

Get periodic interval for lifecycle configuration synchronization in hours. When synchronizing configuration, Lifecycle contacts the different runtimes that are registered with it, gets the list of partitions from those runtimes, and ensure that its configuration is synchronized with those runtimes.

Type: integer/int32

Constraints: Has Default Value: 2

persistenceType

The persistence model that is used by this LifecycleManager service. Either database or a local XML file may be used for an admin server deployment, but a database configuration model is required for a cluster deployment.

Type: string

Constraints: Has Default Value: XML, Legal Values: XML, database

propagationActivateTimeout

Returns the activation timeout in milliseconds for Lifecycle configuration propagation to managed server.

Type: integer/int64

Constraints: Has Default Value: 180000

serverReadyTimeout

The timeout in milliseconds for waiting for a server to be ready to receive requests.

Type: integer/int64

Constraints: Has Default Value: 60000

serverRuntimeTimeout

Returns the timeout in milliseconds for accessing server runtime mbeans.

Type: integer/int64

Constraints: Has Default Value: 600000

tags

Return all tags on this Configuration MBean

Type: array of string

target

The cluster target defined in the current domain that should host the LifecycleManager service when running deployed in Cluster mode.

Type: weblogic.management.configuration.TargetMBean reference

Constraints: Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.LifecycleManagerEndPointMBean

LifecycleManagerEndPointMBean maintains the information necessary to locate and interact with an MT LifecycleManager instance associated with this domain. This information is used by WebLogic Server components to share configuration and runtime changes in a broader context. LifecycleManager instances may either be local or remote to this domain. User credentials may be configured to support authentication, especially important when interaction with a remote domain.

The properties of the `weblogic.management.configuration.LifecycleManagerEndPointMBean` entity are as follows:

URL

Returns the URL for the root REST resource for the LifecycleManager instance. For example, `http://localhost:7001/lifecycle/12.2.1.0/`

Type: string

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to `config.xml`

Type: boolean

Constraints: Read Only, Has Default Value: false

enabled

Returns true if this LifecycleManager endpoint configuration is active and should be used when a WebLogic Server component needs to share a configuration change.

Type: boolean

Constraints: Has Default Value: true

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

Name=user-specified-name

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

password

Get the password in clear text. (disallowed by default - use `getPasswordEncrypted`)

Type: string

Constraints: Encrypted

runtimeName

Returns the runtime name for this WebLogic Server domain. This name can be used to override the domain name of the local domain from the perspective of LifecycleManager.

Type: string

tags

Return all tags on this Configuration MBean

Type: array of string

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

username

The user name that will be passed when opening a connection to a LifecycleManager instance (specified by the URL value for this endpoint). If not set, then no user name will be specified when establishing an connection.

Type: string

weblogic.management.configuration.LogFilterMBean

This MBean represents a filter to qualify log messages which are selected by the specified filter expression criteria. A message must meet all the specified criteria to qualify the filter. Multiple instances of this MBean can be defined, if needed. If there are multiple instances, a message must qualify at least one filter to qualify for the log file.

The properties of the weblogic.management.configuration.LogFilterMBean entity are as follows:

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

filterExpression

The filter expression to be evaluated for qualifying log messages.

The filter expression is specified as a string in the query language. The query language supports Boolean operators: AND, OR, and NOT, and relational operators. You can use the following column names (message attributes) in a query to filter data going to a log destination: RECORDID, DATE, SEVERITY, SUBSYSTEM, MACHINE, SERVER, THREAD, USERID, TXID, CONTEXTID, TIMESTAMP, MSGID, and MESSAGE.

Type: string

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

Name=user-specified-name

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

tags

Return all tags on this Configuration MBean

Type: array of string

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.LogMBean

Configures the threshold severity level and filter settings for logging output.

Specifies whether the server logging is based on a Log4j implementation or the default Java Logging APIs.

Redirects the JVM stdout and stderr output to the registered log destinations.

The properties of the `weblogic.management.configuration.LogMBean` entity are as follows:

bufferSizeKB

Gets the underlying log buffer size in kilobytes

Type: integer/int32

Constraints: Has Default Value: 8

dateFormatPattern

The date format pattern used for rendering dates in the log. The `DateFormatPattern` string conforms to the specification of the `java.text.SimpleDateFormat` class.

Type: string

Constraints: Legal Null: true

domainLogBroadcastFilter

The filter configuration for log events being sent to the domain log.

Type: weblogic.management.configuration.LogFilterMBean reference

domainLogBroadcastSeverity

The minimum severity of log messages going to the domain log from this server's log broadcaster. Messages with a lower severity than the specified value will not be published to the domain log.

Type: string

Constraints: Has Default Value: Notice, Legal Values: Debug, Info, Warning, Error, Notice, Critical, Alert, Emergency, Off

domainLogBroadcasterBufferSize

Broadcasts log messages to the domain log in batch mode.

The size of the buffer for log messages that are sent to the domain log. The buffer is maintained on the Managed Server and is broadcasted to the domain log when it is full.

If you notice performance issues due to a high rate of log messages being generated, set this value higher. This will cause the buffer to be broadcasted less frequently from the Managed Server to the domain log. In production environments, it is not recommended to set the buffer size lower than the production default of 10.

Type: integer/int32

Constraints: Has Default Value: 1, Has Production Mode Default Value: 10, Minimum Value: 1, Maximum Value: 100

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

fileCount

The maximum number of log files that the server creates when it rotates the log. This number does not include the file that the server uses to store current messages. (Requires that you enable Number of Files Limited.)

Type: integer/int32

Constraints: Has Default Value: 7, Has Production Mode Default Value: 100, Minimum Value: 1, Maximum Value: 99999

fileMinSize

The size (1 - 2097150 kilobytes) that triggers the server to move log messages to a separate file. The default is 500 kilobytes. After the log file reaches the specified minimum size, the next time the server checks the file size, it will rename the current log file as *SERVER_NAME.lognnnnn* and create a new one to store subsequent messages. (Requires that you specify a file rotation type of *Size*.)

Type: integer/int32

Constraints: Has Default Value: 500, Has Production Mode Default Value: 5000, Minimum Value: 1, Maximum Value: 2097150

fileName

The name of the file that stores current log messages. Usually it is a computed value based on the name of the parent of this MBean. For example, for a server log, it is `SERVER_NAME.log`

However, if the name of the parent cannot be obtained, the file name is `weblogic.log`. If you specify a relative pathname, it is interpreted as relative to the server's root directory.

To include a time and date stamp in the file name when the log file is rotated, add `java.text.SimpleDateFormat` variables to the file name. Surround each variable with percentage (%) characters.

For example, if the file name is defined to be `myserver_%yyyy%_%MM%_%dd%_%hh%_%mm%.log`, the log file will be named `myserver_yyyy_mm_dd_hh_mm.log`

When the log file is rotated, the rotated file name contains the date stamp. For example, if the log file is rotated for the first time on 2 April, 2003 at 10:05 AM, the log file that contains the old messages will be named `myserver_2003_04_02_10_05.log00001`

If you do not include a time and date stamp, the rotated log files are numbered in order of creation. For example, `myserver.log00007`

Type: string

fileTimeSpan

The interval (in hours) at which the server saves old log messages to another file. (Requires that you specify a file rotation type of `TIME`.)

Type: integer/int32

Constraints: Has Default Value: 24, Minimum Value: 1

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

logFileFilter

The filter configuration for the server log file.

A filter configuration defines simple filtering rules to limit the volume of log messages written to the log file.

Type: `weblogic.management.configuration.LogFilterMBean` reference

logFileRotationDir

The directory where the rotated log files will be stored. By default the rotated files are stored in the same directory where the log file is stored.

Type: string

logFileSeverity

The minimum severity of log messages going to the server log file. By default all messages go to the log file.

Type: string

Constraints: Has Default Value: Trace, Legal Values: Trace, Debug, Info, Notice, Warning

logMonitoringEnabled

Enable or disable log monitoring.

Type: boolean

Constraints: Has Default Value: true

logMonitoringIntervalSecs

Timer interval in seconds to check the counts of messages logged during the interval.

Type: integer/int32

Constraints: Has Default Value: 30, Minimum Value: 5

logMonitoringMaxThrottleMessageSignatureCount

Maximum number of unique message signatures that will be monitored during the throttle interval.

Type: integer/int32

Constraints: Has Default Value: 1000, Minimum Value: 100, Maximum Value: 5000

logMonitoringThrottleMessageLength

Cut-off length of the log message for evaluation during throttle period. The log message length is truncated to this length for evaluation of repeated logging events.

Type: integer/int32

Constraints: Has Default Value: 50, Minimum Value: 10, Maximum Value: 500

logMonitoringThrottleThreshold

The threshold number of messages logged during the evaluation period which enables or disables the throttling.

Once throttling is enabled messages with the same repeating message signatures are throttled. Every nth repeated message specified by this attribute is logged in a monitoring cycle.

Type: integer/int32

Constraints: Has Default Value: 1500, Minimum Value: 5

loggerSeverity

The minimum severity of log messages going to all log destinations.

Type: string

Constraints: Has Default Value: Info, Legal Values: Trace, Debug, Info, Notice, Warning

loggerSeverityProperties

The configuration of the different logger severities keyed by name. The values are one of the predefined Severity strings namely Emergency, Alert, Critical, Error, Warning, Notice, Info, Debug, Trace.

Type: java.util.Properties

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's

`javax.management.ObjectName`

`Name=user-specified-name`

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

numberOfFilesLimited

Indicates whether to limit the number of log files that this server instance creates to store old messages. (Requires that you specify a file rotation type of `SIZE` or `TIME`.)

After the server reaches this limit, it deletes the oldest log file and creates a new log file with the latest suffix.

If you do not enable this option, the server creates new files indefinitely and you must clean up these files as you require.

Type: boolean

Constraints: Has Default Value: true, Has Production Mode Default Value: true

platformLoggerLevels

Specifies the platform logger and the associated level names set through the WebLogic Server configuration.

Note the following behavior:

- The configuration is applicable for `java.util.logging.Logger` instances in the JDK's default global LogManager.
- WebLogic Server loggers are configured in terms of `weblogic.logging.Severities` through the `LoggerSeverities` attribute. These loggers are not available in the JDK's default global LogManager.
- If your WebLogic domain includes Oracle JRF and is configured to use Oracle Diagnostic Logging (ODL), the `java.util.logging` levels set on the `LogMBean.PlatformLoggerLevels` attribute are ignored. For information about how to configure ODL logging for JDK platform loggers, see *Managing Log Files and Diagnostics Data in Administering Oracle Fusion Middleware*

Type: java.util.Properties

redirectStderrToServerLogEnabled

Specifies whether the stderr of the JVM in which a WebLogic Server instance runs is redirected to the WebLogic Logging system. When this attribute is enabled, the stderr content is published to all the registered log destinations, such as the server terminal console and log file.

Note that JVM messages are redirected asynchronously. In the event of an overload situation, these messages may be dropped. As a best practice, Oracle recommends using one of the supported logging APIs instead.

Type: boolean

redirectStdoutToServerLogEnabled

Specifies whether the stdout of the JVM in which a WebLogic Server instance runs is redirected to the WebLogic logging system. When this attribute is enabled, the stdout content is published to all the registered log destinations, such as the server terminal console and log file.

Note that JVM messages are redirected asynchronously. In the event of an overload situation, these messages may be dropped. As a best practice, Oracle recommends using one of the supported logging APIs instead.

Type: boolean

rotateLogOnStartup

Specifies whether a server rotates its log file during its startup cycle. The default value in production mode is false.

Type: boolean

Constraints: Has Default Value: true, Has Production Mode Default Value: false

rotationTime

Determines the start time (hour and minute) for a time-based rotation sequence.

At the time that this value specifies, the server renames the current log file. Thereafter, the server renames the log file at an interval that you specify in File Time Span.

Note that WebLogic Server sets a threshold size limit of 500 MB before it forces a hard rotation to prevent excessive log file growth.

Use the following format: H:mm, where

- H is Hour in day (0-23)
- mm is the minute in hour

Type: string

Constraints: Has Default Value: 00:00

rotationType

Criteria for moving old log messages to a separate file.

- NONE Messages accumulate in a single file. You must erase the contents of the file when the size is too large. Note that WebLogic Server sets a threshold size limit of 500 MB before it forces a hard rotation to prevent excessive log file growth.
- SIZE When the log file reaches the size that you specify in FileMinSize, the server renames the file as *SERVER_NAME.lognnnnn*
- TIME At each time interval that you specify in TimeSpan, the server renames the file as *SERVER_NAME.lognnnnn*

After the server renames a file, subsequent messages accumulate in a new file with the name that you specified as the log file name.

Type: string

Constraints: Has Default Value: bySize, Legal Values: bySize, byTime, none

stdoutFilter

The filter configuration for log events being sent to the standard out.

Type: weblogic.management.configuration.LogFilterMBean reference

stdoutFormat

The output format to use when logging to the console.

Type: string

Constraints: Has Default Value: standard, Legal Values: standard, noid

stdoutLogStack

Specifies whether to dump stack traces to the console when included in logged message.

Type: boolean

Constraints: Has Default Value: true

stdoutSeverity

The minimum severity of log messages going to the standard out. Messages with a lower severity than the specified value will not be published to standard out.

Type: string

Constraints: Has Default Value: Notice, Legal Values: Trace, Debug, Info, Warning, Error, Notice, Critical, Alert, Emergency, Off

tags

Return all tags on this Configuration MBean

Type: array of string

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.MachineMBean

This bean represents a machine on which servers may be booted. A server is bound to a machine by calling to `ServerMBean.setMachine()`. Although it is typical that one `MachineMBean` refers to one physical machine and vice versa, it is possible to have a multihomed machine represented by multiple `MachineMBeans`. The only restriction is that each `MachineMBean` be configured with non-overlapping addresses. A configuration may contain one or more of `MachineMBeans` which may be looked up by their logical names.

The properties of the `weblogic.management.configuration.MachineMBean` entity are as follows:

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to `config.xml`

Type: boolean

Constraints: Read Only, Has Default Value: false

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's

`javax.management.ObjectName`

Name=user-specified-name

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as

XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`.

Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

tags

Return all tags on this Configuration MBean

Type: array of string

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.MailSessionMBean

Facilitates using the JavaMail APIs, which provide applications and other Java EE modules with access to Internet Message Access Protocol (IMAP)- and Simple Mail Transfer Protocol (SMTP)-capable mail servers on your network or the Internet.

In the reference implementation of JavaMail, applications must instantiate `javax.mail.Session` objects, which designate mail hosts, transport and store protocols, and a default mail user for connecting to a mail server. In WebLogic Server, you create a mail session, which configures a `javax.mail.Session` object and registers it in the WebLogic Server JNDI tree. Applications access the mail session through JNDI instead of instantiating their own `javax.mail.Session` object.

The properties of the `weblogic.management.configuration.MailSessionMBean` entity are as follows:

JNDIName

The JNDI Name associated with this resource.

Type: string

Constraints: Legal Null: true

deploymentOrder

A priority that the server uses to determine when it deploys an item. The priority is relative to other deployable items of the same type.

For example, the server prioritizes and deploys all EJBs before it prioritizes and deploys startup classes.

Items with the lowest Deployment Order value are deployed first. There is no guarantee on the order of deployments with equal Deployment Order values. There is no guarantee of ordering across clusters.

Type: integer/int32

Constraints: Has Default Value: 1000, Minimum Value: 0, Maximum Value: 2147483647

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

name

jmsserverjmshat on

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

Name=user-specified-name

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

properties

The configuration options and user authentication data that this mail session uses to interact with a mail server. Each property that you specify overrides the default property value as defined by the JavaMail API Design Specification.

Include only the properties defined by the JavaMail API Design Specification.

If you do not specify any properties, this mail session will use the JavaMail default property values.

Express each property as a *namevalue* pair. Separate multiple properties with a semicolon (`,`).

Type: java.util.Properties

sessionPassword

The decrypted JavaMail Session password attribute, for use only temporarily in-memory; the value returned by this attribute should not be held in memory long term.

The value is stored in an encrypted form in the descriptor file and when displayed in an administration console.

Type: string

Constraints: Encrypted

sessionUsername

Returns the username to be used to create an authenticated JavaMail Session, using a JavaMail Authenticator instance; if this is not set, it will be assumed that the Session is not to be authenticated.

Type: string

tags

Return all tags on this Configuration MBean

Type: array of string

targets

You must select a target on which an MBean will be deployed from this list of the targets in the current domain on which this item can be deployed. Targets must be either servers or clusters. The deployment will only occur once if deployments overlap.

Type: array of weblogic.management.configuration.TargetMBean references

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.MailSessionOverrideMBean

Defines partition-specific mail session attribute overrides of a mail session referenced by a partition resource group definition.

The properties of the weblogic.management.configuration.MailSessionOverrideMBean entity are as follows:

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

`Name=user-specified-name`

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

properties

The configuration options and user authentication data that this mail session uses to interact with a mail server.

Type: `java.util.Properties`

sessionPassword

The decrypted JavaMail Session password attribute, for use only temporarily in-memory; the value returned by this attribute should not be held in memory long term.

Type: string

Constraints: Encrypted

sessionUsername

The username to be used to create an authenticated JavaMail Session, using a JavaMail `Authenticator` instance.

Type: string

tags

Return all tags on this Configuration MBean

Type: array of string

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.ManagedExecutorServiceMBean

Configuration MBean representing parameters of partition level `ManagedExecutorService`.

The properties of the `weblogic.management.configuration.ManagedExecutorServiceMBean` entity are as follows:

deploymentOrder

A priority that the server uses to determine when it deploys an item. The priority is relative to other deployable items of the same type.

For example, the server prioritizes and deploys all EJBs before it prioritizes and deploys startup classes.

Items with the lowest Deployment Order value are deployed first. There is no guarantee on the order of deployments with equal Deployment Order values. There is no guarantee of ordering across clusters.

Type: integer/int32

Constraints: Has Default Value: 1000, Minimum Value: 0, Maximum Value: 2147483647

dispatchPolicy

The name of the Work Manager to use for this Concurrent Managed Object (CMO). If a Work Manager is not specified, the default one is used.

Type: string

Constraints: Has Default Value:

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

longRunningPriority

An integer that specifies the long-running daemon thread's priority. If a value is specified, all long-running threads are affected.

Type: integer/int32

Constraints: Has Default Value: 5, Minimum Value: 1, Maximum Value: 10

maxConcurrentLongRunningRequests

The maximum number of running long-running tasks submitted to this CMO.

Type: integer/int32

Constraints: Has Default Value: 10, Minimum Value: 0, Maximum Value: 65534

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's

`javax.management.ObjectName`

`Name=user-specified-name`

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

tags

Return all tags on this Configuration MBean

Type: array of string

targets

You must select a target on which an MBean will be deployed from this list of the targets in the current domain on which this item can be deployed. Targets must be either servers or clusters. The deployment will only occur once if deployments overlap.

Type: array of `weblogic.management.configuration.TargetMBean` references

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.ManagedExecutorServiceTemplateMBean

Configuration MBean representing parameters of `ManagedExecutorService` template.

The properties of the `weblogic.management.configuration.ManagedExecutorServiceTemplateMBean` entity are as follows:

deploymentOrder

A priority that the server uses to determine when it deploys an item. The priority is relative to other deployable items of the same type.

For example, the server prioritizes and deploys all EJBs before it prioritizes and deploys startup classes.

Items with the lowest Deployment Order value are deployed first. There is no guarantee on the order of deployments with equal Deployment Order values. There is no guarantee of ordering across clusters.

Type: integer/int32

Constraints: Has Default Value: 1000, Minimum Value: 0, Maximum Value: 2147483647

dispatchPolicy

The name of the Work Manager to use for this Concurrent Managed Object (CMO). If a Work Manager is not specified, the default one is used.

Type: string

Constraints: Has Default Value:

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

longRunningPriority

An integer that specifies the long-running daemon thread's priority. If a value is specified, all long-running threads are affected.

Type: integer/int32

Constraints: Has Default Value: 5, Minimum Value: 1, Maximum Value: 10

maxConcurrentLongRunningRequests

The maximum number of running long-running tasks submitted to this CMO.

Type: integer/int32

Constraints: Has Default Value: 10, Minimum Value: 0, Maximum Value: 65534

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

`Name=user-specified-name`

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

tags

Return all tags on this Configuration MBean

Type: array of string

targets

You must select a target on which an MBean will be deployed from this list of the targets in the current domain on which this item can be deployed. Targets must be either servers or clusters. The deployment will only occur once if deployments overlap.

Type: array of weblogic.management.configuration.TargetMBean references

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.ManagedScheduledExecutorService MBean

Configuration MBean representing parameters of partition level ManagedScheduledExecutorService.

The properties of the weblogic.management.configuration.ManagedScheduledExecutorServiceMBean entity are as follows:

deploymentOrder

A priority that the server uses to determine when it deploys an item. The priority is relative to other deployable items of the same type.

For example, the server prioritizes and deploys all EJBs before it prioritizes and deploys startup classes.

Items with the lowest Deployment Order value are deployed first. There is no guarantee on the order of deployments with equal Deployment Order values. There is no guarantee of ordering across clusters.

Type: integer/int32

Constraints: Has Default Value: 1000, Minimum Value: 0, Maximum Value: 2147483647

dispatchPolicy

The name of the Work Manager to use for this Concurrent Managed Object (CMO). If a Work Manager is not specified, the default one is used.

Type: string

Constraints: Has Default Value:

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

longRunningPriority

An integer that specifies the long-running daemon thread's priority. If a value is specified, all long-running threads are affected.

Type: integer/int32

Constraints: Has Default Value: 5, Minimum Value: 1, Maximum Value: 10

maxConcurrentLongRunningRequests

The maximum number of running long-running tasks submitted to this CMO.

Type: integer/int32

Constraints: Has Default Value: 10, Minimum Value: 0, Maximum Value: 65534

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

`Name=user-specified-name`

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

tags

Return all tags on this Configuration MBean

Type: array of string

targets

You must select a target on which an MBean will be deployed from this list of the targets in the current domain on which this item can be deployed. Targets must be either servers or clusters. The deployment will only occur once if deployments overlap.

Type: array of `weblogic.management.configuration.TargetMBean` references

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.ManagedScheduledExecutorServiceTemplateMBean

Configuration MBean representing parameters of `ManagedScheduledExecutorService` template.

The properties of the `weblogic.management.configuration.ManagedScheduledExecutorServiceTemplateMBean` entity are as follows:

deploymentOrder

A priority that the server uses to determine when it deploys an item. The priority is relative to other deployable items of the same type.

For example, the server prioritizes and deploys all EJBs before it prioritizes and deploys startup classes.

Items with the lowest Deployment Order value are deployed first. There is no guarantee on the order of deployments with equal Deployment Order values. There is no guarantee of ordering across clusters.

Type: integer/int32

Constraints: Has Default Value: 1000, Minimum Value: 0, Maximum Value: 2147483647

dispatchPolicy

The name of the Work Manager to use for this Concurrent Managed Object (CMO). If a Work Manager is not specified, the default one is used.

Type: string

Constraints: Has Default Value:

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

longRunningPriority

An integer that specifies the long-running daemon thread's priority. If a value is specified, all long-running threads are affected.

Type: integer/int32

Constraints: Has Default Value: 5, Minimum Value: 1, Maximum Value: 10

maxConcurrentLongRunningRequests

The maximum number of running long-running tasks submitted to this CMO.

Type: integer/int32

Constraints: Has Default Value: 10, Minimum Value: 0, Maximum Value: 65534

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

Name=user-specified-name

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

tags

Return all tags on this Configuration MBean

Type: array of string

targets

You must select a target on which an MBean will be deployed from this list of the targets in the current domain on which this item can be deployed. Targets must be either servers or clusters. The deployment will only occur once if deployments overlap.

Type: array of `weblogic.management.configuration.TargetMBean` references

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.ManagedThreadFactoryMBean

Configuration MBean representing parameters of partition level `ManagedThreadFactory`.

The properties of the `weblogic.management.configuration.ManagedThreadFactoryMBean` entity are as follows:

deploymentOrder

A priority that the server uses to determine when it deploys an item. The priority is relative to other deployable items of the same type.

For example, the server prioritizes and deploys all EJBs before it prioritizes and deploys startup classes.

Items with the lowest Deployment Order value are deployed first. There is no guarantee on the order of deployments with equal Deployment Order values. There is no guarantee of ordering across clusters.

Type: integer/int32

Constraints: Has Default Value: 1000, Minimum Value: 0, Maximum Value: 2147483647

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to `config.xml`

Type: boolean

Constraints: Read Only, Has Default Value: false

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

maxConcurrentNewThreads

The maximum number of concurrent new threads that can be created by this Managed Thread Factory (MTF).

Type: integer/int32

Constraints: Has Default Value: 10, Minimum Value: 0, Maximum Value: 65534

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

`Name=user-specified-name`

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

priority

An integer that specifies the daemon thread's priority. If a value is specified, all concurrent new threads created by this MTF are affected.

Type: integer/int32

Constraints: Has Default Value: 5, Minimum Value: 1, Maximum Value: 10

tags

Return all tags on this Configuration MBean

Type: array of string

targets

You must select a target on which an MBean will be deployed from this list of the targets in the current domain on which this item can be deployed. Targets must be either servers or clusters. The deployment will only occur once if deployments overlap.

Type: array of `weblogic.management.configuration.TargetMBean` references

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.ManagedThreadFactoryTemplateMBean

Configuration MBean representing common parameters of ManagedThreadFactory template.

The properties of the weblogic.management.configuration.ManagedThreadFactoryTemplateMBean entity are as follows:

deploymentOrder

A priority that the server uses to determine when it deploys an item. The priority is relative to other deployable items of the same type.

For example, the server prioritizes and deploys all EJBs before it prioritizes and deploys startup classes.

Items with the lowest Deployment Order value are deployed first. There is no guarantee on the order of deployments with equal Deployment Order values. There is no guarantee of ordering across clusters.

Type: integer/int32

Constraints: Has Default Value: 1000, Minimum Value: 0, Maximum Value: 2147483647

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

maxConcurrentNewThreads

The maximum number of concurrent new threads that can be created by this Managed Thread Factory (MTF).

Type: integer/int32

Constraints: Has Default Value: 10, Minimum Value: 0, Maximum Value: 65534

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's

`javax.management.ObjectName`

`Name=user-specified-name`

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

priority

An integer that specifies the daemon thread's priority. If a value is specified, all concurrent new threads created by this MTF are affected.

Type: integer/int32

Constraints: Has Default Value: 5, Minimum Value: 1, Maximum Value: 10

tags

Return all tags on this Configuration MBean

Type: array of string

targets

You must select a target on which an MBean will be deployed from this list of the targets in the current domain on which this item can be deployed. Targets must be either servers or clusters. The deployment will only occur once if deployments overlap.

Type: array of `weblogic.management.configuration.TargetMBean` references

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.MaxThreadsConstraintMBean

This MBean defines the max number of concurrent threads that can execute requests sharing this max constraint.

`MaxThreadsConstraint` can be used to tell the server that the requests are constrained by an external resource like a database and allocating more threads that the external resource limit is not going to help since the extra threads are just going to wait.

The properties of the `weblogic.management.configuration.MaxThreadsConstraintMBean` entity are as follows:

connectionPoolName

Name of the connection pool whose size is taken as the max constraint.

This can be the name of a JDBC data source. The max capacity of the data source is used as the constraint.

Type: string

count

Maximum number of concurrent threads that can execute requests sharing this constraint.

A count of 0 or -1 is treated as if the constraint is not present. This means that no constraint is enforced for these two values. A count > 0 can be dynamically changed to 0 to indicate that constraint enforcement is no longer needed.

Type: integer/int32

Constraints: Has Default Value: -1

deploymentOrder

A priority that the server uses to determine when it deploys an item. The priority is relative to other deployable items of the same type.

For example, the server prioritizes and deploys all EJBs before it prioritizes and deploys startup classes.

Items with the lowest Deployment Order value are deployed first. There is no guarantee on the order of deployments with equal Deployment Order values. There is no guarantee of ordering across clusters.

Type: integer/int32

Constraints: Has Default Value: 1000, Minimum Value: 0, Maximum Value: 2147483647

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

`Name=user-specified-name`

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

queueSize

Desired size of the MaxThreadsConstraint queue for requests pending execution.

Type: integer/int32

Constraints: Has Default Value: 8192, Minimum Value: 256, Maximum Value: 1073741824

tags

Return all tags on this Configuration MBean

Type: array of string

targets

You must select a target on which an MBean will be deployed from this list of the targets in the current domain on which this item can be deployed. Targets must be either servers or clusters. The deployment will only occur once if deployments overlap.

Type: array of weblogic.management.configuration.TargetMBean references

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.MessagingBridgeMBean

This MBean represents a WebLogic messaging bridge. A messaging bridge instance interoperates between separate implementations of WebLogic JMS or between WebLogic JMS and another messaging product.

For WebLogic JMS and third-party JMS products, a messaging bridge communicates with a configured source and target destinations using the resource adapters provided with WebLogic Server.

The properties of the weblogic.management.configuration.MessagingBridgeMBean entity are as follows:

QOSDegradationAllowed

Specifies if this messaging bridge instance allows the degradation of its QOS (quality of service) when the configured QOS is not available.

- When enabled, the messaging bridge instance degrades the QOS when the configured QOS is not available. If the QOS is degraded, a log message is delivered to the WebLogic startup window or log file.
- When not enabled, if messaging bridge instance cannot satisfy the quality of service requested, an error results and the messaging bridge instance does not start.

Type: boolean

Constraints: Has Default Value: false

asyncEnabled

Specifies if a messaging bridge instance forwards in asynchronous messaging mode.

AsyncEnabled only applies to messaging bridge instances whose source destination supports asynchronous receiving. Messaging bridges instances that forward in

asynchronous mode are driven by the source destination. A messaging bridge instance listens for messages and forwards them as they arrive. When `AsyncEnabled` is not selected, a bridge instance is forced to work in synchronous mode, even if the source supports asynchronous receiving.

Note: For a messaging bridge instance with a QOS of *Exactly-once* to work in asynchronous mode, the source destination has to support the `MDBTransaction` interface. Otherwise, the bridge automatically switches to synchronous mode if it detects that `MDBTransaction` is not supported by the source destination.

Type: boolean

Constraints: Has Default Value: true

batchInterval

The maximum amount of time, in milliseconds, that a messaging bridge instance waits before sending a batch of messages in one transaction, regardless of whether the `Batch Size` has been reached or not.

- Only applies to a messaging bridge instance forwarding messages in synchronous mode and has a QOS (quality of service) that requires two-phase transactions.
- The default value of -1 indicates that the bridge instance waits until the number of messages reaches the `Batch Size` before it completes a transaction.

Type: integer/int64

Constraints: Has Default Value: -1

batchSize

The number of messages that are processed within one transaction.

`Batch Size` only applies to a messaging bridge instance forwarding messages in synchronous mode and has a QOS (quality of service) that requires two-phase transactions.

Type: integer/int32

Constraints: Has Default Value: 10, Minimum Value: 0

deploymentOrder

A priority that the server uses to determine when it deploys an item. The priority is relative to other deployable items of the same type.

For example, the server prioritizes and deploys all EJBs before it prioritizes and deploys startup classes.

Items with the lowest `Deployment Order` value are deployed first. There is no guarantee on the order of deployments with equal `Deployment Order` values. There is no guarantee of ordering across clusters.

Type: integer/int32

Constraints: Has Default Value: 1000, Minimum Value: 0, Maximum Value: 2147483647

distributionPolicy

Specifies how the instances of a configured JMS artifact are named and distributed when cluster-targeted. A JMS artifact is cluster-targeted when its target is directly set to a cluster, or when it is scoped to a resource group and the resource group is in turn targeted to a cluster. When this setting is configured on a store, it applies to all JMS artifacts that reference the store. Valid options:

- **Distributed** Creates an instance on each server JVM in a cluster. Required for all SAF agents and for cluster-targeted or resource-group-scoped JMS servers that host distributed destinations.
- **Singleton** Creates a single instance on a single server JVM within a cluster. Required for cluster-targeted or resource-group-scoped JMS servers that host standalone (non-distributed) destinations and for cluster-targeted or resource-group-scoped path services. The `Migration Policy` must be `On-Failure` or `Always` when using this option with a JMS server, `On-Failure` when using this option with a messaging bridge, and `Always` when using this option with a path service.

Instance Naming Note:

- The `DistributionPolicy` determines the instance name suffix for cluster-targeted JMS artifacts. The suffix for a cluster-targeted `Singleton` is `-01` and for a cluster-targeted `Distributed` is `@ClusterMemberName`.

Messaging Bridge Notes:

- When an instance per server is desired for a cluster-targeted messaging bridge, Oracle recommends setting the bridge `Distributed Policy` and `Migration Policy` to `Distributed/Off`, respectively; these are the defaults.
- When a single instance per cluster is desired for a cluster-targeted bridge, Oracle recommends setting the bridge `Distributed Policy` and `Migration Policy` to `Singleton/On-Failure`, respectively.
- If you cannot cluster-target a bridge and still need singleton behavior in a configured cluster, you can target the bridge to a migratable target and configure the `Migration Policy` on the migratable target to `Exactly-Once`.

Type: string

Constraints: Has Default Value: `Distributed`, Legal Values: `Distributed`, `Singleton`

durabilityEnabled

Specifies whether or not the messaging bridge allows durable messages.

When enabled and the source destination is a JMS topic, a messaging bridge instance uses a durable subscription to ensure that no messages are lost in the event of a failure. `DurabilityEnabled` ignored if the source destination is a JMS queue.

- When enabled and the source destination uses durable subscriptions, the source JMS implementation saves messages that are sent when a messaging bridge instance is not running. When the bridge instance is restarted, these messages are forwarded to the target destination. The administrator can choose not to be durable.
- When not enabled, messages that are sent to the source JMS implementation while the bridge instance is down cannot be forwarded to the target destination.

Type: boolean

Constraints: Has Default Value: `true`

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to `config.xml`

Type: boolean

Constraints: Read Only, Has Default Value: `false`

failbackDelaySeconds

Specifies the amount of time, in seconds, to delay before failing a cluster-targeted JMS artifact instance back to its preferred server after the preferred server failed and was restarted.

This delay allows time for the system to stabilize and dependent services to be restarted, preventing a system failure during a reboot.

- A value > specifies the time, in seconds, to delay before failing a JMS artifact back to its user preferred server.
- A value of indicates that the instance would never failback.
- A value of -1 indicates that there is no delay and the instance would failback immediately.

Note: This setting only applies when the JMS artifact is cluster-targeted and the Migration Policy is set to `On-Failure` or `Always`

Type: integer/int64

Constraints: Has Default Value: -1

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

idleTimeMaximum

The maximum amount of time, in seconds, that a messaging bridge instance remains idle.

- In *asynchronous* mode, this is the longest amount of time a messaging bridge instance stays idle before it checks the sanity of its connection to the source.
- In *synchronous* mode, this is the amount of time the messaging bridge can block on a receive call if no transaction is involved.

Type: integer/int32

Constraints: Has Default Value: 60, Minimum Value: 0, Maximum Value: 2147483647

initialBootDelaySeconds

Specifies the amount of time, in seconds, to delay before starting a cluster-targeted JMS instance on a newly booted WebLogic Server instance. When this setting is configured on a store, it applies to all JMS artifacts that reference the store.

This allows time for the system to stabilize and dependent services to be restarted, preventing a system failure during a reboot.

- A value > is the time, in seconds, to delay before before loading resources after a failure and restart.
- A value of specifies no delay.

Note: This setting only applies when the JMS artifact is cluster-targeted and the Migration Policy is set to `On-Failure` or `Always`

Type: integer/int64

Constraints: Has Default Value: 60

migrationPolicy

Controls migration and restart behavior of cluster-targeted JMS service artifact instances. When this setting is configured on a cluster-targeted store, it applies to all JMS artifacts that reference the store. See the migratable target settings for enabling migration and restart on migratable-targeted JMS artifacts.

- **Off** Disables migration support for cluster-targeted JMS service objects, and changes the default for Restart In Place to false. If you want a restart to be enabled when the Migration Policy is Off, then Restart In Place must be explicitly configured to true. This policy cannot be combined with the Singleton Migration Policy.
- **On-Failure** Enables automatic migration and restart of instances on the failure of a subsystem Service or WebLogic Server instance, including automatic fail-back and load balancing of instances.
- **Always** Provides the same behavior as On-Failure and automatically migrates instances even in the event of a graceful shutdown or a partial cluster start.

Note: Cluster leasing must be configured for On-Failure and Always.

Messaging Bridge Notes:

- When an instance per server is desired for a cluster-targeted messaging bridge, Oracle recommends setting the bridge Distributed Policy and Migration Policy to Distributed/Off, respectively; these are the defaults.
- When a single instance per cluster is desired for a cluster-targeted bridge, Oracle recommends setting the bridge Distributed Policy and Migration Policy to Singleton/On-Failure, respectively.
- A Migration Policy of Always is not recommended for bridges.
- If you cannot cluster-target a bridge and still need singleton behavior in a configured cluster, you can target the bridge to a migratable target and configure the Migration Policy on the migratable target to Exactly-Once.

Type: string

Constraints: Has Default Value: Off, Legal Values: Off, On-Failure, Always

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

Name=user-specified-name

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

numberOfRestartAttempts

Specifies the maximum number of restart attempts.

- A value > specifies the maximum number of restart attempts.
- A value of 0 specifies the same behavior as setting `getRestartInPlace` to `false`
- A value of -1 means infinite retry restart until it either starts or the server instance shuts down.

Type: integer/int32

Constraints: Has Default Value: 6, Minimum Value: -1

partialClusterStabilityDelaySeconds

Specifies the amount of time, in seconds, to delay before a partially started cluster starts all cluster-targeted JMS artifact instances that are configured with a Migration Policy of `Always` or `On-Failure`.

Before this timeout expires or all servers are running, a cluster starts a subset of such instances based on the total number of servers running and the configured cluster size. Once the timeout expires or all servers have started, the system considers the cluster stable and starts any remaining services.

This delay ensures that services are balanced across a cluster even if the servers are started sequentially. It is ignored after a cluster is fully started (stable) or when individual servers are started.

- A value > specifies the time, in seconds, to delay before a partially started cluster starts dynamically configured services.
- A value of 0 specifies no delay.

Type: integer/int64

Constraints: Has Default Value: 240

preserveMsgProperty

Specifies if message properties are preserved when messages are forwarded by a bridge instance.

The following message properties are preserved:

- message ID
- message timestamp
- user ID
- delivery mode
- priority
- expiration time
- redelivery limit
- unit of order name

If the target bridge destination is on a foreign JMS server, the following message properties are preserved:

- delivery mode
- priority
- expiration time

Type: boolean

Constraints: Has Default Value: false

qualityOfService

The QOS (quality of service) for this messaging bridge instance.

- **Exactly-once:** Each message in the source destination is transferred to the target exactly once. This is the highest QOS a messaging bridge instance can offer.
- **Atmost-once:** Each message in the source is transferred to the target only once with the possibility of being lost during the forwarding.
- **Duplicate-okay:** Messages in the source destination are transferred to the target (none are lost) but some may appear in the target more than once.

Type: string

Constraints: Has Secure Value: Exactly-once, Has Default Value: Exactly-once, Legal Values: Exactly-once, Atmost-once, Duplicate-okay

reconnectDelayIncrease

The incremental delay time, in seconds, that a messaging bridge instance increases its waiting time between one failed reconnection attempt and the next retry.

Use with `ReconnectDelayMinimum` and `ReconnectDelayMaximum`. After the first failure to connect to a destination, the bridge instance waits for the number of seconds defined by `ReconnectDelayMinimum`. Each time a reconnect attempt fails, the bridge instance increases its waiting time by the number of seconds defined by `ReconnectDelayIncrease`. The maximum delay time is defined by `ReconnectDelayMaximum`. Once the waiting time is increased to the maximum value, the bridge instance stops increase its waiting time. Once the bridge instance successfully connects to the destination, the bridge instance resets its waiting time to the initial value defined by `ReconnectDelayMinimum`

Type: integer/int32

Constraints: Has Default Value: 5, Minimum Value: 0, Maximum Value: 2147483647

reconnectDelayMaximum

The longest amount of time, in seconds, that a messaging bridge instance waits between one failed attempt to connect to the source or target, and the next retry.

Use with `ReconnectDelayMinimum` and `ReconnectDelayIncrease`. After the first failure to connect to a destination, a bridge instance waits for the number of seconds defined by `ReconnectDelayMinimum`. Each time a reconnect attempt fails, the bridge instance increases its waiting time by the number of seconds defined by `ReconnectDelayIncrease`. The maximum delay time is defined by `ReconnectDelayMaximum`. Once the waiting time is increased to the maximum value, the bridge instance stops increase its waiting time. Once the bridge instance successfully connects to the destination, the bridge instance resets its waiting time to the initial value defined by `ReconnectDelayMinimum`

Type: integer/int32

Constraints: Has Default Value: 60, Minimum Value: 0, Maximum Value: 2147483647

reconnectDelayMinimum

The minimum amount of time, in seconds, that a messaging bridge instance waits before it tries to reconnect to the source or target destination after a failure.

Use with `ReconnectDelayMaximum` and `ReconnectDelayIncrease`. After the first failure to connect to a destination, the bridge instance waits for the number of seconds defined by `ReconnectDelayMinimum`. Each time a reconnect attempt fails, the bridge instance increases its waiting time by the number of seconds defined by `ReconnectDelayIncrease`. The maximum delay time is defined by `ReconnectDelayMaximum`. Once the waiting time is increased to the maximum value, the bridge instance stops increase its waiting time. Once the bridge instance successfully connects to the destination, the bridge instance resets its waiting time to the initial value defined by `ReconnectDelayMinimum`

>

Type: integer/int32

Constraints: Has Default Value: 15, Minimum Value: 0, Maximum Value: 2147483647

restartInPlace

Enables a periodic automatic in-place restart of failed cluster-targeted or standalone-server-targeted JMS artifact instance(s) running on healthy WebLogic Server instances. See the migratable target settings for in-place restarts of migratable-targeted JMS artifacts. When the Restart In Place setting is configured on a store, it applies to all JMS artifacts that reference the store.

- If the Migration Policy of the JMS artifact is set to `Off`, Restart In Place is disabled by default.
- If the Migration Policy of the JMS artifact is set to `On-Failure` or `Always`, Restart In Place is enabled by default.
- This attribute is not used by WebLogic messaging bridges which automatically restart internal connections as needed.
- For a JMS artifact that is cluster-targeted and the Migration Policy is set to `On-Failure` or `Always`, if restart fails after the configured maximum retry attempts, it will migrate to a different server within the cluster.

Type: boolean

secondsBetweenRestarts

Specifies the amount of time, in seconds, to wait in between attempts to restart a failed service instance.

Type: integer/int32

Constraints: Has Default Value: 30, Minimum Value: 1

selector

The filter for messages that are sent across the messaging bridge instance.

Only messages that match the selection criteria are sent across the messaging bridge:

- For queues, messages that do not match the selection criteria are left behind and accumulate in the queue.
- For topics, messages that do not match the connection criteria are dropped.

Type: string

sourceDestination

The source destination from which this messaging bridge instance reads messages.

Type: weblogic.management.configuration.BridgeDestinationCommonMBean reference

Constraints: Restart Required

started

Specifies the initial operating state of a targeted messaging bridge instance.

- If enabled, the messaging bridge instance forwards messages (running).
- If not enabled, the messaging bridge instance does not forward messages (temporarily stopped).

After a messaging bridge has started forwarding messages (running), use `Started` to temporarily suspend an active messaging bridge instance or restart an stopped messaging bridge instance.

- Select the `Started` checkbox to start a messaging bridge instance that has been temporarily stopped.
- Clear the `Started` checkbox to temporarily stop a messaging bridge instance that was running.
- This value does not indicate the run-time state of a messaging bridge instance.

Type: boolean

Constraints: Has Default Value: true

tags

Return all tags on this Configuration MBean

Type: array of string

targetDestination

The target destination where a messaging bridge instance sends the messages it receives from the source destination.

Type: weblogic.management.configuration.BridgeDestinationCommonMBean reference

Constraints: Restart Required

targets

You must select a target on which an MBean will be deployed from this list of the targets in the current domain on which this item can be deployed. Targets must be either servers or clusters. The deployment will only occur once if deployments overlap.

Type: array of weblogic.management.configuration.TargetMBean references

transactionTimeout

The amount of time, in seconds, that the transaction manager waits for each transaction before timing it out.

- Transaction timeouts are used when the QOS (quality of service) for a messaging bridge instance requires transactions.
- If a bridge is configured with *Exactly-once* QOS, the receiving and sending is completed in one transaction.

Type: integer/int32

Constraints: Has Default Value: 30, Minimum Value: 0, Maximum Value: 2147483647

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.MigratableTargetMBean

A target that is suitable for services that shall be active on at most one server of a cluster at a time.

The properties of the weblogic.management.configuration.MigratableTargetMBean entity are as follows:

additionalMigrationAttempts

A migratable service could fail to come up on every possible configured server. This attribute controls how many further attempts, after the service has failed on every server at least once, should be tried. Note that each attempt specified here indicates another full circuit of migrations amongst all the configured servers. So for a 3-server cluster, and a value of 2, a total of 4 additional migrations will be attempted. (the original server is never a valid destination)

Type: integer/int32

Constraints: Has Default Value: 2

allCandidateServers

The list of servers that are candidates to host the migratable services deployed to this migratable target. If the constrainedCandidateServers list is empty, all servers in the cluster are returned. If the constrainedCandidateServers list is not empty, only those servers will be returned. The user-preferred server will be the first element in the list.

Type: array of weblogic.management.configuration.ServerMBean references

cluster

Returns the cluster this singleton service is associated with.

Type: weblogic.management.configuration.ClusterMBean reference

Constraints: Restart Required

constrainedCandidateServers

The (user-restricted) list of servers that can host the migratable services deployed to this migratable target. The migratable service will not be allowed to migrate to a server that is not in the returned list of servers.

For example, this feature may be used to configure two servers that have access to a dual-ported ported disk. All servers in this list must be part of the cluster that is associated with the migratable target.

Type: array of weblogic.management.configuration.ServerMBean references

Constraints: Restart Required

critical

Returns true if the MigratableTarget is critical to the overall health of the WLS Server

Type: boolean

Constraints: Has Default Value: false

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

hostingServer

Returns the name of the server that currently hosts the singleton service.

Type: weblogic.management.configuration.ServerMBean reference

Constraints: Read Only

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

migrationPolicy

Defines the type of migration policy to use for the services hosted by this migratable target. Valid options are:

- `Manual Service Migration Only` Indicates that no automatic migration of services hosted by this migratable target will occur.
- `Auto-Migrate Exactly-Once Services` Indicates that if at least one Managed Server in the candidate server list is running, the services hosted by this migratable target will be active somewhere in the cluster if servers should fail or are administratively shut down (either gracefully or forcibly). For example, it is a recommended best practice to use this policy when a migratable target hosts a path service, so if its preferred server fails or is shut down, the path service will automatically migrate to another candidate server, and so will always be active in the cluster.

Notes

This value can lead to target grouping on a server member. For example, if you have five exactly-once migratable targets and only one Managed Server is started in the cluster, then all five targets will be activated on that server.

This policy does not apply for JTA service migration.

- `Auto-Migrate Failure-Recovery Services` Indicates that the services hosted by this migratable target will only start if the migratable target's User Preferred Server (UPS) is started. If an administrator manually shuts down the UPS, either gracefully or forcibly, then a failure-recovery service will not migrate. However, if the UPS fails due to an internal error, then the service will be migrated to another candidate server. If such a candidate server is unavailable (due to either a manual shutdown or an internal failure), then the migration framework will first attempt to reactivate the service on its UPS server. If the UPS server is not available at that time, then the service will be migrated to another candidate server.
- `Auto-Migrate Shutdown-Recovery Services` Indicates that the services hosted by this migratable target will migrate to one of the candidate servers, if server is administratively shut down (either gracefully or forcibly). Once recovery is done, service is migrated back to failed server.

Type: string

Constraints: Has Default Value: manual, Legal Values: manual, exactly-once, failure-recovery, shutdown-recovery

millisToSleepBetweenAttempts

Controls how long of a pause there should be between the migration attempts described in `getAdditionalMigrationAttempts()`. Note that this delay only happens when the service has failed to come up on every server. It does not cause any sort of delay between attempts to migrate otherwise.

Type: integer/int32

Constraints: Has Default Value: 300000

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

Name=user-specified-name

Type: string

Constraints: Read Only, Legal Null: true

nonLocalPostAllowed

Specifies whether or not the post-deactivation script is allowed to run on a different machine.

Normally, when auto migration occurs, the post-deactivation script will be run on the service's current location, and the pre-activation script on the service's new location. If the current location is unreachable for some reason, this value will be checked to see if it is safe to run it on the service's new machine.

This is useful if the post-deactivation script controls access to a networked resource and does not need any data from the current machine.

Type: boolean

Constraints: Has Default Value: false

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

numberOfRestartAttempts

Specifies how many restart attempts to make before migrating the failed service.

Note that these are consecutive attempts. If the value is set to 6, and the service restart fails 5 times before succeeding, but then fails again later, it will not instantly migrate. Each failure gets its own count of restart attempts.

A value of 0 is identical to setting `getRestartOnFailure` to false. A value of -1 indicates the service should *never* be migrated; instead, it will be restarted until it either works or the server shuts down.

Type: integer/int32

Constraints: Has Default Value: 6

postScript

Specifies the path to the post-migration script to run after a migratable target is fully deactivated. The script *must* be in the `MIDDLEWARE_HOME/user_projects/domains/mydomain/bin/service_migration` directory.

After the migratable target is deactivated, if there is a script specified, *and* Node Manager is available, then the script will run. Specifying a script without an available Node Manager will result in an error upon migration.

Type: string

postScriptFailureFatal

Specifies whether or not a failure during execution of the post-deactivation script is fatal to the migration.

If it is fatal, the migratable target will *not* be automatically migrated until an administrator manually migrates it to a server, thus reactivating it.

Note: Enabling this value will result in weakening the exactly-once guarantee. It is provided to prevent more dangerous data corruption if the post-deactivation script fails. Also if this value is enabled, then the script may be called more than once by the migration framework after the Migratable Target is deactivated or the server or machine hosting the Migratable Target crashed or is network partitioned. The script is expected not to return different exit values when invoked multiple times in such scenarios.

Type: boolean

Constraints: Has Default Value: true

preScript

Specifies the path to the pre-migration script to run before a migratable target is actually activated. The script *must* be in the `MIDDLEWARE_HOME/user_projects/domains/mydomain/bin/service_migration` directory.

Before the migratable target is activated, if there is a script specified, *and* Node Manager is available, then the script will run. Specifying a script without an available Node Manager will result in an error upon migration.

If the script fails or cannot be found, migration will not proceed on the current server, and will be tried on the next suitable server. This could be the next server in the candidate server list, or in the cluster, if there is no candidate server list.

Type: string

restartOnFailure

Specifies whether or not a failed service will first be deactivated and reactivated in place, instead of being migrated.

The number of restart attempts is controlled by `getNumberOfRestartAttempts`. Once these restart attempts are exhausted, the service will migrate. A restarting migratable target will deactivate all services on it in order, then reactivate them all.

Type: boolean

Constraints: Has Default Value: false

secondsBetweenRestarts

Specifies how many seconds to wait in between attempts to restart the failed service.

Type: integer/int32

Constraints: Has Default Value: 30

tags

Return all tags on this Configuration MBean

Type: array of string

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

userPreferredServer

Returns the server that the user prefers the singleton service to be active on.

Type: weblogic.management.configuration.ServerMBean reference

weblogic.management.configuration.MinThreadsConstraintMBean

This MBean defines the minimum number of concurrent threads that should be allocated to this constraint provided there are enough pending requests.

Multiple WorkManagers can share a common MinThreadsConstraint. MinThreadsConstraint perform their own bookkeeping and demand a thread when the constraint is not met and there are enough requests.

MinThreadsConstraint should be used to tell the WebLogic Server that a certain number of minimum threads are necessary to prevent server to server deadlocks. Although the server is self-tuning, specifying MinThreadsConstraint ensures that the server guarantees minimum threads to avoid the distributed deadlocks.

The properties of the weblogic.management.configuration.MinThreadsConstraintMBean entity are as follows:

count

Minimum number of concurrent threads executing requests that share this constraint.

A count of 0 or -1 is treated as if the constraint is not present. This means that the constraint is ignored for these two values. A count > 0 can be dynamically changed to 0 to indicate that constraint enforcement is no longer needed.

Type: integer/int32

Constraints: Has Default Value: -1

deploymentOrder

A priority that the server uses to determine when it deploys an item. The priority is relative to other deployable items of the same type.

For example, the server prioritizes and deploys all EJBs before it prioritizes and deploys startup classes.

Items with the lowest Deployment Order value are deployed first. There is no guarantee on the order of deployments with equal Deployment Order values. There is no guarantee of ordering across clusters.

Type: integer/int32

Constraints: Has Default Value: 1000, Minimum Value: 0, Maximum Value: 2147483647

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

`Name=user-specified-name`

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

tags

Return all tags on this Configuration MBean

Type: array of string

targets

You must select a target on which an MBean will be deployed from this list of the targets in the current domain on which this item can be deployed. Targets must be either servers or clusters. The deployment will only occur once if deployments overlap.

Type: array of `weblogic.management.configuration.TargetMBean` references

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.NetworkAccessPointMBean

A server can specify additional network connections by using a `NetworkAccessPointMBean`. The `NetworkAccessPointMBean` is also used to set the listen address and external DNS name that a server uses for a particular channel.

The properties of the weblogic.management.configuration.NetworkAccessPointMBean entity are as follows:

SDPEnabled

Enables Socket Direct Protocol (SDP) on this channel. Enable this attribute when configuring session replication enhancements for Managed Servers in a WebLogic cluster for Oracle Exalogic.

Type: boolean

Constraints: Has Default Value: false

SSLv2HelloEnabled

Indicate whether SSLv2Hello is enabled in a network channel.

Type: boolean

acceptBacklog

The number of backlogged, new TCP connection requests that this network channel allows. A value of -1 indicates that the network channel obtains its backlog configuration from the server's configuration.

Type: integer/int32

Constraints: Minimum Value: 0

allowUnencryptedNullCipher

Test if the AllowUnEncryptedNullCipher is enabled

see `setAllowUnencryptedNullCipher(boolean enable)` for the NullCipher feature.

Type: boolean

channelIdentityCustomized

Whether or not the channel's custom identity should be used. This setting only has an effect if the server is using a customized keystore. By default the channel's identity is inherited from the server's identity.

Type: boolean

Constraints: Has Default Value: false

channelWeight

A weight to give this channel when creating server-to-server connections.

Type: integer/int32

Constraints: Has Default Value: 50, Minimum Value: 1, Maximum Value: 100

ciphersuites

Indicates the cipher suites being used on a particular WebLogic Server channel.

The strongest negotiated cipher suite is chosen during the SSL handshake. The set of cipher suites used by default by JSEE depends on the specific JDK version with which WebLogic Server is configured.

For a list of possible values, see Cipher Suites

Type: array of string

clientCertificateEnforced

Specifies whether clients must present digital certificates from a trusted certificate authority to WebLogic Server on this channel.

Type: boolean

Constraints: Has Recommended Secure Value: true, Has Default Value: false

clientInitSecureRenegotiationAccepted

Indicate whether TLS client initiated secure renegotiation is accepted.

Type: boolean

Constraints: Has Default Value: false

clusterAddress

The address this network channel uses to generate EJB handles and failover addresses for use in a cluster. This value is determined according to the following order of precedence:

1. If the cluster address is specified via the NAPMBean, then that value is used
2. If this value is not specified, the value of PublicAddress is used.
3. If PublicAddress is not set, this value is derive from the ClusterAddress attribute of the ClusterMbean.
4. If ClusterMbean.clusterAddress is not set, this value is derive from the listen address of the NAPMbean.

Type: string

completeMessageTimeout

The maximum amount of time this network channel waits for a complete message to be received. A value of `disables` network channel complete message timeout. A value of `-1` indicates that the network channel obtains this timeout value from the ServerTemplateMBean.

This timeout helps guard against denial of service attacks in which a caller indicates that they will be sending a message of a certain size which they never finish sending.

Type: integer/int32

Constraints: Minimum Value: 0, Maximum Value: 480

connectTimeout

The amount of time that this network channel should wait to establish an outbound socket connection before timing out. A value of `disables` network channel connect timeout.

Type: integer/int32

Constraints: Minimum Value: 0, Maximum Value: 240

customIdentityKeyStoreFileName

The source of the identity keystore. For a JKS keystore, the source is the path and file name. For an Oracle Key Store Service (KSS) keystore, the source is the KSS URI.

If using a JKS keystore, the keystore path name must either be absolute or relative to where the server was booted.

If using a KSS keystore, the keystore URI must be of the form:

kss://system/keystorename

where *keystorename* is the name of the keystore registered in KSS.

The value in this attribute is only used if `ServerMBean.KeyStores` is `CUSTOM_IDENTITY_AND_JAVA_STANDARD_TRUST`, `CUSTOM_IDENTITY_AND_CUSTOM_TRUST` or `CUSTOM_IDENTITY_AND_COMMAND_LINE_TRUST`

Type: string

customIdentityKeyStorePassPhrase

The encrypted custom identity keystore's passphrase. If empty or null, then the keystore will be opened without a passphrase.

This attribute is only used if `ServerMBean.KeyStores` is `CUSTOM_IDENTITY_AND_JAVA_STANDARD_TRUST`, `CUSTOM_IDENTITY_AND_CUSTOM_TRUST` or `CUSTOM_IDENTITY_AND_COMMAND_LINE_TRUST`

When you get the value of this attribute, WebLogic Server does the following:

1. Retrieves the value of the `CustomIdentityKeyStorePassPhraseEncrypted` attribute.
2. Decrypts the value and returns the unencrypted password as a String.

When you set the value of this attribute, WebLogic Server does the following:

1. Encrypts the value.
2. Sets the value of the `CustomIdentityKeyStorePassPhraseEncrypted` attribute to the encrypted value.

Using this attribute (`CustomIdentityKeyStorePassPhrase`) is a potential security risk because the String object (which contains the unencrypted password) remains in the JVM's memory until garbage collection removes it and the memory is reallocated. Depending on how memory is allocated in the JVM, a significant amount of time could pass before this unencrypted data is removed from memory.

Instead of using this attribute, use `CustomIdentityKeyStorePassPhraseEncrypted`

Type: string

Constraints: Encrypted

customIdentityKeyStoreType

The type of the keystore. Generally, this is `JKS`. If using the Oracle Key Store Service, this would be `KSS`

If empty or null, then the JDK's default keystore type (specified in `java.security`) is used. The custom identity key store type is only used if `ServerMBean.KeyStores` is `CUSTOM_IDENTITY_AND_JAVA_STANDARD_TRUST`, `CUSTOM_IDENTITY_AND_CUSTOM_TRUST` or `CUSTOM_IDENTITY_AND_COMMAND_LINE_TRUST`

Type: string

customPrivateKeyAlias

The string alias used to store and retrieve the channel's private key in the keystore. This private key is associated with the server's digital certificate. A value of `null` indicates that the network channel uses the alias specified in the server's SSL configuration.

Type: string

customPrivateKeyPassPhrase

The passphrase used to retrieve the server's private key from the keystore. This passphrase is assigned to the private key when it is generated. A value of `null`

indicates that the network channel uses the pass phrase specified in the server's SSL configuration.

Type: string

Constraints: Encrypted, Has Default Value: null

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

enabled

Specifies whether this channel should be started.

Type: boolean

Constraints: Has Default Value: true

hostnameVerificationIgnored

Specifies whether to ignore the installed implementation of the `weblogic.security.SSL.HostnameVerifier` interface (when this server is acting as a client to another application server).

Type: boolean

hostnameVerifier

The name of the class that implements the `weblogic.security.SSL.HostnameVerifier` interface.

This class verifies whether the connection to the host with the hostname from URL should be allowed. The class is used to prevent man-in-the-middle attacks. The `weblogic.security.SSL.HostnameVerifier` has a `verify()` method that WebLogic Server calls on the client during the SSL handshake.

Type: string

httpEnabledForThisProtocol

Specifies whether HTTP traffic should be allowed over this network channel.

HTTP is generally required by binary protocols for downloading stubs and other resources.

Type: boolean

Constraints: Has Default Value: true

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

idleConnectionTimeout

The maximum amount of time (in seconds) that a connection is allowed to be idle before it is closed by this network channel. A value of -1 indicates that the network channel obtains this timeout value from the `ServerTemplateMBean`.

This timeout helps guard against server deadlock through too many open connections.

Type: integer/int32

Constraints: Minimum Value: 0

inboundCertificateValidation

Indicates the client certificate validation rules for inbound SSL.

This attribute only applies to ports and network channels using 2-way SSL.

Type: string

Constraints: Legal Values: BuiltinSSLValidationOnly, BuiltinSSLValidationAndCertPathValidators

listenAddress

The IP address or DNS name this network channel uses to listen for incoming connections. A value of `null` indicates that the network channel should obtain this value from the server's configuration.

Type: string

listenPort

The default TCP port this network channel uses to listen for regular (non-SSL) incoming connections. A value of `-1` indicates that the network channel should obtain this value from the server's configuration.

Type: integer/int32

loginTimeoutMillis

The amount of time that this network channel should wait for a connection before timing out. A value of `0` disables network channel login timeout. A value of `-1` indicates that the network channel obtains this timeout value from the server's configuration.

Type: integer/int32

Constraints: Minimum Value: 0, Maximum Value: 100000

maxBackoffBetweenFailures

The maximum back off time between failures while accepting client connections. `-1` implies that this value is inherited from the server.

Type: integer/int32

Constraints: Minimum Value: 0

maxConnectedClients

The maximum number of clients that can be connected on this network channel.

Type: integer/int32

Constraints: Has Default Value: 2147483647

maxMessageSize

The maximum message size allowable in a message header.

This maximum attempts to prevent a denial of service attack whereby a caller attempts to force the server to allocate more memory than is available thereby keeping the server from responding quickly to other requests.

A client can set this value using the `-Dweblogic.MaxMessageSize` property.

Type: integer/int32

Constraints: Minimum Value: 4096, Maximum Value: 100000000

minimumTLSProtocolVersion

Get the minimum SSL/TLS protocol version to be used in a network channel.

Type: string

name

The name of this network channel.

Type: string

Constraints: Read Only, Has Default Value: <unknown>

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

outboundCertificateValidation

Indicates the server certificate validation rules for outbound SSL.

This attribute always applies to outbound SSL that is part of WebLogic Server (that is, an Administration Server talking to the Node Manager). It does not apply to application code in the server that is using outbound SSL unless the application code uses a `weblogic.security.SSL.ServerTrustManager` that is configured to use outbound SSL validation.

Type: string

Constraints: Legal Values: BuiltinSSLValidationOnly, BuiltinSSLValidationAndCertPathValidators

outboundEnabled

Specifies whether new server-to-server connections may consider this network channel when initiating a connection. This is only relevant if the connection needs to be bound to the network channel's listen address. This will only work for binary protocols that support both outbound and inbound traffic.

When this feature is not enabled, connections are initiated using a local address selected by the underlying hardware.

The default is false.

Outbound channels are selected at runtime either by virtue of the fact of being the only outbound-enabled channel for the required protocol, or by name in `weblogic.jndi.Environment#setProviderChannel`

The HTTP protocol is implicitly enabled for all the outbound channels, but you need to use the WLS client library (HTTP client) and set the channel on the connection.

Type: boolean

outboundPrivateKeyAlias

The string alias used to store and retrieve the outbound private key in the keystore. This private key is associated with either a server or a client digital certificate. This attribute value is derived from other settings and cannot be physically set.

The returned value is determined as follows:

- If `isOutboundPrivateKeyEnabled` and `isChannelIdentityCustomized` return true, the value from `getCustomPrivateKeyAlias` is returned.
- Otherwise, the value from `SSLBean#getOutboundPrivateKeyAlias` is returned from the `ServerMBean` for the channel.

Type: string

Constraints: Read Only, Has Default Value: null

outboundPrivateKeyEnabled

Specifies whether the identity specified by `getCustomPrivateKeyAlias` should be used for outbound SSL connections on this channel. In normal circumstances the outbound identity is determined by the caller's environment.

Type: boolean

Constraints: Has Secure Value: false

outboundPrivateKeyPassPhrase

The passphrase used to retrieve the outbound private key from the keystore. This passphrase is assigned to the private key when it is generated. This attribute value is derived from other settings and cannot be physically set.

The returned value is determined as follows:

- If `isOutboundPrivateKeyEnabled` and `isChannelIdentityCustomized` return true, the value from `getCustomPrivateKeyPassPhrase` is returned.
- Otherwise, the value from `SSLBean#getOutboundPrivateKeyPassPhrase` is returned from the `ServerMBean` for the channel.

Type: string

Constraints: Read Only, Has Default Value: null

privateKeyAlias

The string alias used to store and retrieve the channel's private key in the keystore. This private key is associated with the server's digital certificate. This value is derived from other settings on the channel and cannot be physically set.

Type: string

Constraints: Read Only

privateKeyPassPhrase

The passphrase used to retrieve the server's private key from the keystore. This passphrase is assigned to the private key when it is generated. This value is derived from other settings on the channel and cannot be physically set.

Type: string

Constraints: Read Only

protocol

The protocol this network channel should use for connections.

Type: string

Constraints: Has Secure Value: t3s, Has Default Value: t3

proxyAddress

The IP address or DNS name of the HTTP proxy to use for outbound connections on this channel. The HTTP proxy must support the CONNECT tunneling command.

This option is only effective when `OutboundEnabled` is set on the channel.

Type: string

Constraints: Has Default Value: null

proxyPort

The port of the HTTP proxy to use for outbound connections on this channel. The HTTP proxy must support the `CONNECT` tunneling command.

This option is only effective when `OutboundEnabled` and `ProxyHost` are set on the channel.

Type: integer/int32

Constraints: Has Default Value: 80

publicAddress

The IP address or DNS name representing the external identity of this network channel. A value of `null` indicates that the network channel's Listen Address is also its external address. If the Listen Address is `null`, the network channel obtains its external identity from the server's configuration.

This is required for the configurations which need to cross a firewall doing Network Address Translation.

Type: string

publicPort

The externally published listen port for this network channel. A value of `-1` indicates that the network channel's Listen Port is also its public listen port. If the Listen Port is `-1`, the network channel obtains its public listen port from the server's configuration.

Type: integer/int32

resolveDNSName

Resolve the listen address to use for all T3 communication

Type: boolean

Constraints: Has Default Value: false

tags

Return all tags on this Configuration MBean

Type: array of string

timeoutConnectionWithPendingResponses

Determines if connections with pending responses are allowed to timeout. It defaults to `false`. If set to `true`, the connection will be timed out for this channel if it exceeds the `idleConnectionTimeout` value.

Note: This setting only applies to IIOP connections.

Type: boolean

Constraints: Has Default Value: false

tunnelingClientPingSecs

The interval (in seconds) at which this network channel should ping an HTTP-tunneled client to see if its still alive. A value of `-1` indicates that the network channel obtains this interval from the `ServerTemplateMBean`. (Requires you to enable tunneling for the network channel.)

Type: integer/int32

Constraints: Minimum Value: 1

tunnelingClientTimeoutSecs

The amount of time (in seconds) after which this network channel considers a missing HTTP-tunneled client to be dead. A value of -1 indicates that the network channel obtains this timeout value from the ServerTemplateMBean. (Requires you to enable tunneling for the network channel.)

Type: integer/int32

Constraints: Minimum Value: 1

tunnelingEnabled

Specifies whether tunneling via HTTP should be enabled for this network channel. This value is not inherited from the server's configuration.

Type: boolean

Constraints: Has Default Value: false

twoWaySSEnabled

Specifies whether this network channel uses two way SSL.

Type: boolean

Constraints: Has Recommended Secure Value: true, Has Default Value: false

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

useFastSerialization

Specifies whether to use non-standard object serialization for performance. This option works in different ways for different protocols. In particular under IIOP this option uses Java serialization rather than RMI-IIOP serialization. In general using non-standard serialization is not suitable for interop scenarios and may imply some feature loss.

Type: boolean

weblogic.management.configuration.NodeManagerMBean

This bean represents a Node Manager that is associated with a machine.

The properties of the weblogic.management.configuration.NodeManagerMBean entity are as follows:

NMSocketCreateTimeoutInMillis

Returns the timeout value to be used by NodeManagerRuntime when creating a socket connection to the agent. Default set high as SSH agent may require a high connection establishment time.

Type: integer/int32

Constraints: Has Default Value: 180000, Minimum Value: 0

NMType

Returns the node manager type for the server or clients on the server to use when connecting to the NodeManager instance.

Type: string

Constraints: Has Default Value: SSL, Legal Values: SSH, RSH, Plain, SSL, ssh, rsh, ssl, plain

adapter

Gets the node manager client adapter name_version when using a VMM adapter to connect to OVM or other VMM adapter providers

Type: string

adapterName

Gets the node manager client adapter name when using a VMM adapter to connect to OVM or other VMM adapters providers

Type: string

adapterVersion

Gets the node manager client adapter version when using a VMM adapter to connect to OVM or other VMM adapters providers

Type: string

debugEnabled

Specifies whether communication with this Node Manager needs to be debugged. When enabled, connections to the NodeManager from the server or clients on the server will result in more information sent to the server log.

Type: boolean

Constraints: Has Default Value: false

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

listenAddress

The host name or IP address of the NodeManager for the server or clients on the server to use when connecting to the NodeManager instance.

Type: string

Constraints: Has Recommended Secure Value: 127.0.0.1 or ::1, Has Default Value: localhost

listenPort

The port number of the NodeManager for the server or clients on the server to use when connecting to the NodeManager instance.

Type: integer/int32

Constraints: Has Default Value: 5556, Minimum Value: 1, Maximum Value: 65534

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's

`javax.management.ObjectName`

Name=user-specified-name

Type: string

Constraints: Read Only, Legal Null: true

nodeManagerHome

Returns the node manager home directory that will be used to substitute for the shell command template

Type: string

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`;

Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

password

The password used by a Node Manager client to connect to the underlying service to which the Node Manager client delegates operations.

When you get the value of this attribute, WebLogic Server does the following:

1. Retrieves the value of the `PasswordEncrypted` attribute.
2. Decrypts the value and returns the unencrypted password as a String.

When you set the value of this attribute, WebLogic Server does the following:

1. Encrypts the value.
2. Sets the value of the `PasswordEncrypted` attribute to the encrypted value.

Caution: Using the (`Password`) attribute is a potential security risk because the String object (which contains the unencrypted password), remains in the JVM's memory until garbage collection removes it and the memory is reallocated. Depending on how memory is allocated in the JVM, a significant amount of time could pass before this unencrypted data is removed from memory. Therefore, you should use the `PasswordEncrypted()` attribute instead.

Type: string

Constraints: Encrypted

shellCommand

Returns the local command line to use when invoking SSH or RSH node manager functions.

Type: string

tags

Return all tags on this Configuration MBean

Type: array of string

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

userName

The Node Manager client user name used to connect to the underlying service to which the client delegates operations.

Type: string

weblogic.management.configuration.OptionalFeatureDeploymentMBean

Control panel for all optional features, e.g. WSAT, ASYNC_RESPONSE etc. The mbean is designed to be managed by domain and to extend for partition if needed in future.

The properties of the weblogic.management.configuration.OptionalFeatureDeploymentMBean entity are as follows:

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

Name=user-specified-name

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`;

Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

tags

Return all tags on this Configuration MBean

Type: array of string

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.OptionalFeatureMBean

Controls the configuration of an optional feature.

The properties of the weblogic.management.configuration.OptionalFeatureMBean entity are as follows:

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

enabled

Identifies whether the WebLogic Server automatically deploys the internal app in the current domain/partition.

Type: boolean

Constraints: Has Default Value: false

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

Name=user-specified-name

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`;

Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

tags

Return all tags on this Configuration MBean

Type: array of string

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.OsgiFrameworkMBean

An MBean representing an OSGi framework.

The properties of the weblogic.management.configuration.OsgiFrameworkMBean entity are as follows:

deployInstallationBundles

Determines if some WebLogic helper bundles will be installed into the framework

If this is set to "populate" then the bundles found in the WebLogic installation directory under wls_server/server/osgi-lib will be installed into this OSGi framework. Furthermore a few extra packages will be added to the bootdelegation classpath parameters in order to enable the bundles in the osgi-lib directory if they are not already there.

If this is set to "ignore" then the bundles found in the WebLogic installation directory will not be installed into the framework.

Type: string

Constraints: Has Default Value: populate, Legal Values: populate, ignore

deploymentOrder

A priority that the server uses to determine when it deploys an item. The priority is relative to other deployable items of the same type.

For example, the server prioritizes and deploys all EJBs before it prioritizes and deploys startup classes.

Items with the lowest Deployment Order value are deployed first. There is no guarantee on the order of deployments with equal Deployment Order values. There is no guarantee of ordering across clusters.

Type: integer/int32

Constraints: Has Default Value: 1000, Minimum Value: 0, Maximum Value: 2147483647

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

factoryImplementationClass

The name of the framework's implementation class for the org.osgi.framework.launch.FrameworkFactory class.

Type: string

Constraints: Has Default Value: org.apache.felix.framework.FrameworkFactory

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

initProperties

The properties to be used when initializing the framework. All standard properties and all properties specific to the framework can be set.

Type: java.util.Properties

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

Name=user-specified-name

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

orgOsgiFrameworkBootdelegation

The name of the `org.osgi.framework.bootdelegation` property. Note that this value, if set, will take precedence over anything specified in the `init-properties`.

Type: string

Constraints: Has Default Value: null

orgOsgiFrameworkSystemPackagesExtra

The name of the `org.osgi.framework.system.packages.extra` property. Note that this value, if set, will take precedence over anything specified in the `init-properties`.

Type: string

Constraints: Has Default Value: null

osgiImplementationLocation

The location of the OSGi implementation JAR file which contains the `org.osgi.framework.launch.FrameworkFactory` implementation. If this field is not set then an appropriate default implementation that is shipped with the product will be used.

If this field is relative it must be relative to the start directory of the server and the file must exist everywhere this framework is deployed. If this field is not relative then the

given filename must exist at the same location everywhere this framework is deployed.

Type: string

Constraints: Has Default Value: null

registerGlobalDataSources

Returns true if global data sources should be added to the OSGi service registry.

Type: boolean

Constraints: Has Default Value: true

registerGlobalWorkManagers

Returns true if global work managers should be added to the OSGi service registry.

Type: boolean

Constraints: Has Default Value: true

tags

Return all tags on this Configuration MBean

Type: array of string

targets

You must select a target on which an MBean will be deployed from this list of the targets in the current domain on which this item can be deployed. Targets must be either servers or clusters. The deployment will only occur once if deployments overlap.

Type: array of weblogic.management.configuration.TargetMBean references

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.OverloadProtectionMBean

This Mbean has attributes concerning server overload protection.

The properties of the weblogic.management.configuration.OverloadProtectionMBean entity are as follows:

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

failureAction

Enable automatic forceshutdown of the server on failed state. The server self-health monitoring detects fatal failures and mark the server as failed. The server can be restarted using NodeManager or a HA agent.

Type: string

Constraints: Has Default Value: no-action, Legal Values: no-action, force-shutdown, admin-state

freeMemoryPercentHighThreshold

Percentage free memory after which the server overload condition is cleared. WorkManagers stop performing overloadActions and start regular execution once the overload condition is cleared.

Type: integer/int32

Constraints: Has Default Value: 0, Minimum Value: 0, Maximum Value: 99

freeMemoryPercentLowThreshold

Percentage free memory below which the server is considered overloaded. WorkManagers perform overloadAction once the server is marked as overloaded.

Type: integer/int32

Constraints: Has Default Value: 0, Minimum Value: 0, Maximum Value: 99

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

Name=user-specified-name

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

panicAction

Exit the server process when the kernel encounters a panic condition like an unhandled OOME. An unhandled OOME could lead to inconsistent state and a server restart is advisable if backed by node manager or a HA agent.

Type: string

Constraints: Has Default Value: system-exit, Legal Values: no-action, system-exit

sharedCapacityForWorkManagers

Total number of requests that can be present in the server. This includes requests that are enqueued and those under execution.

The server performs a differentiated denial of service on reaching the shared capacity. A request with higher priority will be accepted in place of a lower priority request already in the queue. The lower priority request is kept waiting in the queue till all

high priority requests are executed. Further enqueues of the low priority requests are rejected right away.

Type: integer/int32

Constraints: Has Default Value: 65536, Minimum Value: 1, Maximum Value: 1073741824

tags

Return all tags on this Configuration MBean

Type: array of string

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.ParameterMBean

Specifies the parameters used to configure the DeploymentValidationPluginMBean.

The properties of the weblogic.management.configuration.ParameterMBean entity are as follows:

description

Gets the parameter description.

Type: string

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

name

Gets the parameter name.

Type: string

Constraints: Read Only

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

tags

Return all tags on this Configuration MBean

Type: array of string

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

value

Gets the parameter value.

Type: string

weblogic.management.configuration.PartitionFileSystemMBean

Defines the partition file system configuration.

The properties of the weblogic.management.configuration.PartitionFileSystemMBean entity are as follows:

createOnDemand

Specifies whether the file system should be created on-demand when the partition is first started.

Type: boolean

Constraints: Has Default Value: true

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

`Name=user-specified-name`

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

preserved

Specifies whether the file system should be preserved when the partition is deleted.

Type: boolean

Constraints: Has Default Value: true

root

The full path to the root of this file subsystem of the partition.

Type: string

tags

Return all tags on this Configuration MBean

Type: array of string

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.PartitionLogMBean

Partition scoped logging configuration.

The properties of the weblogic.management.configuration.PartitionLogMBean entity are as follows:

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

enabledServerDebugAttributes

List of attributes from the WebLogic ServerDebugMBean that are enabled for the given partition. Note: Server level debug for a partition should be carefully enabled in consultation with a WebLogic system administrator only for a short period to capture additional debug output when troubleshooting a server problem.

Type: array of string

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

Name=*user-specified-name*

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`.

Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

platformLoggerLevels

Logger names and level map.

Type: java.util.Properties

tags

Return all tags on this Configuration MBean

Type: array of string

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.PartitionMBean

A domain partition. A configuration may define zero or more partitions.

The properties of the `weblogic.management.configuration.PartitionMBean` entity are as follows:

RCMHistoricalDataBufferLimit

The maximum number of elements retained for monitoring RCM usage requests over time.

Type: integer/int32

Constraints: Has Default Value: 250, Minimum Value: 1, Maximum Value: 5000

availableTargets

All the available targets for this partition.

Type: array of `weblogic.management.configuration.TargetMBean` references

batchJobsDataSourceJndiName

The JNDI name of the Batch runtime's `JobRepository` data source, which will be used to store data for Batch jobs submitted from applications deployed to the partition.

When a Java EE component submits a Batch job, the Batch runtime updates the `JobRepository` tables using this data source, which is obtained by looking up the data source's JNDI name.

Type: string

batchJobsExecutorServiceName

The name of the application-scoped Managed Executor Service instance that will be used to run Batch jobs that are submitted from applications deployed to the partition. A Managed Executor Service Template by the same name must exist for the domain when a Batch job is submitted in the partition. If this name returns null, then the Batch runtime will use the default Java EE Managed Executor Service that is bound to the default JNDI name of: `java:comp/DefaultManagedExecutorService`.

Type: string

dataSourceForJobScheduler

The data source required to support the persistence of jobs scheduled with the job scheduler.

Type: `weblogic.management.configuration.JDBCSystemResourceMBean` reference

defaultTargets

A list of default targets for the partition (if any).

Type: array of `weblogic.management.configuration.TargetMBean` references

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to `config.xml`

Type: boolean

Constraints: Read Only, Has Default Value: false

eagerTrackingOfResourceMetricsEnabled

Determines if tracking of resource consumption metrics of this Partition is initiated eagerly from the time the Partition is started, or if it is initiated lazily on first access of `PartitionResourceMetricsRuntimeMBean`.

Type: boolean

Constraints: Has Default Value: false

gracefulShutdownTimeout

The number of seconds a graceful shutdown operation waits before forcing a shut down. A graceful shutdown gives WebLogic Server subsystems time to complete certain application processing currently in progress. If subsystems are unable to complete processing within the number of seconds that you specify here, the partition will force shutdown automatically.

A value of `means` that the partition will wait indefinitely for a graceful shutdown to complete.

The graceful shutdown timeout applies only to graceful shutdown operations.

Type: integer/int32

Constraints: Has Default Value: 0, Minimum Value: 0

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

ignoreSessionsDuringShutdown

Indicates whether a graceful shutdown operation drops all HTTP sessions immediately.

If this is set to `false`, a graceful shutdown operation waits for HTTP sessions to complete or timeout.

Type: boolean

Constraints: Has Default Value: `false`

jobSchedulerTableName

The table name to use for storing timers active with the Job Scheduler.

Type: string

Constraints: Has Default Value: `WEBLOGIC_TIMERS`

maxConcurrentLongRunningRequests

The maximum number of running long-running requests that can be submitted to all the Managed Executor Services or Managed Scheduled Executor Services in the partition on the current server.

Type: integer/int32

Constraints: Has Default Value: 50, Minimum Value: 0, Maximum Value: 65534

maxConcurrentNewThreads

The maximum number of running threads that can be created by all the Managed Thread Factories in the partition on the current server.

Type: integer/int32

Constraints: Has Default Value: 50, Minimum Value: 0, Maximum Value: 65534

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

Name=user-specified-name

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

parallelDeployApplicationModules

Determines if the modules of applications will be deployed in parallel. This setting can be overridden at the per-application level. See `AppDeploymentMBean#isParallelDeployModules()`

Type: boolean

Constraints: Has Default Value: false

parallelDeployApplications

Determines if applications will be deployed in parallel.

Type: boolean

Constraints: Has Default Value: true

partitionID

The ID for this partition.

Type: string

Constraints: Read Only

partitionLifeCycleTimeoutVal

The number of seconds a force shutdown operation waits before timing out. If the operation does not complete within the configured timeout period, the partition will shutdown automatically if the state of the server at that time was `SHUTTING_DOWN`

A value of `means that the partition will wait indefinitely for the life cycle operation to complete.`

Type: integer/int32

Constraints: Has Secure Value: 120, Has Default Value: 30, Has Production Mode Default Value: 120, Minimum Value: 0

partitionWorkManagerRef

A reference to a partition-level work manager policy set by the system administrator.

Type: weblogic.management.configuration.PartitionWorkManagerMBean reference

primaryIdentityDomain

The partition's primary identity domain.

Type: string

realm

The security realm for this partition.

Type: weblogic.management.security.RealmMBean reference

resourceDeploymentPlanPath

The resource deployment plan path.

Type: string

resourceManagerRef

A resource manager reference from the resource management.

Type: weblogic.management.configuration.ResourceManagerMBean reference

startupTimeout

The timeout value for a partition's start and resume operations. If the partition fails to start within the timeout period, it will force a shutdown.

A value of `means` that the server will wait indefinitely for the operation to complete.

Type: integer/int32

Constraints: Has Default Value: 0, Has Production Mode Default Value: 0, Minimum Value: 0

tags

Return all tags on this Configuration MBean

Type: array of string

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

uploadDirectoryName

The directory path on the Administration Server where the uploaded applications for this partition are placed.

Type: string

weblogic.management.configuration.PartitionPropertyMBean

The PartitionPropertyMBean is used when performing macro substitution from elements in the ResourceGroupTemplateMBean. If a macro is encountered in the ResourceGroupTemplate attribute, then the macro name will be used to locate the corresponding PartitionPropertyMBean and the value will be substituted accordingly. Note that ConfigurationMBean contains getName/setName

The properties of the weblogic.management.configuration.PartitionPropertyMBean entity are as follows:

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

`Name=user-specified-name`

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

tags

Return all tags on this Configuration MBean

Type: array of string

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

value

Get the value for the given macro

Type: string

weblogic.management.configuration.PartitionUserFileSystemMBean

Defines the partition file system configuration.

The properties of the `weblogic.management.configuration.PartitionUserFileSystemMBean` entity are as follows:

createOnDemand

Specifies whether the file system should be created on-demand when the partition is first started.

Type: boolean

Constraints: Has Default Value: true

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to `config.xml`

Type: boolean

Constraints: Read Only, Has Default Value: false

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

Name=user-specified-name

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

preserved

Specifies whether the file system should be preserved when the partition is deleted.

Type: boolean

Constraints: Has Default Value: true

root

The full path to the root of this file subsystem of the partition.

Type: string

tags

Return all tags on this Configuration MBean

Type: array of string

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.PartitionWorkManagerMBean

Specifies partition-level work manager policies that are configured by domain system administrators.

The properties of the `weblogic.management.configuration.PartitionWorkManagerMBean` entity are as follows:

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to `config.xml`

Type: boolean

Constraints: Read Only, Has Default Value: false

fairShare

A desired percentage of thread usage by a partition compared to the thread usage by all partitions. It is recommended that the sum of this value for all the partitions running in a WLS domain add up to 100, but it is not strictly enforced. When they do not add up to 100, WLS assigns thread-usage times to different partitions based on their relative values.

Type: integer/int32

Constraints: Has Default Value: 50, Minimum Value: 1, Maximum Value: 99

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

maxThreadsConstraint

The maximum number of concurrent requests that the self-tuning thread pool can be processing on behalf of a partition at any given time. The default value of -1 means that this is only limited by the size of the self-tuning thread pool.

Type: integer/int32

Constraints: Has Default Value: -1

maxThreadsConstraintQueueSize

Desired size of the Partition MaxThreadsConstraint queue for requests pending execution.

Type: integer/int32

Constraints: Has Default Value: 8192, Minimum Value: 256, Maximum Value: 1073741824

minThreadsConstraintCap

This imposes an upper limit on the number of standby threads that can be created for satisfying the minimum threads constraints configured in a partition. If the sum of the configured values of all minimum threads constraints in a partition exceeds this configured value, a warning message will be logged and WLS will limit the number of threads the self-tuning thread pool will allocate to the partition to satisfy its minimum threads constraints. A value of 0 means no limit is imposed on the partition.

Type: integer/int32

Constraints: Has Default Value: 0, Minimum Value: 0, Maximum Value: 65534

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

Name=user-specified-name

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

sharedCapacityPercent

The total number of requests that can be present in the server for a partition, as a percentage of the `sharedCapacityForWorkManagers` attribute value in `OverloadProtection` MBean. This includes requests that are enqueued and those under execution.

Type: integer/int32

Constraints: Has Default Value: 100, Minimum Value: 1, Maximum Value: 100

tags

Return all tags on this Configuration MBean

Type: array of string

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.ResourceGroupMBean

A resource group is a named collection of deployable resources. Typically the resources in a given resource group are related in some way, for example in that they make up a single application suite.

The properties of the `weblogic.management.configuration.ResourceGroupMBean` entity are as follows:

administrative

Does this resource group contain administrative applications and resources? If true, then this is considered an administrative resource group and will be handled differently by the partition lifecycle. Specifically, an administrative resource group will be left running when a partition is shut down (it will be shut down only when the partition is halted).

Note that this Boolean is independent of the targeting of the resource group and works independently of the `autoTargetAdminServer` Boolean.

Type: boolean

Constraints: Has Default Value: false

autoTargetAdminServer

Should this resource group always be targeted to the Administration Server? If true, then this resource group will be targeted to the domain's Administration Server using the partition's administrative virtual target (`AdminVT`) in addition to any targets explicitly set on the resource group. Functionally, this is similar to getting the partition's administrative virtual target and explicitly adding it to the list of resource group targets.

Type: boolean

Constraints: Has Default Value: false

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

Name=user-specified-name

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

resourceGroupTemplate

The resource group template referenced by this resource group.

Type: weblogic.management.configuration.ResourceGroupTemplateMBean reference

tags

Return all tags on this Configuration MBean

Type: array of string

targets

A list of all the targets.

Type: array of weblogic.management.configuration.TargetMBean references

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

uploadDirectoryName

The directory path on the Administration Server where the uploaded applications for this resource group template are placed.

Type: string

useDefaultTarget

Checks whether this resource group uses the default target from the partition that contains the resource group.

Type: boolean

Constraints: Has Default Value: true

weblogic.management.configuration.ResourceGroupTemplateMBean

A resource group template is a named, domain-level collection of deployable resources intended to be used as a pattern by (usually) multiple resource groups. Each resource group that refers to a given template will have its own runtime copies of the resources defined in the template.

The properties of the `weblogic.management.configuration.ResourceGroupTemplateMBean` entity are as follows:

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to `config.xml`

Type: boolean

Constraints: Read Only, Has Default Value: false

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

Name=user-specified-name

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

tags

Return all tags on this Configuration MBean

Type: array of string

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

uploadDirectoryName

The directory path on the Administration Server where the uploaded applications for this resource group template are placed.

Type: string

weblogic.management.configuration.ResourceManagementMBean

This MBean is used to create and edit resource management policy configurations (Resource Managers) for the domain. Partition-scoped resource managers can be created under `PartitionMBean`.

The properties of the `weblogic.management.configuration.ResourceManagementMBean` entity are as follows:

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to `config.xml`

Type: boolean

Constraints: Read Only, Has Default Value: false

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

Name=user-specified-name

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`.

Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

tags

Return all tags on this Configuration MBean

Type: array of string

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.ResourceManagerMBean

A `{@code ResourceManagerMBean}` represents a resource consumption management policy. A policy controls and governs the use of shared resources in a Server runtime, by a Partition that the policy is attached to. A resource manager holds information on constraints and recourse actions for different resources in a Server instance.

A system administrator defines a resource manager and configures child MBeans that represent particular combinations of shares and usage limits of various resources in the Server runtime.

The system administrator may then assign the resource manager to one or more Partitions to ensure fair allocation of shared resources to collocated Domain Partitions, and to ensure that one Partition doesn't exhaust shared resources (potentially affecting other collocated Partitions).

The set of resources on which resource management policies can be assigned to, and the child MBeans through which they can be configured are:

1. File Open: FileOpenMBean
2. Heap Retained: HeapRetainedMBean
3. CPU Utilization: CpuUtilizationMBean

The properties of the `weblogic.management.configuration.ResourceManagerMBean` entity are as follows:

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to `config.xml`

Type: boolean

Constraints: Read Only, Has Default Value: false

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

Name=user-specified-name

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

tags

Return all tags on this Configuration MBean

Type: array of string

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.ResponseTimeRequestClassMBean

This MBean defines the response time goal for this request class.

Response time goals can be used to differentiate request classes. We do not try to meet a response time goal for an individual request. Rather we compute a tolerable waiting time for a request class by subtracting the observed average thread use time. Then we schedule requests so that the average wait for each request class is in proportion to their tolerable waiting time. For example, consider we only have two request classes, A and B, with response time goals 2000ms and 5000ms, respectively, where the time an individual request uses a thread is much smaller. During a period in which both request classes are sufficiently requested, say, zero think time and more clients than threads, we schedule to keep the average response time in the ratio 2:5 so that it is a common fraction or multiple of the stated goal.

The properties of the `weblogic.management.configuration.ResponseTimeRequestClassMBean` entity are as follows:

deploymentOrder

A priority that the server uses to determine when it deploys an item. The priority is relative to other deployable items of the same type.

For example, the server prioritizes and deploys all EJBs before it prioritizes and deploys startup classes.

Items with the lowest Deployment Order value are deployed first. There is no guarantee on the order of deployments with equal Deployment Order values. There is no guarantee of ordering across clusters.

Type: integer/int32

Constraints: Has Default Value: 1000, Minimum Value: 0, Maximum Value: 2147483647

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

goalMs

A response time goal in milliseconds.

You can either define a response time goal or keep the -1 default value, which acts as a placeholder for the response time goal. By doing so, you have not defined the response time goal at run time but can define one later.

Type: integer/int32

Constraints: Has Default Value: -1

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

Name=user-specified-name

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`.

Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

tags

Return all tags on this Configuration MBean

Type: array of string

targets

You must select a target on which an MBean will be deployed from this list of the targets in the current domain on which this item can be deployed. Targets must be either servers or clusters. The deployment will only occur once if deployments overlap.

Type: array of `weblogic.management.configuration.TargetMBean` references

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.RestartLoopProtectionMBean

{@code RestartLoopProtectionMBean} defines the configuration to stop the partition from entering an endless restart loop. It is an optional configuration and when enabled it is a resource manager wide configuration.

The properties of the weblogic.management.configuration.RestartLoopProtectionMBean entity are as follows:

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

maxRestartAllowed

Gets the value of max-restart-allowed. max-restart-allowed is defined as the maximum number of RCM initiated partition restarts allowed in the specified time interval(as specified by max-restart-allowed-interval), after which the partition will be halted upon an RCM initiated request to restart the partition.

Type: integer/int64

Constraints: Minimum Value: 0

maxRestartAllowedInterval

Gets the value of max-restart-allowed-interval. The max-restart-allowed-interval is defined as a fixed-width, sliding-window time interval (in seconds) within which the specified number (as specified by max-restart-allowed) of RCM initiated partition restarts are permitted. A RCM initiated request to restart the partition that exceeds the given max-restart-allowed number in the given max-restart-allowed-interval will lead to the partition being halted than being restarted.

Type: integer/int64

Constraints: Minimum Value: 0

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

`Name=user-specified-name`

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

restartDelay

The restart delay. A restart delay introduces a delay before starting the partition, as part of the RCM initiated restart action.

Type: integer/int64

Constraints: Minimum Value: 0

restartLoopProtectionEnabled

Checks if restart loop protection is enabled.

Type: boolean

tags

Return all tags on this Configuration MBean

Type: array of string

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.RestfulManagementServicesMBean

Controls the configuration of the RESTful Management Services interfaces to WebLogic Server.

The properties of the `weblogic.management.configuration.RestfulManagementServicesMBean` entity are as follows:

delegatedRequestConnectTimeoutMillis

Determines the connection timeout, in milliseconds, when the Management Services Web application propagates an idempotent REST request from the admin server to a managed server.

If `DelegatedRequestConnectTimeouttMillis` is zero, then the default underlying JAXRS client api connection timeout will be used.

Type: integer/int32

Constraints: Has Default Value: 30000, Minimum Value: 0

delegatedRequestMaxWaitMillis

Determines how long the Management Services Web application will wait, in milliseconds, when it propagates an idempotent REST request from the admin server to a managed server. If zero, then it will try to propagate the request once. If greater

than zero, then it will retry the request until it finishes or until it detects that the time limit has been exceeded.

.

A request can override this value by specifying the requestMaxWaitMillis query parameter.

Type: integer/int32

Constraints: Has Default Value: 0, Minimum Value: 0

delegatedRequestMinThreads

Specifies the minimum number of threads that should be dedicated to the Management Services Web application when interacting with managed servers in parallel for improved responsiveness in large domains.

Type: integer/int32

Constraints: Has Default Value: 25, Minimum Value: 1

delegatedRequestReadTimeoutMillis

Determines the read timeout, in milliseconds, when the Management Services Web application propagates an idempotent REST request from the admin server to a managed server.

If DelegatedRequestReadTimeoutMillis is zero, then the default underlying JAXRS client api read timeout will be used.

Type: integer/int32

Constraints: Has Default Value: 10000, Minimum Value: 0

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

enabled

Enables the monitoring of this WebLogic Server domain through the RESTful Management Services Web application.

Type: boolean

Constraints: Has Default Value: true

fannedOutRequestMaxWaitMillis

Determines how long the Management Services Web application will wait, in milliseconds, when it fans out an idempotent REST request from the admin server to all the managed servers. If zero, then it will choose an appropriate timeout.

.

A request can override this value by specifying the requestMaxWaitMillis query parameter.

Type: integer/int32

Constraints: Has Default Value: 180000, Minimum Value: 0

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

javaServiceResourcesEnabled

Specifies whether the REST resource features for administering WebLogic Server as a Java Service within a cloud environment should be enabled in this domain.

Type: boolean

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's

`javax.management.ObjectName`

`Name=user-specified-name`

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as

XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`.

Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

tags

Return all tags on this Configuration MBean

Type: array of string

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.SAFAgentMBean

This class represents a Store-and-Forward (SAF) agent. A SAF sending agent takes care of storing messages to a persistent storage, forwarding messages to the receiving side, and re-transmitting messages when acknowledgements do not come back in time. A SAF receiving agent takes care of detecting and eliminating duplicate messages sent by the receiving agent, and deliver messages to the final endpoint.

The properties of the `weblogic.management.configuration.SAFAgentMBean` entity are as follows:

acknowledgeInterval

The maximum interval between two successive acknowledgements sent by the receiving side.

- Applies only to agents with receiving capability.

- A value of -1 specifies that there is no time limit between successive acknowledgements.
- Updating `AcknowledgeInterval` causes connections starting after the update to use the new value.

Type: integer/int64

Constraints: Has Default Value: -1

bytesMaximum

The maximum bytes quota (total amount of bytes) that can be stored in this SAF agent.

- The default value of -1 specifies that there is no WebLogic-imposed limit on the number of bytes that can be stored. However, excessive bytes volume can cause memory saturation, so this value should correspond to the total amount of available system memory relative to the rest of your application load.
- Applies only to agents with sending capability.
- Updating `BytesMaximum` affects only new requests.

Range of Values: \geq BytesThresholdHigh

Type: integer/int64

Constraints: Has Default Value: -1, Minimum Value: -1

bytesThresholdHigh

The upper threshold value that triggers events based on the number of bytes stored in the SAF agent.

- The default value of -1 disables the events for this SAF agent.
- Applies only to agents with sending capability.
- Updating `BytesThresholdHigh` affects only new requests.
- If the number of bytes exceeds this threshold, the triggered events are:
 - **Log Messages:** A message is logged on the server indicating a high threshold condition.
 - **Flow Control:** The agent becomes armed and instructs producers to begin decreasing their message flow.

Range of Values: \leq BytesMaximum; \geq BytesThresholdLow

Type: integer/int64

Constraints: Has Default Value: -1, Minimum Value: -1

bytesThresholdLow

The lower threshold that triggers events based on the number of bytes stored in the SAF agent.

- The default value of -1 disables the events for this SAF agent.
- Applies only to agents with sending capability.
- Updating `BytesThresholdLow` affects only new requests.
- If the number of bytes falls below this threshold, the triggered events are:
 - **Log Messages:** A message is logged on the server indicating that the threshold condition has cleared.

- **Flow Control:** The agent becomes disarmed and instructs producers to begin increasing their message flow.

Range of Values: \leq BytesThresholdHigh

Type: integer/int64

Constraints: Has Default Value: -1, Minimum Value: -1

conversationIdleTimeMaximum

The maximum amount of time allowed, in milliseconds, before a sending side releases the resources used by a conversation.

- If there is no activity for a conversation for the specified amount of time, the sending agent releases all resources for that conversation and notifies the receiving agent to do the same.
- A value of specifies that resources for a conversation are not released unless the application explicitly closes the conversation.
- Updating ConversationIdleTimeMaximum causes connections starting after the update to use the new value.

Type: integer/int64

Constraints: Has Default Value: 0, Minimum Value: 0

defaultRetryDelayBase

The amount of time, in milliseconds, between the original delivery attempt and the first retry.

- If RetryDelayMultiplier is set to , this defines the interval between any two successive retry attempts.
- Applies only to agents with sending capability.
- Updating DefaultRetryDelayBase causes connections starting after the update to use the new value.

Range of Values: \leq RetryDelayMaximum if RetryDelayMultiplier is not 1.0.

Type: integer/int64

Constraints: Has Default Value: 20000, Minimum Value: 1

defaultRetryDelayMaximum

The maximum amount of time, in milliseconds, between two successive delivery retry attempts.

- Applies only to agents with sending capability.
- Updating DefaultRetryDelayMaximum causes connections starting after the update to use the new value.

Range of Values: $> =$ RetryDelayBase if RetryDelayMultiplier is not 1.0.

Type: integer/int64

Constraints: Has Default Value: 180000, Minimum Value: 1

defaultRetryDelayMultiplier

The factor used to multiply the previous delay time to calculate the next delay time to be used.

- Applies only to agents with sending capability.

- Updating `DefaultRetryDelayMultiplier` causes connections starting after the update to use the new value.

Range of Values: ≥ 1 .

Type: number/double

Constraints: Has Default Value: 1.0, Minimum Value: 1.0

defaultTimeToLive

The default amount of time, in milliseconds, that the agent guarantees to reliably send messages.

- A value of 0 means the agent guarantees to reliably send messages for the duration of the conversation.
- Updating `DefaultTimeToLive` causes conversations starting after the update to use the new value.

Type: integer/int64

Constraints: Has Default Value: 0, Minimum Value: 0

deploymentOrder

A priority that the server uses to determine when it deploys an item. The priority is relative to other deployable items of the same type.

For example, the server prioritizes and deploys all EJBs before it prioritizes and deploys startup classes.

Items with the lowest Deployment Order value are deployed first. There is no guarantee on the order of deployments with equal Deployment Order values. There is no guarantee of ordering across clusters.

Type: integer/int32

Constraints: Has Default Value: 1000, Minimum Value: 0, Maximum Value: 2147483647

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

forwardingPausedAtStartup

Specifies whether the agent is paused for forwarding messages at the startup time.

When enabled, the sending agent forwards messages. Otherwise, the sending agent does not forward any messages.

If the value is changed and activated, you need to restart any servers to which the MBean is targeted before the value will take effect (even though you do not get a warning in the Console that the server needs to be restarted).

Type: boolean

Constraints: Has Default Value: false

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

incomingPausedAtStartup

Specifies whether the agent is paused for incoming messages at startup time.

When enabled, the sending agent accepts new messages. Otherwise, the sending agent does not accept any new messages.

If the value is changed and activated, you need to restart any servers to which the MBean is targeted before the value will take effect (even though you do not get a warning in the Console that the server needs to be restarted).

Type: boolean

Constraints: Has Default Value: false

loggingEnabled

Specifies whether a message is logged in the server log file when a message fails to be forwarded.

- If selected, this applies to messages that fail to be forwarded and delivered to the final destination when there is no error handling in a SAF application or the application's error handling fails.
- Applies only to agents with receiving capability.
- Updating `LoggingEnabled` causes connections starting after the update to use the new value.

Type: boolean

Constraints: Has Default Value: true

maximumMessageSize

The maximum number of bytes allowed in individual messages on this SAF agent.

- The message size includes the message body, any user-defined properties, and the user-defined JMS header fields: `JMSCorrelationID` and `JMSType`
- Producers sending messages that exceed the configured maximum message size for the SAF agent will receive a `ResourceAllocationException`
- The maximum message size is only enforced for the initial production of a message. Messages that are redirected to an error destination or forwarded to a member of a distributed destination are not checked for size. For instance, if a destination and its corresponding error destination are configured with a maximum message size of 128K bytes and 64K bytes, respectively, a message of 96K bytes could be redirected to the error destination (even though it exceeds the 64K byte maximum), but a producer could not directly send the 96K byte message to the error destination.
- Applies only to agents with sending capability.
- Updating `MaximumMessageSize` affects only incoming messages; stored messages are not affected.

Type: integer/int32

Constraints: Has Default Value: 2147483647, Minimum Value: 0

messageBufferSize

The amount of memory used to store message bodies in memory before they are paged out to disk.

- A value of -1 (the default) specifies that the server will automatically determine a size based on the maximum heap size of the JVM. This default will be set to either one-third the maximum heap size, or 512 megabytes, whichever is smaller.
- The larger the buffer, the more memory JMS will consume when many messages are waiting on queues or topics. Once the buffer is surpassed, JMS may write message bodies to the directory specified by `PagingDirectory` in an effort to reduce memory usage below this buffer.
- Surpassing the buffer size does not stop the JMS server from accepting new messages. It is still possible to run out of memory if messages are arriving faster than they can be written to disk. Users with high messaging loads who wish to support the highest possible availability should consider setting a quota or setting a threshold and enabling flow control.
- Applies only to agents with sending capability.
- Paging is always supported.
- Updating the memory size resets the message count so that only requests arriving after the update are charged against the new memory size.

Type: integer/int64

Constraints: Has Default Value: -1, Minimum Value: -1

messageCompressionOptions

Specifies the type of message compression used when JMS message body compression is enabled for Persistent Stores and JMS Paging Stores.

- Use `GZIP_DEFAULT_COMPRESSION` to enable message compression using the JDK GZIP API with `DEFAULT_COMPRESSION` level.
- Use `GZIP_BEST_COMPRESSION` to enable message compression using the JDK GZIP API with `BEST_COMPRESSION` level.
- Use `GZIP_BEST_SPEED` to enable message compression using the JDK GZIP API with `BEST_SPEED` level.
- Use `LZF` to enable message compression using Open Source LZF.

This attribute should be used only when configuring a WebLogic domain in an Oracle Exalogic environment.

Type: string

Constraints: Has Default Value: `GZIP_DEFAULT_COMPRESSION`, Legal Values: `GZIP_DEFAULT_COMPRESSION`, `GZIP_BEST_COMPRESSION`, `GZIP_BEST_SPEED`, `LZF`

messagesMaximum

The maximum message quota (total amount of messages) that can be stored in this SAF agent.

- The default value of -1 specifies that the server instance has no limit on the number of messages that can be stored. However, excessive message volume can cause memory saturation, so this value should correspond to the total amount of available system memory relative to the rest of your application load.
- Applies only to sending agents.
- Updating the maximum message quota resets the message count so that only requests arriving after the update are charged against the new quota.

Range of Values: \geq `MessagesThresholdHigh`

Type: integer/int64

Constraints: Has Default Value: -1, Minimum Value: -1

messagesThresholdHigh

The upper threshold that triggers events based on the number of messages stored in the SAF agent.

- The default value of -1 disables the events for this SAF agent.
- Applies only to agents with sending capability.
- Updating `MessagesThresholdHigh` affects only new requests.
- If the number of messages exceeds this threshold, the triggered events are:
 - **Log Messages:** A message is logged on the server indicating a high threshold condition.
 - **Flow Control:** The agent becomes armed and instructs producers to begin decreasing their message flow.

Range of Values: \leq MessagesMaximum; \geq MessagesThresholdLow

Type: integer/int64

Constraints: Has Default Value: -1, Minimum Value: -1

messagesThresholdLow

The low threshold that triggers events based on the number of messages stored in the SAF agent.

- The default value of -1 disables the events for this SAF agent.
- Applies only to agents with sending capability.
- Updating `MessagesThresholdLow` affects only new requests.
- If the number of messages falls below this threshold, the triggered events are:
 - **Log Messages:** A message is logged on the server indicating that the threshold condition has cleared.
 - **Flow Control:** The agent becomes disarmed and instructs producers to begin increasing their message flow.

Range of Values: \leq MessagesThresholdHigh.

Type: integer/int64

Constraints: Has Default Value: -1, Minimum Value: -1

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

Name=user-specified-name

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

pagingDirectory

Specifies where message bodies are written when the size of the message bodies in the JMS server exceeds the message buffer size. If unspecified, messages are written to the `tmp` directory in the host WebLogic Server instance's directory. For example, `domainName/servers/servername/tmp`.

- For best performance, this directory should not be the same as the directory used by the SAF agent's persistent store.
- Applies only to agents with sending capability.

If the value is changed and activated, you need to restart any servers to which the MBean is targeted before the value will take effect (even though you do not get a warning in the Console that the server needs to be restarted).

Type: string

Constraints: Has Default Value: null, Legal Null: true

pagingMessageCompressionEnabled

Enables the JMS paging store to perform message body compression on persistent and non-persistent messages. When `false`, the default value, no compression is performed.

This attribute should be enabled only when configuring a WebLogic domain in an Oracle Exalogic environment.

Type: boolean

Constraints: Has Default Value: false

receivingPausedAtStartup

Specifies whether the agent is paused for receiving messages at the startup time.

When enabled, the sending agent receives messages. Otherwise, the sending agent does not receive any messages.

If the value is changed and activated, you need to restart any servers to which the MBean is targeted before the value will take effect (even though you do not get a warning in the Console that the server needs to be restarted).

Type: boolean

Constraints: Has Default Value: false

serviceType

The type of service that this SAF agent provides. JMS requires only a Sending agent on the sending side for messages. Whereas, Web Services Reliable Messaging requires both a Sending and Receiving agent for messages.

- **Sending-only** Configures an agent that stores messages in persistent storage, forwards messages to the receiving side, and re-transmits messages when acknowledgements do not come back in time.
- **Receiving-only** Configures an agent that detects and eliminates duplicate messages sent by a receiving agent, and delivers messages to the final destination.

- **Both** Configures an agent that has sending and receiving agent functionality.

If the value is changed and activated, you need to restart any servers to which the MBean is targeted before the value will take effect (even though you do not get a warning in the Console that the server needs to be restarted).

Type: string

Constraints: Has Default Value: Both, Legal Values: Both, Sending-only, Receiving-only

store

The persistent disk-based file store or JDBC-accessible database for the SAF agent.

If a store is not configured, the server's default store is used.

If the value is changed and activated, you need to restart any servers to which the MBean is targeted before the value will take effect (even though you do not get a warning in the Console that the server needs to be restarted).

Type: weblogic.management.configuration.PersistentStoreMBean reference

Constraints: Restart Required

storeMessageCompressionEnabled

Enables the JMS store to perform message body compression. When set to *false*, the default value, no compression is performed.

This attribute should be enabled only when configuring a WebLogic domain in an Oracle Exalogic environment.

Type: boolean

Constraints: Has Default Value: false

tags

Return all tags on this Configuration MBean

Type: array of string

targets

Type: array of weblogic.management.configuration.TargetMBean references

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

windowInterval

The maximum amount of time, in milliseconds, that a JMS sending agent waits before forwarding messages in a single batch. For a distributed queue or topic, `WindowInterval` setting is ignored.

A sending agent waits to forward the message batch until either: (A) the source destination message count is greater than or equal to the configured `Window Size`; (B) it has waited a specified `Window Interval`, whichever comes first.

Type: integer/int64

Constraints: Has Default Value: 0, Minimum Value: 0

windowSize

For JMS messages, the number of messages in a batch. A sending agent waits to forward a message batch until the source destination message count is greater than or equal to this value. For a distributed queue or topic, `WindowSize` setting is ignored and always internally set to 1 message.

For WSRM, the maximum number of unacknowledged messages allowed between a source destination and a target destination during a conversation.

Type: integer/int32

Constraints: Has Default Value: 10, Minimum Value: 1

weblogic.management.configuration.SNMPAgentDeploymentMBean

This MBean is an SNMP agent that can be targeted to instances of WebLogic Server.

With SNMP, you configure **agents** to gather and send data about managed resources in response to a request from **managers**. You can also configure agents to issue unsolicited reports to managers when they detect predefined thresholds or conditions on a managed resource.

In a WebLogic Server domain, you can choose a centralized or de-centralized model for SNMP monitoring and communication:

- In a centralized model, you create an instance of this MBean and target it only to the Administration Server. This agent communicates with all Managed Servers in the domain. SNMP managers communicate only with the SNMP agent on the Administration Server. This model is convenient but introduces performance overhead in WebLogic Server. In addition, if the Administration Server is unavailable, you cannot monitor the domain through SNMP.
- In a de-centralized model, you create an instance of this MBean and target it to each Managed Server that you want to monitor. (Alternatively, you can create multiple instances of this MBean and target each instance to an individual Managed Server.) Your SNMP manager must communicate with the agents on individual Managed Servers.

To support domains that were created with WebLogic Server release 9.2 and earlier, a domain also hosts a singleton SNMP agent whose scope is the entire domain (see `SNMPAgentMBean`). `SNMPAgentMBean` offers the same features as an instance of this MBean (`SNMPAgentDeploymentMBean`) that you have targeted as described in the centralized model above. However, the underlying implementation of `SNMPAgentMBean` is different and it will eventually be deprecated. `SNMPAgentMBean` is overridden if you target an instance of this MBean to the Administration Server.

The properties of the `weblogic.management.configuration.SNMPAgentDeploymentMBean` entity are as follows:

SNMPAccessForUserMBeansEnabled

Configures this SNMP agent to provide read-only access to MBean types that you have created and registered (custom MBeans).

If you enable this access, when you register a custom MBean in a WebLogic Server `MBeanServer`, this SNMP agent dynamically updates a runtime MIB module that WebLogic Server maintains for custom MBeans.

For each custom MBean type, WebLogic Server adds a table to the MIB module. For each instance of the custom MBean, it adds a table row. While WebLogic Server does

not persist the MIB as a file or other data structure, the OIDs in the MIB remain constant across server sessions.

The MIB module for custom MBeans is managed by a subAgent. Its master agent is this WebLogic Server SNMP agent and it communicates with the master agent through the AgentX port.

Type: boolean

SNMPEngineId

An identifier for this SNMP agent that is unique amongst all other SNMP agents in the current WebLogic Server domain.

If you use SNMPv3 to send messages to this SNMP agent, you must specify the SNMP engine ID when you configure the SNMP manager.

For an SNMP agent on an Administration Server, the default value is the name of the WebLogic Server domain. For an agent on a Managed Server, the default is the name of the server.

Type: string

Constraints: Legal Null: true

SNMPPort

The port on which you want this SNMP agent to listen for incoming requests from SNMP managers that use the UDP protocol.

SNMP managers can use this port to ping the SNMP agent and request the status of specific attributes.

If you target this SNMP agent to multiple server instances, and if two or more servers are running on the same computer, WebLogic Server will automatically increment this UDP port value by 1 for each agent. WebLogic Server never assigns port 162 because it is the default port that an agent uses to send notifications. In addition, if any port is already in use, WebLogic Server skips the port and assigns the next available port.

For example, if you use the default value of this attribute and then target this agent to ManagedServer1 and ManagedServer2, and if both servers are running on the same computer, then the agent on ManagedServer1 will listen on UDP port 161 and the agent on ManagedServer2 will listen on UDP port 163.

The incremented port number is not persisted in the domain's configuration; when WebLogic Server increments port numbers, it does so in the order in which servers are started on the same computer.

If WebLogic Server re-assigns the UDP port for an SNMP agent, look in the agent's `SNMPAgentRuntimeMBean` to see the agent's runtime UDP port.

SNMP agents can also communicate through the host server's TCP listen port (7001 by default) or through a TCP port that is configured by a custom network channel.

Type: integer/int32

Constraints: Has Default Value: 161, Minimum Value: 1, Maximum Value: 65535

SNMPTrapVersion

The SNMP notification version that this SNMP agent generates.

Type: integer/int32

Constraints: Has Default Value: 1, Legal Values: 1, 2, 3

authenticationProtocol

The protocol that this SNMP agent uses to ensure that only authorized users can request or receive information about your WebLogic Server domain. Applicable only with SNMPv3.

The protocol also ensures message integrity and prevents masquerading and reordered, delayed, or replayed messages.

To use this protocol when receiving requests from SNMP managers, you must configure credential mapping in the WebLogic Server security realm. To use this protocol when sending responses or notifications, you must configure the security level of your trap destinations.

If you do not choose an authentication protocol, then the SNMP agent does not authenticate incoming SNMPv3 requests; anyone can use SNMPv3 to retrieve information about your WebLogic Server domain.

Type: string

Constraints: Has Default Value: noAuth, Has Production Mode Default Value: MD5, Legal Values: noAuth, MD5, SHA, Legal Null: true

communityBasedAccessEnabled

Specifies whether this SNMP agent supports SNMPv1 and v2.

SNMPv1 and v2 use community strings for authentication. If you disable community strings for this SNMP agent, the agent will process only SNMPv3 requests. If an SNMP manager sends a v1 or v2 message, the agent discards the message and returns an error code to the manager.

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: true

communityPrefix

The password (community name) that you want this SNMP agent to use to secure SNMPv1 or v2 communication with SNMP managers. Requires you to enable community based access for this agent.

SNMPv3 does not use community names. Instead, it encrypts user names and passwords in its PDUs.

When you use SNMPv1 or v2, there are two community names that are needed when the WebLogic SNMP agent and SNMP managers interact:

- The name that you specify in this community prefix. All SNMP managers must send this name when connecting to this SNMP agent.
- The community name that the SNMP manager defines. The SNMP agent must send this name when connecting to the manager. (You supply this community name when you configure a trap destination.)

In addition to using the community prefix as a password, an SNMP agent on an Administration Server uses the prefix to qualify requests from SNMP managers. Because the Administration Server can access data for all WebLogic Server instances in a domain, a request that specifies only an attribute name is potentially ambiguous. For example, the attribute `serverUptime` exists for each WebLogic Server instance in a domain. To clarify requests that you send to SNMP agents on Administration Servers, use the community prefix as follows:

- To request the value of an attribute on a specific Managed Server, when you send a request from an SNMP manager, append the name of the server instance to the community prefix: `community_prefix@server_name`

- To request the value of an attribute for all server instances in a domain, send a community name with the following form: *community_prefix*

To secure access to the values of the WebLogic attributes when using the SNMPv1 or v2 protocols, it is recommended that you set community prefix to a value other than `public`

You cannot specify a null (empty) value for the community prefix. If you delete the prefix value, WebLogic Server resets the value to `public`. If you do not want this agent to receive SNMPv1 or v2 requests, instead of trying to set the community prefix to a null value, disable community based access. With community based access disabled, WebLogic Server ignores the community prefix value.

Type: string

Constraints: Has Recommended Secure Value: A unique value, should not be public or private, Has Default Value: `public`, Legal Null: `true`

deploymentOrder

A priority that the server uses to determine when it deploys an item. The priority is relative to other deployable items of the same type.

For example, the server prioritizes and deploys all EJBs before it prioritizes and deploys startup classes.

Items with the lowest Deployment Order value are deployed first. There is no guarantee on the order of deployments with equal Deployment Order values. There is no guarantee of ordering across clusters.

Type: integer/int32

Constraints: Has Default Value: 1000, Minimum Value: 0, Maximum Value: 2147483647

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to `config.xml`

Type: boolean

Constraints: Read Only, Has Default Value: `false`

enabled

Specifies whether this SNMP agent is enabled.

Type: boolean

Constraints: Has Secure Value: `false`, Has Default Value: `false`

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

informEnabled

Configures this SNMP agent to send notifications as an INFORM instead of a TRAP. Requires you to specify the agent's `SNMPTrapVersion` as `SNMPv2` or `SNMPv3`.

When an agent sends an INFORM notification, it waits for a confirmation response from the SNMP manager. If it does not receive a response, it resends the INFORM notification.

Type: boolean

Constraints: Has Default Value: false

informRetryInterval

The number of milliseconds that this SNMP agent will wait for a response to an INFORM notification.

If the agent does not receive a response within the specified interval, it will resend the notification.

Type: integer/int32

Constraints: Has Default Value: 10000, Minimum Value: 3000, Maximum Value: 30000

listenAddress

The listen address on which you want this SNMP agent to listen for incoming requests from SNMP managers that use the UDP protocol.

If not specified the Server's ListenAddress is used as the ListenAddress for the SNMPAgent.

Type: string

localizedKeyCacheInvalidationInterval

The number of milliseconds after which WebLogic Server invalidates its cache of SNMP security keys. Setting a high value creates a risk that users whose credentials have been removed can still access SNMP data.

An SNMP security key is an encrypted version of an SNMP agent's engine ID and an authentication password or privacy password. WebLogic Server generates one security key for each entry that you create in the SNMP credential map. When a WebLogic Server SNMP agent receives an SNMPv3 request, it compares the key that is in the request with its WebLogic Server keys. If it finds a match, it processes the request. The SNMP agent also encodes these keys in its responses and notifications. (You configure which keys are encoded when you create a trap destination.)

Instead of regenerating the keys for each SNMPv3 communication, WebLogic Server caches the keys. To make sure that the cache contains the latest set of SNMP credentials, WebLogic Server periodically invalidates the cache. After the cache is invalidated, the next time an SNMP agent requests credentials, WebLogic Server regenerates the cache.

Note that making a change to the credential map does not automatically update the cache. Instead, the cache is updated only after it has been invalidated.

For example, if you update a privacy password in an existing entry in the SNMP credential map, the SNMP agent is not aware of the new password until the key cache is invalidated and regenerated. An SNMP user with the old security password can still access WebLogic Server data until the cache is invalidated.

You can invalidate a key immediately instead of waiting for this invalidation interval to expire.

Type: integer/int64

Constraints: Has Default Value: 3600000, Maximum Value: 86400000

masterAgentXPort

The port that this SNMP agent uses to communicate with its subagents.

The agent uses subagents to provide access to custom MBeans (MBeans that you create and register) and to other software components. WebLogic Server SNMP agents do not enable users to register their own subagents.

Type: integer/int32

Constraints: Has Default Value: 705, Minimum Value: 1, Maximum Value: 65535

maxInformRetryCount

The maximum number of times that this SNMP agent will resend INFORM notifications for which it has not received a response.

Type: integer/int32

Constraints: Has Default Value: 1, Minimum Value: 1, Maximum Value: 3

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

`Name=user-specified-name`

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

privacyProtocol

The protocol that this SNMP agent uses to encrypt and unencrypt messages. Applicable only with SNMPv3. Requires you to also use an authentication protocol.

To use this protocol when sending responses or notifications, you must also configure the security level of your trap destinations.

If you do not choose a privacy protocol, then communication between this agent and managers can be viewed (but not altered) by unauthorized users.

Type: string

Constraints: Has Default Value: noPriv, Legal Values: noPriv, DES, AES_128, Legal Null: true

sendAutomaticTrapsEnabled

Specifies whether this SNMP agent sends automatically generated notifications to SNMP managers.

The SNMP agent generates automatic notifications when any of the following events occur:

- The WebLogic Server instance that is hosting the SNMP agent starts.
This type of notification (coldStart) has no variable bindings.
- A server instance starts or stops.

An SNMP agent on a Managed Server generates these notifications only when its host Managed Server starts or stops. An SNMP agent on an Administration Server generates these notifications when any server in the domain starts or stops.

These notification types (serverStart and serverShutdown) contain variable bindings to identify the server that started or stopped and the time at which the notification was generated.

Type: boolean

Constraints: Has Default Value: true

tags

Return all tags on this Configuration MBean

Type: array of string

targets

You must select a target on which an MBean will be deployed from this list of the targets in the current domain on which this item can be deployed. Targets must be either servers or clusters. The deployment will only occur once if deployments overlap.

Type: array of weblogic.management.configuration.TargetMBean references

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.SNMPAgentMBean

This singleton MBean represents an SNMP agent that is scoped to a WebLogic Server domain.

This MBean is provided to support domains that were created with WebLogic Server release 9.2 and earlier. For new domains, create an instance of SNMPAgentDeploymentMBean and target it to the domain's Administration Server.

The properties of the weblogic.management.configuration.SNMPAgentMBean entity are as follows:

SNMPAccessForUserMBeansEnabled

Configures this SNMP agent to provide read-only access to MBean types that you have created and registered (custom MBeans).

If you enable this access, when you register a custom MBean in a WebLogic Server MBeanServer, this SNMP agent dynamically updates a runtime MIB module that WebLogic Server maintains for custom MBeans.

For each custom MBean type, WebLogic Server adds a table to the MIB module. For each instance of the custom MBean, it adds a table row. While WebLogic Server does not persist the MIB as a file or other data structure, the OIDs in the MIB remain constant across server sessions.

The MIB module for custom MBeans is managed by a subAgent. Its master agent is this WebLogic Server SNMP agent and it communicates with the master agent through the AgentX port.

Type: boolean

SNMPEngineId

An identifier for this SNMP agent that is unique amongst all other SNMP agents in the current WebLogic Server domain.

If you use SNMPv3 to send messages to this SNMP agent, you must specify the SNMP engine ID when you configure the SNMP manager.

For an SNMP agent on an Administration Server, the default value is the name of the WebLogic Server domain. For an agent on a Managed Server, the default is the name of the server.

Type: string

Constraints: Legal Null: true

SNMPPort

The port on which you want this SNMP agent to listen for incoming requests from SNMP managers that use the UDP protocol.

SNMP managers can use this port to ping the SNMP agent and request the status of specific attributes.

If you target this SNMP agent to multiple server instances, and if two or more servers are running on the same computer, WebLogic Server will automatically increment this UDP port value by 1 for each agent. WebLogic Server never assigns port 162 because it is the default port that an agent uses to send notifications. In addition, if any port is already in use, WebLogic Server skips the port and assigns the next available port.

For example, if you use the default value of this attribute and then target this agent to ManagedServer1 and ManagedServer2, and if both servers are running on the same computer, then the agent on ManagedServer1 will listen on UDP port 161 and the agent on ManagedServer2 will listen on UDP port 163.

The incremented port number is not persisted in the domain's configuration; when WebLogic Server increments port numbers, it does so in the order in which servers are started on the same computer.

If WebLogic Server re-assigns the UDP port for an SNMP agent, look in the agent's `SNMPAgentRuntimeMBean` to see the agent's runtime UDP port.

SNMP agents can also communicate through the host server's TCP listen port (7001 by default) or through a TCP port that is configured by a custom network channel.

Type: integer/int32

Constraints: Has Default Value: 161, Minimum Value: 1, Maximum Value: 65535

SNMPTrapVersion

The SNMP notification version that this SNMP agent generates.

Type: integer/int32

Constraints: Has Default Value: 1, Legal Values: 1, 2, 3

authenticationProtocol

The protocol that this SNMP agent uses to ensure that only authorized users can request or receive information about your WebLogic Server domain. Applicable only with SNMPv3.

The protocol also ensures message integrity and prevents masquerading and reordered, delayed, or replayed messages.

To use this protocol when receiving requests from SNMP managers, you must configure credential mapping in the WebLogic Server security realm. To use this

protocol when sending responses or notifications, you must configure the security level of your trap destinations.

If you do not choose an authentication protocol, then the SNMP agent does not authenticate incoming SNMPv3 requests; anyone can use SNMPv3 to retrieve information about your WebLogic Server domain.

Type: string

Constraints: Has Default Value: noAuth, Has Production Mode Default Value: MD5, Legal Values: noAuth, MD5, SHA, Legal Null: true

communityBasedAccessEnabled

Specifies whether this SNMP agent supports SNMPv1 and v2.

SNMPv1 and v2 use community strings for authentication. If you disable community strings for this SNMP agent, the agent will process only SNMPv3 requests. If an SNMP manager sends a v1 or v2 message, the agent discards the message and returns an error code to the manager.

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: true

communityPrefix

The password (community name) that you want this SNMP agent to use to secure SNMPv1 or v2 communication with SNMP managers. Requires you to enable community based access for this agent.

SNMPv3 does not use community names. Instead, it encrypts user names and passwords in its PDUs.

When you use SNMPv1 or v2, there are two community names that are needed when the WebLogic SNMP agent and SNMP managers interact:

- The name that you specify in this community prefix. All SNMP managers must send this name when connecting to this SNMP agent.
- The community name that the SNMP manager defines. The SNMP agent must send this name when connecting to the manager. (You supply this community name when you configure a trap destination.)

In addition to using the community prefix as a password, an SNMP agent on an Administration Server uses the prefix to qualify requests from SNMP managers. Because the Administration Server can access data for all WebLogic Server instances in a domain, a request that specifies only an attribute name is potentially ambiguous. For example, the attribute `serverUptime` exists for each WebLogic Server instance in a domain. To clarify requests that you send to SNMP agents on Administration Servers, use the community prefix as follows:

- To request the value of an attribute on a specific Managed Server, when you send a request from an SNMP manager, append the name of the server instance to the community prefix: `community_prefix@server_name`
- To request the value of an attribute for all server instances in a domain, send a community name with the following form: `community_prefix`

To secure access to the values of the WebLogic attributes when using the SNMPv1 or v2 protocols, it is recommended that you set community prefix to a value other than `public`

You cannot specify a null (empty) value for the community prefix. If you delete the prefix value, WebLogic Server resets the value to `public`. If you do not want this agent

to receive SNMPv1 or v2 requests, instead of trying to set the community prefix to a null value, disable community based access. With community based access disabled, WebLogic Server ignores the community prefix value.

Type: string

Constraints: Has Recommended Secure Value: A unique value, should not be public or private, Has Default Value: public, Legal Null: true

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

enabled

Specifies whether this SNMP agent is enabled.

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

informEnabled

Configures this SNMP agent to send notifications as an INFORM instead of a TRAP. Requires you to specify the agent's SNMPTrapVersion as SNMPv2 or SNMPv3.

When an agent sends an INFORM notification, it waits for a confirmation response from the SNMP manager. If it does not receive a response, it resends the INFORM notification.

Type: boolean

Constraints: Has Default Value: false

informRetryInterval

The number of milliseconds that this SNMP agent will wait for a response to an INFORM notification.

If the agent does not receive a response within the specified interval, it will resend the notification.

Type: integer/int32

Constraints: Has Default Value: 10000, Minimum Value: 3000, Maximum Value: 30000

listenAddress

The listen address on which you want this SNMP agent to listen for incoming requests from SNMP managers that use the UDP protocol.

If not specified the Server's ListenAddress is used as the ListenAddress for the SNMPAgent.

Type: string

localizedKeyCacheInvalidationInterval

The number of milliseconds after which WebLogic Server invalidates its cache of SNMP security keys. Setting a high value creates a risk that users whose credentials have been removed can still access SNMP data.

An SNMP security key is an encrypted version of an SNMP agent's engine ID and an authentication password or privacy password. WebLogic Server generates one security key for each entry that you create in the SNMP credential map. When a WebLogic Server SNMP agent receives an SNMPv3 request, it compares the key that is in the request with its WebLogic Server keys. If it finds a match, it processes the request. The SNMP agent also encodes these keys in its responses and notifications. (You configure which keys are encoded when you create a trap destination.)

Instead of regenerating the keys for each SNMPv3 communication, WebLogic Server caches the keys. To make sure that the cache contains the latest set of SNMP credentials, WebLogic Server periodically invalidates the cache. After the cache is invalidated, the next time an SNMP agent requests credentials, WebLogic Server regenerates the cache.

Note that making a change to the credential map does not automatically update the cache. Instead, the cache is updated only after it has been invalidated.

For example, if you update a privacy password in an existing entry in the SNMP credential map, the SNMP agent is not aware of the new password until the key cache is invalidated and regenerated. An SNMP user with the old security password can still access WebLogic Server data until the cache is invalidated.

You can invalidate a key immediately instead of waiting for this invalidation interval to expire.

Type: integer/int64

Constraints: Has Default Value: 3600000, Maximum Value: 86400000

masterAgentXPort

The port that this SNMP agent uses to communicate with its subagents.

The agent uses subagents to provide access to custom MBeans (MBeans that you create and register) and to other software components. WebLogic Server SNMP agents do not enable users to register their own subagents.

Type: integer/int32

Constraints: Has Default Value: 705, Minimum Value: 1, Maximum Value: 65535

maxInformRetryCount

The maximum number of times that this SNMP agent will resend INFORM notifications for which it has not received a response.

Type: integer/int32

Constraints: Has Default Value: 1, Minimum Value: 1, Maximum Value: 3

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

Name=user-specified-name

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

privacyProtocol

The protocol that this SNMP agent uses to encrypt and unencrypt messages. Applicable only with SNMPv3. Requires you to also use an authentication protocol.

To use this protocol when sending responses or notifications, you must also configure the security level of your trap destinations.

If you do not choose a privacy protocol, then communication between this agent and managers can be viewed (but not altered) by unauthorized users.

Type: string

Constraints: Has Default Value: noPriv, Legal Values: noPriv, DES, AES_128, Legal Null: true

sendAutomaticTrapsEnabled

Specifies whether this SNMP agent sends automatically generated notifications to SNMP managers.

The SNMP agent generates automatic notifications when any of the following events occur:

- The WebLogic Server instance that is hosting the SNMP agent starts.
This type of notification (`coldStart`) has no variable bindings.
- A server instance starts or stops.
An SNMP agent on a Managed Server generates these notifications only when its host Managed Server starts or stops. An SNMP agent on an Administration Server generates these notifications when any server in the domain starts or stops.
These notification types (`serverStart` and `serverShutdown`) contain variable bindings to identify the server that started or stopped and the time at which the notification was generated.

Type: boolean

Constraints: Has Default Value: true

tags

Return all tags on this Configuration MBean

Type: array of string

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.SNMPAttributeChangeMBean

This class describes the settings to receive MBean-attribute change notification.

The properties of the `weblogic.management.configuration.SNMPAttributeChangeMBean` entity are as follows:

attributeMBeanName

The name of the MBean instance that you want to monitor. If you leave the name undefined, WebLogic Server monitors all instances of the MBean type that you specify in Monitored MBean Type.

Do not enter the full JMX object name of the MBean instance. Instead, enter only the value that you provided when you created the instance. To create unique MBean object names, WebLogic Server encodes several name-value pairs into each object name. One of these pairs is `Name=name`, and this is the value that you enter for MBean Name. For example:

```
"MedRec:Name=MedRecServer
Type=ServerRuntime"
```

In the previous example, specify `MedRecServer` as the name of the MBean instance.

Type: string

attributeMBeanType

The MBean type that defines the attribute you want to monitor. Do not include the MBean suffix. For example, specify `Server` to monitor a `ServerMBean`.

WebLogic Server does not support using Attribute Change notifications to monitor run-time attributes. Runtime MBeans always include the word `Runtime` in their names. For example, the `ServerRuntime` MBean provides access to runtime attributes while the `Server` MBean provides access to configuration attributes. To monitor changes in an MBean that includes `Runtime` in its name, use a String Monitor, Gauge Monitor, or Counter Monitor.

Type: string

attributeName

The name of the attribute that you want to monitor. This attribute must be in the WebLogic Server MIB.

Type: string

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to `config.xml`

Type: boolean

Constraints: Read Only, Has Default Value: false

enabledServers

This attribute is applicable only when the SNMP Agent is running on the Admin Server of a WebLogic Domain. The `EnabledServers` attribute allows the users to limit the scope of the monitored data sources to the specific named Servers. The `EnabledServers` list is ignored when the `SNMMAgentDeploymentMBean` is targeted to a Managed Server. In the case of a Managed Server the SNMP Agent only looks at the data available in the WebLogic Server where the SNMP Agent is deployed.

For traps based on MBean attributes the SNMP Agent refers to the Domain Runtime MBean Server when it is running on the Admin Server and the Runtime MBean Server when it is deployed to a Managed Server.

In the case of `SNMPJMXMonitorMBean` and `SNMPAttributeChangeMBean` the `MonitoredMBeanType` and `MonitoredMBeanName` attributes specify the type and name of a WebLogic Server MBean for which the trap will be setup. MBeans that meet the Type and Name criteria are qualified to set the trap on. The `EnabledServers` attribute allows a user to specify additional criteria based on the Location of an MBean when the SNMP Agent is targeted to the Admin Server. MBeans whose Location matches one of the Servers in the `EnabledServers` list are considered eligible for the trap to be generated for a corresponding JMX notification. When the `EnabledServers` attribute is not specified all MBeans whose Type and Name match are considered as valid sources for the SNMP trap.

In the case of `SNMPLogFilterMBean` the `EnabledServers` attribute allows a user to specify the Servers in the Domain whose log messages will be monitored when the Agent is running on the Admin Server. When `EnabledServers` is not specified for an Agent running on the Admin Server log messages on all Managed Servers in the domain are monitored for sending traps. This attribute is not applicable when the SNMP Agent is targeted to a Managed Server, in this case the traps are sent based on log messages generated by the respective Managed Server where the Agent is deployed.

Type: array of `weblogic.management.configuration.ServerMBean` references

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

`Name=user-specified-name`

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`.

Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

tags

Return all tags on this Configuration MBean

Type: array of string

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.SNMPCounterMonitorMBean

This class describes the criteria for a Counter-based Monitor. A notification will be generated when this criteria is satisfied.

The properties of the weblogic.management.configuration.SNMPCounterMonitorMBean entity are as follows:

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

enabledServers

This attribute is applicable only when the SNMP Agent is running on the Admin Server of a WebLogic Domain. The EnabledServers attribute allows the users to limit the scope of the monitored data sources to the specific named Servers. The EnabledServers list is ignored when the SNMAgentDeploymentMBean is targeted to a Managed Server. In the case of a Managed Server the SNMP Agent only looks at the data available in the WebLogic Server where the SNMP Agent is deployed.

For traps based on MBean attributes the SNMP Agent refers to the Domain Runtime MBean Server when it is running on the Admin Server and the Runtime MBean Server when it is deployed to a Managed Server.

In the case of `SNMPJMXMonitorMBean` and `SNMPAttributeChangeMBean` the `MonitoredMBeanType` and `MonitoredMBeanName` attributes specify the type and name of a WebLogic Server MBean for which the trap will be setup. MBeans that meet the Type and Name criteria are qualified to set the trap on. The EnabledServers attribute allows a user to specify additional criteria based on the Location of an MBean when the SNMP Agent is targeted to the Admin Server. MBeans whose Location matches one of the Servers in the EnabledServers list are considered eligible for the trap to be generated for a corresponding JMX notification. When the EnabledServers attribute is not specified all MBeans whose Type and Name match are considered as valid sources for the SNMP trap.

In the case of `SNMPLogFilterMBean` the EnabledServers attribute allows a user to specify the Servers in the Domain whose log messages will be monitored when the Agent is running on the Admin Server. When EnabledServers is not specified for an Agent running on the Admin Server log messages on all Managed Servers in the domain are monitored for sending traps. This attribute is not applicable when the SNMP Agent is targeted to a Managed Server, in this case the traps are sent based on log messages generated by the respective Managed Server where the Agent is deployed.

Type: array of weblogic.management.configuration.ServerMBean references

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

modulus

A value to be subtracted from the threshold value when the threshold value is crossed.

If Modulus is 0, a notification is generated each time the agent polls the monitored attribute and its value still exceeds or equals the threshold value.

If Modulus is larger than 0, the value of the modulus is subtracted from the threshold each time the threshold is crossed.

Type: integer/int64

Constraints: Minimum Value: 0

monitoredAttributeName

The name of an MBean attribute to monitor. This attribute must be in the WebLogic Server MIB.

Type: string

monitoredMBeanName

The name of the MBean instance that you want to monitor. If you leave the name undefined, WebLogic Server monitors all instances of the MBean type that you specify in Monitored MBean Type.

If you target SNMP agents to individual Managed Servers, make sure that the MBean instance you specify is active on the Managed Servers you have targeted. For example, if you specify `MServer1` as the name of a `ServerRuntimeMBean` instance, this monitor will only function if you target an SNMP agent either to the Administration Server or to a Managed Server named `MServer1`.

Do not enter the full JMX object name of the MBean instance. Instead, enter only the value of the object name's `Name=name` name-value pair. To create unique MBean object names, WebLogic Server encodes several name-value pairs into each object name. One of these pairs is `Name=name`. For example:

```
"MedRec:Name=MedRecServer
```

```
Type=ServerRuntime"
```

In the previous example, specify `MedRecServer` as the name of the MBean instance.

Type: string

monitoredMBeanType

The MBean type that defines the attribute you want to monitor. Do not include the MBean suffix. For example, `ServerRuntime`

Type: string

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

```
Name=user-specified-name
```

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

offset

A value to be added to the threshold value each time the observed value equals or exceeds the threshold.

Type: integer/int64

Constraints: Minimum Value: 0

pollingInterval

The frequency (in seconds) that WebLogic Server checks the attribute value.

Type: integer/int32

Constraints: Has Default Value: 10, Minimum Value: 1, Maximum Value: 65535

tags

Return all tags on this Configuration MBean

Type: array of string

threshold

Specifies a value that triggers the Counter Monitor to generate a notification.

The monitor generates a notification the first time the observed value transitions from below the threshold to at or above the threshold. While the observed value remains at or above the threshold, the Counter Monitor does not generate additional notifications. If the observed value falls below the threshold and then later equals or exceeds the threshold, the SNMP Counter Monitor will generate a notification every time the threshold is crossed.

You can specify an offset value to cause this threshold value to increase each time the observed value equals or exceeds the threshold. The first time the observed value equals or exceeds the new threshold value, this monitor generates a notification and adds the offset value to the new threshold value.

For example, if you set Threshold to 1000 and Offset to 2000, when the observed attribute equals or exceeds 1000, the Counter Monitor sends a notification and increases the threshold to 3000. When the observed attribute equals or exceeds 3000, the Counter Monitor sends a notification and increases the threshold again to 5000.

Type: integer/int64

Constraints: Minimum Value: 0

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.SNMPGaugeMonitorMBean

This class describes the criteria for a Gauge-based Monitor. A notification will be generated when this criteria is satisfied.

The properties of the `weblogic.management.configuration.SNMPGaugeMonitorMBean` entity are as follows:

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to `config.xml`

Type: boolean

Constraints: Read Only, Has Default Value: false

enabledServers

This attribute is applicable only when the SNMP Agent is running on the Admin Server of a WebLogic Domain. The `EnabledServers` attribute allows the users to limit the scope of the monitored data sources to the specific named Servers. The `EnabledServers` list is ignored when the `SNMMAgentDeploymentMBean` is targeted to a Managed Server. In the case of a Managed Server the SNMP Agent only looks at the data available in the WebLogic Server where the SNMP Agent is deployed.

For traps based on MBean attributes the SNMP Agent refers to the Domain Runtime MBean Server when it is running on the Admin Server and the Runtime MBean Server when it is deployed to a Managed Server.

In the case of `SNMPJMXMonitorMBean` and `SNMPAttributeChangeMBean` the `MonitoredMBeanType` and `MonitoredMBeanName` attributes specify the type and name of a WebLogic Server MBean for which the trap will be setup. MBeans that meet the Type and Name criteria are qualified to set the trap on. The `EnabledServers` attribute allows a user to specify additional criteria based on the Location of an MBean when the SNMP Agent is targeted to the Admin Server. MBeans whose Location matches one of the Servers in the `EnabledServers` list are considered eligible for the trap to be generated for a corresponding JMX notification. When the `EnabledServers` attribute is not specified all MBeans whose Type and Name match are considered as valid sources for the SNMP trap.

In the case of `SNMPLogFilterMBean` the `EnabledServers` attribute allows a user to specify the Servers in the Domain whose log messages will be monitored when the Agent is running on the Admin Server. When `EnabledServers` is not specified for an Agent running on the Admin Server log messages on all Managed Servers in the domain are monitored for sending traps. This attribute is not applicable when the SNMP Agent is targeted to a Managed Server, in this case the traps are sent based on log messages generated by the respective Managed Server where the Agent is deployed.

Type: array of `weblogic.management.configuration.ServerMBean` references

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

monitoredAttributeName

The name of an MBean attribute to monitor. This attribute must be in the WebLogic Server MIB.

Type: string

monitoredMBeanName

The name of the MBean instance that you want to monitor. If you leave the name undefined, WebLogic Server monitors all instances of the MBean type that you specify in Monitored MBean Type.

If you target SNMP agents to individual Managed Servers, make sure that the MBean instance you specify is active on the Managed Servers you have targeted. For example, if you specify `MServer1` as the name of a `ServerRuntimeMBean` instance, this monitor will only function if you target an SNMP agent either to the Administration Server or to a Managed Server named `MServer1`.

Do not enter the full JMX object name of the MBean instance. Instead, enter only the value of the object name's `Name=name` name-value pair. To create unique MBean object names, WebLogic Server encodes several name-value pairs into each object name. One of these pairs is `Name=name`. For example:

```
"MedRec:Name=MedRecServer
Type=ServerRuntime"
```

In the previous example, specify `MedRecServer` as the name of the MBean instance.

Type: string

monitoredMBeanType

The MBean type that defines the attribute you want to monitor. Do not include the MBean suffix. For example, `ServerRuntime`.

Type: string

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

```
Name=user-specified-name
```

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

pollingInterval

The frequency (in seconds) that WebLogic Server checks the attribute value.

Type: integer/int32

Constraints: Has Default Value: 10, Minimum Value: 1, Maximum Value: 65535

tags

Return all tags on this Configuration MBean

Type: array of string

thresholdHigh

The high threshold at which a notification should be generated. A notification is generated the first time the monitored value is equal to or greater than this value.

Subsequent crossings of the high threshold value do not cause additional notifications unless the attribute value becomes equal to or less than the low threshold value.

Type: number/double

thresholdLow

The low threshold at which a notification should be generated. A notification is generated the first time the monitored value is less than or equal to this value.

Subsequent crossings of the low threshold value do not cause additional notifications unless the attribute value becomes equal to or greater than the high threshold value.

Type: number/double

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.SNMPLogFilterMBean

This MBean represents a filter to qualify log messages which are logged to the server logfile. A message must qualify criteria specified as a filter in order to generate a notification. Multiple instances of this MBean can be defined, if needed. If there are multiple instances, a message must qualify atleast one filter to qualify for the server logfile.

The properties of the weblogic.management.configuration.SNMPLogFilterMBean entity are as follows:

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

enabledServers

This attribute is applicable only when the SNMP Agent is running on the Admin Server of a WebLogic Domain. The EnabledServers attribute allows the users to limit the scope of the monitored data sources to the specific named Servers. The EnabledServers list is ignored when the SNMMAgentDeploymentMBean is targeted to a Managed Server. In the case of a Managed Server the SNMP Agent only looks at the data available in the WebLogic Server where the SNMP Agent is deployed.

For traps based on MBean attributes the SNMP Agent refers to the Domain Runtime MBean Server when it is running on the Admin Server and the Runtime MBean Server when it is deployed to a Managed Server.

In the case of SNMPJMXMonitorMBean and SNMPAttributeChangeMBean the MonitoredMBeanType and MonitoredMBeanName attributes specify the type and name of a WebLogic Server MBean for which the trap will be setup. MBeans that meet the Type and Name criteria are qualified to set the trap on. The EnabledServers attribute allows a user to specify additional criteria based on the Location of an MBean when the SNMP Agent is targeted to the Admin Server. MBeans whose Location matches one of

the Servers in the EnabledServers list are considered eligible for the trap to be generated for a corresponding JMX notification. When the EnabledServers attribute is not specified all MBeans whose Type and Name match are considered as valid sources for the SNMP trap.

In the case of `SNMPLogFilterMBean` the EnabledServers attribute allows a user to specify the Servers in the Domain whose log messages will be monitored when the Agent is running on the Admin Server. When EnabledServers is not specified for an Agent running on the Admin Server log messages on all Managed Servers in the domain are monitored for sending traps. This attribute is not applicable when the SNMP Agent is targeted to a Managed Server, in this case the traps are sent based on log messages generated by the respective Managed Server where the Agent is deployed.

Type: array of `weblogic.management.configuration.ServerMBean` references

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

messageIds

A list of message IDs or ID ranges that cause a WebLogic Server SNMP agent to generate a notification.

If no IDs are specified, this filter selects all message IDs.

Example list: 20,50-100,300

Type: array of string

messageSubstring

A string that is searched for in the message text. Only messages that contain the string are selected. If a string is not specified, all messages are selected.

Type: string

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

Name=user-specified-name

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

severityLevel

The minimum severity of a message that causes a WebLogic Server SNMP agent to generate a notification.

Type: string

Constraints: Has Default Value: Notice

subsystemNames

A list of subsystems whose messages are selected by this log filter. If none are specified, messages from all subsystems are selected.

Type: array of string

tags

Return all tags on this Configuration MBean

Type: array of string

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

userIds

A list of user IDs that causes a WebLogic Server SNMP agent to generate a notification.

Every message includes the user ID from the security context in which the message was generated.

If the user ID field for a message matches one of the user IDs you specify in the filter, WebLogic Server generates a notification.

If this log filter doesn't specify user IDs, WebLogic Server can generate a notification for messages from all user IDs.

Type: array of string

weblogic.management.configuration.SNMPProxyMBean

This MBean represents an SNMP agent that is proxied by a WebLogic Server SNMP agent.

The properties of the weblogic.management.configuration.SNMPProxyMBean entity are as follows:

community

The community name to be passed on for all SNMPv1 requests to this proxied SNMP agent.

If you specify a *security name* for this proxied agent, the WebLogic SNMP agent ignores this community name. Instead, the agent encodes the security name in an SNMPv3 request and forwards the SNMPv3 request to this proxied agent.

Type: string

Constraints: Has Secure Value: null, Has Default Value: public

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

listenAddress

The address on which the external SNMP agent for which the WebLogic SNMP Agent is acting as a proxy is listening for incoming requests from SNMP managers that use the UDP protocol.

If not specified the Server's ListenAddress is used as the ListenAddress of the external SNMPAgent.

Type: string

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

Name=user-specified-name

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

oidRoot

The root of the object identifier (OID) tree that this proxied SNMP agent controls.

Type: string

port

The port number on which this proxied SNMP agent is listening.

Type: integer/int32

Constraints: Minimum Value: 0, Maximum Value: 65535

securityLevel

The security level that the proxied SNMP agent expects for the specified security name.

Type: string

Constraints: Has Default Value: noAuthNoPriv, Has Production Mode Default Value: authNoPriv, Legal Values: noAuthNoPriv, authNoPriv, authPriv, Legal Null: true

securityName

The user name on whose behalf the WebLogic SNMP agent forwards v3 requests. If not specified, the request is forwarded as a v1 request.

If you specify a security name, you must also specify a security level that is equal to or lower than the security level that is configured for communication between the WebLogic SNMP agent and SNMP managers. For example, if the WebLogic SNMP agent requires incoming SNMPv3 requests to use the authentication protocol but no privacy protocol, the security level for this proxy must be either Authentication Only or None. Note that if you want to use the authorization or privacy protocols, you must configure credential mapping in the WebLogic Server security realm.

The WebLogic SNMP agent cannot forward or pass through the credentials that are contained in SNMPv3 requests from SNMP managers. Instead, the agent authenticates and performs other security operations on incoming requests, and then constructs a new request to forward to a proxied agent.

Type: string

Constraints: Legal Null: true

tags

Return all tags on this Configuration MBean

Type: array of string

timeout

The number of milliseconds that the WebLogic Server SNMP agent waits for a response to requests that it forwards to this proxy agent.

If the interval elapses without a response, the WebLogic SNMP agent sends an error to the requesting manager.

Type: integer/int64

Constraints: Has Default Value: 5000, Minimum Value: 0

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.SNMPStringMonitorMBean

This class describes the criteria for a String-based Monitor. A notification is generated when this criteria is satisfied.

The properties of the weblogic.management.configuration.SNMPStringMonitorMBean entity are as follows:

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

enabledServers

This attribute is applicable only when the SNMP Agent is running on the Admin Server of a WebLogic Domain. The EnabledServers attribute allows the users to limit

the scope of the monitored data sources to the specific named Servers. The EnabledServers list is ignored when the SNMMAgentDeploymentMBean is targeted to a Managed Server. In the case of a Managed Server the SNMP Agent only looks at the data available in the WebLogic Server where the SNMP Agent is deployed.

For traps based on MBean attributes the SNMP Agent refers to the Domain Runtime MBean Server when it is running on the Admin Server and the Runtime MBean Server when it is deployed to a Managed Server.

In the case of `SNMPJMXMonitorMBean` and `SNMPAttributeChangeMBean` the `MonitoredMBeanType` and `MonitoredMBeanName` attributes specify the type and name of a WebLogic Server MBean for which the trap will be setup. MBeans that meet the Type and Name criteria are qualified to set the trap on. The EnabledServers attribute allows a user to specify additional criteria based on the Location of an MBean when the SNMP Agent is targeted to the Admin Server. MBeans whose Location matches one of the Servers in the EnabledServers list are considered eligible for the trap to be generated for a corresponding JMX notification. When the EnabledServers attribute is not specified all MBeans whose Type and Name match are considered as valid sources for the SNMP trap.

In the case of `SNMPLogFilterMBean` the EnabledServers attribute allows a user to specify the Servers in the Domain whose log messages will be monitored when the Agent is running on the Admin Server. When EnabledServers is not specified for an Agent running on the Admin Server log messages on all Managed Servers in the domain are monitored for sending traps. This attribute is not applicable when the SNMP Agent is targeted to a Managed Server, in this case the traps are sent based on log messages generated by the respective Managed Server where the Agent is deployed.

Type: array of `weblogic.management.configuration.ServerMBean` references

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

monitoredAttributeName

The name of an MBean attribute to monitor. This attribute must be in the WebLogic Server MIB.

Type: string

monitoredMBeanName

The name of the MBean instance that you want to monitor. If you leave the name undefined, WebLogic Server monitors all instances of the MBean type that you specify in Monitored MBean Type.

If you target SNMP agents to individual Managed Servers, make sure that the MBean instance you specify is active on the Managed Servers you have targeted. For example, if you specify `MServer1` as the name of a `ServerRuntimeMBean` instance, this monitor will only function if you target an SNMP agent either to the Administration Server or to a Managed Server named `MServer1`.

Do not enter the full JMX object name of the MBean instance. Instead, enter only the value of the object name's `Name=name` name-value pair. To create unique MBean object names, WebLogic Server encodes several name-value pairs into each object name. One of these pairs is `Name=name`. For example:

```
"MedRec:Name=MedRecServer
```

Type=ServerRuntime"

In the previous example, specify `MedRecServer` as the name of the MBean instance.

Type: string

monitoredMBeanType

The MBean type that defines the attribute you want to monitor. Do not include the MBean suffix. For example, `ServerRuntime`

Type: string

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's

`javax.management.ObjectName`

`Name=user-specified-name`

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`.

Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

notifyDiffer

Generates a notification if the value of the monitored attribute and the value of String to Compare are different.

Type: boolean

Constraints: Has Default Value: false

notifyMatch

Generates a notification if the value of the monitored attribute and the value of String to Compare are the same.

Type: boolean

Constraints: Has Default Value: false

pollingInterval

The frequency (in seconds) that WebLogic Server checks the attribute value.

Type: integer/int32

Constraints: Has Default Value: 10, Minimum Value: 1, Maximum Value: 65535

stringToCompare

The string against which the value of the monitored attribute will be compared.

A notification is generated when the criteria specified by Notify Match or Notify Differ is satisfied.

Type: string

tags

Return all tags on this Configuration MBean

Type: array of string

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.SNMPTrapDestinationMBean

This MBean describes a destination to which an SNMP agent sends SNMP TRAP and INFORM notifications.

The properties of the weblogic.management.configuration.SNMPTrapDestinationMBean entity are as follows:

community

The password (community name) that a WebLogic Server SNMP agent sends to the SNMP manager when the agent generates SNMPv1 or SNMPv2 notifications.

The community name that you enter in this trap destination must match the name that the SNMP manager defines.

Type: string

Constraints: Has Secure Value: null, Has Default Value: public

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

host

The DNS name or IP address of the computer on which the SNMP manager is running.

The WebLogic SNMP agent sends trap notifications to the host and port that you specify.

Type: string

Constraints: Has Recommended Secure Value: 127.0.0.1 or ::1, Has Default Value: localhost

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

`Name=user-specified-name`

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

port

The UDP port on which the SNMP manager is listening.

Type: integer/int32

Constraints: Has Default Value: 162, Minimum Value: 1, Maximum Value: 65535

securityLevel

Specifies the security protocols that the SNMP agent uses when sending SNMPv3 responses or notifications to the SNMP manager that this trap destination represents. Requires you to specify a security name for this trap destination.

Type: string

Constraints: Has Default Value: noAuthNoPriv, Has Production Mode Default Value: authNoPriv, Legal Values: noAuthNoPriv, authNoPriv, authPriv, Legal Null: true

securityName

Specifies the user name that the WebLogic Server SNMP agent encodes into SNMPv3 responses or notifications. Requires you to create a credential map for this user name in the WebLogic Server security realm.

The credential map contains an authentication password and an optional privacy password for this user.

The user name and passwords must match the credentials required by the SNMP manager that this trap destination represents.

Type: string

tags

Return all tags on this Configuration MBean

Type: array of string

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.SSLMBean

This MBean represents the configuration of the SSL protocol.

The properties of the weblogic.management.configuration.SSLMBean entity are as follows:

JSSEEnabled

Determines whether the SSL implementation in Weblogic Server is JSSE based.

Type: boolean

Constraints: Has Default Value: true

SSLRejectionLoggingEnabled

Indicates whether warning messages are logged in the server log when SSL connections are rejected.

Type: boolean

Constraints: Has Default Value: true

SSLv2HelloEnabled

Indicate whether SSLv2Hello is enabled

Type: boolean

Constraints: Has Default Value: true

acceptKSSDemoCertsEnabled

Type: boolean

Constraints: Has Default Value: true

allowUnencryptedNullCipher

Test if the AllowUnEncryptedNullCipher is enabled

see `setAllowUnencryptedNullCipher(boolean enable)` for the NullCipher feature.

Type: boolean

Constraints: Has Default Value: false

ciphersuites

Indicates the cipher suites being used on a particular WebLogic Server.

The strongest negotiated cipher suite is chosen during the SSL handshake. The set of cipher suites used by default by JSEE depends on the specific JDK version with which WebLogic Server is configured.

For a list of possible values, see Cipher Suites

Type: array of string

clientCertAlias

Determines the alias of the client SSL certificate to be used as identity for outbound SSL connections. The certificate is assumed to be stored in the server configured keystore.

Note that to use the client SSL certificate, `setUseClientCertForOutbound` must be enabled.

Type: string

Constraints: Has Default Value: null

clientCertPrivateKeyPassPhrase

The passphrase used to retrieve the private key for the client SSL certificate specified in `getClientCertAlias` from the server configured keystore. This passphrase is assigned to the private key when the private key is generated.

Note that this attribute is usually used when outbound SSL connections specify a client SSL certificate identity.

Note that when you get the value of this attribute, WebLogic Server does the following:

1. Retrieves the value of the `ClientCertPrivateKeyPassPhraseEncrypted` attribute.
2. Decrypts the value and returns the unencrypted passphrase.

Type: string

Constraints: Encrypted, Has Default Value: null

clientCertificateEnforced

Indicates whether or not clients must present digital certificates from a trusted certificate authority to WebLogic Server.

Type: boolean

Constraints: Has Recommended Secure Value: true, Has Default Value: false

clientInitSecureRenegotiationAccepted

Indicate whether TLS client initiated secure renegotiation is accepted.

Type: boolean

Constraints: Has Default Value: false

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to `config.xml`

Type: boolean

Constraints: Read Only, Has Default Value: false

enabled

Indicates whether the server can be reached through the default SSL listen port.

If the administration port is enabled for the WebLogic Server domain, then administrative traffic travels over the administration port and application traffic travels over the Listen Port and SSL Listen Port. If the administration port is disabled, then all traffic travels over the Listen Port and SSL Listen Port.

Type: boolean

Constraints: Has Secure Value: true, Has Default Value: false

exportKeyLifespan

Indicates the number of times WebLogic Server can use an exportable key between a domestic server and an exportable client before generating a new key. The more secure you want WebLogic Server to be, the fewer times the key should be used before generating a new key.

Type: integer/int32

Constraints: Has Default Value: 500, Minimum Value: 1, Maximum Value: 2147483647

hostnameVerificationIgnored

Specifies whether to ignore the installed implementation of the `weblogic.security.SSL.HostnameVerifier` interface (when this server is acting as a client to another application server).

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

hostnameVerifier

The name of the class that implements the `weblogic.security.SSL.HostnameVerifier` interface.

This class verifies whether the connection to the host with the hostname from URL should be allowed. The class is used to prevent man-in-the-middle attacks. The `weblogic.security.SSL.HostnameVerifier` has a `verify()` method that WebLogic Server calls on the client during the SSL handshake.

Type: string

Constraints: Has Default Value: null

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

identityAndTrustLocations

Indicates where SSL should find the server's identity (certificate and private key) as well as the server's trust (trusted CAs).

- If set to `KEYSTORES`, then SSL retrieves the identity and trust from the server's keystores (that are configured on the Server).
- If set to `FILES_OR_KEYSTORE_PROVIDERS`, then SSL first looks in the deprecated KeyStore providers for the identity and trust. If not found, then it looks in the flat files indicated by the SSL Trusted CA File Name, Server Certificate File Name, and Server Key File Name attributes.

Domains created in WebLogic Server version 8.1 or later, default to `KEYSTORES`.

Domains created before WebLogic Server version 8.1, default to `FILES_OR_KEYSTORE_PROVIDERS`.

Type: string

Constraints: Has Default Value: KeyStores, Legal Values: KeyStores, FilesOrKeyStoreProviders

inboundCertificateValidation

Indicates the client certificate validation rules for inbound SSL.

This attribute only applies to ports and network channels using 2-way SSL.

Type: string

Constraints: Has Default Value: BuiltinSSLValidationOnly, Legal Values: BuiltinSSLValidationOnly, BuiltinSSLValidationAndCertPathValidators

listenPort

The TCP/IP port at which this server listens for SSL connection requests.

Type: integer/int32

Constraints: Has Default Value: 7002, Minimum Value: 1, Maximum Value: 65535

loginTimeoutMillis

Specifies the number of milliseconds that WebLogic Server waits for an SSL connection before timing out. SSL connections take longer to negotiate than regular connections.

If clients are connecting over the Internet, raise the default number to accommodate additional network latency.

Type: integer/int32

Constraints: Has Default Value: 25000, Minimum Value: 1, Maximum Value: 2147483647

minimumTLSProtocolVersion

Get the minimum SSL/TLS protocol version currently configured.

Type: string

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

Name=user-specified-name

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

outboundCertificateValidation

Indicates the server certificate validation rules for outbound SSL.

This attribute always applies to outbound SSL that is part of WebLogic Server (that is, an Administration Server talking to the Node Manager). It does not apply to application code in the server that is using outbound SSL unless the application code uses a `weblogic.security.SSL.ServerTrustManager` that is configured to use outbound SSL validation.

Type: string

Constraints: Has Default Value: `BuiltinSSLValidationOnly`, Legal Values: `BuiltinSSLValidationOnly`, `BuiltinSSLValidationAndCertPathValidators`

outboundPrivateKeyAlias

The string alias used to store and retrieve the outbound private key in the keystore. This private key is associated with either a server or a client digital certificate. This attribute value is derived from other settings and cannot be physically set.

The returned value is determined as follows:

- If the `isUseClientCertForOutbound` returns true, the value from `getClientCertAlias` is returned.
- Otherwise, the value from `getServerPrivateKeyAlias` is returned.

Type: string

Constraints: Read Only, Has Default Value: null

outboundPrivateKeyPassPhrase

The passphrase used to retrieve the outbound private key from the keystore. This passphrase is assigned to the private key when it is generated. This attribute value is derived from other settings and cannot be physically set.

The returned value is determined as follows:

- If the `isUseClientCertForOutbound` returns true, the value from `getClientCertPrivateKeyPassPhrase` is returned.
- Otherwise, the value from `getServerPrivateKeyPassPhrase` is returned.

Type: string

Constraints: Read Only, Encrypted, Has Default Value: null

serverPrivateKeyAlias

The string alias used to store and retrieve the server's private key in the keystore. This private key is associated with the server's digital certificate.

Type: string

Constraints: Has Default Value: null

serverPrivateKeyPassPhrase

The passphrase used to retrieve the server's private key from the keystore. This passphrase is assigned to the private key when it is generated.

Type: string

Constraints: Encrypted

tags

Return all tags on this Configuration MBean

Type: array of string

twoWaySSLEnabled

The form of SSL that should be used.

By default, WebLogic Server is configured to use one-way SSL (implied by the `Client Certs Not Requested` value). Selecting `Client Certs Requested But Not Enforced` enables two-way SSL. With this option, the server requests a certificate from the client, but the connection continues if the client does not present a certificate. Selecting `Client Certs Requested And Enforced` also enables two-way SSL and requires a client to present a certificate. However, if a certificate is not presented, the SSL connection is terminated.

Type: boolean

Constraints: Has Recommended Secure Value: true, Has Default Value: false

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

useClientCertForOutbound

Determines whether to use the configured client SSL certificate as identity for outbound SSL connections.

Note that to use a client SSL certificate, one must be specified in `setClientCertAlias`

Type: boolean

Constraints: Has Default Value: false

useServerCerts

Sets whether the client should use the server certificates/key as the client identity when initiating an outbound connection over https.

Type: boolean

Constraints: Has Default Value: false

weblogic.management.configuration.SecureModeMBean

Controls the behavior of Secure Mode in the current WebLogic Server domain. Attributes control whether secure mode is enabled and control the validation that is performed during startup.

The properties of the `weblogic.management.configuration.SecureModeMBean` entity are as follows:

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to `config.xml`

Type: boolean

Constraints: Read Only, Has Default Value: false

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

Name=user-specified-name

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`.

Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

restrictiveJMXPolicies

Returns whether restrictive policies will be used for JMX authorization.

If secure mode is enabled and restrictive policies are enabled, then the default policies for JMX only allow MBean access to the standard WLS roles (Admin, Deployer, Operator, or Monitor). If changed as part of a non-dynamic activation, then the `ServerSecurityRuntimeMBean.resetDefaultPolicies` method should also be invoked.

Type: boolean

Constraints: Has Default Value: true

secureModeEnabled

Returns whether the domain will run in secure mode.

In secure mode, the configuration defaults are those recommended for securing a domain. The authorization policies for JNDI and MBean access are more restrictive in secure mode. In addition, WLS will validate the domain configuration and log warnings and errors for any insecure settings.

Secure mode requires the domain to be in production mode.

Type: boolean

Constraints: Has Default Value: false

tags

Return all tags on this Configuration MBean

Type: array of string

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

warnOnAuditing

Returns whether warnings should be logged if auditing not enabled.

If secure mode is enabled and warnings are enabled, then messages will be logged if auditing is not enabled.

Type: boolean

Constraints: Has Default Value: true

warnOnInsecureApplications

Returns whether warnings should be logged if applications are not secure.

If secure mode is enabled and warnings are enabled, then messages will be logged for insecure application elements.

Type: boolean

Constraints: Has Default Value: true

warnOnInsecureFileSystem

Returns whether warnings should be logged if the File System is not secure.

If secure mode is enabled and warnings are enabled, then messages will be logged for insecure file system setting.

Type: boolean

Constraints: Has Default Value: true

warnOnInsecureSSL

Returns whether warnings should be logged if the SSL configuration is not secure.

If secure mode is enabled and warnings are enabled, then messages will be logged for insecure SSL configuration settings.

Type: boolean

Constraints: Has Default Value: true

warnOnJavaSecurityManager

Returns whether warnings should be logged if the Java Security Manager is not enabled.

If secure mode is enabled and warning is enabled, then a messages will be logged if the Java Security Manager is not enabled.

Type: boolean

Constraints: Has Default Value: true

weblogic.management.configuration.SecurityConfigurationMBean

Provides domain-wide security configuration information.

The properties of the `weblogic.management.configuration.SecurityConfigurationMBean` entity are as follows:

administrativeIdentityDomain

Domain's administrative identity domain.

Type: string

bootAuthenticationMaxRetryDelay

The maximum length of time, in milliseconds, the boot process will wait before retrying the authentication after a login server not available exception. The boot process will use a backoff algorithm starting at 100 milliseconds increasing on each failure until the delay time reaches the `MaxRetryDelay` value.

Type: integer/int64

Constraints: Has Default Value: 60000

bootAuthenticationRetryCount

The maximum number of times the boot process will try to authenticate the boot user with the authentication providers. The authentication will be retried only if a failure occurs that indicates the login server is not available.

Type: integer/int32

Constraints: Minimum Value: 0

clearTextCredentialAccessEnabled

Returns true if allow access to credential in clear text. This can be overridden by the system property `-Dweblogic.management.clearTextCredentialAccessEnabled`

Type: boolean

Constraints: Has Default Value: false

compatibilityConnectionFiltersEnabled

Specifies whether this WebLogic Server domain enables compatibility with previous connection filters.

This attribute changes the protocols names used when filtering needs to be performed.

Type: boolean

Constraints: Has Default Value: false

connectionFilter

The name of the Java class that implements a connection filter (that is, the `weblogic.security.net.ConnectionFilter` interface). If no class name is specified, no connection filter will be used.

This attribute replaces the deprecated `ConnectionFilter` attribute on the `SecurityMBean`.

Type: string

Constraints: Has Default Value: null

connectionFilterRules

The rules used by any connection filter that implements the `ConnectionFilterRulesListener` interface. When using the default implementation and when no rules are specified, all connections are accepted. The default implementation rules are in the format: `target localAddress localPort action protocols`

This attribute replaces the deprecated `ConnectionFilterRules` attribute on the `SecurityMBean`.

Type: array of string

Constraints: Has Default Value: null

connectionLoggerEnabled

Specifies whether this WebLogic Server domain should log accepted connections.

This attribute can be used by a system administrator to dynamically check the incoming connections in the log file to determine if filtering needs to be performed.

This attribute replaces the deprecated `ConnectionLoggerEnabled` attribute on the `SecurityMBean`.

Type: boolean

Constraints: Has Default Value: false

consoleFullDelegationEnabled

Indicates whether the console is enabled for fully delegate authorization.

Type: boolean

Constraints: Has Default Value: false

credential

The password for the domain. In WebLogic Server version 6.0, this attribute was the password of the system user. In WebLogic Server version 7.0, this attribute can be any

string. For the two domains to interoperate, the string must be the same for both domains.

When you set the value of this attribute, WebLogic Server does the following:

1. Encrypts the value.
2. Sets the value of the `UserPasswordEncrypted` attribute to the encrypted value.

Type: string

Constraints: Encrypted

crossDomainSecurityEnabled

Indicates whether or not cross-domain security is enabled.

Type: boolean

Constraints: Has Default Value: false

defaultRealm

Returns the default security realm or null if no realm has been selected as the default security realm.

Type: weblogic.management.security.RealmMBean reference

Constraints: Restart Required

downgradeUntrustedPrincipals

Whether or not to downgrade to anonymous principals that cannot be verified. This is useful for server-server communication between untrusted domains.

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

enforceStrictURLPattern

Whether or not the system should enforce strict URL pattern or not.

Type: boolean

Constraints: Has Default Value: true

enforceValidBasicAuthCredentials

Whether or not the system should allow requests with invalid Basic Authentication credentials to access unsecure resources.

Type: boolean

Constraints: Has Default Value: true

excludedDomainNames

Specifies a list of remote domains for which cross-domain check should not be applied.

Type: array of string

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

identityDomainAwareProvidersRequired

Returns true if all role mapping, authorization, credential mapping, and audit providers configured in the domain must support the IdentityDomainAwareProviderMBean interface's administrative identity domain.

Type: boolean

Constraints: Has Default Value: false

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

Name=user-specified-name

Type: string

Constraints: Read Only, Legal Null: true

nodeManagerPassword

The password that the Administration Server uses to communicate with Node Manager when starting, stopping, or restarting Managed Servers.

When you get the value of this attribute, WebLogic Server does the following:

1. Retrieves the value of the `NodeManagerPasswordEncrypted` attribute.
2. Decrypts the value and returns the unencrypted password as a String.

When you set the value of this attribute, WebLogic Server does the following:

1. Encrypts the value.
2. Sets the value of the `NodeManagerPasswordEncrypted` attribute to the encrypted value.

Using this attribute (`NodeManagerPassword`) is a potential security risk because the String object (which contains the unencrypted password) remains in the JVM's memory until garbage collection removes it and the memory is reallocated. Depending on how memory is allocated in the JVM, a significant amount of time could pass before this unencrypted data is removed from memory.

Instead of using this attribute, you should use `NodeManagerPasswordEncrypted`

Type: string

Constraints: Encrypted

nodeManagerUsername

The user name that the Administration Server uses to communicate with Node Manager when starting, stopping, or restarting Managed Servers.

Type: string

Constraints: Has Default Value:

nonceTimeoutSeconds

Returns the value of the nonce timeout in seconds.

Type: integer/int32

Constraints: Has Default Value: 120, Minimum Value: 15

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

principalEqualsCaseInsensitive

Specifies whether the WebLogic Server principal name is compared using a case insensitive match when the equals method for the principal object is performed.

If this attribute is enabled, matches are case insensitive.

Note: Note that principal comparison is not used by the WebLogic Security Service to determine access to protected resources. This attribute is intended for use with JAAS authorization, which may require case insensitive principal matching behavior.

Type: boolean

Constraints: Has Default Value: false

principalEqualsCompareDnAndGuid

Specifies whether the GUID and DN data in a WebLogic Server principal object are used when the equals method of that object is invoked.

If enabled, the GUID and DN data (if included among the attributes in a WebLogic Server principal object) and the principal name are compared when this method is invoked.

Type: boolean

Constraints: Has Default Value: false

remoteAnonymousJNDIEnabled

Returns true if remote anonymous JNDI access is permitted for list and modify operations.

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: true

tags

Return all tags on this Configuration MBean

Type: array of string

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

useKSSForDemo

Determines whether the Demo Identity and Demo Trust key stores should be obtained from the Oracle Key Store Service (KSS).

If enabled, Weblogic Server will request the Demo Identity and Domain Trust key stores from KSS. Subsequent to installation however, the KSS Demo key stores may have been manipulated such that appropriate Demo certificates or keys are not available.

Please verify the following KSS Demo Identity keystore has an X.509 private key and corresponding public identity certificate signed by the Demo Certificate Authority (CA):

KSS Stripe

system

KSS Key Store

demoidentity

KSS Private Key Alias

DemoIdentity

Please verify the following KSS Domain Trust keystore has a trusted Demo Certificate Authority X.509 certificate:

KSS Stripe

system

KSS Key Store

trust

Type: boolean

Constraints: Has Default Value: false

webAppFilesCaseInsensitive

This property defines the case sensitive URL-pattern matching behavior for security constraints, servlets, filters, virtual-hosts, and so on, in the Web application container and external security policies. **Note:** This is a Windows-only flag that is provided for backward compatibility when upgrading from pre-9.0 versions of WebLogic Server. On Unix platforms, setting this value to `true` causes undesired behavior and is not supported. When the value is set to `os`, the pattern matching will be case-sensitive on all platforms except the Windows file system. Note that on non-Windows file systems, WebLogic Server does not enforce case sensitivity and relies on the file system for optimization. As a result, if you have a Windows Samba mount from Unix or Mac OS that has been installed in case-insensitive mode, there is a chance of a security risk. If so, specify case-insensitive lookups by setting this attribute to `true`. Note also that this property is used to preserve backward compatibility on Windows file systems only. In prior releases, WebLogic Server was case-insensitive on Windows. As of WebLogic Server 9.0, URL-pattern matching is strictly enforced. During the upgrade of older domains, the value of this parameter is explicitly set to `os` by the upgrade plug-in to preserve backward compatibility.

Type: string

Constraints: Has Default Value: false, Legal Values: `os`, `true`, `false`

weblogic.management.configuration.SelfTuningMBean

SelfTuning MBean contains the global work manager component MBeans.

The properties of the `weblogic.management.configuration.SelfTuningMBean` entity are as follows:

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

Name=user-specified-name

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

partitionFairShare

A desired percentage of thread usage by a partition compared to the thread usage by all partitions. It is recommended that the sum of this value for all the partitions running in a WLS domain add up to 100, but it is not strictly enforced. When they do not add up to 100, WLS assigns thread-usage times to different partitions based on their relative values. This attribute is for use in the global domain only. Use the `PartitionWorkManager` MBean for specifying partition fair share values for partitions.

Type: integer/int32

Constraints: Has Default Value: 50, Minimum Value: 1, Maximum Value: 99

tags

Return all tags on this Configuration MBean

Type: array of string

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.ServerDebugMBean

Defines the debug attributes that are specific to WebLogic Server.

While all attributes will be supported in adherence with the standard WebLogic Server deprecation policies, the resultant debug content is free to change in both form and content across releases.

The properties of the weblogic.management.configuration.ServerDebugMBean entity are as follows:

applicationContainer

Debug Application Container deployment processing

Type: boolean

classChangeNotifier

Gets the fastswap ClassChangeNotifier debug attribute of ServerDebugMBean

Type: boolean

Constraints: Has Secure Value: false

classFinder

Debug ClassFinder processing

Type: boolean

classLoader

Debug ClassLoader processing

Type: boolean

classLoaderVerbose

Detailed debug of ClassLoader processing

Type: boolean

classloaderWebApp

Debug WebApp ClassLoader processing

Type: boolean

classpathServlet

Debug ClassPathServlet processing

Type: boolean

debugAbbreviation

Debug abbreviations over JVM to JVM connections

Type: boolean

Constraints: Has Secure Value: false

debugAppAnnotations

Debug AppContainer's scanning and processing of annotations

Type: boolean

Constraints: Has Secure Value: false

debugAppContainer

Debug Application Container processing

Type: boolean

Constraints: Has Secure Value: false

debugAsyncQueue

Debug async replication/persistence information.

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugBeanTreeHarvesterControl

Debug the BeanTree Harvester delegate metric control process.

Type: boolean

debugBeanTreeHarvesterDataCollection

Debug the BeanTree Harvester delegate metric collection process.

Type: boolean

debugBeanTreeHarvesterResolution

Debug the BeanTree Harvester delegate metric resolution process.

Type: boolean

debugBeanTreeHarvesterThreading

Debug BeanTree Harvester delegate threading issues.

Type: boolean

debugBuzzProtocol

Debugs Buzz protocol.

Type: boolean

Constraints: Has Default Value: false

debugBuzzProtocolDetails

Debugs Buzz protocol details.

Type: boolean

Constraints: Has Default Value: false

debugBuzzProtocolHttp

Debugs Buzz protocol http.

Type: boolean

Constraints: Has Default Value: false

debugCertRevocCheck

Debug Security PKI X.509 certificate revocation checking

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugClassLoadingContextualTrace

Contextual Trace Debugger for Class Loading

Type: boolean

debugClassLoadingVerbose

Verbose Debugger for Class Loading

Type: boolean

debugClassRedef

Gets the DebugClassRedef attribute of ServerDebugMBean

Type: boolean

Constraints: Has Secure Value: false

debugClassSize

Gets the fastswap DebugClassSize debug attribute of ServerDebugMBean

Type: boolean

Constraints: Has Secure Value: false

debugCluster

Debug each GroupMessage that is sent or received by multicast.

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugClusterAnnouncements

Debug each Announcement, StateDump, and Attributes message that is sent or received by multicast.

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugClusterFragments

Debug for each fragment that is sent or received by multicast.

Type: boolean

Constraints: Has Secure Value: false

debugClusterHeartbeats

Debug each cluster Heartbeat that is sent or received by multicast.

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugConcurrent

Debug concurrent general processing

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugConcurrentContext

Debug concurrent context processing

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugConcurrentMES

Debug concurrent MES processing

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugConcurrentMSES

Debug concurrent MSES processing

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugConcurrentMTF

Debug concurrent MTF processing

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugConcurrentTransaction

Debug concurrent transaction processing

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugConfigurationEdit

Debug management configuration edit processing

Type: boolean

debugConfigurationRuntime

Debug management configuration runtime processing

Type: boolean

debugConnection

Debug JVM to JVM connections

Type: boolean

Constraints: Has Secure Value: false

debugConnectorService

Debug connector service action processing

Type: boolean

Constraints: Has Default Value: false

debugConsensusLeasing

Debug cluster consensus lease processing

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugDGCEnrollment

Debug each DGC enrollment.

Type: boolean

Constraints: Has Secure Value: false

debugDRSCalls

Debug Data replication service (DRS) API calls.

Type: boolean

Constraints: Has Secure Value: false

debugDRSHearbeats

Debug DRS Heartbeats.

Type: boolean

Constraints: Has Secure Value: false

debugDRSMessages

Debug DRS Message traffic.

Type: boolean

Constraints: Has Secure Value: false

debugDRSQueues

Debug DRS Queueing traffic.

Type: boolean

Constraints: Has Secure Value: false

debugDRSStateTransitions

Debug DRS State transitions.

Type: boolean

Constraints: Has Secure Value: false

debugDRSUpdateStatus

Debug DRS Update status processing.

Type: boolean

Constraints: Has Secure Value: false

debugDeploy

Debug deploy command processing

Type: boolean

debugDeployment

Debug deployment processing

Type: boolean

debugDeploymentConcise

Debug deployment concise processing

Type: boolean

debugDeploymentPlan

Debug deployment plan processing

Type: boolean

debugDeploymentService

Debug deployment service processing

Type: boolean

debugDeploymentServiceInternal

Debug internal deployment service processing

Type: boolean

debugDeploymentServiceStatusUpdates

Debug deployment service status update processing

Type: boolean

debugDeploymentServiceTransport

Debug deployment service transport processing

Type: boolean

debugDeploymentServiceTransportHttp

Debug deployment service HTTP transport processing

Type: boolean

debugDescriptor

Debug descriptor framework processing

Type: boolean

debugDiagnosticAccessor

Debug diagnostic accessor processing

Type: boolean

debugDiagnosticArchive

Debug diagnostic archive processing

Type: boolean

debugDiagnosticArchiveRetirement

Debug diagnostic archive retirement processing

Type: boolean

debugDiagnosticCollections

Debug diagnostic collection processing

Type: boolean

debugDiagnosticContext

Debug diagnostic context processing

Type: boolean

debugDiagnosticDataGathering

Debug data gathering processing

Type: boolean

debugDiagnosticFileArchive

Debug diagnostic file archive processing

Type: boolean

debugDiagnosticImage

Debug diagnostic image processing

Type: boolean

debugDiagnosticInstrumentation

Debug diagnostic instrumentation processing

Type: boolean

debugDiagnosticInstrumentationActions

Debug instrumentation actions/monitors

Type: boolean

debugDiagnosticInstrumentationConfig

Debug instrumentation configuration processing

Type: boolean

debugDiagnosticInstrumentationEvents

Debug instrumentation event records

Type: boolean

debugDiagnosticInstrumentationWeaving

Debug instrumentation weaving

Type: boolean

debugDiagnosticInstrumentationWeavingMatches

Debug instrumentation weaving for matches only

Type: boolean

debugDiagnosticJdbcArchive

Debug diagnostic jdbc archive processing

Type: boolean

debugDiagnosticLifecycleHandlers

Debug diagnostic lifecycle handler processing

Type: boolean

debugDiagnosticQuery

Debug diagnostic query processing

Type: boolean

debugDiagnosticRuntimeControlDriver

Debug the WLDF runtime control MBeans.

Type: boolean

debugDiagnosticRuntimeControlService

Debug the WLDF runtime control service.

Type: boolean

debugDiagnosticWatch

Debug diagnostic policy processing.

Type: boolean

debugDiagnosticWatchEvents

Debug diagnostic policy events processing.

Type: boolean

debugDiagnosticWatchEventsDetails

Debug diagnostic policy event processing details.

Type: boolean

debugDiagnosticWlstoreArchive

Debug diagnostic wlstore archive processing

Type: boolean

debugDiagnosticsBeanExtensionResolver

Debug the bean extensions ELResolver in the Diagnostics expressions framework

Type: boolean

debugDiagnosticsBeanInfoProviders

Debug the custom BeanInfo providers for the Diagnostics expressions framework

Type: boolean

debugDiagnosticsELContext

Debug the ELContext in the Diagnostics expressions framework

Type: boolean

debugDiagnosticsELResolver

Debug the DiagnosticsELResolver in the Diagnostics expressions framework

Type: boolean

debugDiagnosticsExpressionEvaluators

Debug the EL expression evaluators for the Diagnostics expressions framework

Type: boolean

debugDiagnosticsExpressionFunctionMapper

Debug the Diagnostics expressions framework function mapper

Type: boolean

debugDiagnosticsExpressionFunctions

Debug the Diagnostics expressions framework functions

Type: boolean

debugDiagnosticsExpressionMetrics

Debug metrics collection for the Diagnostics expressions framework

Type: boolean

debugDiagnosticsExpressionPoller

Debug metrics polling for the Diagnostics expressions framework

Type: boolean

debugDiagnosticsExpressionPollerBuffer

Debug the Diagnostics expressions poller extract() buffers

Type: boolean

debugDiagnosticsHarvester

Debug diagnostic harvester processing

Type: boolean

debugDiagnosticsHarvesterData

Detailed debug of diagnostic harvester processing

This should be used in conjunction with DebugDiagnosticsHarvester.

Type: boolean

debugDiagnosticsHarvesterMBeanPlugin

Debug MBean harvester processing.

This should probably be used in conjunction with DebugDiagnosticsHarvester.

Type: boolean

debugDiagnosticsHarvesterTreeBeanPlugin

Debug tree bean harvester processing

Type: boolean

debugDiagnosticsMBeanELResolver

Debug the MBean ELResolver in the Diagnostics expressions framework

Type: boolean

debugDiagnosticsModule

Debug diagnostic module processing

Type: boolean

debugDiagnosticsScriptAction

Debug the diagnostics policy script action.

Type: boolean

debugDiagnosticsUtils

Debug the Diagnostics utils

Type: boolean

debugDiagnosticsValueTracingELResolver

Debug the value tracing ELResolver in the Diagnostics expressions framework

Type: boolean

debugDomainLogHandler

Debug Domain Log Handler processing

Type: boolean

debugDynamicSingletonServices

Debug Dynamic Service Migration processing

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugEjbCaching

Debug EJB Caching

Type: boolean

Constraints: Has Secure Value: false

debugEjbCmpDeployment

Debug EJB CMP deployment processing

Type: boolean

Constraints: Has Secure Value: false

debugEjbCmpRuntime

Debug EJB CMP runtime processing

Type: boolean

Constraints: Has Secure Value: false

debugEjbCompilation

Debug EJB compilation

Type: boolean

Constraints: Has Secure Value: false

debugEjbDeployment

Debug EJB deployment

Type: boolean

Constraints: Has Secure Value: false

debugEjbInvoke

Debug EJB invocation processing

Type: boolean

Constraints: Has Secure Value: false

debugEjbLocking

Debug EJB locking

Type: boolean

Constraints: Has Secure Value: false

debugEjbMdbConnection

Debug EJB MDB Connection processing

Type: boolean

Constraints: Has Secure Value: false

debugEjbMetadata

Debug EJB metadata processing

Type: boolean

Constraints: Has Secure Value: false

debugEjbPooling

Debug EJB pooling

Type: boolean

Constraints: Has Secure Value: false

debugEjbSecurity

Debug EJB Security

Type: boolean

Constraints: Has Secure Value: false

debugEjbSwapping

Debug EJB Swapping

Type: boolean

Constraints: Has Secure Value: false

debugEjbTimers

Debug EJB Timer processing

Type: boolean

Constraints: Has Secure Value: false

debugElasticActions

Debug the elastic actions framework

Type: boolean

debugElasticServices

Debug the elastic services framework

Type: boolean

debugEmbeddedLDAP

Debug Embedded LDAP processing

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugEmbeddedLDAPLogLevel

Debug Embedded LDAP processing (log level)

Type: integer/int32

Constraints: Has Secure Value: 0, Has Default Value: 0, Minimum Value: 0, Maximum Value: 11

debugEmbeddedLDAPLogToConsole

Debug Embedded LDAP processing (output to console)

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugEmbeddedLDAPWriteOverrideProps

Embedded LDAP Write All Overrides to Property Files

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugEventManager

Debug Event Manager processing

Type: boolean

Constraints: Has Secure Value: false

debugExpressionBeanLocalizer

Debug the Diagnostics expressions framework extension bean localizer

Type: boolean

debugExpressionExtensionsManager

Debug the Diagnostics expressions extensions manager

Type: boolean

debugFailOver

Debug stub-level fail-over processing

Type: boolean

Constraints: Has Secure Value: false

debugFileDistributionServlet

Debug the file distribution servlet that runs on the Admin Server and is invoked over HTTP by a booting managed server.

Type: boolean

debugHttp

Debug WebApp Container HTTP processing.

Type: boolean

Constraints: Has Secure Value: false

debugHttpConcise

Debug WebApp Container for supplementary HTTP processing.

Type: boolean

Constraints: Has Secure Value: false

debugHttpLogging

Debug log manager in the webapp container.

Type: boolean

Constraints: Has Secure Value: false

debugHttpSessions

Debug Http Session management in the webapp container.

Type: boolean

Constraints: Has Secure Value: false

debugIIOPConnection

Debug IIOP connection management processing

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugIIOPMarshal

Debug buffer-level IIOP processing

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugIIOPNaming

Debug IIOP CosNaming processing

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugIOPOTS

Debug IIOB Object Transaction Service (OTS) processing

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugIOPReplacer

Debug IIOB object replacement processing

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugIOPSecurity

Debug IIOB security processing

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugIOPStartup

Debug IIOB startup processing

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugIOPTransport

Debug IIOB message processing

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugIOPTunneling

Debug IIOB tunnelling

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugInterceptors

Debug interceptors processing

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugJ2EEManagement

Debug Java EE management processing

Type: boolean

debugJAXPDebugLevel

JAXP debugging option: Debug level

Type: integer/int32

Constraints: Has Secure Value: 0, Has Default Value: 0, Minimum Value: 0, Maximum Value: 3

debugJAXPDebugName

JAXP debugging option: Debug name

Type: string

Constraints: Has Secure Value: null, Has Default Value: null, Legal Null: true

debugJAXPIncludeClass

JAXP debugging option: Debug IncludeClass

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugJAXPIncludeLocation

JAXP debugging option: Debug IncludeLocation

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugJAXPIncludeName

JAXP debugging option: Debug IncludeName

Type: boolean

Constraints: Has Secure Value: true, Has Default Value: false

debugJAXPIncludeTime

JAXP debugging option: Debug IncludeTime

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugJAXPUseShortClass

JAXP debugging option: Debug UseShortClass

Type: boolean

Constraints: Has Secure Value: true, Has Default Value: false

debugJDBCConn

Debug JDBC Connection setup/teardown processing

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugJDBCInternal

Debug JDBC Internal processing

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugJDBCONS

Debug ONS client

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugJDBCRCAC

Debug Oracle RAC processing

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugJDBCRMI

Debug JDBC RMI processing

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugJDBCReplay

Debug REPLAY client

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugJDBCSQL

Debug JDBC SQL processing

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugJDBCUCP

Debug Oracle UCP processing

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugJMSBackEnd

Debug JMSBackEnd processing

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugJMSBoot

Debug JMS boot operations

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugJMSCDS

Debug JMS CDS processing

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugJMSCommon

Debug JMSCommon processing

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugJMSConfig

Debug JMSConfig processing

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugJMSDispatcher

Debug JMS Dispatcher processing

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugJMSDispatcherProxy

Debug JMS Dispatcher Proxy

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugJMSDistTopic

Debug JMS Distributed Topic processing

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugJMSFrontEnd

Debug JMSFrontEnd processing

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugJMSMessagePath

Debug JMS MessagePath processing

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugJMSModule

Debug JMSModule deployment processing

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugJMSPauseResume

Debug JMS Pause/Resume processing

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugJMSSAF

Debug JMS SAF processing

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugJMST3Server

Debug DebugJMST3Server processing

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugJMSWrappers

Debug the pooling and wrapping of JMS connections, sessions, and other objects. This feature is enabled when a JMS connection factory, from any vendor, is used inside an EJB or a servlet using the "resource-reference" element in the deployment descriptor.

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugJMX

Debug JMX processing

Type: boolean

debugJMXCompatibility

Debug JMX CompatibilityMBeanServer service processing

Type: boolean

debugJMXCore

Debug core JMX processing

Type: boolean

debugJMXCoreConcise

Debug core JMX connection processing

Type: boolean

debugJMXDomain

Debug JMX domain service processing

Type: boolean

debugJMXEdit

Debug JMX edit service processing

Type: boolean

debugJMXRuntime

Debug JMX runtime service processing

Type: boolean

debugJNDI

Debug basic naming service machinery.

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugJNDIFactories

Debug JNDI state and object factories.

Type: boolean

Constraints: Has Secure Value: false

debugJNDIResolution

Debug naming service name resolution.

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugJTA2PC

Debug JTA 2PC processing

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugJTA2PCStackTrace

Detailed Debug of JTA 2PC processing

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugJTACDI

Debug JTA CDI log processing

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugJTAGateway

Debug JTA imported transactions

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugJTAGatewayStackTrace

Detailed debug of JTA imported transactions

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugJTAHealth

Debug JTA Health Monitoring

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugJTAJDBC

Debug JTA JDBC processing

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugJTALLR

Debug JTA Logging Last Resource

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugJTALifecycle

Debug JTA ServerLifecycle

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugJTAMigration

Debug JTA TLOG Migration

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugJTANaming

Debug JTA naming

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugJTANamingStackTrace

Detailed debug of JTA naming

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugJTANonXA

Debug JTA non-XA resources

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugJTAPropagate

Debug JTA transaction propagation

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugJTAREcovery

Debug JTA Recovery processing

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugJTAResourceHealth

Debug JTA resource health

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugJTAResourceName

Debug JTA Resource name filter

Type: string

debugJTATLOG

Debug JTA transaction log processing

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugJTAXA

Debug JTA XA resources

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugJTAXAStackTrace

Detailed Debug of JTA XA processing

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugJpaDataCache

Debug JPA data cache

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugJpaEnhance

Debug JPA post-compilation

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugJpaJdbcJdbc

Debug JPA RDBMS JDBC interaction

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugJpaJdbcSchema

Debug JPA RDBMS schema manipulation

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugJpaJdbcSql

Debug JPA RDBMS SQL interaction

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugJpaManage

Debug JPA management and monitoring

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugJpaMetaData

Debug JPA MetaData processing

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugJpaProfile

Debug JPA profiling

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugJpaQuery

Debug JPA Query processing

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugJpaRuntime

Debug JPA runtime diagnostics

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugJpaTool

Debug JPA tools

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugLeaderElection

Debug the cluster leader election messages.

Type: boolean

Constraints: Has Secure Value: false

debugLibraries

Debug application library processing

Type: boolean

Constraints: Has Secure Value: false

debugLifecycleManager

Debug Lifecycle Manager

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugLoadBalancing

Debug stub-level load-balancing processing

Type: boolean

Constraints: Has Secure Value: false

debugLocalRemoteJVM

Debug how is LocalRemoteJVM working.

Type: boolean

Constraints: Has Secure Value: false

debugLoggingConfiguration

Debug log configuration processing

Type: boolean

debugMBeanHarvesterControl

Debug the JMX Harvester delegate metric control process.

Type: boolean

debugMBeanHarvesterDataCollection

Debug the JMX Harvester delegate metric collection process.

Type: boolean

debugMBeanHarvesterResolution

Debug the JMX Harvester delegate metric resolution process.

Type: boolean

debugMBeanHarvesterThreading

Debug JMX Harvester delegate threading issues.

Type: boolean

debugMBeanTypeUtilQueue

Debug the Harvester MBean registration queue events

Type: boolean

debugMBeanTypeUtilQueuePriority

Debug the Harvester MBean registration prioritized events processing

Type: boolean

debugMBeanTypeUtilityListener

Debug the Harvester MBean registration processing

Type: boolean

debugMBeanTypingUtility

Debug the Harvester MBean type utility

Type: boolean

debugManagementServicesResource

Debug Management Services Resources

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugMaskCriteria

Dye mask criteria used to determine whether debug will be emitted for a request. Specifies the names of the Dye flags that will be inspected at runtime to determine whether debug needs to be emitted for a request.

Type: array of string

debugMessaging

Debug messages sent over JVM to JVM connections

Type: boolean

Constraints: Has Secure Value: false

debugMessagingBridgeRuntime

Debug Messaging Bridge runtime processing

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugMessagingBridgeRuntimeVerbose

Detailed debug of Messaging Bridge runtime processing

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugMessagingBridgeStartup

Debug Messaging Bridge start up processing

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugMessagingKernel

Debugging for the messaging kernel. The messaging kernel is low-level messaging code that is used by the JMS and store and forward subsystems.

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugMessagingKernelBoot

Debugging for the messaging kernel as the server is being rebooted. This provides detailed information on every persistent message that is recovered.

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugMessagingOwnableLock

Debugging for the messaging kernel ownable lock. This provides detailed information on lock owners.

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugMuxer

Debug Muxer processing

Type: boolean

Constraints: Has Default Value: false

debugMuxerConnection

Debug Muxer connection processing

Type: boolean

Constraints: Has Default Value: false

debugMuxerDetail

Detailed debug for Muxer processing

Type: boolean

Constraints: Has Default Value: false

debugMuxerException

Debug Muxer exception processing

Type: boolean

Constraints: Has Default Value: false

debugMuxerTimeout

Debug Muxer timeout processing

Type: boolean

Constraints: Has Default Value: false

debugNodeManagerRuntime

Debug NodeManagerRuntime

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugParameters

Parameters for debug logging defined as name value pairs. The parameters are prefixed with the name of the debug flag. The parameter names supported for a debug flag is specific to the implementation of the debug output.

Type: java.util.Properties

Constraints: Has Secure Value: null

debugPartitionResourceMetricsRuntime

Debug PartitionResourceMetricsRuntimeMBean operations.

Type: boolean

debugPatchingRuntime

Debug management patching runtime processing

Type: boolean

debugPathSvc

Debug the Path Service

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugPathSvcVerbose

Detailed debug for the Path Service

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugRA

Debug Resource Adapter XA general/top-level processing

Type: boolean

Constraints: Has Default Value: false

debugRAClassloader

Debug Resource Adapter class loading

Type: boolean

Constraints: Has Default Value: false

debugRAConnEvents

Debug Resource Adapter connection event processing

Type: boolean

Constraints: Has Default Value: false

debugRAConnections

Debug Resource Adapter outbound connection operations (get, close, associate, disassociate, ping)

Type: boolean

Constraints: Has Default Value: false

debugRADeployment

Debug Resource Adapter (un)deploy, security id settings

Type: boolean

Constraints: Has Default Value: false

debugRALifecycle

Debug ResourceAdapter Lifecycle processing

Type: boolean

Constraints: Has Default Value: false

debugRALocalOut

Debug Resource Adapter local tx outgoing message processing

Type: boolean

Constraints: Has Default Value: false

debugRAParsing

Debug Resource Adapter descriptor parsing

Type: boolean

Constraints: Has Default Value: false

debugRAPoolVerbose

Debug Java EE Resource Adapter pool management (size management) processing

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugRAPooling

Debug Resource Adapter operations on a connection pool (proxy testing)

Type: boolean

Constraints: Has Default Value: false

debugRASecurityCtx

Debug setup of resource ref processing (container and application managed security set by calling application components)

Type: boolean

Constraints: Has Default Value: false

debugRAWork

Debug Resource Adapter Work submission and cancel processing

Type: boolean

Constraints: Has Default Value: false

debugRAWorkEvents

Debug Resource Adapter work event processing

Type: boolean

Constraints: Has Default Value: false

debugRAXain

Debug Resource Adapter XA incoming message processing

Type: boolean

Constraints: Has Default Value: false

debugRAXAout

Debug Resource Adapter XA outgoing message processing

Type: boolean

Constraints: Has Default Value: false

debugRAXAwork

Debug Resource Adapter XA Work request processing

Type: boolean

Constraints: Has Default Value: false

debugRC4

Debug RC4 cipher processing

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugRCM

Debug RCM

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugRESTNotifications

Debug the diagnostics policy REST action.

Type: boolean

debugRSA

Debug RSA security processing

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugReadyApp

Debug ReadyApp processing.

Type: boolean

Constraints: Has Secure Value: false

debugReplication

Debug cluster replication information.

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugReplicationDetails

Debug low-level cluster replication information.

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugReplicationSize

Debug cluster replication size information.

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugRestJersey1Integration

Debug JAX-RS 1 / Jersey 1 Client integration

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugRestJersey2Integration

Debug JAX-RS 2 / Jersey 2 integration

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugRestartInPlace

Gets debugRestartInPlace attribute of ServerDebugMBean

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugRouting

Debug routing of messages over JVM to JVM connections

Type: boolean

Constraints: Has Secure Value: false

debugSAFAdmin

Debug Messaging SAF Admin.

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugSAFManager

Debug Messaging SAF Manager.

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugSAFReceivingAgent

Debug Messaging SAF ReceivingAgent.

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugSAFSendingAgent

Debug Messaging SAF SendingAgent.

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugSAFStore

Debug Messaging SAF Store.

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugSAFTransport

Debug Messaging SAF Transport.

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugSAFVerbose

Detailed debug of Messaging SAF.

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugSNMPAgent

Debug the SNMP agent framework.

Type: boolean

debugSNMPExtensionProvider

The debug attribute to enable or disable the SNMP Agent Extension Provider discovery and initialization.

Type: boolean

debugSNMPProtocolTCP

Debug the SNMP TCP protocol handler.

Type: boolean

debugSNMPToolkit

Debug the SNMP vendor toolkit implementation.

Type: boolean

debugSSL

Debug SSL processing

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugScaContainer

Debug Weblogic SCA Container

Type: boolean

Constraints: Has Default Value: false

debugSecurityAdjudicator

Debug Security Framework Adjudication processing

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugSecurityAtn

Debug Security Framework Atn processing

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugSecurityAtz

Debug Security Framework Atz processing

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugSecurityAuditor

Debug Security Framework Auditor processing

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugSecurityCertPath

Debug Security Framework CertPath processing

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugSecurityCredMap

Debug Security Framework Credential Mapper processing

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugSecurityEEEngine

Debug Security Framework Entitlements Engine processing

Type: boolean

Constraints: Has Default Value: false

debugSecurityEncryptionService

Debug Security Framework Encryption Service processing

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugSecurityJACC

Debug Security Framework JACC processing

Type: boolean

Constraints: Has Default Value: false

debugSecurityJACCNonPolicy

Debug Security Framework JACC nonPolicy processing

Type: boolean

Constraints: Has Default Value: false

debugSecurityJACCPolicy

Debug Security Framework JACC Policy processing

Type: boolean

Constraints: Has Default Value: false

debugSecurityKeyStore

Debug Security Framework KeyStore processing

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugSecurityPasswordPolicy

Debug Security Password Guessing

Type: boolean

Constraints: Has Default Value: false

debugSecurityPredicate

Debug Security Framework predicate processing

Type: boolean

Constraints: Has Default Value: false

debugSecurityRealm

Debug Security Realm processing

Type: boolean

Constraints: Has Default Value: false

debugSecurityRoleMap

Debug Security Framework Role Mapping

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugSecuritySAML2Atn

Debug Security Framework SAML2 Provider atn processing

Type: boolean

Constraints: Has Default Value: false

debugSecuritySAML2CredMap

Debug Security Framework SAML2 Provider credential mapper processing

Type: boolean

Constraints: Has Default Value: false

debugSecuritySAML2Lib

Debug Security Framework SAML2 library processing

Type: boolean

Constraints: Has Default Value: false

debugSecuritySAML2Service

Debug Security Framework SAML2 SSO profile services

Type: boolean

Constraints: Has Default Value: false

debugSecuritySAMLAtn

Debug Security Framework SAML Provider atn processing

Type: boolean

Constraints: Has Default Value: false

debugSecuritySAMLcredMap

Debug Security Framework SAML Provider credential mapper processing

Type: boolean

Constraints: Has Default Value: false

debugSecuritySAMLlib

Debug Security Framework SAML library processing

Type: boolean

Constraints: Has Default Value: false

debugSecuritySAMLService

Debug Security Framework SAML SSO profile services

Type: boolean

Constraints: Has Default Value: false

debugSecuritySSL

Debug Security SSL and TLS processing

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugSecuritySSLEaten

Debug Security SSL and TLS exception processing

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugSecurityService

Debug Security Service

Type: boolean

Constraints: Has Default Value: false

debugSecurityUserLockout

Debug Security User Lockout processing

Type: boolean

Constraints: Has Default Value: false

debugSelfTuning

Debug WorkManager self-tuning processing

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugServerLifeCycle

Debug Server ServerLifeCycle processing

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugServerMigration

Debug low-level Server Migration processing

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugServerStartStatistics

If statistics about server start will be logged after the running message.

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugStoreAdmin

Debug the persistent store's administration code. This will produce debug events when instances of the store are created and deleted, and when the server is booted.

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugStoreIOLogical

Debug persistent store high-level logical operations, such as read, write, delete, and update. Multiple logical operations may occur in a single physical operation.

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugStoreIOLogicalBoot

Debug persistent store logical boot operations (lists all recovered records).

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugStoreIOPhysical

Debugging for persistent store low-level physical operations which typically directly correspond to file or JDBC operations. Multiple logical operations may occur in a single physical operation.

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugStoreIOPhysicalVerbose

Detailed debug for persistent store low-level physical operations which typically directly correspond to file or JDBC operations.

This will produce a great deal of debugging for every disk I/O performed by the store. Multiple logical operations may occur in a single physical operation.

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugTunnelingConnection

Debug HTTP tunneling connection open/close processing.

Type: boolean

Constraints: Has Secure Value: false

debugTunnelingConnectionTimeout

Debug HTTP tunneling connection timed out processing.

Type: boolean

Constraints: Has Secure Value: false

debugURLResolution

Debug URL resolution for incoming http requests

Type: boolean

Constraints: Has Secure Value: false

debugVerboseRCM

Debug Verbose RCM

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugWANReplicationDetails

Debug low-level wan replication processing

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugWTCCConfig

Debug WTC configuration processing

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugWTCCorbaEx

Debug WTC corba execution

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugWTCCGwtEx

Debug WTC gwt execution

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugWTCJatmiEx

Debug WTC jatmi execution

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugWTCTDomPdu

Debug WTC XATMI Message processing

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugWTCUData

Debug WTC user data processing

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugWTCTBridgeEx

Debug WTC tBridge execution

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugWebAppIdentityAssertion

Debug identity assertion flow when identity assertion occurs in the webapp container.

Type: boolean

Constraints: Has Secure Value: false

debugWebAppModule

Debug WebApp Module deployment callbacks

Type: boolean

Constraints: Has Secure Value: false

debugWebAppSecurity

Debug webapp security

Type: boolean

Constraints: Has Secure Value: false

debugWorkContext

Debug Work context (out of band data propagation)

Type: boolean

Constraints: Has Secure Value: false

debugXMLEntityCacheDebugLevel

XMLEntityCache debugging option: Debug level

Type: integer/int32

Constraints: Has Secure Value: 0, Has Default Value: 0, Minimum Value: 0, Maximum Value: 3

debugXMLEntityCacheDebugName

XMLEntityCache debugging option: Debug name

Type: string

Constraints: Has Secure Value: null, Has Default Value: null, Legal Null: true

debugXMLEntityCacheIncludeClass

XMLEntityCache debugging option: Debug IncludeClass

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugXMLEntityCacheIncludeLocation

XMLEntityCache debugging option: Debug IncludeLocation

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugXMLEntityCacheIncludeName

XMLEntityCache debugging option: Debug IncludeName

Type: boolean

Constraints: Has Secure Value: true, Has Default Value: false

debugXMLEntityCacheIncludeTime

XMLEntityCache debugging option: Debug IncludeTime

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugXMLEntityCacheUseShortClass

XMLEntityCache debugging option: Debug UseShortClass

Type: boolean

Constraints: Has Secure Value: true, Has Default Value: false

debugXMLRegistryDebugLevel

XML Registry debugging option: Debug levels

Type: integer/int32

Constraints: Has Secure Value: 0, Has Default Value: 0, Minimum Value: 0, Maximum Value: 3

debugXMLRegistryDebugName

XML Registry debugging option: Debug name

Type: string

Constraints: Has Secure Value: null, Has Default Value: null, Legal Null: true

debugXMLRegistryIncludeClass

XML Registry debugging option: Debug IncludeClass

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugXMLRegistryIncludeLocation

XML Registry debugging option: Debug IncludeLocation

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugXMLRegistryIncludeName

XML Registry debugging option: Debug IncludeName

Type: boolean

Constraints: Has Secure Value: true, Has Default Value: false

debugXMLRegistryIncludeTime

XML Registry debugging option: Debug IncludeTime

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

debugXMLRegistryUseShortClass

XML Registry debugging option: Debug UseShortClass

Type: boolean

Constraints: Has Secure Value: true, Has Default Value: false

defaultStore

Gets the fastswap DefaultStore debug attribute of ServerDebugMBean

Type: boolean

Constraints: Has Secure Value: false

diagnosticContextDebugMode

Specifies how context based debugging is enabled for the Server. The default behavior in the `Off` mode is that debug output is emitted for all requests.

The DiagnosticContextDebugMode works in conjunction with the DebugMaskCriteria specified in the `And` or `Or` modes. For context based debugging the WLDF Instrumentation needs to be enabled and DyeInjection monitor needs to be configured for the Server.

When the context debug mode is set to `And` mode, debug is emitted only for the requests that have all the bits in the WLDF dye vector set for the flags specified in the DebugMaskCriteria attribute.

When the context debug mode is set to `Or` mode, debug is emitted only for the requests that have any one of the bits in the WLDF dye vector set for the flags specified in the DebugMaskCriteria attribute.

Type: string

Constraints: Has Default Value: Off, Legal Values: Off, And, Or

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

forceGCEachDGCPeiod

Force VM garbage collection on each DGC interval

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

listenThreadDebug

Debug listenThread processing

Type: boolean

Constraints: Has Secure Value: false

logDGCStatistics

Debug DGC with Statistics

Type: boolean

Constraints: Has Secure Value: false

masterDeployer

Debug Master Deployer processing

Type: boolean

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

`Name=user-specified-name`

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

partitionDebugLoggingEnabled

Enables or disables whether Partition Administrators can enable Debug Logging for their respective Partitions.

Type: boolean

Constraints: Has Default Value: false

redefiningClassLoader

Gets the fastswap RedefiningClassLoader debug attribute of ServerDebugMBean

Type: boolean

Constraints: Has Secure Value: false

server

Returns the server for this bean

Type: weblogic.management.configuration.ServerMBean reference

Constraints: Restart Required

slaveDeployer

Debug Slave Deployer processing

Type: boolean

tags

Return all tags on this Configuration MBean

Type: array of string

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

webModule

Debug WebModule processing

Type: boolean

weblogic.management.configuration.ServerFailureTriggerMBean

Configuration to mark the server as failed when threads are stuck. A failed server in turn can be configured to shutdown or go into admin state.

The properties of the weblogic.management.configuration.ServerFailureTriggerMBean entity are as follows:

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

maxStuckThreadTime

The number of seconds that a thread must be continually working before this server diagnoses the thread as being stuck.

For example, if you set this to 600 seconds, WebLogic Server considers a thread to be "stuck" after 600 seconds of continuous use.

Type: integer/int32

Constraints: Has Default Value: 600, Minimum Value: 0, Maximum Value: 2147483647

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's

`javax.management.ObjectName`

`Name=user-specified-name`

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`.

Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

stuckThreadCount

The number of stuck threads after which the server is transitioned into FAILED state. There are options in OverloadProtectionMBean to suspend and shutdown a FAILED server. By default, the server continues to run in FAILED state.

If the StuckThreadCount value is set to zero then the server never transitions into FAILED server irrespective of the number of stuck threads.

Type: integer/int32

Constraints: Has Default Value: 0, Minimum Value: 0, Maximum Value: 2147483647

tags

Return all tags on this Configuration MBean

Type: array of string

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.ServerMBean

This class represents a individual WebLogic Server. A WebLogic Server is a Java process that is a container for Java EE applications.

The properties of the weblogic.management.configuration.ServerMBean entity are as follows:

DGIdlePeriodsUntilTimeout

The number of idle periods allowed before the object is collected.

Type: integer/int32

Constraints: Has Default Value: 5

IIOPEntered

Specifies whether this server has IIOP support enabled for both the regular (non-SSL) and SSL ports.

Type: boolean

Constraints: Has Default Value: true

JDBCLLRTableName

The table name for this server's Logging Last Resource (LLR) database table(s). WebLogic Server creates the table(s) and then uses them during transaction processing for the LLR transaction optimization. This setting must be unique for each server. The default table name is `WL_LLRSERVERNAME`

This setting only applies if this server hosts one or more LLR-enabled JDBC data sources.

The format for the tables that WebLogic Server creates is [[[catalog.]schema.]name.] Each "." in the table name is significant, and schema generally corresponds to username in many databases.

IMPORTANT: If this value is changed but the LLR table already exists in the database, you must preserve the existing table's data. Consequently, when changing the table name, the existing database table must be renamed by a database administrator to match the new configured table name. Otherwise, transaction records may be lost, resulting in heuristic failures that aren't logged.

IMPORTANT: Each server's table name must be unique. Multiple LLR-enabled data sources within the same server may share the same table, but multiple servers must not share the same table. If multiple same-named servers share a table, the behavior is undefined and it is likely that transactions will not recover properly after a crash, creating heuristic hazards.

Type: string

JDBCLoginTimeoutSeconds

The JDBC Login Timeout value. Specified value is passed into `java.sql.DriverManager.setLoginTimeout()`. Note that this `DriverManager` setting will impact *all* JDBC drivers loaded into this JVM. Feature is disabled by default.

Type: integer/int32

Constraints: Has Default Value: 0, Minimum Value: 0, Maximum Value: 300

JMSConnectionFactoryUnmappedResRefMode

Use this unmapped resource reference mode to specify the behavior of any resource reference to a Connection Factory when the resource reference does not directly specify a JNDI name by a lookup attribute, or by a mappedName attribute, or by a jndi-name in a descriptor file. If a JNDI name is specified, the resource reference either resolves to the specified object in the JNDI tree or generates a `javax.naming.NameNotFoundException`.

Following are the available unmapped resource reference modes:

- `FailSafe` : In this mode, an application JMS connection factory resource reference that does not specify a JNDI name resolves to an object bound to the JNDI tree with the same name as the resource reference name if one can be found in JNDI tree. Otherwise, it throws a `javax.naming.NameNotFoundException`. A resource reference without a JNDI name never returns a Java EE 7 Default Connection Factory in this mode.

This mode yields pre-12.2.1 WebLogic Server behavior. This mode is Java EE compliant, but the Java EE 7 specification disallows it from being the default mode.

- `ReturnDefault` : This policy is a Java EE compliant mode and it is the default mode. It complies with Java EE 7 while doing a best effort to try delivering `FailSafe` behavior when it is expected.

(a) If the resource reference name matches the local JNDI name of a configured foreign JMS provider mapping, then WebLogic Server returns the remote JNDI entry from the mapping if it can be resolved, or it throws a `javax.naming.NameNotFoundException`.

(b) If the resource reference does not match with a foreign JMS provider mapping, and if the resource reference name matches the name of an object that is already bound to the JNDI tree, WebLogic Server returns the JNDI tree object.

(c) If neither (a) nor (b) apply, then WebLogic Server returns "java:comp/DefaultJMSConnectionFactory". In addition, it adds an 'Info' message in the server log indicating that a special behavior has occurred. This log message will occur at most once per application per server boot.

Type: string

Constraints: Has Default Value: ReturnDefault, Legal Values: ReturnDefault, FailSafe

JMSDefaultConnectionFactoriesEnabled

Specifies whether this server uses JMS default connection factories.

WebLogic Server provides the following JMS default connection factories:

- `weblogic.jms.ConnectionFactory`
- `weblogic.jms.XAConnectionFactory` An XA factory is required for JMS applications to use JTA user-transactions, but is not required for transacted sessions. All other preconfigured attributes for the default connection factories are set to the same default values as a user-defined connection factory. If the preconfigured settings of the default factories are appropriate for your application, you do not need to configure any additional factories for your application.

Note: When using the default connection factories, you have no control over targeting the WebLogic Server instances where the connection factory may be deployed. However, you can disable the default connection factories on a per-server basis. To deploy a connection factory on independent servers, on specific servers within a cluster, or on an entire cluster, you need to configure a connection factory and specify the appropriate server targets. The default Java EE 7 JMS Connection Factory, `java:comp/DefaultJMSConnectionFactory`, will be available even when the WebLogic JMS default connection factories are disabled.

Type: boolean

Constraints: Has Default Value: true

JNDITransportableObjectFactoryList

List of factories that create transportable objects.

Type: array of string

TGIOPEnabled

Specifies whether this server supports Tuxedo GIOP (TGIOP) requests. (Requires you to configure WebLogic Tuxedo Connector (WTC) for this server.)

Type: boolean

Constraints: Has Secure Value: true, Has Default Value: true

XMLEntityCache

The server's XML entity cache, which is used to configure the behavior of JAXP (Java API for XML Parsing).

Type: `weblogic.management.configuration.XMLEntityCacheMBean` reference

Constraints: Restart Required

XMLRegistry

The server's XML registry, which is used to configure the behavior of JAXP (Java API for XML Parsing).

Type: `weblogic.management.configuration.XMLRegistryMBean` reference

Constraints: Restart Required

acceptBacklog

The number of backlogged, new TCP connection requests that should be allowed for this server's regular and SSL ports.

Setting the backlog to may prevent this server from accepting any incoming connection on some operating systems.

Type: integer/int32

Constraints: Has Default Value: 300, Minimum Value: 0

addWorkManagerThreadsByCpuCount

Enables increased efficiency of the self-tuning thread pool by aligning it with the Exalogic processor architecture threading capabilities. Use only when configuring a WebLogic domain for Oracle Exalogic.

- Enabling this attribute increases efficiency during I/O in environments with high network throughput.
- Disabling this attribute allows the thread pool to self-tune to match the demand of the workload at the expense of longer ramp up time.

Type: boolean

adminReconnectIntervalSeconds

The number of seconds between reconnection attempts to the admin server. When the admin server fails the managed server will periodically try to connect back to it.

Type: integer/int32

Constraints: Has Default Value: 10, Minimum Value: 0, Maximum Value: 2147483647

administrationPort

The secure administration port for the server. This port requires that you enable the domain's administration port and that SSL is configured and enabled.

By default, the server uses the administration port that is specified at the domain level. To override the domain-level administration port for the current server instance, set this server's administration port.

Type: integer/int32

Constraints: Has Recommended Secure Value: 7002, Minimum Value: 0, Maximum Value: 65535

administrationProtocol

Returns the protocol to be used for administrative connections when none is specified.

Type: string

Constraints: Legal Values: t3s, https, iiops, t3, http, iiop

allowShrinkingPriorityRequestQueue

Specifies whether self-tuning should allow shrinking of its priority based queue for pending requests after it has grown in size due to busy workload, and whether it should try to purge work requests that have already been picked up for processing due to minimum threads constraints before growing the queue. Setting this to true would help reduce memory footprint after the busy work period has ended, at the expense of the overhead of growing the request queue again at the next period of busy workload. It would also help to reduce the amount of memory allocated for the request queue, at the expense of the overhead required in purging already processed work requests from the queue.

Type: boolean

Constraints: Has Default Value: true

autoMigrationEnabled

Specifies whether Node Manager can automatically restart this server and its services on another machine if the server fails.

Type: boolean

autoRestart

Specifies whether the Node Manager can automatically restart this server if it crashes or otherwise goes down unexpectedly.

Type: boolean

Constraints: Has Default Value: true

buzzAddress

Buzz endpoint address.

Type: string

buzzEnabled

Enables Buzz for sending/receiving messages with peers. Enabling this attribute increases efficiency during I/O in environments with high network throughput and should be used only when configuring a WebLogic domain for Oracle Exalogic.

Type: boolean

Constraints: Has Default Value: false

buzzPort

Buzz endpoint port.

A value of means system-allocated (dynamic) port.

Type: integer/int32

Constraints: Has Default Value: 0

candidateMachines

Limits the list of candidate machines that the cluster specifies. (Requires you to enable this server for automatic migration and to configure the cluster with a set of candidate machines.)

If this server fails and if it is enabled for automatic migration, Node Manager automatically restarts it. By default, Node Manager restarts the server on any of the candidate machines that the cluster specifies (in order of preference that you configured in the cluster). To change the default, you use this server's list of candidate machines to create a subset of the cluster-wide candidates. You can also change the order of preference.

Type: array of weblogic.management.configuration.MachineMBean references

Constraints: Restart Required

classpathServletDisabled

The ClasspathServlet will serve any class file in the classpath and is registered by default in every Web application (including management). It does not need to be turned on for many applications though, and represents a security hole if unchecked.

WLS components such as JDBC and JMS rely on the ClasspathServlet. If the servlet can not be disabled, then set the ClassPathServletSecureModeEnabled to true.

Type: boolean

Constraints: Has Recommended Secure Value: true, Has Default Value: false

classpathServletSecureModeEnabled

If secure mode is enabled, the ClasspathServlet will serve only class files from wellknown packages required for JDBC and JMS functionality. If secure mode is disabled, it represents a security hole if unchecked as the ClassPatchServlet will serve any class in the classpath and is registered by default in every Web application (including management).

If set to true, the ClasspathServlet will not be disabled by the DefaultInternalServletsDisabled value of true.

Type: boolean

Constraints: Has Secure Value: true, Has Default Value: false

clientCertProxyEnabled

Specifies whether the HttpClusterServlet proxies the client certificate in a special header.

By default (or if you specify `false`), the `weblogic.xml` deployment descriptor for each web application that is deployed on this server determines whether the web application trusts certificates sent from the proxy server plugin. By default (or if the deployment descriptor specifies `false`), users cannot log in to the web application from a proxy server plugin.

A value of `true` causes proxy-server plugins to pass identity certifications from clients to all web applications that are deployed on this server instance. A proxy-server plugin encodes each identify certification in the `WL-Proxy-Client-Cert` header and passes the header to WebLogic Server instances. A WebLogic Server instance takes the certificate information from the header, trusting that it came from a secure source, and uses that information to authenticate the user.

If you specify `true`, use a `weblogic.security.net.ConnectionFilter` to ensure that this WebLogic Server instance accepts connections only from the machine on which the proxy-server plugin is running. Specifying `true` without using a connection filter creates a security vulnerability because the `WL-Proxy-Client-Cert` header can be spoofed.

A cluster can also specify whether the HttpClusterServlet proxies the client certificate in a special header. The cluster-level setting overrides the setting in individual servers that are part of the cluster.

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

cluster

The cluster, or group of WebLogic Server instances, to which this server belongs.

If set, the server will listen for cluster multicast events.

Type: weblogic.management.configuration.ClusterMBean reference

Constraints: Restart Required

clusterWeight

The proportion of the load that this server will bear, relative to other servers in a cluster.

If all servers have the default weight or the same weight, each bears an equal proportion of the load. If one server has weight 50 and all other servers have weight 100, the 50-weight server will bear half as much load as any other server.

Type: integer/int32

Constraints: Has Default Value: 100, Minimum Value: 1, Maximum Value: 100

coherenceClusterSystemResource

The system-level Coherence cluster resource associated with this server.

Type: weblogic.management.configuration.CoherenceClusterSystemResourceMBean reference

Constraints: Restart Required

completeMessageTimeout

The maximum number of seconds that this server waits for a complete message to be received. If you configure network channels for this server, each channel can override this message timeout.

This timeout helps guard against a denial of service attack in which a caller indicates that it will be sending a message of a certain size which it never finishes sending.

CompleteMessageTimeout affects the HTTP Response, such that if WebLogic Server discovers sockets inactive for longer than the CompleteMessageTimeout, the server will close these sockets.

Type: integer/int32

Constraints: Has Default Value: 60, Minimum Value: 0, Maximum Value: 480

completeWriteTimeout

The maximum number of seconds that this server waits for a complete HTTP response to be sent.

A value of `0` disables the complete write timeout. The default value is derived from the CompleteHTTPMessageTimeout. If it is `-1`, then the CompleteMessageTimeout value is used for the default value.

Type: integer/int32

Constraints: Minimum Value: 0

connectTimeout

The amount of time that this server should wait to establish an outbound socket connection before timing out. A value of `0` disables server connect timeout.

Type: integer/int32

Constraints: Has Default Value: 0, Minimum Value: 0, Maximum Value: 240

customIdentityKeyStoreFileName

The source of the identity keystore. For a JKS keystore, the source is the path and file name. For an Oracle Key Store Service (KSS) keystore, the source is the KSS URI.

If using a JKS keystore, the keystore path name must either be absolute or relative to where the server was booted.

If using a KSS keystore, the keystore URI must be of the form:

`kss://system/keystorename`

where *keystorename* is the name of the keystore registered in KSS.

The value in this attribute is only used if `KeyStores` is `CUSTOM_IDENTITY_AND_JAVA_STANDARD_TRUST`, `CUSTOM_IDENTITY_AND_CUSTOM_TRUST` or `CUSTOM_IDENTITY_AND_COMMAND_LINE_TRUST`

Type: string

Constraints: Has Default Value: null

customIdentityKeyStorePassPhrase

The encrypted custom identity keystore's passphrase. If empty or null, then the keystore will be opened without a passphrase.

This attribute is only used if `KeyStores` is `CUSTOM_IDENTITY_AND_JAVA_STANDARD_TRUST`, `CUSTOM_IDENTITY_AND_CUSTOM_TRUST` or `CUSTOM_IDENTITY_AND_COMMAND_LINE_TRUST`

When you get the value of this attribute, WebLogic Server does the following:

1. Retrieves the value of the `CustomIdentityKeyStorePassPhraseEncrypted` attribute.
2. Decrypts the value and returns the unencrypted password as a String.

When you set the value of this attribute, WebLogic Server does the following:

1. Encrypts the value.
2. Sets the value of the `CustomIdentityKeyStorePassPhraseEncrypted` attribute to the encrypted value.

Using this attribute (`CustomIdentityKeyStorePassPhrase`) is a potential security risk because the String object (which contains the unencrypted password) remains in the JVM's memory until garbage collection removes it and the memory is reallocated. Depending on how memory is allocated in the JVM, a significant amount of time could pass before this unencrypted data is removed from memory.

Instead of using this attribute, use `CustomIdentityKeyStorePassPhraseEncrypted`

Type: string

Constraints: Encrypted

customIdentityKeyStoreType

The type of the keystore. Generally, this is `JKS`. If using the Oracle Key Store Service, this would be `KSS`

If empty or null, then the JDK's default keystore type (specified in `java.security`) is used. The custom identity key store type is only used if `KeyStores` is `CUSTOM_IDENTITY_AND_JAVA_STANDARD_TRUST`, `CUSTOM_IDENTITY_AND_CUSTOM_TRUST` or `CUSTOM_IDENTITY_AND_COMMAND_LINE_TRUST`

Type: string

Constraints: Has Default Value: null

customTrustKeyStoreFileName

The source of the custom trust keystore. For a `JKS` keystore, the source is the path and file name. For an Oracle Key Store Service (`KSS`) keystore, the source is the `KSS` URI.

If using a `JKS` keystore, the keystore path name must either be absolute or relative to where the server was booted.

If using a KSS keystore, the keystore URI must be of the form:

```
kss://system/keystorename
```

where *keystorename* is the name of the keystore registered in KSS.

The value in this attribute is only used if `KeyStores` is `CUSTOM_IDENTITY_AND_CUSTOM_TRUST`

Type: string

Constraints: Has Default Value: null

customTrustKeyStorePassPhrase

The custom trust keystore's passphrase. If empty or null, then the keystore will be opened without a passphrase.

This attribute is only used if `KeyStores` is `CUSTOM_IDENTITY_AND_CUSTOM_TRUST`.

When you get the value of this attribute, WebLogic Server does the following:

1. Retrieves the value of the `CustomTrustKeyStorePassPhraseEncrypted` attribute.
2. Decrypts the value and returns the unencrypted password as a String.

When you set the value of this attribute, WebLogic Server does the following:

1. Encrypts the value.
2. Sets the value of the `CustomTrustKeyStorePassPhraseEncrypted` attribute to the encrypted value.

Using this attribute (`CustomTrustKeyStorePassPhrase`) is a potential security risk because the String object (which contains the unencrypted password) remains in the JVM's memory until garbage collection removes it and the memory is reallocated. Depending on how memory is allocated in the JVM, a significant amount of time could pass before this unencrypted data is removed from memory.

Instead of using this attribute, use `CustomTrustKeyStorePassPhraseEncrypted`

Type: string

Constraints: Encrypted

customTrustKeyStoreType

The type of the keystore. Generally, this is `JKS`. If using the Oracle Key Store Service, this would be `KSS`

If empty or null, then the JDK's default keystore type (specified in `java.security`) is used. This keystore type is only used if `KeyStores` is `CUSTOM_IDENTITY_AND_CUSTOM_TRUST`.

Type: string

Constraints: Has Default Value: null

defaultIIOPPassword

The password for the default IIOP user. (Requires you to enable IIOP.)

As of 8.1 sp4, when you get the value of this attribute, WebLogic Server does the following:

1. Retrieves the value of the `DefaultIIOPPasswordEncrypted` attribute.
2. Decrypts the value and returns the unencrypted password as a String.

Using this attribute (`DefaultIIOPPassword`) is a potential security risk because the String object (which contains the unencrypted password) remains in the JVM's memory until garbage collection removes it and the memory is reallocated. Depending on how memory is allocated in the JVM, a significant amount of time could pass before this unencrypted data is removed from memory.

Instead of using this attribute, use `DefaultIIOPPasswordEncrypted`

Type: string

Constraints: Encrypted, Has Default Value: null

defaultIIOPUser

The user name of the default IIOP user. (Requires you to enable IIOP.)

Type: string

Constraints: Has Default Value: null

defaultInternalServletsDisabled

Specifies whether all default servlets in the servlet engine are disabled.

This includes: `weblogic.servlet.ClasspathServlet`
`weblogic.servlet.utils.iop.GetIORServlet` `weblogic.rjvm.http.TunnelSendServlet`
`weblogic.rjvm.http.TunnelRecvServlet` `weblogic.rjvm.http.TunnelLoginServlet`
`weblogic.rjvm.http.TunnelCloseServlet` If set to true, this property overrides the `ClasspathServletDisabled` property.

Type: boolean

Constraints: Has Secure Value: true, Has Default Value: false

defaultProtocol

The protocol to use for connections when none is specified.

Type: string

Constraints: Has Default Value: t3, Legal Values: t3, t3s, http, https, iiop, iiops

defaultSecureProtocol

The protocol to use for secure connections when none is specified.

Type: string

Constraints: Has Default Value: t3s, Legal Values: t3s, https, iiops

defaultTGIOPPassword

The password for the default user associated with the Tuxedo GIOP (TGIOP) protocol. (Requires you to configure WebLogic Tuxedo Connector (WTC) for this server.)

As of 8.1 sp4, when you get the value of this attribute, WebLogic Server does the following:

1. Retrieves the value of the `DefaultTGIOPPasswordEncrypted` attribute.
2. Decrypts the value and returns the unencrypted password as a String.

When you set the value of this attribute, WebLogic Server does the following:

1. Encrypts the value.
2. Sets the value of the `DefaultTGIOPPasswordEncrypted` attribute to the encrypted value.

Using this attribute (`DefaultTGIOPPassword`) is a potential security risk in because the String object (which contains the unencrypted password) remains the JVM's memory

until garbage collection removes it and the memory is reallocated. Depending on how memory is allocated in the JVM, a significant amount of time could pass before this unencrypted data is removed from memory.

Instead of using this attribute, use `DefaultTGIOPPasswordEncrypted`

Type: string

Constraints: Encrypted

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

eagerThreadLocalCleanup

Specifies whether to clean up all ThreadLocals storage from self-tuning thread pool threads after they have finished processing each work request. By default, the self-tuning thread pool only cleans up ThreadLocal storage in its threads after an application is undeployed to avoid ClassLoader memory leak.

Type: boolean

Constraints: Has Default Value: false

externalDNSName

The external IP address or DNS name for this server.

This address will be sent with HTTP session cookies and with dynamic server lists to HTTP proxies. It will also be used by external application clients to enable the propagation of RMI traffic through network address translating (NAT) firewalls.

You must specify an external DNS name for configurations in which a firewall is performing network address translation, unless clients are accessing WebLogic Server using t3 and the default channel. For example, define the external DNS name for configurations in which a firewall is performing network address translation, and clients are accessing WebLogic Server using HTTP via a proxy plug-in.

Type: string

Constraints: Has Default Value: null

extraEjbcOptions

The options passed to the EJB compiler during server-side generation.

Each EJB component can override the compiler options that you specify here. The following options are valid:

-forcegeneration

Forces generation of wrapper classes. Without this flag the classes may not be regenerated if it is determined to be unnecessary.

-disableHotCodeGen

Generate ejb stub and skel as part of ejbc. Avoid HotCodeGen to have better performance.

-keepgenerated

Keep the generated .java files.

-compiler javac

Java compiler to exec. If not specified, the `-compilerclass` option will be used.

-compilerclass com.sun.tools.javac.Main

Specifies the compiler class to invoke.

-g

Compile debugging info into class file.

-normi

Passed through to Symantec's sj.

-classpath path

Classpath to use.

-source source

Source version.

-Joption

Flags passed through to java runtime.

Type: string

Constraints: Has Default Value: null

extraRmicOptions

The options passed to the RMIC compiler during server-side generation.

Each EJB component can override the compiler options that you specify here.

Type: string

Constraints: Has Default Value: null

gatheredWritesEnabled

Enables gathered writes over NIO socket channels. Enabling this attribute increases efficiency during I/O in environments with high network throughput and should be used only when configuring a WebLogic domain for Oracle Exalogic.

Type: boolean

Constraints: Has Default Value: false

gracefulShutdownTimeout

Number of seconds a graceful shutdown operation waits before forcing a shut down. A graceful shutdown gives WebLogic Server subsystems time to complete certain application processing currently in progress. If subsystems are unable to complete processing within the number of seconds that you specify here, then the server will force shutdown automatically.

A value of `0` means that the server will wait indefinitely for graceful shutdown to complete.

The graceful shutdown timeout applies only to graceful shutdown operations.

Type: integer/int32

Constraints: Has Default Value: 0, Minimum Value: 0

healthCheckIntervalSeconds

The number of seconds that defines the frequency of this server's self-health monitoring. The server monitors the health of its subsystems every `HealthCheckIntervalSeconds` and changes the Server's overall state if required.

Type: integer/int32

Constraints: Has Default Value: 180, Minimum Value: 1, Maximum Value: 2147483647

healthCheckStartDelaySeconds

The number of seconds the Node Manager should wait before starting to monitor the server.

Type: integer/int32

Constraints: Has Default Value: 120, Minimum Value: 0, Maximum Value: 2147483647

hostsMigratableServices

Gets the hostsMigratableServices attribute of the ServerMBean object

Type: boolean

Constraints: Read Only, Has Default Value: true

httpTraceSupportEnabled

Returns the HttpTraceSupportEnabled value

Type: boolean

Constraints: Has Default Value: false

httpdEnabled

Whether or not HTTP support is enabled on the regular port or SSL port.

Type: boolean

Constraints: Has Default Value: true

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

idleConnectionTimeout

The maximum number of seconds that a connection is allowed to be idle before it is closed by the server. The T3 and T3S protocols ignore this attribute. If you configure network channels for this server, each channel can override this idle connection message timeout.

This timeout helps guard against server deadlock through too many open connections.

Type: integer/int32

Constraints: Has Secure Value: 65, Has Default Value: 65, Minimum Value: 0

idlePeriodsUntilTimeout

The number of idle periods until peer is considered unreachable.

Type: integer/int32

Constraints: Has Default Value: 4, Minimum Value: 4, Maximum Value: 65534

ignoreSessionsDuringShutdown

Indicates whether a graceful shutdown operation drops all HTTP sessions immediately.

If this is set to `false`, a graceful shutdown operation waits for HTTP sessions to complete or timeout.

Type: boolean

Constraints: Has Default Value: false

instrumentStackTraceEnabled

Specifies whether the server returns stack traces for RMI calls that generate exceptions.

With RMI stack tracking enabled, if a client issues an RMI call to a server subsystem or to a module running within the server, and if the subsystem or module generates an exception that includes a stack trace, the server will return the exception as well as the stack trace. With it disabled, the server will return the exception without the stack trace details.

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: true

interfaceAddress

The IP address of the NIC that this server should use for multicast traffic.

Type: string

isolatePartitionThreadLocals

Specified whether the server needs to ensure that threadlocals storage from self-tuning thread pool threads must be cleaned up before the threads are used for processing work requests from a different partition. This helps ensure that no threadlocals from a different partition can be retrieved from work requests while being processed by a self-tuning thread pool thread. The different between this attribute and the `eagerThreadLocalCleanup` attribute is that threadlocals storage will not be cleared if the previous work request processed by the self-tuning thread pool thread was for the same partition, whereas with `eagerThreadLocalCleanup` set, the threadlocals storage will also be cleared in this case.

Type: boolean

Constraints: Has Default Value: false

javaCompiler

The Java compiler to use for all applications hosted on this server that need to compile Java code.

Type: string

Constraints: Has Secure Value: javac, Has Default Value: javac

javaCompilerPostClassPath

The options to append to the Java compiler classpath when compiling Java code.

Type: string

Constraints: Has Secure Value: null, Has Default Value: null

javaCompilerPreClassPath

The options to prepend to the Java compiler classpath when compiling Java code.

Type: string

Constraints: Has Secure Value: null, Has Default Value: null

javaStandardTrustKeyStorePassPhrase

The password for the Java Standard Trust keystore. This password is defined when the keystore is created.

If empty or null, then the keystore will be opened without a passphrase.

This attribute is only used if KeyStores is CUSTOM_IDENTITY_AND_JAVA_STANDARD_TRUST or DEMO_IDENTITY_AND_DEMO_TRUST.

When you get the value of this attribute, WebLogic Server does the following:

1. Retrieves the value of the `JavaStandardTrustKeyStorePassPhraseEncrypted` attribute.
2. Decrypts the value and returns the unencrypted password as a `String`.

When you set the value of this attribute, WebLogic Server does the following:

1. Encrypts the value.
2. Sets the value of the `JavaStandardTrustKeyStorePassPhraseEncrypted` attribute to the encrypted value.

Using this attribute (`JavaStandardTrustKeyStorePassPhrase`) is a potential security risk because the `String` object (which contains the unencrypted password) remains in the JVM's memory until garbage collection removes it and the memory is reallocated. Depending on how memory is allocated in the JVM, a significant amount of time could pass before this unencrypted data is removed from memory.

Instead of using this attribute, use `JavaStandardTrustKeyStorePassPhraseEncrypted`

Type: string

Constraints: Encrypted

keyStores

Which configuration rules should be used for finding the server's identity and trust keystores?

Type: string

Constraints: Has Default Value: `DemoIdentityAndDemoTrust`, Legal Values: `DemoIdentityAndDemoTrust`, `CustomIdentityAndJavaStandardTrust`, `CustomIdentityAndCustomTrust`, `CustomIdentityAndCommandLineTrust`

listenAddress

The IP address or DNS name this server uses to listen for incoming connections. For example, enter `12.34.5.67` or `mymachine`, respectively.

Note that the value you specify for the listen address is not the URL to the host machine and it does not include the communication protocol, listen port, or channel.

Servers can be reached through the following URL:

```
protocol://listen-address:listen-port
```

Any network channel that you configure for this server can override this listen address.

If a server's listen address is undefined, clients can reach the server through an IP address of the computer that hosts the server, a DNS name that resolves to the host, or the localhost string. The localhost string can be used only for requests from clients that are running on the same computer as the server.

If you want to limit the valid addresses for a server instance, specify one of the following:

- IP address. If you provide an IP address, clients can specify either the IP address or a DNS name that maps to the IP address. Clients that specify an IP address and attempt to connect through an SSL port must disable hostname verification.

- DNS name. If you provide a DNS name, clients can specify either the DNS name or the corresponding IP address.

Do not leave the listen address undefined on a computer that uses multiple IP address (a multihomed computer). On such a computer, the server will bind to all available IP addresses.

Note also that if you are using the demo certificates in a multi-server domain, Managed Server instances will fail to boot if you specify the fully-qualified DNS name. For information about this limitation and suggested workarounds, see "Limitation on CertGen Usage" in *Administering Security for Oracle WebLogic Server*

Type: string

listenPort

The default TCP port that this server uses to listen for regular (non-SSL) incoming connections.

Administrators must have the right privileges before binding to a port or else this operation will not be successful and it will render the console un-reachable.

If this port is disabled, the SSL port must be enabled. Additional ports can be configured using network channels. The cluster (multicast) port is configured separately.

Type: integer/int32

Constraints: Has Default Value: 7001, Minimum Value: 1, Maximum Value: 65535

listenPortEnabled

Specifies whether this server can be reached through the default plain-text (non-SSL) listen port.

If you disable this listen port, you must enable the default SSL listen port.

You can define additional listen ports for this server by configuring network channels.

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: true

listenThreadStartDelaySecs

Returns the maximum time that the server will wait for server sockets to bind before starting a listen thread.

Properties to consider for removal

Type: integer/int32

Constraints: Has Default Value: 60

listenersBindEarly

Determines whether the server should bind server sockets early.

Early binding detects port conflicts quickly and also gives user feedback on the default listen port as to the server state.

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

logRemoteExceptionsEnabled

Specifies whether the server message log includes exceptions that are raised in remote systems.

Type: boolean

Constraints: Has Secure Value: true, Has Default Value: false

loginTimeoutMillis

The login timeout for this server's default regular (non-SSL) listen port. This is the maximum amount of time allowed for a new connection to establish.

A value of `0` indicates there is no maximum.

Type: integer/int32

Constraints: Has Secure Value: 5000, Has Default Value: 5000, Minimum Value: 0, Maximum Value: 100000

machine

The WebLogic Server host computer (machine) on which this server is meant to run.

If you want to use Node Manager to start this server, you must assign the server to a machine and you must configure the machine for Node Manager.

You cannot change this value if a server instance is already running.

Type: weblogic.management.configuration.MachineMBean reference

Constraints: Restart Required

managedServerIndependenceEnabled

Specifies whether this Managed Server can be started when the Administration Server is unavailable.

In such a case, the Managed Server retrieves its configuration by reading a configuration file and other files directly.

Type: boolean

Constraints: Has Secure Value: true, Has Default Value: true

maxConcurrentLongRunningRequests

The maximum number of running long-running requests that can be submitted to all the Managed Executor Services or Managed Scheduled Executor Services in the server.

Type: integer/int32

Constraints: Has Default Value: 100, Minimum Value: 0, Maximum Value: 65534

maxConcurrentNewThreads

The maximum number of running threads that can be created by all the Managed Thread Factories in the server.

Type: integer/int32

Constraints: Has Default Value: 100, Minimum Value: 0, Maximum Value: 65534

maxMessageSize

The maximum number of bytes allowed in messages that are received over all supported protocols, unless overridden by a protocol-specific setting or a custom channel setting.

The order of precedence for setting message size maximums is as follows:

1. A channel-wide maximum in a custom network channel.
2. A protocol-specific setting in the default network channel.

See

- getMaxCOMMessageSize() getMaxCOMMessageSize
- getMaxHTTPMessageSize() getMaxHTTPMessageSize
- getMaxIIOPMessageSize() getMaxIIOPMessageSize
- getMaxT3MessageSize() getMaxT3MessageSize

3. The message maximum in this attribute.

This maximum message size helps guard against a denial of service attack in which a caller attempts to force the server to allocate more memory than is available thereby keeping the server from responding quickly to other requests.

A client can set this value using the `-Dweblogic.MaxMessageSize` property.

Type: integer/int32

Constraints: Has Secure Value: 10000000, Has Default Value: 10000000, Minimum Value: 4096, Maximum Value: 200000000

maxOpenSockCount

The maximum number of open sockets allowed in server at a given point of time.

When the maximum threshold is reached, the server stops accepting new requests until the number of sockets drops below the threshold.

A value less than `Integer.MAX_VALUE` indicates an unlimited size.

Type: integer/int32

Constraints: Has Default Value: -1, Minimum Value: -1, Maximum Value: 2147483647

messageIdPrefixEnabled

Indicates whether message IDs in logged messages will include a prefix. Message ids are 6 digit numeric strings that can be optionally presented in a log entry with a prefix. The prefix used by server messages is "BEA-".

Type: boolean

Constraints: Has Default Value: true

muxerClass

Non-blocking IO is enabled by default on the server side.

The default value is `weblogic.socket.NIOSocketMuxer`.

The Certicom SSL implementation is not supported with `NIOSocketMuxer`. If you need to secure internet communication, Oracle recommends enabling JSSE (Java Secure Socket Extension).

Type: string

name

An alphanumeric name for this server instance. (Spaces are not valid.)

The name must be unique for all configuration objects in the domain. Within a domain, each server, machine, cluster, JDBC connection pool, virtual host, and any other resource type must be named uniquely and must not use the same name as the domain.

For more information on server naming conventions, see Domain and Server Name Restrictions in Understanding Domain Configuration for Oracle WebLogic Server.

The server name is not used as part of the URL for applications that are deployed on the server. It is for your identification purposes only. The server name displays in the

Administration Console, and if you use WebLogic Server command-line utilities or APIs, you use this name to identify the server.

After you have created a server, you cannot change its name. Instead, clone the server and provide a new name for the clone.

Type: string

Constraints: Read Only

nativelOEnabled

Specifies whether native I/O is enabled for the server.

Type: boolean

Constraints: Has Default Value: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

numOfRetriesBeforeMSIMode

Get the number of retries to contact admin server, before starting in Managed Server Independence Mode

Type: integer/int32

Constraints: Has Default Value: 3, Minimum Value: 0, Maximum Value: 65534

outboundEnabled

Specifies whether new server-to-server connections may consider the default server channel when initiating a connection. This is only relevant if the connection needs to be bound to the default listen address. This will only work for binary protocols that support both outbound and inbound traffic.

When this feature is not enabled, connections are initiated using a local address selected by the underlying hardware. For the default channel this is usually what is wanted for IP-routing to be effective. Note that since the default is false, other outbound channels will be considered in preference to the default channel.

Default administration channels, created when the domain-wide administration port is turned on, are always considered and bound when initiating an administrative connection. To allow IP-routing for administration traffic create custom admin with `NetworkAccessPointMBean#isOutboundEnabled` set to false instead of enabling the domain-wide ADMIN port.

Type: boolean

Constraints: Has Default Value: false

outboundPrivateKeyEnabled

Specifies whether the SSL identity specified by `SSLMBean#getServerPrivateKeyAlias()` `getSSLMBean#ServerPrivateKeyAlias` for this server should be used for outbound SSL connections on the default server channel. In normal circumstances the outbound identity is determined by the caller's environment.

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

periodLength

The time interval in milliseconds of the heartbeat period. A value of 0 indicates that heartbeats are turned off.

Type: integer/int32

Constraints: Has Default Value: 60000, Minimum Value: 0

preferredSecondaryGroup

Defines secondary clustered instances considered for hosting replicas of the primary HTTP session states created on the server.

Type: string

printStackTraceInProduction

Specifies whether the server message log includes exception stack trace that are raised in remote systems.

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

reliableDeliveryPolicy

The reliable delivery policy for web services.

Type: weblogic.management.configuration.WSReliableDeliveryPolicyMBean reference

Constraints: Restart Required

replicationGroup

Defines preferred clustered instances considered for hosting replicas of the primary HTTP session states created on the server.

Type: string

replicationPorts

When WLS is running on Exalogic machines, cluster replication traffic could go over multiple replication channels. However multiple replication channels need not be configured on each clustered server instance. Only one replication channel with explicit IP-Address needs to be configured for each server and replicationPorts range can be specified for each server. For eg. range 7001-7010 will create 10 replication channels with ports 7001 to 7010 for the given server. These channels inherits all the properties of the configured replication channel except the listen port. Names of these channels will be derived from the configured replication channel with suffix {x} added where x could be 1,2.. as per the number of ports specified. Public ports are same as the listen port for these additional channels.

Type: string

resolveDNSName

Resolve the listen address to use for all T3 communication

Type: boolean

Constraints: Has Default Value: false

restartDelaySeconds

The number of seconds the Node Manager should wait before restarting this server.

After killing a server process, the system might need several seconds to release the TCP port(s) the server was using. If Node Manager attempts to restart the Managed Server while its ports are still active, the startup attempt fails.

If AutoMigration is enabled and RestartDelaySeconds is 0, the RestartDelaySeconds is automatically set to the lease time. This prevents the server from failing to restart after migration when the previous lease is still valid.

Type: integer/int32

Constraints: Has Default Value: 0, Minimum Value: 0, Maximum Value: 2147483647

restartIntervalSeconds

The number of seconds during which this server can be restarted, up to the number of times specified in RestartMax.

Type: integer/int32

Constraints: Has Default Value: 3600, Minimum Value: 300, Maximum Value: 2147483647

restartMax

The number of times that the Node Manager can restart this server within the interval specified in RestartIntervalSeconds.

Type: integer/int32

Constraints: Has Default Value: 2, Minimum Value: 0, Maximum Value: 2147483647

retryIntervalBeforeMSIMode

Get the number of seconds between the retries to contact admin server, before starting in Managed Server Independence Mode

Type: integer/int32

Constraints: Has Default Value: 5, Minimum Value: 1, Maximum Value: 65534

reverseDNSAllowed

Specifies whether the kernel is allowed to perform reverse DNS lookups.

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

scatteredReadsEnabled

Enables scattered reads over NIO socket channels. Enabling this attribute increases efficiency during I/O in environments with high network throughput and should be used only when configuring a WebLogic domain for Oracle Exalogic.

Type: boolean

Constraints: Has Default Value: false

serverLifeCycleTimeoutVal

Number of seconds a force shutdown operation waits before timing out and killing itself. If the operation does not complete within the configured timeout seconds, the server will shutdown automatically if the state of the server at that time was SHUTTING_DOWN

A value of means that the server will wait indefinitely for life cycle operation to complete.

Type: integer/int32

Constraints: Has Secure Value: 120, Has Default Value: 30, Has Production Mode Default Value: 120, Minimum Value: 0

serverTemplate

The template used to configure this server.

Type: weblogic.management.configuration.ServerTemplateMBean reference

Constraints: Restart Required

sitConfigPollingInterval

Returns the current polling interval for finding the situational config file in the filesystem

Type: integer/int32

Constraints: Has Default Value: 5, Minimum Value: 1, Maximum Value: 65534

socketBufferSizeAsChunkSize

Specifies whether the server's buffer size for sending or receiving data through a raw socket should be set to 4KB.

Otherwise, the server does not impose a limit to the buffer size and defers to the operating system. This option is useful only on some operating systems for improving performance. It should be disabled in most environments.

Type: boolean

Constraints: Has Default Value: false

socketReaders

The number of socket reader threads.

Type: integer/int32

Constraints: Has Default Value: -1, Minimum Value: -1, Maximum Value: 65534

stagingDirectoryName

The directory path on the Managed Server where all staged (prepared) applications are placed.

If an absolute directory name is not specified, the path is relative to the root directory "/". Once configured, you cannot change the staging directory name. Remove all applications from the server prior to changing this attribute. The default staging directory is "stage", relative to the server root.

Type: string

stagingMode

The mode that specifies whether an application's files are copied from a source on the Administration Server to the Managed Server's staging area during application preparation.

During application preparation, the application's files are copied from the source on the Administration Server to the Managed Server's staging area. If you specify `nostage` or `external_stage`, the copy will not occur. This is useful when the staging area is a shared directory, already containing the application files, or if this is a single server domain. The administrator must ensure that the Managed Server's staging directory is set appropriately. Deployment errors will result if the application is not available during the preparation or activation of the application. Each application can override the staging mode specified here.

Type: string

Constraints: Legal Values: stage, nostage, external_stage

startupMode

The state in which this server should be started. If you specify `STANDBY`, you must also enable the domain-wide administration port.

In the `RUNNING` state, a server offers its services to clients and can operate as a full member of a cluster. In the `ADMIN` state, the server is up and running, but available only for administration operations, allowing you to perform server and application-level administration tasks without risk to running applications. In the `STANDBY` state, a server instance does not process any request; its regular Listen Port is closed. The Administration Port is open. It only accepts life cycle commands that transition the server instance to either the `RUNNING` or the `SHUTDOWN` state. Other Administration requests are not accepted. A `STANDBY` server's only purpose is to resume into the `RUNNING` state quickly; it saves server startup time.

Type: string

Constraints: Has Default Value: `RUNNING`

startupTimeout

Timeout value for server start and resume operations. If the server fails to start in the timeout period, it will force shutdown.

A value of `means` that the server will wait indefinitely for the operation to complete.

Type: integer/int32

Constraints: Has Default Value: 0, Has Production Mode Default Value: 0, Minimum Value: 0

stuckThreadTimerInterval

The number of seconds after which WebLogic Server periodically scans threads to see if they have been continually working for the configured maximum length of time.

Type: integer/int32

Constraints: Has Default Value: 60, Minimum Value: 0, Maximum Value: 2147483647

tags

Return all tags on this Configuration MBean

Type: array of string

threadPoolPercentSocketReaders

The percentage of execute threads from the default queue that can be used as socket readers.

Type: integer/int32

Constraints: Has Default Value: 33, Minimum Value: 1, Maximum Value: 99

transactionLogFilePrefix

The path prefix for the server's JTA transaction log files. If the pathname is not absolute, the path is assumed to be relative to the server's root directory.

For a clustered server, if you plan to be able to migrate the Transaction Recovery Service from this server if it fails to another server (backup server) in the same cluster, you must store transaction log files on persistent storage, such as a Storage Area Network (SAN) device or a dual-ported disk, available to both servers.

Do not use an NFS file system to store transaction log files. Because of the caching scheme in NFS, transaction log files on disk may not always be current. Using transaction log files stored on an NFS device for recovery may cause data corruption.

Type: string

Constraints: Has Default Value: ./

transactionLogFileWritePolicy

The policy that determines how transaction log file entries are written to disk. This policy can affect transaction performance. (Note: To be transactionally safe, the Direct-Write policy may require additional OS or environment changes on some Windows systems.)

WebLogic Server supports the following policies:

- Cache-Flush. Flushes operating system and on-disk caches after each write.
- Direct-Write. Tells the operating system to write directly to disk with each write. Direct-Write performs better than Cache-Flush.

If Direct-Write is not supported on the host platform, the policy becomes Cache-Flush and a log message is printed.

Note: On Windows, the "Direct-Write" policy may leave transaction data in the on-disk cache without writing it to disk immediately. This is not transactionally safe because a power failure can cause loss of on-disk cache data. For transactionally safe writes using "Direct-Write" on Windows, either disable all write caching for the disk (enabled by default), or use a disk with a battery-backed cache.

The on-disk cache for a hard-drive on Windows can be disabled through system administration: Control-Panel -> System -> Hardware-tab -> Device-Manager-button -> Disk-Drives -> name-of-drive -> Policies-tab -> "Enable write caching on the disk" check-box. Some file systems do not allow this value to be changed. For example, a RAID system that has a reliable cache.

Type: string

Constraints: Has Default Value: Direct-Write, Legal Values: Cache-Flush, Direct-Write, Legal Null: true

tunnelingClientPingSecs

The interval (in seconds) at which to ping a tunneled client to see if it is still alive.

If you create network channels for this server, each channel can override this setting.

Type: integer/int32

Constraints: Has Default Value: 45, Minimum Value: 1

tunnelingClientTimeoutSecs

The amount of time (in seconds) after which a missing tunneled client is considered dead.

If you create network channels for this server, each channel can override this setting.

Type: integer/int32

Constraints: Has Default Value: 40, Minimum Value: 1

tunnelingEnabled

Specifies whether tunneling for the T3, T3S, HTTP, HTTPS, IIOP, and IIOPS protocols should be enabled for this server.

If you create network channels for this server, each channel can override this setting.

Type: boolean

Constraints: Has Default Value: false

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

uploadDirectoryName

The directory path on the Administration Server where all uploaded applications are placed.

If an absolute directory name is not specified, the path is relative to the root directory "/". The default staging directory is "stage", relative to the server root. On the Managed Server this returns null, and is not configurable.

Type: string

Constraints: Has Recommended Secure Value: An absolute directory that is outside the root directory of any WebLogic Server instance or application, and that resides on a physical disk that is separate from the WebLogic Server host's system disk.

use81StyleExecuteQueues

Backward compatibility mode to switch to 8.1 execute queues instead of WorkManagers. Each of the WorkManagers is converted to an individual execute queue. Setting this attribute requires a server restart.

Type: boolean

Constraints: Has Default Value: false

useConcurrentQueueForRequestManager

Reduces lock contention by using concurrent buffer queue to park incoming requests. Enabling this attribute increases throughput as requests are scheduled without acquiring any locks.

Type: boolean

useDetailedThreadName

Specifies whether to include detailed information in self-tuning thread pool thread names. Setting this flag as true would include additional information, such as the name of the Work Manager for which the execute thread is executing the task, but at the expense of overhead in keeping the thread name updated with such information.

Type: boolean

Constraints: Has Default Value: false

useEnhancedIncrementAdvisor

Specifies whether self-tuning should use the enhanced IncrementAdvisor implementation that uses a different algorithm to adjust the size of the self-tuning thread pool.

Type: boolean

Constraints: Has Default Value: true

useEnhancedPriorityQueueForRequestManager

Reduces lock contention by using the enhanced ConcurrentCalendarQueue as the priority based queue for pending requests that are waiting for a thread.

This attribute should be enabled only in an Oracle Exalogic environment.

Type: boolean

Constraints: Has Default Value: false

useFusionForLLR

Enables the use of the `ADM_DDL` store procedure for LLR. The default value is `false` (not enabled).

When enabled, a `WLS_` prefix and `_DYD` suffix is automatically added to the LLR table name at runtime so the LLR table name in server configuration is not consistent with the actual table name in database.

Type: boolean

weblogicPluginEnabled

Specifies whether this server uses the proprietary `WL-Proxy-Client-IP` header.

Set this attribute to `true` to specify that this server instance uses the proprietary `WL-Proxy-Client-IP` header, which is recommended if the server instance will receive requests from a proxy plug-in. If the server instance is a member of a cluster that will receive proxied requests, enable the WebLogic plug-in at the cluster level. For servers that are members of a cluster, the setting at the cluster level overrides the server's setting. When the WebLogic plug-in is enabled at the cluster level, a call to `getRemoteAddr` will return the address of the browser client from the proprietary `WL-Proxy-Client-IP` header instead of the Web server.

Set this attribute to `false` to disable the `weblogic-plugin-enabled` parameter, `weblogic-plugin-enabled=false`, in the `config.xml` file.

Note: If you are using Oracle HTTP Server, the WebLogic Proxy Plug-In, or Oracle Traffic Director to distribute client requests to a Managed Server or a cluster, Oracle recommends setting this attribute to `true`

Type: boolean

Constraints: Has Default Value: false

weblogic.management.configuration.ServerStartMBean

This bean is used to configure the attributes necessary to start up a server on a remote machine.

The properties of the `weblogic.management.configuration.ServerStartMBean` entity are as follows:

MWHome

The `MWHome` directory (path on the machine running Node Manager) to use when starting this server.

Specify the directory on the Node Manager machine under which all of Oracle's Middleware products were installed. For example, `c:\bea`

This value can also be specified conveniently in the `nodemanager.properties` file using the `weblogic.startup.MWHome` property.

Node Manager does not pass this value to start scripts. It does specify `-Dbea.home` when invoking a Java command line to start the server.

Type: string

arguments

The arguments to use when starting this server.

These are the first arguments appended immediately after `java` portion of the startup command. For example, you can set Java heap memory or specify any `weblogic.Server` option.

This property should not be used to specify `weblogic.management.username` or `weblogic.management.password` as these values will be ignored during server startup. Instead the username and password properties should be set. This will also enable Node Manager to properly encrypt these values on the Managed Server's machine.

Separate arguments with a space.

This value can also be specified conveniently in the `nodemanager.properties` file using the `weblogic.startup.Arguments` property. Node Manager will pass this value to a start script using the `JAVA_OPTIONS` environment variable. When issuing a Java command line to start the server, Node Manager will pass the arguments as options.

Type: string

classPath

The classpath (path on the machine running Node Manager) to use when starting this server.

At a minimum you will need to specify the following values for the class path option:
`WL_HOME/server/lib/weblogic_sp.jar;WL_HOME/server/lib/weblogic.jar`

where `WL_HOME` is the directory in which you installed WebLogic Server on the Node Manager machine.

The shell environment determines which character you use to separate path elements. On Windows, you typically use a semicolon (;). In a BASH shell, you typically use a colon (:).

This value can also be specified conveniently in the `nodemanager.properties` file using the `weblogic.startup.ClassPath` property. Node Manager will pass this value to a start script using the `CLASSPATH` environment variable. When issuing a Java command line to start the server, Node Manager will pass `-Djava.class.path`.

Type: string

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to `config.xml`

Type: boolean

Constraints: Read Only, Has Default Value: false

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

javaHome

The Java home directory (path on the machine running Node Manager) to use when starting this server.

Specify the parent directory of the JDK's bin directory. For example, `c:\bea\jdk141`

This value can also be specified conveniently in the nodemanager .properties file using the `weblogic.startup.JavaHome` or `property`.

Node Manager will pass this value to a start script using the `JAVA_HOME` environment variable. When issuing a Java command line to start the server, Node Manager will use the Java executable from the specified location.

Type: string

javaVendor

The Java Vendor value to use when starting this server.

If the server is part of a cluster and configured for automatic migration across possibly different platforms with different vendors providing the JDKs, then, both `JavaVendor` and `JavaHome` should be set in the generated configuration file instead.

This value can also be specified conveniently in the nodemanager .properties file using the `weblogic.startup.JavaVendor` property.

Node Manager does not pass this value invoking a Java command line to start the server. It does pass this value in the environment variable `JAVA_VENDOR` to the start script.

Type: string

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's

`javax.management.ObjectName`

`Name=user-specified-name`

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

password

The password of the username used to boot the server and perform server health monitoring.

As of 8.1 sp4, when you get the value of this attribute, WebLogic Server does the following:

1. Retrieves the value of the `PasswordEncrypted` attribute.
2. Decrypts the value and returns the unencrypted password as a String.

When you set the value of this attribute, WebLogic Server does the following:

1. Encrypts the value.

2. Sets the value of the `PasswordEncrypted` attribute to the encrypted value.

Using this attribute (`Password`) is a potential security risk because the `String` object (which contains the unencrypted password) remains in the JVM's memory until garbage collection removes it and the memory is reallocated. Depending on how memory is allocated in the JVM, a significant amount of time could pass before this unencrypted data is removed from memory.

Instead of using this attribute, use `PasswordEncrypted`

Type: string

Constraints: Encrypted

rootDirectory

The directory that this server uses as its root directory. This directory must be on the computer that hosts Node Manager. If you do not specify a Root Directory value, the domain directory is used by default.

Type: string

securityPolicyFile

The security policy file (directory and filename on the machine running Node Manager) to use when starting this server.

This value can also be specified conveniently in the `nodemanager.properties` file using the `weblogic.startup.SecurityPolicyFile` property .

When Node Manager is using a start script, the security policy file will be defined in an environment variable, `SECURITY_POLICY`. Additionally, when Node Manager is launching the process directly using a Java command, the security policy file will be defined with `-Djava.security.policy=`

Type: string

tags

Return all tags on this Configuration MBean

Type: array of string

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

username

The user name to use when booting this server.

The Administration Console inserts the user name that you supplied when you logged in to the console. The Domain Configuration Wizard inserts the user name that you defined when you created the domain.

Type: string

Constraints: Has Default Value:

weblogic.management.configuration.ServerTemplateMBean

This class represents a WebLogic Server. A WebLogic Server is a Java process that is a container for Java EE applications.

The properties of the `weblogic.management.configuration.ServerTemplateMBean` entity are as follows:

DGCIdlePeriodsUntilTimeout

The number of idle periods allowed before the object is collected.

Type: integer/int32

Constraints: Has Default Value: 5

IIOPEnabled

Specifies whether this server has IIOP support enabled for both the regular (non-SSL) and SSL ports.

Type: boolean

Constraints: Has Default Value: true

JDBCLLRTableName

The table name for this server's Logging Last Resource (LLR) database table(s). WebLogic Server creates the table(s) and then uses them during transaction processing for the LLR transaction optimization. This setting must be unique for each server. The default table name is `WL_LLRSERVERNAME`

This setting only applies if this server hosts one or more LLR-enabled JDBC data sources.

The format for the tables that WebLogic Server creates is `[[[catalog.]schema.]name.]` Each "." in the table name is significant, and schema generally corresponds to username in many databases.

IMPORTANT: If this value is changed but the LLR table already exists in the database, you must preserve the existing table's data. Consequently, when changing the table name, the existing database table must be renamed by a database administrator to match the new configured table name. Otherwise, transaction records may be lost, resulting in heuristic failures that aren't logged.

IMPORTANT: Each server's table name must be unique. Multiple LLR-enabled data sources within the same server may share the same table, but multiple servers must not share the same table. If multiple same-named servers share a table, the behavior is undefined and it is likely that transactions will not recover properly after a crash, creating heuristic hazards.

Type: string

JDBCLoginTimeoutSeconds

The JDBC Login Timeout value. Specified value is passed into `java.sql.DriverManager.setLoginTimeout()`. Note that this `DriverManager` setting will impact **all** JDBC drivers loaded into this JVM. Feature is disabled by default.

Type: integer/int32

Constraints: Has Default Value: 0, Minimum Value: 0, Maximum Value: 300

JMSConnectionFactoryUnmappedResRefMode

Use this unmapped resource reference mode to specify the behavior of any resource reference to a Connection Factory when the resource reference does not directly specify a JNDI name by a lookup attribute, or by a mappedName attribute, or by a jndi-name in a descriptor file. If a JNDI name is specified, the resource reference either resolves to the specified object in the JNDI tree or generates a `javax.naming.NameNotFoundException`.

Following are the available unmapped resource reference modes:

- **FailSafe** : In this mode, an application JMS connection factory resource reference that does not specify a JNDI name resolves to an object bound to the JNDI tree with the same name as the resource reference name if one can be found in JNDI tree. Otherwise, it throws a `javax.naming.NameNotFoundException`. A resource reference without a JNDI name never returns a Java EE 7 Default Connection Factory in this mode.

This mode yields pre-12.2.1 WebLogic Server behavior. This mode is Java EE compliant, but the Java EE 7 specification disallows it from being the default mode.

- **ReturnDefault** : This policy is a Java EE compliant mode and it is the default mode. It complies with Java EE 7 while doing a best effort to try delivering FailSafe behavior when it is expected.

(a) If the resource reference name matches the local JNDI name of a configured foreign JMS provider mapping, then WebLogic Server returns the remote JNDI entry from the mapping if it can be resolved, or it throws a `javax.naming.NameNotFoundException`.

(b) If the resource reference does not match with a foreign JMS provider mapping, and if the resource reference name matches the name of an object that is already bound to the JNDI tree, WebLogic Server returns the JNDI tree object.

(c) If neither (a) nor (b) apply, then WebLogic Server returns `"java:comp/DefaultJMSConnectionFactory"`. In addition, it adds an 'Info' message in the server log indicating that a special behavior has occurred. This log message will occur at most once per application per server boot.

Type: string

Constraints: Has Default Value: ReturnDefault, Legal Values: ReturnDefault, FailSafe

JMSDefaultConnectionFactoriesEnabled

Specifies whether this server uses JMS default connection factories.

WebLogic Server provides the following JMS default connection factories:

- `weblogic.jms.ConnectionFactory`
- `weblogic.jms.XAConnectionFactory` An XA factory is required for JMS applications to use JTA user-transactions, but is not required for transacted sessions. All other preconfigured attributes for the default connection factories are set to the same default values as a user-defined connection factory. If the preconfigured settings of the default factories are appropriate for your application, you do not need to configure any additional factories for your application.

Note: When using the default connection factories, you have no control over targeting the WebLogic Server instances where the connection factory may be deployed. However, you can disable the default connection factories on a per-server basis. To deploy a connection factory on independent servers, on specific servers within a cluster, or on an entire cluster, you need to configure a connection factory and specify the appropriate server targets. The default Java EE 7 JMS Connection Factory, `java:comp/DefaultJMSConnectionFactory`, will be available even when the WebLogic JMS default connection factories are disabled.

Type: boolean

Constraints: Has Default Value: true

JNDITransportableObjectFactoryList

List of factories that create transportable objects.

Type: array of string

TGIOPEnabled

Specifies whether this server supports Tuxedo GIOP (TGIOPEnabled) requests. (Requires you to configure WebLogic Tuxedo Connector (WTC) for this server.)

Type: boolean

Constraints: Has Secure Value: true, Has Default Value: true

XMLEntityCache

The server's XML entity cache, which is used to configure the behavior of JAXP (Java API for XML Parsing).

Type: weblogic.management.configuration.XMLEntityCacheMBean reference

Constraints: Restart Required

XMLRegistry

The server's XML registry, which is used to configure the behavior of JAXP (Java API for XML Parsing).

Type: weblogic.management.configuration.XMLRegistryMBean reference

Constraints: Restart Required

acceptBacklog

The number of backlogged, new TCP connection requests that should be allowed for this server's regular and SSL ports.

Setting the backlog to may prevent this server from accepting any incoming connection on some operating systems.

Type: integer/int32

Constraints: Has Default Value: 300, Minimum Value: 0

addWorkManagerThreadsByCpuCount

Enables increased efficiency of the self-tuning thread pool by aligning it with the Exalogic processor architecture threading capabilities. Use only when configuring a WebLogic domain for Oracle Exalogic.

- Enabling this attribute increases efficiency during I/O in environments with high network throughput.
- Disabling this attribute allows the thread pool to self-tune to match the demand of the workload at the expense of longer ramp up time.

Type: boolean

adminReconnectIntervalSeconds

The number of seconds between reconnection attempts to the admin server. When the admin server fails the managed server will periodically try to connect back to it.

Type: integer/int32

Constraints: Has Default Value: 10, Minimum Value: 0, Maximum Value: 2147483647

administrationPort

The secure administration port for the server. This port requires that you enable the domain's administration port and that SSL is configured and enabled.

By default, the server uses the administration port that is specified at the domain level. To override the domain-level administration port for the current server instance, set this server's administration port.

Type: integer/int32

Constraints: Has Recommended Secure Value: 7002, Minimum Value: 0, Maximum Value: 65535

administrationProtocol

Returns the protocol to be used for administrative connections when none is specified.

Type: string

Constraints: Legal Values: t3s, https, iiops, t3, http, iiop

allowShrinkingPriorityRequestQueue

Specifies whether self-tuning should allow shrinking of its priority based queue for pending requests after it has grown in size due to busy workload, and whether it should try to purge work requests that have already been picked up for processing due to minimum threads constraints before growing the queue. Setting this to true would help reduce memory footprint after the busy work period has ended, at the expense of the overhead of growing the request queue again at the next period of busy workload. It would also help to reduce the amount of memory allocated for the request queue, at the expense of the overhead required in purging already processed work requests from the queue.

Type: boolean

Constraints: Has Default Value: true

autoMigrationEnabled

Specifies whether Node Manager can automatically restart this server and its services on another machine if the server fails.

Type: boolean

autoRestart

Specifies whether the Node Manager can automatically restart this server if it crashes or otherwise goes down unexpectedly.

Type: boolean

Constraints: Has Default Value: true

buzzAddress

Buzz endpoint address.

Type: string

buzzEnabled

Enables Buzz for sending/receiving messages with peers. Enabling this attribute increases efficiency during I/O in environments with high network throughput and should be used only when configuring a WebLogic domain for Oracle Exalogic.

Type: boolean

Constraints: Has Default Value: false

buzzPort

Buzz endpoint port.

A value of means system-allocated (dynamic) port.

Type: integer/int32

Constraints: Has Default Value: 0

candidateMachines

Limits the list of candidate machines that the cluster specifies. (Requires you to enable this server for automatic migration and to configure the cluster with a set of candidate machines.)

If this server fails and if it is enabled for automatic migration, Node Manager automatically restarts it. By default, Node Manager restarts the server on any of the candidate machines that the cluster specifies (in order of preference that you configured in the cluster). To change the default, you use this server's list of candidate machines to create a subset of the cluster-wide candidates. You can also change the order of preference.

Type: array of weblogic.management.configuration.MachineMBean references

Constraints: Restart Required

classpathServletDisabled

The ClasspathServlet will serve any class file in the classpath and is registered by default in every Web application (including management). It does not need to be turned on for many applications though, and represents a security hole if unchecked.

WLS components such as JDBC and JMS rely on the ClasspathServlet. If the servlet can not be disabled, then set the ClassPathServletSecureModeEnabled to true.

Type: boolean

Constraints: Has Recommended Secure Value: true, Has Default Value: false

classpathServletSecureModeEnabled

If secure mode is enabled, the ClasspathServlet will serve only class files from wellknown packages required for JDBC and JMS functionality. If secure mode is disabled, it represents a security hole if unchecked as the ClassPatchServlet will serve any class in the classpath and is registered by default in every Web application (including management).

If set to true, the ClasspathServlet will not be disabled by the DefaultInternalServletsDisabled value of true.

Type: boolean

Constraints: Has Secure Value: true, Has Default Value: false

clientCertProxyEnabled

Specifies whether the HttpClusterServlet proxies the client certificate in a special header.

By default (or if you specify *false*), the `weblogic.xml` deployment descriptor for each web application that is deployed on this server determines whether the web application trusts certificates sent from the proxy server plugin. By default (or if the deployment descriptor specifies *false*), users cannot log in to the web application from a proxy server plugin.

A value of *true* causes proxy-server plugins to pass identity certifications from clients to all web applications that are deployed on this server instance. A proxy-server plugin encodes each identify certification in the `WL-Proxy-Client-Cert` header and passes the header to WebLogic Server instances. A WebLogic Server instance takes the certificate information from the header, trusting that it came from a secure source, and uses that information to authenticate the user.

If you specify `true`, use a `weblogic.security.net.ConnectionFilter` to ensure that this WebLogic Server instance accepts connections only from the machine on which the proxy-server plugin is running. Specifying `true` without using a connection filter creates a security vulnerability because the `WL-Proxy-Client-Cert` header can be spoofed.

A cluster can also specify whether the `HttpClusterServlet` proxies the client certificate in a special header. The cluster-level setting overrides the setting in individual servers that are part of the cluster.

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

cluster

The cluster, or group of WebLogic Server instances, to which this server belongs.

If set, the server will listen for cluster multicast events.

Type: `weblogic.management.configuration.ClusterMBean` reference

Constraints: Restart Required

clusterWeight

The proportion of the load that this server will bear, relative to other servers in a cluster.

If all servers have the default weight or the same weight, each bears an equal proportion of the load. If one server has weight 50 and all other servers have weight 100, the 50-weight server will bear half as much load as any other server.

Type: integer/int32

Constraints: Has Default Value: 100, Minimum Value: 1, Maximum Value: 100

coherenceClusterSystemResource

The system-level Coherence cluster resource associated with this server.

Type: `weblogic.management.configuration.CoherenceClusterSystemResourceMBean` reference

Constraints: Restart Required

completeMessageTimeout

The maximum number of seconds that this server waits for a complete message to be received. If you configure network channels for this server, each channel can override this message timeout.

This timeout helps guard against a denial of service attack in which a caller indicates that it will be sending a message of a certain size which it never finishes sending.

`CompleteMessageTimeout` affects the HTTP Response, such that if WebLogic Server discovers sockets inactive for longer than the `CompleteMessageTimeout`, the server will close these sockets.

Type: integer/int32

Constraints: Has Default Value: 60, Minimum Value: 0, Maximum Value: 480

completeWriteTimeout

The maximum number of seconds that this server waits for a complete HTTP response to be sent.

A value of `disables` the complete write timeout. The default value is derived from the `CompleteHTTPMessageTimeout`. If it is `-1`, then the `CompleteMessageTimeout` value is used for the default value.

Type: integer/int32

Constraints: Minimum Value: 0

connectTimeout

The amount of time that this server should wait to establish an outbound socket connection before timing out. A value of `disables` server connect timeout.

Type: integer/int32

Constraints: Has Default Value: 0, Minimum Value: 0, Maximum Value: 240

customIdentityKeyStoreFileName

The source of the identity keystore. For a JKS keystore, the source is the path and file name. For an Oracle Key Store Service (KSS) keystore, the source is the KSS URI.

If using a JKS keystore, the keystore path name must either be absolute or relative to where the server was booted.

If using a KSS keystore, the keystore URI must be of the form:

```
kss://system/keystorename
```

where *keystorename* is the name of the keystore registered in KSS.

The value in this attribute is only used if `KeyStores` is `CUSTOM_IDENTITY_AND_JAVA_STANDARD_TRUST`, `CUSTOM_IDENTITY_AND_CUSTOM_TRUST` or `CUSTOM_IDENTITY_AND_COMMAND_LINE_TRUST`

Type: string

Constraints: Has Default Value: null

customIdentityKeyStorePassPhrase

The encrypted custom identity keystore's passphrase. If empty or null, then the keystore will be opened without a passphrase.

This attribute is only used if `KeyStores` is `CUSTOM_IDENTITY_AND_JAVA_STANDARD_TRUST`, `CUSTOM_IDENTITY_AND_CUSTOM_TRUST` or `CUSTOM_IDENTITY_AND_COMMAND_LINE_TRUST`

When you get the value of this attribute, WebLogic Server does the following:

1. Retrieves the value of the `CustomIdentityKeyStorePassPhraseEncrypted` attribute.
2. Decrypts the value and returns the unencrypted password as a String.

When you set the value of this attribute, WebLogic Server does the following:

1. Encrypts the value.
2. Sets the value of the `CustomIdentityKeyStorePassPhraseEncrypted` attribute to the encrypted value.

Using this attribute (`CustomIdentityKeyStorePassPhrase`) is a potential security risk because the String object (which contains the unencrypted password) remains in the JVM's memory until garbage collection removes it and the memory is reallocated. Depending on how memory is allocated in the JVM, a significant amount of time could pass before this unencrypted data is removed from memory.

Instead of using this attribute, use `CustomIdentityKeyStorePassPhraseEncrypted`

Type: string

Constraints: Encrypted

customIdentityKeyStoreType

The type of the keystore. Generally, this is JKS. If using the Oracle Key Store Service, this would be KSS

If empty or null, then the JDK's default keystore type (specified in `java.security`) is used. The custom identity key store type is only used if `KeyStores` is `CUSTOM_IDENTITY_AND_JAVA_STANDARD_TRUST`, `CUSTOM_IDENTITY_AND_CUSTOM_TRUST` or `CUSTOM_IDENTITY_AND_COMMAND_LINE_TRUST`

Type: string

Constraints: Has Default Value: null

customTrustKeyStoreFileName

The source of the custom trust keystore. For a JKS keystore, the source is the path and file name. For an Oracle Key Store Service (KSS) keystore, the source is the KSS URI.

If using a JKS keystore, the keystore path name must either be absolute or relative to where the server was booted.

If using a KSS keystore, the keystore URI must be of the form:

```
kss://system/keystorename
```

where *keystorename* is the name of the keystore registered in KSS.

The value in this attribute is only used if `KeyStores` is `CUSTOM_IDENTITY_AND_CUSTOM_TRUST`

Type: string

Constraints: Has Default Value: null

customTrustKeyStorePassPhrase

The custom trust keystore's passphrase. If empty or null, then the keystore will be opened without a passphrase.

This attribute is only used if `KeyStores` is `CUSTOM_IDENTITY_AND_CUSTOM_TRUST`.

When you get the value of this attribute, WebLogic Server does the following:

1. Retrieves the value of the `CustomTrustKeyStorePassPhraseEncrypted` attribute.
2. Decrypts the value and returns the unencrypted password as a String.

When you set the value of this attribute, WebLogic Server does the following:

1. Encrypts the value.
2. Sets the value of the `CustomTrustKeyStorePassPhraseEncrypted` attribute to the encrypted value.

Using this attribute (`CustomTrustKeyStorePassPhrase`) is a potential security risk because the String object (which contains the unencrypted password) remains in the JVM's memory until garbage collection removes it and the memory is reallocated. Depending on how memory is allocated in the JVM, a significant amount of time could pass before this unencrypted data is removed from memory.

Instead of using this attribute, use `CustomTrustKeyStorePassPhraseEncrypted`

Type: string

Constraints: Encrypted

customTrustKeyStoreType

The type of the keystore. Generally, this is `JKS`. If using the Oracle Key Store Service, this would be `KSS`

If empty or null, then the JDK's default keystore type (specified in `java.security`) is used. This keystore type is only used if `KeyStores` is `CUSTOM_IDENTITY_AND_CUSTOM_TRUST`.

Type: string

Constraints: Has Default Value: null

defaultIIOPPassword

The password for the default IIOP user. (Requires you to enable IIOP.)

As of 8.1 sp4, when you get the value of this attribute, WebLogic Server does the following:

1. Retrieves the value of the `DefaultIIOPPasswordEncrypted` attribute.
2. Decrypts the value and returns the unencrypted password as a `String`.

Using this attribute (`DefaultIIOPPassword`) is a potential security risk because the `String` object (which contains the unencrypted password) remains in the JVM's memory until garbage collection removes it and the memory is reallocated. Depending on how memory is allocated in the JVM, a significant amount of time could pass before this unencrypted data is removed from memory.

Instead of using this attribute, use `DefaultIIOPPasswordEncrypted`

Type: string

Constraints: Encrypted, Has Default Value: null

defaultIIOPUser

The user name of the default IIOP user. (Requires you to enable IIOP.)

Type: string

Constraints: Has Default Value: null

defaultInternalServletsDisabled

Specifies whether all default servlets in the servlet engine are disabled.

This includes: `weblogic.servlet.ClasspathServlet`
`weblogic.servlet.utils.iiop.GetIORServlet` `weblogic.rjvm.http.TunnelSendServlet`
`weblogic.rjvm.http.TunnelRecvServlet` `weblogic.rjvm.http.TunnelLoginServlet`
`weblogic.rjvm.http.TunnelCloseServlet` If set to true, this property overrides the `ClasspathServletDisabled` property.

Type: boolean

Constraints: Has Secure Value: true, Has Default Value: false

defaultProtocol

The protocol to use for connections when none is specified.

Type: string

Constraints: Has Default Value: `t3`, Legal Values: `t3`, `t3s`, `http`, `https`, `iiop`, `iiops`

defaultSecureProtocol

The protocol to use for secure connections when none is specified.

Type: string

Constraints: Has Default Value: t3s, Legal Values: t3s, https, iiops

defaultTGIOPPassword

The password for the default user associated with the Tuxedo GIOP (TGIOP) protocol. (Requires you to configure WebLogic Tuxedo Connector (WTC) for this server.)

As of 8.1 sp4, when you get the value of this attribute, WebLogic Server does the following:

1. Retrieves the value of the `DefaultTGIOPPasswordEncrypted` attribute.
2. Decrypts the value and returns the unencrypted password as a String.

When you set the value of this attribute, WebLogic Server does the following:

1. Encrypts the value.
2. Sets the value of the `DefaultTGIOPPasswordEncrypted` attribute to the encrypted value.

Using this attribute (`DefaultTGIOPPassword`) is a potential security risk in because the String object (which contains the unencrypted password) remains the JVM's memory until garbage collection removes it and the memory is reallocated. Depending on how memory is allocated in the JVM, a significant amount of time could pass before this unencrypted data is removed from memory.

Instead of using this attribute, use `DefaultTGIOPPasswordEncrypted`

Type: string

Constraints: Encrypted

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

eagerThreadLocalCleanup

Specifies whether to clean up all ThreadLocals storage from self-tuning thread pool threads after they have finished processing each work request. By default, the self-tuning thread pool only cleans up ThreadLocal storage in its threads after an application is undeployed to avoid ClassLoader memory leak.

Type: boolean

Constraints: Has Default Value: false

externalDNSName

The external IP address or DNS name for this server.

This address will be sent with HTTP session cookies and with dynamic server lists to HTTP proxies. It will also be used by external application clients to enable the propagation of RMI traffic through network address translating (NAT) firewalls.

You must specify an external DNS name for configurations in which a firewall is performing network address translation, unless clients are accessing WebLogic Server using t3 and the default channel. For example, define the external DNS name for configurations in which a firewall is performing network address translation, and clients are accessing WebLogic Server using HTTP via a proxy plug-in.

Type: string

Constraints: Has Default Value: null

extraEjbcOptions

The options passed to the EJB compiler during server-side generation.

Each EJB component can override the compiler options that you specify here. The following options are valid:

-forcegeneration

Forces generation of wrapper classes. Without this flag the classes may not be regenerated if it is determined to be unnecessary.

-disableHotCodeGen

Generate ejb stub and skel as part of ejbc. Avoid HotCodeGen to have better performance.

-keepgenerated

Keep the generated .java files.

-compiler javac

Java compiler to exec. If not specified, the -compilerclass option will be used.

-compilerclass com.sun.tools.javac.Main

Specifies the compiler class to invoke.

-g

Compile debugging info into class file.

-normi

Passed through to Symantec's sj.

-classpath path

Classpath to use.

-source source

Source version.

-Joption

Flags passed through to java runtime.

Type: string

Constraints: Has Default Value: null

extraRmicOptions

The options passed to the RMIC compiler during server-side generation.

Each EJB component can override the compiler options that you specify here.

Type: string

Constraints: Has Default Value: null

gatheredWritesEnabled

Enables gathered writes over NIO socket channels. Enabling this attribute increases efficiency during I/O in environments with high network throughput and should be used only when configuring a WebLogic domain for Oracle Exalogic.

Type: boolean

Constraints: Has Default Value: false

gracefulShutdownTimeout

Number of seconds a graceful shutdown operation waits before forcing a shut down. A graceful shutdown gives WebLogic Server subsystems time to complete certain application processing currently in progress. If subsystems are unable to complete processing within the number of seconds that you specify here, then the server will force shutdown automatically.

A value of `means` that the server will wait indefinitely for graceful shutdown to complete.

The graceful shutdown timeout applies only to graceful shutdown operations.

Type: integer/int32

Constraints: Has Default Value: 0, Minimum Value: 0

healthCheckIntervalSeconds

The number of seconds that defines the frequency of this server's self-health monitoring. The server monitors the health of its subsystems every `HealthCheckIntervalSeconds` and changes the Server's overall state if required.

Type: integer/int32

Constraints: Has Default Value: 180, Minimum Value: 1, Maximum Value: 2147483647

healthCheckStartDelaySeconds

The number of seconds the Node Manager should wait before starting to monitor the server.

Type: integer/int32

Constraints: Has Default Value: 120, Minimum Value: 0, Maximum Value: 2147483647

hostsMigratableServices

Gets the `hostsMigratableServices` attribute of the `ServerMBean` object

Type: boolean

Constraints: Read Only, Has Default Value: true

httpTraceSupportEnabled

Returns the `HttpTraceSupportEnabled` value

Type: boolean

Constraints: Has Default Value: false

httpdEnabled

Whether or not HTTP support is enabled on the regular port or SSL port.

Type: boolean

Constraints: Has Default Value: true

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

idleConnectionTimeout

The maximum number of seconds that a connection is allowed to be idle before it is closed by the server. The T3 and T3S protocols ignore this attribute. If you configure

network channels for this server, each channel can override this idle connection message timeout.

This timeout helps guard against server deadlock through too many open connections.

Type: integer/int32

Constraints: Has Secure Value: 65, Has Default Value: 65, Minimum Value: 0

idlePeriodsUntilTimeout

The number of idle periods until peer is considered unreachable.

Type: integer/int32

Constraints: Has Default Value: 4, Minimum Value: 4, Maximum Value: 65534

ignoreSessionsDuringShutdown

Indicates whether a graceful shutdown operation drops all HTTP sessions immediately.

If this is set to `false`, a graceful shutdown operation waits for HTTP sessions to complete or timeout.

Type: boolean

Constraints: Has Default Value: `false`

instrumentStackTraceEnabled

Specifies whether the server returns stack traces for RMI calls that generate exceptions.

With RMI stack tracking enabled, if a client issues an RMI call to a server subsystem or to a module running within the server, and if the subsystem or module generates an exception that includes a stack trace, the server will return the exception as well as the stack trace. With it disabled, the server will return the exception without the stack trace details.

Type: boolean

Constraints: Has Secure Value: `false`, Has Default Value: `true`

interfaceAddress

The IP address of the NIC that this server should use for multicast traffic.

Type: string

isolatePartitionThreadLocals

Specified whether the server needs to ensure that threadlocals storage from self-tuning thread pool threads must be cleaned up before the threads are used for processing work requests from a different partition. This helps ensure that no threadlocals from a different partition can be retrieved from work requests while being processed by a self-tuning thread pool thread. The different between this attribute and the `eagerThreadLocalCleanup` attribute is that threadlocals storage will not be cleared if the previous work request processed by the self-tuning thread pool thread was for the same partition, whereas with `eagerThreadLocalCleanup` set, the threadlocals storage will also be cleared in this case.

Type: boolean

Constraints: Has Default Value: `false`

javaCompiler

The Java compiler to use for all applications hosted on this server that need to compile Java code.

Type: string

Constraints: Has Secure Value: javac, Has Default Value: javac

javaCompilerPostClassPath

The options to append to the Java compiler classpath when compiling Java code.

Type: string

Constraints: Has Secure Value: null, Has Default Value: null

javaCompilerPreClassPath

The options to prepend to the Java compiler classpath when compiling Java code.

Type: string

Constraints: Has Secure Value: null, Has Default Value: null

javaStandardTrustKeyStorePassPhrase

The password for the Java Standard Trust keystore. This password is defined when the keystore is created.

If empty or null, then the keystore will be opened without a passphrase.

This attribute is only used if KeyStores is CUSTOM_IDENTITY_AND_JAVA_STANDARD_TRUST or DEMO_IDENTITY_AND_DEMO_TRUST.

When you get the value of this attribute, WebLogic Server does the following:

1. Retrieves the value of the `JavaStandardTrustKeyStorePassPhraseEncrypted` attribute.
2. Decrypts the value and returns the unencrypted password as a String.

When you set the value of this attribute, WebLogic Server does the following:

1. Encrypts the value.
2. Sets the value of the `JavaStandardTrustKeyStorePassPhraseEncrypted` attribute to the encrypted value.

Using this attribute (`JavaStandardTrustKeyStorePassPhrase`) is a potential security risk because the String object (which contains the unencrypted password) remains in the JVM's memory until garbage collection removes it and the memory is reallocated. Depending on how memory is allocated in the JVM, a significant amount of time could pass before this unencrypted data is removed from memory.

Instead of using this attribute, use `JavaStandardTrustKeyStorePassPhraseEncrypted`

Type: string

Constraints: Encrypted

keyStores

Which configuration rules should be used for finding the server's identity and trust keystores?

Type: string

Constraints: Has Default Value: `DemoIdentityAndDemoTrust`, Legal Values: `DemoIdentityAndDemoTrust`, `CustomIdentityAndJavaStandardTrust`, `CustomIdentityAndCustomTrust`, `CustomIdentityAndCommandLineTrust`

listenAddress

The IP address or DNS name this server uses to listen for incoming connections. For example, enter `12.34.5.67` or `mymachine`, respectively.

Note that the value you specify for the listen address is not the URL to the host machine and it does not include the communication protocol, listen port, or channel.

Servers can be reached through the following URL:

```
protocol://listen-address:listen-port
```

Any network channel that you configure for this server can override this listen address.

If a server's listen address is undefined, clients can reach the server through an IP address of the computer that hosts the server, a DNS name that resolves to the host, or the localhost string. The localhost string can be used only for requests from clients that are running on the same computer as the server.

If you want to limit the valid addresses for a server instance, specify one of the following:

- IP address. If you provide an IP address, clients can specify either the IP address or a DNS name that maps to the IP address. Clients that specify an IP address and attempt to connect through an SSL port must disable hostname verification.
- DNS name. If you provide a DNS name, clients can specify either the DNS name or the corresponding IP address.

Do not leave the listen address undefined on a computer that uses multiple IP address (a multihomed computer). On such a computer, the server will bind to all available IP addresses.

Note also that if you are using the demo certificates in a multi-server domain, Managed Server instances will fail to boot if you specify the fully-qualified DNS name. For information about this limitation and suggested workarounds, see "Limitation on CertGen Usage" in *Administering Security for Oracle WebLogic Server*

Type: string

listenPort

The default TCP port that this server uses to listen for regular (non-SSL) incoming connections.

Administrators must have the right privileges before binding to a port or else this operation will not be successful and it will render the console un-reachable.

If this port is disabled, the SSL port must be enabled. Additional ports can be configured using network channels. The cluster (multicast) port is configured separately.

Type: integer/int32

Constraints: Has Default Value: 7001, Minimum Value: 1, Maximum Value: 65535

listenPortEnabled

Specifies whether this server can be reached through the default plain-text (non-SSL) listen port.

If you disable this listen port, you must enable the default SSL listen port.

You can define additional listen ports for this server by configuring network channels.

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: true

listenThreadStartDelaySecs

Returns the maximum time that the server will wait for server sockets to bind before starting a listen thread.

Properties to consider for removal

Type: integer/int32

Constraints: Has Default Value: 60

listenersBindEarly

Determines whether the server should bind server sockets early.

Early binding detects port conflicts quickly and also gives user feedback on the default listen port as to the server state.

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

logRemoteExceptionsEnabled

Specifies whether the server message log includes exceptions that are raised in remote systems.

Type: boolean

Constraints: Has Secure Value: true, Has Default Value: false

loginTimeoutMillis

The login timeout for this server's default regular (non-SSL) listen port. This is the maximum amount of time allowed for a new connection to establish.

A value of indicates there is no maximum.

Type: integer/int32

Constraints: Has Secure Value: 5000, Has Default Value: 5000, Minimum Value: 0, Maximum Value: 100000

machine

The WebLogic Server host computer (machine) on which this server is meant to run.

If you want to use Node Manager to start this server, you must assign the server to a machine and you must configure the machine for Node Manager.

You cannot change this value if a server instance is already running.

Type: weblogic.management.configuration.MachineMBean reference

Constraints: Restart Required

managedServerIndependenceEnabled

Specifies whether this Managed Server can be started when the Administration Server is unavailable.

In such a case, the Managed Server retrieves its configuration by reading a configuration file and other files directly.

Type: boolean

Constraints: Has Secure Value: true, Has Default Value: true

maxConcurrentLongRunningRequests

The maximum number of running long-running requests that can be submitted to all the Managed Executor Services or Managed Scheduled Executor Services in the server.

Type: integer/int32

Constraints: Has Default Value: 100, Minimum Value: 0, Maximum Value: 65534

maxConcurrentNewThreads

The maximum number of running threads that can be created by all the Managed Thread Factories in the server.

Type: integer/int32

Constraints: Has Default Value: 100, Minimum Value: 0, Maximum Value: 65534

maxMessageSize

The maximum number of bytes allowed in messages that are received over all supported protocols, unless overridden by a protocol-specific setting or a custom channel setting.

The order of precedence for setting message size maximums is as follows:

1. A channel-wide maximum in a custom network channel.
2. A protocol-specific setting in the default network channel.

See

- getMaxCOMMessageSize() getMaxCOMMessageSize
- getMaxHTTPMessageSize() getMaxHTTPMessageSize
- getMaxIIOPMessageSize() getMaxIIOPMessageSize
- getMaxT3MessageSize() getMaxT3MessageSize

3. The message maximum in this attribute.

This maximum message size helps guard against a denial of service attack in which a caller attempts to force the server to allocate more memory than is available thereby keeping the server from responding quickly to other requests.

A client can set this value using the `-Dweblogic.MaxMessageSize` property.

Type: integer/int32

Constraints: Has Secure Value: 10000000, Has Default Value: 10000000, Minimum Value: 4096, Maximum Value: 200000000

maxOpenSockCount

The maximum number of open sockets allowed in server at a given point of time.

When the maximum threshold is reached, the server stops accepting new requests until the number of sockets drops below the threshold.

A value less than indicates an unlimited size.

Type: integer/int32

Constraints: Has Default Value: -1, Minimum Value: -1, Maximum Value: 2147483647

messageIdPrefixEnabled

Indicates whether message IDs in logged messages will include a prefix. Message ids are 6 digit numeric strings that can be optionally presented in a log entry with a prefix. The prefix used by server messages is "BEA-".

Type: boolean

Constraints: Has Default Value: true

muxerClass

Non-blocking IO is enabled by default on the server side.

The default value is `weblogic.socket.NIOSocketMuxer`.

The Certicom SSL implementation is not supported with `NIOSocketMuxer`. If you need to secure internet communication, Oracle recommends enabling JSSE (Java Secure Socket Extension).

Type: string

name

An alphanumeric name for this server instance. (Spaces are not valid.)

The name must be unique for all configuration objects in the domain. Within a domain, each server, machine, cluster, JDBC connection pool, virtual host, and any other resource type must be named uniquely and must not use the same name as the domain.

For more information on server naming conventions, see Domain and Server Name Restrictions in Understanding Domain Configuration for Oracle WebLogic Server.

The server name is not used as part of the URL for applications that are deployed on the server. It is for your identification purposes only. The server name displays in the Administration Console, and if you use WebLogic Server command-line utilities or APIs, you use this name to identify the server.

After you have created a server, you cannot change its name. Instead, clone the server and provide a new name for the clone.

Type: string

Constraints: Read Only

nativeIOEnabled

Specifies whether native I/O is enabled for the server.

Type: boolean

Constraints: Has Default Value: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

numOfRetriesBeforeMSIMode

Get the number of retries to contact admin server, before starting in Managed Server Independence Mode

Type: integer/int32

Constraints: Has Default Value: 3, Minimum Value: 0, Maximum Value: 65534

outboundEnabled

Specifies whether new server-to-server connections may consider the default server channel when initiating a connection. This is only relevant if the connection needs to

be bound to the default listen address. This will only work for binary protocols that support both outbound and inbound traffic.

When this feature is not enabled, connections are initiated using a local address selected by the underlying hardware. For the default channel this is usually what is wanted for IP-routing to be effective. Note that since the default is false, other outbound channels will be considered in preference to the default channel.

Default administration channels, created when the domain-wide administration port is turned on, are always considered and bound when initiating an administrative connection. To allow IP-routing for administration traffic create custom admin with `NetworkAccessPointMBean#isOutboundEnabled` set to false instead of enabling the domain-wide ADMIN port.

Type: boolean

Constraints: Has Default Value: false

outboundPrivateKeyEnabled

Specifies whether the SSL identity specified by `SSLMBean#getServerPrivateKeyAlias()` `getSSLMBean#ServerPrivateKeyAlias` for this server should be used for outbound SSL connections on the default server channel. In normal circumstances the outbound identity is determined by the caller's environment.

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

periodLength

The time interval in milliseconds of the heartbeat period. A value of 0 indicates that heartbeats are turned off.

Type: integer/int32

Constraints: Has Default Value: 60000, Minimum Value: 0

preferredSecondaryGroup

Defines secondary clustered instances considered for hosting replicas of the primary HTTP session states created on the server.

Type: string

printStackTraceInProduction

Specifies whether the server message log includes exception stack trace that are raised in remote systems.

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

reliableDeliveryPolicy

The reliable delivery policy for web services.

Type: weblogic.management.configuration.WSReliableDeliveryPolicyMBean reference

Constraints: Restart Required

replicationGroup

Defines preferred clustered instances considered for hosting replicas of the primary HTTP session states created on the server.

Type: string

replicationPorts

When WLS is running on Exalogic machines, cluster replication traffic could go over multiple replication channels. However multiple replication channels need not be configured on each clustered server instance. Only one replication channel with explicit IP-Address needs to be configured for each server and replicationPorts range can be specified for each server. For eg. range 7001-7010 will create 10 replication channels with ports 7001 to 7010 for the given server. These channels inherits all the properties of the configured replication channel except the listen port. Names of these channels will be derived from the configured replication channel with suffix {x} added where x could be 1,2.. as per the number of ports specified. Public ports are same as the listen port for these additional channels.

Type: string

resolveDNSName

Resolve the listen address to use for all T3 communication

Type: boolean

Constraints: Has Default Value: false

restartDelaySeconds

The number of seconds the Node Manager should wait before restarting this server.

After killing a server process, the system might need several seconds to release the TCP port(s) the server was using. If Node Manager attempts to restart the Managed Server while its ports are still active, the startup attempt fails.

If AutoMigration is enabled and RestartDelaySeconds is 0, the RestartDelaySeconds is automatically set to the lease time. This prevents the server from failing to restart after migration when the previous lease is still valid.

Type: integer/int32

Constraints: Has Default Value: 0, Minimum Value: 0, Maximum Value: 2147483647

restartIntervalSeconds

The number of seconds during which this server can be restarted, up to the number of times specified in RestartMax.

Type: integer/int32

Constraints: Has Default Value: 3600, Minimum Value: 300, Maximum Value: 2147483647

restartMax

The number of times that the Node Manager can restart this server within the interval specified in RestartIntervalSeconds.

Type: integer/int32

Constraints: Has Default Value: 2, Minimum Value: 0, Maximum Value: 2147483647

retryIntervalBeforeMSIMode

Get the number of seconds between the retries to contact admin server, before starting in Managed Server Independence Mode

Type: integer/int32

Constraints: Has Default Value: 5, Minimum Value: 1, Maximum Value: 65534

reverseDNSAllowed

Specifies whether the kernel is allowed to perform reverse DNS lookups.

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

scatteredReadsEnabled

Enables scattered reads over NIO socket channels. Enabling this attribute increases efficiency during I/O in environments with high network throughput and should be used only when configuring a WebLogic domain for Oracle Exalogic.

Type: boolean

Constraints: Has Default Value: false

serverLifeCycleTimeoutVal

Number of seconds a force shutdown operation waits before timing out and killing itself. If the operation does not complete within the configured timeout seconds, the server will shutdown automatically if the state of the server at that time was SHUTTING_DOWN

A value of means that the server will wait indefinitely for life cycle operation to complete.

Type: integer/int32

Constraints: Has Secure Value: 120, Has Default Value: 30, Has Production Mode Default Value: 120, Minimum Value: 0

sitConfigPollingInterval

Returns the current polling interval for finding the situational config file in the filesystem

Type: integer/int32

Constraints: Has Default Value: 5, Minimum Value: 1, Maximum Value: 65534

socketBufferSizeAsChunkSize

Specifies whether the server's buffer size for sending or receiving data through a raw socket should be set to 4KB.

Otherwise, the server does not impose a limit to the buffer size and defers to the operating system. This option is useful only on some operating systems for improving performance. It should be disabled in most environments.

Type: boolean

Constraints: Has Default Value: false

socketReaders

The number of socket reader threads.

Type: integer/int32

Constraints: Has Default Value: -1, Minimum Value: -1, Maximum Value: 65534

stagingDirectoryName

The directory path on the Managed Server where all staged (prepared) applications are placed.

If an absolute directory name is not specified, the path is relative to the root directory "/". Once configured, you cannot change the staging directory name. Remove all applications from the server prior to changing this attribute. The default staging directory is "stage", relative to the server root.

Type: string

stagingMode

The mode that specifies whether an application's files are copied from a source on the Administration Server to the Managed Server's staging area during application preparation.

During application preparation, the application's files are copied from the source on the Administration Server to the Managed Server's staging area. If you specify `nostage` or `external_stage`, the copy will not occur. This is useful when the staging area is a shared directory, already containing the application files, or if this is a single server domain. The administrator must ensure that the Managed Server's staging directory is set appropriately. Deployment errors will result if the application is not available during the preparation or activation of the application. Each application can override the staging mode specified here.

Type: string

Constraints: Legal Values: stage, nostage, external_stage

startupMode

The state in which this server should be started. If you specify `STANDBY`, you must also enable the domain-wide administration port.

In the `RUNNING` state, a server offers its services to clients and can operate as a full member of a cluster. In the `ADMIN` state, the server is up and running, but available only for administration operations, allowing you to perform server and application-level administration tasks without risk to running applications. In the `STANDBY` state, a server instance does not process any request; its regular Listen Port is closed. The Administration Port is open. It only accepts life cycle commands that transition the server instance to either the `RUNNING` or the `SHUTDOWN` state. Other Administration requests are not accepted. A `STANDBY` server's only purpose is to resume into the `RUNNING` state quickly; it saves server startup time.

Type: string

Constraints: Has Default Value: RUNNING

startupTimeout

Timeout value for server start and resume operations. If the server fails to start in the timeout period, it will force shutdown.

A value of `means` that the server will wait indefinitely for the operation to complete.

Type: integer/int32

Constraints: Has Default Value: 0, Has Production Mode Default Value: 0, Minimum Value: 0

stuckThreadTimerInterval

The number of seconds after which WebLogic Server periodically scans threads to see if they have been continually working for the configured maximum length of time.

Type: integer/int32

Constraints: Has Default Value: 60, Minimum Value: 0, Maximum Value: 2147483647

tags

Return all tags on this Configuration MBean

Type: array of string

threadPoolPercentSocketReaders

The percentage of execute threads from the default queue that can be used as socket readers.

Type: integer/int32

Constraints: Has Default Value: 33, Minimum Value: 1, Maximum Value: 99

transactionLogFilePrefix

The path prefix for the server's JTA transaction log files. If the pathname is not absolute, the path is assumed to be relative to the server's root directory.

For a clustered server, if you plan to be able to migrate the Transaction Recovery Service from this server if it fails to another server (backup server) in the same cluster, you must store transaction log files on persistent storage, such as a Storage Area Network (SAN) device or a dual-ported disk, available to both servers.

Do not use an NFS file system to store transaction log files. Because of the caching scheme in NFS, transaction log files on disk may not always be current. Using transaction log files stored on an NFS device for recovery may cause data corruption.

Type: string

Constraints: Has Default Value: ./

transactionLogFileWritePolicy

The policy that determines how transaction log file entries are written to disk. This policy can affect transaction performance. (Note: To be transactionally safe, the Direct-Write policy may require additional OS or environment changes on some Windows systems.)

WebLogic Server supports the following policies:

- Cache-Flush. Flushes operating system and on-disk caches after each write.
- Direct-Write. Tells the operating system to write directly to disk with each write. Direct-Write performs better than Cache-Flush.

If Direct-Write is not supported on the host platform, the policy becomes Cache-Flush and a log message is printed.

Note: On Windows, the "Direct-Write" policy may leave transaction data in the on-disk cache without writing it to disk immediately. This is not transactionally safe because a power failure can cause loss of on-disk cache data. For transactionally safe writes using "Direct-Write" on Windows, either disable all write caching for the disk (enabled by default), or use a disk with a battery-backed cache.

The on-disk cache for a hard-drive on Windows can be disabled through system administration: Control-Panel -> System -> Hardware-tab -> Device-Manager-button -> Disk-Drives -> name-of-drive -> Policies-tab -> "Enable write caching on the disk" check-box. Some file systems do not allow this value to be changed. For example, a RAID system that has a reliable cache.

Type: string

Constraints: Has Default Value: Direct-Write, Legal Values: Cache-Flush, Direct-Write, Legal Null: true

tunnelingClientPingSecs

The interval (in seconds) at which to ping a tunneled client to see if it is still alive.

If you create network channels for this server, each channel can override this setting.

Type: integer/int32

Constraints: Has Default Value: 45, Minimum Value: 1

tunnelingClientTimeoutSecs

The amount of time (in seconds) after which a missing tunneled client is considered dead.

If you create network channels for this server, each channel can override this setting.

Type: integer/int32

Constraints: Has Default Value: 40, Minimum Value: 1

tunnelingEnabled

Specifies whether tunneling for the T3, T3S, HTTP, HTTPS, IIOP, and IIOPS protocols should be enabled for this server.

If you create network channels for this server, each channel can override this setting.

Type: boolean

Constraints: Has Default Value: false

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

uploadDirectoryName

The directory path on the Administration Server where all uploaded applications are placed.

If an absolute directory name is not specified, the path is relative to the root directory "/". The default staging directory is "stage", relative to the server root. On the Managed Server this returns null, and is not configurable.

Type: string

Constraints: Has Recommended Secure Value: An absolute directory that is outside the root directory of any WebLogic Server instance or application, and that resides on a physical disk that is separate from the WebLogic Server host's system disk.

use81StyleExecuteQueues

Backward compatibility mode to switch to 8.1 execute queues instead of WorkManagers. Each of the WorkManagers is converted to an individual execute queue. Setting this attribute requires a server restart.

Type: boolean

Constraints: Has Default Value: false

useConcurrentQueueForRequestManager

Reduces lock contention by using concurrent buffer queue to park incoming requests. Enabling this attribute increases throughput as requests are scheduled without acquiring any locks.

Type: boolean

useDetailedThreadName

Specifies whether to include detailed information in self-tuning thread pool thread names. Setting this flag as true would include additional information, such as the

name of the Work Manager for which the execute thread is executing the task, but at the expense of overhead in keeping the thread name updated with such information.

Type: boolean

Constraints: Has Default Value: false

useEnhancedIncrementAdvisor

Specifies whether self-tuning should use the enhanced IncrementAdvisor implementation that uses a different algorithm to adjust the size of the self-tuning thread pool.

Type: boolean

Constraints: Has Default Value: true

useEnhancedPriorityQueueForRequestManager

Reduces lock contention by using the enhanced ConcurrentCalendarQueue as the priority based queue for pending requests that are waiting for a thread.

This attribute should be enabled only in an Oracle Exalogic environment.

Type: boolean

Constraints: Has Default Value: false

useFusionForLLR

Enables the use of the `ADM_DDL` store procedure for LLR. The default value is `false` (not enabled).

When enabled, a `WLS_` prefix and `_DYD` suffix is automatically added to the LLR table name at runtime so the LLR table name in server configuration is not consistent with the actual table name in database.

Type: boolean

weblogicPluginEnabled

Specifies whether this server uses the proprietary `WL-Proxy-Client-IP` header.

Set this attribute to `true` to specify that this server instance uses the proprietary `WL-Proxy-Client-IP` header, which is recommended if the server instance will receive requests from a proxy plug-in. If the server instance is a member of a cluster that will receive proxied requests, enable the WebLogic plug-in at the cluster level. For servers that are members of a cluster, the setting at the cluster level overrides the server's setting. When the WebLogic plug-in is enabled at the cluster level, a call to `getRemoteAddr` will return the address of the browser client from the proprietary `WL-Proxy-Client-IP` header instead of the Web server.

Set this attribute to `false` to disable the `weblogic-plugin-enabled` parameter, `weblogic-plugin-enabled=false`, in the `config.xml` file.

Note: If you are using Oracle HTTP Server, the WebLogic Proxy Plug-In, or Oracle Traffic Director to distribute client requests to a Managed Server or a cluster, Oracle recommends setting this attribute to `true`

Type: boolean

Constraints: Has Default Value: false

weblogic.management.configuration.ShutdownClassMBean

Provides methods for configuring a shutdown class. A shutdown class is a Java program that is automatically loaded and executed when a WebLogic Server instance is shut down gracefully.

The properties of the `weblogic.management.configuration.ShutdownClassMBean` entity are as follows:

arguments

Arguments that a server uses to initialize a class.

Separate multiple arguments with a comma. For example:

```
first=MyFirstName, last=MyLastName
```

Type: string

className

The fully qualified name of a class to load and run. The class must be on the server's classpath.

For example, `mycompany.mypackage.myclass`

Type: string

Constraints: Legal Null: true

deploymentOrder

A priority that the server uses to determine when it deploys an item. The priority is relative to other deployable items of the same type.

For example, the server prioritizes and deploys all EJBs before it prioritizes and deploys startup classes.

Items with the lowest Deployment Order value are deployed first. There is no guarantee on the order of deployments with equal Deployment Order values. There is no guarantee of ordering across clusters.

Type: integer/int32

Constraints: Has Default Value: 1000, Minimum Value: 0, Maximum Value: 2147483647

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to `config.xml`

Type: boolean

Constraints: Read Only, Has Default Value: false

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

```
Name=user-specified-name
```

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

tags

Return all tags on this Configuration MBean

Type: array of string

targets

You must select a target on which an MBean will be deployed from this list of the targets in the current domain on which this item can be deployed. Targets must be either servers or clusters. The deployment will only occur once if deployments overlap.

Type: array of `weblogic.management.configuration.TargetMBean` references

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.SingleSignOnServicesMBean

This MBean represents configuration for SAML 2.0-based local site Single Sign-On Services.

The properties of the `weblogic.management.configuration.SingleSignOnServicesMBean` entity are as follows:

POSTOneUseCheckEnabled

Specifies whether the POST one-use check is enabled.

If set, the local site POST binding endpoints will store identifiers of all inbound documents to ensure that those documents are not presented more than once.

Type: boolean

Constraints: Has Default Value: true

SSOSigningKeyAlias

The keystore alias for the key to be used when signing documents.

The key is used to generate signatures on all the outgoing documents, such as authentication requests and responses. If you do not specify an alias, the server's configured SSL private key alias from the server's SSL configuration is used by default.

Type: string

Constraints: Has Default Value: null

SSOSigningKeyPassPhrase

The passphrase used to retrieve the local site's SSO signing key from the keystore.

If you do not specify a keystore alias and passphrase, the server's configured private key alias and private key passphrase from the server's SSL configuration is used by default.

Type: string

Constraints: Encrypted, Has Default Value: null

artifactMaxCacheSize

The maximum size of the artifact cache.

This cache contains the artifacts issued by the local site that are awaiting referencing by a partner. Specify '0' to indicate that the cache is unbounded.

Type: integer/int32

Constraints: Has Default Value: 10000

artifactTimeout

The maximum timeout (in seconds) of artifacts stored in the local cache.

This cache stores artifacts issued by the local site that are awaiting referencing by a partner. Artifacts that reach this maximum timeout duration are expired in the local cache even if no reference request has been received from the partner. If a reference request is subsequently received from the partner, the cache behaves as if the artifact had never been generated.

Type: integer/int32

Constraints: Has Default Value: 300

authnRequestMaxCacheSize

The maximum size of the authentication request cache.

This cache stores documents issued by the local Service Provider that are awaiting response from a partner Identity Provider.

Specify '0' to indicate that the cache is unbounded.

Type: integer/int32

Constraints: Has Default Value: 10000

authnRequestTimeout

The maximum timeout (in seconds) of <AuthnRequest> documents stored in the local cache.

This cache stores documents issued by the local Service provider that are awaiting response from a partner Identity Provider. Documents that reach this maximum timeout duration are expired from the local cache even if no response is received from the Identity Provider. If a response is subsequently returned by the Identity Provider, the cache behaves as if the <AuthnRequest> had never been generated.

Type: integer/int32

Constraints: Has Default Value: 300

basicAuthPassword

The password used to assign Basic Authentication credentials to outgoing HTTPS connections

Type: string

Constraints: Encrypted

basicAuthUsername

The username that is used to assign Basic authentication credentials to outgoing HTTPS connections.

Type: string

contactPersonCompany

The contact person's company name.

Type: string

Constraints: Has Default Value: null

contactPersonEmailAddress

The contact person's e-mail address.

Type: string

Constraints: Has Default Value: null

contactPersonGivenName

The contact person given (first) name.

Type: string

Constraints: Has Default Value: null

contactPersonSurName

The contact person surname (last name).

Type: string

Constraints: Has Default Value: null

contactPersonTelephoneNumber

The contact person's telephone number.

Type: string

Constraints: Has Default Value: null

contactPersonType

The contact person type.

Type: string

Constraints: Has Default Value: null

defaultURL

The Service Provider's default URL.

When an unsolicited SSO response arrives at the Service Provider without an accompanying target URL, the user (if authenticated) is redirected to this default URL.

Type: string

Constraints: Has Default Value: null

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

entityID

The string that uniquely identifies the local site.

Type: string

Constraints: Has Default Value: null

forceAuthn

Specifies whether the Identity Provider must authenticate users directly and not use a previous security context. The default is *false*.

Note the following:

1. Setting *ForceAuthn* to *true* -- that is, enabling Force Authentication -- has no effect in WebLogic Server. SAML logout is not supported in WebLogic Server, so even if the user is already authenticated at the Identity Provider site and *ForceAuthn* is set to *true*, the user is not forced to authenticate again at the Identity Provider site.
2. Setting both *ForceAuthn* and *IsPassive* to *true* -- that is, Force Authentication and Passive are enabled -- is an invalid configuration that causes WebLogic server to generate an exception and also causes the single sign-on session to fail.

Type: boolean

Constraints: Has Default Value: false

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

identityProviderArtifactBindingEnabled

Specifies whether the Artifact binding is enabled for the Identity Provider.

Type: boolean

Constraints: Has Default Value: true

identityProviderEnabled

Specifies whether the local site is enabled for the Identity Provider role.

Type: boolean

Constraints: Has Default Value: false

identityProviderPOSTBindingEnabled

Specifies whether the POST binding is enabled for the Identity Provider.

Type: boolean

Constraints: Has Default Value: true

identityProviderPreferredBinding

Specifies the preferred binding type for endpoints of the Identity Provider services. Must be set to *None*, *HTTP/POST*, *HTTP/Artifact*, or *HTTP/Redirect*

Type: string

Constraints: Has Default Value: None, Legal Values: None, HTTP/POST, HTTP/Artifact, HTTP/Redirect, Legal Null: true

identityProviderRedirectBindingEnabled

Specifies whether the Redirect binding is enabled for the Identity Provider.

Type: boolean

Constraints: Has Default Value: true

loginReturnQueryParameter

The name of the query parameter to be used for conveying the login-return URL to the login form web application.

Type: string

Constraints: Has Default Value: null

loginURL

The URL of the login form web application to which unauthenticated requests are directed.

By default, the login URL is `/saml2/idp/login` using Basic authentication. Typically you specify this URL if you are using a custom login web application.

Type: string

Constraints: Has Default Value: `/saml2/idp/login`, Legal Null: true

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

`Name=user-specified-name`

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

organizationName

The organization name.

This string specifies the name of the organization to which a user may refer for obtaining additional information about the local site.

Type: string

Constraints: Has Default Value: null

organizationURL

The organization URL.

This string specifies a location to which a user may refer for information about the local site. This string is not used by SAML 2.0 services for the actual handling or processing of messages.

Type: string

Constraints: Has Default Value: null

passive

Determines whether the Identity Provider and the user must not take control of the user interface from the requester and interact with the user in a noticeable fashion. The default setting is `false`

The WebLogic Server SAML 2.0 services generate an exception if `Passive (IsPassive)` is enabled and the end user is not already authenticated at the Identity Provider site. In this situation, web single sign-on fails.

Type: boolean

Constraints: Has Default Value: false

publishedSiteURL

The published site URL.

When publishing SAML 2.0 metadata, this URL is used as a base URL to construct endpoint URLs for the various SAML 2.0 services. The published site URL is also used during request processing to generate and/or parse various URLs.

The hostname and port portion of the URL should be the hostname and port at which the server is visible externally; this may not be the same as the hostname and port by which the server is known locally. If you are configuring SAML 2.0 services in a cluster, the hostname and port may correspond to the load balancer or proxy server that distributes client requests to servers in the cluster.

The remainder of the URL should be a single path component corresponding to the application context at which the SAML 2.0 services application is deployed (typically `/saml2`).

Type: string

Constraints: Has Default Value: null

recipientCheckEnabled

Specifies whether the recipient/destination check is enabled. When true, the recipient of the SAML Request/Response must match the URL in the HTTP Request.

Type: boolean

Constraints: Has Default Value: true

replicatedCacheEnabled

Specifies whether the persistent cache (LDAP or RDBMS) is used for storing SAML 2.0 artifacts and authentication requests.

RDBMS is required by the SAML 2.0 security providers in production environments. Use LDAP only in development environments.

If this is not set, artifacts and requests are saved in memory.

If you are configuring SAML 2.0 services for two or more WebLogic Server instances in a domain, you must enable the replicated cache individually on each server. In

addition, if you are configuring SAML 2.0 services in a cluster, each Managed Server must also be configured individually.

Type: boolean

Constraints: Has Default Value: false

serviceProviderArtifactBindingEnabled

Specifies whether the Artifact binding is enabled for the Service Provider.

Type: boolean

Constraints: Has Default Value: true

serviceProviderEnabled

Specifies whether the local site is enabled for the Service Provider role.

This attribute must be enabled in order to publish the metadata file.

Type: boolean

Constraints: Has Default Value: false

serviceProviderPOSTBindingEnabled

Specifies whether the POST binding is enabled for the Service Provider.

Type: boolean

Constraints: Has Default Value: true

serviceProviderPreferredBinding

Specifies the preferred binding type for endpoints of Service Provider services. Must be set to "None", "POST", or "Artifact".

Type: string

Constraints: Has Default Value: None, Legal Values: None, HTTP/POST, HTTP/Artifact, Legal Null: true

signAuthnRequests

Specifies whether authentication requests must be signed. If set, all outgoing authentication requests are signed.

Type: boolean

Constraints: Has Default Value: false

tags

Return all tags on this Configuration MBean

Type: array of string

transportLayerSecurityKeyAlias

The string alias used to store and retrieve the server's private key, which is used to establish outgoing TLS/SSL connections.

If you do not specify an alias, the server's configured SSL private key alias from the server's SSL configuration is used for the TLS alias by default.

Type: string

transportLayerSecurityKeyPassPhrase

The passphrase used to retrieve the server's private key from the keystore.

If you do not specify either an alias or a passphrase, the server's configured SSL private key alias and private key passphrase from the server's SSL configuration is used for the TLS alias and passphrase by default.

Type: string

Constraints: Encrypted

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

wantArtifactRequestsSigned

Specifies whether incoming artifact requests must be signed.

This attribute can be set if the Artifact binding is enabled.

Type: boolean

Constraints: Has Default Value: false

wantAssertionsSigned

Specifies whether incoming SAML 2.0 assertions must be signed.

Type: boolean

Constraints: Has Default Value: false

wantAuthnRequestsSigned

Specifies whether incoming authentication requests must be signed. If set, authentication requests that are not signed are not accepted.

Type: boolean

Constraints: Has Default Value: false

wantBasicAuthClientAuthentication

Specifies whether Basic Authentication client authentication is required.

If enabled, callers to HTTPS bindings of the local site must specify a Basic authentication header, and the username and password must be validated against the Basic authentication values of the binding client partner.

Type: boolean

Constraints: Has Default Value: false

wantTransportLayerSecurityClientAuthentication

Specifies whether TLS/SSL client authentication is required.

If enabled, callers to TLS/SSL bindings of the local site must specify client authentication (two-way SSL), and the identity specified must validate against the TLS certificate of the binding client partner.

Type: boolean

Constraints: Has Default Value: false

weblogic.management.configuration.SingletonServiceMBean

A service that will be automatically maintained as a Singleton in a cluster. There will always be exactly one instance of it active at any given time.

The properties of the weblogic.management.configuration.SingletonServiceMBean entity are as follows:

additionalMigrationAttempts

A migratable service could fail to come up on every possible configured server. This attribute controls how many further attempts, after the service has failed on every server at least once, should be tried. Note that each attempt specified here indicates another full circuit of migrations amongst all the configured servers. So for a 3-server cluster, and a value of 2, a total of 4 additional migrations will be attempted. (the original server is never a valid destination)

Type: integer/int32

Constraints: Has Default Value: 2

allCandidateServers

Return a list of servers that are candidates to host the services deployed to this migratable target. If the ConstrainedCandidateServer list is empty, all servers in the cluster are returned. If the ConstrainedCandidateServer is not empty those servers only will be returned. The user preferred server will be the first element in the list returned.

Type: array of weblogic.management.configuration.ServerMBean references

className

The fully qualified name of a class to load and run. The class must be on the server's classpath.

For example, `mycompany.mypackage.myclass`

Type: string

Constraints: Legal Null: true

cluster

Returns the cluster this singleton service is associated with.

Type: weblogic.management.configuration.ClusterMBean reference

Constraints: Restart Required

constrainedCandidateServers

Returns the (user restricted) list of servers that may host the migratable target. The target will not be allowed to migrate to a server that is not in the returned list of servers. This feature is used to e.g. configure the two server that have access to a dual ported disk. All servers in this list must be part of the cluster that is associated with the migratable target.

Type: array of weblogic.management.configuration.ServerMBean references

Constraints: Restart Required

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

hostingServer

Returns the name of the server that currently hosts the singleton service.

Type: weblogic.management.configuration.ServerMBean reference

Constraints: Read Only

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

millisToSleepBetweenAttempts

Controls how long of a pause there should be between the migration attempts described in `getAdditionalMigrationAttempts()`. Note that this delay only happens when the service has failed to come up on every server. It does not cause any sort of delay between attempts to migrate otherwise.

Type: integer/int32

Constraints: Has Default Value: 300000

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

Name=user-specified-name

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

tags

Return all tags on this Configuration MBean

Type: array of string

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

userPreferredServer

Returns the server that the user prefers the singleton service to be active on.

Type: weblogic.management.configuration.ServerMBean reference

weblogic.management.configuration.StartupClassMBean

Provides methods that configure startup classes. A startup class is a Java program that is automatically loaded and executed when a WebLogic Server instance is started or restarted. By default, startup classes are loaded and executed after all other server subsystems have initialized and after the server deploys modules. For any startup class, you can override the default and specify that the server loads and executes it and before it deploys JDBC connection pools and before it deploys Web applications and EJBs.

The properties of the `weblogic.management.configuration.StartupClassMBean` entity are as follows:

arguments

Arguments that a server uses to initialize a class.

Separate multiple arguments with a comma. For example:

```
first=MyFirstName,last=MyLastName
```

Type: string

className

The fully qualified name of a class to load and run. The class must be on the server's classpath.

For example, `mycompany.mypackage.myclass`

Type: string

Constraints: Legal Null: true

deploymentOrder

A priority that the server uses to determine when it deploys an item. The priority is relative to other deployable items of the same type.

For example, the server prioritizes and deploys all EJBs before it prioritizes and deploys startup classes.

Items with the lowest Deployment Order value are deployed first. There is no guarantee on the order of deployments with equal Deployment Order values. There is no guarantee of ordering across clusters.

Type: integer/int32

Constraints: Has Default Value: 1000, Minimum Value: 0, Maximum Value: 2147483647

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to `config.xml`

Type: boolean

Constraints: Read Only, Has Default Value: false

failuresFatal

Specifies whether a failure in this startup class prevents the targeted server(s) from starting.

If you specify that failure is **not** fatal, if the startup class fails, the server continues its startup process.

Type: boolean

Constraints: Has Default Value: false

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

loadAfterAppsRunning

Specifies whether the targeted servers load and run this startup class after applications and EJBs are running.

If you enable this feature for a startup class, a server loads and runs the startup class after the activate phase. At this point, JMS and JDBC services are available.

(Deployment for applications and EJBs consists of three phases: prepare, admin and activate.)

Enable this feature if the startup class needs to be invoked after applications are running and ready to service client requests.

If you do not enable this feature, LoadBeforeAppDeployments or LoadBeforeAppActivation, a server instance loads startup classes when applications go to the admin state.

Type: boolean

Constraints: Has Default Value: false

loadBeforeAppActivation

Specifies whether the targeted servers load and run this startup class after activating JMS and JDBC services and before activating applications and EJBs.

If you enable this feature for a startup class, a server loads and runs the startup class before the activate phase. At this point, JMS and JDBC services are available.

(Deployment for applications and EJBs consists of three phases: prepare, admin and activate.)

Enable this feature if the startup class needs to be invoked after JDBC connection pools are available but before the applications are activated and ready to service client requests.

If you do not enable this feature, LoadBeforeAppDeployments or LoadAfterAppsRunning, a server instance loads startup classes when applications go to the admin state.

Type: boolean

Constraints: Has Default Value: false

loadBeforeAppDeployments

Specifies whether the targeted servers load and run this startup class before activating JMS and JDBC services and before starting deployment for applications and EJBs.

If you enable this feature for a startup class, a server loads and runs the startup class before the deployment prepare phase. At this point, JMS and JDBC services are not yet available. (Deployment for applications and EJBs consists of three phases: prepare, admin and activate.)

If you do not enable this feature, LoadBeforeAppActivation or LoadAfterAppsRunning, a server instance loads startup classes when applications go to the admin state.

Type: boolean

Constraints: Has Default Value: false

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's

`javax.management.ObjectName`

`Name=user-specified-name`

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as

XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`.

Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

tags

Return all tags on this Configuration MBean

Type: array of string

targets

You must select a target on which an MBean will be deployed from this list of the targets in the current domain on which this item can be deployed. Targets must be either servers or clusters. The deployment will only occur once if deployments overlap.

Type: array of `weblogic.management.configuration.TargetMBean` references

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.SubDeploymentMBean

This bean represents an individually targetable entity within a deployment package, which is deployable on WLS. This includes :

Modules in an EAR

JMS resources within a app scoped JMS module in an EAR

The properties of the `weblogic.management.configuration.SubDeploymentMBean` entity are as follows:

compatibilityName

This is only set for beans created as a result of conversion from an 8.1 application configured using `ApplicationMBean` and `ComponentMBean`.

Standalone modules in 8.1 have both an ApplicationMBean name and ComponentMBean name. This attribute stores the name of the latter, to be used when the server creates the transient ComponentMBean for backward compatibility.

Type: string

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

moduleType

The values match those defined by jsr88. This attribute may move to another MBean.

Type: string

name

Unique identifier for this bean instance. It is used by the application container to match the module in the application package to the targeting information in the configuration.

For modules within an EAR, the name should be the URI of the module as defined in the META-INF/application.xml deployment descriptor. There is an exception to this for web applications. See below.

For web modules in an EAR, the name should always equal the context root of that webapp, because the URI is not always unique

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (config.xml) as XML PCDATA. All left angle brackets (<) are converted to the XML entity <. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

tags

Return all tags on this Configuration MBean

Type: array of string

targets

You must select a target on which an MBean will be deployed from this list of the targets in the current domain on which this item can be deployed. Targets must be either servers or clusters. The deployment will only occur once if deployments overlap.

Type: array of weblogic.management.configuration.TargetMBean references

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

untargeted

Only relevant for deployments in resource group templates. Sub-deployments cannot have arbitrary targets if they are part of a deployment from resource group template. The sub-deployments, in such cases, may only be targeted to the virtual host of referring partition or stay untargeted. This flag, when specified with true, indicates that the sub-deployment must not be deployed in the referring partition

Type: boolean

Constraints: Has Default Value: false

weblogic.management.configuration.SystemComponentConfigurationMBean

A System Component Configuration MBean allows configuration to be shared between one or more System Components.

The properties of the weblogic.management.configuration.SystemComponentConfigurationMBean entity are as follows:

componentType

Get the system component type Examples of types may include "OHS", "Coherence". New System Components may be added in the future so the list of types is not static.

Type: string

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

Name=user-specified-name

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

sourcePath

Get the source path for configuration files Note: if you use a `SystemComponentConfiguration`, then the files for the `SystemComponents` directory are not used so there is no chance of conflict.

Type: string

systemComponents

System Component Configurations are targeted to System Component instances.

Type: array of `weblogic.management.configuration.SystemComponentMBean` references

tags

Return all tags on this Configuration MBean

Type: array of string

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.SystemComponentMBean

The properties of the `weblogic.management.configuration.SystemComponentMBean` entity are as follows:

autoRestart

Specifies whether the Node Manager can automatically restart this server if it crashes or otherwise goes down unexpectedly.

Type: boolean

Constraints: Has Default Value: true

componentType

Get the system component type Examples of types may include "OHS", "Coherence". New System Components may be added in the future so the list of types is not static.

Type: string

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to `config.xml`

Type: boolean

Constraints: Read Only, Has Default Value: false

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

machine

The WebLogic Server host computer (machine) on which this server is meant to run.

If you want to use a Node Manager to start this server, you must assign the server to a machine and you must configure the machine for the Node Manager.

You cannot change this value if a server instance is already running.

Type: weblogic.management.configuration.MachineMBean reference

Constraints: Restart Required

name

An alphanumeric name for this server instance. (Spaces are not valid.)

The name must be unique for all configuration objects in the domain. Within a domain, each server, machine, cluster, JDBC connection pool, virtual host, and any other resource type must be named uniquely and must not use the same name as the domain.

The server name is not used as part of the URL for applications that are deployed on the server. It is for your identification purposes only. The server name displays in the Administration Console, and if you use WebLogic Server command-line utilities or APIs, you use this name to identify the server.

After you have created a server, you cannot change its name. Instead, clone the server and provide a new name for the clone.

Type: string

Constraints: Read Only

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

restartDelaySeconds

The number of seconds the Node Manager should wait before restarting this server.

After killing a server process, the system might need several seconds to release the TCP port(s) the server was using. If Node Manager attempts to restart the Managed Server while its ports are still active, the startup attempt fails.

If AutoMigration is enabled and RestartDelaySeconds is 0, the RestartDelaySeconds is automatically set to the lease time. This prevents the server from failing to restart after migration when the previous lease is still valid.

Type: integer/int32

Constraints: Has Default Value: 0, Minimum Value: 0, Maximum Value: 2147483647

restartIntervalSeconds

The number of seconds during which this server can be restarted, up to the number of times specified in RestartMax.

Type: integer/int32

Constraints: Has Default Value: 3600, Minimum Value: 300, Maximum Value: 2147483647

restartMax

The number of times that the Node Manager can restart this server within the interval specified in RestartIntervalSeconds.

Type: integer/int32

Constraints: Has Default Value: 2, Minimum Value: 0, Maximum Value: 2147483647

tags

Return all tags on this Configuration MBean

Type: array of string

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.SystemComponentStartMBean

The NodeManager does not directly create the command to start a SystemComponent. This is done through a plugin architecture. So the following properties are not used when starting a SystemComponent from the NodeManager: #getJavaVendor #getJavaHome #getClassPath #getMWHome #getArguments

The properties of the weblogic.management.configuration.SystemComponentStartMBean entity are as follows:

MWHome

The MWHome directory (path on the machine running Node Manager) to use when starting this server.

Specify the directory on the Node Manager machine under which all of Oracle's MW products were installed. For example, c:\Oracle\Middleware\

Type: string

arguments

The arguments to use when starting this server.

These are the first arguments appended immediately after java portion of the startup command. For example, you can set Java heap memory or specify any weblogic.nodemanager.server.provider.WeblogicCacheServer option.

Separate arguments with a space.

Type: string

classPath

The classpath (path on the machine running Node Manager) to use when starting this server.

If you need to add user classes to the classpath, in addition you will need to add the following: `FEATURES_HOME/weblogic.server.modules.coherence.server_10.3.4.0.jar:COHERENCE_HOME/lib/coherence.jar`

where `FEATURES_HOME` is the features directory (typically `$MW_HOME/modules/features`) and `COHERENCE_HOME` the coherence directory (typically `$MW_HOME/coherence_3.6`) on the Node Manager machine. If you do not specify a classpath the above will be used automatically.

The operating system determines which character separates path elements. On Windows, use a semicolon (;). On UNIX a colon (:).

Type: string

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

javaHome

The Java home directory (path on the machine running Node Manager) to use when starting this server.

Specify the parent directory of the JDK's bin directory. For example, `c:\bea\jdk141`

Type: string

javaVendor

The Java Vendor value to use when starting this server.

If the server is part of a cluster and configured for automatic migration across possibly different platforms with different vendors providing the JDKs, then, both `JavaVendor` and `JavaHome` should be set in the generated configuration file instead.

Type: string

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

`Name=user-specified-name`

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

rootDirectory

The directory that this server uses as its root directory. This directory must be on the computer that hosts the Node Manager. If you do not specify a Root Directory value, the domain directory is used by default.

Type: string

tags

Return all tags on this Configuration MBean

Type: array of string

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.TransactionLogJDBCStoreMBean

This class represents a Transaction Log JDBC Store configuration.

The properties of the `weblogic.management.configuration.TransactionLogJDBCStoreMBean` entity are as follows:

XAResourceName

Overrides the name of the XAResource that this store registers with JTA.

You should not normally set this attribute. Its purpose is to allow the name of the XAResource to be overridden when a store has been upgraded from an older release and the store contained prepared transactions. The generated name should be used in all other cases.

Type: string

Constraints: Read Only, Has Default Value: null, Legal Null: true

connectionCachingPolicy

Advanced use only: gets the connection caching policy for the JDBC store.

The return values will be one of:

- `JMSConstants.JDBCSTORE_CONNECTION_CACHING_POLICY_DEFAULT` ("DEFAULT")
- `JMSConstants.JDBCSTORE_CONNECTION_CACHING_POLICY_MINIMAL` ("MINIMAL")
- `JMSConstants.JDBCSTORE_CONNECTION_CACHING_POLICY_NONE` ("NONE")

IMPORTANT: See the below for additional usage information, particularly regarding NONE

DEFAULT

The default mode of operation for the JDBC store. The JDBC store will open two connections to the database and it will keep these connections open for the life of the store. In addition, if the worker count for the store is two or more, then it will open one connection for each of the workers and those connections will also stay open for the life of the JDBC store. If the worker count is 3 then the JDBC store will use 5 database connections. If the worker count is the default of 1 then the JDBC store will use just 2 connections. The DEFAULT setting is the recommended setting to be used when the database backing the JDBC store is not constrained with respect to the number of open connections.

MINIMAL

The JDBC store will open one connection to the database and it will keep that connection open for the life of the store. In addition, if the worker count for the store is two or more, then it will open one connection for each of the workers and those connections will also stay open for the life of the JDBC store. If the worker count is 3 then the JDBC store will use 4 database connections. If the worker count is the default of 1 then the JDBC store will use just 1 connection. The MINIMAL setting may result in a slight reduction of through-put for low concurrency messaging scenarios in comparison to DEFAULT.

NONE

The NONE connection caching policy is for 'advanced usage only'. The JDBC store will open one connection to the database on an as-needed basis to perform I/O and it will release that connection when the operation is complete. The NONE value is not compatible with a configured worker count of 2 or more and will result in a configuration validation exception. The NONE setting may result in a slight reduction of through-put for low concurrency messaging scenarios in comparison to DEFAULT or MINIMAL.

NOTE: It is strongly recommended that a JDBC store be configured with a dedicated data source when the store is configured with the NONE connection caching policy. A store that shares a data source with other non-store components or applications runs the risk of failing due to dead-locks. Please note that a JDBC store will require more than one connection when first started. As such, a data source should be configured to grow and shrink so that the JDBC store can initialize.

Type: string

Constraints: Has Default Value: DEFAULT, Legal Values: DEFAULT, MINIMAL, NONE

createTableDDLFile

Specifies the DDL (Data Definition Language) file to use for creating the JDBC store's backing table.

- This field is ignored when the JDBC store's backing table, `WLStore`, already exists.
- If a DDL file is not specified and the JDBC store detects that a backing table doesn't already exist, the JDBC store automatically creates the table by executing a preconfigured DDL file that is specific to the database vendor. These preconfigured files are located in the `weblogic\store\io\jdbc\ddl` directory of the `MIDDLEWARE_HOME\modules\com.bea.core.store.jdbc_x.x.x.jar` file.

- If a DDL file is specified and the JDBC store detects that a backing table doesn't already exist, then the JDBC store searches for the DDL file in the file path first, and then if the file is not found, it searches for it in the CLASSPATH. Once found, the SQL within the DDL file is executed to create the JDBC store's database table. If the DDL file is not found and the backing table doesn't already exist, the JDBC store will fail to boot.

Type: string

Constraints: Has Default Value: null

dataSource

The JDBC data source used by this JDBC store to access its backing table.

The specified data source must use a non-XA JDBC driver since connection pools for XA JDBC drivers are not supported.

Type: weblogic.management.configuration.JDBCSystemResourceMBean reference

Constraints: Restart Required

deletesPerBatchMaximum

The maximum number of table rows that are deleted per database call.

- When possible, a JDBC store uses JDBC 3.0 batching to batch concurrent client requests.
- Both the maximum batch size for concurrent inserts and for concurrent writes are configurable.
- To disable JDBC 3.0 batching, set the maximum batch size to 1.
- The maximum batch size has no effect on the maximum number of concurrent client requests.

Type: integer/int32

Constraints: Has Default Value: 20, Minimum Value: 1, Maximum Value: 100

deletesPerStatementMaximum

The maximum number of table rows that are deleted per database call.

- Applies only when a JDBC store does not use JDBC 3.0 batching to batch concurrent client requests.
- The maximum deletes per statement has no effect on the maximum number of concurrent client requests.
- For some databases, the JDBC store may choose a lower value than the one configured.

Type: integer/int32

Constraints: Has Default Value: 20, Minimum Value: 1, Maximum Value: 100

deploymentOrder

A priority that the server uses to determine when it deploys an item. The priority is relative to other deployable items of the same type.

For example, the server prioritizes and deploys all EJBs before it prioritizes and deploys startup classes.

Items with the lowest Deployment Order value are deployed first. There is no guarantee on the order of deployments with equal Deployment Order values. There is no guarantee of ordering across clusters.

Type: integer/int32

Constraints: Has Default Value: 1000, Minimum Value: 0, Maximum Value: 2147483647

distributionPolicy

Specifies how the instances of a configured JMS artifact are named and distributed when cluster-targeted. A JMS artifact is cluster-targeted when its target is directly set to a cluster, or when it is scoped to a resource group and the resource group is in turn targeted to a cluster. When this setting is configured on a store, it applies to all JMS artifacts that reference the store. Valid options:

- **Distributed** Creates an instance on each server JVM in a cluster. Required for all SAF agents and for cluster-targeted or resource-group-scoped JMS servers that host distributed destinations.
- **Singleton** Creates a single instance on a single server JVM within a cluster. Required for cluster-targeted or resource-group-scoped JMS servers that host standalone (non-distributed) destinations and for cluster-targeted or resource-group-scoped path services. The `Migration Policy` must be `On-Failure` or `Always` when using this option with a JMS server, `On-Failure` when using this option with a messaging bridge, and `Always` when using this option with a path service.

Instance Naming Note:

- The `DistributionPolicy` determines the instance name suffix for cluster-targeted JMS artifacts. The suffix for a cluster-targeted `Singleton` is `-01` and for a cluster-targeted `Distributed` is `@ClusterMemberName`.

Messaging Bridge Notes:

- When an instance per server is desired for a cluster-targeted messaging bridge, Oracle recommends setting the bridge `Distributed Policy` and `Migration Policy` to `Distributed/Off`, respectively; these are the defaults.
- When a single instance per cluster is desired for a cluster-targeted bridge, Oracle recommends setting the bridge `Distributed Policy` and `Migration Policy` to `Singleton/On-Failure`, respectively.
- If you cannot cluster-target a bridge and still need singleton behavior in a configured cluster, you can target the bridge to a migratable target and configure the `Migration Policy` on the migratable target to `Exactly-Once`.

Type: string

Constraints: Has Default Value: Distributed, Legal Values: Distributed, Singleton

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

enabled

When true, TLOGs are logged to a TLOG JDBC Store; otherwise, TLOGs are logged to the server's default store.

When using the Administration Console, select **JDBC** to enable logging of TLOGs to a JDBC store; select **Default Store** to enable logging of TLOGs to the server's default store.

Type: boolean

failbackDelaySeconds

Specifies the amount of time, in seconds, to delay before failing a cluster-targeted JMS artifact instance back to its preferred server after the preferred server failed and was restarted.

This delay allows time for the system to stabilize and dependent services to be restarted, preventing a system failure during a reboot.

- A value > specifies the time, in seconds, to delay before failing a JMS artifact back to its user preferred server.
- A value of indicates that the instance would never failback.
- A value of -1 indicates that there is no delay and the instance would failback immediately.

Note: This setting only applies when the JMS artifact is cluster-targeted and the Migration Policy is set to `On-Failure` or `Always`

Type: integer/int64

Constraints: Has Default Value: -1

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

initialBootDelaySeconds

Specifies the amount of time, in seconds, to delay before starting a cluster-targeted JMS instance on a newly booted WebLogic Server instance. When this setting is configured on a store, it applies to all JMS artifacts that reference the store.

This allows time for the system to stabilize and dependent services to be restarted, preventing a system failure during a reboot.

- A value > is the time, in seconds, to delay before before loading resources after a failure and restart.
- A value of specifies no delay.

Note: This setting only applies when the JMS artifact is cluster-targeted and the Migration Policy is set to `On-Failure` or `Always`

Type: integer/int64

Constraints: Has Default Value: 60

insertsPerBatchMaximum

The maximum number of table rows that are inserted per database call.

- When possible, a JDBC store uses JDBC 3.0 batching to batch concurrent client requests.
- Both the maximum batch size for concurrent inserts and for concurrent writes are configurable.
- To disable JDBC 3.0 batching, set the maximum batch size to 1.
- The maximum batch size has no effect on the maximum number of concurrent client requests.

Type: integer/int32

Constraints: Has Default Value: 20, Minimum Value: 1, Maximum Value: 100

logicalName

The name used by subsystems to refer to different stores on different servers using the same name.

For example, an EJB that uses the timer service may refer to its store using the logical name, and this name may be valid on multiple servers in the same cluster, even if each server has a store with a different physical name.

Multiple stores in the same domain or the same cluster may share the same logical name. However, a given logical name may not be assigned to more than one store on the same server.

Type: string

Constraints: Has Default Value: null, Legal Null: true

maxRetrySecondsBeforeTLOGFail

The maximum amount of time, in seconds, WebLogic Server tries to recover from a JDBC TLog store failure. If store remains unusable after this period, WebLogic Server set the health state to `HEALTH_FAILED`. A value of 0 indicates WebLogic Server does not conduct a retry and immediately sets the health state as `HEALTH_FAILED`.

Type: integer/int32

Constraints: Has Default Value: 300, Minimum Value: 0, Maximum Value: 2147483647

maxRetrySecondsBeforeTXException

The maximum amount of time, in seconds, WebLogic Server waits before trying to recover from a JDBC TLog store failure while processing a transaction. If store remains unusable after this amount of time, WebLogic Server throws an exception the affected transaction. A value of 0 indicates WebLogic Server does not conduct a retry and an exception will thrown immediately. The practical maximum value is a value less than the current value of `MaxRetrySecondsBeforeTLogFail`

Type: integer/int32

Constraints: Has Default Value: 60, Minimum Value: 0, Maximum Value: 300

migrationPolicy

Controls migration and restart behavior of cluster-targeted JMS service artifact instances. When this setting is configured on a cluster-targeted store, it applies to all JMS artifacts that reference the store. See the migratable target settings for enabling migration and restart on migratable-targeted JMS artifacts.

- `Off` Disables migration support for cluster-targeted JMS service objects, and changes the default for Restart In Place to false. If you want a restart to be enabled when the Migration Policy is `Off`, then Restart In Place must be explicitly configured to true. This policy cannot be combined with the Singleton Migration Policy.
- `On-Failure` Enables automatic migration and restart of instances on the failure of a subsystem Service or WebLogic Server instance, including automatic fail-back and load balancing of instances.
- `Always` Provides the same behavior as `On-Failure` and automatically migrates instances even in the event of a graceful shutdown or a partial cluster start.

Note: Cluster leasing must be configured for `On-Failure` and `Always`.

Messaging Bridge Notes:

- When an instance per server is desired for a cluster-targeted messaging bridge, Oracle recommends setting the bridge `Distributed Policy` and `Migration Policy` to `Distributed/Off`, respectively; these are the defaults.
- When a single instance per cluster is desired for a cluster-targeted bridge, Oracle recommends setting the bridge `Distributed Policy` and `Migration Policy` to `Singleton/On-Failure`, respectively.
- A `Migration Policy` of `Always` is not recommended for bridges.
- If you cannot cluster-target a bridge and still need singleton behavior in a configured cluster, you can target the bridge to a migratable target and configure the `Migration Policy` on the migratable target to `Exactly-Once`.

Type: string**Constraints:** Has Default Value: Off, Legal Values: Off, On-Failure, Always**name**

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's

`javax.management.ObjectName``Name=user-specified-name`**Type:** string**Constraints:** Read Only, Legal Null: true**notes**

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) asXML PCDATA. All left angle brackets (<) are converted to the XML entity `<`.

Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string**numberOfRestartAttempts**

Specifies the maximum number of restart attempts.

- A value `>` specifies the maximum number of restart attempts.
- A value of `0` specifies the same behavior as setting `getRestartInPlace` to `false`
- A value of `-1` means infinite retry restart until it either starts or the server instance shuts down.

Type: integer/int32**Constraints:** Has Default Value: 6, Minimum Value: -1**oraclePiggybackCommitEnabled**

Enables committing a batch of INSERT or DELETE operations with the last operation of the transaction instead of issuing a separate commit call to database server which saves a server round trip. This feature benefits applications that have many transactions of a small number of operations or small messages. This feature should be used only when configuring a JDBC store in Oracle Exalogic environments.

Type: boolean

Constraints: Has Default Value: false

partialClusterStabilityDelaySeconds

Specifies the amount of time, in seconds, to delay before a partially started cluster starts all cluster-targeted JMS artifact instances that are configured with a Migration Policy of Always or On-Failure.

Before this timeout expires or all servers are running, a cluster starts a subset of such instances based on the total number of servers running and the configured cluster size. Once the timeout expires or all servers have started, the system considers the cluster stable and starts any remaining services.

This delay ensures that services are balanced across a cluster even if the servers are started sequentially. It is ignored after a cluster is fully started (stable) or when individual servers are started.

- A value > specifies the time, in seconds, to delay before a partially started cluster starts dynamically configured services.
- A value of specifies no delay.

Type: integer/int64

Constraints: Has Default Value: 240

prefixName

When using multiple TLOG JDBC stores, use this attribute to create a label ending in "_" that is prepended to the name of the server hosting the JDBC TLOG store and ends in "_" to form a unique JDBC TLOG store name for each configured JDBC TLOG store.

The default prefix name is "TLOG_". For example, a valid JDBC TLOG store name using the default Prefix Name is TLOG_MyServer_ where TLOG_ is the Prefix Name and MyServer is the name of the server hosting the JDBC TLOG store.

Type: string

reconnectRetryIntervalMillis

The length of time in milliseconds between reconnection attempts during the reconnection retry period.

The reconnection interval applies to JDBC connections regardless of the database that is used for the JDBC store.

The default value is 200 milliseconds

Type: integer/int32

Constraints: Has Default Value: 200, Minimum Value: 100, Maximum Value: 10000

reconnectRetryPeriodMillis

Returns the length of time in milliseconds during which the persistent store will attempt to re-establish a connection to the database. Successive reconnection attempts will be attempted after a fixed delay that is specified by the reconnection retry interval.

The reconnection period applies to JDBC connections regardless of the database that is used for the JDBC store.

The default value is 1000

Type: integer/int32

Constraints: Has Default Value: 1000, Minimum Value: 200, Maximum Value: 300000

restartInPlace

Enables a periodic automatic in-place restart of failed cluster-targeted or standalone-server-targeted JMS artifact instance(s) running on healthy WebLogic Server instances. See the migratable target settings for in-place restarts of migratable-targeted JMS artifacts. When the Restart In Place setting is configured on a store, it applies to all JMS artifacts that reference the store.

- If the Migration Policy of the JMS artifact is set to `Off`, Restart In Place is disabled by default.
- If the Migration Policy of the JMS artifact is set to `On-Failure` or `Always`, Restart In Place is enabled by default.
- This attribute is not used by WebLogic messaging bridges which automatically restart internal connections as needed.
- For a JMS artifact that is cluster-targeted and the Migration Policy is set to `On-Failure` or `Always`, if restart fails after the configured maximum retry attempts, it will migrate to a different server within the cluster.

Type: boolean

retryIntervalSeconds

The amount of time, in seconds, WebLogic Server waits before attempting to verify the health of the TLOG store after a store failure has occurred.

Type: integer/int32

Constraints: Has Default Value: 5, Minimum Value: 1, Maximum Value: 60

secondsBetweenRestarts

Specifies the amount of time, in seconds, to wait in between attempts to restart a failed service instance.

Type: integer/int32

Constraints: Has Default Value: 30, Minimum Value: 1

tags

Return all tags on this Configuration MBean

Type: array of string

targets

The server instances, clusters, or migratable targets defined in the current domain that are candidates for hosting a file store, JDBC store, or replicated store. If scoped to a Resource Group or Resource Group Template, the target is inherited from the Virtual Target.

When selecting a cluster, the store must be targeted to the same cluster as the JMS server. When selecting a migratable target, the store must be targeted it to the same migratable target as the migratable JMS server or SAF agent. As a best practice, a path service should use its own custom store and share the same target as the store.

Type: array of weblogic.management.configuration.TargetMBean references

threeStepThreshold

Specifies the threshold, in bytes, when the JDBC store uses 3 steps (insert, select, populate) instead of 1 step (insert) to populate an Oracle Blob data type.

Applies only to Oracle databases where a Blob data type is used instead of the default Long Raw data type for record data.

The default value is 200000.

Type: integer/int32

Constraints: Has Default Value: 200000, Minimum Value: 4000, Maximum Value: 2147483647

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

workerCount

The number of JDBC store worker threads to process the workload.

- A value of 1 indicates a single thread is used (the default).
- A value greater than 1 indicates that multiple threads are used.
- For Oracle databases, Oracle recommends users rebuild the primary key index into a reverse index for the JDBC Store table when the worker count is greater than 1.
- For non-Oracle databases, refer to the database provider's documentation for help with indexing.

Type: integer/int32

Constraints: Has Default Value: 1, Minimum Value: 1, Maximum Value: 1000

workerPreferredBatchSize

Specifies the batch size when the `Worker Count` attribute is configured to a value greater than 1.

Used to configure the workload the JDBC store incrementally puts on each worker thread. The workload consists of IO requests which are grouped and pushed to each JDBC worker thread for processing. If the IO request is very large (for example 1M), then tune this attribute to a smaller value.

Type: integer/int32

Constraints: Has Default Value: 10, Minimum Value: 1, Maximum Value: 2147483647

weblogic.management.configuration.TriggerMBean

This mbean is used to configure a Trigger (Usage limit) based policy for a resource type.

The properties of the `weblogic.management.configuration.TriggerMBean` entity are as follows:

action

Gets the configured recourse action that needs to be taken when the usage of resource crosses the value specified in `getValue()`.

Type: string

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to `config.xml`

Type: boolean

Constraints: Read Only, Has Default Value: false

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

`Name=user-specified-name`

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

tags

Return all tags on this Configuration MBean

Type: array of string

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

value

Gets the upper-limit value of the resource assigned to the Trigger configuration.

Type: integer/int64

Constraints: Minimum Value: 1

weblogic.management.configuration.VirtualHostMBean

This bean represents the configuration of virtual web server within a WebLogic Server instance. Note that a server may define multiple web servers to support virtual hosts.

This MBean represents a virtual host.

The properties of the `weblogic.management.configuration.VirtualHostMBean` entity are as follows:

WAPEnabled

Indicates whether the session ID should include JVM information. (Checking this box may be necessary when using URL rewriting with WAP devices that limit the size of the URL to 128 characters, and may also affect the use of replicated sessions in a cluster.) When this box is selected, the default size of the URL will be set at 52 characters, and it will not contain any special characters.

Gets the WAPEnabled attribute of the WebServerMBean object

Type: boolean

Constraints: Has Default Value: false

acceptContextPathInGetRealPath

Indicates whether this server allows the inclusion of the context path in the virtual path to `context.getRealPath()`. (If checked, you cannot use sub directories with the same name as `contextPath`). This is a compatibility switch that will be deprecated 9.0.0.0 in future releases.

Gets the acceptContextPathInGetRealPath attribute of the WebServerMBean object

Type: boolean

Constraints: Has Default Value: false

authCookieEnabled

Whether authcookie feature is enabled or not.

Type: boolean

Constraints: Has Secure Value: true, Has Default Value: true

chunkedTransferDisabled

Indicates whether the use of Chunk Transfer-Encoding in HTTP/1.1 is enabled.

Type: boolean

Constraints: Has Default Value: false

clientIpHeader

Get the Client IP Header from WebServerMBean.

Type: string

defaultWebAppContextRoot

Returns the original context-root for the default Web application for this Web server. Alternatively, you can use the context-root attributes in `application.xml` or `weblogic.xml` to set a default Web application. The context-root for a default Web application is `/`. If "" (empty string) is specified, the Web server defaults to `/`.

Type: string

deploymentOrder

A priority that the server uses to determine when it deploys an item. The priority is relative to other deployable items of the same type.

For example, the server prioritizes and deploys all EJBs before it prioritizes and deploys startup classes.

Items with the lowest Deployment Order value are deployed first. There is no guarantee on the order of deployments with equal Deployment Order values. There is no guarantee of ordering across clusters.

Type: integer/int32

Constraints: Has Default Value: 1000, Minimum Value: 0, Maximum Value: 2147483647

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

frontendHTTPPort

The name of the HTTP port to which all redirected URLs will be sent. If specified, WebLogic Server will use this value rather than the one in the HOST header.

Sets the frontendHTTPPort Provides a method to ensure that the webapp will always have the correct PORT information, even when the request is coming through a firewall or a proxy. If this parameter is configured, the HOST header will be ignored and the information in this parameter will be used in its place.

Type: integer/int32

Constraints: Has Default Value: 0

frontendHTTPSPort

The name of the secure HTTP port to which all redirected URLs will be sent. If specified, WebLogic Server will use this value rather than the one in the HOST header.

Sets the frontendHTTPSPort Provides a method to ensure that the webapp will always have the correct PORT information, even when the request is coming through a firewall or a proxy. If this parameter is configured, the HOST header will be ignored and the information in this parameter will be used in its place.

Type: integer/int32

Constraints: Has Default Value: 0

frontendHost

The name of the host to which all redirected URLs will be sent. If specified, WebLogic Server will use this value rather than the one in the HOST header.

Sets the HTTP frontendHost Provides a method to ensure that the webapp will always have the correct HOST information, even when the request is coming through a firewall or a proxy. If this parameter is configured, the HOST header will be ignored and the information in this parameter will be used in its place.

Type: string

Constraints: Has Default Value: null

httpsKeepAliveSecs

The amount of time this server waits before closing an inactive HTTPS connection.

Number of seconds to maintain HTTPS keep-alive before timing out the request.

Type: integer/int32

Constraints: Has Secure Value: 60, Has Default Value: 60, Minimum Value: 30, Maximum Value: 360

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

keepAliveEnabled

Indicates whether there should be a persistent connection to this server. (This may improve the performance of your Web applications.)

Gets the keepAliveEnabled attribute of the WebServerMBean object

Type: boolean

Constraints: Has Secure Value: true, Has Default Value: true

keepAliveSecs

The amount of time this server waits before closing an inactive HTTP connection.

Number of seconds to maintain HTTP keep-alive before timing out the request.

Type: integer/int32

Constraints: Has Secure Value: 30, Has Default Value: 30, Minimum Value: 5, Maximum Value: 3600

maxPostSize

The maximum post size this server allows for reading HTTP POST and PUT data in a servlet request.

A value less than 0 indicates an unlimited size.

Gets the maxPostSize attribute of the WebServerMBean object

Type: integer/int32

Constraints: Has Default Value: -1

maxPostTimeSecs

Max Post Time (in seconds) for reading HTTP POST data in a servlet request.

MaxPostTime < 0 means unlimited

Gets the maxPostTimeSecs attribute of the WebServerMBean object

Type: integer/int32

Constraints: Has Default Value: -1

maxRequestParameterCount

Max Request Parameter Count this server allows for reading maximum HTTP POST Parameters count in a servlet request.

Gets the maxRequestParameterCount attribute of the WebServerMBean object

Type: integer/int32

Constraints: Has Default Value: 10000

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's

`javax.management.ObjectName`

Name=user-specified-name

Type: string

Constraints: Read Only, Legal Null: true

networkAccessPoint

The dedicated server channel name (NetworkAccessPoint) for which this virtual host will serve http request. If the NetworkAccessPoint for a given http request doesn't match any virtual host's NetworkAccessPoint, incoming HOST header will be matched with the VirtualHostNames in order to resolve the right virtual host.

Type: string

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (config.xml) as XML PCDATA. All left angle brackets (<) are converted to the XML entity <. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

overloadResponseCode

Get the response code to be used when an application is overloaded. An application can get overloaded when the number of pending requests has reached the max capacity specified in the WorkManager or when the server is low on memory. The low memory condition is determined using OverloadProtectionMBean#getFreeMemoryPercentLowThreshold().

Type: integer/int32

Constraints: Has Default Value: 503, Minimum Value: 100, Maximum Value: 599

postTimeoutSecs

Timeout (in seconds) for reading HTTP POST data in a servlet request. If the POST data is chunked, the amount of time the server waits between the end of receiving the last chunk of data and the end of receiving the next chunk of data in an HTTP POST before it times out. (This is used to prevent denial-of-service attacks that attempt to overload the server with POST data.)

Gets the postTimeoutSecs attribute of the WebServerMBean object

Type: integer/int32

Constraints: Has Secure Value: 30, Has Default Value: 30, Minimum Value: 0, Maximum Value: 120

sendServerHeaderEnabled

Indicates whether this server name is sent with the HTTP response. (This is useful for wireless applications where there is limited space for headers.)

Indicates whether this server instance includes its name and WebLogic Server version number in HTTP response headers.

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

singleSignonDisabled

Indicates whether the singleSignonDisabled attribute is enabled

Type: boolean

Constraints: Has Default Value: false

tags

Return all tags on this Configuration MBean

Type: array of string

targets

You must select a target on which an MBean will be deployed from this list of the targets in the current domain on which this item can be deployed. Targets must be either servers or clusters. The deployment will only occur once if deployments overlap.

Type: array of weblogic.management.configuration.TargetMBean references

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

useHeaderEncoding

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

useHighestCompatibleHTTPVersion

Enables use of the highest compatible HTTP protocol version-string in the response. E.g. HTTP spec suggests that HTTP/1.1 version-string should be used in response to a request using HTTP/1.0. This does not necessarily affect the response format.

Type: boolean

Constraints: Has Default Value: true

virtualHostNames

The list of host names, separated by line breaks, for which this virtual host will serve requests.

Type: array of string

writeChunkBytes

The default size of the blocks to be written to the network layer.

Gets the writeChunkBytes attribute of the WebServerMBean object

Type: integer/int32

Constraints: Read Only, Has Default Value: 512

weblogic.management.configuration.VirtualTargetMBean

This bean represents a target for a resource group in a partition. It defines access point to resources, i.e. hostname, port, partition uri path. Moreover, it provide configurations for each protocol, for example, http, t3, ssl, iiop etc.

The properties of the weblogic.management.configuration.VirtualTargetMBean entity are as follows:

deploymentOrder

A priority that the server uses to determine when it deploys an item. The priority is relative to other deployable items of the same type.

For example, the server prioritizes and deploys all EJBs before it prioritizes and deploys startup classes.

Items with the lowest Deployment Order value are deployed first. There is no guarantee on the order of deployments with equal Deployment Order values. There is no guarantee of ordering across clusters.

Type: integer/int32

Constraints: Has Default Value: 1000, Minimum Value: 0, Maximum Value: 2147483647

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

explicitPort

Get the explicit port for this virtual target.

Type: integer/int32

Constraints: Has Default Value: 0, Minimum Value: 0, Maximum Value: 65535

hostNames

Host names, separated by line breaks, for which this virtual target will serve requests.

Type: array of string

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

Name=user-specified-name

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`;

Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

partitionChannel

The channel name to be used as a reference for creating a partition specific channel.

Type: string

Constraints: Has Default Value: PartitionChannel

portOffset

The port offset for this virtual target. If set to the minimum value, the port offset is not set.

Type: integer/int32

Constraints: Has Default Value: 0, Minimum Value: 0, Maximum Value: 65535

tags

Return all tags on this Configuration MBean

Type: array of string

targets

You must select a target from this list of the targets in the current domain. Targets must be either servers or clusters. The deployment will only occur once if the targets overlap. For example, if a deployment is deployed both on a cluster C and on a server S that is a member of that cluster, the deployment will be deployed on server S only once.

Type: array of weblogic.management.configuration.TargetMBean references

Constraints: Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

uriPrefix

The URI prefix for this virtual target.

Type: string

Constraints: Has Default Value: /

weblogic.management.configuration.WLDFDataRetirementByAgeMBean

This MBean specifies how data retirement for a WLDF archive will be performed based on the age of records in WLDF archives.

The properties of the weblogic.management.configuration.WLDFDataRetirementByAgeMBean entity are as follows:

archiveName

Name of the archive for which data retirement is configured

Type: string

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

enabled

Enable data retirement

Type: boolean

Constraints: Has Default Value: true

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

Name=user-specified-name

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

retirementAge

Retirement age for records in hours. Older records will be eligible for deletion.

Type: integer/int32

Constraints: Has Default Value: 72, Minimum Value: 1

retirementPeriod

This attribute specifies the period in hours at which the data retirement task will be periodically performed for the archive during the day after it is first executed. The value of this attribute must be positive

Type: integer/int32

Constraints: Has Default Value: 24, Minimum Value: 1

retirementTime

This attribute specifies the hour of day at which the data retirement task will first run during the day.

Type: integer/int32

Constraints: Has Default Value: 0

tags

Return all tags on this Configuration MBean

Type: array of string

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.WLDFServerDiagnosticMBean

Use this interface to configure the WebLogic Diagnostic Framework (WLDF) components that are defined for each WebLogic Server instance.

The properties of the weblogic.management.configuration.WLDFServerDiagnosticMBean entity are as follows:

WLDFBuiltinSystemResourceType

This attribute specifies the WLDF built-in system resource type in use for this server.

This attribute has the following settings:

- **None** No WLDF built-in system resource in use.
- **Low** The Low WLDF built-in system resource. This is the default.
- **Medium** The Medium built-in system resource.
- **High** The High built-in system resource.

Type: string

Constraints: Has Default Value: None, Has Production Mode Default Value: Low, Legal Values: None, Low, Medium, High

WLDFDataRetirements

Return the WLDFDataRetirementMBeans parented by this WLDFServerDiagnosticMBean.

Type: array of weblogic.management.configuration.WLDFDataRetirementMBean references

Constraints: Read Only

WLDFDiagnosticVolume

Specifies the volume of diagnostic data that is automatically produced by WebLogic Server at run time. Note that the WLDF diagnostic volume setting does not affect explicitly configured diagnostic modules. For example, this controls the volume of events generated for Flight Recorder.

This attribute has the following settings:

- **Off** No diagnostic data is produced.
- **Low** Minimal amounts of automatic diagnostic data are produced. This is the default.
- **Medium** Additional diagnostic data is automatically generated beyond the amount generated for Low
- **High** Additional diagnostic data is automatically generated beyond the amount generated for Medium

Type: string

Constraints: Has Default Value: Low, Legal Values: Off, Low, Medium, High

dataRetirementEnabled

This attribute controls if configuration based data retirement functionality is enabled on the server. If disabled, all retirement policies will be disabled.

Type: boolean

Constraints: Has Default Value: true

diagnosticDataArchiveType

Determines whether the current server persists its harvested metrics and event data in a diagnostic store (file-based store) or a JDBC based archive. The default store is file-based.

Type: string

Constraints: Has Default Value: FileStoreArchive, Legal Values: FileStoreArchive, JDBCArchive

diagnosticDumpsDir

Directory where heap and thread dumps will be generated by actions. This directory is a relative path with respect to the server directory

Type: string

Constraints: Has Default Value: logs/diagnostic_dumps

diagnosticJDBCResource

The JDBC data source that the server uses to archive its harvested metrics and event data.

Type: weblogic.management.configuration.JDBCSystemResourceMBean reference

Constraints: Restart Required

diagnosticJDBCSchemaName

The schema name to use for accessing JDBC-based archive tables.

If multiple WLDF JDBC archive schemas exist in the same database, this value specifies the correct schema to use for accessing JDBC-based archive tables in that database.

There is no default value. If a schema name is not specified, no schema name is applied when WLDF validates the run-time table or is used for the SQL statements.

Type: string

diagnosticStoreBlockSize

The smallest addressable block, in bytes, of a file. When a native `wfileio` driver is available and the block size has not been configured by the user, the store selects the minimum OS specific value for unbuffered (direct) I/O, if it is within the range [512, 8192].

A file store's block size does not change once the file store creates its files. Changes to block size only take effect for new file stores or after the current files have been deleted. See "Tuning the Persistent Store" in *Performance and Tuning for Oracle WebLogic Server*

Type: integer/int32

Constraints: Has Default Value: -1, Minimum Value: -1, Maximum Value: 8192

diagnosticStoreDir

The directory in which the current server maintains its diagnostic store.

Type: string

Constraints: Has Default Value: data/store/diagnostics

diagnosticStoreFileLockingEnabled

Determines whether OS file locking is used.

When file locking protection is enabled, a store boot fails if another store instance already has opened the store files. Do not disable this setting unless you have procedures in place to prevent multiple store instances from opening the same file. File locking is not required but helps prevent corruption in the event that two same-named file store instances attempt to operate in the same directories. This setting applies to both primary and cache files.

Type: boolean

Constraints: Has Default Value: true

diagnosticStoreIoBufferSize

The I/O buffer size, in bytes, automatically rounded down to the nearest power of 2, controls the largest write size.

- When a native `wfileio` driver is available, the setting applies to off-heap (native) memory.
- When a native `wfileio` driver is not available, the setting applies to JAVA heap memory.
- For the best runtime performance, Oracle recommends setting `DiagnosticStoreIoBufferSize` so that it is larger than the largest write (multiple concurrent store requests may be combined into a single write).
- See `AllocatedIoBufferBytes` to find out the actual allocated off-heap (native) memory amount. It is a multiple of `IoBufferSize`

Type: integer/int32

Constraints: Has Default Value: -1, Minimum Value: -1, Maximum Value: 67108864

diagnosticStoreMaxFileSize

The maximum file size, in bytes.

- The `DiagnosticStoreMaxFileSize` value affects the number of files needed to accommodate a diagnostic store of a particular size (number of files = diagnostic store size/MaxFileSize rounded up).
- A diagnostic store automatically reuses space freed by deleted records and automatically expands individual files up to `DiagnosticStoreMaxFileSize` if there is not enough space for a new record. If there is no space left in existing files for a new record, a diagnostic store creates an additional file.
- A small number of larger files is normally preferred over a large number of smaller files as each file allocates Window Buffer and file handles.
- If `DiagnosticStoreMaxFileSize` is larger than $2^{24} * \text{DiagnosticStoreBlockSize}$, then `DiagnosticStoreMaxFileSize` is ignored, and the value becomes $2^{24} * \text{DiagnosticStoreBlockSize}$. The default `DiagnosticStoreBlockSize` is 512, and $2^{24} * 512$ is 8 GB.

Oracle recommends not setting the Diagnostic Store Max File Size above the default value of 1,342,177,280.

Type: integer/int64

Constraints: Has Default Value: 1342177280, Minimum Value: 10485760

diagnosticStoreMaxWindowBufferSize

The maximum amount of data, in bytes and rounded down to the nearest power of 2, mapped into the JVM's address space per diagnostic store file. Applies only when a native `wfileio` library is loaded.

A window buffer does not consume Java heap memory, but does consume off-heap (native) memory. If the store is unable to allocate the requested buffer size, it allocates smaller and smaller buffers until it reaches `DiagnosticStoreMinWindowBufferSize`, and then fails if it cannot honor `DiagnosticStoreMinWindowBufferSize`.

Oracle recommends setting the max window buffer size to more than double the size of the largest write (multiple concurrently updated records may be combined into a single write), and greater than or equal to the file size, unless there are other constraints. 32-bit JVMs may impose a total limit of between 2 and 4GB for combined Java heap plus off-heap (native) memory usage.

Type: integer/int32

Constraints: Has Default Value: 4194304, Minimum Value: -1, Maximum Value: 1073741824

diagnosticStoreMinWindowBufferSize

The minimum amount of data, in bytes and rounded down to the nearest power of 2, mapped into the JVM's address space per diagnostic store file. Applies only when a native `wfileio` library is loaded. See Diagnostic Store Maximum Window Buffer Size.

Type: integer/int32

Constraints: Has Default Value: -1, Minimum Value: -1, Maximum Value: 1073741824

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to `config.xml`.

Type: boolean

Constraints: Read Only, Has Default Value: false

eventPersistenceInterval

The interval, in milliseconds, at which queued up instrumentation events will be periodically dispatched to the archive.

Type: integer/int64

Constraints: Has Default Value: 5000

eventsImageCaptureInterval

The time span, in milliseconds, for which recently archived events will be captured in the diagnostic image. All events archived on or after (`System.currentTimeMillis() - interval`) will be captured.

Type: integer/int64

Constraints: Has Default Value: 60000

id

Return the unique id of this MBean instance.

Type: integer/int64

Constraints: Read Only

imageDir

The default directory where the server stores captured diagnostic images.

If you specify a relative pathname, the root of that path is the server's root directory.

If the directory does not exist, it will be created when the WebLogic Diagnostic Framework is initialized on the server. Note that each image capture request can override this default directory location.

Type: string

imageTimeout

The default timeout period, in minutes, that the server uses to delay future diagnostic image-capture requests.

Type: integer/int32

Constraints: Has Default Value: 1, Minimum Value: 0, Maximum Value: 1440

maxHeapDumpCount

Returns the maximum number of heap dump files to be retained which are generated by heap dump actions. If this limit is reached, oldest heap dumps will be deleted while creating new heap dump so that this limit is not exceeded.

Type: integer/int32

Constraints: Has Default Value: 8, Minimum Value: 1, Maximum Value: 50

maxThreadDumpCount

Returns the maximum number of thread dump files to be retained which are generated by thread dump actions. If this limit is reached, oldest thread dump files will be deleted while creating new thread dump file so that this limit is not exceeded.

Type: integer/int32

Constraints: Has Default Value: 100, Minimum Value: 1, Maximum Value: 1000

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's

`javax.management.ObjectName`

`Name=user-specified-name`

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

preferredStoreSizeLimit

Return the preferred limit on the size of diagnostic store file in MB.

Type: integer/int32

Constraints: Has Default Value: 100, Minimum Value: 10

storeSizeCheckPeriod

Return the period in hours at which diagnostic store file size check will be performed

Type: integer/int32

Constraints: Has Default Value: 1, Minimum Value: 1

synchronousEventPersistenceEnabled

Specifies the instrumentation events persistence policy. If true, events will be persisted synchronously within the same thread. If false, events will be queued up to be persisted in a separate thread.

Type: boolean

Constraints: Has Default Value: false

tags

Return all tags on this Configuration MBean

Type: array of string

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.WLDFSystemResourceMBean

This bean defines a system-level WebLogic Diagnostic Framework (WLDF) resource. It links a separate descriptor that specifies the definition.

The properties of the weblogic.management.configuration.WLDFSystemResourceMBean entity are as follows:

compatibilityName

This is only set for beans created as a result of conversion from an 8.1 application configured using ApplicationMBean and ComponentMBean.

Standalone modules in 8.1 have both an ApplicationMBean name and ComponentMBean name. This attribute stores the name of the latter, to be used when the server creates the transient ComponentMBean for backward compatibility.

Type: string

deploymentOrder

An integer value that indicates when this unit is deployed, relative to other deployable units on a server, during startup.

Units with lower values are deployed before those with higher values.

Type: integer/int32

Constraints: Has Default Value: 100

deploymentPrincipalName

A string value that indicates the principal that should be used when deploying the file or archive during startup and shutdown. This principal will be used to set the current subject when calling out into application code for interfaces such as

ApplicationLifecycleListener. If no principal name is specified, then the anonymous principal will be used.

Type: string

description

Optional short description of this WLDFSystemResource. If provided, the WebLogic Server Administration Console will display the resource description.

Type: string

Constraints: Has Default Value: null

descriptorFileName

The name of the descriptor file that contains the XML configuration information for this system-level resource. The location of this file is a relative path rooted at *DOMAIN_DIR/config*. By default the file resides in the *DOMAIN_DIR/config/diagnostics* directory, and derives its name from the bean name using the following pattern:

<beanName>.xml

Note that the filename is a read-only property, which is set when the WLDF resource is created.

Type: string

Constraints: Read Only

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

moduleType

The values match those defined by jsr88. This attribute may move to another MBean.

Type: string

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

Name=user-specified-name

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

resource

Return the Descriptor for the system resource. This should be overridden by the derived system resources.

Type: weblogic.descriptor.DescriptorBean reference

Constraints: Read Only

sourcePath

Type: string

tags

Return all tags on this Configuration MBean

Type: array of string

targets

You must select a target on which an MBean will be deployed from this list of the targets in the current domain on which this item can be deployed. Targets must be either servers or clusters. The deployment will only occur once if deployments overlap.

Type: array of weblogic.management.configuration.TargetMBean references

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.WSReliableDeliveryPolicyMBean

This class represents the reliable messaging delivery policy for the current WebLogic Server as both a sender and a receiver of a reliable SOAP message to and from a Web service running on a different WebLogic Server.

Reliable messaging is a framework for applications running in WebLogic Server to asynchronously and reliably invoke a Web service running in a different WebLogic Server. Reliable messaging works only between WebLogic Servers. This class encapsulates the default reliable messaging parameters for an application running in this WebLogic Server instance that both sends and receives a SOAP message reliably. These parameters include the number of times to retry sending the message, the time to wait between retries, the persistent store for the reliable message, and so on.

The properties of the weblogic.management.configuration.WSReliableDeliveryPolicyMBean entity are as follows:

JMServer

The JMS server used by WebLogic Server, in its role as a sender, to persist the reliable messages that it sends, or the JMS server used by the receiver WebLogic Server to persist the history of a reliable message sent by a sender.

Type: weblogic.management.configuration.JMServerMBean reference

Constraints: Restart Required

defaultRetryCount

The default maximum number of times that the sender runtime should attempt to redeliver a message that the receiver WebLogic Server has not yet acknowledged.

The default maximum number of times that the sender should attempt to redeliver a message that the receiver WebLogic Web service has not yet acknowledged.

Type: integer/int32

Constraints: Has Default Value: 10

defaultRetryInterval

The default minimum number of seconds that the sender runtime should wait between retries if the receiver does not send an acknowledgement of receiving the message, or if the sender runtime detects a communications error while attempting to send a message.

The default minimum number of seconds that the sender should wait between retries if the receiver does not send an acknowledgement of receiving the message, or if the sender detects a communications error while attempting to send a message.

Type: integer/int32

Constraints: Has Default Value: 6

defaultTimeToLive

The default number of seconds that the receiver of the reliable message should persist the history of the reliable message in its store.

The default minimum number of seconds that the receiver of the reliably sent message should persist the message in its storage.

If the DefaultTimeToLive number of message have passed since the message was first sent, the sender should not resent a message with the same message id.

If a sender cannot send a message successfully before the DefaultTimeToLive has passed, the sender should report a delivery failure. The receiver, after recovering from a crash, will not dispatch saved messages that have expired.

Type: integer/int32

Constraints: Has Default Value: 360

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

Name=*user-specified-name*

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

tags

Return all tags on this Configuration MBean

Type: array of string

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.WTCEXportMBean

This interface provides access to the WTC export configuration attributes. The methods defined herein are applicable for WTC configuration at the WLS domain level.

The properties of the `weblogic.management.configuration.WTCEXportMBean` entity are as follows:

EJBName

The complete name of the EJB home interface to use when invoking a service.

If not specified, the default interface used is `tuxedo.services.servicenameHome`. For example: If the service being invoked is TOUPPER and EJBName attribute is not specified, the home interface looked up in JNDI would be `tuxedo.services.TOUPPERHome`

Type: string

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to `config.xml`

Type: boolean

Constraints: Read Only, Has Default Value: false

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

localAccessPoint

The name of the local access point that exports this service.

Type: string

Constraints: Has Default Value: myLAP, Legal Null: true

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

Name=user-specified-name

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

remoteName

The remote name of this service.

If this value is not specified, the `ResourceName` value is used.

Type: string

resourceName

The name used to identify an exported service.

The combination of `ResourceName` and `LocalAccessPoint` must be unique within defined Exports. This allows you to define unique configurations having the same `ResourceName`.

Type: string

Constraints: Has Default Value: myExport, Legal Null: true

tags

Return all tags on this Configuration MBean

Type: array of string

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.WTCImportMBean

This interface provides access to the WTC import configuration attributes. The methods defined herein are applicable for WTC configuration at the WLS domain level.

The properties of the weblogic.management.configuration.WTCImportMBean entity are as follows:

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

localAccessPoint

The name of the local access point that offers this service.

Type: string

Constraints: Has Default Value: myLAP, Legal Null: true

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

Name=user-specified-name

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`;

Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

remoteAccessPointList

The comma-separated failover list that identifies the remote domain access points through which resources are imported.

For example: TDOM1, TDOM2, TDOM3

Type: string

Constraints: Has Default Value: myRAP, Legal Null: true

remoteName

The remote name of this service.

Note: If not specified, the ResourceName value is used.

Type: string

resourceName

The name used to identify this imported service.

Note: This name must be unique within defined Imports. This allows you to define unique configurations having the same Remote Name.

Type: string

Constraints: Has Default Value: myImport, Legal Null: true

tags

Return all tags on this Configuration MBean

Type: array of string

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.WTCLocalTuxDomMBean

This interface provides access to the WTC local Tuxedo Domain configuration attributes. The methods defined herein are applicable for WTC configuration at the WLS domain level.

The properties of the weblogic.management.configuration.WTCLocalTuxDomMBean entity are as follows:

NWAddr

The network address and port number of this local Tuxedo access point.

Specify the address in one of the following formats:

- TCP/IP address in the format //hostname:port_number or //#.##.##:port_number
- SDP address in the format sdp://hostname:port_number or sdp://#.##.##:port_number

Notes:

- If the hostname is used, the access point finds an address for hostname using the local name resolution facilities (usually DNS). If dotted decimal format is used, each # should be a number from 0 to 255. This dotted decimal number represents the IP address of the local machine. The port_number is the TCP/SDP port number at which the access point listens for incoming requests.
- If SDP format address is specified, the transport protocol for this access point is SDP instead of TCP. This feature is only available when WTC and Tuxedo domain gateway are both deployed on Oracle Exalogic platform. Requires Tuxedo 11gR1PS2 and higher.

Type: string

Constraints: Has Default Value: //localhost:8901

SSLProtocolVersion

The protocol version of the SSL connection this local access point uses when establishing a SSL connection.

Value Restrictions:

- TLSv1.0
- TLSv1.1
- TLSv1.2

Type: string

Constraints: Has Default Value: TLSv1.2, Legal Values: TLSv1.0, TLSv1.1, TLSv1.2

accessPoint

The unique name used to identify this local Tuxedo access point. This name should be unique for all local and remote Tuxedo access points defined within a WTC Service. This allows you to define unique configurations having the same Access Point ID.

Type: string

Constraints: Has Default Value: myLAP, Legal Null: true

accessPointId

The connection principal name used to identify this local Tuxedo access point when attempting to establish a session connection with remote Tuxedo access points.

Note: The AccessPointId must match the corresponding DOMAINID in the *DM_REMOTE_DOMAINS section of your Tuxedo DMCONFIG file.

Type: string

Constraints: Has Default Value: myLAPId, Legal Null: true

blockTime

The maximum number of seconds this local Tuxedo access point allows for a blocking call.

Range of Values: Between and a positive 32 bit integer.

Type: integer/int64

Constraints: Has Default Value: 60, Minimum Value: 0, Maximum Value: 2147483647

cmpLimit

The compression threshold this local Tuxedo access point uses when sending data to a remote Tuxedo access point. Application buffers larger than this size are compressed.

Range of Values: Between and a positive 32-bit integer.

Type: integer/int32

Constraints: Has Default Value: 2147483647, Minimum Value: 0, Maximum Value: 2147483647

connPrincipalName

The principal name used to verify the identity of this domain when establishing a connection to another domain.

Note: This parameter only applies to domains of type TDOMAIN that are running Oracle Tuxedo 7.1 or later software. If not specified, the connection principal name defaults to the AccessPointID for this domain.ConnPrincipalName

Note: ConnPrincipalName is not supported in this release.

Type: string

connectionPolicy

The conditions under which this local Tuxedo access point establishes a session connection with a remote Tuxedo access point.

The connection policies are:

- **ON_DEMAND:** A connection is attempted only when requested by either a client request to a remote service or an administrative connect command.
- **ON_STARTUP:** A domain gateway attempts to establish a connection with its remote Tuxedo access points at gateway server initialization time. Remote services (services advertised in JNDI by the domain gateway for this local access point) are advertised only if a connection is successfully established to that remote Tuxedo access point. If there is no active connection to a remote Tuxedo access point, then the remote services are suspended. By default, this connection policy retries failed connections every 60 seconds. Use the MaxRetry and RetryInterval values to specify application specific values.
- **INCOMING_ONLY:** A domain gateway does not attempt an initial connection to remote Tuxedo access points at startup and remote services are initially suspended. The domain gateway is available for incoming connections from remote Tuxedo access points and remote services are advertised when the domain gateway for this local Tuxedo access point receives an incoming connection. Connection retry processing is not allowed.

Type: string

Constraints: Has Default Value: ON_DEMAND, Legal Values: ON_DEMAND, ON_STARTUP, INCOMING_ONLY

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

identityKeyStoreFileName

The path and file name of the identity keystore.

The path name must either be absolute or relative to where the server was booted. The identity key store file name is only used if KeystoreLocation is "Custom Stores".

Type: string

Constraints: Has Default Value: null

identityKeyStorePassPhrase

The custom identity keystore's passphrase. If empty or null, then the keystore will be opened without a passphrase.

This attribute is only used if KeyStores is "Custom Stores".

When you get the value of this attribute, WebLogic Server does the following:

1. Retrieves the value of the `IdentityKeyStorePassPhraseEncrypted` attribute.
2. Decrypts the value and returns the unencrypted password as a String.

When you set the value of this attribute, WebLogic Server does the following:

1. Encrypts the value.
2. Sets the value of the `CustomIdentityKeyStorePassPhraseEncrypted` attribute to the encrypted value.

Using this attribute (`CustomIdentityKeyStorePassPhrase`) is a potential security risk because the String object (which contains the unencrypted password) remains in the JVM's memory until garbage collection removes it and the memory is reallocated. Depending on how memory is allocated in the JVM, a significant amount of time could pass before this unencrypted data is removed from memory.

Instead of using this attribute, use `CustomIdentityKeyStorePassPhraseEncrypted`

Type: string

Constraints: Encrypted

interoperate

Specifies whether this local Tuxedo access point interoperates with remote Tuxedo access points that are based upon Tuxedo release 6.5. If this value is set to `Yes`, the local Tuxedo access point interoperates with a Tuxedo 6.5 domain.

Type: string

Constraints: Has Default Value: No, Legal Values: Yes, No

keepAlive

Return value tells whether this local Tuxedo access point is configured with Application Level Keep Alive, and its maximum idle time value before wait timer start ticking.

Type: integer/int32

Constraints: Has Default Value: 0, Minimum Value: 0, Maximum Value: 2147483647

keepAliveWait

Return value that tells whether this local Tuxedo access point requires the acknowledgement of Application Level Keep Alive, and how long it will wait without receiving acknowledgement before declare the connection is inaccessible.

Type: integer/int32

Constraints: Has Default Value: 0, Minimum Value: 0, Maximum Value: 2147483647

keyStoresLocation

Provides the configuration rule to be used for finding Local Access Point's identity key store and trust key store. In plain text, it contains information on where the identity key store and trust key store are configured. When `KeyStoreLocation` is configured with `WLS Store`, WTC uses configuration information from the WLS Key Stores

configuration. Otherwise, it uses the key stores information configured in the Local Access Point.

Type: string

Constraints: Has Default Value: Custom Stores, Legal Values: WLS Stores, Custom Stores

maxEncryptBits

The maximum encryption key length (in bits) this local Tuxedo access point uses when establishing a session connection. A value of indicates no encryption is used.

Value Restrictions:

- The MaxEncryptBits value must be greater than or equal to the MinEncrypBits value.
- A MaxEncryptBits of 40 can be used only with domains running Tuxedo 7.1 or higher.

Type: string

Constraints: Has Secure Value: 128, Has Default Value: 128, Legal Values: 0, 40, 56, 128, 256

maxRetries

The maximum number of times that this local Tuxedo access point tries to establish a session connection to remote Tuxedo access points. Use this value only when Connection Policy is set to ON_STARTUP

Range of Values: Between and a positive 64 bit integer.

Note: Use the minimum value to disable the retry mechanism. Use the maximum value to try until a connection is established.

Type: integer/int64

Constraints: Has Default Value: 9223372036854775807, Minimum Value: 0, Maximum Value: 9223372036854775807

minEncryptBits

The minimum encryption key length (in bits) this local Tuxedo access point uses when establishing a session connection. A value of indicates no encryption is used.

Value Restrictions:

- The MinEncrypBits value must be less than or equal to the MaxEncrypBits value.
- A MinEncrypBits value of 40 can be used only with domains running Tuxedo 7.1 or higher.

Type: string

Constraints: Has Secure Value: 40, Has Default Value: 0, Legal Values: 0, 40, 56, 128, 256

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

`Name=user-specified-name`

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`.

Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

privateKeyAlias

The string alias used to store and retrieve the Local Tuxedo access point's private key in the keystore. This private key is associated with the Local Tuxedo access point's digital certificate.

Type: string

Constraints: Has Default Value: null

privateKeyPassPhrase

The passphrase used to retrieve the server's private key from the keystore. This passphrase is assigned to the private key when it is generated.

When you get the value of this attribute, WebLogic Server does the following:

1. Retrieves the value of the `PrivateKeyPassPhraseEncrypted` attribute.
2. Decrypts the value and returns the unencrypted passphrase as a String.

When you set the value of this attribute, WebLogic Server does the following:

1. Encrypts the value.
2. Sets the value of the `PrivateKeyPassPhraseEncrypted` attribute to the encrypted value.

Using this attribute (`PrivateKeyPassPhrase`) is a potential security risk because the String object (which contains the unencrypted passphrase) remains in the JVM's memory until garbage collection removes it and the memory is reallocated. Depending on how memory is allocated in the JVM, a significant amount of time could pass before this unencrypted data is removed from memory.

Instead of using this attribute, use `getPrivateKeyPassPhraseEncrypted`

Type: string

Constraints: Encrypted

retryInterval

The number of seconds that this local Tuxedo access point waits between automatic connection attempts to remote Tuxedo access points. Use this value only when Connection Policy is set to `ON_STARTUP`

Range of Values: Between 0 and a positive 32-bit integer.

Type: integer/int64

Constraints: Has Default Value: 60, Minimum Value: 0, Maximum Value: 2147483647

security

The type of application security enforced.

The types of security are:

- NONE: No security is used.
- APP_PW: Password security is enforced when a connection is established from a remote domain. The application password is defined in the WTCResourcesMBean.
- DM_PW: Domain password security is enforced when a connection is established from a remote domain. The domain password is defined in the WTCPasswordsMBean.

Type: string

Constraints: Has Secure Value: DM_PW, Has Default Value: NONE, Legal Values: NONE, APP_PW, DM_PW

tags

Return all tags on this Configuration MBean

Type: array of string

trustKeyStoreFileName

The path and file name of the trust keystore.

The path name must either be absolute or relative to where the server was booted. This file name is only used if KeyStores is "Custom Stores".

Type: string

Constraints: Has Default Value: null

trustKeyStorePassPhrase

The trust keystore's passphrase. If empty or null, then the keystore will be opened without a passphrase.

This attribute is only used if KeyStores is "Custom Stores".

When you get the value of this attribute, WebLogic Server does the following:

1. Retrieves the value of the TrustKeyStorePassPhraseEncrypted attribute.
2. Decrypts the value and returns the unencrypted password as a String.

When you set the value of this attribute, WebLogic Server does the following:

1. Encrypts the value.
2. Sets the value of the TrustKeyStorePassPhraseEncrypted attribute to the encrypted value.

Using this attribute (TrustKeyStorePassPhrase) is a potential security risk because the String object (which contains the unencrypted password) remains in the JVM's memory until garbage collection removes it and the memory is reallocated. Depending on how memory is allocated in the JVM, a significant amount of time could pass before this unencrypted data is removed from memory.

Instead of using this attribute, use TrustKeyStorePassPhraseEncrypted

Type: string

Constraints: Encrypted

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

useSSL

Specifies if the connection initiated or accepted by this Local Tuxedo access point uses SSL on top of its transport layer. Values are:

- Off: SSL not used.
- TwoWay: Mutual Authentication with SSL required.
- OneWay: Server Authentication with SSL required.

Note: If SDP transport is configured for this access point, the configured value of this attribute is ignored and `off` is used.

Type: string

Constraints: Has Default Value: Off, Legal Values: Off, TwoWay, OneWay

weblogic.management.configuration.WTCPasswordMBean

This interface provides access to the WTC password configuration attributes. The methods defined herein are applicable for WTC configuration at the WLS domain level.

The properties of the `weblogic.management.configuration.WTCPasswordMBean` entity are as follows:

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to `config.xml`

Type: boolean

Constraints: Read Only, Has Default Value: false

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

localAccessPoint

The name of the local access point to which this password applies.

Type: string

Constraints: Has Default Value: myLAP, Legal Null: true

localPassword

The local password used to authenticate connections between the local access point and the remote access point.

Note: This password is used to authenticate connections between the local Tuxedo access point identified by `LocalAccessPoint` and the remote Tuxedo access point identified by `RemoteAccessPoint`.

Type: string

Constraints: Has Default Value: myLPWD, Legal Null: true

localPasswordIV

The initialization vector used to encrypt the local password.

Type: string

Constraints: Has Default Value: myLPWDIV, Legal Null: true

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's

`javax.management.ObjectName`

`Name=user-specified-name`

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as

XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`;

Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

remoteAccessPoint

The name of the remote access point to which this password applies.

Type: string

Constraints: Has Default Value: myRAP, Legal Null: true

remotePassword

The remote password used to authenticate connections between the local access point and remote access point.

Note: This password is used to authenticate connections between the local Tuxedo access point identified by `LocalAccessPoint` and the remote Tuxedo access point identified by `RemoteAccessPoint`.

Type: string

Constraints: Has Default Value: myRPWD, Legal Null: true

remotePasswordIV

The initialization vector used to encrypt the remote password.

Type: string

Constraints: Has Default Value: myRPWDIV, Legal Null: true

tags

Return all tags on this Configuration MBean

Type: array of string

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.WTCRemoteTuxDomMBean

This interface provides access to the WTC remote Tuxedo Domain configuration attributes. The methods defined herein are applicable for WTC configuration at the WLS domain level.

The properties of the `weblogic.management.configuration.WTCRemoteTuxDomMBean` entity are as follows:

NWAddr

The network address and port number of this remote Tuxedo access point.

Specify the address in one of the following formats:

- TCP/IP address in the format `//hostname:port_number` or `//#.##.##:port_number`
- SDP address in the format `sdp://hostname:port_number` or `sdp://#.##.##:port_number`

Notes:

- If the hostname is used, the access point finds an address for hostname using the local name resolution facilities (usually DNS). If dotted decimal format is used, each # should be a number from 0 to 255. This dotted decimal number represents the IP address of the local machine. The `port_number` is the TCP/SDP port number at which the access point listens for incoming requests.
- If SDP format address is specified, the transport protocol for this access point is SDP instead of TCP. This feature is only available when WTC and Tuxedo domain gateway are both deployed on Oracle Exalogic platform. Requires Tuxedo 11gR1PS2 and higher.

Type: string

Constraints: Has Default Value: `//localhost:8902`

SSLProtocolVersion

The protocol version of the SSL connection this remote access point uses when establishing a SSL connection with specific local access point.

Value Restrictions:

- TLSv1.0
- TLSv1.1
- TLSv1.2

Type: string

Constraints: Has Default Value: `TLSv1.2`, Legal Values: `TLSv1.0`, `TLSv1.1`, `TLSv1.2`

accessPoint

The unique name used to identify this remote Tuxedo access point. This name should be unique for all local and remote Tuxedo access points defined within a WTC Service. This allows you to define unique configurations having the same Access Point ID.

Type: string

Constraints: Has Default Value: `myRAP`, Legal Null: `true`

accessPointId

The connection principal name used to identify this remote domain access point when attempting to establish a session connection to local Tuxedo access points. This value must be globally unique among all interconnected Tuxedo and WTC Domains.

Type: string

Constraints: Has Default Value: myRAPId, Legal Null: true

aclPolicy

The inbound access control list (ACL) policy toward requests from a remote Tuxedo access point.

The allowed values are:

- **LOCAL:** The local Tuxedo access point modifies the identity of service requests received from a given remote Tuxedo access point to the principal name specified in the local principal name for a given remote Tuxedo access point.
- **GLOBAL:** The local Tuxedo access point passes the service request with no change in identity.

Note: If Interoperate is set to Yes, AclPolicy is ignored.

Type: string

Constraints: Has Default Value: LOCAL, Legal Values: GLOBAL, LOCAL

allowAnonymous

Specifies whether the anonymous user is allowed to access remote Tuxedo services.

Note: If the anonymous user is allowed to access Tuxedo, the default AppKey will be used for TpUsrFile and LDAP AppKey plug-ins. Interaction with the Custom AppKey plug-in depends on the design of the Custom AppKey generator.

Type: boolean

Constraints: Has Default Value: false

appKey

Specifies the type of AppKey plug-in used.

The allowed values are:

- **TpUsrFile:** TpUsrFile is the default plug-in. It uses an imported Tuxedo TPUSR file to provide user security information. Previous releases of WebLogic Tuxedo Connector support this option.
- **LDAP:** The LDAP plug-in utilizes an embedded LDAP server to provide user security information. The user record must define the Tuxedo UID and GID information in the description field. This functionality is not supported in previous releases of WebLogic Tuxedo Connector.
- **Custom:** The Custom plug-in provides the ability to write your own AppKey generator class to provide the security information required by Tuxedo. This functionality is not supported in previous releases of WebLogic Tuxedo Connector.

Type: string

Constraints: Has Default Value: TpUsrFile, Legal Values: TpUsrFile, LDAP, Custom

cmpLimit

The compression threshold this remote Tuxedo access point uses when sending data to a local Tuxedo access point. Application buffers larger than this size are compressed.

Range of Values: Between `0` and a positive 32-bit integer.

Type: integer/int32

Constraints: Has Default Value: 2147483647, Minimum Value: 0, Maximum Value: 2147483647

connPrincipalName

The principal name used to verify the identity of this remote Tuxedo access point when it establishes a session connection with a local Tuxedo access point. If not specified, the connection principal name defaults to the AccessPointID for this access point.

Note: This parameter only applies to domains of type TDOMAIN that are running Oracle Tuxedo 7.1 or later software.

Note: ConnPrincipalName is not supported in this release.

Type: string

connectionPolicy

The conditions under which this remote Tuxedo access point establishes a session connection with a local Tuxedo access point.

The allowed values are:

- **ON_DEMAND:** A connection is attempted only when requested by either a client request to a remote service or an administrative connect command.
- **ON_STARTUP:** A domain gateway attempts to establish a connection with its remote Tuxedo access points at gateway server initialization time. Remote services (services advertised in JNDI by the domain gateway for this local Tuxedo access point) are advertised only if a connection is successfully established to that remote Tuxedo access point. If there is no active connection to a remote Tuxedo access point, then the remote services are suspended. By default, this connection policy retries failed connections every 60 seconds. Use the MaxRetry and RetryInterval attributes to specify application specific values.
- **INCOMING_ONLY:** A domain gateway does not attempt an initial connection to remote Tuxedo access points at startup and remote services are initially suspended. The domain gateway is available for incoming connections from remote Tuxedo access points and remote services are advertised when the domain gateway for this local Tuxedo access point receives an incoming connection. Connection retry processing is not allowed.
- **LOCAL:** Specifies that the remote domain connection policy is explicitly defaulted to the local domain ConnectionPolicy attribute value.

Type: string

Constraints: Has Default Value: LOCAL, Legal Values: ON_DEMAND, ON_STARTUP, INCOMING_ONLY, LOCAL

credentialPolicy

The outbound access control list (ACL) policy toward requests to a remote Tuxedo access point.

The allowed values are:

- **LOCAL:** The remote Tuxedo access point controls the identity of service requests received from the local Tuxedo access point to the principal name specified in the local principal name for this remote Tuxedo access point.

- GLOBAL: The remote Tuxedo access point passes the service request with no change.

Note: If Interoperate is set to Yes, CredentialPolicy is ignored.

Type: string

Constraints: Has Default Value: LOCAL, Legal Values: GLOBAL, LOCAL

customAppKeyClass

The full pathname to the custom AppKey generator class. (This class is only relevant if you specify Custom as the AppKey Generator.)

Note: This class is loaded at runtime if the Custom AppKey generator plug-in is selected.

Type: string

customAppKeyClassParam

The optional parameters to be used by the custom AppKey class at the class initialization time. This class is only relevant if you specify Custom as the AppKey Generator.)

Type: string

defaultAppKey

The default AppKey value to be used by the anonymous user and other users who are not defined in the user database if the plug-in allows them to access Tuxedo.

Note: The TpUsrFile and LDAP plug-ins do not allow users that are not defined in user database to access Tuxedo unless Allow Anonymous is enabled.

Type: integer/int32

Constraints: Has Default Value: -1

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

federationName

The context at which this remote Tuxedo access point federates to a foreign name service. If omitted, the default federation point is tuxedo.domains

Type: string

federationURL

The URL for a foreign name service that is federated into JNDI.

Note: The Weblogic Tuxedo Connector can federate to non-CORBA service providers.

Note: If this value is not specified, the WebLogic Tuxedo Connector:

- Assumes there is a CosNaming server in the foreign domain.
- Federates to the CosNaming server using TGIOP.

Type: string

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

keepAlive

Indicates whether this remote Tuxedo access point is configured with Application Level Keep Alive.

- Greater than 0: Application Level Keep Alive is enabled and the value indicates the amount of idle time, in milliseconds rounded to the nearest second, allowed before starting the wait timer.
- 0: Application Level Keep Alive is not enabled for the access point.
- -1: Application Level Keep Alive is enabled and indicates that the value from the local Tuxedo access point is used to indicate the amount of idle time, in milliseconds rounded to the nearest second, allowed before starting the wait timer.

Type: integer/int32

Constraints: Has Default Value: 0, Minimum Value: -1, Maximum Value: 2147483647

keepAliveWait

Indicates whether this remote Tuxedo access point requires the acknowledgement of Application Level Keep Alive. If the value is:

- Greater than 0: Application Level Keep Alive is enabled and the value indicates the amount of idle time, in milliseconds rounded to the nearest second, allowed before WebLogic Tuxedo Connector marks the connection as failed if the heartbeat is not acknowledged.
- 0: Application Level Keep Alive is not enabled for the access point but the access point acknowledges if a heartbeat is received.

Type: integer/int32

Constraints: Has Default Value: 0, Minimum Value: 0, Maximum Value: 2147483647

localAccessPoint

The local domain name from which this remote Tuxedo domain is reached.

Type: string

Constraints: Has Default Value: myLAP, Legal Null: true

maxEncryptBits

The maximum encryption key length (in bits) this remote Tuxedo access point uses when establishing a session connection. A value of indicates no encryption is used.

Value Restrictions:

- The value of the MaxEncryptBits attribute must be greater than or equal to the value of the MinEncrypBits attribute.
- A MaxEncryptBits of 40 can be used only with domains running Tuxedo 7.1 or higher.

Type: string

Constraints: Has Default Value: 128, Legal Values: 0, 40, 56, 128

maxRetries

The maximum number of times that this remote Tuxedo access point tries to establish a session connections to local Tuxedo access points. Use only when the ConnectionPolicy value is set to ON_STARTUP

Note: When the ConnectionPolicy value is LOCAL, the MaxRetries value from the local Tuxedo access point is used. When the ConnectionPolicy value is ON_STARTUP, a value of -1 indicates 9223372036854775807.

Range of Values: Between -1 and a positive 64-bit integer.

- Use to disable the retry mechanism.
- Use the maximum value to try until a connection is established.

Type: integer/int64

Constraints: Has Default Value: -1, Minimum Value: -1, Maximum Value: 9223372036854775807

minEncryptBits

The minimum encryption key length (in bits) this remote Tuxedo access point uses when establishing a session connection. A value of indicates no encryption is used.

Value Restrictions:

- The MinEncryptBits value must be less than or equal to the MaxEncryptBits value.
- A MinEncryptBits value of 40 can be used only with domains running Tuxedo 7.1 or higher.

Type: string

Constraints: Has Secure Value: 40, Has Default Value: 0, Legal Values: 0, 40, 56, 128

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

`Name=user-specified-name`

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

retryInterval

The number of seconds that this remote Tuxedo access point waits between automatic connection attempts to local Tuxedo access points. Use this only when the ConnectionPolicy value is set to ON_STARTUP

Range of Values: Between -1 and a positive 32-bit integer.

Note: When the ConnectionPolicy value is LOCAL, the RetryInterval value from the local Tuxedo access point is used. When the ConnectionPolicy value is ON_STARTUP, a value of -1 indicates 60.

Type: integer/int64

Constraints: Has Default Value: -1, Minimum Value: -1, Maximum Value: 2147483647

tags

Return all tags on this Configuration MBean

Type: array of string

tpUsrFile

The full path to the user password file containing UID/GID information. (This field is only relevant if you specify `tpUsrFile` as the AppKey Generator.)

Note: This file is generated by the Tuxedo `tpusradd` utility on the remote Tuxedo domain specified by the remote Tuxedo access point. A copy of this file must be available in your WebLogic Tuxedo Connector environment to provide correct authorization, authentication, and auditing.

Type: string

tuxedoGidKw

The keyword for Tuxedo GID (Group ID) used in the `wlsUser` when using the Tuxedo migration utility `tpmigldap`. This field is only relevant if you specify `LDAP` as the AppKey Generator.)

Note: The keyword is used to find Tuxedo GID in the user record in the embedded LDAP database.

Type: string

Constraints: Has Default Value: TUXEDO_GID

tuxedoUidKw

The keyword for Tuxedo UID (User ID) used in the `wlsUser` when using the Tuxedo migration utility `tpmigldap`. This keyword is only relevant if you specify `LDAP` as the AppKey Generator.)

Note: The keyword is used to find Tuxedo UID in the user record in the embedded LDAP database.

Type: string

Constraints: Has Default Value: TUXEDO_UID

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.WTCResourcesMBean

This interface provides access to the WTC resources configuration attributes. The methods defined herein are applicable for WTC configuration at the WLS domain level.

The properties of the `weblogic.management.configuration.WTCResourcesMBean` entity are as follows:

MBEncodingMapFile

The encoding name map file between Java and Tuxedo MBSTRING.

Type: string

appPassword

The application password as returned from the `genpasswd` utility.

Note: This Tuxedo application password is the encrypted password used to authenticate connections.

Type: string

appPasswordIV

The initialization vector used to encrypt the `AppPassword`

Note: This value is returned from the `genpasswd` utility with the `AppPassword`.

Type: string

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to `config.xml`

Type: boolean

Constraints: Read Only, Has Default Value: false

fldTbl16Classes

The names of `FldTbl16Classes` that are loaded via a class loader and added to a `FldTbl` array.

Value Requirements:

- Used fully qualified names of the desired classes.
- Use a comma-separated list to enter multiple classes.

Type: array of string

fldTbl32Classes

The names of `FldTbl32Classes` that are loaded via a class loader and added to a `FldTbl` array.

Value Requirements:

- Used fully qualified names of the desired classes.
- Use a comma-separated list to enter multiple classes

Type: array of string

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

Name=user-specified-name

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

remoteMBEncoding

The default encoding name of sending MBSTRING data.

Type: string

tags

Return all tags on this Configuration MBean

Type: array of string

tpUsrFile

The full path to the `TPUSR` file, which contains Tuxedo UID/GID information.

Note: This file is generated by the Tuxedo `tpusradd` utility on the remote Tuxedo domain.

Type: string

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

viewTbl16Classes

The names of `ViewTbl16Classes` that are loaded via a class loader and added to a `ViewTbl` array.

Value Requirements:

- Used fully qualified names of the desired classes.
- Use a comma-separated list to enter multiple classes.

Type: array of string

viewTbl32Classes

The names of `ViewTbl32Classes` that are loaded via a class loader and added to a `ViewTbl` array.

Value Requirements:

- Used fully qualified names of the desired classes.
- Use a comma-separated list to enter multiple classes.

Type: array of string

weblogic.management.configuration.WTCServerMBean

This MBean defines a WTC Server.

The properties of the weblogic.management.configuration.WTCTServerMBean entity are as follows:

deploymentOrder

A priority that the server uses to determine when it deploys an item. The priority is relative to other deployable items of the same type.

For example, the server prioritizes and deploys all EJBs before it prioritizes and deploys startup classes.

Items with the lowest Deployment Order value are deployed first. There is no guarantee on the order of deployments with equal Deployment Order values. There is no guarantee of ordering across clusters.

Type: integer/int32

Constraints: Has Default Value: 1000, Minimum Value: 0, Maximum Value: 2147483647

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

`Name=user-specified-name`

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

tags

Return all tags on this Configuration MBean

Type: array of string

targets

You must select a target on which an MBean will be deployed from this list of the targets in the current domain on which this item can be deployed. Targets must be either servers or clusters. The deployment will only occur once if deployments overlap.

Type: array of weblogic.management.configuration.TargetMBean references

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.WTCTBridgeGlobalMBean

This interface provides access to the WTC tBridge Global configuration attributes. The methods defined herein are applicable for tBridge configuration at the WLS domain level.

The properties of the weblogic.management.configuration.WTCTBridgeGlobalMBean entity are as follows:

allowNonStandardTypes

Specifies whether non-standard data types are allowed to pass through this Tuxedo queuing bridge.

A value of NO means that non standard types are rejected and placed onto a specified error location; a value of YES means that non-standard types are placed on the target location as BLOBs with a tag indicating the original type.

Note: Standard types are: ASCII text (TextMessage, STRING), or BLOB (BytesMessage, CARRAY).

Type: string

Constraints: Has Default Value: NO, Legal Values: Yes, No

defaultReplyDeliveryMode

The reply delivery mode to associate with a message when placing messages onto the target location.

Usage Notes:

- Use when messages are being redirected to Tuxedo/Q from JMS and the JMS_BEA_TuxGateway_Tuxedo_ReplyDeliveryMode property is not set for a message.
- If the defaultReplyDeliveryMode and JMS_BEA_TuxGateway_Tuxedo_ReplyDeliveryMode are not set, the default semantics defined for Tuxedo are enforced by the Tuxedo/Q subsystem.

Type: string

Constraints: Has Default Value: DEFAULT, Legal Values: PERSIST, NONPERSIST, DEFAULT

deliveryModeOverride

The delivery mode to use when placing messages onto the target location.

If this value is not specified, the message is placed on the target location with the same delivery mode specified from the source location.

Note: This value overrides any delivery mode associated with a message.

Type: string

Constraints: Has Default Value: NONPERSIST, Legal Values: PERSIST, NONPERSIST

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

jmsFactory

The name of the JMS connection factory.

Example:weblogic.jms.ConnectionFactory

Type: string

Constraints: Has Default Value: weblogic.jms.XAConnectionFactory, Legal Null: true

jmsToTuxPriorityMap

The mapping of priorities from JMS to Tuxedo. The default JMS To Tux Priority Map is: 0:1 | 1:12 | 2:23 | 3:34 | 4:45 | 5:56 | 6:67 | 7:78 | 8:89 | 9:100

Examples:0:1 | 1:12 | 2:23 | 3:34 | 4:45 | 5:56 | 6:67 | 7:78 | 8:89 | 9:100 or
0:1-10|1:11-20|2:21-30|3:31-40|4:41-50|5:51-60|6:61-70|7:71-80|8:81-90|9:91-100

Note: There are 10 possible JMS priorities(0=>9) which can be paired to 100 possible Tuxedo priorities(1=>100). A mapping consists of a "|" separated list of value-to-range pairs (jmsvalue:tuxrange) where pairs are separated by ":" and ranges are separated by "-".

Type: string

jndiFactory

The name of the JNDI lookup factory.

Example:weblogic.jndi.WLInitialContextFactory

Type: string

Constraints: Has Default Value: weblogic.jndi.WLInitialContextFactory, Legal Null: true

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

`Name=user-specified-name`

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

retries

The number of attempts to redirect a message before this Tuxedo queuing bridge places the message in the specified error location and logs an error.

Range of Values: Between 0 and a positive 32-bit integer.

Type: integer/int32

Constraints: Has Default Value: 0, Minimum Value: 0, Maximum Value: 2147483647

retryDelay

The minimum number of milliseconds this Tuxedo queuing bridge waits before redirecting a message after a failure.

Note: During this waiting period, no other messages are redirected from the thread. Other threads may continue to redirect messages.

Range of Values: Between and a positive 32-bit integer.

Type: integer/int32

Constraints: Has Default Value: 10, Minimum Value: 0, Maximum Value: 2147483647

tags

Return all tags on this Configuration MBean

Type: array of string

timeout

The number of timeout seconds for an entire redirection when this Tuxedo queuing bridge places a message on the target location. A value of specifies an infinite wait.

Range of Values: Between and a positive 32-bit integer.

Type: integer/int32

Constraints: Has Secure Value: 60, Has Default Value: 60, Minimum Value: 0, Maximum Value: 2147483647

transactional

Specifies whether this Tuxedo queuing bridge should use transactions when retrieving messages from a source location and when placing messages on a target location.

A value of YES means that transactions are used for both operations; a value of NO means that transactions are not used for either operation.

Note: Transactional is not supported in this release.

Type: string

Constraints: Has Default Value: NO, Legal Values: Yes, No

tuxErrorQueue

The name of the Tuxedo queue used to store a message that cannot be redirected to a Tuxedo/Q source queue.

If not specified, all messages not redirected are lost. If the message cannot be placed into the `TuxErrorQueue`, an error is logged and the message is lost.

Note: This queue is in the same queue space as the source queue.

Type: string

tuxFactory

The name of the Tuxedo connection factory.

Example: `tuxedo.services.TuxedoConnection`

Type: string

Constraints: Has Default Value: `tuxedo.services.TuxedoConnection`, Legal Null: true

tuxToJmsPriorityMap

The mapping of priorities to map from Tuxedo to JMS. The default JMS To Tux Priority Map is: 1-10:0 | 11-20:1 | 21-30:2 | 31-40:3 | 41-50:4 | 51-60:5 | 61-70:6 | 71-80:7 | 81-90:8 | 91-100:9

Examples: 1:0 | 12:1 | 23:2 | 34:3 | 45:4 | 56:5 | 67:6 | 78:7 | 89:8 | 100:9 or 20:0-1 | 40:2-3 | 60:4-5 | 80:6-7 | 100:8-9

Note: There are 100 possible Tuxedo priorities (1=>100) which can be paired to 10 possible JMS priorities (0=>9). A mapping consists of a "|" separated list of value-to-range pairs (tuxvalue:jmsrange) where pairs are separated by ":" and ranges are separated by "-".

Type: string

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

userId

The user identity for all messages handled by this Tuxedo queuing bridge for ACL checks when security is configured.

All messages assume this identity until the security/authentication contexts are passed between the subsystems. Until the security contexts are passed, there is no secure method to identify who generated a message received from the source location.

Note: The user argument may be specified as either a user name or a user identification number (uid).

Type: string

wlsErrorDestination

The name of the location used to store WebLogic Server JMS messages when a message cannot be redirected.

If not specified, all messages not redirected are lost. If the message cannot be placed into `WlsErrorDestination` for any reason, an error is logged and the message is lost.

Type: string

weblogic.management.configuration.WTCTBridgeRedirectMBean

This interface provides access to the WTC tBridge Redirect configuration attributes. The methods defined herein are applicable for tBridge configuration at the WLS domain level.

The properties of the weblogic.management.configuration.WTCTBridgeRedirectMBean entity are as follows:

direction

The direction of data flow. At least one redirection must be specified or the Tuxedo queuing bridge will fail to start and an error will be logged.

Each defined direction is handled by starting a new thread.

Redirection keywords:

- JmsQ2TuxQ
- From JMS to TUXEDO /Q
- TuxQ2JmsQ
- From TUXEDO /Q to JMS
- JmsQ2TuxS
- From JMS to TUXEDO Service reply to JMS
- JmsQ2JmsQ
- From JMS to JMS

Type: string

Constraints: Has Default Value: JmsQ2TuxQ, Legal Values: JmsQ2TuxQ, TuxQ2JmsQ, JmsQ2TuxS, JmsQ2JmsQ, Legal Null: true

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

metaDataFile

The name of the metadata file URL used to pass the call to the XML-to-non-XML WebLogic XML Translator (WLXT).

Note: Not supported for this release.

Type: string

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

Name=user-specified-name

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

replyQ

The name of the JMS queue used specifically for synchronous calls to a Tuxedo service. The response is returned to the JMS ReplyQ.

Type: string

sourceAccessPoint

The name of the local or remote access point where the source is located.

Type: string

sourceName

The name of a source queue or service. Specifies a JMS queue name, a Tuxedo queue name, or the name of a Tuxedo service.

Type: string

Constraints: Has Default Value: mySource, Legal Null: true

sourceQspace

The name of the Qspace for a source location.

Type: string

tags

Return all tags on this Configuration MBean

Type: array of string

targetAccessPoint

The name of the local or remote access point where the target is located.

Type: string

targetName

The name of the target queue or service. Specifies a JMS queue name, a Tuxedo queue name, or the name of a Tuxedo service.

Type: string

Constraints: Has Default Value: myTarget, Legal Null: true

targetQspace

The name of the Qspace for a target location.

Type: string

translateFML

The type of XML/FML translation.

NO indicates that no data translation is performed. FLAT indicates that the message payload is transformed using the WebLogic Tuxedo Connector translator. WLXT indicates that translation is performed by the XML-to-non-XML WebLogic XML Translator (WLXT).

Note: WLXT is not supported for this release.

Type: string

Constraints: Has Default Value: NO, Legal Values: NO, FLAT, WLXT

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.WebAppContainerMBean

This MBean is used to specify domain-wide defaults for the WebApp container. In general, these properties can be overridden at the cluster level (in ClusterMBean, if the same property is present there), the server level (in ServerMBean, if the same property is present there) or for a specific Web application (in weblogic.xml).

The properties of the weblogic.management.configuration.WebAppContainerMBean entity are as follows:

JSPCompilerBackwardsCompatible

Global property to determine the behavior of the JSP compiler. When this property set to "true", the JSP compiler throws a translation error for JSPs that do not conform to the JSP2.0 specification. This property exists for backward compatibility.

Type: boolean

Constraints: Has Default Value: false

WAPEnabled

Indicates whether the session ID should include JVM information. (Checking this box may be necessary when using URL rewriting with WAP devices that limit the size of the URL to 128 characters, and may also affect the use of replicated sessions in a cluster.) When this box is selected, the default size of the URL will be set at 52 characters, and it will not contain any special characters.

Type: boolean

Constraints: Has Default Value: false

XPoweredByHeaderLevel

WebLogic Server uses the X-Powered-By HTTP header, as recommended by the Servlet 3.1 specification, to publish its implementation information.

Following are the options:

- "NONE" (default): X-Powered-By header will not be sent
- "SHORT": "Servlet/3.1 JSP/2.3"
- "MEDIUM": "Servlet/3.1 JSP/2.3 (WebLogic/12.2)"

- "FULL": "Servlet/3.1 JSP/2.3 (WebLogic/12.2 JDK/1.8)"

Type: string

Constraints: Has Default Value: NONE, Legal Values: NONE, SHORT, MEDIUM, FULL

allowAllRoles

In the security-constraints elements defined in a web application's web.xml deployment descriptor, the auth-constraint element indicates the user roles that should be permitted access to this resource collection. Here role-name = "*" is a compact syntax for indicating all roles in the Web application. In previous releases, role-name = "*" was treated as all users/roles defined in the realm.

This parameter is a backward-compatibility switch to restore old behavior. Default behavior is one required by the specification, meaning all roles defined in the web application.

If set, the value defined in weblogic.xml (container-descriptor -> allow-all-roles) takes precedence (if set) over this value.

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

authCookieEnabled

Specifies whether the AuthCookie feature is enabled or not.

Type: boolean

Constraints: Has Secure Value: true, Has Default Value: true

changeSessionIDOnAuthentication

Global property to determine if we need to generate a new SessionID after authentication. When this property is set to "false", the previous sessionID will be retained even after authorization.

Type: boolean

Constraints: Has Default Value: true

clientCertProxyEnabled

Specifies whether or not to honor the WL-Proxy-Client-Cert header coming with the request.

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

filterDispatchedRequestsEnabled

Indicates whether or not to apply filters to dispatched requests. This is a backward compatibility flag. Until version 8.1, WebLogic Server applied ServletFilters (if configured for the web application) on request dispatches (and includes/forwards). Servlet 2.4 has introduced the "Dispatcher" element to make this behavior explicit. The default value is Dispatcher=REQUEST. In order to be compliant with the Java EE specification, the default value for FilterDispatchedRequestsEnabled is false beginning

with WebLogic Server 9.0. Note that if you are using old descriptors (meaning web.xml does not have version=2.4), then WebLogic Server automatically uses `FilterDispatchedRequestsEnabled = true` for the web applications, unless `filter-dispatched-requests-enabled` is explicitly set to `false` in weblogic.xml. This means that old applications will work fine without any modification. Additionally, during migration of old domains to the 9.0 domain, the migration plug-in automatically sets this flag to true.

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

httpTraceSupportEnabled

Returns the value of `HttpTraceSupportEnabled`.

Type: boolean

Constraints: Has Default Value: false

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

jaxRsMonitoringDefaultBehavior

Global property to determine the behavior of monitoring in JAX-RS applications. When the property is set to `{@code true}` (or not set) the monitoring is turned on (if not overridden by properties set directly in application). If the property is set to `{@code false}` the monitoring for all JAX-RS applications is disabled.

Type: boolean

Constraints: Has Default Value: true

maxPostSize

The maximum post size this server allows for reading HTTP POST data in a servlet request. A value less than 0 indicates an unlimited size.

Type: integer/int32

Constraints: Has Default Value: -1

maxPostTimeSecs

Maximum post time (in seconds) for reading HTTP POST data in a servlet request. `MaxPostTime < 0` means unlimited

Type: integer/int32

Constraints: Has Default Value: -1

maxRequestParameterCount

The maximum request parameter count this server allows for reading maximum HTTP POST parameters count in a servlet request.

Gets the `maxRequestParameterCount` attribute of the `WebServerMBean` object.

Type: integer/int32

Constraints: Has Default Value: 10000

mimeMappingFile

Returns the name of the file containing mime-mappings for the domain.

The Format of the file should be: extension=mime-type

For Example:

htm=text/html

gif=image/gif

jpg=image/jpeg

If this file does not exist, WebLogic Server uses an implicit mime-mapping set of mappings defined in `weblogic.utils.http.HttpConstants` (`DEFAULT_MIME_MAPPINGS`). To remove a mapping defined in implicit map, set it to blank.

Type: string

Constraints: Has Default Value: `./config/mimemappings.properties`

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's

`javax.management.ObjectName`

`Name=user-specified-name`

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`;

Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

optimisticSerialization

When `OptimisticSerialization` is turned on, WebLogic Server does not serialize-deserialize context and request attributes upon `getAttribute(name)` when a request gets dispatched across servlet contexts. This means you will need to make sure that the attributes common to web applications are scoped to a common parent classloader (they are application-scoped) or placed in the system classpath if the two web applications do not belong to the same application. When `OptimisticSerialization` is turned off (which is the default), WebLogic Server does serialize-deserialize context and request attributes upon `getAttribute(name)` to avoid the possibility of `ClassCastExceptions`. The value of `OptimisticSerialization` can also be overridden for specific web applications by setting the `optimistic-serialization` value in `weblogic.xml`.

Type: boolean

Constraints: Has Default Value: false

overloadProtectionEnabled

This parameter is used to enable overload protection in the web application container against low memory conditions. When a low memory situation occurs, new session creation attempts will result in `weblogic.servlet.SessionCreationException`. The application code needs to catch this exception and take proper action. Alternatively appropriate error-pages can be configured in `web.xml` against `weblogic.servlet.SessionCreationException`. This check is performed only on memory and replicated sessions.

Type: boolean

Constraints: Has Default Value: false

p3PHeaderValue

Returns the P3P header value that will be sent with all responses for HTTP requests (if non-null). The value of this header points to the location of the policy reference file for the website.

Alternatively, a servlet filter can be used to set the P3P header.

Type: string

postTimeoutSecs

The amount of time this server waits between receiving chunks of data in an HTTP POST data before it times out. (This is used to prevent denial-of-service attacks that attempt to overload the server with POST data.)

Type: integer/int32

Constraints: Has Secure Value: 30, Has Default Value: 30, Minimum Value: 0, Maximum Value: 120

reloginEnabled

Beginning with the 9.0 release, the FORM/BASIC authentication behavior has been modified to conform strictly to the Java EE Specification. If a user has logged-in but does not have privileges to access a resource, the 403 (FORBIDDEN) page will be returned. Turn this flag on to enable the old behavior, which was to return the user to the login form.

Type: boolean

Constraints: Has Default Value: false

retainOriginalURL

The `retain-original-url` property is used in FORM based authentication scenarios. When this property is set to true, after a successful authentication, WebLogic Server will redirect back to the web resource (page/servlet) retaining the protocol (http/https) used to access the protected resource in the original request. If set to false (which is the default value), WebLogic Server will redirect back to the protected resource using the current protocol. The `retain-original-url` value can also be specified at per web application level in `weblogic.xml`. The value in `weblogic.xml`, if specified, overrides the domain level value.

Type: boolean

Constraints: Has Default Value: false

rtexprvalueJspParamName

Global property which determines the behavior of the JSP compiler when a `jsp:param` attribute "name" has a request time value. Without this property set to "true", the JSP

compiler throws an error for a JSP using a request time value for the "name" attribute as mandated by the JSP 2.0 specification. This property exists for backward compatibility.

Type: boolean

Constraints: Has Default Value: false

servletAuthenticationFormURL

ServletAuthenticationFormURL is used for backward compatibility with previous releases of Weblogic Server. If ServletAuthenticationFormURL is set to true (default), then ServletAuthentication.getTargetURLForFormAuthentication() and HttpSession.getAttribute(AuthFilter.TARGET_URL) will return the URL of the protected target resource. If set to false, the above APIs will return the URI of the protected target resource. By default, the value is set to true.(new method added in 9.0.0.1)

Type: boolean

Constraints: Has Default Value: true

servletReloadCheckSecs

Type: integer/int32

Constraints: Has Default Value: 1, Has Production Mode Default Value: -1

showArchivedRealPathEnabled

Global property to determine the behavior of getRealPath() for archived web applications. When this property is set to "true", getRealPath() will return the canonical path of the resource files.

Type: boolean

Constraints: Has Default Value: false

tags

Return all tags on this Configuration MBean

Type: array of string

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogicPluginEnabled

Specifies whether or not the proprietary WL-Proxy-Client-IP header should be honored. (This is needed only when WebLogic Server plug-ins are configured.)

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

workContextPropagationEnabled

Indicates whether or not WorkContextPropagation is enabled. By default, it is turned on. There is a little overhead involved in propagating WorkContexts. Therefore, if you don't want WorkContext propagation, turn this value off in production environments.

Type: boolean

Constraints: Has Default Value: true

weblogic.management.configuration.WebServerLogMBean

Aggregates the logging attributes for the WebServerMBean.

The properties of the weblogic.management.configuration.WebServerLogMBean entity are as follows:

ELFFields

Returns the list of fields specified for the extended logging format for access.log.

Type: string

Constraints: Has Default Value: date time cs-method cs-uri sc-status

bufferSizeKB

Gets the underlying log buffer size in kilobytes

Type: integer/int32

Constraints: Has Default Value: 8

dateFormatPattern

The date format pattern used for rendering dates in the log. The DateFormatPattern string conforms to the specification of the `java.text.SimpleDateFormat` class.

Type: string

Constraints: Legal Null: true

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

fileCount

The maximum number of log files that the server creates when it rotates the log. This number does not include the file that the server uses to store current messages. (Requires that you enable Number of Files Limited.)

Type: integer/int32

Constraints: Has Default Value: 7, Has Production Mode Default Value: 100, Minimum Value: 1, Maximum Value: 99999

fileMinSize

The size (1 - 2097150 kilobytes) that triggers the server to move log messages to a separate file. The default is 500 kilobytes. After the log file reaches the specified minimum size, the next time the server checks the file size, it will rename the current log file as `SERVER_NAME.lognnnnn` and create a new one to store subsequent messages. (Requires that you specify a file rotation type of Size.)

Type: integer/int32

Constraints: Has Default Value: 500, Has Production Mode Default Value: 5000, Minimum Value: 1, Maximum Value: 2097150

fileName

The name of the log file.

Type: string

fileTimeSpan

The interval (in hours) at which the server saves old log messages to another file. (Requires that you specify a file rotation type of `TIME`.)

Type: integer/int32

Constraints: Has Default Value: 24, Minimum Value: 1

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

logFileFormat

The format of the HTTP log file. Both formats are defined by the W3C. With the extended log format, you use server directives in the log file to customize the information that the server records.

Type: string

Constraints: Has Default Value: common, Legal Values: common, extended

logFileRotationDir

The directory where the rotated log files will be stored. By default the rotated files are stored in the same directory where the log file is stored.

Type: string

logTimeInGMT

Specifies whether the time stamps for HTTP log messages are in Greenwich Mean Time (GMT) regardless of the local time zone that the host computer specifies.

Use this method to comply with the W3C specification for Extended Format log files. The specification states that all time stamps for Extended Format log entries be in GMT.

This method applies only if you have specified the `extended` message format.

Type: boolean

Constraints: Has Default Value: false

loggingEnabled

Indicates whether this server logs HTTP requests. (The remaining fields on this page are relevant only if you select this check box.)

Gets the `loggingEnabled` attribute of the `WebServerMBean` object.

Type: boolean

Constraints: Has Secure Value: true, Has Default Value: true

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

Name=user-specified-name

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

numberOfFilesLimited

Indicates whether to limit the number of log files that this server instance creates to store old messages. (Requires that you specify a file rotation type of `SIZE` or `TIME`.)

After the server reaches this limit, it deletes the oldest log file and creates a new log file with the latest suffix.

If you do not enable this option, the server creates new files indefinitely and you must clean up these files as you require.

Type: boolean

Constraints: Has Default Value: true, Has Production Mode Default Value: true

rotateLogOnStartup

Specifies whether a server rotates its log file during its startup cycle. The default value in production mode is false.

Type: boolean

Constraints: Has Default Value: true, Has Production Mode Default Value: false

rotationTime

Determines the start time (hour and minute) for a time-based rotation sequence.

At the time that this value specifies, the server renames the current log file. Thereafter, the server renames the log file at an interval that you specify in File Time Span.

Note that WebLogic Server sets a threshold size limit of 500 MB before it forces a hard rotation to prevent excessive log file growth.

Use the following format: `H:mm`, where

- `H` is Hour in day (0-23)
- `mm` is the minute in hour

Type: string

Constraints: Has Default Value: 00:00

rotationType

Criteria for moving old log messages to a separate file.

- `NONE` Messages accumulate in a single file. You must erase the contents of the file when the size is too large. Note that WebLogic Server sets a threshold size limit of 500 MB before it forces a hard rotation to prevent excessive log file growth.
- `SIZE` When the log file reaches the size that you specify in `FileMinSize`, the server renames the file as `SERVER_NAME.lognnnnn`
- `TIME` At each time interval that you specify in `TimeSpan`, the server renames the file as `SERVER_NAME.lognnnnn`

After the server renames a file, subsequent messages accumulate in a new file with the name that you specified as the log file name.

Type: string

Constraints: Has Default Value: bySize, Legal Values: bySize, byTime, none

tags

Return all tags on this Configuration MBean

Type: array of string

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.WebServerMBean

This bean represents the configuration of virtual web server within a weblogic server. Note that a server may define multiple web servers to support virtual hosts.

This MBean represents a virtual host.

The properties of the weblogic.management.configuration.WebServerMBean entity are as follows:

WAPEnabled

Indicates whether the session ID should include JVM information. (Checking this box may be necessary when using URL rewriting with WAP devices that limit the size of the URL to 128 characters, and may also affect the use of replicated sessions in a cluster.) When this box is selected, the default size of the URL will be set at 52 characters, and it will not contain any special characters.

Gets the WAPEnabled attribute of the WebServerMBean object

Type: boolean

Constraints: Has Default Value: false

acceptContextPathInGetRealPath

Indicates whether this server allows the inclusion of the context path in the virtual path to `context.getRealPath()`. (If checked, you cannot use sub directories with the same name as `contextPath`). This is a compatibility switch that will be deprecated 9.0.0.0 in future releases.

Gets the acceptContextPathInGetRealPath attribute of the WebServerMBean object

Type: boolean

Constraints: Has Default Value: false

authCookieEnabled

Whether authcookie feature is enabled or not.

Type: boolean

Constraints: Has Secure Value: true, Has Default Value: true

chunkedTransferDisabled

Indicates whether the use of Chunk Transfer-Encoding in HTTP/1.1 is enabled.

Type: boolean

Constraints: Has Default Value: false

clientIpHeader

Get the Client IP Header from WebServerMBean.

Type: string

defaultWebAppContextRoot

Returns the original context-root for the default Web application for this Web server. Alternatively, you can use the context-root attributes in application.xml or weblogic.xml to set a default Web application. The context-root for a default Web application is /. If "" (empty string) is specified, the Web server defaults to /.

Type: string

deploymentOrder

A priority that the server uses to determine when it deploys an item. The priority is relative to other deployable items of the same type.

For example, the server prioritizes and deploys all EJBs before it prioritizes and deploys startup classes.

Items with the lowest Deployment Order value are deployed first. There is no guarantee on the order of deployments with equal Deployment Order values. There is no guarantee of ordering across clusters.

Type: integer/int32

Constraints: Has Default Value: 1000, Minimum Value: 0, Maximum Value: 2147483647

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

frontendHTTPPort

The name of the HTTP port to which all redirected URLs will be sent. If specified, WebLogic Server will use this value rather than the one in the HOST header.

Sets the frontendHTTPPort Provides a method to ensure that the webapp will always have the correct PORT information, even when the request is coming through a firewall or a proxy. If this parameter is configured, the HOST header will be ignored and the information in this parameter will be used in its place.

Type: integer/int32

Constraints: Has Default Value: 0

frontendHTTPSPort

The name of the secure HTTP port to which all redirected URLs will be sent. If specified, WebLogic Server will use this value rather than the one in the HOST header.

Sets the frontendHTTPSPort Provides a method to ensure that the webapp will always have the correct PORT information, even when the request is coming through a firewall or a proxy. If this parameter is configured, the HOST header will be ignored and the information in this parameter will be used in its place.

Type: integer/int32

Constraints: Has Default Value: 0

frontendHost

The name of the host to which all redirected URLs will be sent. If specified, WebLogic Server will use this value rather than the one in the HOST header.

Sets the HTTP frontendHost Provides a method to ensure that the webapp will always have the correct HOST information, even when the request is coming through a firewall or a proxy. If this parameter is configured, the HOST header will be ignored and the information in this parameter will be used in its place.

Type: string

Constraints: Has Default Value: null

httpsKeepAliveSecs

The amount of time this server waits before closing an inactive HTTPS connection.

Number of seconds to maintain HTTPS keep-alive before timing out the request.

Type: integer/int32

Constraints: Has Secure Value: 60, Has Default Value: 60, Minimum Value: 30, Maximum Value: 360

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

keepAliveEnabled

Indicates whether there should be a persistent connection to this server. (This may improve the performance of your Web applications.)

Gets the keepAliveEnabled attribute of the WebServerMBean object

Type: boolean

Constraints: Has Secure Value: true, Has Default Value: true

keepAliveSecs

The amount of time this server waits before closing an inactive HTTP connection.

Number of seconds to maintain HTTP keep-alive before timing out the request.

Type: integer/int32

Constraints: Has Secure Value: 30, Has Default Value: 30, Minimum Value: 5, Maximum Value: 3600

maxPostSize

The maximum post size this server allows for reading HTTP POST and PUT data in a servlet request.

A value less than 0 indicates an unlimited size.

Gets the maxPostSize attribute of the WebServerMBean object

Type: integer/int32

Constraints: Has Default Value: -1

maxPostTimeSecs

Max Post Time (in seconds) for reading HTTP POST data in a servlet request.
MaxPostTime < 0 means unlimited

Gets the maxPostTimeSecs attribute of the WebServerMBean object

Type: integer/int32

Constraints: Has Default Value: -1

maxRequestParameterCount

Max Request Parameter Count this server allows for reading maximum HTTP POST Parameters count in a servlet request.

Gets the maxRequestParameterCount attribute of the WebServerMBean object

Type: integer/int32

Constraints: Has Default Value: 10000

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's

`javax.management.ObjectName`

`Name=user-specified-name`

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as

XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`;

Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

overloadResponseCode

Get the response code to be used when an application is overloaded. An application can get overloaded when the number of pending requests has reached the max capacity specified in the WorkManager or when the server is low on memory. The low memory condition is determined using

`OverloadProtectionMBean#getFreeMemoryPercentLowThreshold()`.

Type: integer/int32

Constraints: Has Default Value: 503, Minimum Value: 100, Maximum Value: 599

postTimeoutSecs

Timeout (in seconds) for reading HTTP POST data in a servlet request. If the POST data is chunked, the amount of time the server waits between the end of receiving the last chunk of data and the end of receiving the next chunk of data in an HTTP POST before it times out. (This is used to prevent denial-of-service attacks that attempt to overload the server with POST data.)

Gets the postTimeoutSecs attribute of the WebServerMBean object

Type: integer/int32

Constraints: Has Secure Value: 30, Has Default Value: 30, Minimum Value: 0, Maximum Value: 120

sendServerHeaderEnabled

Indicates whether this server name is sent with the HTTP response. (This is useful for wireless applications where there is limited space for headers.)

Indicates whether this server instance includes its name and WebLogic Server version number in HTTP response headers.

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

singleSignonDisabled

Indicates whether the singleSignonDisabled attribute is enabled

Type: boolean

Constraints: Has Default Value: false

tags

Return all tags on this Configuration MBean

Type: array of string

targets

You must select a target on which an MBean will be deployed from this list of the targets in the current domain on which this item can be deployed. Targets must be either servers or clusters. The deployment will only occur once if deployments overlap.

Type: array of weblogic.management.configuration.TargetMBean references

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

useHeaderEncoding

Type: boolean

Constraints: Has Secure Value: false, Has Default Value: false

useHighestCompatibleHTTPVersion

Enables use of the highest compatible HTTP protocol version-string in the response. E.g. HTTP spec suggests that HTTP/1.1 version-string should be used in response to a request using HTTP/1.0. This does not necessarily affect the response format.

Type: boolean

Constraints: Has Default Value: true

writeChunkBytes

The default size of the blocks to be written to the network layer.

Gets the writeChunkBytes attribute of the WebServerMBean object

Type: integer/int32

Constraints: Read Only, Has Default Value: 512

weblogic.management.configuration.WebServiceBufferingMBean

Represents buffering configuration for web services.

The properties of the weblogic.management.configuration.WebServiceBufferingMBean entity are as follows:

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

Name=user-specified-name

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

retryCount

The number of times a buffered request or response can be retried before it is abandoned (and moved to any error queue defined for the buffer queue)

Type: integer/int32

Constraints: Has Default Value: 3, Minimum Value: 0

retryDelay

The amount time between retries of a buffered request and response. Note, this value is only applicable when `RetryCount > 0`. String value in "Duration" format. Defaults to "P0DT30S" (30 seconds).

Type: string

Constraints: Has Default Value: P0DT30S

tags

Return all tags on this Configuration MBean

Type: array of string

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.WebServiceLogicalStoreMBean

Represents a logical store for web services.

The properties of the `weblogic.management.configuration.WebServiceLogicalStoreMBean` entity are as follows:

cleanerInterval

Get the interval at which the persistent store will be cleaned

Type: string

Constraints: Has Default Value: PT10M

defaultMaximumObjectLifetime

Get the default max time an object can remain in the store. This can be overridden on individual objects placed in the store (internally, but not via this API).

Type: string

Constraints: Has Default Value: P1D

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

name

Get the name of this logical store.

Type: string

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

persistenceStrategy

Get the persistence strategy in use by this logical store. Any physical store configured for use with this logical store should support this strategy.

Type: string

Constraints: Has Default Value: LOCAL_ACCESS_ONLY, Legal Values: LOCAL_ACCESS_ONLY, IN_MEMORY

physicalStoreName

Get the name of the physical store to be used by this logical store. This property is recommended for use only when running off server or in other cases where a buffering queue JNDI name cannot be set via setBufferingQueueJndiName. If a buffering queue JNDI name is set to a non-null/non-empty value, this property is ignored. Defaults to "" to indicate the default WLS file store should be used.

This property is ignored if persistence strategy is IN_MEMORY.

Type: string

Constraints: Has Default Value:

requestBufferingQueueJndiName

Get the JNDI name of the buffering queue that web services should use. (Both for buffering and to find the physical store for this logical store). Defaults to "" to indicate the PhysicalStoreName property should be used.

This property is ignored if persistence strategy is IN_MEMORY.

Type: string

Constraints: Has Default Value:

responseBufferingQueueJndiName

Get the JNDI name of the response buffering queue that web services should use. If this is null, the request buffering queue is used.

Type: string

tags

Return all tags on this Configuration MBean

Type: array of string

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.WebServiceMBean

Encapsulates information about a Web Service configuration.

The properties of the weblogic.management.configuration.WebServiceMBean entity are as follows:

callbackQueue

For use only with the JAX-RPC stack. For JAX-WS, use WebServiceBufferingMBean instead.

Type: string

Constraints: Has Default Value: weblogic.wsee.DefaultCallbackQueue

callbackQueueMDBRunAsPrincipalName

For use only with the JAX-RPC stack. For JAX-WS, use WebServiceBufferingMBean instead.

Type: string

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

jmsConnectionFactory

For use only with the JAX-RPC stack. For JAX-WS, use WebServiceBufferingMBean instead.

Type: string

Constraints: Has Default Value: weblogic.jms.XAConnectionFactory

messagingQueue

For use only with the JAX-RPC stack. For JAX-WS, use WebServiceBufferingMBean instead.

Type: string

Constraints: Has Default Value: weblogic.wsee.DefaultQueue

messagingQueueMDBRunAsPrincipalName

For use only with the JAX-RPC stack. For JAX-WS, use WebServiceBufferingMBean instead.

Type: string

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's

`javax.management.ObjectName`

`Name=user-specified-name`

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as

XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`;

Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

tags

Return all tags on this Configuration MBean

Type: array of string

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.WebServicePersistenceMBean

Represents persistence configuration for web services.

The properties of the weblogic.management.configuration.WebServicePersistenceMBean entity are as follows:

defaultLogicalStoreName

Get the name of the logical store to use, by default, for all web services persistent state in this server.

Type: string

Constraints: Has Default Value: WseeStore

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

Name=user-specified-name

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

tags

Return all tags on this Configuration MBean

Type: array of string

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.WebServicePhysicalStoreMBean

Represents a physical store for web services. Used only for non-WLS containers (e.g. other app-server or standalone client).

The properties of the `weblogic.management.configuration.WebServicePhysicalStoreMBean` entity are as follows:

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to `config.xml`

Type: boolean

Constraints: Read Only, Has Default Value: false

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

location

For file stores, specifies the directory that will hold all files related to the store. The actual file names are controlled internally by the file store implementation. For other types of stores, this location may be a URL or URI, or other description string.

Type: string

name

Get the name of this physical store.

Type: string

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

storeType

Get the type of this physical store.

Type: string

Constraints: Has Default Value: FILE, Legal Values: FILE, JDBC

synchronousWritePolicy

Specifies the algorithm used when performing synchronous writes to the physical store.

Type: string

Constraints: Has Default Value: CACHE_FLUSH, Legal Values: DISABLED, CACHE_FLUSH, DIRECT_WRITE

tags

Return all tags on this Configuration MBean

Type: array of string

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.WebServiceReliabilityMBean

Represents reliability configuration for web services.

The properties of the weblogic.management.configuration.WebServiceReliabilityMBean entity are as follows:

acknowledgementInterval

The maximum time a pending acknowledgement (set after the destination accepts a message) can wait before being delivered back to the RM source. String value in "Duration" format. Defaults to "P0DT0.2S" (200 milliseconds). Set at sequence creation time, and cannot be reset.

Type: string

Constraints: Has Default Value: P0DT0.2S

baseRetransmissionInterval

The interval of time that must pass before a message will be retransmitted to the RM destination (in the event a prior transmission failed). String value in "Duration" format. Defaults to "P0DT3S" (3 seconds). Set at sequence creation time, and cannot be reset.

Type: string

Constraints: Has Default Value: P0DT3S

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

inactivityTimeout

If during this duration, an endpoint (RM source or RM destination) has received no application or control messages, the endpoint MAY consider the RM Sequence to have been terminated due to inactivity. String value in "Duration" format. Defaults to "P0DT600S" (600 seconds). Implementations of RM source and RM destination are free to manage resources associated with the sequence as they please, but in general, there are no guarantees that the sequence will be useable by either party after the inactivity timeout expires. Set at sequence creation time, and cannot be reset.

Type: string

Constraints: Has Default Value: P0DT600S

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

Name=user-specified-name

Type: string

Constraints: Read Only, Legal Null: true

nonBufferedDestination

A boolean flag indicating that RM destinations, by default, will receive non-buffered. Defaults to false. Note, changes to this default will only be picked up by new reliable sequences. Existing reliable sequences have their persistence handling set at creation time and these values will not change.

Type: boolean

Constraints: Has Default Value: false

nonBufferedSource

A boolean flag indicating that RM sources, by default, will send non-buffered. Defaults to false. Note, changes to this default will only be picked up by new reliable sequences. Existing reliable sequences have their persistence handling set at creation time and these values will not change.

Type: boolean

Constraints: Has Default Value: false

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

retransmissionExponentialBackoff

A boolean flag indicating that the retransmission interval will be adjusted using the exponential backoff algorithm ([Tanenbaum]). Defaults to false. Set at sequence creation time, and cannot be reset.

Type: boolean

Constraints: Has Default Value: false

sequenceExpiration

This is the maximum lifetime of a sequence. If this limit is reached before the sequence naturally completes, it will be forcibly terminated. String value in "Duration" format. Defaults to "P1D" (1 day). Set at sequence creation time, and cannot be reset.

Type: string

Constraints: Has Default Value: P1D

tags

Return all tags on this Configuration MBean

Type: array of string

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.WebServiceRequestBufferingQueueMBean

Represents request buffering queue configuration for web services.

The properties of the weblogic.management.configuration.WebServiceRequestBufferingQueueMBean entity are as follows:

connectionFactoryJndiName

The JNDI name of the connection factory to use when buffering messages onto this queue. Defaults to the 'default' JMS connection factory.

Type: string

Constraints: Has Default Value: null

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

enabled

A boolean flag indicating whether buffering is enabled (request buffering if this is the request queue, or response buffering if this is the response queue). Defaults to false.

Type: boolean

Constraints: Has Default Value: false

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

name

Get the name of this buffering queue. This name is the JNDI name of the queue to be used for buffering.

Type: string

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

tags

Return all tags on this Configuration MBean

Type: array of string

transactionEnabled

A boolean flag indicating whether transactions should be used when buffering a message onto or consuming a message off of this queue. Defaults to false.

Type: boolean

Constraints: Has Default Value: false

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.WebServiceResponseBufferingQueueMBean

Represents response buffering queue configuration for web services.

The properties of the `weblogic.management.configuration.WebServiceResponseBufferingQueueMBean` entity are as follows:

connectionFactoryJndiName

The JNDI name of the connection factory to use when buffering messages onto this queue. Defaults to the 'default' JMS connection factory.

Type: string

Constraints: Has Default Value: null

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

enabled

A boolean flag indicating whether buffering is enabled (request buffering if this is the request queue, or response buffering if this is the response queue). Defaults to false.

Type: boolean

Constraints: Has Default Value: false

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

name

Get the name of this buffering queue. This name is the JNDI name of the queue to be used for buffering.

Type: string

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

tags

Return all tags on this Configuration MBean

Type: array of string

transactionEnabled

A boolean flag indicating whether transactions should be used when buffering a message onto or consuming a message off of this queue. Defaults to false.

Type: boolean

Constraints: Has Default Value: false

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.WebserviceCredentialProviderMBean

Encapsulates information about a particular credential provider that has been configured for a Web Service security configuration.

The properties of the `weblogic.management.configuration.WebserviceCredentialProviderMBean` entity are as follows:

className

The fully qualified name of the class that implements a particular credential provider or token handler.

Type: string

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to `config.xml`

Type: boolean

Constraints: Read Only, Has Default Value: false

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

Name=user-specified-name

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

tags

Return all tags on this Configuration MBean

Type: array of string

tokenType

Specifies the type of token used for the particular credential provider or token handler.

WebLogic Server supports, by default, three types of tokens: X.509, UsernameToken, and SAML, as specified by the following WS-Security specifications:

- Web Services Security: Username Token Profile
- Web Services Security: X.509 Token Profile
- Web Services Security: SAML Token Profile

To specify one of these out-of-the-box types, use these values respectively: "ut", "x509", or "saml".

Type: string

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.WebserviceSecurityMBean

Encapsulates information about a Web Service security configuration.

The properties of the weblogic.management.configuration.WebserviceSecurityMBean entity are as follows:

compatibilityOrderingPreference

Gets the value of the compatibilityOrderingPreference attribute.

Type: string

compatibilityPreference

Gets the value of the compatibilityPreference attribute.

Type: string

defaultCredentialProviderSTSURI

Gets the default STS endpoint URL for all WS-Trust enabled credential providers of this Web Service security configuration.

Type: string

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

Name=user-specified-name

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`.

Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

policySelectionPreference

Gets the value of the PolicySelectionPreference attribute.

The preference value can be one of the following:

- NONE
- SCP
- SPC
- CSP
- CPS
- PCS
- PSC

Where: S: Security or functionality; C: Compatibility or Interoperability; P: Performance

If NONE is specified, no preference is applied - the first policy alternative is always chosen, and optional policy assertions are ignored.

Type: string

Constraints: Has Default Value: NONE, Legal Values: NONE, SCP, SPC, CSP, CPS, PCS, PSC

tags

Return all tags on this Configuration MBean

Type: array of string

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.WebserviceSecurityTokenMBean

Encapsulates information about a particular token that has been configured for a Web Service security configuration.

The properties of the `weblogic.management.configuration.WebserviceSecurityTokenMBean` entity are as follows:

className

The fully qualified name of the class that implements a particular credential provider or token handler.

Type: string

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

Name=user-specified-name

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`.

Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

tags

Return all tags on this Configuration MBean

Type: array of string

tokenType

Specifies the type of token used for the particular credential provider or token handler.

WebLogic Server supports, by default, three types of tokens: X.509, UsernameToken, and SAML, as specified by the following WS-Security specifications:

- Web Services Security: Username Token Profile
- Web Services Security: X.509 Token Profile
- Web Services Security: SAML Token Profile

To specify one of these out-of-the-box types, use these values respectively: "ut", "x509", or "saml".

Type: string

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.WebserviceTestpageMBean

Controls the configuration of the Web Service Test Page.

The properties of the weblogic.management.configuration.WebserviceTestpageMBean entity are as follows:

basicAuthEnabled

Specifies whether the basic authentication is automatically used by Web Service Test Page in the current domain.

Type: boolean

Constraints: Has Default Value: true

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

enabled

Specifies whether the WebLogic Server automatically deploys Web Service Test Page in the current domain.

Type: boolean

Constraints: Has Default Value: false

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

Name=user-specified-name

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`.

Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

tags

Return all tags on this Configuration MBean

Type: array of string

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.WebserviceTimestampMBean

Encapsulates the timestamp information that is associated with a Web Service security configuration.

The properties of the weblogic.management.configuration.WebserviceTimestampMBean entity are as follows:

clockSkew

If clocks are synchronized, this attribute describes the accuracy of the synchronization between two clocks: the client and the server.

ClockSkew is expressed in milliseconds. Clock skew is enforced by rendering all times into milliseconds since a common time 0 and using these times for comparisons. For example, if your clocks are accurate to within 1 minute of each other, you would set your skew to 1 minute * 60 seconds * 1000 milliseconds or 60000.

Type: integer/int64

Constraints: Has Default Value: 60000, Minimum Value: 0

clockSynchronized

Specifies whether the Web Service assumes synchronized clocks.

If the clockSynchronized attribute is false, the Web Service rejects all inbound messages with that contain expirations, because this is the only safe way to ensure that the message hasn't already expired. In this case, the Web Service also does not enforce a freshness policy.

If this attribute is set to true, then the Web Service enforces expirations on inbound messages to the best of its ability and enforces an optional freshness policy (via maxProcessingDelay).

The default value of this attribute is true.

Type: boolean

Constraints: Has Default Value: true

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

maxProcessingDelay

Specifies the freshness policy for received messages: the Web Service observes the processing delay by subtracting the Created time in the Timestamp from the current time.

If the observed processing delay is greater than maxProcessingDelay plus clockSkew, then the message is rejected as stale.

This attribute is specified in milliseconds.

Setting maxProcessingDelay to NO_MAX_PROCESSING_DELAY disables to enforcement of the freshness policy.

Type: integer/int64

Constraints: Has Default Value: -1

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

`Name=user-specified-name`

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

tags

Return all tags on this Configuration MBean

Type: array of string

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

validityPeriod

Represents the length of time the sender wants the outbound message to be valid.

When the validityPeriod is positive, the TimestampHandler inserts an Expires element into the Timestamp header. The validityPeriod is expressed in seconds: the Expires time will be that many seconds ahead of the Timestamp's Created time.

Type: integer/int32

Constraints: Has Default Value: 60, Minimum Value: 1

weblogic.management.configuration.WebserviceTokenHandlerMBean

Encapsulates information about a particular token handler that has been configured for a Web Service security configuration.

The properties of the weblogic.management.configuration.WebserviceTokenHandlerMBean entity are as follows:

className

The fully qualified name of the class that implements a particular credential provider or token handler.

Type: string

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

handlingOrder

Specifies the order in which the token handlers execute on a given token.

If you do not specify an order, it is determined by the order in which you added the token handlers.

Type: integer/int32

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

`Name=user-specified-name`

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

tags

Return all tags on this Configuration MBean

Type: array of string

tokenType

Specifies the type of token used for the particular credential provider or token handler.

WebLogic Server supports, by default, three types of tokens: X.509, UsernameToken, and SAML, as specified by the following WS-Security specifications:

- Web Services Security: Username Token Profile
- Web Services Security: X.509 Token Profile
- Web Services Security: SAML Token Profile

To specify one of these out-of-the-box types, use these values respectively: "ut", "x509", or "saml".

Type: string

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.WorkManagerMBean

Configuration MBean representing WorkManager parameters. A WorkManager configuration can have a RequestClass(FairShare, ResponseTime, ContextBased), MinThreadsConstraint, MaxThreadsConstraint, Capacity and ShutdownTrigger. All these are optional and need to be configured as needed. An empty WorkManager without configuration gets its own default fair share. The default fair share value is 50.

The properties of the weblogic.management.configuration.WorkManagerMBean entity are as follows:

applicationScope

Specifies whether this work manager should be scoped to an application. By default, work managers are scoped to an application. Set this value to false if the work manager is to be scoped to a domain

Type: boolean

Constraints: Has Default Value: true

capacity

The total number of requests that can be queued or executing before WebLogic Server begins rejecting requests.

Type: weblogic.management.configuration.CapacityMBean reference

Constraints: Restart Required

contextRequestClass

The mapping of Request Classes to security names and groups.

Type: weblogic.management.configuration.ContextRequestClassMBean reference

Constraints: Restart Required

deploymentOrder

A priority that the server uses to determine when it deploys an item. The priority is relative to other deployable items of the same type.

For example, the server prioritizes and deploys all EJBs before it prioritizes and deploys startup classes.

Items with the lowest Deployment Order value are deployed first. There is no guarantee on the order of deployments with equal Deployment Order values. There is no guarantee of ordering across clusters.

Type: integer/int32

Constraints: Has Default Value: 1000, Minimum Value: 0, Maximum Value: 2147483647

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

fairShareRequestClass

Get the FairShareRequestClass for this WorkManager

Type: weblogic.management.configuration.FairShareRequestClassMBean reference

Constraints: Restart Required

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

ignoreStuckThreads

Specifies whether this Work Manager ignores "stuck" threads. Typically, stuck threads will cause the associated Work Manager to take some action: either switching the application to Admin mode, shutting down the server, or shutting down the Work Manager. If this flag is set, then no thread in this Work Manager is ever considered stuck.

If you do not explicitly specify IGNORE_STUCK_THREADS=TRUE, the default behavior is that upon encountering stuck threads, the server will take one of the aforementioned actions.

Type: boolean

maxThreadsConstraint

The maximum number of concurrent threads that can be allocated to execute requests.

Type: weblogic.management.configuration.MaxThreadsConstraintMBean reference

Constraints: Restart Required

minThreadsConstraint

The minimum number of threads allocated to resolve deadlocks.

Type: weblogic.management.configuration.MinThreadsConstraintMBean reference

Constraints: Restart Required

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

Name=user-specified-name

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

responseTimeRequestClass

The response time goal (in milliseconds).

Type: weblogic.management.configuration.ResponseTimeRequestClassMBean reference

Constraints: Restart Required

tags

Return all tags on this Configuration MBean

Type: array of string

targets

You must select a target on which an MBean will be deployed from this list of the targets in the current domain on which this item can be deployed. Targets must be either servers or clusters. The deployment will only occur once if deployments overlap.

Type: array of weblogic.management.configuration.TargetMBean references

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.WorkManagerShutdownTriggerMBean

This MBean is used to configure the trigger that shuts down the WorkManager. The trigger specifies the number of threads that need to be stuck for a certain amount of time for the trigger to shutdown the WorkManager automatically. A shutdown WorkManager refuses new work and completes pending work.

The properties of the weblogic.management.configuration.WorkManagerShutdownTriggerMBean entity are as follows:

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

maxStuckThreadTime

Time after which a executing thread is declared as stuck.

Type: integer/int32

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

Name=user-specified-name

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

resumeWhenUnstuck

Whether to resume work manager once the stuck threads were cleared

Type: boolean

Constraints: Has Default Value: true

stuckThreadCount

Number of stuck threads after which the WorkManager is shutdown

Type: integer/int32

tags

Return all tags on this Configuration MBean

Type: array of string

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.XMLEntityCacheMBean

Configure the behavior of JAXP (Java API for XML Parsing) in the server.

The properties of the weblogic.management.configuration.XMLEntityCacheMBean entity are as follows:

cacheDiskSize

The disk size, in MB, of the persistent disk cache. The default value is 5 MB.

Return the disk size in MBytes of the cache.

Type: integer/int32

Constraints: Has Default Value: 5, Minimum Value: 0

cacheLocation

Provides the path name for the persistent cache files.

Type: string

Constraints: Has Default Value: xmlcache

cacheMemorySize

The memory size, in KB, of the cache. The default value is 500 KB.

Return the memory size in KBytes of the cache.

Type: integer/int32

Constraints: Has Default Value: 500, Minimum Value: 0

cacheTimeoutInterval

The default timeout interval, in seconds, for the cache. The default value is 120 seconds.

Return the default timeout interval in seconds for the cache.

Type: integer/int32

Constraints: Has Default Value: 120, Minimum Value: 0

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

maxSize

Provides the maximum number of entries that can be stored in the cache at any given time.

Type: integer/int32

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's

`javax.management.ObjectName`

`Name=user-specified-name`

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as

XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`.

Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

tags

Return all tags on this Configuration MBean

Type: array of string

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.XMLEntitySpecRegistryEntryMBean

An Entity Spec Entry specifies how to resolve an external entity based its public and system IDs.

When WebLogic Server is parsing an XML document and it encounters the specified external entity, WebLogic Server resolves the entity according to the values entered for this entry. You can specify that the external entity resolve to a particular resource whose location is either a pathname reachable by the Administration Server or a URI to a local repository.

An Entity Spec entry is part of an XML Registry.

For this type of registry entry the document type is identified by either or both of:

- a public ID (e.g, "-//Sun Microsystems, Inc.//DTD Enterprise JavaBeans 2.0//EN")

- a system ID (e.g, "http://java.sun.com/j2ee/dtds/ejb-jar_2_0.dtd")

This configuration information is used by the WebLogic JAXP implementation to set up SAX EntityResolvers.

The properties of the `weblogic.management.configuration.XMLEntitySpecRegistryEntryMBean` entity are as follows:

cacheTimeoutInterval

Specifies the default timeout interval (in seconds) of the external entity cache.

A value of -1 means that the entity cache timeout interval defers to the one specified for the XML registry of which this Entity Spec entry is a part.

Type: integer/int32

Constraints: Has Default Value: -1, Minimum Value: -1

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to config.xml

Type: boolean

Constraints: Read Only, Has Default Value: false

entityURI

The location of the external entity, either a pathname or URI.

The location of the external entity can be either a pathname relative to the XML Registry directories, reachable by the Administration Server, or a URI of the entity location in some local repository.

Type: string

handleEntityInvalidation

Whether cached DTD/schema is invalidated when parsing error is encountered.

Type: string

Constraints: Has Default Value: defer-to-registry-setting, Legal Values: true, false, defer-to-registry-setting

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

Name=user-specified-name

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

publicId

The public ID of the external entity.

When WebLogic Server is parsing an XML document and it encounters an external entity with this public ID, WebLogic Server resolves the entity (to either a local file or a URL resource) according to the values set for this Entity spec entry.

Type: string

systemId

The system ID of the external entity.

When WebLogic Server is parsing an XML document and it encounters an external entity with this system ID, WebLogic Server resolves the entity (to either a local file or a URL resource) according to the values set for this Entity spec entry.

Type: string

tags

Return all tags on this Configuration MBean

Type: array of string

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

whenToCache

Specifies when WebLogic Server should cache the external entities it retrieves from the Web.

WebLogic Server can cache the entities when they are referenced, as soon as possible (that is, on initialization) or never. Additionally, WebLogic Server can defer to the XML registry's cache setting.

Type: string

Constraints: Has Default Value: `defer-to-registry-setting`, Legal Values: `cache-on-reference`, `cache-at-initialization`, `cache-never`, `defer-to-registry-setting`

weblogic.management.configuration.XMLParserSelectRegistryEntryMBean

A Parser Select Entry specifies the SAX/DOM parser factory implementation classes for a particular document type.

By default, WebLogic server uses either the built-in (out-of-the-box) or default SAX/DOM parser factory implementation classes when it parses an XML document. However, you can specify that particular XML documents, based on their public IDs, system IDs, or root elements, use different parser factory implementation classes than

the default. You do this by first creating an XML Registry and then creating a Parser Select entry and specifying how to identify the document and then the desired implementation classes.

The XML document type is identified by one or more of the following:

- a public ID (e.g, "-//Sun Microsystems, Inc.//DTD Enterprise JavaBeans 2.0//EN")
- a system ID (e.g, "http://java.sun.com/j2ee/dtds/ejb-jar_2_0.dtd")
- a document root tag name (e.g., "ejb-jar")

This configuration information is used by the WebLogic JAXP implementation to choose the appropriate parser factories (SAX and DOM).

The properties of the `weblogic.management.configuration.XMLParserSelectRegistryEntryMBean` entity are as follows:

SAXParserFactory

Specifies the fully qualified name of the class that implements the `SAXParserFactory` API.

When WebLogic Server begins to parse an XML document identified by either the public ID, system ID, or root element specified in this entry, and the applications specifies it wants a SAX parser, then WebLogic Server uses this implementation class when using the `javax.xml.parsers.SAXParserFactory` to obtain the SAX parser.

Type: string

documentBuilderFactory

Specifies the fully qualified name of the class that implements the `DocumentBuilderFactory` API

When WebLogic Server begins to parse an XML document identified by either the public ID, system ID, or root element specified in this entry, and the applications specifies it wants a DOM parser, then WebLogic Server uses this implementation class when using the `javax.xml.parsers.DocumentBuilderFactory` to obtain the DOM parser.

Type: string

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to `config.xml`

Type: boolean

Constraints: Read Only, Has Default Value: false

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

`Name=user-specified-name`

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`. Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

publicId

Specifies the public ID of the XML document type for which this XML registry entry is being configured.

When WebLogic Server starts to parse an XML document that is identified with this public ID, it uses the SAX or DOM parser factory implementation class specified by this registry entry, rather than the built-in or default, when obtaining a SAX or DOM parser.

Type: string

rootElementTag

Specifies the root element of the XML document type for which this XML registry entry is being configured.

When WebLogic Server starts to parse an XML document that is identified with this root element, it uses the SAX or DOM parser factory implementation class specified by this registry entry, rather than the built-in or default, when obtaining a SAX or DOM parser.

Type: string

systemId

Specifies the system ID of the XML document type for which this XML registry entry is being configured.

When WebLogic Server starts to parse an XML document that is identified with this system ID, it uses the SAX or DOM parser factory implementation class specified by this registry entry, rather than the built-in or default, when obtaining a SAX or DOM parser.

Type: string

tags

Return all tags on this Configuration MBean

Type: array of string

transformerFactory

Specifies the fully qualified name of the class that implements the `TransformerFactory` API.

When WebLogic Server begins to transform an XML document identified by either the public ID, system ID, or root element specified in this entry, then WebLogic Server uses this implementation class when using the `javax.xml.transform.TransformerFactory` factory to obtain a `Transformer` object.

Type: string

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

weblogic.management.configuration.XMLRegistryMBean

Configure the behavior of JAXP (Java API for XML Parsing) in the server.

You configure this behavior by creating XML Registries that specify the default DOM and Sax factory implementation class, transformer factory implementation class, external entity resolution and caching.

The properties of the weblogic.management.configuration.XMLRegistryMBean entity are as follows:

SAXParserFactory

The fully qualified name of the class that implements the `SAXParserFactory` interface.

The `javax.xml.parsers.SAXParserFactory` factory API enables applications deployed to WebLogic Server to configure and obtain a SAX-based XML parser to parse XML documents.

The built-in WebLogic Server SAX factory implementation class is `com.sun.org.apache.xerces.internal.jaxp.SAXParserFactoryImpl`. This is the factory class applications deployed to WebLogic Server get by default when they request a SAX parser. You can change this default by updating this value.

Return the class name of the default `SAXParserFactory`

Type: string

Constraints: Has Default Value: `weblogic.xml.jaxp.WebLogicSAXParserFactory`

XMLEventFactory

The fully qualified name of the class that implements the `XMLEventFactory` interface.

The `javax.xml.stream.XMLEventFactory` factory API enables applications deployed to WebLogic Server to configure and obtain a `XMLEvent` object used to parse or build XML streams.

The built-in WebLogic Server `XMLEvent` factory implementation class is `com.ctc.wstx.stax.WstxEventFactory`. This is the factory class applications deployed to WebLogic Server get by default when they request a `XMLEvent` object. You can change this default by updating this value.

Return the class name of the default `XMLEventFactory`

Type: string

Constraints: Has Default Value: `weblogic.xml.jaxp.WebLogicXMLEventFactory`

XMLInputFactory

The fully qualified name of the class that implements the `XMLInputFactory` interface.

The `javax.xml.stream.XMLInputFactory` factory API enables applications deployed to WebLogic Server to configure and obtain a `XMLStreamReader/XMLStreamReader` object used to read XML streams.

The built-in WebLogic Server XML Input factory implementation class is `com.ctc.wstx.stax.WstxInputFactory`. This is the factory class applications deployed

to WebLogic Server get by default when they request a `XMLEventReader/XMLStreamReader` object. You can change this default by updating this value.

Return the class name of the default `XMLInputFactory`

Type: string

Constraints: Has Default Value: `weblogic.xml.jaxp.WebLogicXMLInputFactory`

XMLOutputFactory

The fully qualified name of the class that implements the `XMLOutputFactory` interface.

The `javax.xml.stream.XMLOutputFactory` factory API enables applications deployed to WebLogic Server to configure and obtain a `XMLEventWriter/XMLStreamWriter` object used to write XML streams.

The built-in WebLogic Server XML Output factory implementation class is `com.ctc.wstx.stax.WstxOutputFactory`. This is the factory class applications deployed to WebLogic Server get by default when they request a `XMLEventWriter/XMLStreamWriter` object. You can change this default by updating this value.

Return the class name of the default `XMLOutputFactory`

Type: string

Constraints: Has Default Value: `weblogic.xml.jaxp.WebLogicXMLOutputFactory`

documentBuilderFactory

The fully qualified name of the class that implements the `DocumentBuilderFactory` interface.

The `javax.xml.parsers.DocumentBuilderFactory` factory API enables applications deployed to WebLogic Server to obtain an XML parser that produces DOM object trees from XML documents.

The built-in WebLogic Server DOM factory implementation class is `com.sun.org.apache.xerces.internal.jaxp.DocumentBuilderFactoryImpl`. This is the factory class applications deployed to WebLogic Server get by default when they request a DOM parser. You can change this default by updating this value.

Return the class name of the default `DocumentBuilderFactory`

Type: string

Constraints: Has Default Value: `weblogic.xml.jaxp.WebLogicDocumentBuilderFactory`

dynamicallyCreated

Return whether the MBean was created dynamically or is persisted to `config.xml`

Type: boolean

Constraints: Read Only, Has Default Value: `false`

handleEntityInvalidation

Whether cached DTD/schema is invalidated when parsing error is encountered.

Type: boolean

Constraints: Has Default Value: `false`

id

Return the unique id of this MBean instance

Type: integer/int64

Constraints: Read Only

name

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's

`javax.management.ObjectName`

`Name=user-specified-name`

Type: string

Constraints: Read Only, Legal Null: true

notes

Optional information that you can include to describe this configuration.

WebLogic Server saves this note in the domain's configuration file (`config.xml`) as

XML PCDATA. All left angle brackets (<) are converted to the XML entity `<`;

Carriage returns/line feeds are preserved.

Note: If you create or edit a note from the Administration Console, the Administration Console does not preserve carriage returns/line feeds.

Type: string

schemaFactory

The fully qualified name of the class that implements the `SchemaFactory` interface.

The `javax.xml.validation.SchemaFactory` factory API enables applications deployed to WebLogic Server to configure and obtain a `Schema` object used to validate XML document using schema.

The built-in WebLogic Server Schema factory implementation class is `com.sun.org.apache.xerces.internal.jaxp.validation.XMLSchemaFactory`. This is the factory class applications deployed to WebLogic Server get by default when they request a `Schema` object. You can change this default by updating this value.

Return the class name of the default `SchemaFactory`

Type: string

Constraints: Has Default Value: `weblogic.xml.jaxp.WebLogicSchemaFactory`

tags

Return all tags on this Configuration MBean

Type: array of string

transformerFactory

The fully qualified name of the class that implements the `TransformerFactory` interface.

The `javax.xml.transform.TransformerFactory` factory API enables applications deployed to WebLogic Server to configure and obtain a `Transformer` object used to transform XML data into another format.

The built-in WebLogic Server Transformer factory implementation class is `com.sun.org.apache.xalan.internal.xsltc.trax.TransformerFactoryImpl`. This is the factory class applications deployed to WebLogic Server get by default when they request a `Transformer` object. You can change this default by updating this value.

Return the class name of the default `TransformerFactory`

Type: string

Constraints: Has Default Value: weblogic.xml.jaxp.WebLogicTransformerFactory

type

Returns the type of the MBean.

Type: string

Constraints: Read Only

whenToCache

Specifies when WebLogic Server should cache external entities that it retrieves from the Web.

When WebLogic Server resolves an external entity within an XML file and retrieves the entity from the Web, you can specify that WebLogic Server cache this entity only when the entity is first referenced, when WebLogic Server first starts up, or not at all.

Type: string

Constraints: Has Default Value: cache-on-reference, Legal Values: cache-on-reference, cache-at-initialization, cache-never

xpathFactory

The fully qualified name of the class that implements the XPathFactory interface.

The javax.xml.xpath.XPathFactory factory API enables applications deployed to WebLogic Server to configure and obtain a XPath object used to search XML elements.

The built-in WebLogic Server XPath factory implementation class is com.sun.org.apache.xpath.internal.jaxp.XPathFactoryImpl. This is the factory class applications deployed to WebLogic Server get by default when they request a XPath object. You can change this default by updating this value.

Return the class name of the default XPathFactory

Type: string

Constraints: Has Default Value: weblogic.xml.jaxp.WebLogicXPathFactory

weblogic.management.rest.bean.model.ChangeManager

The ChangeManager entity includes properties that are required for change management.

The properties of the weblogic.management.rest.bean.model.ChangeManager entity are as follows:

editSession

The name of the edit session.

Type: string

hasChanges

True if there are any changes that have been saved.

Type: boolean

lockOwner

The user name of the owner of the current configuration lock.

Type: string

locked

True if a configuration session is currently active.

Type: boolean

mergeNeeded

True if there are any changes in the global configuration that need to be merged with this edit session before the default edit session can be activated.

Type: boolean

weblogic.management.rest.bean.model.CurrentUser

The authenticated user that is making the request.

The properties of the weblogic.management.rest.bean.model.CurrentUser entity are as follows:

partitionId

The ID of the partition where the component that is being invoked resides.

Type: string

partitionName

The human readable name of the partition ID.

Type: string

user

The login of the user making this request, if the user has been authenticated, or null if the user has not been authenticated.

Type: string

weblogic.management.rest.bean.model.Version

A Version entity describes a version of the WebLogic Server resources.

The properties of the weblogic.management.rest.bean.model.Version entity are as follows:

isLatest

True if this is the default version.

Type: boolean

lifecycle

The lifecycle of this version: active or deprecated

Type: string

version

The name of this version.

Type: string

weblogic.management.security.RDBMSecurityStoreMBean

The MBean that represents configuration attributes for a RDBMS security store. It is used to specify the required and optional properties for connecting to a RDBMS back-end store.

The properties of the weblogic.management.security.RDBMSecurityStoreMBean entity are as follows:

JMSExceptionReconnectAttempts

The number of times to attempt to reconnect if the JMS system notifies Kodo of a serious connection error.

The default is 0, and by default the error is logged but ignored. The value cannot be less than 0.

Type: integer/int32

Constraints: Has Default Value: 0, Minimum Value: 0

JMSTopic

The JMS topic to which the Kodo remote commit provider should publish notifications and subscribe for notifications sent from other JVMs. This setting varies depending on the application server in use.

Type: string

JMSTopicConnectionFactory

The JNDI name of a `javax.jms.TopicConnectionFactory` instance to use for finding JMS topics.

This setting varies depending on the application server in use. Consult the JMS documentation for details about how this parameter should be specified.

Type: string

JNDIPassword

The password to authenticate the user defined in the `JNDIUsername` attribute for Kodo notification.

When getting the value of this attribute, WebLogic Server does the following:

- Retrieves the value of the `JNDIPasswordEncrypted` attribute.
- Decrypts the value and returns the unencrypted password as a `String`.

When you set the value of this attribute, WebLogic Server does the following:

- Encrypts the value.
- Sets the value of the `JNDIPasswordEncrypted` attribute to the encrypted value.

Using this attribute (`JNDIPassword`) is a potential security risk because the `String` object (which contains the unencrypted password) remains in the JVM's memory until garbage collection removes it and the memory is reallocated. Depending on how memory is allocated in the JVM, a significant amount of time could pass before this unencrypted data is removed from memory.

Instead of using this attribute, use `JNDIPasswordEncrypted`

Type: string

Constraints: Encrypted

JNDIUsername

The JNDI user name used for Kodo notification.

Type: string

connectionProperties

The JDBC driver specific connection parameters. This attribute is a comma-delimited list of key-value properties to pass to the driver for configuration of JDBC connection pool, in the form of `xxKey=xxValue, xxKey=xxValue`

The syntax of the attribute will be validated and an `InvalidAttributeValueException` is thrown if the check failed.

Type: string

connectionURL

The URL of the database to which to connect. The format of the URL varies by JDBC driver.

The URL is passed to the JDBC driver to create the physical database connections.

Type: string

Constraints: Legal Null: true

driverName

The full package name of the JDBC driver class used to create the physical database connections in the connection pool. Note that this driver class must be in the classpath of any server to which it is deployed.

For example:

- `oracle.jdbc.OracleDriver`
- `com.microsoft.sqlserver.jdbc.SQLServerDriver`

It must be the name of a class that implements the `java.sql.Driver` interface. The full pathname of the JDBC driver is available in the documentation.

Type: string

Constraints: Legal Null: true

name

The name of this configuration.

Type: string

Constraints: Read Only, Has Default Value: `RDBMSSecurityStore`

notificationProperties

The comma-delimited list of key-value properties to pass to the JNDI `InitialContext` on construction, in the form of `xxKey=xxValue, xxKey=xxValue`

The following are examples of keys:

- `java.naming.provider.url`: property for specifying configuration information for the service provider to use. The value of the property should contain a URL string (For example: `iiops://localhost:7002`).
- `java.naming.factory.initial`: property for specifying the initial context factory to use. The value of the property should be the fully qualified class name of the factory class that will create an initial context (For example: `weblogic.jndi.WLInitialContextFactory`).

When setting the attribute, the syntax of its value is validated, and an `InvalidAttributeValueException` is thrown if the check fails.

Type: string

password

The password for the user specified in the `Username` attribute for connecting to the datastore.

When getting the value of this attribute, WebLogic Server does the following:

- Retrieves the value of the `PasswordEncrypted` attribute.
- Decrypts the value and returns the unencrypted password as a `String`.

When you set the value of this attribute, WebLogic Server does the following:

- Encrypts the value.
- Sets the value of the `PasswordEncrypted` attribute to the encrypted value.

Note that use of the `Password` attribute is a potential security risk because the `String` object that contains the unencrypted password remains in the JVM's memory until garbage collection removes it and the memory is reallocated. Depending on how memory is allocated in the JVM, a significant amount of time could pass before this unencrypted data is removed from memory.

Instead of using this attribute, use `PasswordEncrypted`

Type: string

Constraints: Encrypted

realm

Returns the realm that contains this RDBMS security store. Returns null if this RDBMS security store is not contained by a realm.

Type: `weblogic.management.security.RealmMBean` reference

Constraints: Read Only

username

The username to use when connecting to the datastore.

Type: string

Constraints: Legal Null: true

weblogic.management.security.RealmMBean

The MBean that represents configuration attributes for the security realm.

A security realm contains a set of security configuration settings, including the list of security providers to use (for example, for authentication and authorization).

Code using security can either use the default security realm for the domain or refer to a particular security realm by name (by using the JMX display name of the security realm).

One security realm in the WebLogic domain must have the `DefaultRealm` attribute set to true. The security realm with the `DefaultRealm` attribute set to true is used as the default security realm for the WebLogic domain. Note that other available security realms must have the `DefaultRealm` attribute set to false.

When WebLogic Server boots, it locates and uses the default security realm. The security realm is considered active since it is used when WebLogic Server runs. Any security realm that is not used when WebLogic Server runs is considered inactive. All active security realms must be configured before WebLogic Server is boots.

Since security providers are scoped by realm, the `Realm` attribute on a security provider must be set to the realm that uses the provider.

The properties of the `weblogic.management.security.RealmMBean` entity are as follows:

adjudicatorTypes

Returns the types of Adjudication providers that may be created in this security realm, for example, `weblogic.security.providers.authorization.DefaultAdjudicator`. Use this method to find the available types to pass to `createAdjudicator`

Type: array of string

Constraints: Read Only

auditorTypes

Returns the types of Auditing providers that may be created in this security realm, for example, `weblogic.security.providers.audit.DefaultAuditor`. Use this method to find the available types to pass to `createAuditor`

Type: array of string

Constraints: Read Only

authMethods

Returns a comma separated string of authentication methods that should be used when the Web application specifies "REALM" as its auth-method. The authentication methods will be applied in order in which they appear in the list.

Type: string

authenticationProviderTypes

Returns the types of Authentication providers that may be created in this security realm, for example, `weblogic.security.providers.authentication.DefaultAuthenticator`. Use this method to find the available types to pass to `createAuthenticationProvider`

Type: array of string

Constraints: Read Only

authorizerTypes

Returns the types of Authorization providers that may be created in this security realm, for example, `weblogic.security.providers.authorization.DefaultAuthorizer`. Use this method to find the available types to pass to `createAuthorizer`

Type: array of string

Constraints: Read Only

autoRestartOnNonDynamicChanges

Specifies whether the Realm will be auto-restarted if non-dynamic changes are made to the realm or providers within the realm.

Type: boolean

certPathBuilder

Returns the CertPath Builder provider in this security realm that will be used by the security system to build certification paths. Returns null if none has been selected. The provider will be one of this security realm's CertPathProviders

Type: weblogic.management.security.pk.CertPathBuilderMBean reference

Constraints: Restart Required

certPathProviderTypes

Returns the types of Certification Path providers that may be created in this security realm, for example, weblogic.security.providers.pk.WebLogicCertPathProvider. Use this method to find the available types to pass to createCertPathProvider

Type: array of string

Constraints: Read Only

combinedRoleMappingEnabled

Determines how the role mappings in the Enterprise Application, Web application, and EJB containers interact. This setting is valid only for Web applications and EJBs that use the Advanced security model and that initialize roles from deployment descriptors.

When enabled:

- Application role mappings are combined with EJB and Web application mappings so that all principal mappings are included. The Security Service combines the role mappings with a logical OR operator.
- If one or more policies in the web.xml file specify a role for which no mapping exists in the weblogic.xml file, the Web application container creates an empty map for the undefined role (that is, the role is explicitly defined as containing no principal). Therefore, no one can access URL patterns that are secured by such policies.
- If one or more policies in the ejb-jar.xml file specify a role for which no mapping exists in the weblogic-ejb-jar.xml file, the EJB container creates an empty map for the undefined role (that is, the role is explicitly defined as containing no principal). Therefore, no one can access methods that are secured by such policies.

When disabled:

- Role mappings for each container are exclusive to other containers unless defined by the <externally-defined> descriptor element.
- If one or more policies in the web.xml file specify a role for which no role mapping exists in the weblogic.xml file, the Web application container assumes that the undefined role is the name of a principal. It therefore maps the assumed principal to the role name. For example, if the web.xml file contains the following stanza in one of its policies:

```
<auth-constraint> <role-name>PrivilegedUser</role-name>
</auth-constraint>
```

but, if the weblogic.xml file has no role mapping for PrivilegedUser, then the Web application container creates an in-memory mapping that is equivalent to the following stanza:

```
<security-role-assignment> <role-name>PrivilegedUser</role-name>
<principal-name>PrivilegedUser</principal-name>
</security-role-assignment>
```

- Role mappings for EJB methods must be defined in the `weblogic-ejb-jar.xml` file. Role mappings defined in the other containers are not used unless defined by the `<externally-defined>` descriptor element.

Note:

For all applications previously deployed in version 8.1 and upgraded to version 9.x, the combining role mapping is disabled by default.

Type: boolean

Constraints: Has Default Value: true

credentialMapperTypes

Returns the types of Credential Mapping providers that may be created in this security realm, for example,

`weblogic.security.providers.credentials.DefaultCredentialMapper`. Use this method to find the available types to pass to `createCredentialMapper`

Type: array of string

Constraints: Read Only

delegateMBeanAuthorization

Configures the WebLogic Server MBean servers to use the security realm's Authorization providers to determine whether a JMX client has permission to access an MBean attribute or invoke an MBean operation.

You can continue to use WebLogic Server's default security settings or modify the defaults to suit your needs.

If you do not delegate authorization to the realm's Authorization providers, the WebLogic MBean servers allow access only to the four default security roles (Admin, Deployer, Operator, and Monitor) and only as specified by WebLogic Server's default security settings.

Type: boolean

Constraints: Has Secure Value: true, Has Default Value: false

deployableProviderSynchronizationEnabled

Specifies whether synchronization for deployable Authorization and Role Mapping providers is enabled.

The Authorization and Role Mapping providers may or may not support parallel security policy and role modification, respectively, in the security provider database. If the security providers do not support parallel modification, the WebLogic Security Framework enforces a synchronization mechanism that results in each application and module being placed in a queue and deployed sequentially.

Type: boolean

Constraints: Has Default Value: false

deployableProviderSynchronizationTimeout

Returns the timeout value, in milliseconds, for the deployable security provider synchronization operation. This value is only used if `DeployableProviderSynchronizationEnabled` is set to `true`

Type: integer/int32

Constraints: Has Default Value: 60000

enableWebLogicPrincipalValidatorCache

Returns whether the WebLogic Principal Validator caching is enabled.

The Principal Validator is used by Oracle supplied authentication providers and may be used by custom authentication providers. If enabled, the default principal validator will cache WebLogic Principal signatures.

Type: boolean

Constraints: Has Default Value: true

identityAssertionHeaderNamePrecedence

Obtain an ordered list of token type names used for Identity Assertion with HTTP request headers.

The list determines the precedence order when multiple HTTP headers are present in an HTTP request based on the list of active token types maintained on the configured Authentication providers.

Type: array of string

Constraints: Has Default Value: null

managementIdentityDomain

Sets the Management Identity Domain value for the realm.

Type: string

maxWebLogicPrincipalsInCache

Returns the maximum size of the LRU cache for holding WebLogic Principal signatures. This value is only used if `enableWebLogicPrincipalValidatorCache` is set to true

Type: integer/int32

Constraints: Has Default Value: 500

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Has Default Value: Realm

passwordValidatorTypes

Returns the types of Password Validator providers that may be created in this security realm, for example, `com.bea.security.providers.authentication.passwordvalidator.SystemPasswordValidator`. Use this method to find the available types to pass to `createPasswordValidator`

Type: array of string

Constraints: Read Only

retireTimeoutSeconds

Specifies the retire timeout for a realm that is restarted. The old realm will be shutdown after the specified timeout period has elapsed.

Type: integer/int32

Constraints: Has Default Value: 60, Minimum Value: 1

roleMapperTypes

Returns the types of Role Mapping providers that may be created in this security realm, for example, `weblogic.security.providers.authorization.DefaultRoleMapper`. Use this method to find the available types to pass to `createRoleMapper`

Type: array of string

Constraints: Read Only

securityDDModel

Specifies the default security model for Web applications or EJBs that are secured by this security realm. You can override this default during deployment.

Note: If you deploy a module by modifying the domain's `config.xml` file and restarting the server, and if you do not specify a security model value for the module in `config.xml`, the module is secured with the default value of the `AppDeploymentMBean SecurityDDModel` attribute (see `weblogic.management.configuration.AppDeploymentMBean#getSecurityDDModel()` `getSecurityDDModel()`).

Choose one of these security models:

- Deployment Descriptors Only (DDOnly)
- For EJBs and URL patterns, this model uses only the roles and policies in the J2EE deployment descriptors (DD); the Administration Console allows only read access for this data. With this model, EJBs and URL patterns are not protected by roles and policies of a broader scope (such as a policy scoped to an entire Web application). If an EJB or URL pattern is not protected by a role or policy in the DD, then it is unprotected: anyone can access it.
- For application-scoped *roles* in an EAR, this model uses only the roles defined in the WebLogic Server DD; the Administration Console allows only read access for this data. If the WebLogic Server DD does not define roles, then there will be no such scoped roles defined for this EAR.
- For all other types of resources, you can use the Administration Console to create roles or policies. For example, with this model, you can use the Administration Console to create application-scoped *policies* for an EAR.
- Applies for the life of the deployment. If you want to use a different model, you must delete the deployment and reinstall it.
- Customize Roles Only (CustomRoles)
- For EJBs and URL patterns, this model uses only the *policies* in the J2EE deployment descriptors (DD). EJBs and URL patterns are not protected by policies of a broader scope (such as a policy scoped to an entire Web application). This model ignores any *roles* defined in the DDs; an administrator completes the role mappings using the Administration Console.
- For all other types of resources, you can use the Administration Console to create roles or policies. For example, with this model, you can use the Administration Console to create application-scoped policies or roles for an EAR.
- Applies for the life of the deployment. If you want to use a different model, you must delete the deployment and reinstall it.
- Customize Roles and Policies (CustomRolesAndPolicies)
- Ignores any roles and policies defined in deployment descriptors. An administrator uses the Administration Console to secure the resources.

- Performs security checks for **all** URLs or EJB methods in the module.
- Applies for the life of the deployment. If you want to use a different model, you must delete the deployment and reinstall it.
- Advanced (Advanced)

You configure how this model behaves by setting values for the following options:

- When Deploying Web Applications or EJBs

Note: When using the WebLogic Scripting Tool or JMX APIs, there is no single MBean attribute for this setting. Instead, you must set the values for the `DeployPolicyIgnored` and `DeployRoleIgnored` attributes of `RealmMBean`

- Check Roles and Policies (`FullyDelegateAuthorization`)
- Combined Role Mapping Enabled (`CombinedRoleMappingEnabled`)

You can change the configuration of this model. Any changes immediately apply to all modules that use the Advanced model. For example, you can specify that all modules using this model will copy roles and policies from their deployment descriptors into the appropriate provider databases upon deployment. After you deploy all of your modules, you can change this behavior to ignore roles and policies in deployment descriptors so that when you redeploy modules they will not re-copy roles and policies.

Note: Prior to WebLogic Server version 9.0 the Advanced model was the only security model available. Use this model if you want to continue to secure EJBs and Web Applications as in releases prior to 9.0.

Type: string

Constraints: Has Default Value: `DDOnly`, Legal Values: `DDOnly`, `CustomRoles`, `CustomRolesAndPolicies`, `Advanced`

validateDDSecurityData

Not used in this release.

Type: boolean

Constraints: Has Default Value: `false`

weblogic.management.security.audit.AuditorMBean

The SSPI MBean that all Audit providers must extend.

The properties of the `weblogic.management.security.audit.AuditorMBean` entity are as follows:

description

Returns a description of this security provider.

Each security provider's MBean should set the default value of this read-only attribute to a string that describes the provider. In other words, each security provider's MBean hard-wires its description. There are no conventions governing the contents of the description. It should be a human readable string that gives a brief description of the security provider.

Type: string

Constraints: Read Only

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Has Default Value: Provider

realm

Returns the realm that contains this security provider. Returns null if this security provider is not contained by a realm.

Type: weblogic.management.security.RealmMBean reference

Constraints: Read Only

version

Returns this security provider's version.

Each security provider's MBean should set the default value of this read-only attribute to a string that specifies the version of the provider (e.g. 7.3.04). In other words, each security provider's MBean hard-wires its version. There are no conventions governing the contents of the version string.

Type: string

Constraints: Read Only

weblogic.management.security.authentication.AuthenticationProviderMBean

The base MBean for all MBean implementations that manage Authentication providers. If your Authentication provider uses the WebLogic Security SSPI to provide login services, then your MBean must extend `weblogic.management.security.authentication.Authenticator`. If your Authentication provider uses the WebLogic Security SSPI to provide identity-assertion services, then your MBean must extend `weblogic.management.security.authentication.IdentityAsserter`

The properties of the `weblogic.management.security.authentication.AuthenticationProviderMBean` entity are as follows:

description

Returns a description of this security provider.

Each security provider's MBean should set the default value of this read-only attribute to a string that describes the provider. In other words, each security provider's MBean hard-wires its description. There are no conventions governing the contents of the description. It should be a human readable string that gives a brief description of the security provider.

Type: string

Constraints: Read Only

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Has Default Value: Provider

realm

Returns the realm that contains this security provider. Returns null if this security provider is not contained by a realm.

Type: weblogic.management.security.RealmMBean reference

Constraints: Read Only

version

Returns this security provider's version.

Each security provider's MBean should set the default value of this read-only attribute to a string that specifies the version of the provider (e.g. 7.3.04). In other words, each security provider's MBean hard-wires its version. There are no conventions governing the contents of the version string.

Type: string

Constraints: Read Only

weblogic.management.security.authentication.PasswordValidatorMBean

A marker interface to indicate a password validation provider MBean. All password validation provider MBeans must extend this interface.

The properties of the weblogic.management.security.authentication.PasswordValidatorMBean entity are as follows:

description

Returns a description of this security provider.

Each security provider's MBean should set the default value of this read-only attribute to a string that describes the provider. In other words, each security provider's MBean hard-wires its description. There are no conventions governing the contents of the description. It should be a human readable string that gives a brief description of the security provider.

Type: string

Constraints: Read Only

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Has Default Value: Provider

realm

Returns the realm that contains this security provider. Returns null if this security provider is not contained by a realm.

Type: weblogic.management.security.RealmMBean reference

Constraints: Read Only

version

Returns this security provider's version.

Each security provider's MBean should set the default value of this read-only attribute to a string that specifies the version of the provider (e.g. 7.3.04). In other words, each security provider's MBean hard-wires its version. There are no conventions governing the contents of the version string.

Type: string

Constraints: Read Only

weblogic.management.security.authentication.UserLockoutManagerMBean

Lists and manages lockouts on user accounts.

The properties of the weblogic.management.security.authentication.UserLockoutManagerMBean entity are as follows:

lockoutCacheSize

Returns the number of invalid login records that the server places in a cache. The server creates one record for each invalid login.

Type: integer/int64

Constraints: Has Default Value: 5, Minimum Value: 0, Maximum Value: 2147483647

lockoutDuration

Returns the number of minutes that a user account is locked out.

Type: integer/int64

Constraints: Has Default Value: 30, Minimum Value: 0, Maximum Value: 2147483647

lockoutEnabled

Returns whether the server locks out users when there are invalid login attempts. A `true` value for this attribute causes the server to consider the other attributes of this MBean. A `false` value causes the server to ignore the other attributes of this MBean."

Type: boolean

Constraints: Has Default Value: true

lockoutGCThreshold

Returns the maximum number of invalid login records that the server keeps in memory.

If the number of invalid login records is equal to or greater than this value, the server's garbage collection purges the records that have expired. A record expires when the user associated with the record has been locked out.

The lower the threshold, the more often the server uses its resources to collect garbage.

Type: integer/int64

Constraints: Has Default Value: 400, Minimum Value: 0, Maximum Value: 2147483647

lockoutResetDuration

The number of minutes within which consecutive invalid login attempts cause the user account to be locked out.

Type: integer/int64

Constraints: Has Default Value: 5, Minimum Value: 1, Maximum Value: 2147483647

lockoutThreshold

Returns the maximum number of consecutive invalid login attempts before account is locked out. When the number of invalid logins within a specified period of time is greater than `lockoutThresholdvalue`, the user is locked out. For example, with the default setting of `5`, the user is locked out on the second consecutive invalid login. With a setting of `3`, the user is locked out on the third consecutive invalid login.

Type: integer/int64

Constraints: Has Default Value: 5, Minimum Value: 1, Maximum Value: 2147483647

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Has Default Value: UserLockoutManager

realm

Returns the realm that contains this user lockout manager. Returns null if this security provider is not contained by a realm.

Type: weblogic.management.security.RealmMBean reference

Constraints: Read Only

weblogic.management.security.authorization.AdjudicatorMBean

The SSPI MBean that all Adjudication providers must extend.

The properties of the `weblogic.management.security.authorization.AdjudicatorMBean` entity are as follows:

description

Returns a description of this security provider.

Each security provider's MBean should set the default value of this read-only attribute to a string that describes the provider. In other words, each security provider's MBean hard-wires its description. There are no conventions governing the contents of the description. It should be a human readable string that gives a brief description of the security provider.

Type: string

Constraints: Read Only

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Has Default Value: Provider

realm

Returns the realm that contains this security provider. Returns null if this security provider is not contained by a realm.

Type: weblogic.management.security.RealmMBean reference

Constraints: Read Only

version

Returns this security provider's version.

Each security provider's MBean should set the default value of this read-only attribute to a string that specifies the version of the provider (e.g. 7.3.04). In other words, each security provider's MBean hard-wires its version. There are no conventions governing the contents of the version string.

Type: string

Constraints: Read Only

weblogic.management.security.authorization.AuthorizerMBean

The base MBean for Authorization providers. An Authorization provider for a non-deployable module must extend this MBean directly. An Authorization provider for a deployable module must extend the `DeployableAuthorizer` MBean.

The properties of the `weblogic.management.security.authorization.AuthorizerMBean` entity are as follows:

description

Returns a description of this security provider.

Each security provider's MBean should set the default value of this read-only attribute to a string that describes the provider. In other words, each security provider's MBean hard-wires its description. There are no conventions governing the contents of the description. It should be a human readable string that gives a brief description of the security provider.

Type: string

Constraints: Read Only

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Has Default Value: Provider

realm

Returns the realm that contains this security provider. Returns null if this security provider is not contained by a realm.

Type: `weblogic.management.security.RealmMBean` reference

Constraints: Read Only

version

Returns this security provider's version.

Each security provider's MBean should set the default value of this read-only attribute to a string that specifies the version of the provider (e.g. 7.3.04). In other words, each security provider's MBean hard-wires its version. There are no conventions governing the contents of the version string.

Type: string

Constraints: Read Only

weblogic.management.security.authorization.RoleMapperMBean

The base MBean for Role Mapping providers. A Role Mapping provider for a non-deployable module must extend this MBean directly. A Role Mapping provider for a deployable module must extend the `DeployableRoleMapperMBean` interface.

The properties of the `weblogic.management.security.authorization.RoleMapperMBean` entity are as follows:

description

Returns a description of this security provider.

Each security provider's MBean should set the default value of this read-only attribute to a string that describes the provider. In other words, each security provider's MBean hard-wires its description. There are no conventions governing the contents of the description. It should be a human readable string that gives a brief description of the security provider.

Type: string

Constraints: Read Only

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Has Default Value: Provider

realm

Returns the realm that contains this security provider. Returns null if this security provider is not contained by a realm.

Type: `weblogic.management.security.RealmMBean` reference

Constraints: Read Only

version

Returns this security provider's version.

Each security provider's MBean should set the default value of this read-only attribute to a string that specifies the version of the provider (e.g. 7.3.04). In other words, each security provider's MBean hard-wires its version. There are no conventions governing the contents of the version string.

Type: string

Constraints: Read Only

weblogic.management.security.credentials.CredentialMapperMBean

The SSPI MBean that all Credential Mapping providers must extend. The base MBean for Credential Mapping providers. A Credential Mapping provider for a non-deployable module must extend this MBean directly. An Credential Mapping provider for a deployable module must extend `DeployableCredentialMapper`

The properties of the `weblogic.management.security.credentials.CredentialMapperMBean` entity are as follows:

description

Returns a description of this security provider.

Each security provider's MBean should set the default value of this read-only attribute to a string that describes the provider. In other words, each security provider's MBean hard-wires its description. There are no conventions governing the contents of the description. It should be a human readable string that gives a brief description of the security provider.

Type: string

Constraints: Read Only

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Has Default Value: Provider

realm

Returns the realm that contains this security provider. Returns null if this security provider is not contained by a realm.

Type: weblogic.management.security.RealmMBean reference

Constraints: Read Only

version

Returns this security provider's version.

Each security provider's MBean should set the default value of this read-only attribute to a string that specifies the version of the provider (e.g. 7.3.04). In other words, each security provider's MBean hard-wires its version. There are no conventions governing the contents of the version string.

Type: string

Constraints: Read Only

weblogic.management.security.pk.CertPathProviderMBean

The base MBean for all MBean implementations that manage certification path providers. If your certification path provider provides CertPathBuilder services, then your MBean must extend `weblogic.management.security.pk.CertPathBuilder`. If your certification path provider provides CertPathValidator services, then your MBean must extend `weblogic.management.security.pk.CertPathValidator`.

The properties of the `weblogic.management.security.pk.CertPathProviderMBean` entity are as follows:

description

Returns a description of this security provider.

Each security provider's MBean should set the default value of this read-only attribute to a string that describes the provider. In other words, each security provider's MBean hard-wires its description. There are no conventions governing the contents of the description. It should be a human readable string that gives a brief description of the security provider.

Type: string

Constraints: Read Only

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Has Default Value: Provider

realm

Returns the realm that contains this security provider. Returns null if this security provider is not contained by a realm.

Type: weblogic.management.security.RealmMBean reference

Constraints: Read Only

version

Returns this security provider's version.

Each security provider's MBean should set the default value of this read-only attribute to a string that specifies the version of the provider (e.g. 7.3.04). In other words, each security provider's MBean hard-wires its version. There are no conventions governing the contents of the version string.

Type: string

Constraints: Read Only

