

Oracle Insurance Data Foundation Application Pack

Installation and Configuration Guide

Release 8.1.0.0.0

Sep 2021

ORACLE
Financial Services

Oracle Legal Notices

Copyright Notice

Copyright © 1994, 2023, Oracle and/or its affiliates.

License Restrictions

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

Warranty Disclaimer

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

Restricted Rights Notice

If this is software, software documentation, data (as defined in the Federal Acquisition Regulation), or related documentation that is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, then the following notice is applicable:

U.S. GOVERNMENT END USERS: Oracle programs (including any operating system, integrated software, any programs embedded, installed, or activated on delivered hardware, and modifications of such programs) and Oracle computer documentation or other Oracle data delivered to or accessed by U.S. Government end users are "commercial computer software," "commercial computer software documentation," or "limited rights data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, reproduction, duplication, release, display, disclosure, modification, preparation of derivative works, and/or adaptation of i) Oracle programs (including any operating system, integrated software, any programs embedded, installed, or activated on delivered hardware, and modifications of such programs), ii) Oracle computer documentation and/or iii) other Oracle data, is subject to the rights and limitations specified in the license contained in the applicable contract. The terms governing the U.S. Government's use of Oracle cloud services are defined by the applicable contract for such services. No other rights are granted to the U.S. Government.

Hazardous Applications Notice

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

Trademark Notice

Oracle®, Java, MySQL, and NetSuite are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Inside are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC

International, Inc. AMD, Epyc, and the AMD logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark of The Open Group.

Third-Party Content, Products, and Services Disclaimer

This software or hardware and documentation may provide access to or information about content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services unless otherwise set forth in an applicable agreement between you and Oracle. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services, except as set forth in an applicable agreement between you and Oracle.

Pre-General Availability Draft Label and Publication Date

Pre-General Availability: 2023-MM-DD

Pre-General Availability Draft Documentation Notice

If this document is in public or private pre-General Availability status:

This documentation is in pre-General Availability status and is intended for demonstration and preliminary use only. It may not be specific to the hardware on which you are using the software. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to this documentation and will not be responsible for any loss, costs, or damages incurred due to the use of this documentation.

Oracle Confidential Label

ORACLE CONFIDENTIAL. For authorized use only. Do not distribute to third parties.

Revenue Recognition Notice

If this document is in private pre-General Availability status:

The information contained in this document is for informational sharing purposes only and should be considered in your capacity as a customer advisory board member or pursuant to your pre-General Availability trial agreement only. It is not a commitment to deliver any material, code, or functionality, and should not be relied upon in making purchasing decisions. The development, release, timing, and pricing of any features or functionality described in this document may change and remains at the sole discretion of Oracle.

This document in any form, software or printed matter, contains proprietary information that is the exclusive property of Oracle. Your access to and use of this confidential material is subject to the terms and conditions of your Oracle Master Agreement, Oracle License and Services Agreement, Oracle PartnerNetwork Agreement, Oracle distribution agreement, or other license agreement which has been executed by you and Oracle and with which you agree to comply. This document and information contained herein may not be disclosed, copied, reproduced, or distributed to anyone outside Oracle without prior written consent of Oracle. This document is not part of your license agreement nor can it be incorporated into any contractual agreement with Oracle or its subsidiaries or affiliates.

Documentation Accessibility

For information about Oracle's commitment to accessibility, visit the Oracle Accessibility Program website at <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=docacc>.

Access to Oracle Support

Oracle customer access to and use of Oracle support services will be pursuant to the terms and conditions specified in their Oracle order for the applicable services.

Document Control

Version Number	Revision Date	Change Log
1	29-September-2020	Created the document and redesigned with instructions for the installation and configuration of the OI DF Release 8.1.0.0.0.
2	2-December-2020	Added the section Use Oracle Autonomous Data Warehouse as the Database for OI DF .
3	22-September-2021	Added the section View OFSAA Product Licenses after the Installation of Application Pack .
4	17-December-2021	The OFSAAI Mandatory Patch 33663417 information is added.
5	08-September-2023	Section 4.5 updated for Weblogic configuration.
6	23-November-2023	Java settings updated

Table of Contents

1	Preface	11
1.1	What is New in this Release for OIDF Application Pack	11
1.1.1	<i>New Features</i>	11
1.1.2	<i>Deprecated Features</i>	11
1.1.3	<i>Desupported Features</i>	11
1.2	Audience.....	11
1.3	How this Guide is Organized	12
1.4	Access to Oracle Support	12
1.5	Related Information Sources	13
1.6	Conventions.....	14
1.7	Abbreviations.....	14
Part I	16
2	Introduction	17
2.1	Oracle Financial Services Analytical Applications Infrastructure (OFSAAI)	18
2.1.1	<i>Components of OFSAAI</i>	18
2.1.2	<i>OFSAA Infrastructure High Availability</i>	19
2.1.3	<i>Deployment Topology</i>	20
2.2	About the Oracle Insurance Data Foundation Application Pack.....	20
2.3	OFS AAI Extension Pack	21
2.4	Installation and Upgrade Scenarios	21
3	Complete Installation Checklist.....	24
4	Pre-installation.....	27
4.1	Pre-installation Checklist.....	27
4.2	Hardware and Software Requirements	28
4.2.1	<i>Big Data Settings</i>	28
4.2.2	<i>Third-party Licensing Information</i>	29
4.2.3	<i>Verify the System Environment</i>	29
4.3	Preparing for Installation.....	29
4.3.1	<i>Download the OIDF Application Pack Installer</i>	30

4.3.2	Download the Data Model	30
4.3.3	Download the Mandatory Patches.....	30
4.4	Oracle Database Instance Settings.....	31
4.5	Web Application Server Settings	31
4.6	Web Server Settings	32
4.7	Create the Installation, Download, and Metadata Directories	32
4.8	Configure the OS File System Settings and Environment Settings in the .profile File	33
4.8.1	Configure Operating System and File System Settings.....	33
4.8.2	Configure the Environment Settings.....	34
5	Installation	39
5.1	Installation Checklist	39
5.2	Extract the OI DF Application Pack Software	40
5.3	Install Pre-installation Patches.....	41
5.4	Configure the OI DF_PACK.xml File.....	41
5.5	Configure the Schema Creator Utility.....	43
5.5.1	Prerequisites	44
5.5.2	Configure the Schema Creator Utility for RDBMS Installation.....	44
5.5.3	Configure the Schema Creator Utility for HDFS Schema	55
5.6	Configure the OI SAAI_InstallConfig.xml File.....	83
5.6.1	Set Up the SFTP Private Key.....	88
5.7	Configure the Silent.props File.....	89
5.7.1	Silent.template for RDBMS	89
5.7.2	Silent.BIGDATA.template for Stage and Results on Hive.....	92
5.7.3	Silent_Hybrid.template for Stage on Hive and Results on RDBMS	95
5.8	Backup the Configuration Files.....	98
5.9	Execute the Schema Creator Utility.....	98
5.9.1	Execute the Schema Creator Utility in Offline Mode	98
5.9.2	Execute the Schema Creator Utility in Online Mode.....	100
5.9.3	Execute the Schema Creator Utility in TCPS Mode	103
5.9.4	Execute the Schema Creator Utility when Installing the Subsequent Applications Pack.....	105
5.10	Verify the Schema Creator Log Files.....	109
5.11	Install the OI DF Application Pack.....	109
5.12	Install a New OI DF Application Pack on an Existing OI SAA Instance.....	117

6 Use Oracle Autonomous Data Warehouse as the Database for OIDF 118

6.1	Oracle Autonomous Data Warehouse	118
6.2	Deployment Architecture for ADW Certification	118
6.3	Download Client Credentials (Wallet)	119
6.4	Using a JDBC URL Connection String with JDBC Thin Driver	120
6.5	Installation Notes Specific to ADW	120
6.5.1	<i>Hardware and Software Requirements</i>	120
6.5.2	<i>Configure the Schema Creator Utility</i>	120
6.5.3	<i>OFSAAI Installation Notes Specific to ADW</i>	121
6.5.4	<i>OIDF Installation Notes Specific to ADW</i>	122
6.5.5	<i>Installation of OIDF on ADW</i>	123
6.6	Loading Data into OIDF	123
6.6.1	<i>Importing Data into OIDF on ADW Using the OCI Object Storage</i>	123
6.6.2	<i>Batch Execution in OIDF</i>	123
6.7	Additional Note	124

7 Post-installation..... 125

7.1	OFSAA Infrastructure Patch Installation	125
7.2	Verify the Log File Information	126
7.3	Stop the Infrastructure Services	126
7.4	Create and Deploy the EAR/WAR Files	126
7.5	EAR/WAR File - Build Once and Deploy Across Multiple OFSAA Instances	127
7.6	Start the Infrastructure Services	127
7.7	Access the OFSAA Application	127
7.8	OFSAA Landing Page	127
7.9	View OFSAA Product Licenses after the Installation of Application Pack	127
7.10	Configure the excludeURLList.cfg File	127
7.11	Configure the Big Data Processing	127
7.11.1	<i>Copy the Jar Files to the OFSAA Installation Directory</i>	128
7.11.2	<i>Copy the KEYTAB and KRB5 Files in OFSAAI</i>	129
7.11.3	<i>Configure the Apache Livy Interface</i>	129
7.11.4	<i>Verify the External Tables Utility of Oracle</i>	132
7.12	Configuration to Enable the Restatement Support	133
7.13	Create the Application Users	133

7.14	Map the Application User(s) to User Group	134
7.15	Change the ICC Batch Ownership	134
7.16	Add TNS entries in the TNSNAMES.ORA File	135
7.17	Configure Transparent Data Encryption (TDE) and Data Redaction in OFSAA	135
7.18	Implement Data Protection in OFSAA	135
Part II		136
8 Upgrade.....		137
8.1	Upgrade Scenarios	137
8.2	Perform the Data Model Upload Outside of the Installer	138
8.2.1	<i>Execute the ModelUpgrade.sh File for the Prescripts</i>	<i>138</i>
8.3	Prepare for Upgrade.....	139
8.3.1	<i>Download the OIDF Application Pack Installer and Data Model</i>	<i>139</i>
8.3.2	<i>Prepare the Environment for Upgrade</i>	<i>141</i>
8.4	Upgrade from Oracle Insurance Data Foundation Application Pack Release v8.0.x on AIX or Solaris x86 Operating System.....	141
8.5	Upgrade from OIDF v8.0.5.0.0 or Earlier Versions to OIDF v8.0.6.0.0 or a Higher Version	141
8.6	Upgrade from OIDF v8.0.6.0.0 or a Higher Version to OIDF v8.1.0.0.0	142
8.6.1	<i>Clone Your Existing Environment.....</i>	<i>142</i>
8.6.2	<i>Extract the Software</i>	<i>143</i>
8.6.3	<i>Update the OFS_OIDF_PACK.xml File.....</i>	<i>144</i>
8.6.4	<i>Update the Silent.props File.....</i>	<i>145</i>
8.6.5	<i>Trigger the Installation</i>	<i>147</i>
8.6.6	<i>Verify the Log File Information</i>	<i>151</i>
8.6.7	<i>Post-installation Steps.....</i>	<i>151</i>
8.6.8	<i>Additional Configuration.....</i>	<i>152</i>
8.7	Upgrade OIDF Application Pack to v8.1.0.0.0 on an Existing OFSAA Instance.....	152
8.7.1	<i>Extract the Software</i>	<i>152</i>
8.7.2	<i>Update the OFS_OIDF_PACK.xml File.....</i>	<i>153</i>
8.7.3	<i>Update the Silent.props File.....</i>	<i>154</i>
8.7.4	<i>Execute the Schema Creator Utility Only for the OIDF Application Pack</i>	<i>157</i>
8.7.5	<i>Trigger the Installation</i>	<i>158</i>
8.7.6	<i>Verify the Log File Information</i>	<i>162</i>

8.7.7	<i>Post-installation Steps</i>	163
8.7.8	<i>Additional Configuration</i>	163
Part III	164
9	Additional Configuration	165
10	Frequently Asked Questions (FAQs) and Error Dictionary	166

1 Preface

This section provides information about the Oracle Insurance Data Foundation (OIDF) Application Pack Installation and Configuration Guide.

Topics:

- [What is New in this Release for OIDF Application Pack](#)
- [Audience](#)
- [How this Guide is Organized](#)
- [Access to Oracle Support](#)
- [Related Information Sources](#)
- [Conventions](#)
- [Abbreviations](#)

1.1 What is New in this Release for OIDF Application Pack

This section lists new features and changes in the Oracle Insurance Data Foundation (OIDF) Application Pack.

1.1.1 New Features

This section lists the new features described in this manual.

- All Runs are configured in the Process Modeling Framework (PMF) for the RDBMS mode of installation.
- Introduced Restatement Support feature that enables backdated execution for any Start Date or End Date explicitly for T2T metadata.
- Introduction of the ModelUpgrade utility to restore the metadata of the custom model.
- Facilitated loading of the Seeded data using the SQL*Loader utility.

1.1.2 Deprecated Features

There are no deprecated features in this release.

1.1.3 Desupported Features

There are no desupported features in this release.

1.2 Audience

The Oracle Insurance Data Foundation (OIDF) Application Pack Installation and Configuration Guide is intended for Administrators, Business User, Strategists, and Data Analyst, who are responsible for installing and maintaining the application pack components.

- OIDF Application Pack components
- OFSAA Architecture
- UNIX Commands
- Database Concepts
- Web server/Web application server

1.3 How this Guide is Organized

The Installation Guide is organized into the following sections:

- **Introduction:** This section contains an introduction to the OFSAAI and its components, an introduction to the OIDF Application Pack, and installation scenarios that the current release supports.
- **Complete Installation Checklist:** This section lists the procedures required for a complete Oracle Insurance Data Foundation Application Pack installation.
- **Pre-installation:** This section contains the pre-installation requirements for a successful installation and functioning of the Oracle Insurance Data Foundation Application Pack. This section recommends the hardware and base software environment, and the preparatory procedures required before triggering the installation.
- **Installation:** This section details the steps to follow during the Oracle Insurance Data Foundation Application Pack installation.
- **Use Oracle Autonomous Data Warehouse as the Database for OIDF:** This section provides information about using the Oracle Autonomous Data Warehouse as the Database for the Oracle Insurance Data Foundation Application Pack installation and operation.
- **Post-installation:** This section details the steps that are required to be performed after a successful installation of the Oracle Insurance Data Foundation Application Pack.
- **Upgrade:** This section details the steps to follow before, during, and after the Oracle Insurance Data Foundation Application Pack upgrade installation, and different upgrade scenarios.
- **Additional Configuration:** This section contains the additional configuration after a successful installation of the Oracle Insurance Data Foundation Application Pack.
- **Frequently Asked Questions (FAQs) and Error Dictionary:** This section contains a reference to the FAQs and installation error-related information.

1.4 Access to Oracle Support

Oracle customers have access to electronic support through My Oracle Support. For more information, visit <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=info> or visit <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=trs> if you are hearing impaired.

1.5 Related Information Sources

Oracle strives to keep this and all other related documents updated regularly. Visit the [OHC Documentation Library](#) and [My Oracle Support](#) web pages to download the latest document version available. The list of related documents is as follows:

- [OHC Documentation Library](#) for the ODF Application Pack Release 8.1.x.x.x product documents:
 - [Oracle Insurance Data Foundation Application Pack User Guide Release 8.1.0.0.0](#)
 - [Oracle Insurance Data Foundation Application Pack Release Notes 8.1.0.0.0](#)
 - [Oracle Insurance Data Foundation Application Pack Upgrade Guide Release 8.1.0.0.0](#)
- [OHC Documentation Library](#) for the ODF Application Pack Release 8.1.x.x.x other documents:
 - [Oracle Insurance Data Foundation Application Pack Data Protection Implementation Guide Release 8.1.x](#)
 - [Oracle Financial Services Analytical Applications \(OFSAA\) Data Model Extension Guidelines Document Release 8.1.x](#)
 - [Oracle Financial Services Analytical Applications \(OFSAA\) Data Model Naming Standards Guide Release 8.1.x](#)
 - [Oracle Financial Services Analytical Applications \(OFSAA\) Data Model Document Generation Release 8.1.x](#)
 - [Oracle Insurance Data Foundation Application Pack Security Guide Release 8.1.x](#)
 - [Oracle Insurance Data Foundation Application Pack Cloning Reference Guide Release 8.1.x](#)
 - [Oracle Insurance Data Foundation Application Pack Cloning Reference Guide Release 8.0.x](#)
- [My Oracle Support](#) for the ODF Application Pack Release 8.1.x.x.x technical documents:
 - *Run Chart*
 - *Changelog*
 - *SCD Metadata*
 - *T2T Metadata*
- [Oracle Financial Services Analytical Applications \(OFSAA\) Technology Matrix Release 8.1.0.0.0](#)
- [OHC Documentation Library](#) contains the following OFS AAI Application Pack Release 8.1.0.0.0 product documents:
 - [Oracle Financial Services Advanced Analytical Applications Infrastructure Installation Guide Release 8.1.0.0.0](#)
 - [Oracle Financial Services Advanced Analytical Applications Infrastructure User Guide Release 8.1.0.0.0](#)
 - [Oracle Financial Services Advanced Analytical Applications Infrastructure Environment Check Utility Guide Release 8.1.x](#)
 - [Oracle Financial Services Advanced Analytical Applications Infrastructure Administration and Configuration Guide Release 8.1.x](#)

- [Oracle Financial Services Analytical Applications Infrastructure Process Modelling Framework Orchestration Guide Release 8.1.0.0.0](#)
- [Oracle Financial Services Analytical Applications \(OFSAA\) Metadata Browser User Guide Release 8.1.0.0.0](#)
- [OHC Documentation Library](#) contains the following OFSAA Release 8.1.x generic documents:
 - [Oracle Financial Services Analytical Applications Infrastructure Security Guide Release 8.1.x](#)
 - [Oracle Financial Services Analytical Applications Infrastructure Cloning Reference Guide Release 8.1.x](#)
- [Oracle Financial Services Analytical Applications \(OFSAA\) Licensing Information User Manual Release 8.1.0.0.0](#)

1.6 Conventions

The following text conventions are used in this document.

Table 1: Document Conventions

Convention	Meaning
boldface	Boldface type indicates graphical user interface elements associated with an action or terms defined in text or the glossary.
<i>Italic</i>	Italic type indicates book titles, emphasis, or placeholder variables for which you supply particular values.
Monospace	Monospace type indicates commands within a paragraph, URLs, code in examples, file names, text that appears on the screen, or text that you enter.
Hyperlink	Hyperlink type indicates the links to external websites, internal document links to sections.

1.7 Abbreviations

The following table lists the abbreviations used in this document.

Table 2: Abbreviations

Conventions	Description
AIX	Advanced Interactive executive
CDH	Cloudera Distribution Hadoop
DEFQ	Data Entry Forms and Queries
DML	Data Manipulation Language
EAR	Enterprise Archive
EJB	Enterprise JavaBean
ERM	Enterprise Resource Management

Conventions	Description
FTP	File Transfer Protocol
GUI	Graphical User Interface
HTTPS	Hypertext Transfer Protocol Secure
J2C	J2EE Connector
J2EE	Java 2 Enterprise Edition
JDBC	Java Database Connectivity
JDK	Java Development Kit
JNDI	Java Naming and Directory Interface
JRE	Java Runtime Environment
JVM	Java Virtual Machine
LDAP	Lightweight Directory Access Protocol
LHS	Left Hand Side
MFA	Multi-Factor Authentication
MOS	My Oracle Support
OFS	Oracle Financial Services
OFSAAI	Oracle Financial Services Analytical Application Infrastructure
OIDF	Oracle Insurance Data Foundation
OHC	Oracle Help Center
OLAP	On-Line Analytical Processing
OS	Operating System
RAM	Random Access Memory
RDMS	Relational Database Management System
SFTP	Secure File Transfer Protocol
SID	System Identifier
SSL	Secure Sockets Layer
TDE	Transparent Data Encryption
TNS	Transparent Network Substrate
URL	Uniform Resource Locator
VM	Virtual Machine
Web Archive	WAR
XML	Extensible Markup Language

Part I

Topics:


- [Pre-installation](#)
- [Installation](#)
- [Use Oracle Autonomous Data Warehouse as the Database for OI DF](#)
- [Post-installation](#)

2 Introduction

In today's turbulent markets, financial institutions require a better understanding of their risk-return, while strengthening competitive advantage and enhancing long-term customer value. Oracle Financial Services Analytical Applications (OFSAA) enable financial institutions to measure and meet risk-adjusted performance objectives, cultivate a risk management culture through transparency, lower the costs of compliance and regulation, and improve insight into customer behavior.

OFSAA uses industry-leading analytical methods, shared data models, and applications architecture to enable integrated risk management, performance management, customer insight, and compliance management. OFSAA actively incorporates risk into decision making, enables to achieve a consistent view of performance, promote a transparent risk management culture, and provide pervasive intelligence. OFSAA delivers a comprehensive, integrated suite of financial services analytical applications for both banking and insurance domains. The following figure depicts the various application packs that are available across the OFSAA Banking and Insurance domains.

Figure 1: Application Packs of OFSAA



Topics:

- [Oracle Financial Services Analytical Applications Infrastructure \(OFSAAI\)](#)
- [About the Oracle Insurance Data Foundation Application Pack](#)
- [OFS AAI Extension Pack](#)
- [Installation and Upgrade Scenarios](#)

2.1 Oracle Financial Services Analytical Applications Infrastructure (OFSAAI)

Oracle Financial Services Analytical Applications Infrastructure (OFSAAI) powers the Oracle Financial Services Analytical Applications family of products to perform the processing, categorizing, selection, and manipulation of data and information required to analyze, understand and report on specific performance, risk, compliance, and customer insight issues by providing a strong foundation for the entire family of Oracle Financial Services Analytical Applications across the domains of Risk, Performance, Compliance and Customer Insight.


2.1.1 Components of OFSAAI

The OFSAA Infrastructure includes frameworks that operate on and with the Oracle Financial Services Analytical Applications Data Model and forms the array of components within the Infrastructure.

The OFSAA Infrastructure components or frameworks are installed as two layers; primarily, the metadata server and Infrastructure services run on one layer, while the UI and presentation logic runs on the other. The UI and presentation layer is deployed on any of the supported J2EE Servers.

The following figure depicts the various frameworks and capabilities that make up the OFSAA Infrastructure.

Figure 2: Components of OFSAAI




2.1.2 OFSAA Infrastructure High Availability

The current release of the OFSAA Infrastructure supports only the *Single Instance* installation for the Infrastructure components. However, the High Availability (HA) for the Database Server and/ or the Web application server clustering and deployment is supported in this release.

This release supports the Active-Passive model of implementation for OFSAAI components. For more information, see the [Oracle Financial Services Analytical Applications \(OFSAA\) Configuration for High Availability Best Practices Guide Release 8.1.x](#).

2.1.3 Deployment Topology

Figure 3: The logical architecture implemented in the OFSAAAI Application Pack



2.2 About the Oracle Insurance Data Foundation Application Pack

The Oracle Insurance Data Foundation (OIDF) is an analytical data warehouse platform for the Financial Services industry. OIDF combines an industry data model for Financial Services along with a set of management and infrastructure tools that allows Financial Services Institutions to develop, deploy, and operate analytical solutions spanning key functional areas in Financial Services, including:

- Health Insurance
- Property Casualty
- Life Insurance

OIDF is a comprehensive data management platform that helps institutions to manage the analytical data life cycle from sourcing to reporting as a consistent platform and toolset.

The application pack includes a logical data model, a physical data model, and supporting scripts.

OIDF Application Pack includes the following applications:

- **Financial Services Analytical Applications Infrastructure:** This application powers the Oracle Financial Services Analytical Applications family of products to perform the processing, categorizing, selection and manipulation of data and information required to analyze, understand and report on specific performance, risk, compliance and customer insight issues by providing a strong foundation for the entire family of Oracle Financial Services Analytical Applications across the domains of Risk, Performance, Compliance and Customer Insight.

- **Financial Services Big Data Processing:** This option includes, into OI DF, the capability to process data stored in Hadoop Distributed File System (HDFS). With the Big Data Processing (BDP) add-on option, all core data management frameworks within OFSAA such as Data Management Framework (T2T or F2T), Data Quality Framework, and Rules framework are enhanced to operate on both Oracle RDBMS data sources as well as Apache Hive data sources. An OFSAA Run definition can contain tasks that transform data held in the Hive. OFSAA applications that use these frameworks for expressing application logic automatically gain the ability to manage data held in the Hive. The OFSAA platform leverages HiveQL and Map Reduce in order to process data directly in the Hadoop cluster without having to stage data in a relational database.

The application pack includes a logical data model, a physical data model, and supporting scripts.

NOTE The schema or domain for OI DF is referred to as OI DF.

2.3 OFS AAI Extension Pack

The Oracle Financial Services Analytical Applications Infrastructure Extension (OFS AAIE) Pack adds a set of new advanced features for the 8.1.0.0.0 Release across OFSAA applications. This pack can be installed on an OFSAA instance containing one or more OFSAA application packs.

The Oracle Financial Services Analytical Applications Infrastructure Extension Pack includes the following advanced features and functionalities:

- Distributed Processing Capabilities
- Analytic Pipeline and Process models
- Attribution Analysis
- Content Management Interoperability Services

NOTE The pack is enabled by the procurement of an additional license. For more information, see the *OFS AAIE Release Notes* and *Installation Guide* on the [OHC Documentation Library](#).

2.4 Installation and Upgrade Scenarios

The OI DF Application Pack Release v8.1.0.0.0 supports various installation and upgrade scenarios. A high-level overview of the possible scenarios is provided in the following table. The detailed procedural steps are provided in the subsequent sections.

Table 3: OIDF Release 8.1.0.0.0 Installation and Upgrade Scenarios

Scenario	Installation and Upgrade Instructions
<p>New Installation</p> <p>Installing Release 8.1.0.0.0 application pack for the first time (new installation).</p>	<ol style="list-style-type: none"> 1. Prepare for the Installation. 2. Run Schema Creator Utility. 3. Install the OIDF Application Pack.
<p>Install a new OIDF Application Pack v8.1.0.0.0 on an Existing OFSAA Instance</p> <p>In this scenario, you have already installed an application pack versioned v8.1.0.0.0 and now you need to install the OIDF application pack versioned v8.1.0.0.0.</p> <p>Example: OFS ALM Pack is already installed and now you need to install OIDF Pack.</p>	<ol style="list-style-type: none"> 1. Configure the <code>OFS_OIDF_PACK.xml</code> file for the newly licensed OIDF Application Pack. 2. Configure the <code>Silent.props</code> file of the newly licensed pack. 3. Run the schema creator utility ONLY for the newly licensed OIDF Application Pack. 4. Trigger the installation.
<p>Upgrade from Oracle Insurance Data Foundation Application Pack Release v8.0.x on AIX or Solaris x86 Operating System</p>	<p>Release v8.1.0.0.0 of Oracle Insurance Data Foundation Application Pack is not certified for AIX and Solaris x86 Operating Systems. If you are currently running OFSAA v8.0.x on AIX or Solaris x86 Operating Systems and plan to upgrade to Release v8.1.0.0.0, then you must migrate from AIX or Solaris x86 to Linux or Solaris SPARC. See the MOS Doc ID 2700084.1 for details.</p>
<p>Upgrade from OIDF v8.0.5.0.0 or Earlier Versions to OIDF v8.0.6.0.0 or a Higher Version</p> <p>In this scenario, you are upgrading the OIDF application pack from the Release v8.0.5.0.0 or an earlier version to the Release v8.0.6.0.0 or a higher version. Then upgrade to OIDF v8.1.0.0.0.</p> <p>Example: You are using the OIDF v8.0.5.0.0 release and now want to upgrade to the OIDF v8.1.0.0.0.</p>	<ol style="list-style-type: none"> 1. Upgrade your current OIDF version to the OIDF v8.0.6.0.0 or later versions. 2. Clone your existing environment to the OFSAA Technology Matrix v8.1.0.0.0. 3. Upgrade from OIDF v8.0.6.0.0 or a later version to OIDF v8.1.0.0.0. 4. Run the Environment Check Utility tool and ensure that the hardware and software are installed as per the OFSAA Technology Matrix v8.1.0.0.0. 5. Update the <code>OFS_OIDF_PACK.xml</code> file to enable ONLY the existing installed applications. 6. Update the <code>Silent.props</code> file present in the OIDF v8.1.0.0.0 installer pack. 7. Trigger the installation.
<p>Upgrade from OIDF v8.0.6.0.0 or a Higher Version to OIDF v8.1.0.0.0</p> <p>In this scenario, you are upgrading the OIDF Application Pack from Release v8.0.7.0.0 or higher versions to Release v8.1.0.0.0.</p>	<ol style="list-style-type: none"> 1. Perform the Data Model upload outside of the installer (Execute the <code>ModelUpgrade.sh</code> file for the Prescripts to backup and delete the data, and then to backup and delete the metadata). 2. Clone your existing environment to the OFSAA Technology Matrix v8.1.0.0.0. 3. Run the Environment Check Utility tool and ensure that the hardware and software are installed as per the OFSAA Technology Matrix v8.1.0.0.0. 4. Update the <code>OFS_OIDF_PACK.xml</code> file to enable ONLY the existing installed applications. 5. Update the <code>Silent.props</code> file present in the OIDF v8.1.0.0.0 installer pack. 6. Trigger the installation.

Scenario	Installation and Upgrade Instructions
	<ol style="list-style-type: none"> 7. Execute the <code>ModelUpgrade.sh</code> file for the Postscripts to restore the data and then metadata.
<p>Upgrade OIDF Application Pack to v8.1.0.0.0 on an Existing OFSAA Instance</p> <p>In this scenario, an Application Pack of v8.1.0.0.0 is already installed and now you need to upgrade OIDF Application Pack from v.8.0.6.0.0 or a later version to v8.1.0.0.0.</p> <p>Example: OFS ALM v8.1.0.0.0 Application Pack is already installed and now you need to install the OIDF Application Pack.</p>	<ol style="list-style-type: none"> 1. Perform the Data Model upload outside of the installer (Execute the <code>ModelUpgrade.sh</code> file for the Prescripts to backup and delete the data, and then to backup and delete the metadata). 2. Update the <code>OFS_OIDF_PACK.xml</code> file of the OIDF Application Pack. 3. Update the <code>Silent.props</code> file of the OIDF Application Pack. 4. Run the schema creator utility ONLY for the OIDF Application Pack. 5. Trigger the installation. 6. Execute the <code>ModelUpgrade.sh</code> file for the Postscripts to restore the data and then metadata.

3 Complete Installation Checklist

To complete the installation process, you must perform the following steps listed in the Complete Installation Checklist table. Use this checklist to verify whether these steps are completed or not.

Table 4: Pre-installation Checklist

Sl. No.	Activity
1	Install all the prerequisite hardware and software as per the OFSAA Technology Matrix .
2	Install and configure the prerequisite hardware and software for the Big Data (Only for the Big Data installation) as per the OFSAA Technology Matrix .
3	Verify the System Environment using the Environment Check Utility.
4	Download the ODF Application Pack installer kit.
5	Download the Data Model (optional).
6	Download the mandatory patches.
7	Configure the Database Instance settings.
8	Install and configure the web application server.
9	Configure the HTTP settings on the webserver.
10	Create the Installation, Download, and Metadata Repository Directories: <ul style="list-style-type: none"> • Installation directory • Temporary directory • Staging Area/Metadata Repository • Download directory
11	Configure the following Operating System and File System settings: <ul style="list-style-type: none"> • File Descriptor • Total number of processes • Port(s) • <code>.profile</code> file permissions • Set Up the SFTP Private Key
12	Update the following Environment Settings as required for the installation in the <code>.profile</code> file: <ul style="list-style-type: none"> • Java Settings • Oracle Database Server and Client Settings • Add TNS entries in the <code>tnsnames.ora</code> file • Oracle Essbase Settings • Time Zone Settings

Table 5: Installation Checklist

Sl. No.	Activity
1	Extract the ODF Application Pack software.

Sl. No.	Activity
2	Configure the OFS_OIDF_PACK.xml file.
3	Configure the OFS_OIDF_SCHEMA_IN.xml file.
4	Configure the OFS_OIDF_SCHEMA_BIGDATA_IN.xml file for Stage and Results on Hive or Stage on Hive and Results on RDBMS (Only for the Big Data installation).
5	Configure the OFSAAI_InstallConfig.xml file.
6	Configure the Silent.props file.
7	Backup the configuration files.
8	Execute the Schema Creator Utility in Offline , Online , or TCPS modes.
9	Verify the Schema Creator log files.
10	Trigger the OIDF Application Pack installation.

Table 6: Post-installation Checklist

Sl. No.	Activity
1	Verify the installation logs.
2	Stop the OFSAA Infrastructure services.
3	Create and deploy EAR/WAR files. (Alternative) EAR/WAR file - Build Once and Deploy Across Multiple OFSAA Instances.
4	Start the OFSAA Infrastructure services.
5	Configure the web browser (Internet Explorer) settings.
6	Access the OFSAA application.
7	Explore the OFSAA landing page.
8	Configure the excludeURLList.cfg file.
9	Configure Big Data Processing.
10	Create Application Users.
11	Map the Application User(s) to User Groups.
12	Change the ICC batch ownership.
13	Add TNS entries in the tnsnames.ora file.
14	Set TDE and Data Redaction in OFSAAI.
15	Implement Data Protection in OFSAA.

Table 7: Additional Configuration Checklist

Sl. No.	Activity
1	<u>Configure</u> the webserver.
2	<u>Configure</u> the Resource Reference in web application servers.
3	<u>Configure</u> the Work Manager in the web application servers.
4	<u>Add</u> the FTP/SFTP configuration for file transfer.
5	<u>Configure</u> the Process Modeling Framework.
6	<u>Configure</u> the Infrastructure Server Memory.
7	<u>Change</u> IP/Hostname, Ports, Deployed Paths of the OFSAA Instance.
8	<u>Execute</u> the OFSAAI setup information fetching tool.
9	<u>Execute</u> the Encryption Changer.
10	<u>Configure</u> the Infrastructure LDAP.
11	<u>Configure and deploy</u> the OFSAAI web services.
12	<u>Enable</u> the parallel execution of DML statements.
13	<u>Configure</u> the message details in the Forms Designer.
14	<u>Clear</u> the application cache.
15	<u>Configure</u> the password changes.
16	<u>Configure</u> the Java Virtual Machine.
17	<u>Configure</u> the internal service (Document Upload/Download).
18	<u>Migrate</u> the Excel upload functionality.
19	<u>Remove</u> the OFSAA Infrastructure.

4 Pre-installation

This section contains the pre-installation requirements for a successful installation and functioning of the Oracle Insurance Data Foundation Application Pack.

Topics:

- [Pre-installation Checklist](#)
- [Hardware and Software Requirements](#)
- [Preparing for Installation](#)
- [Oracle Database Instance Settings](#)
- [Web Application Server Settings](#)
- [Web Server Settings](#)
- [Create the Installation, Download, and Metadata Directories](#)
- [Configure the OS File System Settings and Environment Settings in the .profile File](#)

4.1 Pre-installation Checklist

To complete the pre-installation process, you must perform the following steps listed in the Pre-installation Checklist table. Use this checklist to verify whether these steps are completed or not.

Table 8: Pre-installation Checklist

Sl. No.	Activity
1	Install all the prerequisite hardware and software as per the OFSAA Technology Matrix .
2	Install and configure the prerequisite hardware and software for the Big Data (Only for the Big Data installation) as per the OFSAA Technology Matrix .
3	Verify the System Environment using the Environment Check Utility.
4	Download the ODF Application Pack installer kit.
5	Download the Data Model (optional).
6	Download the mandatory patches.
7	Configure the Database Instance settings.
8	Install and configure the web application server.
9	Configure the HTTP settings on the webserver.
10	Create the Installation, Download, and Metadata Repository Directories: <ul style="list-style-type: none"> • Installation directory • Temporary directory • Staging Area/Metadata Repository • Download directory
11	Configure the following Operating System and File System settings: <ul style="list-style-type: none"> • File Descriptor

Sl. No.	Activity
	<ul style="list-style-type: none"> Total number of processes Port(s) .profile file permissions Set Up the SFTP Private Key
12	<p>Update the following Environment Settings as required for the installation in the .profile file:</p> <ul style="list-style-type: none"> Java Settings Oracle Database Server and Client Settings Add TNS entries in the tnsnames.ora file Oracle Essbase Settings Time Zone Settings

4.2 Hardware and Software Requirements

This section describes the various Operating System, databases, web servers, and web application server versions, and other variant details on which this release of the Oracle Insurance Data Foundation Application Pack has qualified.

Topics:

- [Big Data Settings](#)
- [Third-party Licensing Information](#)
- [Verify the System Environment](#)

See the [OFSAA Technology Matrix](#) document for the hardware and software required for the Oracle Insurance Data Foundation Application Pack Release 8.1.0.0.0.

Table 9: Recommended Software Combination

Operating System	Database	Web Application Server	Web Server
Oracle Linux	Oracle Database	Oracle WebLogic Server/Apache Tomcat Server	Oracle HTTP Server/Apache HTTP Server
Oracle Solaris	Oracle Database	Oracle WebLogic Server/Apache Tomcat Server	Oracle HTTP Server/Apache HTTP Server

4.2.1 Big Data Settings

This is an optional section and required only if you intend to install the OFSAA Big Data Processing. See the [Oracle Financial Services Analytical Applications 8.1.0.0.0 Technology Matrix](#) document for the software required for the Big Data software Hadoop Distribution on the Oracle Insurance Data Foundation Application Pack Release 8.1.0.0.0.

- Install CDH. For installation information, see the Cloudera documentation at <https://docs.cloudera.com/>.

- Install the Apache Livy (Incubating) web service:
 - a. Go to <https://incubator.apache.org/clutch/livy.html>.
 - b. Download the livy-0.4.0-incubating zip files.
 - c. Install livy-0.4.0-incubating for Spark 2. For installation information, see the documentation at https://docs.cloudera.com/HDPDocuments/HDP2/HDP-2.6.5/bk_command-line-installation/content/install_livy.html.

4.2.2 Third-party Licensing Information

For details on the third-party software tools used, see the [Oracle Financial Services Analytical Applications \(OFSA\) Licensing Information User Manual Release 8.1.0.0.0](#).

4.2.3 Verify the System Environment

To verify your system environment meets the minimum requirements for the installation, a Pre-Install Check utility is available within the Install Kit archive file. This utility can also be obtained separately by contacting [Oracle Support Services](#).

Though the system environment verification is an integral and automated part of the installation of this software product, Oracle strongly recommends running this utility before beginning the installation as part of your organization's "Installation Readiness Verification Process".

For more details on download and usage of this utility, see the [Oracle Financial Services Advanced Analytical Applications Infrastructure Environment Check Utility Guide Release 8.1.x](#).

4.3 Preparing for Installation

This section details the preparatory procedures that must be followed before triggering the installation.

Topics:


- [Download the ODF Application Pack Installer](#)
- [Download the Data Model](#)
- [Download the Mandatory Patches](#)

4.3.1 Download the OIDF Application Pack Installer

To download the OIDF Application Pack installer Release v8.1.0.0.0, follow these steps:

1. Log in to the [Oracle Software Delivery Cloud](#) with a valid Oracle account.

Figure 4: Oracle Software Delivery Cloud Login Page



2. Search for the full product name **Oracle Insurance Data Foundation** and download the installer archive for this release version.
3. Copy the installer archive into the download directory (in Binary mode) in the setup identified for the OIDF Application Pack installation.

4.3.2 Download the Data Model

To download the OIDF OOB v8.1.0.0.0 Data Model, follow these steps:

NOTE This is an optional section, which is applicable if you are performing the customized model upload.

1. Log in to the [My Oracle Support \(MOS\)](#) with a valid Oracle account.
2. In the **Patches & Updates** tab, search for the OIDF Data Model installer patch **31924513** and download the patch. See the Readme available with the patch for further instructions on downloading the patch and extracting the erwin files.

4.3.3 Download the Mandatory Patches

The following table includes information about the mandatory patches that must be applied.

Table 10: Mandatory Patches

One-Off Patch	Description
31605076	Access to features owing to the additional license functionality that gets installed through the OFS AAI Extension Pack.
31545589	For pack-on-pack installation on a new atomic schema.
33663417	Download this mandatory OFSAAI One-Off Patch. See the ATTENTION below.

ATTENTION

For the Mandatory Patch ID **33663417**:

On the 10th of December 2021, Oracle released the Security Alert CVE-2021-44228 in response to the disclosure of a new vulnerability affecting Apache Log4J prior to version 2.15. The application of the **33663417** Mandatory Patch fixes the issue.

For details, see the My Oracle Support Doc ID [2827801.1](#).

Ensure that you reapply the OFSAAI Mandatory Patch **33663417** whenever you Install or Upgrade the Application, or whenever you apply an Incremental Patch.

NOTE

Ensure that the tablespace or tablespaces used for the database user or users are set to AUTOEXTEND ON.

4.4 Oracle Database Instance Settings

Ensure that the following database instance settings are configured:

- NLS_CHARACTERSET to AL32UTF8
- NLS_LENGTH_SEMANTICS to BYTE
- OPEN_CURSORS limit to greater than 1000

4.5 Web Application Server Settings

Ensure that the web application server is installed and the profile (when using WebSphere) or domain (when using WebLogic) is created.

Table 11: Web Application Server Settings

Description	Example Value
WebSphere/ WebLogic/ Tomcat	<p>Web Application Server should be installed and the profile/domain created.</p> <p>You will be prompted to enter the WebSphere Profile path, the WebLogic Domain path, or the Tomcat Deployment path during OFSAAI installation.</p> <p>NOTE: See the Configure the Web Server section for WebSphere Profile and WebLogic Domain creation. Before proceeding with the domain creation, download and install the required one-off Patch or the latest WLS PSU for 14.1.1 from My oracle Support (Doc ID 2806740.2). For more information, refer to <i>Configure WebLogic for Application Deployment</i> in AAI installation guide.</p>

4.6 Web Server Settings

This is an optional requirement. If you have installed an HTTP Server, then configure the appropriate HTTP server settings:

Table 12: Web Server Settings

Description	Example Value
Apache HTTP Server/ Oracle HTTP Server/ IBM HTTP Server	<p>Configure the HTTP Server and note down the IP/ Hostname and Port details as you will be prompted to enter these details during installation.</p> <p>NOTE: See the Configure the Web Server section for the Web Server configuration.</p>

4.7 Create the Installation, Download, and Metadata Directories

To install the ODF Application Pack, create the following directories:

- **OIDF Download Directory (Optional):** Create a download directory and copy the ODF Application Pack Installer File (archive). This is the directory where the downloaded installer or patches can be copied. Assign 755 permission to this directory.
- **OFSAA Installation Directory (Mandatory):** Create an installation directory where the product binaries are installed. Assign 755 user permission to the installation directory. FIC_HOME variable to be set in the `.profile` pointing to this OFSAA Installation Directory.
- **OFSAA Staging or Metadata Repository Directory (Mandatory):** A directory to hold the application metadata artifacts and additionally act as the staging area for the flat files. This directory is also referred to as "FTPSHARE". Create a Staging or Metadata Repository Directory to copy data files, save data extracts, and so on.

The directory must exist on the same system as the OFSAA Installation. This directory can be configured on a different mount or under a different user profile. However, the owner of the installation directory must have RWX (775) permissions to this directory.

NOTE Ensure the OFSAA staging directory is not set to the same path as the OFSAA installation directory and is not a subdirectory inside the OFSAA installation directory.

- **OIDF Hive Directory (Mandatory for Big Data Installation):** Create a directory for the file system stage area of the Hive server. This is commonly referred to as *FTP SHAREH* or *HIVE_SERVER_FTPDRIVE*. Ensure that the user permission is set to 775 on the Installation Directory.

4.8 Configure the OS File System Settings and Environment Settings in the .profile File

Topics:

- [Configure Operating System and File System Settings](#)
- [Configure the Environment Settings](#)

A `.profile` file is a start-up file of a UNIX user. Create the `.profile` file at the home directory of the logged-in user if it is not already available. The user must have 755 permission on the file to execute it. This file consists of various parameters for Environment Settings, OS, and File System Settings.

To set the parameters for the `.profile` file, login as a non-root user, and configure the environment settings.

WARNING Do not modify any other parameters other than the parameters mentioned in the following subsections.

4.8.1 Configure Operating System and File System Settings

The following table displays the required settings for the operating system and file system.

Table 13: Configure Operating System and File System Settings

Parameter	Configuration Action
Installation Directory	In the <code>.profile</code> file, set the variable <code>FIC_HOME</code> to point to the OFSAA Installation Directory.

Parameter	Configuration Action
File Descriptor Settings	<p>In the <code>sysctl.conf</code> file, to change the number of file descriptors, do the following as the root user:</p> <ol style="list-style-type: none"> Edit the following line in the <code>/etc/sysctl.conf</code> file: <code>fs.file-max = <value></code> where <code><value></code> is greater than 15000 Apply the change by running the following command: <code># /sbin/sysctl -p</code> <p>NOTE: The value specified here is the minimum value to be set for the installation process to go forward. For other modules, this value may depend on the available resources and the number of processes executed in parallel.</p>
Total Number of Process Settings	<p>In the <code>sysctl.conf</code> file set the value to greater than 4096.</p> <p>NOTE: The value specified here is the minimum value to be set for the installation process to go forward. For other modules, this value may depend on the available resources and the number of processes executed in parallel.</p>
Port Settings	<p>Default port numbers to be enabled on the system are 6500, 6501, 6505, 6507, 6509, 6510, 6666, 9999, and 10101.</p>
.profile permissions	<p>You must have 755 permission on the <code>.profile</code> file.</p>
OS Locale	<ul style="list-style-type: none"> Linux: <code>en_US.utf8</code> Solaris: <code>en_US.UTF-8</code> <p>To check the locale installed, execute the following command: <code>locale -a grep -i 'en_US.utf'</code></p>

4.8.2 Configure the Environment Settings

This section provides information to configure the environment settings before installation.

Topics:

- [Java Settings](#)
- [Oracle Database Server and Client Settings](#)
- [TNS Entries in the TNSNAMES.ORA File](#)
- [Oracle Essbase Settings](#)
- [Time Zone Settings](#)

NOTE

If you are installing an application pack in an environment, where another application pack is already installed, you may sometimes get a warning message such as "Object Already Exists". This message can be ignored.

4.8.2.1 Java Settings

The following table displays the Java settings required for installation.

Table 14: Java Settings

Description	Example Value
In the <code>.profile</code> file, set <code>PATH</code> to include the Java Runtime Environment (JRE) absolute path. Ensure that <code>SYMBOLIC</code> links to <code>JAVA</code> installation are not set in the <code>PATH</code> variable.	<code>JAVA_HOME=/scratch/jdk<<version>>/jre</code> For example: <code>PATH=/usr/java/jre1.8.0_221/bin:\$ORACLE_HOME/bin:\$PATH</code> <code>JAVA_HOME=/scratch/jdk<<version>>/jre</code>
In the <code>.profile</code> file, set <code>PATH</code> to include the Java Runtime Environment bin path.	<code>JAVA_BIN=/scratch/<<version>>/jre/bin</code> For example: <code>PATH=/usr/java/jre1.8.0_221/bin:\$ORACLE_HOME/bin:\$PATH</code>
In the <code>.profile</code> file, set the Java tool options for all versions JDK 11.0.20 and above updates	<code>JAVA_TOOL_OPTIONS=""</code> <code>Djdk.util.zip.disableZip64ExtraFieldValidation=true"</code> <code>export JAVA_TOOL_OPTIONS</code>
Enable unlimited cryptographic policy for Java.	For more information, see the <i>Enabling Unlimited Cryptographic Policy for Java</i> section from the Oracle Financial Services Advanced Analytical Applications Infrastructure Administration and Configuration Guide Release 8.1x .

4.8.2.2 Oracle Database Server and Client Settings

The following table displays the Oracle Database server and client settings required for installation.

Table 15: Oracle Database Server and Client Settings

Description	Example Value
In the <code>.profile</code> file, set <code>TNS_ADMIN</code> pointing to the appropriate <code>tnsnames.ora</code> file.	<code>TNS_ADMIN=\$HOME/tns</code>
In the <code>.profile</code> file, set <code>ORACLE_HOME</code> pointing to the appropriate Oracle Client installation.	<code>ORACLE_HOME=/scratch/oraofss/app_client19c/product/19.0.0/client_1</code>
In the <code>.profile</code> file, set <code>PATH</code> to include the appropriate <code>\$ORACLE_HOME/bin</code> path.	<code>PATH=\$JAVA_HOME/bin:\$ORACLE_HOME/bin</code>

Description	Example Value
OFSAA Processing Server	<ul style="list-style-type: none"> • ORACLE_HOME must be set in the .profile file and point to the appropriate Oracle DB Client installation. • PATH in the .profile file must be set to include the appropriate \$ORACLE_HOME/bin path. • Ensure that an entry (with SID/SERVICE NAME) is added in the tnsnames.ora file.

4.8.2.3 TNS entries in the TNSNAMES.ORA file for Non-TCPS and TCPS

This section provides information about the TNS entries in the TNSNAMES.ORA file.

Topics:

- [Non-TCPS](#)
- [TCPS](#)

4.8.2.3.1 Non-TCPS

Table 16: TNS entries in the TNSNAMES.ORA file for the Non-TCPS mode

Description	Example Value
Ensure that an entry (with SID/ SERVICE NAME) is added in the tnsnames.ora file on the OFSAA server.	<pre><SID_NAME> = DESCRIPTION = (ADDRESS_LIST = (ADDRESS = (PROTOCOL = TCP) (HOST = <HOST_NAME>.in.oracle.com) (PORT = 1521))) (CONNECT_DATA = (SERVICE_NAME = <SID_NAME>)) <ATOMIC_SCHEMA_NAME> = (DESCRIPTION =(ADDRESS_LIST = (ADDRESS = (PROTOCOL = TCP) (HOST = <HOST_NAME>.in.oracle.com) (PORT = 1521))) (CONNECT_DATA = (SERVICE_NAME = <SID_NAME>)))</pre>

```
<SID NAME> =
  (DESCRIPTION =
    (ADDRESS_LIST =
      (ADDRESS = (PROTOCOL = TCP) (HOST = <HOST NAME>) (PORT = <PORT NUMBER>))
    )
    (CONNECT_DATA =
      (SERVICE_NAME = <SID NAME>)
    )
  )
```

```
<ATOMICSCHEMANAME> =
  (DESCRIPTION =
    (ADDRESS_LIST =
      (ADDRESS = (PROTOCOL = TCP) (HOST = <HOST NAME>) (PORT = <PORT NUMBER>))
    )
    (CONNECT_DATA =
      (SERVICE_NAME = <SID NAME>)
    )
  )
```

)
)

NOTE The ATOMIC SCHEMA NAME must be the same as defined in the OFS_<App Pack>_SCHEMA_IN.xml file.

4.8.2.3.2 TCPS

Table 17: TNS entries in the TNSNAMES.ORA file for the Non-TCPS mode

Description	Example Value
Ensure that an entry (with SID/SERVICE NAME) is added in the tnsnames.ora file on the OFSAA server.	<pre><SID_NAME> = DESCRIPTION = (ADDRESS_LIST = (ADDRESS = (PROTOCOL = TCPS) (HOST = <HOST_NAME>.in.oracle.com) (PORT = 1521))) (CONNECT_DATA = (SERVICE_NAME = <SID_NAME>)) <ATOMIC_SCHEMA_NAME> = (DESCRIPTION =(ADDRESS_LIST = (ADDRESS = (PROTOCOL = TCPS) (HOST = <HOST_NAME>.in.oracle.com) (PORT = 1521))) (CONNECT_DATA = (SERVICE_NAME = <SID_NAME>))) (security=(ssl_server_cert_dn=CN=<HO ST_NAME>)))</pre>
Ensure that an entry (with WALLET_HOME and wallet parameters) is added in the sqlnet.ora file on the OFSAA server must be the same as the Oracle database server running with TCPS.	<pre>NAMES.DIRECTORY_PATH= (TNSNAMES, EZCONNECT) WALLET_LOCATION = (SOURCE = (METHOD = FILE) (METHOD_DATA = (DIRECTORY = <PATH TO WALLET DIRECTORY>))) SQLNET.WALLET_OVERRIDE = TRUE SSL_CLIENT_AUTHENTICATION = FALSE SQLNET.AUTHENTICATION_SERVICES = (TCPS,NTS,BEQ) SSL_CIPHER_SUITES = (SSL_RSA_WITH_AES_256_CBC_SHA, SSL_RSA_WITH_3DES_EDE_CBC_SHA)</pre>

```
<SID NAME> =
  (DESCRIPTION =
    (ADDRESS_LIST =
      (ADDRESS = (PROTOCOL = TCPS) (HOST = <HOST NAME>) (PORT = <PORT
NUMBER>))
    )
    (CONNECT_DATA =
      (SERVICE_NAME = <SID NAME>))
  (security=(ssl_server_cert_dn=CN=<HOST NAME>))
  )
)
```

```
<ATOMICSCHEMANAME> =
  (DESCRIPTION =
    (ADDRESS_LIST =
      (ADDRESS = (PROTOCOL = TCPS) (HOST = <HOST NAME>) (PORT = <PORT
NUMBER>))
    )
    (CONNECT_DATA =
```

```
(SERVICE_NAME = <SID NAME>)

(security=(ssl_server_cert_dn=CN=<HOST NAME>))
)
```

NOTE

The ATOMIC SCHEMA NAME must be the same as defined in the OFS_OIDF_SCHEMA_IN.xml file, which also includes prefix without underscore. For example, DEVOFSAAATM.

4.8.2.4 Oracle Essbase Settings

In the .profile file, set the following parameters if you need to use Oracle Hyperion Essbase OLAP features.

Table 18: Oracle Essbase Settings

Description	Example Value
ARBORPATH to point to an appropriate Oracle Essbase Client installation.	PATH=\$PATH:\$ARBORPATH/bin
ESSBASEPATH to point to an appropriate Oracle Essbase Client installation.	ESSBASEPATH=/scratch/essps3/Oracle/MiddlewareHome/EPMSysstem11R1/common/EssbaseRTC-64/11.1.2.0 export ESSBASEPATH
HYPERION_HOME to point to an appropriate Oracle Essbase Client installation.	HYPERION_HOME=/scratch/essps3/Oracle/MiddlewareHome/EPMSysstem11R1/common/EssbaseRTC-64/11.1.2.0 export HYPERION_HOME

4.8.2.5 Time Zone Settings

In the .profile file, set the Time Zone parameter to indicate the time zone of your region/ location.

Table 19: Time Zone Settings

Description	Example Value
Time Zone	TZ=Asia/Calcutta

5 Installation

This section details the steps to be followed during the OIDF Application Pack installation.

Topics:

- [Installation Checklist](#)
- [Extract the Software](#)
- [Install Pre-installation Patches](#)
- [Configure the OFS_OIDF_PACK.xml File](#)
- [Configure the Schema Creator Utility](#)
- [Configure the OFS_OIDF_SCHEMA_IN.xml File](#)
- [Configure the OFS_OIDF_SCHEMA_BIGDATA_IN.xml File for Stage and Results on Hive](#)
- [Configure the OFS_OIDF_SCHEMA_BIGDATA_IN.xml.HYBRID File for Stage on Hive and Results on RDBMS](#)
- [Configure the OFSAAI_InstallConfig.xml File](#)
- [Configure the Silent.props File](#)
- [Backup the Configuration Files](#)
- [Execute the Schema Creator Utility](#)
- [Verify the Schema Creator Log Files](#)
- [Install the OIDF Application Pack](#)
- [Install a New OIDF Application Pack on an Existing OFSAA Instance](#)

5.1 Installation Checklist

To complete the OIDF Application Pack installation process, you must perform the following steps listed in the Installation Checklist. Use this checklist to verify whether these steps are completed or not.

Table 20: Installation Checklist

Sl. No.	Activity
1	Extract the OIDF Application Pack software.
2	Configure the OFS_OIDF_PACK.xml file.
3	Configure the OFS_OIDF_SCHEMA_IN.xml file.
4	Configure the OFS_OIDF_SCHEMA_BIGDATA_IN.xml file for Stage and Results on Hive or Stage on Hive and Results on RDBMS (Only for the Big Data installation).
5	Configure the OFSAAI_InstallConfig.xml file.
6	Configure the Silent.props file.
7	Backup the configuration files.

Sl. No.	Activity
8	Execute the Schema Creator Utility in Offline , Online , or TCPS modes.
9	Verify the Schema Creator log files.
10	Trigger the OIDF Application Pack installation.

5.2 Extract the OIDF Application Pack Software

You must be logged in to the UNIX operating system as a non-root user to perform the following steps. To extract the software, follow these steps:

1. Download the unzip utility (OS-specific) `unzip_<os>.z` and copy it in Binary mode to the directory that is included in your PATH variable.

If you already have an unzip utility to extract the contents of the downloaded archive, skip this step. Uncompress the unzip installer file with the command:

```
uncompress unzip_<os>.Z
```

NOTE If an error message "uncompress: not found [No such file or directory]" is displayed, contact your UNIX administrator.

2. Assign 751 permission to the file with the following command:

```
chmod 751 unzip_<os>
```

For example, `chmod 751 unzip_sparc`

3. Extract the contents of the OIDF Application Pack Release v8.1.0.0.0 installer archive file in the download directory with the following command:

```
unzip OFS_OIDF_8.1.0.0.0_<Operating_System>.zip
```

NOTE Do not rename the Application Pack installer folder name on extraction from the archive.

4. Navigate to the Download Directory and assign 750 permission to the installer directory with the following command:

```
chmod -R 750 OFS_OIDF_PACK
```

5. Extract the following patches in the download directory:
 - a. **31545589** – OFSAAI mandatory one-off patch. See the ReadMe packaged with the patch for further instructions about how to extract the patch.
 - b. **31605076** – OFSAAI mandatory one-off patch. See the ReadMe packaged with the patch for further instructions about how to extract the patch.

5.3 Install Pre-installation Patches

Before installing OIDF Application Pack 8.1.0.0.0, apply the **31545589** one-off patch. See the ReadMe packaged with the patch for further instructions about how to install the patch.

See [My Oracle Support \(MOS\)](#) for more information on the latest release.

5.4 Configure the OFS_OIDF_PACK.xml File

The `OFS_OIDF_PACK.xml` file contains details of various OFSAA products that are packaged in the OIDF Application Pack.

To configure the `OFS_OIDF_PACK.xml` file, follow these steps:

1. Navigate to the `<INSTALLER_DIRECTORY>/OFS_OIDF_PACK/conf` directory.
 - For the RDBMS mode of installation, rename the file `OFS_OIDF_PACK.xml.template` to `OFS_OIDF_PACK.xml`.
 - In the Big Data mode of installation, for Stage and Results on Hive, rename the file `OFS_OIDF_PACK.xml.BIGDATA.template` to `OFS_OIDF_PACK.xml`.
 - In the Big Data mode of installation, for Stage on Hive and Results on RDBMS, rename the file `OFS_OIDF_PACK.xml.HYBRID.template` to `OFS_OIDF_PACK.xml`.
2. Open the `OFS_OIDF_PACK.xml` file in a text editor.
3. Configure the `OFS_OIDF_PACK.xml` file as mentioned in the following table.

NOTE

During the Big Data mode of installation, for Stage and Results on Hive, enable the option to **YES** for the **APP_ID** parameter with the value **OFS_AAIB** as illustrated in the sample illustration.

During the Big Data mode of installation, for Stage on Hive and Results on RDBMS, enable the option to **YES** for the **APP_ID** parameter with the value **OFS_OIDFHV** as illustrated in the sample illustration.

Figure 5: Sample of the OFS_OIDF_PACK.xml file

```

<APP_PACK_CONFIG>
  <APP_PACK_ID>OFS_OIDF_PACK</APP_PACK_ID>
  <APP_PACK_NAME>Financial Services Foundation Applications Pack</APP_PACK_NAME>
  <APP_PACK_DESCRIPTION>Applications forming analytics foundation such for the Banking and Financial Services Domain
</APP_PACK_DESCRIPTION>
  <VERSION>8.1.0.0.0</VERSION>
  <APP>
    <APP_ID PREREQ="" DEF_SEL_FLG="YES" ENABLE="YES">OFS_AAI</APP_ID>
    <APP_NAME>Financial Services Analytical Applications Infrastructure</APP_NAME>
    <APP_DESCRIPTION>Base Infrastructure for Analytical Applications</APP_DESCRIPTION>
    <VERSION>8.1.0.0.0</VERSION>
  </APP>
  <APP>
    <APP_ID PREREQ="OFS_AAI" ENABLE="YES">OFS_OIDF</APP_ID>
    <APP_NAME>Oracle Insurance Data Foundation</APP_NAME>
    <APP_DESCRIPTION>Data Foundation for Insurance domain</APP_DESCRIPTION>
    <VERSION>8.1.0.0.0</VERSION>
  </APP>
  <APP>
    <APP_ID PREREQ="OFS_AAI" ENABLE="YES">OFS_AAIB</APP_ID>
    <APP_NAME>Financial Services Analytical Applications Infrastructure Big Data Option</APP_NAME>
    <APP_DESCRIPTION>Base Infrastructure for Analytical Applications Big Data Option</APP_DESCRIPTION>
    <VERSION>8.1.0.0.0</VERSION>
  </APP>
  <APP>
    <APP_ID PREREQ="OFS_AAIB" ENABLE="YES">OFS_OIDFHV</APP_ID>
    <APP_NAME>Oracle Insurance Data Foundation</APP_NAME>
    <APP_DESCRIPTION>Data Foundation for Insurance domain</APP_DESCRIPTION>
    <VERSION>8.1.0.0.0</VERSION>
  </APP>
</APP_PACK_CONFIG>

```

Table 21: The OFS_OIDF_PACK.xml file parameters

Tag Name or Attribute Name	Description	Mandatory? (Y or N)	Comments
APP_PACK_ID	Unique Application Pack Identifier	Y	This is a unique seeded value. DO NOT modify this value.
IS_OPT_INSTALL VALUE="TRUE"	Unique Application Entry	Y	This is a unique seeded value. DO NOT modify this value.
APP_PACK_NAME	Unique Application Pack Name	Y	This is a unique seeded value. DO NOT modify this value.
APP_PACK_DESCRIPTION	Unique Application Pack Description	Y	This is a unique seeded value. DO NOT modify this value.
VERSION	Unique release version	Y	This is a unique seeded value. DO NOT modify this value.
APP	Unique Application Entries	Y	This is a unique seeded value. DO NOT modify this value.
APP_ID	Unique Application Identifier	Y	This is a unique seeded value. DO NOT modify this value.

Tag Name or Attribute Name	Description	Mandatory? (Y or N)	Comments
APP_ID/PREREQ	Prerequisite Application/ Product	Y	This is a unique seeded value. For most applications, Infrastructure is the prerequisite set. For some other applications, a required Application ID is set. DO NOT modify this value.
APP_ID/DEF_SEL_FLAG	Default Selected Flag	Y	The default value is YES. In all the Application Packs, the Infrastructure sets this value set to "YES". DO NOT modify this value.
APP_ID/ENABLE	Enable Application/ Product	YES if installing in the SILENT mode.	The default value is YES for Infrastructure. The default value is NO for Others. The permissible values are YES and NO. Set this attribute value to YES against every APP_ID that is licensed and that you need to enable for use. NOTE: You cannot disable the Application or Product after you enable it. Only those Applications or Products, which are enabled, are installed. To enable the other licensed Applications or Products, reinstall by setting the flag to Y for the APP_ID. However, in the case of reinstallation, to enable other Applications or Products, skip the execution of the Schema Creation Utility if it does not include the creation of any additional sandbox.
APP_NAME	Unique Application/ Product Name	Y	This is a unique seeded value. DO NOT modify this value.
APP_DESCRIPTION	Unique Application/ Product Name	Y	This is a unique seeded value. DO NOT modify this value.
VERSION	Unique release version	Y	This is a unique seeded value. DO NOT modify this value.

4. Save the file.

5.5 Configure the Schema Creator Utility

Creating database users or schemas (RDBMS) is one of the primary steps in the complete installation process. The Schema Creator utility enables you to quickly get started with the installation by creating Database User(s) or Schema(s) (RDBMS), assigning the necessary GRANT(s), creating the required entities in the schemas and so on.

The schema creator utility must be configured and executed before the installation of the OIDF Application Pack.

Topics:

- [Prerequisites](#)
- [Configure the Schema Creator Utility for RDBMS Installation](#)
- [Configure the Schema Creator Utility for HDFS Schema](#)

5.5.1 Prerequisites

Ensure you have the following before configuring the Schema Creator Utility:

- Oracle User ID/Password with SYSDBA privileges
- JDBC Connection URL for RAC/Non-RAC database
- The HOSTNAME/IP of the server on which OFSAA is getting installed.

In the case of the HIVE installation, you must also have the following:

- HIVE connection credentials (For example, Kerberos connection properties).
- Hostname/IP of the HIVE Server installation

5.5.2 Configure the Schema Creator Utility for RDBMS Installation

If the installation is being performed for RDBMS, provide the Pack specific schema details in the `OFS_OIDF_SCHEMA_IN.xml` file.

You can configure the following types of schemas:

- **CONFIG:** This schema holds the entities and other objects required for OFSAA setup configuration information. There can be only one CONFIG schema per OFSAA instance
- **ATOMIC:** This schema holds the data model entities. One ATOMIC schema is attached to one Information Domain. There can be multiple ATOMIC schemas per OFSAA Instance.

The `OFS_OIDF_PACK/schema_creator/conf/` directory contains the following files:

- `OFS_OIDF_SCHEMA_IN.xml`
- `OFS_OIDF_SCHEMA_BIGDATA_IN.xml.template`
- `OFS_OIDF_SCHEMA_BIGDATA_IN.xml.HYBRID.template`
- `OFS_OIDF_CFG.dat.template`
- `OFS_OIDF_APP_CFG.dat`
- `App_Pack_Bigdata_Schema_Creator.xsd`
- `App_Pack_Schema_Creator.xsd`

5.5.2.1 Configure the OFS_OIDF_SCHEMA_IN.xml File

Creating database schemas, objects within schemas, and assigning required grants are the primary steps in the installation process of the OFSAA Applications.

The `OFS_OIDF_SCHEMA_IN.xml` file contains details of the various application schemas.

Update the values of various tags and parameters available in this file and then execute the schema creator utility.

NOTE Configure this file only for the RDBMS ONLY target installation of the OIDF Application Pack. Do not configure this file for an HDFS ONLY target installation.

To configure the OFS_OIDF_SCHEMA_IN.xml file, follow these steps:

1. Log in to the system as a non-root user.
2. Navigate to the OFS_OIDF_PACK/schema_creator/conf/ directory.
3. Rename the file OFS_OIDF_SCHEMA_IN.xml.template to OFS_OIDF_SCHEMA_IN.xml.
4. Edit the OFS_OIDF_SCHEMA_IN.xml file using a text editor and configure the values as mentioned in the following table.

Figure 6: Sample of the OFS_OIDF_SCHEMA_IN.xml file

```
<APPPACKSCHEMA>
  <APP_PACK_ID>OFS_OIDF_PACK</APP_PACK_ID>
  <IS_TCPS>FALSE</IS_TCPS>
  <JDBC_URL>jdbc:oracle:thin:@##IP_ADDRESS##:##PORT_NUMBER##:##MYDATABASE##</JDBC_URL>
  <JDBC_DRIVER>oracle.jdbc.driver.OracleDriver</JDBC_DRIVER>
  <HOST>##MYHOSTNAME##</HOST>
  <SETUPINFO NAME="DEV" PREFIX_SCHEMA_NAME="N" />
  <PASSWORD APPLYSAMEFORALL="Y" DEFAULT="" />

  <ADV_SEC_OPTIONS>
    <OPTION NAME="TDE" VALUE="TRUE"/>
    <OPTION NAME="DATA_REDACT" VALUE="TRUE" />
  </ADV_SEC_OPTIONS>

  <!--
  <TABLESPACES>
    <TABLESPACE NAME="OFS_OIDF_DATA_TBSP" VALUE="OFS_OIDF_DATA_1"
      DATAFILE="/PATH/ofs_oidf_data_1.dbf" SIZE="500M" AUTOEXTEND="ON" ENCRYPT="OFF" />
    <TABLESPACE NAME="OFS_OIDF_SBX_TBSP" VALUE="OFS_OIDF_DATA_2"
      DATAFILE="/PATH/ofs_oidf_data_2.dbf" SIZE="512M" AUTOEXTEND="ON" ENCRYPT="OFF" />
  </TABLESPACES>
  -->
  <SCHEMAS>
    <SCHEMA TYPE="CONFIG" NAME="##MYCONSCHEMANAME##" PASSWORD="" APP_ID="OFS_AAI"
      DEFAULTTABLESPACE="##OFS_OIDF_DATA_TBSP##" TEMPTABLESPACE="TEMP" QUOTA ="" />
    <SCHEMA TYPE="ATOMIC" NAME="##MYATMSHEMANAME##" PASSWORD="" APP_ID="OFS_OIDF" INFODOM=
      "OIDFINFO" DEFAULTTABLESPACE="##OFS_OIDF_DATA_TBSP##" TEMPTABLESPACE="TEMP" QUOTA ="" />
  </SCHEMAS>
</APPPACKSCHEMA>
```

Figure 7: Sample of the OFS_OIDF_SCHEMA_IN.xml file (APPPACKSCHEMA Block)

```

<APPPACKSCHEMA>
  <APP_PACK_ID>OFS_OIDF_PACK</APP_PACK_ID>
  <IS_TCPS>FALSE</IS_TCPS>
  <JDBC_URL>jdbc:oracle:thin:@##IP_ADDRESS##:##PORT_NUMBER##:##MYDATABASE##</JDBC_URL>
  <JDBC_DRIVER>oracle.jdbc.driver.OracleDriver</JDBC_DRIVER>
  <HOST>##MYHOSTNAME##</HOST>
  <SETUPINFO NAME="DEV" PREFIX_SCHEMA_NAME="N" />
  <PASSWORD APPLYSAMEFORALL="Y" DEFAULT="" />

```

Table 22: The OFS_OIDF_PACK_SCHEMA_IN.xml file (APPPACKSCHEMA Parameters)

Tag Name or Attribute Name	Description	Mandatory?	Default Value or Permissible Value	Comments
<APP_PACK_ID>	This is a unique Application Pack identifier.	Y	This is a unique seeded value. Example: OFS_OIDF_PACK	DO NOT modify this value.
<IS_TCPS>	Enter the value if the TCPS configuration is required. Entering this parameter creates a secure line between the client and server when using the OIDF application.	Y	This is a seeded value. The default value is FALSE.	Modify this to TRUE, if you require the installer to uptake the configuration.

Tag Name or Attribute Name	Description	Mandatory?	Default Value or Permissible Value	Comments
<JDBC_URL>	Enter the JDBC URL. NOTE: You can enter the RAC and NON-RAC enabled database connectivity URL.	Y	Example: jdbc:oracle:thin:@<HOST>:<PORT>:<SID> or jdbc:oracle:thin:@//[HOST][: PORT]/SERVICE or jdbc:oracle:thin:@(DESCRIPTION=(ADDRESS_LIST=(ADDRESS=(PROTOCOL=TCP)(HOST=[HOST]))(port=[PORT]))(ADDRESS=(PROTOCOL=TCP)(HOST=[HOST])(PORT=[PORT]))(LOAD_BALANCE=yes)(FAILOVER=yes))(CONNECT_DATA=(SERVICE_NAME=[SERVICE]))) For example: jdbc:oracle:thin:@//dbhost.server.com:<port>/service1 or jdbc:oracle:thin:@//dbhost.server.com:<port>/scan-1 or jdbc:oracle:thin:@(DESCRIPTION=(ADDRESS_LIST=(ADDRESS=(PROTOCOL=TCP)(HOST=dbhost1.server.com)(port=<port>))(ADDRESS=(PROTOCOL=TCP)(HOST=dbhost2.server.com)(PORT=<port>))(LOAD_BALANCE=yes)(FAILOVER=yes))(CONNECT_DATA=(SERVICE_NAME=service1)))	Ensure to add an entry (with SID or SERVICE NAME) in the <code>tnsnames.ora</code> file on the OFSAA server. The entry needs to match with the SID or SERVICE NAME used in the JDBC URL.
<JDBC_DRIVER>	By default, the name of this driver is seeded. NOTE: Do not edit this attribute value.	Y	Example: oracle.jdbc.driver.OracleDriver	Only the JDBC Thin Driver is supported. DO NOT modify this value.
<HOST>	Enter the Hostname or IP Address of the system on which you are installing the OFSAA components.	Y	Host Name or IP Address	

Tag Name or Attribute Name	Description	Mandatory?	Default Value or Permissible Value	Comments
<SETUPINFO>/NAME	Enter the acronym for the type of implementation. This information is displayed on the OFSAA Home Page. NOTE: On executing the schema creator utility, this value is prefixed with each schema name. For example, dev_ofsaaconf, uat_ofsaaatm.	Y	Accepts strings with a minimum length of two and a maximum of four. Example: DEV, SIT, PROD	This name appears in the OFSAA Landing Page as “Connected To: XXXX” The schemas that are created, get this prefix. For example: dev_ofsaaconf, uat_ofsaaconf etc.
<SETUPINFO>/PREFIX_SCHEMA_NAME	Identifies if the value specified in <SETUPINFO>/NAME attribute needs to be prefixed to the schema name.	N	The default value is Y. Permissible values are Y or N.	The default value is Y.
<PASSWORD>/APPLYSAMEFORALL	Enter as Y if you need to apply the password specified in the DEFAULT attribute for all the schemas. If you enter as N, you need to provide individual passwords for all schemas. NOTE: In case you have entered Y in APPLYSAMEFORALL attribute and have specified individual passwords for all the schemas, then the specified individual passwords take precedence.	Y	The default value is N Permissible values are Y and N.	NOTE: Setting this attribute value is mandatory. If the DEFAULT attribute is set.
<PASSWORD>/DEFAULT*	Enter the password if you need to set a default password for all schemas. NOTE: You also need to set the APPLYSAMEFORALL attribute as Y to apply the default password for all the schemas.	N	The maximum length allowed is 30 characters. Special characters are not allowed.	

Figure 8: Sample of the OFS_OIDF_SCHEMA_IN.xml file (ADV_SEC_OPTIONS Block)

```

<ADV_SEC_OPTIONS>
  <OPTION NAME="TDE" VALUE="TRUE"/>
  <OPTION NAME="DATA_REDACT" VALUE="TRUE" />
</ADV_SEC_OPTIONS>

```

Table 23: OFS_OIDF_PACK_SCHEMA_IN.xml file (Advance Security Options Parameters)

Tag Name/ Attribute Name	Description	Mandatory/ Optional	Default Value/ Permissible Value	Comments
<ADV_SEC_OPTIONS>	Parent tag to hold Advance Security Options.	N		Uncomment the tag and edit if you need to add security options. For example, TDE and Data Redact. For details, see the example following the table.
<ADV_SEC_OPTIONS>/TDE	Tag to enable/disable TDE.	N	The default value is FALSE. To enable TDE, set this to TRUE.	Ensure this tag is not commented if you have uncommented <ADV_SEC_OPTIONS>/
<ADV_SEC_OPTIONS>/DATA_REDACT	Tag to enable/disable the Data Redaction feature.	N	The default is FALSE. To enable DATA_REDACT, set this to TRUE.	Ensure this tag is not commented if you have uncommented <ADV_SEC_OPTIONS>/

Figure 9: Sample of the OFS_OIDF_SCHEMA_IN.xml file (TABLESPACES Block)

```

<TABLESPACES>
  <TABLESPACE NAME="OFS_BFND_DATA_TBSP" VALUE="OFS_BFND_DATA_1"
  DATAFILE="/PATH/ofs_bfnd_data_1.dbf" SIZE="500M" AUTOEXTEND="ON" ENCRYPT="OFF" />
  <TABLESPACE NAME="OFS_BFND_SBX_TBSP" VALUE="OFS_BFND_DATA_2"
  DATAFILE="/PATH/ofs_bfnd_data_2.dbf" SIZE="512M" AUTOEXTEND="ON" ENCRYPT="OFF" />
</TABLESPACES>

```

Table 24: OFS_OIDF_PACK_SCHEMA_IN.xml file (Tablespaces Parameters)

Tag Name/ Attribute Name	Description	Mandatory/ Optional	Default Value/ Permissible Value	Comments
<TABLESPACES>	Parent tag to hold <TABLESPACE> elements	N	NA	Uncomment the tag and edit. ONLY if tablespaces are to be created as part of the installation. For details, see the example following the table. NOTE: When TDE is TRUE in ADV_SEC_OPTIONS, then the <TABLESPACES> tag must be present in the XML file.
<TABLESPACE>/NAME	Create the Logical Name of the tablespace	Y		Name if specified should be referred to in the <SCHEMA DEFAULTTABLESPACE= "###NAME##"> attribute. Note the ## syntax.
<TABLESPACE>/VALUE	Create the Physical Name of the tablespace	Y	NA	Value, if specified, is the actual name of the TABLESPACE.
<TABLESPACE>/DATAFILE	Specifies the location of the data file on the server	Y	NA	Enter the absolute path of the file to be created.
<TABLESPACE>/AUTOEXTEND	Specifies if the tablespace needs to be extensible or have a hard limit	Y	ON or OFF	Set to ON to ensure that the tablespaces do not run out of space when full.
<TABLESPACE>/ENCRYPT	Specifies if the tablespace(s) needs to be encrypted using TDE.	Y	ON or OFF	Set to ON to ensure that the tablespaces when created are encrypted using TDE.

NOTE Encryption of tablespaces requires enabling Transparent Data Encryption (TDE) on the Database Server.

Figure 10: Sample of the OFS_OIDF_SCHEMA_IN.xml file (SCHEMAS Block)

```
<SCHEMAS>
  <SCHEMA TYPE="CONFIG" NAME="MYCONSCHEMANAME" PASSWORD="" APP_ID="OFS_AAI"
    DEFAULTTABLESPACE="USERS" TEMPTABLESPACE="TEMP" QUOTA ="UNLIMITED" />
  <SCHEMA TYPE="ATOMIC" NAME="MYATMSCHEMANAME" PASSWORD="" APP_ID="OFS_FSDF" INFODOM=
    "MYINFODOMNAME" DEFAULTTABLESPACE="USERS" TEMPTABLESPACE="TEMP" QUOTA ="UNLIMITED" />
</SCHEMAS>
```

Table 25: OFS_OIDF_PACK_SCHEMA_IN.xml file (SCHEMAS Parameters)

Tag Name/ Attribute Name	Description	Mandatory/ Optional	Default Value/ Permissible Value	Comments
<SCHEMA>/TYPE	<p>The different types of schemas that are supported in this release are ATOMIC, CONFIG, SANDBOX, and ADDON.</p> <p>By default, the schemas types are seeded based on the Application Pack.</p> <p>NOTE: Do not edit this attribute value.</p>	Y	<p>ATOMIC/CONFIG/SANDBOX/ADDON</p> <p>NOTE: SANDBOX AND ADDON schemas are not applicable for OIDF Application Pack.</p>	<p>Only One CONFIG schema can exist in the file.</p> <p>This schema identifies as the CONFIGURATION schema that holds the OFSAA setup details and other metadata information.</p> <p>Multiple ATOMIC/SANDBOX/ADDON schemas can exist in the file.</p> <p>ATOMIC schema refers to the Information Domain schema.</p> <p>SANDBOX schema refers to the Sandbox. ADDON schema refers to other miscellaneous schemas (not applicable for this Application Pack).</p>

Tag Name/ Attribute Name	Description	Mandatory/ Optional	Default Value/ Permissible Value	Comments
<SCHEMA>/NAME	<p>By default, the schema names are seeded based on the Application Pack. You can edit the schema names if required.</p> <p>NOTE: The Schema Name has a prefix of the SETUPINFO/ NAME attribute. SCHEMA NAME needs to be the same for all the ATOMIC Schemas of applications within an Application Pack.</p>	Y	The permissible length is 15 characters and only alphanumeric characters are allowed. No special characters are allowed except underscore '_'.	<p>SETUPINFO/NAME attribute value is prefixed to the schema name that is created. For example, If the name is set as 'ofsaaatm' and setupinfo as 'uat' then the schema created is 'uat_ofsaaatm'.</p> <p>Example for <SCHEMA>/ NAME: ##CONFIG_USER_NAME## or ##ATOMIC_USER_NAME##</p> <p>NAME should be the same where APP_GRP=1 for all SCHEMA tags (Not applicable for this Application Pack).</p>
<SCHEMA>/PASSWORD	<p>Enter the password of the schema to be created.</p> <p>NOTE: If this attribute is left blank, then the password specified in the <PASSWORD>/DEFAULT attribute is applied as the Schema Password.</p>	N	The maximum length allowed is 30 characters. Special characters are not allowed.	NOTE: You need to mandatorily enter the password if you have set the <PASSWORD>/ APPLYSAMEFORALL attribute as N.
<SCHEMA>/APP_ID	<p>By default, the Application ID is seeded based on the Application Pack.</p> <p>NOTE: Do not edit this attribute value.</p>	Y	<p>Unique Seeded Value</p> <p>Example: For CONFIG schema, OFS_AAI For ATOMIC schema, OFS_OIDF</p>	<p>Identifies the Application or Product for which the schema is being created.</p> <p>DO NOT modify this value.</p>
<SCHEMA>/DEFAULTTABLESPACE	<p>Enter the available default tablespace for DB User.</p> <p>NOTE: If this attribute is left blank, then USERS is set as the default tablespace.</p>	N	<p>Default – USERS Permissible – Any existing valid tablespace name.</p> <p>Example: ##OFS_OIDF_DATA_TBSP##</p>	Modify this value to associate any valid tablespace with the schema.

Tag Name/ Attribute Name	Description	Mandatory/ Optional	Default Value/ Permissible Value	Comments
<SCHEMA>/TEMPTABLESPACE	Enter the available temporary tablespace for the DB User. NOTE: If this attribute is left blank, then TEMP is set as the default tablespace.	N	Default – TEMP Permissible – Any existing valid temporary tablespace name. Example: ##OFS_OIDF_DATA_TBSP##	Modify this value to associate any valid tablespace with the schema.
<SCHEMA>/QUOTA	Enter the quota to be set on the DEFAULTTABLESPACE attribute for the schema or user. By default, the quota size is set to 500M. Minimum: 500M or Unlimited on default Tablespace	N	For example, 600M/m 20G/g UNLIMITED/unlimited	Modify this value to grant the specified quota on the mentioned tablespace to the user.
<SCHEMA>/INFODOM	Enter the name of the Information Domain to associate this schema. The schema creator utility automatically derives an Information Domain Name based on the Application Pack if no value is specified for this attribute.	N (Optional for Atomic and mandatory for sandbox)	Permissible length is 16 characters and only alphanumeric characters are allowed. No special characters are allowed.	Enter this field in UPPERCASE.

5. Save the file.

5.5.2.1.1 Example of TDE Enablement and TABLESPACES with Encryption ON

The following snippet shows that TDE is enabled and therefore, the tablespaces are shown with the encryption ON.

```
<ADV_SEC_OPTIONS>
<OPTION NAME="TDE" VALUE="FALSE"/>
<OPTION NAME="DATA_REDACT" VALUE="FALSE" />
</ADV_SEC_OPTIONS>
<TABLESPACES>
<TABLESPACE NAME="OFS_AAI_TBSP_1" VALUE="TS_USERS1"
DATAFILE="/scratch/ora19c/app/oracle/oradata/OFSPQA19CDB/ts_users1.dbf" SIZE="500M" AUTOEXTEND="ON"
ENCRYPT="ON" />
```

```
<TABLESPACE NAME="OFS_AAI_TBSP_2" VALUE="TS_USERS2"  
DATAFILE="/scratch/ora19c/app/oracle/oradata/OFSPQA19CDB/ts_users2.dbf" SIZE="500M" AUTOEXTEND="ON"  
ENCRYPT="ON" />
```

```
</TABLESPACES>
```

```
<SCHEMAS>
```

```
<SCHEMA TYPE="CONFIG" NAME="ofsaaconf" PASSWORD="" APP_ID="OFS_AAI" DEFAULTTABLESPACE="##OFS_AAI_TBSP_1##"  
TEMPTABLESPACE="TEMP" QUOTA="unlimited"/>
```

```
<SCHEMA TYPE="ATOMIC" NAME="ofsaaatm" PASSWORD="" APP_ID="OFS_AAAI" DEFAULTTABLESPACE="##OFS_AAI_TBSP_2##"  
TEMPTABLESPACE="TEMP" QUOTA="unlimited" INFODOM="OFSAAAIINFO"/>
```

```
</SCHEMAS>
```

5.5.3 Configure the Schema Creator Utility for HDFS Schema

If the installation is being performed for Big Data, provide the Pack specific schema details in the `OFS_OIDF_SCHEMA_BIGDATA_IN.xml` file.

The schema types that you can configure are:

- **CONFIG:** This schema holds the entities and other objects required for OFSAA setup configuration information. There can be only one CONFIG schema per OFSAA instance. This schema is created only in RDBMS.
- **METADOM:** This schema holds the Data Model entities. One METADOM schema is attached to one Information Domain. There can be multiple DATADOM schemas per OFSAA Instance. This schema is created only in RDBMS. It has only platform entities that hold the metadata details. However, it does not hold the Data Model entities.
- **DATADOM:** This schema holds Data Model entities. One DATADOM schema is attached to one Information Domain. There can be multiple DATADOM schemas per OFSAA Instance.

The `OFS_OIDF_PACK/schema_creator/conf/` directory contains the following files:

- `OFS_OIDF_SCHEMA_IN.xml`
- `OFS_OIDF_SCHEMA_BIGDATA_IN.xml.template`
- `OFS_OIDF_SCHEMA_BIGDATA_IN.xml.HYBRID.template`
- `OFS_OIDF_CFG.dat.template`
- `OFS_OIDF_APP_CFG.dat`
- `App_Pack_Bigdata_Schema_Creator.xsd`
- `App_Pack_Schema_Creator.xsd`

Topics:

- [Configure the OFS_OIDF_SCHEMA_BIGDATA_IN.xml file for Stage and Results on Hive](#)
- [Configure the OFS_OIDF_SCHEMA_BIGDATA_IN.xml file for Stage on Hive and Results on RDBMS](#)

5.5.3.1 Configure the OFS_OIDF_SCHEMA_BIGDATA_IN.xml file for Stage and Results on Hive

Creating Hive schemas and objects within the schemas are the primary steps in the installation process of OFSAA Applications.

The `OFS_OIDF_SCHEMA_BIGDATA_IN.xml` file contains details about various application schemas. Update the values of the various tags and parameters available in this file before executing the Schema Creator Utility.

NOTE

Configure this file only for the HDFS ONLY target installation of the OIDF Application Pack. Do not configure this file for an RDBMS ONLY target installation.

To configure the `OFS_OIDF_SCHEMA_IN.xml` file for Stage and Results on Hive, follow these steps:

1. Log in to the system as a non-root user.
2. Navigate to the `OFS_OIDF_PACK/schema_creator/conf/` directory.
 - Rename the file `OFS_OIDF_SCHEMA_IN.xml` to `OFS_OIDF_SCHEMA_IN.xml.template`.
 - Rename the file `OFS_OIDF_SCHEMA_BIGDATA_IN.xml.template` to `OFS_OIDF_SCHEMA_BIGDATA_IN.xml`.
3. Edit the `OFS_OIDF_SCHEMA_BIGDATA_IN.xml` file using a text editor and configure the values as mentioned in the following table.

Figure 11: Sample of the OFS_OIDF_SCHEMA_BIGDATA_IN.xml file (Stage and Results on Hive)

```

<APPPACKSCHEMA>
  <APP_PACK_ID>OFS_OIDF_PACK</APP_PACK_ID>
  <IS_TCPS>FALSE</IS_TCPS>
  <JDBC_URL>jdbc:oracle:thin:@##IP_ADDRESS##:##PORT_NUMBER##:##MYDATABASE##</JDBC_URL>
  <JDBC_DRIVER>oracle.jdbc.driver.OracleDriver</JDBC_DRIVER>
  <HOST>##MYHOSTNAME##</HOST>
  <IS_HYBRID VALUE="FALSE"/>
  <SETUPINFO NAME="OIDF" PREFIX_SCHEMA_NAME="N"/>
  <PASSWORD APPLYSAMEFORALL="Y" DEFAULT="##CONFIG_META_SCHEMA_PASSWORD##"/>
  <SCHEMAS TYPE="RDBMS">
    <SCHEMA TYPE="CONFIG" NAME="##MYHIVECONSCHEMA##" PASSWORD="" APP_ID="OFS_AAI" DEFAULTTABLESPACE="USERS"
      TEMPTABLESPACE="TEMP" QUOTA="500M"/>
    <SCHEMA TYPE="ATOMIC" NAME="##MYHIVEATMSHEMA##" PASSWORD="" APP_ID="OFS_OIDF" DEFAULTTABLESPACE="USERS"
      TEMPTABLESPACE="TEMP" QUOTA="10G" INFODOM="##MYHIVEINFODOM##"/>
  </SCHEMAS>

  <SCHEMAS TYPE="HDFS">
    <HIVE_SERVER_HOST>##MY_HIVE_SERVER_HOST_NAME_OR_IP##</HIVE_SERVER_HOST>
    <HIVE_LIB_PATH>##MY_HIVE_LIBRARY_PATH##</HIVE_LIB_PATH>
    <SCHEMA NAME="##MYHIVEDATADOM##" TYPE="DATADOM" APP_ID="OFS_OIDF" DB_TYPE="HIVE" INFODOM="##MYHIVEINFODOM##">
      <SCHEMA_PROPERTIES>
        <PROPERTY ID="COMMENT" VALUE="" />
        <PROPERTY ID="LOCATION" VALUE="" />
      </SCHEMA_PROPERTIES>
      <CONNECTION_PROPERTIES>
        <PROPERTY ID="JDBC_DRIVER" VALUE="com.cloudera.hive.jdbc4.HS2Driver" />
        <PROPERTY ID="JDBC_URL" VALUE="
          jdbc:hive2://##MY_HIVE_SERVER_HOST_NAME_OR_IP##:10000/<<PREFIX>>_<<SCHEMA_NAME>>;AuthMech=1;KrbServiceName=hive;KrbHostFQDN=##MY_HIVE_SERVER_HOST_NAME_OR_IP##;KrbRealm=##REALM##" />
        <PROPERTY ID="AUTH_TYPE" VALUE="KERBEROS_WITH_KEYTAB" />
        <PROPERTY ID="AUTH_ALIAS" VALUE="##ALIAS_NAME_FOR_AUTHENTICATION##" />
        <PROPERTY ID="PRINCIPAL" VALUE="##AUTHENTICATION_PRINCIPAL_NAME##" />
        <PROPERTY ID="PASSWORD" VALUE="##HIVE_USER_PASSWORD##"/>
        <PROPERTY ID="KRB_GSSJAAS_FILE_NAME" VALUE="##KEYTAB_PATH_AND_FILE_NAME##" />
        <PROPERTY ID="KRB_REALM_FILE_NAME" VALUE="##REALM_CONFIGURATION_PATH_AND_FILE_NAME##" />
      </CONNECTION_PROPERTIES>
    </SCHEMA>
  </SCHEMAS>
</APPPACKSCHEMA>

```

Figure 12: Sample of the OFS_OIDF_SCHEMA_BIGDATA_IN.xml file (APPPACKSCHEMA Block for Stage and Results on Hive)

```

<APPPACKSCHEMA>
  <APP_PACK_ID>OFS_OIDF_PACK</APP_PACK_ID>
  <IS_TCPS>FALSE</IS_TCPS>
  <JDBC_URL>jdbc:oracle:thin:@##IP_ADDRESS##:##PORT_NUMBER##:##MYDATABASE##</JDBC_URL>
  <JDBC_DRIVER>oracle.jdbc.driver.OracleDriver</JDBC_DRIVER>
  <HOST>##MYHOSTNAME##</HOST>
  <IS_HYBRID VALUE="FALSE"/>
  <SETUPINFO NAME="OIDF" PREFIX_SCHEMA_NAME="N"/>
  <PASSWORD APPLYSAMEFORALL="Y" DEFAULT="##CONFIG_META_SCHEMA_PASSWORD##"/>

```

Table 26: OFS_OIDF_SCHEMA_BIGDATA_IN.xml file (APPPACKSCHEMA Parameters for Stage and Results on Hive)

Tag Name/ Attribute Name	Description	Mandatory (Y/N)	Default Value/ Permissible Value	Comments
<APP_PACK_ID>	Seeded unique ID for the OFSAA Application Pack.	Y	Seeded	DO NOT modify this value.
<IS_TCPS>	Enter if the TCPS configuration is required. This is to create a secure line between the client and server when using the OIDF application.	Y	Seeded, with FALSE as the default value.	Modify this to TRUE if you require the installer to uptake the configuration.
<JDBC_URL>	Enter the JDBC URL. NOTE: You can enter the RAC or NON-RAC enabled database connectivity URL.	Y	Example: jdbc:oracle:thin:@<HOST/ IP>:<PORT>:<SID> or jdbc:oracle:thin:@//[HOS T]:[PORT]/SERVICE or jdbc:oracle:thin:@(DESCRI PTION=(ADDRESS_ LIST=(ADDRESS=(PROT OCOL=TCP)(HOST=[HO ST]))(port=[PORT]))(ADD RESS=(PROTOCOL=TCP) (HOST=[HOST]))(PORT=[PORT]))(LOAD_	For an HDFS ONLY target installation, this URL need to be of the RDBMS instance that hosts the Application's METADOM.

Tag Name/ Attribute Name	Description	Mandatory (Y/N)	Default Value/ Permissible Value	Comments
			BALANCE=yes)(FAILOVER=yes))(CONNECT_DATA=(SERVICE_NAME=[SERVICE])) For example, jdbc:oracle:thin:@//dbhost1.server.com:<port>/service1 or jdbc:oracle:thin:@//dbhost1.server.com:<port>/scan-1 or jdbc:oracle:thin:@(DESCRIPTION=(ADDRESS_LIST=(ADDRESS=(PROTOCOL=TCP)(HOST=dbhost1.server.com)(port=1521)))(ADDRESS=(PROTOCOL=TCP)(HOST=dbhost2.server.com)(PORT=1521))(LOAD_BALANCE=yes)(FAILOVER=yes))(CONNECT_DATA=(SERVICE_NAME=service1)))	
<JDBC_DRIVER>	By default, this driver's name is seeded. NOTE: Do not edit this attribute value.	Y	Example: oracle.jdbc.driver.OracleDriver	Only JDBC Thin Driver is supported. DO NOT modify this value.
<HOST>	Enter the Hostname or IP Address of the system on which you are installing the OFSAA components.	Y	Host Name/ IP Address	
<IS_HYBRID>/VALUE	Tag to enable/disable HYBRID installation (Stage on Hive and Results on RDBMS).	N	The default value is FALSE	The default value is FALSE for Hive.

Tag Name/ Attribute Name	Description	Mandatory (Y/N)	Default Value/ Permissible Value	Comments
<SETUPINFO>/PREFIX_SCHEMA_NAME	Identifies if the value specified in the <SETUPINFO>/NAME attribute needs to be prefixed to the schema name.	N	YES or NO.	The default value is YES.
<SETUPINFO>/NAME	Enter the acronym for the type of implementation. This information is displayed on the OFSAA Home Page. NOTE: On executing the schema creator utility, this value will be prefixed with each schema name. For example, dev_ofsaaconf, uat_ofsaaconf, and so on.	Y	Accepts strings with a minimum length of two and a maximum of four. Example: OIDF	This name appears in the OFSAA Landing Page as "Connected To: XXXX". The schemas created get this prefix. For example, dev_ofsaaconf, uat_ofsaaconf, and so on.
<PASSWORD>/DEFAULT*	Enter the password if you need to set a default password for all schemas. NOTE: You also need to set the APPLYSAMEFORALL attribute as Y to apply the default password for all the schemas.	N	The maximum length allowed is 30 characters. Special characters are not allowed.	Applies only to the RDBMS type METADOM schema(s).

Tag Name/ Attribute Name	Description	Mandatory (Y/N)	Default Value/ Permissible Value	Comments
<PASSWORD>/APPLY SAMEFORALL	<p>Enter as Y if you need to apply the password specified in the DEFAULT attribute for all the schemas.</p> <p>If you enter as N, you need to provide individual passwords for all schemas.</p> <p>NOTE: If you have entered Y in the APPLYSAMEFORALL attribute and have specified individual passwords for all the schemas, then the specified individual passwords takes precedence.</p>	Y	<p>The default value is N.</p> <p>Permissible values are Y and N.</p>	<p>NOTE: Setting this attribute value is mandatory if the DEFAULT attribute is set.</p> <p>Applies only to the RDBMS type METADOM schema(s).</p>

Figure 13: Sample of the OFS_OIDF_SCHEMA_BIGDATA_IN.xml file (SCHEMA type RDBMS Block for Stage and Results on Hive)

```

<SCHEMAS TYPE="RDBMS">
  <SCHEMA TYPE="CONFIG" NAME="##MYHIVECONSCHEMA##" PASSWORD="" APP_ID="OFS_AAI" DEFAULTTABLESPACE="USERS"
  TEMPTABLESPACE="TEMP" QUOTA="500M"/>
  <SCHEMA TYPE="ATOMIC" NAME="##MYHIVEATMSHEMA##" PASSWORD="" APP_ID="OFS_OIDF" DEFAULTTABLESPACE="USERS"
  TEMPTABLESPACE="TEMP" QUOTA="10G" INFODOM="##MYHIVEINFODOM##"/>
</SCHEMAS>

```

Table 27: OFS_OIDF_SCHEMA_BIGDATA_IN.xml file (SCHEMA type RDBMS Parameters for Stage and Results on Hive)

Tag Name/ Attribute Name	Description	Mandatory (Y/N)	Default Value/ Permissible Value	Comments
<SCHEMAS>/TYPE=RDBMS	Identifies the RDBMS schema details.	Y	Default names for schemas within the pack are derived in the absence of any value specified.	In an HDFS ONLY target installation, the Application's METADOM (that hosts the metadata) for an application is stored in the RDBMS schema and the Data Model entities of the application are stored in the DATADOM (which is on Hive).
<SCHEMA>/TYPE	<p>The different types of schemas that are supported in this release are ATOMIC, CONFIG.</p> <p>By default, the schemas types are seeded based on the Application Pack.</p> <p>NOTE: Do not edit this attribute value.</p>	Y	ATOMIC/CONFIG.	<p>Only One CONFIG schema can exist in the file. This schema identifies as the CONFIGURATION schema that holds the OFSAA setup details and other metadata information.</p> <p>Multiple ATOMIC or SANDBOX or ADDON schemas can exist in the file.</p> <p>ATOMIC schema refers to the METADOM within the Information Domain schema. SANDBOX schema refers to the SANDBOX schema.</p> <p>ADDON schema refers to other miscellaneous schemas (not applicable for this Application Pack).</p>
<SCHEMA>/NAME	<p>By default, the schema names are seeded based on the Application Pack.</p> <p>You can edit the schema names if required.</p> <p>NOTE:</p> <p>The Schema Name has a prefix of the SETUPINFO/NAME attribute.</p> <p>The SCHEMA NAME must be the same for all the ATOMIC Schemas of applications within an Application Pack.</p>	Y	The permissible length is 15 characters and only alphanumeric characters are allowed. No special characters are allowed except the Underscore '_'.	<p>SETUPINFO/ NAME attribute value is be prefixed to the schema name created.</p> <p>For example, if the name is set as 'ofsaaatm' and setupinfo as 'uat' then the schema created is 'uat_ofsaaatm'.</p> <p>NAME needs to be the same where APP_GRP=1 for all SCHEMA tags (not applicable for this Application Pack).</p>

Tag Name/ Attribute Name	Description	Mandatory (Y/N)	Default Value/ Permissible Value	Comments
<SCHEMA>/PASSWORD	Enter the password of the schema to be created. NOTE: If this attribute is left blank, then the password specified in the <PASSWORD>/DEFAULT attribute is applied as the Schema Password.	N	The maximum length allowed is 30 characters. Special characters are not allowed.	NOTE: You need to mandatorily enter the password if you have set the <PASSWORD>/APPLYSAMEFORALL attribute as N.
<SCHEMA>/APP_ID	By default, the Application ID is seeded based on the Application Pack. NOTE: Do not edit this attribute value.	Y	Unique Seeded value.	Identifies the Application or Product for which the schema is created. DO NOT modify this value.
<SCHEMA>/DEFAULT TABLESPACE	Enter the available default tablespace for DB User. NOTE: If this attribute is left blank, then USERS is set as the default tablespace.	N	The default value is USERS. Permissible value is any existing valid tablespace name.	Modify this value to associate any valid tablespace with the schema.
<SCHEMA>/TEMPTABLESPACE	Enter the available temporary tablespace for the DB User. NOTE: If this attribute is left blank, then TEMP is set as the default tablespace.	N	The default value is TEMP. Permissible value is any existing valid temporary tablespace name.	Modify this value to associate any valid tablespace with the schema.
<SCHEMA>/QUOTA	Enter the quota to be set on the DEFAULTTABLESPACE attribute for the schema or user. By default, the quota size is set to 500M. Minimum: 500M or Unlimited on default Tablespace.	N	Example: 600M or 600m 20G or 20g UNLIMITED or unlimited	Modify this value to grant the specified quota on the mentioned tablespace to the user.
<SCHEMA>/INFODOM	Enter the name of the Information Domain to associate this schema. The schema creator utility automatically derives an Information Domain Name based	N	Permissible length is 16 characters and only alphanumeric characters are allowed. No special characters are allowed.	

Tag Name/ Attribute Name	Description	Mandatory (Y/N)	Default Value/ Permissible Value	Comments
	on the Application Pack if the value is not specified for this attribute.		##INFODOM_NAME## Example: OIDFINFO	

Figure 14: Sample of the OFS_OIDF_SCHEMA_BIGDATA_IN.xml file (SCHEMA type HDFS Block for Stage and Results on Hive)

```

<SCHEMAS TYPE="HDFS">
  <HIVE_SERVER_HOST>MyHIVEServerHostName</HIVE_SERVER_HOST>
  <HIVE_LIB_PATH>HiveLibraryPath</HIVE_LIB_PATH>
  <SCHEMA NAME="MYHIVEDATADOM" TYPE="DATADOM" APP_ID="OFS_FSDF" DB_TYPE="HIVE" INFODOM="MYHIVEINFODOM">
    <SCHEMA_PROPERTIES>
      <PROPERTY ID="COMMENT" VALUE="" />
      <PROPERTY ID="LOCATION" VALUE="" />
    </SCHEMA_PROPERTIES>
    <CONNECTION_PROPERTIES>
      <PROPERTY ID="JDBC_DRIVER" VALUE="com.cloudera.hive.jdbc4.HS2Driver" />
      <PROPERTY ID="JDBC_URL" VALUE="
jdbc:hive2://##HIVE_SERVER_HOST_NAME_OR_IP##:10000/<<PREFIX>>_<<SCHEMA_NAME>>;AuthMech=1
;KrbServiceName=hive;KrbHostFQDN=##HIVE_SERVER_HOST_NAME_OR_IP##;KrbRealm=##REALM##" />
      <PROPERTY ID="AUTH_TYPE" VALUE="KERBEROS_WITH_KEYTAB" />
      <PROPERTY ID="AUTH_ALIAS" VALUE="AliasNameForAuthentication" />
      <PROPERTY ID="PRINCIPAL" VALUE="AuthenticationPrincipalName" />
      <PROPERTY ID="PASSWORD" VALUE="" />
      <PROPERTY ID="KRB_GSSJAAS_FILE_NAME" VALUE="KEYTABPathAndFileName" />
      <PROPERTY ID="KRB_REALM_FILE_NAME" VALUE="REALMConfigurationPathAndFileName" />
    </CONNECTION_PROPERTIES>
  </SCHEMA>
</SCHEMAS>

```

Table 28: OFS_OIDF_SCHEMA_BIGDATA_IN.xml file (SCHEMA type HDFS Parameters for Stage and Results on Hive)

Tag Name/ Attribute Name	Description	Mandatory (Y/N)	Default Value/ Permissible Value	Comments
<SCHEMAS>/TYPE=HDFS	Type of schemas created.	Y		Refers to the DATADOM of the Application Pack installed.
<HIVE_SERVER_HOST>	IP or HostName of the server where HIVE is installed.	Y		
<HIVE_LIB_PATH>	Folder path where HIVE related drivers or jar files are copied.	Y		Needs to contain the list of jars mentioned in the section Copy the Jar Files to the OFSAA Installation Directory and krb5.conf, keytab files. Manually copy the preceding listed files from CDH distribution to this identified folder. NOTE: The Cloudera administrator provides these two files krb5.conf and keytab.
<SCHEMA>/NAME	By default, the schema names are seeded based on the Application Pack. You can edit the schema names if required. NOTE: The Schema Name has a prefix of the SETUPINFO/NAME attribute.	Y	The permissible length is 20 characters and only alphanumeric characters are allowed. Example: HIVEHYBDATADOM	Schema Name should not be the same as Schema Name specified for Schema Type ATOMIC.
<SCHEMA>/TYPE	Identifies the type of schema where the Data Model entities reside.	Y	By default, the TYPE attribute in this tag is set to DATADOM.	DO NOT modify this value.

Tag Name/ Attribute Name	Description	Mandatory (Y/N)	Default Value/ Permissible Value	Comments
<SCHEMA>/APP_ID	By default, the Application ID is seeded based on the Application Pack.	Y	The supported value is OFS_OIDF.	
<SCHEMA>/DB_TYPE	Identifies the type of driver to be used for the connection.	Y	By default, the only supported type is HIVE in this release.	In the upcoming releases, the type of value can be HIVE, IMPALA, and so on.
<SCHEMA>/INFODOM	Enter the name of the Information Domain to associate this schema. The schema creator utility automatically derives an Information Domain Name based on the Application Pack if the value is not specified for this attribute.	N	Permissible length is 16 characters and only alphanumeric characters are allowed. No special characters are allowed. For example: ##MY_HIVE_INFODOM## For Hive part in Stage on Hive and Results on RDBMS: Example: OIDFHVINFO	
<SCHEMA_PROPERTIES>/<PROPERTY>/COMMENT	COMMENTS for HIVE schema.	N		
<SCHEMA_PROPERTIES>/<PROPERTY>/LOCATION	You can optionally specify a location for the table data.	N	hdfs:// ##HIVE_SERVER_HOST_NAME_OR_IP## :NameNodePort/user/hive/warehouse/<<PREFIX>>__<<SCHEMA_NAME>>/ NOTE: The <<PREFIX>> prefix is applicable only if the <PREFIX_SCHEMA_NAME> tag is "Y" in the <SETUPINFO> tag. For example: When <SETUPINFO NAME="OIDF" PREFIX_SCHEMA_NAME="Y"/>. <<SCHEMA_NAME>> is the DATADOM schema name. Example:	

Tag Name/ Attribute Name	Description	Mandatory (Y/N)	Default Value/ Permissible Value	Comments
			hdfs://whf00bsy.in.oracle.com:8020/user/hive/warehouse/OIDF_BSYDATADOM/	
<CONNECTION_PROPERTIES>/<PROPERTY>/JDBC_DRIVER	HIVE JDBC driver details.	Y	com.cloudera.hive.jdbc4.HS2Driver	The default cloudera HiveServer 2 driver name.
<CONNECTION_PROPERTIES>/<PROPERTY>/JDBC_URL	Enter the HIVE JDBC URL.	Y	A valid Hive JDBC URL to be specified. jdbc:hive2://###HIVE_SERVER_HOST_NAME_OR_IP###:10000/<<PREFIX>>_<<SCHEMA_NAME>>;AuthMech=1;KrbServiceName=hive;KrbHostFQDN=###HIVE_SERVER_HOST_NAME_OR_IP###;KrbRealm=###REALM### NOTE: <<PREFIX>> Prefix is applicable only if the <PREFIX_SCHEMA_NAME> tag is Y in <SETUPINFO> tag. For example, when <SETUPINFO NAME="OIDF" PREFIX_SCHEMA_NAME="Y"/>. <<SCHEMA_NAME>> is the DATADOM schema name. For example: jdbc:hive2://whf00bsy.in.oracle.com:10000/OIDF_BSYDATADOM;AuthMech=1;KrbServiceName=hive;KrbHostFQDN=whf00bsy.in.oracle.com;KrbRealm=WHFBSY.ORACLE.COM	Specify the Hive JDBC URL to connect to the Hive Server.
<CONNECTION_PROPERTIES>/<PROPERTY>/AUTH_TYPE	Authentication Type.	Y	Permissible values: KERBEROS_WITH_KEYTAB.	Only "Kerberos with keytab" based authentication is supported in this release.

Tag Name/ Attribute Name	Description	Mandatory (Y/N)	Default Value/ Permissible Value	Comments
<CONNECTION_PROPERTIES>/<PROPERTY>/AUTH_ALIAS	Alias name for authentication credentials.	Y		An Alias name mapping to a principal and password combination is specified in the following tags.
<CONNECTION_PROPERTIES>/<PROPERTY>/PRINCIPAL	Authentication principal name.	Y		Principal name used in authentication to connect to the Hive Server.
<CONNECTION_PROPERTIES>/<PROPERTY>/PASSWORD	Authentication password.	Y		Password used in authentication to connect to the Hive Server.
<CONNECTION_PROPERTIES>/<PROPERTY>/KRB_GSSJAAS_FILE_NAME	A keytab file containing pairs of Kerberos principals and an encrypted copy of that principal's key.	Y		This file needs to be copied to the location specified in <HIVE_LIB_PATH>.
<CONNECTION_PROPERTIES>/<PROPERTY>/KRB_REALM_FILE_NAME	REALM configuration file.	Y		This file needs to be copied to the location specified in <HIVE_LIB_PATH>.

4. Save the file.

5.5.3.2 Configure the OFS_OIDF_SCHEMA_BIGDATA_IN.xml file for Stage on Hive and Results on RDBMS

Creating Hive schemas and objects within the schemas are the primary steps in the installation process of the OFSAA Applications.

The `OFS_OIDF_SCHEMA_BIGDATA_IN.xml` file contains details about the various application schemas. Update the values of the various tags and parameters available in this file before executing the Schema Creator Utility.

NOTE

Configure this file only for the HDFS ONLY target installation of the OIDF Application Pack. Do not configure this file for an RDBMS ONLY target installation.

To configure the `OFS_OIDF_SCHEMA_IN.xml` file for Stage on Hive and Results on RDBMS, follow these steps:

1. Log in to the system as a non-root user.
2. Navigate to the `OFS_OIDF_PACK/schema_creator/conf/` directory.
 - Rename the file `OFS_OIDF_SCHEMA_IN.xml` to `OFS_OIDF_SCHEMA_IN.xml.template`.
 - Rename the file `OFS_OIDF_SCHEMA_BIGDATA_IN.xml.HYBRID.template` to `OFS_OIDF_SCHEMA_BIGDATA_IN.xml`.
 - Rename the file `OFS_OIDF_APP_CFG.dat` to `OFS_OIDF_APP_CFG.dat.template`.
 - Rename the file `OFS_OIDF_CFG.dat.HYBRID.template` to `OFS_OIDF_APP_CFG.dat`.
3. Edit the `OFS_OIDF_SCHEMA_BIGDATA_IN.xml` file using a text editor and configure the values as mentioned in the following table.

Figure 15: Sample of the OFS_OIDF_SCHEMA_BIGDATA_IN.xml file (Stage on Hive and Results on RDBMS)

```

<APPPACKSCHEMA>
  <APP_PACK_ID>OFS_OIDF_PACK</APP_PACK_ID>
  <IS_TCPS>FALSE<IS_TCPS>
  <JDBC_URL>jdbc:oracle:thin:@##IP_ADDRESS##:##PORT_NUMBER##:##MYDATABASE##</JDBC_URL>
  <JDBC_DRIVER>oracle.jdbc.driver.OracleDriver</JDBC_DRIVER>
  <HOST>##MYHOSTNAME##</HOST>
  <IS_HYBRID VALUE="TRUE"/>
  <SETUPINFO NAME="OIDF" PREFIX_SCHEMA_NAME="N"/>
  <PASSWORD APPLYSAMEFORALL="Y" DEFAULT="##CONFIG_META_SCHEMA_PASSWORD##"/>

  <SCHEMAS TYPE="RDBMS">
    <SCHEMA TYPE="CONFIG" NAME="##MYHIVECONSCHEMA##" PASSWORD="" APP_ID="OFS_AAI" DEFAULTTABLESPACE="USERS"
      TEMPTABLESPACE="TEMP" QUOTA="500M"/>
    <SCHEMA TYPE="ATOMIC" NAME="##MYRDBMSATMSHEMA##" PASSWORD="" APP_ID="OFS_OIDF" APP_GRP="1"
      DEFAULTTABLESPACE="USERS" TEMPTABLESPACE="TEMP" QUOTA="10G" INFODOM="OIDFINFOM"/>
    <SCHEMA TYPE="ATOMIC" NAME="##MYHIVEATMSHEMA##" PASSWORD="" APP_ID="OFS_OIDFHV" INFODOM=
      "##MY_HIVE_INFODOM##" DEFAULTTABLESPACE="USERS" TEMPTABLESPACE="TEMP" QUOTA="10G" />
  </SCHEMAS>

  <SCHEMAS TYPE="HDFS">
    <HIVE_SERVER_HOST>##MY_HIVE_SERVER_HOST_NAME_OR_IP##</HIVE_SERVER_HOST>
    <HIVE_LIB_PATH>##USER_HOME##/libs</HIVE_LIB_PATH>
    <SCHEMA NAME="##DATADOM_SCHEMA_NAME##" TYPE="DATADOM" APP_ID="OFS_OIDFHV" DB_TYPE="HIVE" INFODOM=
      "##MY_HIVE_INFODOM##">
      <SCHEMA_PROPERTIES>
        <PROPERTY ID="COMMENT" VALUE="" />
        <PROPERTY ID="LOCATION" VALUE="" />
      </SCHEMA_PROPERTIES>
      <CONNECTION_PROPERTIES>
        <PROPERTY ID="JDBC_DRIVER" VALUE="com.cloudera.hive.jdbc4.HS2Driver" />
        <PROPERTY ID="JDBC_URL" VALUE=
          "jdbc:hive2://##MY_HIVE_SERVER_HOST_NAME_OR_IP##:10000/<<PREFIX>>_<<SCHEMA_NAME>>;AuthMech=1;KrbServi
          ceName=hive;KrbHostFQDN=##MY_HIVE_SERVER_HOST_NAME_OR_IP##;KrbRealm=##REALM##" />
        <PROPERTY ID="AUTH_TYPE" VALUE="KERBEROS_WITH_KEYTAB" />
        <PROPERTY ID="AUTH_ALIAS" VALUE="##ALIAS_NAME_FOR_AUTHENTICATION##" />
        <PROPERTY ID="PRINCIPAL" VALUE="##AUTHENTICATION_PRINCIPAL_NAME##" />
        <PROPERTY ID="PASSWORD" VALUE="##HIVE_USER_PASSWORD##"/>
        <PROPERTY ID="KRB_GSSJAAS_FILE_NAME" VALUE="##KEYTAB_PATH_AND_FILE_NAME##" />
        <PROPERTY ID="KRB_REALM_FILE_NAME" VALUE="##REALM_CONFIG_PATH_AND_FILE_NAME##" />
      </CONNECTION_PROPERTIES>
    </SCHEMA>
  </SCHEMAS>
</APPPACKSCHEMA>

```

Figure 16: Sample of the OFS_OIDF_SCHEMA_BIGDATA_IN.xml file (APPPACKSCHEMA Block for Stage on Hive and Results on RDBMS)

```

<APPPACKSCHEMA>
  <APP_PACK_ID>OFS_OIDF_PACK</APP_PACK_ID>
  <IS_TCPS>FALSE</IS_TCPS>
  <JDBC_URL>jdbc:oracle:thin:@##IP_ADDRESS##:##PORT_NUMBER##:##MYDATABASE##</JDBC_URL>
  <JDBC_DRIVER>oracle.jdbc.driver.OracleDriver</JDBC_DRIVER>
  <HOST>##MYHOSTNAME##</HOST>
  <IS_HYBRID VALUE="TRUE"/>
  <SETUPINFO NAME="OIDF" PREFIX_SCHEMA_NAME="N"/>
  <PASSWORD APPLYSAMEFORALL="Y" DEFAULT="##CONFIG_META_SCHEMA_PASSWORD##"/>

```

Table 29: OFS_OIDF_SCHEMA_BIGDATA_IN.xml file (APPPACKSCHEMA Parameters for Stage on Hive and Results on RDBMS)

Tag Name/ Attribute Name	Description	Mandatory (Y/N)	Default Value/ Permissible Value	Comments
<APP_PACK_ID>	Seeded unique ID for the OFSAA Application Pack.	Y	Seeded	DO NOT modify this value.
<IS_TCPS>	Enter if the TCPS configuration is required. This is to create a secure line between the client and server when using the OIDF application.	Y	Seeded, with FALSE as the default value.	Modify this to TRUE if you require the installer to uptake the configuration.
<JDBC_URL>	Enter the JDBC URL. NOTE: You can enter the RAC or NON-RAC enabled database connectivity URL.	Y	Example: jdbc:oracle:thin:@<HOST/ IP>:<PORT>:<SID> or jdbc:oracle:thin:@//[HOS T][:PORT]/SERVICE or jdbc:oracle:thin:@(DESCRI PTION=(ADDRESS_ LIST=(ADDRESS=(PROT OCOL=TCP)(HOST=[HO ST]))(port=[PORT]))(ADD RESS=(PROTOCOL=TCP)	For an HDFS ONLY target installation, this URL need to be of the RDBMS instance that hosts the Application's METADOM.

Tag Name/ Attribute Name	Description	Mandatory (Y/N)	Default Value/ Permissible Value	Comments
			(HOST=[HOST])(PORT=[PORT])(LOAD_ BALANCE=yes)(FAILOV ER=yes)(CONNECT_ DATA=(SERVICE_ NAME=[SERVICE])) For example, jdbc:oracle:thin:@//dbhos t.server.com:<port>/service 1 or jdbc:oracle:thin:@//dbsho st.server.com:<port>/scan-1 or jdbc:oracle:thin:@(DESCRI PTION=(ADDRESS_ LIST=(ADDRESS=(PROT OCOL=TCP)(HOST=dbho st1.server.com)(port=1521))(ADDRESS=(PROTOCO L=TCP)(HOST=dbhost2.s erver.com)(PORT=1521))(LOAD_ BALANCE=yes)(FAILOV ER=yes))(CONNECT_ DATA=(SERVICE_ NAME=service1)))	
<JDBC_DRIVER>	By default, this driver's name is seeded. NOTE: Do not edit this attribute value.	Y	Example: oracle.jdbc.driver.OracleD river	Only JDBC Thin Driver is supported. DO NOT modify this value.
<HOST>	Enter the Hostname or IP Address of the system on which you are installing the OFSAA components.	Y	Host Name/ IP Address	
<IS_HYBRID>/VALUE	Tag to enable or disable the HYBRID installation (Stage on Hive and Results on RDBMS).	Y	The default value is FALSE	The default value is TRUE for Stage on Hive and Results on RDBMS.

Tag Name/ Attribute Name	Description	Mandatory (Y/N)	Default Value/ Permissible Value	Comments
<SETUPINFO>/PREFIX_SCHEMA_NAME	Identifies if the value specified in the <SETUPINFO>/NAME attribute needs to be prefixed to the schema name.	N	YES or NO.	The default value is YES.
<SETUPINFO>/NAME	Enter the acronym for the type of implementation. This information is displayed on the OFSAA Home Page. NOTE: On executing the schema creator utility, this value is prefixed with each schema name. For example, dev_ofsaaconf, uat_ofsaaconf, and so on.	Y	Accepts strings with a minimum length of two and a maximum of four. Example: OIDF	This name appears in the OFSAA Landing Page as "Connected To: XXXX". The schemas created get this prefix. For example, dev_ofsaaconf, uat_ofsaaconf, and so on.
<PASSWORD>/DEFAULT*	Enter the password if you need to set a default password for all schemas. NOTE: You also need to set the APPLYSAMEFORALL attribute as Y to apply the default password for all the schemas.	N	The maximum length allowed is 30 characters. Special characters are not allowed.	Applies only to the RDBMS type METADOM schema(s).

Tag Name/ Attribute Name	Description	Mandatory (Y/N)	Default Value/ Permissible Value	Comments
<PASSWORD>/APPLY SAMEFORALL	<p>Enter as Y if you need to apply the password specified in the DEFAULT attribute for all the schemas.</p> <p>If you enter as N, you need to provide individual passwords for all schemas.</p> <p>NOTE: If you have entered Y in the APPLYSAMEFORALL attribute and have specified individual passwords for all the schemas, then the specified individual passwords takes precedence.</p>	Y	<p>The default value is N.</p> <p>Permissible values are Y and N.</p>	<p>NOTE: Setting this attribute value is mandatory if the DEFAULT attribute is set.</p> <p>Applies only to the RDBMS type METADOM schema(s).</p>

Figure 17: Sample of the OFS_OIDF_SCHEMA_BIGDATA_IN.xml file (SCHEMA type RDBMS Block for Stage on Hive and Results on RDBMS)

```

<SCHEMAS TYPE="RDBMS">
  <SCHEMA TYPE="CONFIG" NAME="##MYHIVECONSCHEMA##" PASSWORD="" APP_ID="OFS_AAI" DEFAULTTABLESPACE="USERS"
    TEMPTABLESPACE="TEMP" QUOTA="500M"/>
  <SCHEMA TYPE="ATOMIC" NAME="##MYRDBMSATMSHEMA##" PASSWORD="" APP_ID="OFS_OIDF" APP_GRP="1"
    DEFAULTTABLESPACE="USERS" TEMPTABLESPACE="TEMP" QUOTA="10G" INFODOM="OIDFINFO"/>
  <SCHEMA TYPE="ATOMIC" NAME="##MYHIVEATMSHEMA##" PASSWORD="" APP_ID="OFS_OIDFHV" INFODOM=
    "##MY_HIVE_INFODOM##" DEFAULTTABLESPACE="USERS" TEMPTABLESPACE="TEMP" QUOTA="10G" />
</SCHEMAS>

```

Table 30: OFS_OIDF_SCHEMA_BIGDATA_IN.xml file (SCHEMA type RDBMS Parameters for Stage on Hive and Results on RDBMS)

Tag Name/ Attribute Name	Description	Mandatory (Y/N)	Default Value/ Permissible Value	Comments
<SCHEMAS>/TYPE=RDBMS	Identifies the RDBMS schema details.	Y	Default names for schemas within the pack are derived in the absence of any value specified.	In an HDFS ONLY target installation, the Application's METADOM (that hosts the metadata) for an application is stored in the RDBMS schema and the Data Model entities of the application are stored in the DATADOM (which is on Hive).
<SCHEMA>/TYPE	<p>The different types of schemas that are supported in this release are ATOMIC, CONFIG.</p> <p>By default, the schemas types are seeded based on the Application Pack.</p> <p>NOTE: Do not edit this attribute value.</p>	Y	ATOMIC/CONFIG.	<p>Only One CONFIG schema can exist in the file. This schema identifies as the CONFIGURATION schema that holds the OFSAA setup details and other metadata information.</p> <p>Multiple ATOMIC or SANDBOX or ADDON schemas can exist in the file.</p> <p>ATOMIC schema refers to the METADOM within the Information Domain schema.</p> <p>SANDBOX schema refers to the SANDBOX schema.</p> <p>ADDON schema refers to other miscellaneous schemas (not applicable for this Application Pack).</p>
<SCHEMA>/NAME	<p>By default, the schema names are seeded based on the Application Pack.</p> <p>You can edit the schema names, if required.</p> <p>NOTE:</p> <p>The Schema Name has a prefix of the SETUPINFO/NAME attribute.</p> <p>The SCHEMA NAME must be the same for all the ATOMIC Schemas of applications within an Application Pack.</p>	Y	The permissible length is 15 characters and only alphanumeric characters are allowed. No special characters are allowed except the Underscore '_'.	<p>SETUPINFO/ NAME attribute value is prefixed to the schema name created.</p> <p>For example, if the name is set as 'ofsaaatm' and setupinfo as 'uat' then the schema created is 'uat_ofsaaatm'.</p> <p>NAME needs to be the same where APP_GRP=1 for all SCHEMA tags (not applicable for this Application Pack).</p>

Tag Name/ Attribute Name	Description	Mandatory (Y/N)	Default Value/ Permissible Value	Comments
<SCHEMA>/PASSWORD	Enter the password of the schema to be created. NOTE: If this attribute is left blank, then the password specified in the <PASSWORD>/DEFAULT attribute is applied as the Schema Password.	N	The maximum length allowed is 30 characters. Special characters are not allowed.	NOTE: You need to mandatorily enter the password if you have set the <PASSWORD>/APPLYSAMEFORALL attribute as N.
<SCHEMA>/APP_ID	By default, the Application ID is seeded based on the Application Pack. NOTE: Do not edit this attribute value.	Y	Unique Seeded value.	Identifies the Application or Product for which the schema is created. DO NOT modify this value.
<SCHEMA>/DEFAULT TABLESPACE	Enter the available default tablespace for DB User. NOTE: If this attribute is left blank, the USERS is set as the default tablespace.	N	The default value is USERS. Permissible value is any existing valid tablespace name.	Modify this value to associate any valid tablespace with the schema.
<SCHEMA>/TEMPTABLESPACE	Enter the available temporary tablespace for the DB User. NOTE: If this attribute is left blank, then TEMP is set as the default tablespace.	N	The default value is TEMP. Permissible value is any existing valid temporary tablespace name.	Modify this value to associate any valid tablespace with the schema.
<SCHEMA>/QUOTA	Enter the quota to be set on the DEFAULTTABLESPACE attribute for the schema or user. By default, the quota size is set to 500M. Minimum: 500M or Unlimited on default Tablespace.	N	Example: 600M or 600m 20G or 20g UNLIMITED or unlimited	Modify this value to grant the specified quota on the mentioned tablespace to the user.
<SCHEMA>/INFODOM	Enter the name of the Information Domain to associate this schema. The schema creator utility automatically derives an Information Domain Name based	N	Permissible length is 16 characters and only alphanumeric characters are allowed. No special characters are allowed.	

Tag Name/ Attribute Name	Description	Mandatory (Y/N)	Default Value/ Permissible Value	Comments
	on the Application Pack if the value is not specified for this attribute.		There are two information domains for Stage on Hive and Results on RDBMS installation. One is for RDBMS and another for Hive ##INFODOM_NAME## Example: OIDFINFO Example for Hive part in Stage on Hive and Results on RDBMS (Staging): OIDFHVINFO	

Figure 18: Sample of the OFS_OIDF_SCHEMA_BIGDATA_IN.xml file (SCHEMA type HDFS Block for Stage on Hive and Results on RDBMS)

```
<SCHEMAS TYPE="HDFS">
  <HIVE_SERVER_HOST>##MY_HIVE_SERVER_HOST_NAME_OR_IP##</HIVE_SERVER_HOST>
  <HIVE_LIB_PATH>##USER_HOME##/libs</HIVE_LIB_PATH>
  <SCHEMA NAME="##DATADOM_SCHEMA_NAME##" TYPE="DATADOM" APP_ID="OFS_OIDFHV" DB_TYPE="HIVE" INFODOM=
  "##MY_HIVE_INFODOM##">
    <SCHEMA_PROPERTIES>
      <PROPERTY ID="COMMENT" VALUE="" />
      <PROPERTY ID="LOCATION" VALUE="" />
    </SCHEMA_PROPERTIES>
    <CONNECTION_PROPERTIES>
      <PROPERTY ID="JDBC_DRIVER" VALUE="com.cloudera.hive.jdbc4.HS2Driver" />
      <PROPERTY ID="JDBC_URL" VALUE=
      "jdbc:hive2://##MY_HIVE_SERVER_HOST_NAME_OR_IP##:10000/<<PREFIX>>_<<SCHEMA_NAME>>;AuthMech=1;KrbServiceName=hive;KrbHostFQDN=##MY_HIVE_SERVER_HOST_NAME_OR_IP##;KrbRealm=##REALM##" />
      <PROPERTY ID="AUTH_TYPE" VALUE="KERBEROS_WITH_KEYTAB" />
      <PROPERTY ID="AUTH_ALIAS" VALUE="##ALIAS_NAME_FOR_AUTHENTICATION##" />
      <PROPERTY ID="PRINCIPAL" VALUE="##AUTHENTICATION_PRINCIPAL_NAME##" />
      <PROPERTY ID="PASSWORD" VALUE="##HIVE_USER_PASSWORD##"/>
      <PROPERTY ID="KRB_GSSJAAS_FILE_NAME" VALUE="##KEYTAB_PATH_AND_FILE_NAME##" />
      <PROPERTY ID="KRB_REALM_FILE_NAME" VALUE="##REALM_CONFIG_PATH_AND_FILE_NAME##" />
    </CONNECTION_PROPERTIES>
  </SCHEMA>
</SCHEMAS>
</APPPACKSCHEMA>
```

Table 31: OFS_OIDF_SCHEMA_BIGDATA_IN.xml file (SCHEMA type HDFS Parameters for Stage on Hive and Results on RDBMS)

Tag Name/ Attribute Name	Description	Mandatory (Y/N)	Default Value/ Permissible Value	Comments
<SCHEMAS>/TYPE=HDFS	Type of schemas created.	Y		Refers to the DATADOM of the Application Pack installed.

Tag Name/ Attribute Name	Description	Mandatory (Y/N)	Default Value/ Permissible Value	Comments
<HIVE_SERVER_HOST>	IP or HostName of the server where HIVE is installed.	Y		
<HIVE_LIB_PATH>	Folder path where HIVE related drivers or jar files are copied.	Y		Needs to contain the list of jars mentioned in the section Copy the Jar Files to the OFSAA Installation Directory and krb5.conf, keytab files. Manually copy the preceding listed files from CDH distribution to this identified folder. NOTE: The Cloudera administrator provides these two files krb5.conf and keytab.
<SCHEMA>/NAME	By default, the schema names are seeded based on the Application Pack. You can edit the schema names if required. NOTE: The Schema Name has a prefix of the SETUPINFO/NAME attribute.	Y	The permissible length is 20 characters and only alphanumeric characters are allowed. Example: HIVEHYBDATADOM	Schema Name should not be the same as Schema Name specified for Schema Type ATOMIC.
<SCHEMA>/TYPE	Identifies the type of schema where the Data Model entities reside.	Y	By default, the TYPE attribute in this tag is set to DATADOM.	DO NOT modify this value.
<SCHEMA>/APP_ID	By default, the Application ID is seeded based on the Application Pack.	Y	The supported value is OFS_OIDFHV.	
<SCHEMA>/DB_TYPE	Identifies the type of driver to be used for the connection.	Y	By default, the only supported type is HIVE in this release.	In the upcoming releases, the type of value can be HIVE, IMPALA, and so on.

Tag Name/ Attribute Name	Description	Mandatory (Y/N)	Default Value/ Permissible Value	Comments
<SCHEMA>/INFODOM	Enter the name of the Information Domain to associate this schema. The schema creator utility automatically derives an Information Domain Name based on the Application Pack if the value is not specified for this attribute.	N	Permissible length is 16 characters and only alphanumeric characters are allowed. No special characters are allowed. For example: ##MY_HIVE_INFODOM## For Hive part in Stage on Hive and Results on RDBMS: Example: OIDFHVINFO	
<SCHEMA_PROPERTIES>/<PROPERTY>/COMMENT	COMMENTS for HIVE schema.	N		
<SCHEMA_PROPERTIES>/<PROPERTY>/LOCATION	You can optionally specify a location for the table data.	N	hdfs:// ##HIVE_SERVER_HOST_NAME_OR_IP##:NameNodePort/user/hive/warehouse/<<PREFIX>>_<<SCHEMA_NAME>>/ NOTE: The <<PREFIX>> prefix is applicable only if the <PREFIX_SCHEMA_NAME> tag is "Y" in the <SETUPINFO> tag. For example: When <SETUPINFO NAME="OIDF" PREFIX_SCHEMA_NAME="Y"/>. <<SCHEMA_NAME>> is the DATADOM schema name. Example: hdfs:// whf00bsy.in.oracle.com:8020/user/hive/warehouse/OIDF_BSYDATADOM/	

Tag Name/ Attribute Name	Description	Mandatory (Y/N)	Default Value/ Permissible Value	Comments
<CONNECTION_PROPERTIES>/<PROPERTY>/JDBC_DRIVER	HIVE JDBC driver details.	Y	com.cloudera.hive.jdbc4.HS2Driver	The default cloudera HiveServer 2 driver name.
<CONNECTION_PROPERTIES>/<PROPERTY>/JDBC_URL	Enter the HIVE JDBC URL.	Y	A valid Hive JDBC URL to be specified. jdbc:hive2://###HIVE_SERVER_HOST_NAME_OR_IP###:10000/<<PREFIX>>_<<SCHEMA_NAME>>;AuthMech=1;KrbServiceName=hive;KrbHostFQDN=###HIVE_SERVER_HOST_NAME_OR_IP###;KrbRealm=###REALM### NOTE: <<PREFIX>> Prefix is applicable only if the <PREFIX_SCHEMA_NAME> tag is Y in <SETUPINFO> tag. For example, when <SETUPINFO NAME="OIDF" PREFIX_SCHEMA_NAME="Y"/>. <<SCHEMA_NAME>> is the DATADOM schema name. For example: jdbc:hive2://whf00bsy.in.oracle.com:10000/OIDF_BSYDATADOM;AuthMech=1;KrbServiceName=hive;KrbHostFQDN=whf00bsy.in.oracle.com;KrbRealm=WHFBSY.ORACLE.COM	Specify the Hive JDBC URL to connect to the Hive Server.
<CONNECTION_PROPERTIES>/<PROPERTY>/AUTH_TYPE	Authentication Type.	Y	Permissible values: KERBEROS_WITH_KEYTAB.	Only "Kerberos with keytab" based authentication is supported in this release.
<CONNECTION_PROPERTIES>/<PROPERTY>/AUTH_ALIAS	Alias name for authentication credentials.	Y		An Alias name mapping to a principal and password combination is specified in the following tags.

Tag Name/ Attribute Name	Description	Mandatory (Y/N)	Default Value/ Permissible Value	Comments
<CONNECTION_PROPERTIES>/<PROPERTY>/PRINCIPAL	Authentication Principal name.	Y		Principal name used in authentication to connect to the Hive Server.
<CONNECTION_PROPERTIES>/<PROPERTY>/PASSWORD	Authentication password.	Y		Password used in authentication to connect to the Hive Server.
<CONNECTION_PROPERTIES>/<PROPERTY>/KRB_GSSJAAS_FILE_NAME	A keytab file containing pairs of Kerberos principals and an encrypted copy of that principal's key.	Y		This file needs to be copied to the location specified in <HIVE_LIB_PATH>.
<CONNECTION_PROPERTIES>/<PROPERTY>/KRB_REALM_FILE_NAME	REALM configuration file.	Y		This file needs to be copied to the location specified in <HIVE_LIB_PATH>.

4. Save the file.

5.6 Configure the OFSAAI_InstallConfig.xml File

To configure the OFS_InstallConfig.xml file, follow these steps:

1. Navigate to the OFS_OIDF_PACK/OFS_AAI/conf/ directory.
2. Open the OFSAAI_InstallConfig.xml file in a text editor.
3. Configure the OFSAAI_InstallConfig.xml file as mentioned in the following table.

You must manually set the InteractionVariable parameter values as mentioned in the table. If a value is not applicable, enter NA. Ensure that the value is not entered as NULL.

Table 32: OFSAA Infrastructure Installation Tasks and Descriptions

InteractionVariable Name	Significance and Expected Value	Mandatory
<Layer name="GENERAL">		
InteractionGroup name="WebServerType"		
WEBAPPSERVERTYPE	Identifies the web application server on which the OFSAA Infrastructure web components are deployed. Set the following numeric value depending on the type of web application server: <ul style="list-style-type: none"> • Apache Tomcat = 1 • IBM WebSphere Application Server = 2 • Oracle WebLogic Server = 3 For example, <InteractionVariable name="WEBAPPSERVERTYPE">3</InteractionVariable>	Yes
InteractionGroup name="OFSAA Infrastructure Server Details"		
DBSERVER_IP	Identifies the hostname or IP address of the system on which the Database Engine is hosted. NOTE: For RAC Database, the value must be NA. For example, <InteractionVariable name="DBSERVER_IP">14.15.16.17</InteractionVariable> or <InteractionVariable name="DBSERVER_IP">dbhost.server.com</InteractionVariable>	Yes
InteractionGroup name="Database Details"		
ORACLE_SID/SERVICE_NAME	Identifies the Oracle DB Instance SID or SERVICE_NAME NOTE: The Oracle_SID value must be the same as it is mentioned in JDBC_URL. For example, <InteractionVariable name="ORACLE_SID/SERVICE_NAME">ofsaser</InteractionVariable>	Yes
ABS_DRIVER_PATH	Identifies the directory where the JDBC driver (ojdbc<version>.jar) exists. This is typically the \$ORACLE_HOME/jdbc/lib directory.	Yes

InteractionVariable Name	Significance and Expected Value	Mandatory
	<p>For example, <InteractionVariable name="ABS_DRIVER_PATH">">/oradata6/revwb7/ oracle </InteractionVariable></p> <p>NOTE: See the Hardware and Software Requirements section to identify the correct ojdbc<version>.jar file version to be copied.</p>	
InteractionGroup name="OLAP Detail"		
OLAP_SERVER_IMPLEMENTATION	<p>Identifies whether the OFSAA Infrastructure OLAP component must be configured. It depends on whether you intend to use the OLAP feature. The following numeric value must be set depending on the choice:</p> <ul style="list-style-type: none"> • YES: 1 • NO: 0 <p>NOTE: If the value for OLAP_SERVER_IMPLEMENTATION is set to 1, the installer checks if the following environment variables are set in the .profile file:</p> <ul style="list-style-type: none"> • ARBORPATH • HYPERION_HOME • ESSBASEPATH 	No
InteractionGroup name="SFTP Details"		
SFTP_ENABLE	<p>Identifies if the SFTP (Secure File Transfer Protocol) feature is to be enabled. The following numeric value must be set depending on the choice:</p> <ul style="list-style-type: none"> • SFTP: 1 • FTP: 0 	Yes
<p>NOTE: The default value for SFTP_ENABLE is 1, which signifies that SFTP is used. Oracle recommends using SFTP instead of FTP because SFTP is more secure. However, you can ignore this recommendation and use FTP by setting SFTP_ENABLE to 0. You can change this selection later from the OFSAAI administration interface.</p> <p>Set SFTP_ENABLE to -1 to configure ftpshare and webllocal path as a local path mounted for the OFSAAI server.</p>		
FILE_TRANSFER_PORT	<p>Identifies the port used for the file transfer service. The default value specified is 22 (SFTP). Specify the value like 21 or any other PORT value if the value for SFTP_ENABLE is 0.</p> <p>For example, <InteractionVariable name="FILE_TRANSFER_PORT">21</InteractionVariable></p>	Yes
InteractionGroup name="Locale Detail"		
LOCALE	<p>Identifies the locale information to be used during the installation. This release of the OFSAA Infrastructure supports only US English.</p> <p>For example, <InteractionVariable name="LOCALE">en_US</InteractionVariable></p>	Yes
InteractionGroup name="OFSAA Infrastructure Communicating ports"		
<p>NOTE: The following ports are used internally by the various OFSAA Infrastructure services. The default values mentioned are set in the installation. If you intend to specify a different value, update the parameter value accordingly, ensure that the port value is in the range 1025 to 65535, and the respective port is enabled.</p>		
JAVAPORT	9999	Yes

InteractionVariable Name	Significance and Expected Value	Mandatory
NATIVEPORT	6666	Yes
AGENTPORT	6510	Yes
ICCPORT	6507	Yes
ICCNATIVEPORT	6509	Yes
OLAPPORT	10101	Yes
MSGPORT	6501	Yes
ROUTERPORT	6500	Yes
AMPORT	6505	Yes
InteractionGroup name="Web Details"		
NOTE: If the value for HTTPS_ENABLE is set to 1 , ensure that you have a valid certificate available from a trusted CA and it is configured on your web application server.		
HTTPS_ENABLE	<p>Identifies whether the UI must be accessed using HTTP or HTTPS scheme. The default value is set to 0. The numeric value must be set depending on the following options:</p> <ul style="list-style-type: none"> • YES: 1 • NO: 0 <p>For example, <code><InteractionVariable name="HTTPS_ENABLE">0</InteractionVariable></code></p>	Yes
WEB_SERVER_IP	<p>Identifies the HTTP Server IP/Hostname or Web application server IP/Hostname, to be used to access the UI. This IP is typically the HTTP Server IP.</p> <p>If a separate HTTP Server is not available, then the value must be Web application server IP/Hostname.</p> <p>For example, <code><InteractionVariable name="WEB_SERVER_IP">10.11.12.13</InteractionVariable></code></p> <p>or</p> <p><code><InteractionVariable name="WEB_SERVER_IP">myweb.server.com</InteractionVariable></code></p>	No
WEB_SERVER_PORT	<p>Identifies the Web Server Port, which is typically 80 for non SSL and 443 for SSL. If a separate HTTP Server exists, the port value must be the value configured for the Web Server.</p> <p>Warning: The installer will not accept the port value as:</p> <ul style="list-style-type: none"> • 80, if the HTTPS_ENABLE variable is 1 • 443, if the HTTPS_ENABLE variable is 0 <p>For example, <code><InteractionVariable name="WEB_SERVER_PORT">80</InteractionVariable></code></p>	No
CONTEXT_NAME	<p>Identifies the web application context name which is used to build the URL to access the OFSAA application. You can identify the context name from the following URL format:</p> <p><code><scheme>://<host>:<port>/<context-name>/login.jsp</code></p> <p>The following is an example:</p>	Yes

InteractionVariable Name	Significance and Expected Value	Mandatory
	<p>https://myweb:443/ofsaadev/login.jsp</p> <p>For example, <InteractionVariable name="CONTEXT_NAME">ofsaadev</InteractionVariable></p>	
WEBAPP_CONTEXT_PATH	<p>Identifies the absolute path of the exploded EAR file on the web application server.</p> <ul style="list-style-type: none"> For Tomcat, specify the Tomcat directory path till /webapps. For example, /oradata6/revwb7/tomcat/webapps/. For WebSphere, specify the WebSphere path as <WebSphere profile directory>/installedApps/<NodeCellName>. For example, /data2/test//WebSphere/AppServer/profiles/<ProfileName>/installedApps/aiximfNode01Cell, where aix-imf is the Host name. For WebLogic, specify the WebLogic home directory path. For example, /<WebLogic home directory path>/bea/wlserver_10.3 <p>NOTE: For WebLogic, the value specified for this attribute is ignored and the value provided against the attribute WEBLOGIC_DOMAIN_HOME is considered.</p>	Yes
WEB_LOCAL_PATH	<p>Identifies the absolute path to any directory on the web application server that can hold temporary files, which are uploaded as part of the usage of the application.</p> <p>Set this in the FTPSHARE location.</p> <p>NOTE: During a clustered deployment, ensure that this path and the directory are the same on all the nodes.</p>	Yes
InteractionGroup name="Weblogic Setup Details"		
WEBLOGIC_DOMAIN_HOME	<p>Identifies the WebLogic Domain Home.</p> <p>For example, <InteractionVariable name="WEBLOGIC_DOMAIN_HOME">/home/weblogic/bea/user_projects/domains/mydomain</InteractionVariable></p>	Yes. Specify the value only if WEBAPPSERVER VERTYPE is set as 3 (WebLogic)
InteractionGroup name="OFSAAI FTP Details"		
OFSAAI_FTPSHARE_PATH	<p>Identifies the absolute path of the directory that is identified as the file system stage area.</p> <p>NOTE: The directory must exist on the same system on which the OFSAAI Infrastructure is being installed (can be on a separate mount).</p> <p>The user mentioned in the APP_SFTP_USER_ID parameter in the following example must have RWX permission on the directory.</p> <p>For example, <InteractionVariable name="APP_FTPSHARE_PATH">>/oradata6/revwb7/ftpshare</InteractionVariable></p>	Yes
OFSAAI_SFTP_USER_ID	<p>Identifies the user who has RWX permissions on the directory identified for the parameter APP_FTPSHARE_PATH.</p>	Yes

InteractionVariable Name	Significance and Expected Value	Mandatory
OFSAAI_SFTP_PRIVATE_KEY	<p>Identifies the SFTP private key for OFSAAI.</p> <p>For example,</p> <pre><InteractionVariable name="OFSAAI_SFTP_PRIVATE_KEY">/home/ofsaapp/.ssh/id_ rsa</InteractionVariable></pre> <p>By default, the value is NA, which indicates that, for authentication, you are prompted to enter the password for the user <OFSAAI_SFTP_USER_ID>.</p> <p>For more information on how to generate an SFTP Private key, see the Set Up SFTP Private Key section.</p>	No
OFSAAI_SFTP_PASSPHRASE	<p>Identifies the passphrase for the SFTP private key for OFSAAI.</p> <p>For example,</p> <pre>InteractionVariable name="OFSAAI_SFTP_PASSPHRASE">enter a pass phrase here</InteractionVariable></pre> <p>By default, the value is NA.</p> <p>If the OFSAAI_SFTP_PRIVATE_KEY value is given and the OFSAAI_SFTP_PASSPHRASE value is NA, then the passphrase is identified as empty.</p>	No
<p>InteractionGroup name="Hive Details"</p> <p>The default value set for the interaction variables under this group is NA.</p> <p>NOTE: The following values are required only for Hive Configuration.</p>		
HIVE_SERVER_PORT	<p>Identifies the port used for the file transfer service. The default value is 22 (SFTP). To use this port for FTP, set this value to 21.</p> <p>For example,</p> <pre><InteractionVariable name="HIVE_SERVER_PORT">22</InteractionVariable></pre>	Yes
HIVE_SERVER_FTPDRIVE	<p>Identifies the absolute path to the directory identified as the file system stage area of the HIVE server.</p> <p>For example,</p> <pre><InteractionVariable name="HIVE_SERVER_FTPDRIVE">/scratch/ofsa/ftpshare</ InteractionVariable></pre>	Yes
HIVE_SERVER_FTP_USERID	<p>Identifies the user who has RWX permissions on the directory identified under the parameter HIVE_SERVER_FTPDRIVE.</p> <p>For example,</p> <pre><InteractionVariable name="HIVE_SERVER_FTP_USERID">ofsa</InteractionVariable></pre>	Yes
HIVE_SERVER_FTP_PROTOCOL	<p>If the HIVE_SERVER_PORT is 21, then set the value to FTP. If not, set it to SFTP.</p> <p>For example,</p> <pre><InteractionVariable name="HIVE_SERVER_FTP_PROTOCOL">SFTP</InteractionVariable></pre>	Yes

InteractionVariable Name	Significance and Expected Value	Mandatory
HIVE_SFTP_PRIVATE_KEY	<p>Identifies the SFTP private key for the HIVE server.</p> <p>For example,</p> <pre><InteractionVariable name="HIVE_SFTP_PRIVATE_KEY"/>/scratch/testuser/.ssh/id_rsa</InteractionVariable></pre> <p>By default, the value is NA, which indicates that, for authentication, you are prompted to enter the password for the user <HIVE_SERVER_FTP_USERID>.</p> <p>For more information on generating SFTP Private key, see the Set Up SFTP Private Key section.</p>	
HIVE_SFTP_PASSPHRASE	<p>Identifies the passphrase for the SFTP private key for HIVE.</p> <p>For example,</p> <pre><InteractionVariable name="HIVE_SFTP_PASSPHRASE">NA</InteractionVariable></pre> <p>By default, the value is NA.</p> <p>If the HIVE_SFTP_PRIVATE_KEY value is NA, then the passphrase is identified as empty.</p>	

5.6.1 Set Up the SFTP Private Key

Log in to OFSAA UNIX user using the Putty tool, where you plan for installation and generate a pair of authentication keys using the `ssh-keygen` command. If required, set a passphrase. Otherwise, the OFSAAI_SFTP_PASSPHRASE tag must be set to NA.

To generate a private key, enter the commands as shown:

```
ssh-keygen -t rsa
Generating public/private rsa key pair.
Enter file in which to save the key (/home/ofsaapp/.ssh/id_rsa):
Created directory '/home/ofsaapp/.ssh'.
Enter passphrase (empty for no passphrase):
Enter same passphrase again:
Your identification has been saved in /home/ofsaapp/.ssh/id_rsa.
Your public key has been saved in /home/ofsaapp/.ssh/id_rsa.pub.
The key fingerprint is:
3e:4f:05:79:3a:9f:96:7c:3b:ad:e9:58:37:bc:37:e4
ofsaapp@OFSASERVER:~> cat /home/ofsaapp/.ssh/id_rsa.pub >>
/home/ofsaapp/.ssh/authorized_keys
```

Ensure the following permissions exist for the given directories:

- Permissions of `.ssh` must be 700
- Permissions of `.ssh/authorized_keys` must be 640
- Permissions of `.ssh/id_rsa` must be 400

- Permissions of UNIX User created must be 755

5.7 Configure the Silent.props File

Topics:

- [Silent.template for RDBMS](#)
- [Silent.BIGDATA.template for Stage and Results on Hive](#)
- [Silent_Hybrid.template for Stage on Hive and Results on RDBMS](#)

ATTENTION

Do not install the new applications in the same segment if the preinstalled applications use Run Management.

5.7.1 Silent.template for RDBMS

This section is applicable for the newly licensed ODF Application Pack Release 8.1.0.0 installation in the RDBMS mode.

NOTE

In an integrated environment, Oracle recommends the customers use the same Staging source in the `Silent.props` file for the T2Ts that load data from the Stage tables into the Result tables.

To configure the `Silent.props` file for the fresh or new RDBMS installation, follow these steps:

1. Navigate to the `OFS_OIDF_PACK/appsLibConfig/conf/` directory.
2. Rename the `Silent.template` file to `Silent.props`.
3. Edit the `Silent.props` file in a text editor and mention the parameters mentioned in the following table.

Figure 19: Sample of the Silent.props file (Silent.template) for the RDBMS installation

```

# Specify Log Mode
# 1 = DEBUG Mode [Password will be printed in the log file]
# 0 = GENERAL Mode [Passwords will not be printed in the log file]
# Default is GENERAL
LOG_MODE=0

# Specify the Oracle Insurance Data foundation Segment Code
SEGMENT_1_CODE=

# Specify the Infodom Maintenance log path(to be created) for the new Infodom
# Please ignore if you are doing installation on an existing information domain
APPFTP_LOG_PATH=
DBFTP_LOG_PATH=

# Specify wheter you want to perform Model Upload
# 0 = If you have already performed Model Upload and want to skip model upload process
# 1 = If you want to perform Model Upload
UPLOAD_MODEL=

# Specify whether you want to use the released datamodel or customized datamodel for model upload process
# 0 = If you want to upload the released datamodel
# 1 = If you want to upload the customized datamodel
MODEL_TYPE=

# Specify the path(DM_DIRECTORY) and file(DATAMODEL) name for the cutomized datamodel
# Mandatory only if you want to upload the customized datamodel
# i.e you have specified MODEL_TYPE=1
DATAMODEL=
DM_DIRECTORY=

#Please specify if you want create new ETL Src or use an existing one.
# 0 = If you want to create a new ETL src
# 1 = If you want to use an existing src
ETL_APPSRC_TYPE=

# Specify the ETL and Source Name into ETL Area Definitions will be deployed. This is a Mandatory Field.
# Give new ETL SRC Names, if you have specified ETL_APPSRC_TYPE=0
# Give Exisitng ETL SRC Names, if you have specified ETL_APPSRC_TYPE=1
# Specify the ETL Application and Source Name into ETL Area Definitions will be deployed

#ETL FSDF Staging Source Name
ETL_SRC_1_NAME=
#ETL FSDF CAP ADQ Pack Integration Source Name
ETL_SRC_2_NAME=
#ETL FSDF TR Pack Integration Source Name
ETL_SRC_3_NAME=
#ETL FSDF IFRS Pack Integration Source Name
ETL_SRC_4_NAME=

# Please give description for the ETL App/Src pair
# Mandatory if you want to create new ETL app/src pair
# i.e you have specified ETL_APPSRC_TYPE=0

#ETL FSDF Staging Source Description
ETL_SRC_1_DESC=
#ETL FSDF CAP ADQ Pack Integration Source Description
ETL_SRC_2_DESC=
#ETL FSDF TR Pack Integration Source Description
ETL_SRC_3_DESC=
#ETL FSDF IFRS Pack Integration Source Description
ETL_SRC_4_DESC=

#Support for Parallelism
#ENABLE_CONCURRENCY=1
#CONCURRENCY_LEVEL=10

```

Table 33: Parameters for the Silent.props File (Silent.template)

Property Name	Description of Property	Permissible values	Comments
LOG_MODE	Mode for logging	0 = Debug 1= General	# Optional; Default: 0
SEGMENT_1_CODE	Segment Code	Example: OI DFSEG	# Mandatory Segment Code must not exceed 10 characters and no special characters or extra spaces are allowed.
APPFTP_LOG_PATH	Information Domain Maintenance log path(to be created) for the new information Domain for App Layer	Example: /ftpshare/<INFODOM_NAME>/logs	# Mandatory if this an App Layer Installation and need to create an Information Domain
DBFTP_LOG_PATH	Information Domain Maintenance log path(to be created) for the new Information Domain for DB Layer	Example: /ftpshare/<INFODOM_NAME>/logs	# Mandatory if this an App Layer Installation and need to create an Information Domain
UPLOAD_MODEL	Whether you need to perform Model Upload	0 = No 1 = Yes	# Mandatory
MODEL_TYPE	Released Data Model or Customized Data Model	0 = released 1 = customized	# Mandatory only in the case of UPLOAD_MODEL=1
DATAMODEL	The file name for the customized Data Model	Not Applicable	# Mandatory only in the case of uploading the customized Data Model # Option selected for MODEL_TYPE=1
DM_DIRECTORY	The path for the customized Data Model	Not Applicable	# Mandatory only in the case of uploading the customized Data Model # Option selected for MODEL_TYPE=1
ETL_APPSRC_TYPE	The ETL application name	0 = New Pair 1 = Existing	# Mandatory
ETL_SRC_1_NAME	ETL OI DF Staging Source Name	Example: STAGING	# Mandatory
ETL_SRC_2_NAME	ETL OI DF CAP ADQ Pack Integration Source Name	Example: OI DF_CAP_SRC	# Mandatory
ETL_SRC_3_NAME	ETL OI DF TR Pack Integration Source Name	Example: OI DF_TR_SRC	# Mandatory

Property Name	Description of Property	Permissible values	Comments
ETL_SRC_4_NAME	ETL OIDF IFRS Pack Integration Source Name	Example: OI DF_IFRS_SRC	# Mandatory
ETL_SRC_1_DESC	ETL OIDF Staging Source Description	Example: STAGING	# Mandatory
ETL_SRC_2_DESC	ETL OIDF CAP ADQ Pack Integration Source Description	Example: OI DF_CAP_SRC	# Mandatory
ETL_SRC_3_DESC	ETL OIDF TR Pack Integration Source Description	Example: OI DF_TR_SRC	# Mandatory
ETL_SRC_4_DESC	ETL OIDF IFRS Pack Integration Source Description	Example: OI DF_IFRS_SRC	# Mandatory
ENABLE_CONCURRENCY	#Support for Parallelism	0 = No 1 = Yes	#Optional
CONCURRENCY_LEVEL	#Support for Parallelism	Example: CONCURRENCY_LEVEL=10 , which means 10 threads are triggered to handle the processing of fsapps.	#Optional

4. Save the file.

5.7.2 Silent.BIGDATA.template for Stage and Results on Hive

This section is applicable for the newly licensed OIDF Application Pack Release 8.1.0.0 installation in the Big Data mode (Stage and Results on Hive).

To configure the `Silent.props` file for the fresh or new Big Data installation, follow these steps:

1. Navigate to the `OFS_OIDF_PACK/appsLibConfig/conf/` directory.
2. Rename the file `Silent.BIGDATA.template` to `Silent.props`.
3. Edit the `Silent.props` file in a text editor and mention the parameters mentioned in the following table.

Figure 20: Sample of the Silent.props file (Silent.BIGDATA.template) for the Big Data installation

```
# Specify Log Mode
# 1 = DEBUG Mode [Password will be printed in the log file]
# 0 = GENERAL Mode [Passwords will not be printed in the log file]
# Default is GENERAL
LOG_MODE=0

# Specify the Oracle Insurance Data foundation Segment Code
SEGMENT_1_CODE=

# Specify the Infodom Maintenance log path(to be created) for the new Infodom
# Please ignore if you are doing installation on an existing information domain
HIVE_APPFTP_LOG_PATH=
HIVE_DBFTP_LOG_PATH=

# Specify wheter you want to perform Model Upload on hive infodom
# 0 = If you have already performed Model Upload and want to skip model upload process
# 1 = If you want to perform Model Upload
HIVE_UPLOAD_MODEL=

# Specify whether you want to use the released datamodel or customized datamodel for model upload process
# 0 = If you want to upload the released datamodel
# 1 = If you want to upload the customized datamodel
HIVE_MODEL_TYPE=

# Specify the path(DM_DIRECTORY) and file(DATAMODEL) name for the cutomized datamodel
# Mandatory only if you want to upload the customized datamodel
# i.e you have specified MODEL_TYPE=1
DATAMODEL_HIVE=
DM_DIRECTORY=

#Please specify if you want create new ETL Src or use an existing one.
# 0 = If you want to create a new ETL src
# 1 = If you want to use an existing src
ETL_APPSRC_TYPE=

# Specify the ETL and Source Name into ETL Area Definitions will be deployed. This is a Mandatory Field.
# Give new ETL SRC Names, if you have specified ETL_APPSRC_TYPE=0
# Give Exisitng ETL SRC Names, if you have specified ETL_APPSRC_TYPE=1
# Specify the ETL Application and Source Name into ETL Area Definitions will be deployed

#ETL StagingHive Source Name
ETL_SRC_5_NAME=
ETL_SRC_5_DESC=
```

Table 34: Parameters for the Silent.props File (Silent.BIGDATA.template)

Property Name	Description of Property	Permissible values	Comments
LOG_MODE	Mode for logging	0 = Debug 1= General	# Optional; Default: 0
SEGMENT_1_CODE	Segment Code	Example: O1DFSEG	# Mandatory Segment Code must not exceed 10 characters and no special characters or extra spaces are allowed.

Property Name	Description of Property	Permissible values	Comments
HIVE_APPFTP_LOG_PATH	Infodom Maintenance log path(to be created) for the new Infodom	Example: /scratch/ofsaa/ftpshare/OI DFINFO/logs	# Mandatory to create a new Information Domain
HIVE_DBFTP_LOG_PATH	Information Domain Maintenance log path (to be created) for the new Information Domain for DB Layer	Example: /scratch/ofsaa/ftpshare/OI DFINFO/logs	# Mandatory to create a new Information Domain
HIVE_UPLOAD_MODEL	Whether you need to perform Model Upload on Hive Infodom	0 = No 1 = yes	# Mandatory
HIVE_MODEL_TYPE	Released Data Model or Customized Data Model for model upload process	0 = released 1 = customized	# Option selected for HIVE_MODEL_TYPE=0
DATAMODEL_HIVE	The file name for the customized Data Model in Hive	Not Applicable	# Mandatory only in the case of uploading the customized Data Model # Option selected for HIVE_MODEL_TYPE=1
DM_DIRECTORY	The path for the customized Data Model	Not Applicable	# Mandatory only in the case of uploading the customized Data Model # Option selected for HIVE_MODEL_TYPE=1
ETL_APPSRC_TYPE	The ETL application name	0=New Pair 1=Existing	# Mandatory
ETL_SRC_5_NAME	ETL ODF HIVE Staging Source Name	Example: STAGING	# Mandatory
ETL_SRC_5_DESC	ETL ODF HIVE Staging Source description	Example: STAGING	# Mandatory
ENABLE_CONCURRENCY	#Support for Parallelism	0 = No 1 = Yes	#Optional
CONCURRENCY_LEVEL	#Support for Parallelism	Example: CONCURRENCY_LEVEL=10, which means 10 threads are triggered to handle the processing of fsapps.	#Optional

4. Save the file.

5.7.3 **Silent_Hybrid.template for Stage on Hive and Results on RDBMS**

This section is applicable for the newly licensed OIDF Application Pack Release 8.1.0.0.0 installation in the Big Data mode (Stage on Hive and Results on RDBMS).

To configure the `Silent.props` file for the fresh or new Big Data installation, follow these steps:

1. Navigate to the `OFS_OIDF_PACK/appsLibConfig/conf/` directory.
2. Rename the file `Silent_Hybrid.template` to `Silent.props`.
3. Edit the `Silent.props` file in a text editor and mention the parameters mentioned in the following table.

Figure 21: Sample of the Silent.props file (Silent_Hybrid.template) for the Big Data installation

```

# Specify Log Mode
# 1 = DEBUG Mode [Password will be printed in the log file]
# 0 = GENERAL Mode [Passwords will not be printed in the log file]
# Default is GENERAL
LOG_MODE=0

# Specify the Oracle Insurance Data foundation Segment Code
SEGMENT_1_CODE=

# Specify the Infodom Maintenance log path(to be created) for the new Infodom
# Please ignore if you are doing installation on an existing information domain
APPFTP_LOG_PATH=
DBFTP_LOG_PATH=

# Specify the Infodom Maintenance log path(to be created) for the new hive Infodom
# Please ignore if you are doing installation on an existing information domain
HIVE_APPFTP_LOG_PATH=
HIVE_DBFTP_LOG_PATH=

# Specify wheter you want to perform Model Upload
# 0 = If you have already performed Model Upload and want to skip model upload process
# 1 = If you want to perform Model Upload
UPLOAD_MODEL=

# Specify whether you want to use the released datamodel or customized datamodel for model upload process
# 0 = If you want to upload the released datamodel
# 1 = If you want to upload the customized datamodel
MODEL_TYPE=

# Specify the path(DM_DIRECTORY) and file(DATAMODEL) name for the cutomized datamodel
# Mandatory only if you want to upload the customized datamodel
# i.e you have specified MODEL_TYPE=1
DATAMODEL=
DM_DIRECTORY=

# Specify wheter you want to perform Model Upload on hive infodom
# 0 = If you have already performed Model Upload and want to skip model upload process
# 1 = If you want to perform Model Upload
HIVE_UPLOAD_MODEL=

# Specify whether you want to use the released datamodel or customized datamodel for model upload process
# 0 = If you want to upload the released datamodel
# 1 = If you want to upload the customized datamodel
HIVE_MODEL_TYPE=

# Specify the path(DM_DIRECTORY) and file(DATAMODEL_HIVE) name for the cutomized datamodel
# Mandatory only if you want to upload the customized datamodel
# i.e you have specified HIVE_UPLOAD_MODEL=1
DATAMODEL_HIVE=
DM_DIRECTORY=

#Please specify if you want create new ETL Src or use an existing one.
# 0 = If you want to create a new ETL src
# 1 = If you want to use an existing src
ETL_APPSRC_TYPE=

# Specify the ETL and Source Name into ETL Area Definitions will be deployed. This is a Mandatory Field.
# Give new ETL SRC Names, if you have specified ETL_APPSRC_TYPE=0
# Give Existing ETL SRC Names, if you have specified ETL_APPSRC_TYPE=1
# Specify the ETL Application and Source Name into ETL Area Definitions will be deployed

#ETL ODF Staging Source Name
ETL_SRC_1_NAME=

# Please give description for the ETL App/Src pair
# Mandatory if you want to create new ETL app/src pair
# i.e you have specified ETL_APPSRC_TYPE=0

#ETL ODF Staging Source Description
ETL_SRC_1_DESC=

ETL_SRC_2_NAME=NOT_USED
ETL_SRC_2_DESC=NOT_USED_SOURCE

```

Table 35: Parameters for the Silent.props File (Silent.BIGDATA.template)

Property Name	Description of Property	Permissible values	Comments
LOG_MODE	Mode for logging	0 = Debug 1= General	# Optional; Default: 0
SEGMENT_1_CODE	Segment Code	Example: OIDFSEG	# Mandatory Segment Code must not exceed 10 characters and no special characters or extra spaces are allowed.
HIVE_APPFTP_LOG_PATH	Infodomain Maintenance log path(to be created) for the new Infodomain	Example: /scratch/ofsaa/ftpshare/OIDFINFO/logs	# Mandatory to create a new Information Domain
HIVE_DBFTP_LOG_PATH	Information Domain Maintenance log path (to be created) for the new Information Domain for DB Layer	Example: /scratch/ofsaa/ftpshare/OIDFINFO/logs	# Mandatory to create a new Information Domain
HIVE_UPLOAD_MODEL	Whether you need to perform Model Upload on Hive Infodomain	0 = No 1 = yes	# Mandatory
HIVE_MODEL_TYPE	Released Data Model or Customized Data Model for model upload process	0 = released 1 = customized	# Option selected for HIVE_MODEL_TYPE=0
DATAMODEL_HIVE	The file name for the customized Data Model in Hive	Not Applicable	# Mandatory only in the case of uploading the customized Data Model # Option selected for HIVE_MODEL_TYPE=1
DM_DIRECTORY	The path for the customized Data Model	Not Applicable	# Mandatory only in the case of uploading the customized Data Model # Option selected for HIVE_MODEL_TYPE=1
ETL_APPSRC_TYPE	The ETL application name	0=New Pair 1=Existing	# Mandatory
ETL_SRC_5_NAME	ETL OIDF HIVE Staging Source Name	Example: STAGING	# Mandatory
ETL_SRC_5_DESC	ETL OIDF HIVE Staging Source description	Example: STAGING	# Mandatory
ENABLE_CONCURRENCY	#Support for Parallelism	0 = No 1 = Yes	#Optional
CONCURRENCY_LEVEL	#Support for Parallelism	Example: CONCURRENCY_LEVEL=10, which means 10 threads are	#Optional

Property Name	Description of Property	Permissible values	Comments
		triggered to handle the processing of fsapps.	

4. Save the file.

5.8 Backup the Configuration Files

Back up the following configuration files by creating a copy of the files in a separate directory. Ensure not to store this backup directory in the OIDF v8.1.0.0.0 kit:

Table 36: Directory of Files to Backup

File Name	Directory
OFS_OIDF_SCHEMA_IN.xml and OFS_OIDF_SCHEMA_BIGDATA_IN.xml	OFS_OIDF_PACK/schema_creator/conf
OFS_OIDF_SCHEMA_OUTPUT.xml	OFS_OIDF_PACK/schema_creator/
Silent.props	OFS_OIDF_PACK/appsLibConfig/conf
OFSAAI_InstallConfig.xml	OFS_OIDF_PACK/OFS_AAI/conf/

You can reuse the files in the future to upgrade the existing applications or install new applications.

5.9 Execute the Schema Creator Utility

Depending on the option selected to run the OFSAA Application Pack installer, you must select the appropriate schema creator utility execution mode from the following options: in

- [Execute the Schema Creator Utility in Offline Mode](#)
- [Execute the Schema Creator Utility in Online Mode](#)
- [Execute the Schema Creator Utility in TCPS Mode](#)
- [Execute the Schema Creator Utility when Installing the subsequent Applications Pack](#)

5.9.1 Execute the Schema Creator Utility in Offline Mode

Choose the Offline Mode option, if you do not have login credentials to the database with SYSDBA privileges. In this mode, the utility generates an SQL script with all the required DDLs for Users, Objects, and Grants. That script must be executed by the DBA on the appropriate database identified for OFSAA usage.

To execute the schema creator utility in the offline mode, you must have the following privileges:

- SELECT ON DBA_ROLES
- SELECT ON DBA_USERS

- SELECT ON DBA_DIRECTORIES
- SELECT ON DBA_TABLESPACES
- CREATE SESSION

NOTE

Explicit Grants to the user are required. Grants assigned through Roles are not supported.

To execute the schema creator utility in the offline mode, follow these steps:

1. Log in to the system as a non-root user.
2. Navigate to the `OFS_OIDF_PACK/schema_creator/bin/` directory.
3. Execute the `osc.sh` file using the following command:

```
./osc.sh -s -o
```

The following message is displayed:

You have chosen OFFLINE mode. Triggering the utility in OFFLINE mode will generate the script. Do you wish to proceed? (Y/y or N/n).

4. Enter **Y** to proceed.
5. Enter the DB Username with `SELECT` privileges.
6. Enter the User Password.
7. The console runs the initial validation checks and displays the following message:

You have chosen to install this Application Pack on <Name of the Atomic Schema> ATOMIC schema. Do you want to proceed? (Y/N).

Figure 22: Schema Creation in the Offline Mode - Script Generation

```

You have chosen OFFLINE mode.
Enter the DB User Name with SELECT privileges on following tables
1. DBA_ROLES
2. DBA_USERS
3. DBA_DIRECTORIES
4. DBA_TABLESPACES
sample
Enter the User Password:
=====
                          Schemas Creation Started
=====
OFSAAI installation status...
OFSAAI is not installed
validating the dat file OFS_AAAI_CFG.dat started...
Successfully validated OFS_AAAI_CFG.dat file
Validating the input XML file.../scratch/[REDACTED]/OFS_AAAI_PACK/schema_creator/conf/OFS_AAAI_SCHEMA_IN.xml
XSD validation completed successfully.
=====
Prechecks Execution started on ../OFS_AAAI_SCHEMA_IN.xml
Validating Connection URL ..jdbc:oracle:thin:[REDACTED]
Successfully connected to User - sample URL - jdbc:oracle:thin:[REDACTED]
Connection URL successfully validated...
You have chosen to install this Application Pack on "[REDACTED]" ATOMIC schema. Do you want to proceed? (Y/N)

```

8. Enter **Y** to start the script generation. The following message is displayed:

You have chosen to install this Application Pack on <Name of the Infodomain>. Do you want to proceed? (Y/N).

On successful execution of the schema creator utility, the console displays the following status message:

Schema Creator executed successfully. Please execute

OFS_OIDF_PACK/schema_creator/sysdba_output_scripts.sql before proceeding with the installation.

Additionally, if you have configured the `OFS_OIDF_SCHEMA_BIGDATA_IN.xml` file, a file called `hive_output_scripts.hql` is also created in the `OFS_OIDF_PACK/schema_creator/` directory.

NOTE

If there are any errors during the SQL script execution, reconfigure the `OFS_OIDF_SCHEMA_IN.xml` and/or `OFS_OIDF_SCHEMA_BIGDATA_IN.xml` files and repeat steps in this procedure to execute the utility. This regenerates the scripts with the correct information.

9. Navigate to the `OFS_OIDF_Pack/schema_creator/` directory.
10. Log in to the database using credentials with SYSDBA privileges.
11. Execute the `sysdba_output_scripts.sql` file using the following command:

```
SQL>@sysdba_output_scripts.sql
```

Alternatively, you can copy the `sysdba_output_scripts.sql` file and `SQLScripts` directory to a remote server and execute the `sysdba_output_scripts.sql` file, after providing appropriate execute permissions.

12. Log in to the Hue Browser with System Administrator privileges. Execute the script mentioned under `hive_output_scripts.hql` (omitting the slash '/') in the HIVE Query Editor. For example:

```
CREATE SCHEMA IF NOT EXIST <<HIVE SCHEMA NAME>>
```

NOTE

See the `sysdba_output_scripts.log` file for execution status. If there are any errors, contact [Oracle Support Services](#). If there are no errors in the execution, the log file is empty.

As a result of this procedure, the `OFS_OIDF_SCHEMA_OUTPUT.xml` file is generated. Do not modify this file.

5.9.2 Execute the Schema Creator Utility in Online Mode

Choose the Online Mode option, if you have login credentials to the database with SYSDBA privileges. In this mode, the utility connects to the database and executes the DDLs for Users, Objects, and Grants.

To execute the utility in online mode, follow these steps:

1. Edit the Application Schema file.

- For the RDBMS only mode of installation, edit the file `OFS_OIDF_PACK/schema_creator/conf/OFS_OIDF_SCHEMA_IN.xml` file in a text editor. See the [Configure the OFS OIDF SCHEMA IN.xml File](#) section for values to modify in the XML file.
 - For the Big Data installation (Stage and Results on Hive), edit the file `OFS_OIDF_PACK/schema_creator/conf/OFS_OIDF_SCHEMA_BIGDATA_IN.xml` file in a text editor. See the [Configure the OFS OIDF SCHEMA BIGDATA IN.xml file for Stage and Results on Hive](#) section for values to modify in the XML file.
 - For the Big Data installation (Stage on Hive and Results on RDBMS), edit the file `OFS_OIDF_PACK/schema_creator/conf/OFS_OIDF_SCHEMA_BIGDATA_IN.xml` file in a text editor. See the [Configure the OFS OIDF SCHEMA BIGDATA IN.xml file for Stage on Hive and Results on RDBMS](#) section for values to modify in the XML file.
2. Execute the `osc.sh` file using the following command:
- ```
./osc.sh -s
```

**Figure 23: Schema Creation in the Online Mode**

```

/scratch/██████████/AAI81_Kit/OFS_AAAI_PACK/schema_creator/bin>./osh.sh -s
/scratch/ofsaapp/AAI81_Kit/OFS_AAAI_PACK/schema_creator/bin>ls
osc.sh
/scratch/██████████/AAI81_Kit/OFS_AAAI_PACK/schema_creator/bin>clear
/scratch/██████████/AAI81_Kit/OFS_AAAI_PACK/schema_creator/bin>./osc.sh -s
=====
You have chosen ONLINE mode
=====
Triggering the utility in ONLINE mode will execute the DDLs directly on the Database. Do you wish to proceed? (Y/N):
Y
=====
Java Validation Started ...
Java found in : /██████████/java/jdk1.8.0_172/bin
JAVA Version found : 1.8.0_172
JAVA Bit Version found : 64-bit
Java Validation Completed. Status : SUCCESS
=====
DB specific Validation Started ...
Enter the DB User Name With SYSDBA Privileges:
sys as sysdba
Enter the User Password:
user name is sys
Oracle Client version : 18.0.0.0. Status : SUCCESS
Oracle Server version Current value : 18.0.0.0. Status : SUCCESS
DB specific Validation Completed. Status : SUCCESS
=====
Schema Creation Started
=====
Checking OFSAA installation...
OFSAA installation not found.
Validating the dat file OFS_AAAI_CFG.dat started...
The path is:/scratch/██████████/AAI81_Kit/OFS_AAAI_PACK/schema_creator/conf
Successfully validated OFS_AAAI_CFG.dat file
Validating the input XML file.../scratch/██████████/AAI81_Kit/OFS_AAAI_PACK/schema_creator/conf/OFS_AAAI_SCHEMA_IN.xml
Input XML file validated successfully.

```

3. The following message is displayed:
- You have chosen ONLINE mode. Triggering the utility in ONLINE mode will execute the DDLs directly on the Database. Do you wish to proceed? (Y/y or N/n).*
4. Enter **Y** to proceed.

Figure 24: Schema Creation in the Online Mode – DDL Execution

```

=====
Schema Creation Started
=====
Checking OFSAA installation...
OFSAA installation not found.
Validating the dat file OFS_AAAI_CFG.dat started...
The path is:/scratch/ /AAI81_Kit/OFS_AAAI_PACK/schema_creator/conf
Successfully validated OFS_AAAI_CFG.dat file
Validating the input XML file../scratch/ /AAI81_Kit/OFS_AAAI_PACK/schema_creator/conf/OFS_AAAI_SCHEMA_IN.xml
Input XML file validated successfully.
=====
Validating Connection URL ...jdbc:oracle:thin:@ : /
Connection jdbc:oracle:thin:@ : /
Successfully connected to User - sys as sysdba URL - jdbc:oracle:thin:@ : /
Connection URL successfully validated...
localhost name - IPAddress -
INT LB_HOST not there in schema
IS_HYBRID not there in schema
the redaction flag is inside precheck true
Executing redaction check query
Data Redaction parameters are properly set
checking and creating data security roles
Security role already present in DB
Security role already present in DB
privilege role already present in DB
Parsing file: /scratch/ /AAI81_Kit/OFS_AAAI_PACK/schema_creator/./conf/OFS_AAAI_Pack.xml
Checking: app: OFS_AAI schema_name: schema_type: CONFIG
Checking: app: OFS_AAAI schema_name: schema_type: ATOMIC
You have chosen to install this Application Pack on " " ATOMIC schema. Do you want to proceed? (Y/N)

```

The following message is displayed:

*You have chosen to install this application pack on INFODOM "<INFODOM\_NAME>". Do you wish to proceed? (Y/y or N/n).*

5. Enter **Y** to proceed.

Figure 25: Schema Creation in the Online Mode – Infodom Confirmation

```

Validating Connection URL ...jdbc:oracle:thin:@ : /
Connection jdbc:oracle:thin:@ : /
Successfully connected to User - sys as sysdba URL - jdbc:oracle:thin:@ : /
Connection URL successfully validated...
localhost name - IPAddress -
INT LB_HOST not there in schema
IS_HYBRID not there in schema
the redaction flag is inside precheck true
Executing redaction check query
Data Redaction parameters are properly set
checking and creating data security roles
Security role already present in DB
Security role already present in DB
privilege role already present in DB
Parsing file: /scratch/ /OFS_AAAI_PACK/schema_creator/./conf/OFS_AAAI_Pack.xml
Checking: app: OFS_AAI schema_name: schema_type: CONFIG
Checking: app: OFS_AAAI schema_name: schema_type: ATOMIC
You have chosen to install this Application Pack on " " ATOMIC schema. Do you want to proceed? (Y/N)
Y
You have chosen to install this Application Pack on INFODOM " ". Do you want to proceed? (Y/N)
Y
=====
Executing TableSpace Scripts started...
Executing TableSpace Scripts completed...
=====
Creating Schemas started...
CONFIG User successfully created on Default TableSpace : USERS on Temp TableSpace : TEMP
Grants creation scripts execution started...
Grants creation scripts execution completed...
Connection jdbc:oracle:thin:@ : /
Successfully connected to User - URL - jdbc:oracle:thin:@ : /
Scripts execution for CONFIG schema started ...

```

6. Schema is created successfully.

Figure 26: Schema Creation in the Online Mode –Successful

```

=====
Creating Schemas started...
CONFIG User aj81_ofsaaconf successfully created on Default TableSpace : USERS on Temp TableSpace : TEMP
Grants creation scripts execution started...
Grants creation scripts execution completed...
Connection jdbc:oracle:thin:@[redacted]:[redacted]/[redacted]
Successfully connected to User - [redacted] URL - jdbc:oracle:thin:@[redacted]:[redacted]/[redacted]
Scripts execution for CONFIG schema started ...
Scripts execution for CONFIG schema completed ...
User aj81_ofsaaconf details updated into the dbmaster table
User aj81_ofsaaconf details updated into the I18NMASTER table
User aj81_ofsaaconf details updated into the aai_db_detail table
User aj81_ofsaaconf details updated into the aai_db_auth alias table
User aj81_ofsaaatm details updated into the dbmaster table
User aj81_ofsaaatm details updated into the I18NMASTER table
User aj81_ofsaaatm details updated into the aai_db_detail table
User aj81_ofsaaatm details updated into the aai_db_auth alias table
User aj81_ofsaaatm is successfully created on Default TableSpace : USERS on Temp TableSpace : TEMP
Creating Schemas completed ...
=====
Roles creation scripts execution started ...
Roles creation scripts execution completed ...
the value of redaction flag in atomic schema istrue
=====
Grants creation scripts execution started...
the value of redaction flag in atomic schema istrue
Adding datasec grant file to suffixlist for app name other than AAI
Grants creation scripts execution completed...
=====
Schemas Creation Completed
=====
Schema Creator executed Successfully.Please proceed with the installation.
/scratch/[redacted]/OFS_AA1_PACK/schema_creator/bin>

```

As a result of this procedure, the `OFS_OIDF_SCHEMA_OUTPUT.xml` file is generated. Do not modify this file.

### 5.9.3 Execute the Schema Creator Utility in TCPS Mode

If you intend to run the OIDF Application Pack Installer in the TCPS mode, it is mandatory to execute the schema creator utility in the online mode.

#### Prerequisite:

Configure the Oracle Wallet with trusted certificates between the DB Server with TCPS configured and the DB Client to enable communication through the SSL protocol.

#### NOTE

You can also use Oracle Wallet to support OFSAA for storing Config and Atomic Schema credentials. To add OFSAA Config and Atomic Schema credentials to Oracle Wallet, see the [Oracle Financial Services Advanced Analytical Applications Infrastructure Administration and Configuration Guide Release 8.1x](#).

For example, all the database utilities such as `sqlplus`, `tnsping`, and `sqlldr` must work between the Client and the Server.

To execute the utility, follow these steps:

1. Edit the Application Schema file.
  - For the RDBMS only mode of installation, edit the file `OFS_OIDF_PACK/schema_creator/conf/OFS_OIDF_SCHEMA_IN.xml` file in a text editor. See the [Configure the OFS\\_OIDF\\_SCHEMA\\_IN.xml File](#) section for values to modify in the XML file.

- For the Big Data installation (Stage and Results on Hive), edit the file `OFS_OIDF_PACK/schema_creator/conf/OFS_OIDF_SCHEMA_BIGDATA_IN.xml` file in a text editor. See the [Configure the OFS OIDF SCHEMA BIGDATA IN.xml file for Stage and Results on Hive](#) section for values to modify in the XML file.
  - For the Big Data installation (Stage on Hive and Results on RDBMS), edit the file `OFS_OIDF_PACK/schema_creator/conf/OFS_OIDF_SCHEMA_BIGDATA_IN.xml` file in a text editor. See the [Configure the OFS OIDF SCHEMA BIGDATA IN.xml file for Stage on Hive and Results on RDBMS](#) section for values to modify in the XML file.
2. Execute the `osc.sh` file using the following command:

```
./osc.sh -s TCPS <WALLET_HOME>
```

For example: `./osc.sh -s TCPS /scratch/oraofss/wallet`

**Figure 27: Execution of the Schema Creator in the TCPS Mode**

```

/scratch/ >cd /scratch/ /OFS_AAAI_PACK/schema_creator/bin
/scratch/ /OFS_AAAI_PACK/schema_creator/bin>./osc.sh TCPS /scratch/ /wallet
Error: - Please provide proper arguments
/scratch/ /OFS_AAAI_PACK/schema_creator/bin>./osc.sh -s TCPS /scratch/ /wallet
-s
TCPS
/scratch/ /wallet
-Doracle.net.tns_admin=/scratch/ -Doracle.net.wallet_location=(SOURCE=(METHOD=file) (METHOD_DATA=(DIRECTORY=/scratch
h/ /wallet))) -Doracle.net.ssl_server_dn_match=true -Djavax.net.ssl.trustStoreType=SSO -Djavax.net.ssl.trustStore=c
wallet.sso -Doracle.net.ssl_version=1.2
exporting wallet FALSE
##Entries created by schema creator ##
=====
You have chosen ONLINE mode
=====
Triggering the utility in ONLINE mode will execute the DDLs directly on the Database. Do you wish to proceed? (Y/N):
Y

```

3. The following message is displayed:  
*Triggering the utility in ONLINE mode will execute the DDLs directly on the Database. Do you wish to proceed? (Y/y or N/n).*

4. Enter **Y** to proceed.

The following message is displayed:

*You have chosen to install this application pack on the "<ATOMIC\_SCHEMA\_NAME>" ATOMIC schema. Do you wish to proceed? (Y/y or N/n).*

**Figure 28: Schema Creation in the TCPS Mode – Install on Atomic Schema**

```

0430: 58 8D 05 B2 02 0F 2D 01 0C 00 00 00 00 00 04 X.....-.....
0440: 01 01 02 23 E4 00 02 05 7B 00 00 01 0C 01 0E 03 ...#.....
0450: 00 00 00 00 00 00 00 00 00 00 00 00 10 00 01 01
0460: 00 00 00 00 02 05 7B 00 19 4F 52 41 2D 30 31 34ORA-014
0470: 30 33 3A 20 6E 6F 20 64 61 74 61 20 66 6F 75 6E 03: no data foun
0480: 64 0A 61 1D D5 6D 51 10 60 C1 A6 85 B4 88 52 0F d.a.mQ.R.
0490: A4 F8 CA 1B 2C F2 09 09 09 09 09 09 09 09
You have chosen to install this Application Pack on " " ATOMIC schema. Do you want to proceed? (Y/N)
Y

```

5. Enter **Y** to proceed.
6. Schema is created successfully.

**Figure 29: Successful Schema Creation in the TCPS Mode**

```

0030: 05 02 24 2C 00 00 00 00 01 10 00 2B 00 00 00 00 ..$,.....+...
0040: 00 00 00 00 00 00 00 00 58 00 01 01 00 00 00 00X.....
0050: 00 00 EE 63 D9 C7 F0 3C A2 23 E1 34 68 01 68 96 ...c...<#.4h.h.
0060: 4F 69 FD 59 9F 23 09 09 09 09 09 09 09 09 09 09 Oi.Y.#.....
Grants creation scripts execution completed...
=====
 Schemas Creation Completed
=====
Schema Creator executed Successfully.Please proceed with the installation.
/scratch/_____/OFS AAI PACK/schema creator/bin>

```

As a result of this procedure, the `OFS_OIDF_SCHEMA_OUTPUT.xml` file is generated. Do not modify this file.

## 5.9.4 Execute the Schema Creator Utility when Installing the Subsequent Applications Pack

When executing the schema creator utility during the installation of a subsequent Applications Pack, you can choose to install the pack either on the same Information Domain or Atomic Schema of the existing application pack or on a new Information Domain or Atomic Schema. You can execute the schema creator utility either in the Online or Offline mode.

To execute the schema creator utility while installing OFSAAI Application Pack over an existing Application Pack, follow these steps:

1. Edit the Application Schema file.
  - For the RDBMS only mode of installation, edit the file `OFS_OIDF_PACK/schema_creator/conf/OFS_OIDF_SCHEMA_IN.xml` file in a text editor. See the [Configure the OFS\\_OIDF\\_SCHEMA\\_IN.xml File](#) section for values to modify in the XML file.
  - For the Big Data installation (Stage and Results on Hive), edit the file `OFS_OIDF_PACK/schema_creator/conf/OFS_OIDF_SCHEMA_BIGDATA_IN.xml` file in a text editor. See the [Configure the OFS\\_OIDF\\_SCHEMA\\_BIGDATA\\_IN.xml file for Stage and Results on Hive](#) section for values to modify in the XML file.
  - For the Big Data installation (Stage on Hive and Results on RDBMS), edit the file `OFS_OIDF_PACK/schema_creator/conf/OFS_OIDF_SCHEMA_BIGDATA_IN.xml` file in a text editor. See the [Configure the OFS\\_OIDF\\_SCHEMA\\_BIGDATA\\_IN.xml file for Stage on Hive and Results on RDBMS](#) section for values to modify in the XML file..
2. Execute the utility with the `-s` option.

For Example: `./osc.sh -s -o`



**Figure 31: Execution of the sysdba\_output\_scripts.sql file to install the subsequent Applications Pack**

```

INT LB_HOST not there in schema
IS_HYBRID not there in schema
Parsing file: /scratch/██████████/OFS_AAAI_PACK/schema_creator/./conf/OFS_AAAI_Pack.xml
Enabled applist: [OFS_AAIB, OFS_AAAI]
Enabled applist: [OFS_AAIB, OFS_AAAI]
Checking: app: OFS_AAI schema name: ██████████ schema type: CONFIG
Checking: app: OFS_AAAI schema name: ██████████ schema type: ATOMIC
You have chosen to install this Application Pack on "██████████" ATOMIC schema. Do you want to proceed? (Y/N)
Y
You have chosen to install this Application Pack on INFODOM "██████████". Do you want to proceed? (Y/N)
Y
=====
Generating TableSpace creation Scripts started...
Generating TableSpace creation Scripts completed...
=====
Generating Schema creation scripts started...
CONFIG User ██████████ creation script generated successfully on Default TableSpace : USERS on Temp TableSpace : TEMP
Generation of grants creation scripts started...
Generation of grants creation scripts completed...
Scripts Generation for CONFIG schema started ...
Scripts Generation for CONFIG schema completed ...
User ██████████ details updated into the dbmaster table
User ██████████ details updated into the I18NMASTER table
User ██████████ details updated into the aai_db_detail table
User ██████████ details updated into the aai_db_auth_alias table
User ██████████ details updated into the dbmaster table
User ██████████ details updated into the I18NMASTER table
User ██████████ details updated into the aai_db_detail table
User ██████████ details updated into the aai_db_auth_alias table
User ██████████ creation script generated successfully on Default TableSpace : USERS on Temp TableSpace : TEMP
Generating Schema creation scripts completed...
=====
Generating Roles creation Scripts started...
Generating Roles creation Scripts completed...
the value of redaction flag in atomic schema isfalse
=====
Generating Grants creation scripts started...
Generating Grants creation scripts completed...
=====
Generating Schema Creation Scripts Completed
=====
Schema Creator executed Successfully.Please execute /scratch/██████████/OFS_AAAI_PACK/schema_creator/sysdba_output_scripts.sql
before proceeding with the installation.
/scratch/██████████/OFS_AAAI_PACK/schema_creator/bin>

```

#### NOTE

You must use the same config schema user name as the previous Application Pack.

3. The utility identifies the Application Packs that are already installed on the current OFSAA setup and displays the following on the console:
  - Atomic schema of the existing Application Pack
  - Information Domain Name of the existing Pack
  - List of Installed Application Packs

Figure 32: Select the Atomic Schema and Infodom to install the subsequent Applications Pack

```

=====
 Generating Schema Creation Scripts Started
=====
Checking OFSAA installation...
Found OFSAA installation at /scratch/_____/OFSAAI
Validating the dat file OFS_AAAI_CFG.dat started...
Sucessfully validated OFS_AAAI_CFG.dat file
Parsing /scratch/_____/OFSAAI/conf/DynamicServices.xml
Successfully connected to User - dev_conf1 URL - jdbc:oracle:thin:@_____:_____:_____
Validating the input XML file.../scratch/_____/OFS_AAAI_PACK/schema_creator/conf/OFS_AAAI_SCHEMA_IN.xml
Input XML file validated successfully.
=====
Validating Connection URL ...jdbc:oracle:thin:@_____:_____:_____
Successfully connected to User - sample URL - jdbc:oracle:thin:@_____:_____:_____
Connection URL successfully validated...
You have chosen to install this Application Pack on "_____" ATOMIC sche
ma. Do you want to proceed? (Y/N)
Y
You have chosen to install this Application Pack on INFODOM "_____" . Do y
ou want to proceed? (Y/N)
Y
=====

```

4. Select the Atomic User on which you need to install the Application Pack.

Figure 33: Successful Schema creation to install the subsequent Applications Pack

```

Validating Connection URL ...jdbc:oracle:thin:@_____:_____:_____
Successfully connected to User - sys as sysdba URL - jdbc:oracle:thin:@_____:_____:_____
Connection URL successfully validated...
The following Application Packs are already installed in this OFSAA setup:

_____- INFOTR- *OFS_TR_PACK*

You have selected to install this Application Pack on "_____" ATOMIC schema. To proceed enter (Y/y). To change the selection, enter (N/n).
n
Choose the ATOMIC schema from the below list on which you wish to install this Application Pack:

1. _____- INFOTR- *OFS_TR_PACK*
2. _____- INFOTR- *OFS_TR_PACK*

Enter the option number:2
=====
Generating TableSpace creation Scripts started...
Generating TableSpace creation Scripts completed...
=====
Generating Schema creation scripts started...
Skipping the creation of CONFIG user dev_conf1 as OFSAAI is already installed on _____
User _____ details updated into the dbmaster table
User _____ creation script generated successfully on Default TableSpace : USERS on Temp TableSpace : TEMP
User _____ creation is skipping as the user is already created.
Generating Schema creation scripts completed...
=====
Generating Roles creation Scripts started...
Generating Roles creation Scripts completed...
=====
Generating Grants creation scripts started...
Generating Grants creation scripts completed...
=====
 Generating Schema Creation Scripts Completed
=====
Schema Creator executed Successfully.Please execute /scratch/_____/OFS_AAAI_PACK/schema_creator/sysdba_output_scripts.sql
before proceeding with the installation.

```

On successful execution of schema creator utility, the console displays the following status message:

Success. Please proceed with the installation.

**NOTE**

See If there are any errors, contact [Oracle Support Services](#).

## 5.10 Verify the Schema Creator Log Files

See the following logs directory for more information:

- OFS\_OIDF\_PACK/schema\_creator/logs/
- The log file `sysdba_output_scripts.log` in the `OFS_OIDF_PACK/schema_creator/logs/` directory for execution status if executed in offline mode. This log will be empty if there are no errors in the execution.

## 5.11 Install the OIDF Application Pack

**ATTENTION**

Before you begin the installation, configure and execute the following files:

1. [Configure the OS File System Settings and Environment Settings in the .profile File](#)
2. [Configure the OFS\\_OIDF\\_PACK.xml File](#)
3. [Configure the Schema Creator Utility](#).
  - [Configure the OFS\\_OIDF\\_SCHEMA\\_IN.xml File](#) (for RDBMS installation)
  - [Configure the OFS\\_OIDF\\_SCHEMA\\_BIGDATA\\_IN.xml file for Stage and Results on Hive](#) (for Big Data installation)
  - [Configure the OFS\\_OIDF\\_SCHEMA\\_BIGDATA\\_IN.xml file for Stage on Hive and Results on RDBMS](#)
4. [Configure the OFSAAI\\_InstallConfig.xml File](#) (do not configure this file if an installation of OFSAAI 8.1 already exists.)
5. [Configure the Silent.props File](#)
  - [Silent.template for RDBMS](#)
  - [Silent.BIGDATA.template for Stage and Results on Hive](#)
  - [Silent\\_Hybrid.template for Stage on Hive and Results on RDBMS](#)
6. [Execute the Schema Creator Utility](#)

**NOTE** Before installing the OIDF Application Pack in the Big Data mode of Stage on Hive and Results on RDBMS, install the OIDF Application Pack in the RDBMS mode.

To install the OIDF Application Pack v8.1.0.0.0, follow these steps:

1. Log in to the system as a non-root user.
2. Identify a directory for installation and set the same in the user `.profile` file as follows:
 

```
FIC_HOME=<OFSAA Installation Directory>
export FIC_HOME
```
3. Execute the user `.profile` file using the following command:
 

```
./profile
```
4. For the Big Data mode of installation, give access permission using the following command:
 

```
chmod -R 775 ftpshare ftpshareh $FIC_HOME libs
```
5. Create a folder `kit/<release_number>` in the user's home.  
For example: `/scratch/ofsaa/kit/81100`
6. For the Big Data mode of installation, place the installer zip folder in the path mentioned in the previous step, and then extract the installer using the following command:
 

```
unzip -a OFS_OIDF_8.1.0.0.0_<Operating_System>.zip
```

**NOTE** After the extraction, if you have a space issue, delete the `.zip` file.

7. For the Big Data mode of installation, ensure that the `ofsaa-hive-udf.jar` file is present in the `HiveAuxDir` directory and `spark2 lib` is present in the CDH installed server. If it is a cluster, then each node must consist of the file in these locations:
  - `/scratch/ofsaa/kit/<Release_Version>/OFS_OIDF_PACK/OFS_AAAI_PACK/fic home/utility/DMT/UDF/lib/ofsaa-hive-udf.jar`
  - SPARK2 lib directory
8. If you are installing on the Big Data infodomain, then navigate to the `OFS_OIDF_PACK/OFS_OIDF/conf/` directory:
  - For Stage and Results on Hive, do the following:
    - i. Rename the `default.properties` file to `default.properties_RDBMS.template`.
    - ii. Rename the `default.properties.BIGDATA.template` file to `default.properties`.
  - For Stage and Results on Hive, do the following:
    - i. Rename the `default.properties` file to `default.properties_RDBMS.template`.

- ii. Rename the `default.properties_Hybrid.template` file to `default.properties`.
9. Navigate to the following directory:  
`OFS_OIDF_Pack/bin/`
  10. Execute the OIDF Application Pack installer in the SILENT mode using the following command:  
`./setup.sh SILENT`

**Figure 34: Execute the OIDF installer in the SILENT mode**

```

/scratch/ [redacted] /kit/OFS_OIDF_PACK/bin>clear
/scratch/ [redacted] /kit/OFS_OIDF_PACK/bin>./setup.sh SILENT
Current OS Type ---- Linux
FIC_HOME : /scratch/[redacted]/OFSAAI
Environment check utility started...
=====

```

11. The installer proceeds with the Pre-installation Checks.

**Figure 35: Pre-installation Checks**

```

Environment Variables Validation Completed. Status : SUCCESS
=====
OS specific Validation Started ...
Checking en_US.utf8 locale. Status : SUCCESS
Unix shell found : /bin/ksh. Status : SUCCESS
Total file descriptors : 65535. Status : SUCCESS
Total number of process : 4096. Status : SUCCESS
OS version : 7. Status : SUCCESS
OS specific Validation Completed. Status : SUCCESS
=====
DB specific Validation Started ...
Oracle Client version : 18.0.0.0.0. Status : SUCCESS
client version 18.0
Successfully connected to schema fsdf8latm. Status : SUCCESS
CREATE SESSION has been granted to user. Status : SUCCESS
CREATE PROCEDURE has been granted to user. Status : SUCCESS
CREATE VIEW has been granted to user. Status : SUCCESS
CREATE TRIGGER has been granted to user. Status : SUCCESS
CREATE MATERIALIZED VIEW has been granted to user. Status : SUCCESS
CREATE TABLE has been granted to user. Status : SUCCESS
CREATE SEQUENCE has been granted to user. Status : SUCCESS
SELECT privilege is granted for NLS_INSTANCE_PARAMETERS view. Current value : READ. Status : SUCCESS
NLS_LENGTH_SEMANTICS : BYTE. Current value : BYTE. Status : SUCCESS
NLS_CHARACTERSET : AL32UTF8. Current value : AL32UTF8. Status : SUCCESS
SELECT privilege is granted for V_$parameter view. Current value : SELECT. Status : SUCCESS
Open cursor value is greater than 1000. Current value : 1000. Status : SUCCESS
SELECT privilege is granted for USER_TS_QUOTAS view. Current value : READ. Status : SUCCESS
Schema is granted with at least 500 MB table space. Current value : Unlimited. Status : SUCCESS
Oracle db version 18
Oracle db R2 version 18.0
Oracle Server version Current value : 18.0.0.0.0. Status : SUCCESS
DB specific Validation Completed. Status : SUCCESS
=====
Environment check utility Status : SUCCESS
=====

```

12. Enter the OFSAA Processing Tier FTP/SFTP password value and proceed, when prompted in the command prompt.

Figure 36: OFSAA Processing Tier FTP/SFTP Password Prompt

```

* Welcome to Oracle Financial Services Analytical Applications Infrastructure (OFS AAI) Installation *

Checking Infrastructure installation status ...
Infrastructure installation does not exist. Proceeding with Infrastructure installation ...
Triggering Infrastructure installation ...

Please enter Infrastructure Application/Database component FTP/SFTP password : █

```

**NOTE** Enter the password to access the Product Staging/Metadata repository directory FTPSHARE in the application server.

- 13. For the Big Data mode of installation, enter the Hive Server SFTP/FTP password value, when prompted at the command prompt.

**NOTE** Enter the password to access the ODF Hive directory FTPSHAREH in the application server.

- 14. The process displays the OFSAA License. Enter **Y** and proceed.

Figure 37: The OFSAA License Agreement

```

OFSAA APPLICATION PACK LICENSE AGREEMENT

* Oracle Financial Services Analytical Applications (OFSAA) application packs are groups of OFSAA products packaged together into a single installer. Each application pack contains OFSAA applications that address specific functional domains.*
* Every application pack also includes the following OFSAA infrastructure application options which are automatically installed by every application pack installer:
1. Oracle Financial Services Analytical Applications Infrastructure
2. Oracle Financial Services Enterprise Modeling
3. Oracle Financial Services Big Data Processing
* Oracle Financial Services Analytical Applications Infrastructure (OFS AAI) is the base infrastructure for all OFSAA applications and is therefore automatically installed and enabled by the application pack installer.*
* The application pack installer always installs Oracle Financial Services Enterprise Modeling, Oracle Financial Services In-line Processing Engine and Oracle Financial Services Big Data Processing application options along with the application pack applications, but enables them only if any application that requires their functionality is enabled.*
* Any OFSAA application that is enabled must be licensed for use. Oracle Financial Services Analytical Applications Infrastructure, Oracle Financial Services Enterprise Modeling, Oracle Financial Services In-line Processing Engine and Oracle Financial Services Big Data Processing are individually licensable application options.*
* Application products once enabled cannot be disabled. Application products not enabled on installation, may later be enabled using the "Manage OFSAA Product License(s)" feature of the platform.*

Are you accepting the terms and conditions mentioned above? [Y/N]: █

```



**NOTE**

- The Data Model upload may take several hours to complete. You can check the installation logs in the `/OFS_OIDF_PACK/OFS_OIDF/logs/` directory.
- For the existing customers, with the DB XML, the time taken for the Data Model upload will be significantly reduced. You can upload the warehouse data from the operational systems to the database schema using the erwin XML or Database XML file. Using the stand-alone command-line utility for the `TransformErwin.sh` file, you can transform erwin XML into Database XML, and use the DB XML instead of erwin XML to speed up the model upload process. For more information, see the *Command Line Utility for Transforming erwin XML to Database XML* section in the [Oracle Financial Services Advanced Analytical Applications Infrastructure User Guide Release 8.1.0.0.0](#).

**Figure 40: OIDF Application Pack Installation Complete**

```
Starting OFSAA Service...
OFSAA Service - OK
Preparing to install...
Extracting the installation resources from the installer archive...
Configuring the installer for this system's environment...

Launching installer...

Preparing SILENT Mode Installation...

=====
pack_installsilent (created with InstallAnywhere)
=====

Installing...

[=====|=====|=====|=====]
[-----|-----|-----|-----]

Installation Complete.
failurecount --- 0
Core Installation completed successfully
tempdir ---- /scratch/██████/kit/OFS_OIDF_PACK
Checking for hive app. ████████

***** Checking for Fresh app : OFS_OIDF *****
path before app installation: /scratch/██████/kit/OFS_OIDF_PACK
inside checkappstatus-app OFS_OIDF /scratch/██████/kit/OFS_OIDF_PACK/bin
all value /scratch/██████/kit/OFS_OIDF_PACK/bin
In app value
[AppStatusCheck] Checking for app installation OFS_OIDF
[AppStatusCheck] app is selected and ENABLED in db
app status returned: 0
current directory after app installation: /scratch/██████/kit/OFS_OIDF_PACK/OFS_OIDF
Checking for available options...
List of options available:
Pack Name found is: OFS_OIDF_PACK
Utility triggered for XML files
```

17. When the installation is complete, the following message is displayed in the console:

Installation completed...

18. The OFSAA Infrastructure installation performs a post-install health check automatically on the successful installation of the product.
19. To verify if the release is applied successfully, check the log files mentioned in the section [Verify the Log File Information](#).
20. For the Big Data installation mode of installation (Stage and Results on Hive), follow these steps:

**NOTE** During both of the Big Data installation processes, for the Big Data SQL to refresh the data, ensure to truncate the Stage tables during the second time and onwards, and then load the data. Truncation is not required during the first time.

- If the OIDF installation machine and the Cloudera machine are *different*, then follow these steps:
  - i. Create a folder in the Cloudera machine.
  - ii. Copy all the required `csv` files from the `<INSTALLER_KIT>/OFS_OIDF_PACK/OFS_OIDF/bin/scripts/atomic/insert/hive/` directory to the Cloudera machine folder mentioned in the first step:

**NOTE** For the list of `csv` files, see the [Oracle Insurance Data Foundation Application Pack Runchart Release 8.1.0.0.0](#) file.

- iii. Copy the shell script `load-csv-hdfs-run.sh` from the `$FIC_DB/bin/` directory to the Cloudera machine folder mentioned in the first step.
  - iv. Log in as the user having access to Hive in the Cloudera machine, and provide 775 permission to the `load-csv-hdfs-run.sh` file using the following command:
 

```
chmod -R 775 load-csv-hdfs-run.sh
```
- If the OIDF installation machine and the Cloudera machine are the *same*, then follow steps:
    - i. Create a directory in the Hive user's home and place the required `csv` files in that directory.

**NOTE** For the list of `csv` files, see the [Oracle Insurance Data Foundation Application Pack Runchart Release 8.1.0.0.0](#) file.

- ii. Copy all the required `csv` files from the `<INSTALLER_KIT>/OFS_OIDF_PACK/OFS_OIDF/bin/scripts/atomic/insert/hive/` directory to the Cloudera machine folder mentioned in the first step.
- iii. Copy the shell script file `load-csv-hdfs-run.sh` from the `$FIC_DB/bin/` directory to the Cloudera machine folder mentioned in the first step.
- iv. Log in as the user having access to Hive in the Cloudera machine, and provide 775 permission to the `load-csv-hdfs-run.sh` file using the following command:
 

```
chmod -R 775 load-csv-hdfs-run.sh
```

- v. To load the seeded data, run the following command:

```
./load-csv-hdfs-run.sh <HDFS_TEMP_DIR> <HIVE_SCHEMA_NAME>
```

**For example:**

```
./load-csv-hdfs-run.sh /user/ofsaal/load datadom810
```

**NOTE**

HDFS\_TEMP\_DIR is not the Hive warehouse directory. Also, ensure that the path is not the Hive Metastore directory.

The script requires two parameters. They are HDFS\_TEMP\_DIR and

HIVE DATABASE NAME.

Here, HDFS\_TEMP\_DIR is /user/<Cloudera\_hive\_user\_name>/<Any\_Name>.

21. For the Big Data installation mode of installation (Stage on Hive and Results on RDBMS), follow these steps:

Grant the BIGDATA\_SQL user privilege to all the schemas.

**For example:**

```
grant BDSQL_USER to <CONFIG SCHEMA>;
grant BDSQL_USER to <ATOMIC SCHEMA1>;
grant BDSQL_USER to <ATOMIC SCHEMA2>;
grant all privileges to <ATOMIC SCHEMA1>;
```

In \$FIC\_HOME/ficdb/bin, execute the file externaltablecreator\_OIDF.sh with these arguments:

```
$userId = SYSADMN
$infodom = RDBMS_INFODOM
$dbAlias= RDBMS_INFODOM Metadom alias
$hiveSchema = Hive Schema Name
$directory = Warehouse Directory(with double quotes)
$user_connection_url = metadomUID/password@SID
```

**For example:**

```
./externaltablecreator_OIDF.sh SYSADMN OI DFINFO META bszbdsdatadom
"\"ORA_BIGDATA_CL_cluster\" " <ATOMIC SCHEMA1>/password123@OFSAA
```

**NOTE**

- When creating an External Table, ensure that the Hive Schema Name is in lowercase.
- Disregard the *NullPointerException* error during the External Table execution.
- For more information about the External Tables, see the [Verify the External Tables Utility of Oracle](#) section.

22. Perform the steps mentioned in the [Post-installation](#) section. For additional configuration information, see the [Additional Configuration](#) section.

## 5.12 Install a New OIDF Application Pack on an Existing OFSAA Instance

This is an installation scenario, where you have already installed an application pack from Release v8.1.0.0.0 and now you need to install the OIDF Application Pack from Release v8.1.0.0.0. For example, the OFS ALM Application Pack v8.1.0.0.0 is already installed and now you need to install the OIDF Application Pack v8.1.0.0.0.

1. [Configure the OFS\\_OIDF\\_PACK.xml File.](#)
2. Configure the Schema Creator Utility:
  - [Configure the OFS\\_OIDF\\_SCHEMA\\_IN.xml File](#) (for RDBMS installation)
  - [Configure the OFS\\_OIDF\\_SCHEMA\\_BIGDATA\\_IN.xml file for Stage and Results on Hive](#) (for the Big Data mode of installation)
  - [Configure the OFS\\_OIDF\\_SCHEMA\\_BIGDATA\\_IN.xml file for Stage on Hive and Results on RDBMS](#) (for the Big Data mode of installation)

**NOTE**

Configuring the `OFSAAI_InstallConfig.xml` file is not required in this scenario.

3. [Configure the Silent.props File](#)
  - [Silent.template for RDBMS](#)
  - [Silent.BIGDATA.template for Stage and Results on Hive](#)
  - [Silent\\_Hybrid.template for Stage on Hive and Results on RDBMS](#)
4. [Execute the Schema Creator Utility](#)

**NOTE**

While defining the schema details for the application packs, provide the same schema details given in the previous v8.1.0.0.0 installation of the other application pack. The output file `OFS_OIDF_SCHEMA_OUTPUT.xml` is generated as a result of the schema creation process.

5. [Trigger the Installation.](#)
6. [Verify the Log File Information.](#)
7. Do the [Post-installation](#) steps. For additional configuration information, see the [Additional Configuration](#) section.

## 6 Use Oracle Autonomous Data Warehouse as the Database for OIDF

This section explains the deployment procedure of Oracle Insurance Data Foundation (OIDF) on Oracle Autonomous Data Warehouse (ADW).

### Topics:

- [Oracle Autonomous Data Warehouse](#)
- [Deployment Architecture for ADW Certification](#)
- [Download Client Credentials \(Wallet\)](#)
- [Using a JDBC URL Connection String with JDBC Thin Driver](#)
- [Installation Notes Specific to ADW](#)
- [Loading Data into OIDF](#)
- [Additional Note](#)

### 6.1 Oracle Autonomous Data Warehouse

Oracle Autonomous Database is Oracle's new, fully managed database tuned and optimized for both data warehouse and transaction processing workloads with the market-leading performance of the Oracle Database. It delivers a completely new, comprehensive cloud experience for data warehousing and transaction processing workloads that is easy, fast, and elastic and requires no database administration.


OIDF being an analytical data warehouse platform, it is qualified for ADW.

When you create an Autonomous Data Warehouse database, you can deploy it to one of two kinds of Exadata infrastructure:

- **Shared:** A simple and elastic choice. Oracle autonomously operates all aspects of the database life cycle from database placement to backup and updates.
- **Dedicated:** A private cloud in public cloud choice. A completely dedicated compute, storage, network and database service for only a single tenant. Dedicated infrastructure provides for the highest levels of security isolation and governance. The customer has customizable operational policies to guide Autonomous Operations for workload placement, workload optimization, update scheduling, availability level, over provisioning and peak usage.

### 6.2 Deployment Architecture for ADW Certification

The following illustration depicts the deployment architecture used for the ADW certification.



The deployment architecture consists of two Availability Domains used for OFSAA and WebLogic Server in the same Oracle Cloud Infrastructure (OCI) Compartment. Oracle Identity Cloud Service (IDCS) can be used to log in. The Load Balancer (LB) redirects the request to respective compute.

Both Availability Domain 1 and Availability Domain 2 computes use the ID-RSA key to transact between the nodes. The WebLogic Servers and DF Servers are configured to connect the ADW OFSAA schemas with the Wallet files.

Currently, Autonomous Database (ADB) provides 99.95% availability during any calendar month. For customers that need high availability, Autonomous Data Guard provides failover protection.

## 6.3 Download Client Credentials (Wallet)

Oracle client credentials (wallet files) are downloaded from Autonomous Data Warehouse by a service administrator. If you are not an Autonomous Data Warehouse administrator, your administrator must provide you with the client credentials.

To download the client instance (Wallet), you can use the following consoles:

- Oracle Cloud Infrastructure (OCI) console
- Autonomous Data Warehouse Service console

See the [Download Client Credentials \(Wallets\)](#) for more information.

## 6.4 Using a JDBC URL Connection String with JDBC Thin Driver

The connection string is found in the file `tnsnames.ora` which is a part of the client credentials download. The `tnsnames.ora` file contains the predefined services identifiable as high, medium, and low. Each service has its own TNS alias and connection string. See [Predefined Database Service Names for Autonomous Data Warehouse](#) for more information.

The following is a sample entry with `dbname_low` as the TNS alias and a connection string in the `tnsnames.ora` file:

```
dbname_low= (description=
(address=(protocol=tcps) (port=1522) (host=adw.example.oraclecloud.com)) (conne
ct_data=(service_name=adw_jdbctest_high.oraclecloud.com)) (security=(ssl_serv
er_cert_dn="CN=adw.oraclecloud.com,OU=OracleUS,O=Oracle
Corporation,L=Redwood City,ST=California,C=US"))))
```

## 6.5 Installation Notes Specific to ADW

This section provides additional steps applicable to the installation on ADW in OFSAA for OI DF.

### 6.5.1 Hardware and Software Requirements

For OI DF qualification on ADW, the following software are used:

- Database is ADW
- Web application server is Oracle WebLogic Server 12.2.x

See the [Oracle Financial Services Analytical Applications \(OFSAA\) Technology Matrix Release 8.1.0.0.0](#) for the hardware and software required for the installation of OI DF Application Pack Release 8.1.0.0.0.

### 6.5.2 Configure the Schema Creator Utility

The modifications applicable to configuring the schema creator utility for the OI DF installation on ADW are provided in this section.

**NOTE** The schema creator utility configuration is applicable for the OI DF installation on ADW also. See the [Configure the Schema Creator Utility](#) section for more information. The modifications applied to the OI DF installation on ADW are mentioned in this section.

The ADW specific modifications are as follows:

- When configuring the `OFS_OI DF_SCHEMA_IN.xml` file for ADW, follow these modifications:
  - Set the `<IS_TCPS>` tag to TRUE:  
`<IS_TCPS>TRUE</IS_TCPS>`

**NOTE**

The connections to ADW is through the ADW Wallet. Therefore, the `<IS_TCPS>` tag must be always set to TRUE for OIDF installation on ADW.

- The tag `<OPTION NAME="TDE" VALUE="TRUE"/>` can be commented out because ADW is secure by default.
- The tag `<TABLESPACES>` can be commented out because ADW does not consider the TABLESPACES inputs.
- This is a sample of the `<JDBC_URL>` tag for connecting to the ADW:  
`<JDBC_URL>jdbc:oracle:thin:@##dbname##_low</JDBC_URL>`

See the sections [Using a JDBC URL Connection String with JDBC Thin Driver](#), [JDBC Thin Connections and Wallets](#) and [Predefined Database Service Names for Autonomous Data Warehouse](#) for more information about the predefined database service names for ADW.

### 6.5.3 OFSAAI Installation Notes Specific to ADW

The additional steps applicable to the OFSAAI installation on ADW are as follows:

**NOTE**

OFSAAI installation is applicable for the OFSAAI on ADW also. See the [Oracle Financial Services Advanced Analytical Applications Infrastructure Installation Guide Release 8.1.0.0.0](#) for the detailed installation procedure. The additional steps applicable to the OFSAAI installation on ADW are mentioned in this section.

1. Extract the `Wallet_<dbname>.zip` folder into the directory path `$HOME/Wallet_<dbname>`, where you are going to install OIDF on the OCI OEL 7.X virtual machine instance. This directory is also called as the `WALLET_HOME`. For information about downloading the Wallet for ADW, see [Download Client Credentials \(Wallets\)](#).

```
WALLET_HOME=/home/Wallet_<dbname>.zip
```

Example:

```
/u02/ofsa/Wallet_OFSAADB
```

2. For the above-mentioned directory, set the `TNS_ADMIN` in the `.profile` file. Edit the `sqlnet.ora` file for the Wallet path and other directives.

Example:

The contents of the `sqlnet.ora` files are as following:

```
SQLNET.WALLET_OVERRIDE = TRUE
WALLET_LOCATION = (SOURCE = (METHOD = file) (METHOD_DATA =
(DIRECTORY="/u02/ofsa/Wallet_OFSAADB")))
SSL_SERVER_DN_MATCH=yes
```

3. For the above-mentioned directory, set the parameter `IS_ADW=TRUE` in the `.profile` file, and point the `ORACLE_HOME` parameter to the Oracle Database 19c Client installation path.

Example:

Sample of the `.profile` file contents for OI DF with ADW on OCI is follows:

```
export FIC_HOME=/u02/ofsa/OFSASHOME
export TNS_ADMIN=/u02/ofsa/Wallet_OFSADB
export ORACLE_HOME=/u01/app/oracle/product/19.3.0/client_1
export JAVA_HOME=/usr/java/jdk1.8.0_121
export JAVA_BIN=/usr/java/jdk1.8.0_121/bin
export LD_LIBRARY_PATH=$ORACLE_HOME/lib:$LD_LIBRARY_PATH
export PATH=$ORACLE_HOME/bin:$JAVA_HOME:$JAVA_BIN:$PATH
export IS_ADW=TRUE
```

4. Follow the OFSAAI 8.1.0.0.0 installation procedure that supports TCPS. See the [Oracle Financial Services Advanced Analytical Applications Infrastructure Installation Guide Release 8.1.0.0.0](#).
  - a. Before executing the Schema Creator utility, ensure to [Configure the Schema Creator Utility](#).
  - b. Execute the Schema Creator utility:

Example:

```
./osc.sh -s TCPS /u02/ofsa/Wallet_OFSADB
```

This prompts you to enter USER having SYSDBA privileges.

Enter the ADMIN and password details provided to you during the ADW provisioning.

See the [Oracle Financial Services Advanced Analytical Applications Infrastructure Installation Guide Release 8.1.0.0.0](#) for more information.

## 6.5.4 OI DF Installation Notes Specific to ADW

The additional steps applicable to the OI DF installation on ADW are mentioned in this section.

### NOTE

OI DF installation is applicable for the OI DF on ADW also. See the [Install the OI DF Application Pack](#) section for the detailed installation procedure. The additional steps applicable to the OI DF installation on ADW are mentioned in this section.

The ModelUpgrade utility was triggered using the TCPS mode during installation on ADW because the connections to ADW is through the ADW Wallet.

The files configured for the OI DF installation are same for the OI DF installation on ADW also.

When configuring the `OFSAAI_InstallConfig.xml` file for ADW, follow these modifications:

- The `<InteractionGroup name="OLAP Detail">` tag is not supported in ADW.
- Ensure to provide ADW database details similar to the following sample of the `<InteractionGroup name="Database Details">` tag:
 

```
<InteractionGroup name="Database Details"><InteractionVariable
name="ORACLE_SID/SERVICE_NAME">##dbname##_low</InteractionVariable><Int
eractionVariable
```

```
name="ABS_DRIVER_PATH">/u01/app/oracle/product/19.3.0/client_1/jdbc/lib
</InteractionVariable></InteractionGroup>
```

### 6.5.5 Installation of OI DF on ADW

Follow the OFSAAI 8.1.0.0.0 installation procedure and OI DF 8.1.0.0.0 installation procedure.

Execute the `./setup.sh` command.

See the [OFS Advanced Analytical Applications Infrastructure Installation and Configuration Guide Release 8.1.0.0.0](#) for installation and post-installation procedure required for OFSAAI with TCPS.

See the [Install the OI DF Application Pack](#) section for installation and the [Post-installation](#) section for the post-installation procedure required for OI DF with TCPS.

## 6.6 Loading Data into OI DF

For the OI DF deployment on ADW, the Object Store mechanism has been used as the repository for the inbound data.

The following steps were performed to load data to the OI DF schema on the ADW environment and to execute the OI DF batches:

- [Importing Data into OI DF on ADW Using the OCI Object Storage](#)
- [Batch Execution in OI DF](#)

### 6.6.1 Importing Data into OI DF on ADW Using the OCI Object Storage

To import data into OI DF using the Object Storage, follow these steps:

1. To create an Object Storage in the OCI and load data into ADW, see [Import Data Using Oracle Data Pump on Autonomous Data Warehouse](#).
2. To choose appropriate mode to import data into schema, see [Examples of Using Data Pump Import](#) for the data pump examples with all the possible ways to import data.

### 6.6.2 Batch Execution in OI DF

To execute the OI DF batches, follow these steps:

1. Log in to ADW OFSAA schemas and check the load status.
2. Execute the OI DF batches. The tasks executed and data moved successfully to target as are follows:
  - ##INFODOM##\_POP\_DATES\_DIM
  - ##INFODOM##\_MASTER
  - ##INFODOM##\_DATA\_FOUNDATION\_SCD
  - ##INFODOM##\_DIM\_ACCOUNT\_SCD
  - ##INFODOM##\_POP\_MAPPER\_DATA
  - OI DF Source Run

- OIDF Exe Run

See the [Oracle Insurance Data Foundation Application Pack User Guide Release 8.1.0.0.0](#) for more information about the OIDF batch execution.

## 6.7 **Additional Note**

Currently, OIDF Release 8.1.0.0.0 is the qualified for deployment on the ADW.

For more information, log a service request on [My Oracle Support \(MOS\)](#).

## 7 Post-installation

This section provides information for Post-installation required for the ODF Application Pack.

### Topics:

- [OFSAA Infrastructure Patch Installation](#)
- [Verify the Log File Information](#)
- [Stop the Infrastructure Services](#)
- [Create and Deploy the EAR/WAR Files](#)
- [EAR/WAR File - Build Once and Deploy Across Multiple OFSAA Instances](#)
- [Start the Infrastructure Services](#)
- [Access the OFSAA Application](#)
- [OFSAA Landing Page](#)
- [View OFSAA Product Licenses after the Installation of Application Pack](#)
- [Configure the excludeURLList.cfg File](#)
- [Configure the Big Data Processing](#)
- [Configuration to Enable the Restatement Support](#)
- [Create the Application Users](#)
- [Map the Application User\(s\) to User Group](#)
- [Change the ICC Batch Ownership](#)
- [Add TNS entries in the TNSNAMES.ORA File](#)
- [Configure Transparent Data Encryption \(TDE\) and Data Redaction in OFSAA](#)
- [Implement Data Protection in OFSAA](#)

### NOTE

See the *Post-Installation* section in the [Oracle Financial Services Advanced Analytical Applications Infrastructure Installation Guide Release 8.1.0.0.0](#) to complete these procedures.

For additional configuration information, see the [Additional Configuration](#) section.

### 7.1 OFSAA Infrastructure Patch Installation

Oracle strongly recommends installing the latest available patch set to be up-to-date with the various releases of the OFSAA product.

After the installation of ODF Application Pack 8.1.0.0.0:

- Apply the **31605076** one-off patch. See the ReadMe packaged with the patch for further instructions about how to install the patch.

- Apply the OFSAAI Mandatory Patch **33663417**.

**ATTENTION**

On the 10th of December 2021, Oracle released Security Alert CVE-2021-44228 in response to the disclosure of a new vulnerability affecting Apache Log4J prior to version 2.15. The application of the **33663417** Mandatory Patch fixes the issue.

For details, see the My Oracle Support Doc ID [2827801.1](#).

Ensure that you reapply the OFSAAI Mandatory Patch **33663417** whenever you Install or Upgrade the Application, or whenever you apply an Incremental Patch.

For the Patch download information, see the **Download the Mandatory Patches** Section in [Pre-installation](#) for a new installation and in [Upgrade](#) for an upgrade installation.

See [My Oracle Support \(MOS\)](#) for more information about the latest release.

## 7.2 Verify the Log File Information

See the following logs files for more information:

- `Pack_Install.log` file in the `OFS_OIDF_PACK/logs/` directory.
- `OFS_OIDF_installation.log` file and the `OFS_OIDF_installation.err` file in the `OFS_OIDF_PACK/OFS_OIDF/logs` directory.
- Infrastructure installation log files in the `OFS_OIDF_PACK/OFS_AAI/logs/` directory.
- `OFSAAIInfrastructure_Install.log` file in the `$FIC_HOME` directory.

**ATTENTION**

- You can ignore the "ORA-00001: unique constraint" error, and Object already exists and Table has a primary key warnings for the `OFSA_CATALOG_OF_LEAVES` table in the log file.
- In case of any other errors, contact [My Oracle Support \(MOS\)](#).

## 7.3 Stop the Infrastructure Services

See the [Stop the Infrastructure Services](#) section in the *OFSAAI Release 8.1.0.0.0 Installation and Configuration Guide* for details.

## 7.4 Create and Deploy the EAR/WAR Files

See the [Create and Deploy the EAR/WAR Files](#) section in the *OFSAAI Release 8.1.0.0.0 Installation and Configuration Guide* for details.

## 7.5 EAR/WAR File - Build Once and Deploy Across Multiple OFSAA Instances

See the [EAR/WAR File - Build Once and Deploy Across Multiple OFSAA Instances](#) section in the *OFSAAI Release 8.1.0.0.0 Installation and Configuration Guide* for details.

## 7.6 Start the Infrastructure Services

See the [Start the Infrastructure Services](#) section in the *OFSAAI Release 8.1.0.0.0 Installation and Configuration Guide* for details.

## 7.7 Access the OFSAA Application

See the [Access the OFSAA Application](#) section in the *OFSAAI Release 8.1.0.0.0 Installation and Configuration Guide* for details.

## 7.8 OFSAA Landing Page

See the [OFSAA Landing Page](#) section in the *OFSAAI Release 8.1.0.0.0 Installation and Configuration Guide* for details.

## 7.9 View OFSAA Product Licenses after the Installation of Application Pack

In an integrated environment, where you have multiple applications installed on the same domain or infrastructure, OFSAAI allows you to see the other licensed applications through the UI. For more information, see the *View OFSAA Product Licenses after Installation of Application Pack* in the [Oracle Financial Services Advanced Analytical Applications Infrastructure User Guide Release 8.1.0.0.0](#).

## 7.10 Configure the excludeURLList.cfg File

See the section [Configure the excludeURLList.cfg File](#) in the *OFSAAI Release 8.1.0.0.0 Installation and Configuration Guide* for details.

## 7.11 Configure the Big Data Processing

This section is not applicable if you have enabled Financial Services Big Data Processing during the installation of ODF 8.1.0.0.0 full installer. Follow instructions in this section if you intend to enable Big Data Processing.

### Topics:

- [Copy the Jar Files to the OFSAA Installation Directory](#)
- [Copy the KEYTAB and KRB5 Files in OFSAAI](#)
- [Configure the Apache Livy Interface](#)
- [Verify the External Tables Utility of Oracle](#)

## 7.11.1 Copy the Jar Files to the OFSAA Installation Directory

1. Download the supported [Cloudera HIVE JDBC Connectors](#) and copy the following jars files to the `$FIC_HOME/ext/lib/` and `$FIC_WEB_HOME/webroot/WEB-INF/lib/` directory. For the latest supported versions, see [Oracle Financial Services Analytical Applications 8.1.0.0.0 Technology Matrix](#).
  - `hive_service.jar`
  - `hive_metastore.jar`
  - `HiveJDBC4.jar`
  - `zookeeper-3.4.6.jar`
  - `TCLIServiceClient.jar`
2. Copy the following jars files from the `<Cloudera Installation Directory>/jars/` directory based on the CDH version to the `$FIC_HOME/ext/lib/` and `$FIC_WEB_HOME/webroot/WEB-INF/lib/` directories.
  - **CDH v5.13.0:**
    - `commons-collections-3.2.2.jar`
    - `commons-configuration-1.7.jar`
    - `commons-io-2.4.jar`
    - `commons-logging-1.2.jar`
    - `hadoop-auth-2.6.0-cdh5.13.0.jar`
    - `hadoop-common-2.6.0-cdh5.13.0.jar`
    - `hadoop-core-2.6.0-mr1-cdh5.13.0.jar`
    - `hive-exec-1.1.0-cdh5.13.0.jar`
    - `httpclient-4.3.jar`
    - `httpcore-4.3.jar`
    - `libfb303-0.9.3.jar`
    - `libthrift-0.9.3.jar`
    - `slf4j-api-1.7.5.jar`
    - `slf4j-log4j12-1.7.5.jar`
  - **CDH v6.3.0:**
    - `commons-collections-3.2.2.jar`
    - `commons-configuration2-2.1.1.jar`
    - `commons-io-2.6.jar`
    - `commons-logging-1.2.jar`
    - `hadoop-auth-3.0.0-cdh6.3.0.jar`
    - `hadoop-common-3.0.0-cdh6.3.0.jar`

```
— hive-exec-2.1.1-cdh6.3.0.jar
— httpclient-4.5.3.jar
— httpcore-4.4.6.jar
— libfb303-0.9.3.jar
— libthrift-0.9.3.jar
— slf4j-api-1.7.25.jar
— slf4j-log4j12-1.7.25.jar
```

## 7.11.2 Copy the KEYTAB and KRB5 Files in OFSAAI

A Keytab is a file containing pairs of Kerberos principals and encrypted keys (these are derived from the Kerberos password). The krb5.conf file contains Kerberos configuration information, including the locations of KDCs and admin servers for the Kerberos realms of interest, defaults for the current realm, and Kerberos applications, and mappings of hostnames onto Kerberos realms.

If the Authentication is configured as KERBEROS\_WITH\_KEYTAB for the Hive database, then you must use the Keytab file to login to Kerberos. The Keytab and Kerberos files must be copied to `$FIC_HOME/conf` and `$FIC_WEB_HOME/webroot/conf` of the OFSAAI installation directory.

Generate the application EAR/WAR file and redeploy the application onto your configured web application server.

Restart the Web application server and the OFSAAI Application Server. For more information, see the [Start the Infrastructure Services](#) section.

## 7.11.3 Configure the Apache Livy Interface

Apache Livy is an Interface service that enables easy interaction with a Spark cluster over a REST interface.

### Topics:

- [Configure Spark](#)
- [Set metastore Path for Spark](#)
- [Cluster Configuration](#)

Do the following configuration for the Big Data mode of installation.

### 7.11.3.1 Configure Spark

To configure Spark, you must configure crossJoin.

#### NOTE

This section is applicable only during the Stage and Results on Hive installation.

To configure crossJoin, follow these steps:

1. Open the **Cloudera Manager** application.
2. Navigate to **SPARK2** select **Configuration**, and search the `spark-defaults.conf` file.

**For example:**

```
/etc/spark2/conf.cloudera.spark2_on_yarn/spark-defaults.conf
```

3. Set the parameter **spark.sql.crossJoin.enabled** to **true**.
4. Set the parameter **spark.executor.memory** to **10g**.

**NOTE**

When the Spark memory settings are set to low values, T2T execution fails. To resolve this, adjust the value of the `spark.executor.memory` variable.

### 7.11.3.2 Set metastore Path for Spark

To set the metastore path for Spark, follow these steps:

**NOTE**

This section is applicable during both the installation processes in Big Data (Stage and Results on Hive, and Stage on Hive and Results on RDBMS).

1. Copy the `hive-site.xml` file from the `hive conf` directory to the `SPARK2 conf` directory.

**For example:**

```
cp /etc/hive/conf.cloudera.hive/hive-site.xml
 /etc/spark2/conf.cloudera.spark2_on_yarn
```

2. Edit the `hive-site.xml` file to add the following entries in the `SPARK2 conf` directory:

**Table 37: Edit the hive-site.xml File**

| On hive conf                                                                                                                                        | In SPARK2 conf                                                                                                                                 |
|-----------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------|
| <pre>&lt;property&gt; &lt;name&gt;hive.metastore.warehouse.dir&lt;/name&gt; &lt;value&gt;/user/hive/warehouse&lt;/value&gt; &lt;/property&gt;</pre> | <pre>&lt;property&gt; &lt;name&gt;spark.sql.warehouse.dir&lt;/name&gt; &lt;value&gt;/user/hive/warehouse&lt;/value&gt; &lt;/property&gt;</pre> |

**NOTE**

When Cloudera is configured for a cluster, then all the nodes must adhere to this configuration.

### 7.11.3.3 Cluster Configuration

Configure DMT to provide Apache Livy Interface details.

**NOTE** This section is applicable only during the Stage and Results on Hive installation.

Ensure that you have the appropriate User Role to access this screen. To add a New Cluster, add the appropriate role to the user:

**NOTE** To add a new cluster and then register it, the user must have the DMTADMIN (Data Management Admin) role. Therefore, assign the DMTADMIN role to the user, and ensure to map the DMTADMIN role to the ODFADMIN user group.

1. From the ODF Home, select **Data Management Framework**, select **Data Management Tools**, select **DMT Configuration**, select **Register Cluster**, and click **Add Cluster**.
2. Enter the details as shown in the image. In the Livy Service URL field, enter the Livy Server URL of your environment.

**Figure 41: Cluster Configuration**

The screenshot shows the 'Cluster Configurations' form with the following details:

- Name:** OIDFINFO
- Description:** OIDFINFO
- Details Section:**
  - Authentication Type: [Empty]
  - Configuration File Path: [Empty]
  - Principal: [Empty]
  - Keytab File Name: [Empty]
  - KRBS Conf File Name: [Empty]
  - Core Configuration XML: [Empty]
  - HDFS Configuration XML: [Empty]
  - MapReduce Configuration XML: [Empty]
  - Yarn Configuration XML: [Empty]
  - Hive Configuration XML: [Empty]
- SSH Details Section:**
  - SSH Server name: [Empty]
  - SSH Port: [Empty]
  - SSH Auth Alias: [Empty]
- Livy Details Section:**
  - Livy Service URL: http://...in.oracle.com: (highlighted with a red box)
  - Authentication Type: DEFAULT
  - Keytab File Name: [Empty]
  - Principal: [Empty]
  - KRBS Conf File Name: [Empty]
  - Spark Base File Path: [Empty]

3. To populate data in the DIM\_DATES table, navigate to the **Batch Execution** screen. Perform these steps:
  - a. Run the batch `OIDFINFO_POP_DATES_DIM_HIVE`.  
SCD batches (`OIDFINFO_DATA_FOUNDATION_SCD`, `OIDFINFO_DIM_ACCOUNT_SCD`) are sequenced with wait mode **Yes** enabled.

**NOTE** OI DFINFO\_DATA\_FOUNDATION\_SCD and OI DFINFO\_DIM\_ACCOUNT\_SCD batches are made sequential.

- b. Click **Execute Batch**.
4. Monitor the status of the batch in the **Batch Monitor** screen of OFSAAI.
5. Execute T2T Batches in the **Process Modelling Framework**.

**NOTE** In the Process Modelling Framework, the OI DF\_SOURCED\_RUN Runs are made sequential to each other.

## 7.11.4 Verify the External Tables Utility of Oracle

**NOTE** This section is applicable only for the Stage on Hive and Results on RDBMS mode of installation.

After the successful OI DF Application Pack installation in the Big Data mode (Stage on Hive and Results on RDBMS), use the External Tables Utility of Oracle to verify the list of created Hive External Tables. The External Tables Utility of Oracle facilitates Oracle Database to query the data stored outside of the database in the flat files in a way such that they are inside a database. You can create Views and synonyms against these External Tables. As a result, in the Extract Transform and Load (ETL) process of the Data Warehouses, there is no need of staging the data, and you can query the data in parallel. For more information, see [External Tables Concepts](#).

To verify the External Tables created for Big Data, follow these steps:

1. Navigate to the \$FIC\_DB\_HOME/log/OI DF/ directory.
2. Open the CreateExternalTable.log file. This log file consists of the following acknowledgment for the created External Tables:  
Created
3. To verify the External Tables created in the database, follow these steps:
  - a. Open the database application.
  - b. Expand the **Tables** item. A list of External Tables is displayed.
  - c. In the query window, you can execute only the Read queries for these External Tables.

For example:

```
Select * from <external_table_name>;
```

## 7.12 Configuration to Enable the Restatement Support

The Restatement Support feature enables backdated execution for any Start Date and End Date explicitly on a specific list of metadata for the purpose of data refiling in OIDF.

**NOTE** This section is applicable only for RDBMS based installation.

To enable the Restatement Support feature in OIDF, follow these steps:

1. Log in to the application as System Administrator.
2. Navigate to the `$FIC_HOME/ficdb/bin` directory.

**NOTE** Do not edit the `RunSDED.sh` file.

3. Execute the `RunSDED.sh` file with these arguments:

- `$infodom = <Infodom>`
- `$userId = <OFSAA UI User ID>`

For example, `RunSDED.sh <Infodom> <OFSAA UI User ID>`.

4. To check the status of the execution, verify the `sded.log` and `sdedbk.log` files. These logs are generated in the `$FIC_HOME/ficdb/log` directory.

**NOTE** To access the backup of old scripts from the environment, navigate to `$FIC_HOME/scripts_OFS_OIDF/config/insert/postscripts/EnvScriptBkup` directory.

To access the SDED scripts:

- Navigate to `$FIC_HOME/scripts_OFS_OIDF/config/insert/postscripts/sded` directory, in the full installer.
- Navigate to `$FIC_HOME/scripts/config/insert/postscripts/sded` directory, in the upgrade installer.

In the `OIDF_CONFIGURATION.sql` file, for the Paramname field, the value of the `IS_SDED_ENABLED` flag is set to 'FALSE' by default. If the `RunSDED.sh` file execution is successful, this flag is set to 'TRUE'.

## 7.13 Create the Application Users

Create the application users in the OFSAA setup before use.

For details, see the [User Administrator](#) section in the *Oracle Financial Services Analytical Applications Infrastructure User Guide Release 8.1.0.0.0*.

## 7.14 Map the Application User(s) to User Group

User *UserGroup Map* facilitates you to map user(s) to a specific user group which in turn is mapped to a specific Information Domain and role. Every user group mapped to the Information Domain needs to be authorized. Else, it cannot be mapped to users.

User *UserGroup Map* screen displays details such as User ID, Name, and the corresponding Mapped Groups. You can view and modify the existing mappings within the User *UserGroup* Maintenance screen.

Starting with the OFSAA 8.1 release, with the installation of the OIDF Application Pack, preconfigured Application user groups are seeded. These user groups are unique to every OFSAA Application Pack and have application roles pre-configured.

You can access the User *UserGroup Map* by expanding the Identity Management section within the tree structure of the LHS menu.

**Table 38: Seeded User Groups**

| Name              | Description                                                                                                                                                                                                                                   |
|-------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| OIDF Admin        | A user mapped to this group will have access to all the menu items for the entire OIDF Application. The exclusive menus which are available only to this group of users are Application Preference and Global Preference under Settings Menu. |
| OIDF Data Modeler | A user mapped to this group will have access only to Data Model Management and Metadata Browser Menus.                                                                                                                                        |
| OIDF Analyst      | A user mapped to this group will have access to Data Management Framework, Dimension Management, and Metadata Browser Menus.                                                                                                                  |
| OIDF Operator     | A user mapped to this group will have access to Rule Run Framework and Operations Menus.                                                                                                                                                      |

## 7.15 Change the ICC Batch Ownership

All the seeded Batches in the OIDF application are automatically assigned to the SYSADMN user during installation. To see the batches in the **Batch Maintenance** menu, you must execute the following query in the Config Schema of the database:

```
begin
AAI_OBJECT_ADMIN.TRANSFER_BATCH_OWNERSHIP ('fromUser','toUser','infodom');
end;
OR
begin
AAI_OBJECT_ADMIN.TRANSFER_BATCH_OWNERSHIP ('fromUser','toUser');
end;
```

Where:

- `fromUser` indicates the user who currently owns the batch
- `toUser` indicates the user to whom the ownership must be transferred
- `infodom` is an optional parameter. If specified, the ownership of the batches of that Infodom will be changed.

Example:

```
begin
AAI_OBJECT_ADMIN.TRANSFER_BATCH_OWNERSHIP
('SYSADMIN','OIDFOP','OFSOIDFINFO');
end;
```

## 7.16 Add TNS entries in the TNSNAMES.ORA File

See the [Add TNS entries in the TNSNAMES.ORA File](#) section in the *OFSAAI Release 8.1.0.0.0 Installation and Configuration Guide* for details.

## 7.17 Configure Transparent Data Encryption (TDE) and Data Redaction in OFSAA

See the [Configure Transparent Data Encryption \(TDE\) and Data Redaction in OFSAA](#) section in the *OFSAAI Release 8.1.0.0.0 Installation and Configuration Guide* for details.

## 7.18 Implement Data Protection in OFSAA

See the [Oracle Insurance Data Foundation Application Pack Data Protection Implementation Guide Release 8.1.x](#) for details.

# Part II

**Topics:**

- [Upgrade](#)

# 8 Upgrade

## Topics:

- [Upgrade Scenarios](#)
- [Perform the Data Model Upload Outside of the Installer](#)
- [Prepare for Upgrade](#)
- [Upgrade from Oracle Insurance Data Foundation Application Pack Release v8.0.x on AIX or Solaris x86 Operating System](#)
- [Upgrade from OIDF v8.0.5.0.0 or Earlier Versions to OIDF v8.0.6.0.0 or a Higher Version](#)
- [Upgrade from OIDF v8.0.6.0.0 or a Higher Version to OIDF v8.1.0.0.0](#)
- [Upgrade OIDF Application Pack to v8.1.0.0.0 on an Existing OFSAA Instance](#)

### NOTE

- The user profile executing the installation must have the permission on `/tmp` before installation.
- Sufficient space must be available in `/tmp` before installation, else the installation will terminate, and logs are not generated.

## 8.1 Upgrade Scenarios

### ATTENTION

Ensure you run the upgrade installer only on the cloned environment.

Table 39: OIDF Release 8.1.0.0.0 Upgrade Scenarios

| Scenario                                                                                                                                                                                                                                                                                                       | Installation and Upgrade Instructions                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <a href="#">Upgrade from Oracle Insurance Data Foundation Application Pack Release v8.0.x on AIX or Solaris x86 Operating System</a>                                                                                                                                                                           | Release v8.1.0.0.0 of Oracle Insurance Data Foundation Application Pack is not certified for AIX and Solaris x86 Operating Systems. If you are currently running OFSAA v8.0.x on AIX or Solaris x86 Operating Systems and plan to upgrade to Release v8.1.0.0.0, then you must migrate from AIX or Solaris x86 to Linux or Solaris SPARC. See the MOS Doc ID <a href="#">2700084.1</a> for details.                                                                                                                                                                                                                                                                                              |
| <a href="#">Upgrade from OIDF v8.0.5.0.0 or Earlier Versions to OIDF v8.0.6.0.0 or a Higher Version</a><br><br>In this scenario, you are upgrading the OIDF application pack from the Release v8.0.5.0.0 or an earlier version to the Release v8.0.6.0.0 or a higher version. Then upgrade to OIDF v8.1.0.0.0. | <ol style="list-style-type: none"> <li>1. <a href="#">Upgrade</a> your current OIDF version to the OIDF v8.0.6.0.0 or later versions.</li> <li>2. <a href="#">Clone</a> your existing environment to the <a href="#">OFSAA Technology Matrix v8.1.0.0.0</a>.</li> <li>3. <a href="#">Upgrade</a> from OIDF v8.0.6.0.0 or a later version to OIDF v8.1.0.0.0.</li> <li>4. Run the <a href="#">Environment Check Utility</a> tool and ensure that the hardware and software are installed as per the <a href="#">OFSAA Technology Matrix v8.1.0.0.0</a>.</li> <li>5. <a href="#">Update</a> the <code>OFS_OIDF_PACK.xml</code> file to enable ONLY the existing installed applications.</li> </ol> |

| Scenario                                                                                                                                                                                                                                                                                                                                                                                                                     | Installation and Upgrade Instructions                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <p><b>Example:</b> You are using the OIDF v8.0.5.0.0 release and now want to upgrade to the OIDF v8.1.0.0.0.</p>                                                                                                                                                                                                                                                                                                             | <ol style="list-style-type: none"> <li>6. <a href="#">Update</a> the <code>Silent.props</code> file present in the OIDF v8.1.0.0.0 installer pack.</li> <li>7. <a href="#">Trigger</a> the installation.</li> </ol>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| <p><a href="#">Upgrade from OIDF v8.0.6.0.0 or a Higher Version to OIDF v8.1.0.0.0</a></p> <p>In this scenario, you are upgrading the OIDF Application Pack from Release v8.0.7.0.0 or higher versions to Release v8.1.0.0.0.</p>                                                                                                                                                                                            | <ol style="list-style-type: none"> <li>1. <a href="#">Perform</a> the Data Model upload outside of the installer (Execute the <code>ModelUpgrade.sh</code> file for the Prescripts to backup and delete the data, and then to backup and delete the metadata).</li> <li>2. <a href="#">Clone</a> your existing environment to the <a href="#">OFSAA Technology Matrix v8.1.0.0.0</a>.</li> <li>3. Run the <a href="#">Environment Check Utility</a> tool and ensure that the hardware and software are installed as per the <a href="#">OFSAA Technology Matrix v8.1.0.0.0</a>.</li> <li>4. <a href="#">Update</a> the <code>OFS_OIDF_PACK.xml</code> file to enable ONLY the existing installed applications.</li> <li>5. <a href="#">Update</a> the <code>Silent.props</code> file present in the OIDF v8.1.0.0.0 installer pack.</li> <li>6. <a href="#">Trigger</a> the installation.</li> <li>7. <a href="#">Execute</a> the <code>ModelUpgrade.sh</code> file for the Postscripts to restore the data and then metadata.</li> </ol> |
| <p><a href="#">Upgrade OIDF Application Pack to v8.1.0.0.0 on an Existing OFSAA Instance</a></p> <p>In this scenario, an Application Pack of v8.1.0.0.0 is already installed and now you need to upgrade OIDF Application Pack from v.8.0.6.0.0 or a later version to v8.1.0.0.0.</p> <p><b>Example:</b> OFS ALM v8.1.0.0.0 Application Pack is already installed and now you need to install the OIDF Application Pack.</p> | <ol style="list-style-type: none"> <li>1. <a href="#">Perform</a> the Data Model upload outside of the installer (Execute the <code>ModelUpgrade.sh</code> file for the Prescripts to backup and delete the data, and then to backup and delete the metadata).</li> <li>2. <a href="#">Update</a> the <code>OFS_OIDF_PACK.xml</code> file of the OIDF Application Pack.</li> <li>3. <a href="#">Update</a> the <code>Silent.props</code> file of the OIDF Application Pack.</li> <li>4. <a href="#">Run</a> the schema creator utility ONLY for the OIDF Application Pack.</li> <li>5. <a href="#">Trigger</a> the installation.</li> <li>6. <a href="#">Execute</a> the <code>ModelUpgrade.sh</code> file for the Postscripts to restore the data and then metadata.</li> </ol>                                                                                                                                                                                                                                                          |

## 8.2 Perform the Data Model Upload Outside of the Installer

This section is applicable if you are performing the OIDF v8.1 OOB Data Model upload outside of the installer. A utility is introduced called the ModelUpgrade utility, which is packaged in this release of the OIDF OOB Data Model patch. This utility enables the Upgrade installation using the Incremental model upload process. The two execution processes supported in the ModelUpgrade utility are as follows:

- [Execute the ModelUpgrade.sh File for the Prescripts](#)
- [Execute the ModelUpgrade.sh File for the Postscripts](#)

### 8.2.1 Execute the ModelUpgrade.sh File for the Prescripts

Execute the OIDF `ModelUpgrade.sh` file for the Prescripts to backup and delete the data, and then to backup and delete the metadata. Then proceed with the merged model upload and the OIDF Application Pack upgrade to v8.1.0.0.0.

For detailed information, see the *Execute the ModelUpgrade.sh file for the Prescripts and OIDF Application Pack Upgrade Process* sections in the [Oracle Insurance Data Foundation Application Pack Upgrade Guide Release 8.1.0.0.0](#).

## 8.3 Prepare for Upgrade

This section provides information about the preparations that need to be done before proceeding with the upgrade installation.

### Topics:

- [Download the OIDF Application Pack Installer and Data Model](#)
- [Prepare the Environment for Upgrade](#)

### 8.3.1 Download the OIDF Application Pack Installer and Data Model

This section provides the details of the download that you need to complete before triggering the application installation.

### Topics:


- [Download the OIDF Application Pack Installer](#)
- [Download the Data Model](#)
- [Download and Install the Mandatory Patch](#)

#### 8.3.1.1 Download the OIDF Application Pack Installer

To download the OIDF Application Pack installer Release v8.1.0.0.0, follow these steps:

1. Log in to the [Oracle Software Delivery Cloud](#) with a valid Oracle account.

Figure 42: Oracle Software Delivery Cloud Login Page



2. Search for the full product name **Oracle Insurance Data Foundation** and download the installer archive for this release version.

3. Copy the installer archive into the download directory (in Binary mode) in the setup identified for the OI DF Application Pack installation.

### 8.3.1.2 Download the Data Model

To download the OI DF OOB v8.1.0.0.0 Data Model, follow these steps:

**NOTE** This is an optional section that is applicable if you are performing the customized model upload. The ModelUpgrade utility is packaged in this OI DF OOB Data Model patch.

1. Log in to the [My Oracle Support \(MOS\)](#) with a valid Oracle account.
2. In the **Patches & Updates** tab, search for the OI DF Data Model installer patch **31924513** and download the patch. See the Readme available with the patch for further instructions on downloading the patch and extracting the erwin files.

For detailed instructions to perform the OI DF v8.1.0.0.0 OOB Data Model upload outside of the installer, see the [Oracle Insurance Data Foundation Application Pack Upgrade Guide Release 8.1.0.0.0](#).

### 8.3.1.3 Download and Install the Mandatory Patch

The following table includes information about the mandatory patches that must be installed during the OI DF Application Pack upgrade installation.

**Table 40: Mandatory Patches**

| One-Off Patch   | Description                                                                                                                                                                                                                                                                                                                                 |
|-----------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>31509494</b> | Download and install this mandatory OFSAAI one-off patch. This is a mandatory Pre-installation requirement for the OI DF Application Pack upgrade installation from the 8.0.x versions to the 8.1.0.0.0 version on the Solaris operating system. For information about installing the patch, see the ReadMe document attached to the patch. |
| <b>33663417</b> | Download this mandatory OFSAAI One-Off Patch. See the <b>ATTENTION</b> below.                                                                                                                                                                                                                                                               |

**ATTENTION** For the Mandatory Patch ID **33663417**:

On the 10th of December 2021, Oracle released the Security Alert CVE-2021-44228 in response to the disclosure of a new vulnerability affecting Apache Log4J prior to version 2.15. The application of the **33663417** Mandatory Patch fixes the issue.

For details, see the My Oracle Support Doc ID [2827801.1](#).

Ensure that whenever any New or Upgrade or an Incremental Installation Release is applied, the OFSAAI Mandatory Patch **33663417** for Log4J must be reapplied.

### 8.3.2 Prepare the Environment for Upgrade

Before you plan to upgrade any of your application packs to Release 8.1.0.0, ensure that all the application packs in your current OFSAA instance are available in the Release 8.1.0.0 version. Contact [My Oracle Support \(MOS\)](#) for more information about the release version details.

1. Backup the following environment file from the `OFS_OIDF_PACK/conf/` directory:
  - `OFS_OIDF_PACK.xml`
2. Backup the following environment files from the `OFS_OIDF_PACK/schema_creator/conf/` directory:
  - `DBMASTER_SC.xml`
  - `OFS_OIDF_SCHEMA_IN.xml`
  - `OFS_OIDF_SCHEMA_BIGDATA_IN.xml`
3. Backup the following environment file from the `OFS_OIDF_PACK/OFS_AAI/conf/` directory:
  - `OFSAAI_InstallConfig.xml`
4. Ensure that the following property files are present in the `OFS_OIDF_PACK/appsLibConfig/conf/` directory and make a backup:
  - `Silent_upgrade_from_806.template`
5. See [Oracle Financial Services Analytical Applications 8.1.0.0 Technology Matrix](#) for the hardware and software required to upgrade to the OIDF Application Pack Release 8.1.0.0.
6. Enable unlimited cryptographic policy for Java. For more information, see the *Enabling Unlimited Cryptographic Policy* section in the [Oracle Financial Services Advanced Analytical Applications Infrastructure Administration and Configuration Guide Release 8.1.x](#).
7. Clone your environment. For more information, see the [Oracle Financial Services Analytical Applications Infrastructure Cloning Reference Guide Release 8.0.x](#).

## 8.4 Upgrade from Oracle Insurance Data Foundation Application Pack Release v8.0.x on AIX or Solaris x86 Operating System

Release v8.1.0.0 of Oracle Insurance Data Foundation Application Pack is not certified for AIX and Solaris x86 Operating Systems. If you are currently running OFSAA v8.0.x on AIX or Solaris x86 Operating Systems and plan to upgrade to Release v8.1.0.0, then you must migrate from AIX or Solaris x86 to Linux or Solaris SPARC. See the MOS Doc ID [2700084.1](#) for details.

## 8.5 Upgrade from OIDF v8.0.5.0.0 or Earlier Versions to OIDF v8.0.6.0.0 or a Higher Version

If you are upgrading OIDF Application Pack from a release prior to v8.0.6.0.0:

1. Upgrade OIDF to v8.0.6.0.0 or later versions. For more information, see the corresponding version-specific [Oracle Insurance Data Foundation Application Pack Installation and Configuration Guide](#).

2. Upgrade from OIDF v8.0.6.0.0 or later versions to OIDF v8.1.0.0.0. For more information, see [Upgrade from OIDF v8.0.6.0.0 or a Higher Version to OIDF v8.1.0.0.0](#).

**NOTE**

The minimum supported version of OIDF is v8.0.6.0.0

## 8.6 Upgrade from OIDF v8.0.6.0.0 or a Higher Version to OIDF v8.1.0.0.0

This section provides information about upgrading the OIDF Application Pack from Release v8.0.6.0.0 or a higher version to Release v8.1.0.0.0.

For example, you are using OIDF v8.0.7.0.0 and now want to upgrade to the OIDF v8.1.0.0.0.

**NOTE**

If upgrading OIDF Application Pack from a version before OIDF v8.0.6.0.0, then first upgrade to OIDF v8.0.6.0.0 or a higher version. To upgrade to OIDF v8.0.6.0.0 or a higher version, see the corresponding version-specific [Oracle Insurance Data Foundation Application Pack Installation and Configuration Guide](#).

**Topics:**

- [Clone Your Existing Environment](#)
- [Extract the Software](#)
- [Update the OFS\\_OIDF\\_PACK.xml File](#)
- [Update the Silent.props File](#)
- [Trigger the Installation](#)
- [Verify the Log File Information](#)
- [Post-installation Steps](#)
- [Additional Configuration](#)

### 8.6.1 Clone Your Existing Environment

Clone your existing environment to the v8.1.0.0.0 of [OFSAA Technology Matrix](#). For more information, see the [Oracle Financial Services Analytical Applications Infrastructure Cloning Reference Guide Release 8.0.x](#).

**NOTE**

If the OIDF Application Pack v8.0.7.0.0 or higher version is already installed on the Oracle Financial Services Analytical Applications 8.1.0.0.0 Technology Matrix, then you can switch the Oracle Client from 12c to 19c, and update the `.profile` file accordingly.

In this scenario, you can skip the environment Cloning. Switching is done only for v8.1.0.0.0. The Application Pack works only after the upgrade to v8.1.0.0.0 is complete.

## 8.6.2 Extract the Software

You must be logged in to the UNIX operating system as a non-root user to perform the following steps. To extract the OIDF Application Pack software, follow these steps:

1. Download the unzip utility (OS-specific) `unzip_<os>.Z` and copy it in Binary mode to the directory that is included in your PATH variable.

If you already have an unzip utility to extract the contents of the downloaded archive, skip this step. Uncompress the unzip installer file with the command:

```
uncompress unzip_<os>.Z
```

**NOTE**

If an error message "uncompress: not found [No such file or directory]" is displayed, contact your UNIX administrator.

2. Assign 751 permission to the file with the following command:

```
chmod 751 unzip_<os>
```

For example, `chmod 751 unzip_sparc`

3. Extract the contents of the OIDF Application Pack Release v8.1.0.0.0 installer archive file in the download directory with the following command:

```
unzip OFS_OIDF_8.1.0.0.0_<Operating_System>.zip
```

**NOTE**

Do not rename the Application Pack installer folder name on extraction from the archive.

4. Log in to OFSAA Infrastructure Config Schema and execute the following SQL query:

```
ALTER TABLE CONFIGURATION MODIFY PARAMNAME VARCHAR2 (100 CHAR);
```

5. For Solaris OS, extract the one-off patch **31509494**. See the ReadMe packaged with the patch for further instructions on how to install the patch.

**NOTE**

This is a mandatory Pre-installation requirement for the OIDF Application Pack upgrade installation from the 8.0.x versions to the 8.1.0.0.0 version on the Solaris operating system.

- Navigate to the Download Directory and assign 750 permission to the installer directory with the following command:

```
chmod -R 750 OFS_OIDF_PACK
```

### 8.6.3 Update the OFS\_OIDF\_PACK.xml File

Update the OFS\_OIDF\_PACK.xml file. Enable only the existing installed Application Packs.

To configure the OFS\_OIDF\_PACK.xml file, follow these steps:

- Navigate to the <INSTALLER\_DIRECTORY>/OFS\_OIDF\_PACK/conf directory.
- Rename the OFS\_OIDF\_PACK.xml file to OFS\_OIDF\_PACK.xml.template
- Open the OFS\_OIDF\_PACK.xml file in a text editor.
- Update the OFS\_OIDF\_PACK.xml file as mentioned in the following table only for the specified parameter.

#### NOTE

For the Big Data mode of installation, enable the option as **YES** for the **APP\_ID** parameter with the value **OFS\_AAIB** as illustrated in the sample.

Figure 43: Sample OFS\_OIDF\_PACK.xml File with the Update for Upgrade

```
<APP_PACK_CONFIG>
 <APP_PACK_ID>OFS_OIDF_PACK</APP_PACK_ID>
 <APP_PACK_NAME>Oracle Insurance Foundation Pack</APP_PACK_NAME>
 <APP_PACK_DESCRIPTION>Applications forming analytics foundation such for the Insurance Domain
</APP_PACK_DESCRIPTION>
 <VERSION>8.1.0.0.0</VERSION>
 <APP>
 <APP_ID PREREQ="" DEF_SEL_FLG="YES" ENABLE="YES">OFS_AAI</APP_ID>
 <APP_NAME>Financial Services Analytical Applications Infrastructure</APP_NAME>
 <APP_DESCRIPTION>Base Infrastructure for Analytical Applications</APP_DESCRIPTION>
 <VERSION>8.1.0.0.0</VERSION>
 </APP>
 <APP>
 <APP_ID PREREQ="OFS_AAI" ENABLE="YES">OFS_OIDF</APP_ID>
 <APP_NAME>Oracle Insurance Data Foundation</APP_NAME>
 <APP_DESCRIPTION>Data Foundation for Insurance domain</APP_DESCRIPTION>
 <VERSION>8.1.0.0.0</VERSION>
 </APP>
</APP_PACK_CONFIG>
```

**Table 41: Update Specific Parameters in the OFS\_OIDF\_PACK.xml file**

| Tag Name | Attribute Name | Description                       | Mandatory (Y/N)                       | Comments                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
|----------|----------------|-----------------------------------|---------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| APP_ID   | ENABLE         | Enable the Application or Product | YES if installing in the SILENT mode. | <p>The default value is YES for Infrastructure.<br/>The default value is NO for Others.<br/>Permissible values are YES and NO.<br/>Set this attribute value to YES against every APP_ID, which is licensed and should be enabled for the upgrade.</p> <p><b>NOTE:</b> You cannot disable the Application or Product after you enable it. However, the Application or Product not enabled during installation can be enabled later through the Administration UI.</p> |

5. Save the file.

## 8.6.4 Update the Silent.props File

This section provides information about the `Silent.props` file configuration for OIDF upgrade installation.

### Topics:

- [Silent Upgrade to OIDF v8.1.0.0.0 for RDBMS](#)

### ATTENTION

Do not install the new applications in the same segment if the preinstalled applications use Run Management.

### 8.6.4.1 Silent Upgrade to OIDF v8.1.0.0.0 for RDBMS

This section is applicable only for the RDBMS mode of OIDF v8.1.0.0.0 upgrade installation.

### NOTE

In an integrated environment, Oracle recommends the customers use the same Staging source in the `Silent.props` file for the T2Ts that load data from the Stage tables into the Result tables.

To configure the `Silent.props` file to upgrade to the OIDF Application Pack Release 8.1.0.0.0, follow these steps:

1. Navigate to the installer kit `OFS_OIDF_PACK/appsLibConfig/conf/` directory.
2. Rename the `Silent_upgrade_from_806.template` file to `Silent.props`.
3. Update the `Silent.props` file and mention the following parameters:

**Table 42: Parameters for the Silent.props File (Silent\_upgrade\_from\_806.template for RDBMS)**

| Property Name         | Description of Property                                                                              | Permissible values                                   | Comments                                                                                                                                            |
|-----------------------|------------------------------------------------------------------------------------------------------|------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------|
| LOG_MODE              | Mode for logging                                                                                     | 1 = Debug<br>0 = General                             | #Optional<br>Default: 0                                                                                                                             |
| SEGMENT_1_CODE        | Segment Code                                                                                         | Example: OI DFSEG                                    | #Mandatory<br>The Segment Code must be the same as the code that is used during the first OIDF installation (Base Pack).                            |
| APPFTP_LOG_PATH       | Information Domain Maintenance log path (to be created) for the new Information Domain for App Layer | Example:<br>/ftpshare/<INFODOM_NAME>/logs            | #Mandatory<br>Information Domain Maintenance log path must be the same as the log path that is used during the first OIDF installation (Base Pack). |
| DBFTP_LOG_PATH        | Information Domain Maintenance log path (to be created) for the new Information Domain for DB Layer  | Example:<br>/ftpshare/<INFODOM_NAME>/logs            | #Mandatory<br>Information Domain Maintenance log path must be the same as the log path that is used during the first OIDF installation (Base Pack). |
| UPLOAD_MODEL          | Whether you need to perform Model Upload                                                             | 0 = No<br>1 = Yes                                    | #Mandatory                                                                                                                                          |
| MODEL_TYPE            | Released Data Model or Customized Data Model                                                         | 0 = released Data Model<br>1 = customized Data Model | # Mandatory<br>Only when UPLOAD_MODEL=1                                                                                                             |
| DATAMODEL             | The file name for the customized Data Model                                                          | Not Applicable                                       | # Mandatory<br>Only when uploading the customized Data Model.<br># Option selected for MODEL_TYPE=1                                                 |
| DM_DIRECTORY          | The path for the customized Data Model                                                               | Not Applicable                                       | #Mandatory<br>Only when uploading the customized Data Model.<br># Option selected for MODEL_TYPE=1                                                  |
| ETL_APPSRC_TYPE       | The ETL application name                                                                             | 0=New Pair<br>1=Existing                             | #Mandatory                                                                                                                                          |
| ETL_NEW_SRCS_REQUIRED | Whether ETL new sources are required                                                                 | N                                                    | #Mandatory                                                                                                                                          |
| ENABLE_CONCURRENCY    | #Support for Parallelism                                                                             | 0 = No<br>1 = Yes                                    | #Optional                                                                                                                                           |
| CONCURRENCY_LEVEL     | #Support for Parallelism                                                                             | Example:                                             | #Optional                                                                                                                                           |

| Property Name | Description of Property | Permissible values                                                                             | Comments |
|---------------|-------------------------|------------------------------------------------------------------------------------------------|----------|
|               |                         | CONCURRENCY_LEVEL=10, which means 10 threads are triggered to handle the processing of fsapps. |          |

4. Save the file.

## 8.6.5 Trigger the Installation

You are upgrading OIDF Application Pack from Release 8.0.6.0.0 or later to Release 8.1.0.0.0.

For example, you are using release 8.0.7.0.0 and now want to upgrade to Release 8.1.0.0.0.

### NOTE

If upgrading from a version before OIDF v8.0.6.0.0, then first upgrade to v8.0.6.0.0 or a higher version. To upgrade to OIDF v8.0.6.0.0, see the corresponding version-specific [Oracle Insurance Data Foundation Application Pack Installation and Configuration Guide](#).

To upgrade the OIDF Application Pack from Release v8.0.6.0.0 or higher versions to Release v8.1.0.0.0, follow these steps:

1. Ensure that you have completed the following steps:
  - a. [Download](#) the installer.
  - b. [Perform](#) the prerequisites for installation.
  - c. [Prepare](#) the environment for Upgrade.
  - d. [Clone](#) your existing environment.
  - e. [Extract](#) the software.
  - f. [Update](#) the `OFS_OIDF_PACK.xml` file.
  - g. [Update](#) the `Silent.props` file.

### NOTE

Ensure you have downloaded and applied the mandatory OFSAI one-off patch **31509494**. This is a mandatory Pre-installation requirement for the OIDF Application Pack upgrade installation from the 8.0.x versions to the 8.1.0.0.0 version on the Solaris operating system.

2. Enter the following command in the console to execute the OIDF Application Pack installer with the Silent option:
 

```
./setup.sh SILENT
```
3. The installer proceeds with the Pre-Installation Checks.

4. Enter the OFSAA Processing Tier FTP/SFTP password value and proceed, when prompted in the command prompt.

**Figure 44: OFSAA Processing Tier FTP/SFTP Password Prompt**

```

* Welcome to Oracle Financial Services Analytical Applications Infrastructure (OFS AAI) Installation *

Checking Infrastructure installation status ...
Infrastructure installation does not exist. Proceeding with Infrastructure installation ...
Triggering Infrastructure installation ...

Please enter Infrastructure Application/Database component FTP/SFTP password : █
```

**NOTE** Enter the password to access the Product Staging or Metadata repository directory FTPSHARE in the application server.

5. The process displays the OFSAA License. Enter **Y** and proceed.

**Figure 45: Accept the OFSAA License Agreement**

```

OFSAA APPLICATION PACK LICENSE AGREEMENT

* Oracle Financial Services Analytical Applications (OFSAA) application packs are groups of OFSAA products packaged together into a single installer. Each application pack contains OFSAA applications that address specific functional domains.*
* Every application pack also includes the following OFSAA infrastructure application options which are automatically installed by every application pack installer:
1. Oracle Financial Services Analytical Applications Infrastructure
2. Oracle Financial Services Enterprise Modeling
3. Oracle Financial Services Big Data Processing
* Oracle Financial Services Analytical Applications Infrastructure (OFS AAI) is the base infrastructure for all OFSAA applications and is therefore automatically installed and enabled by the application pack installer.*
* The application pack installer always installs Oracle Financial Services Enterprise Modeling, Oracle Financial Services In-line Processing Engine and Oracle Financial Services Big Data Processing application options along with the application pack applications, but enables them only if any application that requires their functionality is enabled.*
* Any OFSAA application that is enabled must be licensed for use. Oracle Financial Services Analytical Applications Infrastructure, Oracle Financial Services Enterprise Modeling, Oracle Financial Services In-line Processing Engine and Oracle Financial Services Big Data Processing are individually licensable application options.*
* Application products once enabled cannot be disabled. Application products not enabled on installation, may later be enabled using the "Manage OFSAA Product License(s)" feature of the platform.*

Are you accepting the terms and conditions mentioned above? [Y/N]:
█
```

6. The installer installs the OFSAAI application.

**Figure 46: OFSAAI Silent Mode Installation**

```
taller:
1. Oracle Financial Services Analytical Applications Infrastructure
2. Oracle Financial Services Enterprise Modeling
3. Oracle Financial Services Big Data Processing
* Oracle Financial Services Analytical Applications Infrastructure (OFS AAI) is the base infrastructure for all OFSAA applications and is therefore automatically installed and enabled by the application pack installer.*
* The application pack installer always installs Oracle Financial Services Enterprise Modeling, Oracle Financial Services In-line Processing Engine and Oracle Financial Services Big Data Processing application options along with the application pack applications, but enables them only if any application that requires their functionality is enabled.*
* Any OFSAA application that is enabled must be licensed for use. Oracle Financial Services Analytical Applications Infrastructure, Oracle Financial Services Enterprise Modeling, Oracle Financial Services In-line Processing Engine and Oracle Financial Services Big Data Processing are individually licensable application options.*
* Application products once enabled cannot be disabled. Application products not enabled on installation, may later be enabled using the "Manage OFSAA Product License(s)" feature of the platform.*

Are you accepting the terms and conditions mentioned above? [Y/N]:
Y
log4j:WARN No appenders could be found for logger (org.apache.commons.vfs2.impl.StandardFileManager).
log4j:WARN Please initialize the log4j system properly.
log4j:WARN See http://logging.apache.org/log4j/1.2/faq.html#noconfig for more info.
hostname is [redacted] oracle.com
hostname is [redacted] oracle.com
Starting installation...
Preparing to install...
Extracting the installation resources from the installer archive...
Configuring the installer for this system's environment...

Launching installer...

Preparing SILENT Mode Installation...

=====
OFSAAInfrastructure (created with InstallAnywhere)
=====

Installing...

[-----]
[-----]
[-----]
```

7. After OFSAAI is installed, the OIDF Application Pack installation begins.

**Figure 47: OIDF Application Pack Installation**

```

Installation Complete.
THE OS VERSION IS: 7
THE CLIENT VERSION IS: 19
Copying done for BE files...
heapsize == 8192
/scratch/██████/kit/OFS_OIDF_PACK/bin
datamodel file = ../DataModel/Manifest.xml ../DataModel/OFS_OIDF_Datamodel.xml
model == 66154337
630
checking version
VersionToBeApplied: 8.1.0.0.0
Fresh installation

Welcome to OFS_OIDF PACK Installation

Starting OFSAA Service...

```

**NOTE**

- The Data Model upload may take several hours to complete. You can check the installation logs in the `/OFS_OIDF_PACK/OFS_OIDF/logs/` directory.
- For the existing customers, with the DB XML, the time taken for the Data Model upload will be significantly reduced. You can upload the warehouse data from the operational systems to the database schema using the erwin XML or Database XML file. Using the stand-alone command-line utility for the `TransformErwin.sh` file, you can transform erwin XML into Database XML, and use the DB XML instead of erwin XML to speed up the model upload process. For more information, see the *Command Line Utility for Transforming erwin XML to Database XML* section in the [Oracle Financial Services Advanced Analytical Applications Infrastructure User Guide Release 8.1.0.0.0](#).

**Figure 48: OIDF Application Pack Installation Complete**

```

Starting OFSAA Service...
OFSAA Service - OK
Preparing to install...
Extracting the installation resources from the installer archive...
Configuring the installer for this system's environment...

Launching installer...

Preparing SILENT Mode Installation...

=====
pack_installsilent (created with InstallAnywhere)
=====

Installing...

[=====|=====|=====|=====]
[-----|-----|-----|-----]

Installation Complete.
failurecount --- 0
Core Installation completed successfully
tempdir ---- /scratch/██████/kit/OFS_OIDF_PACK
Checking for hive app. ████████

***** Checking for Fresh app : OFS_OIDF *****
path before app installation: /scratch/██████/kit/OFS_OIDF_PACK
inside checkappstatus-app OFS_OIDF /scratch/██████/kit/OFS_OIDF_PACK/bin
all value /scratch/██████/kit/OFS_OIDF_PACK/bin
In app value
[AppStatusCheck] Checking for app installation OFS_OIDF
[AppStatusCheck] app is selected and ENABLED in db
app status returned: 0
current directory after app installation: /scratch/██████/kit/OFS_OIDF_PACK/OFS_OIDF
Checking for available options...
List of options available:
Pack Name found is: OFS_OIDF_PACK
Utility triggered for XML files

```

8. When the installation is complete, the following message is displayed in the console:  
*Installation completed...*
9. The OFSAA Infrastructure installation performs a post-install health check automatically on the successful installation of the product.
10. To verify if the release is applied successfully, check the log files mentioned in the section [Verify the Log File Information](#).

**NOTE**

If any applications are installed on top of the OFS AAI Application Pack 8.1.0.0.0 version, execute the script `update_dq_batches_optional_params.sql`, which is available in the folder `$FIC_HOME/Post_AAI_Migration`, after the installation of the applications.

11. For more information on securing your OFSAA Infrastructure, refer to the [Oracle Financial Services Analytical Applications Infrastructure Security Guide Release 8.1.x](#).
12. After successful installation, perform the Post-installation procedures. For detailed information, see the [Post-installation](#) section.
13. Perform the necessary [Additional Configuration](#).

**NOTE**

The DMT screens are no more managed with a generic function since AAI v8.1.0.0.0. Starting from AAI v8.0.6.0.0, each action performed in the DMT screens require specific user roles and functions for various operations. Therefore, OI DF has up taken the user roles and functions available for the AAI v8.1.0.0.0 DMT screens. From v8.1.0.0.0, OI DF and AAI support only new functions and the new user roles mapped to the user groups.

## 8.6.6 Verify the Log File Information

See the following logs files for more information:

- Pack\_Install.log file in the O FS\_OI DF\_PACK/logs/ directory.
- The O FS\_OI DF\_installation.log file and the O FS\_OI DF\_installation.err file in the O FS\_OI DF\_PACK/O FS\_OI DF/logs directory.
- Infrastructure installation log files in the O FS\_OI DF\_PACK/O FS\_AAI/logs/ directory.
- The OFSAAInfrastructure\_Install.log file in the \$FIC\_HOME directory.

**ATTENTION**

- You can ignore the "ORA-00001: unique constraint" error, and Object already exists and Table has a primary key warnings for the OFSA\_CATALOG\_OF\_LEAVES table in the log file.
- In case of any other errors, contact [My Oracle Support \(MOS\)](#).

## 8.6.7 Post-installation Steps

Follow the steps mentioned in the [Post-installation](#) section.

**Topics:**

- [Execute the ModelUpgrade.sh file for the Postscripts](#)

### 8.6.7.1 Execute the ModelUpgrade.sh File for the Postscripts

This section is applicable if you have performed the OI DF v8.1.0.0.0 OOB Data Model upload outside of the installer.

After the successful upgrade of the OIDF Application Pack to the v8.1.0.0.0 release, execute the `OIDF ModelUpgrade.sh` file for Postscripts to restore the data and the metadata.

For detailed information, see the *Execute the ModelUpgrade.sh file for the Postscripts and OIDF Application Pack Upgrade Process* sections in the [Oracle Insurance Data Foundation Application Pack Upgrade Guide Release 8.1.0.0.0](#).

## 8.6.8 Additional Configuration

For additional configuration information, see the [Additional Configuration](#) section.

## 8.7 Upgrade OIDF Application Pack to v8.1.0.0.0 on an Existing OFSAA Instance

In this upgrade installation scenario, an Application Pack of v8.1.0.0.0 is already installed and now you need to upgrade OIDF Application Pack from v.8.0.6.0.0 or a later version to v8.1.0.0.0. For example, OFS ALM v8.1.0.0.0 Application Pack is already installed and now you need to install the OIDF Application Pack.

### NOTE

If you are upgrading the OFSAA Application Pack to the release v8.1.0.0.0, to ensure successful deployment, you must upgrade the other packs installed in the same environment to the release v8.1.0.0.0.

### Topics:

- [Extract the Software](#)
- [Update the OFS\\_OIDF\\_PACK.xml File](#)
- [Update the Silent.props File](#)
- [Execute the Schema Creator Utility Only for the OIDF Application Pack](#)
- [Trigger the Installation](#)
- [Verify the Log File Information](#)
- [Post-installation Steps](#)
- [Additional Configuration](#)

### 8.7.1 Extract the Software

You must be logged in to the UNIX operating system as a non-root user to perform the following steps. To extract the OIDF Application Pack software, follow these steps:

1. Download the unzip utility (OS-specific) `unzip_<os>.z` and copy it in Binary mode to the directory that is included in your PATH variable.

If you already have an unzip utility to extract the contents of the downloaded archive, skip this step. Uncompress the unzip installer file with the command:

```
uncompress unzip_<os>.Z
```

**NOTE** If an error message "uncompress: not found [No such file or directory]" is displayed, contact your UNIX administrator.

2. Assign 751 permission to the file with the following command:

```
chmod 751 unzip_<os>
```

For example, `chmod 751 unzip_sparc`

3. Extract the contents of the OIDF Application Pack Release v8.1.0.0.0 installer archive file in the download directory with the following command:

```
unzip OFS_OIDF_8.1.0.0.0_<Operating_System>.zip
```

**NOTE** Do not rename the Application Pack installer folder name on extraction from the archive.

4. Log in to OFSAA Infrastructure Config Schema and execute the following SQL query:

```
ALTER TABLE CONFIGURATION MODIFY PARAMNAME VARCHAR2 (100 CHAR);
```

5. For Solaris OS, extract the one-off patch **31509494**. See the ReadMe packaged with the patch for further instructions on how to install the patch.

**NOTE** This is a mandatory Pre-installation requirement for the OIDF Application Pack upgrade installation from the 8.0.x versions to the 8.1.0.0.0 version on the Solaris operating system.

6. Navigate to the Download Directory and assign 750 permission to the installer directory with the following command:

```
chmod -R 750 OFS_OIDF_PACK
```

## 8.7.2 Update the OFS\_OIDF\_PACK.xml File

Update the `OFS_OIDF_PACK.xml` file to enable only the existing installed Application Packs.

To configure the `OFS_OIDF_PACK.xml` file, follow these steps:

1. Navigate to the `OFS_OIDF_PACK/conf/` directory.
2. Rename the file `OFS_OIDF_PACK.xml` to `OFS_OIDF_PACK.xml.template`
3. Open the `OFS_OIDF_PACK.xml` file in a text editor.
4. Update the `OFS_OIDF_PACK.xml` file as mentioned in the following table only for the specified parameter.

**NOTE**

For the Big Data mode of installation, enable the option as **YES** for the **APP\_ID** parameter with the value **OFS\_AAIB** as illustrated in the sample.

Figure 49: Sample OFS\_OIDF\_PACK.xml File with the Update for Upgrade

```
<APP_PACK_CONFIG>
 <APP_PACK_ID>OFS_OIDF_PACK</APP_PACK_ID>
 <APP_PACK_NAME>Oracle Insurance Foundation Pack</APP_PACK_NAME>
 <APP_PACK_DESCRIPTION>Applications forming analytics foundation such for the Insurance Domain
</APP_PACK_DESCRIPTION>
 <VERSION>8.1.0.0.0</VERSION>
 <APP>
 <APP_ID PREREQ="" DEF_SEL_FLG="YES" ENABLE="YES">OFS_AAI</APP_ID>
 <APP_NAME>Financial Services Analytical Applications Infrastructure</APP_NAME>
 <APP_DESCRIPTION>Base Infrastructure for Analytical Applications</APP_DESCRIPTION>
 <VERSION>8.1.0.0.0</VERSION>
 </APP>
 <APP>
 <APP_ID PREREQ="OFS_AAI" ENABLE="YES">OFS_OIDF</APP_ID>
 <APP_NAME>Oracle Insurance Data Foundation</APP_NAME>
 <APP_DESCRIPTION>Data Foundation for Insurance domain</APP_DESCRIPTION>
 <VERSION>8.1.0.0.0</VERSION>
 </APP>
</APP_PACK_CONFIG>
```

Table 43: Update Specific Parameters in the OFS\_OIDF\_PACK.xml file

| Tag Name | Attribute Name | Description                       | Mandatory (Y/N)                       | Comments                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
|----------|----------------|-----------------------------------|---------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| APP_ID   | ENABLE         | Enable the Application or Product | YES if installing in the SILENT mode. | <p>The default value is YES for Infrastructure.<br/>The default value is NO for Others.<br/>Permissible values are YES and NO.<br/>Set this attribute value to YES against every APP_ID, which is licensed and should be enabled for the upgrade.</p> <p><b>NOTE:</b> You cannot disable the Application or Product after you enable it. However, the Application or Product not enabled during installation can be enabled later through the Administration UI.</p> |

5. Save the file.

## 8.7.3 Update the Silent.props File

### Topics:

- [Silent Upgrade to OIDF v8.1.0.0.0 for RDBMS](#)

**ATTENTION**

Do not install the new applications in the same segment if the preinstalled applications use Run Management.

### 8.7.3.1 Silent Upgrade to OIDF v8.1.0.0.0 for RDBMS

This section is applicable only for the RDBMS mode of OIDF v8.1.0.0.0 upgrade installation.

**NOTE**

In an integrated environment, Oracle recommends the customers use the same Staging source in the `Silent.props` file for the T2Ts that load data from the Stage tables into the Result tables.

To configure the `Silent.props` file to upgrade to the OIDF Application Pack Release 8.1.0.0.0, follow these steps:

1. Navigate to the installer kit `OFS_OIDF_PACK/appsLibConfig/conf/` directory.
2. Rename the `Silent_upgrade_from_806.template` file to `Silent.props`.
3. Update the `Silent.props` file and mention the following parameters:

**Figure 50: Sample of the Silent.props file (Silent\_upgrade\_from\_806.template for RDBMS) for upgrade installation**

```
Specify Log Mode
1 = DEBUG Mode [Password will be printed in the log file]
0 = GENERAL Mode [Passwords will not be printed in the log file]
Default is GENERAL
LOG_MODE=0

Specify the Oracle Insurance Data foundation Segment Code
SEGMENT_1_CODE=

Specify the Infodom Maintenance log path(to be created) for the new Infodom
Please ignore if you are doing installation on an existing information domain
APPFTP_LOG_PATH=
DBFTP_LOG_PATH=

Specify wheter you want to perform Model Upload
0 = If you have already performed Model Upload and want to skip model upload process
1 = If you want to perform Model Upload
UPLOAD_MODEL=

Specify whether you want to use the released datamodel or customized datamodel for model upload process
0 = If you want to upload the released datamodel
1 = If you want to upload the customized datamodel
MODEL_TYPE=

Specify the path(DM_DIRECTORY) and file(DATAMODEL) name for the cutomized datamodel
Mandatory only if you want to upload the customized datamodel
i.e you have specified MODEL_TYPE=1
DATAMODEL=
DM_DIRECTORY=

#Please specify if you want create new ETL Src or use an existing one.
0 = If you want to create a new ETL src
1 = If you want to use an existing src
ETL_APPSRC_TYPE=1

ETL_NEW_SRCS_REQUIRED=N
```

**Table 44: Parameters for the Silent.props File (Silent\_upgrade\_from\_806.template for RDBMS)**

| Property Name   | Description of Property                                                                              | Permissible values                        | Comments                                                                                                                                            |
|-----------------|------------------------------------------------------------------------------------------------------|-------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------|
| LOG_MODE        | Mode for logging                                                                                     | 1 = Debug<br>0 = General                  | # Optional; Default: 0                                                                                                                              |
| SEGMENT_1_CODE  | Segment Code                                                                                         | Example: OI DFSEG                         | # Mandatory<br>Segment Code must be the same as the code that is used during the first OIDF installation (Base Pack)                                |
| APPFTP_LOG_PATH | Information Domain Maintenance log path (to be created) for the new Information Domain for App Layer | Example:<br>/ftpshare/<INFODOM_NAME>/logs | # Mandatory<br>Information Domain Maintenance log path must be the same as the log path that is used during the first OIDF installation (Base Pack) |

| Property Name         | Description of Property                                                                             | Permissible values                                                                                            | Comments                                                                                                                                           |
|-----------------------|-----------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------|
| DBFTP_LOG_PATH        | Information Domain Maintenance log path (to be created) for the new Information Domain for DB Layer | Example:<br>/ftpshare/<INFODOM_NAME>/logs                                                                     | # Mandatory<br>Information Domain Maintenance log path must be the same as the log path that is used during the first ODF installation (Base Pack) |
| UPLOAD_MODEL          | Whether you need to perform Model Upload                                                            | 0 = No<br>1 = Yes                                                                                             | # Mandatory                                                                                                                                        |
| MODEL_TYPE            | Released Data Model or Customized Data Model                                                        | 0 = released Data Model<br>1 = customized Data Model                                                          | # Mandatory only in the case of UPLOAD_MODEL=1                                                                                                     |
| DATAMODEL             | The file name for the customized Data Model                                                         | Not Applicable                                                                                                | # Mandatory only in the case of uploading the customized Data Model<br># Option selected for MODEL_TYPE=1                                          |
| DM_DIRECTORY          | The path for the customized Data Model                                                              | Not Applicable                                                                                                | # Mandatory only in the case of uploading the customized Data Model<br># Option selected for MODEL_TYPE=1                                          |
| ETL_APPSRC_TYPE       | The ETL application name                                                                            | 0=New Pair<br>1=Existing                                                                                      | # Mandatory                                                                                                                                        |
| ETL_NEW_SRCS_REQUIRED | Whether ETL new sources are required                                                                | N                                                                                                             | # Mandatory                                                                                                                                        |
| ENABLE_CONCURRENCY    | #Support for Parallelism                                                                            | 0 = No<br>1 = Yes                                                                                             | #Optional                                                                                                                                          |
| CONCURRENCY_LEVEL     | #Support for Parallelism                                                                            | Example:<br>CONCURRENCY_LEVEL=10,<br>which means 10 threads are triggered to handle the processing of fsapps. | #Optional                                                                                                                                          |

4. Save the file.

## 8.7.4 Execute the Schema Creator Utility Only for the ODF Application Pack

To execute the schema creator utility, follow these steps:

**NOTE**

When defining the schema details for the application packs, provide the same schema details given in the previous installation. The output file `OFS_OIDF_SCHEMA_OUTPUT.xml` is generated as a result of the schema creation process.

1. Configure the Schema Creator Utility:
  - For the RDBMS installation, edit the `OFS_OIDF_PACK/schema_creator/conf/OFS_OIDF_SCHEMA_IN.xml` file in a text editor. See the [Configure the OFS\\_OIDF\\_SCHEMA\\_IN.xml File](#) section to modify the values in the XML file.
2. Execute the utility with the `-s` option.

For Example: `./osc.sh -s`

For more information, see the [Execute the Schema Creator Utility](#) section.

## 8.7.5 Trigger the Installation

You are upgrading OIDF Application Pack from Release 8.0.6.0.0 or later to Release 8.1.0.0.0. For example, you are using release 8.0.7.0.0 and now want to upgrade to Release 8.1.0.0.0.

**NOTE**

If upgrading from a version before OIDF v8.0.6.0.0, then first upgrade to v8.0.6.0.0 or later versions. To upgrade to OIDF v8.0.6.0.0, see the installation guides [Oracle Insurance Data Foundation Installation and Configuration Guide](#).

To install the OIDF Application Pack, follow these steps:

1. Ensure that you completed the following procedures:
  - a. [Download](#) the installer.
  - b. [Perform](#) the prerequisites for installation.
  - c. [Prepare](#) for Upgrade.
  - d. [Extract](#) the software.
  - e. [Update](#) the `OFS_OIDF_PACK.xml` file.
  - f. [Update](#) the `Silent.props` file.
  - g. [Execute](#) the Schema Creator Utility.

**NOTE**

Ensure you have downloaded and applied the mandatory OFSAAI one-off patch **31509494**. This is a mandatory Pre-installation requirement for the OFSAA Application upgrade installation from the 8.0.x versions to the 8.1.0.0.0 version on the Solaris operating system.

2. Enter the following command in the console to execute the ODF Application Pack installer with the Silent option:

```
./setup.sh SILENT
```

3. The installer proceeds with the Pre-installation Checks.
4. Enter the OFSAA Processing Tier FTP/SFTP password value and proceed, when prompted in the command prompt.

**Figure 51: OFSAA Processing Tier FTP/SFTP Password Prompt**

```

* Welcome to Oracle Financial Services Analytical Applications Infrastructure (OFS AAI) Installation *

Checking Infrastructure installation status ...
Infrastructure installation does not exist. Proceeding with Infrastructure installation ...
Triggering Infrastructure installation ...

Please enter Infrastructure Application/Database component FTP/SFTP password : █
```

#### NOTE

Enter the password to access the Product Staging or Metadata repository directory FTPSHARE in the application server.

5. The process displays the OFSAA License. Enter **Y** and proceed.

**Figure 52: Accept the OFSAA License Agreement**

```

OFSAA APPLICATION PACK LICENSE AGREEMENT

* Oracle Financial Services Analytical Applications (OFSAA) application packs are groups of OFSAA products packaged together into a single installer. Each application pack contains OFSAA applications that address specific functional domains.*
* Every application pack also includes the following OFSAA infrastructure application options which are automatically installed by every application pack installer:
1. Oracle Financial Services Analytical Applications Infrastructure
2. Oracle Financial Services Enterprise Modeling
3. Oracle Financial Services Big Data Processing
* Oracle Financial Services Analytical Applications Infrastructure (OFS AAI) is the base infrastructure for all OFSAA applications and is therefore automatically installed and enabled by the application pack installer.*
* The application pack installer always installs Oracle Financial Services Enterprise Modeling, Oracle Financial Services In-line Processing Engine and Oracle Financial Services Big Data Processing application options along with the application pack applications, but enables them only if any application that requires their functionality is enabled.*
* Any OFSAA application that is enabled must be licensed for use. Oracle Financial Services Analytical Applications Infrastructure, Oracle Financial Services Enterprise Modeling, Oracle Financial Services In-line Processing Engine and Oracle Financial Services Big Data Processing are individually licensable application options.*
* Application products once enabled cannot be disabled. Application products not enabled on installation, may later be enabled using the "Manage OFSAA Product License(s)" feature of the platform.*

Are you accepting the terms and conditions mentioned above? [Y/N]:
█
```



**NOTE**

- The Data Model upload may take several hours to complete. You can check the installation logs in the `/OFS_OIDF_PACK/OFS_OIDF/logs/` directory.
- For the existing customers, with the DB XML, the time taken for the Data Model upload will be significantly reduced. You can upload the warehouse data from the operational systems to the database schema using the erwin XML or Database XML file. Using the stand-alone command-line utility for the `TransformErwin.sh` file, you can transform erwin XML into Database XML, and use the DB XML instead of erwin XML to speed up the model upload process. For more information, see the *Command Line Utility for Transforming erwin XML to Database XML* section in the [Oracle Financial Services Advanced Analytical Applications Infrastructure User Guide Release 8.1.0.0.0](#).

**Figure 55: OIDF Application Pack Installation Complete**

```

Starting OFSAA Service...
OFSAA Service - OK
Preparing to install...
Extracting the installation resources from the installer archive...
Configuring the installer for this system's environment...

Launching installer...

Preparing SILENT Mode Installation...

=====
pack_installsilent (created with InstallAnywhere)
=====

Installing...

[=====|=====|=====|=====]
[-----|-----|-----|-----]

Installation Complete.
failurecount --- 0
Core Installation completed successfully
tempdir ---- /scratch/██████/kit/OFS_OIDF_PACK
Checking for hive app. ████████

***** Checking for Fresh app : OFS_OIDF *****
path before app installation: /scratch/██████/kit/OFS_OIDF_PACK
inside checkappstatus-app OFS_OIDF /scratch/██████/kit/OFS_OIDF_PACK/bin
all value /scratch/██████/kit/OFS_OIDF_PACK/bin
In app value
[AppStatusCheck] Checking for app installation OFS_OIDF
[AppStatusCheck] app is selected and ENABLED in db
app status returned: 0
current directory after app installation: /scratch/██████/kit/OFS_OIDF_PACK/OFS_OIDF
Checking for available options...
List of options available:
Pack Name found is: OFS_OIDF_PACK
Utility triggered for XML files

```

8. When the installation is complete, the following message is displayed in the console:

*Installation completed...*

9. The OFSAA Infrastructure installation performs a post-install health check automatically on the successful installation of the product.
10. To verify if the release is applied successfully, check the log files mentioned in the section [Verify the Log File Information](#).

#### NOTE

If any applications are installed on top of the OFS AAI Application Pack 8.1.0.0.0 version, execute the script `update_dq_batches_optional_params.sql`, which is available in the folder `$FIC_HOME/Post_AAI_Migration`, after the installation of the applications.

11. For more information on securing your OFSAA Infrastructure, refer to the [Oracle Financial Services Analytical Applications Infrastructure Security Guide Release 8.1.x](#).
12. After successful installation, perform the Post-installation procedures. For detailed information, see the [Post-installation](#) section.
13. Perform the necessary [Additional Configuration](#).

#### NOTE

The DMT screens are no more managed with a generic function since AAI v8.1.0.0.0. Starting from AAI v8.0.6.0.0, each action performed in the DMT screens require specific user roles and functions for various operations. Therefore, OIDF has up taken the user roles and functions available for the AAI v8.1.0.0.0 DMT screens. From v8.1.0.0.0, OIDF and AAI support only new functions and the new user roles mapped to the user groups.

## 8.7.6 Verify the Log File Information

See the following logs files for more information:

- The `Pack_Install.log` file in the `OFS_OIDF_PACK/logs/` directory.
- The `OFS_OIDF_installation.log` file and the `OFS_OIDF_installation.err` file in the `OFS_OIDF_PACK/OFS_OIDF/logs` directory.
- The Infrastructure installation log files in the `OFS_OIDF_PACK/OFS_AAI/logs/` directory.
- The `OFSAAInfrastucture_Install.log` file in the `$FIC_HOME` directory.

#### ATTENTION

- When upgrading the OIDF Application Pack to v8.1.0.0.0 in an integrated environment, you can ignore the `Object already exists` and the `Table has a primary key` warnings for the `OFSA_CATALOG_OF_LEAVES` table in the log file.
- You can ignore the "ORA-00001: unique constraint" error.

- In case of any other errors, contact [My Oracle Support \(MOS\)](#).

## 8.7.7 Post-installation Steps

Follow the steps mentioned in the [Post-installation](#) section.

### Topics:

- [Execute the ModelUpgrade.sh file for the Postscripts](#)

### 8.7.7.1 Execute the ModelUpgrade.sh File for the Postscripts

This section is applicable if you have performed the OIDF v8.1.0.0.0 OOB Data Model upload outside of the installer.

After the successful upgrade of the OIDF Application Pack to the v8.1.0.0.0 release, execute the `OIDF ModelUpgrade.sh` file for Postscripts to restore the data and the metadata.

For detailed information, see the *Execute the ModelUpgrade.sh file for the Postscripts* and *OIDF Application Pack Upgrade Process* sections in the [Oracle Insurance Data Foundation Application Pack Upgrade Guide Release 8.1.0.0.0](#).

## 8.7.8 Additional Configuration

For additional configuration information, see the [Additional Configuration](#) section.

# Part III

**Topics:**

- [Additional Configuration](#)
- [Frequently Asked Questions \(FAQs\) and Error Dictionary](#)

## 9 Additional Configuration

This section provides information about the additional configuration required after the ODF Application Pack installation. See the *Additional Configuration* section in the [Oracle Financial Services Advanced Analytical Applications Infrastructure Installation Guide Release 8.1.0.0.0](#) to complete the procedures listed in the following table.

**NOTE** ODF uses the Process Modeling Framework (PMF) to execute two ready-to-use Runs (ODF Sourced Run and ODF Execution Run) for data loading. For more information about the Process Modeling Framework configuration, see the [Oracle Financial Services Advanced Analytical Applications Infrastructure Administration and Configuration Guide Release 8.1.x](#) and the [Oracle Financial Services Analytical Applications Infrastructure Process Modelling Framework Orchestration Guide Release 8.1.0.0.0](#).

**Table 45: Additional Configuration Checklist**

| Sl. No. | Activity                                                                         |
|---------|----------------------------------------------------------------------------------|
| 1       | <a href="#">Configure</a> the webserver.                                         |
| 2       | <a href="#">Configure</a> the Resource Reference in web application servers.     |
| 3       | <a href="#">Configure</a> the Work Manager in the web application servers.       |
| 4       | <a href="#">Add</a> the FTP/SFTP configuration for file transfer.                |
| 5       | <a href="#">Configure</a> the Process Modeling Framework.                        |
| 6       | <a href="#">Configure</a> the Infrastructure Server Memory.                      |
| 7       | <a href="#">Change</a> IP/Hostname, Ports, Deployed Paths of the OFSAA Instance. |
| 8       | <a href="#">Execute</a> the OFSAAI setup information fetching tool.              |
| 9       | <a href="#">Execute</a> the Encryption Changer.                                  |
| 10      | <a href="#">Configure</a> the Infrastructure LDAP.                               |
| 11      | <a href="#">Configure and deploy</a> the OFSAAI web services.                    |
| 12      | <a href="#">Enable</a> the parallel execution of DML statements.                 |
| 13      | <a href="#">Configure</a> the message details in the Forms Designer.             |
| 14      | <a href="#">Clear</a> the application cache.                                     |
| 15      | <a href="#">Configure</a> the password changes.                                  |
| 16      | <a href="#">Configure</a> the Java Virtual Machine.                              |
| 17      | <a href="#">Configure</a> the internal service (Document Upload/Download).       |
| 18      | <a href="#">Migrate</a> the Excel upload functionality.                          |
| 19      | <a href="#">Remove</a> the OFSAA Infrastructure.                                 |

## 10 **Frequently Asked Questions (FAQs) and Error Dictionary**

For FAQs and installation error-related information, see the section [Frequently Asked Questions \(FAQs\) and Error Dictionary](#) in the [Oracle Financial Services Advanced Analytical Applications Infrastructure Installation Guide Release 8.1.0.0.0](#).

## OFSAA Support

Raise a Service Request (SR) in [My Oracle Support \(MOS\)](#) for queries related to the OFSAA applications.

## Send Us Your Comments

Oracle welcomes your comments and suggestions on the quality and usefulness of this publication. Your input is an important part of the information used for revision.

- Did you find any errors?
- Is the information clearly presented?
- Do you need more information? If so, where?
- Are the examples correct? Do you need more examples?
- What features did you like most about this manual?

If you find any errors or have any other suggestions for improvement, indicate the title and part number of the documentation along with the chapter/section/page number (if available) and contact the [Oracle Support](#).

Before sending us your comments, you might like to ensure that you have the latest version of the document wherein any of your concerns have already been addressed. You can access the [My Oracle Support](#) site that has all the revised/recently released documents.

