
PeopleSoft 9.2 Application Installation for DB2 for Linux, UNIX, and Windows (PeopleSoft PeopleTools 8.57)

January 2019

PeopleSoft 9.2 Application Installation for DB2 for Linux, UNIX, and Windows (PeopleSoft PeopleTools 8.57)
Copyright © 2019, Oracle and/or its affiliates. All rights reserved.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited. The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this is software or related documentation that is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, then the following notice is applicable:

U.S. GOVERNMENT END USERS: Oracle programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, delivered to U.S. Government end users are "commercial computer software" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, shall be subject to license terms and license restrictions applicable to the programs. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Xeon are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. AMD, Opteron, the AMD logo, and the AMD Opteron logo are trademarks or registered trademarks of Advanced Micro Devices.

UNIX is a registered trademark of The Open Group.

This software or hardware and documentation may provide access to or information about content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services unless otherwise set forth in an applicable agreement between you and Oracle. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services, except as set forth in an applicable agreement between you and Oracle.

Documentation Accessibility

For information about Oracle's commitment to accessibility, visit the Oracle Accessibility Program website at <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=docacc>.

Access to Oracle Support

Oracle customers that have purchased support have access to electronic support through My Oracle Support. For information, visit <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=info> or visit <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=trs> if you are hearing impaired.

Contents

- Preface**
 - About This Documentation 19**
 - Understanding This Documentation 19
 - Audience 19
 - Typographical Conventions 20
 - Products 21
 - Related Information 22
 - Comments and Suggestions 22

- Part I 23**
 - Mandatory Installation 23

- Chapter 1**
 - Preparing for Installation 25**
 - Understanding the PeopleSoft Installation 25
 - Understanding the PeopleSoft Installation Using Deployment Packages 27
 - Understanding the PeopleSoft Deployment Packages Required for Installation 27
 - Reviewing the PeopleSoft PeopleTools DPKs 28
 - Reviewing the PeopleSoft Application Images 29
 - Reviewing the Installation Choices 31
 - Reviewing the DPK Installation Process (Linux, AIX, HP-UX, Solaris, or Microsoft Windows) 31
 - Understanding the PeopleSoft Upgrade Source Deployment Packages 32
 - Reviewing the PeopleSoft Upgrade Source Image Usage 32
 - Reviewing the PeopleSoft Upgrade Source Image 32
 - Reviewing the PeopleSoft Upgrade Source Image Installation 34
 - Reviewing Hardware Requirements 35
 - Reviewing Hardware Requirements for Microsoft Windows 35
 - Reviewing Hardware Requirements on AIX, HP-UX, Linux, or Solaris 36
 - Reviewing Software Requirements 37
 - Reviewing Software Requirements on Microsoft Windows 37
 - Reviewing Software Requirements on Linux 38
 - Reviewing Software Requirements on AIX 38
 - Reviewing Software Requirements on HP-UX 39
 - Reviewing Software Requirements on Solaris 41

Reviewing Requirements for the Puppet Software on Microsoft Windows	41
Reviewing Requirements for the Puppet Software on Linux	42
Reviewing Requirements for the Puppet Software on AIX	43
Reviewing Requirements for the Puppet Software on HP-UX	44
Reviewing Requirements for the Puppet Software on Solaris	45
Reviewing the System Parameters on Linux, AIX, HP-UX, or Solaris	47
Using Oracle Software Delivery Cloud to Obtain Installation Files	48
Considering Project Planning	48
Planning Your Initial Configuration	48
Understanding Workstations	49
Understanding PeopleSoft Servers and Clients	50
Defining the PeopleTools Client	50
Defining the File Server	51
Defining the Database Server	51
Defining the Application Server	52
Defining the Process Scheduler (Batch) Server	52
Defining Installation Locations	53
Defining the Web Server	55
Planning Database Creation	55
Understanding Database Creation	56
Determining Databases and Database Names	56
Defining DB2 for Linux, UNIX, and Windows, and PeopleSoft Databases	56
Planning Multilingual Strategy	56
Understanding Multilingual Issues	57
Choosing a Base Language	58
Selecting Additional Languages	60
Selecting a Database Character Set	60
Creating PeopleSoft User IDs	61
Understanding PeopleSoft User ID Creation	61
Prerequisite	61
Creating UNIX User IDs	61
Creating Windows User IDs	62
Installing the Database Engine	63
Configuring DB2 UDB for Linux, UNIX, and Windows for Remote Client Access	63
Installing Supporting Applications	65
Performing Backups	66
 Chapter 2	
Installing the PeopleSoft Homes	67
Obtaining the PeopleSoft Application Images and PeopleTools DPKs	67
Obtaining the PeopleSoft Upgrade Source Images	68

Reviewing the DPK Setup Script Options	69
Using the DPK Setup Script Options	69
Preparing to Run the DPK Setup Script	71
Deploying as a Non-Root User on Linux, AIX, HP-UX, or Solaris	73
Preparing to Run the DPK Setup Script as a Non-Root User on Linux, AIX, HP-UX, or Solaris	73
Running the DPK Setup Prerequisite for Linux, AIX, HP-UX, or Solaris	74
Running the DPK Setup Script as a Non-Root User on Linux, AIX, HP-UX, or Solaris	75
Running the DPK Setup Script to Install PS_HOME and PS_APP_HOME	76
Understanding the PS_HOME and PS_APP_HOME Installation	76
Installing PS_HOME and PS_APP_HOME on Microsoft Windows	76
Installing PS_HOME and PS_APP_HOME on Linux, AIX, HP-UX, or Solaris as the Root User	80
Installing PS_HOME and PS_APP_HOME on Linux, AIX, HP-UX, or Solaris as a Non-Root User	84
Reviewing the Deployment Results	87
Running the DPK Setup Script to Install All Software	88
Understanding the DPK Setup Deploying All Software	88
Installing on Microsoft Windows	89
Installing on Linux, AIX, HP-UX, or Solaris as the Root User	92
Installing on Linux, AIX, HP-UX, or Solaris as a Non-Root User	96
Reviewing the Installed Software	99
Obtaining Operating System Packages Required by Puppet	100
Removing a Deployed PeopleSoft Environment	101
Understanding the Removal Process	101
Using the DPK Setup Script to Remove the PeopleSoft Environment on Microsoft Windows	101
Using the DPK Setup Script to Remove the PeopleSoft Environment on Linux, AIX, HP-UX, or Solaris ..	102
Using the DPK Setup Script to Remove the PeopleSoft Environment on Linux, AIX, HP-UX, or Solaris as a Non-Root User	103
Using Puppet to Remove the PeopleSoft Environment on Microsoft Windows	103
Using Puppet to Remove the PeopleSoft Environment on Linux, AIX, HP-UX, or Solaris	103
Troubleshooting the Removal Process on Microsoft Windows	104
Troubleshooting the Removal Process on Linux, AIX, HP-UX, or Solaris	105

Chapter 3

Completing the DPK Initialization with Customizations	107
Understanding PeopleSoft Environment Customizations	107
Preparing Customization Files for Linux, AIX, HP-UX, or Solaris Users and Groups	111
Preparing the Customization File for a Single User and Single Group	112
Preparing the Customization File for a New Single User, New Primary Group, and Existing Secondary Group ..	113
Preparing the Customization File for Existing Users and Groups	115
Preparing the Customization File for PeopleSoft Domain Definitions	117
Preparing the psft_customizations.yaml file	117
Reviewing the Domain Definitions in psft_configuration.yaml	117

Reviewing the Customization File for a Single Application Server Domain	122
Reviewing the Customization File for an Application Server Domain with Custom PS_CFG_HOME	123
Reviewing the Customization File for a PIA Domain on a Separate Host	124
Reviewing the Customization File for Multiple Domains	125
Preparing the Customization File to Create PeopleSoft Domains Without Configuration	130
Preparing the Customization File for JDK on AIX	130
Preparing the Customization File for JDK on HP-UX	131
Preparing the Customization File for Component Software Locations	131
Preparing the Customization File for Unicode	133
Preparing the Customization File for the PeopleSoft Homes	134
Preparing the Customization File for the PS_HOME Location	134
Preparing the Customization File for the PS_APP_HOME Location	135
Preparing the Customization File for the PS_CFG_HOME Location	136
Preparing the Customization File for Jolt SSL and WSL SSL Ports	136
Preparing the Customization File for Oracle HTTP Server	138
Preparing the Customization File for Mid-Tier Connection to a DB2 for Linux, UNIX, and Windows Database .	141
Completing the Customized Deployment	144

Chapter 4

Setting Up the Install Workstation	147
Understanding the Install Workstation	147
Prerequisites	147
Starting Configuration Manager	148
Setting Startup Options	148
Editing the Default Profile	149
Running Client Setup	151

Chapter 5A

Creating a Database Manually on Microsoft Windows or UNIX	153
Understanding Database Creation	153
Determining Tablespace Strategy for Demo Database	154
Editing SQL Scripts	154
Understanding SQL Scripts	155
Editing CREATEDB-95.SQL or CREATEDBU.SQL	155
Executing DB2SET Command to Set Proper Decimal Scale	162
Editing ALTRDB.SQL	162
Editing CREATEBPU.SQL for Unicode	162
Editing XXDDLMS.SQL or XXDDLMSU.SQL	162
Editing DBOWNER.SQL	164
Editing PSADMIN.SQL	164

Running SQL Scripts	165
Configuring and Testing Database Connectivity for DB2 Connect or DB2 Client V9.x or Earlier	166
Configuring Database Connectivity for DB2 Connect or DB2 Client V9.x or Earlier	167
Testing Client Connectivity for DB2 Connect or DB2 Client V9.x or Earlier	174
Configuring and Testing Connectivity for DB2 Connect and DB2 Client V10.x or Later	176
Configuring Database Connectivity for DB2 Connect and DB2 Client V10.x or Later	176
Testing Database Connectivity for DB2 Connect and DB2 Client V10.x or Later	177
Configuring an ODBC Data Source for Connectivity on Microsoft Windows	177
Creating Data Mover Import Scripts	178
Understanding Data Mover Import Scripts	178
Working with Multilingual Databases	179
Running Database Setup to Create Data Mover Import Scripts	179
Running Data Mover Import Scripts	186
Understanding Data Mover Import Scripts	186
Populating Tables in the PeopleSoft Database	186
Cleaning Up Orphaned Language Data	187
Checking the Log Files and Troubleshooting	187
Checking the Log Files	187
Running Data Mover	188
Troubleshooting	188
Improving Performance	190
Changing the Base Language	190

Chapter 5B

Creating a Database on UNIX	191
Understanding the Database Configuration Wizard	191
Fulfilling PeopleSoft Database Configuration Wizard Prerequisites	192
Installing the PeopleSoft Database Server Components on the Database Server	192
Changing the Ownership for the PS_APP_HOME Directory	193
Defining User Groups	193
Creating the Data Directory	193
Completing Registry Settings	193
Rebinding of Packages Requirement	193
Completing Required CLI Settings in the DB2CLI.INI File	193
Defining Database Manager Configuration	194
Defining Database Configuration	194
Running the Shell Script psconfig.sh	194
Using the Database Configuration Wizard in Silent Mode	195
Understanding the Database Configuration Wizard	195
Preparing the Response File	196
Running the Silent Mode Database Creation	199

Changing the Location of the DB2/LUW Database Log Files	200
Cleaning Up Orphaned Language Data	200
Checking the Log Files and Troubleshooting	200
Checking the Log Files	201
Running Data Mover	201
Troubleshooting	203
Improving Performance	205

Chapter 6

Completing the Database Setup	207
Selecting the Necessary Tasks to Complete the Database Setup	207
Running Additional Data Mover Scripts	207
Running SQR Reports	207
Understanding Running SQR Reports	208
Binding the dbcalls.bnd	208
Running SQRs on the Client Workstation	208
Creating a Shortcut to Run SQRs	210
Checking the Database	211
Running SETSPACE.SQR	211

Chapter 7

Deploying Mid-Tier Components	213
Understanding the Mid-Tier Deployment	213
Running the DPK Setup Script for Mid-Tier Deployment	213
Understanding the Mid-Tier Deployment	213
Prerequisites	214
Running with the Mid-Tier Option on Microsoft Windows	215
Running with the Mid-Tier Option on Linux, AIX, HP-UX, or Solaris as the Root User	221
Running with the Mid-Tier Option on Linux, AIX, HP-UX, or Solaris as a Non-Root User	227
Completing Installation Tasks	234

Chapter 8

Completing the Installation	235
Completing Post-Installation Steps	235
Using Fluid User Interface	235
Updating the Installation Table	238
Setting Options for Multilingual Databases	239
Updating PeopleTools Options	239
Updating Time Zone Information	240

Updating Database Information	240
Using the PeopleSoft Installation	240
Accessing the PeopleSoft Environment	240
Reviewing the Deployment File System	241
Reviewing the DPK-Created Users for Root Deployments on Linux, AIX, HP-UX, and Solaris	243
Working with PeopleSoft Utilities and Programs for Root Deployments on Linux, AIX, HP-UX, and Solaris ..	245
Setting Environment Variables for the Non-Root User on Linux, AIX, HP-UX, or Solaris	245

Chapter 9

Deploying the PeopleTools Client DPK	247
Deploying the PeopleTools Client DPK	247
Understanding the Standalone Mode Deployment	247
Preparing for the PeopleTools Client DPK Deployment	248
Deploying in Standalone Mode	248

Part II	253
Discretionary Installation	253

Chapter 10A

Installing and Compiling COBOL on Windows	255
Understanding COBOL	255
Prerequisites	255
Preparing COBOL for a PeopleTools-only Upgrade	256
Installing Micro Focus Net Express on Microsoft Windows	256
Prerequisites	256
Obtaining Installation Files for Micro Focus Net Express from Oracle Software Delivery Cloud	257
Installing Micro Focus Net Express Wrap Pack 6	257
Installing Micro Focus Net Express Wrap Pack 15	269
Managing Micro Focus Net Express Compiler Licenses	274
Understanding Micro Focus Net Express Compiler Licenses	274
Configuring a Full License with the License Server	275
Configuring a Timed License with the License Server	285
Revoking the License Using the License Management System	292
Revoking the License by Removing the Installation	294
Using the Micro Focus COBOL Compiler on Microsoft Windows	296
Understanding COBOL Compilation	297
Compiling COBOL on Microsoft Windows with a PS_HOME Setup	298
Compiling COBOL on Microsoft Windows with a PS_APP_HOME Setup	301

Compiling COBOL on Microsoft Windows with a PS_CUST_HOME Setup	305
Recompiling COBOL on Microsoft Windows	310
Setting Up the Micro Focus Net Express Runtime	311
Defining the GNT and INT Files	313
Distributing COBOL Binaries	313
 Chapter 10B	
Installing and Compiling COBOL on UNIX	315
Understanding COBOL	315
Prerequisites	316
Preparing COBOL for a PeopleTools-only Upgrade	316
Installing Micro Focus Server Express for UNIX and Linux	316
Understanding Micro Focus Server Express	316
Prerequisites	317
Obtaining the Installation Files for Micro Focus Server Express from Oracle Software Delivery Cloud	318
Installing Micro Focus Server Express	318
Using the Micro Focus COBOL Compiler on UNIX	324
Understanding COBOL Compilation	324
Setting Environment Variables	325
Modifying the Liblist64 File (IBM AIX)	326
Compiling COBOL on UNIX with a PS_HOME Setup	326
Compiling COBOL on UNIX with a PS_APP_HOME Setup	327
Compiling COBOL on UNIX with a PS_CUST_HOME Setup	328
Linking COBOL	329
Recompiling COBOL on UNIX	330
Installing IBM COBOL on IBM AIX	331
Understanding the IBM COBOL for AIX Installation	331
Prerequisites	331
Installing IBM COBOL for AIX v5.1.0.0	331
Using the IBM COBOL Compiler on IBM AIX	331
Setting Environment Variables for IBM COBOL	332
Compiling COBOL on AIX with a PS_HOME Setup	332
Compiling COBOL on AIX with a PS_APP_HOME Setup	334
Compiling COBOL on AIX with a PS_CUST_HOME Setup	335
Troubleshooting the IBM COBOL Compiler	336
Setting Up the IBM COBOL Runtime	340
Removing the IBM COBOL Installation	343
 Chapter 11	
Installing Web Server Products	345

Installing Oracle WebLogic Server	345
Understanding the Oracle WebLogic Installation	345
Reviewing Troubleshooting Tips	346
Obtaining Oracle WebLogic Installation Files from Oracle Software Delivery Cloud	347
Installing JDK	348
Installing Oracle WebLogic on Microsoft Windows	350
Installing Oracle WebLogic on UNIX in Silent Mode	359
Configuring JDK for Daylight Savings Time Change	362
Removing the Oracle WebLogic Installation on Microsoft Windows	362
Removing the Oracle WebLogic Installation on UNIX	366

Chapter 12

Installing Additional Components	369
Reviewing Additional Components	369
Installing Oracle Tuxedo	370
Understanding Oracle Tuxedo	370
Prerequisites	372
Debugging the Oracle Tuxedo Installer	372
Obtaining the Oracle Tuxedo Installation Files from Oracle Software Delivery Cloud	373
Obtaining the Oracle Tuxedo Patches from My Oracle Support	373
Removing Existing Oracle Tuxedo Installations from Microsoft Windows (Optional)	374
Designating the Application Server Administrator on Microsoft Windows	375
Installing Oracle Tuxedo on Microsoft Windows in GUI Mode	376
Installing the Oracle Tuxedo Patch on Microsoft Windows	392
Installing Oracle Tuxedo on Microsoft Windows in Silent Mode	394
Uninstalling the Oracle Tuxedo Patch on Microsoft Windows	395
Uninstalling Oracle Tuxedo in GUI Mode	396
Checking the Windows Service Account	397
Restricting Domain Process Privileges	398
Setting Up the Windows Services for Oracle Tuxedo	399
Verifying the Server Installation on Microsoft Windows	401
Removing Existing Oracle Tuxedo Installations from UNIX (Optional)	402
Completing the Preinstallation Checklist on UNIX	402
Designating the Oracle Tuxedo Owner on UNIX	403
Installing Oracle Tuxedo in Silent Mode on UNIX	404
Installing the Oracle Tuxedo Patch on UNIX	406
Uninstalling the Oracle Tuxedo Patch from UNIX	406
Uninstalling Oracle Tuxedo from UNIX Using Silent Mode	407
Verifying the Server Installation on UNIX	407
Ensuring that Oracle Tuxedo Coexists with Earlier Versions	407

Chapter 13A

Configuring the Application Server on Windows	411
Understanding the Application Server	411
Prerequisites	412
Creating a Wallet for the SSL/TLS Setup	413
Using the Delivered Wallet	413
Creating a Wallet with OpenSSL	413
Setting Up COBOL for Remote Call	417
Verifying Database Connectivity	417
Creating, Configuring, and Starting an Initial Application Server Domain	417
Creating, Configuring, and Starting the Application Server Domain	417
Testing the Three-Tier Connection	422
Importing an Existing Application Server Domain Configuration	424
Setting Up a Custom Application Server Domain Configuration	427
Troubleshooting Common Errors	429

Chapter 13B

Configuring the Application Server on UNIX	431
Understanding the Application Server	431
Understanding the Application Server Domain Processes	432
Prerequisites	432
Creating a Wallet for the SSL/TLS Setup	433
Using the Delivered Wallet	433
Creating a Wallet with OpenSSL	433
Setting Environment Variables	437
Setting Up COBOL for Remote Call	438
Verifying Database Connectivity	438
Creating, Configuring, and Starting an Initial Application Server Domain	438
Creating, Configuring, and Starting the Application Server Domain	438
Testing the Three-Tier Connection	443
Importing an Existing Application Server Domain Configuration	445
Setting Up a Custom Application Server Domain Configuration	447
Troubleshooting Common Errors	450

Chapter 14

Setting Up the PeopleSoft Pure Internet Architecture in Silent Mode	451
Understanding PeopleSoft Pure Internet Architecture	451
Using Authentication Domains in the PeopleSoft Pure Internet Architecture Installation	453

Installing the PeopleSoft Pure Internet Architecture in Silent Mode	453
Understanding the Silent Installation and the Response File	454
Editing the Response File	454
Running the Silent Mode Installation	458
Configuring the SSL/TLS Port for JSL	458
Testing and Administering the PeopleSoft Pure Internet Architecture Installation	459
Verifying the PeopleSoft Pure Internet Architecture Installation	459
Starting and Stopping Oracle WebLogic	460
Using PSADMIN to Start and Stop Web Servers	461
Accessing the PeopleSoft Signon	462
Completing Post-Installation Steps	464
Using Fluid User Interface	464
Updating the Installation Table	467
Setting Options for Multilingual Databases	468
Updating PeopleTools Options	468
Updating Time Zone Information	469
Updating Database Information	469

Chapter 15A

Setting Up Process Scheduler on Windows	471
Prerequisites	471
Setting Up Process Scheduler Security	472
Understanding Process Scheduler Security	472
Changing User Account to Start ORACLE ProcMGR V12.2.2.0.0_VS2015	472
Granting Process Scheduler Administrative Rights	475
Setting Up Process Scheduler to Transfer Reports and Logs to the Report Repository	476
Understanding Report Distribution	477
Setting Up Single Signon to Navigate from PIA to Report Repository	479
Determining the Transfer Protocol	479
Starting the Distribution Agent	480
Setting Up the Report Repository	480
Setting Up the Distribution for Your Process Scheduler Server	497
Setting Up Sending and Receiving of Report Folders in the Report Manager	498
Setting Environment Variables	498
Setting Up Process Scheduler Server Agent	498
Understanding Process Scheduler Server Agent	499
Creating and Configuring a Process Scheduler Server	499
Reconfiguring a Process Scheduler Server	504
Verifying the Process Scheduler Server Status	506
Starting Process Scheduler as a Windows Service (Optional)	507
Configuring the Process Scheduler for Microsoft Word (Optional)	510

Configuring Process Scheduler	510
Executing Winword on Mapped Drive	512
Configuring Setup Manager	513
Installing Products for PS/nVision	514
Understanding the PS/nVision Setup	515
Installing Products for PS/nVision in Excel Automation Mode	515
Installing Microsoft .NET Framework 4.6.1	515
Installing Microsoft Open XML SDK for PS/nVision	516

Chapter 15B

Setting Up Process Scheduler on UNIX	521
Prerequisites	521
Setting Up Process Scheduler Security	522
Understanding Process Scheduler Security	522
Granting Process Scheduler Administrative Rights	522
Setting Up Process Scheduler to Transfer Reports and Logs to the Report Repository	523
Understanding Report Distribution	524
Setting Up Single Signon to Navigate from PIA to Report Repository	526
Determining the Transfer Protocol	526
Starting the Distribution Agent	527
Setting Up the Report Repository	527
Setting Up the Distribution for Your Process Scheduler Server	542
Setting Up Sending and Receiving of Report Folders in the Report Manager	543
Setting Up Process Scheduler Server Agent	543
Understanding Process Scheduler Server Agent	543
Changing the Default Operating System	544
Setting Up Your Environment	544
Creating and Configuring a Process Scheduler Server	545
Reconfiguring a Process Scheduler Server	550
Verifying the Process Scheduler Server Status	552

Chapter 16

Installing PeopleSoft Change Assistant	555
Understanding PeopleSoft Change Assistant	555
Installing, Upgrading, or Removing Change Assistant in Silent Mode	556
Understanding the Change Assistant Silent Mode Script	556
Using the Change Assistant Silent Mode Script to Install, Upgrade, or Uninstall	557
Using the Change Assistant Setup Script to Install, Upgrade, or Uninstall	557
Understanding the Change Assistant Setup Script	558
Running the Change Assistant Setup Script to Install	558

Running the Change Assistant Setup Script to Upgrade	559
Running Change Assistant Setup Script to Uninstall	560
Configuring and Using PeopleSoft Change Assistant	561
Verifying the Path Variable	561
Specifying Options	561
Scanning the Workstation	561
Exporting Jobs to XML, HTML, or Microsoft Excel Format	562
Validating Change Assistant Settings	562

Chapter 17

Installing PeopleSoft Change Impact Analyzer	565
Prerequisites	565
Installing and Removing PeopleSoft Change Impact Analyzer in Silent Mode	565
Understanding Silent Mode for PeopleSoft Change Impact Analyzer	566
Installing PeopleSoft Change Impact Analyzer in Silent Mode	566
Removing the PeopleSoft Change Impact Analyzer Installation in Silent Mode	567
Removing and Installing PeopleSoft Change Impact Analyzer in Silent Mode	567

Chapter 18

Adding New Product Modules	569
Adding New Modules to PeopleSoft Installations	569

Chapter 19

Using PeopleSoft Online Help	571
Understanding PeopleSoft Online Help (PeopleBooks)	571
Using the PeopleSoft Online Help Web Site for Context-Sensitive Help	572
Understanding the PeopleSoft Online Help Web Site	572
Setting Up Context-Sensitive Help with the PeopleSoft Online Help Web Site	572
Setting Up F1 Help with the PeopleSoft Online Help Web Site	575
Configuring Context-Sensitive Help with Local Installations	575
Enabling the Help Link from the Application Pages with Local Installations	575
Enabling F1 Help with Local Installations	576
Creating the Help Index for Multi-Product Installations	576
Installing PeopleSoft Online Help Locally	577
Prerequisites	577
Obtaining the PeopleSoft Documentation Files from Oracle Software Delivery Cloud	578
Deploying PeopleSoft Documentation Library on a WebLogic Server	578
Removing the PeopleSoft Online Help Deployment	593
Setting Up Help for Multiple Product Lines on the Same Machine	596

Chapter 20

Installing Software for PS/nVision Drilldowns	599
Understanding PS/nVision DrillDown Add-ins	599
Installing the DrillToPIA Add-In	600
Understanding Drilldown with DrillToPIA Add-in	600
Installing the DrillToPIA Add-in on the Microsoft Excel Environment	600
Installing the nVisionDrill Add-In	601
Understanding PS/nVision DrillDown Using Web Services	601
Understanding Security for DrillDown Using nVisionDrill VSTO Add-in	601
Installing the nVisionDrill Add-in for Microsoft Excel	601
Installing the nVisionDrill Add-Ins for Multi-Language Installations	602
Setting Up PeopleSoft Integration Broker for Using Web Service Capability with nVisionDrill Add-in	602

Chapter 21

Installing the Web Application Deployment Tool	607
Prerequisites	607
Installing the Web Application Deployment Tool in Silent Mode	608
Understanding the Web Application Deployment Tool Silent Mode Installation and the Response File	608
Editing the Web Application Deployment Tool Response File to Deploy DES	608
Running the Web Application Deployment Tool Silent Mode Installation to Deploy DES	610
Testing and Troubleshooting the Web Application Deployment	611

Appendix A

Describing Debugger Requirements	613
Describing Debugger Requirements for the AIX Operating System	613
Describing Debugger Requirements for the HP-UX Operating System	613
Describing Debugger Requirements for the Linux Operating System	613
Describing Debugger Requirements for the Oracle Solaris Operating System	614
Describing Debugger Requirements for the z/OS Operating System	614

Appendix B

Encrypting Passwords for Customizations on Linux, AIX, HP-UX, or Solaris	617
Encrypting Passwords for Customization Files on Linux, AIX, HP-UX, or Solaris	617

Appendix C

Installing IBM ILOG CPLEX	619
--	------------

Understanding the ILOG CPLEX Installation	619
Obtaining ILOG CPLEX	619
Obtaining ILOG CPLEX from Oracle Software Delivery Cloud	619
Obtaining ILOG CPLEX from My Oracle Support	620
Running the ILOG CPLEX Installation Script	620

Appendix D

Relinking SQR on UNIX	621
Understanding SQR Relinking	621
Relinking SQR on UNIX	621

About This Documentation

This preface discusses:

- Understanding This Documentation
- Audience
- Typographical Conventions
- Products
- Related Information
- Comments and Suggestions

Understanding This Documentation

This documentation is designed to direct you through a basic PeopleSoft installation. It is not a substitute for the database administration documentation provided by your relational database management system (RDBMS) vendor, the network administration documentation provided by your network vendor, or the installation and configuration documentation for additional software components that are used with PeopleSoft products.

This documentation is divided into two parts. The chapters in Part 1 include the information that is required to complete a basic PeopleSoft installation. The chapters and appendices in Part 2 include information for less common or optional tasks.

Addenda to the recent PeopleTools installation guides are periodically posted in My Oracle Support on the same page as the initial posting.

This documentation includes the instructions for installing Oracle's PeopleSoft PeopleTools and PeopleSoft applications. You also need the installation instructions that are specific to your PeopleSoft application, which are provided in a separate document for the PeopleSoft application. For instance, if you are installing Oracle's PeopleSoft Customer Relationship Management (CRM), you need both this installation guide and the additional instructions provided for installing PeopleSoft CRM.

To find the installation documentation for PeopleSoft PeopleTools or for your PeopleSoft application, go to My Oracle Support and search for the installation guide for your product and release.

Note. Before proceeding with your installation, check My Oracle Support to ensure that you have the latest version of this installation guide for the correct release of the PeopleSoft product that you are installing.

Audience

This documentation is written for the individuals responsible for installing and administering the PeopleSoft environment. This documentation assumes that you have a basic understanding of the PeopleSoft system. One of the most important components in the installation and maintenance of your PeopleSoft system is your on-site expertise.

You should be familiar with your operating environment and RDBMS and have the necessary skills to support that environment. You should also have a working knowledge of:

- SQL and SQL command syntax.

- PeopleSoft system navigation.
- PeopleSoft windows, menus, and pages, and how to modify them.
- Microsoft Windows.

Oracle recommends that you complete training, particularly a PeopleSoft Server Administration and Installation course, before performing an installation.

See Oracle University, <http://education.oracle.com>.

Typographical Conventions

To help you locate and understand information easily, the following conventions are used in this documentation:

Convention	Description
Monospace	Indicates a PeopleCode program or other code, such as scripts that you run during the install. Monospace is also used for messages that you may receive during the install process.
<i>Italics</i>	Indicates field values, emphasis, and book-length publication titles. Italics is also used to refer to words as words or letters as letters, as in the following example: Enter the letter <i>O</i> . Italics are also used to indicate user-supplied information. For example, the term <i>domain</i> is used as a placeholder for the actual domain name in the user's environment. When two such placeholders are used together, they may be set apart with angle brackets. For example, the path <code><PS_CFG_HOME>/appserv/<domain></code> includes two placeholders that require user-supplied information.
Initial Caps	Field names, commands, and processes are represented as they appear on the window, menu, or page.
lower case	File or directory names are represented in lower case, unless they appear otherwise on the interface.
Menu, Page	A comma (,) between menu and page references indicates that the page exists on the menu. For example, "Select Use, Process Definitions" indicates that you can select the Process Definitions page from the Use menu.
Cross-references	Cross-references that begin with <i>See</i> refer you to additional documentation that will help you implement the task at hand. We highly recommend that you reference this documentation. Cross-references under the heading <i>See Also</i> refer you to additional documentation that has more information regarding the subject.

Convention	Description
⇒ (line-continuation arrow)	A line-continuation arrow inserted at the end of a line of code indicates that the line of code has been wrapped at the page margin. The code should be viewed or entered as a continuous line of code, without the line-continuation arrow.
" " (quotation marks)	Indicate chapter titles in cross-references and words that are used differently from their intended meaning.
Note. Note text.	Text that begins with <i>Note</i> . indicates information that you should pay particular attention to as you work with your PeopleSoft system.
Important! Important note text.	A note that begins with <i>Important!</i> is crucial and includes information about what you need to do for the system to function properly.
Warning! Warning text.	A note that begins with <i>Warning!</i> contains critical configuration information or implementation considerations; for example, if there is a chance of losing or corrupting data. Pay close attention to warning messages.

Products

This documentation may refer to these products and product families:

- Oracle® BPEL Process Manager
- Oracle® Enterprise Manager
- Oracle® Tuxedo
- Oracle® WebLogic Server
- Oracle's PeopleSoft Application Designer
- Oracle's PeopleSoft Change Assistant
- Oracle's PeopleSoft Change Impact Analyzer
- Oracle's PeopleSoft Data Mover
- Oracle's PeopleSoft Process Scheduler
- Oracle's PeopleSoft Pure Internet Architecture
- Oracle's PeopleSoft Customer Relationship Management
- Oracle's PeopleSoft Enterprise Learning Management
- Oracle's PeopleSoft Enterprise Performance Management
- Oracle's PeopleSoft Financial Management
- Oracle's PeopleSoft Human Capital Management
- Oracle's PeopleSoft Interaction Hub
- Oracle's PeopleSoft Pay/Bill Management
- Oracle's PeopleSoft PeopleTools

- Oracle's PeopleSoft Staffing Front Office
- Oracle's PeopleSoft Supply Chain Management

See the Products area on the Oracle web site, <http://www.oracle.com/us/products/product-list/products-a-z/index.html>.

Related Information

Oracle provides reference information about PeopleSoft PeopleTools and your particular PeopleSoft Application. You can access documentation for recent releases of PeopleSoft PeopleTools and PeopleSoft Applications at the PeopleSoft Hosted Documentation site. You can also find documentation by searching for the product name on My Oracle Support.

- My Oracle Support. This support platform requires a user account to log in. Contact your PeopleSoft representative for information.

To locate documentation on My Oracle Support, search for the title and select PeopleSoft Enterprise to refine the search results.

See My Oracle Support, <https://support.oracle.com>.

- *PeopleTools: Getting Started with PeopleTools* for your release. This documentation provides a high-level introduction to PeopleTools technology and usage.

See Oracle PeopleSoft Online Help, <http://www.peoplesoftonlinehelp.com>.

- PeopleSoft Application Fundamentals for your PeopleSoft Application and release. This documentation provides essential information about the setup, design, and implementation of your PeopleSoft Application.

To install additional component software products for use with PeopleSoft products, including those products that are packaged with your PeopleSoft products as well as products from other vendors, you should refer to the documentation provided with those products, as well as this documentation. For those additional components that are offered by Oracle, such as Oracle Middleware products, see the documentation on the Oracle Help Center.

See Also

Oracle Help Center, <https://docs.oracle.com/en/>

Comments and Suggestions

Your comments are important to us. We encourage you to tell us what you like, or what you would like changed about PeopleSoft documentation and other Oracle reference and training materials. Please send your suggestions to:

PSOFT-Infodev_US@oracle.com

While we cannot guarantee to answer every email message, we will pay careful attention to your comments and suggestions. We are always improving our product communications for you.

Part I

Mandatory Installation

The chapters in the first part of this installation guide cover only those tasks that are required for a basic PeopleSoft installation. Everyone carrying out an installation should use the tasks in Part I. After setting up the Application Server, PeopleSoft Pure Internet Architecture, and Process Scheduler Server, you verify that you can sign into the PeopleSoft installation in a browser.

Chapter 1

Preparing for Installation

This chapter discusses:

- Understanding the PeopleSoft Installation
- Understanding the PeopleSoft Installation Using Deployment Packages
- Understanding the PeopleSoft Upgrade Source Deployment Packages
- Reviewing Hardware Requirements
- Reviewing Software Requirements
- Reviewing the System Parameters on Linux, AIX, HP-UX, or Solaris
- Using Oracle Software Delivery Cloud to Obtain Installation Files
- Considering Project Planning
- Planning Your Initial Configuration
- Planning Database Creation
- Planning Multilingual Strategy
- Creating PeopleSoft User IDs
- Installing the Database Engine
- Configuring DB2 UDB for Linux, UNIX, and Windows for Remote Client Access
- Installing Supporting Applications
- Performing Backups

Understanding the PeopleSoft Installation

This chapter will help you plan and prepare for a basic PeopleSoft installation. Before you begin the installation, please note:

- Before you begin your PeopleSoft installation, use the PeopleSoft hardware and software requirements information in the My Oracle Support Certifications area to verify that you have the correct hardware and software in place to support a successful installation. In addition to the information in the Certifications area, review the application-specific hardware and software documentation available on My Oracle Support.
See hardware and software requirements for PeopleSoft PeopleTools and your PeopleSoft application on My Oracle Support.
See My Oracle Support, Certifications.

Warning! If you are unable to meet any of the criteria outlined in the hardware and software requirements and certification information on My Oracle Support, contact Oracle before going forward with the installation. Attempting to complete an installation on an unsupported configuration can be a very costly decision, and Oracle will not provide support for such PeopleSoft installations.

- Use the My Oracle Support Certifications area to determine the latest certified versions of additional components, such as Oracle Tuxedo, which are supported for the PeopleSoft PeopleTools release you are installing.
- If you will be upgrading your current release after you perform this installation, you also need to install Change Assistant. The page on My Oracle Support containing your upgrade documentation and files includes information.
- For critical issues related to the installation process, see the My Oracle Support web site.
- You will use the PeopleSoft application deployment packages (DPKs) for your PeopleSoft installation. The DPKs deliver pre-installed PeopleSoft components, which can be installed on virtualization platforms as well as directly on traditional, non-virtual machines ("bare-metal").

Review the known issues on the PeopleSoft Update Manager (PUM) Home Page, My Oracle Support, Doc ID 1641843.2, for any issues related to the PeopleSoft application DPK installation.

- For online technical support information, use the My Oracle Support web site. My Oracle Support includes tools for self-directed searches of information including reference documents and problem resolutions, as well as service request management tools.

See My Oracle Support, <https://support.oracle.com>.

- To download software and documentation, use the Oracle Software Delivery Cloud portal, and My Oracle Support.

See Oracle Software Delivery Cloud, <http://edelivery.oracle.com>.

See My Oracle Support, <https://support.oracle.com>.

- Be aware that not all application releases are certified and supported to run on all PeopleSoft PeopleTools releases. Check the PeopleSoft policy information on My Oracle Support for further details on the support policy for your particular application. If you are planning to do a PeopleTools-only upgrade, do not continue until you have verified that your application is supported on the target PeopleSoft PeopleTools release.

See Lifetime Support Summary for PeopleSoft Releases, My Oracle Support, Doc ID 2238983.2.

- This installation guide may refer you to other PeopleSoft documentation resources for more information or instructions. You can access Oracle's PeopleSoft Hosted Documentation online during the installation process. For PeopleSoft PeopleTools 8.53 and later, you also have the option to install PeopleSoft Online Help documentation, a dynamic, interactive, accessible HTML version of the documentation formerly known as "PeopleBooks."
- See the PeopleSoft Tech Updates for news about new certifications, end of support or third party retirement notices as well as any other platform related information.

See Tech Update - Main Page, My Oracle Support, Doc ID 764222.1.

See Also

"Installing PeopleSoft Online Help"

Oracle's PeopleSoft Hosted Documentation, <http://www.peoplesoftonlinehelp.com>

"Installing PeopleSoft Change Assistant"

Understanding the PeopleSoft Installation Using Deployment Packages

This section discusses:

- Understanding the PeopleSoft Deployment Packages Required for Installation
- Reviewing the PeopleSoft PeopleTools DPKs
- Reviewing the PeopleSoft Application Images
- Reviewing the Installation Choices
- Reviewing the DPK Installation Process (Linux, AIX, HP-UX, Solaris, or Microsoft Windows)

Understanding the PeopleSoft Deployment Packages Required for Installation

To install PeopleSoft applications built on PeopleSoft PeopleTools 8.57 (PeopleSoft 9.2 applications as well as PeopleSoft Interaction Hub 9.1), you will use the PeopleSoft Application Images, which are comprised of deployment packages (DPKs). For most installation scenarios, you will also download the PeopleSoft PeopleTools DPKs separately.

The PeopleSoft DPKs are the delivery method for many PeopleSoft installation, upgrade, and maintenance products. This documentation refers to the set of DPKs that are used for a fresh installation of a PeopleSoft application environment as PeopleSoft Application Images. These images can also be deployed differently, and used for applying maintenance for PeopleSoft applications. In that use case, they are typically referred to as PeopleSoft Update Images, or PIs.

See PeopleSoft Update Manager (PUM) Home Page, My Oracle Support, Doc ID 1641843.2, for information on applying maintenance updates with the PIs.

See *PeopleSoft PeopleTools 8.57 Deployment Packages Installation*, "Learning About the PeopleSoft Deployment Process."

The PeopleSoft DPKs deliver pre-installed PeopleSoft components that can be deployed onto your environment. The PeopleSoft DPKs offer the flexibility of deployment on supported operating system platforms, both directly on physical machines, and on virtualization platforms. The DPKs are available on My Oracle Support and Oracle Software Delivery Cloud as zip files, and are delivered with a setup script that automates the procedure to set up a PeopleSoft environment. The script is an interactive script that verifies that the downloaded DPKs are correct, and prompts the user for the information required to set up the environment. The script also enables a user to choose various types of environments, such as a full tier, including a PeopleSoft database, or a mid-tier, with Application Server, web server and Process Scheduler, that connects to an existing database.

See "Installing the PeopleSoft Homes," Reviewing the DPK Setup Script Options.

The DPKs are delivered with the PeopleSoft Puppet modules, which are initialization and management scripts based upon the open-source Puppet software. In addition to the convenience of using the interactive DPK setup script, you can take advantage of the Puppet Hiera functionality to customize and control the installation. Note that some installation scenarios require customizations to complete the deployment.

See "Completing the DPK Initialization with Customizations."

This section describes the DPKs used in the PeopleSoft installation and overviews of the installation process for various scenarios. The PeopleSoft Application Images are available as Microsoft Windows, Linux, and Oracle VM VirtualBox DPKs. The VirtualBox DPKs are used for PUM maintenance, and are not covered in this documentation. The PeopleSoft PeopleTools 8.57 DPKs are available for IBM AIX, HP-UX, Linux, Microsoft Windows, and Oracle Solaris on SPARC operating systems.

See [Reviewing the Installation Choices](#).

Note. Oracle recommends that you use the Native OS for Linux or Native OS for Windows DPKs for a fresh installation, not the VirtualBox DPKs.

Note. Oracle supports a number of versions of UNIX and Linux, in addition to Microsoft Windows, for the PeopleSoft installation. Throughout this book, there are references to operating systems. Where necessary, this book refers to specific operating systems by name (for example, Oracle Solaris, IBM AIX, or Linux); however for simplicity and brevity, the word UNIX is sometimes used to refer to all UNIX-like operating systems, including IBM AIX, Linux, HP-UX, and Oracle Solaris for SPARC. For information on operation system support for your database platform, see the Certification information on My Oracle Support.

Reviewing the PeopleSoft PeopleTools DPKs

The PeopleSoft PeopleTools DPKs are delivered for each PeopleTools patch. The files are double-zipped. This table describes the downloaded zip files and the embedded zip files. When you follow the instructions provided in this documentation you will extract the first zip file to get the DPK setup script. When you run the setup script, it takes care of extracting the remaining zip files. Do not unzip before reading the instructions.

Downloaded Zip Files	Embedded Zip Files	Description
PEOPLETOOLS-<OS>-8.57.xx_1of4.zip	The setup folder and other files	Setup DPK
PEOPLETOOLS-<OS>-8.57.xx_2of4.zip	PT-DPK-<OS>-8.57.xx-1of2.zip	PeopleTools server, Part 1
PEOPLETOOLS-<OS>-8.57.xx_3of4.zip	PT-DPK-<OS>-8.57.xx-2of2.zip	PeopleTools server, Part 2
PEOPLETOOLS-<OS>-8.57.xx_4of4.zip	PTC-DPK-<OS>-8.57.xx-1of1.zip	PeopleTools Client for 8.57

The filenames include the following:

- <OS> is one of these operating systems:
 - AIX for IBM AIX
 - HPI for HP-UX
 - LNX for Linux
 - WIN for Microsoft Windows
 - SOL for Oracle Solaris
- xx refers to the patch number.

Reviewing the PeopleSoft Application Images

The PeopleSoft application software is delivered in the PeopleSoft Application Images posted on My Oracle Support. The DPKs that comprise the PeopleSoft Application Images are double-zipped. When you follow the instructions provided in this documentation you will extract the first zip file to get the DPK setup script. When you run the setup script, it takes care of extracting the remaining zip files. Do not unzip before reading the instructions.

The first four zip files in the PeopleSoft Application Images are the same type as the four zip files in the PeopleTools patches; that is, two PeopleTools server DPKs, a PeopleTools client DPK, and a setup DPK. However, because the PeopleSoft Application Images and the PeopleTools patches follow different schedules, the patch releases will not be the same.

Note. The PeopleTools Client DPKs are specific to Microsoft Windows operating systems. The operating system for the PeopleTools server DPKs that are packaged with the PeopleSoft Application Image is the same as the other DPKs that make up the PeopleSoft Application Image.

This table describes the zip files that you download for the Native Linux and Windows DPKs, and the embedded zip files. Note that the content description is also available in the manifest that is posted on the same pages where you can find links to the most current image. On the PeopleSoft Update Image (PUM) Home Page, select the PeopleSoft Update Images tab, and then select the update image home page for your PeopleSoft application. The links and manifest are located in the Update Image Link section.

The VirtualBox version of the PeopleSoft Application Images have a slightly different set of DPK zip files; that is, the VirtualBox Shell OVA and the Elasticsearch DPK are included in the VirtualBox images. These DPKs are not included for the Native OS for Windows and Native OS for Linux DPKs. The current documentation does not describe the installation of the VirtualBox images.

See *PeopleSoft Deployment Packages for Update Images Installation (PeopleSoft PeopleTools 8.57)*, PeopleSoft Update Image (PUM) Home Page, My Oracle Support, Doc ID 1641843.2.

Downloaded Zip Files	Files After First Extraction ¹	Description
<Product>-920-UPD-<PI_Number>-<OS>_1of11.zip	The setup folder and other files	Setup DPK
<Product>-920-UPD-<PI_Number>-<OS>_2of11.zip	PT-DPK-<OS>-8.57.xx-1of2.zip	PeopleTools server, Part 1
<Product>-920-UPD-<PI_Number>-<OS>_3of11.zip	PT-DPK-<OS>-8.57.xx-2of2.zip	PeopleTools server, Part 2
<Product>-920-UPD-<PI_Number>-<OS>_4of11.zip	PTC-DPK-WIN8.55.xx-1of1.zip	PeopleTools Client for 8.55
<Product>-920-UPD-<PI_Number>-<OS>_5of11.zip	PTC-DPK-WIN8.56.xx-1of1.zip	PeopleTools Client for 8.56
<Product>-920-UPD-<PI_Number>-<OS>_6of11.zip	PTC-DPK-WIN8.57.xx-1of1.zip	PeopleTools Client for 8.57
<Product>-920-UPD-<PI_Number>-<OS>_7of11.zip	ODC-DPK-WIN-12.1.0.2-xxxxxx-1of1.zip	Oracle Database client

Downloaded Zip Files	Files After First Extraction ¹	Description
<Product>-920-UPD-<PI_Number>-<OS>_8of11.zip	ODS-DPK-<OS>-12.1.0.2-xxxxxx-1of1.zip	Oracle Database server
<Product>-920-UPD-<PI_Number>-<OS>_9of11.zip	APP-DPK-<OS>-<Product_Name>92-8.57.xx-1of3.zip	PeopleSoft Application DPK, Part 1
<Product>-920-UPD-<PI_Number>-<OS>_10of11.zip	APP-DPK-<OS>-<Product_Name>92-8.57.xx-2of3.zip	PeopleSoft Application DPK, Part 2
<Product>-920-UPD-<PI_Number>-<OS>_11of11.zip	APP-DPK-<OS>-<Product_Name>92-8.57.xx-3of3.zip	PeopleSoft Application DPK, Part 3

¹ The filenames will vary depending upon the date posted or the associated release and patch. Note that the DPK setup script will carry out the first extraction. The names are given here for information.

The filenames for the downloaded zip files have the following format:

<Product>-920-UPD-<PI_Number>-<OS>_#ofn.zip

For example:

HCM-920-UPD-028-LNX_1of11.zip

HCM-920-UPD-028-LNX_2of11.zip

[...]

HCM-920-UPD-028-LNX_11of11.zip

The files names are comprised of the following parts:

- <Product> is an abbreviation that represents the PeopleSoft application name, as described in the following table.

PeopleSoft Application	Product Name Abbreviation
PeopleSoft Customer Relationship Management	CRM
PeopleSoft Campus Solutions	CS
PeopleSoft Enterprise Learning Management	ELM
PeopleSoft Financials and Supply Chain Management	FSCM
PeopleSoft Human Capital Management	HCM
PeopleSoft Interaction Hub	IH

- <PI_Number> is the PI image number, such as 024.
- <OS> is one of these operating systems:
 - LNX for the Native OS DPKs for Oracle Linux
 - WIN for the Native OS DPKs for Microsoft Windows
 - OVA for the VirtualBox DPKs

- n represents the total number of zip files.

Reviewing the Installation Choices

This section includes overviews of the methods to install the PeopleSoft Application Images, depending upon your operating system and other components.

If you want to use the PeopleSoft 9.2 Application PIs to create a PeopleSoft Update Manager (PUM) source for applying updates and fixes, see *PeopleSoft Deployment Packages for Update Images Installation*.

See PeopleSoft Update Manager (PUM) Home Page, My Oracle Support, Doc ID 1641843.2.

Reviewing the DPK Installation Process (Linux, AIX, HP-UX, Solaris, or Microsoft Windows)

These are the high-level steps for using the PeopleSoft Application Images to perform a fresh installation (that is, you are not upgrading or updating an existing environment):

1. Locate the Native OS DPKs for your PeopleSoft 9.2 Application, and download the PeopleSoft Application DPK, Part 1.

For installations on Linux, IBM AIX, HP-UX Itanium, or Solaris for SPARC, download the download the Native OS DPKs for Linux. For installations on Microsoft Windows, download the Native OS DPKs for Windows. Do not unzip the file. If you need to FTP the file, use binary mode.

See "Installing the PeopleSoft Homes," Obtaining the PeopleSoft Application and PeopleTools DPKs.

2. Download the PeopleTools 8.57 DPKs.
 - Select the operating system you want to install on. The PeopleTools 8.57 DPKs are available for Linux, AIX, HP-UX, Solaris, or Microsoft Windows.
 - Select the PeopleTools patch release specified for the PeopleSoft 9.2 application.
3. Before running the DPK setup script, review the setup script options. Certain installation situations require a customized procedure.

See "Installing the PeopleSoft Homes," Reviewing the DPK Setup Script Options.

4. Use the DPK setup script from the PeopleTools DPKs to carry out one of these steps:
 - Install *PS_HOME* and *PS_APP_HOME* only.
PS_HOME includes the PeopleTools utilities that you use in the next step. *PS_APP_HOME* includes the files needed to create an application database.
 - Alternatively, install *PS_HOME*, *PS_APP_HOME*, Oracle Tuxedo, and Oracle WebLogic.
5. Create a DEMO or SYS database.
6. Use the PeopleTools DPK setup script to complete the setup of the PeopleSoft domains.
 - a. If not installed in step 4, install Oracle Tuxedo and Oracle WebLogic.
 - b. Configure the application server, PeopleSoft Pure Internet Architecture (PIA) and Process Scheduler domains.
7. Complete optional tasks, such as installing and compiling COBOL.

Understanding the PeopleSoft Upgrade Source Deployment Packages

This section discusses:

- Reviewing the PeopleSoft Upgrade Source Image Usage
- Reviewing the PeopleSoft Upgrade Source Image
- Reviewing the PeopleSoft Upgrade Source Image Installation

Reviewing the PeopleSoft Upgrade Source Image Usage

The PeopleSoft Upgrade Source Images can be used during a PeopleSoft application upgrade to install a demo database, and are available for each PeopleSoft application. Keep in mind that the PeopleSoft Upgrade Source Images are not interchangeable with the PeopleSoft application images. Here is an overview of the differences:

- The PeopleSoft Upgrade Source Image is released on a different schedule, and the version numbering sequence is independent of both the PeopleSoft application images and the PeopleSoft PeopleTools patches.
- The PeopleSoft Upgrade Source Image zip file names include UPG rather than UPD.
See Reviewing the PeopleSoft Upgrade Source Image.
- The VirtualBox version of the PeopleSoft application image is not recommended for use with a fresh installation, but the VirtualBox version of the Upgrade Source Image can be used to install an upgrade demo database.
- The DPK setup script recognizes the type of DPK, and suppresses unnecessary prompts.
See Reviewing the PeopleSoft Upgrade Source Image Installation.

Reviewing the PeopleSoft Upgrade Source Image

The DPKs for the Upgrade Source Image are double-zipped. When you follow the instructions provided in this documentation you will extract the first zip file to get the DPK setup script. When you run the setup script, it takes care of extracting the remaining zip files. Do not unzip before reading the instructions.

The first four zip files in the Upgrade Source Image are the same type as the four zip files in the PeopleTools patches; that is, two PeopleTools server DPKs, a PeopleTools client DPK, and a setup DPK. However, because the Upgrade Source Image and the PeopleTools patches follow different schedules, the patch releases will not be the same.

This table describes the zip files that you download for the Native OS for Linux and Windows DPKs, and the embedded zip files. Note that the content description is also available in the manifest posted on the upgrade pages where you can find links to the most current Upgrade Source Image.

See Reviewing the PeopleSoft Upgrade Source Image Installation.

The VirtualBox DPKs have a slightly different set of zip files; that is, the VirtualBox Shell OVA and the Elasticsearch DPK are available for VirtualBox DPKs. These two DPKs are not included for the Native OS DPKs for Microsoft Windows and Linux. The current documentation does not describe the installation of the VirtualBox DPKs.

See *PeopleSoft Deployment Packages for Update Images Installation (PeopleSoft PeopleTools 8.57)*, PeopleSoft Update Image (PUM) Home Page, My Oracle Support, Doc ID 1641843.2.

Downloaded Zip Files	Files After First Extraction ¹	Description
<Product>-920-UPG-<Img_Number>-<OS>_1of9.zip	The setup folder and other files	Setup DPK
<Product>-920-UPG-<Img_Number>-<OS>_2of9.zip	PT-DPK-<OS>-8.57.xx-1of2.zip	PeopleTools server, Part 1
<Product>-920-UPG-<Img_Number>-<OS>_3of9.zip	PT-DPK-<OS>-8.57.xx-2of2.zip	PeopleTools server, Part 2
<Product>-920-UPG-<Img_Number>-<OS>_4of9.zip	PTC-DPK-WIN8.57.xx-1of1.zip	PeopleTools Client for 8.57
<Product>-920-UPG-<Img_Number>-<OS>_5of9.zip	ODC-DPK-WIN-12.1.0.2-xxxxxx-1of1.zip	Oracle Database client
<Product>-920-UPG-<Img_Number>-<OS>_6of9.zip	ODS-DPK-<OS>-12.1.0.2-xxxxxx-1of1.zip	Oracle Database server
<Product>-920-UPG-<Img_Number>-<OS>_7of9.zip	APP-DPK-<OS>-<Product_Name>92-8.57.xx-1of3.zip	PeopleSoft Application DPK, Part 1
<Product>-920-UPG-<Img_Number>-<OS>_8of9.zip	APP-DPK-<OS>-<Product_Name>92-8.57.xx-2of3.zip	PeopleSoft Application DPK, Part 2
<Product>-920-UPG-<Img_Number>-<OS>_9of9.zip	APP-DPK-<OS>-<Product_Name>92-8.57.xx-3of3.zip	PeopleSoft Application DPK, Part 3

¹ The filenames will vary depending upon the date posted or the associated release and patch. After you extract the first zip file manually, note that the DPK setup script will carry out the first extraction. The names are given here for information.

The filenames for the downloaded zip files have the following format:

<Product>-920-UPG-<Img_Number>-<OS>_#ofn.zip

For example:

HCM-920-UPG-003-LNX_1of9.zip

HCM-920-UPG-003-LNX_2of9.zip

[...]

HCM-920-UPG-003-LNX_9of9.zip

The files names are comprised of the following parts:

- *<Product>* is an abbreviation that represents the PeopleSoft application name, as described in the following table.

PeopleSoft Application	Product Name Abbreviation
PeopleSoft Customer Relationship Management	CRM
PeopleSoft Campus Solutions	CS
PeopleSoft Enterprise Learning Management	ELM
PeopleSoft Financials and Supply Chain Management	FSCM
PeopleSoft Human Capital Management	HCM
PeopleSoft Interaction Hub	IH

- *<Img_Number>* is the Upgrade Source Image version number, such as 03.
- *<OS>* is one of the following:
 - LNX for the Native OS DPKs for Oracle Linux
 - WIN for the Native OS DPKs for Microsoft Windows
 - OVA for the VirtualBox DPKs
- *n* represents the total number of zip files.

Reviewing the PeopleSoft Upgrade Source Image Installation

The installation process for the Upgrade Source Image is similar to the installation of the PeopleSoft application images, with a few differences outlined here.

Note. These instructions apply to the Upgrade Source Image that is created with PeopleSoft PeopleTools 8.57.

To install the PeopleSoft Upgrade Source Image for use as an upgrade demo database:

1. Download the Upgrade Source Image for your PeopleSoft 9.2 application.

See Reviewing the Upgrade Source Image for information on the naming convention for the downloaded DPKs.

To find usage information and the links to the latest Upgrade Source Image, select the Upgrade Source Image tab on the following upgrade home pages:

- Campus Solutions Upgrade Home Page, My Oracle Support, Doc ID 2078564.2
- CRM Upgrade Home Page, My Oracle Support, Doc ID 1961844.2.
- ELM Upgrade Home Page, My Oracle Support, Doc ID 1962959.2.
- FSCM Upgrade Home Page, My Oracle Support, Doc ID 1963697.2
- HCM Upgrade Home Page, My Oracle Support, Doc ID 1959519.2

2. Obtain the installation guide.

- If you are installing the Native OS for Linux or Windows DPKs, use the installation guide you are currently reading.

See Oracle's PeopleSoft PeopleTools 8.57 Home Page, My Oracle Support, Doc ID 2433119.2. Select

Installation and Upgrade, Installation Documentation, PeopleSoft 9.2 Application Deployment Packages.

- If you are installing the VirtualBox version of the Upgrade Source Image, use *PeopleSoft Deployment Packages for Update Images Installation (PeopleSoft PeopleTools 8.57)*.

You can find this installation guide on the PeopleSoft Update Manager Home Page. Select the Update image home page for your PeopleSoft application (for example, HCM Update Image Home Page), and locate the Installation Documentation section.

See PeopleSoft Update Image (PUM) Home Page, My Oracle Support, Doc ID 1641843.2.

3. Download the PeopleTools 8.57 DPKs.

- Select the operating system you want to install on. The PeopleTools 8.57 DPKs are available for IBM AIX, HP-UX, Linux, Microsoft Windows, and Oracle Solaris.
- Select the PeopleTools patch release specified for the PeopleSoft 9.2 application.

4. Use the PeopleTools DPK setup script to deploy the PeopleSoft environment.

When running the DPK setup script, you will not see the following prompt for the installation type, which is included when deploying the PeopleSoft application images.

```
Enter the PeopleSoft installation [PUM or FRESH] type [PUM]:
```

Task 1-1: Reviewing Hardware Requirements

This section discusses:

- Reviewing Hardware Requirements for Microsoft Windows
- Reviewing Hardware Requirements on AIX, HP-UX, Linux, or Solaris

Task 1-1-1: Reviewing Hardware Requirements for Microsoft Windows

You can install the PeopleSoft Application Image deployment packages (DPKs) or PeopleSoft PeopleTools DPKs directly on a system running a Microsoft Windows operating system. The PeopleSoft Application Images and PeopleSoft PeopleTools DPKs are certified to run on those Microsoft Windows operating systems that are certified for the current PeopleSoft PeopleTools release. The Microsoft Windows system can be a physical computer (sometimes called "bare-metal") or a virtual machine.

Oracle strongly recommends that you dedicate a Microsoft Windows machine for the PeopleTools client. This should be a machine that is not used for other PeopleSoft purposes.

See "Deploying the PeopleSoft PeopleTools Deployment Packages," Deploying the PeopleTools Client DPK in Standalone Mode, for information on installing the PeopleTools client utilities.

- *Host computer:* The PeopleSoft DPKs can be deployed directly on any supported Microsoft Windows host, bare-metal or virtual.

If you deploy on a virtual host computer, you are responsible for provisioning the virtual machine before beginning the deployment.

- *Host operating system:* The host operating system (OS) must be a 64-bit platform that is certified by Oracle for PeopleSoft systems.

Note. My Oracle Support Certification notes include information about the PeopleSoft PeopleTools components that are certified for each operating system. Some OSs are certified only for browsers and clients. If you want to deploy a full PeopleSoft environment, verify that the OS you want to use is certified for server installation.

See My Oracle Support, Certifications.

See PeopleSoft PeopleTools Certifications, My Oracle Support, Doc ID 747587.1, for help searching PeopleSoft Certifications.

- *RAM (Memory):* A minimum of 8 GB RAM is required to run a PeopleSoft environment.
- *Disk space:* The disk space requirements vary depending upon the type of environment you set up.

See "Preparing to Deploy," Understanding PeopleSoft Components.

- 25–35 GB free disk space for the downloaded zip files
You may remove these files after you have successfully initialized your virtual machine.
- 150 GB free disk space is required to deploy and set up a full tier PeopleSoft environment.
- 75 GB free disk space is required to deploy and set up a db-tier PeopleSoft environment.
- 25 GB free disk space is required to deploy and set up a mid-tier PeopleSoft environment.

See Also

Tech Update - Main Page, My Oracle Support, Doc ID 764222.1

Task 1-1-2: Reviewing Hardware Requirements on AIX, HP-UX, Linux, or Solaris

You can install the PeopleSoft Application Image deployment packages (DPKs) directly on a system running an Oracle Linux operating system. You can install the PeopleSoft PeopleTools deployment packages (DPKs) directly on a system running an IBM AIX, HP-UX, Linux, or Solaris operating system. The PeopleSoft Application Images and PeopleSoft PeopleTools DPKs are certified to run on those operating systems that are certified for the current PeopleSoft PeopleTools release. The AIX, HP-UX, Linux, or Solaris system can be a physical computer (sometimes called "bare-metal") or a virtual machine.

- *Host computer:* The PeopleSoft DPKs can be deployed on any supported AIX, HP-UX, Linux, or Solaris host, either a physical computer or virtual machine. The PeopleSoft DPKs can also be deployed on Oracle Exalogic Elastic Cloud.

If you deploy on a virtual host computer, you are responsible for provisioning the virtual machine before beginning the deployment.

- *Host operating system:* The host operating system must be a 64-bit platform that is certified by Oracle for PeopleSoft systems.

See My Oracle Support, Certifications.

See PeopleSoft PeopleTools Certifications, My Oracle Support, Doc ID 747587.1, for help searching PeopleSoft Certifications.

- *RAM (Memory):* A minimum of 8 GB RAM is required to run a PeopleSoft environment.
- *Disk space:* The disk space requirements vary depending upon the type of environment you set up.

See "Preparing to Deploy," Understanding PeopleSoft Components.

- 25–35 GB free disk space for the downloaded zip files

You may remove these files after you have successfully initialized your virtual machine.

- 150 GB free disk space is required to deploy and set up a full tier PeopleSoft environment.
- 75 GB free disk space is required to deploy and set up a db-tier PeopleSoft environment.
- 25 GB free disk space is required to deploy and set up a mid-tier PeopleSoft environment.

See Also

My Oracle Support, Certifications.

Tech Update - Main Page, My Oracle Support, Doc ID 764222.1

Task 1-2: Reviewing Software Requirements

This section discusses:

- Reviewing Software Requirements on Microsoft Windows
- Reviewing Software Requirements on Linux
- Reviewing Software Requirements on AIX
- Reviewing Software Requirements on HP-UX
- Reviewing Software Requirements on Solaris
- Reviewing Requirements for the Puppet Software on Microsoft Windows
- Reviewing Requirements for the Puppet Software on Linux
- Reviewing Requirements for the Puppet Software on AIX
- Reviewing Requirements for the Puppet Software on HP-UX
- Reviewing Requirements for the Puppet Software on Solaris

Task 1-2-1: Reviewing Software Requirements on Microsoft Windows

Here are the software requirements for using the PeopleSoft Deployment Packages on a Microsoft Windows machine:

- Administrative permission
- Read, write, and execute permission on the default temporary folder.

The deployment of a PeopleSoft environment by the DPKs installs required supporting software, such as Oracle WebLogic and Oracle Tuxedo. The DPK process to install this software uses the default temporary folders, as specified by the environment variable for the operating system. The user running the DPK setup script must have read/write/execute permission to these default temporary folders for successful DPK installation, or the deployment steps that install these components will fail.

- The DPK setup script can be run from any drive, regardless of the drive where the Windows operating system is installed.
- Web Browser

You need a version certified for the current PeopleSoft PeopleTools release for end-users.

See PeopleSoft Update Manager (PUM) Home Page, My Oracle Support, Doc ID 1641843.2.

See My Oracle Support, Certifications.

- Zip utility

You need a utility that is able to extract (unzip) the DPK zip files for your operating system.

- Verify that the `PATHEXT` environment variable includes the extension `.bat`.

This is a requirement for running Puppet. For example:

```
PATHEXT=.COM;.EXE;.BAT;.CMD;.VBS;.VBE;.JS;.JSE;.WSF;.WSH;.MSC
```

- Python 3.6.2 is included with the DPKs.
- Specifying `PS_CUST_HOME`

If you wish to use a `PS_CUST_HOME` location to store your site's custom files, you must create the directory manually and set the `PS_CUST_HOME` environment variable. The DPK setup will use the environment variable location for setting up the PeopleSoft domains.

See "Deploying the PeopleSoft Application Deployment Packages," Preparing to Run the DPK Setup Script.

Task 1-2-2: Reviewing Software Requirements on Linux

Here are the software requirements for using the PeopleSoft Deployment Packages on a Linux machine:

- You must have root access to deploy the PeopleSoft DPKs.

See "Deploying the PeopleSoft Homes," Deploying as a Non-Root User on Linux, AIX, HP-UX, or Solaris.

- Read, write, and execute permission on the default temporary folder.

The deployment of a PeopleSoft environment by the DPKs installs required supporting software, such as Oracle WebLogic and Oracle Tuxedo. The DPK process to install this software uses the default temporary folders, as specified by the environment variable for the operating system. The user running the DPK setup script must have read, write, and execute permission to these default temporary folders for successful DPK installation, or the deployment steps that install these components will fail.

- If you are installing the PeopleSoft DPKs on Oracle Linux 6 or 7 with Unbreakable Enterprise Kernel (UEK), apply the latest UEK kernel from the Oracle YUM repository at <http://public-yum.oracle.com/index.html>.

- Zip utility

You need a utility that is able to extract (unzip) the DPK zip files for your operating system; for example, tar or unzip.

- Specifying `PS_CUST_HOME`

If you wish to use a `PS_CUST_HOME` location to store your site's custom files, you must create the directory manually and set the `PS_CUST_HOME` environment variable. The DPK setup will use the environment variable location for setting up the PeopleSoft domains.

See "Deploying the PeopleSoft Application Deployment Packages," Preparing to Run the DPK Setup Script.

- Python 3.6.2 is included with the DPKs.

Task 1-2-3: Reviewing Software Requirements on AIX

Here are the software requirements for using the PeopleSoft Deployment Packages on an IBM AIX machine:

- You must have root access to deploy the PeopleSoft DPKs.

See "Deploying the PeopleSoft Homes," Deploying as a Non-Root User on Linux, AIX, HP-UX, or Solaris.

- Read, write, and execute permission on the default temporary folder.

The deployment of a PeopleSoft environment by the DPKs installs required supporting software, such as Oracle WebLogic and Oracle Tuxedo. The DPK process to install this software uses the default temporary

folders, as specified by the environment variable for the operating system. The user running the DPK setup script must have read, write, and execute permission to these default temporary folders for successful DPK installation, or the deployment steps that install these components will fail.

- Utilities for extracting the DPK zip files

You need both the gunzip and unzip utilities for your operating system in order to extract the DPK zip files, and the PATH for the root user must include the gunzip and unzip locations.

- OpenSSL

Obtain the latest version of OpenSSL for your operating system and install it on the host.

- JDK 8.0

You must manually install JDK 8.0 from the IBM web site. To obtain 64-bit IBM JDK for IBM AIX:

1. Go to the IBM JDK download and service site.

<http://www.ibm.com/developerworks/java/jdk/aix/service.html>

Note. You need a user name and password for downloading IBM JDK. If you don't have the required credentials, contact IBM AIX support.

2. Select the link for Java 8 64-bit under Java SE Version 8.
3. Provide the required information to sign in.
4. Install the JDK on the AIX computer where you will install the PeopleSoft AIX DPK.
5. Make a note of the installation location.

For the AIX DPK installation, you must perform the deployment using the DPK customizations, and specify the AIX JDK installation location.

See "Completing the DPK Initialization With Customizations," Preparing the Customization File for JDK on AIX.

- Specifying PS_CUST_HOME

If you wish to use a *PS_CUST_HOME* location to store your site's custom files, you must create the directory manually and set the *PS_CUST_HOME* environment variable. The DPK setup will use the environment variable location for setting up the PeopleSoft domains.

See "Deploying the PeopleSoft Application Deployment Packages," Preparing to Run the DPK Setup Script.

- Python 3.6.2 is included with the DPKs.

Task 1-2-4: Reviewing Software Requirements on HP-UX

Here are the software requirement for using the PeopleSoft Deployment Packages on HP-UX Itanium.

- You must have root access to deploy the PeopleSoft DPKs.

See "Deploying the PeopleSoft Homes," Deploying as a Non-Root User on Linux, AIX, HP-UX, or Solaris.

- Read, write, and execute permission on the default temporary folder.

The deployment of a PeopleSoft environment by the DPKs installs required supporting software, such as Oracle WebLogic and Oracle Tuxedo. The DPK process to install this software uses the default temporary folders, as specified by the environment variable for the operating system. The user running the DPK setup script must have read, write, and execute permission to these default temporary folders for successful DPK installation, or the deployment steps that install these components will fail.

- Utilities for extracting the DPK zip files

Install tar and zip/unzip utilities from Hewlett Packard and add the locations to your PATH:

1. Go to HP-UX Porting & Archiving Centre, at <http://hpux.connect.org.uk>.
2. Follow the instructions on the HP-UX Porting & Archiving Centre to install tar and its runtime dependencies, gettext, libiconv, and libunistring.
3. Install zip/unzip from the HP-UX Porting & Archiving Centre, at <http://hpux.connect.org.uk>.
4. Add the installation locations for tar, zip, and unzip to PATH.

Make sure that the installation location for tar is first in the PATH. For example, if you installed tar to /usr/local/bin:

```
export PATH=/usr/local/bin:$PATH
```

5. Set LD_LIBRARY_PATH. For example, if your installation location above was in /usr/local:

```
export LD_LIBRARY_PATH=/usr/local/lib${LD_LIBRARY_PATH+:$LD_LIBRARY_PATH}
```

- **OpenSSL**

Install the latest version of OpenSSL on the host where you will run the DPK setup script.

1. Go to the HP-UX Porting and Archive Centre web site, at <http://hpux.connect.org.uk/hppd/hpux/>.
2. Search for *openssl*, and locate the latest version of OpenSSL in the list of results.
3. Select the link for the latest OpenSSL package, for example openssl-1.0.2p.
4. Download the gzipped binary package for 64-bit Itanium; for this example, this is openssl-1.0.2p-ia64-11.31.depot.gz.
5. Use the installation documentation on the same page to install the OpenSSL package.

- **JDK 8.0**

You must manually install JDK 8.0 from the Hewlett Packard web site. To obtain 64-bit JDK for HP-UX Itanium:

1. Go to the Hewlett Packard Software Depot.
See Hewlett Packard Software Depot,
https://h20392.www2.hpe.com/portal/swdepot/index.do?lc=EN_US.
2. Locate the link for the latest JDK/JRE for your HP-UX operating system.
Select the link for Version 8.0.14 or higher.
3. Install the JDK on the HP-UX computer where you will install the PeopleSoft HP-UX DPK.
4. Make a note of the installation location.

For the HP-UX DPK installation, you must perform the deployment using the DPK customizations, and specify the HP-UX JDK installation location.

See "Completing the DPK Initialization With Customizations," Preparing the Customization File for JDK on HP-UX.

- **Specifying PS_CUST_HOME**

If you wish to use a *PS_CUST_HOME* location to store your site's custom files, you must create the directory manually and set the *PS_CUST_HOME* environment variable. The DPK setup will use the environment variable location for setting up the PeopleSoft domains.

See "Deploying the PeopleSoft Application Deployment Packages," Preparing to Run the DPK Setup Script.

- Python 3.6.2 is included with the DPKs.

Task 1-2-5: Reviewing Software Requirements on Solaris

Here are the software requirements for using the PeopleSoft Deployment Packages on Solaris:

- You must have root access to deploy the PeopleSoft DPKs.
See "Deploying the PeopleSoft Homes," Deploying as a Non-Root User on Linux, AIX, HP-UX, or Solaris.
- Read, write, and execute permission on the default temporary folder.
The deployment of a PeopleSoft environment by the DPKs installs required supporting software, such as Oracle WebLogic and Oracle Tuxedo. The DPK process to install this software uses the default temporary folders, as specified by the environment variable for the operating system. The user running the DPK setup script must have read, write, and execute permission to these default temporary folders for successful DPK installation, or the deployment steps that install these components will fail.
- Zip utility
You need a utility that is able to extract (unzip) the DPK zip files for your operating system; for example, tar or unzip.
- OpenSSL
Obtain the latest version of OpenSSL for your operating system and install it on the host.
- Specifying PS_CUST_HOME
If you wish to use a *PS_CUST_HOME* location to store your site's custom files, you must create the directory manually and set the *PS_CUST_HOME* environment variable. The DPK setup will use the environment variable location for setting up the PeopleSoft domains.
See "Deploying the PeopleSoft Application Deployment Packages," Preparing to Run the DPK Setup Script.
- Python 3.6.2 is included with the DPKs.

Task 1-2-6: Reviewing Requirements for the Puppet Software on Microsoft Windows

The PeopleSoft DPKs are delivered with the PeopleSoft Puppet modules, which are initialization and management scripts based upon open-source Puppet software.

- Installation requirements
In most cases, the Puppet software will be installed by the DPKs. In some scenarios it may be necessary for you to install either Puppet or its dependencies directly. If so, use these guidelines:
 - The DPK deployment requires open-source Puppet software.
See the Puppet Labs Web site at www.puppetlabs.com to download the software.
 - Customer installation of Puppet is supported for Microsoft Windows operating systems.
- These are the minimum requirements for the software versions associated with using Puppet with the PeopleSoft DPKs on Microsoft Windows operating systems:
 - Puppet Agent 5.3.5
 - Puppet 5.3.5
 - Hieria 3.4.2
 - Facter 2.4.4
 - Ruby 2.4.3
 - MCollective 2.11.4

- Operating system packages required for Puppet

The Puppet software used for the DPK deployment is dependent on certain OS-level packages, which may not be present in the delivered DPKs. In this case, you can use the information in the DPK setup log file to determine which packages are needed. It is the responsibility of the user to obtain and install the required packages.

See "Deploying the PeopleSoft PeopleTools Deployment Packages," Obtaining Operating System Packages Required for Puppet.

- Installation location

Puppet software is installed in a standard location by the DPKs. The DPK deployment checks for existing Puppet installations only in that standard location. If Puppet software was installed in a different location, for example for other business or development requirements, the DPK will not recognize or try to remove that existing Puppet installation. It will install to the standard location dictated by the DPK requirement, and the other Puppet installation may subsequently cause problems.

Task 1-2-7: Reviewing Requirements for the Puppet Software on Linux

The PeopleSoft DPKs are delivered with the PeopleSoft Puppet modules, which are initialization and management scripts based upon open-source Puppet software.

- You must have root access to deploy the PeopleSoft DPKs.

See "Deploying the PeopleSoft Homes," Deploying as a Non-Root User on Linux, AIX, HP-UX, or Solaris.

- The Puppet directory and its scripts must have read and execute permissions for all users.

Puppet must be installed by the root user, either by running the DPK setup for any env_type or by running the prereq step for non-root users. If the root user has a non-default umask, when Puppet is installed by the root user, the files in the Puppet directory will not have the correct permissions for other users, which would impact non-root users who subsequently try to run the DPK setup.

For example, if root has umask of 027, the permissions would be set as in the following example:

```
-rwxr-x--- 1 root root 126 Feb 12 2018 /opt/puppetlabs/puppet/bin⇒
/wrapper.sh
```

In this case, the root user has read, write, and execute permissions for files in this Puppet installation. The group that root belongs to has read and execute permission, and all other users have no permissions. So a non-root user will not have read and execute permissions for running the scripts in the Puppet directory (wrapper.sh in this example). Without the necessary permissions for the Puppet files, when the non-root user runs the DPK setup, Puppet execution will fail, because that user will not be able to execute any script or binary from the Puppet directory.

- Installation requirements

In most cases, the Puppet software will be installed by the DPKs. In some scenarios it may be necessary for you to install either Puppet or its dependencies directly. If so, use these guidelines:

- The DPK deployment requires open-source Puppet software.

See the Puppet Labs Web site at www.puppetlabs.com to download the software.

- Customer installation of Puppet is supported for Linux operating systems.
- These are the minimum requirements for the software versions associated with using Puppet with the PeopleSoft DPKs on Linux operating systems:
 - Puppet Agent 5.3.5
 - Puppet 5.3.5

- Hiera 3.4.2
- Facter 2.4.4
- Ruby 2.4.3
- MCollective 2.11.4
- Operating system packages required for Puppet

The Puppet software used for the DPK deployment is dependent on certain OS-level packages, which may not be present in the delivered DPKs. In this case, you can use the information in the DPK setup log file to determine which packages are needed. It is the responsibility of the user to obtain and install the required packages.

See "Deploying the PeopleSoft PeopleTools Deployment Packages," Obtaining Operating System Packages Required for Puppet.

- Installation location

Puppet software is installed in a standard location by the DPKs. The DPK deployment checks for existing Puppet installations only in that standard location. If Puppet software was installed in a different location, for example for other business or development requirements, the DPK will not recognize or try to remove that existing Puppet installation. It will install to the standard location dictated by the DPK requirement, and the other Puppet installation may subsequently cause problems.

Task 1-2-8: Reviewing Requirements for the Puppet Software on AIX

The PeopleSoft DPKs are delivered with the PeopleSoft Puppet modules, which are initialization and management scripts based upon open-source Puppet software.

- You must have root access to deploy the PeopleSoft DPKs.

See "Deploying the PeopleSoft Homes," Deploying as a Non-Root User on Linux, AIX, HP-UX, or Solaris.

- The Puppet directory and its scripts must have read and execute permissions for all users.

Puppet must be installed by the root user, either by running the DPK setup for any env_type or by running the prereq step for non-root users. If the root user has a non-default umask, when Puppet is installed by the root user, the files in the Puppet directory will not have the correct permissions for other users, which would impact non-root users who subsequently try to run the DPK setup.

For example, if root has umask of 027, the permissions would be set as in the following example:

```
-rwxr-x--- 1 root root 126 Feb 12 2018 /opt/puppetlabs/puppet/bin→
/wrapper.sh
```

In this case, the root user has read, write, and execute permissions for files in this Puppet installation. The group that root belongs to has read and execute permission, and all other users have no permissions. So a non-root user will not have read and execute permissions for running the scripts in the Puppet directory (wrapper.sh in this example). Without the necessary permissions for the Puppet files, when the non-root user runs the DPK setup, Puppet execution will fail, because that user will not be able to execute any script or binary from the Puppet directory.

- Installation requirements

In most cases, the Puppet software will be installed by the DPKs. In some scenarios it may be necessary for you to install either Puppet or its dependencies directly. If so, use these guidelines:

- The DPK deployment requires open-source Puppet software.
See the Puppet Labs Web site at www.puppetlabs.com to download the software.
- Customer installation of Puppet is not supported for IBM AIX operating systems.

If you are installing the PeopleSoft DPKs for IBM AIX, you must use the Puppet software that is delivered with the DPKs.

- If you are installing the PeopleSoft DPKs for IBM AIX, check the Puppet web site for Puppet dependencies or limitations for those operating systems.
- These are the minimum requirements for the software versions associated with using Puppet with the PeopleSoft DPKs on AIX operating systems:
 - Puppet Agent 5.3.5
 - Puppet 5.3.5
 - Hiera 3.4.2
 - Facter 2.4.4
 - Ruby 2.4.4
- Operating system packages required for Puppet

The Puppet software used for the DPK deployment is dependent on certain OS-level packages, which may not be present in the delivered DPKs. In this case, you can use the information in the DPK setup log file to determine which packages are needed. It is the responsibility of the user to obtain and install the required packages.

See "Deploying the PeopleSoft PeopleTools Deployment Packages," Obtaining Operating System Packages Required for Puppet.

- Installation location

Puppet software is installed in a standard location by the DPKs. The DPK deployment checks for existing Puppet installations only in that standard location. If Puppet software was installed in a different location, for example for other business or development requirements, the DPK will not recognize or try to remove that existing Puppet installation. It will install to the standard location dictated by the DPK requirement, and the other Puppet installation may subsequently cause problems.

Task 1-2-9: Reviewing Requirements for the Puppet Software on HP-UX

The PeopleSoft DPKs are delivered with the PeopleSoft Puppet modules, which are initialization and management scripts based upon open-source Puppet software.

- You must have root access to deploy the PeopleSoft DPKs.

See "Deploying the PeopleSoft Homes," Deploying as a Non-Root User on Linux, AIX, HP-UX, or Solaris.

- The Puppet directory and its scripts must have read and execute permissions for all users.

Puppet must be installed by the root user, either by running the DPK setup for any env_type or by running the prereq step for non-root users. If the root user has a non-default umask, when Puppet is installed by the root user, the files in the Puppet directory will not have the correct permissions for other users, which would impact non-root users who subsequently try to run the DPK setup.

For example, if root has umask of 027, the permissions would be set as in the following example:

```
-rwxr-x--- 1 root root 126 Feb 12 2018 /opt/puppetlabs/puppet/bin⇒
/wrapper.sh
```

In this case, the root user has read, write, and execute permissions for files in this Puppet installation. The group that root belongs to has read and execute permission, and all other users have no permissions. So a non-root user will not have read and execute permissions for running the scripts in the Puppet directory (wrapper.sh in this example). Without the necessary permissions for the Puppet files, when the non-root user runs the DPK setup, Puppet execution will fail, because that user will not be able to execute any script or binary from the Puppet directory.

- Installation requirements

In most cases, the Puppet software will be installed by the DPKs. In some scenarios it may be necessary for you to install either Puppet or its dependencies directly. If so, use these guidelines:

- The DPK deployment requires open-source Puppet software.

See the Puppet Labs Web site at www.puppetlabs.com to download the software.

- Customer installation of Puppet is not supported for HP-UX operating systems.

If you are installing the PeopleSoft DPKs for HP-UX, you must use the Puppet software that is delivered with the DPKs.

- If you are installing the PeopleSoft DPKs for HP-UX, check the Puppet web site for Puppet dependencies or limitations for those operating systems.

- These are the minimum requirements for the software versions associated with using Puppet with the PeopleSoft DPKs on HP-UX operating systems:

- Puppet Agent 5.3.5
- Puppet 5.3.5
- Hiera 3.4.2
- Facter 2.4.4
- Ruby 2.4.4

- Operating system packages required for Puppet

The Puppet software used for the DPK deployment is dependent on certain OS-level packages, which may not be present in the delivered DPKs. In this case, you can use the information in the DPK setup log file to determine which packages are needed. It is the responsibility of the user to obtain and install the required packages.

See "Deploying the PeopleSoft PeopleTools Deployment Packages," Obtaining Operating System Packages Required for Puppet.

- Installation location

Puppet software is installed in a standard location by the DPKs. The DPK deployment checks for existing Puppet installations only in that standard location. If Puppet software was installed in a different location, for example for other business or development requirements, the DPK will not recognize or try to remove that existing Puppet installation. It will install to the standard location dictated by the DPK requirement, and the other Puppet installation may subsequently cause problems.

Task 1-2-10: Reviewing Requirements for the Puppet Software on Solaris

The PeopleSoft DPKs are delivered with the PeopleSoft Puppet modules, which are initialization and management scripts based upon open-source Puppet software.

- You must have root access to deploy the PeopleSoft DPKs.

See "Deploying the PeopleSoft Homes," Deploying as a Non-Root User on Linux, AIX, HP-UX, or Solaris.

- The Puppet directory and its scripts must have read and execute permissions for all users.

Puppet must be installed by the root user, either by running the DPK setup for any env_type or by running the prereq step for non-root users. If the root user has a non-default umask, when Puppet is installed by the root user, the files in the Puppet directory will not have the correct permissions for other users, which would impact non-root users who subsequently try to run the DPK setup.

For example, if root has umask of 027, the permissions would be set as in the following example:

```
-rwxr-x--- 1 root root 126 Feb 12 2018 /opt/puppetlabs/puppet/bin→
/wrapper.sh
```

In this case, the root user has read, write, and execute permissions for files in this Puppet installation. The group that root belongs to has read and execute permission, and all other users have no permissions. So a non-root user will not have read and execute permissions for running the scripts in the Puppet directory (wrapper.sh in this example). Without the necessary permissions for the Puppet files, when the non-root user runs the DPK setup, Puppet execution will fail, because that user will not be able to execute any script or binary from the Puppet directory.

- Installation requirements

In most cases, the Puppet software will be installed by the DPKs. In some scenarios it may be necessary for you to install either Puppet or its dependencies directly. If so, use these guidelines:

- The DPK deployment requires open-source Puppet software.

See the Puppet Labs Web site at www.puppetlabs.com to download the software.

- Customer installation of Puppet is not supported for Solaris operating systems.

If you are installing the PeopleSoft DPKs for Solaris, you must use the Puppet software that is delivered with the DPKs.

- Before installing the PeopleSoft DPKs for Solaris, check the Puppet web site for Puppet dependencies or limitations for those operating systems.

- These are the minimum requirements for the software versions associated with using Puppet with the PeopleSoft DPKs on Oracle Solaris for SPARC operating systems:

- Puppet Agent 5.3.5
- Puppet 5.3.5
- Hiera 3.4.2
- Facter 2.4.4
- Ruby 2.4.4

- Operating system packages required for Puppet

The Puppet software used for the DPK deployment is dependent on certain OS-level packages, which may not be present in the delivered DPKs. In this case, you can use the information in the DPK setup log file to determine which packages are needed. It is the responsibility of the user to obtain and install the required packages.

See "Deploying the PeopleSoft PeopleTools Deployment Packages," Obtaining Operating System Packages Required for Puppet.

- Installation location

Puppet software is installed in a standard location by the DPKs. The DPK deployment checks for existing Puppet installations only in that standard location. If Puppet software was installed in a different location, for example for other business or development requirements, the DPK will not recognize or try to remove that existing Puppet installation. It will install to the standard location dictated by the DPK requirement, and the other Puppet installation may subsequently cause problems.

Task 1-3: Reviewing the System Parameters on Linux, AIX, HP-UX, or Solaris

The generated YAML file for UNIX operating systems includes settings for certain system parameters. When you run the DPK setup script on Linux, AIX, HP-UX, or Solaris, the script overwrites those system-level parameters that are different from the values in *BASE_DIR*/dpk/puppet/production/data/psft_unix_system.yaml.

- The psft_unix_system.yaml file includes the following sysctl parameters:

```
sysctl:
  kernel.msgmnb:      65538
  kernel.msgmni:      1024
  kernel.msgmax:      65536
  kernel.shmmax:      68719476736
  kernel.shmall:      4294967296
  kernel.core_uses_pid: 1
  net.ipv4.tcp_keepalive_time: 90
  net.ipv4.tcp_timestamps: 1
  net.ipv4.tcp_window_scaling: 1
  net.ipv4.ip_local_port_range: '10000 65500'
```

- The psft_unix_system.yaml file includes the following ulimits parameters:

```
ulimit:
  group:
    hard.nofile: 65536
    soft.nofile: 65536
    hard.nproc: 65536
    soft.nproc: 65536
    hard.core: unlimited
    soft.core: unlimited
    hard.memlock: 500000
    soft.memlock: 500000
    hard.stack: 102400
    soft.stack: 102400

  user:
    hard.nofile: 131072
    soft.nofile: 131072
    hard.nproc: 131072
    soft.nproc: 131072
    hard.core: unlimited
    soft.core: unlimited
    hard.memlock: 500000
    soft.memlock: 500000
```

Task 1-4: Using Oracle Software Delivery Cloud to Obtain Installation Files

Before beginning the installation, you should have obtained the PeopleSoft installation software by downloading the necessary zip files from the Oracle Software Delivery Cloud portal or My Oracle Support. Use the information available in the PeopleSoft documentation and My Oracle Support Certifications to be sure that you obtain all the zip files required for your environment.

See Oracle Software Delivery Cloud, <http://edelivery.oracle.com>.

See My Oracle Support, <https://support.oracle.com>.

In case you have not yet obtained the necessary files, this documentation includes sections on obtaining the files at appropriate points during the installation process.

Note. If your PeopleSoft installation uses Oracle SOA Suite, note that the 32-bit versions of the Oracle SOA Suite 10g media components on the Oracle Software Delivery Cloud portal are certified to run on the Linux x86-64 and the Microsoft Windows 64-bit operating system platforms.

See Also

Downloading Software from Oracle Software Delivery Cloud, My Oracle Support, Doc ID 2098595.1

Task 1-5: Considering Project Planning

Identify the maintenance schedule for upcoming PeopleSoft PeopleTools and PeopleSoft application releases. These releases are typically on a regular schedule (for example, quarterly, biannually) and should be included in your project planning and budgeting processes. Maintenance schedules are posted on My Oracle Support. It is important to plan regular maintenance in your overall project plans. For example, for a year-long enterprise upgrade, development, and conversion project, make sure to set aside time for applying the PeopleSoft PeopleTools minor releases that ship during that time frame. Otherwise, if you fall behind, you may find that you need a fix shipped with one of the minor releases that cannot be backported as a patch.

Search for the term "maintenance schedules" on My Oracle Support. You can find schedules by year and quarter for PeopleSoft PeopleTools and PeopleSoft applications. The schedules include lists of bundles and maintenance packs for individual products.

Task 1-6: Planning Your Initial Configuration

This section discusses:

- Understanding Workstations
- Understanding PeopleSoft Servers and Clients
- Defining the PeopleTools Client
- Defining the File Server
- Defining the Database Server
- Defining the Application Server

- Defining the Process Scheduler (Batch) Server
- Defining Installation Locations
- Defining the Web Server

Note. Oracle supports a number of versions of UNIX and Linux in addition to Microsoft Windows for the PeopleSoft installation. Throughout this book, there are references to operating systems. Where necessary, this book refers to specific operating systems by name (for example, Oracle Solaris, IBM AIX, HP-UX, or Linux); however, for simplicity the word UNIX is often used to refer to all UNIX-like operating systems, including Linux.

Note. For the sake of brevity, this documentation sometimes refers to DB2 for Linux, UNIX, and Windows as *DB2/LUW*.

Understanding Workstations

Using the PeopleTools Development Environment (Microsoft Windows-Based Clients)

Microsoft Windows-based clients are referred to as the PeopleTools Development Environment. These clients—which run on supported Microsoft Windows platforms—can connect to the PeopleSoft database directly using client connectivity software (a two-tier connection) or through a PeopleSoft application server (a three-tier connection).

Three-tier connectivity offers great performance advantages over two-tier (especially over a WAN), reduces network traffic, and generally does not require that you install database connectivity on the client. However, any Microsoft Windows-based clients that will be running Data Mover scripts against the database, or running COBOL or Structured Query Report (SQR) batch processes on the client, must have database connectivity installed.

Note. COBOL is not needed for PeopleTools or for applications that contain no COBOL programs. Check My Oracle Support for details about whether your application requires COBOL.

See *Installing Supporting Applications*.

You need to have the PeopleTools Development Environment set up to create your database. For more information on setting up the PeopleTools Development Environment, refer to the product documentation for PeopleSoft Configuration Manager.

See the *PeopleTools: System and Server Administration* product documentation for more information about using PeopleSoft Configuration Manager.

For installation purposes, you must set up at least one Microsoft Windows-based client for sign-on using a two-tier connection to the database, so that it can create and populate the PeopleSoft database. This documentation refers to this client as the install workstation. Depending on your installation plan, you may want to set up more than one install workstation so that you can perform asynchronous installation tasks in parallel.

Note. The Microsoft Windows machine that you use to perform your PeopleSoft PeopleTools installation must be running in 256-color mode or higher when running the PeopleSoft installation and database configuration on Microsoft Windows. This is not necessary for UNIX or console mode.

Using Workstations Equipped with Supported Web Browsers

To run the PeopleSoft Pure Internet Architecture, the client workstation only needs a web browser that is HTML 4.0 compliant. You may need an additional workstation for demonstration and testing purposes if you plan to use a browser running on a platform other than Microsoft Windows—such as Macintosh or UNIX.

See *PeopleTools: Portal Technology*.

See My Oracle Support, Certifications.

Understanding PeopleSoft Servers and Clients

Here is a summary of the functionality included in the PeopleSoft servers and clients:

- *File Server*
All Client executables (such as PeopleSoft Application Designer and Configuration Manager), PS/nVision, Change Assistant, files and directories necessary to perform upgrade, and Client SQR.
See Defining the File Server
- *PeopleTools Client*
All Client executables (such as PeopleSoft Application Designer and Configuration Manager), PS/nVision, Change Assistant, Change Impact Analyzer, PeopleSoft Test Framework, PSEM Agent, and Client SQR.
See Defining the PeopleTools Client.
- *Application Server*
PSADMIN and COBOL for remote call
- *Database Server*
Scripts and data directories, files necessary to run Data Mover.
- *Process Scheduler Server*
PSADMIN, COBOL, and SQR.
- *Web Server*
The Web Server contains all the scripts file, Portal Search data files, and PeopleSoft Pure Internet Architecture (PIA) installation tools that can assist in setting up a web server domain. However, to run the PeopleSoft Pure Internet Architecture, the client workstation only needs a web browser that is HTML 4.0 compliant.

Task 1-6-1: Defining the PeopleTools Client

The PeopleTools Client is the environment repository for the PeopleSoft PeopleTools Development environment. The PeopleTools Client provides two-tier and three-tier connectivity to PeopleSoft applications.

To install the PeopleTools Client, use the script included with the PeopleTools Client DPK. Keep in mind that the PeopleTools Client can be installed *only* on supported Microsoft Windows operating systems.

Note. The client may be referred to as the PeopleTools Client, PT Client, or PeopleSoft Microsoft Windows client in this documentation.

See "Deploying the PeopleTools Client DPK."

Task 1-6-2: Defining the File Server

The file server is the environment (or file) repository for the PeopleTools Development Environment, which is needed for the Database Configuration Wizard. The file server is also the repository for the files necessary to perform an upgrade. This includes Change Assistant and all of the executables and scripts that are necessary to perform an upgrade. You will apply patches and updates from My Oracle Support directly to the file server and then copy the updated files to your other servers. In addition, the file server is a source repository for COBOL and SQR.

Important! Remember, a COBOL compiler is not needed for PeopleSoft PeopleTools unless your application contains COBOL programs. If your application requires COBOL and you are running on Microsoft Windows, we require that you maintain a central repository of your COBOL source code on the Windows file server. See the task Installing Supporting Applications later in this chapter for details on where you should install your COBOL compiler.

If you follow the default procedures recommended in this documentation, the install workstations, Microsoft Windows batch servers, and Microsoft Windows report servers will access the PeopleSoft files on the file server by pointing to a directory referred to in this documentation as *PS_HOME* on a shared network drive. You can install SQR on the file server, or install them locally on Microsoft Windows batch servers and on Microsoft Windows-based clients that will be running these processes locally.

Setting up a file server is part of installations on both UNIX and Microsoft Windows environments. If you are doing an installation only for UNIX computers, you need a Microsoft Windows file server. If you are working only on Microsoft Windows, and you install the file server along with the other servers, you do not need to repeat the file server setup.

If you need to set up the file server on a separate Microsoft Windows machine, you should install PeopleSoft PeopleTools, any PeopleSoft applications, and the Multilanguage files.

In some cases you may choose to set up local copies of the PeopleSoft executables on the PeopleTools Development Environment and Windows batch servers, rather than mapping to a shared directory on the file server. You can use the instructions in the chapter "Using the PeopleSoft Installer" to perform such local installations.

Task 1-6-3: Defining the Database Server

The servers that host your PeopleSoft databases need sufficient processing, storage, and networking resources to process the database requests, store the data and transaction logs, and communicate freely to the clients of this data. These databases will include your own PeopleSoft database prototypes as well as any system and demonstration databases delivered directly from Oracle with the PeopleSoft installation media.

See Planning Database Creation.

Database sizes vary depending on the applications that you install. The size of your prototype PeopleSoft database will also depend on the amount of data to be converted from your legacy system. A good rule of thumb for estimating the size of your prototype PeopleSoft database is to estimate the amount of disk space needed for the data to be converted from your legacy system, add to this the size required for the PeopleSoft System database, and then add an additional 50 percent of this combined figure to allow for growth.

Task 1-6-4: Defining the Application Server

The application server is the centerpiece of the PeopleSoft Pure Internet Architecture. It connects to the PeopleSoft database and handles almost all SQL-intensive interactions with the database server required during online transaction processing. Microsoft Windows-based clients, in three-tier, communicate with the application server using Oracle Tuxedo messages. In the PeopleSoft Pure Internet Architecture, the application server interacts with user workstations through a web server.

The application server also provides functionality required for application messaging and for implementing the PeopleSoft Pure Internet Architecture. An application server is required in all PeopleSoft installations.

With DB2/LUW, you generally install the application server on the same machine as the database server, a configuration called *logical three-tier*. You can also install application servers on one or more separate UNIX, or Microsoft Windows machines. This configuration is called *physical three-tier*. (See the Certification area on My Oracle Support for information on supported operating systems for PeopleSoft Application Servers.)

All application servers require database connectivity to the database server. Before beginning your installation, make sure that you can connect from the application server machine to the database server using a SQL tool. This topic will be addressed later in this chapter.

See Also

PeopleTools: Portal Technology

Task 1-6-5: Defining the Process Scheduler (Batch) Server

The term *batch server* is equivalent to the term *Process Scheduler server*. PeopleSoft batch processes, such as COBOL and SQR, are scheduled and invoked by a Process Scheduler server. In almost all configurations, batch server SQR and COBOL files are located and executed on the same computer as the database server.

Note. If the batch server is located on a UNIX platform, the SQR and COBOL files must be transferred from the file server to the database server, and COBOL source files must be compiled.

Oracle supports setting up the batch environments on a dedicated server, an application server, or even on the database server.

For Windows-specific batch processes—such as nVision reports, Cube Builder, or Microsoft Word—you need to set up a Windows batch environment on a Microsoft Windows application server or on a dedicated Microsoft Windows workstation.

Any computer operating as a batch server must have database connectivity installed so that it can make a two-tier connection to the PeopleSoft database.

See Also

PeopleTools: Process Scheduler

Task 1-6-6: Defining Installation Locations

Understanding Installation Locations

As you proceed through the PeopleSoft PeopleTools installation, you are asked to specify several installation locations. Use the information in this section to choose how to specify the installation locations for the various components in a PeopleSoft installation.

In addition to these installation locations, there are home directories for the various supporting software, such as Oracle WebLogic, which are described in the appropriate chapters.

Defining the DPK Base Directory

When you use the PeopleSoft DPKs to install a PeopleSoft environment, you specify a base directory, referred to in this documentation as *BASE_DIR*. The DPK setup script creates the following directories under *BASE_DIR*:

- *BASE_DIR*/dpk
 - The script uses this directory to extract the archives from the PeopleSoft DPKs.
 - The Puppet YAML files for the installation configuration are installed in *BASE_DIR*/dpk/puppet/production.
- *BASE_DIR*/pt

The script deploys the PeopleSoft components to the following installation locations:

- *PS_HOME* is installed by default in *<BASE_DIR>/pt/ps_home<peopletools_patch_version>*, where *<peopletools_patch_version>* is the full release; for example, *ps_home8.57.12*.
- *PS_APP_HOME* is installed by default in *<BASE_DIR>/pt/<app>_app_home*, where *<app>* is the PeopleSoft product, such as *fscm_app_home*.
- The Oracle Tuxedo software is installed by default in *BASE_DIR*/pt/bea/tuxedo.
- The Oracle WebLogic software is installed by default in *BASE_DIR*/pt/bea/wlserver.
- The supported JDK software is installed by default in *<BASE_DIR>/pt/jdk1.8.0_yy*, where *yy* is the supported JDK version.
- For a full-tier installation, the files needed to install the supported version of the PeopleSoft PeopleTools client software are installed in *BASE_DIR*/pt/tools_client.
- *BASE_DIR*/db

This directory is used for an Oracle RDBMS full-tier installation.

 - Oracle database server software is installed by default in *BASE_DIR*/db/oracle-server.
 - For a full-tier installation, Oracle container database (CDB) and pluggable database (PDB) files and tables for the PeopleSoft application are installed by default in *BASE_DIR*/db/oradata.

Defining PS_HOME

The *PS_HOME* directory holds the PeopleSoft PeopleTools files. For information on setting up *PS_HOME* as a read-only environment, see the *PeopleTools: System and Server Administration* product documentation on securing *PS_HOME* and *PS_CFG_HOME*.

PS_HOME can be used in the following ways:

- Multiple hosts can access *PS_HOME* on a shared (Microsoft Windows) or mounted (UNIX) location.
- Several Application Server, PIA, and Process Scheduler domains can use the same *PS_HOME*.

Defining *PS_APP_HOME*

The *PS_APP_HOME* location holds the PeopleSoft application files, in a location that is separate from *PS_HOME*. The *PS_APP_HOME* location is sometimes referred to as "Application Home."

Note. The PeopleSoft DPK setup requires that *PS_APP_HOME* be installed to a different location than *PS_HOME*. In earlier PeopleSoft releases, it was possible to set up an environment with the *PS_APP_HOME* location the same as the *PS_HOME* location. This configuration is not supported for the DPK installations.

Defining *PS_CFG_HOME*

The *PS_CFG_HOME* location holds the configuration files for the application server, batch server and search server domains.

It also holds the configuration files for web server domains if *PIA_HOME*, defined in the next section, is equal to *PS_CFG_HOME*. This location is sometimes referred to as "Config Home."

When you install PeopleSoft PeopleTools and the PeopleSoft application software, the PeopleSoft installer places the required files into the specified *PS_HOME* directory. When you create an application server, batch server, or search server domain, the configuration files associated with that domain are installed into a directory referred to as *PS_CFG_HOME*.

By default, the system separates the binary files (executables and libraries) stored in *PS_HOME* from the ASCII files (configuration and log files) associated with a domain stored in *PS_CFG_HOME*. This separation applies only to these servers:

- PeopleSoft Application Server
- PeopleSoft Process Scheduler Server
- PeopleSoft Search Server

The DPK deployment creates the *PS_CFG_HOME* directory in the following locations:

Operating System	<i>PS_CFG_HOME</i> Default Location
UNIX	/home/psadm2/psft/pt/<peopletools_major_version>
Microsoft Windows	%USERPROFILE%\psft\pt\<peopletools_major_version>

For example, if *USERPROFILE* is C:\Users\psftuser and the PeopleTools version is 8.57, by default *PS_CFG_HOME* would be C:\Users\psftuser\psft\pt\8.57. The configuration and log files for the application server, process scheduler server, and search server are installed below this directory.

Note. The *PS_CFG_HOME* directory is associated with the *PS_HOME* from which it was originally generated. The DPK deployment process supports a single *PS_CFG_HOME* to be used for all domains for a given environment.

This server domain configuration allows for a more flexible installation. You also have the opportunity to place different security restrictions on the binary and configuration files. For installations using DPKs, use the Puppet customizations to change the *PS_CFG_HOME*.

Defining PS_CUST_HOME

The *PS_CUST_HOME* location holds customized file system objects (that is, objects you provide as opposed to being installed with the software).

Anything that is changed from the file system objects that are delivered with the PeopleSoft application installation should be placed here. The sub-directory structure must mirror the *PS_APP_HOME* upon which it is based. For example, when you install your PeopleSoft application, the directory structure includes SQR scripts in *PS_APP_HOME/sqr*. If you have customized SQR scripts, you would place them in *PS_CUST_HOME/sqr*.

To define a *PS_CUST_HOME* location, use the Puppet customizations.

Defining PIA_HOME

When you install the PeopleSoft Pure Internet Architecture, the files are installed in the *PIA_HOME* directory. The *PIA_HOME* location holds the webserv directory, and the files for the PeopleSoft Pure Internet Architecture installation. The directory where you install PeopleSoft Pure Internet Architecture, *PIA_HOME*, does not have to be the same as the location where you install PeopleSoft PeopleTools and the PeopleSoft application software, *PS_HOME*. You have the option to specify the installation location for the PeopleSoft Pure Internet Architecture by using the Puppet customizations.

The *PS_CFG_HOME* directory is created the first time that the PSADMIN utility starts. PSADMIN recognizes that *PS_CFG_HOME* is not present and creates it when necessary. This is done before any domains are created. When you invoke PeopleSoft Pure Internet Architecture, the installer checks your environment to determine the *PS_CFG_HOME*. If the environment variable *PS_CFG_HOME* is defined, the *PS_CFG_HOME* location is seen as the directory to which that environment variable points. If *PS_CFG_HOME* is not defined the default value is used.

See the product documentation for using the %V Meta variable in *PeopleTools: System and Server Administration* product documentation for more information about setting the *PS_CFG_HOME* environment variable.

Task 1-6-7: Defining the Web Server

A web server is required to run the PeopleSoft Pure Internet Architecture. The PeopleSoft Pure Internet Architecture is certified to work with the Oracle WebLogic Server J2EE web application servers (also commonly referred to as web servers)

Refer to the Certifications page on My Oracle Support for supported web server combinations.

To find support information for the HTTP servers that can be used as reverse proxy servers (RPS), see the Oracle WebLogic documentation, included with Oracle Fusion Middleware.

Oracle WebLogic and the supported reverse proxy server will provide out-of-the-box SSL support across all supported operating systems. Oracle WebLogic provided demo digital certificates, but for production grade SSL you must purchase digital certificates from a Certificate Authority supported by the web server that you are using (for example, Verisign, Baltimore, Entrust, and so on).

Task 1-7: Planning Database Creation

This section discusses:

- Understanding Database Creation
- Determining Databases and Database Names

- Defining DB2 for Linux, UNIX, and Windows, and PeopleSoft Databases

Understanding Database Creation

When performing a PeopleSoft installation, you will create these types of PeopleSoft databases:

- System (also called SYS) databases, which contain the PeopleSoft PeopleTools and product-specific metadata required for development of a production database.
- Demo (DMO) databases, which are populated with sample data for study, demonstration, or training purposes.

Note. If you are using the PeopleSoft Upgrade Source Image, you must create a Demo database.

Task 1-7-1: Determining Databases and Database Names

Before you begin the installation process, you should determine how many PeopleSoft databases (System or Demo) of which type you need and how you intend to use them. You should also determine the names of the databases at this point, using database names that:

- Are limited to eight characters, all UPPERCASE.
- Capture information about the PeopleSoft product line and the type of database.

For example, you may want to create two databases with the names PSHRDMO and PSHRSYS, using the two characters HR (for Human Resources) to indicate the product line.

Task 1-7-2: Defining DB2 for Linux, UNIX, and Windows, and PeopleSoft Databases

In this chapter we refer to both a DB2/LUW database and a PeopleSoft database. It is important to understand the difference.

- A DB2/LUW database is a set of SQL objects defined by one system catalog, using one instance of the DB2/LUW server executables and associated files. A DB2/LUW instance may have several databases.
- A PeopleSoft database is a set of SQL objects defined as having the same owner ID. These tables are always within a single DB2/LUW database. A PeopleSoft database includes the PeopleSoft objects and application data for one or more products in a PeopleSoft product line.

Each PeopleSoft database is created in a single DB2/LUW database. The database name is entered on the PeopleSoft logon screen. A suggested database name might be PPF80DMO (for an EPM demo database).

Note. Your database server should have sufficient space for the demo database. If you plan on substantially increasing the size of tables in your demo database, ensure that your file systems have ample space to accommodate growth.

Note. Starting with PeopleSoft PeopleTools 8.50, DB2/LUW installation (on supported UNIX operating systems, and Microsoft Windows) should configure and use a 64-bit DB2 instance.

Task 1-8: Planning Multilingual Strategy

This section discusses:

- Understanding Multilingual Issues
- Choosing a Base Language
- Selecting Additional Languages
- Selecting a Database Character Set

Understanding Multilingual Issues

Before beginning your installation, you should determine which languages your PeopleSoft system will need to support. If multiple languages are required, determine which language will be used most often. These decisions will affect tasks at various stages of the installation, including file server setup, database creation, and the ability to change the base language of the PeopleSoft database after it is created. Even if you do not plan on running your system in more than one language, you should decide the following information before completing this task:

- Database base language
- Additional languages (if any)
- Database character set (Unicode recommended)

The current languages provided by Oracle and their language codes are listed in the following table, as well as the corresponding database character sets for that language. These are the languages for which Oracle provides pre-translated products. If you plan to provide users access to your applications in these languages, Oracle recommends that you install the translations during your initial installation. This approach will keep you from having to perform an upgrade if you decide to add the Oracle-provided translations at a later date. After installation, you also have the option of performing your own translations, and adding additional languages.

In considering which languages to include, whether for pre-translated objects or for your own application development, keep in mind that certain languages require a Unicode database. Oracle recommends Unicode character sets rather than non-Unicode character sets, including Western European and Japanese Shift-JIS, for all installations and upgrades regardless of the languages used.

See [Selecting a Database Character Set](#).

Language Code	Language	Database Character Set
ARA	Arabic	Unicode only
CFR	Canadian French	Unicode recommended
CZE	Czech	Unicode only
DAN	Danish	Unicode recommended
DUT	Dutch	Unicode recommended
ENG	US English	Unicode recommended
FIN	Finnish	Unicode recommended
ESP	Spanish	Unicode recommended
FRA	French	Unicode recommended

Language Code	Language	Database Character Set
GER	German	Unicode recommended
HUN	Hungarian	Unicode only
ITA	Italian	Unicode recommended
JPN	Japanese	Unicode recommended
KOR	Korean	Unicode only
NOR	Norwegian	Unicode recommended
POL	Polish	Unicode only
POR	Portuguese	Unicode recommended
ROM	Romanian	Unicode only
RUS	Russian	Unicode only
SVE	Swedish	Unicode recommended
THA	Thai	Unicode only
TUR	Turkish	Unicode only
UKE	United Kingdom English	Unicode recommended
ZHS	Simplified Chinese	Unicode only
ZHT	Traditional Chinese	Unicode only


See Also

PeopleTools: Global Technology

Task 1-8-1: Choosing a Base Language

Each PeopleSoft database can have only one base language. PeopleSoft databases ship with English as the default base language. Typically, the base language of your database should match the language most commonly used by your organization, as it affects the performance of PeopleSoft applications.

When PeopleSoft PeopleTools attempts to open language-sensitive objects (such as pages and menus), it first compares the operator's preferred language to the base language of the database. If the preferred language matches the base language, PeopleSoft PeopleTools immediately loads the required definition from the base language PeopleSoft PeopleTools tables. However, if the user's preferred language differs from the database's base language, PeopleSoft PeopleTools must first query the related language tables for the object. Should a translation of the object not be found in the operator's preferred language, a query is then performed on the base language tables. The following process flow illustrates the selection of the language used for language-sensitive objects, beginning with the language selected when the user signs in to the PeopleSoft application:



Language selection process using the base language and the preferred language

While these queries typically occur very quickly, they still take up valuable processing time. To optimize performance you can set the base language of your database as the language that is used most often by your users. Another consideration is that because PeopleSoft databases are shipped with a base language of English, maintenance is simpler if English remains the base language. Both configurations are supported by Oracle.

Task 1-8-2: Selecting Additional Languages

Oracle provides translations of all end-user objects with the Global Multi-Language installation files. It is much easier to install additional languages upon initial database creation than to add them later in your implementation process, so we recommend that you choose which additional languages may be required now. There is no limit to the number of languages that can coexist in a single PeopleSoft database; however, remember that each language will require additional storage space, primarily for PeopleSoft PeopleTools objects.

Task 1-8-3: Selecting a Database Character Set

This section discusses:

- Understanding Character Sets
- Using Unicode Databases

Understanding Character Sets

Oracle recommends Unicode, but also supports non-Unicode (legacy) code sets, in PeopleSoft databases.

The following table lists a selection of the code sets, code pages, and languages that the PeopleSoft software supports for DB2 for Linux, UNIX, and Windows:

Code Set	Code Page	Languages Supported
1208	UTF-8	All languages
1252	1252	Western European languages
ISO8859-1	819	Western European languages
ISO8859-15	923	Western European languages

See *PeopleTools: Global Technology*, "Selecting and Configuring Character Sets."

Using Unicode Databases

Unicode databases are required if the languages that you selected do not share the same character set. Typically, a single character set can encode all languages written in a single script. For example, English, French, and Spanish all share the same script (Latin), so they can coexist in a non-Unicode database. However, Japanese does not share the same script as French, so if you need to have Japanese and French coexist in a single system, you need a Unicode database.

If you decide to use Unicode for your database, you do not need to select a character set.

See Understanding Multilingual Issues.

See Understanding Character Sets.

Task 1-9: Creating PeopleSoft User IDs

This section discusses:

- Understanding PeopleSoft User ID Creation
- Prerequisite
- Creating UNIX User IDs
- Creating Windows User IDs

Understanding PeopleSoft User ID Creation

In this task you will create the user IDs required for installation.

Note. The term *user ID* refers to the UNIX or Windows user name, not the UNIX or Windows user ID.

Prerequisite

The following procedure assumes the team member performing these steps has understanding of the tools required to create the described UNIX and Microsoft Windows entities.

Task 1-9-1: Creating UNIX User IDs

This procedure lists required steps in the creation of the PeopleSoft-required UNIX User IDs.

To create UNIX IDs:

1. Create a UNIX group for the DB2/LUW instance owner.

This group ID will be the primary group of the UNIX ID for the DB2/LUW instance owner. The recommended group ID name is db2adm1.

Note. Any UNIX ID that belongs to this group will inherit System Administration authority (SYSADM) for the given DB2/LUW instance. Therefore, take extra care when you place a UNIX ID under this group.

2. Create a UNIX ID for the DB2/LUW for UNIX instance owner.

This ID will be used in the next task to create an instance. The group ID for this user should be the same as the one created in the previous step. We suggest that you name this ID db2udbx, where the final x might be set to *d* for development or *p* for production. IBM restrictions on names apply (for example, you cannot use names beginning with SYS).

3. Create a UNIX ID for the PeopleSoft access ID/table owner ID.

The access ID, which is also known as the table owner ID, will be granted DBADM authority by the Data Mover import script that will be run in the chapter concerning creating a database. The access ID and access password must be tightly controlled. Both are encrypted in the PeopleSoft database. The access ID cannot be more than eight characters long. The group ID for this user can be the same as the one created in step 1 or a completely different group ID. However, making this group ID the same as the one in step 1 will implicitly grant this UNIX ID the SYSADM authority.

Refer to your database platform documentation for information about access ID and password length requirements, and work with your database administrator to set the password. In addition to the database

platform restrictions, the following requirements are set for access ID passwords by the PeopleSoft system:

- The first character must be *only* a letter.
- Every other character must be *only* a letter, number, underbar (_), pound sign (#) or dollar sign (\$).
- The maximum length is 30. Excess characters will be truncated and the remaining value will be assigned for the password.
- The minimum length (though not recommended) is 1.

Warning! A short password is not recommended. Oracle recommends 8 or more characters for password security.

4. Create a UNIX ID for the PeopleSoft connect ID.

The connect ID will be used by PeopleSoft to connect to the database. The Data Mover script generated by Database Setup grants this user minimal database privileges. Set the group, environment variables, and permissions to enable this UNIX ID to access the DB2/LUW database. This ID cannot be more than eight characters long. The password for the connect ID cannot be more than 30 characters long or contain any percent characters (%). The group ID for user should not be the same as the one created in step 1. This UNIX ID should have minimal authority and no SYSADM privilege.

5. Create another separate group ID and UNIX ID for the DB2/LUW Fenced User.

This fenced group ID and UNIX ID are to be used by DB2/LUW for fenced User Defined function (UDF) and stored procedures. Although PeopleSoft does not use the fenced ID, the fenced ID is required for DB2/LUW instance creation. The recommended group ID and username for this UNIX ID are db2fadm1 and db2fenc1 respectively.

See Also

"Creating a Database"

IBM DB2 UDB for Linux, UNIX, and Windows administration guide

IBM DB2 UDB for Linux, UNIX, and Windows installations manual

Task 1-9-2: Creating Windows User IDs

This procedure lists required steps in the creation of the PeopleSoft-required Microsoft Windows user IDs.

To create Microsoft Windows IDs:

1. Create a USER ID for the DB2/LUW Instance Owner.

Note. For Microsoft Windows, DB2/LUW requires that users have Administrative Authority on the Windows machine to install the DB2/LUW for Windows. A DB2/LUW Administrator ID is required, which must have Local Administrator authority to set up the DB2/LUW Catalog information and the ODBC Data Source Administration. In addition, the DB2/LUW Administrator User ID has to be eight characters or less; as in "db2admin." The password also must be eight characters or less.

2. Create a user ID for the PeopleSoft access ID/table owner ID.

The access ID, which is also known as the table owner ID, will be granted DBADM authority by the Data Mover import script that will be run during database creation. The access ID and access password must be tightly controlled. Both are encrypted in the PeopleSoft database.

Refer to your database platform documentation for information about access ID and password length requirements, and work with your database administrator to set the password. In addition to the database

platform restrictions, the following requirements are set for access ID passwords by the PeopleSoft system:

- The first character must be *only* a letter.
- Every other character must be *only* a letter, number, underbar (_), pound sign (#) or dollar sign (\$).
- The maximum length is 30. Excess characters will be truncated and the remaining value will be assigned for the password.
- The minimum length (though not recommended) is 1.

Warning! A short password is not recommended. Oracle recommends 8 or more characters for password security.

3. Create a user ID for the PeopleSoft connect ID.

The connect ID will be used by PeopleSoft to connect to the database. The Data Mover script generated by Database Setup grants this user minimal database privileges.

Note. You must limit the access ID and connect ID to eight characters or less, and the passwords for each to 30 characters or less. In addition, the connect ID password should not contain any forward-slash characters (/).

Task 1-10: Installing the Database Engine

To install the database engine:

1. If you have not already done so, install the DB2/LUW database engine on your database server.
2. Create an instance if one does not already exist.

Create an instance of the database engine. On UNIX, the name of the instance matches the name of the user ID corresponding to the DB2/LUW Instance Owner ID that you created in the previous task, such as "db2udb1". On Microsoft Windows, the default instance name is DB2.

For connectivity between the DB2/LUW database and clients or utilities running on other systems, install a supported version of DB2 Connect or DB2 Client.

Beginning with PeopleSoft PeopleTools 8.53, the 64-bit version of DB2 Connect or DB2 Client is required on Microsoft Windows.

See Also

IBM DB2 UDB for Linux, UNIX, and Windows installations manual

IBM DB2 UDB for Linux, UNIX, and Windows administration manual

My Oracle Support, Certifications

Task 1-11: Configuring DB2 UDB for Linux, UNIX, and Windows for Remote Client Access

The following procedure outlines the steps to configure DB2/LUW for access by clients running on systems other than the UNIX system hosting DB2.

To configure DB2/LUW for remote client access:

1. Set up the DB2 Communication Protocol.

Verify that the communication protocol for the DB2/LUW server is set to TCP/IP by typing the following from the UNIX prompt:

```
/home/db2udb1 >db2set -all
[i] DB2COMM=tcpip
[g] DB2SYSTEM=rt-ibm08
[g] DB2ADMINSERVER=db2as
```

If the DB2COMM environment variable is not defined, define this variable by issuing:

```
db2set DB2COMM=tcpip
```

2. Include the DB2 Runtime Client Library Path.

Ensure that the environment variable for the runtime client library path is properly set for the UNIX or Linux ID by editing the appropriate profile file to include ~/sqllib/lib. The environment variable depends upon the operating system, as described in this table:

Operating System	Environment Variable
IBM AIX	LIBPATH
HP-UX Itanium	LD_LIBRARY_PATH
Linux and Oracle Solaris	LD_LIBRARY_PATH

The profile file depends upon the UNIX shell you are using. These examples show how to set the LIBPATH environment variable for an IBM AIX operating system. For other operating systems, use the correct environment variable.

- If the default shell for the UNIX ID is Bourne Shell or Korn Shell, add the following lines in the file ~/sqllib/db2profile:

```
LIBPATH=${LIBPATH}:${INSTHOME}/sqllib/lib
export LIBPATH
```

- If the default shell is C Shell, add the following line in the file ~/sqllib/db2cshrc:

```
set LIBPATH=($LIBPATH ${INSTHOME}/sqllib/lib)
```

3. Edit the /etc/services file to add a service name entry pair for DB2/LUW.

On UNIX, the services file is under /etc/services. On Microsoft Windows, it is under C:\WINDOWS\system32\drivers\etc.

```
db2cdb2udb1 50000/tcp      # DB2 UDB Runtime Client
db2idb2udb1 50001/tcp      # DB2 UDB Runtime Client interrupt
```

The service names (db2cdb2udb1 and db2idb2udb1) are user-defined values. Additional suggestions include db2udbp and db2udbpi, where "p" stands for "production." You must define a unique pair of service names for each instance created per machine.

Port numbers (50000 and 50001 above) may be arbitrarily assigned. That is, you could use 50000 and 50001 or any other pair of sequential unassigned numbers greater than 1024. However, port numbers usually follow installation or industry protocols, so consult with your network administrators.

4. Update Database Manager SVCENAME Parameter on the DB2/LUW Server.

To establish the service name that clients will use to communicate with DB2/LUW, issue the following command using the DB2/LUW Command Line Processor:


```
db2 update dbm cfg using svcename db2cdb2udb1
```

Note. Although a port number and a service name were assigned for the Interrupt port (for example, db2idb2udb1), it is never used.

To put the above changes into effect, you have to re-login and re-start the DB2/LUW database instance. Here are the commands:

```
login db2udb1
db2stop
db2start
```

Task 1-12: Installing Supporting Applications

Oracle requires that a number of supporting applications be installed for the PeopleSoft installation on batch servers and on any Windows-based client on which batch processes will be run locally. (Throughout the rest of this section we refer to these Windows-based clients as *two-tier clients*.) Be sure to check My Oracle Support, Certifications to ensure that you are installing software versions that are certified by Oracle.

COBOL

- Consult the PeopleSoft information on My Oracle Support to verify whether your application requires COBOL. Remember that COBOL is not needed for PeopleSoft PeopleTools or for applications that do not contain COBOL programs.
See PeopleSoft Enterprise Frequently Asked Questions about PeopleSoft and COBOL Compilers, My Oracle Support, (search for the article name).
See PeopleSoft Enterprise Frequently Asked Questions about PeopleSoft and the IBM COBOL Compiler, My Oracle Support, (search for the article name).
- For PeopleSoft applications written in COBOL, install the appropriate version of the COBOL compiler on the server where you will compile.
See "Installing and Compiling COBOL on Windows."
See "Installing and Compiling COBOL on UNIX."
 - For UNIX servers, install Micro Focus Server Express or IBM Compiler for IBM AIX.
 - For Microsoft Windows servers, install the appropriate version of Micro Focus Net Express.
- If all your servers are on Microsoft Windows operating systems, Oracle recommends that you install a COBOL compiler on the file server.
You can install PeopleSoft PeopleTools plus any patches on the file server, compile your COBOL there, and then copy the COBOL binaries to your application and batch servers.
- If your application and batch servers are on UNIX, we recommend that you designate a single server as the compile server, so that you can compile COBOL from this central location and then distribute it to the rest of your application and batch servers.

If you use this approach, you only need to copy patches or customizations over to the compile server. In this case, you would install a COBOL compiler on the master (or compile) server and either the COBOL compiler or runtime on the rest. You can also copy patches or customizations from the file server to all of your UNIX servers and compile the COBOL on each machine.

Note that the compile server must have the same operating system as any destination application or batch servers. For example, if your compile server is an IBM AIX machine, you can only copy COBOL compiled there to other IBM AIX application and batch servers. Oracle recommends this approach. It will help you keep

your COBOL source code in sync and only requires that you install COBOL in a single location.

- The format of COBOL source file names of patches or customizations on the file server should always be UPPERCASE.cbl to ensure compatibility with your UNIX servers.

SQR

- You must install SQR on any non-Windows batch server.
- On Microsoft Windows batch servers and two-tier clients, you have the option of installing SQR locally, or mapping to a copy installed on the file server.
- Because SQR does not require any local registry settings, you can execute SQR from any Microsoft Windows batch server or two-tier client once SQR has been installed to a shared directory. Installing SQR locally will result in improved performance; over a slow network connection the improvement will be significant.

Microsoft Office

Install Microsoft Office (Excel and Word) on any Windows batch server or two-tier client that will be running PS/nVision or Microsoft Word batch processes.

Microsoft Office must be installed locally, because it requires registry settings.

See Also

My Oracle Support, Certifications

Task 1-13: Performing Backups

Before proceeding, you should back up all servers and workstations that are set up for installation so you can recover to this point if necessary. Do the following:

- Back up any changes you made to the database server in setting up your PeopleSoft system.
- Back up any changes you made to your file server while setting aside space for your PeopleSoft system and setting up access privileges.
- Once you set up your install workstations to access the file server and database server simultaneously, back up the workstations.

Chapter 2

Installing the PeopleSoft Homes

This chapter discusses:

- Obtaining the PeopleSoft Application Images and PeopleTools DPKs
- Obtaining the PeopleSoft Upgrade Source Images
- Reviewing the DPK Setup Script Options
- Deploying as a Non-Root User on Linux, AIX, HP-UX, or Solaris
- Running the DPK Setup Script to Install PS_HOME and PS_APP_HOME
- Running the DPK Setup Script to Install All Software
- Obtaining Operating System Packages Required by Puppet
- Removing a Deployed PeopleSoft Environment

Task 2-1: Obtaining the PeopleSoft Application Images and PeopleTools DPKs

If you have not already done so, this section describes how to locate and obtain the PeopleSoft Application Images and PeopleTools DPKs required for a fresh installation.

The PeopleSoft Application Images and PeopleTools DPKs are available on My Oracle Support. Contact Oracle if you need a user ID and password for My Oracle Support.

1. Go to the PeopleSoft Update Manager Home Page, My Oracle Support, Doc ID 1641843.2, to find the information on locating and downloading the current PeopleSoft Application Image.

Note. On the PeopleSoft Update Manager Home Page, the term PeopleSoft Update Image (PI) is used for the images.

2. Select the tab PeopleSoft Update Image Home Pages, and select the link for your PeopleSoft application.
3. Expand the Update Image Link section, and then select the link for Native OS to find the details for the current PeopleSoft Application Image for Microsoft Windows and Linux.
4. In the Update Image Link table on the PeopleSoft Update Image Home Page, download or open the Update Image Manifest, and note the following:
 - The PeopleTools patch release in the Software Version Included column.
 - The file name for Application DPK Zip 1, normally *FILENAME_9of11.zip*.
5. To obtain the PeopleTools DPK, in My Oracle Support, select the Patches & Updates tab.
6. Select Product or Family (Advanced).
7. Specify the following information, and then click Search:
 - PeopleSoft Enterprise PT PeopleTools as the Product

- The current PeopleSoft PeopleTools 8.5x release, such as 8.57, as the Release
 - Your operating system, IBM AIX, HP-UX for Itanium, Linux, Microsoft Windows, or Oracle Solaris on SPARC, as the Platform
8. On the search results page, locate the PeopleTools patch corresponding to the patch release that you noted in step 4, and download the DPKs into a single directory, referred to in this documentation as *DPK_INSTALL*.

Note. You can also find links to the most recent PeopleTools patches on the PeopleSoft PeopleTools Patches Home Page, My Oracle Support, Doc ID 2062712.2.

9. To obtain the PeopleSoft Application DPK Zip1, return to the PeopleSoft Update Image Home Page, and in the Update Image Links table, select the link in the column *<Product> Update Image Link*.
10. From the patch page, download the zip file for Application DPK Zip 1 to the same *DPK_INSTALL* directory as in step 8.

For PeopleSoft installations on AIX, HP-UX, Linux, or Solaris, download the PeopleSoft Application DPK for Linux. Do not unzip the file at this point. If you download to a Microsoft Windows computer and FTP to your AIX, HP-UX, Linux, or Solaris computer, FTP in binary mode.

The first Application DPK Zip 1 includes the content needed for the PeopleSoft application, *PS_APP_HOME*. The other Application DPK files are not needed for this installation.

See "Preparing for Installation," Understanding the PeopleSoft Installation to review a list of the contents of the DPKs and file name syntax.

Task 2-2: Obtaining the PeopleSoft Upgrade Source Images

If you have not already done so, this section describes how to locate and obtain the Upgrade Source Images from My Oracle Support. Contact Oracle if you need a user ID and password for My Oracle Support.

1. Go to the upgrade home page for your PeopleSoft application, and select the tab *<Product> Upgrade Source Images*.
2. In the Upgrade Source Image Link and Manifest table, locate the row for Native OS for Microsoft Windows and or Native OS for Linux.
3. Download or open the software manifest, and note the following:
 - The PeopleTools patch release in the Software Version Included column.
 - The file name for Application DPK Zip 1, normally *FILENAME_7of9.zip*.
4. To obtain the PeopleTools DPK, in My Oracle Support, select the Patches & Updates tab.
5. Select Product or Family (Advanced).
6. Specify the following information, and then click Search:
 - PeopleSoft Enterprise PT PeopleTools as the Product
 - The current PeopleSoft PeopleTools 8.5x release, such as 8.57, as the Release
 - Your operating system, IBM AIX, HP-UX, Linux, Microsoft Windows, or Oracle Solaris on SPARC, as the Platform
7. On the search results page, locate the PeopleTools patch corresponding to the patch release that you noted in step 4, and download the DPKs into a single directory, referred to in this documentation as *DPK_INSTALL*.

Note. You can also find links to the most recent PeopleTools patches on the PeopleSoft PeopleTools Patches Home Page, My Oracle Support, Doc ID 2062712.2.

8. To obtain the PeopleSoft Application DPK, return to the PeopleSoft Upgrade Source Image page, and in the table, select the link in the column Link to Upgrade Source Image.
9. From the patch page, download the zip file for Application DPK Zip 1 to the same *DPK_INSTALL* directory as in step 8.

For PeopleSoft installations on AIX, Linux, or Solaris, download the PeopleSoft Application DPK for Linux. Do not unzip the file at this point. If you download to a Microsoft Windows computer and FTP to your AIX, HP-UX, Linux, or Solaris computer, FTP in binary mode.

The first Application DPK Zip 1 includes the content needed for the PeopleSoft application, *PS_APP_HOME*. The other Application DPK files are not needed for this installation.

See "Preparing for Installation," Understanding the PeopleSoft Installation Using Deployment Packages to review a list of the contents of the DPKs and file name syntax.

Task 2-3: Reviewing the DPK Setup Script Options

This section discusses:

- Using the DPK Setup Script Options
- Preparing to Run the DPK Setup Script

Task 2-3-1: Using the DPK Setup Script Options

The PeopleSoft PeopleTools DPK setup script alleviates the installation process by automating most of the manual tasks on a virtual or bare-metal host running a supported operating system. By convention, the setup DPK is the first zip file (*FILENAME_1ofn.zip*) in the group of PeopleSoft DPK zip files you download from My Oracle Support.

The DPK setup zip file includes two scripts, a Microsoft Windows script (*psft-dpk-setup.bat*) and a shell script for Linux, AIX, HP-UX, or Solaris (*psft-dpk-setup.sh*). To set up a PeopleSoft environment, run the script pertinent to the host operating system (OS) platform on which the DPK setup script is invoked. The DPK setup script offers a variety of options for setting up mid-tier components, *PS_HOME* folder, and PeopleSoft domains, depending upon the options you supply. The script is an interactive script that detects the downloaded DPKs and verifies that they are correct. It also prompts the user for input, and once that information is gathered, will set up a complete functional PeopleSoft mid-tier environment connecting to an existing PeopleSoft database.

Note. The DPK setup script does not provide any default passwords. It is a good idea to be prepared to supply passwords such as user ID, PeopleSoft Connect ID, Application Server Domain Connection, and so on.

The following table lists the options available for the DPK setup script, *psft-dpk-setup.bat* for Microsoft Windows and *psft-dpk-setup.sh* for Linux, AIX, HP-UX, or Solaris. The suffix *<ext>* in the table refers to the operating system specific extension.

See the section Preparing to Deploy with a Non-Root User for additional script options.

Note that the command options require two dashes when running on Microsoft Windows, Linux, AIX, HP-UX, or Solaris.

Note. The commands in the table include line feeds to improve readability.

Deployment	DPK Setup Script Command
<p>Perform the following:</p> <ul style="list-style-type: none"> Install the software required for the mid-tier components, including Oracle Tuxedo, Oracle WebLogic, and Oracle database client. Deploy and set up the domains for the mid-tier components (Application Server, web server, Process Scheduler and Oracle database client). <p>The deployment sets up one each of Application Server, web server, and Process Scheduler domains.</p> <ul style="list-style-type: none"> Install the <i>PS_HOME</i> directory. 	<pre>psft-dpk-setup.<ext> --env_type midtier or psft-dpk-setup.<ext> --env_type midtier --domain_type all</pre>
<p>Perform the following:</p> <ul style="list-style-type: none"> Install the software required for the mid-tier components, including Oracle Tuxedo, Oracle WebLogic and Oracle database client, without setting up the mid-tier domains. Install the <i>PS_HOME</i> directory. <p>*There is additional information following this table.</p>	<pre>psft-dpk-setup.<ext> --env_type midtier --deploy_only or psft-dpk-setup.<ext> --env_type midtier --deploy_only --deploy_type all</pre>
<p>Deploy the <i>PS_HOME</i> directory only.</p> <p>This option does not set up any domains.</p> <p>*There is additional information following this table.</p>	<pre>psft-dpk-setup.<ext> --env_type midtier --deploy_only --deploy_type tools_home</pre>
<p>Deploy and set up the domain for the Application Server only.</p>	<pre>psft-dpk-setup.<ext> --env_type midtier --domain_type appserver</pre>
<p>Deploy and set up the domain for the Process Scheduler only.</p>	<pre>psft-dpk-setup.<ext> --env_type midtier --domain_type prcs</pre>
<p>Deploy and set up the domain for PIA only.</p> <p>Note. Before beginning the PIA domain deployment, ensure that application server and Process Scheduler domains are available.</p>	<pre>psft-dpk-setup.<ext> --env_type midtier --domain_type pia</pre>
<p>Deploy and set up the domains for the Application Server and the Process Scheduler.</p>	<pre>psft-dpk-setup.<ext> --env_type midtier --domain_type appbatch</pre>
<p>Deploy the <i>PS_APP_HOME</i> directory only.</p> <p>This option does not set up any domains.</p> <p>*There is additional information following this table.</p>	<pre>psft-dpk-setup.<ext> --env_type midtier --deploy_only --deploy_type app_home</pre>

Deployment	DPK Setup Script Command
Deploy the <i>PS_HOME</i> and <i>PS_APP_HOME</i> directories only. This option does not set up any domains. *There is additional information following this table.	<code>psft-dpk-setup.<ext></code> <code>--env_type midtier</code> <code>--deploy_only</code> <code>--deploy_type app_and_tools_home</code>
Specify the full path of the downloaded DPKs. The script assumes that the downloaded DPKs are in the parent directory of the DPK setup script. If the DPKs are located in a different directory, use this option.	<code>psft-dpk-setup.<ext></code> <code>--env_type midtier</code> <code>--dpk_src_dir <full_DPK_path></code>
Remove a deployed environment. See "Using and Maintaining the PeopleSoft Environment," Removing a Deployed PeopleSoft Environment.	<code>psft-dpk-setup.<ext></code> <code>--cleanup</code>
List the DPK setup script usage.	<code>psft-dpk-setup.<ext></code> <code>--help</code>

* When you use the `--deploy_only` options on Linux, AIX, HP-UX, or Solaris operating systems, the deployment does not set environment variables needed for subsequent tasks. After the deployment is complete, you can set the environment variables using one of these methods:

- Change directory to *BASE_DIR*/pt/ps_home8.57.xx and run `./psconfig.sh`.
- Run the following command:

```
<PUPPET_DIR>/puppet apply --confdir=<BASE_DIR>/dpk/puppet
-e "include ::pt_profile::pt_psft_environment" --debug --trace
--detailed-exitcodes
--logdest <DPK_INSTALL>/<log_file_name>
```

For Linux, *PUPPET_DIR* is /opt/puppetlabs/bin. For AIX, HP-UX or Solaris, *PUPPET_DIR* is /opt/oracle/puppetlabs/bin.

Note. The command text given here includes line feeds for readability.

Task 2-3-2: Preparing to Run the DPK Setup Script

Include the following decisions in preparing to install with the DPK setup script:

- On Linux, AIX, HP-UX, or Solaris, you have the option to deploy the PeopleSoft environment as a non-root user.

See Preparing to Run the DPK Setup Script as a Non-Root User on Linux, AIX, HP-UX, or Solaris

- FRESH or PUM installation type

For this documentation, select a FRESH, or new installation, which enables you to make selections for RDBMS, Unicode, and multi-language support.

The PUM installation type is used with the PeopleSoft Update Image DPKs to create and set up a PeopleSoft environment to be used as the source for the PeopleSoft Update Manager. If you select the PUM installation type, the DPK setup script installs an Oracle DEMO multi-lingual database without presenting you with other options.

See the documentation on the PeopleSoft Update Manager (PUM) Home Page, My Oracle Support, Doc ID 1641843.2.

Note. If you are using the PeopleSoft Upgrade Source DPKs to set up an environment for the Upgrade Source database, you do not see the prompt for FRESH or PUM installation type.

- Default or manual configuration

After extracting the DPKs, you are given the option to exit the process, create a customization file, and complete the configuration manually using the Puppet apply command with a user-written customization file. Use the manual configuration if you want to change installation locations and so on.

See "Completing the DPK Initialization with Customizations."

The following installation scenarios require manual configuration using the customizations:

- Installing on an AIX operating system

See Reviewing the Software Requirements on AIX

See Preparing the Customization File for JDK on AIX.

- Installing on HP-UX operating system.

See Reviewing the Software Requirements on HP-UX.

See Preparing the Customization File for JDK on HP-UX.

- Connecting to a non-Oracle RDBMS platform

See Preparing the Customization File for Mid-Tier Connection to a DB2 for Linux, UNIX, and Windows Database

- User IDs and password

The DPK setup script does not provide any default passwords. It is a good idea to be prepared to supply passwords such as user ID, PeopleSoft Connect ID, Application Server Domain Connection, and so on.

- Multi-language support

You are given the option to use the DPK setup script to deploy translated files to *PS_APP_HOME* for a multi-language installation.

- Unicode or non-Unicode

While running the DPK setup script, you can choose to install a Unicode or non-Unicode environment.

Alternatively, specify Unicode using the customizations and Puppet apply command.

See "Completing the DPK Initialization with Customizations," Preparing the Customization File for Unicode.

- Specifying *PS_CUST_HOME*

You may wish to set up a *PS_CUST_HOME* (PeopleSoft Customization Home) directory in your environment to store your site's customized files, separate from *PS_HOME* and *PS_APP_HOME*.

If you wish to use a *PS_CUST_HOME* for your environment, use the following steps:

1. Before running the DPK setup script, manually create the directory structure to use as *PS_CUST_HOME*.
See *PeopleTools: System and Server Administration*, "Working with *PS_CUST_HOME*."
2. Set the *PS_CUST_HOME* environment variable.
3. When you run the DPK setup script, the setup process uses the *PS_CUST_HOME* environment variable for setting up the PeopleSoft domains.

Task 2-4: Deploying as a Non-Root User on Linux, AIX, HP-UX, or Solaris

This section discusses:

- Preparing to Run the DPK Setup Script as a Non-Root User on Linux, AIX, HP-UX, or Solaris
- Running the DPK Setup Prerequisite for Linux, AIX, HP-UX, or Solaris
- Running the DPK Setup Script as a Non-Root User on Linux, AIX, HP-UX, or Solaris

Preparing to Run the DPK Setup Script as a Non-Root User on Linux, AIX, HP-UX, or Solaris

Review the information in this section before deploying on Linux, AIX, HP-UX, or Solaris. You have the option of downloading the DPK zip files and deploying the PeopleSoft environment as a non-root user. The non-root user owns all of the deployed environment, including *PS_HOME* and *PS_CFG_HOME*.

To run the DPK setup script as a non-root user, fulfill the following requirements:

- You can use an existing non-root user account. It is not necessary to create a new user.
- The deployment supports only a single non-root user who deploys into a single *BASE_DIR*.
- The non-root user's home directory must be writable.
- The non-root user must be configured to use the Bash, Bourne, or Korn shell.
- The non-root user must have permission to read and execute the *DPK_INSTALL* folder and its contents, including the downloaded zip files, and *DPK_INSTALL/setup*.

If the root user downloads the DPK zip files and saves them in *DPK_INSTALL*, the root user must ensure that the necessary permissions are granted to allow the non-root user to read and execute the files.

- Before a non-root user deploys the PeopleSoft environment, the root user must perform a prerequisite task.

Note. The log files for the non-root deployment are saved in *<USER_HOME>/psft_dpk_work/psft_dpk_setup_<PID>.log*, where *<USER_HOME>* is the home directory for the user running the script, and *<PID>* is a process ID. For example, if the home directory for the root user is */root*, when the root user runs the step *./psft-dpk-setup.sh --prereq* the log file is saved in */root/psft_dpk_work/psft_dpk_setup_1234.log*. If the home directory for the non-root user is */home/psft_user*, the log file when the non-root user runs *./psft-dpk-setup.sh --midtier* is */home/psft_user/psft_dpk_work_5678.log*.

The following table lists the high-level steps required to deploy a PeopleSoft environment by a non-root user, with a root user performing a prerequisite. The table uses a mid-tier deployment as an example, but the process also applies to other deployments, such as deploying full-tier, or deploying PeopleSoft domains only, and so on.

Note. The commands in the table include line feeds to improve readability.

Step Number	Reference	Comment
1. Obtain DPKs and extract the first zip file.	Obtaining the PeopleSoft PeopleTools DPKs	NA

Step Number	Reference	Comment
2. Select one of these commands to run. <ul style="list-style-type: none"> To install Puppet only: <code>./psft-dpk-setup.sh --prereq</code> To install Puppet and set system configuration parameters: <code>./psft-dpk-setup.sh --prereq --syscfg</code> 	Running the DPK Setup Prerequisite for Linux, AIX, HP-UX, or Solaris	Important! This step must be run by the root user. This action is required once for each host.
3. Run the DPK setup script; for example: <code>./psft-dpk-setup.sh --env_type midtier</code>	Running the DPK Setup Script as a Non-Root User on Linux, AIX, HP-UX, or Solaris	For other deployment options, see the table in the section Using the DPK Setup Script Options.
4. Run the command: <code>./psft-dpk-setup.sh --cleanup</code>	"Using and Maintaining the PeopleSoft Environment," Using the DPK Setup Script to Remove the PeopleSoft Environment on Linux, AIX, HP-UX, or Solaris as a Non-Root User	Run cleanup of the environment (optional).
5. Source the script to set environment variables: <code>source \$BASE_DIR/pt⇒/psft_env.sh</code>	"Using and Maintaining the PeopleSoft Environment," Setting Environment Variables for the Non-Root User on Linux, AIX, HP-UX, or Solaris	Before using PeopleSoft utilities and programs, source the script to set the required environment variables.

Task 2-4-1: Running the DPK Setup Prerequisite for Linux, AIX, HP-UX, or Solaris

This section discusses:

- Understanding the DPK Setup Prerequisite
- Running the DPK Setup Prerequisite to Install Puppet and Set the System Configuration
- Running the DPK Setup Prerequisite to Install Puppet

Understanding the DPK Setup Prerequisite

Before a non-root user can install the PeopleSoft environment, the root user must first run the DPK setup script to install the Puppet software to the standard location required by the DPK setup, and optionally perform system configuration. This prerequisite step is required only once for each host.

- To install the Puppet software and update the system configuration on the host, use the DPK setup script command `./psft-dpk-setup.sh --prereq --syscfg`.

This command installs the required Puppet software to the standard location. It also sets system configuration variables such as kernel parameters, user and group ulimits.

- To install only the Puppet software, use the DPK setup script command `./psft-dpk-setup.sh --prereq`.

Use this command if you do not want to update the system configuration variables on your host.

Running the DPK Setup Prerequisite to Install Puppet and Set the System Configuration

To run the DPK setup script prerequisite step:

1. Open a terminal window as a user with root access, and extract the first zip file (*FILENAME_1ofn.zip*). The extraction creates the *DPK_INSTALL/setup* folder and other files.

Note. It is a good idea to extract into the same directory where you downloaded the zip files, *DPK_INSTALL*.

2. Change directory to *DPK_INSTALL/setup*.
3. Run the script as follows:

```
./psft-dpk-setup.sh --prereq --syscfg
```
4. After the script completes the Puppet software installation, log out and log in as a non-root user to deploy the PeopleSoft environment.

Running the DPK Setup Prerequisite to Install Puppet

To install Puppet without performing system configuration:

1. Open a terminal window as a user with root access, and extract the first zip file (*FILENAME_1ofn.zip*). The extraction creates the *DPK_INSTALL/setup* folder and other files.

Note. It is a good idea to extract into the same directory where you downloaded the zip files, *DPK_INSTALL*.

2. Change directory to *DPK_INSTALL/setup*.
3. Run the script as follows:

```
./psft-dpk-setup.sh --prereq
```

The DPK setup log is written to the file *<ROOT_HOME>/psft_dpk_work/psft_dpk_setup_<PID>.log*, where *<ROOT_HOME>* is the home directory for the root user running the script, and *<PID>* is a process ID.

4. After the script completes the Puppet software installation, log out and log in as a non-root user to deploy the PeopleSoft environment.

Task 2-4-2: Running the DPK Setup Script as a Non-Root User on Linux, AIX, HP-UX, or Solaris

After the root user completes the prerequisite, start a terminal session as a non-root user and run the DPK setup script with the appropriate options. The following items are specific to the process when run by a non-root user.

See Reviewing the DPK Setup Script Options.

- The DPK setup script includes a prompt for *PS_CFG_HOME*.
 The script validates whether the specified *PS_CFG_HOME* location is writable and has 10 GB free space.
- More than one non-root user can run the DPK setup script from the same *DPK_INSTALL/setup*.
- The non-root user must have permission to read and execute the *DPK_INSTALL* folder and its contents,

including the downloaded zip files, and *DPK_INSTALL/setup*.

If the root user downloads the DPK zip files and saves them in *DPK_INSTALL*, the root user must ensure that the necessary permissions are granted to allow the non-root user to read and execute the files.

- The DPK setup log is written to the file *<USER_HOME>/psft_dpk_work/psft_dpk_setup_<PID>.log*, where *<USER_HOME>* is the home directory for the user running the script, and *<PID>* is a process ID.

Task 2-5: Running the DPK Setup Script to Install PS_HOME and PS_APP_HOME

This section discusses:

- Understanding the PS_HOME and PS_APP_HOME Installation
- Installing PS_HOME and PS_APP_HOME on Microsoft Windows
- Installing PS_HOME and PS_APP_HOME on Linux, AIX, HP-UX, or Solaris as the Root User
- Installing PS_HOME and PS_APP_HOME on Linux, AIX, HP-UX, or Solaris as a Non-Root User
- Reviewing the Deployment Results

Understanding the PS_HOME and PS_APP_HOME Installation

Use the DPK setup script to install the PeopleSoft PeopleTools software in *PS_HOME* and the PeopleSoft application software in *PS_APP_HOME*, using the `--deploy_only --deploy_type app_and_tools_home` option. This deployment requires the presence of PeopleSoft application DPKs in the deployment folder, *DPK_INSTALL*.

Note. You can also use the DPK setup script to deploy *PS_HOME* or *PS_APP_HOME* individually. See *Reviewing the DPK Setup Script Options*.

This procedure assumes that you have downloaded all of the required PeopleSoft Application Image DPKs for Linux or Microsoft Windows, and saved them in a location referred to here as *DPK_INSTALL*.

Task 2-5-1: Installing PS_HOME and PS_APP_HOME on Microsoft Windows

To use the DPK setup script for deployment only:

1. Extract the first zip file (*FILENAME_1ofn.zip*).

Note. It is a good idea to extract into the same directory where you downloaded the zip files, *DPK_INSTALL*.

The extraction creates the *DPK_INSTALL/setup* folder and other files.

2. Open a command prompt with Run as Administrator.
3. Change directory to *DPK_INSTALL/setup*.
4. Run the script with the options for deployment only.

Note. If you see an error message similar to "The application has failed to start because its side-by-side configuration is incorrect," it indicates that your machine does not include the necessary Microsoft C++ runtime libraries. Go to the Microsoft Web site, locate the Microsoft Visual C++ redistributable package for your system, and install as directed.

- If you extracted the first zip file into the same directory where you downloaded the zip files, use this command:

```
psft-dpk-setup.bat --env_type midtier --deploy_only --deploy_type app_
and_tools_home
```

- If you extracted the first zip file into a different directory, include the option `dpk_src_dir` to specify the location of the downloaded zip files, such as `DPK_INSTALL`, as follows:

```
psft-dpk-setup.bat --dpk_src_dir DPK_INSTALL --env_type midtier -->
deploy_only --deploy_type app_and_tools_home
```

5. Wait while the script locates the valid PeopleSoft zip files and extracts them.

The system displays messages indicating the steps in the setup process. The success or failure of each step is indicated by [OK] or [FAILED].

The script locates the valid PeopleSoft zip files and extracts them. After it completes the extraction, it deletes the original downloaded zip files.

See "Preparing for Installation," Understanding the PeopleSoft Installation Using Deployment Packages, for the filename syntax of the DPK zip files.

Starting the PeopleSoft Environment Setup Process:

```
Validating User Arguments: [ OK ]
Validating PeopleSoft Supported Platform: [ OK ]

Extracting the Zip File FILENAME_1of11.zip: [ OK ]
Extracting the Zip File FILENAME_2of11.zip: [ OK ]
...
Extracting the Zip File FILENAME_11of11.zip: [ OK ]
```

6. Specify whether to install the Puppet software if necessary at the next prompt.

The script verifies if Puppet software is installed in the default location specified by the DPKs. If not, answer *y* (yes) to install the Puppet software and *n* to abort the PeopleSoft environment setup process. The default action (if nothing is entered at the prompt) is to install the software.

If there is any error during the Puppet software installation, the script aborts the setup process.

Verifying if Puppet Software is Installed:

Puppet Software is not installed on the Windows Host. If PeopleSoft environment needs to be setup on this Host, Puppet software should be Installed.

Do you want to proceed with the Puppet Installation? [Y|n]: **y**

```
Installing Puppet Software on the Windows Host: [ OK ]
```

The script verifies whether the eYAML Hiera files are installed.

```
Verifying if eYAML Hiera Backend is Installed: [ OK ]
```

The script verifies if the DPKs are available in `DPK_INSTALL`, and aborts with the message [FAILED] if they are not.

Preparing the Windows 2012 Server VM for PeopleSoft Environment:

```
Checking if PeopleSoft DPKs are Present: [ OK ]
```

7. At the following prompt, enter a location that is accessible to the host to be used as the PeopleSoft base directory, referred to here as *BASE_DIR*.

The base directory is used to extract the DPKs as well as for deploying PeopleSoft components. The script creates the base directory if it does not exist.

Use forward slashes only (/) when specifying the base directory; for example, C:/psft. Do not use a base directory name that begins with a number.

The base folder is used to extract the PeopleSoft DPKs. It is also used to deploy the PeopleSoft components. This folder should be accessible on the Windows VM, must have write permissions and should have enough free space

```
Enter the PeopleSoft Base Folder: C:/psft
Are you happy with your answer? [Y|n|q]:
```

The script validates if there is enough free space available under the specified base directory for the PeopleSoft environment. The PeopleSoft environment setup is aborted if there is not enough free space.

Note. A mid-tier setup of a PeopleSoft environment requires about 25 GB of disk space.

```
Checking if the Base Folder has Enough Free Space: [ OK ]
```

8. Review the status messages as the script validates the files found in the download directory, *DPK_INSTALL*, and extracts the archives from the DPKs.

The script carries out validations for the specified mid-tier deployment. If any of the validations fail, the PeopleSoft environment setup is aborted.

Note. The messages have been truncated for brevity.

```
Validating the PeopleSoft DPKs in the Windows VM:
[...]
Extracting the PeopleSoft DPK Archives in the Windows VM:
[...]
```

9. Review the status messages as the script sets up the Puppet file system.

The script sets up Puppet on the host. It then copies the PeopleSoft Puppet modules to the standard location (*BASE_DIR\dpk*) and updates the YAML files to reflect the type of PeopleSoft environment setup.

```
Setting up Puppet on the Windows VM:
Generating eYAML Hiera Backend Encryption Keys: [ OK ]
Updating the Puppet Hiera YAML Files in the Windows VM: [ OK ]
Updating the Role in Puppet Site File for the Windows VM: [ OK ]
```

10. Specify the information for your database platform.

- a. For the database platform, enter DB2UNIX for DB2 for Linux, UNIX, and Windows.

```
Enter the PeopleSoft database platform [ORACLE]: DB2UNIX
```

- b. Enter y (yes) to indicate that the database you are connecting to is a Unicode database, or n (no) for a non-Unicode database.

```
Is the PeopleSoft database unicode? [Y|n]: y
```

11. Enter *y* if you want the script to include multi-language files in the installation.

Do you want Multi Language support in PeopleSoft database? [y|N]: *y*

12. Enter *y* to continue with the script.

Are you happy with your answers? [y|n]: *y*

Encrypting the Passwords in the User Data: [OK]

Updating the Puppet Hiera YAML Files with User Data: [OK]

13. If you want to continue running the initialization script using the default configuration, answer *y* (yes) to the following prompt, and continue with the next step.

The components that are installed during a default initialization are described in the section *Reviewing the Installation Results*. The process for completing the initialization with customizations is described in the chapter "Completing the DPK Initialization with Customizations."

If you want to customize the PeopleSoft environment using the Puppet YAML files, answer *n* (no) to stop the script.

The bootstrap script is ready to deploy and configure the PeopleSoft environment using the default configuration defined in the Puppet Hiera YAML files. You can proceed by answering 'y' at the following prompt. And, if you want to customize the environment by overriding the default configuration, you can answer 'n'. If you answer 'n', you should follow the instructions in the PeopleSoft Installation Guide for creating the customization Hiera YAML file and running the Puppet 'apply' command directly to continue with the setup of the PeopleSoft environment

Do you want to continue with the default initialization process? [y|n]:

14. Review the status messages as the script runs Puppet profiles to set up the PeopleSoft environment.

A message of [OK] indicates that the profile has been applied successfully while a message [FAILED] indicates that the profile application failed.

The script stops and exits the first time a profile application fails, and displays an error message. This example shows the error message after the first step failed:

Starting the Deployment of PeopleSoft Components:

Deploying Application Components: [FAILED]

The initialization of PeopleSoft environment setup failed. Check the log file [C:\DPK_INSTALL\setup\psft_dpk_setup.log] for the errors. After correcting the errors, run the following commands to continue with the setup of PeopleSoft environment.

```
1. cd /d C:\psft\dpk\puppet\production\manifests
2. "C:\Program Files\Puppet Labs\Puppet\bin\puppet.bat" apply
   --confdir=C:\psft\dpk\puppet site.pp --debug --trace
   --detailed-exitcodes
   --logdest /some_valid_path/to/log/psft_dpk_setup.log
```

Exiting the PeopleSoft environment setup process.

Note. To run step 2, the puppet apply step, it is a good idea to use a log name other than `psft_dpk_setup.log`, to differentiate the log from that for the DPK initialization.

Upon successful completion, the DPK setup script displays the following message:

Starting the Deployment of PeopleSoft Components:

```
Deploying Application Components:           [ OK ]
Deploying PeopleTools Components:         [ OK ]
```

The PeopleSoft Environment Setup Process Ended.

The complete setup log is written to the file `psft_dpk_setup.log` in the same location as the DPK setup script.

See Obtaining Operating System Packages Required by Puppet if you see messages about missing packages in the log.

Task 2-5-2: Installing PS_HOME and PS_APP_HOME on Linux, AIX, HP-UX, or Solaris as the Root User

To use the DPK setup script for deployment only:

1. Extract the first zip file (*FILENAME_1ofn.zip*).

Note. It is a good idea to extract into the same directory where you downloaded the zip files, *DPK_INSTALL*.

The extraction creates the *DPK_INSTALL/setup* folder and other files.

2. Open a terminal window and change directory to *DPK_INSTALL/setup*.
3. As a user with root access, run the `psft-dpk-setup.sh` script with the options for deployment only.
 - If you extracted the first zip file into the same directory where you downloaded the zip files, run the script with no options, as follows:

```
./psft-dpk-setup.sh --env_type midtier --deploy_only --deploy_type=>
app_and_tools_home
```

- If you extracted the first zip file into a different directory, use the option `dpk_src_dir` to specify the location of the downloaded zip files, such as *DPK_INSTALL*, as follows:

```
./psft-dpk-setup.sh --dpk_src_dir DPK_INSTALL --env_type midtier -->
deploy_only --deploy_type app_and_tools_home
```

4. Wait while the script locates the valid DPK zip files and extracts them.

The system displays messages indicating the steps in the setup process. The success or failure of each step is indicated by [OK] or [FAILED].

See "Preparing for Installation," Understanding the PeopleSoft Installation Using Deployment Packages, for the filename syntax of the DPK zip files.

Starting the PeopleSoft Environment Setup Process:

```
Validating User Arguments:                 [ OK ]
Validating PeopleSoft Supported Platform:  [ OK ]
```

```
Extracting the Zip File FILENAME_1of11.zip: [ OK ]
```



```
Extracting the Zip File FILENAME_2of11.zip: [ OK ]
...
Extracting the Zip File FILENAME_11of11.zip: [ OK ]
```

5. Specify whether to install the Puppet software if necessary at the next prompt.

The script verifies if Puppet software is installed in the default location specified by the DPKs. If not, answer *y* (yes) to install the Puppet software and *n* to abort the PeopleSoft environment setup process. The default action (if nothing is entered at the prompt) is to install the software.

If there is any error during the Puppet software installation, the script aborts the setup process.

```
Verifying if Puppet Software is Installed: [ OK ]
```

Puppet Software is not installed on the Linux Host. If PeopleSoft environment needs to be setup on this Host, Puppet software should be Installed.

```
Do you want to proceed with the Puppet Installation? [Y|n]: y
```

```
Installing Puppet Software on the Host: [ OK ]
```

The script verifies whether the eYAML Hiera files are installed:

```
Verifying if eYAML Hiera Backend is Installed: [ OK ]
```

The script verifies if the DPKs are available in *DPK_INSTALL*, and aborts with the message [FAILED] if they are not.

```
Preparing the Linux VM for PeopleSoft Environment:
```

```
Checking if PeopleSoft DPKs are Present: [ OK ]
```

6. At the following prompt, enter a location that is accessible to the host to be used as the PeopleSoft base directory, referred to here as *BASE_DIR*.

The base directory is used to extract the PeopleSoft DPKs as well as for deploying PeopleSoft components. The script creates the directory if it does not exist.

Use forward slashes only (/) when specifying the base directory; for example, */opt/oracle/psft*. Do not use a base directory name that begins with a number.

The base folder is used to extract the PeopleSoft DPKs. It is also used to deploy the PeopleSoft components. This directory should be accessible on the Linux VM, must have write permissions and should have enough free space.

```
.
Enter the PeopleSoft Base Directory: /opt/oracle/psft
Are you happy with your answer? [Y|n|q]:
```

The script validates if there is enough free space available under the specified base directory for the PeopleSoft environment. The PeopleSoft environment setup is aborted if there is not enough free space. The script creates the base directory if it does not exist.

Note. A mid-tier setup of a PeopleSoft environment requires about 25 GB of disk space.

```
Checking if the Base Directory has Enough Free Space: [ OK ]
```

7. If the default home directory is not writable, enter a new location at the following prompt.

The DPK setup creates local users on the host. These users deploy the PeopleSoft components and own the PeopleSoft runtime domains. The script checks whether the default home directory for the PeopleSoft users (/home) is writable. If not, it will prompt the user to enter a new location to be used for creating the home directories for these local users.

```
Checking if Default User Home Directory /home is Writable: [WARNING]
```

```
The PeopleSoft environment setup creates local users on the Linux VM.
The default Home directory [/home] do not have write permission to
create the user's home directory. Please
ensure this directory is writable or provide a new directory on the
Linux VM that is writable.
```

```
Enter a directory on the Linux VM that is writable [/home]: /ds1
Are you happy with your answer? [y|n|q]:
```

If the /home directory is writable, no response is required.

```
Checking if Default User Home Directory /home is Writable: [ OK ]
```

8. Review the status messages as the script validates the files found in the download directory, *DPK_INSTALL*, and extracts the archives from the DPKs.

The script carries out validations for the specified mid-tier deployment. If any of the validations fail, the PeopleSoft environment setup is aborted.

Note. The messages have been truncated for brevity.

```
Validating the PeopleSoft DPKs in the Linux VM:
[...]
Extracting the PeopleSoft DPK Archives in the Linux VM:
[...]
```

9. Review the status messages as the script sets up the Puppet file system.

The script sets up Puppet on the host. It then copies the PeopleSoft Puppet modules to the standard location (*BASE_DIR/dpk*) and updates the YAML files to reflect the type of PeopleSoft environment setup.

```
Setting up Puppet on the Linux VM:
Generating eYAML Hierarchical Backend Encryption Keys: [ OK ]
Updating the Puppet Hierarchical YAML Files in the Linux VM: [ OK ]
Updating the Role in Puppet Site File for the Linux VM: [ OK ]
```

10. Specify the information for your database platform.

- a. For the database platform, enter DB2UNIX for DB2 for Linux, UNIX, and Windows.

```
Enter the PeopleSoft database platform [ORACLE]: DB2UNIX
```

- b. Enter y (yes) to indicate that the database you are connecting to is a Unicode database, or n (no) for a non-Unicode database.

```
Is the PeopleSoft database unicode? [Y|n]: y
```

11. Enter y if you want the script to include multi-language files in the installation.

```
Do you want Multi Language support in PeopleSoft database? [y|N]:
```

12. Enter y to continue with the script.

```
Are you happy with your answers? [y|n]: y
Encrypting the Passwords in the User Data:          [ OK ]
Updating the Puppet Hiera YAML Files with User Data: [ OK ]
```

13. If you want to continue running the initialization script using the default configuration, answer *y* (yes) to the following prompt, and continue with the next step.

The components that are installed during a default initialization are described in the section *Reviewing the Installation Results*. The process for completing the initialization with customizations is described in the chapter "Completing the DPK Initialization with Customizations."

If you want to customize the PeopleSoft environment using the Puppet YAML files, answer *n* (no) to stop the script.

The bootstrap script is ready to deploy and configure the PeopleSoft environment using the default configuration defined in the Puppet Hiera YAML files. You can proceed by answering 'y' at the following prompt. And, if you want to customize the environment by overriding the default configuration, you can answer 'n'. If you answer 'n', you should follow the instructions in the PeopleSoft Installation Guide for creating the customization Hiera YAML file and running the Puppet 'apply' command directly to continue with the setup of the PeopleSoft environment

```
Do you want to continue with the default initialization process? [y|n]:
```

14. Review the status messages as the script runs Puppet profiles to set up the PeopleSoft environment.

A message of [OK] indicates that the profile has been applied successfully while a message [FAILED] indicates that the profile application failed.

The script stops and exits the first time a profile application fails, and displays an error message. This example shows the error message after the first step failed:

Starting the Deployment of PeopleSoft Components:

```
Setting Up System Settings                                [FAILED]
```

The initialization of PeopleSoft environment setup failed. Check the log file [DPK_INSTALL/setup/psft_dpk_setup.log] for the errors. After correcting the errors, run the following commands to continue with the setup of PeopleSoft environment.

```
1. cd /opt/oracle/psft/dpk/puppet/production/manifests
2. PUPPET_DIR/puppet apply
--confdir=/opt/oracle/psft/dpk/puppet site.pp
--debug --trace --detailed-exitcodes
--logdest /some_valid_path/to/log/psft_dpk_setup.log
```

Exiting the PeopleSoft environment setup process.

Note. For Linux, *PUPPET_DIR* is /opt/puppetlabs/bin. For AIX or Solaris, *PUPPET_DIR* is /opt/oracle/puppetlabs/bin.

Note. To run step 2, the puppet apply step, it is a good idea to use a log name other than psft_dpk_setup.log, to differentiate the log from that for the DPK initialization.

See "Completing the DPK Initialization with Customizations."

Upon successful completion, the DPK setup script displays the following message:

Starting the Deployment of PeopleSoft Components:

```
Setting Up System Settings           [ OK ]
Deploying Application Components:    [ OK ]
Deploying PeopleTools Components:   [ OK ]
```

The PeopleSoft Environment Setup Process Ended.

The complete setup log is written to the file `psft-dpk_setup.log` in the same location as the DPK setup script.

Task 2-5-3: Installing PS_HOME and PS_APP_HOME on Linux, AIX, HP-UX, or Solaris as a Non-Root User

If you are installing the PeopleSoft environment as a non-root user, ensure that you fulfill the prerequisites in the section Deploying as a Non-Root User on Linux, AIX, HP-UX, or Solaris.

To use the DPK setup script for deployment only:

1. Open a terminal window and change directory to `DPK_INSTALL/setup`.
2. Run the `psft-dpk-setup.sh` script with the options for deployment only.
 - If you extracted the first zip file into the same directory where you downloaded the zip files, run the script with no options, as follows:

```
./psft-dpk-setup.sh --env_type midtier --deploy_only --deploy_type⇒
app_and_tools_home
```

- If you extracted the first zip file into a different directory, use the option `dpk_src_dir` to specify the location of the downloaded zip files, such as `DPK_INSTALL`, as follows:

```
./psft-dpk-setup.sh --dpk_src_dir DPK_INSTALL --env_type midtier --⇒
deploy_only --deploy_type app_and_tools_home
```

3. Answer `y` (yes) at the following prompt:

Starting the PeopleSoft Environment Setup Process:

```
You are running DPK setup without root/administrator access.
This is fine as long as the system administrator has performed
all necessary tasks and all prerequisites have been met.
Please see the documentation to determine the prerequisite tasks
that need to be performed to successfully run DPK set up
without root/administrator privilege.
Would you like to proceed with the setup as a non-root user? [y/n]: y
```

4. Wait while the script verifies that the necessary PeopleSoft DPK zip files are available and that the Puppet software is installed.

The system displays messages indicating the steps in the setup process. The success or failure of each step is indicated by `[ OK ]` or `[FAILED]`.

```
Validating User Arguments           [ OK ]
Validating PeopleSoft Supported Platform [ OK ]
Verifying if Puppet Software is Installed: [ OK ]
```

```
Verifying if eYAML Hiera Backend is Installed:          [ OK ]
```

```
Preparing the Linux VM for PeopleSoft Environment:
```

```
Checking if PeopleSoft DPKs are Present:              [ OK ]
```

5. At the following prompt, enter a location that is accessible to the host to be used as the PeopleSoft base directory, referred to here as *BASE_DIR*.

The base directory is used to extract the PeopleSoft DPKs as well as for deploying PeopleSoft components. The script creates the directory if it does not exist.

Use forward slashes only (/) when specifying the base directory; for example, /opt/oracle/psft. Do not use a base directory name that begins with a number.

The base folder is used to extract the PeopleSoft DPKs. It is also used to deploy the PeopleSoft components. This directory should be accessible on the Linux VM, must have write permissions and should have enough free space.

```
.
Enter the PeopleSoft Base Directory: /opt/oracle/psft
Are you happy with your answer? [Y|n|q]:
```

The script validates if there is enough free space available under the specified base directory for the PeopleSoft environment. The PeopleSoft environment setup is aborted if there is not enough free space. The script creates the base directory if it does not exist.

Note. A mid-tier setup of a PeopleSoft environment requires about 25 GB of disk space.

```
Checking if the Base Directory has Enough Free Space:  [ OK ]
```

6. Enter a writable directory with at least 10 GB available space for *PS_CFG_HOME*.

The default is *USER_HOME*/psft/pt/8.57, where *USER_HOME* is the home directory for the logged-in user. The *PS_CFG_HOME* directory holds the configuration and log files for the PeopleSoft Application Server, Process Scheduler, and PIA domains.

```
Enter a writable ps_config_home directory for PeopleSoft domains
with at least 10.0GB space [/home/psftuser/psft/pt/8.57]:
Are you happy with your answer? [Y|n|q]: y
```

7. Review the status messages as the script validates the files found in the download directory, *DPK_INSTALL* and extracts the DPK archives.

The script carries out validations for the specified mid-tier deployment. If any of the validations fail, the PeopleSoft environment setup is aborted.

Note. The messages have been truncated for brevity. The messages vary depending upon the DPKs used.

```
Validating the PeopleSoft DPKs in the Linux VM:
[...]
Extracting the PeopleSoft DPK Archives in the Linux VM:
[...]
```

8. Review the status messages as the script sets up the Puppet file system.

The script sets up Puppet on the host. It then copies the PeopleSoft Puppet modules to the standard location (*BASE_DIR*/dpk) and updates the YAML files to reflect the type of PeopleSoft environment setup.

```
Setting up Puppet on the Linux VM:
```

```

Generating eYAML Hiera Backend Encryption Keys:          [ OK ]
Updating the Puppet Hiera YAML Files in the Linux VM:    [ OK ]
Updating the Role in Puppet Site File for the Linux VM:  [ OK ]

```

9. Specify the information for your database platform.

- a. For the database platform, enter DB2UNIX for DB2 for Linux, UNIX, and Windows.

```
Enter the PeopleSoft database platform [ORACLE]: DB2UNIX
```

- b. Enter *y* (yes) to indicate that the database you are connecting to is a Unicode database, or *n* (no) for a non-Unicode database.

```
Is the PeopleSoft database unicode? [Y|n]: y
```

10. Enter *y* if you want the script to include multi-language files in the installation.

```
Do you want Multi Language support in PeopleSoft database? [y|N]:
```

11. Enter *y* to continue with the script.

```

Are you happy with your answers? [y|n]: y
Encrypting the Passwords in the User Data:          [ OK ]
Updating the Puppet Hiera YAML Files with User Data: [ OK ]

```

12. If you want to continue running the initialization script using the default configuration, answer *y* (yes) to the following prompt, and continue with the next step.

The components that are installed during a default initialization are described in the section *Reviewing the Installation Results*. The process for completing the initialization with customizations is described in the chapter "Completing the DPK Initialization with Customizations."

If you want to customize the PeopleSoft environment using the Puppet YAML files, answer *n* (no) to stop the script.

The bootstrap script is ready to deploy and configure the PeopleSoft environment using the default configuration defined in the Puppet Hiera YAML files. You can proceed by answering 'y' at the following prompt. And, if you want to customize the environment by overriding the default configuration, you can answer 'n'. If you answer 'n', you should follow the instructions in the PeopleSoft Installation Guide for creating the customization Hiera YAML file and running the Puppet 'apply' command directly to continue with the setup of the PeopleSoft environment

```
Do you want to continue with the default initialization process? [y|n]:
```

13. Review the status messages as the script runs Puppet profiles to set up the PeopleSoft environment.

A message of [OK] indicates that the profile has been applied successfully while a message [FAILED] indicates that the profile application failed.

The script stops and exits the first time a profile application fails, and displays an error message. This example shows the error message after the first step failed:

```
Starting the Deployment of PeopleSoft Components:
```

```
Setting Up System Settings [FAILED]
```

```
The initialization of PeopleSoft environment setup failed. Check the
log file [DPK_INSTALL/setup/psft_dpk_setup.log] for the errors.
```

After correcting the errors, run the following commands to continue with the setup of PeopleSoft environment.

```
1. cd /opt/oracle/psft/dpk/puppet/production/manifests
2. PUPPET_DIR/puppet apply
--confdir=/opt/oracle/psft/dpk/puppet site.pp
--debug --trace --detailed-exitcodes
--logdest /some_valid_path/to/log/psft_dpk_setup.log
```

Exiting the PeopleSoft environment setup process.

Note. For Linux, *PUPPET_DIR* is /opt/puppetlabs/bin. For AIX, HP-UX, or Solaris, *PUPPET_DIR* is /opt/oracle/puppetlabs/bin.

Note. To run step 2, the puppet apply step, it is a good idea to use a log name other than psft_dpk_setup.log, to differentiate the log from that for the DPK initialization.

See "Completing the DPK Initialization with Customizations."

Upon successful completion, the DPK setup script displays the following message:

Starting the Deployment of PeopleSoft Components:

```
Setting Up System Settings           [ OK ]
Deploying Application Components:    [ OK ]
Deploying PeopleTools Components:    [ OK ]
```

The PeopleSoft Environment Setup Process Ended.

setup.log is written to the file <USER_HOME>/psft_dpk_work/psft_dpk_setup_<PID>.log, where <USER_HOME> is the home directory for the user running the script, and <PID> is a process ID.

Task 2-5-4: Reviewing the Deployment Results

This section describes some of the files and folders installed by the script. These are the standard default locations. If you want to change the installation locations, see "Completing the DPK Initialization with Customizations."

The script creates the following three sub-directories under the user-specified base directory, *BASE_DIR*:

- *BASE_DIR*/pt

The script uses this directory to deploy the *PS_HOME* and *PS_APP_HOME* utilities and scripts, including the following:

- *PS_HOME* installed to the default location under the DPK base directory, *BASE_DIR*/pt/ps_home8.57.xx.
- *PS_HOME*/appserv/PSADMIN.exe
- *PS_HOME*/bin/client/winx86/pscfg.exe (Configuration Manager)
- *PS_HOME*/bin/client/winx86/psdmt.exe (Data Mover)
- *PS_HOME*/bin/client/winx86/pside.exe (Application Designer)
- *PS_HOME*/scripts
- *PS_HOME*/setup/PsMpPIAInstall (PeopleSoft Pure Internet Architecture installer)
- *PS_HOME*/setup/PsMpDbInstall (Database installer)

- *PS_HOME/setup/PsCA* (Change Assistant installer)
- *PS_HOME/setup/PsCIA* (Change Impact Analyzer installer)
- *PS_HOME/setup/PsMpWebAppDeployInstall* (Web Application Deployment installer)
- Microsoft Windows DPKs include Microsoft Visual C++ Redistributable Packages for Visual Studio, which include required Microsoft C++ runtime libraries.
- *PS_APP_HOME* installed to the default location under the DPK base directory, *BASE_DIR/pt/<Product>_app_home*, where *<Product>* is the abbreviation for the PeopleSoft application; for example, *hcm_app_home* for PeopleSoft Human Capital Management.

Note. The DPK setup requires a decoupled *PS_APP_HOME*; that is, the installation location of *PS_APP_HOME* is different from *PS_HOME*.

Files for the specific PeopleSoft application, including files needed for database creation.

If you answered yes when asked whether you wanted multi-language support during the DPK setup script process, the files required for translations are installed under *BASE_DIR/pt/<Product>_app_home*.

- *BASE_DIR/dpk*

The script uses this directory to extract the archives from the PeopleSoft DPKs, and contains the Puppet YAML files for the deployment. Do not alter the installed Puppet YAML files.

See Completing the DPK Initialization with Customizations for information on creating a YAML file to customize the environment.

- *BASE_DIR/db*

This directory is not used for this deployment.

Task 2-6: Running the DPK Setup Script to Install All Software

This section discusses:

- Understanding the DPK Setup Deploying All Software
- Installing on Microsoft Windows
- Installing on Linux, AIX, HP-UX, or Solaris as the Root User
- Installing on Linux, AIX, HP-UX, or Solaris as a Non-Root User
- Reviewing the Installed Software

Understanding the DPK Setup Deploying All Software

Use these instructions to install all software required to continue with the PeopleSoft installation. This deployment uses the DPK setup script `--env_type midtier --deploy_only --deploy_type all` options to install the PeopleSoft PeopleTools software in *PS_HOME*, the PeopleSoft application software in *PS_APP_HOME*, and the software required for the mid-tier components. This deployment does not set up the PeopleSoft domains; you will do that in a later chapter. If you plan to use the Database Configuration Wizard to create your PeopleSoft database on Linux, AIX, HP-UX, or Solaris platforms, Oracle Tuxedo is a prerequisite. Using the DPK setup script options in this section installs Oracle Tuxedo along with other software.

This procedure assumes that you have downloaded all of the required DPKs, and saved them in a location referred to here as *DPK_INSTALL*. This deployment requires the presence of the PeopleSoft application DPK (Application DPK, Part 1) in the deployment folder, *DPK_INSTALL*.

Task 2-6-1: Installing on Microsoft Windows

To use the DPK setup script to deploy the software required to set up a PeopleSoft environment:

1. Extract the first zip file (*FILENAME_1ofn.zip*).

Note. It is a good idea to extract into the same directory where you downloaded the zip files, *DPK_INSTALL*.

The extraction creates the *DPK_INSTALL/setup* folder and other files.

2. Open a command prompt with Run as Administrator.
3. Change directory to *DPK_INSTALL/setup*.
4. Run the script with the option for deployment only.

Note. If you see an error message similar to "The application has failed to start because its side-by-side configuration is incorrect," it indicates that your machine does not include the necessary Microsoft C++ runtime libraries. Go to the Microsoft Web site, locate the Microsoft Visual C++ redistributable package for your system, and install as directed.

- If you extracted the first zip file into the same directory where you downloaded the zip files, use this command:
- If you extracted the first zip file into a different directory, include the option *dpk_src_dir* to specify the location of the downloaded zip files, such as *DPK_INSTALL*, as follows:

```
psft-dpk-setup.bat --env_type midtier --deploy_only --deploy_type all
```

```
psft-dpk-setup.bat --dpk_src_dir DPK_INSTALL --env_type midtier ⇒
--deploy_only --deploy_type all
```

5. Wait while the script locates the valid DPK zip files and extracts them.

The system displays messages indicating the steps in the setup process. The success or failure of each step is indicated by [OK] or [FAILED].

After the script completes the extraction, it deletes the original downloaded zip files.

See "Preparing for Installation," Understanding the PeopleSoft Installation Using Deployment Packages, for the filename syntax of the DPKs zip files.

Starting the PeopleSoft Environment Setup Process:

```
Validating User Arguments:                [ OK ]
Validating PeopleSoft Supported Platform:  [ OK ]

Extracting the Zip File FILENAME_1of11.zip: [ OK ]
Extracting the Zip File FILENAME_2of11.zip: [ OK ]
...
Extracting the Zip File FILENAME_11of11.zip: [ OK ]
```

6. Specify whether to install the Puppet software if necessary at the next prompt.

The script verifies if Puppet software is installed in the default location specified by the DPKs. If not, answer *y* (yes) to install the Puppet software and *n* to abort the PeopleSoft environment setup process. The default action (if nothing is entered at the prompt) is to install the software.

If there is any error during the Puppet software installation, the script aborts the setup process.

Verifying if Puppet Software is Installed:

Puppet Software is not installed on the Windows Host. If PeopleSoft environment needs to be setup on this Host, Puppet software should be Installed..

Do you want to proceed with the Puppet Installation? [Y|n]: **y**

Installing Puppet Software on the Windows Host: [OK]

The script verifies whether the eYAML Hiera files are installed.

Verifying if eYAML Hiera Backend is Installed: [OK]

The script verifies if the DPKs are available in the download directory, *DPK_INSTALL*, and aborts with the message [FAILED] if they are not.

Preparing the Windows 2012 Server VM for PeopleSoft Environment:

Checking if PeopleSoft DPKs are Present: [OK]

7. At the following prompt, enter a location that is accessible to the host to be used as the PeopleSoft base folder.

The base folder is used to extract the PeopleSoft DPKs as well as for deploying PeopleSoft components. The script creates the folder if it does not exist.

Use forward slashes (/) to specify the base folder location; for example, C:/psft. Do not use a name for the base folder that begins with a number.

The base folder is used to extract the PeopleSoft DPKs. It is also used to deploy the PeopleSoft components. This folder should be accessible on the Windows VM, must have write permissions and should have enough free space

Enter the PeopleSoft Base Folder: **C:/psft**

Are you happy with your answer? [Y|n|q]:

The script validates if there is enough free space available under the specified base folder for the PeopleSoft environment. The PeopleSoft environment setup is aborted if there is not enough free space.

Note. A mid-tier setup of a PeopleSoft environment requires about 25 GB of disk space.

Checking if the Base Folder has Enough Free Space: [OK]

8. Review the status messages as the script validates the files found in the download location, *DPK_INSTALL* and extracts the DPK archives.

The script carries out validations for the mid-tier deployment. If any of the validations fail, the PeopleSoft environment setup is aborted.

Note. The messages vary depending upon the DPKs present, and have been truncated for brevity.

Validating the PeopleSoft DPKs in the Windows VM:

[...]

Extracting the Peoplesoft DPK Archives in Windows VM:

[...]

9. Review the status messages as the script sets up the Puppet file system.

The script sets up Puppet on the host. It then copies the PeopleSoft Puppet modules to the standard location (*BASE_DIR\dpk*) and updates the YAML files to reflect the type of PeopleSoft environment setup.

Setting up Puppet on the Windows VM:

```
Generating eYAML Hiera Backend Encryption Keys:          [ OK ]
Updating the Puppet Hiera YAML Files in the Windows VM:  [ OK ]
Updating the Role in Puppet Site File for the Windows VM: [ OK ]
```

10. Specify the information for your database platform.

- a. For the database platform, enter DB2UNIX for DB2 for Linux, UNIX, and Windows.

Enter the PeopleSoft database platform [ORACLE]: **DB2UNIX**

- b. Enter *y* (yes) to indicate that the database you are connecting to is a Unicode database, or *n* (no) if it is a non-Unicode database.

Is the PeopleSoft database unicode? [Y|n]: **y**

11. Enter *y* if you want the DPK setup script to install files required for a multi-lingual installation.

Do you want Multi Language support in PeopleSoft database? [y|N]: **n**

12. Enter *y* to continue with the script.

```
Are you happy with your answers? [y|n]: y
Encrypting the Passwords in the User Data:          [ OK ]
Updating the Puppet Hiera YAML Files with User Data: [ OK ]
```

13. If you want to continue running the initialization script with the default configuration, answer *y* (yes) to the following prompt, and continue with the next step.

If you want to customize the PeopleSoft environment using the Puppet YAML files, answer *n* (no) to stop the script.

The bootstrap script is ready to deploy and configure the PeopleSoft environment using the default configuration defined in the Puppet Hiera YAML files. You can proceed by answering 'y' at the following prompt. And, if you want to customize the environment by overriding the default configuration, you can answer 'n'. If you answer 'n', you should follow the instructions in the PeopleSoft Installation Guide for creating the customization Hiera YAML file and running the Puppet 'apply' command directly to continue with the setup of the PeopleSoft environment

Do you want to continue with the default initialization process? [y|n]:

14. Review the status messages as the script runs Puppet profiles to set up the PeopleSoft environment.

A message of [OK] indicates that the profile has been applied successfully while a message [FAILED] indicates that the profile application failed.

The script stops and exits the first time a profile application fails, and displays an error message. This example shows the error message after the first step failed:

Starting the Deployment of PeopleSoft Components:

```
Deploying Application Components:                      [FAILED]
```

The initialization of PeopleSoft environment setup failed. Check the log file [C:\DPK_INSTALL\setup\psft_dpk_setup.log] for the errors.

After correcting the errors, run the following commands to continue with the setup of PeopleSoft environment.

```
1. cd /d C:\psft\dpk\puppet\production\manifests
2. "C:\Program Files\Puppet Labs\Puppet\bin\puppet.bat" apply
   --confdir=C:\psft\dpk\puppet site.pp --debug --trace
   --detailed-exitcodes
   --logdest /some_valid_path/to/log/psft_dpk_setup.log
```

Exiting the PeopleSoft environment setup process.

Note. If you run step 2, the puppet apply step, it is a good idea to use a log name other than `psft_dpk_setup.log`, to differentiate the log from that for the DPK initialization.

See "Completing the DPK Initialization with Customizations."

Upon successful completion, the DPK setup script displays the following message:

Starting the Deployment of PeopleSoft Components:

```
Deploying Application Components:           [ OK ]
Deploying PeopleTools Components:          [ OK ]
```

The PeopleSoft Environment Setup Process Ended.

The complete setup log is written to the file `psft_dpk_setup.log` in the same location as the DPK setup script.

Task 2-6-2: Installing on Linux, AIX, HP-UX, or Solaris as the Root User

To run the DPK setup script as the root user to deploy the software required to set up a PeopleSoft environment:

1. Extract the first zip file (*FILENAME_1ofn.zip*).

Note. It is a good idea to extract into the same directory where you downloaded the zip files, *DPK_INSTALL*.

The extraction creates the *DPK_INSTALL/setup* folder and other files.

2. Open a terminal window and change directory to *DPK_INSTALL/setup*.
3. As a user with root access, run the script with the option for deployment only.
 - If you extracted the first zip file into the same directory where you downloaded the zip files, run the script as follows:


```
./psft-dpk-setup.sh --env_type midtier --deploy_only --deploy_type all
```
 - If you extracted the first zip file into a different directory, use the option `dpk_src_dir` to specify the location of the downloaded zip files, such as *DPK_INSTALL*, as follows:


```
./psft-dpk-setup.sh --dpk_src_dir DPK_INSTALL --env_type midtier -->
deploy_only --deploy_type all
```

4. Wait while the script locates the valid PeopleSoft zip files and extracts them.

The system displays messages indicating the steps in the setup process. The success or failure of each step is indicated by [OK] or [FAILED].

See "Preparing for Installation," Understanding the PeopleSoft Installation Using Deployment Packages, for the filename syntax of the DPK zip files.

Starting the PeopleSoft Environment Setup Process:

```
Validating User Arguments:                [ OK ]
Validating PeopleSoft Supported Platform: [ OK ]

Extracting the Zip File FILENAME_1of11.zip: [ OK ]
Extracting the Zip File FILENAME_2of11.zip: [ OK ]
...
Extracting the Zip File FILENAME_11of11.zip: [ OK ]
```

5. Specify whether to install the Puppet software if necessary at the next prompt.

The script verifies if Puppet software is installed in the default location specified by the DPKs. If not, answer *y* (yes) to install the Puppet software and *n* to abort the PeopleSoft environment setup process. The default action (if nothing is entered at the prompt) is to install the software.

If there is any error during the Puppet software installation, the script aborts the setup process.

Verifying if Puppet Software is Installed:

Puppet Software is not installed on the Linux Host. If PeopleSoft environment needs to be setup on this Host, Puppet software should be Installed.

Do you want to proceed with the Puppet Installation? [Y|n]: **y**

```
Installing Puppet Software on the Host:    [ OK ]
```

The script verifies whether the eYAML Hiera files are installed.

```
Verifying if eYAML Hiera Backend is Installed: [ OK ]
```

The script verifies if the DPKs are available in *DPK_INSTALL*, and aborts with the message [FAILED] if they are not.

Preparing the Linux VM for PeopleSoft Environment:

```
Checking if PeopleSoft DPKs are Present:    [ OK ]
```

6. At the following prompt, enter a location that is accessible to the host to be used as the PeopleSoft base directory.

The base directory is used to extract the PeopleSoft DPKs as well as for deploying PeopleSoft components.

Use forward slashes (/) to specify the directory; for example, */opt/oracle/psft*. Do not use a name for the base directory that begins with a number.

The base directory is used to extract the PeopleSoft DPKs. It is also used to deploy the PeopleSoft components. This directory should be accessible on the Linux VM, must have write permissions and should have enough free space.

.

Enter the PeopleSoft Base Directory: **/opt/oracle/psft**

Are you happy with your answer? [Y|n|q]: **y**

The script validates if there is enough free space available under the specified base directory for the PeopleSoft environment. The PeopleSoft environment setup is aborted if there is not enough free space. The script creates the directory if it does not exist.

Note. A mid-tier setup of a PeopleSoft environment requires about 25 GB of disk space.

Checking if the Base Directory has Enough Free Space: [OK]

7. If the default home directory is not writable, enter a new location at the following prompt.

The DPK setup creates local users on the host. These users deploy the PeopleSoft components and own the PeopleSoft runtime domains. The script checks whether the default home directory for the PeopleSoft users (/home) is writable. If not, it will prompt the user to enter a new location to be used for creating the home directories for these local users.

Checking if Default User Home Directory /home is Writable: [WARNING]

The PeopleSoft environment setup creates local users on the Linux VM. The default Home directory [/home] do not have write permission to create the user's home directory. Please ensure this directory is writable or provide a new directory on the Linux VM that is writable.

Enter a directory on the Linux VM that is writable [/home]: **/ds1**
Are you happy with your answer? [y|n|q]:

If the /home directory is writable, no response is required.

Checking if Default User Home Directory /home is Writable: [OK]

8. Review the status messages as the script validates the files found in the download directory, *DPK_INSTALL* and extracts the archives from the DPKs.

The script carries out validations for the mid-tier deployment. If any of the validations fail, the PeopleSoft environment setup is aborted.

Note. The messages have been truncated here for brevity.

Validating the PeopleSoft DPKs in the Linux VM:

[...]

Extracting the Peoplesoft DPK Archives in the Linux VM:

[...]

9. Review the status messages as the script sets up the Puppet file system.

The script sets up Puppet on the host. It then copies the PeopleSoft Puppet modules to the standard location (*BASE_DIR\dpk*) and updates the YAML files to reflect the type of PeopleSoft environment setup.

Setting up Puppet on the Linux VM:

Generating eYAML Hiera Backend Encryption Keys: [OK]

Updating the Puppet Hiera YAML Files in the Linux VM: [OK]

Updating the Role in Puppet Site File for the Linux VM: [OK]

10. Specify the information for your database platform.

- a. For the database platform, enter DB2UNIX for DB2 for Linux, UNIX, and Windows.

Enter the PeopleSoft database platform [ORACLE]: **DB2UNIX**

- b. Enter y (yes) to indicate that the database you are connecting to is a Unicode database, or n (no) if it is a non-Unicode database.

Is the PeopleSoft database unicode? [Y|n]: **y**

11. Enter *y* if you want the DPK setup script to install files required for a multi-lingual installation.

```
Do you want Multi Language support in PeopleSoft database? [y|N]: n
```

12. Enter *y* to continue with the script.

```
Are you happy with your answers? [y|n]: y
Encrypting the Passwords in the User Data:                [ OK ]
Updating the Puppet Hiera YAML Files with User Data:      [ OK ]
```

13. If you want to continue running the initialization script with the default configuration, answer *y* (yes) to the following prompt, and continue with the next step.

If you want to customize the PeopleSoft environment using the Puppet YAML files, answer *n* (no) to stop the script.

See "Completing the DPK Initialization with Customizations."

The bootstrap script is ready to deploy and configure the PeopleSoft environment using the default configuration defined in the Puppet Hiera YAML files. You can proceed by answering 'y' at the following prompt. And, if you want to customize the environment by overriding the default configuration, you can answer 'n'. If you answer 'n', you should follow the instructions in the PeopleSoft Installation Guide for creating the customization Hiera YAML file and running the Puppet 'apply' command directly to continue with the setup of the PeopleSoft environment

```
Do you want to continue with the default initialization process? [y|n]:
```

14. Review the status messages as the script runs Puppet profiles to set up the PeopleSoft environment.

A message of [OK] indicates that the profile has been applied successfully while a message [FAILED] indicates that the profile application failed.

The script stops and exits the first time a profile application fails, and displays an error message. This example shows the error message after the first step failed:

```
Starting the Deployment of PeopleSoft Components:
```

```
Setting Up System Settings:                                [FAILED]
```

The initialization of PeopleSoft environment setup failed. Check the log file [DPK_INSTALL/setup/psft_dpk_setup.log] for the errors. After correcting the errors, run the following commands to continue with the setup of PeopleSoft environment.

```
1. cd /opt/oracle/psft/dpk/puppet/production/manifests
2. PUPPET_DIR/puppet apply
--confdir=/opt/oracle/psft/dpk/puppet site.pp
--debug --trace --detailed-exitcodes
--logdest /some_valid_path/to/log/psft_dpk_setup.log
```

Exiting the PeopleSoft environment setup process.

Note. For Linux, *PUPPET_DIR* is /opt/puppetlabs/bin. For AIX, HP-UX, or Solaris, *PUPPET_DIR* is /opt/oracle/puppetlabs/bin.

Note. If you run step 2, the puppet apply step, it is a good idea to use a log name other than `psft_dpk_setup.log`, to differentiate the log from that for the DPK initialization.

See "Completing the DPK Initialization with Customizations."

Upon successful completion, the DPK setup script displays the following message:

Starting the Deployment of PeopleSoft Components:

```
Setting Up System Settings:           [ OK ]
Deploying Application Components:      [ OK ]
Deploying PeopleTools Components:     [ OK ]
```

The PeopleSoft Environment Setup Process Ended.

The complete setup log is written to the file `psft_dpk_setup.log` in the same location as the DPK setup script.

Task 2-6-3: Installing on Linux, AIX, HP-UX, or Solaris as a Non-Root User

If you are installing the PeopleSoft environment as a non-root user, ensure that you fulfill the prerequisites in the section Deploying as a Non-Root User on Linux, AIX, HP-UX, or Solaris.

To run the DPK setup script as a non-root user to deploy the software required to set up a PeopleSoft environment:

1. Open a terminal window and change directory to `DPK_INSTALL/setup`.
2. Run the script with the option for deployment only.
 - If you extracted the first zip file into the same directory where you downloaded the zip files, run the script as follows:


```
./psft-dpk-setup.sh --env_type midtier --deploy_only --deploy_type all
```
 - If you extracted the first zip file into a different directory, use the option `dpk_src_dir` to specify the location of the downloaded zip files, such as `DPK_INSTALL`, as follows:


```
./psft-dpk-setup.sh --dpk_src_dir DPK_INSTALL --env_type midtier ⇒
--deploy_only --deploy_type all
```
3. Answer `y` (yes) at the following prompt:


```
You are running DPK setup without root/administrator access.
This is fine as long as the system administrator has performed
all necessary tasks and all prerequisites have been met.
Please see the documentation to determine the prerequisite tasks
that need to be performed to successfully run DPK set up
without root/administrator privilege.
Would you like to proceed with the setup as a non-root user? [y/n]: y
```
4. Wait while the script verifies that the necessary PeopleSoft DPK zip files are available and that the Puppet software is installed.

The system displays messages indicating the steps in the setup process. The success or failure of each step is indicated by `[ OK ]` or `[FAILED]`.

```
Validating User Arguments:           [ OK ]
Validating PeopleSoft Supported Platform: [ OK ]
Verifying if Puppet Software is Installed: [ OK ]
```



```
Verifying if eYAML Hiera Backend is Installed:          [ OK ]
```

```
Preparing the Redhat Linux VM for PeopleSoft Environment:
```

```
Checking if PeopleSoft DPKs are Present:              [ OK ]
```

5. At the following prompt, enter a location that is accessible to the host to be used as the PeopleSoft base directory.

The base directory is used to extract the PeopleSoft DPKs as well as for deploying PeopleSoft components.

Use forward slashes (/) to specify the directory; for example, /opt/oracle/psft. Do not use a name for the base directory that begins with a number.

The base directory is used to extract the PeopleSoft DPKs. It is also used to deploy the PeopleSoft components. This directory should be accessible on the Linux VM, must have write permissions and should have enough free space.

```
.
Enter the PeopleSoft Base Directory: /opt/oracle/psft
Are you happy with your answer? [Y|n|q]: y
```

The script validates if there is enough free space available under the specified base directory for the PeopleSoft environment. The PeopleSoft environment setup is aborted if there is not enough free space. The script creates the directory if it does not exist.

Note. A mid-tier setup of a PeopleSoft environment requires about 25 GB of disk space.

```
Checking if the Base Directory has Enough Free Space:  [ OK ]
```

6. Enter a writable directory with at least 10 GB available space for *PS_CFG_HOME*.

The default is *USER_HOME*/psft/pt/8.57, where *USER_HOME* is the home directory for the logged-in user. The *PS_CFG_HOME* directory holds the configuration and log files for the PeopleSoft Application Server, Process Scheduler, and PIA domains.

```
Checking if Default User Home Directory /home is Writable: [WARNING]
```

The PeopleSoft environment setup creates local users on the Linux VM. The default Home directory [/home] do not have write permission to create the user's home directory. Please ensure this directory is writable or provide a new directory on the Linux VM that is writable.

```
Enter a directory on the Linux VM that is writable [/home]: /ds1
Are you happy with your answer? [y|n|q]:
```

7. Review the status messages as the script validates the files found in the download directory, *DPK_INSTALL* and extracts the DPK archives.

The script carries out validations for the mid-tier deployment. If any of the validations fail, the PeopleSoft environment setup is aborted.

Note. The messages have been truncated here for brevity.

```
Validating the PeopleSoft DPKs in the Linux VM:
[...]
```

```
Extracting the Peoplesoft DPK Archives in the Linux VM:
[...]
```

8. Review the status messages as the script sets up the Puppet file system.

The script sets up Puppet on the host. It then copies the PeopleSoft Puppet modules to the standard location (*BASE_DIR*\dpk) and updates the YAML files to reflect the type of PeopleSoft environment setup.

```
Setting up Puppet on the Linux VM:
Generating eYAML Hiera Backend Encryption Keys:           [ OK ]
Updating the Puppet Hiera YAML Files in the Linux VM:     [ OK ]
Updating the Role in Puppet Site File for the Linux VM:   [ OK ]
```

9. Specify the information for your database platform.

- a. For the database platform, enter DB2UNIX for DB2 for Linux, UNIX, and Windows.

```
Enter the PeopleSoft database platform [ORACLE]: DB2UNIX
```

- b. Enter y (yes) to indicate that the database you are connecting to is a Unicode database, or n (no) if it is a non-Unicode database.

```
Is the PeopleSoft database unicode? [Y|n]: y
```

10. Enter y if you want the DPK setup script to install files required for a multi-lingual installation.

```
Do you want Multi Language support in PeopleSoft database? [y|N]: n
```

11. Enter y to continue with the script.

```
Are you happy with your answers? [y|n]: y
Encrypting the Passwords in the User Data:           [ OK ]
Updating the Puppet Hiera YAML Files with User Data: [ OK ]
```

12. If you want to continue running the initialization script with the default configuration, answer y (yes) to the following prompt, and continue with the next step.

If you want to customize the PeopleSoft environment using the Puppet YAML files, answer n (no) to stop the script.

See "Completing the DPK Initialization with Customizations."

The bootstrap script is ready to deploy and configure the PeopleSoft environment using the default configuration defined in the Puppet Hiera YAML files. You can proceed by answering 'y' at the following prompt. And, if you want to customize the environment by overriding the default configuration, you can answer 'n'. If you answer 'n', you should follow the instructions in the PeopleSoft Installation Guide for creating the customization Hiera YAML file and running the Puppet 'apply' command directly to continue with the setup of the PeopleSoft environment

```
Do you want to continue with the default initialization process? [y|n]:
```

13. Review the status messages as the script runs Puppet profiles to set up the PeopleSoft environment.

A message of [OK] indicates that the profile has been applied successfully while a message [FAILED] indicates that the profile application failed.

The script stops and exits the first time a profile application fails, and displays an error message. This example shows the error message after the first step failed:

Starting the Deployment of PeopleSoft Components:

Setting Up System Settings: [FAILED]

The initialization of PeopleSoft environment setup failed. Check the log file [DPK_INSTALL/setup/psft_dpk_setup.log] for the errors. After correcting the errors, run the following commands to continue with the setup of PeopleSoft environment.

```
1. cd /opt/oracle/psft/dpk/puppet/production/manifests
2. PUPPET_DIR/puppet apply
--confdir=/opt/oracle/psft/dpk/puppet site.pp
--debug --trace --detailed-exitcodes
--logdest /some_valid_path/to/log/psft_dpk_setup.log
```

Exiting the PeopleSoft environment setup process.

Note. For Linux, *PUPPET_DIR* is /opt/puppetlabs/bin. For AIX or Solaris, *PUPPET_DIR* is /opt/oracle/puppetlabs/bin.

Note. If you run step 2, the puppet apply step, it is a good idea to use a log name other than psft_dpk_setup.log, to differentiate the log from that for the DPK initialization.

See "Completing the DPK Initialization with Customizations."

Upon successful completion, the DPK setup script displays the following message:

Starting the Deployment of PeopleSoft Components:

```
Setting Up System Settings:           [ OK ]
Deploying Application Components:     [ OK ]
Deploying PeopleTools Components:    [ OK ]
```

The PeopleSoft Environment Setup Process Ended.

The setup.log is written to the file <USER_HOME>/psft_dpk_work/psft_dpk_setup_<PID>.log, where <USER_HOME> is the home directory for the user running the script, and <PID> is a process ID.

Task 2-6-4: Reviewing the Installed Software

This section describes some of the files and folders installed by the script. These are the standard default locations. If you want to change the installation locations, see "Completing the DPK Initialization with Customizations."

The script creates the following three sub-directories under the user-specified base directory, *BASE_DIR*:

- *BASE_DIR*/pt

The script uses this directory to deploy the *PS_HOME* and *PS_APP_HOME* utilities and scripts, including the following:

- *PS_HOME* installed to the default location under the DPK base directory, *BASE_DIR*/pt/ps_home8.57.xx.
- *PS_HOME*/appserv/PSADMIN.exe
- *PS_HOME*/bin/client/winx86/pscfg.exe (Configuration Manager)

- *PS_HOME/bin/client/winx86/psdmt.exe* (Data Mover)
- *PS_HOME/bin/client/winx86/pside.exe* (Application Designer)
- *PS_HOME/scripts*
- *PS_HOME/setup/PsMpPIAInstall* (PeopleSoft Pure Internet Architecture installer)
- *PS_HOME/setup/PsMpDbInstall* (Database installer)
- *PS_HOME/setup/PsCA* (Change Assistant installer)
- *PS_HOME/setup/PsCIA* (Change Impact Analyzer installer)
- *PS_HOME/setup/PsMpWebAppDeployInstall* (Web Application Deployment installer)
- *PS_APP_HOME* installed to the default location under the DPK base directory, *BASE_DIR/pt/<Product>_app_home*, where *<Product>* is the abbreviation for the PeopleSoft application; for example, *hcm_app_home* for PeopleSoft Human Capital Management.

Note. The DPK setup requires a decoupled *PS_APP_HOME*; that is, the installation location of *PS_APP_HOME* is different from *PS_HOME*.

Files for the specific PeopleSoft application, including files needed for database creation.

If you answered yes when asked whether you wanted multi-language support during the DPK setup script process, the files required for translations are installed under *BASE_DIR/pt/<Product>_app_home*.

- Oracle Tuxedo software in the standard location, *<BASE_DIR>/pt/bea/tuxedo*
- Oracle Tuxedo services on Microsoft Windows:
ORACLE ProcMGR VS12.2.2.0.0_VS2015 and Tlisten VS12.2.2.0.0_VS2015
- Oracle WebLogic software in the standard location, *BASE_DIR/pt/bea/wlserver*
- Oracle database client software in the standard location, *BASE_DIR/pt/oracle-client*
- Java software in the standard location, *BASE_DIR/pt/jdk1.8.0_yy*, where *yy* is the JDK version.
- *BASE_DIR/dpk*
The script uses this directory to extract the archives from the PeopleSoft DPKs, and contains the Puppet YAML files for the deployment. Do not alter the installed Puppet YAML files.
See Completing the DPK Initialization with Customizations for information on creating a YAML file to customize the environment.
- *BASE_DIR/db*
This directory is not used for this deployment.

Task 2-7: Obtaining Operating System Packages Required by Puppet

The Puppet software used for the DPK deployment is dependent on certain OS-level packages, which may not be present in the delivered DPKs. In this case, you can use the information in the log file that is generated when you run the DPK setup script to determine which packages are needed. It is the responsibility of the user to obtain and install the required packages.

This is a one-time requirement, for a specific Puppet version, the first time the host is set up. If you are using a virtual machine, depending upon your organization's standards, you can add the missing packages to the standard OS from which you instantiate VMs, or create a custom OS image and re-use it later.

1. If you are using a virtual OS platform, create a new VM instance.

2. Use the DPK setup script, `psft-dpk-setup.bat` (Microsoft Windows), or `psft-dpk-setup.sh` (Linux, AIX, HP-UX, or Solaris) to deploy on the host.
3. Review the deployment log file in `DPK_INSTALL\setup`.
The log file will list any missing OS packages.
4. Remove the PeopleSoft environment created by the DPK deployment, using `psft-dpk-setup.bat --cleanup` (Microsoft Windows) or `psft-dpk-setup.sh --cleanup` (Linux, AIX, HP-UX, or Solaris).
5. If you are using a virtual OS platform, recreate the VM instance.
6. Obtain and load the missing OS packages on the new OS instance.
7. Rerun the DPK setup script.
The log file should not list any missing packages.

Task 2-8: Removing a Deployed PeopleSoft Environment

This section discusses:

- Understanding the Removal Process
- Using the DPK Setup Script to Remove the PeopleSoft Environment on Microsoft Windows
- Using the DPK Setup Script to Remove the PeopleSoft Environment on Linux, AIX, HP-UX, or Solaris
- Using the DPK Setup Script to Remove the PeopleSoft Environment on Linux, AIX, HP-UX, or Solaris as a Non-Root User
- Using Puppet to Remove the PeopleSoft Environment on Microsoft Windows
- Using Puppet to Remove the PeopleSoft Environment on Linux, AIX, HP-UX, or Solaris
- Troubleshooting the Removal Process on Microsoft Windows
- Troubleshooting the Removal Process on Linux, AIX, HP-UX, or Solaris

Understanding the Removal Process

There will be times when an existing PeopleSoft environment needs to be completely removed. For example, applying a new PeopleSoft PeopleTools patch requires that an existing environment be cleaned up and a new one created. The cleanup process described here conducts an orderly shutdown and removal of all the configured runtime domains — Application Server, Process Scheduler, and PIA domains. Additionally, it will remove all the deployed components. The PeopleSoft environment can be cleaned up either using the PeopleSoft DPK setup script or using a Puppet `apply` command. You can use the PeopleSoft DPK setup script cleanup for environments created with the default initialization or with the `psft_customizations.yaml` file.

Note. The Puppet software that is installed by the DPK setup script is not removed by the cleanup process.

Task 2-8-1: Using the DPK Setup Script to Remove the PeopleSoft Environment on Microsoft Windows

Use these steps to remove a deployed PeopleSoft environment using the PeopleSoft DPK setup script on Microsoft Windows:

1. Open a command prompt window; for example:

- Select Start, and navigate to Accessories, Command Prompt.
 - Right-click and select Run as Administrator.
2. Go to *DPK_INSTALL*\setup and run the following command:


```
psft-dpk-setup.bat --cleanup
```
 3. Specify the base directory (*BASE_DIR*) that you want to remove.

Enter the PeopleSoft Base Folder specified during setup:

You see this prompt only when there is more than one deployment. For example:

 - You carried out deployment A followed by deployment B.
 - You removed the second deployment B. For the cleanup of deployment B, you do not see this prompt for the *BASE_DIR*.
 - You run the script a second time. At the prompt, specify the *BASE_DIR* for deployment A.
 4. Review the cleanup log file in *DPK_INSTALL*\setup.

The DPK setup script displays [OK] for each step of the process, and [FAILED] if any of the steps are not successful. After completing these steps, verify that the DPK installation directories (*BASE_DIR*/pt and *BASE_DIR*/db) have been cleared. On Microsoft Windows, verify that any services have been removed. If anything remains, the cleanup process was not successful. Try running the process again, and if it is still not successful, you may need to carry out advanced cleanup.

See Troubleshooting the Removal Process on Microsoft Windows.

Task 2-8-2: Using the DPK Setup Script to Remove the PeopleSoft Environment on Linux, AIX, HP-UX, or Solaris

Use these steps to remove a deployed PeopleSoft environment using the PeopleSoft DPK setup script on Linux, AIX, HP-UX, or Solaris:

1. Open a terminal window as a user with root permission.
2. Go to *DPK_INSTALL*\setup and run the following command:


```
sh psft-dpk-setup.sh --cleanup
```
3. Specify the base directory (*BASE_DIR*) that you want to remove.

Enter the PeopleSoft Base Folder specified during setup:

You see this prompt only when there is more than one deployment. For example:

 - You carried out deployment A followed by deployment B.
 - You removed the second deployment B. For the cleanup of deployment B, you do not see this prompt for the *BASE_DIR*.
 - You run the script a second time. At the prompt, specify the *BASE_DIR* for deployment A.
4. Review the cleanup log file.

If you deployed as root, the cleanup log file is in *DPK_INSTALL*/setup.

The DPK setup script displays [OK] for each step of the process, and [FAILED] if any of the steps are not successful. After completing these steps, verify that the DPK installation directories (*BASE_DIR*/pt and *BASE_DIR*/db) have been cleared. On Linux, AIX, HP-UX, or Solaris, check for leftover processes. If anything remains, the cleanup process was not successful. Try running the cleanup process again, and if it is still not successful, you may need to carry out advanced cleanup.

See Troubleshooting the Removal Process on Linux, AIX, HP-UX, or Solaris.

Task 2-8-3: Using the DPK Setup Script to Remove the PeopleSoft Environment on Linux, AIX, HP-UX, or Solaris as a Non-Root User

If you deployed as a non-root user, after you use the `./psft-dpk-setup.sh --cleanup` command, you can find the cleanup log file in a directory of the deploying user's home directory, `USER_HOME`. The log file is appended with a process ID. For example, if the home directory is `/opt/userhome` and the PID is 1234, the cleanup log is `/opt/userhome/psft_dpk_work/psft_dpk_setup_cleanup_1234.log`.

If more than one non-root user deploys from the same `DPK_INSTALL`, the cleanup process will prompt for the correct `BASE_DIR`.

Task 2-8-4: Using Puppet to Remove the PeopleSoft Environment on Microsoft Windows

Use the `puppet apply` command to remove the PeopleSoft environment manually. When you run the `puppet apply --confdir=BASE_DIR/dpk/puppet site.pp --debug --trace` command, the debug and trace messages appear in the command prompt. If you want to save them as a file, see the Puppet Labs documentation for the correct options.

See Puppet Labs Documentation, <http://docs.puppetlabs.com>.

To remove the environment manually on Microsoft Windows:

1. Open the file `BASE_DIR/dpk/puppet/production/data/defaults.yaml` in a text editor, such as Notepad.
See "Using the Puppet Hiera YAML Files for Customization."
2. Change the value of the `ensure` attribute from `present` to `absent`.
3. Open a command prompt.
4. If the Puppet environment is not set, run the following command (optional):

```
C:\>"Program Files\Puppet Labs\Puppet\bin\puppet_shell.bat"
```

5. Change directory to the `BASE_DIR/dpk/puppet/production/manifests` folder.
6. Run the following command.

Supply a location and file name to save the log for the `-logdest` option. Note that when you use this option you do not see progress messages in the command prompt window. The process is complete when the prompt returns.

Note. The options require double dashes. The command text given here includes line feeds inserted for readability.

```
"C:\Program Files\Puppet Labs\Puppet\bin\puppet.bat" apply
--confdir=BASE_DIR/dpk/puppet site.pp
--debug --trace --detailed-exitcodes
--logdest <log_directory>/dpk/<log_file_name.log>
```

Task 2-8-5: Using Puppet to Remove the PeopleSoft Environment on Linux, AIX, HP-UX, or Solaris

To remove the environment manually on Linux, AIX, HP-UX, or Solaris:

1. Open the file *BASE_DIR*/dpk/puppet/production/data/defaults.yaml in a text editor, such as vi.
See "Using the Puppet Hiera YAML Files for Customization."
2. Change the value of the `ensure` attribute from `present` to `absent`.
3. Open a new session and log in as root.
4. Change directory to the *BASE_DIR*/dpk/puppet/production/manifests directory.
5. Run the following command.
Supply a location and file name to save the log for the `--logdest` option. Note that when you use this option you do not see progress messages in the command prompt window. The process is complete when the prompt returns.

Note. The options require double dashes. The command text given here includes line feeds inserted for readability.

On Linux:

```
/opt/puppetlabs/bin/puppet apply --confdir=BASE_DIR/dpk/puppet site.pp
--debug --trace --detailed-exitcodes
--logdest <log_directory>/dpk/<log_file_name.log>
```

On AIX, HP-UX, or Solaris:

```
/opt/oracle/puppetlabs/bin/puppet apply --confdir=BASE_DIR/dpk/puppet⇒
site.pp
--debug --trace --detailed-exitcodes
--logdest <log_directory>/dpk/<log_file_name.log>
```

Task 2-8-6: Troubleshooting the Removal Process on Microsoft Windows

This section includes advanced steps to be used only if the previous procedures in this section failed. If the cleanup process on Microsoft Windows was not totally successful, the *BASE_DIR* folders may not be entirely cleared, or you may have trouble when carrying out another deployment. Before carrying out the advanced steps in this section:

1. Run the command `psft-dpk-setup.bat --cleanup`.
2. If the script displays a `FAILED` message, run it again.
3. If it succeeds, check the *BASE_DIR* folders to be sure everything has been deleted.
4. If the *BASE_DIR* folders are not clear, or if a subsequent deployment is not successful, carry out the steps below.

For the advanced manual cleanup on Microsoft Windows, there are several steps. The steps in this section should be performed by someone familiar with modifying the Microsoft Windows registry. Depending upon where the cleanup process failed, some of the items mentioned in these steps may have already been removed. The user should remove whatever remains in this order:

1. Start Services.
2. Stop the services for the PeopleSoft application server, Process Scheduler, and PeopleSoft PIA domains, if necessary.
3. Open a command prompt, running as administrator, and remove the two database services and the PeopleSoft domains services with the commands:

```
sc delete PsftAppServerDomain<Appserver_domain_name>Service
```



```
sc delete PsftPrCsDomain<ProcSched_domain_name>Service
sc delete PsftPIADomain<PIA_domain_name>Service
```

4. In the Services window, stop ORACLE ProcMGR V12.2.2.0.0_VS2015 and TListen 12.2.2.0.0_VS2015(Port3050) by highlighting the names, right-clicking and selecting Stop.
5. In the Services window, right-click each of the services in step 5, select Properties, and copy the correct service name (rather than the alias).

6. Open a command prompt and remove the two preceding services with the command:

```
sc delete <service_name>
```

7. Open the Microsoft Windows registry; for example, select Start, Run, and enter regedit.
8. In the Registry Editor, locate the HKLM\SOFTWARE\ORACLE folder.

Select the following keys and verify that they contain references to the DPK installation locations in *BASE_DIR*:

- KEY_OraTux1222Home (*BASE_DIR*\pt\bea\tuxedo by default)
- KEY_OraWL12213Home (*BASE_DIR*\pt\bea by default)

9. In the Registry Editor, locate the HKLM\SOFTWARE\ORACLE\TUXEDO folder.

Select the 12.2.2.0.0_VS2015 key and verify that it contains references to the DPK installation locations in *BASE_DIR* (*BASE_DIR*\pt\bea\tuxedo by default).

10. In the Registry Editor, only for the keys from step 9 and 10 that reference the DPK installation locations, right-click and select Delete.
11. Close the Registry Editor window.
12. Open the file C:\Program Files\Oracle\Inventory\ContentsXML\inventory.xml in a text editor.
13. Locate the lines that reference the DPK deployment:

Note. This sample has been formatted for readability.

```
<HOME NAME="OraWL12213Home" LOC="C:/psft/pt/bea" TYPE="O" IDX="16"/>
<HOME NAME="OraTux1222Home" LOC="C:\psft\pt\bea\tuxedo" TYPE="O"
IDX="17"/>
```

14. Delete only the lines referencing the DPK deployment, and save the file.
15. Remove everything under the *BASE_DIR* folder (*BASE_DIR*\db, *BASE_DIR*\dpk, and *BASE_DIR*\pt).

Note. You may get a message that some of the file names are too big for the recycle bin. Click OK to accept.

16. Remove C:/User/<username>/psft/pt/8.57 (PS_CFG_HOME).

Task 2-8-7: Troubleshooting the Removal Process on Linux, AIX, HP-UX, or Solaris

This section includes advanced steps to be used only if the previous procedures in this section failed. If the cleanup process on Linux, AIX, HP-UX, or Solaris was not totally successful, the *BASE_DIR* folders may not be entirely cleared, or you may have trouble when carrying out another deployment. Before carrying out the advanced steps in this section:

1. Run the command `./psft-dpk-setup.sh --cleanup`.
2. If the script displays a FAILED message, run it again.

3. If it succeeds, check the *BASE_DIR* folders to be sure everything has been deleted.
4. If the *BASE_DIR* folders are not clear, or if a subsequent deployment is not successful, try the following troubleshooting steps.

Here are a few things to check for the advanced manual cleanup on Linux, AIX, HP-UX, or Solaris. Depending upon where the cleanup process failed, some of the items mentioned may have already been removed.

- Kill any left-over processes.

1. For example, use this command, and look for PeopleSoft processes:

```
ps -aux|more
```

2. To stop the processes, for example, use this command with the process ID:

```
kill -9 <PID>
```

- Check for left-over PeopleSoft users.

When you carry out the cleanup using the DPK setup script, it should remove the PeopleSoft users cleanly. However, if the users' home directory was deleted by mistake before running the cleanup, the user definition may remain.

1. Check for the five PeopleSoft user IDs using these commands:

```
id psadm1
id psadm2
id psadm3
id oracle2
id esadm1
```

If the commands give an output, it means the user exists.

2. Check for running processes associated with the users with this command:

```
ps -ef|grep <user_id>
```

3. Stop any running processes associated with the users, if necessary.

4. Delete the users, with this command:

```
userdel -r <user_id>
```

- Check for leftover directories on AIX.

On AIX if *BASE_DIR* is on NFS, you may not be able to use the command `rm` to remove the *BASE_DIR*. If so, check for the presence of a directory beginning with ".nfs" in *BASE_DIR*/pt/bea/oui/lib/aix_ppc64. Remove the *BASE_DIR*/pt/bea/oui/lib/aix_ppc64/.nfsxxx directory manually before deleting *BASE_DIR*.

Chapter 3

Completing the DPK Initialization with Customizations

This chapter discusses:

- Understanding PeopleSoft Environment Customizations
- Preparing Customization Files for Linux, AIX, HP-UX, or Solaris Users and Groups
- Preparing the Customization File for PeopleSoft Domain Definitions
- Preparing the Customization File to Create PeopleSoft Domains Without Configuration
- Preparing the Customization File for JDK on AIX
- Preparing the Customization File for JDK on HP-UX
- Preparing the Customization File for Component Software Locations
- Preparing the Customization File for Unicode
- Preparing the Customization File for the PeopleSoft Homes
- Preparing the Customization File for Jolt SSL and WSL SSL Ports
- Preparing the Customization File for Oracle HTTP Server
- Preparing the Customization File for Mid-Tier Connection to a DB2 for Linux, UNIX, and Windows Database
- Completing the Customized Deployment

Understanding PeopleSoft Environment Customizations

The PeopleSoft DPK setup script allows setup of a PeopleSoft environment quickly using the default data from the packaged Hiera YAML files. This section gives a few examples of ways to use the YAML files for customization, but is not meant to be an exhaustive list of the possible customizations.

Always use the documented procedures to make changes to your environment. Doing so will allow you to retain your customizations when removing a deployment before deploying a new patch or version.

Use these guidelines when customizing your environment:

- Do not change any of the original delivered YAML files.

This practice enables you to retain your customizations after deploying a new patch or update.

When you deploy the PeopleSoft DPKs, the YAML files associated with the deployment are installed in the following location:

- *BASE_DIR*/dpk/puppet/production/data/defaults.yaml
- *BASE_DIR*/dpk/puppet/production/data/psft_configuration.yaml
- *BASE_DIR*/dpk/puppet/production/data/psft_deployment.yaml

- `BASE_DIR/dpk/puppet/production/data/psft_unix_system.yaml`

- Start with the DPK setup script and choose not to continue with the default initialization.

Answer *no* at the prompt "Do you want to continue with the default initialization process? [y|n]:" to exit the script and bypass the default initialization process.

To set up a customized PeopleSoft environment, the DPK setup script can still be used to automate the tasks of extracting the DPK zip files, installing Puppet (if not installed), and copying the Puppet modules and Hieradata YAML files from the DPK into the location where Puppet looks for these files during the orchestration process.

- Always use the customizations for these setups:
 - Installing on an AIX operating system
 - Connecting to a non-Oracle RDBMS platform.
- Always create a `psft_customizations.yaml` file to use for modified parameters.

Never modify the delivered YAML files. Instead, copying the parameters that you want to modify into the `psft_customizations.yaml` file gives you the option to save the customization.

- Verify the content of the delivered YAML files with each release.

The YAML files may have changed since this document was published. It is important that you copy the appropriate section of code from the YAML files you install with each new deployment, and use it as the basis for your `psft_customizations.yaml` file.

- Do not create new parameters for `psft_customizations.yaml`.

The deployment recognizes only those parameters in the delivered YAML files or given in the product documentation.

- Use a single `psft_customizations.yaml` file.

You can copy sections from more than one of the delivered YAML files and include them in a single `psft_customizations.yaml` file.

- Use the same `psft_customizations.yaml` file for all deployments on a given base folder.

This applies to a use case in which you carry out more than one deployment on the same `BASE_DIR`. For example, you first install `PS_HOME` only, and use a `psft_customizations.yaml` file to specify a non-default `PS_HOME` location. Then you later do a second deployment, with the same `BASE_DIR`, to install mid-tier components, and you want to customize the location of Oracle WebLogic. In this case, use the first `psft_customizations.yaml` file, including the non-default `PS_HOME`, append the customization for the Oracle WebLogic location, and use it for the second deployment.

- Include the `remove: false` attribute to retain your customizations through the clean-up process.

To ensure that your customizations are not removed when removing a deployed environment:

- For each segment of customization parameters in the `psft_customizations.yaml` file, include the `remove: false` attribute at the end of the segment.
- If you remove the environment using the `puppet apply` command, set the `ensure` attribute to *absent* in `default.yaml`.

If you remove the environment using the `--cleanup` option for the PeopleSoft DPK setup script, you do not need to set the attribute first because it is part of the script process.

- Remove the environment using the `--cleanup` option for the PeopleSoft DPK setup script, as described in this documentation.

See "Installing the PeopleSoft Homes," Removing a Deployed PeopleSoft Environment.

- Copy an entire section containing the parameter to be modified, and be sure to retain the indentation from the delivered YAML file.

The hierarchy and alignment of the YAML files are very important to the correct operation. In addition to the brief overview given here, review the information in the appendix "Using the Puppet Hiera YAML Files for Customization."

- The YAML files include scalar type and collection type parameters.

Scalar parameters are of the form **key: value**; for example:

```
db_platform: ORACLE
```

Collection type parameters include a parameter name followed by one or more indented lists of **key: value** pairs. In this case, the value of the collection parameter is defined by the indented list of values; for example:

```
ps_home:
  db_type:      "%{hiera('db_platform')}}"
  unicode_db:   "%{hiera('unicode_db')}}"
  location:     "%{hiera('ps_home_location')}}"
```

- When you locate a parameter that you want to modify, be sure to locate the section heading that begins at the first column of the YAML file. This ensures that the deployment operation modifies the correct parameter.
- Be sure to retain the indentation from the delivered YAML file.

Typically there is an indentation of 2 or 3 spaces for each successive subsection. This is necessary in order for the parameters to be correctly interpreted.

Note. Be sure when copying and pasting that you retain the indentation. Depending upon the authoring or editing tools you use, the desired indentation may be lost when you copy and paste. It is a good idea to double-check the final `psft_customizations.yaml` file, especially for the special cases where you copy a sample from this documentation.

- When copying and modifying collection type parameters, use only spaces, not tabs, to indent the subsections.
- Use the encrypted passwords from the generated YAML files.

The DPK setup script encrypts user-supplied passwords and includes them in the generated YAML files. If you copy a section of a YAML file with encrypted passwords, do not replace or remove the encrypted text.

The encrypted passwords are quite long. Be sure to copy the entire string, without adding spaces, tabs, or line feeds.

Note. For the majority of the customizations described in this documentation, you copy the encrypted passwords from the generated YAML files. If that is not possible, see the appendix "Encrypting Passwords for Customizations on Linux, AIX, HP-UX, or Solaris."

- Replace the entire attribute string.

The parameters in the delivered YAML files are written with Hiera interpolation functions that act as variables. To modify each parameter, you must replace the entire string after the colon, and enclose your new value in double quotes. For example, in the `psft_deployment.yaml` file, the location for an Oracle WebLogic installation is given by the following parameters

```
weblogic_location: "%{hiera('pt_location')}/bea"
weblogic:
  location:  "%{hiera('weblogic_location')}"
```

The second Hiera function refers to the first. When `pt_location` is set as `C:/psft`, Oracle WebLogic will be installed in `C:/psft/bea`. To change this, remove both strings of text

"%{hiera('pt_location')}/bea" and "%{hiera('weblogic_location')}", and replace them with the full path to the new location. Retain the two-space indentation, and use a forward slash (/) for paths on both Microsoft Windows and Linux; for example:

On Microsoft Windows:

```
weblogic_location: "C:/psft/weblogic"
weblogic:
  location: "C:/psft/weblogic"
```

On Linux:

```
weblogic_location: "/opt/bea/weblogic"
weblogic:
  location: "/opt/bea/weblogic"
```

- Do not use the customizations to set up a non-Unicode environment if you are deploying the PeopleSoft Update Image DPKs for use with PeopleSoft Update Manager.

The environments for the PeopleSoft Update Images are required to be Unicode.

- Verify existing installations before beginning deployment.

You have the option to use existing installations, for example for Oracle WebLogic, but you have the responsibility to ensure that the installation is supported, complete, and correct. The deployment script does not verify whether an installation directory includes a valid, working installation.

- Set the Puppet environment if necessary.

The last step in the examples given in this chapter is to run the `puppet apply` command. If you receive a message saying that the term "puppet" is not recognized when running this command, it probably means that the Puppet software is not included in your system's path. You should also set the Puppet environment if you need to run `puppet apply` after the script execution has ended with an error.

- On Microsoft Windows, to set the Puppet environment, run this command:

```
"C:\Program Files\Puppet Labs\Puppet\bin\puppet_shell.bat"
```

- On Linux, specify the following environment variables before running the `puppet apply` command:

```
export PUPPET_DIR=/opt/puppetlabs
export PUPPET_BIN=${PUPPET_DIR}/bin
export PUPPET_LIB=${PUPPET_DIR}/lib
export PATH=${PUPPET_BIN}:${PATH}
export LD_LIBRARY_PATH=${PUPPET_LIB}:${LD_LIBRARY_PATH}
```

- On AIX or Solaris, specify the following environment variables before running the `puppet apply` command:

```
export PUPPET_DIR=/opt/oracle/puppetlabs
export PUPPET_BIN=${PUPPET_DIR}/bin
export PUPPET_LIB=${PUPPET_DIR}/lib
export PATH=${PUPPET_BIN}:${PATH}
export LIBPATH=${PUPPET_LIB}:${LIBPATH}
```

- On HP-UX, specify the following environment variables before running the `puppet apply` command:

```
export PUPPET_DIR=/opt/oracle/puppetlabs
export PUPPET_BIN=${PUPPET_DIR}/bin
export PUPPET_LIB=${PUPPET_DIR}/lib
export PATH=${PUPPET_BIN}:${PATH}
export SHLIB_PATH=${PUPPET_LIB}:${SHLIB_PATH}
```

```
export LD_LIBRARY_PATH=${PUPPET_LIB}:${LD_LIBRARY_PATH}
```

- On AIX, HP-UX, or Solaris operating systems, instead of using the export commands above, you can use the `pspuppet.sh` script to set the Puppet environment.

Use this method if the DPK setup script is interrupted, either intentionally to apply customizations, or by an error, and you need to proceed by running `puppet apply`. The script will set the Puppet PATH and LIBRARY environment variables. The `pspuppet.sh` script is installed by the DPK setup script in `/opt/oracle/puppetlabs`. Source the script by entering the following command:

```
. /opt/oracle/puppetlabs/pspuppet.sh
```

The dot, or period (".") at the beginning of the command is a source operator that ensures that the script commands persist in the shell environment that you are deploying from. After sourcing the script, continue with the deployment by running the `puppet apply` command.

- When using the customizations for a PeopleSoft web server domain, do not use the names PIA, PIA1, PIA2, or weblogic for the domain name.

The name of the WebLogic domain and the server and cluster names within it must be unique. The names PIA, PIA1, and PIA2 are reserved for use by the PeopleSoft system. The name weblogic is reserved for use by the Oracle WebLogic software. These restrictions apply to single server and multi-server domain creation.

See *Preparing the Customization File for PeopleSoft Domain Definitions*.

See *PeopleTools: System and Server Administration*, "WebLogic Domain Types."

- See the Puppet Labs documentation if you want to save the log files.

When you run the `--confdir=BASE_DIR/dpk/puppet site.pp --debug --trace` command, the debug and trace messages appear in the command prompt. If you want to save them as a file, see the Puppet Labs documentation for the correct options.

See Puppet Labs Documentation, <http://docs.puppetlabs.com>.

Task 3-1: Preparing Customization Files for Linux, AIX, HP-UX, or Solaris Users and Groups

This section discusses:

- Preparing the Customization File for a Single User and Single Group
- Preparing the Customization File for a New Single User, New Primary Group, and Existing Secondary Group
- Preparing the Customization File for Existing Users and Groups

Note. If you are running the DPK setup script as a non-root user, the customizations for users and groups in this section are not supported.

Note. If you want to set up your environment to use existing LDAP or existing users and groups on Linux, AIX, HP-UX, or Solaris, you must meet these requirements: 1) The user home directory should have read/write/execute permission for the root user. 2) The user default shell should be Bash.

Note. To use an encrypted password with one of the customization files in this section, note that the successful use of the encrypted password depends on the presence of the public and private keys in the `BASE_DIR/dpk/puppet` directory referred to in the `eyaml encrypt` command. You cannot save an encrypted password and use it with an installation with a different `BASE_DIR`.

Task 3-1-1: Preparing the Customization File for a Single User and Single Group

This user customization applies to Linux, AIX, HP-UX, and Solaris OS platforms only. If you choose the default initialization when running the DPK setup script, the Puppet framework creates local users and default groups, which are contained in the generated `psft_unix_system.yaml` file. Use the sample customization file in this section if you do not want to use the default users and groups, and instead want to set up your environment with a different single user and single group for the whole PeopleSoft environment. This user customization applies to the following scenarios:

- New single user + new single group
- New single user + existing single group
- Existing single user + new single group
- Existing single user + existing single group

Note. After completing the initialization, the system will prompt you to provide a new password the first time you log in. This requirement applies to both a new single user and an existing single user.

This customization will create a single user and single group. You must specify values for two parameters that are not included in the generated `psft_unix_system.yaml` file, `psft_user` and `psft_group`.

- `groups/psft_group`
 - Use the `groups/psft_group` collection parameter only if you want to create a group for a single user. The DPK process will create the group. If there is an existing group with the same name, the script will skip it.
 - Specify the same value for `groups/psft_group/name` and for `users/psft_user/gid`.
Use a group name (string), not a GID (number), for both the name in the group collection parameter, and the gid in the users collection parameter.
 - Note that you must use the parameters exactly as given in this documentation. If you try to create a different parameter name or alter the parameter, the DPK process will not recognize it.
- `users/psft_user`
 - Use the `users/psft_user` collection parameter to create a new user and add that user to the group specified by `groups/psft_group`.
 - This group is the primary group for the new user.
 - Specify the same value for `users/psft_user/name` and for the scalar parameter `psft_runtime_user_name`.
- `users/psft_user/home_dir`

When you run the DPK setup script, it includes a prompt for the users' home directory. That value is included in the generated `psft_unix_system.yaml` file. You can accept that same value in this customization file for `users/psft_user/home_dir`, or you can change it here. If you change it, the DPK process will create the new home directory.

To prepare the customization file:

1. Create a `psft_customizations.yaml` using a standard editing tool, such as `vi` on Linux, and save it in the same location as the `psft_unix_system.yaml` file.

By default, the DPK setup script installs the YAML files in `BASE_DIR/dpk/puppet/production/data`.

2. Use the sample below in creating the `psft_customizations.yaml` file, and modify the values as needed.

Note. Be sure that your final `psft_customizations.yaml` file includes the indentation shown here. The indentation may be lost if you copy from this documentation and paste into the file.

In this example, the new single user *newusr* will be created and assigned to the primary group *newgrp*.

```
---
groups:
  psft_group:
    name: newgrp
    remove: false

psft_runtime_user_name: newusr

users:
  psft_user:
    name: newusr
    gid: newgrp
    home_dir: /dpk_base/home/userhome
    password: ENC[PKCS7,MIIBeQYJKoZIhvcNA.....]
    remove: false
```

Important! Verify that you fulfill the following requirements:

- Ensure that the file begins with three dashes (- - -).
- Replace the password sample above with an encrypted password.

Enter the encrypted password on a single line. Do not include spaces or line feeds. See the instructions later in this documentation to generate the encrypted password.

See "Encrypting Passwords for Customizations on Linux, AIX, HP-UX, or Solaris."

3. Save the file.

Task 3-1-2: Preparing the Customization File for a New Single User, New Primary Group, and Existing Secondary Group

This user customization applies to Linux, AIX, HP-UX, and Solaris OS platforms only. If you choose the default initialization when running the DPK setup script, the Puppet framework creates local users and default groups, which are contained in the generated `psft_unix_system.yaml` file. Use the sample customization file in this section if you do not want to use the default users and groups, and instead want to set up your environment with a new single user assigned to two groups.

Note. After completing the initialization, the system will prompt you to provide a new password for the new user, the first time you log in.

This customization will create a new single user and a new group, the primary group. The new user is also assigned to an existing, secondary group. You must specify values for two parameters that are not included in the generated `psft_unix_system.yaml` file, `psft_user` and `psft_group`.

- `groups/psft_group`
 - Use the `groups/psft_group` collection parameter only if you want to create a new group for a single user. The DPK process will create the group. If there is an existing group with the same name, the script will skip it.
 - Specify the same value for `groups/psft_group/name` and for `users/psft_user/gid`.

Use a group name (string), not a GID (number), for both the name in the group collection parameter, and the gid in the users collection parameter.

- Note that you must use the parameters exactly as given in this documentation. If you try to create a different parameter name or alter the parameter, the DPK process will not recognize it.
- **users/psft_user**
 - Use the users/psft_user collection parameter to create a new user and add that user to the new group specified by groups/psft_group/name.
 - Specify the same value for users/psft_user/name and for the scalar parameter psft_runtime_user_name.
 - The new group specified by users/psft_user/gid and groups/psft_group/name is the primary group for the new user.
 - The existing group specified by users/psft_user/groups is the secondary group for the new user.
- **users/psft_user/home_dir**

When you run the DPK setup script, it includes a prompt for the users' home directory. That value is included in the generated psft_unix_system.yaml file. You can accept that same value in this customization file for users/psft_user/home_dir, or you can change it here. If you change it, the DPK process will create the new home directory.

To prepare the customization file:

1. Create a psft_customizations.yaml using a standard editing tool, such as vi on Linux, and save it in the same location as the psft_unix_system.yaml file.

By default, the DPK setup script installs the YAML files in *BASE_DIR*/dpk/puppet/production/data.

2. Use the sample below in creating the psft_customizations.yaml file, and modify the values as needed.

Note. Be sure that your final psft_customizations.yaml file includes the indentation shown here. The indentation may be lost if you copy from this documentation and paste into the file.

In this example, the new single user *newusr2* will be created and assigned to the newly created primary group *primgrp* and the existing secondary group *secgrp*.

```
---
groups:
  psft_group:
    name: primgrp
    remove: false

psft_runtime_user_name: newusr2

users:
  psft_user:
    name: newusr2
    gid: primgrp
    groups: secgrp
    home_dir: /dpk_base/home/userhome
    password: ENC[PKCS7,MIIBeQYJKoZIhvcNA.....]
    remove: false
```

Important! Verify that you fulfill the following requirements:

- Ensure that the file begins with three dashes (- - -).
- Replace the password sample above with an encrypted password.

Enter the encrypted password on a single line. Do not include spaces or line feeds. See the instructions later in this documentation to generate the encrypted password.

See "Encrypting Passwords for Customizations on Linux, AIX, HP-UX, or Solaris."

3. Save the file.

Task 3-1-3: Preparing the Customization File for Existing Users and Groups

This user customization applies to Linux, AIX, HP-UX, and Solaris OS platforms only. If you choose the default initialization, the Puppet framework creates default local users and groups. However, your security policies may prohibit creating these OS users. In such a scenario, you can override these default users using the customizations file. The customizations file can refer to one or more existing users or existing groups and Puppet will use them instead of the default users.

Note. After completing the initialization, the system will prompt you to provide a new password for the existing user, the first time you log in.

Ensure you fulfill these requirements:

- The users, groups, and GIDs that you specify in the `psft_customizations.yaml` file are present before you begin the installation.
 - Do not use the same name for the four group parameters. Ensure that the names that you specify for these parameters in `psft_cutomizations.yaml` are different.
 - `psft_runtime_group_name`
 - `psft_app_install_group_name`
 - `oracle_install_group_name`
 - `oracle_runtime_group_name`
 - The customizations file does not specify new passwords, because it is assumed that the passwords associated with the existing users will be used.
 - When you run the DPK setup script, you must specify a user home directory in which the existing user resides.
1. Locate the `psft_unix_system.yaml` file, which includes default users and groups.

By default, the DPK setup script installs the YAML files in `BASE_DIR/dpk/puppet/production/data`.

Note. The code examples in this topic are for illustrative purposes only. Remember to use the text from the YAML files you install with each new deployment as the basis for your `psft_customizations.yaml` file.

2. If necessary, create a `psft_customizations.yaml` using a standard editing tool, such as `vi` on Linux, and save it in the same location as the `psft_unix_system.yaml` file.

If this is the first entry in the `psft_customizations.yaml` file, ensure that there are three dashes (- - -) on the first line. Do not indent the dashes.

3. Copy the entire section for the users and groups from the `psft_unix_system.yaml` file into the `psft_customizations.yaml` file and modify the values as needed.

Note. Be sure that your final `psft_customizations.yaml` file includes the indentation from the generated YAML file. The indentation may be lost when you copy and paste.

For example:

```
---
```

```

psft_install_user_name:      psadm5
psft_runtime_user_name:      psadm6
psft_app_install_user_name:  psadm7
oracle_user_name:            oraclex3

psft_runtime_group_name:      psftrungrp
psft_app_install_group_name:  psftappgrp
oracle_install_group_name:    orainstgrp
oracle_runtime_group_name:    orarungrp

user_home_dir:    /data1/home
users:
  tools_install_user:
    name:          "%{hiera('psft_install_user_name')}}"
    gid:           orainstgrp
    groups:         "%{hiera('psft_runtime_group_name')}}"
    home_dir:       "%{hiera('user_home_dir')}/%{hiera('psft_install_user_⇒
name')}"

  psft_runtime_user:
    name:          "%{hiera('psft_runtime_user_name')}}"
    gid:           orainstgrp
    home_dir:       "%{hiera('user_home_dir')}/%{hiera('psft_runtime_user_⇒
name')}"

  app_install_user:
    name:          "%{hiera('psft_app_install_user_name')}}"
    gid:           psftappgrp
    home_dir:       "%{hiera('user_home_dir')}/%{hiera('psft_app_install_user_⇒
name')}"

  oracle_user:
    name:          "%{hiera('oracle_user_name')}}"
    gid:           orainstgrp
    home_dir:       "%{hiera('user_home_dir')}/%{hiera('oracle_user_name')}"

  es_user:
    name:          esuserx3
    gid:           users
    home_dir:       /data1/home/esuserx3

```

- The four default users psadm1, psadm2, psadm3, and oracle2 have been replaced by psadm5, psadm6, psadm7, and oraclex3, respectively.
- The oracle_install_group_name has been replaced by orainstgrp. This group is the primary group for the oracle_user, psft_runtime_user, and tools_install_user.
- The tools_install_user must belong to the psft runtime group as a secondary group. To satisfy this requirement, the value for users/tools_install_user/groups is set to the interpolation function "%{hiera('psft_runtime_group_name')}".
- The default psft_app_install_group_name has been replaced by psftappgrp. This group is the primary group for the app_install_user.

4. Save the file.

Task 3-2: Preparing the Customization File for PeopleSoft Domain Definitions

This section discusses:

- Preparing the `psft_customizations.yaml` file
- Reviewing the Domain Definitions in `psft_configuration.yaml`
- Reviewing the Customization File for a Single Application Server Domain
- Reviewing the Customization File for an Application Server Domain with Custom `PS_CFG_HOME`
- Reviewing the Customization File for a PIA Domain on a Separate Host
- Reviewing the Customization File for Multiple Domains

Task 3-2-1: Preparing the `psft_customizations.yaml` file

Use this information if you want to customize the PeopleSoft domains — the application server, Process Scheduler, and PIA domains. For example, you may want to create multiple Application Server domains rather than a single domain.

Note. As mentioned, do not use the names PIA, PIA1, PIA2, or weblogic to create a PIA (web server) domain.

1. Locate the `psft_configuration.yaml` file, which was installed by the deployment, in `BASE_DIR/dpk/puppet/production/data`.

Note. The code examples in this topic are for illustrative purposes only. Remember to use the text from the YAML files you install with each new deployment as the basis for your `psft_customizations.yaml` file.

2. If necessary, create a `psft_customizations.yaml` using a standard editing tool, such as Notepad on Microsoft Windows or vi on Linux, AIX, HP-UX, or Solaris, and save it in the same location as the `psft_configuration.yaml` file.

If this is the first entry in the `psft_customizations.yaml` file, ensure that there are three dashes (- - -) on the first line of the file. Do not indent the dashes.

3. Copy the sections that you want to customize from the `psft_configuration.yaml` file into the `psft_customizations.yaml` file and modify the values as needed.

The following sections include sample `psft_customizations.yaml` files.

4. Save the file.

Task 3-2-2: Reviewing the Domain Definitions in `psft_configuration.yaml`

To customize the PeopleSoft domains, you begin with the `psft_configuration.yaml` file, which lists the attributes pertinent to the PeopleSoft domains.

Note. The `psft_configuration.yaml` file includes definitions for Automated Configuration Manager (ACM) plug-ins, which configure components such as Integration Broker and Report Distribution. Depending upon the PeopleSoft domain being set up, certain ACM configurations will run as part of the deployment.

This sample shows a portion of a `psft_configuration.yaml` file, with annotations added (marked by `###`) for the purposes of this explanation. The default application server name, `APPDOM`, is defined in the first portion of the file for the parameter `appserver_domain_name`, which is then referenced with an interpolation token `"{%hiera('appserver_domain_name')}"` in the `appserver_domain_list` section.

The DPK setup script encrypts user-supplied passwords and includes them in the generated YAML files. The encrypted text will be a long single line of letters and numbers. Be sure to copy the text in one unbroken line, with no spaces or line feeds. This sample includes short strings of text beginning with "ENC" to represent encrypted passwords.

```
---
db_name:          FS85706C
db_user:          VP1

#####
# Replace this password sample with encrypted text from the #
# generated psft_configuration.yaml file.                  #
#####
db_user_pwd:      ENC[xxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx]
db_connect_id:    people

#####
# Replace this password sample with encrypted text from the #
# generated psft_configuration.yaml file.                  #
#####
db_connect_pwd:   ENC[xxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx]

domain_user:      "%{hiera('psft_runtime_user_name')}}"
ps_config_home:   "C:/Users/%{::env_username}/psft/pt/8.57"
appserver_template: small
appserver_domain_name: APPDOM
prcs_domain_name: PRCSDOM
prcs_domain_id:   "PRCS%{::rand}"
report_node_name: "%{hiera('prcs_domain_id')}}"
pia_domain_name:  peoplesoft
pia_site_name:    ps
pia_http_port:    8000
pia_https_port:   8443
jolt_port:        9033
wsl_port:         7000
db_port:          1521
gateway_node_name: QE_LOCAL
pia_gateway_user: administrator

#####
# Replace this password sample with encrypted text from the #
# generated psft_configuration.yaml file.                  #
#####
pia_gateway_user_pwd: ENC[xxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx]

webserver_type:   weblogic
pia_webprofile_name: PROD
pia_psserver_list: "%{::fqdn}:%{hiera('jolt_port')}}"
report_repository_dir: "%{hiera('ps_config_home')}/psreports"
```

```
#####
# Replace this password sample with encrypted text from the #
# generated psft_configuration.yaml file. #
#####
domain_conn_pwd:      ENC[xxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx]

help_uri:              pt854pbh1
tns_dir:               "%{hiera('db_location')}}"
tns_admin_list:
  "%{hiera('db_name')}}" :
    db_host:            "%{::fqdn}"
    db_port:            "%{hiera('db_port')}}"
    db_protocol:        TCP
    db_service_name:    "%{hiera('db_name')}}"

db2_server_list:
  "%{hiera('db_name')}}" :
    db2_type:           "%{hiera('db_platform')}}"
    db2_host:           "%{::fqdn}"
    db2_port:           "%{hiera('db_port')}}"
    db2_node:           TCPLNX01
    db2_target_db:      "%{hiera('db_name')}}"

mssql_server_list:
  "%{hiera('db_name')}}" :
    mss_server_name:    "%{::fqdn}"
    mss_odbc_name:      "ODBC Driver 11 for SQL Server"

#####
# Copy the entire section beginning here for #
# application server customization. #
#####

appserver_domain_list:
  "%{hiera('appserver_domain_name')}}" :
    os_user:            "%{hiera('domain_user')}}"
    ps_cfg_home_dir:    "%{hiera('ps_config_home')}}"
    template_type:      "%{hiera('appserver_template')}}"

db_settings:
  db_name:              "%{hiera('db_name')}}"
  db_type:              "%{hiera('db_platform')}}"
  db_opr_id:            "%{hiera('db_user')}}"
  db_opr_pwd:           "%{hiera('db_user_pwd')}}"
  db_connect_id:        "%{hiera('db_connect_id')}}"
  db_connect_pwd:       "%{hiera('db_connect_pwd')}}"

config_settings:
  Domain Settings/Domain ID:  "%{hiera('appserver_domain_name')}}"
  PSAPPSRV/Min Instances:     2
  PSAPPSRV/Max Instances:     2
  PSAPPSRV/Max Fetch Size:    15000
  Security/DomainConnectionPwd: "%{hiera('domain_conn_pwd')}}"
```

```

JOLT Listener/Port:           "%{hiera('jolt_port')}}"
JOLT Listener/Address:        0.0.0.0
Workstation Listener/Port:    "%{hiera('wsl_port')}}"

feature_settings:
  PUBSUB:                      "Yes"
  QUICKSRV:                    "No"
  QUERYSRV:                    "No"
  JOLT:                        "Yes"
  JRAD:                        "No"
  WSL:                         "Yes"
  DBGSRV:                      "No"
  RENSrv:                      "No"
  MCF:                         "No"
  PPM:                         "Yes"
  PSPMSRV:                     "Yes"
  ANALYTICSRV:                 "No"
  SERVER_EVENTS:               "Yes"
  DOMAIN_GW:                   "No"
#####
# End application server section.                                     #
#####

#####
# Copy the entire section beginning here for                         #
# Process Scheduler customization                                    #
#####

prcs_domain_list:
  "%{hiera('prcs_domain_name')}":
    os_user:                    "%{hiera('domain_user')}}"
    ps_cfg_home_dir:           "%{hiera('ps_config_home')}}"

db_settings:
  db_name:                     "%{hiera('db_name')}}"
  db_type:                     "%{hiera('db_platform')}}"
  db_opr_id:                   "%{hiera('db_user')}}"
  db_opr_pwd:                   "%{hiera('db_user_pwd')}}"
  db_connect_id:               "%{hiera('db_connect_id')}}"
  db_connect_pwd:              "%{hiera('db_connect_pwd')}}"

config_settings:
  Process Scheduler/PrCsServerName: "%{hiera('prcs_domain_id')}}"
  Security/DomainConnectionPwd:      "%{hiera('domain_conn_pwd')}}"

feature_settings:
  MSTRSRV:                      "Yes"
  APPENG:                       "Yes"
#####
# End Process Scheduler section.                                     #
#####

#####

```



```

# Copy the entire section beginning here for PIA customization.      #
#####
pia_domain_list:
  "%{hiera('pia_domain_name')}":
    os_user:                "%{hiera('domain_user')}}"
    ps_cfg_home_dir:        "%{hiera('ps_config_home')}}"
    gateway_user:           "%{hiera('pia_gateway_user')}}"
    gateway_user_pwd:       "%{hiera('pia_gateway_user_pwd')}}"
    auth_token_domain:      ":%{::domain}"

    webserver_settings:
      webserver_type:        "%{hiera('webserver_type')}}"
      webserver_home:        "%{hiera('weblogic_location')}}"
      webserver_admin_user:  system
      webserver_admin_user_pwd: ENC[xxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx]

#####
# Replace this password sample with encrypted text from the #
# generated psft_configuration.yaml file.                  #
#####

    webserver_admin_port:    "%{hiera('pia_http_port')}}"
    webserver_http_port:     "%{hiera('pia_http_port')}}"
    webserver_https_port:    "%{hiera('pia_https_port')}}"

site_list:
  "%{hiera('pia_site_name')}":
    appserver_connections: "%{hiera('pia_psserver_list')}}"
    domain_conn_pwd:        "%{hiera('domain_conn_pwd')}}"

    webprofile_settings:
      profile_name:          "%{hiera('pia_webprofile_name')}}"
      profile_user:          PTWEBSERVER
      profile_user_pwd:      ENC[xxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx]

#####
# Replace this password sample with encrypted text from the #
# generated psft_configuration.yaml file.                  #
#####

    report_repository_dir: "%{hiera('report_repository_dir')}}"
#####
# End PIA section.                                          #
#####

ohs_domain:
  name:                ohsdom

#####
# Remaining text removed for brevity.                      #
#####

```

Task 3-2-3: Reviewing the Customization File for a Single Application Server Domain

This sample shows a `psft_customizations.yaml` file for a single application server domain with the domain name APPDOM1. Note that the indentation in the original `psft_configuration.yaml` file must be maintained when creating a `psft_customizations.yaml` file.

Note. Do not modify the `ps_cfg_home_dir` parameter. It must be the same as `ps_config_home` for this customization. If you want to customize the `PS_CFG_HOME` location, see the next section.

```
---
appserver_domain_list:

### Custom domain name ###
"APPDOM1":
  os_user:           "%{hiera('domain_user')}}"
  template_type:     "%{hiera('appserver_template')}}"

  ### Do not change the ps_cfg_home_dir parameter. ###
  ps_cfg_home_dir:  "%{hiera('ps_config_home')}}"

db_settings:
  db_name:           "%{hiera('db_name')}}"
  db_type:           "%{hiera('db_platform')}}"
  db_opr_id:         "%{hiera('db_user')}}"
  db_opr_pwd:        "%{hiera('db_user_pwd')}}"
  db_connect_id:     "%{hiera('db_connect_id')}}"
  db_connect_pwd:    "%{hiera('db_connect_pwd')}}"

config_settings:
  Domain Settings/Domain ID:      IBUPG0
  PSAPPSRV/Min Instances:         3
  PSAPPSRV/Max Instances:         5
  JOLT Listener/Port:             "%{hiera('jolt_port')}}"
  Workstation Listener/Port:      "%{hiera('wsl_port')}}"

feature_settings:
  PUBSUB:              "Yes"
  QUICKSRV:            "No"
  QUERYSRV:            "No"
  JOLT:                "Yes"
  JRAD:                "No"
  WSL:                 "Yes"
  DBGSRV:              "No"
  RENSrv:              "No"
  MCF:                 "No"
  PPM:                 "Yes"
  PSPPMsRV:            "Yes"
  ANALYTICSrv:         "No"
  SERVER_EVENTS:       "Yes"
```

```
DOMAIN_GW:      "No"
```

Task 3-2-4: Reviewing the Customization File for an Application Server Domain with Custom PS_CFG_HOME

If you want to create PeopleSoft domains in a non-default *PS_CFG_HOME* location, you must specify the desired value for the scalar parameter *ps_config_home* outside the *appserver_domain_list* section. Enter the same values for *ps_config_home* and *ps_cfg_home_dir*.

```
---
```

```
### Custom PS_CFG_HOME location ###
ps_config_home:      C:/user/psft_config/8.57

appserver_domain_list:

### Custom domain name ###
"APPDOM2":
  os_user:            "%{hiera('domain_user')}}"
  template_type:      "%{hiera('appserver_template')}}"

### Custom PS_CFG_HOME location, same as ps_config_home. ###
ps_cfg_home_dir:     C:/user/psft_config/8.57

db_settings:
  db_name:             "%{hiera('db_name')}}"
  db_type:             "%{hiera('db_platform')}}"
  db_opr_id:           "%{hiera('db_user')}}"
  db_opr_pwd:          "%{hiera('db_user_pwd')}}"
  db_connect_id:       "%{hiera('db_connect_id')}}"
  db_connect_pwd:      "%{hiera('db_connect_pwd')}}"

config_settings:
  Domain Settings/Domain ID:      IBUPG0
  PSAPPSRV/Min Instances:          3
  PSAPPSRV/Max Instances:          5
  JOLT Listener/Port:              "%{hiera('jolt_port')}}"
  Workstation Listener/Port:       "%{hiera('wsl_port')}}"

feature_settings:
  PUBSUB:                  "Yes"
  QUICKSRV:                "No"
  QUERYSRV:                "No"
  JOLT:                    "Yes"
  JRAD:                    "No"
  WSL:                     "Yes"
  DBGSRV:                  "No"
  RENSRV:                  "No"
  MCF:                     "No"
  PPM:                     "Yes"
  PSPPMRSRV:               "Yes"
  ANALYTICSRV:             "No"
```

```
SERVER_EVENTS: "Yes"
DOMAIN_GW:     "No"
```

Task 3-2-5: Reviewing the Customization File for a PIA Domain on a Separate Host

If you want to set up an environment in which the PIA domain and web server are not on the same machine as the application server domain, you must use customizations to specify the machine where the application server is installed. This customization is required for the Integration Broker configuration.

The generated `psft_configuration.yaml` includes the following parameter, which sets the host for Integration Broker to the PIA host, which by default is the machine where the DPK setup script is run:

```
env.ib_appserver_host:           "%{hiera('pia_host_name')}}"
```

If you use the DPK setup script to set up a PIA domain only, and the PIA domain is not on the same machine as your application server domain, the value for the `env.ib_appserver_host` parameter must be set to application server machine name.

See "Deploying the PeopleSoft PeopleTools Deployment Packages," Running the DPK Setup Script to Deploy a PIA Domain.

Copy the entire `component_postboot_setup_list` collection section from `psft_configuration.yaml` and paste it into `psft_customizations.yaml`. Change the value for `env.ib_appserver_host` to point to the host where the application server is set up, for example `ps_app_server1`.

This sample shows a sample `psft_customizations.yaml` file, with annotations added (marked by `###`) for the purposes of this explanation.

```
---
component_postboot_setup_list:
  integration_broker:
    run_control_id:      intbroker
    os_user:             "%{hiera('domain_user')}}"

  db_settings:
    db_name:             "%{hiera('db_name')}}"
    db_type:             "%{hiera('db_platform')}}"
    db_opr_id:           "%{hiera('db_user')}}"
    db_opr_pwd:          "%{hiera('db_user_pwd')}}"
    db_connect_id:       "%{hiera('db_connect_id')}}"
    db_connect_pwd:      "%{hiera('db_connect_pwd')}}"

  acm_plugin_list:
    PTIBActivateDomain:
      domain.activate_retry_count: 10
      domain.activate_wait_time:   10

    PTIBConfigureGatewayNodes:
      env.gateway_host:             "%{hiera('pia_host_name')}}"
      env.gateway_port:             "%{hiera('pia_http_port')}}"
      env.gateway_ssl_port:         "%{hiera('pia_https_port')}}"
      env.use_ssl_gateway:          false
      env.default_local_node:       "%{hiera('gateway_node_name')}}"
      env.gateway_user:             "%{hiera('pia_gateway_user')}}"
```

```

    env.gateway_password:                "%{hiera('pia_gateway_user_⇒
pwd')}}"

###Custom application server name ###
    env.ib_appserver_host:                ps_app_server1
    env.ib_jolt_port:                     "%{hiera('jolt_port')}}"
    env.ib_node_proxy_userid:             "%{hiera('db_user')}}"
    env.ib_node_proxy_password:           "%{hiera('db_user_pwd')}}"
    env.tools_release:                    "%ToolsRelease"
    env.ib_appserver_domain_password:     "%{hiera('domain_conn_pwd')}}"
    env.ib_set_as_default_node:            true

PTIBConfigureGatewayProperties:
    env.gateway_keystore_password:        password

PTWebServerConfigUpdate:
    env.domainname:                       "%{hiera('pia_domain_name')}}"
    env.sitename:                         "%{hiera('pia_site_name')}}"
    env.piahome:                          "%{hiera('ps_config_home')}}"
    env.psserver:                         ""
    env.KeyStorePwd:                      ""

acm_plugin_order:
- PTIBActivateDomain
- PTIBConfigureGatewayNodes
- PTIBConfigureGatewayProperties
- PTWebServerConfigUpdate

```

Task 3-2-6: Reviewing the Customization File for Multiple Domains

For multiple domains, duplicate the entire domain section, again maintaining the indentation from the original `psft_configuration.yaml` file. This sample shows a `psft_customizations.yaml` file for two application server domains, two PIA domains, and two Process Scheduler domains, with annotations added (marked by `###` characters) for the purposes of this explanation.

Follow these guidelines in creating a `psft_customizations.yaml` file for customized PeopleSoft domains. The letters correspond to those in the code sample above:

- (A) For more than one application server, include the `pia_psserver_list` entry at the top of the `psft_customizations.yaml` definitions. List the application server domains that are used by the PIA domains, using the format `<application_server_host>:<Jolt port>`. Separate the entries with a comma.
- (B) Copy the entire section for the domains that you want to customize.
- (C) Specify unique names for each domain.
- (D) Specify unique ports for each domain.
- (E) If specifying more than one application server domain, you must configure the REN server to use a unique port by setting the attribute `PSRENSRV/default_http_port` to a value other than the default, 7180 in the `psft_customizations.yaml`.

Note. The REN server setting is also a requirement for a traditional PeopleSoft installation when setting up more than one application server on a single machine.

- (F) If specifying more than one Process Scheduler domain, you must specify unique Process Scheduler server

names.

In this sample, the first Process Scheduler server uses the default value, which is defined as an interpolation token. The second Process Scheduler server has a different name, PRCS222.

(G) In addition, the Master Scheduler Server should be enabled for the first Process Scheduler domain (MSTRSRV: "Yes"), and disabled for subsequent Process Scheduler domains (MSTRSRV: "No").

See *PeopleTools: Process Scheduler*, "Understanding PeopleSoft Master Scheduler Server."

- (H) If specifying more than one PIA domain, you must specify different site names for each.

In this sample, the first PIA site name uses the default value, which is defined as an interpolation token. The second PIA site name has a different name, ps222.

```

---
pia_psserver_list:      "hostname.example.com:9033,hostname.example.com:9043"
### (A) ###

appserver_domain_list:
  "APPD0M111":          ### (B), (C) ###
    os_user:             "%{hiera('domain_user')}}"
    template_type:       "%{hiera('appserver_template')}}"
    ps_cfg_home_dir:     "%{hiera('ps_config_home')}}"

    db_settings:
      db_name:            "%{hiera('db_name')}}"
      db_type:            "%{hiera('db_platform')}}"
      db_opr_id:          "%{hiera('db_user')}}"
      db_opr_pwd:         "%{hiera('db_user_pwd')}}"
      db_connect_id:      "%{hiera('db_connect_id')}}"
      db_connect_pwd:     "%{hiera('db_connect_pwd')}}"

    config_settings:
      Domain Settings/Domain ID:    IBUPG0
      PSAPPSRV/Min Instances:        3
      PSAPPSRV/Max Instances:        5
      JOLT Listener/Port:            9033          ### (D) ###
      Workstation Listener/Port:     7000          ### (D) ###

    feature_settings:
      PUBSUB:                    "Yes"
      QUICKSRV:                  "No"
      QUERYSRV:                  "No"
      JOLT:                      "Yes"
      JRAD:                      "No"
      WSL:                       "Yes"
      DBGSRV:                    "No"
      RENSrv:                    "No"
      MCF:                       "No"
      PPM:                       "Yes"
      PSPMSRV:                   "Yes"
      ANALYTICSRV:               "No"
      SERVER_EVENTS:             "Yes"
      DOMAIN_GW:                 "No"

```

```

"APPDOM222":
    os_user:          "%{hiera('domain_user')}}"
    template_type:    "%{hiera('appserver_template')}}"
    ps_cfg_home_dir:  "%{hiera('ps_config_home')}}"

    db_settings:
        db_name:      "%{hiera('db_name')}}"
        db_type:      "%{hiera('db_platform')}}"
        db_opr_id:     "%{hiera('db_user')}}"
        db_opr_pwd:    "%{hiera('db_user_pwd')}}"
        db_connect_id: "%{hiera('db_connect_id')}}"
        db_connect_pwd: "%{hiera('db_connect_pwd')}}"

    config_settings:
        Domain Settings/Domain ID:    IBUPG0
        PSAPPSRV/Min Instances:        3
        PSAPPSRV/Max Instances:        5
        JOLT Listener/Port:            9043
        Workstation Listener/Port:     7001
        PSRENSRV/default_http_port:    7191

    feature_settings:
        PUBSUB:      "Yes"
        QUICKSRV:    "No"
        QUERYSRV:    "No"
        JOLT:        "Yes"
        JRAD:        "No"
        WSL:         "Yes"
        DBGSRV:      "No"
        RENSrv:      "No"
        MCF:         "No"
        PPM:         "Yes"
        PSPPMsRV:    "Yes"
        ANALYTICSrv: "No"
        SERVER_EVENTS: "Yes"
        DOMAIN_GW:   "No"

pia_domain_list:
    "PIADOM111":
        os_user:          "%{hiera('domain_user')}}"
        ps_cfg_home_dir:  "%{hiera('ps_config_home')}}"
        gateway_user:     "%{hiera('pia_gateway_user')}}"
        gateway_user_pwd: "%{hiera('pia_gateway_user_pwd')}}"
        auth_token_domain: ".%{:domain}"

    webserver_settings:
        webserver_type:    "%{hiera('webserver_type')}}"
        webserver_home:    "%{hiera('weblogic_location')}}"
        webserver_admin_user: system
        webserver_admin_user_pwd: ENC[xxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx]

#####

```

```

# Replace this password sample with encrypted text from the #
# generated psft_configuration.yaml file. #
#####

    webserver_admin_port:      8000          ### (D) ###
    webserver_http_port:      8000          ### (D) ###
    webserver_https_port:     8443          ### (D) ###

site_list:
  "%{hiera('pia_site_name')}":          ### (H) ###
    appserver_connections: "%{hiera('pia_psserver_list')}"
    domain_conn_pwd:       "%{hiera('domain_conn_pwd')}"

    webprofile_settings:
      profile_name:        "%{hiera('pia_webprofile_name')}"
      profile_user:        PTWEBSEVER
      profile_user_pwd:    ENC[xxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx]

#####
# Replace this password sample with encrypted text from the #
# generated psft_configuration.yaml file. #
#####

    report_repository_dir: "%{hiera('report_repository_dir')}"

"PIADOM222":          ### (B), (C) ###
  os_user:            "%{hiera('domain_user')}"
  ps_cfg_home_dir:    "%{hiera('ps_config_home')}"
  gateway_user:       "%{hiera('pia_gateway_user')}"
  gateway_user_pwd:   "%{hiera('pia_gateway_user_pwd')}"
  auth_token_domain:  ".%{::domain}"

  webserver_settings:
    webserver_type:    "%{hiera('webserver_type')}"
    webserver_home:    "%{hiera('weblogic_location')}"
    webserver_admin_user: system
    webserver_admin_user_pwd: ENC[xxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx]

#####
# Replace this password sample with encrypted text from the #
# generated psft_configuration.yaml file. #
#####

    webserver_admin_port:      8002          ### (D) ###
    webserver_http_port:      8002          ### (D) ###
    webserver_https_port:     8445          ### (D) ###

site_list:
  "ps222":          ### (H) ###
    appserver_connections: "%{hiera('pia_psserver_list')}"
    domain_conn_pwd:       "%{hiera('domain_conn_pwd')}"

    webprofile_settings:

```



```

        profile_name:      "%{hiera('pia_webprofile_name')}}"
        profile_user:      PTWEBSERVER
        profile_user_pwd:  ENC[xxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx]

#####
# Replace this password sample with encrypted text from the #
# generated psft_configuration.yaml file.                  #
#####

        report_repository_dir: "%{hiera('report_repository_dir')}}"

prcs_domain_list:
  "PRCSDOM111":
    os_user:      "%{hiera('domain_user')}}"
    ps_cfg_home_dir: "%{hiera('ps_config_home')}}"

    db_settings:
      db_name:      "%{hiera('db_name')}}"
      db_type:      "%{hiera('db_platform')}}"
      db_opr_id:    "%{hiera('db_user')}}"
      db_opr_pwd:   "%{hiera('db_user_pwd')}}"
      db_connect_id: "%{hiera('db_connect_id')}}"
      db_connect_pwd: "%{hiera('db_connect_pwd')}}"

    config_settings:
      Process Scheduler/PrcsServerName: "%{hiera('prcs_domain_id')}}" ###=>
(F) ###
      Security/DomainConnectionPwd:    "%{hiera('domain_conn_pwd')}}"

    feature_settings:
      MSTRSRV:      "Yes"                      ### (G) ###
      APPENG:       "Yes"

  "PRCSDOM222":
    os_user:      "%{hiera('domain_user')}}"
    ps_cfg_home_dir: "%{hiera('ps_config_home')}}"

    db_settings:
      db_name:      "%{hiera('db_name')}}"
      db_type:      "%{hiera('db_platform')}}"
      db_opr_id:    "%{hiera('db_user')}}"
      db_opr_pwd:   "%{hiera('db_user_pwd')}}"
      db_connect_id: "%{hiera('db_connect_id')}}"
      db_connect_pwd: "%{hiera('db_connect_pwd')}}"

    config_settings:
      Process Scheduler/PrcsServerName: PRC222                      ### (F) ###
      Security/DomainConnectionPwd:    "%{hiera('domain_conn_pwd')}}"

    feature_settings:
      MSTRSRV:      "No"                      ### (G) ###
      APPENG:       "Yes"

```

Task 3-3: Preparing the Customization File to Create PeopleSoft Domains Without Configuration

The default DPK initialization includes pre-boot and post-boot processes that use Automated Configuration Manager (ACM) plug-ins to configure and start the PeopleSoft domains. The ACM configuration, for example, sets up Integration Broker and the report repository for the Process Scheduler.

Use this customization if you want to install the necessary software for the PeopleSoft Application Server, PIA, and Process Scheduler servers without running the pre-boot and post-boot ACM processes. After you complete the DPK deployment with this customization, you can complete the configuration as needed.

To prepare the customization file:

1. Locate the `psft_configuration.yaml` file, which was installed by the deployment, in `BASE_DIR/dpk/puppet/production/data`.
2. If necessary, create a `psft_customizations.yaml` using a standard editing tool, such as Notepad on Microsoft Windows or `vi` on Linux, AIX, HP-UX, or Solaris, and save it in the same location as the generated `psft_configuration.yaml` file.
3. Copy the parameters below from the `psft_configuration.yaml` file and paste them into the `psft_customizations.yaml` file.

If this is the first entry in the `psft_customizations.yaml` file, ensure that there are three dashes (- - -) on the first line of the file. Do not indent the dashes.

```
run_preboot_config_setup: true
run_postboot_config_setup: true
```

4. To specify that the deployment does not run the pre-boot and post-boot ACM processes, change the values to "false"; for example:

```
---
run_preboot_config_setup: false
run_postboot_config_setup: false
```

5. Save the file.

Task 3-4: Preparing the Customization File for JDK on AIX

As mentioned in the section *Reviewing Software Requirements for AIX*, you must use customizations to specify the installation location of the manually installed JDK 8.0 for the AIX DPK.

1. Locate the `psft_deployment.yaml` file in `BASE_DIR/dpk/puppet/production/data`.

Note. The code examples in this topic are for illustrative purposes only. Remember to use the text from the YAML files you install with each new deployment as the basis for your `psft_customizations.yaml` file.

The installation location for JDK is defined in the `psft_deployment.yaml` file that is installed with the deployment.

2. If necessary, create a `psft_customizations.yaml` using a standard editing tool such as `vi`, and save it in the same location as the `psft_deployment.yaml` file.

If this is the first entry in the `psft_customizations.yaml` file, ensure that there are three dashes (- - -) on the first line of the file. Do not indent the dashes.

3. Copy the `jdk_location` scalar parameter, and the entire `jdk` collection-type section from the `psft_deployment.yaml` file into the `psft_customizations.yaml` file. Be sure to set the locations to the same value. Do not indent `jdk_location` or `jdk`, as shown in this example:

As previously mentioned, setting the optional attribute `remove: false` means that the parameters in this section will not be deleted when the deployed environment is removed.

```
---
jdk_location:      /home/java/ibm-java-ppc64-80
jdk:
  location:        /home/java/ibm-java-ppc64-80
  remove:          false
```

4. Save the file.

Task 3-5: Preparing the Customization File for JDK on HP-UX

As mentioned in the section *Reviewing Software Requirements for HP-UX*, you must use customizations to specify the installation location of the manually installed JDK 8.0 for the HP-UX DPK.

1. Locate the `psft_deployment.yaml` file in `BASE_DIR/dpk/puppet/production/data`.

Note. The code examples in this topic are for illustrative purposes only. Remember to use the text from the YAML files you install with each new deployment as the basis for your `psft_customizations.yaml` file.

The installation location for JDK is defined in the `psft_deployment.yaml` file that is installed with the deployment.

2. If necessary, create a `psft_customizations.yaml` using a standard editing tool, such as `vi`, and save it in the same location as the `psft_deployment.yaml` file.

If this is the first entry in the `psft_customizations.yaml` file, ensure that there are three dashes (- - -) on the first line of the file. Do not indent the dashes.

3. Copy the `jdk_location` scalar parameter, and the entire `jdk` collection-type section from the `psft_deployment.yaml` file into the `psft_customizations.yaml` file. Be sure to set the locations to the same value. Do not indent `jdk_location` or `jdk`, as shown in this example:

As previously mentioned, setting the optional attribute `remove: false` means that the parameters in this section will not be deleted when the deployed environment is removed.

```
---
jdk_location:      /home/jdk/jdk1.8.0.14
jdk:
  location:        /home/jdk/jdk1.8.0.14
  remove:          false
```

4. Save the file.

Task 3-6: Preparing the Customization File for Component Software Locations

Use the information in this section if you want to customize an installation location, for example to use an existing installation of Oracle Tuxedo or Oracle WebLogic.

1. Locate the `psft_deployment.yaml` file in `BASE_DIR/dpk/puppet/production/data`.

Note. The code examples in this topic are for illustrative purposes only. Remember to use the text from the YAML files you install with each new deployment as the basis for your `psft_customizations.yaml` file.

The installation locations for Oracle Tuxedo, Oracle WebLogic, and JDK are defined in the `psft_deployment.yaml` file that is installed with the deployment.

2. If necessary, create a `psft_customizations.yaml` using a standard editing tool, such as Notepad on Microsoft Windows or vi on Linux, AIX, HP-UX or Solaris, and save it in the same location as the `psft_deployment.yaml` file.

If this is the first entry in the `psft_customizations.yaml` file, ensure that there are three dashes (- - -) on the first line of the file. Do not indent the dashes.

3. Select one or more of the sections corresponding to the components that you want to customize, and copy them to the `psft_customizations.yaml` file.

As previously mentioned, setting the optional attribute `remove: false` means that the parameters in this section will not be deleted when the deployed environment is removed.

- For JDK, copy the `jdk_location` scalar parameter, and the entire `jdk` collection-type section from the `psft_deployment.yaml` file into the `psft_customizations.yaml` file. Be sure to set the locations to the same value. Do not indent `jdk_location` or `jdk`, as shown in this example:

```
---
jdk_location:      C:/jdk
jdk:
  location:        C:/jdk
  remove:          false
```

- For Oracle Tuxedo, copy both the `tuxedo_location` scalar parameter and the entire `tuxedo` collection-type section from the `psft_deployment.yaml` file into the `psft_customizations.yaml` file. Be sure to set the locations to the same value. Do not indent `tuxedo_location` or `tuxedo`, as shown in this example:

```
---
tuxedo_location:   C:/psft/tuxedo
tuxedo:
  location:         C:/psft/tuxedo
  remove:           false
```

- For Oracle WebLogic, copy both the `weblogic_location` scalar parameter and the entire `weblogic` collection-type section from the `psft_deployment.yaml` file into the `psft_customizations.yaml` file. Be sure to set the locations to the same value. Do not indent `weblogic_location` or `weblogic`, as shown in this example:

```
---
weblogic_location: C:/psft/weblogic
weblogic:
  location:         C:/psft/weblogic
  remove:           false
```

- If you want to customize JDK, Oracle Tuxedo, and Oracle WebLogic, add all three entries to `psft_customizations.yaml`; for example:

```
---

jdk_location:      C:/jdk
```

```

jdk:
  location:      C:/jdk
  remove:       false

tuxedo_location: C:/psft/tuxedo
tuxedo:
  location:      C:/psft/tuxedo
  remove:       false

weblogic_location: C:/psft/weblogic
weblogic:
  location:      C:/psft/weblogic
  remove:       false

```

4. Save the file.

Task 3-7: Preparing the Customization File for Unicode

Use these instructions if you want to change the Unicode designation for your database.

1. Locate the `psft_deployment.yaml` file.

Note. The code examples in this topic are for illustrative purposes only. Remember to use the text from the YAML files you install with each new deployment as the basis for your `psft_customizations.yaml` file.

By default, the DPK setup script installs the YAML files in `BASE_DIR/dpk/puppet/production/data`.

The `unicode_db` parameter is part of the `ps_home` section.

```

ps_home:
  db_type:      "%{hiera('db_platform')}}"
  unicode_db:   "%{hiera('unicode_db')}}"
  location:     "%{hiera('ps_home_location')}}"

```

2. If necessary, create a `psft_customizations.yaml` using a standard editing tool, such as Notepad on Microsoft Windows or vi on Linux, AIX, HP-UX, or Solaris, and save it in the same location as the `psft_deployment.yaml` file.

If this is the first entry in the `psft_customizations.yaml` file, ensure that there are three dashes (- - -) on the first line of the file. Do not indent the dashes.

3. Copy the entire `ps_home` section from `psft_deployment.yaml`, maintaining the indentation, into the `psft_customizations.yaml` file.

For a Unicode database, set the value for `unicode_db` to true:

```

---
ps_home:
  db_type:      "%{hiera('db_platform')}}"
  unicode_db:   true
  location:     "%{hiera('ps_home_location')}}"

```

For a non-Unicode database, set the value for `unicode_db` to false:

```

---
ps_home:
  db_type:      "%{hiera('db_platform')}}"

```

```
unicode_db: false
location:    "%{hiera('ps_home_location')}}"
```

4. Save the file.

Task 3-8: Preparing the Customization File for the PeopleSoft Homes

This section discusses:

- Preparing the Customization File for the PS_HOME Location
- Preparing the Customization File for the PS_APP_HOME Location
- Preparing the Customization File for the PS_CFG_HOME Location

Task 3-8-1: Preparing the Customization File for the PS_HOME Location

By default, the DPK setup script creates the *PS_HOME* directory in *BASE_DIR/pt/ps_home<release>*, where *<release>* is the PeopleSoft PeopleTools patch release, such as 8.57.12. Use these steps to specify a different *PS_HOME* location.

1. Locate the *psft_deployment.yaml* file in *BASE_DIR/dpk/puppet/production/data*.

Note. The code examples in this topic are for illustrative purposes only. Remember to use the text from the YAML files you install with each new deployment as the basis for your *psft_customizations.yaml* file.

The *PS_HOME* installation location is specified by the *ps_home* section.

```
ps_home:
  db_type:      "%{hiera('db_platform')}}"
  unicode_db:   "%{hiera('unicode_db')}}"
  location:     "%{hiera('ps_home_location')}}"
```

2. If necessary, create a *psft_customizations.yaml* using a standard editing tool, such as Notepad on Microsoft Windows or vi on Linux, AIX, HP-UX, or Solaris, and save it in the same location as the *psft_deployment.yaml* file.

If this is the first entry in the *psft_customizations.yaml* file, ensure that there are three dashes (- - -) on the first line of the file. Do not indent the dashes.

3. Copy the entire section from the *psft_deployment.yaml* file into the *psft_customizations.yaml* file and modify the location value as needed.

For example, on Linux, AIX, HP-UX, or Solaris:

```
---
ps_home:
  db_type:      "%{hiera('db_platform')}}"
  unicode_db:   "%{hiera('unicode_db')}}"
  location:     "/home/psft8.57.12"
```

For example, on Microsoft Windows:

```
---
ps_home:
```

```
db_type:      "%{hiera('db_platform')}}"
unicode_db:   "%{hiera('unicode_db')}}"
location:     "C:/psft8.57.12"
```

4. Save the file.

Task 3-8-2: Preparing the Customization File for the PS_APP_HOME Location

By default, the DPK setup script creates the *PS_APP_HOME* directory in *BASE_DIR/pt/<Product>_app_home*, where *<Product>* is the abbreviation for the PeopleSoft application, such as *fscm* for PeopleSoft Financials and Supply Chain Management.

Here are two scenarios where you might use this customization:

- If you are performing a new installation using the PeopleSoft DPKs, and you do not want to use the default *PS_APP_HOME* location created by the DPK setup script, use this customization to specify and create the desired *PS_APP_HOME* directory.
- If you are performing a mid-tier deployment to connect to an existing environment, use this customization to specify the existing *PS_APP_HOME*.

Use these steps to specify the *PS_APP_HOME* location.

1. Locate the *psft_deployment.yaml* file in *BASE_DIR/dpk/puppet/production/data*.

Note. The code examples in this topic are for illustrative purposes only. Remember to use the text from the YAML files you install with each new deployment as the basis for your *psft_customizations.yaml* file.

The *PS_APP_HOME* installation location is specified by the *ps_app_home* section.

```
ps_apphome_location:  "%{hiera('pt_location')}/hcm_app_home"
ps_app_home:
  db_type:  "%{hiera('db_platform')}}"
  include_ml_files: false
  location: "%{hiera('ps_apphome_location')}}"
```

2. If necessary, create a *psft_customizations.yaml* using a standard editing tool, such as Notepad on Microsoft Windows or *vi* on Linux, AIX, HP-UX, or Solaris, and save it in the same location as the *psft_deployment.yaml* file.

If this is the first entry in the *psft_customizations.yaml* file, ensure that there are three dashes (- - -) on the first line of the file. Do not indent the dashes.

3. To override the location, copy the entire section from the *psft_deployment.yaml* file into the *psft_customizations.yaml* file and modify the location value as needed.

For example, on Linux, AIX, HP-UX, or Solaris:

```
---
ps_apphome_location:  "/home/hcm92_home"
ps_app_home:
  db_type:  "%{hiera('db_platform')}}"
  include_ml_files: false
  location:  "/home/hcm92_home"
```

For example, on Microsoft Windows:

```
---
```

```
ps_apphome_location: "C:/hcm92_home"
ps_app_home:
  db_type: "%{hiera('db_platform')}}"
  include_ml_files: false
  location: "C:/hcm92_home"
```

4. Save the file.

Task 3-8-3: Preparing the Customization File for the PS_CFG_HOME Location

By default, the DPK setup script creates the *PS_CFG_HOME* directory in *<user_profile>/psft/pt/8.57*, such as *C:/users/username/psft/pt/8.57* on Microsoft Windows, and */home/psadm2/psft/pt/8.57* on Linux, AIX, HP-UX, or Solaris. Note that you cannot specify different *PS_CFG_HOME* locations for different PeopleSoft domains. The DPK installation requires the same *PS_CFG_HOME* be used for all domains. Use these steps to specify the *PS_CFG_HOME* location.

1. Locate the *psft_configuration.yaml* file in *BASE_DIR/dpk/puppet/production/data*.

Note. The code examples in this topic are for illustrative purposes only. Remember to use the text from the YAML files you install with each new deployment as the basis for your *psft_customizations.yaml* file.

The *PS_CFG_HOME* installation location is specified by the *ps_config_home* parameter.

```
ps_config_home: "%{hiera('user_home_dir')}/%{hiera('domain_⇒
user')}/psft/pt/8.57"
```

2. If necessary, create a *psft_customizations.yaml* using a standard editing tool, such as Notepad on Microsoft Windows or vi on Linux, AIX, HP-UX, or Solaris, and save it in the same location as the *psft_configuration.yaml* file.

If this is the first entry in the *psft_customizations.yaml* file, ensure that there are three dashes (- - -) on the first line of the file. Do not indent the dashes.

3. Copy the entire section from the *psft_configuration.yaml* file into the *psft_customizations.yaml* file and modify the location value as needed.

For example, on Linux, AIX, HP-UX, or Solaris:

```
---
ps_config_home: "/home/pt857_config"
```

For example, on Microsoft Windows:

```
---
ps_config_home: "C:/pt857_config"
```

4. Save the file.

Task 3-9: Preparing the Customization File for Jolt SSL and WSL SSL Ports

You have the option to use the Secure Socket Layers/Transport Layer Security (SSL/TSL) protocol for Workstation Listener and Jolt Listener ports for the application server configuration. To use this protocol you must set up an Oracle wallet for the digital certificates.

See *PeopleTools: Integration Broker*, "Installing Web Server-Based Digital Certificates."

1. Locate the `psft_configuration.yaml` file in `BASE_DIR/dpk/puppet/production/data`.

Note. The code examples in this topic are for illustrative purposes only. Remember to use the text from the YAML files you install with each new deployment as the basis for your `psft_customizations.yaml` file.

2. If necessary, create a `psft_customizations.yaml` using a standard editing tool, such as Notepad on Microsoft Windows or vi on Linux, AIX, HP-UX, or Solaris, and save it in the same location as the `psft_configuration.yaml` file.

If this is the first entry in the `psft_customizations.yaml` file, ensure that there are three dashes (- - -) on the first line of the file. Do not indent the dashes.

3. Copy the entire `appserver_domain_list` section from `psft_configuration.yaml` to `psft_customizations.yaml`:
4. Add the following parameters to the `psft_customizations.yaml` file:

Note. These parameters are not included in the delivered `psft_configuration.yaml` file.

- Specify the SSL/TSL port for the Jolt listener; for example 9010.

JOLT Listener/SSL Port: 9010

- Specify the SSL/TSL port for the Workstation listener, for example 9010:

Workstation Listener/SSL Port: 9010

- Specify the location of the wallet containing the certificates:

Oracle Wallet/SEC_PRINCIPAL_LOCATION: test/security

- Specify the wallet name, for example psft:

Oracle Wallet/SEC_PRINCIPAL_NAME: psft

- Specify the wallet password:

Oracle Wallet/SEC_PRINCIPAL_PASSWORD:

5. Modify the `psft_customizations.yaml` file, including the added parameters from the previous step, with values for your environment.

Note. Be sure to retain the indentation shown in this example.

This sample `psft_customizations.yaml` file shows the parameters added from step 4 in bold font:

```
appserver_domain_list:
  "{hiera('appserver_domain_name')}":
    os_user:           "{hiera('domain_user')}"
    ps_cfg_home_dir:  "{hiera('ps_config_home')}"
    template_type:    "{hiera('appserver_template')}"

    db_settings:
      db_name:         "{hiera('db_name')}"
      db_type:         "{hiera('db_platform')}"
      db_opr_id:       "{hiera('db_user')}"
```

```

db_opr_pwd:      "%{hiera('db_user_pwd')}}"
db_connect_id:   "%{hiera('db_connect_id')}}"
db_connect_pwd:  "%{hiera('db_connect_pwd')}}"

config_settings:
  Domain Settings/Allow Dynamic Changes:      Y
  Domain Settings/Domain ID:                  "%{hiera('appserver_domain_⇒
name')} }}"
  PSAPPSRV/Min Instances:                      2
  PSAPPSRV/Max Instances:                     2
  PSAPPSRV/Max Fetch Size:                    15000
  Security/DomainConnectionPwd:               "%{hiera('domain_conn_⇒
pwd')} }}"
  JOLT Listener/Port:                         "%{hiera('jolt_port')}}"
  JOLT Listener/Address:                      0.0.0.0
  JOLT Listener/SSL Port:                  9010
  Workstation Listener/Port:                  "%{hiera('wsl_port')}}"
  Workstation Listener/SSL Port:          9010

  Oracle Wallet/SEC_PRINCIPAL_LOCATION:    test/security

  Oracle Wallet/SEC_PRINCIPAL_NAME:        psft

  Oracle Wallet/SEC_PRINCIPAL_PASSWORD:

feature_settings:
  PUBSUB:      "Yes"
  QUICKSRV:    "No"
  QUERYSRV:    "No"
  JOLT:        "Yes"
  JRAD:        "No"
  WSL:         "Yes"
  DBGSRV:      "No"
  RENSRV:      "No"
  MCF:         "No"
  PPM:         "Yes"
  PSPMSRV:     "Yes"
  ANALYTICSRV: "No"
  SERVER_EVENTS: "Yes"
  DOMAIN_GW:   "No"

```

6. Save the file.

Task 3-10: Preparing the Customization File for Oracle HTTP Server

Use the information in this section if you want to customize the installation of Oracle HTTP Server (OHS). OHS is included as part of Oracle WebLogic, and is used as a reverse proxy server (RPS).

See *PeopleTools: Portal Technology*, "Using Reverse Proxy Servers."

See *Fusion Middleware Installing and Configuring Oracle HTTP Server*, Oracle Help Center, <https://docs.oracle.com/middleware/1213/core/install-ohs/toc.htm>.

1. Locate the `psft_deployment.yaml` and `psft_configuration.yaml` files in `BASE_DIR/dpk/puppet/production/data`.

The parameter to turn OHS on, and the installation location are located in `psft_deployment.yaml`. The OHS domain configuration parameters are included in `psft_configuration.yaml`.

Note. The code examples in this topic are for illustrative purposes only. Remember to use the text from the YAML files you install with each new deployment as the basis for your `psft_customizations.yaml` file.

2. If necessary, create a `psft_customizations.yaml` using a standard editing tool, such as Notepad on Microsoft Windows or vi on Linux, AIX, HP-UX, or Solaris, and save it in the same location as the `psft_deployment.yaml` and `psft_configuration.yaml` files.

Ensure that the file begins with three dashes (- - -).

3. Change the value for `setup_ohs` to true.

This is mandatory to enable OHS. In addition, select other sections listed below, corresponding to the components that you want to customize, and copy them to the `psft_customizations.yaml` file.

As previously mentioned, setting the optional attribute `remove: false` means that the parameters in this section will not be deleted when the deployed environment is removed.

- To enable OHS (mandatory), copy the `setup_ohs` scalar parameter from `psft_deployment.yaml` into the `psft_customizations.yaml` file, and set it to true. Do not indent `setup_ohs`, as shown in this example:

```
---
setup_ohs:  true
```

Note. If you copy only this parameter into `psft_customizations.yaml`, the deployment will use the default installation location and default domain configuration.

- To change the location of the OHS installation (optional), copy the following scalar and collection parameters from `psft_deployment.yaml` into the `psft_customizations.yaml` file, and edit to specify the desired location.

Enter the full path to the installation location. Do not indent `ohs_location` or `ohs`. Be sure to enter the same value for both `ohs_location` and `location`, as shown in the later example.

```
---
setup_ohs:  true
ohs_location:    "%{hiera('pt_location')}/bea/ohs"

ohs:
  location:    "%{hiera('ohs_location')}"
```

- To customize the OHS domain configuration (optional), copy the following collection parameters from `psft_configuration.yaml` into the `psft_customizations.yaml` file and modify for your environment.

Replace the password sample below (for `webserver_admin_user_pwd`) with an encrypted password. Enter the encrypted password on a single line. Do not include spaces or line feeds. See the instructions later in this documentation to generate the encrypted password.

See "Encrypting Passwords for Customizations on Linux, AIX, HP-UX, or Solaris."

```
---
setup_ohs:  true
ohs_domain:
```

```

name:                ohsdom
os_user:             "%{hiera('domain_user')}}"
domain_home_dir:     "%{hiera('ps_config_home')}}"
pia_webserver_type:  "%{hiera('webserver_type')}}"
pia_webserver_host:  "%{hiera('pia_host_name')}}"
pia_webserver_port:  "%{hiera('pia_http_port')}}"
node_manager_port:   7500

webserver_settings:
  webserver_type:     ohs
  webserver_home:     "%{hiera('ohs_location')}}"
  webserver_admin_user: system
  webserver_admin_user_pwd: ENC[PKCS7,MIIBeQYJKoZ.....]
  webserver_admin_port: 7700
  webserver_http_port:  7740
  webserver_https_port: 7743

```

- If you want to customize the installation location and domain configuration, copy all three entries into `psft_customizations.yaml` and edit. For example, to modify the installation location and the OHS domain name:

```

---
setup_ohs: true

ohs_location:      "C:/psft_ohs"

ohs:
  location: "C:/psft_ohs"

ohs_domain:
  name:                ohsdomain2
  os_user:             "%{hiera('domain_user')}}"
  domain_home_dir:     "%{hiera('ps_config_home')}}"
  pia_webserver_type:  "%{hiera('webserver_type')}}"
  pia_webserver_host:  "%{hiera('pia_host_name')}}"
  pia_webserver_port:  "%{hiera('pia_http_port')}}"
  node_manager_port:   7500

  webserver_settings:
    webserver_type:     ohs
    webserver_home:     "%{hiera('ohs_location')}}"
    webserver_admin_user: system
    webserver_admin_user_pwd: ENC[PKCS7,MIIBeQYJKoZ.....]
    webserver_admin_port: 7700
    webserver_http_port:  7740
    webserver_https_port: 7743

```

4. Save the file.

Task 3-11: Preparing the Customization File for Mid-Tier Connection to a DB2 for Linux, UNIX, and Windows Database

Use these steps to set up PeopleSoft mid-tier components to connect to a DB2 for Linux, UNIX, and Windows (DB2 LUW) database. The DPK setup script does not identify or verify the database client software on the host machine. You have the responsibility to ensure that the installation is supported, complete, and correct.

This section assumes:

- You installed the appropriate client software for DB2 LUW on the host machine and made a note of the DB2 client installation location.
 - When running the DPK setup script, you specified DB2 LUW (DB2UNIX) as the database platform.
 - You have completed manually cataloging the database, and noted the values you used.
1. Locate the `psft_configuration.yaml` and `psft_deployment.yaml` files in `BASE_DIR/dpk/puppet/production/data`.

Note. The code examples in this topic are for illustrative purposes only. Remember to use the text from the YAML files you install with each new deployment as the basis for your `psft_customizations.yaml` file.

You need parameters from both files. The `db_platform` parameter appears in `psft_deployment.yaml`, and the `db2_server_list` section appears in `psft_configuration.yaml`. In addition, you must include parameters for the client connectivity that are described in this section, and which are not included in the generated YAML files.

2. If necessary, create a `psft_customizations.yaml` using a standard editing tool, such as Notepad on Microsoft Windows or `vi` on Linux, AIX, HP-UX, or Solaris, and save it in the same location as the `psft_configuration.yaml` file.

If this is the first entry in the `psft_customizations.yaml` file, ensure that there are three dashes (- - -) on the first line of the file. Do not indent the dashes.

3. Complete the `psft_customizations.yaml` using these section:

- a. Copy the `db_platform` section from `psft_deployment.yaml` to `psft_customizations.yaml`:

```
db_platform:      DB2UNIX
```

- b. Copy the `db2_server_list` section from `psft_configuration.yaml` to `psft_customizations.yaml`:

```
db2_server_list:
  "%{hiera('db_name')}":
    db2_type:      "%{hiera('db_platform')}"
    db2_host:      "%{::fqdn}"
    db2_port:      "%{hiera('db_port')}"
    db2_node:      TCPLNX01
    db2_target_db: "%{hiera('db_name')}"
```

- c. Add the `db2_client` section:

```
db2_client:
  sqllib_location: /home/ibm/sqllib
  instance_user:   ibm
  remove:          false
```

- d. If necessary for your environment, add `db2_user_name`, `db2_user_pwd`, and `instance_user`

(Linux, AIX, HP-UX, or Solaris).

- e. Modify the `psft_customizations.yaml` for your environment.

This table describes some of the values used in this `psft_customizations.yaml` example.

psft_customizations.yaml attribute and sample value	Description
db_platform: DB2UNIX and db2_type: DB2UNIX	Specify the RDBMS for DB2 LUW.
sqllib_location: /home/ibm⇒ /sqllib	Specify the location of the connectivity software for the DB2 client.
instance_user: ibm	This attribute only applies to Linux, AIX, HP-UX, and Solaris platforms. This refers to the user name where the sqllib is installed.
db2_host: host.example.com	Specify the fully qualified host name or host IP address for the TCP/IP node.
db2_port: 60031	Specify the TCP/IP port number.
db2_node: TCPDBX	Specify the TCP/IP node name.
db2_target_db: EP92DMO	Specify the database name.
db2_user_name: psftuser db2_user_pwd: password	Include these attributes if required for your environment setup.

For example, on Linux, AIX, HP-UX, or Solaris:

```
db_platform: DB2UNIX
db2_client:
  sqllib_location: /home/ibm/sqllib
  instance_user: ibm
  remove: false

db2_server_list:
  EP92DMO:
    db2_type: DB2UNIX
    db2_host: host.example.com
    db2_port: 60031
    db2_node: TCPDBX
    db2_target_db: EP92DMO
    db2_user_name: psftuser
    db2_user_pwd: password
    remove: false
```

On Microsoft Windows:

```
db_platform: DB2UNIX
```

```

db2_client:
  sqllib_location:  C:/db2105/bin
  remove:           false

db2_server_list:
  EP92DMO:
    db2_type:        DB2UNIX
    db2_host:         host.example.com
    db2_port:         50001
    db2_node:         TCPDBX
    db2_target_db:    EP92DMO
    db2_user_name:     psftuser
    db2_user_pwd:      password
    remove:           false

```

4. Save the file.

Task 3-12: Completing the Customized Deployment

Use these steps to complete the customized deployment of the PeopleSoft environment:

1. Run the DPK setup script as previously described.
2. Answer *n* (no) to the following prompt:

```

Do you want to continue with the default initialization process? [y|n]: ⇒
n

```

The script stops.

3. Prepare the `psft_customizations.yaml` file as previously described and save it in `BASE_DIR/dpk/puppet/production/data`.
4. Open a command prompt, running as administrator, and change directory to the Puppet manifest directory, `BASE_DIR/dpk/puppet/production/manifests`.
5. Run the following command to set up the PeopleSoft environment using the modified YAML files.

The debug and trace messages appear in the window where you run the command. See the next step if you want to capture them.

Note. The `confdir`, `debug`, and `trace` options begin with two dashes. Line feeds have been added to these samples for readability.

On Microsoft Windows:

```

"C:\Program Files\Puppet Labs\Puppet\bin\puppet.bat" apply
--confdir=BASE_DIR/dpk/puppet site.pp --debug --trace

```

On Linux:

```

/opt/puppetlabs/bin/puppet apply --confdir=BASE_DIR/dpk/puppet
site.pp --debug --trace

```

On AIX, HP-UX, or Solaris:

```

/opt/oracle/puppetlabs/bin/puppet apply
--confdir=BASE_DIR/dpk/puppet site.pp --debug --trace

```


6. To redirect the output to a log file, add the `logdest` option, and supply a location and file name to save the log.

Note. Since these commands redirect the output to a log file, you cannot follow the progress. The process is complete when the prompt returns.

On Microsoft Windows:

```
"C:\Program Files\Puppet Labs\Puppet\bin\puppet.bat" apply
--confdir=BASE_DIR/dpk/puppet site.pp
--debug --trace --detailed-exitcodes
--logdest <log_directory\dpk\<log_filename.log>
```

On Linux:

```
/opt/puppetlabs/bin/puppet apply
--confdir=BASE_DIR/dpk/puppet site.pp
--debug --trace --detailed-exitcodes
--logdest <log_directory/dpk/<log_filename.log>
```

On AIX, HP-UX, or Solaris:

```
/opt/oracle/puppetlabs/bin/puppet apply
--confdir=BASE_DIR/dpk/puppet site.pp
--debug --trace --detailed-exitcodes
--logdest log_directory/dpk/<log_filename.log>
```


Chapter 4

Setting Up the Install Workstation

This chapter discusses:

- Understanding the Install Workstation
- Prerequisites
- Starting Configuration Manager
- Setting Startup Options
- Editing the Default Profile
- Running Client Setup

Understanding the Install Workstation

This chapter describes how to set up a PeopleSoft Windows-based client for connecting to the database server in two-tier mode, specifically for the purpose of performing install-related tasks from the workstation. You must configure at least one two-tier Windows-based client for running the Data Mover and SQR processes required for setting up the batch server and for creating the PeopleSoft database. For some installations you may wish to set up multiple install workstations, so that you can perform asynchronous tasks at the same time; for example, you could create and populate multiple databases simultaneously. You can quickly configure multiple workstations by exporting a configuration file from one workstation and importing it to another workstation.

See Also

PeopleTools: System and Server Administration

Prerequisites

The following tasks are prerequisites for setting up the install workstation:

- The workstation must have database connectivity software installed.
- You must have planned your database creation strategy. You should know the precise names of the databases that you intend to create.
- Make sure that you have created your connect strategy. You must use a Connect ID. You should know both the Connect ID and Connect password.

For information on PeopleSoft Connect ID and Connect password, consult the *PeopleTools: System and Server Administration* product documentation for information on setting Application Server domain parameters.

- The workstation must have a logical drive mapped to *PS_HOME* on the file server (or, if the file server and

install workstation are one and the same, *PS_HOME* can be installed on a local drive).

- The person performing the installation must have read access to the *PS_HOME* directory.

If this is the same workstation on which the PeopleSoft PeopleTools installation was performed, it should have a PeopleTools 8.5 installation program group, which was created when you loaded the PeopleTools software. This isn't a requirement, but it does make it more convenient to run the PeopleTools install applications.

See Also

"Preparing for Installation"

"Using the PeopleSoft Installer"

Task 4-1: Starting Configuration Manager

Configuration Manager is a utility for configuring workstations being used as the PeopleTools Development Environment. These are its principal functions:

- Sets up and make changes to PeopleSoft configuration settings.
- Creates a program group containing Microsoft Windows shortcuts to PeopleSoft applications.
- Installs local DLLs.

The first time you run Configuration Manager on the client, it will populate certain fields with default values specified in a configuration file stored on the file server, specifically: *PS_HOME\setup\pstools.cfg*. This configuration file was set up when you ran the installation. Once you set up and run Configuration Manager, it will populate fields using values that are stored in the Windows system registry.

To start Configuration Manager, do one of the following:

- On Microsoft Windows 7, select *Start, Programs, PeopleTools 8.57, Configuration Manager*. (This program group will be available if you installed PeopleSoft PeopleTools on this workstation.)
- On Microsoft Windows 8 or 2012 R2, access the Apps screen, navigate to the PeopleTools 8.57 category, and select Configuration Manager.

Note. See the documentation for your operating system for information on accessing the Apps screen.

- If the *PeopleTools 8.57* program group was not installed on this workstation, run *pscfg.exe* directly from the *PS_HOME\bin\client\winx86* directory on the file server.

Task 4-2: Setting Startup Options

The Startup tab of Configuration Manager sets the default options for the PeopleSoft sign-on screen that is used for connecting to a PeopleSoft database. It also contains a setting that specifies the local directory for storing cached PeopleSoft data.

To set Startup options:

1. Confirm that you are viewing the Configuration Manager Startup tab (this tab is what you see if you started Configuration Manager as described in the previous task).
2. Set the following options:
 - *Database type* — Verify the type of RDBMS. This should already be set to DB2 UDB for UNIX, NT.

- *Application Server Name* — This option appears if you select a database type of Application Server. It is where you enter your application server name if you are setting up a three-tier connection.
- *Database name* — The name of the default database to connect to. Enter the name of one of the databases that you intend to create.
- *User ID* — The name of the default user that will appear in the sign-on screen. This can be any valid user name, although for installation setup it normally matches the name of one of the built-in PeopleSoft users (typically PS or VP1) that will be installed in the database.
- *Connect ID and Connect Password* — Type your connect ID and password into these fields.

Task 4-3: Editing the Default Profile

Begin by editing the default profile for the workstation. Among other things, this will verify that the paths to *PS_HOME* and its subdirectories are correctly set, which is required for subsequent tasks.

For more information on using Configuration Manager, see the *PeopleTools: System and Server Administration* product documentation for configuring user profiles.

To edit the default profile:

1. Select the Profile tab in Configuration Manager.
Only one profile, the Default Profile, has been defined.
2. Select Edit to display the Edit Profile dialog box, and then select the Process Scheduler tab.

3. In the Process Scheduler tab verify the options listed below the example.
These should have been set correctly by the PeopleSoft installation program.

Edit Profile - 'Default'

Database/Application Server | **Process Scheduler** | nVision | Common

General

PeopleSoft Home Directory (PS_HOME): C:\psft\pt\ps_home8.57\

PeopleSoft App Home Directory (PS_APP_HOME): C:\psft\pt\pscm_app_home\

PeopleSoft Customizations Home Directory (PS_CUST_HOME):

Temp Directory (TEMP): c:\temp

Crystal Reports (CRWRPTPATH): C:\psft\pt\ps_home8.57\crw

Database Drivers (DBBIN): C:\sqlib\bin

Output Directory (OUTPUT): c:\temp\

Word Executables Directory (WINWORD):

Log Directory (LOG): c:\temp

☐ Redirect Output

Application Engine

☐ Debug

☐ Disable Restart

SQR

SQR Executables (SQRBIN): C:\psft\pt\ps_home8.57\bin\sqr\DBX\binw

PSSQR Path: C:\psft\pt\ps_home8.57\sqr

SQR Flags (PSSQRFLAGS): -ZIFC:\psft\pt\ps_home8.57\sqr\pssqr.ini

COBOL

COBOL Executables (CBLBIN): C:\psft\pt\ps_home8.57\cblbin

OK Cancel Apply

Edit Profile dialog box: Process Scheduler tab

- Verify that the PeopleSoft Home Directory (PS_HOME) field is set to the path to *PS_HOME* on the file server.
- Verify that the PeopleSoft Apps Home Directory (PS_APP_HOME) field is set to the path to *PS_APP_HOME* on the file server, C:\psft\pt\pscm_app_home in this example.

Note. The installation using PeopleSoft DPKs requires that *PS_APP_HOME* and *PS_HOME* be different.


- On Microsoft Windows operating systems, set the Database Drivers (DBBIN) field to the path for the database connectivity files, if necessary.

The example shows the default for DB2/LUW, C:\sqlib\bin.

- Set the SQR Executables (SQRBIN) field to the file server directory where SQR for Windows was installed when you ran the PeopleSoft Installer.
- Set the SQR Flags (PSSQRFLAGS) field to *-ZIF<PS_HOME>\sqr\pssqr.ini*.
- Set the SQR Report Search 1 (PSSQR1) field to *PS_HOME\sqr*. The remaining SQR Report Search fields

can be left blank, because no additional SQR report directories have been created yet.

4. Select the Common tab of the Edit Profile dialog box, shown in this example:



Edit Profile dialog box: Common tab

The following fields on the Common tab are used to set Data Mover default input, output, and log directories.

- Verify that the Input Directory and Output Directory fields are set to *PS_HOME\data*. This directory will store the Data Mover scripts and .DAT files required to populate the PeopleSoft database.
- Set the Log Directory to a local workstation directory to store the Data Mover log files. The default is *C:\TEMP*.

Data Mover will not create a new directory under *PS_APP_HOME* or *PS_HOME* for log files. If you want Data Mover to write log files into *PS_APP_HOME*, you must create a new directory named log under *PS_APP_HOME*.

5. Select OK to close the Edit Profile dialog box.

Task 4-4: Running Client Setup

The Client Setup tab does the following:

- Installs a PeopleSoft program group on the workstation.
- Installs system DLLs on the workstation.

These Client Setup functions are performed when you click OK or Apply from Configuration Manager only if the Install Workstation option on the Client Setup tab is selected.

Note. Any files installed by Client Setup on the workstation from the file server use the paths specified in the default profile.

To run Client Setup:

1. Select the Client Setup tab in Configuration Manager.
2. In the Group Title text box enter the name of the program group for the icons you want on the client workstation. (A program group name cannot contain any of the following characters: \ / : * ? " < > |)
You can call the program group anything you want, but this documentation uses *PeopleTools 8.57*.
3. If you do not have a PeopleTools 8.57 program group set up on the workstation, be sure to check the following two options for installing shortcuts to applications essential for installation.

Note. When you run Client Setup, it will uninstall any existing shortcuts in the PeopleTools 8.57 program group, and install shortcuts for the applications you have selected. If you subsequently want to install or uninstall shortcuts, you can always re-run Client Setup.

- *Data Mover*
 - *Configuration Manager*
4. Select the option Install Workstation.
This check box determines whether Client Setup runs when you click Apply or OK in Configuration Manager. If this option is not selected, Client Setup will create or update settings in the registry, but it will not set up the PeopleTools 8.57 program group or install local DLLs.
 5. Click OK to run Client Setup and close Configuration Manager.

Chapter 5A

Creating a Database Manually on Microsoft Windows or UNIX

This chapter discusses:

- Understanding Database Creation
- Determining Tablespace Strategy for Demo Database
- Editing SQL Scripts
- Running SQL Scripts
- Configuring and Testing Database Connectivity for DB2 Connect or DB2 Client V9.x or Earlier
- Configuring and Testing Connectivity for DB2 Connect and DB2 Client V10.x or Later
- Configuring an ODBC Data Source for Connectivity on Microsoft Windows
- Creating Data Mover Import Scripts
- Running Data Mover Import Scripts
- Cleaning Up Orphaned Language Data
- Checking the Log Files and Troubleshooting
- Changing the Base Language

Understanding Database Creation

This section describes the tasks required to create a PeopleSoft product database. During a standard PeopleSoft installation you will execute these tasks to create two distinct types of databases.

- *System*: The System (SYS) database has no company specific data, and can be used to load your data and begin development of your production database.
- *Demo*: The Demo (DMO) database contains data for a sample company, and can be used immediately for demonstration, for testing, and as a development reference.

Note. The PeopleTools System Database (PTSYS) is not available with the current release. As an alternative, install the latest PeopleSoft Interaction Hub database.

Note. If you are using the PeopleSoft Upgrade Source Image, you must create a Demo database.

The requirements for these databases vary, so not all of this section's tasks apply to each database. The instructions will note any distinctions between creating a Demo and a System database.

- You must have installed the Database component of your PeopleSoft application installation software to your database server.
- You must have the PeopleTools Development Environment set up to create your database.

Important! Do not forget that application-specific installation steps are provided in a separate document specific to the application. For instance, if you are performing PeopleSoft CRM installation, you need both this documentation for the basic installation of PeopleSoft PeopleTools and the PeopleSoft application, and any additional instructions provided by CRM. Search in My Oracle Support for the installation documentation specific to your application.

Note. For the sake of brevity, this documentation sometimes refers to DB2 for Linux, UNIX, and Windows as *DB2/LUW*.

Note. The Database Configuration Wizard cannot be used on a Microsoft Windows operating system. You must use the manual method of creating a database for this configuration.

After you complete the tasks in this chapter, read the chapter "Completing the Database Setup." Depending upon your environment, you may not need to carry out every task in that chapter. However it is important that you evaluate the requirements and perform the necessary tasks.

Note. Oracle supports a number of versions of UNIX and Linux in addition to Microsoft Windows for the PeopleSoft installation. Throughout this book, there are references to operating systems. Where necessary, this book refers to specific operating systems by name (for example, Oracle Solaris, IBM AIX, HP-UX Itanium, or Linux); however, for simplicity the word UNIX is often used to refer to all UNIX-like operating systems, including Linux.

See Also

"Preparing for Installation," Planning Database Creation

"Setting Up the Install Workstation"

Task 5A-1: Determining Tablespace Strategy for Demo Database

The default installation for PeopleSoft databases uses separate tablespaces for *Data* and *Index* storage. Due to the separation of Index tablespaces, the only available tablespace choice for PeopleSoft databases is DMS.

For multiple tablespaces, the PeopleSoft installation provides a tablespace strategy for demonstration and system databases aimed at identifying high-growth and high-update tables. This limits the number of tables the DBA must monitor and analyze, and simplifies capacity planning and database tuning activities. The standard tablespace names that Oracle delivers for the PeopleSoft installation categorize tables as follows:

- High growth and high update tables are grouped together into tablespaces named *XXLARGE*, where *XX* is a PeopleSoft application identifier. It's expected that each table defined in *XXLARGE* will be placed in its own tablespace for system testing or production for performance and recovery reasons.
- Relatively stable tables are grouped into tablespaces named *XXAPP*, where *XX* is a PeopleSoft application identifier. These tables may be placed in shared tablespaces defined with a moderate freespace specification.
- Tables containing rows exceeding 4K in width and/or containing LOB data types are assigned in the *PSIMAGE* or *PSIMAGE2* tablespace.

Task 5A-2: Editing SQL Scripts

This section discusses:

- Understanding SQL Scripts
- Editing CREATEDB-95.SQL or CREATEDBU.SQL
- Executing DB2SET Command to Set Proper Decimal Scale
- Editing ALTRDB.SQL
- Editing CREATEBPU.SQL for Unicode
- Editing XXDDLDMMS.SQL or XXDDLDMMSU.SQL
- Editing DBOWNER.SQL
- Editing PSADMIN.SQL

Understanding SQL Scripts

Before creating the PeopleSoft database, you need to modify these SQL scripts in the *PS_HOME/scripts* (UNIX) or *PS_HOME\scripts* (Microsoft Windows) directory.

- DBMCFG.SQL
- CREATEDB-95.SQL (non-Unicode)
- CREATEDBU.SQL (Unicode)
- ALTRDB.SQL
- CREATEBPU.SQL (Unicode)
- XXDDLDMMS.SQL, where *XX* is a two-character code corresponding to the product line you are installing
- XXDDLDMMSU.SQL (Unicode), where *XX* is a two-character code corresponding to the product line you are installing
- DBOWNER.SQL
- DBOWNERU.SQL (Unicode)
- PSADMIN.SQL

See Editing XXDDLDMMS.SQL or XXDDLDMMSU.SQL.

Task 5A-2-1: Editing CREATEDB-95.SQL or CREATEDBU.SQL

Select the appropriate script for the database you are creating:

- Use CREATEDB-95.SQL for non-Unicode installations.
- Use CREATEDBU.SQL for Unicode installations.

Edit the CREATEDB-95.SQL or CREATEDBU.SQL script in *PS_HOME/scripts* (UNIX) or *PS_HOME\scripts* (Microsoft Windows) script, replacing the following items with your information.

Items to Edit	Appropriate Values
<db2-database-name>	This is usually the same name as the PeopleSoft database name.

Items to Edit	Appropriate Values
<dir-name>	<p>This is the DB2 UDB for Linux, UNIX, and Windows directory where the database and log files will reside. Optionally, you can specify another directory or device for logs using the NEWLOGPATH statement.</p> <p>See "Creating a Database on UNIX," Changing the Location of the DB2/LUW Database Log Files.</p> <p>Note. On Microsoft Windows, specify a drive letter. See the IBM documentation for more information.</p>
<supplied-codeset>	Consult the DB2/LUW reference manual section on "Supported territory codes and code pages" for information on territory identifiers and code sets. This applies to the CREATEDB-95.SQL script only.
<supplied-territory>	Consult the DB2/LUW reference manual section on "Supported territory codes and code pages" for information on territory identifiers and code sets. This applies to the CREATEDB-95.SQL script only.

Make note of the following:

- The database name must be in UPPERCASE and cannot exceed eight characters.
- Oracle recommends placing the data and log files in separate file systems and creating each file system on a different physical disk drive to reduce I/O contentions.
- The value assigned for database bufferpool size is the minimum for a PeopleSoft database. Consider increasing the size of the BUFFPAGE to improve performance. The total amount of BUFFPAGE memory allocated for all the databases running on the same computer should not exceed 75% of the computer memory.
- All the remaining configuration settings are the minimum recommendations to run PeopleSoft database. Do not change any settings to a lower value. To operate the database effectively, most of the database configuration parameters will have to be tuned for the end-user computing environment.

Note. For Unicode databases you need to set the db2 codepage for your db2 instance. To do this execute the command `db2set db2codepage=1208`

- The CREATEDB-95.SQL, or CREATEDBU.SQL script assumes that you are using circular logs for your demonstration database. For a production database, the archive logs are recommended.
- Statements near the end of the script examples define 16K Bufferpool (non-Unicode) and 32K Bufferpool (Unicode) to support LOB data types for PeopleSoft PeopleTools 8.53 and later.

The following are examples of these scripts:

Note. The database configuration is done with a call to an inline defined Stored Procedure, `ps_db_cfg`. DO NOT change the Stored Procedure definition.

CREATEDB-95.SQL, for non-Unicode:

```
-- *****
-- This software and related documentation are provided under a
-- license agreement containing restrictions on use and
-- disclosure and are protected by intellectual property
```

```

-- laws. Except as expressly permitted in your license agreement
-- or allowed by law, you may not use, copy, reproduce,
-- translate, broadcast, modify, license, transmit, distribute,
-- exhibit, perform, publish or display any part, in any form or
-- by any means. Reverse engineering, disassembly, or
-- decompilation of this software, unless required by law for
-- interoperability, is prohibited.
-- The information contained herein is subject to change without
-- notice and is not warranted to be error-free. If you find any
-- errors, please report them to us in writing.
--
-- Copyright (C) 1988, 2017, Oracle and/or its affiliates.
-- All Rights Reserved.
-- *****

--
-- *****
-- *****
--
--
--
--
--                                     /pt_install/SCRIPTS/DBX/CREATEDB-95.SQL /main/pt84x⇒
/9 3
--
-- *****

-- After running this script do these steps to enable dbm and db updates
--     1. Stop the instance at the Unix prompt      $db2stop
--     2. Start the instance at the Unix prompt      $db2start
--
CREATE DATABASE <db2-database-name>
ON <dir-name>
USING CODESET <supplied-codeset> TERRITORY <supplied-territory>
COLLATE USING IDENTITY
USER TABLESPACE MANAGED BY SYSTEM USING ('data') EXTENTSIZE 8
TEMPORARY TABLESPACE MANAGED BY SYSTEM USING ('temp') EXTENTSIZE 8
;

CONNECT TO <db2-database-name> ;

CREATE PROCEDURE ps_db_cfg
(IN p_control CHAR(2)
,IN p_control_ver DEC(3,1)
,IN p_cfg_name VARCHAR(30)
,IN p_cfg_value VARCHAR(30)
,OUT p_out_msg VARCHAR(110)
,OUT p_out_dec DEC(3,1))

LANGUAGE SQL

SPECIFIC ps_db_cfg

```

```

BEGIN

  DECLARE v_CurrVer DECIMAL (3,1) ;--
  DECLARE v_CurrVer_Len,v_Cfg_Flag INT DEFAULT 0 ;--

  DECLARE v_Cfg_cmd VARCHAR(60) DEFAULT 'UPDATE DB CFG USING ' ;--

  SET p_out_msg = p_cfg_name || ' UNCHANGED';--

  SET v_CurrVer_Len = (select length(substr(SERVICE_LEVEL,6,posstr(substr⇒
(SERVICE_LEVEL,6),'.')-1)) FROM TABLE(SYSPROC.ENV_GET_INST_INFO()) AS⇒
  INSTANCEINFO) ;--

  if v_CurrVer_Len > 1
  then
    SET v_CurrVer = (SELECT DEC(substr(SERVICE_LEVEL,6,4),3,1) FROM TABLE⇒
    (SYSPROC.ENV_GET_INST_INFO()) AS INSTANCEINFO) ;--
    SET p_out_dec = v_CurrVer ;--

    else
    SET v_CurrVer = (SELECT DEC(substr(SERVICE_LEVEL,6,3),3,1) FROM TABLE⇒
    (SYSPROC.ENV_GET_INST_INFO()) AS INSTANCEINFO) ;--
    SET p_out_dec = v_CurrVer ;--

  End if ;--

  CASE p_control

    WHEN 'LT' THEN
      If v_CurrVer < p_control_ver THEN SET v_Cfg_Flag = 1 ;--
      End if ;--

    WHEN 'LE' THEN
      If v_CurrVer <= p_control_ver THEN SET v_Cfg_Flag = 1 ;--
      End if ;--

    WHEN 'EQ' THEN
      If v_CurrVer = p_control_ver THEN SET v_Cfg_Flag = 1 ;--
      End if ;--

    WHEN 'GT' THEN
      If v_CurrVer > p_control_ver THEN SET v_Cfg_Flag = 1 ;--
      End if ;--

    WHEN 'GE' THEN
      If v_CurrVer >= p_control_ver THEN SET v_Cfg_Flag = 1 ;--
      End if ;--

    ELSE
      SET v_Cfg_Flag = 0 ;--

  End CASE ;--

```

```

IF v_Cfg_Flag = 1 THEN

    SET p_out_msg = p_cfg_name || ' SET TO ' || p_cfg_value ;--

    SET v_Cfg_cmd = v_Cfg_cmd || p_cfg_name || ' ' || p_cfg_value ;--

    CALL ADMIN_CMD(v_Cfg_cmd) ;--

END IF ;--

END;

CALL ps_db_cfg('GE',9.5,'BUFFPAGE','15000',?,?) ;
CALL ps_db_cfg('GE',9.5,'LOCKTIMEOUT','180',?,?) ;
CALL ps_db_cfg('GE',9.5,'LOGBUFSZ','24',?,?) ;
CALL ps_db_cfg('GE',9.5,'LOGFILSIZ','12000',?,?) ;
CALL ps_db_cfg('GE',9.5,'LOGPRIMARY','10',?,?) ;
CALL ps_db_cfg('GE',9.5,'LOGSECOND','20',?,?) ;
CALL ps_db_cfg('GE',9.5,'MAXAPPLS','150',?,?) ;
CALL ps_db_cfg('GE',9.5,'MIN_DEC_DIV_3','YES',?,?) ;

CREATE BUFFERPOOL PS16KPOOL SIZE -1 PAGESIZE 16K ;

CREATE TEMPORARY TABLESPACE TEMPSPACE16K PAGESIZE 16K MANAGED BY SYSTEM⇒
    USING ('temp16k') EXTENTSIZE 16 BUFFERPOOL PS16KPOOL ;

TERMINATE ;

```

CREATEDBU.SQL for Unicode:

```

-- *****
-- This software and related documentation are provided under a
-- license agreement containing restrictions on use and
-- disclosure and are protected by intellectual property
-- laws. Except as expressly permitted in your license agreement
-- or allowed by law, you may not use, copy, reproduce,
-- translate, broadcast, modify, license, transmit, distribute,
-- exhibit, perform, publish or display any part, in any form or
-- by any means. Reverse engineering, disassembly, or
-- decompilation of this software, unless required by law for
-- interoperability, is prohibited.
-- The information contained herein is subject to change without
-- notice and is not warranted to be error-free. If you find any
-- errors, please report them to us in writing.
--
-- Copyright (C) 1988, 2017, Oracle and/or its affiliates.
-- All Rights Reserved.
-- *****
--
-- *****

```

```

-- *****
--
--
--
--          /pt_install/SCRIPTS/DBX/CREATEDBU.SQL /main/pt84x/10
--
-- *****

-- After running this script do these steps to enable dbm and db updates
--     1. Stop the instance at the Unix prompt      $db2stop
--     2. Start the instance at the Unix prompt      $db2start
--

CREATE DATABASE <db2-database-name> on <dir-name> using codeset UTF-8⇒
territory US
USER TABLESPACE MANAGED BY SYSTEM USING
    ('data') EXTENTSIZE 8
TEMPORARY TABLESPACE MANAGED BY SYSTEM USING
    ('temp') EXTENTSIZE 8 ;

CONNECT TO <db2-database-name> ;

CREATE PROCEDURE ps_db_cfg
(IN p_control CHAR(2)
,IN p_control_ver DEC(3,1)
,IN p_cfg_name VARCHAR(30)
,IN p_cfg_value VARCHAR(30)
,OUT p_out_msg VARCHAR(110)
,OUT p_out_dec DEC(3,1))

LANGUAGE SQL

SPECIFIC ps_db_cfg

BEGIN

    DECLARE v_CurrVer DECIMAL (3,1) ;--
    DECLARE v_CurrVer_Len,v_Cfg_Flag INT DEFAULT 0 ;--

    DECLARE v_Cfg_cmd VARCHAR(60) DEFAULT 'UPDATE DB CFG USING ' ;--

    SET p_out_msg = p_cfg_name || ' UNCHANGED';--

    SET v_CurrVer_Len = (select length(substr(SERVICE_LEVEL,6,posstr(substr⇒
(SERVICE_LEVEL,6),'.')-1)) FROM TABLE(SYSPROC.ENV_GET_INST_INFO()) AS⇒
INSTANCEINFO) ;--

    if v_CurrVer_Len > 1
    then
    SET v_CurrVer = (SELECT DEC(substr(SERVICE_LEVEL,6,4),3,1) FROM TABLE⇒
(SYSPROC.ENV_GET_INST_INFO()) AS INSTANCEINFO) ;--
    SET p_out_dec = v_CurrVer ;--

```



```

else
SET v_CurrVer = (SELECT DEC(substr(SERVICE_LEVEL,6,3),3,1) FROM TABLE⇒
(SYSPROC.ENV_GET_INST_INFO()) AS INSTANCEINFO) ;--
SET p_out_dec = v_CurrVer ;--

End if ;--

CASE p_control

WHEN 'LT' THEN
    If v_CurrVer < p_control_ver THEN SET v_Cfg_Flag = 1 ;--
    End if ;--

WHEN 'LE' THEN
    If v_CurrVer <= p_control_ver THEN SET v_Cfg_Flag = 1 ;--
    End if ;--

WHEN 'EQ' THEN
    If v_CurrVer = p_control_ver THEN SET v_Cfg_Flag = 1 ;--
    End if ;--

WHEN 'GT' THEN
    If v_CurrVer > p_control_ver THEN SET v_Cfg_Flag = 1 ;--
    End if ;--

WHEN 'GE' THEN
    If v_CurrVer >= p_control_ver THEN SET v_Cfg_Flag = 1 ;--
    End if ;--

ELSE
    SET v_Cfg_Flag = 0 ;--

End CASE ;--

IF v_Cfg_Flag = 1 THEN

    SET p_out_msg = p_cfg_name || ' SET TO ' || p_cfg_value ;--

    SET v_Cfg_cmd = v_Cfg_cmd || p_cfg_name || ' ' || p_cfg_value ;--

    CALL ADMIN_CMD(v_Cfg_cmd) ;--

END IF ;--

END;

CALL ps_db_cfg('GE',9.5,'BUFFPAGE','15000',?,?,) ;
CALL ps_db_cfg('GE',9.5,'LOCKTIMEOUT','180',?,?,) ;
CALL ps_db_cfg('GE',9.5,'LOGBUFSZ','24',?,?,) ;
CALL ps_db_cfg('GE',9.5,'LOGFILSIZ','12000',?,?,) ;
CALL ps_db_cfg('GE',9.5,'LOGPRIMARY','10',?,?,) ;
CALL ps_db_cfg('GE',9.5,'LOGSECOND','20',?,?,) ;
CALL ps_db_cfg('GE',9.5,'MAXAPPLS','150',?,?,) ;

```

```
CALL ps_db_cfg('GE',9.5,'MIN_DEC_DIV_3','YES',?,?) ;

CREATE BUFFERPOOL PS32KPOOL SIZE -1 PAGESIZE 32K ;

CREATE TEMPORARY TABLESPACE TEMPSPACE32K PAGESIZE 32K MANAGED BY SYSTEM⇒
  USING ('temp32k') EXTENTSIZE 32 BUFFERPOOL PS32KPOOL ;

TERMINATE ;
```

Task 5A-2-2: Executing DB2SET Command to Set Proper Decimal Scale

Execute db2set command:

```
db2set db2_min_dec_div_6=yes
```

Task 5A-2-3: Editing ALTRDB.SQL

Edit the *PS_HOME*/scripts/ALTRDB.SQL (UNIX) or *PS_HOME*\scripts\ALTRDB.SQL (Microsoft Windows) directory, replacing <db2-database-name> with the PeopleSoft database name. ALTRDB.SQL enables the BUFFPAGE parameter set in CREATEDB-95.SQL or CREATEDBU.SQL by setting the Buffer Pool NPAGES to -1.

Task 5A-2-4: Editing CREATEBPU.SQL for Unicode

Edit the *PS_HOME*/scripts/CREATEBPU.SQL (UNIX) or *PS_HOME*\scripts\CREATEBPU.SQL (Microsoft Windows) directory, replacing <db2-database-name> with the PeopleSoft database name. This script creates an 8K bufferpool.

Task 5A-2-5: Editing XXDDLMS.SQL or XXDDLMSU.SQL

If you are creating a Unicode database, replace all references to *XXDDLMS.sql* below with *XXDDLMSU.sql*.

Edit the *XXDDLMS.SQL* script, where *XX* is a two-character code corresponding to the product line. Use the following table to determine the code for the product line you are installing.

Code	Product Line
CS	PeopleSoft Campus Solutions
CR	PeopleSoft Customer Relationship Management
LM	PeopleSoft Enterprise Learning Management
PF	PeopleSoft Enterprise Performance Management
EP	PeopleSoft Financials / Supply Chain Management
EA	PeopleSoft Financials / Supply Chain Management Argentina

Code	Product Line
EB	PeopleSoft Financials / Supply Chain Management Brazil
HC	PeopleSoft Human Capital Management
PA	PeopleSoft Portal Solutions

Note. This is a complete list of available product lines for the current PeopleSoft PeopleTools release. Note that not all products go out on all PeopleSoft PeopleTools releases, so you may not see a script corresponding to every product line. In addition, some bolt-on products reference their own scripts within their application installation documentation. Please see your application-specific installation documentation for details.

The *XXDDLMS.SQL* script configures DMS tablespaces (DATABASE MANAGED SPACE) and is run against the SYS and DMO database. For a discussion of DMS tablespace management, search for the tuning and administration documentation on My Oracle Support.

Each of these scripts is in *PS_HOME/scripts* (UNIX) on the database server or *PS_HOME\scripts* (Microsoft Windows) directory on the file server. Edit the scripts to change the containers, using your site-specific values. The container path names in the delivered script are samples; any path name may be used.

We recommend that each container (data1, data2, data3, and so forth) reside on a separate physical hard drive. The sample script illustrates how to divide the database into three homogenous sets of DB2/LUW containers. You may want to increase or decrease the number of containers based on the number of physical disk drives available for your database use.

Multilanguage databases

If you are installing a multilanguage database, you need to increase the size of several tablespaces configured in *XXDDLMS.SQL* to accommodate additional system data related to each non-U.S. English language.

The following table shows the amount each affected tablespace should be increased for each non-US English language:

Tablespace	Amount of Increase
PTTBL	2284 4K pages (9MB)
PSIMAGE	8408 4K pages (34MB)

DB2 Automatic re-sizing

Support for the DB2 Automatic re-sizing of Tablespaces feature is enabled by default. However, when creating a database manually, both *XXDDLMS.sql* and *XXDDLMSU.sql* scripts must be edited first to include the **AUTORESIZE** parameter for each Tablespace DDL as follows (the new entries are in bold text):

```
CREATE TABLESPACE <TBSPCNAME> MANAGED BY DATABASE USING
( FILE '/data1/psdb2/<DBNAME>/<TBSPCNAME>.DBF' 10 M
) EXTENTSIZE 16 PREFETCHSIZE 48 DROPPED TABLE RECOVERY OFF
AUTORESIZE YES INCREASE 10M MAXSIZE NONE;
```

Additional tablespaces

Beginning with PeopleSoft PeopleTools 8.53, new tablespaces PSIMAGE2, PSIMAGE2IDX, and PSIMAG2LOB are delivered. These tablespaces are created with pagesize 16K (non-Unicode) and 32K (Unicode), and bufferpool size 16K (non-Unicode) and 32K (Unicode). These required tablespaces contain tables with LOB (CLOB/DBCLOB/BLOB) data types.

See PeopleTools 8.53 Release Notes, My Oracle Support.

Before running the Data Mover import task, verify that the *XXDDLMS.SQL* and *XXDDLMSU.SQL* scripts include these tablespaces.

Task 5A-2-6: Editing DBOWNER.SQL

If you are creating a Unicode database, replace all references to DBOWNER.sql below with DBOWNERU.sql.

Edit the DBOWNER.SQL script, substituting values as specified in the following table:

Items to Edit	Appropriate Values
<db2-database-name>	The database name as specified in the CREATEDB-95.SQL or CREATEDBU.SQL script.

This script creates the PS.PSDBOWNER table.

For example:

Original:

```
-- Create table PS.PSDBOWNER, and grant access --
connect to <db2-database-name>
create table ps.psdowner (dbname char(8), ownerid char(8))
grant select on ps.psdowner to public
commit
```

Unicode:

```
-- Create table PS.PSDBOWNER, and grant access --
connect to <db2-database-name>
create table ps.psdowner (dbname VARGRAPHIC(8), ownerid VARGRAPHIC(8))
grant select on ps.psdowner to public
commit
```

Note. The Owner ID specified in this script must be the same value specified in the Access ID field in the task Creating Data Mover Import Scripts later in this chapter.

Task 5A-2-7: Editing PSADMIN.SQL

Edit the PSADMIN.SQL script, substituting values as specified in the following table:

Items to Edit	Appropriate Values
db2-database-name	The database name as specified in the CREATEDB-95.SQL or CREATEDBU.SQL script.
<owner-id>	The Table Owner ID you selected earlier in this chapter.

This script grants privileges on the database to the Owner ID.

Task 5A-3: Running SQL Scripts

Run the scripts edited in the preceding step to create the database and tablespaces.

To create the DB2/LUW database:

1. Log in to the DB2/LUW database server as the PeopleSoft Table Owner.

This USER ID was created in an earlier task in this installation guide.

See "Preparing for Installation," Creating PeopleSoft User ID.

2. On Microsoft Windows, run the following command:

```
db2set DB2_CREATE_DB_ON_PATH=YES
```

3. Execute the CREATEDB-95.SQL script (if non-Unicode) or the CREATEDBU.SQL script (if Unicode), using the db2 utility. For example:

- *For Microsoft Windows:*

```
db2 -vtf createdb-95.sql > createdb-95.sql.out
```

- *For UNIX:*

```
db2 -vtf createdb-95.sql |tee createdb-95.sql.out
```

After the script completes, check the log file to verify that the database has been successfully created and took all the database configuration changes.

1. Stop the instance with DB2STOP and then start it again with DB2START.
2. Execute the ALTRDB.SQL script using the db2 utility. For example:

For Microsoft Windows:

```
db2 -vf altrdb.sql > altrdb.sql.out
```

For UNIX:

```
db2 -vf altrdb.sql | tee altrdb.sql.out
```

This script enables the system to use the bufferpool specified in the BUFFPAGE parameter previously in the CREATEDB-95.SQL or CREATEDBU.SQL script.

3. If you are creating a Unicode database, execute the CREATEBPU.SQL script using the db2 utility. For example:

For Microsoft Windows:

```
db2 -vf createbpu.sql > createbpu.sql.out
```

For UNIX:

```
db2 -vf createbpu.sql | tee createbpu.sql.out
```

4. Connect to the database and execute XXDDLMS.

The user who runs this script must have read and write authority to the container (for example, /data1/psdb2/ptdbname on UNIX or C:\PS_DB\ptdbname on Microsoft Windows). Make sure the Table Owner ID has read and write authority to these containers.

Note. If you are creating a Unicode database, replace all references to *XXDDLDMs.sql* below with *XXDDLDMsU.sql*.

- a. Connect to the new database by issuing this command (substituting your database name for HR920SYS):
`db2 connect to HR920SYS`
 - b. Execute the SQL script by issuing this command (substituting for hrddldms as appropriate):
For Microsoft Windows:
`db2 -vtf hrddldms.sql > hrddldms.sql.out`
For UNIX:
`db2 -vtf hrddldms.sql | tee hrddldms.sql.out`
 - c. Verify from the generated log file that all tablespaces were created.
5. Execute the DBOWNER.SQL script to create the PS.PSDBOWNER table and create the owner for your PeopleSoft database. Use the following command:
-

Note. If you are creating a Unicode database, replace all references to *DBOWNER.sql* below with *DBOWNERU.sql*.

For Microsoft Windows:

```
db2 -vf dbowner.sql > dbowner.sql.out
```

For UNIX:

```
db2 -vf dbowner.sql | tee dbowner.sql.out
```

6. Execute the PSADMIN.SQL script to grant DBADM privileges to the database owner. Use the following command:

For Microsoft Windows:

```
db2 -vf psadmin.sql > psadmin.sql.out
```

For UNIX:

```
db2 -vf psadmin.sql | tee psadmin.sql.out
```

After the successful execution of all the scripts detailed above, and after the database has been created, review the task *Creating Data Mover Import Scripts*, and the following tasks, to create and execute the Data Mover scripts to populate the database with start-up data.

Task 5A-4: Configuring and Testing Database Connectivity for DB2 Connect or DB2 Client V9.x or Earlier

This section discusses:

- Configuring Database Connectivity for DB2 Connect or DB2 Client V9.x or Earlier
- Testing Client Connectivity for DB2 Connect or DB2 Client V9.x or Earlier

Task 5A-4-1: Configuring Database Connectivity for DB2 Connect or DB2 Client V9.x or Earlier

You must configure client connectivity on the install workstation, and on any other Windows client that needs to make a two-tier connection to the PeopleSoft database. This will be required on any workstation that needs to run COBOL or SQR batch processes on the client. Use the instructions in this section if you are using DB2 Connect or DB2 Client version 9.x or earlier, where x refers to the version number.

See My Oracle Support, Certifications, for information on supported versions.


To configure each workstation connecting to DB2/LUW, you must catalog the database name and an ODBC data source using the DB2 Connect Client Configuration Assistant. You must do this for each PeopleSoft database that you have created.

To install Catalog Database on the Windows client:

1. From the Configuration Assistant panel, click Selected, Add Database Using Wizard to display the Add Database Wizard dialog box.
2. Select the Source page, and then select Manually configure a connection to a DB2 database.
Click Next to display the Protocol page.

3. On the Protocol page, select the option TCP/IP as the communication protocol.

The page will now prompt you to choose a target operating system. Do *not* select OS/400. Click Next.



Selecting a communications protocol

4. On the TCP/IP page, type either the IP address or the DNS name of the server hosting the DB2/LUW database to which you will be connecting in the Host name field.

For the Port number, enter the TCP/IP port number assigned for the DB2 instance (IBM's default value is 50000). Consult your Operating System administrator or DBA for this information.

Add Database Wizard

1. Source
2. Protocol
3. **TCP/IP**
4. Database
5. Data Source
6. Node Options
7. System Options
8. Security Options

Specify TCP/IP communication parameters

You must provide the communication information required to connect to the database that you want to add. Your database administrator can provide the information necessary to configure communications for a database connection. If you specify a Service name only, there must be an existing service name entry in the TCP/IP services file.

Host name:

Service name:

Port number:

Specifying the TCP/IP communication parameters

- On the Database page, enter the database name to which you will be connecting in the Database name field. Note that the Database alias should be the same as the Database name.

Add Database Wizard

1. Source
2. Protocol
3. TCP/IP
4. Database
5. Data Source
6. Node Options
7. System Options
8. Security Options

Specify the name of the database to which you want to connect

You must identify the database to which you are connecting. The database name is dependent on the type of server to which you are connecting. For OS/390 and z/OS databases specify the Location name. For OS/400 databases use the RDB name. For VM/VSE specify the DBNAME. Otherwise use the name of the database on the server.

Database name: T844113C


Database alias: T844113C

Comment:

Back Next Finish Cancel

Specifying the database name

6. On the Data Source page, verify that the check box Register this database for ODBC is selected and the option As a system data source is selected.



Registering the database as a data source

7. Verify the information on the System Option page, including the System name, Host name, and Operating system.

Click Next.

Add Database Wizard

Specify the system options

You must provide the following information in order to configure the system for the database connection.

System name:

Host name:

Operating system:

Comment:

Navigation buttons:

Specifying the system options

8. On the Security Options page, select Server authentication (SERVER) and leave Enable encryption *cleared*.



Specifying the security options

9. Click Finish to complete changes to the Add Database Wizard dialog box.
 10. Modify the DB2CLI.INI file as follows:

For Windows:

```
<DB2 INSTALL DIRECTORY>\db2cli.ini
```

Add the following parameters to the [Common] section. (Create the [Common] section if it does not already exist.)

```
[Common]
IGNOREWARNINGS=1
DISABLEKEYSETCURSOR=1
```

For UNIX:

```
<DB2 INSTALL DIRECTORY>/cfg/db2cli.ini
```

Add the following parameters to the [Common] section. (Create the [Common] section if it does not already exist.)


```
[Common]
IGNOREWARNINGS=1
DISABLEKEYSETCURSOR=1
```

Task 5A-4-2: Testing Client Connectivity for DB2 Connect or DB2 Client V9.x or Earlier

Use DB2 Connect Configuration Assistant to test connectivity to a database on the database server if you are using DB2 Connect or DB2 Client version 9.x or earlier.


To test DB2/LUW client connectivity:

1. In the Configuration Assistant, highlight the database and right-click on Test Connection:




Testing connectivity with Configuration Assistant

2. Select CLI and ODBC. Enter the user ID and password as defined earlier in the task Creating PeopleSoft IDs. See "Preparing for Installation," Creating PeopleSoft User IDs.



Testing connectivity settings

The following example shows the a message saying the connection tested successfully.



Successful connection results page

Note. Pinging or using Telnet tests network communication to the database server, but you must successfully run the connection command above to validate DB2 UDB Client Enabler connectivity.

If you are unable to connect check the following items:

- Review all previous tasks in this chapter.
- Is the DB2/LUW instance started?
- Can you issue the Connect command on the DB2/LUW database server using the CLP?
- Can you log into the database using the user name and password you're using as a Connect ID?
- Does the database exist on the DB2/LUW database server? Is it catalogued on the client?
- Are you spelling the database name properly on the command line? Case does not matter because CLP converts the database name to uppercase.
- On Windows, make sure the \SQLLIB directory is in the PATH.
- On Windows, make sure that environment variable DB2INSTANCE=DB2.
- Check the DB2 UDB db2diag.log diagnosis file, located by default in /<instance-owner home directory>/sqllib/db2dump/.

Note. IBM, or your DB2/LUW vendor, is best equipped to assist you if you have any problems installing any DB2/LUW products or connecting to your DB2/LUW database.

Task 5A-5: Configuring and Testing Connectivity for DB2 Connect and DB2 Client V10.x or Later

This section discusses:

- Configuring Database Connectivity for DB2 Connect and DB2 Client V10.x or Later
- Testing Database Connectivity for DB2 Connect and DB2 Client V10.x or Later

Task 5A-5-1: Configuring Database Connectivity for DB2 Connect and DB2 Client V10.x or Later

You must configure client connectivity on the install workstation, and on any other Windows client that needs to make a two-tier connection to the PeopleSoft database. This will be required on any workstation that needs to run COBOL or SQR batch processes on the client. Use the instructions in this section if you are using DB2 Connect or DB2 Client version 10.x or later, where x refers to the version number.

See My Oracle Support, Certifications, for information on supported versions.

Note. Configuration Assistant has been deprecated from version 10.x DB2 Connect and DB2 Client products so creating and updating the DB2 Client Catalog must be done manually.

To create and update the DB2 Client catalog, open a DB2 Command window for the client you wish to create the db2 catalog on and run the following commands to catalog the TCPIP NODE and the DB2 DATABASE:

```
db2 catalog TCPIP node <NODE-NAME> remote <DB2-DATABASE-HOST-NAME> server =>
<DB2-COMMUNICATION-PORT-NUMBER>
db2 catalog DATABASE <DATABASE-NAME> as <ALIAS-NAME> at node <NODE-NAME>
```

For example, to catalog a DB2 database on AIX:

```
db2 catalog TCPIP node TCPAIX06 remote qt-ibm06 server 5000
db2 catalog DATABASE T854U40 as T854U40 at node TCPAIX06
```


Task 5A-5-2: Testing Database Connectivity for DB2 Connect and DB2 Client V10.x or Later

To test the database connectivity, run the following command:

```
db2 connect to <DATABASE-NAME> user <USER-ID> using <USER-PASSWORD>
```

For example:

```
db2 connect to T854U40 user people using people
```

Task 5A-6: Configuring an ODBC Data Source for Connectivity on Microsoft Windows

This task applies only to installations on Microsoft Windows operating systems. Use these instructions to configure and validate a 64-bit ODBC data source for connectivity to PeopleSoft PeopleTools components including PeopleSoft Application Server, Application Designer and Data Mover.

This section assumes that you have installed a supported version of DB2 Client or DB2 Connect.

See My Oracle Support, Certifications.

To configure a 64-bit data source for PeopleSoft PeopleTools components:

1. Select Start, IBM DB2, *instance id*, Command Line Tools, Command Window.

For example, if you accepted the default, *instance id* would be DB2.

The Command Window opens.

2. Run the following command and confirm that the response specifies that the DB2 Client or DB2 Connect installation is 64-bit:

```
db2level
```

3. Run the following commands, specifying your DB2/LUW PeopleSoft database name:

```
db2 catalog system odbc data source <database-name>
db2 terminate
```

4. Run the following command and confirm that your data source for your database is now registered.

```
db2 list system odbc data sources
```

5. To validate, start your Application Server, Application Designer, or Data Mover.

You should not get any connectivity errors.

If the 64-bit data source is not properly configured, you see an error similar to the one below. This is an example of an error seen when starting PeopleSoft Application Server:

```
PSADMIN.3992 (0) [12/30/11 00:22:52] (0) Begin boot attempt on domain⇒
Q8533I1E
```

```
PSAPPSRV.3612 (0) [12/30/11 00:23:04] (0) PeopleTools Release 8.55 ⇒
(Windows) starting. Tuxedo server is APPSRV(99)/2
```

```
PSAPPSRV.3612 (0) [12/30/11 00:23:04] (0) Cache Directory being used: d:⇒
```

```
\pshome\appserv\Q8533I1E\CACHE\PSAPPSRV_2\
```

```
PSAPPSRV.3612 (0) [12/30/11 00:23:04] (3) File: SQL Access ManagerSQL⇒
error.
```

```
Stmt #: 2 Error Position: 0 Return: 8600 - [Microsoft][ODBC Driver⇒
Manager]
```

```
The specified DSN contains an architecture mismatch between the Driver⇒
and Application (SQLSTATE IM014) 0
```

```
PSAPPSRV.3612 (0) [12/30/11 00:23:04] (1) GenMessageBox(200, 0, M): SQL⇒
Access Manager: File: SQL Access ManagerSQL error. Stmt #: 2 Error⇒
Position: 0 Return: 8600 - [Microsoft][ODBC Driver Manager] The⇒
specified DSN contains an architecture mismatch between the Driver and⇒
Application (SQLSTATE IM014) 0
```

```
PSAPPSRV.3612 (0) [12/30/11 00:23:04] (1) GenMessageBox(0, 0, M):⇒
Database Signon: Could not sign on to database Q8533I1E with user⇒
QEDMO.
```

```
PSAPPSRV.3612 (0) [12/30/11 00:23:04] (0) Server failed to start
```

```
PSADMIN.3992 (0) [12/30/11 00:23:11] (0) End boot attempt on domain⇒
Q8533I1E
```

Task 5A-7: Creating Data Mover Import Scripts

This section discusses:

- Understanding Data Mover Import Scripts
- Working with Multilingual Databases
- Running Database Setup to Create Data Mover Import Scripts

Understanding Data Mover Import Scripts

The Data Mover Import scripts are used to populate the PeopleSoft database with data. You use the Database Setup feature of the PeopleSoft Data Mover utility to create the Data Mover import scripts.

Note. This task and the next one (Running Data Mover Import Scripts) should be executed from a Microsoft Windows client machine. Before you can load PeopleSoft data from a Microsoft Windows client machine, you need to install PeopleSoft PeopleTools and your PeopleSoft Application to the Microsoft Windows client machine and be sure to select File Server and Database Server.

To complete the database creation procedure you must supply information on various authorization IDs and passwords, including Access ID, Connect ID, Symbolic ID, and User IDs. Before beginning this procedure, review the information in the section Planning Database Creation and make a note of the authorization information for your environment. For PeopleSoft PeopleTools 8.53 and later releases, the user profiles in PeopleTools demo databases are delivered disabled. During the procedure to create Data Mover import scripts you will choose whether to enable the delivered user profiles, and how to assign passwords for the profiles. In addition, you will supply several passwords that were previously provided as defaults. Be sure to note the passwords that you supply, as they will be needed for subsequent installation procedures.

See the information on administering user profiles in the *PeopleTools: Security Administration* product documentation.

See "Preparing for Installation," Planning Database Creation.

Task 5A-7-1: Working with Multilingual Databases

All PeopleSoft releases are shipped with English as the database's base language. Therefore when selecting components for the Data Mover Import script, you must select the English components in addition to any other languages you are installing. After the installation is complete, you can change the database's base language to the language that you plan to use most frequently, or leave the base language as English.

Read the section Planning Multilingual Strategy for information on installing multiple languages and changing your base language.

See "Preparing for Installation," Planning Multilingual Strategy.

If you are creating a database and want to load Oracle-provided translations for non-English languages, you must load English (ENG) in addition to the foreign language components.

If you are creating a non-Unicode database, you must ensure that the languages you select are all supported by the character set you used to create your database.

Note. During the database setup process, you have the option to select the database's base language. Select the language that you plan to use most frequently. If the database's base language is different than that set in this database setup process, generate the `SWAP_BASE_LANGUAGE` command in the Data Mover Import script to swap the language.

See *PeopleTools: Global Technology*.


Task 5A-7-2: Running Database Setup to Create Data Mover Import Scripts

To create the import scripts using Data Mover:

See *PeopleTools: Data Management*.

1. Run Configuration Manager by using one of the following methods:
 - On Microsoft Windows 2012 R2, access the Apps screen and navigate to PeopleTools 8.57, Configuration Manager.
 - Run `PS_HOME\bin\client\winx86\pscfg.exe`.

2. Verify in the Signon Defaults on the Startup page that the Database Type of DB2 UDB for Unix, NT is selected, as shown in the example.



Startup tab on the Configuration Manager dialog box

3. Verify that the connect ID is correct.
If you accepted all defaults, the connect ID is people. Enter and confirm a value for the connect ID password.
4. If the *PS_APP_HOME* location is not the same as *PS_HOME*, make sure it is set in Configuration Manager, as follows:
 - a. In Configuration Manager, select Profile.
 - b. Highlight the Default Profile and select Edit.
 - c. On the Edit Profile dialog box, select the Process Scheduler tab.
 - d. Verify that the *PS_APP_HOME* value is correct.
See "Setting Up the Install Workstation," Editing the Default Profile.
5. Run Data Mover by using one of these methods:


- On Microsoft Windows systems, access the Apps screen or Start menu, and navigate to PeopleTools 8.57, Data Mover.
 - Run `PS_HOME\bin\client\winx86\psdmt.exe`.
6. Log on using the access ID as the user id to start Data Mover in bootstrap mode; this should be the user that creates the database.

See Checking the Log Files and Troubleshooting, Running Data Mover.

Note. You must limit the access ID to eight characters or less. See "Preparing for Installation," Creating PeopleSoft User IDs, for access ID password requirements.

7. Select File, Database Setup.

The Database Setup dialog box appears, as shown in this example:



Selecting target database and character set on the Database Setup dialog box

8. Select your database platform from the Select Target Database drop-down list.
9. Select your database type, Unicode or non-Unicode, and character set.

Choose the Database Type—Unicode or Non-Unicode—that you selected in the section on multilingual

strategy. If you choose Non-Unicode, select the character set that you decided upon in that section from the drop-down list.

Note. When you select a non-Unicode character set, only the characters within that character set can be stored in your database. Oracle recommends that you create your database using Unicode.

See "Preparing for Installation," Planning Multilingual Strategy.

Note. The database setup does not actually modify the character set of your database. That is done by the DBA during database creation. The database setup process only creates customized scripts based on your selection.

10. Select the Demo or System radio button, depending on which type of PeopleSoft database you are installing.
-

Note. If you are using the PeopleSoft Upgrade Source Image, you must create a Demo database.

11. Select the Products for which you want to create a Data Mover script from the PeopleSoft Application list box, and move the items you have selected into the Data Mover Scripts to Create list box by clicking on the Add or Add All button.

If you installed the Multilanguage software, each application will be listed several times, once for each language. If you are installing languages other than English, make sure to select the appropriate language data files for each application you select in English. This will load the translated database objects.

See "Preparing for Installation," Planning Multilingual Strategy.

If you are installing an application in any language other than English, you must also select the English component of the application. For example, if you select PeopleSoft Fin/SCM - French, you must also select PeopleSoft Fin/SCM Database - US English. This ensures that you install the necessary base-language components.

12. Set the database parameters described below and then click Finish.

Database Setup - Database Parameters

Database Parameters

Database Name: FSCMPROD

Symbolic ID: db2adm

Access ID: db2adm

Access Password:

Connect ID: people

Application Server ID:

Application Server Password:

Web Server ID: PTWEBSERVER

Web Server Password:

☒ Enable All Profiles ☒ Set Global Password

Global Password:

< Back Finish Cancel

Specifying Database Parameters on the Database Setup dialog box

- **Database Name:** Specify the database name that users will enter on the PeopleSoft signon screen. This corresponds to the owner ID. It can be up to eight characters long and must be entered in uppercase.
- **Symbolic ID:** This is used as the key to retrieve ACCESSID and ACCESSPSWD from PSACCESSPROFILE.
For initial installation set it equal to the Database Name. The symbolic ID cannot be longer than eight characters.
- **Access ID:** Specify the user you used to create the database. Limit this to eight characters or less.
This value is case sensitive. You will use the access ID every time you want to sign on to Data Mover in bootstrap mode. Limit this to eight characters or less.
See "Preparing for Installation," Creating PeopleSoft IDs for more information about access IDs.
- **Access Password:** This is the PeopleSoft access ID password. See "Preparing for Installation " for access ID password requirements.
- **Connect ID:** This is the connect ID that is used for the initial connection to DB2/LUW. This ID is used for connecting to the database. Limit this to eight characters or less.

Note. The connect ID was defined as a valid logon ID in the database security management software. The connect ID only needs to be granted SELECT access on PSACCESSPROFILE, PSOPERDEFN, and PSSTATUS. This ID should be granted no other database authorities.

Refer to the section Creating PeopleSoft IDs in the chapter "Preparing for Installation " for more information about connect IDs.

- *Application Server ID:* The Application Server ID has privileges to start or shut down the Application Server domain. It is also used during the Application Server configuration. Enter one of the delivered PeopleSoft user IDs.
- *Application Server Password:* Specify a password for the Application Server ID.
- *Web Server Password:* Specify a password for the Web Server ID.

The default Web Server ID, as displayed in the example, is PTWEBSERVER. The Web Server ID, also referred to in this documentation as Web Profile User ID, is used to access the web profile information from the database through the Application Server Jolt service.

- *Enable All Profiles:* Select this option to leave the User profiles (other than the Application Server profile and the Web Server User profiles) unchanged.

If you do not select this option, all of the User profiles in the database, with the exception of the Application Server profile and Web Server User profiles, remain disabled as delivered.

- *Set Global Password:* If you enabled all profiles, you can choose to set the same password for all of the profiles.

Note. This option is enabled when the Enable All Profiles option is selected, as shown in the example.

- *Global Password:* Enter the password to be used for all user profiles.

Note. This option is enabled when the Set Global Password option is selected, as shown in the example.


Note. The connect ID was defined as a valid logon ID in the database security management software. The connect ID only needs to be granted SELECT access on PSACCESSPROFILE, PSOPERDEFN, and PSSTATUS. This ID should be granted no other database authorities.

13. Select your database's base language.

Note. This window appears only if you selected a database for a language other than English. If you see this window it is critical to select the correct base language. When you select a base language other than ENG, DBSETUP generates the Data Mover import script with the `SWAP_BASE_LANGUAGE` command to swap the base language.

See "Preparing for Installation," Planning Multilingual Strategy.

See Working with Multilingual Databases.



Selecting a base language in the Database Setup dialog box

Use the following information in making your selection:

- If you have not already done so, read the earlier section on multilingual strategy before determining whether to install multiple languages and whether to change your base language.
- If you are creating a database and want to load Oracle-provided translations for non-English languages, you must load English (ENG) in addition to the foreign language components.
- All PeopleSoft releases are shipped with English as the database's base language. Therefore when selecting components for the Data Mover Import script, you must select the English components in addition to any other languages you are installing. During the Database Setup wizard, you need to select the database's base language that you plan to use most frequently. If your database's base language is different than the Database Setup wizard generate the `SWAP_BASE_LANGUAGE` command in the Data Mover Import script to swap the language.
- If you are creating a non-Unicode database, you must ensure that the languages you select are all

supported by the character set you used to create your database.

14. Click Finish.

Note. If the Database Setup - Base Language window does not appear, click Finish after supplying the parameters on the Database Setup - Database Parameters window.

At this point you are in Data Mover, with the DMS script you just created ready to run.

See Also

PeopleTools: Data Management

PeopleTools: Security Administration, "PeopleSoft Authorization IDs"

Task 5A-8: Running Data Mover Import Scripts

This section discusses:

- Understanding Data Mover Import Scripts
- Populating Tables in the PeopleSoft Database

Understanding Data Mover Import Scripts

Now you will run the Data Mover scripts (DMS) that you created in the preceding task to import the data for your PeopleSoft database. The Data Mover script creates either a system (SYS) or a demo (DMO) database.

When you initially logged onto Data Mover to create the DMS scripts, you logged in with the Access ID and password, using bootstrap mode. You need to use bootstrap mode to run the Data Mover import script, because there are not yet any PeopleSoft security tables in the database.

When you start Data Mover in bootstrap mode, the word "BootStrap" appears in the Data Mover status bar.

See *PeopleTools: Data Management*.

See Also

Checking the Log Files and Troubleshooting, Running Data Mover

Task 5A-8-1: Populating Tables in the PeopleSoft Database

To populate tables in the PeopleSoft database:

1. The DMS import script for your application will contain hard-coded file names for log files and data files.
Modify the DMS script if you have moved any files from the delivered directories or want to write log files to another location than that specified in the script.
2. Select File, Run to execute the script.

When you run the script, Data Mover typically performs the following actions:

- IMPORT *
Create all the PeopleTools and application tables with their indexes.

- **ENCRYPT_PASSWORD ***
Encrypt security information for the database.
- **CREATE_TRIGGER ***
Create application required triggers.
- **REPLACE_VIEW ***
Create PeopleSoft views.
- **CREATE_TEMP_TABLE ***
Create PeopleSoft temporary tables.

Task 5A-9: Cleaning Up Orphaned Language Data

Perform this task if you are a Multilingual customer and are installing non-English languages. This task assumes that you have loaded the necessary language files. If you have not yet loaded the language files, follow the instructions in the Global Technology product documentation.

See *PeopleTools: Global Technology*, "Adding Translations to an Existing Database on the Same PeopleTools Version."

The Application Engine program PTIACLEANLNGCA removes any orphaned related language objects that do not have a matching base language object.

Run the PTIACLEANLNGCA application engine program. From the command line utility, the syntax is:

```
<PS_HOME>\bin\client\winx86\psae -CD <dbname> -CT DB2UNIX -CO <oprid> -CP=>  
<pswd> -R <run_control> -AI PTIACLEANLNGCA -FP <log_path>
```

Use the values for the database name and user ID that you entered on the startup tab of the Configuration Manager for <dbname> and <userid> respectively. However, be aware that <userpswd> is not the same as the connect password you entered on the Configuration Manager startup tab. Enter a value for <userpswd> that is the password associated with the <userid>. For <log_path>, specify the path where you want the log file for the application engine program to be generated, such as C:\temp\.

Task 5A-10: Checking the Log Files and Troubleshooting

This section discusses:

- Checking the Log Files
- Running Data Mover
- Troubleshooting
- Improving Performance

Task 5A-10-1: Checking the Log Files

After running each Data Mover script, examine the .LOG files to make sure that all the commands were executed successfully. The log files are located in the directory you specified in the Data Mover script.

See "Setting Up the Install Workstation," Editing the Default Profile.

Task 5A-10-2: Running Data Mover

Use one of these methods to run Data Mover.

Microsoft Windows

- Depending upon your Microsoft Windows operating system, select PeopleTools 8.57, Data Mover from the Start, Programs list or the Apps screen to run a graphical user interface (GUI mode).
- Run `PS_HOME\bin\client\winx86\psdmt.exe` from the command line.

On UNIX, run `PS_HOME/bin/psdmtx` from the command line.

If you use the access ID that you specified during the database configuration to log on, you log on in "bootstrap mode." When you start Data Mover in bootstrap mode, the word "BootStrap" appears in the Data Mover status bar.

If you use a valid PeopleSoft Operator ID, such as PS for Human Capital Management or VP1 for Financials/Supply Chain Management, you log on in "user mode." In this mode, no designation appears in the Data Mover status bar.

See Also

PeopleTools: Data Management

Task 5A-10-3: Troubleshooting

If the DMS script has stopped midway (this can happen for a number of reasons) you need to edit the script and start again.

If running a script results in an SQL error, it may be because the PS.PSDBOWNER table contains duplicate rows, an invalid user ID is specified, or the Owner ID column in the PSLOCK table is specified in uppercase or is incorrect. If this is the case fix PS.PSDBOWNER.

To edit and restart the DMS script:

1. Determine the record that was being imported (that is, which IMPORT command was running) when the script stopped, and use the following guidelines to edit and rerun the DMS scripts.

When building a DMO database or a multilingual database, adding the SET START statement can be tricky because the Data Mover script used to load the database will include more than one IMPORT statement. The key is to view the log files and determine which IMPORT section of the script Data Mover failed on.

- If the failure occurred during the first IMPORT statement, add the SET START statement before the first IMPORT *; statement.
- If the failure occurred during a subsequent IMPORT statement, comment out all statements preceding the IMPORT *; statement where the failure occurred and add the SET START statement before the IMPORT *; statement of the section in which the failure occurred.
- *This is very important:* If you see any "unique index constraint" error messages in the "Building required indexes" section, your IMPORT script failed during a subsequent IMPORT but the SET START statement was added to the first IMPORT. In this situation, you can run the Data Mover script in its originally generated form, with only one modification. In the first IMPORT section, change the statement "IMPORT *;" to "REPLACE_DATA *;". This will delete all the data in the tables, and re-import it. This process will take some time to run, and you will need to separately create each of the indexes that failed.

2. Run Data Mover as previously described.

See Running Data Mover.

The PeopleSoft Logon dialog box appears.

3. Log on using the Access ID to start Data Mover in *bootstrap mode*.

Use the Access ID you specified when you created the Data Mover scripts with the Database Setup utility.

The input window should display the DMS import script for the database. The script has the format
<dbname>dbx.dms.

4. If necessary, select File, Open, and browse to the *PS_APP_HOME/scripts* directory to find the appropriate DMS script.
5. Add the following line before the offending IMPORT command (the one being executed when the failure occurred):

```
SET START <RECORD NAME>;
```

<RECORD NAME> is the name of the record that failed. Make sure to review the Data Mover log file to see where the script failed and locate the last record that imported successfully. The SET START command will begin the Data Mover import at the specified record name.

Note. It is a good idea to change the name of the log file in the script before each attempt at running it. This ensures that you have a separate log file for each attempt, if you run the import more than once.

For example, if the script stops and the table is partially inserted with a message similar to this one:

```
Importing PSPNLFIELD
Rows inserted into PSPNLFIELD

3000
```

First drop the partially inserted table (for example, record) by using the DROP TABLE command, and then restart Data Mover at the record that failed using the SET START command and continue the Data Mover import. This can be done in a single pass.

Add the following lines before the offending IMPORT *; command (the one being executed when the failure occurred):

```
SET START <RECORD NAME>;
DROP TABLE <RECORD NAME>;
```

where <RECORD NAME> is the name of the record that failed. The SET START statement will begin the Data Mover import at the specified <RECORD NAME>.

Example of the original script:

```
REM - PeopleSoft Database - US English
/
SET LOG epengs.log;
SET INPUT epengs.db;
SET COMMIT 30000;
SET NO VIEW;
SET NO SPACE;
SET NO TRACE;
SET UNICODE ON;
IMPORT *;
```

Example of script after modification, with changes in bold font:

```
REM - PeopleSoft Database - US English
/
```

```

SET LOG epengs2.log;
SET INPUT epengs.db;
SET COMMIT 30000;
SET NO VIEW;
SET NO SPACE;
SET NO TRACE;
SET UNICODE ON;
SET START PSPNLFIELD;
DROP TABLE PSPNLFIELD;
IMPORT *;

```

For the DROP statement, for records with a recname without a leading PS, add PS_ to the beginning of the recname; otherwise the table will not be found. For example, PS_<RECNAME>.

6. Restart the script in Data Mover by selecting File, Run Script, or use the `psdmtx` command to execute Data Mover on the command line.

Task 5A-10-4: Improving Performance

The following tips can help you save time when running the Data Mover scripts:

- Run Data Mover from the fastest workstation available.
- Run Data Mover on the database server.
- Run only a single instance of Data Mover, and do not have any other applications running during the import.
- In the PeopleSoft Configuration Manager, turn off all trace options.

Tracing during a DMS load will add considerable time to the process.

- Copy the database file over to the workstation so that Data Mover can access it locally instead of over the network.
- Run Data Mover on the database server with the .db or .dat file located locally.

If you are comfortable changing the options available for a DB2/LUW instance and database, you might consider "tuning" the instance and database used for the import. Some of these options are appropriate only during the import, so you may not want to keep them in effect after the import is complete.

Task 5A-11: Changing the Base Language

The information in the earlier task Planning Multilingual Strategy will help you determine whether you should change your base language, and lists the currently supported languages.

See "Preparing for Installation," Planning Multilingual Strategy.

See PeopleTools Certifications — Supported Languages, My Oracle Support (search for article name).

This task applies only if your users will be operating PeopleSoft applications *primarily* in one particular language other than English. It gives a performance boost to the language you designate as the base language, but requires more administrative overhead than leaving English as the base language. The details are spelled out in the *PeopleTools: Global Technology* product documentation.

Chapter 5B

Creating a Database on UNIX

This chapter discusses:

- Understanding the Database Configuration Wizard
- Fulfilling PeopleSoft Database Configuration Wizard Prerequisites
- Using the Database Configuration Wizard in Silent Mode
- Changing the Location of the DB2/LUW Database Log Files
- Cleaning Up Orphaned Language Data
- Checking the Log Files and Troubleshooting

Understanding the Database Configuration Wizard

The Database Configuration Wizard is a tool designed to simplify your PeopleSoft database installation. When you run the Database Configuration Wizard, Data Mover is also running silently.

See *PeopleTools: Data Management*.

Important! Do not forget that application-specific installation steps are provided in a separate document specific to the application. For instance, if you are performing PeopleSoft CRM installation, you need both this PeopleSoft PeopleTools installation guide and you also need any additional instructions provided by CRM. My Oracle Support provides installation guides that are specific to your application.

See My Oracle Support, (search for "installation," the application name, and release).

You also have the option of using a manual process for creating a PeopleSoft database, instead of using the Database Configuration Wizard. The manual process is mandatory for some configurations.

See "Creating a Database Manually on Microsoft Windows or UNIX."

Note. If you are using the PeopleSoft Upgrade Source Image, you must create a Demo database.

Note. For the sake of brevity, this documentation sometimes refers to DB2 UDB for Linux, UNIX, and Windows as *DB2/LUW*.

After you complete the tasks in this chapter, read the chapter "Completing the Database Setup." Depending upon your environment, you may not need to carry out every task in that chapter. However it is important that you evaluate the requirements and perform the necessary tasks.

Task 5B-1: Fulfilling PeopleSoft Database Configuration Wizard Prerequisites

This section discusses:

- Installing the PeopleSoft Database Server Components on the Database Server
- Changing the Ownership for the PS_APP_HOME Directory
- Defining User Groups
- Creating the Data Directory
- Completing Registry Settings
- Rebinding of Packages Requirement
- Completing Required CLI Settings in the DB2CLI.INI File
- Defining Database Manager Configuration
- Defining Database Configuration
- Running the Shell Script psconfig.sh

Task 5B-1-1: Installing the PeopleSoft Database Server Components on the Database Server

To run the PeopleSoft Database Configuration Wizard, your setup *must* fulfill these requirements:

- You must have installed the Database component of your application installation software to your database server.
- You must have the PeopleTools Development Environment set up to create your database.
- You must have the Oracle Tuxedo software installed before you run the Database Configuration Wizard.
 - The Database Configuration Wizard invokes the PeopleSoft Data Mover utility. Data Mover on the UNIX platform has a dependency on the Oracle Tuxedo software. Install Oracle Tuxedo and verify that the TUXDIR environment variable is set.
See Installing Oracle Tuxedo.
- You must run the Database Configuration Wizard at the database server.

Note. Before you can configure the database, the system administrator ID must have a corresponding password.

See the information on PeopleSoft Configuration Manager in the *PeopleTools: System and Server Administration* product documentation.

See Also

"Using the PeopleSoft Installer"

"Setting Up the Install Workstation"

Task 5B-1-2: Changing the Ownership for the PS_APP_HOME Directory

Before running the Database Configuration Wizard, change the ownership of the *PS_APP_HOME* directory. The user who runs the Database Configuration Wizard must have write permission to the *PS_APP_HOME* directory to access logs and scripts. After completing the database setup, you can revoke the permission.

Task 5B-1-3: Defining User Groups

The user who runs the Database Configuration Wizard (psadm1) must have db2grp and pshome groups as primary and secondary groups.

Task 5B-1-4: Creating the Data Directory

The Database Configuration Wizard requires the name of a directory where the database will reside. You must create the data directory before running the Database Configuration Wizard.

When filling out the response file, specify the full path for the data directory for the parameter DB_DIR_NME.

Task 5B-1-5: Completing Registry Settings

For the Database Configuration Wizard to run successfully, certain DB2 UDB for Linux, UNIX, and Windows registry settings must be set. These settings are required for the Database Configuration Wizard and PeopleSoft PeopleTools to function properly:

Required DB2/LUW Registry Setting	Purpose
db2set DB2CODEPAGE=1208 (Unicode only)	Sets the client codepage to Unicode.
db2set DB2_MIN_DEC_DIV_6=yes	Supports decimal precision up to 31 decimal places.

Task 5B-1-6: Rebinding of Packages Requirement

For DB2/LUW clients that are at a higher fixpack than the server, a rebind of the DB2/LUW utilities packages and CLI packages is required for each new database that the client will be accessing. The rebind is required because our truncate table support uses the DB2/LUW import function to truncate the table. The import function requires rebinding of the DB2/LUW utilities package. The commands for rebinding are:

```
"DB2 bind @db2ubind.lst blocking all grant public" for DB2 utilities⇒
packages.
```

```
"DB2 bind @db2cli.lst blocking all grant public" for CLI packages.
```

Task 5B-1-7: Completing Required CLI Settings in the DB2CLI.INI File

Complete the following required CLI settings in the DB2CLI.INI file. These settings are required for the Database Configuration Wizard and PeopleSoft PeopleTools to function properly.

- DISABLEKEYSETCURSOR=1 (COMMON STANZA)

This is needed for SQR to function properly.

- IGNOREWARNINGS=1 (DATABASE STANZA)

This is used to suppress the warning message that appears when an UPDATE or DELETE statement is executed without a WHERE clause.

Note. The default DB2CLI.INI file delivered by IBM does not contain the COMMON STANZA or DATABASE STANZA. You will need to edit the DB2CLI.INI file and add the COMMON STANZA or DATABASE STANZA. Below is an example of COMMON STANZA and DATABASE STANZA for database ABC to be added to the DB2CLI.INI file.

[COMMON]

DISABLEKEYSETCURSOR=1

[ABC]

IGNOREWARNINGS=1

Task 5B-1-8: Defining Database Manager Configuration

The DB2/LUW database manager configuration parameters are in the dbmcfg.sql file. These are the minimum requirements provided by Oracle for the database manager configuration. But these dbm parameters are *not* necessarily the optimal configuration for your environment. You may need to configure your DB2/LUW instance so that it is optimal for your environment.

Task 5B-1-9: Defining Database Configuration

The database configuration parameters are in one of the following files:

- CREATEDB-95.SQL — Non-Unicode
- CREATEDBU.SQL — Unicode

These are the minimum requirements provided by Oracle for creating a PeopleSoft database. But these database parameters are *not* necessarily the optimal database configuration. You will need to tune it for your environment. You can add to or update the CREATEDB-95.SQL or CREATEDBU.SQL file with the appropriate database parameters for your environment because the Database Configuration Wizard will use it as a template to create a PeopleSoft database.

Beginning with PeopleSoft PeopleTools 8.53, new tablespaces PSIMAGE2, PSIMAGE2IDX, and PSIMAG2LOB are delivered. These tablespaces are created with pagesize 16K (non-Unicode) and 32K (Unicode), and bufferpool size 16K (non-Unicode) and 32K (Unicode). These required tablespaces contain tables with LOB (CLOB/DBCLOB/BLOB) data types.

See PeopleTools 8.53 Release Notes, My Oracle Support.

Before running the Database Configuration Wizard, verify that the XXDDLDMMS.SQL (non-Unicode) and XXDDLDMMSU.SQL (Unicode) scripts include these tablespaces (XX is a two-character code corresponding to the product line you are installing).

See "Creating a Database Manually on Microsoft Windows or UNIX," Editing SQL Scripts.

Task 5B-1-10: Running the Shell Script psconfig.sh

The shell script psconfig.sh sets up the environment for Data Mover to run. The PeopleSoft Data Mover utility is used to load the database.

To run `psconfig.sh`:

1. Change the directory to `PS_HOME`.
2. Run `psconfig.sh (. /psconfig.sh)`

Task 5B-2: Using the Database Configuration Wizard in Silent Mode

This section discusses:

- Understanding the Database Configuration Wizard
- Preparing the Response File
- Running the Silent Mode Database Creation

Understanding the Database Configuration Wizard

When you run the Database Configuration Wizard, Data Mover typically performs the following actions:

1. `IMPORT *`. Create all the PeopleTools and application tables with their indexes.
2. `ENCRYPT_PASSWORD *` Encrypt security information for the database.
3. `CREATE_TRIGGER *` Create application-required triggers.
4. `REPLACE_VIEW *` Create PeopleSoft views.
5. `CREATE_TEMP_TABLE *` Create PeopleSoft temporary tables.

If Data Mover fails at any of the above steps, it will complete the rest of the steps but will not start the next step—instead the Database Configuration Wizard aborts and tells the user what file to review for the detailed error message. If Data Mover fails at step 1 or 2, it is fatal. If Data Mover fails at step 3 or 4, it is not necessarily fatal. You may continue the next step(s) manually.

To complete the database creation procedure you must supply information on various authorization IDs and passwords, including Access ID, Connect ID, Symbolic ID, and User IDs. Before beginning this procedure, review the information in the section Planning Database Creation and make a note of the authorization information for your environment. For the current release, the user profiles in PeopleTools demo databases are delivered disabled. During the database configuration procedure you will choose whether to enable the delivered user profiles, and how to assign passwords for the profiles. In addition, you will supply several passwords that were previously provided as defaults. Be sure to note the passwords that you supply, as they will be needed for subsequent installation procedures. See the information on user profiles in the *PeopleTools: Security Administration* product documentation.

Note. The Database Configuration Wizard is not supported on Microsoft Windows.

Note. Oracle supports a number of versions of UNIX and Linux in addition to Microsoft Windows for the PeopleSoft installation. Throughout this book, there are references to operating systems. Where necessary, this book refers to specific operating systems by name (for example, Oracle Solaris, IBM AIX, HP-UX, or Linux); however, for simplicity the word UNIX is often used to refer to all UNIX-like operating systems, including Linux.

Task 5B-2-1: Preparing the Response File

In the current release, the Database Configuration Wizard is run in silent mode. In silent mode, you provide the required information in a response text files and run the script without further interaction. After installation, you can find a sample response file, `dbx_resp_file.txt`, in `PS_HOME/setup/PsMpDbInstall`.

The response file is organized with basic and RDBMS-specific sections, with explanations for many entries. Copy the file and modify the values for your environment. Save the file in a location referred to in this section as `<path_to_response_file>`. To exclude a line of text in the file, enter a pound sign (#) at the beginning of the line.

1. Review the comments and instructions.

Note the command to run the silent installation, and the proper syntax for specifying paths in UNIX.

```
#
# Response file for Database Configuration Wizard (DCW)
# 1. In Linux or UNIX:
#   Go to PS_HOME/setup/PsMpDbInstall and run the following command:
#   setup.sh -f <path_to_response_file>
#
# 2. Change the values for your environment.
#
```

2. Specify the location for the PeopleSoft application software, `PS_APP_HOME`.

Note that the DPK installation requires that the `PS_APP_HOME` location, where the PeopleSoft application is installed, is different than the `PS_HOME` location where the PeopleSoft PeopleTools software is installed. The `PS_HOME` location cannot be changed in the Database Configuration Wizard response file.

```
#####
```

BASIC Input

```
#####
```

```
#The following inputs are required in the response file for
#silent installation.
#PS_HOME=Installation location.
#Do not change anything. It will be determined automatically
#by the installer.
PS_APP_HOME=/home/fscm_app_home
```

```
#If you have installed PeopleSoft Applications outside
#PeopleTools PS_HOME then choose the PeopleSoft Applications
#home PS_APP_HOME, else leave the default PS_HOME.
```

3. To create a DB2/LUW database, choose `DB_SERVER_TYPE=DB2UNIX`, and leave the comment characters in front of the other selections.

```
#DB_SERVER_TYPE=ORA
#DB_SERVER_TYPE=MSS
#DB_SERVER_TYPE=DB2
DB_SERVER_TYPE=DB2UNIX
#DB_SERVER_TYPE=DB2ODBC
```

4. Specify whether you want to create a Demo or System database for `DB_TYPE`.

```
# DB_TYPE=DMO/SYS
# This specifies the type of database you want to create.
# Specify DMO for Demo Database or SYS for System Database.
#
CREATE_DB_TYPE=DMO
```

5. To create a Unicode database, specify 1 (one) for the UNICODE parameter, or 0 (zero) for non-Unicode.

Oracle recommends Unicode, but also supports non-Unicode (legacy) code sets, in PeopleSoft databases. Use the values listed previously to specify the character set for DB_CHARSET_CODE and description for DB_CHAR_DES.

See "Preparing for Installation," Planning Multilingual Strategy for information on allowed character sets.

If you decide to use Unicode for your database, you do not need to select a character set.

```
#UNICODE=0
# This value is determined in unicode.cfg.
# Specify the value here to override that setting.
#
UNICODE=1
DB_CHARSET_CODE=UTF8/UCS2
DB_CHAR_DES=DB2 Codepage 1208
```

For a non-Unicode database, specify a supported code set:

```
#UNICODE=0
# This value is determined in unicode.cfg.
# Specify the value here to override that setting.
#
UNICODE=0
DB_CHARSET_CODE=ISO8859-1
DB_CHAR_DES=Western European Languages
```

6. The base language selection (BASE_LANGUAGE) is used to determine what primary base language you want to run the PeopleSoft application on.

If you choose a language other than English, the base language will be swapped during the database creation script. See "Preparing for Installation," Planning Multilingual Strategy. This step applies only if your users will be operating PeopleSoft applications primarily in one particular language other than English. This step gives a performance boost to the language you designate as the base language, but would require more administrative overhead than leaving English as the base language does. See *PeopleTools: Global Technology*.

```
BASE_LANGUAGE=ENG
#APP_LANGUAGE = UKE
```

7. Specify the user name for the Connect ID, and the Connect ID password.

The Connect ID must be eight characters or less. The password for the Connect ID must be between 6 and 30 characters and cannot contain any percent characters (%).

```
DB_DB_NAME=FSDMO
PS_CONNECT_ID=people
PS_CONN_PWD=password
PS_CONN_PWD_RETYPE=password
```

8. Specify the Application Server User ID and password.

The password should contain only alphanumeric characters and is between 1 and 32 characters in length.

```
PS_APP_USER=PS
PS_APP_PWD=password
PS_APP_PWD_RETYPE=password
```

9. Specify the user ID and password for the PTWEBSEVER profile.

The default Web server user is PTWEBSEVER. The Web Server user ID, also referred to in this documentation as Web Profile User ID, is used to access the web profile information from the database through the Application Server Jolt service.

The password should contain only alphanumeric characters and is between 6 and 32 characters in length.

```
PS_WEB_USER=PTWEBSEVER
PS_WEB_PWD=password
PS_WEB_PWD_RETYPE=password
```

10. Set the parameter ENABLE_USERPROFILE to 1 (one) to leave the User profiles (other than the Application Server User Profile and Web server User profiles) unchanged. Set this option to 0 (zero) to disable all the User profiles in the database except the Application Server User Profile and Web server User profiles.

```
ENABLE_USERPROFILE=1
```

11. Specify how to set the user passwords.

- Set the parameter SET_GLOBAL_PWD to 0 (zero) to specify a password that is the same as the User ID (for example, VP1/VP1). For example:

```
SET_GLOBAL_PWD=0
#PS_GLOBAL_PWD=
```

- Set the parameter SET_GLOBAL_PWD to 1 (one) to set a common global password for all the User profiles in the database.

If you set the SET_GLOBAL_PWD option to 1, remove the comment (#) character in front of the parameter PS_GLOBAL_PWD, and specify the password to be used for all user profiles. For example:

```
SET_GLOBAL_PWD=1
PS_GLOBAL_PWD=password
```

12. Choose whether to configure a server and create a database (DB_CONFIG_SRVR=0), or create a database on an existing server (DB_CONFIG_SRVR=1).

.Which options you choose tells PeopleSoft Database Configuration Wizard whether to run the dbmcfg.sql script in addition to creating a PeopleSoft database. The dbmcfg.sql script updates the default DB2 instance with the PeopleSoft recommended value. If you select Configure a server and create database, the DB2 instance must be recycled for the PeopleSoft recommended parameters to take effect at the instance level. If you select Create database on existing server, the dbmcfg.sql does not get executed, which in turn does not require the DB2 instance to be recycled. This implies that the DB2 instance is already configured at a minimum with the PeopleSoft recommended values and satisfies the prerequisites.

```
#####
```

```
DB2UNIX Input
```

```
#####
```

```
DB_CONFIG_SRVR=0
```

13. Indicate the name and full path for the database (DB_DIR_NME), ending with a forward slash (/).

```
DB_DIR_NME=/data1/database/dbx/FSDMO/
```

14. Specify the territory code.

Note. Consult the DB2/LUW reference manual section on "Supported territory codes and code pages" for information on territory identifiers and code sets.

```
DB2_TERR_CODE=US
```

15. Indicate the full path for the directory where the tablespace will be created, ending with a forward slash (/).

Enable or disable the Auto-Resize feature.

PeopleSoft databases running on the DB2/LUW platform can take advantage of the IBM DB2 Auto-Resize option for tablespaces. The auto-resize option creates a tablespace that automatically increases its size, in configurable increments, to accommodate increase in data volume. Note, however, that you cannot measure the total size of the system database with Auto-Resize on.

Note. Disabling Auto Resize (AUTO_RESIZE=1) can cause a Tablespace "out-ofspace" error condition during database creation.

```
TBL_SPCE_LOC=/data1/database/dbx/FSDMO/  
AUTO_RESIZE=1
```

16. Specify the PeopleSoft Access ID and enter the password two times.

This is the PeopleSoft Access ID defined in the task "Planning Database Creation." You use it when signing on to Data Mover in "bootstrap mode." This value is case sensitive, and you must limit it to eight characters or less.

See "Preparing for Installation," Planning Database Creation.

See "Preparing for Installation," Creating PeopleSoft User ID, for Access ID password requirements.

```
ACCESS_ID=accessid  
ACCESS_PWD=password  
ACCESS_PWD_RETYPE=password
```

Task 5B-2-2: Running the Silent Mode Database Creation

Use the response file that you modified for your configuration. Substitute the location where you saved the response file for <path_to_response_file> in the following procedure.

UNIX:

1. In a command prompt, go to *PS_HOME*\setup\PsmPDbInstall.
2. Run the following command, using forward slashes (/) to specify the path:

```
setup.sh -f <path_to_response_file>
```

For example:

```
setup.sh -f /home/psftinstall
```

Task 5B-3: Changing the Location of the DB2/LUW Database Log Files

The CREATE DATABASE command in the createdb-95.sql or createdbu.sql script creates the database with the default log files located in a subdirectory called SQLOGDIR under the directory created for the database. If the default location is not appropriate, follow these steps:

To change the location of log files:

1. Connect to the newly created database.
2. Issue the following DB2 command:

```
db2 UPDATE DB CFG FOR <db2-database-name> USING NEWLOGPATH <dir-name>
```

where <db2-database-name> refers to the newly created PeopleSoft database from the previous task, Running the Database Configuration Wizard, and <dir-name> is the location where you want the new log files to be located.

Task 5B-4: Cleaning Up Orphaned Language Data

Perform this task if you are a Multilingual customer and are installing non-English languages. This task assumes that you have loaded the necessary language files. If you have not yet loaded the language files, follow the instructions in the Global Technology product documentation.

See *PeopleTools: Global Technology*, "Adding Translations to an Existing Database on the Same PeopleTools Version."

The Application Engine program PTIACLEANLNGCA removes any orphaned related language objects that do not have a matching base language object.

Run the PTIACLEANLNGCA application engine program. From the command line utility, the syntax is:

```
<PS_HOME>\bin\client\winx86\psae -CD <dbname> -CT DB2UNIX -CO <oprid> -CP=>  
<pswd> -R <run_control> -AI PTIACLEANLNGCA -FP <log_path>
```

Use the values for the database name and user ID that you entered on the startup tab of the Configuration Manager for <dbname> and <userid> respectively. However, be aware that <userpswd> is not the same as the connect password you entered on the Configuration Manager startup tab. Enter a value for <userpswd> that is the password associated with the <userid>. For <log_path>, specify the path where you want the log file for the application engine program to be generated, such as C:\temp\.

Task 5B-5: Checking the Log Files and Troubleshooting

This section discusses:

- Checking the Log Files
- Running Data Mover
- Troubleshooting
- Improving Performance

Task 5B-5-1: Checking the Log Files

After the Database Configuration Wizard finishes its execution, look for all log output in the *PS_HOME/log* directory. Open all the log files. There is a log file for each of the steps that the Database Configuration Wizard carries out—importing, encrypting passwords, creating triggers, replacing views, and creating temp tables. *None should contain error messages.*

Task 5B-5-2: Running Data Mover

If the Database Configuration Wizard does not complete successfully, you must run Data Mover manually, using one of the following methods.

On UNIX, run *PS_HOME/bin/psdmtx* from the command line.

If you use the access ID that you specified during the database configuration to log on, you log on in "bootstrap mode." When you start Data Mover in bootstrap mode, the word "BootStrap" appears in the Data Mover status bar.

If you use a valid PeopleSoft Operator ID, such as PS for Human Capital Management or VP1 for Financials/Supply Chain Management, you log on in "user mode." In this mode, no designation appears in the Data Mover status bar.

To run Data Mover on the command line:

Note. You can run *psdmtx* by supplying arguments on the command line, or by passing the arguments from a text file. This section describes the text file method.

1. Go to *PS_HOME/bin*.

```
cd $PS_HOME/bin
```

2. Use the following command to view the help for `psdmtx`:

```
$ psdmtx /help
Usage:  psdmtx  [-CT DB2|DB2ODBC|DB2UNIX|MICROSFT|ORACLE]
              [-CS server name]
              [-CD database name]
              [-CO user id]
              [-CP user pswd]
              [-CI connect id]
              [-CW connect id pswd]
              [-I process instance]
              [-FP filename]

      or
psdmtx  [parmfile]
```

To capture the output in a file, use a greater-than symbol ("pipe", >) followed by a filename. For example:

```
psdmtx [arguments] > filename.txt
```

Use the following list of commands and descriptions for the `psdmtx` arguments:

Command Argument	Description
-CT <DB type>	The type of database to connect to. The valid values are: DB2 and DB2UNIX.
-CD <DBNAME>	Your selected Database Name.
-CO <ACCESSID>	Use the <DBNAME> Access ID to run Data Mover in bootstrap mode.
-CP <ACCESSPWD>	The password for <DBNAME> Access ID.
-CI <CONN ID>	The ID used to connect to the database server.
-CW <CONN PSWD>	The password for the specified connection ID.
-FP <filename>	The filename for the Data Mover import script (DMS) to run.

3. To set up Data Mover to rerun the Data Mover import script in bootstrap mode, do the following:
- Change directory to `PS_HOME/setup`.
 - Copy `parmfile` to `parm<DBNAME>`. For example, `parmPT857`.
 - Edit `parm<DBNAME>`.

Use the information in the table above to edit the file for your configuration.

Use DB2UNIX for <DB type>.

For example:

Before

```
-CT <DB type> -CD <DBNAME> -CO <ACCESSID> -CP <ACCESSPWD> -CI <CONN⇒
ID> -CW⇒
```

```
<CONN PSWD> -FP <filename>
```

After

```
-CT DB2UNIX -CD HRDMO -CO HRDMO -CP HRDMO -CI people -CW people -FP⇒
$PS ⇒
HOME/scripts/pt857dbx.dms
```

4. To launch Data Mover in bootstrap mode, do the following:

- Change directory (cd) to *PS_HOME/bin*
- Run the *psdmtx* command with the edited *parm<DBNAME>* file.

```
pt-sun20:$ psdmtx ../setup/parmPT857
```

You see Data Mover log messages tracking the progress.

See Also

PeopleTools: Data Management

Task 5B-5-3: Troubleshooting

If the Database Configuration Wizard did not complete successfully, read this troubleshooting information. If your script has stopped midway (this can happen for a number of reasons) you need to edit the Data Mover script generated automatically by the Database Configuration Wizard and restart Data Mover manually. The Data Mover script files have the extension *.dms* and are sometimes referred to as "DMS scripts."

The generated Data Mover import script is saved in the *PS_APP_HOME/scripts* directory. The script conforms to the following naming convention:

```
<dbname>dbx.dms
```

If the Database Configuration Wizard fails while creating views, clear the cache folder, for example, *USER_HOME/PS_CACHE*, and restart from the create views step.

See the information on startup settings in PeopleSoft Configuration Manager in the *PeopleTools: System and Server Administration* product documentation.

If running a script results in an SQL error, it may be because the *PS.PSDBOWNER* table contains duplicate rows, an invalid user ID is specified, or the Owner ID column in the *PSLOCK* table is specified in uppercase or is incorrect. If this is the case fix *PS.PSDBOWNER*.

To edit and restart the DMS script:

1. Determine the record that was being imported (that is, which *IMPORT* command was running) when the script stopped, and use the following guidelines to edit and rerun the DMS scripts.

When building a DMO database or a multilingual database, adding the *SET START* statement can be tricky because the Data Mover script used to load the database will include more than one *IMPORT* statement. The key is to view the log files and determine which *IMPORT* section of the script Data Mover failed on.

- If the failure occurred during the first *IMPORT* statement, add the *SET START* statement before the first *IMPORT *; statement*.
- If the failure occurred during a subsequent *IMPORT* statement, comment out all statements preceding the *IMPORT *; statement* where the failure occurred and add the *SET START* statement before the *IMPORT *; statement* of the section in which the failure occurred.
- *This is very important:* If you see any "unique index constraint" error messages in the "Building required

indexes" section, your IMPORT script failed during a subsequent IMPORT but the SET START statement was added to the first IMPORT. In this situation, you can run the Data Mover script in its originally generated form, with only one modification. In the first IMPORT section, change the statement "IMPORT *;" to "REPLACE_DATA *;". This will delete all the data in the tables, and re-import it. This process will take some time to run, and you will need to separately create each of the indexes that failed.

2. Start Data Mover by running psdmtx on the command line.

See Running Data Mover.

3. Log on using the Access ID to start Data Mover in *bootstrap mode*.

The input window should display the DMS import script for the database. The script has the format <dbname>dbx.dms.

4. If necessary, select File, Open, and browse to the *PS_APP_HOME/scripts* directory to find the appropriate DMS script.
5. Add the following line before the offending IMPORT command (the one being executed when the failure occurred):

```
SET START <RECORD NAME>;
```

<RECORD NAME> is the name of the record that failed. Make sure to review the Data Mover log file to see where the script failed and locate the last record that imported successfully. The SET START command will begin the Data Mover import at the specified record name.

Note. It is a good idea to change the name of the log file in the script before each attempt at running it. This ensures that you have a separate log file for each attempt, if you run the import more than once.

For example, if the script stops and the table is partially inserted with a message similar to this one:

```
Importing PSPNLFIELD
Rows inserted into PSPNLFIELD

3000
```

First drop the partially inserted table (for example, record) by using the DROP TABLE command, and then restart Data Mover at the record that failed using the SET START command and continue the Data Mover import. This can be done in a single pass.

Add the following lines before the offending IMPORT *; command (the one being executed when the failure occurred):

```
SET START <RECORD NAME>;
DROP TABLE <RECORD NAME>;
```

where <RECORD NAME> is the name of the record that failed. The SET START statement will begin the Data Mover import at the specified <RECORD NAME>.

Example of the original script:

```
REM - PeopleSoft Database - US English
/
SET LOG epengs.log;
SET INPUT epengs.db;
SET COMMIT 30000;
SET NO VIEW;
SET NO SPACE;
SET NO TRACE;
SET UNICODE ON;
```

```
IMPORT *;
```

Example of script after modification, with changes in bold font:

```
REM - PeopleSoft Database - US English
/
SET LOG epengs2.log;
SET INPUT epengs.db;
SET COMMIT 30000;
SET NO VIEW;
SET NO SPACE;
SET NO TRACE;
SET UNICODE ON;
SET START PSPNLFIELD;
DROP TABLE PSPNLFIELD;
IMPORT *;
```

For the DROP statement, for records with a recname without a leading PS, add PS_ to the beginning of the recname; otherwise the table will not be found. For example, PS_<RECNAME>.

6. To restart the script, use the `psdmtx` command to execute Data Mover on the command line.
See Running Data Mover.

Task 5B-5-4: Improving Performance

The following tips can help you save time when running the Data Mover scripts:

- Run Data Mover from the fastest workstation available.
- Run Data Mover on the database server.
- Run only a single instance of Data Mover, and do not have any other applications running during the import.
- In the PeopleSoft Configuration Manager, turn off all trace options.
Tracing during a DMS load will add considerable time to the process.
- Copy the database file over to the workstation so that Data Mover can access it locally instead of over the network.
- Run Data Mover on the database server with the .db or .dat file located locally.

If you are comfortable changing the options available for a DB2/LUW instance and database, you might consider "tuning" the instance and database used for the import. Some of these options are appropriate only during the import, so you may not want to keep them in effect after the import is complete.

Chapter 6

Completing the Database Setup

This chapter discusses:

- Selecting the Necessary Tasks to Complete the Database Setup
- Running Additional Data Mover Scripts
- Running SQR Reports
- Checking the Database
- Running SETSPACE.SQR

Selecting the Necessary Tasks to Complete the Database Setup

Review each of the tasks in this chapter to determine which are required for your database setup. Depending upon the details of your installation you may not need to complete every task. However, it is important to evaluate the tasks with respect to your specific situation.

Task 6-1: Running Additional Data Mover Scripts

To import additional data for your specific PeopleSoft database, or to make other required changes, you may need to run additional Data Mover scripts. These script files have the extension .dms and are sometimes referred to as "DMS scripts." They are located in the *PS_HOME*\scripts or *PS_APP_HOME*\scripts directory of your file server, and need to be run from the file server by means of Data Mover.

For the details on which additional application-specific Data Mover scripts to run, consult your application-specific installation instructions.

Task 6-2: Running SQR Reports

This section discusses:

- Understanding Running SQR Reports
- Binding the dbcalls.bnd
- Running SQRs on the Client Workstation
- Creating a Shortcut to Run SQRs

Understanding Running SQR Reports

The instructions in this section describe how to run SQR reports from the client workstation. On the Microsoft Windows client, you may prefer to create a shortcut to allow you to run the reports repeatedly. You can use these instructions to run SQRs required in the upcoming task Checking the Database.

You can also choose to run SQR reports from the command line in console mode. Before running SQR from the command line on Microsoft Windows operating systems, set PS_HOME from the prompt. For example:

```
set PS_HOME=C:\PT857
```

See Also

PeopleTools: SQR for PeopleSoft Developers

PeopleTools: SQR Language Reference for PeopleSoft

Task 6-2-1: Binding the dbcalls.bnd

You need to bind the dbcalls.bnd before running SQR reports.

On Microsoft Windows operating systems, the PeopleSoft installation installs one version of SQR that supports both the CLI interface and the ODBC interface for DB2/LUW.

Note. The version of DB2, which SQR uses on Microsoft Windows and Linux, will try to bind dbcalls.bnd automatically in some cases. To avoid possible errors if this does not occur, you must carry out this step.

To bind dbcalls.bnd:

1. Choose Start, Programs, IBM DB2, Command Window.
2. Connect to the database. For example,

```
C:\db2odbc9\BIN>db2 connect to PSDMO user dbxuser using dbxuser
```
3. Change to the directory where SQRW.exe resides, for example:

```
PS_HOME\bin\sqr\dbx\binw
```
4. From there, type

```
db2 bind dbcalls.bnd
```

Note. The executable program PSSQR.EXE is a wrapper program used by PeopleSoft Process Scheduler to run SQR reports. It is not designed to run manually outside of Process Scheduler. That is, the PeopleSoft system does not support running PSSQR from the command line.


Task 6-2-2: Running SQRs on the Client Workstation

To run an SQR on the client workstation:

1. Select Start, Run, click Browse, and navigate to *PS_HOME\bin\sqr\DBX\binw*.
Select *sqrw.exe* and click Open.

2. Add any needed flags at the end of the command line.

Refer to the table that follows. For those flags that require attributes, append the attributes to the flags with no intervening spaces (for example, `-fE:\fsdmo\bin\sqr\pssqr.ini`).



Microsoft Windows Run dialog box launching SQRW


The following table summarizes the SQR report arguments used by PeopleSoft software. (For a full listing of report arguments, press the Help button to view the SQR help topic for this dialog box.)

Flag	Description
-I	Specifies the directories that SQR will search for the #INCLUDE files. (A trailing slash is required.)
-f	Specifies the directory where the report output will be sent. If you use the <code>-keep</code> flag, you must specify the directory with a trailing slash. If you use the <code>-printer</code> flag, specify a full pathname with a filename for the HTML file.
-ZIF	Sets the full path and name of the SQR initialization file. The <code>-ZIF</code> flag should point to your <code>PS_HOME\sqr\pssqr.ini</code> file.
-keep	Keeps the .SPF file after the program runs. This enables you to view the report with the SQR viewer.
-printer:ht	Generates the output file in HTML format. Specify the filename, with path location, with the <code>-f</code> flag.

3. Click OK.

The SQR for PeopleSoft V8.57 dialog box appears, displaying the attributes that you entered in the Run dialog box. The fields on this dialog box are described in the next step:

Note. The report arguments in this example have been arranged for readability.



SQR for PeopleSoft dialog box with DDDAUDIT.SQR

4. Enter the following values:

- Enter the report name.
You must specify the full path.
- Enter the access ID in the Username field.
- Enter the access password in the Password field.
- Enter the database name.

5. Click OK to run the SQR report.

Task 6-2-3: Creating a Shortcut to Run SQRs

If you think you may need to run the SQR reports more than once, you may want to create a shortcut on the Windows client workstation. To save the report arguments:

1. Open Windows Explorer on the machine on which you want to run SQR.
2. Navigate to *PS_HOME\bin\sqr\DBX\binw*.
3. Right-click *sqrw.exe* and click Create Shortcut.
4. Right-click the shortcut that you just created and select Properties.
5. On the Shortcut tab, add the same *sqr* flags that you used in the previous task after *sqrw.exe* in the Target entry box.
6. Click OK.
7. To run the report, double-click the shortcut and specify the following information in the dialog box:
 - Report Name: Enter the full path and the name.

- Database name
 - Username: Enter the access ID.
 - Password: Enter the access password.
 - Report arguments: Make any necessary modifications to the saved arguments.
8. Click OK.

Task 6-3: Checking the Database

Run and examine the SQR reports to verify that your database is complete.

See Running SQR Reports.

To verify that the database is complete, run the following SQR reports from the *PS_HOME\sqr* directory:

- dddaudit.sqr
- sysaudit.sqr
- swpaudit.sqr, if you plan to swap your base language

For further information about these reports, consult PeopleSoft product documentation. This documentation includes specific information on how to interpret the reports and how to fix any errors found there.

It is good practice to run and read the audit reports, which include sysaudit, dddaudit, swpaudit, and alter audit, after making changes such as applying patches, bundles, and upgrades to the database, to make sure that the tables are internally and externally in synch. It is also a good idea to schedule regular maintenance, for example weekly, in which you run and review the reports. You can find information on these audit reports in the *PeopleTools: Data Management* product documentation.

See *PeopleTools: Global Technology*, "Running the Swap Audit Report."

Note. If any records show up in the VIEWS-2 or TABLE-3 section of dddaudit and are contained within the PPLTLS84CURDEL project, you may safely drop these records using the SQL query tool for your platform.

See Also

PeopleTools: Data Management

PeopleTools: System and Server Administration


Task 6-4: Running SETSPACE.SQR

Run the SETSPACE.SQR script to populate or synchronize Tablespace information with the system catalog. To run SETSPACE.SQR:

1. Using the instructions provided earlier, run SETSPACE.SQR from the *PS_HOME\SQR* directory.

See Running SQR Reports.

Note. Your results will vary depending on the application you are loading. The dialog box example shown here is typical. The report arguments in this example have been arranged for readability.



SQR for PeopleSoft dialog box with setspace.sqr

2. Click OK.
3. As SETSPACE.SQR runs you see a progress indicator similar to the following.

Set Table Space Name in PSRECTBLSPC

Table PSRECTBLSPC column DDLSPACENAME have been updated
with the tablespace found in the system catalog table.

The total number of records updated appears at the bottom of this→
report.

Recname	New DDLSpaceName	Old DDLSpaceName
---------	------------------	------------------

This phase of SETSPACE will sync up the PSRECTBLSPC and
PSTBLSPCCAT tables

PSRECTBLSPC Records Updated:	0
------------------------------	---

PSTBLSPCCAT Records Inserted:	0
-------------------------------	---

Ending SQR.

Chapter 7

Deploying Mid-Tier Components

This chapter discusses:

- Understanding the Mid-Tier Deployment
- Running the DPK Setup Script for Mid-Tier Deployment
- Completing Installation Tasks

Understanding the Mid-Tier Deployment

After you complete the database creation, run the PeopleTools DPK setup script again to deploy the mid-tier components for the PeopleSoft environment. Specify the same *BASE_DIR* that you specified when you used the DPK setup script to install the software.

The default mid-tier deployment performs the following:

- Sets up a single application server domain, Process Scheduler domain, and PIA domain.
- On Microsoft Windows, sets up services for the PeopleSoft domains.

Note. On Windows, when running the setup script to deploy mid-tier components for previously-created domains, first stop and delete services for configured domains to avoid errors.

- Installs Oracle Tuxedo and Oracle WebLogic software, unless the DPK setup script installed them in previous deployment to the same *BASE_DIR*/pt location.

Task 7-1: Running the DPK Setup Script for Mid-Tier Deployment

This section discusses:

- Understanding the Mid-Tier Deployment
- Prerequisites
- Running with the Mid-Tier Option on Microsoft Windows
- Running with the Mid-Tier Option on Linux, AIX, HP-UX, or Solaris as the Root User
- Running with the Mid-Tier Option on Linux, AIX, HP-UX, or Solaris as a Non-Root User

Understanding the Mid-Tier Deployment

Use this procedure to install the PeopleSoft mid-tier components. The deployment includes the following:

- *PS_HOME* installed to the default location under the DPK base directory

- Oracle Tuxedo installed to the default location under the DPK base directory
- Oracle WebLogic installed to the default location under the DPK base directory
- Oracle database client installed to the default location under the DPK base directory
- Deployed and set up PeopleSoft domains. There is a single Application Server domain, single Process Scheduler domain, and single PIA domain.
- The Microsoft Windows DPKs include Microsoft Visual C++ Redistributable Packages for Visual Studio, which include required Microsoft C++ runtime libraries

Prerequisites

Before performing the mid-tier deployment, be sure that you have fulfilled the following requirements:

- You have downloaded all of the required PeopleSoft PeopleTools DPKs, and saved them in a location accessible to the Microsoft Windows, Linux, AIX, HP-UX, or Solaris host, referred to here as *DPK_INSTALL*.

See "Installing the PeopleSoft Homes," Obtaining the PeopleSoft Application and PeopleTools DPKs

Note. After the DPK setup script extracts the downloaded zip files, it will delete the original zip files in *DPK_INSTALL*. If you want to save the original zip files, make a backup copy in a different folder.

Note. If you want to have a PeopleSoft application-specific local node, for Integration Broker or Report Node, configured during the mid-tier creation, you must also download the first application DPK (normally zip file 9ofn.zip). If the application DPK is not present, the mid-tier deployment will create a PeopleTools-specific default local node.

- Remove any previous installations of the same version of Oracle Tuxedo.
- You extracted the first zip file. The extraction gives a setup folder and other files.
See "Deploying the PeopleSoft Homes."
- The user running the script *must have administrative permission* on Microsoft Windows.

Note. Restarting services for the deployed PeopleSoft environment, such as those for Oracle Tuxedo, must be performed by the same user (with administrative permission) who carried out the installation.

- You must have *root access* to deploy the PeopleSoft DPKs on Linux, AIX, HP-UX, or Solaris.
For information on non-root deployment, see the section Deploying as a Non-Root User on Linux, AIX, HP-UX, or Solaris.
- For deployment on Linux, AIX, HP-UX, or Solaris, there is a writable directory available for the home for the users that own the PeopleSoft environment. The default is /home.
If you install as a non-root user, the DPK setup script uses the home directory of the logged-in user. If you do the entire installation as root, the DPK setup script includes a prompt for the default users' home directories.
- There is enough space on the host for the PeopleSoft environment.
See "Prerequisites," Reviewing Hardware Requirements on Microsoft Windows.
- For deployment with the AIX or HP-UX DPK, you have installed JDK required for the operating system.
See Reviewing Software Requirements.
- You have installed database connectivity software for the database that you want to access on the machine on which you deploy the mid-tier components.

See "Completing the DPK Initialization with Customizations."

Note. When installing mid-tier components for environments on DB2 LUW, you must use customizations to complete the installation. The delivered YAML files may not include the necessary RDBMS client information for your environment. Create a `psft_customizations.yaml` file, and include the correct client information. See the chapter "Completing the DPK Initialization with Customizations."

- For all installations on DB2 for Linux, UNIX, or Windows (DB2 LUW), you must catalog the database before mid-tier deployment using DPKs. To catalog the database, see the documentation for DB2 LUW for information.
- You have the information for the database to connect to, including:
 - RDBMS platform
 - Database name, service name, host, and listening port
 - Unicode or non-Unicode database
 - For DB2 LUW, database catalog information
- You have the information for the user IDs and passwords needed for the deployment, including the following:
 - PeopleSoft Connect ID and password
 - PeopleSoft operator ID (such as PS or VP1) and password
 - Application Server Domain Connection password (optional)
 - PTWEBSERVER web profile user password
 - Oracle WebLogic server administrator password
 - Integration Gateway administrator

Task 7-1-1: Running with the Mid-Tier Option on Microsoft Windows

To deploy mid-tier components on physical or virtual Microsoft Windows hosts:

1. Open a command prompt window with Run as Administrator.
2. Change directory to the location where you extracted the first zip file, `DPK_INSTALL/setup`.
3. Run the script with the mid-tier option to set up the Application Server, PIA, and web server mid-tier components.

Note. If you see an error message similar to "The application has failed to start because its side-by-side configuration is incorrect," it indicates that your machine does not include the necessary Microsoft C++ runtime libraries. Go to the Microsoft Web site, locate the Microsoft Visual C++ redistributable package for your system, and install as directed.

- If you extracted the first zip file into the same directory where you downloaded the zip files, use this command:


```
psft-dpk-setup.bat --env_type midtier
```
- If you extracted the first zip file into a different directory, include the option `dpk_src_dir` to specify the location of the downloaded zip files, such as `DPK_INSTALL`.


```
psft-dpk-setup.bat --dpk_src_dir DPK_INSTALL --env_type midtier
```

Note. Running the DPK setup script with the `--env_type midtier` option deploys all servers. If you want to deploy one of the servers (application server, Process Scheduler server, PIA, or application server and Process Scheduler server) see the command options in "Installing the PeopleSoft Homes," Reviewing the DPK Setup Script Options.

4. Wait while the script locates the valid PeopleSoft DPK zip files and extracts them.

The system displays messages indicating the steps in the setup process. The success or failure of each step is indicated by [OK] or [FAILED].

After the script completes the extraction, it deletes the original files. Make a backup copy if you want to keep them.

See "Preparing for Installation," Understanding the PeopleSoft Installation Using Deployment Packages, for the filename syntax of the DPK zip files.

Starting the PeopleSoft Environment Setup Process:

```
Validating User Arguments:                [ OK ]
Validating PeopleSoft Supported Platform:  [ OK ]
```

5. Specify whether to install the Puppet software if necessary at the next prompt.

The script verifies if Puppet software is installed in the default location specified by the DPKs. If not, answer *y* (yes) to install the Puppet software and *n* to abort the PeopleSoft environment setup process. The default action (if nothing is entered at the prompt) is to install the software.

If there is any error during the Puppet software installation, the script aborts the setup process. Review the log file in *DPK_INSTALL/setup*. If there are missing operating system packages, you will need to carry out additional steps.

See Obtaining Operating System Packages Required for Puppet.

```
Verifying if Puppet Software is Installed: [ OK ]
```

Puppet Software is not installed on the Host. If this Host is used to setup a PeopleSoft environment, Puppet Software should be Installed.

```
Do you want to Install Puppet Software on this Host? [Y|n]: y
```

```
Installing Puppet Software on the Host:    [ OK ]
```

The script verifies the eYAML software.

```
Verifying if eYAML Hiera Backend is Installed: [ OK ]
```

The script verifies if the DPKs are available in *DPK_INSTALL*, and aborts with the message [FAILED] if they are not.

Preparing the Windows 2012Server VM for PeopleSoft Environment:

```
Checking if PeopleSoft DPKs are Present:    [ OK ]
```

6. At the following prompt, enter a location that is accessible to the host to be used as the PeopleSoft base directory.

The base folder is used to extract the PeopleSoft DPKs as well as for deploying PeopleSoft components. The script creates the folder if it is not present.

Note. When entering the path for the base folder, use forward slashes (/). For example, `C:/psft`. Enclose any names with special characters in double quotes. Do not use a name for the base folder that begins with a number.

The base folder is used to extract the PeopleSoft DPKs. It is also used to deploy the PeopleSoft components. This folder should be accessible on the Windows VM, must have write permissions and should have enough free space.

Enter the PeopleSoft Base Folder: `C:/psft`
 Are you happy with your answer? [Y|n|q]:

The script validates if there is enough free space available under the specified base directory for the PeopleSoft environment. The PeopleSoft environment setup is aborted if there is not enough free space.

Note. A mid-tier setup of a PeopleSoft environment requires about 25 GB of disk space.

Checking if the Base Folder has Enough Free Space: [OK]

The script creates the following three sub-directories under the user provided base directory, *BASE_DIR*:

- *BASE_DIR*\dpk
 The script uses this directory to extract the archives from the PeopleSoft DPKs, and contains the Puppet YAML files for the deployment.
- *BASE_DIR*\pt
 The script uses this directory to deploy PeopleSoft components.
- *BASE_DIR*\db
 This directory is not used for a mid-tier deployment.

7. Review the status messages as the script validates the files found in *DPK_INSTALL* and extracts the DPK archives.

The script carries out validations for the mid-tier deployment. If any of the validations fail, the PeopleSoft environment setup is aborted.

Note. The messages have been truncated for brevity.

Validating the PeopleSoft DPKs in the Windows VM:

[...]

Extracting the PeopleSoft DPK Archives in the Windows VM:

[...]

8. Review the status messages as the script sets up the Puppet file system.

The script sets up Puppet on the host or VM. It then copies the PeopleSoft Puppet modules to the standard location under the base folder (*BASE_DIR*\dpk) and updates the YAML files to reflect the type of PeopleSoft environment setup.

Setting up Puppet on the Windows VM:

Generating eYAML Hiera Backend Encryption Keys: [OK]

Updating the Puppet Hiera YAML Files in the Windows VM: [OK]

Updating the Role in Puppet Site File for the Windows VM: [OK]

9. Specify the installation type.

Enter the PeopleSoft installation [PUM or FRESH] type [PUM]: **FRESH**

Note. You see this prompt only when PeopleSoft application DPKs that were built on the same PeopleTools release, are present in *DPK_INSTALL*.

Note. If you are using the PeopleSoft Upgrade Source Image to set up an environment for the Upgrade Source database, you do not see this prompt.

10. Specify the information for the database that you want to connect to.

- a. Enter DB2UNIX for a DB2 for Linux, UNIX, and Windows database platform.

Enter the PeopleSoft database platform [ORACLE]: **DB2UNIX**

- b. Enter y (yes) if the database you are connecting to is a Unicode database, or n (no) for a non-Unicode database.

Is the PeopleSoft database unicode? [Y|n]:

- c. Enter y (yes) if you want to install the files needed for multi-language support.

Note. You see this prompt only when PeopleSoft application DPKs that were built on the same PeopleTools release, are present in *DPK_INSTALL*.

Do you want Multi Language support in PeopleSoft database? [y|N]:

- d. Enter the database name.

Enter a new PeopleSoft database name. Ensure that the database name start with a letter and contains only uppercase letters and numbers and is no more than 8 characters in length [HCM92]:

- e. Enter the name of the host where the database is installed, and the DB2 LUW instance port number:

Use forward slashes if necessary. If the host name includes non-alphanumeric characters such as periods, enclose the name in double quotes. For example, "host.example.com".

Enter the PeopleSoft database host name:

Enter the PeopleSoft database port [1521]: **50000**

11. Enter the PeopleSoft Connect ID at the following prompt:

The default is people.

Enter a new PeopleSoft database Connect ID. Ensure that the ID contains only alphanumeric characters and is at most 8 characters in length [people]:

12. Enter a password for the PeopleSoft Connect ID, and enter again on the next line, at the following prompt.

Enter the PeopleSoft database Connect ID [people] password: Ensure the password contains only alphanumeric characters and is between 6 and 30 characters in length:

Re-Enter the PeopleSoft database Connect ID password:

13. Enter the PeopleSoft Operator ID (user ID) at the next prompt:

Enter the PeopleSoft database Operator ID [PS]:

14. Enter the password twice for the PeopleSoft operator ID, such as PS or VP1.

Enter a new PeopleSoft database Operator ID [PS] password. Ensure the password contains only alphanumeric characters and is between 1 and 32 characters in length:

Re-Enter the PeopleSoft Operator ID password:

15. Enter the Application Server Domain Connection password, following the guidelines in the prompt.

The window does not display masking characters as you type. There is no default password.

Note. This is an optional password. If no password is entered, the connection between Web Server and Application Server will not be password protected.

[Optional] Enter a new Application Server Domain connection password. Ensure the password contains only alphanumeric characters and is between 8 and 30 characters in length:

Re-Enter the Application Server Domain connection password:

16. Enter the password for the PTWEBSEVER web profile user.

Note. The guideline in the prompt for the PTWEBSEVER user password does not allow special characters. However, the PeopleSoft system does allow special characters for the PTWEBSEVER password. If you want to change the password to include special characters, you have the option to do so in the PeopleSoft Pure Internet Architecture (PIA) after you complete the installation and domain creation.

See *PeopleTools: Security Administration*, "Working with Passwords."

Enter a new PeopleSoft WebProfile user [PTWEBSEVER] password. Ensure that the password contains only alphanumeric characters and is between 8 and 32 characters in length:

Re-Enter the PeopleSoft WebProfile user password:

17. Enter the Oracle WebLogic Server Admin password, following the guidelines in the prompt.

The default Oracle WebLogic server administrator is system. The window does not display masking characters as you type. There is no default password.

Enter a new WebLogic Server Admin user [system] password. Ensure that the password is between 8 and 30 characters in length with at least one lowercase letter, one uppercase letter and one number or one special character (!@#\$\$%^&):

Re-Enter the WebLogic Server Admin user password:

18. Enter the Integration Gateway user ID and password at the following prompt.

The default user ID is administrator.

Note. The guideline in the prompt for the Integration Gateway user ID password does not allow special characters. However, the PeopleSoft system does allow special characters for the Integration Gateway user ID password. If you want to change the password to include special characters, you have the option to do so in the PeopleSoft Pure Internet Architecture (PIA) after you complete the installation and domain creation.

See *PeopleTools: Security Administration*, "Working with Passwords."

```
Enter the PeopleSoft Integration Gateway user [administrator]:
Enter the PeopleSoft Integration Gateway user [administrator] password.
Ensure the password contains only alphanumeric characters and is
between 8 and 30 characters in length:
Re-Enter the PeopleSoft Integration Gateway user password:
```

19. If you want to change any of the answers to the previous questions, enter *n* (no) at the following prompt, or enter *y* (yes) to continue:

```
Are you happy with your answers? [y|n]:
```

20. Review the status messages as the script updates the Puppet YAML files with the user input.

```
Encrypting the Passwords in the User Data:          [ OK ]
Updating the Puppet Hiera YAML Files with User Data: [ OK ]
```

21. Answer *n* (no) to indicate that you do not want to continue running the initialization script using the default configuration.

The script stops. Follow the instructions for using customizations for mid-tier connectivity to complete the mid-tier deployment.

Note. The "cd /d" command included in the prompt changes to the correct drive in the command prompt.

Note. To run step 2, the puppet apply step, it is a good idea to use a log name other than `psft_dpk_setup.log`, to differentiate the log from that for the DPK initialization process.

See "Completing the DPK Initialization with Customizations."

The bootstrap script is ready to deploy and configure the PeopleSoft environment using the default configuration defined in the Puppet Hiera YAML files. You can proceed by answering 'y' at the following prompt. And, if you want to customize the environment by overriding the default configuration, you can answer 'n'. If you answer 'n', you should follow the instructions in the PeopleSoft Installation Guide for creating the customization Hiera YAML file and running the Puppet 'apply' command directly to continue with the setup of the PeopleSoft environment.

```
Do you want to continue with the default initialization process? [y|n]: =>
n
```

You have decided not to continue with the default PeopleSoft environment setup process. Any customizations to the PeopleSoft environment should be done in the Hiera YAML file 'psft_customizations.yaml' and place it under [c:\psft\dpk\puppet\production\data] folder. After making the necessary customizations, run the following commands to continue with the setup of PeopleSoft environment.

```
1. cd /d C:\psft\dpk\puppet\production\manifests
2. "C:\Program Files\Puppet Labs\Puppet\bin\puppet.bat" apply
--confdir=C:\psft\dpk\puppet site.pp --debug --trace
--detailed-exitcodes --logdest /some_valid_path/to/log/psft_dpk_>
setup.log
```

Exiting the PeopleSoft environment setup process.

The complete setup log is written to the file `psft_dpk_setup.log` in the same location as the DPK setup script.

Task 7-1-2: Running with the Mid-Tier Option on Linux, AIX, HP-UX, or Solaris as the Root User

If you are installing the PeopleSoft environment as a non-root user, see the following section, Running with the Mid-Tier Option on Linux, AIX, HP-UX, or Solaris as a Non-Root User.

To deploy mid-tier components on Linux, AIX, HP-UX, or Solaris hosts as the root user:

1. Open a terminal window and change directory to `DPK_INSTALL/setup`.
2. Run the script as follows:
 - If you extracted the first zip file into the same directory where you downloaded the zip files, use this command:


```
./psft-dpk-setup.sh --env_type midtier
```
 - If you extracted the first zip file into a different directory, include the option `dpk_src_dir` to specify the location of the downloaded zip files, such as `DPK_INSTALL`.


```
./psft-dpk-setup.sh --dpk_src_dir DPK_INSTALL --env_type midtier
```

Note. Running the DPK setup script with the `--env_type midtier` option deploys all servers. If you want to deploy one of the servers (application server, Process Scheduler server, PIA, or application server and Process Scheduler server) see the command options in the section Reviewing the DPK Setup Script Options.

3. Wait while the script locates the valid PeopleSoft DPK zip files and extracts them.

The system displays messages indicating the steps in the setup process. The success or failure of each step is indicated by [OK] or [FAILED].

After the script completes the extraction, it deletes the original files. Make a backup copy if you need to keep them.

See "Preparing for Installation," Understanding the PeopleSoft Installation Using Deployment Packages, for the filename syntax of the DPK zip files.

Starting the PeopleSoft Environment Setup Process:

```
Validating User Arguments:                [ OK ]
Validating PeopleSoft Supported Platform:  [ OK ]
```

4. Specify whether to install the Puppet software if necessary at the next prompt.

The script verifies if Puppet software is installed in the default location specified by the DPKs. If not, answer *y* (yes) to install the Puppet software and *n* to abort the PeopleSoft environment setup process. The default action (if nothing is entered at the prompt) is to install the software.

If there is any error during the Puppet software installation, the script aborts the setup process. Review the log file in `DPK_INSTALL/setup`. If there are missing operating system packages, you will need to carry out additional steps.

See Obtaining Operating System Packages Required for Puppet.

```
Verifying if Puppet Software is Installed: [ OK ]
```

```
Puppet Software is not installed on the Host. If this Host is
```

used to setup a PeopleSoft environment, Puppet Software should be Installed.

Do you want to Install Puppet Software on this Host? [Y|n]:

Installing Puppet Software on the Host: [OK]

The script verifies the eYAML software.

Verifying if eYAML Hiera Backend is Installed: [OK]

The script verifies if the DPKs are available in *DPK_INSTALL*, and aborts with the message [FAILED] if they are not.

Preparing the Linux VM for PeopleSoft Environment:

Checking if PeopleSoft DPKs are Present: [OK]

5. At the following prompt, enter a location that is accessible to the host to be used as the PeopleSoft base directory.

The base directory is used to extract the PeopleSoft DPKs as well as for deploying PeopleSoft components. The directory */cs1/psft* is used in this example:

Note. When entering the path for the base directory, use forward slashes (/). For example, */cs1/psft*. If the name includes any non-alphanumeric characters such as periods, enclose the name in double quotes. Do not use a name for the base directory that begins with a number.

The base directory is used to extract the PeopleSoft DPKs. It is also used to deploy the PeopleSoft components. This directory should be accessible on the Linux VM, must have write permissions and should have enough free space.

Enter the PeopleSoft Base Directory: **/cs1/psft**

Are you happy with your answer? [Y|n|q]:

The script validates if there is enough free space available under the specified base directory for the PeopleSoft environment. The PeopleSoft environment setup is aborted if there is not enough free space.

Note. A mid-tier setup of a PeopleSoft environment takes about 25 GB of disk space.

Checking if the Base Directory has Enough Free Space: [OK]

The script creates the following three sub-directories under the user provided base directory, *BASE_DIR*:

- *BASE_DIR/dpk*

The script uses this directory to extract the archives from the PeopleSoft PeopleTools DPKs, and contains the Puppet YAML files for the deployment.

- *BASE_DIR/pt*

The script uses this directory to deploy PeopleSoft components.

- *BASE_DIR/db*

This directory is not used for this deployment.

6. Specify a writable home directory for the user home directory.

The DPK setup creates local users on the host. These users deploy the PeopleSoft components and own the

PeopleSoft runtime domains. The script checks whether the default home directory for the PeopleSoft users (/home) is writable. If not, it will prompt the user to enter a new location to be used for creating the home directories for these local users.

```
Checking if Default User Home Directory /home is Writable: [WARNING]
```

```
The PeopleSoft environment setup creates local users on the Linux VM.
The default Home directory [/home] do not
have write permission to create the user's home directory. Please
ensure this directory is writable or provide a new directory on the
Linux VM that is writable.
```

```
Enter a directory on the Linux VM that is writable [/home]: /ds1
Are you happy with your answer? [y|n|q]:
```

If the /home directory is writable, no response is required.

```
Checking if Default User Home Directory /home is Writable: [ OK ]
```

7. Review the status messages as the script validates the files found in *DPK_INSTALL* and extracts the DPK archives.

The script carries out validations for the mid-tier deployment. If any of the validations fail, the PeopleSoft environment setup is aborted.

Note. The messages have been truncated for brevity.

```
Validating the PeopleSoft DPKs in the Linux VM:
[...]
Extracting the PeopleSoft DPK Archives in the Linux VM:
[...]
```

8. Review the status messages as the script sets up the Puppet file system.

The script sets up Puppet on the host or VM. As part of this setup, if the EYAML files are installed, it will generate the encryption keys. It then copies the PeopleSoft Puppet modules to the standard location (*BASE_DIR/dpk*) and updates the YAML files to reflect the type of PeopleSoft environment setup.

```
Setting up Puppet on the Linux VM:
Generating eYAML Hierarchical Backend Encryption Keys: [ OK ]
Updating the Puppet Hierarchical YAML Files in the Linux VM: [ OK ]
Updating the Role in Puppet Site File for the Linux VM: [ OK ]
```

9. Specify FRESH for the installation type.

```
Enter the PeopleSoft installation [PUM or FRESH] type [PUM]: FRESH
```

Note. You see this prompt only when PeopleSoft application DPKs that were built on the same PeopleTools release, are present in *DPK_INSTALL*.

Note. If you are using the PeopleSoft Upgrade Source Image to set up an environment for the Upgrade Source database, you do not see this prompt.

10. Specify the information for the database that you want to connect to.
 - a. Enter DB2UNIX for a DB2 for Linux, UNIX, and Windows database platform.

```
Enter the PeopleSoft database platform [ORACLE]: DB2UNIX
```

- b. Enter *y* (yes) if the database you are connecting to is a Unicode database, or *n* (no) for a non-Unicode database.

Is the PeopleSoft database unicode? [Y|n]:

- c. Enter *y* (yes) if you want to install the files needed for multi-language support.

Note. You see this prompt only when PeopleSoft application DPKs that were built on the same PeopleTools release, are present in *DPK_INSTALL*.

Do you want Multi Language support in PeopleSoft database? [y|N]:

- d. Enter the database name.

Enter a new PeopleSoft database name. Ensure that the database name start with a letter and contains only uppercase letters and numbers and is no more than 8 characters in length [HCM92]:

- e. Enter the name of the host where the database is installed, and the DB2 instance port number:

Use forward slashes if necessary. If the database name or service name includes non-alphanumeric characters such as periods, enclose the name in double quotes. For example, "host.example.com".

Enter the PeopleSoft database host name:

Enter the PeopleSoft database port [1521]: **50000**

11. Enter the PeopleSoft Connect ID at the following prompt:

The default is people.

Enter a new PeopleSoft database Connect ID. Ensure that the ID contains only alphanumeric characters and is at most 8 characters in length [people]:

12. Enter a password for the PeopleSoft Connect ID, and enter again on the next line, at the following prompt.

Enter a new PeopleSoft database Connect ID [people] password. Ensure the password contains only alphanumeric characters and is between 6 and 30 characters in length:

Re-Enter the PeopleSoft database Connect ID password:

13. Enter the PeopleSoft Operator ID (user ID):

Enter the PeopleSoft database Operator ID [PS]:

14. Enter the password twice for the PeopleSoft operator ID, such as PS or VP1.

Enter a new PeopleSoft database Operator ID [PS] password. Ensure the password contains only alphanumeric characters and is between 1 and 32 characters in length

Re-Enter the PeopleSoft Operator ID password:

15. Enter the Application Server Domain Connection password, following the guidelines in the prompt.

The window does not display masking characters as you type. There is no default password.

Note. This is an optional password. If no password is entered, the connection between Web Server and Application Server will not be password protected.

[Optional] Enter a new Application Server Domain connection password.

Ensure the password contains only alphanumeric characters and is between 8 and 30 characters in length:
Re-Enter the Application Server Domain connection password.

16. Enter the password twice for the PTWEBSEVER web profile user.

Note. The guideline in the prompt for the PTWEBSEVER user password does not allow special characters. However, the PeopleSoft system does allow special characters for the PTWEBSEVER password. If you want to change the password to include special characters, you have the option to do so in the PeopleSoft Pure Internet Architecture (PIA) after you complete the installation and domain creation.

See *PeopleTools: Security Administration*, "Working with Passwords."

Enter a new PeopleSoft WebProfile user [PTWEBSEVER] password. Ensure the password contains only alphanumeric characters and is between 8 and 32 characters in length:
Re-Enter the PeopleSoft WebProfile user password:

17. Enter the Oracle WebLogic Server Admin password, following the guidelines in the prompt.

The default Oracle WebLogic server administrator is system. The window does not display masking characters as you type. There is no default password.

Enter a new WebLogic Server Admin user [system] password. Ensure that the password is between 8 and 30 characters in length with at least one lowercase letter, one uppercase letter, one number or one special character (!@#\$\$%^&):
Re-Enter the WebLogic Server Admin user password:

18. Enter the Integration Gateway user ID and password.

The default user ID is administrator.

Note. The guideline in the prompt for the Integration Gateway user ID password does not allow special characters. However, the PeopleSoft system does allow special characters for the Integration Gateway password. If you want to change the password to include special characters, you have the option to do so in the PeopleSoft Pure Internet Architecture (PIA) after you complete the installation and domain creation.

See *PeopleTools: Security Administration*, "Working with Passwords."

Enter the PeopleSoft Integration Gateway user [administrator]:
Enter the PeopleSoft Integration Gateway user [administrator] password.
Ensure the password contains only alphanumeric characters and is between 8 and 30 characters in length:
Re-Enter the PeopleSoft Integration Gateway user password:

19. If you want to change any of the answers to the previous questions, enter *n* (no) at the following prompt, or enter *y* (yes) to continue:

Are you happy with your answers? [y|n]:

20. Review the status messages as the script updates the Puppet YAML files with the user input.

If EYAML files are installed, the passwords are encrypted and updated in the YAML file.

```
Encrypting the Passwords in the User Data:           [ OK ]
Updating the Puppet Hiera YAML Files with User Data: [ OK ]
```

21. Answer *n* (no) to indicate that you do not want to continue running the initialization script using the default

configuration.

The script stops. Follow the instructions for using customizations for mid-tier connectivity to complete the mid-tier deployment.

Note. To run step 2, the puppet apply step, it is a good idea to use a log name other than `psft_dpk_setup.log`, to differentiate the log from that for the DPK initialization.

See "Completing the DPK Initialization with Customizations."

The bootstrap script is ready to deploy and configure the PeopleSoft environment using the default configuration defined in the Puppet Hiera YAML files. You can proceed by answering 'y' at the following prompt. And, if you want to customize the environment by overriding the default configuration, you can answer 'n'. If you answer 'n', you should follow the instructions in the PeopleSoft Installation Guide for creating the customization Hiera YAML file and running the Puppet 'apply' command directly to continue with the setup of the PeopleSoft environment.

```
Do you want to continue with the default initialization process? [y|n]: =>
n
```

You have decided not to continue with the default PeopleSoft environment setup process. Any customizations to the PeopleSoft environment should be done in the Hiera YAML file 'psft_customizations.yaml' and place it under `[/cs1/psft/dpk/puppet/production/data]` folder. After making the necessary customizations, run the following commands to continue with the setup of PeopleSoft environment.

```
1. cd /cs1/psft/dpk/puppet/production/manifests
2. PUPPET_DIR/puppet apply
--confdir=/cs1/psft/dpk/puppet site.pp
--debug --trace --detailed-exitcodes
--logdest /some_valid_path/to/log/psft_dpk_setup.log
```

Exiting the PeopleSoft environment setup process.
The PeopleSoft Environment Setup Process Ended.

Note. For Linux, `PUPPET_DIR` is `/opt/puppetlabs/bin`. For AIX, HP-UX, or Solaris, `PUPPET_DIR` is `/opt/oracle/puppetlabs/bin`.

22. Review the status messages as the script runs Puppet profiles to set up the PeopleSoft environment.

A message of [OK] indicates that the profile has been applied successfully while a message [FAILED] indicates that the profile application failed.

The script stops and exits the first time a profile application fails, and displays an error message. This example shows the error message after the first step failed:

```
Starting the Default Initialization of PeopleSoft Environment:
```

```
Setting Up System Settings: [FAILED]
```

The initialization of PeopleSoft environment setup failed. Check the

log file [DPK_INSTALL/setup/psft_dpk_setup.log] for the errors. After correcting the errors, run the following commands to continue with the setup of PeopleSoft environment.

```
1. cd /cs1/psft/dpk/puppet/production/manifests
2. PUPPET_DIR/puppet apply
--confdir=/cs1/psft/dpk/puppet site.pp
--debug --trace --detailed-exitcodes
--logdest /some_valid_path/to/log/psft_dpk_setup.log
```

Exiting the PeopleSoft environment setup process.
The PeopleSoft Environment Setup Process Ended.

Note. For Linux, *PUPPET_DIR* is /opt/puppetlabs/bin. For AIX, HP-UX or Solaris, *PUPPET_DIR* is /opt/oracle/puppetlabs/bin.

Note. To run step 2, the puppet apply step, it is a good idea to use a log name other than psft_dpk_setup.log, to differentiate the log from that for the DPK initialization.

See "Completing the DPK Initialization with Customizations."

Upon successful completion, the DPK setup script displays the following message:

```
Starting the Default Initialization of PeopleSoft Environment:
Setting Up System Settings:                [ OK ]
Deploying PeopleTools Components:          [ OK ]
DSetting up PeopleSoft OS Users Environment: [ OK ]
Setting up PeopleSoft Application Server Domain: [ OK ]
Setting up PeopleSoft Process Scheduler Domain: [ OK ]
Setting up PeopleSoft PIA Domain:          [ OK ]
Changing the Passwords for the Environment: [ OK ]
Configuring Pre-Boot PeopleSoft Environment: [ OK ]
Starting PeopleSoft Domains:               [ OK ]
Configuring Post-Boot PeopleSoft Environment: [ OK ]
Setting up Source Details for PeopleTools Client: [ OK ]
The PeopleSoft Environment Setup Process Ended.
```

The complete setup log is written to the file psft_dpk_setup.log in the same location as the DPK setup script.

Task 7-1-3: Running with the Mid-Tier Option on Linux, AIX, HP-UX, or Solaris as a Non-Root User

If you are installing the PeopleSoft environment as a non-root user, ensure that you fulfill the prerequisites in the section Deploying as a Non-Root User on Linux, AIX, HP-UX, or Solaris.

To deploy mid-tier components on Linux, AIX, HP-UX, or Solaris hosts as a non-root user

1. Open a terminal window and change directory to *DPK_INSTALL/setup*.
2. Run the script as follows:
 - If you extracted the first zip file into the same directory where you downloaded the zip files, use this command:


```
./psft-dpk-setup.sh --env_type midtier
```

- If you extracted the first zip file into a different directory, include the option `dpk_src_dir` to specify the location of the downloaded zip files, such as `DPK_INSTALL`.

```
./psft-dpk-setup.sh --dpk_src_dir DPK_INSTALL --env_type midtier
```

Note. Running the DPK setup script with the `--env_type midtier` option deploys all servers. If you want to deploy one of the servers (Application Server, Process Scheduler server, PIA, or application server and Process Scheduler server) see the command options in the section Reviewing the DPK Setup Script Options.

3. Answer y (yes) at the following prompt:

```
You are running DPK setup without root/administrator access.
This is fine as long as the system administrator has performed
all necessary tasks and all prerequisites have been met.
Please see the documentation to determine the prerequisite tasks
that need to be performed to successfully run DPK set up
without root/administrator privilege.
```

```
Would you like to proceed with the setup as a non-root user? [y/n]: y
```

4. Wait while the script verifies that the necessary PeopleSoft DPK zip files are available and that the Puppet software is installed.

The system displays messages indicating the steps in the setup process. The success or failure of each step is indicated by [OK] or [FAILED].

```
Validating User Arguments:                [ OK ]
Validating PeopleSoft Supported Platform:  [ OK ]
```

```
Verifying if Puppet Software is installed: [ OK ]
Verifying if eYAML Hiera Backend is Installed: [ OK ]
```

```
Preparing the Redhat Linux VM for PeopleSoft Environment:
```

```
Checking if PeopleSoft DPKs are Present:   [ OK ]
```

5. At the following prompt, enter a location that is accessible to the host to be used as the PeopleSoft base directory.

The base directory is used to extract the PeopleSoft DPKs as well as for deploying PeopleSoft components. The directory `/cs1/psft` is used in this example:

Note. When entering the path for the base directory, use forward slashes (/). For example, `/cs1/psft`. If the name includes any non-alphanumeric characters such as periods, enclose the name in double quotes. Do not use a name for the base directory that begins with a number.

The base directory is used to extract the PeopleSoft DPKs. It is also used to deploy the PeopleSoft components. This directory should be accessible on the Linux VM, must have write permissions and should have enough free space.

```
Enter the PeopleSoft Base Directory: /cs1/psft
Are you happy with your answer? [Y|n|q]:
```

The script validates if there is enough free space available under the specified base directory for the PeopleSoft environment. The PeopleSoft environment setup is aborted if there is not enough free space.

Note. A mid-tier setup of a PeopleSoft environment takes about 25 GB of disk space.

Checking if the Base Directory has Enough Free Space: [OK]

The script creates the following three sub-directories under the user provided base directory, *BASE_DIR*:

- *BASE_DIR*/dpk

The script uses this directory to extract the archives from the PeopleSoft PeopleTools DPKs, and contains the Puppet YAML files for the deployment.

- *BASE_DIR*/pt

The script uses this directory to deploy PeopleSoft components.

- *BASE_DIR*/db

This directory is not used for this deployment.

6. Enter a writable directory with at least 10 GB available space for *PS_CFG_HOME*.

The default is *USER_HOME*/psft/pt/8.57, where *USER_HOME* is the home directory for the logged-in user. The *PS_CFG_HOME* directory holds the configuration and log files for the PeopleSoft Application Server, Process Scheduler, and PIA domains.

Enter a writable ps_config_home directory for PeopleSoft domains with at least 10.0GB space [/home/psftuser/psft/pt/8.57]:
Are you happy with your answer? [Y|n|q]: y

7. Review the status messages as the script validates the files found in *DPK_INSTALL* and extracts the DPK archives.

The script carries out validations for the mid-tier deployment. If any of the validations fail, the PeopleSoft environment setup is aborted.

Note. The messages have been truncated for brevity.

Validating the PeopleSoft DPKs in the Linux VM:

[...]

Extracting the PeopleSoft DPK Archives in the Linux VM:

[...]

8. Review the status messages as the script sets up the Puppet file system.

The script sets up Puppet on the host or VM. As part of this setup, if the EYAML files are installed, it will generate the encryption keys. It then copies the PeopleSoft Puppet modules to the standard location (*BASE_DIR*/dpk) and updates the YAML files to reflect the type of PeopleSoft environment setup.

Setting up Puppet on the Linux VM:

Generating eYAML Hiera Backend Encryption Keys: [OK]

Updating the Puppet Hiera YAML Files in the Linux VM: [OK]

Updating the Role in Puppet Site File for the Linux VM: [OK]

9. Specify FRESH for the installation type.

Enter the PeopleSoft installation [PUM or FRESH] type [PUM]: **FRESH**

Note. You see this prompt only when PeopleSoft application DPKs that were built on the same PeopleTools release, are present in *DPK_INSTALL*.

Note. If you are using the PeopleSoft Upgrade Source Image to set up an environment for the Upgrade Source database, you do not see this prompt.

10. Specify the information for the database that you want to connect to.

- a. Enter DB2UNIX for a DB2 for Linux, UNIX, and Windows database platform.

Enter the PeopleSoft database platform [ORACLE]: **DB2UNIX**

- b. Enter y (yes) if the database you are connecting to is a Unicode database, or n (no) for a non-Unicode database.

Is the PeopleSoft database unicode? [Y|n]:

- c. Enter y (yes) if you want to install the files needed for multi-language support.

Note. You see this prompt only when PeopleSoft application DPKs that were built on the same PeopleTools release, are present in *DPK_INSTALL*.

Do you want Multi Language support in PeopleSoft database? [y|N]:

- d. Enter the database name.

Enter a new PeopleSoft database name. Ensure that the database name start with a letter and contains only uppercase letters and numbers and is no more than 8 characters in length [HCM92]:

- e. Enter the name of the host where the database is installed, and the DB2 instance port number:

Use forward slashes if necessary. If the database name or service name includes non-alphanumeric characters such as periods, enclose the name in double quotes. For example, "host.example.com".

Enter the PeopleSoft database host name:

Enter the PeopleSoft database port [1521]: **50000**

11. Enter the PeopleSoft Connect ID at the following prompt:

The default is people.

Enter a new PeopleSoft database Connect ID. Ensure that the ID contains only alphanumeric characters and is at most 8 characters in length [people]:

12. Enter a password for the PeopleSoft Connect ID, and enter again on the next line, at the following prompt.

Enter a new PeopleSoft database Connect ID [people] password. Ensure the password contains only alphanumeric characters and is between 6 and 30 characters in length:

Re-Enter the PeopleSoft database Connect ID password:

13. Enter the PeopleSoft Operator ID (user ID):

Enter the PeopleSoft database Operator ID [PS]:

14. Enter the password twice for the PeopleSoft operator ID, such as PS or VP1.

Enter a new PeopleSoft database Operator ID [PS] password. Ensure the password contains only alphanumeric characters and is between 1 and 32 characters in length

Re-Enter the PeopleSoft Operator ID password:

15. Enter the Application Server Domain Connection password, following the guidelines in the prompt.

The window does not display masking characters as you type. There is no default password.

Note. This is an optional password. If no password is entered, the connection between Web Server and Application Server will not be password protected.

[Optional] Enter a new Application Server Domain connection password. Ensure the password contains only alphanumeric characters and is between 8 and 30 characters in length:
Re-Enter the Application Server Domain connection password.

16. Enter the password twice for the PTWEBSEVER web profile user.

Note. The guideline in the prompt for the PTWEBSEVER user password does not allow special characters. However, the PeopleSoft system does allow special characters for the PTWEBSEVER password. If you want to change the password to include special characters, you have the option to do so in the PeopleSoft Pure Internet Architecture (PIA) after you complete the installation and domain creation.

See *PeopleTools: Security Administration*, "Working with Passwords."

Enter a new PeopleSoft WebProfile user [PTWEBSEVER] password. Ensure the password contains only alphanumeric characters and is between 8 and 32 characters in length:
Re-Enter the PeopleSoft WebProfile user password:

17. Enter the Oracle WebLogic Server Admin password, following the guidelines in the prompt.

The default Oracle WebLogic server administrator is system. The window does not display masking characters as you type. There is no default password.

Enter a new WebLogic Server Admin user [system] password. Ensure that the password is between 8 and 30 characters in length with at least one lowercase letter, one uppercase letter, one number or one special character (!@#\$%^&):
Re-Enter the WebLogic Server Admin user password:

18. Enter the Integration Gateway user ID and password.

The default user ID is administrator.

Note. The guideline in the prompt for the Integration Gateway user ID password does not allow special characters. However, the PeopleSoft system does allow special characters for the Integration Gateway password. If you want to change the password to include special characters, you have the option to do so in the PeopleSoft Pure Internet Architecture (PIA) after you complete the installation and domain creation.

See *PeopleTools: Security Administration*, "Working with Passwords."

Enter the PeopleSoft Integration Gateway user [administrator]:
Enter the PeopleSoft Integration Gateway user [administrator] password. Ensure the password contains only alphanumeric characters and is between 8 and 30 characters in length:
Re-Enter the PeopleSoft Integration Gateway user password:

19. If you want to change any of the answers to the previous questions, enter *n* (no) at the following prompt, or enter *y* (yes) to continue:

Are you happy with your answers? [y|n]:

20. Review the status messages as the script updates the Puppet YAML files with the user input.

If EYAML files are installed, the passwords are encrypted and updated in the YAML file.

```
Encrypting the Passwords in the User Data:          [ OK ]
Updating the Puppet Hiera YAML Files with User Data: [ OK ]
```

21. Answer *n* (no) to indicate that you do not want to continue running the initialization script using the default configuration.

The script stops. Follow the instructions for using customizations for mid-tier connectivity to complete the mid-tier deployment.

See "Completing the DPK Initialization with Customizations."

The bootstrap script is ready to deploy and configure the PeopleSoft environment using the default configuration defined in the Puppet Hiera YAML files. You can proceed by answering 'y' at the following prompt. And, if you want to customize the environment by overriding the default configuration, you can answer 'n'. If you answer 'n', you should follow the instructions in the PeopleSoft Installation Guide for creating the customization Hiera YAML file and running the Puppet 'apply' command directly to continue with the setup of the PeopleSoft environment.

Do you want to continue with the default initialization process? [y|n]: ⇒
n

You have decided not to continue with the default PeopleSoft environment setup process. Any customizations to the PeopleSoft environment should⇒
be

done in the Hiera YAML file 'psft_customizations.yaml' and place it⇒
under

[/cs1/psft/dpk/puppet/production/data] folder. After making the
necessary customizations, run the following commands to continue with⇒
the
setup of PeopleSoft environment.

```
1. cd /cs1/psft/dpk/puppet/production/manifests
2. PUPPET_DIR/puppet apply --confdir=/cs1/psft/dpk/puppet site.pp
--debug --trace --detailed-exitcodes
--logdest /some_valid_path/to/log/psft_dpk_setup.log
```

Exiting the PeopleSoft environment setup process.
The PeopleSoft Environment Setup Process Ended.

Note. For Linux, *PUPPET_DIR* is /opt/puppetlabs/bin. For AIX, HP-UX, or Solaris, *PUPPET_DIR* is /opt/oracle/puppetlabs/bin.

Note. To run step 2, the puppet apply step, it is a good idea to use a log name other than psft_dpk_setup.log, to differentiate the log from that for the DPK initialization.

22. Review the status messages as the script runs Puppet profiles to set up the PeopleSoft environment.

A message of [OK] indicates that the profile has been applied successfully while a message [FAILED] indicates that the profile application failed.

The script stops and exits the first time a profile application fails, and displays an error message. This example shows the error message after the first step failed:

Starting the Default Initialization of PeopleSoft Environment:

Setting Up System Settings: [FAILED]

The initialization of PeopleSoft environment setup failed. Check the log file [DPK_INSTALL/setup/psft_dpk_setup.log] for the errors. After correcting the errors, run the following commands to continue with the setup of PeopleSoft environment.

```
1. cd /cs1/psft/dpk/puppet/production/manifests
2. PUPPET_DIR/puppet apply --confdir=/cs1/psft/dpk/puppet site.pp
   --debug --trace --detailed-exitcodes
   --logdest /some_valid_path/to/log/psft_dpk_setup.log
```

Exiting the PeopleSoft environment setup process.
The PeopleSoft Environment Setup Process Ended.

Note. For Linux, *PUPPET_DIR* is /opt/puppetlabs/bin. For AIX, HP-UX or Solaris, *PUPPET_DIR* is /opt/oracle/puppetlabs/bin.

Note. If you run step 2, the puppet apply step, given in the failure message, it is a good idea to use a log name other than psft_dpk_setup.log, to differentiate the log from that for the DPK initialization.

See "Completing the DPK Initialization with Customizations."

Upon successful completion, the DPK setup script displays the following message:

```
Starting the Default Initialization of PeopleSoft Environment:
Setting Up System Settings: [ OK ]
Deploying PeopleTools Components: [ OK ]
DSetting up PeopleSoft OS Users Environment: [ OK ]
Setting up PeopleSoft Application Server Domain: [ OK ]
Setting up PeopleSoft Process Scheduler Domain: [ OK ]
Setting up PeopleSoft PIA Domain: [ OK ]
Changing the Passwords for the Environment: [ OK ]
Configuring Pre-Boot PeopleSoft Environment: [ OK ]
Starting PeopleSoft Domains: [ OK ]
Configuring Post-Boot PeopleSoft Environment: [ OK ]
Setting up Source Details for PeopleTools Client: [ OK ]
The PeopleSoft Environment Setup Process Ended.
```

The setup.log is written to the file <USER_HOME>/psft_dpk_work/psft_dpk_setup_<PID>.log, where <USER_HOME> is the home directory for the user running the script, and <PID> is a process ID

Task 7-2: Completing Installation Tasks

After completing the installation process, be sure to go to the chapter "Completing the Installation." This chapter includes information on accessing the PeopleSoft environment, as well as post-installation steps.

It is important that you perform the tasks in the section Completing Post-Installation Steps that apply to your environment.

Chapter 8

Completing the Installation

This chapter discusses:

- Completing Post-Installation Steps
- Using the PeopleSoft Installation
- Working with PeopleSoft Utilities and Programs for Root Deployments on Linux, AIX, HP-UX, and Solaris
- Setting Environment Variables for the Non-Root User on Linux, AIX, HP-UX, or Solaris

Task 8-1: Completing Post-Installation Steps


This section discusses:

- Using Fluid User Interface
- Updating the Installation Table
- Setting Options for Multilingual Databases
- Updating PeopleTools Options
- Updating Time Zone Information
- Updating Database Information

Task 8-1-1: Using Fluid User Interface

When you sign in to your PeopleSoft application, you may see the PeopleSoft Fluid User Interface by default. To access the menu items, as seen in the classic user interface, from the PeopleSoft Fluid User Interface:


1. On the PeopleSoft Fluid User Interface, shown in this example, select (press) the NavBar button at the top right (diamond inside a circle).



PeopleSoft Fluid User Interface home page

The Navigation bar (NavBar) side page appears.


2. Select (press) Navigator.



NavBar side page

The menu structure appears.

3. Navigate to the desired item, such as Set Up HCM or PeopleTools.



Navigator side page with PeopleSoft menu items

See Also

PeopleTools: Applications User's Guide, "Working With Fluid Homepages"

PeopleTools: Fluid User Interface Developer's Guide

Task 8-1-2: Updating the Installation Table

After you complete the installation process, creating the database, installing the Application Server, and installing the PeopleSoft Pure Internet Architecture, you must complete this additional step. This postinstallation step ensures that only the products you are entitled to use are active in the installation. The location of the installation table in the PeopleSoft system varies depending upon the PeopleSoft application that you installed.

Note. For information on the products you are entitled to use, contact your Oracle Support representative.

1. Sign on to the PeopleSoft system in a browser.
2. Select Set Up *Application_name* (where *Application_name* is the PeopleSoft application you installed), Install, Installation Table.
3. Select the Products tab.

4. Clear the check boxes for the products that you are not entitled to use.

Task 8-1-3: Setting Options for Multilingual Databases

Setting the Data Field Length Checking Option

The value to specify data field length checking must be set correctly in order for PeopleSoft applications to perform correctly in a browser. Use one of these methods to set the data field length checking option:

- Select PeopleTools, Utilities, Administration, PeopleTools Options, and select the Data Field Length Checking option from the drop-down list.
- Alternatively, use the SQL tool for your database platform to modify the DBLENGTHTYPE parameter in the PSOPTIONS table.

See *PeopleTools: Global Technology*, "Setting Data Field Length Checking."

See *PeopleTools: Global Technology*, "Selecting Character Sets."

Use the guidelines in this table to select the correct option for your environment:

Environment	PeopleTools Option Page Selection	PSOPTIONS.DBLENGTHTYPE Value
Unicode-encoded database or a non-Unicode SBCS database	Others	N
Japanese database on DB2 LUW	DB2 MBCS	D
Non-Unicode Japanese database Note. If your installation uses the Shift-JIS character set for Japanese, you must use this option.	MBCS Note. The MBCS option is not supported for DB2 z/OS.	M

Setting the Unicode Enabled Option

If you are running a Unicode database, verify that the UNICODE_ENABLED parameter in the PSSTATUS table is set correctly. For example:

- For non-Unicode databases, including those using the Shift-JIS character set for Japanese, set UNICODE_ENABLED=0.
- For Unicode databases, set UNICODE_ENABLED=1.

See the information on converting to Unicode in the *PeopleTools: Global Technology* product documentation.

Task 8-1-4: Updating PeopleTools Options

You can set the following options on the PeopleTools Options page:

- Multi-Currency — Select this check box if you plan to use currency conversion.
See *PeopleTools: Global Technology*, "Using System-Wide Multicurrency Settings."
- Base Time Zone — Enter a value for the base time zone for your PeopleTools database.

See *PeopleTools: Global Technology*, "Setting the Base Time Zone."

- Sort Order Option — If you specified a non-binary sort order for your database, choose the Sort Order Option that most closely approximates your database sort order.

See *PeopleTools: Global Technology*, "Setting the Sort Order."

Task 8-1-5: Updating Time Zone Information

Additional steps may be required to configure your time zone after you complete the installation.

See *PeopleTools: Global Technology*, "Maintaining Time Zones."

Task 8-1-6: Updating Database Information

The database information updated in this procedure is used by the PeopleSoft software update tools to identify your PeopleSoft database when searching for updates. These steps should be followed for all additional databases that you create to enable the accurate identification of your databases.

1. Sign on to your PeopleSoft database.
2. Navigate to PeopleTools, Utilities, Administration, PeopleTools Options.
3. Specify long and short names for your environment. For example:
 - Environment Long Name — Customer HR Demo Database
 - Environment Short Name — HR Demo DB
4. Select a system type from the drop-down list. For example, Demo Database.
5. Save your changes.

Task 8-2: Using the PeopleSoft Installation

This section discusses:

- Accessing the PeopleSoft Environment
- Reviewing the Deployment File System
- Reviewing the DPK-Created Users for Root Deployments on Linux, AIX, HP-UX, and Solaris

Task 8-2-1: Accessing the PeopleSoft Environment

To sign in to the deployed PeopleSoft environment in a browser (that is, use the PeopleSoft Pure Internet Architecture, or PIA), use a URL with this format:

`http://<host_name>:<http_port>/<PIA_site_name>/signon.html`

For example, for a deployment with the default port, 8000, and default PIA site name, ps, the URL would be `http://server1.example.com:8000/ps/signon.html`.

See the PeopleSoft Hosted Online Help, <http://www.peoplesoftonlinehelp.com>, for information on working with the components in a PeopleSoft installation.

Task 8-2-2: Reviewing the Deployment File System

The PeopleSoft installation deployed by the PeopleSoft DPKs sets up an environment comprised of several directories. This table lists the directories with the location, contents of the directory, and the owner.

Directory	Description	Default Location	Access
PS_HOME	<i>PS_HOME</i> is a secure location for the PeopleTools binary installation files.	<p><BASE_DIR>/pt/ps_home <ptools_patch_ver></p> <p>The descriptor <ptools_patch_ver> is the PeopleSoft PeopleTools full release, for example 8.57.01.</p>	This directory can only be written to by the PeopleSoft administrator, psadm1.
PS_CFG_HOME	The <i>PS_CFG_HOME</i> location holds the configuration and log files for the PeopleSoft Application Server and Process Scheduler server domains.	<ul style="list-style-type: none"> On Linux, AIX, HP-UX, or Solaris, /home/psadm2/psft/pt/ <ptools_major_ver> On Microsoft Windows, C:\%USERPROFILE%\psft\pt\ <ptools_major_ver> <p>For example, if the USERPROFILE environment variable is C:\Users\username, the location is C:\Users\username\psft\pt\8.57.</p> <p>The descriptor <ptools_major_ver> is the PeopleSoft PeopleTools major release without patch numbers; for example, 8.57.</p>	This directory is owned by psadm2.

Directory	Description	Default Location	Access
PIA_HOME	The web server (PIA) configuration files are located in <i>PS_CFG_HOME</i> /webserve.	<ul style="list-style-type: none"> On Linux, AIX, HP-UX, or Solaris, /home/psadm2/psft/pt/<ptools_major_ver>/webserve On Microsoft Windows, C:\%USERPROFILE%\psft\pt\<ptools_major_ver>\webserve <p>For example, if the USERPROFILE environment variable is C:\Users\username, the location is C:\Users\username\psft\pt\8.57\webserve.</p> <p>The descriptor <ptools_major_ver> is the PeopleSoft PeopleTools major release without patch numbers; for example, 8.57.</p>	This directory is owned by psadm2.
PS_APP_HOME	The <i>PS_APP_HOME</i> location holds the PeopleSoft application installation files.	<p><i>BASE_DIR</i>/pt/<Product>_app_home</p> <p>The descriptor <Product> is an abbreviation for the PeopleSoft application, such as hcm for PeopleSoft Human Capital Management</p>	This directory can only be written to by psadm3.
ORACLE_HOME (Oracle RDBMS software)	<p>This directory includes the Oracle RDBMS database server and client connectivity software, including the SQL*Plus program.</p> <p>The Oracle RDBMS client installation is the 64-bit client used by PeopleSoft PeopleTools to connect from the PeopleSoft Application Server and Process Scheduler domains to the PeopleTools Database.</p> <p>Note. The default listener port is 1521.</p>	<i>BASE_DIR</i> /db/oracle-server	This directory is owned by user oracle2.

Directory	Description	Default Location	Access
Oracle WebLogic	This directory includes the installation files for the Oracle WebLogic web server. Note. The configuration files for the PIA domain are located in <i>PS_CFG_HOME/webserve</i> .	<i>BASE_DIR/pt/bea/wlserver</i>	This directory is owned by psadm1.
Oracle Tuxedo	This directory includes the installation files for Oracle Tuxedo.	<i>BASE_DIR/pt/bea/tuxedo</i>	This directory is owned by psadm1.
PeopleSoft database files (on Oracle RDBMS)	This directory includes the Oracle database files and tables for the PeopleSoft application.	<i>BASE_DIR/db/oradata</i>	The owner of the database tables is oracle2 and its group is oinstall. Note. This is different from the users for the PeopleSoft installation and configuration.

See Also

PeopleTools: System and Server Administration, "Securing PS_HOME and PS_CFG_HOME"

Task 8-2-3: Reviewing the DPK-Created Users for Root Deployments on Linux, AIX, HP-UX, and Solaris

When deploying on Linux, AIX, HP-UX, and Solaris as the root user, the deployed configuration includes the default users and default passwords described in the following table.

Important! All of the passwords for the DPK-created users are set to expire immediately. On the first login of one of the DPK-created users, the system will prompt you to provide new passwords.

In the case of the passwords that expire immediately, such as those for psadm1 and so on, if you do not log in as the user specified in this table and change the password, the default passwords documented here remain in effect.

New passwords must include the following characteristics:

- At least 14 characters long
- At least one digit (0–9)
- At least one special character (for example, * or #)
- At least one lowercase letter (a–z)
- At least one uppercase letter (A–Z)

User Name	Default Password	Home Directory	Role Definition
psadm1	Oradmin (the first character is the number zero)	<i>USER_HOME</i> /psadm1 You supply the location for the <i>USER_HOME</i> when you run the DPK setup script. The default value is /home.	The PeopleSoft installation administrator who owns <i>PS_HOME</i> . This user cannot write into <i>PS_CFG_HOME</i> .
psadm2	Oradmin (the first character is the number zero)	<i>USER_HOME</i> /psadm2 You supply the location for the <i>USER_HOME</i> when you run the DPK setup script. The default value is /home.	The PeopleTools domain user who creates and configures the Application Server domain, Process Scheduler (batch server) domain, and the PIA. This user cannot write to <i>PS_HOME</i> , but has read-execute access.
psadm3	Oradmin (the first character is the number zero)	<i>USER_HOME</i> /psadm3 You supply the location for the <i>USER_HOME</i> when you run the DPK setup script. The default value is /home.	The PeopleSoft installation administrator who owns <i>PS_APP_HOME</i> .
oracle2	oracle	<i>USER_HOME</i> /oracle2 You supply the location for the <i>USER_HOME</i> when you run the DPK setup script. The default value is /home.	The Oracle Database Server user name.
esadm1	Oradmin (the first character is the number zero)	<i>USER_HOME</i> /esadm1 You supply the location for the <i>USER_HOME</i> when you run the DPK setup script. The default value is /home.	The Elasticsearch DPK user Note. This is not the same as the esadmin administrator, which is used in configuring a search instance.

Note. The Elasticsearch DPK user, esadm1, is deployed for the Native OS for Linux, AIX, HP-UX, and Solaris DPKs, as well as the VirtualBox DPK. However, Elasticsearch is installed and configured only as part of the VirtualBox DPK deployment.

See Also

"Completing the DPK Initialization with Customizations," Preparing the Customization File for Linux, AIX, HP-UX, or Solaris Users

Task 8-3: Working with PeopleSoft Utilities and Programs for Root Deployments on Linux, AIX, HP-UX, and Solaris

When you run the DPK setup script with the default initialization, the script installs, configures and starts a single Application Server, a single Process Scheduler, and a single PIA domain. After the root user completes the deployment of the PeopleSoft environment using the DPK setup script `DPK_INSTALL/setup/psft-dpk-setup.sh`, in order to carry out operations on the PeopleSoft environment such as stopping and starting the DPK-created domains, or creating additional domains with PSADMIN, the root user must start a new shell session, and sign in with the DPK-created user `psadm2`.

See *PeopleTools: System and Server Administration* for information on working with PeopleSoft domains.

The first time that you sign in as user `psadm2`, you are prompted to change the default password. You must start the session again and sign in with the new password. When you first sign in, the system sources the `PS_HOME/psconfig.sh` script. Sourcing the `psconfig.sh` script sets environment variables such as `TUXDIR`, `PATH`, and `LD_LIBRARY_PATH`, which are needed to run PeopleSoft utilities and programs. Sourcing the `psconfig.sh` script sets the environment variables for the current session in the current shell, so that the programs and utilities you run in that shell inherit the environment variables.

Similarly, to carry out operations using programs owned by the DPK-created users `psadm1` or `psadm3`, sign in to a shell as those users.

See *Reviewing the DPK-Created Users for Root Deployment on Linux, AIX, HP-UX, and Solaris*.

Task 8-4: Setting Environment Variables for the Non-Root User on Linux, AIX, HP-UX, or Solaris

When you use the DPK setup script with the default initialization, the script installs, configures and starts a single Application Server, a single Process Scheduler, and a single PIA domain.

When a non-root user deploys the PeopleSoft environment, as part of the deployment, the DPK setup script sources a shell script that sets environment variables, such as `TUXDIR`, `PATH`, and `LD_LIBRARY_PATH`, which are needed to run PeopleSoft utilities and programs.

See *PeopleTools: System and Server Administration* for information on working with PeopleSoft domains.

After the non-root user completes the deployment of the PeopleSoft environment using the DPK setup script `DPK_INSTALL/setup/psft-dpk-setup.sh`, to carry out operations on the PeopleSoft environment such as stopping and starting the DPK-created domains, creating additional domains with PSADMIN, or running Application Engine programs, the non-root user must source the script `BASE_DIR/pt/psft_env.sh`. For example, use the following command:

```
source BASE_DIR/pt/psft_env.sh
```

Note that it is important to source the shell script (`source BASE_DIR/pt/psft_env.sh`), rather than simply running it (`BASE_DIR/pt/psft_env.sh`) in order for the environment variables to persist in the current shell. See your operating system documentation for the correct command to source the script.

Sourcing the `psft_env.sh` script sets the environment variables for the current session in the current shell, so that the programs and utilities you run in that shell inherit the environment variables. You must source the script and run the PeopleSoft utilities and programs from the same `BASE_DIR`. That is, the environment variables apply only to the programs in the `PS_HOME` installed under the `BASE_DIR` from which you run the script.

If your environment includes more than one deployment, be sure to source *BASE_DIR/pt/psft_env.sh* as needed in separate shells for each *BASE_DIR*.

The *psft_env.sh* script points to default or user-specified installation locations as set up by the DPK setup script. See *Reviewing the Deployment File System* for default locations. Here is a summary of the environment variables set by the *BASE_DIR/pt/psft_env.sh* script:

- The script sets a pseudo random number generator to avoid getting stuck in entropy collection for the default random number generation.
- The script sets the *TUXDIR*, *PATH*, and *LD_LIBRARY_PATH* environment variables to point to the Tuxedo installation.
- The script sets the *TNS_ADMIN*, *ORACLE_HOME*, and *LD_LIBRARY_PATH* environment variables to point to the installations of the Oracle database and Oracle database client.
- The script sets language/locale.
- The script sets *PS_CFG_HOME*.
- The script adds the *PS_HOME/appserv* and *PS_HOME/setup* directories to the *PATH*.
- The script sources the *PS_HOME/psconfig.sh* script.

The *psconfig.sh* script was used previously to set environment variables for non-DPK installations. Because it is included in the *BASE_DIR/pt/psft_env.sh* script, you do not need to source *psconfig.sh* separately.

Chapter 9

Deploying the PeopleTools Client DPK

This chapter discusses:

- Deploying the PeopleTools Client DPK

Task 9-1: Deploying the PeopleTools Client DPK

This section discusses:

- Understanding the Standalone Mode Deployment
- Preparing for the PeopleTools Client DPK Deployment
- Deploying in Standalone Mode

Task 9-1-1: Understanding the Standalone Mode Deployment

Use the standalone mode (SA mode) deployment for the PeopleTools Client DPKs when deploying the DPKs alone, without first deploying the PeopleSoft application or PeopleSoft PeopleTools DPKs. Use this method, for example, when carrying out a PeopleTools-only upgrade.

Use SA mode deployment for the following tasks:

- PeopleTools Upgrade

The deployment process installs a PeopleTools client *PS_HOME* that includes the directories needed for a PeopleSoft PeopleTools-only upgrade, such as data, projects, and scripts directories.

- PeopleTools Patch

The deployment process installs a PeopleTools client *PS_HOME* that includes the directories needed for a PeopleSoft PeopleTools patch application, such as the PTP directory.

See "Learning About the PeopleSoft Deployment Process," Reviewing the PeopleTools Patch DPKs.

- PeopleTools Client

The deployment process installs a PeopleTools client *PS_HOME*. Choose the deployment type "None of the above" for this deployment.

- Change Assistant installation

You can install Change Assistant as part of the PeopleTools Client deployment, or as a separate installation. The deployment process installs, but does not configure Change Assistant. To use Change Assistant for a PeopleSoft PeopleTools-only upgrade or to apply a PeopleSoft PeopleTools patch, you must configure Change Assistant manually. See the PeopleTools upgrade or patch documentation for information.

If there is an existing Change Assistant installation, the deployment process removes or upgrades it to the current release, and saves a configuration file with the existing setup.

- Change Impact Analyzer

You can install Change Impact Analyzer as part of the PeopleTools Client deployment, or as a separate installation.

- PeopleSoft Test Framework (PTF) installation

You can install PeopleSoft Test Framework as part of the PeopleTools Client deployment, or as a separate installation.

- PeopleSoft Test Framework (PTF) configuration

If you choose to configure PTF, the deployment process prompts you for setup parameters. You can configure PTF either at the same time that you install it or later. For example, you may choose to configure PTF separately if you install and configure it first, and then later the middle-tier components in your environment change. In this case, you do not need to install, but you can use the deployment process to reconfigure PTF.

- Configuration Manager

If you accept the option to configure the PeopleTools client, the information that you supply is used to configure Configuration Manager.

- The PeopleTools Client deployment installs Microsoft Visual C++ Redistributable Packages for Visual Studio, which include required Microsoft C++ runtime libraries.

Task 9-1-2: Preparing for the PeopleTools Client DPK Deployment

To deploy the PeopleTools Client DPK:

1. Go to the download location for the PeopleSoft PeopleTools DPKs, and download only the last zip file to a location known as *DPK_INSTALL* on a Microsoft Windows computer.

The last zip file, for example *Filename_4of4.zip*, is the PeopleSoft PeopleTools client DPK.

See Obtaining the PeopleSoft PeopleTools Patch DPKs, for the filename syntax of the DPK zip files.

2. Extract the downloaded zip file, which yields another zip file.
3. Extract the resulting zip file to a local or shared directory; for example *C:\tools-client*.

Task 9-1-3: Deploying in Standalone Mode

This section assumes that the user running the script has administrative permission.

To deploy the PeopleTools Client DPK in SA mode:

1. Verify that the Microsoft Windows folders options are set to show known file extensions.


Hidden file extensions may interfere with the script. To show file extensions, for example:

- a. Open Windows Explorer and select Tools, Folder Options.

Note. Depending upon the Microsoft Windows operating system, you may use a different method to set the folder options.

- b. On the Folder Options dialog box, select the View tab.

- c. Verify that the check box for Hide extensions for known file types is not selected, as shown in this example:



Folder Options dialog box: View tab

- d. Click OK to close the box.
2. Open a command prompt, running as administrator, and change directory to the C:\tools_client folder. The tools_client folder includes various sub-folders, and the following files:

- SetupPTClient.bat

The interactive script that installs the PeopleSoft PeopleTools components such as Application Designer, Change Assistant, Change Impact Analyzer, and PeopleSoft Test Framework.

- readme.txt

3. Run the setup script with the following command:

```
SetupPTClient.bat -t
```

Note. If you see an error message similar to "The application has failed to start because its side-by-side configuration is incorrect," it indicates that your machine does not include the necessary Microsoft C++ runtime libraries. Go to the Microsoft Web site, locate the Microsoft Visual C++ redistributable package for your system, and install as directed.

- The setup script deploys to drive C by default. To deploy to a different drive, you can use the option `-d <drive>`:

```
SetupPTClient.bat -t -d E
```

This option installs all specified software (Change Assistant, Change Impact Analyzer, PeopleSoft Test Framework), installation and temporary directories, and log files to the specified drive, E:\ in this example. The drive can be any valid local or mapped shared drive.

- To enable logging, include the option `-l` in the command:

```
SetupPTClient.bat -t -l
```

4. Answer *y* (yes) at the following prompt to deploy the PeopleTools Client.

If you are running the script after having deployed the PeopleTools Client previously, and you want to install Change Assistant, Change Impact Analyzer, or PeopleSoft Test Framework without deploying the PeopleTools Client again, answer *n* (no), and continue with step 9.

```
***** SetupPTClient started at 11:42:38.91 *****
set logger to true
Do you want to deploy PeopleTools client? [Y/N]: y
```

5. Specify the RDBMS type for the PeopleTools Client that you want to deploy.

In this example, the RDBMS is option 2, DB2 for LUW.

```
Please Select the Database Platform:
```

1. Oracle
2. DB2 for LUW
3. Microsoft SQL Server
4. DB2 for zOS

```
Enter your choice [1-4] : 2
```

6. Specify the installation directory, referred to as PSHOME, for the PeopleTools Client, or press ENTER to accept the default directory, C:\PT<release_number>_Client_<database_type>, for example C:\PT8.57.02_Client_DBX.

```
Please specify the PSHOME for the PeopleTools Client
[C:\PT8.57.02_Client_DBX]:
```

7. Specify whether you want to supply configuration details at the following prompt.

```
Do you want to configure PeopleTools client? [Y/N]:
```

If you answer *n* (no), you do not want to configure the PeopleTools client, continue with step 9.

If you answer *y* (yes), specify the information for your environment at the following prompts:

```
Database Name: HCM92
Server Name: example.com
UserId: VP1
Connect ID: people
Connect Password:
Retype Connect Password:
```

Note. When you enter the password, the script does not echo the password or any masking characters as you type.

- Specify the database name and database server to connect to.
- The connect ID a valid database-level ID that the PeopleSoft system uses to make the initial connection to the database.
- For User ID, specify a PeopleSoft user ID, such as VP1 or PS, that has permission to access the database from the PeopleTools client, Application Designer, and so on.

8. Select the type of deployment at the following prompt:

See the definitions in Understanding the Standalone Mode Deployment.

Please make your selection for the Tools Client deployment:

1. People Tools Full Upgrade
2. People Tools Patch
3. None of the above

Enter your choice [1-3]:

9. Specify whether you want to install Change Assistant at the following prompt:

Do you want to install Change Assistant? [Y/N]:

If you answer y (yes), specify the installation directory, or accept the default, C:\Program Files\PeopleSoft\Change Assistant:

Please specify the directory to install Change Assistant
[C:\Program Files\PeopleSoft\Change Assistant]:

10. Specify whether you want to install Change Impact Analyzer at the following prompt:

Do you want to install Change Impact Analyzer? [Y/N]:

If you answer y (yes), specify the installation directory for Change Impact Analyzer, or accept the default, C:\Program Files\PeopleSoft\Change Impact Analyzer:

Please specify the directory to install Change Impact Analyzer
[C:\Program Files\PeopleSoft\Change Impact Analyzer]:

11. Specify whether you want to install PeopleSoft Test Framework at the following prompt:

Do you want to install PeopleSoft Test Framework? [Y/N]:

If you answer y (yes), specify the installation directory for PeopleSoft Test Framework, or accept the default, C:\Program Files\PeopleSoft\PeopleSoft Test Framework:

Please specify the directory to install PeopleSoft Test Framework
[C:\Program Files\PeopleSoft\PeopleSoft Test Framework]:

12. Specify whether you want to configure the PeopleSoft Test Framework at the following prompt:

Do you want to configure PeopleSoft Test Framework? [Y/N]:

If you answer y (yes), specify the information for your environment. For information on these parameters, see the PeopleTools Test Framework product documentation.

See *PeopleTools: Test Framework*, "Installing a PTF Client."

Database Name: **HCM92**

Server:Port: **example.com:443**

```

Node ID: node_name
User ID: VP1
Proxy [Y/N]: y
Proxy Server: proxyserver.com
Proxy Port: 5000
Proxy User: username
Proxy Password: *****
Retype Proxy Password: *****

```

13. Review the setup steps.

The messages you see depend upon your choices.

```

Starting Tools Client Deployment!
Deploying PeopleTools 8.57.02 Client in C:\PT8.57.02_Client_DBX
Configuring PeopleTools 8.57.02 Client
Deployment of PeopleTools Client Complete.
Tools Client Deployment Ended.
***** SetupPTClient ended at 11:35:08.91 *****
Please review C:\PeopleSoft\PTClientDeploy.log for additional⇒
information.

```

14. To review the log file for the setup process, go to %USERPROFILE%\AppData\Local\Temp\PeopleSoft\PTClientDeploy.log.

For example, if the USERPROFILE environment variable is C:\Users\username, the log file location is C:\Users\username\AppData\Local\Temp\PeopleSoft\PTClientDeploy.log.

Note. If you used the `-d <drive>` option to deploy to a drive other than drive C:\, the log file is found in `<drive>:\Users\<username>\AppData\Local\Temp\PeopleSoft\PTClientDeploy.log` and creates the directory if it does not exist.

The PTClientDeploy.log file includes a record of each of the steps in the PeopleTools Client deployment process. If any of the steps fail, a detailed error or warning message will be written to the same log file.

Part II

Discretionary Installation

The second part of the installation guide includes optional tasks, tasks that are only required by certain environments, and those that you may decide to defer until after the initial installation.

Chapter 10A

Installing and Compiling COBOL on Windows

This chapter discusses:

- Understanding COBOL
- Prerequisites
- Preparing COBOL for a PeopleTools-only Upgrade
- Installing Micro Focus Net Express on Microsoft Windows
- Managing Micro Focus Net Express Compiler Licenses
- Using the Micro Focus COBOL Compiler on Microsoft Windows

Understanding COBOL

This chapter describes how to compile and link PeopleSoft COBOL batch programs, if necessary.

COBOL is not needed for PeopleSoft PeopleTools because the Process Scheduler is written in C++. In addition, COBOL is not required for PeopleSoft applications that contain no COBOL programs. See My Oracle Support for the details on whether your application requires COBOL.

The chapter includes instructions for the Micro Focus Net Express COBOL compiler.

See Also

"Preparing for Installation," Installing Supporting Applications

PeopleSoft Enterprise Frequently Asked Questions About PeopleSoft and COBOL Compilers, My Oracle Support, (search for the article name)

PeopleSoft Enterprise Frequently Asked Questions About PeopleSoft and the IBM COBOL Compiler, My Oracle Support, (search for the article name)

PeopleTools Certifications - Suggested Fixes COBOL, My Oracle Support, (search for the article name and select the current release)

PeopleTools: Global Technology, "Understanding COBOL in a Unicode Environment"

Prerequisites

Before you attempt to run COBOL from the command line you should do the following:

- Make sure the variable PS_SERVER_CFG points to a valid psprcs.cfg file.

- Make sure %PS_HOME%\bin\server\winx86 is in your path. It should appear before %PS_HOME%\bin\client\winx86 if that also appears in the path.
- Before compiling COBOL, you must obtain and install Perl on the machine used to compile COBOL. Perl is used to perform conversions on COBOL source files. Make sure the Perl installation location is included in the system's PATH environment variable. Contact the Perl vendor for installation and reference documentation.

Task 10A-1: Preparing COBOL for a PeopleTools-only Upgrade

When performing a PeopleTools-only upgrade, if you have COBOL modules, recompile all PeopleSoft PeopleTools and PeopleSoft application COBOL programs, as explained in a later section.

Ensure that the following COBOL runtime files in your client and server bin directories match those of your Micro Focus Net Express installation:

- CBLINTS.DLL
- CBLRTSS.DLL
- CBLVIOS.DLL
- COB32API.DLL

See Recompiling COBOL on Microsoft Windows.

Task 10A-2: Installing Micro Focus Net Express on Microsoft Windows

This section discusses:

- Prerequisites
- Obtaining Installation Files for Micro Focus Net Express from Oracle Software Delivery Cloud
- Installing Micro Focus Net Express Wrap Pack 6
- Installing Micro Focus Net Express Wrap Pack 15

Prerequisites

Micro Focus® Net Express™ 5.1 Wrap Pack 15 is the supported COBOL compiler on Microsoft Windows for the current PeopleSoft PeopleTools release. This Wrap Pack is a product update and does require a previous version of the product to be installed. Micro Focus Net Express 5.1 Wrap Pack 15 can upgrade any of the following releases or any combination of these releases:

- Micro Focus Net Express 5.1 Wrap Pack 6
- Micro Focus Net Express 5.1 Wrap Pack 7
- Micro Focus Net Express 5.1 Wrap Pack 8
- Micro Focus Net Express 5.1 Wrap Pack 9
- Micro Focus Net Express 5.1 Wrap Pack 10
- Micro Focus Net Express 5.1 Wrap Pack 11
- Micro Focus Net Express 5.1 Wrap Pack 12

- Micro Focus Net Express 5.1 Wrap Pack 13
- Micro Focus Net Express 5.1 Wrap Pack 14

If you are running a Wrap Pack prior to Wrap Pack 6 or have no Net Express version installed, install Wrap Pack 6 before installing Wrap Pack 15.

See Installing Micro Focus Net Express Wrap Pack 6.

Check the certification information on My Oracle Support for the supported version for Microsoft Windows operating systems.

Note that Oracle is the exclusive reseller of the Micro Focus COBOL compiler for use with PeopleSoft applications.

See Also

PeopleSoft Enterprise Frequently Asked Questions About PeopleSoft and COBOL Compilers, My Oracle Support, Doc ID 747059.1

Using the Micro Focus COBOL Compiler on Microsoft Windows

Task 10A-2-1: Obtaining Installation Files for Micro Focus Net Express from Oracle Software Delivery Cloud

The Micro Focus Net Express installation files are available on Oracle Software Delivery Cloud. At this point you may have already downloaded the necessary files. This section includes additional information on finding and using the files for Micro Focus Net Express if necessary.

See "Preparing for Installation," Using Oracle Software Delivery Cloud to Obtain Installation Files.

See Oracle Software Delivery Cloud, <https://edelivery.oracle.com>.

To obtain the files for the Micro Focus Net Express installation:

1. Log in to Oracle Software Delivery Cloud at <https://edelivery.oracle.com>.
2. Enter Micro Focus in the type-ahead Product field, and select Micro Focus International Ltd. Net Express COBOL for Windows.
3. Select the link Selected Software.
4. Click Continue.
5. Read the license agreement, select the check box to acknowledge that you accept the agreement, and then click Continue.
6. Click one of the filenames to download an individual zip file, or click Download All to obtain all of the files listed.

The files include software, wrap packs, and documentation. Save the zip files to a temporary directory on your local system. The directory where you save the zip files for both versions is referred to in this documentation as *NE_INSTALL*. You must extract (unzip) each file on the platform for which it is intended. For example, if you download the zip file for Microsoft Windows, you must unzip it on Microsoft Windows to avoid problems.

Task 10A-2-2: Installing Micro Focus Net Express Wrap Pack 6


The following procedure assumes that you saved the installation files from Oracle Software Delivery Cloud in the directory *NE_INSTALL*.

Note. Micro Focus Net Express Wrap Pack 6 is a full product release and does not require a previous version of the product to be installed.

To install Micro Focus Net Express Wrap Pack 6:

1. Double-click *NE_INSTALL/nxp3251060079.exe*.

If a security screen appears, click Run to launch the installer.




Open File - Security Warning for the Micro Focus installation executable

The Install Shield Wizard starts extracting files. This may take a few minutes until the files are extracted, and then the Installation Wizard dialog box appears.


2. Click Next on the welcome window.

The screen includes a button to open a Readme file.



Micro Focus Net Express Installation Wizard Welcome window

3. Read the terms of the License Agreement, select the option to accept the terms, and click Next.




License Agreement window for Micro Focus Express

4. Complete the Customer Information window:
 - a. Enter your name in the User Name field, and enter your Company Name.
In the example shown below, the user name is USER NAME, and the Company Name is ORACLE.
 - b. Leave the Serial Number and W.O. Number fields blank. Oracle does not provide these numbers to you and they are not required.

Note. The message at the top of the window reads "We STRONGLY recommend you enter your Serial Number and Works Order (W.O.) number here. You will need them later to obtain a full license key." The example here leaves these fields blank.


- c. Click Next.



The image shows a Windows installation wizard window titled "Micro Focus Net Express 5.1 - InstallShield Wizard". The window has a blue title bar with a close button. Below the title bar, the text "Customer Information" is displayed in bold. A red message states: "We STRONGLY recommend you enter your Serial Number and Works Order (W.O.) number here to obtain a full license key later." The Micro Focus logo is visible in the top right corner. The main area contains four input fields: "User Name:" with the text "USER NAME", "Company Name:" with the text "ORACLE", "Serial Number:" which is empty, and "W.O. Number:" which is empty. At the bottom left, the text "InstallShield" is visible. At the bottom right, there are three buttons: "< Back", "Next >", and "Cancel".

Customer Information window


5. The Custom Setup window appears as in this example, with all of the options selected initially:



Custom Setup window before selecting features

6. You must clear several features on the Custom Setup window before proceeding.

You can turn off a feature by clicking on the drop-down button beside the feature and selecting the option "X This feature will not be available," as shown in this example:



Custom Setup window displaying selection and deselection options


The Traditional Graphical User Interfaces feature is the only feature required for the PeopleSoft installation. (The Traditional Graphical User Interfaces feature also includes Dialog System and Class Library Files.) Clear the following features:

- Net Express support for .NET

Note. Microsoft .NET framework is not required for compiling and running COBOL applications in PeopleSoft architecture. Neither is .NET required for successful installation of MicroFocus Net Express 5.1.

- Interface Mapping Toolkit
When you clear this feature, the Workflow Capture Server option is automatically cleared also.
- Enterprise Server
- UNIX Option
- XDB Relational Database

7. Verify that your final selection matches this example, with only Traditional Graphical User Interfaces, Dialog System, and Class Library Files, selected:



Custom Setup window with options selected for PeopleSoft applications


8. Highlight Traditional Graphical User Interfaces.

The installation directory is listed below the feature list. If you want to install to another location, click Change. If not, click Next.

This documentation refers to the installation directory as *NE_HOME*. The Micro Focus Net Express 5.1 default installation directory, for 64-bit systems, is:


C:\Program Files (x86)\Micro Focus\Net Express 5.1

9. Click Install.




Micro Focus Net Express Installation window: Ready to Install the Program

The installation status window appears, tracking the installation progress.




Installation status for the Micro Focus Net Express Installation

10. Click Finish.



Installation Wizard Completed window


11. To confirm the installation, select Start, All Programs, Micro Focus Net Express 5.1, Net Express.



Selecting Micro Focus Net Express from the Microsoft Windows Start menu


The Net Express Integrated Development Environment (IDE) appears.

12. On the Micro Focus Management System dialog box, read the information under Current License Status, indicating that there is a 30-day license for the compiler that you installed.



Micro Focus License Management System dialog box

13. Click Help, About Net Express.




Micro Focus Net Express Integrated Development Environment Help menu

14. Verify that the following information is included on the message box that appears:

Net Express 5.1

Version: 5.106.0079



About Micro Focus Net Express window with version number


Task 10A-2-3: Installing Micro Focus Net Express Wrap Pack 15

The following procedure assumes that you saved the installation files from Oracle Software Delivery Cloud in the directory `NE_INSTALL`, and that Micro Focus Net Express Wrap Pack 6 or later is installed.

To update to Micro Focus Net Express Wrap Pack 15:

1. Double-click *NE_INSTALL\nxp3251150025.msp*.


If a security screen appears, as in this example, click Open to launch the installer.



Open File - Security Warning dialog box


A Welcome window appears.

2. Click Update to continue, as in this example:




Welcome to the Micro Focus Net Express 5.1 WrapPack #15 window

You see a window indicating the progress of the installation.



Micro Focus Net Express 5.1 Installation Wizard progress indicator

3. After the installation is complete, click Finish on the completion window, as in this example:




Installation Wizard Completed window

4. To verify the installation, select Start, All Programs, Micro Focus Net Express 5.1, Net Express.
Alternatively, you can run *NE_HOME*\Base\Bin\MFNETX.EXE, where *NE_HOME* refers to the directory where you installed Micro Focus Net Express, such as C:\Program Files\Micro Focus.

The Micro Focus Net Express 5.1 Integrated Development Environment (IDE) opens.

5. On the Micro Focus License Management System dialog box, read the information under Current License Status.

In this example, the current license status indicates 29 days remaining on the license. Click OK.



Micro Focus License Management System dialog box


6. Click Continue on the Welcome to Micro Focus Net Express window.

7. Select Help, About Net Express.

Verify that the following information is included on the message box that appears:

Net Express 5.1

Version 5.115.0025



About Micro Focus Net Express 5.1 message box

Task 10A-3: Managing Micro Focus Net Express Compiler Licenses

This section discusses:

- Understanding Micro Focus Net Express Compiler Licenses
- Configuring a Full License with the License Server
- Configuring a Timed License with the License Server
- Revoking the License Using the License Management System
- Revoking the License by Removing the Installation

Understanding Micro Focus Net Express Compiler Licenses

The Micro Focus Net Express 5.1 Wrap Pack 15 compiler can be licensed with a Micro Focus License Server or with the Request Key/Response Key mechanism. This section discusses the License Server method, which Oracle recommends because it is more flexible and licensing is immediate. For more details, see the Micro Focus documentation.

There are two types of Micro Focus Net Express licenses. Here is a brief comparison:

- Timed License
 - Timed Licenses expire after the specified duration and can be renewed over the network.
 - Timed Licenses are the default given by the license server.
 - There are two types of Timed Licenses; one is valid for seven days, and other for one day.
- Full License
 - Full Licenses do not expire.
 - The user can request and revoke Full Licenses using the License Management System.

It is a good idea to use Timed Licenses, unless you have a compelling demand. Mostly developers who work with COBOL on a daily basis should use a Full License. If you require COBOL for a few compiles, and only for some days, use a Timed License. When the Timed License expires, you can renew it again.


Task 10A-3-1: Configuring a Full License with the License Server

To configure a Full License for permanent use:

1. Select Start, All Programs, Micro Focus Net Express 5.1, Configuration, License Management System.


Note. Alternatively, run `NE_HOME\Bin\protcfg.exe`, where `NE_HOME` is the directory where you installed Micro Focus Net Express.

2. Select the option Use Network Licensing, and click Connection Wizard, as shown in this example:




MICRO FOCUS License Management System Configuration window

3. Click Next on the License Server Connection Wizard window, shown in this example:



License Server Connection Wizard window


4. Enter information for the server location, and then click Next.



License Server Connection Wizard - Server Location window

- Server Name—Enter the name of the license server; for example, server.example.com.
- Virtual Directory; for example, /LS4.
- Port Number—The default is 80, as shown in the example.
Select a port that is not in use by another application.

5. You see a message saying the wizard found the server, as in this example.
Click Next.




License Server Connection Wizard - Searching window

6. Enter your group ID, which is COBOL_GROUP_1 in this example, and 1 for the number of days before you have to renew the license.


Note. Although you enter one day here, you complete a step later that requests permanent license status.

Click Next.




License Server Connection Wizard - Configuration window

7. Click Finish to exit the wizard, as shown in this example:



License Server Connection Wizard - The End window


8. In the details list on the MICRO FOCUS License Management System Configuration dialog box, select the check box for Net Express, and then click Request Full License, as shown in this example:



MICRO FOCUS License Management System Configuration window


9. Click Yes to confirm that you want to request a full license, as shown in this example.

The warning message says that requesting a full license permanently removes a license from the license server.




Warning message box when requesting a Full License

10. Click OK on the License Information dialog box.



License Management System Configuration - License Information window

11. Verify that the License Status for Net Express has changed to Full License, as shown in this example, and click Close.



MICRO FOCUS License Management System Configuration window with Full License status


Task 10A-3-2: Configuring a Timed License with the License Server

To configure a Timed License for temporary use:

1. Select Start, All Programs, Micro Focus Net Express 5.1, Configuration, License Management System.


Note. Alternatively, run `NE_HOME\Bin\protcfg.exe`, where `NE_HOME` is the directory where you installed Micro Focus Net Express.

2. Select the option Use Network Licensing, and click Connection Wizard, as shown in this example:




MICRO FOCUS License Management System Configuration window

3. Click Next on the License Server Connection Wizard window, shown in this example:



License Server Connection Wizard window

4. Enter information for the server location, and then click Next.



License Server Connection Wizard - Server Location


- Server Name—Enter the name of the license server; for example, server.example.com.
- Virtual Directory; for example, /LS4.
- Port Number—The default is 80, as shown in the example.

Select a port that is not in use by another application.

5. You see a message saying the wizard found the server.
Click Next.

6. Enter your group ID, which is COBOL_TEMP_1 in this example, and specify the number of days before you have to renew the license, which is 1 (one) day in this example.

Click Next.




License Server Connection Wizard - Configuration window

7. Click Finish to exit the wizard.
8. In the details list on the MICRO FOCUS License Management System Configuration dialog box, select the check box for Net Express, and then click Request 1-day License.


9. Click Yes to confirm that you want to request a timed (temporary) license, as shown in this example.

The warning message says that the license will run out in one day. When you run the product after the license has expired, the License Server will be contacted automatically to renew the license for one day.




Warning message box when requesting a timed license

10. Click OK on the License Information message box.



License Management System Configuration - License Information window

11. Verify that the license status has changed to "1 day left on this license," as shown in this example, and click Close.



MICRO FOCUS License Management System Configuration window showing Timed License

Task 10A-3-3: Revoking the License Using the License Management System


Revoking (deallocating) the compiler license returns it to the license pool, and makes it available for re-use, either by you or another user. This section describes how to use the Micro Focus License Management System to revoke a compiler license. For information on revoking the license by completely removing the Micro Focus Net Express installation, see the following section.

See Revoking the License by Removing the Installation.

To revoke a Full License using the Micro Focus License Management System:

1. Select Start, All Programs, Micro Focus Net Express 5.1, Configuration, License Management System.
2. Select the check box for Net Express under Product in the details list, and click Revoke Full License.
3. Click Yes on the warning message box to confirm that you want to revoke a full license, as shown in this example.


The warning message says that revoking a full license means that you will no longer have a valid license.



Warning message box on Revoking a Full License

4. Click OK.

The License Information message box says that the Net Express license has been revoked.



License Management System Configuration - License Information

5. Verify that the license status has changed to "license has expired" and click Close.


Task 10A-3-4: Revoking the License by Removing the Installation

Revoking (deallocating) the compiler license returns it to the license pool, and makes it available for re-use, either by you or another user. This section describes how to revoke the license by completely removing the Micro Focus Net Express 5.1 installation. For information on using the Micro Focus License Management System to revoke a compiler license, see the previous section.

See Revoking the License Using the License Management System.


To remove the installation and revoke the license:

1. Select Start, All Programs, All Control Panel Items, Programs and Features.
2. Highlight Micro Focus Net Express 5.1 in the list of programs.
3. Right-click and select Uninstall, as shown in this example:



Microsoft Windows Control Panel Programs and Features

4. Click Revoke on the Uninstalling Product Warning message box, as shown in this example:



Uninstalling Product Warning message box

The MICRO FOCUS License Management System Configuration window appears.

5. Follow the instructions in the previous section to revoke the license.
See Revoking the License Using the License Management System.
6. When the process to revoke the license is complete, close the MICRO FOCUS License Management System Configuration window, and complete the process to remove Micro Focus Net Express 5.1.

Task 10A-4: Using the Micro Focus COBOL Compiler on Microsoft Windows

This section discusses:

- Understanding COBOL Compilation
- Compiling COBOL on Microsoft Windows with a PS_HOME Setup
- Compiling COBOL on Microsoft Windows with a PS_APP_HOME Setup
- Compiling COBOL on Microsoft Windows with a PS_CUST_HOME Setup
- Recompiling COBOL on Microsoft Windows
- Setting Up the Micro Focus Net Express Runtime

- Defining the GNT and INT Files
- Distributing COBOL Binaries

Understanding COBOL Compilation

With PeopleSoft PeopleTools 8.50 and higher, your COBOL always needs to be compiled on Microsoft Windows. (This is a change from previous versions of PeopleSoft PeopleTools, which delivered compiled COBOL for Microsoft Windows.) This section assumes that you are carrying out the compile process from your file server. (The COBOL compiler itself does not need to be on the file server, as long as the user can write to the file server and can link to the src and bin directories.) The recommended approach for the PeopleSoft installation is to use CBLBLD.BAT to compile all your COBOL source files at once. Another alternative is CBLMAKE.BAT, which you can use to compile selected COBOL files.

The way that you set up your installation environment determines how you compile COBOL. This section includes different procedures for the different installation environments, as follows:

- *PS_HOME Setup*

If you installed the PeopleSoft Application software to a *PS_APP_HOME* location that is the same as the *PS_HOME* location where you installed the PeopleSoft PeopleTools software, follow the instructions in these sections:

- Compiling COBOL on Microsoft Windows with a *PS_HOME* Setup
- Defining the GNT and INT Files

- *PS_APP_HOME Setup*

As described earlier, for PeopleSoft PeopleTools 8.52 and later, you have the option to install the PeopleSoft Application software to a location outside *PS_HOME*. If the *PS_APP_HOME* environment variable is defined and is different from *PS_HOME*, the COBOL build scripts behave differently under certain build options. There are also some new build options under certain environments which would be recognized if *PS_APP_HOME* is defined.

If you installed the PeopleSoft Application software to a *PS_APP_HOME* location that is different from the *PS_HOME* location where you installed the PeopleSoft PeopleTools software, follow the instructions in these sections:

- Compiling COBOL on Microsoft Windows with a *PS_APP_HOME* Setup
- Defining the GNT and INT Files

- *PS_CUST_HOME Setup*

For PeopleSoft PeopleTools 8.53 and later, you have the option to place customized COBOL baseline sources into a location referenced by the environment variable *PS_CUST_HOME*.

The *PS_CUST_HOME* directory structure must replicate that of *PS_HOME* or *PS_APP_HOME*; that is, any COBOL source file that is customized should be placed in the same relative path as was present in the original location.

If your environment includes customized files in a *PS_CUST_HOME* directory, follow the instructions in these sections:

- Compiling COBOL on Microsoft Windows with a *PS_CUST_HOME* Setup
- Defining the GNT and INT Files

For those systems on which you only need to run COBOL, but do not need to compile it, you must install and license the Micro Focus Net Express Runtime.

See Setting Up the Micro Focus Net Express Runtime.

Make certain to check whether you need to apply any late-breaking patches.

See My Oracle Support, Patches & Updates.

See Also

"Preparing for Installation," Defining Installation Locations.

Task 10A-4-1: Compiling COBOL on Microsoft Windows with a PS_HOME Setup

This section discusses:

- Prerequisites
- Compiling with CBLBLD.BAT with a PS_HOME Setup
- Compiling with CBLMAKE.BAT with a PS_HOME Setup

Prerequisites

This section assumes that you installed both PeopleSoft PeopleTools and PeopleSoft Application software to *PS_HOME*, and that you have not set *PS_CUST_HOME*.

Compiling with CBLBLD.BAT with a PS_HOME Setup

To compile COBOL with CBLBLD.BAT:

1. Set up two environment variables, %PS_HOME% and %COBROOT%, on the machine from which you'll compile COBOL. (This should be either your file server or a machine that has access to your file server.)

You can do this from a command prompt window. This table gives the environment variables and their purposes.

Environment Variable	Purpose
PS_HOME	PeopleSoft home directory—that is, the drive letter and high-level PeopleSoft directory where you installed PeopleTools and the application.
COBROOT	Drive letter and root directory of the COBOL compiler.

For example, you could enter the following in the DOS command prompt:

```
set PS_HOME=C:\HR92
set COBROOT="C:\Program Files\Micro Focus\Net Express 5.1\base"
```

2. Open a command prompt window if you do not have one open already, and change directories to *PS_HOME* setup.
3. Execute CBLBLD.BAT as follows:

```
cblbld <compile drive> <compile directory>
```

In this command, *<compile drive>* is the drive where the compile takes place, and *<compile directory>* is the temp directory where the compile takes place.

The CBLBLD.BAT file will create the compile directory for you if it does not already exist.

Note. Make sure to include a space between the *<compile drive>* and *<compile directory>* parameters; they are treated as two different parameters within the CBLBLD.BAT batch program. Also ensure that you have write permission to *<compile drive>* and *<compile directory>* as the compile process will take place there.

For example, the following command will take the COBOL source from *PS_HOME\src\cbl* and do the compile process under *c:\temp\compile*:

```
cblbld c: \temp\compile
```

Make note of the information that is displayed on the screen while the process is running; it provides the locations of important files that you will need to examine.

4. After you have successfully compiled your source code, all of the executables should have been placed in your *<PS_HOME>\CBLBIN<X>* directory (this directory will be named CBLBINA or CBLBINU, depending on whether you are using ANSI or Unicode). Make sure that all of the files were copied correctly to this directory.
5. If the files were copied correctly, you can delete the entire temporary compile directory to free space on your disk drive.

Note. You may want to keep the files in the compile directory for testing purposes. Make sure that you have enough space on the drive where *<compile directory>* is located. Estimate about three times the amount in the *<PS_HOME>\CBLBIN<X>* directory.

Note. If you chose the Unicode option while running the PeopleSoft Installer, the file UNICODE.CFG was created in the setup directory. UNICODE.CFG automatically triggers the batch file CBL2UNI.BAT when you run CBLBLD.BAT. Another batch file, CBLRTCPY.BAT, copies four DLLs (CBLINTS.DLL, CBLRTSS.DLL, CBLVIOS.DLL, COB32API.DLL) from the Microfocus compiler directory (identified by %COBROOT% setting) into the appropriate CBLBIN directory (CBLBINA or CBLBINU) when you run CBLBLD. These files are needed for COBOL to run; they can reside anywhere as long as they are in the path. You can run either of these BAT files independently from the command line (they reside in *PS_HOME\setup*). For CBLRTCPY.BAT you need to specify a target directory.

Compiling with CBLMAKE.BAT with a PS_HOME Setup

CBLBLD.BAT compiles all your COBOL source files at once, which can take a lot of time. CBLMAKE.BAT, in contrast, lets you employ one or more parameters to compile a specific COBOL source file or a selected group of COBOL source files. Unlike CBLBLD.BAT, however, CBLMAKE.BAT does not automatically trigger the batch file CBL2UNI.BAT or CBLRTCPY.BAT.

Here is the basic syntax for CBLMAKE.BAT:

```
CBLMAKE.BAT [] [ALL] [wildcard filename[ALL]] [wildcard filename | =>
wildcard=>
filename without extension[INT | GNT | EXE]] [LIST]
```

Note. The switches are well documented in the CBLMAKE.BAT file in the form of comments.

Note. If the change in the COBOL source is a copy member, you must compile all of the COBOL programs using CBLBLD.BAT. You know it is a copy member when the third letter in the file name is a C, as in PTC SQLRT.CBL.

The following table describes the various options for CBLMAKE.BAT.

Option	Purpose
Cblmake	Compiles all source
Cblmake all	Compiles all source
Cblmake PT*	Compiles all source files that start with PT
Cblmake PT* ALL	Compiles all source files that start with PT
Cblmake PT* INT	Generates INT files for all source files that start with PT
Cblmake PT* GNT	Generates GNT files for all source files that start with PT
Cblmake PT* EXE	Generates EXE files for all source files that start with PT
Cblmake PTPDBTST INT	Generates PTPDBTST.INT file
Cblmake PTPDBTST INT LIST	Generates PTPDBTST.INT and source listing file
Cblmake PTPDBTST GNT	Generates PTPDBTST.GNT file
Cblmake PTPDBTST EXE	Generates PTPDBTST.EXE file

The LIST option creates a source listing file under *<compile directory>\<filename>.lis*. The LIST option is useful when the compile fails during the debugging phase. The source listing files show exactly where an error occurred. This option is not recommended when the program compiles successfully because the .LIS files can grow to be quite large.

Note. By default, when the program fails to compile, the system will generate a .LIS file.

To compile with CBLMAKE.BAT:

1. Verify that the %PS_HOME% and %COBROOT% environment variables are set up correctly.
2. Open a command prompt window.
3. Make sure the compile directory exists; it may already exist if you've run CBLBLD.BAT. If it does exist, remove any files residing there—just as a safeguard. If it does not exist, you need to create it.

Note. Make sure you have write permission to *<compile directory>* as the compile process will take place there.

4. Change to the *PS_HOME\setup* directory.
5. If the installation is Unicode, run CBL2UNI (with no parameters).
6. Execute the following command to copy all the COBOL source files from the *PS_HOME* directory to the compile directory:

```
cblsrc <source directory>    <compile directory>
```

where *<source directory>* is the drive and directory where the source resides (it should be the same as *PS_HOME*), and *<compile directory>* is the drive and directory to which the source files will be copied.

For example, the following command will take the COBOL source from *PS_HOME* and copy all the necessary files to the location where the compile process will take place.

```
cblsrc PS_HOME c:\temp\compile
```

If the COBOL source that will be compiled is different from the one under *PS_HOME*, copy that COBOL source to *<compile directory>*.

Note. The compile in the next step will generate a GNT file unless the exception file, CBLINT.XX already exists (the XX represents the Product ID). CBLINT.XX contains the list of files that need to be compiled to the INT file. Make sure the intended CBLINT.XX is located under *<compile directory>* before executing CBLMAKE.

7. After CBLSRC completes, change directories to the compile directory, and run CBLMAKE.BAT, using the basic syntax as well as the CBLMAKE table shown earlier as your guide.
8. After CBLMAKE.BAT completes, copy the EXE, GNT, or INT files to the appropriate *PS_HOME\CBLBINX* directory (CBLBINA or CBLBINU).

```
copy *.exe PS_HOME\cblbina
copy *.gnt PS_HOME\cblbina
copy *.int PS_HOME\cblbina
```

Note. You have to copy these files to the appropriate cblbin directory manually when you use CBLMAKE; they are not copied automatically, as when you use CBLBLD.

Task 10A-4-2: Compiling COBOL on Microsoft Windows with a PS_APP_HOME Setup

This section discusses:

- Prerequisites
- Compiling with CBLBLD.BAT with a PS_APP_HOME Setup
- Compiling with CBLMAKE.BAT with a PS_APP_HOME Setup

Prerequisites

This section assumes that you installed PeopleSoft application software to a *PS_APP_HOME* directory that is different from the *PS_HOME* directory where you installed PeopleSoft PeopleTools. It also assumes that there is no separate *PS_CUST_HOME* directory with customized COBOL source files.

Compiling with CBLBLD.BAT with a PS_APP_HOME Setup

The usage for running CBLBLD.BAT is:

```
cblbld <compile drive> <compile directory> [BUILD_option] [BUILD_home]
```

Substitute the appropriate values as follows:

- *<compile drive>*
Enter the drive letter for the drive containing the directory where the compile takes place.
- *<compile directory>*

Enter the directory where the compile takes place. Be sure to include a space between <compile drive> and <compile directory>.

- **BUILD_option**

The allowed values are nothing (blank), ASCII or Unicode.

BUILD_option refers to the encoding scheme of your PeopleSoft installation. This parameter is optional.

- **BUILD_home**

The allowed values are nothing (blank), PS_HOME or PS_APP_HOME.

Note. The values PS_HOME and PS_APP_HOME are case-insensitive.

BUILD_home refers to the directory from which the COBOL source files will be compiled.

This parameter is optional.

- If the option is PS_HOME, the COBOL source files placed under %PS_HOME%\src\cbl will be compiled.
- If the option is PS_APP_HOME, the COBOL source files placed under %PS_APP_HOME%\src\cbl will be compiled.
- If the option is blank, the COBOL source files under %PS_HOME%\src\cbl and COBOL source files under %PS_APP_HOME%\src\cbl will be compiled one after the other.

To compile COBOL sources on Microsoft Windows:

1. In a command prompt, set the environment variables described in this table:

Environment Variable	Purpose
PS_HOME	PeopleSoft PeopleTools home directory—that is, the drive letter and high-level directory where you installed PeopleSoft PeopleTools.
COBROOT	Drive letter and root directory of the COBOL compiler.
PS_APP_HOME	PeopleSoft Application home directory—that is, the drive letter and high-level directory where you installed the PeopleSoft Application software.

For example:

```
set PS_HOME=C:\PTcompile
set COBROOT="C:\Program Files\Micro Focus\Net Express 5.1\base"
set PS_APP_HOME=C:\HRcompile
```

2. Change directory to *PS_HOME*\setup:

```
cd %PS_HOME%\setup
```

3. Run CBLBLD.BAT, using one of these methods:

- To compile all the COBOL source files under your PeopleSoft application, that is, all PeopleSoft PeopleTools source files and all PeopleSoft Application source files, run this command:

```
cblbld <compile drive> <compile directory>
```

For example:

```
cblbld c: \temp\PTcompile
```

- To compile only PeopleSoft PeopleTools COBOL source files, run this command:

```
cblbld <compile drive> <compile directory> PS_HOME
```

For example:

```
cblbld c: \temp\PTcompile PS_HOME
```

- To compile only PeopleSoft Application COBOL source files, run this command:

```
cblbld <compile drive> <compile directory> PS_APP_HOME
```

For example:

```
cblbld c: \temp\HRcompile PS_APP_HOME
```

PeopleSoft PeopleTools COBOL compiled executables will be placed under the `<PS_HOME>\CBLBIN<X>` directory. PeopleSoft Application COBOL compiled executables will be placed under the `<PS_APP_HOME>\CBLBIN<X>` directory. CBLBIN<X> will be one of the following:

- CBLBINA if you are using ANSI encoding scheme
- CBLBINU if you are using Unicode encoding scheme

Compiling with CBLMAKE.BAT with a PS_APP_HOME Setup

CBLBLD.BAT compiles all your COBOL source files at once, which can take a lot of time. CBLMAKE.BAT, in contrast, lets you employ one or more parameters to compile a specific COBOL source file or a selected group of COBOL source files. The procedure is slightly different depending upon whether the file that you want to compile is a PeopleSoft Application or PeopleSoft PeopleTools COBOL file. Both procedures are covered in this section.

Note. The options for CBLMAKE.BAT are defined in a table in the previous section Compiling with CBLMAKE.BAT with a *PS_HOME* Setup.

To compile a PeopleSoft Application COBOL file with CBLMAKE.BAT:

1. Open a command prompt window.
2. Verify that the PS_HOME, COBROOT, and PS_APP_HOME environment variables are set, as previously defined.

See Compiling with CBLBLD.BAT with a PS_APP_HOME Setup.

3. Verify that the environment variable PS_compile_apps is set, as follows:

```
set PS_compile_apps=Y
```

Important! This variable setting is required for individual file compilation with CBLMAKE.BAT.

4. Make sure the compile directory, `<compile directory>`, exists, and that you have write permission to it. This directory may already exist if you have run CBLBLD.BAT before. If it does exist, remove any files residing there—just as a safeguard. If it does not exist, you need to create it.
5. Change to the `PS_HOME\setup` directory.
6. If the installation is Unicode, run CBL2UNI (with no parameters).
7. Execute the following command to copy all the COBOL source files from the `PS_APP_HOME` directory to the compile directory:

```
cblsrc <source directory>    <compile directory>
```

Here <source directory> is the drive and directory where the source resides (it should be the same as *PS_APP_HOME*), and <compile directory> is the drive and directory to which the source files will be copied.

For example, the following command will take the COBOL source from *PS_APP_HOME* and copy all the necessary files to the location where the compile process will take place, *c:\temp\HRcompile* in this example:

```
cblsrc %PS_APP_HOME% c:\temp\HRcompile
```

Note. The compile in the next step will generate a GNT file unless the exception file, *CBLINT.XX* already exists (the *XX* represents the Product ID). *CBLINT.XX* contains the list of files that need to be compiled to the INT file. Make sure the intended *CBLINT.XX* is located under <compile directory> before executing *CBLMAKE*.

8. After *CBLSRC* completes, change directories to the compile directory, and run *CBLMAKE.BAT*, using the basic syntax as well as the *CBLMAKE* table shown earlier as your guide.

For example, to compile a file named *GPPDPRUN*, run this command:

```
cblmake GPPDPRUN
```

9. After *CBLMAKE.BAT* completes, copy the EXE, GNT, or INT files to the appropriate <*PS_APP_HOME*>\CBLBIN<*X*> directory (CBLBINA for ANSI or CBLBINU for Unicode).

These examples use the ANSI encoding:

```
copy *.exe %PS_APP_HOME%\cblbina
copy *.gnt %PS_APP_HOME%\cblbina
copy *.int %PS_APP_HOME%\cblbina
```

Note. You have to copy these files to the appropriate cblbin directory manually when you use *CBLMAKE*; they are not copied automatically, as when you use *CBLBLD*.

10. Verify that the compiler runtime files (*CBLINTS.DLL*, *CBLRTSM.DLL*, *CBLRTSS.DLL*, *CBLVIOM.DLL*, *CBLVIOS.DLL*, *COB32API.dll*, *MFLANGDF.lbr*) are present in the <*PS_APP_HOME*>\CBLBIN<*X*> directory.

If they are not present, then you will have to run *%PS_HOME%\setup\cblrtcpy.bat* as follows:

```
cblrtcpy %PS_APP_HOME%\cblbina
```

The procedure to compile a PeopleSoft PeopleTools COBOL file with *CBLMAKE.BAT* is similar, but the environment variable *PS_compile_apps* must *not* be set.

1. Open a command prompt window.
2. Verify that the *PS_HOME*, *COBROOT*, and *PS_APP_HOME* environment variables are set, as previously defined.

See Compiling with *CBLBLD.BAT* with a *PS_APP_HOME* Setup.

3. Verify that the environment variable *PS_compile_apps* is *not* set, as follows:

```
set PS_compile_apps=
```

Important! Unsetting this environment variable is required for individual file compilation with *CBLMAKE.BAT* for PeopleSoft PeopleTools files.

4. Make sure the compile directory, <compile directory>, exists, and that you have write permission to it.

This directory may already exist if you have run CBLBLD.BAT before. If it does exist, remove any files residing there—just as a safeguard. If it does not exist, you need to create it.

5. Change to the *PS_HOME*\setup directory.
6. If the installation is Unicode, run CBL2UNI (with no parameters).
7. Execute the following command to copy all the COBOL source files from the *PS_HOME* directory to the compile directory:

```
cblsrc <source directory>    <compile directory>
```

where *<source directory>* is the drive and directory where the source resides (it should be the same as *PS_HOME*), and *<compile directory>* is the drive and directory to which the source files will be copied.

For example, the following command will take the COBOL source from *PS_HOME* and copy all the necessary files to the location where the compile process will take place, c:\temp\PTcompile in this example:

```
cblsrc %PS_HOME% c:\temp\PTcompile
```

8. After CBLSRC completes, change directories to the compile directory, and run CBLMAKE.BAT, using the basic syntax as well as the CBLMAKE table shown earlier as your guide.

For example, to compile a file named PTPDBTST, run this command:

```
cblmake PTPDBTST
```

9. After CBLMAKE.BAT completes, copy the EXE, GNT, or INT files to the appropriate *<PS_HOME>*\CBLBIN<X> directory (CBLBINA for ANSI or CBLBINU for Unicode).

These examples use the ANSI encoding:

```
copy *.exe %PS_HOME%\cblbina
copy *.gnt %PS_HOME%\cblbina
copy *.int %PS_HOME%\cblbina
```

Note. You have to copy these files to the appropriate cblbin directory manually when you use CBLMAKE; they are not copied automatically, as when you use CBLBLD.

10. Verify that the compiler runtime files (CBLINTS.DLL, CBLRTSM.DLL, CBLRTSS.DLL, CBLVIOM.DLL, CBLVIOS.DLL, COB32API.dll, MFLANGDF.lbr) are present in the *<PS_HOME>*\CBLBIN<X> directory.

If they are not present, then you will have to run %PS_HOME%\setup\cblrtcpy.bat as follows:

```
cblrtcpy %PS_HOME%\cblbina
```

Note. If you plan to use cblmake.bat to compile a single (or a set) of PeopleSoft PeopleTools or PeopleSoft Application COBOL program at the same time, it would be a good idea to use two different command prompts and two different compile directories—one for PeopleSoft PeopleTools COBOL programs and the other for the PeopleSoft Application COBOL programs. This avoids setting and unsetting the PS_compile_apps environment variable.

Task 10A-4-3: Compiling COBOL on Microsoft Windows with a PS_CUST_HOME Setup

This section discusses:

- Prerequisites
- Compiling with CBLBLD.BAT with a PS_CUST_HOME Setup

- Compiling with CBLMAKE.BAT with a PS_CUST_HOME Setup

Prerequisites

This section assumes that you installed PeopleSoft application software to a *PS_APP_HOME* directory that is different from the *PS_HOME* directory where you installed PeopleSoft PeopleTools. It also assumes that you have set up a *PS_CUST_HOME* environment variable for customized COBOL source files.

Compiling with CBLBLD.BAT with a PS_CUST_HOME Setup

The usage for running CBLBLD.BAT is:

```
cblbld <compile drive> <compile directory> [BUILD_option] [BUILD_home]
```

Substitute the appropriate values as follows:

- **<compile drive>**
Enter the drive letter for the drive containing the directory where the compile takes place.
- **<compile directory>**
Enter the directory where the compile takes place. Be sure to include a space between <compile drive> and <compile directory>.
- **BUILD_option**
The allowed values are nothing (blank), ASCII or Unicode.
BUILD_option refers to the encoding scheme of your PeopleSoft installation. This parameter is optional.
- **BUILD_home**
The allowed values are nothing (blank), PS_HOME, PS_APP_HOME, or PS_CUST_HOME.

Note. The values PS_HOME, PS_APP_HOME, and PS_CUST_HOME are case-insensitive.

BUILD_home refers to the directory from which the COBOL source files will be compiled.

This parameter is optional.

- If the option is PS_HOME, the COBOL source files placed under %PS_HOME%\src\cbl will be compiled.
- If the option is PS_APP_HOME, the COBOL source files placed under %PS_APP_HOME%\src\cbl will be compiled.
- If the option is PS_CUST_HOME, the COBOL source files placed under %PS_CUST_HOME%\src\cbl will be compiled.
- If the option is blank, the COBOL source files under %PS_HOME%\src\cbl, under %PS_APP_HOME%\src\cbl (if PS_APP_HOME is different from PS_HOME), and under %PS_CUST_HOME%\src\cbl will be compiled one after the other.

To compile COBOL sources on Microsoft Windows:

1. In a command prompt, set the environment variables described in this table:

Environment Variable	Purpose
PS_HOME	PeopleSoft PeopleTools home directory—that is, the drive letter and high-level directory where you installed PeopleSoft PeopleTools.
PS_APP_HOME (if different from PS_HOME)	PeopleSoft Application home directory—that is, the drive letter and high-level directory where you installed the PeopleSoft Application software.
PS_CUST_HOME	PeopleSoft Application customized home directory—that is, the drive letter and high-level directory containing your customized PeopleSoft COBOL programs.
COBROOT	Drive letter and root directory of the COBOL compiler.

For example:

```
set PS_HOME=C:\PTcompile
set COBROOT="C:\Program Files\Micro Focus\Net Express 5.1\base"
set PS_CUST_HOME=C:\CUSTcompile

set PS_APP_HOME=C:\HRcompile
```

2. Change directory to *PS_HOME*\setup:

```
cd %PS_HOME%\setup
```

3. Run CBLBLD.BAT, using one of these methods:

- To compile all the COBOL source files under your PeopleSoft application, that is, all PeopleSoft PeopleTools source files, all PeopleSoft Application source files, and all customized PeopleSoft source files, run this command:

```
cblbld <compile drive> <compile directory>
```

For example:

```
cblbld c: \temp\PTcompile
```

- To compile only PeopleSoft PeopleTools and PeopleSoft Application COBOL source files, run this command:

```
cblbld <compile drive> <compile directory> PS_HOME
```

For example:

```
cblbld c: \temp\PTcompile PS_HOME
```

- To compile only customized PeopleSoft Application or PeopleSoft PeopleTools COBOL source files, run this command:

```
cblbld <compile drive> <compile directory> PS_CUST_HOME
```

For example:

```
cblbld c: \temp\CUSTcompile PS_CUST_HOME
```

Delivered (that is, non-customized) PeopleSoft PeopleTools and PeopleSoft Application COBOL compiled executables will be placed under the `<PS_HOME>\CBLBIN<X>` directory. Customized PeopleSoft Application or PeopleSoft PeopleTools COBOL compiled executables will be placed under the `<PS_CUST_HOME>\CBLBIN<X>` directory. CBLBIN<X> will be one of the following:

- CBLBINA if you are using ANSI encoding scheme
- CBLBINU if you are using Unicode encoding scheme

Compiling with CBLMAKE.BAT with a PS_CUST_HOME Setup

CBLBLD.BAT compiles all your COBOL source files at once, which can take a lot of time. CBLMAKE.BAT, in contrast, lets you employ one or more parameters to compile a specific COBOL source file or a selected group of COBOL files. The procedure is slightly different depending upon whether the file that you want to compile is a PeopleSoft Application, PeopleSoft PeopleTools, or customized COBOL source file. Both procedures are covered in this section.

Note. The options for CBLMAKE.BAT are defined in a table in the previous section Compiling with CBLMAKE.BAT with a *PS_HOME* Setup.

To compile a customized COBOL file with CBLMAKE.BAT:

1. Open a command prompt window.
2. Verify that the PS_HOME, COBROOT, PS_APP_HOME (if not the same as PS_HOME), and PS_CUST_HOME environment variables are set, as previously defined.

See Compiling with CBLBLD.BAT with a PS_CUST_HOME Setup.

3. Verify that the environment variable PS_compile_cust is set, as follows:

```
set PS_compile_cust=Y
```

Important! This variable setting is required for individual file compilation with CBLMAKE.BAT.

4. Ensure that the compile directory, *<compile directory>*, exists, and that you have write permission to it. This directory may already exist if you have run CBLBLD.BAT before. If it does exist, remove any files residing there—just as a safeguard. If it does not exist, you need to create it.
5. Change to the *PS_HOME\setup* directory.
6. If the installation is Unicode, run CBL2UNI (with no parameters).
7. Execute the following command to copy all the COBOL source files from the *PS_CUST_HOME* directory to the compile directory:

```
cblsrc <source directory> <compile directory>
```

Here *<source directory>* is the drive and directory where the source resides (it should be the same as *PS_CUST_HOME*), and *<compile directory>* is the drive and directory to which the source files will be copied.

For example, the following command will take the COBOL source files from *PS_CUST_HOME* and copy all the necessary files to the location where the compile process will take place, *c:\temp\CUSTcompile* in this example:

```
cblsrc %PS_CUST_HOME% c:\temp\CUSTcompile
```

Note. The compile in the next step will generate a GNT file unless the exception file, CBLINT.*XX* already exists (the *XX* represents the Product ID). CBLINT.*XX* contains the list of files that need to be compiled to the INT file. Make sure the intended CBLINT.*XX* is located under *<compile directory>* before executing CBLMAKE.

8. After CBLSRC completes, change directories to the compile directory, and run CBLMAKE.BAT, using the basic syntax as well as the CBLMAKE table shown earlier as your guide.

For example, to compile a file named GPPDPRUN, run this command:

```
cblmake GPPDPRUN
```

9. After CBLMAKE.BAT completes, copy the EXE, GNT, or INT files to the appropriate *<PS_CUST_HOME>\CBLBIN<X>* directory (CBLBINA for ANSI or CBLBINU for Unicode).

These examples use the ANSI encoding:

```
copy *.exe %PS_CUST_HOME%\cblbina
copy *.gnt %PS_CUST_HOME%\cblbina
copy *.int %PS_CUST_HOME%\cblbina
```

Note. You have to copy these files to the appropriate cblbin directory manually when you use CBLMAKE; they are not copied automatically, as when you use CBLBLD.

10. Verify that the compiler runtime files (CBLINTS.DLL, CBLRTSM.DLL, CBLRTSS.DLL, CBLVIOM.DLL, CBLVIOS.DLL, COB32API.DLL, MFLANGDF.lbr) are present in the *<PS_CUST_HOME>\CBLBIN<X>* directory.

If they are not present, then you will have to run %PS_HOME%\setup\cblrtcpy.bat as follows:

```
cblrtcpy %PS_CUST_HOME%\cblbina
```

The procedure to compile a PeopleSoft PeopleTools COBOL file with CBLMAKE.BAT is similar, but the environment variable PS_compile_cust must *not* be set.

1. Open a command prompt window.
2. Verify that the PS_HOME, COBROOT, and PS_APP_HOME environment variables are set, as previously defined.

See Compiling with CBLBLD.BAT with a PS_APP_HOME Setup.

3. Verify that the environment variable PS_compile_cust is *not* set, as follows:

```
set PS_compile_cust=
```

Important! Unsetting this environment variable is required for individual file compilation with CBLMAKE.BAT for PeopleSoft PeopleTools files.

4. Make sure the compile directory, *<compile directory>*, exists, and that you have write permission to it. This directory may already exist if you have run CBLBLD.BAT before. If it does exist, remove any files residing there—just as a safeguard. If it does not exist, you need to create it.
5. Change to the *PS_HOME\setup* directory.
6. If the installation is Unicode, run CBL2UNI (with no parameters).
7. Execute the following command to copy all the COBOL source files from the *PS_HOME* directory to the compile directory:

```
cblsrc <source directory>    <compile directory>
```

Here *<source directory>* is the drive and directory where the source resides (it should be the same as *PS_HOME*), and *<compile directory>* is the drive and directory to which the source files will be copied.

For example, the following command will take the COBOL source from *PS_HOME* and copy all the necessary files to the location where the compile process will take place, *c:\temp\PTcompile* in this example:

```
cblsrc %PS_HOME% c:\temp\PTcompile
```

8. After CBLSRC completes, change directories to the compile directory, and run CBLMAKE.BAT, using the basic syntax as well as the CBLMAKE table shown earlier as your guide.

For example, to compile a file named PTPDBTST, run this command:

```
cblmake PTPDBTST
```

9. After CBLMAKE.BAT completes, copy the EXE, GNT, or INT files to the appropriate *<PS_HOME>\CBLBIN<X>* directory (CBLBINA for ANSI or CBLBINU for Unicode).

These examples use the ANSI encoding:

```
copy *.exe %PS_HOME%\cblbina
copy *.gnt %PS_HOME%\cblbina
copy *.int %PS_HOME%\cblbina
```

Note. You have to copy these files to the appropriate cblbin directory manually when you use CBLMAKE; they are not copied automatically, as when you use CBLBLD.

10. Verify that the compiler runtime files (CBLINTS.DLL, CBLRTSM.DLL, CBLRTSS.DLL, CBLVIOM.DLL, CBLVIOS.DLL, COB32API.DLL, MFLANGDF.lbr) are present in the *<PS_HOME>\CBLBIN<X>* directory.

If they are not present, then you will have to run *%PS_HOME%\setup\cblrtcpy.bat* as follows:

```
cblrtcpy %PS_HOME%\cblbina
```

Note. If you plan to use *cblmake.bat* to compile a single (or a set) of PeopleSoft PeopleTools or PeopleSoft Application COBOL program at the same time, it would be a good idea to use two different command prompts and two different compile directories—one for PeopleSoft PeopleTools COBOL programs and the other for the PeopleSoft Application COBOL programs. This avoids setting and unsetting the *PS_compile_cust* environment variable.

Task 10A-4-4: Recompiling COBOL on Microsoft Windows

You always need to compile at installation, so you will only need to recompile COBOL in the following situations:

- You are installing PeopleSoft software for the first time.
- The supported COBOL compiler changes.
- You change the version of your RDBMS.
- You change the version of your operating system.
- You apply a PeopleSoft PeopleTools upgrade, patch, or fix.

You can recompile selected COBOL files by using CBLMAKE.BAT, or recompile all your COBOL source files by using CBLBLD.BAT.

Note. If you want to recompile all your COBOL, you can follow the appropriate procedure for compiling COBOL, as described earlier.

See Compiling COBOL on Microsoft Windows with a PS_HOME Setup, Compiling COBOL on Microsoft Windows with a PS_APP_HOME Setup, or Compiling COBOL on Microsoft Windows with a PS_CUST_HOME Setup.

Task 10A-4-5: Setting Up the Micro Focus Net Express Runtime

This section discusses:

- Understanding the Micro Focus Net Express Runtime
- Installing the Runtime Files and Setting Up the License
- Removing the Runtime License
- Troubleshooting

Understanding the Micro Focus Net Express Runtime

The Micro Focus Net Express 5.1 Runtime provides the COBOL runtime environment required for COBOL programs to run. Install and license the runtime on each system that will run PeopleSoft COBOL applications. Typically, PeopleSoft COBOL application programs are run on PeopleSoft application server systems and PeopleSoft batch (Process Scheduler) systems.

The Micro Focus Net Express 5.1 Runtime consists of the following components:

- Six DLLs
 - CBLINTS.DLL
 - CBLRTSM.DLL
 - CBLRTSS.DLL
 - CBLVIOM.DLL
 - CBLVIOS.DLL
 - COB32API.DLL
- A Microsoft Windows registry entry for ASLMF
For 64-bit Microsoft Windows systems, the entry is:
HKEY_LOCAL_MACHINE\SOFTWARE\Wow6432Node\MICRO FOCUS\ASLMF
- The directory that contains the runtime license database, C:\psft-mf-nx-as-license, which contains the following files:
 - mfasdb
 - prodfile
 - semfile
- The Application Server License Manager Service

The Micro Focus Net Express 5.1 Runtime DLLs installation is done automatically as part of the COBOL compilation process. When CBLBLD.bat is run, it invokes CBLRTCPY.bat to copy the COBOL runtime DLLs listed above, from the %COBROOT%\bin directory to %PS_HOME%\CBLBINx directory.

CBLBIN x is CBLBINA, CBLBINE or CBLBINU, based on the compilation mode of ASCII, EBCDIC or Unicode respectively.

If you have already set up the Micro Focus Net Express COBOL compiler on a system, there is no explicit installation necessary for the runtime. For those systems where you only want to run COBOL, but have no need to compile it, use the following instructions in the section Installing the Runtime Files and Setting Up the License.

Installing the Runtime Files and Setting Up the License

The license files are included with the files that you downloaded from Oracle Software Delivery Cloud. The Micro Focus Net Express 5.1 Wrap Pack 15 Runtime Licensing files are contained in the self-extracting zip file, MFLicense_51WP15.exe. This executable provides the COBOL runtime system with unlimited runtime Net Express licenses specifically for PeopleSoft installations.

Always use the runtime files created for the version of the compiler that you used in compiling the COBOL files. For example, use the MFLicense_51WP15.exe runtime license file for the Micro Focus Net Express 5.1 Wrap Pack 15 compiler.

This section assumes that:

- You installed and compiled the PeopleSoft COBOL application files on the runtime system.
- You saved the files from Oracle Software Delivery Cloud in a directory referred to as *NE_INSTALL*.

To set up the runtime license:

1. Set the environment variable PS_HOME to the directory where your PeopleSoft software is installed.

For example, use this command in a command prompt window:

```
set PS_HOME=C:\HR92
```

2. Delete the following Microsoft Windows registry entry if it exists:
`\HKEY_LOCAL_MACHINE\SOFTWARE\Wow6432Node\Micro Focus\ASLMF`
3. Delete the directory C:\psft-mf-nx-as-license if it exists.
4. Go to *NE_INSTALL*, and run the self-extracting zip file MFLicense_51WP15.exe.
5. Specify the directory to save the files, for example C:\MFLicense-Extract-51WP15.
6. Change directory to C:\MFLicense-Extract-51WP15 and run the script setupMF.bat.

This script makes the following changes:

- Installs the Micro Focus Net Express Application Server License Database.
 - Creates the Microsoft Windows registry entry
`\HKEY_LOCAL_MACHINE\SOFTWARE\Wow6432Node\Micro Focus\ASLMF`, which point to the directory c:\psft-mf-nx-as-license.
 - Adds the files mfasdb, prodfile, and semfile to the directory C:\psft-mf-nx-as-license.
7. Run the command MFLMWin with the option to install, as follows:

```
MFLMWin.exe -i
```

8. To verify that the Micro Focus license manager was installed, run Microsoft Windows Services.

For example, run the following command in the command prompt window:

```
services.msc
```

You should see the service Micro Focus License Manager with status Started, and the Startup type should be Automatic.

Removing the Runtime License

To uninstall the runtime license:

- Delete the Microsoft Windows registry key:
`\HKEY_LOCAL_MACHINE\SOFTWARE\Wow6432Node\Micro Focus\ASLMF`
- Delete the `C:\psft-mf-nx-as-license` directory and its contents.

Troubleshooting

If you install the Micro Focus Net Express 5.1 Runtime License on a system where the Micro Focus Net Express 5.1 compiler is already installed, you see an error message that mentions that Runtime DLL CBLRRSS is not found. Use one of the following solutions:

- If the system where you are installing the license will be used only for running COBOL programs, but not compiling, remove the Micro Focus Net Express 5.1 COBOL compiler installation, and then re-install the Micro Focus Net Express 5.1 Runtime License.
- If the system where you are installing the license will be used for both compiling and running COBOL programs, just ignore the error message. The Net Micro Focus Express 5.1 COBOL compiler is already installed, and has an embedded runtime, which will be used to execute the COBOL programs. Thus there is no need to install and license the Micro Focus Net Express 5.1 Runtime.

If you see an error "ASLM: Erno 1000" it means the runtime license is not installed. Use the instructions in the earlier section to install the license.

See Installing the Runtime Files and Setting Up the License.

Task 10A-4-6: Defining the GNT and INT Files

By default, the compile generates a GNT file unless the exception file, `CBLINT.XX` already exists. `CBLINT.XX` contains the list of files that need to be compiled to the INT file.

Note. The INT exception file is sometimes needed to overcome Micro Focus execution error with GNT files.

For example, the exception file, `CBLINT.PT`, where *PT* represents PeopleTools, would contain the following information:

```
Call cblcrint <file name without file extension>
```

or:

```
Call cblcprint PTPDBTST
```

Task 10A-4-7: Distributing COBOL Binaries

After you have compiled your COBOL, you must transfer it to the needed locations. The required action depends upon how you set up `PS_HOME`, `PS_APP_HOME`, and `PS_CUST_HOME`.

- *PS_HOME* Setup

If the `PS_APP_HOME` location is the same as the `PS_HOME` location:

Copy the contents of `<PS_HOME>\CBLBIN<X>` (CBLBINA or CBLBINU) directory into `<PS_HOME>\CBLBIN<X>` (CBLBINA or CBLBINU) on your batch and application server machines.

- *PS_APP_HOME* Setup

If the *PS_APP_HOME* location is different than the *PS_HOME* location:

1. Copy the contents of <*PS_HOME*>\CBLBIN<*X*> (CBLBINA or CBLBINU) directory into <*PS_HOME*>\CBLBIN<*X*> (CBLBINA or CBLBINU) on your batch and application server machines.
2. Copy the contents of <*PS_APP_HOME*>\CBLBIN<*X*> (CBLBINA or CBLBINU) directory into <*PS_APP_HOME*>\CBLBIN<*X*> (CBLBINA or CBLBINU) on your batch and application server machines.

- *PS_CUST_HOME* Setup

If you have customized files in *PS_CUST_HOME*:

1. Copy the contents of <*PS_HOME*>\CBLBIN<*X*> (CBLBINA or CBLBINU) directory into <*PS_HOME*>\CBLBIN<*X*> (CBLBINA or CBLBINU) on your batch and application server machines.
2. If *PS_APP_HOME* is different from *PS_HOME*, copy the contents of <*PS_APP_HOME*>\CBLBIN<*X*> (CBLBINA or CBLBINU) directory into <*PS_APP_HOME*>\CBLBIN<*X*> (CBLBINA or CBLBINU) on your batch and application server machines.
3. Copy the contents of <*PS_CUST_HOME*>\CBLBIN<*X*> (CBLBINA or CBLBINU) directory into <*PS_CUST_HOME*>\CBLBIN<*X*> (CBLBINA or CBLBINU) on your batch and application server machines.

Chapter 10B

Installing and Compiling COBOL on UNIX

This chapter discusses:

- Understanding COBOL
- Prerequisites
- Preparing COBOL for a PeopleTools-only Upgrade
- Installing Micro Focus Server Express for UNIX and Linux
- Using the Micro Focus COBOL Compiler on UNIX
- Installing IBM COBOL on IBM AIX
- Using the IBM COBOL Compiler on IBM AIX

Understanding COBOL

This chapter describes how to compile and link PeopleSoft COBOL batch programs, if necessary.

COBOL is not needed for PeopleSoft PeopleTools because the Process Scheduler is written in C++. In addition, COBOL is not required for PeopleSoft applications that contain no COBOL programs. See My Oracle Support for the details on whether your application requires COBOL.

The chapter includes instructions for Micro Focus Net Express COBOL compiler, sometimes referred to here as "Micro Focus COBOL", and the IBM COBOL compiler for IBM AIX, sometimes referred to here as "IBM COBOL."

See Also

"Preparing for Installation," Installing Supporting Applications

PeopleSoft Enterprise Frequently Asked Questions About PeopleSoft and COBOL Compilers, My Oracle Support, (search for the article name)

PeopleSoft Enterprise Frequently Asked Questions About PeopleSoft and the IBM COBOL Compiler, My Oracle Support, (search for the article name)

PeopleTools Certifications - Suggested Fixes COBOL, My Oracle Support, (search for the article name and select the current release)

PeopleTools: Global Technology, "Understanding COBOL in a Unicode Environment"

Prerequisites

Before you attempt to run COBOL from the command line you should make sure the variable `PS_SERVER_CFG` points to a valid `psprcs.cfg` file.

Task 10B-1: Preparing COBOL for a PeopleTools-only Upgrade

When performing a PeopleTools-only upgrade, if you have COBOL modules, you must recompile all COBOL.

For Micro Focus Server Express COBOL, recompile and relink all COBOL programs for PeopleSoft PeopleTools and PeopleSoft applications, as described in a later section.

See Using the Micro Focus COBOL Compiler on UNIX.

Task 10B-2: Installing Micro Focus Server Express for UNIX and Linux

This section discusses:

- Understanding Micro Focus Server Express
- Prerequisites
- Obtaining the Installation Files for Micro Focus Server Express from Oracle Software Delivery Cloud
- Installing Micro Focus Server Express

Understanding Micro Focus Server Express

Micro Focus® Server Express™ 5.1 Wrap Pack 15 is the supported COBOL compiler on UNIX for the current PeopleSoft PeopleTools release. This section provides installation instructions for Micro Focus Server Express 5.1 Wrap Pack 15 COBOL compiler and the License Management Facility used to manage product licenses. These instructions are specifically for installing the Server Express COBOL compiler to use with PeopleSoft software. For more general installation instructions or other supporting documentation concerning Server Express, consult the documentation that comes with the installation software.

Note. Oracle supports a number of versions of UNIX and Linux in addition to Microsoft Windows for the PeopleSoft installation. Throughout this book, there are references to operating systems. Where necessary, this book refers to specific operating systems by name (for example, Oracle Solaris, IBM AIX, HP-UX Itanium, or Linux); however, for simplicity the word UNIX is often used to refer to all UNIX-like operating systems, including Linux.

Note that Oracle is the exclusive reseller of the Micro Focus COBOL compiler for use with PeopleSoft applications.

See Also

PeopleSoft Enterprise Frequently Asked Questions About PeopleSoft and COBOL Compilers, My Oracle Support, Doc ID 747059.1

Micro Focus web site: <http://supportline.microfocus.com/>

Server Express Documentation

Using the Micro Focus COBOL Compiler on UNIX

Prerequisites

You must install the Micro Focus Server Express COBOL compiler on any machine that will compile, execute, or run COBOL programs. The Micro Focus Server Express COBOL compiler includes an embedded runtime system. You can compile COBOL programs on those servers for which you have licenses, and copy the compiled programs to other servers, but to run the compiled programs, you must also install the compiler with the runtime system.

In addition, in order to execute COBOL programs that are created using a Server Express product and deployed in a UNIX environment, the Server Express compiler with the embedded runtime system, must be installed on the target runtime system, and the "Micro Focus Application Server runtime license" must also be installed on the target runtime system.

For information on obtaining licenses for Micro Focus COBOL compilers, see:

- The documentation included with the software on Oracle Software Delivery Cloud.
 - The Micro Focus Server Express Extras Install Documentation for PeopleSoft and Runtime Licenses, includes information on how to add development, Application Server, and unlimited license patch (ULP) licenses
 - The Micro Focus COBOL for PeopleSoft Quick Reference Guide summarizes the delivered software and licensing requirements.
- PeopleSoft Enterprise Frequently Asked Questions About PeopleSoft and COBOL Compilers, My Oracle Support, Doc ID 747059.1.

If you have a previous Micro Focus COBOL product installed we recommend that you make a backup of any COBOL systems files that you have changed. Examples include cobkeymp, ADISCTRL, cobopt and cobconfig. After you have installed Server Express you might want to apply to the new COBOL product the changes previously applied to these files.

If you want to maintain more than one COBOL installation, Oracle recommends that you do not install one version over another. Instead, use one of these suggested methods:

- Remove (uninstall) the existing version before installing the new version
- Leave the existing version in its current directory (do not move it) and install the new version in its own, different directory.

If you have installed, or plan to install, Micro Focus Application Server or any other Micro Focus product on the same machine as this product, you must install them in different directories.

This Micro Focus product is managed by a License Management Facility (LMF). This facility helps you keep track of the number of licenses you have for the product. In order to use this product it is necessary for you to install the License Management Facility (which is provided with the Server Express software). This software should not be installed in the same directory as Server Express. The default directory depends upon the operating system; for example:

- /opt/lib/mflmf for HP-UX Itanium
- /usr/lib/mflmf for RS/6000 and PowerPC systems running AIX
- /opt/lib/mflmf on other systems

If /opt/lib does not exist, use /usr/lib/mflmf instead.

Task 10B-2-1: Obtaining the Installation Files for Micro Focus Server Express from Oracle Software Delivery Cloud

The Micro Focus Server Express installation files are available on Oracle Software Delivery Cloud. At this point you should have already downloaded the necessary files. This section includes additional information on finding and using the files for Micro Focus Server Express if necessary.

See "Preparing for Installation," Using Oracle Software Delivery Cloud to Obtain Installation Files.

To obtain the files for the Micro Focus Server Express installation:

1. Log in to Oracle Software Delivery Cloud at <https://edelivery.oracle.com>.
2. Enter Micro Focus in the type-ahead Product field, and select Micro Focus International Ltd. Server Express COBOL for UNIX from the drop-down list.
3. Click Select Platform, select the operating system you are running on, and then click Select.
4. Click Continue.
5. Click Continue.
6. Read the license agreement, select the check box to acknowledge that you accept the terms, and then click Continue.
7. Click one of the file names to download an individual zip file, or click Download All to obtain all of the files listed.

The files include software, wrap packs, and documentation. Save the zip files to a temporary directory on your local system. You must extract (unzip) the file on the platform for which it is intended. For example, if you download the zip file for Oracle Solaris, you must unzip it on Oracle Solaris to avoid problems. If you unzip the file to a staging directory on a Microsoft Windows computer and copy the staging directory to an Oracle Solaris computer, the stage area files may be corrupt.

Task 10B-2-2: Installing Micro Focus Server Express

The following section is provided as an example installation and illustrates a typical Micro Focus Server Express 5.1 Wrap Pack 15 installation for PeopleSoft application, as outlined in the overview section above.

The answers to the prompts provided in the following example are recommended by Oracle for PeopleSoft installations, with the exception of the installation directory for the Micro Focus License Management Facility. For this step, you can use the default directory names or choose directory names based on your site's naming conventions.

It is recommended by Micro Focus and Oracle to install LMF in its own directory, instead of in a sub-directory of the Server Express install.

Important! Make sure to specify the *correct* bit mode for your UNIX platform. Enter *64* for all UNIX platforms.

The following example was done on a Red Hat Linux x86-64 operating system platform. Installation prompts will vary slightly with respect to specifics of the different UNIX platforms.

1. Log in as root.
2. Create a directory (if it does not exist) where you want to install the Micro Focus Server Express 5.1 Wrap Pack 15. For example:

```
$ mkdir -p /products/mf/svrexpr-5.1_wp15-64bit
```
3. Change directory to the one you created in the previous step.

```
$ cd /products/mf/svrexpr-5.1_wp15-64bit
```

4. Copy or ftp the Micro Focus Server Express 5.1 Wrap Pack 15 tar file that you obtained from Oracle Software Delivery Cloud to this directory.

In this example, the file name is `sx51_wp15_redhat_x86_64_dev.tar`.

5. List the items in the directory with the following command:

```
$ ls -l /products/mf/svrexpr-5.1_wp15-64bit
total 409600
-rwxr-xr-x    1 root    root          209295360 Feb 03 19:23 sx51_wp15_redhat_x86_64_dev.tar
```

6. Extract the tar file:

```
$ tar -xvf sx51_wp15_redhat_x86_64_dev.tar
```

7. List the items in the directory with the following command:

```
$ ls
ADISCTRL  bin      demo     dialog   dynload   es          etc          =>
install  lib      snmp     sx51_ws6_redhat_x86_64_dev.tar  xdb aslmf      =>
cpylib   deploy  docs     dynload64  eslmf-mess include lang        lmf =>
src      terminfo
```

8. To begin the installation, type:

```
$sh ./install
```

9. Read the text and follow the instructions to review the `readme.txt` file:

```
This script will install Micro Focus Server Express 5.1 on this computer.
```

```
The readme.txt file included in this delivery contains details of new features, enhancements and any restrictions of which you should be aware. This file is located in :
```

```
/products/mf/svrexpr-5.1_wp15-64bit/docs
```

```
We strongly recommend you read this file once the installation is complete.
```

```
Do you wish to continue (y/n): y
```

10. Read the following License Agreement and type `y` (yes) to accept it:

```
Before installing and using this software product you must agree to be bound by the terms and conditions of the end user license agreement ("License Agreement") which accompanies this product. Please take this time to read the License Agreement. If you are not in agreement with the terms and conditions of the License Agreement, please return the product to your Account Representative and your money will be refunded. If you require a replacement copy of the License Agreement, please contact your Account Representative before proceeding with the
```

install process.

Do you agree to the terms of the License Agreement? (y/n): **y**

11. If you are installing on an operating system platform that Micro Focus has not built the product on, you see the following message. Type y (yes) at the prompt:

Micro Focus Install

This product was not built or tested on this version of the Operating System.

This product was built on Operating System:

RedHatEnterpriseServer 2.6.18-348.el5 x86_64

Red Hat Enterprise Linux Server release 5.9 (Tikanga)

and you are installing it on Operating System:

Linux 3.8.13-16.2.1.el6uek.x86_64

Any product issues you report will only be corrected if they can be reproduced on one of our systems running:

RedHatEnterpriseServer 2.6.18-348.el5 x86_64

Red Hat Enterprise Linux Server release 5.9 (Tikanga)

OracleServer 3.8.13-35.3.5.el6uek.x86_64 x86_64

Red Hat Enterprise Linux Server release 6.5 (Santiago)

RedHatEnterpriseServer 2.6.18-398.el5 x86_64

Red Hat Enterprise Linux Server release 5.11 (Tikanga)

RedHatEnterpriseServer 2.6.32-504.el6.x86_64 x86_64

Red Hat Enterprise Linux Server release 6.6 (Santiago)

Please confirm that you want to continue with this installation (y/n): **y**

12. After reading the following information press ENTER to continue:

When you press return you will be shown details of the reference environment (and any compatibility environments).

Please press return when you are ready:

13. Type y (yes) to continue after reading the listing of the reference environment. For the sake of brevity, the text has been truncated, as indicated by [...].

This product is certified on the following reference environment:

The command(s) used to gather the information is given following each entry.

Operating System

RedHatEnterpriseServer 2.6.18-348.el5 x86_64

Red Hat Enterprise Linux Server release 5.9 (Tikanga)

lsb_release -si

uname -r

uname -m

cat /etc/redhat-release

C Compiler

cc gcc version 4.1.2 20080704 (Red Hat 4.1.2-54)


```
gcc -v 2>&1 | tail -1
```

```
C++ Compiler
```

```
-----
```

```
/usr/bin/g++ gcc version 4.1.2 20080704 (Red Hat 4.1.2-54)
```

```
g++ -v 2>&1 | tail -1
```

```
Assembler
```

```
-----
```

```
as GNU assembler version 2.17.50.0.6-20.el5_8.3 (x86_64-redhat-linux)⇒  
  using BFD version 2.17.50.0.6-20.el5_8.3 20061020
```

```
as -v 2>&1 < /dev/null
```

```
Linker
```

```
-----
```

```
ld GNU ld version 2.17.50.0.6-20.el5_8.3 20061020
```

```
ld -V 2>&1 | head -1
```

```
Supported versions of Java
```

```
-----
```

```
Java version = 1.6.0_15  
Java vendor = Sun Microsystems Inc.  
Java OS name = Linux  
Java OS arch = amd64  
Java OS version = 2.6.18-348.el5
```

```
Java version = 1.6.0_15  
Java vendor = Sun Microsystems Inc.
```

```
Java OS name = Linux  
Java OS arch = amd64  
Java OS version = 2.6.18-348.el5
```

```
Java version = 1.7.0_05  
Java vendor = Oracle Corporation  
Java OS name = Linux  
Java OS arch = i386  
Java OS version = 2.6.18-348.el5
```

```
Java version = 1.7.0_05  
Java vendor = Oracle Corporation  
Java OS name = Linux  
Java OS arch = amd64  
Java OS version = 2.6.18-348.el5
```

```
$JAVA_HOME/bin/java -classpath $COBDIR/lib WhatJava
```

```
Unicode
```

```
-----
```

```
Unicode mapping tables must be installed for J2EE and Web Services to
```

function correctly. These tables are required for converting between any combination of UTF-16/UCS-2, UTF-8 and other installed locales.

[...]

Please confirm your understanding of the above reference environment⇒ details (y/n): **y**

If you require this support, you will need to install the TCP/IP⇒ Development System libraries prior to installation of your COBOL⇒ system.

14. Answer *n* (no) to the following prompt:

Do you want to make use of COBOL and Java working together? (y/n): **n**
Skipping Java setup

Should you want to use Java with COBOL later on as super user, run the⇒ command /products/mf/svrexpr-5.1_wp15-64bit/bin/java_setup to select⇒ the version of Java you want to use.

Note. PeopleSoft COBOL implementations do not require COBOL and Java to work together.

15. Answer *y* (yes) to the following prompt concerning the License Management Facility:

This product is protected using the Micro Focus License Management⇒ Facility (LMF). Please refer to the Development System Licensing Guide⇒ for information relating to the installation of the licensing system⇒ and licenses.

If you do not have LMF installed or want to upgrade to the latest⇒ version, we recommend that you install it now.

Would you like to install LMF now? (y/n): **y**

16. At the following prompt, enter the directory name where you want to install License Manager.

Note. Micro Focus and Oracle recommend that you install LMF in its own directory, instead of a sub-directory of the Server Express installation.

Enter the directory name where you wish to install License Manager.
(Press Enter for default directory /opt/microfocus/mflmf)

/products/mf/mflmf-svrexpr-5.1_wp15-64bit

17. Enter *y* (yes) to restrict access to the License Admin System to the superuser account:

Do you want only superuser to be able to access the License Admin⇒ System? (y/n) **y**

18. Enter *y* (yes) to start license manager automatically at boot time:

It is recommended that you let license manager autostart at boot time.

Do you want license manager to be automatically started at boot time? ⇒ (y/n) **y**

LMF installation complete.

19. If you want to consult the documentation on how to install licenses, follow the instructions in this prompt:

Please consult the Development Licensing Guide for detailed information⇒
on how to install licenses.

This may be done by running the mfllicense tool.

To run your applications you need a deployment license installed using⇒
Apptrack.

See your Deployment Licensing Guide for details.
Installing Apptrack...

Access permissions on directory /var/mfaslmf have changed on this⇒
release

Write access permission has been removed except for superuser use
Apptrack installation complete

20. Enter 64 for the system default bit mode:

This product can be used in either 32-bit or 64-bit modes.
Please enter either 32 or 64 to set the system default mode: **64**
System default COBMODE has been set to 64.

21. Wait for the documentation to be installed:

Installing documentation. Please wait...

22. Enter *n* (no) at the following prompt:

Enterprise Server provides a scalable, managed, and high-performance⇒
transactional environment for the deployment of COBOL applications and⇒
services, COBOL/J2EE applications and direct COBOL Web Services.

Your Enterprise Server requires configuration. You can either do it now⇒
or later. To do it now, you need to know the alphanumeric user ID of⇒
the Enterprise Server System Administrator.

To do it later, enter the following commands whilst logged in as root:

```
/products/mf/svrex-5.1_wp15-64bit/bin/eslminstall
/products/mf/svrex-5.1_wp15-64bit/bin/casperm
```

Do you wish to configure Enterprise Server now? (y/n): **n**

23. Review the information concerning setting the COBDIR, LD_LIBRARY_PATH, and PATH environment variables in the concluding prompt:

(Remember to set COBDIR to /products/mf/svrex-5.1_wp15-64bit, include ⇒
/products/mf/svrex-5.1_wp15-64bit/lib in LD_LIBRARY_PATH, and include ⇒
/products/mf/svrex-5.1_wp15-64bit/bin on your PATH.)

WARNING: Any executables (whether a Run-Time System or an application)⇒
must be relinked using this new release. Otherwise, the results of⇒
running the older executables with this new release are undefined.

Installation completed successfully.

The COBOL system is ready to use.

Task 10B-3: Using the Micro Focus COBOL Compiler on UNIX

This section discusses:

- Understanding COBOL Compilation
- Setting Environment Variables
- Modifying the Liblist64 File (IBM AIX)
- Compiling COBOL on UNIX with a PS_HOME Setup
- Compiling COBOL on UNIX with a PS_APP_HOME Setup
- Compiling COBOL on UNIX with a PS_CUST_HOME Setup
- Linking COBOL
- Recompiling COBOL on UNIX

Understanding COBOL Compilation

On UNIX operating systems, you always need to compile your COBOL programs at installation time. After you set up your application or batch server, perform the steps discussed in this section.

The Micro Focus Server Express COBOL compiler includes an embedded runtime system, so the compiler must be installed on machines that will compile the COBOL programs and also on any machine where COBOL programs are to be executed or run.

You have two options for compiling:

- You can treat one application or batch server as your compile server, compile all your COBOL programs there, and then distribute cblbin from there to all other relevant servers. In this case, you would copy any patches and customizations from your file server to this designated server before carrying out the compile. You would also need to install the Server Express compiler on all servers, in order to have the embedded runtime system present.
- The second option is to compile on all servers. In this situation, all servers would need a COBOL compiler, and you would need to copy any patches and customizations from the file server to all of these servers before carrying out the compile.

Note. You should have read/write access to the directory *PS_HOME/cblbin* to be able to compile the COBOL programs.

Note. To copy a compiled COBOL program from one UNIX server to another, they must be on the same operating system that the compile took place on. For example, if you compile on Oracle Solaris for the Application Server, and the Process Scheduler is on AIX, you cannot copy the compiled program (you will also need to compile on the AIX machine).

The way that you set up your installation environment determines how you compile COBOL. This section includes different procedures for the different installation environments, as follows:

- *PS_HOME Setup*

If you installed the PeopleSoft Application software to a *PS_APP_HOME* location that is the same as the *PS_HOME* location where you installed PeopleSoft PeopleTools, follow the instructions in the section Compiling COBOL on UNIX with a PS_HOME Setup.

- *PS_APP_HOME Setup*

As described earlier, for PeopleSoft PeopleTools 8.52 and later, you have the option to install the PeopleSoft Application software to a location outside *PS_HOME*. If the *PS_APP_HOME* environment variable is defined and is different from *PS_HOME*, the COBOL build scripts behave differently under certain build options. There are also some new build options under certain environments which would be recognized if *PS_APP_HOME* is defined.

If you installed the PeopleSoft Application software to a *PS_APP_HOME* location that is different from the *PS_HOME* location where you installed PeopleSoft PeopleTools, follow the instructions in the section Compiling COBOL on UNIX with a *PS_APP_HOME* Setup.

- *PS_CUST_HOME Setup*

For PeopleSoft PeopleTools 8.53 and later, you have the option to place customized COBOL baseline sources into a location referenced by the environment variable *PS_CUST_HOME*.

The *PS_CUST_HOME* directory structure must replicate that of *PS_HOME* or *PS_APP_HOME*; that is, any COBOL source file that is customized should be placed in the same relative path as was present in the original location. If your environment includes customized files in a *PS_CUST_HOME* directory, follow the instructions in the section Compiling COBOL on UNIX with a *PS_CUST_HOME* Setup.

See Also

"Preparing for Installation," Defining Installation Locations.

Task 10B-3-1: Setting Environment Variables

On your UNIX system, you need to log in and ensure the following environment variables are set appropriately. Alternatively, make sure the following environment variables are set in the *.profile* file in the user's home directory:

- *\$COBDIR* must be set to the Micro Focus Server Express installation; for example:
`COBDIR=/products/mf/svrexpress-51_wp15; export COBDIR`
- *\$COBDIR/lib* must be appended to *LD_LIBRARY_PATH*, *LIBPATH*, or *SHLIB_PATH*, whichever is appropriate for your platform.
`LD_LIBRARY_PATH=$LD_LIBRARY_PATH:$COBDIR/lib; export LD_LIBRARY_PATH`
`LIBPATH=$LIBPATH:$COBDIR/lib; export LIBPATH`
`SHLIB_PATH=$SHLIB_PATH:$COBDIR/lib; export SHLIB_PATH`
- *\$COBDIR/bin* must be appended to the *PATH*; for example:
`PATH=$PATH:$COBDIR/bin; export PATH`

To set the required DB2/LUW environment, run *db2profile*. Enter the following command:

```
cd <DB2_INSTANCE_DIRECTORY>/sqllib
. ./db2profile
```

To set the required PeopleSoft environment variables, source the script *psconfig.sh*. Enter the following command from the *PS_HOME* directory:

```
. ./psconfig.sh
```

Task 10B-3-2: Modifying the Liblist64 File (IBM AIX)

Understanding Liblist Modifications

If you are compiling COBOL on AIX, modify the liblist64 file as described here. Check My Oracle Support for additional information about modifications that need to be made in the liblist64 file for COBOL.

See My Oracle Support, Certifications.

Modifying the Liblist64 File for AIX

To modify the liblist64 file for AIX:

1. cd to \$COBDIR/lib.
2. Add the following line to the liblist file:

```
x:*:s!t:-lC
```

The following listing shows where to make the changes (in bold font):

```
#          More emulation of cc (MUST be after MF/user libraries):
x:*:st:-L/usr/lib/threads
x:*:st:-lpthreads
x:*:s!t:-lC                                <=== Add this line
x:*:s:-lc
```

Task 10B-3-3: Compiling COBOL on UNIX with a PS_HOME Setup

This section assumes that you installed the PeopleSoft Application software to a *PS_APP_HOME* directory that is the same as the *PS_HOME* directory where you installed PeopleSoft PeopleTools. It also assumes that there is no separate *PS_CUST_HOME* directory with customized COBOL source files.

To compile COBOL on UNIX:

1. If you haven't already done so, download all required patches to your file server, and from there FTP the contents of src\cbl\base and src\cbl\unix over to src/cbl on the relevant application or batch server.

Note. When you copy patches over from the file server, the files need to have a lowercase cbl extension and an uppercase program name, as in PATCH.cbl.

2. Source the script psconfig.sh from *PS_HOME* to set up environment variables correctly on your application or batch server.

```
. ./psconfig.sh
```

3. Change to the *PS_HOME/setup* directory:

```
cd $PS_HOME/setup
```

4. To compile all the COBOL source dynamically, issue the command:

```
./pscbl.mak
```

The dynamic compile creates INT, LST, and GNT files, which are copied to these locations:

File	Location
INT	<i>PS_HOME</i> /src/cbl/int
LST	<i>PS_HOME</i> /src/cbl/lst
GNT	<i>PS_HOME</i> /cblbin

Warning! Proposed ISO 2000 COBOL features are enabled. Please refer to documentation for details, and do not rely on these features being supported in future products from Micro Focus due to changes in the proposed COBOL standard.

Note. For Server Express, PeopleSoft sets the COBOL directive INTLEVEL to 4. Setting this directive to this value enables you to raise the significant digits of numeric fields from 18 to 31. This is in accordance with the ISO 2000 COBOL standard. During the compilation of each program, the vendor of Server Express will display a warning. This should not be considered a compilation error.

Task 10B-3-4: Compiling COBOL on UNIX with a PS_APP_HOME Setup

This section assumes that you installed the PeopleSoft Application software to a *PS_APP_HOME* directory that is different from the *PS_HOME* directory where you installed PeopleSoft PeopleTools. It also assumes that there is no separate *PS_CUST_HOME* directory with customized COBOL source files.

Use the shell script pscbl.mak, found in *PS_HOME*/setup, to do the PeopleSoft COBOL compilation. This table describes the allowed arguments for pscbl.mak:

Command	Description
pscbl.mak	Use this command, with no argument, to compile all the COBOL programs.
pscbl.mak PS_HOME	Use this argument to compile only the PeopleSoft PeopleTools COBOL programs.
pscbl.mak PS_APP_HOME	Use this argument to compile only the PeopleSoft Application COBOL programs.
pscbl.mak <COBOL_PROGRAM>	Enter the name for a valid PeopleSoft PeopleTools or PeopleSoft Application COBOL program to compile a specific program.

If you specify any argument other than the ones mentioned above, you will get the following usage display message:

```
echo Correct usage of the program is:
```

```

echo 1. pscbl.mak
echo 2. pscbl.mak PS_HOME
echo 3. pscbl.mak PS_APP_HOME
echo 4. pscbl.mak PTPDBTST (or any tools/apps program, Note Peoplesoft⇒
COBOL programs are 6, 7 or 8 characters long)

```

To compile COBOL programs on UNIX:

1. Set PS_HOME environment variable in the UNIX shell prompt from which you want to run the COBOL compile.

You can run *PS_HOME/psconfig.sh* with the following command to set the PS_HOME environment variable in the shell.

```

cd <PS_HOME>
. ./psconfig.sh

```

Verify if PS_HOME is set with this command:

```

$ echo $PS_HOME
$ /home/<user>/PTcompile

```

2. Set the PS_APP_HOME environment variable (PS_APP_HOME refers to the location where you have installed the PeopleSoft Application software) with this command:

```
PS_APP_HOME=/home/<user>/HRcompile; export PS_APP_HOME
```

3. Run pscbl.mak, using one of these methods:

- To compile all PeopleSoft COBOL programs, that is, those for PeopleSoft PeopleTools and PeopleSoft Application, run this command:

```
pscbl.mak
```

This will compile the programs that are under *PS_HOME/src/cbl* and *PS_APP_HOME/src/cbl*.

- To compile only PeopleSoft PeopleTools COBOL programs, run this command:

```
pscbl.mak PS_HOME
```

- To compile only PeopleSoft Application COBOL programs, run this command:

```
pscbl.mak PS_APP_HOME
```

- To compile a single COBOL program, run the command with the COBOL program name excluding the .cbl extension.

For example, for a PeopleSoft PeopleTools COBOL program PTPDBTST.CBL, or a PeopleSoft Application COBOL program GPPDPRUN.CBL, run:

```

pscbl.mak PTPDBTST
pscbl.mak GPPDPRUN

```

PeopleSoft PeopleTools compiled COBOL programs will be placed under the *PS_HOME\cblbin* directory.

PeopleSoft Application compiled COBOL programs will be placed under the *PS_APP_HOME\cblbin* directory.

Task 10B-3-5: Compiling COBOL on UNIX with a PS_CUST_HOME Setup

This section assumes that you have set up a PS_CUST_HOME environment variable for customized COBOL source files.

To compile COBOL programs on UNIX:

1. Set *PS_HOME* environment variable in the UNIX shell prompt from which you want to run the COBOL compile.

You can run *PS_HOME/psconfig.sh* with the following command to set the *PS_HOME* environment variable in the shell:

```
cd <PS_HOME> . ./psconfig.sh
```

Verify if the *PS_HOME* environment variable is set with this command:

```
$ echo $PS_HOME $ /home/<user>/PTcompile
```

2. If *PS_APP_HOME* is different from *PS_HOME*, set the *PS_APP_HOME* environment variable with this command:

```
PS_APP_HOME=/home/<user>/HRcompile; export PS_APP_HOME
```

3. Set the *PS_CUST_HOME* environment variable with this command:

```
PS_CUST_HOME=/home/<user>/CUSTcompile; export PS_CUST_HOME
```

4. To compile all the COBOL source under *PS_CUST_HOME* dynamically, issue the command:

```
./pscb1.mak PS_CUST_HOME
```

PeopleSoft PeopleTools compiled COBOL programs and PeopleSoft Application compiled COBOL programs will be placed under the *PS_CUST_HOME/cblbin* directory.

Task 10B-3-6: Linking COBOL

This section discusses:

- Understanding COBOL Linking
- Linking COBOL Components on UNIX

Understanding COBOL Linking

PSRUN is the PeopleSoft procedure that connects the COBOL batch programs with the RDBMS API.

PSRUNRMT is the PeopleSoft procedure that connects the remote COBOL programs with the RDBMS API.

Both PSRUN and PSRUNRMT are compiled uniquely for each platform and consist of modules provided with PeopleSoft software, the RDBMS platform, and the operating system.

You need to create the PSRUN and PSRUNRMT programs in the following situations:

- You are installing PeopleSoft software for the first time.
- Any COBOL programs have changed.
- The version of the RDBMS running the PeopleSoft system has changed.
- The COBOL compiler has changed.
- One of the C programs supplied with the PeopleSoft system has changed.

Note. The PeopleSoft system only supports dynamic linking of COBOL. Static linking is not an option.

Linking COBOL Components on UNIX

To link COBOL components on UNIX:

1. Change to the *PS_HOME/setup* directory:

```
cd $PS_HOME/setup
```

2. For dynamic linking, run:

```
./psrun.mak
```

The PSRUN.MAK script should return the UNIX prompt when done. If the compile completes without errors, the files PSRUN and PSRUNRMT will now exist in the *PS_HOME/bin* directory. If you encounter errors, check *PS_HOME/setup/psrun.err* and *PS_HOME/setup/psrunrmt.err*

Task 10B-3-7: Recompiling COBOL on UNIX

You always need to compile at installation, so you will only need to recompile COBOL in the following situations:

- You are installing PeopleSoft software for the first time.
- The supported COBOL compiler changes.
- You change the version of your RDBMS.
- You change the version of your operating system.
- You apply a PeopleSoft PeopleTools upgrade, patch, or fix.

Note. Remember, you must always use your file server as the source repository for your COBOL. You should download any patches and apply any customizations to the file server, and disseminate them from there.

You can compile a *single* COBOL program dynamically by using this command syntax:

```
./pscbl.mak <PROGRAM NAME WITHOUT "cbl" EXTENSION>
```

For example, the following command compiles the lone file PTPDBTST.

```
./pscbl.mak PTPDBTST
```

Note. If you want to recompile all your COBOL, you can follow the appropriate procedure as described earlier.

See Compiling COBOL on UNIX with a PS_HOME Setup, Compiling COBOL on UNIX with a PS_APP_HOME Setup, or Compiling COBOL on UNIX with a PS_CUST_HOME Setup.

The compile should run without errors until it completes. After the script is complete, check the destination directories for the newly created files. They should have a length greater than zero as well as a current date and time stamp. You can find the files in the following locations:

- For PS_HOME Setup: *PS_HOME/src/cbl/int*, *PS_HOME/src/cbl/lst*, and *PS_HOME/cblbin*
 - For PS_APP_HOME Setup: *PS_APP_HOME/src/cbl/int*, *PS_APP_HOME/src/cbl/lst*, and *PS_APP_HOME/cblbin*
 - For PS_CUST_HOME Setup: *PS_CUST_HOME/src/cbl/int*, *PS_CUST_HOME/src/cbl/lst*, and *PS_CUST_HOME/cblbin*
-

Note. You can also use pscbl.mak PTP*** to compile all source files that start with PTP.

Task 10B-4: Installing IBM COBOL on IBM AIX

This section discusses:

- Understanding the IBM COBOL for AIX Installation
- Prerequisites
- Installing IBM COBOL for AIX v5.1.0.0

Understanding the IBM COBOL for AIX Installation

The IBM COBOL for AIX compiler version 5.1.0.0 is supported for the current PeopleSoft PeopleTools release. This section includes the installation of the IBM COBOL Compiler on IBM AIX.

Prerequisites

To install and use IBM COBOL for AIX 5.1.0.0, you must have the following:

- PeopleSoft PeopleTools
We recommend that you take the latest available PeopleSoft PeopleTools patch level. You should install PeopleSoft PeopleTools and your PeopleSoft application software before you compile the IBM COBOL for AIX source files.
- IBM COBOL for AIX version 5.1.0.0.
You must obtain IBM COBOL for AIX compiler from your IBM vendor. Obtain the installation documentation and review the information on system prerequisites and installation methods. The following instructions assume that you have the IBM installation files and installation documentation. Contact your IBM representative to obtain the software.
See IBM COBOL for AIX on the IBM web site, <https://www.ibm.com/us-en/marketplace/cobol-compiler-aix/>.
See IBM Knowledge Center, <https://www.ibm.com/support/knowledgecenter/>.
- The IBM COBOL compiler uses the system temporary space for some steps. Be sure the space is not full before beginning the compilation.
See Using the IBM COBOL Compiler on IBM AIX, Troubleshooting the IBM COBOL Compiler.

Task 10B-4-1: Installing IBM COBOL for AIX v5.1.0.0

This procedure assumes that you have obtained the installation file from IBM and installed the COBOL compiler and COBOL runtime components on your system.

See IBM Knowledge Center, COBOL for AIX, V5.1 Documentation, https://www.ibm.com/support/knowledgecenter/SS6SGM_5.1.0/com.ibm.cobol51.aix.doc/welcome.html.

Task 10B-5: Using the IBM COBOL Compiler on IBM AIX

This section discusses:

- Setting Environment Variables for IBM COBOL

- Compiling COBOL on AIX with a `PS_HOME` Setup
- Compiling COBOL on AIX with a `PS_APP_HOME` Setup
- Compiling COBOL on AIX with a `PS_CUST_HOME` Setup
- Troubleshooting the IBM COBOL Compiler
- Setting Up the IBM COBOL Runtime
- Removing the IBM COBOL Installation

Setting Environment Variables for IBM COBOL

Before compiling the IBM COBOL for AIX, or before installing the files on machines where the COBOL will be run, you must specify environment variables as described in this section. This procedure assumes that the installation directory for PeopleSoft PeopleTools is `PS_HOME`.

To set the environment variables for IBM COBOL for AIX, go to the PeopleSoft PeopleTools installation directory and source the `psconfig.sh` script:

```
cd <PS_HOME>
. ./psconfig.sh
```

This section includes different procedures depending upon how you set up your installation environment.

- *PS_HOME Setup*

If you installed the PeopleSoft Application software to a `PS_APP_HOME` location that is the same as the `PS_HOME` location where you installed the PeopleSoft PeopleTools software, follow the instructions in the section Compiling COBOL on AIX with a `PS_HOME` Setup.

- *PS_APP_HOME Setup*

If you installed the PeopleSoft Application software to a `PS_APP_HOME` location that is different from the `PS_HOME` location where you installed the PeopleSoft PeopleTools software, follow the instructions in the section Compiling COBOL on AIX with a `PS_APP_HOME` Setup.

- *PS_CUST_HOME Setup*

For PeopleSoft PeopleTools 8.53 and later, you have the option to place customized COBOL baseline sources into a location referenced by the environment variable `PS_CUST_HOME`.

The `PS_CUST_HOME` directory structure must replicate that of `PS_HOME` or `PS_APP_HOME`; that is, any COBOL source file that is customized should be placed in the same relative path as was present in the original location. If you set up a `PS_CUST_HOME` directory for your customized COBOL source files, follow the instructions in the section Compiling COBOL on AIX with a `PS_CUST_HOME` Setup.

See Also

"Preparing for Installation," Defining Installation Locations.

Task 10B-5-1: Compiling COBOL on AIX with a `PS_HOME` Setup

This section assumes that you have installed the PeopleSoft Application software in the same directory (`PS_APP_HOME`) where you installed the PeopleSoft PeopleTools software (`PS_HOME`), and that you do not have customized COBOL source files in a `PS_CUST_HOME` directory. In addition, this procedure assumes that you have set the environment variables as described in the previous section.

This section is only required for those who need to compile the COBOL sources, not for those who only need to run the compiled COBOL.

To compile the COBOL source files:

1. Change the directory to *PS_HOME/setup*; for example:

```
cd $PS_HOME/setup
```

2. Depending on the character encoding type that your installation uses, set the environment variable *PS_ENCODING*, as specified in this table:

Database Encoding	Command
ANSI	export PS_ENCODING=ansi
Unicode	export PS_ENCODING=unicode

Make sure that you are giving the correct value of this environment variable. You will receive errors if the wrong value of this environment variable is specified.

- If your setup includes the file *\$PS_HOME/setup/unicode.cfg*, indicating that the character encoding for your installation is Unicode, but you set the value of *PS_ENCODING* to *ansi* with the commands above, you will get the following error

```
pscbldm.mak : ERROR : <PS_HOME>/unicode.cfg EXISTS, but INCOMPATIBLE⇒
encoding of $PS_ENCODING was specified, EXITING!!!
```

- If your setup does not have the file *\$PS_HOME/setup/unicode.cfg*, indicating that the character encoding for your installation is non-Unicode, but you set the value of *PS_ENCODING* to *unicode*, you will get the following error

```
pscbldm.mak : ERROR : <PS_HOME>/setup/unicode.cfg does not EXIST,⇒
but INCOMPATIBLE encoding of $PS_ENCODING was specified, EXITING!!!
```

3. Use this command to compile:

```
./pscbldm.mak apps
```

The optional parameter *apps* determines the location of the work area where the compilation takes place. The allowed values and compilation location for PeopleSoft product lines are listed in this table:

Product Line	Apps Parameter	Location
PeopleSoft PeopleTools	pt (default)	<i>PS_HOME</i> /sdk/cobol/pscbldpt/src
Human Capital Management	hcm	<i>PS_HOME</i> /sdk/cobol/pscbldhcms/src
Financials/Supply Chain Management	fscm	<i>PS_HOME</i> /sdk/cobol/pscbldfscm/src

The compiled COBOL programs will be placed under *<PS_HOME>/CBLBIN_IBM<X>*.

<X> is A for ANSI or U for Unicode.

Note. If you see the following output during the compilation, you can ignore it:

```
Preprocessing COBOL files ls: 0653-341 The file *.cfg does not exist.
Preprocessing the file PSPBASCH.cbl Can't open input file
```

Task 10B-5-2: Compiling COBOL on AIX with a PS_APP_HOME Setup

This section assumes that you have installed the PeopleSoft Application software in a directory (*PS_APP_HOME*) which is different than the PeopleSoft PeopleTools software installation directory (*PS_HOME*) and that you do not have customized COBOL source files in a *PS_CUST_HOME* directory. In addition, this procedure assumes that you have set the environment variables as described earlier.

This section is only required for those who need to compile the COBOL sources, not for those who only need to run the compiled COBOL.

To compile the COBOL source files:

1. Ensure that the directory `sdk/cobol/psclapps` is present under *PS_APP_HOME* directory for the application you are trying to compile.

For example if the installed PeopleSoft Application is Human Capital Management (*apps* = *hcm*), then the following directory structure should be present and the user must have write access to it:

```
sdk/cobol/psclhcm
```

2. Set the environment variable for *PS_HOME*, the directory where you installed the PeopleSoft software; for example:

```
PS_HOME = ~/PTcompile; export PS_HOME
```

3. Set the environment variable for *PS_APP_HOME*, the directory where you installed the PeopleSoft Application software; for example:

```
PS_APP_HOME = ~/HRcompile; export PS_APP_HOME
```

4. Change the directory to *PS_HOME/setup*; for example:

```
cd $PS_HOME/setup
```

5. Depending on the character encoding type that your installation uses, set the environment variable *PS_ENCODING*, as specified in this table:

Database Encoding	Command
ANSI	<code>export PS_ENCODING=ansi</code>
Unicode	<code>export PS_ENCODING=unicode</code>

Make sure that you are giving the correct value of this environment variable. You will receive errors if the wrong value of this environment variable is specified, as follows:

- If your setup includes the file `$PS_HOME/setup/unicode.cfg`, indicating that the character encoding for your installation is Unicode, but you set the value of *PS_ENCODING* to `ansi` with the commands above, you will get the following error:

```
psclibm.mak : ERROR : <PS_HOME>/unicode.cfg EXISTS, but INCOMPATIBLE⇒
encoding of $PS_ENCODING was specified, EXITING!!!
```

- If your setup does not have the file `$PS_HOME/setup/unicode.cfg`, indicating that the character encoding for your installation is non-Unicode, but you set the value of *PS_ENCODING* to `unicode`, you will get the following error:

```
psclibm.mak : ERROR : <PS_HOME>/setup/unicode.cfg does not EXIST,⇒
but INCOMPATIBLE encoding of $PS_ENCODING was specified, EXITING!!!
```

6. Use this command to compile:

```
./pscbllibm.mak apps
```

The optional parameter *apps* determines the location of the work area where the compilation takes place. The allowed values and compilation locations are listed in this table:

Product Line	Apps Parameter	Location
PeopleSoft PeopleTools	pt (default)	<i>PS_HOME</i> /sdk/cobol/pscbllpt/src
Human Capital Management	hcm	<i>PS_APP_HOME</i> / sdk/cobol/pscbllhcms/src
Financials/Supply Chain Management	fscm	<i>PS_APP_HOME</i> / sdk/cobol/pscbllfscm/src

The PeopleSoft PeopleTools compiled COBOL programs will be placed under *<PS_HOME>/CBLBIN_IBM<X>* and the PeopleSoft Application compiled COBOL programs will be placed under *<PS_APP_HOME>/CBLBIN_IBM<X>*.

<X> is A for ANSI or U for Unicode.

Task 10B-5-3: Compiling COBOL on AIX with a PS_CUST_HOME Setup

This section assumes that you have set up a *PS_CUST_HOME* environment variable for customized COBOL source files. Furthermore, it assumes that you have set the environment variables as described earlier.

This section is only required for those who need to compile the COBOL sources, not for those who only need to run the compiled COBOL.

1. Ensure that the directory *sdk/cobol/pscbllapps* is present under the *PS_APP_HOME* directory for the application you are trying to compile.

For example if the installed PeopleSoft Application is Human Capital Management (*apps* = *hcm*), then the following directory structure should be present and the user must have write access to it:

```
sdk/cobol/pscbllhcm
```

2. Set the environment variable for *PS_HOME*, the directory where you installed the PeopleSoft PeopleTools software; for example:

```
PS_HOME = ~/PTcompile; export PS_HOME
```

3. If *PS_APP_HOME* is different from *PS_HOME*, set the environment variable for *PS_APP_HOME*, the directory where you installed the PeopleSoft Application software; for example:

```
PS_APP_HOME = ~/HRcompile; export PS_APP_HOME
```

4. Set the environment variable for *PS_CUST_HOME*, the directory where you installed the PeopleSoft Application software; for example:

```
PS_CUST_HOME = ~/CUSTcompile; export PS_CUST_HOME
```

5. Change the directory to *PS_HOME/setup*; for example:

```
cd $PS_HOME/setup
```

6. Depending on the character encoding type that your installation uses, set the environment variable `PS_ENCODING`, as specified in this table:

Database Encoding	Command
ANSI	<code>export PS_ENCODING=ansi</code>
Unicode	<code>export PS_ENCODING=unicode</code>

Make sure that you are giving the correct value of this environment variable. You will receive errors if the wrong value of this environment variable is specified, as follows:

- If your setup includes the file `$PS_HOME/setup/unicode.cfg`, indicating that the character encoding for your installation is Unicode, but you set the value of `PS_ENCODING` to `ansi` with the commands above, you will get the following error:

```
psclibm.mak : ERROR : <PS_HOME>/unicode.cfg EXISTS, but INCOMPATIBLE⇒
encoding of $PS_ENCODING was specified, EXITING!!!
```
- If your setup does not have the file `$PS_HOME/setup/unicode.cfg`, indicating that the character encoding for your installation is non-Unicode, but you set the value of `PS_ENCODING` to `unicode`, you will get the following error:

```
psclibm.mak : ERROR : <PS_HOME>/setup/unicode.cfg does not EXIST,⇒
but INCOMPATIBLE encoding of $PS_ENCODING was specified, EXITING!!!
```
- Use this command to compile:

```
./psclibm.mak cust
```

The customized PeopleSoft PeopleTools and PeopleSoft Application COBOL programs will be placed under `<PS_CUST_HOME>/CBLBIN_IBM<X>`.

`<X>` is A for ANSI or U for Unicode.

Task 10B-5-4: Troubleshooting the IBM COBOL Compiler

This section discusses:

- Understanding Troubleshooting for the IBM COBOL Compiler
- Reviewing Screen Output from `psclibm.mak`
- Reviewing `erroribm.lst`
- Reviewing the `LISTOUT.LST` file
- Reviewing `COBOL_PROGRAM.LST` files
- Reviewing temporary space errors

Understanding Troubleshooting for the IBM COBOL Compiler

You can find the error and list files discussed in this section in the following locations, depending upon your installation setup:

- If `PS_APP_HOME` and `PS_CUST_HOME` are the same as `PS_HOME` or both `PS_APP_HOME` and `PS_CUST_HOME` are undefined, all error and list files mentioned here are placed in directories under `PS_HOME`.

- If *PS_APP_HOME* is different from *PS_HOME*, and you compile PeopleSoft PeopleTools COBOL source files, the error and list files mentioned here are placed in directories under *PS_HOME*.
- If *PS_APP_HOME* is different from *PS_HOME*, and you compile PeopleSoft Application COBOL source files, the error and list files mentioned here are placed in directories under *PS_APP_HOME*.
- If *PS_CUST_HOME* is different from *PS_HOME*, and you compile PeopleSoft Application COBOL source files, the error and list files mentioned here are placed in directories under *PS_CUST_HOME*.

When compiling COBOL programs on AIX using the IBM COBOL compiler, compiler and linker informational messages are reported in the following locations:

- screen output from *psclibm.mak*
- *erroribm.lst*
PS_HOME/setup/erroribm.lst
- *LISTOUT.lst* file
<PS_HOME>/sdk/cobol/pscl<APPS>/src/LISTOUT.lst
<APPS> is the PeopleSoft product family, such as *hcm*.
See Compiling COBOL on AIX with a *PS_HOME* Setup
- *COBOL_PROGRAM.lst*
<PS_HOME>/sdk/cobol/pscl<APPS>/lst/<COBOL_PROGRAM>.lst

Initially, either review the screen output or the *erroribm.lst* file in *PS_HOME/setup*. The *erroribm.lst* file will contain the names of the programs that failed to compile. You can examine the file *LISTOUT.lst* to find the COBOL program names listed in *erroribm.lst* to review the cause of the failures. Then review the *COBOL_PROGRAM.lst* file to analyze the COBOL error in context of the COBOL source code. After you have corrected the compile or linker errors, you can simply start a complete re-compile.

Depending on the relevancy of the failing compiled modules to your project mission, you can decide to resolve all compile and linker errors or continue without the failed modules.

The programs *PTPPSRUN* and *PTPPSRMT* must be compiled correctly. If these programs do not compile correctly, none of the COBOL programs will run. These programs are located at *PS_HOME/src/cbl/ibm/unix*.

If these programs fail to compile, you will get the following errors:

```
./psclibm.mak : Error : Critical program PTPPSRUN did not compile
./psclibm.mak : Error : This error must be fixed prior to running any⇒
cobol programs...

./psclibm.mak : Error : Critical program PTPPSRMT did not compile
./psclibm.mak : Error : This error must be fixed prior to running any⇒
cobol programs via RemoteCall
```

Be sure to resolve the errors for these programs before proceeding.

Reviewing Screen Output from *psclibm.mak*

The screen output is the first place you should look to determine if there is a compilation or linking error. Errors including the phrase "fail to compile/link" will be displayed at the end of the screen output. For example:

```
./psclibm.mak: Error : The list of file(s) failed to compile/link.
CEPCROLL fail to compile/link
ENPBTRNS fail to compile/link
ENPMMAIN fail to compile/link
```

```

GLPJEDT2 fail to compile/link
SFPCRELS fail to compile/link
SFPREVAL fail to compile/link
./psclibm.mak : The list of file(s) that failed to compile/link can be⇒
  found at /data1/home/easa/pt854/setup/erroribm.lst
./psclibm.mak : The compilation log is generated at /data1/home/easa⇒
  /pt854/sdk/cobol/psclpt/src/LISTOUT.lst
./psclibm.mak : The compile listing of the COBOL programs can be seen at ⇒
  /data1/home/easa/pt854/sdk/cobol/psclpt/lst

```

Reviewing erroribm.lst

The erroribm.lst file is located in the *PS_HOME*/setup directory, and contains a list of the programs that failed to compile. For example:

```

CEPCROLL fail to compile/link
ENPBTRNS fail to compile/link
ENPMAIN fail to compile/link
GLPJEDT2 fail to compile/link
SFPCRELS fail to compile/link
SFPREVAL fail to compile/link

```

Reviewing the LISTOUT.LST file

The LISTOUT.lst file is located in the <*PS_HOME*>/sdk/cobol/pscl<*APPS*>/src directory and contains compiler and linker informational, warning and error messages.

For example, the following error is related to program PTPDBTST:

```

exec: /usr/bin/ld -b64 -bpT:0x100000000 -bpD:0x110000000 -bhalt:5 /lib⇒
  /crt0_64.o -lg -bexport:/usr/lib/libg.exp -o PTPCURND PTPCURND.o -brtl -bE⇒
  symlist.
exp -lpthreads -ldl -lnsl -L/home/sphilli2/852-803-I1-AIX-ORAU-DEBUG/bin -⇒
  lpscompat_ansi -lpssqlapi_ansi -lpsuser_ansi -lpspetssl -lpsora_ansi -⇒
  lpscobnet_ansi -L/usr/lpp/cobol/lib -L/usr/lpp/SdU/vsam/lib -L/usr/lpp/Sd⇒
  U/sfs/lib -lcob2s -lsmrtlite -lC128 -lc -lc
unlink: PTPCURND.o
exec: /usr/lpp/cobol/bin/IGYCCOB2 -qtest -qdynamic -qaddr(64),flag(w),trunc⇒
  (bin),arith(extend) -qADDR(64) PTPDBTST.cbl
PP 5724-V62 IBM COBOL for AIX 3.1.0 in progress ...
LineID  Message code  Library phase message text
          IGYLI0090-W    4 sequence errors were found in this program.
Messages      Total      Informational      Warning      Error      Severe      ⇒
Terminating
Printed:           1                               1
LineID  Message code  Message text
          IGYSC0205-W    Warning message(s) were issued during library phase⇒
  processing. Refer to the beginning of the listing.
  588  IGYPA3007-S      "ZZ000-SQL-ERROR-ROUTINE" was not defined as a
                                procedure-name. The statement was discarded.

```

```

Messages      Total      Informational      Warning      Error      Severe      =>
Terminating
Printed:        2                      1                      1
Suppressed:     6                      6
End of compilation 1,  program PTPDBTST,  highest severity: Severe.
Return code 12
PTPDBTST fail to compile/link

```

Reviewing COBOL_PROGRAM.LST files

The COBOL_PROGRAM.lst files are located in `<PS_HOME>/sdk/cobol/pscbi<APPS>/lst` directory and contain the compiler output for a specific program.

For example, a portion of the PTPDBTST.lst file contains this compilation error found for program PTPDBTST, where the ZZ000-SQL-ERROR-ROUTINE was not defined:

```

588  IGYPA3007-S  "ZZ000-SQL-ERROR-ROUTINE" was not defined as a
procedure-name.  The statement was discarded.
-
Messages      Total      Informational      Warning      Error      Severe      =>
Terminating
0Printed:        2                      1                      1
0Suppressed:     6                      6
-* Statistics for COBOL program PTPDBTST:
*   Source records = 805
*   Data Division statements = 213
*   Procedure Division statements = 52

```

Reviewing temporary space errors

IBM COBOL compiler uses the system temporary space to do some steps of the compilation. Like other UNIX processes, the compiler may give errors when the system temporary space is full.

To avoid or correct this problem, clean up the system temporary space on your machine.

Here is a sample of errors seen during compilation, when the system temporary space (/tmp) was full in a development AIX machine:

```

pscbibm.mak : Compiling EGPPRCTL.cbl ...
IGYDS5247-U  An error occurred while attempting to write a compiler work=>
file, "SYSUT7".
Compiler aborted with code 1247
IGYSI5258-U  Error removing WCode file.: A file or directory in the path=>
name does not exist.
IGYSI5258-U  Error removing WCode file.: A file or directory in the path=>
name does not exist.
IGYSI5259-U  Error closing WCode file.: A file descriptor does not refer=>
to an open file.
IGYSI5258-U  Error removing WCode file.: A file or directory in the path=>
name does not exist.
IGYSI5259-U  Error closing WCode file.: A file descriptor does not refer=>
to an open file.
IGYSI5258-U  Error removing WCode file.: A file or directory in the path=>

```

```

name does not exist.
IGYSI5259-U   Error closing WCode file.: A file descriptor does not refer⇒
to an open file.
IGYSI5258-U   Error removing WCode file.: A file or directory in the path⇒
name does not exist.
IGYSI5259-U   Error closing WCode file.: A file descriptor does not refer⇒
to an open file.

```

Task 10B-5-5: Setting Up the IBM COBOL Runtime

This section discusses:

- Installing the IBM COBOL for AIX Runtime Files
- Setting Environment Variables for a PS_APP_HOME or PS_CUST_HOME Setup
- Configuring the Application Server Domain
- Configuring the Process Scheduler Domain

Installing the IBM COBOL for AIX Runtime Files

For those machines that only need to run the compiled COBOL files, you must have obtained the installation file from IBM and installed the cobol runtime components on your system. You do not need to install the compiler. You must also configure the PeopleSoft Application Server and Process Scheduler domains.

See Installing IBM COBOL on IBM AIX.

Setting Environment Variables for a PS_APP_HOME or PS_CUST_HOME Setup

This section applies to those installations in which:

- You have several Application Server or Process Scheduler domains.
- Each of those domains is going to be associated with a particular *PS_APP_HOME* or *PS_CUST_HOME* directory.

In this case it is a good idea to define *PS_APP_HOME* or *PS_CUST_HOME* in *PS_HOME/psconfig.sh*. For example, edit *psconfig.sh* to add one of these lines:

```

PS_APP_HOME="/home/psft/HRcompile"; export PS_APP_HOME
PS_CUST_HOME="/home/psft/CUSTcompile"; export PS_CUST_HOME

```

After making this change, you must source the *PS_HOME/psconfig.sh* file again.

This way you would not need to add the *PS_APP_HOME* or *PS_CUST_HOME* environment variable through the "Edit environment variable" Application Server and Process Scheduler administration menus in PSADMIN each time you create a new domain.

Configuring the Application Server Domain

This section assumes that you have created an Application Server domain, as described in the chapter "Configuring the Application Server on UNIX." The configuration and log files for application server domains reside in a directory referred to as *PS_CFG_HOME*.

See the information on working with *PS_CFG_HOME* in the *PeopleTools: System and Server Administration* product documentation.

Note. You must create a new domain to configure the environment for running IBM COBOLs. You will not be able to reuse an existing domain for the same.

To create and configure the Application Server domain:

1. Go to the *PS_HOME/appserv* directory and run `psadmin`.
2. When the menu appears, specify *1* for Application Server and press ENTER.
3. Enter *2* for Create a Domain, and press ENTER.
4. Specify the domain name. For example:

```
Please enter name of domain to create : HCM92
```

Note. If you have already set the environment variables *PS_APP_HOME* and/or *PS_CUST_HOME*, as explained in the section Setting Environment Variables for a *PS_APP_HOME* or *PS_CUST_HOME* Setup, you can skip the steps 5 through 10.

5. On the Quick-configure menu, select *16*, Edit environment settings.
6. If *PS_APP_HOME* is different from *PS_HOME*, carry out steps a and b below.

Note. If *PS_APP_HOME* is the same as *PS_HOME*, skip these two steps and continue with step 7.

- a. On the PeopleSoft Domain Environment Settings, select *2* to add environment variable.
- b. Enter *PS_APP_HOME* as the name of the environment variable, and installation directory where you installed your PeopleSoft Application software as the value of the environment variable. For example:

```
Enter name of environment variable: PS_APP_HOME
Enter value: /home/psft/HRcompile
```

You will see an asterisk (*) in front of the modified environment variables, because these variables have not been saved.

7. If your *PS_CUST_HOME* is defined and is different from *PS_HOME*, carry out the following two steps:

Note. If *PS_CUST_HOME* is the same as *PS_HOME*, skip these two steps and continue with step 8.

- a. On the PeopleSoft Domain Environment Settings, select *2* to add environment variable.
- b. Enter *PS_CUST_HOME* as the name of the environment variable, and the installation directory where you installed the customized COBOL files as the value of the environment variable.

For example:

```
Enter name of environment variable: PS_CUST_HOME
Enter value: /home/psft/CUSTcompile
```

You will see an asterisk in front of the *PS_APP_HOME* and *PS_CUST_HOME* environment variables, indicating that these variables have not been saved.

8. Specify *6* to save the environment variables.
9. Press ENTER to continue at the following message:

```
Your changes have been saved.
```

```
Please be aware these changes will not take effect until you complete⇒
```

```
the domain configuration process.
Press Enter to continue...
```

10. Enter *q* for return to the previous menu.
11. On the Quick-configure menu, enter *15*, for Custom configuration.
12. Answer *n* (no) when asked if you want to change the values, until you see the section Remote Call.

```
Values for config section - RemoteCall
COBOL Platform=
RCCBL Redirect=0
RCCBL PRDBIN=%PS_HOME%\cblbin%PS_COBOLTYPE%
Do you want to change any values (y/n/q)? [n]: y
```

Enter *y* (yes) to make a change, as shown in this example.

13. Enter *IBM* as the COBOL platform and ignore the remaining options.

```
COBOL Platform [] : IBM
```

14. Answer *n* (no) when asked if you want to change any of the remaining sections.
15. Enter *1* to boot the domain.
16. Enter *1* for Boot (Serial Boot), or *2* for Parallel Boot.

Configuring the Process Scheduler Domain

To create and configure the Process Scheduler domain:

Note. You must create a new domain to configure the environment for running IBM COBOLs. You will not be able to reuse an existing domain for the same.

1. Go to the *PS_HOME/appserv* directory and run *psadmin*.
2. When the menu appears, specify *2* for Process Scheduler and press ENTER.
3. Enter *2* for Create a Domain.
4. Specify the domain name. For example:

```
Please enter name of domain to create : HCM92
```

Note. Domain names are case-sensitive and must be eight characters or less.

Note. If you have already set the environment variables *PS_APP_HOME* and/or *PS_CUST_HOME*, as explained in the section Setting Environment Variables for a *PS_APP_HOME* or *PS_CUST_HOME* Setup, you can skip the steps 5 through 10.

5. On the Quick-configure menu, select *7*, Edit environment settings.
6. If *PS_APP_HOME* is different from *PS_HOME*, carry out steps a and b below.

Note. If *PS_APP_HOME* is the same as *PS_HOME*, skip these two steps and continue with step 7.

- a. On the PeopleSoft Domain Environment Settings, select *2* to add environment variable.
- b. Enter *PS_APP_HOME* as the name of the environment variable, and the installation directory where you installed your PeopleSoft Application software as the value of the environment variable.

For example:

Enter name of environment variable: PS_APP_HOME

Enter value: /home/psft/HRcompile

7. If your *PS_CUST_HOME* is different from *PS_HOME*, carry out the following two steps.

Note. If *PS_CUST_HOME* is the same as *PS_HOME*, skip these two steps and continue with step 8.

- a. On the PeopleSoft Domain Environment Settings, select 2 to add an environment variable.
- b. Enter PS_CUST_HOME as the name of the environment variable, and the installation directory where you installed your PeopleSoft Application software as the value of the environment variable.

For example:

Enter name of environment variable: PS_CUST_HOME

Enter value: /home/psft/CUSTcompile

8. Enter 6 to save the environment variables.

9. Press ENTER to continue at the following message:

Your changes have been saved.

Please be aware these changes will not take effect until you complete⇒
the domain configuration process.

Press Enter to continue...

10. Enter *q* to return to the previous menu.

11. On the Quick-configure menu, enter 6, for Custom configuration.

12. Answer *n* (no) when asked if you want to change the values, until you see the section Remote Call.

Values for config section - RemoteCall

COBOL Platform=

RCCBL Redirect=0

RCCBL PRDBIN=%PS_HOME%\cblbin%PS_COBOLTYPE%

Do you want to change any values (y/n/q)? [n]: **y**

Enter *y* (yes) to make a change, as shown in this example.

13. Enter *IBM* as the COBOL Platform and ignore the remaining options.

COBOL Platform [] : **IBM**

14. Answer *n* (no) when asked if you want to change any of the remaining sections.

15. Enter *1* to boot the domain.

Task 10B-5-6: Removing the IBM COBOL Installation

Before you remove the IBM COBOL compiler on IBM AIX, review the requirements in the IBM documentation. Follow the uninstalling instructions in the IBM COBOL for AIX installation guide.

See IBM Knowledge Center, COBOL for AIX v5.1 Documentation,

https://www.ibm.com/support/knowledgecenter/SS6SGM_5.1.0/com.ibm.cobol51.aix.doc/welcome.html.

Chapter 11

Installing Web Server Products

This chapter discusses:

- Installing Oracle WebLogic Server

Task 11-1: Installing Oracle WebLogic Server

This section discusses:

- Understanding the Oracle WebLogic Installation
- Reviewing Troubleshooting Tips
- Obtaining Oracle WebLogic Installation Files from Oracle Software Delivery Cloud
- Installing JDK
- Installing Oracle WebLogic on Microsoft Windows
- Installing Oracle WebLogic on UNIX in Silent Mode
- Configuring JDK for Daylight Savings Time Change
- Removing the Oracle WebLogic Installation on Microsoft Windows
- Removing the Oracle WebLogic Installation on UNIX

Understanding the Oracle WebLogic Installation

PeopleSoft PeopleTools 8.57 supports Java 8 enabled 64-bit Oracle WebLogic Server 12.2.1.3.0. You must install an operating-system specific Java Developers Kit (JDK) before beginning the Oracle WebLogic installation.

See Installing JDK for Oracle WebLogic.

Note. Oracle supports a number of versions of UNIX and Linux in addition to Microsoft Windows for the PeopleSoft installation. Throughout this book, there are references to operating systems. Where necessary, this book refers to specific operating systems by name (for example, Oracle Solaris, IBM AIX, or HP-UX Itanium, or Linux); however, for simplicity the word UNIX is often used to refer to all UNIX-like operating systems, including Linux.

This section describes a traditional installation of Oracle WebLogic. When you use the PeopleSoft DPKs for either a full-tier installation using the PeopleSoft Application Images or for a mid-tier installation using the PeopleTools DPKs, Oracle WebLogic is installed as part of the installation, and you do not need to carry out the separate installation in this section. If you choose to install Oracle WebLogic independently of the DPK installation, you can obtain installation files for Oracle WebLogic on the Oracle Software Delivery Cloud portal and use the steps in this section.

See Obtaining Oracle WebLogic Installation Files from Oracle Software Delivery Cloud.

Note that to use a separate Oracle WebLogic installation with a DPK deployment, you must use customizations to specify the Oracle WebLogic installation location.

See "Completing the DPK Initialization with Customizations," Preparing the Customization File for Component Software Locations.

To familiarize yourself with the most current support information and information about any required Oracle WebLogic service packs based on operating system platform or PeopleSoft PeopleTools versions, consult the Certifications area of My Oracle Support.

See Also

Oracle Software Delivery Cloud, <http://edelivery.oracle.com>

My Oracle Support, Certifications

Clustering and High Availability for PeopleTools, My Oracle Support, (search for the article title)

Operating System, RDBMS, and Additional Component Patches Required for Installation PeopleTools, My Oracle Support, (search for the article title and release number)

Oracle WebLogic Server 12.2.1.3.0 documentation, <http://docs.oracle.com/middleware/12213/wls/index.html>

Reviewing Troubleshooting Tips

If you have trouble with the installation, review these tips:

- It can require up to 800 MB space to install Oracle WebLogic. If there is not enough space, the installer displays an error with information about the space limitation. You will need to exit the installation and create some space under your home directory before starting over.
- The Oracle WebLogic installer makes use of the default system temporary space. It will stop and display an error message if the temporary space is not sufficient. Clean up the default system temp space and try again. If you do not have the privilege to clean up that directory and need to proceed, the workaround is to set aside a directory under your Home directory and use it as the temporary space. This can be achieved by setting -Djava.io.tmpdir in the command for launching the installer.

The following command is a sample Linux command for silent mode installation, which uses the "temp" directory under your Home directory. *RESPONSE_DIR* refers to the location of the silent mode response file, and *INVENTORY_DIR* refers to the location of the Oracle inventory file.

See Installing Oracle WebLogic on UNIX in Silent Mode.

```
$JAVA_HOME/bin/java -jar -Djava.io.tmpdir=~/.temp ./fmw_12.2.1.3.0_>
wls.jar -silent -responseFile RESPONSE_DIR/res.rsp -invPtrLoc INVENTORY_>
DIR/oraInst.loc
```

Note. This workaround may not be applicable on all platforms. If you tried and the installer still errors out due to the amount of temporary space, contact your system administrator to clean up the system temporary space before proceeding.

- If the installation fails, and the Middleware Home directory that you specified for the Oracle WebLogic 12.2.1.3.0 installation is one in which other Oracle products have been installed in previous releases, (for example c:\oracle folder in Microsoft Windows), it may indicate corruption in the registry.xml file inside your existing Middleware Home. Pick a different location for the Oracle WebLogic 12.2.1.3.0 installation directory and try the installation again.
- If you are installing onto a UNIX environment, in case of installation failure, refer to the log file

Wls1221Install.log under the installation logs directory to view the events that occurred.

- If you encounter the following error message while running in console mode on a Microsoft Windows operating system, it means an environment variable `_JAVA_OPTIONS` has been set in your system. It causes the Java process initiated by the Oracle WebLogic installer to fail.

```
ERROR: JVMPI, an experimental interface, is no longer supported.
Please use the supported interface: the JVM Tool Interface (JVM TI).
```

To resolve the problem, remove the environment variable `_JAVA_OPTIONS` from your system and rerun the installation.

- If you encounter the following error message while installing on an Oracle Solaris operating system, it means there is a problem with access to the temporary directory:

```
*sys-package-mgr*: can't write cache file
```

This message appears because the Oracle WebLogic installer creates a temporary directory (for example, on Oracle Solaris it is `/var/tmp/wlstTemp`) that is shared by all users, and it is unable to differentiate between users. As a result, access to the directory is blocked when the user accessing the directory is not the one who originally created the directory. The workaround for this problem is to remove the installation and install it again after manually adjusting the temporary directory permissions. A user with superuser privileges can use the following command to adjust the permissions:

```
chmod -R 777 /var/tmp/wlstTemp
```

For more information, search the Oracle documentation for Oracle WebLogic.

Task 11-1-1: Obtaining Oracle WebLogic Installation Files from Oracle Software Delivery Cloud

At this point you should have already downloaded the necessary files from Oracle Software Delivery Cloud. If not, this section includes additional information on finding and using the files for Oracle WebLogic if necessary.

See "Preparing for Installation," Using Oracle Software Delivery Cloud to Obtain Installation Files.

See Oracle Software Delivery Cloud, <https://edelivery.oracle.com>.

To obtain the files for Oracle WebLogic installation:

1. After logging in to Oracle Software Delivery Cloud, read the information about export restrictions, and then click Accept.
2. Enter Oracle WebLogic in the Product field, and select Oracle WebLogic Server Enterprise Edition (FMW, WLS, WebLogic Server 12c), from the drop-down list.

Note. The Enterprise Edition includes Oracle WebLogic Server and Oracle Coherence, as well as other items.

3. Click Select Platform, select the operating system you are running on, and click Select.

The following operating systems are supported:

- IBM AIX
 - HP-UX
 - Linux
 - Microsoft Windows
 - Oracle Solaris
4. Click Continue.

- On the page listing the selected product, click Continue.

Note. Click the arrow to view the list of products included.

- Read the license agreements, and select the check box to acknowledge that you accept the agreement, and then click Continue.
- Click Continue on the Download Queue page.
- On the File Download window, download the zip files for Oracle WebLogic Server and Oracle Coherence.

Download the files you need by clicking a file name to download an individual file, or click Download All to obtain all of the files listed.

Save the zip files to a temporary directory on your local system. The directory where you save the zip file is referred to in this documentation as *WLS_INSTALL*. You must extract (unzip) the file on the platform for which it is intended. For example, if you download the zip file for Oracle Solaris, you must unzip it on Oracle Solaris to avoid problems. If you unzip the file to a staging directory on a Microsoft Windows computer and copy the staging directory to an Oracle Solaris, the stage area files may be corrupt.

- Extract the files into *WLS_INSTALL*.

The Oracle WebLogic installer file is `fmw_12.2.1.3.0_wls.jar`.

Note. If you need to FTP the downloaded file, make sure to FTP it in Binary mode.

Task 11-1-2: Installing JDK

This section discusses:

- Understanding the JDK Requirement for Oracle WebLogic
- Installing JDK for IBM AIX
- Installing JDK for HP-UX Itanium
- Installing JDK for Linux
- Installing JDK for Microsoft Windows
- Installing JDK for Oracle Solaris on SPARC

Understanding the JDK Requirement for Oracle WebLogic

Before beginning the Oracle WebLogic installation you must install the 64-bit Java 8 JDK. The specific JDK required depends upon the operating system and vendor, as described in this table:

Operating System Platforms	JDK Version Supported	64-bit or Mixed Mode*
IBM AIX	IBM JDK 8.0 SR5 FP15	64-bit
HP-UX Itanium	Java version "1.8.0.14-hp-ux"	Mixed mode Use "-d64" to run in 64-bit mode.
Linux	Oracle JDK 1.8.0_171+	64-bit
Microsoft Windows	Oracle JDK 1.8.0_171+	64-bit

Operating System Platforms	JDK Version Supported	64-bit or Mixed Mode*
Oracle Solaris on SPARC	Oracle JDK 1.8.0_171+	64-bit

* The mixed mode installer runs in 32-bit by default. The parameter *-d64* is required to run them in 64-bit mode.

Installing JDK for IBM AIX

To install 64-bit IBM JDK for IBM AIX:

1. Go to the IBM JDK download and service site:

<http://www.ibm.com/developerworks/java/jdk/aix/service.html>

Note. You need a user name and password for downloading IBM JDK. If you don't have the required credentials, your AIX support personnel should be able to help.

2. Select the link for Java 8 64-bit under Java SE Version 8.
3. Provide the required information to sign in.
4. Install the JDK on the AIX computer where you will install the Oracle WebLogic server.

The directory where you install the JDK is referred to in this documentation as *JAVA_HOME*.

Note. Spaces are not allowed in the *JAVA_HOME* name.

Installing JDK for HP-UX Itanium

To install Hewlett-Packard JDK on HP-UX Itanium:

1. Go to the Hewlett-Packard Downloads and Documentation site.

See JDK/JRE 8.0.x Downloads and Documentation,

<https://h20392.www2.hp.com/portal/swdepot/displayProductInfo.do?productNumber=HPUXJDKJRE80>.

2. Select the link for Version 8.0.14 or higher.
3. Provide the required information to sign in.
4. Click Next and download JDK.
5. Install the JDK on the computer where you will install the Oracle WebLogic server, following the instructions in the Hewlett-Packard documentation.

The directory where you install the JDK is referred to in this documentation as *JAVA_HOME*.

Note. Spaces are not allowed in the *JAVA_HOME* name.

Installing JDK for Linux

To install 64-bit JDK on Linux:

1. Go to the Oracle Java download site:

<http://www.oracle.com/technetwork/java/javase/downloads/index.html>

2. Download Oracle Java 8 64-bit JDK version 1.8.0_171 or higher for Linux x86-64.

Refer to the JDK installation instructions at the following link:

http://docs.oracle.com/javase/8/docs/technotes/guides/install/linux_jdk.html#BJFGGEFG

3. Install the JDK on the computer where you will install the Oracle WebLogic server. The directory where you install the JDK is referred to in this documentation as *JAVA_HOME*.

Note. Spaces are not allowed in the *JAVA_HOME* name.

Installing JDK for Microsoft Windows

To install 64-bit JDK on Microsoft Windows:

1. Go to the Oracle JDK download site:

<http://www.oracle.com/technetwork/java/javase/downloads/index.html>

2. Download Oracle Java 8 64-bit JDK version 1.8.0_171 or higher for Microsoft Windows x86-64.

Refer to the JDK installation instructions at the following link:

http://docs.oracle.com/javase/8/docs/technotes/guides/install/windows_jdk_install.html#CHDEBCCJ

3. Install the JDK on the computer where you will install the Oracle WebLogic server. The directory where you install the JDK is referred to in this documentation as *JAVA_HOME*.

Note. Spaces are not allowed in the *JAVA_HOME* name.

Installing JDK for Oracle Solaris on SPARC

To install JDK on Oracle Solaris on SPARC (64-bit):

1. Go to the Oracle JDK download site:

<http://www.oracle.com/technetwork/java/javase/downloads/index.html>

2. Download the Oracle Java 8 64-bit JDK version 1.8.0_171 or higher for Solaris SPARC.

Refer to the installation instructions at the following link:

http://docs.oracle.com/javase/8/docs/technotes/guides/install/solaris_jdk.html#CHDBJEFD

3. Install the JDK on the computer where you will install the Oracle WebLogic server.

The directory where you install the JDK is referred to in this documentation as *JAVA_HOME*.

Note. Spaces are not allowed in the *JAVA_HOME* name.

Task 11-1-3: Installing Oracle WebLogic on Microsoft Windows

The following procedure assumes that you saved the installation file *fmw_12.2.1.3.0_wls.jar* from Oracle Software Delivery Cloud in the directory *WLS_INSTALL*. Installation in GUI mode is normally used for Microsoft Windows operating systems. You should have installed the appropriate JDK to *JAVA_HOME* before beginning this installation.

See Installing JDK for Oracle WebLogic.

Note. Previous releases of Oracle WebLogic Server, such as 9.2 MPX, and 10.3.X, can coexist with 12.2.1.3.0 on a single machine. The best practice is to install Oracle WebLogic 12.2.1.3.0 into an empty directory, or at least one that does not contain other Oracle WebLogic (previously BEA) products.

If you choose, however, to install this version of Oracle WebLogic in an existing *WLS_HOME* directory (for example, c:\oracle), you must shut down all instances of Oracle WebLogic Server running in that *WLS_HOME* before performing this installation.

To install Oracle WebLogic Server 12.2.1.3.0:

1. Open a command prompt and change directory to *WLS_INSTALL*.

Note. If you are running on a Microsoft Windows operating system, you must run the command prompt as administrator.

2. Set the environment variable *JAVA_HOME* to be the location where you installed the Oracle Java JDK 1.8. For example, if you installed JDK to D:\jdk1.8.0_171 use this command:

```
set JAVA_HOME=D:\jdk1.8.0_171
```

3. Use the following command to launch the installer:

```
%JAVA_HOME%\bin\java -jar fmw_12.2.1.3.0_wls.jar
```

Note. It may take up to five minutes to extract the installer. You see system check messages during the extraction process. The Welcome window appears when the extraction is complete.

4. Click Next on the Welcome window for Oracle Fusion Middleware 12c (12.2.1.3.0) WebLogic Server and Coherence Installer.



Oracle Fusion Middleware 12c WebLogic Server and Coherence Installation - Step 1 of 8

5. Select the Skip Auto Updates radio button.

Oracle Fusion Middleware 12c WebLogic Server and Coherence Installation - Step 2 of 8

Auto Updates

ORACLE[®]
FUSION MIDDLEWARE

- Welcome
- Auto Updates**
- Installation Location
- Installation Type
- Prerequisite Checks
- Installation Summary
- Installation Progress
- Installation Complete

☒ Skip Auto Updates

☐ Select patches from directory

Location:

☐ Search My Oracle Support for Updates

Username:


Password:

Oracle Fusion Middleware 12c WebLogic Server and Coherence Installation - Step 2 of 8

6. On the Installation Location window, enter a location for the Oracle Home, or browse to an existing directory. Do not choose a directory that contains an existing installation of Oracle WebLogic.


If the directory does not exist, the Oracle WebLogic installer creates it. The directory where you install Oracle WebLogic is referred to as *WLS_HOME* in this documentation. In this example *WLS_HOME* is C:\WLS122130.

Click Next to continue.



Oracle Fusion Middleware 12c WebLogic Server and Coherence Installation - Step 3 of 8


7. Accept the default WebLogic Server installation option on the Installation Type window, for WebLogic Server Installation, and then click Next.



Oracle Fusion Middleware 12c WebLogic Server and Coherence Installation - Step 4 of 8

8. Wait while the installer carries out prerequisite checks, and then click Next.

In this example the system passed the prerequisite checks.




Oracle Fusion Middleware 12c WebLogic Server and Coherence Installation - Step 5 of 8

9. Verify your choices in the installation summary, such as the installation location and features to install.


If you want to save a response file to be used in silent installation, click Save Response File and provide a location.

Click Install to begin the installation.




Oracle Fusion Middleware 12c WebLogic Server and Coherence Installation - Step 6 of 8

A progress indicator appears. Click Next when the tasks are complete, as shown in this example:



Oracle Fusion Middleware 12c WebLogic Server and Coherence Installation - Step 7 of 8

10. When the installation has completed successfully, clear the Automatically Launch the Configuration Wizard option, and click Finish.



Oracle Fusion Middleware 12c WebLogic Server and Coherence Installation - Step 8 of 8

Task 11-1-4: Installing Oracle WebLogic on UNIX in Silent Mode

Use these instructions for silent mode installation for UNIX operating systems. With silent mode installation, you provide the required settings in a response file.

Note. Console mode installation is not supported for Oracle WebLogic 12.2.1.3.0.

See the information on silent installation for Oracle WebLogic in the Oracle Middleware documentation.

The following procedure assumes that you saved the installation file `fmw_12.2.1.3.0_wls.jar` from Oracle Software Delivery Cloud in the directory `WLS_INSTALL`. You should have installed the appropriate JDK to `JAVA_HOME` before beginning this installation.

Note. If you downloaded the zip file for the Oracle WebLogic installation from Oracle Software Delivery Cloud to a Microsoft Windows computer, FTP the zip file in binary mode to your UNIX computer before unzipping it into `WLS_INSTALL`.

To run the Oracle WebLogic installation in silent mode:

1. Change directory to *WLS_INSTALL* and make the installer file executable using the following command:

```
chmod a+x fmw_12.2.1.3.0_wls.jar
```

2. In a shell window, change directory to *WLS_INSTALL*:

```
cd WLS_INSTALL
```

3. Set *JAVA_HOME* to be the location where you installed the JDK.

For example, if the JDK is installed under "/home/jdklnk8u171", use the following command:

```
export JAVA_HOME=/home/jdklnk8u171
```

4. If it does not exist, use a text editor, such as "vi", to create the central inventory location file, named *oraInst.loc*, in a directory referred to in this documentation as *INVENTORY_DIR*.

The *oraInst.loc* file contains only the following two lines:

```
inventory_loc=/home/psftuser/oraInventory
inst_group=wlsgrp
```

The *oraInst.loc* file contains the following information:

- *inventory_loc* — Specify the full path to the directory where you want the installer to create the inventory directory. The location in the example is /home/psftuser/oraInventory. Use any directory other than the *WLS_INSTALL* directory where you placed the *fmw_12.2.1.3.0_wls.jar* file.
- *oui_install_group* — Specify the name of the group whose members have write permissions to this directory. The group name in the example is *wlsgrp*.

5. Copy the following content into a text editor and save it as *res.rsp*.

This is the silent response file. The directory where you save it is referred to here as *RESPONSE_DIR*.

```
[ENGINE]
```

```
#DO NOT CHANGE THIS.
```

```
Response File Version=1.0.0.0.0
```

```
[GENERIC]
```

```
#Set this to true if you wish to skip software updates
```

```
DECLINE_AUTO_UPDATES=true
```

```
#My Oracle Support User Name
```

```
MOS_USERNAME=
```

```
#My Oracle Support Password
```

```
MOS_PASSWORD=<SECURE VALUE>
```

```
#If the Software updates are already downloaded and available on your⇒
local system, then specify
```

```
the path to the directory where these patches are available and set⇒
```

```
SPECIFY_DOWNLOAD_LOCATION
```

```
to true
```

```
AUTO_UPDATES_LOCATION=
```



```
#Proxy Server Name to connect to My Oracle Support
SOFTWARE_UPDATES_PROXY_SERVER=
```

```
#Proxy Server Port
SOFTWARE_UPDATES_PROXY_PORT=
```

```
#Proxy Server Username
SOFTWARE_UPDATES_PROXY_USER=
```

```
#Proxy Server Password
SOFTWARE_UPDATES_PROXY_PASSWORD=<SECURE VALUE>
```

```
#The oracle home location. This can be an existing Oracle Home or a new⇒
Oracle Home
ORACLE_HOME=
```

```
#Set this variable value to the Installation Type selected. e.g. Web⇒
Logic Server, Coherence,
Complete with Examples.
INSTALL_TYPE=WebLogic Server
```

6. Use a text editor to enter the full path for ORACLE_HOME; for example:

```
#The oracle home location. This can be an existing Oracle Home or a new⇒
Oracle Home
ORACLE_HOME=/home/wls122130
```

Oracle WebLogic will be installed into the ORACLE_HOME directory entered here. This must be a new directory; do not enter a directory that has been used previously.

7. If this is the first time you are installing on your system (meaning there is no pre-existing Oracle inventory location), use the following commands to perform a silent installation.

These commands use res.rsp as the name for the response file.

- For IBM AIX, Linux, or Oracle Solaris on SPARC:

```
$JAVA_HOME/bin/java -jar ./fmw_12.2.1.3.0_wls.jar -silent -response⇒
File RESPONSE_DIR/res.rsp -invPtrLoc INVENTORY_DIR/oraInst.loc
```

- For HP-UX Itanium, the JVM parameter "-d64" is required:

```
$JAVA_HOME/bin/java -d64 -jar ./fmw_12.2.1.3.0_wls.jar -silent -⇒
responseFile RESPONSE_DIR/res.rsp -invPtrLoc INVENTORY_DIR/ora⇒
Inst.loc
```

8. If you have previously installed an Oracle product on your system and do not need to specify an Oracle inventory location, use the following commands to perform a silent installation:

- For IBM AIX, Linux, or Oracle Solaris on SPARC:

```
$JAVA_HOME/bin/java -jar ./fmw_12.2.1.3.0_wls.jar -silent -response⇒
File RESPONSE_DIR/res.rsp
```

- For HP-UX Itanium, the JVM parameter "-d64" is required:

```
$JAVA_HOME/bin/java -d64 -jar ./fmw_12.2.1.3.0_wls.jar -silent -⇒
responseFile RESPONSE_DIR/res.rsp
```

9. After you enter the appropriate command from the previous steps, the installer is launched in silent mode, and a progress indicator tracks the installation.

When the installation is complete, you should see a completion message such as "The installation of Oracle Fusion Middleware 12c WebLogic Server and Coherence 12.2.1.3.0 completed successfully."

Task 11-1-5: Configuring JDK for Daylight Savings Time Change

The version of JDK mentioned in the previous section Installing JDK for Oracle WebLogic includes the Daylight Saving Time (DST) rules available at the time of packaging. If new rules are implemented after this time, you should use the instructions in this section to update the time zone definition files.

You can skip this section unless a change to the DST rules has happened near or after the general availability date of Oracle WebLogic or PeopleSoft PeopleTools. Consult the information on configuring PeopleSoft time zone definitions in the *PeopleTools: Global Technology* product documentation.

This section provides an example of how the time zone updater utility (TZUPDATER), which is supplied by the JDK vendors, can be used to update the time zone definition files contained in the JDK used by Oracle WebLogic server.

1. Identify and shut down any JVM processes that are using the JDK that you will be updating.
2. For future reference or restoration, back up the location where the targeted JDK is located.

The JDK being used for different operating systems is different. For Oracle WebLogic 12.2.1.3.0, refer to the `commBaseEnv.cmd` (for Microsoft Windows), or `commBaseEnv.sh` (for UNIX) file under `WLS_HOME\oracle_common\common\bin` to determine the setting for `JAVA_HOME` and the exact name and location for the JDK being used by your Oracle WebLogic server. `WLS_HOME` is the directory where Oracle WebLogic is installed.

3. Download the appropriate updater utility for your operating system from the JDK vendor.

Each tzupdater provided by the vendor comes with instructions (typically in a readme file) describing how to:

- Locate the correct JDK.
- Apply classes using the tzupdater or provided scripts.
- Check tzupdater versions.

Read the instructions carefully as the steps and instructions are vendor-specific. Keep in mind that these instructions and versions may be updated when the vendor finds it necessary.

Note. After successfully running the TZUPDATER to update a JDK location, the changes will take effect only for newly started Java processes from that location. In the event that you did not identify and stop all Java processes running from this location, it will be necessary to stop and restart these for the changes to take effect.

See Also

Timezone Updater Tool, Oracle Technology Network, <http://www.oracle.com/technetwork/java/javase/tzupdater-readme-136440.html>


Task 11-1-6: Removing the Oracle WebLogic Installation on Microsoft Windows

To remove the Oracle WebLogic installation on Microsoft Windows (GUI mode):

1. Before running the deinstaller, stop all servers and processes associated with the Oracle home you are going to remove.


2. Change directory to the `WLS_HOME\oui\bin` folder and run the `deinstall.cmd` script.

You see one or two command prompts with progress messages, and then the Welcome window appears. `WLS_HOME` is the location where you installed your Oracle WebLogic 12.2.1.3.0, for example `C:\WLS122130`. Click Next on the Welcome window.



Oracle Fusion Middleware 12c Deinstallation - Step 1 of 4

3. Verify the components that you want to uninstall on the summary page (by default all components are selected as shown in this example).




Oracle Fusion Middleware 12c Deinstallation - Step 2 of 4

4. Click the Save Response File button and browse to a location to save the file, which you can use for a silent mode deinstallation at another time.


See Removing the Oracle WebLogic Installation on UNIX.

Click Deinstall. A progress indicator appears. Click Next when the tasks are complete, as shown in this example.



Oracle Fusion Middleware 12c Deinstallation - Step 3 of 4

- Click Finish on the Deinstallation Complete window.



Oracle Fusion Middleware 12c Deinstallation - Step 4 of 4

- Remove the `WLS_HOME` directory manually after the deinstallation.

Task 11-1-7: Removing the Oracle WebLogic Installation on UNIX

To remove the installation on UNIX, you run in console mode, and use a response file.

Note. The previous section, Removing the Oracle WebLogic Installation on Microsoft Windows, included a step in which you saved a response file. You can edit and use this response file for different operating system platforms.

To remove the Oracle WebLogic installation on UNIX in silent mode:

- Before running the deinstaller, stop all servers and processes associated with the Oracle home you are going to remove.
- If you need to create a response file, copy the following content into a text editor and save it.

This is the silent response file, referred to here as `RESPONSE_DIR/response.txt`.

```
[ENGINE]
```

```
#DO NOT CHANGE THIS.
Response File Version=1.0.0.0.0
```

```
[GENERIC]
```

```
#This will be blank when there is nothing to be de-installed in⇒
distribution level
SELECTED_DISTRIBUTION=WebLogic Server~12.2.1.3.0
```

```
#The oracle home location. This can be an existing Oracle Home or a new⇒
Oracle Home
ORACLE_HOME=
```

3. Edit the ORACLE_HOME line to add the location where you installed Oracle WebLogic 12.2.1.3.0; for example:

```
#The oracle home location. This can be an existing Oracle Home or a new⇒
Oracle Home
ORACLE_HOME=/home/wls122130
```

4. Change directory to *WLS_HOME*/oui/bin and locate the deinstall.sh script.
WLS_HOME is the location where you installed your Oracle WebLogic 12.2.1.3.0.

5. Run the following command.

For *INVENTORY_DIR*, specify the full directory path containing the Oracle installer inventory file, oraInst.loc.

See Installing Oracle WebLogic on UNIX in Silent Mode.

```
./deinstall.sh -silent -response RESPONSE_DIR/response.txt -invPtrLoc ⇒
INVENTORY_DIR/oraInst.loc
```

6. An indicator shows the progress of the removal process, followed by a completion message such as "The uninstall of Oracle Fusion Middleware 12c WebLogic Server and Coherence 12.2.1.3.0 completed successfully."
7. Remove the *WLS_HOME* directory manually to complete the deinstallation.

Chapter 12

Installing Additional Components

This chapter discusses:

- Reviewing Additional Components
- Installing Oracle Tuxedo

Reviewing Additional Components

Depending upon your PeopleSoft installation environment, you may need to install and configure software components that are not included with the PeopleSoft PeopleTools installation files, or which you acquire from vendors other than Oracle. Some of the components that are discussed in this installation guide include:

- Oracle Tuxedo

The installation of Oracle Tuxedo is required for a basic PeopleSoft PeopleTools installation, and is covered in this chapter.

- COBOL

COBOL is not needed for PeopleSoft PeopleTools or for PeopleSoft Applications that contain no COBOL programs. Check My Oracle Support for details about whether your application requires COBOL.

See "PeopleSoft Enterprise Frequently Asked Questions About PeopleSoft and COBOL Compilers," My Oracle Support, Doc ID 747059.1.

See "PeopleSoft Enterprise Frequently Asked Questions About PeopleSoft and the IBM COBOL Compiler," My Oracle Support, Doc ID 1211907.1.

The installation and configuration of Micro Focus and IBM COBOL compilers are covered in later chapters.

See "Installing and Configuring COBOL on UNIX."

See "Installing and Configuring COBOL on Windows."

- Elasticsearch

Elasticsearch is the search engine for the PeopleSoft Search Framework for the current release. Oracle provides Elasticsearch as deployment packages (DPKs) for Microsoft Windows and Linux that deliver the required Elasticsearch software version, Java-based plug-ins needed for integration with PeopleSoft environments, and customized code where required. Be sure to obtain and use the Elasticsearch DPKs provided for use with the PeopleSoft installation.

See Elasticsearch Home Page, My Oracle Support, Doc ID 2205540.2.

Note. Oracle Secure Enterprise Search (SES) and Verity are not supported for the current release.

Note. Use the My Oracle Support Certifications area to determine the latest certified versions of additional components that are supported for the PeopleSoft PeopleTools release you are installing.

Task 12-1: Installing Oracle Tuxedo

This section discusses:

- Understanding Oracle Tuxedo
- Prerequisites
- Debugging the Oracle Tuxedo Installer
- Obtaining the Oracle Tuxedo Installation Files from Oracle Software Delivery Cloud
- Obtaining the Oracle Tuxedo Patches from My Oracle Support
- Removing Existing Oracle Tuxedo Installations from Microsoft Windows (Optional)
- Designating the Application Server Administrator on Microsoft Windows
- Installing Oracle Tuxedo on Microsoft Windows in GUI Mode
- Installing the Oracle Tuxedo Patch on Microsoft Windows
- Installing Oracle Tuxedo on Microsoft Windows in Silent Mode
- Uninstalling the Oracle Tuxedo Patch on Microsoft Windows
- Uninstalling Oracle Tuxedo in GUI Mode
- Checking the Windows Service Account
- Restricting Domain Process Privileges
- Setting Up the Windows Services for Oracle Tuxedo
- Verifying the Server Installation on Microsoft Windows
- Removing Existing Oracle Tuxedo Installations from UNIX (Optional)
- Completing the Preinstallation Checklist on UNIX
- Designating the Oracle Tuxedo Owner on UNIX
- Installing Oracle Tuxedo in Silent Mode on UNIX
- Installing the Oracle Tuxedo Patch on UNIX
- Uninstalling the Oracle Tuxedo Patch from UNIX
- Uninstalling Oracle Tuxedo from UNIX Using Silent Mode
- Verifying the Server Installation on UNIX
- Ensuring that Oracle Tuxedo Coexists with Earlier Versions

Understanding Oracle Tuxedo

This section describes a traditional installation of Oracle Tuxedo. When you use the PeopleSoft DPKs for either a full-tier installation using the PeopleSoft Application Images or for a mid-tier installation using the PeopleTools DPKs, Oracle Tuxedo is installed as part of the installation, and you do not need to carry out the separate installation in this section. If you choose to install Oracle Tuxedo independently of the DPK installation, you can obtain installation files for Oracle Tuxedo on the Oracle Software Delivery Cloud portal and use the steps in this section.

Note that to use a separate Oracle Tuxedo installation with a DPK deployment, you must use customizations to specify the Oracle Tuxedo installation location.

See "Completing the DPK Initialization with Customizations," Preparing the Customization File for Component Software Locations.

The PeopleSoft application server uses the Oracle® Fusion Middleware product, Oracle Tuxedo, to perform transaction management, messaging, and administration. This task guides you through the installation of Oracle Tuxedo on your server. It is essential that you install Oracle Tuxedo 64-bit, version 12c Release 2 (12.2.2.0), which is available on Oracle Software Delivery Cloud. You need to install Oracle Tuxedo before you go any further in setting up your application server and your PeopleSoft Pure Internet Architecture. After you perform the installation described here, you will configure the application server environment to incorporate Oracle Tuxedo with the PeopleSoft components.

Oracle supports Oracle Tuxedo 12c Release 2 (64-bit) for UNIX, and Oracle Tuxedo 12c Release 2 (64-bit) with MS Visual Studios 2015 for Microsoft Windows, with PeopleSoft PeopleTools 8.57.

Note. Oracle supports a number of versions of UNIX and Linux in addition to Microsoft Windows for the PeopleSoft installation. Throughout this book, there are references to operating systems. Where necessary, this book refers to specific operating systems by name (for example, Oracle Solaris, IBM AIX, HP-UX Itanium, or Linux); however, for simplicity the word UNIX is often used to refer to all UNIX-like operating systems, including Linux.

The minimum patch level certified for running Oracle Tuxedo 12c Release 2 with PeopleSoft PeopleTools 8.57 is Rolling Patch 23 (RP023). These installation instructions include the installation of the base Oracle Tuxedo 12c Release 2, followed by the patch installation.

Note. Oracle Tuxedo 12c Release 2 for Linux operating systems supports Exalogic optimizations.

For PeopleSoft customers running on Oracle Exalogic Elastic Cloud, we strongly recommend the use of the Exalogic OVM Template for PeopleSoft.

See Oracle's PeopleSoft Virtualization Products, My Oracle Support, Doc ID 1538142.1.

Note. For the sake of brevity and convenience, this documentation shortens "Oracle Tuxedo 12c Release 2 (64-bit)" to "Oracle Tuxedo 12cR2" and "Oracle Tuxedo 12c Release 2 (64-bit) with MS Visual Studios 2015" to "Oracle Tuxedo 12cR2_VS2015."

If you have a previous version of Oracle Tuxedo installed, you need to install the new version of Oracle Tuxedo, and re-create your application server domains. (You must create your domains using PSADMIN; you cannot migrate existing domains.) You can also use the PSADMIN domain import utility.

You can install Oracle Tuxedo once for each release on a machine, regardless of the number of PeopleSoft applications or databases the server supports. For example, if you installed Oracle Tuxedo 10gR3 for an earlier release of your PeopleSoft application, you may install Oracle Tuxedo 12cR2 on the same machine in a separate directory. For example:

On Microsoft Windows, you may install into C:\oracle\tuxedo10gR3_VS2008 and C:\oracle\tuxedo12.2.2.0.0_VS2015.

On UNIX, you may install into /home/oracle/tuxedo10gR3 and /home/oracle/tuxedo12cR2.

If more than one PeopleSoft application uses the same Oracle Tuxedo version (that is, the same patch level), then it is recommended that you have a single installation of Oracle Tuxedo to serve all the supported PeopleSoft applications. A single Oracle Tuxedo installation simplifies future maintenance (such as applying patches). However, if you choose to have more than one Oracle Tuxedo installation (this scenario is possible only on UNIX systems, as Oracle Tuxedo does not allow multiple installations of the same version of Oracle Tuxedo on Microsoft Windows), you must install and maintain the same Oracle Tuxedo version more than once in different directories.

See Also

Oracle Tuxedo Documentation on Oracle Technology Network,
<http://www.oracle.com/technetwork/middleware/tuxedo/documentation/index.html>

PeopleTools: Portal Technology

PeopleTools: System and Server Administration

Operating System, RDBMS, and Additional Component Patches Required for Installation PeopleTools, My Oracle Support (search for article name and select the release)

Clustering and High Availability for PeopleTools, My Oracle Support (search for title)

Using OVM Templates for PeopleSoft on Exalogic, My Oracle Support (search for title)

Prerequisites

Before you begin to install Oracle Tuxedo, make sure that you have the following resources in place:

- Before beginning the Oracle Tuxedo installation you must install 64-bit Java 8 JDK.
The specific JDK required depends upon the operating system and vendor. Follow the instructions in the Oracle WebLogic section to install Java 8 JDK for your operating system.
See Installing JDK for Oracle WebLogic.
- TCP/IP connectivity (required for PeopleSoft PeopleTools 8.50 or higher) between the client machine and the application server
- For UNIX, you must have root access.
- Enough free disk space on the application server to install the product.
The disk space requirements vary by operating system. For free disk space requirements, see the Oracle Tuxedo documentation.

The Oracle Tuxedo installer uses the default system temporary space. If there is not enough space for installation, it will stop with an error. To specify a different temporary directory on Microsoft Windows, use the following command before starting the installer:

```
set IATEMPDIR=Complete_Path_Temp_Dir
```

Replace *Complete_Path_Temp_Dir* with the full path to the temporary directory that you want to use for the installation.

If you are sure you have enough space, but the installer still gives an error about low disk space (this usually happens on Linux), run the following command before starting the installer:

```
unset BLOCKSIZE
```

Debugging the Oracle Tuxedo Installer

If the Oracle Tuxedo installation fails with no error message, open a command prompt and enter the following command:

```
set LAX_DEBUG=1
```

After entering this command, start the installer again. If you are using GUI mode on Microsoft Windows, you must start the installer using the same command prompt.

Task 12-1-1: Obtaining the Oracle Tuxedo Installation Files from Oracle Software Delivery Cloud

You can obtain the files needed to install Oracle Tuxedo 12cR2 or 12cR2_VS2015 from the Oracle Software Delivery Cloud portal. At this point you should have already downloaded the necessary files. If you have not yet downloaded the files, this section includes additional information on finding and using the files for Oracle Tuxedo if necessary.

See "Preparing for Installation," Using Oracle Software Delivery Cloud to Obtain Installation Files.

See Oracle Software Delivery Cloud, <https://edelivery.oracle.com>.

1. After logging in to Oracle Software Delivery Cloud, read the export restrictions, and then click Accept.
2. Enter Oracle Tuxedo in the Product field, and select Oracle Tuxedo 12.2.2.0.0 to add it to your cart.
3. Click Selected Software.
4. From the Platforms/Languages drop-down list, select the operating system you are running on, and then click Continue.
5. Read the license agreement and select the check box to acknowledge that you accept the agreement.
6. Click Continue.
7. Click the filenames to download.

Save the zip file to a temporary directory on your local system, referred to in this documentation as *TUX_INSTALL*.

8. After you download the installation files from Oracle Software Delivery Cloud, if it is necessary, transfer the files to a UNIX computer using FTP. Unzip the file and change the permissions of the unzipped file to make it an executable, for example using the `chmod +x` command.
9. Extract the files into *TUX_INSTALL*.

After you extract, you see a Disk1 folder with two subfolders, install and stage.

Note. For the PeopleTools Client, install Oracle Tuxedo 12cR2_VS2015 for Microsoft Windows (64-bit) to run with PeopleSoft PeopleTools 8.57.

Task 12-1-2: Obtaining the Oracle Tuxedo Patches from My Oracle Support

You can download the latest patch for Oracle Tuxedo 12cR2_VS2015 for Microsoft Windows or Oracle Tuxedo 12cR2 for UNIX from My Oracle Support.

Note. To obtain older Oracle Tuxedo patches, raise a service request through My Oracle Support.

To obtain the latest Oracle Tuxedo patch:

1. Sign in to My Oracle Support with your account name and password:
<https://support.oracle.com>
2. Select the Patches & Updates tab.
3. Under Patch Search, select Product or Family (Advanced Search).
4. Select *Oracle Tuxedo* from the product drop-down list.
5. Select *Oracle Tuxedo 12.2.2.0.0* from the release drop-down list.
6. Select your platform.

Note. For detailed supported platform information, see the certifications area on My Oracle Support.

The supported platforms are:

- AIX
- HP-UX Itanium
- Linux
- Microsoft Windows
- Oracle Solaris on SPARC

7. Click Search.

Download the necessary files from the list of results. For installation on Microsoft Windows operating systems, make sure your rolling patch (RP) description has "VS2015" or "Visual Studio 2015" in the description.

Note. To begin a new search, select Edit Search in the top right of the results page.

8. Download the patch file for your operating system platform to a convenient directory, referred to here as *TUX_INSTALL*.

9. After you install a patch, use these steps to verify the installation:

- a. In a command prompt, change directory to *TUXDIR*\bin (where *TUXDIR* is the Oracle Tuxedo installation location).
- b. Execute the following command:

```
tmadmin -v
```

The command displays the patch level. For example:

```
INFO: Oracle Tuxedo, Version 12.2.2.0.0_VS2015, 64-bit, Patch Level=>
023
```

Task 12-1-3: Removing Existing Oracle Tuxedo Installations from Microsoft Windows (Optional)

You may already have prior versions of Oracle Tuxedo installed on your system from an earlier version of PeopleSoft PeopleTools. If you are completely upgrading to PeopleSoft PeopleTools 8.57 from an earlier version of PeopleSoft PeopleTools, then you may uninstall the existing version and patches.

Note. It is not mandatory to uninstall the existing version of PeopleSoft PeopleTools, as Oracle Tuxedo 12cR2_VS2015 can coexist with prior versions on the same machine.

If you wish to use two versions of PeopleSoft PeopleTools that depend on different versions of Oracle Tuxedo, you should read the section "Ensuring that Oracle Tuxedo Coexists with Earlier Versions" before continuing.

You may have to uninstall Oracle Tuxedo for these reasons:

- You are having problems starting Oracle Tuxedo and decide to reinstall.
- You no longer need Oracle Tuxedo on a machine.

To uninstall Oracle Tuxedo from Microsoft Windows:

1. Using PSADMIN, shut down any application server, Process Scheduler, and Search server domains that may be running on the machine.

2. Stop the processes for the Tuxedo Monitor and the Tuxedo Administrative Web Server (wlisten and tuxwsvr), if applicable.
 - a. Right-click on the task bar and select Task Manager.
 - b. Highlight wlisten, and click the End Task button.
 - c. Highlight tuxwsvr and click the End Task button.
 - d. Exit Task Manager.
3. Stop and set the TListen *VERSION* service to manual, if applicable.
 Replace *VERSION* with the version number for the existing service. For example, this would be TListen 9.1 or TListen 10gR3.
 - a. Select Start, Settings, Control Panel. Double-click Administrative Tools, and double-click the Services icon.
 - b. Select TListen *VERSION* and click the Stop button.
 - c. Choose the Startup Type and set to Manual.
4. Stop and set the ORACLE ProcMGR *VERSION* (or BEA ProcMGR *VERSION* for earlier releases) service to manual.
 - a. Select Start, Settings, Control Panel. Double-click Administrative Tools, and double-click the Services icon.
 - b. Select ORACLE ProcMGR *VERSION* and click the Stop button.
 - c. Choose the Startup Type and set to Manual.
5. Reboot your machine.
6. Uninstall Oracle Tuxedo in one of the following ways:
 - Using the Oracle Tuxedo *VERSION* installation CD provided by Oracle for PeopleSoft installations, open a Command Window, navigate to the root of the CD, and enter `pstuxinstall rmall`. This will remove Oracle Tuxedo *VERSION* plus any delivered Oracle Tuxedo patches from your system.
 - Using the Add/Remove Programs dialog, in sequence remove: Oracle Tuxedo*VERSION* RP and then Oracle Tuxedo *VERSION*.
7. Go to the Control Panel, double-click on the System icon, and then perform the following actions:
 - a. Make sure *TUXDIR*\bin is deleted from the PATH environment variable definition.
TUXDIR refers to the Oracle Tuxedo installation directory.
 - b. Delete the environment variable *TUXDIR*.
 - c. Make sure you click on Apply and OK to save your changes.
8. Using Explorer, delete the Tuxedo home directory, such as C:\bea\tuxedo8.1.
 If you are unable to delete any files, reboot your machine and retry.

Task 12-1-4: Designating the Application Server Administrator on Microsoft Windows

Before beginning the installation, you need to designate an existing user—or create a new user such as TUXADM or some other account—to be the Application Server Administrator. The Application Server Administrator, not the Windows Administrator, will install Oracle Tuxedo.

The designated user must be a local Microsoft Windows administrator and must have full system privileges. The Oracle Tuxedo installation program creates a new service for Microsoft Windows—called ORACLE ProcMGR V12.2.2.0.0_VS2015—for which you need administrator privileges. This service was developed to port Oracle Tuxedo from UNIX to Microsoft Windows. Administrator rights are required since system registry settings are updated. Once this new service is created, you must reboot to start it.

When you configure your application server domain in a read-only *PS_HOME* environment, the user ID designated to be the Application Server Administrator must have read-only access to *PS_HOME*, read and write access to *PS_CFG_HOME*, and read-only access to the Oracle Tuxedo installation directory, *TUXDIR*, (for example, C:\oracle\tuxedo12.2.2.0.0_VS2015). Otherwise, in a scenario where *<PS_CFG_HOME> = <PS_HOME>*, the Application Server Administrator must have read and write access to *PS_HOME* and read-only access to *TUXDIR*.

See "Configuring the Application Server on Windows."

See "Preparing for Installation," Defining Installation Locations.

To designate the Application Server Administrator:

1. Add the user ID by selecting Start, Administrative Tools, Computer Management, Local Users and Groups.
Keep in mind that you can also use an existing account if you do not care to create a new one. You can set this to the system account or an account that is a domain administrator (if there is a need to access files on the domain).
2. Expand Local Users and Groups.
3. If the user ID does not yet exist, highlight the Users folder, and select Action, New User.
4. On the New User dialog box, specify the information for the new account.
Make sure to deselect the User must change password at next logon check box.
5. Expand the Groups folder.
6. Right-click the Administrators group, and select All Tasks, Add to Group, Add.
7. Click Locations to select the local machine or the network domain in which you created the new user.
8. Enter the new user name you created in the object names box.
9. Click OK, and click Apply and OK again to accept the changes.

Task 12-1-5: Installing Oracle Tuxedo on Microsoft Windows in GUI Mode


The following procedure assumes that you saved and extracted the installation files from Oracle Software Delivery Cloud in the directory *TUX_INSTALL*. Installation in GUI mode is normally used for Microsoft Windows operating systems.

Note. Oracle Tuxedo 12cR2_VS2015 can coexist on a machine with other versions of Oracle Tuxedo.

To install Oracle Tuxedo on Microsoft Windows:


1. Double-click `TUX_INSTALL\Disk1\install\setup.bat` to begin the installation process.

Click OK on the Welcome window, shown in this example:



Oracle Universal Installer: Welcome window for Oracle Tuxedo 12c Release 2

2. Accept the default option, Full Install, on the Select Installation Type window, as shown in this example, and click Next.



Oracle Universal Installer: Select Installation Type window

3. Specify a name and the home directory path for the installation.

You can enter a new name, or choose an existing name from the drop-down list. The name that you supply will be used to identify this Oracle Tuxedo installation in the Oracle Universal Installer, when reviewing the Installed Products list. In this example, the name is `tuxedo1222vs2015`.


Specify the full path for the home directory. You can choose an existing path from the drop-down list. The Path refers to the location where the Oracle Tuxedo will be installed. The default is `ORACLE_HOME\tuxedo12.2.2.0.0_VS2015`. In this example, the path is `C:\oracle`, which is the recommended location, so the software will be installed to `C:\oracle\tuxedo12.2.2.0.0_VS2015`. The installation directory is referred to in this documentation as *TUXDIR*.

Note. In previous Oracle Tuxedo and PeopleSoft PeopleTools releases, the installation directory was referred to as *BEA_HOME*, and the default was `C:\bea`. You may see installation directories from previous releases displayed here, and if so, you can select one.

Oracle Universal Installer: Specify Home Details window

4. If you select an existing directory that is not empty, you may see a warning message.

The message recommends that you install to an empty directory unless the directory contains Operating System generated files or subdirectories like lost+found. Click Yes to close the message and continue.




Warning message for a non-empty directory

5. If you have other versions of Oracle Tuxedo on your system, you may get a warning that earlier versions were detected, and with a recommendation that you exit and remove the earlier versions.

You can either quit and remove the earlier version, or install to a different directory if you want to maintain more than one version of the software. The message directs you to the earlier Installation Guide for instructions for using more than one version of the software. Click Next to continue.


6. Select No on the TSAM Plus agent enable choice window, as shown in this example, and then click Next.

This indicates that you do not want to enable Oracle Tuxedo System and Applications Monitor Plus (Oracle TSAM Plus) agent.




Oracle Universal Installer: TSAM Plus agent enable choice window

7. Select No to indicate that you do not want to install Oracle Tuxedo Samples, as shown in this example, and then click Next.




Oracle Universal Installer: Oracle Tuxedo Samples Installation Choice window

8. Select Yes to indicate that you want to configure Oracle Tuxedo tlisten, as shown in this example, and then click Next.



Oracle Universal Installer: Oracle Tuxedo tlisten configuration Choice window


9. Enter a password for Oracle Tuxedo tlisten.



The screenshot shows a window titled "Oracle Universal Installer: Configure tlisten password". In the top right corner, it says "Oracle® Tuxedo 12c Release 2". The main heading is "Configure tlisten password". There are two input fields: "Password:" and "Verify Password:", both containing seven asterisks. At the bottom, a note states: "Machines those will participate in the same domain need to have the same tlisten password defined." Below this note are five buttons: "Help", "Installed Products...", "Back", "Next", and "Install", followed by a "Cancel" button. At the very bottom, the copyright text reads: "Copyright © 1996, 2016, Oracle and/or its affiliates. All rights reserved."


Oracle Universal Installer: Configure tlisten password window

10. Accept the default tlisten port, 3050, or enter another port number.



Oracle Universal Installer: Configure tlisten Port window

11. Select LLE as the Tlistener encryption method.




Oracle Universal Installer: Tlistener encryption method choose window

12. Accept the default value of 0 (zero) for the minimum encryption bits.




Oracle Universal Installer: Choose Min Encryption Bits window

13. Accept the default value of 256 as the default value of maximum encryption bits.




Oracle Universal Installer: Choose Max Encryption Bits window

14. Select Yes on the SSL Support Choice window, as shown in this example, and then click Next.



Oracle Universal Installer: SSL Support Choice window


15. Select No for the option Would you like to configure LDAP for SSL Support? and then click Next.



Oracle Universal Installer: LDAP Support Choice window

16. Review the summary information, and click Install to continue.


The summary information, shown in this example, includes the product name, install folder, installation type, and disk space information. If you want to change any of your choices, click Back.



Oracle Universal Installer: Summary window

A progress indicator appears during the installation.

17. Click Exit when you see the window indicating the installation completed successfully, as shown in this example.



Oracle Universal Installer: End of Installation window

Task 12-1-6: Installing the Oracle Tuxedo Patch on Microsoft Windows

These instructions assume that you have installed the base Oracle Tuxedo 12cR2_VS2015, and have downloaded the platform-specific version of the rolling patch to a directory referred to here as *TUX_INSTALL*. Carry out these steps as a user with administrative privileges.

To install the patch:

1. Stop all PeopleSoft PeopleTools domains that are running and using your Oracle Tuxedo installation.
2. Verify that the environment variable TUXDIR is set to the Oracle Tuxedo installation location, such as C:\oracle\tuxedo12.2.2.0.0_VS2015.

Note. The TUXDIR directory should include subdirectories bin and udataobj.

3. Verify that the environment variable ORACLE_HOME is set to the *ORACLE_HOME* location you specified when you installed Oracle Tuxedo, such as C:\oracle.

Note. This is the parent directory for the Oracle Tuxedo installation. It should include subdirectories OPatch and oui.

4. Verify that the environment variable JAVA_HOME is set to the 64-bit JDK 1.8 directory, as mentioned in the prerequisites section.

5. Run the following command to verify the opatch version:

```
%ORACLE_HOME%\OPatch\opatch.bat version
```

The version should be 12.1.0.1.1 or later. If the version is lower, you must first update opatch by installing patch 19166960.

6. Launch the Services window; for example, select Start, Administrative Tools, Services.

7. Select each of the following services, right-click, and select Stop:

- ORACLE ProcMGR V12.2.2.0.0_VS2015
- TListen 12.2.2.0.0_VS2015 (Port: 3050)

Note. The port number is variable.

8. Uninstall any existing patches.

9. Go to the directory where you downloaded the patch zip file from My Oracle Support, *TUX_INSTALL*, and unzip the file.

This creates a directory that includes a zip file named 27127314.zip with the patch.

10. Set the environment variable for the platform ID; for example:

```
set OPATCH_PLATFORM_ID=233
```

You can find the value for OPATCH_PLATFORM_ID in the file *ORACLE_HOME/inventory/ContentsXML/oraclehomeproperties.xml*.

11. Open a command prompt and go to the *TUX_INSTALL/27127314* directory.

12. Run the following command:

```
%ORACLE_HOME%\OPatch\opatch.bat apply 27127314.zip
```

Note. The patch installer backs up all files being patched. The backup copy is located in the directory *ORACLE_HOME\patch_storage*. Do not delete these backup files. They will be used if you need to remove the patch installation.

You see a message similar to the following:

```
Oracle Home       : C:\oracle
Central Inventory : C:\Program Files\Oracle\Inventory
    from          : n/a
OPatch version    : 12.2.0.1.0
OUI version       : 12.2.0.1.0
Log file location : C:\oracle\cfgtoollogs\opatch\opatch<datetime>.log
```

13. If OPatch cannot locate the Oracle inventory, you may see a message such as the following:

```
Applying interim patch 27127314 to OH 'C:\Oracle'
Verifying environment and performing prerequisite checks.
OPatch system modification phase did not start
```

In this case, specify the full path to the Oracle inventory file oraInst.loc, with the `invPtrLoc` option:

```
%ORACLE_HOME%\OPatch\opatch.bat apply 25391869.zip -invPtrLoc <full_⇒
path_to_inventory_file>
```

Task 12-1-7: Installing Oracle Tuxedo on Microsoft Windows in Silent Mode

This section discusses:

- Understanding Silent Installation on Microsoft Windows
- Running the Silent Mode Installation on Microsoft Windows

Understanding Silent Installation on Microsoft Windows

You can carry out a silent installation of Oracle Tuxedo 12cR2_VS2015 by providing all the required settings in a response file. With silent installation there is little or no user interaction.

See Oracle Tuxedo documentation.

Use a text editor to create the response file and specify the values according to your installation requirements.

Here is a sample response file:

```
#
# ..... Silent Installation Properties file .....
#

RESPONSEFILE_VERSION=2.2.1.0.0

ORACLE_HOME="C:\oracle"

ORACLE_HOME_NAME="tuxedo1222_VS2015"

INSTALL_TYPE="Full Install"

ENABLE_TSAM_AGENT=false

LDAP_SUPPORT_SSL=false

INSTALL_SAMPLES=false

ENCRYPT_CHOICE=0

CONFIG_TLISTEN=false
```

Most of the entries are similar to those seen in the GUI installation. Note the following definitions:

- **ORACLE_HOME:** The high level installation directory, for example C:\oracle.
The installer creates the Oracle Tuxedo installation directory, *TUXDIR*, as ORACLE_HOME\tuxedo12.2.2.0.0_VS2015.
- **ORACLE_HOME_NAME:** The name of the current Oracle installation, for example tuxedo1222_VS2015.
This identifies the Oracle Tuxedo installation in the Oracle Universal Installer, when reviewing the Installed Products list.

Running the Silent Mode Installation on Microsoft Windows

The following procedure assumes that you saved and extracted the installation file from Oracle Software Delivery Cloud in the directory *TUX_INSTALL*.

See Obtaining the Oracle Tuxedo Installation Files from Oracle Software Delivery Cloud.

To run the installer:

1. Create a response file as described in the previous section and copy it to *TUX_INSTALL*.
2. Open a command prompt and change directory to *TUX_INSTALL\Disk1\install*.
3. Run the installer.

- If you specify an empty directory for *ORACLE_HOME*, use this command:

```
setup.exe -silent -responseFile response_file
```

Specify the full path to the response file. For example, if the response file name is *response.rsp*, and *TUX_INSTALL* is *D:\Temp*, use this command:

```
setup.exe -silent -responseFile D:\Temp\response.rsp
```

- If you specify an existing directory that is not empty for *ORACLE_HOME*, you must include the **–force** option.

When you use the **–force** option with a non-empty *ORACLE_HOME*, you may see a warning message recommending that you install to an empty directory or one that includes Operating System generated files. You may close the message to continue the installation.

```
setup.exe -silent -responseFile D:\Temp\response.rsp -force
```

Note. If you do not include the **–force** option with an *ORACLE_HOME* directory that is not empty, the installer will abort.

4. After you enter the commands in the previous steps, the installer is launched in silent mode, and a progress indicator tracks the installation.

When the installation is complete, you should see a completion message such as "The installation of Oracle Tuxedo was successful."

Task 12-1-8: Uninstalling the Oracle Tuxedo Patch on Microsoft Windows

To remove an Oracle Tuxedo installation, you must first remove the rolling patch, as follows:

1. Stop all PeopleSoft PeopleTools domains that are running and using your Oracle Tuxedo installation.
2. Verify that the environment variable *TUXDIR* is set to the Oracle Tuxedo installation location, such as *C:\oracle\tuxedo12.2.2.0.0_VS2015*.
3. Verify that the environment variable *ORACLE_HOME* is set to the *ORACLE_HOME* location you specified when you installed Oracle Tuxedo, such as *C:\oracle*.
4. Open a command prompt and run the following command:

```
%ORACLE_HOME%\OPatch\opatch.bat rollback -id 27127314
```

Task 12-1-9: Uninstalling Oracle Tuxedo in GUI Mode

To remove the Oracle Tuxedo 12cR2_VS2015 or 12cR2 installation, use Oracle Universal Installer (OUI).

1. Start Oracle Universal Installer (OUI).

The way that you access OUI may vary depending upon your environment. Use one of the following methods, for example:


- On Microsoft Windows 2012 R2, access the Apps screen, and select Oracle 12c, Oracle Installation Products, Universal Installer.
- Double-click *TUX_INSTALL*\Disk1\install\setup.exe.

2. Click Deinstall Products, as shown in this example:



Oracle Universal Installer: Welcome window

- On the Contents page, select the name for the Oracle Tuxedo installation, which is tuxedo1222vs2015 in this example, and then click Remove.



Inventory window: Contents page

- Open the Microsoft Windows registry, for example by selecting Start, Run, regedit.

Verify that the following key has been removed from the registry:

HKEY_LOCAL_MACHINE\SOFTWARE\ORACLE\TUXEDO\12.2.2.0.0_VS2015

Task 12-1-10: Checking the Windows Service Account

Use the information in this section to ensure that the Microsoft Windows services are properly configured. Oracle recommends installing the application server binaries locally on your C drive, for best performance. The procedure to set up the ORACLE ProcMGR V12.2.2.0.0_VS2015 service in the next section includes options for the account type. Use the following guidelines to choose between the Local System account option and the This Account option. (For the option This Account, you must specify a user ID and password.)

Note. For the sake of brevity and convenience, this documentation sometimes shortens "ORACLE ProcMGR V12.2.2.0.0_VS2015" to "Oracle ProcMGR."

- If you plan to install the PeopleSoft application server binaries (as in, psappsrv.exe and so on) on a remote file

server, you must select the This Account option.

- If the PeopleSoft application server binaries are *local*, that is, they exist on your local hard drive, you can use either the Local System account or This Account option.
- If you intend to use this Microsoft Windows service to start Process Scheduler, you must *always* select the This Account option. Enter the name of your Domain/Windows user name—not the machine name—and your password.
- If you are running on Microsoft Windows and are configuring a search index that resides on a mapped network drive, you must ensure that the user ID of the Oracle ProcMGR service has access to network drives accessed by the search engine. The search engine stores the search indexes at *PS_HOME/data/search*. However, this path can be changed in the application or the Process Scheduler's configuration. If this path is changed in these configurations and it points to a network drive, you must ensure that the user ID that starts the Oracle ProcMGR service has access to these network drives. The application server and the Process Scheduler are started by the Oracle ProcMGR service and therefore inherit the same permissions as the Oracle ProcMGR service.

See Also

"Setting Up Process Scheduler on Windows," Setting Up Process Scheduler Security

Task 12-1-11: Restricting Domain Process Privileges

This section discusses:

- Understanding Domain Process Privileges
- Setting TM_CPAU Environment Variable

Understanding Domain Process Privileges

For PeopleSoft systems, the Oracle ProcMGR service (tuxipc.exe) is responsible for starting Oracle Tuxedo domain processes on Microsoft Windows. By default, domain processes run as the same user ID that the service is running as. In a default installation, the service is configured to log on to Microsoft Windows as the Local System user. Microsoft does not support assigning network privileges to the Local System user for security reasons, but the Local System user otherwise has full administrative access to the local system.

In this configuration, PeopleSoft PeopleTools domain processes also run as the Local System user, which presents several potential issues, including:

- PeopleSoft PeopleTools domain processes are unable to access network resources.
- PeopleSoft PeopleTools domain processes run with more privileges than are necessary. A compromised PeopleSoft PeopleTools process will have full access to the local system and could potentially be used to gain unauthorized access to the local system.
- All PeopleSoft PeopleTools domain processes on the system run as the same user ID.

These problems are not present on UNIX systems where domain processes are always started as the user that runs tadmin (by way of PSADMIN for PeopleSoft installations) to boot the domain. UNIX systems therefore support multiple domains, each running under different user IDs, with only the desired local privileges, and with no undesirable restrictions to network resources.

For Microsoft Windows platforms, you can use the Oracle Tuxedo `TM_CPAU` environment variable to achieve behavior similar to UNIX systems. If `TM_CPAU` is set to *YES* before `tuxipc` is started, `tuxipc` creates an Oracle Tuxedo process that belongs to the user who initiated `tmboot`. If the Oracle ProcMGR service (`tuxipc.exe`) is started with the `TM_CPAU=YES` environment variable set, then domain processes will run as the user ID used to run `tmadmin` (PSADMIN) to boot the domain.

Using the `TM_CPAU` environment variable enables a variety of configuration options, including:

- The Oracle ProcMGR service can be run as the Local System user, but domain processes can be run using a minimally privileged user. This reduces the chance of a compromised PeopleSoft PeopleTools process being used to gain unauthorized access to the system. Note that the option "Allow services to interact with Desktop" should *not* be selected.
- The Oracle ProcMGR service can be configured to log on to Microsoft Windows using a minimally privileged user ID and PeopleSoft PeopleTools processes can run as a user with more privileges than the Oracle Tuxedo user ID. For example, the Oracle Tuxedo user ID could have read-only access to `PS_CFG_HOME`, but the PeopleSoft PeopleTools user could have read-write access. The Oracle Tuxedo user ID does not actually require read access to `PS_HOME`. When `CreateProcessAsUser` runs, access to the executable to start is evaluated using the user ID that the process will run as.
- A single Microsoft Windows system can be used to host multiple PeopleSoft PeopleTools installations that are each administered by a different user. A non-administrative user ID used to boot one domain will have no privileges to processes started with a different user ID.
- Domain processes can be identified and managed in Windows Task Manager by a non-administrative user.

See File Formats, Data Descriptions, MIBs, and System Processes Reference, Oracle Tuxedo Reference Topics, http://docs.oracle.com/cd/E35855_01/tuxedo/docs12c/rf5/rf5.html.

Setting `TM_CPAU` Environment Variable

This is a recommended step. Perform this step only if Local System account is used in the task Setting Up the Windows Services for Oracle Tuxedo.

To set the `TM_CPAU` environment variable:

1. Access the Control Panel, and then select System and Security, System, on Microsoft Windows 2012 R2, or Microsoft Windows 2016.
2. Select Advanced system settings.
3. Select the Advanced tab.
4. Click Environment Variables.
5. In the System variables area, click New to add a new environment variable.
6. Enter `TM_CPAU` as the variable name, *YES* as the value, and click OK three times to close the dialog boxes.
7. Restart your machine.

Task 12-1-12: Setting Up the Windows Services for Oracle Tuxedo

To set up the Microsoft Windows services for Oracle Tuxedo:

1. Log on again as the Application Server Administrator, `TUXADM`, or a designated user ID.
2. Open the Control Panel and double-click Administrative Tools.
3. Select Computer Management and expand Services and Applications.
4. Select Services and locate the service labeled *ORACLE ProcMGR V12.2.2.0.0_VS2015*.


Double-click ORACLE ProcMGR V12.2.2.0.0_VS2015 to open the properties dialog box.

5. On the General tab, if the Stop button is enabled, click it to stop the current ORACLE ProcMGR V12.2.2.0.0_VS2015 process.
6. Select Log On.
7. Choose either Local System account or This account.

If you select This account, as shown in this example, be sure to specify a user with the appropriate permissions, and then enter and confirm the password.

Note. The option used—Local System account or This account—must be consistent with your ODBC catalog definition, due to registry operations. For example, if you use the Local System Account option, you must also catalog your ODBC data source using System DSN.


See Checking the Windows Service Account.



ORACLE ProcMGR V12.2.2.0.0_VS2015 Properties dialog box: Log On tab

8. Select General.

Make sure that Startup Type is set to *Automatic*, as shown in this example.



ORACLE ProcMGR V12.2.2.0.0_VS2015 Properties dialog box: General tab

9. Click Start.

The status Started appears both on the General tab of the Oracle ProcMGR V12.2.2.0.0_VS2015 Properties dialog box and in the Services dialog box. Click OK to close the dialog box.

10. As mentioned, unless you intend to use the Tuxedo Web Monitor, you should disable the TListen 12.2.2.0.0_VS2015 (Port: *PORT*) service, where *PORT* is the port number you entered during the installation. The default is 3050.

Task 12-1-13: Verifying the Server Installation on Microsoft Windows

At this point, you should verify that the server installation was successful.

To verify the installation:

1. Open a command prompt.
2. Set the TUXDIR environment variable; for example:

```
set TUXDIR=C:\oracle\tuxedo12.2.2.0.0_VS2015
```
3. Go to the directory where you installed Oracle Tuxedo, *TUXDIR*, and then to the bin sub-directory. For

example:

```
C:\oracle\tuxedo12.2.2.0.0_VS2015\bin
```

4. Issue this command:

```
tmadmin -v
```

The command will return the Oracle Tuxedo version that is installed. For example:

```
INFO: Oracle Tuxedo, Version 12.2.2.0.0_VS2015, 64-bit, Patch Level 023
```

If you do not see the desired output, review your steps and reinstall Oracle Tuxedo 12cR2_VS2015.

5. Open the Microsoft Windows registry, for example by selecting Start, Run, regedit.

Verify that the following key is created in the Windows registry:

```
HKEY_LOCAL_MACHINE\SOFTWARE\ORACLE\TUXEDO\12.2.2.0.0_VS2015
```

Task 12-1-14: Removing Existing Oracle Tuxedo Installations from UNIX (Optional)

You may have older versions of Oracle Tuxedo installed on your system from an earlier version of PeopleSoft PeopleTools. If you are completely upgrading to PeopleSoft PeopleTools 8.57 from an earlier version of PeopleSoft PeopleTools and you do not require the older Oracle Tuxedo anymore, then, you may uninstall it.

Note. It is not mandatory to uninstall older Oracle Tuxedo versions from the machine where you are installing Oracle Tuxedo 12cR2, as older Oracle Tuxedo versions and Oracle Tuxedo 12cR2 can exist on the same machine.

You may have to remove your Oracle Tuxedo installation on UNIX for the following reasons:

- You are having problems starting Oracle Tuxedo and decide to reinstall.
- You no longer need Oracle Tuxedo on a machine.

To remove Oracle Tuxedo from UNIX:

1. Using PSADMIN, shut down any application server, Process Scheduler, and Search server domains that may be running on the machine.
2. Use the UNIX `rm` command to directly remove the Oracle Tuxedo installation.
Be sure to remove the directory containing Oracle Tuxedo, referred to here as *TUXDIR*.
3. Remove the TUXDIR environment variable and any entries containing your platform-specific LIBRARY PATH and PATH environment variables.

Task 12-1-15: Completing the Preinstallation Checklist on UNIX

We recommend that you complete the following preinstallation checklist before you begin the Oracle Tuxedo installation. The checklist includes various parameters with descriptions and example values. Specify your values in the Real Value column. Completing this information first should save you time during your installation.

Item	Description	Example Value	Real Value
ORACLE_HOME	The high level installation directory. You specify this value in the silent installation file.	/oracle	<enter value>

Item	Description	Example Value	Real Value
ORACLE_HOME_NAME	The name of the current Oracle installation. This identifies the Oracle Tuxedo installation in the Oracle Universal Installer, when reviewing the Installed Products list.	tuxedo1222	<enter value>
TUXDIR	The full path to the Oracle Tuxedo installation. The installer creates this as ORACLE_HOME/tuxedo12.2.2.0.0	/oracle/tuxedo12.2.2.0.0	<enter value>
Username	The UNIX user name of the Application Server Administrator (Oracle Tuxedo owner). See the next section for instructions.	tuxedo	<enter value>
UNIX_GROUP_NAME	The UNIX group name of the Oracle Tuxedo owner. See the next section for instructions.	tuxedo	<enter value>
FROM_LOCATION	The full path to the directory containing the products to be installed.	/home/temp/Disk1/stage/products.xml	<enter value>

Note. You can select any user name and group name you want; however, you might want to use the "tuxedo" convention for simplicity.

Task 12-1-16: Designating the Oracle Tuxedo Owner on UNIX

A new or existing user must be designated as the Oracle Tuxedo owner.

Note. The application server can be booted only by the Oracle Tuxedo owner or the group that the owner is in. The predefined UNIX "other" group does not have read or execute permission. If it is required that members of the "other" group be able to boot and shut down an application server domain, you must manually give read and execute permissions to all files and folders under the *TUXDIR/locale* and *TUXDIR/udataobj* directories.

To designate the Oracle Tuxedo owner:

1. Log in as root.
2. Create the UNIX group and the user name of the individual who will be the owner of Oracle Tuxedo.

Using the values from the preinstallation checklist, create the group and specify the group name. Then create the user who will be the Oracle Tuxedo owner, specifying the user name, group name, and home directory, denoted by TUXDIR from the checklist.

Note. The utility that you use to create the user and group varies, depending on your operating system. For example, HP-UX Itanium uses the "sam" utility, IBM AIX uses the "smit" utility, and so on. For the exact utility, refer to your operating system documentation.

Task 12-1-17: Installing Oracle Tuxedo in Silent Mode on UNIX

This section discusses:

- Understanding the Silent Mode Installation on UNIX
- Running the Silent Mode Installation on UNIX

Understanding the Silent Mode Installation on UNIX

You can carry out a silent installation of Oracle Tuxedo 12cR2 by providing all the required settings in a response file. With silent installation there is little or no user interaction.

Note. Console mode installation is not supported for Oracle Tuxedo 12cR2.

Use a text editor to modify the values in the response file according to your installation requirements. Here is a sample response file:

```
#
# ..... Silent Installation Properties file .....
#

RESPONSEFILE_VERSION=2.2.1.0.0
#Unix group to be set for the inventory directory. Valid only in Unix⇒
platforms.
UNIX_GROUP_NAME="dba"

#Complete path of the Oracle Home.
ORACLE_HOME="/home/psftuser/oracle"

#Oracle Home Name. Used in creating folders and services.
ORACLE_HOME_NAME="tuxedo1222"
DEINSTALL_LIST={"Tuxedo","12.2.2.0.0"}
SELECTED_LANGUAGES={"en"}
COMPONENT_LANGUAGES={"en"}
INSTALL_TYPE="Full Install"
ENABLE_TSAM_AGENT=false
LDAP_SUPPORT_SSL=false
TLISTEN_PORT="3050"
MIN_CRYPT_BITS_CHOOSE=0
MAX_CRYPT_BITS_CHOOSE=256
INSTALL_SAMPLES=true
ENCRYPT_CHOICE=0
CONFIG_TLISTEN=true
TLISTEN_PASSWORD=password
```

Running the Silent Mode Installation on UNIX

The following procedure assumes that:

- You saved and extracted the installation files from Oracle Software Delivery Cloud in the directory *TUX_INSTALL*.
- You installed the supported version of Java 8.

The command requires the full path for the JRE file, such as */home/java/jre1.8.0_65*.

To install Oracle Tuxedo on UNIX:

1. If it does not exist, use a text editor, such as "vi", to create the central inventory location file, named *oraInst.loc*, in a convenient directory.

If you have previously installed Oracle software on the system, the *oraInst.loc* file may already exist. The *oraInst.loc* file contains only the following two lines:

```
inventory_loc=/home/psftuser/oraInventory
inst_group=ccpt
```

The *oraInst.loc* file contains the following information:

- *inventory_loc* — Specify the full path to the directory where you want the installer to create the inventory directory. The location in the example is */home/psftuser/oraInventory*.
 - *oui_install_group* — Specify the name of the group whose members have write permissions to this directory. The group name in the example is *ccpt*.
2. Create a response file as described in the previous section and copy it to *TUX_INSTALL*.
 3. Open a command prompt and change directory to *TUX_INSTALL/Disk1/install*.
 4. If this is the first time you are installing on your system (that is, there is no pre-existing Oracle inventory location, and you had to create the *oraInst.loc* file in the first step), use the following command to perform a silent installation:

```
./runInstaller -responseFile <complete_filename> -silent -invPtrLoc =>
<complete_inventory_filename> -jreLoc <JRE file location>
```

Specify the full path and name for the response file, the *oraInst.loc* file, and the JRE file. For example:

```
./runInstaller -responseFile /home/temp/response.rsp -silent -invPtrLoc=>
/home/psftuser/oraInventory/oraInst.loc -jreLoc /home/java/jre1.8.0_65
```

5. If you have previously installed an Oracle product on your system and do not need to specify an Oracle inventory location, use the following command to perform a silent installation:

```
./runInstaller -responseFile <complete_filename> -silent -jreLoc <JRE=>
file location>
```

Specify the full path and name for the response file and the JRE file. For example:

```
./runInstaller -responseFile /home/temp/response.rsp -silent -jreLoc =>
/home/java/jre1.8.0_102
```

6. After you enter the commands in the previous steps, the installer is launched in silent mode, and a progress indicator tracks the installation.

The progress indicator includes the name and location of the installation log file. When the installation is complete, you should see a successful completion message.

Task 12-1-18: Installing the Oracle Tuxedo Patch on UNIX

These instructions assume that you have installed the base Oracle Tuxedo 12cR2, and have downloaded the platform-specific version of the rolling patch to a directory referred to here as *TUX_INSTALL*.

To install the patch:

1. Stop all PeopleSoft PeopleTools domains that are running and using your Oracle Tuxedo installation.

Shut down any tlisten processes.

2. Verify that the environment variable TUXDIR is set to the Oracle Tuxedo installation location, such as /home/psftuser/oracle/tuxedo12.2.2.0.0.

Note. The TUXDIR directory should include subdirectories bin and udataobj.

3. Verify that the environment variable ORACLE_HOME is set to the *ORACLE_HOME* location you specified when you installed Oracle Tuxedo, such as /home/psftuser/oracle.

Note. This is the parent directory for the Oracle Tuxedo installation. It should include subdirectories OPatch and oui.

4. Verify that the environment variable JAVA_HOME is set to the 64-bit JDK 1.8 directory, as mentioned in the prerequisites section.

5. Go to the directory where you downloaded the patch zip file from My Oracle Support, *TUX_INSTALL*, and extract the file.

This creates a directory 25391869, which includes a zip file with the patch.

6. Open a command prompt and go to the *TUX_INSTALL/25391869* directory.

7. Run the following command:

```
$ORACLE_HOME/OPatch/opatch apply 25391869.zip
```

Note. The patch installer backs up all files being patched. The backup copy is located in the directory *ORACLE_HOME\patch_storage*. Do not delete these backup files. They will be used if you need to remove the patch installation.

8. If OPatch cannot locate the Oracle inventory, you may see a message such as the following:

```
Applying interim patch 25391869 to OH '/oracle'
Verifying environment and performing prerequisite checks.
OPatch system modification phase did not start
```

In this case, specify the full path to the Oracle inventory file oraInst.loc, with the *invPtrLoc* option:

```
%ORACLE_HOME%/OPatch/opatch.bat apply 25391869.zip -invPtrLoc <full_⇒
path_to_inventory_file>
```

Task 12-1-19: Uninstalling the Oracle Tuxedo Patch from UNIX

To remove an Oracle Tuxedo installation, you must first remove the rolling patch, as follows:

1. Stop all PeopleSoft PeopleTools domains that are running and using your Oracle Tuxedo installation.
2. Verify that the environment variable TUXDIR is set to the Oracle Tuxedo installation location, such as /home/psftuser/oracle/tuxedo12.2.2.0.0.

3. Verify that the environment variable `ORACLE_HOME` is set to the *ORACLE_HOME* location you specified when you installed Oracle Tuxedo, such as `/home/psftuser/oracle`.
4. Open a command prompt and run the following command:

```
$ORACLE_HOME/OPatch/opatch rollback -id 25391869
```

Task 12-1-20: Uninstalling Oracle Tuxedo from UNIX Using Silent Mode

To remove the Oracle Tuxedo 12cR2 installation from UNIX:

1. Open a command prompt and change directory to *TUX_INSTALL/Disk1/install*.
2. Run the following command, where `ORACLE_HOME` refers to the high-level installation director, and `REMOVE_HOMES` refers to the directory to be removed:

```
./runInstaller -deinstall -silent ORACLE_HOME=<LOCATION_OF_ORACLE_HOME>⇒  
"REMOVE_HOMES={<LOCATION_OF_ORACLE_HOME_TO_BE_REMOVED>}"
```

For example:

```
./runInstaller -deinstall -silent ORACLE_HOME="/home/psftuser/oracle"⇒  
"REMOVE_HOMES={/home/psftuser/oracle}"
```

See Oracle Tuxedo documentation.

Task 12-1-21: Verifying the Server Installation on UNIX

To verify that the server installation was successful:

1. Open a shell.
2. Change directory to *TUXDIR/bin*. For example:

```
/home/psftuser/oracle/tuxedo1222/bin
```
3. Issue the following command:

```
tmadmin -v
```

The command will return the Oracle Tuxedo version that is installed. For example:

```
INFO: Oracle Tuxedo, Version 12.2.2.0.0, 64-bit, Patch Level 023
```

If you do not see the desired output, review your steps and reinstall Oracle Tuxedo 12cR2.

Task 12-1-22: Ensuring that Oracle Tuxedo Coexists with Earlier Versions

This section discusses:

- Understanding the Use of Multiple Oracle Tuxedo Versions
- Checking Your Environment Variables
- Changing the TListen Port

Understanding the Use of Multiple Oracle Tuxedo Versions

Earlier versions of PeopleSoft PeopleTools rely on earlier versions of Oracle Tuxedo—for example, PeopleSoft PeopleTools 8.49 uses Oracle Tuxedo 9.1. If you are installing only PeopleSoft PeopleTools 8.57, you can safely skip this section. If you need to run application servers on PeopleSoft PeopleTools 8.57 and earlier PeopleSoft PeopleTools versions on the same machine, read this section to learn about coexistence issues. Although Oracle Tuxedo 12cR2 coexists with earlier Oracle Tuxedo versions on the same machine, you may need to take a number of manual steps to ensure that these products share the same environment gracefully.

Checking Your Environment Variables

Installing Oracle Tuxedo changes your `TUXDIR` and `PATH` environment variables. Although you do not need to change these environment variables to successfully run PeopleSoft PeopleTools 8.57 with Oracle Tuxedo 12cR2, earlier versions of PeopleSoft PeopleTools rely on these environment variables being set.

To change your environment variables manually:

1. Set your `TUXDIR` environment variable to reflect the installation directory of your earlier Oracle Tuxedo release.
For example, Oracle Tuxedo 8.1 may be installed to `C:\tux8.1`. This means that `TUXDIR=C:\tux8.1` is the correct setting.
2. Your `PATH` environment variable must contain `TUXDIR\bin` for the earlier Oracle Tuxedo version before any entries for `TUXDIR\bin` for Oracle Tuxedo 12cR2.

For example the setting `PATH=C:\winnt;C:\oracle\tuxedo12.2.2.0.0_VS2015\bin;C:\tux8.1\bin` will cause your pre-8.49 domains to no longer work. You would need to change this to `PATH=C:\winnt;C:\tux8.1\bin;C:\oracle\tuxedo12.2.2.0.0_VS2015\bin` to work with pre-PeopleSoft PeopleTools 8.49 domains.

Note. PeopleSoft PeopleTools 8.44 and later do not use environment variables to discover the installation location of Oracle Tuxedo 8.1 and later. The PSADMIN tool retrieves these values from the Microsoft Windows registry.

3. Your library path on UNIX (whichever of the environment variables `LD_LIBRARY_PATH`, `LIBPATH`, or `SHLIB_PATH` is appropriate for your platform) must contain `TUXDIR/lib` for the earlier Oracle Tuxedo version before any entries for Oracle Tuxedo 12cR2.

For example the setting `LD_LIBRARY_PATH=/lib:/usr/lib:/home/user/Oracle/tuxedo12cR2/lib:/prod/tuxedo/8.1/lib`, will cause your pre-8.49 domains to no longer work. You would need to change this to `LD_LIBRARY_PATH=/lib:/usr/lib:/prod/tuxedo/8.1/lib:/home/user/Oracle/tuxedo12cR2/lib` for your pre-8.49 domains to work.

Alternatively, you can set the environment variables for a desired release using these steps:

1. Go to the `TUXDIR` directory for the release that you want to run and run the command `./tux.env`.
This command sets the environment variables needed to run Oracle Tuxedo.
2. Verify the correct Oracle Tuxedo version by running this command:

```
tmadmin -v
```

See Verifying the Server Installation on UNIX.

Changing the TListen Port

Installing Oracle Tuxedo 12cR2 and earlier creates a new service known as TListen. In most cases, you can disable this service as it is not required to run PeopleSoft PeopleTools application server domains. However, if you intend to use the Tuxedo Web Monitor you may wish to ensure that there is no port clash with earlier versions. This port is determined at installation and should be changed to a port other than the default 3050 if you intend on using the TListen service for Oracle Tuxedo 12cR2 and earlier Oracle Tuxedo versions concurrently.

Chapter 13A

Configuring the Application Server on Windows

This chapter discusses:

- Understanding the Application Server
- Prerequisites
- Creating a Wallet for the SSL/TLS Setup
- Setting Up COBOL for Remote Call
- Verifying Database Connectivity
- Creating, Configuring, and Starting an Initial Application Server Domain

Understanding the Application Server

The information in this chapter is provided to help you configure your PeopleSoft application server.

Note. COBOL is not needed for PeopleSoft PeopleTools or for PeopleSoft Applications that contain no COBOL programs. Check the information on My Oracle Support, and your application-specific documentation, for the details on whether your application requires COBOL.

Oracle supports a Microsoft Windows application server to use with any of our supported databases for the PeopleSoft installation. For detailed information, consult the certification information on My Oracle Support. The application server support can be found on the certification pages for PeopleSoft systems.

You can install the application server using either a "logical" or "physical" three-tier configuration.

- Installing the application server on the same machine as the database server is known as a logical three-tier configuration. For your initial PeopleSoft installation, Oracle suggests that you install a logical configuration to simplify setup.
- Installing the application server on a machine separate from the database server machine is known as a physical three-tier configuration.

The configuration and log files for application server domains reside in *PS_CFG_HOME*. If you do not set a *PS_CFG_HOME* environment variable before beginning the application server configuration, the system installs it in a default location based on the current user's settings, as follows:

```
%USERPROFILE%\psft\pt\<peopletools_version>
```

See "Preparing for Installation," Defining Installation Locations.

Note. You can start application servers as a Windows service, which means that administrators no longer need to manually start each application server that runs on a Windows machine.

See Also

"Preparing for Installation," Understanding PeopleSoft Servers and Clients

"Setting Up Process Scheduler on Windows," Starting Process Scheduler as a Windows Service

PeopleTools: System and Server Administration, "Using PSADMIN Menus"

PeopleTools: Data Management

My Oracle Support, Certifications

"Setting Up the Install Workstation"

"Installing and Compiling COBOL on Windows"

Prerequisites

Before beginning this procedure, you should have completed the following tasks:

- Installed your application server.
See "Using the PeopleSoft Installer," Planning Your Initial Configuration.
- Installed the supported version of Oracle Tuxedo
See "Installing Additional Components."
- Set up SSL/TLS protocol for the workstation connection.
The Secure Socket Layers/Transport Layer Security (SSL/TLS) protocol is supported for Workstation Listener and Jolt Listener ports for the current PeopleSoft PeopleTools release. The application server domain configuration requires a wallet. You can use the delivered wallet or create your own.
See *PeopleTools: Integration Broker*, "Installing Web Server-Based Digital Certificates."
- Granted authorization to a PeopleSoft user ID to start the application server.
The database configuration procedure includes a step for setting up the user ID with authorization to start the application server. See the application-specific installation instructions for information on the user IDs for your PeopleSoft application. See the *PeopleTools: Security Administration* product documentation for information on PeopleSoft PeopleTools delivered user profiles.
See "Creating a Database on UNIX," Running the Database Configuration Wizard.
See "Creating a Database Manually on Microsoft Windows or UNIX," Creating Data Mover Import Scripts.
- Run the following SQL statements on your database server to review and if needed, update the PSCLASSDEFN table:

```
SELECT CLASSID, STARTAPPSERVER FROM PSCLASSDEFN
WHERE CLASSID IN (SELECT OPRCLASS FROM PSOPRCLS WHERE OPRID='<OPRID>')
UPDATE PSCLASSDEFN SET STARTAPPSERVER=1 WHERE CLASSID='<CLASSID>'
```

Note. Installers typically use VP1 or PS to test the application server. If these users are deleted or their passwords are changed, the application server will no longer be available. To avoid this problem, you can set up a new operator (called PSADMIN or PSASID, for instance) with privileges to start the application server. If you do this, you can use the new operator for your application servers and you won't need to change the password each time VP1 or PS is changed.

See Also

"Creating a Database Manually on Microsoft Windows or UNIX," Configuring an ODBC Data Source for Connectivity on Microsoft Windows

Task 13A-1: Creating a Wallet for the SSL/TLS Setup

This section discusses:

- Using the Delivered Wallet
- Creating a Wallet with OpenSSL

Task 13A-1-1: Using the Delivered Wallet

Before you configure the application server to use the SSL/TLS protocol, you need a wallet. Use these instructions to create wallets for the application server and workstation client.

Note. The term "Oracle Wallet" is sometimes used in the software and documentation, for example in PSADMIN custom configuration, to refer to wallets on all RDBMS. In this context it does not refer to an entity specific to an Oracle RDBMS.

You also have the option to use the wallets that are included with the PeopleSoft PeopleTools installation. The default wallet for the application server is named psft and is located in `$PS_SERVDIR/security`. When you configure the application server, define the default wallet as follows:

- `SEC_PRINCIPAL_LOCATION=%PS_SERVDIR%\security`
- `SEC_PRINCIPAL_NAME=psft`

To specify the default wallet for the workstation client:

- `SEC_PRINCIPAL_LOCATION=PS_HOME\bin\client\winx86\security`
- `SEC_PRINCIPAL_NAME=wscpsft`

The default Java Keystore file used for the SSL/TLS configuration for JSL ports is located in `<PIA_HOME>\webserv\<DOMAIN_NAME>\piaconfig\keystore\pskey`. If you change the Keystore password in this file, you must also provide the password in the PIA configuration.properties file at `<PIA_HOME>\webserv\<DOMAIN_NAME>\application\peoplesoft\PORTAL.war\WEB_INF\psftdoc\ps`.

Task 13A-1-2: Creating a Wallet with OpenSSL

This section discusses:

- Defining OpenSSL Options
- Creating a Server Wallet for the Application Server Domain with OpenSSL
- Creating a Client Wallet for the Workstation Client with OpenSSL
- Adding the Server's Certificate to the Client's Trust Store with OpenSSL

Defining OpenSSL Options

An example of an OpenSSL command that can be used to create a wallet is as follows.

For more information, see the OpenSSL documentation.

```
openssl pkcs12 -export -out ewallet.p12 -inkey server.key -in server.crt ->
chain -CAfile caCert.crt -passout pass:<password>
```

- **-export:** indicates that a PKCS 12 file is being created
- **-chain:** specifies that an attempt is made to include the entire certificate chain of the user certificate
- **-inkey:** specifies the private key file
- **-in:** specifies the file that contains the user certificate and any other certificates in the certificate chain
- **-CAfile:** specifies a file containing trusted certificates
- **-out:** specifies the output file name, which must be ewallet.p12 for an Oracle Wallet for PeopleSoft installations.
- **-passin:** specifies the password for the private key file
- **-passout:** specifies the password for the newly created wallet

Creating a Server Wallet for the Application Server Domain with OpenSSL

This section gives an example of creating a wallet for the application server with the open-source tool OpenSSL.

1. Create a directory, for example wallet.server.

For example on Microsoft Windows:

```
mkdir C:\wallet.server
```

2. Change directory to wallet.server.

```
cd wallet.server
```

3. Enter the following command:

```
openssl genrsa -out server.key 4096
```

4. Enter the following command.

```
openssl req -new -key server.key -out server.csr -subj <subject>
```

For example:

```
openssl req -new -key server.key -out server.csr -subj '/C=country/CN=>
commonName'
```

The *<subject>* values in this step and step 7 are used to replace the specified data in an input request, and output a modified request. The format for *<subject>* is *'/type0=value0/type1=value1/type2= . . . '*. Characters must be escaped with a backslash (\), and no spaces are skipped. Use the following fields:

- /C — Country
- /CN — Common name
- /L — Location

- /O — Organization
- /OU — Organizational Unit
- /ST — State

5. Enter the following command:

```
openssl genrsa -out caCert.key 4096
```

6. Enter the following command,

```
openssl req -new -x509 -days 1826 -key caCert.key -out caCert.crt -subj =>
<subject>
```

For example:

```
openssl req -new -x509 -days 1826 -key caCert.key -out caCert.crt -subj=>
'/C=US/OU=Class 2 Public Primary Certification Authority/O=My=>
Organization'
```

7. Enter the following command:

```
openssl x509 -req -days 730 -in server.csr -CA caCert.crt -CAkey ca=>
Cert.key -set_serial 01 -out server.crt
```

8. Enter the following command to create the wallet ewallet.p12 and specify the server password:

```
openssl pkcs12 -export -out ewallet.p12 -inkey server.key -in=>
server.crt -chain -CAfile caCert.crt -passout pass:<server_password>
```

Creating a Client Wallet for the Workstation Client with OpenSSL

This section gives an example of creating a client wallet with the open-source tool OpenSSL.

1. Create a directory, for example wallet.client, and change to that directory.

```
mkdir wallet.client
cd wallet.client
```

2. Copy the server's trust store to the client wallet.

```
cp wallet.server\caCert.crt wallet.client
cp wallet.server\caCert.key wallet.client
```

3. Enter these commands:

```
openssl genrsa -out client.key 4096
```

4. Run this command:

```
openssl req -new -key client.key -out client.csr -subj <subject>
```

For example:

```
openssl req -new -key client.key -out client.csr -subj '/C=country/CN=>
commonName'
```

5. Run this command:

```
openssl x509 -req -days 730 -in client.csr -CA caCert.crt -CAkey ca=>
```

```
Cert.key -set_serial 01 -out client.crt
```

6. Enter the following command to create the wallet ewallet.p12 and specify the client password:

```
openssl pkcs12 -export -out ewallet.p12 -inkey client.key -in⇒
client.crt -chain -CAfile caCert.crt -passout pass:<client_password>
```

7. Remove the client wallet password:

- a. Make a backup copy of the wallet, ewallet.p12:

On Microsoft Windows:

```
xcopy ewallet.p12 oldwallet.p12
```

- b. Run this command:

```
openssl pkcs12 -clcerts -nokeys -in oldwallet.p12 -out⇒
certificate.crt -password pass:<client_password> -passin pass:⇒
<client_password>
```

- c. Run this command:

```
openssl pkcs12 -cacerts -nokeys -in oldwallet.p12 -out ca-cert.ca -⇒
password pass:C<client_password> -passin pass:<client_password>
```

- d. Run this command:

```
openssl pkcs12 -nocerts -in oldwallet.p12 -out private.key -password⇒
pass:<client_password> -passin pass:<client_password> -passout pass:⇒
temp
```

- e. Run this command:

```
openssl rsa -in private.key -out NewKeyFile.key -passin pass:temp
```

- f. Run the command to create the PEM.pem file.

This file is created to copy the public key and root certificates.

On Microsoft Windows:

```
type certificate.crt ca-cert.ca >PEM.pem
```

- g. Run this command:

```
openssl pkcs12 -export -nodes -in PEM.pem -inkey NewKeyFile.key -out⇒
ewallet.p12 -passout pass:TrustedCertsOnlyNoPWNeeded
```

Adding the Server's Certificate to the Client's Trust Store with OpenSSL

To complete the setup, add the application server's certificate to the workstation client's trust store:

1. Change directory.

```
cd %ORACLE_HOME%\jdk\bin
```

2. Add the certificate to the trust store found in the web server directory for the application server domain.

```
keytool -import -file <server_wallet>/<certificate> -alias srvcert -⇒
keystore <PIA_HOME>\webserver\<DOMAIN_NAME>\piaconfig\keystore\pskey -⇒
```



```
storepass password -noprompt
```

For example, on Microsoft Windows:

```
keytool -import -file wallet.server/caCert.crt -alias srvcert -keystore⇒  
C:\user\psft\pt\8.57\webserve\ps\piaconfig\keystore\pskey -storepass⇒  
password -noprompt
```

Task 13A-2: Setting Up COBOL for Remote Call

Remote Call is a PeopleCode feature that launches a COBOL program from an application server, PeopleCode program or a batch Application Engine PeopleCode program and waits for it to complete execution before continuing. The execution of a COBOL program via Remote Call is completely independent of the Process Scheduler. You need to set up a COBOL runtime environment and COBOL executables on the application server to support Remote Call.

See "Installing and Compiling COBOL on Windows."

Note. If your application does not contain COBOL programs, you do not need to purchase or compile COBOL.

Task 13A-3: Verifying Database Connectivity

Before continuing, it is critical to verify connectivity to the database that the application server domain will use. To verify connectivity, connect to the database server from the application server using the native SQL tool on the application server.

For DB2 for Linux, UNIX, and Windows, use the Command Center.

Task 13A-4: Creating, Configuring, and Starting an Initial Application Server Domain

This section discusses:

- Creating, Configuring, and Starting the Application Server Domain
- Testing the Three-Tier Connection
- Importing an Existing Application Server Domain Configuration
- Setting Up a Custom Application Server Domain Configuration
- Troubleshooting Common Errors

Task 13A-4-1: Creating, Configuring, and Starting the Application Server Domain

To create, configure, and start the application server domain:

1. Run the `psadmin` command.

You see the PeopleSoft Server Administration menu, as in this example:

```

-----
PeopleSoft Server Administration
-----

```

```

PS_CFG_HOME:  C:\Users\JSMITH\psft\pt\8.57
PS_HOME:      C:\psft\pt\ps_home8.57
PS_APP_HOME:  C:\psft\pt\hcm_app_home

```

- ```

1) Application Server
2) Process Scheduler
3) Search Server
4) Web (PIA) Server
5) Switch Config Home
6) Service Setup
7) Replicate Config Home
8) Refresh Config Home
q) Quit

```

Command to execute (1-8, q): **1**

---

**Note.** Make sure you change the directory from the *PS\_HOME* on the file server to the *PS\_HOME*, or high-level directory, on the application server.

---

- Depending on your environment, you may see a message after the initial menu, which indicates that PSADMIN has modified the *PS\_CFG\_HOME*/peopletools.properties file with the current *PS\_HOME* location:

```

PS_CFG_HOME/peopletools.properties file has been updated.
You should use the Config Home Refresh feature in PSAdmin
to ensure that all of your domains are current.
Alternatively, you may recreate all of your domains.
Please press any key to continue...

```

This indicates that one of these situations exists:

- The *PS\_CFG\_HOME* that you are working with was used previously from a different *PS\_HOME*. In this case, you should recreate any existing Application Server, Process Scheduler, Search, or PIA domains in this *PS\_CFG\_HOME*.
- You configured your environment such that *PS\_CFG\_HOME* is the same as *PS\_HOME*. The first time you use PSADMIN to create a domain, it updates the *PS\_CFG\_HOME*/peopletools.properties file. Continue with the next step.

- Specify **1** for Application Server and press ENTER.
- Specify **2** to Create a domain and press ENTER.

```

PeopleSoft Application Server Administration

```

- ```

1) Administer a domain
2) Create a domain
3) Delete a domain
4) Import domain configuration

```

q) Quit

Command to execute (1-4, q): **2**

5. Specify the domain name.

In this example the domain name is HRDMO:

Please enter name of domain to create : **HRDMO**

Domain names are case sensitive and must be eight US-ASCII characters or less. The domain name is used to create a directory name under the *PS_CFG_HOME*\appserv directory.

See the information on *PS_CFG_HOME* and server domain configuration in the *PeopleTools: System and Server Administration* product documentation.

6. Specify 4 for small if this is your initial domain installation, press ENTER.

See *PeopleTools: System and Server Administration*.

7. After the system creates the domain, the PeopleSoft Application Server Administration menu appears with a Quick-configure menu similar to this:

```
-----
Quick-configure menu -- domain: HRDMO
-----
```

Features =====	Settings =====
1) Pub/Sub Servers : No	17) DBNAME : [HRDMO]
2) Quick Server : No	18) DBTYPE : [DB2UNIX]
3) Query Servers : No	19) UserId : [QEDMO]
4) Jolt : Yes	20) UserPswd : []
5) Jolt Relay : No	21) DomainID : [TESTSERV]
6) WSL : No	22) AddToPATH : [C:\Apps\db⇒
\db2odbc91\bin]	
7) PC Debugger : No	23) ConnectID : [people]
8) Event Notification : Yes	24) ConnectPswd : []
9) MCF Servers : No	25) DomainConnectPswd: []
10) Perf Collator : No	26) WSL Port : [7000]
11) Analytic Servers : Yes	27) WSL SSL Port : [7010]
12) Domains Gateway : No	28) JSL Port : [9000]
13) Push Notifications : No	29) JSL SSL Port : [9010]
	30) JRAD Port : [9100]

Actions =====
14) Load config as shown
15) Custom configuration
16) Edit environment settings
h) Help for this menu
q) Return to previous menu

HINT: Enter 17 to edit DBNAME, then 14 to load

Enter selection (1-28, h, or q):

Note. If your installation includes more than one application server domain on a given machine, read the troubleshooting section for more information.

See Troubleshooting Common Errors.

8. If you need to modify any of the values for these settings, enter the number next to the parameter name, press ENTER, then type the new value, and press ENTER again.

If you need to change any of the features, type the number next to the feature name and press ENTER.

9. Configure the WSL to boot by changing option 6 to Yes.

Enter 6, and press ENTER.

10. If you intend to use the PeopleSoft Report Distribution system, you must select Yes for feature 8, Event Notification.

This enables the REN server, which is used by the "run to window" functionality of the Report Distribution system. *The Report Distribution system, MultiChannel Framework, and Optimization Framework use REN servers.* You must also remember to enter an Authentication Token Domain when installing the PeopleSoft Pure Internet Architecture (PIA).

11. If you are configuring an application server domain to support applications based on the PeopleSoft MultiChannel Framework (such as PeopleSoft CRM ERMS), select feature 9, MCF Servers.

See the information on configuring REN Servers in the product documentation.

See *PeopleTools: MultiChannel Framework*.

12. Enter 22 for AddToPATH, and enter the path to the 64-bit connectivity software. For example:

```
C:\sqllib\bin
```

Note. You can skip this step if the PATH environment variable already includes the database connectivity path.

13. Enter the values for the 20) UserPswd and 24) ConnectPswd that you specified during the database configuration.

Reenter each password to verify the value. The password is hidden by masking characters as you type and in the Quick-configure menu.

14. If you want to set a Domain Connection password, enter 25 and specify a password of 8 characters or less.

Reenter the password to verify the value. The password is hidden by masking characters as you type and in the Quick-configure menu.

The Domain Connection password is optional. You can specify a value or leave it blank. However, if you do specify a value, you must supply the same value when installing the PeopleSoft Pure Internet Architecture, to ensure the connection to the Application Server.

15. To set up the Workstation Listener for SSL/TLS protocol, enter 27 for WSL SSL Port, and specify an available port number.

The default port number is 7010.

16. To set up the Jolt listener for SSL/TLS protocol, enter 29 for JSL SSL Port, and specify an available port number.

The default port number is 9010.

17. Use the custom configuration menu to specify the settings for SSL/TLS encryption and the wallet location.

See *PeopleTools: Integration Broker*, "Installing Web Server-Based Digital Certificates."

- a. To specify the minimum and maximum encryption for SSL/TLS, select 15 for Custom Configuration.

- b. Reply y, and press ENTER, at this prompt:

```
Do you want to change any config values (y/n) [n]?
```

- c. Reply *n*, and press ENTER, at this prompt:

Do you want to change any values (y/n) [n]?

Continue to enter *n*, for No, for all sections until you see the Workstation Listener section, and then answer *y*. (Be aware that there are several sections.)

- d. If necessary, change the values for WSL minimum and maximum encryption to correspond to your installed SSL/TLS cipher. The default minimum is 0 and the default maximum is 256. The maximum is the number of bits that indicates the highest level of encryption possible for the installed SSL/TLS version.

Values for config section - Workstation Listener

```
Address=%PS_MACH%
Port=7000
SSL Port=7010
WSL Min Encryption=0
WSL Max Encrytion=256
Min Handlers=1
Max Handlers=2
Max Clients per Handler=40
Client Cleanup Timeout=60
Init Timeout=5
Tuxedo Compression Threshold=5000
```

- e. Accept the defaults for the next series of questions until asked if you want Oracle Wallet configured. In this case, answer *y*.

- f. Specify the values for the Oracle Wallet location, name, and password, or accept the defaults.

You can use an existing wallet that you created, or use the default wallet found in the security directory.

Values for config section - Oracle Wallet

```
SEC_PRINCIPAL_LOCATION=%PS_SERVDIR%\security
SEC_PRINCIPAL_NAME=psft
SEC_PRINCIPAL_PASSWORD=
```

- g. Accept the defaults for the next series of questions until asked if you want the JOLT Listener configured. In this case, answer *y*

- h. If necessary, change the values for JSL minimum and maximum encryption to correspond to your installed SSL/TLS cipher. The default minimum is 0 and the default maximum is 256. The maximum is the number of bits that indicates the highest level of encryption possible for the installed SSL/TLS version.

Values for config section - JOLT Listener

```
Address=%PS_MACH%
Port=9000
SSL Port=9010
JSL Min Encryption=0
JSL Max Encrytion=256
Min Handlers=1
Max Handlers=2
Max Clients per Handler=40
Client Cleanup Timeout=10
Init Timeout=5
Client Connection Mode=ANY
Jolt Compression Threshold=1000000
```

- i. Accept the default for the remaining questions; the configuration will load automatically.

18. If you are installing a REN server:

- a. Enter *15* for Custom configuration.
- b. Reply *y*, and press ENTER, at this prompt:
Do you want to change any config values (y/n) [n]?
- c. Reply *n*, and press ENTER, at this prompt:
Do you want to change any values (y/n) [n]?

Continue to enter *n*, for No, for all sections until you see the PSRENSRV section, and then answer *y*. (Be aware that there are several sections.)

- d. Leave the defaults for all settings except for default_auth_token, which you should set to the domain name for your web server.

Note. The default_auth_token setting should be identical to the Authentication Token Domain that you set during PIA installation.

See "Setting Up the PeopleSoft Pure Internet Architecture in GUI Mode."

- e. Accept the defaults for the next series of questions until asked if you want Event Notification configured. In this case, answer *y*.
 - f. Accept the default for the remaining questions; the configuration will load automatically.
19. If you are not installing a REN server, after you update the settings you can load the configuration by entering *14*, for Load config as shown, from the Quick-configure menu.
 20. To start the application server (whether you installed a REN server or not), select *1*, Boot this domain, from the PeopleSoft Domain administration menu.
 21. Select *1*, Boot (Serial Boot) or *2*, Parallel Boot, from the PeopleSoft Domain Boot Menu.

Note. The messages you see and the number of processes started will depend on the options you chose during configuration.

22. If you plan to continue with PIA installation and testing, do not shut down the application server at this time.
23. If you want to shut down your PeopleSoft application server domain later, follow these simple steps:
 - a. From the PeopleSoft Domain Administration menu, enter *2* for Domain shutdown menu.
 - b. From the PeopleTools Domain Shutdown Menu, enter *1* for Normal shutdown.
You see messages about the application server processes being shut down. The number of processes stopped will vary depending on the number of processes that started when you booted the domain.
 - c. Enter *q* to quit the PeopleSoft Domain Administration Menu.

Task 13A-4-2: Testing the Three-Tier Connection

If you get an error message when you try to sign in to the Application Server in Application Designer (that is, three-tier mode), it may be due to an incorrect server name or port number, because the database server is not running, or because the application server was not booted. To test a three-tier connection from the PeopleTools Development Environment (the Windows-based client):

1. Start Configuration Manager with one of these methods:
 - On Microsoft Windows 7, select Start, Programs, PeopleTools 8.57, Configuration Manager.
 - On Microsoft Windows 8 or 2012 R2, access the Apps screen and navigate to PeopleTools 8.57, Configuration Manager.

- Run *PS_HOME\bin\client\winx86\pscfg.exe*.
2. Select the Profile Tab. Highlight Default and select Edit.
 3. On the Edit Profile dialog box, select *Application Server* as the Connection Type.
 4. Enter values for these parameters:
 - Application Server Name
 - Machine Name or IP Address
 - Port Number (WSL)

Enter the WSL port that you specified when creating the application server domain. If you want to use the SSL/TLS protocol for connection, enter the WSL SSL port number (the default is 7010). If you want to use the LLE protocol, enter the non-SSL WSL port (the default is 7000).
 - Domain Connection Password and Domain Connection Password (confirm)

Specify a value for the password, and repeat your entry for confirmation. The password must be 8 characters or less.

This password is optional. If you did not set the Domain Connection Password in Configuration Manager or in the Application Server configuration, leave it blank. If you specify a password, you must supply the same password during the PeopleSoft Pure Internet Architecture installation for a successful connection between the Application Server and PeopleSoft Pure Internet Architecture.

See the *PeopleTools: System and Server Administration* product documentation for information on using PeopleSoft Configuration Manager and PSADMIN.
 - Wallet Location

Enter the location that you specified for the client wallet. The default location is %PS_HOME%\bin\client\winx86\security.
 - Wallet Name

Enter the name for the client wallet that you specified. The default name is wscpsft.
 5. Select Set to add the definition to the list and select OK to close the dialog box.
 6. On the Configuration Manager dialog box, select the Startup tab.
 7. Select *Application Server* from the Database Type list. Your application server name should be displayed.
 8. Enter the values for User ID, Connect ID, and password.
 9. Click OK.

Note. Confirm that the application server is running by booting it from PSADMIN. Select *1, Boot* this domain, from the PeopleSoft Domain administration menu. Select option *1, Boot (Serial Boot)* or *2, Parallel Boot*, from the PeopleSoft Domain Boot menu.

10. Start Application Designer with one of these methods:
 - On Microsoft Windows 7, select Start, Programs, PeopleTools 8.57, Application Designer.
 - On Microsoft Windows 8 or 2012 R2, access the Apps screen and navigate to PeopleTools 8.57, Application Designer.
 - Run *PS_HOME\bin\client\winx86\pside.exe*.
11. In the PeopleSoft Signon dialog box:
 - Select *Application Server* as the Connection Type.
 - Confirm that the Application Server Name is correct.
 - Enter values for User ID and password.

12. Select OK to open Application Designer.

If you see the following error message when you try to sign in to the Application Server in Application Designer:

```
Network API: "Could not connect to application server 'Application Server⇒
Name' Make sure the PeopleTools authentication server (PSAUTH) is booted."
```

This may indicate a problem with the Domain Connection Password. For example, if the password set in the Application Server configuration file does not match the value in Configuration Manager, you may get this error message when you sign in to Application Designer in three-tier mode. Check the Application Server logs for more information.

Task 13A-4-3: Importing an Existing Application Server Domain Configuration

If you have an existing application server configuration for a previous PeopleSoft PeopleTools release, you can import it to create a new domain. You can import an existing domain configuration by specifying a file or by specifying the path to an existing domain. To import from a file, you must use the `psappsrv.cfg` file found inside an existing application server domain folder (you must specify the full path to `psappsrv.cfg`). This file can be located anywhere in the file system, but must be named `psappsrv.cfg`. To import from an existing domain configuration that you created in the current PeopleSoft PeopleTools release, you must specify `PS_CFG_HOME` and the name of an existing application server domain. (If you are importing a domain from a release before PeopleSoft PeopleTools 8.50, note that the domains were created in `PS_HOME`, and that is the path that you should provide.)

To import an existing application server domain configuration:

1. Go to the `PS_HOME\appserv` directory and run the `psadmin` command.

You see the PeopleSoft Server Administration menu, as in this example:

```
-----
PeopleSoft Server Administration
-----

PS_CFG_HOME:  C:\Users\JSMITH\psft\pt\8.57
PS_HOME:      C:\psft\pt\ps_home8.57
PS_APP_HOME:  C:\psft\pt\hcm_app_home

1) Application Server
2) Process Scheduler
3) Search Server
4) Web (PIA) Server
5) Switch Config Home
6) Service Setup
7) Replicate Config Home
8) Refresh Config Home
q) Quit
```

Command to execute (1-8, q): **1**

The `PS_CONFIG_HOME` location, also referred to as Config Home, corresponds to the current working directory. For information on how Config Home is set, see the *PeopleTools: System and Server Administration* product documentation.

Note. Make sure you change the directory from the *PS_HOME* on the file server to the *PS_HOME* on the application server.

2. Depending on your environment, you may see a message after the initial menu, which indicates that PSADMIN has modified the *PS_CFG_HOME*/peopletools.properties file with the current *PS_HOME* location:

```
*****
PS_CFG_HOME/peopletools.properties file has been updated.
You should use the Config Home Refresh feature in PSAdmin
to ensure that all of your domains are current.
Alternatively, you may recreate all of your domains.
Please press any key to continue...
*****
```

This indicates that one of these situations exists:

- The *PS_CFG_HOME* that you are working with was used previously from a different *PS_HOME*. In this case, you should recreate any existing Application Server, Process Scheduler, Search, or PIA domains in this *PS_CFG_HOME*.
- You configured your environment such that *PS_CFG_HOME* is the same as *PS_HOME*. The first time you use PSADMIN to create a domain, it updates the *PS_CFG_HOME*/peopletools.properties file. Continue with the next step.

3. Specify *1* for Application Server.
4. Specify *4* for Import domain configuration.

```
-----
PeopleSoft Application Server Administration
-----
```

- ```
1) Administer a domain
2) Create a domain
3) Delete a domain
4) Import domain configuration
q) Quit
```

Command to execute (1-4, q): **4**

5. Specify *1* for Import regular domain.

```

PeopleSoft Import Application Server Configuration

```

- ```
1) Import regular domain
2) Import IB Master Configuration
q) Quit
```

Command to execute (1-2, q) : **1**

6. Specify whether to import the domain configuration from a file (option 1) or from an existing application domain configuration (option 2).

```
-----
PeopleSoft Import Application Server Configuration
-----
```

- 1) Import from file
- 2) Import from application domain
- q) Quit

Command to execute (1-2, q) :

7. If you selected 1, provide the full path to the file `psappsrv.cfg`, and then specify the name of the domain you want to create. If you selected 2, go to the next step.

Enter full path to configuration file
:C:\temp\oldconfig\psappsrv.cfg

Enter domain name to create
:HRDMO

8. If you selected 2, to Import from application domain, provide the full path to the `PS_CFG_HOME` of the existing domain.

If importing from PeopleTools 8.49 or earlier, provide `PS_HOME` for `PS_CFG_HOME`.

Enter `PS_CFG_HOME` of domain you wish to import: C:\Users\JSMITH\psft\pt⇒\8.57

If applicable, choose among the existing application server domains in the specified `PS_CFG_HOME`:

Tuxedo domain list:

- 1) HRDBA
- 2) HRDBB

Select domain number to import: **1**

Enter a name for new domain: **HRDMO**

After you create the domain, continue to the next task to verify that the imported configuration parameters are appropriate for the newly created domain. You may need to change the following values:

- **DBName**
DBName can be the same or different, depending on which database the application server needs to point to.
- **DBType**
DBType depends on the database type of DBName.
- **UserId and UserPswd**
UserId and UserPswd are the user's choice.
- **Workstation Listener Port**
Workstation Listener Port will need to be modified if the old domain will be up and running in the same machine.
- **Jolt Listener Port**
Jolt Listener Port will also need a different number if the old domain will be up and running in the same machine.
- **Jolt Relay Adapter Listener Port**
Jolt Relay Adapter Listener Port will need a different number if the old domain will be up and running in the same machine, and will be using Jolt Relay Adapter.

Task 13A-4-4: Setting Up a Custom Application Server Domain Configuration

The Quick-configure menu is initially displayed when you choose to configure your domain. This menu is intended for the commonly adjusted parameters—those most likely to change from domain to domain. However, there are additional configuration parameters that are not available through the Quick-configure menu. For such configuration parameters, you must use the Custom Configuration option, which you can access from the Quick-configure menu. Feel free to skip this procedure if you have already created and configured your Application Server using the Quick-configure menu and want to move forward.

The following steps assume you will be using PSADMIN to specify parameter settings.

To reconfigure an application server domain:

1. Go to the *PS_HOME*\appsrv directory and run the `psadmin` command.

Note. Make sure you change the directory from the *PS_HOME* on the file server to the *PS_HOME* on the application server.

2. Depending on your environment, you may see a message after the initial menu, which indicates that PSADMIN has modified the *PS_CFG_HOME*/peopletools.properties file with the current *PS_HOME* location:

```
*****
PS_CFG_HOME/peopletools.properties file has been updated.
You should use the Config Home Refresh feature in PSAdmin
to ensure that all of your domains are current.
Alternatively, you may recreate all of your domains.
Please press any key to continue...
*****
```

This indicates that one of these situations exists:

- The *PS_CFG_HOME* that you are working with was used previously from a different *PS_HOME*. In this case, you should recreate any existing Application Server, Process Scheduler, Search, or PIA domains in this *PS_CFG_HOME*.
 - You configured your environment such that *PS_CFG_HOME* is the same as *PS_HOME*. The first time you use PSADMIN to create a domain, it updates the *PS_CFG_HOME*/peopletools.properties file. Continue with the next step.
3. Specify *1* for Application Server and press ENTER.
 4. Specify *1* for Administer a domain and press ENTER.
 5. Select the domain to administer and press ENTER.
 6. Specify *4* for Configure this domain and press ENTER.

The option Configure this domain performs the following tasks:

- Shuts down the application server, if it is running. (Shutdown is required since the binary file PSTUXCFG must be deleted and re-created to enable new configuration values. If there are no processes running when shutdown is attempted, an error will be displayed but the script continues on. This is normal.)
 - Initiates an interactive dialog, prompting for configuration parameters.
 - Updates psappsrv.cfg, generates psappsrv.ubb, and internally invokes Tuxedo's tmloadcf executable to create binary file PSTUXCFG used during the domain boot process.
7. Specify *15* for Custom Configuration and press ENTER.

8. Respond to this prompt:

Do you want to change any config values (y/n):

- Specify *y* to start an interactive dialog to change or examine parameter values, as described in the next step.

Oracle recommends this option for more experienced users.

- Specify *n* if you have already edited `psappsrv.cfg`, skip the next step, and continue with the step to select server process options.

9. Complete the interactive dialog to specify configuration parameters.

Configuration parameters are grouped into sections. For each section, you are asked whether you want to change any parameters in that section, as in the following example:

Values for config section - Startup

```

DBName=
DBType=
UserId=
UserPswd=
ConnectId=
ConnectPswd=
ServerName=
StandbyDBName=
StandbyDBType=
StandbyUserId=
StandbyUserPswd=
InMemoryDBName=
InMemoryDBType=

```

Do you want to change any values (y/n)? [n]: y

- Specify *y* to change any parameter values for the current configuration section displayed.

You are prompted for each parameter value. Either specify a new value, or press ENTER to accept the default if applicable. After pressing ENTER, you are positioned at the next parameter in that section. When you are done with that section, you are again asked whether you want to re-edit any of the values you changed.

- Enter the user ID and user password that has security to start the application server. All application databases are delivered with one or more application server security users, usually PS or VP1.

The password you enter is hidden by masking characters.

- The parameters `StandbyDBName`, `StandbyDBType`, `StandbyUserId`, and `StandbyUserPswd`, are used for a standby database in an Oracle environment.

See *PeopleTools: Data Management*, "Implementing Oracle Active Data Guard."

- The parameters `InMemoryDBName` and `InMemoryDBType` are reserved for internal use.
- The WSL, JSL, and JRAD port numbers, which are found in other sections of the configuration parameters, have default values of 7000, 9000, and 9100, respectively. These values must be unique for each application server domain. You may alter the port values if necessary to ensure that they are unique.
- If you do not wish to change any values, specify *n* and you will be prompted for the next configuration section.

Note. When setting up your application server, make a note of the values you use for Database Name, Application Server Name (the machine name), and JSL Port. You will need to use these same values when installing the PeopleSoft Pure Internet Architecture.

See *PeopleTools: System and Server Administration*.

10. Select server process options.

At this point, you will be prompted to select server process options. If this is your initial installation, we suggest you accept the defaults. A message similar to this appears:

```
Setting Log Directory to the default... [PS_SERVDIR\LOGS]
Configuration file successfully created.
Loading new configuration...
```

The message "Loading new configuration" indicates that PSADMIN is generating a binary file named PSTUXCFG, which is used to boot the application server. At this point, your application server should be properly configured.

Task 13A-4-5: Troubleshooting Common Errors

For troubleshooting help, you can access a log file through the PSADMIN PeopleSoft Domain Administration menu. The following list includes possible errors and troubleshooting tips.

- Use PSADMIN menu option 6 for Edit configuration/log files menu to check for errors in `<PS_CFG_HOME>\appserv\<domain>\LOGS\APPSRV_mmdd.log` and `<PS_CFG_HOME>\appserv\<domain>\LOGS\TUXLOG.mmddyy`.
- If a PeopleSoft server such as PSAPPSRV fails, examine your configuration parameters. The failure of the PSAPPSRV process is often signalled by the message "Assume failed"—which means the process has failed to start. Check the SIGNON section for misspelled or invalid database name, an invalid or unauthorized OprId, or ConnectId or ServerName is missing or invalid. Finally, make sure the database connectivity is set correctly.
- If a WSL (or JSL) fails to start, try specifying another port number (it may be in use already by another application server domain process).
- If you are unable to start the BBL, check that your Tuxedo is installed fully and that the directory really exists.
- If the installation includes more than one application server domain on a single machine, before booting the second domain, adjust the REN server configuration to avoid conflict in one of these ways:
 - Use PSADMIN to disable Event Notification (option 8 on the Quick-configure menu) for the second and subsequent app server domains.
 - Change default_http_port to a value other than 7180.

See Also

PeopleTools: System and Server Administration

PeopleTools: MultiChannel Framework

Chapter 13B

Configuring the Application Server on UNIX

This chapter discusses:

- Understanding the Application Server
- Understanding the Application Server Domain Processes
- Prerequisites
- Creating a Wallet for the SSL/TLS Setup
- Setting Environment Variables
- Setting Up COBOL for Remote Call
- Verifying Database Connectivity
- Creating, Configuring, and Starting an Initial Application Server Domain

Understanding the Application Server

The information in this chapter is provided to help you configure your PeopleSoft application server.

Note. COBOL is not needed for PeopleSoft PeopleTools or for PeopleSoft Applications that contain no COBOL programs. Check the information on My Oracle Support, and your application-specific documentation, for the details on whether your application requires COBOL.

Oracle supports application servers for the PeopleSoft installation on several UNIX and Linux operating system platforms. For detailed information, consult the certification information on My Oracle Support. The application server support can be found on the certification pages for PeopleSoft systems.

Note. Oracle supports a number of versions of UNIX and Linux in addition to Microsoft Windows for the PeopleSoft installation. Throughout this book, there are references to operating systems. Where necessary, this book refers to specific operating systems by name (for example, Oracle Solaris, IBM AIX, or Linux); however, for simplicity the word UNIX is often used to refer to all UNIX-like operating systems, including Linux.

You can install the application server using either a "logical" or "physical" three-tier configuration.

- Installing the application server on the same machine as the database server is known as a logical three-tier configuration. For your initial PeopleSoft installation, Oracle suggests that you install a logical configuration to simplify setup.
- Installing the application server on a machine separate from the database server machine is known as a physical three-tier configuration.

The configuration and log files for application server domains reside in *PS_CFG_HOME*. If you do not set a *PS_CFG_HOME* environment variable before beginning the application server configuration, the system installs it in a default location based on the current user's settings, as follows:

```
$HOME/psft/pt/<peopletools_version>
```

See "Preparing for Installation," Defining Installation Locations.

See Also

"Preparing for Installation," Understanding PeopleSoft Servers and Clients

PeopleTools: System and Server Administration, "Using PSADMIN Menus"

PeopleTools: Data Management

My Oracle Support, Certifications

"Setting Up the Install Workstation"

"Installing and Compiling COBOL on UNIX"

Understanding the Application Server Domain Processes

On most platforms (IBM AIX, Oracle Solaris, Linux, and HP-UX Itanium) no changes are required from the system defaults, in order to allow the "small" and "development" domains that are shipped with PeopleSoft PeopleTools to boot successfully.

Refer to the performance documentation for guidance in configuring your system to run larger domains. That document describes the suggested minimum kernel settings for running PeopleSoft PeopleTools in a real-world environment.

See PeopleTools Performance Guidelines Red Paper on My Oracle Support (search for the article title).

Permanently changing system-wide parameters generally requires root privileges, and any changes to the kernel configuration of your operating system should be done with care.

If you are installing on HP-UX 11.31 operating systems, be aware that hosts with machine names longer than 8 characters require the HP-UX kernel configuration `uname_eoverflow` to be set to 0 (zero).

Prerequisites

Before beginning this procedure, you should have completed the following tasks:

- Installed your application server.
See "Using the PeopleSoft Installer," Planning Your Initial Configuration.
- Installed the supported version of Oracle Tuxedo
See "Installing Additional Components."
- Set up SSL/TLS protocol for the workstation connection.
The Secure Socket Layers/Transport Layer Security (SSL/TLS) protocol is supported for Workstation Listener and Jolt Listener ports for the current PeopleSoft PeopleTools release. The application server domain configuration requires a wallet. You can use the delivered wallet or create your own.
See *PeopleTools: Integration Broker*, "Installing Web Server-Based Digital Certificates."
- Granted authorization to a PeopleSoft user ID to start the application server.
The database configuration procedure includes a step for setting up the user ID with authorization to start the application server. See the application-specific installation instructions for information on the user IDs for your PeopleSoft application. See the *PeopleTools: Security Administration* product documentation for information on PeopleSoft PeopleTools delivered user profiles.

See "Creating a Database on UNIX," Running the Database Configuration Wizard.

See "Creating a Database Manually on Microsoft Windows or UNIX," Creating Data Mover Import Scripts.

- Run the following SQL statements on your database server to review and if needed, update the PSCLASSDEFN table:

```
SELECT CLASSID, STARTAPPSERVER FROM PSCLASSDEFN
WHERE CLASSID IN (SELECT OPRCLASS FROM PSOPRCLS WHERE OPRID='<OPRID>')
UPDATE PSCLASSDEFN SET STARTAPPSERVER=1 WHERE CLASSID='<CLASSID>'
```

Note. Installers typically use VP1 or PS to test the application server. If these users are deleted or their passwords are changed, the application server will no longer be available. To avoid this problem, you can set up a new operator (called PSADMIN or PSASID, for instance) with privileges to start the application server. If you do this, you can use the new operator for your application servers and you won't need to change the password each time VP1 or PS is changed.

Task 13B-1: Creating a Wallet for the SSL/TLS Setup

This section discusses:

- Using the Delivered Wallet
- Creating a Wallet with OpenSSL

Task 13B-1-1: Using the Delivered Wallet

Before you configure the application server to use the SSL/TLS protocol, you need a wallet. Use these instructions to create wallets for the application server and workstation client.

Note. The term "Oracle Wallet" is sometimes used in the software and documentation, for example in PSADMIN custom configuration, to refer to wallets on all RDBMS. In this context it does not refer to an entity specific to an Oracle RDBMS.

You also have the option to use the wallets that are included with the PeopleSoft PeopleTools installation. The default wallet for the application server is named psft and is located in `$PS_SERVDIR/security`. When you configure the application server, define the default wallet as follows:

- SEC_PRINCIPAL_LOCATION=%PS_SERVDIR%\security
- SEC_PRINCIPAL_NAME=psft

To specify the default wallet for the workstation client:

- SEC_PRINCIPAL_LOCATION=PS_HOME\bin\client\winx86\security
- SEC_PRINCIPAL_NAME=wscpsft

The default Java Keystore file used for the SSL/TLS configuration for JSL ports is located in `<PIA_HOME>\webserv\<DOMAIN_NAME>\piaconfig\keystore\pskey`. If you change the Keystore password in this file, you must also provide the password in the PIA configuration.properties file at `<PIA_HOME>\webserv\<DOMAIN_NAME>\application\peoplesoft\PORTAL.war\WEB_INF\psftdoc\ps`.

Task 13B-1-2: Creating a Wallet with OpenSSL

This section discusses:

- Defining OpenSSL Options
- Creating a Server Wallet for the Application Server Domain with OpenSSL
- Creating a Client Wallet for the Workstation Client with OpenSSL
- Adding the Server's Certificate to the Client's Trust Store with OpenSSL

Defining OpenSSL Options

An example of an OpenSSL command that can be used to create a wallet is as follows.

For more information, see the OpenSSL documentation.

```
openssl pkcs12 -export -out ewallet.p12 -inkey server.key -in server.crt ->
chain -CAfile caCert.crt -passout pass:<password>
```

- **-export**: indicates that a PKCS 12 file is being created
- **-chain**: specifies that an attempt is made to include the entire certificate chain of the user certificate
- **-inkey**: specifies the private key file
- **-in**: specifies the file that contains the user certificate and any other certificates in the certificate chain
- **-CAfile**: specifies a file containing trusted certificates
- **-out**: specifies the output file name, which must be ewallet.p12 for an Oracle Wallet for PeopleSoft installations.
- **-passin**: specifies the password for the private key file
- **-passout**: specifies the password for the newly created wallet

Creating a Server Wallet for the Application Server Domain with OpenSSL

This section gives an example of creating a wallet for the application server with the open-source tool OpenSSL.

1. Create a directory, for example wallet.server.

For example on UNIX:

```
mkdir /home/wallet.server
```

2. Change directory to wallet.server.

```
cd wallet.server
```

3. Enter the following command:

```
openssl genrsa -out server.key 4096
```

4. Enter the following command.

```
openssl req -new -key server.key -out server.csr -subj <subject>
```

For example:

```
openssl req -new -key server.key -out server.csr -subj '/C=country/CN=>
commonName '
```

The *<subject>* values in this step and step 7 are used to replace the specified data in an input request, and output a modified request. The format for *<subject>* is

'/type0=value0/type1=value1/type2=...'. Characters must be escaped with a backslash (\),

and no spaces are skipped. Use the following fields:

- /C — Country
- /CN — Common name
- /L — Location
- /O — Organization
- /OU — Organizational Unit
- /ST — State

5. Enter the following command:

```
openssl genrsa -out caCert.key 4096
```

6. Enter the following command,

```
openssl req -new -x509 -days 1826 -key caCert.key -out caCert.crt -subj =>
<subject>
```

For example:

```
openssl req -new -x509 -days 1826 -key caCert.key -out caCert.crt -subj=>
'/C=US/OU=Class 2 Public Primary Certification Authority/O=My=>
Organization'
```

7. Enter the following command:

```
openssl x509 -req -days 730 -in server.csr -CA caCert.crt -CAkey ca=>
Cert.key -set_serial 01 -out server.crt
```

8. Enter the following command to create the wallet ewallet.p12 and specify the server password:

```
openssl pkcs12 -export -out ewallet.p12 -inkey server.key -in=>
server.crt -chain -CAfile caCert.crt -passout pass:<server_password>
```

Creating a Client Wallet for the Workstation Client with OpenSSL

This section gives an example of creating a client wallet with the open-source tool OpenSSL.

1. Create a directory, for example wallet.client, and change to that directory.

```
mkdir wallet.client
cd wallet.client
```

2. Copy the server's trust store to the client wallet.

```
cp wallet.server\caCert.crt wallet.client
cp wallet.server\caCert.key wallet.client
```

3. Enter these commands:

```
openssl genrsa -out client.key 4096
```

4. Run this command:

```
openssl req -new -key client.key -out client.csr -subj <subject>
```

For example:

```
openssl req -new -key client.key -out client.csr -subj '/C=country/CN=>
commonName'
```

5. Run this command:

```
openssl x509 -req -days 730 -in client.csr -CA caCert.crt -CAkey ca=>
Cert.key -set_serial 01 -out client.crt
```

6. Enter the following command to create the wallet ewallet.p12 and specify the client password:

```
openssl pkcs12 -export -out ewallet.p12 -inkey client.key -in=>
client.crt -chain -CAfile caCert.crt -passout pass:<client_password>
```

7. Remove the client wallet password:

a. Make a backup copy of the wallet, ewallet.p12:

On UNIX:

```
cp ewallet.p12 oldwallet.p12
```

b. Run this command:

```
openssl pkcs12 -clcerts -nokeys -in oldwallet.p12 -out=>
certificate.crt -password pass:<client_password> -passin pass:>
<client_password>
```

c. Run this command:

```
openssl pkcs12 -cacerts -nokeys -in oldwallet.p12 -out ca-cert.ca ->
password pass:C<client_password> -passin pass:<client_password>
```

d. Run this command:

```
openssl pkcs12 -nocerts -in oldwallet.p12 -out private.key -password=>
pass:<client_password> -passin pass:<client_password> -passout pass:>
temp
```

e. Run this command:

```
openssl rsa -in private.key -out NewKeyFile.key -passin pass:temp
```

f. Run the command to create the PEM.pem file.

This file is created to copy the public key and root certificates.

On UNIX:

```
cat certificate.crt ca-cert.ca >PEM.pem
```

g. Run this command:

```
openssl pkcs12 -export -nodes -in PEM.pem -inkey NewKeyFile.key -out=>
ewallet.p12 -passout pass:TrustedCertsOnlyNoPWNeeded
```

Adding the Server's Certificate to the Client's Trust Store with OpenSSL

To complete the setup, add the application server's certificate to the workstation client's trust store:

1. Change directory.

```
cd %ORACLE_HOME%\jdk\bin
```

2. Add the certificate to the trust store found in the web server directory for the application server domain.

```
keytool -import -file <server_wallet>/<certificate> -alias srvcert ->
keystore <PIA_HOME>\webserver\<DOMAIN_NAME>\piaconfig\keystore\pskey ->
storepass password -noprompt
```

For example, on UNIX:

```
keytool -import -file wallet.server/caCert.crt -alias srvcert -keystore=>
/home/psft_user/psft/pt/8.57/webserver/ps/piaconfig/keystore/pskey ->
storepass password -noprompt
```

Task 13B-2: Setting Environment Variables

Telnet to your UNIX system. Log in and ensure the following environment variables are set appropriately.

Note. The environment variables for Tuxedo must be set explicitly; they are not set by running psconfig.sh. These can be also set using the .profile file in the user's home directory.

- \$TUXDIR must be set to the correct Oracle Tuxedo installation directory. For example:
TUXDIR=/home/user/Oracle/tuxedo12cR1; export TUXDIR
- \$TUXDIR/lib must be prepended to LD_LIBRARY_PATH, LIBPATH, or SHLIB_PATH, whichever is appropriate for your platform. For example:
LD_LIBRARY_PATH=\$TUXDIR/lib:\$LD_LIBRARY_PATH; export LD_LIBRARY_PATH
- \$TUXDIR/bin must be prepended to PATH. For example:
PATH=\$TUXDIR/bin:\$PATH; export PATH

One method to ensure that the following PeopleSoft environment variables are set is to source psconfig.sh. Go to the PS_HOME directory, and enter the following command:

```
. ./psconfig.sh
```

Note. After running psconfig.sh, you can invoke the psadmin utility from any location.

Alternatively you can make sure the following environment variables are set in the .profile file in the user's home directory:

- \$COBDIR must be set to the Server Express installation directory. For example:
COBDIR=/cobol/prod/svrexpress-5.1_wp15-64bit; export COBDIR

Note. If your application does not contain COBOL programs, you do not need to set the \$COBDIR environment variables.

- \$COBDIR/bin must be appended to the PATH; for example:
PATH=\$PATH:\$COBDIR/bin; export PATH
- \$COBDIR/lib must be appended to LD_LIBRARY_PATH, LIBPATH, or SHLIB_PATH, whichever is appropriate for your platform. For example:

```
LD_LIBRARY_PATH=$LD_LIBRARY_PATH:$COBDIR/lib;export LD_LIBRARY_PATH
LIBPATH=$LIBPATH:$COBDIR/lib;export LIBPATH
SHLIB_PATH=$SHLIB_PATH:$COBDIR/lib;export SHLIB_PATH
```

To set the required DB2/LUW environment, run db2profile. Go to the *<DB2 INSTANCE DIRECTORY>/sqllib* directory, and enter the following command:

```
. ./db2profile
```

Ensure that the DB2 instance being used, is a 64-bit instance.

See "Creating a Database on UNIX," Fulfilling PeopleSoft Database Configuration Wizard Prerequisites.

Task 13B-3: Setting Up COBOL for Remote Call

Remote Call is a PeopleCode feature that launches a COBOL program from an application server, PeopleCode program or a batch Application Engine PeopleCode program and waits for it to complete execution before continuing. The execution of a COBOL program via Remote Call is completely independent of the Process Scheduler. You need to set up a COBOL runtime environment and COBOL executables on the application server to support Remote Call.

See "Installing and Compiling COBOL on UNIX."

Note. If your application does not contain COBOL programs, you do not need to purchase or compile COBOL.

Task 13B-4: Verifying Database Connectivity

Before continuing, it is critical to verify connectivity to the database that the application server domain will use. To verify connectivity, connect to the database server from the application server using the native SQL tool on the application server.

For DB2 for Linux, UNIX, and Windows, use the Command Center.

Task 13B-5: Creating, Configuring, and Starting an Initial Application Server Domain

This section discusses:

- Creating, Configuring, and Starting the Application Server Domain
- Testing the Three-Tier Connection
- Importing an Existing Application Server Domain Configuration
- Setting Up a Custom Application Server Domain Configuration
- Troubleshooting Common Errors

Task 13B-5-1: Creating, Configuring, and Starting the Application Server Domain

To create, configure, and start the application server domain:

1. Run the `psadmin` command.

You see the PeopleSoft Server Administration menu, as in this example:

```
-----
PeopleSoft Server Administration
-----
PS_CFG_HOME:  /home/JSMITH/peopletools/8.57
PS_HOME:      /opt/psft/pt/ps_home8.57
PS_APP_HOME:  /opt/psft/pt/hcm_app_home
```

```
1) Application Server
2) Process Scheduler
3) Search Server
4) Web (PIA) Server
5) Switch Config Home
6) Replicate Config Home
7) Refresh Config Home
q) Quit
```

Command to execute (1-7, q): **1**

2. Depending on your environment, you may see a message after the initial menu, which indicates that PSADMIN has modified the `PS_CFG_HOME/peopletools.properties` file with the current `PS_HOME` location:

```
*****
PS_CFG_HOME/peopletools.properties file has been updated.
You should use the Config Home Refresh feature in PSAdmin
to ensure that all of your domains are current.
Alternatively, you may recreate all of your domains.
Please press any key to continue...
*****
```

This indicates that one of these situations exists:

- The `PS_CFG_HOME` that you are working with was used previously from a different `PS_HOME`. In this case, you should recreate any existing Application Server, Process Scheduler, Search, or PIA domains in this `PS_CFG_HOME`.
- You configured your environment such that `PS_CFG_HOME` is the same as `PS_HOME`. The first time you use PSADMIN to create a domain, it updates the `PS_CFG_HOME/peopletools.properties` file. Continue with the next step.

3. Specify `1` for Application Server and press ENTER.

4. Specify `2` to Create a domain and press ENTER.

```
-----
PeopleSoft Application Server Administration
-----
1) Administer a domain
2) Create a domain
3) Delete a domain
4) Import domain configuration
q) Quit
```

Command to execute (1-4, q): **2**

5. Specify the domain name.

In this example the domain name is HRDMO:

Please enter name of domain to create : **HRDMO**

Domain names are case sensitive and must be eight characters or less. The domain name is used to create a directory name under the *PS_CFG_HOME/appserv* directory.

See the information on *PS_CFG_HOME* and server domain configuration in the *PeopleTools: System and Server Administration* product documentation.

6. Specify 4 for small if this is your initial domain installation, press ENTER.

See *PeopleTools: System and Server Administration*.

7. After the system creates the domain, the PeopleSoft Application Server Administration menu appears with a Quick-configure menu similar to this:

```
-----
Quick-configure menu -- domain: HRDMO
-----
```

Features =====	Settings =====
1) Pub/Sub Servers : No	17) DBNAME : [HRDMO]
2) Quick Server : No	18) DBTYPE : [DB2UNIX]
3) Query Servers : No	19) UserId : [VP1]
4) Jolt : Yes	20) UserPswd : []
5) Jolt Relay : No	21) DomainID : [TESTSERV]
6) WSL : No	22) AddToPATH : []
7) PC Debugger : No	23) ConnectID : [people]
8) Event Notification : Yes	24) ConnectPswd : []
9) MCF Servers : No	25) DomainConnectPswd: []
10) Perf Collator : No	26) WSL Port : [7000]
11) Analytic Servers : Yes	27) WSL SSL Port : [7010]
12) Domains Gateway : No	28) JSL Port : [9000]
13) Push Notifications : No	29) JSL SSL Port : [9010]
	30) JRAD Port : [9100]

Actions
=====

14) Load config as shown
 15) Custom configuration
 16) Edit environment settings
 h) Help for this menu
 q) Return to previous menu

HINT: Enter 17 to edit DBNAME, then 14 to load

Enter selection (1-28, h, or q):

Note. If your installation includes more than one application server domain on a given machine, read the troubleshooting section for more information.

See Troubleshooting Common Errors.

8. If you need to modify any of the values for these settings, enter the number next to the parameter name, press

ENTER, then type the new value, and press ENTER again.

If you need to change any of the features, type the number next to the feature name and press ENTER.

9. Configure the WSL to boot by changing option 6 to Yes.

Enter 6, and press ENTER.

10. If you intend to use the PeopleSoft Report Distribution system, you must select Yes for feature 8, Event Notification.

This enables the REN server, which is used by the "run to window" functionality of the Report Distribution system. *The Report Distribution system, MultiChannel Framework, and Optimization Framework use REN servers.* You must also remember to enter an Authentication Token Domain when installing the PeopleSoft Pure Internet Architecture (PIA).

11. If you are configuring an application server domain to support applications based on the PeopleSoft MultiChannel Framework (such as PeopleSoft CRM ERMS), select feature 9, MCF Servers.

See the information on configuring REN Servers in the product documentation.

See *PeopleTools: MultiChannel Framework*.

12. Enter the values for the 20) UserPswd and 24) ConnectPswd that you specified during the database configuration.

Reenter each password to verify the value. The password is hidden by masking characters as you type and in the Quick-configure menu.

13. If you want to set a Domain Connection password, enter 25 and specify a password of 8 characters or less.

Reenter the password to verify the value. The password is hidden by masking characters as you type and in the Quick-configure menu.

The Domain Connection password is optional. You can specify a value or leave it blank. However, if you do specify a value, you must supply the same value when installing the PeopleSoft Pure Internet Architecture, to ensure the connection to the Application Server.

14. To set up the Workstation Listener for SSL/TLS protocol, enter 27 for WSL SSL Port, and specify an available port number.

The default port number is 7010.

15. To set up the Jolt listener for SSL/TLS protocol, enter 29 for JSL SSL Port, and specify an available port number.

The default port number is 9010.

16. Use the custom configuration menu to specify the settings for SSL/TLS encryption and the wallet location.

See *PeopleTools: Integration Broker*, "Installing Web Server-Based Digital Certificates."

- a. To specify the minimum and maximum encryption for SSL/TLS, select 15 for Custom Configuration.

- b. Reply y, and press ENTER, at this prompt:

Do you want to change any config values (y/n) [n]?

- c. Reply n, and press ENTER, at this prompt:

Do you want to change any values (y/n) [n]?

Continue to enter n, for No, for all sections until you see the Workstation Listener section, and then answer y. (Be aware that there are several sections.)

- d. If necessary, change the values for WSL minimum and maximum encryption to correspond to your installed SSL/TLS cipher. The default minimum is 0 and the default maximum is 256. The maximum is the number of bits that indicates the highest level of encryption possible for the installed SSL/TLS version.

```

Values for config section - Workstation Listener
Address=%PS_MACH%
Port=7000
SSL Port=7010
WSL Min Encryption=0
WSL Max Encrytion=256
Min Handlers=1
Max Handlers=2
Max Clients per Handler=40
Client Cleanup Timeout=60
Init Timeout=5
Tuxedo Compression Threshold=5000

```

- e. Accept the defaults for the next series of questions until asked if you want Oracle Wallet configured. In this case, answer y.
- f. Specify the values for the Oracle Wallet location, name, and password, or accept the defaults.

You can use an existing wallet that you created, or use the default wallet found in the security directory.

```

Values for config section - Oracle Wallet
SEC_PRINCIPAL_LOCATION=%PS_SERVDIR%\security
SEC_PRINCIPAL_NAME=psft
SEC_PRINCIPAL_PASSWORD=

```

- g. Accept the defaults for the next series of questions until asked if you want the JOLT Listener configured. In this case, answer y
- h. If necessary, change the values for JSL minimum and maximum encryption to correspond to your installed SSL/TLS cipher. The default minimum is 0 and the default maximum is 256. The maximum is the number of bits that indicates the highest level of encryption possible for the installed SSL/TLS version.

```

Values for config section - JOLT Listener
Address=%PS_MACH%
Port=9000
SSL Port=9010
JSL Min Encryption=0
JSL Max Encrytion=256
Min Handlers=1
Max Handlers=2
Max Clients per Handler=40
Client Cleanup Timeout=10
Init Timeout=5
Client Connection Mode=ANY
Jolt Compression Threshold=1000000

```

- i. Accept the default for the remaining questions; the configuration will load automatically.
17. If you are installing a REN server:
- a. Enter 15 for Custom configuration.
 - b. Reply y, and press ENTER, at this prompt:
Do you want to change any config values (y/n) [n]?
 - c. Reply n, and press ENTER, at this prompt:
Do you want to change any values (y/n) [n]?

Continue to enter *n*, for No, for all sections until you see the PSRENSRV section, and then answer *y*. (Be aware that there are several sections.)

- d. Leave the defaults for all settings except for `default_auth_token`, which you should set to the domain name for your web server.

Note. The `default_auth_token` setting should be identical to the Authentication Token Domain that you set during PIA installation.

See "Setting Up the PeopleSoft Pure Internet Architecture in GUI Mode."

- e. Accept the defaults for the next series of questions until asked if you want Event Notification configured. In this case, answer *y*.
 - f. Accept the default for the remaining questions; the configuration will load automatically.
18. If you are not installing a REN server, after you update the settings you can load the configuration by entering *14*, for Load config as shown, from the Quick-configure menu.
 19. To start the application server (whether you installed a REN server or not), select *1*, Boot this domain, from the PeopleSoft Domain administration menu.
 20. Select *1*, Boot (Serial Boot) or *2*, Parallel Boot, from the PeopleSoft Domain Boot Menu.

Note. The messages you see and the number of processes started will depend on the options you chose during configuration.

21. If you plan to continue with PIA installation and testing, do not shut down the application server at this time.
22. If you want to shut down your PeopleSoft application server domain later, follow these simple steps:
 - a. From the PeopleSoft Domain Administration menu, enter *2* for Domain shutdown menu.
 - b. From the PeopleTools Domain Shutdown Menu, enter *1* for Normal shutdown.
You see messages about the application server processes being shut down. The number of processes stopped will vary depending on the number of processes that started when you booted the domain.
 - c. Enter *q* to quit the PeopleSoft Domain Administration Menu.

Task 13B-5-2: Testing the Three-Tier Connection

If you get an error message when you try to sign in to the Application Server in Application Designer (that is, three-tier mode), it may be due to an incorrect server name or port number, because the database server is not running, or because the application server was not booted. To test a three-tier connection from the PeopleTools Development Environment (the Windows-based client):

1. Start Configuration Manager with one of these methods:
 - On Microsoft Windows 7, select Start, Programs, PeopleTools 8.57, Configuration Manager.
 - On Microsoft Windows 8 or 2012 R2, access the Apps screen and navigate to PeopleTools 8.57, Configuration Manager.
 - Run `PS_HOME\bin\client\winx86\pscfg.exe`.
2. Select the Profile Tab. Highlight Default and select Edit.
3. On the Edit Profile dialog box, select *Application Server* as the Connection Type.
4. Enter values for these parameters:
 - Application Server Name
 - Machine Name or IP Address

- Port Number (WSL)

Enter the WSL port that you specified when creating the application server domain. If you want to use the SSL/TLS protocol for connection, enter the WSL SSL port number (the default is 7010). If you want to use the LLE protocol, enter the non-SSL WSL port (the default is 7000).

- Domain Connection Password and Domain Connection Password (confirm)

Specify a value for the password, and repeat your entry for confirmation. The password must be 8 characters or less.

This password is optional. If you did not set the Domain Connection Password in Configuration Manager or in the Application Server configuration, leave it blank. If you specify a password, you must supply the same password during the PeopleSoft Pure Internet Architecture installation for a successful connection between the Application Server and PeopleSoft Pure Internet Architecture.

See the *PeopleTools: System and Server Administration* product documentation for information on using PeopleSoft Configuration Manager and PSADMIN.

- Wallet Location

Enter the location that you specified for the client wallet. The default location is %PS_HOME%\bin\client\winx86\security.

- Wallet Name

Enter the name for the client wallet that you specified. The default name is wscpsft.

5. Select Set to add the definition to the list and select OK to close the dialog box.
6. On the Configuration Manager dialog box, select the Startup tab.
7. Select *Application Server* from the Database Type list. Your application server name should be displayed.
8. Enter the values for User ID, Connect ID, and password.
9. Click OK.

Note. Confirm that the application server is running by booting it from PSADMIN. Select *1, Boot this domain*, from the PeopleSoft Domain administration menu. Select option *1, Boot (Serial Boot)* or *2, Parallel Boot*, from the PeopleSoft Domain Boot menu.

10. Start Application Designer with one of these methods:

- On Microsoft Windows 7, select Start, Programs, PeopleTools 8.57, Application Designer.
- On Microsoft Windows 8 or 2012 R2, access the Apps screen and navigate to PeopleTools 8.57, Application Designer.
- Run `PS_HOME\bin\client\winx86\pside.exe`.

11. In the PeopleSoft Signon dialog box:

- Select *Application Server* as the Connection Type.
- Confirm that the Application Server Name is correct.
- Enter values for User ID and password.

12. Select OK to open Application Designer.

If you see the following error message when you try to sign in to the Application Server in Application Designer:

```
Network API: "Could not connect to application server 'Application Server⇒
Name' Make sure the PeopleTools authentication server (PSAUTH) is booted."
```

This may indicate a problem with the Domain Connection Password. For example, if the password set in the Application Server configuration file does not match the value in Configuration Manager, you may get this error message when you sign in to Application Designer in three-tier mode. Check the Application Server logs for more information.

Task 13B-5-3: Importing an Existing Application Server Domain Configuration

If you have an existing application server configuration for a previous PeopleSoft PeopleTools release, you can import it to create a new domain. You can import an existing domain configuration by specifying a file or by specifying the path to an existing domain. To import from a file, you must use the `psappsrv.cfg` file found inside an existing application server domain folder (you must specify the full path to `psappsrv.cfg`). This file can be located anywhere in the file system, but must be named `psappsrv.cfg`. To import from an existing domain configuration that you created in the current PeopleSoft PeopleTools release, you must specify `PS_CFG_HOME` and the name of an existing application server domain. (If you are importing a domain from a release before PeopleSoft PeopleTools 8.50, note that the domains were created in `PS_HOME`, and that is the path that you should provide.)

To import an existing application server domain configuration:

1. Run the `psadmin` command.

You see the PeopleSoft Server Administration menu, as in this example:

```
-----
PeopleSoft Server Administration
-----
PS_CFG_HOME:  /home/JSMITH/peopletools/8.57
PS_HOME:      /opt/psft/pt/ps_home8.57
PS_APP_HOME:  /opt/psft/pt/hcm_app_home
```

```
1) Application Server
2) Process Scheduler
3) Search Server
4) Web (PIA) Server
5) Switch Config Home
6) Replicate Config Home
7) Refresh Config Home
q) Quit
```

Command to execute (1-7, q): **1**

The `PS_CONFIG_HOME` location, also referred to as Config Home, corresponds to the current working directory. For information on how Config Home is set, see the *PeopleTools: System and Server Administration* product documentation.

2. Depending on your environment, you may see a message after the initial menu, which indicates that PSADMIN has modified the `PS_CFG_HOME/peopletools.properties` file with the current `PS_HOME` location:

```
*****
PS_CFG_HOME/peopletools.properties file has been updated.
You should use the Config Home Refresh feature in PSAdmin
to ensure that all of your domains are current.
```

Alternatively, you may recreate all of your domains.
Please press any key to continue...

This indicates that one of these situations exists:

- The *PS_CFG_HOME* that you are working with was used previously from a different *PS_HOME*. In this case, you should recreate any existing Application Server, Process Scheduler, Search, or PIA domains in this *PS_CFG_HOME*.
- You configured your environment such that *PS_CFG_HOME* is the same as *PS_HOME*. The first time you use PSADMIN to create a domain, it updates the *PS_CFG_HOME/peopletools.properties* file. Continue with the next step.

3. Specify *1* for Application Server.
4. Specify *4* for Import domain configuration.

```
-----
PeopleSoft Application Server Administration
-----
```

- ```
1) Administer a domain
2) Create a domain
3) Delete a domain
4) Import domain configuration
q) Quit
```

Command to execute (1-4, q): **4**

5. Specify *1* for Import regular domain.

```

PeopleSoft Import Application Server Configuration

```

- ```
1) Import regular domain
2) Import IB Master Configuration
q) Quit
```

Command to execute (1-2, q) : **1**

6. Specify whether to import the domain configuration from a file (option 1) or from an existing application domain configuration (option 2).

```
-----
PeopleSoft Import Application Server Configuration
-----
```

- ```
1) Import from file
2) Import from application domain
q) Quit
```

Command to execute (1-2, q) :

7. If you selected *1*, provide the full path to the file *psappsrv.cfg*, and then specify the name of the domain you want to create. If you selected *2*, go to the next step.

```
Enter full path to configuration file
:/home/oldconfig/psappsrv.cfg
```

```
Enter domain name to create
:HRDMO
```

8. If you selected 2, to Import from application domain, provide the full path to the *PS\_CFG\_HOME* of the existing domain.

If importing from PeopleTools 8.49 or earlier, provide *PS\_HOME* for *PS\_CFG\_HOME*.

```
Enter PS_CFG_HOME of domain you wish to import: /home/JSMITH⇒
/peopletools/8.57
```

If applicable, choose among the existing application server domains in the specified *PS\_CFG\_HOME*:

Tuxedo domain list:

- 1) HRDBA
- 2) HRDBB

```
Select domain number to import: 1
```

```
Enter a name for new domain: HRDMO
```

After you create the domain, continue to the next task to verify that the imported configuration parameters are appropriate for the newly created domain. You may need to change the following values:

- **DBName**  
DBName can be the same or different, depending on which database the application server needs to point to.
- **DBType**  
DBType depends on the database type of DBName.
- **UserId and UserPswd**  
UserId and UserPswd are the user's choice.
- **Workstation Listener Port**  
Workstation Listener Port will need to be modified if the old domain will be up and running in the same machine.
- **Jolt Listener Port**  
Jolt Listener Port will also need a different number if the old domain will be up and running in the same machine.
- **Jolt Relay Adapter Listener Port**  
Jolt Relay Adapter Listener Port will need a different number if the old domain will be up and running in the same machine, and will be using Jolt Relay Adapter.

## Task 13B-5-4: Setting Up a Custom Application Server Domain Configuration

The Quick-configure menu is initially displayed when you choose to configure your domain. This menu is intended for the commonly adjusted parameters—those most likely to change from domain to domain. However, there are additional configuration parameters that are not available through the Quick-configure menu. For such configuration parameters, you must use the Custom Configuration option, which you can access from the Quick-configure menu. Feel free to skip this procedure if you have already created and configured your Application Server using the Quick-configure menu and want to move forward.

The following steps assume you will be using PSADMIN to specify parameter settings.

To reconfigure an application server domain:

1. Run the `psadmin` command.
2. Depending on your environment, you may see a message after the initial menu, which indicates that PSADMIN has modified the `PS_CFG_HOME/peopletools.properties` file with the current `PS_HOME` location:

```

PS_CFG_HOME/peopletools.properties file has been updated.
You should use the Config Home Refresh feature in PSAdmin
to ensure that all of your domains are current.
Alternatively, you may recreate all of your domains.
Please press any key to continue...

```

This indicates that one of these situations exists:

- The `PS_CFG_HOME` that you are working with was used previously from a different `PS_HOME`. In this case, you should recreate any existing Application Server, Process Scheduler, Search, or PIA domains in this `PS_CFG_HOME`.
  - You configured your environment such that `PS_CFG_HOME` is the same as `PS_HOME`. The first time you use PSADMIN to create a domain, it updates the `PS_CFG_HOME/peopletools.properties` file. Continue with the next step.
3. Specify `1` for Application Server and press ENTER.
  4. Specify `1` for Administer a domain and press ENTER.
  5. Select the domain to administer and press ENTER.
  6. Specify `4` for Configure this domain and press ENTER.

The option Configure this domain performs the following tasks:

- Shuts down the application server, if it is running. (Shutdown is required since the binary file `PSTUXCFG` must be deleted and re-created to enable new configuration values. If there are no processes running when shutdown is attempted, an error will be displayed but the script continues on. This is normal.)
  - Initiates an interactive dialog, prompting for configuration parameters.
  - Updates `psappsrv.cfg`, generates `psappsrv.ubb`, and internally invokes Tuxedo's `tmloadcf` executable to create binary file `PSTUXCFG` used during the domain boot process.
7. Specify `15` for Custom Configuration and press ENTER.
  8. Respond to this prompt:

Do you want to change any config values (y/n):

- Specify `y` to start an interactive dialog to change or examine parameter values, as described in the next step.  
Oracle recommends this option for more experienced users.
  - Specify `n` if you have already edited `psappsrv.cfg`, skip the next step, and continue with the step to select server process options.
9. Complete the interactive dialog to specify configuration parameters.

Configuration parameters are grouped into sections. For each section, you are asked whether you want to change any parameters in that section, as in the following example:

Values for config section - Startup



```

DBName=
DBType=
UserId=
UserPswd=
ConnectId=
ConnectPswd=
ServerName=
StandbyDBName=
StandbyDBType=
StandbyUserId=
StandbyUserPswd=
InMemoryDBName=
InMemoryDBType=

```

Do you want to change any values (y/n)? [n]: y

- Specify *y* to change any parameter values for the current configuration section displayed.  
You are prompted for each parameter value. Either specify a new value, or press ENTER to accept the default if applicable. After pressing ENTER, you are positioned at the next parameter in that section. When you are done with that section, you are again asked whether you want to re-edit any of the values you changed.
- Enter the user ID and user password that has security to start the application server. All application databases are delivered with one or more application server security users, usually PS or VP1.  
The password you enter is hidden by masking characters.
- The parameters StandbyDBName, StandbyDBType, StandbyUserId, and StandbyUserPswd, are used for a standby database in an Oracle environment.  
See *PeopleTools: Data Management*, "Implementing Oracle Active Data Guard."
- The parameters InMemoryDBName and InMemoryDBType are reserved for internal use.
- The WSL, JSL, and JRAD port numbers, which are found in other sections of the configuration parameters, have default values of 7000, 9000, and 9100, respectively. These values must be unique for each application server domain. You may alter the port values if necessary to ensure that they are unique.
- If you do not wish to change any values, specify *n* and you will be prompted for the next configuration section.

---

**Note.** When setting up your application server, make a note of the values you use for Database Name, Application Server Name (the machine name), and JSL Port. You will need to use these same values when installing the PeopleSoft Pure Internet Architecture.

---

See *PeopleTools: System and Server Administration*.

#### 10. Select server process options.

At this point, you will be prompted to select server process options. If this is your initial installation, we suggest you accept the defaults. A message similar to this appears:

```

Setting Log Directory to the default... [PS_SERVDIR/LOGS]
Configuration file successfully created.
Loading new configuration...

```

The message "Loading new configuration" indicates that PSADMIN is generating a binary file named PSTUXCFG, which is used to boot the application server. At this point, your application server should be properly configured.

## Task 13B-5-5: Troubleshooting Common Errors

For troubleshooting help, you can access a log file through the PSADMIN PeopleSoft Domain Administration menu. The following list includes possible errors and troubleshooting tips.

- Use the PSADMIN PeopleSoft Domain Administration menu option 6 for Edit configuration/log files menu to check for errors in `<PS_CFG_HOME>/appserv/<domain>/LOGS/APPSRV_mmdd.LOG` and `<PS_CFG_HOME>/appserv/<domain>/LOGS/TUXLOG.mmddyy`.
- If a PeopleSoft server such as PSAPPSRV fails, examine your configuration parameters. The failure of the PSAPPSRV process is often signalled by the message "Assume failed"—which means the process has failed to start. Check the SIGNON section for misspelled or invalid database name, an invalid or unauthorized OprId, or ConnectId or ServerName is missing or invalid. Finally, make sure the database connectivity is set correctly.
- If a WSL (or JSL) fails to start, try specifying another port number (it may be in use already by another application server domain process).
- If you are unable to start the BBL, check that your Tuxedo is installed fully and that the directory really exists.
- If the installation includes more than one application server domain on a single machine, before booting the second domain, adjust the REN server configuration to avoid conflict in one of these ways:
  - Use PSADMIN to disable Event Notification (option 8 on the Quick-configure menu) for the second and subsequent app server domains.
  - Change `default_http_port` to a value other than 7180.
- Check that you do not have older Tuxedo releases prepended in your PATH or runtime library (LIBPATH, SHLIB\_PATH or LD\_LIBRARY\_PATH, depending on the UNIX operating system).

### See Also

*PeopleTools: System and Server Administration*

*PeopleTools: MultiChannel Framework*

## Chapter 14

# Setting Up the PeopleSoft Pure Internet Architecture in Silent Mode

This chapter discusses:

- Understanding PeopleSoft Pure Internet Architecture
- Using Authentication Domains in the PeopleSoft Pure Internet Architecture Installation
- Installing the PeopleSoft Pure Internet Architecture in Silent Mode
- Configuring the SSL/TLS Port for JSL
- Testing and Administering the PeopleSoft Pure Internet Architecture Installation
- Completing Post-Installation Steps

## **Understanding PeopleSoft Pure Internet Architecture**

---

This chapter explains how to install and configure the components of the PeopleSoft Pure Internet Architecture in silent mode.

See "Installing Web Server Products."

The setup program for the PeopleSoft Pure Internet Architecture is installed to the web server machine when you run the PeopleSoft Installer and select the PeopleSoft Web Server option.

See "Using the PeopleSoft Installer."

Oracle only supports customer installations that use web servers that are certified for PeopleSoft PeopleTools. *You must install the web server before you install the PeopleSoft Pure Internet Architecture.* Before you install the PeopleSoft Pure Internet Architecture, you must also have configured an application server, as described in the previous chapter.

The location where you install the PeopleSoft Pure Internet Architecture is referred to in this documentation as *PIA\_HOME*. You can specify different locations for *PS\_HOME* and *PIA\_HOME*. After you complete the PeopleSoft Pure Internet Architecture installation, you can locate the installation files in the directory *PIA\_HOME/webserv*.

For PeopleSoft PeopleTools 8.51 and later, if you are setting up the PeopleSoft Pure Internet Architecture on a Microsoft Windows platform, the directory and path that you specify for *PIA\_HOME* may include spaces. However, parentheses in the directory name (for example, "C:\Program Files (x86)") are *not* allowed for *PIA\_HOME*.

See "Preparing for Installation," Defining Installation Locations.

If your web server is on a different machine than your application server, you need to make sure you have JRE installed on your web server to run the PeopleSoft Pure Internet Architecture installation.

The initial PeopleSoft Pure Internet Architecture setup automatically creates the default PeopleSoft site named *ps*. In subsequent PeopleSoft Pure Internet Architecture setups, change the site name from *ps* to a unique value. We recommend using the database name. This is handy for easy identification and ensures that the database web server files are installed in a unique web site.

The URL that you use to invoke the PeopleSoft Pure Internet Architecture must conform to ASN.1 specifications. That is, it may contain only alphanumeric characters, dots ("."), or dashes ("-"). The URL must not begin or end with a dot or dash, or contain consecutive dots (".."). If the URL includes more than one portion, separated by dots, do not use a number to begin a segment if the other segments contain letters. For example, "mycompany.second.country.com" is correct, but "mycompany.2nd.country.com" is wrong.

Review the following additional notes before beginning the PeopleSoft Pure Internet Architecture installation:

- If you want to connect between multiple application databases, you need to implement single signon.
- If the PeopleSoft Pure Internet Architecture installation encounters an error, it will indicate which log files to refer to.

See "Installing Web Server Products."

- The machine on which you run the PeopleSoft Pure Internet Architecture install must be running in 256 *color mode*. This is not necessary for UNIX or console mode.

The PeopleSoft Pure Internet Architecture installation includes the following products:

- *PeopleSoft Pure Internet Architecture*. This product is the centerpiece of the PeopleSoft architecture that enables users to work on a machine with only a supported browser installed. This option installs the servlets required for deploying PeopleSoft Applications and for the PeopleSoft portal. The portal packs and PeopleSoft Portal Solutions have their own installation instructions, which are available on My Oracle Support. For an overview of the various types of portals, consult the *PeopleTools: Portal Technology* product documentation.
- *PeopleSoft Report Repository*. This product works in conjunction with Process Scheduler to allow report distribution over the web.
- *PeopleSoft Integration Gateway*. This product is the entry and exit point for all messages to and from the Integration Broker. Its Java-based Connector architecture allows asynchronous and synchronous messages to be sent over a variety of standard protocols, many that are delivered at install, or through custom connectors.

---

**Important!** For PeopleSoft PeopleTools 8.50 and later, review the product documentation concerning security properties for Integration Gateway. When setting the properties in the `integrationGateways.properties` file, the property `secureFileKeystorePasswd` must be encrypted, and the `secureFileKeystorePath` must be set.

---

See *PeopleTools: Integration Broker Administration*.

- *PeopleSoft CTI Console*. This product works in conjunction with CTI vendor software to enable call center agents to take advantage of browser-based teleset management and automatic population of application pages with relevant data associated with incoming calls, such as customer or case details.

See *PeopleTools: MultiChannel Framework*.

- *Environment Management Hub*. The Environment Management hub is a web application that is installed with the PeopleSoft Pure Internet Architecture and portal. It is started along with the rest of the web applications when the user boots the web server. You cannot start the Environment Management Hub on a server that is configured to run HTTPS; in other words, if you plan to run Environment Management, your PIA server needs to be configured in HTTP mode.

See *PeopleTools: Change Assistant and Update Manager*.

## See Also

*PeopleTools: Security Administration*

*PeopleTools: System and Server Administration*

## Using Authentication Domains in the PeopleSoft Pure Internet Architecture Installation

---

You have the option to specify an authentication domain when you install the PeopleSoft Pure Internet Architecture on Oracle WebLogic.

**Note.** The authentication domain was referred to as the Authentication Token Domain in previous releases, and that term is still seen in the software.

---

When an authentication domain is specified during the PeopleSoft Pure Internet Architecture installation, that value gets used as the Cookie domain in the web server configuration. The main requirements when setting a cookie domain are:

- The cookie domain value being set must begin with a dot (.ps.com is valid, ps.com is NOT valid).
- The cookie domain value being set must contain at least 1 embedded dot (.ps.com is valid, .corp.ps.com is valid, .com is NOT valid).
- The cookie domain value can only be a single domain name. It cannot be a delimiter-separated list of domains.

By default, the browser only sends cookies back to the machine that set the cookie. So if web server `crm.yourdomain.com` sets a cookie, the browser will only send it back there. You can make the browser send the single signon cookie to all servers at `yourdomain.com` by typing your domain name in the Authentication Token Domain list box of web server `crm`.

Specifying the authentication domain may be necessary in certain cases. For example, if you plan to use the PeopleSoft portal technology, be sure to read the supporting documentation on configuring the portal environment, to determine whether setting the authentication domain is required for correct operation.

See *PeopleTools: Portal Technology*.

Specify an authentication domain if you plan to run a REN Server. REN Servers are required for PeopleSoft MultiChannel Framework, Reporting, and some PeopleSoft CRM applications supported by PeopleSoft MultiChannel Framework.

See *PeopleTools: MultiChannel Framework*.

If you use the PeopleSoft Mobile Application Platform (MAP), you must specify the same authentication domain during the PeopleSoft Pure Internet Architecture installation, for MAP, and for Integration Broker and integration hubs.

See *PeopleTools: Mobile Application Platform*.

See *PeopleTools: Integration Broker*.

## Task 14-1: Installing the PeopleSoft Pure Internet Architecture in Silent Mode

---

This section discusses:

- Understanding the Silent Installation and the Response File
- Editing the Response File

- Running the Silent Mode Installation

## Understanding the Silent Installation and the Response File

You can carry out a silent installation of the PeopleSoft Pure Internet Architecture by providing all the required settings in a response file. With silent installation there is no user interaction. Silent mode installation of PeopleSoft Pure Internet Architecture is supported for both Microsoft Windows and UNIX operating systems platforms.

### Task 14-1-1: Editing the Response File

You need a response file to start the installer in silent mode. The PeopleSoft Pure Internet Architecture installer comes with a response file template (`resp_file.txt`) that can be found under `PS_HOME\setup\PsmPiaInstall\scripts`. Modify the values in the response file according to your installation requirements. To exclude sections that are not needed, begin the line with a pound sign (`#`).

---

**Note.** When specifying paths on Microsoft Windows operating systems, use forward slashes (`/`), as shown in the examples in the response file.

---

The response file should contain all the input parameters that are needed for deploying PeopleSoft Pure Internet Architecture. Modify the following sections in the response file for your environment:

- The location where you want to install the PeopleSoft Pure Internet Architecture, `PIA_HOME`.  
`PS_CFG_HOME=C:/PT8.57`
  - The default is the same as the same as the `PS_CFG_HOME`.
  - You can specify any directory on your machine, including `PS_HOME`.
  - To specify the path on both Microsoft Windows and UNIX operating systems, use a forward slash (`/`), not a back slash (`\`).
- PIA Domain name, for example *peoplesoft*.  
`# Name of the PIA domain`  
`DOMAIN_NAME=peoplesoft`
- Enter *weblogic* for the Web server type.  
`SERVER_TYPE=weblogic`
- Enter the Oracle WebLogic installation location for the `BEA_HOME` parameter.  
`BEA_HOME=c:/bea`
- Specify the administrator login ID, and the password for the web server domain.  
`# admin console user id/password for securing`  
`WebLogic/WebSphere admin console credential`  
`USER_ID=system`  
`USER_PWD=`  
`USER_PWD_RETYPE=`
- Select one of the installation actions listed for the `INSTALL_ACTION` parameter.  
`# Install action to specify the core task that installer should perform.`  
`# For creating new PIA domain - CREATE_NEW_DOMAIN.`  
`# For redeploying PIA - REDEPLOY_PSAPP.`

```
For recreating PIA domain - REBUILD_DOMAIN.
For installing additional PSFT site - ADD_SITE
For installing Extensions - ADD_PSAPP_EXT
INSTALL_ACTION=CREATE_NEW_DOMAIN
```

- **CREATE\_NEW\_DOMAIN**

Create a new PeopleSoft Pure Internet Architecture domain.

- **REDEPLOY\_PSAPP**

On an Oracle WebLogic web server, this option affects all of the PeopleSoft Pure Internet Architecture web applications installed to the local Oracle WebLogic domain. Select this option to redeploy all of the web components of the PeopleSoft Pure Internet Architecture. The redeployment process updates all of the web components of the PeopleSoft Pure Internet Architecture, without modifying the configuration files or scripts that belong to the Oracle WebLogic server domain.

- **REBUILD\_DOMAIN**

This option affects Oracle WebLogic Server domain configuration and all of the PeopleSoft Pure Internet Architecture web applications installed to the local Oracle WebLogic domain. Select this option to completely remove an existing Oracle WebLogic domain and deploy the PeopleSoft Pure Internet Architecture components to create the newly specified PeopleSoft site.

---

**Warning!** Re-creating an existing domain will delete everything previously installed into that domain.

---

- **ADD\_SITE**

This option is relevant only to the PeopleSoft PORTAL web application, and does not modify or revert any other configuration settings. Select this option to install only the necessary files for defining an additional PeopleSoft site onto an existing Oracle WebLogic configuration. The new site will be accessed using its name in the URL. A site named "CRM" would be accessed using a URL similar to `http://mywebserver_machine/CRM`. To reset or re-create an existing PeopleSoft site, simply enter that site's name as the site to create. On your web server, a PeopleSoft site is comprised of the following directories within the PORTAL web application:

```
<WEBLOGIC_DOMAIN>\applications\peoplesoft\PORTAL\<site>*
```

```
<WEBLOGIC_DOMAIN>\applications\peoplesoft\PORTAL\WEB-INF\psftdocs\<site>*
```

- **ADD\_PSAPP\_EXT**

This option is solely for use with PeopleSoft applications. PeopleSoft application extensions are provided with certain PeopleSoft applications, and this option allows you to deploy those extensions. Consult the installation documentation for your PeopleSoft application to see if this option is appropriate. PeopleSoft PeopleTools does not use application extensions.

- For the **DOMAIN\_TYPE** parameter, enter **NEW\_DOMAIN** to create a new domain or **EXISTING\_DOMAIN** to modify an existing domain.

```
DOMAIN_TYPE=NEW_DOMAIN
```

- Specify the installation location for the PeopleSoft application software, **PS\_APP\_HOME**.

Specify the **PS\_APP\_HOME** location only when you are installing extensions for a PeopleSoft application. If you are not installing PeopleSoft application extensions, do not remove the comment character. The silent installer can detect any deployable application extensions present in the **PS\_APP\_HOME**.

```
PS_APP_HOME=D:/CR9.2
```

- Enter one of the following parameters for **INSTALL\_TYPE** to specify whether the installation is a single server, multi-server, or distributed server installation.

```
INSTALL_TYPE=SINGLE_SERVER_INSTALLATION
```

- **SINGLE\_SERVER\_INSTALLATION**

The single server domain configuration contains one server named PIA, and the entire PeopleSoft application is deployed to it. This configuration is intended for single user or very small scale, non-production environments.

- **MULTI\_SERVER\_INSTALLATION**

The multi-server domain configuration contains seven unique server definitions, an Oracle WebLogic cluster, and the PeopleSoft application split across multiple servers. This configuration is intended for a production environment.

- **DISTRIBUTED\_SERVER\_INSTALLATION**

The distributed server option is an extension of the Multi-Server Domain selection and installs the necessary files to boot a managed server.

This option requires a Multi Server installation to be performed to some other location, which will contain the configuration for this managed server.

- The PeopleSoft web site name.

---

**Warning!** Warning! The site name can include underscores ( \_ ), but an underscore cannot be followed by a numeric character or the string "newwin" (for example, my\_site\_3 or my\_newwin\_site).

---

```
WEBSITE_NAME=ps
```

- Use the optional PSSERVER parameter to enable Jolt failover and load balancing.

For information on the optional PSSERVER parameter, see the information on configuring Jolt failover and load balancing in the *PeopleTools: System and Server Administration* production documentation.

```
To enable jolt failover and load balancing, provide a list
of application server domains in the format of; PSSERVER=AppSrvr:⇒
JSLport,...
```

```
For example: PSSERVER=SERVER1:9000,SERVER2:9010,SERVER3:9020
```

```
PSSERVER is optional, but if set will have precedence
over APPSERVER_NAME & JSL_PORT.
```

```
PSSERVER=
```

- Specify the application server name, its JSL (Jolt Station Listener) port number, its HTTP and HTTPS port numbers, the Authentication Token Domain (optional).

```
AppServer Name
```

```
APPSERVER_NAME=
```

```
Appserver JSL Port
```

```
JSL_PORT=
```

```
HTTP Port
```

```
HTTP_PORT=80
```

```
HTTPS Port
```

```
HTTPS_PORT=443
```

```
Authentication Domain (optional)
```

```
AUTH_DOMAIN=
```



- APPSERVER\_NAME — the name of your application server
- JSL\_PORT — the JSL port number you specified when setting up your application server.
- HTTP\_PORT — the port to access the software in a browser using HTTP.
- HTTPS\_PORT — the port to access the software in a browser using HTTPS.
- AUTH\_DOMAIN

This is optional. The value you enter for Authentication Token Domain must match the value you specify when configuring your application server, as described earlier in this book. In addition, certain installation configurations require that you specify an authentication domain.

If you enter a value for Authentication Token Domain, the URL to invoke PeopleSoft Pure Internet Architecture must include the network domain name in the URL. For example, if you do not enter an authentication domain, the URL to invoke PeopleSoft Pure Internet Architecture is `http://MachineName/ps/signon.html`. If you do enter a value for the authentication domain (for example, `.myCompany.com`), the URL to invoke PeopleSoft Pure Internet Architecture is `http://MachineName.myCompany.com/ps/signon.html`. In addition, if the web server for the database is using an http port other than the default port of 80, the URL must include the port number, for example `http://MachineName:8080/ps/signon.html` if there is no authentication domain, or `http://MachineName.myCompany.com:8080/ps/signon.html` if there is an authentication domain. The URL must also comply with the naming rules given earlier in this chapter.

See *Using Authentication Domains in the PeopleSoft Pure Internet Architecture Installation*.

- Web profile name and password

Enter a Web Profile Name, and enter the password two times. The example below shows the default web profile name, PROD, and default user ID, PTWEBSEVER. The web profile name will be used to configure this web site. You can specify one of the other predelivered web profiles, DEV, TEST, or KIOSK, or enter a different name. If you intend to use a Web Profile User ID other than the default, PTWEBSEVER, be sure to review the information on web profile configuration and security in the *PeopleTools: Portal Technology* product documentation.

```
Web Profile Name Possible Values are "DEV", "TEST", "PROD", "KIOSK"
WEB_PROF_NAME=PROD
```

```
Web Profile password for User "PTWEBSEVER"
WEB_PROF_PWD=
WEB_PROF_PWD_RETYPE=
```

- Enter the Integration Gateway user name and password.

See *PeopleTools: Integration Broker Administration*.

```
Integration Gateway user profile.
IGW_USERID=administrator
IGW_PWD=
IGW_PWD_RETYPE=
```

- AppServer Domain Connection password (optional).

If you configured your Application Server domain to require a Domain Connection password, enter it here. Otherwise, leave it blank as shown in this example. This password will be propagated to the Integration Gateway. For more information about Application Server domain configuration and setting domain parameters, see the product documentation *PeopleTools: System and Server Administration*.

```
AppServer connection user profile
APPSRVR_CONN_PWD=
```

```
APPSRVR_CONN_PWD_RETYPE=
```

- The root directory for the Report Repository

Make sure that the report repository directory is shared. You must have write access to the Report Repository directory.

---

**Note.** In setting up the Process Scheduler to transfer reports, if you choose the FTP transfer protocol, use the same directory for the Home Directory as you use here for the report repository.

---

See *PeopleTools: Portal Technology*.

See "Setting Up Process Scheduler on Windows," Setting Up Process Scheduler to Transfer Reports and Logs to the Report Repository.

```
Directory path for reports
REPORTS_DIR=
```

## Task 14-1-2: Running the Silent Mode Installation

Use the response file that you modified for your configuration. Substitute the location where you saved the response file for *<path\_to\_response\_file>* in the following procedures.

To install the PeopleSoft Pure Internet Architecture in silent mode on Microsoft Windows:

1. In a command prompt, go to *PS\_HOME\setup\PsmPPIAInstall*.
2. Run the following command, using forward slashes (/) to specify the path:  

```
setup.bat -i silent -DRES_FILE_PATH=<path_to_response_file>
```

For example:

```
setup.bat -i silent -DRES_FILE_PATH=D:/PT8.57/resp_file.txt
```

To install the PeopleSoft Pure Internet Architecture in silent mode on UNIX:

1. Go to *PS\_HOME/setup/PsmPPIAInstall*.
2. Run the following command, using forward slashes (/) to specify the path:  

```
setup.sh -i silent -DRES_FILE_PATH=<path_to_response_file>
```

For example:

```
setup.sh -i silent -DRES_FILE_PATH=/home/PT857/resp_file.txt
```

## Task 14-2: Configuring the SSL/TLS Port for JSL

Supply the SSL/TLS port for JSL in the configuration.properties file for the web server.

See *PeopleTools: Integration Broker*, "Installing Web Server-Based Digital Certificates."

1. Using a text editor, open the configuration.properties file in the web server deployment folder located here:  
*<PIA\_HOME>\webserv\<DOMAIN\_NAME>\application\peoplesoft\PORTAL.war\WEB\_INF\psftdoc\ps.*
2. Locate the psserver section and enter the application server name and the SSL/TLS port.

Enter the SSL/TLS port that you specified for the JSL SSL Port when setting up the application server domain.

See Creating, Configuring, and Starting an Initial Application Server Domain.

```
psserver=<machine_name>:<SSL_port_for_JSL>
```

3. Locate the section Keystore password for ssl connection.

If you reset the SSL/TLS Java Keystore password, enter it here. Otherwise, accept the default value. The default Java Keystore file is located in `<PIA_HOME>\websrv\<DOMAIN_NAME>\piaconfig\keystore\pskey`.

```
#Keystore password for ssl connection
KeyStorePwd=={V1.1}7m4OtVwXFNyLc1j6pZG69Q==
```

4. Save and close the file.

If the JDK used for your web server does not support the algorithm used for SSL connection, you may see an error similar to the following when you sign in to the PeopleSoft Pure Internet Architecture through an SSL port: "Cannot support TLS\_RSA\_WITH\_AES\_256\_CBC\_SHA with currently installed providers"

This applies to the Oracle JDK for Linux, Microsoft Windows, or Oracle Solaris for SPARC operating systems.

See "Installing Web Server Products," Installing JDK.

To resolve the issue, use the following steps to upgrade the JDK with Java Cryptography Extension (JCE) Unlimited Strength Jurisdiction Policy Files:

1. Download the file `jce_policy-8.zip` from this site to a convenient directory:  
<http://www.oracle.com/technetwork/java/javase/downloads/jce8-download-2133166.html>
2. Unzip the file `jce_policy-8.zip`.
3. Copy the files `local_policy.jar` and `US_export_policy.jar` from `jce_policy-8\UnlimitedJCEPolicyJDK8`.
4. Paste the two files into the `<JAVA_HOME>\jre\lib\security` folder, and replace the existing files.

## Task 14-3: Testing and Administering the PeopleSoft Pure Internet Architecture Installation

---

This section discusses:

- Verifying the PeopleSoft Pure Internet Architecture Installation
- Starting and Stopping Oracle WebLogic
- Using PSADMIN to Start and Stop Web Servers
- Accessing the PeopleSoft Signon

### Verifying the PeopleSoft Pure Internet Architecture Installation

After installing the PeopleSoft Pure Internet Architecture, you should make sure that your configuration is functional. You can test this by signing on to PeopleSoft, navigating within the menu structure, and accessing pages. (Make sure the application server is configured and booted.) This section includes procedures to start and stop the Oracle WebLogic web server whenever necessary.

## Task 14-3-1: Starting and Stopping Oracle WebLogic

When using the Oracle WebLogic web server, you need to sign on to Oracle WebLogic before using these commands. Use the following commands in the Oracle WebLogic domain directory.

---

**Note.** Starting from Oracle WebLogic 9.2 and later releases, all the Life-cycle management scripts and other batch scripts for the PIA server on Oracle WebLogic are located in `<PIA_HOME>\webserver\<domain_name>\bin` folder.

---

- To start Oracle WebLogic Server as a foreground process on a single server, use the following commands:  
 On Microsoft Windows:  

```
startPIA.cmd
```

  
 On UNIX:  

```
startPIA.sh
```
- To start Oracle WebLogic Server as a foreground process on multiple-servers or distributed servers, use the following commands:
  1. Execute the following command:  
 On Microsoft Windows:  

```
startWebLogicAdmin.cmd
```

  
 On UNIX:  

```
startWebLogicAdmin.sh
```
  2. Then execute:  
 On Microsoft Windows:  

```
startManagedWebLogic.cmd ManagedServerName
```

  
 On UNIX:  

```
startManagedWebLogic.sh ManagedServerName
```
- To stop the server, use the following commands:
  - Single Server on Microsoft Windows:  

```
stopPIA.cmd
```

  
 Single Server on UNIX:  

```
stopPIA.sh
```
  - Multiple Servers or Distributed Servers on Microsoft Windows:  

```
stopWebLogic.cmd ManagedServerName
```

  
 Single Server on UNIX:  

```
stopWebLogic.sh ManagedServerName
```

For more information on working with Oracle WebLogic multiple servers or distributed servers, see the *PeopleTools: System and Server Administration* product documentation.

---

**Note.** For more information on working with Oracle WebLogic multiple or distributed servers, search My Oracle Support.

---

## Task 14-3-2: Using PSADMIN to Start and Stop Web Servers

In addition to the methods given in the previous sections for starting and stopping Oracle WebLogic web servers, in PeopleSoft PeopleTools 8.52 and later releases you can use PSADMIN to administer a web server domain.

See *PeopleTools: System and Server Administration*.

To start and stop web servers:

1. Specify 4 for Web (PIA) Server.

The location of Config Home is the current working directory. The PSADMIN utility determines the Config Home directory by checking for the PS\_CFG\_HOME environment variable. If that is not set, it checks for the presence of domains in the default PS\_CFG\_HOME location. If none exists, it uses the PS\_HOME location from which it was launched.

See "Preparing for Installation," Defining Installation Locations.

2. Select 1 for Administer a domain.

The PSADMIN utility determines the PIA Home location displayed here by first checking for a PIA\_HOME environment variable. If none is set, it checks for the PS\_CFG\_HOME environment variable. If neither is set, it uses the default PS\_CFG\_HOME directory.

3. Select the domain you want to administer by entering the appropriate number.

```

PeopleSoft PIA Domain Administration - Choose a Domain

1) psftTST
2) peoplesoft

q) Quit

Command to execute: 2
```

4. To start a web server domain, enter 1, Boot this domain.

```
Starting the domain.....
...
Verifying domain status..
The domain has started.
```

5. To stop a web server domain, select 2, Shutdown this domain.

```
Stopping the domain.....
.....
Verifying domain status.....
The domain has stopped.
```

6. Select 1 to install a service, or 2 to remove it.

This command invokes the installNTservice script, and creates a service named *WebLogicDomain-WebLogicServer*.

```

Windows Service Setup
```

```

PIA Home: C:\psft_websrv
PIA Domain: peoplesoft
Domain status: started

1) Install Service
2) Uninstall Service

q) Quit

Command to execute:
```

### Task 14-3-3: Accessing the PeopleSoft Signon

To access the PeopleSoft signon:

1. Open your web browser.

2. Enter the name of the site you want to access—for example (the default value for `<site_name>` is ps):

`http://<machine_name>:<http_port>/<site_name>/signon.html`

This will take you to the sign-in window corresponding to your browser's language preference, as shown in this example:



Oracle PeopleSoft Enterprise Sign in window

---

**Note.** If you do not see the signon screen, check that you supplied all the correct variables and that your application server and the database server are running.

---

3. Sign in to the PeopleSoft system by entering a valid user ID and password.

The user ID and password are case sensitive.

---

**Note.** The user ID and password were set during the database configuration and also used to boot the application server.

---

The PeopleSoft PeopleTools and PeopleSoft applications include various default user IDs. For information on using the user IDs delivered with your PeopleSoft application demo database, see the application-specific

installation instructions. For information on using and securing PeopleSoft PeopleTools default user IDs, see the information on administering user profiles in the *PeopleTools: Security Administration* product documentation.

## **Task 14-4: Completing Post-Installation Steps**

---

This section discusses:

- Using Fluid User Interface
- Updating the Installation Table
- Setting Options for Multilingual Databases
- Updating PeopleTools Options
- Updating Time Zone Information
- Updating Database Information

### **Task 14-4-1: Using Fluid User Interface**

When you sign in to your PeopleSoft application, you may see the PeopleSoft Fluid User Interface by default. To access the menu items, as seen in the classic user interface, from the PeopleSoft Fluid User Interface:




1. On the PeopleSoft Fluid User Interface, shown in this example, select (press) the NavBar button at the top right (diamond inside a circle).



PeopleSoft Fluid User Interface home page

The Navigation bar (NavBar) side page appears.


2. Select (press) Navigator.



NavBar side page

The menu structure appears.

3. Navigate to the desired item, such as Set Up HCM or PeopleTools.



Navigator side page with PeopleSoft menu items

## See Also

*PeopleTools: Applications User's Guide, "Working With Fluid Homepages"*

*PeopleTools: Fluid User Interface Developer's Guide*

## Task 14-4-2: Updating the Installation Table

After you complete the installation process, creating the database, installing the Application Server, and installing the PeopleSoft Pure Internet Architecture, you must complete this additional step. This postinstallation step ensures that only the products you are entitled to use are active in the installation. The location of the installation table in the PeopleSoft system varies depending upon the PeopleSoft application that you installed.

---

**Note.** For information on the products you are entitled to use, contact your Oracle Support representative.

---

1. Sign on to the PeopleSoft system in a browser.
2. Select Set Up *Application\_name* (where *Application\_name* is the PeopleSoft application you installed), Install, Installation Table.
3. Select the Products tab.

4. Clear the check boxes for the products that you are not entitled to use.

## Task 14-4-3: Setting Options for Multilingual Databases

### Setting the Data Field Length Checking Option

The value to specify data field length checking must be set correctly in order for PeopleSoft applications to perform correctly in a browser. Use one of these methods to set the data field length checking option:

- Select PeopleTools, Utilities, Administration, PeopleTools Options, and select the Data Field Length Checking option from the drop-down list.
- Alternatively, use the SQL tool for your database platform to modify the DBLENGTHTYPE parameter in the PSOPTIONS table.

See *PeopleTools: Global Technology*, "Setting Data Field Length Checking."

See *PeopleTools: Global Technology*, "Selecting Character Sets."

Use the guidelines in this table to select the correct option for your environment:

| Environment                                                                                                                                     | PeopleTools Option Page Selection                                       | PSOPTIONS.DBLENGTHTYPE Value |
|-------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------|------------------------------|
| Unicode-encoded database or a non-Unicode SBCS database                                                                                         | Others                                                                  | N                            |
| Japanese database on DB2 LUW                                                                                                                    | DB2 MBCS                                                                | D                            |
| Non-Unicode Japanese database<br><br><b>Note.</b> If your installation uses the Shift-JIS character set for Japanese, you must use this option. | MBCS<br><br><b>Note.</b> The MBCS option is not supported for DB2 z/OS. | M                            |

### Setting the Unicode Enabled Option

If you are running a Unicode database, verify that the UNICODE\_ENABLED parameter in the PSSTATUS table is set correctly. For example:

- For non-Unicode databases, including those using the Shift-JIS character set for Japanese, set UNICODE\_ENABLED=0.
- For Unicode databases, set UNICODE\_ENABLED=1.

See the information on converting to Unicode in the *PeopleTools: Global Technology* product documentation.

## Task 14-4-4: Updating PeopleTools Options

You can set the following options on the PeopleTools Options page:

- Multi-Currency — Select this check box if you plan to use currency conversion.  
See *PeopleTools: Global Technology*, "Using System-Wide Multicurrency Settings."
- Base Time Zone — Enter a value for the base time zone for your PeopleTools database.

See *PeopleTools: Global Technology*, "Setting the Base Time Zone."

- Sort Order Option — If you specified a non-binary sort order for your database, choose the Sort Order Option that most closely approximates your database sort order.

See *PeopleTools: Global Technology*, "Setting the Sort Order."

### **Task 14-4-5: Updating Time Zone Information**

Additional steps may be required to configure your time zone after you complete the installation.

See *PeopleTools: Global Technology*, "Maintaining Time Zones."

### **Task 14-4-6: Updating Database Information**

The database information updated in this procedure is used by the PeopleSoft software update tools to identify your PeopleSoft database when searching for updates. These steps should be followed for all additional databases that you create to enable the accurate identification of your databases.

1. Sign on to your PeopleSoft database.
2. Navigate to PeopleTools, Utilities, Administration, PeopleTools Options.
3. Specify long and short names for your environment. For example:
  - Environment Long Name — Customer HR Demo Database
  - Environment Short Name — HR Demo DB
4. Select a system type from the drop-down list. For example, Demo Database.
5. Save your changes.



## Chapter 15A

# Setting Up Process Scheduler on Windows

This chapter discusses:

- Prerequisites
- Setting Up Process Scheduler Security
- Setting Up Process Scheduler to Transfer Reports and Logs to the Report Repository
- Setting Environment Variables
- Setting Up Process Scheduler Server Agent
- Starting Process Scheduler as a Windows Service (Optional)
- Configuring the Process Scheduler for Microsoft Word (Optional)
- Configuring Setup Manager
- Installing Products for PS/nVision

## Prerequisites

---

Before setting up your Process Scheduler, you must:

- Install Tuxedo.  
See "Installing Additional Components."
- Install database connectivity to be able to communicate with your database server (Process Scheduler requires a direct connection to the database).  
See "Preparing for Installation."
- Set up the web server with the PeopleSoft Pure Internet Architecture, as described in the previous chapter. This is required to set up the Process Scheduler to transfer reports or log files to the Report Repository.
- Set up your COBOL batch environment if you need to run COBOL processes through Process Scheduler. If the PeopleSoft modules purchased do not contain any COBOL modules, the COBOL run time libraries are not required. Also, COBOL is not required for applications that contain no COBOL programs. Consult My Oracle Support for the details on whether your application requires COBOL.  
See "Preparing for Installation," Planning Your Initial Configuration.
- Install the Microsoft Office products Microsoft Word and Microsoft Excel.
- Have both your application server and the PeopleSoft Pure Internet Architecture started. In this chapter, you must modify security options of the designated PeopleSoft user ID that will be used to boot up Process Scheduler. This requires that the user ID's profile be modified through the User Security component. Please refer to earlier chapters for the details on starting the application server and the PeopleSoft Pure Internet Architecture.
- Refer to the following location for required DB2CLI.INI and registry settings.

See "Creating a Database," Fulfilling PeopleSoft Database Configuration Wizard Prerequisites.

In PeopleSoft PeopleTools 8.50 and later, the configuration and log files for Process Scheduler server domains reside in *PS\_CFG\_HOME*. If you do not set a *PS\_CFG\_HOME* environment variable before beginning the application server configuration, the system installs it in a default location based on the current user's settings, as follows:

`%USERPROFILE%\psft\pt\<peopletools_version>`

See "Preparing for Installation," Defining Installation Locations.

See the product documentation *PeopleTools: System and Server Administration* for more information on the *PS\_CFG\_HOME* environment variable and working with server domain configuration.

## See Also

*PeopleTools: Process Scheduler*

My Oracle Support, Certifications

## Task 15A-1: Setting Up Process Scheduler Security

---

This section discusses:

- Understanding Process Scheduler Security
- Changing User Account to Start ORACLE ProcMGR V12.2.2.0.0\_VS2015
- Granting Process Scheduler Administrative Rights

### Understanding Process Scheduler Security

This task—in which you set up the PeopleSoft User ID that will be used to boot Process Scheduler server so it has administrative rights to both Process Scheduler and Report Manager—guarantees that security is set up properly both in Microsoft Windows and within your PeopleSoft database.

You must carry out this task to start Process Scheduler successfully.

In the next section you set up ORACLE ProcMGR V12.2.2.0.0\_VS2015 with a network user ID. When you install Oracle Tuxedo, the ORACLE ProcMGR V12.2.2.0.0\_VS2015 service is set up by default to be started by local system account—a user account that does not have access to the Windows network. If the Process Scheduler server or processes initiated through Process Scheduler will be using a network printer, accessing files from a network drive, or using Microsoft Windows utilities such as XCOPY that may access UNC paths, you need to change the user account used to start ORACLE ProcMGR V12.2.2.0.0\_VS2015 with a network user account.


### Task 15A-1-1: Changing User Account to Start ORACLE ProcMGR V12.2.2.0.0\_VS2015

To change User Account to start ORACLE ProcMGR V12.2.2.0.0\_VS2015:



1. Launch the Services dialog box; for example, on Microsoft Windows 2012 R2, select Administrative Tools, Services.

In the Services dialog box, find the service labeled *ORACLE ProcMGR V12.2.2.0.0\_VS2015*. This service is installed automatically when you install Tuxedo, and is highlighted in this example.




Microsoft Windows Services dialog box with ORACLE ProcMGR service highlighted

2. If the Stop button is enabled, click it to stop the current ORACLE ProcMGR V12.2.2.0.0\_VS2015 process.
  - a. Click Yes when a message informs you of the status change.
  - b. Double-click ORACLE ProcMGR V12.2.2.0.0\_VS2015.

The Properties dialog box appears.

3. Select the option This account on the Log On tab.

Enter an account name and password. In this example, the account name is CORP\USER1.



ORACLE ProcMGR V12.2.2.0.0\_VS2015 Properties dialog box: Log On tab


---

**Note.** When you configure your Oracle Tuxedo server as outlined in the chapter, "Configuring the Application Server on Windows," the user ID designated to be the Application Server Administrator must have read/write permissions to the PeopleSoft file directory and read permission to the %TUXDIR% directory, such as C:\oracle\tuxedo12.2.2.0.0\_VS2015.

---

4. Select the General tab.

Make sure that Startup Type is set to Automatic, as shown in this example, and click OK.



ORACLE ProcMGR V12.2.2.0.0\_VS2015 Properties dialog box: General tab

5. Click Start.

A message in the Properties dialog box will indicate the "Started" status. You also see the status in the Services dialog box. Click OK to close the dialog box.

## Task 15A-1-2: Granting Process Scheduler Administrative Rights

To grant Process Scheduler administrative rights:

1. Log onto your PeopleSoft database through the PeopleSoft Pure Internet Architecture.
2. Select PeopleTools, Security, User Profiles.
3. Select the User Profiles component. Use the Search dialog to select the PeopleSoft User ID you plan to use to boot the Process Scheduler server.

- Click the Roles tab, click the plus icon to insert a new row, and there enter the *ProcessSchedulerAdmin* role to grant the user ID with administrative rights in the Process Scheduler components.

ORACLE®

Home | Worklist | MultiChannel Console | Add to Favorites | Sign

Favorites | Main Menu > PeopleTools > Security > User Profiles > User Profiles

New Window | Personalize Page | http

General | ID | Roles | Workflow | Audit | Links | User ID Queries

User ID: QEDMO  
Description: QE User

**Dynamic Role Rule**

Execute on Server:

Test Rule(s) Refresh

Execute Rule(s)

[Process Monitor](#)  
[Service Monitor](#)

**User Roles** Personalize | Find | View All | First 2-11 of 18 Last

| Role Name                | Description                 | Dynamic                  | Route Control                 | View Definition                 |   |   |
|--------------------------|-----------------------------|--------------------------|-------------------------------|---------------------------------|---|---|
| PTF Administrator        | PTF Administrator           | <input type="checkbox"/> | <a href="#">Route Control</a> | <a href="#">View Definition</a> | + | - |
| PeopleSoft Administrator | PeopleSoft Admin Privileges | <input type="checkbox"/> | <a href="#">Route Control</a> | <a href="#">View Definition</a> | + | - |
| PeopleSoft User          | PeopleSoft User             | <input type="checkbox"/> | <a href="#">Route Control</a> | <a href="#">View Definition</a> | + | - |
| Portal Administrator     | Portal Administrator        | <input type="checkbox"/> | <a href="#">Route Control</a> | <a href="#">View Definition</a> | + | - |
| Portal Manager           | Portal Manager              | <input type="checkbox"/> | <a href="#">Route Control</a> | <a href="#">View Definition</a> | + | - |
| ProcessSchedulerAdmin    | Process Scheduler Admin     | <input type="checkbox"/> | <a href="#">Route Control</a> | <a href="#">View Definition</a> | + | - |
| QE Role                  | QE Role                     | <input type="checkbox"/> | <a href="#">Route Control</a> | <a href="#">View Definition</a> | + | - |
| Search Administrator     | Search Administrator        | <input type="checkbox"/> | <a href="#">Route Control</a> | <a href="#">View Definition</a> | + | - |
| Search Developer         | Search Developer            | <input type="checkbox"/> | <a href="#">Route Control</a> | <a href="#">View Definition</a> | + | - |
| ReportDistAdmin          | Report Distribution Admin   | <input type="checkbox"/> | <a href="#">Route Control</a> | <a href="#">View Definition</a> | + | - |

Save Return to Search Previous in List Next in List Add Update/Display

General | ID | Roles | Workflow | Audit | Links | User ID Queries

Process Scheduler window: Roles tab

- Repeat the instructions in step 4 to add the role *ReportDistAdmin*.  
This will grant the user ID administrative rights to the Report Manager component. Carry out this step only if the same user is also responsible for maintaining the content of Report Manager.
- Click Save to save your changes.
- Select the General tab and jot down the Permission List name assigned to the Process Profile field.
- From the Portal menu, choose PeopleTools, Security, Permissions & Roles, Permission Lists.
- In the Search dialog, enter the Permission List you noted in step 7.
- Select the Can Start Application Server check box.
- Click Save to save your changes.

## Task 15A-2: Setting Up Process Scheduler to Transfer Reports and Logs to the Report Repository

This section discusses:

- Understanding Report Distribution

- Setting Up Single Signon to Navigate from PIA to Report Repository
- Determining the Transfer Protocol
- Starting the Distribution Agent
- Setting Up the Report Repository
- Setting Up the Distribution for Your Process Scheduler Server
- Setting Up Sending and Receiving of Report Folders in the Report Manager

## Understanding Report Distribution

The PeopleSoft PeopleTools Report Distribution lets you access reports and log files generated from process requests run by a Process Scheduler Server Agent. Using the PeopleSoft Pure Internet Architecture, you can view reports and log files from the web browser through the Report Manager or Process Monitor Detail page. Report Distribution enables you to restrict access to these reports to authorized users based either on user ID or role ID.

This product also includes the Distribution Agent component, which runs on the same server as the Process Scheduler Server Agent. The Distribution Agent, a process that runs concurrently with the Process Scheduler Server Agent, transfers to the Report Repository files generated by process requests initiated by the Process Scheduler Server Agent.

The Distribution Agent transfers files to the Report Repository when one of these criteria is true:

- The Process Scheduler Server Agent is set up in the *Server Definition* to transfer all log files to the Report Repository.
- The process request output destination type is *Web/Window*.

In either case, the Process Scheduler Server Agent inserts a row in the Report List table (PS\_CDM\_LIST). The server agent then updates the distribution status for a process request to *Posting* upon completion of the program associated with the process request. The distribution status of *Posting* signals that the files for the process request are ready for transfer to the Report Repository. The Distribution Agent is notified by Process Scheduler for any process requests that are ready for transferring. As part of the process to transfer files to the Report Repository, the Distribution Agent performs the following steps:

- *Transfer files to the Report Repository.* All the report and log files are transferred to the Report Repository. For each process request transferred, a directory is created in the Report Repository using the following format: \<database name>\<date yyyymmdd>\<report id>. All the files for a process request are stored in this directory.
- *Delete the directory from the Process Scheduler Agent's Log/Output directory.* When the output destination type specified for a process request is *Web/Window*, all the files and directory associated with the process request are deleted from the Process Scheduler Log/Output directory after the files are transferred to the Report Repository.

The following diagram illustrates the Process Scheduler and Report Repository architecture. The diagram includes the following items:


- The web browser gives access to the Process Request dialog and the Report or Log Viewer.
- The Report Repository is part of the PeopleSoft Pure Internet Architecture.

---

**Note.** The PeopleSoft Pure Internet Architecture must be installed for Process Scheduler to be able to transfer reports to the Report Repository.

---

- The Process Scheduler Server includes the Process Scheduler Server Agent and the Distribution Agent.
- The transfer protocol between Process Scheduler and the Report Repository may be FTP/FTPS, XCOPY, HTTP/HTTPS, or SFTP.



Process Scheduler and Report Repository Architecture

Before users can view a report, they are authenticated against the PeopleSoft database.

You should set up single signon if you do not want users to have to log on an additional time to view reports in the Report Repository. For the details on setting up single signon, consult the security documentation.

See *PeopleTools: Security Administration*.

## Task 15A-2-1: Setting Up Single Signon to Navigate from PIA to Report Repository

To view reports (log files or system files) from Report Repository, you need to pass the authentication. Report Repository should be treated as a separate PeopleSoft application. To navigate from PeopleSoft Pure Internet Architecture (PIA) to Report Repository, you need to set up single signon to avoid getting a prompt for a second signon. This section includes some considerations for setting up single signon to navigate from PIA to Report Repository.

If Report Repository resides on the same web server as PIA, make sure your Local Message Node is set up to be a "trusted" node for single signon for your system.

If Report Repository resides on a different web server than PIA, do the following:

- Make sure your Local Message Node is set up to be a "trusted" node for single signon for your system.
- Use a fully qualified domain name when addressing the web server for both PIA and Report Repository. For example, enter `http://<machineName>.peoplesoft.com/<site_name>/signon.html` instead of `http://<machineName>/<site_name>/signon.html`.
- Specify the Authentication Domain for your application during installation. If you have multiple applications, and you want them to employ single signon, it is important to specify the same Authentication Domain for all applications.

See the information on implementing single signon in the *PeopleTools: Security Administration* product documentation.

- Set up single signon with a password, like this:
  - Choose PeopleTools, Integration Broker, Integration Setup, Nodes.
  - Click Search and then select the node marked as Default Local Node.
  - Select *Password* for the Authentication Option.
  - Enter a password of your choice.
  - Enter the password again in the Confirm Password field.
  - Enter the user ID for which you are setting up single signon in the Default User ID field.
  - Save the Node Definition.
  - Sign out from the PeopleSoft application.
  - Reboot your application server.

### See Also

*PeopleTools: Security Administration*

## Task 15A-2-2: Determining the Transfer Protocol

*We recommend using HTTP as your transfer protocol.*

Before transferring the files to the Report Repository, you need to determine which transfer protocol to use. If you have a Microsoft Windows Process Scheduler and a Microsoft Windows web server, you can use either an XCOPY, FTP/FTPS, SFTP, or HTTP/HTTPS protocol. (If FTP information is not specified, Process Scheduler will perform an XCOPY.) If you have a PeopleSoft Process Scheduler on Microsoft Windows and a UNIX web server, you can use FTP/FTPS, SFTP, or HTTP/HTTPS. If you have a PeopleSoft Process Scheduler on UNIX, you can use FTP/FTPS, SFTP, or HTTP/HTTPS.

---

**Note.** If you are using FTP/FTPS or SFTP, the corresponding service must be set up in your web server.

---

---

**Note.** JRE is installed automatically on your Process Scheduler server.

---

## Task 15A-2-3: Starting the Distribution Agent

The Distribution Agent is automatically started as another Oracle Tuxedo server when a Process Scheduler Server is booted. If a Process Scheduler Server was set up without specifying a Distribution Node in the *Server Definition* page, the Process Scheduler server will have a status in Process Monitor of "Running with No Report Node." After a node is defined for the Process Scheduler server, in the next cycle the Process Scheduler server checks the state of the system, and the Distribution Agent dynamically sets up its environment.

## Task 15A-2-4: Setting Up the Report Repository

This section discusses:

- Defining ReportRepositoryPath
- Defining the Report Node to Use HTTP/HTTPS
- Defining the Report Node to Use XCOPY
- Defining the Report Node to Use FTP
- Defining the Report Node to Use FTPS
- Defining the Report Node to Use SFTP

### Defining ReportRepositoryPath

The ReportRepositoryPath specifies the location of a directory for the Report Repository. You can specify the location for the Report Repository Path on the General page of the Web Profile during installation. If you do not set the location in the Web Profile, the location given by ReportRepositoryPath in the configuration.properties file is used for the default location. Note that the value entered for Report Repository Path in the Web Profile overrides any entry in the configuration.properties file.

See *PeopleTools: Portal Technology*, "Configuring Web Profiles."

Use the following formats to enter the name for the directory that you want to use for the ReportRepositoryPath. The examples below give the default values. Note that you must use a forward slash (/) in both cases:

- *Microsoft Windows*: ReportRepositoryPath=c:/psreports
- *UNIX*: ReportRepositoryPath=<user\_home>/PeopleSoft Internet Architecture/psreports

For <user\_home> substitute the home directory for the current user.

### Defining the Report Node to Use HTTP/HTTPS

To define the report node to use HTTP/HTTPS:

1. Select PeopleTools, Process Scheduler, Report Nodes.
2. Select the Add a New Value link and enter the Report node name.



- On the Report Node Definition page, select HTTP or HTTPS from the Protocol drop-down list.

Select the HTTP option if you are *not* using SSL. Select the HTTPS option if you are using SSL. The pages for HTTP and HTTPS have the same fields. These examples show HTTP.

Note that if you are using SSL you need to have Client Certificates installed on your web server.

The screenshot shows the 'Report Node Definition' page in the Oracle PeopleTools interface. The breadcrumb trail at the top indicates the path: Favorites > Main Menu > PeopleTools > Process Scheduler > Report Nodes. The page title is 'Report Node Definition'. The 'Node Name' is set to 'HTTP'. The '\*Protocol' dropdown is also set to 'HTTP', with a 'Validate' button to its right. Below this is the 'Distribution Node Details' section, which includes a 'URLID' field with a placeholder 'http://<machine\_name>:<port\_number>/psreports/<site\_name>', a 'Description' field, and an 'Operating System' dropdown set to 'Windows'. The 'Login Details' section has 'Login ID', 'Password', and 'Confirm Password' fields. The 'URL Details' section includes 'URI Host' (placeholder '<machine\_name>'), 'URI Port' (value '80'), and 'URI Resource' (placeholder 'SchedulerTransfer/<site\_name>'). At the bottom are buttons for 'Save', 'Return to Search', 'Notify', and 'Refresh'.

Report Node Definition page for the HTTP protocol

- Enter the following information in the Distribution Node Details area:

- URLID:** Enter the URL of the web server using the following format:

`http://<machine_name>:<port_number>/psreports/<site_name>`

Replace `<machine_name>` with the name of your machine. Use the fully qualified host name for your web server. If you are using an HTTP or HTTPS port other than the defaults, you need to specify the port number.

**Note.** If you specify the Authentication Token Domain name during the PIA installation, you must include a fully qualified domain name for the URL instead of the IP address.

- Description:** Enter a description of the server (optional).
- Operating System:** Select the web server operating system, Windows or UNIX.

- Enter the following information in the Login Details area:

- *Login ID*: Enter the Login ID. This is not required, unless basic authentication has been set up on the web server by the Web Administrator.
- *Password and Confirm Password*: Enter the password, and confirm it, for the user ID specified in the Login ID field. This is not required, unless basic authentication has been set up on the web server by the Web Administrator.

---

**Note.** The setup of authentication is optional, but is recommended for security of the Report Repository when using the HTTP to transfer files. For information on setting up authentication on the web server where the Report Repository resides, refer to the *PeopleTools: Security Administration* product documentation.

---

6. Enter the following information in the URI Details area:

- *URI Host*: Enter the machine name for the report repository.

---

**Note.** In a basic setup, the machine name for the report repository will match the machine name of the web server URL. However, under certain circumstances—for example, if you are using a reverse proxy server—the URL and URI Host may have different machine names.

---

- *URI Port*: Enter the port number, which must match the port number of your web server (defaults are HTTP = 80, HTTPS = 443). If you change a port number you will lose the default values for both protocols.
- *URI Resource*: Enter SchedulerTransfer/<site name>.

7. Click Save to save your entries.

8. Click Validate to confirm that your entries are complete and correct.

The validation confirms that the necessary parameters are present and correct, and simulates a file transfer with the entered information. You either see a message that confirms the success of the validation, or a message that displays an error for missing parameters or an unsuccessful transfer simulation.

9. To add additional report nodes, click Add to return to the Search page.

## Defining the Report Node to Use XCOPY

Both the Process Scheduler machine and the Report Repository machine must be Microsoft Windows machines for XCOPY to be used.

To define the report node to use XCOPY:

1. Select PeopleTools, Process Scheduler, Report Nodes.
2. Select Add a New Value, enter the Report node name, and click Add.

- On the Report Node Definition page, select XCOPY from the Protocol drop-down list.

The screenshot shows the Oracle Report Node Definition page. The breadcrumb navigation at the top indicates the path: Favorites > Main Menu > PeopleTools > Process Scheduler > Report Nodes. The Oracle logo is on the left, and a search bar is in the center. On the right, there are links for 'New Window', 'Help', 'Personalize Page', and a 'Home' icon. The main heading is 'Report Node Definition'. Below this, the 'Node Name' is set to 'XCOPY'. The '\*Protocol' is a dropdown menu currently showing 'XCOPY', with a 'Validate' button to its right. A section titled 'Distribution Node Details' contains several fields: 'URLID' with a placeholder 'http://<machine\_name>:<port\_number>/psreports/<site\_name>', 'Description' (empty), 'Operating System' (dropdown showing 'Windows'), and 'Network Path' (placeholder '\\<machine\_name>\psreports'). At the bottom of this section are three buttons: 'Save', 'Notify', and 'Refresh'.

Report Node Definition page for the XCOPY protocol

- Enter the following information in the Distribution Node Details area:

- URLID:** Enter the URL of the web server using this format:

`http://<machine_name>:<port_number>/psreports/<site_name>`

Replace *<machine name>* with the name of your web server. Replace *<site name>* with the directory where you installed the PIA files.

If you installed the web server software with the default TCP port of 80, you do not need to specify the port number in the URL path. However, if you installed the web server to some other port, you must specify the port number in the URL path.

- Description:** Enter an optional description for the node.
- Network Path:** Enter the path that points to your Report Repository share, using this format (where *<machine\_name>* refers to the web server machine):

`\\<machine_name>\psreports`

Make sure that this directory is shared with the login accounts used to start Process Scheduler. Use UNC format instead of mapped drive format.

- Select Save to save your entries.
- Click Validate to confirm that your entries are correct.

The validation confirms that the necessary parameters are present and correct, and simulates a file transfer with the entered information. You either see a message that confirms the success of the validation, or a message that displays an error for missing parameters or an unsuccessful transfer simulation.

- To add additional report nodes, select Add to return to the Search page.

## Defining the Report Node to Use FTP

If you use the FTP report node protocol, note that:

- If your FTP server is a Microsoft Windows server, you may have to set up the FTP service.
- The Distribution Agent will perform a validation after FTP has transferred files into the Report Repository by sending a query request to the web server. For this task to be completed, it is critical that the value entered in the URL is accurate. Verify that the machine name, port number, and site number that you specify are correct.

If this setup is not completed, the process request will get a status of NOT POSTED in the Process Monitor Detail page and will log the message "Unable to verify files posted."

To define the report node to use FTP:

1. Select PeopleTools, Process Scheduler, Report Nodes.
2. Select Add a New Value, enter the Report node name, and click Add.

3. On the Report Node Definition page, select FTP from the Protocol drop-down list.

**Report Node Definition**

Node Name: FTP

\*Protocol:  Validate

**Distribution Node Details**

URLID:

Description:

Operating System:  Network Path:

**Login Details**

Login ID:

Password:  Confirm Password:

**File Transfer Details**

Home Directory:

FTP Address:  SSL Mode:

**Connection Properties**

| Property Name        | Property Value       |
|----------------------|----------------------|
| <input type="text"/> | <input type="text"/> |

**▼ Password Encryption**

Password:  Confirm Password:

Encrypt Encrypted Password:

Save Return to Search Notify Refresh

Report Node Definition page for the FTP protocol

4. In the Distribution Node Details area, enter the following information:

- **URLID:** Enter the URL of the web server using this format:

`http://<machine_name>:<port_number>/psreports/<site_name>`

Replace *<machine name>* with the name of your web server. If you are using an HTTP port other than 80, you need to specify the port number. The variable *<site name>* refers to the directory where you installed the PIA files; this will default to ps for the first installation.

---

**Note.** If you specify the Authentication Token Domain name during the PIA installation, you must include a fully qualified domain name for the URL instead of the IP address.

---

---

**Note.** If you installed the web server software with the default TCP port of 80, you do not need to specify the port number in the URL path. However, if you installed the web server to some other port, you must specify the port number in the URL path.

---

- *Description:* Enter a description of the server (optional).
  - *Operating System:* Select the operating system of the Report Repository, Windows or UNIX.
  - *Network Path:* This information is not required for the FTP protocol
5. In the Login Details area, enter the following information:
- *Login ID:* Enter the FTP User ID.
  - *Password and Confirm Password:* Enter the password, and enter it a second time, for the FTP User ID specified in the Login ID field.
6. In the File Transfer Details area, enter the following information:
- *Home Directory:* Enter the directory specified during the PIA installation as the Report Repository. The FTP User ID must have write access to this directory. Note that this is not a required field for FTP transfer, as the system uses the Report Repository directory specified at install time or the current directory assigned to ReportRepositoryPath in configuration.properties. Note that the value you enter for the Report Repository Path in the Web Profile at install time overrides any entry for ReportRepositoryPath in configuration.properties.
- For Microsoft Windows operating systems, the directory needs to match the Report Repository path. Make sure that you do not include any drive information—as in c:\psreports\—because you are using the FTP protocol to interpret this parameter.
- *FTP Address:* Enter the machine name or the IP address of the Report Repository. If the name of the machine is used, it must be included on a DNS server.

7. If you need to specify additional properties, use the Connection Properties area. Specifying the Connection Properties is optional.

Click the lookup button (magnifying glass) and select one of the properties in the following table. Click the plus sign to add another connection property.

| Property Name       | Property Value                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
|---------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ACTIVEMODE          | To enable active mode, add the ACTIVEMODE property to the URL and set it to Y.<br><br>The default FTP connection mode is extended passive mode.                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| ACTIVEPORTOPTION    | This property can be used along with ACTIVEMODE. When active mode is enabled, you can use ACTIVEPORTOPTION to specify the IP address and port on which the FTP server can be accessed. This is useful when the server is behind a firewall. By default, ACTIVEPORTOPTION uses the default IP address of your system. If you want to use a particular IP address, set the ACTIVEPORTOPTION value to either the full IP address, a host name to resolve to an IP address, or a local network interface name.<br><br>You can also specify a port range. For example:<br><i>10.176.147.111:10000-13000</i> |
| ENABLEEPRPRT        | This option can be used only with Active Mode. If Active Mode is enabled and ENABLEEPRPRT is set to N, then the system will use a PORT (IPv4) Active Mode connection.<br><br>By default, ENABLEEPRPRT is Y, if Active Mode is set to Y.                                                                                                                                                                                                                                                                                                                                                                |
| EXTENDEDPASSIVEMODE | <ul style="list-style-type: none"> <li>0: Disable EPSV</li> <li>1: Enable EPSV</li> </ul> <p>This property enables you to control whether extended passive mode (EPSV) will be used by FTP.</p> <p>EPSV is used by default. That is, by default, this value is considered to be 1.</p> <p>If the client fails to connect to the server with EPSV, then the system will try passive mode (PASV). To use PASV only, add EXTENDEDPASSIVEMODE to the URL Properties and set it to 0.</p>                                                                                                                   |
| JKSPASSWORD         | Specify the Java keystore (JKS) password.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| JKSPATH             | Specify the Java keystore (JKS) path.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| PASSWORD            | Specify the password associated with the USER property, which identifies the FTP User ID.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| USER                | Specify the FTP User ID used for authentication when accessing the FTP site.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |

8. If you need to specify an encrypted password in any of the property fields, use the Password Encryption area to generate the encrypted password, as follows:
  - a. In the Password field, enter a password.
  - b. In the Confirm Password field, enter the password again.
  - c. Click Encrypt.  
The encrypted password is displayed in the Encrypted Password field.
  - d. From the Encrypted Password field, cut the encrypted password and then copy the encrypted value to the appropriate location.
9. Select Save to save your entries.
10. Click Validate to confirm that your entries are correct.  
The validation confirms that the necessary parameters are present and correct, and simulates a file transfer with the entered information. You either see a message that confirms the success of the validation, or a message that displays an error for missing parameters or an unsuccessful transfer simulation.
11. To add additional report nodes, click Add to return to the Search page.

## Defining the Report Node to Use FTPS

To define the report node to use FTPS:

1. Select PeopleTools, Process Scheduler, Report Nodes.
2. Select Add a New Value, enter the Report node name, and click Add.



3. On the Report Node Definition page, select FTPS from the Protocol drop-down list.

The screenshot shows the Oracle Report Node Definition page for the FTPS protocol. The page is titled "Report Node Definition" and includes a navigation bar with "Favorites", "Main Menu", "PeopleTools", "Process Scheduler", and "Report Nodes". The Oracle logo is visible in the top left. The page contains several sections for defining the report node:

- Node Name:** FTPS
- \*Protocol:** FTPS (selected from a dropdown)
- Validate:** A button to validate the node.
- Distribution Node Details:**
  - URLID:** http://<machine\_name>:<port\_number>/psreports/<site\_name>
  - Description:** FTPS sample
  - Operating System:** Windows (selected from a dropdown)
  - Network Path:** (empty field)
- Login Details:**
  - Login ID:** <user\_id>
  - Password:** (masked with dots)
  - Confirm Password:** (masked with dots)
- File Transfer Details:**
  - Home Directory:** \\<machine\_name>\psreports
  - FTP Address:** <machine\_name>
  - SSL Mode:** EXPLICIT (selected from a dropdown)
- Connection Properties:** A table with columns for Property Name and Property Value.
- Password Encryption:**
  - Password:** (empty field)
  - Confirm Password:** (empty field)
  - Encrypt:** A button to encrypt the password.
  - Encrypted Password:** (empty field)

At the bottom of the page, there are buttons for "Save", "Notify", and "Refresh".

Report Node Definition page for the FTPS protocol

4. In the Distribution Node Details area, enter the following information:

- **URLID:** Enter the URL of the web server using this format:

`http://<machine_name>:<port_number>/psreports/<site_name>`

Replace *<machine name>* with the name of your web server. If you are using an HTTP port other than 80, you need to specify the port number. The variable *<site name>* refers to the directory where you installed the PIA files; this will default to ps for the first installation.

---

**Note.** If you specify the Authentication Token Domain name during the PIA installation, you must include a fully qualified domain name for the URL instead of the IP address.

---



---

**Note.** If you installed the web server software with the default TCP port of 80, you do not need to specify the port number in the URL path. However, if you installed the web server to some other port, you must specify the port number in the URL path.

---

- *Description:* Enter a description of the server (optional).
  - *Operating System:* Select the operating system of the Report Repository, Windows or UNIX.
  - *Network Path:* This information is not required for the FTPS protocol.
5. In the Login Details area, enter the following information:
- *Login ID:* Enter the FTP User ID.
  - *Password and Confirm Password:* Enter the password, and enter it a second time, for the user ID specified in the Login ID field.
6. In the File Transfer Details area, enter the following information:
- *Home Directory:* Enter the directory specified during the PIA installation as the Report Repository. The FTP User ID must have write access to this directory. Note that this is not a required field for FTP transfer, as the system uses the Report Repository directory specified at install time or the current directory assigned to ReportRepositoryPath in configuration.properties. Note that the value you enter for the Report Repository Path in the Web Profile at install time overrides any entry for ReportRepositoryPath in configuration.properties.

For Microsoft Windows operating systems, the directory needs to match the Report Repository path. Make sure that you do not include any drive information—as in c:\psreports\—because you are using the FTP protocol to interpret this parameter.

- *FTP Address:* Enter the machine name or the IP address of the Report Repository. If the name of the machine is used, it must be included on a DNS server.
- *SSL Mode:* Select Explicit or Implicit from the drop-down list.

These are two separate methods developed to invoke the client security for use with FTP clients. With the explicit mode, FTPS-aware clients can invoke security with an FTPS-aware server without breaking overall FTP functionality with non-FTPS-aware clients. The implicit method requires that all clients of the FTPS server be aware that SSL is to be used on the session, and thus is incompatible with non-FTPS-aware clients.

7. In the Connection Properties area, click the lookup button (magnifying glass) and select one of the properties in the following table:

Click the plus sign to add another connection property.

| Property Name       | Property Value                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
|---------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ACTIVEMODE          | To enable active mode, add the ACTIVEMODE property to the URL and set it to Y.<br><br>The default FTPS connection mode is extended passive mode.                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| ACTIVEPORTOPTION    | This property can be used along with ACTIVEMODE. When active mode is enabled, you can use ACTIVEPORTOPTION to specify the IP address and port on which the FTP server can be accessed. This is useful when the server is behind a firewall. By default, ACTIVEPORTOPTION uses the default IP address of your system. If you want to use a particular IP address, set the ACTIVEPORTOPTION value to either the full IP address, a host name to resolve to an IP address, or a local network interface name.<br><br>You can also specify a port range. For example:<br><i>10.176.147.111:10000-13000</i> |
| CERTALIAS           | Certificate Alias: The Certificate Alias must be an alias name of a certificate stored in the database (using the PeopleSoft PeopleTools Digital Certificates page).<br><br><b>Note.</b> Currently, only PEM certificates are supported for FTPS.                                                                                                                                                                                                                                                                                                                                                      |
| ENABLEEPRPRT        | This option can be used only with Active Mode. If Active Mode is enabled and ENABLEEPRPRT is set to N, then the system will use a PORT (IPv4) Active Mode connection.<br><br>By default, ENABLEEPRPRT is Y, if Active Mode is set to Y.                                                                                                                                                                                                                                                                                                                                                                |
| EXTENDEDPASSIVEMODE | <ul style="list-style-type: none"> <li>0: Disable EPSV</li> <li>1: Enable EPSV</li> </ul> <p>This property enables you to control whether extended passive mode (EPSV) will be used by FTP.</p> <p>EPSV is used by default. That is, by default, this value is considered to be 1.</p> <p>If the client fails to connect to the server with EPSV, then the system will try passive mode (PASV). To use PASV only, add EXTENDEDPASSIVEMODE to the URL Properties and set it to 0.</p>                                                                                                                   |
| JKSPASSWORD         | Specify the Java keystore (JKS) password.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| JKSPATH             | Specify the Java keystore (JKS) user.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |

| Property Name    | Property Value                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
|------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| KEYSTOREPASSWORD | <p>This property is required for FTPS and HTTPS repositories. For attachments transferred from the PeopleSoft system to the FTPS or HTTPS repository, the system retrieves the key pair for the client certificate from the digital certificate store and writes the pair to a file in PKCS12 format with password protection. The value of this property will be used as the password for the PKCS12 file.</p> <p>The PKCS12 file enables connection and file transfer, and it exists only temporarily in &lt;PS_SERVDIR&gt;\files\&lt;CERT ALIAS NAME&gt; for the duration of the file transfer. The system deletes the file after the file transfer transaction.</p> <p><b>Note.</b> If the system fails to delete the certificate alias file, a message will be written to the application server log. The maximum number of files that can exist at any time is equal to the total number of FTPS and HTTPS URL identifiers defined in the system.</p> <p>For information on setting the PS_SERVDIR environment variable, see the <i>PeopleTools: Integration Broker</i> product documentation.</p> |
| PASSWORD         | Specify the password associated with the USER property, which identifies the FTP User ID.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| SSLUAGELEVEL     | <ul style="list-style-type: none"> <li>0 - <i>No SSL</i>: No SSL will be used.</li> <li>1 - <i>Try SSL</i>: Try using SSL, but proceed as normal otherwise.</li> <li>2 - <i>Control</i>: Require SSL for the control connection.</li> <li>3 - <i>SSL Only</i>: (Default) Require SSL for all communication.</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| USER             | Specify the FTP User ID used for authentication when accessing the FTP site.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| VERIFYHOST       | <ul style="list-style-type: none"> <li>0: Do not verify the server for host name.</li> <li>1: Check if there exists any value in the common name field in the server certificate. This check does not verify if it matches with what the client specifies.</li> <li>2: (Default) Check for a match with the host name in the URL with the common name or Subject Alternate field in the server certificate.</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| VERIFYPEER       | <ul style="list-style-type: none"> <li><i>False</i>: Do not verify the peer.</li> <li><i>True</i>: (Default) Verify the peer by authenticating the certificate sent by the server.</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |

8. If you need to specify an encrypted password in any of the property fields, use the Password Encryption area to generate the encrypted password, as follows:

- a. In the Password field, enter a password.
- b. In the Confirm Password field, enter the password again.
- c. Click Encrypt.

The encrypted password is displayed in the Encrypted Password field.

- d. From the Encrypted Password field, cut the encrypted password and then copy the encrypted value to the appropriate location.
9. Select Save to save your entries.
  10. Click Validate to confirm that your entries are correct.

The validation confirms that the necessary parameters are present and correct, and simulates a file transfer with the entered information. You either see a message that confirms the success of the validation, or a message that displays an error for missing parameters or an unsuccessful transfer simulation.

11. To add additional report nodes, click Add to return to the Search page.

## Defining the Report Node to Use SFTP

To define the report node to use SFTP:

1. Select PeopleTools, Process Scheduler, Report Nodes.
2. Select Add a New Value, enter the Report node name, and click Add.

3. On the Report Node Definition page, select SFTP from the Protocol drop-down list.

The screenshot shows the Oracle Report Node Definition page for the SFTP protocol. The page is titled "Report Node Definition" and includes a navigation bar with "Favorites", "Main Menu", "PeopleTools", "Process Scheduler", and "Report Nodes". The Oracle logo is visible in the top left. The page contains several sections for configuring the report node:

- Node Name:** SFTP
- \*Protocol:** SFTP (selected from a dropdown menu)
- Validate:** A button to validate the configuration.
- Distribution Node Details:**
  - URLID:** `http://<machine_name>:<port_number>/psreports/<site_name>`
  - Description:** SFTP sample
  - Operating System:** Windows (selected from a dropdown menu)
- Login Details:**
  - Login ID:** <user\_id>
  - Password:** (masked with dots)
  - Confirm Password:** (masked with dots)
- File Transfer Details:**
  - Home Directory:** \\<machine\_name>\psreports
  - FTP Address:** <machine\_name>
- Connection Properties:** A table with columns for Property Name and Property Value.
- Password Encryption:**
  - Password:** (input field)
  - Confirm Password:** (input field)
  - Encrypt:** A button to encrypt the password.
  - Encrypted Password:** (input field)

At the bottom of the page, there are buttons for "Save", "Notify", and "Refresh".

Report Node Definition page for the SFTP protocol

4. In the Distribution Node Details area, enter the following information:

- **URLID:** Enter the URL of the web server using this format:

`http://<machine_name>:<port_number>/psreports/<site_name>`

Replace *<machine name>* with the name of your web server. If you are using an HTTP port other than 80, you need to specify the port number. The variable *<site name>* refers to the directory where you installed the PIA files; this will default to ps for the first installation.

---

**Note.** If you specify the Authentication Token Domain name during the PIA installation, you must include a fully qualified domain name for the URL instead of the IP address.

---

---

**Note.** If you installed the web server software with the default TCP port of 80, you do not need to specify the port number in the URL path. However, if you installed the web server to some other port, you must specify the port number in the URL path.

---

- *Description:* Enter a description of the server (optional).
  - *Operating System:* Select the operating system of the Report Repository, Windows or UNIX.
  - *Network Path:* This information is not required for the SFTP protocol.
5. In the Login Details area, enter the following information:
- *Login ID:* Enter the FTP User ID.
  - *Password and Confirm Password:* Enter the password, and enter it a second time, for the user ID specified in the Login ID field.
6. In the File Transfer Details area, enter the following information:
- *Home Directory:* Enter the directory specified during the PIA installation as the Report Repository. The FTP User ID must have write access to this directory. Note that this is not a required field for FTP transfer, as the system uses the Report Repository directory specified at install time or the current directory assigned to ReportRepositoryPath in configuration.properties. Note that the value you enter for the Report Repository Path in the Web Profile at install time overrides any entry for ReportRepositoryPath in configuration.properties.
- For Microsoft Windows operating systems, the directory needs to match the Report Repository path. Make sure that you do not include any drive information—as in c:\psreports\—because you are using the FTP protocol to interpret this parameter.
- *FTP Address:* Enter the machine name or the IP address of the Report Repository. If the name of the machine is used, it must be included on a DNS server.

7. In the Connection Properties area, click the lookup button (magnifying glass) and select one of the properties in the following table.

Click the plus sign to add additional connection properties.

| Property Name | Property Value                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
|---------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| AUTHTYPE      | Select one of the following the authentication types: <ul style="list-style-type: none"> <li>• <i>PUBLICKEY</i></li> <li>• <i>PASSWORD</i></li> <li>• <i>ANY</i></li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| PASSWORD      | Specify the user password. You can enter the password in the Password Encryption box, click Encrypt, and then copy the encrypted value to the Password property.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| PASSWORDKEY   | Enter the password for the private key.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| PRIVATEKEY    | Select the private key.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| PUBLICKEY     | Select the public key.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| SSHKEYALIAS   | <p>Select the SSH certificate saved to the database using the PeopleTools Security, Digital Certificates page (select PeopleTools, Security, Security Objects, Digital Certificates). The SSH certificate added through the Digital Certificates page contains both the public and private key data, identified by the Alias column value on the Digital Certificates page.</p> <p>If using the SSHKEYALIAS URL property, the Property Value prompt displays only the list of SSH certificates that have been added to the Digital Certificates page. If you have added the SSH certificate using the Digital Certificates page, and you have assigned an SSH certificate to the SSHKEYALIAS URL property, the system ignores the PUBLICKEY and PRIVATEKEY properties, regardless of whether they refer to valid key files in the file system.</p> <p>If you provided a password (or passphrase) when generating your SSH certificate, specify that value using the PASSWORDKEY URL property.</p> <p>See <i>PeopleTools: Security Administration</i>, "Configuring Digital Certificates."</p> |
| USER          | Specify the user ID to be authenticated.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |

8. If you need to specify an encrypted password in any of the property fields, use the Password Encryption area to generate the encrypted password, as follows:
- In the Password field, enter a password.
  - In the Confirm Password field, enter the password again.
  - Click Encrypt.



The encrypted password is displayed in the Encrypted Password field.

- d. From the Encrypted Password field, cut the encrypted password and then copy the encrypted value to the appropriate location.
9. Select Save to save your entries.
10. Click Validate to confirm that your entries are correct.

The validation confirms that the necessary parameters are present and correct, and simulates a file transfer with the entered information. You either see a message that confirms the success of the validation, or a message that displays an error for missing parameters or an unsuccessful transfer simulation.

11. To add additional report nodes, click Add to return to the Search page.

## Task 15A-2-5: Setting Up the Distribution for Your Process Scheduler Server

To set up the Distribution Settings for your Process Scheduler Server:

1. Select PeopleTools, Process Scheduler, Servers.
2. Enter the Server Name (such as PSNT). The Server Definition page appears.
3. Select the Distribution tab.

The screenshot shows the Oracle PeopleTools interface. The breadcrumb trail at the top reads: Favorites > Main Menu > PeopleTools > Process Scheduler > Servers. The Oracle logo is on the left, and a search bar is in the center. On the right, there are links for 'Advanced Search' and 'Last Search Results'. Below the breadcrumb trail, there are links for 'New Window', 'Help', and 'Personalize Page'. The main content area has five tabs: 'Server Definition', 'Distribution' (which is selected), 'Operation', 'Notification', and 'Daemon'. Under the 'Distribution' tab, the 'Server Name' is set to 'PSNT'. Below this is a section titled 'Server Distribution Details' with a search icon. It contains four fields: 'Distribution Node Name' (with a search icon), 'Maximum Transfer Retries' (with a numeric input field), 'Interval for Transfer Attempt' (with a numeric input field and the unit 'seconds'), and 'Transfer System Files to Report Repository' (with a checkbox). At the bottom of the form are five buttons: 'Save', 'Return to Search', 'Notify', 'Add', and 'Update/Display'. Below the buttons is a link to 'Server Definition' and a breadcrumb trail: 'Server Definition | Distribution | Operation | Notification | Daemon'.

Server Definition page for PSNT: Distribution tab

4. Click the lookup button for Distribution Node Name to display the report node names and select the name of the required report node.
5. Enter a number for the Maximum Transfer Retries. This is the maximum number of times the server can try to send a report before it errors out.
6. Enter the number of seconds for the Interval for Transfer Attempt field. This is the interval between attempts to send the report.

7. Select the check box Transfer Log Files to Report Repository if you want to transfer all log and trace files from processes that do not generate reports.
8. Click Save to save your entries.
9. If Process Scheduler is running, you must reboot for any new settings to take effect.

To view reports (log files or system files) from Report Repository, you need to pass the authentication. Report Repository should be treated as a separate PeopleSoft application. To navigate from PIA to Report Repository, you need to set up single signon in order to avoid getting a prompt for a second signon.

## Task 15A-2-6: Setting Up Sending and Receiving of Report Folders in the Report Manager

To be able to view reports in the Report Manager Explorer and List pages, you need to set up the sending and receiving of report folders in the Report Manager by activating the domain on which a sending and receiving server resides. Consult the documentation covering the PeopleSoft Integration Broker to learn how to activate the sending and receiving server domain.

See *PeopleTools: Integration Broker*.

See *PeopleTools: Integration Broker Service Operations Monitor*.

## Task 15A-3: Setting Environment Variables

---

To set the appropriate Tuxedo environment variables, carry out these steps. (If you have already set these variables on the machine you are using as your Process Scheduler Server, you can skip this task.)

See "Installing Additional Components," Installing Oracle Tuxedo on Microsoft Windows.

To set the variables:

1. Choose Start, Settings, Control Panel.
2. Double-click the System icon.
3. Make sure that the NLSPATH environment variable is set.

NLSPATH does not need to be explicitly set since Oracle Tuxedo sets NLSPATH in its own registry tree. This value can be displayed using Control Panel, Tuxedo, on the Environment tab. However, the installation of certain products, such as IBM DB2 connectivity (DB2 for z/OS and DB2 for Linux, UNIX, and Windows) sets NLSPATH to a value that causes Oracle Tuxedo to fail. The solution is to either set NLSPATH=c:\tuxedo\locale\c, or to delete it entirely and let Oracle Tuxedo pick up the value from its registry tree. If you are running DB2 for Linux, UNIX, and Windows, the solution instead is to append the c:\tuxedo\locale\c directory in the NLSPATH directory.

Search the Oracle Tuxedo documentation for additional information on NLSPATH.

## Task 15A-4: Setting Up Process Scheduler Server Agent

---

This section discusses:

- Understanding Process Scheduler Server Agent
- Creating and Configuring a Process Scheduler Server
- Reconfiguring a Process Scheduler Server

- Verifying the Process Scheduler Server Status

## Understanding Process Scheduler Server Agent

For installation purposes, you can use predefined server names and other definitions. The predefined name that you might use is as follows:

| Server Name | Operating System  |
|-------------|-------------------|
| PSNT        | Microsoft Windows |

To test this, use processes already defined in your PeopleSoft database. To set up a new server definition in your PeopleSoft database, refer to the *PeopleTools: Process Scheduler* product documentation.

**Note.** When creating multiple Process Scheduler Servers for the same database, each server must have a unique server name. For example, two Process Scheduler Servers, both named PSNT, cannot run against the same database.

## Task 15A-4-1: Creating and Configuring a Process Scheduler Server

This section describes how to create and configure a Process Scheduler server.

You can set Process Scheduler configuration parameters either by using PSADMIN, which provides an interactive dialog, or by editing the configuration file `psprcs.cfg` located in the `PS_CFG_HOME\appserv\prcs\database name` directory. The following steps assume you are using PSADMIN to specify parameter settings.

**Note.** For Cube Builder users, if Essbase Server is installed on a different machine than the Process Scheduler, you must install Essbase Client 11.1.2.1 on the process scheduler server machine. You must also ensure that the `%ESSBASEPATH%` and `%ARBORPATH%` environmental variables are properly set in the Process Scheduler.

**Note.** If you use the configuration file `psprcs.cfg`, be aware that in the PeopleSoft PeopleTools 8.49 release and later, the section [Output Dest Exceptions] has been modified to trap metastring exceptions not only in the output destination but in other process parameters as well. In this section the entry `OUTDEST_EXCEPT01=%ANYMETASTRING%` has been changed to `PARAMETER_EXCEPT01=%ANYMETASTRING%`.

To create and configure a Process Scheduler Server:

1. From `PS_HOME\appserv` on the batch server, type `psadmin`.

You see the PeopleSoft Server Administration menu, as in this example:

```

PeopleSoft Server Administration

PS_CONFIG_HOME C:\User\JSMITH\psft\pt\8.57
PS_HOME C:\psft\pt\ps_home8.57
PS_APP_HOME C:\psft\pt\hcm_app_home

1) Application Server
2) Process Scheduler
3) Search Server
4) Web (PIA) Server
```

- 5) Switch Config Home
- 6) Service Setup
- 7) Replicate Config Home
- 8) Refresh Config Home
- q) Quit

Command to execute (1-8 q):

2. Depending on your environment, you may see a message after the menu selection, which indicates that PSADMIN has modified the *PS\_CFG\_HOME*/peopletools.properties file with the current *PS\_HOME* location:

```

PS_CFG_HOME/peopletools.properties file has been updated.
You should use the Config Home Refresh feature in PSAdmin
to ensure that all of your domains are current.
Alternatively, you may recreate all of your domains.
Please press any key to continue...

```

This indicates that one of these situations exists:

- The *PS\_CFG\_HOME* that you are working with was used previously from a different *PS\_HOME*. In this case, you should recreate any existing Application Server, Process Scheduler, Search, or PIA domains in this *PS\_CFG\_HOME*.
- You configured your environment such that *PS\_CFG\_HOME* is the same as *PS\_HOME*. The first time you use PSADMIN to create a domain, it updates the *PS\_CFG\_HOME*/peopletools.properties file. Continue with the next step.

3. Select 2 to access the Process Scheduler submenus.
4. Select 2 for Create a domain from the PeopleSoft Process Scheduler Administration menu.

```

PeopleSoft Process Scheduler Administration

1) Administer a domain
2) Create a domain
3) Delete a domain
4) Import domain configuration

q) Quit
```

Command to execute (1-4, q) : 2

5. Enter the name of the domain at the following prompt, such as HRDMO in this example, and press ENTER:

Please enter name of domain to create : **HRDMO**

6. After the system creates the domain, the Quick-configure menu appears:

```

Quick-configure menu -- domain: HRDMO

 Features Settings
 ===== =====
1) App Engine : Yes 9) DBNAME : [HRDMO]
2) Master Scheduler : Yes 10) DBTYPE : [DB2UNIX]
```

```

3) Perf Collator : No
4) Domains Gateway : No
5) Push Notifications: No

output]
\binw]
\SYSTEM32]
directory>]

 Actions
 =====
6) Load config as shown
7) Custom configuration
8) Edit environment settings
h) Help for this menu
q) Return to previous menu

HINT: Enter 9 to edit DBNAME, then 6 to load

Enter selection (1-20, h, or q):
11) PrcsServer :[PSNT]
12) UserId :[PS]
13) UserPswd :[]
14) ConnectID :[people]
15) ConnectPswd:[]
16) Log/Output Dir:[%PS_SERVDIR%\log_⇒
17) SQRBIN :[%PS_HOME%\bin\sqr\DB2⇒
18) AddToPATH :[%WINDIR%;%WINDIR%⇒
19) DBBIN :[C:\<connectivity⇒
20) DomainConnectPswd:[]

```

7. If you need to modify any of these settings, enter the number next to the parameter name, type the new value, and press ENTER. This table lists the parameters and gives brief descriptions.

| Parameter                 | Description                                                                                                                                                                                                                                                                                                                                            |
|---------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Master Scheduler          | Select this option to enable the Master Scheduler Server (PSMSTPRC). The default is to enable the server.<br><br><i>See PeopleTools: Process Scheduler.</i>                                                                                                                                                                                            |
| App Engine                | Select this option to initiate Application Engine programs through the AE Tuxedo Server (PSAESRV). The default is set to run AE using PSAESRV.<br><br><i>See PeopleTools: Process Scheduler.</i>                                                                                                                                                       |
| Perf Collator             | Select this option to enable the PSPPMSSRV server process.<br><br><i>See PeopleTools: Performance Monitor, "Enabling the Required Elements on the Monitoring System."</i>                                                                                                                                                                              |
| Domain Gateways           | Select this option to enables inter domain communication, for example between Application Server and Process Scheduler domains.<br><br><i>See PeopleTools: Fluid User Interface Developer's Guide, "Setting Up Push Notification Configurations."</i>                                                                                                  |
| Push Notifications        | Select this option to enables pushing server events from PeopleSoft PeopleTools server runtime, such as Application Server and Process Scheduler, to browser clients and other PeopleSoft PeopleTools server runtime components.<br><br><i>See PeopleTools: Fluid User Interface Developer's Guide, "Setting Up Push Notification Configurations."</i> |
| Load config as shown      | Load the selections you made in the Quick Configure menu.                                                                                                                                                                                                                                                                                              |
| Custom configuration      | Make custom selections in PSADMIN, using options that are not available in the Quick Configure menu.                                                                                                                                                                                                                                                   |
| Edit environment settings | Edit, add, remove, comment out, and review domain-level environment variables.                                                                                                                                                                                                                                                                         |
| DBNAME                    | Specify the database name that is associated with a PeopleSoft Process Scheduler Server Agent, such as HRDMO, FSDMO, SADMO, and so on.                                                                                                                                                                                                                 |
| DBTYPE                    | Specify the database type: DB2UNIX (for DB2 for Linux, UNIX, and Windows).                                                                                                                                                                                                                                                                             |
| PrCsServer                | Specify the process server name. This must match the name defined in the Server Definition table, such as PSNT or PSUNX.                                                                                                                                                                                                                               |

| Parameter         | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
|-------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| UserId            | Enter the user ID, such as VP1 or PS.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| UserPswd          | <p>Enter the password for the user ID, as you specified during the database configuration.</p> <p>The password is hidden by masking characters as you type, in the Quick-configure menu after entry.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| ConnectID         | Enter the connect ID. This value is required.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| ConnectPswd       | <p>Enter the connect password, as you specified during the database configuration. This value is required.</p> <p>The password is hidden by masking characters as you type, in the Quick-configure menu after entry.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Log/Output Dir    | <p>Specify the directory in which files that are generated by the program are written. When PeopleSoft Process Scheduler initiates a process request, it creates a subdirectory in the format &lt;Process Type ID&gt;_&lt;Program Name&gt;_&lt;Process Instance&gt; that contains the generated files. For instance, the SQR program XRFWIN that ran with process instance 20 has all reports, trace, and log files in the subdirectory SQR_XRFWIN_20. It is also the optional directory used with the Output Destination field when scheduling a request. This variable (%%OutputDirectory%%) can be used in the File/Printer field of the Process Scheduler Request dialog box.</p> |
| SQRBIN            | Enter the path to the SQR executables.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| AddToPATH         | <p>(Optional for Tuxedo) Specify an additional directory that is appended to the PATH environment variable.</p> <p>For a DB2 LUW installation, specify the 64-bit connectivity software. For example, c:\sqllib\bin.</p> <p><b>Note.</b> If the PATH environment variable already includes the database connectivity location, you do not need to change the setting for AddToPATH.</p>                                                                                                                                                                                                                                                                                               |
| DBBIN             | Enter the path to the database drivers; that is, your connectivity software.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| DomainConnectPswd | <p>If you configured your Application Server domain to require a Domain Connection password, enter it here. Otherwise, leave it blank.</p> <p>The password is hidden by masking characters as you type, and in the Quick-configure menu after entry.</p> <p>See the information on setting Application Server Domain Parameters in the <i>PeopleTools: System and Server Administration</i> product documentation.</p>                                                                                                                                                                                                                                                                |

For descriptions of the PSADMIN options that do not appear in the Quick-configure menu, see the information on using PSADMIN in the *PeopleTools: Process Scheduler* product documentation. For a basic installation, in most cases you can accept the defaults.

8. When you have updated the settings as needed, choose 5, *Load config as shown*, from the Quick-Configure menu to save your settings to the Process Scheduler configuration file, `pstuxcfg`.
9. To start Process Scheduler, choose 1, for Administer Domain.
10. On the PeopleSoft Process Scheduler Administration menu, choose 1 for Boot this domain.

```

PeopleSoft Process Scheduler Administration

```

Domain Name: HRDMO

- ```
1) Boot this domain
2) Domain shutdown menu
3) Domain status menu
4) Configure this domain
5) TUXEDO command line (tmadmin)
6) Edit configuration/log files menu
7) Clean IPC resources of this domain
q) Quit
```

Command to execute (1-7, q) :

11. Choose 1, Boot (Serial Boot), or 2, Parallel Boot, from the PeopleSoft Domain Boot Menu.

Note. The messages you see and the number of processes started will depend on the options you chose during configuration.

12. If you want to stop Process Scheduler Server, from the PeopleSoft Domain Administration menu, choose 2, for Domain Shutdown menu, and then enter the number corresponding to the name of the appropriate database.

Note. If you see the following message, then the server is already down:

```
Command to execute (1-2, q) [q]: 1 Loading command line administration
utility ... tmadmin - Copyright (c) 2007-2008, Oracle. Portions *
Copyright 1986-1997 RSA Data Security, Inc. All Rights Reserved.
Distributed under license by Oracle. Tuxedo is a registered trademark. No
bulletin board exists. Entering boot mode. > TMADMIN_CAT:111: ERROR: No
such command.
```

Task 15A-4-2: Reconfiguring a Process Scheduler Server

If you create and then immediately configure a Process Scheduler server, you can use the Quick-configure menu. Alternatively, you can use PSADMIN as described in this section. Feel free to skip this procedure if you have already created and configured your Process Scheduler Server using the Quick-configure menu and want to move forward with your installation.

Note. If you want to configure the Process Scheduler Server while it is running, you need to stop and restart the server to load the new settings.

To reconfigure a Process Scheduler Server:

1. Go to *PS_HOME*\appserv and enter:

```
psadmin
```

2. Depending on your environment, you may see a message after the initial menu, which indicates that PSADMIN has modified the *PS_CFG_HOME*/peopletools.properties file with the current *PS_HOME* location:

```
*****
PS_CFG_HOME/peopletools.properties file has been updated.
You should use the Config Home Refresh feature in PSAdmin
to ensure that all of your domains are current.
Alternatively, you may recreate all of your domains.
Please press any key to continue...
*****
```

This indicates that one of these situations exists:

- The *PS_CFG_HOME* that you are working with was used previously from a different *PS_HOME*. In this case, you should recreate any existing Application Server, Process Scheduler, Search, or PIA domains in this *PS_CFG_HOME*.
- You configured your environment such that *PS_CFG_HOME* is the same as *PS_HOME*. The first time you use PSADMIN to create a domain, it updates the *PS_CFG_HOME*/peopletools.properties file. Continue with the next step.

3. Select 2 for Process Scheduler in the PeopleSoft Server Administration menu.
4. In the PeopleSoft Process Scheduler Administration menu, select 1 for Administer a domain.
5. Select the database for which the Process Scheduler needs to be configured.
6. You see the following prompt:

```
Do you want to change any config values (y/n)? [n]:
```

Specify y to start an interactive dialog that lets you examine or change parameter values.

7. Specify the configuration parameters one by one.

Configuration parameters are grouped into sections. At each section, you are asked whether to change any parameters—for example:

```
Values for config section - Startup
```

```
DBName=
DBType=
UserId=
UserPswd=
ConnectId=
ConnectPswd=
ServerName=
StandbyDBName=
StandbyDBType=
StandbyUserId=
StandbyUserPswd=
InMemoryDBName=
InMemoryDBType=
```

```
Do you want to change any values (y/n)? [n]:
```

- Specify y to change any parameter values for the current section. You are prompted for each parameter

value. Either specify a new value or press ENTER to accept the default. After you press ENTER, you are positioned at the next parameter in that section. When you are done with that section, you are again asked whether you want to re-edit any of the values you changed.

- The parameters StandbyDBName, StandbyDBType, StandbyUserID, and StandbyUserPswd are used for a standby database in an Oracle database environment.

See the information on implementing Oracle Active Data Guard in the *PeopleTools: Data Management*, product documentation.

- The parameters InMemoryDBName and InMemoryDBType are reserved for internal use.
- If you do not want to change any values, specify *n* and you are prompted for the next configuration section.

8. After you have selected all your parameters, you see this message:

```
You will need to shut down and start up the server to read the new⇒
settings.
```

For descriptions of the Process Scheduler options in the PSADMIN, see the *PeopleTools: Process Scheduler* product documentation. In most cases you can accept the defaults.

Task 15A-4-3: Verifying the Process Scheduler Server Status

At this stage it is a good idea to verify the Process Scheduler Server status.

To verify the Process Scheduler Server status:

1. From the PeopleSoft Process Scheduler Administration menu, choose option 3, for Domain status menu.

```
-----
PeopleSoft Process Scheduler Administration
-----
```

```
Domain Name: HRDMO
```

- ```
1) Boot this domain
2) Domain shutdown menu
3) Domain status menu
4) Configure this domain
5) TUXEDO command line (tmadmin)
6) Edit configuration/log files menu
7) Clean IPC resources of this domain
q) Quit
```

```
Command to execute (1-7, q) : 3
```

2. To verify the status of the Process Scheduler Server for a specific database, type the number corresponding to the appropriate database.

For example:

```
Database list:
```

- ```
1) HRDMO
```

```
Select item number to start: 1
```

```
Loading command line administration utility ...
tmadmin - Copyright (c) 2007-2008 Oracle.
Portions * Copyright 1986-1997 RSA Data Security, Inc.
All Rights Reserved.
Distributed under license by Oracle.
Tuxedo is a registered trademark.
```

```

> Prog Name      Queue Name  Grp Name      ID RqDone Load Done Current=>
Service
-----
BBL.exe          46845      PSSERVER+      0      9      450 ( IDLE )
PSMONITORSRV.e  MONITOR    MONITOR        1      0      0 ( IDLE )
PSAESRV.exe      00101.00001 AESRV          1      0      0 ( IDLE )
PSAESRV.exe      00101.00002 AESRV          2      0      0 ( IDLE )
PSAESRV.exe      00101.00003 AESRV          3      0      0 ( IDLE )
PSPRCSRV.exe     SCHEDQ     BASE           101     0      0 ( IDLE )
PSMSTPRC.exe     MSTRSCHQ   BASE           102     0      0 ( IDLE )
PSDSTSRV.exe     DSTQ       BASE           103     0      0 ( IDLE )
>

```

You can also verify the status of the Process Scheduler Server from Process Monitor in PeopleSoft Pure Internet Architecture. To verify the Process Scheduler Server status from the Process Monitor page, go to PeopleTools, Process Scheduler, Process Monitor, and select *Server List*.

If the user has the process security rights to update the server status, the *Refresh* button can be used to refresh the screen, too.

See [Setting Up Process Scheduler Security](#).

This example of the Server List page shows two Process Scheduler servers with status Down, and one with status Running.

Process List Server List		<div>Refresh</div>							
Server	Hostname	Last Update Date/Time	Dist Node	Master	CPU (%)	Memory (%)	Active	Status	Details
PSNT	PTLAB95	10/28/2003 9:53:33AM	https	N	1	29	0	Down	Details
QEPSNT2	PTLAB95	10/28/2003 9:53:45AM	https	N	1	29	0	Down	Details
QE_HPX1	pt-hp07	10/28/2003 10:05:47AM	https	Y	21	34	1	Running	Details

Process Monitor page: Server List tab

Task 15A-5: Starting Process Scheduler as a Windows Service (Optional)

You can start the Process Scheduler server as a Windows service. This means that administrators do not need to manually boot each Process Scheduler server that runs on a Microsoft Windows machine. Instead, each time you boot the Microsoft Windows server where the Process Scheduler server resides, the Process Scheduler Server will boot automatically. You can also still manually boot Process Scheduler Servers on your Microsoft Windows server.

Note. If you have set up TUXDIR and TEMP as new SYSTEM variables, you need to reboot your machine before any Windows services will pick up the value of these environment variables.

Note. You can also set up application servers and search servers as a Windows service using the instructions provided here.

The following directions assume that the Process Scheduler is already configured on the Microsoft Windows server.

To set up the Windows Service for a Process Scheduler Server:

1. Open the System utility within the Control Panel, and set the variables, listed with a brief explanation in the following table, in the System Variables section of the Environment tab.

Note. Even if the following variables are in the User Variables section, they must also be in the System Variables section because the Windows service will be started under the System Account.

Variable	Value
TEMP	Specify the location of the TEMP directory on the Windows server, as in C:\TEMP.
TUXDIR	Specify the location of the Tuxedo directory on the Windows server, as in C:\tuxedo.

2. Reboot the Windows computer if any changes or additions were made for the system variables.
3. Run the PeopleSoft PSADMIN utility (psadmin.exe in the *PS_HOME*\appserv directory), and press ENTER.
4. Select 6 for Service Setup from the PeopleSoft Server Administration menu.

```

-----
PeopleSoft Server Administration
-----
PS_CFG_HOME          C:\Users\JSMITH\psftuser\psft\pt\8.57
PS_HOME              C:\psft\pt\ps_home8.57
PS_APP_HOME          C:\HC9.2

```

- ```

1) Application Server
2) Process Scheduler
3) Search Server
4) Web (PIA) Server
5) Switch Config Home
6) Service Setup
7) Replicate Config Home
8) Refresh Config Home
q) Quit

```

Command to execute (1-8, q): 6

5. Select 1 from the PeopleSoft Services Administration menu.

```

PeopleSoft Services Administration

```

- 1) Configure Windows Service
- 2) Install Windows Service
- 3) Delete Windows Service
- 4) Edit Service Configuration File
- q) Quit

Command to execute (1-4, q) : **1**

When asked if you want to change configuration values, enter y.

- 6. Enter the name of the Process Scheduler databases that you intend to include as part of the Windows service.

Values for config section - NT Services

```
Service Start Delay=60
Application Server Domains=HRDMO
Process Scheduler Databases=HRDMO
Search Server Domains=HRDMO
```

Do you want to change any values (y/n)? [n]:

If you specify more than one Process Scheduler database, separate each entry with a comma.

---

**Note.** You can use PSADMIN to set up Process Scheduler Servers, application servers, or search servers as a Windows service. The Windows Service psntrsvr.exe automatically starts application servers, Process Scheduler servers, and search servers that reside on the same Microsoft Windows machine. Occasionally, psntrsvr.exe would attempt to initiate a connection between an application server, Process Scheduler server, or search server and a database on the same machine that was not ready to receive requests. As a result the connection would fail. When you set up these servers as a Windows Service, you can specify a Service Start Delay, in seconds, that elapses before a service attempts to start any application server domains, Process Scheduler servers, or search servers. This allows the RDBMS to boot and become available to accept requests. The default setting for the Service Start Delay parameter is 60 seconds.

---



---

**Note.** The NT Services section of the PSADMIN modifies the psntrsvr.cfg file located in the *PS\_CFG\_HOME\appserv* directory. You can edit this file manually by selecting *4, Edit Service Configuration File* from the PeopleSoft Services Administration menu. If you edit it, you need to delete and then install the service again.

---

- 7. Select option 2 from the PeopleSoft Services Administration menu.

```

PeopleSoft Services Administration

1) Configure Windows Service
2) Install Windows Service
3) Delete Windows Service
4) Edit Service Configuration File
q) Quit
```

Command to execute (1-4, q) : **2**

- 8. Return to the Control Panel, choose *Administrative Tools*, and launch the Services utility.
- 9. On the Services dialog, scroll to find the entry that adheres to the following naming convention, and select it:

PeopleSoft <PS\_CFG\_HOME>

For example:

PeopleSoft C:\Users\JSMITH\psftuser\psft\pt\8.57

---

**Note.** The default Startup mode is Manual.

---

10. Click *Startup*.

11. On the Service dialog in the Startup Type group, select *Automatic*, and in the Log On As group, select *Local System Account*. Then click OK.

---

**Note.** The *Log On As* setting needs to reflect that which you set for your ORACLE ProcMGR V12.2.2.0.0\_VS2015 and Tlisten processes. Oracle recommends that you set these services to *Local System Account* when you install Tuxedo. The *Log On As* value only affects the application server because Process Scheduler runs independently from Tuxedo. See the chapter "Installing Additional Components" for more information on installing Tuxedo, and refer to the chapter "Configuring the Application Server on Windows" for the details on configuring the application server.

---

12. On the Services dialog, make sure the PeopleSoft service is selected, and click Start.

13. Use the Process Monitor to verify that the Process Scheduler Server is running. You can also use Task Manager to verify that the executables involved with the service are running.

For the Process Scheduler, make sure that the psprcsrv.exe is running. If you have customized the name of psprcsrv.exe, make sure the appropriate executable is running.

## Task 15A-6: Configuring the Process Scheduler for Microsoft Word (Optional)

---

This section discusses:

- Configuring Process Scheduler
- Executing Winword on Mapped Drive

### Task 15A-6-1: Configuring Process Scheduler

Some applications process documents using Microsoft Word. Here is how to configure Microsoft Word to work with the Process Scheduler.

---

**Note.** Microsoft Word must already be installed on the server; it is not included with the PeopleSoft PeopleTools install.

---

To configure Process Scheduler for Microsoft Word:

1. Log in to the PeopleSoft application in a browser and select PeopleTools, Process Scheduler, Processes.
2. Search for Process Type *Winword* and select a process.

3. On the Process Definition page, select Override Options, as shown in this example.

Process Definition page: Override Options

4. In the Parameter List field, enter %%PS\_HOME%%\WINWORD\WORDSAMP.DOCX/mWORDSAMP and save.
5. Locate the Process Scheduler configuration file psprcs.cfg in *PS\_CFG\_HOME*\appserv\prcs\*<database\_name>* directory and open it for editing.
6. In the [Process Scheduler] section, edit the WINWORD entry so that it points to the directory where winword.exe is installed—for example, "WINWORD=C:\Program Files\Microsoft Office\OFFICE 12" (include the quotes in the entry).
7. If spaces exist in the WINWORD path in the Process Scheduler configuration file (psprcs.cfg), Microsoft Word reports will fail. You will need to modify the Process Type Definition and add quotes around the entry in the Command Line field, for example " %%WINWORD%%\winword.exe".
8. Change the Microsoft Word macro security to allow macros to be run.  
Start Microsoft Word and select Tools, Macro, Security. Select the *Low* security setting and click OK.
9. If you are running on Microsoft Windows, modify your macros to include the following line:  
`Application.AutomationSecurity=msoAutomationSecurityLow`  
You can see an example by viewing the macros in *PS\_HOME*\winword\Wordsamp.doc.
10. Make sure that all the servers (that is, Application Server and Process Scheduler servers) are running in the context of the logged-in user, as WinWord is executed in the same context.

## Task 15A-6-2: Executing Winword on Mapped Drive

If you encounter a problem in executing the WinWord process on a mapped drive, there are a couple of solutions to try. If the first solution does not work, try the second one. Try the following workaround suggestions in the order given.

To perform the first workaround:

1. Copy the file WORDSAMP.dotm from *PS\_HOME\WINWORD\*.
2. Locate the WinWord templates folder and place the file WORDSAMP.dotm there.

In general, you can find the templates folder under the logged-in user's directory. For example, for user psftuser, this would be:

C:\Users\psftuser\Microsoft\Templates


3. Open the WinWord.docx file under *PS\_HOME\WINWORD* folder and verify macro is present.
4. Sign in to the PeopleSoft application to execute the WinWord process and verify its status in Process Monitor.

To perform the second workaround:

1. In Microsoft Word, click the Microsoft Office button, and click Word Options.
2. Select Trust Center, and then click Trust Center Settings, Trusted Locations.
3. Select the check box for Allow Trusted Locations on my network, and clear the check box Disable all Trusted Locations.



4. Create a new trusted location with path pointing to the *PS\_HOME\WINWORD* folder on your mapped drive. In this example, the trusted location is *\\server1\pt854\WINWORD*:



Microsoft Word Trusted Locations window


## Task 15A-7: Configuring Setup Manager

Before you can use Setup Manager, you must fulfill these requirements:

- To use the Excel to CI template-generation feature of Setup manager, the Process Scheduler must be PSNT. That is, Process Scheduler must be installed on a Microsoft Windows machine.
- Process Scheduler must be running.
- Any Process Scheduler environment variables (especially %PS\_FILEDIR%) must be specified.
- A supported version Microsoft Office must be present on the process scheduler server, and Microsoft Excel must be installed.
- The MSXML COM object for Microsoft Excel, msxml4.dll, must be present on the system.

For confirmation, navigate to %SystemRoot%\system32\msxml4.dll. Right-click and select Properties. On the

msxml4.dll Properties dialog box, select the Version tab, and then Product Version. As shown on this example of the msxml4.dll Properties dialog box, the version number must be 4.20 or above.



msxml4.dll Properties dialog box: Version tab

## See Also

*PeopleTools: Setup Manager*

Microsoft support, [support.microsoft.com](http://support.microsoft.com)

## Task 15A-8: Installing Products for PS/nVision

---

This section discusses:

- Understanding the PS/nVision Setup
- Installing Products for PS/nVision in Excel Automation Mode
- Installing Microsoft .NET Framework 4.6.1
- Installing Microsoft Open XML SDK for PS/nVision

## Understanding the PS/nVision Setup

PS/nVision can operate in the following three modes for PS/nVision:

- OpenXML mode

OpenXML is the default mode for PeopleSoft PeopleTools.

- Excel automation mode
- Cross-platform mode

Cross Platform is the only supported mode on the UNIX platforms that are certified for executing PS/nVision Reports on the web.

See "Setting Up Process Scheduler on UNIX," Using PS/nVision in Cross-Platform Mode on UNIX.

The different modes of executing PS/nVision are enabled by setting the UseExcelAutomation parameter in the Process Scheduler configuration file (psprcs.cfg) as follows:

- 0 - OpenXML mode
- 1 - Excel Automation mode
- 2 - Cross Platform mode

### See Also

*PeopleTools: PS/nVision*

*PeopleTools: Process Scheduler*

## Task 15A-8-1: Installing Products for PS/nVision in Excel Automation Mode

To set up PS/nVision in Excel automation mode:

- For all batch servers, install Microsoft Excel on the batch server. PeopleSoft PeopleTools supports 64-bit versions of Microsoft Excel 2010, Excel 2013, and Excel 2016.

---

**Note.** The 32-bit version of Microsoft Excel should not be installed on the machine where PS/nVision needs to run in Excel Automation Mode, as that would cause issues with running PS/nVision with 64-bit Microsoft Excel.

---

- If the batch server is on a 64-bit Microsoft Windows machine, create an empty "Desktop" folder with this path:  
C:\Windows\System32\config\systemprofile\Desktop

## Task 15A-8-2: Installing Microsoft .NET Framework 4.6.1

Before setting up PS/nVision in OpenXML mode, use these instructions to install Microsoft .NET Framework. Microsoft Open XML SDK 2.0 requires Microsoft .NET Framework versions 4.6.1.

---

**Note.** Microsoft .NET Framework 4.6.1 may be included as a feature on your operating system. See your operating system instructions to verify whether it is installed and enabled.

---

To install Microsoft .NET Framework 4.6.1:

1. If there is an existing installation of Microsoft .NET Framework 4.0 or 4.6 installed on your computer:


- a. Select Start, Programs, Control Panel, Add/Remove Programs
- b. Locate the existing Microsoft .NET Framework installation and remove it.
2. Go to *PS\_HOME*\setup\dotnetredist.
3. Run the dotNetFx461\_Full\_x86\_x64.exe file.
4. Review the license agreement, select the option I have read and accept the license terms, and then click Install.  
A progress indicator appears.
5. Click Finish when the installation is complete.

### Task 15A-8-3: Installing Microsoft Open XML SDK for PS/nVision

As described in the previous section, you must have installed Microsoft .NET Framework versions 4.6.1 before beginning this installation.


To install Microsoft Open XML SDK V2.0:

1. Go to *PS\_HOME*\setup\OpenXmlSDK.
2. Run the OpenXMLSDKv2.msi file.
3. Click Next on the welcome window.




Microsoft Open XML SDK 2.0 welcome window

4. Review the license agreement, select the option I agree, and then click Next.




Microsoft Open XML SDK 2.0 License Agreement window

5. Accept the default location for the installation, C:\Program Files\Open XML SDK\V2.0, and then click Next.




Microsoft Open XML SDK 2.0 Select Installation Folder window

6. Click Next on the Confirm Installation window to begin the installation.



Microsoft Open XML SDK 2.0 Confirm Installation window

7. Click Close when the installation is complete.



Microsoft Open XML SDK 2.0 Installation Complete window



## Chapter 15B

# Setting Up Process Scheduler on UNIX

This chapter discusses:

- Prerequisites
- Setting Up Process Scheduler Security
- Setting Up Process Scheduler to Transfer Reports and Logs to the Report Repository
- Setting Up Process Scheduler Server Agent

## Prerequisites

---

If your database runs on UNIX, you need to set up a Microsoft Windows batch environment on a Microsoft Windows application server or on a dedicated Microsoft Windows workstation for Microsoft Windows-specific batch processes, such as nVision reports, Cube Builder, or Microsoft Word. These processes are Microsoft Windows-specific applications that cannot be executed by the Process Scheduler on UNIX.

---

**Note.** Oracle supports a number of versions of UNIX and Linux in addition to Microsoft Windows for the PeopleSoft installation. Throughout this book, there are references to operating systems. Where necessary, this book refers to specific operating systems by name (for example, Oracle Solaris, IBM AIX, or Linux); however, for simplicity the word UNIX is often used to refer to all UNIX-like operating systems, including Linux. Oracle supports a number of versions of UNIX and Linux in addition to Microsoft Windows for the PeopleSoft installation. Throughout this book, there are references to operating systems. Where necessary, this book refers to specific operating systems by name (for example, Oracle Solaris, IBM AIX, HP-UX Itanium, or Linux); however, for simplicity the word UNIX is often used to refer to all UNIX-like operating systems, including Linux.

---

Before setting up your Process Scheduler, you must:

- Install Tuxedo.  
See "Installing Additional Components."
- Install database connectivity to be able to communicate with your database server (Process Scheduler requires a direct connection to the database).  
See "Preparing for Installation."
- Set up the web server with the PeopleSoft Pure Internet Architecture, as described in the previous chapter. This is required to set up the Process Scheduler to transfer reports or log files to the Report Repository.
- Set up your COBOL batch environment if you need to run COBOL processes through Process Scheduler. If the PeopleSoft modules purchased do not contain any COBOL modules, the COBOL run time libraries are not required. Also, COBOL is not required for applications that contain no COBOL programs. Consult My Oracle Support for the details on whether your application requires COBOL.  
See "Preparing for Installation," Planning Your Initial Configuration.
- Have both your application server and the PeopleSoft Pure Internet Architecture started. In this chapter, you must modify security options of the designated PeopleSoft user ID that will be used to boot up Process

Scheduler. This requires that the user ID's profile be modified through the User Security component. Please refer to earlier chapters for the details on starting the application server and the PeopleSoft Pure Internet Architecture.

- Refer to the following location for required DB2CLI.INI and registry settings.

See "Creating a Database," Fulfilling PeopleSoft Database Configuration Wizard Prerequisites.

In PeopleSoft PeopleTools 8.50 and later, the configuration and log files for Process Scheduler server domains reside in *PS\_CFG\_HOME*. If you do not set a *PS\_CFG\_HOME* environment variable before beginning the application server configuration, the system installs it in a default location based on the current user's settings, as follows:

```
$HOME/psft/pt/<peopletools_version>
```

See "Preparing for Installation," Defining Installation Locations.

See the product documentation *PeopleTools: System and Server Administration* for more information on the *PS\_CFG\_HOME* environment variable and working with server domain configuration.

## See Also

*PeopleTools: Process Scheduler*

My Oracle Support, Certifications

## Task 15B-1: Setting Up Process Scheduler Security

---

This section discusses:

- Understanding Process Scheduler Security
- Granting Process Scheduler Administrative Rights

### Understanding Process Scheduler Security

This task—in which you set up the PeopleSoft User ID that will be used to boot Process Scheduler server so it has administrative rights to both Process Scheduler and Report Manager—guarantees that security is set up properly within your PeopleSoft database.

You must carry out this task to start Process Scheduler successfully.

### Task 15B-1-1: Granting Process Scheduler Administrative Rights

To grant Process Scheduler administrative rights:

1. Log onto your PeopleSoft database through the PeopleSoft Pure Internet Architecture.
2. Select PeopleTools, Security, User Profiles.
3. Select the User Profiles component. Use the Search dialog to select the PeopleSoft User ID you plan to use to boot the Process Scheduler server.

- Click the Roles tab, click the plus icon to insert a new row, and there enter the *ProcessSchedulerAdmin* role to grant the user ID with administrative rights in the Process Scheduler components.

ORACLE®

Home | Worklist | MultiChannel Console | Add to Favorites | Sign

Favorites | Main Menu > PeopleTools > Security > User Profiles > User Profiles

New Window | Personalize Page | http

General | ID | Roles | Workflow | Audit | Links | User ID Queries

User ID: QEDMO  
Description: QE User

**Dynamic Role Rule**

Execute on Server:

Test Rule(s) Refresh

Execute Rule(s)

[Process Monitor](#)  
[Service Monitor](#)

**User Roles** Personalize | Find | View All | First 2-11 of 18 Last

| Role Name                | Description                 | Dynamic                  | View Definition                                                   |
|--------------------------|-----------------------------|--------------------------|-------------------------------------------------------------------|
| PTF Administrator        | PTF Administrator           | <input type="checkbox"/> | <a href="#">Route Control</a> <a href="#">View Definition</a> + - |
| PeopleSoft Administrator | PeopleSoft Admin Privileges | <input type="checkbox"/> | <a href="#">Route Control</a> <a href="#">View Definition</a> + - |
| PeopleSoft User          | PeopleSoft User             | <input type="checkbox"/> | <a href="#">Route Control</a> <a href="#">View Definition</a> + - |
| Portal Administrator     | Portal Administrator        | <input type="checkbox"/> | <a href="#">Route Control</a> <a href="#">View Definition</a> + - |
| Portal Manager           | Portal Manager              | <input type="checkbox"/> | <a href="#">Route Control</a> <a href="#">View Definition</a> + - |
| ProcessSchedulerAdmin    | Process Scheduler Admin     | <input type="checkbox"/> | <a href="#">Route Control</a> <a href="#">View Definition</a> + - |
| QE Role                  | QE Role                     | <input type="checkbox"/> | <a href="#">Route Control</a> <a href="#">View Definition</a> + - |
| Search Administrator     | Search Administrator        | <input type="checkbox"/> | <a href="#">Route Control</a> <a href="#">View Definition</a> + - |
| Search Developer         | Search Developer            | <input type="checkbox"/> | <a href="#">Route Control</a> <a href="#">View Definition</a> + - |
| ReportDistAdmin          | Report Distribution Admin   | <input type="checkbox"/> | <a href="#">Route Control</a> <a href="#">View Definition</a> + - |

Save Return to Search Previous in List Next in List Add Update/Display

General | ID | Roles | Workflow | Audit | Links | User ID Queries

Process Scheduler window: Roles tab

- Repeat the instructions in step 4 to add the role *ReportDistAdmin*.  
This will grant the user ID administrative rights to the Report Manager component. Carry out this step only if the same user is also responsible for maintaining the content of Report Manager.
- Click Save to save your changes.
- Select the General tab and jot down the Permission List name assigned to the Process Profile field.
- From the Portal menu, choose PeopleTools, Security, Permissions & Roles, Permission Lists.
- In the Search dialog, enter the Permission List you noted in step 7.
- Select the Can Start Application Server check box.
- Click Save to save your changes.

## Task 15B-2: Setting Up Process Scheduler to Transfer Reports and Logs to the Report Repository

This section discusses:

- Understanding Report Distribution

- Setting Up Single Signon to Navigate from PIA to Report Repository
- Determining the Transfer Protocol
- Starting the Distribution Agent
- Setting Up the Report Repository
- Setting Up the Distribution for Your Process Scheduler Server
- Setting Up Sending and Receiving of Report Folders in the Report Manager

## Understanding Report Distribution

The PeopleSoft PeopleTools Report Distribution lets you access reports and log files generated from process requests run by a Process Scheduler Server Agent. Using the PeopleSoft Pure Internet Architecture, you can view reports and log files from the web browser through the Report Manager or Process Monitor Detail page. Report Distribution enables you to restrict access to these reports to authorized users based either on user ID or role ID.

This product also includes the Distribution Agent component, which runs on the same server as the Process Scheduler Server Agent. The Distribution Agent, a process that runs concurrently with the Process Scheduler Server Agent, transfers to the Report Repository files generated by process requests initiated by the Process Scheduler Server Agent.

The Distribution Agent transfers files to the Report Repository when one of these criteria is true:

- The Process Scheduler Server Agent is set up in the *Server Definition* to transfer all log files to the Report Repository.
- The process request output destination type is *Web/Window*.

In either case, the Process Scheduler Server Agent inserts a row in the Report List table (PS\_CDM\_LIST). The server agent then updates the distribution status for a process request to *Posting* upon completion of the program associated with the process request. The distribution status of *Posting* signals that the files for the process request are ready for transfer to the Report Repository. The Distribution Agent is notified by Process Scheduler for any process requests that are ready for transferring. As part of the process to transfer files to the Report Repository, the Distribution Agent performs the following steps:

- *Transfer files to the Report Repository.* All the report and log files are transferred to the Report Repository. For each process request transferred, a directory is created in the Report Repository using the following format: \<database name\<date yyyymmdd>\<report id>. All the files for a process request are stored in this directory.
- *Delete the directory from the Process Scheduler Agent's Log/Output directory.* When the output destination type specified for a process request is *Web/Window*, all the files and directory associated with the process request are deleted from the Process Scheduler Log/Output directory after the files are transferred to the Report Repository.

The following diagram illustrates the Process Scheduler and Report Repository architecture. The diagram includes the following items:


- The web browser gives access to the Process Request dialog and the Report or Log Viewer.
- The Report Repository is part of the PeopleSoft Pure Internet Architecture.

---

**Note.** The PeopleSoft Pure Internet Architecture must be installed for Process Scheduler to be able to transfer reports to the Report Repository.

---

- The Process Scheduler Server includes the Process Scheduler Server Agent and the Distribution Agent.
- The transfer protocol between Process Scheduler and the Report Repository may be FTP/FTPS, HTTP/HTTPS, or SFTP.



Process Scheduler and Report Repository Architecture

Before users can view a report, they are authenticated against the PeopleSoft database.

You should set up single signon if you do not want users to have to log on an additional time to view reports in the Report Repository. For the details on setting up single signon, consult the security documentation.

See *PeopleTools: Security Administration*.

## Task 15B-2-1: Setting Up Single Signon to Navigate from PIA to Report Repository

To view reports (log files or system files) from Report Repository, you need to pass the authentication. Report Repository should be treated as a separate PeopleSoft application. To navigate from PeopleSoft Pure Internet Architecture (PIA) to Report Repository, you need to set up single signon to avoid getting a prompt for a second signon. This section includes some considerations for setting up single signon to navigate from PIA to Report Repository.

If Report Repository resides on the same web server as PIA, make sure your Local Message Node is set up to be a "trusted" node for single signon for your system.

If Report Repository resides on a different web server than PIA, do the following:

- Make sure your Local Message Node is set up to be a "trusted" node for single signon for your system.
- Use a fully qualified domain name when addressing the web server for both PIA and Report Repository. For example, enter `http://<machineName>.peoplesoft.com/<site_name>/signon.html` instead of `http://<machineName>/<site_name>/signon.html`.
- Specify the Authentication Domain for your application during installation. If you have multiple applications, and you want them to employ single signon, it is important to specify the same Authentication Domain for all applications.

See the information on implementing single signon in the *PeopleTools: Security Administration* product documentation.

- Set up single signon with a password, like this:
  - Choose PeopleTools, Integration Broker, Integration Setup, Nodes.
  - Click Search and then select the node marked as Default Local Node.
  - Select *Password* for the Authentication Option.
  - Enter a password of your choice.
  - Enter the password again in the Confirm Password field.
  - Enter the user ID for which you are setting up single signon in the Default User ID field.
  - Save the Node Definition.
  - Sign out from the PeopleSoft application.
  - Reboot your application server.

### See Also

*PeopleTools: Security Administration*

## Task 15B-2-2: Determining the Transfer Protocol

*We recommend using HTTP as your transfer protocol.*

Before transferring the files to the Report Repository, you need to determine which transfer protocol to use. If you have a Microsoft Windows Process Scheduler and a Microsoft Windows web server, you can use either an XCOPY, FTP/FTPS, SFTP, or HTTP/HTTPS protocol. (If FTP information is not specified, Process Scheduler will perform an XCOPY.) If you have a PeopleSoft Process Scheduler on Microsoft Windows and a UNIX web server, you can use FTP/FTPS, SFTP, or HTTP/HTTPS. If you have a PeopleSoft Process Scheduler on UNIX, you can use FTP/FTPS, SFTP, or HTTP/HTTPS.

---

**Note.** If you are using FTP/FTPS or SFTP, the corresponding daemon must be set up in your web server.

---

---

**Note.** JRE is installed automatically on your Process Scheduler server.

---

## Task 15B-2-3: Starting the Distribution Agent

The Distribution Agent is automatically started as another Oracle Tuxedo server when a Process Scheduler Server is booted. If a Process Scheduler Server was set up without specifying a Distribution Node in the *Server Definition* page, the Process Scheduler server will have a status in Process Monitor of "Running with No Report Node." After a node is defined for the Process Scheduler server, in the next cycle the Process Scheduler server checks the state of the system, and the Distribution Agent dynamically sets up its environment.

## Task 15B-2-4: Setting Up the Report Repository

This section discusses:

- Defining ReportRepositoryPath
- Defining the Report Node to Use HTTP/HTTPS
- Defining the Report Node to Use FTP
- Defining the Report Node to Use FTPS
- Defining the Report Node to Use SFTP

### Defining ReportRepositoryPath

The ReportRepositoryPath specifies the location of a directory for the Report Repository. You can specify the location for the Report Repository Path on the General page of the Web Profile during installation. If you do not set the location in the Web Profile, the location given by ReportRepositoryPath in the configuration.properties file is used for the default location. Note that the value entered for Report Repository Path in the Web Profile overrides any entry in the configuration.properties file.

See *PeopleTools: Portal Technology*, "Configuring Web Profiles."

Use the following formats to enter the name for the directory that you want to use for the ReportRepositoryPath. The examples below give the default values. Note that you must use a forward slash ("/") in both cases:

- *Microsoft Windows*: ReportRepositoryPath=c:/psreports
- *UNIX*: ReportRepositoryPath=<user\_home>/PeopleSoft Internet Architecture/psreports

For <user\_home> substitute the home directory for the current user.

### Defining the Report Node to Use HTTP/HTTPS

To define the report node to use HTTP/HTTPS:

1. Select PeopleTools, Process Scheduler, Report Nodes.
2. Select the Add a New Value link and enter the Report node name.

- On the Report Node Definition page, select HTTP or HTTPS from the Protocol drop-down list.

Select the HTTP option if you are *not* using SSL. Select the HTTPS option if you are using SSL. The pages for HTTP and HTTPS have the same fields. These examples show HTTP.

Note that if you are using SSL you need to have Client Certificates installed on your web server.

The screenshot shows the 'Report Node Definition' page in the Oracle PeopleTools interface. The breadcrumb trail at the top indicates the path: Favorites > Main Menu > PeopleTools > Process Scheduler > Report Nodes. The page title is 'Report Node Definition'. The 'Node Name' is set to 'HTTP'. The '\*Protocol' dropdown is also set to 'HTTP', with a 'Validate' button to its right. Below this is the 'Distribution Node Details' section, which includes a 'URLID' field with a placeholder 'http://<machine\_name>:<port\_number>/psreports/<site\_name>', a 'Description' field, and an 'Operating System' dropdown set to 'UNIX'. The 'Login Details' section has 'Login ID', 'Password', and 'Confirm Password' fields. The 'URL Details' section includes 'URI Host' (placeholder '<machine\_name>'), 'URI Port' (set to '80'), and 'URI Resource' (placeholder 'SchedulerTransfer/<site\_name>'). At the bottom, there are buttons for 'Save', 'Return to Search', 'Notify', and 'Refresh'.

Report Node Definition page for the HTTP protocol

- Enter the following information in the Distribution Node Details area:

- URLID:** Enter the URL of the web server using the following format:

`http://<machine_name>:<port_number>/psreports/<site_name>`

Replace `<machine_name>` with the name of your machine. Use the fully qualified host name for your web server. If you are using an HTTP or HTTPS port other than the defaults, you need to specify the port number.

**Note.** If you specify the Authentication Token Domain name during the PIA installation, you must include a fully qualified domain name for the URL instead of the IP address.

- Description:** Enter a description of the server (optional).
- Operating System:** Select the web server operating system, Windows or UNIX.

- Enter the following information in the Login Details area:



- *Login ID*: Enter the Login ID. This is not required, unless basic authentication has been set up on the web server by the Web Administrator.
- *Password and Confirm Password*: Enter the password, and confirm it, for the user ID specified in the Login ID field. This is not required, unless basic authentication has been set up on the web server by the Web Administrator.

---

**Note.** The setup of authentication is optional, but is recommended for security of the Report Repository when using the HTTP to transfer files. For information on setting up authentication on the web server where the Report Repository resides, refer to the *PeopleTools: Security Administration* product documentation.

---

6. Enter the following information in the URI Details area:

- *URI Host*: Enter the machine name for the report repository.

---

**Note.** In a basic setup, the machine name for the report repository will match the machine name of the web server URL. However, under certain circumstances—for example, if you are using a reverse proxy server—the URL and URI Host may have different machine names.

---

- *URI Port*: Enter the port number, which must match the port number of your web server (defaults are HTTP = 80, HTTPS = 443). If you change a port number you will lose the default values for both protocols.
- *URI Resource*: Enter SchedulerTransfer/<site name>.

7. Click Save to save your entries.

8. Click Validate to confirm that your entries are complete and correct.

The validation confirms that the necessary parameters are present and correct, and simulates a file transfer with the entered information. You either see a message that confirms the success of the validation, or a message that displays an error for missing parameters or an unsuccessful transfer simulation.

9. To add additional report nodes, click Add to return to the Search page.

## Defining the Report Node to Use FTP

If you use the FTP report node protocol, note that:

- If your FTP server is a Microsoft Windows server, you may have to set up the FTP service.
- The Distribution Agent will perform a validation after FTP has transferred files into the Report Repository by sending a query request to the web server. For this task to be completed, it is critical that the value entered in the URL is accurate. Verify that the machine name, port number, and site number that you specify are correct.

If this setup is not completed, the process request will get a status of NOT POSTED in the Process Monitor Detail page and will log the message "Unable to verify files posted."

To define the report node to use FTP:

1. Select PeopleTools, Process Scheduler, Report Nodes.
2. Select Add a New Value, enter the Report node name, and click Add.

3. On the Report Node Definition page, select FTP from the Protocol drop-down list.

**Report Node Definition**

Node Name: FTP

\*Protocol: FTP Validate

**Distribution Node Details**

URLID: http://<machine\_name>:<port\_number>/psreports/<site\_name>

Description: FTP sample

Operating System: UNIX

**Login Details**

Login ID: <user\_id>

Password: ..... Confirm Password: .....

**File Transfer Details**

Home Directory: /home/psreports

FTP Address: <machine\_name> SSL Mode: EXPLICIT

**Connection Properties**

| Property Name | Property Value |
|---------------|----------------|
|               |                |

**Password Encryption**

Password: ..... Confirm Password: .....

Encrypt Encrypted Password: .....

Save Return to Search Notify Refresh

Report Node Definition page for the FTP protocol

4. In the Distribution Node Details area, enter the following information:

- **URLID:** Enter the URL of the web server using this format:

`http://<machine_name>:<port_number>/psreports/<site_name>`

Replace *<machine name>* with the name of your web server. If you are using an HTTP port other than 80, you need to specify the port number. The variable *<site name>* refers to the directory where you installed the PIA files; this will default to ps for the first installation.

---

**Note.** If you specify the Authentication Token Domain name during the PIA installation, you must include a fully qualified domain name for the URL instead of the IP address.

---

---

**Note.** If you installed the web server software with the default TCP port of 80, you do not need to specify the port number in the URL path. However, if you installed the web server to some other port, you must specify the port number in the URL path.

---

- *Description:* Enter a description of the server (optional).
  - *Operating System:* Select the operating system of the Report Repository, Windows or UNIX.
  - *Network Path:* This information is not required for the FTP protocol
5. In the Login Details area, enter the following information:
- *Login ID:* Enter the FTP User ID.
  - *Password and Confirm Password:* Enter the password, and enter it a second time, for the FTP User ID specified in the Login ID field.
6. In the File Transfer Details area, enter the following information:
- *Home Directory:* Enter the directory specified during the PIA installation as the Report Repository. The FTP User ID must have write access to this directory. Note that this is not a required field for FTP transfer, as the system uses the Report Repository directory specified at install time or the current directory assigned to ReportRepositoryPath in configuration.properties. Note that the value you enter for the Report Repository Path in the Web Profile at install time overrides any entry for ReportRepositoryPath in configuration.properties.  
For UNIX, the default directory is <user\_home>/PeopleSoft Internet Architecture/psreports/.
  - *FTP Address:* Enter the machine name or the IP address of the Report Repository. If the name of the machine is used, it must be included on a DNS server.

7. If you need to specify additional properties, use the Connection Properties area. Specifying the Connection Properties is optional.

Click the lookup button (magnifying glass) and select one of the properties in the following table. Click the plus sign to add another connection property.

| Property Name       | Property Value                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
|---------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ACTIVEMODE          | <p>To enable active mode, add the ACTIVEMODE property to the URL and set it to Y.</p> <p>The default FTP connection mode is extended passive mode.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| ACTIVEPORTOPTION    | <p>This property can be used along with ACTIVEMODE. When active mode is enabled, you can use ACTIVEPORTOPTION to specify the IP address and port on which the FTP server can be accessed. This is useful when the server is behind a firewall. By default, ACTIVEPORTOPTION uses the default IP address of your system. If you want to use a particular IP address, set the ACTIVEPORTOPTION value to either the full IP address, a host name to resolve to an IP address, or a local network interface name.</p> <p>You can also specify a port range. For example:<br/><i>10.176.147.111:10000-13000</i></p> |
| ENABLEEPRPRT        | <p>This option can be used only with Active Mode. If Active Mode is enabled and ENABLEEPRPRT is set to N, then the system will use a PORT (IPv4) Active Mode connection.</p> <p>By default, ENABLEEPRPRT is Y, if Active Mode is set to Y.</p>                                                                                                                                                                                                                                                                                                                                                                 |
| EXTENDEDPASSIVEMODE | <ul style="list-style-type: none"> <li>0: Disable EPSV</li> <li>1: Enable EPSV</li> </ul> <p>This property enables you to control whether extended passive mode (EPSV) will be used by FTP.</p> <p>EPSV is used by default. That is, by default, this value is considered to be 1.</p> <p>If the client fails to connect to the server with EPSV, then the system will try passive mode (PASV). To use PASV only, add EXTENDEDPASSIVEMODE to the URL Properties and set it to 0.</p>                                                                                                                           |
| JKSPASSWORD         | Specify the Java keystore (JKS) password.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| JKSPATH             | Specify the Java keystore (JKS) path.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| PASSWORD            | Specify the password associated with the USER property, which identifies the FTP User ID.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| USER                | Specify the FTP User ID used for authentication when accessing the FTP site.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |

8. If you need to specify an encrypted password in any of the property fields, use the Password Encryption area to generate the encrypted password, as follows:
  - a. In the Password field, enter a password.
  - b. In the Confirm Password field, enter the password again.
  - c. Click Encrypt.  
The encrypted password is displayed in the Encrypted Password field.
  - d. From the Encrypted Password field, cut the encrypted password and then copy the encrypted value to the appropriate location.
9. Select Save to save your entries.
10. Click Validate to confirm that your entries are correct.  
The validation confirms that the necessary parameters are present and correct, and simulates a file transfer with the entered information. You either see a message that confirms the success of the validation, or a message that displays an error for missing parameters or an unsuccessful transfer simulation.
11. To add additional report nodes, click Add to return to the Search page.

## Defining the Report Node to Use FTPS

To define the report node to use FTPS:

1. Select PeopleTools, Process Scheduler, Report Nodes.
2. Select Add a New Value, enter the Report node name, and click Add.

3. On the Report Node Definition page, select FTPS from the Protocol drop-down list.

The screenshot shows the Oracle Report Node Definition page for the FTPS protocol. The page is titled "Report Node Definition" and includes a navigation bar with "Favorites", "Main Menu", "PeopleTools", "Process Scheduler", and "Report Nodes". The Oracle logo is visible in the top left. The page contains several sections for configuring the report node:

- Node Name:** FTPS
- \*Protocol:** FTPS (selected from a dropdown menu)
- Validate:** A button to validate the configuration.
- Distribution Node Details:**
  - URLID:** `http://<machine_name>:<port_number>/psreports/<site_name>`
  - Description:** FTPS sample
  - Operating System:** UNIX (selected from a dropdown menu)
  - Network Path:** (empty text field)
- Login Details:**
  - Login ID:** `<user_id>`
  - Password:** (masked with dots)
  - Confirm Password:** (masked with dots)
- File Transfer Details:**
  - Home Directory:** `/home/psreports`
  - FTP Address:** `<machine_name>`
  - SSL Mode:** EXPLICIT (selected from a dropdown menu)
- Connection Properties:**
  - Property Name:** (empty text field)
  - Property Value:** (empty text field)
  - Buttons:** +, -
- Password Encryption:**
  - Password:** (empty text field)
  - Confirm Password:** (empty text field)
  - Encrypt:** A button to encrypt the password.
  - Encrypted Password:** (empty text field)

At the bottom of the page, there are buttons for "Save", "Notify", and "Refresh".

Report Node Definition page for the FTPS protocol

4. In the Distribution Node Details area, enter the following information:

- **URLID:** Enter the URL of the web server using this format:

`http://<machine_name>:<port_number>/psreports/<site_name>`

Replace `<machine name>` with the name of your web server. If you are using an HTTP port other than 80, you need to specify the port number. The variable `<site name>` refers to the directory where you installed the PIA files; this will default to `ps` for the first installation.

---

**Note.** If you specify the Authentication Token Domain name during the PIA installation, you must include a fully qualified domain name for the URL instead of the IP address.

---



---

**Note.** If you installed the web server software with the default TCP port of 80, you do not need to specify the port number in the URL path. However, if you installed the web server to some other port, you must specify the port number in the URL path.

---

- *Description:* Enter a description of the server (optional).
  - *Operating System:* Select the operating system of the Report Repository, Windows or UNIX.
  - *Network Path:* This information is not required for the FTPS protocol.
5. In the Login Details area, enter the following information:
- *Login ID:* Enter the FTP User ID.
  - *Password and Confirm Password:* Enter the password, and enter it a second time, for the user ID specified in the Login ID field.
6. In the File Transfer Details area, enter the following information:
- *Home Directory:* Enter the directory specified during the PIA installation as the Report Repository. The FTP User ID must have write access to this directory. Note that this is not a required field for FTP transfer, as the system uses the Report Repository directory specified at install time or the current directory assigned to ReportRepositoryPath in configuration.properties. Note that the value you enter for the Report Repository Path in the Web Profile at install time overrides any entry for ReportRepositoryPath in configuration.properties.

For UNIX, the default directory is <user\_home>/PeopleSoft Internet Architecture/psreports/.

- *FTP Address:* Enter the machine name or the IP address of the Report Repository. If the name of the machine is used, it must be included on a DNS server.
- *SSL Mode:* Select Explicit or Implicit from the drop-down list.

These are two separate methods developed to invoke the client security for use with FTP clients. With the explicit mode, FTPS-aware clients can invoke security with an FTPS-aware server without breaking overall FTP functionality with non-FTPS-aware clients. The implicit method requires that all clients of the FTPS server be aware that SSL is to be used on the session, and thus is incompatible with non-FTPS-aware clients.

7. In the Connection Properties area, click the lookup button (magnifying glass) and select one of the properties in the following table:

Click the plus sign to add another connection property.

| Property Name       | Property Value                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
|---------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ACTIVEMODE          | <p>To enable active mode, add the ACTIVEMODE property to the URL and set it to Y.</p> <p>The default FTPS connection mode is extended passive mode.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| ACTIVEPORTOPTION    | <p>This property can be used along with ACTIVEMODE. When active mode is enabled, you can use ACTIVEPORTOPTION to specify the IP address and port on which the FTP server can be accessed. This is useful when the server is behind a firewall. By default, ACTIVEPORTOPTION uses the default IP address of your system. If you want to use a particular IP address, set the ACTIVEPORTOPTION value to either the full IP address, a host name to resolve to an IP address, or a local network interface name.</p> <p>You can also specify a port range. For example:<br/><i>10.176.147.111:10000-13000</i></p> |
| CERTALIAS           | <p>Certificate Alias: The Certificate Alias must be an alias name of a certificate stored in the database (using the PeopleSoft PeopleTools Digital Certificates page).</p> <p><b>Note.</b> Currently, only PEM certificates are supported for FTPS.</p>                                                                                                                                                                                                                                                                                                                                                       |
| ENABLEEPRPRT        | <p>This option can be used only with Active Mode. If Active Mode is enabled and ENABLEEPRPRT is set to N, then the system will use a PORT (IPv4) Active Mode connection.</p> <p>By default, ENABLEEPRPRT is Y, if Active Mode is set to Y.</p>                                                                                                                                                                                                                                                                                                                                                                 |
| EXTENDEDPASSIVEMODE | <ul style="list-style-type: none"> <li>0: Disable EPSV</li> <li>1: Enable EPSV</li> </ul> <p>This property enables you to control whether extended passive mode (EPSV) will be used by FTP.</p> <p>EPSV is used by default. That is, by default, this value is considered to be 1.</p> <p>If the client fails to connect to the server with EPSV, then the system will try passive mode (PASV). To use PASV only, add EXTENDEDPASSIVEMODE to the URL Properties and set it to 0.</p>                                                                                                                           |
| JKSPASSWORD         | Specify the Java keystore (JKS) password.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| JKSPATH             | Specify the Java keystore (JKS) user.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |



| Property Name    | Property Value                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
|------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| KEYSTOREPASSWORD | <p>This property is required for FTPS and HTTPS repositories. For attachments transferred from the PeopleSoft system to the FTPS or HTTPS repository, the system retrieves the key pair for the client certificate from the digital certificate store and writes the pair to a file in PKCS12 format with password protection. The value of this property will be used as the password for the PKCS12 file.</p> <p>The PKCS12 file enables connection and file transfer, and it exists only temporarily in &lt;PS_SERVDIR&gt;\files\&lt;CERT ALIAS NAME&gt; for the duration of the file transfer. The system deletes the file after the file transfer transaction.</p> <p><b>Note.</b> If the system fails to delete the certificate alias file, a message will be written to the application server log. The maximum number of files that can exist at any time is equal to the total number of FTPS and HTTPS URL identifiers defined in the system.</p> <p>For information on setting the PS_SERVDIR environment variable, see the <i>PeopleTools: Integration Broker</i> product documentation.</p> |
| PASSWORD         | Specify the password associated with the USER property, which identifies the FTP User ID.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| SSLUAGELLEVEL    | <ul style="list-style-type: none"> <li>• <i>0 - No SSL:</i> No SSL will be used.</li> <li>• <i>1 - Try SSL:</i> Try using SSL, but proceed as normal otherwise.</li> <li>• <i>2 - Control:</i> Require SSL for the control connection.</li> <li>• <i>3 - SSL Only:</i> (Default) Require SSL for all communication.</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| USER             | Specify the FTP User ID used for authentication when accessing the FTP site.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| VERIFYHOST       | <ul style="list-style-type: none"> <li>• <i>0:</i> Do not verify the server for host name.</li> <li>• <i>1:</i> Check if there exists any value in the common name field in the server certificate. This check does not verify if it matches with what the client specifies.</li> <li>• <i>2:</i> (Default) Check for a match with the host name in the URL with the common name or Subject Alternate field in the server certificate.</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| VERIFYPEER       | <ul style="list-style-type: none"> <li>• <i>False:</i> Do not verify the peer.</li> <li>• <i>True:</i> (Default) Verify the peer by authenticating the certificate sent by the server.</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |

8. If you need to specify an encrypted password in any of the property fields, use the Password Encryption area to generate the encrypted password, as follows:

- a. In the Password field, enter a password.
- b. In the Confirm Password field, enter the password again.
- c. Click Encrypt.

The encrypted password is displayed in the Encrypted Password field.

- d. From the Encrypted Password field, cut the encrypted password and then copy the encrypted value to the appropriate location.
9. Select Save to save your entries.
  10. Click Validate to confirm that your entries are correct.

The validation confirms that the necessary parameters are present and correct, and simulates a file transfer with the entered information. You either see a message that confirms the success of the validation, or a message that displays an error for missing parameters or an unsuccessful transfer simulation.

11. To add additional report nodes, click Add to return to the Search page.

## Defining the Report Node to Use SFTP

To define the report node to use SFTP:

1. Select PeopleTools, Process Scheduler, Report Nodes.
2. Select Add a New Value, enter the Report node name, and click Add.

- On the Report Node Definition page, select SFTP from the Protocol drop-down list.

The screenshot shows the Oracle Report Node Definition page for the SFTP protocol. The page is divided into several sections:

- Node Name:** SFTP
- \*Protocol:** SFTP (dropdown menu)
- Validate:** Button
- Distribution Node Details:**
  - URLID:** `http://<machine_name>:<port_number>/psreports/<site_name>`
  - Description:** SFTP sample
  - Operating System:** UNIX (dropdown menu)
- Login Details:**
  - Login ID:** <user\_id>
  - Password:** [Masked]
  - Confirm Password:** [Masked]
- File Transfer Details:**
  - Home Directory:** /home/psreports
  - FTP Address:** <machine\_name>
- Connection Properties:**

| Property Name | Property Value |   |   |
|---------------|----------------|---|---|
|               |                | + | - |
- Password Encryption:**
  - Password:** [Masked]
  - Confirm Password:** [Masked]
  - Encrypt:** Button
  - Encrypted Password:** [Masked]

At the bottom of the page, there are buttons for **Save**, **Notify**, and **Refresh**.

Report Node Definition page for the SFTP protocol

- In the Distribution Node Details area, enter the following information:
  - URLID:** Enter the URL of the web server using this format:  
`http://<machine_name>:<port_number>/psreports/<site_name>`

Replace *<machine name>* with the name of your web server. If you are using an HTTP port other than 80, you need to specify the port number. The variable *<site name>* refers to the directory where you installed the PIA files; this will default to ps for the first installation.

---

**Note.** If you specify the Authentication Token Domain name during the PIA installation, you must include a fully qualified domain name for the URL instead of the IP address.

---

---

**Note.** If you installed the web server software with the default TCP port of 80, you do not need to specify the port number in the URL path. However, if you installed the web server to some other port, you must specify the port number in the URL path.

---

- *Description:* Enter a description of the server (optional).
  - *Operating System:* Select the operating system of the Report Repository, Windows or UNIX.
  - *Network Path:* This information is not required for the SFTP protocol.
5. In the Login Details area, enter the following information:
- *Login ID:* Enter the FTP User ID.
  - *Password and Confirm Password:* Enter the password, and enter it a second time, for the user ID specified in the Login ID field.
6. In the File Transfer Details area, enter the following information:
- *Home Directory:* Enter the directory specified during the PIA installation as the Report Repository. The FTP User ID must have write access to this directory. Note that this is not a required field for FTP transfer, as the system uses the Report Repository directory specified at install time or the current directory assigned to ReportRepositoryPath in configuration.properties. Note that the value you enter for the Report Repository Path in the Web Profile at install time overrides any entry for ReportRepositoryPath in configuration.properties.  
For UNIX, the default directory is <user\_home>/PeopleSoft Internet Architecture/psreports/.
  - *FTP Address:* Enter the machine name or the IP address of the Report Repository. If the name of the machine is used, it must be included on a DNS server.

7. In the Connection Properties area, click the lookup button (magnifying glass) and select one of the properties in the following table.

Click the plus sign to add additional connection properties.

| Property Name | Property Value                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
|---------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| AUTHTYPE      | Select one of the following the authentication types: <ul style="list-style-type: none"> <li>• <i>PUBLICKEY</i></li> <li>• <i>PASSWORD</i></li> <li>• <i>ANY</i></li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| PASSWORD      | Specify the user password. You can enter the password in the Password Encryption box, click Encrypt, and then copy the encrypted value to the Password property.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| PASSWORDKEY   | Enter the password for the private key.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| PRIVATEKEY    | Select the private key.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| PUBLICKEY     | Select the public key.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| SSHKEYALIAS   | <p>Select the SSH certificate saved to the database using the PeopleTools Security, Digital Certificates page (select PeopleTools, Security, Security Objects, Digital Certificates). The SSH certificate added through the Digital Certificates page contains both the public and private key data, identified by the Alias column value on the Digital Certificates page.</p> <p>If using the SSHKEYALIAS URL property, the Property Value prompt displays only the list of SSH certificates that have been added to the Digital Certificates page. If you have added the SSH certificate using the Digital Certificates page, and you have assigned an SSH certificate to the SSHKEYALIAS URL property, the system ignores the PUBLICKEY and PRIVATEKEY properties, regardless of whether they refer to valid key files in the file system.</p> <p>If you provided a password (or passphrase) when generating your SSH certificate, specify that value using the PASSWORDKEY URL property.</p> <p>See <i>PeopleTools: Security Administration</i>, "Configuring Digital Certificates."</p> |
| USER          | Specify the user ID to be authenticated.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |

8. If you need to specify an encrypted password in any of the property fields, use the Password Encryption area to generate the encrypted password, as follows:
- In the Password field, enter a password.
  - In the Confirm Password field, enter the password again.
  - Click Encrypt.

The encrypted password is displayed in the Encrypted Password field.

- d. From the Encrypted Password field, cut the encrypted password and then copy the encrypted value to the appropriate location.
9. Select Save to save your entries.
10. Click Validate to confirm that your entries are correct.

The validation confirms that the necessary parameters are present and correct, and simulates a file transfer with the entered information. You either see a message that confirms the success of the validation, or a message that displays an error for missing parameters or an unsuccessful transfer simulation.

11. To add additional report nodes, click Add to return to the Search page.

## Task 15B-2-5: Setting Up the Distribution for Your Process Scheduler Server

To set up the Distribution Settings for your Process Scheduler Server:

1. Select PeopleTools, Process Scheduler, Servers.
2. Enter the Server Name (such as PSUNIX). The Server Definition page appears.
3. Select the Distribution tab.

The screenshot shows the Oracle PeopleTools interface. The breadcrumb trail at the top reads: Favorites > Main Menu > PeopleTools > Process Scheduler > Servers. The Oracle logo is on the left, and a search bar is in the center. On the right, there are links for 'Advanced Search' and 'Last Search Results'. Below the breadcrumb trail, there are tabs for 'Server Definition', 'Distribution' (which is selected), 'Operation', 'Notification', and 'Daemon'. The 'Server Name' is set to 'PSUNIX'. The 'Server Distribution Details' section contains the following fields: 'Distribution Node Name' with a lookup button, 'Maximum Transfer Retries' with a text input, 'Interval for Transfer Attempt' with a text input and 'seconds' label, and 'Transfer System Files to Report Repository' with a checkbox. At the bottom, there are buttons for 'Save', 'Return to Search', 'Notify', 'Add', and 'Update/Display'. A footer bar contains links for 'Server Definition', 'Distribution', 'Operation', 'Notification', and 'Daemon'.

Server Definition page for PSUNIX: Distribution tab

4. Click the lookup button for Distribution Node Name to display the report node names and select the name of the required report node.
5. Enter a number for the Maximum Transfer Retries. This is the maximum number of times the server can try to send a report before it errors out.
6. Enter the number of seconds for the Interval for Transfer Attempt field. This is the interval between attempts to send the report.

7. Select the check box Transfer Log Files to Report Repository if you want to transfer all log and trace files from processes that do not generate reports.
8. Click Save to save your entries.
9. If Process Scheduler is running, you must reboot for any new settings to take effect.

To view reports (log files or system files) from Report Repository, you need to pass the authentication. Report Repository should be treated as a separate PeopleSoft application. To navigate from PIA to Report Repository, you need to set up single signon in order to avoid getting a prompt for a second signon.

## Task 15B-2-6: Setting Up Sending and Receiving of Report Folders in the Report Manager

To be able to view reports in the Report Manager Explorer and List pages, you need to set up the sending and receiving of report folders in the Report Manager by activating the domain on which a sending and receiving server resides. Consult the documentation covering the PeopleSoft Integration Broker to learn how to activate the sending and receiving server domain.

See *PeopleTools: Integration Broker*.

See *PeopleTools: Integration Broker Service Operations Monitor*.

## Task 15B-3: Setting Up Process Scheduler Server Agent

---

This section discusses:

- Understanding Process Scheduler Server Agent
- Changing the Default Operating System
- Setting Up Your Environment
- Creating and Configuring a Process Scheduler Server
- Reconfiguring a Process Scheduler Server
- Verifying the Process Scheduler Server Status

### Understanding Process Scheduler Server Agent

For installation purposes, you can use predefined server names and other definitions. The predefined name that you might use is as follows:

| Server Name | Operating System |
|-------------|------------------|
| PSUNIX      | UNIX             |

To test this, use processes already defined in your PeopleSoft database. To set up a new server definition in your PeopleSoft database, refer to the *PeopleTools: Process Scheduler* product documentation.

**Note.** When creating multiple Process Scheduler Servers for the same database, each server must have a unique server name. For example, two Process Scheduler Servers, both named PSNT, cannot run against the same database.

---

## Task 15B-3-1: Changing the Default Operating System

By default, Process Scheduler is set up to run a process request from a Process Scheduler Server Agent started in a Microsoft Windows server when the value of the *ServerName* field in the Process Request Dialog page is left blank. If you plan to run all processes other than Microsoft Windows-based programs (such as nVision) from UNIX, you must change the default operating system.

---

**Note.** If you do not change the default operating system from Windows to UNIX and you do not plan to set up a Process Scheduler Server Agent in Microsoft Windows, process requests that are created will be directed to a Microsoft Windows-based operating system and will remain in the "Queued" status.

---

To change the default operating system for process requests that were not assigned a Process Scheduler Server Name:

1. Select PeopleTools, Process Scheduler, System Settings.
2. Under *Primary Operating System*, choose *UNIX* from the drop-down list.
3. Click on the *System Purge Options* tab. Enter the date for the next purge of process requests in the *Next Purge Date* field.
4. Enter the time for the next purge of process requests in the *Next Purge Time* field. The default time is 12:00:00AM.
5. Enter a *Recurrence* if you want to set a regular purging basis.
6. Choose *Save*.

## Task 15B-3-2: Setting Up Your Environment

Telnet to your UNIX system. Log in and ensure the following environment variables are set appropriately:

---

**Note.** The environment variables for Tuxedo must be set explicitly; they are not set by running `psconfig.sh`. These can be also set using the `.profile` file in the user's home directory.

---

- `$TUXDIR` must be set to the correct Oracle Tuxedo installation directory; for example:  
`TUXDIR=/home/user/Oracle/tuxedo12cR1; export TUXDIR`
- `$TUXDIR/lib` must be prepended to `LD_LIBRARY_PATH`, `LIBPATH`, or `SHLIB_PATH`, whichever is appropriate for your platform; for example:  
`LD_LIBRARY_PATH=$TUXDIR/lib:$LD_LIBRARY_PATH; export LD_LIBRARY_PATH`
- `$TUXDIR/bin` must be prepended to `PATH`; for example:  
`PATH=$TUXDIR/bin:$PATH; export PATH`

Alternatively, make sure the following environment variables are set in the profile file in the user's home directory:

If your application does not contain COBOL programs, you do not need to set the `$COBDIR` environment variables.

See "Preparing for Installation," Installing Supporting Applications.

- `$COBDIR` must be set to the Micro Focus Server Express installation; for example:  
`COBDIR=/cobol/prod/svrexpress-5.1_wp6; export COBDIR`
- `$COBDIR/lib` must be appended to `LD_LIBRARY_PATH`, `LIBPATH`, or `SHLIB_PATH`, whichever is



appropriate for your platform.

```
LD_LIBRARY_PATH=$LD_LIBRARY_PATH:$COBDIR/lib; export LD_LIBRARY_PATH
LIBPATH=$LIBPATH:$COBDIR/lib; export LIBPATH
SHLIB_PATH=$SHLIB_PATH:$COBDIR/lib; export SHLIB_PATH
```

- \$COBDIR/bin must be appended to the PATH; for example:

```
PATH=$PATH:$COBDIR/bin;export PATH
```

For required DB2CLI.INI and registry settings, consult the following.

See "Creating a Database," Fulfilling PeopleSoft Database Configuration Wizard Prerequisites.

To set the required DB2/LUW environment, run db2profile. Enter the following command:

```
cd <DB2_INSTANCE_DIRECTORY>/sqlllib
. ./db2profile
```

To set the required PeopleSoft environment variables, run psconfig.sh. Go to the *PS\_HOME* directory and enter the following command:

```
. ./psconfig.sh
```

---

**Note.** After running psconfig.sh, you can invoke the PSADMIN utility from any location.

---

## Task 15B-3-3: Creating and Configuring a Process Scheduler Server

This section describes how to create and configure a Process Scheduler server.

You can set Process Scheduler configuration parameters either by using PSADMIN, which provides an interactive dialog, or by editing the configuration file pspcrs.cfg located in the *PS\_CFG\_HOME/appserv/prcs/database name* directory. The following steps assume you are using PSADMIN to specify parameter settings.

---

**Note.** If you use the configuration file pspcrs.cfg, be aware that in the PeopleSoft PeopleTools 8.49 release and later, the section [Output Dest Exceptions] has been modified to trap metastring exceptions not only in the output destination but in other process parameters as well. In this section the entry `OUTDEST_EXCEPT01=%ANYMETASTRING%` has been changed to `PARAMETER_EXCEPT01=%ANYMETASTRING%`.

---

To create and configure a Process Scheduler Server:

1. Run the `psadmin` command.

You see the PeopleSoft Server Administration menu, as in this example:

```

PeopleSoft Server Administration

PS_CONFIG_HOME /home/JSMITH/psft/pt/8.57
PS_HOME /opt/psft/pt/ps_home8.57
PS_APP_HOME /opt/psft/pt/hcm_app_home

1) Application Server
2) Process Scheduler
3) Search Server
4) Web (PIA) Server
5) Switch Config Home
```

- 6) Replicate Config Home
- 7) Refresh Config Home
- q) Quit

Command to execute (1-7 q):

2. Depending on your environment, you may see a message after the menu selection, which indicates that PSADMIN has modified the *PS\_CFG\_HOME*/peopletools.properties file with the current *PS\_HOME* location:

```

PS_CFG_HOME/peopletools.properties file has been updated.
You should use the Config Home Refresh feature in PSAdmin
to ensure that all of your domains are current.
Alternatively, you may recreate all of your domains.
Please press any key to continue...

```

This indicates that one of these situations exists:

- The *PS\_CFG\_HOME* that you are working with was used previously from a different *PS\_HOME*. In this case, you should recreate any existing Application Server, Process Scheduler, Search, or PIA domains in this *PS\_CFG\_HOME*.
- You configured your environment such that *PS\_CFG\_HOME* is the same as *PS\_HOME*. The first time you use PSADMIN to create a domain, it updates the *PS\_CFG\_HOME*/peopletools.properties file. Continue with the next step.

3. Select 2 to access the Process Scheduler submenus.
4. Select 2 for Create a domain from the PeopleSoft Process Scheduler Administration menu.

```

PeopleSoft Process Scheduler Administration

1) Administer a domain
2) Create a domain
3) Delete a domain
4) Import domain configuration

q) Quit
```

Command to execute (1-4, q) : 2

5. Enter the name of the domain at the following prompt, such as HRDMO in this example, and press ENTER:

Please enter name of domain to create : **HRDMO**

6. After the system creates the domain, the Quick-configure menu appears:

```

Quick-configure menu -- domain: HRDMO

 Features Settings
 ===== =====
1) App Engine : Yes 9) DBNAME : [HRDMO]
2) Master Scheduler : Yes 10) DBTYPE : [DB2UNIX]
3) Perf Collator : No 11) PrcsServer : [PSUNIX]
4) Domains Gateway : No 12) UserId : [QEDMO]
```

```

5) Push Notifications: No
13) UserPswd :[]
14) ConnectID :[people]
15) ConnectPswd:[]
16) Log/Output Dir:[%PS_SERVDIR%/log_⇒
output]
/bin]
17) SQRBIN :[%PS_HOME%/bin/sqr/DB2⇒
18) AddToPATH :[%PS_HOME%/cblbin]
19) DomainConnectPswd: []

```

Actions  
=====

- 6) Load config as shown
- 7) Custom configuration
- 8) Edit environment settings
- h) Help for this menu
- q) Return to previous menu

HINT: Enter 9 to edit DBNAME, then 6 to load

Enter selection (1-18, h, or q):

7. If you need to modify any of these settings, enter the number next to the parameter name, type the new value, and press ENTER. This table lists the parameters and gives brief descriptions.

| Parameter                 | Description                                                                                                                                                                                                                                                                                                                                            |
|---------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Master Scheduler          | Select this option to enable the Master Scheduler Server (PSMSTPRC). The default is to enable the server.<br><br><i>See PeopleTools: Process Scheduler.</i>                                                                                                                                                                                            |
| App Engine                | Select this option to initiate Application Engine programs through the AE Tuxedo Server (PSAESRV). The default is set to run AE using PSAESRV.<br><br><i>See PeopleTools: Process Scheduler.</i>                                                                                                                                                       |
| Perf Collator             | Select this option to enable the PSPPMSSRV server process.<br><br><i>See PeopleTools: Performance Monitor, "Enabling the Required Elements on the Monitoring System."</i>                                                                                                                                                                              |
| Domain Gateways           | Select this option to enables inter domain communication, for example between Application Server and Process Scheduler domains.<br><br><i>See PeopleTools: Fluid User Interface Developer's Guide, "Setting Up Push Notification Configurations."</i>                                                                                                  |
| Push Notifications        | Select this option to enables pushing server events from PeopleSoft PeopleTools server runtime, such as Application Server and Process Scheduler, to browser clients and other PeopleSoft PeopleTools server runtime components.<br><br><i>See PeopleTools: Fluid User Interface Developer's Guide, "Setting Up Push Notification Configurations."</i> |
| Load config as shown      | Load the selections you made in the Quick Configure menu.                                                                                                                                                                                                                                                                                              |
| Custom configuration      | Make custom selections in PSADMIN, using options that are not available in the Quick Configure menu.                                                                                                                                                                                                                                                   |
| Edit environment settings | Edit, add, remove, comment out, and review domain-level environment variables.                                                                                                                                                                                                                                                                         |
| DBNAME                    | Specify the database name that is associated with a PeopleSoft Process Scheduler Server Agent, such as HRDMO, FSDMO, SADMO, and so on.                                                                                                                                                                                                                 |
| DBTYPE                    | Specify the database type: DB2UNIX (for DB2 for Linux, UNIX, and Windows).                                                                                                                                                                                                                                                                             |
| PrsServer                 | Specify the process server name. This must match the name defined in the Server Definition table, such as PSNT or PSUNIX.                                                                                                                                                                                                                              |

| Parameter         | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
|-------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| UserId            | Enter the user ID, such as VP1 or PS.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| UserPswd          | Enter the password for the user ID, as you specified during the database configuration.<br><br>The password is hidden by masking characters as you type, in the Quick-configure menu after entry.                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| ConnectID         | Enter the connect ID. This value is required.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| ConnectPswd       | Enter the connect password, as you specified during the database configuration. This value is required.<br><br>The password is hidden by masking characters as you type, in the Quick-configure menu after entry.                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Log/Output Dir    | Specify the directory in which files that are generated by the program are written. When PeopleSoft Process Scheduler initiates a process request, it creates a subdirectory in the format <Process Type ID>_<Program Name>_<Process Instance> that contains the generated files. For instance, the SQR program XRFWIN that ran with process instance 20 has all reports, trace, and log files in the subdirectory SQR_XRFWIN_20. It is also the optional directory used with the Output Destination field when scheduling a request. This variable (%%OutputDirectory%%) can be used in the File/Printer field of the Process Scheduler Request dialog box. |
| SQRBIN            | Enter the path to the SQR executables.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| AddToPATH         | (Optional for Tuxedo) Specify an additional directory that is appended to the PATH environment variable.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| DomainConnectPswd | If you configured your Application Server domain to require a Domain Connection password, enter it here. Otherwise, leave it blank.<br><br>The password is hidden by masking characters as you type, and in the Quick-configure menu after entry.<br><br>See the information on setting Application Server Domain Parameters in the <i>PeopleTools: System and Server Administration</i> product documentation.                                                                                                                                                                                                                                              |

For descriptions of the PSADMIN options that do not appear in the Quick-configure menu, see the information on using PSADMIN in the *PeopleTools: Process Scheduler* product documentation. For a basic installation, in most cases you can accept the defaults.

8. When you have updated the settings as needed, choose *5, Load config as shown*, from the Quick-Configure menu to save your settings to the Process Scheduler configuration file, `pstuxcfg`.
9. To start Process Scheduler, choose *1*, for Administer Domain.
10. On the PeopleSoft Process Scheduler Administration menu, choose *1* for Boot this domain.

```

PeopleSoft Process Scheduler Administration

```

Domain Name: HRDMO

- 1) Boot this domain
- 2) Domain shutdown menu
- 3) Domain status menu
- 4) Configure this domain
- 5) TUXEDO command line (tmadmin)
- 6) Edit configuration/log files menu
- 7) Clean IPC resources of this domain
- q) Quit

Command to execute (1-7, q) :

11. Choose 1, Boot (Serial Boot), or 2, Parallel Boot, from the PeopleSoft Domain Boot Menu.

---

**Note.** The messages you see and the number of processes started will depend on the options you chose during configuration.

---

12. If you want to stop Process Scheduler Server, from the PeopleSoft Domain Administration menu, choose 2, for Domain Shutdown menu, and then enter the number corresponding to the name of the appropriate database.

---

**Note.** If you see the following message, then the server is already down:

```
Command to execute (1-2, q) [q]: 1 Loading command line administration
utility ... tmadmin - Copyright (c) 2007-2008, Oracle. Portions *
Copyright 1986-1997 RSA Data Security, Inc. All Rights Reserved.
Distributed under license by Oracle. Tuxedo is a registered trademark. No
bulletin board exists. Entering boot mode. > TMADMIN_CAT:111: ERROR: No
such command.
```

---

## Task 15B-3-4: Reconfiguring a Process Scheduler Server

If you create and then immediately configure a Process Scheduler server, you can use the Quick-configure menu. Alternatively, you can use PSADMIN as described in this section. Feel free to skip this procedure if you have already created and configured your Process Scheduler Server using the Quick-configure menu and want to move forward with your installation.

---

**Note.** If you want to configure the Process Scheduler Server while it is running, you need to stop and restart the server to load the new settings.

---

To reconfigure a Process Scheduler Server:

1. Run the command:

```
psadmin
```

2. Depending on your environment, you may see a message after the initial menu, which indicates that PSADMIN has modified the *PS\_CFG\_HOME*/peopletools.properties file with the current *PS\_HOME* location:

```

PS_CFG_HOME/peopletools.properties file has been updated.
You should use the Config Home Refresh feature in PSAdmin
to ensure that all of your domains are current.
Alternatively, you may recreate all of your domains.
Please press any key to continue...

```

This indicates that one of these situations exists:

- The *PS\_CFG\_HOME* that you are working with was used previously from a different *PS\_HOME*. In this case, you should recreate any existing Application Server, Process Scheduler, Search, or PIA domains in this *PS\_CFG\_HOME*.
- You configured your environment such that *PS\_CFG\_HOME* is the same as *PS\_HOME*. The first time you use PSADMIN to create a domain, it updates the *PS\_CFG\_HOME/peopletools.properties* file. Continue with the next step.

3. Select 2 for Process Scheduler in the PeopleSoft Server Administration menu.
4. In the PeopleSoft Process Scheduler Administration menu, select 1 for Administer a domain.
5. Select the database for which the Process Scheduler needs to be configured.
6. You see the following prompt:

Do you want to change any config values (y/n)? [n]:

Specify *y* to start an interactive dialog that lets you examine or change parameter values.

7. Specify the configuration parameters one by one.

Configuration parameters are grouped into sections. At each section, you are asked whether to change any parameters—for example:

Values for config section - Startup

```

DBName=
DBType=
UserId=
UserPswd=
ConnectId=
ConnectPswd=
ServerName=
StandbyDBName=
StandbyDBType=
StandbyUserId=
StandbyUserPswd=
InMemoryDBName=
InMemoryDBType=

```

Do you want to change any values (y/n)? [n]:

- Specify *y* to change any parameter values for the current section. You are prompted for each parameter value. Either specify a new value or press ENTER to accept the default. After you press ENTER, you are positioned at the next parameter in that section. When you are done with that section, you are again asked whether you want to re-edit any of the values you changed.
- The parameters *StandbyDBName*, *StandbyDBType*, *StandbyUserID*, and *StandbyUserPswd* are used for a standby database in an Oracle database environment.

See the information on implementing Oracle Active Data Guard in the *PeopleTools: Data Management*, product documentation.

- The parameters InMemoryDBName and InMemoryDBType are reserved for internal use.
- If you do not want to change any values, specify *n* and you are prompted for the next configuration section.

8. After you have selected all your parameters, you see this message:

```
You will need to shut down and start up the server to read the new⇒
settings.
```

For descriptions of the Process Scheduler options in the PSADMIN, see the *PeopleTools: Process Scheduler* product documentation. In most cases you can accept the defaults.

## Task 15B-3-5: Verifying the Process Scheduler Server Status

At this stage it is a good idea to verify the Process Scheduler Server status.

To verify the Process Scheduler Server status:

1. From the PeopleSoft Process Scheduler Administration menu, choose option 3, for Domain status menu.

```

PeopleSoft Process Scheduler Administration

```

```
Domain Name: HRDMO
```

```
1) Boot this domain
2) Domain shutdown menu
3) Domain status menu
4) Configure this domain
5) TUXEDO command line (tmadmin)
6) Edit configuration/log files menu
7) Clean IPC resources of this domain
q) Quit
```

```
Command to execute (1-7, q) : 3
```

2. To verify the status of the Process Scheduler Server for a specific database, type the number corresponding to the appropriate database.

For example:

```
Database list:
```

```
1) HRDMO
```

```
Select item number to start: 1
```

```
Loading command line administration utility ...
tmadmin - Copyright (c) 2007-2008 Oracle.
Portions * Copyright 1986-1997 RSA Data Security, Inc.
All Rights Reserved.
Distributed under license by Oracle.
Tuxedo is a registered trademark.
```

```
> Prog Name Queue Name Grp Name ID RqDone Load Done Current⇒
```



```

Service

DDL 46845 pt-ibm20 0 9 450 (IDLE)
PSMONITORSRV MONITOR MONITOR 1 0 0 (IDLE)
PSAESRV 00101.00001 AESRV 1 0 0 (IDLE)
PSAESRV 00101.00002 AESRV 2 0 0 (IDLE)
PSAESRV 00101.00003 AESRV 3 0 0 (IDLE)
PSPRCSRV SCHEDQ BASE 101 0 0 (IDLE)
PSMSTPRC MSTRSCHQ BASE 102 0 0 (IDLE)
PSDSTSRV DSTQ BASE 103 0 0 (IDLE)
>

```

---

**Note.** You can also do this using the following command line argument:

```
psadmin -p status -d <DBNAME>
```

---

**Note.** You can also verify the status of the Process Scheduler Server from Process Monitor in PeopleSoft Pure Internet Architecture. To verify the Process Scheduler Server status from the Process Monitor page, go to PeopleTools, Process Scheduler, Process Monitor, and select *Server List*.

---



## Chapter 16

# Installing PeopleSoft Change Assistant

This chapter discusses:

- Understanding PeopleSoft Change Assistant
- Installing, Upgrading, or Removing Change Assistant in Silent Mode
- Using the Change Assistant Setup Script to Install, Upgrade, or Uninstall
- Configuring and Using PeopleSoft Change Assistant
- Validating Change Assistant Settings

## Understanding PeopleSoft Change Assistant

---

Oracle's PeopleSoft Change Assistant is a standalone tool, provided with PeopleSoft PeopleTools, that enables you to assemble and organize the steps necessary to apply patches and fixes for maintenance updates as well as perform PeopleSoft upgrades. You use different modes of Change Assistant to carry out maintenance both for PeopleSoft applications using the PeopleSoft Update Manager, and those using the classic patching method. Change Assistant is a Java-based tool that runs only on Microsoft Windows-based operating systems.

When you run the setup script for the PeopleTools Client DPK, you can choose to install Change Assistant as part of the client installation. If you need to install, upgrade, or remove Change Assistant independently of the PeopleTools Client DPK deployment, use the instructions in this chapter.

See "Deploying the PeopleTools Client DPK."

For the current PeopleSoft PeopleTools release, the Change Assistant installation includes the following features:

- You can install, upgrade, or remove Change Assistant using either a silent mode script or an interactive mode script.  
The *PS\_HOME/setup/PsCA* folder includes scripts and sample response text files for both the silent mode and interactive mode installation. The *PS\_HOME/setup/PsCA* folder is available in both the PeopleTools Client DPK deployment and PeopleTools DPK server deployments.
- You must run from *PS\_HOME/setup/PsCA*.  
Do not copy the PsCA folder alone to another location and try to install
- You can install multiple instances of Change Assistant from the current release on one physical machine.

---

**Note.** Multiple instances of Change Assistant can run in parallel on the same machine. However, when configuring Change Assistant, for example to set up update or upgrade jobs, you cannot run multiple instances against the same target database. That is, you cannot specify the same target database on different Change Assistant instances.

---

See *PeopleTools: Change Assistant and Update Manager*, "Running Multiple Instances of Change Assistant."

---

- You must remove installations of Change Assistant from PeopleSoft PeopleTools 8.55 or earlier before

installing from the current release. Change Assistant from PeopleSoft PeopleTools 8.57 cannot coexist with that from earlier releases.

- You must install each Change Assistant instance in a separate installation location.
- You can remove or upgrade each Change Assistant instance separately.
- When you remove an installation instance, you have the option to save the existing configuration information in a group of files gathered in a zip archive. You can configure Change Assistant at a later time by importing the zip file.

For more information on using Change Assistant for updates and for software upgrades, see the PeopleSoft product documentation.

## See Also

*PeopleTools: Change Assistant and Update Manager*

*PeopleTools: Application Designer Lifecycle Management Guide*

## Task 16-1: Installing, Upgrading, or Removing Change Assistant in Silent Mode

---

This section discusses:

- Understanding the Change Assistant Silent Mode Script
- Using the Change Assistant Silent Mode Script to Install, Upgrade, or Uninstall

### Understanding the Change Assistant Silent Mode Script

You can carry out a silent installation of Change Assistant by supplying command-line parameters to a script. With silent installation there is no user interaction after you begin the installation. You do not need to edit a text file before running the script.

You can install and upgrade multiple Change Assistant instances in silent mode for the current PeopleSoft PeopleTools release. In addition, you can use silent mode to remove installations from the current or earlier PeopleSoft PeopleTools releases. For example, running the silent mode installation from PeopleSoft PeopleTools 8.57 will remove a Change Assistant installation from PeopleSoft PeopleTools 8.54 or earlier, and also install the 8.57 version of Change Assistant.

The silent mode installation of Change Assistant uses the following files in the directory *PS\_HOME\setup\PsCA*:

- *silentInstall.bat* — Use this script to upgrade or remove an existing PeopleSoft Change Assistant instance or install a new instance.

See *Using the Silent Mode Script*.

- *CA-silentInstall-ResultCodes.rtf* — Review this file to interpret the results seen in the *PS\_HOME\setup\psCA\setup.log* file after installation.

The file is in Rich Text Format (RTF), and is most easily read if you open it with word processing software such as Microsoft Word.

## Task 16-1-1: Using the Change Assistant Silent Mode Script to Install, Upgrade, or Uninstall

The Change Assistant silent mode script requires the following command-line parameters:

- **Install Home**  
Specify the installation location for the Change Assistant instance. If the location includes spaces, surround it with double quotes, such as "C:\PS\Change Assistant".  
As mentioned earlier in this chapter, you can install multiple instances of Change Assistant. You must specify a different installation location for each instance.
- **Install Type**
  - Specify *NEW* to create a new Change Assistant instance.
  - Specify *UPGRADE* to upgrade an existing instance that was installed from the current PeopleSoft PeopleTools release.
  - Specify *UNINSTALL* to remove an existing Change Assistant instance.
- **Backup Config**
  - Specify *BACKUP* to create a zip file containing files with configuration information. The backup file, changeassistantcfgbak.zip, is saved in the installation location.
  - Specify *NOBACKUP* if you do not want to create a backup file with the configuration information.

To use the Change Assistant silent installation script:

1. In a command prompt, go to *PS\_HOME\setup\PsCA*.

---

**Note.** Do not move the file to another location.

---

2. Run the following command:

```
silentInstall.bat [Install Home] [Install Type] [Backup Config]
```

You must include all three parameters. For example:

- To install a new instance without retaining a configuration file  
`silentInstall.bat "C:\PS\Change Assistant" NEW NOBACKUP`
- To upgrade an existing instance, and retain a configuration file:  
`silentInstall.bat "C:\PS\Change Assistant 3" UPGRADE BACKUP`
- To remove an existing instance, and retain a configuration file:  
`silentInstall.bat D:\CA UNINSTALL BACKUP`

## Task 16-2: Using the Change Assistant Setup Script to Install, Upgrade, or Uninstall

---

This section discusses:

- Understanding the Change Assistant Setup Script
- Running the Change Assistant Setup Script to Install

- Running the Change Assistant Setup Script to Upgrade
- Running Change Assistant Setup Script to Uninstall

## Task 16-2-1: Understanding the Change Assistant Setup Script

You can run an interactive script located in installed in *PS\_HOME\setup\PsCA* to install, update, or remove Change Assistant. Note that you must run the script from the *PS\_HOME* installation. Do not copy the script or the PsCA folder alone to a different location to run.

To install Change Assistant, you can supply the installation location to the script on the command file or in a response text file. If you do not supply the installation location, the script prompts you for the necessary information. To upgrade or remove an existing installation, you run the script with no options.

## Task 16-2-2: Running the Change Assistant Setup Script to Install

To install Change Assistant with the setup script, open a command prompt, and change directory to *PS\_HOME\setup\PsCA*. Choose one of the following methods to install:

- If you want to specify the installation location on the command line, enter this command:

```
setup.bat -p <installation_path>
```

For example:

```
setup.bat -p C:\PS\Change Assistant
```

- If you want to specify the installation location and the location for the log file on the command line, enter this command:

```
setup.bat -p <installation_path> -lp <log_file_location>
```

- If you want to specify the installation location in a text file:

1. Open the sample response file *PS\_HOME\setup\PsCA\resp\_file.txt* for editing, for example in Notepad.
2. Modify the parameter `INSTALL_PATH="C:\PS\Change Assistant"` to specify the desired installation path.

If the installation location includes spaces, enclose it in double quotes.

3. Run this command:

```
setup.bat -f resp_file.txt
```

- If you want to run the installation interactively:

1. Run the script with no parameters:

```
setup.bat
```

The script checks for a response file and old installations.

2. Enter 1 for New Installation:

```

PeopleSoft Change Assistant

1) New Installation
2) Maintain or Update
q) Quit
Command to execute (1-2, q):1
```

3. Enter an installation location, or accept the default, C:\PS\Change Assistant.

PeopleSoft will install Change Assistant to the following directory .  
Destination Folder [C:\PS\Change Assistant] :

4. Wait until the script completes.

PeopleSoft Change Assistant Successfully Installed in C:\PS\Change⇒  
Assistant

### Task 16-2-3: Running the Change Assistant Setup Script to Upgrade

Run the setup script with no parameters to upgrade an existing Change Assistant installation. You can only upgrade an existing Change Assistant instance that was installed from the same, current PeopleTools release. For example, upgrade Change Assistant based on PeopleTools 8.57.04 to Change Assistant based on PeopleTools 8.57.12.

1. Open a command prompt, and change directory to *PS\_HOME\setup\PsCA*.
2. Run the script with no parameters:

```
setup.bat
```

3. Enter 2 for Maintain or Update.

```

PeopleSoft Change Assistant

1) New Installation
2) Maintain or Update
q) Quit
Command to execute (1-2, q):2
```

4. Select the instance of Change Assistant to update.

```
Please select the instance of Change Assistant :
1) Change Assistant 1 8.56.07 C:\Program Files\Change Assistant 2
2) Change Assistant 2 8.56.09 C:\Program Files\PeopleSoft\Change⇒
 Assistant
3) Change Assistant 3 8.57.04 C:\PS\Change Assistant

q)Quit
Command to execute (1-3, q):3
Selected
Change Assistant 3 8.57.04 C:\PS\Change Assistant
```

5. Enter 1 to update to the current PeopleTools patch release.

```
Please select the activity :
1) Upgrade Selected Instance
2) Uninstall Selected Instance
q)Quit
Command to execute (1-3, q):1
Selected
Change Assistant 3 8.57.04 C:\PS\Change Assistant
```

6. Enter 1 to upgrade without saving a configuration file.

Alternatively, if you want to retain a configuration file, enter 2 to create a zip file containing files with configuration information. The backup file, changeassistantcfgbak.zip, is saved in the installation location.

```
Please select the activity :
1)Without Retaining existing configuration
2)Retaining existing configuration
q)Quit
Command to execute (1-3, q):1
```

## Task 16-2-4: Running Change Assistant Setup Script to Uninstall

Run the setup script with no parameters to remove an existing Change Assistant installation.

1. Open a command prompt, and change directory to *PS\_HOME\setup\PsCA*.

2. Run the script with no parameters:

```
setup.bat
```

3. Enter 2 for Maintain or Update.

```

PeopleSoft Change Assistant

1) New Installation
2) Maintain or Update
q) Quit
Command to execute (1-2, q):2
```

4. Select the instance of Change Assistant to remove.

```
Please select the instance of Change Assistant :
1) Change Assistant 1 8.56.07 C:\Program Files\Change Assistant 2
2) Change Assistant 2 8.56.09 C:\Program Files\PeopleSoft\Change⇒
Assistant
3) Change Assistant 3 8.57.04 C:\PS\Change Assistant

q)Quit
Command to execute (1-3, q):3
Selected
Change Assistant 3 8.57.04 C:\PS\Change Assistant
```

5. Enter 2 to remove the selected instance.

```
Please select the activity :
1) Upgrade Selected Instance
2) Uninstall Selected Instance
q)Quit
Command to execute (1-3, q):2
Selected
Change Assistant 3 8.57.04 C:\PS\Change Assistant
```

6. Enter 1 to uninstall without saving a configuration file.

Alternatively, if you want to retain a configuration file, enter 2 to create a zip file containing files with configuration information. The backup file, changeassistantcfgbak.zip, is saved in the installation location.

```
Please select the activity :
```



```
1) Without Retaining existing configuration
2) Retaining existing configuration
q) Quit
Command to execute (1-3, q): 1
```

## Task 16-3: Configuring and Using PeopleSoft Change Assistant

---

This section discusses:

- Verifying the Path Variable
- Specifying Options
- Scanning the Workstation
- Exporting Jobs to XML, HTML, or Microsoft Excel Format

### Task 16-3-1: Verifying the Path Variable

After installing PeopleSoft Change Assistant, verify that the following values are the first entries in the PATH environment variable:

- `PS_HOME\bin\client\winx86`
- `PS_HOME\jre\bin`

See *PeopleTools: Change Assistant and Update Manager*, "Setting Up Change Assistant."

### Task 16-3-2: Specifying Options

You can configure PeopleSoft Change Assistant modes to carry out updates, upgrades, work with upgrade templates, or access PeopleSoft Update Manager. The mode selection determines which menu options you see when you use PeopleSoft Change Assistant.

#### See Also

*PeopleTools: Change Assistant and Update Manager*

PeopleSoft Update Manager Home Page, My Oracle Support, Doc ID 1641843.2

### Task 16-3-3: Scanning the Workstation

The first time you use PeopleSoft Change Assistant, it automatically scans your workstation for applications that it will use in order to automate the steps. For example, it automatically finds the SQL Query tool and uses it to run SQL commands or scripts.

If you add a new application or update an existing application, PeopleSoft Change Assistant must perform a scan of the system in order to discover the changes. To perform this scan, select Tools, Scan Configuration.

## Task 16-3-4: Exporting Jobs to XML, HTML, or Microsoft Excel Format

Change Assistant allows users to export jobs to XML, HTML, or Microsoft Excel file formats. Do this by selecting File, Export Job in Change Assistant. Then, enter the desired exported filename and select the desired file type format.

## Task 16-4: Validating Change Assistant Settings

---

After you have set up and configured PeopleSoft Change Assistant and the Environment Management components, you should validate your PeopleSoft Change Assistant and environment settings.

PeopleSoft Change Assistant validates settings by:


- Locating valid SQL query tools required to run SQL scripts.
- Testing the Environment Management hub and ensuring that PeopleSoft Change Assistant can communicate with it.
- Testing My Oracle Support and ensuring that PeopleSoft Change Assistant can communicate with it.

PeopleSoft Change Assistant sends a ping to My Oracle Support and then tests the connection. In order for the validation to succeed, the machine where you have PeopleSoft Change Assistant installed must have the ping feature enabled.

You can also print a summary of your environment, which can facilitate the diagnosis of problems by OracleSoftware Support.

To validate your environment, select Tools, Options, Validate. Click Start Validation.


If any of the steps were unable to complete successfully, open the log file to determine the cause. This example shows a summary with both successful messages ("Done") and unsuccessful ("Failed" or "Unsuccessful completion"):



Validating Change Assistant Settings in Your Environment

**Note.** If you use proxy servers, the system will ping those and prompt for proxy server user ID and password. In this case, the validation step numbers would be different from the example.

To review the log file, click the View Log button at the bottom of the screen. This example shows the first several lines of a log file:



```
validate_2018_9_24_14_45.log - Notepad
File Edit Format View Help
\psjoa.jar;C:\PS\ChangeAssistant\AbsoluteLayout.jar;C:\PS\ChangeAssistant
\log4j-api.jar;C:\PS\ChangeAssistant\log4j-core.jar;C:\PS\ChangeAssistant
\log4j-jcl.jar;C:\PS\ChangeAssistant\commons-io-2.5.jar;C:\PS\ChangeAssistant
\jwt4-12.2.1.1.0.jar;C:\PS\ChangeAssistant\share-12.2.1.1.0.jar;C:\PS
\ChangeAssistant\axis.jar;C:\PS\ChangeAssistant\j2ee.jar;C:\PS
\ChangeAssistant\psmanagement.jar;C:\PS\ChangeAssistant
\jre\lib\ext\jfxrt.jar;C:\PS\ChangeAssistant\je-7.4.5.jar
Current Working Directory: C:\PS\ChangeAssistant
Done.
(Step 2) Pinging Environment Management Hub
Pinging localhost
Done.
(Step 3) Connecting to Hub: http://localhost:8000/PSEMHUB/hub
Done.
(Step 4) Discovering Hub Environments.
Failed. No Environments were found in the Environment Management Hub.
Note: All agents should be running and sending pulses for all
Application,
Batch, File and Web Servers for the environment before Change Assistant
is started.
(Step 5) Validating your SQL Query Tools
Found Microsoft SQL Query Tool at c:\Program Files\Microsoft SQL Server
\100\Tools\Binn\SQLCMD.exe
Found DB2 SQL Query Tool at c:\Program Files\IBM\SQLLIB\bin\DB2CMD.exe
Found Oracle SQL Query Tool at c:\oracle32bitclient\product
\12.1.0\client_1\bin\sqlplus.exe
Done. 3 SQL Query Tools found.
[Mon Sep 24 14:48:38 MDT 2018] End Validation
Unsuccessful completion (1 Step Failed). Click on View Log to see additional
messages.
```

Change Assistant Validation log

## Chapter 17

# Installing PeopleSoft Change Impact Analyzer

This chapter discusses:

- Prerequisites
- Installing and Removing PeopleSoft Change Impact Analyzer in Silent Mode

## Prerequisites

---

Oracle's PeopleSoft Change Impact Analyzer is a tool you can use to evaluate the effect of changes you make on your installation. PeopleSoft Change Impact Analyzer can help you monitor the impact a Change Package has on your system, as well as monitor the impact from other changes such as customizations.

Ensure that your system meets the following requirements before you begin this installation:

- PeopleSoft Change Impact Analyzer runs on Microsoft Windows platforms. For database platforms that do not run on Microsoft Windows, install PeopleSoft Change Impact Analyzer on the Windows client.
- You can install PeopleSoft Change Impact Analyzer from downloaded files as a standalone application, or as a part of your PeopleSoft PeopleTools installation. These instructions assume you have installed PeopleSoft PeopleTools on the machine on which you want to run PeopleSoft Change Impact Analyzer, and have completed the PeopleSoft Change Assistant installation.
- You must install JDBC drivers for connectivity to your database platform. PeopleSoft Change Impact Analyzer uses Type 4 JDBC drivers by default.

You can normally obtain JDBC drivers from your RDBMS vendor. Search the vendor's web site or contact the vendor for information.

## See Also

*PeopleTools: Change Impact Analyzer*

## Task 17-1: Installing and Removing PeopleSoft Change Impact Analyzer in Silent Mode

---

This section discusses:

- Understanding Silent Mode for PeopleSoft Change Impact Analyzer
- Installing PeopleSoft Change Impact Analyzer in Silent Mode
- Removing the PeopleSoft Change Impact Analyzer Installation in Silent Mode

- Removing and Installing PeopleSoft Change Impact Analyzer in Silent Mode

## Understanding Silent Mode for PeopleSoft Change Impact Analyzer

You can carry out a silent installation or removal of PeopleSoft Change Impact Analyzer by editing a response file to correspond to your installation requirement. When you work in silent mode there is no user interaction after you begin the installation or removal.

The PeopleSoft Change Impact Analyzer installer includes the following files in the directory *PS\_HOME\setup\PsCIA*:

- CIA-silent-install-response-file.txt — Use this response file to install PeopleSoft Change Impact Analyzer.
- CIA-silent-uninstall-response-file.txt — Use this response file to remove PeopleSoft Change Impact Analyzer installations.
- silentInstall.bat — Use this script to remove an existing PeopleSoft Change Impact Analyzer installation, and install a new instance.
- silentInstall-ResultCodes.rtf — Review this file to interpret the results seen in the setup.log file after installation.

The file is in Rich Text Format (RTF), and is most easily read if you open it with an authoring tool, such as Microsoft Word.

## Task 17-1-1: Installing PeopleSoft Change Impact Analyzer in Silent Mode

This section discusses:

- Editing the Response File
- Running the Silent Mode Installation

### Editing the Response File

Review the header portion at the top of the response file for instructions on running the silent installation. Modify the response file according to your installation requirement. The sections labelled NOTE TO USER include items to be modified.

Open the file *PS\_HOME\setup\PsCIA\CIA-silent-install-response-file.txt* for editing, modify the following items, and then save the file:

- JDBC driver type

Enter 1 to specify your RDBMS platform, and 0 for the other selections. The options are: Oracle (default), MSS (Microsoft SQL Server), or DB2 (DB2 z/OS or DB2/LUW).

```
NOTE TO USER
the following option is for DB type for JDBC driver
the default is Sel-0=1, for Oracle
set the Sel-1=1 for MSS
set the Sel-2=1 for DB2
NOTE: the options are mutually exclusive
Sel-0=1
Sel-1=0
Sel-2=0
```

- Path to JDBC driver

Enter the full path to the JDBC driver for szPath.

```
NOTE TO USER
For MSS & DB2 please enter the path to JDBC driver for "szPath" below
szPath=c:\jdbcDrivers
```

- Installation location

The default location is C:\Program Files\PeopleSoft\Change Impact Analyzer. If you want to install to a different location, enter the location for szDir.

```
NOTE TO USER
For "szDir" enter the path where you want to install the Change Impact⇒
Analyzer
szDir=C:\Program Files\PeopleSoft\Change Impact Analyzer
```

## Running the Silent Mode Installation

To run the silent mode installation with the modified response file:

1. In a command prompt, go to *PS\_HOME\setup\PscIA*.
2. Run the following command, substituting your *PS\_HOME* location for %PS\_HOME% in the command:

```
installCIA.exe /s /f1"%PS_HOME%\setup\PscIA\CIA-silent-install-response-⇒
file.txt"
```

3. After the installation is complete, review the result status in the file *PS\_HOME\setup\PscIA\setup.log*.  
Result code 0 means a successful installation. The result codes are described in the file *PS\_HOME\setup\PscIA\silentInstall-ResultCodes.rtf*.

## Task 17-1-2: Removing the PeopleSoft Change Impact Analyzer Installation in Silent Mode

Review the header portion at the top of the response file for instructions. The process will search for and remove an existing installation of PeopleSoft Change Impact Analyzer. You do not need to edit the file before running. The file must be located in *PS\_HOME\setup\PscIA*.

1. In a command prompt, go to *PS\_HOME\setup\PscIA*.
2. Run the following command, substituting your *PS\_HOME* location for %PS\_HOME% in the command

```
installCIA.exe /s /f1"%PS_HOME%\setup\PscIA\CIA-silent-uninstall-⇒
response-file.txt"
```

3. After the installation is complete, review the result status in the file *PS\_HOME\setup\PscIA\setup.log*.  
Result code 0 means a successful installation. The result codes are described in the file *PS\_HOME\setup\PscIA\silentInstall-ResultCodes.rtf*.

## Task 17-1-3: Removing and Installing PeopleSoft Change Impact Analyzer in Silent Mode

Use the silentInstall.bat script to remove an existing installation of PeopleSoft Change Impact Analyzer and install a new installation. This script runs commands using CIA-silent-uninstall-response-file.txt followed by CIA-silent-install-response-file.txt. Refer to the previous sections for information on those response files.

To remove an existing installation and reinstall:

1. In a command prompt, go to *PS\_HOME\setup\PsCIA*.

2. Run the following command:

```
silentInstall.bat
```

3. After the installation is complete, review the result status in the file *PS\_HOME\setup\PsCIA\setup.log*.

Result code 0 means a successful installation. The result codes are described in the file *PS\_HOME\setup\PsCIA\silentInstall-ResultCodes.rtf*.



## Chapter 18

# Adding New Product Modules

### Task 18-1: Adding New Modules to PeopleSoft Installations

---

This task explains how to add new application modules to an existing PeopleSoft installation. Follow this procedure if, for example, you already installed HCM Benefits Administration and now you need to install Pension Administration.

When you add new application modules to an existing installation, you may overwrite files that were included as part of a patch or fixes, or customizations that you applied. For example, suppose you customize a report that is updated in a subsequent PeopleSoft release. If you install the update into your current working directory, your customized report will be overwritten with the newly installed, updated report.

The PeopleSoft system does not currently provide an automated way to notify you before overwriting customized modules or patch files. You can make preparations to protect important files from being overwritten. For your customized modules, you need to maintain a backup of any customizations. It is also a good idea to make a copy of your *PS\_HOME* directory before beginning this process, so that you can find and restore necessary patch files. Check My Oracle Support to identify any patches or fixes required for your installation.

See My Oracle Support, Patches & Updates.

To add new module(s) to PeopleSoft installations:

1. Back up the database, file server, application server, Process Scheduler Server, and web server components of your current system.
2. Install the PeopleSoft Application software on the file server.
3. Launch Data Mover in bootstrap mode by logging on with the access ID and password.  
Data Mover is located in *PS\_HOME\bin\client\winx86\psdmt.exe*.  
See Checking the Log Files and Troubleshooting, Running Data Mover, in the chapters on creating a database.
4. Select File, Database Setup and choose your database type in the resulting dialog.
5. Select Next and select add new product.
6. Select Finish and a Data Mover script will be generated in Data Mover.
7. Select File, Run script and your database updates are complete.
8. Install software to your batch server.  
See the chapters on setting up Process Scheduler in this documentation.
9. Reapply all code customizations if needed.

---

**Note.** Remember to maintain backup copies of your customizations.

---

10. Compile and link COBOL.

See the chapters on installing and compiling COBOL in this documentation.

11. Verify that the appropriate Installation Records are selected.

If they are not checked, check them and save the page. To open the page, select Set Up <apptype>, Install, Installation Options, where <apptype> is CRM, Financials/Supply Chain Management, and so on. For example, Set Up CRM, Install, Installation Options. (For HCM the navigation is Set Up HCM, Install, Installation Table.)

12. Run the dddaudit and sysaudit SQR reports.

If you are swapping the base language, also run swpaudit.sqr.

See "Completing the Database Setup," Checking the Database.

13. Shut down all application servers.

14. Install software to your application server.

See the chapters on configuring the Application Server in this documentation.

15. Restart all required application servers.

16. Shut down all web servers.

17. Install software to your web server.

See the chapters on setting up the PeopleSoft Pure Internet Architecture in this documentation.

## Chapter 19

# Using PeopleSoft Online Help

This chapter discusses:

- Understanding PeopleSoft Online Help (PeopleBooks)
- Using the PeopleSoft Online Help Web Site for Context-Sensitive Help
- Configuring Context-Sensitive Help with Local Installations
- Installing PeopleSoft Online Help Locally

## Understanding PeopleSoft Online Help (PeopleBooks)

---

The documentation for PeopleSoft PeopleTools and PeopleSoft software applications, formerly known as PeopleBooks, is now available in a dynamic, interactive, accessible HTML version, the hosted PeopleSoft Online Help Web site. The PeopleSoft Online Help documentation that is accessed with the Help link in the PeopleSoft navigation bar, and the Oracle's PeopleSoft Online Help Web site, are developed for advanced users, administrators, and implementers of the application. End users should utilize embedded help or licensed UPK content for more specific help assistance.

PeopleSoft software applications will include translated embedded help. With the PeopleSoft 9.2 release, PeopleSoft documentation aligned with the other Oracle applications by focusing on embedded help. We offer very direct translated help at crucial spots within our application through our embedded help widgets. Additionally, we have a one-to-one mapping of application and help translations. This means that the software and embedded help translation footprint are identical, something we were never able to accomplish in the past.

The PeopleSoft Online Help is delivered for on-premises installations of PeopleSoft PeopleTools and every PeopleSoft application. You have several options for deploying PeopleSoft Online Help to benefit your organization. This chapter describes the methods for accessing, installing, and configuring PeopleSoft Online Help.

- *Hosted PeopleSoft Online Help Web site:* Use PeopleSoft Online Help over the Internet with the hosted content on the hosted PeopleSoft Online Help Web site.  
See PeopleSoft Hosted Online Help,  
[https://docs.oracle.com/cd/E17566\\_01/epm91pbr0/eng/psbooks/psft\\_homepage.htm](https://docs.oracle.com/cd/E17566_01/epm91pbr0/eng/psbooks/psft_homepage.htm).
- *Context-sensitive help:* Configure PeopleSoft PeopleTools to call PeopleSoft Online Help as context-sensitive help from both Internet applications and Microsoft Windows-based programs. For instance, when a user clicks the Help link in a browser or presses F1 in Windows, the appropriate documentation appears. You can set up context-sensitive help for both local installations and to access the hosted content on the PeopleSoft Online Help Web site.

---

**Note.** The F1 button accesses PeopleSoft Online Help only for the PeopleTools Development Environment (the Windows-based client). If you press F1 while using the portal, you invoke the help for your current browser. For context-sensitive help in the portal, users need to click the Help link to call PeopleSoft Online Help.

---

- *PDF format:* You can download a PDF version of PeopleSoft Online Help, organized in the traditional PeopleBooks format, from the PeopleSoft Documentation Portal.  
See PeopleSoft Documentation Portal,  
[https://docs.oracle.com/cd/E17566\\_01/epm91pbr0/eng/psbooks/psft\\_docall.htm](https://docs.oracle.com/cd/E17566_01/epm91pbr0/eng/psbooks/psft_docall.htm).
- *Local installation:* For on-premises environments, install and configure PeopleSoft Online Help so you can deploy the documentation at your site.

## See Also

"Preparing for Installation," Planning Multilingual Strategy

*PeopleTools: Applications User's Guide*, "Accessing Embedded Help"

*About This Help*, PeopleSoft Hosted Online Help,

[https://docs.oracle.com/cd/E17566\\_01/epm91pbr0/eng/psbooks/psft\\_homepage.htm](https://docs.oracle.com/cd/E17566_01/epm91pbr0/eng/psbooks/psft_homepage.htm)

## Task 19-1: Using the PeopleSoft Online Help Web Site for Context-Sensitive Help

---

This section discusses:

- Understanding the PeopleSoft Online Help Web Site
- Setting Up Context-Sensitive Help with the PeopleSoft Online Help Web Site
- Setting Up F1 Help with the PeopleSoft Online Help Web Site

### Understanding the PeopleSoft Online Help Web Site

PeopleSoft Online Help is immediately available for use over the Internet at the PeopleSoft Online Help Web site. To configure context-sensitive help with the PeopleSoft Online Help web site, you must have an Internet connection available to your server where PeopleSoft PeopleTools is installed.

See PeopleSoft Online Help, [www.peoplesoftonlinehelp.com](http://www.peoplesoftonlinehelp.com).

### Task 19-1-1: Setting Up Context-Sensitive Help with the PeopleSoft Online Help Web Site

You can configure your PeopleSoft server to use the hosted documentation from the PeopleSoft Online Help Web site for context-sensitive help. Each page in your PeopleSoft applications includes a Help icon that, when clicked, opens a new browser window displaying help topics that discuss that page. To enable the Help link from application pages:

1. Log in to your PeopleSoft application in a browser.
2. Select PeopleTools, Web Profile, Web Profile Configuration.
3. Click Search and select the Profile Name you specified during your PeopleSoft Pure Internet Architecture installation, for example, PROD.
4. Gather the information for the help URL.

You can access the URLs from the PeopleSoft Online Help Web site. Under Setting Up Context-Sensitive Help, select the link Enabling the Help Link from the Application Pages.

See PeopleSoft Online Help,  
[http://docs.oracle.com/cd/E17566\\_01/epm91pbr0/eng/psbooks/pdfs/EnablingtheHelpLinkfromApplicationPages.pdf](http://docs.oracle.com/cd/E17566_01/epm91pbr0/eng/psbooks/pdfs/EnablingtheHelpLinkfromApplicationPages.pdf).

The URLs have the following format, where UlinkID1, UlinkID2, ...UlinkID $n$  refer to universal linking product line codes:

[http://www.oracle.com/pls/topic/lookup?id=%CONTEXT\\_ID%&ctx=UlinkID1&ctx=UlinkID2....&ctx=UlinkIDn](http://www.oracle.com/pls/topic/lookup?id=%CONTEXT_ID%&ctx=UlinkID1&ctx=UlinkID2....&ctx=UlinkIDn)

The URL for the PeopleTools documentation must come before the URLs for PeopleSoft application documentation, as in this example:

[http://www.oracle.com/pls/topic/lookup?id=%CONTEXT\\_ID%&ctx=pt857pbr1&ctx=hcm92pbr28](http://www.oracle.com/pls/topic/lookup?id=%CONTEXT_ID%&ctx=pt857pbr1&ctx=hcm92pbr28)

- On the General page in the Help URL field, enter the URL for one or more products.

This example shows the Web Profile Configuration page with a sample help URL for PeopleSoft PeopleTools 8.57 and PeopleSoft HCM 9.2:

**Manager Self Service** **Web Profile Co...**

[New Window](#) | [Help](#) | [Personalize Page](#)

**General** | Security | Virtual Addressing | Cookie Rules | Authorized Site | Caching | Debugging

Profile Name: PROD Save As ... View History

Description: Installation Defaults

Authentication Domain: .example.com

Help URL: w.oracle.com/pls/topic/lookup?id=%CONTEXT\_ID%&ctx=pt857pbr1&ctx=hcm92pbr: x

☒ Compress Responses

☒ Compress Response References

Compress Mime Types: application/x-javascript,text/javascript,text/css,text/html

☒ Compress Query

Save Confirmation Display Time: 3,000 Milliseconds

☒ Enable Processing Message

☒ Enable New Window

☐ Enable Print

☒ Enable PPM Agent

PPM Monitor Buffer Size: 51,200 KB

☐ Single Thread Netscape

Single Thread Delay: 1,000 Milliseconds

Non-standard Base Path:

**Reports**

☒ Enable Report Repository

Report Repository Path:

**Compress Report Output**

☒ All Browsers

☐ Exclude NetScape

☐ Do Not Compress

[Save](#) [Return to Search](#) [Previous in List](#) [Next in List](#) [Notify](#) [Previous tab](#) [Next tab](#) [Add](#)

[General](#) | [Security](#) | [Virtual Addressing](#) | [Cookie Rules](#) | [Authorized Site](#) | [Caching](#) | [Debugging](#) | [Look and Feel](#) | [Custom Properties](#)

Web Profile Configuration General page with a sample PeopleSoft Hosted Documentation URL

- Save and exit the Web Profile Configuration page.
- Restart the following servers:
  - If your PeopleSoft Pure Internet Architecture (PIA) is running on Oracle WebLogic, restart the PIA and admin web servers.
  - If the Help link does not appear in the next step, it may be necessary to also stop and restart the application

server.

8. Test the help functionality by clicking the Help icon on a PeopleSoft application page.

## Task 19-1-2: Setting Up F1 Help with the PeopleSoft Online Help Web Site

PeopleTools Application Designer also has context-sensitive help available through the user's F1 key. To enable this help functionality, the PeopleTools Options must be configured to access the hosted content on the PeopleSoft Online Help Web site as follows:

1. In your PeopleSoft application, select PeopleTools, Utilities, Administration, PeopleTools Options.
2. Scroll down to the Help Options group.
3. Enter the value for the F1 URL field.

Specify the URL for the PeopleSoft PeopleTools online help for your release. The URL should be similar to the following:

[http://www.oracle.com/pls/topic/lookup?id=%CONTEXT\\_ID%&ctx=pt857pbr1](http://www.oracle.com/pls/topic/lookup?id=%CONTEXT_ID%&ctx=pt857pbr1)

You can access the URL from the PeopleSoft Online Help Web site. Under Setting Up Context-Sensitive Help, select the link Enabling the Help Link from the Application Pages.

See PeopleSoft Online Help,

[http://docs.oracle.com/cd/E17566\\_01/epm91pbr0/eng/psbooks/pdfs/EnablingtheHelpLinkfromApplicationPages.pdf](http://docs.oracle.com/cd/E17566_01/epm91pbr0/eng/psbooks/pdfs/EnablingtheHelpLinkfromApplicationPages.pdf).

4. Save and exit the PeopleTools Options page.
5. Stop and restart the application server each time you update the help URL.
6. Open Application Designer. Press F1 to display the online help content.
7. For context-sensitive help, open an object, such as a panel or PeopleCode, then press F1.

## Task 19-2: Configuring Context-Sensitive Help with Local Installations

---

This section discusses:

- Enabling the Help Link from the Application Pages with Local Installations
- Enabling F1 Help with Local Installations
- Creating the Help Index for Multi-Product Installations

### Task 19-2-1: Enabling the Help Link from the Application Pages with Local Installations

You can configure your PeopleSoft installation so that each page in your PeopleSoft software applications includes a Help link. Clicking the Help link opens a new browser window displaying help topics that discuss that page. Use the instructions in this section to enable the Help link for locally-installed PeopleSoft Online Help only.

To enable the Help link from application pages:

1. In your PeopleSoft application, navigate to the PeopleTools, Web Profile, Web Profile Configuration page.
2. Click Search and select the Profile Name you specified during your PeopleSoft Pure Internet Architecture installation.

3. Specify the value for the Help URL field as follows:

```
http://<server_name>:<port_number>/<help_folder>/help.html?ContextID=&=&CONTEXT_ID%&LangCD=%LANG_CD%
```

---

**Note.** If you do not want the Help icon to display in your applications, clear the Help URL field value.

---

For example, if your web server is called myserver, you are using port 7001, and your *help\_folder* is pt857pbr1, the Help URL value would be:

```
http://myserver:7001/pt857pbr1/help.html?ContextID=%CONTEXT_ID%&LangCD=&=&LANG_CD%
```

- Enter your web server name for <server\_name>.
  - Enter the web server port for <port\_number>.
  - Enter the folder where you installed the help system files for <help\_folder>.
  - The system resolves %CONTEXT\_ID% to the page name from which you called help. The system resolves %LANG\_CD% to the signon language of the user.
4. Save and exit the Web Profile Configuration page.
5. Before testing help functionality, purge the browser cache on the client and close all web browsers. Restart the application server and web server for PIA.
6. Test the help functionality by clicking the Help link on a PeopleSoft application page.

## Task 19-2-2: Enabling F1 Help with Local Installations

This procedure describes how to enable F1 help for Application Designer, PeopleCode Editor, and other Microsoft Windows-based PeopleSoft programs.

To enable F1 help:

1. Sign on to your PeopleSoft application using your browser.
2. Select the PeopleTools, Utilities, Administration, PeopleTools Options page.
3. Enter the same URL as in the previous procedure (where <server\_name>, <port\_number>, and <help\_folder> reflect your installation) into the F1 Help URL field:

```
http://<server_name>:<port_number>/<help_folder>/help.html?ContextID=&=&CONTEXT_ID%&LangCD=%LANG_CD%
```

For example:

```
http://myserver:7001/pt857pbr1/help.html?ContextID=%CONTEXT_ID%&LangCD=&=&LANG_CD%
```

4. Save the page.

## Task 19-2-3: Creating the Help Index for Multi-Product Installations

The PeopleSoft Online Help site contains a precompiled context-sensitive help index containing all context IDs for the product family. To have the help processor deliver help pages from other product families, you need to re-create this help index to include the context IDs for all applicable product families.



Note that this procedure does not support help sites for PeopleSoft 9.1 and PeopleTools 8.52 and earlier. To include help sites for those releases, select About This help in the PeopleSoft PeopleTools product documentation.

See *Managing Locally Installed PeopleSoft Online Help*, "Including Multiple Online Help Sites for PeopleSoft 9.1 and PeopleTools 8.52 and Earlier."

To re-create the context-sensitive help index follow the instructions "Creating Index for multi-domain online help site" described in the README.txt file included with the downloaded zip files.

See *Managing Locally Installed PeopleSoft Online Help*, "Including Multiple Online Help Sites for PeopleSoft 9.2 and PeopleTools 8.53 and Later."

## Task 19-3: Installing PeopleSoft Online Help Locally

---

This section discusses:

- Prerequisites
- Obtaining the PeopleSoft Documentation Files from Oracle Software Delivery Cloud
- Deploying PeopleSoft Documentation Library on a WebLogic Server
- Removing the PeopleSoft Online Help Deployment
- Setting Up Help for Multiple Product Lines on the Same Machine

### Prerequisites

Before installing the PeopleSoft online help:

- Obtain the installation file for the PeopleSoft Online Help from Oracle Software Delivery Cloud, as described in the next section.
- Install a supported web server and verify that it is up and running.

This task describes the steps for Oracle WebLogic on Microsoft Windows. Determine the URL, user name, and password for the Oracle WebLogic administration console.

---

**Note.** If you install Oracle WebLogic as part of the PeopleSoft DPK deployment, you can find the port number and user name in the `psft_configuration.yaml` file. In this case, the default port is 8000 and the default name is system. You supply the password during the deployment.

---

- Install the Elasticsearch search utility and verify that it is up and running.

The "Search Utility for locally installed PeopleSoft Documentation" contains a customized version of Elasticsearch for PeopleSoft Online Help that is independent of the Elasticsearch that is used for the PeopleSoft search framework. The utility is available on Oracle Software Delivery Cloud in the same delivery package as the PeopleSoft online help documentation. The downloaded zip file includes a text file with instructions.

---

**Note.** For the sake of brevity, this task refers to the "Search Utility for locally installed PeopleSoft Documentation" as the "search utility."

---

- The PeopleSoft Online Help installation requires Java 8.

---

**Note.** Oracle supports a number of versions of UNIX and Linux in addition to Microsoft Windows for the PeopleSoft installation. Throughout this book, there are references to operating systems. Where necessary, this book refers to specific operating systems by name (for example, Oracle Solaris, IBM AIX, HP-UX Itanium, or Linux); however, for simplicity the word UNIX is often used to refer to all UNIX-like operating systems, including Linux.

---

## Task 19-3-1: Obtaining the PeopleSoft Documentation Files from Oracle Software Delivery Cloud

This section explains locating and using the installation files for PeopleSoft Online Help and the search utility, if you have not already done so. The files are included in the installation files for PeopleSoft applications and PeopleSoft PeopleTools.

To obtain files for the PeopleSoft Online Help installation from Oracle:

1. Sign in to Oracle Software Delivery Cloud.  
See Oracle Software Delivery Cloud, <https://edelivery.oracle.com>.
2. Search for the current PeopleSoft PeopleTools release.
3. In the search results, locate the PeopleSoft PeopleTools download package, and click Add to Cart.
4. If you want to obtain the PeopleSoft Online Help installation files for a PeopleSoft application, search for the name of a specific PeopleSoft application product, and locate the download package.  
For example, for PeopleSoft Human Capital Management, enter and select PeopleSoft Enterprise Human Resources. For PeopleSoft Financials and Supply Chain Management, enter and select PeopleSoft Enterprise Financials.
5. Click Selected Software.
6. On the Selected Software page, locate the PeopleSoft PeopleTools or PeopleSoft application documentation files.
7. Click Continue.
8. Read the license agreement, select the check box to acknowledge that you accept the agreement, and then click Continue.
9. On the File Download window, select the links for the online help zip file and the search utility.
10. Download the zip files into a convenient local directory.

## Task 19-3-2: Deploying PeopleSoft Documentation Library on a WebLogic Server

This task uses the PeopleSoft PeopleTools 8.57 documentation library as an example.

1. Create folder C:\PeopleBooks2 to serve as the documentation root.
2. Install and set up the search utility.

This section refers to the installation location as *SRCH\_UTILITY\_INSTALL*. Follow the instructions in the *INSTALL.txt* file included with the downloaded zip file to:

- Set up Elasticsearch for PeopleSoft Online Help
- Deploy Elasticsearch for PeopleSoft Online help search page

These instructions assume that you copy the *pssearch* folder to C:\PeopleBooks2.

3. Copy the zip file containing the PeopleSoft Online Help to C:\PeopleBooks2, and extract into the same folder.

4. Create a folder WEB-INF under the C:\PeopleBooks2 folder.
5. In the WEB-INF folder create a file named "web.xml" that has the following content:

```
<?xml version="1.0" encoding="UTF-8"?>

<!DOCTYPE web-app PUBLIC

"-//Sun Microsystems, Inc.//DTD Web Application 2.3//EN"

"http://java.sun.com/j2ee/dtds/web-app_2_3.dtd">

<web-app>

</web-app>
```


This allows Oracle WebLogic to recognize the C:\PeopleBooks2 folder as a valid deployment.

6. Open the Oracle WebLogic administration console by entering the following URL in a browser:

`http://<hostname>:<port>/console`

For example, `http://server.example.com:7001/console`

7. Log in using Oracle WebLogic administrator credentials.



Oracle WebLogic Server Administration Console 12c

8. Select Deployments from the Domain Structure section on the left side of the window:

**ORACLE WebLogic Server Administration Console 12c**

Home Log Out Preferences Record Help

Welcome, weblogic Connected to: base\_domain

Home > Summary of Deployments

**Home Page**

**Change Center**  
View changes and restarts  
Configuration editing is enabled. Future changes will automatically be activated as you modify, add or delete items in this domain.

**Domain Structure**  
base\_domain  
• Domain Partitions  
• Environment  
• Deployments  
• Services  
• Security Realms  
• Interoperability  
• Diagnostics

**How do I...**  
• Search the configuration  
• Use the Change Center  
• Record WLST scripts  
• Change Console preferences  
• Manage Console extensions  
• Monitor servers

**System Status**  
Health of Running Servers as of 6:14 PM  
Failed (0)  
Critical (0)  
Overloaded (0)  
Warning (0)  
OK (1)

**Information and Resources**  
Helpful Tools  
• Configure applications  
• Configure GridLink for RAC Data Source  
• Configure a Dynamic Cluster  
• Recent Task Status  
• Set your console preferences  
General Information  
• Common Administration Task Descriptions  
• Read the documentation  
• Ask a question on My Oracle Support

**Domain Configurations**  
Domain  
• Domain  
Domain Partitions  
• Domain Partitions  
• Partition Work Managers  
Environment  
• Servers  
• Clusters  
• Server Templates  
• Migratable Targets  
• Coherence Clusters  
• Machines  
• Virtual Hosts  
• Virtual Targets  
• Work Managers  
• Concurrent Templates  
Resource Group Templates  
• Resource Group Templates  
Resource Groups  
• Resource Groups  
Deployed Resources  
• Deployments  
Services  
• Messaging  
• JMS Servers  
• Store-and-Forward Agents  
• JMS Modules  
• Path Services  
• Bridges  
• Data Sources  
• Persistent Stores  
Interoperability  
• WTC Servers  
• Jolt Connection Pools  
Diagnostics  
• Log Files  
• Diagnostic Modules  
• Built-in Diagnostic Modules  
• Diagnostic Images  
• Request Performance  
• Archives  
• Context  
• SNMP  
• Interceptors  
Charts and Graphs  
• Monitoring Dashboard

Oracle WebLogic Administration Console Home Page

9. Click Install on the Deployments section of the Configuration tab under Summary of Deployments.

**ORACLE WebLogic Server Administration Console 12c**

Home Log Out Preferences Record Help

Welcome, weblogic Connected to: base\_domain

Home > Summary of Deployments

**Summary of Deployments**

Configuration Control Monitoring

This page displays the list of Java EE applications and standalone application modules installed to this domain.

You can update (redeploy) or delete installed applications and modules from the domain by selecting the checkbox next to the application name and then using the controls on this page.

To install a new application or module for deployment to targets in this domain, click **Install**.

[Customize this table](#)

**Deployments**

Install Update Delete Showing 1 to 1 of 1 Previous Next

<input type="checkbox"/>	Name	State	Health	Type	Targets	Scope	Domain Partitions	Deployment
<input type="checkbox"/>	PeopleBooks	Active	OK	Web Application	AdminServer	Global		100

Install Update Delete Showing 1 to 1 of 1 Previous Next

System Status


Health of Running Servers as of 6:15 PM

- Failed (0)
- Critical (0)
- Overloaded (0)
- Warning (0)
- OK (1)

Configuration tab on the Summary of Deployments page


10. If necessary, enter C:\ for the path.

You see the computer directory structure. The entry for PeopleBooks includes a radio button indicating that this folder can be deployed as an application.



Locate deployment to install and prepare for deployment page

11. Select PeopleBooks2 (open directory) and then click Next.



Select folder on the Locate deployment to install and prepare for deployment page



12. On the Choose installation type and scope page, select the option Install this deployment as an application. Accept Global as the Scope, and then click Next.

**ORACLE WebLogic Server Administration Console 12c**

Home Log Out Preferences Record Help

Welcome, weblogic Connected to: base\_domain

Home > Summary of Deployments

### Install Application Assistant

Back Next Finish Cancel

#### Choose installation type and scope

Select if the deployment should be installed as an application or library. Also decide the scope of this deployment.

The application and its components will be targeted to the same locations. This is the most common usage.

☒ **Install this deployment as an application**

Application libraries are deployments that are available for other deployments to share. Libraries should be available on all of the targets running their referencing applications.

☐ **Install this deployment as a library**

Select a scope in which you want to install the deployment.

Scope: Global

Back Next Finish Cancel

**Change Center**

**View changes and restarts**

Configuration editing is enabled. Future changes will automatically be activated as you modify, add or delete items in this domain.

**Domain Structure**

- base\_domain
  - Domain Partitions
  - Environment
  - Deployments
  - Services
  - Security Realms
  - Interoperability
  - Diagnostics

**How do I...**

- Start and stop a deployed enterprise application
- Configure an enterprise application
- Create a deployment plan
- Target an enterprise application to a server instance
- Test the modules in an enterprise application

**System Status**

Health of Running Servers as of 6:22 PM

Failed (0)
Critical (0)
Overloaded (0)
Warning (0)
OK (1)

Choose installation type and scope page

13. Accept the default entries on the Optional Settings page, and click Next.

The page includes sections General, Security, Source Accessibility, and Plan Source Accessibility.

**ORACLE WebLogic Server Administration Console 12c**

Home Log Out Preferences Record Help

Welcome, weblogic Connected to: base\_domain

Home > Summary of Deployments

**Install Application Assistant**

Back Next Finish Cancel

**Optional Settings**

You can modify these settings or accept the defaults.  
\* Indicates required fields

**General**

What do you want to name this deployment?

\* Name: PeopleBooks2

**Security**

What security model do you want to use with this application?

☒ **DD Only:** Use only roles and policies that are defined in the deployment descriptors.

☐ **Custom Roles:** Use roles that are defined in the Administration Console; use policies that are defined in the deployment descriptor.

☐ **Custom Roles and Policies:** Use only roles and policies that are defined in the Administration Console.

☐ **Advanced:** Use a custom model that you have configured on the realm's configuration page.

**Domain Structure**

- base\_domain
  - Domain Partitions
  - Environment
  - Deployments
  - Services
  - Security Realms
  - Interoperability
  - Diagnostics

**Change Center**

**View changes and restarts**

Configuration editing is enabled. Future changes will automatically be activated as you modify, add or delete items in this domain.

**How do I...**

- Start and stop a deployed enterprise application
- Configure an enterprise application
- Create a deployment plan
- Target an enterprise application to a server instance
- Test the modules in an enterprise application

Top section of the Optional Settings page

System Status

Health of Running Servers as of 11:25 AM

Failed (0)

Critical (0)

Overloaded (0)

Warning (0)

OK (1)

Source Accessibility

How should the source files be made accessible?

☒ Use the defaults defined by the deployment's targets

Recommended selection.

☐ Copy this application onto every target for me

During deployment, the files will be copied automatically to the Managed Servers to which the application is targeted.

☐ I will make the deployment accessible from the following location

Location:

Provide the location from where all targets will access this application's files. This is often a shared directory. You must ensure the application files exist in this location and that each target can reach the location.

Plan Source Accessibility

How should the plan source files be made accessible?

☒ Use the same accessibility as the application

Recommended selection.

☐ Copy this plan onto every target for me

During deployment, the plan files will be copied automatically to the Managed Servers to which the application is targeted.

☐ Do not copy this plan to targets

You must ensure the plan files exist in the shared location and that each target can reach the location.

Bottom section of the Optional Settings page

14. On the Review your choices and click Finish page, select the option Yes, take me to the deployment's configuration screen.

Click Finish.

The screenshot displays the Oracle WebLogic Server Administration Console 12c interface. The main content area is titled 'Install Application Assistant' and shows the 'Review your choices and click Finish' step. The left sidebar contains navigation links for 'Change Center', 'Domain Structure', 'How do I...', and 'System Status'. The 'Domain Structure' shows a tree view with 'base\_domain' expanded, including 'Domain Partitions', 'Environment', 'Deployments', 'Services', 'Security Realms', 'Interoperability', and 'Diagnostics'. The 'System Status' shows the health of running servers as of 11:27 AM, with a green bar indicating 'OK (1)'. The main content area has a breadcrumb trail 'Home > Summary of Deployments' and a 'Welcome, weblogic' message. The 'Review your choices and click Finish' section includes a message: 'Click Finish to complete the deployment. This may take a few moments to complete.' Below this is the 'Additional Configuration' section, which asks: 'In order to work successfully, this application may require additional configuration. Do you want to review this application's configuration after completing this assistant?'. There are two radio button options: 'Yes, take me to the deployment's configuration screen.' (selected) and 'No, I will review the configuration later.' Below this is the 'Summary' section, which lists deployment details: 'Deployment: C:\PeopleBooks2', 'Name: PeopleBooks2', 'Staging Mode: Use the defaults defined by the chosen targets', 'Plan Staging Mode: Use the same accessibility as the application', 'Security Model: DDOnly: Use only roles and policies that are defined in the deployment descriptors.', and 'Scope: Global'. At the bottom is the 'Target Summary' table, which has two columns: 'Components' and 'Targets'. The table contains one row: 'PeopleBooks2' under 'Components' and 'AdminServer' under 'Targets'. Navigation buttons 'Back', 'Next', 'Finish', and 'Cancel' are present at the top and bottom of the main content area.

**Oracle WebLogic Server Administration Console 12c**

Home Log Out Preferences Record Help

Welcome, weblogic Connected to: base\_domain

Home > Summary of Deployments

**Install Application Assistant**

Back Next Finish Cancel

**Review your choices and click Finish**

Click Finish to complete the deployment. This may take a few moments to complete.

**Additional Configuration**

In order to work successfully, this application may require additional configuration. Do you want to review this application's configuration after completing this assistant?

☒ Yes, take me to the deployment's configuration screen.

☐ No, I will review the configuration later.

**Summary**

**Deployment:** C:\PeopleBooks2

**Name:** PeopleBooks2

**Staging Mode:** Use the defaults defined by the chosen targets

**Plan Staging Mode:** Use the same accessibility as the application

**Security Model:** DDOnly: Use only roles and policies that are defined in the deployment descriptors.

**Scope:** Global

**Target Summary**

Components	Targets
PeopleBooks2	AdminServer

Back Next Finish Cancel

Review your choices and click Finish page

15. If necessary, click **Activate Changes** under **Change Center** on the left to save and **Activate** the deployment. Otherwise, click **Save**.

**ORACLE WebLogic Server Administration Console 12c**

Home Log Out Preferences Record Help

Welcome, weblogic Connected to: base\_domain

Home > Summary of Deployments > PeopleBooks2 > Summary of Deployments > PeopleBooks2

### Settings for PeopleBooks2

**Overview** Deployment Plan Configuration Security Targets Control Testing Monitoring

Notes

**Save**

Use this page to view the installed configuration of a Web application.

<b>Name:</b>	PeopleBooks2	The name of this application deployment. <a href="#">More Info...</a>
<b>Scope:</b>	Global	Specifies if this Web application is accessible within the domain, a partition, or a resource group template. <a href="#">More Info...</a>
<b>Context Root:</b>	/PeopleBooks2	The specific path at which this Web application is found by a servlet. <a href="#">More Info...</a>
<b>Path:</b>	C:\PeopleBooks2	The path to the source of the deployable unit on the Administration Server. <a href="#">More Info...</a>
<b>Deployment Plan:</b>	(no plan specified)	The path to the deployment plan document on the Administration Server. <a href="#">More Info...</a>
<b>Staging Mode:</b>	(not specified)	Specifies whether an application's files are copied from a source on the Administration Server to the Managed Server's staging area during application preparation. <a href="#">More Info...</a>
<b>Plan Staging Mode:</b>	(not specified)	Specifies whether a deployment plan's files are copied from a source on the Administration Server to the Managed Server's staging area during application preparation. <a href="#">More Info...</a>
<b>Security Model:</b>	DDOnly	The security model specifies how this deployment should be secured. <a href="#">More Info...</a>

Top section of Settings for PeopleBooks 2 page


**Deployment Order:**


An integer value that indicates when this unit is deployed, relative to other deployable units on a server, during startup. [More Info...](#)


**Deployment Principal Name:**


A string value that indicates the principal that should be used when deploying the file or archive during startup and shutdown. This principal will be used to set the current subject when calling out into application code for interfaces such as ApplicationLifecycleListener. If no principal name is specified, then the anonymous principal will be used. [More Info...](#)

**Modules and Components**

Showing 1 to 1 of 1
Previous
Next

Name 	Type
 PeopleBooks2	Web Application
 REST Services	None to display
 Web Services	None to display

Showing 1 to 1 of 1
Previous
Next

Bottom section of Settings for PeopleBooks 2 page

16. After the deployment is activated, select Deployments from the Domain Structure frame.
17. Select the Control tab in the Summary of Deployments section

18. Select the check box for the deployment, and click Start.

Choose Servicing All requests from the Start menu.

**ORACLE WebLogic Server Administration Console 12c**

Home Log Out Preferences Record Help

Welcome, weblogic Connected to: base\_domain

Home > Summary of Deployments > PeopleBooks2 > Summary of Deployments > PeopleBooks2 > Summary of Deployments

### Summary of Deployments

Configuration **Control** Monitoring

This page displays the list of Java EE applications and standalone application modules installed to this domain.

You can start and stop applications and modules from the domain by selecting the checkbox next to the application name and then using the controls on this page.

[Customize this table](#)

#### Deployments

Start Stop Showing 1 to 2 of 2 Previous Next

<input type="checkbox"/>	Name	State	Health	Type	Targets	Scope	Domain Partitions
<input type="checkbox"/>	PeopleBooks	Active	OK	Web Application	AdminServer	Global	
<input checked="" type="checkbox"/>	PeopleBooks2	Active	OK	Web Application	AdminServer	Global	

Start Stop Showing 1 to 2 of 2 Previous Next

Servicing all requests

Servicing only administration requests

**Change Center**

**View changes and restarts**

Configuration editing is enabled. Future changes will automatically be activated as you modify, add or delete items in this domain.

**Domain Structure**

- base\_domain
  - Domain Partitions
  - Environment
  - Deployments
  - Services
  - Security Realms
  - Interoperability
  - Diagnostics

**How do I...**

- Configure an enterprise application
- Start applications and modules
- Stop applications and modules
- View the modules of an enterprise application
- Monitor the modules of an enterprise application

**System Status**

Health of Running Servers as of 11:36 AM

- Failed (0)
- Critical (0)
- Overloaded (0)
- Warning (0)
- OK (1)

Start deployment on Summary of Deployments page


19. Log out of the Oracle WebLogic Administration console.

20. Verify that you can access the PeopleSoft Online Help by entering this URL in a browser:

`http://<hostname>:<weblogic port>/PeopleBooks/<library name>/eng/<product family>/index.html`

Enter the fully qualified machine name for `<hostname>`, the Oracle WebLogic port for `<weblogic port>`. Enter the PeopleSoft documentation library name (that is, the name of the folder extracted from the downloaded zip file) for `<library name>`. The `<product family>` is an abbreviation for the PeopleSoft product, such as `pt` for PeopleSoft PeopleTools. For example, this URL displays the PeopleSoft PeopleTools 8.57 documentation home page:

`http://server.example.com:7001/PeopleBooks2/pt857pbr1/eng/pt/index.html`



PeopleSoft PeopleTools 8.57 Help Home Page

21. Crawl the online help site.



See the instructions in `INSTALL.txt`.

- a. In a command prompt, change directory to `SRCH_UTILITY_INSTALL/pscrawler`.
- b. Run this command:

```
crawler.<ext> <elasticsearch host> <elasticsearch port> index =>
<online help URL>
```

For example, on Microsoft Windows:

```
crawler.bat hostname.example.com 9260 index http=>
//hostname.example.com:7001/PeopleBooks/pt857pbr1/eng/pt/index.html
```

For example, on UNIX:

```
./crawler.sh hostname.example.com 9260 index http=>
//hostname.example.com:7001/PeopleBooks/pt857pbr1/eng/pt/index.html
```

22. To enable the search capability on the PeopleSoft Online Help pages, so that when you click the search icon the PeopleSoft Online Help Search Console appears:

- a. Locate the `common.js` file and open it for editing.  
Using the folder structure used in this task as an example, the `common.js` file is located in `C:\PeopleBooks2\<library name>\js`.
- b. Edit the variables `searchURL`, `searchOpt` and `queryTextParamName`.

For example:

```
var searchURL = "/PeopleBooks/psessearch/index.html";
var altHelpURL = "";
var searchOpt = "product=PeopleSoft PeopleTools 8.57";
var queryTextParamName = "query"; //q
```

For more information on using locally installed online help, see *About This Help*. From the PeopleSoft PeopleTools Online Help site, select *About This Help* from the Contents frame. Then select *Managing Locally Installed PeopleSoft Online Help*, *Enabling the Search Button and Field*.

### Task 19-3-3: Removing the PeopleSoft Online Help Deployment

Use this procedure if you need to remove the deployed PeopleSoft Online Help to redeploy or upgrade. You must first remove the deployment from the Oracle WebLogic administration console, and then remove the index in the search crawler.

1. If the PeopleSoft Online Help or the search console are open, close them.
2. Log in to the Oracle WebLogic administration console using Oracle WebLogic administrator credentials.
3. Select Deployments from the Domain Structure section on the left side of the window:

4. Select the check box beside the PeopleBooks deployment, and click Delete.

The screenshot shows the Oracle WebLogic Server Administration Console 12c. The browser address bar displays `http://server.example.com`. The page title is "Summary of Deployments - ...". The console header includes "ORACLE WebLogic Server Administration Console 12c" and navigation links: Home, Log Out, Preferences, Record, and Help. A search bar is also present. The user is logged in as "weblogic" and connected to the "base\_domain".

On the left, the "Change Center" section indicates that configuration editing is enabled. Below it, the "Domain Structure" tree shows the following hierarchy:

- base\_domain
  - Domain Partitions
  - Environment
  - Deployments**
  - Services
  - Security Realms
  - Interoperability
  - Diagnostics

The "How do I..." and "System Status" sections are also visible on the left.

The main content area is titled "Summary of Deployments" and has tabs for Configuration, Control, and Monitoring. The Configuration tab is active. It contains the following text:

This page displays the list of Java EE applications and standalone application modules installed to this domain.

You can update (redeploy) or delete installed applications and modules from the domain by selecting the checkbox next to the application name and then using the controls on this page.

To install a new application or module for deployment to targets in this domain, click **Install**.

Below this text is a "Customize this table" link and a "Deployments" section. The Deployments section includes "Install", "Update", and "Delete" buttons. A table lists the installed applications:


<input checked="" type="checkbox"/>	Name	State	Health	Type	Targets	Scope	Domain Partitions	Deployment Order
<input checked="" type="checkbox"/>	PeopleBooks	Active	OK	Web Application	AdminServer	Global		100

Below the table are "Install", "Update", and "Delete" buttons. The table pagination shows "Showing 1 to 1 of 1" with "Previous" and "Next" links.

At the bottom of the console, the version information is displayed: "WebLogic Server Version: 12.2.1.0.0. Copyright (c) 1996, 2015, Oracle and/or its affiliates. All rights reserved. Oracle is a registered trademark of Oracle Corporation and/or its affiliates. Other names may be trademarks of their respective owners."

Summary of Deployment page with PeopleBooks deployment selected

5. Wait until you see messages saying the deployment was removed.  
Verify that PeopleBooks does not appear in the Deployments section.



Summary of Deployments page after PeopleBooks deployment was removed

6. Log out of the Oracle WebLogic administration console.
7. Open a command prompt and change directory to the location where the search utility was installed; for example:  

```
cd SRCH_UTILITY_HOME\pscrawler
```
8. Run this command to remove the search index:  

```
crawler.bat <elasticsearch host> <elasticsearch port> delete <product>
```

Enter the fully qualified machine name for *<elasticsearch host>*, the search engine port for *<elasticsearch port>*, and the PeopleSoft product name for *<product>*. For example:  

```
crawler.bat server.example.com 9260 delete "PeopleSoft PeopleTools 8.57"
```
9. Wait until the process is complete, as indicated by "Deletion completed"  

```
SUCCESS: Specified value was saved.
Checking for running Elasticsearch instance
Starting deletion of product-PeopleSoft PeopleTools 8.57
Deletion completed
```

## Task 19-3-4: Setting Up Help for Multiple Product Lines on the Same Machine

Use these steps if you want to deploy multiple product line online help sites, such as PeopleSoft PeopleTools and Financials/Supply Chain Management (FSCM) on a single server.

This section assumes that you have set up a web server and the search utility as previously mentioned.

1. Extract the contents of the documentation library zip file for product line 1 (for example, pt857pbr1.zip) to the web server folder where the pssesearch folder resides, for example, C:\PeopleBooks.
2. Extract the contents of the documentation library zip file for product line 2 (for example, fscm92pbr30.zip) to the same folder where the product line 1 was extracted.
3. Repeat step 2 for other product lines as needed. The contents of the Web server folder includes these folders (plus others depending upon your web server):

```
C:\PeopleBooks\fscm92pbr30
C:\PeopleBooks\pssesearch
C:\PeopleBooks\pt857pbr1
```

4. Open a command prompt and change directory to the location where the search utility was installed; for example:

Microsoft Windows

```
cd SRCH_UTILITY_HOME\pscrawler
```

UNIX

```
cd SRCH_UTILITY_HOME/pscrawler
```

5. Run this command for each product line:

```
crawler.<ext> <elasticsearch host> <elasticsearch port> index <online>
help URL>
```

For example, to crawl FSCM and PT on Microsoft Windows:

```
crawler.bat server.example.com 9260 index http://server.example.com⇒
/PeopleBooks/pt857pbr1/eng/pt/index.html
crawler.bat server.example.com 9260 index http://server.example.com⇒
/PeopleBooks/fscm92pbr30/eng/fscm/index.html
```

- Use .bat for <ext> on Microsoft Windows, and .sh on UNIX.
- Enter the fully qualified machine name for the online help web server <elasticsearch host>
- Enter the search engine port for <elasticsearch port>.
- The <online help URL> is the URL used to view the documentation home page.

6. Locate the common.js file and open it for editing.

Using the folder structure used in this task as an example, the common.js file is located in C:\PeopleBooks\<library name>\js.

7. For all product lines, edit the variables searchURL, searchOpt and queryTextParamName.

For example, for product line 1, pt857pbr1:

```
var searchURL = "/PeopleBooks/pssesearch/index.html"; // "http://host:⇒
```

```
port/search/query";
var altHelpURL = ""; //"http://www.oracle.com/pls/topic/lookup?id=>
%CONTEXT_ID%&ctx=fscm92pbr30"
 //"http://host/path/help.html?ContextID=%CONTEXT_>
ID%&LangCD=%Lang%
var searchOpt = "product=PeopleSoft PeopleTools 8.57";
var queryTextParamName = "query";
```

For product line 2, fscm92pbr30:

```
var searchURL = "/PeopleBooks/psessesearch/index.html"; //"http://host:>
port/search/query";
var altHelpURL = ""; //"http://www.oracle.com/pls/topic/lookup?id=>
%CONTEXT_ID%&ctx=fscm92pbr30"
 //"http://host/path/help.html?ContextID=%CONTEXT_>
ID%&LangCD=%Lang%
var searchOpt = "product=PeopleSoft Financials and Supply Chain=>
Management 9.2";
var queryTextParamName = "query";
```



## Chapter 20

# Installing Software for PS/nVision Drilldowns

This chapter discusses:

- Understanding PS/nVision DrillDown Add-ins
- Installing the DrillToPIA Add-In
- Installing the nVisionDrill Add-In
- Installing the nVisionDrill Add-Ins for Multi-Language Installations
- Setting Up PeopleSoft Integration Broker for Using Web Service Capability with nVisionDrill Add-in

## Understanding PS/nVision DrillDown Add-ins

---

When you use PS/nVision to view reports, you can use the DrillDown feature to select a cell in your report and expand it according to criteria contained in a special DrillDown layout.

See *PeopleTools: PS/nVision*, "Using DrillDown."

To use the PS/nVision DrillDown feature with Microsoft Excel reports, you need to install one of the following add-ins, as described in this chapter:

---

**Note.** DrillToPIA and nVisionDrill VSTO add-ins do not coexist. You can use only one add-in at a time.

---

- DrillToPIA add-in
- nVisionDrill VSTO add-in (Visual Studio tools for Microsoft Office SE Runtime).

See *PeopleTools: PS/nVision*, "Understanding PS/nVision Reporting on the Web."

Here is the way the two drilldown add-ins work with the supported version of Microsoft Excel:

If the nVisionDrill VSTO add-in was installed, the nVisionDrill add-in runs and the nVisionDrill VSTO drilldown menu is available when Microsoft Excel opens.

Optionally, you can disable the nVisionDrill VSTO add-in and run the DrillToPIA add-in.

---

**Note.** To disable the nVisionDrill VSTO add-in and use the DrillToPIA add-in, access the Add-Ins dialog box and select the DrillToPIA check box. This selection replaces the nVisionDrill VSTO add-in with the DrillToPIA add-in, and the DrillToPIA drilldown menu appears until you reinstall the nVisionDrill VSTO add-in.

To reinstall the nVisionDrill VSTO, double-click the setup.exe file and select the Repair option.

---

## Task 20-1: Installing the DrillToPIA Add-In

---

This section discusses:

- Understanding Drilldown with DrillToPIA Add-in
- Installing the DrillToPIA Add-in on the Microsoft Excel Environment

### Understanding Drilldown with DrillToPIA Add-in

DrillDowns are run on the PS/nVision report server – like Report Requests and Report Books – and are accessible through Report Manager. You can also select to run the DrillDown using the output type of *Window*, which automatically delivers the results to a new browser window. A copy of the results will also be accessible through Report Manager.

You can drill down on individual cells within the report by selecting the cell and using Drill from the nVisionDrill menu for a Microsoft Excel report.

---

**Note.** A drilldown result report inherits the output format of its parent report. So, if the parent instance is in Excel format, then the drilldown result is in Excel format.

---

DrillDown in a web browser does not include the AutoDrill, Drill-to-Query, and Drill-to-Panel options.

### Task 20-1-1: Installing the DrillToPIA Add-in on the Microsoft Excel Environment

To drill down on Microsoft Excel reports, the Microsoft Visual Basic Application (VBA) add-in DrillToPIA.xla file needs to be installed on the Microsoft Excel environment. This file is stored in the *PS\_HOME*\Excel directory on the Application Server. Your System Administrator needs to distribute a copy of this file to all users who need to drill down on Microsoft Excel reports on the Web.

---

**Note.** If a non-English version of Microsoft Excel is used, translated versions of DrillToPIA.xla can be found in the *<PS\_HOME>\Excel\<Language>* directory on the Application Server.

---

In Apple Macintosh systems, PS/nVision DrillToPIA add-in launches Microsoft Internet Explorer for the drilldown page when drilling is performed on a Microsoft Excel report, regardless of the browser from which the original report is opened.

To install the add-in DrillToPIA.xla file into the Microsoft Excel environment:

1. Copy the *PS\_HOME*\Excel\DrillToPIA.xla file, and paste it into the Excel add-in directory.  
If Microsoft Office is installed in the directory *MS\_OFFICE*, the Excel add-ins directory is *MS\_OFFICE*\Office\Library.
2. Launch Microsoft Excel and select Tools, Add-ins from Excel toolbar.
3. Select the DrillToPIA option in the Add-ins dialog box.  
The nVisionDrill menu appears in the Excel menu bar.

---

**Note.** To remove the add-in from the Excel menu, clear the DrillToPIA option from the Add-Ins dialog box.

---



## Task 20-2: Installing the nVisionDrill Add-In

---

This section discusses:

- Understanding PS/nVision DrillDown Using Web Services
- Understanding Security for DrillDown Using nVisionDrill VSTO Add-in
- Installing the nVisionDrill Add-in for Microsoft Excel

### Understanding PS/nVision DrillDown Using Web Services

For PeopleSoft PeopleTools 8.50 and later releases, you are able to use the web service capability when drilling from summarized to detailed PS/nVision reports using the nVisionDrill VSTO add-in.

PeopleSoft PeopleTools supports 64-bit Microsoft Excel 2010 and Excel 2013 for the nVisionDrill VSTO add-in.

---

**Note.** During the installation for the nVisionDrill VSTO add-in, if there is a message that pre-requisites are not found, run PIARedist.exe and vstor\_redist.exe available in the *PS\_HOME\setup\nVisionDrill* folder.

---

In addition, take note of the following requirements:

- You must set up and configure Integration Broker to use the nVision Drilldown feature as a web service. See Setting Up Integration Broker for Using Web Service Capability with nVisionDrill Add-in.

- The web servers should be SSL enabled.

This is because all the web service calls happen through secure channels.

When you create the SSL-enabled web server domain, you need to provide the optional parameter Authentication Token Domain with the appropriate domain name.

---

**Note.** The new nVisionDrill VSTO add-in is mainly designed for remote standalone file drilldown (where the end user doesn't have access to the PeopleSoft Pure Internet Architecture system). For all other purposes and Web drilldown, the nVision users are still encouraged to use the DrillToPIA add-in.

---

### Understanding Security for DrillDown Using nVisionDrill VSTO Add-in

The nVisionDrill VSTO Add-in allows users to perform drilldown without having to access the PeopleSoft Pure Internet Architecture pages. This necessitates that the end users of nVisionDrill must sign in to the PeopleSoft system to be able to submit the drilldown process and access the subreports. The users of nVisionDrill VSTO add-in will be prompted to enter a user ID and password for the first time. This user ID and password are validated. If the users have access, they are taken to the menu with the list of DrillDown layouts for further drilldown operation.

When the users attempt another drilldown using the same parent report instance which is already open, the system does not prompt for the credentials, and the credentials of the first login are re-used. But for each new report instance or new drilldown report instance, the credentials must be entered again.

---

**Note.** All web service calls between the Microsoft Excel and PeopleSoft applications are SSL-enabled.

---

### Task 20-2-1: Installing the nVisionDrill Add-in for Microsoft Excel

To install the nVisionDrill VSTO add-in for Microsoft Excel:

1. Go to *PS\_HOME\setup\nVisionDrill*.
2. Run the *nVisionDrillSetup.msi* file.

If all required software items have been installed, the nVisionDrill add-in installation will run to success.

During the installation, if you see a message that pre-requisites are not found, run *PIARedist.exe* and *vstor\_redist.exe* available in the *PS\_HOME\setup\nVisionDrill* folder.

3. Ensure that the web server domain's SSL Root certificate is installed on the machine where the nVisionDrill VSTO add-in is installed.

The Root Certificate should be installed correctly on the default browser of the machine. For example, on Microsoft Internet Explorer 8 the SSL Root Certificate should be installed under Trusted Root Certification Authorities.

## **Task 20-3: Installing the nVisionDrill Add-Ins for Multi-Language Installations**

---

If you have a multi-language installation, first install *NVisionDrillSetup.msi* for English, as described above, and then install the *NVisionDrillSetup\_xxx.msi* for the desired languages, where the extension *xxx* is the three-letter language code.

See *PeopleTools: Global Technology*.

## **Task 20-4: Setting Up PeopleSoft Integration Broker for Using Web Service Capability with nVisionDrill Add-in**

---

To set up Integration Broker for using web service capability with PS/nVision DrillDown:

1. Select PeopleTools, Integration Broker, Configuration, Gateways.
2. Select the Integration Gateway ID for which the Local Gateway is enabled from the search results.  
An enabled Local Gateway is marked as "Y" in the search results.

3. In the URL field, enter the following value, where <machine\_name> is the Web server machine name, including the domain name, and <port> is the HTTP port number of the PeopleSoft web server:

`http://<machine_name>:<port>/PSIGW/PeopleSoftListeningConnector`

This example shows the Integration Broker Gateways page with the URL

`http://webs07.dom1.com:8000/PSIGW/PeopleSoftListeningConnector`, where webs07.dom1.com is the combined machine name and domain name, and 8000 is the HTTP port:

**Gateways**

Gateway ID: LOCAL [Inbound Gateways](#)

☒ Local Gateway ☐ Load Balancer

URL:

[Gateway Setup Properties](#)

Connectors				Personalize   Find       First 1-9 of 9 Last	
	*Connector ID	Description	*Connector Class Name	Properties	
1	AS2TARGET		AS2TargetConnector	<a href="#">Properties</a>	
2	FILEOUTPUT		SimpleFileTargetConnector	<a href="#">Properties</a>	
3	FTPTARGET		FTPTargetConnector	<a href="#">Properties</a>	
4	GETMAILTARGET		GetMailTargetConnector	<a href="#">Properties</a>	
5	HTTPTARGET		HttpTargetConnector	<a href="#">Properties</a>	
6	JMSTARGET		JMSTargetConnector	<a href="#">Properties</a>	
7	PSFT81TARGET		ApplicationMessagingTargetConnector	<a href="#">Properties</a>	
8	PSFTTARGET		PeopleSoftTargetConnector	<a href="#">Properties</a>	
9	SMTPTARGET		SMTPTargetConnector	<a href="#">Properties</a>	

Integration Broker Gateways page

4. Click Ping Gateway.

A message appears saying "Gateway URL has changed. Existing connector information will be cleared". Click OK on this message.

You should see a message with the status ACTIVE, indicating a successful connection. Close this message.

5. On the Gateways page, click the Load Gateway Connectors button to load the list of connectors, and then click Save.

If the ping is unsuccessful, check the Web server URL entered, and also make sure Pub/Sub servers are enabled in the Application Server configuration.

6. Select PeopleTools, Integration Broker, Service Operations Monitor, Administration, Domain Status.
7. Purge the unnecessary domains and enable the required domain.

You should be able to see at least three dispatchers under Dispatcher Status. This is required for running asynchronous requests through Integration Broker.

---

**Note.** PeopleSoft Integration Broker must process all nVision web service requests that are sent from nVisionDrill VSTO add-in, so the Local PeopleSoft Node of PeopleSoft Integration Broker gateway must include at least three dispatchers.

---

8. Select PeopleTools, Integration Broker, Configuration, Gateways.


Select the same Integration Gateway ID that you chose in step 1.

9. On the Gateways page, select the link Gateway Setup Properties.

The Gateways Properties page appears.

10. Enter the Integration Gateway administrator user ID and password.

The default User ID is administrator, as shown in this example. Enter the password that you specified when setting up the PeopleSoft Pure Internet Architecture.



**Gateway Properties**

Sign on to access integrationGateway.properties file.

The default user ID is 'administrator' and the default password is 'password'.

User ID: administrator

Password: ●●●●●●●●

☐ Change Password

OK Cancel

Gateway Properties sign on page

## 11. Add a new node in the PeopleSoft Node Configuration page.

**PeopleSoft Node Configuration**

**URL:** http://webs07.dom1.com:8000/PSIGW/PeopleSoftListeningConnector

**Gateway Default App. Server**

App Server URL: //<machine name>:<jolt port>    User ID: <database user>    Password: .....    Tools Release: <peopletools>    Domain Password: .....    Virtual Server Node:

**PeopleSoft Nodes**    Customize | Find | View All | First 1 of 1 Last

Node Name	App Server URL	User ID	Password	Tools Release	Domain Password	
\$NODENAME	//<machine name>:<jolt port>	<database user>	.....	<peopletools>	.....	Ping Node + -

[Advanced Properties Page](#)

OK    Cancel    Save

PeopleSoft Node Configuration page

Node Name: Enter the name of the active default node.

This example uses \$NODENAME.

To find the active default node, navigate to Integration Broker, Integration Setup, Nodes. Do a search, and choose the node for which the Local Node value is "1" and the Default Local Node value is "Y".

Enter the following values to complete the page:

---

**Note.** The following information can be retrieved by pressing CTRL+J on the PeopleSoft Node Configuration page.

---

- App Server URL: Enter the application server machine name and the Jolt port.
- User ID: Enter PeopleSoft user ID
- Password: Enter the password for the PeopleSoft user ID specified in the User ID field.
- Tools Release: Provide the exact PeopleSoft PeopleTools release that your application server is using.

## 12. Click Save.

## 13. Click Ping Node to be sure the node is accessible, and then exit.

See *PeopleTools: Integration Broker Administration*.



## Chapter 21

# Installing the Web Application Deployment Tool

This chapter discusses:

- Prerequisites
- Installing the Web Application Deployment Tool in Silent Mode
- Testing and Troubleshooting the Web Application Deployment

## Prerequisites

---

This chapter includes instructions for installing the Web Application Deployment tool on Oracle WebLogic. Complete the instructions for the web server you selected when you carried out the PeopleSoft PeopleTools installation. Typically, you would choose GUI mode for Microsoft Windows platforms and console mode for UNIX platforms.

---

**Note.** Oracle supports a number of versions of UNIX and Linux in addition to Microsoft Windows for the PeopleSoft installation. Throughout this book, there are references to operating systems. Where necessary, this book refers to specific operating systems by name (for example, Oracle Solaris, IBM AIX, HP-UX Itanium, or Linux); however, for simplicity the word UNIX is often used to refer to all UNIX-like operating systems, including Linux.

---

When you install your PeopleSoft application, consult the product-specific installation guide to determine whether the Web Application Deployment tool is required. If the Web Application Deployment tool is not referenced in the product-specific installation guide, you can skip this chapter.

Before you install the Web Application Deployment tool, confirm that you have completed the following requirements.

If you use Oracle WebLogic as your web server, you must fulfill these requirements:

- Java 8 must be installed and working properly. Your PATH environment variable must include an entry for Java 8 (for example, `<java>/bin`). If you do not install Java 8 the deployment will fail due to the absence of a Java compiler.
- The PeopleSoft web server must be installed during the PeopleSoft PeopleTools installation.
- Oracle WebLogic 12.2.1 must be installed.

## See Also

"Installing Web Server Products"

"Setting Up the PeopleSoft Pure Internet Architecture in GUI Mode"

"Setting Up the PeopleSoft Pure Internet Architecture in Console Mode"

"Using the PeopleSoft Installer"

*PeopleTools: System and Server Administration*

*PeopleSoft Customer Relationship Management Installation*

## Task 21-1: Installing the Web Application Deployment Tool in Silent Mode

---

This section discusses:

- Understanding the Web Application Deployment Tool Silent Mode Installation and the Response File
- Editing the Web Application Deployment Tool Response File to Deploy DES
- Running the Web Application Deployment Tool Silent Mode Installation to Deploy DES

### Understanding the Web Application Deployment Tool Silent Mode Installation and the Response File

You can carry out a silent installation of the Web Application Deployment tool by providing all the required settings in a response file. With silent installation there is no user interaction after the installation begins. Silent mode installation of the Web Application Deployment tool is supported for both Microsoft Windows and UNIX operating systems platforms.

**Note.** Oracle supports a number of versions of UNIX and Linux in addition to Microsoft Windows for the PeopleSoft installation. Throughout this book, there are references to operating systems. Where necessary, this book refers to specific operating systems by name (for example, Oracle Solaris, IBM AIX, HP-UX Itanium, or Linux); however, for simplicity the word UNIX is often used to refer to all UNIX-like operating systems, including Linux.

---

### Task 21-1-1: Editing the Web Application Deployment Tool Response File to Deploy DES

You need a response file to start the installer in silent mode. The Web Application Deployment tool installer comes with a response file template (responsefile.txt) that can be found under `PS_HOME\setup\PsmPWebAppDeployInstall`. Modify the values in the response file according to your installation requirements. The response file should contain all the input parameters that are needed for deploying Web Application Deployment tool. To exclude sections that are not needed, begin the line with a pound sign (#).

The sample response file template includes the following sections:

- Comments and instructions, including the command to run the silent installation.  
See Running the Web Application Deployment Tool Silent Mode Installation to Deploy DES.
- The directory where you want to deploy the web server domain for the Web Application Deployment. The default directory is `PS_CFG_HOME`. You can deploy to any directory on your machine.  
`PS_CFG_HOME=`
- Specify a name for the Web Application Deployment domain, such as `PSWebApp`.  
Use a fully qualified domain name, and do not use an IP address.



---

**Note.** The domain that you create for the Web Application Deployment cannot be the same as any existing PeopleSoft Pure Internet Architecture domains. Be sure you do not enter a name that you used for a PeopleSoft Pure Internet Architecture domain.

---

```
DOMAIN_NAME=PSWebApp
```

- Enter *weblogic* for the web server type, Oracle WebLogic.

```
SERVER_TYPE=weblogic
```

- Specify the root directory where you installed Oracle WebLogic for BEA\_HOME.

On Microsoft Windows, use two back slashes (\\) to specify the path.

```
BEA_HOME=C:\\oracle
```

On UNIX, use a forward slash to specify the path.

```
BEA_HOME=/opt/oracle/bea
```

- The login ID and password for the new web server domain that you are creating.

---

**Note.** The default login ID is system, as shown on this example. The password, which you specified during the PeopleSoft Pure Internet Architecture setup, must be at least 8 alphanumeric characters with at least one number or special character.

---

```
USER_ID=system
```

```
USER_PWD=
```

```
USER_PWD_RETYPE=
```

- Specify HTTP and HTTPS port numbers.

Do not use the same values that you used for the HTTP and HTTPS ports when setting up the PeopleSoft Pure Internet Architecture.

```
HTTP_PORT=8000
```

```
HTTPS_PORT=4430
```

- The domain type and install action values in the sample response file are mandatory.

Do not change these parameters.

```
DES support only NEW_DOMAIN , so please do not change the
below variable.
```

```
DOMAIN_TYPE=NEW_DOMAIN
```

```
DES support only CREATE_NEW_DOMAIN , so please do not change the
below variable.
```

```
INSTALL_ACTION=CREATE_NEW_DOMAIN
```

- Specify one of the following values for the INSTALL\_TYPE parameter.

```
INSTALL_TYPE=singleserver
```

- **Singleserver** (Single Server Domain) — This configuration is intended for single user or very small scale, non-production environments.
- **Multiserver** (Multi-Server Domain) — This configuration is intended for a production environment.
- **Distributedmanagedserver** (Distributed Managed Server) — This option is an extension of the Multi-

Server Domain selection and installs the necessary files to boot a managed server.

This option requires a Multi Server installation to be performed to some other location, which will contain the configuration for this managed server.

- Specify the *PS\_APP\_HOME* location.

Note that the DPK installation requires that the *PS\_APP\_HOME* location be different from the *PS\_HOME* location; that is, a decoupled *PS\_APP\_HOME*.

```
PS_APP_HOME=
```

- Specify the information about your database.

```
Please enter the CRM specific DB information
```

```
possible values for DB_TYPE are MSSQL,ORACLE,DB2UDB
DB_TYPE=MSSQL
DB_SERVER_NAME=
DB_PORT=1433
DB_SERVER_INSTANCE=
DB_USER=Admin
DB_PASSWORD=
```

- **DB\_TYPE** — The RDBMS type, Microsoft SQL Server (MSSQL), Oracle, or DB2 for Linux, UNIX, and Windows (DB2UDB).
- **DB\_SERVER\_NAME** — the name of the machine that is hosting the database
- **DB\_PORT** — Consult with your database administrator for the correct port number.
- **DB\_SERVER\_INSTANCE** — the database name.
- **DB\_USER** — the user name for the database
- **DB\_PASSWORD** — the password for the database user

## Task 21-1-2: Running the Web Application Deployment Tool Silent Mode Installation to Deploy DES

To install the Web Application Deployment tool in silent mode, use the response file that you modified for your configuration. Substitute the location where you saved the response file for *<path\_to\_response\_file>* in the following procedures:

1. Open *PS\_HOME\setup\PsmPWebAppDeployInstall\responsefile.txt* for editing.
2. Modify the file for your environment, and then save the file.
3. In a command prompt, go to *PS\_HOME\setup\PsmPWebAppDeployInstall*.
4. On Microsoft Windows, run the following command, using "\\" as a separator in the file path:

```
setup.bat -i silent -DRES_FILE_PATH=<path_to_response_file>
```

For example:

```
setup.bat -i silent -DRES_FILE_PATH=C:\\pt857\\setup\\PSMpWebAppDeployInstall\\responsefile.txt
```

5. On UNIX, run the following command, using "/" as a separator in the file path:

```
setup.sh -i silent -DRES_FILE_PATH=<path_to_response_file>
```

For example:

```
setup.sh -i silent -DRES_FILE_PATH=/home/pt857/setup/PsMpWebAppDeploy⇒
Install/responsefile.txt
```

## Task 21-2: Testing and Troubleshooting the Web Application Deployment

---

Check the log file for any problems encountered during installation. The log file is saved in the following location:

`<WebAppDeploy_DIR>/webserv/webappinstall<domain_name>.log`

The *WebAppDeploy\_DIR* is the directory where the web server domain for the Web Application Deployment was installed. The *<domain\_name>* is the name you specified for the Web Application Deployment web server domain, such as PSWebApp.

If you need to start or stop Oracle WebLogic, use the commands given in the chapter on installing the PeopleSoft Pure Internet Architecture.

See Testing the PeopleSoft Pure Internet Architecture Installation in the chapters on setting up the PeopleSoft Pure Internet Architecture.



## Appendix A

# Describing Debugger Requirements

This appendix discusses:

- Describing Debugger Requirements for the AIX Operating System
- Describing Debugger Requirements for the HP-UX Operating System
- Describing Debugger Requirements for the Linux Operating System
- Describing Debugger Requirements for the Oracle Solaris Operating System
- Describing Debugger Requirements for the z/OS Operating System

## Describing Debugger Requirements for the AIX Operating System

If you are installing on an AIX platform, download and install the latest gdb RPM from IBM's website, and install it.

## Describing Debugger Requirements for the HP-UX Operating System

If you are installing on an HP-UX platform, download and install the latest wdb from <http://www.hp.com/go/wdb>.

## Describing Debugger Requirements for the Linux Operating System

If you are installing on a Linux platform, install the "glibc-debuginfo" RPM package.

There should be one "glibc-debuginfo" package for each installed "glibc" package and the version numbers must match exactly. Use the following commands to determine the packages installed:

- To see the installed "glibc" versions, run:

```
rpm -q --queryformat "%{NAME}-%{VERSION}-%{RELEASE}-%{ARCH}\n" glibc
```

For example, running this command on an Intel-based Linux system should produce output similar to this:

```
glibc-2.5-24-i686
glibc-2.5-24-x86_64
```

Running this command on a zSeries Linux system should produce output similar to this:

```
glibc-2.4-31.2-s390x
```

- To see the installed "glibc-debuginfo" packages, run:

```
rpm -q --queryformat "%{NAME}-%{VERSION}-%{RELEASE}-%{ARCH}\n" glibc-
debuginfo
```

Make sure that the "glibc-debuginfo" RPM version is exactly the same as the "glibc" version.

## Describing Debugger Requirements for the Oracle Solaris Operating System

---

If you are installing on an Oracle Solaris platform, install dbx. No compiler license of any kind is needed for this. Download the latest Sun Studio, and on the Select Components page of the installer, expand the Compilers and Tools component and deselect all of the subcomponents except dbx. Also deselect the Performance Library and Third-Party Tools components. The installer will install the dbx subcomponent and the Support files subcomponent. The Support files subcomponent includes packages on which dbx depends. After you complete the installation, add the full path to dbx to your PATH environment variable.

## Describing Debugger Requirements for the z/OS Operating System

---

If you are installing on a z/OS platform, dbx comes with z/OS UNIX. Starting with z/OS v1r5, dbx requires the Common Debug Architecture (CDA) libraries to be present. They must be accessible by dbx in order for it to run. The libraries are as follows:

Library	Description
CDAEED	Amode31 ELF/DWARF library
CDAEQED	Amode64 ELF/DWARF library
CDAEDPI	Amode31 DDPI library
CDAEQDPI	Amode64 DDPI library

---

**Note.** CDAEDPI and CDAEQDPI are only present on a z/OS v1r7 and higher systems.

---

Depending on the size of the program you are debugging with dbx, plus how many others are also using dbx on your system, you may run out of SQA and/or CSA storage on your z/OS system, because this storage is global z/OS storage. Consult the z/OS initialization and tuning guide for information on how to modify the z/OS parameters.

When diagnosing crashes, be aware that a crash is more strictly defined on z/OS as a program check that is handled by z/OS UNIX as a fatal signal (for example, SIGSEGV for PIC4; 10, 11, or SIGILL for PIC1). A crash would also occur because of a fault in the JVM, or because of a fault in native (JNI) code that is being run inside the Java process.

When one of these fatal signals occurs, obtain the following documents to help you debug:

- a formatted LE dump (CEEDUMP)

The CEEDUMP shows the C-Stack (or native stack). The traceback from a CEEDUMP shows where a failure

occurred for a C/C++ program

- a JVM trace snap dump
- a formatted JVM dump (javacore)

The default action of the z/OS UNIX signal handler is to produce a transaction dump (through the BCP IEATDUMP service), CEEDUMP, JVM dump javacore.





## Appendix B

# Encrypting Passwords for Customizations on Linux, AIX, HP-UX, or Solaris

## Task B-1: Encrypting Passwords for Customization Files on Linux, AIX, HP-UX, or Solaris

---

This section describes how to produce an encrypted version of a clear text password and include it in the `psft_customizations.yaml` file for a customized deployment for non-default users and groups on Linux, AIX, HP-UX, or Solaris. This section applies to installations with the Native OS for Linux, AIX, HP-UX, or Solaris DPKs.

In general, when you run the DPK setup script, you supply several user IDs and passwords, such as the Connect ID password and operator ID password. The script encrypts the passwords that you supply and includes them in the generated YAML files in `BASE_DIR/dpk/puppet/production/data`. When you create a `psft_customizations.yaml` file, you can copy these encrypted passwords from the generated YAML files and include them in the `psft_customizations.yaml` file. However, the passwords for the Linux, AIX, HP-UX, or Solaris users are not prompted for, and therefore the encrypted passwords are not available in any of the generated YAML files.

Note that the successful use of the encrypted password depends on the presence of the public and private keys in the `BASE_DIR/dpk/puppet` directory referred to in the `eyaml encrypt` command. You cannot save an encrypted password and use it with a deployment with an installation with a different `BASE_DIR`.

This procedure assumes that you have carried out the first portion of a customized deployment, and stopped at the question "Do you want to continue with the default initialization?"

See "Completing the DPK Initialization with Customizations," Preparing the Customization Files for Linux, AIX, HP-UX, or Solaris Users and Groups.

To encrypt a password:

1. Open the `BASE_DIR/dpk/puppet/hiera.yaml` file and note the full path to the public and private keys:

```
:pkcs7_private_key: BASE_DIR/dpk/puppet/secure/keys/private_⇒
key.pkcs7.pem
:pkcs7_public_key: BASE_DIR/dpk/puppet/secure/keys/public_key.pkcs7.pem
```

2. Run the following command in a terminal window, supplying the paths from the previous step:

```
eyaml encrypt -s "<clear_password>" --pkcs7-private-key=<private_key_⇒
location> --pkcs7-public-key=<public_key_location> --output=string
```

---

**Note.** The double-quotes around the password are required. Be sure to use the correct punctuation for the command. Note that the command uses different punctuation for the keys than the `hiera.yaml` file.

---

Example for Linux:

```
/opt/puppetlabs/puppet/bin/eyaml encrypt -s "password" --pkcs7-private-key=/cs1/psft/dpk/puppet/secure/keys/private_key.pkcs7.pem --pkcs7-public-key=/cs1/psft/dpk/puppet/secure/keys/public_key.pkcs7.pem --output=string
```

Example for AIX, HP-UX, or Solaris:

```
/opt/oracle/puppetlabs/bin/eyaml encrypt -s "password" --pkcs7-private-key=/cs1/psft/dpk/puppet/secure/keys/private_key.pkcs7.pem --pkcs7-public-key=/cs1/psft/dpk/puppet/secure/keys/public_key.pkcs7.pem --output=string
```

3. Copy the encrypted password from the output in the terminal window.

The encrypted text will be a long single line of letters and numbers. Be sure to copy the text in one unbroken line, with no spaces or line feeds. Here is a truncated representation of an encrypted password:

```
ENC[PKCS7,MIIBeQYJKoZIhvc.....]
```

4. Paste the encrypted password in the `psft_customizations.yaml` file, replacing the text `password`.

Again, the encrypted text must be a single line. Also, be sure to retain the indentation in the `psft_customizations.yaml` file. This is a sample `psft_customizations.yaml` for a new single user and existing single group:

```

psft_runtime_user_name: newusr3

users:
 psft_user:
 name: newusr3
 gid: 35000
 home_dir: /dpk_base/home/userhome
 password: ENC[PKCS7,MIIBeQYJKoZIhvc.....]
 remove: false
```

5. Use the `psft_customizations.yaml` file for deployment with the puppet apply command.

The DPK deployment will automatically decrypt the password from the `psft_customizations.yaml` and use it for deployment.

## Appendix C

# Installing IBM ILOG CPLEX

This appendix discusses:

- Understanding the ILOG CPLEX Installation
- Obtaining ILOG CPLEX
- Running the ILOG CPLEX Installation Script

## Understanding the ILOG CPLEX Installation

---

PeopleSoft PeopleTools Optimization Framework uses IBM ILOG CPLEX to expose and provide optimization features for PeopleSoft Applications. For the current release, you must download the ILOG CPLEX zip file from My Oracle Support and install it using the script provided.

ILOG CPLEX is needed for certain PeopleSoft products, including PeopleSoft Financials and Supply Chain Management (FSCM) Enterprise Service Automation and Supply Chain Management. For information, see your application-specific documentation.

## Task C-1: Obtaining ILOG CPLEX

---

This section discusses:

- Obtaining ILOG CPLEX from Oracle Software Delivery Cloud
- Obtaining ILOG CPLEX from My Oracle Support

### Task C-1-1: Obtaining ILOG CPLEX from Oracle Software Delivery Cloud

To download ILOG CPLEX for PeopleSoft from Oracle Software Delivery Cloud:

1. Sign in to Oracle Software Delivery Cloud at <https://edelivery.oracle.com>.
2. Enter PeopleSoft PeopleTools in the Search By field, and locate the download package for the current release.
3. Click Add to Cart.
4. Click Selected Software.
5. Locate ILOG CPLEX 12.7.1 in the selected software list.
6. Select the operating system you are running on from the Platform/Languages drop-down list, and click Continue.
7. Read the license agreements, select the check box to acknowledge that you accept the agreement, and then click Continue.
8. Download the zip file, for example ILOG-CPLEX-12.7.1\_00.zip, to a convenient location, referred to here as

*ILOG\_INSTALL.*

## Task C-1-2: Obtaining ILOG CPLEX from My Oracle Support

To download ILOG CPLEX for PeopleSoft from My Oracle Support:

1. Sign in to My Oracle Support at <https://support.oracle.com>.  
Contact Oracle if you need a user ID and password for My Oracle Support.
2. Select the Patches & Updates tab.
3. Select Product or Family (Advanced), and search for PeopleSoft PeopleTools.
4. Select the current release from the Release drop-down list.
5. Click Search.
6. In the list of results, locate the ILOG CPLEX file for your operating system.
7. Download the zip file, for example ILOG-CPLEX-12.7.1\_00.zip, to a convenient location, referred to here as *ILOG\_INSTALL*.

## Task C-2: Running the ILOG CPLEX Installation Script

---

This section assumes that you have installed PeopleSoft PeopleTools and have access to *PS\_HOME*.

1. Change directory to the location where you downloaded the ILOG CPLEX zip file, *ILOG\_INSTALL*.
2. Extract the zip file (for example ILOG-CPLEX-12.7.1\_00.zip) in the same directory.  
The contents extracted from the zip file include setup scripts and an InstData directory.
3. Run the following command, specifying the full path for *PS\_HOME* as the *<ps\_home\_location>*:  
Windows: `setup.bat <ps_home_location>`  
UNIX: `./setup.sh <ps_home_location>`

The installer verifies the following:

- The file `peopletools.properties` is present in *PS\_HOME*.
- The directories *PS\_HOME*\bin\server and *PS\_HOME*\python are present.

The installer copies the ILOG CPLEX .files from *INSTALL\_DIR*\PsMPCplexInstall\InstData\archive\*operating\_sys\_platform* to *PS\_HOME*\bin\server. The source and destination are listed in the installer progress message.

The installation log file, *PIAInstall.log*, is located under the user's home directory.

## Appendix D

# Relinking SQR on UNIX

This appendix discusses:

- Understanding SQR Relinking
- Relinking SQR on UNIX

## Understanding SQR Relinking

---

PeopleSoft SQR is now linked with Unicode libraries and therefore no longer requires relinking with Unicode libraries. PeopleSoft SQR uses dynamic linking for database connectivity libraries and should not require relinking to support new versions of database connectivity. The exception to this rule is if the PeopleSoft PeopleTools release spans multiple RDBMS versions and the database connectivity changes the names or functionality of required libraries in the new release. In addition, relinking may be required for invoking an external application's APIs using the UFUNC.C interface, as described in the PeopleSoft product documentation.

See *PeopleTools: SQR for PeopleSoft Developers*, "Invoking an External Application API by Using the UFUNC.C Interface."

For example, PeopleSoft PeopleTools is currently supported on Oracle 12c. Based on the timing of our release we built the SQR modules for a specific PeopleSoft release with the lowest supported RDBMS version. For the current PeopleSoft PeopleTools release, the minimum supported Oracle version is Oracle 12c (12.1.0.x). This means PeopleSoft SQR will work right out of the box on Oracle 12c (no relink required).

## Task D-1: Relinking SQR on UNIX

---

Here's a high-level overview of what you need to do, on a UNIX platform, to relink SQR:

1. Export the following environment variables:
  - SQRDIR, the location of the SQR executable.
  - PS\_HOME, the PeopleSoft home directory.
  - PS\_DB, the platform identifier variable:  
DBX for DB2 UDB for Linux, UNIX, and Windows

2. Export the database install home directory:

DB2\_HOME

3. Add SQRDIR to the library path.

```
export LD_LIBRARY_PATH=$SQRDIR:$LD_LIBRARY_PATH
```

or

```
export SHLIB_PATH=$SQRDIR:$SHLIB_PATH
```

4. Change directory to `<PS_HOME>/bin/sqr/<PS_DB>/lib`
5. Run `sqrmake`.